DOE/PC/89769-T12
AUG 17 1992

DOE/PC/89769--T12

DE93 000938

12th TECHNICAL PROGRESS REPORT

JULY 1992

Predictive Models of Circulating Fluidized Bed Combustors

U.S. Department of Energy Grant
DE-FG 22-89PC89769

D. Gidaspow, Principal Investigator
Department of Chemical Engineering
Illinois Institute of Technology
Chicago, IL 60616

OCT 07 1992

ABSTRACT

The overall objective of this investigation is to develop experimentally verified models for circulating fluidized bed (CFB) combustors.

During this period two presentations were made by the author summarizing the work performed. The first was at the International Fluidization Conference in Brisbane, Australia. No financial support was used for the travel expenses from DOE, since this trip was not anticipated three years ago and since no money is available. The paper has been published in the proceedings of the conference.

The second presentation was at the June 1992 University of Coal Research Pittsburgh meeting. The project results were summarized in the poster session with an abstract published in the proceedings of the meeting. Similarly, no travel expenses were charged to the grant.

The attached chapter from a book manuscript to be submitted for publication by Academic Press summarizes some of the new work performed as part of this project. The new results are the dimensional scale factors for CFB. The significance of such groups was discussed at last year's presentation in Morgantown and in Brisbane.

MASTER

EP

VISCOUS FLOW AND CIRCULATING FLUIDIZED BEDS

Chapter 8

by

Dimitri Gidaspow

1. Introduction
2. Multiphase Navier-Stokes Equation Model
 - A. Incompressible Flow
 - B. Compressible Flow
3. Dimensional Analysis: Scale Factors
4. CFB or Riser Flow: Experimental
5. Need for Clusters in One-D Modeling
6. Computation of Cluster Flow
7. Computation of Core-Annular Regime
8. Radial Profiles and Turbulence

CHAPTER 8

VISCOUS FLOW AND CIRCULATING FLUIDIZED BEDS

1. INTRODUCTION

In chapter seven, it was shown that inviscid models predicted the formation, the growth and the bursting of bubbles in a reasonable agreement with experiments when a flow pattern was established by means of a jet. In such a case time averaged porosities agreed well with experiments. Transient and time average wall to bed heat transfer coefficients were also computed in rough agreement with data using empirical effective thermal conductivities (Syamlal and Gidaspow, 1985), since the inviscid model gives an approximately correct residence time for particles contacting a wall (Gidaspow, 1986). However, analogous to classical fluid dynamics, inviscid models do not predict the forces acting on the tubes or obstacles immersed in fluidized beds. This can be made clear by using a simple example. Consider steady incompressible laminar boundary layer flow over a flat plate at zero incidence to flow at a constant velocity U_∞ far away from the plate of width b and length L . For a fluid of viscosity μ and density ρ Schlichting (1960) shows that the drag on both sides of the plate is as follows

$$\text{Drag} = 1.328bU_\infty^{3/2}(\mu\rho L)^{1/2} \quad (8-1)$$

Drag, as well as the momentum boundary layer thickness, δ

$$\delta \approx \left(\frac{\mu L}{\rho U_\infty}\right)^{1/2} \quad (8-2)$$

are both proportional to square root of the fluid viscosity. Hence a fluid of zero viscosity will exert no drag on a plate immersed in the fluid. A wall will not cause

the development of a momentum boundary layer. Hence steady flows influenced by walls cannot be described by inviscid models. Flows in circulating fluidized beds have significant wall effects. Particles in the form of clusters or layers can be seen to run down the walls. Hence modeling of circulating fluidized beds (CFB) without a viscosity is not possible. However, in interpreting Equations (8-1) and (8-2) it must be kept in mind that CFB or most other two phase flows are never in a true steady state. Then the viscosity in Equations (8-1) and (8-2) may not be the true fluid viscosity to be discussed next, but an Eddy type viscosity caused by two phase flow oscillations usually referred to as turbulence. In view of the transient nature of two-phase flow, the drag and the boundary layer thickness may not be proportional to the square root of the intrinsic viscosity but depend upon it to a much smaller extent. As another example, liquid-solid flow and settling of colloidal particles in a lamella electrosettler (Gidaspow, et al. 1989 ; Jayaswal, et al 1990) the settling process is only moderately affected by viscosity. Inviscid flow with settling is a good first approximation to this electric field driven process.

The physical meaning of the particulate phase viscosity is described in detail in the chapter on kinetic theory. Here the conventional derivation presented in single phase fluid mechanics is generalized to multiphase flow.

2. MULTIPHASE NAVIER-STOKES MODEL

A generalization of the Navier-Stokes equation to multiphase flow can be obtained in a very simple way. The conservation of mass and momentum for each phase were given by Equations (7-1) and (7-2). For inviscid flow the traction $\bar{T}_k$ was simply the negative of the pressure of phase k. Now consider flow with frictional forces due to differences in velocity. For simplicity, let us first treat incompressible

flow. In multiphase flow this means the bulk density of phase k is constant.

2A. INCOMPRESSIBLE FLOW

In single phase flow the traction $\bar{\bar{T}}$ is a function of the symmetric gradient of the velocity. The driving force for the transfer of shear is the symmetric gradient of velocity rather than the ordinary gradient due to the need to satisfy invariance under a change of frame of reference under rotation, called objectivity in continuum mechanics or the Galileo relativity principle. Similarly there exists a driving force of $\bar{\bar{T}}_k$ due to its gradient of velocity. To meet the requirement of objectivity, let

$$\bar{\bar{T}}_k = T_k(\nabla^s \vec{v}_k) \quad (8-3)$$

Linearization of the T_k gives

$$\bar{\bar{T}}_k = A_k \bar{\bar{I}} + B_k \nabla^s \vec{v}_k \quad (8-4)$$

For incompressible fluids A_k is chosen to be the negative of the pressure of fluid k and the derivative of the traction with respect to the symmetric gradient is the viscosity of fluid k , as shown below,

$$A_k = -P_k \quad (8-5)$$

$$B_k = 2\mu_k = \frac{\partial \bar{\bar{T}}_k}{\partial \nabla^s \vec{v}_k} \quad (8-6)$$

Then using the tensor identity

$$\nabla \nabla^s \vec{v} = \frac{1}{2} \nabla^2 \vec{v} + \frac{1}{2} \nabla \nabla \cdot \vec{v} \quad (8-7)$$

and the assumption of constancy of bulk density

$$\epsilon_k \rho_k = \text{constant} \quad (8-8)$$

$$\nabla \cdot \vec{v}_k = 0 \quad (8-9)$$

the traction for phase k becomes as follows.

$$\vec{T}_k = -P_k \vec{I} + 2\mu_k \nabla^s \vec{v}_k \quad (8-10)$$

Then for a constant phase viscosity, μ_k the incompressible multiphase Navier-Stokes equation becomes as shown below.

$$\begin{aligned} \frac{\partial(\epsilon_k \rho_k \vec{v}_k)}{\partial t} + \nabla \cdot \epsilon_k \rho_k \vec{v}_k \vec{v}_k = \\ \epsilon_k \rho_k \vec{f}_k + \sum_j \beta_j (\vec{v}_j - \vec{v}_k) + \dot{m}_k \vec{v}_k - \nabla P_k + \mu_k \nabla^2 \vec{v}_k \end{aligned} \quad (8-11)$$

Equation (8-11) differs from the single-phase incompressible Navier-Stokes equation principally due to coupling of the momentum balances through drag.

2B. COMPRESSIBLE FLOW

For the more general case of compressible flow with negligible phase change Equation (8-9) is replaced by the rearranged form of Equation (7-1) shown below.

$$\nabla \cdot \vec{v}_k = -\frac{1}{\epsilon_k \rho_k} \frac{d(\epsilon_k \rho_k)}{dt^{(k)}} \quad (8-12)$$

Equation (8-12) states that the divergence of the velocity of phase k is the relative rate of change of bulk density of phase k moving with its own velocity.

Analogously to single phase flow, let

$$A_k = -P_k \bar{I} + \lambda_k \nabla \cdot \vec{v}_k \quad (8-13)$$

to take into account the additional variable. Then the traction becomes

$$\bar{T}_k = -P_k \bar{I} + 2\mu_k \nabla^s \vec{v}_k + \lambda_k \bar{I} \nabla \cdot \vec{v}_k \quad (8-14)$$

Define the phase k pressure to be minus one third of the trace of the traction in the three directions x, y and z, as shown below.

$$-3\bar{P}_k = T_{kxx} + T_{kyy} + T_{kzz} \quad (8-15)$$

Using Cartesian tensor notation and Einstein summation convention Equation (8-14) can be expressed in terms of components of direction lm (Jeffreys, 1961) as

$$\begin{aligned} T_{klm} = & -P_k \delta_{lm} + 2\mu_k \frac{1}{2} \left(\frac{\partial v_{kl}}{\partial x_m} + \frac{\partial v_{km}}{\partial x_l} \right) \\ & + \lambda_k \frac{\partial v_{kl}}{\partial x_l} \delta_{lm} \end{aligned} \quad (8-16)$$

Now perform a tensor contraction, e.i., let $l = m$ and sum over l

$$T_{kxx} + T_{kyy} + T_{kzz} = -3P_k + 2\mu_k \frac{\partial v_{kl}}{\partial x_l} + 3\lambda_k \frac{\partial v_{kl}}{\partial x_l} \quad (8-17)$$

If

$$\bar{P}_k = P_k \quad (8-18)$$

then Equation (8-17) shows that

$$2\mu_k + 3\lambda_k = 0 \quad (8-19)$$

or that the bulk viscosity λ_k is related to the shear viscosity by the simple relation

$$\lambda_k = -\frac{2}{3}\mu_k \quad (8-20)$$

The compressible multiphase Navier-Stokes equation in convective form then becomes as follows.

$$\begin{aligned} \epsilon_k \rho_k \frac{dv_k}{dt} &= \epsilon_k \rho_k \tilde{f}_k + \sum_j \beta_j (\tilde{v}_j - \tilde{v}_k) - \nabla P_k \\ &+ \nabla (2\mu_k \nabla^s \tilde{v}_k - \frac{2}{3}\mu_k \bar{I} \nabla \cdot \tilde{v}_k) \end{aligned} \quad (8-21)$$

Although the stress in Equation (8-3) can be taken to depend upon other variables in addition to the velocity and the compressibility (Drew and Lahey, 1979), the kinetic theory justifies the phenomenological approach presented above.

DIMENSIONAL ANALYSIS: SCALE FACTORS

The multi-fluid model derived in this chapter can be used to establish the basic dimensionless groups that govern such flows, as is conventionally done for single phase flow (Schlichting 1960, Bird, et al. 1960). These dimensionless groups called scale factors, may be useful in design and scale-up and for correlation of experimental data. In fluidization Fitzgerald (1985), Blake, et al. (1990) and others have successfully used such an approach. The analysis presented below is an extension of the work of Glickman (1984). He used the inviscid, incompressible form of the equations discussed below. Here the assumption of incompressibility will be lifted and the solids pressure caused by particle collisions which gives rise to the modulus G will be retained. However, as is common in compressible single-phase flow, the

compressibility effect in the multi-phase Navier-Stokes equation will be considered to be negligible.

Then the well-posed model B momentum balances for the fluid and for the solid are as follows.

DISPERSED SOLIDS MOMENTUM BALANCE

$$\begin{aligned} \epsilon_s \rho_s \left(\frac{\partial \vec{v}_s}{\partial t} + \vec{v}_s \cdot \nabla \vec{v}_s \right) = & \beta_B (\vec{v}_g - \vec{v}_s) - G \nabla \epsilon_s \\ & + (\rho_s - \rho_g) \epsilon_s \vec{g} + \mu_s \nabla^2 \vec{v}_s \end{aligned} \quad (8-22)$$

where $G = \left(\frac{\partial P_s}{\partial \epsilon_s} \right)$

CONTINUOUS FLUID MOMENTUM BALANCE

$$\epsilon \rho_f \left(\frac{\partial \vec{v}_f}{\partial t} + \vec{v}_f \cdot \nabla \vec{v}_f \right) = \beta_B (\vec{v}_s - \vec{v}_g) - \nabla P + \rho_g \vec{g} + \mu_f \nabla^2 \vec{v}_f \quad (8-23)$$

Let us choose the same characteristic length and velocity used by Glickman (1984). In fluidization the inlet velocity U_o is a good reference velocity. When wall effects are neglected, the particle diameter, d_p is the only invariant reference for length. The reference pressure is P_o and the inlet gas density is ρ_{go} . Then as in Bird, et al. (1960), let

$$\bar{\vec{v}}_k = \frac{\vec{v}_k}{U_o}, k = f, s; \quad \bar{P} = \frac{P - P_o}{\rho_{go} U_o^2} \quad (8-24, 25)$$

$$\bar{t} = \frac{t U_o}{d_p}; \quad \bar{x}_i = \frac{x_i}{d_p}, \quad i = 1, 2, 3 \quad (8-25, 26)$$

$$\bar{\nabla} = \frac{\nabla}{d_p}; \quad \bar{\nabla}^2 = \frac{1}{d_p^2} \nabla^2 \quad (8-26, 27)$$

In terms of the dimensionless variables, the momentum balances become as follows.

DIMENSIONLESS SOLIDS MOMENTUM

$$\begin{aligned} \epsilon_s \frac{d\bar{\vec{v}}_s}{d\bar{t}^s} = & \left(\frac{\beta_B d_P}{\rho_s U_o} \right) (\bar{\vec{v}}_g - \bar{\vec{v}}_s) + \left(\frac{G}{\rho_s U_o^2} \right) \nabla \epsilon \\ & + \left(\frac{\Delta \rho \epsilon_s \bar{g} d_p}{\rho_s U_o^2} \right) + \frac{\mu_f}{\rho_f U_o d_P} \left(\frac{\rho_f}{\rho_s} \right) \left(\frac{\mu_s}{\mu_f} \right) \nabla^2 \bar{\vec{v}}_s \end{aligned} \quad (8-28)$$

In the dimensionless solids momentum balance a group involving a particle Reynolds number was formed. The drag group is one used by Glickman (1984).

DIMENSIONLESS FLUID MOMENTUM

$$\begin{aligned} \epsilon \frac{d\bar{\vec{v}}_f}{d\bar{t}^f} = & \left(\frac{\rho_s}{\rho_f} \right) \left(\frac{\beta_B d_P}{\rho_s U_o} \right) (\bar{\vec{v}}_s - \bar{\vec{v}}_g) - \nabla \bar{P} \\ & + \left(\frac{g d_p}{U_o^2} \right) + \left(\frac{\mu_f}{\rho_f U_o d_p} \right) \nabla^2 \bar{\vec{v}}_f \end{aligned} \quad (8-29)$$

The fluid momentum balance differs from the single-phase momentum balance only due to the presence of a drag group and the porosity multiplying the fluid acceleration.

The common groups are the fluid Reynolds number and the Froude number.

In single-phase compressible fluid flow the Mach number is the dimensionless group that measures the extent of compressibility. With the pressure scaled as it is given by Equation (8-25), the Mach number is obtained from the continuity equation which in terms of the dimensionless flux $\bar{F} = \rho \vec{v} / \rho_{fo} U_o$ can be written as

$$\bar{\nabla} \bar{F} + M^2 \frac{\partial \bar{P}}{\partial \bar{t}} = 0 \quad (8-30)$$

where

$$M = \left(\frac{U_o}{C} \right) = \text{Mach number} \quad (8-31)$$

with the sonic velocity C defined as

$$C = \left(\frac{\partial P}{\partial \rho} \right)^{\frac{1}{2}} \quad (8-32)$$

Equation (8-30) gives a measure of how fast the convective terms in the momentum equation change with time. It also provides a more natural scale for time than is given by Equation (8-25). Equation (8-30) suggests that for a constant sonic velocity a more natural scale for time is obtained by incorporating M into time, as follows.

$$\hat{t} = \bar{t}/M^2 = \left(\frac{tc}{d_p} \right) \left(\frac{c}{U} \right) \quad (8-33)$$

The grouping (8-33) and the wave equation which is obtained by combining (8-30) with the inviscid fluid momentum balance, as done in Chapter 7, and an order of magnitude analysis

$$\text{order } (tc/d) = 1 \quad (8-34)$$

strongly suggest the relation

$$C = \text{frequency} \cdot \text{length} \quad (8-35)$$

where frequency is $1/t$. Equation (8-35) states that for a unit length, the frequency of oscillation is high for a high sonic velocity. Gas oscillations in turbulent flow are known to be of the order of 300 Hertz and larger. A similar analysis performed for granular flow in Chapter 7 shows that the granular flux or the bulk density satisfy a wave equation with C equal to $(G/\rho_s)^{1/2}$. See Equation (7-15) and (7-16). Since hopper flow experiments show that the critical flux or the granular "sound velocity" is of the order of one meter per second, for a length of one meter the characteristic frequency should be one Hertz. Indeed most bubbling beds have a dominant frequency of oscillation of about one Hertz.

This granular sonic group already appeared in Equation (8-28), since the solids pressure in Equation (8-22) was assumed to be a function of the solids volume fraction, as suggested by kinetic theory of granular flow and experiments. The fluid pressure in Equation (8-23) was, however, treated as an independent variable. To bring in the sonic velocity into the momentum balance it could have been taken as a function of density and the Mach number then defined. The alternate way is to bring in the Mach number using the approach illustrated for single-phase flow in Equation (8-30).

For two phase flow with incompressible solid grains, the solids continuity equation provides no additional scaling factors. The gas continuity equation alone has a troublesome porosity variation with time. Only the sum of the two continuity equations give the well-known mixture sonic velocity already discussed in Chapter 7. In terms of the mixture density ρ_m and the sum of the fluid and solid fluxes the mixture continuity equation is

$$\frac{\partial \rho_m}{\partial t} + \nabla F_m = 0 \quad (8-36)$$

where

$$F_m = \epsilon_f \rho_f v_f + \epsilon_s \rho_s v_s \quad (8-37)$$

In terms of the mixture sound velocity, C_m defined by Equation (7-41), the mixture continuity equation in dimensionless form becomes as follows.

$$\bar{\nabla} \bar{F}_m + \left(\frac{U_o}{C_m} \right)^2 \frac{\partial \bar{P}}{\partial \bar{t}} = 0 \quad (8-38)$$

Roy et al (1990) measured C_m in fluidized beds.

The dimensionless groups that appeared is scaling the solid and the fluid momentum and mass balances are finally as follows.

$$\left(\frac{\beta_B d_p}{\rho_s U_o} \right) = \text{Dimensionless drag group} \quad (8-39)$$

$$\left(\frac{g d_p}{U_o^2} \right) = \text{Froude number} \quad (8-40)$$

$$\frac{\rho_f U_o d_p}{\mu_f} = \text{Reynolds number} \quad (8-41)$$

$$\left(\frac{\rho_f}{\rho_s} \right) = \text{Density ratio} \quad (8-42)$$

$$\left(\frac{\mu_s}{\mu_f} \right) = \text{Relative viscosity} \quad (8-43)$$

$$\left(\frac{G}{\rho_s}\right)^{\frac{1}{2}} \frac{1}{U_o} = \frac{\text{granular "sonic" velocity}}{\text{inlet fluid velocity}} \quad (8-44)$$

$$\left(\frac{U_o}{C_m}\right) = \text{Mach number based on mixture sonic speed} \quad (8-45)$$

The solids and the fluid momentum balances Equations (8-28) and (8-29) show that for some typical values, such as

$$\left(\frac{\rho_f U_o d_p}{\mu_f}\right) = 100, \left(\frac{\rho_g}{\rho_s}\right) = 10^{-3}, \frac{\mu_s}{\mu_g} = 10^2 \quad (8-46, 48)$$

the viscous effects vanish away from the surfaces. The momentum balances reduce themselves to the inviscid flow studied in Chapter 7 and used by Glickman (1984).

The granular dimensionless sonic velocity defined by the scale factor, Equation (8-44) vanishes for dilute flow. It is of the order of unity, however, near minimum fluidization. The Mach number based on the sonic velocity is small, except at high flows, of the order of 10 m/s. The deletion of these terms by Glickman (1984) in scaling fluidized beds will not generally lead to errors.

By using the Ergun equation for the friction coefficient, Glickman observed that the drag group, Equation (8-39) could be expressed in terms of the particle Reynolds number, defined by Equation (8-41), in the viscous limit. In this limit his scale factors that are obtained from the momentum balances are then the Reynolds number, the Froude number and the sphericity which occurs in the Ergun equation. For high particle Reynolds numbers, the corresponding scale factors are the Froude number, the density ratio and the sphericity. As pointed out by Glickman (1990) these groups help to explain Geldart's classification of particles. In Chapter 6 it was

already shown that the transition between the bubbling B group and the disperse D group depended upon the use of the first, viscous or the second, inertial term in the Ergun equation for A and D groups, respectively. The transition to the A group depends upon the minimum bubbling velocity. Hence it involves the group given by Equation (8-44), the granular sonic velocity group, not used by Glickman. The transition to Geldart C category involves the cohesive force which was not used in the constitutive equation for traction. Electrical forces of importance for fine particles were also not included in the theory developed in this chapter. Application of the present theory to dispersed gas-liquid flow will involve consideration of the surface tension. This will lead to another fundamental group, called the Weber number (Lyczkowski, et al 1982). Dimensionalization of the boundary, inlet, outlet and the initial conditions will lead to additional scale factors, most of which were recognized by Glickman (1984). For no slip boundary conditions at the walls, the only dimensionless groups will be the geometric length ratios recognized by Glickman (1984) and given below.

$$\frac{L_i}{d_p} = \text{geometric scale factors, } i = 1, 2, 3 \quad (8 - 49)$$

With particle slip at the wall, a slip ratio group may appear.

With a prescribed inlet fluid velocity U_o , a pressure P_{in} and no entering solids, that is for a batch system, such as a bubbling bed, there exists a pressure scale factor recognized by Glickman (1984) and given below

$$\frac{P_{in}}{\rho_{go} U_o^2} = \text{pressure scale factor} \quad (8 - 50)$$

The outlet pressure may be used as a reference pressure. For zero gradients at the

outlet, there are no scale factors contributing to the above list.

For large times, of practical interest in scaling, the influence of the initial conditions will disappear, except for the inventory of particles in a batch system. The inventory contributes an initial height of particles, $L_{initial}$ and the additional scale-factor shown below.

$$\frac{L_{initial}}{dp} = \text{inventory height} \quad (8 - 51)$$

The scale-factor (8-51) is clearly an important group overlooked by Glickman (1984) in scaling fluidized beds. It is well-known that shallow beds and deep beds do not operate in the same flow regime. For example, deep beds will slug.

For a flow system in place of the dimensionless inventory, an inlet solids flux, or an inlet porosity must be prescribed to completely characterize the system (Arastoopour and Gidaspow, 1979). For example, pressure drop data for circulating fluidized beds are generally given as a function of gas flow rate and solids flux (Yerushalmi, 1986).

This will clearly lead to an additive dimensionless group. In such a flow system such a group will replace the scale-factor (8-51).

Other geometrical factors and flow ratios will result from use of complex geometries with several inlet flows. The presence of so many scale factors that must be the same for complete similarity, makes the traditional scale-up of fluidized beds quite difficult. An alternate approach is to simply numerically solve the equations of change.

4. CFB OR RISER FLOW: EXPERIMENTAL

Circulating fluidized beds (CFB) are common in the petroleum industry in which the older bubbling fluidized bed reactors are being replaced by the circulating fluidized bed risers due to the recently developed highly active catalysts. The second major emerging application is to circulating fluidized bed combustors which are being built to burn high sulfur coals. These combustors offer the potential of burning coal and incinerating wastes with low SO_2 and NO_x emissions.

Figure 5-1 shows a schematic of flow in a CFB. The standpipe is filled with solids which may be fluidized to yield fast recirculation rates. The flow in the riser section discussed here lies in the range between the minimum fluidization volume fraction which may occur near the bottom of the riser and the dilute pneumatic transport discussed in Chapter 2. The pressure drop versus the superficial velocity behavior is to the left of the minimum shown in Fig. 2.8. Gas velocities are in the range of 5 to 15 m/s.

Although CFBs are widely used in the petroleum and chemical industries, the understanding of riser flow hydrodynamics came slowly. A systematic study began at the City College of New York. (Squires et al, 1985; Yerushalmi, 1986). Pressure drop, solids flux and gas velocity data were correlated in terms of a slip, as shown below.

$$\text{slip velocity} = v_g - G_s / \rho_s \epsilon_s \quad (8 - 52)$$

where G_s is the measured solids flux and where ϵ_s , the solids volume fraction was determined by assuming that the pressure drop equals the weight of the solids. These slip velocities turned out to be many times the terminal solids velocity. The explanation given was that the solids formed clusters which behaved like large particles. Indeed high speed movies do show the formation of dense regions of particles, especially near the walls. However, later measurements at the City College of New York (Weinstein, et al, 1986) at Bradford in England (Geldart and Rhodes, 1986, Rhodes, et al. 1989), at IGT (Bader, et al, 1988), in France (Galtier, et al, 1989) and elsewhere showed that there exist large

radial non-uniformities and that the flow can be characterized as a core-annular flow with particles descending down the walls either in the form of sheets or clusters. Figure 8-1 shows an idealized velocity profile constructed by Miller (1991). Solids are transported up the riser pipe in a dilute core. For them to flow up, the axial pressure drop must be larger than the weight of the dilute core in developed flow. At the walls there exists a thick dense annular region. The weight of this annulus exceeds the axial pressure drop. Hence this annular region moves down slowly. The core is generally thicker at the bottom of the riser than near the top. There exists internal refluxing. Particles move from the annular region to the core near the bottom of the riser. They move from the core to the annulus near the top. The flow is never steady but oscillates slowly.

Some typical data obtained by Miller (Miller and Gidaspow, 1992; Miller, 1991) are presented below to clarify the observed hydrodynamics. Time-averaged data were obtained for flow of $75\text{ }\mu\text{m}$ FCC catalyst particles in a 7.5 cm diameter clear acrylic riser shown in Figure (8-2) for the central section as a function of gas and solids flow rates. Particle concentrations show the data for the top section. We see a dilute core and the central dense annulus. To obtain particle velocities, fluxes were measured using the extraction probe depicted in Figure 8-5. Flux data are shown in Figure (8-6) for three sections. The largest downflow at the wall is near the bottom. This flux exceeds the average feed by several times, illustrating the internal refluxing. A video of the experiment shows an oscillating downflow at the wall. A similar high speed video of a more dilute flow of Geldart group B $500\text{ }\mu\text{m}$ particles showed the flow to be in the form of clusters. (Gidaspow, et al 1989). They descended down the wall at a rate of about 1 m/sec .

Flux and concentration data were used to construct radial particle velocity profiles. Figure 8-7 shows such typical curves for the three sections at one gas velocity. At the wall the solids descend at velocities of 10 cm/s to 1.5 m/s . A fully developed flow momentum balance depicted in Figure (8-8) shows how the velocity, concentration and pressure drop data can be used to obtain the mixture solids viscosities. The pressure drop minus the

radially integrated weight of the bed over the core equals the shear at the core-annular interface. For developed flow the solids shear equals the mixture viscosity times the radial velocity gradient which was computed from least square fits of data such as shown in Figure (8-7). Such computations produced the viscosities shown in Figure (8-8). The dashed lines show the 95% confidence levels. When a correction was made for developing flow (Miller and Gidaspow, 1992, Miller, 1991) the values of the viscosities decreased a little, but not significantly. The viscosities shown in Figure (8-8) extrapolate to the bubbling bed viscosities which are of the order of poises (Schügerl, 1971). Like the viscosities for liquid-solid systems reviewed by Jeffreys and Acrivos (1976), the viscosities measured for CFB flow correlate with the solids volume fraction.

5. NEED FOR CLUSTERS IN ONE-D MODELING

CFB or riser flow involves vertical transport of solids with downflow either in the form of cluster-like solid waves or in the form of a more continuous downward moving sheet of solids. One dimensional modeling of the type described in Chapter 2 clearly cannot give two solids velocities without breaking up the pipe region into at least two parts: a downward moving region and an upward moving region. Insistence on the use of the convenient one dimensional model led to the concept of a cluster. Drag was simply increased artificially by the use of a large cluster diameter in place of the actual particle size (Arastoopour and Gidaspow, 1979). This trick which unfortunately can also be supported by visual observation of clusters, produced the correct large particle concentration in the pipe and the correspondingly large pressure drop. Other investigators had modified the drag correlations in different ways or simply presented the particle distribution as an empirical correlation. To show that one dimensional modeling using standard drag relations produces a particle concentration in the riser that is too low, the following problem was solved by Tsuo and Gidaspow (1990). $520\mu\text{m}$ glass beads were conveyed vertically upward with a gas at a velocity of 5 m/sec, with a solids flux of 25 kg/m^2 in a grounded 7.67 cm diameter acrylic plastic pipe in a set-up similar to that shown in Figure 8-2. For this low gas velocity a high

speed motion picture showed that the solids were descending down the wall in the form of clusters. The clusters disappeared when the velocity was raised to 5.5 m/s. The axial particle concentration profile was similar to that shown in Figure 2.4 for the pneumatic transport regime. In the cluster regime, at 5 m/s the fully developed particle volume fraction was 0.0115.

To obtain the computed axial concentration profile the transient version of the steady state one dimensional equations fully discussed in Chapter 2 were solved. Table 8-1 shows these equations. As in the experiment, initially the pipe was free of solids. At zero time the solids were introduced into the pipe, as shown in Figure (8-9). This figure also shows the computed axial distribution as a function of time. The system reached a steady state after a period of 5 seconds. The computed solids volume fraction in the fully developed region was only 0.0065, or almost half the measured value. Two dimensional analysis described in the next section produced much more realistic results.

6. COMPUTATION OF CLUSTER FLOW

Two dimensional computations were done using the equations shown in Table 8-2 for the geometry shown in Fig. (8-10). As a crude approximation constant inlet conditions were used. Characteristics discussed in Chapter 7 demand that outlet conditions be prescribed. For naturally occurring downflow, there are no simple outlet conditions that can be assigned. (Tsuo and Gidaspow, 1990). Hence a bend in the pipe was included as part of the computational geometry. There continuous outflow was assigned, as shown in Figure (8-9). At the walls a no slip boundary condition is a good approximation for both the gas and fine solids. A viscosity coefficient of 0.509 Pa-s was used in the computation.

The two-dimensional simulation was done for 18 s. It took a 4 s period to fully fill the empty pipe with particles. Tsuo (1989) shows the outlet solids mass flux as a function of time. The outlet solids mass flux reached the inlet solids mass flux of $25 \text{ kg/m}^2 \cdot \text{s}$ at 11 s of real fluidization time. Outlet mass flux of solids oscillated at an average period of 5 s. This very low frequency of around 0.2 Hertz is consistent with the observed and

computed wall cluster descent speed of about 1 m/s. Similar speeds and low frequencies were reported by Weinstein et al. (1986) and Abed (1984) in their CFB systems.

Figure (8-10) shows the solids concentration profiles as a function of time. The first cluster of particles forms after 3.0 s in the center region (Tsuo, 1989). The cluster at first grew larger and denser, then it started falling down. Later several clusters formed near the wall and started to run down. A few clusters joined together and created a significant downflow. The typical wall clusters observed descend at a velocity of 1.1 m/s. The average cluster size was about 2 to 3 cm. All these phenomena were observed in the high speed motion pictures of the experiment.

The cluster behaves as a hydrodynamic unit or as a particle of a large effective diameter, as arbitrarily assumed in the modeling study of Arastoopour and Gidaspow (1979). Figure (8-10) shows the negative velocities of the clusters.

Figure (8-11) shows typical computed time-averaged and measured radial profiles of solids concentration in a developed region. Both the model and the experiment show a much higher solids concentration at the wall of the tube due to the formation of clusters near the wall.

Figure (8-12) shows typical computed time-average and measured radial distribution of axial solids velocities at an axial location of 3.4 m. In general, a comparison between the experimental and the computed radial distribution of axial solids velocities is good. There are some discrepancies in the center region. The solids volume fraction in the center region is around 0.005. The x-ray densitometer, which was used in Luo's (1987) experiment for measuring the solids concentration, is not considered to be accurate for such small values of solids concentration. Therefore, the experimental solids velocity, computed from the measured local flux using a ball probe and the measured local concentration, is also not accurate in the center region. Figure (8-13) shows typical computed time-average and measured radial distributions of axial gas velocity at an axial location of 3.4 m. A comparison between the experimental and the computed radial distributions of axial gas

velocities is good.

Several parametric studies were conducted in order to understand the formation of clusters in CFB risers. (Tuso and Gidaspow, 1990). Cluster density increased with an increasing solids flux, with a decreasing gas velocity and with a decreasing pipe radius, as expected. The cluster flow appeared to change into a smoother core - annular flow as the particle size was decreased to 100 μm .

7. COMPUTATION OF CORE-ANNULAR REGIME

At the time of computation typical dense CFB data have been obtained by Weinstein et al. (1984) at the City College of New York and by Bader et al. (1988) at the Institute of Gas Technology (IGT). The experimental conditions of Bader et al. were chosen for the computer simulation. The simulations and the experiment were conducted in a 30.5 cm dia. riser with 76 μm FCC catalyst. The superficial gas velocity is 3.7 m/s and the circulating solids flux is 98 $\text{kg}/\text{m}^2 \cdot \text{s}$. Figure 8-14 shows the configuration of the system and the computational conditions. A viscosity coefficient of 0.724 Pa-s was used.

The computer simulation was done for 18 s of the real fluidization time. It took 8 s to fully fill the empty pipe with particles.

The computed volume fraction data were converted into a series of density plots. The number of black dots is proportional to the volume fraction of the solid phase. Figure (8-15) shows the density plots for the solids volume fraction at times of 10 and 16 s after the start-up of particle injection. The empty pipe was fully filled with particles after 8 s of real fluidization time. From the dot density plots, the nonhomogeneous distribution of solid particles can be seen in both the axial and the radial directions. There is a dense annular layer at the wall and a dilute core at the center of the riser. Typical computed distributions of porosity in the riser at two axial locations equal to 4.1 and 9.1 m above the solids entry port are shown in Figure 8-16 and 8-17, respectively. The experimental data of Bader et al. (1988) are also included in Figures 8-16 and 8-17. The match between the computed and the measured porosities is reasonably good. Both the theory and the

computation show high solids concentrations near the wall of the riser corresponding to porosities of 0.85 and 0.75, but much higher porosities, 0.95 to 0.98, at the center of the riser.

Figures 8-18 and 8-19 show typical radial distributions of axial time-averaged solids velocities at axial locations of 4.1 and 9.1 m, respectively. The particle velocity in the center of the riser was computed to be two to three times the superficial gas velocity in the riser.

This sharp rise of the center velocity is caused by the fact that the thick annular region seen in Figure 8-15 blocks the upward motion of the gas and the particles. By conservation of mass the smaller effective flow area leads to a correspondingly larger gas and through the drag a larger central particle velocity. This effect is also seen in all of the measurements obtained by Miller (1991). For example, Fig 8-7 shows the particle velocity near the center for the middle section of the riser to be about 6 m/sec for an inlet gas velocity of 2.9 m/sec. Miller's upper section shows a lower velocity due to the bend close to the upper section. In his lowest section the particles did not fully accelerate as yet. Miller's calculations showed a significant acceleration effect in this lowest section.

Figures 8-18 and 8-19 also show the experimental data of Bader, et al. (1988). They determined their particle velocities directly by use of a pitot tube, averaging the wild fluctuations in pressure. The flux was obtained by the extraction probe already discussed in the previous paragraph. The porosity plotted in Figures 8-17 and 8-18 was obtained indirectly from the flux and the solids velocity. In Figures 8-18 and 8-19 the downward and the upward refer to the upward or downward position of the Pitot tube. The difference between the data shows the order of fluctuations of velocity. Such fluctuations were observed in Miller's experiments visually. In view of these experimental difficulties and the use of an only rough value of the solids viscosity in the model, highly idealized inlet conditions and a slice approximation for radial geometry, the comparison between Bader's et al. (1988) experiment and the theory is very reasonable.

Figure 8-20 shows typical distributions of axial gas velocity at the two locations. For 76 μm FCC particle flow the gas flow pattern is similar to the solids flow patterns.

Figure 8-21 shows radial distributions of radial solids velocities at 15 s of real fluidization time at the two locations of 4.1 and 9.1 m. The particles at the 4.1 m level moved from the wall to the center and at the 9.1 m level moved in the reverse direction, from the center to the wall in the left-hand side of the pipe at 15 s after start-up. These velocities oscillate in a turbulent like manner. The radial velocities are small compared with the axial velocities.

8. RADIAL PROFILES AND TURBULENCE

The objective of comparing the viscous model radial particle concentration profiles to experiments was to determine whether the model could predict the radial inhomogeneities observed in real systems and in experiments. An alternate approach was to use an extension of semi-empirical turbulence models widely used in single-phase flows. Such an approach involves the substitution of average plus fluctuating components of all dependent variables into the conservation laws, performing a time averaging and then using some semi-empirical equations for the unknown Reynolds stresses. Although such an approach had a considerable success in single phase flow, the low frequency turbulence normally observed in dense two phase flow makes it possible to directly compute the large scale turbulence. The small scale turbulence related to the isotropic part of the Reynolds stresses is computed in the kinetic theory chapter using our equation for an oscillating kinetic energy. Hence there is not need to introduce two- phase turbulence. As in low Reynolds number single phase flow, turbulence is computed by direct numerical simulation. However, as in single phase flow, such direct numerical simulations take longer, since all the oscillations must be resolved.

At the time of the simulation, the only radial concentration data that were available were those of Weinstein, et al (1986) from CCNY. Their system was approximated as shown in Figure 8-22. Two simulations were performed by feeding particles into an initially empty

pipe. A viscosity coefficient of 7.24 poises was used. Figure 8-23 shows the particle velocity and concentrations 12 seconds after injection for the high flux simulation. There exists a dilute core of rapidly rising particles with a dense slowly descending annulus. For the conditions of the experiment flow never develops. The bottom half of the pipe is much denser than the top half. In Fig. 18-23, the first meter of the pipe does not correspond to the experiment due to an unrealistic assumption of constant inlet conditions. Figure 8-24 shows a comparison of time averaged particle concentration to Weinstein's et al (1986) data. The agreement is very good. The model predicts the observed behavior.

NOMENCLATURE

A_k	Constant related to phase k pressure
B_k	Constant related to phase k viscosity
C	Sonic velocity
d_p	Particle diameter
f	Friction factor
F	Flux
g	Acceleration due to gravity
G	Particle-particle modulus, $\partial P_s / \partial \epsilon_s$
$\bar{T}$	Stress tensor of phase k (traction)
U	Velocity
$\vec{v}_k$	Velocity of phase k
x_i	Coordinate in the i-th direction

Greek Letters

β	Fluid-particle friction coefficient, $\text{kg/m}^3\text{-s}$
ϵ	Gas volume fraction (porosity)
ϵ_k	Volume fraction of phase k
λ_k	Bulk viscosity of phase k
μ_k	Viscosity of phase k
ρ_k	Density of phase k
μ_{sc}	Viscosity coefficient of solid phase, $\mu_s = \epsilon_s \mu_{sc}$

Operators and Identities

∇	Gradient
$\nabla \cdot$	Divergence
∇^T	Transpose of the gradient
∇^S	Symmetric gradient = $\frac{1}{2}(\nabla + \nabla^T)$
$\nabla^S \vec{v}$	Deformation tensor = $\frac{1}{2} \left(\frac{\partial v_i}{\partial x_j} + \frac{\partial v_j}{\partial x_i} \right)$
$\nabla \vec{v}$	$\frac{1}{2}(\nabla \vec{v} + \nabla^T \vec{v}) + \frac{1}{2}(\nabla \vec{v} - \nabla^T \vec{v})$
	$\nabla^S \vec{v} = \frac{1}{2} \nabla^2 \vec{v} + \frac{1}{2} \nabla \nabla \cdot \vec{v}$

Table 8-1. One Dimensional Equations of Change

Gas Continuity Equation

$$\frac{\partial(\rho_g \epsilon_g)}{\partial t} + \frac{\partial(\rho_g \epsilon_g U_g)}{\partial x} = 0 \quad (T1)$$

Solid Continuity Equation

$$\frac{\partial(\rho_s \epsilon_s)}{\partial t} + \frac{\partial(\rho_s \epsilon_s U_s)}{\partial x} = 0 \quad (T2)$$

Gas Momentum Equation

$$\frac{\partial(\rho_g \epsilon_g U_g)}{\partial t} + \frac{\partial(\rho_g \epsilon_g U_g U_g)}{\partial x} = -\frac{\partial P}{\partial x} + \beta(U_s - U_g) + \frac{2f_g \epsilon_g \rho_g U_g^2}{D} + \rho_g g \quad (T3)$$

Solids Momentum Equation

$$\frac{\partial(\rho_s \epsilon_s U_s)}{\partial t} + \frac{\partial(\rho_s \epsilon_s U_s U_s)}{\partial x} = \beta(U_g - U_s) - G \frac{\partial \epsilon_s}{\partial x} + \frac{2f_s \epsilon_s \rho_s U_s^2}{D} + (\rho_s - \rho_g) \epsilon_s g \quad (T4)$$

$$\epsilon_g + \epsilon_s = 1 \quad (T5)$$

The Ideal Gas Equation

$$\rho_g = \frac{P}{RT} \quad (T6)$$

Inter Phase Friction Coefficient β :

Based on Ergun Equation

$$\epsilon_g \leq 0.8 \quad \beta = 150 \frac{\epsilon_s^2 \mu_g}{(\epsilon_g d_p \phi_s)^2} + 1.75 \frac{\rho_g |U_g - U_s| \epsilon_s}{(\epsilon_g d_p \phi_s)} \quad (T7)$$

Based on Single Sphere Drag

$$\epsilon_g \geq 0.8 \quad \beta = \frac{3}{4} C_d \frac{|U_g - U_s| \rho_g \epsilon_s}{d_p \phi_s} \epsilon_g^{-2.65} \quad (T8)$$

Table 8-1. One Dimensional Equations of Change (Continued)

with

$$C_d = \frac{24}{Re_s} (1 + 0.15 Re_s^{0.687}) \quad Re_s \leq 1000 \quad (T9)$$

$$C_d = 0.44 \quad Re_s \geq 1000 \quad (T10)$$

$$Re_s = \frac{|U_g - U_s| d_p \rho_g \epsilon_g}{\mu_g} \quad (T11)$$

Solids Stress Modulus

$$G(\epsilon_g) = \frac{\partial P_s}{\partial \epsilon_s} = 10^{-8.76 \epsilon_g + 5.43} \quad (T12)$$

Friction Factors: Modified Hagen-Poiseuille Expression

$$f_g = \frac{16}{Re_g} \quad \text{for } Re_g \leq 2100 \quad (T13)$$

$$f_g = \frac{0.0791}{Re_g^{0.25}} \quad \text{for } 2100 < Re_g \leq 100,000 \quad (T14)$$

$$\frac{1}{\sqrt{f_g}} = 2 \log (Re_g \sqrt{f_g}) - 0.8 \quad \text{for } Re_g > 100,000 \quad (T15)$$

where

$$Re_g = \frac{DU_g \rho_g \epsilon_g}{\mu_g} \quad (T16)$$

Konno's Correlation

$$f_s = 0.0025 U_s^{-1} \quad (T17)$$

Table 8-2.
Viscosity Coefficient Hydrodynamic Model B

Hydrodynamic Model

Continuity Equations

Gas Phase

$$\frac{\partial(\rho_g \epsilon_g)}{\partial t} + \nabla \cdot (\rho_g \epsilon_g \vec{v}_g) = 0 \quad (T1)$$

Solid phase

$$\frac{\partial(\rho_s \epsilon_s)}{\partial t} + \nabla \cdot (\rho_s \vec{v}_s \epsilon_s) = 0 \quad (T2)$$

Momentum Equations

Gas Momentum

$$\frac{\partial(\rho_g \epsilon_g \vec{v}_g)}{\partial t} + \nabla \cdot (\rho_g \epsilon_g \vec{v}_g \vec{v}_g) = -\nabla P + \beta(\vec{v}_s - \vec{v}_g) + \nabla \cdot \epsilon_g \bar{\bar{T}}_g + \rho_g g \quad (T3)$$

where

$$\bar{\bar{T}}_g = 2\mu_g \nabla^s \vec{v}_g - 2/3 \mu_g \nabla \cdot \vec{v}_g \bar{I} \quad (T4)$$

$$\nabla^s \vec{v}_g = 1/2 [\nabla \vec{v}_g + (\nabla \vec{v}_g^T)] \quad (T5)$$

Solids momentum

$$\frac{\partial(\rho_s \epsilon_s \vec{v}_s)}{\partial t} + \nabla \cdot (\rho_s \epsilon_s \vec{v}_s \vec{v}_s) = \beta(\vec{v}_g - \vec{v}_s) \quad (T6)$$

$$-G \nabla \epsilon_s + \nabla \cdot \epsilon_s \bar{\bar{T}}_s + (\rho_s - \rho_g) \epsilon_s g \quad (T7)$$

where

$$\bar{\bar{T}}_s = 2\mu_s \nabla^s \vec{v}_s - 2/3 \mu_s \nabla \cdot \vec{v}_s \bar{I} \quad (T8)$$

$$\nabla^s \vec{v}_s = 1/2 [\nabla \vec{v}_s + (\nabla \vec{v}_s^T)] \quad (T9)$$

$$\epsilon_g + \epsilon_s = 1 \quad (T10)$$

Constitutive Equations

Ideal Gas Equation

$$\rho_g = \frac{P}{RT} \quad (T11)$$

Interphase Friction Coefficient β

$$\epsilon_g \leq 0.8 \quad \beta = 150 \frac{\epsilon_s^2 \mu_g}{(\epsilon_g d_p \phi_s)^2} + 1.75 \frac{\rho_g |\vec{v}_g - \vec{v}_s| \epsilon_s}{(\epsilon_g d_p \phi_s)} \quad (T12)$$

Based on single sphere drag

$$\epsilon_g \geq 0.8 \quad \beta = \frac{3}{4} C_d \frac{|\vec{v}_g - \vec{v}_s| \rho_g \epsilon_s}{d_p \phi_s} \epsilon_g^{-2.65} \quad (T13)$$

with

$$C_d = \frac{24}{Re} (1 + 0.15 Re^{0.687}) \quad Re \leq 1,000 \quad (T14)$$

$$C_d = 0.44 \quad Re \geq 1,000 \quad (T15)$$

$$Re = \frac{|\vec{v}_g - \vec{v}_s| d_p \rho_g \epsilon_g}{\mu_g} \quad (T16)$$

Solids Stress Modulus

$$G(\epsilon_g) = \frac{\partial P_s}{\partial \epsilon_s} = 10^{-8.76 \epsilon_g + 5.43} N/m^2 \quad (T17)$$

----- IDEAL VELOCITY PROFILE

Fig. 8-1. Particle Velocity Profile for Dense, Vertical Transport of 75 μ m FCC Catalyst Particles in the CFB Shown in Fig. 8-2. (Miller and Gidaspow, 1991)

Fig. 8-2. Circulating Fluidized Bed (CFB) at IIT (Miller and Gidaspow, 1991)

X-RAY PROBE

Fig. 8-3. X-ray Probe Constructed by Miller (1991) to Measure Particle Concentrations (Miller and Gidaspow, 1991)

☆ AVERAGE FLUX=32.8 KG/(M²-SEC)
 □ AVERAGE FLUX=19.7 KG/(M²-SEC)
 ◇ AVERAGE FLUX=12.0 KG/(M²-SEC)
 SUPERFICIAL GAS VELOCITY(118.56kPa)=2.89 M/S
 HEIGHT=5.52 M

Fig. 8-4. Typical 75 μ m FCC Particle Concentration: Dense Layer at the Wall with a Dilute Core (Miller and Gidaspow, 1991)

EXTRACTION PROBE

Fig. 8-5. Extraction Probe for Measuring Flux (Miller and Gidaspow, 1991)

Fig. 8-6. Typical Flux Profile in IIT's CFB for 75 μ m FCC Particles. Note Large Downward Flux Near the Wall. (Miller and Gidaspow, 1991)

Fig. 8-7. Typical Particle Velocities in IIT's CFB for 75 μ m FCC Particles Determined from Flux and Concentration Measurements. Note Acceleration and then Deceleration due to Top Bend (Miller and Gidaspow, 1991)

Fig. 8-8. Viscosity of 75 μm FCC Particles without a Correction for Acceleration (Miller and Gidaspow, 1991)

Fig. 8-9. One-dimensional Simulation of Transient Vertical Conveying (Tsuo and Gidaspow, 1990)

Fig. 8-10. IIT Geometry and Computed Distributions of Solids Velocities and Particle Density for Inlet and Initial Conditions in Fig. 8-9. $d_p = 520 \mu\text{m}$; $\rho_p = 2.62 \text{ g/cm}^3$ (Tsuo and Gidaspow, 1990)

Fig. 8-11. Radial Variation of Computed and Measured Solids Volume Fraction of $520 \mu\text{m}$ Glass Beads in the Cluster Regime. (Tsuo and Gidaspow, 1990)

Fig. 8-12. Radial Variation of Computed and Measured Solids Velocities (Averaged from 10 to 15 s for computed results) Experimental Velocities Obtained from Flux Measurements using an Electrostatic Ball Probe (Tsuo and Gidaspow, 1990)

Fig. 8-13. Radial Variation of Computed and Measured Gas Velocities in the IIT Riser (Averaged from 10 to 15 s for computed results) (Tsuo and Gidaspow, 1990)

Fig. 8-14. IGT System Configuration and Computational Inlet Conditions

Fig. 8-15. Computed Distributions of Gas Velocities, Solids Velocities, and Particle Density of $76 \mu\text{m}$ FCC Particles in the IGT Riser (Tsuo and Gidaspow, 1990)

Fig. 8-16. Radial Variation of Computed and Measured Void Fraction in the IGT Riser at 4.1m. Averaged from 12 to 18 s for computed results. (Tsuo and Gidaspow, 1990)

Fig. 8-17. Radial Variation of Computed and Measured Void Fraction in the IGT Riser at 9.1 m. (Averaged from 12 to 18 s for computed results) (Tsuo and Gidaspow, 1990)

Fig. 8-18. Radial Variation of Computed and Measured Axial Solids Velocity in the IGT Riser at 4.1 m. (Tsuo and Gidaspow)

Fig. 8-19. Radial Variation of Computed and Measured Axial Solids Velocity in the IGT Riser at 9.1 m. (Tsuo and Gidaspow, 1990)

Fig. 8-20. Computed Radial Variation of Axial Gas Velocity (Tsuo and Gidaspow, 1990)

Fig. 8-21. Radial Variation of Computed Radial Solids Velocity at 15 s Real Fluidization Time in the IGT Riser (Tsuo and Gidaspow, 1990)

Case 1: High solid rate

$$W_s = 121.0 \text{ kg/m}^2\text{s}$$

$$\text{BC 1: } V_g = 3.1 \text{ m/s}$$

$$\text{BC 2: } V_s = 43.62 \text{ cm/s}$$

$$\text{BC 3: } \epsilon_s = 0.19$$

$$\text{BC 4: } P = 1.2015 \text{ atm}$$

Case 2: Low solid rate

$$W_s = 74.9 \text{ kg/m}^2\text{s}$$

$$\text{BC 1: } V_g = 3.1 \text{ m/s}$$

$$\text{BC 2: } V_s = 34.2 \text{ cm/s}$$

$$\text{BC 3: } \epsilon_s = 0.15$$

$$\text{BC 4: } P = 1.109 \text{ atm}$$

$$\text{CC 1: } \delta x = 0.076 \text{ cm}$$

$$\text{CC 2: } \delta y = 15.2 \text{ cm}$$

$$\text{CC 3: } \delta t = 0.00025 \text{ second}$$

$$d_p = 59 \mu\text{m} \quad \rho_p = 1460 \text{ kg/m}^3$$

Fig. 8-22. Geometry of the City College of New York Fast Fluid Bed for Computer Modeling with an Idealized Inlet Condition

Fig. 8-23. Computed Velocities and Concentrations for CCNY Riser for $W_s = 121$ (Gidaspow, et al. 1991)

Fig. 8-24. A Comparison of Computed and Measured Porosities in the CCNY Riser; $d_p = 59 \mu\text{m}$, $\rho_p = 1460 \text{ Kg/m}^3$, Viscosity Coefficient = 7.24 Poises (Gidaspow, et al. 1991)

REFERENCES CITED

Abed, R. (1984) "The Characterization of Turbulent Fluid-Bed Hydrodynamics" in "Fluidization," edited by H. Kunii and R. Toei, Engineering Foundation," available from AIChE, New York.

Arastoopour, H., and D. Gidaspow (1979) "Analysis of IGT Pneumatic Conveying Data and Fast Fluidization Using a Thermodynamic Model," Powder Technology, **22**, 77-87.

Bader, R., J. Findlay and T.M. Knowlton (1988). "Gas/Solid Flow Patterns in a 30.5-Cm-Diameter Circulating Fluidized Bed," in Circulating Fluidized Bed Technology II, edited by Basu P. and J.F. Large, Pergamon Press, 123-137.

Blake, T.R., H. Webb and P.B. Sunderland (1990) "The Nondimensionalization of Equations Describing Fluidization with Application to the Correlation of Jet Penetration Height," Chem. Eng. Science **45**, 365-371.

Bird, R.B., W.E. Stewart and E.N. Lightfoot (1960) "Transport Phenomena," Wiley, New York.

Drew, D.A. and Lahey, Jr. R.T. (1979) "Application of General Constitutive Principles to the Derivation of Multidimensional Two Phase Flow Equations," Int. J. Multiphase Flow **5**, 243-264.

Fitzgerald, T.J. (1985), "Course Particle Systems," Ch. 12, pp. 413-435 in "Fluidization," edited by J.F. Davidson, R. Clift and D. Harrison, Academic Press, New York.

Galtier, P.A., R.J. Pointer and T.E. Patureaux (1989) "Near Full-Scale Cold Flow Model for the R2R Catalytic Cracking Process," pp. 17-24, "Fluidization VI," J.R. Grace, L.W. Shemilt and M.A. Bergougnou, ed. Engineering Foundation, New York.

Geldart D., and M.J. Rhodes (1986) "From Minimum Fluidization to Pneumatic Transport - A Critical Review of the Hydrodynamics," in Circulating Fluidized Bed Technology, edited by Basu P., Pergamon Press, pp. 21-32.

Gidaspow, D. (1986) "Hydrodynamics of Fluidization and Heat Transfer: Supercomputer Modeling," Appl. Mech. Rev. **39**, No. 1, 1-23.

Gidaspow, D., Y.P. Tsuo and K.M. Luo (1989). "Computed and Experimental Cluster Formation and Velocity Profiles in Circulating Fluidized Beds," in Fluidization VI, J.C. Grace, L.W. Shemilt and M.A. Bergougnou, editors, pp. 81-88 Engineering Foundation, NY; available from AIChE.

Gidaspow, D., Y.-T. Shi, J. Bouillard and D. Wasan (1989) "Hydrodynamics of a Lamella Electrosettler," AIChE Journal, 35, 714-724.

Gidaspow, D., Y.P. Tsuo and J. Ding (September 1989) "Hydrodynamics of Circulating and Bubbling Fluidized Beds, Presented at the Materials Issues in Circulating Fluidized Bed Combustors," EPRI-Argonne National Lab Symposium, EPRI GS-6747, pp. 4-1 to 4-27, Feb. 1990 and preprinted for the U.S.-Korea Joint Seminar on Fluids Engineering and Science. Published in "Fluids Engineering: Korea-U.S. Progress," edited by J.H. Kim, J.M. Hyun & C. Lee, Hemisphere Publishing Co., New York (1991) pp. 485-512.

Glickman, L.R. (1984), "Scaling Relationships for Fluidized Beds," Chem. Eng. Science 39, 1373-1379.

Jayaswal, U.K., D. Gidaspow and D. Wasan (1990). "Continuous Separation of Particles in Nonaqueous Media in a Lamella Electrosettler" Separations Technology, 1, 3-17.

Jeffreys, H. (1961) "Cartesian Tensors," Cambridge Univ. Press, Cambridge, Great Britain.

Jeffrey, D.J. and A. Acrivos (1976) "The Rheological Properties of Suspensions of Rigid Particles," AIChE Journal 22, 417-432.

Luo, K.M. (1987), "Experimental Gas-Solid Vertical Transport," Ph.D. Thesis, Illinois Institute of Technology, Chicago, IL.

Lyzczkowski, R.W., D. Gidaspow and C.W. Solbrig, "Multiphase Flow-Models for Nuclear, Fossil and Biomass Energy Conversion," Chapter in Vol. II of Advances in Transport Processes, A.S. Majumdar and R.A. Mashelkar, Editors, Wiley-Eastern Publisher, pp. 198-351.

Miller, A. (1991), "Dense, Vertical Gas-Solid Flow in a Pipe," Ph.D. Thesis, Illinois Institute of Technology, Chicago, IL.

Miller, A. and D. Gidaspow (1992) "Dense, Vertical Gas-Solid Flow in a Pipe," submitted for publication.

Rhodes, M.J., T. Hirama, G. Cerutti and D. Geldart, "Non-Uniformities of Solids Flow in Risers of Circulating Fluidized Beds," pp. 73-80, "Fluidization VI," J.R. Grace, L.W. Shemilt and M.A. Bergougnou ed., Engineering Foundation, New York (1989).

Roy, R., J.F. Davidson and V.G. Tuponogov (1990) "The Velocity of Sound in Fluidized Beds," Chem. Eng. Science 45, 3233-3245.

Schlichting, H. (1960) "Boundary Layer Theory," McGraw-Hill, New York.

Schügerl, K. (1971), "Rheological Behavior of Fluidized Systems," Chapter 6 in "Fluidization," edited by J.F. Davidson and D. Harrison, Academic Press, New York.

Squires, A.M., M. Kwauk, and A.A. Avidan (1985). "Fluid Beds: At Last, Challenging Two Entrenched Practices," Science, **230**, 4732, 1329-1337.

Syamial, M. and D. Gidaspow, "Hydrodynamics of Fluidization: Prediction of Wall to Bed Heat Transfer Coefficients." AIChE Journal, **31**, 127-135 (1985).

Tsuo, Y.P. (1989), "Computation of Flow Regimes in Circulating Fluidized Beds," Ph.D. Thesis, Illinois Institute of Technology, Chicago, IL.

Tsuo, Y.P. and Gidaspow, D., "Computation of Flow Patterns in Circulating Fluidized Beds," AIChE Journal, **36**, 885-896 (1990).

Weinstein, H., M. Meller, M.J. Shao, and R.J. Parisi (1984) "The Effect of Particle Density on Holdup in a Fast Fluid Bed," in Fluidization and Fluid Particle Systems: Theories and Applications, T.M. Knowlton, Ed., AIChE Symposium Series, 234, 80, 52-59.

Weinstein, H., M. Shao, M. Schnitzlein, and R.A. Graff (1986). "Radial Variation in Void Fraction in a Fast Fluidized Bed," Fluidization V., Proceedings of the Fifth Engineering Foundation Conference on Fluidization, Elsinore, Denmark, edited by Ostergaard, K. and A Sorensen, pp. 329-336 (1986). Available from AIChE, New York.

Yerushalmi, J. (1986) "High Velocity Fluidized Beds," Ch. 7 in "Gas Fluidization Technology," D. Geldart, ed., Wiley, New York (1986).

END

**DATE
FILMED**

12 / 15 / 92