VIBRATION OF A GROUP OF CIRCULAR
CYLINDERS IN A CONFINED FLUID

by

Ho Chung and Shoei-sheng Chen

Components Technology Division

NOTICE

PORTIONS OF THIS REPORT ARE ILLEGIBLE. It
has been reproduced from the best available
copy to permit the broadest possible avail-
ability.

MASTER

U of C-AUA-USERDA

Base Technology

February 1976

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

The facilities of Argonne National Laboratory are owned by the United States Government. Under the terms of a contract (W-31-109-Eng-38) between the U. S. Energy Research and Development Administration, Argonne Universities Association and The University of Chicago, the University employs the staff and operates the Laboratory in accordance with policies and programs formulated, approved and reviewed by the Association.

MEMBERS OF ARGONNE UNIVERSITIES ASSOCIATION

The University of Arizona	Kansas State University	The Ohio State University
Carnegie-Mellon University	The University of Kansas	Ohio University
Case Western Reserve University	Loyola University	The Pennsylvania State University
The University of Chicago	Marquette University	Purdue University
University of Cincinnati	Michigan State University	Saint Louis University
Illinois Institute of Technology	The University of Michigan	Southern Illinois University
University of Illinois	University of Minnesota	The University of Texas at Austin
Indiana University	University of Missouri	Washington University
Iowa State University	Northwestern University	Wayne State University
The University of Iowa	University of Notre Dame	The University of Wisconsin

cc: Director, ERDA-RDD
Deputy Director for Technology, ERDA-RDD
Assistant Director for Technology, ERDA-RDD
Assistant Director for Engineering, ERDA-RDD
Assistant Director for CRBRPO, ERDA-RDD (Oak Ridge)
Assistant Director for FFTFPO, ERDA-RDD (Hanford)
Director Reactor Programs Division, ERDA-CH
Director Demonstration Plant Office, ERDA-CH
Chief, Reactor Analysis Branch, ERDA-RDD
Chief, Component Development Branch, ERDA-RDD
Chief, ANL Branch, ERDA-RDD
N. Grossman, ERDA-RDD
B. C. Wei, ERDA-RDD
S. J. Sims, ERDA-CH
J. F. Murdock, ERDA-OR
T. L. King, ERDA-HEDL
CT AUA Review Committee

VIBRATION OF A GROUP OF CIRCULAR
CYLINDERS IN A CONFINED FLUID

by

Ho Chung and Shoei-sheng Chen

Components Technology Division

NOTICE

PORTIONS OF THIS REPORT ARE ILLEGIBLE. It has been reproduced from the best available copy to permit the broadest possible availability.

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

U of C-AUA-IISERDA

Base Technology

February 1976

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

PREFACE

The work reported herein was performed as part of the base technology activity under the Flow Induced Vibration Program (189a No. CA054-A and CA070-A) sponsored by ERDA/RDD. The overall objective of the activity is to develop new and/or improved analytical methods and guidelines for designing LMFBR components to avoid detrimental flow induced vibration.

Heat exchanger tubes and reactor fuel pins are long, slender, beam-like components typically arranged in bundles and immersed in a flowing fluid. As such, they are susceptible to flow-induced vibration. The excitation mechanism may be associated with vortex-shedding, fluidelastic interaction, or random pressure fluctuations in the turbulent flow. Designing to avoid large amplitude motion, that is, to avoid a resonance condition or instability condition, and the prediction of component response, require knowledge of the dynamic behavior of the components. However, cylinders in a closely spaced bundle do not respond as single cylinders immersed in a fluid, rather, interaction with the fluid causes coupled motion of groups of cylinders. The fundamental natural frequency of the coupled system will be lower than that of a single cylinder immersed in a fluid.

Understanding and modeling fluid/structure interaction in cylinder bundles is a basic requirement in the development of analytical methods and guidelines for designing heat exchanger and reactor fuel assemblies that are free from component vibration problems. As a step toward satisfying this requirement, in this report a method of analysis based on the potential flow theory is developed for analyzing free vibration of a group of cylinders immersed in a fluid contained in a cylinder. The method of analysis presented can determine the added

mass coefficients and natural frequencies of coupled cylinder-fluid systems. To demonstrate the method the coupled natural frequencies for two eccentrically located cylinders with a fluid-filled gap are calculated and discussed. A few other examples are also given to show the added mass coefficients.

TABLE OF CONTENTS

	<u>Page</u>
PREFACE	i
TABLE OF CONTENTS	iii
LIST OF FIGURES	iv
LIST OF TABLES	v
NOMENCLATURE	vi
ABSTRACT	ix
I. INTRODUCTION	1
II. ADDED MASS MATRIX	3
A. Formulation and Solution	3
B. Reciprocal Relations	14
C. Numerical Results	17
III. VIBRATION OF A GROUP OF CYLINDERS	24
A. Frequency Equation	24
B. Sample Problem: Free Vibration of Two Eccentric Cylinders with a Fluid-Filled Gap	26
IV. CONCLUSIONS	33
REFERENCES	35
APPENDIX: Computer Program (AMASS)	37

LIST OF FIGURES

<u>No.</u>	<u>Title</u>	<u>Page</u>
1	Schematic and Coordinate System for a Group of Circular Cylinders in a Fluid-Containing Cylinder	4
2	Variations of Added Mass Coefficients with the Number of Terms n Used in Calculations	18
3	Added Mass Coefficients for Two Eccentric Cylinders with a Fluid-Filled Gap	20
4	Added Mass Coefficients for a Seven-Cylinder Bundle in a Fluid-Containing Cylinder	23
5	Two Eccentric Cylinders with a Fluid-Filled Gap	27
6	Natural Frequencies for Two Eccentric Cylinders with a Fluid-Filled Gap as Functions of Eccentricity	31

LIST OF TABLES

<u>No.</u>	<u>Title</u>	<u>Page</u>
1	Added Mass Coefficients for Two Eccentric Cylinders with a Fluid-Filled Gap	19
2	Variations of Added Mass Coefficients for a Seven- Cylinder Bundle in a Fluid-Containing Cylinder	22
3	Natural Frequencies for Two Eccentric Cylinders with a Fluid-Filled Gap	29

NOMENCLATURE

a_{in}, b_{in}	Arbitrary constants to be determined in Eq. (17)
C_{mn}	Coefficients in Eqs. (4-7, 12, 13); $(m+n-1)!/[m!(n-1)!]$
D_{mn}	Coefficients in Eqs. (9, 10); $n!/[m!(n-m)!]$
e	Eccentricity for two eccentric cylinders
$\vec{e}_i, \vec{e}_\ell$	Unit vectors
E	Modulus of elasticity
f	External loading per unit length
f_{pn}	Generalized force in Eq. (42)
$F_{\ell i}$	Hydrodynamic force acting on cylinder ℓ due to the motion of cylinder i
G	Gap size between cylinders
H_i, G_i	Fluid dynamic forces acting on cylinder i in the x-direction and in the y-direction
h_{pn}	Generalized coordinates in Eqs. (41,42)
$\bar{h}_{pn}$	Normal modes of cylinders
I	Moment of inertia
k	Total number of inner cylinders under consideration
ℓ	Length of cylinder
m_i	Mass per unit length of cylinder i
p	Fluid pressure
r_i, θ_i	Coordinates associated with cylinder i
R_i	Radius of cylinder i
R_{ij}	Distance between the centers of cylinder i and j
S_i	Surface of cylinder i
S, S_r	Surfaces
t	Time
u_i, v_i	Displacements in the x-direction and in the y-direction of cylinder i

U_i	Displacement of cylinder i
V	Fluid velocity component in radial direction
x, y	Cartesian coordinates
x_j, y_j	Local cartesian coordinates associated with cylinder j
X, Y	Coordinates associated with the outer cylinder 0
z	Axial coordinate
$\alpha_{il}, \beta_{il}, \sigma_{il}, \tau_{il}$	Added mass coefficients
$\alpha_{inl}, \beta_{inl}, \sigma_{inl}, \tau_{inl}$	Constants determined from Eqs. (18-20)
γ_{pq}	Element of added mass matrix
δ_{il}	Kronecker's delta
ϵ	Nondimensionalized eccentricity; $e/(R_0 - R_1)$
λ_{01}	Coefficient in Eq. (50)
$\vec{v}$	Unit vector normal to cylinder surface
ρ	Mass density of fluid
Φ_i	Velocity potential associated with the motion of cylinder i assuming all other cylinders are stationary
Φ	Total velocity potential
ϕ_i	Normalized velocity potential of Φ_i
$\psi_n(z)$	Orthonormal function of cylinders in vacuo
ψ_{ij}	Angle between the x-axis and the vector from the center of cylinder i to that of cylinder j
$\bar{\omega}_{pn}$	nth natural frequency of cylinder p in vacuo
ω_{pn}	nth uncoupled natural frequency of cylinder p in fluid
Ω_{pn}	Coupled natural frequency of the p mode associated with the axial mode number n

Subscripts

$i, j, \ell = 0, 1, 2, \dots k$

$p, q = 0, 1, 2, \dots 2k$

$m = 0, 1, 2, \dots \infty$

$n = 1, 2, 3, \dots \infty$

Superscripts

i = Variables written in terms of coordinates associated with cylinder i

VIBRATION OF A GROUP OF CIRCULAR CYLINDERS IN A CONFINED FLUID

by

Ho Chung and Shoei-sheng Chen

ABSTRACT

This report presents an analytical method for evaluating the hydrodynamic masses of a group of circular cylinders immersed in a fluid contained in a cylinder. The analysis is based on the two dimensional potential flow theory. The fluid coupling effect among cylinders is taken into account; self-added masses and mutual-added masses for both inner and outer cylinders are evaluated. Based on the proposed method, the free vibration of two eccentric cylinders with a fluid-filled gap is analyzed as an example.

I. INTRODUCTION

The dynamic behavior of a group of cylinders submerged in a fluid has been of great interest to many engineers in recent years. In a group of cylinders, because of fluid coupling effects, the motion of any cylinder will excite the others and all cylinders will respond as a group rather than as an individual one. Therefore, a group of cylinders will have coupled natural modes in which all cylinders vibrate at the same frequency with definite phase relations among them. Coupled motions of multiple cylinders in infinite fluid are studied by several authors [1-12].* Studies of two cylinders located concentrically with a fluid-filled gap have also been made [13-14]. However, to the best of the authors' knowledge, coupled vibrations of eccentric cylinders and a group of cylinders in a confined fluid have not been reported. The objective of this report is to present a general method of analysis for coupled vibrations of multiple cylinders in a confined fluid. The results of this study have important application in the design evaluation of nuclear reactor internals and heat exchangers.

The fluid is assumed to be incompressible, inviscid and irrotational; thus, the potential flow theory is applied. The cylinders are assumed to be infinitely long and their axes are parallel to one another; i.e., the two dimensional problem is solved. The mathematical technique employed in this report is the method of coordinate transformations [11, 12]. The fluid velocity potential is expressed in terms of a series with unknown coefficients. The velocity potential of one coordinate system is then expressed in terms of the similar potential function of a second coordinate system using coordinate transformations. Unknown expansion coefficients of the series formulation are determined by matrix inversion of a truncated set of infinite equations obtained by imposing the prescribed boundary conditions. These coefficients are then used to calculate fluid pressure and hydrodynamic forces acting on

*Numbers in brackets designate References at end of report.

each cylinder. Once the hydrodynamic forces associated with the motions of each cylinder are determined, coupled vibrations of the cylinders can be studied in a straight forward manner.

After a general method of solution is presented, a few numerical examples are given and discussed in order to demonstrate the method. Numerical results for the added mass coefficients are given for three cases: (1) two eccentric cylinders with a fluid-filled gap, (2) two cylinders in a fluid contained in an outer cylinder, and (3) seven cylinders in a fluid-containing cylinder. The rate of convergence for the added mass coefficients is studied with respect to the number of terms used in calculations and compared for two typical cases with small and large gap sizes between inner cylinders. The effects on the added mass coefficients due to the variation of eccentricity for case (1), and due to the variation of radius of the containing cylinder for case (3) are studied. Natural frequencies and mode shapes for coupled vibrations of two eccentric cylinders with a fluid-filled gap are calculated and discussed.

II. ADDED MASS MATRIX

A. Formulation and Solution

Consider the motion of a group of k circular cylinders in a cylindrical container (Fig. 1). The container is filled with incompressible, inviscid and irrotational fluid. The axes of the cylinders are assumed to be perpendicular to the x - y plane. Let R_0 be the radius of the container and (X, Y) be global coordinates with the origin at the center of the container. Let R_j be the radius of cylinder j and (x_j, y_j) be the local coordinates associated with inner cylinder j .

The velocity potential associated with the motions of these cylinders can be written in terms of their own local coordinates. Assuming all inner cylinders are stationary, the velocity potential associated with the motion of the outer cylinder 0 is

$$\phi_0 = \sum_{n=1}^{\infty} \frac{r_0^n}{R_0^{n-1}} (a_{0n} \cos n\theta_0 + b_{0n} \sin n\theta_0) \quad (1)$$

The velocity potential for inner cylinder j assuming all other cylinders are stationary is

$$\phi_j = \sum_{n=1}^{\infty} \frac{R_j^{n+1}}{r_j^n} (a_{jn} \cos n\theta_j + b_{jn} \sin n\theta_j) \quad , \quad (j = 1, 2, 3, \dots, k) \quad (2)$$

In equations (1) and (2), (r_0, θ_0) and (r_j, θ_j) are cylindrical coordinates referred to the outer cylinder 0 and inner cylinder j respectively,

and a_{0n} , b_{0n} , a_{jn} and b_{jn} are arbitrary constants to be determined.

The total velocity potential is the sum of all the partial potentials generated by every cylinder, i.e.,

$$\phi = \phi_0 + \sum_{j=1}^k \phi_j \quad (3)$$

In order to impose the boundary conditions at a particular cylinder, the total velocity potential associated with all cylinders must be expressed

FIGURE 1. Schematic and Coordinate System for a Group of Circular Cylinders in a Fluid-Containing Cylinder

in terms of the coordinates of that cylinder. Therefore, it is necessary to acquire three transformation relationships for coordinates of the outer and inner cylinders; these transformations are accomplished by using Taylor series expansion.

Expansion of the function $[r_0 \exp(i\theta_0) - R_{0j} \exp(i\psi_{0j})]^{-n}$ in terms of Taylor series leads to the expressions of the coordinates of inner cylinder j written in terms of (r_0, θ_0) associated with the outer cylinder 0. The above function can be expanded in powers of either $r_0 \exp(i\theta_0)$ or $R_{0j} \exp(i\psi_{0j})$, i.e.,

$$\frac{\cos n\theta_j}{r_j^n} = \sum_{m=0}^{\infty} C_{mn} \frac{R_{0j}^m}{r_0^{m+n}} \cos[m\psi_{0j} - (m+n)\theta_0] , \quad (4)$$

$$\frac{\sin n\theta_j}{r_j^n} = - \sum_{m=0}^{\infty} C_{mn} \frac{R_{0j}^m}{r_0^{m+n}} \sin[m\psi_{0j} - (m+n)\theta_0] ,$$

(for $n = 1, 2, 3, \dots, \infty$)

or

$$\frac{\cos n\theta_j}{r_j^n} = (-1)^n \sum_{m=0}^{\infty} C_{mn} \frac{r_0^m}{R_{0j}^{m+n}} \cos[m\theta_0 - (m+n)\psi_{0j}] , \quad (5)$$

$$\frac{\sin n\theta_j}{r_j^n} = (-1)^{n+1} \sum_{m=0}^{\infty} C_{mn} \frac{r_0^m}{R_{0j}^{m+n}} \sin[m\theta_0 - (m+n)\psi_{0j}] ,$$

(for $n = 1, 2, 3, \dots, \infty$)

where

$$C_{mn} = \frac{(m+n-1)!}{m!(n-1)!}$$

and R_{0j} is the distance between the centers of the outer cylinder 0 and inner cylinder j , and ψ_{0j} is the angle between the x-axis and the vector from the center of the outer cylinder 0 to that of inner cylinder j . Any velocity potential ϕ_j in Eq. (2) can be written in terms of the coordinates (r_0, θ_0) associated with the outer cylinder 0 using the above relationships, i.e.,

$$\begin{aligned} \phi_j^0 = \sum_{n=1}^{\infty} \sum_{m=0}^{\infty} C_{mn} \frac{R_j^{n+1} r_0^m}{r_0^{m+n}} \{ a_{jn} \cos[m\psi_{0j} - (m+n)\theta_0] \\ - b_{jn} \sin[m\psi_{0j} - (m+n)\theta_0] \} , \quad (j = 1, 2, \dots, k) \end{aligned} \quad (6)$$

or

$$\begin{aligned} \phi_j^0 = \sum_{n=1}^{\infty} \sum_{m=0}^{\infty} (-1)^n C_{mn} \frac{R_j^{n+1} r_0^m}{R_{0j}^{m+n}} \{ a_{jn} \cos[m\theta_0 - (m+n)\psi_{0j}] \\ - b_{jn} \sin[m\theta_0 - (m+n)\psi_{0j}] \} , \quad (j = 1, 2, \dots, k) \end{aligned} \quad (7)$$

where the superscript 0 denotes a variable written in terms of the coordinates associated with the outer cylinder 0. If the origin of an inner cylinder j coincides with that of the outer cylinder, then, it becomes

$$\phi_j^0 = \sum_{n=1}^{\infty} \frac{R_j^{n+1}}{r_0^n} (a_{jn} \cos n\theta_0 + b_{jn} \sin n\theta_0) . \quad (8)$$

Expansion of the function $[r_i \exp(i\theta_i) + R_{0i} \exp(i\psi_{0i})]^n$ in terms of Taylor series leads to the following relationships of the coordinates (r_0, θ_0) of the outer cylinder written in terms of (r_i, θ_i) associated with inner cylinder i , i.e.,

$$r_0^n \cos n\theta_0 = \sum_{m=0}^n D_{mn} \frac{R_{0i}^n r_i^m}{R_{0i}^m} \cos[(n-m)\psi_{0i} + m\theta_i] ,$$

and

$$r_0^n \sin n\theta_0 = \sum_{m=0}^n D_{mn} \frac{R_{0i}^n r_i^m}{R_{0i}^m} \sin[(n-m)\psi_{0i} + m\theta_i] ,$$

(for $n = 0, 1, 2, \dots, \infty$)

where

$$D_{mn} = \frac{n!}{m!(n-m)!} .$$

The velocity potential ϕ_0 in Eq. (1) written in terms of the local coordinates associated with inner cylinder i can be now written

$$\phi_0^i = \sum_{n=1}^{\infty} \sum_{m=0}^n D_{mn} \frac{r_i^{m,n-m} R_0^{n-1}}{R_0^{n-1}} \{a_{0n} \cos[(n-m)\psi_{0i} + m\theta_i] + b_{0n} \sin[(n-m)\psi_{0i} + m\theta_i]\} , (i = 1, 2, \dots, k). \quad (10)$$

If the origin of the outer cylinder is the same as that of inner cylinder i , it becomes

$$\phi_0^i = \sum_{n=1}^{\infty} \frac{r_i^n}{R_0^{n-1}} (a_{0n} \cos n\theta_i + b_{0n} \sin n\theta_i) . \quad (11)$$

Finally the velocity potential ϕ_j in Eq. (2) can be expressed in terms of the local coordinates of cylinder i using the following relationships [12].

$$\frac{\cos n\theta_j}{r_j^n} = (-1)^n \sum_{m=0}^{\infty} C_{mn} \frac{r_i^m}{R_{ij}^{m+n}} \cos[m\theta_i - (m+n)\psi_{ij}] ,$$

and

$$\frac{\sin n\theta_j}{r_j^n} = (-1)^{n+1} \sum_{m=0}^{\infty} C_{mn} \frac{r_i^m}{R_{ij}^{m+n}} \sin[m\theta_i - (m+n)\psi_{ij}] , \quad (12)$$

(for $n = 1, 2, 3, \dots, \infty$)

where C_{mn} is defines previously, and R_{ij} and ψ_{ij} are defined in Fig. 1.

Thus, using Eqs. (2) and (12) gives

$$\phi_j^i = \sum_{n=1}^{\infty} \sum_{m=0}^{\infty} (-1)^n C_{mn} \frac{R_j^{n+1} r_i^m}{R_{ij}^{m+n}} \{a_{jn} \cos[m\theta_i - (m+n)\psi_{ij}] - b_{jn} \sin[m\theta_i - (m+n)\psi_{ij}]\} , (i, j = 1, 2, \dots, k). \quad (13)$$

It is necessary to consider two cases: (1) one of the inner cylinders is concentric with the outer cylinder; and (2) none of the inner cylinders are concentric with the outer cylinder. The former is the general case and treated in this report. Thus, the system consists of $k+1$ cylinders: cylinder 0 is the outer cylinder, cylinder 1 is the inner cylinder which is concentric with the outer cylinder, and the cylinders

2 ~ k are other inner cylinders. Note that case 2 may be treated as a special case of case 1. The total velocity potential (3) can be written as

$$\Phi^i = \Phi_i + \sum_{j=0}^{k*} \Phi_j^i, \quad (i=0,1,2,\dots,k) \quad (14)$$

where Σ^* denotes the summation for j from 0 to k except j = i.

The displacement components of cylinder i in the x and y directions are u_i and v_i , respectively. The fluid velocity component in radial direction is V and can be written in terms of the coordinates of cylinder i;

$$V^i = \frac{\partial \Phi^i}{\partial r_i}, \quad (i=0,1,2,\dots,k). \quad (15)$$

At the interface of the cylinders and fluid, the following conditions must be satisfied;

$$V^i \Big|_{r_i = R_i} = \frac{\partial u_i}{\partial t} \cos \theta_i + \frac{\partial v_i}{\partial t} \sin \theta_i, \quad (i=0,1,2,\dots,k). \quad (16)$$

Let the coefficients a_{in} and b_{in} be defined as follows:

$$a_{in} = \sum_{\ell=0}^k \left(\alpha_{in\ell} \frac{\partial u_\ell}{\partial t} + \sigma_{in\ell} \frac{\partial v_\ell}{\partial t} \right), \quad (17)$$

$$b_{in} = \sum_{\ell=0}^k \left(\tau_{in\ell} \frac{\partial u_\ell}{\partial t} + \beta_{in\ell} \frac{\partial v_\ell}{\partial t} \right),$$

$$(i=0, 1, 2, \dots, k),$$

where, $\alpha_{in\ell}$, $\beta_{in\ell}$, $\sigma_{in\ell}$ and $\tau_{in\ell}$ are solutions of the following system of algebraic equations. For i = 0, substituting equations (1), (2) and (6) into (14-16) yields

$$n\alpha_{0n\ell} - n \left(\frac{R_1}{R_0} \right)^{n+1} \alpha_{in\ell} - \sum_{j=2}^k \sum_{m=0}^{n-1} \frac{R_j^{n-m+1} R_{0j}^m}{R_0^{n+1}} \frac{n!}{m!(n-m-1)!} \quad (18)$$

$$\{ \alpha_{j(n-m)\ell} \cos m\psi_{0j} - \tau_{j(n-m)\ell} \sin m\psi_{0j} \} = \delta_{n1} \delta_{0\ell},$$

$$n\sigma_{On\ell} - n \left(\frac{R_1}{R_0} \right)^{n+1} \sigma_{ln\ell} - \sum_{j=2}^k \sum_{m=0}^{n-1} \frac{R_j^{n-m+1} R_{0j}^m}{R_0^{n+1}} \frac{n!}{m!(n-m-1)!}$$

$$\{\sigma_{j(n-m)\ell} \cos m\psi_{Oj} - \beta_{j(n-m)\ell} \sin m\psi_{Oj}\} = 0 ,$$

(18)

$$n\tau_{On\ell} - n \left(\frac{R_1}{R_0} \right)^{n+1} \tau_{ln\ell} - \sum_{j=2}^k \sum_{m=0}^{n-1} \frac{R_j^{n-m+1} R_{0j}^m}{R_0^{n+1}} \frac{n!}{m!(n-m-1)!}$$

(Contd.)

$$\{\alpha_{j(n-m)\ell} \sin m\psi_{Oj} + \tau_{j(n-m)\ell} \cos m\psi_{Oj}\} = 0 ,$$

$$n\beta_{On\ell} - n \left(\frac{R_1}{R_0} \right)^{n+1} \beta_{ln\ell} - \sum_{j=2}^k \sum_{m=0}^{n-1} \frac{R_j^{n-m+1} R_{0j}^m}{R_0^{n+1}} \frac{n!}{m!(n-m-1)!}$$

$$\{\sigma_{j(n-m)\ell} \sin m\psi_{Oj} + \beta_{j(n-m)\ell} \cos m\psi_{Oj}\} = \delta_{n1} \delta_{0\ell} ,$$

where

$$\ell = 0, 1, 2, \dots, k$$

$$n = 1, 2, 3, \dots, \infty$$

$$m = 0, 1, 2, \dots, (n-1) .$$

For $i = 1$, substituting equations (1), (2) and (7) into (14)-(16) yields

$$n \left(\frac{R_1}{R_0} \right)^{n-1} \alpha_{On\ell} - n\alpha_{ln\ell} + \sum_{j=2}^k \sum_{m=1}^{\infty} \frac{R_1^{n-1} R_j^{m+1}}{R_{0j}^{m+n}} \frac{(-1)^m (m+n-1)!}{(m-1)!(n-1)!}$$

$$\{\alpha_{jml} \cos (m+n)\psi_{Oj} + \tau_{jml} \sin (m+n)\psi_{Oj}\} = \delta_{n1} \delta_{1\ell} ,$$

$$n \left(\frac{R_1}{R_0} \right)^{n-1} \sigma_{On\ell} - n\sigma_{ln\ell} + \sum_{j=2}^k \sum_{m=1}^{\infty} \frac{R_1^{n-1} R_j^{m+1}}{R_{0j}^{m+n}} \frac{(-1)^m (m+n-1)!}{(m-1)!(n-1)!}$$

$$\{\sigma_{jml} \cos (m+n)\psi_{Oj} + \beta_{jml} \sin (m+n)\psi_{Oj}\} = 0 ,$$

(19)

$$n \left(\frac{R_1}{R_0} \right)^{n-1} \tau_{On\ell} - n\tau_{ln\ell} + \sum_{j=2}^k \sum_{m=1}^{\infty} \frac{R_1^{n-1} R_j^{m+1}}{R_{0j}^{m+n}} \frac{(-1)^m (m+n-1)!}{(m-1)!(n-1)!}$$

$$\{\alpha_{jml} \sin (m+n)\psi_{Oj} - \tau_{jml} \cos (m+n)\psi_{Oj}\} = 0 ,$$

$$n \left(\frac{R_1}{R_0} \right)^{n-1} \beta_{Onl} - n \beta_{lnl} + \sum_{j=2}^{k*} \sum_{m=1}^{\infty} \frac{R_1^{n-1} R_j^{m+1}}{R_{Oj}^{m+n}} \frac{(-1)^m (m+n-1)!}{(m-1)! (n-1)!} \quad (19)$$

(Contd.,)

$$\{\sigma_{jml} \sin (m+n) \psi_{Oj} - \beta_{jml} \cos (m+n) \psi_{Oj}\} = \delta_{nl} \delta_{1l} ,$$

where

$$l = 0, 1, 2, \dots, k$$

$$m, n = 1, 2, 3, \dots, \infty .$$

For $i \geq 2$, substituting equations (2), (10) and (13) into (14)-(16) yields

$$\begin{aligned} -n \alpha_{inl} + \sum_{m=1}^{\infty} \frac{R_{Oi}^{m-n} R_i^{n-1}}{R_0^{m-1}} \frac{m!}{(n-1)! (m-n)!} \{ \alpha_{Oml} \cos (m-n) \psi_{Oi} \\ + \tau_{Oml} \sin (m-n) \psi_{Oi} \} + \sum_{j=1}^{k*} \sum_{m=1}^{\infty} \frac{R_i^{n-1} R_j^{m+1}}{R_{ij}^{m+n}} \frac{(-1)^m (m+n-1)!}{(m-1)! (n-1)!} \\ \{ \alpha_{jml} \cos (m+n) \psi_{ij} + \tau_{jml} \sin (m+n) \psi_{ij} \} = \delta_{nl} \delta_{il} , \end{aligned}$$

$$\begin{aligned} -n \sigma_{inl} + \sum_{m=1}^{\infty} \frac{R_{Oi}^{m-n} R_i^{n-1}}{R_0^{m-1}} \frac{m!}{(n-1)! (m-n)!} \{ \sigma_{Oml} \cos (m-n) \psi_{Oi} \\ + \beta_{Oml} \sin (m-n) \psi_{Oi} \} + \sum_{j=1}^{k*} \sum_{m=1}^{\infty} \frac{R_i^{n-1} R_j^{m+1}}{R_{ij}^{m+n}} \frac{(-1)^m (m+n-1)!}{(m-1)! (n-1)!} \end{aligned} \quad (20)$$

$$\{ \sigma_{jml} \cos (m+n) \psi_{ij} + \beta_{jml} \sin (m+n) \psi_{ij} \} = 0 ,$$

$$\begin{aligned} -n \tau_{inl} + \sum_{m=1}^{\infty} \frac{R_{Oi}^{m-n} R_i^{n-1}}{R_0^{m-1}} \frac{m!}{(n-1)! (m-n)!} \{ -\alpha_{Oml} \sin (m-n) \psi_{Oi} \\ + \tau_{Oml} \cos (m-n) \psi_{Oi} \} + \sum_{j=1}^{k*} \sum_{m=1}^{\infty} \frac{R_i^{n-1} R_j^{m+1}}{R_{ij}^{m+n}} \frac{(-1)^m (m+n-1)!}{(m-1)! (n-1)!} \\ \{ \alpha_{jml} \sin (m+n) \psi_{ij} - \tau_{jml} \cos (m+n) \psi_{ij} \} = 0 , \end{aligned}$$

$$-n\beta_{inl} + \sum_{m=1}^{\infty} \frac{R_{Oi}^{m-n} R_i^{n-1}}{R_0^{m-1}} \frac{m!}{(n-1)!(m-n)!} \{-\sigma_{Oml} \sin(m-n)\psi_{Oi} + \beta_{Oml} \cos(m-n)\psi_{Oi}\} + \sum_{j=1}^k \sum_{m=1}^{\infty} \frac{R_i^{n-1} R_j^{m+1}}{R_{ij}^{m+n}} \frac{(-1)^m (m+n-1)!}{(m-1)!(n-1)!} \{\sigma_{jml} \sin(m+n)\psi_{ij} - \beta_{jml} \cos(m+n)\psi_{ij}\} = \delta_{nl} \delta_{il} \quad (20)$$

(Contd.)

$$\{\sigma_{jml} \sin(m+n)\psi_{ij} - \beta_{jml} \cos(m+n)\psi_{ij}\} = \delta_{nl} \delta_{il} \quad ,$$

where

$$i = 2, 3, 4, \dots, k$$

$$l = 0, 1, 2, \dots, k$$

$$m, n = 1, 2, 3, \dots, \infty$$

For the special case in which there is no concentric inner cylinder with the outer cylinder, equation (19) is not needed. Equations (18)-(20) form the systems of infinite equations for infinite numbers of the undetermined coefficients: α_{inl} , β_{inl} , δ_{inl} , and τ_{inl} . Taking a finite number of terms in the expressions of velocity potentials and coordinate transformations leads to the systems of finite equations. It will be shown that fast convergence is achieved and accurate solutions can be obtained with a few terms.

The fluid forces acting on the cylinders can be calculated from fluid pressure p ;

$$p = -\rho \frac{\partial \Phi}{\partial t} \quad , \quad (21)$$

where ρ is mass density of fluid. The two components in the x and y directions of fluid force acting on cylinder i are H_i and G_i ;

$$H_i = - \int_0^{2\pi} p^i \Big|_{r_i=R_i} \cdot R_i \cos \theta_i d\theta_i \quad ,$$

and

$$G_i = - \int_0^{2\pi} p^i \Big|_{r_i=R_i} \cdot R_i \sin \theta_i d\theta_i \quad .$$

(22)

$$(i = 0, 1, 2, \dots, k)$$

Using equations (14), and (17)-(22) yields

$$\begin{aligned}
 H_i &= -\rho\pi \sum_{\ell=0}^k \left(\frac{R_i + R_\ell}{2} \right)^2 \left(\alpha_{i\ell} \frac{\partial^2 u_\ell}{\partial t^2} + \sigma_{i\ell} \frac{\partial^2 v_\ell}{\partial t^2} \right), \\
 \text{and} \\
 G_i &= -\rho\pi \sum_{\ell=0}^k \left(\frac{R_i + R_\ell}{2} \right)^2 \left(\tau_{i\ell} \frac{\partial^2 u_\ell}{\partial t^2} + \beta_{i\ell} \frac{\partial^2 v_\ell}{\partial t^2} \right).
 \end{aligned} \tag{23}$$

(i = 0, 1, 2, ..., k)

Here the so-called added mass coefficients $\alpha_{i\ell}$, $\beta_{i\ell}$, $\sigma_{i\ell}$ and $\tau_{i\ell}$ are obtained as follows:

(1) For the outer cylinder (i = 0),

$$\begin{aligned}
 \alpha_{0\ell} &= \frac{4R_0^2}{(R_0 + R_\ell)^2} \sum_{i=0}^k \left(\frac{R_i}{R_0} \right)^2 \alpha_{i1\ell}, \\
 \beta_{0\ell} &= \frac{4R_0^2}{(R_0 + R_\ell)^2} \sum_{i=0}^k \left(\frac{R_i}{R_0} \right)^2 \beta_{i1\ell}, \\
 \sigma_{0\ell} &= \frac{4R_0^2}{(R_0 + R_\ell)^2} \sum_{i=0}^k \left(\frac{R_i}{R_0} \right)^2 \sigma_{i1\ell}, \\
 \tau_{0\ell} &= \frac{4R_0^2}{(R_0 + R_\ell)^2} \sum_{i=0}^k \left(\frac{R_i}{R_0} \right)^2 \tau_{i1\ell},
 \end{aligned} \tag{24}$$

(ℓ = 0, 1, 2, ..., k)

(2) For the inner cylinder (i = 1) concentric with the outer cylinder,

$$\begin{aligned}
 \alpha_{1\ell} &= -\frac{4R_1^2}{(R_1 + R_\ell)^2} \left[\alpha_{01\ell} + \alpha_{11\ell} + \sum_{n=1}^{\infty} \sum_{j=2}^k (-1)^n \left(\frac{R_j}{R_{0j}} \right)^{n+1} \right. \\
 &\quad \left. \{ \alpha_{jn\ell} \cos (n+1)\psi_{0j} + \tau_{jn\ell} \sin (n+1)\psi_{0j} \} \right], \\
 \beta_{1\ell} &= -\frac{4R_1^2}{(R_1 + R_\ell)^2} \left[\beta_{01\ell} + \beta_{11\ell} + \sum_{n=1}^{\infty} \sum_{j=2}^k (-1)^n \left(\frac{R_j}{R_{0j}} \right)^{n+1} \right. \\
 &\quad \left. \{ \sigma_{jn\ell} \sin (n+1)\psi_{0j} - \beta_{jn\ell} \cos (n+1)\psi_{0j} \} \right],
 \end{aligned} \tag{25}$$

$$\sigma_{1\ell} = -\frac{4R_1^2}{(R_1+R_\ell)^2} \left[\sigma_{01\ell} + \sigma_{11\ell} + \sum_{n=1}^{\infty} \sum_{j=2}^k (-1)^n \left(\frac{R_j}{R_{0j}} \right)^{n+1} \{ \sigma_{jn\ell} \cos (n+1)\psi_{0j} + \beta_{jn\ell} \sin (n+1)\psi_{0j} \} \right], \quad (25)$$

(Contd.)

$$\tau_{1\ell} = -\frac{4R_1^2}{(R_1+R_\ell)^2} \left[\tau_{01\ell} + \tau_{11\ell} + \sum_{n=1}^{\infty} \sum_{j=2}^k (-1)^n \left(\frac{R_j}{R_{0j}} \right)^{n+1} \{ \alpha_{jn\ell} \sin (n+1)\psi_{0j} - \tau_{jn\ell} \cos (n+1)\psi_{0j} \} \right],$$

$$(\ell = 0, 1, 2, \dots, k).$$

(3) For inner cylinders, $i = 2, 3, 4, \dots, k$,

$$\begin{aligned} \alpha_{i\ell} = & \frac{4R_i^2}{(R_i+R_\ell)^2} \left[-\alpha_{i1\ell} - \sum_{n=1}^{\infty} n \left(\frac{R_{0i}}{R_0} \right)^{n-1} \{ \alpha_{0n\ell} \cos (n-1)\psi_{0i} \right. \\ & + \tau_{0n\ell} \sin (n-1)\psi_{0i} \} - \sum_{n=1}^{\infty} \sum_{j=1}^{k*} (-1)^n \left(\frac{R_j}{R_{ij}} \right)^{n+1} \\ & \left. \{ \alpha_{jn\ell} \cos (n+1)\psi_{ij} + \tau_{jn\ell} \sin (n+1)\psi_{ij} \} \right], \\ \beta_{i\ell} = & \frac{4R_i^2}{(R_i+R_\ell)^2} \left[-\beta_{i1\ell} - \sum_{n=1}^{\infty} n \left(\frac{R_{0i}}{R_0} \right)^{n-1} \{ -\sigma_{0n\ell} \sin (n-1)\psi_{0i} \right. \\ & + \beta_{0n\ell} \cos (n-1)\psi_{0i} \} - \sum_{n=1}^{\infty} \sum_{j=1}^{k*} (-1)^n \left(\frac{R_j}{R_{ij}} \right)^{n+1} \\ & \left. \{ \sigma_{jn\ell} \sin (n+1)\psi_{ij} - \beta_{jn\ell} \cos (n+1)\psi_{ij} \} \right], \end{aligned} \quad (26)$$

$$\begin{aligned} \sigma_{i\ell} = & \frac{4R_i^2}{(R_i+R_\ell)^2} \left[-\sigma_{i1\ell} - \sum_{n=1}^{\infty} n \left(\frac{R_{0i}}{R_0} \right)^{n-1} \{ \sigma_{0n\ell} \cos (n-1)\psi_{0i} \right. \\ & + \beta_{0n\ell} \sin (n-1)\psi_{0i} \} - \sum_{n=1}^{\infty} \sum_{j=1}^{k*} (-1)^n \left(\frac{R_j}{R_{ij}} \right)^{n+1} \\ & \left. \{ \sigma_{jn\ell} \cos (n+1)\psi_{ij} + \beta_{jn\ell} \sin (n+1)\psi_{ij} \} \right], \end{aligned}$$

$$\tau_{i\ell} = \frac{4R_i^2}{(R_i+R_\ell)^2} \left[-\tau_{i1\ell} - \sum_{n=1}^{\infty} n \left(\frac{R_{0i}}{R_0} \right)^{n-1} \{ -\alpha_{0n\ell} \sin (n-1)\psi_{0i} \right.$$

$$\begin{aligned}
 & + \tau_{0nl} \cos (n-1)\psi_{0i} \} - \sum_{n=1}^{\infty} \sum_{j=1}^{k*} (-1)^n \left(\frac{R_j}{R_{ij}} \right)^{n+1} \\
 & \left\{ \alpha_{jnl} \sin (n+1)\psi_{ij} - \tau_{jnl} \cos (n+1)\psi_{ij} \right\} \quad (26) \\
 & \quad (l = 0, 1, 2, 3, \dots, k) \quad (\text{Contd.})
 \end{aligned}$$

α_{ii} , β_{ii} , σ_{ii} and τ_{ii} are self-added mass coefficients, which are proportional to the hydrodynamic force acting on cylinder i due to its own acceleration, while the others are mutual-added mass coefficients, which are proportional to the hydrodynamic force acting on a cylinder due to the acceleration of another cylinder.

B. Reciprocal Relations

Useful general reciprocal relationships regarding the hydrodynamic forces due to the movement of cylinders can be developed based on the theory of potential [15].

Let us consider the hydrodynamic force acting on cylinder l in the direction of $\vec{e}_l$ due to the movement of cylinder i in the direction of $\vec{e}_i$. Assuming all other cylinders are stationary except cylinder i , the hydrodynamic force can be written as follows,

$$F_{li} = -\gamma_{li} \frac{\partial^2 U_i}{\partial t^2}, \quad (27)$$

where

$$\gamma_{li} = - \iint_{S_l} \rho \phi_i \frac{\partial \phi_l}{\partial n} dS_l. \quad (28)$$

Here, ϕ_i and ϕ_ℓ are normalized velocity potentials associated with cylinder i and ℓ , (ϕ_i is the velocity potential for cylinder i having a unit acceleration) and U_i is the displacement of cylinder i in the direction of the vector $\vec{e}_i$. ν is a unit vector normal to the cylinder surface toward the fluid and S_ℓ is the surface of cylinder ℓ .

Similarly, consider the case that all cylinders are stationary except cylinder ℓ moving in the direction of $\vec{e}_\ell$. The hydrodynamic force exerting on cylinder i in the direction of $\vec{e}_i$ is

$$F_{i\ell} = -\gamma_{i\ell} \frac{\partial^2 U_\ell}{\partial t^2}, \quad (29)$$

where

$$\gamma_{i\ell} = -\iint_{S_i} \rho \phi_\ell \frac{\partial \phi_i}{\partial \nu} dS_i. \quad (30)$$

As the velocity potentials ϕ_i and ϕ_ℓ are harmonic functions, Green's theorem prevails [15], i.e.,

$$\iint_S \left(\phi_i \frac{\partial \phi_\ell}{\partial \nu} - \phi_\ell \frac{\partial \phi_i}{\partial \nu} \right) dS = 0. \quad (31)$$

This equation holds for any closed surface S within a region in which ϕ_i and ϕ_ℓ are harmonic functions. We may choose $S = S_0$ which is the inner surface of the outer cylinder, then it follows that

$$\begin{aligned} & \iint_{S_\ell} \phi_i \frac{\partial \phi_\ell}{\partial \nu} dS_\ell - \iint_{S_i} \phi_\ell \frac{\partial \phi_i}{\partial \nu} dS_i \\ &= \iint_{S_0} \left(\phi_i \frac{\partial \phi_\ell}{\partial \nu} - \phi_\ell \frac{\partial \phi_i}{\partial \nu} \right) dS_0 = 0. \end{aligned} \quad (32)$$

If ϕ_ℓ is associated with the outer cylinder, letting $S = S_0$ in equation (30) yields

$$\iint_{S_0} \phi_i \frac{\partial \phi_0}{\partial v} dS_0 - \iint_{S_i} \phi_0 \frac{\partial \phi_i}{\partial v} dS_i = 0 \quad (33)$$

Therefore from equations (28), (30), (32) and (33)

$$\gamma_{i\ell} = \gamma_{\ell i} \quad (i, \ell = 0, 1, 2, \dots, k) \quad (34)$$

This relationship delivers a physical meaning that the hydrodynamic force acting on cylinder ℓ in the $\vec{e}_\ell$ direction due to a unit acceleration of cylinder i in the $\vec{e}_i$ direction is equal to the hydrodynamic force acting on cylinder i in the $\vec{e}_i$ direction due to a unit acceleration of cylinder ℓ in the $\vec{e}_\ell$ direction. This general reciprocal relationship is valid between any pair of cylinders including inner and outer cylinders.

The reciprocal relations of the added mass coefficients defined in section II-A are generated from equation (34) as special cases. When $\vec{e}_i$ and $\vec{e}_\ell$ are equal, and if they are in x-direction

$$\alpha_{i\ell} = \alpha_{\ell i} \quad (35)$$

if they are in y-direction

$$\beta_{i\ell} = \beta_{\ell i} \quad (36)$$

When $\vec{e}_i$ is in x-direction and $\vec{e}_\ell$ is in y-direction, or vice versa

$$\sigma_{i\ell} = \tau_{\ell i} \quad (37)$$

The added mass coefficients $\alpha_{i\ell}$, $\beta_{i\ell}$, $\sigma_{i\ell}$ and $\tau_{i\ell}$ can be combined to form an added mass matrix γ_{pq} , i.e.,

$$[\gamma_{pq}] = \begin{bmatrix} \rho\pi \left(\frac{R_i + R_\ell}{2}\right)^2 \alpha_{i\ell} & \rho\pi \left(\frac{R_i + R_\ell}{2}\right)^2 \sigma_{i\ell} \\ \rho\pi \left(\frac{R_i + R_\ell}{2}\right)^2 \tau_{i\ell} & \rho\pi \left(\frac{R_i + R_\ell}{2}\right)^2 \beta_{i\ell} \end{bmatrix} \quad (38)$$

$$(p, q = 0, 1, 2, \dots, 2k+1).$$

Since γ_{pq} is symmetric, for a group of k cylinders contained in an outer cylinder, there are $(k+1)(2k+3)$ independent added mass components. We

can also find a group of $2(k+1)$ axes as the principal axes of added mass coefficient such that

$$\gamma_{pq} = 0 \quad \text{for } p \neq q \quad . \quad (39)$$

The principal values of added mass matrix may be called effective added masses for the system [12].

C. Numerical Results

The preceding analytical method to evaluate the added mass matrix was programmed (AMASS) on a digital computer and listed in the Appendix of this report. This program can be used to calculate all elements of the added mass matrix for a group of cylinders submerged in a fluid-containing cylinder. The cylinders may have different radii and may be arranged in arbitrary pattern; however, all cylinders must be parallel to one another.

Added mass coefficients are written in terms of infinite series; only a limited number of terms is needed to give results with sufficient accuracy. In order to check the rate of convergence of the solution, the added mass coefficients for two cylinders submerged in a fluid-containing cylinder are shown in Fig. 2 as functions of the number of terms n taken in calculations. The rate of convergence is much faster in the case of widely-spaced inner cylinders than in the closely-spaced case. In general, $n = 10$ will give sufficiently accurate solutions in practical situations. In the following calculations, the number of terms are taken to be 10.

Table 1 and Fig. 3 show the added mass coefficients as functions of the eccentricity of two eccentric cylinders with a fluid-filled gap. As the eccentricity increases the magnitude of all added mass coefficients increase. It is interesting to note that the self-added mass coefficients of the inner cylinder are strongly influenced by eccentricity and the mutual-added mass coefficients have also considerable dependence on eccentricity. However, the variation of the self-added mass coefficients

FIGURE 2. Variations of Added Mass Coefficients with the Number of Terms n Used in Calculations

Table 1. Added Mass Coefficients for Two Eccentric Cylinders with a Fluid-Filled Gap

Eccentricity (ϵ)	α_{00}	α_{11}	α_{12}
0	1.667	1.667	-1.185
0.2	1.672	1.686	-1.194
0.4	1.688	1.751	-1.223
0.6	1.722	1.889	-1.284
0.8	1.799	2.196	-1.420
0.9	1.884	2.537	-1.572
0.95	1.966	2.865	-1.718
0.97	2.020	3.080	-1.813
0.99	2.104	3.414	-1.962
0.999	2.170	3.681	-2.081

where $R_0/R_1 = 2$, $\epsilon = e/(R_0 - R_1)$

$$\alpha_{ij} = \beta_{ij}, \quad \sigma_{ij} = \tau_{ij} = 0, \quad (i, j = 0, 1)$$

FIGURE 3. Added Mass Coefficients for Two Eccentric Cylinders with a Fluid-Filled Gap

of outer cylinder with the eccentricity is relatively small, and is negligible in the case of $R_0/R_1 = 4$.

The added mass coefficients for a seven-cylinder bundle in a fluid-containing cylinder are shown in Table 2 and Fig. 4. The arrangement of the inner seven cylinders is fixed, while the radius of the outer cylinder is varied in order to investigate the influence of the gap size on the added mass coefficients. The self-added mass coefficients associated with the innermost cylinder 1, the inner cylinder 4 and the outer cylinder 0 are presented. As the gap size increases all of them decrease; specifically α_{00} approaches 1, whereas α_{11} and α_{44} approach the asymptotic values for the case of seven cylinders in an infinite fluid medium. It is interesting to note that the sensitivities of α_{11} and α_{44} to variations of the gap size are very similar to each other even though the cylinder 1 is surrounded by more fixed cylinders. Among the self-added mass coefficients considered, α_{00} is most sensitive to gap size. The mutual added mass coefficients, α_{01} , α_{04} and α_{14} are also presented. As the gap size increases the magnitudes of α_{01} and α_{04} decrease and finally approach zero, yet the magnitude of α_{14} increases and approaches the asymptote for the case of infinite fluid. These results reveal that as the gap size increases the coupling between the inner cylinders and the outer cylinder becomes smaller, and the coupling between inner cylinders 1 and 4 becomes larger. This study also shows that the solutions based on the assumption of infinite fluid medium are not sufficiently accurate for the case of G/R , say less than 5.

Table 2. Variation of Added Mass Coefficients for a Seven Cylinder Bundle in a Fluid-Containing Cylinder

G/R	α_{00}	α_{11}	α_{44}	α_{01}	α_{04}	α_{14}
0.1	7.084	5.129	4.070	-2.211	-1.545	-0.944
0.2	5.571	4.826	3.712	-1.699	-1.200	-1.114
0.3	4.708	4.653	3.510	-1.402	-0.997	-1.214
0.4	4.127	4.538	3.378	-1.200	-0.857	-1.284
0.5	3.702	4.454	3.284	-1.051	-0.753	-1.335
0.6	3.375	4.389	3.214	-0.935	-0.672	-1.375
0.7	3.115	4.339	3.159	-0.843	-0.607	-1.408
0.8	2.902	4.297	3.116	-0.766	-0.553	-1.435
0.9	2.725	4.263	3.081	-0.702	-0.507	-1.458
1.0	2.575	4.234	3.052	-0.647	-0.468	-1.477
1.5	2.075	4.139	2.962	-0.461	-0.334	-1.542
2.0	1.795	4.086	2.916	-0.353	-0.256	-1.580
3.0	1.496	4.030	2.871	-0.233	-0.169	-1.620
4.0	1.344	4.002	2.851	-0.168	-0.122	-1.641
5.0	1.254	3.985	2.839	-0.128	-0.093	-1.653
10.0	1.090	3.954	2.820	-0.049	-0.036	-1.675
20.0	1.028	3.943	2.814	-0.016	-0.012	-1.683
30.0	1.014	3.940	2.812	-0.008	-0.006	-1.685
50.0	1.002	3.938	2.811	-0.001	-0.001	-1.686
100.0	1.001	3.937	2.811	-0.0007	-0.0009	-1.687
∞	1.000	3.936	2.810	0	0	-1.687

FIGURE 4. Added Mass Coefficients for Two Eccentric Cylinders with a Fluid-Filled Gap

III. VIBRATION OF A GROUP OF CYLINDERS

As discussed in earlier chapters, added mass matrix can accurately be obtained for a group of circular cylinders submerged in a confined liquid; the cylinders may have different radii and can be arranged in an arbitrary manner as long as they are parallel to one another. The added mass matrix can be used to study the free and forced vibration of cylinders. In this section, a frequency equation is derived for a group of cylinders with the same boundary conditions and the same length, and numerical results are presented for free vibration of two eccentric cylinders with a fluid-filled gap.

A. Frequency Equation

Motions of cylinders consist of displacements along the x-axis and y-axis. Assuming the fluid is stationary and neglecting the effects of fluid static pressure, damping, drag force and gravity effect the equations of motions for a group of k cylinders in a fluid-containing cylinder are as follows:

$$E_p I_p \frac{\partial^4 u_p}{\partial z^4} + m_p \frac{\partial^2 u_p}{\partial t^2} + \sum_{q=0}^{2k+1} \gamma_{pq} \frac{\partial^2 u_q}{\partial t^2} = f_p, \quad (40)$$

$$(p, q = 0, 1, 2, \dots, 2k+1)$$

where the subscripts p and q denote variables associated with cylinders p and q in the x-z plane, while p+k+1 and q+k+1 in the y-z plane. $E_p I_p$ is flexural rigidity, m_p is mass per unit length, f_p is external excitation force, and γ_{pq} is the element of added mass matrix defined in equation (38).

When all cylinders are of the same length and have the same type of boundary conditions, the displacement of any cylinder can be written as

$$u_p(z, t) = \sum_{n=1}^{\infty} h_{pn}(t) \psi_n(z), \quad (41)$$

where $\psi_n(z)$ is the nth orthonormal function of the cylinders in vacuo.

Using equations (40) and (41) yields

$$m_p \ddot{h}_{pn} + \sum_{q=0}^{2k} \gamma_{pq} \ddot{h}_{qn} + m_p \bar{\omega}_{pn}^2 h_{pn} = f_{pn} \quad , \quad (42)$$

$$(p, q = 0, 1, 2, \dots, 2k+1), \quad (n = 1, 2, 3, \dots, \infty)$$

where

$$f_{pn} = \frac{1}{\ell} \int_0^\ell f_p \psi_n dz \quad , \quad \bar{\omega}_{pn}^2 = \frac{E_p I_p}{m_p} \frac{\psi_n''''}{\psi_n} \quad .$$

Here $\bar{\omega}_{pn}$ is the nth natural frequency of the cylinder p in vacuo and f_{pn} is the generalized external force. Note that equations (42) can be applied to all values of n. For each n, there are coupled equations the number of which is twice the number of cylinders. However, there is no coupling among the equations for different n. This is true for a group of cylinders with the same type of boundary conditions and of the same length. For a given n, equations (42) may be written in matrix form,

$$[M]\{\ddot{h}\} + [K]\{h\} = \{F\} \quad , \quad (43)$$

where M is symmetric square matrix and K is diagonal matrix. The elements of these matrices are as follows:

$$\begin{aligned} m_{pq} &= m_p \delta_{pq} + \gamma_{pq} \quad , \\ k_{pq} &= m_p \bar{\omega}_{pn}^2 \delta_{pq} \quad , \end{aligned} \quad (44)$$

$$(p, q = 0, 1, 2, \dots, 2k+1) \quad .$$

For free vibration, neglect external forcing terms, and let

$$\{h\} = \{\bar{h}\} \exp(i\Omega t) \quad . \quad (45)$$

The coupled natural frequency Ω and the coupled normal modes $\{\bar{h}\}$ of the system are computed from the homogeneous equations

$$[[K] - \Omega^2 [M]]\{\bar{h}\} = 0 \quad . \quad (46)$$

B. Sample Problem: Free Vibration of Two Eccentric Cylinders with a Fluid-Filled Gap

As an example, consider the motion of two eccentric cylinders with a fluid-filled gap as illustrated in Fig. 5. The axes of the cylinders are located on the x-z plane and parallel to the z-axis. In this case, it is found that

$$\begin{aligned} \alpha_{00} &= \beta_{00} , \\ \alpha_{11} &= \beta_{11} , \\ \alpha_{01} &= \alpha_{10} = \beta_{01} = \beta_{10} , \\ \sigma_{jl} &= \tau_{jl} = 0 , \quad (j, l = 0, 1) . \end{aligned} \tag{47}$$

Hence, the added matrix can be written

$$[\gamma_{pq}] = \rho\pi \begin{bmatrix} R_0^2 \alpha_{00} & \left(\frac{R_0 + R_1}{2}\right)^2 \alpha_{01} & 0 & 0 \\ \left(\frac{R_0 + R_1}{2}\right)^2 \alpha_{01} & R_1^2 \alpha_{11} & 0 & 0 \\ 0 & 0 & R_0^2 \alpha_{00} & \left(\frac{R_0 + R_1}{2}\right)^2 \alpha_{01} \\ 0 & 0 & \left(\frac{R_0 + R_1}{2}\right)^2 \alpha_{01} & R_1^2 \alpha_{11} \end{bmatrix} . \tag{48}$$

Examining this added mass matrix we may conclude that the x-z plane and the y-z plane motions can be considered separately. For the x-z plane motion equation (46) becomes

$$\begin{bmatrix} m_0 \bar{\omega}_{0n}^2 - \Omega^2 (m_0 + \gamma_{00}) & -\Omega^2 \gamma_{01} \\ -\Omega^2 \gamma_{01} & m_1 \bar{\omega}_{1n}^2 - \Omega^2 (m_1 + \gamma_{11}) \end{bmatrix} \begin{Bmatrix} \bar{h}_{0n} \\ \bar{h}_{1n} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \end{Bmatrix} . \tag{49}$$

The frequency equation for the coupled modes yields

$$(1 - \lambda_{01})\Omega^4 - (\omega_{0n}^2 + \omega_{1n}^2)\Omega^2 + \omega_{0n}^2 \omega_{1n}^2 = 0 , \tag{50}$$

FIGURE 5. Two Eccentric Cylinders with a Fluid-Filled Gap

where

$$\lambda_{01} = \frac{\gamma_{01}\gamma_{10}}{(m_0 + \gamma_{00})(m_1 + \gamma_{11})},$$

$$\omega_{pn} = \bar{\omega}_{pn} \sqrt{\frac{m_p}{m_p + \gamma_{pp}}}, \quad (p = 0, 1).$$

Here ω_{0n} and ω_{1n} are the uncoupled natural frequencies for each cylinder.

The coupled natural frequencies Ω_{1n} and Ω_{2n} are found from equation (50),

$$\Omega_{1n} = \left\{ (\omega_{1n}^2 + \omega_{2n}^2) - [(\omega_{1n}^2 - \omega_{2n}^2)^2 + 4\lambda_{01}\omega_{1n}^2\omega_{2n}^2]^{1/2} \right\}^{1/2} / [2(1 - \lambda_{01})]^{1/2},$$

and

(51)

$$\Omega_{2n} = \left\{ (\omega_{1n}^2 + \omega_{2n}^2) + [(\omega_{1n}^2 - \omega_{2n}^2)^2 + 4\lambda_{01}\omega_{1n}^2\omega_{2n}^2]^{1/2} \right\}^{1/2} / [2(1 - \lambda_{01})]^{1/2}.$$

For each n there are two coupled normal modes. The amplitude ratio $\bar{h}_{1n}/\bar{h}_{0n}$ is given by

$$\frac{\bar{h}_{1n}}{\bar{h}_{0n}} = \frac{\omega_{0n}^2 - \Omega^2 (m_0 + \gamma_{00})}{\Omega^2 \gamma_{01}}. \quad (52)$$

Natural frequencies for the y-z plane motion can be found in an analogous manner; the results are exactly the same as the x-z plane motion.

Numerical results presented here are based on two eccentric stainless steel tubes with a water-filled gap. Both tubes have the same length of 1.27 m (50 in.) and wall thickness of 0.15875 cm (0.0625 in.). The radii of outer and inner tube are 5.08 cm (2 in.) and 2.54 cm (1 in.) respectively. The distance between the centers of two cylinders is allowed to vary in order to investigate the effects of eccentricity on natural frequencies.

Table 3 and Fig. 6 summarize the results. For both cases of x-z plane and y-z plane vibrations, the lower frequency is associated with the mode in which two cylinders move out-of-phase, while the higher frequency is associated with in-phase mode. Fig. 6 shows the lowest two natural frequencies ($n=1$) for uncoupled as well as coupled modes. It can be also seen from Figure 6 and Table 3 that for each n the frequencies for the first coupled modes

Table 3. Natural Frequencies (Hz) for Two Eccentric Cylinders with a Fluid-Filled Gap

n	ϵ	Uncoupled Vibration		Coupled Vibration	
		Cylinder 0	Cylinder 1	First Mode	Second Mode
1	0	83.660	52.279	48.571	108.54
	0.1	83.637	52.232	48.529	108.54
	0.2	83.566	52.087	48.400	108.53
	0.3	83.442	51.836	48.177	108.51
	0.4	83.254	51.461	47.843	108.47
	0.5	82.985	50.934	47.372	108.43
	0.6	82.604	50.205	46.719	108.37
	0.7	82.053	49.188	45.808	108.29
	0.8	81.211	47.714	44.481	108.17
	0.9	79.747	45.344	42.338	108.00
	0.95	78.428	43.392	40.564	107.88
	0.975	77.394	41.967	39.263	107.79
	0.995	76.169	40.384	37.815	107.69
2	0	334.64	209.12	194.28	434.18
	0.1	334.55	208.93	194.12	434.16
	0.2	334.27	208.35	193.60	434.11
	0.3	333.77	207.35	192.71	434.02
	0.4	333.02	205.85	191.37	433.89
	0.5	331.94	203.74	189.49	433.71
	0.6	330.41	200.82	186.88	433.47
	0.7	328.21	196.75	183.23	433.14
	0.8	324.85	190.86	177.93	432.69
	0.9	318.99	181.37	169.35	432.02
	0.95	313.71	173.57	162.25	431.50
	0.975	309.57	167.87	157.05	431.15
	0.995	304.68	161.53	151.26	430.78
3	0	752.94	470.51	437.14	976.89
	0.1	752.74	470.09	436.76	976.86
	0.2	752.10	468.79	435.60	976.74
	0.3	750.98	466.53	433.59	976.55
	0.4	749.29	463.15	430.58	976.25

Table 3. Natural Frequencies (Hz) for Two Eccentric Cylinders with a Fluid-Filled Gap (Contd.)

n	ϵ	Uncoupled Vibration		Coupled Vibration	
		Cylinder 0	Cylinder 1	First Mode	Second Mode
3	0.5	746.87	458.40	426.34	975.85
	0.6	743.43	451.84	420.47	975.31
	0.7	738.47	442.70	412.27	974.58
	0.8	730.90	429.43	400.33	973.56
	0.9	717.73	408.09	381.04	972.04
	0.95	705.85	390.53	365.07	970.88
	0.975	696.54	377.70	353.37	970.08
	0.995	685.52	363.45	340.33	969.25

$$R_0 = 5.08 \text{ cm (2 in.)}$$

$$R_1 = 2.54 \text{ cm (1 in.)}$$

$$h_0 = h_1 = 0.15875 \text{ cm (0.0625 in.)}$$

$$\ell_0 = \ell_1 = 127 \text{ cm (50 in.)}$$

$$\rho = 8.015 \times 10^3 \text{ Kg/m}^3 \quad (7.5 \times 10^{-4} \text{ lb-sec}^2/\text{in}^4)$$

$$E = 2.017 \times 10^{11} \text{ Pa (3.0} \times 10^7 \text{ psi)}$$

$$\rho_f = 9.982 \times 10^2 \text{ Kg/m}^3 \quad (9.34 \times 10^{-5} \text{ lb-sec}^2/\text{in}^4)$$

FIGURE 6. Natural Frequencies for Two Eccentric Cylinders with a Fluid-Filled Gap as Functions of Eccentricity

(out-of-phase modes) are lower than either of the uncoupled natural frequencies, while the frequencies for the second coupled modes (in-phase modes) are higher than either of the uncoupled natural frequencies.

It is also interesting to note the effects of eccentricity on coupled and uncoupled modes. For coupled frequencies the effects are pronounced for the out-of-phase modes, but these effects are much smaller and considered to be negligible for the in-phase modes. However, for uncoupled vibrations the effects of eccentricity remain comparable for both cylinders. Fig. 6 also reveals that as eccentricity becomes larger, its influence on frequencies becomes larger.

IV. CONCLUSIONS

In this report, a general method of analysis is presented for coupled motions of a group of cylinders in a fluid-containing cylinder; the coupling effects are accounted for using self- and mutual-added mass coefficients of cylinders. The method can be applied to a group of cylinders with different radii. These cylinders may be arranged arbitrarily as long as they are parallel to one another. With this method of analysis, free and forced vibrations of a group of cylinders in a fluid-containing cylinder can readily be analyzed.

The analysis is based on the two dimensional flow theory. In many practical situations, the displacement of the cylinders are much smaller than the radius. Therefore, the potential flow theory is applicable. Furthermore, many system components, such as nuclear fuel bundles and heat exchanger tubes are long enough such that the hydrodynamic forces based on the two dimensional theory are sufficiently accurate.

Numerical results are given for a few selected problems. From the study of seven cylinders in a fluid-containing cylinder, it is seen that the influence of the outer cylinder on the motions of a group of inner cylinders is similar to that of two concentric cylinders. When the outer cylinder is relatively close to the inner cylinders, the coupling effects become pronounced and have to be considered. For the problem of two eccentric cylinders with a fluid-filled gap, the self-added mass coefficient of the inner cylinder is sensitive to the eccentricity of cylinders. The effects of eccentricity are also found to be distinct for the out-of-phase modes of coupled vibrations while they are almost negligible for the in-phase modes.

ACKNOWLEDGMENT

This work was performed under the sponsorship of the U. S. Energy Research and Development Administration.

REFERENCES

1. Livesey, J. L., and Dye, C. F., "Vortex Excited Vibration of a Heat Exchanger Tube Row," Journal of Mechanical Engineering Science, 4(4), 1962, pp. 349-352.
2. Laird, A. D. K., and Warren, R. P., "Groups of Vertical Cylinders Oscillating in Water," Journal of Engineering Mechanics Division, Proceedings ASCE, Vol. 89(EM 1), February, 1963, pp. 25-35.
3. Kito, F., "On Vibration of Two Circular Cylinders, which are Immersed in a Water Region of Infinite Extent," Journal of Society Naval Architecture in Japan, Vol. 122, 1967, pp. 1-9.
4. Mazur, V. Y., "Motion of Two Circular Cylinders in an Ideal Fluid," Izvestiya Akademii Nauk SSSR, Mekhanika Zhidkosti i Gaza, No. 6, 1970, pp. 80-84.
5. Connors, H. J., Jr., "Fluidelastic Vibration of Tube Arrays Excited by Cross Flow," Flow Induced Vibration in Heat Exchangers, ASME publication, 1970, pp. 42-56.
6. Shimogo, T., Inui, T., "Coupled Vibration of Many Elastic Circular Bars in Water," Proceedings 21st Japan National Congress for Applied Mechanics, 1971, pp. 495-505.
7. Dalton, C., and Helfinstine, R. A., "Potential Flow Past a Group of Circular Cylinders," Journal of Basic Engineering, Trans. ASME, Vol. 93, December, 1971, pp. 636-642.
8. Shimogo, T., Niino, T., and Setogawa, S., "Coupled Vibration of Elastic Circular Bars in Viscous Fluid," ASME Paper 75-DET-76, 1975.
9. Moretti, P. M., and Lowery, R. L., "Hydrodynamic Inertia Coefficients for a Tube Surrounded by Rigid Tubes," ASME Paper 75-PVP-47, 1975.
10. Chen, S. S., "Dynamic Response of Two Parallel Circular Cylinders in a Liquid," Journal of Pressure Vessel Technology, Trans. ASME, Vol. 97(2), 1975, pp. 77-83.
11. Chen, S. S., "Vibration of a Row of Circular Cylinders in a Liquid," Journal of Engineering for Industry, Trans. ASME, Vol. 97, 4, 1975, pp. 1212-1218.
12. Chen, S. S., "Vibration of Fuel Bundles," Nuclear Engineering and Design; Vol. 35, 1975, pp. 399-422.
13. Fritz, R. J., "The Effect of Liquids on the Dynamic Motions of Immersed Solids," ASME Paper No. 71-Vibr-100, 1971.

REFERENCES (Cont.d)

14. Chen, S. S., "Dynamics of a Rod-Shell System Conveying Fluid," Nuclear Engineering and Design, Vol. 30, 1974, pp. 223-233.
15. MacMillan, W. D., The Theory of Potential, Dover, New York, 1958.

APPENDIX: Computer Program (AMASS)

This appendix gives a list of the computer program, AMASS, which was used to calculate the added mass coefficients for this report. This program can be used for a group of cylinders immersed either in a fluid-containing cylinder or in an infinite fluid medium. The computer program is written in Fortran IV for IBM/370 computer system. The program is not necessarily written in an optimal manner in terms of computing time.

*** SUBROUTINE AMASS ***

ADDED MASS COEFFICIENTS OF A GROUP OF CIRCULAR
CYLINDERS IN A CONFINED FLUID

THIS PROGRAM CALCULATES ADDED MASS COEFFICIENTS OF A GROUP OF CIRCULAR
CYLINDERS IMMersed IN A FLUID CONTAINED IN A CYLINDER OR IN AN INFINITE
FLUID MEDIUM

INPUT VARIABLES

NNN: NUMBER OF TERMS USED (NNN=10 WILL GIVE RESULTS WITH SUFFICIENT
ACCURACY IN GENERAL)
KKI: TOTAL NUMBER OF CYLINDERS INCLUDING THE OUTER CYLINDER
ICLK: IF ICLK=1, GENERAL CASE WITH OUTER, CONCENTRIC & NON-CONCENTRIC
INNER CYLINDERS, IK=0
IF ICLK=2, OUTER & NON-CONCENTRIC INNER CYLINDERS, IK=1
IF ICLK=3, NO OUTER & CONCENTRIC INNER CYLINDERS; INFINITE
FLUID, IK=2
RA(I): RADIUS OF CYLINDER I
XA(I),YA(I): COORDINATES OF CYLINDER I
** INPUT SEQUENCE OF CYLINDER GEOMETRIES **
OUTER CYLINDER, CONCENTRIC INNER CYLINDER & OTHER CYLINDERS

OUTPUT VARIABLES

ALP(I,J),BET(I,J),SIG(I,J),TAU(I,J): ADDED MASS COEFFICIENTS

** DIMENSION SPECIFICATIONS **

(KKI) RA,XA,YA
(KKK) R,X,Y
(KKI,KKI) RAIJ,PHYA,ALP,BET,SIG,TAU
(KKK,KKK) RIJ,PHY
(KKI,NNN,KKI) AL,BE,SI,TA,H
(KKK,NNN,KKK,NNN) HA,BB,CC,DD
(KN+2,KN+2) E
(KN+2,KKK) F
KKK=KKI+IK
KN=KKK+NNN

SUBROUTINE AMASS(NNN,KKI,ICLK,RA,XA,YA,ALP,BET,SIG,TAU)
DIMENSION RA(8),XA(8),YA(8),R(8),X(8),Y(8)
DIMENSION RAIJ(8,8),PHYA(8,8),RIJ(8,8),PHY(8,8)
DIMENSION AA(8,10,8,10),BB(8,10,8,10)
DIMENSION CC(8,10,8,10),DD(8,10,8,10)
DIMENSION H(8,10,8),E(160,160),F(160,8)
DIMENSION AL(8,10,8),BE(8,10,8),SI(8,10,8),TA(8,10,8)
DIMENSION ALP(8,8),BET(8,8),SIG(8,8),TAU(8,8)
GO TO (4001,4002,4003),ICLK

4001 IK=0
IKK=2

```

        GO TO 4004
4002  IK=1
      IKK=1
      GO TO 4004
4003  IK=2
      IKK=0
4004  KKK=KKI+IK
C ** CLEAR WORK SPACES **
      DO 4005 I=1, KKK
        R(I) =0.0
        X(I) =0.0
        Y(I) =0.0
      DO 4005 J=1, KKK
        RIJ(I, J)=0.0
        PHY(I, J)=0.0
      DO 4005 N=1, NNN
      DO 4005 M=1, NNN
        RA(I, N, J, M)=0.0
        BB(I, N, J, M)=0.0
        CC(I, N, J, M)=0.0
4005  DD(I, N, J, M)=0.0
C ** GO TO INDEX KKK FROM KKI **
      GO TO (4031, 40331, 4033), ICHK
4031  DO 4032 I=1, KKK
        X(I)=XA(I)
        Y(I)=YA(I)
        R(I)=RA(I)
      DO 4032 J=1, KKK
        RIJ(I, J)=RAIJ(I, J)
4032  PHY(I, J)=PHYA(I, J)
      GO TO 4040
40331 X(I)=XA(I)
        Y(I)=YA(I)
        R(I)=RA(I)
        RIJ(1, 1)=RAIJ(1, 1)
        PHY(1, 1)=PHYA(1, 1)
4033  DO 4036 I=3, KKK
        IIK=I-IK
        X(I)=XA(IIK)
        Y(I)=YA(IIK)
        R(I)=RA(IIK)
      GO TO (4034, 4035), IK
4034  IM1=I-1
        RIJ(I, 1)=RAIJ(IM1, 1)
        RIJ(1, I)=RAIJ(1, IM1)
        PHY(I, 1)=PHYA(IM1, 1)
        PHY(1, I)=PHYA(1, IM1)
4035  DO 4036 J=3, KKK
        JJK=J-IK
        RIJ(I, J)=RAIJ(IIK, JJK)
4036  PHY(I, J)=PHYA(IIK, JJK)
4040  CONTINUE
C ** FORM AA, BB, CC, DD MATRICES **
      GO TO (4050, 4050, 5010), ICHK
4050  DO 5000 I=1, IKK

```

```
      DO 5000 N=1,NNN
      GO TO (8881,8882),I
8881   MMM=N
      GO TO 8883
8882   MMM=NNN
8883   CONTINUE
      DO 5000 J=1,KKK
      IF (ICLK.EQ.1) GO TO 4051
      IF (J.EQ.2) GO TO 5000
4051   CONTINUE
      DO 5000 M=1,MMM
      GO TO (4052,7770),I
4052   CONTINUE
      IF (J-2) 4053,4053,4100
4053   IF (N-M) 4061,4054,4061
4054   IF (I-J) 4058,4055,4058
4055   AA(I,N,J,M)=N
      BB(I,N,J,M)=N
      CC(I,N,J,M)=0.0
      DD(I,N,J,M)=0.0
      GO TO 5000
4058   AA(I,N,J,M)=-N*(R(2)/R(1))** (N+1)
      BB(I,N,J,M)=-N*(R(2)/R(1))** (N+1)
      CC(I,N,J,M)=0.0
      DD(I,N,J,M)=0.0
      GO TO 5000
4061   AA(I,N,J,M)=0.0
      BB(I,N,J,M)=0.0
      CC(I,N,J,M)=0.0
      DD(I,N,J,M)=0.0
      GO TO 5000
4100   MM1=M-1
      NMM=N-M
      ARG11=(M-1)*PI*(1,J)
      AGG1=R(J)*R(J)/(R(I)*RIJ(1,J))
      DO 4101 MC=1,M
4101   AGG1=AGG1*RIJ(1,J)/R(J)
      CNA1=1.0
      DO 4102 MC=1,N
      CNA1=CNA1*MC
4102   AGG1=AGG1*R(J)/R(I)
      CMA1=1.0
      IF (M-1) 4103,4105,4103
4103   DO 4104 MC=1,MM1
4104   CMA1=CMA1*MC
4105   CNMMA=1.0
      IF (NMM) 4106,4108,4106
4106   DO 4107 MC=1,NMM
4107   CNMMA=CNMMA*MC
4108   AA(I,N,J,NMM+1)=-AGG1*CNA1*COS(ARG11)/(CMA1*CNMMA)
      BB(I,N,J,NMM+1)=AA(I,N,J,NMM+1)
      CC(I,N,J,NMM+1)=AGG1*CNA1*SIN(ARG11)/(CMA1*CNMMA)
      DD(I,N,J,NMM+1)=-CC(I,N,J,NMM+1)
      GO TO 5000
7770   CONTINUE
```

```

IF (J.GT.2) GO TO 7774
IF (N.NE.M) GO TO 7772
IF (I.EQ.J) GO TO 7771
IF (N.EQ.1) GO TO 7773
AA(I,N,J,M)=N*(R(2)/R(1))** (N-1)
BB(I,N,J,M)=N*(R(2)/R(1))** (N-1)
CC(I,N,J,M)=0.0
DD(I,N,J,M)=0.0
GO TO 5000
7771 AA(I,N,J,M)=-N
BB(I,N,J,M)=-N
CC(I,N,J,M)=0.0
DD(I,N,J,M)=0.0
GO TO 5000
7772 AA(I,N,J,M)=0.0
BB(I,N,J,M)=0.0
CC(I,N,J,M)=0.0
DD(I,N,J,M)=0.0
GO TO 5000
7773 AA(I,N,J,M)=1.0
BB(I,N,J,M)=1.0
CC(I,N,J,M)=0.0
DD(I,N,J,M)=0.0
GO TO 5000
7774 IN1=N-1
IM1=M-1
INM1=N+M-1
ARG1=(N+M)*PI*(I,J)
AGG=R(I)/RIJ(I,J)*R(J)/R(I)
DO 15051 MC=1,M
15051 AGG=AGG*(-1.)*R(J)/R(I)
CNA=1.0
IF (IN1) 15052,15054,15052
15052 DO 15053 MC=1,IN1
15053 CNA=CNA*MC
15054 CNA=1.0
IF (IM1) 15055,15057,15055
15055 DO 15056 MC=1,IM1
15056 CMA=CMA*MC
15057 CNMA=1.0
DO 15058 MC=1,INM1
15058 CNMA=CNMA*MC/(RIJ(I,J)/R(I))
AA(I,N,J,M)=AGG*CNMA/CNA/CMA*CDS(ARG1)
BB(I,N,J,M)=-AA(I,N,J,M)
CC(I,N,J,M)=AGG*CNMA/CNA/CMA*SIN(ARG1)
DD(I,N,J,M)=CC(I,N,J,M)
5000 CONTINUE
IF (KKK-2) 206,206,5010
5010 CONTINUE
DO 205 I=3,KKK
DO 205 N=1,NNN
DO 205 J=1,KKK
GO TO (5011,5012,5013),ICHK
5012 IF (J-2) 5011,205,5011
5013 IF (J-2) 205,205,5011

```

```

5011 CONTINUE
      DO 205 M=1,MMN
        IF (I-J) 5017,5014,5017
5014 IF (N-M) 5016,5015,5016
5015 AA(I,N,J,M)=-N
      BB(I,N,J,M)=-N
      CC(I,N,J,M)=0.0
      DD(I,N,J,M)=0.0
      GO TO 205
5016 AA(I,N,J,M)=0.0
      BB(I,N,J,M)=0.0
      CC(I,N,J,M)=0.0
      DD(I,N,J,M)=0.0
      GO TO 205
5017 IN1=N-1
      IM1=M-1
      INM1=N+M-1
      MMN=M-N
      IF (J-1) 5050,5018,5050
5018 IF (M-N) 5019,5020,5020
5019 AA(I,N,J,M)=0.0
      BB(I,N,J,M)=0.0
      CC(I,N,J,M)=0.0
      DD(I,N,J,M)=0.0
      GO TO 205
5020 ARG12=(M-N)*PIY(I,I)
      AGG2=R(I)/RIJ(I,I)
      CNA2=1.0
      DO 5021 MC=1,M
        AGG2=AGG2*RIJ(I,I)/R(I)
5021 CNA2=CNA2*MC
      CNA2=1.0
      IF (N-1) 5022,5024,5022
5022 DO 5023 MC=1,IN1
      AGG2=AGG2*R(I)/RIJ(I,I)
5023 CNA2=CNA2*MC
5024 CMMNA=1.0
      IF (MMN) 5025,5027,5025
5025 DO 5026 MC=1,MMN
5026 CMMNA=CMMNA*MC
5027 AA(I,N,J,M)=AGG2+CNA2+COS(ARG12)/(CNA2+CMMNA)
      BB(I,N,J,M)=AA(I,N,J,M)
      CC(I,N,J,M)=AGG2+CNA2+SIN(ARG12)/(CNA2+CMMNA)
      DD(I,N,J,M)=-CC(I,N,J,M)
      GO TO 205
5050 ARG1=(N+M)*PIY(I,J)
      AGG=R(I)/RIJ(I,J)+R(J)/R(I)
      DO 5051 MC=1,M
5051 AGG=AGG*(-1.)*R(J)/R(I)
      CNA=1.0
      IF (IN1) 5052,5054,5052
5052 DO 5053 MC=1,IN1
5053 CNA=CNA*MC
5054 CNA=1.0
      IF (IM1) 5055,5057,5055

```



```

5055 DO 5056 MC=1,IM1
5056 CMA=CMA*MC
5057 CNMA=1.0
      DO 5058 MC=1,INM1
5058 CNMA=CNMA*MC/(RIJ(I,J)/R(I))
      AA(I,N,J,M)=ASG*CNMA/CNA/CMA*COS(ARG1)
      BB(I,N,J,M)=-AA(I,N,J,M)
      CC(I,N,J,M)=ASG*CNMA/CNA/CMA*SIN(ARG1)
      DD(I,N,J,M)=CC(I,N,J,M)
205  CONTINUE
206  CONTINUE
      GO TO (5200,5100,5100),ICLK
5100 DO 50 N=1,NNN
      DO 50 M=1,NNN
      DO 50 I=3,KKK
      I1=I-1
      I2=I-2
      GO TO (11,12),IK
11  AA(I1,N,1,M)=AA(I,N,1,M)
      BB(I1,N,1,M)=BB(I,N,1,M)
      CC(I1,N,1,M)=CC(I,N,1,M)
      DD(I1,N,1,M)=DD(I,N,1,M)
12  DO 50 J=3,KKK
      GO TO (21,23),IK
21  IF (I-4) 22,23,23
22  JJ1=J-1
      AA(I,N,JJ1,M)=AA(I,N,J,M)
      BB(I,N,JJ1,M)=BB(I,N,J,M)
      CC(I,N,JJ1,M)=CC(I,N,J,M)
      DD(I,N,JJ1,M)=DD(I,N,J,M)
23  JJK=J-2
      AA(I2,N,JJK,M)=AA(I,N,J,M)
      BB(I2,N,JJK,M)=BB(I,N,J,M)
      CC(I2,N,JJK,M)=CC(I,N,J,M)
      DD(I2,N,JJK,M)=DD(I,N,J,M)
50  CONTINUE
5200 KN=KKI*NNN
C ♦♦ PREPARE TO SOLVE SYSTEM OF EQUATIONS FOR X-AXIS ♦♦
      DO 230 I=1,KKI
      DO 230 N=1,NNN
      IN=(I-1)*NNN+N
      II=IN+KN
      DO 230 J=1,KKI
      DO 230 M=1,NNN
      JM=(J-1)*NNN+M
      JJ=JM+KN
      E(IN,JM)=AA(I,N,J,M)
      E(II,JJ)=BB(I,N,J,M)
      E(IN,JJ)=CC(I,N,J,M)
      E(II,JM)=DD(I,N,J,M)
230 CONTINUE
      DO 220 I=1,KKI
      DO 220 N=1,NNN
      DO 220 L=1,KKI
      IF (KN-1) 62,60,62

```

```

60   IF (I-L) 62,61,62
61   H(I,N,L)=1.0
    GO TO 220
62   H(I,N,L)=0.0
220  CONTINUE
    DO 240 I=1,KKI
    DO 240 N=1,NNN
    IN=(I-1)*NNN+N
    II=IN+KN
    DO 240 L=1,KKI
    F(IN,L)=H(I,N,L)
240  F(II,L)=0.0
    KNKN=2*KN
C ** SOLVE SYSTEM OF EQUATIONS **
    CALL CROUT(E,KNKN,F,KKI,DETERM,160)
    DO 250 I=1,KKI
    DO 250 N=1,NNN
    IN=(I-1)*NNN+N
    II=IN+KN
    DO 250 L=1,KKI
    AL(I,N,L)=F(IN,L)
    TA(I,N,L)=F(II,L)
250  CONTINUE
C ** PREPARE TO SOLVE SYSTEM OF EQUATIONS FOR Y-AXIS **
    DO 270 I=1,KKI
    DO 270 N=1,NNN
    IN=(I-1)*NNN+N
    II=IN+KN
    DO 270 L=1,KKI
    F(IN,L)=0.0
270  F(II,L)=H(I,N,L)
    DO 231 I=1,KKI
    DO 231 N=1,NNN
    IN=(I-1)*NNN+N
    II=IN+KN
    DO 231 J=1,KKI
    DO 231 M=1,NNN
    JM=(J-1)*NNN+M
    JJ=JM+KN
    E(IN,JM)=AA(I,N,J,M)
    E(II,JJ)=BB(I,N,J,M)
    E(IN,JJ)=CC(I,N,J,M)
231  E(II,JM)=DD(I,N,J,M)
C ** SOLVE SYSTEM OF EQUATIONS **
    CALL CROUT(E,KNKN,F,KKI,DETERM,160)
    DO 280 I=1,KKI
    DO 280 N=1,NNN
    IN=(I-1)*NNN+N
    II=IN+KN
    DO 280 L=1,KKI
    SI(I,N,L)=F(IN,L)
    BE(I,N,L)=F(II,L)
280  CONTINUE
C ** CALCULATE ADDED MASS COEFFICIENTS **
    GO TO (6001,6002,6003),ICLK

```

```

6001  I=1
      R21=RA(2)*RA(2)/(RA(1)*RA(1))
      DO 600 L=1,KKI
        ALP(1,L)=AL(1,1,L)+AL(2,1,L)*R21
        SIG(1,L)=SI(1,1,L)+SI(2,1,L)*R21
        TAU(1,L)=TA(1,1,L)+TA(2,1,L)*R21
        BET(1,L)=BE(1,1,L)+BE(2,1,L)*R21
        IF (KKI.LE.2) GO TO 600
      DO 6000 J=3,KKI
        RJI2=RA(J)*RA(J)/(RA(1)*RA(1))
        ALP(1,L)=ALP(1,L)+AL(J,1,L)*RJI2
        SIG(1,L)=SIG(1,L)+SI(J,1,L)*RJI2
        TAU(1,L)=TAU(1,L)+TA(J,1,L)*RJI2
6000  BET(1,L)=BET(1,L)+BE(J,1,L)*RJI2
600  CONTINUE
      I=2
      DO 7004 L=1,KKI
        ALP(2,L)=AL(1,1,L)+AL(2,1,L)
        SIG(2,L)=SI(1,1,L)+SI(2,1,L)
        TAU(2,L)=TA(1,1,L)+TA(2,1,L)
        BET(2,L)=BE(1,1,L)+BE(2,1,L)
        IF (KKI.LE.2) GO TO 7004
      DO 7003 J=3,KKI
        ARG=0.0
        BGG=0.0
        CGG=0.0
        DGG=0.0
        RJIJ=RA(J)/RAIJ(2,J)
        DO 7002 N=1,NNN
          ARG=(N+1)*PHYA(2,J)
          AG1=N*RJIJ*(COS(ARG)*AL(J,N,L)+TA(J,N,L)*SIN(ARG))
          BG1=N*RJIJ*(COS(ARG)*SI(J,N,L)+BE(J,N,L)*SIN(ARG))
          CG1=N*RJIJ*(SIN(ARG)*AL(J,N,L)-TA(J,N,L)*COS(ARG))
          DG1=N*RJIJ*(SIN(ARG)*SI(J,N,L)-BE(J,N,L)*COS(ARG))
          DO 7001 NC=1,N
            AG1=-AG1*RJIJ
            BG1=-BG1*RJIJ
            CG1=-CG1*RJIJ
7001  DG1=-DG1*RJIJ
          AGG=AGG+AG1
          BGG=BGG+BG1
          CGG=CGG+CG1
7002  DGG=DGG+DG1
          ALP(2,L)=ALP(2,L)+AGG
          SIG(2,L)=SIG(2,L)+BGG
          TAU(2,L)=TAU(2,L)+CGG
7003  BET(2,L)=BET(2,L)+DGG
7004  CONTINUE
      DO 605 L=1,KKI
        ALP(2,L)=-ALP(2,L)
        SIG(2,L)=-SIG(2,L)
        TAU(2,L)=-TAU(2,L)
605  BET(2,L)=-BET(2,L)
      GO TO 6003
6002  DO 700 L=1,KKI

```

```

ALP(1,L)=AL(1,1,L)
SIG(1,L)=SI(1,1,L)
TAU(1,L)=TA(1,1,L)
BET(1,L)=BE(1,1,L)
DO 700 J=2,KKI
RJ12=RA(J)*RA(J)/(RA(1)*RA(1))
ALP(1,L)=ALP(1,L)+AL(J,1,L)*RJ12
SIG(1,L)=SIG(1,L)+SI(J,1,L)*RJ12
TAU(1,L)=TAU(1,L)+TA(J,1,L)*RJ12
700 BET(1,L)=BET(1,L)+BE(J,1,L)*RJ12
6003 ISS=IKK+1
IF(KKI-ISS)899,6004,6004
6004 CONTINUE
DO 800 I=ISS,KKI
DO 800 L=1,KKI
ALP(I,L)=AL(I,1,L)
SIG(I,L)=SI(I,1,L)
TAU(I,L)=TA(I,1,L)
BET(I,L)=BE(I,1,L)
DO 790 J=1,KKI
AGG=0.0
BGG=0.0
CGG=0.0
DGG=0.0
IF (I-J) 801,770,801
801 GO TO (802,802,805),ICLK
802 IF (J-1) 805,803,805
803 DO 750 N=1,NNN
ARG1=(N-1)*PHYA(1,I)
R1IJ=RA(1)/RAIJ(1,I)
RIJ1=RAIJ(1,I)/RA(1)
AG11=N*R1IJ*(COS(ARG1)*AL(1,N,L)+TA(1,N,L)*SIN(ARG1))
BG11=N*R1IJ*(COS(ARG1)*SI(1,N,L)+BE(1,N,L)*SIN(ARG1))
CG11=N*R1IJ*(-SIN(ARG1)*AL(1,N,L)+TA(1,N,L)*COS(ARG1))
DG11=N*R1IJ*(-SIN(ARG1)*SI(1,N,L)+BE(1,N,L)*COS(ARG1))
DO 804 MC=1,N
AG11=AG11*RIJ1
BG11=BG11*RIJ1
CG11=CG11*RIJ1
804 DG11=DG11*RIJ1
AGG=AGG+AG11
BGG=BGG+BG11
CGG=CGG+CG11
750 DGG=DGG+DG11
GO TO 770
805 RJIJ=RA(J)/RAIJ(I,J)
DO 760 N=1,NNN
ARG=(N+1)*PHYA(I,J)
AG1=N*RJIJ*(COS(ARG)*AL(J,N,L)+TA(J,N,L)*SIN(ARG))
BG1=N*RJIJ*(COS(ARG)*SI(J,N,L)+BE(J,N,L)*SIN(ARG))
CG1=N*RJIJ*(SIN(ARG)*AL(J,N,L)-TA(J,N,L)*COS(ARG))
DG1=N*RJIJ*(SIN(ARG)*SI(J,N,L)-BE(J,N,L)*COS(ARG))
DO 806 MC=1,N
AG1=-AG1*RJIJ
BG1=-BG1*RJIJ

```

```
      CG1=-CG1*RIIJ
806    DG1=-DG1*RIIJ
      AG6=AG6+AG1
      BG6=BG6+B61
      CG6=CG6+CG1
760    DG6=DG6+DG1
770    CONTINUE
      ALP(I,L)=ALP(I,L)+AG6
      SIG(I,L)=SIG(I,L)+BG6
      TAU(I,L)=TAU(I,L)+CG6
790    BET(I,L)=BET(I,L)+DG6
800    CONTINUE
      DO 299 I=ISS,KKI
      DO 299 L=1,KKI
      ALP(I,L)=-ALP(I,L)
      SIG(I,L)=-SIG(I,L)
      TAU(I,L)=-TAU(I,L)
299    BET(I,L)=-BET(I,L)
899    CONTINUE
      DO 8800 I=1,KKI
      DO 8800 L=1,KKI
      ALP(I,L)=ALP(I,L)*RA(I)*RA(I)
      SIG(I,L)=SIG(I,L)*RA(I)*RA(I)
      TAU(I,L)=TAU(I,L)*RA(I)*RA(I)
8800    BET(I,L)=BET(I,L)*RA(I)*RA(I)
      DO 810 I=1,KKI
      DO 810 L=1,KKI
      RIL=4./((RA(I)+RA(L))*2)
      ALP(I,L)=ALP(I,L)*RIL
      SIG(I,L)=SIG(I,L)*RIL
      TAU(I,L)=TAU(I,L)*RIL
810    BET(I,L)=BET(I,L)*RIL
      RETURN
      END
```

```

C *****
C *
C *      *** SUBROUTINE  CROUT ***
C *
C *****

```

THIS PROGRAM SOLVES MATRIX EQUATION $AX=B$ BY THE CROUT METHOD

INPUT VARIABLES

```

C   A:  MATRIX
C   N:  ORDER OF A
C   B:  COLUMN MATRIX
C   M:  NUMBER OF COLUMN VECTOR B
C   DETERM:  RETURN CODE, IF ZERO A IS SINGULAR
C   NMAX:  ROW DIMENSION FOR A & B

```

OUTPUT

B: SOLUTION X STORED

SUBROUTINE CROUT(A,N,B,M,DETERM,NMAX)

DIMENSION A(NMAX,N),B(NMAX,M)

DIMENSION V(160)

DETERM=1.0

DO 1000 K=1,N

KP1=K+1

KM1=K-1

TEMP=0.0

DO 20 I=K,N

DO 2 L=1,K

V(L)=A(I,L)

A(I,K)=A(I,K)-DOTP(V,A(I,K),KM1)

IF (ABS(A(I,K)).LT.TEMP) GO TO 20

TEMP=ABS(A(I,K))

IMAX=I

CONTINUE

AMAX=A(IMAX,K)

IF (DETERM.EQ.0.0) RETURN

IF (IMAX.EQ.K) GO TO 600

DETERM=-DETERM

DO 50 J=1,N

TEMP=A(K,J)

A(K,J)=A(IMAX,J)

A(IMAX,J)=TEMP

CONTINUE

IF (M.LE.0) GO TO 600

DO 400 J=1,M

TEMP=B(K,J)

B(K,J)=B(IMAX,J)

B(IMAX,J)=TEMP

CONTINUE

DO 666 L=1,K

V(L)=A(K,L)

IF (K.EQ.N) GO TO 850

2

3

20

50

0

600

666

```

      DO 700 I=KP1,N
700   A(I,K)=A(I,K)/AMAX
      DO 800 J=KP1,N
800   A(K,J)=A(K,J)-DOTP(V,A(1,J),KM1)
850   IF(M.LE.0) GO TO 1000
      DO 900 J=1,M
900   B(K,J)=B(K,J)-DOTP(V,B(1,J),KM1)
1000  CONTINUE
      IF(M.LE.0) RETURN
      DO 8000 I=1,N
      K=N+1-I
      DO 6666 L=K,N
6666  V(L)=A(K,L)
      DO 7000 J=1,M
7000  B(K,J)=(B(K,J)-DOTP(V(K+1),B(K+1,J),I-1))/A(K,K)
8000  CONTINUE
      RETURN
      END

```

```

C *****
C *
C *      *** FUNCTION  DOTP ***
C *
C *****

```

C MATRIX MULTIPLICATION SUBPROGRAM

```

C
      FUNCTION DOTP(A,B,N)
      REAL*4 A,B,DOTP
      DIMENSION A(1),B(1)
      DOTP=0.0
      IF (N.EQ.0) RETURN
      DO 100 I=1,N
100   DOTP=DOTP+A(I)*B(I)
      RETURN
      END

```