**Preliminary Investigation of the Potential for Transient
Vapor Release Events During In Situ Vitrification
Based on Thermal-Hydraulic Modeling**

**J. S. Roberts
S. L. Woosley
D. L. Lessor
C. Strachan^(a)**

July 1992

**Prepared for the
U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Richland, Washington 99352**

-
- (a) This research was supported by the Northwest College and University Association for Science (Washington State University) under Grant DE-FG06-89ER-75522 with the U.S. Department of Energy.

MAILED

Executive Summary

This study investigates a possible cause of molten glass displacements that occurred during two recent in situ vitrification (ISV) tests. The study was conducted for the U.S. Department of Energy by Pacific Northwest Laboratory. It is hypothesized that these glass displacements are caused by large gas bubbles rising up through the ISV melt and bursting at its surface. These bubbles cause the molten surface to upwell and possibly overflow. When the bubbles burst, molten glass is thrown from the melt surface and the volume of gas contained in the bubble is released into the hood. Both of these phenomena are undesirable because the molten soil ejected from the melt is dangerous to operating personnel and can damage equipment. The sudden gas release can cause a temporary pressurization of the hood, allowing potentially contaminated gas to escape to the atmosphere. This study attempts to explain the conditions necessary for formation of large gas bubbles in the melt so that future glass displacements can be avoided.

It is believed that the large bubbles are formed when relatively high-pressure gas under the melt is forced upward through the melt. This research uses computer simulations of the thermal-hydraulic phenomena taking place in the soil under the melt to predict these pressure buildups. Two powerful computer codes are used in these simulations; TEMPEST to model the electric heating of the ISV system, and TOUGH2 to model the thermal-hydraulic response in the porous soil below the melt.

The effects of soil type and site geometry were explored in these simulations. Two extreme soil types were examined: a sandy soil of relatively high hydraulic permeability and a clay with low hydraulic permeability. The effect of physical obstructions on gas and liquid flow was examined by including vertical impermeable regions surrounding the melt which represent adjacent vitrified soil monoliths or other impermeable inclusions. Additionally, stationary electrodes that extend into the soil below the melt were modeled. It is believed that this electrode configuration may produce more variable melt shapes that could increase gas pressures beneath the melt.

The results presented here are preliminary. In spite of the parametric nature of this study, it roughly parallels an experimental ISV test where a glass displacement event occurred. ISV tests at other power levels, test durations, and soil morphology may result in slightly different conclusions.

Results from this study include

- The gas pressure beneath a large-scale ISV melt in sandy soils is not likely to be greater than 2 psig unless sealed containers of water-bearing materials are present beneath the melt. If contained water exists and is allowed to escape as vapor in a steady manner, the localized pressure under the melt is not likely to be greater than 5 psig. Based on the limited studies outlined in this report, it appears to be highly improbable that a bubble displacement event could occur when processing soils that do not contain sealed containers in high permeability soils such as Hanford soils.
- A pressure buildup from boiling resident liquid in the soil and slow releases from drums are not likely to cause a bubble glass displacement event.

- Based on the experimental evidence and these simulations, it is probable that the glass displacement events in ISV melts are caused by sudden gas releases.
- Adjacent melts or other media that block vapor transport on three sides of the melt slightly increase (~ 0.5 psig) the gas pressure beneath the melt. The temperature and saturation distributions in the soil are dramatically affected by such structures.
- Melt growth down the electrodes is likely to be the normal mode of melt progression for fixed electrode tests. This can probably be avoided by dynamically feeding the electrodes downward as the melt advances.
- Phase resistance between electrodes in a melt can be accurately predicted by TEMPEST and a simple equation presented in this paper. Melt diameter can be predicted given phase resistance and centerline depth. However, melt growth down fixed electrodes cannot be distinguished from an oblate spheroid melt shape using melt centerline depth and phase resistance information.

Contents

Executive Summary	iii
1.0 Introduction	1.1
2.0 Background	2.1
2.1 In Situ Vitrification Background	2.1
2.2 General Description of In Situ Vitrification Technique	2.1
2.3 Gas Displacement Events	2.2
3.0 Hypothesis	3.1
3.1 Source of Gas Pressure Buildup	3.1
3.1.1 Slow Pressure Buildup	3.1
3.1.2 Short Term Pressure Increases	3.2
3.1.3 Sudden Steam Release	3.2
4.0 The Model	4.1
4.1 Two Part Model	4.1
4.2 Computer Codes	4.2
4.3 TEMPEST Joule Heat Model	4.2
4.3.1 Modeling Region	4.2
4.3.2 Electrical Properties	4.2
4.3.3 Model for Contained Water Sources Under the Melt	4.3
4.3.4 Approximations	4.4
4.4 TOUGH2 Transient Thermal-hydraulic Model	4.4
4.4.1 Modeling Region	4.5
4.4.2 Material Properties	4.5
4.4.3 Boundary Conditions	4.5
4.4.4 Models for Flow Restrictions Within the Soil	4.5
4.4.5 Model for Contained Water Sources Beneath the Melt	4.7
4.4.6 Approximations	4.7
4.5 Simulations	4.8
5.0 Results	5.1
5.1 TEMPEST Joule Heating Model	5.1
5.1.1 Matching Experimental Conditions	5.1
5.1.2 Model for Melt Size Based on Phase Resistance and Melt Centerline Depth	5.1
5.1.3 Unusual Melt Shapes	5.2
5.1.4 Variations in Joule Heating within the Melt	5.3
5.1.5 Joule Heating in the drum Array	5.4
5.2 Thermal-Hydraulic Model Results	5.4
5.2.1 Pressure Histories Under the Melt	5.5
5.2.2 Pressure Contour Plots	5.6
5.2.3 Temperature Contour Plots	5.6

5.2.2 Pressure Contour Plots	5.6
5.2.3 Temperature Contour Plots	5.6
5.2.4 Liquid Saturation Contour Plots	5.7
6.0 Conclusions and Recommendations	6.1
7.0 References	7.1
Appendix A - Relative Permeability and Capillary Pressure Functions	A.1
Appendix B - Investigation of Unusual ISV Melt Shapes Due to Stationary Electrode Configuration	B.1

Figures

4.1	Modeled ISV Geometry	4.3
5.1	TEMPEST and Simple Model Predicted Phase Resistances	5.3
5.2	Joule Heating Contours for ISV Melt (inside Melt)	5.8
5.3	Joule Heating Contours for ISV Melt (in Soil)	5.8
5.4	Gas Pressure Histories Under the Melt Centerline	5.5
5.5	Gas Pressure Contours for ISV Melt in Sand 75 hours into Test	5.8
5.6	Gas Pressure Contours for ISV Melt in Sand 74 hours into Test with no Adjacent Vitrified Monoliths	5.8
5.7	Temperature Contours for ISV Melt in Sand 75 hours into Test	5.9
5.8	Temperature Contours for ISV Melt in Sand with no Adjacent Vitrified Monoliths, 74 hours into Test	5.9
5.9	Temperature Contours for ISV Melt in Clay 27 hours into Test	5.9
5.10	Temperature Contours for ISV Melt in Sand 28 hours into Test	5.9
5.11	Liquid Saturation Contours for ISV Melt in Sand 75 hours into Test	5.10
5.12	Liquid Saturation Contours for ISV Melt in Sand with no Adjacent Vitrified Monoliths, 74 hours into test	5.10
5.13	Liquid Saturation Contours for ISV Melt in Clay 27 hours into Test	5.10

Tables

4.1	Electric Properties	4.3
4.2	Thermal-Hydraulic Properties	4.6
5.1	Predicted Phase Resistances Based on Melt Shape	5.2
5.2	Drum Boiling Times	5.6

1.0 Introduction

In situ vitrification (ISV) is a thermal-electric process used to treat wastes and contaminated soil in situ, that is, without first removing them from the ground. ISV melts soils through electrical heating to treat any resident hazardous wastes. This is accomplished by inserting an array of electrodes into the ground. The electric current among the electrodes causes resistive heating and melts the soil, typically to temperatures of 1600 to 2000°C. The melting process destroys and/or removes organic contaminants from the site. Inorganic contaminants are immobilized within the large, chemically inert, physically stable glass and crystalline monolith that results.

This study investigates a possible cause for glass displacements of molten glass that occurred during some recent ISV tests. The study was conducted for the U.S. Department of Energy by Pacific Northwest Laboratory.^(a) These large glass displacements are not typical of ISV tests and have been observed in only 2 out of over 150 tests. The glass displacements occurred in aggressive tests that involved advanced R&D applications. It is hypothesized that these glass displacements were caused by large gas bubbles rising up through the ISV melt. The bubbles burst at the melt surface, throwing molten glass and releasing large volumes of superheated gas into the hood. Both of these phenomena are undesirable because the molten soil is dangerous to the test operators and can damage equipment, and the sudden gas release can cause a temporary pressurization of the hood, allowing potentially contaminated gas to escape to the atmosphere. This study attempts to explain the conditions necessary for formation of these large gas bubbles so that future glass displacement events can be avoided.

This report contains six sections, references, and appendixes. Section 2 provides background information, and Section 3 gives the hypothesis. The model is discussed in Section 4 and results are detailed in Section 5. Section 6 lists the conclusions and results.

(a) Pacific Northwest Laboratory is operated for the U.S. Department of Energy by Battelle Memorial Institute.

2.0 Background

Background information is presented in this section, along with a general description of the ISV technique and a discussion of the glass displacement events.

2.1 In Situ Vitrification Background

The ISV process grew out of the need for a cost-effective treatment process for contaminated soils. Existing techniques typically are ex situ in nature, where the soils and wastes are physically removed and transported elsewhere for treatment. This type of treatment is costly and time consuming, and permanent storage of the extracted waste is still required. There are dangers of contamination of personnel and excavation equipment and the potential for spills during shipment to the treatment facility. With in situ techniques, contaminated soils and wastes are treated where they are found. Once they have been immobilized, they are either left in place or safely extracted and transported.

2.2 General Description of In Situ Vitrification Technique

In situ vitrification is the technique of melting contaminated soils and wastes through electrical heating. The technique involves placing cylindrical electrodes vertically into the ground, typically in a four-electrode array, in a region of contaminated soil. These electrodes are powered by a two-phase electrical system with electrodes receiving voltages 90° out of phase from neighboring electrodes.

Because the unmelted soil is very electrically resistive, a low resistance starter path (typically glass frit and graphite) is required between the electrodes. The starter path melts quickly when power is applied to the electrode system, followed by relatively slow melting of the surrounding soil. The molten mass grows primarily downward to encompass the contaminated soil region as power continues to be supplied. As the melt grows, the resistance between the electrodes drops. For a large-scale test (electrodes spaced approximately 3 m to 5 m) this resistance reaches approximately 10 to 15 Ω at its peak and tapers down to about 0.1-1 Ω in the final stages of the melt, depending on soil composition. The voltage is monitored and adjusted to maintain a relatively constant power level. With no interruptions, a large-scale ISV melt requires 5 to 8 days to complete a melt to a depth of 5 to 6 m.

As the melt progresses, it boils water and liberates or destroys volatile contaminants resident in the ground. The gaseous water and contaminants typically travel around the melt, upward to the soil surface. There is also the possibility that gases may recondense as they enter cooler regions of the soil; although experimental findings have shown that this is probably not a dominant transport mechanism. Any gases that reach the surface are collected in the off-gas treatment system. Radionuclides and nonvolatile hazardous substances, such as heavy metal, are incorporated or encapsulated into the glass structure.

2.3 Gas Displacement Events

Recently, two ISV tests have been prematurely ended by glass displacement of the molten glass. These glass displacements are unusual phenomena and occurred during advanced R&D test applications that were processed aggressively. The glass displacements are dangerous to operating personnel and damaging to the ISV equipment. They are accompanied by a sudden pressure pulse to the off-gas collection system. If this pulse is large, it can cause pressurization of the hood and release contaminants into the atmosphere. Glass displacement events of this nature must be avoided if the ISV technology is to be used widely for waste treatment.

Experimental observations have given clues to the causes and chain of events leading up to glass displacements.

- Large gas bubbles have been observed at the melt surface prior to the glass displacements.
- The pressure measured in the off-gas system increases at the time of glass displacement incidents. This pressure increase is consistent with a large addition of gas into the off-gas system from a large bubble bursting.

3.0 Hypothesis - Source of Gas Pressure Buildup

As the region of soil below the melt is heated by conduction and convection, any liquids present start to boil. These liquids could be water or contaminants interstitial in the soil or contained in buried enclosures (i.e., drums). Gas may slowly accumulate under the melt if escape routes are restricted, causing a slow pressure buildup. A sudden pressure buildup may occur from the release of gas trapped in a buried enclosure. From either source, a volume of gas may enter the melt if the pressure beneath the melt builds to the point where it exceeds the pressure required to penetrate the viscous sintered layer at the melt edge and overcome the static head of the melt.

The gas forms a bubble inside the melt. The bubble expands due to superheating of the gas and decreasing pressure as it travels upward by buoyancy through the melt. When it reaches the surface, it bursts. Large amounts of molten soil may be thrown out of the melt and gas is released when the bubble bursts.

This hypothesis seems to be well supported by the limited experimental information. The remaining question is the cause of the pressure buildup under the melt. The causes of pressure increases and the magnitudes resulting from the various sources are examined in this work. It is beyond the scope of this paper to address the bubble formation, bubble dynamics in the melt, and the influence of the sintered layer on bubble formation.

Boiling water is the dominant source of gas (steam) leading to pressure buildups under the melt. Likely sources for this steam are boiling of the interstitial water content of the soil and the water contained in confined spaces beneath the melt. Gas released from these sources could result in a slow buildup of pressure (resident soil moisture), relatively short periods of increased pressure (steady boiling of liquid in confined spaces), or a sudden steam release (high-pressure gas bursting out of confined spaces).

3.1 Slow Pressure Buildup

As the ISV process progresses, water resident in the soil is constantly being turned into steam ahead of the molten glass front. This causes a dry zone around the melt with a temperature in excess of 100°C. Just outside this zone is a 100°C isoband, which is speculated to be a relatively wet region of varying thickness with temperature at, or close to, the boiling point of water. The steam generated at the outer edge of the dry zone can travel upward around the melt to be collected in the off-gas system, it can recondense back to water as it comes into contact with the cooler soil of the 100°C isoband, or if the gas pressure overcomes the static pressure of the melt, it can travel up through the molten glass.

Restrictions to gas flow caused by physical obstructions (foundations or adjacent vitrified monoliths), an unusual melt shape, drums, or other soil inclusions beneath the melt, could have caused a buildup in pressure under a melt sufficient to overcome its static head and to rupture into the bottom of the melt. It is estimated that the pressure required to do this is greater than the static head of the melt (unpublished experimental data suggest ~0.5 psig greater) because of the added flow resistance of the sintered layer. Because the sintered layer does cause flow resistance, a slow pressure buildup to greater than the static head of the melt could be realized.

3.2 Short-Term Pressure Increases

Short-term pressure increases may occur if the liquid in drums or other subsurface confined regions begins to boil and is allowed to leave the confining structure without significant pressure buildups. For this scenario, the pressure under the melt would show periods of increased pressure under approximately equilibrium conditions during the time of vapor release.

3.3 Sudden Steam Release

A release of high pressure gas (> 0.5 psig over the melt static head) from a confined space (i.e., steel container) could cause a sudden burst of steam and a rapid, local pressure buildup. If the liquid within the drum starts to boil and is not allowed to escape, the drum pressure would increase until its seal ruptures accompanied by a sudden release of steam. As the high pressure is relieved, the saturation temperature drops and more liquid boils, contributing further to the steam release. If the drums became resealed by the advancing melt front or the lids are again forced closed by the static head of the overhead melt and soil, pressures could again build up and cause another sudden steam release in a reoccurring fashion.

4.0 The Model

Modeling the phenomena taking place under an ISV melt is very complex. To model it accurately, a closely coupled solution is required for the electric field equations (to determine joule heating), continuity and momentum equations (indicating mass movement in space, time, and between phases), and energy equations (solving for the temperature field). Currently, there is no computer program available capable of modeling all of these phenomena in porous media. There are computer codes, however, that can model portions of the phenomena. In this work, such codes are used in a loosely coupled fashion to approximate the actual phenomena.

The option exists to approximate the joule heating as a uniform heat source throughout the melt, avoiding the requirement for electric field computations. This approach is simplifying, but forfeits the possibility of learning how the melt progresses, the factors contributing to a specific melt shape, and the actual joule heat distribution. For these reasons, the simulations described in this report modeled the joule heating accurately based on the solution of the electric field equations.

4.1 Two-Part Model

Two computer codes, loosely coupled, were used for these investigations. The problem was divided into two parts, with one computer code (TEMPEST) modeling the electric-field driven joule heating responsible for melting the soil, and the other computer code (TOUGH2) incorporating this joule heating to predict the transient hydrothermal response.

The coupling of these two codes was accomplished by applying them sequentially, using TEMPEST to predict heating patterns, then applying them as heat sources in TOUGH2, which, in turn predicts the hydrothermal response. The melt shape and joule heating were assumed to be constant during each application of TOUGH2.

For this study, two of these iterations were used for each simulations in the following manner:

- The total simulation was broken into two time periods, one representing the first half of the simulation, the other the last half.
- For each of these time periods, a representative melt shape was selected. A joule heating distribution was calculated for each of these melt shapes using TEMPEST.
- The simulation method was as follows:
 - with an impermeable melt in place, initial conditions were applied to the domain
 - the joule heat distribution for the first time period was applied and the TOUGH2 simulations were run for the first time period
 - the joule heat distribution for the second time period was applied to the conditions at the end of the first time period, and the TOUGH2 simulation was continued to the end of the test.

This approach does not realistically represent the early hydrothermal phenomena under the melt. The melt is assumed to exist from the beginning of the simulation so the simulation does not capture

the transient nature of the progressing melt front. In spite of this approximation, the simulation does a reasonable job modeling phenomena occurring later in the simulation.

4.2 Computer Codes

TEMPEST is a hydrothermal computer code developed by Pacific Northwest Laboratory, and typically applied to fluid flow and heat transfer applications in nonporous media. The ability to solve electric field equations for multi-phase electrical systems was recently implemented for modeling ISV melts and waste melters. This code does not have multiple fluid phase capabilities and is not specifically suited to porous media calculations. It was used only for joule heat distribution calculations.

TOUGH2 is a unsaturated groundwater modeling code developed by Lawrence Berkeley Laboratory. The code is capable of treating non-isothermal problems. TOUGH2 treats unsaturated groundwater and gas flow in response to pressure, temperature, and liquid saturation gradients. It computes the changes in phase between liquid and gas and includes models for relative permeability and capillary pressure. TOUGH2 was used to model the transient hydrothermal phenomena.

4.3 TEMPEST Joule Heat Model

The joule heat models for all melt shapes presented in this report were three dimensional (3-D) and included representations of the melt, soil, drums containing liquid-saturated soil located below the melt, and simulated adjacent vitrified monoliths surrounding the melt on three sides. The geometry of this system is shown in Figure 4.1. A 3-D simulation was required to model the 3-D character of the electric fields.

The two electric fields powering the electrodes were modeled by applying experimentally observed power across two pairs of electrodes (two diagonally opposite electrodes form a pair) from a specific large-scale test. The two electric fields were 90° out of phase so that when going from one electrode to the next the phase of the electric field changes by 90°. The electric fields were allowed to pass through the melt, soil, drums, and simulated vitrified monoliths.

4.3.1 Modeling Region

The modeling region for the TEMPEST simulations consisted of a domain approximately twice the height and width of the assumed melt. The large domain size was used so that domain boundaries would not affect the electric field distribution. The surface of the melt was assumed to be insulated, as were all of the side and bottom boundaries of the simulated domain.

4.3.2 Electrical Properties

The electrical properties used in the TEMPEST joule heating models are listed in Table 4.1. Most of these values were estimated from the publications referenced in the table. The electrical conductivity of soil was based on experimental data. This conductivity represents a uniform 50% liquid saturation of the soil. The melt electrical conductivity was also considered homogeneous at 1500°C. The assumption of an isothermal melt was necessary because it would have been too

Figure 4.1. Modeled ISV Geometry

Table 4.1. Electrical Properties

Material	Electrical Conductivity	Source
Moist soil/adjacent monoliths	0.000882 1/ Ω m	personal communication
Liquid-saturated soil	0.00169 1/ Ω m	personal communication
Melt	4.9 1/ Ω m	@1500C, Buelt et al. 1987
Electrode and steel drums	1.0299x10 ⁷ 1/ Ω m	CRC 1972

computationally intensive for TEMPEST to solve for the thermal-hydraulics of the melt in addition to the electric fields to predict an accurate temperature (and electrical conductivity distribution).

4.3.3 Model for Contained Water Sources Under the Melt

An array of filled drums containing liquid-saturated soil that were located under the melt were included in the model to provide a potential vapor source, hypothesized to cause a bubble event. These drums were modeled as a homogeneous region. This region had an electrical conductivity equivalent to serial and parallel resistance paths across the steel drums, moist soil surrounding them, and fully liquid-saturated soil contained in them.

4.3.4 Approximations

Approximations in the TEMPEST model include the assumed homogeneous electrical conductivity for soil and melt, soil electrical conductivity values, and continuum drums array model. The effects of these assumptions follow:

- The melt was assumed to be at a uniform temperature. This means that the higher temperature region near the electrodes, and the lower temperature region at the periphery of the melt are not accurately modeled. The conductivity of the melt changes significantly as the melt temperature changes (Buel et al. 1987):

<u>Temp (°C)</u>	<u>Conductivity (1/Ωm)</u>
1300	2.1
1400	3.3
1500	4.9
1600	7.1
1700	8.9
1800	13.4

The conductivity of the melt around the electrodes is underestimated, and that at the edges of the melt is overestimated. This results in an over prediction of the resistance between the electrodes because of the large current flux in the regions around the electrodes where melt conductivity is underestimated. The outer regions are presented with a smaller current flux and the error introduced by the approximation is small.

- Contact resistance is not considered in this simulation. Little is known about this phenomena so realistic contact resistance values could not be incorporated into the model. However, the overestimated melt resistance around the electrodes (described above) may have inadvertently approximated this phenomena.
- The adjacent monoliths and the drum array are modeled reasonably well (although not exactly) and are not in a primary current path so they do not significantly affect the joule heat distribution.

Overall, these assumptions should not affect the resulting joule heating calculations significantly because the power input is specified and the joule heating principally occurs in the melt. Small redistributions of joule heating within the melt will not overly affect the thermal-hydraulic solution in the TOUGH2 simulations.

4.4 TOUGH2 Transient Thermal-Hydraulic Model

The purpose of the TOUGH2 simulations was to predict whether gas pressure under the melt could build up to the point where gas bubbles through the melt. To accomplish this, a worst-case melt shape was used which creates the greatest potential for pressure buildup. A "normal" melt shape produced with movable electrodes is an oblate spheroid with its minor axis vertical. With stationery electrodes, the melt shape may be more complex due to melt growth down the electrodes. For either of these electrode configurations, the worst-case melt shape is where the melt was large enough to

seal against the modeled adjacent vitrified monoliths. This maximizes the distance gas under the melt must travel to reach the soil surface. This is the configuration used for these simulations and shown in Figure 4.1.

The extensive computations required to model this problem dictated a two-dimensional model for the transient thermal-hydraulic modeling. With this in mind, a slice was taken through the 3-D TEMPEST simulation domain to represent the worst-case melt shape. This shape gives the greatest restriction to liquid and gas flow and the most likely case for building up gas pressure beneath the melt. This slice was located through a plane bisecting two neighboring electrodes.

4.4.1 Modeling Region

The TOUGH2 model took advantage of the approximate symmetry of the theoretical worst-case melt shape and domain about the melt centerline by using the melt centerline as a symmetric boundary. The final computational grid was composed of 600 cells, in an approximately square matrix. The model extended down to the water table (approximately 5 times the melt depth), and 4 times the melt half-width.

4.4.2 Material Properties

The material properties used in the thermal-hydraulic TOUGH2 simulation are listed in Table 4.2. Two sets of data were used in these tests; one to represent sand and the other to represent clay soils. Data from dune sand collected near the Vernita bridge on the Hanford reservation provided the sand values (internal memo). The clay properties were taken from a catalog of soil properties (Mualem 1976). The clay is described as Lamberg Clay, number 1003 in the catalog. Models based on formulas by VanGenuchten (1980) were used for the saturation-dependent capillary pressure and relative permeability curves. These models are described in detail in the appendix.

4.4.3 Boundary Conditions

The boundary conditions used for the TOUGH2 modeling were chosen to affect the area around the melt as little as possible. The side boundaries of the modeled domain represent regions far from the melt. These boundaries were at constant temperature and pressure and were allowed to "drain" vertically with the rest of the soil. The bottom boundary of the domain modeled the water table, a large isothermal reservoir of liquid-saturated soil. This boundary can accept large amounts of liquid as the soil above it drains. The top boundary of the domain was considered to be at constant atmospheric pressure and temperature. Gas flow and heat were allowed to escape from the domain through the top boundary.

Radiant heat transfer from the melt surface was modeled by calculating the heat transfer coefficient necessary to keep the melt at 1500°C, 0.2242 m below the surface while the hood temperature was 300°C. The vapor release from the surface accounted for convective heat losses.

4.4.4 Models for Flow Restrictions Within the Soil

The melt and restricting regions (adjacent vitrified monoliths) were assumed to be impermeable to gas and liquid flow, although conducive to heat flow.

Table 4.2. Thermal-Hydraulic Properties

Property	Value	Units
sand- absolute permeability ^(a)	1.066x10 ⁻¹¹	m ²
relative permeability and capillary pressure VanGenuchten Model (see appendix)		
$\alpha^{(a)}$	0.0235	1/cm
n	5.95	
S _r	0.10	
S _e	0.891	
P _{max}	100,000	Pa
porosity	0.4	
grain density	2.72	g/cm ³
heat capacity	800	J/kg C
heat conductivity (sat)	5.28	W/m K
clay- absolute permeability ^(b)	3.44x10 ⁻¹³	m ²
relative permeability and capillary pressure VanGenuchten Model		
$\alpha^{(b)}$	0.0975	1/cm
n	2.52	
S _r	0.22	
S _e	1.0	
P _{max}	100,000	Pa
porosity ^(b)	0.537	
grain density ^(b)	2.23	g/cm ³
heat capacity	800	J/kg C
heat conductivity (sat)	5.28	W/m K

(a) Based on an unpublished memo.

(b) Based on Mualem 1976.

Heat transfer within the melt was restricted to conduction since the TOUGH2 program does not account for fluid movement of the melt matrix (i.e., convection). Previous numerical studies have shown that natural convection plays a part in mixing the melt and keeping the melt temperature more uniform. For this reason, the thermal conductivity of the melt was increased to account for the lack of mixing within the modeled melt. Thermal conductivities were increased from the measured value of 15 W/mK at 1500°C (Buelt et al. 1987) to between 50 and 100 W/mK. These adjustments were made during the computer simulation to diffuse the local temperature increases.

4.4.5 Model for Contained Water Sources Beneath the Melt

An array of drums beneath the melt were included in the model to act as both a vapor source and a restriction to liquid and gas flow. The drums were modeled by using a set of "shaft" and "drum" cells. The "drum" cells represented the actual liquid-saturated, soil-filled drums. No liquid or gas flow was allowed horizontally or through the bottom of these cells. The tops of the cells were sealed during the first part of the simulation. When pressure inside the drums built up to approximately 2 atmospheres, the tops were opened with an area of 1/10th the lid surface area. This simulated a break in the seal of the drum.

The "shaft" cells were models of the soil passages between the drums. These cells allowed vertical movement of liquid, gas, and heat. Heat transfer horizontally through both the shaft and drum cells was also allowed.

This model allows a steady release of trapped gas from a confined space and the slow boiling of resident soil moisture. Repeated sudden bursts of steam are not modeled.

4.4.6 Approximations

Some approximations were required due to lack of experimental information and the necessity to simplify the physical geometry. These are discussed below.

- The uniform initial condition of 50% liquid saturation was arbitrarily chosen to give a worst-case scenario. The relatively large amount of water resident in the soil would result in the worst-case model because it would cause a low relative permeability to gas flow and be a large source for steam. Both would contribute to pressure buildup.
- Although the melt conductivity was increased to approximate convection, the actual convection phenomenon was not modeled. This assumption probably had little affect on the TOUGH2 thermal-hydraulic solution since the correct total power was delivered to the system.
- Limitations of the drum model restricted the heat transfer through the lids and bottoms of the drums. Heat was not permitted to flow through the bottom of the drums and was restricted by 90% through the lids. This was an imposed requirement resulting from the reduced connection area required to model a leak in the drum seal. This approximation may have slightly retarded the heating of the drums.
- The hydrothermal properties of the soils are approximated. They represent ideal homogeneous soil with no hysteresis in the capillary pressure and relative permeability curves with saturation. Even well-characterized soil may have properties that vary over orders of magnitude at one site. These uncertainties of soil characteristics combine to have more effect than any other approximation on this modeling. For this reason, two extreme soil types were used to bracket the physical situation.
- The step-wise joule heating model and melt shape changes prevented the observance of phenomena related to a slow and constantly moving melt front.

4.5 Simulations

A set of parametric studies were made to explore the effects of near-by flow restrictions (adjacent vitrified monoliths), and soil permeability on the gas pressure built up under the melt. Three simulations were completed, all using liquid-saturated, soil-filled drums beneath the melt as a vapor source.

1. Model using an oblate spheroid melt shape (generally characteristic of ISV melts) with adjacent vitrified monoliths (as flow restrictions) in sand.
2. Model as in 1 but excluding adjacent vitrified monoliths.
3. Model as in 1 but substituting clay for sand (including adjacent vitrified monoliths).

5.0 Results

Results of this work are presented below; including joule heating contour plots and phase resistance models from the TEMPEST simulations, pressure, temperature, and saturation contour plots, and pressure histories under the melt from the TOUGH2 simulations.

5.1 TEMPEST Joule Heating Model

Several interesting results were observed from the TEMPEST joule heating models. These results include matches to experimental data, development of a simple model to predict phase resistance, and relative heat distribution between the melt and surrounding soil. These results are described below.

5.1.1 Matching Experimental Conditions

The TEMPEST simulations displayed the ability of matching experimentally measured phase resistance between electrodes in a representative large-scale ISV test. These simulations assumed a uniform 1500°C melt temperature.

With matched power, the electrical potential predicted across a pair of electrodes was within 12.9% of the measured quantity. The current flow predicted through each pair of electrodes was within 15.0% of that measured experimentally. This remarkable agreement was achieved with an estimated melt shape extrapolated from partial data of the experimental melt shape.

5.1.2 Model for Melt Size Based on Phase Resistance and Melt Centerline Depth

Several TEMPEST simulations were completed during this project which gave the opportunity to determine if melt diameter could be predicted if the melt centerline depth and phase resistance were known. A simple model was developed based on the Stanek model described in equation 1.

$$R_{\text{phase}} = (\sigma\pi L)^{-1} \ln\{D/d + [(D/d)^2 - 1]^{1/2}\} \quad (1)$$

This Stanek model predicts the electrical resistance between two parallel cylinders in an infinite medium. In this equation, both the electrodes and the medium are of thickness L . The electrode diameter is d , the spacing between the driven electrodes is D . The conductivity of the medium between the electrodes is σ . Since ISV melts are not infinite in the plane perpendicular to the electrodes, a correction for melt diameter (Δ) was included with the Stanek model resulting in the simple model shown in Equation (2). This correction has two empirically fit coefficients; $c_1 = 0.635$, $c_2 = 2.04$.

$$R_{\text{phase}} = (\sigma\pi L)^{-1} \ln\{D/d + [(D/d)^2 - 1]^{1/2}\} \exp[c_1(D/\Delta)^{c_2}] \quad (2)$$

ISV melts are not of uniform depth and the electrodes (in fixed electrode tests) protrude from the bottom of the melt. There is some confusion determining which depth value to use for L . The electrical conductivity of the melt is orders of magnitude greater than that of the soil. For this reason, it makes sense to consider the melt depth instead of the electrode depth for length L . Portions

of the electrode extending below the melt contribute little to the current path. The melt depth at the centerline is the most likely melt depth measurement to be monitored, so for these calculations, this quantity will be used for L .

Phase resistances predicted by TEMPEST and the simple model Equation (2) for several melt shapes are listed in Table 5.1. These simulations have common soil and melt properties as well as driving power. They only differ in melt shape and size.

The TEMPEST-predicted phase resistance is compared to the Stanek formula and the simple model with domain correction in Figure 5.1. The simple model predicts the TEMPEST-calculated phase resistance very accurately.

Given a phase resistance value and melt depth, the melt diameter can be estimated. This is an important feature for ISV operators. This model also implies that unusual melt shapes do not affect the phase resistance measurably. In other words, the melt shape cannot be deduced from phase resistance and melt centerline depth.

The domain correction factor used in this model was derived for the electrode diameter and spacing of a specific ISV test. It is unclear how variations in electrode diameter and array spacing affect the correction.

5.1.3 Unusual Melt Shapes

A set of simulations was run to explore the possible causes of experimentally observed unusual melt shapes associated with the use of fixed electrodes. These tests are described in detail in the appendix. Melt growths down the electrodes are primarily caused by heat conduction down the electrode and concentrated joule heating at the electrode from high current flux. These simulations

Table 5.1. Predicted Phase Resistances Based on Melt Shape

<u>Melt Shape</u>	<u>Melt Depth Centerline (m)</u>	<u>Average Melt</u>		<u>Phase Resistance (Ω)</u>	
		<u>Electrode (m)</u>	<u>Diameter (m)</u>	<u>TEMPEST</u>	<u>Simple</u>
Oblate Spheroid	3.47	3.47	7.72	0.083	0.084
Oblate Spheroid	3.02	3.02	8.28	0.090	0.093
Oblate Spheroid	4.32	4.32	8.37	0.056	0.065
Oblate Spheroid	1.74	1.74	7.21	0.165	0.167
Oblate Spheroid	2.18	2.18	7.21	0.133	0.134
Oblate Spheroid	3.47	3.47	7.21	0.083	0.084
Oblate Spheroid	3.02	3.02	7.21	0.095	0.096
Oblate Spheroid	3.46	3.46	7.21	0.083	0.084
Oblate Spheroid	1.34	1.34	6.00	0.250	0.257
Oblate Spheroid	1.34	1.34	7.21	0.214	0.216
Oblate Spheroid	3.47	3.47	11.1	0.072	0.073
Deep Irregular	1.31	5.21	7.21	0.131	0.135
Shallow Irregular	2.16	4.36	7.21	0.215	0.222

Figure 5.1. TEMPEST and Simple Model Predicted Phase Resistances

showed melt 'roots' growing down the electrodes at 1.34 in./hr with the rest of the melt lagging at 0.54 in./hr. This implies that root growth is probably the normal mode of melt progression for tests with fixed position electrodes.

5.1.4 Variations in Joule Heating Within the Melt

For simulations that were performed of the ISV process, the clear majority of the joule heating occurs within the molten soil, little heating occurs in the unmelted soil. The joule heating within the melt is peaked close to the electrodes, tapering down several orders of magnitude toward the sides of the melt. This joule heat distribution is shown in Figure 5.2. The electrodes and close surrounding melt are likely to be hotter than the rest of the melt because of this distribution. This would tend to support the assertion that melt growth down the electrodes is a normal mode of melt advancement.

Melt growth near the electrodes also is slightly encouraged by the joule heating distributions in the unmelted soil. When the electrodes protrude from the bottom of the melt, a current path exists from one electrode, upward through the sand toward the melt, through the bottom levels of the melt, back down through the sand to the opposing electrode. This provides enhanced heating in the soil

near the electrodes. This phenomena would tend to encourage melt growth around the electrodes until the electrodes are surrounded by melt (either by local melt growths or by the entire melt advancing to the electrode depth). Figure 5.3 shows the greater joule heating present in the soil surrounding the electrodes.

This joule heating-induced melt advancement competes against the advancement of other parts of the melt by conduction heat transfer. If the melt has progressed down the electrodes, the resulting concave center region is subjected to heat from several directions while the outer regions of the melt experience heat supplied by the advancing melt (in one direction). This tends to encourage melt growth at the center, and encourages a more oblate spheroid melt shape. It is likely that the conduction heat transfer and joule heating near the electrodes are dominant during most of a stationary electrode ISV test, with the conduction heat transfer at the center of the melt tending to round out the melt after the melt developed around the electrodes (this is supported by experimental evidence).

Relatively little joule heating occurs in the electrodes themselves. The conductivity of the electrodes is much greater than that of the melt, resulting in less joule heating. The electrodes can be seen in Figure 5.2 as the low joule heating regions running vertically through the melt. (Figures 5.2, 5.3, 5.5 through 5.13 are color plots and are placed at the back of this section.) The joule heating is greatest in the melt surrounding the electrodes, decreasing as inverse distance squared moving away from the electrodes. The portions of the electrodes protruding from the melt cannot be distinguished from the surrounding sand.

5.1.5 Joule Heating in the Drum Array

Another factor that was evaluated in this worst-case theoretical ISV application involved the potential for joule heating in the drums placed below the melt. The joule heating in the drum array was on the same order as the surrounding soil ($\sim 10 \text{ w/m}^3$). The drum array can hardly be distinguished from the surrounding soil in Figures 5.2 and 5.3. At this joule heating rate, it would take more than 7 months to heat the soil and water within the drums to thermodynamic saturation, and another 2.5 years would be required to boil off the water. This implies that the drums and their contents are heated by conduction and convection instead of direct joule heating.

5.2 Thermal-Hydraulic Model Results

Significant findings from the transient TOUGH2 thermal-hydraulic simulations include

- probable pressures under the ISV melt resulting from slow gas release from resident soil moisture and constant gas venting from drums
- locations of pressure buildups
- locations and width of the 100°C isoband and the dry band between it and the melt, and apparent lack of significant wet band.

These results are discussed in detail below for the three parametric simulations of an oblate spheroid melt shape: melt in sand with confining adjacent vitrified monoliths, melt in sand with no adjacent vitrified monoliths, and melt in clay with adjacent vitrified monoliths.

5.2.1 Pressure Histories Under the Melt

Histories of pressure beneath the melt give indications of the pressure to be expected from slow boiling for liquid resident in the soil, time and duration of drum venting and the pressure increases expected from them, and the effects of soil permeability and adjacent vitrified monoliths.

The pressure histories for the soil region directly below the melt centerline for the three simulations are plotted in Figure 5.4. The simulations made in this study were intended to parallel an experimental ISV run where glass displacement events occurred. The simulations were run to the point of the observed glass displacement event, not steady state. This means that the pressures cited here may not represent maximum pressures observed over the duration of the melt run to completion. The simulation with clay as the soil surrounding the melt experienced numerical difficulty (matrix singularity) about 27 hours into the simulation, so its trace stops at this point.

The pressure history curves for all simulations reach a relatively steady value midway into the test (20 to 35 hours). This value reflects the relatively steady boiling of the water resident in the soil. This pressure was only slightly above atmospheric pressure, approximately 1 psig for all simulations.

The peaks in pressure histories of 2 runs (melt in sand with and without adjacent vitrified monoliths) between approximately 40 hours and the end of the simulation result from water boiling within the drums. The drums started boiling at approximately the same time for both of the sand simulations with the drum close to the electrode boiling first. The first peak in the pressure history curve reflects the gas released from the first drum boiling. At this point, the simulation with flow restrictions (adjacent vitrified monoliths) showed a slightly higher pressure (3 psig) than did the similar case without flow restrictions (2.5 psig). The typical pressure increase over the steady value for this period of boiling is 2 psig. The second pressure increase is caused by the additional boiling

Figure 5.4. Gas Pressure Histories Under the Melt Centerline

of the drum near the melt centerline. The pressure increase for this event is approximately 3 psig. A slight dip occurs in pressure as the first drum dries out and discontinues boiling. The times of boiling in the drums for each of the simulations is listed in Table 5.2.

It is important to note that the 4 psig maximum pressure underneath the melt computed in these simulations is not enough to overcome the static head of the melt. This implies that the experimentally observed glass displacement event was probably due to a rapid violent release from one or more water-saturated drums into the soil beneath the melt or directly into the melt. This fast release of gas would probably result from the melt sealing the drums before they fully dried out, causing a steep increase in pressure within the drums as the remaining water boils until it is great enough to overcome the static head of the melt. This gas would then be released directly into the melt.

5.2.2 Pressure Contour Plots

Contour plots of gas pressure around the ISV melt for the three simulations are presented in Figures 5.5 and 5.6. Plotted pressure is scaled between atmospheric and the maximum observed for each figure. This scaling was necessary to display the location of pressure buildups.

The melts in sand with and without adjacent melts show similar pressure plots. They both show venting from the drum close to the melt centerline. The maximum pressures differ slightly from the "without adjacent melts" simulation showing 5.25 psig and the "with adjacent melts" simulation showing 4.1 psig. This difference in pressures is due to the different times of the simulations plotted. It can be seen in the pressure history plot (Figure 5.4) that the simulation with the adjacent melts did have a higher pressure than the similar one without the adjacent melts.

5.2.3 Temperature Contour Plots

Temperature plots are presented in Figures 5.7 through 5.10. These plots have the 100°C isoband highlighted by white. All of the plots have a temperature scale between 24 and 1500°C.

The isoband is about 3 m (10 ft) wide in the oblate spheroid melt shape with adjacent melts. The shape seems to be forced downward by the presence of the adjacent melts. Without the adjacent melts, the isoband is thinner (about 2 m or 7 ft) and extends farther away horizontally from the melt centerline. It is unclear how this result affects the melt growth.

Table 5.2. Drum Boiling Times

Simulation	<u>Drum Near Centerline</u>		<u>Drum Near Electrode</u>	
	<u>Start (h)</u>	<u>Stop (h)</u>	<u>Start (h)</u>	<u>Stop (h)</u>
Melt in sand w/ Adj. Vitrified Monoliths	49	-	37	61
Melt in sand w/o Adj. Vitrified Monoliths	48	-	37	60
Melt in clay w/ Adj. Vitrified Monoliths	Simulation Did Not Reach Boiling of Drums			

The major difference between the clay and sand simulations is seen in the thickness of the isobands below the melt. The clay has a 100°C isoband almost twice as thick as the sand simulations. This phenomena results from a combination of effects by capillary pressure and liquid relative permeability. At the liquid saturations observed in the inner regions of the 100°C isobands, the capillary pressure in clay is much higher than in sand. This implies that the liquid does not as easily leave (and is drawn back with greater force) the high-temperature regions in clay as in sand. The liquid relative permeability for clay is also greater than for sand at the saturation observed at the far side of the isoband. This allows a portion of the liquid to travel outward into the surrounding soil more freely. These two effects combine to widen the isotherm in clay.

5.2.4 Liquid Saturation Contour Plots

Liquid saturation plots (Figures 5.11 through 5.13) show a dry band surrounding the melt in all the simulations. Outside this band is a region at approximately 100°C (ranging from between 1.5 to 2 m wide [5 to 7 ft]), where water is continuously boiling and recondensing. It has been previously speculated that this band contains a region of high liquid saturation, where the void space is almost completely filled with liquid water. This hypothesized "wet band" was not found in this work. This region did not appear to a measurable extent in any of the simulations (including the clay simulation). The liquid saturation steadily increased between the dry region near the melt to the saturation of the surrounding soil. This result is supported by ISV field testing which demonstrated that virtually all the water displaced by the melt is collected in the off-gas system. Water moving outward into the soil as gas, recondensing to liquid, and being drawn back into the hot, dry soil regions by capillary pressure is probably not a dominant transport process. Kuhn (1991) used this observation in mathematical modeling to predict transport of water, steam, and volatile trace contaminants in soil during ISV processing.

The finding that the previously assumed "wet band" may not exist has important implications. The "wet band" was assumed to be a barrier to flow, isolating the gases in regions on either side of the band from each other. Without this barrier, both contaminants and water (in gas and liquid form) may flow toward or away from the melt. This implies that the likelihood for destruction of a contaminant is strongly dependent on its sorption characteristics. Kuhn's (1991) report studies this problem in detail.

The color contour plots (Figures 5.2, 5.3, and 5.5 through 5.13) show a cross-sectional view through the melt. The left side of the figure corresponds to the symmetric boundary at the melt center. The bottom and right borders are sized to show the phenomena of interest, they do not represent the computational domain boundary. Within the figures, black objects represent regions impermeable to flow: the large round mass of the melt, the small rectangular liquid-filled drums below it, and the narrow, vertical concrete wall to the right side of the melt.

Figure 5.2. Joule Heating Contours for ISV Melt (inside melt)

Figure 5.3. Joule Heating Contours for ISV Melt (in soil)

Figure 5.5. Gas Pressure Contours for ISV Melt in Sand, 75 hours into Test

Figure 5.6. Gas Pressure Contours for ISV Melt in Sand, 74 hours into Test with no Adjacent Vitrified Monoliths

Maximum Temperature = 2000 C

Figure 5.7. Temperature Contours for ISV Melt in Sand, 75 hours into Test

Maximum Temperature = 1466 C

Figure 5.8. Temperature Contours for ISV Melt in Sand with no Adjacent Vitrified Monoliths, 74 hours into Test

Maximum Temperature = 1039C

Figure 5.9. Temperature Contours for ISV Melt in Clay, 27 hours into Test

Maximum Temperature = 1122 C

Figure 5.10. Temperature Contours for ISV Melt in Sand, 28 hours into Test

Figure 5.11. Liquid Saturation Contours for ISV Melt in Sand, 75 hours into Test

Figure 5.12. Liquid Saturation Contours for ISV Melt in Sand with no Adjacent Vitrified Monoliths, 74 hours into test

Figure 5.13. Liquid Saturation Contours for ISV Melt in Clay, 27 hours into Test

6.0 Conclusions and Recommendations

The following conclusions can be made from this study:

1. The majority of joule heat occurs inside the melt, concentrated around the electrodes. Negligible joule heating occurs in the drum array or surrounding sand. The little joule heating that does occur outside the melt is concentrated in a small region around the electrodes in the soil, below the melt in cases where stationery electrodes are used.
2. Melt growth down the electrodes is likely to be the normal mode of melt progression for fixed electrode systems. This can probably be avoided by dynamically feeding the electrodes downward as the melt advances.
3. Phase resistance between electrodes in a melt can be accurately predicted by TEMPEST and a simple equation presented in this paper. Melt diameter can be predicted given phase resistance and centerline depth. However, melt growth down electrodes cannot be distinguished from an oblate spheroid melt shape using melt centerline depth and phase resistance information.
4. The gas pressure beneath an ISV melt in sand is not likely to be greater and 2 psig unless contained water is present beneath the melt. If contained water exists but is allowed to boil off in a steady manner (not blocked by the melt), the pressure under the melt is not likely to be greater than 5 psig.
5. Based on the experimental evidence and these simulations, it is probable that the glass displacement events in ISV melts are caused by a sudden gas releases. The pressure buildup from boiling resident liquid in the soil and slow releases from drums are not likely to cause a large bubble event.
6. Adjacent melts or other impermeable zones that partially restrict vapor transport do slightly increase the gas pressure beneath the melt in sand (~ 0.5 psig increase). The temperature and saturation distributions are significantly affected by such structures.
7. There is a need for further study to determine the magnitude of the wet band in the 100°C isoband region. There is a potential for gas flow through this band if the liquid saturation is as low as predicted in these simulations.

7.0 References

Buelt, J.L. et al. 1987. *In Situ Vitrification of Transuranic Waste: An Updated Systems Evaluation and Applications Assessment*. PNL-4800-Suppl.1, Pacific Northwest Laboratory, Richland, Washington.

Hayden, N.K., J.K. Johnstone, and R.R. Peters. 1983. "Parameters and Material Properties for Hydrologic Modeling of the Topopah Spring Unit". Memo to Distribution, Sandia National Laboratories, Albuquerque, New Mexico.

Kuhn, W. 1992. *Steady-State Analysis of the Fate of Volatile Contaminants During In Situ Vitrification*. PNL-8059, Pacific Northwest Laboratory, Richland, Washington.

Mantell, C.L. 1968. *Carbon and Graphite Handbook*. J. Wiley and Sons-Interscience.

Mualem, Y. 1976. *A Catalogue of the hydraulic properties of unsaturated soils*. Technion, Israel Institute of Technology & Research & Development Foundation, Ltd., Haifa, Israel.

VanGenuchten, M. T. 1980. "A Closed-Form Equation for Predicting the Hydraulic Conductivity of Unsaturated Soils." *Soil Sci. Soc. Am. J.* 44:892-898.

Weast, R.C, editor. 1972. *Handbook of Chemistry and Physics*. The Chemical Rubber Co., Cleveland, Ohio.

Appendix A

Appendix A

Relative Permeability and Capillary Pressure Functions

The relative permeability and capillary pressure functions used in these simulations are based on functional forms developed by VanGenuchten (1980) and Hayden (1983). These functions are widely used to fit experimental data. See Figures A.1 through A.3.

These functions are:

$$S^* = (S_l - S_{lr}) / (S_u - S_{lr})$$

$$\begin{aligned} P_{cap} &= 0 \text{ (if } S_l \geq S_u) \\ &= -1/\alpha \{ [S^*]^{-1/m} - 1 \}^{1-m} \\ &= P_{max} \text{ (if } 1/\alpha \{ [S^*]^{-1/m} - 1 \}^{1-m} \geq P_{max}) \end{aligned}$$

$$\begin{aligned} k_{rl} &= (S^*)^5 \{ 1 - (1 - [S^*]^{1/m})^m \}^2 \text{ (if } S_l < S_u) \\ &= 1 \text{ (if } S_l \geq S_u) \end{aligned}$$

$$K_{rg} = 1 - k_{rl}$$

where: P_{cap} = capillary pressure

k_{rl} = liquid relative permeability

k_{rg} = gas relative permeability

S_l = liquid saturation

S_{lr} = residual saturation

S_u = maximum saturation

P_{max} = maximum allowable capillary pressure

α and m are empirically fit variables.

Figure A.1. VanGenuchten Capillary Pressure Curves

Figure A.2. VanGenuchten Relative Permeability Functions for Sand

Figure A.3. VanGenuchten Relative Permeability Functions for Clay

Appendix B

Appendix B

Investigation of Unusual ISV Melt Shapes Due to Stationary Electrode Configuration

B.1 Introduction

It was previously hypothesized that ISV melts with both stationary and dynamically fed electrodes progress uniformly from the graphite and frit starter path downward to an oblate spheroid melted region with the minor axis vertical. Recently, experimental evidence has shown that the uniform melt progression assumption may not be valid for fixed electrode ISV applications. The local melt regions surrounding the electrodes may progress faster than the bulk of the melt.

The purpose of this investigation is to use TEMPEST computer modeling to determine if the irregular melt shape is a normal mode of melt progression for fixed electrode ISV systems and explain why it occurs.

B.2 TEMPEST Modeling

The TEMPEST computer code was used to model ISV melt progression. TEMPEST is a hydrothermal computer code developed by Pacific Northwest Laboratory, typically applied to fluid flow and heat transfer applications in nonporous media (see Table B.1). The ability to solve electric field equations for multi-phase electrical systems was recently implemented for modeling ISV melts and waste melters. The electric field and thermal solution portions of this code were used for these simulations.

This investigation closely modeled experimental conditions (geometry, soil and melt properties and powering) of an ISV melt which resulted in an irregularly shaped melt. This was accomplished by focusing the model on one electrode of the typical four-electrode driving system. The model used cylindrical coordinates with the origin centered on the electrode of interest. This electrode is surrounded by soil and at a distance, an artificial electrode. The artificial electrode is concentric to the

Table B.1. Basic Properties of the TEMPEST Model

<u>Property</u>	<u>Amount/Description</u>
Number of electrodes	2
Electrode geometry	coaxial cylinders
Electrode radius	0.5 ft
Electrode separation	6 ft
Electrode depth	20 ft
Initial melt region	top 1 ft of soil
Initial soil temperature	200°C
Initial melt temperature	1500°C
Simulation time	40 hours
Modeled power range	3.1 kW - 0.75 Mw per 10 deg. wedge

electrode of interest and necessary to provide a source/sink for the electric field. This concentric configuration was modeled as a 10 degree, 2-D wedge. The modeled was powered using a range representative of the experimental system being modeled. Properties of molten soil were obtained from Buelt et al. (1987), and electrode properties (HPC graphite) were take from Mantell (1968). In order to help determine the factors that contribute to nonuniform melt progression, two types of simulations were made:

1. Thermal conduction model, neglecting electrical joule heating and fluid flow.
2. Model including both joule heating and thermal conduction (no fluid flow).

B.3 Thermal Conduction Simulation

In this simulation, a thermal transient was calculated, starting from an initial condition of a 1500°C melt layer 1 ft thick capping 200°C soil. No joule heat was added in order to observe the effects of the different thermal conductivities of the soil, melt, and electrodes. Figure B.1 is a temperature contour plot of this simulation after 6.6 hours. This plot illustrates that without electrical heating, the thermal energy tends to dissipate, causing the melt front (contour line 5, 1100°C) to retreat towards the soil surface. However, the higher conductivity of the electrode tends to conduct some of the heat downward, retarding this effect near the electrode.

B.4 Combined Joule Heating and Thermal Conduction Simulation

A relatively realistic model of the experimental ISV system was constructed using a layer of 300°C air at the melt surface that accepted radiation and convective heat transfer and a power of 5.5 kW. This model considers both electrical joule heating and thermal conduction (melt movement is still neglected). This model gave much insight on melt progression.

B.4.1 Melt Front Progression

Figure B.2 shows melt front progression by movement of temperature contours during the simulation. The melting point of the soil (1100°C) is shown on the plots as contour level 3. The melt growth down the electrode with time is evident in these figures. Forty hours into the simulation, the maximum melt temperature is 2091°C. This is slightly higher than the 2000 C maximum temperature observed experimentally.

The melt depths at various radial positions and times are given in Figure B.3. Axial melt rates vary from 0.034 m/hr (1.34 in./hr) at $r=0.183$ m (just outside the center electrode), to 0.014 m/hr (0.54 in./hr) at $r=1.65$ m (just inside the outer electrode). These values match well with experimentally predicted progression rates of ~ 1 in/hr.

B.4.2 Joule Heating

The accelerated melt progression close to the electrodes that was experimentally and numerically predicted can be attributed to the joule heating distribution within the melt and soil. Joule heating contour plots for three periods of time during the simulation are given in Figure B.4. These plots

Plot at time = 6.561 hours

Figure B.1. Temperature Contour plot at Time = 6.6 Hours of Thermal Conduction Solution

show a region of increased joule heat close to the center electrode that extends downward with time as the melt region expands. There are two competing factors influencing this joule heat distribution; high electrical conductivity and high current density near the electrode. Joule heating per unit volume (P_v) can be expressed as:

$$P_v = \langle J^2 \rangle / s$$

Figure B.2. Temperature Contour Plots of Thermal and Electric Field Simulation Showing Melt Front Progression

Figure B.3. Melt Depths at Different Radial Positions Versus Time. Linear curve fits show various melt rates

where: σ = electrical conductivity
 J = current density

The melt temperature is highest near the electrode, which implies higher electrical conductivities and a tendency to decrease joule heating near the electrode if current paths are not effected. However, the increased conductivity of the melt near the electrode results in preferential path of the electric current, increasing the current density in that area. The current density is also high near the electrodes because it is forced through a small surface area of the electrode, increasing the current density and joule heating. The expression for joule heating shows that an increase in current density has more of an effect on the joule heating than an increase in conductivity. This implies that joule heat tends to be high near the electrodes and in the melt region.

An interesting effect is observed at the bottom of the melt root close to the electrode. There is a decrease in the joule heating in this area where the axial current direction changes from upwards along the melt to downward in the electrode. This effect is a physical phenomenon, and is not strongly effected by mesh size.

Figure B.4. Joule Heating Contour Plots at Times $t=5, 20$, and 40 hours

As the melt front advances, the overall resistance between electrodes decreases (Figure B.5) due to the larger volume of conductive melt at the high current density region surrounding the center electrode, and the greater overall volume of melt.

B.5 Summary

Non-uniform melt growth observed experimentally was confirmed using TEMPEST modeling. This accelerated melt progression down the electrodes is probably caused by two phenomena; high joule heating in the melt region near the electrode, and higher thermal conductivity of the electrode compared to the soil.

TEMPEST simulations predicted reasonable values for melt temperatures ($\sim 2000^{\circ}\text{C}$) and melt front progression (~ 1 in./hr).

Based on these findings, is hypothesized that fixed electrode ISV melts do not progress uniformly from the initial graphite and frit starter path to an oblate spheroid shape. Initially, they progress at an accelerated rate down the electrodes. When the melt reaches the bottom of the electrodes, it fills out into an oblate spheroid shape.

Figure B.5. Total Resistance Between Electrodes Versus Time

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

12 DOE/Office of Scientific and Technical
Information

21 DOE Office of Environmental
Restoration and Waste Management
Trevion II Building
12800 Middlebrook Road
Germantown, MD 20874
ATTN: W. W. Alexander
T. D. Anderson
J. E. Baublitz
D. L. Biancasino
J. O. Boda
J. Coleman
S. P. Cowan
J. J. Fiore
C. W. Frank
K. O. Hain
J. M. Lankford
J. C. Lehr
S. C. Lein
J. E. Lytle
S. A. Mann
S. M. Prestwich
M. Shupe
C. H. Sink
L. H. Taylor
H. F. Walter
R. P. Whitfield

2 DOE Albuquerque Operations
Office
P.O. Box 5400
Albuquerque, NM 87115
ATTN: P. A. Saxman
D. H. Bandy

4 DOE Oak Ridge Office
P.O. Box 2001
Oak Ridge, TN 37831
ATTN: J. Moore (2)
J. Sweeney (2)

3 Battelle Memorial Institute
505 King Avenue
Columbus, OH 43201
ATTN: W. A. Carbeiner
R. A. Nathan
Technical Library

4 EG&G Idaho
P.O. Box 1625
Idaho Falls, ID 83415
ATTN: S. K. Merrill
D. F. Nickelson
R. R. Stiger
S. Stiger

4 Geosafe Corporation
2000 Logston Boulevard
Richland, WA 99352
ATTN: C. L. Timmerman (2)
B. E. Campbell
J. E. Hanson

8 Oak Ridge National Laboratory
P.O. Box Y
Oak Ridge, TN 37830
ATTN: G. K. Jacobs (4)
M. Naney (2)
B. P. Spalding (2)

No. of
Copies

- 5 Sandia Laboratories
P.O. Box 5800
Albuquerque, NM 87185
ATTN: D. Berry
R. Knowlton
J. Phelan
L. D. Tyler
Technical Library
- 6 Westinghouse Savannah River
Company
P.O. Box 616
Aiken, SC 29801
ATTN: J. S. Haselow
C. M. Jantzen
M. J. Plodinec
J. F. Sproull
J. L. Steele
T. Walton
- J. R. Berreth
Westinghouse Idaho Nuclear
Co., Inc.
P.O. Box 4000
Idaho Falls, ID 83401
- W. Fitch
DOE Idaho Operations Office
785 DOE Place
Idaho Falls, ID 83402
- B. Haas
Ames Laboratory
7 Spedding Hall
Iowa State University
Ames, IA 50011
- J. Hall
DOE Nevada Field Office
P.O. Box 98518
Las Vegas, NV 89193-8518

No. of
Copies

- J. Haugen
DOE Chicago Field Office
9800 South Cass Avenue
Argonne, IL 60439
- W. Holman
DOE San Francisco Field Office
1333 Broadway
Oakland, CA 94612
- S. Ketola
DOE West Valley Project
P.O. Box 191
West Valley, NY 14171
- J. Koger
Martin Marietta Energy Systems
P.O. Box 2009
Oak Ridge, TN 37831-8097
- K. Nuhfer
Westinghouse Materials Co. of Ohio
P.O. Box 398704
Cincinnati, OH 45239-8704
- M. O'Rear
DOE Savannah River Operations
Office
P.O. Box A
Aiken, SC 29801
- P. T. Owen
Martin Marietta Energy Systems
P.O. Box 2003
Oak Ridge, TN 37831-7256
- J. M. Pope
West Valley Nuclear
Services Co.
P.O. Box 191
West Valley, NY 14171

No. of
Copies

M.A.H. Reimus
Los Alamos National Laboratory
P.O. Box 1663
Los Alamos, NM 87545

L. Rogers
EG&G Energy Measurements, Inc.
P.O. Box 1912, MS RSL-11
Las Vegas, NV 89125

R. Tyler
DOE Rocky Flats Office
DOE Building 116
Golden, CO 80402-0928

Jesse L. Yow, Jr.
Lawrence Livermore National
Laboratory
7000 East Avenue
Livermore, CA 94550

ONSITE

13 DOE Richland Field Office

E. A. Bracken, A6-95
K. W. Bracken, A5-22
R. P. Carter, A5-21
P. K. Clark, A6-80
P. F. Dunigan, A6-95
J. K. Erickson, A5-19
R. D. Freeburg, A5-19
M. J. Furman, A6-80
R. E. Gerton, A6-80
J. D. Goodenough, A5-22
J. M. Hennig, A5-21
R. D. Izatt, A6-95
J. J. Sutey, A5-90

No. of
Copies

13 Westinghouse Hanford Company

W. C. Alaconis, L4-92
H. Babad, B3-68
J. D. Berger, L0-18
J. W. Cammann, H4-54
K. R. Fecht, H4-56
R. E. Lerch, B2-35
H. E. McGuire, B2-35
J. W. Shade, R4-03
D. A. Turner, R1-10
D. D. Wodrich, R1-48
R. D. Wojtasek, B2-15
B. A. Wolfe, L5-61
R. L. Gilchrist, L5-63

44 Pacific Northwest Laboratory

T. M. Bergsman, P7-41
W. F. Bonner, P7-44
J. L. Buelt, P7-41 (5)
H. C. Burkholder, P7-41
C. C. Chapman, P7-41
T. T. Claudson, K1-66
W. O. Heath, P7-41
C. H. Kindle, P7-41
W. L. Kuhn, P8-38
D. L. Lessor, K7-15
P. A. Lowery, K7-15
J. Luey, P7-41
J. L. McElroy, P7-46
M. E. Peterson, P7-41 (5)
T. D. Powell, P7-39
J. S. Roberts, K7-15 (3)
M. R. Shay, K6-25
S. C. Slate, K1-25
S. L. Stein, PNWD
C. Strachan, K7-15
L. E. Thompson, P7-41 (5)
J. S. Tixier, P7-41
R. G. Winkelman, P7-41
S. L. Woosley, P7-41
Publishing Coordination
Technical Report Files (5)

END

**DATE
FILMED
9 / 3 / 92**