2
DOE-PC-91308-3

DOE/PC/91308--3

DE92 019858

**PARTICULATE BEHAVIOR IN A CONTROLLED-PROFILE PULVERIZED COAL-FIRED
REACTOR: A STUDY OF COUPLED TURBULENT PARTICLE DISPERSION AND
THERMAL RADIATION TRANSPORT**

Quarterly Technical Progress Report
For Period March 15, 1992 to June 14, 1992

Mardson Queiroz and Brent W. Webb
Brigham Young University
Provo, UT 84602

Received PETC
AUG 21 1992

Prepared for the United States Department of Energy
Pittsburgh Energy Technology Center (PETC)

Under Contract No. DE-FG22-91PC91308

"US/DOE Patent Clearance is not required prior to
the publication of this document"

MASTER

6
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONFIDENTIAL

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees nor any of their contractors, subcontractors, or their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would infringe privately owned rights.

FORWARD

This report summarizes technical progress during the third quarter (March 15, 1992 to June 14, 1992) of a three-year study conducted for the Department of Energy (DOE) under contract number DE-FG22-91PC91308. The principal investigators for this work are Dr. Mardson Queiroz and Dr. Brent W. Webb; Dr. Clifford Smith is the technical representative for DOE.

TABLE OF CONTENTS

	PAGE
DISCLAIMER	i
FORWARD	ii
ABSTRACT	iv
1. OBJECTIVES AND SCOPE	1
1.1 BACKGROUND	1
1.2 OBJECTIVES	1
1.3 TECHNICAL APPROACH	1
2. SUMMARY OF TECHNICAL PROGRESS	2
2.1 REACTOR REFURBISHMENT	2
2.2 TRANSMISSOMETER DEVELOPMENT	2
2.3 RADIATION AND PARTICLE DISPERSION MODELLING	3
3. REFERENCES	3
4. APPENDIX	4

ABSTRACT

During the third quarter progress has been made in the following areas: preparation for reactor refurbishment, instrumentation development, and radiation and particle dispersion modelling. Refurbishment of the Controlled Profile Reactor was initiated this summer. The experimental testing will begin when NEPA approval has been obtained. Design work has been completed and construction work began during the last part of this quarter for the local transmissometer probe. This laser-based instrument, combined with the data from the PCSV probe will enable estimate of the local concentration of particulates below 0.5 μm in size. Additionally, it will permit measurement of the temporal statistics of the local particulate number density.

1. OBJECTIVES AND SCOPE

1.1 BACKGROUND

Improved understanding of the fundamental processes involved in pulverized-coal combustion is needed to make the energy extraction more efficient and the combustion byproducts environmentally safe. While the characterization of the local particulate behavior (concentration, size, and velocity) is important to the understanding of virtually all processes in a pulverized coal-fired furnace, it influences in a more direct way the turbulent particle dispersion and thermal radiation heat transfer. Yet the local particulate dynamics have gone relatively unaddressed, primarily because of lack of adequate instrumentation to carry out such a study. With recent advances in optical techniques such an effort is now possible. This proposal seeks to characterize the local particulate concentration, velocity, and size distribution in a well-controlled, parametrically-varied laboratory-scale reactor using a new laser diagnostic technique. This newly-developed technique is the only one currently available for the investigation of aspherical particles. The particulate data will be collected simultaneously with local gas temperature and wall radiant heat flux distributions.

1.2 OBJECTIVES

This report describes recent progress in a fundamental, three-year investigation of the coupled problem of turbulent particle dispersion and thermal radiation transport. The project's objective is to make measurements of particle size, velocity, number density, temperature and wall radiant heat flux in a parametrically-controlled reactor presently existent at Brigham Young University (BYU). Although the study proposed here is primarily designed to provide experimental data not currently available for the evaluation of turbulent particle dispersion and radiation models, comparisons of analytical predictions and the experimental data obtained will be performed, using appropriate submodels integral to comprehensive pulverized-coal combustion codes existent at BYU.

1.3 TECHNICAL APPROACH

To accomplish the above objectives, the project is divided in the following tasks:

- Design and fabrication of a modified section for the BYU controlled-profile reactor, which will allow access of several probes to be used in the proposed study.
- Design and fabrication of a two-color pyrometer and cooled probe for local particulate temperature measurement.
- Characterization of the non-reacting turbulent flow field in the reactor using the PCSV-P probe, which will serve as an input during the turbulent particle dispersion submodel validation.
- Literature review dealing with particle dispersion and radiation transport in support of the model validation effort.

- Perform the parametrically-controlled measurements in the controlled-profile reactor.
- Experimental data analysis.
- A comprehensive comparison of experimental data and model predictions.
- Final report.

2. SUMMARY OF TECHNICAL PROGRESS

2.1 REACTOR REFURBISHMENT

Although the Controlled-Profile Reactor is designed and functioning, prior use has motivated the need for its refurbishment. While waiting for NEPA approval of the experimental tests, the reactor will undergo a replacement of worn components and an update of several existing systems. During the summer of 1992 the controlled profile reactor (CPR) will undergo a replacement of worn components and an update of several components to improve flame axisymmetry, coal feed rates, and reactor wall isothermality. New temperature data acquisition boards will be installed that allow sampling from all 140 wall temperature thermocouples. Reactor wall temperatures, air flow rates, and coal feed rates will be acquired by a single Macintosh computer running National Instruments' LabVIEW software package. Closed-loop control will minimize variations in reactor wall temperatures and coal feed rates.

2.2 TRANSMISSOMETER DEVELOPMENT

Figure 1 shows the proposed design for a transmissometer probe to be used in combination with the Insitac Particle Concentration, Size, and Velocity (PCSV) instrument in resolving particle number densities below the 1 μm lower bound of the PCSV. The probe measures transmission through the diagnostic volume and uses a reference signal detector to minimize errors resulting from laser beam intensity drift. The double pass of the beam through the diagnostic volume increases the signal-to-noise ratio and allows the two temperature-sensitive detectors to be placed near each other to minimize temperature differences between them. Data acquisition is accomplished by simultaneous sample-and-hold of the two detector signals through a twelve-bit A/D board at a user-defined sampling frequency. The acquired transmission data will be used in Beer's Law and in combination with number density data gathered with the PCSV instrument to infer a sub-micron number density distribution. Emission and absorption properties of the measured particles for use in Beer's Law are calculated from Mie theory.

Figure 1. Schematic of transmissometer probe.

2.3 RADIATION AND PARTICLE DISPERSION MODELLING

While waiting for NEPA approval to initiate the experimental work, supporting analytical work in the areas of radiation and particle dispersion modeling was begun. In the radiation modelling, a two-dimensional, axisymmetric discrete ordinates code for the solution of the Radiative Transfer Equation has been written, and predictions have been compared with published benchmarks. The comparisons reveal good agreement with previously reported predictions. Under separate funding, work has begun in the formulation of suitable particle and gas radiation properties for input to the code. A new spectral gas phase radiative property model is being developed that is suitable for use in complex geometries and multidimensional systems. The spectral gas model is being formulated so as to be compatible with continuum radiation properties of non-gray particulates and boundary conditions.

In particle dispersion modelling, the initial objective is to evaluate the performance of the particle sub-model incorporated in a 2-dimensional comprehensive pulverized coal combustion code (PCGC-2) with the help of the particle dispersion data of Bonin (1992). The particle sub-model used in PCGC-2 is based on the Lagrangian or "tracking" approach in which it calculates the trajectories of representative particles through the gas-phase field accounting for the aerodynamic particle drag and turbulent particle dispersion. The mutual coupling between the gas-phase and particles is accounted by estimating the particles source terms (mass, momentum and energy) for each computational cell visited by the particle. This is followed by recalculation of the flow field incorporating these source terms.

4. REFERENCES

Bonin, M.P. (1992). "Optical Measurement of Particle Size, Velocity and Number Density in Pulverized Coal Flames," Ph.D. Dissertation, Mechanical Engineering Department, Brigham Young University.

END

**DATE
FILMED**

10 / 9 / 92