(200)
R290

no. 76-285

USGS-OFR-76-285

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

[Reports - Open file
series

Audio-magnetotelluric data log, apparent resistivity
maps and station location map for the Darrough
Known Geothermal Resource Area (KGRA), Nevada

TM
am
Ivan

By

Carl L. Long, Robert M. Senterfit and Harold E. Kaufmann

U.S. Geological Survey

Open-file Report No. 76-285
1976

This report is preliminary and has not been
edited or reviewed for conformity with U.S.
Geological Survey standards and nomenclature.

MASTER

265502

U.S.G.S. Report

76-285

Reston Reference Service

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

pc/

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DARROUGH, NEVADA
1976

1.

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
1B-S	pa	16.7	18.5	17.2	20.8	17.5	28.8	44.6	49.2	123.	130.	300.	1536.
	N	7	6	8	7	6	6	6	6	6	6	5	1
	Er	2.2	4.2	.7	2.2	1.1	2.8	2.0	2.3	20.6	15.	63.	-
1E-W	pa	17.4	11.4	12.0	15.6	23.0	37.2	88.1	60.8	123.	90.9	335.	514.
	N	7	8	7	9	6	7	8	6	7	8	6	1
	Er	1.3	1.3	.7	.9	.9	2.8	6.1	6.8	39.6	5.8	26.	-
2N-S	pa	11.2	25.1	19.7	33.5	41.4	92.3	183.	153.	242.	225.	273.	765
	N	7	9	8	9	10	9	8	5	6	9	3	1
	Er	2.66	5.54	1.71	2.42	1.47	8.95	27.1	32.4	43.2	48.5	36.2	-
2E-W	pa	6.3	69.9	54.6	66.2	99.2	209.	904.	502.	1656.	505.	1076.	352.
	N	7	10	10	9	10	9	12	9	8	11	1	1
	Er	11.1	8.93	2.61	3.66	6.19	22.9	108.	82.2	22.9	34.8	-	-
3N-S	pa	14.4	6.07	5.75	5.40	4.93	9.50	30.8	-	22.9	19.7	142.	31.0
	N	6	10	11	7	6	10	7	-	4	6	6	1
	Er	5.16	.73	.54	.92	1.08	1.59	6.49	-	4.22	5.01	31.7	-
3E-W	pa	39.2	34.0	38.9	45.1	50.3	30.0	66.4	-	46.5	109.	89.7	57.7
	N	8	8	10	7	11	8	8	-	8	6	5	1
	Er	8.77	4.69	2.83	5.81	2.59	2.33	18.7	-	5.05	16.2	10.6	-
4N-S	pa	13.6	10.6	22.9	21.2	7.79	28.5	40.9	-	-	47.1	73.7	328.
	N	11	9	9	11	8	12	1	-	-	9	5	1
	Er	2.3	1.85	7.75	1.7	.70	2.2	-	-	-	3.03	9.56	-
4E-W	pa	18.2	19.8	24.1	26.7	47.9	68.1	100.	-	-	101.6	179.	2917.
	N	11	11	9	8	10	12	3	-	-	11	6	1
	Er	1.9	2.44	1.44	1.11	3.05	4.22	26.3	-	-	11.7	3.44	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
5NS	pa	5.66	6.31	5.33	5.90	6.55	9.2	-	-	-	786.	826.	6990.
	N	11	6	10	13	10	12	-	-	-	11	5	1
	Er	0.7	2.13	0.40	0.4	0.4	0.4	-	-	-	60.7	41.3	-
5EW	pa	5.0	2.56	3.04	3.87	6.25	10.6	-	-	-	108.	309.	590.
	N	14	10	10	12	8	13	-	-	-	11	5	1
	Er	0.6	0.29	0.24	0.20	0.32	0.70	-	-	-	4.5	3.31	-
6NS	pa	6.0	9.76	8.02	9.4	11.4	25.6	-	-	-	2605.	1787.	8734.
	N	14	4	7	8	10	8	-	-	-	7	6	1
	Er	1.7	1.79	1.84	0.9	0.88	2.9	-	-	-	220.	208.	-
6EW	pa	5.2	7.06	4.32	5.20	12.6	20.0	-	-	-	220.	823.	1148.
	N	7	7	10	8	10	10	-	-	-	11	8	1
	Er	0.9	0.82	0.72	1.2	3.14	6.0	-	-	-	5.82	55.7	-
7NS	pa	6.7	58.4	45.9	36.6	24.4	36.0	590.	836.	3647.	3600.	2583.	17650.
	N	7	4	4	8	7	11	10	8	7	9	7	1
	Er	1.8	17.8	9.37	13.3	3.19	5.8	95.1	141.	631.	225.	150.	-
7EW	pa	8.7	9.00	8.01	8.60	11.7	24.9	507.	104.	88.3	505.	2462.	2605.
	N	10	6	10	10	10	12	7	9	10	14	8	1
	Er	1.34	3.71	1.04	1.50	0.43	4.7	134.	13.5	10.1	36.2	69.19	-
8NS	pa	7.7	52.9	5.26	5.1	6.32	10.4	30.1	235.	136.	515.	777.	3868.
	N	7	5	8	11	10	8	5	7	4	6	5	1
	Er	1.1	13.3	0.58	0.60	0.56	1.30	3.0	51.3	39.2	69.	74.2	-
8EW	pa	24.1	18.9	3.12	3.9	7.06	9.1	24.4	28.6	41.9	1206	161.	577.
	N	6	2	10	15	10	15	10	10	10	13	5	1
	Er	4.8	1.40	0.26	0.20	.87	0.80	1.91	5.67	1.02	15.0	3.26	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
9 _{NS}	pa	11.3	34.2	26.9	24.4	26.3	168.	88.4	38.7	115.	104.	128.	486.
	N	5	5	6	7	6	8	9	6	6	6	8	1
	Er	1.35	2.75	3.74	5.5	5.26	33.1	11.9	12.3	16.2	10.8	26.2	-
9 _{EW}	pa	17.4	11.7	15.9	14.9	-	27.7	53.0	14.1	70.7	43.8	80.9	249.
	N	7	10	9	5	-	7	8	8	5	7	7	1
	Er	3.42	1.35	1.95	2.97	-	1.7	7.72	3.46	17.1	8.20	9.0	-
10 _{NS}	pa	97.6	150.	236.	164.	150.	190.	-	-	-	175.	150.	858.
	N	10	13	11	13	11	12	-	-	-	11	9	1
	Er	14.9	23.3	45.	11.8	9.7	9.3	-	-	-	7.3	9.1	-
10 _{EW}	pa	83.1	68.9	73.6	71.9	63.4	72.3	-	-	-	44.7	106.	170.
	N	12	12	13	12	10	10	-	-	-	8	13	1
	Er	8.1	7.2	15.	2.9	2.8	2.7	-	-	-	3.7	5.0	-
11 _{NS}	pa	36.1	12.3	82.7	52.1	34.1	27.7	-	-	-	179.	216.	817.
	N	5	2	8	13	10	12	-	-	-	11	3	1
	Er	5.9	2.17	14.0	5.2	2.07	1.5	-	-	-	11.3	34.5	-
11 _{EW}	pa	17.2	12.1	18.4	25.6	43.5	66.9	-	-	-	52.2	206.	114.
	N	10	6	6	10	10	12	-	-	-	17	1	1
	Er	2.95	4.13	2.60	2.80	1.65	3.5	-	-	-	1.8	-	-
12 _{NS}	pa	17.4	30.8	32.4	27.7	21.2	22.5	55.7	31.6	98.7	239.	247.	837.
	N	6	5	9	11	6	8	6	5	5	7	4	1
	Er	1.82	7.82	5.6	3.29	1.58	5.09	10.0	9.32	15.5	21.	43.8	-
12 _{EW}	pa	20.4	22.1	18.9	24.4	28.9	9.28	131.	53.8	64.2	85.1	311.	70.2
	N	6	5	9	10	10	10	6	5	7	9	5	1
	Er	2.53	2.55	2.22	1.05	1.81	1.79	8.7	11.2	7.24	6.93	3.58	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
13 _{NS}	pa	10.4	14.2	21.3	16.1	24.7	31.4	50.9	25.0	387.	451.	365.	1536.
	N	10	5	6	15	10	12	10	11	10	14	12	1
	Er	1.4	3.66	1.71	1.80	4.01	4.4	5.3	2.4	54.	36.8	41.2	-
13 _{EW}	pa	17.4	25.0	19.2	15.8	18.6	47.5	179.	72.1	216.	842.	2308.	1093.
	N	12	9	8	14	10	13	10	8	11	11	11	1
	Er	3.0	4.77	1.73	0.9	1.12	6.4	29.9	14.9	23.	49.6	169.	-
14 _{NS}	pa	16.5	110.	74.0	114.6	43.5	48.	263.	920.	517.	39.0	1104.	5235.
	N	7	4	2	6	5	12	6	11	9	12	5	1
	Er	2.6	52.4	52.1	20.1	7.97	10.2	48.1	142.	62.0	3.3	66.8	-
14 _{EW}	pa	15.3	18.3	16.1	17.5	30.3	71.8	300.	95.7	232.	763.	1387.	308
	N	10	5	10	13	9	15	6	9	10	13	5	1
	Er	1.3	4.33	1.85	1.1	3.41	9.8	92.7	15.8	17.2	39.8	36.7	-
15 _{NS}	pa	17.8	50.6	11.4	18.2	19.8	24.2	196.	-	91.7	217.	336.	1150.
	N	4	5	3	7	6	9	7	-	7	11	14	1
	Er	3.08	11.0	2.43	5.39	8.28	3.69	42.6	-	28.3	14.8	19.2	-
15 _{EW}	pa	24.1	71.7	23.7	25.6	48.8	124.	577.	-	269.6	1294.	2943.	1206.
	N	7	3	7	10	4	10	7	-	12	10	12	1
	Er	2.56	16.1	3.18	5.74	19.2	18.0	144.	-	26.9	99.3	238.	-
16 _{NS}	pa	8.22	11.2	24.4	9.9	10.4	15.3	79.8	41.1	98.4	132.	254.	-
	N	6	3	5	9	13	14	9	10	17	10	7	-
	Er	1.55	4.41	7.52	1.4	1.2	3.0	16.5	10.3	9.45	7.8	7.0	-
16 _{EW}	pa	47.7	24.3	25.5	19.4	31.7	64.5	213.	124.	243.	1123.	2022.	-
	N	7	5	20	11	11	11	10	11	23	8	8	-
	Er	10.9	8.42	6.81	2.4	3.4	7.6	42.	23.	10.0	87.8	97.0	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres - = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
17 _{NS}	pa	7.6	11.5	5.48	4.8	4.47	6.90	108.	-	-	366.	366.	1435.
	N	8	7	13	11	17	10	3	-	-	9	8	1
	Er	.3	1.33	0.51	0.3	0.22	1.90	27.9	-	-	21.3	38.2	-
17 _{EW}	pa	12.0	11.3	13.2	18.1	23.9	39.4	618.	-	-	490.	1031.	4780.
	N	10	18	18	11	10	11	4	-	-	10	9	1
	Er	2.9	1.00	1.30	1.50	0.85	3.60	214.	-	-	21.8	98.2	-
18 _{NS}	pa	10.0	14.0	13.1	22.2	41.8	3.8	-	-	-	179.	510.	-
	N	5	4	12	10	12	7	-	-	-	7	11	-
	Er	1.57	3.42	0.82	1.79	4.95	0.88	-	-	-	7.0	12.1	-
18 _{EW}	pa	8.45	20.5	19.3	23.5	62.8	106	1853.	-	-	1017.	2537.	2826.
	N	6	7	10	7	6	8	6	-	-	7	9	1
	Er	1.91	2.87	1.99	3.99	10.1	23.2	368.	-	-	180.	190.	-
19 _{NS}	pa	8.9	11.5	17.4	28.2	22.1	140.	-	36.9	-	1665.	2001.	6144.
	N	9	12	13	10	7	10	-	2	-	13	11	1
	Er	1.8	2.33	1.88	3.3	1.63	32.9	-	5.2	-	115.	189.	-
19 _{EW}	pa	16.2	20.9	16.2	20.0	22.6	53.0	161.5	243.	-	837	1514.	634
	N	10	8	19	10	10	11	4	2	-	12	21	1
	Er	2.2	4.02	1.18	1.40	1.60	7.3	83.9	40.1	-	112	73.7	-
20 _{NS}	pa	4.4	9.97	12.7	14.5	14.4	20.7	-	28.2	-	908.	975.	4193.
	N	5	6	12	6	13	7	-	1	-	9	8	1
	Er	0.8	2.11	1.22	1.3	0.64	1.6	-	-	-	52.2	104.2	-
20 _{EW}	pa	20.0	15.3	11.5	12.6	20.3	32.6	92.1	-	-	386.	82.1	1329.
	N	8	6	12	8	9	8	2	-	-	10	12	1
	Er	2.8	5.32	2.45	0.54	1.82	5.2	64.6	-	-	11.8	2.97	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm-metres - = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
21 _{NS}	pa	175.	157.	259.	105.	181.	157.	88.8	30.9	260.	521.	1180.	2856.
	N	7	6	9	15	14	17	15	7 9	5	10	8	1
21 _{EW}	Er	37.7	17.8	32.6	17.8	4.88	9.06	11.05	7.93	38.2	82.1	341.	-
21 _{EW}	pa	77.0	56.1	62.1	70.0	88.9	101.	121.	21.2	33.5	393.	604.	2295.
	N	9	14	23	18	26	21	20	8	5	20	27	1
	Er	11.6	13.8	5.27	4.95	3.55	4.89	24.7	3.18	4.53	43.5	37.8	-
22 _{NS}	pa	4.73	6.88	10.35	11.9	12.9	12.9	-	-	-	661.	685.	3992.
	N	10	15	12	36	33	15	-	-	-	17	1	1
	Er	.53	.90	.93	.67	.43	1.22	-	-	-	36.3	-	-
22 _{EW}	pa	5.64	7.30	8.22	10.6	24.2	27.5	302.	-	-	297.	1052.	1596.
	N	6	19	25	36	23	24	2	-	-	19	9	1
	Er	0.85	0.57	0.45	0.42	2.41	1.51	55.9	-	-	13.6	103.5	-
	pa												
	N												
	Er												
	pa												
	N												
	Er												
	pa												
	N												
	Er												
	pa												
	N												
	Er

Scale: 1:62500

Explanation:

⊗ station location

Resistivity contours shown are on a logarithmic interval for ohm-metres.

Figure 2. Audio-magnetotelluric apparent resistivity map at 27 Hz. telluric line east-west, Darrough Hot Springs KGRA, Nevada.

Scale: 1:62500

Explanation:

⊙ Station location

Resistivity contours shown are on a logarithmic interval in ohm-metres.

Figure 3. Audio-magnetotelluric apparent resistivity map at 27 Hz., telluric line north-south, Darrough Hot Springs KGRA, Nevada.