EGG-GEO--10274

DE92 018038

**FLASH - A FINITE ELEMENT COMPUTER CODE
FOR VARIABLY SATURATED FLOW**

**Robert G. Baca
Swen O. Magnuson**

**Subsurface and Environmental Modeling Unit
Geosciences Group**

May 1992

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
P. O. Box 1625
Idaho Falls, Idaho 83415**

**Prepared for the
U. S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Idaho Field Office Contract No. DE-AC07-76ID01570**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

A numerical model was developed for use in performance assessment studies at the INEL. The numerical model, referred to as the FLASH computer code, is designed to simulate two-dimensional fluid flow in fractured-porous media. The code is specifically designed to model variably saturated flow in an arid site vadose zone and saturated flow in an unconfined aquifer. In addition, the code also has the capability to simulate heat conduction in the vadose zone. This report presents the following:

- o description of the conceptual framework and mathematical theory,*
- o derivations of the finite element techniques and algorithms,*
- o computational examples that illustrate the capability of the code, and*
- o input instructions for the general use of the code.*

The FLASH computer code is aimed at providing environmental scientists at the INEL with a predictive tool for the subsurface water pathway. This numerical model is expected to be widely used in performance assessments for: (1) the Remedial Investigation/Feasibility Study process and (2) compliance studies required by the U. S. Department of Energy Order 5820.2A.

Table of Contents

	Page
List of Figures	ii
1.0 INTRODUCTION	1
1.1 Background	1
1.2 Motivation	3
1.3 Objectives and Scope	4
2.0 CONCEPTUAL FRAMEWORK	5
2.1 Physical Setting	5
2.2 Fluid Flow in the Variably Saturated Zone	7
2.3 Fluid Flow in a Free Surface Aquifer	8
2.4 Heat Transport in the Soil	8
3.0 MATHEMATICAL MODELS AND ASSUMPTIONS	10
3.1 Introduction	10
3.2 Fluid Flow Equation for the Variably Saturated Zone	10
3.3 Fluid Flow Equations for a Free Surface Aquifer	11
3.4 Heat Transport Equation for the Vadose Zone	12
4.0 FINITE ELEMENT FORMULATION	14
4.1 Computational Approach	14
4.2 Galerkin Weak Statement	15
4.3 Newton Based Weak Statement	19
4.4 Picard Based Weak Statement	20
4.5 Time Integration Scheme	22
4.6 Solution of Algebraic Equations	24
5.0 COMPUTATIONAL EXAMPLES	26
5.1 Partially Saturated Flow in a Dry Soil	26
5.2 Saturated-Unsaturated Flow in a Two-Dimensional Domain	30
5.3 Heat Transport from a Buried Heat Source	34
6.0 INPUT GUIDE	38
6.1 Introduction	38
6.2 Summary of Command Instructions	39
6.3 Description Input Stream	39

Table of Contents (Continued)

	Page
ACKNOWLEDGMENTS	47
REFERENCES	48
APPENDIX I - SAMPLE INPUT FILES FOR TEST PROBLEMS	52
DISTRIBUTION LIST	58

List of Figures

1	Location of INEL Site and Facilities	2
2	Conceptual Sketch of Physical Setting	6
3	Types of Finite Elements used in Constructing a Computational Mesh	14
4	Superposition of Finite Elements	16
5	Domain and Boundary Conditions for Variably Saturated Flow Problem	26
6	Comparison of Pressure Head Profiles computed with FLASH and UNSAT1D codes	29
7	Comparison of Moisture Content Profiles computed with FLASH and UNSAT1D codes	29
8	Domain and Boundary Conditions for Saturated-Unsaturated Flow Problem	30
9	Comparison of Pressure Head Profiles computed with FLASH and PORFLO-3 codes	33
10	Comparison of Moisture Content Profiles computed with FLASH and PORFLO-3 codes	33
11	Domain and Boundary Conditions for Heat Transport Problem	34
12	Comparison of Soil Temperature Distributions computed with FLASH and Analytical Solution	37
13	Sample Finite Element Mesh	44

1.0 INTRODUCTION

1.1 Background

Environmental activities at the Idaho National Engineering Laboratory (INEL) include evaluating low-level radioactive, hazardous and mixed-waste sites at such facilities as the Radioactive Waste Management Complex (RWMC), Test Area North (TAN), Test Reactor Area (TRA) and others, see Figure 1. These evaluations are being conducted as part of: (1) the Remedial Investigation/Feasibility Study (RI/FS) process and/or (2) compliance studies required by the U. S. Department of Energy (DOE) Order 5820.2A. An important part of these evaluations, referred to as the performance assessment, is the analysis of contaminant movement from waste sites through the atmospheric, biotic, and water pathways.

At the INEL, like other DOE sites, the water pathway is the most significant (Case, et al., 1989, RAE, 1990). Because of the absence of natural, surface-water features at the INEL, these performance assessments generally focus on the issue of contaminant movement through the subsurface, i.e., vadose zone and Snake River Plain aquifer. Specific attention is given to:

- o identifying the hydrologic factors and geochemical mechanisms controlling contaminant transport,
- o assessing the rate, direction and extent of movement, and
- o predicting the contaminant concentrations in subsurface environment.

With this information, informed decisions can be made regarding the selection of alternative actions for site clean-up and environmental restoration.

Numerical models are playing a central role in performance assessments at the INEL because of their usefulness in predicting migration of dissolved and colloidal phase contaminants. An important prerequisite, however, is the analysis and interpretation of pore-water movement in the subsurface. In the vadose zone, for example, moisture movement must be related to such factors as: (1) infiltration and/or liquid discharge rates, (2) natural driving processes, eg., capillarity and gravity, and (3) hydraulic properties of distinct stratigraphic features. Similarly, water movement in the saturated zone or aquifer must be described as a function of: (1) recharge and discharge rates, (2) hydraulic gradients and properties, and (3) groundwater dynamics associated with pumping wells at neighboring sites.

Figure 1. Location of the INEL Site and Facilities

Flow and transport models were originally developed for use in performance assessments of waste sites at the RWMC. Recently, these models were generalized for application to other facilities at the INEL. This report describes a finite element, fluid flow model referred to as the FLASH computer code. This numerical model is designed for use in simulating two-dimensional, variably-saturated, single-phase flow and heat conduction in the vadose zone; these processes are modeled for an arbitrary, vertical cross-section. The code also has the capability to simulate saturated flow in the unconfined aquifer; flow in the aquifer is modeled in the horizontal plane taking into account the changes in water level elevation. The FLASH computer code is interfaced with a companion numerical model referred to as the FLAME computer code. The FLAME code uses the flow computations from the FLASH code and then simulates contaminant transport in the subsurface. The FLAME code is documented in a separate report.

1.2 Motivation

A large number of numerical models have been developed by the scientific community for the purpose of predicting subsurface fluid flow and contaminant transport. These numerical models are described in the literature (Bachmat, et al. 1980; Oster, 1982) and are available through the International Groundwater Modeling Center, the National Water Well Association, and other sources. Many of the existing models, however, were developed for specific applications and therefore have distinct limitations. For example, many of the available models are limited in that they:

- o are not applicable to both vadose zone and unconfined groundwater flow,
- o do not work well when applied to arid sites,
- o do not have a contaminant transport capability,
- o are not applicable to fractured-porous media, and/or
- o do not accommodate strata with complex geometry.

Recent code testing and code benchmark studies (Magnuson, et al, 1991; Baca and Magnuson, 1991) performed at the INEL suggests that relatively few, truly general, models currently exist. Moreover, many of the existing models have limited documentation, have not been independently verified or benchmark tested, and/or are not maintained under a software QA or configuration control program. Such limitations place in question the predictive reliability of these numerical models, and therefore, on the conclusions drawn in a performance assessment.

To avoid potential model limitations and questions of reliability, the FLASH code and its counterpart FLAME were developed for general use at the INEL. Both codes are extensions and refinements of the MAGNUM fluid flow code (Baca and Langford, 1986; England, et al., 1986) and CHAINT contaminant transport code (Baca and Langford, 1986; Kline, et al., 1986); these computer codes were originally developed by the principal author for groundwater studies at the Hanford Site. The FLASH and FLAME computer codes are maintained under a formal software control procedure (Baca, 1990). The source codes have been thoroughly tested using the INEL's CRAFT and FORWARN FORTRAN analyzers. In addition, these codes are currently being independently verified and benchmark tested by researchers at Washington State University.

The development of the FLASH code is aimed at providing environmental scientists with a versatile and reliable predictive tool. Thus numerical model, and its counterpart, are expected to have wide applications to performance assessments and environmental restoration studies at the INEL.

1.3 Objectives and Scope

The primary objective of this report is to provide formal documentation for the FLASH computer code, Version 3.0. The scope of the documentation includes:

- o a description of the conceptual models for which the numerical model is applicable,
- o discussion of the mathematical theory and assumptions,
- o derivations of the numerical techniques and algorithms used in the code,
- o presentation of computational examples to illustrate the capability of the numerical model, and
- o input instructions for general use of the computer code.

Input files for computational examples are presented in an appendix and can be used to gain familiarity with the use of the FLASH code.

2.0 CONCEPTUAL FRAMEWORK

The applicability of a numerical model to a particular physical system greatly depends on the completeness and correctness of the assumed conceptual model. A conceptual model, as used here, is a description of the: (1) unique physical features and properties of the natural system that influence its behavior, (2) the physical processes and coupling effects that control the system response, and (3) the fundamental assumptions that are made in formulating the mathematical models. The conceptual framework used in developing the FLASH computer code is presented in this section.

2.1 Physical Setting

Arid sites, such as the INEL, NTS and Hanford, are highly attractive for waste disposal because of ideal climatic conditions, thick vadose zones and low average annual precipitation, eg., 20 cm (~ 8 in) or less. At such sites, the average annual infiltration into the geologic setting can be quite low, eg., less than 10 cm (~ 4 in). Under these conditions, the surficial sediments can provide a high degree of isolation to waste buried in shallow pits, trenches and soil vaults. However, the occurrence of several and closely spaced precipitation events can result in pulses of infiltration, which in turn, may enhance waste migration. A scenario of concern at the INEL is a combination of events such as warm winds, rapid snowmelt and heavy rains that produce water ponding and infiltration (Vigil, 1988).

To model subsurface flow phenomena at the INEL, the geologic setting is conceptualized as: (1) thick vadose zone composed of thin surficial sediments and a sequence of basalt strata with interbedded sediments and (2) a deep saturated zone composed on fractured-porous basalt strata, see Figure 2. The basalt strata constitutes about 95 percent of the geologic profile. Individual basalt flows generally exhibit considerable structural and textural variation and are heterogeneous, anisotropic, fractured-porous media. At certain sites, such as the RWMC, the basalt geology is reasonably well characterized (Anderson and Lewis, 1989; Knutson, et al., 1992).

Data compiled by Knutson, et al. (1992) indicate that basalt flow thicknesses vary from .31 m (1 ft) to 17.2 m (56 ft) with an average of 4.6 m (15 ft). These authors define the generic elements of a typical basalt flow as consisting of: (1) top vesicular zone, (2) central zone, and (3) bottom vesicular zone. In general, the vesicular zones have significantly higher permeability than the central zone. Observations by Rightmire and Lewis (1987) suggest that fracture infilling material was transported through interconnected fracture networks.

Figure 2. Conceptual Sketch of Physical Setting

The void structure of the basalt flows is quite diverse (Knutson, et al., 1992). Porosity of vesicular zones ranges from about 5% to 22%, whereas, the porosity of dense central zones ranges less than 1% to about 3%. Permeability measurements on basalt core suggest that the porosity can be very poorly interconnected or conversely very well interconnected by micro-fractures. However, field injection and tracer tests (Schmalz, 1969) indicate that fractures are the principal cause of the large scale rock mass permeability. Horizontal permeabilities measured at various different sites have ranged from 40 to 120 Darcies. In contrast, the matrix permeability of basalt is typically in the milli-Darcy range.

2.2 Fluid Flow in the Variably Saturated Zone

The surficial sediments are primarily composed of eolian and alluvial sand, loess, and lacustrine deposits (Barraclough, et al., 1976). Moisture movement through the sediments occurs at different rates depending on depth (Pittman, 1989; Davis and Pittman, 1990; McElroy and Hubbell, 1990). For example, in the upper 0.1 to 1 m of sediments, moisture movement is very dynamic and responds quickly to precipitation events as well as to periods of evaporation. Below this dynamic zone is a zone where the patterns of moisture movement are more gradual. At greater depth, changes in moisture movement are very small so that the moisture profile appears to be at steady-state.

Moisture movement occurs as a result of liquid and vapor phase flow (Hillel, 1971; Campbell, 1985). However, the vapor phase component is generally negligibly small. Liquid phase flow occurs as a result of capillary and gravity forces. Rates of liquid flow are functions of the: (1) moisture flux at the surface, (2) plant uptake, and (3) moisture retention and unsaturated hydraulic conductivity properties (McElroy, 1990; Kaminsky, 1991) of the surficial sediments. These flow phenomena in porous materials are reasonably well understood and described by Darcian flow theory.

In the case of the basalt strata, the physics of partially saturated flow are not well understood or defined. Although by analogy, it is expected that partially saturated flow in the rock matrix occurs by the same physical processes that occur in the soil. Only limited data (Bishop, 1991) currently exist on the retention and unsaturated hydraulic conductivity properties of basalt. The nature of the unsaturated flow properties of discrete fractures are presently unknown. Available theoretical work (Rasmussen, et al., 1987) suggests that fractures play a minimal role until the medium becomes fully saturated.

For the purposes of flow modeling, partially saturated flow in the vadose zone is conceptualized in terms of the following assumptions:

- o the moisture flux at the surface is known and no plant uptake occurs,
- o the hydraulic properties of the surficial sediments, interbeds, and basalt strata are homogeneous and anisotropic,
- o moisture movement occurs as liquid phase transport only,
- o the moisture retention (i.e., characteristic curve) properties of the sediments and basalt are non-hysteretic,
- o Darcy's law for unsaturated flow is applicable to the fractured-porous basalt strata.

In general, the above idealization is reasonable and applicable to conditions at the INEL.

The last assumption, however, requires validation with laboratory and/or field data.

2.3 Fluid Flow in a Free Surface Aquifer

Dynamics of groundwater in a basalt geology are, to a large degree, controlled by the layered nature of the lava flows. In general, the top and bottom vesicular zones determine the rates and directions of horizontal groundwater flow because of their higher permeability. Flow along individual flow tops and bottoms are often hydraulically interconnected by vertical fractures through the central zone.

At relatively large scales (i.e., 100's of meters to kilometers), groundwater flow in the fractured-porous basalt geology can be modeled using the so-called "equivalent porous media" (EPM) approximation. This approximation is based on the idea that the large rock volume contains a sufficient number of fractures to exhibit an average rock mass permeability. Snow (1969) and Long, et al. (1982) have proposed theoretical criteria for judging the applicability of the EPM approximation.

Based on the aspects outlined above, groundwater flow in the saturated zone is conceptualized in terms of the following characteristics:

- o the hydrostratigraphic units in the basalt geology are laterally extensive, continuous, and characterized as anisotropic,
- o the flow system is unconfined with predominantly horizontal flow (i.e., Dupuit-Forchheimer approximation), and
- o the large scale flow is described as Darcian flow in an equivalent porous medium,

Past groundwater modeling studies at the INEL have used this type of conceptualization with considerable success. Robertson (1974), and more recently, Arnett et al. (1990) have modeled various contaminant plumes in the Snake River Plain aquifer and obtained good comparisons with field measurements.

2.4 Heat Transport in the Soil

Soil temperature is an important environmental variable because of its effects on the physical and chemical properties of contaminants. Heat transfer in the vadose zone occurs as a result of atmospheric heating and cooling at the soil surface. Principal modes of this surface heat transfer include: (1) long and short wave radiation, (2) evaporation, and (3) convection. Data for the RWMC (Pittman, 1989; Davis and Pittman, 1990) show that soil temperatures vary in a harmonic fashion over an annual cycle. These variations penetrate to a depth of about 5 m (16 ft).

Thermal energy moves through the vadose zone by the processes of conduction and advection. The advective component, however, is negligibly small because of the low velocity of the pore-water movement. Available data indicates that thermal properties of the surficial sediments are relatively similar to those of basalt. For example, the thermal diffusivity of the sediments is estimated to be about $4.3 \times 10^{-3} \text{ cm}^2/\text{s}$, whereas, that of basalt is about $7.5 \times 10^{-3} \text{ cm}^2/\text{s}$. Because the mechanism of heat transfer in soil is relatively simple and the thermal properties are fairly uniform, soil temperature can be accurately predicted with a numerical model of heat conduction.

Based on the aspects described above, heat transport in the surficial sediments and basalt is conceptualized in terms of the following:

- o heat transport occurs by pure conduction only,
- o heat flux variation at the surface drives heat transport, and
- o the earth materials are characterized as porous media with homogeneous thermal properties.

The appropriateness of this conceptual representation has been demonstrated by the authors through model applications and comparisons to available field data (Pittman, 1989).

3.0 MATHEMATICAL MODELS AND ASSUMPTIONS

3.1 Introduction

To provide a general predictive tool for analysis of waste disposal sites, the FLASH computer code has been written to solve three general equations: (1) Richards' equations for variably saturated flow in the vadose zone, (2) the Dupuit-Forchheimer equation for saturated groundwater flow in an unconfined aquifer, and (3) the conduction heat transfer equation. The computer code is written to solve these equations in two-dimensions for transient or steady-state flow conditions.

3.2 Fluid Flow Equation for the Variably Saturated Zone

The mathematical model for variably saturated flow in the vadose zone is based on the continuity equation for conservation of mass and Richards' extension of Darcy's law for unsaturated flow. The combination of these two equations produces the general governing equation for fluid flow in an unsaturated soil. This equation, modified to consider simultaneous saturated and unsaturated conditions, is expressed in the head-based form as:

$$\left[S_s \frac{\theta}{\theta_s} + C(\psi) \right] \frac{\partial \psi}{\partial t} = \nabla \cdot [\bar{K}(\psi) (\nabla \psi + \hat{k})] \quad (1)$$

where ψ is the pressure head (cm), S_s is the specific storage (1/cm), θ and θ_s are the volumetric moisture content and saturated moisture content (i.e., porosity), $\bar{K}(\psi)$ is the unsaturated hydraulic conductivity tensor (cm/s), and $\hat{k}$ is the unit vector in the vertical direction (positive upwards).

The two-dimensional, component form of the governing equation is

$$\left[S_s \frac{\theta}{\theta_s} + C(\psi) \right] \frac{\partial \psi}{\partial t} = \frac{\partial}{\partial x} \left(K_x(\psi) \frac{\partial \psi}{\partial x} \right) + \frac{\partial}{\partial z} \left[K_z(\psi) \left(\frac{\partial \psi}{\partial z} + 1 \right) \right] \quad (2)$$

The nonlinear coefficient $C(\psi)$ is the specific moisture capacity (1/cm), is defined by

$$C(\psi) = \frac{\partial \theta}{\partial \psi} \quad (3)$$

which is the slope of the soil moisture characteristic curve. The above equation, in most applications, is strongly nonlinear. As described later, this equation is solved iteratively using either a Picard or Newton iteration technique.

Note that for positive pressure heads, $\psi > 0$, $\theta = \theta_s$, $K(\psi) = K_s$, and $C(\psi) = 0$, reducing the variable saturated equation (1) to that for confined flow:

$$S_s \frac{\partial \psi}{\partial t} = \nabla(K(\nabla \psi + \hat{k})) \quad (4)$$

Rigorous derivations of the variably saturated flow equation can be found in porous media textbooks (Hillel, 1971, Bear, 1972) and in the technical literature (Celia, et al., 1991).

The mathematical theory, however, makes a number of basic assumptions:

- o Low Reynolds number and single phase flow,
- o Vapor phase flow is negligible,
- o Non-hysteretic soil hydraulic characteristics,
- o No internal sources or sinks of fluid,
- o Fluid properties, i.e., density and viscosity, are independent of temperature, and
- o Hydraulic properties of the porous continuum are volume averages.

In the model formulation implemented in the FLASH computer code, the further assumption is made that the conductivity tensor is aligned with the horizontal and vertical axes.

The variably saturated flow equation is solved with any combination of three types of boundary conditions

1. Dirichlet or specified pressure head

$$\psi = \psi(x_b, z_b, t)$$

2. Neumann or prescribed flux

$$-K_x(\psi) \frac{\partial \psi}{\partial x} \hat{n}_1 - K_z(\psi) \frac{\partial \psi}{\partial z} \hat{n}_2 = q(t)$$

3. Unit gradient or free drainage

$$q_f = -K_z(\psi) \hat{k}$$

where x_b and y_b are the coordinates of the boundary with Dirichlet boundary conditions; $\hat{n}_1$ and $\hat{n}_2$ are the components of the outward pointing unit normal; q_f is the fluid flux.

3.3 Fluid Flow Equations for a Free Surface Aquifer

The mathematical model for areal groundwater flow in an unconfined aquifer originates from continuity and Darcy's law. By making the assumption that the groundwater flow is essentially horizontal, the applicable governing equation is the so-called Dupuit-Forchheimer equation (Freeze and Cherry, 1979). This well known governing equation is expressed in two-dimensional form as:

$$S_y \frac{\partial h}{\partial t} = \frac{\partial}{\partial x} \left(K_x h \frac{\partial h}{\partial x} \right) + \frac{\partial}{\partial y} \left(K_y h \frac{\partial h}{\partial y} \right) \quad (5)$$

where h is the water level elevation (cm), S_y is the specific yield (1/cm), K_x and K_y are the saturated hydraulic conductivity (cm/s) in the x- and y-directions.

This formulation is limited by the assumptions listed previously with the addition of three other fundamental assumptions:

- o Vertical components of groundwater flow are small,
- o Fluid exchanges across the capillary fringe are negligible, and
- o The bottom boundary of the aquifer is horizontal and h represents the saturated thickness.

The Dupuit-Forchheimer equation for flow in an unconfined aquifer is mildly nonlinear. As implemented in the FLASH computer code, this formulation is solved iteratively using the Newton-Raphson method.

Boundary conditions used in solving the Dupuit-Forchheimer flow equation consist of two types:

1. Dirichlet or specified pressure head

$$h = h(x_b, z_b, t)$$

2. Neumann or prescribed flux

$$-T_x \frac{\partial h}{\partial x} \hat{n}_1 - T_z \frac{\partial h}{\partial z} \hat{n}_2 = q_f(t)$$

where T_x and T_y are the transmissivities; q_f is the fluid flux; all other quantities are as previously defined.

3.4 Heat Transport Equation for the Vadose Zone

The principle of energy conservation together with Fourier's law provides the basis for the mathematical model of heat transport in the vadose zone. The balance of thermal energy is expressed as governing equation of the form

$$S_t \frac{\partial T}{\partial t} = \frac{\partial}{\partial x} \left(D_t \frac{\partial T}{\partial x} \right) + \frac{\partial}{\partial y} \left(D_t \frac{\partial T}{\partial y} \right) \quad (6)$$

where T is the temperature ($^{\circ}\text{C}$), S_t and D_t are the average volumetric heat capacity ($\text{cal}/\text{cm}^3\text{-}^{\circ}\text{C}$) and thermal conductivity ($\text{cal}/\text{s-cm-}^{\circ}\text{C}$). The average thermal properties are computed as a weighted average of the properties of the soil and water according to the formulas:

$$S_t = \rho_f c_f \theta + (1 - \theta) \rho_s c_s \quad (7)$$

$$D_t = \theta D_f + (1 - \theta) D_s \quad (8)$$

where ρ_f and ρ_s are the densities of the fluid and soil, c_f and c_s are the specific heat capacities of the fluid and soil, D_f and D_s are thermal conductivities of the fluid and soil.

The applicability of this formulation is constrained by the following set of assumptions:

- o The fluid and soil are in local thermodynamic equilibrium,
- o Convective heat transport is small compared to transport by conduction.
- o Thermal properties of the fluid are independent of temperature,
- o Thermal properties of the soil are independent of moisture content,

Because the heat transport equation is independent of moisture content, it can be solved separately from the variably saturated flow equation.

Two types of boundary conditions apply to the heat transport equation. These boundary conditions are:

1. Dirichlet or specified temperature

$$T = T(x_b, z_b)$$

2. Neumann or prescribed flux

$$-D_t \frac{\partial T}{\partial x} \hat{n}_1 - D_t \frac{\partial T}{\partial z} \hat{n}_2 = q_h$$

where q_h is the heat flux; all other quantities are as previously defined.

4.0 FINITE ELEMENT FORMULATION

A general finite element solution approach was developed to solve the partial differential equations for fluid flow and heat transport, described in the previous section. The finite element approach was selected because it provides a computational capability that easily accommodates the complex and variable geometry of hydrogeologic features. This section describes the basic computational approach, numerical techniques and aspects of computer implementation.

4.1 Computational Approach

The finite element approach is an integral based method for solving linear and nonlinear partial differential equations on computational mesh composed of quadrilateral, triangular and/or linear elements. As implemented in the FLASH computer code, these elements may have straight or curved sides. These computational elements are illustrated in Figure 3.

Figure 3. Types of Finite Elements used in Constructing a Computational Mesh

4.2 Galerkin Weak Statement

A general finite element algorithm for the fluid flow and heat conduction equations was developed by applying the Galerkin method of weighted residuals (Baker, 1983). The fundamental concept is to form a functional χ as the integral of the product of the residual error ϵ and a set of weighting functions ω_j . The Galerkin functional is

$$\chi = \int_{\mathfrak{R}} \epsilon \omega_j d\bar{x} \quad (1)$$

where $\mathfrak{R}$ is the domain of interest, ϵ is formed from the governing equations, and $\bar{x}$ represents the generalized spatial coordinates (x, y, z) . Baca, et al. (1984) have shown that a direct superposition approach can be used to construct a functional equation that is applicable to flow and transport in a "fractured-porous" media.

Mathematically, the Galerkin weak statement for fractured-porous media χ_{fp} is derived from

$$\chi_{fp} = \int_{\Omega_c} \epsilon^c \omega_j dR + \int_{\Omega_d} \epsilon^d \omega_j dl \quad (2)$$

where ϵ^c and ϵ^d are the residual error terms for the continuum domain Ω_c and discrete domain Ω_d , respectively.

As in standard finite element procedure, the weak statement will be partitioned into subdomains or elements so that

$$\chi_{fp} = \chi_{fp,1} + \chi_{fp,2} + \chi_{fp,3} + \dots + \chi_{fp,M} = \sum_{i=1}^M \chi_{fp,i} \quad (3)$$

where M is the total number of elements. Setting $\chi_{fp} = 0$ imposes a requirement of orthogonality so that the weak statement becomes an error distribution principle (Collatz, 1960) by which the residual ϵ is minimized over the domain $\mathfrak{R} = \Omega_c \cup \Omega_d$.

In this superposition approach, the continuum domain is represented by a mesh of two-dimensional, isoparametric, finite elements (eg., quadrilaterals and/or triangles) whereas, the discrete domain is represented by a network of line elements. The computational mesh used in this approach is the same as any standard finite element mesh with the exception that the line elements are superimposed along the boundaries of the two-dimensional elements, see Figure 4. Because the two types of elements share the same nodes, continuity of flow and transfer of thermal energy between the two elements is automatically enforced.

Figure 4. Superposition of Finite Elements

In developing the finite element algorithm for solution of the governing equations, a method referred to as the Taylor-Galerkin approach was used. This approach (Baca, et al., 1978) is an extension of the classical Galerkin method and is based on the use of a Taylor series expansion of the residual error. To demonstrate the approach, it is applied to the specific case of the heat conduction equation. In this particular case, the residual error is approximated by

$$\epsilon^{m+1} = \epsilon^m + \frac{\partial \epsilon^m}{\partial T} \Delta T \quad (4)$$

Substituting this expression into equation (1) for an arbitrary element yields

$$\chi_e = \int_{\Omega_e} \epsilon^{m+1} \omega_j d\bar{x} = \int_{\Omega_e} \left(\epsilon^m + \frac{\partial \epsilon}{\partial T} \Delta T \right) \omega_j d\bar{x} \quad (5)$$

where m is the iteration index and ΔT is the incremental change in temperature. Setting this equation to zero and rearranging the equation to place the unknowns on the left handside produces

$$\int_{\Omega_e} \frac{\partial \epsilon}{\partial T} \Delta T \omega_j d\bar{x} = - \int_{\Omega_e} \epsilon^m \omega_j d\bar{x} \quad (6)$$

Once integrated, this equation leads to a set of algebraic equations for the finite element of the form

$$[J_e] \{\Delta T\} = \{R_e\} \quad (7)$$

where $[J_e]$ is called the elemental Jacobian matrix, $\{\Delta T\}$ is the solution vector containing the incremental changes of temperature at each node point, and $\{R_e\}$ is called the elemental load vector and contains known information obtained from integration of $\{\epsilon^m\}$ and the boundary conditions.

Specific expressions for $[J_e]$ and $\{R_e\}$ are obtained as follows. First, define the residual error in terms of the heat conduction equation:

$$\epsilon^m = S_i \frac{\partial T}{\partial t} - \nabla \cdot (D_i \nabla T) \quad (8)$$

The $\{R_e\}$ vector is thus expanded

$$\{R_e\} = - \int_{\Omega_e} \omega_j \left[S_i \frac{\partial T}{\partial t} - \nabla \cdot (D_i \nabla T) \right] d\bar{x} \quad (9)$$

Applying the divergence theorem to the integral of the spatial derivative term

$$\{R_e\} = - \int_{\Omega_e} \left[\omega_j S_i \frac{\partial T}{\partial t} + \nabla \omega_j \cdot D_i \nabla T \right] d\bar{x} + \int_{\partial \Omega_e} \omega_j D_i \nabla T \cdot \bar{n} dS \quad (10)$$

where $\bar{n}$ is the outward pointing normal on the boundary defined by $\partial \Omega_e$. The quantity $D_i \nabla T$ in the surface integral can be replaced by the heat flux $\bar{q}_h$ vector; thus, one can write

$$\{R_e\} = - \int_{\Omega_e} \left[\omega_j S_i \frac{\partial T}{\partial t} + \nabla \omega_j \cdot D_i \nabla T \right] d\bar{x} - \int_{\partial \Omega_e} \omega_j \bar{q}_h \cdot \bar{n} dS \quad (11)$$

The expression for the Jacobian matrix is derived from equation (11) by differentiating with respect to temperature. Specifically,

$$[J_e] = \int_{\Omega_e} \left[\omega_j S_i \frac{\partial}{\partial T} \left(\frac{\partial T}{\partial t} \right) + \nabla \omega_j \cdot D_i \frac{\partial}{\partial T} (\nabla T) \right] d\bar{x} \quad (12)$$

The surface integral term vanishes in the Jacobian because the heat flux is not temperature dependant. In the above expression, the derivative of the time-dependent term was approximated as follows:

$$\frac{\partial}{\partial T} \left(\frac{\partial T^{n+1}}{\partial t} \right) = \frac{\partial}{\partial T} \left(\frac{\alpha}{\Delta t} (T^{n+1} - T^n) + (1 - \alpha) \frac{\partial T^n}{\partial t} \right) = \frac{\alpha}{\Delta t} \quad (13)$$

where n is the time plane index, α is a weighting factor, and Δt is the time-step. The formula in the parenthesis is derived in a subsequent section. The final form for the Jacobian matrix becomes:

$$[J_e] = \int_{\Omega_e} \left[\omega_j S_i \frac{\alpha}{\Delta t} \omega_i + \nabla \omega_j \cdot D_i \nabla \omega_i \right] d\bar{x} \quad (14)$$

In equations (11) and (12), the temperature over the domain of the finite element was approximated by

$$T(\bar{x}, t) = \sum_{i=1}^N \omega_i T_i \quad (15)$$

where N is number of node points, ω_i is the set of basis functions and T_i is the set of temperatures at the node points. The basis functions are selected to be the same as the weighting functions, as required by the Galerkin procedure. Integrating the Jacobian matrix and load vector by a Gauss-Legendre quadrature method produces the final elemental matrices.

Combining the elemental matrices (Burnett, 1987) for all the elements in the mesh produces a system of symmetric, sparse, and banded algebraic equations of the general form:

$$[J] \{\Delta T\} = \{R\} \quad (16)$$

where $[J]$ is the global Jacobian matrix, $\{\Delta T\}$ is the solution vector containing the incremental changes of temperature at all the node points, and $\{R\}$ is the global load vector. The solution of equation (16) is obtained by Gaussian elimination techniques (see section 4.6) and then used in the iteration formula:

$$\{T\}^{m+1} = \{T\}^m + \{\Delta T\} \quad (17)$$

Because the heat conduction equation is linear, only a single iteration of the above is required.

4.3 Newton Based Weak Statement

An important characteristic of the governing partial differential equation for variably-saturated flow is its strongly nonlinear nature. Because of the nonlinearity, an iterative method is required to obtain numerical solutions. A weak statement for the nonlinear equation was developed from the Taylor-Galerkin weak statement. This approach produces the iteration formula for residual error:

$$\epsilon^{m+1} = \epsilon^m + \frac{\partial \epsilon^m}{\partial \psi} \Delta \psi \quad (18)$$

Inserting this expression into the general equation for the functional (see section 4.2) gives:

$$\int_{\Omega} \left(\epsilon^m + \frac{\partial \epsilon^m}{\partial \psi} \Delta \psi \right) \omega_j d\bar{x} = 0 \quad (19)$$

Because the first term in the functional represents known quantities the equation can be rearranged

$$\int_{\Omega} \left(\frac{\partial \epsilon^m}{\partial \psi} \Delta \psi \right) \omega_j d\bar{x} = - \int_{\Omega} \epsilon^m \omega_j d\bar{x} \quad (20)$$

This equation, once expanded using the finite element procedure (Burnett, 1987), leads to a system of unsymmetric, sparse, and banded algebraic equations of the form

$$[J] \{ \Delta \psi \} = \{ R \} \quad (21)$$

where $[J]$ is the global Jacobian matrix, $\{ \Delta \psi \}$ is the solution vector containing the incremental changes of pressure head at each node, and $\{ R \}$ is the global load vector. The solution of equation (21) is used in the iteration formula:

$$\{ \psi \}^{m+1} = \{ \psi \}^m + \{ \Delta \psi \} \quad (22)$$

Using $\{ \psi \}^{m+1}$, the matrices in equation (4) are updated and then solved repeatedly along with equation (22) until convergence is achieved, i.e., $|\Delta \psi| < \epsilon$.

Specific expressions for the elemental matrices, $[J_e]$ and $\{ R_e \}$, are obtained as follows.

The residual error for the flow equation is:

$$\epsilon^m = \left(S_s \frac{\theta}{\theta_s} + \frac{\partial \theta}{\partial \psi} \right) \frac{\partial \psi}{\partial t} - \nabla \cdot K(\nabla \psi + \hat{k}) \quad (23)$$

The load vector is thus

$$\{R_e\} = - \int_{\Omega} \left\{ \left(S_s \frac{\theta}{\theta_s} + \frac{\partial \theta}{\partial \psi} \right) \frac{\partial \psi}{\partial t} \omega_j + \nabla \omega_j \cdot K(\nabla \psi + \hat{k}) \right\} d\bar{x} - \int_{\partial \Omega} \omega_j \bar{q}_f \cdot \bar{n} dS \quad (24)$$

where $\bar{q}_f$ in the surface integral is the Darcy flux vector. The Jacobian matrix is given by

$$[J_e] = \int_{\Omega} \left\{ \left[\left(S_s \frac{\theta}{\theta_s} + \frac{\partial \theta}{\partial \psi} \right) \frac{\alpha}{\Delta t} \omega_i + \frac{\partial^2 \theta}{\partial \psi^2} \frac{\partial \psi}{\partial t} \right] \omega_j + \nabla \omega_j \cdot \left(K \nabla \omega_i + \frac{\partial K}{\partial \psi} (\nabla \psi + \hat{k}) \right) \right\} d\bar{x} \quad (25)$$

In both equations (24) and (25), the divergence theorem was applied to reduce the second order derivative terms. Also, the derivative of the time-dependent term was approximated by

$$\frac{\partial}{\partial \psi} \left(\frac{\partial \psi^{n+1}}{\partial t} \right) = \frac{\partial}{\partial \psi} \left(\frac{\alpha}{\Delta t} (\psi^{n+1} - \psi^n) + (1 - \alpha) \frac{\partial \psi^n}{\partial t} \right) = \frac{\alpha}{\Delta t} \quad (26)$$

where n is the time plane index, α is a weighting factor, and Δt is the time-step.

4.4 Picard Based Weak Statement

Development of a Picard based finite element solution for the fluid flow equation requires generation of a weak statement. The weak statement is formed as the integral of the product of the residual error and a set of weighting functions. An expression for the residual error is derived from the governing partial differential equation for variably saturated flow.

As described by Celia, et al. (1990), numerical solutions of the mixed-form of Richards' equation yields results with excellent mass conservation properties. This mixed-form of the governing equation is derived directly from the following form of the flow equation:

$$\left(S_s \frac{\theta}{\theta_s} \right) \frac{\partial \psi}{\partial t} + \frac{\partial \theta}{\partial t} = \nabla \cdot K(\nabla \psi + \hat{k}) \quad (27)$$

where θ is the volumetric water content, θ_s is the saturated water content or porosity, S_s is the specific storage coefficient and $\hat{k}$ is the unit normal pointing up.

The mixed-form is derived by first approximating θ through the iteration space using a first order Taylor series:

$$\theta^{m+1} = \theta^m + \left(\frac{d\theta}{d\psi} \right)^m (\psi^{m+1} - \psi^m) \quad (28)$$

where m is the iteration index. By differentiating both sides of this expression, one obtains

$$\frac{\partial \theta^{m+1}}{\partial t} = \frac{\partial \theta^m}{\partial t} + \left(\frac{d\theta}{d\psi} \right)^m \left(\frac{\partial \psi^{m+1}}{\partial t} - \frac{\partial \psi^m}{\partial t} \right) \quad (29)$$

where all the above quantities are at the $n + 1$ time level. Substituting this approximation into equation (1) and rearranging yields the desired mixed-form of Richards' equation

$$\left(S_s \frac{\theta}{\theta_s} \right) \frac{\partial \psi^m}{\partial t} + C(\psi) \frac{\partial \delta}{\partial t} - \nabla \cdot K(\nabla \delta + \hat{k}) + \nabla \cdot K \nabla \psi^m - \frac{\partial \theta^m}{\partial t} \quad (30)$$

where $C(\psi) = \partial \theta / \partial \psi$ and $\delta = \psi^{m+1} - \psi^m$. In the above equation, the term $\partial \psi^m / \partial t$ is set to zero for unsaturated conditions, whereas, the terms δ and $\partial \theta^m / \partial t$ automatically go to zero as θ goes to θ_s , i.e., saturation. Because the state variable is now δ , the above mixed-form is naturally suited to a Picard type iteration method (Huyakorn and Pinder, 1983). For unsaturated conditions, the pressure head at the new iteration is computed from the iteration formula

$$\psi^{m+1} = \psi^m + \delta \quad (31)$$

The weak statement for the mixed-form of Richards' equation is formulated using the classical Galerkin approach (see section 4.2). The weak statement for an arbitrary element is written as

$$\int_{\Omega_e} \left\{ \left(S_s \frac{\theta}{\theta_s} \right) \frac{\partial \psi^m}{\partial t} + C(\psi) \frac{\partial \delta}{\partial t} - \nabla \cdot K(\nabla \delta + \hat{k}) - \nabla \cdot K \nabla \psi^m + \frac{\partial \theta^m}{\partial t} \right\} \omega_j d\bar{x} = 0 \quad (32)$$

Applying the divergence theorem to reduce the second-order derivatives, the final form of the Picard based weak statement is obtained:

$$\begin{aligned} \int_{\Omega_e} \left\{ \omega_j \left[\left(S_s \frac{\theta}{\theta_s} \right) \frac{\partial \psi^m}{\partial t} + C(\psi) \frac{\partial \delta}{\partial t} + \frac{\partial \theta^m}{\partial t} \right] + \nabla \omega_j \cdot [K(\nabla \delta + \hat{k}) + K \nabla \psi^m] \right\} d\bar{x} \\ - \int_{\partial \Omega_e} \omega_j [K(\nabla \delta + \hat{k}) + K \nabla \psi^m] \cdot \vec{n} dS = 0 \end{aligned} \quad (33)$$

The first integral, in the above equation, applies to each finite element in the domain Ω_e ; whereas, the surface integral applies to that portion of the element boundary $\partial \Omega_e$ where fluid fluxes are specified. Application of the standard finite element procedure (Burnett, 1987) produces a matrix problem of the general form

$$[A] \{\delta\} = \{R\} \quad (34)$$

where $[A]$ and $\{R\}$ are the global coefficient matrix and load vector; the coefficient matrix is symmetric, sparse and banded. The matrix equation is solved by Gaussian elimination techniques (see section 4.6) for each iteration until convergence is achieved by equation (31), i.e., $|\delta| < \epsilon$. Specific expressions for the elemental matrices are given by:

$$\{R_e\} = - \int_{\Omega_e} \left[\omega_j \left(S_s \frac{\partial \psi^m}{\partial t} + \frac{\partial \theta^m}{\partial t} \right) + \nabla \omega_j \cdot K(\nabla \psi^m + \hat{k}) \right] d\bar{x} - \int_{\partial \Omega_e} \omega_j \bar{q}_f \cdot \bar{n} dS \quad (35)$$

$$[A_e] = \int_{\Omega_e} \left[\omega_j C(\psi) \frac{\alpha}{\Delta t} \omega_i + \nabla \omega_j \cdot K(\nabla \delta + \hat{k}) \right] d\bar{x} \quad (36)$$

4.5 Time Integration Scheme

The Galerkin weak statement derived in the previous section utilized an approximation for the time derivatives of the pressure head, ψ , and the temperature, T . These quantities are approximated using a predictor-corrector method in conjunction with a Hermitian polynomial. This approach has been found to be significantly faster than the standard, weighted finite-difference method (Burnett, 1987).

4.5.1 Predictor-Corrector Algorithm

For simplicity, a simple two-step predictor-corrector algorithm was adopted. The algorithm uses an Euler predictor with a modified Euler corrector (Gerald and Wheatley, 1984). The predictor formula is a simple Euler method given by:

$$\phi_p^{n+1} = \phi^n + \Delta t \frac{d\phi^n}{dt} \quad (37)$$

where the state variable ϕ , represents either pressure head ψ or temperature T . The above predictor formula has a global error of order $O(\Delta t)$. The corrector formula is the modified Euler approximation and expressed as

$$\phi_c^{n+1} = \phi^n + \frac{\Delta t}{2} \left\{ \frac{d\phi_p^{n+1}}{dt} + \frac{d\phi^n}{dt} \right\} \quad (38)$$

which has a global error of $O(\Delta t^2)$. The calculation of ϕ_c is followed by a smoothing step which is based on the formula

$$\phi^{n+1} = (1 - \omega)\phi_c^{n+1} + \omega\phi^n \quad (39)$$

where ω is a weighting factor. A fixed value of 0.5 is set in the computer code.

4.5.2 Derivation of Approximating Formula

The time derivatives appearing in the previous predictor-corrector formulas are computed using an approximating Hermitian polynomial. The approximation formula was derived by first assuming an expression for the state variable as an explicit function of time. Specifically, the function is given by

$$\phi^{n+1} = \phi^n + at + bt^\alpha \quad (40)$$

for any point in space. The terms a , b and α are constants; t is the independent variable of time. It follows that the time derivative at the $n + 1$ time plane is then:

$$\frac{d\phi^{n+1}}{dt} = a + \alpha bt^{\alpha-1} \quad (41)$$

An expression for the constant b can be obtained from equation (40), namely

$$b = \frac{1}{t^{\alpha-1}} \left\{ \frac{\phi^{n+1} - \phi^n}{t} - a \right\} \quad (42)$$

The constant a is determined from equation (41) by setting $t = 0$. The result is the expression

$$a = \frac{d\phi^n}{dt} \quad (43)$$

Substituting the above expressions into equation (41) and replacing t with Δt , the following approximation formula is obtained.

$$\frac{d\phi^{n+1}}{dt} = \frac{\alpha}{\Delta t} (\phi^{n+1} - \phi^n) + (1 - \alpha) \frac{d\phi^n}{dt} \quad (44)$$

This formula is a simple Hermitian polynomial (Strang and Fix, 1973). For α equal to 1, the approximation reduces to a first-order backward difference. Similarly, for α equal to 2, the equation yields a second order approximation that is equivalent to the Crank-Nicolson approximation. In most applications, a value of α between 1.6 and 1.8 generally provides the most accurate results.

4.5.3 Automatic Time-Stepping

For the purpose of user convenience and overall computational efficiency, an automatic time-stepping algorithm is implemented in the computer code. This feature is particularly useful when simulating partially saturated flow in relatively dry soils. The algorithm automatically increases or decreases the time-step to assure a stable and accurate solution.

The strategy used in code varies the time-step in such a manner as to maintain a relatively uniform time truncation error. This accomplished by monitoring the values of $\max |\Delta\psi|$ and/or $\max |\Delta T|$ and comparing them against limits specified by the user. The time-step amplification factor is selected on the basis of an intricate criteria which considers:

- o the maximum and minimum changes in the state variables,
- o the number of iterations,
- o rate of convergence,
- o number of previous step reductions (if any).

For cases where the maximum values are exceeded for any of the above parameters, the time-step is reduced by a factor ranging from as little as 0.9 to as much as 0.5; the code then recalculates the solution with the smaller time-step. The algorithm monitors and limits the number of sequential time step reductions. For the case where the parameters are less than the minimum limiting values, the time-step is increased by a factor as little as 1.01 to as much as 1.9.

4.6 Solution of Algebraic Equations

The application of the Galerkin finite element method to the governing equations produces a large system of algebraic equations of the form

$$[A]\{x\} = \{b\} \quad (45)$$

The coefficient matrix $[A]$ is a banded, sparse matrix which contains the assembly of the elemental matrices for all finite elements in the mesh. The $\{x\}$ and $\{b\}$ vectors are the solution vector and load vector, respectively.

For the case of the Picard based weak statement, the finite element method produces a coefficient matrix that is banded and symmetric. In contrast, the Newton-Raphson based weak statement generates a banded but unsymmetric coefficient matrix. For either case, the system of equations are solved using a Gaussian elimination procedure without pivoting.

Two distinct algorithms are implemented in the computer code. The first method is a standard band solver algorithm that utilizes a skyline storage scheme (Tewarson, 1973). This solver is very fast but can be limited by the bandwidth of the $[A]$; the bandwidth is direct function of the node numbering. The second method is referred to as the frontal method (Hinton and Owen, 1977). This method, in general, is slower than the band solver but has the advantage that it is independent of bandwidth and requires much less storage. In the frontal method, the elimination process is carried out according to the element numbering.

Algorithms for minimizing matrix bandwidth (Cuthill, 1972, Gibbs, et al., 1976) exist that use strategies for optimizing the node number ordering. Similarly, techniques for minimizing the front width are based on reordering of element numbers (King, 1970). For problems with very large matrices, these minimization techniques often produce significant reductions of simulation run times.

5.0 COMPUTATIONAL EXAMPLES

A set of computational examples were selected and to demonstrate the general capability of the FLASH computer code. The examples serve to illustrate the application of the FLASH code to such simulation problems as modeling partially saturated flow, saturated-unsaturated flow, and conduction heat transfer. Examples for free surface flow are in preparation. The FLASH solutions to these computational examples are compared to analytical and benchmark numerical solutions. These input files for these computational examples are presented in Appendix I.

5.1 Partially Saturated Flow in a Dry Soil

5.1.1 Problem Statement

In this first computational example, the difficult problem of modeling partially saturated flow in a relatively dry soil column is considered. The physical setting is a vertical soil-column, idealized as a homogeneous porous medium, see Figure 5. Initially, the soil is at a very low saturation level, i.e., large negative pressure head. A wetting front is produced by maintaining the top surface at a near saturated condition. Vertical movement of the wetting front occurs by the action of capillary and gravity forces. The objective of the simulation problem is to compute the soil-moisture profile at various times.

Figure 5. Domain and Boundary Conditions for Variably Saturated Flow Problem

This particular computational example was originally used by Celia, et al. (1990) to test the stability and accuracy of various numerical techniques. The example is an exceptionally good one because the flow problem is a strongly nonlinear and exhibits a very sharp wetting front. These characteristics are typical of soil-moisture dynamics in arid site vadose zones such those at the INEL, Hanford and the Nevada Test Site.

One-dimensional flow in a partially-saturated porous medium is described by a nonlinear governing equation, known as Richards' equation, expressed as:

$$C(\psi) \frac{\partial \psi}{\partial t} = \frac{\partial}{\partial z} \left[K(\psi) \left(\frac{\partial \psi}{\partial z} + 1 \right) \right]$$

where ψ is the pressure head, $K(\psi)$ is the unsaturated hydraulic conductivity, t is time, and z is the distance along the vertical coordinate which is positive in the upward direction. The specific moisture capacity $C(\psi)$ is defined by $C(\psi) = \partial \theta / \partial \psi$; θ is the volumetric moisture content. The applicable boundary conditions are

$$\psi(0, t) = \psi_b$$

$$\psi(-L, t) = \psi_i$$

where L is the length of the soil column. As indicated above, the top boundary is fixed at a pressure head of ψ_b , whereas, the bottom boundary is held at the initial value ψ_i .

5.1.2 Benchmark Numerical Solution

Numerical solutions for this computation example are presented and discussed in Celia, et al. (1990) and Celia (1991). The model domain used by these authors consisted of a 100 cm vertical, soil column. A computational grid was used to represent the domain consisting of a column of grid blocks, each being 2.5 cm in length. Celia utilized the UNSAT1D computer code (Celia, 1991) to compute the pressure head and moisture content profiles at various times.

Hydraulic properties assigned to the idealized soil column were taken from data for the Jornada test site in New Mexico. These properties were represented using the van Genuchten formulas (van Genuchten, 1980) for the characteristic and unsaturated conductivity curves:

$$\theta(\psi) = \theta_r + \frac{\theta_s - \theta_r}{[1 + (\alpha |\psi|)^n]^m}$$

$$K(\psi) = K_s \frac{\{1 - (\alpha |\psi|)^{n-1} [1 + (\alpha |\psi|)^n]^m\}^2}{[1 + (\alpha |\psi|)^n]^{m/2}}$$

where θ is the volumetric moisture content, θ_r is the residual moisture content, θ_s is the saturated water content or porosity, and the α , n and m are fitting parameters. Specific values used in this computational example were $\alpha = 0.0335$, $n = 2$, $\theta_s = 0.368$ and $\theta_r = 0.102$. The fitting parameter m is computed from $m = 1 - 1/n$. The saturated hydraulic conductivity, K_s , and specific storage coefficient, S_s , were 9.22×10^{-3} cm/s and 1.0×10^{-5} cm⁻¹, respectively. The initial and surface boundary pressure heads were set at $\psi_i = 1000$ cm and $\psi_b = -75$ cm, respectively.

For the purposes of this computational example, the UNSAT1D code (Celia, 1991) was run to simulate the moisture movement for a 1 day simulation period. Pressure head and moisture content profiles at $t = 0.5$ days and $t = 1.0$ days were computed for use in making comparisons with results from the FLASH computer code. The UNSAT1D code was run using a fixed time-step $\Delta t = 600$ sec.

5.1.3 Numerical Solution

The FLASH computer code was setup to simulate this one-dimensional flow problem for a total simulation period of 1.0 day. A uniformly spaced, finite element mesh composed of 40 line elements and with a total of 81 nodes was used to represent the soil column. The FLASH code was run using the Picard iteration option, linear elements, and automatic time-stepping. As the simulation progressed, the time steps sizes varied from 600 sec to 8000 sec. Solutions for each time converged in 3 to 5 iterations.

Pressure head and moisture content profiles computed with the FLASH code are compared with those obtained with the UNSAT1D code for three time planes: $t = 1.5 \times 10^4$, 6.0×10^4 and 1.35×10^5 s. The graphical comparisons are summarized in Figures 6 and 7. The comparison of numerical results show exceptionally good agreement at the first time plane. However, for the second and third time planes, the results indicate that the solutions differ slightly with regard to the front location. This is probably due to the different approaches used to account for the variation of hydraulic conductivity across the element.

In any case, it is clear from the graphical comparisons that both codes do an excellent job of capturing the sharp wetting front without introducing spurious oscillations. Computer execution times for this computational example were 20 seconds for the FLASH code and 1000 seconds for the UNSAT1D code. Both computer codes were run on a 386 personal computer.

Figure 6. Comparison of Pressure Head Profiles
computed with FLASH and UNSAT1D codes

Figure 7. Comparison of Moisture Content Profiles
computed with FLASH and UNSAT1D codes

5.2 Saturated-Unsaturated Flow in a Two-Dimensional Domain

5.2.1 Problem Statement

The second computational example involves the modeling of two-dimensional flow in a system with both saturated and partially saturated flow regimes. The physical setting is conceptualized as a vertical cross-section with a shallow vadose zone and an unconfined aquifer, see Figure 8. Flow through the vadose zone is driven by a constant moisture flux at the surface. In the aquifer, a hydraulic gradient is maintained by fixed pressure head on the boundaries. The objective of this simulation problem is to compute the moisture content distribution throughout the domain.

This example, taken from Huyakorn, et al. (1989), has been used in previous computational testing of computer codes (Magnuson, et al., 1991). The example poses a good test case because of its nonlinear and linear behavior, large pressure variations and mixed boundary conditions. Many practical model applications exhibit these characteristics and conditions.

Figure 8. Domain and Boundary Conditions for Saturated-Unsaturated Flow Problem

Saturated-unsaturated flow in porous media is described by the nonlinear governing equation:

$$\left[S_s \frac{\theta}{\theta_s} + C(\psi) \right] \frac{\partial \psi}{\partial t} = \frac{\partial}{\partial x} K(\psi) \frac{\partial \psi}{\partial x} + \frac{\partial}{\partial z} K(\psi) \left(\frac{\partial \psi}{\partial z} + 1 \right)$$

where S_s is the specific storage and θ_s is the saturated moisture content; all other parameters are as previously defined. The boundary conditions on the physical system are those used by Huyakorn, et al. (1989):

- o Constant flux q on the soil surface,
- o No flow on the vertical boundaries of the vadose zone,
- o Fixed pressure heads on vertical boundaries of the aquifer, and
- o No flow on the bottom boundary.

The prescribed pressure heads on the boundary of the aquifer were based on height of the water column and were selected to produce flow from left to right.

5.2.2 Benchmark Numerical Solution

A number of independent numerical solutions are available in the literature for this computational example. The numerical solutions obtained by Magnuson, et al. (1990) with the PORFLO-3 code were selected for benchmark comparisons. For their numerical solutions, these authors used a finite difference grid consisting of 31 nodes in the horizontal direction and 27 nodes in the vertical direction. The grid spacing was uniform in the horizontal direction but was graded in the vertical direction.

Soil hydraulic properties assigned to the porous domain were taken from Huyakorn, et al., (1989). These authors utilized the analytic equations for the characteristics and hydraulic conductivity curves of the form:

$$\theta(\psi) = \theta_r + \frac{(\theta_s - \theta_r)}{[1 + (\alpha |\psi|^\beta)]^\gamma}$$

$$K(\psi) = K_s \left[\frac{(\theta - \theta_r)}{(\theta_s - \theta_r)} \right]^\tau$$

where α , β , γ and τ are fitting parameters. Parameter values used in this example were taken from Magnuson, et al. (1990) and are listed below

$$\begin{aligned} \alpha &= 0.2 & \beta &= 2. \\ \gamma &= -1 & \tau &= 4 \end{aligned}$$

$$\theta_s = 0.41 \quad \theta_r = 0.25$$

The saturated hydraulic conductivity was $K_s = 2.378 \times 10^{-3}$ cm/s and the surface moisture flux was $q = 3.171 \times 10^{-6}$ cm/s.

The initial condition for pressure head in the saturated zone was chosen to create the water table at an average height of 18 m above the bottom boundary. In the vadose zone, the pressure heads were initially set to a uniform pressure of -1000 cm.

5.2.3 Numerical Solution

The FLASH computer code was set up to model the variably saturated flow problem using a time-marching approach to steady-state. The specific storage coefficient was arbitrarily set at a value of $S_s = 0.01 \text{ cm}^{-1}$ for use in the time-dependent computations. The code was run using the Picard iteration and linear elements, and automatic time stepping. A graded finite element mesh was generated and superimposed on the rectangular domain. The mesh consisted of 42 quadrilateral elements in the horizontal direction and 60 elements in the vertical direction.

The pressure head distribution computed with the FLASH code reached steady-state after a time period of 100 days. The pressure head solution along a centered plane was summarized in a profile plot and compared graphically with PORFLO-3 results similar to those published in Magnuson et al. (1990). The comparison of pressure head profiles showed good agreement between the FLASH and PORFLO-3 results, see Figure 9. In addition, the moisture content profile along the same centered vertical plane is shown in Figure 10.

Figure 9. Comparison of Pressure Head Profiles
computed with FLASH and PORFLO-3 codes

Figure 10. Comparison of Moisture Content Profiles
computed with FLASH and PORFLO-3 codes

5.3 Heat Transport from a Buried Heat Source

5.3.1 Problem Statement

This computational example considers the problem of modeling heat transfer from an infinitely long cylindrical heat source, buried in a homogeneous soil. For simplicity, the soil is assumed to have uniform thermal properties, moisture content, and to be in thermal equilibrium with the atmosphere. The heat source is buried at a depth H and has a radius R_c , see Figure 11. Heat is transferred from the cylinder, through the soil, and to the soil surface at a steady-state rate. The objective of this computational test is to compute the temperature distribution in a localized soil region around the heat source.

Figure 11. Domain and Boundary Conditions for Heat Transport Problem

In terms of a boundary value problem, the heat transfer in the soil can be modeled in Cartesian coordinates using the governing equation

$$K_t \frac{\partial^2 T}{\partial x^2} + K_t \frac{\partial^2 T}{\partial z^2} = 0$$

where K_t is the thermal conductivity. The geometry of the problem has a plane of symmetry along the vertical axis which simplifies the boundary conditions. The boundary conditions are:

$$\frac{\partial T(0, z)}{\partial x} = 0$$

$$T(x_{R_c}, z_{R_c}) = T_c$$

$$T(x, 0) = T_s$$

$$T(\infty, z) = \text{finite}$$

Analytical and numerical solutions for this boundary were compared to illustrate the heat transport capability of the FLASH computer code.

5.3.2 Analytical Solution

The above heat transport problem has a closed-form analytical solution which is easily derived by first converting the governing equation to bipolar coordinates η and ψ (Arfken, 1970, pp. 97-102). The transformation to bipolar coordinates is achieved using

$$\eta = \ln \left[\frac{x^2 + (a - z)^2}{x^2 + (-a - z)^2} \right] \quad \psi = \frac{2ax}{x^2 + z^2 - a^2}$$

where

$$a = (H^2 - R_c^2)^{1/2}$$

Using the above expressions, the governing equation transforms to

$$\frac{\partial^2 T}{\partial \eta^2} = 0$$

with boundary conditions of

$$T(0, \psi) = 0 \quad T(\eta_c, \psi) = 1$$

which has the solution in the Cartesian space of

$$T(x, z) = \frac{T_c}{2} \ln \left[\frac{x^2 + (a - z)^2}{x^2 + (-a - z)^2} \right] / \ln \left[\frac{H + a}{R_c} \right]$$

This analytical solution was evaluated for the following parameter values:

$$K_t = 1 \quad T_c = 1 \quad T_s = 0$$

$$H = 4.8m \quad R_c = 1m$$

The resulting analytical temperature distribution is presented in Figure 12.

5.3.3 Numerical Solution

The FLASH computer code was set up to model the conduction heat transfer in the idealized porous medium. Only a half space was modeled because of the plane of symmetry. The temperature along the top boundary of the domain was set at $T_s = 0$ while the temperature at the cylinder surface was fixed at $T_c = 1$. The left boundary of the domain was treated as a natural or zero gradient boundary condition. To better satisfy the conditions at the right and bottom boundaries, the analytical solution was used to calculate and specify the boundary values.

A finite element mesh was generated that conformed to the cylinder and half space geometry. The mesh extended 15 m in the x-direction and -30 m in the y-direction. The mesh consisted of 119 isoparametric, quadrilateral elements with a total of 386 nodes. The FLASH computer code was run in the steady-state mode to yield a direct solution to heat transport problem. The numerical solution was compared with the analytical solution at all interior node locations. Both solutions agreed exceptionally well with the maximum difference of about $5 \times 10^{-4} \text{ }^\circ\text{C}$.

Figure 12. Comparison of Soil Temperature Distributions
computed with FLASH and Analytical Solution

6.0 INPUT GUIDE

6.1 Introduction

To apply the FLASH computer code to a given problem, the user constructs an input file that specifies the unique characteristics of the simulation. These characteristics typically include the hydraulic and/or thermal properties of the porous medium, initial and boundary conditions, computational grid, and solution procedure. The input file for the FLASH code is constructed using a narrative style command sequence. Input is read into the code using an algorithm that is designed with three basic objectives in mind: (1) to permit the user to incorporate detailed documentation of input data, (2) provide a flexible assembly of the data stream, and (3) allow user to easily construct input files for new applications using existing data files.

These objectives were met by a general and user-friendly input scheme with the following features:

- o comment lines may be inserted in any location to document data sources, units, assumptions and conditions,
- o data are entered as free-form, case and order independent,
- o simulation specified by use of command instructions and special keywords,
- o soil properties, initial conditions, and computational mesh may be input from external files,
- o default parameters are set for unspecified input, and
- o input data is processed and checked for consistency with general specifications.

The above features minimize, to a great degree, the need to refer to the input guide during data file preparation. The following conventions are used in constructing the input data file for a specific simulation:

- o In using the planar coordinates (x, z) or radial coordinates (r, z), the z -coordinate is positive upwards,
- o All hydraulic properties are in units of centimeters and seconds; all thermal properties are in units of calories,
- o Numerical values are input in a list-directed format,
- o Command instructions and keywords start in the first three columns of the file, and
- o The pound sign ($\#$) is used to designate a comment or text line.

6.2 Summary of Command Instructions

In the present version of the FLASH code, version 3.0, the input file is constructed using up to fifteen (15) unique command instructions. The available commands are listed and briefly explained below:

- o ECHO - specifies the requirement for echo of the input file
- o TITLE - declares a unique run identifier to be input
- o TEXT - declares a sequence of text lines
- o CONTROL - specifies the simulation control parameters
- o FILES - declares the use of external files
- o SOLVE - specifies the solution procedure
- o TIME PLANE - lists the time intervals and output planes
- o INITIAL CONDITION - keys the input of initial conditions
- o FIXEDBC - keys input of Dirichlet boundary conditions
- o FLUXBC - keys input of Neumann boundary conditions
- o GRID - keys input of finite element mesh
- o PROPERTIES - keys input of hydraulic and thermal properties
- o TABLES - keys input of characteristic and hydraulic conductivity curve data
- o THERMAL - keys input of thermal conductivity curve data
- o OUTPUT - defines hard copy output requirements

Of the above command instructions, the ECHO, TEXT, FILES, THERMAL and OUTPUT commands are optional. More detailed descriptions and representative examples of the individual command instructions and keywords are presented in the next subsection.

6.3 Description of Input Stream

As outlined previously, the input file is constructed using a combination of the 15 command instructions. Each unique command is used by the computer code to specify the nature of the input data and keywords that follow. With few exceptions, unspecified data, parameters and/or unused keywords are assigned default values. The keywords described in the following subsections are shown in *italics*.

6.3.1 ECHO Command

The ECHO command is utilized to produce a listing of the complete input data file. This listing is appended to the standard report file, (i.e, hard copy output) generated by the computer code. The echo of the input file can be eliminated by use of the command ECHO SUPPRESS or SUPPRESS ECHO.

6.3.2 TITLE Command

The TITLE command line is usually the first input line in the data file. This line is followed by single line of text which becomes the unique title and run identifier. This title is written to the report file and to all binary output files as a file header. Also written to these output files is a numerical identifier which is a combination of the date and time. Additional lines of text may be placed after the title, however, these lines of text are not used elsewhere.

6.3.3 TEXT Command

The TEXT command keys the input routine that a block of text will follow; the purpose of this text is to document the unique aspects of the input data or simulation. Any number of text lines can be inserted following the TEXT command. It is recommended that this option be used to identify the user, explain the nature of the simulation, identify the particular case or run number, date of the computer run, list key assumptions, etc.

6.3.4 CONTROL Command

Specification of the simulation problem and solution procedure is accomplished using the CONTROL command. Following this command, the user utilizes various keywords to define: (1) processes to be modeled, (2) characteristics of the boundary value problem, (3) computational solution procedures, (4) coordinate system to be used, and (5) output print control. The keywords can be used with other descriptions; the input is case and order independent.

To specify the processes to be modeled, the following alternative keywords can be used:

- o *Heat Transfer* or *Heat Transport*
- o *Fluid Flow, Unsaturated Flow, Richards Flow* Equation
- o *Dupuit or Dupuit-Forchheimer Flow* Equation
- o *Horizontal Flow* Equation

To suppress either process, the above keywords are preceded with: *No, Non, Dont, Don't*.

Definition of the boundary value problem is accomplished with the use of the following keywords:

- o *Uniform Initial Conditions* or *Nonuniform Initial Conditions*
- o *Specified, Flux, or Mixed Boundary Conditions*
- o *Time-dependent, Transient, or Steady-State Mode*

In the latter specification, the keyword *Mode* must appear in the text line. Use of first type boundary conditions are allowed with both the *Specified* and *Mixed* keywords. Similarly, prescribed fluxes are allowed with both the *Flux* and *Mixed* keywords. In addition, the specification of flux boundary conditions also requires specification of the type of flux model, i.e., constant flux, interpolation flux from a table, or use of an empirical formula.

This specification is made by use of the keywords:

- o *Varying Flux Boundaries*
- o *Constant, Interpolation or Empirical Flux Model*

The empirical flux model must be coded in the appropriate routine by the user.

In order to specify the computational solution procedure, the user enters numerical values for: number of finite elements, number of nodes, number of iterations, and initial start time. In addition, the user selects: (1) iteration method, (2) type of shape functions, and (3) matrix solution method. The following keywords can be used:

- o *Picard or Newton Iteration*
- o *Linear or Quadratic Shape Functions*
- o *Band or Frontal Solver*

The above are optional specifications; the code uses the following default specifications: (1) Newton iteration, (2) quadratic shape functions, and (3) band solver.

The code has the capability to solve the governing equations in either Cartesian or radial coordinates. Appropriate specification of the coordinate system is accomplished by use of the keywords: *Cartesian* (x,z) or *Radial* (r,z) Coordinates. If not specified, the code defaults to a Cartesian coordinate system.

Control of printed output is achieved by use of such keywords as: *Echo All*, *Minimum Echo*, *Full Echo*. The latter specification should only be used for data debugging purposes.

6.3.5 FILES Command

Use of the FILE command indicates that next lines of input will define the use of external files. External files are defined for specific input and/or output functions. For example, the code allows the user to read or write restart files, output numerical solutions for post-processing, read the finite element grid (i.e., element-node table and node coordinates), initial conditions, soil-hydraulic property tables, and data for velocity field computations.

The following are examples of the applicable keywords:

- o *Read Restart* Input or *Write Restart* Output
- o *Write Simulation* Results

- o *Read Mesh* Input
- o *Read Initial Conditions* or *Write Initial Conditions*
- o *Read Soil Properties*
- o *Write Velocity Output Data*

Any of the input or output operations can be suppressed by preceding the keyword string with: *No*, *Don't*, or *Don't*. The code defaults to setting of no external inputs or outputs.

6.3.6 SOLVE Command

The SOLVE command is used to indicate the input of six parameters that are used in the solution procedure. These parameters consist of: (1) the time integration factor, α , (2) relative error criteria, $\epsilon_{\max}$, (3) maximum change in pressure head, τ_p , (4) maximum change in temperature, τ_T , (5) grid scale factor in the x-direction, s_x and (6) grid scale factor in the y-direction, s_y . These numerical values are read as list-direct input.

6.3.7 TIME PLANE Command

The TIME PLANE command is used to specify the time domain for a time-dependent simulation heat or fluid flow. This command is followed by two columns of numerical input consisting: (1) number of subintervals and (2) output time plane in days. Each of input defines an interval of time referenced to the initial start time or the previous interval. If the user enters a value of 1 for the number of subintervals, the computer code will calculate the appropriate number from the initial interval. Time-stepping within a given time interval is automatically varied to maintain a constant truncation error.

An example of the TIME PLANE command and input is shown below:

```
TIME PLANE
# No. Steps  Time (days)
    10      0.1
     1      1.0
```

If the steady-state simulations option is selected under the CONTROL command, these data are simply ignored.

6.3.8 INITIAL CONDITIONS Command

Time-dependent simulations require the specification of initial conditions for each computational node. This specification is accomplished using the INITIAL CONDITIONS command. The command is followed by three columns on numerical input consisting of: (1) node number, (2) initial temperature °C, and (3) initial pressure head (cm). This command is typically used to specify uniform initial conditions. An example is shown below:

INITIAL CONDITIONS

#	N	T(C)	H (cm)
	1	T_o	ψ_o

For cases where the initial conditions vary over the entire grid, the use of external file input (see the FILES command) is recommended.

6.3.9 FIXEDBC Command

To define the boundary value problem, the user will usually need to input the Dirichlet boundary conditions, i.e., the known temperature or pressure head values at specific nodes. The FIXEDBC command is used to queue the input of node points with fixed values. The command is followed by from five to eleven columns of numerical values consisting of: (1) node number, n (2) boundary type index, $N1$, for temperature, (3) boundary type index, $N2$, for pressure head, (4) fixed temperature value, T_B ($^{\circ}\text{C}$) and (5) up to seven coefficients to define the transient fixed pressure head (total head for saturated flow) value, ψ_B (cm), where

$$\psi_B = A + Bt + Ct^2 + D \cos(Et) + F \sin(Gt).$$

FIXEDBC

#	n	N1	N2	T ($^{\circ}\text{C}$)	ψ (cm)							
	1	0	1	T_B	A	B	C	D	E	F	G	

A constant fixed pressure head can be obtained by only specifying the A coefficient. The boundary type index is set to 0 for a computational or "free" node or set to 1 for a non-computational or "fixed" node.

6.3.10 FLUXBC Command

In a number of cases, the user will need to input flux or Neumann boundary conditions at specific nodes. The FLUXBC command is used to key the input of node points with prescribed flux values. The command is followed four groups of numerical values consisting of: (1) heat flux (cal/s) and fluid flux (cm/s), (2) list of prescribed flux nodes each having the previously defined flux value, (3) list of unit gradient nodes, and (4) a node number and coefficients for defining a transient volumetric flux. This transient flux is evaluated by

$$Q = A + Bt + Ct^2 + D \cos(Et) + F \sin(Gt).$$

The list of nodes for (2) and (3) are entered in groups of 8. An example is given below:

FLUXBC

```
# qb (cal/s)      qr (cm/s)
      qho          qfo
# Surface Flux Nodes
  1   2   3   0   0   0   0   0
# Unit Gradient Nodes
101 102 103   0   0   0   0   0
# Volumetric Flux Nodes
# Node A   B   C   D   E   F   G
  88 10   1   0  0.1  2.2  0   0
```

The unit gradient conditions can also be established using the "natural" boundary condition of zero pressure head gradient. This boundary condition automatically imposed on boundary nodes that are not designated as Dirichlet boundary condition nodes.

6.3.11 GRID Command

The FLASH code solves the governing equations on a finite element mesh composed of line, triangular, and/or quadrilateral elements. This mesh is defined in terms of an element-node table and list of node coordinates. This information can be entered into the input file using the GRID command. Following this command, the 11 column table consisting of: (1) the element number, (2) the corresponding node numbers listed in counter-clockwise order, (3) the element material number, and (4) element ordering index is entered. The last entry in the table must be entered to complete the input block; however, it is only used if the frontal solver option is selected under the CONTROL command. This index defines the order in which the frontal matrix solver will proceed (Hinton and Owen, 1977). The element-node table is followed by a 3 column input block consisting of: (1) node number, (2) x-coordinate location, and (3) z-coordinate location. A three element mesh which consists of a quadrilateral, triangle, and a line element superimposed between the these two elements is shown in Figure 13.

Figure 13. Sample Finite Element Mesh

The corresponding GRID input is shown below:

GRID

Element-node table for example FE mesh

#	m	N1	N2	N3	N4	N5	N6	N7	N8	km	k
	1	1	2	3	7	11	10	9	6	1	1
	2	3	4	5	8	11	7	0	0	1	2
	3	3	7	11	0	0	0	0	0	1	3

Node point locations

#	N	X (cm)	Z (cm)
	1	0.0	0.0
	2	0.5	0.0
	3	1.0	0.0
	4	1.5	0.0
	5	2.0	0.0
	etc	etc	etc

The above data are loaded into the code using a list-directed read. In practical applications, the mesh is composed of thousands of elements and nodes; thus, it is more convenient to read the above information from an external file using the FILES command.

6.3.12 PROPERTIES Command

The stratigraphic features of the porous medium generally exhibit distinct thermal and/or hydraulic properties. The PROPERTIES command is used to enter these properties for each material type. Following this command, the following data are entered: (1) material number, (2) volumetric heat capacity C_h (cal/cm³-°C), (3) thermal conductivity K_t (cal/cm-s-°C), (4) specific storage S_s (1/cm), (5) saturated hydraulic conductivity K_x (cm/s), (6) saturated hydraulic conductivity K_z (cm/s), (7) saturated moisture content θ_s or porosity, and (8) line-element width b (cm). An example input is shown below:

PROPERTIES

#	km	C_h	K_t	S_s	K_x	K_z	θ_s	b
	1	0.5	0.5	0.0001	1.0E-03	1.0E-03	0.25	1.0

A line of data is entered for each material type and designated by the material number km.

6.3.13 TABLES Command

The TABLES command is used to input the characteristic and relative hydraulic conductivity curve data. These data are typically generated by first fitting van Genuchten (1980), Campbell (1985) or Brooks-Corey (Corey, 1986) formulas to laboratory data. These analytical formulas are then evaluated to produce the tabular data. The tabular data consists of three columns: (1) pressure head ψ , (2) volumetric moisture content θ , and (3) relative hydraulic conductivity K_r .

Typically, the tabular data should be ordered from zero pressure head to the lowest (i.e., most negative) pressure head. However, the input routine will accept pressure head as a positive quantity and will automatically sort the data and add the appropriate sign to the pressure head. It is highly recommended that the data be generated uniformly in the log space and that each variable be calculated from the analytical formulas to at least five significant figures. One table for each material type must be entered following the TABLES command. An example input table is shown below:

```
TABLES
# Material Properties for soil type 1
#      Shi (cm)      Theta      Kr
      0.00000E+00      0.25000      1.00000E+00
      -1.00000E-01      0.24999      9.99999E-01
      -2.00000E-01      0.24990      9.99950E-01
      -3.00000E-01      0.24910      9.99100E-01
      etc             etc             etc
```

The keyword *Material* must appear in the comment card before the tabular data.

Alternate keywords such as *Soil-Hydraulic*, *Soil Hydraulic*, *Soil-Properties*, *Soil Properties*, and *Characteristic*. It is recommended that 30 or more points be used in defining the characteristic and relative conductivity curves. For practical applications with several tables, it is more convenient to load these data using an external file (see FILES command).

6.3.14 THERMAL Command

In certain special applications, it is important to account for the dependent of the thermal conductivity on moisture content level or pressure head. The THERMAL command is an optional command that allows the user to enter tabular data defining the appropriate functional relationship. Following this command, two columns of data are entered: (1) pressure head and (2) relative thermal conductivity. The input structure is similar to that described previously under the TABLES command.

6.3.15 OUTPUT Command

The OUTPUT command, which is optional, can be used by the user to suppress selected portions of the report file. For example, the usually lengthy element-node table and node point coordinates can be suppressed by following this command with the keyword *Grid*. Similarly, the lengthy list of initial conditions can be suppressed using the keyword *Initial*.

ACKNOWLEDGMENTS

The authors wish to thank a number of individuals that contributed to this project. First and foremost, the authors thank Ms. M. Beth Sussman, Technology Programs, for her patience during the conduct of this study. The authors acknowledge the contributions of Ms. Annette Schafer-Perini for modifying the FLASH code to solve the Dupuit-Forchheimer equation. The authors also thank Mr. Tony R. Moser of EG&G for his assistance with preparation of graphs and illustrations.

REFERENCES

- Arfken, G., *Mathematical Methods for Physicist*, Academic Press, New York, NY (1970).
- Arnett, R. C., R. C. Martineau, and M. J. Lehto, "Preliminary Numerical Model of Radionuclide Transport in the Snake River Plain Aquifer Near the Idaho National Engineering Laboratory," *EGG-WM-8820*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Baca, R. G., I. P. King, and W. R. Norton, "Finite Element Models for Simultaneous Head and Moisture Transport in Unsaturated Soils," Proceedings of the Second International Conference on *Finite Elements in Water Resources*, Imperial College, Pentech Press, London, UK (1978).
- Baca, R. G. and D. W. Langford, "MAGNUM-2D - A Numerical Model for Coupled Heat Transfer and Groundwater Flow in Fractured-Porous Media: Model Theory, Numerical Methods, and Computational Tests," (Draft), Rockwell Hanford Operations, Richland, WA (1986).
- Baca, R. G., and D. W. Langford, "CHAI NT - A Numerical Model for Radionuclide Transport with Decay Chains in Fractured-Porous Media: Model Theory, Numerical Methods, and Computational Tests," (Draft), Rockwell Hanford Operations, Richland, WA (1986).
- Baca, R. G., R. C. Arnett, and D. W. Langford, "Modelling Fluid Flow in Fractured-Porous Masses by Finite Element Techniques," *International Journal for Numerical Methods in Fluids*, Vol. 4, pp. 337-348 (1984).
- Baca, R. G., "Configuration Management and Software Control Procedure for Subsurface Flow and Transport Simulation Codes," *EGG-WM-9103*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Baca, R. G., and S. O. Magnuson, "Independent Verification and Benchmark Testing of the UNSAT-H Computer Code, Version 2.0," *EGG-BEG-8811*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Baca, R. G., S. O. Magnuson, H. D. Nguyen, and P. Martian, "A Modeling Study of Water Flow in the Vadose Zone Beneath the Radioactive Waste Management Complex," *EGG-GEO-10068*, EG&G Idaho, Inc., Idaho Falls, ID (1992).
- Bachmat, Y., J. Bredehoeft, B. Andrews, D. Holt, and S. Sebastian, *Ground-Water Management: The Use of Numerical Models*, Water Resources Monograph 5, American Geophysical Union, Washington, DC (1980).

- Bishop, C. W., "Hydraulic Properties of Vesicular Basalt," MS Thesis, University of Arizona, Tucson, AZ (1991).
- Borghese, J. V., "Hydraulic Characteristics of Soil Cover, Subsurface Disposal Area, Idaho National Engineering Laboratory," MS Thesis, Univ. of Idaho, Moscow, ID (1988).
- Burnett, D. S., *Finite Element Analysis*, Addison-Wesley Publishing Company, Reading, MA (1987).
- Case, M. J., S. J. Maheras, M. A. McKenzie-Carter, M. E. Sussman, and P. Voilleque, "Radioactive Waste Management Complex Performance Assessment," *EGG-WM-8773*, EG&G Idaho, Inc., Idaho Falls, ID (1989).
- Celia, M. A., E. T. Bouloutas, and R. L. Zarba, "A General Mass-Conservative Numerical Solution for the Unsaturated Flow Equation," *Water Resources Research*, Vol. 26, No. 7, pp. 1483-1496 (1990).
- Celia, M. A. "The One-Dimensional Princeton Unsaturated Code," Department of Civil Engineering, Water Resources Program, Princeton, NJ (1991).
- Cuthill, E., "Several Strategies for Reducing the Bandwidth of Matrices," in *Sparse Matrices and their Applications*, eds. D. J. Rose and R. A. Willoughby, Plenum Press, New York, NY (1972).
- Davis, L. C. and J. R. Pittman, "Hydrological, Meteorological, and Geohydrological Data for an Unsaturated Zone Study Near the Radioactive Waste Management Complex, Idaho National Engineering Laboratory, Idaho--1987," *Report 90-114*, U.S. Geological Survey, Idaho Falls, ID (1990).
- EG&G "Methodology for Compliance with DOE Order 5820.2A, Chapter III: Management of Low-Level Waste," *DOE/LLW-75T*, prepared by the National Low-Level Waste Management Program, EG&G Idaho, Inc., Idaho Falls, ID (1988).
- England, R. L., N. W. Kline, K. J. Ekblad, and R. G. Baca, "MAGNUM-2D Computer Code: User's Guide," *RHO-CR-143 P*, Rockwell Hanford Operations, Richland, WA (1986).
- Gerald, C. F. and P. O. Wheatley, *Applied Numerical Analysis*, Addison-Wesley Publishing Co., Reading, MA (1984).
- Gibbs, N. E., W. G. Poole, Jr., and P. K. Stockmeyer, "A Comparison of Several Bandwidth and Profile Reduction Algorithms," *Association for Computing Machinery Transactions of Mathematical Software*, Vol. 2, pp. 322-330 (1976).
- Hinton, E. and D. R. J. Owen, *Finite Element Programming*, Academic Press, New York, NY (1977).

- Hood, P., "Frontal Solution Program for Unsymmetric Matrices," *International Journal for Numerical Methods in Engineering*, Vol. 10., pp. 329-400 (1976).
- Humphrey, T. G., T. H. Smith, and M. C. Pope, "Projected Subsurface Migration of Radionuclides from Buried Idaho National Engineering Laboratory Transuranic Waste," *Nuclear Technology*, Vol. 58, pp. 136-149 (1982).
- Huyakorn, P. S. and G. F. Pinder, *Computational Methods in Subsurface Flow*, Academic Press, New York, NY (1983).
- Kaminsky, J. F., "Insitu Characterization of Unsaturated Hydraulic Properties of Surficial Sediments adjacent to the Radioactive Waste Management Complex, Idaho National Engineering Laboratory, Idaho," MS Thesis, Idaho State Univ., Pocatello, ID (1991).
- King, I. P., "An Automatic Reordering Scheme for Simultaneous Equations derived from Network Analysis," *International Journal for Numerical Methods in Engineering*, Vol. 2, pp. 525-533 (1970).
- Kline, N. W., R. L. England, and R. G. Baca, "CHAI NT Computer Code: User's Guide," *RHO-CR-144 P*, Rockwell Hanford Operations, Richland, WA (1986).
- Knutson, C. F., K. A. McCormick, R. P. Smith, W. R. Hackett, J. P. O'Brien, and J. C. Crocker, "FY 89 Report - RWMC Vadose Zone Basalt Characterization," *EGG-WM-8949*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Long, J. C. S., J. S. Remer, C. R. Wilson, and P. A. Witherspoon, "Porous Media Equivalents for Networks of Discontinuous Fractures," *Water Resources Research*, Vol. 18, No. 2, pp. 645-658 (1982).
- Magnuson, S. O., R. G. Baca, and A. J. Sondrup, "Independent Verification and Benchmark Testing of the PORFLO-3 Computer Code, Version 1.0," *EGG-BG-9175*, EG&G Idaho, Inc. Idaho Falls, ID (1990).
- McElroy, D. L., "Vadose Zone Monitoring at the Radioactive Waste Management Complex at the Idaho National Engineering Laboratory, 1985-1989," *EGG-WM-9229*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- McElroy, D. L. and J. M. Hubbell, "Hydrologic and Physical Properties of Sediments at the Radioactive Waste Management Complex," *EGG-WM-9147*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Mizell, S. A. and L. C. Hull, "Preliminary Modeling of Radionuclide Migration through the Subsurface at the INEL Radioactive Waste Management Complex using the Unsaturated Flow and Transport Model UNSAT," *RE-PB-83-038*, EG&G Idaho, Inc., Idaho Falls, ID (1983).

- Oster, C. A., "Review of Ground-Water Flow and Transport Models in the Unsaturated Zone," NUREG/CR-2917, PNL-4427, Battelle-Pacific Northwest Laboratory, Richland, WA (1982).
- Pittman, J. R. "Hydrological and Meteorologic Data for an Unsaturated Zone Study near the Radioactive Waste Management Complex, Idaho National Engineering Laboratory, Idaho-1985-86," *Report 89-74*, U.S. Geological Survey, Idaho Falls, ID (1989).
- Pope, M. C. and H. W. Reno, "Modeling Radionuclide Transport in the Unsaturated Zone Beneath the Radioactive Waste Management Complex," (*Draft Report*), EG&G Idaho, Inc., Idaho Falls, ID (1982).
- RAE (Rogers and Associates Engineering), "DOE Site Performance Assessment Activities," DOE/LLW-99, prepared for EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Rasmussen, T. C., D. D. Evans, and T. J. Nicholson, "Unsaturated Flow and Transport Through Fractured Rock Related to High-Level Waste Repositories, Final Report, Phase II," NUREG/CR-45, prepared by the Department of Hydrology and Water Resources, University of Arizona, Tucson, AZ (1987).
- Rightmire, C. T. and B. D. Lewis, "Hydrology and Geochemistry of the Unsaturated Zone, Radioactive Waste Management Complex, Idaho National Engineering Laboratory, Idaho," *Report 87-4198*, U. S. Geological Survey, Idaho Falls, ID (1987).
- Robertson, J. B. "Digital Modeling of Radioactive and Chemical Waste Transport in the Snake River Plain Aquifer at the National Reactor Testing Station, Idaho," U.S.G.S. Open File Report *IDO-22054*, Idaho Falls, ID (1974).
- Snow, D. T., "Anisotropic Permeability of Fractured Media," *Water Resources Research*, Vol. 5, pp. 1273-1288 (1969).
- Strang, G. and G. Fix, *An Analysis of the Finite Element Method*, Prentice-Hall, Englewood Cliffs, NJ (1973).
- Tewarson, R. P., *Sparse Matrices*, Academic Press, New York, NY (1973).
- van Genuchten, M. T., "A Closed-Form Equation for Predicting the Hydraulic Conductivity of Unsaturated Soils," *Soil Science Society of America Journal*, Vol. 44, pp. 892-898 (1980).
- Vigil, M. J., "Estimate of Water Pits During Flooding Events", *EDF-BWP-12*, EG&G Idaho, Inc., Idaho Falls, ID (1988).

APPENDIX I - SAMPLE INPUT FILES FOR TEST PROBLEMS

This appendix presents condensed versions of the input files prepared for two of the computational examples described in section 5.0. The two examples consist of: (1) partially saturated flow in a dry soil and (2) heat transport from a buried heat source. Certain portions of the input files have been omitted because of their length. These portions, which include the grid definition and soil property tables, can be easily reconstructed by the user from information given in section 5.0.

A-1 Summary of Input File for Computational Example 1

ECHO

TITLE

Example 1 - Partially Saturated Flow in a Dry Soil

TEXT

This one-dimensional partially saturated flow problem was originally solved by Celia, et al., (1990). The problem considers transient flow in a homogeneous, vertical soil column. The top boundary is held at a fixed pressure head near saturation. The bottom boundary is held at the initial pressure head which is set a large negative pressure head, characteristic of an arid or desert site. The initial and boundary conditions produce a steep moisture front moving through the soil.

CONTROL

```
#  NE  NP  ITERLM  SSF
50 101   7      0.
```

Time-dependent mode

Band Solver

Picard Iteration

Linear Shape Functions

Fluid flow simulation

Thermal properties are constant

Cartesian coordinates

Uniform initial conditions

Fixed boundary conditions

Echo all data

Don't print velocity output

FILES

Don't Read Restart file
 Don't Write Simulation Results
 Don't Write Restart Data
 Don't Read Input Mesh File
 No Initial Conditions File
 Don't Write Initial Conditions
 No Soil Properties File
 Don't Write Velocity Output File

SOLVE

#	Alfa	Epsmax	Tauh	Taut	Scalex	Scaley
1	1.6	.01	0.10	10.0	1.	1.

TIME PLANE

#	Nts	Time
300	0.173511	
1	0.69444	
1	1.56250	

INITIAL CONDITIONS

#	N	T1	T2
1	10.0	-1000.	

FIXEDBC

#	N	N1	N2	BCS(1)	BCS(2)
1	1	1	1	10.0	-75.0
81	1	1	1	10.0	-1000.

GRID

ELEMENT-NODE TABLE

#	N	NOP								IMAT	NFIXH
1	1	2	3	0	0	0	0	0	0	1	1
2	3	4	5	0	0	0	0	0	0	1	2
3	5	6	7	0	0	0	0	0	0	1	3
4	7	8	9	0	0	0	0	0	0	1	4
5	9	10	11	0	0	0	0	0	0	1	5

(Lines Omitted)

48	95	96	97	0	0	0	0	0	1	48
49	97	98	99	0	0	0	0	0	1	49
50	99	100	101	0	0	0	0	0	1	50
1		0.000		0.000		0.00		0.00		
2		0.000		-1.000		0.00		0.00		
3		0.000		-2.000		0.00		0.00		
4		0.000		-3.000		0.00		0.00		
5		0.000		-4.000		0.00		0.00		
6		0.000		-5.000		0.00		0.00		
7		0.000		-6.000		0.00		0.00		

95	0.000	-94.000	0.00	0.00
96	0.000	-95.000	0.00	0.00
97	0.000	-96.000	0.00	0.00
98	0.000	-97.000	0.00	0.00
99	0.000	-98.000	0.00	0.00
100	0.000	-99.000	0.00	0.00
101	0.000	-100.000	0.00	0.00

PROPERTIES

#	L	Ch	Thrlk	Specs	Satkx	Satky	Poros	Width
#	=	==	=====	=====	=====	=====	=====	=====
1	0.5		2.6E-03	0.1000	9.22E-03	9.22E-03	0.368	1.

TABLES

101 Hydraulic & Characteristic Curves for Yolo light Clay

#	Shi	Theta	Relk
-0.150E+04	0.1073	0.5527E-08	
-0.145E+04	0.1075	0.6441E-08	
-0.140E+04	0.1077	0.7506E-08	
-0.135E+04	0.1079	0.8747E-08	
-0.131E+04	0.1081	0.1019E-07	
-0.127E+04	0.1083	0.1188E-07	
-0.122E+04	0.1085	0.1384E-07	
-0.118E+04	0.1087	0.1613E-07	
-0.114E+04	0.1089	0.1880E-07	
-0.110E+04	0.1092	0.2190E-07	
-0.107E+04	0.1094	0.2552E-07	
-0.103E+04	0.1097	0.2974E-07	
-0.997E+03	0.1100	0.3466E-07	
-0.964E+03	0.1102	0.4038E-07	
-0.932E+03	0.1105	0.4706E-07	
-0.901E+03	0.1108	0.5483E-07	
-0.870E+03	0.1111	0.6389E-07	

(Lines Omitted)

-0.535E+02	0.2316	0.1120E-01
-0.517E+02	0.2349	0.1267E-01
-0.500E+02	0.2384	0.1431E-01

OUTPUT

Echo all Input Data

A-2 Summary of Input File for Computational Example 3

ECHO

Don't SUPPRESS EXECUTION

TITLE

Example 3 - Heat Conduction from a Buried Heat Source

TEXT

This two-dimensional heat transport problem considers steady-state heat conduction from a cylindrical source. The cylinder is buried at a depth H from the surface. The temperature on the cylinder surface and soil surface are fixed. This boundary value problem has an exact solution which was used to verify the computational accuracy of the numerical solution.

CONTROL

#	NE	NP	ITERLM	SSF
90	313	0	0.	

Steady-State mode

Heat Transfer

No Fluid flow simulation

Constant Thermal Properties

Cartesian Coordinates

Uniform Conditions

Specified Boundary Conditions

Echo All Data

Don't Print Velocity Output

FILES

Don't Read Restart file

Write Simulation Results

Don't Write Restart Data

Don't Read Input Mesh File

No Initial Conditions File

Don't Write Initial Conditions

No Soil Properties File

Don't Write Velocity Output File

TIME PLANE

#	Nts	Time
	1	1.0

FIXEDBC

#	N	N1	N2	BCS(1)	BCS(2)
1	1	0	1.0000	0.0	
2	1	0	1.0018	0.0	
3	1	0	1.0022	0.0	
4	1	0	1.0012	0.0	
5	1	0	1.0005	0.0	

308	1	0	0.1208	0.0
309	1	0	0.1236	0.0
310	1	0	0.1256	0.0
311	1	0	0.1269	0.0
312	1	0	0.1276	0.0
313	1	0	0.1278	0.0

GRID

ELEMENT-NODE TABLE

#	N	NOP								IMAT	NFIXH
1	1	2	3	13	20	19	18	12	1	1	
2	3	4	5	14	22	21	20	13	1	2	
3	5	6	7	15	24	23	22	14	1	3	
4	7	8	9	16	26	25	24	15	1	4	
5	9	10	11	17	28	27	26	16	1	5	
6	18	19	20	30	37	36	35	29	1	6	
7	20	21	22	31	39	38	37	30	1	7	
8	22	23	24	32	41	40	39	31	1	8	
9	24	25	26	33	43	42	41	32	1	9	

(Lines Omitted)

85	285	286	287	292	299	298	297	291	1	85
86	287	288	289	293	301	300	299	292	1	86
87	215	294	295	302	307	306	233	221	1	87
88	295	296	297	303	309	308	307	302	1	88
89	297	298	299	304	311	310	309	303	1	89
90	299	300	301	305	313	312	311	304	1	90

1	0.000	-3.800	0.00	0.00
2	0.131	-3.812	0.00	0.00
3	0.254	-3.837	0.00	0.00
4	0.369	-3.873	0.00	0.00
5	0.475	-3.921	0.00	0.00
6	0.574	-3.981	0.00	0.00
7	0.663	-4.053	0.00	0.00
8	0.745	-4.136	0.00	0.00
9	0.818	-4.232	0.00	0.00
10	0.883	-4.339	0.00	0.00

(Lines Omitted)

305	0.000	-29.893	0.00	0.00
306	11.865	-32.860	0.00	0.00
307	9.780	-32.860	0.00	0.00
308	7.825	-32.860	0.00	0.00
309	6.000	-32.860	0.00	0.00
310	4.305	-32.860	0.00	0.00
311	2.740	-32.860	0.00	0.00
312	1.305	-32.860	0.00	0.00
313	0.000	-32.860	0.00	0.00

PROPERTIES

#	L	Ch	Thrlk	Specs	Satkx	Satky	Poros	Width
#	=	==	=====	=====	=====	=====	=====	=====
1	0.5		0.5	0.0001	1.230E-05	1.230E-05	0.495	1.

TABLES

51 Hydraulic & Characteristic Curves for Yolo light Clay

#	Shi	Theta	Relk
	0.000E+00	0.4950	0.1000E+01
	-0.114E+01	0.4950	0.9900E+00
	-0.130E+01	0.4950	0.9874E+00
	-0.148E+01	0.4950	0.9842E+00
	-0.169E+01	0.4950	0.9801E+00
	-0.193E+01	0.4949	0.9750E+00
	-0.219E+01	0.4948	0.9687E+00
	-0.250E+01	0.4946	0.9609E+00
	-0.285E+01	0.4944	0.9512E+00
	-0.325E+01	0.4940	0.9392E+00
	-0.371E+01	0.4935	0.9246E+00
	-0.423E+01	0.4928	0.9067E+00

(Lines Omitted)

-0.414E+03	0.2572	0.2893E-02
-0.472E+03	0.2499	0.2295E-02
-0.539E+03	0.2430	0.1821E-02
-0.614E+03	0.2365	0.1445E-02
-0.700E+03	0.2302	0.1146E-02

OUTPUT

Echo all Input Data

DISTRIBUTION LIST

OFFSITE

D. J. Alexander
U. S. Department of Energy
Forrestal Bldg., MS RW-23-2
Washington, DC 20585

W. Barrish
INEL Oversight Program
1410 N. Hilton
Boise, ID 83706

J. S. Baldwin
Martin Marietta
Central Waste Management
Oak Ridge, TN 37831

A. J. Baker
Engineering Science and Mechanics
University of Tennessee
Knoxville, TN 37996-2030

A. K. Bhattacharyya
Department of Environmental Resources
Bureau of Radiation Protection
P. O. Box 2063
Harrisburg, PA 17120

K. H. Birdsell
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

T. N. Blandford
HydroGeoLogic, Inc.
1165 Herndon Pkwy, Suite 900
Herndon VA, 22070

G. Bloomsburg
Agricultural Engineering Department
University of Idaho
Moscow, ID 83843

A. Bumb
Fluor Daniel, Inc.
100 Fluor Daniel Drive
Greenville, SC 29607

T. C. Chee
U. S. Department of Energy
Research and Management Division
DP-123, A237
Germantown, MD 20545

D. L. Chery, Jr.
U. S. Nuclear Regulatory Commission
MS-4H3
Washington, DC 20555

J. N. Chung
Mechanical and Material Engineering
Washington State University
Pullman, WA 99164-2920

R. B. Codell
U. S. Nuclear Regulatory Commission
MS-4H3
Washington, DC 20555

J. R. Cook
Westinghouse Savannah River Company
Savannah River Laboratory
P. O. Box 616, Bldg. 773-43A
Aiken, SC 29802

J. C. Corey
Westinghouse Savannah River Site
P. O. Box A
Aiken, SC 29808

M. Cunnane
Golder Associates, Inc.
4104 148th Avenue NE
Redmond, WA 98052

J. Davis
Westinghouse Hanford
450 Hills St.
Richland, WA 99352

P. A. Davis
Sandia National Laboratories
Division 6416
P. O. Box 5800
Albuquerque, NM 87185

P. Dickman
U. S. Department of Energy
Waste Management Project Office
P. O. Box 14100
Las Vegas, NV 89114

M. R. Dolenc
Reynolds Electrical and Engineering Co.
P. O. Box 98521
Las Vegas, NV 89193-8521

F. H. Dove
IT Corporation
5301 Central Ave, N.E., Suite 700
Albuquerque, NM 87108

R. R. Eaton
Sandia National Laboratories
Fluid Mechanics and Heat Transfer Div.
Albuquerque, NM 87185

M. Ebra
Westinghouse Savannah River Company
Environmental Restoration Program
P. O. Box 616
Aiken, SC 29802

L. Ebeling
Reynolds Electrical and Engineering Co.
P. O. Box 98521
Las Vegas, NV 89193-8521

A. I. El-Kadi
Univ. of Hawaii at Manoa
Dept. of Geology and Geophysics
2525 Correa Road
Honolulu, HI 96822

C. G. Enfield
U. S. Environmental Protection Agency
Robert S. Kerr Environmental Lab
P. O. Box 1198
Ada, OK 74820

M. J. Fayer
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

J. I. Finnie
Civil Engineering Department
University of Idaho
Moscow, ID 83843

R. A. Freeze
Department of Geological Sciences
University of British Columbia
Vancouver, BC V6T 2B4, Canada

G. W. Gee
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

T. C. Gunderson
Los Alamos National Laboratory
P. O. Box 1663, MS K491
Los Alamos, NM 87545

D. Hillel
Dept. of Plant and Soil Science
University of Massachusetts
12A Stockbridge Hall
Amherst, MA 01003

C. Y. Hung
U. S. Environmental Protection Agency
Office of Radiation Programs, ANR-460
401 M Street, S. W.
Washington, DC 20460

P. S. Huyakorn
HydroGeoLogic, Inc.
1165 Herndon Pkwy, Suite 900
Herndon, VA 22070

V. Ichimura
Chem-Nuclear Systems
P. O. Box 726
Barnwell, SC 29182

B. Izadi
Agricultural Engineering Dept.
Univ. of Idaho
Moscow, ID 83843

T. L. Jones
Department of Agronomy
and Horticulture
New Mexico State University
Las Cruces, NM 88003-0003

W. A. Jury
Department of Soils
University of California
at Riverside
Riverside, CA 90024

P. Kearl
Oak Ridge National Laboratory
Grand Junction Office
Grand Junction, CO 81502

K. Kersch
SAIC, Inc.
101 Convention Ctr. Drive,
Suite 407
Las Vegas, NV 89109

C. T. Kincaid
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

R. G. Knowlton
Sandia National Laboratories
P.O. Box 5800, Div 6416
Albuquerque, NM 87185

C. P. Liou
Civil Engineering Department
University of Idaho
Moscow, ID 83843

J. T. McCord
Sandia National Laboratories
Division 6416
Albuquerque, NM 85185-5800

L. M. McDowell-Boyer
Oak Ridge National Laboratory
Grand Junction Office
Grand Junction, CO 81502

C. McLane
ENVIRON International Corp.
4350 N. Fairfax Dr., Suite 300
Arlington, VA 22203

D. B. McLaughlin
Department of Civil Engineering
Massachusetts Institute of Technology
Room 48-329
Cambridge, MA 02139

S. A. Mizell
Desert Research Institute
P. O. Box 60220
Reno, NV 89506

D. J. Mulla
Soils Department
Washington State University
Pullman, WA 99164

S. P. Neuman
Dept. of Hydrology and Water Resources
University of Arizona
Tucson, AZ 85721

W. Newberry
U. S. Department of Energy
Nuclear Energy LLW Management
Program, NE-24
Washington, DC 20545

T. J. Nicholson
U. S. Nuclear Regulatory Commission
Division of Engineering Safety
MS NL-005
Washington, DC 20555

J. W. Nyhan
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

U. S. Park
Science Applications International Corp.
101 Convention Center Drive
Las Vegas, NV 89109

F. L. Parker
4400 Iroquois
Nashville, TN 37205

D. M. Peterson
INTEKA Associates, Inc.
8100 Mountain Road NE, Suite 213
Albuquerque, NM

O. A. Plumb
Mechanical and Material Engineering
Washington State University
Pullman, WA 99164-2920

J. Pope
Westinghouse Savannah River Company
Environmental Restoration Program
P. O. Box 616
Aiken, SC 29802

R. W. Prindle
Sandia National Laboratories
Division 6312
P. O. Box 5800
Albuquerque, NM 87185

T. C. Rasmussen
Dept. of Hydrology and Water Resources
University of Arizona
Tucson, AZ 85721

M. Reeves
INTERA Associates, Inc.
6850 Austin Cntr. Blvd.,
Suite 300
Austin, TX 78731

M. L. Rockhold
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

V. C. Rogers
Rogers & Associates Engineering Corp.
P. O. Box 330
Salt Lake City, UT 84110

A. K. Runchal
ACR, Inc.
3106 Inglewood Blvd.
Los Angeles, CA 90066

B. Sagar
Center for Nuclear Waste Repository
Analyses
Southwest Research Institute
6220 Culebra Rd.
P. O. Drawer 28510
San Antonio, TX 78284

S. G. Schmelling
U. S. Environmental Protection Agency
Robert S. Kerr Environmental Lab
P. O. Box 1198
Ada, OK 74820

M. Silberberg
U. S. Nuclear Regulatory Commission
Office Nuclear Regulatory Research
Washington, DC 20555

J. L. Smoot
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

C. J. Suen
Brookhaven National Laboratory
Nuclear Waste and Materials
Technology Division
Upton, Long Island, NY 11973

R. J. Starmer
ERM-Program Management Corp
7926 Jones Branch Drive, Suite 210
McLean, VA 22102

Technical Library
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

Technical Library
Oak Ridge National Laboratory
P. O. Box X
Oak Ridge, TN 37830

Technical Library
Savannah River Laboratory
P. O. Box 616
Aiken, SC 29802

B. Troutman
Dames and Moore, Inc.
1970 E. 17th St, Suite 111
Idaho Falls, ID 83401

B. J. Travis
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

S. W. Tyler
Water Resources Center
Desert Research Institute
P. O. Box 60220
Reno, NV 89506-0220

B. L. Roberts
EG&G Rocky Flats, Inc.
P. O. Box 464
Golden, CO 80402-0464

M. T. van Genuchten
USDA-ARS, U.S. Salinity Laboratory
4500 Glenwood Drive
Riverside, CA 92501

P. van der Heijde
International Groundwater Modeling Center
Colorado School of Mines
Golden, CO 80401-1887

J. Wang
Lawrence Berkely Laboratory
Earth Sciences Division
1 Cyclotron Road,
Berkely, CA 94720

A. W. Warrick
University of Arizona
Dept. of Soil and Water Science
Tucson, AZ 85721

E. P. Weeks
U. S. Geological Survey
Federal Center, MS 413
Denver, CO 80225

M. Weinstein
U. S. Nuclear Regulatory Commission
MS NL/S-260
Washington, DC 20555

P. J. Wierenga
University of Arizona
Dept. of Soil and Water Science
Tucson, AZ 85721

D. C. Wiggert
Michigan State University
A120 Engineering Research Complex
East Lansing, Michigan 48824

J. L. Wilson
New Mexico Institute of Mining
and Technology
Dept. of Geosciences
Socorro, NM 87801

Westinghouse Hanford Company
P. O. Box 1970
Richland, WA 99352

J. D. Davis, MS H4-54
R. Khaleel, MS H4-54
J. C. Sonnichsen, MS H4-54

A. Yu
Westinghouse Savannah River Company
Savannah River Laboratory
P. O. Box 616
Aiken, SC 29802

ONSITE

DOE-ID

M. C. Bennett
L. A. Green

EG&G Idaho, Inc.

R. C. Arnett
R. G. Baca
L. C. Hull
J. M. Hubbell
C. B. Lee
J. A. Logan
S. O. Magnuson
S. J. Maheras
J. N. McCarthy
J. W. McConnell

R. L. Nitschke
H. D. Nguyen
R. R. Seitz
J. B. Sisson
C. S. Smith
A. J. Sondrup
L. V. Street

INEL Technical Library
Westinghouse Idaho Nuclear Co., Inc.

T. R. Thomas

U.S. Geological Survey

J. R. Pittman
L. J. Mann

END

**DATE
FILMED**

8 / 27 / 92