2F

BNWL-2043

UC-70

Heat Transfer Analysis of an Underground Storage Tank Containing Solidified Heat Generating Wastes

by
S. C. Slate and P. J. Pelto

August 1976

**Prepared for the Energy Research
and Development Administration
under Contract E(45-1):1830**

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE
for the
ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION
Under Contract E(45-1)-1830

Printed in the United States of America
Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22151
Price: Printed Copy \$5.50; Microfiche \$2.25

3 3679 00062 4991

BNWL-2043
UC-70

HEAT TRANSFER ANALYSIS OF AN
UNDERGROUND STORAGE TANK
CONTAINING SOLIDIFIED HEAT
GENERATING WASTES

by
S. C. Slate and P. J. Pelto

August 1976

BATTELLE
Pacific Northwest Laboratories
Richland, Washington 99352

CONTENTS

LIST OF FIGURES	iv
LIST OF TABLES	iv
INTRODUCTION	1
SUMMARY.	3
SYSTEM DESCRIPTION	5
THE COMPUTER MODELS	8
THE ONE-DIMENSIONAL MODEL.	8
THE TWO-DIMENSIONAL MODEL.	11
THE THREE-DIMENSIONAL MODEL	15
COMPARISON OF THE MODELS	22
RECOMMENDATIONS	25
APPENDIX A - DERIVATION OF EQUATIONS FOR THE ONE- DIMENSIONAL MODEL	A-1
APPENDIX B - ATANK THE COMPUTER PROGRAM FOR THE ONE- DIMENSIONAL MODEL	B-1
APPENDIX C - AN EXAMPLE OF THE HEATING4 OUTPUT FOR THE TWO-DIMENSIONAL MODEL	C-1
APPENDIX D - VAPOR SPACE MODEL	D-1
REFERENCES.	Ref-1

LIST OF FIGURES

1	Section Diagram of a Typical Underground Storage Tank	7
2	Schematic Diagram of the One-Dimensional Model	9
3	Schematic Diagram of the Two-Dimensional Model Showing Dimensions and Region Numbers.	13
4	Temperature Distribution in the Two-Dimensional Model Using an Annular Sludge Pile	16
5	Sludge Piles Found in Tank 101-A.	17
6	Approximation of Sludge Piles for Use in the Three-Dimensional, 360° Model	18
7	Temperatures from the Three-Dimensional, 360° Model	20
8	Temperatures from the Three-Dimensional, 180° Model	21
9	Plots of Wall Temperature Versus Specific Heat Generation for Various Geometries	23
10	Linear Regression Equations of Data in Figure 9.	23
D-1	Schematic Diagrams of Two Vapor Space Models.	D-3
D-2	Temperature Distribution in the Soil Next to the Vapor Space for the Two Dimensional Model Using an Annual Sludge Pile.	D-3

LIST OF TABLES

1	Summary of the One-Dimensional Test Cases	10
2	Critical System Temperatures Using Different Numbers of Nodes	14
3	Summary of the Two-Dimensional Test Cases	14
4	Summary of the Three-Dimensional Test Cases	19

HEAT TRANSFER ANALYSIS OF AN UNDERGROUND STORAGE TANK CONTAINING SOLIDIFIED HEAT GENERATING WASTES

S. C. Slate and P. J. Pelto

INTRODUCTION

Elevated temperatures are one of the major problems in storing radioactive wastes underground. Battelle-Northwest has conducted a heat transfer analysis study of the underground tank system at Hanford in support of Atlantic Richfield Hanford Company's ERDA high-level waste solidification program.

Previous studies have considered various aspects of this problem including the transient thermal histories involved in startup of tanks containing boiling solutions.⁽¹⁾ Combined thermal and load stresses have been evaluated to determine the amount of solution that can safely be held by a tank⁽²⁾ and a heat transfer analogue, consisting of electrically conductive paper, has been developed.⁽³⁾ Also, temperatures have been calculated in tanks that have lost their liquid cover and heat transfer has been analyzed in leaks from buried tanks.⁽⁴⁾ Jansen has conducted the most recent study in 1966 which provided methods for predicting temperature distributions in a tank containing only solidified waste.⁽⁵⁾ He also developed useful correlations between certain system parameters.

The present work developed heat transfer models of an underground storage tank containing solidified wastes (salt cake) and a residual sludge with a higher heat generation rate. These models calculate the temperature distribution in the tank assuming steady-state conditions and idealized materials having thermal properties independent of position or temperature. Thus, the results must be regarded only as a reference system to compare analyses of real cases. It should not be regarded as a definitive description of the true thermal characteristics of an operational tank system.

This report presents the models developed for the Hanford waste tanks. It discusses the computer programs and how they were used as well as the assumptions and results for each model which are discussed individually. The results presented in this report are from cases run in testing the models and from the modeling of one particular tank. The only parametric variation studies were those made with the one-dimensional model.

SUMMARY

Three steady-state models for heat transfer in an underground storage tank are presented in this report. The first is a simplified 1-D model of a general symmetrical tank developed for preliminary calculations and parameteric studies. The second and third models use the finite difference computer program, HEATING4, and are based on 2- and 3-D geometries, respectively. The 2-D model describes a radially symmetrical tank and is used for relatively detailed calculations and testing the assumptions made in the 1-D model while the 3-D, 360° model describes the actual sludge configuration in Waste Tank 101-A.

The heat transfer calculations are made for a 76-ft diameter tank in a tank system with 120-ft center-to-center spacing. For this system heat is lost to the atmosphere and to a water table at a depth of 252 ft; about 51% of the heat goes straight up from the tank, 36% out the side, and 13% down to the water table. Since most of the thermal resistance for this system is in the soil and the salt cake, the shape of the roof is important because the resistance to heat transfer increases as the soil depth above the tank increases. The other factors in modeling the vapor space such as thermal resistance and air flow, are relatively unimportant. The metal liner in the tank and the convective heat transfer coefficient also have very little effect on the system temperatures.

The 1-D model estimates heat flows and calculates temperatures along the axis of the tank which is assumed to have a uniform sludge layer. The model includes all the system variables and can be used to determine: 1) the maximum temperature at the bottom of the tank given a sludge thickness; 2) the maximum uniform sludge thickness given a bottom centerline temperature criteria; and 3) the salt cake thickness given a sludge thickness and a temperature criteria. This model, which uses the interactive computer program ATANK, can be used to generate preliminary information and to study the effects of varying the system parameters. Maximum tank centerline temperatures are calculated for a typical tank as a function of the

system variables. These calculated maximum centerline temperatures are in excellent agreement with those of the 2-D iterative model.

The 2-D model calculates the complete temperature distribution in the tank using the HEATING4 computer program. A uniform sludge layer with or without an annular pile along the wall is assumed. The 2-D model is relatively easy to set up and modify for different cases and can be used to calculate the tank temperature distribution as a function of the system variables. Maximum tank wall temperatures are calculated for a typical tank with varying sludge distribution and heat generation.

The 3-D model, which also uses the HEATING4 computer program, specifically models the sludge configuration in Tank 101-A. The actual piles of sludge are modeled in three dimensions and the tank temperatures are given as a function of the sludge heat generation rate. For a sludge volume of 422 ft³, a heat rate of 18 Btu/hr-ft³, and a 24-ft salt cake layer, the 3-D model predicts a maximum edge temperature of 243°F and a circumferential gradient of 0.36°F/ft.

A comparison of the 1-, 2-, and 3-D models indicates that the accuracy increases as the complexity of the model increases. This increased accuracy is offset by the lost flexibility of applying the models and the increase in cost. The three models can be used together to perform a complete heat transfer analysis of an underground storage tank system. A time and cost effective study will result from applying the simpler models first and proceeding to the more complex models as the desired degree of accuracy and the use of the results require.

SYSTEM DESCRIPTION

Two areas of concern in the storage of heat generating fission waste in the underground tanks at Hanford are the temperatures in the tank and the thermal gradients in the tank walls. To prevent possible structural failures, the temperatures and gradients should not exceed the operating limits of the concrete shell, particularly the bottom of the tank wall. If this area exceeds the temperature limit of the concrete for an extended period of time, cracking could occur and the dome of the tank could subsequently be damaged. The bottom edge is particularly susceptible because there is a residual layer of high heat generating sludge left after sluicing operations. The sludge is 1 to 4 in. deep and has a heat generation rate nearly 200 times that of the salt cake. The problem is increased by the fact that the sludge tends to accumulate along the walls of the tank.

The heat transfer of an underground tank containing salt cake and sludge is difficult to describe for several reasons. Inside the tank the heat generation of the waste and sludge is not uniform and varies in time due to decay, and the thermal properties of the material are not uniform or well known. Also, the thermal properties of soil outside the tank are not uniform and the moisture content is unpredictable. Another difficulty in knowing the material properties is that the system will take a long time to reach steady-state. Due to these difficulties, the heat transfer analysis must be an idealized one.

The analysis is steady-state and is based on conservative values for the thermal properties of the materials and on a simplified geometry. The values, which were supplied by ARHCO and were selected as being representative, are:

- the salt cake's depth is 24 ft
- heat generation rate for the salt cake is 0.1 Btu/hr-ft^3 , and
- the conductivity for the soil, concrete, salt cake, and sludge is $0.25 \text{ Btu/hr-ft-}^\circ\text{F}$.

The geometry is based on the system of a steel tank with a concrete shell. This tank is 76 ft in diameter and 32 ft tall on the inside edge. It has

7 ft of soil cover at the center of the ellipsoidal roof and is assumed to be in a large array of tanks with 120 ft center-to-center spacing. The geometry is simplified by assuming the concrete has the same conductivity as the soil and by neglecting the effects of the reinforcing steel and the 3/8-in. thick steel liner. The inclusion of a steel liner caused the wall temperature to decrease only 6°F. All equipment in the tank such as recirculators, pipes, and instrumentation are neglected. A section drawing of an actual tank is shown in Figure 1.

The boundary conditions assumed for the system are:

- no radial heat flow beyond a 60-ft radius (other tanks in the farm are also generating heat which creates a null area between the tanks where there is no heat transfer),
- a water table at a 252 ft depth which serves as an infinite heat sink at 60°F, and
- convection to the air at ground level.

The average conditions at ground level are: temperature equal to 55°F and wind velocity equal to 7.6 mph (heat transfer coefficient = 4.0 Btu/hr-ft²-°F).⁽⁶⁾

FIGURE 1. Section Diagram of a Typical Underground Storage Tank

THE COMPUTER MODELS

Three models, with several versions each, are used in the heat transfer analysis of the Hanford waste tanks. The first model, which uses one dimensional (1-D) analysis, is used to generate preliminary information and to determine the effects of varying the parameters of the tank system. This model is intended only to estimate the heat flows and to calculate the temperatures along the axis of the tank. It does not calculate the temperature distribution throughout the tank system as do the other two models.

The second model uses the finite difference program, HEATING4, and is based on a 2-D geometry. The purpose of the 2-D model is to provide an accurate and general description of the tank. Although the 2-D model is more difficult to use than the 1-D, it has the capability of providing more accurate temperatures and a complete temperature distribution. This model can have a uniform layer of sludge with or without an annular pile along the wall. The amount and configuration of the sludge and its heat generation rate are varied in the use of the model. The 2-D model is also used to study the effects of changing the number of nodes, using a steel liner, changing the boundary conditions, and using different vapor space models.

The third model also uses the finite difference program, HEATING4, and is based on a 3-D geometry. The 3-D model consists of two versions. The first version is a 360° model which was developed to specifically model one tank. It is used to model actual piles of sludge as found in Tank 101-A and also serves as a reference for comparison with the 2-D model. The second version is a 180° model which was developed to have a 3-D model with more versatility. This model is easier to use than the 360° model, requires less computer time, and allows the use of smaller nodes resulting in better computational accuracy.

THE ONE-DIMENSIONAL MODEL

The 1-D model provides a rapid approximate calculation of the tank system temperatures and heat flows; Figure 2 shows a sketch of the model and the nomenclature used for the various system parameters is defined in

FIGURE 2. Schematic Diagram of the One-Dimensional Model

Table 1. The 1-D model assumes a uniform heat generating layer of sludge on the bottom of a waste tank containing salt cake. The input for this model is: tank geometry, soil cover depth, water table depth, sludge, salt cake, and soil thermal characteristics, and ambient temperatures. The model initially assumes no radial heat transfer in the tank and calculates the temperature distribution in the tank as a function of the bottom centerline temperature. A lumped parameter approach is then used and the heat flows from the tank are approximated by using overall heat transfer coefficients,

TABLE 1. Summary of the One-Dimensional Test Cases^(a)

Run	Variables						1-D Model	2-D Model		Percent Difference
	K_S	K_C	K_G	L_S	L_C	S_S	T_2	T_2	T_E	
1	0.5	0.25	0.25	1	24	18	1421	1414	1091	+0.5
2	0.25	0.25	0.25	0.5	18	18	759	708	548	+7.2
3	0.25	0.25	0.25	0.1875	12	18	313	288	232	+8.7
4	0.25	0.25	0.25	0.1875	18	18	382	350	280	+9.1
5	0.5	0.5	0.25	0.1875	24	18	342	328	282	+4.3
6	0.25	0.25	0.5	0.1875	24	18	293	277	217	+5.8
7	0.25	0.25	0.25	0.1875	24	18	431	404	324	+6.7
8	0.25	0.25	0.25	0.1667	24	18	405	394	309	+2.8
9	0.25	0.25	0.25	0.1667	24	27	508	507	392	+0.2
10	0.25	0.25	0.25	0.1667	24	36	611	622	476	-1.8

(a) A comparison is made with a simplified two-dimensional model.

Variables used in Figure 2 and Appendix A

L_G = Soil cover depth = 11 ft
 L_V = Vapor space thickness = $36 - (L_C + L_S)$ ft
 L_C = Saltcake thickness, ft
 L_W = Water table depth below tank = 200 ft
 L_S = Sludge thickness, ft

R = Tank radius = 37.5 ft
 B_R = One half tank center to center dist = 60 ft
 W = Mass flow rate of air = 0
 C_p = Heat capacity of air = 0.24 Btu/lb°F

K_S = Thermal conductivity of sludge, Btu/hr ft°F
 K_C = Thermal conductivity of saltcake, Btu/hr ft°F
 K_G = Thermal conductivity of soil, Btu/hr ft°F
 H = Convective heat transfer coefficient = 2 Btu/hr ft²
 S_C = Saltcake heat generation = 0.1 Btu/hr ft³
 S_S = Sludge heat generation = 18 Btu/hr ft³

T_A = Ambient air temp = 60°F
 T_W = Water table temp = 60°F
 T_2 = Bottom centerline temp of tank, °F (T_{CL} , for the other models)
 T_1 = Centerline temp of top of saltcake, °F
 T_E = Maximum edge temp of tank, °F (T_{wall} , for the other models)

Q_A = Heat flow to circulating air, Btu/hr
 Q_B = Heat flow from bottom of tank to water table, Btu/hr
 Q_C = Heat flow from side of salt cake to air, Btu/hr
 Q_D = Heat flow from top of salt cake to air, Btu/hr
 Q_V = Heat flow from side of vapor space to air, Btu/hr

average areas, and path lengths. A heat balance is then made and the system temperatures are calculated. Due to the 1-D heat transfer assumption, the bottom centerline temperature is over-estimated. Thus, a correction factor is applied based on the respective axial and radial heat transfer resistances.

The derivation and detailed assumptions for the 1-D model are given in Appendix A while Appendix B gives a listing of the computer program ATANK. This program is set up to run interactively on the CYBER system. The code presently has the capability of finding the maximum temperature at the bottom of the tank given a sludge thickness, calculating the maximum uniform sludge thickness given a bottom centerline temperature criteria, or calculating the salt cake thickness given a sludge thickness and a temperature criteria. The system heat flows are also printed out.

The results from the different cases run with the 1-D model are shown in Table 1. These results are compared to the 2-D model version that has a geometry very similar to the 1-D model (Table 1). The percentage differences between the two models are well within the degree of accuracy of the input data. The benefits of using the 1-D model are fast running time, low cost, and the ability to easily vary system parameters. However, it must be emphasized that the 1-D model is approximate, is not as accurate, and does not provide the same kind and detail of information as the 2- and the 3-D models. Thus, these later models should be used when more precise results are required.

THE TWO-DIMENSIONAL MODEL

Both the 2- and 3-D models use the HEATING4 heat conduction program⁽⁸⁾ which is available to the users of the CYBER system at Hanford. This program was selected because of its general acceptance as a good and versatile modeling tool. HEATING4 is a finite difference program which uses the "Extrapolated Liebman" numerical method and has been shown to be accurate within 1% if the convergence criterion is 10^{-5} . This does not imply the temperatures calculated are that close to those temperatures generated in the real tank. The

reality of the temperatures is dependent on the assumptions and data used as input. A complete discussion of the program's capabilities, numerical methods, and use is available in Reference 7. Appendix C presents a sample case illustrating the output of HEATING4.

A schematic diagram of the geometry for the 2-D model is given in Figure 3. The tank system is broken up into regions with specified properties and a grid of nodes is set up. A system of heat balance equations are solved to obtain a temperature at each node. The number of nodes does influence the results as is verified in Table 2 which shows that increasing the number of nodes, or decreasing their size, causes an apparent increase in the temperatures. This is a result of a weighting method HEATING4 uses in setting up the heat balance equations at the nodes. This phenomena may be important in the use of the 3-D models. In these models, the nodes are necessarily quite large due to the fact that the CYBER computer system is not able to handle the number of nodes required for a fine grid.

After dividing the system into numbered regions, the boundary conditions are established and a model for the vapor space is set up. The model of the vapor space in the tank is unimportant when considering the overall analysis of the tank since the vapor space provides only about 1% of the total thermal resistance to the heat flow in the vertical direction. The main heat transfer mechanism in the vapor space is assumed to be radiation, and, at the temperatures considered, the heat transfer coefficient is estimated to be $1.0 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$. The model selected replaces the air with materials having a thermal resistance, $\frac{X}{k}$ (where X is the material thickness and k is the thermal conductivity) equal to the thermal resistance of $\frac{1}{h}$, where $h = 1.0 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$. The shape of the dome is approximated by four steps. This model provides good results and fast convergence; for further discussion of the vapor space model see Appendix D.

Table 3 summarizes the cases run. The first five cases use a uniform sludge layer, the next four use an annular sludge pile on a uniform layer, and the last case uses no sludge. The uniform layer cases approximate

(a) VALUES FOR CONDUCTIVITY, $\text{Btu/hr ft}^{\circ}\text{F}$

FIGURE 3. Schematic Diagram of the Two Dimensional Model Showing Dimensions and Region Numbers

TABLE 2. Critical System Temperatures Using Different Numbers of Nodes^(a)

Number of Nodes	Different Numbers of Temperature, °F ^(b)		
	T _{CL}	T _{wall}	T _{vap}
140	261	235	136
228	273	238	137
726	284	242	139
1014	284	243	139

(a) The two-dimensional model with the "k/X" vapor space was used.

(b) T_{CL} -- The bottom centerline temperature

T_{wall} -- The bottom wall temperature (maximum in the 3-D model)

T_{vap} -- The vapor space temperature

TABLE 3. Summary of the Two-Dimensional Test Cases

Case Number	Heat Rate Btu/hr-ft ³	Sludge Configuration, in.	Temperature, °F		Vapor Space	Number of Nodes
			T _{wall}	T _{CL}		
1	18.0	3/4 Uniform Layer	192	221	k/X ^(a)	209
2	18.0	2-1/4 Uniform Layer	334	406	Surf-to-Surf	170
3	18.0	2 Uniform Layer	309	394	k/X	672
4	27.0	2 Uniform Layer	392	507	k/X	672
5	36.0	2 Uniform Layer	476	622	k/X	672
6	18.0	3/4 Uniform, 1-1/3 Annular	238	273	k/X	228
7	36.0	3/4 Uniform, 1-1/3 Annular	340	398	k/X	672
8	18.0	3/4 Uniform, 2-1/4 Annular	290	323	k/X	209
8	36.0	3/4 Uniform, 2-1/4 Annular	445	490	Surf-to-Surf	180
9	--	No sludge	145	173	k/X	672

(a) k/X indicates the vapor space model using the materials with the same thermal resistance as calculated for the real vapor space.

those tanks where the sludge distribution is unknown. The annular sludge pile provides a better approximation of the suspected sludge configuration than the uniform layer. The annular version has a much lower temperature gradient across the floor of the tank which is closer to the 360° reference model, which has a known sludge configuration.

In addition to specifically examining the wall temperatures for various sludge configurations, the 2-D model was also used to examine the temperature distribution in the entire system. The temperature distribution for a tank with a 3/4-in. uniform layer on the bottom and a 1-1/3-in. annular pile of sludge (422-ft³, which is equal to the sludge volume in the 3-D runs) is shown in Figure 4. The total heat generated is 18,500 Btu/hr. Calculations show that 51% of the heat goes through the dome, 36% out the side, and 13% out the bottom. Heat transfer paths are perpendicular to the isothermal lines. The temperature map of the system also allows one to determine the thermal gradients in the radial and vertical directions.

THE THREE-DIMENSIONAL MODEL

The main emphasis of the 3-D work is to model the actual sludge configuration as found in Tank 101-A. This model is needed to determine whether piles of sludge along the wall could create hot spots exceeding the cement temperature limit or cause excessive temperature gradients along the wall. An illustration of the sludge piles, which was supplied by ARHCO, is shown in Figure 5. The final representation of the piles for the model is shown in Figure 6. There are three distinct levels of sludge: a 3/4-in. uniform layer, a series of piles at 2-1/4 in., and an area 3-1/4-in. deep. The large and rather crude approximations are necessary to allow the program to run on the CYBER system. The small slice missing from the model is necessary to avoid a convergence problem in HEATING4. The slice does not affect the results because it is in an area of very little circumferential heat transfer. (Note the small temperature difference across it.)

FIGURE 4. Temperature Distribution in the Two-Dimensional Model Using an Annular Sludge Pile

FIGURE 5. Sludge Piles Found in Tank 101-A

FIGURE 6. Approximation of Sludge Piles for Use in the Three-Dimensional, 360° Model. (The temperature distribution of the first three-dimensional case is shown. These temperatures are from Z latitude Line 4.)

Three cases were run with the 360° model. The results from the first case can be seen in Figures 6 and 7 and a summary of all three cases is in Table 4. At the heat rate of 18.0 Btu/hr-ft³ for the sludge, the maximum wall temperature is 243°F and the largest circumferential gradient is 0.36°F/ft. The hottest spot is 260°F which is on the corner of Region 22 (Figure 6). The results for T_{wall} are very similar to those found by the 2-D model that uses the same amount of sludge. The temperatures were within 1 to 5°F at the sludge heat rate of 18.0 and 36.0 Btu/hr-ft³. There is a large difference between the 2-D and 3-D models in the magnitude of the temperature gradient along the floor which is much smaller in the 3-D model due to the nonsymmetrical distribution of sludge.

A compromise between the 360° and the 2-D models is the 180° model which predicts conservative temperatures. The results from this model are summarized in Table 4 and Figure 8. This model approximates the sludge piles as one or two large piles. The smaller size of this model allows smaller nodes and easier analysis of the data. This model comes quite close to the temperatures predicted by the 360° model and the circumferential gradients are very similar.

TABLE 4. Summary of the Three-Dimensional Test Cases^(a)

Case Number	Type	Heat Rate Btu/hr-ft ³	Temperature, °F				Max Grad °F/ft	Number of Nodes
			T_{CL}	T_{wall}	T_{max}	T_{vap}		
1	360°	18.0	256	243	260	132	0.36	1089
2	360°	36.0	358	345	370	161	0.69	1089
3	360°	54.0	459	446	479	190	1.02	1089
4	180°	18.0	263	254	271	136	0.42	936

(a) All cases used the "k/X" vapor space

FIGURE 7. Temperatures from the Three-Dimensional, 360° Model (Case one).
(The temperatures are from Theta Lattice Line 7.)

COMPARISON OF THE MODELS

The 1-D model provides useful information about the waste tank. It can be used to provide preliminary numbers and to show trends which are useful in setting up the more complex models, or it can provide results for direct use. The centerline temperatures predicted by this model are within 10% of those predicted by the simple 2-D model. The advantages of the 1-D model are that it is very easy to use, it has a fast running time, and it has a low use cost. The disadvantages are that it calculates only the centerline temperatures and it loses accuracy as the sludge configuration diverges from a uniform layer.

The 2-D model eliminates the disadvantages of the 1-D model with a small increase in complexity and running cost. In a simplified form this model can also be run for parametric studies. The 2-D model does not provide heat flows as the 1-D model does but the temperature map allows one to plot isotherms which show the heat flows. This map also allows the user to calculate the radial and vertical thermal gradients in the concrete. Precise results from this model are limited to tanks with 360° symmetry in the sludge configuration. However, the 2-D model will predict wall temperatures for a nonsymmetrical tank within 5% of those calculated by the 360° model. Therefore, in routine studies, the 2-D model should be used over the more complex and costly 3-D model.

The results from the 2-D and 3-D models were plotted on a graph of edge temperature versus specific heat generation. The specific heat generation rate is the heat rate multiplied by the thickness of an equivalent uniform layer. As shown in Figures 9 and 10, the results plot out as three straight lines which means that one can take any case for one of the three general geometries and find the maximum edge temperature. This graph is based on the conditions and properties as listed in Figure 9 and is therefore limited in application. This type of correlation is possible because the sludge piles appear as a plane heat source relative to the rest of the model. This suggests that a

FIGURE 9. Plots of Wall Temperature Versus Specific Heat Generation for Various Geometries

FIGURE 10. Linear Regression Equations of Data in Figure 9

2-D model could be set up with one segmented layer on the bottom of the tank. The heat rate for each segment could be varied so as to simulate various heights of sludge. From Figure 9, it can be seen that the 2-D model is slightly nonconservative as compared to the 3-D model. However, this is only true for the maximum wall temperature. The majority of the wall temperatures in a 3-D case are lower than in the equivalent 2-D case. Caution should be taken when using the 3-D line. The 3-D model was developed for a specific case and other 3-D models are not applicable unless they have a very similar geometry.

The 3-D model has some further advantages over the others along with an increase in complexity and running cost. The 3-D model is necessary to show hot spots and circumferential temperature gradients that are due to the concentration of sludge into piles. Also, the effects of vertical cooling pipes can be evaluated using this model. In cases of critical analysis, the 3-D model will provide more precise wall temperatures than can be gained from the 2-D model. This may be somewhat offset by a small loss of computational accuracy due to the large size of the nodes in the 3-D model. This loss can be minimized by taking advantage of symmetry and using the 180° model.

A comparison of the 1-, 2-, and 3-D models shows that as the accuracy of the results increases the complexity of the model increases. This means that for a time- and cost-effective analysis the simple models should be used predominantly. Their use should emphasize developing the geometry, checking assumptions, and making parametric studies. After the assumptions and various parameters are set, the 3-D model should be run once or twice to obtain the final temperatures. All of the models should be used for a complete heat transfer analysis of a tank system.

RECOMMENDATIONS

Further work on the heat transfer analysis of a waste tank should be done. The work, as discussed in this report, was directed primarily at developing a set of steady-state models and demonstrating their usefulness. Only the 3-D model was applied to an actual situation. Future work should be directed toward using the present models and developing new ones with extended capabilities.

Parametric studies should be made with the existing models to evaluate the effects and importance of various system parameters. As circumstances change, these models can be used to test different modeling techniques and assumptions. For example, the effect of air flow in the vapor space should be evaluated if the air flow rate becomes significant. Other work can be directed toward evaluating different approaches of cooling the tank. As an example, work has been started on modeling vertical heat pipes in the tank. These heat pipes appear to have a good potential for lowering the tank temperatures. Finally, an effort should be made to relate the results of these models to actual data from a tank. This is important when confirming the confidence in predicted temperatures.

Work on new or improved models should be directed two ways. First, work should continue on the 3-D model to improve its convergence time and flexibility. A possible approach to increasing flexibility is to set up HEATING4 on a larger computer which would allow more nodes to be used. Secondly, work should be done on setting up a model that describes the transient response of the system. This can be done by modifying the existing models to use the transient capability of HEATING4. A prediction of temperature versus time for the system will be important in monitoring whether the tank system is approaching the steady-state condition predicted by the existing models. This should allow any corrective action to be taken before any problems develop.

APPENDIX A

DERIVATION OF EQUATIONS FOR THE ONE-DIMENSIONAL MODEL

APPENDIX A

DERIVATION OF EQUATIONS FOR THE ONE-DIMENSIONAL MODEL

A sketch of the one-dimensional (1-D) model was shown in Figure 2. The horizontal plane of maximum temperature across which no heat flows is assumed to lie in the sludge layer. This assumption is true for the typical situations encountered with a fairly large water table depth and sludge heat generation rate. The heat transfer out the sides of the saltcake and the sludge is initially neglected, that is, the heat flow is assumed one dimensional. Table 1 defines the variables used in the analysis.

An overall heat balance on the cake and sludge and a heat balance on the section below the null plane gives

$$S_C \pi R^2 L_C + S_S \pi R^2 L_S = \frac{K_G}{L_W} \pi R^2 (T_2 - T_W) + H \pi R^2 (T_1 - T_V) \quad (A-1)$$

$$S_S \pi R^2 X_N = \frac{K_G}{L_W} \pi R^2 (T_2 - T_W) \quad (A-2)$$

where

T_V = vapor space temp

X = vertical direction

X_N = location of null plane.

The relationship between T_1 at the top of the saltcake and T_2 at the bottom of the sludge is found by solving the heat equation for each region and applying the proper boundary conditions. These relationships are:

for the sludge

$$\frac{d^2 T}{dX^2} = - \frac{S_S}{K_S}$$

at $X = X_N$, $\frac{dT}{dX} = 0$

$$\text{at } X = 0, T = T_2.$$

for the saltcake

$$\frac{d^2T}{dX^2} = - \frac{S_C}{K_C}$$

$$\text{at } X = L_S, K_S \frac{dT}{dX} = K_C \frac{dT}{dX}$$

$$\text{at } X = L_C + L_S, T = T_1.$$

The resulting expression is

$$T_2 = T_1 + \frac{S_C L_C^2}{2K_C} + \frac{S_S L_S L_C}{K_C} + \frac{S_S L_S^2}{2K_S} - \frac{S_S X_N L_S}{K_S} - \frac{S_S X_N L_C}{K_C}. \quad (A-3)$$

As a whole heat flows in the waste tank are examined. Referring to Figure 2 the following approximations are made for the various heat flows:

$$Q_A = WC_P (T_V - T_A) \quad (A-4)$$

$$Q_B = \frac{K_G A_R}{L_W} (T_2 - T_W) \quad (A-5)$$

$$Q_C = \frac{T_C - T_A}{\frac{\sqrt{(B_R - R)^2 + \left(\frac{L_C}{2} + L_V + L_G\right)^2}}{K_G \frac{(A_C + A_{BR} - A_R)}{2}}} \quad (A-6)$$

$$Q_D = \frac{T_V - T_A}{\frac{L_G}{K_G A_R} + \frac{1}{H A_R}} \quad (A-7)$$

$$Q_V = \frac{T_V - T_A}{\frac{1}{H A_V} + \frac{\sqrt{(B_R - R)^2 + \left(L_G + \frac{L_V}{2}\right)^2}}{K_G \frac{(A_V + A_{BR} - A_R)}{2}}} \quad (A-8)$$

where the variables are defined in Table 1 or given below:

T_V = vapor space temperature

T_C = average edge temperature of saltcake = $\frac{T_1 + 0.5T_2}{2}$

$A_R = \pi R^2$

$A_{BR} = \pi B_R^2$

$A_C = 2\pi R L_C$

$A_V = 2\pi R L_V$

An overall heat balance can be written as

$$Q_A + Q_B + Q_C + Q_D + Q_V = S_C A_R L_C + S_S A_R L_S \quad (A-9)$$

using the simplifying and conservative assumption that $T_V \approx T_1$ with Equations (A-2) through (A-8) one gets

$$T_1 = \frac{Z_6 + Z_7}{Z_5} \quad (A-10)$$

$$T_2 = \frac{T_1 + Z_0}{Z_1} = \frac{\frac{Z_6 + Z_7}{Z_5} + Z_0}{Z_1} \quad (A-11)$$

where

$$Z_0 = \frac{S_C L_C^2}{2K_C} + \frac{S_S L_S L_C}{K_C} + \frac{S_S L_S^2}{2K_S} + T_W \left(\frac{L_S K_G}{K_S L_W} + \frac{L_C K_G}{K_C L_W} \right)$$

$$Z_1 = 1 + \frac{L_S K_G}{K_S L_W} + \frac{L_C K_G}{K_C L_W}$$

$$Z_3 = \frac{L_G}{K_G A_R} + \frac{1}{H A_R}$$

$$Z_4 = \frac{1}{H A_V} + \sqrt{\frac{(B_R - R)^2 + (L_G + \frac{L_V}{2})^2}{K_G \frac{(A_V + A_{BR} - A_R)}{2}}}$$

$$Z_5 = W C_P + \frac{K_G A_R}{L_W Z_1} + \frac{1}{2Z_2} + \frac{1}{4Z_1 Z_2} + \frac{1}{Z_3} + \frac{1}{Z_4}$$

$$Z_6 = S_C A_R L_C + S_S A_R L_S + W C_P T_A - \frac{K_G A_R Z_0}{L_W Z_1} + \frac{K_G A_R T_W}{L_W}$$

$$Z_7 = -\frac{Z_0}{4Z_1 Z_2} + T_A \left(\frac{1}{Z_2} + \frac{1}{Z_3} + \frac{1}{Z_4} \right).$$

Equations (A-10) and (A-11) are the desired equations and give T_2 as a function of known quantities. Due to the 1-D heat transfer assumption, the bottom centerline temperature is overestimated. A correction factor based on the respective axial and radial heat transfer resistances is applied. In the comparison with the iterative results T_1 is found to be modeled correctly. When calculating T_2 from Equation (A-11), the following factor is applied based on the fraction of vertical versus radial heat transfer in the sludge and saltcake.

$$Q_T = S_C A_R L_C + S_S A_R L_S = \text{total heat generated}$$

$$Q_C = \text{heat flow through side of saltcake}$$

$$X = 1 - \frac{Q_C}{Q_T - Q_C}$$

$$T_{2C} = T_1 + X(T_2 - T_1).$$

ATANK - A simplified model for underground storage tank heat transfer is the computer program incorporating the above equations. It is presently set up to run interactively on the CYBER INTERCOM system; a listing of this program is given in Appendix B. ATANK is intended to calculate

temperatures only along the axis of the tank and not the temperature distribution as HEATING4 does. The model is approximate and should be used to generate preliminary information. The two or three dimensional HEATING4 iterative models should be used for critical calculations.

APPENDIX B

ATANK

THE COMPUTER PROGRAM

FOR THE ONE-DIMENSIONAL MODEL

```

PROGRAM ATANK(INPUT,OUTPUT)                                000100
REAL LG,LV,LC,LS,LW,LH,KG,KC,KS,LC1,LS1,LV1,KC1,KS1      000110
PRINT*,"          PROGRAM ATANK-A SIMPLIFIED MODEL FOR UNDERGROUND"000120
PRINT*,"          STORAGE TANK HEAT TRANSFER"              000130
PRINT*," "                                                  000140
PRINT*,"THE FOLLOWING BLOCKS OF DATA ARE INPUT"           000150
PRINT*," "                                                  000151
PRINT*,"          SYSTEM GEOMETRY"                         000160
PRINT*,"          R=TANK RADIUS, FT"                       000170
PRINT*,"          HR=ONE-HALF TANK CENTER TO CENTER DIST., FT." 000180
PRINT*,"          LG=SOIL COVER DEPTH, FT."                 000190
PRINT*,"          LV=VAPOR SPACE THICKNESS, FT"             000200
PRINT*,"          LC=SALTCAKE THICKNESS, FT"                 000210
PRINT*,"          LS=SLUDGE THICKNESS, FT"                  000220
PRINT*,"          LW=WATERTABLE DEPTH, FT."                 000230
PRINT*,"          LH=TANK HEIGHT, FT"                        000235
PRINT*," "                                                  000240
PRINT*,"          THERMAL CHARACTERISTICS"                  000250
PRINT*,"          KG=THERMAL CONDUCTIVITY OF SOIL, BTU/HRFT.F" 000260
PRINT*,"          KC=THERMAL CONDUCTIVITY OF SALTCAKE"       000270
PRINT*,"          KS=THERMAL CONDUCTIVITY OF SLUDGE"         000280
PRINT*,"          H=CONVECTIVE HEAT TRANSFER COEF, BTU/HRFT.F" 000290
PRINT*,"          SC=SALTCAKE HEAT GENERATION, BTU/HRFT3"    000300
PRINT*,"          SS=SLUDGE HEAT GENERATION, BTU/HRFT3"      000310
PRINT*,"          CP=HEAT CAPACITY OF AIR, BTU/LB.F"         000320
PRINT*," "                                                  000330
PRINT*,"          BOUNDARY TEMPERATURES AND AIR FLOW RATE"  000340
PRINT*,"          TA=AMBIENT AIR TEMP, .F"                  000350
PRINT*,"          TW=WATERTABLE TEMP, .F"                   000360
PRINT*,"          T2=BOTTOM CENTERLINE TEMP OF TANK, .F"    000370
PRINT*,"          W=MASS FLOW RATE OF AIR, LB/HR"            000371
PRINT*," "                                                  000372
PRINT*," "                                                  000373
PRINT*,"ENTER 1 IF WANT A DIAGRAM OF THE MODEL; 0 IF NOT"   000374
READ*,FLAGX                                                 000375
IF (FLAGX.EQ.0) GO TO 5                                     000376
PRINT*," "                                                  000377
PRINT*," "                                                  000378
PRINT*," "                                                  000379
PRINT*," "                                                  000380
PRINT*,"          SIMPLIFIED WASTE TANK DIAGRAM"           000381
PRINT*," "                                                  000382
PRINT*,"          T0=AIR TEMPERATURE"                      000383
PRINT*," "                                                  000384
PRINT*," "                                                  000385
PRINT*,"          QC  QV          QA          QD          W          " 000386
PRINT*,"          ^  ^          ^          ^          !          " 000387
PRINT*,"          -----*-----*-----*-----*-----*-----SOIL" 000388
PRINT*," !          *          *          *          *          *          " 000389
PRINT*," !          .          .          .          .          .          " 000390
PRINT*," !          *          *          *          *          *          " 000391
PRINT*," !          .          .          .          .          .          LG" 000392
PRINT*," !          *          *          *          *          *          " 000393
PRINT*," !          .          .          .          .          .          " 000394
PRINT*," !          *-----*-----*-----*-----*-----*-----" 000395
PRINT*," !          .          *          *          *          *          " 000396
PRINT*," !          .          *          TV          *          " 000397
PRINT*," !          .          *          (VAPOR SPACE)          *          " 000398
PRINT*," !          .          *          *          *          *          LV" 000399
PRINT*," !          .          *          *          *          *          " 000400
PRINT*," !          .          *          TI          *          " 000401
PRINT*," !          .          *-----*-----*-----*-----*-----" 000402
PRINT*," !          .          *          *          *          *          " 000403
PRINT*," !          .          *          *          *          *          " 000404

```

```

PRINT*," ! * (SALTCAKE) * ." 000405
PRINT*," ! * LC" 000406
PRINT*," ! * ." 000407
PRINT*," ! * ." 000408
PRINT*," ! * ." 000409
PRINT*," ! *****" 000410
PRINT*," ! * ." 000411
PRINT*," ! * (SLUDGE) * ." 000412
PRINT*," ! * LS" 000413
PRINT*," ! *****" 000414
PRINT*," ! !.....R.....!T2 . ." 000415
PRINT*," ! .....B.....! . ." 000416
PRINT*," ! .....QB . ." 000417
PRINT*," ! LW" 000418
PRINT*," ! ." 000419
PRINT*," ! ." 000420
PRINT*," ! ." 000421
PRINT*," ! ." 000422
PRINT*," ! ." 000423
PRINT*," ! -----TW=WATER TABLE TEMP-----" 000424
PRINT*," " 000425
PRINT*," " 000426
PRINT*," " 000427
5 PRINT*,"ENTER 1 IF WANT TO CONTINUE,ENTER 0 IF WANT TO STOP" 000430
READ*,FLAG1 000431
IF (FLAG1.EQ.0) GO TO 140 000432
PRINT*," " 000433
PRINT*," " 000434
PRINT*," " 000435
PRINT*,"THIS PROGRAM HAS THREE OPTIONS" 000436
PRINT*," 1 KNOW LS AND LC CALCULATE T2" 000440
PRINT*," 2 KNOW LC AND T2 CALCULATE LS" 000450
PRINT*," 3 KNOW LS AND T2 CALCULATE LC" 000460
PRINT*,"ENTER 1, 2, OR 3 FOR DESIRED OPTION" 000470
READ*,FLAG 000480
IF (FLAG.EQ.1) GO TO 10 000490
IF (FLAG.EQ.2) GO TO 20 000500
IF (FLAG.EQ.3) GO TO 30 000510
10 PRINT*,"ENTER R,BR,LG,LV,LC,LS,LW SEPARATED BY COMMAS" 000520
PRINT*," " 000530
READ*,R,BR,LG,LV,LC,LS,LW 000540
PRINT*,"ENTER KG,KC,KS,H,SC,SS,CP SEPARATED BY COMMAS" 000550
PRINT*," " 000560
READ*,KG,KC,KS,H,SC,SS,CP 000570
PRINT*,"ENTER TA,TW,W SEPARATED BY COMMAS" 000580
PRINT*," " 000590
READ*,TA,TW,W 000600
N=1 000610
GO TO 40 000620
20 PRINT*,"ENTER P,BR,LG,LV,LC,LW SEPARATED BY COMMAS" 000630
PRINT*," " 000640
READ*,P,BR,LG,LV,LC,LW 000650
PRINT*,"ENTER KG,KC,KS,H,SC,SS,CP SEPARATED BY COMMAS" 000660
PRINT*," " 000670
READ*,KG,KC,KS,H,SC,SS,CP 000680
PRINT*,"ENTER TA,TW,T2,W SEPARATED BY COMMAS" 000690
PRINT*," " 000700
READ*,TA,TW,T2,W 000710
PRINT*,"ENTER INITIAL ESTIMATE FOR LS" 000720
PRINT*," " 000730
READ*,LS 000740
LC1=LC 000750
LS1=LS 000760
SC1=SC 000770
SS1=SS 000780
KC1=KC 000790

```

	KS1=KC	000800
	T21=T2	000810
	LS=LC	000820
	KS=KC	000830
	CS=SC	000835
	AR=3.14*R**2	000840
	ABR=3.14*BR**2	000850
	AC=2*3.14*R*LC	000860
	AV=2*3.14*R*(LV+LS)	000870
	LC=0	000880
	SC=0	000890
	N=0	000900
	GO TO 15	000910
30	PRINT*, "ENTER R, BR, LG, LS, LW, LH SEPARATED BY COMMAS"	000920
	PRINT*, " "	000930
	READ*, R, BR, LG, LS, LW, LH	000940
	PRINT*, "ENTER KG, KC, KS, H, SC, SS, CP SEPARATED BY COMMAS"	000950
	PRINT*, " "	000960
	READ*, KG, KC, KS, H, SC, SS, CP	000970
	PRINT*, "ENTER TA, TW, T2, W SEPARATED BY COMMAS"	000980
	PRINT*, " "	000990
	READ*, TA, TW, T2, W	001000
	PRINT*, "ENTER INITIAL ESTIMATE FOR LC"	001010
	READ*, LC	001020
	LV=LH-(LC+LS)	001025
	LC1=LC	001030
	LS1=LS	001040
	LV1=LV	001041
	SC1=SC	001050
	SS1=SS	001060
	KC1=KC	001070
	KS1=KS	001080
	T21=T2	001090
	AR=3.14*R**2	001100
	ABR=3.14*BR**2	001110
	AC=2*3.14*R*LS	001120
	AV=2*3.14*R*(LV+LC)	001130
	LC=0	001140
	SC=0	001150
	LV=LH-LS	001159
	N=0	001160
	GO TO 15	001170
50	TN=T2A	001180
	LC=LC1	001190
	LS=LS1	001200
	LV=LV1	001201
	SC=SC1	001210
	SS=SS1	001220
	KC=KC1	001230
	KS=KS1	001240
	T2=T21	001250
	N=1	001260
	IF (TN.GE.T2) GO TO 180	001270
40	AR=3.14*R**2	001280
	ABR=3.14*BR**2	001290
	AV=2*3.14*R*LV	001300
	AC=2*3.14*R*LC	001310
15	R=.5	001315
	V0=TW*(LS*KG/(KS*LW)+LC*KC/(KC*LW))	001320
	Z0=SC*LC**2/(2*KC)+SS*LS*LC/KC+SS*LS**2/(2*KS)+X0	001330
	Z1=1+LS*KG/(KS*LW)+LC*KG/(KC*LW)	001340
	Z2=(SQRT((BR-R)**2+(LC/2+LV*LG)**2))/((KG/2)*(AC+ABR-AR))	001350
	Z3=LG/(KG*AR)+1/(H*AR)	001360
	Z4=1/(H*AV)+(SQRT((BR-R)**2+(LG+LV/2)**2))/((KG/2)*(AV+ABR-AR))	001370
	Z5=4*CP*KG*AR/(LW*Z1)+1/(2*Z2)+F/(2*Z1*Z2)+1/Z3+1/Z4	001380
	Z6=SC*AR*LC+SS*AR*LS+W*CP*Z4-KG*AC*Z0/(LW*Z1)+KG*AR*TW/LW	001390

	T7=-F*20/(2*Z1+Z2)+TA*(1/2+1/3+1/4)	001400
	T1=(T4+T7)/75	001410
	T2B=(T1+Z0)/Z1	001420
	TC=(T1+F*T2B)/2	001421
	QCA=(TC-TA)/Z2	001422
	X=1-QCA/(SS*LS*AR+SC*LC*AP-QCA)	001423
	T2A=T1+X*(T2B-T1)	001424
	IF(M.EQ.0) GO TO 50	001430
	IF(FLAG.EQ.1) GO TO 60	001440
	IF(FLAG.EQ.2) GO TO 70	001450
	IF(FLAG.EQ.3) GO TO 80	001460
60	T2=T2A	001470
170	TV=T1	001480
	QA=W*CP*(TV-TA)	001490
	QB=(KG*AP/LW)*(T2-TW)	001500
	TC=(T1+F*T2)/2	001510
	QC=(TC-TA)/Z2	001520
	QD=(TV-TA)/Z3	001530
	QV=(TV-TA)/Z4	001540
	PRINT*," "	001541
	PRINT*," "	001542
	PRINT*," RESULTS OF ATANK"	001543
	PRINT*,"-----"	001544
	PRINT*," "	001545
	PRINT*," "	001550
	PRINT*," INPUT DATA"	001555
	PRINT*," "	001556
	PRINT*," R="R	001560
	PRINT*," PR="PR	001570
	PRINT*," LG="LG	001580
	PRINT*," LW="LW	001590
	IF(FLAG.EQ.1) GO TO 90	001600
	IF(FLAG.EQ.2) GO TO 100	001610
	IF(FLAG.EQ.3) GO TO 110	001620
90	PRINT*," LC="LC	001630
	PRINT*," LS="LS	001640
	GO TO 200	001650
100	PRINT*," LC="LC	001660
	GO TO 200	001670
110	PRINT*," LS="LS	001680
	PRINT*," LH="LH	001685
200	PRINT*," "	001690
	PRINT*," KG="KG," SC="SC	001700
	PRINT*," KC="KC," SS="SS	001710
	PRINT*," KS="KS," CP="CP	001720
	PRINT*," H="H	001730
	PRINT*," "	001740
	PRINT*," TA="TA	001750
	PRINT*," TW="TW	001760
	PRINT*," W="W	001770
	IF(FLAG.EQ.1) GO TO 120	001780
	PRINT*," T2="T2	001790
120	PRINT*," "	001800
	PRINT*," "	001801
	PRINT*," OUTPUT"	001810
	PRINT*," "	001811
	PRINT*," "	001820
	PRINT*," APPROXIMATE SYSTEM HEAT FLOWS"	001830
	PRINT*," "	001831
	PRINT*,"QA=HEAT FLOW TO CIRC AIR, BTU/HR="QA	001840
	PRINT*,"QB=HEAT FROM BOTTOM OF TANK TO WATERBATH="QB	001850
	PRINT*,"QC=HEAT FROM SIDE OF SALTCAKE TO AIR="QC	001860
	PRINT*,"QD=HEAT FROM TOP OF SALTCAKE TO AIR="QD	001870
	PRINT*,"QV=HEAT FROM SIDE OF VAPOR SPACE TO AIR="QV	001880
	PRINT*," "	001881
	PRINT*," "	001882

	PRINT*,"	APPROXIMATE SYSTEM TEMPERATURES"	001883
	PRINT*," "		001884
	PRINT*,"T1=TOP CENTERLINE TEMP OF SALTCAKE, .F=",T1		001885
	PRINT*,"T2=BOTOM CENTERLINE TEMP OF TANK, .F=",T2		001886
	PRINT*," "		001887
	PRINT*," "		001888
	PRINT*,"	APPROXIMATE CAKE & SLUDGE THICKNESSES"	001889
	PRINT*," "		001890
	PRINT*,"LC=SALTCAKE THICKNESS, FT=",LC		001891
	PRINT*,"LS=SLUDGE THICKNESS, FT=",LS		001892
	PRINT*," "		001893
	PRINT*," "		001894
	PRINT*," "		001895
	PRINT*," "		001896
	PRINT*," "		001897
	GO TO 5		001990
70	IF (ABS(T2-T2A).LE.5) GO TO 170		002000
	IF ((T2-T2A).GT.0) LS=LS+.01		002010
	IF ((T2-T2A).LT.0) LS=LS-.01		002020
	GO TO 40		002030
80	IF (ABS(T2-T2A).LE.5) GO TO 170		002040
	IF ((T2-T2A).GT.0) LC=LC+.1		002050
	IF ((T2-T2A).LT.0) LC=LC-.1		002060
	GO TO 40		002070
180	PRINT*,"STEADY STATE TEMP WITH CAKE ONLY OR WITH SLUDGE ONLY"		002080
	PRINT*,"EQUALS ",IN,"PICK A HIGHER VALUE FOR T2"		002090
	GO TO 5		002100
190	STOP		002110
	END		002120

APPENDIX C

AN EXAMPLE OF THE HEATING4 OUTPUT FOR THE TWO-DIMENSIONAL MODEL

APPENDIX C

AN EXAMPLE OF THE HEATING4 OUTPUT FOR THE TWO-DIMENSIONAL MODEL

THE HEATING CODE WITH TEMPERATURE-DEPENDENT THERMAL PROPERTIES AND
NON-LINEAR AND SURFACE-TO-SURFACE BOUNDARY CONDITIONS AND CHANGE OF PHASE CAPABILITIES.
THIS VERSION OF HEATING CAN HANDLE A MAXIMUM OF 2120 LATTICE POINTS.

INPUT RETURN

DATE 05/19/76

TIME 09.21.1

JOB DESCRIPTION-- ARMO SALT CAKE STORAGE. SALT CAKE DEPTH 24FT. SLUDGE VOL. 422CU. FT.

GEOMETRY TYPE NO. 1

NUMBER OF REGIONS 24

NUMBER OF MATERIALS 8

NUMBER OF MATERIALS WITH CHANGE OF PHASE CAPABILITIES. -0

NUMBER OF INITIAL TEMPERATURE FUNCTIONS 4

NUMBER OF GENERAL POSITION DEPENDENT FUNCTIONS 4

NUMBER OF HEAT GENERATION FUNCTIONS 2

NUMBER OF TIME DEPENDENT FUNCTIONS -0

TYPE OF OUTPUT DESIRED -0

NUMBER OF POINTS IN GROSS X OR R LATTICE 8

NUMBER OF POINTS IN GROSS Y OR THETA LATTICE -0

NUMBER OF POINTS IN GROSS Z LATTICE 12

NUMBER OF DIFFERENT KINDS OF BOUNDARIES 3

NUMBER OF LATTICE POINTS FOR WHICH THE INITIAL TEMPERATURES ARE ENTERED -0

PROBLEM TYPE NUMBER 1

MAXIMUM NUMBER OF STEADY-STATE ITERATIONS 900

NUMBER OF S-S ITERATIONS BEFORE CALC BETA -0

NUMBER OF S-S ITERATIONS BEFORE EXTRAPOLATION -0

NUMBER OF DELTAS PER MONITOR PRINT -0

THE CONDUCTIVITY, DENSITY, AND HEAT CAPACITY ARE TEMPERATURE DEPENDENT.

CONVERGENCE CRITERION .1000000E-04

INITIAL BETA 1.90000000

TIME INCREMENT -0.

NUMBER OF STABLE TIME STEPS UNTIL MODIFIED EXPLICIT METHOD IS ACTIVATED -0

INITIAL TIME -0.

NUMBERS AND		FCN NUMBER		SUMMARY OF REGION DATA										BOUNDARY NUMBERS			
REG. NO.	MATL NO.	INIT TEMP	HEAT GEN.	LEFT-X-OR INNER-R	RIGHT-X-OR OUTER-R	LOWER-Y-OR LEFT-THETA	UPPER-Y-OR RIGHT-THETA	REAR-Z	FRONT-Z	LF-X IN-R	RT-X OT-R	LO-Y LF-C	UB-Y RT-C	RD-7	FT-7		
1	1	1	-0	.1000	15.0000	-0.0000	-0.0000	248.0000	252.0000	-0	-0	-0	-0	-0	1		
2	1	1	-0	15.0000	22.0000	-0.0000	-0.0000	248.0000	252.0000	-0	-0	-0	-0	-0	1		
3	1	1	-0	22.0000	29.0000	-0.0000	-0.0000	241.0000	252.0000	-0	-0	-0	-0	-0	1		
4	1	1	-0	23.0000	34.0000	-0.0000	-0.0000	241.0000	252.0000	-0	-0	-0	-0	-0	1		
5	1	1	-0	29.0000	35.0000	-0.0000	-0.0000	238.0000	241.0000	-0	-0	-0	-0	-0	-0		
6	1	1	-0	35.0000	34.0000	-0.0000	-0.0000	238.0000	241.0000	-0	-0	-0	-0	-0	-0		
7	1	1	-0	34.0000	34.0000	-0.0000	-0.0000	235.0000	238.0000	-0	-0	-0	-0	-0	-0		
8	1	1	-0	34.0000	60.0000	-0.0000	-0.0000	235.0000	252.0000	-0	-0	-0	-0	-0	1		
9	1	1	-0	34.3313	60.0000	-0.0000	-0.0000	235.0000	235.0000	-0	-0	-0	-0	-0	-0		
10	1	3	-0	34.3313	60.0000	-0.0000	-0.0000	199.6637	224.0000	-0	-0	-0	-0	-0	-0		
11	1	1	-0	.1000	60.0000	-0.0000	-0.0000	150.0000	199.6637	-0	-0	-0	-0	-0	-0		
12	1	1	-0	.1000	60.0000	-0.0000	-0.0000	0.0000	150.0000	-0	-0	-0	-0	-0	-0		
13	4	2	-0	15.0000	15.0000	-0.0000	-0.0000	224.0000	244.0000	-0	-0	-0	-0	-0	3		
14	4	2	-0	15.0000	22.0000	-0.0000	-0.0000	224.0000	244.0000	-0	-0	-0	-0	-0	-0		
15	5	2	-0	22.0000	29.0000	-0.0000	-0.0000	224.0000	241.0000	-0	-0	-0	-0	-0	-0		
16	5	2	-0	29.0000	35.0000	-0.0000	-0.0000	224.0000	238.0000	-0	-0	-0	-0	-0	-0		
17	6	2	-0	35.0000	34.0000	-0.0000	-0.0000	224.0000	235.0000	-0	-0	-0	-0	-0	-0		
18	7	2	-0	34.0000	34.3313	-0.0000	-0.0000	224.0000	235.0000	-0	-0	-0	-0	-0	-0		
19	2	3	1	.1000	34.0000	-0.0000	-0.0000	200.1112	224.0000	-0	-0	-0	-0	-0	-0		
20	2	4	1	1.000	22.0000	-0.0000	-0.0000	200.0625	200.1112	-0	-0	-0	-0	-0	-0		
21	3	4	2	22.0000	34.0000	-0.0000	-0.0000	200.0625	200.1112	-0	-0	-0	-0	-0	-0		
22	3	4	2	.1000	34.0000	-0.0000	-0.0000	200.0000	200.0625	-0	-0	-0	-0	-0	-0		
23	8	3	-0	.1000	38.3313	-0.0000	-0.0000	199.6637	200.0000	-0	-0	-0	-0	-0	-0		
24	8	3	-0	34.0000	34.3313	-0.0000	-0.0000	200.0000	224.0000	-0	-0	-0	-0	-0	-0		

MATERIAL DESCRIPTION DATA

CONDUCTIVITY AS A FUNCTION OF TEMPERATURE.

MATERIAL NUMBR	MATERIAL NAME	NUMBR	TEMPERATURE K
1	SOTL	1	0.
2	SALCAKF	1	0.
3	SLUDGE	1	0.
4	ATR 1	1	0.
5	ATR 2	1	0.
6	ATR 3	1	0.
7	GAP	1	0.
8	STEEL	1	0.

HEAT GENERATION FUNCTION DATA

1	-0	1	-0
2	-0	2	-0

INITIAL TEMPERATURE FUNCTION DATA

1	3	-0	-0
2	4	-0	-0
3	5	-0	-0
4	6	-0	-0

GENERAL POSITION DEPENDENT FUNCTION COEFFICIENTS

1	1.00000E-01	0.	0.	0.	0.	0.	0.
2	1.00000E+01	0.	0.	0.	0.	0.	0.
3	1.00000E+02	0.	0.	0.	0.	0.	0.
4	1.50000E+02	0.	0.	0.	0.	0.	0.
5	2.00000E+02	0.	0.	0.	0.	0.	0.
6	2.50000E+02	0.	0.	0.	0.	0.	0.

RESULTS FROM STEADY STATE CALCULATIONS
TIME = -0.0
ITERATIONS COMPLETED = 0

LATTICE POINT TEMPERATURES					LATTICE POINT TEMPERATURES					LATTICE POINT TEMPERATURES					LATTICE POINT TEMPERATURES								
POINT NO.	INDICES				POINT TEMPERAT. (QLTY)	POINT NO.	INDICES				POINT TEMPERAT. (QLTY)	POINT NO.	INDICES				POINT TEMPERAT. (QLTY)	POINT NO.	INDICES				POINT TEMPERAT. (QLTY)
1	1	1	1	1	100.000(****)	51	7	1	5	207.130(****)	101	2	1	10	200.000(****)	151	8	1	14	100.000(****)			
2	2	1	1	1	100.000(****)	52	8	1	5	200.000(****)	102	3	1	10	200.000(****)	152	9	1	14	100.000(****)			
3	3	1	1	1	100.000(****)	53	9	1	5	200.000(****)	103	4	1	10	200.000(****)	153	10	1	14	100.000(****)			
4	4	1	1	1	100.000(****)	54	10	1	5	200.000(****)	104	5	1	10	200.000(****)	154	11	1	14	100.000(****)			
5	5	1	1	1	100.000(****)	55	11	1	5	200.000(****)	105	6	1	10	200.000(****)	155	1	1	15	150.000(****)			
6	6	1	1	1	100.000(****)	56	1	1	6	250.000(****)	106	7	1	10	200.000(****)	156	2	1	15	150.000(****)			
7	7	1	1	1	100.000(****)	57	2	1	6	250.000(****)	107	8	1	10	200.000(****)	157	3	1	15	150.000(****)			
8	8	1	1	1	100.000(****)	58	3	1	6	250.000(****)	108	9	1	10	200.000(****)	158	4	1	15	136.506(****)			
9	9	1	1	1	100.000(****)	59	4	1	6	250.000(****)	109	10	1	10	200.000(****)	159	5	1	15	112.759(****)			
10	10	1	1	1	100.000(****)	60	5	1	6	250.000(****)	110	11	1	10	200.000(****)	160	6	1	15	100.000(****)			
11	11	1	1	1	100.000(****)	61	6	1	6	250.000(****)	111	1	1	11	176.029(****)	161	7	1	15	100.000(****)			
12	1	1	2	1	114.205(****)	62	7	1	6	244.928(****)	112	2	1	11	176.029(****)	162	8	1	15	100.000(****)			
13	2	1	2	1	114.205(****)	63	8	1	6	200.000(****)	113	3	1	11	176.029(****)	163	9	1	15	100.000(****)			
14	3	1	2	1	114.205(****)	64	9	1	6	200.000(****)	114	4	1	11	176.029(****)	164	10	1	15	100.000(****)			
15	4	1	2	1	114.205(****)	65	10	1	6	200.000(****)	115	5	1	11	176.029(****)	165	11	1	15	100.000(****)			
16	5	1	2	1	114.205(****)	66	11	1	6	200.000(****)	116	6	1	11	176.029(****)	166	1	1	16	113.636(****)			
17	6	1	2	1	114.205(****)	67	1	1	7	200.404(****)	117	7	1	11	176.029(****)	167	2	1	16	113.636(****)			
18	7	1	2	1	114.205(****)	68	2	1	7	200.404(****)	118	8	1	11	153.062(****)	168	3	1	16	113.636(****)			
19	8	1	2	1	114.205(****)	69	3	1	7	200.404(****)	119	9	1	11	152.058(****)	169	4	1	16	106.276(****)			
20	9	1	2	1	114.205(****)	70	4	1	7	200.404(****)	120	10	1	11	152.058(****)	170	5	1	16	100.000(****)			
21	10	1	2	1	114.205(****)	71	5	1	7	200.404(****)	121	11	1	11	152.058(****)	171	6	1	16	100.000(****)			
22	11	1	2	1	114.205(****)	72	6	1	7	200.404(****)	122	1	1	12	150.000(****)	172	7	1	16	100.000(****)			
23	1	1	3	1	200.000(****)	73	7	1	7	200.363(****)	123	2	1	12	150.000(****)	173	8	1	16	100.000(****)			
24	2	1	3	1	200.000(****)	74	8	1	7	200.000(****)	124	3	1	12	150.000(****)	174	9	1	16	100.000(****)			
25	3	1	3	1	200.000(****)	75	9	1	7	200.000(****)	125	4	1	12	150.000(****)	175	10	1	16	100.000(****)			
26	4	1	3	1	200.000(****)	76	10	1	7	200.000(****)	126	5	1	12	150.000(****)	176	11	1	16	100.000(****)			
27	5	1	3	1	200.000(****)	77	11	1	7	200.000(****)	127	6	1	12	150.000(****)	177	1	1	17	100.000(****)			
28	6	1	3	1	200.000(****)	78	1	1	8	200.000(****)	128	7	1	12	150.000(****)	178	2	1	17	100.000(****)			
29	7	1	3	1	200.000(****)	79	2	1	8	200.000(****)	129	8	1	12	102.094(****)	179	3	1	17	100.000(****)			
30	8	1	3	1	200.000(****)	80	3	1	8	200.000(****)	130	9	1	12	100.000(****)	180	4	1	17	100.000(****)			
31	9	1	3	1	200.000(****)	81	4	1	8	200.000(****)	131	10	1	12	100.000(****)	181	5	1	17	100.000(****)			
32	10	1	3	1	200.000(****)	82	5	1	8	200.000(****)	132	11	1	12	100.000(****)	182	6	1	17	100.000(****)			
33	11	1	3	1	200.000(****)	83	6	1	8	200.000(****)	133	1	1	13	150.000(****)	183	7	1	17	100.000(****)			
34	1	1	4	1	200.000(****)	84	7	1	8	200.000(****)	134	2	1	13	150.000(****)	184	8	1	17	100.000(****)			
35	2	1	4	1	200.000(****)	85	8	1	8	200.000(****)	135	3	1	13	150.000(****)	185	9	1	17	100.000(****)			
36	3	1	4	1	200.000(****)	86	9	1	8	200.000(****)	136	4	1	13	150.000(****)	186	10	1	17	100.000(****)			
37	4	1	4	1	200.000(****)	87	10	1	8	200.000(****)	137	5	1	13	150.000(****)	187	11	1	17	100.000(****)			
38	5	1	4	1	200.000(****)	88	11	1	8	200.000(****)	138	6	1	13	143.860(****)								
39	6	1	4	1	200.000(****)	89	1	1	9	200.000(****)	139	7	1	13	132.753(****)								
40	7	1	4	1	200.000(****)	90	2	1	9	200.000(****)	140	8	1	13	101.755(****)								
41	8	1	4	1	200.000(****)	91	3	1	9	200.000(****)	141	9	1	13	100.000(****)								
42	9	1	4	1	200.000(****)	92	4	1	9	200.000(****)	142	10	1	13	100.000(****)								
43	10	1	4	1	200.000(****)	93	5	1	9	200.000(****)	143	11	1	13	100.000(****)								
44	11	1	4	1	200.000(****)	94	6	1	9	200.000(****)	144	1	1	14	150.000(****)								
45	1	1	5	1	207.936(****)	95	7	1	9	200.000(****)	145	2	1	14	150.000(****)								
46	2	1	5	1	207.936(****)	96	8	1	9	200.000(****)	146	3	1	14	150.000(****)								
47	3	1	5	1	207.936(****)	97	9	1	9	200.000(****)	147	4	1	14	150.000(****)								
48	4	1	5	1	207.936(****)	98	10	1	9	200.000(****)	148	5	1	14	137.759(****)								
49	5	1	5	1	207.936(****)	99	11	1	9	200.000(****)	149	6	1	14	116.702(****)								
50	6	1	5	1	207.936(****)	100	1	1	10	200.000(****)	150	7	1	14	100.000(****)								

TEMPERATURES ON NUMBERED BOUNDARIES

BOUNDARY NUMBER	TEMPERATURE
1	55.000000
2	-0.000000
3	60.000000

ELAPSED CPU TIME IS 1.27 SECONDS

NUMBER OF ITERATIONS	CONVERGENCE	NODE	TEMPERATURE	EXTRAPOLATION FACTOR
5	-2.60773E-01	114	9.90878E+01	-4.63544E-01
10	2.22724E-01	23	1.87807E+02	-2.49497E+00
15	1.22882E-01	90	1.93728E+02	3.56247E+00
20	6.94773E-02	100	1.62790E+02	4.94182E+00
25	4.87742E-02	100	1.64690E+02	-5.80743E-01
30	4.20666E-02	100	1.70004E+02	-2.26677E+00
35	2.47202E-02	100	1.70867E+02	-6.42400E-01
40	1.97103E-02	100	1.72801E+02	-7.11345E-01
45	1.24551E-02	89	2.11665E+02	-1.80947E+00
50	3.46082E-03	78	2.37767E+02	-4.65918E+00
55	2.86091E-03	100	1.76225E+02	-5.77651E+00
60	1.90513E-03	78	2.40660E+02	1.54114E+00
65	1.59986E-03	34	2.53827E+02	-9.24595E+00
70	1.30755E-03	34	2.55118E+02	-2.27371E+02
75	1.24470E-03	44	1.83573E+02	-2.47644E+03
80	1.18518E-03	44	1.84681E+02	3.78500E+02
85	1.12362E-03	44	1.85739E+02	2.62658E+02
90	1.06160E-03	44	1.86747E+02	1.38947E+02
95	1.00495E-03	44	1.87707E+02	1.20811E+02
100	9.57332E-04	44	1.88625E+02	1.11592E+02
105	9.16395E-04	12	1.77013E+02	1.31644E+02
EXTRAPOLATION				
110	-7.81478E-04	89	2.34530E+02	1.77948E+00
115	-2.53506E-04	89	2.34617E+02	-3.02311E-01
120	-1.63566E-04	100	1.93174E+02	-4.69303E-01
125	1.81532E-04	100	1.93184E+02	-3.69911E-01
130	-1.32024E-04	89	2.34563E+02	-6.29020E-01
135	-5.53966E-05	90	2.33888E+02	-4.83507E-01
140	-3.51340E-05	34	2.79020E+02	-4.58413E-01
145	-4.35657E-05	78	2.63368E+02	-2.29357E+01
150	-2.31171E-05	34	2.79000E+02	-2.75128E+00
155	-1.69568E-05	34	2.78980E+02	-1.17372E+01
160	-1.24481E-05	34	2.78977E+02	-1.25300E+01
165	-1.11586E-05	100	1.93074E+02	-1.32841E+01
BETA REDUCED TO 1.800				

APPENDIX D

VAPOR SPACE MODEL

APPENDIX D

VAPOR SPACE MODEL

The vapor space model was not a critical part of the overall heat transfer analysis of the Hanford waste storage tanks. From preliminary calculations, it is found that the vapor space accounts for about 1% of the total thermal resistance between the sludge and the surface of the ground. However, a relatively accurate and representative model is deemed desirable for several reasons. The vapor space model does influence temperatures and gradients in the area and these values should be accurate for structural analysis of the dome. The model should demonstrate the effects of radial heat transfer from the vapor space. Finally, the model should have the capability to demonstrate air cooling. Air cooling can be of significant help in reducing temperatures if enough air is put through the space.

For this work, several assumptions are made on the actual heat transfer mechanisms in the vapor space. It is assumed that the air flow is negligible, and the air temperature goes to steady state with the rest of the tank. This assumption is conservative, but it does approach reality. The air flow will usually be less than 50 cfm and, at times, it will be zero. The remaining mechanisms for heat transfer in the vapor space are natural convection and radiation.

The natural convection heat transfer coefficient was calculated to be about $0.06 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$.

$$h_{NC} = \frac{K}{L} (0.54)(Gr_L Pr)^{1/4} \quad (D-1)$$

evaluated at 150°F , $h_{NC} = 0.11 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$

$$\frac{1}{h_{eq}} = \frac{1}{h_{NC}} + \frac{1}{h_{NC \text{ bottom}}}, \text{ assuming } h_{NC} \text{ is the same for top and bottom}$$

$$h_{eq} = 0.06 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$$

The radiation heat transfer coefficient was calculated for an average vapor temperature of 150°F and an emissivity - shape factor product equal to 0.70.

$$h_r = \epsilon F_{1-2} \sigma (T_2^3 + T_2^2 T_1 + T_2 T_1^2 + T_1^3)^{1/4} \quad (D-2)$$

at $T_1 = 150^\circ\text{F}$ and $T_2 - T_1 = 1^\circ - 10^\circ\text{F}$

$$h_r = 1.09 - 1.11 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$$

The main mechanism of heat transfer is seen to be radiation. The final value used for the heat transfer coefficient was, $h = 1.0 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$

The first model of the vapor space used the radiation surface-to-surface boundary condition which is a special feature found in HEATING4. This boundary allows direct heat transfer between two parallel surfaces, across a region or gap. The radiation heat transfer coefficient is a function of temperature. Due to problems, this model was replaced by a constant heat transfer coefficient equal to $1.0 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$. This model gives good results; however, it is slow to converge and it does not account for radial heat transfer from the vapor space.

Two other models were tried, both of which allowed for radial heat transfer. The first model replaces the air with a material with a high conductivity, $k = 200 \text{ Btu/hr-ft}^2\text{-}^\circ\text{F}$, and uses surface-to-surface boundaries across the gaps between the salt cake and vapor and the soil and vapor in the radial direction [see Figure D-1(a)]. This did improve the convergence time slightly. The second model replaces the air with materials such that their value of k/X equaled the value of the heat transfer coefficient [see Figure D-1(b)]. This model converges much faster.

All the models provided temperatures with a maximum deviation of 4° to 8°F between each other. This shows that the vapor model is not critical in the overall modeling of the system, and that the selection of the model used should not depend entirely on its accuracy. The second two models showed

FIGURE D-1. Schematic Diagrams of Two Vapor Space Models

FIGURE D-2. Temperature Distribution in the Soil Next to the Vapor Space for the 2-D Model Using an Annual Sludge Pile

that the net radial heat transfer is small (see Figure D-2). Modeling the radial heat transfer does become important when evaluating the temperature gradients in the wall and soil next to the vapor space.

The model selected for use in this analysis was the one using the materials with the value of k/X equal to the heat transfer coefficient. This model is slightly conservative to the others and is the fastest converging. The speed of convergence becomes very important when running models with many nodes, such as the 360° model.

REFERENCES

1. D. W. McLenegan, Temperature Transients in Underground Tanks Storing Nuclear Process Residues, HW-56821, General Electric Company, Richland, Washington, July 28, 1958.
2. E. Doud and H. W. Stivers, Limitations for Existing Storage Tanks for Radioactive Wastes from Separations Plants, HW-59919, General Electric Company, Richland, Washington, October 22, 1959.
3. M. W. Cook, The Design and Application of a Heat Transfer Analogue for Radially Symmetric Problems, HW-47088, General Electric Company, Richland, Washington, January 30, 1957.
4. G. Jansen, Jr., W. E. Willingham, and W. V. DeMier, Buried Radioactive Waste Storage Tank Temperatures and Soil Temperatures Near Leaks, BNWL-181, February 1966.
5. W. E. Willingham and G. Jansen, Jr., Heat Transfer from Solidified Wastes in Underground Storage Tanks, BNWL-262, October 1966.
6. Handbook of the American Society of Heating, Ventilation, and Air Conditioning.
7. W. D. Turner and M. Siman-Tov, HEATING 3--An IBM 360 Heat Conduction Program, ORNL-TM-3208, February 1971.

DISTRIBUTION

No. of
Copies

OFFSITE

1 ERDA Chicago Patent Group
 9800 South Cass Avenue
 Argonne, IL 60439
 A. A. Churm

27 ERDA Technical Information Center

ONSITE

15 Atlantic Richfield Hanford Company
 L. Fong

1 ERDA Richland Operations
 P. G. Holsted

26 Battelle-Northwest
 H. C. Burkholder
 C. C. Chapman
 J. H. Jarrett
 D. H. Lester
 J. L. McElroy
 P. J. Pelto (3)
 S. C. Slate (10)
 D. L. Williams
 Technical Information Files (5)
 Technical Publications (2)