DOE/PC/90304--T2

DE92 018879

THE EFFECT OF SELECTIVE ABSORPTION ON COAL CONVERSION

Report for the period of
October - December 1991

John W. Larsen, Lazarin Lazarov and Jewel Amui

Department of Chemistry
Lehigh University

May 1992

RECEIVED
AUG 06 1992

PREPARED FOR THE UNITED STATES DEPARTMENT OF ENERGY
Under Contract ~~DE-PS22-90PC90282~~

DE-FG22-90PC90304

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

JUN 18 1952

OBJECTIVES AND SCOPE OF WORK

Objectives

1. To determine the importance of the presence of added hydrogen donor compounds within the coal in the first stage of direct liquefaction processes.
2. To determine the composition of the solvent absorbed by and present within the coal in the first stage of direct coal liquefaction.

Scope of Work

1. Importance of Hydrogen Donors in the Coal

Prepare highly pure 2-t-butyltetralin. Study the conversion of Argonne coals in tetralin and 2-t-butyltetralin and compare the following: conversion to soluble products, product molecular weight distributions, and product structure. Hydrogen donated by both solvents will be measured by gas chromatography and the same technique will be used to establish the amount of dealkylation of 2-t-butyltetralin. Reactions will be run at several temperatures for varying times.

2. Selective Recycle Solvent Absorption

Argonne coals will be exposed to recycle solvents at several elevated temperatures and the non-absorbed portion of the solvent will be separated by filtration. The composition of the whole oil and non-absorbed portion will be analyzed spectroscopically and chromatographically and compared to determine the composition of the recycle oil dissolved in the coal.

PART I. The Wilsonville Interstage Oil Absorption by Argonne Coals

The Absorption of the Wilsonville Interstage Oil (see Report #3) by coals of the entire Argonne series was measured at 150°C and the data are presented in Figure 1.

Attempt at Preparative HPLC of the Recycle Oil

In Report #2, HPLC conditions (a normal-phase separation on Nucleosil NO₂ with gradient elution system) which provide a good fingerprinting of the coal oils were described. To obtain information about the origin of the only material absorbed by the coal (see Figures 7 and 8 in Report #2) an attempt at preparative separation and analysis by Mass Spectrometry was made. A higher concentration (20 mg/mL in Fisher grade chloroform) sample was separated and fractions were collected. The material eluting at the proper time (capacity factors 11.1 - 11.5), was analysed by Plasma Desorption Mass Spectrometry. This technique utilizes a radioactive ²⁵²Cf source to volatilize and ionize molecules without causing fragmentation and is an effective method for determining molecular weights of biological molecules, having molecular weights up to 25000 amu.¹ A Bioion 20 time-of-flight spectrometer was used employing 10 kV acceleration voltage. The sample was prepared by direct application of the solution onto mylar foil. Figure 2 presents the normalized and computer smoothed spectrum. If the mylar blank is taken into account, one can conclude that the chromatographic fraction studies is enriched in a few compounds having molecular weights in the range 115 - 480 amu.

PART 2: Hydrogen Transfer from Tetralin and 2-t-Butyltetralin

In the present work, 100% pure 2-t-butyl tetralin was synthesized by a procedure similar to that of Whitmore et al.³ The purity was confirmed by G.C. and ¹H nmr. 2-t-butyl-naphthalene was prepared by refluxing 2-t-butyltetralin with excess sulfur (2:3 mole ratio) at 215°C for twenty hours. This reaction proceeded quantitatively to 2-t-butylnaphthalene.

With cis-decalin as the internal standard, standard solutions of tetralin, naphthalene, 2-t-butyltetralin, 2-t-butylnaphthalene and cis-decalin were made and used to determine G.C. response factors. These data are necessary for accurate G.C. measurements of the liquefaction products.

Parallel liquefaction reactions of dried Ill#6 coal in tetralin and 2-t-butyltetralin will be run for 10 minutes at temperatures from 350- 450°C. The liquefaction experiments will be carried out using a 2:1 ratio of solvent to coal in parallel runs, identical conditions and dry nitrogen atmosphere. The separation of coal from the solvent and reaction products will be done by extraction with pyridine. The overall conversion will be determined by pyridine extractability in comparison with the non-solvent reacted coal to determine the change in percent pyridine extractibles and their molecular weight distribution.

REFERENCES

1. Cotter, R. J.; Anal. Chem., 1988, 60, 781A
2. Matsunaga, A.; Anal. Chem., 1983, 55, 1375
3. Whitmore, F.C.; James, W.H.; JACS 65, 1943 2088 -2090

LIST OF FIGURES:

FIG.1. Absorption of Wilsonville Interstage Oil by Argonne Coals at 150°C (2 hrs. Exposure Time; Solvent/Coal = 2.0);

Coals: Beulah-Zap (Lignite, 73%C,daf); Wyodak-Anderson (Subbituminous, 75%C,daf); Illinois #6 (High Vol.Bituminous, 78%C,daf); Pittsburgh #8 (High Vol.Bituminous, 83%C,daf); Upper-Freeport (Medium Vol.Bituminous, 86%C,daf); Pocahontas #3 (Low Vol.Bituminous, 91%C,daf);

FIG.2. Plasma Desorption (10 kV) Mass Spectrum of the Chromatographic Cut - Distribution of the Smoothed Number Intensities;

FIG.3. HPLC of Model Mixture of Compounds (Gradient Elution of 4 vol.%/min from Hexane to Chloroform - see Report #2); Flow: 1 mL/min;

Figure 1

Figure 2

END

**DATE
FILMED**

9 / 24 / 92