ORNL/ENG/TM-40

**OAK RIDGE
NATIONAL
LABORATORY**

**DYNAMIC IMPACT ANALYSIS
OF THE M1 105MM PROJECTILE**

MARTIN MARIETTA

J. C. Walls
D. S. Webb

**MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY**

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Central Engineering Services

DYNAMIC IMPACT ANALYSIS OF THE M1 105MM PROJECTILE

J. C. Walls
D. S. Webb

June 1993

Research sponsored by the Packaging Division, Armament
Research, Development and Engineering Center (ARDEC),
Picatinny Arsenal under Interagency Agreement 1892-A078-A1
between the U.S. Department of Energy and ARDEC.

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831-6285
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under contract DE-AC05-84OR21400

MASTER

EB

CONTENTS

	<u>Page</u>
LIST OF FIGURES	v
ABSTRACT	vii
INTRODUCTION AND BACKGROUND	1
DESCRIPTION OF THE PACKAGE CONFIGURATIONS ANALYZED	1
FINITE ELEMENT MODELS	2
IMPACT CONDITIONS	2
ANALYSIS RESULTS	3
BARE PROJECTILE	3
Bare Projectile Impacting Flat onto Its Nose	3
Bare Projectile Impacting Flat onto Its Base	4
Bare Projectile Impacting Flat onto Its Side	4
Bare Projectile Impacting at 45° Angle on Its Nose	4
PROJECTILE IN A FIBER TUBE	4
PROJECTILES INSIDE A WOODEN SHIPPING CRATE	5
DISCUSSION OF RESULTS	5
SUMMARY AND CONCLUSIONS	6
REFERENCES	7

LIST OF FIGURES

<u>No.</u>	<u>Title</u>	<u>Page</u>
1	Typical M1 105MM Howitzer artillery shell	8
2	Projectile section and finite element model showing general location of high residual tensile stresses	9
3	Major model components	10
4	Model components for the fiber ammunition tube drop cases	11
5	Model components for the fiber ammunition tube drop cases	12
6	Cutaway view of the wooden shipping crate model	13
7	Rigid body acceleration for bare projectile dropped flat on nose	14
8	Projectile velocity, bare projectile dropped flat on nose	15
9	Kinetic energy, bare projectile dropped flat on nose	16
10	Elements in nose region of bare projectile model	17
11	Time history of maximum principal stress in elements 537 and 538	18
12	Time history of maximum principal stress in elements 505 and 506	19
13	Time history of maximum principal stress in elements 473 and 474	20
14	Projectile acceleration, bare projectile dropped flat on base	21
15	Element numbers in nose region of model	22
16	Time history of maximum principal stress in elements 521 and 522	23
17	Time history of maximum principal stress in elements 489 and 490	24
18	Time history of maximum principal stress in elements 457 and 458	25
19	Projectile acceleration, bare projectile dropped flat on side	26
20	Kinetic energy vs time for bare projectile impacting at 45°	27
21	Element numbers in nose region of projectile for 45° impact case	28

<u>No.</u>	<u>Title</u>	<u>Page</u>
22	Time history of maximum principal stress for elements 670–672	29
23	Time history of maximum principal stress for elements 718–720	30
24	Time history of maximum principal stress for elements 667–669	31
25	Projectile acceleration, projectile in fiber tube dropped flat on projectile end	32
26	Peak axial stress, projectile in fiber tube dropped flat on projectile end	33
27	Projectile acceleration, projectile in fiber tube dropped flat on cartridge end	34
28	Peak von Mises stress, projectile in fiber tube dropped flat on cartridge end	35
29	Projectile acceleration, projectile in fiber tube dropped flat on side	36
30	Peak von Mises stress, projectile in fiber tube dropped flat on side	37
31	Projectile acceleration, projectile in wooden shipping crate dropped flat on bottom	38
32	Peak von Mises stress, projectile in wooden shipping crate dropped flat on bottom	39
33	Projectile acceleration, projectile in wooden shipping crate dropped flat on projectile end	40
34	Peak von Mises stress, projectile in wooden shipping crate dropped flat on projectile end	41

ABSTRACT

Evaluation of the effects of "rough-handling"-induced stresses in the nose region of a 105mm artillery projectile was performed to determine if these stresses could have contributed to the premature explosion of a projectile during a Desert Shield training mission of the 101st Army Airborne in Saudi Arabia. The rough-handling evaluations were simulated by dynamic impact analysis. It was concluded that the combined residual stress and dynamic impact-induced stress would not be of sufficient magnitude to cause cracking of the projectile in the nose region.

INTRODUCTION AND BACKGROUND

An in-bore premature explosion of an M1 105mm Howitzer artillery projectile (Fig. 1) was reported to have occurred during a Desert Shield training mission of the 101st Army Airborne in Saudi Arabia. One possible reason for this failure was thought to be nose cracks in the projectile resulting from either rough handling, high residual stresses, and/or manufacturing defects.¹ Figure 2 shows a typical 105mm projectile as well as the location of potential nose cracks.

Results of tensile tests performed on material from the nose area of two projectile bodies from the malfunctioned round lot¹ show that the material strength averaged about 103 ksi, which is well above the required 65-ksi value. This high strength may be an indication that a significant stress relief was not performed.¹ Also, high tensile residual stresses were detected in the nose area of M1 projectiles from the malfunctioned round lot. The maximum tensile residual stresses are located on the inside wall surface (see Fig. 2), are oriented in the hoop direction, and are on the order of one-third the yield stress.¹ The magnitude of these residual stresses would also indicate that the shells were not properly stress relieved and would be readily susceptible to the generation of longitudinal cracks when subjected to rough handling or excessive acceleration loads. If these conditions occur at extremely low temperatures, brittle fracture may become a consideration.

Considering the results of the residual stress and material tensile strength determinations, the objective of this report is to evaluate the effects of "rough-handling"-induced stresses and determine if these stresses could have contributed to the projectile failure.

The rough-handling evaluations were simulated by dynamic impact analysis. Finite element models were formulated for the projectile, cartridge case, fiber tube assembly, and the wooden shipping crate in which the projectiles are shipped. These models were then used to simulate drops from a 7-ft height onto an unyielding surface for various orientations and package configurations. The resulting accelerations and stresses were then analyzed to determine if the drop scenarios could have induced cracks and influenced premature failure of the projectile.

Actual drop testing of some of the projectile configurations were conducted at Picatinny Arsenal. However, limited accelerometer data were available for comparison with the dynamic analysis results reported herein. In this regard, a secondary objective of this report was to verify that computer code predictive methodologies could be a cost-effective alternative to physical testing of armament packaging.

DESCRIPTION OF THE PACKAGE CONFIGURATIONS ANALYZED

The M1 105mm projectile, along with other components that comprise the artillery shell, is shipped inside a wooden shipping crate. The shipping crate contains components for two complete artillery rounds. Each individual projectile and cartridge case within the wooden crate is enclosed inside a fiber tube along with protector cones, washers, and end caps. The details of the components of the M1 105mm artillery round, the wooden box, and all the other items contained in the box for shipping are defined by the drawings and

specifications obtained from Packaging Division, Armament Research, Development and Engineering Center (ARDEC), Picatinny Arsenal, and are shown in Table 1.

Table 1. Drawings and specifications used to define package configurations

Drawing/specification	Description
10535878	Projectile body
8595386	Cartridge case
9258026	Fiber ammunition container
9258027	Fiber ammunition container
9271050	Fiber ammunition container
Specification MIL-C-2439E	Fiber ammunition container
Specification MIL-B-2427G	Wooden shipping crate

FINITE ELEMENT MODELS

Finite element models were generated to simulate the various components of the M1 105mm shell and its packaged configuration for the dynamic impact analyses. All models were formulated and analyzed with the VEC/DYNA3D,² INGRID,³ and TAURUS⁴ finite element computer codes. The codes reside on a Silicon Graphics 4D/35 engineering workstation computer. INGRID is a preprocessor code that was used to formulate the various models and components. Figures 3 through 6 show the various components and how they were assembled for the dynamic analyses.

Three different projectile/package models were analyzed. The first configuration analyzed was the bare projectile without the fuse or fuse plug. The second configuration consisted of a projectile contained within the fiber ammunition tube. An exploded view of the model components can be seen in Fig. 4. The third package configuration model consisted of the complete wooden shipping crate with two projectiles and all the packaged components. An exploded view of this model is shown in Fig. 5. A cutaway view of the complete wooden shipping crate model is shown in Fig. 6.

Material properties used for the projectile were a modulus of elasticity of 29×10^6 psi and a yield strength of 110,000 psi.⁵ Material properties for some of the components in the wooden shipping crate were estimated. The properties of the wooden box were assumed to be generic plywood. Similarly, the properties of the fiber ammunition tube material were assumed.

IMPACT CONDITIONS

The drop height used for all analyses was taken as 7 ft. Also, all impacts were assumed to be onto a flat, unyielding surface. The assumption of an unyielding surface will most

likely cause accelerations and stress magnitudes in the projectile to be conservatively predicted because actual surfaces are more flexible, which tends to lower stresses in the projectile.

The bare projectile model impact response was examined for four different orientations of the projectile at impact. These were (1) projectile impacting flat onto its nose, (2) projectile impacting flat onto its base, (3) projectile impacting flat onto its side, and (4) projectile impacting at an angle of 45° to the surface onto its nose.

The projectile in its fiber shipping tube model was analyzed for three different impact orientations. These were (1) tube impacting flat onto the projectile end of the model, (2) tube impacting flat onto the cartridge end of the model, and (3) tube impacting flat onto its side.

The complete wooden shipping crate model was analyzed for two different impact orientations: flat onto the crate bottom and flat onto the projectile end of the crate.

ANALYSIS RESULTS

As previously mentioned, three different projectile/package models were analyzed: (1) a bare projectile, (2) a projectile in a fiber tube, and (3) a complete wooden shipping crate with two projectiles. Results of the analyses are given in the following paragraphs.

BARE PROJECTILE

The bare projectile model was analyzed for four different orientations of the projectile at impact. There were (1) projectile impacting flat onto its nose, (2) projectile impacting flat onto its base, (3) projectile impacting flat onto its side, and (4) projectile impacting at an angle of 45° to the surface onto its nose. Results of the analyses are given below.

Bare Projectile Impacting Flat onto Its Nose

The dynamic impact of the bare projectile model impacting the rigid, unyielding surface flat onto its nose was analyzed with the VEC/DYNA3D computer code. Accelerations, velocities, kinetic energy, stresses, strains, and deformations can be obtained for the model at any time in the impact event and examined with the postprocessor, TAURUS. For this impact simulation, for example, Figs. 7 to 9 show the acceleration, velocity, and kinetic energy vs time. The plot of kinetic energy is often used to verify that the impact event is being simulated correctly. A smooth kinetic energy curve usually indicates that energy is being expended without computational difficulties in the finite element model.

The large values of acceleration indicated by Fig. 7 occur at times early in the impact event and are indicative of the relatively rigid projectile impacting the rigid, unyielding surface. It should be noted that the assumption of the rigid, unyielding impact surface is quite conservative; and it is therefore likely that accelerations, stresses, etc., will be overestimated for this analysis.

Since tensile stresses in the nose region of the projectile are of interest, a time history of maximum principal stresses was recorded for elements in this region. Figure 10 indicates the location of elements in the nose region of the bare projectile. Figures 11 to 13 show time

histories of the maximum principal stress in selected elements in the nose region of the projectile. From these plots it is seen that peak stresses of ~20,000 psi are indicated.

Bare Projectile Impacting Flat onto Its Base

The projectile acceleration vs time for the base impact scenario is shown in Fig. 14. As mentioned previously, the combination of a relatively rigid projectile model impacting an unyielding surface creates a sharply defined maximum acceleration at impact.

As before, tensile stresses in the nose region of the projectile are of concern. Figure 15 shows the element numbering scheme for this impact model. Maximum principal stresses vs time are plotted in Figs. 16 to 18 for typical elements in the nose region of the projectile. For this impact scenario, the maximum values of stress are of the order of 31,000 psi.

Bare Projectile Impacting Flat onto Its Side

The projectile acceleration vs time for the side impact event is recorded in Fig. 19. It is seen that the acceleration levels are much less than those obtained from the nose and base impact events. The lower level of acceleration is probably a result of greater flexibility of the projectile model for loads acting on the sides of the projectile. Also, for this case, stress levels in the nose area of the projectile were examined and found to be of the order of 10,000 psi or less.

Bare Projectile Impacting at 45° Angle on Its Nose

The scenario of a base projectile impacting the unyielding surface at an angle of 45° on its nose was analyzed. This event is much more complex than the other base projectile impact events and includes a simulation of initial impact and rotation of the projectile until secondary impact occurs. A plot of the kinetic energy dissipation is shown in Fig. 20.

Locations of elements in the nose region of the projectile are indicated in Fig. 21. It is noted that the point of impact occurs on the line of nodes between elements 531 and 576. Maximum principal stresses were examined for several of the elements in the nose region for this impact event. From the stress results plotted in Figs. 22 to 24, it is seen that maximum values approach 50,000 psi.

PROJECTILE IN A FIBER TUBE

Impact simulations of the projectile and cartridge packaged in the fiber ammunition tube were analyzed for three different orientations at surface impact. The orientations were for flat-end impacts at both the projectile and cartridge ends of the tube and for flat impact onto the tube side. As would be expected, maximum accelerations and stresses experienced by the projectile are much less in the fiber tube when compared to results from the bare projectile impact simulations.

Results of the impact analyses are shown in Figs. 25 to 30 for the three different impact orientations. The results for the tube impacting the projectile end are shown in Figs. 25 and 26. Maximum acceleration is 2480 g, and maximum stress in the projectile is <20,000 psi. For impact on the cartridge end, accelerations are quite low (Fig. 27) because of the cushioning effect of the protector cone inside the fiber tube. Also, for this case, stresses in

the nose region of the projectile are generally less than 10,000 psi (Fig. 28). Results of the side impact indicate that maximum accelerations reach 1000 g (Fig. 29), but maximum stresses in the nose area of the projectile are less than 10,000 psi.

PROJECTILES INSIDE A WOODEN SHIPPING CRATE

Impact simulations of a wooden shipping crate containing two fiber ammunition tubes were completed for two different impact orientations: flat on the projectile end of the crate and flat onto the bottom of the crate.

The inclusion of the wooden box in the impact model results in smaller values of acceleration experienced by the projectiles as compared to previous configurations. For the case of a crate dropped flat on its bottom, Fig. 31 indicates that the maximum acceleration is 770 g. Maximum stresses experienced by the projectile in the nose region are less than 10,000 psi, as shown by Fig. 32. Results of the case of crate dropped on its projectile end are shown in Figs. 33 and 34. Maximum accelerations are 355 g, and stresses in the nose regions of the projectile are <10,000 psi.

DISCUSSION OF RESULTS

Dynamic impact simulations were performed on the M1 105mm projectile in a variety of packaged configurations and impact orientations. As might be expected, the maximum accelerations and maximum principal stress levels in the projectile are experienced for the bare projectile impact configuration. Review of results from the bare projectile impact simulations show that maximum principal stress levels in the nose region of the projectile occur for the 45° angle impact orientation of the projectile. For this case, stress values approach 50,000 psi.

As was stated in the introduction, studies have shown that tensile residual stresses of 30,000 to 35,000 psi could exist in the nose region of the projectile. However, it is also indicated that these high residual stresses could exist only if proper stress relieving of the projectile were not performed. Also, when these high residual stresses are present, the material yield strength is 100,000 psi or greater. If the maximum principal stress obtained in the impact scenarios (50,000 psi) is combined with a potential residual stress (35,000 psi), the summation is still less than the material yield stress.

Drop testing of the M1 projectile has been performed.⁶ Results obtained from an accelerometer attached to the base of the M1 projectile were recorded for some impact orientations and packaged configurations. For a bare projectile dropped flat onto its side, a maximum acceleration of 2915 g was recorded from the test. For the bare projectile impact simulation reported herein, a value of 7165 g was indicated. This difference could be attributed to conservative assumptions in the model material data and also to the rigid, unyielding surface assumed for the analysis. Another consideration is the fact that the test accelerometer response time may underestimate sharp acceleration peaks that occur for the bare projectile impact. For the case of a projectile contained in a fiber tube, test accelerations for a flat side impact were measured to be 1744 g, while the analysis indicated a value of 1000 g. Finally, for the wooden shipping crate configuration, test accelerations were 719 g, while analysis results were 770 g. A much better correlation between test accelerations and analysis accelerations is obtained for the shipping crate configuration. This

supports the idea that hardness of both the impacting item and the impacted surface influence accelerations obtained in the dynamic simulation analysis.

SUMMARY AND CONCLUSIONS

Results from the dynamic impact analysis indicate that maximum principal tensile stresses of ~50,000 psi occur in the nose of a bare projectile impacting an unyielding surface at a 45° angle of incidence. If preexisting residual stresses were present, the impact-induced stress would combine to raise the stress levels to ~85,000 psi. Considering that yield strength for the projectile material is greater than 100,000 psi, it is believed that the combined residual stress and dynamic impact-induced stress would not be of sufficient magnitude to cause cracking of the projectile in the nose region.

It is felt that reasonably good comparisons were obtained between limited test data and the analysis, considering the assumptions made in the analysis. Therefore, it is concluded that dynamic impact analyses can be a valuable and cost-effective alternative to physical testing of ammunition and shipping packages.

REFERENCES

1. K. F. Lukens, *Malfunction Investigation of an In-Bore Explosion of an M1, 105MM Projectile - MIF A-2-91*, Report No. MMB-02-92 (Draft), ARDEC, Picatinny Arsenal, N.J., Feb. 7, 1992.
2. John O. Hallquist and Douglas W. Stillman, *VEC/DYNA3D User's Manual (Nonlinear Dynamic Analysis of Structures in Three Dimensions)*, LSTC Report 1018, June 1990.
3. John O. Hallquist and Douglas W. Stillman, *INGRID: A Three-Dimensional Mesh Generator for Modeling Nonlinear Systems*, UCID-10506, Lawrence Livermore Laboratory, July 1985.
4. John O. Hallquist and B. E. Brown, *TAURUS: An Interactive Post-Process for the Analysis Codes NIKE3D, DYNA3D, TACO3D, and GEMINI*, UCID-19392, Rev. 1, Lawrence Livermore Laboratory, May 1984.
5. Personal communication with J. C. Walls, Martin Marietta Energy Systems, Inc., and Tony D'Angelo, Picatinny Packaging Division.
6. Personal communication, J. C. Walls, Martin Marietta Energy Systems, Inc., and Gene Farrell, Picatinny Arsenal, Aug. 10, 1992.

Fig. 1. Typical M1 105MM Howitzer artillery shell.

Fig. 2. Projectile section and finite element model showing general location of high residual tensile stresses.

M1 105MM Projectile Major Model Components

Fiber Ammunition Tube Assembly

Cartridge Case

Wooden Shipping Crate

Projectile and Fuze

Fig. 3. Major model components.

Fig. 4. Model components for the fiber ammunition tube drop cases.

M1 105MM Projectile Complete Model

Fig. 5. Model components for the fiber ammunition tube drop cases.

M1 105MM Package Model.

**Complete model including
Projectile, Cartridge Case,
Fiber Ammunition Tube, and
Wooden Box.**

Cutaway view of model shown.

Fig. 6. Cutaway view of the wooden shipping crate model.

Fig. 7. Rigid body acceleration for bare projectile dropped flat on nose.

Fig. 8. Projectile velocity, bare projectile dropped flat on nose.

Fig. 9. Kinetic energy, bare projectile dropped flat on nose.

Note: Odd numbered elements are located on inside surface of the model.

Fig. 10. Elements in nose region of bare projectile model.

Bare Projectile On Nose 7ft

Fig. 11. Time history of maximum principal stress in elements 537 and 538.

Bare Projectile On Nose 7ft

Fig. 12. Time history of maximum principal stress in elements 505 and 506.

Bare Projectile On Nose 7ft

Fig. 13. Time history of maximum principal stress in elements 473 and 474.

Fig. 14. Projectile acceleration, bare projectile dropped flat on base.

Bare Projectile On Base 7ft

Fig. 15. Element numbers in nose region of model.

Bare Projectile On Base 7ft

Fig. 16. Time history of maximum principal stress in elements 521 and 522.

Bare Projectile On Base 7ft

Fig. 17. Time history of maximum principal stress in elements 489 and 490.

Bare Projectile On Base 7ft

Fig. 18. Time history of maximum principal stress in elements 457 and 458.

Fig. 19. Projectile acceleration, bare projectile dropped flat on side.

Bare Projectile On Nose at 45

Fig. 20. Kinetic energy vs time for bare projectile impacting at 45°.

Bare Projectile On Nose at 45

Note: Impact Occurs at
Line of Nodes
Between Elements
531 and 576

Fig. 21. Element numbers in nose region of projectile for 45° impact case.

Bare Projectile On Nose at 45

Fig. 22. Time history of maximum principal stress for elements 670-672.

Bare Projectile On Nose at 45

Fig. 23. Time history of maximum principal stress for elements 718-720.

Bare Projectile On Nose at 45

Fig. 24. Time history of maximum principal stress for elements 667-669.

Fiber Tube on Projectile End

time = 0.4598E-03

fringes of stress

min = -1.998E+04 in element 374
 max = 1.681E+04 in element 375

fringe levels

-1.130E+04
 -7.964E+03
 -1.587E+03
 4.791E+03
 1.120E+04

Peak Axial Stress in Projectile, Dropped
 in Fiber Ammunition Tube, Flat on
 Projectile End of Tube.

Max Stress 20,000 psi at a
 time of 0.46E-03 sec.

Fig. 26. Peak axial stress, projectile in fiber tube dropped flat on projectile end.

Fig. 27. Projectile acceleration, projectile in fiber tube dropped flat on cartridge end.

Fiber Tube on Cartridge End
 time = 0.74399E-02
 fringes of eff. stress in mm
 min = 3.944E-01 in element 763
 max = 1.246E+04 in element 763

Fringe Levels
 1.835E+03
 4.090E+03
 6.344E+03
 8.598E+03
 1.060E+04

Peak Von Mises Stress In The
 Projectile, Dropped In Fiber
 Ammunition Container, Flat On
 Cartridge End From 7 Feet.

Stress in psi.

Maximum stress of 12,460 psi at
 a time of 0.74E-02 sec.

Fig. 28. Peak von Mises stress, projectile in fiber tube dropped flat on cartridge end.

Fig. 29. Projectile acceleration, projectile in fiber tube dropped flat on side.

Fig. 30. Peak von Mises stress, projectile in fiber tube dropped flat on side.

Fig. 31. Projectile acceleration, projectile in wooden shipping crate dropped flat on bottom.

Projectile, Tube, and Box

time = 0.2385E-02

fringes of eff. stress (psi)

min = 1.228E+03 in element 306
max = 2.350E+04 in element 601

(fringe level)s

5.260E+03
9.024E+03
1.440E+04
1.900E+04
2.350E+04

Peak Von Mises Stress In
Projectile, Dropped In Wooden
Shipping Crate Flat On Bottom
From 7 Feet.

Stress in psi.

Maximum stress 27,550 psi at
a time of 0.238E-02 sec.

Fig. 32. Peak von Mises stress, projectile in wooden shipping crate dropped flat on bottom.

Fig. 33. Projectile acceleration, projectile in wooden shipping crate dropped flat on projectile end.

Projectile, Tube, and Box
time = 0.33899E-02
fringes of z-stress
min=-2.948E+04 in element 379
max=2.374E+04 in element 444

fringe levels
2.130E+04
-1.210E+04
-2.869E+03
5.357E+03
1.550E+04

Peak Axial Stress In Projectile,
Dropped In Wooden Shipping
Crate Flat On Projectile
End From 7 Feet.

Stress in psi.

Maximum stress 29,480 psi at
a time of 0.339E-02 sec.

Fig. 34. Peak von Mises stress, projectile in wooden shipping crate dropped flat on projectile end.

INTERNAL DISTRIBUTION

1-3.	R. M. Davis	14.	ORNL Patent Office
4-6.	J. H. Hannah	15.	Central Research Library
7.	K. D. Handy	16.	Document Reference Section
8.	T. L. Ryan	17.	Laboratory Records Department
9-12.	J. C. Walls	18.	Laboratory Records (RC)
13.	D. S. Webb		

EXTERNAL DISTRIBUTION

- 19. Assistant Manager, Energy Research and Development, U.S. Department of Energy, Oak Ridge Operations, P.O. Box 2001, Oak Ridge, TN 37831
- 20. A. D'Angelo, Packaging Division, SMCAR-AEP, Picatinny Arsenal, NJ 07806-5000
- 21. N. F. Gravenstede, PM-AMMOLOG, Picatinny Arsenal, NJ 07806-5000
- 22. W. Healy, Packaging Division, SMCAR-AEP, Picatinny Arsenal, NJ 07806-5000
- 23. G. L. Kent, PM-AMMOLOG, Picatinny Arsenal, NJ 07806-5000
- 24. Robert J. Kuper, Chief, Packaging Division, SMCAR-AEP, Picatinny Arsenal, NJ 07806-5000
- 25-26. U.S. Department of Energy, Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831

END

**DATE
FILMED
9 / 13 / 93**