To be published in the Journal of the American Chemical Society

2900-1211

AEC-3432

40134

THE TRIPLE POINT TEMPERATURE OF TRITIUM OXIDE *

by W. M. Jones

University of California
Los Alamos Scientific Laboratory
Los Alamos, New Mexico

26118

ABSTRACT: The triple point temperature of tritium oxide was found to be $4.49 \pm 0.02^\circ\text{C}$.

Preparation of Tritium Oxide.

The value of tritium, its particular health hazard as tritium oxide, and difficulties associated with its decomposition by radioactivity made the use of a small amount of material desirable. Tritium gas, which was 99.49 percent T and 0.51 percent H according to analysis on a Consolidated-Hier mass spectrometer, was oxidized to T_2O by copper oxide. The tritium gas was contained initially in a well-outgassed bulb provided with a break-off seal and was attached to the small preparation system by means of a mercury seal standard taper joint. Provision was made to run mercury up through the single stopcock in the system to eliminate contact with stopcock grease. The 8 grams of copper oxide were contained in a 12 mm. O.D. quartz tube which was electrically heated along about 3 inches of its length. A small trap surrounded by liquid nitrogen was located as close as possible to the furnace tube exit so that the tritium oxide could be condensed as soon as possible after its formation, in order to minimize exchange effects. Prior to the preparation of the T_2O sample, the system had been baked out and then exposed to 5 successive portions of T_2 . Each such portion was converted to T_2O and the water vapor

*This work was sponsored by the AEC.

allowed to be in contact with the system for several days before its removal and admission of the next portion. About 40 minutes were required for conversion of approximately 99 percent of the T_2 to T_2O with the CuO at $325^{\circ}C$. The furnace was then cooled down, and the small amount of unreacted gas (some of which was He^3 formed by radioactive decay of tritium) was removed by a Toepler pump. The T_2O was then sublimed into the triple point apparatus, and the latter was sealed off. About 0.15 cc. of T_2O were prepared.

The Triple Point Temperature of Tritium Oxide.

The apparatus employed is shown in Figure 1. The tritium oxide occupied the annular space "C" between the middle and innermost tubes. A copper-constantan thermocouple "H" of No. 40 silk-covered wires passed down through the inner tube. A thin-walled copper cap "B" fitted over and was soldered to the thin-walled Kovar tube "D" which was sealed to the end of the inner section of glass tubing. The thermocouple junction passed through a small hole in the copper cap and was then bent over. A vacuum-tight, soft solder seal was then made. A small amount of Wood's metal in the bottom of the Kovar tube, covered by a little kerosene, helped to bring the thermocouple to the temperature of the surrounding T_2O . After the T_2O had been frozen into its proper location and the apparatus had been sealed off from the preparation line, the silvered jacket "A" was put on and evacuated for thermal insulation. By placing a dewar of liquid nitrogen around the jacket, the solid T_2O could be cooled by radiation to the desired starting temperature. A dewar of water was then placed around the jacket and its temperature adjusted so as to be about two degrees above the triple point temperature, which was known approximately from observations on the small portions of T_2O used in the conditioning of the preparation line. The sample warmed up partly by the energy release associated

with the radioactive decay of the tritium. Thermocouple readings were made as a function of time, with a precision of $0.001\text{--}0.002^{\circ}\text{C}$, using a White potentiometer and a sensitive galvanometer. The thermocouple was calibrated in place before and after the experiment in the region from 0 to 25°C by comparison with a platinum resistance thermometer calibrated by the National Bureau of Standards. This allowed construction of a percentage deviation plot of thermocouple readings from the typical e.m.f.-temperature relationship for a copper-constantan thermocouple. The absolute error in temperature measurement should not be greater than about 0.01°C .

After completion of the first determination, the sample was cooled down and a second determination immediately made. The material was then kept at low temperature for about 40 hours before the third determination was made. The three determinations, after correction for the small amount of hydrogen impurity, gave triple point temperatures of 4.491 , 4.491 , and 4.495°C , respectively. The temperature-time curve in the region of interest is shown for Run 3 in Figure 2. The measurements were commenced immediately after the preparation in order to minimize any small effects arising from tritium peroxide produced by the action of beta-rays on the T_2O . The agreement of the three values, in spite of the presence of the material as liquid during part of the measurements, and the time lapse before the third determination, make it seem likely that such an effect is negligible. This conclusion is in accord with reasonable estimates of peroxide concentrations likely to exist, based on analyses of the decomposition gases of solid and liquid T_2O made in other connections. In correcting the observations for the hydrogen content, the percentage tritium was assumed to be 99.35. This is an average of the original composition of the gas and the composition of gas collected later from the T_2O decomposition. The corresponding uncertainty in the triple point temperature

amounts to 0.007°C . From the above measurements, the triple point temperature of tritium oxide is taken to be $4.49 \pm 0.02^{\circ}\text{C}$.

Prior to the measurements described above, a similar experiment was performed with deuterium, providing a test of the preparation system, particularly with regard to hydrogen contamination, as well as of the triple point apparatus. The preparation system was pre-treated several times with deuterium. The triple point temperature was found to be 3.81°C , in good agreement with the measurements of Taylor and Selwood⁽¹⁾ (3.82°C), La Mer and Baker⁽²⁾ (3.80°C), Eucken and Schüller⁽³⁾ (3.80°C), Long and Kemp⁽⁴⁾ (3.82°C), and Stokland⁽⁵⁾ (3.813°C).

The progressive increase of the triple point temperature in going from H_2O to T_2O is probably connected, at least in part, with an increasing strength of the hydrogen-bonds in the solid, which is in turn to be associated with a decreasing zero point vibrational energy. This effect in the solid dominates over the oppositely acting effect in the liquid.

(1) Taylor and Selwood, This Journal, 56, 998 (1934).

(2) La Mer and Baker, This Journal, 56, 2641 (1934).

(3) Eucken and Schüller, Ges. d. Wiss. Nachrichten. Math.-Phys. Kl. Fachgr. III, N.F.Bd. 1, 109 (1935).

(4) Long and Kemp, This Journal, 58, 1829 (1935).

(5) Stokland, Kgl. Norske. Videnskab. Selskabs, Forh. 10, No. 39, 145-8 (1937); also cf. Chemical Abstracts 32, 6121 (1938).

Figure 1

Triple Point Temperature Apparatus

- A - silvered vacuum jacket
- B - copper cap
- C - annular space occupied by sample
- D - Kovar
- E - kerosene level in inner tube
- F - mercury seal standard taper ground joints
- G - jacket pump-out lead
- H - No. 40 copper-constantan thermocouple wires
- I - sealed-off lead to T_2O preparation system. A lead provided with a break-off seal for removal of T_2O after the experiment is not shown.

Figure 2

Temperature vs Time in Triple Point Temperature of T.O

Run 3