74B
-68-1
pt. 1

221-265

TECHNICAL REPORT M-68-1

DYNAMICS OF WHEELED VEHICLES

Report 1

A MATHEMATICAL MODEL FOR THE TRAVERSAL OF
RIGID OBSTACLES BY A PNEUMATIC TIRE

APPENDIX B: DIGITAL IMPLEMENTATION OF
SEGMENTED TIRE MODEL

by

N. R. Murphy, Jr.

August 1969

Metz Reference Room
Civil Engineering Department
B106 C. E. Building
University of Illinois
URBANA-CHAMPAIGN
ENGINEERING

Sponsored by

U. S. Army Materiel Command

Conducted by

U. S. Army Engineer Waterways Experiment Station
CORPS OF ENGINEERS
Vicksburg, Mississippi

Approved for Public Release; Distribution Unlimited

approval of U. S. Army Materiel Command.

metadc304024

Destroy this report when no longer needed. Do not return
it to the originator.

The findings in this report are not to be construed as an official
Department of the Army position unless so designated
by other authorized documents.

TECHNICAL REPORT M-68-1

DYNAMICS OF WHEELED VEHICLES

Report 1

A MATHEMATICAL MODEL FOR THE TRAVERSAL OF RIGID OBSTACLES BY A PNEUMATIC TIRE

APPENDIX B: DIGITAL IMPLEMENTATION OF SEGMENTED TIRE MODEL

by

N. R. Murphy, Jr.

August 1969

Sponsored by

U. S. Army Materiel Command

Conducted by

U. S. Army Engineer Waterways Experiment Station
CORPS OF ENGINEERS

Vicksburg, Mississippi

ARMY-MRC VICKSBURG, MISS.

Approved for Public Release; Distribution Unlimited

to
or

approval of U. S. Army Materiel Command.

THE CONTENTS OF THIS REPORT ARE NOT TO BE
USED FOR ADVERTISING, PUBLICATION, OR
PROMOTIONAL PURPOSES. CITATION OF TRADE
NAMES DOES NOT CONSTITUTE AN OFFICIAL EN-
DORSEMENT OR APPROVAL OF THE USE OF SUCH
COMMERCIAL PRODUCTS.

Foreword

The digital implementation of the segmented tire model is an extension of the study reported in the basic report and was developed at the U. S. Army Engineer Waterways Experiment Station (WES) as a part of the vehicle mobility research program under DA Project 1T062103A046, "Trafficability and Mobility Research," Task 03, "Mobility Fundamentals and Model Studies," sponsored by the Directorate of Development and Engineering, U. S. Army Materiel Command.

The study described herein was accomplished by personnel of the Vehicle Dynamics Section (VDS), Mobility Research Branch, Mobility and Environmental Division, under the general supervision of Messrs. W. G. Shockley and S. J. Knight, and under the direct supervision of Dr. D. R. Freitag and Mr. A. J. Green. Mr. N. R. Murphy, Jr., of the VDS and Mr. J. F. Smith of the Mathematics and Analysis Section, Electronic Computer Branch, wrote the computer programs. Mr. Murphy prepared this appendix.

COL Levi A. Brown, CE, was Director of WES during the preparation of this appendix. Mr. F. R. Brown was Technical Director.

Contents

	<u>Page</u>
Foreword	v
Conversion Factors, British to Metric Units of Measurement	ix
Summary.	xi
Program 1.	B1
Program 2.	B3
Computer calculations.	B3
Notation	B6
Summary.	B7
Damping.	B8
Figs. B1-B4	

Conversion Factors, British to Metric Units of Measurement

British units of measurement used in this report can be converted to metric units as follows:

<u>Multiply</u>	<u>By</u>	<u>To Obtain</u>
inches	2.54	centimeters
pounds	4.444	newtons
pounds per square inch	0.689476	newtons per square centimeter

Summary

This appendix presents the procedures for digital implementation of the segmented tire model, developed in the basic report for an analog computer. Two procedures are required: (a) determination of the segment spring coefficient from measured load-deflection test results, and (b) computation of the resultant force vector transmitted to the axle. Digital programs for both procedures were written in Fortran IV for a GE-420 system, and are included.

DYNAMICS OF WHEELED VEHICLES

A MATHEMATICAL MODEL FOR THE TRAVERSAL OF RIGID OBSTACLES BY A PNEUMATIC TIRE

APPENDIX B: DIGITAL IMPLEMENTATION OF SEGMENTED TIRE MODEL

1. For digital implementation of the segmented tire model, basically two procedures are required: (a) determination of the segment spring coefficient from measured load-deflection test results, and (b) computation of the resultant force vector transmitted to the axle. Therefore, two computer programs have been prepared.

Program 1

2. The first program (fig. B1) is used to compute the average deflection of each segment for a given vertical center-line deflection.* It is written in Fortran IV and programmed to run on a GE-420 system. The only input requirement is a card containing the tire radius in inches, the number of segments for 180 deg (current status of the program limits the maximum number of segments to 60), and the desired maximum vertical center-line deflection in inches multiplied by 10. This maximum deflection serves as a cutoff criterion for the computer and should be a number that does not exceed the tire section height. The actual maximum deflection is multiplied by 10 to ensure an integer value. This is a restriction imposed by the "DO-loop" that successively increments the center-line deflection.

3. A representative computer printout is shown in fig. B2 to illustrate the format of the output and to demonstrate, in conjunction with the following example, how the results are used to determine an appropriate segment spring coefficient:

* Appendix A to this report presents procedures for computing the necessary effective radial deflections.

- a. Problem. A 9.00-14, 2-PR tire with a 14-in.* radius is inflated to 30-psi pressure; at this pressure it deflects 1 in. under a 760-lb load. Divide the lower half (180 deg) of the tire into 18 equal segments and determine the segment spring coefficient.
- b. Solution. Prepare an input data card containing the tire radius in inches (14), the number of segments in 180 deg (18), and the maximum vertical center-line deflection in inches multiplied by 10 (say $3 \times 10 = 30$). Run, using the program in fig. B1. Since the coordinate (1.0, 760) was chosen from the load-deflection curve, examine the computer printout (fig. B2) and find the values of segment deflections for a center-line deflection of 1 in. Two segments on each side of the vertical center line are seen to be influenced at this particular deflection. Compute the segment spring coefficient K from the equation**

$$\begin{aligned}
 K &= \frac{F}{2 \sum_{i=1}^2 \Delta_i \cos \phi_i} \\
 &= \frac{760}{2(0.914 \cos 5^\circ + 0.384 \cos 15^\circ)} \\
 &= \frac{760}{2.56} \\
 &= 297 \text{ lb/in.}
 \end{aligned}$$

This value is assigned as the spring coefficient for each segment and will change only if the number of segments or the inflation pressure is changed. Choosing a small deflection, such as 0.2 or 0.4 in., as a basis for determining the spring coefficient would most likely yield a K-value somewhat different from one with a larger value of deflection as a basis. Comparisons of measured load-deflection curves with those computed for K-values obtained from the segmented tire model at various deflections revealed that greater accuracy and consistency were obtained when K was computed from a deflection of 1 in. This deflection is generally in the area of maximum curvature on the load-deflection curve.

* A table of factors for converting British units of measurement to metric units is presented on page ix.

** See equation development in paragraph 21 of the main report.

Program 2

4. The second program (fig. B3) is used to compute the vertical and horizontal components of the resultant force vector transmitted to the axle. It, too, is written in Fortran IV for the GE-420 system. It is a complete, self-contained program that was assembled from a section of a more comprehensive one that represented a multidegree-of-freedom vehicle. Taken out of context, it contains none of the dynamics of the problem, i.e. the influence of the coupled differential equations describing the dynamics of the sprung mass of the system has been removed. Certain modifications were made regarding the input requirements, so the program demonstrates, in a static sense, how the components of the resultant wheel spring force are computed with the segmented tire concept. With other slight modifications, this program can be adapted as a subprogram to describe the tire compliance in other vehicle dynamics programs.

5. The solution is based on a purely geometric approach that treats each discrete axle movement interval in terms of space-oriented coordinates of the terrain and wheel center with respect to a fixed reference frame. The current program will handle up to 100 terrain profile points and up to 24 tire segments equally divided about a vertical axis through the axle of each wheel. Experience has indicated that twelve 10-deg segments, six on each side of the vertical, are sufficient to describe the tire compliance for most terrain conditions and obstacle configurations. The angle to each segment center line is measured from the vertical and is considered positive in a counterclockwise direction.

Computer calculations

6. The following sequence of calculations is used in this second program:

- a. Dimension the appropriate space for segment angles, segment spring coefficients, terrain profile points, segment forces, etc.
- b. Provide a "degree-to-radian" converter = $\pi/180$.
- c. Read in: Coordinates of wheel center (X1,Y1), tire radius, number of tire segments, number of terrain points, number of positions to be calculated, and X and Y increments.

- d. Check for end of data; if no more data, exit computer.
- e. Read in and store all segment angles, spring coefficients, and terrain points.
- f. Print headings and terrain profile table.
- g. Designate a variable name for the number of tire segments; e.g. NNN = NSEG.
- h. Determine maximum horizontal projection of tire, i.e.
XRET = X1 - WRAD, XFET = X1 + WRAD.
- i. Initialize ITR = 2.
- j. Change all segment angles from degrees to radians.
- k. Compute the coordinates of each (undeflected) tire segment (i) location with respect to the wheel axle:

$$\begin{aligned} CX(i) &= \sin(DSEG(i) * WRAD) \\ CY(i) &= -\cos(DSEG(i) * WRAD) \end{aligned}$$

(These then remain constant for a given wheel.)

- l. Set VVV(1) = 0 VVV(2) = 0.
- m. Now determine the coordinates of each (undeflected) segment with respect to the fixed reference system, e.g.

$$\begin{aligned} RXY(1,i) &= X1 + CX(i) \\ RXY(2,i) &= Y1 + CY(i) \end{aligned}$$

- n. At this time compute intersections of the tire segment centers with terrain. For each tire segment:
 - (1) Set DMIN = 1.E10, i.e. some large number definitely greater than tire radius.
 - (2) Compute slope of tire segment (i), e.g. SM = CY(i)/CX(i).
 - (3) KTR = ITR. This is a counter to account for terrain stations.
 - (4) Set X2 = 0, i.e. first terrain point begins at X = 0.
 - (5) Recall Y2 from proper storage location; now there is terrain coordinate X2,Y2.
 - (6) Recall X3,Y3, i.e. the next forward terrain coordinate.
 - (7) Obtain the slope of this line (terrain segment).
 - (8) Compare it with the slope of ith tire segment.
 - (9) If slopes are not the same, the lines will intersect; use the point slope method to obtain coordinate of intersection, i.e. XX,YY for ith tire segment. (This is

coordinate of deflected tire segment with respect to fixed reference system.)

- (10) Now determine whether this coordinate falls within the tire circumference.
- (11) If not, then increment the terrain segment and recheck as before until a coordinate is determined that falls within the tire circumference.
- (12) Compute the radial distance of this intersection from the wheel center and set this distance equal to the variable, DMIN. This represents a new "minimum" length.
- (13) Check this length against last minimum value.
- (14) If it is smaller, let the coordinates of this deflected tire segment be: $RXY(1,i) = XX$; $RXY(2,i) = YY$.
- (15) If, however, it is larger, check to see whether forward edge of tire is ahead of the terrain station.
- (16) If so, then advance the station by one. Go back to step (1).
- (17) If not, go to next tire segment and repeat the procedures described above until all intersections of tire segment centers with terrain segments have been computed.

This operation should locate the positions (with respect to the fixed and moving reference) of each deflected tire segment.

- o. Now compute the actual deflection of each tire segment beginning as follows:

$$\begin{aligned}RXY(1,i) &= X1 - RXY(1,i) \\ RXY(2,i) &= Y1 - RXY(2,i)\end{aligned}$$

These are vertical and horizontal components of new segment length.

- p. Store these values in a temporary storage $AA(1), AA(2)$.
- q. Compute the radial distance of each segment using the Pythagorean Theorem, i.e. $TMAG(i)$ = square root of sum of squares of the respective components.
- r. Obtain the sin and cos of each segment angle as follows:

$$\begin{aligned}RXY(1,i) &= AA(1)/TMAG(i) = \sin \text{ of the segment angle} \\ RXY(2,i) &= AA(2)/TMAG(i) = \cos \text{ of the segment angle}\end{aligned}$$

- s. Compute the radial force in each segment, i.e.

$$TMAG(i) = (WRAD - TMAG(i)) * SEGK(i) = K\delta$$

where $\delta = WRAD - TMAG(i)$

- t. Compute the horizontal and vertical components of the resultant force vector, e.g.

$$VVV(1) = \sum TMAG(i) * RXY(1,i) \rightarrow \text{horizontal component}$$

$$VVV(2) = \sum TMAG(i) * RXY(2,i) \rightarrow \text{vertical component}$$

- u. Print results.
v. Increment tire center position and repeat procedures.

7. Computation of resultant tire spring force vector is summarized as follows:

- a. The points where all tire segment centers (spring locations) intersect the undeflected tire circumference are located.
b. The points where tire segment centers intersect the terrain are located.
c. The radial reduction in length of each tire segment center intersecting the terrain is computed.
d. The force vector for each segment is computed using the displacement of the segment center and the segment spring coefficient.
e. The segment force vectors are summed to yield the vertical and horizontal components of the resultant spring force vector for the wheel.

Notation

8. Symbols used in the second program are defined below:

CX,CY	Coordinates (with respect to the wheel axle) of points where segment center lines intersect the undeflected tire circumference
DSEG	Segment angle in degrees; the angle measured from a vertical line through the wheel axle to center line of segment (positive value, counterclockwise)
DTR	Degree-to-radian conversion factor
HGT	Elevation of profile
NPOS	Number of wheel positions to be computed
NSEG,NNN	Number of tire segments
NTP	Number of terrain points to be used

RXY	Absolute coordinates (with respect to fixed X-Y reference) of the points where segment center lines intersect the undeflected tire circumference
SE GK	Segment spring coefficient (can vary with each segment)
ST	Slope of a terrain segment
STA	Horizontal distance of terrain profile
TMAG	Radial force of segment
VV(1)	Horizontal component of force
VV(2)	Vertical component of force
WRAD	Wheel radius
XX,YY	Absolute coordinates of the intersection points of the terrain with tire segment
X1,Y1	Coordinates of wheel center
X2,Y2	Absolute coordinates of the rear terrain station
X3,Y3	Absolute coordinates of the adjacent terrain station in increasing X-direction
XFET,XRET	Forward and rear extremes of tire (horizontal)
XINCR,YINCR	Increment of axle movement of wheel in X- and Y-directions

Summary

9. The required input information for the second program consists of (a) the coordinates of the tire center, (b) the undeflected tire radius, (c) the number of segments to be used, (d) the number of terrain coordinates, (e) the number of axle positions to be calculated, (f) the X- and Y-increments (i.e. the movements of the axle), (g) each segment angle in degrees, (h) each segment spring constant (may be different for each segment if desired), and (i) the terrain profile coordinates. The tire-center coordinates are the only inputs that do not remain constant. When the program is used in an appropriate vehicle dynamics program that describes the motions of the sprung masses, these coordinates are determined at each time step by the differential equations that describe the dynamics of the vehicle system. The coordinates (X1,Y1) of the tire center are used to compute forward and rear extremes of the tire for each increment of movement. This is accomplished by subtracting or adding the tire radius (WRAD) to the coordinate X1. (See fig. B4.) The program can then be used to compute

the location of the points, relative to the axle, where each segment center intersects the tire circumference. These values never change and are stored in the computer under the identification CX(i) and CY(i).

10. Then for each increment of horizontal axle movement (XINCR), the program proceeds as follows:

The points of the wheel at each segment's center line are located relative to the fixed (X-Y) reference frame and stored as coordinates under the identification RXY(1,i) and RXY(2,i). This gives the complete orientation of each undeflected segment "spring." The program then proceeds into a loop that calculates the intersections of the segment center lines and the terrain profile segments, which are constructed from straight-line connections of the terrain profile points. These intersections are determined by the point-slope method, which compares the slopes of each segment center line (proceeding in a counterclockwise sequence beginning with the rear segment) with the slopes of each terrain segment within the forward extreme of the tire. A check is made in each instance to determine if the intersections occur within the periphery of the undeflected tire. This indicates whether a particular segment is influenced by the terrain and the amount that each segment deflects in a radial direction. The radial deflection that is computed for each segment spring is multiplied by the appropriate spring constant to yield a segment force vector whose magnitude and orientation are known. These individual vectors are summed to yield the vertical and horizontal components of the resultant force vector acting at the axle. The axle is then advanced to the next position and the process is repeated.

Damping

11. No provision has been made to incorporate segment damping forces at this time. The influence of tire damping is currently computed as a gross vertical force from the relative motion between the axle and a point directly beneath the axle.

```

      C      A PROGRAM TO COMPUTE AVG DEFLECTIONS OF PNEUMATIC TIRE SEGMENTS
1     DIMENSION AVGDEL(60)
2     TANF (AZ) = SIN (AZ)/ COS (AZ)
3     PI = 3.1416
4     1 READ 10, R, N, IDEFL
5     PRINT 155
6     40 PRINT 60
      C      R IS TIRE RADIUS IN IN., N IS NO. OF SEGMENTS FOR 180 DEGREES
      C      IDEFL IS MAX. VERTICAL DEFLECTION AT VRP IN IN. TIMES 10
7     THETA = PI/N
8     W = R * THETA
9     TTHETA = THETA * 180.0/PI
10    DO 15 J = 1, IDEFL
11    DELTA = J/10.
      C      DELTA IS CENTERLINE DEFLECTION IN IN.
12    X = SQRT (2 * R * DELTA - DELTA * DELTA)
13    PHI = ATAN2 ( X, R - DELTA)
      C      ARC IS ARC OF CONTACT, W IS ARC OF ENTIRE SEGMENT
14    B = PHI/THETA
15    IF (B - 1.0) 5, 6, 6
16    5 M = 1
17    I = 1
18    ARC = R * PHI
      C      M IS THE NO. OF SEGMENTS INFLUENCED BY DELTA DEFLECTION
19    AVGDEL(I) = R - SQRT ((W - ARC)/W * R * R + R/W * ((R - DELTA)
      1 **2)*(TANF(PHI)))
      C      AVGDEL IS AVG DEFLECTION OF SEGMENT
20    GO TO 14
21    6 K = B
      C      NO. OF SEGMENTS FULLY DEPRESSED
22    IF (B - K) 3, 8, 7
      C      IS B AN INTEGER
23    3 STOP 55
24    7 M = B + 1.0
25    GO TO 9
26    8 M = B
27    9 DO 4 I = 1, K
28    4 AVGDEL(I) = R - SQRT (R/W*((R-DELTA)**2)*(TANF(I*THETA)
      1 - TANF((I - 1) * THETA)))
29    IF (M-B) 11, 13, 11
30    13 IF(I-14) 14, 14, 17
31    11 I = M
32    ARC = R * PHI - (I - 1) * W
33    AVGDEL(I) = R - SQRT ((W - ARC)/W * R * R + (R/W * ((R - DELTA)
      1 **2) * (TANF(PHI) - TANF((I-1)*THETA))))
34    IF(I-14) 14, 14, 17
35    14 PRINT 185
36    PRINT 186
37    PRINT 187, DELTA, N, TTHETA, (AVGDEL(I), I=1, M)
38    GO TO 15
39    17 PRINT 185
40    PRINT 186
41    PRINT 188, DELTA, N, TTHETA, (AVGDEL(I), I= 1, 14)
42    PRINT 189
43    PRINT 190, (AVGDEL(I), I=15, M)
44    15 CONTINUE
45    GO TO 1
46    10 FORMAT (F10.2,2I5)
47    155 FORMAT (1H1)
48    60 FORMAT (41X, 34HCOMPUTATION OF AVERAGE DEFLECTIONS//)
49    185 FORMAT (3X, 2HCL, 3X, 2HNO, 3X, 5HTHETA, 18X, 7HAVERAGE, 2X
      1 7HSEGMENT, 2X,10HDEFLECTION, 2X, 2HIN, 2X, 6HINCHES)
50    186 FORMAT(2X, 4HDEFL, 2X, 3HSEG, 3X, 3HDEG, 3X, 4HSEG1, 3X, 4HSEG2,
      1 3X, 4HSEG3, 3X, 4HSEG4, 3X, 4HSEG5, 3X, 4HSEG6, 3X, 4HSEG7,
      1 3X, 4HSEG8, 3X, 4HSEG9, 2X, 5HSEG10, 2X, 5HSEG11, 2X, 5HSEG12,
      1 2X, 5HSEG13, 2X, 5HSEG14)
51    187 FORMAT (F6.2, 15, F6.2, 14F7.3/)
52    188 FORMAT (F6.2, 15, F6.2, 14F7.3/)
53    189 FORMAT(19X, 5HSEG15, 2X, 5HSEG16, 2X, 5HSEG17, 2X, 5HSEG18,
      1 2X, 5HSEG19, 2X, 5HSEG20, 2X, 5HSEG21, 2X, 5HSEG22, 2X, 5HSEG23,
      1 2X, 5HSEG24, 2X, 5HSEG25, 2X, 5HSEG26, 2X, 5HSEG27, 2X, 5HSEG28)
54    190 FORMAT (17X, 14F7.3/)
55    END

```

Fig. B1. Program for computing average deflections
of pneumatic tire segments

COMPUTATION OF AVERAGE DEFLECTIONS

CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.10	18	10.00	0.041													
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.20	18	10.00	0.115													
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.30	18	10.00	0.210	0.001												
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.40	18	10.00	0.311	0.015												
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.50	18	10.00	0.411	0.044												
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.60	18	10.00	0.512	0.088												
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.70	18	10.00	0.612	0.145												
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.80	18	10.00	0.713	0.213												
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
0.90	18	10.00	0.813	0.293												
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.00	18	10.00	0.914	0.384												
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.10	18	10.00	1.014	0.485	0.000											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.20	18	10.00	1.115	0.589	0.008											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.30	18	10.00	1.216	0.692	0.025											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.40	18	10.00	1.316	0.796	0.052											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.50	18	10.00	1.417	0.900	0.087											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.60	18	10.00	1.517	1.003	0.131											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.70	18	10.00	1.618	1.107	0.183											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.80	18	10.00	1.718	1.211	0.243											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
1.90	18	10.00	1.819	1.314	0.312											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.00	18	10.00	1.919	1.418	0.389											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.10	18	10.00	2.020	1.522	0.474											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.20	18	10.00	2.120	1.625	0.566											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.30	18	10.00	2.221	1.729	0.666											
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.40	18	10.00	2.321	1.833	0.774	0.000										
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.50	18	10.00	2.422	1.936	0.885	0.005										
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.60	18	10.00	2.522	2.040	0.995	0.017										
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.70	18	10.00	2.623	2.144	1.106	0.037										
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.80	18	10.00	2.723	2.248	1.217	0.063										
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
2.90	18	10.00	2.824	2.351	1.327	0.097										
CL	NO	THETA	AVERAGE SEGMENT DEFLECTION IN INCHES													
DEFL	SEG	DEG	SEG1	SEG2	SEG3	SEG4	SEG5	SEG6	SEG7	SEG8	SEG9	SEG10	SEG11	SEG12	SEG13	SEG14
3.00	18	10.00	2.924	2.455	1.438	0.137										

Fig. B2. Printout of computations of average deflections

06/30/69	INGRAM	INGRAM TC1 04-G2-R0-010 7 FEBRUARY 1969	PAGE # 1	INGR	SDL6
		S TITLE INGRAM TC1 04-G2-R0-010 7 FEBRUARY 1969 C THIS CODE WAS TAKEN FROM A VEHICLE DYNAMICS PROGRAM WHICH IS NOW C BEING USED AT WES, C THE PROGRAM PRESENTED HERE CONTAINS NONE OF THE DYNAMICS OF THE C PROBLEM, BUT IS INTENDED ONLY TO DEMONSTRATE STATICALLY HOW THE C RESULTANT WHEEL SPRING FORCE IS COMPUTED USING THE SEGMENTED WHEEL C CONCEPT. 1 DIMENSION DSEG(24), SEGK(24), STA(100), HGT(100), TMAG(24), RXY(2,24) 2 DIMENSION VVV(2), AA(2), CX(24), CY(24) 3 1 FORMAT (8F10,0) 4 DTR = 3.141592653 / 180, C THE ANGLE, DSEG(I), TO EACH SEGMENT CENTER IS MEASURED FROM THE C VERTICAL, POSITIVE COUNTERCLOCKWISE IN DEGREES, C UNITS FOR OTHER VARIABLES ARE ARBITRARY, BUT SHOULD BE CONSISTENT, 5 100 READ 1, X1, Y1, WRAD, NSEG, NTP, NPOS, XINCR, YINCR 6 CALL EOSTST(50, ITEST) 7 GO TO(120,110), ITEST 8 110 CALL EXIT 9 120 READ 1, (DSEG(I), SEGK(I), I = 1, NSEG) 10 READ 1, (STA(I), HGT(I), I = 1, NTP) 11 PRINT 3, WRAD, NSEG 12 3 FORMAT(115H WHEEL RADIUS = F8.2, // 221H NUMBER OF SEGMENTS = I5//) 13 PRINT 4, (I, DSEG(I), SEGK(I), I = 1, NSEG) 14 4 FORMAT (34H SEGMENT ANGLE TO SPRING / 1 36H NUMBER CENTERLINE CONSTANT // 2 (I5, F15.2, F14.2)) 15 PRINT 5, (STA(I), HGT(I), I = 1, NTP) 16 5 FORMAT (16H TERRAIN PROFILE / 1 16H X Y / 2 (2F8.2)) 17 NNN = NSEG 18 XRET = X1 - WRAD 19 XFET = X1 + WRAD 20 ITR = 2 21 DO 1065 I = 1, NSEG 22 DSEG(I) = DSEG(I) * DTR 23 CX(I) = SIN(DSEG(I)) * WRAD 24 CY(I) = -COS(DSEG(I)) * WRAD 25 1065 CONTINUE 26 PRINT 10 27 10 FORMAT(50H LOCATION OF WHEEL CENTER RESULTANT FORCES / 1 7X, 1HX, 9X, 1HY, 17X, 4HF(X), 6X, 4HF(Y)) 28 DO 200 II = 1, NPOS 29 VVV(1) = 0, 30 VVV(2) = 0, C ... LOCATE ALL POINTS ALONG TIRE CIRCUMFERENCE 31 DO 5325 I = 1, NNN 32 RXY(1, I) = X1 + CX(I) 33 RXY(2, I) = Y1 + CY(I) 34 5325 CONTINUE C ... INTERSECT SEGMENT CENTERS WITH TERRAIN 35 DO 5350 I = 1, NNN 36 DMIN = 1.E10 37 SM = CY(I) / CX(I) 38 KTR = ITR 39 X2 = 0, 40 Y2 = HGT(KTR-1) 41 5329 CONTINUE 42 X3 = STA(KTR) - STA(ITR-1) 43 Y3 = HGT(KTR) 44 ST = (Y2 - Y3) / (X2 - X3) 45 IF(SM - ST) 5331, 5330, 5331 46 5330 XX = 1.E35 47 GO TO 5333 48 5331 XX = (Y2 - Y1 + SM * X1 - ST * X2) / (SM - ST) 49 5333 YY = ST * (XX - X2) + Y2 50 KERR = KBTWN(X2, XX, X3) 51 GO TO (5332, 5336), KERR 52 5332 KERS = KBTWN(Y2, YY, Y3) 53 GO TO (5334, 5336), KERS 54 5334 KERT = KBTWN(X1, XX, RXY(1, I)) 55 GO TO (5335, 5336), KERT 56 5335 KERU = KBTWN(Y1, YY, RXY(2, I)) 57 GO TO (5340, 5336), KERU 58 5336 IF(XFET - STA(KTR)) 5350, 5350, 5338 59 5338 KTR = KTR + 1 60 X2 = X3 61 Y2 = Y3 62 GO TO 5329 63 5340 DMIN1 = SQRT((XX - X1)**2 + (YY - Y1)**2) 64 IF(DMIN1 - DMIN) 5341, 5341, 5336 65 5341 DMIN = DMIN1 66 RXY(1, I) = XX 67 RXY(2, I) = YY 68 GO TO 5336 69 5350 CONTINUE 70 5355 CONTINUE C 71 DO 5356 I = 1, NNN 72 RXY(1, I) = X1 - RXY(1, I) 73 RXY(2, I) = Y1 - RXY(2, I) 74 5356 CONTINUE C ... NORMALIZE RXY AND LET TMAG BE MAGNITUDE 75 DO 5357 I = 1, NNN 76 AA(1) = RXY(1, I) 77 AA(2) = RXY(2, I) 78 TMAG(I) = SQRT(AA(1)*AA(1) + AA(2)*AA(2)) 79 RXY(1, I) = AA(1) / TMAG(I) 80 RXY(2, I) = AA(2) / TMAG(I) 81 5357 CONTINUE C ... COMPUTE FORCE FOR EACH SEGMENT 82 DO 5358 I = 1, NNN 83 TMAG(I) = (WRAD - TMAG(I)) * SEGK(I) 84 5358 CONTINUE C ... COMPUTE COMPOSITE FORCE VECTOR 85 DO 5359 I = 1, NNN 86 VVV(1) = VVV(1) + TMAG(I) * RXY(1, I) 87 VVV(2) = VVV(2) + TMAG(I) * RXY(2, I) 88 5359 CONTINUE 89 PRINT 2, X1, Y1, VVV 90 2 FORMAT(2F10,2, 10X, 2F10,2) 91 Y1 = Y1 + YINCR 92 X1 = X1 + XINCR 93 200 CONTINUE 94 GO TO 100 95 END			
06/30/69	OKBTWNF	INGRAM TC1 04-G2-R0-010 7 FEBRUARY 19	FUNCTION	PAGE # 1	KBTW SDL6
		1 FUNCTION KBTWN(A, P, B) 2 IF(A = P) 30, 40, 20 3 20 IF(B = P) 40, 40, 50 C IS P BETWEEN A AND B 4 30 IF(B = P) 50, 40, 40 C VALID RETURN 5 40 KBTWN = 1 6 RETURN C INVALID RETURN 7 50 KBTWN = 2 8 RETURN 9 END			

Fig. B3. Program for computing vertical and horizontal components of the resultant force vector transmitted to the axle

Fig. B4. Schematic diagram depicting space coordinates of digital segmented tire program

DISTRIBUTION LIST A

(For Distribution of TR's and MP's on Trafficability and Mobility Studies
and Related Investigations)

<u>Address</u>	<u>No. of Copies</u>
Commanding General, U. S. Army Materiel Command ATTN: AMCRD-DM	1
AMCRD-TV	2
AMCRD-G	1
Washington, D. C.	
Commanding Officer, USA Terrestrial Sciences Research Center ATTN: Library	1
Hanover, N. H.	
Commanding Officer, U. S. Army Mobility Equipment Research and Development Center	2
ATTN: Technical Documents Center, Building 315 Fort Belvoir, Va.	
Commanding Officer, USA Electronics Command Meteorological Support Activity	1
Fort Huachuca, Ariz.	
Commanding Officer, USA Electronics Research and Development Laboratories	1
ATTN: SELRA/ADT Fort Monmouth, N. J.	
Chief of Research and Development	1
ATTN: Chief, Combat Materiel Division Department of the Army Washington, D. C.	
Chief of Research and Development	1
ATTN: CRDES, Department of the Army Washington, D. C.	
Chief of Research and Development Headquarters, Department of the Army	3 copies of Form
ATTN: Director of Army Technical Information Washington, D. C.	1473
Defense Intelligence Agency	1
ATTN: DIAAP-4B Washington, D. C.	
Special Assistant for Environmental Services Joint Chiefs of Staff	1
Washington, D. C.	

Address	No. of Copies
Director, OSD/ARPA Regional Field Office ARMISH-MAAG (RFO-I) APO New York 09205	1
Commanding Officer, U. S. Army Arctic Test Center APO Seattle, Wash.	1
Chief of Engineers	
ATTN: ENGME-RD	1
ENGAS-I	2
ENGMC-ER	2
ENGME-RO (for Engineer Standardization Program)	4
Department of the Army Washington, D. C.	
War Plans Division, Engineer Strategic Studies Group Office, Chief of Engineers, U. S. Army Erskin Hall, Army Map Service Washington, D. C.	1
Commander, U. S. Army Combat Development Command Engineer Agency ATTN: CSGEN-M Fort Belvoir, Va.	1
The Librarian, U. S. Army Engineer School Library Thayer Hall Fort Belvoir, Va.	2
USA Engr School ATTN: Heavy Construction Section, Department of Engineering Pavements and Materials Group Fort Belvoir, Va.	1
Commanding General, XVIII Airborne Corps ATTN: Corps Engineer Fort Bragg, N. C.	2
Senior Engineer Instructor, Office of Military Instruction United States Corps of Cadets West Point, N. Y.	1
U. S. Continental Army Command Intelligence Center ATTN: Library, IPO Fort Bragg, N. C.	2

<u>Address</u>	<u>No. of Copies</u>
President, U. S. Army Armor Board Fort Knox, Ky.	1
President, U. S. Army Artillery Board Fort Sill, Okla.	1
President, U. S. Army Infantry Board Fort Benning, Ga.	1
Commanding General, U. S. Army Weapons Command ATTN: AMSWE-RDR Rock Island, Ill.	1
Commanding General, U. S. Army Tank-Automotive Command ATTN: AMSTA-BSL Warren, Mich.	2
Commander, U. S. Army Forces Southern Command ATTN: Engineer Fort Amador, Canal Zone	1
Commanding General, U. S. Continental Army Command Engineer Division, DCSLOG ATTN: ATLOG-E-MB Fort Monroe, Va.	2
Commanding General, U. S. Continental Army Command ATTN: ATIT-RD Fort Monroe, Va.	1
Commandant, Command and General Staff College ATTN: Archives Fort Leavenworth, Kans.	1
Commanding General, U. S. Army Tank-Automotive Command Land Locomotion Division ATTN: AMSTA-UL Warren, Mich.	2
Commander, U. S. Army Picatinny Arsenal ATTN: SMUPA-VCL, Mr. D. Sen Dover, N. J.	1
Commanding Officer, Yuma Proving Ground ATTN: STEYP-TGM Yuma, Ariz.	1

Address	No. of Copies
Technical Library, Branch No. 4 U. S. Army Limited War Laboratory Aberdeen Proving Ground, Md.	1
Automotive Engineering Laboratory ATTN: STEAP-DP-LU Aberdeen Proving Ground, Md.	1
Director, Development and Proof Services ATTN: STEAP-DS-TU Aberdeen Proving Ground, Md.	1
Commanding Officer ATTN: Tech Library, Bldg 313 Aberdeen Proving Ground, Md.	2
Commanding Officer, U. S. Army General Equipment Test Activity Fort Lee, Va.	1
Chief, Crops Division, U. S. Army Biological Laboratories Fort Detrick, Md.	1
Commanding Officer, U. S. Army Combat Developments Command Transportation Agency ATTN: Mr. Earl S. Brown Fort Eustis, Va.	1
Asst. Chief of Staff for Force Development Hqs, Department of the Army, ATTN: FOR DS SSS Washington, D. C.	1
United States Army Attaché, American Embassy U. S. Navy 100, Box 36 Fleet Post Office New York, N. Y.	2
Office of Naval Research ATTN: Geography Branch Department of the Navy Washington, D. C.	1
Commanding Officer, PHIBCB Two U. S. Naval Amphibious Base Little Creek, Norfolk, Va.	1
U. S. Naval Academy ATTN: Library, Serials Division Annapolis, Md. 21402	2

<u>Address</u>	<u>No. of Copies</u>
Commanding Officer, PHIBCB One U. S. Naval Amphibious Base Coronado, San Diego, Calif.	1
Commanding Officer and Director Naval Civil Engineering Laboratory Port Hueneme, Calif.	1
Director, Naval Warfare Research Center Stanford Research Institute Menlo Park, Calif.	1
Commander, Naval Facilities Engineering Command Navy Department, Code 03 Washington, D. C.	2
Commanding Officer, U. S. Naval Photographic Interpretation Center Washington, D. C.	1
Chief, Combat Service Support Division Marine Corps Landing Force Development Center Marine Corps Schools Quantico, Va.	1
Commander, 3800th AB Wing, AU ATTN: BDCE-ED Maxwell AFB, Ala.	1
Headquarters, USAF (AFRSTC) Astronautics Division DCS/Research and Development Washington, D. C.	1
Commander, U. S. Strike Command ATTN: J4-E McDill AFB, Fla.	1
Chief, Concepts and Evaluation Group U. S. Strike Command McDill AFB, Fla.	1
Commander, ADTC ATTN: ADBPS-12 Eglin AFB, Fla.	1
Dr. Nicholas C. Costes, Space Sciences Laboratory, Code RSSL-N Marshall Spaceflight Center Huntsville, Ala.	1

Address	No. of Copies
Headquarters, Air Force Systems Command Directorate of Civil Engineering (SCOC) Andrews AFB, Washington, D. C.	2
Headquarters, Tactical Air Command ATTN: DEPL Langley AFB, Va.	2
Headquarters, U. S. Air Force Director of Civil Engineering (AFOCE-KA) Washington, D. C.	2
Headquarters, USAF Base Structures Branch, Directorate of Civil Engineering ATTN: AFOCE-GC Washington, D. C.	1
Commander, Hqs, Military Airlift Command ATTN: MAMCE/FS Scott AFB, Ill.	1
Commander, ASD (ASNMS-20) Wright-Patterson AFB, Ohio	1
Air Force Weapons Laboratory ATTN: Civil Engineering Branch, WLDC Kirtland AFB, N. Mex.	2
Terrestrial Sciences Lab (CRJT) Air Force Cambridge Res Lab, L. G. Hanscom Field Bedford, Mass.	1
Library, Division of Public Documents U. S. Government Printing Office Washington, D. C.	1
Library of Congress, Documents Expediting Project Washington, D. C.	3
Defense Documentation Center ATTN: Mr. Myer Kahn Cameron Station Alexandria, Va.	20
National Tillage Machinery Laboratory U. S. Department of Agriculture Auburn, Ala.	1

<u>Address</u>	<u>No. of Copies</u>
Chief, World Soil Geography Unit, Soil Conservation Service USDA, Room 233A Federal Center Bldg Hyattsville, Md.	1
Director, Pacific Southwest Forest and Range Experiment Station ATTN: Henry W. Anderson Berkeley, Calif.	1
U. S. Geological Survey Chief, Source Material Unit, Branch of Military Geology Washington, D. C.	2
Coastal Studies Institute Louisiana State University Baton Rouge, La.	1
Librarian, Bureau of Public Roads U. S. Department of Commerce Washington, D. C.	1
New York University ATTN: Engineering Library University Heights, Bronx, N. Y.	1
Professor L. C. Stuart University of Michigan Ann Arbor, Mich.	1
University of Arkansas, College of Engineering ATTN: Mr. Henry H. Hicks, Jr. Fayetteville, Ark.	1
Stanford Research Institute ATTN: Mr. Gordon S. Wiley Menlo Park, Calif.	1

Address	No. of Copies
Engineering Societies Library New York, N. Y.	1
Highway Research Board Washington, D. C.	1
Research Analysis Corporation ATTN: Library McLean, Va. 22101	1
Davidson Laboratory, Stevens Institute of Technology ATTN: Dr. I. R. Ehrlich Hoboken, N. J.	1
Center for Research and Engineering Science University of Kansas Lawrence, Kansas	1
Mr. David Sloss, Civil Engineering Department University of Detroit Detroit, Mich. 48221	1
Institute of Transportation and Traffic Engineering Library University of California Richmond, Calif. 94804	1
Wilson, Nuttall, Raimond Engineers, Inc. ATTN: Library Chestertown, Md.	1
Cornell Aeronautical Laboratory, Inc. P. O. Box 235 Buffalo, N. Y. 14221	1
Technical Library USACDC Institute of Land Combat 301 Taylor Drive Alexandria, Va. 22314	1

Address	No. of Copies
<u>Consultants</u>	
Dr. A. A. Warlam	1
Prof. K. B. Woods	1
Mr. Robert Horonjeff	1
Mr. C. J. Nuttall	1
Mr. R. E. Fadum	1
Dr. N. M. Newmark	1
Dr. Gerald Pickett	1
Dr. M. J. Hvorslev	1
Dr. Arthur Casagrande	1

Unclassified
Security Classification

DOCUMENT CONTROL DATA - R & D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) U. S. Army Engineer Waterways Experiment Station Vicksburg, Mississippi		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE DYNAMICS OF WHEELED VEHICLES, Report 1; A MATHEMATICAL MODEL FOR THE TRAVERSAL OF RIGID OBSTACLES BY A PNEUMATIC TIRE; APPENDIX B: DIGITAL IMPLEMENTATION OF SEGMENTED TIRE MODEL		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Appendix B to final report		
5. AUTHOR(S) (First name, middle initial, last name) Newell R. Murphy, Jr.		
6. REPORT DATE August 1969	7a. TOTAL NO. OF PAGES 18	7b. NO. OF REFS None
8a. CONTRACT OR GRANT NO. a. PROJECT NO. 1TO62103A046 c. Task 03 d.		8b. ORIGINATOR'S REPORT NUMBER(S) Technical Report M-68-1, Report 1 Appendix B
		8c. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
9. DISTRIBUTION STATEMENT This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of U. S. Army Materiel Command.		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY U. S. Army Materiel Command Washington, D. C.
13. ABSTRACT This appendix presents the procedures for digital implementation of the segmented tire model, developed in the basic report for an analog computer. Two procedures are required: (a) determination of the segment spring coefficient from measured load-deflection test results, and (b) computation of the resultant force vector transmitted to the axle. Digital programs for both procedures were written in Fortran IV for a GE-420 system, and are included.		

DD FORM 1473

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

Unclassified
Security Classification

Unclassified
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Mathematical models						
Obstacles						
Tires						
Vehicle dynamics						

~~Unclassified~~
~~Security Classification~~

Metz Reference Room
University of Illinois
B106 NCEL
★ 208 N. Romine Street
Urbana, Illinois 61801

Metz Reference Room
University of Illinois
B106 NCEL
208 N. Romine Street
Urbana, Illinois 61801