TEI-773

Report TEI-773

INTERIM GEOLOGICAL INVESTIGATIONS
IN THE U12e.06 TUNNEL, NEVADA
TEST SITE, NYE COUNTY, NEVADA

By W. L. Emerick

With a section on

GAMMA - RADIOACTIVITY

By C. M. Bunker

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

metadc304695

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

INTERIM GEOLOGICAL INVESTIGATIONS IN THE U12e.06 TUNNEL,
NEVADA TEST SITE, NYE COUNTY, NEVADA*

By

W. L. Emerick

with a section on gamma-radioactivity

By

C. M. Bunker

January 1962

*Prepared on behalf of the U. S. Atomic Energy Commission.

CONTENTS

	Page
Abstract-----	4
Introduction-----	6
Geology-----	9
General-----	9
Rocks-----	12
Subunit H of Tunnel Bed 4-----	12
Subunit G of Tunnel Bed 4-----	15
Physical properties-----	30
Gamma-radioactivity, by C. M. Bunker-----	34
References-----	37

ILLUSTRATIONS

Figure 1. Index map showing the tunnel area, Nevada Test Site, Nye County, Nev.-----	7
2. Index map showing the U12e tunnel system, Rainier Mesa, Nevada Test Site, Nye County, Nev.-----	8
3. Generalized geologic cross section along U12e and U12e.06 tunnels, Rainier Mesa, Nevada Test Site, Nye County, Nev.-----	10
4. Geologic map and cross section of tunnel U12e.06 showing gamma-radioactivity data, Nevada Test Site, Nye County, Nev.-----	In pocket

TABLES

	Page
Table 1. Modal analyses, in percent, of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev. -----	14
2. Chemical analyses, in percent, of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev. -----	16
3. Semiquantitative spectrographic analyses of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev. -----	22
4. Physical properties of tuffs from U12e.06 tunnel, Nevada Test Site, Nye County, Nev. -----	31

INTERIM GEOLOGICAL INVESTIGATION IN THE U12e.06 TUNNEL,
NEVADA TEST SITE, NYE COUNTY, NEVADA

By W. L. Emerick

ABSTRACT

The U12e.06 tunnel is a part of the U12e tunnel system which has been driven southwestward beneath Rainier Mesa in the northern part of the Nevada Test Site. The tunnel was driven in nonwelded tuff near the top of the lower member, in the Tunnel Beds, of the Oak Spring Formation of (Miocene(?) or younger) Tertiary age. Dolomite of Paleozoic age lies from 958 to 971 feet below the tunnel; vertical cover over the end of the tunnel to the surface of Rainier Mesa is about 1,440 feet.

The tuffs in the tunnel strike northwest and northeast and dip southwest and northwest. Northwest- and northeast-trending faults with steep dips are common. All appear to be normal faults and the displacement on them is generally small. Joints are common in the tuffs of the tunnel, and they trend dominantly either northwest or northeast with generally vertical to steep dips. The dominant structural features of the rocks in the tunnel are the southwest-trending Caprock syncline, and a minor southwest-trending syncline and anticline lying on the south limb of the Caprock syncline.

Petrologically and chemically the tuffs in the U12e.06 tunnel are similar to other tuffs of the Oak Spring Formation from the Nevada Test Site.

The tuffs in the tunnel have an average porosity of 35.4 percent, dry-bulk density of 1.56 grams per cubic centimeter (g/cc), grain density of 2.41 g/cc, Shore scleroscope hardness of 25, and unconfined compressive strength of 3,300 pounds per square inch (psi).

A gamma-radioactivity survey of the tunnel was made with a portable scintillation-type detector to obtain quantitative data on the radioactivity emitted by radioisotopes in the rock. Results of the survey indicate that the method cannot be used to aid stratigraphic discrimination. The natural radioactivity in the tuffs is low enough not to interfere with studies of gamma-emitting radioisotope distribution resulting from underground nuclear explosions. Anomalous radioactivity is apparently related to the amount of fracturing and faulting; the highest radioactivity is found where these are more prevalent.

INTRODUCTION

The U12e.06 tunnel is a part of the U12e tunnel system, which has been driven southwestward beneath Rainier Mesa, a prominent topographic feature in the northern part of the Nevada Test Site (fig. 1). The geologic studies in the U12e.06 tunnel were conducted by the U.S. Geological Survey on behalf of the Atomic Energy Commission under the Vela Uniform program, Project Shade, for the purpose of (1) determining the pre-explosion chemical and physical properties of the tuffs exposed in the tunnel for comparison with similar post-shot geologic data and (2) evaluating these data in terms of predicting the geologic effects of the planned explosion.

The U12e.06 tunnel trends S. 65° W. for 2,600 feet from the main U12e tunnel at a point 3,802 feet from the portal (fig. 2). For most of its length, the U12e.06 tunnel averages 11 by 12 feet in cross section and is supported by 9-foot steel sections spaced at various intervals ranging from 4 to 6 feet, and lagged with wood plank.

**FIGURE 1--INDEX MAP, SHOWING LOCATION OF TUNNEL AREA,
RAINIER MESA, WHITEROCK SPRING QUADRANGLE,
NYE COUNTY, NEVADA**

5 4 3 2 1 0 5 MILES

**FIGURE 2.--INDEX MAP SHOWING THE U12e TUNNEL SYSTEM, RAINIER MESA,
NEVADA TEST SITE, NYE COUNTY, NEVADA**

1000 0 1000 FEET

Contour interval 200 feet, except 7600-foot contour also shown
Datum is mean sea level

GEOLOGY

General

The U12e.06 tunnel was driven in nonwelded tuff of Tunnel Bed 4, the upper unit of the lower member of the Oak Spring Formation of Tertiary age (fig. 3). The lower member consists of Tunnel Beds 1 through 4 (Hinrichs and Orkild, 1961), which are equivalent to map units 1 through 4 of Hansen and Lemke (1957) and units 1 through 4 of McKeown and Dickey (1961). Mappable subunits are designated by capital letters following the unit symbol.

The tuffs of the lower member rest upon an erosional surface cut in dolomite of early to middle Paleozoic age. The distance beneath the U12e.06 tunnel to the contact between the tuffs and dolomite was determined from two vertical core holes (U12e.06a and U12e.06b) drilled from floor of the tunnel at 5+00 to 21+80 feet. These distances are 971 and 959 feet, respectively. Vertical distance to the surface of Rainier Mesa over the end of the tunnel is about 1,440 feet. The total thickness of the Oak Spring Formation in this area is about 2,400 feet as compared to 1,900 feet in the U12b tunnel area and 1,896 feet (Diment, Gibbons, and Roller, written communication, 1957) at the Hagestad drill hole (fig. 2), approximately 4,100 feet N. 16°30' W. of Station 22+00 feet in the U12e.06 tunnel.

The principal structural features of the tuffs in the tunnel are the southwest-trending Caprock syncline, a minor southwest-

**FIGURE 3.--GENERALIZED GEOLOGIC CROSS SECTION ALONG U12e AND U12e-06 TUNNELS,
RAINIER MESA, NEVADA TEST SITE, NYE COUNTY, NEVADA**

1000 0 1000 FEET
Datum is mean sea level

NOTE: All symbols refer to units of the Oak Spring Formation of Tertiary age.
Tr, Rainier Mesa Member; Ts, Survey Butte Member; Tgl, lower part of Grouse
Canyon Member; Tlt₁-Tlt₄, Tunnel Beds 1-4 of the lower member.

trending syncline and anticline on its southern limb, and the northwest- and northeast-trending steeply dipping normal faults (fig. 4). Joints are abundant and parallel the attitudes of the faults.

The axes of the minor syncline and anticline cross the tunnel at about 2+00 and 3+15 feet, respectively. The two folds plunge 3° to 4° SW. and their amplitudes are about 10 feet. The axis of the Caprock syncline crosses the tunnel in a southwesterly trend at about 23+50 feet. The Caprock syncline was mapped in the U12e main tunnel by McKeown and Dickey (1961) and on the surface by Gibbons and others (1960).

The tuffs exposed in the tunnel strike N. 74° W. to N. 15° E., and dip 3° SW. to 14° NW. Faults are common and strike predominantly northwest and northeast. They dip steeply and most have vertical displacements ranging from 0.3 to 6.0 feet. All the faults appear to be normal. Locally, as in the vicinity of 14+68 the tuffs are extensively fractured, and the beds have been displaced vertically from 8 to 10 feet. Drips and trickles of water issue from many of the faults and joints.

Joints are common in the tuffs cut by the U12e.06 tunnel. A total of 685 joints was recorded in the tunnel; of these 62 percent trend northeast, 36 percent trend northwest, and 2 percent trend equally north-south and east-west. The northeast-trending joints have three equally prominent dips: (1) vertical; (2) average dip

of 76° NW.; and (3) average dip of 76° SE. The northwest-trending joints have an average dip of 70° SW.

Rocks

The U12e.06 tunnel was driven principally in subunits H and G of Tunnel Bed 4, the uppermost unit of the lower member of the Oak Spring Formation. Subunits H and G are the topmost mapped subunits in Tunnel Bed 4.

Subunit H of Tunnel Bed 4

Megascopically, subunit H is a white, red, and gray massive to bedded fine- to coarse-grained pumiceous tuff. As mapped, the lower part of the subunit consists of about 35 feet of bedded white tuff (zone H_1) with abundant dark lithic fragments, which are principally quartzite or other metamorphic and volcanic rock. Locally, the lower part has red streaks and wider red bands. The white tuff (H_1) grades upward into more than 40 feet of massive and indistinctly bedded, soft, greenish- to yellowish-gray zeolitized tuff (zone H_2) with mottled and banded red zones at top and bottom. The top of the upper red zone is not exposed in the tunnel. Coarse lithic fragments are common at the top of the 9-foot-thick bottom red zone of H_2 , but lithic fragments are sparse in the yellowish-gray middle zone. The total thickness of subunit H is not exposed in either the U12e.06 tunnel or elsewhere in the U12e tunnel system, but the subunit is estimated to be as much as 85 feet thick.

The tuff of subunit H (H_1 and H_2) consists of fine to lapilli pumice, phenocrysts, and lithic fragments in a very fine grained matrix (table 1). Pumice makes up 25 to 35 percent of the tuff. Irregular vesicles make up 5.6 to 24 percent of the tuffs in the H_1 and H_2 zones. The phenocrysts average 11.7 percent of the tuffs and in order of abundance are potassium feldspar, quartz, plagioclase, magnetite, and biotite. They are euhedral to subhedral. Lithic fragments are fine to coarse (as much as 1 cm across) in the subunit and are made up dominantly of quartzite with other metamorphic or volcanic rock. The matrix, which includes the fine and lapilli pumice, forms as much as 90 percent of the tuff and by X-ray analyses is shown to consist predominantly of a zeolite^{1/},

^{1/} The zeolite corresponds in X-ray pattern to heulandite; it has been found to be stable above 260°C which corresponds with clinoptilolite, the high-silica counterpart of heulandite, as redefined by Mumpton (1958). To avoid confusion with older definitions of clinoptilolite and because of its general similarity, it is here referred to as heulandite.

with very minor or trace amounts of beta-cristobalite, and with clay minerals absent or in trace amounts (table 1). The X-ray patterns of the clay fractions are not clearly defined but they indicate that illite or mixed-layer montmorillonite, or mixtures of both are present. The modal (volume percentage) and X-ray

Table 1.--Modal analyses, in percent, of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev.

[Modal analyses by W. L. Emerick; X-ray analyses by Theodore Botinelly. Location of samples are shown on figure 4. The sample number indicates footage from tunnel entrance referred to Holmes and Narver, Inc. survey followed by the letter R or L indicating right or left wall. R or L followed by lower case a or b indicates two samples taken from approximately the same location but at different heights above track level.]

Sample No.-----	E6-61R	E6-192R	E6-285L	E6-480R	E-600L	E6-700L	E6-800R	E6-1034R	E6-1400R	E6-1600R	E6-1900R	E6-2119R	E6-2200Ra	E6-2200Rb	Mean	Remarks
Lithologic subunits of Tunnel Bed 4-----	G	G	G	H ₁	H ₁	H ₁	H ₂	H ₂	H ₂	H ₁	H ₂	H ₂	H ₂	H ₂		
Matrix ^{1/} :																
Vesicles-----	25.4	10.7	17.7	11.2	10.7	5.6	13.5	10.1	17.8	15.5	21.1	18.5	13.4	24.0	15.4	Many lined with zeolites.
Total matrix-----	79.2	79.3	85.3	75.2	86.9	80.2	90.2	78.3	80.3	81.0	84.0	85.9	73.0	89.6	82.0	
Lithic fragments-----	2.4	2.0	6.1	10.8	6.4	5.9	4.4	7.6	13.5	5.6	4.6	2.8	13.9	1.5	6.2	Principally quartzite with other metamorphic or volcanic rocks-- up to 6 mm.
Phenocrysts:																
Potassian feldspar--	8.7	3.6	5.3	9.4	1.7	7.0	1.9	8.5	3.1	11.2	6.3	6.2	7.2	4.8	6.1	Probably partly K-feldspar and partly Na-feldspar.
Plagioclase-----	2.7	8.2	.8	2.4	.9	.9	.7	2.4	.7	.8	1.9	1.8	.8	1.2	1.9	
Quartz-----	6.5	5.8	2.4	1.9	3.9	5.5	2.7	3.1	2.4	1.1	3	3.2	5	2.8	3.5	
Magnetite-----	.4	.2	0	.3	<.1	.5	<.1	0	0	<.1	.2	<.1	.1	<.1	<.1	A few grains altered to red oxide and to limonite.
Biotite-----	<.1	<.1	<.1	0	<.1	0	0	<.1	0	<.1	0	0	0	0	<.1	Brown.
Other mafics-----	0	.8	0	0	0	0	0	0	0	<.1	0	0	0	0	.1	Hornblende(?).
Total-----	18.4	18.7	8.6	14	6.7	13.9	5.4	14.1	6.2	13.4	11.4	11.3	13.1	8.9	11.7	
Grand total-----	100	100	100	100	100	100	100	100	100	100	100	100	100	100	-----	
Area measured (mm ²)---	2,367	1,875	2,914	2,090	3,007	3,427	3,238	1,600	2,511	955	2,812	1,109	2,975	2,700	2,399	
Heulandite ^{2/} -----		Predomi- nant		Dominant				Predomi- nant			Predomi- nant		Predomi- nant	Predomi- nant		
Beta-cristobalite ^{2/} ---		Trace		Trace				Minor			Minor		Trace	Trace		
Clay minerals ^{2/} -----		Trace		Trace				-----			Minor		Trace(?)	-----		

^{1/} The matrix includes the fine and lapilli pumice. The constituent minerals were estimated from X-ray diffractometer patterns.

^{2/} The amounts of heulandite, beta-cristobalite, and clay minerals are estimated on the intensity of the X-ray diffractometer pattern of the three minerals present in the matrix and are at best only rough approximations: predominant - <75 to 100 percent; dominant - 50 to 75 percent; major - 25 to 50 percent; minor - 10 to 25 percent; and trace - <10 percent.

analyses of the tuff of subunit H are given in table 1. From study of the thin sections, some secondary spherulitic chalcedony was found in the middle part of zone H₂. Hematite accounts for the color of the red streaks and bands in the subunit. It occurs as a coating on pumice or lapilli and as a cementing material. Silica, as beta-cristobalite, is probably a minor cementing agent. The heulandite, beta-cristobalite, and clay minerals are alteration products of an original pumiceous material.

Chemical analyses of samples from subunit H are given in table 2 and semiquantitative spectrographic analyses in table 3. The chemical composition and trace element content of the tuffs of the subunit are similar to other tuffs of the Oak Spring Formation from the Nevada Test Site.

Subunit G of Tunnel Bed 4

Megascopically, subunit G is a red and white, relatively hard, pumiceous, and generally coarse-grained tuff. Beds in this subunit are generally indistinct, irregular, and 15 feet or more thick; thin beds and laminae are rare (McKeown and Dickey, 1961). A complete thickness of the subunit is not exposed in the U12e.06 tunnel, but in the U12e main tunnel to the northeast the subunit is about 45 feet thick. Elsewhere in the U12e tunnel system the thickness of the subunit has been estimated to be more than 50 feet (McKeown and Dickey, 1961).

Table 2.--Chemical analyses, in percent, of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev.

[Rapid rock analysis by P. L. D. Elmore, I. H. Barlow, S. D. Botts, G. W. Chloe, USGS, using methods similar to those described in USGS Bulletin 1036-C (Shapiro and Brannock, 1956). Equivalent uranium determined by Beta-gamma scaler by L. M. Lee and Wayne Mountjoy, USGS.]

Sample						
No.-----	E6-61R	E6-192R	E6-285L	E6-400L	E6-480R	E6-600L
Laboratory						
No.-----	157594	157595	157623	157622	157614	157621
Lithologic						
subunit----	T1t ₄ G	T1t ₄ G	T1t ₄ G	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₁
SiO ₂	69.70	66.20	68.90	69.60	68.80	67.60
Al ₂ O ₃	12.9	14.1	11.8	12.8	13.0	12.8
Fe ₂ O ₃	1.7	2.0	1.0	1.1	1.2	1.2
FeO	< .05	.13	< .05	< .05	.12	< .05
MgO	.31	.56	.19	.31	.42	.31
CaO	.71	1.5	.68	.46	.44	.82
Na ₂ O	2.8	2.9	3.5	2.8	2.6	2.8
K ₂ O	4.8	4.2	3.3	5.4	5.8	4.8
H ₂ O	6.5	7.8	10.1	7.6	7.2	9.2
TiO ₂	.21	.35	.17	.18	.22	.22
P ₂ O ₅	.01	.02	.00	.00	.00	.00
MnO	.06	.06	.06	.06	.06	.06
CO ₂	< .05	< .05	< .05	< .05	< .05	< .05
Sum	100	100	100	100	100	100
Equivalent U	0.002	0.001	0.002	0.002	0.003	0.004

Table 2.--Chemical analyses, in percent, of tuff from U12e.06
tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No.-----	E6-680L	E6-700L	E6-800R	E6-900R	E6-954R	E6-1034R
Laboratory No.-----	157596	157620	157619	157618	157597	157598
Lithologic subunit----	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₂	T1t ₄ H ₂	T1t ₄ H ₂	T1t ₄ H ₂
SiO ₂	68.50	67.20	66.90	69.60	69.10	70.10
Al ₂ O ₃	12.4	12.5	13.1	12.4	13.5	11.8
Fe ₂ O ₃	1.2	1.2	1.8	1.3	1.5	1.3
FeO	< .05	.09	.07	< .05	< .05	< .05
MgO	.25	.33	.40	.34	.48	.38
CaO	1.2	.90	.94	1.1	1.0	1.4
Na ₂ O	2.4	2.4	2.7	2.4	2.3	2.2
K ₂ O	4.4	4.6	4.6	4.1	4.4	3.8
H ₂ O	9.0	10.0	8.8	8.4	7.0	8.8
TiO ₂	.20	.22	.26	.22	.26	.12
P ₂ O ₅	.01	.00	.01	.00	.01	.00
MnO	.08	.06	.06	.08	.11	.06
CO ₂	< .05	< .05	< .05	< .05	< .05	< .05
Sum	100	100	100	100	100	100
Equivalent U	0.002	0.003	0.002	0.003	0.002	0.001

Table 2.--Chemical analyses, in percent, of tuff from U12e.06
tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No.-----	E6-1100L	E6-1170L	E6-1200R	E6-1296L	E6-1400R
Laboratory No.-----	157617	157599	157616	157615	157613
Lithologic subunit----	T1t ₄ H ₂	T1t ₄ H ₂	T1t ₄ H ₂	T1t ₄ H ₂	T1t ₄ H ₂
SiO ₂	68.90	71.10	70.60	71.00	72.70
Al ₂ O ₃	12.3	11.2	11.5	11.1	10.3
Fe ₂ O ₃	1.7	2.1	1.9	1.8	1.6
FeO	.07	< .05	< .05	.12	.15
MgO	.90	.44	.57	.64	.47
CaO	1.4	.94	1.4	1.5	1.1
Na ₂ O	1.2	2.0	1.4	1.1	1.4
K ₂ O	4.6	4.1	3.8	3.5	3.5
H ₂ O	8.5	7.3	8.7	8.6	8.2
TiO ₂	.16	.10	.16	.16	.11
P ₂ O ₅	.00	.01	.01	.01	.00
MnO	.04	.05	.04	.06	.04
CO ₂	< .05	< .05	< .05	< .05	< .05
Sum	100	99	100	100	100
Equivalent U	0.003	0.002	0.002	0.003	0.002

Table 2.--Chemical analyses, in percent, of tuff from U12e.06
tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No.-----	E6-1466La	E6-1466Lb	E6-1500L	E6-1600R	E6-1700R
Laboratory No.-----	157600	157601	157612	157611	157610
Lithologic subunit----	T1t ₄ H ₂	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₁
SiO ₂	68.10	66.90	68.90	67.60	67.20
Al ₂ O ₃	13.5	15.0	12.4	12.9	13.7
Fe ₂ O ₃	2.1	1.6	1.1	1.2	1.3
FeO	.12	< .05	.12	.12	.08
MgO	.47	.35	.52	.62	.42
CaO	1.4	1.2	1.6	1.8	1.9
Na ₂ O	1.6	2.0	1.2	1.0	1.4
K ₂ O	4.6	7.0	4.8	5.2	5.2
H ₂ O	7.4	5.5	8.9	9.2	8.4
TiO ₂	.20	.26	.22	.24	.24
P ₂ O ₅	.01	.01	.00	.00	.01
MnO	.08	.08	.05	.06	.06
CO ₂	< .05	< .05	< .05	< .05	< .05
Sum	100	100	100	100	100
Equivalent U	0.002	0.005	0.002	0.002	0.003

Table 2.--Chemical analyses, in percent, of tuff from U12e.06
tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No.-----	E6-1800R	E6-1900R	E6-1995R	E6-2048R	E6-2085R
Laboratory No.-----	157609	157608	157607	157606	157605
Lithologic subunit----	T1t ₄ H ₁	T1t ₄ H ₂	T1t ₄ H ₁	T1t ₄ H ₂	T1t ₄ H ₂
SiO ₂	68.20	69.20	67.60	68.80	70.70
Al ₂ O ₃	12.5	12.4	13.3	12.4	11.2
Fe ₂ O ₃	1.3	1.4	1.6	2.8	2.0
FeO	.07	< .05	< .05	< .05	< .05
MgO	.37	.58	.54	.41	.25
CaO	1.0	.72	.73	.65	.46
Na ₂ O	2.5	2.8	2.9	2.4	2.7
K ₂ O	4.1	3.2	4.3	4.6	3.7
H ₂ O	9.0	9.3	8.0	7.6	8.2
TiO ₂	.20	.19	.28	.27	.12
P ₂ O ₅	.01	.01	.01	.02	.01
MnO	.05	.05	.10	.04	.04
CO ₂	< .05	< .05	< .05	< .05	< .05
Sum	99	100	99	100	99
Equivalent U	0.002	0.001	0.001	0.002	0.002

Table 2.---Chemical analyses, in percent, of tuff from U12e.06
tunnel, Nevada Test Site, Nye County, Nev.---Continued

Sample No.-----	E6-2119R	E6-2200Ra	E6-2200Rb
Laboratory No.-----	157604	157602	157603
Lithologic subunit-----	T1t ₄ H ₂	T1t ₄ H ₂	T1t ₄ H ₂
SiO ₂	69.40	70.40	68.30
Al ₂ O ₃	11.9	11.2	12.0
Fe ₂ O ₃	1.5	2.1	1.8
FeO	< .05	.12	< .05
MgO	.34	.28	.36
CaO	.57	.44	.58
Na ₂ O	3.2	2.8	3.3
K ₂ O	3.6	3.9	3.6
H ₂ O	9.2	8.2	9.6
TiO ₂	.16	.11	.15
P ₂ O ₅	.00	.01	.00
MnO	.05	.04	.04
CO ₂	< .05	< .05	< .05
Sum	100	100	100
Equivalent U	0.001	0.001	0.002

Table 3.--Semiquantitative spectrographic analyses of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev.

[Semiquantitative spectrographic analysis by N. M. Conklin, USGS. Looked for but not found: P, Ag, As, Au, B, Bi, Cd, Co, Dy, Er, Eu, Gd, Ge, Hf, Hg, Ho, In, Ir, Li, Lu, Mo, Ni, Os, Pd, Pr, Pt, Re, Rh, Ru, Sb, Sc, Sm, Ta, Tb, Te, Th, Tl, Tm, U, W, Zn. Figures are reported to the nearest number in the series 7, 3, 1.5, 0.7, 0.3, 0.15, etc., in percent. These numbers represent midpoints of group data on geometric scale. Comparisons of this type of semiquantitative results with data obtained by quantitative methods, either chemical or spectrographic, show that the assigned group includes the quantitative value about 60 percent of the time. d - Barely detected and concentration uncertain. 0 - Looked for but not detected.]

Sample No.-----	E6-61R	E6-192R	E6-285L	E6-400L	E6-480R	E6-600L
Laboratory No.-----	286947	286948	286976	286975	286967	286974
Lithologic subunit--	Tlt ₄ G	Tlt ₄ G	Tlt ₄ G	Tlt ₄ H ₁	Tlt ₄ H ₁	Tlt ₄ H ₁
Ba	.07	.07	.015	.003	.007	.007
Be	.0007	.0003	.0003	.0003	.0003	.0003
Ce	d	d	d	0	.03	d
Cr	0	.0003	d	0	0	0
Cu	.0003	.0003	0	0	0	0
Ga	.003	.003	.003	.003	.003	.003
La	.007	.007	.007	.007	.007	.007
Nb	.003	.0015	.0015	.0015	.003	.003
Nd	0	0	0	0	0	0
Pb	.007	.003	.003	.003	.003	.003
Sn	0	0	0	0	0	0
Sr	.015	.07	.007	.003	.007	.007

Table 3.--Semiquantitative spectrographic analyses of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No.-----	E6-61R	E6-192R	E6-285L	E6-400L	E6-480R	E6-600L
Laboratory No.-----	286947	286948	286976	286975	286967	286974
Lithologic subunit--	T1t ₄ G	T1t ₄ G	T1t ₄ G	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₁
V	.0015	.003	0	0	0	0
Y	.003	.003	.003	.003	.003	.003
Yb	.0003	.0003	.0003	.0003	.0003	.0003
Zr	.015	.015	.015	.015	.03	.03

Table 3. --Semiquantitative spectrographic analyses of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev. --Continued

Sample No.-----	E6-680L	E6-700L	E6-800R	E6-900R	E6-954R	E6-1034R
Laboratory No.-----	286949	286973	286972	286971	286950	286951
Lithologic subunit--	Tlt ₄ H ₁	Tlt ₄ H ₁	Tlt ₄ H ₂	Tlt ₄ H ₂	Tlt ₄ H ₂	Tlt ₄ H ₂
Ba	.007	.007	.03	.007	.03	.007
Be	.0007	.0003	.0003	.0003	.0007	.0007
Ce	d	0	0	0	d	0
Cr	d	d	.0007	.0003	.0003	0
Cu	.0003	0	.0003	.0003	.0007	.00015
Ga	.003	.003	.003	.003	.003	.003
La	.007	.007	.007	.007	.015	.007
Nb	.003	.0015	.0015	.0015	.003	.003
Nd	0	0	0	0	d	0
Pb	.003	.003	.003	.003	.003	.003
Sn	0	0	0	0	0	0
Sr	.007	.007	.03	.015	.03	.007
V	0	0	0	0	.0015	0
Y	.003	.003	.003	.003	.007	.003
Yb	.0003	.0003	.0003	.0003	.0007	.0003
Zr	.03	.015	.015	.03	.03	.03

Table 3.--Semiquantitative spectrographic analyses of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No.-----	E6-1100L	E6-1170L	E6-1200R	E6-1296L	E6-1400R	E6-1466La
Laboratory No.-----	286970	286952	286969	286968	286966	286953
Lithologic subunit--	Tlt ₄ H ₂	Tlt ₄ H ₂	Tlt ₄ H ₂	Tlt ₄ H ₂	Tlt ₄ H ₂	Tlt ₄ H ₂
Ba	.007	.007	.015	.007	.007	.015
Be	.0007	.0007	.0003	.0007	.0007	.0003
Ce	0	0	d	0	0	d
Cr	.0003	d	.0003	.0003	0	.0003
Cu	.0003	.00015	.0003	.0003	.0003	.0003
Ga	.003	.003	.003	.003	.003	.003
La	.007	.007	.007	.007	.007	.007
Nb	.003	.003	.003	.003	.003	.003
Nd	0	d	0	0	0	d
Pb	.003	.007	.003	.003	.007	.007
Sn	0	.0015	0	d	d	d
Sr	.007	.007	.015	.007	.007	.015
V	0	0	0	0	0	0
Y	.003	.015	.007	.007	.007	.007
Yb	.0003	.0007	.0007	.0007	.0007	.0007
Zr	.03	.07	.03	.07	.07	.07

Table 3.--Semiquantitative spectrographic analyses of tuff from U12e.06
tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No. -----	E6-1466Lb	E6-1500L	E6-1600R	E6-1700R	E6-1800R	E6-1900R
Laboratory No. -----	286954	286965	286964	286963	286962	286961
Lithologic subunit--	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₁	T1t ₄ H ₂
Ba	.03	.007	.007	.015	.03	.007
Be	.0003	.0003	.0003	.0003	.0003	.0003
Ce	.03	0	0	0	d	d
Cr	d	d	d	d	d	d
Cu	.00015	.00015	0	0	.0003	.00015
Ga	.003	.003	.003	.003	.003	.003
La	.015	.007	.007	.015	.007	.007
Nb	.0015	.0015	.0015	.0015	.0015	.003
Nd	d	0	0	d	0	0
Pb	.007	.003	.003	.003	.003	.003
Sn	0	0	0	0	0	0
Sr	.03	.007	.007	.03	.03	.007
V	.0015	0	0	0	0	0
Y	.003	.003	.003	.003	.003	.003
Yb	.0003	.0003	.0003	.0003	.0003	.0003
Zr	.03	.015	.015	.015	.015	.015

Table 3.--Semiquantitative spectrographic analyses of tuff from U12e.06
tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No.-----	E6-1995R	E6-2048R	E6-2085R	E6-2119R	E6-2200Ra
Laboratory No.-----	286960	286959	286958	286957	286955
Lithologic subunit--	T1t ₄ H ₁	T1t ₄ H ₂	T1t ₄ H ₂	T1t ₄ H ₂	T1t ₄ H ₂
Ba	.015	.03	.007	.015	.007
Be	.0003	.0007	.0007	.0007	.0007
Ce	d	d	d	d	0
Cr	.0003	.0007	0	.0003	d
Cu	.0003	.0007	.00015	.0003	.0003
Ga	.003	.003	.003	.003	.003
La	.007	.007	.007	.007	.007
Nb	.003	.003	.003	.003	.003
Nd	0	d	d	0	d
Pb	.003	.003	.007	.003	.007
Sn	0	d	d	0	.0015
Sr	.015	.03	.007	.015	.007
V	.0015	.003	0	0	0
Y	.003	.007	.007	.007	.007
Yb	.0003	.0007	.0007	.0007	.0007
Zr	.015	.03	.07	.03	.07

Table 3.--Semiquantitative spectrographic analyses of tuff from U12e.06 tunnel, Nevada Test Site, Nye County, Nev.--Continued

Sample No.-----	E6-2200Rb	Standard spectrographic sensitivity
Laboratory No.-----	286956	
Lithologic subunit----	Tlt ₄ H ₂	
Ba	.007	.0002
Be	.0007	.0001
Ce	0	.02
Cr	.0003	.0001
Cu	.0003	.0001
Ga	.003	.0002
La	.007	.002
Nb	.003	.001
Nd	0	.01
Pb	.003	.001
Sn	0	.001
Sr	.007	.002
V	0	.001
Y	.007	.001
Yb	.0007	.0005
Zr	.07	.001

The tuff of subunit G consists of fine to lapilli pumice, phenocrysts, and minor amounts of lithic fragments in a vesicular aphanitic matrix (table 1). Pumice makes up from 15 to 20 percent of the rock. Irregular vesicles make up 10.7 to 25.4 percent of the tuffs. The phenocrysts make up 8.6 to 18.7 percent of the tuffs and in order of abundance are potassium feldspar, quartz, plagioclase, magnetite, and biotite. They are euhedral to subhedral. Lithic fragments are fine and are made up principally of quartzite with other metamorphic or volcanic rock. The matrix, which includes the fine to lapilli pumice, forms as much as 85 percent of the tuff and is shown by X-ray analyses (table 1) to consist predominantly of heulandite, with very minor or trace amounts to beta-cristobalite and clay minerals. The X-ray patterns of the clay fractions from the tuff are ill-defined but indicate that possibly illite or mixed-layer montmorillonite, or mixtures of both are present. The modal (volume percentage) and X-ray analyses of the tuff of subunit G are given in table 1. Some secondary spherulitic chalcedony is visible in thin sections of the tuff. Hematite is abundant and accounts for the red color of the rock. It occurs as a coating on the pumice and as a cementing material. Silica, as beta-cristobalite, is probably a minor cementing agent. The heulandite, beta-cristobalite, and clay minerals are alteration products of an originally pumiceous material.

Chemical analyses of the samples from subunit G are given in table 2 and semiquantitative spectrographic analyses in table 3. The chemical composition and trace element content of the tuff of subunit G are similar to other tuffs of the Oak Spring Formation from the Nevada Test Site.

PHYSICAL PROPERTIES

Measurements were made of porosity, rock or bulk density, grain density, hardness, and unconfined compressive strength of 30 samples from subunits H and G in the U12e.06 tunnel. The natural-state of the samples was not preserved, so water content and natural-state bulk densities were not determined. Locations of the samples are shown on figure 4.

The laboratory procedure used to determine the porosity, rock or bulk density, and grain density is the same, with the omission of the steps necessary for determining water content and natural-state density, are described by Diment and others (1959, p. 51-53). The results of these laboratory tests are given in table 4.

Hardness of the tuffs of subunits H and G was tested using a Shore scleroscope. In this test the height of rebound of the scleroscope point from the rock surface is read in terms of arbitrary units on a scale of 140 divisions, with the value of 100 divisions representing the rebound from hardened, pure-carbon steel (Wuerker, 1956). Results of these hardness tests on samples from subunits H and G are given in table 4.

Table 4. --Physical properties of tuffs from U12e.06 tunnel, Nevada Test Site, Nye County, Nev.

[Analyses of porosity, dry bulk density, and grain density by C. H. Roach, G. R. Johnson, and J. G. McGrath, USGS. Determination of hardness and unconfined compressive strengths by J. C. Thomas, USGS. Sample number indicates footage from tunnel entrance referred to Holmes and Narver, Inc. survey followed by letter R or L indicating right or left wall. R or L followed by lower case a or b indicates two samples taken from approximately the same location but at different heights above track level.]

Sample No.	Rock subunit of Tunnel Bed 4	Porosity (P) (percent)	Dry bulk density (Dbd) (g/cc)	Grain density (Dg) (g/cc)	Shore hardness	Unconfined compressive strength (psi)
E6-61R	G	37.7	1.54	2.47	18	2,600
E6-192R	G	32.3	1.67	2.47	13	3,900
E6-285L	G	33.5	1.58	2.37	32	3,900
Avg	G	34.5	1.60	2.44	21	3,500
E6-400L	H ₁	38.3	1.50	2.44	26	2,600
E6-480R	H ₁	38	1.50	2.43	24	3,900
E6-600L	H ₁	42.8	1.38	2.42	19	2,600
E6-680L	H ₁	42.9	1.38	2.41	22	1,300
E6-700L	H ₁	42.3	1.38	2.39	21	2,600
E6-800R	H ₂	40.2	1.47	2.46	17	6,600
E6-900R	H ₂	35.8	1.57	2.45	23	2,600
E6-954R	H ₂	31	1.72	2.49	24	2,600
E6-1034R	H ₂	32	1.64	2.42	32	6,600
E6-1100L	H ₂	31.8	1.60	2.35	23	3,900

Table 4. --Physical properties of tuffs from U12e.06 tunnel, Nevada Test Site, Nye County, Nev. --Continued

Sample No.	Rock subunit of Tunnel Bed 4	Porosity (P) (percent)	Dry bulk density (Dbd) (g/cc)	Grain density (Dg) (g/cc)	Shore hardness	Unconfined compressive strength (psi)
E6-1170L	H ₂	32.8	1.67	2.48	29	3,900
E6-1200R	H ₂	30.5	1.59	2.29	22	2,600
E6-1296L	H ₂	25.2	1.77	2.37	38	5,300
E6-1400R	H ₂	43.2	1.35	2.37	13	No core
E6-1466La	H ₂	45.3	1.32	2.42	8	1,300
E6-1466Lb	H ₁	36.4	1.57	2.46	13	1,300
E6-1500L	H ₁	46.1	1.49	2.40	26	2,600
E6-1600R	H ₁	25.8	1.74	2.35	43	No core
E6-1700R	H ₁	31.4	1.58	2.31	31	3,900
E6-1800R	H ₁	28.9	1.70	2.39	32	3,900
E6-1900R	H ₂	31.8	1.64	2.41	29	3,900
E6-1995R	H ₁	32.4	1.65	2.44	23	3,900
E6-2048R	H ₂	39	1.52	2.50	16	1,300
E6-2085R	H ₂	30.7	1.67	2.41	35	2,600
E6-2119R	H ₂	35	1.56	2.40	19	2,600
E6-2200Ra	H ₂	31.1	1.65	2.40	46	No core
E6-2200Rb	H ₂	36	1.55	2.43	24	3,900
Avg	H	35.4	1.56	2.41	25	3,300

Unconfined compressive strength of 27 of the 30 samples from subunits H and G were made on 1 inch long by 1 inch in diameter plugs from the rock samples. The plugs were inserted under a hydraulic jack equipped with a pressure gauge. The point at which the rock fails under pressure was recorded to the nearest 1,000 pounds; this was recalculated to pounds per square inch for the 1-inch diameter plug tested. Results of these tests on the 27 samples are given in table 4.

GAMMA-RADIOACTIVITY

By C. M. Bunker

A gamma-radioactivity survey of tunnel U12e.06 was made on October 20, 1960, to determine the natural radioactivity of lithologic units penetrated by the tunnel. The data obtained may also be used as a basis for determining the distribution of anomalous gamma-radioactivity from radioisotopes produced by a proposed underground nuclear explosion in a chamber at the end of the tunnel.

The survey was made with a portable scintillation-type detector that was calibrated with a radium-226 source to obtain quantitative data on the radioactivity emitted by radioisotopes in the rock. The radioactivity values obtained during the survey are probably accurate to within plus or minus 10 percent. Factors that contribute to the error include statistical error in the readings during both calibration and surveying, variations in geometry between the detector and the wall rock, the effect of shielding from steel sets and lagging in the tunnel, and drift in the response of the instrument during the survey.

Gamma-radioactivity measurements were started at 0+40, in the U12e.06 tunnel near the intersection with the U12e main drift and were terminated at station 20+63 (fig. 4). Measurements were generally made at a height of 4 to $4\frac{1}{2}$ feet above the level of the tunnel floor; a few exceptions occurred where wood lagging prevented measurements at that height. The measurements were made at intervals

of 20 feet and were indexed to station locations that had been established by Holmes and Narver, Inc. surveys.

The natural gamma-radioactivity observed in the tunnel ranges from 0.020 to 0.033 milliroentgens per hour (mr per hr). The range of radioactivity exceeds the range of error; therefore, the changes in radioactivity observed in the tunnel are considered real. The radioactivity is essentially the same in subunits G and H of Tunnel Bed 4, except in fractured and faulted zones. The observed gamma-radioactivity seems to be related, in general, to the number of faults that intersect the tunnel. The radioactivity is greatest where faults are most numerous, for example between 8+00 to 14+80, where a maximum value of 0.033 mr per hr was observed. The radioactivity in relatively unfaulted sections of the tunnel, 0+40 to 8+00, is in the range of 0.020 to about 0.025 mr per hr; and the radioactivity in slightly faulted sections, 14+80 to 20+63, is in the range of 0.024 to 0.029 mr per hr.

The source of the anomalous gamma-radioactivity in the section between stations 8+00 and 14+80 has not been determined. Several water seeps were observed in this section of the tunnel, and the orientation of the fractures and faults from which water is seeping does not exclude the possibility of water migration from the northeast in the vicinity of tunnel U12b. Therefore, the anomalous gamma-radioactivity may be caused by water-borne radioisotopes resulting from one or more nuclear explosions in the U12b tunnel system.

The gamma-radioactivity in subunits G and H is essentially the same; therefore, gamma-radioactivity surveys cannot be used in this tunnel to aid stratigraphic discrimination. Anomalous gamma-radioactivity is apparently related to the amount of fracturing and faulting; the highest radioactivity is found where these are more prevalent. Water seeps were observed in the fractured and faulted zone between 8+00 and 14+80. The anomalous radioactivity may be caused by fluid-borne radioisotopes. Except for the zone between 8+00 and 14+80 where the radioactivity is anomalously high, the natural radioactivity is low enough to prevent interference with studies of the distribution of gamma-emitting radioisotopes resulting from underground nuclear explosions in the tunnel system.

REFERENCES

- Diment, W. H., and others, 1959, Geological Survey investigations in the U12b.03 and U12b.04 tunnels, Nevada Test Site: U.S. Geol. Survey TEM-996, 75 p.
- Gibbons, A. B., Hinrichs, E. N., Hansen, W. R., and Lemke, R. W., 1960, Preliminary geologic map of the Tippipah Spring NW quadrangle, Nye County, Nevada: U.S. Geol. Survey TEI-754, open-file rept.
- Hansen, W. R., and Lemke, R. W., 1957, Geology of the USGS and Rainier tunnel areas, Nevada Test Site: U.S. Geol. Survey TEI-716, open-file rept.
- Hinrichs, E. N., and Orkild, P. P., 1961, Eight members of the Oak Spring formation, Nevada Test Site and vicinity, Nye and Lincoln Counties, Nevada, in Short papers in the geologic and hydrologic sciences: U.S. Geol. Survey Prof. Paper 424-D, art. 327.
- McKeown, F. A., and Dickey, D. D., 1961, Interim report on geologic investigations of U12e tunnel system, Nevada Test Site, Nye County, Nevada: U.S. Geol. Survey TEI-772, open-file rept.
- Mumpton, F. A., 1958, Clinoptilolite redefined [abs.]: Geol. Soc. America Bull., v. 69, no. 12, pt. 2, p. 1620.

- Shapiro, Leonard, and Brannock, W. W., 1956, Rapid analysis of silicate rocks: U.S. Geol. Survey Bull. 1036-C, p. 19-56.
- Wuerker, R. G., 1956, Annotated tables of strength and elastic properties of rocks: Am. Inst. Mining Metall. Petroleum Engineers, Petroleum Branch, Paper 663-G, 10 p.