780

OFFICIAL USE ONLY

U. S. GEOLOGICAL SURVEY
Field Library
Albuquerque, New Mexico

THE GARM-LAMOREAUX MINE

LEMHI COUNTY, IDAHO

By Frank C. Armstrong and Paul L. Weis

Trace Elements Memorandum Report 780

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

OFFICIAL USE ONLY

metadc502254

OFFICIAL USE ONLY

Geology and Mineralogy

This document consists of 14 pages,
plus 2 figures.
Series A

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

THE GARM-LAMOREAUX MINE, LEMHI COUNTY, IDAHO*

By

Frank C. Armstrong and Paul L. Weis

January 1954

Trace Elements Memorandum Report 780

This preliminary report is distributed
without editorial and technical review
for conformity with official standards
and nomenclature. It is not for public
inspection or quotation.

*This report concerns work done on behalf of the Division
of Raw Materials of the U. S. Atomic Energy Commission.

OFFICIAL USE ONLY

OFFICIAL USE ONLY

2

USGS - TEM-780

GEOLOGY AND MINERALOGY

<u>Distribution (Series A)</u>	<u>No. of copies</u>
American Cyanamid Company, Winchester	1
Argonne National Laboratory	1
Atomic Energy Commission, Washington.	1
Battelle Memorial Institute, Columbus	1
Carbide and Carbon Chemicals Company, Y-12 Area	1
Division of Raw Materials, Albuquerque.	1
Division of Raw Materials, Butte.	1
Division of Raw Materials, Denver	1
Division of Raw Materials, Douglas.	1
Division of Raw Materials, Hot Springs.	1
Division of Raw Materials, Ishpeming.	1
Division of Raw Materials, New York	6
Division of Raw Materials, Phoenix.	1
Division of Raw Materials, Richfield.	1
Division of Raw Materials, Salt Lake City	1
Division of Raw Materials, Washington	3
Dow Chemical Company, Pittsburgh	1
Exploration Division, Grand Junction Operations Office.	1
Grand Junction Operations Office.	1
Technical Information Service, Oak Ridge.	6
Tennessee Valley Authority, Wilson Dam.	1
U. S. Geological Survey:	
Alaskan Geology Branch, Menlo Park	1
Fuels Branch, Washington.	1
Geochemistry and Petrology Branch, Washington	1
Geophysics Branch, Washington	1
Mineral Deposits Branch, Washington	2
E. H. Bailey, Menlo Park.	1
K. L. Buck, Denver.	1
J. R. Cooper, Denver.	1
N. M. Denson, Denver.	1
C. E. Dutton, Madison	1
R. P. Fischer, Grand Junction	1
L. S. Gardner, Albuquerque.	1
M. R. Klepper, Washington	1
A. H. Koschmann, Denver	1
R. A. Laurence, Knoxville	1
D. M. Lemmon, Washington.	1
J. D. Love, Laramie	1
V. E. McKelvey, Menlo Park.	1
W. L. Emerick, Plant City.	1
R. J. Roberts, Salt Lake City	1
Q. D. Singewald, Beltsville	1
J. F. Smith, Jr., Denver.	1
A. E. Weissenborn, Spokane.	2
TEPCO, Denver	2
TEPCO, RPS, Washington.	2
(Including master)	62

OFFICIAL USE ONLY

OFFICIAL USE ONLY

3

CONTENTS

	Page
Abstract.	4
Introduction.	5
Development	6
Geology	7
Radioactivity	8
Samples	9
Conclusions	11
Literature cited.	14
Unpublished reports	14

ILLUSTRATIONS

- Figure 1. Surface sketch map of the Garm-Lamoreaux mine,
Lemhi County, Idaho In envelope
2. Composite underground geologic map, Garm-
Lamoreaux mine, Idaho. In envelope

TABLE

- Table 1. Samples from the Garm-Lamoreaux property, Lemhi
County, Idaho 10

OFFICIAL USE ONLY

4

THE GARM-LAMOREAUX MINE, LEMHI COUNTY, IDAHO

By Frank C. Armstrong and Paul L. Weis

ABSTRACT

The Garm-Lemoreaux property, Lemhi County, Idaho is known to have uraninite and zippeite on two of its dumps. The property has been explored by five adits, two of which are now caved, and one of which is partly caved. The country rock is schistose micaceous quartzite and argillaceous quartzite of Belt age. An east-west fault cuts the quartzite, and the Lamoreaux vein, a gold-sulfide-quartz vein, occurs in the fault. The uranium minerals are believed to have come from the vein, on the now inaccessible No. 3 level.

An alidade and plane-table map was made to tie in the positions of the five underground workings. The lowest adit, the first 200 feet of the No. 2 tunnel and the Hardrock tunnel were mapped. Maps of the other workings made by Gilbert in 1933 were combined with the writer's maps.

Samples were collected from the radioactive parts of the number two and number three dumps. Chemical analyses of the samples showed a range of from .001 to .54 percent uranium. It appears probable that at least some uranium could have been leached by sulfate-bearing waters in the dump material. The presence of as much as .54 percent uranium in one sample from the No. 3 dump suggests that an exploration program would be advisable. Recommended exploration would begin by reopening No. 3 level, examining the Lamoreaux vein, and drifting east and west along the vein.

OFFICIAL USE ONLY

5

INTRODUCTION

The Garm-Lamoreaux mine is in sec. 31, T. 26 N., R. 21 E., Lemhi County, Idaho. It is about 11 miles northwest of North Fork, Idaho, on Allan Creek, a small south-flowing tributary of Hughes Creek. The property is a group of unpatented claims owned by the estate of Ira Lamoreaux, deceased, for which Ralph E. Yates, 631 South Fourth Street, Springfield, Ill., is the agent. G. I. Hurley of Salmon, Idaho, is the local manager of the property. Dr. J. E. Goggins and Mr. Keith Evarts, both of Salmon, Idaho, had a lease on the property in the summer of 1953.

D. C. Gilbert (1933) examined the mine for gold in 1933 and made a map of the accessible underground workings. J. S. Vhay (1950) and A. F. Trites and E. W. Tooker (1952), all of the U. S. Geological Survey, examined the property for radioactivity in 1949 and 1951, respectively. In August and September 1953 the writers spent four days at the property, the last day in company with Messrs. John D. Bradley, Roger H. McConnel, and Charles Hathhorn of the Bradley Mining Company. At the request of Dr. Goggins, the Bradley Mining Company was considering participating in Goggins and Evarts' lease.

OFFICIAL USE ONLY

6

DEVELOPMENT

The deposit has been developed by five adits totaling over 2,900 feet in length. The four upper tunnels were driven previous to the start of the present lease. The lowest adit is being driven by Goggins and Everts to intersect the downward projection of the Lamoreaux vein. At the time of the writers' examination, work on the lowest level had been discontinued temporarily. The approximate lengths of the adits and elevations (datum assumed) of their portals are as follows:

	Length (feet)	Elevation (feet)
Lowest tunnel	690	4,752
Tunnel No. 3	1,160†	5,000
Tunnel No. 2	445†	5,092
Tunnel No. 1	195 (?)	5,146
Hardrock Tunnel	445†	-5,186

The writers made a surface sketch map by plane table and telescopic alidade tying the five adits together, and made Brunton and tape geologic maps of the lowest and Hardrock tunnels. The portal of Tunnel No. 2 was partially caved, but Armstrong and McConnel were able to map the first 200 feet. The rest of the workings were inaccessible due to cave-ins. In 1933 Gilbert was able to map practically all of Tunnels Nos. 2 and 3, but Tunnel No. 1 was caved. Gilbert's and the writers' work have been combined to produce figures 1 and 2. Since Gilbert made his examination, Tunnel No. 3 has been advanced about 270 feet. In 1949, Whay entered the first 300 feet of Tunnel No. 3 at which point there was a cave. He did no mapping.

OFFICIAL USE ONLY

7

GEOLOGY

The area is underlain by micaceous, schistose quartzite and argillaceous quartzite of the pre-Cambrian Belt series. Prominent schistosity in the quartzite strikes north to northeast and dips steeply to the east. Numerous small faults and brecciated zones are parallel and subparallel to the schistosity. Where bedding was definitely recognized it strikes approximately east and dips 45° to 60° south. In only one place, on the lowest level, was it thought that the beds were overturned.

Both Gilbert (1933) and Hurley (oral communication) have described the Lamoreaux vein as a fractured quartz vein containing a little pyrite, galena, and free gold. In Tunnel No. 1, Gilbert (1933) reports the vein to be $3\frac{1}{2}$ feet thick. The vein occurs in a fault that appears to strike east in Tunnels No. 1 and No. 2 and northwest in Tunnel No. 3. The dip of the fault appears to be nearly vertical between Tunnels No. 1 and No. 2 and about 45° NE between Tunnels No. 2 and No. 3; below Tunnel No. 3 the dip is reported to be 87° NE. G. I. Hurley reports the fault zone to be as much as 9 feet thick in Tunnel No. 3. The strike of the fault suggests that the Lamoreaux vein is similar to the veins at 310 feet and the end of the Hardrock Tunnel and is not related to the faults that approximate the attitude of the schistosity. Vein material on the dumps, reported to be from the Lamoreaux vein, consists of fractured, slightly iron-stained quartz containing a little chlorite and sparse pyrite and galena.

OFFICIAL USE ONLY

8

In the northwest corner of Tunnel No. 3 dump, brilliant yellow efflorescence was found on several dark siliceous vein fragments and all of these fragments showed abnormal radioactivity. Mineralogists of the U. S. Geological Survey identified uraninite in the dark siliceous vein material and identified the yellow efflorescence as zippeite. Both identifications were by X-ray diffraction patterns. A dark gray to black, powdery material occurs in minute veinlets in and coating the same and other vein fragments, but the fragments do not show sufficient abnormal radioactivity for all of the powdery material to be sooty pitchblende.

RADIOACTIVITY

The radiation background in the vicinity of the mine is 0.016 milliroentgens per hour. A traverse of Tunnel No. 3 dump for abnormal radioactivity showed a 225 square foot area to be more than ten times background; a 1,000 square foot area, more than five times background; and the northern half of the dump, more than twice background (fig. 1). The lack of vegetation and marks of old ties and track suggest that the north half of the dump is some of the last, though not the very last, rock mined from the adit. A similar traverse of Tunnel No. 2 dump showed a small area on the south part of the dump to be about twice background (fig. 1). The lowest and Hardrock adits showed no abnormal radioactivity.

SAMPLES

The writers took two samples from Tunnel No. 3 dump and two from Tunnel No. 2 dump. Samples Nos. FCA-10A and FCA-14A were taken from the part of dump No. 3 that showed ten times background. Judging from the radioactivity shown by many other pieces, other samples with a uranium content similar to No. FCA-10A (0.54 percent) could have been taken. The samples from Tunnel No. 2 dump are believed to be representative of the abnormally radioactive south part of the dump.

In 1949 Vhay (1950) took four samples from the property, and in 1950 Trites and Tooker (1952) took six samples. The results of the analyses of the 14 samples are shown below in table 1.

In addition to the above samples, Mr. Kenneth White of Sweet Home, Oreg., sent two samples to the U. S. Bureau of Mines at Albany, Oreg., for radioactivity analysis. Through the courtesy of Mr. Keith Evarts a copy of the Bureau's reply, signed by A. H. Robertson, Acting Chief, Technical Services Branch, was given to the writers. Robertson's reply says in part: "The uranium contents as determined radiometrically, are as follows:

Sample	Percent eU
1	1.00
2	0.08

Sample 1 consists of quartz with small amounts of associated chlorite, kaolinite, pyrite, barite and a hydrous iron oxide. The uranium mineral is pitchblende. It occurs intimately associated with chlorite as minute veinlets and encrustations in fractures in quartz.

Table 1.--Samples from the Garm-Lamoreaux property, Lemhi County, Idaho

Sample Number	Location	Description	Equivalent Uranium (percent)	Uranium (percent)	Gold (oz. per ton)	Silver (oz. per ton)
FCA-10A	Northwest part of Tunnel No. 3 dump	Selected radioactive pieces	0.45	0.54	0.15	0.18
FCA-14A	" "	Representative sample of most radioactive part of dump	.042	.055	.12	.14
FCA-12A	South part of Tunnel No. 2 dump	" "	.011	.005	.24	.30
FCA-13A	" "	" "	.011	.006	.40	.38
9-VS-8	Northwest part of Tunnel No. 3 dump	Random sample across dump face	.027	.018	N.D.	N.D.
9-VS-9	" "	Selected material	.024	.008	N.D.	N.D.
9-VS-10	Tunnel No. 2 dump	Yellow-stained quartz and gossan	.015	.005	N.D.	N.D.
9-VL-24	Tunnel No. 3 dump	Fragments of fractured quartz, chlorite, pyrite, and secondary minerals taken for study	.13	.11	N.D.	N.D.
AFT-S5-50	Northeast part of Tunnel No. 3 dump	Composite sample of vein material	.013	.009	N.D.	N.D.
AFT-S2-50	Near center of Tunnel No. 2 dump	Grab sample containing limonite-stained quartz	.007	.005	N.D.	N.D.
AFT-S3-50	" "	" "	.014	.010	N.D.	N.D.
AFT-S4-50	" "	Grab sample of dump material	.003	.001	N.D.	N.D.
AFT-S6-50	North and south parts of Tunnel No. 2 dump	Composite sample of dump material	.003	.001	N.D.	N.D.
AFT-S7-50	Tunnel No. 1 dump	" "	.004	.001	N.D.	N.D.

N.D. = Not determined

All analyses by the U. S. Geological Survey's Trace Elements Laboratory at Denver, Colorado

"Sample 2 is mineralogically similar to Sample 1 except that it contains more barite and much less pitchblende. By tedious methods, it was possible to concentrate enough of the uranium mineral in both of these samples to confirm the identification of pitchblende by X-ray analysis." Mr. Evarts states that both of White's samples came from Tunnel No. 3 dump.

On September 10, 1953, Messrs. L. D. Jarrard and R. Nicolls of the Butte, Mont., sub-office of the Atomic Energy Commission visited the property. A sample they collected from an ore pile at the residence of G. I. Hurley in Salmon, Idaho, reported to be from the mine, assayed 0.47 percent equivalent U_3O_8 and 0.36 percent U_3O_8 .

CONCLUSIONS

Phair and Levine (1953) have shown that "once - [pitchblende] has been partly oxidized by contact with oxygen, either in the air or dissolved in mine waters, - [it] is readily susceptible to solution by H_2SO_4 invariably present in and around sulfide mines." They leached two 2 g splits of a specimen of Katanga pitchblende in 31 ml of 1.84 N and 0.17 N sulfuric acid for 144 hours, and leached 41.00 and 30.46 percent, respectively, of the uranium originally present in the splits. The presence of sparse sulfides in the Garm-Lamoreaux dumps and of pulverulent zippeite $[(UO_2)(SO_4)(OH)_2 \cdot nH_2O]$ on uraninite-bearing fragments of vein material, suggests that the dumps are in the process of being leached by sulfuric acid solutions. The quantity of uranium removed from the dump is not known but in the light of Phair and Levine's findings it could be appreciable. The possibility of substantial leaching of the dump material, together with the rather high uranium

content of the samples collected from the dump appears to indicate a reasonably good possibility of the occurrence of at least some high grade uranium ore underground. The writers believe that this possibility is sufficiently good to justify further investigation of the property as a uranium prospect.

Tunnel No. 3 should be made accessible. The portal has caved since the autumn of 1949 and should not be too difficult to open. From Whay's work it is known that about 300 feet from the portal there is another cave. This cave may extend to the surface for Whay observed surface matter in the caved material. According to Evarts, who has been in Tunnel No. 3, there were only three sets of timber supporting this loose ground which extended 15 or 20 feet along the drift. He believes the cave can be spiled through without much trouble. If it is found too expensive to spile through the cave, a drift can be run to the northeast around the caved area. Because of the lack of detailed information on the location of the workings and the resultant difficulty of re-entering the adit on grade, the length of the by-pass should be kept to a minimum.

Evarts states that the "big fault" mapped by Gilbert (1933) about 90 feet east of the cave, is not likely to be caved, nor is the rest of the adit southwest of the split in the adit (fig. 1). Northeast of the split Evarts thinks there may be cave-ins. If the adit is too badly caved to be cleaned out, crosscuts from both branches of the split in the adit should be driven to the vein (fig. 1).

Because it is not known exactly where the radioactivity occurs in Tunnel No. 3, it is important that as much as possible of the old workings be made accessible for examination. When the level is made accessible a traverse for abnormal radioactivity should be made and the favorable areas sampled. Phair and Levine (1953) have pointed out that uranium may be leached from the walls of old mine workings in the same manner as from old dumps. Therefore, even if the results of this traverse are negative, some drifting along the vein should be done.

If development in Tunnel No. 3 is successful, then Tunnel No. 2 should be reopened and the lowest adit extended to intersect the Lamoresaux vein. The shortest route from the face of the lowest adit to the Lamoresaux vein appears to be N. 40° E. 600 or 700 feet, but because of the incompleteness of the information at hand and the distance between the No. 3 Tunnel and the lowest level, 248 feet, the distance to the vein may be greatly in error.

The Geological Survey has no plans for further work on this specific property. It is recommended that the lessees reopen Tunnel No. 3 and drift on the vein.

OFFICIAL USE ONLY

14

LITERATURE CITED

Phair, George, and Levine, Harry, 1953, Notes on the differential leaching of uranium, radium, and lead from pitchblende in H_2SO_4 solutions: Econ. Geology, v. 48, p. 358-369.

UNPUBLISHED REPORTS

Gilbert, D. C., 1933, Report on the Lamoreaux mine, Gibbonsville district, Lemhi County, Idaho: Unpublished typescript private mining report, 6 p., 2 figs.

Jarrard, L. D. and Nicolls, R., 1953, Preliminary Reconnaissance Report NI-B-45, U. S. Atomic Energy Comm.

Trites, Albert F., and Tooker, Edwin W., 1952, Uranium and thorium deposits in east-central Idaho and southwestern Montana: U. S. Geol. Survey Trace Elements Inv. Rept. 140, p. 21-23.

Vhay, J. S., 1950, Reconnaissance examinations of uranium at six mines, and properties in Idaho and Montana: U. S. Geol. Survey Trace Elements Memo. Rept. 30, p. 6-8.

OFFICIAL USE ONLY

FIGURE I. - SURFACE SKETCH MAP OF THE GARM-LAMOREAUX MINE, LEMHI COUNTY, IDAHO

Topography and geology by
F. C. Armstrong and P. L. Weiss

August and September 1953

August and September 1953

OFFICIAL USE ONLY

FIGURE 2. - COMPOSITE UNDERGROUND GEOLOGIC MAP OF THE GARM-LAMOREAUX MINE, LEMHI COUNTY, IDAHO

50 0 50 100 150 Feet
Datum assumed

Geology by
F. C. Armstrong and P. L. Weis
Hardrock and lowest tunnels
F. C. Armstrong and Roger H. McConnell
first 200 feet of No. 2 Tunnel