2
11-26-80
y/llz

(1)

UCRL- 35078
PREPRINT

CONF-8006102--3

MASTER

The Spent Fuel Test Project, Climax Granite Stock,
Nevada Test Site

L. D. Ramspott

DISCLAIMER
This report was prepared for the U.S. Department of Energy under contract number DE-AC02-79OR21400. It contains information that is preliminary, incomplete, and subject to change without notice. It is not to be distributed outside the Department of Energy, nor is it to be used for any purpose other than that for which it was prepared. The U.S. Government is authorized to reproduce and distribute reprints for government purposes not withstanding any copyright notation that may appear hereon. This report is the property of the U.S. Department of Energy and is loaned to you. It and its contents are not to be distributed outside your agency.

This paper was prepared for submittal to
the Proceedings of the International Symposium for
Environmental Protection, Low Cost Storage
and Energy Savings, Stockholm, SWEDEN

October 24, 1980

This is a preprint of a paper intended for publication in a journal or proceedings. Since changes may be made before publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

21

THE SPENT FUEL TEST PROJECT
CLIMAX GRANITIC STOCK, NEVADA TEST SITE*

L. D. Ramspott
Lawrence Livermore National Laboratory
Livermore, California
U.S.A.

ABSTRACT

The Spent Fuel Test-Climax (SFT-C) is a test of dry geologic storage of spent nuclear reactor fuel. The SFT-C is located at a depth of 420 m in the Climax granitic stock at the Nevada Test Site of the U.S. Department of Energy. Eleven canisters of spent commercial PWR fuel assemblies are to be stored for 3 to 5 years. Additional heat is supplied by electrical heaters, and more than 800 channels of technical information are being recorded. The measurements include rock temperature, rock displacement and stress, joint motion, and monitoring of the ventilation air volume, temperature, and dewpoint.

KEYWORDS

Nuclear Waste Disposal, Spent Fuel Storage, rock mechanics, mined repository for radioactive waste, thermal stress in rock.

TEST DESCRIPTION

The Lawrence Livermore National Laboratory (LLNL) as a participant in the Nevada Nuclear Waste Storage Investigations (NNWSI) program is responsible for the technical direction of a test of geologic storage of spent reactor fuel. This test (generally referred to as the Spent Fuel Test-Climax or SFT-C) is at a depth of 420 m in the Climax granite at the Nevada Test Site. The NNWSI is part of the commercial waste management activities of the National Waste Terminal Storage (NWTS) program of the U.S. Department of Energy (DOE).

At the time the SFT-C was authorized in June 1978, there was no high level nuclear waste in deep geologic storage, even at a demonstration or pilot scale. Furthermore, the only previous such test, Project Salt Vault (Bradshaw and McClain, 1971), was in bedded salt, and no actual experience with deep geologic storage in other rock types existed. At the Nevada Test Site (NTS) of the DOE, there existed facilities both for encapsulating spent fuel assemblies in canisters suitable for underground storage and for a test layout near previously mined workings at a depth of 420 m. Therefore, a test was planned which would have both educational and demonstration value as well as address technical issues of rock response to the waste.

The technical concept for the SFT-C (Ramspott and others, 1979) provides a simulation of the thermal field of a large repository within a 15-m x 15-m repository model cell. The heat sources are 11 canisters of spent commercial PWR fuel assemblies and 6 electrical fuel-simulators in a central canister storage drift. These are supplemented by 10 electrical heaters in each of 2 adjacent heater drifts (Fig. 1). By comparison of the electrical simulators with the spent fuel, it is possible to evaluate the effects of heat alone with heat plus ionizing radiation.

*Work performed under the auspices of the U.S. Department of Energy by the Lawrence Livermore National Laboratory under contract No. W-7405-ENG-48.

FIG. 1. Plan view of the Climax granite spent-fuel-storage test.

Spent fuel emplacement was completed by May 28, 1980, at which time the decay heat from each fuel assembly was about 1550 W. Following encapsulation at a facility about 75 km from the storage site, the canistered fuel was transported and emplaced with a system designed specifically for this test (Duncan and others, 1980). No hot cell was built at the site, and although sufficiently shielded for personnel access at all times, operations at the Climax site were remotely controlled.

With the young fuel (2.5 years out-of-core) used in this test, the thermal maxima on the storage hole walls are expected about 6 months after fuel insertion and within 2 years at edges of the 15-m x 15-m repository model cell (Fig. 1). Therefore, the test has a planned duration of 3 to 5 years. Thermal and thermomechanical calculations are documented by Butkovich (1980), Butkovich and Montan (1980), and Montan (1980).

The SFT-C underground openings were newly mined for the test. First, a 420-m deep canister access hole was drilled from the surface. Then, the two heater drifts were driven to the access hole. Prior to mining the 4.5-m x 6-m storage drift in two passes, displacement and stress instrumentation was emplaced in order to document the rock response to mining (Ramsport, 1979). These data are available for later comparison with the rock response to the thermal load. Prior calculations of both responses were made (Butkovich, 1980), and later calculations of the mining response are continuing (Heuze and others, 1980).

Prior to test construction, the geotechnical program consisted of core logging, careful mapping of the drifts, and an *in situ* state-of-stress measurement (Carlson and others, 1980). Later, measurements of rock deformability, stress, and Poisson's ratio were made *in situ* (Heuze and others, 1980).

More than 900 data channels are installed and operating. Information on the test instrumentation and some preliminary data are given by Carlson and others (1980). The technical instrumentation consists of thermocouples (487), rod extensometers (115 anchors), stress meters (18), wire extensometers (34), and 7 stations of 3-component joint-motion gages. There are also a number of manually monitored displacement pins set at various locations through the test array. Finally there is a system of ventilation and dewpoint monitors, and an array of radiation monitors.

In addition to the SFT-C, LLNL has developed a program plan for the measurement of radionuclide migration along fractures in an area adjacent to the SFT-C. We are currently carrying out field hydrologic testing in order to prepare a detailed engineering test plan. Assuming favorable results, we expect to carry out field testing with radionuclides during 1982.

REFERENCES

- Bradshaw, R. and W. C. McClain (1971). Project Salt Vault: A Demonstration of the Disposal of High-activity Solidified Wastes in Underground Salt Mines. Oak Ridge National Laboratory Report ORNL-4555, Oak Ridge, TN.
- Butkovich, T. R. (1980). Mechanical and Thermomechanical Calculations for a Spent Nuclear Fuel Test in Granite. Lawrence Livermore National Laboratory Report UCRL 52985, Livermore, CA.
- Butkovich, T. R. and D. H. Montan (1980). A Method for Calculating Internal Radiation and Ventilation with the ADINAT Heat-flow Code. Lawrence Livermore National Laboratory Report UCRL 52918, Livermore, CA.
- Carlson, R. C., W. C. Patrick, D. G. Wilder, W. G. Brough, D. N. Montan, P. Harben, L. B. Ballow, and H. C. Heard (1980). Spent Fuel Test-Climax: Technical Measurements Interim Report FY 1980. Lawrence Livermore National Laboratory Report UCRL 53064, Livermore, CA.
- Duncan, J. D., P. A. House, and G. W. Wright (1980). Spent Fuel Handling System for a Geologic Storage Test at the Nevada Test Site. Lawrence Livermore National Laboratory Report UCRL 83728, Livermore, CA. Proceedings of American Nuclear Society Meeting, Las Vegas, NV, June 1980.

- Heuze, F. E., W. C. Patrick, R. V. De La Cruz, and C. F. Voss (1980). In Situ Deformability, In Situ Stresses and In Situ Poisson's Ratio, Climax granite, Nevada Test Site, to be published as Lawrence Livermore Laboratory report.
- Heuze, F. E., T. R. Butkovich, and F. C. Peterson (1980). A New Analysis of the Mine-by Experiment in Climax granite, Nevada Test Site, to be published as Lawrence Livermore National Laboratory report.
- Montan, D. N. (1980). Thermal Analysis for a Spent Reactor Fuel Storage Test in Granite. Lawrence Livermore National Laboratory Report UCRL 83995, Livermore, CA.
- Ramspott, L. D. (1979). Climax granite test results. In F. Holzer and L. Ramspott (Ed.) Proceedings of a Workshop on Thermomechanical Modeling for a Hardrock Waste Repository, Lawrence Livermore National Laboratory Report UCAR 10043, Livermore, CA. pp. 92-112.
- Ramspott, L.D., L. B. Bailou, R. C. Carlson, D. N. Montan, T. R. Butkovich, J. E. Duncan, W. C. Patrick, D. G. Wilder, W. G. Brough, and M. C. Mayr (1979). Technical Concept for a Test of Spent Reactor Fuel in the Climax Granite, Nevada Test Site. Lawrence Livermore Laboratory Report UCRL-52796, Livermore, CA.

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government thereof, and shall not be used for advertising or product endorsement purposes.