DOE/PC/91054--T15

FINAL REPORT

EFFECT OF PRETREATING OF HOST OIL ON COPROCESSING

Principal Investigators

Irving Wender

John W. Tierney

Chemical and Petroleum Engineering Department

University of Pittsburgh

Pittsburgh PA 15261

RECEIVED
USDOE/PETC
95 OCT 27 AM 9:10
ADJUTANT & ASSISTANCE DIV.

Prepared for

United States Department of Energy

Contract DE-AC22-91PC91054

October, 1995

**CLEARED BY
PATENT COUNSEL**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

ABSTRACT

A petroleum vacuum resid (1000°F+) was pretreated by catalytic hydrogenation and hydrocracking reactions and the pretreated resids (host oils) were then coprocessed with coal. The fraction of coal converted to soluble products and the yield of pentane-soluble oils were determined after coprocessing. The phenolic oxygen concentration of the oil product provided a means for estimating the fraction of coal liquids in the products; oils originating from coal had much higher concentrations of phenolic oxygen than those originating from petroleum. Resids that were pretreated by mild temperature hydrogenation reactions, where cracking was suppressed, became better host oils; when these pretreated resids were coprocessed with coal, more of the mixture was converted to tetrahydrofuran-soluble products. Depending on the pretreatment, the pentane-soluble oil yields following thermal coprocessing were either significantly lower or slightly higher than the oil yields obtained with untreated resid. The yield of oils was strongly affected by the concentration of coal in the feed. The presence of small amounts, less than 33% of coal, enhanced the conversion of petroleum resid to oils during coprocessing, although the increases were small.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TABLE OF CONTENTS

ABSTRACT	ii
LIST OF FIGURES	vi
LIST OF TABLES	ix
1.0 INTRODUCTION	1
2.0 BACKGROUND	4
2.1 Coal Structure and Its Conversion to Liquid Products	4
2.2 Composition of Heavy Petroleum Fractions	8
2.3 Upgrading of Heavy Petroleum Fractions	11
2.4 Coal-Heavy Oil Coprocessing Technology	17
2.5 Coal-Heavy Oil Coprocessing Studies	22
3.0 RESEARCH OBJECTIVES	28
4.0 PRETREATMENT OF PETROLEUM RESID	29
4.1 Objectives	29
4.2 Experimental	30
4.2.1 Properties of Petroleum Resids	30
4.2.2 Resid Pretreatment Reactions and Product Workup	33
4.2.3 Reactant and Product Characterization Techniques	38
4.3 Results and Discussion	39
4.3.1 Effect of Reaction Parameters on Pretreatment Product Yields	39

4.3.2	Effect of Pretreatment Temperature on the Available Hydrogen Content of the Host Oil	52
4.3.3	Pretreatment Experiments with the Citgo Resid	54
4.4	Summary	58
5.0	Heavy Oil-Coal Coprocessing Experiments	59
5.1	Objectives	59
5.2	Experimental	60
5.2.1	Properties of Coal Samples	60
5.2.2	Coal-Heavy Oil Coprocessing Experiments and Product Workup	62
5.2.3	Product Characterization Techniques	64
5.3	Results and Discussion	65
5.3.1	Effect of Host Oil Type and Coal-Feed Concentration on Coal Conversion	65
5.3.2	Effect of Host Oil Type and Coal Feed Concentration on Product Yields	72
5.3.3	The Amount of Coal Liquids in the Oil Products	89
5.3.4	Effect of Coal Type on Coprocessing	101
5.3.5	Effect of the Presence of Hydrogen Gas on Coprocessing . .	103
5.3.6	Host Oil Demetallation by Coprocessing with Coal	105
5.4	Summary	108
6.0	CONCLUSIONS	111
	ACKNOWLEDGMENT	112

BIBLIOGRAPHY	113
--------------------	-----

LIST OF FIGURES

Figure 2.0	Comparison Between Direct Coal Liquefaction and Coal-Heavy Oil Coprocessing	18
Figure 4.0	Stirred 300 ml Autoclave Reactor System	34
Figure 4.1	Liquid Temperature and Pressure History of Amoco Resid Pretreatment Run # 54	36
Figure 4.2	Stirred Autoclave Product Workup Scheme	37
Figure 4.3	Gas Yield vs ERT for Pretreatments of Amoco Resid	44
Figure 4.4	Asphaltene Yield vs ERT for Amoco Resid Pretreatments	46
Figure 4.5	Coke Formation vs ERT for Amoco Pretreatments	47
Figure 4.6	Atomic C/S Ratio of the THF-soluble Product from Pretreatments of Amoco Resid	49
Figure 4.7	Atomic C/N Ratio of the THF-soluble Product from Pretreatments of Amoco Resid	50
Figure 4.8	Atomic H/C Ratio of the THF-soluble Product from Pretreatments of Amoco Resid	51
Figure 4.9	Available Hydrogen Content of the THF-Soluble Product from Pretreatments of the Amoco Resid	53
Figure 5.0	Shaken Microreactor System	63
Figure 5.1	Illinois No.6 Coal Conversions to Soluble Products vs Coal-Feed Concentration	71
Figure 5.2	Product Yields, as wt% of Feed, vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal+untreated Citgo resid)	73

Figure 5.3	Product Yields, as wt% of Feed, vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal+ host oil A)	74
Figure 5.4	Product Yields, as wt% of Feed, vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal+ host oil B)	75
Figure 5.5	Product Yields, as wt% of Feed, vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil C)	76
Figure 5.6	Product Yields, as wt% of Feed, vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil D)	77
Figure 5.7	Product Yields, as wt% of Feed, vs Host Oil Used	79
Figure 5.8	Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + untreated Citgo resid)	83
Figure 5.9	Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil A)	84
Figure 5.10	Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal+ host oil B)	85
Figure 5.11	Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil C)	86
Figure 5.12	Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil D)	87
Figure 5.13	Concentration of Phenolic Oxygen in Oil Products vs Coal-Feed Concentration	91

Figure 5.14	Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + untreated Citgo resid)	96
Figure 5.15	Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil A)	97
Figure 5.16	Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil B)	98
Figure 5.17	Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil C)	99
Figure 5.18	Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (Coprocessing conditions: Illinois No.6 coal + host oil D)	100

LIST OF TABLES

Table 2.0	Processes for Upgrading Heavy Oils	12
Table 2.1	Selective Homogeneous Hydrogenation of Some Polynuclear Aromatic Compounds With $\text{Co}_2(\text{CO})_8$, 1:1 H_2/CO 2500-3500 psig .	16
Table 2.2	Summary of Coal-Heavy Oil Coprocessing Technology	19
Table 4.0	Properties of Two Petroleum Resids (1000 °F+)	32
Table 4.1	Reaction Conditions and Results of Amoco Resid Pretreatments . .	40
Table 4.2	Reaction Conditions and Results of Amoco Resid Pretreatments . .	41
Table 4.3	Reaction Conditions and Results of Amoco Resid Pretreatments . .	42
Table 4.4	Reaction Conditions and Results of Amoco Resid Pretreatments . .	43
Table 4.5	Reaction Conditions and Product Yields for Pretreatments of Citgo Resid	55
Table 4.6	Properties of Citgo Pretreated Host Oils	57
Table 5.0	Properties of Argonne Coal Samples	61
Table 5.1	Reaction Conditions and Results of Illinois No.6 Coproprocessing Runs	66
Table 5.2	Reaction Conditions and Results of Illinois No.6 Coproprocessing Runs	67
Table 5.3	Reaction Conditions and Results of Illinois No.6 Coproprocessing Runs	68
Table 5.4	Properties of Pentane-Soluble Oil Products from Coprocessing Illinois No.6 Coal with Various Citgo Host Oils	81
Table 5.5	Properties of Asphaltene Products from Coprocessing Illinois No.6 Coal with Various Citgo Host Oils	88

Table 5.6	Phenolic Oxygen Concentration and Fraction of Coal-Derived Liquid in Pentane-Soluble Oil Samples	93
Table 5.7	Results of Coprocessing Wyodak Coal with Various Citgo Host Oils	102
Table 5.8	Results of Coprocessing Experiments Under Helium	104
Table 5.9	Distribution of V and Ni in Products Obtained by Coprocessing Illinois No.6 Coal and Untreated Citgo Resid	105
Table 5.10	Distribution of V and Ni in Products Obtained by Coprocessing Illinois No.6 Coal and Host Oil A	106
Table 5.11	Distribution of V and Ni in Products Obtained by Coprocessing Illinois No.6 Coal and Host Oil C	107

1.0 INTRODUCTION

This three-year research project, under DOE contract No. DE-AC22-91PC91054, was undertaken to determine if coprocessing performance (i.e., coal conversion and oil yield) could be significantly improved by pretreating a petroleum resid prior to reacting it with coal. Professor Irving Wender was the principal investigator, Professor John W. Tierney was the co-principal investigator and Paul E. Hajdu was the graduate student on the project. Paul Hajdu obtained a Ph.D. degree based on his work on this project. His dissertation is entitled "Effect of Pretreating of Host Oil on Coprocessing". The following publications and presentations were based on this work.

1. A peer review of the work was held on January 25th, 1995.
2. Results of the study were also presented at the ACS National Meeting in Anaheim, CA on April 2, 1995.
3. A paper describing results will be presented at the upcoming DOE Coal Liquefaction and Gas Conversion Contractors Meeting to be held in Pittsburgh during August 29-31, 1995.
4. A technical paper titled "Effect of Pretreating of Host Oil on Coprocessing" describing the research is being submitted for publication.

The world's supply of petroleum crude is becoming heavier so that the amount of vacuum tower bottoms (resid) has been steadily increasing. Coprocessing of coal with petroleum resid (1000°F+) may be an attractive way of obtaining valuable distillates from these readily available and relatively inexpensive hydrocarbon sources. Petroleum resid and coal differ in several ways; coal is more aromatic, contains more inorganic material, is richer in oxygen, and has smaller clusters of organic material. Resids, on the other hand, are more aliphatic and less aromatic, richer in hydrogen, have very little oxygen, somewhat smaller amounts of nitrogen, significantly more sulfur, and small amounts of vanadium, nickel and iron, some of which are trapped in porphyrin structures.

In general, petroleum is a poor liquefaction solvent; coal conversion in heavy oil in the absence of a liquefaction catalyst is usually less than that achieved in a coal-derived recycle solvent in conventional liquefaction processes. This is mainly because petroleum contains fewer aromatic and hydroaromatic compounds than do coal liquids. In general, hydroaromatic compounds can function as hydrogen donors while many polynuclear aromatic compounds are able to shuttle hydrogen during coal liquefaction. Both of these types of compounds are effective for bringing about high levels of coal dissolution.

The approach of modifying the petroleum-derived host oil for improving coprocessing performance has been used by other researchers. Takeshita and Mochida¹ obtained a coal conversion of 88% in a petroleum pitch that had first been hydrotreated

at high pressure over a Ni/Mo/Al₂O₃ catalyst. Sato and coworkers² obtained high coal conversions and high distillable oil yields from a Japanese subbituminous Taiheiyo coal using a tar sand bitumen prehydrotreated with a Ni-Mo catalyst. Curtis and coworkers^{3,4,5} showed that high levels of coal conversion can be obtained in a host oil that contained a mixture of both heavy oil and hydrogen donor compounds.

There are many ways to pretreat a resid. In this project, pretreatments involving hydrocracking and hydrogenation reactions were aimed at improving the resid as a coprocessing vehicle by attempting to; (1) convert aromatic structures in the petroleum to hydroaromatic compounds capable of donating hydrogen, (2) crack the heavy oil to lower molecular weight material that might serve as a better solvent, (3) reduce the coking propensity of the heavy oil by the hydrogenation of polynuclear aromatic compounds, and (4) remove metals and heteroatoms that might poison a coprocessing catalyst.

In this report, the term host oil refers to any petroleum liquid that is coprocessed with coal. This may include untreated vacuum resid or the liquid product from resid pretreatments. Oils refer to the fraction of starting resid, pretreated resid or products from coprocessing that are soluble in pentane. Oils are free of asphaltenes and solids. The terms heavy oil and resid are used interchangeably.

2.0 BACKGROUND

2.1 Coal Structure and Its Conversion to Liquid Products

The organic material in coal is believed to have a three-dimensional crosslinked macromolecular structure in which a small amount of lighter organic material is trapped. The organic structures in coal are made up of small aromatic and hydroaromatic clusters crosslinked by aliphatic and aliphatic-heteroatomic chains. The precise chemical structure of the organic material in coal is not known. Several molecular models have been proposed to represent important features, such as the type and distribution of functional groups and the carbon skeleton^{6,7,8,9}.

Shinn's model⁸ of a bituminous coal, which was based on characterization and reactivity data, has a molecular weight of 10,000 atomic mass units (amu) and a distribution of atoms as follows;

Based on NMR data, Shinn assigned 70% of the carbons and 30% of the hydrogens to aromatic ring systems, which contain no more than three rings. Oxygen is the predominant heteroatom, and is distributed between hydroxyl, carboxyl, ether, and carbonyl functional groups. Organically bound sulfur is distributed between aliphatic sulfur (i.e., dialkyl sulfides) and aromatic sulfur (i.e., thiophenes and diaryl sulfides). Shinn placed nitrogen atoms in aromatic ring systems to reflect their relatively unreactive

nature. Nitrogen functionalities include; basic pyridines and quinolines, the weakly acidic or neutral indoles and carbazoles, and quaternary nitrogen.

Our knowledge of bonding in coal is improving as more data becomes available. Early views that the coal network is tightly held together almost entirely by covalent bonds has evolved to a contemporary picture in which weaker non-covalent interactions (i.e., hydrogen and van der Waal's bonding) also play important roles in coal structure¹⁰. The view that the coal structure is somewhat loosely held together helps explain why some coals swell upon heating or when soaked in certain polar organic solvents, such as pyridine¹¹. Under conditions that cause swelling, coal behaves more like a gel than a rock, but covalent crosslinkages prevent full dissolution. Therefore, any process that converts coal to small fragments, such as would constitute a distillable oil, must rupture covalent bonds. Thermal or solvent pretreatments that swell the coal may be effective at promoting coal dissolution by "loosening" the coal network, thus making it more accessible to reactants and allowing more complete diffusion of reactant products out of the coal structure.

The first step in the conversion of coal to liquids involves heating coal to a temperature at which the inherently weaker bonds begin to break, around 350°C. Free radicals formed by thermolysis of weak bonds are capped by external hydrogen atoms supplied by hydrogen gas or hydrogen donor molecules present in the recycle solvent, and internal hydrogens from the transfer of hydrogen within the coal¹². If external hydrogen is supplied the process is termed hydroliquefaction. In pyrolysis, external

hydrogen is not supplied and radicals are stabilized to some extent by hydrogen present in the coal.

Liquefaction products from bituminous coal at short contact time are predominantly preasphaltenes, which are high molecular weight materials containing a high concentration of functional groups. At longer contact times, preasphaltenes undergo additional reactions that remove functional groups and depolymerize the large fragments into smaller ones. The smaller molecules comprise asphaltenes and oils, depending on their size and number of functional groups.

During liquefaction, coal fragments that have not been stabilized by hydrogen atoms can recombine to form heavier molecules. These retrogressive reactions can lead to formation of coke and char.

The view that the coal structure comes apart solely by thermolysis of inherently weak bonds upon heating cannot fully explain the liquefaction process. McMillen et al.^{13,14,15} have postulated that even strong linkages, such as $C_{aryl}-C_{alkyl}$ bonds, can undergo cleavage under liquefaction conditions. These bonds are strong (90 kcal/mole) and should not break under liquefaction conditions. Malhotra and McMillen¹³ propose that cleavage of this type of strong bond would be expected if a hydrogen atom were placed at the ipso position (the aromatic carbon atom bearing the linkage). A hydrogen atom can be transferred to the ipso position by several pathways, according to the authors. One pathway, called radical hydrogen transfer, involves a direct bimolecular transfer of a hydrogen atom from a radical to a closed-shell polynuclear aromatic hydrocarbon,

many of which are in good supply in coal liquids.

From our current understanding of coal liquefaction, it is apparent that a good liquefaction solvent not only scavenges free radicals formed by thermolysis of weak bonds, but can also selectively transfer hydrogen to ipso positions, resulting in rapid cleavage of strong linkages. A good coal liquefaction vehicle, especially in the absence of a catalyst, should contain a supply of hydrogen donor agents, as well as hydrogen acceptor and transfer agents.

Throughout the history of coal liquefaction, transition metals, in particular Mo, Sn and Fe, have been used as catalysts to promote the breakdown of the coal structure to liquid products¹⁶. These catalysts have been used in a dispersed form, either by impregnating onto coal directly or by adding as finely divided solids or water- and oil-soluble salts, in order to attain intimate contact with the coal.^{17,18,19,20,21,22,23} At liquefaction conditions, and in the presence of sulfur (inherent in the coal or added externally with the catalyst), the transition metal is converted to a sulfide. The metal sulfide, along with hydrogen sulfide, is the active liquefaction catalyst.

Iodine compounds such as hydrogen iodine, methyl iodine, or elemental iodine have been used to enhance coal liquefaction.^{24,25,26,27,28} The mechanism of coal conversion with iodine compounds may involve $I\cdot$ and $H\cdot$ radicals that attack the coal structure, breaking apart weak bonds. The acidic nature of hydrogen iodine may also play a role in the degradation of coal structure.

2.2 Composition of Heavy Petroleum Fractions

Petroleum is made up of a wide mixture of compounds. Petroleum usually contains an appreciable number of sulfur compounds, including thiols (mercaptans), sulfides, cyclic sulfides, disulfides, and thiophenes. Generally, the higher the density of the crude, the higher is its sulfur content. Nitrogen compounds are also present in petroleum, although at lower concentrations than sulfur. Nitrogen functional groups are classified as basic, neutral or acidic. Basic compounds include pyridine, quinoline and amines; neutral compounds include alkylindoles and alkylacridines. The acidic ones include indoles and carbazoles. Like sulfur compounds, nitrogen compounds tend to concentrate in the residuum fraction of petroleum. Organic oxygen compounds are present in petroleum; however, usually in low concentrations, less than 2%.

It is convenient to divide petroleum into groups of compounds that share some common physical or chemical property. In a refinery, crude oil is fractionated in atmospheric and vacuum distillation columns into several products each of which has a narrow boiling point range. Naphtha, used to make gasoline, contain compounds that have an atmospheric equivalent boiling point (AEBP) below about 430 °F. Middle distillates (jet fuel and diesel fuel) consists of compounds that have an AEBP in the range of 430-650°F. Vacuum gas oil is the overhead stream from a vacuum distillation tower and contains compounds that have an AEBP in the range of 650-1000°F. Vacuum resid is the bottom stream from a vacuum tower and usually contains material that has an

AEBP above 1000°F.

The compounds within a narrow boiling range can have vastly different molecular weights, chemical structures and can contain different functional groups. As the boiling point of the oil increases the number of different compounds increases and the structures of the compounds become more complex. This makes it essentially impossible, to isolate and identify all the possible compounds present in the heavier petroleum fractions.

The molecules within a narrow boiling range can usually be separated by adsorption techniques^{29,30} into at least three classes of compounds; saturates, aromatics and polar molecules. The saturates contain paraffins (straight and branched chain hydrocarbons) and naphthenes (cyclic paraffins) with one or more rings. High boiling point saturates can contain multiple rings highly substituted with aliphatics. The aromatic rings usually bear paraffinic side chains and also may be connected to naphthenic rings. The number of substitutions and the number of aromatic rings usually increases with boiling point. Saturates and aromatics, especially in the higher boiling point fractions, can also contain neutral heteroatoms of S, N, and O. Polar compounds are heterocompounds that contain one or more heteroatoms.

By solvent extraction techniques, a petroleum resid can be divided into maltenes and asphaltenes. The maltenes are soluble in a light non-polar solvent, such as n-pentane; this fraction contains saturated and aromatic compounds, and resins. Compounds in the resins fraction, which can comprise over 50% of petroleum resid, have molecular weights of about 1000 amu and atomic H/C ratios of 1.3 to 1.6. It is

postulated that resin compounds are long paraffinic chains with condensed aromatic and naphthenic rings, and contain heteroatoms of N, S and O and metals.

The asphaltene fraction of petroleum are soluble in toluene, but insoluble in pentane. Asphaltenes are dark brown to black solids at room temperature and have molecular weights in the range of 600-5,000 amu. They have atomic H/C ratios of about 1.15 and are rich in heteroatoms and metals. Although the precise structure of asphaltenes is not known, it has been proposed³¹ that they are made up of condensed aromatic structures that are attached to alkyl and alicyclic systems. It appears that asphaltenes form micellar agglomerates by the stacking of aromatic plates. Although these asphaltene micelles are insoluble in the oil fraction, they remain dispersed in petroleum due to the presence of resins, which associate with the asphaltenes and weaken asphaltene-asphaltene intermolecular attractions.

Petroleum resids usually contain a small amount, usually less than 1,000 ppm, of metals; mostly V, Ni and Fe chelated with porphyrins or in other structures³². It is possible that the planar metalloporphyrins can be incorporated readily into the asphaltene micelles between the aromatic sheets of the asphaltenes. It has also been suggested that the metalloporphyrins are bonded directly to the asphaltenes.

2.3 Upgrading of Heavy Petroleum Fractions

There are a number of possible ways to upgrade a heavy oil, resulting in an increase in its atomic H/C ratio. Schuetze and Hofmann³³, as well as Schuetze³⁴ have reviewed industrial methods for upgrading heavy oils. The more common resid upgrading processes are summarized in Table 2.0. The H/C ratio of a heavy oil can be increased by rejecting carbon (including disproportionation of hydrogen) or by adding hydrogen. Carbon rejection methods include delayed coking³⁵, fluid coking³⁶, and visbreaking³⁷. These thermal processes improve the H/C ratio of the cracked liquid products by rejection of coke and unsaturated aromatic hydrocarbons from the resid. In the present study, we were interested in increasing the H/C ratio of resids by adding hydrogen, rather than rejecting carbon. Hydrotreating is a well-established method for treating both distillate and residual fuels with the primary goal of removing sulfur and metals. Resid hydrotreating can also cause hydrogenation of polynuclear structures, resulting in reduction of Ramsbottom carbon number³⁸. Material causing high Ramsbottom carbon number is predominantly molecules with five or more aromatic rings. There are currently a large number of commercial hydrotreatment processes available; Chevron's VRDS³⁹ or RDS⁴⁰, Exxon's RESIDfining⁴¹, Shell's bunker flow⁴², Union Oil's Unicracking RDS⁴³ and UOP's⁴⁴ RCD Unibon and BOC Unibon. Hydrotreating is usually performed over a fixed-bed catalyst (e.g., Ni/Mo/support or Co/Mo/support).

Table 2.0 Processes for Upgrading Heavy Oils

Process	Licenser	Gas used	Catalyst	T; °C	P, atms	Time min	Goals	No. of Plants ^a
Hydrotreat, fixed bed	Chevron Exxon Shell Union Oil UOP	H ₂	Co Mo on Al-Si support	400- 440	50- 250	10- 30	remove metals + sulfur	26
Hydrocrack, ebullating bed	HRI LC-fining	H ₂	Ni/Mo	430- 470	100- 200	30- 90	high conversion	6
Hydrocrack, slurry phase	CANMET VEBA Exxon	H ₂	coal + Fe char Mo	470, 430- 470, 440	100- 150, 150- 300, 170	30- 90	high conversion	pilot testing
Visbreaking				430- 490	10- 50	2-20	partial conversion	139
Coking; delayed or Fluid	Exxon			490- 510, 510- 566	2-5 1-2	24 hr 15- 30 s	convert resid to distillate	75 13

a: Number of plants in US as of 1991

The catalyst, which has a dual function, consists of a hydrogenation metal on an acidic support (e.g., amorphous silica-alumina). In industry, hydrotreating is usually combined with catalytic cracking or coking to attain complete conversion of the resid.

Hydrocracking is performed at more severe conditions than hydrotreating and therefore converts a greater fraction of the resid to distillate. Choudhary and Saraf⁴⁵ published an extensive review of hydrocracking technology, which was later updated by Mohanty, Kunzru and Saraf⁴⁶. A major problem associated with resid hydrocracking is rapid catalyst deactivation due to coke and metal fouling.^{47,48,49,50} Under the severe conditions that exist in a hydrocracker, the life of the catalyst is short, and therefore spent catalyst must be continuously replaced with fresh catalyst. HRI's H-Oil and Lummus Crest Inc.'s LC-fining⁵¹ processes employ ebullating-bed reactors in which their proprietary catalyst is fluidized in oil. This reactor configuration facilitates on-line catalyst replacement.

Slurry phase hydrocracking is a major new area of hydrocracking technology. In these processes, the resid is cracked at high temperatures (450-485°C) and under high pressures (2,000-3,500 psig) in the presence of a finely divided powder additive or catalyst in a once-through mode. Examples of slurry-phase processes, all of which are in the testing stage, include VEBA-Combi-Cracking⁵², the Aurabon process⁵³, the CANMET process⁵⁴, and Exxon's M-Coke process⁵⁵. The VEBA process, developed from coal liquefaction experience gained during World War II in Germany, uses a powdered catalyst which is either a waste product of the alumina industry ("Bayer mass")

or lignitic char. The Aurabon process (developed by UOP) uses metals as a catalyst. The CANMET process uses an iron-based additive, essentially an iron sulfate salt impregnated on coal. In Exxon's process, the catalyst is formed in situ from dispersed metals such as molybdenum and coke precursors. In all these slurry-phase processes, the catalyst/additive serves to suppress coke formation.

The reactions involved in hydrotreating and hydrocracking of heavy oils are complex and not fully understood. A large number of studies have been carried out on model hydrocarbons such as paraffins,^{56,57,58,59,60} aromatics and polycyclic alkylaromatics⁶¹ in an attempt to understand the underlying reaction mechanisms and for providing some basis for predicting product distribution. In petroleum resid hydrocracking studies, the reactants and products are usually grouped into pseudo-components based on some physical property such as solubility.^{62,63,64} However, these oversimplified models generally do not adequately describe the actual reaction network and are of limited use. Heck and DiGuseppi^{65,66} studied slurry-phase hydrocracking of a petroleum resid in the presence of a molybdenum hexacarbonyl catalyst. They concluded that resid conversion was largely thermally driven and independent of the presence of hydrogen, but that activated hydrogen was needed to suppress coke formation and secondary cracking of primary products. Activated hydrogen can be in the form of hydrogen donor solvents or hydrogen on an active catalyst. Heck et al.⁶⁵ postulated that the mechanism of resid hydrocracking involved cracking of largely aliphatic fragments away from aromatic cores, typically found in the asphaltene fraction of petroleum. As conversion proceeded

they found that the size of the aliphatic fragments attached to the aromatic core became smaller and increasingly more difficult to remove. The authors suggested that high conversions could be achieved without excessive formation of coke by insuring that conditions are such that cracking rates do not significantly outpace hydrogenation rates. It is useful to remember three important facts when considering resid upgrading processes:

- 1) hydrocarbons, except methane, have a positive free enthalpy of formation at temperatures higher than 500 K; thermodynamic equilibrium favors formation of carbon and hydrogen,
- 2) hydrogenation is exothermic and cracking is endothermic (the overall hydrocracking reaction is exothermic), and
- 3) time-temperature reaction characteristics, especially with respect to increased temperature, are such that the rate of cracking increases faster than the rate of hydrogenation.

Another approach for hydrogenating a petroleum resid involves use of a metal carbonyl homogeneous catalyst. Friedman et al.⁶⁷ and Wender et al.⁶⁸ found that dicobalt octacarbonyl, $\text{Co}_2(\text{CO})_8$, can partially hydrogenate polynuclear aromatic compounds to make hydroaromatic compounds at relatively low temperatures, below 250°C, in the presence of CO and H_2 . Project SEACOCKE⁶⁹, carried out by ARCO, also demonstrated the action of transition metal carbonyls using coal model compounds as well as coal derived liquids. Some of Friedman and Wender's results are summarized in Table 2.1.

Table 2.1 Selective Homogeneous Hydrogenation of Some Polynuclear Aromatic Compounds With $\text{Co}_2(\text{CO})_8$, 1:1 H_2/CO 2500-3500 psig (initial)

<u>Aromatic Compounds</u>	<u>Reaction Temp, °C</u>	<u>Reaction Products</u>	<u>Yield, %</u>
Anthracene	135	9,10-Dihydro-	99
Phenanthrene	200	Di- + Tetra-	8
	232	Mostly Di-	94
2-Methylnaphthalene	200	Methyltetralins	45
Fluoranthene	200	Tetra-	54
Pyrene	200	4,5-Di-	69
Perylene	150	Hexa-	72
1-Naphthol	185	Tetra-	95
2-Naphthol	185	Tetra-	100

Friedman and Wender found that non-linear aromatics such as phenanthrene are more resistant towards hydrogenation than linear polynuclear aromatics such as anthracene. Polynuclear aromatics tend to produce products with isolated benzene rings or phenanthrene structures. Work carried out under the SEACoke project gave similar results and determined that cobalt carbonyl was essentially unreactive towards dibenzothiophene under an initial pressure of 2800 psi H_2 and CO at 185 °C. Dibenzothiophene is a model often used as a compound with an organosulfur functional group found in coal and heavy oil.

2.4 Coal-Heavy Oil Coprocessing Technology

The basic elements of coal-heavy oil coprocessing are illustrated in Figure 2.0. Coal and heavy oil are reacted under hydrogen at high temperature and pressure in a once-through mode. During this process, coal is converted to soluble products and the heavy oil to distillate. Products from the first reactor require further upgrading using a hydroprocessing catalyst. Products from coprocessing include gases, upgraded distillates, residue, and solids.

Several different configurations for coprocessing have been tested both in the laboratory and in larger scale pilot equipment with encouraging results, although coprocessing has not yet received commercial-scale application in the United States. Curtis and Winschel⁷⁰ reported that the cost for coprocessing appears to lie between those of direct coal liquefaction and residuum upgrading.

The efficiency of these processes can be evaluated in terms of conversion of coal and heavy oil to distillable products, suppression of coke yield, hydrogen usage, removal of heteroatoms (e.g., S, N and O) and demetalization of liquid products. Independent parameters of coprocessing include; feedstock (coal and heavy oil type), catalyst, hydrogen pressure, reactor temperature, reaction time, and coal-feed concentration. Table 2.2 summarizes coprocessing technology and serves to illustrate the general direction in which coprocessing technology development has gone.

Direct Coal Liquefaction

Coal-Heavy Oil Coprocessing

Figure 2.0 Comparison Between Direct Coal Liquefaction and Coal-Heavy Oil Coprocessing

Table 2.2 Summary of Coal-Heavy Oil Coprocessing Technology

	Chevron	Lummus	HRI	Canmet
No. of stages	2	2	2	1
Catalyst	none/ Hydroproc.	none/ Ni/Mo	Ni/Mo Ni/Mo	Fe additive ^b
Temp., °C	?	435/416	430	450
Coal	Illinois No.6	Pitt.	Ohio 5/6	Forestburg
Heavy Oil	Boscan Crude	Arib VTR ^a	Cold Lake ATR	Cold Lake VTR
Coal feed conc., wt%	?	?	50	47
Coal Conv, wt%	89	95	95	81
Resid Conv, wt%	76	78	87	63
HDS, wt%	90		76	
HDN, wt%	27		68	
HDM, wt%	90		98	

a: In the Lummus process, a hydrogenated petroleum resid is mixed with coal and fed to the first reactor.

b: The Canmet additive consists of 30% iron sulfate salt impregnated on lignite coal.

Chevron's Co-Refining process⁷¹ employs two reactors in series. A coal-oil slurry and hydrogen gas are fed to the first reactor where thermal reactions dissolve the coal and convert the heavy oil. Effluent from the first reactor is fed directly to the second reactor, which contains a hydroprocessing catalyst to further upgrade the liquid. Effluent from the second reactor is separated into gas, solid, oil, and residuum streams. A portion of the oil stream is recycled to the first reactor. Hydrogen is removed from the gas stream and recycled to the first reactor.

Chevron has processed bituminous as well as subbituminous rank coals, and crude oils as well as atmospheric tower resids (650° F+). Table 2.2 shows results from one run where Chevron coprocessed a Boscan crude oil with an Illinois No. 6 coal.

The Lummus Crest Inc. (LCI) concept⁷² appears to be similar to the Chevron Co-Refining process and also uses two close-coupled reactors; the first is a thermal reactor, while the second reactor contains a supported catalyst (Shell 324M LC-Fining) for hydrocracking. One important difference between the two processes is that, in the LCI concept, coal is blended with heavy oil that has been previously hydrogenated.

Hydrocarbon Research Inc. (HRI)⁷³ developed a catalytic coprocessing technology using fluidized bed reactors. The concept is based on their commercial H-Oil process (for upgrading heavy crude and/or petroleum residuum) and H-Coal process (for direct liquefaction of coal). The process involves mixing coal with heavy oil and then feeding the coal-oil slurry along with hydrogen to an ebullated bed catalytic reactor. Single-stage as well as two-stage configurations have been demonstrated. Effluent from the reactor

is separated into a vapor and slurry stream. Hydrogen is recovered from the vapor and recycled to the reactor. The slurry stream is fractionated in atmospheric pressure and vacuum distillation towers to produce high quality distillate products. The non-distillable vacuum bottom stream contains unconverted resid, coal and ash. A portion of the atmospheric tower bottoms stream is recycled to the reactor.

The Canada Center for Mineral and Energy Technology (CANMET)⁷⁴ developed a scheme for coprocessing coal with bitumen, heavy oil or petroleum residuum. The process is a single-stage once-through operation that uses an iron-based disposable additive at concentrations of 5-10%. The additive is a finely-ground lignite or subbituminous coal that has been impregnated with an inorganic salt, usually iron sulfate. The additive comprises 70% coal and 30% salt. The CANMET reactor operates at 450°C and 13.8 MPa total pressure.

2.5 Coal-Heavy Oil Coprocessing Studies

There are many published studies of coal-heavy oil coprocessing. Most of these studies report results of high temperature (400-450°C) high pressure (1000-2000 psig) reactions of coal and heavy oil in small-scale reactors. The quantity as well as the quality of oil produced by coprocessing and the fraction of coal and host oil converted to distillable products depend on the following reaction parameters; coal type, heavy oil type, coal/heavy oil feed ratio, reaction temperature, reaction time, and presence of hydrogen gas and a catalyst. The catalyst can be added with the feed or it might be generated from minerals already present in the coal.

The following describes how the level of coal conversion is affected by coprocessing reaction parameters. Derbyshire and Whitehurst⁷⁵ showed that the percentage of coal that can be converted to pyridine solubles under hydrogen-poor reaction conditions (e.g., argon atmosphere in a non-donor solvent or short (3 min) reaction time in tetralin) depends on the carbon content of the coal. Maximum conversions of 70-95 wt% were achieved for coals with 82-88 wt% carbon, reported on a moisture and ash-free (maf) basis. They attributed this behavior to the coal's crosslinking density, which reached a minimum in approximately the same range. A similar trend has been observed for coal fluidity⁷⁶.

When the same coals were reacted in the presence of hydrogen, conversion was always higher. The incremental increase in coal conversion, above that obtained at

hydrogen-poor conditions, could be correlated with the amount of ash present in the coal. Coals that were low in ash showed little improvement in conversion with addition of hydrogen gas. Coals that contained appreciable amounts of ash were more reactive, and addition of hydrogen gas resulted in higher coal conversions. Derbyshire et al.⁷⁵ suggested that there is a catalytic effect of the coal mineral matter, such as iron pyrites. Curtis and Hwang⁷⁷ showed that high coal conversions (84-93 wt%) could be obtained by addition of a hydrogenation catalyst and hydrogen atmosphere, regardless of the coal or petroleum resid type. In Curtis' study, the catalyst was a washed and regenerated resid hydrotreating catalyst that had been pulverized to -100 mesh.

The effects of reaction parameters on coal are best studied under non-catalytic reaction conditions, where the level of coal conversion is low. In non-catalytic coprocessing, the heavy oil type as well as the concentration of coal in the feed have strong effects on the level of coal conversion. Cugini et al.⁷⁸ and Rahimi et al.⁷⁹ demonstrated this in a number of coprocessing experiments. In general, coal conversion was highest in feeds that were low in coal. As the concentration of coal in the feed was increased, coal conversion decreased. This trend demonstrates the limited ability of petroleum-base heavy oil to bring about coal dissolution.

The rate and final level of coal conversion for a particular coal-host oil feed is influenced by reaction temperature and residence time. Miller et al.⁸⁰ demonstrated the complex behavior of coal conversion in thermal (no added catalyst) coprocessing runs of an Illinois No.6 coal with a Maya ATB and a Boscan crude in a 20 ml microreactor.

Miller et al.⁸⁰ found that, at a coal loading of 25 wt% in Maya ATB, the highest level of coal conversion was achieved at a reaction temperature of 410°C in about 20 min. At reaction times longer than 30 min, they found that the level of coal conversion dropped off, and the amount of coke produced increased. This trend was especially evident for runs made at a higher reaction temperature, 450°C. The authors concluded that retrogressive reactions become important at high reaction temperatures, and that this class of reactions plays a key role in hindering production of THF-solubles in coprocessing when the demand for hydrogen is high (i.e., at high temperatures or when the feed contains a high concentration of coal).

These next paragraphs describe how the quality of the oil can be affected by reaction parameters. It appears that upgrading the first stage coprocessing products to make distillable oils is more difficult and requires more severe conditions than are needed to convert coal into soluble products. Rahimi et al.⁸¹ found that they could achieve high coal conversions with CANMET coprocessing in a one liter continuous-flow stirred tank reactor at low severity (430°C, SV=1.0 kg/h-L); however, resid conversion remained relatively low at these conditions. At high severity (460°C, SV=0.5 kg/h-L) the amount of residue decreased significantly. With increasing severity, gas production also increased.

Cugini et al.⁷⁸ demonstrated, in numerous coprocessing runs with an Illinois No.6 coal and three petroleum resids (North Slope VTR, Boscan ATB and Maya ATB), that the yields of heptane-soluble oils (free of asphaltenes) were highest when the resid was

processed in the absence of coal. As coal was added to the feed the overall heptane-soluble oil yield decreased. The oil yields dropped off sharply at coal-feed concentrations above about 20 wt%.

Rahimi et al.⁸¹ found that the yield of distillate (b.p. <975°F) was highest at a coal feed concentration of 3.7 wt% (maf), and distillate yield decreased as the concentration of coal in the feed was increased above that level. The authors concluded that up to 40-50 wt% of the converted coal ended up in the distillate. This assumes that there is no interaction between coal and bitumen so that any excess distillate over what would be expected from the bitumen, if reacted separately, is from the coal. Rahimi et al. coprocessed a Forestburg subbituminous coal with a Cold Lake vacuum bottom in a one liter continuous-flow stirred tank reactor. Coprocessing experiments were performed at 450°C, with a total pressure maintained at 2000 psig, a normal space velocity of 1kg/hr-L. Part of the coal feed was impregnated with FeSO₄.

Rahimi et al.⁸¹ also found that properties of the distillate were affected by the concentration of coal in the feed. As the coal-feed concentration increased from 3.7 to 39.5 wt % (maf) the sulfur content of the distillate (250°-525°C) decreased from 2.58 to 1.88 wt%, the nitrogen content increased from 0.43 to 0.6 wt% and oxygen content increased from 0.38 to 1.3 wt%. The H/C ratio of the distillate decreased slightly, from 1.50 to 1.48. The fraction of aromatic carbons (f_a), increased slightly from 0.29 to 0.33. Changes in distillate properties were rationalized both in terms of the contribution of more aromatic coal-derived liquids in the distillate and enhancement in upgrading of the

bitumen in the presence of coal.

It has been shown that coprocessing of coal and heavy oils is accompanied by significant demetalization of the heavy oil. Miller et al.⁸⁰ showed this when coprocessing an Illinois No.6 coal with a Maya atmospheric tower bottom (ATB) that contained 400 ppm of vanadium, of which 66.5 wt% was in the asphaltene fraction and 33.5% was in the oil fraction. The reaction resulted in removal of approximately 90 % of vanadium from the starting heavy oil. In their experiment, the feed, 60 wt% Maya ATM and 40 wt% coal, was reacted at 425 °C for one hr under 1000 psig (cold) hydrogen gas. Processing the heavy oil without coal under the same reaction conditions resulted in removal of only 65% of the vanadium. The authors suggested that demetalization of heavy oil in coprocessing with coal is not physical adsorption of the metals onto the coal or coke surface, but rather that the metals become incorporated in coke as it is formed. Demetalization may occur via polymerization of the planar porphyrin structures and asphaltenic molecules to form mesophase. Mesophase is an intermediate between starting resid and solid semicoke.

In coal-oil coprocessing, there has been a search for synergism between the coal and petroleum-based host oil. But, it is difficult to detect if a synergy exists, since it requires knowledge of the nature of the coal-derived and petroleum-derived components that make up the products. These individual components are commingled and cannot easily be separated from one another.

Cugini et al.⁷⁸ estimated that the production of heptane-soluble oil from

coprocessing Illinois No.6 coal with Boscan ATB as well as with Maya ATB was higher than expected, based on oil yields from the heavy oil and coal when processed separately. The authors estimated that the contribution of coal-derived liquid to the heptane-soluble product was low and varied in a linear manner with coal addition. They based their conclusion on the level of phenolic oxygen in the heptane-soluble products, which was low (about 0.1 wt%) at a coal feed concentration of 10 wt% and increased with coal addition in a linear way.

Steer et al.⁸² developed a method, which has been used by others^{83, 84} to quantitatively determine, by isotope mass balance, the amount of coal incorporated into a oil generated by coprocessing. The method takes advantage of the difference in $^{13}\text{C}/^{12}\text{C}$ ratio between coals and bitumen/heavy oils, which varies according to geological origins of carbonaceous materials in the order of 3-5 parts per thousand. The method is quite complicated and requires that a sample first be quantitatively converted to CO_2 . The CO_2 is then separated from H_2O and non-condensable gases before being measured using a mass spectrometer. Steer et al.⁸² used this method to estimate the amount of Highvale coal-derived liquid in a oil from the coprocessing of the coal with a Suncor bitumen. The coal and heavy oil differed in $^{13}\text{C}/^{12}\text{C}$ by only 3.68 %.

3.0 RESEARCH OBJECTIVES

The principal objective of this research was to gain information on the role that host petroleum-derived oils play when used as liquefaction solvents in coprocessing with coal. More specifically, we were interested in determining if coprocessing performance (i.e., coal conversion and oil yield) could be significantly improved by pretreating the host oil prior to reacting it with coal. For this purpose, two petroleum vacuum resids were used as such and after they had been pretreated by catalytic hydrogenation and hydrocracking reactions. The catalyst systems used in this study were highly dispersed, fine particle Fe- and Mo-based, and dicobalt octacarbonyl, $\text{Co}_2(\text{CO})_8$.

The untreated resids and pretreated host oils were characterized in order to determine chemical changes brought about by the pretreatments. The modified host oils were then coprocessed with an Illinois No.6 coal as well as a Wyodak coal, and compared to coprocessing with untreated resids under the same hydroliquefaction conditions. The amount of oil derived from coal was estimated by measuring the level of phenolic oxygen (derived mainly from coal) present in the oil products.

4.0 PRETREATMENT OF PETROLEUM RESID

4.1 Objectives

The main objective for pretreating petroleum resid prior to coprocessing with coal was to increase its atomic H/C ratio through catalytic reactions such as hydrogenation and hydrocracking, while at the same time minimizing formation of coke and gas. If the resid could be enriched with hydrogen to a level of about 11.5%, equivalent to a H/C ratio of about 1.6, it might serve as a better host solvent for coprocessing with coal, since it would probably contain more donatable hydrogen.

4.2 Experimental

4.2.1 Properties of Petroleum Resids

Two different petroleum vacuum tower resids (1,000°F+); one from the Amoco Oil Company and the other from the Citgo Oil Company were used in this work. Properties of the resids are listed in Table 4.0. A series of experiments were first conducted with the Amoco resid, derived from a wide mixture of crude oils from around the world, to explore reaction conditions required to hydrogenate and hydrocrack a heavy oil, and to evaluate the sensitivity of reaction parameters such as time, temperature and pressure on product yields. The Citgo resid, however, was chosen as the primary heavy oil to test mainly because it came from only one country, Venezuela.

Several different finely dispersed catalysts were used; $\text{Fe}_2\text{O}_3/\text{SO}_4$, $\text{Mo}/\text{Fe}_2\text{O}_3/\text{SO}_4$, $\text{Mo}(\text{CO})_6 + \text{Fe}(\text{CO})_5$ and Mo naphthenate. The sulfated iron oxides, synthesized in our laboratories, have been previously described and successfully tested in coal liquefaction and coprocessing reactions.^{85, 86, 87} Iron and Mo carbonyls were obtained from the Aldrich Chemical Co. and Mo naphthenate, which contained 6% Mo by weight, was obtained from ICN Biomedical Inc. It is known that the iron compounds used in this study are transformed to pyrrhotites (Fe_{1-x}S) at reaction conditions in the presence of sulfur, which was supplied in our experiments by adding either H_2S gas or elemental sulfur in excess to the reactants. It is generally accepted that pyrrhotites, along with H_2S gas, function as hydrogenation catalysts. Under similar conditions, the Mo compounds

are transformed to MoS_2 . For comparison, pretreatment runs were made without added catalyst, and pretreatment runs were made with a commercial Shell 324 hydrotreating catalyst ($\text{Ni}/\text{Mo}/\text{Al}_2\text{O}_3$). The Shell catalyst was first calcined at 350°C for one hour and then sulfided with H_2S gas during the pretreatment.

A system to make a good host oil using a homogeneous catalyst, dicobalt octacarbonyl ($\text{Co}_2(\text{CO})_8$) and 1:1 synthesis gas system was based on work by Friedman et al. and Wender et al. who found that $\text{Co}_2(\text{CO})_8$ can convert polynuclear aromatic compounds to hydroaromatics at relatively low temperatures, below 250°C .

Table 4.0 Properties of Two Petroleum Resids (1000 °F+)

	Citgo Resid	Amoco Resid
S.G. @ 60°F		1.03
C, wt%	85.4	84.3
H, wt%	10.1	10.2
S, wt%	3.4	4.6
N, wt%	0.8	0.5
O, wt%	0.3	0.4
Atomic H/C	1.42	1.45
V, ppm	555	251
Distribution		
Asphaltenes, %	85.7	
Oils, %	14.3	
Ni, ppm	110	57
Distribution		
Asphaltenes, %	82.1	
Oils, %	17.9	
Fe, ppm	12	13
Pentane insolubles, wt%	29	20
Available H/100 C atoms	9.8	
f_a , fraction of total C	0.33	0.32

f_a = Fraction of aromatic carbon, determined by Brown and Ladner⁸⁸ method.

4.2.2 Resid Pretreatment Reactions and Product Workup

The petroleum vacuum resids were pretreated in a well-stirred stainless-steel 300 ml autoclave batch reactor. The reactor system is shown schematically in Figure 4.0. During a typical run, the reactor was charged with catalyst and 50-100 g of resid, which had been preheated to about 100°C. Since the resid is a semi-solid at room temperature, it was necessary to preheat them in order to make them fluid enough to pour into the reactor. For pretreatment runs made with the $\text{Co}_2(\text{CO})_8$ catalyst, it was not possible to preheat the resid because the carbonyl catalyst is sensitive to heating in air and would dissociate upon contact with the hot oil. In these runs, the resid and catalyst were dissolved in toluene at room temperature, and this mixture was poured into the reactor. The reactor was then sealed, pressure tested with He to the maximum anticipated reaction pressure and charged with either pure H_2 or a mixture of $\text{H}_2\text{S}/\text{H}_2$ or H_2/CO (1:1), depending on the pretreatment. An electric heater brought the reactants to the set temperature at a rate of about 7.5 °/min. During the run, an on-line computer recorded liquid and gas temperatures and reactor pressures, and controlled the heater. During some runs made at elevated temperatures, a significant amount of hydrogen was consumed and so hydrogen gas was added in order to maintain the overall pressure above 1500 psig.

Figure 4.0 Stirred 300 ml Autoclave Reactor System

At the end of the reaction time, measured from the time reaction temperature was reached, the heater was lowered and the reactor quenched with water and cooled in air to room temperature. Figure 4.1 shows the reactor pressure and liquid temperature history for a pretreatment of the Amoco resid. The pressure spikes during the run correspond to times when hydrogen gas was added.

Once the reactor contents reached room temperature, gases were vented and collected for analysis. The remaining liquid and solid products were removed by washing the inside of the reactor with tetrahydrofuran (THF). The THF-washed material was sonicated for 30 minutes and then filtered to remove any THF-insoluble solids. THF was removed from the liquid by a rotovapor. Solids were vacuum dried at 80-90 °C overnight prior to weighing. The THF-soluble liquid, which contained oils and asphaltenes, was used as a host in coprocessing runs. Asphaltenes are soluble in THF but insoluble in pentane, and oils are soluble in both THF and pentane.

The product workup procedure was later improved by adding an atmospheric distillation step to remove light (bp < 380°F) products directly from the reactor prior to washing with THF (Figure 4.2). During the distillation step, the reactor head was fitted with a water-cooled condenser and the reactor contents stirred and slowly heated. Products not removed by distillation were recovered using THF, as described above. Because the boiling point of THF is well below that of the heavier products, good separation with minimal product losses was possible by distillation. The light oil fraction was recombined with the heavier fraction before use as a host oil.

Products containing $\text{Co}_2(\text{CO})_8$ were refluxed for three hours to destroy the carbonyl. To facilitate removal of the cobalt, silica-alumina powder was added to the liquid mixture prior to filtering.

Figure 4.1 Liquid Temperature and Pressure History of Amoco Resid Pretreatment Run # 54 (conditions: 440°C, 1000 psig (cold) H_2 , 1000 ppm Mo naphthenate, 86 min reaction time)

Figure 4.2 Stirred Autoclave Product Workup Scheme

4.2.3 Reactant and Product Characterization Techniques

Product gases, containing H_2 , H_2S and C_1 - C_5 compounds were analyzed using an HP 5880A GC. Light oils were analyzed with an HP 5890 series II GC/HP 5970 mass selective detector. A boiling point curve for oil samples was estimated by simulated distillation⁸⁹ using an HP 5890 series II GC. Untreated and pretreated resid samples were analyzed for their hydrogen type and aromatic content by 1H NMR using a Bruker 300 MSL spectrometer; samples were prepared in deuterated chloroform with tetramethylsilane for internal reference. Catalytic dehydrogenation⁹⁰ was used to measure the "available" hydrogen of untreated and pretreated resids. Available hydrogen was defined as the amount of hydrogen gas evolved when a sample was catalytically dehydrogenated at atmospheric pressure in boiling phenanthridine (bp=349°C). Reactions were carried out for 285 min over a reduced Pd/CaCO₃ catalyst. Metal contents (Ni, Fe and V) of selected samples were measured by The Pittsburgh Applied Research Corp. using the ICP technique. Elemental compositions (C, H, S, and N) of selected samples were determined by Galbraith Laboratories Inc. and CONSOL Inc.

4.3 Results and Discussion

4.3.1 Effect of Reaction Parameters on Pretreatment Product Yields

The reaction conditions and results of pretreatment runs made with the Amoco resid are summarized in Tables 4.1-4.4. The data are grouped by catalyst type.

By comparing runs made at different pressures, with all other reaction parameters constant, it was found that reaction pressure had little, if any, influence on product yields, within the 1500-3000 psig pressure range. This result is consistent with the finding of R.H.Heck et al.⁶⁵ that resid conversion to lighter products is independent of the presence of hydrogen.

The yield of reaction products appeared to depend on their time-temperature history (thermal severity). The thermal severity of each run was represented by the parameter equivalent residence time at 425°C (ERT). The calculation for ERT combines reaction temperature and time into a single parameter that is equivalent to the length of time the resid was reacted at 425 °C, assuming an overall activation energy of 50 kcal/mol. Runs made at a reaction temperature below 425°C had an ERT that was shorter than their actual reaction time. Conversely, runs made at a reaction temperature above 425°C had an ERT that was longer than their actual reaction time.

Table 4.1 Reaction Conditions and Results of Amoco Resid Pretreatments

Cat.	Cat Conc. wt%	Run No.	T, °C	P, psig	t, min	ERT, min	Gas, wt%	Asph, wt%	Coke, wt%	H ₂ uptake moles/100g	Avail-H, moles/100g	H/C	C/S	C/N
Fe-1	1.2	2	403	1630	60	18.6	5.3	19.2	0.6			1.44	47.9	197
Fe-1	1.1	8	413	2888	60	31.9	38.8	12.0	8.3					
Fe-1	1.4	10	402	2879	60	17.6	4.5	16.8	0.6					
Fe-1	1.0	13	432	2786	60	85.8	25.6	14.5	2.9					
Fe-1	1.0	15	405	3640	120	41.4	19.9	13.8	0.6					
Fe-2	2.3	4	414	1890	60	33.7	3.9	16.0	0.8			1.47	50.8	196
Fe-2	2.8	11	403	2978	60	18.6	4.2	13.2	3.7					
Fe-2	1.7	17	407	3064	175	67.4	29.0	7.4	1.7					
Fe-3	1.1	3	405	1491	60	20.7	6.5	18.1	0.7		0.63	1.46	51.1	197

Fe-1 = Fe₂O₃/SO₄

Fe-2 = Mo(CO)₆/Fe(CO)₅ (1.5-3.0 wt% Mo(CO)₆)

Fe-3 = Mo/Fe₂O₃/SO₄ (1 wt% Mo)

ERT= Equivalent residence time at 425°C

Avail H= available hydrogen as determined by catalytic dehydrogenation

H/C, C/S and C/N= atomic ratios of liquid (THF soluble) products

Table 4.2 Reaction Conditions and Results of Amoco Resid Pretreatments

Cat.	Cat Conc. wt%	Run No.	T, °C	P, psig	t, min	ERT, min	Gas, wt%	Asph, wt%	Coke, wt%	H ₂ uptake moles/100g	Avail-H, moles/100g	H/C	C/S	C/N
Fe-3	1.1	7	399	2532	60	14.9	11.9	16.2	0.5		0.66			
Fe-3	1.0	16	405	3344	200	69.0	29.8	9.6	0.6		0.60			
Fe-3	1.6	27	440	2145	120	256.2	32.6	8.8	11.3					
MN	1.6	73	375	1511	300	18.6				0.31	0.61	1.47	70.8	124
MN	0.8	23	407	1800	60	23.1	10.2	12.5	3.3					
MN	0.8	24	404	1685	60	19.6	4.4	16.1	1.4					
MN	0.9	26	441	1840	120	269.2	25.2	8.4	2.5			1.51	81.1	199
MN	0.8	30	441	1895	120	269.2	20.8	8.9	1.3	1.0				
MN	0.8	31	440	1894	100	213.5	36.8		9.8	0.9				

Fe-3 = Mo/Fe₂O₃/SO₄ (1 wt% Mo)

MN = Mo Naphthenate (6 wt% Mo)

ERT= Equivalent residence time at 425°C

Avail H= available hydrogen as determined by catalytic dehydrogenation.

H/C, C/S and C/N= atomic ratios of liquid (THF soluble) products

Table 4.3 Reaction Conditions and Results of Amoco Resid Pretreatments

Cat.	Cat Conc. wt%	Run No.	T, °C	P, psig	t, min	ERT, min	Gas, wt%	Asph, wt%	Coke, wt%	H ₂ uptake moles/100g	Avail-H, moles/100g	H/C	C/S	C/N
MN	3.3	33	440	1910	120	256.2	23.6	7.8	3.2	1.03				
MN	3.3	35	439	1970	120	243.8	32.0	6.0	2.5	1.41				
MN	1.6	53	440	1824	120	256.2	31.8	6.9	10.8	0.2				
MN	1.6	54	440	1855	86	183.6	20.2	10.6	1.5	0.68	0.29	1.5	71.2	133
MN	1.6	55	440	1840	95	202.8	18.4	11.5	1.9	0.69				
MN	1.7	59	445	1885	46	125.6	15.2	9.2	4.0	0.52				
MN	1.6	72	440	1459	15	32.0	0		1.3	0.41	0.36			
Shell	15.3	5	399	1852	60	14.9	7.9	8.9			0.13	1.56	144	336
Shell	12.5	9	398	2253	60	14.1	12.2	4.0	2.1		0.49			

MN = Mo Naphthenate (6 wt% Mo)

Shell = Shell 324 (Ni/Mo/Al)

ERT= Equivalent residence time at 425°C

Avail H= available hydrogen as determined by catalytic dehydrogenation

H/C, C/S and C/N= atomic ratios of liquid (THF soluble) products

Table 4.4 Reaction Conditions and Results of Amoco Resid Pretreatments

Cat.	Cat Conc. wt%	Run No.	T, °C	P, psig	t, min	ERT, min	Gas, wt %	Asph, wt %	Coke, wt %	H ₂ uptake moles/100g	Avail-H, moles/100g	H/C	C/S	C/N
Shell	9.0	64	435	1945	40	66.6	15.8		7.4					
none	0.0	6	403	1442	60	18.6	10.6	22.6	0.3					
none	0.0	12	404	2941	60	19.6	8.1	18.7	0.5					
none	0.0	28	440	2660	120	256.2	33.5	8.7	11.8					
none	0.0	63	435	2700	124	206.3	25.1		15.6		0.32			
none	0.0	66	441	3111	90	201.9	18.8		17.1					
none	0.0	67	442	2941	120	282.8	17.8		18.5					

Shell = Shell 324 (Ni/Mo/Al)

ERT= Equivalent residence time at 425°C

Avail H= available hydrogen as determined by catalytic dehydrogenation

H/C, C/S and C/N= atomic ratios of liquid (THF soluble) products

Figure 4.3, a plot of gas yield vs ERT for the various Amoco pretreatment runs, shows that gas production increased with increasing ERT. Hydrocarbon gases are believed to be generated by thermal cracking of aliphatic and alkylaromatic compounds. Although there is scatter in the data, it appears that the pretreatment runs made with the iron-based catalysts produced more gas than runs made with Mo naphthenate.

Figure 4.3 Gas Yield vs ERT for Pretreatments of Amoco Resid

Figure 4.4 shows that the amount of asphaltenes remaining in the pretreated THF-soluble products decreased as the reaction progressed, reaching a level of 5-10% of the starting material at long reaction times. The presence of a dispersed iron or Mo-based catalyst had little effect on asphaltene conversion. A reduction in amount of asphaltenes with increasing reaction severity is consistent with resid hydrocracking resulting largely from cracking of aliphatic fragments from aromatic centers in asphaltenes.

Figure 4.5 shows that at high thermal severity, the level of coke formation depends strongly on the catalyst used. The Mo naphthenate catalyst appeared to be effective at suppressing coke formation to below 5 wt%. Three Mo concentrations (500, 1,000 and 2,000 ppm) were tested at these conditions; all three gave similar results in suppressing coke formation. The Mo/Fe₂O₃/SO₄ catalyst was clearly ineffective at suppressing coke formation at high thermal severity. In the absence of a catalyst, coke formation was significant at high thermal severity.

Figure 4.4 Asphaltene Yield vs ERT for Amoco Resid Pretreatments

Figure 4.5 Coke Formation vs ERT for Amoco Pretreatments

Figure 4.6 shows that pretreatments made with the Mo naphthenate catalyst at high severity produced a THF-soluble product that had an atomic C/S ratio higher than that of the starting resid, indicating that sulfur had been removed. Pretreatments at lower severity using iron-based catalysts resulted in little change in the C/S ratio of the liquid product.

A plot of the atomic C/N ratio of pretreated THF-soluble products is shown in Figure 4.7; nitrogen heteroatoms were not removed by pretreatments, even at high thermal severity. For comparison, a hydrotreatment of the Amoco resid at 400°C for 60 min (ERT = 14.9 min) using the commercial Shell 324 hydrotreating catalyst produced a THF-soluble product that had a C/S ratio of 144 and a C/N ratio of 336. Based on this, the Shell 324 catalyst is superior to that of the dispersed Mo catalyst for bringing about HDS and HDN of the Amoco resid.

One objective for pretreating the resid was to increase its overall hydrogen content to 11.5%, which is equivalent to an atomic H/C ratio of around 1.6. Figure 4.8 shows that pretreatments made with the Mo naphthenate catalyst at severe reaction conditions resulted in a slight increase in the atomic H/C ratio of the THF-soluble product, reaching just over 1.5. Runs made with the iron-based catalysts at low severity had little effect on increasing the overall H/C ratio of the resid. These results indicate that it is not possible to raise the overall H/C ratio of the resid to a level of 1.6 with the dispersed catalysts used in this study.

Figure 4.6 Atomic C/S Ratio of the THF-soluble Product from Pretreatments of Amoco Resid

Figure 4.7 Atomic C/N Ratio of the THF-soluble Product from Pretreatments of Amoco Resid

Figure 4.8 Atomic H/C Ratio of the THF-soluble Product from Pretreatments of Amoco Resid

For comparison, hydrotreatment of the Amoco resid using the Shell 324 catalyst produced a THF-soluble product that had an overall H/C ratio of 1.56.

4.3.2 Effect of Pretreatment Temperature on the Available Hydrogen Content of the Host Oil

A critical property of a host oil is its ability to supply hydrogen to coal during coprocessing. One way of determining available (donatable) hydrogen content of a sample is to measure the amount of hydrogen gas released when it is catalytically dehydrogenate. Using this technique, we found that the available hydrogen content of the resids was sensitive to pretreatment temperature, as shown in Figure 4.9. Pretreatment of the Amoco resid at a reaction temperature of 440 °C, using Mo naphthenate as the catalyst, resulted in a decrease in available hydrogen content of the pretreated resid. When the same resid was pretreated at 400°C using either Mo/Fe₂O₃/SO₄ or Mo naphthenate catalyst, the available hydrogen content of the pretreated resid almost doubled.

It appears that, below 400°C, cracking rates were low and hydrogen was available on the catalyst surface to hydrogenate aromatic structures to form hydroaromatics and other hydrogen donors in the resid. At much higher reaction temperatures, cracking rates were significant and the demand for hydrogen was such that hydrogen was not available for hydrogenating aromatic structures in the resid. Under hydrogen poor conditions, it is possible that hydrogen is transferred from hydroaromatic structures

present in the resid to cap free radicals. The end result was a liquid product that, while lighter and richer in hydrogen, contains less available (donatable) hydrogen than that of the starting resid.

Figure 4.9 Available Hydrogen Content of the THF-Soluble Product from Pretreatments of the Amoco Resid

4.3.3 Pretreatment Experiments with the Citgo Resid

Four different pretreatments of the Citgo resid were performed around 400°C; one above this temperature and three below it. Conditions for these runs are summarized in Table 4.5. The first pretreatment, referred to as A, involved cracking the resid at 440°C for two hr under 1000 psig (cold) with the main objective of reducing molecular weight and removing sulfur and metals. The other three pretreatments, referred to as B through D, involved hydrogenating the resid at temperatures below 400°C where cracking is suppressed. The objective of these runs was to increase the available hydrogen content of the pretreated resid. From work on the Amoco resid, we did not expect the atomic H/C, C/S and C/N ratios of the pretreated resid to change as a result of the low temperature pretreatments. In pretreatment B the Citgo resid was reacted at 375°C under hydrogen gas, 1000 psig (cold), for 5 hr using 1000 ppm of Mo naphthenate. In C the Citgo resid was treated using a finely dispersed Mo/Fe₂O₃/SO₄ catalyst (2 wt%); other conditions were the same as used in B. In pretreatment D, the Citgo resid was dissolved in toluene and hydrogenated using dicobalt octacarbonyl, (Co₂(CO)₈), at 130°C for two hr under 2600 psig of 1:1 synthesis gas. The objective of this last pretreatment was to selectively hydrogenating polynuclear aromatic structures in the heavy oil to generate hydroaromatic compounds. In this report, the different pretreated resids are identified at host oil A, B, C, and D, corresponding to the pretreatment used.

Table 4.5 Reaction Conditions and Product Yields for Pretreatments of Citgo Resid

Conditions	A	B	C	D
Catalyst, concentration	MN, 1000 ppm	MN, 1000 ppm	Mo/Fe ₂ O ₃ /SO ₄ , 200 ppm Mo 13000 ppm Fe	Co ₂ (CO) ₈ , 6.2 wt%
Gas used	H ₂	H ₂	H ₂	CO/H ₂ (1:1)
Temperature, °C	440	375	375	135
Pressure (cold), psig	1,000	1,000	1,000	2,000
Time, hrs	2	5	5	2
Gas yield, wt%	25	1	3	0
Liquid yield, wt%	72	97	95	100
Coke yield, wt%	3	2	2	0

MN=Mo naphthenate

Note: elemental sulfur was added in pretreatments A, B and C in excess of amounts needed to sulfide the catalyst

Properties of the untreated Citgo resid and the four pretreated resids are listed in Table 4.6. Host oil A was lighter, based on wt% of distillate (bp < 565°C), than the untreated Citgo resid as well as the other pretreated resids. This was due to the higher pretreatment temperature used. The atomic H/C ratio of host oil A was slightly higher than that of the untreated resid and its C/S ratio was higher, indicating that sulfur had been removed. The atomic C/N ratio was slightly lower than that of the starting resid; little or no nitrogen had been removed. The available hydrogen content of host oil A was slightly higher than that of the untreated resid. The available hydrogen content of the host oils from the mild temperature pretreatments (B, C and D) was much higher than that of the untreated resid and of host oil A. The increase in available hydrogen for host oils B, C and D was slightly below the amount of hydrogen gas consumed during these runs, indicating significant hydrogen utilization. The atomic H/C, C/S and C/N ratios of the resids exposed to mild temperature pretreatments were essentially unchanged.

Table 4.6 Properties of Citgo Pretreated Host Oils

	Citgo resid	Host Oil A	Host Oil B	Host Oil C	Host Oil D
b.p. <565°C ^a , wt%		62.6	29.7	33.3	17.9
b.p. >565°C, wt%		37.4	70.3	66.7	82.1
C, wt%	85.4	85.1	85.9	85.6	84.8
H, wt%	10.1	10.6	10.4	10.8	10.0
S, wt%	3.4	2.2	2.7	2.9	2.9
N, wt%	0.8	0.9	0.9	0.8	0.8
O, wt%	0.3	1.2	0.1	0.0	1.5
Atomic H/C	1.42	1.49	1.45	1.51	1.42
Atomic C/S	67	103	85	79	78
Atomic C/N	124	110	111	125	124
V, ppm	555	393		472	
Ni, ppm	110	67		95	
Available ^b Hydrogen per 100 C atoms	9.9	12.4	16.8	14.0	17.5
wt% H ₂ added		1.4	0.5	0.5	0.5

a: b.p. <565°C consists of pentane-soluble oil having a simulated distillation b.p. <565°C (1050°F). b.p. >565°C consists of pentane-insoluble asphaltenes, and pentane-soluble oil having simulated distillation b.p. >565°C.

b: Value based on catalytic dehydrogenation.

4.4 Summary

Resid pretreatment experiments showed that mild temperature (400°C and lower) hydrogenation of Amoco and Citgo resids using iron-based and Mo naphthenate catalysts, as well as a cobalt carbonyl with a 1:1 mixture of CO:H₂, can produce a host oil that contains more available hydrogen atoms than that of the untreated resids. The atomic H/C , C/S and C/N ratios of these pretreated resids are similar to those of the starting resid. Pretreating the resids at 440 °C for two hr can cause significant cracking of the resid and removal of metals and sulfur; nitrogen levels remained unchanged. At these severe thermal conditions, Mo naphthenate at concentrations of 500 ppm or above was effective at suppressing coke below a level of 5 wt%. The host oil from high temperature pretreatments using Mo naphthenate had slightly higher atomic H/C ratio than that of the starting resid. However, their available hydrogen content remained low.

5.0 Heavy Oil-Coal Coprocessing Experiments

5.1 Objectives

The main objective for coprocessing petroleum resids with coal is to produce distillable liquid fuels. Coprocessing experiments were conducted with untreated Amoco and Citgo resids and pretreated resids to evaluate the effect of the pretreatments on the level of coal conversion and the yield of coal- and petroleum-derived oil products. We were also interested in determining if there was a synergeristic effect when coal and heavy oils were coprocessing. If such an effect exists, can it be enhanced by pretreating the heavy oil prior to reacting with coal?

5.2 Experimental

This section provides a description of the coprocessing experiments and the analytical methods used to characterize the reactants and products.

5.2.1 Properties of Coal Samples

Two different coal samples were used; an Illinois No.6 bituminous, and a Wyodak subbituminous. The Illinois coal was used in most of the project. Both coals were Argonne premium samples that had been ground to -100 mesh and stored in sealed glass vials. Properties of the coal samples are listed in Table 5.0.

Table 5.0 Properties of Argonne Coal Samples

	Illinois No.6	Wyodak
Moisture, wt%	8.0	28.1
Ash, wt%	14.3	6.3
Volatile matter, wt%	35.8	32.2
Rank	hvb	Subbituminous
C, wt% (maf)	77.7	75.0
H, wt% (maf)	5.0	5.3
N, wt% (maf)	1.4	1.1
S, wt% (maf)	2.4	0.5
Cl, wt% (maf)	0.06	0.03
O, wt% (maf)	13.5	18.0
Atomic H/C	0.77	0.85
f_a	0.71	0.62

f_a = Fraction of aromatic carbon, determined by the Brown and Ladner method

5.2.2 Coal-Heavy Oil Coprocessing Experiments and Product Workup

Coprocessing experiments were performed in a horizontal, stainless-steel microreactor fitted with a thermocouple to measure liquid temperature and a pressure transducer to measure reactor pressure. Figure 5.0 shows a schematic of the reactor system. In a typical run, the reactants were weighed (this totaled 5-10 g) and placed into the reactor body, which has a total volume of approximately 30 ml. The reactor was then sealed, pressure tested and charged with 1000 psig of H_2 at ambient temperature. Reactants were brought to the set reaction temperature, usually within 15 min, by immersing the reactor into a preheated fluidized sand bath. The reactor was shaken horizontally (3 times/sec) to ensure adequate mixing. At the end of the desired reaction time, the reactor was removed from the sand bath, quenched with water and cooled to room temperature. During each experiment, liquid temperature, reactor pressure and elapsed time were recorded.

At room temperature, gases were vented and collected for analysis. Gas production was determined by weight loss. Oil products were recovered by washing the reactor with pentane, asphaltenes were recovered by washing with THF. This involved flushing the reactor with several volumes of solvent and sonicating until the reactor was clean. The material that was insoluble in both pentane and THF consisted of coke, coal-derived mineral matter and, when used, catalyst. Pentane was removed from the filtered oil by a rotovapor at atmospheric pressure instead of under vacuum to minimize losses

of light components during the product recovery step. However, under these mild separation conditions, a small amount of pentane did remain dissolved in the oil. This amount was later measured by simulated distillation. THF was removed from the asphaltenes by rotovapor followed by vacuum drying at 90°C overnight.

Figure 5.0 Shaken Microreactor System

5.2.3 Product Characterization Techniques

Product gases, containing H_2 , H_2S , CO_2 , and C_1 - C_5 compounds were analyzed using an HP 5880A GC. Light oils were analyzed using an HP 5890 series II GC/HP 5970 mass selective detector. A boiling point curve for oil samples was estimated by simulated distillation using an HP 5890 series II GC. Oil and asphaltene samples were analyzed for their hydrogen type and aromatic content by 1H NMR using a Bruker 300 MSL spectrometer; samples were prepared in deuterated chloroform with tetramethylsilane for internal reference. Metal contents (V and Ni) of selected samples were determined by The Pittsburgh Applied Research Corp. using the ICP technique. Elemental compositions (C, H, S, and N) of selected samples were determined by Galbraith Laboratories Inc. and CONSOL Inc; oxygen was determined by difference. The phenolic oxygen concentration of oil samples was measured by CONSOL Inc. using an FTIR method⁹¹.

5.3 Results and Discussion

Coprocessing experiments were conducted in order to evaluate the four Citgo host oils (A, B, C, and D) under thermal (no added catalyst) as well as catalytic conditions. Results of these experiments were compared to base-line runs made with the untreated Amoco and Citgo resids. The bulk of the work was done with Illinois No.6 coal at coprocessing conditions consisting of 425°C, 1000 psig (cold) H₂ and 30 min reaction time. In these runs, the coal-feed concentration was varied from 10 to 50 wt%.

5.3.1 Effect of Host Oil Type and Coal-Feed Concentration on Coal Conversion

Tables 5.1-5.3 lists the reaction conditions and results (coal conversion and product yields) for coprocessing experiments made with the Illinois No.6 coal. The data are grouped by host oil type, starting with the untreated resids and ending with host oil D (Tables 4.5-4.6).

Table 5.1 Reaction Conditions and Results of Illinois No.6 Coprocessing Runs
(Conditions: 1000 psig (cold) H₂, 30 min reaction time, other conditions shown in Table)

Host Oil	Run	Cat.	Oil: Coal	T, °C	P, psig	Coal Conv wt%	Gas yield, wt%	Oil yield, wt%	Asph. yield, wt%	Coke yield wt%
Amoco Resid	69	none	2:1	427	2104	56	10.1	73.1	in oil	16.8
Citgo Resid	85	none	2:1	415	2046	74	3.3	69.4	13.9	8.7
Citgo Resid	87	none	1:1	427	2227	58	6.0	40.4	28.7	17.8
Citgo Resid	119	Fe-3	2:1	423	1889	81	6.7	70.2	12.3	6.1
Citgo Resid	136	MN	2:1	425	---	88	5.0	70.0	16.0	4.2
A	115	none	2:1	425	2097	74	4.7	48.4	34.5	7.6
A	114	none	1:1	425	2257	71	3.9	40.0	37.3	11.7
B	96	none	9:1	426	1756	85	4.9	95.1	-4.2	2.8
B	142	none	4:1	424	1805	85	7.1	78.0	8.3	3.7
B	91	none	2:1	427	1766	92	6.5	65.0	20.5	3.3

Fe-3 = Mo/Fe₂O₃/SO₄ (1 wt% Mo)

MN = Mo Naphthenate (6 wt% Mo)

A = Citgo resid hydrotreated with 1000 ppm Mo naphthenate at 440°C for 2 hr

B = Citgo resid hydrotreated with 1000 ppm Mo naphthenate at 375°C for 5 hr

Asph. = Asphaltenes (determined by difference)

Table 5.2 **Reaction Conditions and Results of Illinois No.6 Coprocessing Runs**
(Conditions: 1000 psig (cold) H₂, 30 min reaction time, other conditions shown in Table)

Host Oil	Run	Cat.	Oil: Coal	T, °C	P, psig	Coal Conv wt%	Gas yield, wt%	Oil yield, wt%	Asph. yield, wt%	Coke yield wt%
B	95	none	2:1	428	1790	93	5.1	67.3	19.8	3.0
B	141	none	1.5:1	424	1844	90	5.8	64.6	19.7	4.2
B	93	none	1:1	425	1849	89	6.0	46.8	34.8	5.2
C	100	none	9:1	425	1803	72	10.1	99.0	-16.2	5.6
C	143	none	9:1	423	1796	89	4.1	68.4	23.4	2.7
C	144	none	4:1	425	1813	94	3.3	61.3	29.9	2.6
C	117	none	2:1	425	1915	94	6.7	74.5	10.0	4.1
C	97	none	2:1	426	1874	93	4.1	46.9	39.9	4.4
C	145	none	1.5:1	425	1844	89	5.7	43.4	39.4	5.7
C	98	none	1:1	425	2311	56	6.0	31.0	36.7	19.1

B = Citgo resid hydrotreated with 1000 ppm Mo naphthenate at 375°C for 5 hr

C = Citgo resid hydrotreated with 2 wt% Mo/Fe₂O₃/SO₄ (1% Mo) at 375°C for 5 hr

Asph. = Asphaltenes (determined by difference)

Table 5.3 Reaction Conditions and Results of Illinois No.6 Coprocessing Runs
(Conditions: 1000 psig (cold) H₂, 30 min reaction time, other conditions shown in Table)

Host Oil	Run	Cat.	Oil: Coal	T, °C	P, psig	Coal Conv wt%	Gas yield, wt%	Oil yield, wt%	Asph. yield, wt%	Coke yield wt%
C	107	none	1:1	425	1890	90	6.5	53.3	27.4	5.6
D	106	none	9:1	424	1697	86	3.3	71.3	20.7	3.3
D	118	none	9:1	424	1710	43	6.5	85.0	0.3	6.8
D	147	none	4:1	424	1777	85	11.3	63.7	17.7	4.5
D	102	none	2:1	425	1032	88	4.2	78.5	7.7	4.8
D	137	none	2:1	426	2071	44	13.6	42.4	23.4	16.1
D	146	none	1.5:1	425	1781	90	5.2	47.5	37.2	4.4
D	103	none	1:1	426	1764	91	4.3	56.7	27.2	4.7

C = Citgo resid hydrotreated with 2 wt% Mo/Fe₂O₃/SO₄ (1% Mo) at 375°C for 5 hr

D = Citgo resid hydrotreated with 6.2 wt% Co₂(CO)₈ and 1:1 H₂:CO at 135°C for 2 hr

Asph. = Asphaltenes (determined by difference)

At baseline reaction conditions and an oil:coal feed ratio of 2:1, the Illinois coal reacted with the untreated Citgo resid, resulting in 74 wt% (maf) of coal converted to THF-soluble products and gases. When the Illinois coal was coprocessed with untreated Amoco resid under the same reaction conditions, 56 wt% of the coal was converted. The fraction of coal converted to gases and soluble products was not measured directly, but was determined by the amount of unconverted THF-insolubles. The following equation was used to calculate coal conversion.

$$Y_T = 100 * \left[1.0 - \frac{W_i - W_{ash} - W_{cat} - W_{pc}}{W_{maf}} \right] \quad (5-1)$$

where;

Y_T = coal conversion, wt% (maf)

W_{ash} , W_{cat} , W_i , W_{maf} , W_{pc} = mass of ash, catalyst, THF insolubles, maf coal, and petroleum-derived coke, g

The low coal conversions obtained with the two different untreated petroleum resids confirm that petroleum is a poor liquefaction solvent, due to its low supply of donatable hydrogen and its more aliphatic structure than coal. Increasing the supply of active hydrogen by addition of 2000 ppm of Mo to the Citgo resid, with other reaction parameters held constant, resulted in an increase in Illinois coal conversion, from 74

wt% to 88 wt%. However, the aim of this study was to determine whether coal conversion could be increased by improving the host solvent by pretreatment with a catalyst and a source of hydrogen.

Figure 5.1 shows the amount of Illinois coal that was converted to soluble products, determined using equation 5-1, when coprocessed with the various host oils. Coal conversion is plotted against the concentration of coal in the feed. The Figure shows that the conversions of Illinois coal with the resids that were pretreated at the milder temperatures (B, C and D) were higher than levels achieved with the untreated Citgo resid or with the resid that was pretreated at 440°C. Coal conversions in the Citgo resid decreased as the concentration of coal in the feed was increased. This trend demonstrates the limited ability of petroleum resid to aid in coal conversion. On the other hand, coal conversions with host oils B, C and D remained high at all coal loadings tested. Coal conversions in the last three host oils were slightly higher than conversions obtained when the coal was catalytically coprocessed with the Citgo resid in the presence of either Mo naphthenate (2000 ppm) or Mo/Fe₂O₃/SO₄ (2 wt%).

These results demonstrate that the resids that were pretreated at the milder temperatures were superior to untreated Citgo resid or the resid that was pretreated at 440°C when used to obtain higher levels of coal conversion. These results can be rationalized in terms of available hydrogen content of the three host oils, which was higher than that of host oil A or the untreated Citgo resid (Table 4.6).

Figure 5.1 Illinois No.6 Coal Conversions to Soluble Products vs Coal-Feed Concentration (coprocessing conditions: 425°C, 1000 psig (cold) H₂, 30 min reaction time, symbols represent the host oil used)

5.3.2 Effect of Host Oil Type and Coal Feed Concentration on Product Yields

Products from coal-heavy oil coprocessing include gases, oil, asphaltenes, and THF-insoluble coke (excludes coal-derived minerals and, when used, catalyst). Asphaltene yields were determined by difference. Oil yields were corrected to exclude dissolved pentane, based on simulated distillation. We found that product yield was affected by the concentration of coal in the feed. This can be seen by Figures 5.2-5.6, which show that oil yields reached maxima at coal-feed concentrations below 33 wt%. With every host oil, asphaltene yields were highest at a coal loading of 50 wt%, the highest coal-feed concentration studied. In general, asphaltene yields were lowest at coal-feed concentration where the oil yields were highest; both gas and coke yield remained at a low level and did not change significantly with coal-feed concentration, suggesting that high level of oil production are brought about by conversion of asphaltenes (petroleum- or coal-derived) to oils. Furthermore, oil yields appear to be enhanced by the presence of small amounts, less than 33 wt%, of coal. In coprocessing runs made with host oil A, oil yield decreased as coal was added to the feed, while asphaltene and coke yields increased.

Figure 5.2 Product Yields, as wt% of Feed, vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal+untreated Citgo resid, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.3 Product Yields, as wt% of Feed, vs Coal-Feed Concentration
(coprocessing conditions: Illinois No.6 coal + host oil A, 425°C, 1000 psig
(cold) H₂, 30 min reaction time)

Figure 5.4 Product Yields, as wt% of Feed, vs Coal-Feed Concentration
(coprocessing conditions: Illinois No.6 coal+ host oil B, 425°C, 1000 psig
(cold) H₂, 30 min reaction time)

Figure 5.5 Product Yields, as wt% of Feed, vs Coal-Feed Concentration
(coprocessing conditions: Illinois No.6 coal + host oil C, 425°C, 1000
psig (cold) H₂, 30 min reaction time)

Figure 5.6 Product Yields, as wt% of Feed, vs Coal-Feed Concentration
(coprocessing conditions: Illinois No.6 coal + host oil D, 425°C, 1000
psig (cold) H₂, 30 min reaction time)

Distribution of products from coprocessing Illinois coal with untreated Citgo resid and with the various pretreated resids is shown in Figure 5.7. Based on amount of oil yield, the host oils are ranked in the following order; $D > C > \text{untreated Citgo resid} > B > A$. The differences between the oil yield for host oils D, C and untreated Citgo resid are small; little improvement in oil yield was actually realized as a result of our pretreatments of the Citgo resid, an important conclusion of this study.

Figure 5.7 Product Yields, as wt% of Feed, vs Host Oil Used (coprocessing conditions: Illinois No. coal, 425°C, 1000 psig (cold) H₂, 30 min reaction time, host oil:coal=2:1)

The oil samples were characterized by elemental analysis to determine atomic H/C ratio and concentration of heteroatoms (S,N and O). A boiling point curve was obtained for each oil sample by simulated distillation. The curve was used to estimate the weight percent of material that had a boiling point within the gasoline range ($< 421^{\circ}\text{F}$), diesel range ($421\text{-}650^{\circ}\text{F}$), vacuum gas oil range ($650\text{-}1050^{\circ}\text{F}$), and vacuum resid range ($1050^{\circ}\text{F}+$). The fraction of aromatic carbon atoms, f_a , was determined by ^1H NMR.

Properties of the oils from the various coprocessing runs are listed in Table 5.4. In general, the oils had atomic H/C ratios above 1.6, a low concentration of nitrogen (about 0.3%) and contained significant amounts of oxygen (higher than 1.4 %) and sulfur (above 1.5 %). Essentially all of the oxygen is derived from the coal. Oil from the coprocessing runs with host oil A was the lightest of all the oils produced; over 55 wt% of this oil had a simulated distillation boiling range below 650°F . Host oil A was lighter than the other host oils. Product oils from the other coprocessing runs contained over 25 wt% of resid material; over 65 wt% of the oil boiled above 650°F , indicating that only a small fraction of the starting host oil and coal was converted to light distillate products.

Table 5.4 Properties of Pentane-Soluble Oil Products from Coprocessing Illinois No.6 Coal with Various Citgo Host Oils (conditions: 425°C, 1000 psig (cold) H₂, host oil:coal = 2:1, 30 min reaction time)

Run No.	Host oil	< 421°F wt%	421-650°F wt%	650-1050°F wt%	1050+ °F wt%	H/C	S, wt%	N, wt%	O, wt%	f _a , frac
85	Citgo resid	13.4	21.0	38.6	27.0	1.62	2.3	0.3	1.4	0.29
115	Oil-A	19.5	36.4	36.9	7.2	1.67	1.55	0.2	2.7	0.25
95	Oil-B	12.6	16.4	43.7	27.3	1.66	1.8	0.3	4.0	0.25
117	Oil-C	9.5	15.5	39.4	35.6	1.69	2.0	0.3	3.0	0.22
102	Oil-D	14.2	12.1	42.4	31.3	1.64	2.2	0.3	3.3	0.27

f_a = Fraction of aromatic carbons

Figures 5.8-5.12 show that there was only a small effect of coal-feed concentration on the boiling range distribution of the product oils. In general, the fraction of resid (1050°F+) decreased as the concentration of coal in the feed increased. The decrease in resid fraction was accompanied by an increase in the vacuum gas oil fraction (650-1050°F). Coal-feed concentration seemed to have had little effect on the fraction of light distillate products that boiled in the gasoline and diesel range.

Figure 5.8 Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + untreated Citgo resid, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.9 Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil A, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.10 Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil B, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.11 Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil C, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.12 Simulated Distillation Boiling Range Distribution of Oil vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil D, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

The asphaltenes from coprocessing runs had about the same concentration of S and O as the corresponding oils, but were richer in N and contained metals (Table 5.5). The asphaltenes had a high aromatic carbon content (over 60 %), according to ^1H NMR, and an average atomic H/C ratio of less than one.

Table 5.5 Properties of Asphaltene Products from Coprocessing Illinois No.6 Coal with Various Citgo Host Oils (conditions: 425°C, 1000 psig (cold) H_2 , host oil:coal = 2:1, 30 min reaction time)

Run No.	Host oil	H/C	S, wt%	N, wt%	O, wt%	V, ppm	Ni, ppm	f_a , frac
85	Citgo resid	0.35		2.5		1015	204	
115	A	0.86		1.8		206	43	0.74
95	B	0.96	1.8	1.8	3.5			0.62
117	C	0.86		1.9		750	205	0.75
102	D	0.90	2.2	1.8	2.9			0.66

5.3.3 The Amount of Coal Liquids in the Oil Products

The products from coprocessing of coal and heavy oil are a mixture of coal-derived and petroleum-derived material that cannot easily be separated. In order to estimate the fraction of coal liquids in the oil products, the phenolic oxygen concentration of oil samples was measured and correlated with the fraction of coal liquid in the products. Phenolic oxygen concentration was determined by the height of the peak in the IR spectrum produced by the stretching vibration of the phenolic O-H bond (3550-3100 $1/\text{cm}$). Since Illinois coal contains much more oxygen than that of the Citgo resid (Tables 4.0 and 5.0) and about half oxygen in coal is associated with phenols, it was assumed that the phenolic oxygen in the oil was essentially from the coal.

Robbins et al.⁹¹ measured the phenolic OH concentration of distillate and resid process oil samples throughout an extended test of the Lummus and HRI's two-stage coal liquefaction process. Although the phenolic OH concentration of the samples was sensitive to process variables such as catalyst age and space velocity, which influenced deoxygenation reactions, the authors still found it to be a useful indicator of liquefaction process performance. In the present study, we measured the phenolic oxygen concentration of both petroleum- and coal-derived oil samples and found them to be significantly different, as shown in Figure 5.12. The data point at zero coal-feed concentration was measured on oil obtained by processing the untreated Citgo resid without coal; all other conditions were the same as those used in the coprocessing runs.

From this measurement, we assigned the petroleum-derived oil component an average phenolic oxygen concentration of 0.26 wt%, which is roughly the oxygen concentration of the untreated resid. The two data points at 100 % coal-feed concentration were the phenolic oxygen of the oil products from processing Illinois coal in the non-hydrogen donor solvent, diphenylmethane (DPM); all other conditions were the same as those used in the coprocessing runs. The values, which average 1.78 wt%, have been corrected to account for the presence of DPM, and they reflect the estimated phenolic oxygen concentration of the coal-derived oil. This value is consistent with measurements made by Robbins et al.⁹¹ on coal liquefaction resid samples. Although the phenolic oxygen concentration of the coal-derived oil was much lower than the oxygen concentration of the unreacted coal, indicating that the coal had undergone deoxygenation, the value was still higher than that of the petroleum-derived oil sample. As shown in Figure 5.13, the phenolic oxygen concentration of the oil products fall between the two end points and increase as the concentration of coal in the feed is increased. This indicates that the amount of coal liquid in the oils increased as the concentration of coal in the feed was increased.

Figure 5.13 Concentration of Phenolic Oxygen in Oil Products vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal, 425°C, 1000 psig (cold) H₂, 30 min reaction time, symbols represent the host oil used)

An estimate of the fraction of coal liquid present in the oils allowed study of the effect of host oil type and coal-feed concentration on the yield of coal-derived and petroleum-derived oils. Using phenolic oxygen concentration, the weight fraction of coal liquid in the oil products was calculated by the following equation.

$$x = \left[\frac{C_t - C_p}{C_c - C_p} \right] \quad (5-2)$$

where,

x = fraction of coal-derived liquid in oil product

C_c, C_p, C_t = concentration of phenolic oxygen in coal-derived oil, petroleum-derived oil and oil products, wt%

The equation assumes that the phenolic oxygen concentration of the coal and petroleum components did not change as a result of interactions between coal and heavy oil during coprocessing. Table 5.6 lists the phenolic oxygen concentration as well as the calculated fraction of coal liquid (x) in the product oil samples.

Table 5.6 Phenolic Oxygen Concentration and Fraction of Coal-Derived Liquid in Pentane-Soluble Oil Samples

Run No.	Host oil	Oil/Coal	Phenol-OH meq/g	O as Phenol-OH, wt%	x (coal liquid fract.)
86	Citgo resid	1:0	0.163	0.26	0
85		2:1	0.340	0.54	0.18
87		1:1	0.534	0.85	0.39
115	A	2:1	0.436	0.70	0.29
114		1:1	0.524	0.84	0.38
96	B	9:1	0.375	0.60	0.22
95		2:1	0.408	0.65	0.26
93		1:1	0.599	0.96	0.46
100	C	9:1	0.331	0.53	0.18
97		2:1	0.413	0.66	0.26
117		2:1	0.450	0.72	0.30
107		1:1	0.644	1.03	0.51
106	D	9:1	0.253	0.40	0.09
102		2:1	0.396	0.63	0.24
103		1:1	0.560	0.90	0.42
105	DPM	2:1	1.15	1.84	1.0
109		1:1	1.08	1.73	1.0

Three oil yield curves for each host oil-coal combination are shown in Figures 5.13-5.17. The top curve represents the overall oil yield. The yield of coal-derived oil, as measured by phenolic oxygen content, is represented by the lowest curve. It starts at zero and ends at 28 wt%. This last point was obtained by processing the Illinois coal in DPM. The yield of petroleum-derived oil, determined by difference, is represented by the middle curve. The starting point for this curve was determined by processing the resid without coal, with all other reaction conditions the same as those used in coprocessing runs. The straight dashed lines drawn between the end points represent the oil yields assuming no interaction between coal and host oil. These lines are simply the linear extrapolation of oil yields obtained when the coal and resids were processed separately. Any deviation of the experimental data points above or below the dashed lines would imply interaction between coal and host oil which either resulted in an enhancement or reduction in the oil yield.

In coprocessing runs with host oil C (Figure 5.17) and D (Figure 5.18) the presence of small amounts (less than 33 wt%) of coal seemed to enhance the yield of petroleum-derived oil; the data points were above the dashed line. This behavior was also seen with the untreated Citgo resid (Figure 5.14). Conversely, the presence of coal with host oil B (Figure 5.16) caused a slight reduction in the yield of petroleum-derived oil, and the yield of oils from host oil A (Figure 5.15) were adversely affected by the presence of coal.

The untreated Citgo resid and host oil A had no enhancing effect on the

production of coal-derived oil; the data points fell on the dashed line. On the other hand, the resids that were pretreated at the milder temperatures (B, C and D) brought about a higher yield of coal-derived oil than were obtained in DPM.

Figure 5.14 Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + untreated Citgo resid, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.15 Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil A, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.16 Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil B, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.17 Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (coprocessing conditions: Illinois No.6 coal + host oil C, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

Figure 5.18 Yield of Total (top curve), Petroleum-Derived (lower curve) and Coal-Derived (bottom curve) Oils vs Coal-Feed Concentration (Coproprocessing conditions: Illinois No.6 coal + host oil D, 425°C, 1000 psig (cold) H₂, 30 min reaction time)

5.3.4 Effect of Coal Type on Coprocessing

Several coprocessing runs were made with a Wyodak coal. Reaction conditions were the same as those used with the Illinois coal (i.e., 425°C, 1000 psig (cold) H₂, 30 min, host oil:coal = 2:1). Results of coprocessing runs made with the Wyodak coal are listed in Table 5.7. The Wyodak coal was less reactive than the Illinois coal when thermally (no added catalyst) coprocessed with untreated Citgo resid or host oil C. Oil yields were also lower in runs made with the Wyodak coal as compared to the Illinois coal.

When the Wyodak coal was catalytically coprocessed with untreated Citgo resid in the presence of 2000 ppm of Mo naphthenate, coal conversion increased to from 54 to 98 wt%, which was higher than the level achieved with the Illinois coal under the same conditions. The oil yield also increased from 58 % without catalyst to 65.5 % with the catalyst.

Table 5.7 Results of Coprocessing Wyodak Coal with Various Citgo Host Oils
(conditions: 425 °C, 1000 psig (cold) H₂, host oil:coal = 2:1,
30 min reaction time)

Run No.	Catalyst	Host oil	Coal Conv., wt%	Gas yield, wt%	Oil yield, wt%	Asph. yield, wt%	Coke yield, wt%
131	none	Citgo resid	54	8.2	58.0	20.0	11.7
135	MN	Citgo resid	98	6.7	65.5	23.3	2.4
133	none	C	83	6.6	45.0	40.1	6.2

MN = Mo Naphthenate (6 wt% Mo)

Asph. = Asphaltenes (determined by difference)

5.3.5 Effect of the Presence of Hydrogen Gas on Coprocessing

Coprocessing experiments were conducted using an inert atmosphere of helium to evaluate host oils in the absence of hydrogen. The results of these runs are summarized in Table 5.8. The resids, untreated as well as pretreated, could not bring about high levels of coal conversion in the absence of hydrogen gas. Hydrogen gas is evidently utilized as the main supply of hydrogen.

The conversion of the Wyodak coal was the same with or without hydrogen gas under non-catalytic conditions. However, the conversion of the Illinois coal was higher in the presence hydrogen. This is probably due to the fact that the Illinois coal contained about 1.2 wt% pyrite, which is converted to pyrrhotites at reaction conditions. The Wyodak coal contained only about 0.2 wt% pyrite.

Table 5.8 Results of Coprocessing Experiments Under Helium (conditions: 425 °C, host oil:coal = 2:1, 30 min reaction time)

Run	Coal	Host oil	Pavg, psig	Coal Conv., wt%	Gas yield, wt%	Oil yield, wt%	Asph. yield, wt%	Coke yield, wt%
128	Ill#6	Citgo resid	2043	48	8.3	45.1	26.9	14.9
126	Ill#6	C	2201	56	8.5	43.1	31.1	12.6
137	Ill#6	D	2071	44	13.6	42.4	23.4	16.1
130	Wyodak	Citgo resid	2236	54	10.0	47.1	29.4	11.4

5.3.6 Host Oil Demetallation by Coprocessing with Coal

The untreated Citgo resid contained about 560 ppm of V and 110 ppm of Ni, as determined by ICP. As shown in Table 5.9, about 85% of V and 82 % of Ni was associated with the asphaltenes, the remainder with the oils. Analysis of products from coprocessing Citgo resid with Illinois coal showed that significant amounts of V and Ni were removed, becoming concentrated in the solids. At a host oil:coal feed ratio of 2:1, 14% of V and 53 % of Ni was removed with the solids. At a higher host oil:coal ratio of 1:1, 50% of the V was removed with the solids.

Table 5.9 Distribution of V and Ni in Products Obtained by Coprocessing Illinois No.6 Coal and Untreated Citgo Resid (conditions: 425°C, 1000 psig (cold) H₂, 30 min, host oil:coal = 2:1, and 1:1)

	Citgo resid before coprocessing	Citgo resid + Ill#6 (2:1) coprocessing products	Citgo resid + Ill#6 (1:1) coprocessing products
V Distribution, wt%			
Oils	15	4	4
Asphaltenes	85	83	46
Solids		14	50
Ni Distribution, wt%			
Oils	18	4	4
Asphaltenes	82	43	56
Solids		53	40

The concentration of V and Ni in host oil A was lower than that of the untreated Citgo resid, and almost all the metals were associated with the asphaltenes. Pretreatment of the Citgo resid at 440°C with 1000 ppm of Mo naphthenate was effective at reducing its metal content and was especially effective at removing essentially all the metals from the oil fraction.

Coprocessing of host oil A with Illinois coal at a host oil:coal feed ratio of 2:1 resulted in the removal of 77% of V and 63% of Ni from the host oil (Table 5.10).

Table 5.10 Distribution of V and Ni in Products Obtained by Coprocessing Illinois No.6 Coal and Host Oil A (conditions: 425°C, 1000 psig (cold) H₂, 30 min, host oil:coal = 2:1)

	Host Oil A before coprocessing	Host Oil A + Ill#6 (2:1) coprocessing products
V Distribution, wt%		
Oils	0	0
Asphaltenes	100	23
Solids		77
Ni Distribution, wt%		
Oils	1	1
Asphaltenes	99	37
Solids		63

Host oil C contained slightly less V and Ni than the untreated Citgo resid, and 95% of the metals were concentrated in the asphaltenes. As shown in Table 5.11, when the host oil was coprocessed at an oil:coal feed ratio of 2:1, about 35 % of V and 14% of Ni was removed with the solids. Further removal of V and Ni was realized when the host oil was coprocessed at an oil:coal feed ratio of 1:1.

Table 5.11 Distribution of V and Ni in Products Obtained by Coprocessing Illinois No.6 Coal and Host Oil C (conditions: 425°C, 1000 psig (cold) H₂, 30 min, host oil:coal = 2:1, and 1:1)

	Host Oil C before coprocessing	Host Oil C + Ill#6 (2:1)	Host Oil C + Ill#6 (1:1)
V Distribution, wt%			
Oils	5	5	5
Asphaltenes	95	60	43
Solids		35	52
Ni Distribution, wt%			
Oils	5	5	5
Asphaltenes	95	81	54
Solids		14	41

5.4 Summary

Coprocessing Illinois No.6 coal with untreated Citgo resid and the four host oils allowed us to evaluate the effect of our pretreatments on coprocessing performance. The resids that had been hydrogenated at milder temperatures (B, C and D) were better liquefaction solvents and brought about higher levels of coal conversion than the untreated Citgo resid and the resid pretreated at 440°C. Coal conversions obtained in these three host oils were slightly higher than levels obtained under catalytic coprocessing using either Mo naphthenate or Mo/Fe₂O₃/SO₄. The level of coal conversion in the resid that was pretreated at 440°C was about the same as that obtained in the untreated Citgo resid. The level of coal conversion was related to the available hydrogen content of the host oil. Host oils B, C and D had significantly higher available hydrogen than host oil A or the untreated Citgo resid.

Oil and asphaltene yields were strongly affected by the concentration of coal in the feed, but were only slightly improved by our milder temperature pretreatments. In the untreated Citgo resid and in B, C and D, oil product yields reached maxima at coal-feed concentrations in the range 10 to 33 wt%. In every run, asphaltene product yields reached a maxima at 50 wt%, the highest coal loading used. In general, asphaltene yields were at their lowest where oil yields were at their highest.

Based on oil product yield, the host oils were ranked in the following order; D > C > untreated Citgo resid > B > A; but, differences between C, D and the

untreated Citgo resid were small.

The pentane-soluble oils from coprocessing the Illinois coal with the various Citgo heavy oils (untreated resid and pretreated host oils) had atomic H/C ratios greater than 1.6, low concentrations of nitrogen (around 0.3%), and significant amounts of sulfur and oxygen (higher than 1.4%). Except for the oil product from host oil A, the oils contained over 25 wt% of resid material (bp > 1050°F); over 65 wt% of the oil contained hydrocarbons that boiled above 650°F. The boiling range of the oils was slightly affected by the concentration of coal in the feed. The fraction of resid material decreased slightly and the fraction of 650-1050°F material increased somewhat as the coal-feed concentration was increased. There was little change in the fraction of light distillate boiling in the gasoline or diesel range.

The asphaltene products were rich in metals, and contained about the same level of sulfur and oxygen and a higher level of nitrogen than the oils. Over 60% of the carbon in the asphaltenes were aromatic and the overall atomic H/C ratio was less than one. This suggests the presence of condensed and/or substituted aromatic structures.

The fraction of coal liquids in the product oils was determined by phenolic oxygen concentration. The yield of oils from Illinois coal when coprocessed in the resids that were pretreated at milder temperatures (B, C or D) was higher than that obtained with the resid pretreated at 440°C or with untreated Citgo resid. The coal-derived oil yields with host oil A were the same as those obtained in the untreated Citgo resid, and were consistent with oil yields obtained in DPM.

The presence of less than 33 wt% of Illinois coal enhanced the yield of oil from the untreated Citgo resid and host oils C and D. When these same host oils were coprocessed with Illinois No.6 coal at a coal-feed concentration of 50 wt%, the yield of petroleum-derived oils decreased. The presence of Illinois coal caused a reduction in the yield of oil from host oils A and B at all coal-feed concentrations studied.

The Wyodak coal was less reactive (i.e., lower coal conversion and lower oil yields) than the Illinois coal under identical non-catalytic coprocessing conditions. Wyodak coal conversion was significantly increased when it was coprocessed in the presence of Mo naphthenate (2000 ppm Mo).

Hydrogen gas is needed during coprocessing of Illinois coal and the untreated and pretreated host oils. Without hydrogen, coal conversions and oil yields are low.

When the Citgo host oils were coprocessed with the Illinois coal, V and Ni was removed with the THF-insoluble solids. The redistribution of V and Ni from petroleum asphaltenes to solids was highest for coprocessing runs made with host oil A and lowest for the untreated Citgo resid. Metal removal increased as the concentration of coal in the feed was increased.

6.0 CONCLUSIONS

In this study the effect of pretreating a petroleum resid, by catalytic hydrogenation and hydrocracking reactions, on coprocessing performance (i.e., coal conversion and oil yield) was investigated. The results led us to the following conclusions concerning the effect of pretreating the resids on coprocessing in general.

(1) Pretreatment of heavy oil prior to coprocessing can lead to an increase in the amount of coal converted to soluble products. The level of coal conversion during coprocessing increased when the resid was first hydrogenated at 375°C using Mo naphthenate or Mo/Fe₂O₃/SO₄, or at 135°C with Co₂(CO)₈ and 1:1 synthesis gas. The pretreated resids which had increases in available hydrogen content provided higher coal conversions when compared to the untreated resids.

(2) Pretreating the resid at 440°C with Mo naphthenate made it lighter and lower in sulfur and metals, but did not improve it as a host oil; coal conversions with the pretreated resid were about the same as those obtained with untreated resid.

(3) At best, only a small fraction of the host oils and coal were converted to light distillate products during our coprocessing runs. This was true for the untreated as well as the pretreated resids.

(4) Oil yields were only slightly improved by our pretreatments, and were strongly

affected by the concentration of coal in the feed.

(5) Determination of phenolic oxygen in the products of coprocessing by FTIR is an effective way for estimating the fraction of coal liquids in the oil products from coprocessing.

(6) There was a synergy between coal and untreated resid and resids pretreated at milder temperatures during coprocessing that brought about an enhancement in oil yield; however, the effect was small.

ACKNOWLEDGMENT

The financial assistance of the U.S. Department of Energy, Pittsburgh Energy Technology Center, is gratefully acknowledged. We would also like to thank the Citgo Oil Company as well as the Amoco Oil Company for providing the petroleum resid samples, and Argonne Premium Coal Sample Bank for providing coal samples. A thanks goes to CONSOL Inc., in particular to Dr Susan Brandes, for providing elemental and FTIR analyses of samples.

BIBLIOGRAPHY

1. Takeshita, K. and Mochida, I., Jap. Pat. 80-45703 (1980)
2. Sato, Y., Yamamoto, Y., Kamo, T., Inaba, A., Miki, K., and Saito, I., "Effect of Hydrotreatment of Various Heavy Oils as Solvent for Coal Liquefaction", Energy & Fuels, Vol 5, (1991), pp. 90-102.
3. Curtis, C.W., Tsai, K.-J. and Guin, J.A., "Effect of Solvent Composition on Coprocessing Coal with Petroleum Residua", Fuel Processing Technology, Vol 16, (1987), pp. 71-87.
4. Bedell, M.W., Curtis, C.W. and Hool, J.L., "Reactivity of Argonne coals in the presence of cyclic olefins and other donors", Fuel Processing Technology, Vol 37, (1994), pp. 1-18.
5. Owens, R.M. and Curtis, C.W., "An Investigation of Hydrogen Transfer from Naphthenes during Coprocessing", Energy & Fuels, Vol 8, (1994), pp. 823-829.
6. Given, P.H., Fuel, Vol. 39, (1960), pp 147.
7. Proceedings of the EPRI Conference on Coal Catalysis, Palo Alto, CA., 1973, Wiser, W.H., p. 3.
8. Shinn, J.H., "From Coal to Single-Stage and Two-Stage Products: a Reactive Model of Coal Structure," Fuel, Vol. 63, (1984), pp. 1187-1192.
9. Haenel, M.W., "Recent Progress in Coal Structure Research," Fuel, Vol. 71, (1992), pp. 1211-1223.
10. Gorbaty, M.L., "Prominent Frontiers of Coal Science: Past, Present and Future," Fuel, Vol. 73, (1994), pp. 1819-1827.
11. Coal Liquefaction, a Research Needs Assessment-Technical Background, DOE report, March 1989.
12. Whitehurst, D.D., Mitchell, T.O., and Farcasiu, M., Coal Liquefaction (New York: Academic Press, 1980), pp. 274-345.

13. McMillen, D.F., Ripudaman, M., and Tse, D.S., "Interactive Effects Between Solvent Components: Possible Chemical Origin of Synergy in Liquefaction and Coprocessing," Energy & Fuels, Vol. 5, (1991), pp. 179-187.
14. Malhotra, R., and McMillen, D.F., "Relevance of Cleavage of Strong Bonds in Coal Liquefaction," Energy & Fuels, Vol. 7, (1993), pp. 227-233.
15. Malhotra, R., McMillen, D.F., Tse, D.S., Lorents, D.C., Ruoff, R.S., and Keegan, D.M., "Hydrogen-Transfer Reactions Catalyzed by Fullerenes," Energy & Fuels, Vol. 7, (1993), pp. 685-686.
16. Derbyshire, Frank J., Catalysis In Coal Liquefaction (London: IEA Coal Research, June 1988).
17. Derbyshire, F. and Hager, T., "Coal Liquefaction and Catalysis," Fuel, Vol. 73, No. 7, (1994), pp. 1087-1092.
18. Cui, Z. and Sun, J., "Lignite Liquefaction with Promoted Iron Ores," Fuel, Vol. 73, (1994), pp. 429-431.
19. Wei, X-Y, Ogata, E., Zong, Z-M., and Niki, E., "Effects of Iron Catalyst Precursors, Sulfur, Hydrogen Pressure and Solvent Type on the Hydrocracking of di(1-Naphthyl)Methane," Fuel, Vol. 72, (1993), pp. 1547-1552.
20. Hirchon, A.S. and Wilson Jr, R.B., "Highly Dispersed Coal Liquefaction Catalysts," Fuel, Vol. 71, (1992), pp. 1025-1031.
21. Artok, L., Schobert, H.H., and Davis, A., "Temperature-Staged Liquefaction of Coals Impregnated with Ferrous Sulfate," Fuel Processing Technology, Vol. 32, (1992), pp. 87-100.
22. Yokoyama, S., Yamamoto, M., Yoshida, R., Maekawa, Y., and Kotanigawa, T., "Catalytic Behaviour of Sulphate and Sulphide in S-Promoted Iron Oxide Catalysts for Liquefaction of Bituminous Coal and Lignite," Fuel, Vol. 70, (1991), pp. 163-168.
23. Yokoyama, S., Yoshida, R., Narita, H., Kodaira, K., and Maekawa, Y., "Catalytic Activity of Various Iron Sulphides in Coal Liquefaction," Fuel, Vol. 65, (1989), pp. 164-170.
24. Berthelot, P.E.M., Ann. Chim. Phys., Vol. 20, (1870), pp. 526.

25. Fraenkel, D., Pradhan, V.R., Tierney, J.W., and Wender, I., "Liquefaction of Coal Under Mild Conditions, Catalysis by Strong Acids, Iodine and their Combination," Fuel, Vol. 70, (1991), pp. 64-74.
26. Vassallo, A.M., Wilson, M.A. and Attalla, M., "Promotion of Coal Liquefaction by Iodomethane," Energy & Fuels, Vol. 2, (1988), pp. 539-547.
27. Attalla, M.I., Wilson, M.A., Quezada, R.A., and Vassallo, A.M., "Promotion of Coal Liquefaction by Iodomethane. 2. Reactions of Coal Model Compounds with Iodomethane at Coal Liquefaction Temperatures," Energy & Fuels, Vol. 3, (1989), pp. 59-64.
28. Joseph, J.T., Duffield, J.E. and Davidson, M.G., "Iodine-Catalyzed Coal Liquefaction," Energy & Fuels, Vol. 6, (1992), pp. 764-770.
29. ASTM Designation:D 2007-91, Annual Book of ASTM Standards.
30. Proceedings of the Division of Petroleum Chemistry, ACS Dallas Meeting, April 9-14, 1989, "Characterization of Coal Reaction Products Using Preparative-Scale Liquid Chromatography and Automated Thin-Layer Chromatography by M.B. Perry, D.L. Cillo and T.C. Barrage" (Preprints), pp. 229-235.
31. Speight, J. G., The Chemistry and Technology of Petroleum (New York: Marcel Dekker, 1991).
32. Yen, T.F., ed., The Role of Trace Metals in Petroleum, "Chemical Aspects of Metals in Native Petroleum by T.F. Yen" (Ann Arbor, MI: Ann Arbor Science Pub. Co., 1975).
33. Schuetze, B., and Hofmann, H., "How to Upgrade Heavy Feeds," Hydrocarbon Processing, (February 1984), pp. 75-82.
34. Proceedings of the UNITAR/UNDP 5th International Conference on Heavy Crude and Tar Sands, Caracas, Venezuela, August 5-10, 1991, "Upgrading Heavy Crudes: A Wide Range of Excellent Technologies Now Available, by B.L. Schulman and R. L. Dickenson, (Preprint).
35. De Baise, R. and Elliot, J.D., Hydrocarbon Processing, Vol. 61, No.5, (1982), pp. 99-104.
36. Main Meeting of German Society of Petroleum and Coal Engineering, DMGK-Haupttagung, Oct. 1978, W.O. Taff, p. 26.

37. Akbar, M. and Geelen, H., Hydrocarbon Processing, Vol. 60, No.5, (1981), pp. 81-85.
38. ASTM Designation: D 524-88, Annual Book of ASTM Standards.
39. Reynolds, B.E., Brown, E.C. and Silverman, M.A., "Clean Gasoline via VRDS/RFCC," Hydrocarbon Processing, (April 1992), pp. 43-48.
40. Scheuerman, G.L., Johnson, D.R., Reynolds, B.E., Bachtel, R.W., and Threlkel, R.S., "Advances in Chevron RDS Technology for Heavy Oil Upgrading Flexibility," Fuel Processing Technology, Vol. 35, (1993), pp. 39-54.
41. Christ, M.A., Oil & Gas Journal, (May 28, 1979).
42. Van Zijll Langhout, W.C., Oil & Gas Journal, (Dec.1, 1980), pp. 120-126.
43. Anon, Hydrocarbon Processing, Vol.61, No. 9, (1982), p.135.
44. Sikonia, J.G., Hydrocarbon Processing, Vol. 59, No.6, (1980), pp. 73-79.
45. Choudhary, N. and Saraf, D.N., "Hydrocracking: A Review," Ind. Eng. Chem. Prod. Res. Dev., Vol 14, No.2, (1975), pp. 74-83.
46. Mohanty, S., Kunzru, D., and Saraf, D.N., "Hydrocracking: a Review," Fuel, Vol. 69, (1990), pp. 1467-1473.
47. Thakur, D.S., and Thomas, M.G., "Catalyst Deactivation in Heavy Petroleum and Synthetic Crude Processing: A Review," Applied Catalysis, Vol. 15, (1985), pp. 197-225.
48. Proceedings of the 205th National Meeting, American Chemical Society, Denver, CO, March 28-April 2, 1993, "Metal and Coke Deactivation of Resid Hydroprocessing Catalysts by J. Bartholdy and B.H. Cooper" (Preprint).
49. Absi-Halabi, M., Stanislaus, A, and Trimm, D.L., "Coke Formation on Catalysts During the Hydroprocessing of Heavy Oils," Applied Catalysts, Vol. 72, (1991), pp. 193-215.
50. Mitchell, P.C and Scott, C.E., "The Interaction of Vanadium and Nickel Porphyrins and Metal-Free Prophyrins with Molybdenum-Based Hydroprocessing Catalysts," Polyhedron, Vol. 5, No.1.2, (1986), pp. 237-241.
51. Van Driesen, R.P. and Fornoff, L.L., "Upgrade Resids with LC-Fining," Hydrocarbon Processing, (September 1995), pp. 91-95.

52. Niemann, K., and Wenzel, F., "The Veba-Combi-Cracking Technology: An Update," Fuel Processing Technology, Vol. 35, (1993), pp. 1-20.
53. Proceedings of the 2nd Unitar Conference, February 7-17, 1982, Anderson, R.F.
54. Proceedings of the 1983 NPRA Annual Meeting, San Francisco, CA, March 1982, "CANMET Hydrocracking Handles Wide Range of Heavy Crude by R.J. Waugh, L.W. Chambers, M.A. Menzies, and D.J. Patmore" (Preprint).
55. Bearden, R. and Aldridge, C.L., Energy Progress, Vol. 1, (1981), pp. 44-48.
56. Glannetto, G.E., Perot, G.R. and Guisnet, M.R., "Hydroisomerization and Hydrocracking of n-Alkanes," Ind. Eng. Chem. Prod. Res. Div., Vol. 25, (1986), pp. 481-490.
57. Vansina, H, Baltanas, M.A. and Froment, G.F., " Hydroisomerization and Hydrocracking: Product Distribution From n-Octane and 2,2,4-Trimethylpentane," Ind.Eng.Chem.Res.Dev. Vol. 22, (1983), pp. 526-531.
58. Steijns, M, Froment, G, Jacobs, P., Uytterhoeven, J, and Weitkamp, J., "Hydroisomerization and Hydrocracking: Product Distribution From n-Decane and n-Dodecane," Ind.Eng.Chem.Prod.Res.Dev., Vol. 20, (1981), pp. 654-660.
59. Coonradt, H.L., and Garwood, W.E., "Mechanism of Hydrocracking, Reactions of Paraffins and Olefins," I&EC Processing Design and Development, Vol.3, No.1, (1964), pp. 38-45.
60. Greensfelder, B.S., Voge, H.H. and Good, G.M., "Catalytic and Thermal Cracking of Pure Hydrocarbons," I&EC, Vol.41, No. 11, (1949), pp. 2573-2584.
61. Smith, C.M. and Savage, P.E., "Reactions of Polycyclic Alkylaromatics, Hydrogenolysis in Binary Mixtures," Energy & Fuels, Vol. 8, (1994), pp. 545-551.
62. Bianco, A.D., Panariti, N., Anelli, M., Beltrame, P.L., and Carniti, P., "Thermal Cracking of Petroleum Residues, 1. Kinetic Analysis of the Reaction," Fuel, Vol. 72, (1993), pp. 75-80.
63. Del Bianco, A., Panariti, N., Prandini, B., Beltrame, P.L., and Carniti, P., "Thermal Cracking of Petroleum Residues, Hydrogen-Donor Solvent Addition," Fuel, Vol. 72, (1993), pp. 81-85.

64. Proceedings of the 205th National Meeting, ACS, Denver, CO, March 1993, "Hydrocracking Kinetics of Gudao Residue in the Presence of Dispersed-Phase Mo Catalyst by C. Liu, J. Zhou, G. Que, W. Liang, and Y. Zhu" (Preprint).
65. Proceedings of the 205th National Meeting, ACS, Denver, CO, March 1993, "Kinetic and Mechanistic Effects in Residue Hydrocracking by R.H. Heck and F.T. DiGuseppi" (Preprint).
66. Heck, R.H., Rankel, L.A. and DiGuseppi, F.T., "Conversion of Petroleum Resid from Maya crude: Effects of H-donors, Hydrogen Pressure and Catalyst," Fuel Processing Technology, Vol.30, (1992), pp. 69-81.
67. Friedman, S., Metlin, S., Svedi, A., and Wender, I., "Selective Hydrogenation of Polynuclear Aromatic Hydrocarbons," J. Org. Chem, Vol. 24, (1959), pp. 1287.
68. Wender, I., Levine, R., and Orchin, M., J. Am. Chem. Soc., Vol. 72, (1950), pp. 4375.
69. ARCO Chemical Company, "Catalytic Hydrogenation of Coal-Derived Liquids", Project SEACoke, Phase II, Final Rep., Contract No. 14-01-0001-472, Off. Coal Res., U.S. Dept. of Interior, Washington, DC (1966).
70. Coal Liquefaction, A Research Needs Assessment, Technical Background, U.S. DOE Contract No., DE-AC01-87er30110, (February, 1989), pp. 7-25.
71. Proceedings of the Ninth Annual EPRI Contractors Conference on Coal Liquefaction, Palo Alto, CA, May 1984, "The Chevron Co-Refining Process by J.H. Shinn, A.J. Dahlberg, C.W. Keuhler, and J.W. Rosenthal" (Preprint).
72. Proceedings of the DOE Direct Liquefaction Contractors' Review Meeting, Pittsburgh, PA, October, 1986, "LCI's Two-Stage Co-Processing Route: Continuous Bench-Scale Operations by M. Greene, A. Gupta and W. Moon" (Preprints).
73. Proceedings of the Fifteenth Annual EPRI Conference on Fuel Science, Pal Alto, CA, August, 1991, "HRI's Co-Processing Program by J. Duddy, S. Panvelker and G. Popper" (Preprint).
74. Proceedings of the CANMET Coal Conversion Contractors' Review Meeting, Calgary, Alberta, November, 1984, "CANMET Co-Processing: A Status Report by J.F. Kelly, S.A. Fouda, P.M. Rahimi, and M. Ikura" (Preprints).

75. Derbyshire, F.J. and Whitehurst, D.D., "Study of Coal Conversion in Polycondensed Aromatic Compounds," Fuel, Vol. 60, (1981), pp. 655-662.
76. Whitehurst, D.D., Farcasiu, M., Mitchell, T.O., and Dickert, Jr., J.J., The Nature and Origin of Asphaltenes in Processed Coals, Third Report Under EPRI Project RP-410, (December 1979).
77. Curtis, C.W. and Hwang, J-S., "The Reactivity of Different Coal and Residuum Combinations in Coprocessing," Fuel Processing Technology, Vol. 30, (1992), pp. 47- 67.
78. Cugini, A.V., Lett, R.G., and Wender, I., "Coal/Oil Coprocessing Mechanism Studies," Energy and Fuels, Vol. 3, (1989), pp. 120-126.
79. Rahimi, P.M., Fouda, S.A., Kelly, J.F., Malhotra, R., and McMillen, D.F., "Characteristics of CANMET Coprocessing Distillates at Different Coal Concentrations," Fuel, Vol. 68, (1989), pp. 422-429.
80. Miller, T.J., Panvelker, S.V., Wender, I., and Tierney, J.W., " Thermal Non-Catalytic Coprocessing of Illinois No. 6 Coal With Maya Resid and Boscan Crude," Fuel Processing Technology, Vol. 23, (1989), pp. 23-38.
81. Proceedings of the Division of Petroleum Chemistry, Inc. 205th National Meeting, ACS, Denver, CO, March 28-April 2, 1993, "High Conversion Coprocessing by P.M. Rahimi, S.A. Fouda, J.F. Kelly, D. Liu, W.I. Beaton, and U. Lenz" (Preprints).
82. Steer, J.G., Ohuchi, T. and Muehlenbachs, K, " Efficacy of Coal-Bitumen Coprocessing as Determined by Isotropic Mass Balance Calculations," Fuel Processing Technology, Vol. 15, (1987), pp. 429-438.
83. Ettinger, M.D. and Stock, L.M., "Coprocessing Reactions of Illinois No.6 and Wyodak Coals with Lloydminster and Hondo Petroleum Resids in the Presence of Dideutrium under Severe Conditions," Energy & Fuels, Vol. 8, (1994), pp. 960-971.
84. Proceedings of the Am. Chem. Soc., Div. Fuel Chem., 1991 by Lancet, M.S., Winschel, R.A., and Burke, F.P., (Preprint), pp. 1266.
85. Pradhan, V.R., Hu, J., Tierney, J.W., and Wender, I., "Activity and Characterization of Anion-Modified Iron(III) Oxides as Catalysts for Direct Liquefaction of Low Pyrite Coals," Energy & Fuels, Vol. 7, (1993), pp. 446-

454.

86. Pradhan, V.R., Herrick, D.E., Tierney, J.W., and Wender, I., "Finely Dispersed Iron, Iron-Molybdenum, and Sulfated Iron Oxides as Catalyst for Coprocessing Reactions," Energy & Fuels, Vol 5, (1991), pp. 712-720.
87. Pradhan, V.R., Holder, G.D., Wender, I., and Tierney, J.W., "Kinetic Modeling of Direct Liquefaction of Wyodak Coal Catalyzed by Sulfated Iron Oxides," I&EC Res. Vol. 31, (1992), pp. 2051-2056.
88. Brown, J.K. and Ladner, W.R., Fuel, Vol. 39, (1960), pp. 87.
89. ASTM Designation: D 2887-89, Annual Book of ASTM Standards.
90. Whitcomb, J.H., "A Study of the Nature and Content of Hydroaromatic Hydrogen of Model Compounds, Coals, Heavy Oils, and Recycle Resids by Catalytic Dehydrogenation" (unpublished M.S. Thesis, Department of Chemical and Petroleum Engineering, School of Engineering, University of Pittsburgh, 1993).
91. Robbins, G.A., Winschel, R.A., and Burke, F.P., "Phenolic-OH as a Process-Performance Indicator in Two-Stage Liquefaction," Am. Chem. Soc. Div. Fuel Chem. Prepr., (1986), pp. 155-163.