Final Technical Report

Re: Contract # 9-X60-D1200-1 Task # 32

LA-SUB--95-127

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Prioritizing Information for the Discovery of Phenomena by

Paul Helman

Department of Computer Science
The University of New Mexico
Albuquerque, NM 87131-1386
helman@cs.unm.edu

Technical Report No. CS94-8

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Prioritizing Information for the Discovery of Phenomena

Paul Helman[†]

Department of Computer Science
University of New Mexico
Albuquerque, New Mexico 87131

Abstract

We consider the problem of prioritizing a collection of discrete pieces of information, or transactions. The goal is to rank the transactions in such a way that the user can best pursue a subset of the transactions in hopes of discovering those which were generated by an *interesting* source. The problem is shown to differ from traditional classification in several fundamental ways. Ranking algorithms are divided into two classes, depending on the amount of information they may utilize. We demonstrate that while ranking by the less constrained algorithm class is consistent with classification, such is not the case for the more constrained class of algorithms. We demonstrate also that while optimal ranking by the former class is "easy", optimal ranking by the latter class is NP-hard. We present heuristics for optimally solving restricted versions of the detection problem, including symmetric anomaly detection. Finally, we explore heuristics for more general detection applications and present preliminary results of an experimental implementation of these heuristics.

1. Introduction

The problem treated in this paper is described as follows. We are to analyze a massive quantity of information which is naturally partitioned into discrete pieces. We have *a priori* only a nebulous description of *interesting information*, in particular, generic characterizations of how interesting information might differ from *mundane information*. By expending large sums of money and/or time we can pursue a seemingly interesting information piece and determine if it is truly interesting; we benefit greatly if indeed the information pursued was truly interesting. Since we can afford to pursue only a tiny fraction of the information with which we are presented, our goal is to prioritize (i.e., rank) the information pieces, allowing us to pursue the most appropriate collection of α pieces, for any α .

The information prioritization problem has a wide range of applications, including:

1. *Computer security*: The information is a computer system's audit trail and our task is to prioritize the recorded activities according to the likelihood that they are indicative of malicious intent (e.g., an intruder or a virus).
2. *Astronomy*: The information is radio signals collected from deep space and our task is to prioritize bursts of signals according to the likelihood that they are the product of an intelligent life form.
3. *Biomedical testing*: The information is batteries of medical test results and our task is to prioritize the subjects according to the likelihood that their results are indicative of the early stages of serious disease.

Our problem differs in several fundamental ways from traditional classification [1,2,3,5,7,8,10,11,12,13]. Firstly, we cannot obtain an optimal ranking from an optimal classification, since if two information pieces optimally are placed in the same category, we have no guidance regarding their optimal relative prioritization. A surprising result is that, in the context of the problem version of most interest to us, classification and prioritization are *not necessarily consistent*. In particular, it may be optimal to rank x as less likely to be interesting than y , yet optimal also to classify y as mundane and x as interesting. Hence, it need not be the case that an optimal ranking can be turned into an optimal classification with appropriate choice of cutoff point.

[†]This work is supported in part by grants from Los Alamos National Laboratory and the NSA.

Another key difference from the more traditional problem is that we are willing to consider contexts in which our training data is exclusively from the mundane process. Our approach assumes neither that an exact characterization nor a sample of the interesting process is available, and relies on various statistical abstractions of what is likely to distinguish mundane and interesting.

Two classes of phenomena detectors are considered. A Class 1 detector must assign a priority value to each information piece as it is encountered. A Class 2 detector waits until it has seen all the information and then ranks the entire collection of information pieces. Class 2 contains Class 1 as a special case, but many applications require a Class 1 detector. The motivations for a Class 1, rather than Class 2, detector include:

1. We need to provide a real-time evaluation of each information piece x as x enters the system and act upon this evaluation immediately. For example, if x and y are the first information pieces encountered and x is evaluated as being more likely to be interesting than y , we may begin exploring x while awaiting the arrival and evaluation of additional information pieces. We continue to explore x until a higher ranked information piece z arrives; we may resume exploration of x after all higher ranked information pieces have been explored fully. In this way, even if x later falls out of the top α ranked information pieces, the dovetailing exploration strategy will not delay the time to completion of the exploration of the top ranked α pieces, since no time is expended on an information piece so long as an already encountered, higher ranked information piece is not explored completely.
2. When the amount of information is massive (e.g., as in radio astronomy), we may be able to store only a small fraction of the information we collect. If we know in advance that we will be able to investigate at most α information pieces, a Class 1 detector requires only that we maintain a priority queue of the top α information pieces, allowing us to discard any information piece that does not rank among the current top α .
3. Practically speaking, a Class 1 detector operates faster on-line (i.e., once constructed and put into operation), since its evaluation of x depends on only x . On-line efficiency often is critical for real-time applications.

Our results demonstrate many theoretical difference between the two detector classes, including: (A) Optimal Class 2 prioritization is completely consistent with optimal Class 2 classification (that is, when the classifier may inspect all the information before classifying any of the information pieces), while optimal Class 1 prioritization is not always consistent with optimal Class 1 classification (that is, when the classifier must classify each information piece as it is encountered); and (B) Optimal Class 2 prioritization is solvable in polynomial time (assuming the risk expression is a finite sum or a polynomial time evaluable integral), while Class 1 is not, unless $P=NP$.

The final sections of the paper consider heuristics for Class 1 detection. The results include simple detectors which are optimal for restricted problem instances, the development of heuristic evaluation functions for attribute selection and process representation, and the definition of a k -ordered detector, a simple method of resolving competing evidence. We also describe briefly a software system implementing our detection methodology and present limited test results as a preliminary proof of concept.

2. Mathematical Formulation

In [9] we present a mathematical formulation of the detection problem in the context of computer security, in particular, misuse detection. Reference [9] defines a penalty function, gives optimal performance bounds, specifies the form of an optimal detector under perfect information (processes known exactly), and considers methods for heuristic detection, including data reduction (attribute selection and value aggregation). The formulation developed in the current paper extends the results to the more interesting and complex problem in which processes are not known, but described by prior distributions. The results of the current work subsume [9] in that the earlier work is an instance of the current when exactly one process pair has nonzero density, *a priori*. The theory developed here also gives new mathematical justification to a general type of heuristic, which

includes heuristics described in [2,4,9,10]. To our knowledge, this is the first risk-minimization based justification of attribute selection.

2.1 Basic Assumptions and Notation

The information to be analyzed is represented as a collection of transactions. A transaction template defines the structure of the transactions, that is, specifies the set of attributes to which each transaction assigns a value. For example, in a computer security application, a transaction template might include the attributes *user_id*, *command*, *port*, *time*, and *elapsed_cpu*. A computer's audit trail then collects instances of this transaction template, such as

user_id=Fred, *command*=edit file, *port*=xterm20, *time*=1994.06.07.08.01.0002, *elapsed_cpu*=2.2.

We assume the collection of transactions is homogeneous, each being an instance of a single, fixed and predetermined, transaction template. We assume also that the domain of each attribute (i.e., the set of values an attribute can assume) is finite, and hence the transaction space (i.e., the set of possible transaction instances)

$$S = \{x_1, x_2, \dots, x_i, \dots, x_{|S|}\}$$

is finite.

We model the transactions as generated by two, independent, stationary stochastic processes, the normal (mundane) process N and the phenomena (interesting) process M , each with its image in S . This simple, binary partitioning simplifies the presentation, but our results easily generalize to applications for which we wish to refine the partition.

A problem instance consists of a finite training sample DB and a finite rank stream RS , the actual transactions which must be ranked. Each of these transaction sequences is written as $\langle y_1, \dots, y_j, \dots, y_m \rangle$, where $y_j \in S$ is the j^{th} transaction in the sequence, and the y_j are not necessarily distinct. RS is assumed to be generated by a mix of N and M , with the proportion determined by $\lambda = Pr\{N\}$, the *a priori* probability of process N . The stochastic process T that selects between N and M for the generation of each transaction in RS is itself stationary and independent of each of N and M .

In the applications under study, DB is assumed generated by N only (though there are important applications in which the training data is of the same mix as RS). Hence, we lack any "tagged" occurrences from process M . That we lack tagged representatives of the process M is one of the characteristics that distinguishes our problem from the traditional classification problem; this work considers methods for coping with this severe problem constraint.

The formulation developed below is simplified by the assumption that each of DB and RS is of a fixed size, denoted $|DB|=n$ and $|RS|=k$ (where multiple occurrences of a transaction are counted multiple times toward the count). This assumption can be relaxed, replacing the fixed sizes by distributions over the possible sizes of DB and RS ; all results apply in this case, provided that the resulting quantities are convergent.

The processes N and M are characterized by their probability distributions on S , that is, by the vectors $\theta_N = \langle \theta_N(x_1), \dots, \theta_N(x_i), \dots, \theta_N(x_{|S|}) \rangle$ and $\theta_M = \langle \theta_M(x_1), \dots, \theta_M(x_i), \dots, \theta_M(x_{|S|}) \rangle$, such that the coordinates of each of θ_N and θ_M are nonnegative, real valued, and sum to 1. The entries $\theta_N(x_i)$ and $\theta_M(x_i)$ represent the probabilities $Pr\{x_i | \theta_N\}$ and $Pr\{x_i | \theta_M\}$, respectively.

Let Θ_N and Θ_M denote the spaces of all normal and phenomena distributions, and let $\Theta = \Theta_N \times \Theta_M$ denote the set of all distribution pairs. For any $\theta = \langle \theta_N, \theta_M \rangle \in \Theta$ and any $x_i \in S$:

$\theta_r(x_i)$ denotes the ratio $\theta_M(x_i)/\theta_N(x_i)$

$\theta_h(x_i)$ denotes the linear combination $\lambda * \theta_N(x_i) + (1-\lambda) * \theta_M(x_i)$.

Note that $\theta_h(x_i)$ is the probability that, under θ , transaction x_i is generated as the j^{th} transaction, for any j , that is, $\theta_h(x_i) = Pr\{x_i | \theta\}$.

2.2 Two Classes of Phenomena Detectors

We consider two classes of phenomena detectors and demonstrate that the classes have rather different theoretical properties.

A phenomena detector pd from either class trains on DB . A Class 1 detector, after training on DB , is instantiated to a map $pd:S \rightarrow \mathbb{R}$. Hence, as the j^{th} transaction x of an RS is generated, a pd of Class 1 provides an immediate evaluation $pd(x)$ that is independent of the RS that contains x . In contrast, a Class 2 detector does not provide an evaluation of x until it has examined both the training data DB and the entire rank stream RS that contains x . We shall demonstrate that Class 2 detectors are in a sense both potentially of greater power and "easier" to construct. Unfortunately, as was discussed in Section 1, the requirements of many applications mandate the use of a Class 1 detector.

More formally, we have the following definitions. Let G denote the set $G=\{g \mid g \text{ is a (prior) density or probability function over } \Theta\}$.

A Class 1 detector is a function

$$pd:G \times \{\text{samples } DB \ni |DB|=n\} \times S \rightarrow \mathbb{R}.$$

Hence, such a pd 's evaluation of each $x \in S$ does not depend on the RS which is encountered. Effectively, pd defines a single permutation $pd_{g,DB}(S)=\Pi(S)$ of S and pd 's ranking of any RS is the restriction of $\Pi(S)$ to the distinct transactions appearing in RS . Practically, such a pd is instantiated to a map from $S \rightarrow \mathbb{R}$ once DB is presented during the (off-line) training phase.

A Class 2 detector is a function

$$pd:G \times \{\text{samples } DB \ni |DB|=n\} \times \{\text{rank streams } RS \ni |RS|=k\} \times S \rightarrow \mathbb{R}.$$

Hence, such a pd 's evaluation of $x \in S$ may depend on the RS which is encountered. Effectively, pd defines a permutation $pd_{g,DB}(RS)=\Pi(RS)$ for each RS encountered[†] and these permutations may be independent, i.e., $\Pi(RS)$ and $\Pi(RS')$ need not be consistent. Practically, such a pd is not fully instantiated to a map from $S \rightarrow \mathbb{R}$ during the (off-line) training phase; analysis of RS must be performed in the course of on-line operation.

Observe that the second class of detectors properly contains the first -- a Class 1 detector is a Class 2 detector that is constant in the argument RS .

Our prior distribution g on Θ typically will be fixed, in which case we write $pd(DB,x)$ (or $pd(DB,RS,x)$ for a Class 2 detector). This notation emphasizes the perspective that specialized algorithms are used to construct pd depending on the characteristics of g appropriate for a particular application.

2.3 Bayesian Risk Formulation

Loss Function

The following notational conventions are used.

1. pd is shown to include RS as an argument; if pd is from Class 1, it is understood that pd is constant in this argument.
2. The prior distribution on Θ is understood to be g .

[†] pd 's prioritization of transactions in S but not RS is inconsequential and hence $pd(g,DB,RS,x)$ may be defined arbitrarily for any $x \in S$ not appearing in RS .

3. The summation $\sum_{\{x,y\} \subset RS}$, where RS is a rank stream (i.e., a sequence of not necessarily distinct transactions), is taken over all unordered pairs of distinct transactions from the sequence RS , such that if x appears multiple times in RS , it will appear in multiple terms of the summation paired with the same y . In particular, if x appears $c(x)$ times and y appears $c(y)$ times, the pair $\{x,y\}$ appears $c(x)*c(y)$ times in the summation.

Loss is based on prioritization error as defined in [9]. For any phenomena detector pd , training set DB , and rank stream RS , $L(pd, DB, RS; \theta)$ is the prioritization error incurred by pd over all transactions pairs from RS (see (3) above) when the sample is DB and $\theta \in \Theta$ is the true distribution vector characterizing the processes N and M .

Formally, we define loss as follows. For any pair $\{x,y\}$ of transactions, define
 $l(<x,y>;\theta) = Pr\{M|x;\theta\} * Pr\{N|y;\theta\}$
 $l(<x=y>;\theta) = 1/2(Pr\{M|x;\theta\} * Pr\{N|y;\theta\} + Pr\{M|y;\theta\} * Pr\{N|x;\theta\})$.

The loss $L_{x,y}$ incurred by pd on transaction pair $\{x,y\} \subset RS$ when the observation is DB , rank stream is RS , and the processes are characterized by θ is:

$$L_{x,y}(pd, DB, RS; \theta) = \begin{cases} l(<x,y>;\theta) & \text{if } pd(DB, RS, x) < pd(DB, RS, y) \\ l(<x=y>;\theta) & \text{if } pd(DB, RS, x) = pd(DB, RS, y) \\ l(<y,x>;\theta) & \text{if } pd(DB, RS, x) > pd(DB, RS, y) \end{cases}$$

Loss function L is defined as:

$$L(pd, DB, RS; \theta) = [1/(|RS| * (|RS| - 1))] * \sum_{\{x,y\} \subset RS} L_{x,y}(pd, DB, RS; \theta)$$

Discussion:

1. $L_{x,y}(pd, DB, RS; \theta)$ specifies that the loss incurred by a pd such that $pd(DB, RS, x) < pd(DB, RS, y)$ is the probability that, when θ characterizes the operative processes, x is generated by the phenomena process while y is generated by the normal process. This is an appropriate penalty, since it is exactly the probability that, when θ is operative, pd 's ordering of x and y is a misdirection. (When $pd(x) = pd(y)$, the penalty is the average of the two directional penalties, reflecting the fact that in this case pd provides no guidance and x and y must be ranked by arbitrary means [e.g., a coin flip].) Note also that loss does not include terms $L_{x,x}$, since no detector prioritizes a pair of identical transaction instances.
2. A loss function appropriate for classification is $pen_I * Pr\{M|x;\theta\}$ when x is classified as normal and $pen_{II} * Pr\{N|x;\theta\}$ when x is classified as phenomena. (Here, pen_I and pen_{II} are chosen to model the relative importance of Type I and Type II errors.) While classification error is not applicable to our ranking problem, we shall demonstrate that the ranking induced by an optimal Class 2 detector is trivially converted, for any pen_I and pen_{II} , into an optimal classifier, where the classification of x may be based on g, DB , and RS . In contrast, we demonstrate that the ranking induced by an optimal Class 1 detector is not consistent with optimal classification, where the classification of x may be based on g and DB , but not RS .
3. Loss $L()$ is normalized by $|RS| * (|RS| - 1)$, which represents the maximum number of terms contributed by a rank stream of size $|RS|$, thus allowing meaningful comparisons of loss incurred on RS of different sizes.

From the definition of Bayes risk we have

$$rsk(pd) = \int_{\Theta} R_{pd}(\theta) g(\theta) d\theta, \text{ where}$$

$$R_{pd}(\theta) = \sum_{DB, RS} L(pd, DB, RS; \theta) * Pr\{DB, RS | \theta\}$$

$$= \sum_{DB} \sum_{RS} [1/(|RS| * (|RS| - 1))] * (\sum_{\{x,y\} \subset RS} L_{x,y}(pd, DB, RS; \theta)) * Pr\{RS|\theta\} * Pr\{DB|\theta_N\}$$

$$= \sum_{DB} [1/k * (k-1)] * (\sum_{RS} (\sum_{\{x,y\} \subset RS} L_{x,y}(pd, DB, RS; \theta)) * Pr\{RS|\theta\} * Pr\{DB|\theta_N\}).$$

(Recall that k is the size of the rank stream to be analyzed.)

Technical Note: $R_{pd}(\theta)$ is bounded and continuous; hence, we are justified in the use of the Riemann integral whenever the prior distribution on Θ has integrable density $g(\theta)$. However, in many applications (and many of our examples) $g(\theta)$ will be a discrete probability function, in which case the integral is interpreted as a sum. In fact, important families of prior distributions (e.g., those considered in Sections 5 and 6) can be enlarged to include more general probability measures over Θ , in which case the Riemann integral is replaced by the Lebesgue integral.

The expression for Bayes risk involves the distributions $Pr\{DB|\theta_N\}$, the probability that θ_N generates sample DB , and $Pr\{RS|\theta\}$, the probability that $\theta = \langle \theta_N, \theta_M \rangle$ generates rank stream RS .

Theorem 2.1:

- (a) Let DB be a sample (i.e., a sequence of transactions), with $Count(DB)$ the vector $\langle c_1, \dots, c_i, \dots, c_s \rangle$ giving the frequency count in DB of each $x_i \in S$, including those with 0 count. Then the probability $Pr\{DB|\theta_N\}$ that process N characterized by θ_N generates this DB is given by $Pr\{DB|\theta_N\} = (\prod_{i=1}^s (\theta_N(x_i)^{c_i}))$.
- (b) Let RS be a rank stream (i.e., a sequence of transactions), with $Count(RS)$ the vector $\langle c_1, \dots, c_i, \dots, c_s \rangle$ giving the frequency count in RS of each $x_i \in S$, including those with 0 count. Then the probability $Pr\{RS|\theta\}$ that processes N and M characterized by θ generates this RS is given by $Pr\{RS|\theta\} = (\prod_{i=1}^s (\theta_h(x_i)^{c_i}))$.

Proof: The transactions in each of DB and RS are generated by a sequence of i.i.d. random variables whose distributions are given by θ_N and θ_h , respectively. $\square$

2.4 Optimal Class 2 Detection

Since the sums are over a finite number of terms, we can write

$$rsk(pd) = [1/k * (k-1)] * \sum_{DB \in \Theta} (\sum_{RS} (\sum_{\{x,y\} \subset RS} L_{x,y}(pd, DB, RS; \theta)) * Pr\{RS|\theta\}) * Pr\{DB|\theta_N\} g(\theta) d\theta.$$

Observe that pd minimizes risk if and only if $pd(DB, \cdot; \cdot)$ is the minimizer for each $\overline{DB}$ of

$$rsk(pd, \overline{DB}) = [1/k * (k-1)] * \sum_{\theta \in \Theta} (\sum_{RS} (\sum_{\{x,y\} \subset RS} L_{x,y}(pd, \overline{DB}, RS; \theta)) * Pr\{RS|\theta\}) * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta.$$

Similarly, any optimal Class 2 detector must be optimal for each $(\overline{DB}, \overline{RS})$ pair encountered. That is, an optimal pd of Class 2 must rank $\overline{RS}$ so as to minimize

$$rsk(pd, \overline{DB}, \overline{RS}) = \sum_{\theta \in \Theta} (\sum_{\{x,y\} \subset \overline{RS}} L_{x,y}(pd, \overline{DB}, \overline{RS}; \theta)) * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta.$$

We therefore have the following necessary and sufficient condition for the optimality of a Class 2 detector.

Definition 2.1: Function $f_2: T \rightarrow \mathbb{R}$ orders set T consistently with function $f_1: T \rightarrow \mathbb{R}$ if, for all $x, y \in T$,
 $f_1(x) < f_1(y) \Rightarrow f_2(x) < f_2(y)$.

Observe that if f_2 orders consistently with f_1 then: (a) When $f_1(x) = f_1(y)$, $f_2(x)$ and $f_2(y)$ may stand in any relation, and (b) We may have $f_2(x) = f_2(y)$ only when $f_1(x) = f_1(y)$.

Theorem 2.2: pd is an optimal Class 2 detector if and only if, for each $(\overline{DB}, \overline{RS})$, pd orders $\overline{RS}$ consistently with $pd^*(\overline{DB}, \overline{RS}, x) = \int_{\Theta} Pr\{M|x;\theta\} * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta$.

Proof: Inspection of $rsk(pd, \overline{DB}, \overline{RS})$ reveals that the contribution of the pair $\{x, y\}$ to pd 's risk is minimized when $pd(\overline{DB}, \overline{RS}, x) < pd(\overline{DB}, \overline{RS}, y)$ if and only if

$$\int_{\Theta} Pr\{M|x;\theta\} * (1 - Pr\{M|y;\theta\}) * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta \leq \int_{\Theta} Pr\{M|y;\theta\} * (1 - Pr\{M|x;\theta\}) * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta$$

or, equivalently, if and only if

$$\int_{\Theta} Pr\{M|x;\theta\} * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta \leq \int_{\Theta} Pr\{M|y;\theta\} * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta.$$

Similarly, the contribution of the pair $\{x, y\}$ to pd 's risk is minimized when $pd(\overline{DB}, \overline{RS}, x) = pd(\overline{DB}, \overline{RS}, y)$ if and only if $\int_{\Theta} Pr\{M|x;\theta\} * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta = \int_{\Theta} Pr\{M|y;\theta\} * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta$. $\square$

Observation 2.1: Given a fixed pair $(\overline{DB}, \overline{RS})$, the probability that transaction x is generated by the phenomena process is $Pr\{M|x\} = \int_{\Theta} Pr\{M|x;\theta\} * f(\theta|\overline{RS} \wedge \overline{DB}) d\theta$, where $f(\theta|\overline{RS} \wedge \overline{DB})$ is the posterior distribution on Θ , given training sample $\overline{DB}$ and rank stream $\overline{RS}$.

Corollary 2.2: For each $(\overline{DB}, \overline{RS})$, $pd^*(x)$ is equal to $Pr\{\overline{DB} \wedge \overline{RS}\} * Pr\{M|x\}$, and hence ranking by the probability $Pr\{M|x\}$ each $x \in S$ was generated by M (given $\overline{DB}$ and $\overline{RS}$) is optimal.

Proof: $pd^*(x) = \int_{\Theta} Pr\{M|x;\theta\} * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta$

$$= \int_{\Theta} Pr\{M|x;\theta\} * Pr\{\overline{RS} \wedge \overline{DB}|\theta\} d\theta = \int_{\Theta} Pr\{M|x;\theta\} * f(\theta|\overline{RS} \wedge \overline{DB}) * Pr\{\overline{DB} \wedge \overline{RS}\} d\theta = Pr\{\overline{DB} \wedge \overline{RS}\} * Pr\{M|x\} \quad \square$$

Discussion:

1. The ranking problem and the classification problem (classify each x into either N or M) are consistent when all of RS may be inspected before ranking or classifying any of its transactions. That is, the penalty for Type I or Type II error simply determines where in the optimal ranking to place the threshold on $Pr\{M|x\}$ for classifying x and, consequently, $[x \text{ optimally classified as } N \text{ and } y \text{ optimally classified as } M] \Rightarrow [pd^*(x) \leq pd^*(y)]$.
2. The optimal ranking produced by pd^* depends on $\lambda = Pr\{N\}$. (It is easy to see that $Pr\{\overline{RS}|\theta\}$ depends on λ and this quantity can be made to dominate.)
3. While the optimal Class 2 detector is specified by a simple expression, its evaluation for a given prior distribution g on Θ may be infeasible. However, if g is nonzero on only finitely many $\theta \in \Theta$ (or if the integral is evaluable in polynomial time), the optimization problem is in P . While this latter result does not ensure feasibility for real problem instances (where the problem size can be enormous), the result is of theoretical interest, especially in contrast to the results for Class 1 detectors (see point 4).
4. The results for Class 1 detectors will be shown to be quite different from those for Class 2 detectors. It will be shown that when evaluation (for ranking or classification) must be performed on each x , independent of the overall RS , optimal ranking is not consistent with optimal classification and that the optimal ranking is independent of λ . We establish further that, even when the prior distribution g is nonzero on only finitely many $\theta \in \Theta$, no polynomial time evaluable Class 1 detector exists, unless $P=NP$. Section 4 pursues such computational issues.

2.5 Class 1 vs. Class 2 Detectors

The distinction between the two classes of detectors is significant; for certain prior distributions on Θ , all optimal detectors lie in (Class 2 - Class 1). The following example demonstrates that the optimal detector indeed can depend on RS . In particular, the example demonstrates that, for a fixed DB , the optimal detector's ordering of rank stream $RS_1 = \langle x_1, x_2, x_3 \rangle$ is not consistent with its ordering of rank stream $RS_2 = \langle x_1, x_1, x_2 \rangle$. This demonstrates that the overall optimal detector comes from (Class 2 - Class 1), since the overall optimal detector must be optimal on each rank stream, while any detector from Class 1 induces a single ranking of S , with which

the ranking of any rank stream is consistent.

Example 2.1: Suppose $S = (x_1, x_2, x_3)$ and that the distribution g on Θ is nonzero on only the following θ_1 and θ_2 .

	θ_1	
	θ_{N_1}	θ_{M_1}
x_1	0.9	0.1
x_2	$0.1 - \epsilon$	$0.9 - \epsilon$
x_3	ϵ	ϵ

	θ_2	
	θ_{N_2}	θ_{M_2}
x_1	0.3332	0.3333...
x_2	0.3335	0.3333...
x_3	0.3333	0.3333...

Suppose $\lambda = 0.5$.

The optimal detector from either class must be optimal for each individual DB . Consider $\overline{DB}$ and g such that $Pr\{\overline{DB}|\theta_1\} * g(\theta_1) = Pr\{\overline{DB}|\theta_2\} * g(\theta_2)$; hence, we can suppress this product in our analysis. Consider first $RS_1 = \langle x_1, x_2, x_3 \rangle$. The optimal Class 2 pd^* must be such that $pd^*(\overline{DB}, RS_1, x_2) < pd^*(\overline{DB}, RS_1, x_3) < pd^*(\overline{DB}, RS_1, x_1)$, since any optimal pd must minimize

$$\sum_{\theta_1, \theta_2} \left(\sum_{(x,y) \in RS_1} L_{x,y}(pd, \overline{DB}, RS_1; \theta) \right) * Pr\{RS_1|\theta\}$$

and, for sufficiently small $\epsilon \geq 0$, $Pr\{RS_1|\theta_1\}$ is so small that the optimal ordering is determined exclusively from the θ_2 term.

Consider now $RS_2 = \langle x_1, x_2, x_3 \rangle$. The optimal pd^* must be such that $pd^*(\overline{DB}, RS_2, x_1) < pd^*(\overline{DB}, RS_2, x_2)$, since any optimal pd must minimize also

$$\sum_{\theta_1, \theta_2} \left(\sum_{(x,y) \in RS_2} L_{x,y}(pd, \overline{DB}, RS_2; \theta) \right) * Pr\{RS_2|\theta\}.$$

and the difference in loss incurred on the θ_1 term by the orderings $x_1 < x_2$ versus $x_2 < x_1$, which is great, dominates this difference on the θ_2 term, which it is minuscule. (Observe also that $Pr\{RS_2|\theta_1\} > Pr\{RS_2|\theta_2\}$.)

The optimal member of Class 1 must select a single ordering of S , not depending on RS , and hence the overall optimal is in (Class 2 - Class 1). The results of the sections which follow (specifically, see Example 3.1) allow us to demonstrate that, in fact, the optimal ordering of S by a Class 1 detector is $x_1 < x_2 < x_3$. It is interesting to note that this ordering differs from the way the optimal Class 2 detector must order the rank stream $RS_1 = \langle x_1, x_2, x_3 \rangle$. Intuitively, a Class 2 detector, when presented with an RS may adjust its posterior on Θ ; a Class 1 detector may not depend on RS and produces a single ordering of S which minimizes an "expectation" over the distribution of possible RS . $\square$

Hence, we have the following.

Theorem 2.3: There exist prior distributions g on Θ such that all optimal detectors lie in (Class 2 - Class 1).

Proof: Example 2.1 provides one such distribution g .

3. Theoretical Study of Class 1 Detectors

Theorem 2.2 established that a detector is optimal within Class 2 if and only if it orders consistently with $pd^*(x) = \int_{\Theta} Pr\{M|x;\theta\} * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta$. For many applications, however, a Class 1 detector is required. In Section 4 we demonstrate that specifying an optimal Class 1 detector is far more difficult than is specifying an optimal Class 2 detector; in particular, we demonstrate that, even when the distribution g is nonzero on only finitely many $\theta \in \Theta$ (or results in an easily evaluable risk integral), the problem of determining an optimal Class 1 ranking is NP-hard.

We begin now to consider the problem of finding the best (or good) detector within Class 1.

3.1 Risk for Class 1 Detectors

Let pd be any Class 1 detector. Then the expression

$$rsk_1(pd) = \int_{\Theta} \left(\sum_{DB} \sum_{\{x,y\} \subset S} \theta_h(x) * \theta_h(y) * L_{x,y}(pd, DB; \theta) \right) * Pr\{DB|\theta_N\} * g(\theta) d\theta,$$

in which RS does not appear, is well defined. (It is not, however, well defined for a detector in (Class 2 - Class 1), since such a detector depends on the missing RS argument.) We now establish that rsk_1 and our original expression for risk

$$rsk(pd) = \int_{\Theta} \left(\sum_{DB} [1/k(k-1)] * \left(\sum_{RS} \sum_{\{x,y\} \subset RS} L_{x,y}(pd, DB; \theta) \right) * Pr\{RS|\theta\} * Pr\{DB|\theta_N\} \right) * g(\theta) d\theta$$

yield the same value for any detector in Class 1 (where we continue to suppress RS as an argument to pd since pd is in Class 1).

Theorem 3.1: Let pd be any member of Class 1. Then for each fixed $\theta \in \Theta$ and training sample DB , the inner term

$$[1/k(k-1)] * \left(\sum_{RS} \sum_{\{x,y\} \subset RS} L_{x,y}(pd, DB; \theta) \right) * Pr\{RS|\theta\}$$

of $rsk(pd)$ is equivalent to

$$\sum_{\{x,y\} \subset S} \theta_h(x) * \theta_h(y) * L_{x,y}(pd, DB; \theta).$$

Proof: For any pair z, w of transactions in S , consider the total weight, over all rank streams RS of size k , attached to the term $L_{z,w}$. Consider first the weight contributed by a fixed $\overline{RS}$ of size k . The number of times the term $L_{z,w}$ occurs in the sum

$$\sum_{\{x,y\} \subset \overline{RS}} L_{x,y}(pd, DB; \theta)$$

is $n(z) * n(w)$, where $n(z)$ and $n(w)$ are, respectively, the number of occurrences of z and w in $\overline{RS}$. Hence, the contribution to risk of terms $L_{z,w}$ for such an $\overline{RS}$ is $n(z) * n(w) * (L_{z,w}(pd, DB; \theta) * Pr\{\overline{RS}|\theta\})$.

Consider now the total weight attached to $L_{z,w}$ by all RS with the same counts $n(z)$ and $n(w)$. To compute this quantity, we require the total probability of this collection of rank streams, that is, $Pr\{RS \text{ with counts } n(z) \text{ and } n(w) | \theta\}$. Let V denote the set $S - \{z, w\}$ of remaining transactions. Then $n(V) = k - (n(z) + n(w))$ is the number of occurrences in RS of members of V and $\theta_h(V) = 1 - (\theta_h(z) + \theta_h(w))$ is the probability that any single transaction generated by θ is other than z or w . Hence,

$$Pr\{RS \text{ with counts } n(z) \text{ and } n(w) | \theta\} = \frac{k!}{n(z)! * n(w)! * n(V)!} * \theta_h(z)^{n(z)} * \theta_h(w)^{n(w)} * \theta_h(V)^{n(V)}.$$

The total weight, over all RS of size k , attached to the term $L_{z,w}$ hence is

$$\sum_{(n(z), n(w), n(V))} [(n(z) * n(w)) * \frac{k!}{n(z)! * n(w)! * n(V)!} * \theta_h(z)^{n(z)} * \theta_h(w)^{n(w)} * \theta_h(V)^{n(V)}], \text{ where the sum is take over}$$

all 3-tuples $(n(z), n(w), n(V))$ such that $n(z), n(w) \geq 1, n(V) \geq 0, n(z) + n(w) + n(V) = k$. (Note that $n(z), n(w) > 0$ since, otherwise, an RS with these counts does not contribute any z, w pairs.) This weight equivalently can be written as

$$k*(k-1)*\theta_h(x)*\theta_h(y)*\left(\sum_{(a,b,c)} \frac{(k-2)!}{a!*b!*c!} * \theta_h(x)^a * \theta_h(y)^b * \theta_h(z)^c\right), \text{ where the sum is take over all 3-tuples } (a,b,c) \text{ such that } a,b,c \geq 0, a+b+c=k-2. \text{ But this quantity is equal to } k*(k-1)*\theta_h(x)*\theta_h(y)*(\theta_h(x)+\theta_h(y)+\theta_h(z))^{(k-2)} = k*(k-1)*\theta_h(x)*\theta_h(y), \text{ since } (\theta_h(x)+\theta_h(y)+\theta_h(z))=1. \text{ Since this is the total weight, over all RS of size } k, \text{ attached to each term } L_{z,w} \text{ we have established that } [1/k(k-1)]*(\sum_{RS} \sum_{(x,y) \subset RS} L_{x,y}(pd, DB; \theta)) * Pr\{RS|\theta\} = \sum_{(x,y) \subset S} \theta_h(x)*\theta_h(y)*L_{x,y}(pd, DB; \theta). \quad \square$$

In the following, when studying Class 1 detectors, we shall work with the more convenient form rsk_1 of risk.

3.2 Properties of Class 1 Detectors

The risk expression $rsk_1(pd, \overline{DB})$ for any fixed $\overline{DB}$ and Class 1 detector is a sum of $\{x,y\}$ -terms, each of which is a function of only how pd orders x,y when trained on $\overline{DB}$. In particular, if pd orders as $pd(\overline{DB}, x) < pd(\overline{DB}, y)$, the $\{x,y\}$ -contribution to $rsk_1(pd, \overline{DB})$ is

$$\int_{\theta} Pr\{M|x;\theta\}*(1-Pr\{M|y;\theta\})*\theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta \\ = \int_{\theta} Pr\{M|x;\theta\}*\theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta - \int_{\theta} Pr\{M|x;\theta\}*Pr\{M|y;\theta\}*\theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta.$$

Similarly, if pd orders as $pd(\overline{DB}, x) > pd(\overline{DB}, y)$, the $\{x,y\}$ -contribution to $rsk_1(pd, \overline{DB})$ is

$$\int_{\theta} Pr\{M|y;\theta\}*\theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta - \int_{\theta} Pr\{M|x;\theta\}*Pr\{M|y;\theta\}*\theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta.$$

(In case $pd(\overline{DB}, x) = pd(\overline{DB}, y)$, the contribution is the average of these two quantities.)

Dropping the common second term of each ordering's contribution, the effect of the ordering choice $pd(\overline{DB}, x) < pd(\overline{DB}, y)$ is a contribution of

$$\int_{\theta} Pr\{M|x;\theta\}*\theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta$$

as opposed to a contribution of

$$\int_{\theta} Pr\{M|y;\theta\}*\theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta$$

for the ordering $pd(\overline{DB}, y) < pd(\overline{DB}, x)$. (In case $pd(\overline{DB}, x) = pd(\overline{DB}, y)$, the contribution is the average of these two quantities.)

Applying Bayes Theorem to the posteriors $Pr\{M|z;\theta\}$, we write the consequences of the orders as

$$\int_{\theta} \frac{\theta_M(x)(1-\lambda)}{\theta_M(x)(1-\lambda) + \theta_N(x)\lambda} * \theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta$$

versus

$$\int_{\theta} \frac{\theta_M(y)(1-\lambda)}{\theta_M(y)(1-\lambda) + \theta_N(y)\lambda} * \theta_h(x)*\theta_h(y)*Pr\{\overline{DB}|\theta\}*g(\theta)d\theta.$$

Using the identity $\theta_h(z) = \theta_N(z)\lambda + \theta_M(z)(1-\lambda)$ and suppressing common terms, we write the two consequences as $\lambda(1-\lambda)*[\int_{\theta} \theta_M(x)\theta_N(y)Pr\{\overline{DB}|\theta\}g(\theta)d\theta]$

versus

$$\lambda(1-\lambda) * \int_{\Theta} [\theta_M(y) \theta_N(x) Pr\{\overline{DB}|\theta\} g(\theta) d\theta].$$

When $\theta_N(x) \neq 0$ and $\theta_N(y) \neq 0$, we also can write the consequences of the orderings in terms of the ratios $\theta_r(z) = \theta_M(z)/\theta_N(z)$:

$$\lambda(1-\lambda) * \int_{\Theta} [\theta_r(x) * (\theta_N(x) \theta_N(y) Pr\{\overline{DB}|\theta\} g(\theta) d\theta)]$$

versus

$$\lambda(1-\lambda) * \int_{\Theta} [\theta_r(y) * (\theta_N(x) \theta_N(y) Pr\{\overline{DB}|\theta\} g(\theta) d\theta)].$$

Consequently, a Class 1 detector can be evaluated by summing, over all pairs x, y , pd 's ranking of x, y 's contribution to risk, cancelling the terms and factors common to all rankings. In particular, if pd ranks x, y as $pd(\overline{DB}, x) < pd(\overline{DB}, y)$ the contribution can be written as

$$\int_{\Theta} \theta_M(x) \theta_N(y) Pr\{\overline{DB}|\theta\} g(\theta) d\theta \quad (1)$$

or, equivalently, when $\theta_N(x) \neq 0$, as

$$\int_{\Theta} \theta_r(x) * (\theta_N(x) \theta_N(y) Pr\{\overline{DB}|\theta\} g(\theta) d\theta). \quad (2)$$

(If $pd(\overline{DB}, x) = pd(\overline{DB}, y)$, the average of $\theta_M(x) * \theta_N(y)$ and $\theta_M(y) * \theta_N(x)$ replaces $\theta_M(x) * \theta_N(y)$ in the integrand of (1), and the average of $\theta_r(x)$ and $\theta_r(y)$ replaces $\theta_r(x)$ in the integrand of (2)).

A detector is optimal within Class 1 if and only if its ranking minimizes these contributions, summed over all $\{x, y\} \subset S$ pairs. Notice that the optimal ranking by a Class 1 detector does not depend on λ , a fact that is in contrast to the optimal ranking by a Class 2 detector (see Theorem 2.2).

In [9] we demonstrate that pd defined by $pd_r(x) = \theta_r(x)$ minimizes a penalty expression that, when a single θ is such that $g(\theta) = 1$, is equivalent to rsk_1 . That rsk_1 is minimized by this pd_r when a single θ has mass 1 follows immediately from inspection of (the single nonzero term of) expression (1) or (2). It is apparent also that, when a single θ is such that $g(\theta) = 1$, pd_r is optimal not only within Class 1, but within Class 2, i.e., in this case, a pd that is permitted to depend on RS has no advantage, since in this case the posterior distribution on Θ obviously is the same as the prior distribution, namely $f(\theta|DB, RS) = g(\theta) = 1$.

When g is nonzero on more than one $\theta \in \Theta$, the minimization of risk within Class 1 can become significantly more difficult. Analysis of expressions (1) and (2) reveals important characteristics of the minimization. Observe, for example, that the optimal pairwise orderings -- that is, the collection of pairwise orderings that minimizes each $\{x, y\}$ pair's contribution to $rsk_1(pd, DB)$ -- need not induce a consistent order on S . For example, $x_1 < x_2$, $x_2 < x_3$, and $x_3 < x_1$ might each be the ordering minimizing the corresponding transaction pair's contribution to $rsk_1(pd, DB)$; hence, the optimal detector of Class 1 (which maps $pd: DB \times S \rightarrow \mathbb{R}$, and thus induces a single, consistent ordering on S) in such a case cannot be pairwise optimal.

Example 3.1: Consider again Example 2.1 of Section 2.5 used to demonstrate that the optimal member of Class 2 must rank $RS_1 = \langle x_1, x_2, x_3 \rangle$ and $RS_2 = \langle x_1, x_1, x_2 \rangle$ inconsistently. This same example demonstrates also that, when attention is restricted to Class 1, the pairwise orderings which minimize each $\{x, y\}$ pair's contribution to risk are inconsistent with each other. Specifically (assuming ϵ is sufficiently small), it is easy to demonstrate [e.g., in terms of (1) or (2)] that:

- $x_1 < x_2$ contributes less to risk than does $x_2 < x_1$, since θ_1 dominates this pair's ranking differential
- $x_2 < x_3$ contributes less to risk than does $x_3 < x_2$, since θ_2 dominates this pair's ranking differential
- $x_3 < x_1$ contributes less to risk than does $x_1 < x_3$, since θ_2 dominates this pair's ranking differential

The optimal Class 1 detector hence cannot be pairwise optimal.

Further, expression (1) or (2) easily can be used to show that the optimal Class 1 detector orders S as $x_1 < x_2 < x_3$. To see this, note that the optimal must order as $x_1 < x_2$, since the difference between the contribution

of $x_1 < x_2$ and $x_2 < x_1$ under θ_1 dominates all other contributions. In determining where in the optimal ordering x_3 must be placed, we observe that only θ_2 is significant, since any term involving x_3 and θ_1 includes a factor of ϵ , and hence goes to 0. It is then easy to verify that, with $x_1 < x_2$ fixed, the best placement of x_3 is following x_2 . Hence, we have established also the claim made at the conclusion of Example 2.1, that the optimal member of Class 1 must order S as $x_1 < x_2 < x_3$, while the optimal detector in Class 2 must order the rank stream $RS_1 = \langle x_1, x_2, x_3 \rangle$ as $x_2 < x_3 < x_1$. In particular, we have demonstrated the suboptimality of $pd(\overline{DB}, x) = \int_{\Theta} Pr\{M|x;\theta\} * Pr\{RS = \langle x_1, \dots, x_{|S|} \rangle | \theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta$ (where $S = \{x_1, \dots, x_{|S|}\}$) with respect to the minimization of risk for a Class 1 detector. $\square$

3.3 The Suboptimality of Posterior-Based Class 1 Detectors and the Divergence of Class 1 Ranking from Classification

Corollary 2.2 demonstrates that ranking by a Class 2 detector is optimal if and only if its ranking is consistent with $Pr\{M|x; DB, RS\} = \int_{\Theta} Pr\{M|x;\theta\} * f(\theta|\overline{RS}, \overline{DB}) d\theta$. It therefore is natural to consider the Class 1 detector

$$pd_{Post}(DB, x) = Pr\{M|x; DB\} = \int_{\Theta} Pr\{M|x;\theta\} f(\theta|x; DB) d\theta$$

that ranks based on the posterior of x being phenomena given DB (but not RS).

Example 2.1 can be used to demonstrate that pd_{Post} is not an optimal Class 1 detector. It can be verified easily that $Pr\{M|x_1; \overline{DB}\} < Pr\{M|x_3; \overline{DB}\} < Pr\{M|x_2; \overline{DB}\}$ (for the $\overline{DB}$, g , and λ specified in that example), while we have already established (Example 3.1) that the optimal order of S is $x_1 < x_2 < x_3$. Intuitively, the posterior on θ_2 is increased greatly by any rank stream that contains x_3 ; hence, θ_2 alone determines the optimal placement of x_3 relative the other two transactions, since this placement matters only for rank streams which do contain x_3 . In contrast, θ_1 dominates the relative ordering of the posteriors $Pr\{M|x_1; \overline{DB}\}$ and $Pr\{M|x_2; \overline{DB}\}$, while $Pr\{M|x_3; \overline{DB}\} = 0.5$ and hence falls between the other two posteriors.

Therefore, even if we were able to determine exactly $Pr\{M|x; DB\}$, we could not construct an optimal ranking for a Class 1 detector. As we shall demonstrate in the next section, optimal ranking by Class 1 detectors in fact is NP-hard. It is interesting to observe that, in contrast, $Pr\{M|x; DB\}$ does determine the optimal probabilistic classification for x into N or M , given DB . That is, the optimal Class 1 classifier classifies x as normal and y as interesting only if $Pr\{M|x; DB\} \leq Pr\{M|y; DB\}$ and, given any fixed penalties for Type I and Type II classification errors, y is classified as interesting if and only if $pen_{II} * (1 - Pr\{M|y; DB\}) \leq pen_I * Pr\{M|y; DB\}$. (This result parallels the comments following Corollary 2.2 for Class 2 classification.)

4. The Complexity of Constructing Optimal Detectors

4.1 Optimization Over Class 2

Theorem 2.2 establishes $pd^* = \int_{\Theta} Pr\{M|x;\theta\} * Pr\{\overline{RS}|\theta\} * Pr\{\overline{DB}|\theta_N\} g(\theta) d\theta$ as an optimal Class 2 detector. If there is a finite number of nonzero density θ (specified explicitly in a problem instance's input), or if the integral is evaluable in polynomial time, evaluating pd^* requires time bounded by a low order polynomial in the size of the problem instance's description, and hence the problem of optimal Class 2 detection is in P . Corollary 2.2 establishes that, under these same assumptions, optimal Class 2 classification is in P also, i.e., when the classifier may inspect all of RS before classifying any x . For comparison with the results derived in this section we restate these results as the following theorem.

Theorem 4.1: If g is nonzero on only finitely many $\theta \in \Theta$, or if the above integral is evaluable in polynomial time, the problem of obtaining an optimal ranking [classification] by Class 2 detectors [classifiers] is in P .

4.2 Optimization Over Class 1

In contrast to the polynomial time evaluable expression for an optimal Class 2 detector, we have for Class 1 not specified an optimal detector. We establish here that, even when a finite number of θ have nonzero density, an optimal Class 1 detector, evaluable in polynomial time, in fact cannot exist, unless $P=NP$.

Observe that the problems of finding an optimal Class 1 detector and of constructing an optimal ordering of S are of equivalent complexity: if an optimal detector exists which is evaluable in polynomial time it can be applied to each member of S to sort S ; if an optimal ordering of S can be obtained in polynomial time, an optimal pd can be defined by $pd(x)=position(x)$. Our first step is to establish the NP-completeness of the following abstract problem, which we call nontransitive sorting (NTS).

NTS is defined as:

INSTANCE: Collection $S=\{x_1, \dots, x_n\}$ of items, a list of values $F(x_i, x_j) \in \mathbb{Z}$ for each $1 \leq i \neq j \leq n$, and an integer bound K .

QUESTION: Is there a permutation $\Pi(S)$ such that $Cost(\Pi(S)) = \sum_{(x_i, x_j) \text{ such that } x_i < x_j \text{ in } \Pi(S)} F(x_i, x_j) \leq K$?

Theorem 4.2: NTS is NP-complete.

Proof: Clearly, NTS is in NP, as we can guess a permutation $\Pi(S)$ and in polynomial time compute its cost. We establish the NP-completeness of NTS by reducing Maximum 2-Satisfiability (Max 2-SAT) [6;LO5] to it.

Let the instance I of Max 2-SAT be:

$$\begin{aligned} U &= \{x_1, \dots, x_n\} \\ C &= \{c_1, \dots, c_m\} \\ K & \end{aligned}$$

Create as follows an instance I' of NTS:

S contains a total of $6m$ elements: Each clause $c_j = \{l_{ij}, l_{kj}\}$, where l_{ij} and l_{kj} denote complemented or uncomplemented occurrences of the distinct[†] variables x_i and x_k , generates four members of S , namely x_{ij}, x'_{ij}, x_{kj} , and x'_{kj} . Each c_j additionally generates the two enforcer elements u_j and z_j in S . Intuitively, ordering as $x_{ij} < x'_{ij}$ in I' will correspond to setting x_i true in I , while ordering as $x'_{ij} < x_{ij}$ in I' will correspond to setting x_i false.

$F(\cdot, \cdot)$ is defined as follows: Unless explicitly assigned a value below, $F(a, b) = 0$.

We first specify F so as to enforce the requirement that, for each i , the pairs x_{ij}, x'_{ij} are ordered the same way across the j , and hence that the induced assignment to x_i is consistent. To this end, we first force the permutation to be consistent with the clause ordering, that is, we ensure that, for each $i=1, 2, \dots, n$, $x_{ij} < x_{ik}$ and $x'_{ij} < x'_{ik}$ for every pair $j < k$ such that $x_{ij}, x_{ik} \in S$. To accomplish this, set

$$F(x_{ik}, x_{ij}) = B_1, \text{ for each } i \text{ and every pair } k > j \text{ such that } x_{ij}, x_{ik} \in S$$

$$F(x'_{ik}, x'_{ij}) = B_1, \text{ for each } i \text{ and every pair } k > j \text{ such that } x'_{ij}, x'_{ik} \in S,$$

where $B_1 = 7nm + 7m + n + 1$. The only way to avoid incurring a cost of B_1 is to order the variables by clause, as described above. As we shall see, B_1 is sufficiently large that if a single B_1 cost is incurred by an ordering, the total cost of this ordering is guaranteed to be positive, and hence greater than the bound we shall select for instance I' .

Next, we force, for any i , all the x_{ij} variables to come either before or after all the x'_{ij} variables. Let $f(i)$ and $l(i)$ respectively denote the subscripts of the first and last clause in which x_i or x'_i appears. Set

$$F(x_{if(i)}, x_{il(i)}) = B_2, \text{ for each } i$$

$$F(x'_{il(i)}, x'_{if(i)}) = B_2, \text{ for each } i,$$

[†]Any instance of Max 2-SAT containing a clause $\{x, x'\}$ trivially can be transformed to an equivalent instance without such a clause, since all truth assignments satisfy such a clause.

where $B_2 = 7m + 1$. There are exactly two ways to avoid a B_2 cost, assuming all B_1 costs are avoided:

If, for any i , all the x_{ij}' follow all the x_{ij} , the above function values are not activated and neither B_2 nor $-B_2$ costs are incurred.

If, for any i , all the x_{ij}' precede all the x_{ij} , each of the above 2 function values are activated and the costs cancel.

Notice that any interleaving necessarily will incur a B_2 cost (assuming B_1 is not incurred and hence the clause ordering holds) which won't be cancelled. As we shall see, if an ordering incurs even a single B_2 cost that is not cancelled by a $-B_2$ cost, the cost of the ordering will be positive. Observe also that even if all n $-B_2$ costs are obtained, this would not compensate for incurring even a single B_1 cost.

Now define F to check satisfiability. Let clause $c_j = \{l_a, l_b\}$, where literals l_a and l_b are complemented or uncomplemented occurrences of the distinct variables x_a and x_b of U . l_{aj} denotes $x_{aj} \in S$ if l_a is uncomplemented and $x_{aj}' \in S$ if l_a is complemented; similarly for l_{bj} . Also, if l_{aj} represents x_{aj} , $\neg l_{aj}$ represents x_{aj}' and if l_{aj} represents x_{aj}' , $\neg l_{aj}$ represents x_{aj} ; similarly for l_{bj} .

We use F to force, for each clause $c_j = \{l_a, l_b\}$:

$u_j < l_{aj}$, by setting $F(l_{aj}, u_j) = B_1$

$u_j < l_{bj}$, by setting $F(l_{bj}, u_j) = B_1$

$\neg l_{aj} < z_j$, by setting $F(z_j, \neg l_{aj}) = B_1$

$\neg l_{bj} < z_j$, by setting $F(z_j, \neg l_{bj}) = B_1$

Hence, we force both

$u_j < l_{aj}, l_{bj}$ and $\neg l_{aj}, \neg l_{bj} < z_j$,

without specifying how the "in clause" variables l_{aj} and l_{bj} are ordered, nor how the "out clause" variables $\neg l_{aj}$ and $\neg l_{bj}$ are ordered, nor how the two chains interact. Note, for example, that any order of the form $u_j < \pi < z_j$ (π denotes any ordering of the four complemented and uncomplemented variables) does not incur any of these B_1 costs. However, there also are orderings not incurring a B_1 cost in which u_j follows z_j .

Clause c_j specifies also:

$F(l_{aj}, \neg l_{bj}) = -2$

$F(l_{bj}, \neg l_{aj}) = -2$

$F(z_j, u_j) = -3$

Observe that if an ordering is credited with -3 for $z_j < u_j$, the ordering avoids a B_1 cost only if it is of the form:

$\neg l_{aj}, \neg l_{bj} < z_j < u_j < l_{aj}, l_{bj}$.

Hence, in this case, the ordering is not credited with either of the -2 terms, and as we shall argue, the corresponding assignment will not satisfy c_j .

The transformation is completed by setting the the target minimization value in instance I' of NTS to $-4K - 3(m - K)$.

We now demonstrate that if instance I of Max 2-SAT has an assignment A satisfying J clauses then the constructed instance I' of NTS has a permutation achieving cost $-4J - 3(m - J)$; hence, I is a YES instance implies I' is a YES instance.

Consider any clause $c_j = \{l_a, l_b\}$. We demonstrate that if assignment A satisfies c_j , we can order the corresponding elements of S so that we obtain a value of -4 on these pairs, and that if A does not satisfy c_j , we can order the corresponding elements of S so that we obtain a value of -3 on these pairs.

Case 1: A satisfies c_j .

1a: Both l_a and l_b are assigned true. Then we order as

$u_j < l_{aj} < l_{bj} < \neg l_{bj} < \neg l_{aj} < z_j$.

We obtain 2 pairs of -2 , hence achieving the -4 .

1b: l_a is assigned true and l_b assigned false. Then we order as

$$u_j < l_{aj} < \neg l_{bj} < l_{bj} < \neg l_{aj} < z_j$$

As in Case 1a, we obtain 2 pairs of -2.

1c: l_a is assigned false and l_b assigned true. Then we order as

$$u_j < l_{bj} < \neg l_{aj} < l_{aj} < \neg l_{bj} < z_j$$

Again we obtain 2 pairs of -2.

Case 2: A does not satisfy c_j . Then we order as

$$\neg l_{aj} < \neg l_{bj} < z_j < u_j < l_{aj} < l_{bj}$$

We obtain -3 on $F(z_j, u_j)$.

We now extend to a total order on S the orderings specified above, while incurring zero additional (cumulative) cost. Let $y_{1j} < y_{2j} < y_{3j} < y_{4j}$ denote the ordering of the "literals" $l_{aj}, l_{bj}, \neg l_{aj}, \neg l_{bj}$ specified by clause c_j . Then the orders already specified are consistent with the total order

$y_{11} < y_{21} < y_{12} < y_{22} < \dots < y_{1m} < y_{2m} < y_{31} < y_{41} < y_{32} < y_{42} < \dots < y_{3m} < y_{4m}$
of $U = \{u_j, z_j \mid j=1,2,\dots,m\}$. (The variables u_j and z_j are placed into the above chain in a manner depending on the case for clause c_j).

To see that the new pairwise orders specified by this total order incur zero additional cost, observe first that the order specifies $x_{ij} < x_{ik}$ and $x_{ij}' < x_{ik}'$ for all i and $j < k$ such that $x_{ij}, x_{ik}, x_{ij}', x_{ik}' \in S$. Hence, the B_1 costs of $F(x_{ik}, x_{ij})$ and $F(x_{ik}', x_{ij}')$ for $j < k$ are avoided.

Next, note that all the x_{ij} precede all the x_{ij}' if A assigns x_i true, while all the x_{ij} follow all the x_{ij}' if A assigns x_i false, i.e., there is no interleaving. To see this, observe that the orders prescribed by each c_j places the two literals assigned true before the two literals assigned false, i.e., in all cases, the pattern is $T < T' < F < F'$. Hence, any B_2 cost incurred by $F(x_{ij(i)}', x_{il(i)})$ is paired with a $-B_2$ cost obtained by $F(x_{il(i)}', x_{ij(i)})$.

Finally, the remaining pairwise orderings are of the form $\{l_{ij}, l_{jk}\}$, $i \neq j$ and $j \neq k$ (the variables may be primed or unprimed, in any combination), and u_j, z_j variables paired with variables from clauses other than j . Since $F(\cdot, \cdot) = 0$ for either ordering of all such pairs, the cost of the total ordering remains $-4J - 3(m - J)$.

To complete the proof, we must demonstrate that the constructed instance I' of NTS is a YES instance only when the original instance I of Max 2-SAT is a YES instance. Suppose we have an order $\Pi(S)$ of S such that $\text{Cost}(\Pi(S)) \leq -4K - 3(m - K)$. Since this cost is negative: (i) all B_1 costs are avoided, and hence (ii) B_2 and $-B_2$ costs are incurred in pairs. Consequently, for each i , all x_{ij} variables come either before or after all x_{ij}' variables and we may equate $\Pi(S)$ unambiguously with an assignment A_Π to the variables of U , that is, A_Π assigns x_i true if all the x_{ij} precede all the x_{ij}' , while A_Π assigns x_i false if all the x_{ij} follow all the x_{ij}' .

By (i) and (ii), the cost obtained by $\Pi(S)$ is obtained on the clause specific function values and, since the cost is negative, the B_1 costs are avoided here as well. Observe that no single clause can achieve a cumulative cost of less than -4. To see this, observe that if a clause obtains a -3 value for ordering $z_j < u_j$, it cannot additionally obtain a -2 value without incurring an B_1 cost. Hence, it must be the case that K or more clauses contribute a cost of -4 each. Now observe that if c_j contributes -4, it must be the case that assignment A_Π satisfies c_j . To see this, suppose that A_Π does not satisfy $c_j = \{l_{aj}, l_{bj}\}$ and hence A_Π assigns false to both of these literals. But then by the way A_Π is constructed from $\Pi(S)$, $\Pi(S)$ orders $\neg l_{aj} < l_{aj}$ and $\neg l_{bj} < l_{bj}$. Hence, all consistent orderings of $\neg l_{aj}, l_{aj}, \neg l_{bj}, l_{bj}$ must end in either l_{aj} or l_{bj} , meaning that the clause can contribute a -2 value for at most one of $F(l_{aj}, \neg l_{bj})$ and $F(l_{bj}, \neg l_{aj})$. Since we have already argued that c_j cannot obtain a -3 value for ordering $z_j < u_j$, and additionally obtain a -2 value without incurring an B_1 cost, c_j can contribute at best -3.

Therefore, we have established that K clauses must contribute a cost of -4 each, and that each of these clauses must be satisfied by A_Π . $\square$

Corollary 4.2: NTS is NP-complete even when $F(\cdot, \cdot)$ is restricted to the five values in $\{0, 1, 3, B_2 + 3, B_1 + 3\}$, where B_1 and B_2 are defined in the proof of the previous theorem.

Proof: Modify the transformation to use $F'(a, b) = F(a, b) + 3$ and a target minimization value of $3*W - 4K - 3(m - K)$, where $W = \binom{6m}{2}$, which is the number of terms appearing in the cost of any Π . $\square$

We next demonstrate that Optimal Risk 1 Ordering (OR1O) defined as follows is NP-complete.

INSTANCE: A set $S=\{x_1, \dots, x_s\}$ of transactions, a set $\Theta=\{\theta_1, \dots, \theta_z\}$ such that each θ_i assigns the rational pair $(\theta_{iN}(x_j), \theta_{iM}(x_j))$ of probabilities to each $x_j \in S$, a (rational) prior probability value $g(\theta_i)$ for each $\theta_i \in \Theta$, a sample $\overline{DB}=\langle count(x_1), \dots, count(x_s) \rangle$, and a rational bound K .

QUESTION: Is there a permutation Π of $\{x_1, \dots, x_s\}$ such that $risk(\Pi; \Theta, g, \overline{DB}) \leq K$, where

$$risk(\Pi; \Theta, g, \overline{DB}) = \sum_{(x_j, x_k) \triangleright x_j < x_k \text{ in } \Pi} \left(\sum_{i=1}^z \theta_{iM}(x_j) \theta_{iN}(x_k) Pr\{\overline{DB} | \theta_i\} g(\theta_i) \right).$$

Note that it follows from (1) of Section 3.2 that a Class 1 detector minimizes risk if and only if the ordering Π it induces minimizes $risk(\Pi; \cdot, \cdot)$ as defined in OR1O. (If pd minimizes risk and $pd(x) = pd(y)$ so too does pd' obtained by ordering x and y either way.)

Theorem 4.3: OR1O ordering is NP-complete.

Proof: Clearly, OR1O is in NP, as we can guess a permutation $\Pi(S)$ and in polynomial time compute its cost. We establish the NP-completeness of OR1O by reducing the restricted version of NTS to it.

Let the instance I of NTS be specified by $S=\{x_1, \dots, x_n\}$, $F(\cdot, \cdot)$, and bound K_{NTS} . We construct the following instance I' of OR1O.

The set of elements to be ordered is $S' = S \cup \{x_0\}$.

$\overline{DB}$ contains only 1 transaction, and this is a single occurrence of x_0 , that is, $count(x_0)=1$ and $count(x_i)=0$, $1 \leq i \leq n$.

$\Theta = \{\theta_{ij} \mid 1 \leq i \neq j \leq s\}$, where for each ordered pair (i, j) $i \neq j$, $\theta_{ij,N}(x_0) = \theta_{ij,N}(x_j) = 1/2$, $\theta_{ij,M}(x_i) = 1$, and $\theta_{ij} = 0$ elsewhere. Notice $Pr\{\overline{DB} | \theta_{ij}\} = 1/2$ for each $\theta_{ij} \in \Theta$.

Probability function g on Θ is defined as follows. Let $sum_F = \sum_{(x_i, x_j) \triangleright 1 \leq i \neq j \leq n} F(x_i, x_j)$ and define

$g(\theta_{ij}) = F(x_i, x_j) / sum_F$. Clearly the g values sum to 1.

Set the target minimization value $K_{OR1O} = (1/(4 * sum_F)) * K_{NTS}$.

Let Π' denote any ordering of S' . Then we have

$$\begin{aligned} & risk(\Pi'; \Theta, g, \overline{DB}) \\ &= \sum_{(x_i, x_j) \triangleright x_i < x_j \text{ in } \Pi' \text{ and } i, j > 0} \theta_{ij,M}(x_i) \theta_{ij,N}(x_j) Pr\{\overline{DB} | \theta_{ij}\} g(\theta_{ij}) \\ &+ \sum_{(x_k, x_0) \triangleright x_k < x_0 \text{ in } \Pi' \atop \substack{j=1 \\ k \neq j}}^s \left(\sum_{i=1}^s \theta_{ki,M}(x_k) \theta_{ki,N}(x_0) Pr\{\overline{DB} | \theta_{ki}\} g(\theta_{ki}) \right) \\ &= 1/4 * \sum_{(x_i, x_j) \triangleright x_i < x_j \text{ in } \Pi' \text{ and } i, j > 0} g(\theta_{ij}) + 1/4 * \sum_{(x_k, x_0) \triangleright x_k < x_0 \text{ in } \Pi' \atop \substack{j=1 \\ k \neq j}}^s \left(\sum_{i=1}^s g(\theta_{ki}) \right) \\ &= 1/(4 * sum_F) * \sum_{(x_i, x_j) \triangleright x_i < x_j \text{ in } \Pi' \text{ and } i, j > 0} F(x_i, x_j) + 1/(4 * sum_F) * \sum_{(x_k, x_0) \triangleright x_k < x_0 \text{ in } \Pi' \atop \substack{j=1 \\ k \neq j}}^s \left(\sum_{i=1}^s F(x_k, x_i) \right) \\ &= 1/(4 * sum_F) * Cost_{NTS}(\Pi(S)) + 1/(4 * sum_F) * \sum_{(x_k, x_0) \triangleright x_k < x_0 \text{ in } \Pi' \atop \substack{j=1 \\ k \neq j}}^s \left(\sum_{i=1}^s F(x_k, x_i) \right), \end{aligned}$$

where $\Pi(S)$ is formed from Π' by removing x_0 .

Observe that if x_0 appears in the first position of Π' , then the second term, which represents the contribution to risk of pairs involving x_0 , is zero; further, this second term is never negative. Hence, if I a YES instance of NTS with $Cost(\Pi) \leq K$, then Π' formed by placing x_0 at the beginning of Π has $risk(\Pi') \leq 1/(4 * sum_F) * K$ and I'

hence is a YES instance of OR1O. Similarly, if I' is a YES instance of OR1O with $rsk(\Pi') \leq 1/(4 * sum_F) * K$, then Π obtained by removing x_0 has $Cost(\Pi) \leq K$ and I hence is a YES instance of NTS. $\square$

The main results of this section are stated in the following theorem.

Theorem 4.4:

- (A) OR1O is NP-complete even if there are exactly $|S|^2 - |S|$ nonzero density $\theta \in \Theta$, each giving nonzero probability to no more than 3 transactions.
 - (B) The optimization version is NP-hard, that is, finding the ordering of S that minimizes risk is NP-hard.
 - (C) No optimal, polynomial time evaluable Class 1 detector $pd: G \times \{DB\} \times S \rightarrow \mathbb{R}$ can exist unless $P=NP$.
- Proof:** (A) follows directly from the construction of Theorem 4.3. (B) follows trivially from a Turing reduction of the decision problem to the optimization problem (the cost of a permutation can be obtained in polynomial time). (C) follows since the existence of such a detector allows the NP-hard ordering problem to be solved in polynomial time. $\square$

To complete the contrast with Class 2 methods (where ranking and classification are essentially equivalent), we state the following.

Theorem 4.5: If g is nonzero on only finitely many $\theta \in \Theta$, or if the integral for $Pr\{M|z;DB\}$ is evaluable in polynomial time, the problem of obtaining an optimal classification by Class 1 methods is in P .

Proof: As observed at the conclusion of Section 3, given penalties for Type I and Type II classification errors, the optimal classification of y is phenomena if and only if $pen_{II} * (1 - Pr\{M|y;DB\}) \leq pen_I * Pr\{M|y;DB\}$. The posterior can be computed in time polynomial in the size of the input under the conditions of the theorem. $\square$

5. Minimizing Risk Under Simple Assumptions

In the remainder of the paper we focus on Class 1 detection methods (though, where noted, some of the general results apply as well to Class 2 detection). The main results of the current section are theorems which specify efficient optimal detectors for prior densities g on Θ that generalize anomaly detection, under either of the following assumptions: (i) g is symmetric, reflecting the absence of any prior semantic knowledge of the attributes; or (ii) A particular, known set of attributes completely characterizes the processes. Section 6 then considers the problem of specifying good, though not necessarily optimal, detectors for a broader class of prior distributions, which includes applications outside the realm of anomaly detection.

5.1 A Sufficient Condition for Class 1 Optimality

In this section we derive a condition sufficient for establishing the optimality of Class 1 detectors. Sections 5.2 and 5.3 apply the result to establish the optimality of a Class 1 detector for each of the aforementioned families of prior distributions on Θ .

It is convenient to extend the definition of $\theta_r(x)$ so that it is defined even when $\theta_N(x)=0$.

Definition 5.1: For $\theta \in \Theta$ and $x \in S$, define $\theta_r(x) = \theta_M(x)/\theta_N(x)$ when $\theta_N(x) \neq 0$, $\theta_r(x) = 1$ when $\theta_N(x) = \theta_M(x) = 0$, and $\theta_r(x) = \infty$ when $\theta_N(x) = 0$, $\theta_M(x) \neq 0$. The ∞ symbol behaves as: $v < \infty$ for all $v \in \mathbb{R}$ and $\infty = \infty$.

Observation 5.1: Under this definition, $\theta_M(x) * \theta_N(y) < \theta_M(y) * \theta_N(x)$ if and only if $\theta_r(x) < \theta_r(y)$.

Definition 5.2: Let g be a fixed probability or density function[†] on Θ . For any fixed pair $\{x, y\}$ of transactions,

[†]As discussed in Section 2, our notation assumes g is a Riemann integrable density function or a discrete probability function; in the latter case, the integrals are to be interpreted as sums. The families of distributions considered here can be enlarged to include more general probability measures over Θ , in which

we partition as follows the subset of Θ on whose members g is nonzero:

$$\begin{aligned}\Theta_{x \prec y} &= \{\theta \in \Theta \mid g(\theta) \neq 0 \text{ and } \theta_r(x) < \theta_r(y)\} \\ \Theta_{x \succ y} &= \{\theta \in \Theta \mid g(\theta) \neq 0 \text{ and } \theta_r(x) > \theta_r(y)\} \\ \Theta_{x=y} &= \{\theta \in \Theta \mid g(\theta) \neq 0 \text{ and } \theta_r(x) = \theta_r(y)\}\end{aligned}$$

Observation 5.2: Since g is assumed to be a valid probability or density function (in the discrete and continuous cases), it follows that each of $\sum_{\theta} Pr\{DB|\theta\} * g(\theta)$ and $\int_{\Theta} Pr\{DB|\theta\} * g(\theta) d\theta$ converges to $Pr\{DB\}$.

The following lemmas are used in the proof of Theorem 5.1.

Lemma 5.1: Suppose Θ contains an infinite sequence $\theta_1, \theta_2, \dots, \theta_i, \dots$ (with each θ_i distinct) nondecreasing in $Pr\{DB|\theta_i\} * g(\theta_i)$, (i.e., $Pr\{DB|\theta_i\} * g(\theta_i) \leq Pr\{DB|\theta_{i+1}\} * g(\theta_{i+1})$, for all $i \geq 1$) with $Pr\{DB|\theta_j\} * g(\theta_j) > 0$ for some $j \geq 1$. Then:

- (i) When g is nonzero on a countably infinite number of $\theta \in \Theta$, the convergence of $\sum_{\theta} Pr\{DB|\theta\} g(\theta)$ is contradicted.
- (ii) When g is a probability density function, the convergence of $\int_{\Theta} Pr\{DB|\theta\} g(\theta) d\theta$ is contradicted.

Proof:

(i) g is nonzero on a countably infinite number of $\theta \in \Theta$: Then the existence of the monotone sequence contradicts the convergence of $\sum_{\theta} Pr\{DB|\theta\} g(\theta)$, since the series contains the infinite subseries $\sum_i Pr\{DB|\theta_i\} g(\theta_i)$ whose terms do not converge to zero.

(ii) g is a probability density function: The existence of the divergent series in (i) over discrete points on which the integral is evaluated implies the integral diverges. $\square$

Lemma 5.2: For any transaction pair $\{x, y\}$ and training sample $\overline{DB}$, the existence of bijections

$$\begin{aligned}\Phi_{x,y}: \Theta_{x \prec y} &\rightarrow \Theta_{x \succ y} \\ \Phi_{y,x}: \Theta_{y \prec x} &\rightarrow \Theta_{y \succ x}\end{aligned}$$

such that for every $\theta \in \Theta_{x \prec y}$, $\theta' \in \Theta_{y \prec x}$ we have both

$$[Pr\{\overline{DB}|\theta\} * g(\theta) \leq Pr\{\overline{DB}|\Phi_{x,y}(\theta)\} * g(\Phi_{x,y}(\theta))] \text{ and } [Pr\{\overline{DB}|\theta'\} * g(\theta') \leq Pr\{\overline{DB}|\Phi_{y,x}(\theta')\} * g(\Phi_{y,x}(\theta'))],$$

where the inequality is strict for at least one θ or θ' :

- (a) Is impossible when g is nonzero on a finite number of $\theta \in \Theta$.
- (b) Contradicts the convergence of $\sum_{\theta} Pr\{DB|\theta\} g(\theta)$ when g is nonzero on a countably infinite number of $\theta \in \Theta$.
- (c) Contradicts the convergence of $\int_{\Theta} Pr\{DB|\theta\} g(\theta) d\theta$ when g is a probability density function.

Proof: Assume the existence of such a pair of bijections and, WLOG, assume there exists $\theta_1 \in \Theta_{x \prec y}$ such that $[Pr\{\overline{DB}|\theta_1\} * g(\theta_1) < Pr\{\overline{DB}|\Phi_{x,y}(\theta_1)\} * g(\Phi_{x,y}(\theta_1))]$. (The statement of the theorem guarantees that at least one strict inequality holds; the argument is symmetric if we must choose $\theta_1 \in \Theta_{y \prec x}$).

Form an infinite sequence $\theta_1, \theta_2, \dots, \theta_i, \dots$ as:

$$\begin{aligned}\theta_{i+1} &= \Phi_{x,y}(\theta_i), \text{ if } \theta_i \in \Theta_{x \prec y} \text{ (i.e., if } i \text{ odd)} \\ \theta_{i+1} &= \Phi_{y,x}(\theta_i), \text{ if } \theta_i \in \Theta_{y \prec x} \text{ (i.e., if } i \text{ even)}\end{aligned}$$

Observe that this sequence is nondecreasing, that is, $Pr\{DB|\theta_i\} * g(\theta_i) \leq Pr\{DB|\theta_{i+1}\} * g(\theta_{i+1})$, $i \geq 1$, with strict inequality when $i=1$.

a) g is nonzero on a finite number of $\theta \in \Theta$. Since only θ_1 could be such that $g(\theta_1)=0$, some θ_k must repeat in the sequence. If θ_1 is not the first to repeat, the injective property of one of the bijections is violated. If θ_1 is the first to repeat, we have the inconsistent chain

$$Pr\{DB|\theta_1\} * g(\theta_1) < Pr\{DB|\theta_2\} * g(\theta_2) \leq \dots \leq Pr\{DB|\theta_{k-1}\} * g(\theta_{k-1}) \leq Pr\{DB|\theta_1\} * g(\theta_1)$$

of inequalities, a contradiction.

b-c) If some θ_k repeats in the sequence, we have the same inconsistent chain of inequalities as in (a). Otherwise, the θ_i in the sequence are distinct and the previous lemma contradicts the convergence of the sum and

case the Riemann integral is replaced by the Lebesgue integral.

integral. $\square$

Definition 5.2: Let $\hat{\Theta}$ be any subset of Θ , and x, y any pair of transactions. Φ is an x, y -reflection on $\hat{\Theta}$ if for each $\theta = \langle \theta_N, \theta_M \rangle \in \hat{\Theta}$, $\Phi(\theta) = \langle \theta'_N, \theta'_M \rangle$ is such that:

$$\theta_N(x) = \theta'_N(y), \theta_N(y) = \theta'_N(x), \theta_M(x) = \theta'_M(y), \text{ and } \theta_M(y) = \theta'_M(x).$$

We also apply Φ component-wise, that is, for $\theta = \langle \theta_N, \theta_M \rangle \in \hat{\Theta}$, we shall write $\Phi(\theta) = \langle \Phi(\theta_N), \Phi(\theta_M) \rangle$.

Note that there is no restriction on an x, y -reflection's effect on coordinates other than x and y .

We now prove a general result that is useful in establishing the form of an optimal detector for certain simple prior distributions g .

Theorem 5.1: Let g be a probability or density function over Θ and $\overline{DB}$ some training sample. Suppose that for each x, y transaction pair there exists a bijection (possibly depending on $\overline{DB}$)

$$\Phi_{x,y}: \Theta_{x \prec y} \rightarrow \Theta_{x \succ y},$$

which is an x, y -reflection on $\Theta_{x \prec y}$, such that either:

$$\forall \theta \in \Theta_{x \prec y}, Pr\{\overline{DB} | \theta\} * g(\theta) \geq Pr\{\overline{DB} | \Phi_{x,y}(\theta)\} * g(\Phi_{x,y}(\theta)) \text{ or}$$

$$\forall \theta \in \Theta_{x \prec y}, Pr\{\overline{DB} | \theta\} * g(\theta) \leq Pr\{\overline{DB} | \Phi_{x,y}(\theta)\} * g(\Phi_{x,y}(\theta)).$$

Then the collection of pairwise orders defined by:

$x \prec y$ when a bijection exists to satisfy the first condition, with the inequality strict for at least one $\theta \in \Theta_{x \prec y}$

$y \prec x$ when a bijection exists to satisfy the second condition, with the inequality strict for at least one $\theta \in \Theta_{x \prec y}$

$x = y$ when bijections exist to satisfy both conditions (and hence none of the inequalities is strict.)

is a collection of optimal pairwise orderings given $\overline{DB}$ (that is, each ordering in the collection minimizes each $\{x, y\}$'s contribution to rsk_1 given this fixed $\overline{DB}$).

Proof: Lemma 5.2 implies that, when a bijection Φ exists to satisfy one of the two conditions and the inequality is strict for at least one $\theta \in \Theta_{x \prec y}$, a bijection cannot exist to satisfy the other condition; hence the ordering rule is well defined.

We now establish that this ordering of each $\{x, y\}$ minimizes this pair's contribution to rsk_1 . θ with $g(\theta) = 0$ have no effect on risk contribution. For a fixed x, y , the loss incurred on $\theta \in \Theta_{x=y}$ by any ranking of x, y is identical, since in this case $\theta_M(x) * \theta_N(y) = \theta_M(y) * \theta_N(x)$. Hence, in the following analysis, we suppress θ such that $g(\theta) = 0$ or $\theta \in \Theta_{x=y}$.

It follows from (1) of Section 3.2 that the contribution to $rsk_1(\cdot, \overline{DB})$ of each $\{x, y\}$ transaction pair assumes one of the following values:

If we order as $x \prec y$:

$$\int_{\Theta_{x \prec y}} \theta_M(x) * \theta_N(y) * Pr\{DB | \theta\} g(\theta) + \Phi(\theta_M)(x) * \Phi(\theta_N)(y) * Pr\{DB | \Phi(\theta)\} g(\Phi(\theta)) d\theta$$

If we order as $x \succ y$:

$$\int_{\Theta_{x \prec y}} \theta_M(y) * \theta_N(x) * Pr\{DB | \theta\} g(\theta) + \Phi(\theta_M)(y) * \Phi(\theta_N)(x) * Pr\{DB | \Phi(\theta)\} g(\Phi(\theta)) d\theta$$

If we order as $x = y$: average of the above two quantities.

Since $\theta_N(x) = \Phi(\theta_N)(y)$ and $\theta_M(x) = \Phi(\theta_M)(y)$, we can write the contributions as

If we order as $x \prec y$:

$$\int_{\Theta_{x \prec y}} \theta_M(x) * \theta_N(y) * Pr\{DB | \theta\} g(\theta) + \theta_M(y) * \theta_N(x) * Pr\{DB | \Phi(\theta)\} g(\Phi(\theta)) d\theta$$

If we order as $x \succ y$:

$$\int_{\Theta_{x \prec y}} \theta_M(y) * \theta_N(x) * Pr\{DB | \theta\} g(\theta) + \theta_M(x) * \theta_N(y) * Pr\{DB | \Phi(\theta)\} g(\Phi(\theta)) d\theta$$

If we order as $x=y$: average of the above two quantities.

Since, by definition, $\theta_r(x) < \theta_r(y)$ (and hence $\theta_M(x) * \theta_N(y) < \theta_M(y) * \theta_N(x)$) for each $\theta \in \Theta_{x \prec y}$:

$Pr\{DB|\theta\} * g(\theta) \geq Pr\{DB|\Phi(\theta)\} * g(\Phi(\theta))$ for each $\theta \in \Theta_{x \prec y}$ implies the first contribution is no more than the second, while

$Pr\{DB|\theta\} * g(\theta) \leq Pr\{DB|\Phi(\theta)\} * g(\Phi(\theta))$ for each $\theta \in \Theta_{x \prec y}$ implies the second contribution is no more than the first. (When there is equality for each $\theta \in \Theta_{x \prec y}$, the contributions are identical.) Hence, the order specified for the pair $\{x, y\}$ orders the transaction pair in a manner that minimizes its contribution to rsk_1 . $\square$

Remark: As the following example demonstrates, the required bijections can exist and induce a collection of pairwise orders that is not consistent; in this case, the optimal Class 1 detector is not specified by this ordering rule (i.e., the optimal Class 1 detector is not pairwise optimal).

Example 5.1: First suppose that the following are the only four $\theta \in \Theta$ such that $g(\theta) > 0$.

θ_1 is such that $\theta_{1r}(x) < \theta_{1r}(y) < \theta_{1r}(z)$. Note $\theta_1 \in (\Theta_{x \prec y} \cap \Theta_{y \prec z} \cap \Theta_{x \prec z})$.

θ_2 is such that $\theta_{2r}(y) < \theta_{2r}(x) < \theta_{2r}(z)$. Note $\theta_2 \in (\Theta_{y \prec x} \cap \Theta_{y \prec z} \cap \Theta_{x \prec z})$.

θ_3 is such that $\theta_{3r}(z) < \theta_{3r}(x) = \theta_{3r}(y)$. Note $\theta_3 \in (\Theta_{z \prec x} \cap \Theta_{z \prec y})$.

θ_4 is such that $\theta_{4r}(z) < \theta_{4r}(x) = \theta_{4r}(y)$. Note $\theta_4 \in (\Theta_{z \prec y} \cap \Theta_{z \prec x})$.

Suppose that $\overline{DB}$ and g are such that

$$Pr\{\overline{DB}|\theta_1\} * g(\theta_1) = Pr\{\overline{DB}|\theta_4\} * g(\theta_4) < Pr\{\overline{DB}|\theta_2\} * g(\theta_2) = Pr\{\overline{DB}|\theta_3\} * g(\theta_3).$$

Define bijections:

$$\Phi_{x \prec y}: \Theta_{x \prec y} \rightarrow \Theta_{y \prec x} \text{ as } \Phi_{x \prec y}(\theta_1) = \theta_2.$$

$$\Phi_{y \prec z}: \Theta_{y \prec z} \rightarrow \Theta_{z \prec y} \text{ as } \Phi_{y \prec z}(\theta_1) = \theta_4 \text{ and } \Phi_{y \prec z}(\theta_2) = \theta_3.$$

$$\Phi_{z \prec x}: \Theta_{z \prec x} \rightarrow \Theta_{x \prec z} \text{ as } \Phi_{z \prec x}(\theta_4) = \theta_1 \text{ and } \Phi_{z \prec x}(\theta_3) = \theta_2.$$

It is easily verified that each of these bijections obeys the inequalities of Theorem 5.1 and together prescribe the orders $x \prec y$, $y \prec z$, and $z \prec x$. These three orders together are inconsistent, but do leave open the possibility that a consistent (and optimal) pd could be defined by resolving the equalities in a consistent way (any orderings of y and z and of z and x are pairwise optimal). However, we can mirror the cyclic structure from above, using disjoint collections of θ to augment each of the six sets $\Theta_{v \prec w}$ so that the resulting 3 bijections (which extend the 3 specified above) prescribe the orders $x \prec y$, $y \prec z$, and $z \prec x$. Hence, the pairwise optimal orderings in this case cannot be used to construct an optimal pd . $\square$

A theorem parallel to Theorem 5.1 holds for Class 2 detectors, where $Pr\{\overline{RS} \wedge \overline{DB}|\theta\}$ replaces $Pr\{\overline{DB}|\theta\}$ in the inequality conditions. The result for Class 2 detectors is established simply by showing that the pairwise orderings prescribed by the bijections are identical to those induced by the optimal Class 2 detector pd^* of Theorem 2.2 (and hence are consistent). The result, however, is of less utility for Class 2 detectors than Class 1 detectors, since the optimality of pd^* gives us a more convenient and broadly applicable tool for establishing the optimality of a given Class 2 detector.

5.2 Symmetric Anomaly Detection

An important illustration of how Theorem 5.1 can be applied is anomaly detection; when no prior information on attribute meaning is available.

Definition 5.3: $\theta = \langle \theta_N, \theta_M \rangle \in \Theta$ is N -ordered if, for each x and y pair, $\theta_r(x) < \theta_r(y)$ implies $\theta_N(x) \geq \theta_N(y)$. We say that distribution g on Θ is consistent with anomaly detection if g has mass 1 on $\Theta_{AD} = \{\theta \in \Theta \mid \theta \text{ is } N\text{-ordered}\}$.

Discussion: Anomaly detection has been characterized [9] as detecting events rarest in N , without explicit reference to the process M . Perhaps the most intuitive abstraction of a (N, M) relationship consistent with anomaly detection is *common in N implies rare in M* , meaning $\theta_N(x) > \theta_N(y)$ implies $\theta_M(x) \leq \theta_M(y)$. Observe that the common-rare condition implies N -ordered, since if we had $\theta_r(x) < \theta_r(y)$ yet also $\theta_N(x) < \theta_M(y)$, the common-rare

condition leads to a contradiction, since it forces $\theta_M(x) \geq \theta_M(y)$ making impossible the premise $\theta_r(x) < \theta_r(y)$. On the other hand, we can have N -ordered without obeying this common-rare condition: We can have $\theta_r(x) < \theta_r(y)$, $\theta_N(x) > \theta_N(y)$, and $\theta_M(x) > \theta_M(y)$. Further, if θ is N -ordered, the most suspicious x (highest $\theta_r(x)$ value) are indeed the events rarest in N (lowest $\theta_N(x)$ value). Hence, θ_{AD} is a precise characterization of anomaly detection.

The following operator is used in the proof of Theorem 5.2.

Definition 5.4: For any θ (in either Θ_N or Θ_M) let $\theta_{x/y}$ denote the θ' obtained by interchanging the coordinates $\theta(x)$ and $\theta(y)$. Extend to $\theta \in \Theta$ this exchange operator by $\theta_{x/y} = \langle (\theta_N)_{x/y}, (\theta_M)_{x/y} \rangle$.

Observe that for any $\theta \in \Theta$ and any transactions x, y , $\theta_N(x) = (\theta_N)_{x/y}(y)$, $\theta_M(x) = (\theta_M)_{x/y}(y)$, and $\theta_r(x) = (\theta_r)_{x/y}(y)$.

Theorem 5.2: If g is consistent with anomaly detection and has the additional property that, for each $\theta \in \Theta_{AD}$, $g(\theta) = g(\theta_{x/y})$, then the frequentist detector defined by $pd(x) = 1/\text{count}(DB, x)$ minimizes risk among Class 1 detectors.

Proof: We establish that, when the conditions of the current theorem are satisfied, bijections exist to satisfy the conditions of Theorem 5.1 and that $pd(x) = 1/\text{count}(DB, x)$ orders each $\{x, y\}$ pair identically with the order prescribed by Theorem 5.1. (Except in the trivial special case handled at the proof's conclusion.) Since pd maps S to $\mathbb{R}$, the resulting collection of pairwise orderings necessarily is consistent and hence Theorem 5.1 implies the optimality of pd among Class 1 detectors.

Observe first that each member θ of the partition cell $\Theta_{x < y} \subset \Theta_{AD}$ has the property that $\theta_N(x) > \theta_N(y)$, or $\theta_N(x) = \theta_N(y)$ and $\theta_M(x) < \theta_M(y)$. Similarly, each member θ of the partition cell $\Theta_{x > y} \subset \Theta_{AD}$ has the property that $\theta_N(x) < \theta_N(y)$, or $\theta_N(x) = \theta_N(y)$ and $\theta_M(x) > \theta_M(y)$. We define Φ to satisfy Theorem 5.1 as the x/y exchange operator from Definition 5.4 (clearly this is an x, y -reflection) and claim this Φ is a bijection from $\Theta_{x < y}$ to $\Theta_{x > y}$. The first step is to establish that if $\theta \in \Theta_{AD}$, then also $\Phi(\theta) \in \Theta_{AD}$. The condition for $\Phi(\theta)$'s membership in Θ_{AD} obviously is preserved on w and z different from x and y , since these components are identical in θ and $\Phi(\theta)$. It holds also if one of w and z is x or y ; WLOG, consider the pair x and z , z different from y . Since in θ the condition must hold for y and z , it must hold for x and z in $\Phi(\theta)$. Finally, consider x, y and suppose $\Phi(\theta)_r(y) < \Phi(\theta)_r(x)$. Then it must be that $\theta_r(x) < \theta_r(y)$ and hence that $\theta_N(x) \geq \theta_N(y)$. Therefore $\Phi(\theta_N)(y) \geq \Phi(\theta_N)(x)$, as required. It then is apparent that Φ maps from $\Theta_{x < y}$ to $\Theta_{x > y}$. To see Φ is a bijection, define Φ^{-1} to operate on members of $\Theta_{x > y}$ in the same manner that Φ operates on members of $\Theta_{x < y}$; it is apparent that Φ and Φ^{-1} are inverses.

To see that Φ obeys the inequality conditions of Theorem 5.1, consider three cases for $\overline{DB}$:

1. $\text{count}(\overline{DB}, x) < \text{count}(\overline{DB}, y)$: It follows from the Theorem 2.1 that $Pr\{\overline{DB}|\theta\}$ and $Pr\{\overline{DB}|\Phi(\theta)\}$ differ only in that $Pr\{\overline{DB}|\theta\}$ contains the terms $\theta_N(x)^{\text{count}(\overline{DB}, x)}$ and $\theta_N(y)^{\text{count}(\overline{DB}, y)}$ while $Pr\{\overline{DB}|\Phi(\theta)\}$ contains instead $\theta_N(x)^{\text{count}(\overline{DB}, y)}$ and $\theta_N(y)^{\text{count}(\overline{DB}, x)}$. Since $\theta_N(x) \geq \theta_N(y)$ and $g(\theta) = g(\Phi(\theta))$, we have $Pr\{\overline{DB}|\theta\} * g(\theta) \leq Pr\{\overline{DB}|\Phi(\theta)\} * g(\Phi(\theta))$ for every $\theta \in \Theta_{x < y}$.
2. $\text{count}(\overline{DB}, x) > \text{count}(\overline{DB}, y)$: We similarly obtain $Pr\{\overline{DB}|\theta\} * g(\theta) \geq Pr\{\overline{DB}|\Phi(\theta)\} * g(\Phi(\theta))$ for every $\theta \in \Theta_{x < y}$.
3. $\text{count}(\overline{DB}, x) = \text{count}(\overline{DB}, y)$: We similarly obtain $Pr\{\overline{DB}|\theta\} * g(\theta) = Pr\{\overline{DB}|\Phi(\theta)\} * g(\Phi(\theta))$ for every $\theta \in \Theta_{x < y}$.

We now establish that pd orders each $\{x, y\}$ pair in the manner prescribed by Theorem 5.1. (This assumes at least one $\theta \in \Theta_{x < y}$ is such that $\theta_N(x) \neq \theta_N(y)$; the special case where this assumption fails is handled below.) To see this, we need only observe that when $\text{count}(\overline{DB}, x) \neq \text{count}(\overline{DB}, y)$, the inequality obeyed by the bijection $\Phi_{x < y}$ is strict on any $\theta \in \Theta_{x, y}$ such that $\theta_N(x) \neq \theta_N(y)$, and the direction of the inequality prescribes the same ordering of x, y as that induced by pd ; when $\text{count}(\overline{DB}, x) = \text{count}(\overline{DB}, y)$ both Theorem 5.1 and pd order $x = y$.

In the trivial case that $\theta_N(x) = \theta_N(y)$ for all $\theta_N \in \Theta_{x < y}$, the correspondence induced by Φ (i.e., as used in the proof of Theorem 5.1) makes it easy to see that any of the three orderings of x, y results in the same contribution to risk, since in this case $Pr\{\overline{DB}|\theta\} * g(\theta) = Pr\{\overline{DB}|\Phi(\theta)\} * g(\Phi(\theta))$ for every $\overline{DB}$ and every $\theta \in \Theta_{x < y}$.

Hence, pd induces a collection of optimal pairwise orderings which, since pd maps from $S \rightarrow \mathbb{R}$, is consistent. $\square$

Discussion: The symmetry property of g required by the theorem is implied when we have no prior information on attribute meaning, and hence no transaction can be favored over another. In particular, the condition is equivalent to the condition that all permutations of any given probability vector have the same prior density, since a sequence of interchanges can map any permutation to any other permutation. Hence, while the condition allows different shaped distributions (e.g., all transactions equally likely vs. distributions that makes some transactions more likely than other) to be assigned different priors, it prohibits assigning larger prior density to a distribution that favors x over y than to an identically-shaped distribution that favors y over x .

A simple prior distribution that satisfies the conditions of Theorem 5.2 associates each θ_N only with the flat (uniform) θ_M (denoted θ_{M_U}), and further assigns density so that $g(\theta_N, \theta_{M_U}) = g(\theta'_N, \theta_{M_U})$ for every $\theta_N, \theta'_N \in \Theta_N$. This prior distribution may be considered *anomaly detection with a completely uninformed prior on Θ_N* .

5.3 Minimizing Class 1 Risk Under the Hypothesis of Specific Relevant Attributes

Theorem 5.2 may seem to go against experience, which shows that using a pd defined in terms of raw frequency counts leads to poor results. In particular, it generally is the case that a great majority of the transactions in the training data have count 1, and transactions encountered in the data to be analyzed were unseen in the training data, making useless the raw frequency counts. Experience indicates that selection of subsets of the attributes is required before an effective detector can be defined. Basing a detector on projection sets, however, appears contrary to the result of Theorem 5.2. The reconciliation of theory and practice is that we do not lack totally information regarding attribute behavior. Rather, we believe *a priori* that some attributes will be irrelevant, though we don't know which. Since the modeling of such prior information results in a prior distribution g which violates the symmetry required for the applicability of Theorem 5.2 (see Observation 5.4 which follows), the use of raw, unprojected frequency counts is not supported in such cases.

In this section, we begin the analysis by supposing we know the set of relevant attributes. Section 6 considers the more realistic problem in which the set(s) of relevant attributes is not known in advance.

Definition 5.5: Let $A \subseteq U$ be a subset of attributes and x any transaction. The projection $x[A]$ of x onto A is the transaction obtained by restricting x to the attributes in A . We write $x[A] = z[A]$ if and only if x and z agree on each attribute in A and observe that projection onto any $A \subseteq U$ induces on S an equivalence class structure, that is, $z \in [x]_A$ iff $z[A] = x[A]$. We define also the following aggregate class quantities:

$$\begin{aligned}\theta_N(x[A]) &= \sum_{z \in [x]_A} \theta_N(z) \\ \theta_M(x[A]) &= \sum_{z \in [x]_A} \theta_M(z) \\ \theta_r(x[A]) &= \theta_M(x[A]) / \theta_N(x[A]) \\ \text{count}(DB, x[A]) &= \sum_{z \in [x]_A} \text{count}(DB, z)\end{aligned}$$

Consider now the following family of prior distributions on Θ which, intuitively, states that only the subset A of attributes is relevant to determining the relative frequencies of transactions generated by N and M and, consequently, to detection.

Definition 5.6: The subset Θ_A of Θ is defined as $\Theta_A = \{\theta \mid \text{whenever } x[A] = z[A], \theta_N(x) = \theta_N(z) \text{ and } \theta_M(x) = \theta_M(z)\}$. We say that g is consistent with H_A (the hypothesis that only A is relevant to detection) if g has mass 1 on Θ_A .

Observation 5.3: A sufficient condition for the validity of H_A is:

In each of N and M , attributes in $(U-A)$ are independent of those in A and N and M is each uniform on $(U-A)$ in the sense that for all x and z , $\theta_N(x[U-A]) = \theta_N(z[U-A])$ and $\theta_M(x[U-A]) = \theta_M(z[U-A])$. In this case, if $x[A] = z[A]$ then $\theta_N(x) = \theta_N(x[A]) * \theta_N(x[U-A]) = \theta_N(z[A]) * \theta_N(z[U-A]) = \theta_N(z)$ and similarly for θ_M .

Observation 5.4: Suppose g is such that the inequality $g(\theta) > g(\theta')$ holds whenever $\theta \in \Theta_A$ for *some* proper subset $A \subset U$ and $\theta' \notin \Theta_B$ for *every* proper subset $B \subset U$. Then g violates the symmetry required by Theorem 5.2 since, as the following lemma demonstrates, $\theta \in \Theta_A \Rightarrow \theta_{x/y} \notin \Theta_B$ for any proper subset $B \subset U$. (The result assumes each attribute has more than 2 distinct values and $\theta_N(x) \neq \theta_N(y)$ or $\theta_M(x) \neq \theta_M(y)$.)

Lemma 5.3: Let $A \subset U$ be a proper subset of the set U of all attributes. Let $\theta \in \Theta_A$ and let x and y be transactions such that $\theta_N(x) \neq \theta_N(y)$ or $\theta_M(x) \neq \theta_M(y)$. Then $\theta_{x/y} \notin \Theta_B$ for any proper subset $B \subset U$. (The result assumes each attribute has more than 2 distinct values.)

Proof: First we argue that unless $A \cup B = U$, we cannot have $\theta_{x/y} \in \Theta_B$. Suppose $A \cup B \neq U$. Then class $x[A]$ contains z different from x , but with $x[A \cup B] = z[A \cup B]$. Since $z \in [x]_A$, we have $\theta_N(x) = \theta_N(z)$ and $\theta_M(x) = \theta_M(z)$. Since z is neither x nor y , we must have $\theta_{x/yN}(x) \neq \theta_{x/yN}(z)$ or $\theta_{x/yM}(x) \neq \theta_{x/yM}(z)$, by the lemma's premise. But $x[B] = z[B]$ and hence $\theta_{x/y} \notin \Theta_B$.

Now we argue that unless $A \subset B$, we cannot have $\theta_{x/y} \in \Theta_B$. Suppose $a \in (A - B)$. Choose any z such that $x[A \cup B - \{a\}] = z[A \cup B - \{a\}]$, and $x[a] \neq z[a]$ and $z[a] \neq y[a]$. Choose any x' different from x such that $x[A] = x'[A]$. Choose $z' \in [z]_A$, different from z , so that $x'[A \cup B - \{a\}] = z'[A \cup B - \{a\}]$. Observe that:

since $x[A] = x'[A]$, $\theta_N(x) = \theta_N(x')$ and $\theta_M(x) = \theta_M(x')$

since $z[A] = z'[A]$, $\theta_N(z) = \theta_N(z')$ and $\theta_M(z) = \theta_M(z')$

Further, since $x[B] = z[B]$ and $x'[B] = z'[B]$, if $\theta_{x/y} \in \Theta_B$, we must have

$\theta_{x/yN}(x) = \theta_{x/yN}(z)$ and $\theta_{x/yM}(x) = \theta_{x/yM}(z)$

$\theta_{x/yN}(x') = \theta_{x/yN}(z')$ and $\theta_{x/yM}(x') = \theta_{x/yM}(z')$

But $\theta_N(x) \neq \theta_{x/yN}(x)$ or $\theta_M(x) \neq \theta_{x/yM}(x)$ by the lemma's premise. Further, none of x' , z , or z' is x or y ; hence the θ_N and θ_M values for each of these transactions is the same under θ and $\theta_{x/y}$. Consequently, the above equalities cannot be satisfied simultaneously. $\square$

The following map is used in the proof of Theorem 5.3, playing the role of the bijection required by Theorem 5.1.

Definition 5.7: Define $Q_A(x, y; \theta)$ for any $\theta \in \Theta_A$ as interchanging the (common) θ_N and θ_M values of members of $x[A]$ with the (common) values of members of $y[A]$.

Clearly Q_A is well defined on Θ_A and maps Θ_A to itself. Observe also that $Q_U(x, y; \theta)$ is exactly the x/y interchange operation.

Theorem 5.3: If g has mass 1 on $\Theta_A \cap \Theta_{AD}$, and if for each x, y pair $g(\theta) = g(Q_A(x, y; \theta))$ for all $\theta \in \Theta_A \cap \Theta_{AD}$, then the detector $pd_A(x) = 1/\text{count}(DB, x[A])$ minimizes risk among Class 1 detectors.

Proof: As in the proof of Theorem 5.2, we establish that, when the conditions of the current theorem are satisfied, bijections exist to satisfy the conditions of Theorem 5.1 and that $pd_A(x) = 1/\text{count}(DB, x[A])$ orders each $\{x, y\}$ pair identically with the order prescribed by Theorem 5.1. (Except in the trivial special case handled at the proof's conclusion.) Since pd_A maps S to $\mathbb{R}$, the resulting collection of pairwise orderings is necessarily consistent and hence Theorem 5.1 implies the optimality of pd_A among Class 1 detectors.

Observe first that each member θ of the partition cell $\Theta_{x < y} \subset \Theta_A \cap \Theta_{AD}$ has the property that $\theta_N(x) > \theta_N(y)$, or $\theta_N(x) = \theta_N(y)$ and $\theta_M(x) < \theta_M(y)$. Similarly, each member θ of the partition cell $\Theta_{x > y} \subset \Theta_A \cap \Theta_{AD}$ has the property that $\theta_N(x) < \theta_N(y)$, or $\theta_N(x) = \theta_N(y)$ and $\theta_M(x) > \theta_M(y)$. Of course these relationships hold between all members of $x[A]$ and $y[A]$. We define Φ as the function $Q_A(x, y; \cdot)$ from above (clearly this is an x, y -reflection) and claim this Φ is a bijection from $\Theta_{x < y}$ to $\Theta_{x > y}$. The argument that Φ is a bijection closely follows that from Theorem 5.2; the three cases here being w and z are in classes other than $x[A]$ and $y[A]$, one of w and z is in one of the classes $x[A]$ and $y[A]$, and $w \in [y]_A$ and $z \in [y]_A$.

To see that Φ obeys the inequality conditions of Theorem 5.1, consider three cases for $\overline{DB}$:

1. $\text{count}(\overline{DB}, x[A]) < \text{count}(\overline{DB}, y[A])$: It follows from the Theorem 2.1 that $Pr\{\overline{DB} | \theta\}$ and $Pr\{\overline{DB} | \Phi(\theta)\}$ differ only in that $Pr\{\overline{DB} | \theta\}$ contains the terms $\theta_N(x)^{\text{count}(\overline{DB}, x[A])}$ and $\theta_N(y)^{\text{count}(\overline{DB}, y[A])}$ while $Pr\{\overline{DB} | \Phi(\theta)\}$ contains instead $\theta_N(x)^{\text{count}(\overline{DB}, y[A])}$ and $\theta_N(y)^{\text{count}(\overline{DB}, x[A])}$. (Note that since in each of θ_N and $\Phi(\theta_N)$ components for transactions agreeing on A are identical to each other, multiple terms of the product collapse to single terms such as the above.) Since $\theta_N(x) > \theta_N(y)$ and $g(\theta) = g(\Phi(\theta))$, we have

- $Pr\{\overline{DB}|\theta\} * g(\theta) \leq Pr\{DB|\Phi(\theta)\} * g(\Phi(\theta))$ for every $\theta \in \Theta_{x \prec y}$.
2. $count(\overline{DB}, x[A]) > count(\overline{DB}, y[A])$: We similarly obtain $Pr\{\overline{DB}|\theta\} * g(\theta) \geq Pr\{\overline{DB}|\Phi(\theta)\} * g(\Phi(\theta))$ for every $\theta \in \Theta_{x \prec y}$.
 3. $count(\overline{DB}, x[A]) = count(\overline{DB}, y[A])$: We similarly obtain $Pr\{\overline{DB}|\theta\} * g(\theta) = Pr\{\overline{DB}|\Phi(\theta)\} * g(\Phi(\theta))$ for every $\theta \in \Theta_{x \prec y}$. Note that this case holds whenever $x[A] = y[A]$.

The argument that the collection of orders induced by pd_A is pairwise optimal is completely analogous to that of Theorem 5.2. When at least one $\theta \in \Theta_{x \prec y}$ is such that $\theta_N(x) \neq \theta_N(y)$, $\{x, y\}$ is ordered in the manner prescribed by Theorem 5.1; otherwise, any of the three orderings of x, y results in the same contribution to risk. Hence, pd_A induces a collection of optimal pairwise orderings which, since pd maps from $S \rightarrow \mathbb{R}$, is consistent. $\square$

Discussion:

1. To our knowledge, this is the first risk-based justification of the common practice of attribute projection (known also as *attribute selection*).
2. The condition on g is the natural generalization of that for Theorem 5.2, when density is restricted to Θ_A ; all permutations within Θ_A of any given probability vector have equal prior density, while a permutation outside of Θ_A has zero density.
3. If $g(\Theta_A) = 1$ then $g(\Theta_{A'}) = 1$ for all $A' \supset A$ (since then $\Theta_{A'} \supset \Theta_A$). However, in this case, if g satisfies the symmetry condition on $\mathcal{Q}_A$ it generally will not satisfy it on $\mathcal{Q}_{A'}$, since for $\theta \in \Theta_{A'} - \Theta_A$, $g(\theta) = 0$, yet, for some such θ , $\theta' = \mathcal{Q}_{A'}(x, y; \theta)$ is a member of Θ_A and $g(\theta') \neq 0$. Consequently, the theorem's premise is generally satisfied only by the minimal A such that $g(\Theta_A) = 1$.
4. A simple prior distribution that satisfies the condition of Theorem 5.3 associates each $\theta_N \in \Theta_A$ only with θ_{M_U} , and further assigns density so that $g(\theta_N, \theta_{M_U}) = g(\theta'_N, \theta_{M_U})$ for every $\theta_N, \theta'_N \in \Theta_{A_N}$.

6. Heuristic Risk Minimization for Class 1 Detectors

The previous sections developed a mathematical framework and derived theoretical results for phenomena detection, including NP-hardness results for Class 1 detection. While Section 5 presented simple, optimal detectors for phenomena detection when the distribution g on Θ obeys certain restrictions, the detection problems of interest typically are far more difficult. For example, Theorem 5.3 justifies attribute projection onto A if we know that A is the only attribute set relevant to detection. In practice, however, while we may believe that only a fraction of the attributes are relevant to detection, we typically don't know *a priori* the identity of the relevant attributes.

Tackling the detection problems of the most practical importance requires a heuristic approach. We have developed an experimental software system embodying a detection methodology ground in the theory developed in the previous sections of this paper. Extensive testing of the system is underway, and detailed experimental results will be reported in a forthcoming paper. In this section, we describe several theoretically interesting aspects of the methodology, including:

1. Techniques for identifying important attribute subsets.
2. The use of surrogate phenomena models.
3. The definition of a k -ordered detector as a simple mechanism for consistently resolving conflicting evidence.

Section 6.3 reports limited test results as a preliminary proof of concept for our methodology.

6.1 Assumptions on the Prior Distribution

In order to study the prior distributions of interest, we introduce the concept of a minimal hypothesis.

Definition 6.1: For $A \subseteq U$, Θ_{mA} denotes a minimal hypothesis, defined as the subset

$$\Theta_{mA} = \{\theta \mid \theta \in \Theta_A \text{ and } \theta \notin \Theta_{A'} \text{ for each } A' \subset A\} \text{ of } \Theta_A.$$

These hypotheses are of interest because we will wish to specify a prior distribution that assigns density to a θ based on the (unique) minimal hypothesis that contains it (i.e., otherwise, θ is a member of many nested Θ_A).

The following results establish that the collection $\{\Theta_{m_i}\}$ of minimal hypotheses partition Θ .

Lemma 6.1: If $\theta \in \Theta_A \cap \Theta_B$, then $\theta \in \Theta_{A \cap B}$.

Proof: Let $C = A \cap B$ and suppose to the contrary, that $\theta \in \Theta_A \cap \Theta_B$ but $\theta \notin \Theta_C$. Then there exist distinct transactions x, y such that $x[C] = y[C]$ but either $\theta_N(x) \neq \theta_N(y)$ or $\theta_M(x) \neq \theta_M(y)$. Assume $\theta_N(x) \neq \theta_N(y)$; the argument is identical if $\theta_M(x) \neq \theta_M(y)$. Construct as follows a third transaction z :

$z[U - (A \cup B)] \leftarrow \text{anything}$
 $z[C] \leftarrow x[C]$ (recall $x[C] = y[C]$)
 $z[A - C] \leftarrow x[A - C]$
 $z[B - C] \leftarrow y[B - C]$

Since $z[A] = x[A]$ and $\theta \in \Theta_A$, we must have $\theta_N(z) = \theta_N(x)$. Since $z[B] = y[B]$ and $\theta \in \Theta_B$, we must have $\theta_N(z) = \theta_N(y)$. But this is impossible, given that $\theta_N(x) \neq \theta_N(y)$. $\square$

Lemma 6.2: If $\theta \in \Theta_A \cap \Theta_B$ and A and B are disjoint, each of θ_N and θ_M is uniform on S .

Proof: If $\theta \in \Theta_\emptyset$, $x[\emptyset] = y[\emptyset]$ for all $x, y \in S$ and hence $\theta(x) = \theta(y)$ for all x, y .

Lemma 6.3: The minimal hypotheses $\{\Theta_{m_i}\}$ partition Θ , that is, every $\theta \in \Theta$ is a member of exactly one Θ_{m_i} .

Proof:

At least one: Since $\Theta_U = \Theta$, if $\theta \notin \Theta_{m_U}$, there must be an $A \subset U$ such that $\theta \in \Theta_A$ and there thus must be at least one minimal such A . For this A , $\theta \in \Theta_{m_A}$.

At most one: Suppose $\theta \in \Theta_{m_A} \cap \Theta_{m_B}$ for distinct sets A and B . Then $\theta \in \Theta_A \cap \Theta_B$ and by Lemma 6.1, $\theta \in \Theta_{A \cap B}$. But for distinct A and B , $A \cap B$ is a proper subset of at least one of A and B , contradicting that $\theta \in \Theta_{m_A} \cap \Theta_{m_B}$. $\square$

Our techniques for heuristic risk minimization are most appropriate when the prior distribution g approximates the following two conditions.

1. For each $A_i \subset U$ of a given cardinality, the $\Theta_{m_{A_i}}$ have the same mass under g . This restriction is consistent with the fact that we have no prior semantic knowledge applying to the attributes and, hence, all subsets of k attributes are equally likely to be a relevant set.
2. Within any $\Theta_{m_{A_i}}$, g is uniform on the N component. That is, for every $\bar{\theta}_N \in \Theta_{m_{A_i}}$, the marginal densities $g(\bar{\theta}_N) \triangleq \int_{\theta_M \in \Theta_{m_{A_i}}} g(\bar{\theta}_N, \theta_M) d\theta_M$ are the same. This restriction states that we have no prior knowledge (beyond what might be captured by our distribution on the minimal hypotheses) of what N processes to expect.

These are reasonable global assumptions with respect to which we develop a generally applicable class of detection algorithms. A wide variety of prior structures approximate the two conditions, for example:

- a) *Different biases on cardinality are permitted.* While we often will have no explicit prior information specifying the relationship between g and cardinality, for a given application we might have some prior bias, such as a rough idea of the fraction of attributes likely to be irrelevant. Heuristics under study are tailored to g 's cardinality bias, either (i) By explicitly modeling its functional form; or (b) By less explicit means such as the k -ordered detector defined in Section 6.2.
- b) *Different N and M relationships are permitted.* Within a given $\Theta_{m_{A_i}}$, the θ_N, θ_M pairs g associates is not constrained. For example, it may be that under one g , a relatively flat θ_N is paired only with relatively flat θ_M , while under a second g , a relatively flat θ_N is paired with certain peaked θ_M . Different g characteristics mandate different instantiations for the detection heuristics; in particular, our heuristics capture

such characteristics via choice of M surrogates.

Observe that the restriction to (N,M) relationships consistent with Θ_{AD} has been dropped. Among the motivations for moving outside Θ_{AD} are: (i) We wish our techniques to be applicable beyond anomaly detection; and (ii) The restriction to Θ_{AD} , which allowed us to derive optimal pd when g was symmetric (Theorem 5.2) and when only one Θ_A had mass (Theorem 5.3), is of only limited utility in the current context.

6.2 General Description of Our Heuristic Technique

We obtain from expression (1) of Section 3.2 the following expression, arranged with respect to the partitioning collection $\{\theta_{m_{A_i}}\}$ of minimal hypotheses. In the following, $prod_pd(x,y;\theta)$ denotes $\theta_M(x)*\theta_N(y)$ if $pd(x)<pd(y)$, $\theta_M(y)*\theta_N(x)$ if $pd(y)<pd(x)$, and $\frac{1}{2}*(\theta_M(x)*\theta_N(y) + \theta_M(y)*\theta_N(x))$ if $pd(x)=pd(y)$.

$$rsk'(pd) = \sum_{DB} \left(\sum_{\{x,y\}} \left(\int_{\Theta_{m_{A_1}}} prod_pd(x,y;\theta) * Pr\{DB|\theta_N\} g(\theta) d\theta + \int_{\Theta_{m_{A_2}}} prod_pd(x,y;\theta) * Pr\{DB|\theta_N\} g(\theta) d\theta + \dots + \int_{\Theta_{m_{A_k}}} prod_pd(x,y;\theta) * Pr\{DB|\theta_N\} g(\theta) d\theta \right) \right),$$

where $A_1, \dots, A_k$ are the subsets of U , including the empty set and U itself. It follows from (1) that for Class 1 detector pd , $rsk'(pd)$ differs from $rsk_1(pd)$ (and hence from $rsk(pd)$) only by terms and factors common to the risk of every Class 1 detector.

A Heuristic for Ranking a Transaction Pair With Respect to a Single $\Theta_{m_{A_i}}$

Because the class of prior distributions under consideration permits a wide range of (N,M) relationships, determining the optimal ranking of an $\{x,y\}$ -transaction pair, even with respect to a single nonzero mass $\Theta_{m_{A_i}}$, is a complex task. Though we shall not be assuming a single nonzero mass $\Theta_{m_{A_i}}$, we begin by describing a technique for ranking transaction pairs based on a single $\Theta_{m_{A_i}}$. This technique is a central component of the heuristics to follow, which attempt to rank each $\{x,y\}$ pair optimally with respect to a single $\Theta_{m_{A_i}}$, selected by search heuristics specifically for $\{x,y\}$.

Let $\theta_{m_{A_i},N}^*$ denote the N component of the $\theta_{A_i}^*$, identified in the following theorem[†], that maximizes $Pr\{DB|\theta\}$ among $\theta \in \Theta_{m_{A_i}}$.

Theorem 6.1: Let DB be any sample of size n with count vector $\langle c_1, \dots, c_i, \dots, c_s \rangle$. $\theta_{A_i}^* \in \Theta_{A_i}$ maximizes $Pr\{DB|\theta\}$ among $\theta \in \Theta_{A_i}$ if and only if for $1 \leq i \leq s$, the component $\theta_{A_i,N}^*(x_i)$ of $\theta_{A_i}^*$ is equal to

$$\frac{a_i}{k_i * n},$$

where $a_i = \text{count}(DB, x_i[A])$ and k_i is the number of distinct members of equivalence class $x_i[A]$.

Proof: Let the classes under A be numbered $1, 2, \dots, m$. Then, since we are restricted to $\theta \in \Theta_{A_i}$, we denote by θ_i

[†]If this $\theta_{A_i}^*$ happens to be a member of Θ_B for $B \subset A_i$, perturb by ϵ the appropriate components of the maximizer so that the resulting $\theta' \in \Theta_{m_{A_i}}$.

the probability $\theta_N(y)$ assigned to each member y of the i^{th} class, and (summing exponents of each common base θ_i) the quantity to be maximized is

$$\theta_1^{a_1} \dots \theta_{m-1}^{a_{m-1}} \left[\frac{1 - \sum_{i=1}^{m-1} k_i \theta_i}{k_m} \right]^{a_m}.$$

For permissible values of θ_i , this function is maximized at $\theta_i = \frac{a_i}{k_i \cdot n}$, $1 \leq i \leq m-1$, as can be verified by inspection of the $s-1$ partial derivatives. That is, for $1 \leq i \leq m-1$, the derivative with respect to θ_i is

$$\text{constant} * [a_i \theta_i^{a_i-1} * \left[\frac{1 - \sum_{i=1}^{m-1} k_i \theta_i}{k_m} \right]^{a_m} - \frac{k_i}{k_m} \theta_i^{a_i} * a_m * \left[\frac{1 - \sum_{i=1}^{m-1} \theta_i}{k_m} \right]^{a_{m-1}}].$$

These derivatives are simultaneously 0 when $\theta_j = \frac{a_j}{(k_j \cdot n)}$, for $1 \leq j \leq m-1$, i.e., under this assignment, the above simplifies to:

$$a_i * \left(\frac{a_i}{k_i n} \right)^{a_i-1} * \left(\frac{a_m}{k_m n} \right)^{a_m} - \frac{k_i}{k_m} * \left(\frac{a_i}{k_i n} \right)^{a_i} * a_m * \left(\frac{a_m}{k_m n} \right)^{a_{m-1}}$$

which is 0. This is the derivative's only zero for permissible values of θ_i and inspection shows the point to be a maxima. $\square$

The detector used for a single $\Theta_{m_{A_i}}$ is: $pd_i(x) = F[\Theta_{m_{A_i},N}^*(x)] / \Theta_{m_{A_i},N}^*(x)$, where $F[\cdot]$ denotes a mapping from $\Theta_{m_{A_i},N}$ to $\Theta_{m_{A_i},M}$. Intuitively, we attempt to construct F so as to map to a surrogate θ_M most representative of the M models which g associates with $\theta_{m_{A_i},N}^*$. Often, this is the θ_M that maximizes $g(\theta_{m_{A_i},N}^*, \cdot)$, though other choices sometimes are appropriate. Observe that it follows from Theorem 6.1 that $pd_i(x)$'s denominator is $\text{count}(DB, [x]_{m_{A_i}}) / | [x]_{m_{A_i}} |$. When $\text{count}(DB, [x]_{m_{A_i}}) = 0$, we define $pd_i(x)$ to be equal to the infinity constant (see the extended definition of $\theta_r(x)$ at the beginning of Section 5), unless $F[\Theta_{m_{A_i},N}^*(x)] = 0$ also, in which case $pd_i(x)$ is defined to be unity.

Before describing our overall technique -- which includes heuristics for determining which $\Theta_{m_{A_i}}$ is to be used in the ranking of each $\{x, y\}$ -- we justify briefly the two central aspects of the above rule for ranking with respect to a single $\Theta_{m_{A_i}}$.

1. *Justification of Form of pd :* We are selecting a single point $\theta \in \Theta_{m_{A_i}}$ at which to evaluate the integrand and using the value at this point to represent the integral's behavior; ordering x, y by the values $pd_i(x)$ and $pd_i(y)$ minimizes $\Theta_{m_{A_i}}$'s contribution to rsk' at this point, since $\theta_r(x) < \theta_r(y)$ if and only if $\theta_M(x) * \theta_N(y) < \theta_M(y) * \theta_N(x)$. The technique for choosing the representative evaluation point first finds maximizer θ_N^* within $\Theta_{m_{A_i}}$ of $Pr\{DB|\theta\}$ and then evaluates the $pd_i(x)$ with respect to this θ_N^* and the surrogate $F[\theta_N^*]$. Notice that assumption (2) on g (g uniform on θ_N within any $\Theta_{m_{A_i}}$) implies that maximizer θ_N^* within $\Theta_{m_{A_i}}$ of $Pr\{DB|\theta\}$ maximizes also $\int_{\Theta_{m_{A_i},M}} Pr\{DB|\theta\} g(\theta_N, \theta_M) d\theta_M = Pr\{DB|\theta_N\} \int_{\Theta_{m_{A_i},M}} g(\theta_N, \theta_M) d\theta_M$ within $\Theta_{m_{A_i}}$.

The strategy of fixing the N model at the maximizing θ_N^* and only then selecting the M model most closely linked with this θ_N^* , of course, is only a heuristic. The heuristic may not be effective if, for example, g 's slope is dramatically greater than that of $Pr\{DB|\theta\}$, in which case $F[\theta_N^*]$ could be significantly different from $F[\theta_N^*]$.

for θ'_N near θ_N^* (sufficiently close that $Pr\{DB|\theta'_N\} \approx Pr\{DB|\theta_N^*\}$), potentially making $(\theta'_N, F[\theta'_N])$ a significantly better representative of the integral. However, the assumption that g 's slope is well behaved is consistent with g capturing a minimal amount of prior bias.

2. Justification and Choice of Surrogates: The technique of using surrogates in detection was proposed in [9]. Observe that once θ_N^* is chosen by the above method, the important characteristic of g to be modeled is which θ_M 's g associates with θ_N^* . $F[]$ is constructed to summarize our prior beliefs; the technique assumes that we can approximate sufficiently well the expected N, M relationship by means of one or more simple surrogate M models that are functions of the N model.

Note that no claim is made that the surrogates models resemble the actual phenomena processes. Rather, the hope is that these simple surrogates will abstract some significant characteristics that *differentiate* the normal and phenomena processes. The following example, based on a computer security application [9], illustrates the role of surrogates in detection.

Example 6.1: Suppose that transaction templates consist of the attributes *user* and *command*, with respective value sets {Fred, Sue} and {execute, edit}. Suppose further that the training sample *DB* consists of 100 transactions, yielding observed frequencies of the four possible transactions as shown below.

	execute	edit
Fred	4	90
Sue	2	4

Since the raw frequency counts are sufficiently large, we do not eliminate attributes and compute, for example, $\theta_N^*(\langle \text{Fred}, \text{execute} \rangle) = .0400$ and $\theta_N^*(\langle \text{Sue}, \text{execute} \rangle) = .0200$.

When the uniform model θ_{M_U} is used for the misuse surrogate, we obtain for any $x \in S$ $\theta_{M_U}(x) = .250$, and hence $pd_U(\langle \text{Fred}, \text{execute} \rangle) = 6.25$ and $pd_U(\langle \text{Sue}, \text{execute} \rangle) = 12.5$. Therefore, under the uniform misuse surrogate, $\langle \text{Sue}, \text{execute} \rangle$ is deemed to be the most suspect transaction simply because it is the least frequent in the sample, a result consistent with anomaly detection applications.

The independence surrogate θ_{M_I} assigns to each transaction $x = \langle A_1 = v_1, \dots, A_i = v_i, \dots, A_n = v_n \rangle$ $\theta_{M_I}(x) = \prod_{i=1}^n \theta_N^*(v_i)$, where $\theta_N^*(v_i) = \sum_{x: x[A_i] = v_i} \theta_N^*(x)$. Hence, in our example,

$$\theta_{M_I}(\langle \text{Fred}, \text{execute} \rangle) = (.940) * (.0600) = .0564$$

$$\theta_{M_I}(\langle \text{Sue}, \text{execute} \rangle) = (.0600) * (.0600) = .00360$$

$$pd_I(\langle \text{Fred}, \text{execute} \rangle) = 1.41; \quad pd_I(\langle \text{Sue}, \text{execute} \rangle) = 0.180$$

Therefore, under the independence surrogate, $\langle \text{Fred}, \text{execute} \rangle$ is deemed the most suspicious transaction because Fred is doing something *relatively unusual, for him*. $\square$

The k -ordered detectors introduced below provide a simple framework in which the results of competing surrogates can be resolved. When performance feedback is available, the application of adaptive learning techniques for weighting and combining surrogates appears to be a promising approach. Section 6.3 presents limited test results indicating that simple surrogates perform relatively well compared to the optimal detector, which is based on perfect knowledge of the underlying processes.

Heuristic for Finding Dominant $\Theta_{m_{A_i}}$

When multiple $\Theta_{m_{A_i}}$ have nonzero mass, minimization (exact or heuristic) of the individual integrals of rsk' may imply different rankings for an x, y pair (e.g., uniform surrogate and $count(DB, x[A]) > count(DB, y[A])$ but $count(DB, y[B]) > count(DB, x[B])$), and hence determining the optimal ranking of any pair x, y would require assessing the overall effect of the x, y ranking on the entire risk expression, rather than simply determining the ranking of each x, y pair indicated by a single integral. Further, even if it were feasible to determine the optimal ranking of each x, y pair, the collection of pairwise optimal rankings need not be consistent (see Example 3.1) and, as Theorem 4.4 demonstrates, the optimal ranking problem is NP-hard.

Two general forms of heuristics thus present themselves:

1. Search the space of rankings of S (i.e., permutations of S), approximating the risk incurred by each. Only a small fraction of this space can be considered explicitly and it appears quite difficult to approximate the risk of a candidate ranking. Further, pruning rules that would support an effective implicit enumeration of the space are not evident.
2. Approximate the optimal ranking of each x,y pair in such a manner that the resultant collection of pairwise rankings is guaranteed to be consistent. We focus here on this class of heuristic.

Consider the following outline of an approach, ignoring for the moment the issue of whether the resulting collection of pairwise orders is consistent. We attempt to rank each x,y correctly (as determined by the method described above) relative to the single Θ_{mA_i} for which ranking this x,y pair correctly has the most significant positive impact on the pair's contribution to risk. Hence, rather than trying to balance ranking effects across Θ_{mA_i} , we look for the dominant Θ_{mA_i} with respect to x,y . Such an assessment ideally would account for both the magnitude, at a θ^* representative of Θ_{mA_i} 's integrand, of the difference $\theta_M^*(x) * \theta_N^*(y) - \theta_M^*(y) * \theta_N^*(x)$ (which represents how important is the x,y ordering were Θ_{mA_i} to contain the operative θ) weighted by $Pr\{DB|\theta^*\} * g(\theta^*)$ (which represents how likely is Θ_{mA_i} given DB and g).

The above description of the ranking method ignores the issue that, if we were to choose arbitrary Θ_{mA_i} for each x,y pair, ranking each pair with respect to its Θ_{mA_i} as described above, the resultant collection of pairwise orders would not necessarily be consistent. One simple solution to this problem is to choose a single Θ_{mA_i} and use it to rank all pairs; the method described above when applied to a single Θ_{mA_i} for all pairs will result in a consistent collection of pairwise orders, since the transactions are ranked according to the real values $pd_i(x)$. Several techniques suggest themselves for selecting the single Θ_{mA_i} to employ; for example, choose a single Θ_{mA_i} based on the "average" importance over all x,y pairs in S^2 , or over a random collection of these pairs.

One drawback of the single Θ_{mA_i} solution is that for many pairs x,y , it may be the case that x,y is being ranked with respect to a Θ_{mA_i} for which there is little benefit to risk in ranking x,y correctly. That is, the contribution of this integral to rsk' is little or not affected by how the x,y pair is ranked. In particular, $Pr\{M|x;DB,\Theta_{mA_i}\}$ and $Pr\{M|y;DB,\Theta_{mA_i}\}$ may be so close that the alternative orderings of x and y incur essentially the same loss when Θ_{mA_i} is operational. (This would be the case, for example, when the projected A_i counts in DB are similar and g favors M models which are near uniform.)

In response to this observation, we propose a more sophisticated pairwise ranking method. This method selects a collection $\{\Theta_{mA_1}, \dots, \Theta_{mA_k}\}$ of minimal hypotheses, links each with one or more surrogate maps $F[]$, and adopts a rule for deciding on which $(\Theta_{mA_i}, F[])$ the ranking of each x,y pair should be based. The rule is such that (a) a consistent collection of orders is ensured; (b) the resulting ranking algorithm can be expressed as a Class 1 detector mapping $S \rightarrow \mathbb{R}$; and (c) the on-line analysis component is fast.

A Class of k -Ordered Ranking Functions

We consider first a general class of ranking functions and demonstrate that its members each induces a consistent ordering on the function's domain. We then identify as a subclass of this general class of ranking functions a promising class of detectors.

Definition 6.2: Let $T=(f_1, \dots, f_i, \dots, f_k)$ be a k -tuple of functions, $f_i:S \rightarrow \mathbb{R}$. For each i , let $EQUIV(i,u,v)$ be an equivalence relation on $S \times S$ such that

- (a) $f_i(u)=f_i(v) \Rightarrow EQUIV(i,u,v)$.

(b) $[\neg \text{EQUIV}(i, v, w) \text{ and } \text{EQUIV}(i, u, w) \text{ and } f_i(v) < f_i(w)] \Rightarrow f_i(v) < f_i(u)$.
 (Observe that the left hand side of (b) implies $\neg \text{EQUIV}(i, u, v)$, since equivalence relation $\text{EQUIV}(i, \cdot, \cdot)$ is transitive.) $<_T$ defined by the following rule is called a k -ordered ranking function on S . Each $u, v \in S$ is ordered as $u <_T v$ iff for the smallest i such that $\neg \text{EQUIV}(i, u, v)$, $f_i(u) < f_i(v)$; if there is no such i , $u =_T v$.

Theorem 6.2: Every k -ordered ranking function $<_T$ defines a consistent order on S . That is, for any $u, v, w \in S$, $u <_T v$ and $v <_T w$ implies $u <_T w$, with $u =_T w$ if and only if $u =_T v$ and $v =_T w$.

Proof: Consider any triple $u, v, w \in S$. If each of the 3 pairs are ranked $=_T$, the result is established. Otherwise, let i be smallest integer such that $\neg \text{EQUIV}(i, \cdot, \cdot)$ for at least one of these pairs. Without loss of generality, suppose $\neg \text{EQUIV}(i, u, v)$. It then follows that i also is the first integer such that $\neg \text{EQUIV}(i, \cdot, \cdot)$ for at least one of the other two pairs, since $\text{EQUIV}(i, u, w)$ and $\text{EQUIV}(i, v, w)$ implies $\text{EQUIV}(i, u, v)$.

If $\text{EQUIV}(i, u, w)$, $\text{EQUIV}(i, v, w)$, and $\text{EQUIV}(i, u, v)$, the result is established, since in this case the same $f_i: S \rightarrow \mathbb{R}$ determines the three rankings. Otherwise, without loss of generality, suppose, in addition to $\neg \text{EQUIV}(i, u, v)$, we have not $\neg \text{EQUIV}(i, v, w)$ and $\text{EQUIV}(i, u, w)$. Then, condition (b) on f_i and EQUIV implies that under f_i , and hence $<_T$, v is either less than both of u and w or greater than both of u and w . Hence, regardless of whether $u <_T w$, $w <_T u$, or $u =_T w$, the ordering of u, v, w is consistent. $\square$

Many reasonable detectors from the class of k -ordered ranking functions can be considered; we consider here one such family of detectors, motivated by the the previous analyses. These detectors are specified by:

1. A k -tuple $(A_1, \dots, A_k)$ of (not necessarily distinct) attribute sets.
2. A k -tuple $PD = (pd_1, \dots, pd_k)$ of functions corresponding to the sets A_i . $pd_i(x) = F_i[\theta_{mA_i, N}^*(x)] / \theta_{mA_i, N}^*(x)$, where $\theta_{mA_i, N}^*$ and surrogate map F_i are as described earlier. By allowing each pd_i to utilize its own surrogate map F_i , we can capture different linkages by g of N to M for different sets A_i of relevant attributes. Further, by allowing A_i to repeat in the k -tuple, any A_i may be associated with multiple F_i (reflecting competing linkages), with our prioritization of the k -tuple resolving the competing evidence that results.
3. For each $1 \leq i \leq k$, a partitioning of the real line so that $\text{EQUIV}(i, u, v)$ ($1 \leq i \leq k$) iff $pd_i(u)$ and $pd_i(v)$ fall into the same interval of this partition.
4. The order $<_{PD}$ is determined on u, v as follows.
 - i. Attempt to find the first i such that $\neg \text{EQUIV}(i, u, v)$. If such an i is found, $<_{PD}$ orders by the values $pd_i(u)$ and $pd_i(v)$.
 - ii. If no such i is found, attempt to find the first j such that $pd_j(u) \neq pd_j(v)$. If such a j is found, $<_{PD}$ orders by these values.
 - iii. If $pd_j(u) = pd_j(v)$ for all j , order as $u =_{PD} v$.

Hence, we attempt to rank u, v based on the first pd_i such that $pd_i(u)$ and $pd_i(v)$ fall into distinct intervals. This is a heuristic for ranking u, v based on the first pd_i whose values are "far enough" apart to be significant; notice that a simple threshold on the distance $|pd_i(u) - pd_i(v)|$ would not necessarily lead to a transitive relation.

Note that in order to capture this $<_{PD}$ formally as a k -ordered ranking function, we use the tuple $(A_1, \dots, A_k, A_{k+1}, \dots, A_{2k})$ of attribute sets, where $A_{k+i} = A_i$, $1 \leq i \leq k$. For $1 \leq i \leq k$ define $\text{EQUIV}(i, u, v)$ as above; for $k+1 \leq j \leq 2k$ define $\text{EQUIV}(j, u, v)$ as equality on pd_{j-k} . (Hence, each A_i appears in the tuple $2 \cdot s_i$ times, where s_i is the number of surrogate maps F associated with A_i .)

While such a $<_{PD}$ is not itself an explicit mapping of a transaction to $\mathbb{R}$, it is conceptually simple to implement such a $<_{PD}$ so as to have the effect of a Class 1 detector. As each new x of the rank stream is encountered, $<_{PD}$'s ranking rule is employed to place x in its correct position relative to the already encountered members of the rank stream. Theorem 6.2 ensures that this can be done consistently, and whatever is the ultimate contents of the rank stream RS , the ranking obtained by this implementation is a restriction to RS of the (single) permutation of S defined by $<_{PD}$. More theoretically, $<_{PD}$ can be converted to a pd mapping S to $\mathbb{R}$ such that pd induces on S the same ordering as does $<_{PD}$. This can be accomplished, for example, by either: (i) Using $<_{PD}$ to order all of S and then defining $pd(x) = x$'s position in this ordering, or (ii) Summing transformed pd'_i values, where the pd'_i values are obtained by scaling and shifting the pd_i values so that pd'_i dominates the

ranking of x and y exactly when $EQUIV(j, x, y)$ for all $j < i$ and $\neg EQUIV(i, x, y)$.

Example 6.2: The experiments reported in the next section consider the k -ordered detector defined by the tuple (U, A) of attribute sets and a single surrogate map F , where U is the set of all attributes and attribute set $A \subset U$ is selected by our search heuristics. We define $pd_1(x) = F[\theta_{U,N}^*(x)]/\theta_{U,N}^*(x)$, $pd_2(x) = F[\theta_{A,N}^*(x)]/\theta_{A,N}^*(x)$, and $EQUIV(i, \cdot, \cdot)$ ($i=1,2$) so that each point on the real line is its own interval. Hence, pd_2 is used to rank x, y if and only if $F[\theta_{U,N}^*(x)]/\theta_{U,N}^*(x) = F[\theta_{U,N}^*(y)]/\theta_{U,N}^*(y)$. $\square$

6.3 Preliminary Results of an Experimental System

An operational detection system based on the methodology described in the previous sections includes the following components:

Surrogate basis: A collection of simple phenomena model surrogates, available for use by the on-line detectors, as well as by the attribute subset evaluation measures.

Detector instantiation module: The detector is constructed off-line, before the rank stream is encountered. The off-line instantiation module takes as input the training sample DB along with a characterization of the prior distribution g on Θ , producing the actual k -ordered detector used in the application. Specifically, the instantiation consists of choosing (1) the k -tuple $(A_1, \dots, A_k)$ of attribute subsets; (2) the surrogate maps F_i ; and (3) the equivalence relations $EQUIV(i, \dots)$, each of which partitions the real line into intervals.

Support of this approach requires (a) fast evaluation measures for predicting relatively how valuable an attribute subset A_i is to include as a member of a yet to be specified k -tuple; (b) effective search strategies for choosing the candidate A_i to evaluate, i.e., for exploring the search space; and (c) algorithms for forming the k -ordered detector by assembling and prioritizing the selected subsets and associating them with surrogate maps.

On-line detection module: The on-line module for a Class 1 detector applies to each transaction x encountered the detector produced by the instantiation module to determine x 's relative prioritization.

We have implemented a software system embodying these components. Ongoing experimentation with the system is assessing such factors as: choice of surrogate models; choice of evaluation measures and search algorithms; choice of the $EQUIV$ relations; and the sensitivity of these results to actual normal and phenomena process pairs. Detailed results will be reported in a forthcoming paper; here, we briefly illustrate the methodology and provide an indication of its potential effectiveness.

The two simple experiments reported here have three (essentially) orthogonal goals.

1. Demonstrate the effectiveness of various evaluation measures in identifying attribute subsets on which density estimation for the normal process can be based. To this end, Experiment 1 factors out the *unknown phenomena model* problem dimension by fixing the M model to uniform. Since $(\theta_N, \theta_{M,U}) \in \Theta_{AD}$ for all θ_N , these results indicate the effectiveness of the methodology for *anomaly detection*.
2. Demonstrate the effectiveness of simple surrogate models. Experiment 2 introduces the *unknown phenomena model* problem dimension. In particular, a phenomena process is obtained from the normal process by reversing a relationship that exist between attributes. We then assess how well simple, generic surrogates (constructed in advance, without knowledge of either the normal or phenomena process pair being simulated) differentiate the two processes.
3. Indicate the effectiveness of the proposed family of k -ordered detectors. To this end, both experiments utilize two simple members of the family:
 - i. A 1-dimensional detector, (pd), utilizing a single selected subset A and surrogate map $F[\cdot]$. Hence, the same $pd(x) = F[\theta_{A,N}^*(x)]/\theta_{A,N}^*(x)$ is used to rank all transaction pairs when a 1-dimensional

detector is employed.

ii. The 2-dimensional detector of Example 6.2.

We note that *choice of search algorithms* is not one of the dimensions studied here. In particular, we generate sufficiently small problem instances so that an exhaustive search can be used, i.e., the evaluation measures are invoked on all attribute subsets and the subset ranked best by each evaluation measure is selected. Also, as indicated above in the third goal, we consider only simple detection k -tuples and hence *tuple construction* is not an issue, i.e., the simple k -tuples under study are completely specified once the attribute subset and surrogate map are selected.

Following is a description of the two experiments. For each, we fix the process pair (N,M) simulated, and report the observed prioritization error[†], averaged over 100 rank streams of 100 transactions each, of the 1-dimensional and 2-dimensional detectors described above, constructed using a variety of subset evaluation measures and surrogate maps. The results of the experiments are benchmarked by comparison of these observed prioritization errors to those for the optimal detector pd_r (which, recall, can be computed given perfect knowledge of the fixed process pair) and the naive detector, which uses the full attribute set U combined with the uniform surrogate, i.e., $naive(x) = 1/count(DB, x)$.

Experiment 1: Assess feature selection in the context of anomaly detection.

Transaction Space: 5 attributes, each with domain $D=\{1,...,10\}$.

Training Sample DB : Size = 1,000 transactions.

True N Process: The attributes are pairwise independent. The marginal probability distributions are:

For $i=1,2$

$$Pr\{A_i=v\}=0.1111, \text{ for } v=1,2,3$$

$$Pr\{A_i=v\}=0.1667, \text{ for } v=4,5$$

$$Pr\{A_i=v\}=0.0667, \text{ for } v=6,7,8,9,10$$

For $i=3,4,5$

$$Pr\{A_i=v\}=0.1000, v \in D, \text{ i.e., these } A_i \text{ are uniformly distributed on } D.$$

True M Process: The attributes are pairwise independent, with each marginal distribution uniform on D .

Surrogate Maps: All evaluation measures, and all detectors, employ the uniform surrogate exclusively, i.e., $F_U[\cdot]$ is the constant function mapping to θ_{M_U} . (This is appropriate since Experiment 1 assumes we are addressing an anomaly detection application.)

Subset Evaluation Measures:

M_1 : $\theta_M^*(x) * \theta_N^*(y)$ separation: This evaluator, based on Section 6.2's analysis of expression rsk' , attempts to measure the importance of candidate subset A_i based on the separation of this product, summed over all x,y pairs whose A_i -classes appear in DB . In particular, θ_N^* is the maximal likelihood distribution estimate for DB within $\Theta_{m_{A_i}}$ (as identified in Theorem 6.1), and, for this instantiation of the measure, $\theta_M^* = F_U[\theta_{m_{A_i,N}}] = \theta_{M_U}$. The measure's value on candidate subset A_i then is

$$M_1(A_i) = \sum_{(x,y) \models [x]_{A_i} \text{ and } [y]_{A_i} \text{ in } DB} | \theta_{M_U}(x) * \theta_N^*(y) - \theta_{M_U}(y) * \theta_N^*(x) |.$$

The larger this sum relative to that of other A_i , the more significance we attach to A_i .

M_2 : This measure is identical to M_1 , except that, for efficiency reasons, the sum may be taken over a random collection of x,y pairs, rather than over all pairs. For this experiment, a limit of 1,000 is placed on the number of pairs considered. If, for candidate A_i , the number of pairs of A_i -classes (appearing in DB) is greater than 1,000, the sum is taken over a random sample of 1,000 pairs; otherwise, the measure is computed on A_i exactly as described for M_1 . In the case that a sample is used, the total measure value is scaled up so as to extrapolate a sum over all pairs.

M_3 : $\theta_M^*(x) * \theta_N^*(y)$ separation, weighted by $Pr\{DB|\theta_N^*\}$. While measures M_1 and M_2 are based on the importance of correct x,y orderings were the operative θ contained in $\Theta_{m_{A_i}}$, these measures ignore the

[†]In the computation of observed prioritization error, an error of 1 is incurred by each transaction pair ranked $x < y$ when x is generated by M and y is generated by N ; an error of 0.5 is incurred by each pair ranked $x = y$ when x and y are generated by different processes.

factor $Pr\{DB|\theta_N^*\} * g(\theta^*)$ of the expression rsk' . Recall that this factor represents how likely is Θ_{MA_i} given DB and prior distribution g . Measure M_3 , for simplicity, continues to ignore the $g(\theta^*)$ factor, and computes

$$M_3(A_i) = Pr\{DB|\theta_N^*\} * M_1(A_i),$$

where, as in M_1 , θ_N^* is the maximal likelihood distribution estimate for DB within Θ_{MA_i} . Since for this experiment we have chosen here to ignore the g factor, another means is required to capture our cardinality bias, else the term $Pr\{DB|\theta_N^*\}$, which favors large sets, will dominate the measure and U always will evaluate best. Here, we simply force the selection of a cardinality 2 subset; in practice, the cardinality bias for a given application would be handled by a more sophisticated weighting scheme (or by more sophisticated k -ordered detectors).

M_4 : This measure approximates M_3 by sampling, just as M_2 approximates M_1 .

Results of Experiment 1: In Figures 1 and 2, the 31 nonempty subsets of $\{A_1, \dots, A_5\}$ are numbered as:

$S_0 = \{A_1, A_2, A_3, A_4, A_5\}$, $S_1 = \{A_2, A_3, A_4, A_5\}$, $S_2 = \{A_1, A_3, A_4, A_5\}$, $S_3 = \{A_1, A_2, A_4, A_5\}$, $S_4 = \{A_1, A_2, A_3, A_5\}$, $S_5 = \{A_1, A_2, A_3, A_4\}$, $S_6 = \{A_3, A_4, A_5\}$, $S_7 = \{A_2, A_4, A_5\}$, $S_8 = \{A_2, A_3, A_5\}$, $S_9 = \{A_2, A_3, A_4\}$, $S_{10} = \{A_1, A_4, A_5\}$, $S_{11} = \{A_1, A_3, A_5\}$, $S_{12} = \{A_1, A_3, A_4\}$, $S_{13} = \{A_1, A_2, A_5\}$, $S_{14} = \{A_1, A_2, A_4\}$, $S_{15} = \{A_1, A_2, A_3\}$, $S_{16} = \{A_4, A_5\}$, $S_{17} = \{A_3, A_5\}$, $S_{18} = \{A_3, A_4\}$, $S_{19} = \{A_2, A_5\}$, $S_{20} = \{A_2, A_4\}$, $S_{21} = \{A_2, A_3\}$, $S_{22} = \{A_1, A_5\}$, $S_{23} = \{A_1, A_4\}$, $S_{24} = \{A_1, A_3\}$, $S_{25} = \{A_1, A_2\}$, $S_{26} = \{A_5\}$, $S_{27} = \{A_4\}$, $S_{28} = \{A_3\}$, $S_{29} = \{A_2\}$, $S_{30} = \{A_1\}$.

Figure 1 shows the scores assigned by measures M_1 and M_2 to each of the 31 nonempty subsets. Of note are that (i) Subset $S_{25} = \{A_1, A_2\}$ is the clear preference of each measure, and (ii) The sampling performed in the computation of M_2 provides an excellent approximation of M_1 . Figure 2 shows the natural logarithm of the scores assigned by measures M_3 and M_4 to each of the 10 cardinality 2 subsets of $\{A_1, \dots, A_5\}$. Of note are that (i) The introduction of the term $Pr\{DB|\theta_N^*\}$ increases greatly the advantage of subset S_{25} over the other cardinality 2 subsets (recall that Figure 2 displays the natural logarithms of scores), and (ii) The sampling performed in the computation of M_4 results in an error beneath the resolution of the graph's logarithmic scale.

Figure 3 shows the average prioritization errors incurred by 8 detectors:

The naive detector.

The 1-dimensional detector based on S_{25} and uniform surrogate.

The 2-dimensional detector based on S_{25} and uniform surrogate.

The 1-dimensional detector based on $S_{19} = \{A_2, A_5\}$, the subset evaluated second best by the measures, and uniform surrogate.

The 2-dimensional detector based on S_{19} and uniform surrogate.

The 1-dimensional detector based on $S_{29} = \{A_2\}$ and uniform surrogate. This is the second best performing 1-dimensional detector based on uniform surrogate.

The 2-dimensional detector based on S_{29} and uniform surrogate. This is the second best performing 2-dimensional detector based on uniform surrogate.

The optimal detector pd_r .

Of note are that: (i) Detectors based on S_{25} performed substantially better than the naive detector, somewhat better than the next best performing detectors that could have been built, and only slightly worse than the theoretically optimal detector. This is interpreted as verifying that density estimation is enhanced greatly by the elimination of irrelevant attributes, and that the measures did a good job of identifying the most appropriate set of attributes to use; (ii) Detectors based on S_{19} performed relatively well, and subset S_{29} was evaluated relatively highly, further indicating a relationship between measure preference and performance; and (iii) The performances of the 1- and 2-dimensional detectors were indistinguishable on this experiment.

Experiment 2: Crossover relationship, assess the effectiveness of simple, generic surrogates.

Transaction Space: 5 attributes, each with domain $D = \{1, \dots, 10\}$.

Training Sample DB : Size = 1,000 transactions.

True N Process: Attributes A_1, A_3, A_4, A_5 are pairwise independent, with each marginal distribution uniform on D . Attribute A_2 is correlated as follows with attribute A_1 . If the value assumed by A_1 is odd [even], A_2 assumes the maximum [minimum] of 3 random variables, each uniformly distributed over D .

True M Process: Identical to the true N process, except that the sense of the correlation between A_1 and A_2

is reversed. That is, if the value assumed by A_1 is odd [even], A_2 assumes the minimum [maximum] of 3 random variables, each uniformly distributed over D .

Surrogate Maps: Evaluation measures and detectors are formed from each of the uniform surrogate map $F_U[]$ and the independence surrogate map $F_I[\theta_N] = \theta_{M_i}$, where, as described in Example 6.1, $\theta_{M_i}(x)$ is the product of the marginal probabilities for the attribute values of x , as specified by θ_N .

Subset Evaluation Measures:

M_1, M_2, M_3 , and M_4 : As in Experiment 1.

M_5 : Like M_1 , except that the independence surrogate map $F_I[]$ replaces the uniform surrogate map.

M_6 : Like M_2 , except that the independence surrogate map $F_I[]$ replaces the uniform surrogate map.

M_7 : Like M_3 , except that the independence surrogate map $F_I[]$ replaces the uniform surrogate map.

M_8 : Like M_4 , except that the independence surrogate map $F_I[]$ replaces the uniform surrogate map.

Results of Experiment 2: In Figures 4 - 6, the 31 nonempty subsets of $\{A_1, \dots, A_5\}$ are numbered as in Figures 1 and 2. Figure 4 shows the scores assigned by measures M_1 and M_2 to each of the 31 nonempty subsets of $\{A_1, \dots, A_5\}$. Figure 5[†] shows the scores assigned by measures M_5 and M_6 . Of note are that (i) Subset $S_{25} = \{A_1, A_2\}$ again is the clear preference of each measure; (ii) The sampling performed in the computation of M_2 and M_6 provides an excellent approximation of M_1 and M_5 ; and (iii) The uniform and independence surrogates resulted in essentially the same relative evaluation of the subsets. Figure 6 shows the natural logarithm of the scores assigned by measures M_3, M_4, M_7 , and M_8 to each of the 10 cardinality 2 subsets of $\{A_1, \dots, A_5\}$. Of note are (i) That the introduction of the term $Pr\{DB|\theta_N^*\}$ increases greatly the advantage of S_{25} relative to the other cardinality 2 subsets, and (ii) The sampling performed in the computation of M_4 and M_8 results in an error beneath the resolution of the scores' logarithmic scale.

Figure 7 shows the average prioritization errors incurred by 10 detectors:

The naive detector.

The 1-dimensional detector based on S_{25} and uniform surrogate.

The 2-dimensional detector based on S_{25} and uniform surrogate.

The 1-dimensional detector based on S_{25} and independence surrogate.

The 2-dimensional detector based on S_{25} and independence surrogate.

The 1-dimensional detector based on $S_{13} = \{A_1, A_2, A_5\}$ and uniform surrogate. This is the second best performing 1-dimensional detector based on uniform surrogate.

The 2-dimensional detector based on $S_{13} = \{A_1, A_2, A_5\}$ and uniform surrogate. This is the second best performing 2-dimensional detector based on uniform surrogate.

The 1-dimensional detector based on $S_{13} = \{A_1, A_2, A_5\}$ and independence surrogate. This is the second best performing 1-dimensional detector based on independence surrogate.

The 2-dimensional detector based on $S_{13} = \{A_1, A_2, A_5\}$ and independence surrogate. This is the second best performing 2-dimensional detector based on independence surrogate.

The optimal detector pd_r .

The conclusions drawn from this experiment are consistent with those drawn from Experiment 1; in Experiment 2, the performance of the detectors based on the preferred subset S_{25} is even closer to that of the theoretically optimal detector, and significantly better than that of the next best performing detectors that could have been built. We speculate that the independence surrogate did not improve performance in this experiment because the relationship between attributes A_1 and A_2 in the normal model was so strong that transactions violating the relationship are rare. Hence, those transactions most likely generated by M were least likely generated by N .

7. Conclusions

We have defined the information prioritization problem and considered two classes of phenomena detectors. We have demonstrated that the two classes have rather different theoretical properties, including that optimal detection by one class is consistent with optimal classification, while such is not the case for the other class. The

[†]The difference in scale between scores on measures M_1 and M_2 and measures M_3 and M_4 is explained by the fact that M_1 and M_2 use the constant value 1.0 in the numerator, rather than an actual (constant) probability (e.g., $1/|S|$). This simplification has no effect on the comparison of the scores assigned by these measures to the various subsets, but makes meaningless comparison with M_3 and M_4 scores.

computational complexity of optimal detection diverges for the two classes as well. In particular, optimal detection by algorithms in one class is shown to be solvable in polynomial time (assuming a finite prior distribution), while optimal detection by the other class is NP-hard.

We presented heuristics for optimally solving restricted versions of the detection problem, including symmetric anomaly detection. We considered also heuristic approaches to more general problem versions. Preliminary results of an experimental software system appear to indicate that the approach holds promise. Future work will analyze more extensively the performance of the system, and will develop and implement more sophisticated detection heuristics.

ACKNOWLEDGEMENT: The author wishes to thank Jessie Bhangoo for obtaining the experimental results presented in Section 6. Mr. Bhangoo also suggested the phrase *phenomena detector*. The author is grateful also to Henry Shapiro for his help in debugging a preliminary version of the reduction used in the proof of Theorem 4.2.

References

1. Angluin, D. and Smith, C., "Inductive inference: Theory and methods," *ACM Computing Surveys*, vol. 15, no. 3, pp. 237-269, 1983.
2. Baim, P. W., "A method for attribute selection in inductive learning systems," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 10, No. 6, pp. 888-896, 1988.
3. Blumer, A., Ehrenfeucht, A., Haussler, D, and Warmuth, M., "Learnability and the Vapnik-Chervonenkis dimension," *J. ACM*, vol 36, no. 4, pp. 929-965, 1989.
4. Doak, J., "An evaluation of feature selection methods and their application to computer security," University of California at Davis, Technical Report CSE-92-18, 1992.
5. Duda, R. and Hart, P., *Pattern Classification and Scene Analysis*, John Wiley and Sons, New York, 1973.
6. Garey, M. and Johnson, D., *Computers and Intractability*, W. H. Freeman, San Fransisco, 1979.
7. Gonzalez, R.C. and Thomason, M.G., *Syntactic Pattern Recognition, an Introduction*, Addison-Wesley, Reading, Mass., 1978.
8. Haussler, D., "Learning conjunctive concepts in structured domains," *Machine Learning*, vol. 4, no. 1, 1989.
9. Helman, P. and Liepins, G., "Statistical foundations of audit trail analysis for the detection of computer misuse," *IEEE Trans. on Software Engineering*, vol. 19, no. 9, pp. 886-901, 1993.
10. Littlestone, N., "Learning quickly when irrelevant attributes abound: A new linear-threshold algorithm," *Machine Learning*, vol. 2, no. 2, pp. 285-318, 1988.
11. Tou, J.T. and Gonzalez, R.C., *Pattern Recognition Principles*, Addison-Wesley, Reading, Mass., 1974.
12. Valiant, L., "A theory of the learnable," *Comm. ACM*, vol. 27, no. 11, pp. 1134-1142, 1984.
13. Watanabe, S., *Pattern Recognition: Human and Mechanical*, John Wiley and Sons, New York, 1985.

Predictive Scores for Subsets (Experiment 1)

Figure 2

Figure 4

Experiment 1: Prioritization Errors

Figure 6.