Economic Recovery of Oil Trapped at Fan Margins Using High Angle Wells and Multiple Hydraulic Fractures

**Quarterly Report
January 1 - March 31, 1998**

**By:
Mike L. Laue**

Work Performed Under Contract No.: DE-FC22-95BC14940

For
U.S. Department of Energy
Office of Fossil Energy
Federal Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880

By
Atlantic Richfield Company
P. O. Box 147
Bakersfield, California 93302

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**TITLE: ECONOMIC RECOVERY OF OIL TRAPPED AT FAN MARGINS USING
HIGH ANGLE WELLS AND MULTIPLE HYDRAULIC FRACTURES**

Cooperative Agreement No.: DE-FC22-95BC14940--12

Contractor Name and Address: Atlantic Richfield Co., P.O. Box 147,
Bakersfield, California 93302

Date of Report: May 29, 1998

Award Date: September 28, 1995

Anticipated Completion Date: September 28, 2001

Government Award for
Current Fiscal Year: \$3,926,267

Principal Investigator: Mike L. Laue, ARCO

Project Manager: Dan Ferguson, NPTO

Reporting Period: Jan. 1-Mar. 31, 1998

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Objective

This project attempts to demonstrate the effectiveness of exploiting thin-layered, low-energy deposits at the distal margin of a prograding turbidite complex through the use of hydraulically fractured horizontal or high-angle wells. The combination of a horizontal or high-angle well and hydraulic fracturing will allow greater pay exposure than can be achieved with conventional vertical wells while maintaining vertical communication between thin interbedded layers and the wellbore.

A high-angle well will be drilled in the fan-margin portion of a slope-basin clastic reservoir and will be completed with multiple hydraulic-fracture treatments. Geologic modeling, reservoir characterization, and fine-grid reservoir simulation will be used to select the well location and orientation. Design parameters for the hydraulic-fracture treatments will be determined, in part, by fracturing an existing test well. Fracture azimuth will be predicted by passive seismic monitoring of a fracture-stimulation treatment in the test well using logging tools in an offset well.

Summary of Technical Progress

The remaining pay intervals in Yowlumne Unit B 91X-3 were perforated during the fourth quarter of 1997. The well was allowed to produce and cleanup during the first quarter of 1998 while future stimulation options were evaluated.

Completion Operations

Production Performance

The remaining pay intervals in Yowlumne Unit B 91X-3 (behind the 7 in. liner) were perforated in November 1997. Figure 1 shows the location of all perforated intervals relative to the major Stevens sand layers. The well has been allowed to produce and clean up since then while future stimulation options are being evaluated.

Prior to perforating the remaining pay intervals, the well was producing 160 BOPD and 80 BWPD. Initial production following the wellwork was 220 BOPD and 20 BWPD. The well has now stabilized at approximately 150 BOPD and 150 BWPD (Fig. 2).

Inflow performance relationship (IPR) curves were established by layer (Fig. 3). The 240 BPD total liquid rate for Sand C represents the initial production rate from the lower perforations. Adding perforations in Sands A and B were expected to add 170 BPD, however, the actual increase was only 80 BPD.

Future Plans

The new perforations will be stimulated to improve production similar to an earlier stimulation of the lower perforations. A non-acid reactive fluid consisting of a blend of KCl water, iron chelating agents, mutual solvents, surfactants, and nitrogen was pumped through coiled tubing into the lower perforations. This treatment of the original completion interval successfully increased production from a trace of oil and 40 BWPD to 220 BOPD and 20 BWPD.

Following stimulation of the upper perforations, the well will be produced for a period of time to clean up and observe production trends and pressure behavior. Based on these results, a hydraulic fracture treatment may be considered for these perforations.

Technology Transfer

Dr. M.S. Clark published the following paper: *Characterization and Exploitation of the Distal Margin of a Layered, Low-Permeability Turbidite Reservoir, Yowlumne field, San Joaquin Basin, California*, Houston Geological Society Bulletin, v. 40, pp. 12-15, December 1997.

A workshop is being planned for August 1998 in Bakersfield, CA to review the project to date with industry and other interested parties.

Dr. M.S. Clark will be presenting a paper titled *Reservoir Characterization of a Fan-Shaped Turbidite Complex in an Active-Margin Basin, Miocene Stevens Sandstone, Yowlumne Field, San Joaquin Basin, California* at the EAGE/AAPG Third Research Symposium on DEVELOPING AND MANAGING TURBIDITE RESERVOIRS: CASE HISTORIES AND EXPERIENCES in Almeria, Spain on October 4-9, 1998.

Figure 1. Actual well path relative to major Yowlumne sand intervals. Also shown are existing perforated intervals.

Figure 2. Well tests before and after perforating Sands A and B.

Figure 3. Vogel IPR curve for Sand C and expected IPR curves for Sands A and B.