~~SECRET~~

UNCLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

~~MASTER~~ UNCLASSIFIED

AUG 8 1948

Distributed:

Prepared by: J. L. Richmond

Date: June 1-30, 1948

GROUP 1
Excluded from automatic
downgrading and
declassification

THIS DOCUMENT CONTAINS RESTRICTED DATA WITHIN THE MEANING
OF THE ATOMIC ENERGY ACT OF 1946 AND INFORMATION AFFECTING
THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE
MEANING OF THE ESPIONAGE ACT 50 U.S.C. 31 AND 32. ANY
TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY
MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED AND MAY
RESULT IN SEVERE CRIMINAL PENALTIES.

NEUTRON SOURCE PROGRAM REPORT

Excluded from automatic
downgrading and
declassification

SPECIAL REVIEW FINAL DETERMINATION	
Classification:	<i>Unclassified</i>
Category:	
Signature:	<i>P.O. Dwyer</i>
Date:	<i>3/17/80</i>

M. M. Harting
Laboratory Director

DAYTON, OHIO

MONSANTO CHEMICAL COMPANY - UNIT III

Contract Number AT-33-1-GEN-53

MM-M-111-4866-0025

NIM-139

DATE *1/29/80* INITIALS *J.S.*

UNCLASSIFIED
THIS DOCUMENT CONSISTS OF 14 PAGES
THIS IS COPY 11 OF 120

~~SECRET~~

UNCLASSIFIED

~~UNCLASSIFIED~~

MLM-139

~~SECRET~~

DISTRIBUTION

1. - Unit III
2. - Unit IV
3. - Site Y
4. - Site Y
5. - Area Manager
6. - Area Manager
7. - Area Manager
8. - Author
9. - Central Files
10. - Central Files
11. - Central Files
12. - Central Files

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

UNCLASSIFIED

~~UNCLASSIFIED~~

~~SECRET~~

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

~~SECRET~~

~~UNCLASSIFIED~~

MIM-139

UNCLASSIFIED

NEUTRON SOURCE GROUP

L. Bentz, J. Birden, R. Hertz, J. Richmond, W. Schrantz,
and R. Watrous

ABSTRACT

In the Future Plans Section is given a review of the status of neutron source production and an outline of the work anticipated for the next six months.

I. Postum-Beryllium Neutron Source

In the electrochemical deposition of postum or beryllium powder postum is deposited rapidly for ten to twenty minutes; it then partially redissolves, and redeposits at a slower rate. Experiments with beryllium foil and a beryllium sphere show the same phenomenon and indicate that this is caused by oxidation of the beryllium or postum. Plans are under way for exclusion of oxygen to test this conclusion.

In order to better understand variations in amounts of postum deposited and in efficiencies of finished sources, the surface areas of several powders have been measured by adsorption of water vapor. For beryllium the area of 230-325 mesh was four times that of 120-240 mesh, while floatings had over twice the area of 230-325 mesh. Calculation shows that nearly eight times as much postum has been deposited on 230-325 mesh beryllium as could be deposited in a monomolecular layer. If this is true, a certain amount of treeing probably occurs, and consequently self-absorption of the alphas.

II. Postum-Boron and Postum-Fluoborate Neutron Sources

Two methods have been investigated for determining the end-point of evaporations during preparation of neutron sources. Passing the effluent vapors over indicating Drierite shows a change in color until evaporation is completed. A more satisfactory method is collection of the effluent acid vapors in distilled water and following the decrease in resistance by means of an ohmmeter.

Tests have been made which show that sodium fluoborate does not decompose at the temperature required for volatilization of postum chloride. A vacuum system has been constructed for the preparation and volatilization of postum chloride.

UNCLASSIFIED

~~UNCLASSIFIED~~

~~SECRET~~

~~SECRET~~

UNCLASSIFIED

~~UNCLASSIFIED~~

MIM-139

III. Postum-Lithium and Postum-Sodium Neutron Sources

A check of lithium fluoborate neutron sources which were decreasing in efficiency indicated that they were slowly taking up moisture, though they were in closed containers (not vacuum tight). Since lithium fluoborate is extremely hygroscopic, it is possible that the sources were not completely dried, and this will be determined.

The low efficiency of postum-lithium sources prepared in a lithium-ammonia complex may be due to incomplete evaporation of ammonia and tests are in progress.

Postum-sodium neutron sources with measured efficiencies of 144 and 88 per cent were prepared by melting sodium and postum together.

DETAILED REPORT

I. Postum-Beryllium Neutron Source

A. Source Preparation

In scrubbing postum on beryllium from dilute nitric acid there is a rapid rate of deposition for a short time. Then some postum is redissolved, after which scrubbing is resumed at a slower rate. It is desirable to eliminate this anomaly so that reproducible sources can be made.

A beryllium foil and sphere, each of 6 sq. cm. area have been used to scrub postum from dilute nitric acid. The above mentioned anomaly was more noticeable when beryllium powder was used. Because of increased chances for oxidation with the foil and sphere, it is felt that oxidation of postum or beryllium is responsible for the difficulty. Consequently, a dry box is being prepared so that a carbon dioxide atmosphere can be used. It is planned to use two spheres freed of oxide in order to check results and to compare with an oxidized sphere.

A possible method of getting postum in the source container for the volatilization method is by electrolytic deposition. Apparatus is being assembled to determine the amount of postum that can be deposited in a given size source container with a minimum of contamination.

B. Surface Area Measurement

Because of its probable value in the investigation of factors affecting the efficiency of neutron sources, a measurement of the specific surface areas of the various powdered target materials was

~~UNCLASSIFIED~~

UNCLASSIFIED

~~SECRET~~

~~SECRET~~~~UNCLASSIFIED~~
~~SECRET~~MIM-139 ~~SECRET~~

made. The method adopted was that of Smith and Greene (Ind. & Engr. Chem., Anal. Ed. 14, 382 (1942)), by which the adsorption of water vapor, at room temperature and pressure, on the powder was measured. Assuming adsorption to occur in a single layer of molecules, the surface area could be calculated on the basis of the known size of the water molecule and the number of molecules adsorbed.

The apparatus consisted of two 125 ml. flasks interconnected through a sensitive manometer in such a manner that the pressure difference between them could be measured. (See Figure 1). The sample, weighed and dried in a vacuum at 200°C. for eighteen hours, was sealed in a thin glass bulb and placed in one of the flasks, after which water vapor was introduced into the system. After the manometer was read, the sample bulb was broken by shaking; and a final reading of the manometer was made. From the known volume of the flask and the pressure change due to adsorption of water vapor, the number of molecules adsorbed was calculated. Using an adsorbed cross sectional area of the water molecule of 10 Å² (obtained from the literature), the surface area of the powder was calculated. For use with powders which were likely to combine at a rapid rate chemically with water, carbon tetrachloride was used. Dibutyl phthalate was used in the manometer because of its low vapor pressure.

Results obtained are given in Table I. In each case the result given is the average of approximately six individual determinations. For each series of determinations the average deviations from the mean were approximately ten per cent. This was not considered excessive since the error normally expected in reading the manometer would cause deviations up to ten per cent. The accuracy of the method could also be improved by placing the apparatus in a constant temperature bath.

The results are what might be expected from the microscopic examination of the particles. In a comparison of the above data with that on various sources made by the electrochemical deposition of postum on beryllium the cross sectional area of the postum atom was calculated as follows:

$$\text{Area} = \left(\frac{M}{ND} \right)^{2/3}$$

When M equals the atomic weight of postum, N equals Avogadro's number, and D equals the density of postum. The value for the cross sectional area of postum was found to be 11.8 Å² or 11.8 x 10⁻¹⁶ cm². The number of postum atoms per case is

$$\frac{224 \times 10^{-6} \times 6.02 \times 10^{23}}{210} \quad \text{or} \quad 6.42 \times 10^{17} \text{ atoms.}$$

~~UNCLASSIFIED~~~~SECRET~~

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

— FIGURE 1 —
SURFACE AREA APPARATUS

~~SECRET~~

~~SECRET~~

~~UNCLASSIFIED~~

~~SECRET~~

Table 1

SURFACE AREA

Powder	Mesh Size	Approximate Particle Size Range by Microscope Microns	Theoretical Surface Area Based on Cubes of Aver. Mesh Size cm ² /gm.	Surface Area H ₂ O V Adsor cm ² /g
Beryllium	230-325	40-70	630	2433
Beryllium	120-140		260	687
Beryllium. Washings from 230-325 Mesh		10-60		5944
Boron	230-325	40-70	506	651
Boron	120-140		210	343
NaF		2-50		1982
Beryllium Powder Etched 3 hrs. with 1.5 N HNO ₃	230-325			1682
Beryllium Powder Etched 3 hrs. with 3 N HNO ₃	230-325			1638

UNCLASSIFIED

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

UNCLASSIFIED

~~UNCLASSIFIED~~

MM-139

~~SECRET~~

The area required for the adsorption of one case of postum would be $6.42 \times 10^{17} \times 11.8 \times 10^{-16}$ or 758 cm^2 . This would indicate that a maximum of 3.2 cases could be scrubbed on a gram of 230-325 mesh beryllium powder in a monomolecular layer. In actual practice 18.45 cases per gram has been scrubbed on 230-325 mesh beryllium powder with a neutron efficiency of 93.4 per cent and 25.8 cases per gram with a neutron efficiency of 72 per cent. Postum deposited in layers up to eight atoms in thickness, or there was a great increase in surface area of the beryllium powder during scrubbing caused by an etching action of the 3 N nitric acid in which the postum is dissolved.

In view of the above, a new series of surface areas measurements were made on powders previously etched with acid. Beryllium powder 230-325 mesh, was etched for three hours with 1.5 N and 3 N nitric acid. The powder was then rinsed, dried, and the surface area determined as in previous experiments. The surface area of the powder etched with 1.5 N nitric acid was $1682 \text{ cm}^2/\text{gm.}$, while for powder etched with 3 N nitric acid, it was $1638 \text{ cm}^2/\text{gm.}$ per gram. This can be compared to $2433 \text{ cm}^2/\text{gm.}$ for powder not etched.

The reduction rather than expected increase in surface area by etching was believed due to the total solution of fine particles as well as the protective effect of bubble formation in fissures and re-entrant angles so that action took place primarily on projecting angles. From microscopic examination, it was apparent that this type of action had occurred.

II. Postum-Fluoborate and Postum-Boron Neutron Sources

A. Volatilization

For the last year the method of preparing fluoborate and boron has been evaporation of the liquid from an acid solution of postum, leaving the postum deposited on the target material. The evaporation method gave highly efficient sources but proved hard to adapt to remote control and to a closed system.

Recently several beryllium neutron sources have been made using a thermal volatilization method. Postum is introduced into the final source container, either covered by porous nickel or enclosed in a quartz tube after which beryllium powder is added. The entire container is sealed with nickel from nickel carbonyl.

The potential source is then changed into a neutron source by heating with an induction heater to around a thousand degrees centigrade in a vacuum system. This method did not give as high efficiencies as the former beryllium method, but it did decrease

~~UNCLASSIFIED~~

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

~~UNCLASSIFIED~~

UNCLASSIFIED

MLM-139

remarkably the chances of both neutron bombardment and alpha contamination. Several improvements have been foreseen in getting higher efficiencies for this method.

Since the thermal volatilization method offered so many advantages to making beryllium neutron sources, it was felt that through a few modifications in the method it could be adapted to the production of fluoborate and boron neutron sources.

Fluoborate salts decompose at high temperature, and therefore, the use of metallic postum was prohibited. A search of project literature brought out the fact that postum chloride made by passing carbon tetrachloride fumes over postum metal would vaporize around 165°C. to 185°C. Several tests of sodium fluoborate at 200°C. showed no decomposition took place which would make postum chloride the ideal postum salt for our volatilization work.

With this in mind, a vacuum system has been under construction and is rapidly nearing completion. The vacuum system will be used to prepare postum chloride and the neutron sources. The postum chloride will be introduced into the source container in a quartz tube or by vaporizing the chloride into the source container directly. In both cases the chloride will be sealed in and volatilized throughout the powder.

In order to obtain higher neutron efficiencies, finer powders will be used and the source container walls will be lined with target material so as to produce a uniform target.

B. Evaporation Methods

One of the problems of the evaporation process for making sources was the development of a remote control indicator for the end-point of the evaporation. Two methods have been developed: (1) a resistance measuring device and (2) a tube using indicating Drierite.

1. This device feeds the acid fumes into approximately 2 ml. of water which is in constant contact with two platinum wire electrodes. It is an improvement over the instrument referred to in the Neutron Source Progress Report, January 1-15, 1948. The latest instrument is of glass, thus more rugged. It eliminates the anti-splash plates and enables the tube to be heated so that almost all of the fumes reach the water containing electrodes, as condensation of the fumes in the lines is lessened.

In a number of trials an initial resistance of 200,000 to 500,000 ohms was reduced after evaporation to 15,000 to 20,000 ohms, with a break sharp enough for estimating the end-point.

UNCLASSIFIED

~~UNCLASSIFIED~~

~~SECRET~~

~~SECRET~~

~~UNCLASSIFIED~~

~~SECRET~~

UNCLASSIFIED

MLM-139

2. Another method which could be used in conjunction with or as a standby to the resistance measuring device was a length of 8 mm. glass tubing filled with indicating Drierite. A by-pass for the fumes was provided. It was found that .05 ml. of 1 N hydrochloric acid changed about eight inches of the Drierite. As in the first method, it was necessary for the fumes to be heated in their passage from the evaporation block to the indicating tube.

III. Postum-Lithium and Postum-Sodium Neutron Sources

A. Postum-Lithium Neutron Source

For some time the work on the element lithium has been devoted to finding various ways of preparing postum-lithium neutron sources. The problem in mind has been to find a method to prepare a source of greatest efficiency that can be duplicated with relative ease. The methods worked on have been melting postum with lithium and dissolving postum in a lithium ammonia complex. In each case a number of refinements have been developed to aid in the production of such sources.

The work first began by melting lithium (LB-25 - 0.214 c. 11/7/47) in a nickel cylinder, inserting a microfoil of activity and mixing by tapping the nickel cylinder. A top efficiency of 28 per cent was realized. A second source (LB-26 - 0.164 c. 11/14/47) prepared by this method had a top efficiency of 59 per cent. A third source (LB-27 - 0.337 c. 1/5/48), prepared by volatilizing postum onto the inside surface of a cold nickel cylinder, was 60 per cent efficient. Another source (LB-29 - 0.260 c. 2/5/48), prepared by volatilizing postum onto a cold lithium-coated nickel cylinder, had a peak efficiency of 64 per cent.

In dissolving postum in a lithium-ammonia complex, the sources prepared ranged in efficiency from 23-26 per cent. This is quite low and plans are being made to try to increase this efficiency by drying the sources in a heater after the liquid ammonia has been vaporized at atmospheric temperature.

Two postum-lithium fluoborate neutron sources have been prepared by evaporating the activity from 0.5 N hydrochloric acid onto the target material. LB-39 - 1.168 c. 5/28/48 had an overall efficiency of 62.0 per cent, while LB-40 - 0.256 c. 6/7/48 had an efficiency of 52.4 per cent. To date six postum-lithium fluoborate neutron sources have been prepared; all were counted at the time they were prepared. Later three sources were counted at the same time, and finally all were counted at the same time. Below is listed the sources, dates counted, and neutron efficiencies.

~~UNCLASSIFIED~~

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

UNCLASSIFIED
~~UNCLASSIFIED~~

MLM-13

~~SECRET~~

LB-32	LB-33	LB-35	LB-38	LB-39	LB-40
3/26 72.2%	3/31 63.3%	5/3 54.2%	5/19 56.9%	5/26 62.0%	5/28 52.4%
5/17 58.3%	5/17 54.9%	5/17 51.4%	6/18 50.0%	6/18 56.3%	6/18 50.5%
6/18 51.6%	6/18 48.8%	6/18 47.4%			

As can be seen in each case, the neutron efficiency dropped. At first it was thought that the drop was probably due to an error in the neutron count at the time the source was prepared. Later (6/18) when all the sources were counted again, the sources all dropped in efficiency. This drop could not be due to counter error since two previously prepared postum-lithium fluoride sources were used as checks on the counter. The efficiency of these sources checked previous values well within the probable error. Since lithium fluoborate is quite hygroscopic, absorption of moisture was probable. A preliminary test substantiated this, and further work will be done.

B. Postum-Sodium Neutron Source

Two postum-sodium neutron sources have been prepared, LB-41 - 0.207 c. 6/15/48 and LB-42 - 0.194 c. 6/23/48, with efficiencies of 144.3 and 88.1 per cent respectively. The sources were prepared by melting sodium in a brass cylinder and then inserting an active microfoil into the molten sodium. The sodium and postum were heated above the melting point of postum and mixed on a mechanical vibrator several times. Work is in progress to determine the cause of the above high efficiencies.

FUTURE PLANS

Neutron source production has as its goal the preparation of sources emitting neutrons in any numbers up to 10^9 per second, making them with energy spectra from thermal range to several m.e.v. placing them in the smallest container in which maximum efficiency can be obtained and standardizing procedures to such point that any given source can be reproduced, while observing tolerance limits of neutron exposure.

Neutron sources are, or can be, used at various sites on the project for studies in fundamental physics, biology, and medicine for calibration purposes, and as pile starters.

~~UNCLASSIFIED~~

~~SECRET~~

~~SECRET~~

UNCLASSIFIED

UNCLASSIFIED

~~SECRET~~

~~UNCLASSIFIED~~

MIM-139

The status of neutron source production is covered in Final Report No. 34 by W. J. Argersinger, Jr., and Information Report No. MIM-101 by J. L. Richmond. Supplemental Information Reports will be issued in the near future.

A research and development program was outlined in Information Report No. 29 by G. O. Gutekunst. A more specific outline for the next six months is given below. The total number of persons working on the various problems will be six. The number on a given problem will be listed in each Progress Report, as there is some interchange of personnel.

I. Postum-Beryllium Neutron Sources

A. Scrubbing

A method of preparing neutron sources by scrubbing postum on beryllium has been developed to the point that efficient sources can be prepared by semi-remote control. There still remains the problem of removing the source container from the scrubbing apparatus and sealing it by remote control. Some work will be done on this, but it is not anticipated that it will be completed in the next six months.

B. Volatilization

Several sources have been prepared by coating postum on platinum with a thin layer of nickel, placing it in a container with beryllium powder, sealing with nickel from decomposition of nickel carbonyl, and heating to about 1000°C. to distribute the postum. Control of thickness of nickel layers should be refined, impurities eliminated, and improvements made in operating techniques.

Replacing the nickel covered postum by directly volatilized or electrolytically deposited postum will be tried.

C. Purification

As mentioned elsewhere in this report, oxidation of beryllium and postum are interfering in the preparation of most efficient neutron sources. It is planned to eliminate oxides through reaction with substances such as chlorine and carbon tetrachloride, which form volatile compounds.

Beryllium contains numerous impurities which absorb alphas and reduce neutron yields. Its purification by distillation will be attempted.

~~UNCLASSIFIED~~
UNCLASSIFIED

~~SECRET~~
SECRET

~~SECRET~~

~~UNCLASSIFIED~~

~~SECRET~~

MIM-139

UNCLASSIFIED

D. Surface Area

Surface area is important in the determination of the optimum ratio of postum to beryllium. Experiments will be continued in which integral amounts of postum are deposited on a known surface area and the neutron efficiencies measured.

II. Postum-Boron and Postum-Fluoborate Neutron Sources

A. Evaporation

A method of preparing these sources by evaporating acid solutions of postum from the powders has been worked out. Addition of solution to the powder and sealing the container are only partially remotely controlled; the work will be continued to accomplish this.

B. Volatilization

The preparation of neutron sources by preparation of a volatile salt of postum as postum chloride, and volatilization of the salt onto the target will be studied.

III. Postum-Lithium and Postum-Sodium Neutron Sources

Neutron sources of these elements are of interest because the neutrons have lower energies than neutrons from beryllium and boron. The yields from them are low so that they may be used with greater safety to study general factors relating to neutron source preparation. Their great reactivity makes an inert atmosphere essential. Techniques in handling, conditions for evaporations, and methods of preparation can be worked out for lithium and sodium with reasonable assurance that they will be applicable to elements more easily handled. General problems will be continued using them.

IV. Immersion Alpha Counter

Counting of alphas by an immersion tube would enable one to follow the course of a reaction continuously and to quickly evaluate solutions with a minimum contamination.

Several commercial tubes are on the market but do not cover the range of one millicurie to one curie per milliliter that we wish to measure.

A tube of the Simpson proportional variety having an evacuated quartz tube with thin quartz windows at both ends has been constructed. It has to be properly shielded and minor changes made in its design before it can be completely successful. It is expected that adsorption of activity on the quartz windows will require some work.

UNCLASSIFIED

~~UNCLASSIFIED~~

~~SECRET~~

~~SECRET~~

~~SECRET~~

~~UNCLASSIFIED~~

UNCLASSIFIED

MIM-139

~~SECRET~~

V. Neutron and Gamma Counting

Neutron sources made by this group have been counted by the Physics Group, but will be done by the Neutron Source Group at Mound Laboratory. As this was not anticipated at the time space was assigned in the "T" Building, minor adjustments must be made to accomodate neutron counting.

Certain alpha-neutron reactions are accompanied by gamma emission. This may prove to be a more accurate measure of neutrons than direct counting.

The next six months will be required for assembling equipment and gaining experience in operating it.

JLR/rcc

~~THIS DOCUMENT CONTAINS RESTRICTED DATA WITHIN THE MEANING OF THE ATOMIC ENERGY ACT OF 1946 AND/OR INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE ACT 50 U.S.C. 31 AND 32, AS AMENDED. ITS TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED AND MAY RESULT IN SEVERE PENALTIES.~~

UNCLASSIFIED ~~UNCLASSIFIED~~

~~SECRET~~ ~~SECRET~~