M-AREA HAZARDOUS WASTE MANAGEMENT FACILITY GROUNDWATER MONITORING AND CORRECTIVE-ACTION REPORT (U)

FIRST QUARTER 1995

Volume I

Publication Date: May 1995

Authorized Derivative Classifier:

Joseph P. Kunglitz

UNCLASSIFIED

Does Not Contain Unclassified

Controlled Nuclear Information

Reviewing Official:

Joseph P. Kunglitz, Senior Engineer
(Name and Title)

Date:

5/24/95

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

M-AREA HAZARDOUS WASTE MANAGEMENT FACILITY GROUNDWATER MONITORING AND CORRECTIVE-ACTION REPORT (U)

FIRST QUARTER 1995

Volume I

Publication Date: May 1995

Authorized Derivative Classifier:

UNCLASSIFIED
Does Not Contain Unclassified
Controlled Nuclear Information

Reviewing Official:

(Name and Title)

Date:

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

M-AREA HAZARDOUS WASTE MANAGEMENT FACILITY GROUNDWATER MONITORING AND CORRECTIVE-ACTION REPORT (U)

FIRST QUARTER 1995

Publication Date: May 1995

Key Words

**Air stripper
Appendix IX constituents
DNAPL
Tetrachloroethylene
Trichloroethylene**

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED WV

MASTER

Prepared for the U.S. Department of Energy under Control Contract No. DE-AC09-89SR18035

THIS PAGE LEFT BLANK INTENTIONALLY.

Contents

Volume I	Page
List of Figures	v
List of Tables	vi
Summary	1
Introduction	5
Description of Facilities	5
Compliance Monitoring Program	5
Corrective-Action Monitoring Program	6
Sampling and Results	8
Groundwater Sampling	8
Compliance Monitoring Results	9
Corrective-Action Monitoring Results	10
Hydrogeologic Assessment	12
Groundwater Flow Directions and Rates	12
Recharge and Water-Elevation Changes	13
Water Quality Assessment	16
Horizontal Extent of Contamination	16
Inorganic Constituents	17
Time Series Plots and Effects of the Recovery System	17
Effectiveness of the Corrective-Action Program	18
Water Quality Changes	18
Rate of Removal	18
Corrective-Action System Operation and Performance	19
Air Stripper Performance	19
Vadose Zone Unit Performance	20
Recovery Well System	20
Vapor Extraction Well System	20
Air Stripper Modifications	21
Vadose Zone Unit Modifications	21
Monitoring and Corrective-Action Program Assessment	22
New Findings	22
Ongoing Programs	22
Proposed Monitoring and Corrective-Action Program Modifications	28
Groundwater Monitoring Program	28
Corrective-Action Program	28

References Cited	29
Errata and Revisions	31
Appendix A—Standards	A-1
Appendix B—Flagging Criteria	B-1
Appendix C—Figures	C-1
Appendix D—Monitoring Results Tables	D-1
Appendix E—Data Quality/Usability Assessment	E-1

Volume II

Appendix F—Time Series Plots	F-1
Modifications to Appendix F	F-3
Appendix G—Hydrographs	G-1
Appendix H—CUSUM Data	H-1

Volume III

Appendix I—Water Elevation and Isoconcentration Contour Maps	I-1
---	------------

List of Figures

	Page
Figure 1. Location of the M-Area HWMF at the Savannah River Site	C-3
Figure 2. Location of the M-Area HWMF within A/M Areas and Location of the Point-of-Compliance Wells at the M-Area HWMF	C-4
Figure 3. Location of the Plume Definition and Background Wells at the M-Area HWMF	C-5
Figure 4. Location of the Recovery Wells at the M-Area HWMF	C-6
Figure 5. Water-Elevation Differences, M-Area Aquifer Zone, First Quarter 1985 to First Quarter 1995	C-7
Figure 6. Water-Elevation Differences, Upper Lost Lake Aquifer Zone, First Quarter 1985 to First Quarter 1995	C-8
Figure 7. Water-Elevation Differences, Lower Lost Lake Aquifer Zone, First Quarter 1985 to First Quarter 1995	C-9
Figure 8. Water-Elevation Differences, Middle Sand Aquifer Zone of the CBCU, First Quarter 1985 to First Quarter 1995	C-10
Figure 9. Average Monthly Influent Concentrations vs. Time for RWM 1	C-11
Figure 10. Average Monthly Influent Concentrations vs. Time for RWM 2	C-12
Figure 11. Average Monthly Influent Concentrations vs. Time for RWM 3	C-13
Figure 12. Average Monthly Influent Concentrations vs. Time for RWM 4	C-14
Figure 13. Average Monthly Influent Concentrations vs. Time for RWM 5	C-15
Figure 14. Average Monthly Influent Concentrations vs. Time for RWM 6	C-16
Figure 15. Average Monthly Influent Concentrations vs. Time for RWM 7	C-17
Figure 16. Average Monthly Influent Concentrations vs. Time for RWM 8	C-18
Figure 17. Average Monthly Influent Concentrations vs. Time for RWM 9	C-19
Figure 18. Average Monthly Influent Concentrations vs. Time for RWM 10	C-20
Figure 19. Average Monthly Influent Concentrations vs. Time for RWM 11	C-21

Figure 20.	Average Monthly Influent Concentrations vs. Time for RWM 12	C-22
Figure 21.	Average Monthly Influent Concentrations vs. Time for the M-1 Air Stripper	C-23
Figure 22.	Average Monthly Influent Concentrations vs. Time for the A-1 Air Stripper	C-24

List of Tables

	Page
Table 1.	Synchronous Water Elevations D-7
Table 2.	Groundwater Monitoring Results for Point-of-Compliance Wells D-16
Table 3.	Groundwater Monitoring Results for Background Wells D-57
Table 4.	Groundwater Monitoring Results for Plume Definition Wells D-63
Table 5.	Groundwater Monitoring Results for Recovery Wells D-403
Table 6.	Constituents Exceeding Standards or Background Concentrations in Point-of-Compliance Wells D-439
Table 7.	Maximum Results for Appendix IX Constituents Not Currently Used to Determine Compliance D-444
Table 8.	CUSUM Analysis of Trichloroethylene Concentrations in Selected Monitoring Wells D-445
Table 9.	CUSUM Analysis of Trichloroethylene Concentrations in Recovery Wells D-446
Table 10.	Summary of Water-Elevation Drawdowns in the M-Area Aquifer Zone D-447
Table 11.	Summary of Water-Elevation Drawdowns in the Upper Lost Lake Aquifer Zone D-451
Table 12.	Summary of Water-Elevation Drawdowns in the Lower Lost Lake Aquifer Zone D-453
Table 13.	Summary of Water-Elevation Drawdowns in the Middle Sand Aquifer Zone of the CBCU D-455

Table 14.	1994 Summary of Downtime for the M-1 Air Stripper, the A-1 Air Stripper, and the Integrated Demonstration Vadose Zone Unit	D-457
Table 15.	1994 Operating and Performance Summary of the M-1 Air Stripper	D-459
Table 16.	1985-1994 Operating and Performance Summary of the M-1 Air Stripper	D-461
Table 17.	1994 Operating and Performance Summary of the A-1 Air Stripper	D-462
Table 18.	1992-1994 Operating and Performance Summary of the A-1 Air Stripper	D-464
Table 19.	1994 Operating and Performance Summary of the Integrated Demonstration Vadose Zone Unit	D-465
Table 20.	1994 Summary of Volume Pumped and Average Flow from Individual Recovery Wells	D-466
Table 21.	1994 Summary of Tetrachloroethylene and Trichloroethylene Concentrations	D-470
Table 22.	Summary of Downtime for the M-1 Air Stripper, the A-1 Air Stripper, and the Integrated Demonstration Vadose Zone Unit	D-474
Table 23.	Summary of Monthly Operation and Performance of the M-1 Air Stripper	D-475
Table 24.	Summary of Monthly Operation and Performance of the A-1 Air Stripper	D-476
Table 25.	Volume Pumped and Average Flow from Individual Recovery Wells	D-477
Table 26.	Average Monthly Tetrachloroethylene and Trichloroethylene Concentrations in Individual Recovery Wells	D-478
Table 27.	Summary of Monthly Operation and Performance of the Integrated Demonstration Vadose Zone Unit	D-479
Table 28.	Horizontal Gradients and Flow Rates in the Five Aquifer Zones	D-480

THIS PAGE LEFT BLANK INTENTIONALLY.

Summary

This report describes the groundwater monitoring and corrective-action program at the M-Area Hazardous Waste Management Facility (HWMF) at the Savannah River Site (SRS) during fourth quarter 1994 and first quarter 1995. This program is required by South Carolina Hazardous Waste Permit SC1-890-008-989 and section 264.100(g) of the South Carolina Hazardous Waste Management Regulations. Program activities are summarized below.

- Beginning third quarter 1994, changes in sampling, analyses, and reporting, as outlined in the M-Area HWMF 1992 RCRA Part B permit renewal application (Revision 3, June 1994), were initiated. The quarterly reports will reflect these changes as follows: (1) first quarter reports will include monitoring results for first quarter and the previous quarter, corrective-action results for first quarter, and an annual summary from the previous calendar year of the corrective-action program; (2) second quarter reports will contain corrective-action results for second quarter; (3) third quarter reports will contain monitoring results for second and third quarters, corrective-action results for third quarter, an annual summary from the previous calendar year of the monitoring results, and Appendix IX analyses results; and (4) fourth quarter reports will include corrective-action results for fourth quarter and average annual groundwater flow rates.
- Thirty-eight of the 41 point-of-compliance (POC) wells were sampled for the Appendix IX constituents required by Permit SC1-890-008-989, drinking water parameters, and water quality parameters during first quarter 1995. None of the POC wells were sampled during fourth quarter 1994. 1,1-Dichloroethylene, lead, nickel, selenium, tetrachloroethylene, and trichloroethylene exceeded the Groundwater Protection Standard (GWPS) in one or more of the POC wells. Aluminum, chloride, gross alpha, nitrate-nitrite, nonvolatile beta, sodium, sulfate, total alpha-emitting radium, and total phosphates exceeded standard background concentrations or drinking water standards in one or more of the POC wells (see the *Compliance Monitoring Results* subsection and Tables 2 and 6, Appendix D, Volume I).
- Nitrate, sodium, tetrachloroethylene, and trichloroethylene exceeded standards most frequently in the POC wells. Nitrate was elevated in 26 wells, sodium was elevated in 24 wells, tetrachloroethylene was elevated in 30 wells, and trichloroethylene was elevated in 33 wells (see Table 6, Appendix D, Volume I). First quarter 1995 results were similar to third quarter 1994 results.
- During third quarter 1994, groundwater from POC wells MSB 8A, 8B, 8C, 64B, 64C, and 64D was analyzed for the full suite of Appendix IX constituents. Mercury, tin, and zinc, which are not currently listed in Appendix A of Permit SC1-890-008-989, exceeded their analytical method detection limits. These constituents were re-analyzed during first quarter 1995 to confirm the third quarter 1994 results and to determine if any should be included in Appendix A of the permit (see the *Compliance Monitoring Results* subsection and Table 7, Appendix D, Volume I). First quarter 1995 results exceeding detection limits for well MSB 58D, which could not be sampled third quarter 1994 due to mechanical problems, are also included in Table 7.
- Five of the plume definition wells scheduled for sampling fourth quarter 1994 could not be sampled; three were dry, and two had mechanical problems. Twenty-five of the plume

definition wells scheduled for sampling first quarter 1995 could not be sampled; eight were dry, 16 had mechanical problems, and one went dry before sampling began. Thirty-six sampling events (three per well) were scheduled each quarter for the recovery wells; eight sampling events did not occur during fourth quarter 1994 and 11 sampling events did not occur first quarter 1995 because the pumps were off (see the *Corrective-Action Monitoring Results* subsection and Tables 4 and 5, Appendix D, Volume I).

- Total alpha-emitting radium exceeded standards in background well MSB 29D during fourth quarter 1994 and first quarter 1995. No constituents exceeded standards in the remaining background wells during either quarter (see Table 3, Appendix D, Volume I).
- Aluminum, chloride, 1,1-dichloroethylene, gross alpha, lead, nickel, nitrate-nitrite, sodium, sulfate, tetrachloroethylene, total alpha-emitting radium, total phosphates, and trichloroethylene exceeded standards in one or more of the plume definition wells during fourth quarter 1994 and first quarter 1995. Barium also exceeded standards in one or more plume definition wells during fourth quarter 1994; and cadmium, mercury, and nonvolatile beta exceeded standards in one or more plume definition wells during first quarter 1995 (see the *Corrective-Action Monitoring Results* subsection and Table 4, Appendix D, Volume I).
- Aluminum, nickel, nitrate-nitrite, sodium, tetrachloroethylene, and trichloroethylene exceeded standards in one or more of the recovery wells during fourth quarter 1994, and mercury, nickel, tetrachloroethylene, and trichloroethylene exceeded standards in one or more recovery wells during first quarter 1995 (see Table 5, Appendix D, Volume I).
- Trichloroethylene concentrations in 40 monitoring wells exhibited the following long-term trends during first quarter 1995: 2 showed no trend, 26 showed an upward trend, and 12 showed a downward trend. Trichloroethylene concentrations in 11 recovery wells showed the following long-term trends: 6 recovery wells showed a downward trend, and 5 showed an upward trend. Twenty-three monitoring wells provided no data this quarter (see the *Water Quality Changes* subsection and Tables 8 and 9, Appendix D, Volume I).
- Compared to fourth quarter 1994, average water levels increased in the M-Area Aquifer Zone, Upper Lost Lake Aquifer Zone, and Middle Sand Aquifer Zone of the Crouch Branch Confining Unit during first quarter 1995. The average water level in the Lower Lost Lake Aquifer Zone remained the same. (see the *Recharge and Water-Elevation Changes* subsection).
- During 1994, the M-1 air stripper removed a total of 17,403 lbs of solvent from the groundwater beneath the M-Area HWMF. The M-1 operated a total of 8,334.6 hours with a downtime of 425.4 hours, resulting in a total utility of 95.2 percent. The emission rate was 2.09 lbs/hr. The average monthly influent of tetrachloroethylene was 3,690 $\mu\text{g/L}$ and of trichloroethylene was 5,880 $\mu\text{g/L}$. The average monthly effluent total was less than 2.5 $\mu\text{g/L}$ (see the *Air Stripper Performance* subsection and Tables 14–16, Appendix D, Volume I).
- During first quarter 1995, the M-1 air stripper removed a total of 2,925 lbs of solvent from the groundwater beneath the M-Area HWMF. The M-1 operated a total of 2,043.4 hours with a downtime of 116.6 hrs, resulting in a total utility of 94.6 percent. The emission rate was 1.40 lbs/hr. The quarterly throughput was 36,733,530 gal at an average water feed rate of 297 gallons per minute (gpm). The average quarterly influent of tetrachloroethylene was 3,469 $\mu\text{g/L}$ and of trichloroethylene was 5,693 $\mu\text{g/L}$. The average quarterly effluent total was less than 3.34 $\mu\text{g/L}$ (see the *Air Stripper Performance* subsection and Table 23, Appendix D, Volume I).

- During 1994, the A-1 air stripper removed a total of 534 lbs of solvent from the groundwater beneath the M-Area HWMF. The A-1 operated a total of 7,705.0 hours with a downtime of 1,055.0 hours, resulting in a total utility of 88.0 percent. The emission rate was 0.07 lbs/hr. The average monthly influent of tetrachloroethylene was less than 80 $\mu\text{g/L}$ and of trichloroethylene was less than 2,484 $\mu\text{g/L}$. The average quarterly effluent total was less than 2.0 $\mu\text{g/L}$ (see the *Air Stripper Performance* subsection and Tables 14, 17, and 18, Appendix D, Volume I).
- The A-1 air stripper removed a total of 110 lbs of solvent from the groundwater beneath the M-Area HWMF during first quarter 1995. The A-1 operated 1,567.0 hours with a downtime of 593.0 hours. The total utility was 70.8 percent. The quarterly throughput was 4,944,432 gal at an average water feed rate of 53 gallons per minute. The average quarterly influent of tetrachloroethylene was less than 165 $\mu\text{g/L}$. The average quarterly influent of trichloroethylene was 2,998 $\mu\text{g/L}$. The average quarterly effluent total was less than 3.34 $\mu\text{g/L}$ (see the *Air Stripper Performance* subsection and Table 24, Appendix D, Volume I).
- During 1994, the Integrated Demonstration Vadose Zone Unit removed a total of 2,102.8 lbs of degreaser solvent while operating at a utility of 43.8 percent and with an emission rate for the year of 0.66 lbs/hr hydrogen chloride vapor, 0.05 lbs/hr tetrachloroethylene, and 0.01 lbs/hr trichloroethylene. The average yearly influent of tetrachloroethylene was 89.4 parts per million volume (ppmv) and trichloroethylene was 55.2 ppmv. The average yearly effluent total was 8.8 ppmv (see the *Vadose Zone Unit Performance* subsection and Tables 14 and 19, Appendix D, Volume I).
- During the first quarter of 1995, the Integrated Demonstration Vadose Zone Unit (IDU) removed a total of 344.9 lbs of degreaser from the vadose zone beneath the M-Area HWMF. The IDU operated a total of 273.4 hrs with a downtime of 1,886.6 hrs, resulting in a total utility of 12.7 percent. The emission rate was 0.34 lbs/hr hydrogen chloride vapor, 0.02 lbs/hr tetrachloroethylene, and 0.003 lbs/hr trichloroethylene. The average inlet air feed rate was 69.3 cubic feet per minute. The average quarterly influent of tetrachloroethylene was 56.9 ppmv and of trichloroethylene was 27.1 ppmv. The average quarterly effluent total was 4.6 ppmv (see the *Vadose Zone Unit Performance* subsection and Tables 22 and 27, Appendix D, Volume I).
- Horizontal flow rate estimates in the five aquifer zones were as follows during first quarter 1995: M-Area Aquifer Zone, 120 to 440 ft/year; Upper Lost Lake Aquifer Zone, 240 to 370 ft/year; Lower Lost Lake Aquifer Zone, 240 ft/year; Middle Sand Aquifer Zone, 310 ft/year; and Crouch Branch Aquifer Zone, 260 ft/year (see the *Groundwater Flow Directions and Rates* subsection and Table 28, Appendix D, Volume I).
- Concentrations of volatile organics in plume definition well MSB 84A, installed in response to the elevated trichloroethylene concentrations at nearby well MSB 82A, could not be determined fourth quarter because analyses were not scheduled. The well was not sampled during first quarter 1995 because of maintenance problems. Well MSB 84A, which is located near the northern boundary of SRS, monitors a zone similar to the zone monitored by well MSB 82A. Soil samples collected during coring and installation activities at well MSB 84A during 1994 showed no evidence of volatile organic contaminants (see the *New Findings* subsection and Table 4, Appendix D, Volume I).
- The following portions of ongoing programs were completed: South Carolina Department of Health and Environmental Control (SCDHEC) held a comment and response period to the Part B permit renewal application; a final document updating the hydrostratigraphy of the A/M

Areas and the Metallurgical Laboratory HWMF was submitted to SCDHEC; the four soil vacuum extraction units are currently being tested; a final report was issued on the aquifer test on the new recovery wells in the northern sector; a Phase I final report on the investigation of the groundwater contaminant plume in the western sector of A/M Areas was submitted to SCDHEC; modifications to the M-Area HWMF drainage ditch were completed; and piezometer wells were installed near Phase V wells in the southern sector and a pump test was performed (see the *Ongoing Programs* subsection).

Introduction

Description of Facilities

The M-Area Hazardous Waste Management Facility (HWMF), located in the northwest portion of the Savannah River Site (SRS) (Figures 1 and 2, Appendix C, Volume I), consists of the M-Area Settling Basin; a seepage area, overflow ditch, and inlet process sewer line; and Lost Lake, a shallow upland depression.

The unlined settling basin operated from 1958 until 1985, receiving waste water that contained volatile organic solvents used for metal degreasing and chemical constituents and depleted uranium from fuel fabrication processes in M Area. The underground process sewer line transported M-Area process waste waters to the basin. Water periodically overflowed from the basin through the ditch to the seepage area adjacent to the ditch and to Lost Lake.

Because of the hazardous nature of the constituents released to the environment during operation of the basin, the M-Area HWMF is subject to the requirements of the Resource Conservation and Recovery Act (RCRA). The facility currently is operating under a RCRA Part B post-closure care permit application (WSRC, 1994). A brief history of the M-Area HWMF compliance and post-closure programs is located in the *Monitoring and Corrective-Action Program Assessment* section of this report.

Compliance Monitoring Program

Requirements and Standards

Point-of-compliance (POC) wells monitor groundwater quality at the M-Area HWMF (Figure 2, Appendix C) as mandated by RCRA and associated South Carolina regulations. The M-Area HWMF RCRA Part B post-closure care permit application (WSRC, 1994) specifies the following monitoring regimen:

- quarterly monitoring for synchronous water elevations
- quarterly monitoring of new wells for one year
- semiannual monitoring for pH, specific conductance, temperature, and Groundwater Protection Standard (GWPS) constituents (except polychlorinated biphenyls [PCBs]); only POC wells MSB 1D, 2D, 3D, 4D, 57D, 58D, 59D, and 60D are monitored for PCBs
- annual monitoring for gross alpha, nonvolatile beta, total alpha-emitting radium, and selected inorganic constituents
- monitoring during the third quarter of each year of 20 percent of the POC wells (MSB 3B, 8A, 8B, 8C, 58D, 64B, 64C, and 64D in 1994) for Appendix IX constituents (EPA, 1992)

Analytical results are compared to the GWPS as defined in Table E-20 of the current Part B permit application (WSRC, 1994), standard background concentrations as defined in the 1987 Part B

permit (WSRC, 1987), or drinking water standards (EPA, 1993a, 1993b) (see Appendix A). Standard background concentrations were determined during the assessment monitoring program, using groundwater samples from background wells MSB 29B, 29C, 29D, 43A, 43B, and 43D (WSRC, 1987, 1994). Results are also compared to flagging criteria established by the SRS Environmental Protection Department/Environmental Monitoring Section (EPD/EMS) (see Appendix B).

The SRS Environmental Restoration Department (ERD) reports the monitoring results to the South Carolina Department of Health and Environmental Control (SCDHEC) as required by South Carolina Hazardous Waste Permit SC1-890-008-989 (SCDHEC, 1987) and section 264.100(g) of the South Carolina Hazardous Waste Management Regulations (SCDHEC, 1992).

Point-of-Compliance Well Network

Currently, the M-Area HWMF POC well network is composed of 41 wells: MSB 1B, 1C, 1CC, 1D, 2B, 2C, 2D, 3B, 3C, 3D, 4B, 4C, 4D, 5A, 5B, 5C, 6A, 6B, 6C, 7A, 7B, 7C, 8A, 8B, 8C, 13A, 13CC, 13D, 57D, 58D, 59D, 60D, 62B, 62C, 62D, 63B, 63C, 63D, 64B, 64C, and 64D.

This network developed as follows:

- Wells MSB 1A, 2A, 3A, 4A, 5A, 6A, 7A, 8A, 13A, 13B, and 13C, installed in the early 1980s, were approved by SCDHEC as the original POC wells.
- Well MSB 22 was approved by SCDHEC for interim sampling to replace well MSB 3A.
- Sampling at wells MSB 1A, 2A, 3A, 4A, and 13C was stopped in 1990 due to declining water levels at the M-Area HWMF resulting from basin closure and the recovery system operation.
- Sampling of well MSB 22 as a POC well was stopped in 1991; this well currently is part of the plume definition well network.
- Wells MSB 1B, 1C, 1CC, 1D, 2B, 2C, 2D, 3B, 3C, 3D, 4B, 4C, 4D, 5B, 5C, 6B, 6C, 7B, 7C, 8B, 8C, 13CC, 13D, 57D, 58D, 59D, 60D, 62B, 62C, 62D, 63B, 63C, 63D, 64B, 64C, and 64D were installed in 1990 (MSB 1D, 2D, 3D, 4D, and 13D replaced wells MSB 1A, 2A, 3A, 4A, and 13C).
- Well MSB 13B was removed from the POC well network beginning third quarter 1994.

A record of well installations, replacements, and abandonments is found in the EPD/EMS well inventory (EPD/EMS, 1995). The aquifer zones monitored by the POC well network, described in WSRC 1994 and identified in this report in the *Key to Reading the Tables* section of Appendix D (Volume I), are defined according to Lewis and Aadland (1993).

Corrective-Action Monitoring Program

Requirements and Standards

Data from background, plume definition, and recovery wells (Figures 3 and 4, Appendix C, Volume I) are used to assess the effectiveness of the corrective-action program for the M-Area HWMF. Background and plume definition wells monitor the horizontal and vertical extent of groundwater contamination, groundwater flow rates and directions, groundwater quality, and changes in piezometric and potentiometric surfaces. Recovery wells pump contaminated

groundwater to air strippers, which remove volatile organic contaminants from the water before it is returned to the ground.

The M-Area HWMF RCRA Part B post-closure care permit application (WSRC, 1994) specifies the following monitoring regimen for these wells to meet RCRA requirements:

Background wells

- quarterly monitoring for synchronous water elevations
- quarterly monitoring of new wells for one year
- semiannual monitoring for pH, specific conductance, temperature, and GWPS constituents (except PCBs)
- annual monitoring for gross alpha, nonvolatile beta, and total alpha-emitting radium

Plume definition wells

- quarterly monitoring for synchronous water elevations
- quarterly monitoring of new wells for one year
- semiannual monitoring for pH, specific conductance, temperature, and GWPS constituents (except PCBs); only plume definition wells MSB 9B, 9C, 10C, and 31C are monitored semiannually for PCBs
- annual monitoring for gross alpha, nonvolatile beta, and total alpha-emitting radium
- annual monitoring of 53 plume definition wells for selected inorganic constituents

Recovery wells

- monthly monitoring for water elevations
- monthly monitoring for pH, specific conductance, temperature, and GWPS constituents (except PCBs); only recovery wells RWM 1, 6, and 10 are monitored for PCBs

Analytical results are compared to standards and reported to SCDHEC as described for the POC wells.

Corrective-Action Monitoring Well Network

The background, plume definition, and recovery well network currently consists of the following wells:

- Background wells: MSB 29B, 29C, 29D, 43A, 43B, and 43D
- Plume definition wells (352 total wells): 7 wells of the ABP series, 1 well of the ABW series, 6 wells of the AC series, 4 wells of the ACB series, 25 wells of the AMB series, 3 wells of the AOB series, 4 wells of the ARP series, 21 wells of the ASB series, 7 wells of the MCB series, 235 wells of the MSB series, and 39 wells of the SRW series
- Recovery wells: RWM 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13B, 13C, 14B, 14C, 15B, and 16

A record of well installations, replacements, and abandonments is found in the EPD/EMS well inventory (EPD/EMS, 1995). The aquifer zones monitored by the background, plume definition, and recovery well network, described in WSRC (1994) and identified in this report in the *Key to Reading the Tables* section of Appendix D (Volume I), are defined according to Lewis and Aadland (1993).

Sampling and Results

Groundwater Sampling

During first quarter 1995, synchronous water elevations (Table 1, Appendix D, Volume I) were measured on March 22 and March 23. Water elevations were not determined for some wells because low water content prevented water from rising in the standpipe where elevation measurements are taken. Wells MSB 3A, 10D, and 17C were dry when the synchronous measurements were taken. Wells MSB 3B, 23, 25, 45C, and 46B and SRW 8BB, 10, 14C, and 17D had no water in their standpipes.

The groundwater sampling procedure (WSRC, 1992) requires evacuation of a minimum of two well volumes and stabilization of pH, specific conductance, and turbidity prior to sample collection. Stability is established when a minimum of three successive measurements, taken within a given time period, are within a specified range.

If a well pumps dry before two well volumes are purged or before stabilization is achieved, it must be revisited within 24 hours for the data to be considered from a single sampling event. On the second visit within 24 hours, samples are taken without purging or stability measurements; thus, these samples may not be representative of the groundwater quality. Tables 2, 3, and 4 (Appendix D, Volume I) show the number of well volumes purged for each POC, background, and plume definition well, respectively.

At present, every POC and background well has a single-speed centrifugal downhole pump. Variable-speed pumps are installed in plume definition wells MCB 5C; MSB 32B, 32C, 87B, 87C, 88B, 88C, 88D, 89B, and 89C; and SRW 1, 17C, and 17D because these wells have histories of elevated metals. New plume definition wells AMB 14D, 15D, 16, 18C, and 19C also have variable-speed pumps. Samples from wells with variable-speed pumps are collected at a slower rate to minimize turbidity, which has been associated with elevated metal levels. Decreased aluminum and iron concentrations, as well as lower turbidity values, have been observed for samples from wells with variable-speed pumps. Samples from plume definition wells MSB 11E, 15C, 16C, 17C, 37D, 40D, 42D, 44C, 45C, and 46C are collected using an open-bucket bailer. The remaining plume definition wells have single-speed centrifugal downhole pumps. The recovery wells have pumps that run continuously. Pump types for POC, background, plume definition, and recovery wells are indicated in Tables 2, 3, 4, and 5 (Appendix D, Volume I), respectively.

Samples are collected by GE-HY Environmental Sampling of New Ellenton, South Carolina, and analyzed by General Engineering Laboratories of Charleston, South Carolina (South Carolina certification number 10120), and Roy F. Weston, Inc., of Lionville, Pennsylvania. Samples are treated as specified in the M-Area HWMF RCRA Part B permit renewal application (WSRC, 1994), and the Westinghouse Savannah River Company Quality Assurance Plan (WSRC, 1990).

Compliance Monitoring Results

Sampling Problems

Table 2 (Appendix D, Volume I) provides sampling codes (defined in the *Key to Reading the Tables* section of Appendix D, Volume I) that describe unusual sampling events for the POC wells. Unusual sampling events are summarized as follows:

Fourth Quarter 1994

- The wells had synchronous water elevations taken, and some were sampled for alpha spectroscopy uranium (uranium 233/234, 235, and 238). No unusual sampling events occurred during fourth quarter 1994.

First Quarter 1995

- Wells MSB 1C, 1CC, 1D, 2B, 2C, 2D, 4C, 5C, 6C, 7B, 7C, 13CC, 13D, 57D, 58D, 59D, 60D, 62D, and 63D went dry during purging and were sampled after the wells recovered (sampling code X).
- Wells MSB 3B, 3C, and 3D were not sampled because of maintenance or access problems (sampling code P).
- Well MSB 5A has no water elevation or volume purged because no water was in the standpipe.

No unusual sampling events occurred at the remaining POC wells.

Well MSB 3D contains dense nonaqueous phase liquid (DNAPL) with dissolved PCBs in sediments trapped in the well sump (memorandum SWE-ERG-93-0966, M. A. Ebra, SRS, to J. W. Cook and J. V. Odum, SRS, December 7, 1993). The ERD has recommended a notice to SCDHEC that regular quarterly sampling be stopped at the well and that it be used in characterization of DNAPL and assessment of remediation technologies.

Field and Analytical Results

Table 2 (Appendix D, Volume I) presents the field and analytical results for samples collected from POC wells for fourth quarter 1994 and first quarter 1995. The table identifies the constituents that exceeded the following standards: GWPS, standard background concentrations, or drinking water standards (Appendix A, Volume I), the SRS flagging criteria (Appendix B, Volume I), and the EPA-approved holding times. Well screen assignments follow the hydrostratigraphic nomenclature derived by Lewis and Aadland (1993) and are identified in the *Key to Reading the Tables* section of Appendix D (Volume I).

Table 6 (Appendix D, Volume I) summarizes the results that exceeded the GWPS, standard background concentrations, or drinking water standards in POC wells for first quarter 1995.

The *Key to Reading the Tables* section of Appendix D (Volume I) also defines abbreviations used in the data tables and provides discussions of holding times, data rounding, and data qualification. The latter includes a description of the result modifiers used in the data tables, which help define analytical accuracy and precision. Appendix E (Volume I) provides a general assessment of the quality and usability of the data.

Appendix IX Results

During the third quarter of each year, samples from 20 percent of the POC wells are analyzed for Appendix IX constituents (EPA, 1992). Constituents detected above method detection limits are re-analyzed in subsequent quarters and statistically compared to background concentrations to determine if they are true contaminants or artifacts of the analyses.

During first quarter 1995, POC wells MSB 8A, 8B, 8C, 58D, 64B, 64C, and 64D were analyzed for Appendix IX constituents. Analytes that exceeded method detection limits are reported in Table 7 (Appendix D, Volume I).

Corrective-Action Monitoring Results

Sampling Problems

Tables 3 and 4 (Appendix D, Volume I) provide sampling codes (see the *Key to Reading the Tables* section of Appendix D, Volume I) that describe unusual sampling events for the background and plume definition wells, respectively. Unusual sampling events are summarized in the following paragraphs:

Fourth Quarter 1994

- Wells MSB 12D and 17C; and SRW 17D were dry (sampling code *D*).
- Mechanical problems (sampling code *P*) prevented sampling of wells MSB 11E and 40D. Well RWM 9 was not sampled in October because the pump was off; wells RWM 8 and 9 were not sampled in November because the pumps were off; and wells RWM 1, 4, 8, 9, and 10 were not sampled in December because the pumps were off.
- Well MSB 15C went dry after field analyses and before all laboratory samples were collected (sampling code *I*).
- Wells AMB 4D, 6, 7, 10A, and 13AR; AOB 3; ASB 5AR and 6TA; MSB 9B, 14C, 18C, 36D, and 39A; and SRW 7 and 16A went dry during purging and were sampled within 24 hours (sampling code *X*).
- Wells SRW 8BB, 10, and 14C have no water elevations or volumes purged because they had no water in their standpipes.

First Quarter 1995

- Wells MSB 11E, 12D, 17C, 23, 25, 35D, and 45C; and SRW 17D were dry (sampling code *D*).
- Mechanical problems (sampling code *P*) prevented sampling of wells ARP 1A and 3; and MSB 10C, 12B, 22, 24A, 26B, 42A, 45A, 54C, 84A, 88B, 88C, 88D, 89B, and 89C. Wells RWM 1, 4, 8, 9, and 10 were not sampled during January because the pumps were off; wells RWM 6, 9, and 10 were not sampled during February because the pumps were off; and wells RWM 6, 8, and 9 were not sampled during March because the pumps were off. Wells AMB 14D, 15D, 16D, 17A, 18A, 18C, and 19C also received a sampling code of *P* in February; however, these wells were revisited and sampled in March but the data were unavailable for the draft copy of this report.

- Wells MSB 15C and 52D went dry after field analyses and before all laboratory samples were collected (sampling code I).
- Well ABP 8D went dry before sampling began; only depth to water was determined (sampling code L).
- Wells ABP 8C; AMB 4D, 6, 7, and 10A; AOB 3; ASB 5AR and 6TA; MCB 2, 4, 5C, 6, and 7C; MSB 9B, 14C, 15D, 18C, 20C, 23TR, 24, 30AA, 36D, 37A, 38D, 39A, 41D, 46A, 48D, 49D, 51D, 55HC, 61D, 65D, 69C, 70D, 71B, 74C, 74D, 75C, 77D, 79B, 82A, 83D, 85C, 85D, and 85TA; and SRW 7 and 16A went dry during purging and were sampled within 24 hours (sampling code X).
- Wells MSB 41D and SRW 8BB, 10, and 14C have no water elevations or volumes purged because no water was in their standpipes.

SRS has recommended a notice to SCDHEC that sampling at well MSB 22 be stopped because this well has residual DNAPL in sediments trapped in the well sump (memorandum SWE-ERG-93-0966, M. A. Ebra, SRS, to J. W. Cook and J. V. Odum, SRS, December 7, 1993). Although not confirmed, the DNAPL may contain dissolved PCBs.

No unusual sampling events occurred at the remaining background, plume definition, and recovery wells.

Thus, during fourth quarter 1994, all of the background wells and 134 of the 345 plume definition wells were sampled, and 28 of 36 sampling events scheduled for the recovery wells were completed. During first quarter 1995, all of the background wells and 315 of the 352 plume definition wells were sampled, and 25 of 36 sampling events scheduled for the recovery wells occurred.

Field and Analytical Results

Tables 3, 4, and 5 (Appendix D, Volume I) present the field and analytical results for samples collected from the background, plume definition, and recovery wells, respectively, for fourth quarter 1994 and first quarter 1995. Table 5 presents three sets of results for each recovery well because these wells are monitored monthly as required in the permit application (WSRC, 1994). Tables 3, 4, and 5 identify the constituents that exceeded the GWPS, standard background concentrations, or drinking water standards (see Appendix A, Volume I); the SRS flagging criteria (see Appendix B, Volume I); and the EPA-approved holding times. Well screen assignments use the hydrostratigraphic nomenclature derived by Lewis and Aadland (1993) and identified in the *Key to Reading the Tables* section of Appendix D (Volume I).

The *Key to Reading the Tables* section of Appendix D (Volume I) also defines abbreviations used in the data tables and provides discussions of holding times, data rounding, and data qualification. The latter includes a description of the result modifiers used in the data tables, which help define laboratory accuracy and precision. Appendix E (Volume I) provides a general assessment of the quality and usability of the SRS data.

Hydrogeologic Assessment

The hydrogeologic system in A/M Areas is evaluated using piezometric and potentiometric maps (Appendix I, Volume III) to determine groundwater flow rates and directions and water-elevation difference maps (Figures 4 through 7, Appendix C, Volume I), precipitation data, and hydrographs (Appendix G, Volume II) to determine the effects of the recovery well system.

The piezometric, potentiometric, and water-elevation maps for this report were constructed using synchronous water elevations taken during first quarter 1995 (Table 1, Appendix D, Volume I). Maps were constructed for each of the aquifer zones described in Figure E-11 of WSRC (1994). Aquifer zones are identified in this report in the *Key to Reading the Tables* section of Appendix D (Volume I). Map directions are oriented to true north.

Groundwater Flow Directions and Rates

Piezometric and Potentiometric Surfaces

- Horizontal gradients in the M-Area Aquifer Zone (Map 1, Appendix I, Volume III) are low and variable. The natural stratigraphy, variability in recharge, and the removal of water by wells RWM 3, 6, 9, 10, and 11 produce the mounds and depressions found on the piezometric surface. South of the M-Area HWMF, near the Miscellaneous Chemical Basin, a water-table divide appears to divert flow naturally to the southwest and southeast.
- Potentiometric contours for the Upper Lost Lake Aquifer Zone (Map 2, Appendix I, Volume III) indicate a semi-radial flow pattern, with the highest water elevations located north of A/M Areas, and flow away from this area to the southwest, south, and southeast. Near the M-Area HWMF and A-014 outfall, flow is directed to the south. A mound in the potentiometric surface at the M-Area HWMF may result from local recharge from the M-Area Aquifer Zone at this location, possibly enhanced by recovery system water-level drawdown to the north. Another mound in the potentiometric surface located north of the Metallurgical Laboratory Seepage Basin may be the result of pumping by recovery wells RWM 12 to the northeast and RWM 9 and 11 to the southwest.
- Flow beneath the Lower Lost Lake Aquifer Zone (Map 3, Appendix I, Volume III) is multi-directional, toward the east, southeast, and south. The most prominent feature is a north-south oriented trough beneath the M-Area HWMF. The potentiometric depression that occurs near the recovery wells surrounding the M-Area HWMF may result from the recovery well system.
- The south to southeast flow direction in the Middle Sand Aquifer Zone of the Crouch Branch Confining Unit (CBCU) (Map 4, Appendix I, Volume III) is similar to that of the Lower Lost Lake Aquifer Zone. The effects of pumping in the overlying Upper and Lower Lost Lake Aquifer Zones cause a slight depression beneath the M-Area HWMF.
- Flow in the Crouch Branch Aquifer Zone (Map 5, Appendix I, Volume III) is from the northeast to the southwest, apparently controlled by regional discharge to the Savannah River.

Horizontal Groundwater Flow Rates

Horizontal groundwater flow rates are calculated using the following equation:

$$\text{Flow (ft/day)} = \frac{\text{Hydraulic Conductivity (ft/day)}}{\text{Porosity (unitless)}} \times \frac{dh \text{ (ft)}}{dl \text{ (ft)}}$$

Hydraulic conductivity constants estimated for the M-Area Aquifer Zone, the Upper Lost Lake Aquifer Zone, the Lower Lost Lake Aquifer Zone, the Middle Sand Aquifer Zone of the CBCU, and the Crouch Branch Aquifer Zone are 27, 45, 45, 45, and 40 ft/day, respectively; the effective porosity value for each is 0.20 (Lewis and Aadland, 1992). The value dh is the difference in head, and dl is the length of the flow path shown on the map. The ratio dh/dl is the horizontal gradient. Gradient, flow rate per day, and flow rate per year were each determined to two significant digits in the calculations.

The estimated groundwater flow rates for first quarter 1995 (Table 28, Appendix D, Volume I) were as follows:

- M-Area Aquifer Zone: 120 to 440 ft/year
- Upper Lost Lake Aquifer Zone: 240 to 370 ft/year
- Lower Lost Lake Aquifer Zone: 240 ft/year
- Middle Sand Aquifer Zone of the CBCU: 310 ft/year
- Crouch Branch Aquifer Zone: 260 ft/year

These rates are within the same order of magnitude as the flow rates for third quarter 1994.

Recharge and Water-Elevation Changes

Precipitation measurements for the A/M Areas during fourth quarter 1994 and first quarter 1995 are provided below.

A/M Areas Precipitation Data for Fourth Quarter 1994 and First Quarter 1995

	Monthly Precipitation (in.)	Historical Average 1952–1994 (in.)
October	10.01	3.20
November	3.05	2.70
December	4.62	3.54
January	6.95	4.34
February	7.97	4.46
March	0.91	4.90
Six-month total	33.51	

Figures 4 through 7 (Appendix C, Volume I) show water-elevation drawdowns in the different aquifer zones caused by the operation of the recovery well system from first quarter 1985 to first quarter 1995. First quarter 1985 water elevations represent conditions prior to pumping by the recovery well system. First quarter 1995 water elevations represent conditions after ten years of recovery system operation. Data used to construct the maps are presented in Tables 10 through 13 (Appendix D, Volume I), and the results are described below:

- The water-elevation difference map for M-Area Aquifer Zone (Figure 4) shows the area of greatest decline bordered by recovery wells RWM 1, 2, 3, 4, 8, and 10. The maximum decline (-14.0 ft) during first quarter 1995 was less than the maximum decline during fourth quarter 1994.
- The areas of greatest decline in Upper Lost Lake Aquifer Zone (Figure 5) center around recovery wells RWM 2, 3, and 8. The maximum decline (-18.7 ft) during first quarter 1995 was greater than the maximum decline in fourth quarter 1994.
- The water-elevation decline for Lower Lost Lake Aquifer Zone (Figure 6) is greatest near recovery well RWM 10. Maximum decline (-15.4 ft) during first quarter 1995 was slightly less than the fourth quarter 1994 maximum decline for this unit.
- The location of the maximum decline in Middle Sand Aquifer Zone of the CBCU (Figure 7) is an area bordered by recovery wells RWM 2, 5, 6, 7, 8, and 10. The maximum decline (-12.0 ft) during first quarter 1995 was greater than the maximum decline during fourth quarter 1994.

The estimated water-elevation drawdown in each aquifer zone during first quarter 1995 is provided below.

Estimated Water-Elevation Drawdown Due to the Recovery Well System

Aquifer Zone	Maximum Water-Elevation Drawdown (ft)	Water-Elevation Drawdown Outside Zone of Capture ^a (ft)	Estimated Drawdown Due to Recovery System (ft)
M-Area	14.0	8.7 ^b	5.3
Upper Lost Lake	18.7	7.0 ^b	11.7
Lower Lost Lake	15.4	5.5 ^c	9.9
Middle Sand of the CBCU	12.0	6.9 ^b	5.1

^a Silverton Road Waste Site.

^b Observed at well cluster SRW 15.

^c Observed at well SRW 13A.

The above estimates were made by subtracting the water-elevation drawdown in each unit in wells outside the influence of the recovery well system (outside the zone of capture) from the maximum water-elevation drawdown in each unit in wells influenced by the recovery well system. The changes in water elevation outside the zone of capture were obtained from measurements from well cluster SRW 15 and well SRW 13A.

Compared to fourth quarter 1994, average water levels increased in each aquifer zone except Lower Lost Lake Aquifer Zone during first quarter 1995. The average water level in the Lower Lost Lake Aquifer Zone remained the same. These changes are shown below.

Change in Average Water-Elevation Drawdown^a (ft) from Previous Quarter

Aquifer Zone	4Q94	1Q95	Change
M-Area	9.1	8.6	0.5
Upper Lost Lake	10.0	9.9	0.1
Lower Lost Lake	8.6	8.6	0.0
Middle Sand of the CBCU	6.1	5.8	0.3

^a This drawdown has not been corrected for natural decline.

Hydrographs, showing water-elevation changes for selected M-Area HWMF monitoring wells over time, are provided in Appendix G (Volume II). Monitoring wells located near recovery wells generally reflect water-level decline caused by the recovery well system. Water elevations in monitoring wells away from the recovery wells system show variations related to rainfall, proximity to streams and other physical features, and other factors.

Water Quality Assessment

The current assessment of the extent of groundwater contamination is described in this section. Water quality data from plume definition and point-of-compliance monitoring wells were used to construct isoconcentration contour maps. Changes in water quality caused by operation of the recovery system at individual monitoring wells also are discussed.

Horizontal Extent of Contamination

The discussion of the isoconcentration contour maps (Maps 6 through 15, Appendix I, Volume III) generally centers on the horizontal distribution of trichloroethylene, the primary contaminant. Tetrachloroethylene, while similar to trichloroethylene, is usually present in lower concentrations and to a lesser extent.

Contour lines are solid when the horizontal extent of the groundwater contamination was confidently interpreted, and when concentration boundaries were somewhat uncertain, contour lines are dashed. The maps are based on interpretation and the overall relationship between areas of different concentrations. Also, the contoured boundaries depict areas of suspected groundwater contamination and should not be interpreted as homogeneous zones of equivalent concentrations. The subsurface is a heterogeneous mixture of coarse and fine sand sediments layered with thicker restricting clays; therefore, fluid flow is selective through the varying lithologies.

M-Area Aquifer Zone

Maps 6 and 7 (Appendix I, Volume III) show the distribution of tetrachloroethylene and trichloroethylene in the M-Area Aquifer Zone. The 5 $\mu\text{g/L}$ contour is the interpreted boundary where the contaminant exceeded the Safe Drinking Water Act final PDWS during first quarter 1995. The contaminant plume shown on these maps is generally limited to the vicinity of known or suspected solvent disposal sites, which include the M-Area HWMF, the Solvent Storage Facility, the A-014 outfall, the Metallurgical Laboratory Seepage Basin, the Silverton Road Waste Site, and the A-Area Metals Burning Pit, Burning/Rubble Pit, and Miscellaneous Chemicals Basin.

Upper Lost Lake Aquifer Zone

Maps 8 and 9 (Appendix I, Volume III) are the isoconcentration maps for the Upper Lost Lake Aquifer Zone. The 5 $\mu\text{g/L}$ dashed contour illustrates the interpreted boundary of groundwater contamination. The pattern of contamination in the Upper Lost Lake Aquifer Zone in relation to known point sources is similar to, but more extensive than, the pattern in the M-Area Aquifer Zone. In general, the extent of the plume in this unit is greater in the downgradient direction than in the M-Area Aquifer Zone due to greater horizontal flow rates in both the Upper and Lower Lost Lake Aquifer Zones.

Lower Lost Lake Aquifer Zone

Degreaser solvent concentrations in the Lower Lost Lake Aquifer Zone are shown on Maps 10 and 11 (Appendix I, Volume III). The lateral extent of the plume as defined by the 5 $\mu\text{g/L}$ contour is greater in the downgradient directions than in the upper units because the Upper and Lower Lost Lake Aquifer Zones have a higher potential for horizontal flow. The 1,000 $\mu\text{g/L}$

contour has been drawn to generalize the extent of some concentrations that are suspect, but is not to be interpreted as a zone of ubiquitous occurrence. The 100 $\mu\text{g/L}$ contour includes a region northeast of the Savannah River Technical Center (SRTC) around well MSB 48B.

Middle Sand Aquifer Zone of the CBCU

The distribution of constituents in the Middle Sand Aquifer Zone is shown in Maps 12 and 13 (Appendix I, Volume III). Monitoring is limited in the Middle Sand Aquifer Zone. Chlorinated solvent concentrations in this unit, as in the overlying units, are highest in the vicinity of known sources. Contamination is less extensive beneath western M Area in the Middle Sand Aquifer Zone than in overlying units. Beneath the eastern sector of M Area, contamination patterns are similar to, but less extensive than, contamination in the Lower Lost Lake Aquifer Zone.

Crouch Branch Aquifer Zone

Chlorinated solvent contamination in the Crouch Branch Aquifer Zone is primarily limited to the area beneath SRTC and an area extending from the SRTC north to well MSB 55TA, which is generally upgradient of these facilities. Downward vertical hydraulic gradients from the M-Area Aquifer Zone to the Crouch Branch Aquifer Zone characterize the vicinity of the SRTC. The presence of a zone of increased transmissivity in the Middle Sand Aquifer Zone, which allows downward flow into the Crouch Branch Aquifer Zone, is indicated by the solvent concentrations measured in wells monitoring that portion of the Crouch Branch Aquifer Zone.

Inorganic Constituents

The results of a special program conducted to determine the extent of inorganic contamination near the M-Area HWMF were presented in the 1987 annual report (DuPont, 1988). The results indicate that a plume of mobile inorganic constituents is present south-southeast of the M-Area HWMF. The plume is evident in most of the hydrostratigraphic units composing the M-Area Aquifer Zone and appears to have a pattern similar to the chlorinated solvent plumes. Plume maps for the inorganics were also shown in the revised RCRA Part B post-closure care permit application submitted May 31, 1988; however, they are not presented in this report. Because these constituents are within the more extensive chlorinated solvent plumes, they will be addressed by the current corrective-action system or by future measures, such as those proposed in the revised permit application.

Time Series Plots and Effects of the Recovery System

Figures 9 through 20 (Appendix C, Volume I) are the time series plots of the RWM wells. Time series plots for the monitoring wells are shown in Appendix F (Volume II). The effects of the recovery system on tetrachloroethylene and trichloroethylene concentrations will be discussed in the third quarter 1995 report.

Effectiveness of the Corrective-Action Program

The effectiveness of the corrective-action program is evaluated using two techniques: water quality changes and rate of removal. The duration of the cleanup program is assessed by tracking the time it takes contaminants to be removed from the groundwater. The results of each analysis for first quarter 1995 are provided below.

Water Quality Changes

Changes in tetrachloroethylene and trichloroethylene concentrations during the past several years in samples from POC, background, plume definition, and recovery wells are illustrated in time series plots in Appendix F (Volume II). Isoconcentration contour maps showing tetrachloroethylene and trichloroethylene concentrations are in Appendix I (Maps 6 through 15, Volume III).

Changes in trichloroethylene concentrations during first quarter 1995 and over the long term were statistically evaluated using the cumulative summations (CUSUM) test as described in the 1987 annual monitoring and corrective-action report (DuPont, 1988).

Results of the CUSUM test for 40 monitoring wells and 11 recovery wells are summarized in Tables 8 and 9 (Appendix D, Volume I), respectively. Data are presented in Appendix H (Volume II). Long-term trends in trichloroethylene concentrations, determined using data collected since CUSUM analysis was initiated, are as follows: 2 showed no trend, 26 showed an upward trend, and 12 showed a downward trend. Six of the 11 recovery wells showed a long-term downward trend; 5 recovery wells showed a long-term upward trend. Twenty-three monitoring wells provided no data for first quarter 1995.

Rate of Removal

SRS determines the rate of removal using mass balance calculations that subtract the concentration of trichloroethylene in the effluent from the concentration of trichloroethylene in the influent. This amount is then multiplied by the number of gallons of water that passed through the stripper column during a given period. The results of this technique are described in the *Corrective-Action System Operation and Performance* section.

Corrective-Action System Operation and Performance

Corrective action is accomplished in A/M Areas by pumping contaminated groundwater to two air strippers where volatile organic compounds are removed and by pumping contaminated air, using vacuum extraction, from the vadose zone to a catalytic-oxidation unit where the volatile organic compounds are destroyed. A production air stripper in M Area (M-1), fed by 11 recovery wells, has been in operation since April 1985 and operating full scale since September 1985. A second air stripper in A Area (A-1), fed by a single recovery well, has been in operation since March 1992. A production catalytic-oxidation unit at the Integrated Demonstration Site (782-7M IDU), fed by a single vapor extraction well, has been in experimental operation since 1990 and in full-scale operation since August 1994. A description of the systems that compose the corrective-action program is presented in WSRC (1994). Summary tables for 1994 of the downtime, operation, and performance of the M-1 Air Stripper, the A-1 Air Stripper, and the Integrated Demonstration Vadose Zone Unit are provided in Tables 14 through 21 (Appendix D, Volume I).

Air Stripper Performance

A summary of the system downtime during first quarter 1995 for both air strippers is presented in Table 22 (Appendix D, Volume I).

M-1 Air Stripper

A summary of first quarter 1995 operating and performance data for the M-1 air stripper is presented in Table 23 (Appendix D, Volume I). During the quarter, the stripper removed 2,925 lbs of degreaser solvent from 36,733,530 gal of water while operating at a utility of 94.6 percent and with an emission rate of 1.40 lbs/hr for the quarter. The average inlet water feed rate was 297 gallons per minute (gpm) for first quarter. The average quarterly influent of tetrachloroethylene was 3,469 $\mu\text{g/L}$ and of trichloroethylene was 5,693 $\mu\text{g/L}$. The average quarterly effluent total was less than 3.34 $\mu\text{g/L}$.

The M-1 air stripper has removed a cumulative total of 293,621 lbs of solvent from more than 2.0 billion gal of groundwater while operating at an average utility of 95.2 percent. When combined with the contaminated water treated by the pilot air stripper, the prototype air stripper, and the start-up of the full-scale M-1 air stripper system (16,200, 15,900, and 2,100 lbs, respectively, for a total of 34,200 lbs), the total mass of tetrachloroethylene and trichloroethylene removed by the M-1 air stripper is 327,820 lbs.

The water feed rate to the M-1 air stripper has averaged 425 gpm since startup. Total inlet solvent concentrations have decreased from roughly 47,100 $\mu\text{g/L}$ in April 1985 to a low of less than 6,796 $\mu\text{g/L}$ in June 1993. Stripping efficiency has always been greater than 99.95 percent, with effluent tetrachloroethylene and trichloroethylene concentrations less than their permit limits of 5 $\mu\text{g/L}$.

A-1 Air Stripper

A summary of first quarter 1995 operating and performance data for the A-1 air stripper is presented in Table 24 (Appendix D, Volume I). During the quarter, the stripper removed 110 lbs of degreaser solvent from 4,944,432 gal of water while operating at a utility of 72.5 percent and with

an emission rate of 0.08 lbs/hr for the quarter. The average inlet water feed rate was 53 gpm. The average quarterly influent of tetrachloroethylene was less than 165 $\mu\text{g/L}$. The average quarterly influent of trichloroethylene was 2,998 $\mu\text{g/L}$. The average quarterly effluent total was less than 3.34 $\mu\text{g/L}$.

The A-1 air stripper has removed a cumulative total of 1,756 lbs of solvent from more than 77 million gal of groundwater while operating at an average utility of 90.5 percent. The water feed rate to the A-1 air stripper has averaged 54 gpm since startup. Stripping efficiency has been greater than 99.8 percent, with effluent tetrachloroethylene and trichloroethylene concentrations less than their permit limits of 5 $\mu\text{g/L}$.

Vadose Zone Unit Performance

Integrated Demonstration Unit

A summary of the system downtime for the Integrated Demonstration Vadose Zone Unit (IDU) is presented in Table 22 (Appendix D, Volume I).

A summary of first quarter 1995 operating and performance data for the IDU is presented in Table 27 (Appendix D, Volume I). During the quarter, the IDU removed a total of 344.9 lbs of degreaser solvent while operating at a utility of 12.7 percent and with emission rates for the quarter of 0.34 lbs/hr hydrogen chloride vapor, 0.02 lbs/hr tetrachloroethylene, and 0.003 lbs/hr trichloroethylene. The average quarterly influent of tetrachloroethylene was 56.9 parts per million volume (ppmv) and trichloroethylene was 27.1 ppmv. The average quarterly effluent total was 4.6 ppmv.

The IDU has removed a total of 2,448 lbs of solvent while operating at an average utility of 32.2 percent. Combined with the experimental vadose zone stripping (approximately 1,500 lbs in 1987 and 16,000 lbs in 1990), the total mass of tetrachloroethylene and trichloroethylene removed by the IDU is 19,948 lbs.

Recovery Well System

Monthly and cumulative volumes of groundwater pumped from the recovery well system and average flow rates for recovery wells RWM 1 through 12 are presented in Table 25 (Appendix D, Volume I). Monthly concentrations ($\mu\text{g/L}$) of tetrachloroethylene and trichloroethylene in each well are presented in Table 26 (Appendix D, Volume I).

The concentration data in Table 26 (Appendix D, Volume I) are presented as a function of time in Figures 8 through 21 (Appendix C, Volume I). Missing data for these plots are due to a scheduling error during first quarter 1994; WSRC inadvertently missed two months (January and March) of analytical sampling at recovery wells RWM 1 through 12.

Vapor Extraction Well System

Vapor extraction well AMH 2 pumps contaminated air to the IDU. Table 27 (Appendix D, Volume I) presents a summary of first quarter activity at the IDU.

Air Stripper Modifications

M-1 and A-1 Air Strippers

No major modifications were made to the M-1 or A-1 air stripper during first quarter 1995.

Vadose Zone Unit Modifications

Integrated Demonstration Unit

No major modifications were made to the IDU during first quarter 1995.

Monitoring and Corrective-Action Program Assessment

As required by Hazardous Waste Permit SC1-890-008-989, Condition V.A.3, SRS is continuing to assess the contamination in the Tertiary age (uppermost) aquifers and the deeper Cretaceous aquifer at the M-Area HWMF. The purpose of this continued assessment is to identify sources of contamination and modify the existing corrective-action program as necessary. A discussion of new findings and ongoing programs designed to fulfill this requirement is presented in this section.

New Findings

Northern Sector Monitoring

Elevated concentrations of trichloroethylene were observed in well MSB 82A during 1992 as documented in WSRC (1993). Well MSB 82A, located north of the Savannah River Technology Center and approximately 1,500 ft from the SRS boundary, monitors the Middle Sand Aquifer Zone of the CBCU, 245–250 ft below ground surface.

In response to the elevated trichloroethylene concentrations at well MSB 82A, SRS installed groundwater monitoring well MSB 84A near the SRS northern boundary to monitor the same aquifer zone as MSB 82A. During coring and installation at MSB 84A, soil samples were collected for volatile organic analysis. No evidence of contaminants was detected.

Routine groundwater sampling at MSB 84A began first quarter 1994. Analysis from first and second quarters of 1994 showed no evidence of volatile organic contaminants. This well was not monitored during third quarter 1994 because of a broken pump or during fourth quarter 1994 because analyses were not scheduled. The well was not sampled during first quarter 1995 because of maintenance problems.

Ongoing Programs

M-Area Compliance and Post-Closure Programs

- In 1980, the U.S. Department of Energy (DOE) submitted a notification of the SRS hazardous waste activities to SCDHEC; DOE then submitted a RCRA Part A hazardous waste permit application.
- SRS notified SCDHEC of volatile organic solvent contamination when it was first detected in the groundwater beneath the settling basin in June 1981. A network of monitoring wells was initiated to define the extent, concentration, distribution, and migration rate of the contaminant plume.
- Interim status monitoring began in 1983 and continued through September 1987; assessment monitoring was initiated second quarter 1986 and completed fourth quarter 1987.
- In February 1983, SRS voluntarily began a pilot remediation system to treat contaminated groundwater.

- A groundwater protection plan was submitted to Congress in June 1984 to meet the requirements of Public Law 98-181.
- In compliance with the requirements of Public Law 98-181, a closure plan for the settling basin was submitted to SCDHEC in 1984, with revisions in 1985 and 1987.
- A full-scale corrective-action program was initiated in 1985 to remove and treat hazardous constituents from the groundwater beneath the M-Area HWMF.
- The M-Area HWMF RCRA Part B post-closure care permit application was approved by SCDHEC in 1987.
- Closure was approved by SCDHEC on July 10, 1987; a closure cap was completed during 1989 and 1990; and closure was certified by SCDHEC on April 26, 1991.
- The 1992 M-Area HWMF RCRA Part B permit renewal application was submitted to SCDHEC in April 1992 as specified in SCHWMR R.61-79.270.30(b) and 270.50(a).
- Revision 1 of the 1992 M-Area HWMF RCRA Part B permit renewal application was submitted to SCDHEC in March 1993. The revision included proposals to reduce the sampling, analysis, and reporting requirements for the groundwater monitoring program in A/M Areas.
- Modifications to the 1992 M-Area HWMF RCRA Part B permit renewal application (Revision 2) and the 1987 Part B permit application (Revision 4) were submitted to SCDHEC December 20, 1993. The modifications included a proposal to include PCB monitoring at specified A/M Areas groundwater monitoring wells.
- To expedite SCDHEC's approval of the program to reduce sampling, analysis, and reporting, Revision 5 of the 1987 Part B permit application was submitted in February 1994. SRS received a Notice of Deficiency (NOD) on Revision 5 in June 1994.
- Revision 6 of the 1987 Part B permit application, submitted to SCDHEC in July 1994, has been approved by SCDHEC. The revision addresses the NOD on Revision 5, with modifications to the proposed reductions in sampling, analysis, and reporting.
- Also in July 1994, Revision 3 of the 1992 Part B permit renewal application was submitted to SCDHEC in response to their NOD. Revision 3 modifications included updating the hydrostratigraphic nomenclature; updating information on the purged water disposal station, closure and corrective-action activities, DNAPL investigations, and proposed demonstration programs; adding information on new investigations in the western and southern sectors of A/M Areas; and revising text on contingency plans, personnel training, and procedures to prevent hazards. The renewal document adheres to the format specified in the U.S. Environmental Protection Agency (EPA) Regulatory Completeness Checklist for Post-Closure Permit Applications (Revision 4, February 4, 1986). SCDHEC reviewed the application and held a comment and response period in March 1995.
- The final report updating the hydrostratigraphy of the A/M Areas and the Metallurgical Laboratory HWMF was submitted to SCDHEC in February 1995.

A/M Areas Vadose Zone Remediation

Although the corrective-action system in A/M Areas has proven effective in removing and treating contaminated groundwater, it does not remove contaminants from the vadose zone, which is the unsaturated layer of soil between the ground surface and the water table. Vadose zone remediation decreases the migration of residual contaminants into the groundwater and reduces the time required for groundwater remediation.

The following four sites, which have elevated levels of tetrachloroethylene and trichloroethylene in the vadose zone, have been chosen for vadose zone remediation using vacuum extraction: the abandoned process sewer line, the M-Area Settling Basin, the A-014 outfall, and the 321-M former solvent storage area. Vacuum extraction was selected after a successful pilot demonstration removed more than 1,500 lbs of solvents during a 21-day test in 1987.

Four soil vacuum extraction (SVE) units were installed in A/M Areas during 1994. Design of the SVE units was completed March 11, 1994; construction began March 28, 1994, and has been completed; and the SVE units are currently being tested. Two vapor extraction wells have been completed near the A-014 outfall. Operations for the SVE units are anticipated to begin in May 1995.

On March 25, 1994, SRS requested temporary authorization to initiate vadose zone vacuum extraction at the four locations. SCDHEC granted temporary authorization in June 1994 (letter, J. Litton to W. Wierzbicki, June 16, 1994).

The soil vacuum extraction systems will operate under air quality control permits 0080-0041-M-CA, 0080-0041-M-CB, 0080-0041-M-CC, and 0080-0041-A-CA issued by SCDHEC in January 1993.

Integrated Demonstration Project-Subsystem I

The Integrated Demonstration Project was transferred to ERD on March 30, 1994. Preliminary startup activities to conduct soil vacuum extraction in the vadose zone, including component and system testing, also were completed on March 30, 1994. Regulatory approval for full-scale operation was obtained in June 1994 (letter, J. Litton to W. Wierzbicki, June 16, 1994). Full-scale operation of the extraction equipment began on schedule August 1, 1994.

The following products related to the demonstration were issued during third quarter 1994: a numerical simulation model (LANL), a cost analysis report (LANL), a preliminary technology report, a level 2 summary report, a bioremediation demonstration video, an integrated demonstration 3D video, and an integrated discussion video.

Barometric Pumping and Solar-Enhanced Barometric Pumping Demonstrations

Subsurface pressure fluctuations are correlated to atmospheric barometric pressure fluctuations but are damped in amplitude and lagging in phase. The damping and lag occur because pressure between the vadose zone and the atmosphere can produce air flows if the two regions are connected (e.g., by a well screened in the vadose zone). Barometric pumping and solar-enhanced barometric pumping take advantage of these naturally produced forces to remove volatile organic compounds from the subsurface in the form of soil gas. SRS plans to evaluate these technologies through a demonstration (WSRC, 1994).

SRS requested temporary authorization for barometric pumping and solar-enhanced barometric pumping from SCDHEC on May 23, 1994; temporary authorization was granted in June 1994 (letter, J. Litton to W. Wierzbicki, June 16, 1994). Both technologies will be demonstrated for less than one year. Currently, work is being conducted and data are being collected for both projects.

Electron Beam Demonstration

Electron beam technology has been in commercial use since 1950. Applications include sterilization of medical supplies, rubber vulcanization, disinfection of wastewater, etc. The reaction by-products are nontoxic.

DOE and EPA are jointly demonstrating electron beam technology at SRS to obtain engineering and cost data for remediation activities (WSRC, 1994). The method uses a commercial electron beam to demonstrate the treatment of groundwater contaminated with chlorinated volatile organic compounds.

SRS requested temporary authorization for electron beam technology from SCDHEC on May 23, 1994; temporary authorization was granted in June 1994 (letter, J. Litton to W. Wierzbicki, June 16, 1994). Subsequently, the initial demonstration was performed, the appropriate modifications were made, and the final demonstration was performed the first week of November 1994.

Purge Water Management

During third quarter 1993, construction of a facility to receive, store, and transfer purged water from the M-Area monitoring wells to the M-1 air stripper was completed. This Purged Water Disposal Station, 782-2M, houses a 10,000-gal, double-wall tank. This facility has been used continuously for containment of purged water since January 1994.

Northern Sector—Aquifer Step Test on New Recovery Wells

The variable yield step test, which measures drawdown at varying pump rates, is used to evaluate the relationship between laminar and turbulent flow in a pumping well and the extent of head loss. Data from these tests also provide estimated ranges of specific capacity, available drawdown, transmissivity, and storativity for the aquifer units.

Variable yield step tests were conducted during 1994 on each of the newly installed recovery wells RWM 13B, 13C, 14B, 14C, and 15B, and a final report was issued in September 1994. All groundwater withdrawn from the wells was containerized and transported by permitted tanker truck to the purged water disposal station, treated in the M-1 air stripper, and subsequently released to the A-014 outfall. Groundwater samples were obtained from the Lost Lake Aquifer Zone to characterize solvent concentrations and detect any changes that may have occurred during the test period.

Western Sector—Characterization

During the first three quarters of 1994, SRS investigated the groundwater contaminant plume in the western sector of A/M Areas. The plume is outside the influence of the M-Area groundwater recovery well system and is being studied to determine the magnitude and extent of contamination and to define the geology and hydrology of the area.

Phase I characterization to define the boundaries of the plume was completed during second quarter 1994 and consisted of the following:

- Six soil coreholes were drilled to approximately 250 ft (upper part of the CBCU) and sampled for soil headspace analysis. Soil plugs were taken at 10-ft intervals from the water table down to the target depth.
- A cone penetrometer survey was completed at six locations after approval from SCDHEC was received January 20, 1994 (letter, R. Ede to J. Cook). Geotechnical data were collected at the six locations, and groundwater samples were collected at three locations using the hydrocone method.

All soil and groundwater samples were analyzed for volatile organic compounds. As required by SRS, the analytical data was subjected to quality assurance/quality control (QA/QC) procedures. A Phase I final report, detailing the characterization, including analytical results and additional characterization needs, was issued to SCDHEC in February 1995. Future investigations depend on Phase I results.

Southern Sector—Soil Coring

Beginning June 1994, SRS drilled 10 coreholes to help define the lateral and vertical dimensions of the groundwater contaminant plume southeast of the M-Area HWMF and south of the A-014 outfall. The coreholes were drilled to approximately 250 ft in areas of known data deficiency. Soil plug samples were taken at 10-ft intervals from the water table down to the target depth and will be analyzed for volatile organic compounds. A final report on the soil coring will be issued by fourth quarter 1995.

Southern Sector—Aquifer Tests on Phase V Wells

Phase V wells will provide information on the hydraulic parameters of the Steed Pond Aquifer to use in groundwater flow models. The following activities have been initiated in the southern sector:

- Pretest calculations suggest the location of the existing wells, designated as observation points, is not satisfactory to denote the response to pumping of a 2-in. diameter well approximately 600 to 2,000 ft away. Therefore, 2-in. piezometers that screen the entire aquifer zone of concern were installed at closer radial distances (i.e., 25 to 50 ft) within the vicinity of existing monitoring wells. A total of five piezometers was installed: two piezometers (screened across the Upper and Lower Lost Lake Aquifer Zones) near well MSB 32; two piezometers (screened across the Lost Lake and M-Area Aquifer Zones) near well MSB 89; and one piezometer (screened across the Lost Lake Aquifer Zone) near well cluster MSB 88.
- A 72-hour pump test using the newly installed piezometers as pumping wells (because they screen the entire aquifer zone of concern) and the existing monitoring wells as observation points was conducted at the following well locations: MSB 32B, 32C, and 89C. These wells were selected because their VOC concentrations are less than 5 ppb and SRS currently does not have the resources to containerize the groundwater as outlined in the SRS Investigative Derived Waste Plan.

Metallurgical Laboratory Phase X Drilling Project

In response to the January 28, 1994, NOD issued by SCDHEC on the 1992 Metallurgical Laboratory (Met Lab) HWMF RCRA Part B permit renewal application (Revision 0), SRS constructed the following Phase X monitoring wells:

- M-Area Aquifer Zone: 1 POC well and 2 plume definition wells
- Lost Lake Aquifer Zones: 2 POC wells
- Middle Sand Aquifer Zone of the CBCU: 2 POC wells

The positions of the wells were based on present groundwater flow information in the respective aquifers. The new wells, all downgradient to the Met Lab Basin, provide three additional monitoring wells in the M-Area Aquifer Zone, one additional well in the Lost Lake Aquifer Zone, one additional well immediately south of the Carolina Bay in the Lost Lake Aquifer Zone, and two additional wells in the Middle Sand Aquifer Zone of the CBCU. Cone penetrometer technology was used to place the plume definition wells. A final report will be issued by fourth quarter 1995.

M-Area HWMF Drainage Ditch Modifications

SRS completed the modifications to the drainage ditch around the southern and eastern sides of the M-Area HWMF cap in early February 1995. These modifications channel water away from the facility and prevent seepage back into the basin. Temporary authorization was granted by SCDHEC in June 1994 (letter, J. Litton to W. Wierzbicki, June 16, 1994).

Proposed Monitoring and Corrective-Action Program Modifications

Progress regarding modifications to the A/M Areas Corrective-Action Program at SRS is described in this section. The M-Area HWMF RCRA Part B permit renewal application includes discussions of soil and groundwater investigations in A/M Areas at SRS. Several commitments made in the application have been fulfilled or are in progress as discussed below.

Groundwater Monitoring Program

Update of the Hydrogeologic Setting of A/M Areas

SRS has updated the geologic interpretation of A/M Areas. The document, *Hydrogeologic Framework for the A/M Area (U)*, WSRC-RP-95-52, was finalized and submitted in February 1995. The report includes new geologic cross sections and information on the subsurface stratigraphy and structure of A/M Areas. The report was based on data collected from the A/M Areas Phase II, III, III-A, and IV well-drilling programs. The new nomenclature is incorporated in this report.

Corrective-Action Program

SRS submitted the 5-year renewal application of the Part B permit to SCDHEC in April 1992 (WSRC, 1992) as specified in the South Carolina Hazardous Waste Management Regulations R.61-79.270.30(b) and 270.50(a) (SCDHEC, 1992). The renewal application describes the corrective-action programs for the M-Area HWMF, and the permit includes a policy of evaluating the overall effectiveness of the corrective-action program.

MSB 3D and 22D are the focal points for future DNAPL characterization and remediation assessment technologies. Periodic reports of findings during DNAPL assessment studies will be submitted to SCDHEC. The reports will document ongoing investigations for residual solvents at M Area and will replace quarterly sampling and reporting for these wells.

A/M-Areas Vadose Zone Remediation Program

The M-Area HWMF RCRA Part B permit renewal application includes a proposal to remediate the vadose zone at several specific sites in A/M Areas at SRS. SRS officials have initiated a program to reduce contamination levels in the unsaturated zone at old source sites and to protect the groundwater from additional contamination. Vacuum extraction technology was selected for remediation of contamination in the vadose zone based on the success of a pilot study in which approximately 1,500 lbs were removed in 1987 and 16,000 lbs were removed in 1990. A total of 17,500 lbs of degreaser solvents were extracted during test periods associated with the pilot study. A vadose zone characterization program, designed to provide information for the soil-vapor extraction systems, and four of six proposed vertical extraction wells were completed during 1994. Start-up of the extraction units is expected to begin by May 1995. See the *Monitoring and Corrective-Action Program Assessment* section for more information about this program.

References Cited

DuPont (E. I. du Pont de Nemours & Company), 1988. **M-Area Hazardous Waste Management Facility Post-Closure Care Permit Groundwater Monitoring and Corrective-Action Program 1987 Annual Report**, Appendix D, DPSP-88-172-1. Savannah River Plant, Aiken, SC.

EPA (Environmental Protection Agency), 1992. *Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities*, **Code of Federal Regulations**, Title 40, Part 264, pp. 324-330. Washington, DC.

EPA (Environmental Protection Agency), 1993a. *National Primary Drinking Water Regulations*, **Code of Federal Regulations**, Title 40, Part 141, pp. 589-729. Washington, DC.

EPA (Environmental Protection Agency), 1993b. *National Secondary Drinking Water Regulations*, **Code of Federal Regulations**, Title 40, Part 143, pp. 772-776. Washington, DC.

EPD/EMS (Environmental Protection Department/Environmental Monitoring Section), 1995. **Environmental Protection Department's Well Inventory (through the fourth quarter of 1994)**, ESH-EMS-940519. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Lewis, S. E., and R. K. Aadland, 1992. **Hydrogeologic Setting of A/M Area: Framework for Groundwater Transport**, WSRC-TR-92-355. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Lewis, S. E., and R. K. Aadland, 1993. **Hydrogeologic Setting of A/M Area: Framework for Groundwater Transport**, WSRC-TR-92-355 (December 10, 1993, revision). Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

SCDHEC (South Carolina Department of Health and Environmental Control), 1987. **Hazardous Waste Permit SC1-890-008-989**. Office of Environmental Quality Control, Bureau of Solid and Hazardous Waste Management, Columbia, SC.

SCDHEC (South Carolina Department of Health and Environmental Control), 1992. **South Carolina Hazardous Waste Management Regulations**; R. 61-79.124, 260 through 266, 268, and 270; December 1992. Columbia, SC.

WSRC (Westinghouse Savannah River Company), 1987. **Application for a Post-Closure Permit, M-Area Hazardous Waste Management Facility**, Vol. III, Rev. 2. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1988. **Application for a Post-Closure Permit, M-Area Hazardous Waste Management Facility**, Vol. III, Rev. 3. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1990. **Quality Assurance Plan**, Rev. 1, WSRC-1-05. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1992. *Sampling Groundwater Monitoring Wells, Hydrogeologic Data Collection Procedures and Specifications*, Manual 3Q5, Rev. 1, Chapter 15. Savannah River Site, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1993. **Groundwater Monitoring Observations in the Northern Sector, A/M Area**, WSRC-RP-93-909. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1994. **M-Area Hazardous Waste Management Facility 1992 Renewal Application for a RCRA Part B Permit**, Vol. III, Rev. 3, WSRC-IM-91-53. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Errata and Revisions

Result values for earlier quarters presented in this report may differ from the values for those same quarters presented in previous reports because some re-analyses may have occurred after the quarterly reports were printed. Also, samples for field data are collected once each quarter, but samples for analytical data may be collected more than once each quarter. Thus, because the results tables present the highest analytical result for the quarter, the reported analytical result may be from a sample collected on a different date from the date the field data sample was collected.

First Quarter 1994:

- Pages 2-6 through 2-47, Table 2-1, Groundwater Monitoring Results for Point-of-Compliance Wells. The following data modifiers should be added to the *Mod* column for the wells and analytes indicated.

<u>Well</u>	<u>Analyte</u>	<u>Mod</u>
MSB 1B	all Appendix IX analytes	1
MSB 1C	chloride	3
MSB 2B, 2C, 4B, 13B	all Appendix IX analytes	Y
MSB 3C, 6B	aluminum, arsenic, barium, cadmium, chromium, copper, lead, mercury, nickel, selenium, silver, sodium, uranium, zinc	Y
MSB 7C	mercury	J3
MSB 8C	selenium	J3
MSB 13CC	chlorobenzene, 1,1-dichloroethane, 1,1-dichloroethylene, trans-1,2-dichloroethylene, 1,1,2,2-tetrachloroethane, tetrachloroethylene, 1,1,1-trichloroethane	1
MSB 58D	lead	3
	selenium	J3
MSB 62B	zinc	3

- Pages 3-14 through 3-353, Table 3-2, Appendix IX Constituents in Groundwater from Plume Definition Wells. The following data modifiers should be added to the *Mod* column for the wells and analytes indicated.

<u>Well</u>	<u>Analyte</u>	<u>Mod</u>
ABP 8C, ASB 9B, MSB 40D, 40TA, 41B, 41C, 41D, 41TA, 42B, 42C, 42D, 42TA, 43A, 43B, 43D, 43TA, 44A, 79B, 79C	all analytes	Y
MSB 12TA, 75B, SRW 1, 3A, 4BB, 5, 6, 7, 8BB, 10, 10BB, 11, 11BB, 16A, 17BB, 17C	all analytes	1
MSB 12TB	chlorobenzene, 1,1-dichloroethane, 1,1- dichloroethylene, trans-1,2-dichloroethylene, tetrachloroethylene, 1,1,2,2-tetrachloroethane, 1,1,1-trichloroethane	1
MSB 27A, SRW 16B	trichloroethylene	1
MSB 53C	chlorobenzene, 1,1-dichloroethane, 1,1- dichloroethylene, trans-1,2 dichloroethylene, 1,1,2,2-tetrachloroethane, 1,1,1-trichloroethane	1
SRW 1BB	trans-1,2-dichloroethylene	1
SRW 2, 4, 12C	tetrachloroethylene, trichloroethylene	1
SRW 3BB	tetrachloroethylene	3
	chlorobenzene, trans-1-2 dichloroethylene, 1,1,2,2-tetrachloroethane, 1,1,1-trichloroethane	J3
SRW 8	trichloroethylene	3
SRW 15A	chlorobenzene, 1,1-dichloroethane, 1,1- dichloroethylene, trans-1-2 dichloroethylene, 1,1,2,2-tetrachloroethane, tetrachloroethylene, 1,1,1-trichloroethane, trichloroethylene	J3

- Pages 3-354 through 3-407, Table 3-3, Inorganic Constituents in Groundwater from Selected Plume Definition Wells. The following data modifiers should be added to the *Mod* column for the wells and analytes indicated.

<u>Well</u>	<u>Analyte</u>	<u>Mod</u>
MSB 12A	aluminum, arsenic, barium, chromium, copper, lead, mercury, nickel, selenium, silver, sodium, uranium, zinc	Y
MSB 12B	aluminum, arsenic, barium, chromium, copper, mercury, nickel, selenium, silver, sodium, uranium, zinc	Y
	lead	JY3
MSB 17B	sulfate	J3

<u>Well</u>	<u>Analyte</u>	<u>Mod</u>
MSB 21C, 31B, 36B	selenium	J3
MSB 39A	total phosphates	3
RWM 1	cyanide	1
	sulfate	3

Second Quarter 1994:

- Page 1-1, Chapter 6. In the first bulleted item, sodium was elevated in 27 (not 25) wells and trichloroethylene was elevated in 37 (not 38) wells.

Third Quarter 1994:

- Pages 1 and 2, Summary and pages D-437 and D-438, Table 7, Appendix D, Volume I. The results reported for many of the Appendix IX constituents in this table were for laboratory quality control spikes, not groundwater samples.
- Page I-8, Map 2, Appendix I, Volume III. Flow path line C-C' was unintentionally omitted from the Upper Lost Lake Aquifer Zone potentiometric contour map. The flow rate derived from this path line is provided in Table 8, Appendix D, Volume I.

Fourth Quarter 1994:

- No errata have been reported.

THIS PAGE LEFT BLANK INTENTIONALLY.

Appendix A

Standards

THIS PAGE LEFT BLANK INTENTIONALLY.

Standards

<u>Constituent</u>	<u>Unit</u>	<u>Standard</u>	<u>Source</u>
Aluminum	µg/L	100	WSRC (1987) ^a
Arsenic	µg/L	50	EPA (1993a) ^b
Barium	µg/L	1,000	WSRC (1994) ^c
Cadmium	µg/L	5	EPA (1993a)
Chloride	µg/L	4,200	WSRC (1987)
Chlorobenzene	µg/L	100	WSRC (1994)
Chromium	µg/L	100	EPA (1993a)
Cobalt	µg/L	4	WSRC (1994)
Copper	µg/L	1,300	WSRC (1994)
Cyanide	µg/L	200	WSRC (1994)
1,1-Dichloroethane	µg/L	5	WSRC (1994)
1,1-Dichloroethylene	µg/L	7	WSRC (1994)
trans-1,2-Dichloroethylene	µg/L	100	WSRC (1994)
Gross alpha	pCi/L	15	EPA (1993a)
Lead	µg/L	50	WSRC (1994)
Mercury	µg/L	2	EPA (1993a)
Nickel	µg/L	4	WSRC (1994)
Nitrate	µg/L	2,400	WSRC (1987)
Nonvolatile beta	pCi/L	50	EPA (1993a)
PCB 1254	µg/L	0.5	WSRC (1994)
Radium, total alpha-emitting ^d	pCi/L	5	EPA (1993a)
Selenium	µg/L	10	WSRC (1994)
Silver	µg/L	100	EPA (1993b)
Sodium	µg/L	4,600	WSRC (1987)
Sulfate	µg/L	3,000	WSRC (1987)
1,1,2,2-Tetrachloroethane	µg/L	5	WSRC (1994)
Tetrachloroethylene	µg/L	5	WSRC (1994)
Total phosphate as P	µg/L	300	WSRC (1987)
1,1,1-Trichloroethane	µg/L	200	WSRC (1994)
Trichloroethylene	µg/L	5	WSRC (1994)
Uranium	µg/L	100	WSRC (1987)
Zinc	µg/L	5,000	EPA (1993b)

^a Concentrations with WSRC (1987) sources are background concentrations.

^b Concentrations and activities with EPA (1993a) sources are primary drinking water standards.

Concentrations with EPA (1993b) sources are secondary drinking water standards.

^c Concentrations with WSRC (1994) sources are groundwater protection standards.

^d The standard used for total alpha-emitting radium is the primary drinking water standard for total radium.

References Cited

EPA (Environmental Protection Agency), 1993a. *National Primary Drinking Water Regulations, Code of Federal Regulations*, Title 40, Part 141, pp. 592-732. Washington, DC.

EPA (Environmental Protection Agency), 1993b. *National Secondary Drinking Water Regulations, Code of Federal Regulations*, Title 40, Part 143, pp. 774-777. Washington, DC.

WSRC (Westinghouse Savannah River Company), 1987. **Application for a Post-Closure Permit, M-Area Hazardous Waste Management Facility**, Vol. III, Rev. 2. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1994. **M-Area Hazardous Waste Management Facility 1992 Renewal Application for a RCRA Part B Permit**, Vol. III, Rev. 3, WSRC-IM-91-53. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Appendix B

Flagging Criteria

THIS PAGE LEFT BLANK INTENTIONALLY.

Flagging Criteria

The Savannah River Site Environmental Protection Department/Environmental Monitoring Section (EPD/EMS) flagging criteria are as follows:

- Flag 2 criteria for constituents equal the Safe Drinking Water Act (SDWA) final Primary Drinking Water Standards (PDWS), the SDWA proposed PDWS, or the SDWA Secondary Drinking Water Standards (SDWS). If a constituent does not have a drinking water standard, the Flag 2 criterion equals 10 times the method detection limit (MDL) calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 1 criteria for constituents equal one-half of the final PDWS, one-half the proposed PDWS, or one-half the SDWS. If a constituent does not have a drinking water standard, the Flag 1 criterion equals 5 times the MDL calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 0 criteria are assigned to constituent levels below Flag 1 criteria, constituent levels below the sample detection limits, or constituents having no flagging criteria.

The following parameters are exceptions to the flagging rules:

- EPD/EMS sets flagging criteria for pH and specific conductance. No flags are set for alkalinity, calcium, carbonate, magnesium, potassium, silica, sodium, total dissolved solids, total phosphates (as P), and total phosphorus. Analyses for these parameters are conducted as part of the biennial comprehensive analyses or by special request.
- Aesthetic parameters such as color, corrosivity, Eh, odor, surfactants, and turbidity are not assigned flagging criteria but are analyzed by special request.
- Common laboratory contaminants and cleaners such as dichloromethane (methylene chloride), ketones, phthalates, and toluene are not assigned flagging criteria unless they have primary drinking water standards. These constituents are analyzed by special request.

Analyte	Unit	Flag 1	Flag 2	Source ^a
Acenaphthene	µg/L	50	100	EPA Method 8270
Acenaphthylene	µg/L	50	100	EPA Method 8270
Acetone	µg/L	500	1,000	EPA Method 8240
Acetonitrile (Methyl cyanide)	µg/L	500	1,000	EPA Method 8240
Acetophenone	µg/L	50	100	EPA Method 8270
2-Acetylaminofluorene	µg/L	50	100	EPA Method 8270
Acrolein	µg/L	100	200	EPA Method 8240
Acrylonitrile	µg/L	100	200	EPA Method 8240
Actinium-228	pCi/L	1.64E+03	3.27E+03	Proposed PDWS (EPA, 1991)
Alachlor	µg/L	1	2	Final PDWS (EPA, 1993a)
Aldicarb ^b	µg/L	1.5	3	Final PDWS (EPA, 1993a)
Aldicarb sulfone ^b	µg/L	1	2	Final PDWS (EPA, 1993a)
Aldicarb sulfoxide ^b	µg/L	2	4	Final PDWS (EPA, 1993a)
Aldrin	µg/L	0.25	0.5	EPA Method 8080
Alkalinity (as CaCO ₃)		No flag	No flag	Set by EPD/EMS
Allyl chloride	µg/L	250	500	EPA Method 8240
Aluminum	µg/L	25	50	SDWS (EPA, 1993b)
Aluminum, dissolved	µg/L	25	50	SDWS (EPA, 1993b)
Aluminum, total recoverable	µg/L	25	50	SDWS (EPA, 1993b)

Analyte	Unit	Flag 1	Flag 2	Source
Americium-241	pCi/L	3.17E+00	6.34E+00	Proposed PDWS (EPA, 1991)
Americium-243	pCi/L	3.19E+00	6.37E+00	Proposed PDWS (EPA, 1991)
4-Aminobiphenyl	µg/L	50	100	EPA Method 8270
Ammonia	µg/L	500	1,000	APHA Method 417B
Ammonia nitrogen	µg/L	500	1,000	EPA Method 350.1
Aniline	µg/L	50	100	EPA Method 8270
Anthracene	µg/L	50	100	EPA Method 8270
Antimony	µg/L	3	6	Final PDWS (EPA, 1993a)
Antimony, dissolved	µg/L	3	6	Final PDWS (EPA, 1993a)
Antimony, total recoverable	µg/L	3	6	Final PDWS (EPA, 1993a)
Antimony-125	pCi/L	1.5E+02	3E+02	Interim Final PDWS (EPA, 1977)
Aramite	µg/L	50	100	EPA Method 8270
Arsenic	µg/L	25	50	Final PDWS (EPA, 1993a)
Arsenic, dissolved	µg/L	25	50	Final PDWS (EPA, 1993a)
Arsenic, total recoverable	µg/L	25	50	Final PDWS (EPA, 1993a)
Asbestos	Fibers/L	3,500,000	7,000,000	Final PDWS (EPA, 1993a)
Atrazine	µg/L	1.5	3	Final PDWS (EPA, 1993a)
Azobenzene	µg/L	50	100	EPA Method 625
Barium	µg/L	1,000	2,000	Final PDWS (EPA, 1993a)
Barium, dissolved	µg/L	1,000	2,000	Final PDWS (EPA, 1993a)
Barium, total recoverable	µg/L	1,000	2,000	Final PDWS (EPA, 1993a)
Barium-140 ^C	pCi/L	4.5E+01	9E+01	Interim Final PDWS (EPA, 1977)
Benzene	µg/L	2.5	5	Final PDWS (EPA, 1993a)
alpha-Benzene hexachloride	µg/L	0.25	0.5	EPA Method 8080
beta-Benzene hexachloride	µg/L	0.25	0.5	EPA Method 8080
delta-Benzene hexachloride	µg/L	0.25	0.5	EPA Method 8080
Benzidine	µg/L	250	500	EPA Method 8270
Benzo[a]anthracene	µg/L	0.05	0.1	Proposed PDWS (EPA, 1990)
Benzo[b]fluoranthene	µg/L	0.1	0.2	Proposed PDWS (EPA, 1990)
Benzo[k]fluoranthene	µg/L	0.1	0.2	Proposed PDWS (EPA, 1990)
Benzoic acid	µg/L	250	500	EPA Method 8270
Benzo[g,h,i]perylene	µg/L	50	100	EPA Method 8270
Benzo[a]pyrene	µg/L	0.1	0.2	Final PDWS (EPA, 1993a)
1,4-Benzoquinone	µg/L	50	100	EPA Method 8270
Benzyl alcohol	µg/L	50	100	EPA Method 8270
Beryllium	µg/L	2	4	Final PDWS (EPA, 1993a)
Beryllium, dissolved	µg/L	2	4	Final PDWS (EPA, 1993a)
Beryllium, total recoverable	µg/L	2	4	Final PDWS (EPA, 1993a)
Beryllium-7	pCi/L	3E+03	6E+03	Interim Final PDWS (EPA, 1977)
Bis(2-chloroethoxy) methane	µg/L	50	100	EPA Method 8270
Bis(2-chloroethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-chloroisopropyl) ether	µg/L	50	100	EPA Method 8270
Bis(chloromethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-ethylhexyl) phthalate	µg/L	3	6	Final PDWS (EPA, 1993a)
Bismuth-214	pCi/L	9.4E+03	1.89E+04	Proposed PDWS (EPA, 1991)
Boron	µg/L	150	300	EPA Method 6010
Boron, dissolved	µg/L	150	300	EPA Method 6010
Boron, total recoverable	µg/L	150	300	EPA Method 6010
Bromide	µg/L	5,000	10,000	EPA Method 300.0
Bromodichloromethane	µg/L	50	100	Final PDWS (EPA, 1993a)
Bromoform	µg/L	50	100	Final PDWS (EPA, 1993a)
Bromomethane (Methyl bromide)	µg/L	5	10	EPA Method 8240
4-Bromophenyl phenyl ether	µg/L	50	100	EPA Method 8270
Butylbenzyl phthalate		No flag	No flag	Set by EPD/EMS
2-sec-Butyl-4,6-dinitrophenol	µg/L	3.5	7	Final PDWS (EPA, 1993a)

Analyte	Unit	Flag 1	Flag 2	Source
Cadmium	µg/L	2.5	5	Final PDWS (EPA, 1993a)
Cadmium, dissolved	µg/L	2.5	5	Final PDWS (EPA, 1993a)
Cadmium, total recoverable	µg/L	2.5	5	Final PDWS (EPA, 1993a)
Calcium		No flag	No flag	Set by EPD/EMS
Calcium, dissolved		No flag	No flag	Set by EPD/EMS
Calcium, total recoverable		No flag	No flag	Set by EPD/EMS
Carbofuran	µg/L	20	40	Final PDWS (EPA, 1993a)
Carbon-14	pCi/L	1E+03	2E+03	Interim Final PDWS (EPA, 1977)
Carbonate		No flag	No flag	Set by EPD/EMS
Carbon disulfide	µg/L	5	10	EPA Method 8240
Carbon tetrachloride	µg/L	2.5	5	Final PDWS (EPA, 1993a)
Cerium-141 ^c	pCi/L	1.5E+02	3E+02	Interim Final PDWS (EPA, 1977)
Cerium-144	pCi/L	1.31E+02	2.61E+02	Proposed PDWS (EPA, 1991)
Cesium-134 ^d	pCi/L	4.07E+01	8.13E+01	Proposed PDWS (EPA, 1991)
Cesium-137	pCi/L	1E+02	2E+02	Interim Final PDWS (EPA, 1977)
Chlordane	µg/L	1	2	Final PDWS (EPA, 1993a)
Chloride	µg/L	125,000	250,000	SDWS (EPA, 1993b)
4-Chloroaniline	µg/L	50	100	EPA Method 8270
Chlorobenzene	µg/L	50	100	Final PDWS (EPA, 1993a)
Chlorobenzilate	µg/L	50	100	EPA Method 8270
4-Chloro-m-cresol	µg/L	50	100	EPA Method 8270
Chloroethane	µg/L	5	10	EPA Method 8240
Chloroethene (Vinyl chloride)	µg/L	1	2	Final PDWS (EPA, 1993a)
Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
2-Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
Chloroform	µg/L	50	100	Final PDWS (EPA, 1993a)
Chloromethane (Methyl chloride)	µg/L	5	10	EPA Method 8240
2-Chloronaphthalene	µg/L	50	100	EPA Method 8240
2-Chlorophenol	µg/L	50	100	EPA Method 8270
4-Chlorophenyl phenyl ether	µg/L	50	100	EPA Method 8270
Chloroprene	µg/L	1,000	2,000	EPA Method 8240
Chromium	µg/L	50	100	Final PDWS (EPA, 1993a)
Chromium, dissolved	µg/L	50	100	Final PDWS (EPA, 1993a)
Chromium, total recoverable	µg/L	50	100	Final PDWS (EPA, 1993a)
Chromium-51 ^c	pCi/L	3E+03	6E+03	Interim Final PDWS (EPA, 1977)
Chrysene	µg/L	0.1	0.2	Proposed PDWS (EPA, 1990)
Cobalt	µg/L	20	40	EPA Method 6010
Cobalt, dissolved	µg/L	20	40	EPA Method 6010
Cobalt, total recoverable	µg/L	20	40	EPA Method 6010
Cobalt-57	pCi/L	5E+02	1E+03	Interim Final PDWS (EPA, 1977)
Cobalt-58 ^d	pCi/L	4.5E+03	9E+03	Interim Final PDWS (EPA, 1977)
Cobalt-60	pCi/L	5E+01	1E+02	Interim Final PDWS (EPA, 1977)
Color		No flag	No flag	Set by EPD/EMS
Copper	µg/L	500	1,000	Final PDWS (SCDHEC, 1981)
Copper, dissolved	µg/L	500	1,000	Final PDWS (SCDHEC, 1981)
Copper, total recoverable	µg/L	500	1,000	Final PDWS (SCDHEC, 1981)
Corrosivity		No flag	No flag	Set by EPD/EMS
m-Cresol (3-Methylphenol)	µg/L	50	100	EPA Method 8270
o-Cresol (2-Methylphenol)	µg/L	50	100	EPA Method 8270
p-Cresol (4-Methylphenol)	µg/L	50	100	EPA Method 8270
Curium-242	pCi/L	6.65E+01	1.33E+02	Proposed PDWS (EPA, 1991)
Curium-243	pCi/L	4.15E+00	8.3E+00	Proposed PDWS (EPA, 1991)
Curium-243/244 ^e	pCi/L	4.15E+00	8.3E+00	Proposed PDWS (EPA, 1991)
Curium-244	pCi/L	4.92E+00	9.84E+00	Proposed PDWS (EPA, 1991)
Curium-245/246 ^e	pCi/L	3.12E+00	6.23E+00	Proposed PDWS (EPA, 1991)

Analyte	Unit	Flag 1	Flag 2	Source
Curium-246	pCi/L	3.14E+00	6.27E+00	Proposed PDWS (EPA, 1991)
Cyanide	µg/L	100	200	Final PDWS (EPA, 1993a)
Dalapon ^b	µg/L	100	200	Final PDWS (EPA, 1993a)
p,p'-DDD	µg/L	0.5	1	EPA Method 8080
p,p'-DDE	µg/L	0.5	1	EPA Method 8080
p,p'-DDT	µg/L	0.5	1	EPA Method 8080
Diallate	µg/L	50	100	EPA Method 8270
Dibenz[a,h]anthracene	µg/L	0.15	0.3	Proposed PDWS (EPA, 1990)
Dibenzofuran	µg/L	50	100	EPA Method 8270
Dibromochloromethane	µg/L	50	100	Final PDWS (EPA, 1993a)
1,2-Dibromo-3-chloropropane	µg/L	0.1	0.2	Final PDWS (EPA, 1993a)
1,2-Dibromoethane	µg/L	0.025	0.05	Final PDWS (EPA, 1993a)
Dibromomethane (Methylene bromide)	µg/L	5	10	EPA Method 8240
Di-n-butyl phthalate		No flag	No flag	Set by EPD/EMS
1,2-Dichlorobenzene	µg/L	300	600	Final PDWS (EPA, 1993a)
1,3-Dichlorobenzene	µg/L	50	100	EPA Method 8270
1,4-Dichlorobenzene	µg/L	37.5	75	Final PDWS (EPA, 1993a)
3,3'-Dichlorobenzidine	µg/L	50	100	EPA Method 8270
trans-1,4-Dichloro-2-butene	µg/L	150	300	EPA Method 8240
Dichlorodifluoromethane	µg/L	5	10	EPA Method 8240
1,1-Dichloroethane	µg/L	5	10	EPA Method 8240
1,2-Dichloroethane	µg/L	2.5	5	Final PDWS (EPA, 1993a)
1,1-Dichloroethylene	µg/L	3.5	7	Final PDWS (EPA, 1993a)
1,2-Dichloroethylene	µg/L	25	50	Final PDWS (EPA, 1993a)
cis-1,2-Dichloroethylene	µg/L	35	70	Final PDWS (EPA, 1993a)
trans-1,2-Dichloroethylene	µg/L	50	100	Final PDWS (EPA, 1993a)
Dichloromethane (Methylene chloride)	µg/L	2.5	5	Final PDWS (EPA, 1993a)
2,4-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,6-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,4-Dichlorophenoxyacetic acid	µg/L	35	70	Final PDWS (EPA, 1993a)
1,2-Dichloropropane	µg/L	2.5	5	Final PDWS (EPA, 1993a)
cis-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
trans-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
Dieldrin	µg/L	2.5	5	EPA Method 8080
Di(2-ethylhexyl) adipate	µg/L	200	400	Final PDWS (EPA, 1993a)
Diethyl phthalate		No flag	No flag	Set by EPD/EMS
Dimethoate	µg/L	50	100	EPA Method 8270
p-Dimethylaminoazobenzene	µg/L	50	100	EPA Method 8270
p-(Dimethylamino)ethylbenzene	µg/L	50	100	EPA Method 8270
7,12-Dimethylbenz[a]anthracene	µg/L	50	100	EPA Method 8270
3,3'-Dimethylbenzidine	µg/L	50	100	EPA Method 8270
a,a-Dimethylphenethylamine	µg/L	50	100	EPA Method 8270
2,4-Dimethyl phenol	µg/L	50	100	EPA Method 8270
Dimethyl phthalate		No flag	No flag	Set by EPD/EMS
1,3-Dinitrobenzene	µg/L	50	100	EPA Method 8270
2,4-Dinitrophenol	µg/L	250	500	EPA Method 8270
2,4-Dinitrotoluene	µg/L	50	100	EPA Method 8270
2,6-Dinitrotoluene	µg/L	50	100	EPA Method 8270
Di-n-octyl phthalate		No flag	No flag	Set by EPD/EMS
1,4-Dioxane	µg/L	50	100	EPA Method 8270
Diphenylamine	µg/L	50	100	EPA Method 8270
1,2-Diphenylhydrazine	µg/L	50	100	EPA Method 8270
Diquat dibromide ^b	µg/L	10	20	Final PDWS (EPA, 1993a)

Analyte	Unit	Flag 1	Flag 2	Source
Dissolved organic carbon	µg/L	5,000	10,000	EPA Method 9060
Disulfoton	µg/L	50	100	EPA Method 8270
Eh		No flag	No flag	Set by EPD/EMS
Endosulfan I	µg/L	0.5	1	EPA Method 8080
Endosulfan II	µg/L	0.5	1	EPA Method 8080
Endosulfan sulfate	µg/L	0.5	1	EPA Method 8080
Endothall ^b	µg/L	50	100	Final PDWS (EPA, 1993a)
Endrin	µg/L	1	2	Final PDWS (EPA, 1993a)
Endrin aldehyde	µg/L	0.5	1	EPA Method 8080
Endrin ketone		No flag	No flag	Set by EPD/EMS
Ethylbenzene	µg/L	350	700	Final PDWS (EPA, 1993a)
Ethyl methacrylate	µg/L	50	100	EPA Method 8270
Ethyl methanesulfonate	µg/L	50	100	EPA Method 8270
Europium-152	pCi/L	3E+01	6E+01	Interim Final PDWS (EPA, 1977)
Europium-154	pCi/L	1E+02	2E+02	Interim Final PDWS (EPA, 1977)
Europium-155	pCi/L	3E+02	6E+02	Interim Final PDWS (EPA, 1977)
Famphur	µg/L	50	100	EPA Method 8270
Fluoranthene	µg/L	50	100	EPA Method 8270
Fluorene	µg/L	50	100	EPA Method 8270
Fluoride	µg/L	2,000	4,000	Final PDWS (EPA, 1993a)
Glyphosate ^b	µg/L	350	700	Final PDWS (EPA, 1993a)
Gross alpha	pCi/L	7.5E+00	1.5E+01	Final PDWS (EPA, 1993a)
Heptachlor	µg/L	0.2	0.4	Final PDWS (EPA, 1993a)
Heptachlor epoxide	µg/L	0.1	0.2	Final PDWS (EPA, 1993a)
Heptachlorodibenzo-p-dioxin isomers	µg/L	0.00325	0.0065	EPA Method 8280
1,2,3,4,6,7,8-HPCDD	µg/L	0.00325	0.0065	EPA Method 8280
Heptachlorodibenzo-p-furan isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,6,7,8-HPCDF	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorobenzene	µg/L	0.5	1	Final PDWS (EPA, 1993a)
Hexachlorobutadiene	µg/L	50	100	EPA Method 8270
Hexachlorocyclopentadiene	µg/L	25	50	Final PDWS (EPA, 1993a)
Hexachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,7,8-HXCDD	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280
1,2,3,4,7,8-HXCDF	µg/L	0.002	0.004	EPA Method 8280
Hexachloroethane	µg/L	50	100	EPA Method 8270
Hexachlorophene	µg/L	250	500	EPA Method 8270
Hexachloropropene	µg/L	50	100	EPA Method 8270
2-Hexanone	µg/L	50	100	EPA Method 8240
Indeno[1,2,3-c,d]pyrene	µg/L	50	100	EPA Method 8270
Iodine	µg/L	250	500	APHA Method 415A
Iodine-129	pCi/L	5E-01	1E+00	Interim Final PDWS (EPA, 1977)
Iodine-131 ^c	pCi/L	1.5E+00	3E+00	Interim Final PDWS (EPA, 1977)
Iodomethane (Methyl iodide)	µg/L	75	150	EPA Method 8240
Iron	µg/L	150	300	SDWS (EPA, 1993b)
Iron, dissolved	µg/L	150	300	SDWS (EPA, 1993b)
Iron, total recoverable	µg/L	150	300	SDWS (EPA, 1993b)
Iron-55 ^c	pCi/L	1E+03	2E+03	Interim Final PDWS (EPA, 1977)
Iron-59 ^c	pCi/L	1E+02	2E+02	Interim Final PDWS (EPA, 1977)
Isobutyl alcohol	µg/L	500	1,000	EPA Method 8240
Isodrin	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
Isophorone	µg/L	50	100	EPA Method 8270
Isosafrole	µg/L	50	100	EPA Method 8270
Kepone	µg/L	50	100	EPA Method 8270
Lanthanum-140 ^c	pCi/L	3E+01	6E+01	Interim Final PDWS (EPA, 1977)
Lead	µg/L	25	50	Final PDWS (SCDHEC, 1981)
Lead, dissolved	µg/L	25	50	Final PDWS (SCDHEC, 1981)
Lead, total recoverable	µg/L	25	50	Final PDWS (SCDHEC, 1981)
Lead-212	pCi/L	6.2E+01	1.23E+02	Proposed PDWS (EPA, 1991)
Lindane	µg/L	0.1	0.2	Final PDWS (EPA, 1993a)
Lithium	µg/L	25	50	EPA Method 6010
Lithium, dissolved	µg/L	25	50	EPA Method 6010
Lithium, total recoverable	µg/L	25	50	EPA Method 6010
Magnesium		No flag	No flag	Set by EPD/EMS
Magnesium, dissolved		No flag	No flag	Set by EPD/EMS
Magnesium, total recoverable		No flag	No flag	Set by EPD/EMS
Manganese	µg/L	25	50	SDWS (EPA, 1993b)
Manganese, dissolved	µg/L	25	50	SDWS (EPA, 1993b)
Manganese, total recoverable	µg/L	25	50	SDWS (EPA, 1993b)
Manganese-54	pCi/L	1.5E+02	3E+02	Interim Final PDWS (EPA, 1977)
Mercury	µg/L	1	2	Final PDWS (EPA, 1993a)
Mercury, dissolved	µg/L	1	2	Final PDWS (EPA, 1993a)
Mercury, total recoverable	µg/L	1	2	Final PDWS (EPA, 1993a)
Methacrylonitrile	µg/L	250	500	EPA Method 8240
Methapyrilene	µg/L	50	100	EPA Method 8270
Methoxychlor	µg/L	20	40	Final PDWS (EPA, 1993a)
3-Methylcholanthrene	µg/L	50	100	EPA Method 8270
2-Methyl-4,6-dinitrophenol	µg/L	250	500	EPA Method 8270
Methyl ethyl ketone		No flag	No flag	Set by EPD/EMS
Methyl isobutyl ketone		No flag	No flag	Set by EPD/EMS
Methyl methacrylate	µg/L	50	100	EPA Method 8270
Methyl methanesulfonate	µg/L	50	100	EPA Method 8270
2-Methylnaphthalene	µg/L	50	100	EPA Method 8270
Molybdenum	µg/L	250	500	EPA Method 6010
Molybdenum, dissolved	µg/L	250	500	EPA Method 6010
Molybdenum, total recoverable	µg/L	250	500	EPA Method 6010
Naphthalene	µg/L	50	100	EPA Method 8270
1,4-Naphthoquinone	µg/L	50	100	EPA Method 8270
1-Naphthylamine	µg/L	50	100	EPA Method 8270
2-Naphthylamine	µg/L	50	100	EPA Method 8270
Neptunium-237	pCi/L	3.53E+00	7.06E+00	Proposed PDWS (EPA, 1991)
Nickel	µg/L	50	100	Final PDWS (EPA, 1993a)
Nickel, dissolved	µg/L	50	100	Final PDWS (EPA, 1993a)
Nickel, total recoverable	µg/L	50	100	Final PDWS (EPA, 1993a)
Nickel-59 ^c	pCi/L	1.5E+02	3E+02	Interim Final PDWS (EPA, 1977)
Nickel-63 ^c	pCi/L	2.5E+01	5E+01	Interim Final PDWS (EPA, 1977)
Niobium-95 ^c	pCi/L	1.5E+02	3.E+02	Interim Final PDWS (EPA, 1977)
Nitrate as nitrogen	µg/L	5,000	10,000	Final PDWS (EPA, 1993a)
Nitrate-nitrite as nitrogen	µg/L	5,000	10,000	Final PDWS (EPA, 1993a)
Nitrite as nitrogen	µg/L	500	1,000	Final PDWS (EPA, 1993a)
m-Nitroaniline	µg/L	50	100	EPA Method 8270
o-Nitroaniline	µg/L	50	100	EPA Method 8270
p-Nitroaniline	µg/L	50	100	EPA Method 8270
Nitrobenzene	µg/L	50	100	EPA Method 8270
Nitrogen by Kjeldahl method	µg/L	500	1,000	EPA Method 351.2
2-Nitrophenol	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
4-Nitrophenol	µg/L	50	100	EPA Method 8270
4-Nitroquinoline-1-oxide	µg/L	50	100	EPA Method 8270
N-Nitrosodi-n-butylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodiethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodimethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodiphenylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodipropylamine	µg/L	50	100	EPA Method 8270
N-Nitrosomethylethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosomorpholine	µg/L	50	100	EPA Method 8270
N-Nitrosopiperidine	µg/L	50	100	EPA Method 8270
N-Nitrosopyrrolidine	µg/L	50	100	EPA Method 8270
5-Nitro-o-toluidine	µg/L	50	100	EPA Method 8270
Nonvolatile beta	pCi/L	2.5E+01	5E+01	Interim Final PDWS (EPA, 1977)
Octachlorodibenzo-p-dioxin isomers	µg/L	0.005	0.01	EPA Method 8280
Octachlorodibenzo-p-furan isomers	µg/L	0.005	0.01	EPA Method 8280
Odor		No flag	No flag	Set by EPD/EMS
Oil & Grease	µg/L	5,000	10,000	EPA Method 413.1
Oxamyl ^b	µg/L	100	200	Final PDWS (EPA, 1993a)
Parathion	µg/L	0.25	0.5	EPA Method 8080
Parathion methyl	µg/L	0.25	0.5	EPA Method 8080
PCB 1016	µg/L	0.25	0.5	Final PDWS (EPA, 1993a)
PCB 1221	µg/L	0.25	0.5	Final PDWS (EPA, 1993a)
PCB 1232	µg/L	0.25	0.5	Final PDWS (EPA, 1993a)
PCB 1242	µg/L	0.25	0.5	Final PDWS (EPA, 1993a)
PCB 1248	µg/L	0.25	0.5	Final PDWS (EPA, 1993a)
PCB 1254	µg/L	0.25	0.5	Final PDWS (EPA, 1993a)
PCB 1260	µg/L	0.25	0.5	Final PDWS (EPA, 1993a)
PCB 1262	µg/L	0.25	0.5	Final PDWS (EPA, 1993a)
Pentachlorobenzene	µg/L	50	100	EPA Method 8270
Pentachlorodibenzo-p-dioxin isomers	µg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-PCDD	µg/L	0.00275	0.0055	EPA Method 8280
Pentachlorodibenzo-p-furan isomers	µg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-PCDF	µg/L	0.00275	0.0055	EPA Method 8280
Pentachloroethane	µg/L	50	100	EPA Method 8270
Pentachloronitrobenzene	µg/L	50	100	EPA Method 8270
Pentachlorophenol	µg/L	0.5	1	Final PDWS (EPA, 1993a)
pH	pH	8	10	Set by EPD/EMS
pH	pH	4	3	Set by EPD/EMS
Phenacetin	µg/L	50	100	EPA Method 8270
Phenanthrene	µg/L	50	100	EPA Method 8270
Phenol	µg/L	50	100	EPA Method 8270
Phenols	µg/L	25	50	EPA Method 420.1
p-Phenylenediamine	µg/L	50	100	EPA Method 8270
Phorate	µg/L	0.5	1	EPA Method 8080
Picloram ^b	µg/L	250	500	Final PDWS (EPA, 1993a)
2-Picoline	µg/L	50	100	EPA Method 8270
Plutonium-238	pCi/L	3.51E+00	7.02E+00	Proposed PDWS (EPA, 1991)
Plutonium-239	pCi/L	3.11E+01	6.21E+01	Proposed PDWS (EPA, 1991)
Plutonium-239/240 ^e	pCi/L	3.11E+01	6.21E+01	Proposed PDWS (EPA, 1991)
Plutonium-240	pCi/L	3.11E+01	6.22E+01	Proposed PDWS (EPA, 1991)
Plutonium-241 ^c	pCi/L	3.13E+01	6.26E+01	Proposed PDWS (EPA, 1991)

Analyte	Unit	Flag 1	Flag 2	Source
Plutonium-242 ^C	pCi/L	3.27E+01	6.54E+01	Proposed PDWS (EPA, 1991)
Potassium		No flag	No flag	Set by EPD/EMS
Potassium, dissolved		No flag	No flag	Set by EPD/EMS
Potassium, total recoverable		No flag	No flag	Set by EPD/EMS
Potassium-40	pCi/L	1.5E+02	3E+02	Proposed PDWS (EPA, 1986)
Promethium-144	pCi/L	5E+01	1E+02	EPA Method 901.1
Promethium-146	pCi/L	5E+01	1E+02	EPA Method 901.1
Promethium-147	pCi/L	2.62E+03	5.24E+03	Proposed PDWS (EPA, 1991)
Pronamid	µg/L	50	100	EPA Method 8270
Propionitrile	µg/L	1,000	2,000	EPA Method 8240
Pyrene	µg/L	50	100	EPA Method 8270
Pyridine	µg/L	50	100	EPA Method 8270
Radium (alpha-emitting) ^f	pCi/L	1E+01	2E+01	Proposed PDWS (EPA, 1991)
Radium-226	pCi/L	1E+01	2E+01	Proposed PDWS (EPA, 1991)
Radium-228	pCi/L	1E+01	2E+01	Proposed PDWS (EPA, 1991)
Radon-222	pCi/L	1.5E+02	3E+02	Proposed PDWS (EPA, 1991)
Ruthenium-103 ^C	pCi/L	1E+02	2E+02	Interim Final PDWS (EPA, 1977)
Ruthenium-106	pCi/L	1.5E+01	3E+01	Interim Final PDWS (EPA, 1977)
Safrole	µg/L	50	100	EPA Method 8270
Selenium	µg/L	25	50	Final PDWS (EPA, 1993a)
Selenium, dissolved	µg/L	25	50	Final PDWS (EPA, 1993a)
Selenium, total recoverable	µg/L	25	50	Final PDWS (EPA, 1993a)
Silica		No flag	No flag	Set by EPD/EMS
Silica, dissolved		No flag	No flag	Set by EPD/EMS
Silica, total recoverable		No flag	No flag	Set by EPD/EMS
Silver	µg/L	50	100	SDWS (EPA, 1993b)
Silver, dissolved	µg/L	50	100	SDWS (EPA, 1993b)
Silver, total recoverable	µg/L	50	100	SDWS (EPA, 1993b)
Simazine ^b	µg/L	2	4	Final PDWS (EPA, 1993a)
Sodium		No flag	No flag	Set by EPD/EMS
Sodium, dissolved		No flag	No flag	Set by EPD/EMS
Sodium, total recoverable		No flag	No flag	Set by EPD/EMS
Sodium-22	pCi/L	2.33E+02	4.66E+02	Proposed PDWS (EPA, 1991)
Specific conductance	µS/cm	250	500	Set by EPD/EMS
Strontium-89	pCi/L	1E+01	2E+01	Interim Final PDWS (EPA, 1977)
Strontium-89/90 ^e	pCi/L	4E+00	8E+00	Final PDWS (EPA, 1993a)
Strontium-90	pCi/L	4E+00	8E+00	Final PDWS (EPA, 1993a)
Styrene	µg/L	50	100	Final PDWS (EPA, 1993a)
Sulfate	µg/L	200,000	400,000	Proposed PDWS (EPA, 1990)
Sulfide	µg/L	5,000	10,000	EPA Method 9030
Sulfotep	µg/L	50	100	EPA Method 8270
Surfactants		No flag	No flag	Set by EPD/EMS
2,3,7,8-TCDD	µg/L	0.000015	0.00003	Final PDWS (EPA, 1993a)
2,3,7,8-TCDF	µg/L	0.002	0.004	EPA Method 8280
Technetium-99	pCi/L	4.5E+02	9E+02	Interim Final PDWS (EPA, 1977)
1,2,4,5-Tetrachlorobenzene	µg/L	50	100	EPA Method 8270
Tetrachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
Tetrachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280
1,1,1,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
1,1,2,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
Tetrachloroethylene	µg/L	2.5	5	Final PDWS (EPA, 1993a)
2,3,4,6-Tetrachlorophenol	µg/L	50	100	EPA Method 8270
Thallium	µg/L	1	2	Final PDWS (EPA, 1993a)

Analyte	Unit	Flag 1	Flag 2	Source
Thallium, dissolved	µg/L	1	2	Final PDWS (EPA, 1993a)
Thallium, total recoverable	µg/L	1	2	Final PDWS (EPA, 1993a)
Thionazin	µg/L	50	100	EPA Method 8270
Thorium-228	pCi/L	6.25E+01	1.25E+02	Proposed PDWS (EPA, 1991)
Thorium-230	pCi/L	3.96E+01	7.92E+01	Proposed PDWS (EPA, 1991)
Thorium-232	pCi/L	4.4E+01	8.8E+01	Proposed PDWS (EPA, 1991)
Thorium-234	pCi/L	2E+02	4.01E+02	Proposed PDWS (EPA, 1991)
Tin	µg/L	10	20	EPA Method 282.2
Tin, dissolved	µg/L	10	20	EPA Method 282.2
Tin, total recoverable	µg/L	10	20	EPA Method 282.2
Tin-113 ^c	pCi/L	1.5E+02	3E+02	Interim Final PDWS (EPA, 1977)
Toluene	µg/L	500	1,000	Final PDWS (EPA, 1993a)
o-Toluidine	µg/L	50	100	EPA Method 8270
Total carbon	µg/L	5,000	10,000	EPA Method 9060
Total coliform		0	0	Final PDWS (EPA, 1993a)
Total dissolved solids		No flag	No flag	Set by EPD/EMS
Total hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total inorganic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic halogens	µg/L	25	50	EPA Method 9020
Total organic nitrogen	µg/L	500	1,000	APHA Method 420
Total petroleum hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total phosphates (as P)		No flag	No flag	Set by EPD/EMS
Total phosphorus		No flag	No flag	Set by EPD/EMS
Toxaphene	µg/L	1.5	3	Final PDWS (EPA, 1993a)
2,4,5-TP (Silvex)	µg/L	25	50	Final PDWS (EPA, 1993a)
Tributyl phosphate	µg/L	50	100	EPA Method 8270
1,2,4-Trichlorobenzene	µg/L	35	70	Final PDWS (EPA, 1993a)
1,1,1-Trichloroethane	µg/L	100	200	Final PDWS (EPA, 1993a)
1,1,2-Trichloroethane	µg/L	2.5	5	Final PDWS (EPA, 1993a)
Trichloroethylene	µg/L	2.5	5	Final PDWS (EPA, 1993a)
Trichlorofluoromethane	µg/L	5	10	EPA Method 8240
2,4,5-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,6-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,5-Trichlorophenoxyacetic acid	µg/L	2.5	5	EPA Method 8150
1,2,3-Trichloropropane	µg/L	5	10	EPA Method 8240
O,O,O-Triethyl phosphorothioate	µg/L	50	100	EPA Method 8270
1,3,5-Trinitrobenzene	µg/L	50	100	EPA Method 8270
Tritium	pCi/mL	1E+01	2E+01	Final PDWS (EPA, 1993a)
Turbidity ^g		No flag	No flag	Set by EPD/EMS
Uranium	µg/L	10	20	Proposed PDWS (EPA, 1991)
Uranium, dissolved	µg/L	10	20	Proposed PDWS (EPA, 1991)
Uranium, total recoverable	µg/L	10	20	Proposed PDWS (EPA, 1991)
Uranium alpha activity	pCi/L	1.5E+01	3E+01	Proposed PDWS (EPA, 1991)
Uranium-233/234 ^e	pCi/L	6.9E+00	1.38E+01	Proposed PDWS (EPA, 1991)
Uranium-234	pCi/L	6.95E+00	1.39E+01	Proposed PDWS (EPA, 1991)
Uranium-235	pCi/L	7.25E+00	1.45E+01	Proposed PDWS (EPA, 1991)
Uranium-238	pCi/L	7.3E+00	1.46E+01	Proposed PDWS (EPA, 1991)
Vanadium	µg/L	40	80	EPA Method 6010
Vanadium, dissolved	µg/L	40	80	EPA Method 6010
Vanadium, total recoverable	µg/L	40	80	EPA Method 6010
Vinyl acetate	µg/L	5	10	EPA Method 8240

<u>Analyte</u>	<u>Unit</u>	<u>Flag 1</u>	<u>Flag 2</u>	<u>Source</u>
Xylenes	µg/L	5,000	10,000	Final PDWS (EPA, 1993a)
Yttrium-88	pCi/L	5E+01	1E+02	EPA Method 901.1
Zinc	µg/L	2,500	5,000	SDWS (EPA, 1993b)
Zinc, dissolved	µg/L	2,500	5,000	SDWS (EPA, 1993b)
Zinc, total recoverable	µg/L	2,500	5,000	SDWS (EPA, 1993b)
Zinc-65	pCi/L	1.5E+02	3E+02	Interim Final PDWS (EPA, 1977)
Zirconium-95 ^c	pCi/L	1E+02	2E+02	Interim Final PDWS (EPA, 1977)
Zirconium/Niobium-95 ^c	pCi/L	1E+02	2E+02	Interim Final PDWS (EPA, 1977)

- ^a References for methods are in Appendix E; references for dated sources are at the end of this appendix.
- ^b EMS is currently unable to perform this analysis.
- ^c EMS discontinued monitoring this radionuclide because it is inappropriate for the SRS Groundwater Monitoring Program.
- ^d EPD/EMS set this flagging criterion using the 1991 proposed PDWS because the final PDWS in 1977 may have been in error.
- ^e For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.
- ^f The applied standard is for radium-226.
- ^g The primary maximum contaminant level range for turbidity is 1–5 NTU, which is inappropriate for the SRS Groundwater Monitoring Program.

References Cited

EPA (U.S. Environmental Protection Agency), 1977. **National Interim Primary Drinking Water Regulations**, EPA-570/9-76-003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1986. *Water Pollution Control; National Primary Drinking Water Regulations, Radionuclides (Proposed)*. **Federal Register**, September 30, 1986, pp. 34835–34862. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. *National Primary and Secondary Drinking Water Regulations; Synthetic Organic Chemicals and Inorganic Chemicals (Proposed Rule)*. **Federal Register**, July 25, 1990, pp. 30369–30448. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. *National Primary Drinking Water Regulations; Radionuclides; Proposed Rule*. **Federal Register**, July 18, 1991, pp. 33052–33127. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1993a. *National Primary Drinking Water Regulations*. **Code of Federal Regulations**, Title 40, Part 141, pp. 592–732. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1993b. *National Secondary Drinking Water Regulations*. **Code of Federal Regulations**, Title 40, Part 143, pp. 774–777. Washington, DC.

SCDHEC (South Carolina Department of Health and Environmental Control), 1981. **State Primary Drinking Water Regulations**, R.61–58.5. Columbia, SC.

Appendix C

Figures

THIS PAGE LEFT BLANK INTENTIONALLY.

Figure 1. Location of the M-Area HWMF at the Savannah River Site

Figure 2. Location of the M-Area HWMF within A/M Areas and Location of the Point-of-Compliance Wells at the M-Area HWMF

Figure 3. Location of the Plume Definition and Background Wells at the M-Area HWMF

Figure 4. Location of the Recovery Wells at the M-Area HWMF

Figure 5. Water-Elevation Differences, M-Area Aquifer Zone, First Quarter 1985 to First Quarter 1995

Figure 6. Water-Elevation Differences, Upper Lost Lake Aquifer Zone, First Quarter 1985 to First Quarter 1995

Figure 8. Water-Elevation Differences, Middle Sand Aquifer Zone of the CBCU, First Quarter 1985 to First Quarter 1995

M-Area HMMF

C-11

First Quarter 1995

Well RWM 1

Figure 9. Average Monthly Influent Concentrations vs. Time for RWM 1

M-Area HWMF

C-12

First Quarter 1995

Well RWM 2

Figure 10. Average Monthly Influent Concentrations vs. Time for RWM 2

Well RWM 3

M-Area HWMF

CONCENTRATION (µg/L)
C-13

First Quarter 1995

Figure 11. Average Monthly Influent Concentrations vs. Time for RWM 3

Well RWM 6

WSRC-TR-95-0138-1
Unclassified

ns vs. Time for RWM 6

WSRC-TR-95-0138-1
Unclassified

DETHYLENE --■-- TRICHLOROETHYLENE —■— TOTAL

Well RWM 4

Figure 12. Average Monthly Influent Concentrations vs. Time for RWM 4

Well RWM 5

Figure 13. Average Monthly Influent Concentrations vs. Time for RWM 5

Figure 14. Average Monthly Influent Concentrations vs. Time for RWM 6

M-Area HWMF

C-17

First Quarter 1995

Well RWM 7

Figure 15. Average Monthly Influent Concentrations vs. Time for RWM 7

WSRC-TR-95-0138-1
Unclassified

Well RWM 8

Figure 16. Average Monthly Influent Concentrations vs. Time for RWM 8

Well RWM 9

Figure 17. Average Monthly Influent Concentrations vs. Time for RWM 9

Well RWM 10

Figure 18. Average Monthly Influent Concentrations vs. Time for RWM 10

M-Area HMMF

C-21

First Quarter 1995

Well RWM 11

Figure 19. Average Monthly Influent Concentrations vs. Time for RWM 11

M-Area HWMF

C-22

First Quarter 1995

Well RWM 12

Figure 20. Average Monthly Influent Concentrations vs. Time for RWM 12

WSRC-TR-95-0138-1
Unclassified

M-1 Air Stripper

Figure 21. Average Monthly Influent Concentrations vs. Time for the M-1 Air Stripper

M-Area HWM/F

C-24

First Quarter 1995

A-1 Air Stripper

Figure 22. Average Monthly Influent Concentrations vs. Time for the A-1 Air Stripper

WSRC-TR-95-0138-1
Unclassified

Appendix D

Monitoring Results Tables

THIS PAGE LEFT BLANK INTENTIONALLY.

Key to Reading the Tables

The following abbreviations may appear in the data tables:

Constituents

PCB	polychlorinated biphenyl
Sp. conductance	specific conductance

Laboratories

CN	Clemson Technical Center, Inc.
EM	Environmental Protection Department/Environmental Monitoring Section (EPD/EMS) Laboratory
GE and GP	General Engineering Laboratories
SC	Savannah River Technology Center
SP	Spencer Testing Services, Inc.
TM	TMA/Eberline
WA and WS	Roy F. Weston, Inc.

Miscellaneous

CS	carbon steel
DF	dilution factor column in data tables
H	holding time column in data tables
Mod	modifier column in data tables
PDWS	primary drinking water standard
PVC	polyvinyl chloride
ST	exceeded standard column in data tables
SZ	screen zone column in data tables
TOC	top of casing

Nomenclature

AZ	Aquifer Zone
Crouch Branch AZ	previously Black Creek
• CBA	Crouch Branch Aquifer
• CBC or CBCU	Crouch Branch Confining Unit
• LCBC	Lost Lake AZ - CBCU
CZ	Confining Zone
Lower Lost Lake AZ	previously Lower Congaree
• L	Lost Lake (Undifferentiated) AZ
• LL	Lower Lost Lake AZ
• (LL)L/MCBC	Lower Lost Lake/Middle Sand AZ of the CBCU
M-Area AZ	previously Water Table
• GC	Green Clay CZ
• GCL	Green Clay - Lost Lake
• M	M-Area AZ
• MGC	M-Area AZ - Green Clay CZ

Nomenclature (cont.)

Middle Sand AZ of the CBCU	previously Ellenton Sand
• MCBC	Middle Sand AZ of the CBCU
Upper Lost Lake AZ	previously Upper Congaree
• UL	Upper Lost Lake AZ
Miscellaneous Nomenclature	
• MGCL	M-Area AZ - Green Clay CZ - Lost Lake AZ
• UD	Undifferentiated
• VZ	Vadose Zone

Sampling Codes

B	blank sample was collected
C	well was pumping continuously
D	well was dry
E	equipment blank was collected
I	well went dry during sampling; insufficient water to collect all samples
L	well went dry before sampling began; only depth to water can be determined
P	inaccessibility or mechanical failure prevented sample collection and field analysis of the water
S	no water in standpipe; for water level events only
X	well went dry during purging; samples collected after well recovered

Sampling Methods

B	sample collected using an open-bucket bailer
P	sample collected using a bladder pump
S	sample collected using a single-speed centrifugal downhole pump
V	sample collected using a variable-speed pump

Units

E	exponential notation (e.g., $1.1\text{E}-09 = 1.1 \times 10^{-9} = 0.000000011$)
mg/L	milligrams per liter
msl	mean sea level
MSL	million structures per liter
NTU	nephelometric turbidity unit
pCi/L	picocuries per liter
pCi/mL	picocuries per milliliter
pH	pH unit
$\mu\text{g/L}$	micrograms per liter
$\mu\text{S/cm}$	microsiemens per centimeter

Holding Times

Standard analytical methods include a limit, called holding time, on the maximum elapsed time between sample collection and extraction or analysis by the laboratory. In the data tables, a large bullet (•) in the *H* (holding time) column indicates that holding time was exceeded. Analyses performed beyond holding times may not yield valid results.

The South Carolina Department of Health and Environmental Control allows only 15 minutes to elapse between sampling and analysis for pH. Thus, only field pH measurements can meet the holding time criterion; laboratory pH analyses always will exceed it.

The laboratory procedure used for the determination of specific conductance allows one day to elapse between sampling and analysis. Thus, laboratory specific conductance measurements may exceed the holding time criterion.

Data Rounding

Constituent results in analytical results tables that appear to equal the groundwater protection standard, background standard, or drinking water standard but are not marked in the *ST* (exceeded the groundwater protection standard, background standard, or drinking water standard) column are below the standards in the database. Values stored in the database contain more significant digits than the reported results. Apparent discrepancies in the tables are due to the rounding of reported results.

Data Qualification

The contract laboratories continually assess their own accuracy and precision according to U.S. Environmental Protection Agency (EPA) guidelines. They submit sample- or batch-specific quality assurance/quality control information either at the same time as analytical results or in a quarterly summary. Properly defined and used result modifiers (also referred to as qualifiers) can be a key component in assessing data usability. Result modifiers designed by EPD/EMS and provided to the primary laboratories are defined below. These modifiers appear in the data tables under the column *Mod*. The lettered modifiers are based on EPA's STORET codes.

Result Modifiers

(Blank)	Data are not qualified. Numbers should be interpreted exactly as reported.
I	The value in the result field is the instrument reading, not the sample quantification limit. Always used with the result qualifier <i>U</i> .
J	Value is estimated because quantitation in the sample or in associated quality control samples did not meet specifications.
M	Presence of the analyte is verified but not quantified.
R	Result was rejected because performance requirements in the sample analysis or associated quality control analyses were not met.

Result Modifiers (cont.)

T	Analyte was not detected; if present, it was below the criteria for detection.
U	Material analyzed for but not detected. Analytical result reported is less than the sample quantitation limit.
V or VV	Analyte was detected in an associated method blank.
Y	Result was obtained from an unpreserved or improperly preserved sample. Data may not be accurate.
1	Result may be an underestimation of the true value due to analytical bias.
2	Result may be an overestimation of the true value due to analytical bias.
3	The associated result may be of poor precision (high variability) due to analytical bias.
4	Result is associated with QA results indicating matrix interference.
6	The associated result is from a reanalysis performed out of holding time due to problems with an earlier analysis.

Table 1. Synchronous Water Elevations

M-Area Aquifer Zone

<u>Well</u>	<u>SZ^a</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
ABP 1A	GCL	225.8	225.3	225.0	224.9
ABP 1DD	MGC	226.8	227.1	227.3	225.6
ABP 2A	GCL	224.7	224.3	223.8	223.7
ABP 2DD	MGC	224.5	224.1	223.5	223.4
ABP 3	MGC	226.2	225.9	225.3	225.2
ABP 4	MGCL	224.2	224.0	223.4	223.4
ABP 4DD	MGC	225.3	225.0	224.4	224.3
ABP 6D	MGC	224.6	224.1	223.6	223.5
ABP 7D	MGC	225.3	225.0	224.4	224.4
ABP 8D	M	224.2	223.8	223.2	223.1
AC 1B	GCL	214.5	213.9	213.4	214.1
AC 2B	MGC	228.2	227.8	227.5	227.5
AC 3B	M	214.0	213.7	213.1	213.0
ACB 1A	M	238.1	238.1	238.2	238.7
ACB 2A	M	239.4	239.4	239.3	239.8
ACB 3A	M	239.2	239.1	239.0	239.6
ACB 4A	MGC	239.5	239.5	239.7	239.8
AMB 4D	M	233.8	234.0	233.9	234.4
AMB 5	MGCL	234.2	234.3	234.3	234.8
AMB 6	GCL	234.3	234.5	234.5	234.9
AMB 7	M	234.7	234.7	234.8	235.2
AMB 8D	M	234.3	234.4	234.4	234.9
AMB 9D	M	234.6	234.7	234.8	235.3
AMB 10D	M	236.0	236.1	236.2	236.6
AMB 10DD	M	359.1	359.1	359.4	359.2
AMB 11D	M	237.0	236.9	236.9	237.2
AMB 12D	M	235.5	235.5	235.5	235.8
AMB 14D	M	— ^b	—	—	233.7
AMB 15D	M	—	—	—	235.0
AMB 16D	M	—	—	—	234.4
AOB 1	M	237.2	237.1	236.8	237.6
AOB 2	M	237.9	237.8	237.6	238.3
AOB 3	M	238.8	238.8	238.7	239.1
ARP 1A	GCL	228.5	218.2	217.5	217.4
ARP 2	GC	220.8	220.3	219.8	219.7
ARP 3	GCL	223.5	223.1	222.6	222.0
ARP 4	GCL	220.8	220.4	219.9	219.7
ASB 1A	M	237.7	247.8	237.7	238.3
ASB 2A	M	—	—	—	—
ASB 2AR	MGCL	239.2	239.2	239.0	239.7
ASB 3A	M	—	—	—	—
ASB 3AR	MGCL	239.7	239.7	239.5	240.3
ASB 4	M	238.9	238.8	238.6	239.4
ASB 5A	M	—	—	—	—
ASB 5AR	MGCL	237.5	237.4	237.2	237.7
ASB 6A	MGCL	237.3	237.4	237.1	237.8
ASB 7	MGCL	—	—	—	—
ASB 8	GCL	235.6	234.9	234.8	235.0
ASB 9	MGC	242.3	242.3	241.7	242.6
MCB 2	M	226.5	225.9	225.2	225.2
MCB 4	MGCL	226.5	226.2	225.6	225.4

Table 1 (cont.)

M-Area Aquifer Zone (cont.)

Well	SZ	2Q94	3Q94	4Q94	1Q95
MCB 5	MGC	226.8	226.3	225.8	225.7
MCB 6	MGC	213.2	213.4	213.2	220.5
MCB 8D	MGC	227.0	226.8	226.1	226.0
MCB 9D	MGCL	225.2	224.6	224.0	223.8
MSB 1A	M	232.3	—	—	232.1
MSB 1D	MGCL	231.8	231.5	231.3	231.6
MSB 2A	MGC	232.9	163.7	233.4	232.7
MSB 2D	MGCL	232.5	232.1	232.0	232.4
MSB 3A	M	—	—	—	—
MSB 3D	MGC	231.3	230.9	230.8	—
MSB 4A	M	231.6	231.3	231.2	231.3
MSB 4D	M	231.0	230.4	230.5	230.5
MSB 5A	M	—	228.6	228.4	228.4
MSB 6A	M	228.7	228.4	223.6	228.0
MSB 7A	MGC	229.6	229.4	229.0	229.0
MSB 7C	GCL	224.0	223.6	223.5	223.5
MSB 8A	M	230.7	230.5	230.1	230.1
MSB 9B	GCL	231.1	230.8	230.7	230.9
MSB 9C	M	231.1	230.9	230.7	230.9
MSB 10C	GCL	230.3	230.1	230.0	230.2
MSB 10D	M	—	—	—	—
MSB 11D	GC	231.2	231.0	231.1	231.2
MSB 11E	M	239.8	239.8	—	239.8
MSB 11F	M	231.5	231.3	231.2	231.4
MSB 12D	MGC	234.2	234.2	234.1	234.0
MSB 13C	M	230.0	229.8	229.5	229.6
MSB 13CC	GCL	225.8	225.3	225.9	225.7
MSB 13D	MGC	229.5	229.2	229.0	229.1
MSB 14B	GCL	219.0	217.7	219.7	219.0
MSB 14C	M	232.3	232.3	232.1	232.4
MSB 15C	M	243.2	242.8	243.0	245.1
MSB 15D	MGC	233.1	232.8	232.9	233.2
MSB 16C	M	231.3	231.4	231.5	231.7
MSB 17B	GCL	227.1	226.7	226.4	226.4
MSB 17C	M	—	—	—	—
MSB 17D	M	228.1	227.8	227.4	227.5
MSB 18B	GCL	223.3	222.9	222.6	222.6
MSB 18C	MGC	230.6	230.0	228.8	228.5
MSB 19C	M	239.4	238.9	238.8	239.4
MSB 20C	M	228.2	227.9	227.6	227.6
MSB 21C	M	230.2	230.0	229.7	229.8
MSB 22	M	—	231.7	231.7	—
MSB 23	M(VZ)	—	—	—	—
MSB 24	M	234.8	235.2	234.9	235.3
MSB 25	M	—	—	237.2	—
MSB 26	M	237.1	237.0	—	237.6
MSB 27	M	236.1	236.2	235.9	236.3
MSB 27A	MGC	229.4	229.6	229.5	230.2
MSB 28	M	231.1	231.1	230.9	231.2
MSB 29D	MGCL	233.1	233.0	232.8	233.1
MSB 29DD	M	233.5	233.3	233.2	233.4

Table 1 (cont.)

M-Area Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
MSB 30C	M	231.6	231.4	231.2	231.5
MSB 31C	MGC	235.2	235.2	235.0	235.9
MSB 32	MGC	224.8	224.3	224.6	225.6
MSB 33	MGC	218.3	217.6	217.5	219.2
MSB 34C	MGCL	229.9	230.3	230.2	230.8
MSB 35D	M(VZ)	243.5	243.5	243.4	243.5
MSB 36D	M	238.0	237.9	237.9	237.9
MSB 37D	MGC	232.6	232.6	232.4	233.0
MSB 38D	M	234.0	233.9	233.9	234.4
MSB 39D	MGC	233.2	233.0	232.7	232.8
MSB 40D	MGC	228.9	228.5	228.1	227.8
MSB 41D	M	241.0	241.0	241.0	241.0
MSB 42D	MGC	235.2	233.8	233.8	234.2
MSB 43D	MGCL	230.2	232.1	229.8	232.2
MSB 43DD	M	232.5	232.3	230.0	232.1
MSB 44C	MGCL	235.5	235.7	235.8	236.3
MSB 45C	MGC	—	—	—	—
MSB 46C	MGC	236.2	240.4	239.3	240.7
MSB 47D	MGC	234.4	234.3	233.9	234.3
MSB 49D	M	230.3	230.3	229.7	229.5
MSB 50D	M	202.4	201.9	202.2	203.1
MSB 51D	GC	211.3	210.6	210.3	211.2
MSB 51DD	MGC	211.8	—	—	211.6
MSB 52D	M	239.1	239.0	238.6	239.4
MSB 53D	MGC	234.3	234.1	233.9	234.3
MSB 54D	GCL	234.2	233.9	233.7	233.7
MSB 55D	GCL	234.2	233.9	233.6	233.7
MSB 56D	M	220.6	221.2	220.7	222.0
MSB 57D	M	232.5	232.3	232.0	232.4
MSB 58D	M	232.2	232.0	231.9	232.3
MSB 59D	M	231.3	231.0	230.9	231.1
MSB 60D	M	231.6	231.3	231.1	231.3
MSB 61D	GCL	226.8	226.5	226.3	227.0
MSB 62D	M	230.5	230.1	230.0	230.3
MSB 63D	MGC	230.8	230.6	230.2	230.4
MSB 64D	MGC	228.4	228.1	227.8	227.9
MSB 65D	M	234.2	233.9	233.7	234.5
MSB 66D	MGC	231.8	231.8	231.7	232.1
MSB 67D	MGC	233.7	233.6	233.3	233.7
MSB 68D	MGC	234.6	234.5	234.2	234.5
MSB 69D	MGCL	234.2	234.0	233.8	234.0
MSB 70D	M	222.7	222.4	222.0	222.1
MSB 74D	MGCL	233.6	233.3	232.8	231.3
MSB 77D	MGCL	235.1	234.8	234.4	234.7
MSB 78D	MGC	225.4	225.0	224.7	224.9
MSB 82D	MGCL	233.9	233.8	233.5	233.7
MSB 83D	MGCL	234.3	214.1	233.8	233.9
MSB 85D	MGCL	234.0	233.7	233.5	233.6
MSB 88D	MGC	204.7	204.9	205.0	206.3
SRW 1	M	213.7	213.3	212.9	212.7
SRW 2	M	215.7	215.1	214.7	214.5

Table 1 (cont.)

M-Area Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
SRW 3A	GCL	214.8	214.3	213.9	213.9
SRW 4	M	214.4	214.0	213.5	213.5
SRW 5	M	212.6	217.1	211.7	211.6
SRW 6	M	203.3	212.9	212.5	212.4
SRW 7	M	211.8	211.6	211.1	211.0
SRW 8	M	209.6	207.3	208.7	208.8
SRW 9	M	200.2	199.3	198.7	200.5
SRW 9A	MGC	199.8	198.6	198.7	200.4
SRW 9B	M	201.1	200.0	199.6	201.5
SRW 10	M	—	—	—	—
SRW 11	M	211.5	211.1	210.7	210.6
SRW 12A	M	195.0	193.6	193.5	196.4
SRW 12B	M	189.6	187.6	187.9	192.2
SRW 12C	M	196.8	195.2	194.6	199.7
SRW 13C	M	210.8	212.3	209.8	210.0
SRW 14C	M	—	—	—	—
SRW 15C	M	213.9	213.4	213.0	212.8
SRW 16C	MGC	216.6	216.1	215.7	215.8

Upper Lost Lake Aquifer Zone

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
ABP 3C	UL	198.5	198.1	197.7	198.8
ABP 8C	UL	198.5	198.8	198.0	198.6
ABW 1	UL	226.5	226.4	226.3	226.8
AC 1A	UL	214.5	214.0	213.4	214.1
AC 2A	UL	221.8	221.5	221.7	221.9
AC 3A	UL	212.0	211.6	211.1	211.1
AMB 11B	UL	223.6	223.5	223.6	224.4
AMB 18C	UL	—	—	—	234.5
AMB 19C	UL	—	—	—	232.5
ASB 2C	UL	—	—	—	—
ASB 3C	UL	—	—	—	—
ASB 6C	UL	225.4	224.8	224.8	224.8
ASB 8C	UL	223.0	224.1	224.0	224.6
ASB 9C	UL	221.8	221.6	221.4	222.2
ASB 10C	UL	—	—	—	—
MCB 5C	UL	196.6	195.9	195.6	196.5
MCB 6C	UL	196.9	196.4	196.1	197.0
MCB 7C	UL	195.4	194.9	194.6	195.5
MSB 1C	UL	218.5	216.2	219.3	217.5
MSB 1CC	UL	219.7	218.3	220.8	219.5
MSB 2C	UL	219.0	217.7	220.4	219.2
MSB 3C	UL	220.5	219.3	222.2	220.5
MSB 4C	UL	218.9	214.1	219.4	215.4
MSB 5C	UL	224.3	223.8	224.3	224.2
MSB 6C	UL	225.2	224.9	224.7	224.9
MSB 8C	UL	221.4	220.9	221.4	221.3
MSB 11B	UL	218.1	217.5	221.8	218.7

Table 1 (cont.)

Upper Lost Lake Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
MSB 11C	UL	220.2	219.9	224.0	221.2
MSB 12B	UL	219.3	218.7	219.8	215.4
MSB 12C	UL	224.3	223.8	224.6	224.2
MSB 13B	UL	191.2	206.0	214.1	192.8
MSB 15A	UL	220.9	220.5	222.8	221.7
MSB 16A	UL	220.1	220.0	224.0	220.6
MSB 17A	UL	218.0	217.5	218.0	217.9
MSB 18A	UL	214.0	213.4	214.0	213.9
MSB 19B	UL	217.4	216.9	217.4	218.5
MSB 20A	L(UD)	220.0	219.4	219.9	219.7
MSB 23B	UL	223.1	223.2	223.9	225.4
MSB 24A	UL	225.2	225.5	225.9	227.9
MSB 26A	UL	224.6	224.9	225.2	225.0
MSB 27B	UL	225.5	225.7	225.9	227.9
MSB 28A	UL	224.6	224.3	224.9	224.8
MSB 29C	UL	231.5	231.1	230.9	231.2
MSB 30CC	UL	226.0	225.7	226.1	226.2
MSB 31CC	UL	213.9	213.7	214.1	220.8
MSB 32C	UL	216.6	216.3	216.5	218.0
MSB 33C	UL	211.1	210.7	210.9	211.6
MSB 34B	UL	227.2	227.6	227.5	228.2
MSB 35B	UL	220.2	219.9	220.4	221.9
MSB 36C	UL	215.2	214.6	215.4	216.0
MSB 37C	UL	229.0	229.0	228.9	229.4
MSB 39C	UL	216.5	215.7	216.9	216.9
MSB 40C	UL	205.4	204.9	205.0	205.7
MSB 42C	UL	232.0	232.1	232.1	232.6
MSB 43B	UL	230.2	229.9	229.8	230.2
MSB 44B	L(UD)	225.1	225.2	225.6	226.3
MSB 45B	UL	226.2	226.7	226.9	227.7
MSB 46B	UL	-	-	-	-
MSB 47C	UL	233.6	233.3	233.0	233.4
MSB 48D	UL	233.6	233.3	233.1	233.2
MSB 50B	UL	202.2	201.8	201.9	202.8
MSB 53C	UL	224.2	223.9	223.9	224.4
MSB 55HC	UL	233.8	233.5	233.3	233.4
MSB 61C	UL	224.7	224.5	224.4	224.9
MSB 62C	UL	224.6	223.7	225.0	224.3
MSB 63C	UL	221.7	221.0	221.8	221.7
MSB 64C	UL	224.2	223.6	223.7	223.7
MSB 70C	UL	219.2	218.8	218.5	218.6
MSB 74C	UL	211.4	210.9	211.2	212.0
MSB 75C	UL	210.3	209.8	210.2	210.9
MSB 76C	UL	222.3	221.9	221.6	221.7
MSB 79C	UL	210.8	210.2	210.9	211.3
MSB 87C	UL	243.7	243.2	242.9	243.6
MSB 88C	UL	204.3	203.7	203.8	205.2
MSB 89C	UL	230.6	230.0	229.7	229.9
SRW 2B	UL	209.0	208.4	207.9	209.1
SRW 14B	UL	206.6	206.0	205.5	206.6
SRW 15B	UL	210.8	210.3	209.7	210.7

Table 1 (cont.)

Lower Lost Lake Aquifer Zone

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
AMB 4B	LL	225.1	225.1	225.2	225.8
AMB 7B	LL	225.4	225.3	225.4	226.1
AMB 10B	LL	223.6	223.6	223.8	224.6
ASB 2CR	LL	224.3	221.8	223.8	224.4
ASB 3CR	LL	224.0	223.5	223.4	224.0
ASB 5C	LL	224.1	223.5	223.4	224.0
ASB 8B	(LL)L/MCBC	220.7	221.3	221.3	221.8
ASB 9B	L(UD)	221.4	221.2	221.2	221.9
ASB 10CR	LL	224.2	223.8	223.7	224.3
MSB 1B	LL	214.1	207.7	215.8	209.3
MSB 2B	LL	214.6	210.1	216.2	211.6
MSB 3B	LL	—	209.5	216.1	—
MSB 4B	LL	214.3	205.0	216.2	206.6
MSB 5B	LL	209.4	208.0	212.1	211.0
MSB 6B	LL	207.8	206.9	208.7	208.4
MSB 7B	LL	208.4	207.6	209.1	209.0
MSB 8B	LL	210.0	208.9	211.1	210.5
MSB 9A	LL/CBC	213.9	208.7	215.9	210.4
MSB 10B	LL	215.7	212.9	217.6	214.4
MSB 11A	LL	214.5	211.9	216.3	213.2
MSB 12A	LL	210.1	208.6	213.0	211.6
MSB 13A	LL	209.3	207.5	212.7	211.0
MSB 14A	L(UD)	217.3	215.5	218.3	216.8
MSB 15AA	LL	215.2	213.7	217.1	215.0
MSB 17BB	LL	213.8	213.1	214.3	214.0
MSB 21A	LL	221.9	221.5	222.4	222.0
MSB 21B	LL	221.3	220.7	221.8	221.3
MSB 25A	LL	216.6	216.3	217.6	219.9
MSB 26B	LL	219.1	218.8	220.8	219.9
MSB 29B	LL	225.6	225.0	225.0	225.4
MSB 30B	LL	226.2	225.9	226.1	226.3
MSB 31B	LL	213.9	213.8	214.1	220.8
MSB 32B	LL	211.4	211.2	211.2	212.9
MSB 33B	LL/CBC	208.0	207.6	207.7	208.6
MSB 36B	LL	215.1	214.5	213.3	215.9
MSB 38B	LL/CBC	216.2	215.2	217.2	217.6
MSB 38C	LL	218.9	218.4	219.8	221.1
MSB 39B	LL	213.3	211.8	214.1	213.4
MSB 40B	LL	205.5	204.9	205.0	205.7
MSB 41C	LL	218.6	218.4	218.5	219.3
MSB 42B	LL	226.5	226.5	226.5	227.0
MSB 43A	LL	230.1	229.8	229.6	230.0
MSB 45A	LL	216.9	216.4	217.2	217.9
MSB 47B	LL	229.4	225.9	225.7	226.3
MSB 48C	LL	225.6	225.2	225.1	225.5
MSB 49B	LL	204.2	203.6	204.2	204.4
MSB 51B	L(UD)	205.0	204.5	204.6	205.6
MSB 52B	LL	220.1	220.0	220.1	220.8
MSB 53B	LL	223.3	223.0	223.0	223.5

Table 1 (cont.)

Lower Lost Lake Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
MSB 54C	LL	228.0	227.4	227.2	227.6
MSB 55C	LL	230.5	229.9	229.8	230.0
MSB 62B	LL	212.2	207.9	214.4	210.3
MSB 63B	LL	210.9	208.8	212.5	210.9
MSB 66C	LL	229.4	229.3	229.2	229.7
MSB 67C	LL	229.0	227.2	227.1	227.5
MSB 68C	LL	228.1	225.4	225.3	225.8
MSB 69C	LL	229.1	228.1	227.9	228.3
MSB 71B	L(UD)	218.6	218.1	217.7	217.9
MSB 72B	LL	200.8	200.2	200.0	200.8
MSB 73B	LL	202.9	202.3	202.6	203.0
MSB 74B	LL/CBC	211.4	211.0	211.2	212.1
MSB 75B	LL	210.5	210.0	210.5	211.5
MSB 77C	LL	225.1	224.7	224.6	225.2
MSB 79B	LL	208.8	208.0	208.9	209.1
MSB 81B	LL	220.9	220.7	220.8	221.4
MSB 82C	LL	229.9	228.8	228.6	229.0
MSB 83C	LL	229.5	229.0	228.8	225.0
MSB 84C	LL	230.7	230.3	230.1	230.4
MSB 85C	LL	226.0	225.4	225.3	225.7
MSB 86C	LL	226.0	225.7	225.6	226.0
MSB 87B	LL	218.7	218.4	218.8	219.8
MSB 89B	LL	—	—	207.5	208.6
SRW 1BB	LL	208.8	208.0	207.7	208.7
SRW 3BB	LL	209.9	209.1	208.9	209.9
SRW 4BB	LL	208.5	207.9	207.5	208.5
SRW 8BB	LL	—	—	—	—
SRW 10BB	LL	206.6	205.8	205.5	207.7
SRW 11BB	LL	206.9	206.1	205.8	207.1
SRW 13A	LL	202.9	201.0	201.5	202.9
SRW 16A	LL/CBC	215.4	214.7	214.5	214.6
SRW 16B	L	216.0	215.5	215.0	215.3
SRW 17BB	LL	213.5	212.9	212.5	213.1
SRW 17C	LL	213.8	212.9	212.8	213.3
SRW 17D	LL	—	—	—	—

Middle Sand Aquifer Zone of the Crouch Branch Confining Unit

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
AMB 4A	MCBC	219.9	219.6	219.8	220.4
AMB 7A	MCBC	219.8	219.6	219.8	220.4
AMB 10A	MCBC	248.8	218.5	218.7	219.5
AMB 13AR	MCBC	219.5	219.3	219.5	220.3
AMB 17A	MCBC	—	—	—	220.4
AMB 18A	MCBC	—	—	—	220.2
ASB 6AA	MCBC	219.5	219.1	219.1	219.8
ASB 8A	MCBC	220.5	220.1	220.1	220.4
MSB 10A	MCBC	213.5	210.1	215.6	211.8
MSB 12TA	CBC	192.8	192.7	193.1	194.1

Table 1 (cont.)

Middle Sand Aquifer Zone of the Crouch Branch Confining Unit (cont.)

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
MSB 19A	MCBC	215.0	214.5	215.0	216.0
MSB 29A	MCBC	221.1	220.6	220.8	221.2
MSB 30AA	MCBC	224.8	224.5	224.7	224.8
MSB 33A	MCBC	205.1	204.8	205.0	205.8
MSB 34A	MCBC	219.4	219.2	219.5	220.2
MSB 34TA	CBC	203.2	202.7	203.1	204.0
MSB 35A	CBC	217.1	216.9	217.2	218.3
MSB 36A	MCBC	211.3	210.1	212.2	211.7
MSB 37B	MCBC	220.3	220.0	220.1	220.7
MSB 39A	MCBC	210.5	209.2	211.5	210.8
MSB 40A	MCBC	203.7	203.1	203.4	204.0
MSB 41A	MCBC	217.9	217.7	217.8	218.6
MSB 41B	MCBC	218.0	217.9	218.0	218.8
MSB 42A	MCBC	219.9	219.9	220.1	220.7
MSB 44A	MCBC	218.6	218.4	218.7	219.3
MSB 46A	MCBC	213.8	215.8	217.0	217.0
MSB 47BB	MCBC	220.9	220.5	220.5	221.0
MSB 48A	CBC	223.7	223.3	223.3	223.7
MSB 48B	CBC	225.1	224.7	224.6	225.0
MSB 49A	MCBC	198.3	197.8	198.3	198.8
MSB 54B	MCBC	223.4	223.0	222.9	223.3
MSB 55B	CBC	223.0	222.6	222.6	223.0
MSB 64B	MCBC	209.2	208.1	210.8	210.1
MSB 66B	MCBC	220.2	219.9	220.0	220.6
MSB 67B	MCBC	220.1	219.7	219.8	220.3
MSB 68B	MCBC	220.7	220.2	220.3	220.8
MSB 69B	MCBC	222.2	221.7	221.7	222.2
MSB 77B	MCBC	223.0	222.6	222.6	223.2
MSB 82A	MCBC	219.1	222.5	223.2	221.2
MSB 82B	LL/CBC	221.5	221.0	221.1	221.5
MSB 83B	MCBC	223.0	222.6	222.5	223.0
MSB 84A	MCBC	186.2	200.3	—	194.1
MSB 88B	MCBC	201.0	201.1	201.3	202.2
SRW 2A	MCBC	207.8	206.9	206.9	207.8
SRW 13B	MCBC	204.5	201.6	203.5	204.7
SRW 14A	CBC	204.7	203.8	203.8	204.8
SRW 15A	MCBC	210.4	209.8	209.4	210.5

Crouch Branch Aquifer Zone

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
ASB 6TA	CBA	215.2	214.9	214.9	215.5
ASB 8TA	CBA	216.9	216.5	216.6	217.2
MSB 12TB	CBA	193.0	192.9	193.3	194.3
MSB 21TA	CBA	194.8	194.4	194.8	195.8
MSB 23TA	CBA	202.1	201.6	202.1	202.9
MSB 23TR	CBA	199.5	199.5	199.9	200.7
MSB 27TA	CBA	201.8	201.4	201.8	202.7
MSB 29TA	CBA	213.3	212.3	212.9	213.6

Table 1 (cont.)

Crouch Branch Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>2Q94</u>	<u>3Q94</u>	<u>4Q94</u>	<u>1Q95</u>
MSB 30A	CBA	199.3	199.0	199.3	200.3
MSB 31A	CBA	198.4	199.4	198.7	199.7
MSB 33TA	CBA	195.0	195.0	195.3	196.3
MSB 34TB	CBA	203.6	203.4	203.7	204.6
MSB 35TA	CBA	200.3	200.3	200.6	206.5
MSB 36TA	CBA	195.2	195.1	195.4	196.4
MSB 37A	CBA	208.3	207.9	208.2	209.0
MSB 37TA	CBA	208.1	207.8	208.0	208.8
MSB 38TA	CBA	198.4	198.1	198.8	199.6
MSB 39TA	CBA	193.0	192.8	193.3	194.4
MSB 40TA	CBA	189.6	189.5	189.8	190.9
MSB 41TA	CBA	206.9	206.9	207.1	207.9
MSB 42TA	CBA	206.5	206.4	206.7	207.5
MSB 43TA	CBA	203.8	202.6	203.6	204.5
MSB 47TA	CBA	217.7	217.4	217.4	218.0
MSB 48TA	CBA	223.5	223.2	223.1	223.5
MSB 54TA	CBA	220.7	220.3	220.3	220.7
MSB 55TA	CBA	215.2	214.7	214.9	215.4
MSB 66TA	CBA	207.3	206.7	207.2	208.0
MSB 69TA	CBA	216.4	215.8	216.0	216.7
MSB 77TA	CBA	222.7	222.3	222.4	222.8
MSB 82TA	CBA	215.5	214.9	215.2	215.8
MSB 83TA	CBA	216.7	216.2	216.3	216.9
MSB 85B	CBA	222.8	222.3	222.3	222.8
MSB 85TA	CBA	222.2	221.8	221.8	222.2

Note: See pages D-3 and D-4 of this appendix for definitions of the abbreviations used in the screen zone (SZ) column.

- ^a SZ = screen zone.
^b – = no data available.

Table 2. Groundwater Monitoring Results for Point-of-Compliance Wells

WELL MSB 1B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>		
N101833.0 E48483.2	33.330080 °N 81.736980 °W	142.6-137.9 ft msl	354.8 ft msl	4" PVC	S	LL		
SAMPLE DATE			01/17/95					
FIELD DATA								
<u>Parameter</u>	<u>4Q94</u>		<u>1Q95</u>			<u>Unit</u>		
Water elevation			215.8			ft msl		
pH			5.3			pH		
Sp. conductance			24			µS/cm		
Water temperature			19.0			°C		
Alkalinity as CaCO ₃			2			mg/L		
Turbidity			0.9			NTU		
Volume purged			2.66			well volumes		
Sampling code								
Synchronous water level	215.8 (12/21/94)		209.3 (03/23/95)			ft msl		
ANALYTICAL DATA								
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable							0	GE µg/L
Arsenic, total recoverable							0	GE µg/L
Barium, total recoverable							0	GE µg/L
Cadmium, total recoverable							0	GE µg/L
Chloride							0	GE µg/L
Chlorobenzene							0	GE µg/L
Chromium, total recoverable							0	GE µg/L
Cobalt, total recoverable								µg/L
Copper, total recoverable								µg/L
Cyanide							0	GE µg/L
1,1-Dichloroethane							0	GE µg/L
1,1-Dichloroethylene							0	GE µg/L
trans-1,2-Dichloroethylene							0	GE µg/L
Gross alpha							0	GP pCi/L
Lead, total recoverable							0	GE µg/L
Mercury, total recoverable							0	GE µg/L
Nickel, total recoverable							0	GE µg/L
Nitrate-nitrite as nitrogen							0	GE µg/L
Nonvolatile beta							0	GP pCi/L
PCB 1254								µg/L
Radium, total alpha-emitting							0	GP pCi/L
Selenium, total recoverable							0	GE µg/L
Silver, total recoverable							0	GE µg/L
Sodium, total recoverable							0	GE µg/L
Sulfate							0	GE µg/L
1,1,2,2-Tetrachloroethane							0	GE µg/L
Tetrachloroethylene							0	GE µg/L
Total phosphates (as P)							0	GE µg/L
1,1,1-Trichloroethane							0	GE µg/L
Trichloroethylene							2	GE µg/L
Uranium, total recoverable							0	GE µg/L
Zinc, total recoverable							0	GE µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 1C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101832.5 E48512.7	33.330130 °N 81.736900 °W	166.0-161.3 ft msl	355.1 ft msl	4" PVC	S	UL

SAMPLE DATE 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		219.3	ft msl
pH		11.7	pH
Sp. conductance		1,003	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		200	mg/L
Turbidity		0.7	NTU
Volume purged		0.814	well volumes
Sampling code		X	
Synchronous water level	219.3 (12/21/94)	217.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								3,500	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								73.7	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,800	1				0	GE	µg/L
Chlorobenzene								<8.34	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<8.34	5				0	GE	µg/L
1,1-Dichloroethylene								<8.34	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.34	5				0	GE	µg/L
Gross alpha								2.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								9,820	8		■		1	GE	µg/L
Nonvolatile beta								1.3E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								2.02	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								37,000	2		■		0	GE	µg/L
Sulfate								5,170	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.34	5				0	GE	µg/L
Tetrachloroethylene								345	5		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<8.34	5				0	GE	µg/L
Trichloroethylene								66.0	5		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 1CC

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101832.5 E48498.0	33.330100 °N 81.736940 °W	192.5-187.8 ft msl	354.9 ft msl	4" PVC	S	UL

SAMPLE DATE 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		220.8	ft msl
pH		7.3	pH
Sp. conductance		151	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		36	mg/L
Turbidity		3.0	NTU
Volume purged		0.646	well volumes
Sampling code		X	
Synchronous water level	220.8 (12/21/94)	219.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								42.8	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								19.5	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,050	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								7.35	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								5,640	4				1	GE	µg/L
Nonvolatile beta								6.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.5E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								16,100	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								22.6	1				2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								30.6	1				2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								30.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 1D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101833.4 E48452.2	33.330030 °N 81.737060 °W	229.8-210.4 ft msl	354.8 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		230.7	ft msl
pH		5.2	pH
Sp. conductance		53	µS/cm
Water temperature		18.2	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		2.0	NTU
Volume purged		1.20	well volumes
Sampling code		X	
Synchronous water level	231.3 (12/21/94)	231.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								88.1	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								16.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								3,980	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.7E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,900	2				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254								<0.809	1				0	GE	µg/L
Radium, total alpha-emitting								5.4E+00	1			■	0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								5,650	1			■	0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								27.6	1			■	2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								14.3	1			■	2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								28.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 2B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101997.9 E48748.2	33.330880 °N 81.736600 °W	150.3-145.6 ft msl	354.6 ft msl	4" PVC	S	LL

SAMPLE DATE 01/16/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		215.8	ft msl
pH		11.6	pH
Sp. conductance		1,464	µS/cm
Water temperature		19.7	°C
Alkalinity as CaCO ₃		311	mg/L
Turbidity		41.7	NTU
Volume purged		0.869	well volumes
Sampling code		X	
Synchronous water level	216.2 (12/21/94)	211.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								1,550	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								106	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								1,270	1				0	GE	µg/L
Chlorobenzene								<167	100				0	GE	µg/L
Chromium, total recoverable								4.87	1	J			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<167	100				0	GE	µg/L
1,1-Dichloroethylene								<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene								<167	100				0	GE	µg/L
Gross alpha								2.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								6,810	4		■		1	GE	µg/L
Nonvolatile beta								3.6E+01	1				1	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								2.99	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								56,400	3		■		0	GE	µg/L
Sulfate								2,610	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<167	100				0	GE	µg/L
Tetrachloroethylene								2,720	100		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<167	100				0	GE	µg/L
Trichloroethylene								7,310	100		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 2C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101982.5 E48749.3	33.330840 °N 81.736570 °W	194.7-190.0 ft msl	354.7 ft msl	4" PVC	S	UL

SAMPLE DATE 01/16/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		219.6	ft msl
pH		10.7	pH
Sp. conductance		637	µS/cm
Water temperature		20.2	°C
Alkalinity as CaCO ₃		186	mg/L
Turbidity		4.9	NTU
Volume purged		0.720	well volumes
Sampling code		X	
Synchronous water level	220.4 (12/21/94)	219.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								535	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								46.5	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,000	1				0	GE	µg/L
Chlorobenzene								<418	250				0	GE	µg/L
Chromium, total recoverable								12.7	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<418	250				0	GE	µg/L
1,1-Dichloroethylene								<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene								<418	250				0	GE	µg/L
Gross alpha								3.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								11,800	10		■		2	GE	µg/L
Nonvolatile beta								3.0E+01	1				1	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.7E+00	1				0	GP	pCi/L
Selenium, total recoverable								3.33	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								63,900	3		■		0	GE	µg/L
Sulfate								2,850	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<418	250				0	GE	µg/L
Tetrachloroethylene								13,000	250		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<418	250				0	GE	µg/L
Trichloroethylene								11,400	250		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								4.14	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 2D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102014.0 E48755.7	33.330920 °N 81.736610 °W	230.1-210.7 ft msl	353.8 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/16/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		231.3	ft msl
pH		4.4	pH
Sp. conductance		51	µS/cm
Water temperature		19.5	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		2.8	NTU
Volume purged		1.63	well volumes
Sampling code		X	
Synchronous water level	232.0 (12/21/94)	232.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								191	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								15.2	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,100	1				0	GE	µg/L
Chlorobenzene								<16.7	10				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															ug/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	1			0	GE	µg/L
1,1-Dichloroethane								<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene								<16.7	10				0	GE	µg/L
Gross alpha								1.6E+01	1		■		2	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,830	4		■		0	GE	µg/L
Nonvolatile beta								6.6E+00	1				0	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								1.1E+01	1		■		1	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								2,060	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L
Tetrachloroethylene								997	50		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<16.7	10				0	GE	µg/L
Trichloroethylene								944	50		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								10.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 3B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102191.7 E48568.0	33.331010 °N 81.737450 °W	145.8-141.1 ft msl	361 ft msl	4" PVC	S	LL

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	216.1 (12/21/94)		ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 3C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102189.6 E48538.5	33.330960 °N 81.737530 °W	193.7-189.0 ft msl	360.8 ft msl	4" PVC	S	UL

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	222.2 (12/21/94)	220.5 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 3D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102188.6 E48524.6	33.330930 °N 81.737560 °W	230.7-211.2 ft msl	360.2 ft msl	4" PVC	S	MGC

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	230.8 (12/21/94)	231.1 (01/16/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															µg/L
Lead, total recoverable															pCi/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 4B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101978.3 E48312.8	33.330120 °N 81.737710 °W	143.1-138.4 ft msl	355.3 ft msl	4" PVC	S	LL

SAMPLE DATE 01/18/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		216.1	ft msl
pH		5.5	pH
Sp. conductance		45	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.4	NTU
Volume purged		3.33	well volumes
Sampling code			
Synchronous water level	216.2 (12/21/94)	206.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<33.33	1				0	GE	µg/L
Barium, total recoverable								10.1	1				0	GE	µg/L
Cadmium, total recoverable								<33.33	1				0	GE	µg/L
Chloride								2,970	1				0	GE	µg/L
Chlorobenzene								<33.4	20				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<33.4	20				0	GE	µg/L
1,1-Dichloroethylene								<33.4	20				0	GE	µg/L
trans-1,2-Dichloroethylene								<33.4	20				0	GE	µg/L
Gross alpha								1.8E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3,530	4		■		0	GE	µg/L
Nonvolatile beta								2.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								5,410	1		■		0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<33.4	20				0	GE	µg/L
Tetrachloroethylene								4,820	100		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<33.4	20				0	GE	µg/L
Trichloroethylene								2,440	100		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								7.12	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 4C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101963.2 E48313.6	33.330090 °N 81.737680 °W	168.1-163.3 ft msl	355.2 ft msl	4" PVC	S	UL

SAMPLE DATE 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		219.1	ft msl
pH		11.6	pH
Sp. conductance		516	µS/cm
Water temperature		16.4	°C
Alkalinity as CaCO ₃		177	mg/L
Turbidity		3.2	NTU
Volume purged		0.765	well volumes
Sampling code		X	
Synchronous water level	219.4 (12/21/94)	215.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								32.6	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								183	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								3,630	1				0	GE	µg/L
Chlorobenzene								<167	100				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<167	100				0	GE	µg/L
1,1-Dichloroethylene								<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene								<167	100				0	GE	µg/L
Gross alpha								5.4E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								15,000	20			■	2	GE	µg/L
Nonvolatile beta								1.2E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.6E+00	1				0	GP	pCi/L
Selenium, total recoverable								2.51	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								23,000	1			■	0	GE	µg/L
Sulfate								2,230	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<167	100				0	GE	µg/L
Tetrachloroethylene								2,460	100			■	2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<167	100				0	GE	µg/L
Trichloroethylene								2,480	100			■	2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 4D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102007.5 E48311.7	33.330180 °N 81.737770 °W	228.4-209.0 ft msl	355.5 ft msl	4" PVC	S	M

SAMPLE DATE 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		230.1	ft msl
pH		4.5	pH
Sp. conductance		82	µS/cm
Water temperature		19.5	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.9	NTU
Volume purged		10.0	well volumes
Sampling code			
Synchronous water level	230.5 (12/21/94)	230.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								190	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								18.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,690	1				0	GE	µg/L
Chlorobenzene								<3.34	2				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<3.34	2				0	GE	µg/L
1,1-Dichloroethylene								<3.34	2				0	GE	µg/L
trans-1,2-Dichloroethylene								<3.34	2				0	GE	µg/L
Gross alpha								1.1E+01	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								6,160	4		■		1	GE	µg/L
Nonvolatile beta								3.6E+00	1				0	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								6.8E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								7,540	1		■		0	GE	µg/L
Sulfate								4,020	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<3.34	2				0	GE	µg/L
Tetrachloroethylene								105	2		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<3.34	2				0	GE	µg/L
Trichloroethylene								125	2		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								3.79	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 5A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101971.5 E46998.7	33.327960 °N 81.741160 °W	247.2-217.2 ft msl	344.6 ft msl	4" PVC	S	M

SAMPLE DATE 10/19/94 01/26/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	228.5		ft msl
pH	5.4	5.3	pH
Sp. conductance	36	45	µS/cm
Water temperature	18.9	18.9	°C
Alkalinity as CaCO ₃	2	3	mg/L
Turbidity	0.5	0.8	NTU
Volume purged	15.0		well volumes
Sampling code			
Synchronous water level	228.4 (12/20/94)	228.4 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1					GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	<5.00	1					GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Chloride	2,260	1					GE	2,260	1				0	GE	µg/L
Chlorobenzene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1					GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Gross alpha	9.9E-01	1					GP	9.9E-01	1				0	GP	pCi/L
Lead, total recoverable	<5.00	1					GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1					GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	2,760	2					GE	2,760	2				0	GE	µg/L
Nonvolatile beta	8.0E-01	1	UI				GP	8.0E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	5.0E-01	1					GP	5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	6,240	1					GE	6,240	1				0	GE	µg/L
Sulfate	1,810	1					GE	1,810	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	1.51	1	J				GE	1.51	1	J			0	GE	µg/L
Total phosphates (as P)	74.2	1	J				GE	74.2	1	J			0	GE	µg/L
1,1,1-Trichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Trichloroethylene	1.37	1	J				GE	1.37	1	J			0	GE	µg/L
Uranium, total recoverable	<33.3	1					GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	6.92	1					GE	6.92	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 5B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101971.1 E46983.6	33.327930 °N 81.741200 °W	136.1-131.4 ft msl	345 ft msl	4" PVC	S	LL

SAMPLE DATE 01/26/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		212.0	ft msl
pH		5.3	pH
Sp. conductance		21	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.0	NTU
Volume purged		2.89	well volumes
Sampling code			
Synchronous water level	212.1 (12/20/94)	211.0 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								22.6	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.38	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,400	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								5.7E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								224	1				0	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								1,630	1				0	GE	µg/L
Sulfate								1,880	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								4.75	1				1	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								11.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 5C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101970.4 E46968.6	33.327910 °N 81.741230 °W	188.1-183.4 ft msl	345.2 ft msl	4" PVC	S	UL

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		223.6	ft msl
pH		6.0	pH
Sp. conductance		260	µS/cm
Water temperature		17.0	°C
Alkalinity as CaCO ₃		23	mg/L
Turbidity		72.2	NTU
Volume purged		1.33	well volumes
Sampling code		X	
Synchronous water level	224.3 (12/20/94)	224.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								131	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								72.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								4,090	1				0	GE	µg/L
Chlorobenzene								<16.7	10				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								26.0	10		■		2	GE	µg/L
trans-1,2-Dichloroethylene								<16.7	10				0	GE	µg/L
Gross alpha								8.6E+00	1				1	GP	pCi/L
Lead, total recoverable								9.52	1				0	GE	µg/L
Mercury, total recoverable								0.841	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								19,700	20		■		2	GE	µg/L
Nonvolatile beta								8.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.6E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								27,100	2		■		0	GE	µg/L
Sulfate								1,090	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L
Tetrachloroethylene								214	10		■		2	GE	µg/L
Total phosphates (as P)								469	1		■		0	GE	µg/L
1,1,1-Trichloroethane								15.0	10	J			0	GE	µg/L
Trichloroethylene								11.0	10	J	■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								185	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 6A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101133.8 E46319.9	33.325000 °N 81.741310 °W	241.9-211.9 ft msl	343.8 ft msl	4" PVC	S	M

SAMPLE DATE 10/18/94 01/26/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	228.3	227.1	ft msl
pH	5.1	5.0	pH
Sp. conductance	35	39	µS/cm
Water temperature	18.8	18.6	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.0	1.4	NTU
Volume purged	2.60	7.24	well volumes
Sampling code			
Synchronous water level	223.6 (12/20/94)	228.0 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								31.1	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.13	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								4,820	1		■		0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.0E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								309	1				0	GE	µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.7E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								5,600	1		■		0	GE	µg/L
Sulfate								1,640	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 6B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101148.5 E46321.6	33.325030 °N 81.741340 °W	129.8-125.1 ft msl	343.9 ft msl	4" PVC	S	LL

SAMPLE DATE 01/18/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		208.7	ft msl
pH		5.7	pH
Sp. conductance		40	µS/cm
Water temperature		19.1	°C
Alkalinity as CaCO ₃		7	mg/L
Turbidity		0.6	NTU
Volume purged		2.43	well volumes
Sampling code			
Synchronous water level	208.7 (12/20/94)	208.4 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1					GE	µg/L							
Arsenic, total recoverable	<3.33	1					GE	µg/L							
Barium, total recoverable	23.1	1					GE	µg/L							
Cadmium, total recoverable	<3.33	1					GE	µg/L							
Chloride	2,230	1					GE	µg/L							
Chlorobenzene	<41.8	25					GE	µg/L							
Chromium, total recoverable	<6.67	1					GE	µg/L							
Cobalt, total recoverable							GE	µg/L							
Copper, total recoverable							GE	µg/L							
Cyanide	<8.33	1					GE	µg/L							
1,1-Dichloroethane	<41.8	25					GE	µg/L							
1,1-Dichloroethylene	<41.8	25					GE	µg/L							
trans-1,2-Dichloroethylene	<83.5	25					GE	µg/L							
Gross alpha	2.3E+00	1					GP	pCi/L							
Lead, total recoverable	<5.00	1					GE	µg/L							
Mercury, total recoverable	<0.333	1					GE	µg/L							
Nickel, total recoverable	<6.67	1					GE	µg/L							
Nitrate-nitrite as nitrogen	2,580	4					GE	µg/L							
Nonvolatile beta	2.8E+00	1					GP	pCi/L							
PCB 1254							GE	µg/L							
Radium, total alpha-emitting	1.2E+00	1					GP	pCi/L							
Selenium, total recoverable	<3.33	1					GE	µg/L							
Silver, total recoverable	<3.33	1					GE	µg/L							
Sodium, total recoverable	3,120	1					GE	µg/L							
Sulfate	1,310	1	J				GE	µg/L							
1,1,2,2-Tetrachloroethane	<41.8	25					GE	µg/L							
Tetrachloroethylene	48.8	25					GE	µg/L							
Total phosphates (as P)	<83.3	1					GE	µg/L							
1,1,1-Trichloroethane	<41.8	25					GE	µg/L							
Trichloroethylene	1,610	25					GE	µg/L							
Uranium, total recoverable	<33.3	1					GE	µg/L							
Zinc, total recoverable	4.30	1					GE	µg/L							

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 6C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101169.1 E46324.1	33.325080 °N 81.741370 °W	194.0-189.3 ft msl	343.8 ft msl	4" PVC	S	UL

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.3	ft msl
pH		5.9	pH
Sp. conductance		696	µS/cm
Water temperature		17.7	°C
Alkalinity as CaCO ₃		25	mg/L
Turbidity		156.0	NTU
Volume purged		1.05	well volumes
Sampling code		X	
Synchronous water level	224.7 (12/20/94)	224.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								187	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								63.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								3,950	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								1.70	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								5.0E+00	1				0	GP	pCi/L
Lead, total recoverable								8.39	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								45,500	40		■		2	GE	µg/L
Nonvolatile beta								1.7E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								128,000	10		■		0	GE	µg/L
Sulfate								4,680	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								138	5		■		2	GE	µg/L
Total phosphates (as P)								1,560	1		■		0	GE	µg/L
1,1,1-Trichloroethane								1.70	1				0	GE	µg/L
Trichloroethylene								35.4	1		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								497	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 7A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100585.7 E46726.1	33.324450 °N 81.739180 °W	242.0-212.0 ft msl	344.3 ft msl	4" PVC	S	MGC

SAMPLE DATE	10/19/94	01/26/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	229.3	227.8	ft msl
pH	4.7	4.7	pH
Sp. conductance	36	38	µS/cm
Water temperature	18.5	18.2	°C
Alkalinity as CaCO ₃	2	1	mg/L
Turbidity	0.8	0.7	NTU
Volume purged	7.06	6.47	well volumes
Sampling code			
Synchronous water level	229.0 (12/20/94)	229.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<33.3	1					GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	14.2	1					GE	14.2	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Chloride	3,680	1					GE	3,680	1				0	GE	µg/L
Chlorobenzene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable													0		µg/L
Copper, total recoverable													0		µg/L
Cyanide	<8.33	1					GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Gross alpha	3.6E+00	1					GP	3.6E+00	1				0	GP	pCi/L
Lead, total recoverable	<5.00	1					GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1					GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,200	1					GE	1,200	1				0	GE	µg/L
Nonvolatile beta	9.0E-01	1	UI				GP	9.0E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	3.3E+00	1					GP	3.3E+00	1				0	GP	pCi/L
Selenium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	3,960	1					GE	3,960	1				0	GE	µg/L
Sulfate	1,420	1	J				GE	1,420	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<83.3	1					GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<33.3	1					GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 7B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100597.6 E46718.1	33.324460 °N 81.739220 °W	147.5-142.7 ft msl	344.1 ft msl	4" PVC	S	LL

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		208.5	ft msl
pH		6.8	pH
Sp. conductance		164	µS/cm
Water temperature		17.3	°C
Alkalinity as CaCO ₃		40	mg/L
Turbidity		46.9	NTU
Volume purged		1.69	well volumes
Sampling code		X	
Synchronous water level	209.1 (12/20/94)	209.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								182	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								48.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,270	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								5,920	8		■		1	GE	µg/L
Nonvolatile beta								3.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								9,820	1		■		0	GE	µg/L
Sulfate								2,570	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								83.5	1		■		2	GE	µg/L
Total phosphates (as P)								1,290	1		■		0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								56.1	1		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								11.1	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 7C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100609.2 E46709.1	33.324480 °N 81.739270 °W	200.1-195.4 ft msl	344.5 ft msl	4" PVC	S	GCL

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		222.4	ft msl
pH		5.8	pH
Sp. conductance		362	µS/cm
Water temperature		17.4	°C
Alkalinity as CaCO ₃		15	mg/L
Turbidity		12.0	NTU
Volume purged		0.846	well volumes
Sampling code		X	
Synchronous water level	223.5 (12/20/94)	223.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								290	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								43.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								4,170	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								3.40	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.5E+00	1				0	GP	pCi/L
Lead, total recoverable								5.30	1				0	GE	µg/L
Mercury, total recoverable								0.232	1	J			0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								32,100	20		■		2	GE	µg/L
Nonvolatile beta								8.1E+01	1		■		2	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.7E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								48,100	3		■		0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								44.7	1		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								2.70	1				0	GE	µg/L
Trichloroethylene								16.8	1		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								9.14	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 8A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100815.1 E47293.2	33.325880 °N 81.738130 °W	242.4-212.4 ft msl	344.2 ft msl	4" PVC	S	M

SAMPLE DATE 10/19/94 02/06/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	230.3	229.7	ft msl
pH	4.6	4.3	pH
Sp. conductance	36	40	µS/cm
Water temperature	19.0	17.8	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	0.6	0.7	NTU
Volume purged	4.00	5.83	well volumes
Sampling code			
Synchronous water level	230.1 (12/20/94)	230.1 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	Unit	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								µg/L	94.1	1	VV			2	WA	µg/L
Arsenic, total recoverable								µg/L	1.50	1	JY			0	WA	µg/L
Barium, total recoverable								µg/L	7.10	1	JY			0	WA	µg/L
Cadmium, total recoverable								µg/L	0.930	1	JVVY			0	WA	µg/L
Chloride								µg/L	2,040	1	JY			0	WA	µg/L
Chlorobenzene								µg/L	<1.67	1				0	GE	µg/L
Chromium, total recoverable								µg/L	4.90	1	J			0	WA	µg/L
Cobalt, total recoverable								µg/L								µg/L
Copper, total recoverable								µg/L								µg/L
Cyanide								µg/L	<8.33	1				0	GE	µg/L
1,1-Dichloroethane								µg/L	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								µg/L	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								µg/L	<1.67	1				0	GE	µg/L
Gross alpha								pCi/L	1.1E+01	1			1	TM		pCi/L
Lead, total recoverable								µg/L	<5.00	1				0	GE	µg/L
Mercury, total recoverable								µg/L	0.0730	1	JY			0	WA	µg/L
Nickel, total recoverable								µg/L	3.00	1	J			0	WA	µg/L
Nitrate-nitrite as nitrogen								µg/L	2,630	2		■		0	GE	µg/L
Nonvolatile beta								pCi/L	8.4E+00	1				0	TM	pCi/L
PCB 1254								µg/L								µg/L
Radium, total alpha-emitting								pCi/L	4.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								µg/L	19.0	1	JV	■		0	WA	µg/L
Silver, total recoverable								µg/L	<1.40	1	Y			0	WA	µg/L
Sodium, total recoverable								µg/L	2,990	1				0	GE	µg/L
Sulfate								µg/L	351	1	JY			0	WA	µg/L
1,1,2,2-Tetrachloroethane								µg/L	<1.67	1				0	GE	µg/L
Tetrachloroethylene								µg/L	88.4	1		■		2	GE	µg/L
Total phosphates (as P)								µg/L	22.0	1	J			0	WA	µg/L
1,1,1-Trichloroethane								µg/L	<1.67	1				0	GE	µg/L
Trichloroethylene								µg/L	16.4	1		■		2	GE	µg/L
Uranium, total recoverable								µg/L	<33.3	1				0	GE	µg/L
Zinc, total recoverable								µg/L	5.00	1	JVVY			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 8B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100805.8 E47281.9	33.325850 °N 81.738140 °W	150.8-146.1 ft msl	343.9 ft msl	4" PVC	S	LL

SAMPLE DATE 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		211.2	ft msl
pH		5.0	pH
Sp. conductance		27	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.4	NTU
Volume purged		3.52	well volumes
Sampling code			
Synchronous water level	211.1 (12/20/94)	210.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.43	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,210	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.7E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,170	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								2,170	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								2.97	1				1	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								17.5	1				2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								5.35	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 8C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100793.2 E47264.6	33.325790 °N 81.738160 °W	195.9-191.2 ft msl	344 ft msl	4" PVC	S	UL

SAMPLE DATE 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		221.1	ft msl
pH		4.7	pH
Sp. conductance		250	μS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃			mg/L
Turbidity		0.5	NTU
Volume purged		4.02	well volumes
Sampling code			
Synchronous water level	221.4 (12/20/94)	221.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								88.7	1				2	GE	μg/L
Arsenic, total recoverable								<3.33	1				0	GE	μg/L
Barium, total recoverable								59.2	1				0	GE	μg/L
Cadmium, total recoverable								<3.33	1				0	GE	μg/L
Chloride								4,990	1		■		0	GE	μg/L
Chlorobenzene								<8.34	5				0	GE	μg/L
Chromium, total recoverable								<6.67	1				0	GE	μg/L
Cobalt, total recoverable															μg/L
Copper, total recoverable															μg/L
Cyanide								<8.33	1				0	GE	μg/L
1,1-Dichloroethane								<8.34	5				0	GE	μg/L
1,1-Dichloroethylene								13.5	5		■		2	GE	μg/L
trans-1,2-Dichloroethylene								<8.34	5				0	GE	μg/L
Gross alpha								8.4E+00	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	μg/L
Mercury, total recoverable								0.294	1	J			0	GE	μg/L
Nickel, total recoverable								<6.67	1				0	GE	μg/L
Nitrate-nitrite as nitrogen								25,800	20		■		2	GE	μg/L
Nonvolatile beta								1.2E+01	1				0	GP	pCi/L
PCB 1254															μg/L
Radium, total alpha-emitting								5.8E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	μg/L
Silver, total recoverable								<3.33	1				0	GE	μg/L
Sodium, total recoverable								20,900	1		■		0	GE	μg/L
Sulfate								<1,670	1				0	GE	μg/L
1,1,2,2-Tetrachloroethane								<8.34	5				0	GE	μg/L
Tetrachloroethylene								104	5		■		2	GE	μg/L
Total phosphates (as P)								<83.3	1				0	GE	μg/L
1,1,1-Trichloroethane								10.0	5				0	GE	μg/L
Trichloroethylene								57.5	5		■		2	GE	μg/L
Uranium, total recoverable								<33.3	1				0	GE	μg/L
Zinc, total recoverable								5.71	1				0	GE	μg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 13A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101725.7 E47525.4	33.328280 °N 81.739290 °W	136.4-131.4 ft msl	346.7 ft msl	4" PVC	S	LL

SAMPLE DATE 10/18/94 01/20/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	207.4	212.6	ft msl
pH	5.0	4.9	pH
Sp. conductance	28	33	µS/cm
Water temperature	19.5	19.0	°C
Alkalinity as CaCO ₃	1	0	mg/L
Turbidity	0.7	0.6	NTU
Volume purged	1.87	3.47	well volumes
Sampling code			
Synchronous water level	212.7 (12/20/94)	211.0 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								27.4	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.40	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,420	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.2E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,700	2				0	GE	µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								2,280	1				0	GE	µg/L
Sulfate								1,450	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								1.29	1	J			0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								706	100				2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								19.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 13CC

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101728.8 E47525.7	33.328280 °N 81.739300 °W	196.8-192.0 ft msl	346.9 ft msl	4" PVC	S	GCL

SAMPLE DATE 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		225.4	ft msl
pH		4.9	pH
Sp. conductance		179	µS/cm
Water temperature		17.1	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.7	NTU
Volume purged		0.821	well volumes
Sampling code		X	
Synchronous water level	225.9 (12/20/94)	225.7 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								78.7	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,320	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								2.20	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								20.2	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								15,600	10		■		2	GE	µg/L
Nonvolatile beta								3.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								16,500	1		■		0	GE	µg/L
Sulfate								4,370	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								13.6	1		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								3.00	1				0	GE	µg/L
Trichloroethylene								12.1	1		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								181	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 13D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101778.1 E47517.5	33.328380 °N 81.739410 °W	231.5-211.5 ft msl	347.6 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		228.3	ft msl
pH		6.1	pH
Sp. conductance		573	µS/cm
Water temperature		17.1	°C
Alkalinity as CaCO ₃		33	mg/L
Turbidity		24.1	NTU
Volume purged		1.09	well volumes
Sampling code		X	
Synchronous water level	229.0 (12/20/94)	229.1 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								58.1	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								29.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								3,290	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								9.10	1			■	2	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.6E+00	1				0	GP	pCi/L
Lead, total recoverable								5.59	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								54,300	40			■	2	GE	µg/L
Nonvolatile beta								5.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								107,000	10			■	0	GE	µg/L
Sulfate								3,100	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								38.7	1			■	2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								12.4	1				0	GE	µg/L
Trichloroethylene								20.6	1			■	2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								20.1	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 57D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101829.5 E48701.5	33.330430 °N 81.736400 °W	229.6-210.1 ft msl	356.2 ft msl	4" PVC	S	M

SAMPLE DATE 01/31/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		231.3	ft msl
pH		4.9	pH
Sp. conductance		48	µS/cm
Water temperature		17.8	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		18.0	NTU
Volume purged		1.22	well volumes
Sampling code		X	
Synchronous water level	232.0 (12/21/94)	232.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								78.1	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.10	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,920	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,050	2				0	GE	µg/L
Nonvolatile beta								2.5E+00	1				0	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								2.6E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								4,850	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								309	25				2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								96.9	1				2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								8.64	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 58D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102200.6 E48693.5	33.331230 °N 81.737140 °W	230.5-211.1 ft msl	357.9 ft msl	4" PVC	S	M

SAMPLE DATE 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		231.9	ft msl
pH		5.2	pH
Sp. conductance		34	µS/cm
Water temperature		15.4	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		47.0	NTU
Volume purged		0.953	well volumes
Sampling code		X	
Synchronous water level	231.9 (12/21/94)	232.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								111	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								14.5	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								4,890	1		■		0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable								<6.67	1				0	GE	µg/L
Copper, total recoverable								84.2	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								3.69	1				1	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.8E+00	1				0	GP	pCi/L
Lead, total recoverable								50.9	1		■		2	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								9.09	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen								1,050	1				0	GE	µg/L
Nonvolatile beta								4.2E+00	1				0	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								1.6E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								2,450	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								780	100		■		2	GE	µg/L
Total phosphates (as P)								82.4	1	J			0	GE	µg/L
1,1,1-Trichloroethane								16.3	1				0	GE	µg/L
Trichloroethylene								1,820	100		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								144	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 59D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102182.2 E48314.8	33.330570 °N 81.738100 °W	229.3-209.9 ft msl	359.3 ft msl	4" PVC	S	M

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		230.8	ft msl
pH		6.1	pH
Sp. conductance		71	µS/cm
Water temperature		14.8	°C
Alkalinity as CaCO ₃		8	mg/L
Turbidity		15.0	NTU
Volume purged		1.09	well volumes
Sampling code		X	
Synchronous water level	230.9 (12/21/94)	231.1 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								226	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								38.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								3,470	1				0	GE	µg/L
Chlorobenzene								<418	250				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<418	250				0	GE	µg/L
1,1-Dichloroethylene								<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene								<418	250				0	GE	µg/L
Gross alpha								1.5E+00	1				0	GP	pCi/L
Lead, total recoverable								4.40	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								4,520	4		■		0	GE	µg/L
Nonvolatile beta								2.5E+00	1				0	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								2.7E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								6,990	1		■		0	GE	µg/L
Sulfate								1,380	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<418	250				0	GE	µg/L
Tetrachloroethylene								65,700	1000	J2	■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<418	250				0	GE	µg/L
Trichloroethylene								19,700	250	J2	■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								26.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 60D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101835.5 E48326.8	33.329830 °N 81.737390 °W	228.3-208.9 ft msl	354.5 ft msl	4" PVC	S	M

SAMPLE DATE 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		230.3	ft msl
pH		4.5	pH
Sp. conductance		49	µS/cm
Water temperature		17.4	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		20.5	NTU
Volume purged		1.14	well volumes
Sampling code		X	
Synchronous water level	231.1 (12/21/94)	231.3 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								97.6	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.71	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,150	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								2.40	1				0	GE	µg/L
1,1-Dichloroethylene								6.50	1				1	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.0E+01	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3,150	4		■		0	GE	µg/L
Nonvolatile beta								5.4E+00	1				0	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								5.6E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								4,350	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								168	5		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								6.30	1				0	GE	µg/L
Trichloroethylene								83.5	5		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								11.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 62B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101865.3 E47906.8	33.329210 °N 81.738560 °W	141.0-136.3 ft msl	349.1 ft msl	4" PVC	S	LL

SAMPLE DATE 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		214.9	ft msl
pH		5.3	pH
Sp. conductance		33	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		5	mg/L
Turbidity		2.6	NTU
Volume purged		3.61	well volumes
Sampling code			
Synchronous water level	214.4 (12/21/94)	210.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								94.8	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								14.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,030	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,030	1				0	GE	µg/L
Nonvolatile beta								6.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								2,950	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								42.1	1			■	2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								60.4	1			■	2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								9.11	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 62C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101857.2 E47895.0	33.329170 °N 81.738570 °W	190.0-185.2 ft msl	349.1 ft msl	4" PVC	S	UL

SAMPLE DATE 02/02/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		224.4	ft msl
pH		5.0	pH
Sp. conductance		186	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.3	NTU
Volume purged		3.03	well volumes
Sampling code			
Synchronous water level	225.0 (12/21/94)	224.3 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1						<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Barium, total recoverable	23.8	1						23.8	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Chloride	4,080	1						4,080	1				0	GE	µg/L
Chlorobenzene	<8.34	5						<8.34	5				0	GE	µg/L
Chromium, total recoverable	<6.67	1						<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1						<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<8.34	5						<8.34	5				0	GE	µg/L
1,1-Dichloroethylene	15.0	5						15.0	5				2	GE	µg/L
trans-1,2-Dichloroethylene	<8.34	5						<8.34	5				0	GE	µg/L
Gross alpha	3.8E+00	1						3.8E+00	1				0	GP	pCi/L
Lead, total recoverable	<5.00	1						<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.273	1						0.273	1	J			0	GE	µg/L
Nickel, total recoverable	<6.67	1						<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	12,100	20						12,100	20				2	GE	µg/L
Nonvolatile beta	4.7E+00	1						4.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.5E+00	1						1.5E+00	1				0	GP	pCi/L
Selenium, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Sodium, total recoverable	25,500	2						25,500	2				0	GE	µg/L
Sulfate	<1,670	1						<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<8.34	5						<8.34	5				0	GE	µg/L
Tetrachloroethylene	262	5						262	5				2	GE	µg/L
Total phosphates (as P)	<83.3	1						<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	10.0	5						10.0	5				0	GE	µg/L
Trichloroethylene	122	5						122	5				2	GE	µg/L
Uranium, total recoverable	<33.3	1						<33.3	1				0	GE	µg/L
Zinc, total recoverable	83.8	1						83.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 62D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101849.0 E47882.9	33.329130 °N 81.738590 °W	231.9-212.4 ft msl	349.5 ft msl	4" PVC	S	M

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		229.9	ft msl
pH		11.9	pH
Sp. conductance		485	µS/cm
Water temperature		13.3	°C
Alkalinity as CaCO ₃		114	mg/L
Turbidity		2.3	NTU
Volume purged		0.783	well volumes
Sampling code		X	
Synchronous water level	230.0 (12/21/94)	230.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	Unit	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								µg/L	1,860	1		■		2	GE	µg/L
Arsenic, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Barium, total recoverable								µg/L	34.7	1				0	GE	µg/L
Cadmium, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Chloride								µg/L	2,120	1				0	GE	µg/L
Chlorobenzene								µg/L	<16.7	10				0	GE	µg/L
Chromium, total recoverable								µg/L	<6.67	1				0	GE	µg/L
Cobalt, total recoverable								µg/L								µg/L
Copper, total recoverable								µg/L								µg/L
Cyanide								µg/L	<8.33	1				0	GE	µg/L
1,1-Dichloroethane								µg/L	<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								µg/L	<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene								µg/L	<16.7	10				0	GE	µg/L
Gross alpha								pCi/L	1.8E+00	1				0	GP	pCi/L
Lead, total recoverable								µg/L	<5.00	1				0	GE	µg/L
Mercury, total recoverable								µg/L	<0.333	1				0	GE	µg/L
Nickel, total recoverable								µg/L	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								µg/L	7,200	8		■		1	GE	µg/L
Nonvolatile beta								pCi/L	8.9E+00	1				0	GP	pCi/L
PCB 1254								µg/L								µg/L
Radium, total alpha-emitting								pCi/L	3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Silver, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Sodium, total recoverable								µg/L	45,900	3		■		0	GE	µg/L
Sulfate								µg/L	6,680	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								µg/L	<16.7	10				0	GE	µg/L
Tetrachloroethylene								µg/L	178	10		■		2	GE	µg/L
Total phosphates (as P)								µg/L	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								µg/L	16.0	10	J			0	GE	µg/L
Trichloroethylene								µg/L	60.0	10		■		2	GE	µg/L
Uranium, total recoverable								µg/L	<33.3	1				0	GE	µg/L
Zinc, total recoverable								µg/L	3.98	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 63B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101184.4 E47861.0	33.327630 °N 81.737350 °W	140.9-136.2 ft msl	346.9 ft msl	4" PVC	S	LL

SAMPLE DATE 02/02/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		212.0	ft msl
pH		5.1	pH
Sp. conductance		33	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.2	NTU
Volume purged		2.81	well volumes
Sampling code			
Synchronous water level	212.5 (12/20/94)	210.9 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.17	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,140	1				0	GE	µg/L
Chlorobenzene								<8.34	5	J1			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<8.34	5	J1			0	GE	µg/L
1,1-Dichloroethylene								<8.34	5	J1			0	GE	µg/L
trans-1,2-Dichloroethylene								<8.34	5	J1			0	GE	µg/L
Gross alpha								7.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,850	1				0	GE	µg/L
Nonvolatile beta								8.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								2,320	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.34	5	J1			0	GE	µg/L
Tetrachloroethylene								15.0	5	J1	■		2	GE	µg/L
Total phosphates (as P)								52.8	1	J			0	GE	µg/L
1,1,1-Trichloroethane								<8.34	5	J1			0	GE	µg/L
Trichloroethylene								300	5	J1	■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								15.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 63C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101174.6 E47849.2	33.327590 °N 81.737370 °W	195.8-191.1 ft msl	347 ft msl	4" PVC	S	UL

SAMPLE DATE 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.1	ft msl
pH		5.2	pH
Sp. conductance		41	µS/cm
Water temperature		18.9	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.7	NTU
Volume purged		4.15	well volumes
Sampling code			
Synchronous water level	221.8 (12/20/94)	221.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.54	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,570	1				0	GE	µg/L
Chlorobenzene								<1.67	1	J1			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1	J1			0	GE	µg/L
1,1-Dichloroethylene								<1.67	1	J1			0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1	J1			0	GE	µg/L
Gross alpha								1.0E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,300	2				0	GE	µg/L
Nonvolatile beta								5.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								4,210	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1	J1			0	GE	µg/L
Tetrachloroethylene								15.2	1	J1	■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1	J1			0	GE	µg/L
Trichloroethylene								5.80	1	J1	■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								20.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 63D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101165.2 E47837.4	33.327550 °N 81.737380 °W	232.8-212.8 ft msl	346.8 ft msl	4" PVC	S	MGC

SAMPLE DATE 02/03/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		229.3	ft msl
pH		9.8	pH
Sp. conductance		78	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		21	mg/L
Turbidity		12.6	NTU
Volume purged		0.926	well volumes
Sampling code		X	
Synchronous water level	230.2 (12/20/94)	230.4 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								908	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.14	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,320	1				0	GE	µg/L
Chlorobenzene								<8.34	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<8.34	5				0	GE	µg/L
1,1-Dichloroethylene								<8.34	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.34	5				0	GE	µg/L
Gross alpha								9.2E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,840	2		■		0	GE	µg/L
Nonvolatile beta								2.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								5,550	1		■		0	GE	µg/L
Sulfate								1,050	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.34	5				0	GE	µg/L
Tetrachloroethylene								183	5		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<8.34	5				0	GE	µg/L
Trichloroethylene								28.0	5		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								4.98	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 64B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101831.0 E46579.7	33.326960 °N 81.741990 °W	124.3-119.6 ft msl	348.3 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/18/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		210.7	ft msl
pH		6.0	pH
Sp. conductance		48	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		0.5	NTU
Volume purged		2.58	well volumes
Sampling code			
Synchronous water level	210.8 (12/20/94)	210.1 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								23.9	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,660	1				0	GE	µg/L
Chlorobenzene								<83.5	50	J			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<83.5	50				0	GE	µg/L
1,1-Dichloroethylene								<83.5	50	J1			0	GE	µg/L
trans-1,2-Dichloroethylene								<83.5	50				0	GE	µg/L
Gross alpha								7.0E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3,520	4		■		0	GE	µg/L
Nonvolatile beta								2.5E+00	1				0	GP	pCi/L
PCB 1254								<0.817	1				0	GE	µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								3,780	1				0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<83.5	50	J			0	GE	µg/L
Tetrachloroethylene								58.0	50	J1	■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<83.5	50	J			0	GE	µg/L
Trichloroethylene								2,960	50	J1	■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								13.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 64C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101842.9 E46589.2	33.327010 °N 81.741980 °W	181.2-176.5 ft msl	348.4 ft msl	4" PVC	S	UL

SAMPLE DATE 01/30/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		223.9	ft msl
pH		4.7	pH
Sp. conductance		142	µS/cm
Water temperature		18.1	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.4	NTU
Volume purged		3.66	well volumes
Sampling code			
Synchronous water level	223.7 (12/20/94)	223.7 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								182	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								26.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								3,550	1				0	GE	µg/L
Chlorobenzene								<8.35	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<8.35	5				0	GE	µg/L
1,1-Dichloroethylene								<8.35	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.35	5				0	GE	µg/L
Gross alpha								8.6E+00	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.341	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								14,300	10		■		2	GE	µg/L
Nonvolatile beta								6.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.4E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable								11,900	1		■		0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.35	5				0	GE	µg/L
Tetrachloroethylene								471	5		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane								<8.35	5				0	GE	µg/L
Trichloroethylene								73.2	5		■		2	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								5.13	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 64D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101854.8 E46598.5	33.327050 °N 81.741980 °W	230.1-210.1 ft msl	348.6 ft msl	4" PVC	S	MGC

SAMPLE DATE 02/02/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		226.3	ft msl
pH		5.8	pH
Sp. conductance		121	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		23	mg/L
Turbidity		0.6	NTU
Volume purged		6.39	well volumes
Sampling code			
Synchronous water level	227.8 (12/20/94)	227.9 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1						<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Barium, total recoverable	16.9	1						16.9	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Chloride	3,460	1						3,460	1				0	GE	µg/L
Chlorobenzene	<1.67	1						<1.67	1	J1			0	GE	µg/L
Chromium, total recoverable	<6.67	1						<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1						<8.33	1	J3			0	GE	µg/L
1,1-Dichloroethane	<1.67	1						<1.67	1	J1			0	GE	µg/L
1,1-Dichloroethylene	<1.67	1						<1.67	1	J1			0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1						<1.67	1	J1			0	GE	µg/L
Gross alpha	1.1E+00	1						1.1E+00	1	UI			0	GP	pCi/L
Lead, total recoverable	<5.00	1						<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1						<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1						<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	5,680	4						5,680	4		■		1	GE	µg/L
Nonvolatile beta	2.3E+00	1						2.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	2.0E-01	1						2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Sodium, total recoverable	17,900	1						17,900	1		■		0	GE	µg/L
Sulfate	3,440	1						3,440	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1						<1.67	1	J1			0	GE	µg/L
Tetrachloroethylene	2.70	1						2.70	1	J1			1	GE	µg/L
Total phosphates (as P)	<83.3	1						<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.67	1						<1.67	1	J1			0	GE	µg/L
Trichloroethylene	<1.67	1						<1.67	1	J1			0	GE	µg/L
Uranium, total recoverable	<33.3	1						<33.3	1				0	GE	µg/L
Zinc, total recoverable	20.2	1						20.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

Table 3. Groundwater Monitoring Results for Background Wells

WELL MSB 29B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>									
N107319.3 E51217.5	33.346670 °N 81.740450 °W	151.7-145.1 ft msl	365 ft msl	4" PVC	S	LL									
SAMPLE DATE		10/31/94		01/30/95											
FIELD DATA															
<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>			<u>Unit</u>										
Water elevation	225.2	225.3			ft msl										
pH	4.5	4.6			pH										
Sp. conductance	30	32			µS/cm										
Water temperature	19.1	18.3			°C										
Alkalinity as CaCO ₃	0				mg/L										
Turbidity	0.8	0.4			NTU										
Volume purged	3.67	2.78			well volumes										
Sampling code															
Synchronous water level	225.0 (12/20/94)		225.4 (03/22/95)		ft msl										
ANALYTICAL DATA															
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								44.4	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.01	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,110	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha	3.8E-01	1	UI			0	GP	2.0E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,260	1				0	GE	µg/L
Nonvolatile beta	1.3E+00	1	UI			0	GP	1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.4E+00	1	J			0	GP	1.9E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 29C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107315.0 E51206.6	33.346640 °N 81.740470 °W	179.7-174.1 ft msl	365 ft msl	4" PVC	S	UL

SAMPLE DATE 10/31/94 01/30/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	231.3	230.5	ft msl
pH	4.6	4.9	pH
Sp. conductance	29	31	µS/cm
Water temperature	19.0	18.2	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	1.0	0.2	NTU
Volume purged	3.07	4.65	well volumes
Sampling code			
Synchronous water level	230.9 (12/20/94)	231.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								27.7	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.92	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								1,820	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha	1.4E+00	1	J			0	GP	2.4E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,390	1				0	GE	µg/L
Nonvolatile beta	1.5E+00	1	J			0	GP	1.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	2.0E+00	1				0	GP	1.9E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								6.63	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 29D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107323.3 E51226.9	33.346700 °N 81.740430 °W	227.6-207.0 ft msl	364.9 ft msl	4" PVC	S	MGCL

SAMPLE DATE 10/31/94 01/30/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	234.4	232.9	ft msl
pH	4.4	4.6	pH
Sp. conductance	35	35	µS/cm
Water temperature	18.8	18.2	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	1.1	0.3	NTU
Volume purged	6.02	4.54	well volumes
Sampling code			
Synchronous water level	232.8 (12/20/94)	233.1 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								40.4	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.06	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								2,290	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha	1.0E+01	1				1	GP	6.7E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,620	1				0	GE	µg/L
Nonvolatile beta	4.2E+00	1				0	GP	6.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	9.4E+00	1				0	GP	5.9E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 43A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107275.3 E49293.7	33.343430 °N 81.745430 °W	140.5-134.9 ft msl	357.7 ft msl	4" PVC	S	LL

SAMPLE DATE 10/31/94 01/30/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	229.9	228.9	ft msl
pH	5.3	5.1	pH
Sp. conductance	22	23	µS/cm
Water temperature	19.3	18.5	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.1	0.5	NTU
Volume purged	3.02	2.63	well volumes
Sampling code			
Synchronous water level	229.6 (12/20/94)	230.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.76	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								1,000	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha	1.7E-01	1	UI			0	GP	6.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,110	1				0	GE	µg/L
Nonvolatile beta	1.2E+00	1	UI			0	GP	7.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	5.0E-01	1	J			0	GP	6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								5.09	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 43B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107274.6 E49311.8	33.343460 °N 81.745380 °W	175.5-169.9 ft msl	357.8 ft msl	4" PVC	S	UL

SAMPLE DATE 10/31/94 01/30/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	230.0	229.9	ft msl
pH	4.8	4.9	pH
Sp. conductance	24	26	µS/cm
Water temperature	19.5	18.8	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.4	0.2	NTU
Volume purged	4.13	3.23	well volumes
Sampling code			
Synchronous water level	229.8 (12/20/94)	230.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								1,290	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha	2.6E+00	1				0	TM	3.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,230	1				0	GE	µg/L
Nonvolatile beta	2.7E+00	1				0	TM	1.8E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.2E+00	1	J			0	GP	1.6E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								4.91	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 43D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107274.2 E49322.0	33.343480 °N 81.745360 °W	220.8-200.2 ft msl	358 ft msl	4" PVC	S	MGCL

SAMPLE DATE 10/31/94 01/30/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	232.1	231.7	ft msl
pH	4.8	4.7	pH
Sp. conductance	22	23	µS/cm
Water temperature	19.5	18.0	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	1.2	0.5	NTU
Volume purged	5.92	4.21	well volumes
Sampling code			
Synchronous water level	229.8 (12/20/94)	232.2 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								54.1	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.64	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride								1,440	1				0	GE	µg/L
Chlorobenzene	<1.00	1			0		GE	<16.7	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1			0		GE	<16.7	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1			0		GE	<16.7	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1			0		GE	<16.7	1				0	GE	µg/L
Gross alpha	6.2E-01	1	UI		0		GP	1.1E+00	1				0	GP	pCi/L
Lead, total recoverable								4.05	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								744	1				0	GE	µg/L
Nonvolatile beta	7.6E-01	1	UI		0		GP	2.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	7.0E-01	1	J		0		GP	9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1			0		GE	<16.7	1				0	GE	µg/L
Trichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable								<33.3	1				0	GE	µg/L
Zinc, total recoverable								2.42	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

Table 4. Groundwater Monitoring Results for Plume Definition Wells

WELL ABP 1A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone		
N97501.6 E44425.6	33.313880 °N 81.739240 °W	202.9-172.9 ft msl	359.9 ft msl	4" PVC	S	GCL		
SAMPLE DATE			01/18/95					
FIELD DATA								
Parameter	4Q94	1Q95	Unit					
Water elevation		224.8	ft msl					
pH		5.2	pH					
Sp. conductance		12	µS/cm					
Water temperature		19.2	°C					
Alkalinity as CaCO ₃		1	mg/L					
Turbidity		0.6	NTU					
Volume purged		3.11	well volumes					
Sampling code								
Synchronous water level	225.0 (12/20/94)	224.9 (03/22/95)	ft msl					
ANALYTICAL DATA								
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable							0	GE µg/L
Arsenic, total recoverable							0	GE µg/L
Barium, total recoverable							0	GE µg/L
Cadmium, total recoverable							0	GE µg/L
Chloride							0	GE µg/L
Chlorobenzene							0	GE µg/L
Chromium, total recoverable							0	GE µg/L
Cobalt, total recoverable								µg/L
Copper, total recoverable								µg/L
Cyanide							0	GE µg/L
1,1-Dichloroethane							0	GE µg/L
1,1-Dichloroethylene							0	GE µg/L
trans-1,2-Dichloroethylene							0	GE µg/L
Gross alpha							0	GP pCi/L
Lead, total recoverable							0	GE µg/L
Mercury, total recoverable							0	GE µg/L
Nickel, total recoverable							0	GE µg/L
Nitrate-nitrite as nitrogen								µg/L
Nonvolatile beta							0	GP pCi/L
PCB 1254								µg/L
Radium, total alpha-emitting							0	GP pCi/L
Selenium, total recoverable							0	GE µg/L
Silver, total recoverable							0	GE µg/L
Sodium, total recoverable								µg/L
Sulfate							0	GE µg/L
1,1,2,2-Tetrachloroethane							2	GE µg/L
Tetrachloroethylene								µg/L
Total phosphates (as P)							0	GE µg/L
1,1,1-Trichloroethane							2	GE µg/L
Trichloroethylene								µg/L
Uranium, total recoverable							0	GE µg/L
Zinc, total recoverable								µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ABP 2A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97764.3 E44118.8	33.313960 °N 81.740550 °W	211.1-181.1 ft msl	371.9 ft msl	4" PVC	S	GCL

SAMPLE DATE 01/19/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		223.8	ft msl
pH		4.1	pH
Sp. conductance		89	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		1.6	NTU
Volume purged		5.78	well volumes
Sampling code			
Synchronous water level	223.8 (12/20/94)	223.7 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								144	1	VV	■		2	WA	µg/L
Arsenic, total recoverable								1.40	1	J			0	WA	µg/L
Barium, total recoverable								35.7	1				0	WA	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.9E+01	1		■		2	TM	pCi/L
Lead, total recoverable								2.00	1	JVV			0	WA	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								1.70	1	J			0	WA	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.3E+01	1				0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+01	1		■		1	TM	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<1.40	1				0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								2.17	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.20	1	JVV			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ABP 3

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97794.1 E44509.3	33.314660 °N 81.739580 °W	236.9-206.9 ft msl	353.7 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/18/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		225.1	ft msl
pH		5.0	pH
Sp. conductance		12	µS/cm
Water temperature		19.1	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.2	NTU
Volume purged		5.01	well volumes
Sampling code			
Synchronous water level	225.3 (12/20/94)	225.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.26	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								7.9E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								3.17	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ABP 3C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97778.2 E44506.3	33.314620 °N 81.739560 °W	165.3-160.3 ft msl	354.5 ft msl	4" PVC	S	UL

SAMPLE DATE 01/18/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		198.0	ft msl
pH		6.5	pH
Sp. conductance		61	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		15	mg/L
Turbidity		1.2	NTU
Volume purged		3.11	well volumes
Sampling code			
Synchronous water level	197.7 (12/20/94)	198.8 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								43.7	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								17.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.7E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								21.6	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								41.5	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								8.64	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ABP 4

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N97489.7 E44096.0	33.313310 °N 81.740080 °W	212.5-182.5 ft msl	364.3 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		223.7	ft msl
pH		5.0	pH
Sp. conductance		11	µS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.4	NTU
Volume purged		2.89	well volumes
Sampling code			
Synchronous water level	223.4 (12/20/94)	223.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								11.5	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								83.4	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ABP 8C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N97855.6 E43968.7	33.313910 °N 81.741130 °W	190.6-185.5 ft msl	372.1 ft msl	4" PVC	S	UL

SAMPLE DATE 01/31/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		201.8	ft msl
pH		12.8	pH
Sp. conductance		3,000	µS/cm
Water temperature		16.0	°C
Alkalinity as CaCO ₃		937	mg/L
Turbidity		14.4	NTU
Volume purged		0.281	well volumes
Sampling code		X	
Synchronous water level	198.0 (12/20/94)	198.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								3,540	10		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								396	10				0	GE	µg/L
Cadmium, total recoverable								<33.3	10				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<66.7	10				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.5E+00	1				0	GP	pCi/L
Lead, total recoverable								12.2	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<66.7	10				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.6E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.7E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<33.3	10				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<33.3	10				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ABP 8D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97854.9 E43984.1	33.313940 °N 81.741090 °W	228.2-208.1 ft msl	370.9 ft msl	4" PVC	S	M

SAMPLE DATE 01/19/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		223.4	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		L	
Synchronous water level	223.2 (12/20/94)	223.1 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ABW 1

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105939.9 E55016.4	33.349830 °N 81.727760 °W	215.1-185.1 ft msl	324.8 ft msl	4" PVC	S	UL

SAMPLE DATE 01/12/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		226.2	ft msl
pH		4.5	pH
Sp. conductance		27	µS/cm
Water temperature		17.7	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.8	NTU
Volume purged		3.67	well volumes
Sampling code			
Synchronous water level	226.3 (12/20/94)	226.8 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.07	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.2E+00	1				0	GP	pCi/L
Lead, total recoverable								4.17	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.4E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								2.99	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AC 1A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105865.0 E42238.8	33.328790 °N 81.761260 °W	145.7-140.7 ft msl	262.1 ft msl	4" Steel	S	UL

SAMPLE DATE 01/13/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		212.8	ft msl
pH		5.0	pH
Sp. conductance		23	µS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.6	NTU
Volume purged		7.10	well volumes
Sampling code			
Synchronous water level	213.4 (12/20/94)	214.1 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								23.3	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.76	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								7.6E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								440	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AC 1B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105862.8 E42250.5	33.328800 °N 81.761230 °W	202.1-197.1 ft msl	262 ft msl	4" Steel	S	GCL

SAMPLE DATE 01/13/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		213.4	ft msl
pH		5.1	pH
Sp. conductance		27	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		1.1	NTU
Volume purged		22.4	well volumes
Sampling code			
Synchronous water level	213.4 (12/20/94)	214.1 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								24.2	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.46	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.8E+00	1				0	GP	pCi/L
Lead, total recoverable								5.55	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.5E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								910	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AC 2A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105636.4 E46428.6	33.335130 °N 81.749790 °W	146.0-141.0 ft msl	344.7 ft msl	4" PVC	S	UL

SAMPLE DATE 01/13/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		221.3	ft msl
pH		5.4	pH
Sp. conductance		33	µS/cm
Water temperature		18.5	°C
Alkalinity as CaCO ₃		7	mg/L
Turbidity		0.4	NTU
Volume purged		3.15	well volumes
Sampling code			
Synchronous water level	221.7 (12/20/94)	221.9 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								27.9	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.81	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.70	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AC 2B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105648.7 E46444.5	33.335180 °N 81.749770 °W	236.4-216.4 ft msl	344.8 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/13/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		227.4	ft msl
pH		5.0	pH
Sp. conductance		21	µS/cm
Water temperature		19.4	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.7	NTU
Volume purged		3.75	well volumes
Sampling code			
Synchronous water level	227.5 (12/20/94)	227.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.33	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable															
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.2E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								7.1E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable								8.48	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AC 3A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100989.1 E42119.8	33.317820 °N 81.752090 °W	153.6-148.6 ft msl	302.3 ft msl	4" PVC	S	UL

SAMPLE DATE 01/13/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		210.6	ft msl
pH		6.1	pH
Sp. conductance		51	µS/cm
Water temperature		19.5	°C
Alkalinity as CaCO ₃		12	mg/L
Turbidity		2.4	NTU
Volume purged		2.71	well volumes
Sampling code			
Synchronous water level	211.1 (12/20/94)	211.1 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								26.5	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								11.2	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								2.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								0.0E+00	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								264	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AC 3B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N100996.5 E42113.6	33.317830 °N 81.752120 °W	213.4-193.4 ft msl	302.5 ft msl	4" PVC	S	M

SAMPLE DATE 01/13/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		212.5	ft msl
pH		9.6	pH
Sp. conductance		82	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		21	mg/L
Turbidity		0.6	NTU
Volume purged		5.11	well volumes
Sampling code			
Synchronous water level	213.1 (12/20/94)	213.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								132	1	VVY	■		2	WA	µg/L
Arsenic, total recoverable								3.30	1	JY			0	WA	µg/L
Barium, total recoverable								5.10	1	JY			0	WA	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								5.00	1	JY			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.5E+00	1	J1			0	TM	pCi/L
Lead, total recoverable								1.60	1	JY3			0	WA	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								1.10	1	JVVY			0	WA	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								6.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1	J1			0	TM	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								1.50	1	VY			0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								5.90	1	JY			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ACB 1A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102622.9 E51369.9	33.336540 °N 81.730910 °W	247.6-217.6 ft msl	359.6 ft msl	4" PVC	S	M

SAMPLE DATE	10/21/94	01/13/95
-------------	----------	----------

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	238.5	238.4	ft msl
pH	5.7	5.8	pH
Sp. conductance	66	58	µS/cm
Water temperature	18.7	19.0	°C
Alkalinity as CaCO ₃	7	8	mg/L
Turbidity	4.4	2.1	NTU
Volume purged	8.92	4.99	well volumes
Sampling code			
Synchronous water level	238.2 (12/20/94)	238.7 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	1.2E+00	1	J			0	GP	1.7E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								6.31	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta	9.6E-01	1	UI			0	GP	1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.0E+00	1	J			0	GP	1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable								3.75	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								5,400	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ACB 2A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102367.4 E51561.3	33.336290 °N 81.729910 °W	237.8-207.8 ft msl	349.8 ft msl	4" PVC	S	M

SAMPLE DATE 10/21/94 01/13/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	244.3	239.4	ft msl
pH	5.3	5.9	pH
Sp. conductance	57	51	µS/cm
Water temperature	18.5	18.6	°C
Alkalinity as CaCO ₃	5	7	mg/L
Turbidity	1.3	0.5	NTU
Volume purged	8.03	6.33	well volumes
Sampling code			
Synchronous water level	239.3 (12/20/94)	239.8 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	-1.5E-01	1	UI			0	GP	2.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								3.66	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta	7.1E-01	1	UI			0	GP	6.0E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	-2.0E-01	1	UI			0	GP	-3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								3.91	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								9,550	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ACB 3A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102154.3 E51313.3	33.335410 °N 81.730150 °W	236.3-206.3 ft msl	348.3 ft msl	4" PVC	S	M

SAMPLE DATE 10/21/94 01/13/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	239.3	239.1	ft msl
pH	4.7	5.4	pH
Sp. conductance	106	253	µS/cm
Water temperature	18.2	18.5	°C
Alkalinity as CaCO ₃	0	1	mg/L
Turbidity	1.6	0.9	NTU
Volume purged	8.50	4.56	well volumes
Sampling code			
Synchronous water level	239.0 (12/20/94)	239.6 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								54.0	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								24.9	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	6.7E+00	1				0	GP	3.7E+01	1		■		2	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.709	1				0	GE	µg/L
Nickel, total recoverable								20.7	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta	3.2E+00	1	J			0	GP	1.2E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	6.3E+00	1		■		0	GP	1.4E+01	1		■		1	GP	pCi/L
Selenium, total recoverable								6.72	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								125,000	2		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								9.70	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ACB 4A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102343.9 E51116.2	33.335510 °N 81.731040 °W	241.7-211.7 ft msl	359.1 ft msl	4" PVC	S	MGC

SAMPLE DATE 10/21/94 01/18/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	239.7	239.2	ft msl
pH	4.2	4.2	pH
Sp. conductance	501	502	µS/cm
Water temperature	19.0	18.9	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.9	0.7	NTU
Volume purged	6.80	6.10	well volumes
Sampling code			
Synchronous water level	239.7 (12/20/94)	239.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								6,150	1	V	■		2	WA	µg/L
Arsenic, total recoverable								3.20	1	J			0	WA	µg/L
Barium, total recoverable								14.3	1				0	WA	µg/L
Cadmium, total recoverable								2.00	1	J			0	WA	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								1.40	1	J			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	5.9E+01	1		■		2	GP	1.7E+02	1		■		2	TM	pCi/L
Lead, total recoverable								5.73	1				0	GE	µg/L
Mercury, total recoverable								0.355	1				0	GE	µg/L
Nickel, total recoverable								96.4	1		■		1	WA	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta	1.4E+01	1				0	GP	8.1E+01	1		■		2	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	5.5E+01	1		■		2	GP	5.9E+01	1		■		2	TM	pCi/L
Selenium, total recoverable								5.00	1				0	GE	µg/L
Silver, total recoverable								<1.40	1				0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate								246,000	5		■		1	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								344	1	V			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 4A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104131.6 E51469.8	33.340040 °N 81.733580 °W	126.3-121.3 ft msl	380.5 ft msl	4" PVC	S	MCBC

SAMPLE DATE 10/26/94 01/25/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	220.7	219.9	ft msl
pH	6.4	7.0	pH
Sp. conductance	44	40	µS/cm
Water temperature	19.2	18.7	°C
Alkalinity as CaCO ₃	12	3	mg/L
Turbidity	1.7	0.6	NTU
Volume purged	2.75	2.60	well volumes
Sampling code			
Synchronous water level	219.8 (12/20/94)	220.4 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								22.7	1	J			0	GE	µg/L
Arsenic, total recoverable								2.28	1	J			0	GE	µg/L
Barium, total recoverable								5.49	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	1,380	1				0	GE	1,920	1				0	GE	µg/L
Chlorobenzene	<25.0	25				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<25.0	25				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<25.0	25				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<25.0	25				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								3.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	785	1				0	GE	884	1				0	GE	µg/L
Nonvolatile beta								6.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.2E+00	1	J			0	GP	1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<25.0	25				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	42.5	25				■	2	29.1	1			■	2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<25.0	25				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	523	25				■	2	358	10			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 4B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N104145.6 E51482.7	33.340090 °N 81.733580 °W	157.3-152.3 ft msl	380.4 ft msl	4" PVC	S	LL									
SAMPLE DATE		10/27/94	02/01/95												
FIELD DATA															
Parameter	4Q94	1Q95			Unit										
Water elevation	225.0	225.8			ft msl										
pH	4.7	4.9			pH										
Sp. conductance	29	27			µS/cm										
Water temperature	18.9	18.6			°C										
Alkalinity as CaCO ₃	0	0			mg/L										
Turbidity	1.0	1.5			NTU										
Volume purged	4.72	2.70			well volumes										
Sampling code															
Synchronous water level	225.2 (12/20/94)	225.8 (03/23/95)			ft msl										
ANALYTICAL DATA															
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								29.8	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.45	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	3,780	1			0		GE	4,400	1		■		0	GE	µg/L
Chlorobenzene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1			0		GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Gross alpha								7.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1			0		GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	584	1			0		GE	724	1				0	GE	µg/L
Nonvolatile beta								1.4E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	9.0E-01	1	J		0		GP	1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1			0		GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Trichloroethylene	3.60	1			1		GE	3.30	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 4D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104154.7 E51489.0	33.340120 °N 81.733580 °W	233.4-213.4 ft msl	380.3 ft msl	4" PVC	S	M

SAMPLE DATE 10/28/94 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	233.4	234.1	ft msl
pH	5.1	4.8	pH
Sp. conductance	39	49	µS/cm
Water temperature	18.5	17.4	°C
Alkalinity as CaCO ₃	3	3	mg/L
Turbidity	5.9	18.9	NTU
Volume purged	0.916	1.18	well volumes
Sampling code	X	X	
Synchronous water level	233.9 (12/20/94)	234.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								129	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.95	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	2,500	1				0	GE	3,450	1				0	GE	µg/L
Chlorobenzene	<2.00	2				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<2.00	2				0	GE	1.23	1	J			0	GE	µg/L
1,1-Dichloroethylene	<2.00	2				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<2.00	2				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.1E+01	1				1	GP	pCi/L
Lead, total recoverable								7.81	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	2,470	2		■		0	GE	1,970	2				0	GE	µg/L
Nonvolatile beta								2.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	5.7E+00	1		■		0	GP	8.6E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<2.00	2				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	10.0	2		■		2	GE	8.99	1		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<2.00	2				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	135	2		■		2	GE	129	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								22.6	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 5

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104083.4 E51467.2	33.339930 °N 81.733500 °W	242.1-222.1 ft msl	379.6 ft msl	4" PVC	S	MGCL

SAMPLE DATE 10/28/94 02/01/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	234.3	234.6	ft msl
pH	5.3	5.3	pH
Sp. conductance	47	42	µS/cm
Water temperature	18.8	19.0	°C
Alkalinity as CaCO ₃	5	5	mg/L
Turbidity	27.2	4.5	NTU
Volume purged	9.87	10.7	well volumes
Sampling code			
Synchronous water level	234.3 (12/20/94)	234.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								111	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.46	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	2,740	1			0		GE	3,250	1				0	GE	µg/L
Chlorobenzene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1			0		GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Gross alpha								4.1E+00	1	J			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1			0		GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	708	1			0		GE	726	1				0	GE	µg/L
Nonvolatile beta								2.6E+00	1	J			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	3.7E+00	1			0		GP	2.9E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1			0		GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	2.70	1			1		GE	2.15	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Trichloroethylene	39.7	1			■	2	GE	36.6	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 6

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104034.1 E51466.0	33.339810 °N 81.733410 °W	242.6-222.6 ft msl	377.2 ft msl	4" PVC	S	GCL

SAMPLE DATE 10/28/94 02/02/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	234.4	234.7	ft msl
pH	5.8	5.5	pH
Sp. conductance	44	48	µS/cm
Water temperature	18.4	17.9	°C
Alkalinity as CaCO ₃	10	10	mg/L
Turbidity	9.9	62.8	NTU
Volume purged	0.516	0.380	well volumes
Sampling code	X	X	
Synchronous water level	234.5 (12/20/94)	234.9 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								2,320	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.31	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	2,340	1				0	GE	2,790	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.1E+00	1				0	GP	pCi/L
Lead, total recoverable								38.2	1				1	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	4.88	1	J	■		0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	236	1				0	GE	365	1				0	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.0E+00	1	J			0	GP	1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								149	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	7.20	1		■		2	GE	11.4	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								24.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 7

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103920.0 E51624.9	33.339820 °N 81.732760 °W	242.1-222.1 ft msl	369.9 ft msl	4" PVC	S	M

SAMPLE DATE 10/28/94 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	234.7	235.0	ft msl
pH	6.3	6.0	pH
Sp. conductance	66	66	µS/cm
Water temperature	17.7	17.8	°C
Alkalinity as CaCO ₃	28	25	mg/L
Turbidity	9.9	8.6	NTU
Volume purged	1.09	1.18	well volumes
Sampling code	X	X	
Synchronous water level	234.8 (12/20/94)	235.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								156	1		■	2		GE	µg/L
Arsenic, total recoverable								<3.33	1			0		GE	µg/L
Barium, total recoverable								8.38	1			0		GE	µg/L
Cadmium, total recoverable								<3.33	1			0		GE	µg/L
Chloride	1,920	1	Y			0	GE	2,070	1			0		GE	µg/L
Chlorobenzene	<1.00	1	Y			0	GE	<1.67	1			0		GE	µg/L
Chromium, total recoverable								<6.67	1			0		GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1	Y			0	GE	<8.33	1			0		GE	µg/L
1,1-Dichloroethane	<1.00	1	Y			0	GE	<1.67	1			0		GE	µg/L
1,1-Dichloroethylene	<1.00	1	Y			0	GE	<1.67	1			0		GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1	Y			0	GE	<1.67	1			0		GE	µg/L
Gross alpha								1.2E+00	1			0		GP	pCi/L
Lead, total recoverable								10.8	1			0		GE	µg/L
Mercury, total recoverable								<0.333	1			0		GE	µg/L
Nickel, total recoverable	6.97	1		■		0	GE	<6.67	1			0		GE	µg/L
Nitrate-nitrite as nitrogen	186	1	Y			0	GE	239	1			0		GE	µg/L
Nonvolatile beta								1.0E+00	1	UI		0		GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	4.0E-01	1	UI			0	GP	1.0E-01	1	UI		0		GP	pCi/L
Selenium, total recoverable								<3.33	1			0		GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1			0		GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1	Y			0	GE	<1.67	1			0		GE	µg/L
Tetrachloroethylene	<1.00	1	Y			0	GE	<1.67	1			0		GE	µg/L
Total phosphates (as P)								<83.3	1			0		GE	µg/L
1,1,1-Trichloroethane	<1.00	1	Y			0	GE	<1.67	1			0		GE	µg/L
Trichloroethylene	4.10	1	Y			1	GE	4.16	1			1		GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								114	1			0		GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 7A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103987.1 E51591.0	33.339920 °N 81.732980 °W	125.6-115.6 ft msl	373.6 ft msl	4" PVC	S	MCBC

SAMPLE DATE 10/28/94 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	219.5	220.3	ft msl
pH	5.9	5.9	pH
Sp. conductance	27	25	µS/cm
Water temperature	18.7	18.5	°C
Alkalinity as CaCO ₃	4	5	mg/L
Turbidity	1.5	1.7	NTU
Volume purged	2.60	2.87	well volumes
Sampling code			
Synchronous water level	219.8 (12/20/94)	220.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.63	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	1,390	1	Y			0	GE	1,690	1				0	GE	µg/L
Chlorobenzene	<2.00	2	Y			0	GE	<8.34	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1	Y			0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<2.00	2	Y			0	GE	<8.34	5				0	GE	µg/L
1,1-Dichloroethylene	<2.00	2	Y			0	GE	<8.34	5				0	GE	µg/L
trans-1,2-Dichloroethylene	<2.00	2	Y			0	GE	<8.34	5				0	GE	µg/L
Gross alpha								4.2E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	792	1	Y			0	GE	811	1				0	GE	µg/L
Nonvolatile beta								8.0E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	2.0E-01	1	UI			0	GP	3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<2.00	2	Y			0	GE	<8.34	5				0	GE	µg/L
Tetrachloroethylene	15.8	2	Y	■		2	GE	16.9	5		■		2	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<2.00	2	Y			0	GE	<8.34	5				0	GE	µg/L
Trichloroethylene	200	5	Y	■		2	GE	268	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								5.37	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 7B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103972.0 E51590.3	33.339880 °N 81.732960 °W	162.9-152.9 ft msl	373 ft msl	4" PVC	S	LL

SAMPLE DATE 10/28/94 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	225.2	226.0	ft msl
pH	5.1	5.0	pH
Sp. conductance	26	24	µS/cm
Water temperature	18.6	18.8	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.3	0.5	NTU
Volume purged	3.16	4.17	well volumes
Sampling code			
Synchronous water level	225.4 (12/20/94)	226.1 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	2,870	1	Y			0	GE	3,350	1				0	GE	µg/L
Chlorobenzene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable													0	GE	µg/L
Copper, total recoverable													0	GE	µg/L
Cyanide	<5.00	1	Y			0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Gross alpha								2.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	329	1	Y			0	GE	410	1				0	GE	µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	3.0E-01	1	UI			0	GP	4.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	4.00	1	Y			1	GE	3.96	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								14.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 8D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N103874.7 E51400.5	33.339360 °N 81.733270 °W	240.8-220.8 ft msl	369.6 ft msl	4" PVC	S	M									
SAMPLE DATE	10/26/94		02/01/95												
FIELD DATA															
Parameter	4Q94		1Q95			Unit									
Water elevation	234.5		234.7			ft msl									
pH	5.6		5.5			pH									
Sp. conductance	58		49			µS/cm									
Water temperature	18.8		18.5			°C									
Alkalinity as CaCO ₃	12		15			mg/L									
Turbidity	1.1		0.7			NTU									
Volume purged	11.5		5.83			well volumes									
Sampling code															
Synchronous water level	234.4 (12/20/94)		234.9 (03/23/95)			ft msl									
ANALYTICAL DATA															
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	2,130	1			0		GE	2,940	1				0	GE	µg/L
Chlorobenzene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1			0		GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Gross alpha								1.7E+00	1	J			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1			0		GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	280	1			0		GE	499	1				0	GE	µg/L
Nonvolatile beta								1.0E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	3.1E+00	1			0		GP	3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1			0		GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 9D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103585.2 E51263.0	33.338490 °N 81.733070 °W	239.7-219.7 ft msl	367.9 ft msl	4" PVC	S	M

SAMPLE DATE 10/26/94 02/01/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	234.9	235.1	ft msl
pH	5.6	5.5	pH
Sp. conductance	41	37	µS/cm
Water temperature	18.0	17.5	°C
Alkalinity as CaCO ₃	6	5	mg/L
Turbidity	1.5	0.5	NTU
Volume purged	8.12	6.45	well volumes
Sampling code			
Synchronous water level	234.8 (12/20/94)	235.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	2,750	1				0	GE	3,090	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								6.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	112	1				0	GE	148	1				0	GE	µg/L
Nonvolatile beta								7.3E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	7.0E-01	1	J			0	GP	1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								15.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 10A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103326.4 E51410.0	33.338160 °N 81.732180 °W	111.4-106.4 ft msl	366.5 ft msl	4" PVC	S	MCBC

SAMPLE DATE 11/1/94 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	218.7	219.0	ft msl
pH	9.8	11.5	pH
Sp. conductance	170	177	µS/cm
Water temperature	18.2	14.7	°C
Alkalinity as CaCO ₃	79	84	mg/L
Turbidity	8.6	13.5	NTU
Volume purged	1.11	1.14	well volumes
Sampling code	X	X	
Synchronous water level	218.7 (12/20/94)	219.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								298	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								24.2	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	1,790	1				0	GE	1,640	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								8.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	231	1				0	GE	153	1				0	GE	µg/L
Nonvolatile beta								4.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	2.0E-01	1	UI			0	GP	0.0E+00	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.18	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 10B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103337.3 E51418.3	33.338200 °N 81.732180 °W	154.3-149.3 ft msl	366.4 ft msl	4" PVC	S	LL

SAMPLE DATE 10/31/94 02/01/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	223.7	224.6	ft msl
pH	5.9	6.2	pH
Sp. conductance	51	45	µS/cm
Water temperature	18.0	18.4	°C
Alkalinity as CaCO ₃	4	14	mg/L
Turbidity	1.3	1.6	NTU
Volume purged	5.23	2.83	well volumes
Sampling code			
Synchronous water level	223.8 (12/20/94)	224.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								12.5	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	3,940	1				0	WA	3,370	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								5.7E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	576	1				0	GE	97.9	1				0	GE	µg/L
Nonvolatile beta								8.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	0.0E+00	1	UI			0	GP	-1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.87	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 10D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103293.4 E51456.0	33.338160 °N 81.731990 °W	239.4-219.4 ft msl	365.5 ft msl	4" PVC	S	M

SAMPLE DATE 11/01/94 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	236.5	236.4	ft msl
pH	5.5	5.4	pH
Sp. conductance	44	41	µS/cm
Water temperature	17.8	17.8	°C
Alkalinity as CaCO ₃	9	10	mg/L
Turbidity	1.1	0.6	NTU
Volume purged	8.01	7.53	well volumes
Sampling code			
Synchronous water level	236.2 (12/20/94)	236.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								89.3	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.27	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	2,430	1				0	GE	3,570	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	82.0	1	J			0	GE	107	1				0	GE	µg/L
Nonvolatile beta								1.6E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.2E+00	1	J			0	GP	1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 10DD

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103278.7 E51456.0	33.338130 °N 81.731960 °W	358.6-338.6 ft msl	365.4 ft msl	4" PVC	S	M

SAMPLE DATE	11/01/94	02/02/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	359.3	359.3	ft msl
pH	6.4	6.4	pH
Sp. conductance	139	107	µS/cm
Water temperature	20.0	17.4	°C
Alkalinity as CaCO ₃	65	50	mg/L
Turbidity	1.2	1.0	NTU
Volume purged	7.59	5.45	well volumes
Sampling code			
Synchronous water level	359.4 (12/20/94)	359.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								3.05	1	J			0	GE	µg/L
Barium, total recoverable								11.0	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	1,410	1				0	GE	2,660	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								7.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
Nonvolatile beta								9.6E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.0E-01	1	UI			0	GP	3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 11B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103154.2 E51919.5	33.338610 °N 81.730500 °W	184.5-174.5 ft msl	364.6 ft msl	4" PVC	S	UL

SAMPLE DATE	10/28/94	02/03/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	223.4	224.2	ft msl
pH	5.8	6.1	pH
Sp. conductance	42	44	µS/cm
Water temperature	17.7	17.2	°C
Alkalinity as CaCO ₃	1	12	mg/L
Turbidity	0.8	0.6	NTU
Volume purged	3.62	3.01	well volumes
Sampling code			
Synchronous water level	223.6 (12/20/94)	224.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								32.9	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	3,440	1	Y			0	GE	3,730	1				0	GE	µg/L
Chlorobenzene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1	Y			0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Gross alpha								5.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	244	1	Y			0	GE	329	1				0	GE	µg/L
Nonvolatile beta								5.9E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	4.0E-01	1	J			0	GP	1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1	J3			0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								7.26	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 11D

SRS Coord.	Lat/Longitude	Screen Zone Elevation					Top of Casing		Casing	Pump	Screen Zone					
N103132.3 E51932.6	33.338580 °N 81.730420 °W	240.5-220.5 ft msl					364 ft msl		4" PVC	S	M					
SAMPLE DATE		10/28/94					02/03/95									
FIELD DATA																
Parameter		4Q94					1Q95					Unit				
Water elevation		236.9					236.8					ft msl				
pH		6.1					6.0					pH				
Sp. conductance		62					51					µS/cm				
Water temperature		17.3					17.5					°C				
Alkalinity as CaCO ₃		19					2					mg/L				
Turbidity		0.9					0.5					NTU				
Volume purged		6.79					8.79					well volumes				
Sampling code																
Synchronous water level		236.9 (12/20/94)					237.2 (03/23/95)					ft msl				
ANALYTICAL DATA																
Parameter		4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable									<33.3	1				0	GE	µg/L
Arsenic, total recoverable									<3.33	1				0	GE	µg/L
Barium, total recoverable									7.60	1				0	GE	µg/L
Cadmium, total recoverable									<3.33	1				0	GE	µg/L
Chloride		2,380	1	Y			0	GE	2,470	1				0	GE	µg/L
Chlorobenzene		<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable									<6.67	1				0	GE	µg/L
Cobalt, total recoverable																µg/L
Copper, total recoverable																µg/L
Cyanide		<5.00	1	Y			0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane		<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene		<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene		<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Gross alpha									4.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable									<5.00	1				0	GE	µg/L
Mercury, total recoverable									<0.333	1				0	GE	µg/L
Nickel, total recoverable		<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen		56.0	1	JY			0	GE	93.2	1				0	GE	µg/L
Nonvolatile beta									3.0E-01	1	UI			0	GP	pCi/L
PCB 1254																µg/L
Radium, total alpha-emitting		2.0E-01	1	UI			0	GP	2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable									<3.33	1				0	GE	µg/L
Silver, total recoverable		<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable																µg/L
Sulfate																µg/L
1,1,2,2-Tetrachloroethane		<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene		<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)									<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane		<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene		<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable																µg/L
Zinc, total recoverable									<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 12D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103602.4 E51901.6	33.339570 °N 81.731420 °W	239.4-219.4 ft msl	369.8 ft msl	4" PVC	S	M

SAMPLE DATE 10/28/94 02/03/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	235.4	235.5	ft msl
pH	5.7	5.6	pH
Sp. conductance	22	24	µS/cm
Water temperature	18.3	18.7	°C
Alkalinity as CaCO ₃	2	3	mg/L
Turbidity	2.4	1.1	NTU
Volume purged	11.0	7.67	well volumes
Sampling code			
Synchronous water level	235.5 (12/20/94)	235.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								34.9	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.55	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	1,250	1	Y			0	GE	1,460	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.2E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	875	1	Y			0	GE	868	1				0	GE	µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	6.0E-01	1	J			0	GP	1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1	Y			0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								8.93	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 13AR

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103082.0 E51396.0	33.337600 °N 81.731740 °W	110.9-100.9 ft msl	365.1 ft msl	4" PVC	S	MCBC

SAMPLE DATE	11/01/94	02/02/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	219.7	220.1	ft msl
pH	10.2	7.2	pH
Sp. conductance	190	83	µS/cm
Water temperature	19.3	19.1	°C
Alkalinity as CaCO ₃	100	33	mg/L
Turbidity	6.7	14.4	NTU
Volume purged	0.886	2.43	well volumes
Sampling code	X		
Synchronous water level	219.5 (12/20/94)	220.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								82.8	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								31.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride	2,300	1				0	GE	2,420	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								2.6E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	886	1				0	GE	988	1				0	GE	µg/L
Nonvolatile beta								4.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	7.0E-01	1	J			0	GP	1.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)								218	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	1.02	1	J			0	GE	1.54	1	J			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.37	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 14D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104278.7 E51360.8	33.340180 °N 81.734160 °W	235.1-215.1 ft msl	382.4 ft msl	2" PVC		M

SAMPLE DATE 03/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		232.1	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level		233.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	G	H	Flag	Lab	1Q95	DF	Mod	G	H	Flag	Lab	Unit
Aluminum, total recoverable								167	1	V	■		2	GE	µg/L
Arsenic, total recoverable								<5.00	1				0	GE	µg/L
Barium, total recoverable								13.6	1	V			0	GE	µg/L
Cadmium, total recoverable								<2.00	1				0	GE	µg/L
Chloride								2,110	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								3.65	1	JV			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<20.0	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								1.13	1	J			0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								-5.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								2.01	1	J			0	GE	µg/L
Mercury, total recoverable								<0.200	1				0	GE	µg/L
Nickel, total recoverable								13.0	1	V	■		0	GE	µg/L
Nitrate-nitrite as nitrogen								300	1				0	GE	µg/L
Nonvolatile beta								2.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								1.42	1	JVV			0	GE	µg/L
Silver, total recoverable								<0.650	1	VV			0	GE	µg/L
Sodium, total recoverable								18,100	1		■		0	GE	µg/L
Sulfate								3,430	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								20.0	1		■		2	GE	µg/L
Total phosphates (as P)								50.0	1	J			0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								79.8	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								19.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 15D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104500.6 E51383.8	33.340710 °N 81.734530 °W	236.2-216.2 ft msl	383.4 ft msl	2" PVC		M

SAMPLE DATE 03/17/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		234.5	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level		235.0 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>G</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>G</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								622	1	V	■		2	GE	µg/L
Arsenic, total recoverable								<5.00	1				0	GE	µg/L
Barium, total recoverable								30.3	1	V			0	GE	µg/L
Cadmium, total recoverable								0.695	1	J			0	GE	µg/L
Chloride								2,540	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								5.88	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<20.0	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.9E+00	1				0	GP	pCi/L
Lead, total recoverable								32.0	1				1	GE	µg/L
Mercury, total recoverable								<0.200	1				0	GE	µg/L
Nickel, total recoverable								38.8	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen								640	1				0	GE	µg/L
Nonvolatile beta								4.1E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								1.92	1	JVV			0	GE	µg/L
Silver, total recoverable								<0.650	1				0	GE	µg/L
Sodium, total recoverable								27,300	2		■		0	GE	µg/L
Sulfate								5,890	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)								700	1		■		0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								30.0	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								85.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 16D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104268.8 E51557.5	33.340480 °N 81.733620 °W	233.4-213.4 ft msl	380.4 ft msl	2" PVC		M

SAMPLE DATE 03/16/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		233.9	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level		234.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	G	H	Flag	Lab	1Q95	DF	Mod	G	H	Flag	Lab	Unit
Aluminum, total recoverable								109	1	V	■		2	GE	µg/L
Arsenic, total recoverable								<5.00	1				0	GE	µg/L
Barium, total recoverable								1.24	1	JV			0	GE	µg/L
Cadmium, total recoverable								<2.00	1				0	GE	µg/L
Chloride								2,710	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<20.0	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								5.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.200	1				0	GE	µg/L
Nickel, total recoverable								2.72	1	J			0	GE	µg/L
Nitrate-nitrite as nitrogen								510	1				0	GE	µg/L
Nonvolatile beta								1.4E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<5.00	1	VV			0	GE	µg/L
Silver, total recoverable								<0.650	1				0	GE	µg/L
Sodium, total recoverable								6,780	1		■		0	GE	µg/L
Sulfate								3,310	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)								<100	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								8.54	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<5.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 17A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104056.7 E51465.4	33.339860 °N 81.733450 °W	125.0-120.0 ft msl	379.1 ft msl	4" PVC		MCBC

SAMPLE DATE 03/16/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		220.3	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level		220.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	G	H	Flag	Lab	1Q95	DF	Mod	G	H	Flag	Lab	Unit
Aluminum, total recoverable								230	1	V	■		2	GE	µg/L
Arsenic, total recoverable								<5.00	1				0	GE	µg/L
Barium, total recoverable								6.78	1	V			0	GE	µg/L
Cadmium, total recoverable								<2.00	1				0	GE	µg/L
Chloride								1,690	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<20.0	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								5.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								1.21	1	J			0	GE	µg/L
Mercury, total recoverable								<0.200	1				0	GE	µg/L
Nickel, total recoverable								<10.0	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								940	1				0	GE	µg/L
Nonvolatile beta								6.0E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<5.00	1	VV			0	GE	µg/L
Silver, total recoverable								<0.650	1				0	GE	µg/L
Sodium, total recoverable								2,960	1				0	GE	µg/L
Sulfate								795	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								34.4	1		■		2	GE	µg/L
Total phosphates (as P)								120	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								395	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								6.10	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 18A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103988.8 E51418.8	33.339640 °N 81.733440 °W	136.4-131.4 ft msl	377.3 ft msl	4" PVC		MCBC

SAMPLE DATE 03/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		220.3	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level		220.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	G	H	Flag	Lab	1Q95	DF	Mod	G	H	Flag	Lab	Unit
Aluminum, total recoverable								972	1	V	■		2	GE	µg/L
Arsenic, total recoverable								<5.00	1				0	GE	µg/L
Barium, total recoverable								8.70	1	V			0	GE	µg/L
Cadmium, total recoverable								<2.00	1				0	GE	µg/L
Chloride								2,150	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<4.00	1	V			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<20.0	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.4E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.200	1				0	GE	µg/L
Nickel, total recoverable								2.01	1	JVV			0	GE	µg/L
Nitrate-nitrite as nitrogen								1,020	1				0	GE	µg/L
Nonvolatile beta								1.4E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								0.0E+00	1	UI			0	GP	pCi/L
Selenium, total recoverable								<5.00	1				0	GE	µg/L
Silver, total recoverable								<0.650	1	VV			0	GE	µg/L
Sodium, total recoverable								3,150	1				0	GE	µg/L
Sulfate								907	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								3.10	1				1	GE	µg/L
Total phosphates (as P)								<100	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								49.8	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.26	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 18C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103983.4 E51432.8	33.339650 °N 81.733390 °W	214.2-209.2 ft msl	376 ft msl	2" PVC		UL

SAMPLE DATE 03/16/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		234.1	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level		234.5 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>G</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>G</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								25.2	1	V			1	GE	µg/L
Arsenic, total recoverable								<5.00	1				0	GE	µg/L
Barium, total recoverable								3.49	1	V			0	GE	µg/L
Cadmium, total recoverable								<2.00	1				0	GE	µg/L
Chloride								2,670	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								3.40	1	J			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<20.0	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.200	1				0	GE	µg/L
Nickel, total recoverable								6.89	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen								410	1				0	GE	µg/L
Nonvolatile beta								5.8E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-4.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<5.00	1	VV			0	GE	µg/L
Silver, total recoverable								<0.650	1				0	GE	µg/L
Sodium, total recoverable								5,210	1		■		0	GE	µg/L
Sulfate								1,790	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)								<100	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.43	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AMB 19C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102941.1 E51503.7	33.337460 °N 81.731180 °W	196.7-191.7 ft msl	363.7 ft msl	2" PVC		UL

SAMPLE DATE 03/16/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		231.9	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level		232.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	G	H	Flag	Lab	1Q95	DF	Mod	G	H	Flag	Lab	Unit
Aluminum, total recoverable								89.1	1	V			2	GE	µg/L
Arsenic, total recoverable								<5.00	1				0	GE	µg/L
Barium, total recoverable								0.986	1	JV			0	GE	µg/L
Cadmium, total recoverable								<2.00	1				0	GE	µg/L
Chloride								2,210	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								2.53	1	J			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<20.0	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								-3.2E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.200	1				0	GE	µg/L
Nickel, total recoverable								2.50	1	J			0	GE	µg/L
Nitrate-nitrite as nitrogen								90.0	1	J			0	GE	µg/L
Nonvolatile beta								3.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-4.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								1.72	1	JVV			0	GE	µg/L
Silver, total recoverable								<0.650	1				0	GE	µg/L
Sodium, total recoverable								10,900	1				0	GE	µg/L
Sulfate								9,430	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)								<100	1				0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<5.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AOB 1

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N101910.7 E50485.9	33.333520 °N 81.731860 °W	248.5-218.5 ft msl	341.1 ft msl	4" PVC	S	M									
SAMPLE DATE	11/01/94			01/13/95											
FIELD DATA															
Parameter	4Q94			1Q95		Unit									
Water elevation	237.2			236.9		ft msl									
pH	5.1			5.3		pH									
Sp. conductance	36			35		µS/cm									
Water temperature	19.2			18.7		°C									
Alkalinity as CaCO ₃	1			1		mg/L									
Turbidity	1.8			0.4		NTU									
Volume purged	3.09			7.53		well volumes									
Sampling code															
Synchronous water level	236.8 (12/20/94)			237.6 (03/23/95)		ft msl									
ANALYTICAL DATA															
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								12.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								3.5E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								2.1E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	35.7	1		■		2	GE	42.7	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	39.5	1		■		2	GE	39.5	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AOB 2

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N102009.8 E50724.7	33.334130 °N 81.731420 °W	250.2-220.2 ft msl	345.4 ft msl	4" PVC	S	M									
SAMPLE DATE		11/01/94		01/13/95											
FIELD DATA															
Parameter	4Q94	1Q95			Unit										
Water elevation	238.0	237.7			ft msl										
pH	5.2	5.4			pH										
Sp. conductance	20	18			µS/cm										
Water temperature	19.3	19.0			°C										
Alkalinity as CaCO ₃	2	2			mg/L										
Turbidity	1.5	1.3			NTU										
Volume purged	9.76	7.82			well volumes										
Sampling code															
Synchronous water level	237.6 (12/20/94)	238.3 (03/23/95)			ft msl										
ANALYTICAL DATA															
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.52	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Gross alpha								2.0E+00	1				0	GP	pCi/L
Lead, total recoverable								5.05	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								4.67	1	J			0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1			0		GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								14.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL AOB 3

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102164.4 E50959.4	33.334850 °N 81.731100 °W	243.9-223.9 ft msl	352.6 ft msl	4" PVC	S	M

SAMPLE DATE 11/02/94 01/13/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	238.9	238.7	ft msl
pH	5.2	5.8	pH
Sp. conductance	39	27	µS/cm
Water temperature	15.3	19.0	°C
Alkalinity as CaCO ₃	2	2	mg/L
Turbidity	3.4	2.3	NTU
Volume purged	0.912	1.03	well volumes
Sampling code	X	X	
Synchronous water level	238.7 (12/20/94)	239.1 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								161	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.89	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								5.7E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								2.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.02	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ARP 1A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N99102.9 E44317.4	33.317240 °N 81.742640 °W	223.0-193.0 ft msl	355.1 ft msl	4" PVC	S	GCL

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	217.5 (12/20/94)	217.4 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ARP 2

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N99119.8 E44876.1	33.318190 °N 81.741200 °W	220.3-190.3 ft msl	337.3 ft msl	4" PVC	S	GC

SAMPLE DATE 01/13/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		219.9	ft msl
pH		4.9	pH
Sp. conductance		14	µS/cm
Water temperature		18.3	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.1	NTU
Volume purged		6.23	well volumes
Sampling code			
Synchronous water level	219.8 (12/20/94)	219.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<33.3	1						0	GE	µg/L					
Arsenic, total recoverable	<3.33	1						0	GE	µg/L					
Barium, total recoverable	4.00	1	J					0	GE	µg/L					
Cadmium, total recoverable	<3.33	1						0	GE	µg/L					
Chloride										µg/L					
Chlorobenzene	<1.67	1						0	GE	µg/L					
Chromium, total recoverable	<6.67	1						0	GE	µg/L					
Cobalt, total recoverable										µg/L					
Copper, total recoverable										µg/L					
Cyanide	<8.33	1						0	GE	µg/L					
1,1-Dichloroethane	<1.67	1						0	GE	µg/L					
1,1-Dichloroethylene	<1.67	1						0	GE	µg/L					
trans-1,2-Dichloroethylene	<1.67	1						0	GE	µg/L					
Gross alpha	7.2E-01	1	UI					0	GP	pCi/L					
Lead, total recoverable	4.21	1	J					0	GE	µg/L					
Mercury, total recoverable	<0.333	1						0	GE	µg/L					
Nickel, total recoverable	<6.67	1						0	GE	µg/L					
Nitrate-nitrite as nitrogen										µg/L					
Nonvolatile beta	7.8E-01	1	UI					0	GP	pCi/L					
PCB 1254										µg/L					
Radium, total alpha-emitting	4.0E-01	1						0	GP	pCi/L					
Selenium, total recoverable	<3.33	1						0	GE	µg/L					
Silver, total recoverable	<3.33	1						0	GE	µg/L					
Sodium, total recoverable										µg/L					
Sulfate										µg/L					
1,1,2,2-Tetrachloroethane	<1.67	1						0	GE	µg/L					
Tetrachloroethylene	<1.67	1						0	GE	µg/L					
Total phosphates (as P)										µg/L					
1,1,1-Trichloroethane	<1.67	1						0	GE	µg/L					
Trichloroethylene	<1.67	1						0	GE	µg/L					
Uranium, total recoverable										µg/L					
Zinc, total recoverable	<3.33	1						0	GE	µg/L					

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ARP 3

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N98638.2 E44903.7	33.317170 °N 81.740190 °W	218.2-188.2 ft msl	339.8 ft msl	4" PVC	S	GCL

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	222.6 (12/20/94)	222.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ARP 4

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N98567.7 E44374.8	33.316150 °N 81.741440 °W	227.8-197.8 ft msl	348.4 ft msl	4" PVC	S	GCL

SAMPLE DATE 01/13/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		220.1	ft msl
pH		4.9	pH
Sp. conductance		16	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		2.9	NTU
Volume purged		4.79	well volumes
Sampling code			
Synchronous water level	219.9 (12/20/94)	219.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.66	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.3E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								7.04	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								2.45	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								10.6	1			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.43	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 1A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105535.0 E52614.0	33.345010 °N 81.733300 °W	247.2-217.2 ft msl	349.1 ft msl	4" PVC	S	M

SAMPLE DATE	10/07/94	01/20/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	247.6	238.0	ft msl
pH	5.6	5.8	pH
Sp. conductance	72	59	µS/cm
Water temperature	19.2	18.7	°C
Alkalinity as CaCO ₃	6	13	mg/L
Turbidity	1.0	1.4	NTU
Volume purged	4.21	4.48	well volumes
Sampling code			
Synchronous water level	237.7 (12/20/94)	238.3 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.7	1				0	GE	13.6	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	4,260	1		■		0	GE	4,510	1		■		0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	15.9	1				0	GE	17.8	1				0	GE	µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	1.8E+00	1	J			0	GP	2.2E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	556	1	J2			0	GE	644	1				0	GE	µg/L
Nonvolatile beta	2.2E-01	1	UI			0	GP	1.9E+00	1				0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	1.0E+00	1	J			0	GP	1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	12,100	1		■		0	GE	10,300	1		■		0	GE	µg/L
Sulfate	7,800	1		■		0	GE	6,750	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	3.75	1				1	GE	3.79	1				1	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.80	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 2AR

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105550.5 E52881.7	33.345480 °N 81.732630 °W	240.1-220.2 ft msl	355.6 ft msl	4" PVC	S	MGCL

SAMPLE DATE 10/07/94 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	239.2	239.1	ft msl
pH	6.0	5.6	pH
Sp. conductance	68	71	µS/cm
Water temperature	18.4	18.2	°C
Alkalinity as CaCO ₃	9	14	mg/L
Turbidity	0.7	0.5	NTU
Volume purged	5.13	10.5	well volumes
Sampling code			
Synchronous water level	239.0 (12/20/94)	239.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								40.7	1	JVV			1	WA	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	11.6	1				0	GE	11.7	1	Y			0	WA	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,510	1				0	GE	4,550	1	Y	■		0	WA	µg/L
Chlorobenzene								<1.67	1	Y			0	GE	µg/L
Chromium, total recoverable	5.27	1	J			0	GE	6.40	1	J			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE	2.10	1	J			0	WA	µg/L
Cyanide								<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane								<1.67	1	Y			0	GE	µg/L
1,1-Dichloroethylene								<1.67	1	Y			0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1	Y			0	GE	µg/L
Gross alpha	1.3E-01	1	UI			0	GP	2.5E+00	1				0	TM	pCi/L
Lead, total recoverable	<3.00	1				0	GE	5.20	1	JVV			0	WA	µg/L
Mercury, total recoverable	<0.200	1				0	GE	0.210	1	JVVY			0	WA	µg/L
Nickel, total recoverable	<4.00	1				0	GE	0.890	1	JVV			0	WA	µg/L
Nitrate-nitrite as nitrogen	217	1	J2			0	GE	251	1	Y			0	GE	µg/L
Nonvolatile beta	1.0E+00	1	UI			0	GP	1.5E+00	1	UI			0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	8.0E-01	1	J			0	GP	1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<1.40	1				0	WA	µg/L
Sodium, total recoverable	11,600	1		■		0	GE	12,200	1		■		0	GE	µg/L
Sulfate	5,480	1		■		0	GE	7,750	1	Y	■		0	WA	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1	Y			0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	1.58	1	J			0	WA	µg/L
Total phosphates (as P)	<50.0	1				0	GE	5.04	1	J			0	WA	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1	Y			0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1	Y			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	4.00	1	JVV			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 2CR

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105540.2 E52862.7	33.345430 °N 81.732660 °W	183.1-173.1 ft msl	355.6 ft msl	4" PVC	S	LL

SAMPLE DATE 10/07/94 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	223.8	223.9	ft msl
pH	6.4	5.8	pH
Sp. conductance	102	97	µS/cm
Water temperature	19.0	18.8	°C
Alkalinity as CaCO ₃	9	19	mg/L
Turbidity	3.5	3.2	NTU
Volume purged	3.13	4.65	well volumes
Sampling code			
Synchronous water level	223.8 (12/20/94)	224.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								29.4	1	J			1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	2.00	1	J			0	GE	µg/L
Barium, total recoverable	64.0	1				0	GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	8,030	1		■		0	GE	8,140	1		■		0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	9.0E-01	1	UI			0	GP	1.7E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	718	1	J2			0	GE	756	1				0	GE	µg/L
Nonvolatile beta	1.6E-01	1	UI			0	GP	1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	6.0E-01	1				0	GP	5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	8,610	1		■		0	GE	8,610	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	2,040	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	22.7	5		■	2	GE		20.6	1		■	2	GE	µg/L	
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<5.00	5				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	188	5		■	2	GE		172	10		■	2	GE	µg/L	
Uranium, total recoverable															
Zinc, total recoverable	7.16	1				0	GE	6.08	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 3AR

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105605.1 E53115.0	33.345980 °N 81.732120 °W	243.1-223.1 ft msl	341.6 ft msl	4" PVC	S	MGCL

SAMPLE DATE 10/05/94 01/24/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	229.7	239.5	ft msl
pH	5.7	6.3	pH
Sp. conductance	57	52	µS/cm
Water temperature	19.2	18.1	°C
Alkalinity as CaCO ₃	7	10	mg/L
Turbidity	0.8	0.7	NTU
Volume purged	14.7	6.79	well volumes
Sampling code			
Synchronous water level	239.5 (12/20/94)	240.3 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.5	1				0	GE	19.9	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,580	1				0	GE	3,230	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	4.0E-01	1	UI			0	GP	4.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	9.70	1	JVV			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	312	1	J2			0	GE	356	1				0	GE	µg/L
Nonvolatile beta	3.5E-02	1	UI			0	GP	5.3E-02	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	5.0E-01	1	J			0	GP	6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	10,500	1				0	GE	10,700	1				0	GE	µg/L
Sulfate	6,170	1				0	GE	6,720	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 3CR

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105614.5 E53130.4	33.346030 °N 81.732100 °W	184.0-174.0 ft msl	341.5 ft msl	4" PVC	S	LL

SAMPLE DATE 10/05/94 01/24/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	223.5	223.5	ft msl
pH	5.3	5.5	pH
Sp. conductance	53	46	µS/cm
Water temperature	19.2	18.0	°C
Alkalinity as CaCO ₃	2	4	mg/L
Turbidity	0.5	0.3	NTU
Volume purged	3.48	3.14	well volumes
Sampling code			
Synchronous water level	223.4 (12/20/94)	224.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								23.2	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	1,050	1		■		1	GE	950	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	7,350	1		■		0	GE	7,340	1		■		0	GE	µg/L
Chlorobenzene								<16.7	10				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene								<16.7	10				0	GE	µg/L
Gross alpha	1.3E+00	1	J			0	GP	5.2E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.644	1				0	GE	0.423	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	569	1	J2			0	GE	640	1				0	GE	µg/L
Nonvolatile beta	2.1E+00	1	J			0	GP	3.8E+00	1				0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	9.0E-01	1	J			0	GP	1.9E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	4,670	1		■		0	GE	4,710	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,700	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L
Tetrachloroethylene	<100	100				0	GE	19.6	10		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<100	100				0	GE	<16.7	10				0	GE	µg/L
Trichloroethylene	452	100		■		2	GE	325	10		■		2	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	19.8	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 4

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105935.7 E53177.2	33.346810 °N 81.732600 °W	256.1-226.1 ft msl	335.6 ft msl	4" PVC	S	M

SAMPLE DATE 10/10/94 02/22/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	277.9	238.6	ft msl
pH	5.6	5.6	pH
Sp. conductance	49	54	µS/cm
Water temperature	19.7	21.4	°C
Alkalinity as CaCO ₃	6	9	mg/L
Turbidity	6.2	4.9	NTU
Volume purged	3.18	4.88	well volumes
Sampling code			
Synchronous water level	238.6 (12/20/94)	239.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								25.1	1				1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	1.81	1	J			0	GE	µg/L
Barium, total recoverable	7.21	1				0	GE	6.91	1	V			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Chloride	2,070	1				0	GE	2,350	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE	1.67	1	J			0	GE	µg/L
Cyanide								<20.0	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	1.4E+00	1	J			0	GP	1.5E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	2.10	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.200	1	V			0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<10.0	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	883	1	J2			0	GE	816	1				0	GE	µg/L
Nonvolatile beta	2.7E+00	1	J			0	GP	1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	5.0E-01	1				0	GP	9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.31	1	J			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<0.650	1	V			0	GE	µg/L
Sodium, total recoverable	7,750	1				0	GE	8,330	1				0	GE	µg/L
Sulfate	3,630	1				0	GE	5,050	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	36.6	1	J			0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.60	1	J			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	5.04	1				0	GE	5.97	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 5AR

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105900.5 E52854.4	33.346210 °N 81.733380 °W	243.8-223.8 ft msl	347 ft msl	4" PVC	S	MGCL

SAMPLE DATE	10/11/94	02/03/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	237.4	237.5	ft msl
pH	5.7	5.0	pH
Sp. conductance	61	59	µS/cm
Water temperature	13.1	17.9	°C
Alkalinity as CaCO ₃	11	8	mg/L
Turbidity	7.7	7.9	NTU
Volume purged	0.783	0.556	well volumes
Sampling code	X	X	
Synchronous water level	237.2 (12/20/94)	237.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								95.1	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.79	1				0	GE	5.09	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,750	1				0	GE	3,740	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	1.6E+00	1	J			0	GP	5.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	381	1				0	GE	485	1				0	GE	µg/L
Nonvolatile beta	3.1E+00	1	J			0	GP	5.8E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	2.0E-01	1	UI			0	GP	4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.50	1	J			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	9,300	1				0	GE	9,590	1				0	GE	µg/L
Sulfate	5,080	1				0	GE	6,180	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<5.00	5				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	111	1				0	GE	µg/L
1,1,1-Trichloroethane	<5.00	5				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	121	5				2	GE	58.5	1				2	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	3.97	1				0	GE	3.97	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 5C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105884.8 E52837.8	33.346150 °N 81.733390 °W	175.1-165.1 ft msl	347.3 ft msl	4" PVC	S	LL

SAMPLE DATE 10/11/94 02/02/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	223.5	224.1	ft msl
pH	5.7	5.6	pH
Sp. conductance	46	47	µS/cm
Water temperature	19.0	19.1	°C
Alkalinity as CaCO ₃	7	7	mg/L
Turbidity	3.0	0.5	NTU
Volume purged	3.23	2.71	well volumes
Sampling code			
Synchronous water level	223.4 (12/20/94)	224.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								53.9	1	JVV			2	WA	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	6.25	1				0	GE	7.50	1				0	WA	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	1.60	1	J			0	WA	µg/L
Chloride	3,800	1				0	GE	4,580	1		■		0	WA	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	1.70	1	J			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE	12.3	1	J			0	WA	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	7.3E-01	1	UI			0	GP	1.1E+00	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	1.90	1	J			0	WA	µg/L
Mercury, total recoverable	<0.200	1				0	GE	0.0800	1	J			0	WA	µg/L
Nickel, total recoverable	<4.00	1				0	GE	28.0	1		■		0	WA	µg/L
Nitrate-nitrite as nitrogen	900	1				0	GE	1,030	1				0	GE	µg/L
Nonvolatile beta	1.5E+00	1	J			0	GP	1.1E+00	1	UI			0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	2.0E-01	1	UI			0	GP	4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	3.50	1	J			0	WA	µg/L
Silver, total recoverable	<2.00	1				0	GE	0.390	1	J			0	WA	µg/L
Sodium, total recoverable	2,560	1				0	GE	2,620	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	387	1	J			0	WA	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	161	10		■		2	GE	120	1		■		2	WA	µg/L
Total phosphates (as P)	<50.0	1				0	GE	6.70	1	J			0	WA	µg/L
1,1,1-Trichloroethane	<10.0	10				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	356	10		■		2	GE	365	5	J1	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	2.21	1	J			0	GE	23.5	1	V			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 6A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105716.0 E52675.9	33.345510 °N 81.733490 °W	248.2-218.2 ft msl	350.2 ft msl	4" PVC	S	MGCL

SAMPLE DATE	10/07/94	01/24/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	237.1	237.1	ft msl
pH	5.4	5.8	pH
Sp. conductance	75	67	µS/cm
Water temperature	19.5	18.0	°C
Alkalinity as CaCO ₃	3	5	mg/L
Turbidity	1.3	0.8	NTU
Volume purged	8.05	9.11	well volumes
Sampling code			
Synchronous water level	237.1 (12/20/94)	237.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	<3.00	1				0	GE	4.62	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	4,250	1		■		0	GE	4,770	1		■		0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	4.93	1	J			0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	2.4E+00	1	J			0	GP	3.8E+00	1				0	GP	pCi/L
Lead, total recoverable	4.90	1	J			0	GE	8.00	1	JVV			0	GE	µg/L
Mercury, total recoverable	0.215	1	J			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	8.90	1		■		0	GE	8.18	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen	1,910	2	J2			0	GE	1,710	1				0	GE	µg/L
Nonvolatile beta	1.2E+00	1	UI			0	GP	7.2E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	1.7E+00	1				0	GP	2.3E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	13,200	1		■		0	GE	13,600	1		■		0	GE	µg/L
Sulfate	8,930	1		■		0	GE	9,590	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	1.54	1	J			0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.12	1	J			0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	6.55	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 6AA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105727.0 E52643.9	33.345480 °N 81.733600 °W	82.8-78.1 ft msl	354.2 ft msl	4" PVC	S	MCBC

SAMPLE DATE 10/26/94 01/25/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	219.3	219.1	ft msl
pH	10.8	10.5	pH
Sp. conductance	161	107	µS/cm
Water temperature	19.5	18.0	°C
Alkalinity as CaCO ₃	46	42	mg/L
Turbidity	2.2	1.3	NTU
Volume purged	3.35	4.00	well volumes
Sampling code			
Synchronous water level	219.1 (12/20/94)	219.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								273	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	13.3	1				0	GE							GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,610	1				0	GE	2,140	1				0	GE	µg/L
Chlorobenzene								<41.8	25				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable														GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<41.8	25				0	GE	µg/L
1,1-Dichloroethylene								<41.8	25				0	GE	µg/L
trans-1,2-Dichloroethylene								<41.8	25				0	GE	µg/L
Gross alpha	3.3E-01	1	UI			0	GP	2.6E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE							GE	µg/L
Nitrate-nitrite as nitrogen	1,300	1	J2			0	GE	1,220	1				0	GE	µg/L
Nonvolatile beta	1.3E+00	1	UI			0	GP	6.0E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	1.8E+00	1				0	GP	4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE							GE	µg/L
Sodium, total recoverable	3,900	1				0	GE	3,550	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,370	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<41.8	25				0	GE	µg/L
Tetrachloroethylene	433	100		■		2	GE	<41.8	25				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<100	100				0	GE	<41.8	25				0	GE	µg/L
Trichloroethylene	4,060	500	J1	■		2	GE	3,130	50		■		2	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 6C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105736.8 E52655.9	33.345520 °N 81.733580 °W	178.5-173.8 ft msl	353.6 ft msl	4" PVC	S	UL

SAMPLE DATE 10/07/94 01/24/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	224.7	224.8	ft msl
pH	5.2	5.5	pH
Sp. conductance	35	32	µS/cm
Water temperature	20.0	18.6	°C
Alkalinity as CaCO ₃	1	3	mg/L
Turbidity	1.0	1.0	NTU
Volume purged	2.94	2.78	well volumes
Sampling code			
Synchronous water level	224.8 (12/20/94)	224.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	11.0	1				0	GE	10.7	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	4,340	1		■		0	GE	4,860	1		■		0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	5.67	1	J			0	GE	4.67	1	J			0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	8.5E-01	1	UI			0	GP	1.2E+00	1				0	GP	pCi/L
Lead, total recoverable	3.53	1	J			0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	384	1	J2			0	GE	404	1				0	GE	µg/L
Nonvolatile beta	1.1E+00	1	UI			0	GP	1.0E+00	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	6.0E-01	1	J			0	GP	1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,480	1				0	GE	2,570	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,300	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	35.5	1		■		2	GE	44.4	1		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	23.7	1		■		2	GE	18.5	1		■		2	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	14.3	1				0	GE	11.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 6TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105749.5 E52671.3	33.345580 °N 81.733570 °W	40.0-34.5 ft msl	352.9 ft msl	4" PVC	S	CBA

SAMPLE DATE 10/27/94 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	215.0	215.0	ft msl
pH	10.1	10.2	pH
Sp. conductance	89	85	µS/cm
Water temperature	14.6	15.2	°C
Alkalinity as CaCO ₃	28	29	mg/L
Turbidity	3.5	5.0	NTU
Volume purged	0.329	0.0253	well volumes
Sampling code	X	X	
Synchronous water level	214.9 (12/20/94)	215.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								177	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	4.23	1				0	GE	µg/L
Barium, total recoverable	19.8	1				0	GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,550	1				0	GE	2,190	1				0	GE	µg/L
Chlorobenzene								<41.8	25				0	GE	µg/L
Chromium, total recoverable	12.8	1				0	GE	12.6	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<41.8	25				0	GE	µg/L
1,1-Dichloroethylene								<41.8	25				0	GE	µg/L
trans-1,2-Dichloroethylene								<41.8	25				0	GE	µg/L
Gross alpha	9.8E-01	1	UI			0	GP	1.6E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	3.34	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,140	1				0	GE	1,020	1				0	GE	µg/L
Nonvolatile beta	6.6E+00	1				0	GP	5.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	0.0E+00	1	UI			0	GP	1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.47	1	J			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	8,120	1		■		0	GE	7,960	1		■		0	GE	µg/L
Sulfate	3,740	1		■		0	GE	4,980	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<41.8	25				0	GE	µg/L
Tetrachloroethylene	<50.0	50				0	GE	<41.8	25				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<50.0	50				0	GE	<41.8	25				0	GE	µg/L
Trichloroethylene	1,290	50		■		2	GE	781	25		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	5.02	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 8

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106381.6 E53136.6	33.347730 °N 81.733570 °W	226.6-206.6 ft msl	349 ft msl	4" PVC	S	GCL

SAMPLE DATE 10/11/94 01/24/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	234.8	234.6	ft msl
pH	4.9	5.0	pH
Sp. conductance	33	31	µS/cm
Water temperature	18.9	18.2	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.1	0.8	NTU
Volume purged	6.06	1.96	well volumes
Sampling code			
Synchronous water level	234.8 (12/20/94)	235.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,960	1				0	GE	3,440	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	45.6	1				0	GE	52.0	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	9.8E-01	1	J			0	GP	2.5E+00	1				0	GP	pCi/L
Lead, total recoverable	4.81	1	J			0	GE	4.65	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	733	1				0	GE	692	1				0	GE	µg/L
Nonvolatile beta	7.2E-01	1	UI			0	GP	5.9E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	9.0E-01	1	J			0	GP	9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	4,510	1				0	GE	5,170	1			■	0	GE	µg/L
Sulfate	1,800	1				0	GE	3,240	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.75	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	5.24	1				0	GE	6.06	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 8A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106369.3 E53117.5	33.347670 °N 81.733600 °W	83.5-77.9 ft msl	349.3 ft msl	4" PVC	S	MCBC

SAMPLE DATE 10/14/94 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	220.3	220.1	ft msl
pH	5.3	5.2	pH
Sp. conductance	22	19	µS/cm
Water temperature	18.8	18.4	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.3	0.9	NTU
Volume purged	3.05	2.59	well volumes
Sampling code			
Synchronous water level	220.1 (12/20/94)	220.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	6.70	1				0	WA	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,110	1				0	WA	2,260	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	1.6E+00	1	J1			0	TM	9.2E-01	1				0	GP	pCi/L
Lead, total recoverable	3.80	1				0	WA	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1	J			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	870	1				0	GE	881	1				0	GE	µg/L
Nonvolatile beta	6.5E+00	1				0	TM	5.6E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	2.0E-01	1	UI			0	GP	3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	4.60	1	J3			0	WA	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,120	1	V			0	WA	1,740	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,560	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	29.9	1				0	GE	15.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 8B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106362.3 E53109.6	33.347650 °N 81.733610 °W	128.4-122.8 ft msl	349.8 ft msl	4" PVC	S	(LL)L/MC

SAMPLE DATE 10/27/94 01/25/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	221.3	221.0	ft msl
pH	4.8	4.8	pH
Sp. conductance	30	27	µS/cm
Water temperature	17.8	18.5	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.7	0.5	NTU
Volume purged	3.87	2.45	well volumes
Sampling code			
Synchronous water level	221.3 (12/20/94)	221.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								24.7	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	6.16	1				0	GE	6.36	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,830	1				0	GE	2,360	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable													0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	8.2E-01	1	UI			0	GP	1.6E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	3.52	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,680	1				0	GE	1,850	2				0	GE	µg/L
Nonvolatile beta	1.5E+00	1	J			0	GP	1.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	3.0E-01	1	UI			0	GP	1.6E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,610	1				0	GE	2,610	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,260	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<100	100				0	GE	17.5	1			■	2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<100	100				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	3,020	100			■	2	GE	2,150	250			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	7.40	1				0	GE	16.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 8C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N106354.4 E53101.0	33.347610 °N 81.733610 °W	188.3-182.7 ft msl	349.7 ft msl	4" PVC	S	UL

SAMPLE DATE 10/27/94

01/25/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	224.1	224.0	ft msl
pH	4.9	4.8	pH
Sp. conductance	42	40	µS/cm
Water temperature	17.6	18.3	°C
Alkalinity as CaCO ₃	0	1	mg/L
Turbidity	0.8	0.5	NTU
Volume purged	6.01	5.35	well volumes
Sampling code			
Synchronous water level	224.0 (12/20/94)	224.6 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								26.7	1	J			1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.2	1				0	GE	10.1	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	4,440	1		■		0	GE	5,220	1		■		0	GE	µg/L
Chlorobenzene								<418	250				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable								<8.33	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<418	250				0	GE	µg/L
1,1-Dichloroethane								<418	250				0	GE	µg/L
1,1-Dichloroethylene								<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene								<418	250				0	GE	µg/L
Gross alpha	1.8E+00	1	J			0	GP	2.4E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	2.12	1		■		2	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	2,240	2				0	GE	1,770	2				0	GE	µg/L
Nonvolatile beta	2.6E+00	1	J			0	GP	2.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.1E+00	1	J			0	GP	2.2E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	4,260	1				0	GE	4,400	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,260	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<418	250				0	GE	µg/L
Tetrachloroethylene	170	100		■		2	GE	<418	250				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<100	100				0	GE	<418	250				0	GE	µg/L
Trichloroethylene	15,500	500		■		2	GE	10,300	250		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	3.35	1				0	GE	3.77	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 8TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N106375.8 E53124.7	33.347700 °N 81.733590 °W	24.6-19.4 ft msl	349.6 ft msl	4" CS	S	CBA

SAMPLE DATE	10/11/94	01/25/95
-------------	----------	----------

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	216.6	216.5	ft msl
pH	5.1	4.9	pH
Sp. conductance	21	19	µS/cm
Water temperature	18.5	18.2	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	2.3	2.0	NTU
Volume purged	2.84	2.54	well volumes
Sampling code			
Synchronous water level	216.6 (12/20/94)	217.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.35	1				0	GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,460	1				0	GE	2,090	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	5.23	1	J			0	GE	4.14	1	J			0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	7.1E-01	1	UI			0	GP	6.2E-01	1				0	GP	pCi/L
Lead, total recoverable	6.26	1				0	GE	7.18	1				0	GE	µg/L
Mercury, total recoverable	0.229	1	J			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	985	1				0	GE	1,050	1				0	GE	µg/L
Nonvolatile beta	1.5E+00	1	UI			0	GP	8.5E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	5.0E-01	1				0	GP	4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,340	1				0	GE	1,430	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,200	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	4.00	1				1	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	5.90	1		■		2	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 9

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104589.2 E54226.2	33.345550 °N 81.727220 °W	236.4-216.4 ft msl	309 ft msl	4" PVC	S	MGC

SAMPLE DATE 10/12/94 01/24/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	242.1	241.7	ft msl
pH	5.9	5.7	pH
Sp. conductance	63	66	µS/cm
Water temperature	17.7	18.0	°C
Alkalinity as CaCO ₃	7	11	mg/L
Turbidity	0.7	0.4	NTU
Volume purged	5.71	6.22	well volumes
Sampling code			
Synchronous water level	241.7 (12/20/94)	242.6 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								90.0	1	JVVY			2	WA	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	6.73	1				0	GE	7.10	1	JY			0	WA	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,720	1				0	GE	3,210	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	28.1	1				0	GE	31.7	1	Y			0	WA	µg/L
Cobalt, total recoverable															
Copper, total recoverable	6.46	1	J			0	GE	9.00	1	JVVY			0	WA	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	4.2E-01	1	UI			0	GP	1.2E+00	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	3.60	1	JVVY			0	WA	µg/L
Mercury, total recoverable	<0.200	1	J			0	GE	0.109	1	JVVY			0	WA	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<0.540	1	Y			0	WA	µg/L
Nitrate-nitrite as nitrogen	409	1				0	GE	378	1				0	GE	µg/L
Nonvolatile beta	1.7E+00	1	J			0	GP	2.1E+00	1				0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	2.0E-01	1	UI			0	GP	1.0E+00	1				0	TM	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.70	1	JY			0	WA	µg/L
Silver, total recoverable	<2.00	1				0	GE	0.190	1	JY			0	WA	µg/L
Sodium, total recoverable	12,000	1		■		0	GE	12,400	1		■		0	GE	µg/L
Sulfate	7,130	1		■		0	GE	8,660	1	Y	■		0	WA	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	13.3	1	JY			0	WA	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	<2.00	1				0	GE	7.30	1	JVVY			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 9B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104564.7 E54215.3	33.345480 °N 81.727200 °W	164.4-158.8 ft msl	309 ft msl	4" PVC	S	L(UD)

SAMPLE DATE 10/14/94 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	221.4	220.5	ft msl
pH	6.6	6.3	pH
Sp. conductance	87	83	µS/cm
Water temperature	18.1	18.2	°C
Alkalinity as CaCO ₃	25	24	mg/L
Turbidity	0.6	0.6	NTU
Volume purged	5.41	6.99	well volumes
Sampling code			
Synchronous water level	221.2 (12/20/94)	221.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								44.7	1				1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	39.0	1				0	WA	35.1	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,990	1				0	WA	3,680	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	3.8E+00	1				0	TM	1.7E+00	1				0	GP	pCi/L
Lead, total recoverable	3.10	1				0	WA	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1	J			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	728	1				0	GE	691	1				0	GE	µg/L
Nonvolatile beta	1.7E+00	1	J1			0	TM	1.3E+00	1				0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	1.3E+00	1	J			0	GP	9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	3,520	1	V			0	WA	3,210	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,320	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	36.9	2		■	2	WA	27.6	1			■	2	GE	µg/L	
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	41.7	5		■	2	GE	33.1	1			■	2	GE	µg/L	
Uranium, total recoverable															
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 9C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104568.1 E54201.1	33.345460 °N 81.727240 °W	182.9-178.2 ft msl	309.9 ft msl	4" PVC	S	UL

SAMPLE DATE 10/12/94 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	221.6	220.9	ft msl
pH	5.9	5.7	pH
Sp. conductance	41	51	µS/cm
Water temperature	17.9	18.2	°C
Alkalinity as CaCO ₃	5	8	mg/L
Turbidity	1.2	0.9	NTU
Volume purged	5.20	4.32	well volumes
Sampling code			
Synchronous water level	221.4 (12/20/94)	222.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								36.8	1					GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	18.2	1				0	GE	27.9	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,490	1				0	GE	3,950	1				0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha	9.9E-01	1	UI			0	GP	2.0E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1	J			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	794	1				0	GE	796	1				0	GE	µg/L
Nonvolatile beta	2.1E+00	1	J			0	GP	1.8E+00	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	7.0E-01	1	J			0	GP	4.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,740	1				0	GE	2,910	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,260	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	28.9	2		■		2	GE	20.8	1		■		2	GE	µg/L
Total phosphates (as P)	52.6	1	J			0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<2.00	2				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	34.5	2		■		2	GE	21.7	1		■		2	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	<2.00	1				0	GE	2.16	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL ASB 10CR

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105655.4 E52969.7	33.345850 °N 81.732600 °W	181.7-171.7 ft msl	349.2 ft msl	4" PVC	S	LL

SAMPLE DATE 10/07/94 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	223.6	223.9	ft msl
pH	5.2	5.1	pH
Sp. conductance	58	43	µS/cm
Water temperature	18.6	18.6	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.6	0.5	NTU
Volume purged	3.49	3.22	well volumes
Sampling code			
Synchronous water level	223.7 (12/20/94)	224.3 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								21.5	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	11.8	1				0	GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	9,170	1		■		0	GE	9,540	1		■		0	GE	µg/L
Chlorobenzene								<16.7	10				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene								<16.7	10				0	GE	µg/L
Gross alpha	8.6E-01	1	J			0	GP	1.4E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	1.31	1				1	GE	1.43	1				1	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,170	1	J2			0	GE	1,060	1				0	GE	µg/L
Nonvolatile beta	1.4E+00	1	UI			0	GP	1.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.0E+00	1	J			0	GP	1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	6,330	1		■		0	GE	6,480	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,260	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L
Tetrachloroethylene	<25.0	25				0	GE	54.0	10		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<25.0	25				0	GE	<16.7	10				0	GE	µg/L
Trichloroethylene	676	25		■		2	GE	738	10	J2	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MCB 2

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N97012.6 E45129.0	33.313940 °N 81.736430 °W	225.9-205.9 ft msl	328.4 ft msl	4" PVC	S	M

SAMPLE DATE 02/07/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.6	ft msl
pH		5.2	pH
Sp. conductance		28	µS/cm
Water temperature		17.0	°C
Alkalinity as CaCO ₃		5	mg/L
Turbidity		38.0	NTU
Volume purged		0.896	well volumes
Sampling code		X	
Synchronous water level	225.2 (12/20/94)	225.2 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								1,710	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.60	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.5E+00	1	J			0	GP	pCi/L
Lead, total recoverable								16.4	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								2.10	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								17.9	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								134	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MCB 4

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97532.5 E44705.1	33.314400 °N 81.738560 °W	229.6-208.6 ft msl	350.4 ft msl	4" PVC	S	MGCL

SAMPLE DATE 02/07/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		225.0	ft msl
pH		4.8	pH
Sp. conductance		15	µS/cm
Water temperature		16.6	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		7.4	NTU
Volume purged		0.745	well volumes
Sampling code		X	
Synchronous water level	225.6 (12/20/94)	225.4 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								37.5	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.48	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<8.34	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<8.34	5				0	GE	µg/L
1,1-Dichloroethylene								<8.34	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.34	5				0	GE	µg/L
Gross alpha								1.9E+00	1	J			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								2.1E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<8.34	5				0	GE	µg/L
Tetrachloroethylene								75.0	5		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<8.34	5				0	GE	µg/L
Trichloroethylene								296	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								16.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MCB 5

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N97335.6 E44863.9	33.314230 °N 81.737760 °W	226.3-206.3 ft msl	339.6 ft msl	4" PVC	S	MGC

SAMPLE DATE 02/06/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.4	ft msl
pH		6.2	pH
Sp. conductance		37	µS/cm
Water temperature		18.9	°C
Alkalinity as CaCO ₃		10	mg/L
Turbidity		0.4	NTU
Volume purged		4.55	well volumes
Sampling code			
Synchronous water level	225.8 (12/20/94)	225.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								127	1	VVY	■		2	WA	µg/L
Arsenic, total recoverable								3.90	1	Y			0	WA	µg/L
Barium, total recoverable								5.60	1	JY			0	WA	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								1.70	1	JY			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.8E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								0.950	1	JY3			0	WA	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.7E+00	1	J1			0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.9E+00	1				0	TM	pCi/L
Selenium, total recoverable								2.80	1	JY			0	WA	µg/L
Silver, total recoverable								0.370	1	JY			0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								14.2	1	Y	■		2	WA	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								149	1	Y	■		2	WA	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								7.00	1	JVVY			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MCB 5C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97315.1 E44862.8	33.314180 °N 81.737720 °W	161.2-156.2 ft msl	339.1 ft msl	4" PVC	V	UL

SAMPLE DATE 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		195.8	ft msl
pH		12.5	pH
Sp. conductance		2,170	µS/cm
Water temperature		16.8	°C
Alkalinity as CaCO ₃		797	mg/L
Turbidity		264.0	NTU
Volume purged		0.346	well volumes
Sampling code		X	
Synchronous water level	195.6 (12/20/94)	196.5 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								1,190	10		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								565	10				0	GE	µg/L
Cadmium, total recoverable								<33.1	10				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<66.7	10				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.5E+01	1		■		2	GP	pCi/L
Lead, total recoverable								55.1	1		■		2	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<66.7	10				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								5.5E+01	1		■		2	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.1E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<33.3	10				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								23.3	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								57.3	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								73.3	10				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MCB 6

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97425.7 E45214.0	33.315000 °N 81.737010 °W	219.7-199.7 ft msl	332.1 ft msl	4" PVC	S	MGC

SAMPLE DATE 02/07/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		213.1	ft msl
pH		5.1	pH
Sp. conductance		17	µS/cm
Water temperature		16.6	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		13.3	NTU
Volume purged		0.456	well volumes
Sampling code		X	
Synchronous water level	213.2 (12/20/94)	220.5 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								177	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.70	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1	J			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								3.10	1				1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								14.4	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								10.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MCB 6C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97413.1 E45207.7	33.314960 °N 81.737000 °W	170.0-165.0 ft msl	332.1 ft msl	4" PVC	S	UL

SAMPLE DATE 02/06/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		196.3	ft msl
pH		6.0	pH
Sp. conductance		57	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		14	mg/L
Turbidity		3.0	NTU
Volume purged		4.09	well volumes
Sampling code			
Synchronous water level	196.1 (12/20/94)	197.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								27.1	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								25.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.7E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								3.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								3.00	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MCB 7C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97139.9 E44870.6	33.313800 °N 81.737360 °W	160.7-155.7 ft msl	337.7 ft msl	4" PVC	S	UL

SAMPLE DATE 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		195.0	ft msl
pH		12.3	pH
Sp. conductance		2,020	µS/cm
Water temperature		16.6	°C
Alkalinity as CaCO ₃		556	mg/L
Turbidity		9.7	NTU
Volume purged		0.583	well volumes
Sampling code		X	
Synchronous water level	194.6 (12/20/94)	195.5 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								5,120	10		■		2	GE	µg/L
Arsenic, total recoverable								3.00	1	J			0	GE	µg/L
Barium, total recoverable								89.5	10				0	GE	µg/L
Cadmium, total recoverable								<33.3	10				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<66.7	10				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.7E+00	1				0	GP	pCi/L
Lead, total recoverable								8.60	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<66.7	10				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.6E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.5E+00	1				0	GP	pCi/L
Selenium, total recoverable								3.81	1				0	GE	µg/L
Silver, total recoverable								<33.3	10				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								6.00	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								30.0	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								29.0	10	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 9A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102236.7 E48242.5	33.330580 °N 81.738400 °W	144.2-139.2 ft msl	359.1 ft msl	4" PVC	S	LL/CBC

SAMPLE DATE 10/24/94 01/16/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	209.1	215.9	ft msl
pH	6.0	5.8	pH
Sp. conductance	29	39	µS/cm
Water temperature	19.2	18.8	°C
Alkalinity as CaCO ₃	7	9	mg/L
Turbidity	2.1	0.7	NTU
Volume purged	4.23	2.59	well volumes
Sampling code			
Synchronous water level	215.9 (12/21/94)	210.4 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.05	1	J			0	GE	4.54	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,850	1				0	GE	1,620	1				0	GE	µg/L
Chlorobenzene	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	1			0	GE	µg/L
1,1-Dichloroethane	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
1,1-Dichloroethylene	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene	<10.0	10				0	GE	16.7	10	J			0	GE	µg/L
Gross alpha								7.7E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	3.50	1	J			0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	236	1	J2			0	GE	316	1				0	GE	µg/L
Nonvolatile beta								2.2E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,530	1				0	GE	1,660	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
Tetrachloroethylene	913	10		■		2	GE	1,250	50		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
Trichloroethylene	567	10		■		2	GE	1,090	50		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	2,830	1				1	GE	2,520	1				1	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 9B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102239.4 E48251.7	33.330600 °N 81.738380 °W	209.3-204.3 ft msl	359.3 ft msl	4" PVC	S	GCL

SAMPLE DATE 10/25/94 01/16/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	230.5	230.7	ft msl
pH	8.7	8.9	pH
Sp. conductance	167	155	µS/cm
Water temperature	17.4	18.0	°C
Alkalinity as CaCO ₃	14	56	mg/L
Turbidity	2.6	1.4	NTU
Volume purged	0.465	0.289	well volumes
Sampling code	X	X	
Synchronous water level	230.7 (12/21/94)	230.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	33.1	1				0	GE	28.2	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,890	1	Y			0	GE	4,180	1				0	GE	µg/L
Chlorobenzene	<1,000	1000	VY			0	GE	<835	500				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1,000	1000	VY			0	GE	<835	500				0	GE	µg/L
1,1-Dichloroethylene	<1,000	1000	VY			0	GE	<835	500				0	GE	µg/L
trans-1,2-Dichloroethylene	<1,000	1000	VY			0	GE	<835	500				0	GE	µg/L
Gross alpha								2.1E+00	1				0	GP	pCi/L
Lead, total recoverable	11.6	1				0	GE	6.29	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	13,300	20	J2	■		2	GE	11,000	10				2	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								1.5E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	7,920	1		■		0	GE	7,700	1				0	GE	µg/L
Sulfate	1,170	1	JY			0	GE	1,210	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1,000	1000	VY			0	GE	<835	500				0	GE	µg/L
Tetrachloroethylene	31,300	1000	VY	■		2	GE	32,400	500				2	GE	µg/L
Total phosphates (as P)	<50.0	1	Y			0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1,000	1000	VY			0	GE	<835	500				0	GE	µg/L
Trichloroethylene	20,800	1000	VY	■		2	GE	17,800	500				2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	2,450	1				0	GE	907	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 9C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102245.6 E48273.0	33.330650 °N 81.738330 °W	241.6-221.6 ft msl	359.6 ft msl	4" PVC	S	M

SAMPLE DATE 10/24/94 01/16/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	230.6	231.9	ft msl
pH	4.1	3.8	pH
Sp. conductance	141	159	µS/cm
Water temperature	19.4	19.5	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	1.4	2.0	NTU
Volume purged	5.41	4.89	well volumes
Sampling code			
Synchronous water level	230.7 (12/21/94)	230.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	2,300	1		■		2	GE	2,450	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	35.0	1				0	GE	40.4	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,460	1				0	GE	3,320	1				0	GE	µg/L
Chlorobenzene	<1,000	1000				0	GE	<418	250				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	14.1	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	1			0	GE	µg/L
1,1-Dichloroethane	<1,000	1000				0	GE	<418	250				0	GE	µg/L
1,1-Dichloroethylene	<1,000	1000				0	GE	<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene	<1,000	1000				0	GE	<418	250				0	GE	µg/L
Gross alpha								7.1E+01	1		■		2	GP	pCi/L
Lead, total recoverable	5.02	1				0	GE	5.96	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	10.7	1		■		0	GE	13.6	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen	12,900	20	J2	■		2	GE	16,900	10		■		2	GE	µg/L
Nonvolatile beta								3.2E+01	1				1	GP	pCi/L
PCB 1254								<0.833	1				0	GE	µg/L
Radium, total alpha-emitting								5.2E+01	1		■		2	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	4,820	1		■		0	GE	7,490	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1,000	1000				0	GE	<418	250				0	GE	µg/L
Tetrachloroethylene	12,400	1000		■		2	GE	14,800	250		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1,000	1000				0	GE	<418	250				0	GE	µg/L
Trichloroethylene	5,870	1000		■		2	GE	7,590	250		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	23.7	1				0	GE	24.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 10A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102451.8 E47954.4	33.330580 °N 81.739570 °W	125.2-120.2 ft msl	357.2 ft msl	4" PVC	S	MCBC

SAMPLE DATE 10/11/94 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	212.8	215.1	ft msl
pH	5.4	5.5	pH
Sp. conductance	20	23	µS/cm
Water temperature	18.7	18.2	°C
Alkalinity as CaCO ₃	1	2	mg/L
Turbidity	0.5	0.4	NTU
Volume purged	2.73	1.86	well volumes
Sampling code			
Synchronous water level	215.6 (12/20/94)	211.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.16	1	J			0	GE	4.43	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,690	1				0	GE	2,510	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	248	1				0	GE	251	1				0	GE	µg/L
Nonvolatile beta								1.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,400	1				0	GE	1,530	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,440	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	7.10	1		■		2	GE	6.61	1		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	21.1	1		■		2	GE	30.2	1		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	35.8	1				0	GE	19.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 10B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102488.2 E47943.1	33.330640 °N 81.739670 °W	157.4-152.4 ft msl	357.6 ft msl	4" PVC	S	LL

SAMPLE DATE 10/11/94 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	213.6	216.8	ft msl
pH	5.1	5.1	pH
Sp. conductance	37	39	µS/cm
Water temperature	18.3	18.6	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.0	1.5	NTU
Volume purged	3.51	2.27	well volumes
Sampling code			
Synchronous water level	217.6 (12/20/94)	214.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	39.3	1				1	WA	23.7	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	13.0	1				0	WA	11.5	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,320	1				0	WA	2,490	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	8.00	1				0	WA	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	8.90	1				0	WA								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.1E+00	1				0	GP	pCi/L
Lead, total recoverable	5.20	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	8.30	1				0	WA	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	61.3	1	J			0	GE	<83.0	1				0	GE	µg/L
Nonvolatile beta								-8.4E-02	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,620	1	V			0	WA	2,390	1				0	GE	µg/L
Sulfate	8,570	1				0	WA	8,000	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	2.62	1	J3			1	WA	2.69	1				1	GE	µg/L
Uranium, total recoverable	0.940	1				0	TM	<33.3	1				0	GE	µg/L
Zinc, total recoverable	43.2	1	V			0	WA	21.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 10C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>									
N102465.6 E47951.1	33.330610 °N 81.739610 °W	211.0-206.2 ft msl	357.1 ft msl	4" PVC	S	GCL									
SAMPLE DATE		10/25/94		01/17/95											
FIELD DATA															
<u>Parameter</u>	<u>4Q94</u>				<u>1Q95</u>	<u>Unit</u>									
Water elevation	230.1				230.0	ft msl									
pH	10.7					pH									
Sp. conductance	274					µS/cm									
Water temperature	18.7					°C									
Alkalinity as CaCO ₃	64					mg/L									
Turbidity	2.7					NTU									
Volume purged	2.94				0.384	well volumes									
Sampling code					P										
Synchronous water level	230.0 (12/20/94)				230.2 (03/23/95)	ft msl									
ANALYTICAL DATA															
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	65.5	1				2	GE								µg/L
Arsenic, total recoverable	<2.00	1				0	GE								µg/L
Barium, total recoverable	157	1				0	GE								µg/L
Cadmium, total recoverable	<2.00	1				0	GE								µg/L
Chloride	2,600	1	Y			0	GE								µg/L
Chlorobenzene	<1,000	1000	VY			0	GE								µg/L
Chromium, total recoverable	<4.00	1				0	GE								µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	4.64	1	J			0	GE								µg/L
Cyanide	<5.00	1	Y			0	GE								µg/L
1,1-Dichloroethane	<1,000	1000	VY			0	GE								µg/L
1,1-Dichloroethylene	<1,000	1000	VY			0	GE								µg/L
trans-1,2-Dichloroethylene	<1,000	1000	VY			0	GE								µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE								µg/L
Mercury, total recoverable	<0.200	1				0	GE								µg/L
Nickel, total recoverable	<4.00	1				0	GE								µg/L
Nitrate-nitrite as nitrogen	14,500	20	JY2	■		2	GE								µg/L
Nonvolatila beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE								µg/L
Silver, total recoverable	<2.00	1				0	GE								µg/L
Sodium, total recoverable	13,400	1		■		0	GE								µg/L
Sulfate	<1,000	1	Y			0	GE								µg/L
1,1,2,2-Tetrachloroethane	<1,000	1000	VY			0	GE								µg/L
Tetrachloroethylene	58,500	1000	VY	■		2	GE								µg/L
Total phosphates (as P)	<50.0	1	Y			0	GE								µg/L
1,1,1-Trichloroethane	<1,000	1000	VY			0	GE								µg/L
Trichloroethylene	32,700	1000	VY	■		2	GE								µg/L
Uranium, total recoverable	<20.0	1				0	GE								µg/L
Zinc, total recoverable	7.98	1				0	GE								µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 11A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102638.9 E48577.6	33.332010 °N 81.738300 °W	135.8-130.8 ft msl	365.4 ft msl	4" PVC	S	LL

SAMPLE DATE 10/19/94 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	211.8	216.5	ft msl
pH	6.2	6.4	pH
Sp. conductance	35	43	µS/cm
Water temperature	18.0	18.3	°C
Alkalinity as CaCO ₃	12	13	mg/L
Turbidity	2.6	0.9	NTU
Volume purged	3.75	2.63	well volumes
Sampling code			
Synchronous water level	216.3 (12/20/94)	213.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	20.7	1	J			0	GE	20.9	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	14.6	1				0	GE	18.0	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,580	1				0	GE	2,280	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								7.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	244	1	J2			0	GE	180	1				0	GE	µg/L
Nonvolatile beta								-2.2E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,460	1				0	GE	1,600	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,470	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	1.60	1	J			0	GE	3.25	1				1	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	17.1	1		■		2	GE	47.0	1		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	155	1				0	GE	55.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 11B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N102648.9 E48578.5	33.332040 °N 81.738310 °W	165.7-160.7 ft msl	365.4 ft msl	4" PVC	S	UL									
SAMPLE DATE		10/24/94		01/17/95											
FIELD DATA															
Parameter	4Q94				1Q95	Unit									
Water elevation	217.2				221.7	ft msl									
pH	5.8				6.2	pH									
Sp. conductance	28				27	µS/cm									
Water temperature	18.8				18.7	°C									
Alkalinity as CaCO ₃	3				6	mg/L									
Turbidity	1.2				0.6	NTU									
Volume purged	3.24				2.68	well volumes									
Sampling code															
Synchronous water level	221.8 (12/20/94)				218.7 (03/23/95)	ft msl									
ANALYTICAL DATA															
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.93	1				0	GE	9.76	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,890	1				0	GE	1,750	1				0	GE	µg/L
Chlorobenzene	<10.0	10				0	GE	<41.7	25				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<10.0	10				0	GE	<41.7	25				0	GE	µg/L
1,1-Dichloroethylene	<10.0	10				0	GE	<41.7	25				0	GE	µg/L
trans-1,2-Dichloroethylene	<10.0	10				0	GE	<41.7	25				0	GE	µg/L
Gross alpha								1.2E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	635	1	J2			0	GE	426	1				0	GE	µg/L
Nonvolatile beta								1.4E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.6E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,630	1				0	GE	1,710	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<10.0	10				0	GE	<41.7	25				0	GE	µg/L
Tetrachloroethylene	41.0	10			■	2	GE	29.0	25	J		■	2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<10.0	10				0	GE	<41.7	25				0	GE	µg/L
Trichloroethylene	999	10			■	2	GE	933	25			■	2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	33.4	1				0	GE	45.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 11C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102658.6 E48579.4	33.332060 °N 81.738330 °W	182.9-177.9 ft msl	365.5 ft msl	4" PVC	S	UL

SAMPLE DATE	10/24/94	01/17/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	219.6	223.7	ft msl
pH	4.7	4.4	pH
Sp. conductance	123	128	µS/cm
Water temperature	18.3	18.2	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.9	0.6	NTU
Volume purged	4.79	3.99	well volumes
Sampling code			
Synchronous water level	224.0 (12/20/94)	221.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	90.6	1				2	GE	124	1		■	2	GE	µg/L	
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1			0	GE	µg/L	
Barium, total recoverable	29.8	1				0	GE	38.9	1			0	GE	µg/L	
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1			0	GE	µg/L	
Chloride	2,310	1				0	GE	2,430	1			0	GE	µg/L	
Chlorobenzene	<1,000	1000				0	GE	<1,670	1000			0	GE	µg/L	
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1			0	GE	µg/L	
Cobalt, total recoverable															
Copper, total recoverable	<4.00	1				0	GE								
Cyanide	<5.00	1				0	GE	<8.33	1	J1		0	GE	µg/L	
1,1-Dichloroethane	<1,000	1000				0	GE	<1,670	1000			0	GE	µg/L	
1,1-Dichloroethylene	<1,000	1000				0	GE	<1,670	1000			0	GE	µg/L	
trans-1,2-Dichloroethylene	<1,000	1000				0	GE	<1,670	1000			0	GE	µg/L	
Gross alpha								1.3E+01	1			1	GP	pCi/L	
Lead, total recoverable	<3.00	1				0	GE	<5.00	1			0	GE	µg/L	
Mercury, total recoverable	0.361	1				0	GE	0.361	1			0	GE	µg/L	
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1			0	GE	µg/L	
Nitrate-nitrite as nitrogen	10,600	20	J2	■		2	GE	14,400	10		■	2	GE	µg/L	
Nonvolatile beta								7.4E+00	1			0	GP	pCi/L	
PCB 1254															
Radium, total alpha-emitting								1.1E+01	1		■	1	GP	pCi/L	
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1			0	GE	µg/L	
Silver, total recoverable	<2.00	1				0	GE	<3.33	1			0	GE	µg/L	
Sodium, total recoverable	6,790	1		■		0	GE	7,410	1		■	0	GE	µg/L	
Sulfate	<1,000	1				0	GE	<1,670	1			0	GE	µg/L	
1,1,2,2-Tetrachloroethane	<1,000	1000				0	GE	<1,670	1000			0	GE	µg/L	
Tetrachloroethylene	<1,000	1000				0	GE	<1,670	1000			0	GE	µg/L	
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1			0	GE	µg/L	
1,1,1-Trichloroethane	<1,000	1000				0	GE	<1,670	1000			0	GE	µg/L	
Trichloroethylene	95,100	1000		■		2	GE	93,200	1000		■	2	GE	µg/L	
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1			0	GE	µg/L	
Zinc, total recoverable	4.39	1				0	GE	19.4	1			0	GE	µg/L	

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 11D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102669.5 E48579.7	33.332080 °N 81.738350 °W	208.9-203.9 ft msl	365.8 ft msl	4" PVC	S	GC

SAMPLE DATE 10/18/94 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	230.8	231.2	ft msl
pH	5.0	4.8	pH
Sp. conductance	27	28	µS/cm
Water temperature	17.9	18.0	°C
Alkalinity as CaCO ₃	1	0	mg/L
Turbidity	0.7	0.5	NTU
Volume purged	5.89	5.13	well volumes
Sampling code			
Synchronous water level	231.1 (12/20/94)	231.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	40.2	1				1	WA	31.6	1	J			1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.59	1				0	GE	7.04	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,790	1				0	WA	2,980	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<8.35	5				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	4.64	1	J			0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<8.35	5				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<8.35	5				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<8.35	5				0	GE	µg/L
Gross alpha								2.5E+00	1				0	GP	pCi/L
Lead, total recoverable	5.80	1				0	WA	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,180	1	J2			0	GE	792	1				0	GE	µg/L
Nonvolatile beta								2.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.5E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,120	1				0	GE	2,130	1				0	GE	µg/L
Sulfate	1,570	1	J			0	GE	2,070	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<8.35	5				0	GE	µg/L
Tetrachloroethylene	352	5		■		2	WA	338	5		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	2.20	1				0	GE	<8.35	5				0	GE	µg/L
Trichloroethylene	615	5		■		2	WA	646	10		■		2	GE	µg/L
Uranium, total recoverable	0.0700	1				0	TM	<33.3	1				0	GE	µg/L
Zinc, total recoverable	17.1	1				0	WA	13.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 11E

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102678.5 E48579.6	33.332100 °N 81.738370 °W	251.0-231.0 ft msl	365.2 ft msl	4" PVC	B	M

SAMPLE DATE 01/20/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code	P	D	
Synchronous water level		239.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 11F

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102629.3 E48577.0	33.331990 °N 81.738280 °W	243.1-223.1 ft msl	365.6 ft msl	4" PVC	S	M

SAMPLE DATE	10/24/94	01/17/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	231.1	231.1	ft msl
pH	4.7	5.1	pH
Sp. conductance	22	21	µS/cm
Water temperature	18.5	19.2	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	1.4	2.1	NTU
Volume purged	14.1	8.37	well volumes
Sampling code			
Synchronous water level	231.2 (12/20/94)	231.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	43.9	1				1	GE	51.4	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,750	1				0	GE	2,630	1				0	GE	µg/L
Chlorobenzene	<10.0	10				0	GE	<3.34	2	J			0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<10.0	10				0	GE	<3.34	2	J1			0	GE	µg/L
1,1-Dichloroethylene	<10.0	10				0	GE	<3.34	2	J1			0	GE	µg/L
trans-1,2-Dichloroethylene	<10.0	10				0	GE	<3.34	2				0	GE	µg/L
Gross alpha								2.0E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	183	1	J2			0	GE	172	1				0	GE	µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.1E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,640	1				0	GE	2,670	1				0	GE	µg/L
Sulfate	1,810	1				0	GE	1,090	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<10.0	10				0	GE	<3.34	2	J			0	GE	µg/L
Tetrachloroethylene	40.4	10		■		2	GE	11.3	2	J1	■		2	GE	µg/L
Total phosphates (as P)	66.0	1	J			0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<10.0	10				0	GE	<3.34	2	J			0	GE	µg/L
Trichloroethylene	67.5	10		■		2	GE	37.2	2	J1	■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	2.70	1	J			0	GE	3.43	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 12A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102283.2 E47138.2	33.328880 °N 81.741400 °W	121.5-116.5 ft msl	348.9 ft msl	4" PVC	S	LL

SAMPLE DATE 10/24/94 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	208.6	213.0	ft msl
pH	4.5	4.9	pH
Sp. conductance	19	17	µS/cm
Water temperature	19.1	19.1	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.5	0.7	NTU
Volume purged	3.28	2.81	well volumes
Sampling code			
Synchronous water level	213.0 (12/20/94)	211.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.02	1	J			0	GE	4.00	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,540	1				0	GE	1,620	1				0	GE	µg/L
Chlorobenzene	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	7.26	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
1,1-Dichloroethylene	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
trans-1,2-Dichloroethylene	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Gross alpha								1.4E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	436	1	J2			0	GE	369	1				0	GE	µg/L
Nonvolatile beta								1.7E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.1E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,500	1				0	GE	1,480	1				0	GE	µg/L
Sulfate	1,130	1	J			0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Tetrachloroethylene	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Trichloroethylene	1,040	25		■		2	GE	998	25		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	17.3	1				0	GE	20.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 12B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102251.8 E47139.6	33.328810 °N 81.741330 °W	162.2-157.2 ft msl	349.5 ft msl	4" PVC	S	UL

SAMPLE DATE 10/24/94 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	218.6	219.8	ft msl
pH	4.3		pH
Sp. conductance	112		µS/cm
Water temperature	19.3		°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	2.6		NTU
Volume purged	3.70	0.0243	well volumes
Sampling code		P	
Synchronous water level	219.8 (12/20/94)	215.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	59.0	1				2	GE								µg/L
Arsenic, total recoverable	<2.00	1				0	GE								µg/L
Barium, total recoverable	17.9	1				0	GE								µg/L
Cadmium, total recoverable	<2.00	1				0	GE								µg/L
Chloride	2,700	1				0	GE								µg/L
Chlorobenzene	<500	500				0	GE								µg/L
Chromium, total recoverable	<4.00	1				0	GE								µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	5.55	1	J			0	GE								µg/L
Cyanide	<5.00	1				0	GE								µg/L
1,1-Dichloroethane	<500	500				0	GE								µg/L
1,1-Dichloroethylene	<500	500				0	GE								µg/L
trans-1,2-Dichloroethylene	<500	500				0	GE								µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE								µg/L
Mercury, total recoverable	0.243	1	J			0	GE								µg/L
Nickel, total recoverable	11.4	1		■		0	GE								µg/L
Nitrate-nitrite as nitrogen	11,300	20	J2	■		2	GE								µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE								µg/L
Silver, total recoverable	<2.00	1				0	GE								µg/L
Sodium, total recoverable	11,700	1		■		0	GE								µg/L
Sulfate	<1,000	1				0	GE								µg/L
1,1,2,2-Tetrachloroethane	<500	500				0	GE								µg/L
Tetrachloroethylene	8,600	500		■		2	GE								µg/L
Total phosphates (as P)	<50.0	1				0	GE								µg/L
1,1,1-Trichloroethane	<500	500				0	GE								µg/L
Trichloroethylene	20,200	500		■		2	GE								µg/L
Uranium, total recoverable	<20.0	1				0	GE								µg/L
Zinc, total recoverable	7.56	1				0	GE								µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 12C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102274.4 E47138.4	33.328860 °N 81.741380 °W	183.9-178.9 ft msl	349 ft msl	4" PVC	S	UL

SAMPLE DATE 10/24/94 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	223.7	224.5	ft msl
pH	4.9	5.3	pH
Sp. conductance	122	121	µS/cm
Water temperature	19.4	19.3	°C
Alkalinity as CaCO ₃	1	7	mg/L
Turbidity	1.2	1.7	NTU
Volume purged	3.03	2.74	well volumes
Sampling code			
Synchronous water level	224.6 (12/20/94)	224.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	39.8	1				1	GE	53.9	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	40.7	1				0	GE	42.0	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,100	1				0	GE	3,160	1				0	GE	µg/L
Chlorobenzene	<250	250				0	GE	<418	250				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<250	250				0	GE	<418	250				0	GE	µg/L
1,1-Dichloroethylene	<250	250				0	GE	<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene	<250	250				0	GE	<418	250				0	GE	µg/L
Gross alpha								1.9E+01	1		■		2	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.344	1				0	GE	0.238	1	J			0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	12,000	20	J2	■		2	GE	13,800	10		■		2	GE	µg/L
Nonvolatile beta								1.3E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.7E+00	1		■		0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	14,900	1		■		0	GE	15,500	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<250	250				0	GE	<418	250				0	GE	µg/L
Tetrachloroethylene	4,530	250		■		2	GE	4,100	250		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<250	250				0	GE	<418	250				0	GE	µg/L
Trichloroethylene	16,600	250		■		2	GE	12,500	250		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	88.0	1				0	GE	78.6	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 12D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>						<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>						
N102262.2 E47139.7	33.328830 °N 81.741350 °W	245.3-225.3 ft msl						349.4 ft msl	4" PVC	S	MGC						
SAMPLE DATE		10/19/94						02/03/95									
FIELD DATA																	
<u>Parameter</u>	<u>4Q94</u>						<u>1Q95</u>						<u>Unit</u>				
Water elevation													ft msl				
pH													pH				
Sp. conductance													µS/cm				
Water temperature													°C				
Alkalinity as CaCO ₃													mg/L				
Turbidity													NTU				
Volume purged													well volumes				
Sampling code	D						D										
Synchronous water level	234.1 (12/20/94)						234.0 (03/23/95)						ft msl				
ANALYTICAL DATA																	
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>		
Aluminum, total recoverable															µg/L		
Arsenic, total recoverable															µg/L		
Barium, total recoverable															µg/L		
Cadmium, total recoverable															µg/L		
Chloride															µg/L		
Chlorobenzene															µg/L		
Chromium, total recoverable															µg/L		
Cobalt, total recoverable															µg/L		
Copper, total recoverable															µg/L		
Cyanide															µg/L		
1,1-Dichloroethane															µg/L		
1,1-Dichloroethylene															µg/L		
trans-1,2-Dichloroethylene															µg/L		
Gross alpha															pCi/L		
Lead, total recoverable															µg/L		
Mercury, total recoverable															µg/L		
Nickel, total recoverable															µg/L		
Nitrate-nitrite as nitrogen															µg/L		
Nonvolatile beta															pCi/L		
PCB 1254															µg/L		
Radium, total alpha-emitting															pCi/L		
Selenium, total recoverable															µg/L		
Silver, total recoverable															µg/L		
Sodium, total recoverable															µg/L		
Sulfate															µg/L		
1,1,2,2-Tetrachloroethane															µg/L		
Tetrachloroethylene															µg/L		
Total phosphates (as P)															µg/L		
1,1,1-Trichloroethane															µg/L		
Trichloroethylene															µg/L		
Uranium, total recoverable															µg/L		
Zinc, total recoverable															µg/L		

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 12TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102266.7 E47127.3	33.328820 °N 81.741390 °W	(-102.8)-(-112.8) ft msl	348.9 ft msl	4" Steel	S	CBC

SAMPLE DATE 10/19/94 02/03/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	192.9	194.4	ft msl
pH	5.9	5.7	pH
Sp. conductance	32	35	µS/cm
Water temperature	19.2	19.4	°C
Alkalinity as CaCO ₃	9	10	mg/L
Turbidity	1.2	0.5	NTU
Volume purged	2.15	2.14	well volumes
Sampling code			
Synchronous water level	193.1 (12/20/94)	194.1 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	155	1		■		2	GE	28.7	1	J			1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.8	1				0	GE	8.73	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,610	1				0	GE	1,670	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE						0	GE	µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.7E+00	1				0	GP	pCi/L
Lead, total recoverable	8.14	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	5.06	1	J	■		0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	<50.0	1	J2			0	GE	<83.3	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	3.02	1	J			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,760	1				0	GE	1,230	1				0	GE	µg/L
Sulfate	7,740	1		■		0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	8.52	1				0	GE	5.54	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 12TB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N102260.1 E47133.0	33.328820 °N 81.741360 °W	14.5-(-5.5) ft msl	349.3 ft msl	4" Steel	S	CBA									
SAMPLE DATE		10/19/94		02/03/95											
FIELD DATA															
Parameter	4Q94				1Q95	Unit									
Water elevation	193.1				193.4	ft msl									
pH	5.1				4.8	pH									
Sp. conductance	21				23	µS/cm									
Water temperature	19.0				19.3	°C									
Alkalinity as CaCO ₃	1				2	mg/L									
Turbidity	2.7				1.5	NTU									
Volume purged	2.93				2.30	well volumes									
Sampling code															
Synchronous water level	193.3 (12/20/94)				194.3 (03/23/95)	ft msl									
ANALYTICAL DATA															
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	29.1	1	JVV3			1	WA	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	3.30	1	J			0	GE	4.00	1	J			0	WA	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,690	1				0	GE	2,290	1	J			0	WA	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	4.02	1	J			0	GE								µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1	J1			0	TM	pCi/L
Lead, total recoverable	7.43	1				0	GE	9.80	1	J			0	WA	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	2.00	1	JVV3			0	WA	µg/L
Nitrate-nitrite as nitrogen	120	1	J2			0	GE	126	1				0	GE	µg/L
Nonvolatile beta								2.1E+00	1	J1			0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	TM	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.30	1	J3			0	WA	µg/L
Silver, total recoverable	<2.00	1				0	GE	0.460	1	JVV			0	WA	µg/L
Sodium, total recoverable	1,580	1				0	GE	1,590	1				0	GE	µg/L
Sulfate	1,110	1	J			0	GE	1,370	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	10.3	1	J			0	WA	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	10.2	1				0	GE	12.6	1	JVV3			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 14A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101629.5 E48521.9	33.329690 °N 81.736480 °W	164.6-144.6 ft msl	348.7 ft msl	4" PVC	S	L(UD)

SAMPLE DATE 10/25/94 01/18/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	215.5	219.2	ft msl
pH	4.6	5.0	pH
Sp. conductance	175	162	µS/cm
Water temperature	18.5	18.0	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.9	8.0	NTU
Volume purged	2.19	2.70	well volumes
Sampling code			
Synchronous water level	218.3 (12/21/94)	216.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	57.7	1				2	GE	70.8	1			2	GE	µg/L	
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1			0	GE	µg/L	
Barium, total recoverable	53.2	1				0	GE	52.7	1			0	GE	µg/L	
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1			0	GE	µg/L	
Chloride	3,520	1	Y			0	GE	4,580	1		■	0	GE	µg/L	
Chlorobenzene	<100	100	VY			0	GE	<167	100			0	GE	µg/L	
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1			0	GE	µg/L	
Cobalt, total recoverable														µg/L	
Copper, total recoverable	<4.00	1				0	GE							µg/L	
Cyanide	<5.00	1	Y			0	GE	<8.33	1			0	GE	µg/L	
1,1-Dichloroethane	<100	100	VY			0	GE	<167	100			0	GE	µg/L	
1,1-Dichloroethylene	<100	100	VY			0	GE	<167	100			0	GE	µg/L	
trans-1,2-Dichloroethylene	<100	100	VY			0	GE	<167	100			0	GE	µg/L	
Gross alpha								1.1E+01	1			1	GP	pCi/L	
Lead, total recoverable	<3.00	1				0	GE	<5.00	1			0	GE	µg/L	
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1			0	GE	µg/L	
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1			0	GE	µg/L	
Nitrate-nitrite as nitrogen	17,500	20	JY2	■		2	GE	17,500	20		■	2	GE	µg/L	
Nonvolatile beta								8.9E+00	1			0	GP	pCi/L	
PCB 1254														µg/L	
Radium, total alpha-emitting								3.4E+00	1			0	GP	pCi/L	
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1			0	GE	µg/L	
Silver, total recoverable	<2.00	1				0	GE	<3.33	1			0	GE	µg/L	
Sodium, total recoverable	15,400	1				0	GE	15,200	1		■	0	GE	µg/L	
Sulfate	<1,000	1	Y			0	GE	<1,670	1			0	GE	µg/L	
1,1,2,2-Tetrachloroethane	<100	100	VY			0	GE	<167	100			0	GE	µg/L	
Tetrachloroethylene	2,990	100	VY	■		2	GE	2,400	100		■	2	GE	µg/L	
Total phosphates (as P)	<50.0	1	Y			0	GE	101	1			0	GE	µg/L	
1,1,1-Trichloroethane	<100	100	VY			0	GE	<167	100			0	GE	µg/L	
Trichloroethylene	2,830	100	VY	■		2	GE	2,230	100		■	2	GE	µg/L	
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1			0	GE	µg/L	
Zinc, total recoverable	2.78	1	J			0	GE	4.00	1			0	GE	µg/L	

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 14B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101639.0 E48519.1	33.329710 °N 81.736510 °W	193.9-188.9 ft msl	348.9 ft msl	4" PVC	S	GCL

SAMPLE DATE	10/18/94	01/31/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	217.6	220.5	ft msl
pH	4.9	4.9	pH
Sp. conductance	129	134	µS/cm
Water temperature	19.0	18.7	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.8	0.3	NTU
Volume purged	3.67	3.14	well volumes
Sampling code			
Synchronous water level	219.7 (12/21/94)	219.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	42.6	1				1	GE	34.2	1				1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	41.3	1				0	GE	37.8	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,930	1				0	GE	3,370	1				0	WA	µg/L
Chlorobenzene	<10.0	10				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	1.40	1	J			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<10.0	10				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<10.0	10				0	GE	2.00	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<10.0	10				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								6.2E+00	1				0	TM	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.235	1	J			0	GE	0.209	1	J			0	WA	µg/L
Nickel, total recoverable	<4.00	1				0	GE	1.10	1	J			0	WA	µg/L
Nitrate-nitrite as nitrogen	18,000	10	J2	■		2	GE	13,700	10		■		2	GE	µg/L
Nonvolatile beta								6.7E+00	1				0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.8E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.13	1	J			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<1.40	1				0	WA	µg/L
Sodium, total recoverable	13,100	1		■		0	GE	12,800	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	<700	1				0	WA	µg/L
1,1,2,2-Tetrachloroethane	<10.0	10				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	128	10		■		2	GE	98.7	1		■		2	WA	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<30.0	1				0	WA	µg/L
1,1,1-Trichloroethane	<10.0	10				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	50.0	10		■		2	GE	43.5	1		■		2	WA	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	7.72	1				0	GE	12.9	1	VV			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 14C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101648.6 E48517.3	33.329730 °N 81.736530 °W	243.9-223.9 ft msl	349.2 ft msl	4" PVC	S	M

SAMPLE DATE 10/19/94 01/31/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	232.2	234.3	ft msl
pH	6.3	6.6	pH
Sp. conductance	69	65	µS/cm
Water temperature	15.6	16.9	°C
Alkalinity as CaCO ₃	11	6	mg/L
Turbidity	16.4	25.0	NTU
Volume purged	0.551	0.293	well volumes
Sampling code	X	X	
Synchronous water level	232.1 (12/21/94)	232.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	165	1		■		2	GE	158	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	13.0	1				0	GE	14.1	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,030	1				0	GE	2,010	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	10.9	1				0	GE	11.1	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	4.61	1	J			0	GE								µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								2.3E+01	1		■		2	GP	pCi/L
Lead, total recoverable	24.3	1				0	GE	22.6	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	15.6	1		■		0	GE	14.6	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen	2,810	2	J2	■		0	GE	2,120	2				0	GE	µg/L
Nonvolatile beta								1.2E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.1E+00	1		■		0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	3,230	1				0	GE	3,180	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	9.30	1		■		2	GE	8.00	1		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	20.1	1		■		2	GE	16.1	1		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	311	1				0	GE	248	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 15A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102983.5 E48827.0	33.333180 °N 81.738310 °W	167.8-162.8 ft msl	367.7 ft msl	3.75" PVC	S	UL

SAMPLE DATE 10/25/94

01/31/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	220.4	224.1	ft msl
pH	6.0	6.2	pH
Sp. conductance	37	29	µS/cm
Water temperature	18.4	17.3	°C
Alkalinity as CaCO ₃	9	8	mg/L
Turbidity	1.8	1.3	NTU
Volume purged	4.22	4.11	well volumes
Sampling code			
Synchronous water level	222.8 (12/20/94)	221.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.74	1				0	GE	8.20	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,990	1				0	GE	2,600	1				0	WA	µg/L
Chlorobenzene	<100	100	V			0	GE	<5.00	1				0	WA	µg/L
Chromium, total recoverable	<4.00	1				0	GE	1.50	1	J			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<100	100	V			0	GE	<5.00	1				0	WA	µg/L
1,1-Dichloroethylene	<100	100	V			0	GE	<5.00	1				0	WA	µg/L
trans-1,2-Dichloroethylene	<100	100	V			0	GE	<5.00	1				0	WA	µg/L
Gross alpha								1.4E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	2.10	1	J			0	WA	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<5.40	1				0	WA	µg/L
Nitrate-nitrite as nitrogen	568	1	J2			0	GE	625	1				0	GE	µg/L
Nonvolatile beta								1.3E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	TM	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.00	1	JVV			0	WA	µg/L
Silver, total recoverable	<2.00	1				0	GE	<1.40	1				0	WA	µg/L
Sodium, total recoverable	1,910	1				0	GE	1,960	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	330	1	J			0	WA	µg/L
1,1,2,2-Tetrachloroethane	<100	100	V			0	GE	<5.00	1				0	WA	µg/L
Tetrachloroethylene	840	100	V	■		2	GE	769	100		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	6.70	1	J			0	WA	µg/L
1,1,1-Trichloroethane	<100	100	V			0	GE	<5.00	1				0	WA	µg/L
Trichloroethylene	7,190	100	V	■		2	GE	8,340	100		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	10.4	1				0	GE	11.9	1	VV			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 15AA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102953.2 E48818.5	33.333100 °N 81.738270 °W	147.1-142.4 ft msl	369.2 ft msl	4" PVC	S	LL

SAMPLE DATE 01/04/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		216.8	ft msl
pH		6.3	pH
Sp. conductance		27	µS/cm
Water temperature		17.5	°C
Alkalinity as CaCO ₃		6	mg/L
Turbidity		1.3	NTU
Volume purged		3.16	well volumes
Sampling code			
Synchronous water level	217.1 (12/20/94)	215.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.47	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<8.34	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<8.34	5				0	GE	µg/L
1,1-Dichloroethylene								<8.34	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.34	5				0	GE	µg/L
Gross alpha								2.6E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								109	1				0	GE	µg/L
Nonvolatile beta								1.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.34	5				0	GE	µg/L
Tetrachloroethylene								6.75	5	J	■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<8.34	5				0	GE	µg/L
Trichloroethylene								215	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 15C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N103002.1 E48834.0	33.333240 °N 81.738330 °W	260.6-240.6 ft msl	366.7 ft msl	3.75" PVC	B	M									
SAMPLE DATE		10/27/94	01/31/95												
FIELD DATA															
Parameter	4Q94	1Q95				Unit									
Water elevation	243.8	244.6				ft msl									
pH	5.3	5.8				pH									
Sp. conductance	41	34				µS/cm									
Water temperature	12.6	14.9				°C									
Alkalinity as CaCO ₃	6	7				mg/L									
Turbidity	6.9	66.2				NTU									
Volume purged	1.65	1.29				well volumes									
Sampling code	I	I													
Synchronous water level	243.0 (12/20/94)	245.1 (03/23/95)				ft msl									
ANALYTICAL DATA															
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	31.6	1	J			1	GE	142	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	3.95	1	J			0	GE	6.41	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<200	200				0	GE	<418	250				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<200	200				0	GE	<418	250				0	GE	µg/L
1,1-Dichloroethylene	<200	200				0	GE	<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene	<200	200				0	GE	<418	250				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	7.99	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								505	1				0	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.88	1	J			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,200	1				0	GE	2,600	1				0	GE	µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<200	200				0	GE	<418	250				0	GE	µg/L
Tetrachloroethylene	3,560	200		■		2	GE	2,930	250		■		2	GE	µg/L
Total phosphates (as P)								156	1				0	GE	µg/L
1,1,1-Trichloroethane	<200	200				0	GE	<418	250				0	GE	µg/L
Trichloroethylene	4,420	200		■		2	GE	5,180	250		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	12.2	1				0	GE	23.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 15D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102971.2 E48827.5	33.333160 °N 81.738290 °W	241.4-221.9 ft msl	368.5 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		233.1	ft msl
pH		6.2	pH
Sp. conductance		24	µS/cm
Water temperature		17.3	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		5.7	NTU
Volume purged		0.547	well volumes
Sampling code		X	
Synchronous water level	232.9 (12/20/94)	233.2 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								130	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<835	500				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<835	500				0	GE	µg/L
1,1-Dichloroethylene								<835	500				0	GE	µg/L
trans-1,2-Dichloroethylene								<835	500				0	GE	µg/L
Gross alpha								1.2E+00	1				0	GP	pCi/L
Lead, total recoverable								24.7	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								713	1				0	GE	µg/L
Nonvolatile beta								6.5E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<835	500				0	GE	µg/L
Tetrachloroethylene								1,250	500		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<835	500				0	GE	µg/L
Trichloroethylene								12,000	500		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								21.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 16A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103693.9 E48965.1	33.334980 °N 81.739330 °W	166.8-161.8 ft msl	367.5 ft msl	3.75" PVC	S	UL

SAMPLE DATE 01/30/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		226.2	ft msl
pH		6.1	pH
Sp. conductance		34	µS/cm
Water temperature		18.3	°C
Alkalinity as CaCO ₃		7	mg/L
Turbidity		2.2	NTU
Volume purged		3.26	well volumes
Sampling code			
Synchronous water level	224.0 (12/20/94)	220.6 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.42	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<83.5	50				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<83.5	50				0	GE	µg/L
1,1-Dichloroethylene								<83.5	50				0	GE	µg/L
trans-1,2-Dichloroethylene								<83.5	50				0	GE	µg/L
Gross alpha								6.6E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								944	1				0	GE	µg/L
Nonvolatile beta								5.7E-02	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<83.5	50				0	GE	µg/L
Tetrachloroethylene								1,020	50		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<83.5	50				0	GE	µg/L
Trichloroethylene								13,000	500		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								14.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 16C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103714.1 E48970.5	33.335030 °N 81.739350 °W	244.8-224.8 ft msl	367.6 ft msl	3.75" PVC	B	M

SAMPLE DATE 02/01/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		231.6	ft msl
pH		7.2	pH
Sp. conductance		53	µS/cm
Water temperature		17.0	°C
Alkalinity as CaCO ₃		15	mg/L
Turbidity		203.0	NTU
Volume purged		2.30	well volumes
Sampling code			
Synchronous water level	231.5 (12/20/94)	231.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								514	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								25.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<41.8	25				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<41.8	25				0	GE	µg/L
1,1-Dichloroethylene								<41.8	25				0	GE	µg/L
trans-1,2-Dichloroethylene								<41.8	25				0	GE	µg/L
Gross alpha								5.3E+00	1	J			0	GP	pCi/L
Lead, total recoverable								5.36	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								307	1				0	GE	µg/L
Nonvolatile beta								1.1E+01	1	J			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.8E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,360	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<41.8	25				0	GE	µg/L
Tetrachloroethylene								3,040	200		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<41.8	25				0	GE	µg/L
Trichloroethylene								5,970	200		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								92.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 17A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101976.6 E46245.7	33.326740 °N 81.743150 °W	160.6-155.6 ft msl	359.3 ft msl	3.75" PVC	S	UL

SAMPLE DATE 10/18/94 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	217.3	218.1	ft msl
pH	4.6	4.6	pH
Sp. conductance	202	225	µS/cm
Water temperature	18.7	18.5	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	1.3	0.8	NTU
Volume purged	3.68	3.44	well volumes
Sampling code			
Synchronous water level	218.0 (12/20/94)	217.9 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	71.1	1				2	GE	76.2	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	40.0	1				0	GE	41.0	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,810	1				0	GE	3,580	1				0	GE	µg/L
Chlorobenzene	<10.0	10				0	GE	<8.35	5				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<10.0	10				0	GE	<8.35	5				0	GE	µg/L
1,1-Dichloroethylene	30.0	10		■		2	GE	35.5	5		■		2	GE	µg/L
trans-1,2-Dichloroethylene	<10.0	10				0	GE	<8.35	5				0	GE	µg/L
Gross alpha								1.9E+01	1		■		2	GP	pCi/L
Lead, total recoverable	3.09	1	J			0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.817	1				0	GE	0.615	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	29,300	20	J2	■		2	GE	21,500	20		■		2	GE	µg/L
Nonvolatile beta								2.1E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E+00	1		■		0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	22,100	1		■		0	GE	23,100	2		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<10.0	10				0	GE	<8.35	5				0	GE	µg/L
Tetrachloroethylene	237	10		■		2	GE	230	5		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	10.7	10	J			0	GE	10.0	5				0	GE	µg/L
Trichloroethylene	84.0	10		■		2	GE	96.0	5		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	13.5	1				0	GE	7.04	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 17B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101994.6 E46237.7	33.326770 °N 81.743200 °W	190.8-185.8 ft msl	359.2 ft msl	3.75" PVC	S	GCL

SAMPLE DATE 10/25/94

01/16/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	226.6	226.2	ft msl
pH	4.9	4.8	pH
Sp. conductance	94	117	µS/cm
Water temperature	18.9	18.6	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.1	0.8	NTU
Volume purged	6.16	4.33	well volumes
Sampling code			
Synchronous water level	226.4 (12/20/94)	226.4 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	130	1		■	2	GE		132	1		■	2	GE		µg/L
Arsenic, total recoverable	<2.00	1			0	GE		<3.33	1			0	GE		µg/L
Barium, total recoverable	23.0	1			0	GE		24.9	1			0	GE		µg/L
Cadmium, total recoverable	<2.00	1			0	GE		<3.33	1			0	GE		µg/L
Chloride	2,860	1			0	GE		2,710	1			0	GE		µg/L
Chlorobenzene	<10.0	10	VY		0	GE		<167	100			0	GE		µg/L
Chromium, total recoverable	<4.00	1			0	GE		<6.67	1			0	GE		µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	4.61	1	J		0	GE									µg/L
Cyanide	<5.00	1	Y		0	GE		<8.33	1	1		0	GE		µg/L
1,1-Dichloroethane	<10.0	10	VY		0	GE		<167	100			0	GE		µg/L
1,1-Dichloroethylene	20.0	10	VY	■	2	GE		<167	100			0	GE		µg/L
trans-1,2-Dichloroethylene	<10.0	10	VY		0	GE		<100	100			0	GE		µg/L
Gross alpha								1.0E+01	1			1	GP		pCi/L
Lead, total recoverable	4.46	1	J		0	GE		<5.00	1			0	GE		µg/L
Mercury, total recoverable	<0.200	1			0	GE		<0.333	1			0	GE		µg/L
Nickel, total recoverable	<4.00	1			0	GE		<6.67	1			0	GE		µg/L
Nitrate-nitrite as nitrogen	9,810	20	JY2	■	1	GE		10,600	10		■	2	GE		µg/L
Nonvolatile beta								3.9E+00	1			0	GP		pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E+01	1		■	1	GP		pCi/L
Selenium, total recoverable	<2.00	1			0	GE		<3.33	1			0	GE		µg/L
Silver, total recoverable	<2.00	1			0	GE		<3.33	1			0	GE		µg/L
Sodium, total recoverable	12,400	1		■	0	GE		12,600	1		■	0	GE		µg/L
Sulfate	<1,000	1			0	GE		<1,670	1			0	GE		µg/L
1,1,2,2-Tetrachloroethane	<10.0	10	VY		0	GE		<167	100			0	GE		µg/L
Tetrachloroethylene	1,240	200	VY	■	2	GE		1,080	100		■	2	GE		µg/L
Total phosphates (as P)	<50.0	1			0	GE		<83.3	1			0	GE		µg/L
1,1,1-Trichloroethane	<10.0	10	VY		0	GE		<167	100			0	GE		µg/L
Trichloroethylene	6,910	200	VY	■	2	GE		7,120	100		■	2	GE		µg/L
Uranium, total recoverable	<20.0	1			0	GE		<33.3	1			0	GE		µg/L
Zinc, total recoverable	4.90	1			0	GE		4.42	1			0	GE		µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 17BB

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102009.5 E46220.8	33.326770 °N 81.743280 °W	137.3-132.6 ft msl	359 ft msl	4" PVC	S	LL

SAMPLE DATE 01/16/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		214.7	ft msl
pH		5.0	pH
Sp. conductance		111	µS/cm
Water temperature		18.8	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		3.1	NTU
Volume purged		3.25	well volumes
Sampling code			
Synchronous water level	214.3 (12/20/94)	214.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								106	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								32.9	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<41.8	25				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	1			0	GE	µg/L
1,1-Dichloroethane								<41.8	25				0	GE	µg/L
1,1-Dichloroethylene								<41.8	25				0	GE	µg/L
trans-1,2-Dichloroethylene								<41.8	25				0	GE	µg/L
Gross alpha								3.5E+00	1				0	GP	pCi/L
Lead, total recoverable								2.87	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								15,300	20		■		2	GE	µg/L
Nonvolatile beta								4.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<41.8	25				0	GE	µg/L
Tetrachloroethylene								755	25		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<41.8	25				0	GE	µg/L
Trichloroethylene								1,310	25		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.96	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 17C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102004.6 E46234.3	33.326780 °N 81.743230 °W	253.9-233.9 ft msl	358.2 ft msl	3.75" PVC	B	M

SAMPLE DATE 01/16/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code	D	D	
Synchronous water level			ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 17D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102056.9 E46226.2	33.326890 °N 81.743360 °W	232.8-213.3 ft msl	359.9 ft msl	4" PVC	S	M

SAMPLE DATE 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		227.3	ft msl
pH		5.0	pH
Sp. conductance		30	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.9	NTU
Volume purged		5.11	well volumes
Sampling code			
Synchronous water level	227.4 (12/20/94)	227.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								21.9	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.77	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,490	2				0	GE	µg/L
Nonvolatile beta								3.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.2E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,560	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								3.80	1				1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								17.5	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 18A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100416.1 E46110.4	33.323070 °N 81.740470 °W	163.9-158.9 ft msl	341.9 ft msl	3.75" PVC	S	UL

SAMPLE DATE 10/18/94 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	213.3	214.2	ft msl
pH	4.6	4.7	pH
Sp. conductance	40	46	µS/cm
Water temperature	18.2	18.6	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	1.2	1.2	NTU
Volume purged	5.13	4.05	well volumes
Sampling code			
Synchronous water level	214.0 (12/20/94)	213.9 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	35.4	1				1	GE	34.9	1				1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	12.5	1				0	GE	13.5	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,990	1				0	GE	1,940	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								8.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	4.46	1	J			0	GE	5.29	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	5.56	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen	3,680	5	J2	■		0	GE	3,570	2		■		0	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.8E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,790	1				0	GE	2,920	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	10.9	1		■		2	GE	11.3	1		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	19.4	1		■		2	GE	21.4	1		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	<2.00	1				0	GE	2.55	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 18B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100424.1 E46115.7	33.323100 °N 81.740470 °W	198.5-193.5 ft msl	342.1 ft msl	3.75" PVC	S	GCL

SAMPLE DATE 10/18/94 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	222.8	222.6	ft msl
pH	5.2	6.3	pH
Sp. conductance	118	188	µS/cm
Water temperature	18.1	18.4	°C
Alkalinity as CaCO ₃	3	33	mg/L
Turbidity	7.7	4.5	NTU
Volume purged	9.52	6.87	well volumes
Sampling code			
Synchronous water level	222.6 (12/20/94)	222.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	40.8	1				1	GE	293	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	42.5	1				0	GE	45.7	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,880	1				0	GE	4,380	1		■		0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	4.90	1				1	GE	6.20	1				1	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								5.5E+00	1				0	GP	pCi/L
Lead, total recoverable	4.77	1	J			0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	14,300	10	J2	■		2	GE	9,960	10		■		1	GE	µg/L
Nonvolatile beta								6.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.6E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	12,000	1		■		0	GE	11,800	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	2,180	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	38.1	1		■		2	GE	37.2	1		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	2.30	1				0	GE	2.00	1				0	GE	µg/L
Trichloroethylene	14.3	1		■		2	GE	13.5	1		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	15.0	1				0	GE	7.41	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 18C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100430.9 E46121.4	33.323120 °N 81.740470 °W	229.2-209.2 ft msl	342.5 ft msl	4" PVC	S	MGC

SAMPLE DATE 10/19/94 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	229.9	228.3	ft msl
pH	4.5	4.4	pH
Sp. conductance	27	29	µS/cm
Water temperature	15.6	18.0	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	13.3	9.8	NTU
Volume purged	0.736	0.719	well volumes
Sampling code	X	X	
Synchronous water level	228.8 (12/20/94)	228.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	82.0	1				2	GE	84.2	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	8.56	1				0	GE	8.45	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,910	1				0	GE	2,640	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	8.68	1				0	GE								µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								3.2E+00	1				0	GP	pCi/L
Lead, total recoverable	7.10	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,240	1	J2			0	GE	435	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.1E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,750	1				0	GE	1,880	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,500	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	2.98	1	J			0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 19A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100983.0 E50934.4	33.332200 °N 81.728870 °W	119.7-114.7 ft msl	300.3 ft msl	3.75" PVC	S	MCBC

SAMPLE DATE 10/21/94

01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	214.9	214.7	ft msl
pH	4.8	4.7	pH
Sp. conductance	24	25	µS/cm
Water temperature	18.9	18.7	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.3	0.7	NTU
Volume purged	4.02	3.50	well volumes
Sampling code			
Synchronous water level	215.0 (12/20/94)	216.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	27.6	1	J			1	GE	27.0	1	J			1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.38	1	J			0	GE	4.60	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,560	1				0	GE	2,140	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.7E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,120	1				0	GE	1,080	1				0	GE	µg/L
Nonvolatile beta								1.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.3E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,840	1				0	GE	1,830	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,720	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	3.80	1				1	GE	3.41	1			1	GE	µg/L	
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	29.3	1				2	GE	30.4	1			2	GE	µg/L	
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	12.9	1				0	GE	12.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 19B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100999.3 E50934.8	33.332240 °N 81.728900 °W	147.7-142.7 ft msl	300.4 ft msl	3.75" PVC	S	UL

SAMPLE DATE 10/21/94 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	217.2	216.9	ft msl
pH	4.9	4.9	pH
Sp. conductance	20	21	µS/cm
Water temperature	18.9	18.6	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	2.3	0.5	NTU
Volume purged	3.42	4.42	well volumes
Sampling code			
Synchronous water level	217.4 (12/20/94)	218.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.11	1	J			0	GE	4.16	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,520	1				0	GE	2,090	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	14.4	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								5.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	4.75	1	J			0	GE	3.45	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	683	1				0	GE	605	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,530	1				0	GE	1,510	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,320	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	126	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	4.18	1				0	GE	5.44	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 19C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100992.1 E50942.4	33.332240 °N 81.728870 °W	218.7-198.7 ft msl	300.8 ft msl	3.75" PVC	S	M

SAMPLE DATE 10/21/94 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	239.0	248.3	ft msl
pH	5.0	5.0	pH
Sp. conductance	96	102	µS/cm
Water temperature	19.6	19.2	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.9	1.3	NTU
Volume purged	3.49	4.16	well volumes
Sampling code			
Synchronous water level	238.8 (12/20/94)	239.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	9.32	1				0	GE	9.54	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	4,850	1		■		0	GE	5,060	1		■		0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								2.7E+00	1				0	GP	pCi/L
Lead, total recoverable	7.78	1				0	GE	4.84	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	6,320	5		■		1	GE	6,040	4		■		1	GE	µg/L
Nonvolatile beta								2.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.9E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	12,100	1		■		0	GE	12,000	1		■		0	GE	µg/L
Sulfate	5,120	1		■		0	GE	6,350	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	7.40	1		■		2	GE	7.73	1		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	41.3	1		■		2	GE	61.8	1		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	98.1	1				0	GE	99.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 20A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103545.1 E46060.5	33.329910 °N 81.746690 °W	162.6-157.6 ft msl	355.3 ft msl	3.75" PVC	S	L(UD)

SAMPLE DATE 01/19/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		219.9	ft msl
pH		5.5	pH
Sp. conductance		20	µS/cm
Water temperature		10.3	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		4.1	NTU
Volume purged		8.40	well volumes
Sampling code			
Synchronous water level	219.9 (12/20/94)	219.7 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1					GE	µg/L							
Arsenic, total recoverable	<3.33	1					GE	µg/L							
Barium, total recoverable	7.90	1					GE	µg/L							
Cadmium, total recoverable	<3.33	1					GE	µg/L							
Chloride								µg/L							
Chlorobenzene	<41.8	25					GE	µg/L							
Chromium, total recoverable	<6.67	1					GE	µg/L							
Cobalt, total recoverable								µg/L							
Copper, total recoverable								µg/L							
Cyanide	<8.33	1					GE	µg/L							
1,1-Dichloroethane	<41.8	25					GE	µg/L							
1,1-Dichloroethylene	<41.8	25					GE	µg/L							
trans-1,2-Dichloroethylene	<41.8	25					GE	µg/L							
Gross alpha	1.2E+00	1					GP	pCi/L							
Lead, total recoverable	<5.00	1					GE	µg/L							
Mercury, total recoverable	<0.333	1					GE	µg/L							
Nickel, total recoverable	<6.67	1					GE	µg/L							
Nitrate-nitrite as nitrogen	1,180	1					GE	µg/L							
Nonvolatile beta	8.0E-01	1	UI				GP	pCi/L							
PCB 1254								µg/L							
Radium, total alpha-emitting	2.0E-01	1	UI				GP	pCi/L							
Selenium, total recoverable	<3.33	1					GE	µg/L							
Silver, total recoverable	<3.33	1					GE	µg/L							
Sodium, total recoverable								µg/L							
Sulfate	1,210	1	J				GE	µg/L							
1,1,2,2-Tetrachloroethane	<41.8	25					GE	µg/L							
Tetrachloroethylene	<41.8	25					GE	µg/L							
Total phosphates (as P)								µg/L							
1,1,1-Trichloroethane	<41.8	25					GE	µg/L							
Trichloroethylene	810	25				■	GE	µg/L							
Uranium, total recoverable								µg/L							
Zinc, total recoverable	18.0	1					GE	µg/L							

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 20C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103556.3 E46088.8	33.329980 °N 81.746640 °W	232.7-212.7 ft msl	354.7 ft msl	3.75" PVC	S	M

SAMPLE DATE 01/05/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		227.5	ft msl
pH		11.5	pH
Sp. conductance		146	µS/cm
Water temperature		11.1	°C
Alkalinity as CaCO ₃		34	mg/L
Turbidity		13.1	NTU
Volume purged		1.40	well volumes
Sampling code		X	
Synchronous water level	227.6 (12/20/94)	227.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								431	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.26	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.2E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								4.97	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,590	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	J			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								6,430	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								26.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 21A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103967.0 E47217.2	33.332730 °N 81.744460 °W	159.5-154.5 ft msl	354.8 ft msl	3.75" PVC	S	LL

SAMPLE DATE 10/19/94 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	221.4	222.2	ft msl
pH	5.0	5.2	pH
Sp. conductance	23	25	µS/cm
Water temperature	18.5	18.1	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	2.9	1.0	NTU
Volume purged	4.56	3.18	well volumes
Sampling code			
Synchronous water level	222.4 (12/20/94)	222.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.05	1				0	GE	5.24	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,430	1				0	GE	2,270	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	8.36	1				0	GE								µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.4E+00	1				0	GP	pCi/L
Lead, total recoverable	7.79	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,490	1				0	GE	1,080	1				0	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,740	1				0	GE	2,190	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,300	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	15.0	1			■	2	GE	14.5	1			■	2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	52.6	1				0	GE	29.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 21B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104000.1 E47271.8	33.332890 °N 81.744380 °W	147.2-142.5 ft msl	355 ft msl	4" PVC	S	LL

SAMPLE DATE 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		221.8	ft msl
pH		5.7	pH
Sp. conductance		28	µS/cm
Water temperature		18.1	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		0.5	NTU
Volume purged		3.19	well volumes
Sampling code			
Synchronous water level	221.8 (12/20/94)	221.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								63.8	1	JVV			2	WA	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								13.1	1	Y			0	WA	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								1.10	1	JY3			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								1.89	1	JY			0	WA	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.7E+00	1				0	GP	pCi/L
Lead, total recoverable								1.30	1	JVY			0	WA	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								0.990	1	JY			0	WA	µg/L
Nitrate-nitrite as nitrogen								659	1				0	GE	µg/L
Nonvolatile beta								2.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								2.70	1	JVY			0	WA	µg/L
Silver, total recoverable								0.330	1	JY			0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,380	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								223	2	Y	■		2	WA	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.70	1	JY			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 21C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103973.0 E47234.6	33.332770 °N 81.744430 °W	233.2-213.2 ft msl	354.8 ft msl	3.75" PVC	S	M

SAMPLE DATE	10/19/94	01/20/95
-------------	----------	----------

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	229.9	229.5	ft msl
pH	5.0	5.3	pH
Sp. conductance	20	22	µS/cm
Water temperature	18.2	18.2	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	2.1	2.4	NTU
Volume purged	15.6	10.4	well volumes
Sampling code			
Synchronous water level	229.7 (12/20/94)	229.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	6.20	1				0	GE	6.51	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,450	1				0	GE	2,060	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	6.08	1	J			0	GE								µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								2.7E+00	1				0	GP	pCi/L
Lead, total recoverable	4.20	1	J			0	GE	3.44	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,090	1				0	GE	731	1				0	GE	µg/L
Nonvolatile beta								1.6E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.3E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,660	1				0	GE	1,660	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,350	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	11.3	1				0	GE	10.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 21TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103980.9 E47218.2	33.332760 °N 81.744490 °W	22.6-17.3 ft msl	354.6 ft msl	4" CS	S	CBA

SAMPLE DATE 10/19/94 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	194.7	195.0	ft msl
pH	5.8	5.8	pH
Sp. conductance	53	58	µS/cm
Water temperature	19.1	18.7	°C
Alkalinity as CaCO ₃	9	9	mg/L
Turbidity	5.1	2.0	NTU
Volume purged	2.28	2.38	well volumes
Sampling code			
Synchronous water level	194.8 (12/20/94)	195.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	26.5	1	J			1	GE	133	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	8.21	1				0	GE	11.2	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,440	1				0	GE	2,400	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								5.0E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	5.44	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	4.68	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen	<50.0	1				0	GE	<83.0	1				0	GE	µg/L
Nonvolatile beta								4.1E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.6E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,240	1				0	GE	2,350	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	8,850	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	5.44	1				0	GE	9.10	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 22

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102186.5 E48508.8	33.330900 °N 81.737600 °W	243.2-223.2 ft msl	360.1 ft msl	4" PVC	S	M

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	231.7 (12/21/94)	231.7 (01/16/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 23

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104312.0 E49294.0	33.336880 °N 81.739670 °W	250.4-230.4 ft msl	371.8 ft msl	4" PVC	S	M(VZ)

SAMPLE DATE 01/16/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		D	
Synchronous water level			ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 23B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104336.6 E49286.4	33.336920 °N 81.739730 °W	176.1-171.1 ft msl	371.6 ft msl	4" PVC	S	UL

SAMPLE DATE 01/16/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		224.9	ft msl
pH		4.7	pH
Sp. conductance		344	µS/cm
Water temperature		20.1	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		2.2	NTU
Volume purged		3.68	well volumes
Sampling code			
Synchronous water level	223.9 (12/20/94)	225.4 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								384	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								90.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1,670	1000				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	1			0	GE	µg/L
1,1-Dichloroethane								<1,670	1000				0	GE	µg/L
1,1-Dichloroethylene								<1,670	1000				0	GE	µg/L
trans-1,2-Dichloroethylene								<1,670	1000				0	GE	µg/L
Gross alpha								3.1E+01	1		■		2	GP	pCi/L
Lead, total recoverable								4.15	1	J			0	GE	µg/L
Mercury, total recoverable								0.812	1				0	GE	µg/L
Nickel, total recoverable								7.28	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen								33,700	50		■		2	GE	µg/L
Nonvolatile beta								1.6E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.3E+01	1		■		2	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1,670	1000				0	GE	µg/L
Tetrachloroethylene								26,200	1000		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1,670	1000				0	GE	µg/L
Trichloroethylene								31,700	1000		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								107	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 23TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104298.8 E49225.8	33.336740 °N 81.739820 °W	65.4-60.4 ft msl	372.9 ft msl	4" Steel	S	CBA

SAMPLE DATE 01/16/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		202.8	ft msl
pH		5.3	pH
Sp. conductance		32	µS/cm
Water temperature		19.9	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		1.7	NTU
Volume purged		2.20	well volumes
Sampling code			
Synchronous water level	202.1 (12/20/94)	202.9 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.15	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.4E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	µg/L
Nonvolatile beta								1.3E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.5E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								3,630	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								1.39	1	J			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 23TR

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104278.5 E49036.0	33.336390 °N 81.740280 °W	40.8-35.9 ft msl	372.7 ft msl	4" PVC	S	CBA

SAMPLE DATE 01/05/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		200.0	ft msl
pH		6.1	pH
Sp. conductance		66	µS/cm
Water temperature		13.1	°C
Alkalinity as CaCO ₃		22	mg/L
Turbidity		12.6	NTU
Volume purged		0.381	well volumes
Sampling code		X	
Synchronous water level	199.9 (12/20/94)	200.7 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								127	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								5.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								6.10	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	µg/L
Nonvolatile beta								4.4E+00	1	J			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								5,880	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								23.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 24

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104614.4 E49842.9	33.338450 °N 81.738810 °W	243.9-223.9 ft msl	380.2 ft msl	4" PVC	S	M

SAMPLE DATE 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		235.2	ft msl
pH		10.5	pH
Sp. conductance		146	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		25	mg/L
Turbidity		6.5	NTU
Volume purged		1.08	well volumes
Sampling code		X	
Synchronous water level	234.9 (12/20/94)	235.3 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								189	1		■		2	GE	µg/L
Arsenic, total recoverable								2.12	1	J			0	GE	µg/L
Barium, total recoverable								6.01	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<167	100				0	GE	µg/L
Chromium, total recoverable								4.54	1	J			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<167	100				0	GE	µg/L
1,1-Dichloroethylene								<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene								<167	100				0	GE	µg/L
Gross alpha								8.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,870	2				0	GE	µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								3,890	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<167	100				0	GE	µg/L
Tetrachloroethylene								2,240	100		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<167	100				0	GE	µg/L
Trichloroethylene								5,210	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								17.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 24A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104625.3 E49845.3	33.338470 °N 81.738820 °W	178.8-168.8 ft msl	381.6 ft msl	4" PVC	S	UL

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	225.9 (12/20/94)	227.9 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 25

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>						<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>					
N103498.8 E49668.9	33.335700 °N 81.737100 °W	244.7-224.7 ft msl						366.9 ft msl	4" PVC	S	M					
SAMPLE DATE									02/08/95							
FIELD DATA																
<u>Parameter</u>	<u>4Q94</u>							<u>1Q95</u>							<u>Unit</u>	
Water elevation															ft msl	
pH															pH	
Sp. conductance															µS/cm	
Water temperature															°C	
Alkalinity as CaCO ₃															mg/L	
Turbidity															NTU	
Volume purged															well volumes	
Sampling code								D								
Synchronous water level	237.2 (12/20/94)														ft msl	
ANALYTICAL DATA																
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>	
Aluminum, total recoverable															µg/L	
Arsenic, total recoverable															µg/L	
Barium, total recoverable															µg/L	
Cadmium, total recoverable															µg/L	
Chloride															µg/L	
Chlorobenzene															µg/L	
Chromium, total recoverable															µg/L	
Cobalt, total recoverable															µg/L	
Copper, total recoverable															µg/L	
Cyanide															µg/L	
1,1-Dichloroethane															µg/L	
1,1-Dichloroethylene															µg/L	
trans-1,2-Dichloroethylene															µg/L	
Gross alpha															pCi/L	
Lead, total recoverable															µg/L	
Mercury, total recoverable															µg/L	
Nickel, total recoverable															µg/L	
Nitrate-nitrite as nitrogen															µg/L	
Nonvolatile beta															pCi/L	
PCB 1254															µg/L	
Radium, total alpha-emitting															pCi/L	
Selenium, total recoverable															µg/L	
Silver, total recoverable															µg/L	
Sodium, total recoverable															µg/L	
Sulfate															µg/L	
1,1,2,2-Tetrachloroethane															µg/L	
Tetrachloroethylene															µg/L	
Total phosphates (as P)															µg/L	
1,1,1-Trichloroethane															µg/L	
Trichloroethylene															µg/L	
Uranium, total recoverable															µg/L	
Zinc, total recoverable															µg/L	

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 25A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103504.8 E49657.9	33.335690 °N 81.737140 °W	169.7-159.7 ft msl	366.4 ft msl	4" PVC	S	LL

SAMPLE DATE 01/27/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		218.0	ft msl
pH		5.4	pH
Sp. conductance		23	µS/cm
Water temperature		19.7	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.6	NTU
Volume purged		3.66	well volumes
Sampling code			
Synchronous water level	217.6 (12/20/94)	219.9 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.57	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1				0	GE	µg/L
Chloride								µg/L
Chlorobenzene	<83.5	50				0	GE	µg/L
Chromium, total recoverable	<6.67	1				0	GE	µg/L
Cobalt, total recoverable								µg/L
Copper, total recoverable								µg/L
Cyanide	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<83.5	50				0	GE	µg/L
1,1-Dichloroethylene	<83.5	50				0	GE	µg/L
trans-1,2-Dichloroethylene	<83.5	50				0	GE	µg/L
Gross alpha	1.1E+00	1				0	GP	pCi/L
Lead, total recoverable	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,600	1				0	GE	µg/L
Nonvolatile beta	9.8E-01	1	UI			0	GP	pCi/L
PCB 1254								µg/L
Radium, total alpha-emitting	4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	µg/L
Sodium, total recoverable								µg/L
Sulfate	1,270	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<83.5	50				0	GE	µg/L
Tetrachloroethylene	205	50	J2	■		2	GE	µg/L
Total phosphates (as P)								µg/L
1,1,1-Trichloroethane	<83.5	50				0	GE	µg/L
Trichloroethylene	1,720	50	J2	■		2	GE	µg/L
Uranium, total recoverable								µg/L
Zinc, total recoverable	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 26

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104612.8 E48941.7	33.336970 °N 81.741180 °W	240.7-220.7 ft msl	361.7 ft msl	4" PVC	S	M

SAMPLE DATE 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		237.2	ft msl
pH		5.2	pH
Sp. conductance		18	µS/cm
Water temperature		19.8	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		1.9	NTU
Volume purged		3.52	well volumes
Sampling code			
Synchronous water level		237.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								20.4	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<16.7	10				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene								<16.7	10				0	GE	µg/L
Gross alpha								9.4E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								242	1				0	GE	µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,750	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L
Tetrachloroethylene								89.0	10			■	2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<16.7	10				0	GE	µg/L
Trichloroethylene								377	10			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.35	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 26A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104602.3 E48440.7	33.336130 °N 81.742480 °W	179.8-169.8 ft msl	361.8 ft msl	4" PVC	S	UL

SAMPLE DATE 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.2	ft msl
pH		5.2	pH
Sp. conductance		20	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.8	NTU
Volume purged		3.36	well volumes
Sampling code			
Synchronous water level	225.2 (12/20/94)	225.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<8.35	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<8.35	5				0	GE	µg/L
1,1-Dichloroethylene								<8.35	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.35	5				0	GE	µg/L
Gross alpha								2.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.279	1	J			0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								141	1				0	GE	µg/L
Nonvolatile beta								2.9E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								2,240	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.35	5				0	GE	µg/L
Tetrachloroethylene								26.0	5		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<8.35	5				0	GE	µg/L
Trichloroethylene								97.0	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.70	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

☛ = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 26B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>									
N104646.7 E48944.6	33.337050 °N 81.741240 °W	136.9-132.1 ft msl	362.8 ft msl	4" PVC	S	LL									
SAMPLE DATE				01/05/95											
FIELD DATA															
<u>Parameter</u>	<u>4Q94</u>				<u>1Q95</u>	<u>Unit</u>									
Water elevation					220.6	ft msl									
pH						pH									
Sp. conductance						µS/cm									
Water temperature						°C									
Alkalinity as CaCO ₃						mg/L									
Turbidity						NTU									
Volume purged						well volumes									
Sampling code					P										
Synchronous water level	220.8 (12/20/94)				219.9 (03/23/95)	ft msl									
ANALYTICAL DATA															
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 27

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104972.8 E49487.7	33.338660 °N 81.740440 °W	244.0-234.0 ft msl	375.5 ft msl	4" PVC	S	M

SAMPLE DATE 01/11/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		237.8	ft msl
pH		4.7	pH
Sp. conductance		65	µS/cm
Water temperature		19.7	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.9	NTU
Volume purged		26.8	well volumes
Sampling code			
Synchronous water level	235.9 (12/20/94)	236.3 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	Unit	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								µg/L	113	1		■		2	GE	µg/L
Arsenic, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Barium, total recoverable								µg/L	17.0	1				0	GE	µg/L
Cadmium, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Chloride								µg/L								
Chlorobenzene								µg/L	<1.67	1				0	GE	µg/L
Chromium, total recoverable								µg/L	<6.67	1				0	GE	µg/L
Cobalt, total recoverable								µg/L								
Copper, total recoverable								µg/L								
Cyanide								µg/L	<8.33	1				0	GE	µg/L
1,1-Dichloroethane								µg/L	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								µg/L	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								µg/L	<1.67	1				0	GE	µg/L
Gross alpha								pCi/L	2.4E+00	1				0	GP	pCi/L
Lead, total recoverable								µg/L	<5.00	1				0	GE	µg/L
Mercury, total recoverable								µg/L	<0.333	1				0	GE	µg/L
Nickel, total recoverable								µg/L	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								µg/L	3,380	4		■		0	GE	µg/L
Nonvolatile beta								pCi/L	9.6E-01	1				0	GP	pCi/L
PCB 1254								µg/L								
Radium, total alpha-emitting								pCi/L	2.9E+00	1				0	GP	pCi/L
Selenium, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Silver, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Sodium, total recoverable								µg/L								
Sulfate								µg/L	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								µg/L	<1.67	1				0	GE	µg/L
Tetrachloroethylene								µg/L	1.06	1	J			0	GE	µg/L
Total phosphates (as P)								µg/L								
1,1,1-Trichloroethane								µg/L	<1.67	1				0	GE	µg/L
Trichloroethylene								µg/L	2.20	1				0	GE	µg/L
Uranium, total recoverable								µg/L								
Zinc, total recoverable								µg/L	2.18	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

◆ = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 27A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104962.8 E49487.8	33.338640 °N 81.740420 °W	203.8-193.8 ft msl	375.2 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/27/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		229.5	ft msl
pH		5.3	pH
Sp. conductance		22	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.4	NTU
Volume purged		4.44	well volumes
Sampling code			
Synchronous water level	229.5 (12/20/94)	230.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								20.2	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.29	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<418	250				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<418	250				0	GE	µg/L
1,1-Dichloroethylene								<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene								<418	250				0	GE	µg/L
Gross alpha								1.1E+00	1				0	GP	pCi/L
Lead, total recoverable								4.95	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,100	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI3			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,360	1	J			0	GE	µg/L
1,1,1,2-Tetrachloroethane								<418	250				0	GE	µg/L
Tetrachloroethylene								1,900	250	J2	■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<418	250				0	GE	µg/L
Trichloroethylene								17,500	250	J2	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								141	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 27B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104940.3 E49486.4	33.338590 °N 81.740380 °W	169.9-164.4 ft msl	376.8 ft msl	4" PVC	S	UL

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		226.0	ft msl
pH		5.3	pH
Sp. conductance		22	µS/cm
Water temperature		18.1	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.5	NTU
Volume purged		4.41	well volumes
Sampling code			
Synchronous water level	225.9 (12/20/94)	227.9 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.29	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<418	250				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<418	250				0	GE	µg/L
1,1-Dichloroethylene								<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene								<418	250				0	GE	µg/L
Gross alpha								4.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,100	1				0	GE	µg/L
Nonvolatile beta								4.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,350	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<418	250				0	GE	µg/L
Tetrachloroethylene								2,080	250	J2	■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<418	250				0	GE	µg/L
Trichloroethylene								24,600	500	J2	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.46	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 27TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104951.4 E49486.5	33.338610 °N 81.740400 °W	55.9-50.6 ft msl	376.6 ft msl	4" CS	S	CBA

SAMPLE DATE 01/11/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		202.2	ft msl
pH		4.9	pH
Sp. conductance		27	µS/cm
Water temperature		19.1	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.8	NTU
Volume purged		2.50	well volumes
Sampling code			
Synchronous water level	201.8 (12/20/94)	202.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								20.2	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable								6.42	1				0	GE	µg/L
Mercury, total recoverable								0.223	1	J			0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	µg/L
Nonvolatile beta								1.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.6E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								3,030	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.11	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 28

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104941.8 E48517.3	33.337010 °N 81.742940 °W	230.6-210.6 ft msl	354.8 ft msl	4" PVC	S	M

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		230.0	ft msl
pH		6.6	pH
Sp. conductance		61	µS/cm
Water temperature		17.9	°C
Alkalinity as CaCO ₃		20	mg/L
Turbidity		1.4	NTU
Volume purged		8.64	well volumes
Sampling code			
Synchronous water level	230.9 (12/20/94)	231.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								39.1	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.32	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.6E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								207	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								332	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 28A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>		
N104947.7 E48521.9	33.337030 °N 81.742940 °W	157.8-152.8 ft msl	355 ft msl	4" PVC	S	UL		
SAMPLE DATE				01/10/95				
FIELD DATA								
<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>				<u>Unit</u>		
Water elevation		223.8				ft msl		
pH		4.8				pH		
Sp. conductance		22				µS/cm		
Water temperature		18.1				°C		
Alkalinity as CaCO ₃		0				mg/L		
Turbidity		0.5				NTU		
Volume purged		3.22				well volumes		
Sampling code								
Synchronous water level	224.9 (12/20/94)	224.8 (03/23/95)				ft msl		
ANALYTICAL DATA								
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable		<33.3	1				0	GE µg/L
Arsenic, total recoverable		<3.33	1				0	GE µg/L
Barium, total recoverable		3.08	1	J			0	GE µg/L
Cadmium, total recoverable		<3.33	1				0	GE µg/L
Chloride								µg/L
Chlorobenzene		<8.35	5				0	GE µg/L
Chromium, total recoverable		<6.67	1				0	GE µg/L
Cobalt, total recoverable								µg/L
Copper, total recoverable								µg/L
Cyanide		<8.33	1	J1			0	GE µg/L
1,1-Dichloroethane		<8.35	5				0	GE µg/L
1,1-Dichloroethylene		<8.35	5				0	GE µg/L
trans-1,2-Dichloroethylene		<8.35	5				0	GE µg/L
Gross alpha		8.8E-01	1	UI			0	GP pCi/L
Lead, total recoverable		<5.00	1				0	GE µg/L
Mercury, total recoverable		<0.333	1				0	GE µg/L
Nickel, total recoverable		<6.67	1				0	GE µg/L
Nitrate-nitrite as nitrogen		361	1				0	GE µg/L
Nonvolatile beta		1.3E+00	1	UI			0	GP pCi/L
PCB 1254								µg/L
Radium, total alpha-emitting		1.0E+00	1				0	GP pCi/L
Selenium, total recoverable		<3.33	1				0	GE µg/L
Silver, total recoverable		<3.33	1				0	GE µg/L
Sodium, total recoverable								µg/L
Sulfate		<1,670	1				0	GE µg/L
1,1,2,2-Tetrachloroethane		<8.35	5				0	GE µg/L
Tetrachloroethylene		<8.35	5				0	GE µg/L
Total phosphates (as P)								µg/L
1,1,1-Trichloroethane		<8.35	5				0	GE µg/L
Trichloroethylene		26.5	5			■	2	GE µg/L
Uranium, total recoverable								µg/L
Zinc, total recoverable		34.5	1				0	GE µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 29A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107326.8 E51236.4	33.346720 °N 81.740420 °W	122.9-117.3 ft msl	365.2 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/30/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		221.1	ft msl
pH		6.1	pH
Sp. conductance		50	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		8	mg/L
Turbidity		0.8	NTU
Volume purged		2.25	well volumes
Sampling code			
Synchronous water level	220.8 (12/20/94)	221.2 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								21.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.6E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								514	1				0	GE	µg/L
Nonvolatile beta								2.1E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								4,620	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								22.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 29TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107330.4 E51245.7	33.346740 °N 81.740400 °W	63.9-58.6 ft msl	365 ft msl	4" CS	S	CBA

SAMPLE DATE 01/30/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		213.2	ft msl
pH		4.6	pH
Sp. conductance		21	µS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃			mg/L
Turbidity		0.8	NTU
Volume purged		2.53	well volumes
Sampling code			
Synchronous water level	212.9 (12/20/94)	213.6 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								6.28	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								461	1				0	GE	µg/L
Nonvolatile beta								9.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								2.72	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 30A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105727.4 E48004.1	33.337900 °N 81.745820 °W	36.9-26.9 ft msl	355 ft msl	4" PVC	S	CBA

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		199.3	ft msl
pH		6.2	pH
Sp. conductance		69	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		16	mg/L
Turbidity		1.4	NTU
Volume purged		2.46	well volumes
Sampling code			
Synchronous water level	199.3 (12/20/94)	200.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								114	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								15.0	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.1E+00	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	µg/L
Nonvolatile beta								2.1E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								4,930	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								10.6	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 30AA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105715.7 E47970.5	33.337820 °N 81.745880 °W	96.4-90.8 ft msl	353 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.2	ft msl
pH		6.3	pH
Sp. conductance		93	µS/cm
Water temperature		17.5	°C
Alkalinity as CaCO ₃		23	mg/L
Turbidity		0.8	NTU
Volume purged		0.560	well volumes
Sampling code		X	
Synchronous water level	224.7 (12/20/94)	224.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<33.3	1					GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	19.4	1					GE	19.4	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Chloride							µg/L								µg/L
Chlorobenzene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable							µg/L								µg/L
Copper, total recoverable							µg/L								µg/L
Cyanide	<8.33	1	J1				GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Gross alpha	3.3E-01	1	UI				GP	3.3E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<5.00	1					GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1					GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	<83.3	1					GE	<83.3	1				0	GE	µg/L
Nonvolatile beta	1.8E+00	1					GP	1.8E+00	1				0	GP	pCi/L
PCB 1254							µg/L								µg/L
Radium, total alpha-emitting	6.0E-01	1					GP	6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable							µg/L								µg/L
Sulfate	12,100	1					GE	12,100	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)							µg/L								µg/L
1,1,1-Trichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable							µg/L								µg/L
Zinc, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 30B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105719.9 E47981.8	33.337850 °N 81.745860 °W	128.7-123.1 ft msl	353.5 ft msl	4" PVC	S	LL

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		225.4	ft msl
pH		3.8	pH
Sp. conductance		35	µS/cm
Water temperature		18.3	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.3	NTU
Volume purged		2.67	well volumes
Sampling code			
Synchronous water level	226.1 (12/20/94)	226.3 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								55.6	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.21	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.1E+00	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								50.0	1	J			0	GE	µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.7E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								4,310	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								6.28	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 30C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105731.1 E48013.7	33.337930 °N 81.745800 °W	237.6-217.6 ft msl	354.6 ft msl	4" PVC	S	M

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		230.1	ft msl
pH		4.8	pH
Sp. conductance		16	µS/cm
Water temperature		17.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.0	NTU
Volume purged		9.99	well volumes
Sampling code			
Synchronous water level	231.2 (12/20/94)	231.5 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								5.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								299	1				0	GE	µg/L
Nonvolatile beta								1.7E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								28.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 30CC

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105724.2 E47993.3	33.337880 °N 81.745840 °W	164.0-158.4 ft msl	354 ft msl	4" PVC	S	UL

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		225.6	ft msl
pH		4.8	pH
Sp. conductance		23	µS/cm
Water temperature		18.5	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.5	NTU
Volume purged		2.93	well volumes
Sampling code			
Synchronous water level	226.1 (12/20/94)	226.2 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.34	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								840	1				0	GE	µg/L
Nonvolatile beta								3.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,020	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								11.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 31A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101979.3 E50100.2	33.333040 °N 81.733000 °W	22.0-12.0 ft msl	348.1 ft msl	4" PVC	S	CBA

SAMPLE DATE 10/21/94

02/01/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	198.7	198.7	ft msl
pH	5.1	4.7	pH
Sp. conductance	18	20	µS/cm
Water temperature	19.1	19.0	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.3	0.3	NTU
Volume purged	2.49	2.42	well volumes
Sampling code			
Synchronous water level	198.7 (12/20/94)	199.7 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,510	1				0	GE	1,770	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	10.9	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								-1.5E-02	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	370	1				0	GE	396	1				0	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.2E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,460	1				0	GE	1,460	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,010	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	3.47	1				0	GE	3.89	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 31B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101981.3 E50078.7	33.333010 °N 81.733060 °W	157.3-152.3 ft msl	348.3 ft msl	4" PVC	S	LL

SAMPLE DATE 10/21/94 02/01/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	214.1	221.1	ft msl
pH	4.7	4.7	pH
Sp. conductance	32	27	µS/cm
Water temperature	19.0	19.4	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	1.0	0.3	NTU
Volume purged	3.73	4.10	well volumes
Sampling code			
Synchronous water level	214.1 (12/20/94)	220.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	29.0	1	J			1	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.35	1				0	GE	4.82	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,670	1				0	GE	1,950	1				0	GE	µg/L
Chlorobenzene	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
1,1-Dichloroethylene	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
Gross alpha								1.6E+00	1	J			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	2,110	2				0	GE	1,350	1				0	GE	µg/L
Nonvolatile beta								1.7E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,190	1				0	GE	1,990	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
Tetrachloroethylene	286	10		■		2	GE	755	10		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<10.0	10				0	GE	<16.7	10				0	GE	µg/L
Trichloroethylene	627	10		■		2	GE	599	10		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	3.06	1	J			0	GE	2.91	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 31C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101979.6 E50089.9	33.333030 °N 81.733030 °W	236.1-216.1 ft msl	348.1 ft msl	4" PVC	S	MGC

SAMPLE DATE 10/25/94 01/25/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	235.2	235.3	ft msl
pH	5.4	5.4	pH
Sp. conductance	117	109	µS/cm
Water temperature	19.3	18.2	°C
Alkalinity as CaCO ₃	4	3	mg/L
Turbidity	1.1	1.7	NTU
Volume purged	7.92	5.39	well volumes
Sampling code			
Synchronous water level	235.0 (12/20/94)	235.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	42.0	1				1	GE	40.3	1				1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	20.7	1				0	GE	20.0	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	4,790	1		■		0	GE	5,500	1		■		0	GE	µg/L
Chlorobenzene	<1,000	1000	V			0	GE	<835	500				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1,000	1000	V			0	GE	<835	500				0	GE	µg/L
1,1-Dichloroethylene	<1,000	1000	V			0	GE	<835	500				0	GE	µg/L
trans-1,2-Dichloroethylene	<1,000	1000	V			0	GE	<835	500				0	GE	µg/L
Gross alpha								1.3E+01	1				1	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	0.213	1	J			0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	9,020	20	J2	■		1	GE	6,830	10		■		1	GE	µg/L
Nonvolatile beta								1.0E+01	1				0	GP	pCi/L
PCB 1254	<0.476	1				0	GE	<0.817	1				0	GE	µg/L
Radium, total alpha-emitting								1.0E+01	1		■		1	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	11,700	1		■		0	GE	12,200	1		■		0	GE	µg/L
Sulfate	7,400	1		■		0	GE	8,750	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1,000	1000	V			0	GE	<835	500				0	GE	µg/L
Tetrachloroethylene	45,600	1000	V	■		2	GE	42,600	2500		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1,000	1000	V			0	GE	<835	500				0	GE	µg/L
Trichloroethylene	29,000	1000	V	■		2	GE	41,800	500		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	17.4	1				0	GE	15.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 31CC

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101983.1 E50067.9	33.333000 °N 81.733100 °W	181.4-176.7 ft msl	348.6 ft msl	4" PVC	S	UL

SAMPLE DATE 02/01/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		222.0	ft msl
pH		5.2	pH
Sp. conductance		55	µS/cm
Water temperature		19.5	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.7	NTU
Volume purged		2.59	well volumes
Sampling code			
Synchronous water level	214.1 (12/20/94)	220.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								37.8	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								14.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<8.35	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<8.35	5				0	GE	µg/L
1,1-Dichloroethylene								<8.35	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.35	5				0	GE	µg/L
Gross alpha								1.1E+00	1	J			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3,320	2		■		0	GE	µg/L
Nonvolatile beta								1.4E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								2,300	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.35	5				0	GE	µg/L
Tetrachloroethylene								157	5		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<8.35	5				0	GE	µg/L
Trichloroethylene								490	10		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								9.88	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 32

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N99655.6 E52733.9	33.332210 °N 81.721550 °W	218.1-198.1 ft msl	255.1 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.5	ft msl
pH		5.1	pH
Sp. conductance		26	µS/cm
Water temperature		18.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.9	NTU
Volume purged		20.3	well volumes
Sampling code			
Synchronous water level	224.6 (12/20/94)	225.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.6E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								902	1				0	GE	µg/L
Nonvolatile beta								1.3E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,140	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 32B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N99676.0 E52742.5	33.332260 °N 81.721570 °W	132.5-127.5 ft msl	255.4 ft msl	2" PVC	V	LL

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		210.5	ft msl
pH		5.0	pH
Sp. conductance		21	µS/cm
Water temperature		18.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.3	NTU
Volume purged		2.20	well volumes
Sampling code			
Synchronous water level	211.2 (12/20/94)	212.9 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.69	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.1E+00	1				0	GP	pCi/L
Lead, total recoverable								46.0	1				1	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								913	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								6.69	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 32C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N99684.9 E52746.9	33.332290 °N 81.721570 °W	188.6-183.7 ft msl	255.7 ft msl	2" PVC	V	UL

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		216.8	ft msl
pH		5.4	pH
Sp. conductance		25	µS/cm
Water temperature		20.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.4	NTU
Volume purged		2.58	well volumes
Sampling code			
Synchronous water level	216.5 (12/20/94)	218.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.20	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.1E-02	1	UI			0	GP	pCi/L
Lead, total recoverable								12.5	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								969	1				0	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								5.51	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 33

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N98031.0 E51736.3	33.326990 °N 81.721020 °W	228.7-208.7 ft msl	255.9 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/27/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		216.2	ft msl
pH		4.9	pH
Sp. conductance		63	µS/cm
Water temperature		18.5	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.3	NTU
Volume purged		6.93	well volumes
Sampling code			
Synchronous water level	217.5 (12/20/94)	219.2 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								20.3	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.6E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3,550	4		■		0	GE	µg/L
Nonvolatile beta								9.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,830	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								4.20	1	J2			1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								7.10	1	J2	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 33A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N98006.7 E51738.0	33.326930 °N 81.720960 °W	88.4-82.8 ft msl	255.4 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		204.4	ft msl
pH		4.9	pH
Sp. conductance		23	µS/cm
Water temperature		18.3	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.2	NTU
Volume purged		2.97	well volumes
Sampling code			
Synchronous water level	205.0 (12/20/94)	205.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								107	1	VVY	■		2	WA	µg/L
Arsenic, total recoverable								2.80	1	JVV			0	WA	µg/L
Barium, total recoverable								4.30	1	JY			0	WA	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1	J1			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1	J1			0	GE	µg/L
1,1-Dichloroethylene								<1.67	1	J1			0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1	J1			0	GE	µg/L
Gross alpha								2.6E+00	1				0	TM	pCi/L
Lead, total recoverable								3.60	1	JY			0	WA	µg/L
Mercury, total recoverable								0.167	1	JVVY			0	WA	µg/L
Nickel, total recoverable								0.850	1	J			0	WA	µg/L
Nitrate-nitrite as nitrogen								849	1				0	GE	µg/L
Nonvolatile beta								2.8E+00	1				0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								0.350	1	JVV			0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,550	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1	J1			0	GE	µg/L
Trichloroethylene								19.5	1	J2	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.90	1	JVV			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 33B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N97995.9 E51741.9	33.326920 °N 81.720930 °W	126.3-120.7 ft msl	255 ft msl	4" PVC	S	LL/CBC

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		207.5	ft msl
pH		5.0	pH
Sp. conductance		33	µS/cm
Water temperature		18.1	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.6	NTU
Volume purged		3.34	well volumes
Sampling code			
Synchronous water level	207.7 (12/20/94)	208.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								814	1				0	GE	µg/L
Nonvolatile beta								2.9E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								2,600	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								7.92	1			■	2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								19.0	1			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 33C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97984.8 E51746.7	33.326900 °N 81.720900 °W	171.0-165.4 ft msl	255.3 ft msl	4" PVC	S	UL

SAMPLE DATE 01/27/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		210.4	ft msl
pH		4.9	pH
Sp. conductance		46	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.2	NTU
Volume purged		3.89	well volumes
Sampling code			
Synchronous water level	210.9 (12/20/94)	211.6 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.70	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.2E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,650	2		■		0	GE	µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,530	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								2.86	1				1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								6.96	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 33TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N98018.2 E51734.0	33.326950 °N 81.721000 °W	23.4-18.1 ft msl	255.5 ft msl	4" CS	S	CBA

SAMPLE DATE 01/27/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		194.5	ft msl
pH		4.9	pH
Sp. conductance		23	µS/cm
Water temperature		18.8	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.8	NTU
Volume purged		2.19	well volumes
Sampling code			
Synchronous water level	195.3 (12/20/94)	196.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.22	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.0E+00	1				0	GP	pCi/L
Lead, total recoverable								6.47	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								320	1				0	GE	µg/L
Nonvolatile beta								4.2E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								2,920	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								1.70	1	J2			0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								20.3	1	J2	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.44	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 34A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104954.9 E50534.9	33.340330 °N 81.737650 °W	118.6-113.6 ft msl	384 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/20/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		219.8	ft msl
pH		5.6	pH
Sp. conductance		20	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.6	NTU
Volume purged		2.61	well volumes
Sampling code			
Synchronous water level	219.5 (12/20/94)	220.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	23.1	1	J			0	GE	µg/L
Arsenic, total recoverable	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.90	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1				0	GE	µg/L
Chloride								µg/L
Chlorobenzene	<167	100				0	GE	µg/L
Chromium, total recoverable	<6.67	1				0	GE	µg/L
Cobalt, total recoverable								µg/L
Copper, total recoverable								µg/L
Cyanide	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<167	100				0	GE	µg/L
1,1-Dichloroethylene	<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene	<167	100				0	GE	µg/L
Gross alpha	7.7E-01	1				0	GP	pCi/L
Lead, total recoverable	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	917	1				0	GE	µg/L
Nonvolatile beta	-1.4E-01	1	UI			0	GP	pCi/L
PCB 1254								µg/L
Radium, total alpha-emitting	7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	µg/L
Sodium, total recoverable								µg/L
Sulfate	1,390	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<167	100				0	GE	µg/L
Tetrachloroethylene	<167	100				0	GE	µg/L
Total phosphates (as P)								µg/L
1,1,1-Trichloroethane	<167	100				0	GE	µg/L
Trichloroethylene	2,720	100				2	GE	µg/L
Uranium, total recoverable								µg/L
Zinc, total recoverable	63.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 34B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104944.7 E50534.9	33.340310 °N 81.737630 °W	187.0-182.0 ft msl	384 ft msl	4" PVC	S	UL

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		227.5	ft msl
pH		5.2	pH
Sp. conductance		21	µS/cm
Water temperature		20.7	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.5	NTU
Volume purged		3.48	well volumes
Sampling code			
Synchronous water level	227.5 (12/20/94)	228.2 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								29.8	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.25	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.2E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.230	1	J			0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								987	1				0	GE	µg/L
Nonvolatile beta								1.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.8E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								17.7	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								17.9	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								14.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 34C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104934.1 E50535.5	33.340280 °N 81.737610 °W	240.9-220.9 ft msl	383.9 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/12/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		230.3	ft msl
pH		4.7	pH
Sp. conductance		21	µS/cm
Water temperature		20.7	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.7	NTU
Volume purged		7.01	well volumes
Sampling code			
Synchronous water level	230.2 (12/20/94)	230.8 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								58.3	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.10	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<3.34	2				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<3.34	2				0	GE	µg/L
1,1-Dichloroethylene								<3.34	2				0	GE	µg/L
trans-1,2-Dichloroethylene								<3.34	2				0	GE	µg/L
Gross alpha								1.2E+01	1				1	GP	pCi/L
Lead, total recoverable								12.5	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,520	1				0	GE	µg/L
Nonvolatile beta								3.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.5E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<3.34	2				0	GE	µg/L
Tetrachloroethylene								38.1	2		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<3.34	2				0	GE	µg/L
Trichloroethylene								126	2		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								11.1	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 34TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104905.8 E50536.6	33.340220 °N 81.737550 °W	(91.9)-(101.9) ft msl	383.4 ft msl	4" Steel	S	CBC

SAMPLE DATE 01/12/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		203.1	ft msl
pH		6.0	pH
Sp. conductance		26	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		8	mg/L
Turbidity		3.8	NTU
Volume purged		2.48	well volumes
Sampling code			
Synchronous water level	203.1 (12/20/94)	204.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.5E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								448	1				0	GE	µg/L
Nonvolatile beta								6.5E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								4.30	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								9.38	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 34TB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104891.6 E50537.9	33.340190 °N 81.737520 °W	75.8-65.8 ft msl	383.6 ft msl	4" Steel	S	CBA

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		203.8	ft msl
pH		5.6	pH
Sp. conductance		24	µS/cm
Water temperature		19.3	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.9	NTU
Volume purged		2.89	well volumes
Sampling code			
Synchronous water level	203.7 (12/20/94)	204.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<33.3	1											0	GE	µg/L
Arsenic, total recoverable	<3.33	1											0	GE	µg/L
Barium, total recoverable	3.65	1	J										0	GE	µg/L
Cadmium, total recoverable	<3.33	1											0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<1.67	1											0	GE	µg/L
Chromium, total recoverable	<6.67	1											0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1											0	GE	µg/L
1,1-Dichloroethane	<1.67	1											0	GE	µg/L
1,1-Dichloroethylene	<1.67	1											0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1											0	GE	µg/L
Gross alpha	8.5E-01	1											0	GP	pCi/L
Lead, total recoverable	11.7	1											0	GE	µg/L
Mercury, total recoverable	<0.333	1											0	GE	µg/L
Nickel, total recoverable	<6.67	1											0	GE	µg/L
Nitrate-nitrite as nitrogen	255	1											0	GE	µg/L
Nonvolatile beta	9.3E-01	1	UI										0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	6.0E-01	1											0	GP	pCi/L
Selenium, total recoverable	2.51	1	J										0	GE	µg/L
Silver, total recoverable	<3.33	1											0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate	4,580	1											0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1											0	GE	µg/L
Tetrachloroethylene	<1.67	1											0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.67	1											0	GE	µg/L
Trichloroethylene	<1.67	1											0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	11.8	1											0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 35A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102098.0 E50945.2	33.334680 °N 81.731010 °W	128.8-123.2 ft msl	350.9 ft msl	4" PVC	S	CBC

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		217.0	ft msl
pH		4.9	pH
Sp. conductance		29	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.5	NTU
Volume purged		2.78	well volumes
Sampling code			
Synchronous water level	217.2 (12/20/94)	218.3 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.23	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								825	1				0	GE	µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.66	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 35B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102110.8 E50947.9	33.334720 °N 81.731030 °W	169.3-163.7 ft msl	351.6 ft msl	4" PVC	S	UL

SAMPLE DATE 01/11/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		220.0	ft msl
pH		5.6	pH
Sp. conductance		34	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		7	mg/L
Turbidity		0.4	NTU
Volume purged		4.47	well volumes
Sampling code			
Synchronous water level	220.4 (12/20/94)	221.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.76	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.6E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								185	1				0	GE	µg/L
Nonvolatile beta								6.6E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,070	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								25.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 35D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102122.4 E50949.7	33.334750 °N 81.731050 °W	254.5-233.8 ft msl	351.9 ft msl	4" PVC	S	M(VZ)

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		D	
Synchronous water level	243.4 (12/20/94)	243.5 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 35TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102101.6 E50919.6	33.334650 °N 81.731080 °W	38.2-32.9 ft msl	350.3 ft msl	4" CS	S	CBA

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		200.7	ft msl
pH		5.1	pH
Sp. conductance		19	µS/cm
Water temperature		19.3	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		4.1	NTU
Volume purged		2.93	well volumes
Sampling code			
Synchronous water level	200.6 (12/20/94)	206.5 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								3.20	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								319	1				0	GE	µg/L
Nonvolatile beta								8.7E-01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 36A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100511.3 E49514.9	33.328840 °N 81.731690 °W	100.5-94.9 ft msl	340.6 ft msl	4" PVC	S	MCBC

SAMPLE DATE	10/20/94	02/03/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	210.2	211.9	ft msl
pH	4.1	4.3	pH
Sp. conductance	39	41	µS/cm
Water temperature	19.8	19.7	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	1.3	0.2	NTU
Volume purged	2.12	2.25	well volumes
Sampling code			
Synchronous water level	212.2 (12/20/94)	211.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	63.8	1				2	GE	60.8	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.1	1				0	GE	10.6	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,580	1				0	GE	1,710	1				0	GE	µg/L
Chlorobenzene	<2.00	2				0	GE	<8.34	5				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	7.03	1				0	GE								µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<2.00	2				0	GE	<8.34	5				0	GE	µg/L
1,1-Dichloroethylene	<2.00	2				0	GE	<8.34	5				0	GE	µg/L
trans-1,2-Dichloroethylene	<2.00	2				0	GE	<8.34	5				0	GE	µg/L
Gross alpha								1.7E+00	1				0	GP	pCi/L
Lead, total recoverable	3.77	1	J			0	GE	4.05	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	4.01	1	J	■		0	GE	6.08	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen	328	1				0	GE	400	1				0	GE	µg/L
Nonvolatile beta								2.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,770	1				0	GE	1,790	1				0	GE	µg/L
Sulfate	5,280	1		■		0	GE	6,420	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane	<2.00	2				0	GE	<8.34	5				0	GE	µg/L
Tetrachloroethylene	82.2	2		■		2	GE	76.5	5		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<2.00	2				0	GE	<8.34	5				0	GE	µg/L
Trichloroethylene	1,090	50		■		2	GE	1,600	100		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	13.7	1				0	GE	14.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 36B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100514.9 E49526.3	33.328870 °N 81.731670 °W	163.7-158.1 ft msl	340.8 ft msl	4" PVC	S	LL

SAMPLE DATE 10/25/94 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	214.6	215.4	ft msl
pH	4.8	4.7	pH
Sp. conductance	178	159	µS/cm
Water temperature	19.5	18.2	°C
Alkalinity as CaCO ₃	1	0	mg/L
Turbidity	2.3	0.7	NTU
Volume purged	4.18	3.75	well volumes
Sampling code			
Synchronous water level	213.3 (12/20/94)	215.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	132	1		■		2	GE	123	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	63.6	1				0	GE	66.4	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,100	1				0	GE	2,690	1				0	GE	µg/L
Chlorobenzene	<50.0	50	V			0	GE	<41.8	25				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	7.81	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<50.0	50	V			0	GE	<41.8	25				0	GE	µg/L
1,1-Dichloroethylene	<50.0	50	V			0	GE	<41.8	25				0	GE	µg/L
trans-1,2-Dichloroethylene	<50.0	50	V			0	GE	<41.8	25				0	GE	µg/L
Gross alpha								1.3E+01	1				1	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	18,400	20	J2	■		2	GE	17,600	20		■		2	GE	µg/L
Nonvolatile beta								9.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.6E+00	1		■		0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	7,120	1		■		0	GE	7,320	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,360	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<50.0	50	V			0	GE	<41.8	25				0	GE	µg/L
Tetrachloroethylene	<50.0	50	V			0	GE	<41.8	25				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<50.0	50	V			0	GE	<41.8	25				0	GE	µg/L
Trichloroethylene	1,040	50	V	■		2	GE	1,060	25		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	26.0	1				0	GE	30.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 36C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100518.3 E49537.2	33.328890 °N 81.731640 °W	194.2-188.6 ft msl	340.9 ft msl	4" PVC	S	UL

SAMPLE DATE 10/20/94 02/03/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	214.7	215.8	ft msl
pH	4.5	4.7	pH
Sp. conductance	45	56	µS/cm
Water temperature	18.4	18.7	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	2.0	0.2	NTU
Volume purged	10.2	9.30	well volumes
Sampling code			
Synchronous water level	215.4 (12/20/94)	216.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	42.1	1				1	GE	46.5	1				1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.1	1				0	GE	11.6	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,970	1				0	GE	5,250	1		■		0	GE	µg/L
Chlorobenzene	<5.00	5	V			0	GE	<3.33	2	J1			0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<5.00	5	V			0	GE	<3.33	2	J1			0	GE	µg/L
1,1-Dichloroethylene	<5.00	5	V			0	GE	<3.33	2	J1			0	GE	µg/L
trans-1,2-Dichloroethylene	<5.00	5	V			0	GE	<3.33	2	J1			0	GE	µg/L
Gross alpha								2.6E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	2,610	2		■		0	GE	3,100	4		■		0	GE	µg/L
Nonvolatile beta								1.3E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	4,900	1		■		0	GE	5,890	1		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<5.00	5	V			0	GE	<3.33	2	J1			0	GE	µg/L
Tetrachloroethylene	7.00	5	JV	■		2	GE	2.60	2	J1		1	GE	µg/L	
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<5.00	5	V			0	GE	<3.33	2	J1			0	GE	µg/L
Trichloroethylene	90.3	5	V	■		2	GE	31.6	2	J1	■	2	GE	µg/L	
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	7.98	1				0	GE	10.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 36D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100521.7 E49548.3	33.328920 °N 81.731620 °W	249.5-228.8 ft msl	341.6 ft msl	4" PVC	S	M

SAMPLE DATE 10/21/94 02/03/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	237.9	237.0	ft msl
pH	5.9	6.1	pH
Sp. conductance	40	36	µS/cm
Water temperature	14.3	18.4	°C
Alkalinity as CaCO ₃	8	9	mg/L
Turbidity	268.0	345.0	NTU
Volume purged	1.01	0.746	well volumes
Sampling code	X	X	
Synchronous water level	237.9 (12/20/94)	237.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	28.1	1	J			1	GE	22.2	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.23	1				0	GE	6.93	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,850	1				0	GE	2,520	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	1,000	1				2	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								-2.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	286	10		■		2	GE	242	5			■	2	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	17.2	1		■		0	GE	12.0	1			■	0	GE	µg/L
Nitrate-nitrite as nitrogen	297	1				0	GE	390	1				0	GE	µg/L
Nonvolatile beta								2.9E-02	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,800	1				0	GE	3,140	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	1.50	1	J			0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	3.50	1				1	GE	µg/L
Uranium, total recoverable	<40.0	2				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	270	1				0	GE	90.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 36TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N100507.7 E49503.0	33.328810 °N 81.731710 °W	53.4-48.4 ft msl	340.6 ft msl	4" CS	S	CBA

SAMPLE DATE 10/20/94 02/03/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	195.4	192.9	ft msl
pH	4.9	5.2	pH
Sp. conductance	23	25	µS/cm
Water temperature	19.5	19.0	°C
Alkalinity as CaCO ₃	1	2	mg/L
Turbidity	3.5	2.8	NTU
Volume purged	2.59	2.50	well volumes
Sampling code			
Synchronous water level	195.4 (12/20/94)	196.4 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.46	1				0	GE	5.47	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,750	1				0	GE	1,880	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	5.10	1	J			0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								3.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	3.94	1	J			0	GE	4.37	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
Nonvolatile beta								1.0E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,510	1				0	GE	1,510	1				0	GE	µg/L
Sulfate	2,040	1				0	GE	2,520	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 37A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105295.0 E51439.8	33.342560 °N 81.735930 °W	73.7-68.1 ft msl	383 ft msl	4" PVC	S	CBA

SAMPLE DATE 02/08/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		209.0	ft msl
pH		5.9	pH
Sp. conductance		69	µS/cm
Water temperature		16.6	°C
Alkalinity as CaCO ₃		14	mg/L
Turbidity		1.1	NTU
Volume purged		0.833	well volumes
Sampling code		X	
Synchronous water level	208.2 (12/20/94)	209.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								14.2	1				0	GE	µg/L
Cadmium, total recoverable								11.1	1		■		2	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.8E+00	1				0	GP	pCi/L
Lead, total recoverable								13.0	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								694	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								5,580	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1		■		0	GE	µg/L
Tetrachloroethylene								24.6	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								113	5	J1	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								63.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 37B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105289.5 E51450.0	33.342560 °N 81.735890 °W	142.3-136.7 ft msl	382.7 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		220.2	ft msl
pH		5.7	pH
Sp. conductance		22	µS/cm
Water temperature		20.2	°C
Alkalinity as CaCO ₃		4	mg/L
Turbidity		0.4	NTU
Volume purged		2.74	well volumes
Sampling code			
Synchronous water level	220.1 (12/20/94)	220.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.99	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<3.34	2				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<3.34	2				0	GE	µg/L
1,1-Dichloroethylene								<3.34	2				0	GE	µg/L
trans-1,2-Dichloroethylene								<3.34	2				0	GE	µg/L
Gross alpha								5.7E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								5.07	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								855	1				0	GE	µg/L
Nonvolatile beta								1.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								2.96	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<3.34	2				0	GE	µg/L
Tetrachloroethylene								73.7	2				2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<3.34	2				0	GE	µg/L
Trichloroethylene								37.9	2				2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								25.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 37C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105283.2 E51439.8	33.342530 °N 81.735900 °W	180.8-175.2 ft msl	383 ft msl	4" PVC	S	UL

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		228.9	ft msl
pH		5.4	pH
Sp. conductance		25	µS/cm
Water temperature		20.0	°C
Alkalinity as CaCO ₃		4	mg/L
Turbidity		1.0	NTU
Volume purged		2.98	well volumes
Sampling code			
Synchronous water level	228.9 (12/20/94)	229.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<33.3	1					GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.55	1	J				GE	4.55	1	J			0	GE	µg/L
Cadmium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable															
Cyanide	<8.33	1					GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Gross alpha	6.4E+00	1					GP	6.4E+00	1				0	GP	pCi/L
Lead, total recoverable	<5.00	1					GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1					GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	4.51	1	J				GE	4.51	1	J			0	GE	µg/L
Nitrate-nitrite as nitrogen	680	1					GE	680	1				0	GE	µg/L
Nonvolatile beta	2.1E+00	1					GP	2.1E+00	1				0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting	2.9E+00	1					GP	2.9E+00	1				0	GP	pCi/L
Selenium, total recoverable	2.21	1	J				GE	2.21	1	J			0	GE	µg/L
Silver, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate	<1,670	1					GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	20.9	1					GE	20.9	1				2	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Trichloroethylene	6.37	1					GE	6.37	1				2	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	9.20	1					GE	9.20	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 37D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105271.0 E51440.3	33.342510 °N 81.735880 °W	245.7-225.1 ft msl	382.7 ft msl	4" PVC	B	MGC

SAMPLE DATE 02/07/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		232.6	ft msl
pH		4.7	pH
Sp. conductance		36	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃			mg/L
Turbidity		40.8	NTU
Volume purged		2.04	well volumes
Sampling code			
Synchronous water level	232.4 (12/20/94)	233.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								80.2	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								11.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.9E+00	1				0	GP	pCi/L
Lead, total recoverable								5.41	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,460	2		■		0	GE	µg/L
Nonvolatile beta								2.2E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.8E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								1.20	1	J			0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								9.37	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 37TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105301.3 E51449.8	33.342590 °N 81.735910 °W	35.1-29.8 ft msl	382.3 ft msl	4" CS	S	CBA

SAMPLE DATE 01/19/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		208.2	ft msl
pH		5.8	pH
Sp. conductance		23	µS/cm
Water temperature		18.8	°C
Alkalinity as CaCO ₃		4	mg/L
Turbidity		7.3	NTU
Volume purged		2.44	well volumes
Sampling code			
Synchronous water level	208.0 (12/20/94)	208.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								11.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<83.5	50				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<83.5	50				0	GE	µg/L
1,1-Dichloroethylene								<83.5	50				0	GE	µg/L
trans-1,2-Dichloroethylene								<83.5	50				0	GE	µg/L
Gross alpha								1.1E+00	1				0	GP	pCi/L
Lead, total recoverable								12.9	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								781	1				0	GE	µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,320	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<83.5	50				0	GE	µg/L
Tetrachloroethylene								64.5	50	J	■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<83.5	50				0	GE	µg/L
Trichloroethylene								1,730	50		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								15.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 38B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102360.8 E49746.1	33.333310 °N 81.734680 °W	146.5-141.8 ft msl	359 ft msl	4" PVC	S	LL/CBC

SAMPLE DATE 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		218.4	ft msl
pH		6.1	pH
Sp. conductance		35	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		6	mg/L
Turbidity		0.8	NTU
Volume purged		2.83	well volumes
Sampling code			
Synchronous water level	217.2 (12/20/94)	217.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								22.0	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								13.0	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<83.5	50				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<83.5	50				0	GE	µg/L
1,1-Dichloroethylene								<83.5	50				0	GE	µg/L
trans-1,2-Dichloroethylene								<83.5	50				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,710	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,730	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<83.5	50				0	GE	µg/L
Tetrachloroethylene								511	50			■	2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<83.5	50				0	GE	µg/L
Trichloroethylene								903	50			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 38C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102373.1 E49762.0	33.333360 °N 81.734660 °W	169.0-164.3 ft msl	358.8 ft msl	4" PVC	S	LL

SAMPLE DATE 01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		221.4	ft msl
pH		6.6	pH
Sp. conductance		42	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		10	mg/L
Turbidity		0.6	NTU
Volume purged		3.71	well volumes
Sampling code			
Synchronous water level	219.8 (12/20/94)	221.1 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								31.8	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								30.0	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<167	100				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<167	100				0	GE	µg/L
1,1-Dichloroethylene								<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene								<167	100				0	GE	µg/L
Gross alpha								1.6E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,780	1				0	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,290	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<167	100				0	GE	µg/L
Tetrachloroethylene								3,830	100				2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<167	100				0	GE	µg/L
Trichloroethylene								4,640	100				2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.79	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 38D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102385.6 E49777.8	33.333410 °N 81.734640 °W	240.4-220.9 ft msl	358.5 ft msl	4" PVC	S	M

SAMPLE DATE 01/31/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		237.0	ft msl
pH		6.3	pH
Sp. conductance		114	µS/cm
Water temperature		15.5	°C
Alkalinity as CaCO ₃		34	mg/L
Turbidity		12.2	NTU
Volume purged		0.0944	well volumes
Sampling code		X	
Synchronous water level	233.9 (12/20/94)	234.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								67.4	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								29.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								10.3	1				2	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.5E+00	1				0	GP	pCi/L
Lead, total recoverable								3.21	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,220	2				0	GE	µg/L
Nonvolatile beta								4.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								83.4	50				2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								10.1	1				0	GE	µg/L
Trichloroethylene								83.4	50				2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								94.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 38TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102434.9 E49810.4	33.333580 °N 81.734650 °W	32.0-26.7 ft msl	359.1 ft msl	4" CS	S	CBA

SAMPLE DATE 02/01/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		199.5	ft msl
pH		4.9	pH
Sp. conductance		20	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.0	NTU
Volume purged		2.43	well volumes
Sampling code			
Synchronous water level	198.8 (12/20/94)	199.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.31	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								10.9	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								77.3	1	J			0	GE	µg/L
Nonvolatile beta								9.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,270	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 39A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100837.6 E48367.3	33.327690 °N 81.735350 °W	111.7-106.1 ft msl	341.6 ft msl	4" PVC	S	MCBC

SAMPLE DATE 10/20/94 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	209.2	211.2	ft msl
pH	6.4	6.0	pH
Sp. conductance	83	80	µS/cm
Water temperature	18.4	18.2	°C
Alkalinity as CaCO ₃	18	19	mg/L
Turbidity	0.9	1.1	NTU
Volume purged	0.932	0.972	well volumes
Sampling code	X	X	
Synchronous water level	211.5 (12/20/94)	210.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	70.7	1				2	GE	129	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.3	1				0	GE	10.4	1				0	GE	µg/L
Cadmium, total recoverable	4.92	1				1	GE	4.74	1				1	GE	µg/L
Chloride	1,890	1				0	GE	2,510	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable	3.47	1	J			0	GE	5.21	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	5.74	1	J	■		0	GE	4.66	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen	1,820	2				0	GE	1,550	2				0	GE	µg/L
Nonvolatile beta								2.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	4,580	1				0	GE	4,450	1				0	GE	µg/L
Sulfate	3,770	1		■		0	GE	5,120	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	11.6	1		■		2	GE	3.74	1				1	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	95.3	1				0	GE	96.6	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 39B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100844.6 E48376.9	33.327720 °N 81.735330 °W	149.6-144.0 ft msl	341.8 ft msl	4" PVC	S	LL

SAMPLE DATE 10/19/94 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	211.8	213.9	ft msl
pH	4.4	4.2	pH
Sp. conductance	257	285	µS/cm
Water temperature	18.9	18.6	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.6	0.4	NTU
Volume purged	3.57	2.79	well volumes
Sampling code			
Synchronous water level	214.1 (12/20/94)	213.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	96.9	1				2	GE	98.3	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	45.5	1				0	GE	47.1	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,800	1				0	GE	4,390	1		■		0	GE	µg/L
Chlorobenzene	<5.00	5				0	GE	<8.35	5				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<5.00	5				0	GE	<8.35	5				0	GE	µg/L
1,1-Dichloroethylene	15.0	5		■		2	GE	10.5	5		■		2	GE	µg/L
trans-1,2-Dichloroethylene	<5.00	5				0	GE	<8.35	5				0	GE	µg/L
Gross alpha								6.5E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.467	1				0	GE	0.460	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	38,900	20		■		2	GE	29,600	20		■		2	GE	µg/L
Nonvolatile beta								1.9E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.4E+00	1		■		0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	34,200	2		■		0	GE	36,900	2		■		0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,500	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<5.00	5				0	GE	<8.35	5				0	GE	µg/L
Tetrachloroethylene	171	5		■		2	GE	170	5		■		2	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<5.00	5				0	GE	<8.35	5				0	GE	µg/L
Trichloroethylene	339	5		■		2	GE	347	5		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	3.78	1				0	GE	4.06	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 39C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100852.1 E48386.7	33.327750 °N 81.735320 °W	199.6-194.0 ft msl	341.5 ft msl	4" PVC	S	UL

SAMPLE DATE 10/20/94 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	215.7	216.8	ft msl
pH	4.6	4.3	pH
Sp. conductance	44	47	µS/cm
Water temperature	19.0	18.4	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	1.3	0.5	NTU
Volume purged	4.08	6.62	well volumes
Sampling code			
Synchronous water level	216.9 (12/20/94)	216.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	69.4	1				2	GE	67.6	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.54	1				0	GE	7.70	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,630	1				0	GE	3,320	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								8.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	2,530	2		■		0	GE	2,670	2		■		0	GE	µg/L
Nonvolatile beta								7.0E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,920	1				0	GE	2,980	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,590	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	3.90	1				1	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	4.40	1				1	GE	34.0	1		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 39D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100858.7 E48396.0	33.327780 °N 81.735310 °W	239.7-219.0 ft msl	341.8 ft msl	4" PVC	S	MGC

SAMPLE DATE	10/20/94	01/26/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	232.9	231.8	ft msl
pH	5.2	4.9	pH
Sp. conductance	28	29	µS/cm
Water temperature	20.1	18.7	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	2.0	0.9	NTU
Volume purged	5.04	10.2	well volumes
Sampling code			
Synchronous water level	232.7 (12/20/94)	232.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.32	1	J			0	GE	3.94	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	3,020	1				0	GE	3,500	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	18.6	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								3.4E+00	1				0	GP	pCi/L
Lead, total recoverable	8.22	1				0	GE	6.75	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	781	1				0	GE	633	1				0	GE	µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.6E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,450	1				0	GE	2,370	1				0	GE	µg/L
Sulfate	<1,000	1				0	GE	1,660	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	4.70	1				1	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	40.4	1		■		2	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	2.32	1	J			0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 39TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N100830.6 E48357.7	33.327660 °N 81.735360 °W	49.7-44.4 ft msl	341.8 ft msl	4" CS	S	CBA
SAMPLE DATE	10/20/94		01/26/95			
FIELD DATA						
Parameter	4Q94		1Q95			Unit
Water elevation	193.2		193.4			ft msl
pH	5.0		4.8			pH
Sp. conductance	19		20			µS/cm
Water temperature	18.8		18.9			°C
Alkalinity as CaCO ₃	1		0			mg/L
Turbidity	10.2		7.6			NTU
Volume purged	3.43		3.24			well volumes
Sampling code						
Synchronous water level	193.3 (12/20/94)		194.4 (03/23/95)			ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,900	1				0	GE	2,640	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	4.84	1	J			0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								7.7E-01	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
Nonvolatile beta								9.5E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,390	1				0	GE	1,400	1				0	GE	µg/L
Sulfate	1,090	1	J			0	GE	2,460	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	252	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	2.56	1	J			0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 40A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N97672.8 E48279.4	33.320550 °N 81.729420 °W	116.2-110.6 ft msl	321.2 ft msl	4" PVC	S	MCBC

SAMPLE DATE 10/20/94 02/06/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	203.2	202.5	ft msl
pH	4.5	4.5	pH
Sp. conductance	49	53	µS/cm
Water temperature	19.3	18.8	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	0.8	0.7	NTU
Volume purged	2.73	2.52	well volumes
Sampling code			
Synchronous water level	203.4 (12/20/94)	204.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	74.9	1				2	GE	79.5	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	17.2	1				0	GE	17.9	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	2,000	1				0	GE	2,050	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								2.0E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	4.29	1	J	■		0	GE	4.51	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
Nonvolatile beta								2.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,950	1				0	GE	1,960	1				0	GE	µg/L
Sulfate	10,400	1		■		0	GE	12,400	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	19.6	1				0	GE	19.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 40B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N97685.0 E48281.6	33.320580 °N 81.729440 °W	154.7-149.1 ft msl	321.7 ft msl	4" PVC	S	LL

SAMPLE DATE 10/26/94 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	204.9	205.3	ft msl
pH	4.9	4.7	pH
Sp. conductance	48	44	µS/cm
Water temperature	18.1	18.1	°C
Alkalinity as CaCO ₃	0	1	mg/L
Turbidity	1.1	0.8	NTU
Volume purged	5.08	3.85	well volumes
Sampling code			
Synchronous water level	205.0 (12/20/94)	205.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	26.0	1	J			1	GE	31.0	1	J			1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.7	1				0	GE	11.3	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,740	1				0	GE	2,260	1				0	GE	µg/L
Chlorobenzene	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	9.50	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
1,1-Dichloroethylene	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
trans-1,2-Dichloroethylene	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Gross alpha								2.6E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	4.00	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	18,800	20	J2	■		2	GE	3,600	2		■		0	GE	µg/L
Nonvolatile beta								4.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.9E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	3,510	1				0	GE	3,600	1				0	GE	µg/L
Sulfate	1,040	1	J			0	GE	2,310	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Tetrachloroethylene	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<25.0	25				0	GE	<41.8	25				0	GE	µg/L
Trichloroethylene	1,900	25		■		2	GE	1,680	25		■		2	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	15.9	1				0	GE	17.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 40C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N97697.8 E48283.5	33.320610 °N 81.729460 °W	192.4-186.8 ft msl	322 ft msl	4" PVC	S	UL

SAMPLE DATE 10/20/94 02/06/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	205.0	204.8	ft msl
pH	5.5	5.5	pH
Sp. conductance	57	62	µS/cm
Water temperature	19.5	19.4	°C
Alkalinity as CaCO ₃	3	5	mg/L
Turbidity	0.8	0.8	NTU
Volume purged	2.18	2.12	well volumes
Sampling code			
Synchronous water level	205.0 (12/20/94)	205.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	134	1		■		2	GE	124	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	9.21	1				0	GE	9.51	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,290	1				0	GE	1,690	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	13.9	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								3.6E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	331	1				0	GE	308	1				0	GE	µg/L
Nonvolatile beta								7.6E-02	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								0.0E+00	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	2,180	1				0	GE	2,190	1				0	GE	µg/L
Sulfate	8,450	1				■	GE	10,000	1				■	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	1,070	1				■	GE	1,200	1				■	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	11.0	1				■	GE	9.40	1				■	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	13.4	1				0	GE	14.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 40D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97709.3 E48285.1	33.320640 °N 81.729480 °W	236.8-216.2 ft msl	322.9 ft msl	4" PVC	B	MGC

SAMPLE DATE 02/06/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		227.5	ft msl
pH		5.6	pH
Sp. conductance		34	µS/cm
Water temperature		17.3	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		885.0	NTU
Volume purged		3.10	well volumes
Sampling code	P		
Synchronous water level	228.1 (12/20/94)	227.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	4,990	1		■		2	GE	µg/L
Arsenic, total recoverable	4.35	1				0	GE	µg/L
Barium, total recoverable	82.6	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1				0	GE	µg/L
Chloride	1,890	1				0	GE	µg/L
Chlorobenzene	<1.67	1				0	GE	µg/L
Chromium, total recoverable	9.10	1				0	GE	µg/L
Cobalt, total recoverable								µg/L
Copper, total recoverable								µg/L
Cyanide	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1				0	GE	µg/L
Gross alpha	2.6E+01	1		■		2	GP	pCi/L
Lead, total recoverable	7.63	1	J			0	GE	µg/L
Mercury, total recoverable	0.531	1				0	GE	µg/L
Nickel, total recoverable	21.2	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen	661	1				0	GE	µg/L
Nonvolatile beta	1.3E+01	1				0	GP	pCi/L
PCB 1254								µg/L
Radium, total alpha-emitting	9.5E+00	1		■		0	GP	pCi/L
Selenium, total recoverable	<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,510	1				0	GE	µg/L
Sulfate	4,080	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.67	1				0	GE	µg/L
Total phosphates (as P)	22,800	20		■		0	GE	µg/L
1,1,1-Trichloroethane	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<33.3	1				0	GE	µg/L
Zinc, total recoverable	75.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 40TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97660.4 E48277.2	33.320520 °N 81.729400 °W	29.0-23.7 ft msl	320.9 ft msl	4" CS	S	CBA

SAMPLE DATE 10/20/94 02/06/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	189.8	189.6	ft msl
pH	5.5	5.6	pH
Sp. conductance	27	32	µS/cm
Water temperature	19.2	19.0	°C
Alkalinity as CaCO ₃	4	7	mg/L
Turbidity	3.5	1.8	NTU
Volume purged	1.96	2.51	well volumes
Sampling code			
Synchronous water level	189.8 (12/20/94)	190.9 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.27	1				0	GE	6.26	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride	1,710	1				0	GE	1,750	1				0	GE	µg/L
Chlorobenzene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable	9.47	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Gross alpha								-2.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	7.11	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
Nonvolatile beta								4.5E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable	1,340	1				0	GE	1,380	1				0	GE	µg/L
Sulfate	2,340	1				0	GE	2,910	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)	<50.0	1				0	GE	<83.3	1				0	GE	µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable	<20.0	1				0	GE	<33.3	1				0	GE	µg/L
Zinc, total recoverable	3.64	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 41A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102184.4 E53424.1	33.338920 °N 81.724650 °W	87.9-82.3 ft msl	323.8 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/03/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		217.3	ft msl
pH		5.5	pH
Sp. conductance		30	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		4	mg/L
Turbidity		0.4	NTU
Volume purged		2.60	well volumes
Sampling code			
Synchronous water level	217.8 (12/20/94)	218.6 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.88	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.4E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,220	1				0	GE	µg/L
Nonvolatile beta								2.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.8E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								2.96	1				1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.68	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 41B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102194.5 E53417.8	33.338940 °N 81.724690 °W	114.2-108.6 ft msl	324 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/03/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		217.3	ft msl
pH		5.8	pH
Sp. conductance		26	µS/cm
Water temperature		18.2	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		0.3	NTU
Volume purged		2.60	well volumes
Sampling code			
Synchronous water level	218.0 (12/20/94)	218.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.16	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1	Y			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane								<1.67	1	Y			0	GE	µg/L
1,1-Dichloroethylene								<1.67	1	Y			0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1	Y			0	GE	µg/L
Gross alpha								2.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,120	1	Y			0	GE	µg/L
Nonvolatile beta								8.2E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1	Y			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1	Y			0	GE	µg/L
Tetrachloroethylene								9.05	1	Y	■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1	Y			0	GE	µg/L
Trichloroethylene								3.32	1	Y			1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 41C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102203.9 E53410.6	33.338940 °N 81.724720 °W	152.5-146.9 ft msl	324.6 ft msl	4" PVC	S	LL

SAMPLE DATE 01/03/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		218.0	ft msl
pH		4.9	pH
Sp. conductance		20	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.3	NTU
Volume purged		2.92	well volumes
Sampling code			
Synchronous water level	218.5 (12/20/94)	219.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.34	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1	Y			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane								<1.67	1	Y			0	GE	µg/L
1,1-Dichloroethylene								<1.67	1	Y			0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1	Y			0	GE	µg/L
Gross alpha								1.5E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								243,000	200	Y	■		2	GE	µg/L
Nonvolatile beta								1.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1	Y			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1	Y			0	GE	µg/L
Tetrachloroethylene								<1.67	1	Y			0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1	Y			0	GE	µg/L
Trichloroethylene								<1.67	1	Y			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.40	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 41D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102213.4 E53403.7	33.338950 °N 81.724760 °W	247.8-227.1 ft msl	325 ft msl	4" PVC	S	M

SAMPLE DATE 01/04/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation			ft msl
pH		5.0	pH
Sp. conductance		19	µS/cm
Water temperature		10.5	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		41.3	NTU
Volume purged			well volumes
Sampling code		X	
Synchronous water level	241.0 (12/20/94)	241.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								10.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.2E+00	1				0	GP	pCi/L
Lead, total recoverable								103	1				2	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								7.47	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								390	1				0	GE	µg/L
Nonvolatile beta								2.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.8E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,040	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								48.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 41TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102176.5 E53429.7	33.338920 °N 81.724620 °W	26.7-21.4 ft msl	323.7 ft msl	4" CS	S	CBA

SAMPLE DATE 01/03/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		206.4	ft msl
pH		5.0	pH
Sp. conductance		24	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.7	NTU
Volume purged		2.25	well volumes
Sampling code			
Synchronous water level	207.1 (12/20/94)	207.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.83	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1	Y			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane								<1.67	1	Y			0	GE	µg/L
1,1-Dichloroethylene								<1.67	1	Y			0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1	Y			0	GE	µg/L
Gross alpha								6.6E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								8.35	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,040	2	Y			0	GE	µg/L
Nonvolatile beta								6.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1	Y			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1	Y			0	GE	µg/L
Tetrachloroethylene								<1.67	1	Y			0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1	Y			0	GE	µg/L
Trichloroethylene								<1.67	1	Y			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 42A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104557.9 E51582.3	33.341160 °N 81.734120 °W	129.4-123.8 ft msl	376.5 ft msl	4" PVC	S	MCBC

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	220.1 (12/20/94)	220.7 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 42B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104569.8 E51582.8	33.341190 °N 81.734140 °W	166.3-160.7 ft msl	376.4 ft msl	4" PVC	S	LL

SAMPLE DATE 02/07/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		227.1	ft msl
pH		4.6	pH
Sp. conductance		24	μS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃			mg/L
Turbidity		0.2	NTU
Volume purged		3.53	well volumes
Sampling code			
Synchronous water level	226.5 (12/20/94)	227.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	Unit	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								μg/L	<33.3	1				0	GE	μg/L
Arsenic, total recoverable								μg/L	<3.33	1				0	GE	μg/L
Barium, total recoverable								μg/L	3.65	1	J			0	GE	μg/L
Cadmium, total recoverable								μg/L	<3.33	1				0	GE	μg/L
Chloride								μg/L								
Chlorobenzene								μg/L	<8.34	5				0	GE	μg/L
Chromium, total recoverable								μg/L	<6.67	1				0	GE	μg/L
Cobalt, total recoverable								μg/L								
Copper, total recoverable								μg/L								
Cyanide								μg/L	<8.33	1				0	GE	μg/L
1,1-Dichloroethane								μg/L	<8.34	5				0	GE	μg/L
1,1-Dichloroethylene								μg/L	<8.34	5				0	GE	μg/L
trans-1,2-Dichloroethylene								μg/L	<8.34	5				0	GE	μg/L
Gross alpha								pCi/L	1.7E+00	1				0	GP	pCi/L
Lead, total recoverable								μg/L	<5.00	1				0	GE	μg/L
Mercury, total recoverable								μg/L	0.404	1				0	GE	μg/L
Nickel, total recoverable								μg/L	<6.67	1				0	GE	μg/L
Nitrate-nitrite as nitrogen								μg/L	964	1				0	GE	μg/L
Nonvolatile beta								pCi/L	6.0E-01	1	UI			0	GP	pCi/L
PCB 1254								μg/L								
Radium, total alpha-emitting								pCi/L	1.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								μg/L	<3.33	1				0	GE	μg/L
Silver, total recoverable								μg/L	<3.33	1				0	GE	μg/L
Sodium, total recoverable								μg/L								
Sulfate								μg/L	<1,670	1				0	GE	μg/L
1,1,2,2-Tetrachloroethane								μg/L	<8.34	5				0	GE	μg/L
Tetrachloroethylene								μg/L	<8.34	5				0	GE	μg/L
Total phosphates (as P)								μg/L								
1,1,1-Trichloroethane								μg/L	<8.34	5				0	GE	μg/L
Trichloroethylene								μg/L	38.0	5		■		2	GE	μg/L
Uranium, total recoverable								μg/L								
Zinc, total recoverable								μg/L	<3.33	1				0	GE	μg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 42C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104581.9 E51582.8	33.341220 °N 81.734160 °W	204.3-198.7 ft msl	376.4 ft msl	4" PVC	S	UL

SAMPLE DATE 02/07/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		232.4	ft msl
pH		4.9	pH
Sp. conductance		29	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.2	NTU
Volume purged		3.99	well volumes
Sampling code			
Synchronous water level	232.1 (12/20/94)	232.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								21.4	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.30	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,490	1				0	GE	µg/L
Nonvolatile beta								5.9E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								2.70	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 42D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104595.2 E51582.5	33.341250 °N 81.734190 °W	247.2-226.6 ft msl	376.4 ft msl	4" PVC	B	MGC

SAMPLE DATE 02/07/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		234.0	ft msl
pH		4.5	pH
Sp. conductance		22	µS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃			mg/L
Turbidity		166.0	NTU
Volume purged		3.09	well volumes
Sampling code			
Synchronous water level	233.8 (12/20/94)	234.2 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								352	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								10.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								4.33	1	J			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								5.2E+00	1				0	GP	pCi/L
Lead, total recoverable								9.95	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								5.22	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen								1,140	1				0	GE	µg/L
Nonvolatile beta								2.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.9E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								8.80	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								42.9	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								7.06	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 42TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104545.6 E51581.7	33.341130 °N 81.734100 °W	45.8-40.5 ft msl	376.6 ft msl	4" CS	S	CBA

SAMPLE DATE 02/07/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		207.3	ft msl
pH		5.0	pH
Sp. conductance		20	µS/cm
Water temperature		18.8	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		3.7	NTU
Volume purged		2.34	well volumes
Sampling code			
Synchronous water level	206.7 (12/20/94)	207.5 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1					GE	<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	3.18	1					GE	3.18	1	J			0	GE	µg/L
Cadmium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Chloride							µg/L								µg/L
Chlorobenzene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Chromium, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable							µg/L								µg/L
Copper, total recoverable							µg/L								µg/L
Cyanide	<8.33	1					GE	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1					GE	<1.67	1				0	GE	µg/L
Gross alpha	9.5E-01	1					GP	9.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	8.90	1					GE	8.90	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1					GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1					GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	636	1					GE	636	1				0	GE	µg/L
Nonvolatile beta	6.1E-01	1					GP	6.1E-01	1	UI			0	GP	pCi/L
PCB 1254							µg/L								µg/L
Radium, total alpha-emitting	7.0E-01	1					GP	7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable							µg/L								µg/L
Sulfate	<1,670	1					GE	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Tetrachloroethylene	14.8	1					GE	14.8	1		■	2	GE	µg/L	
Total phosphates (as P)							µg/L								µg/L
1,1,1-Trichloroethane	<1.67	1					GE	<1.67	1				0	GE	µg/L
Trichloroethylene	28.5	1					GE	28.5	1		■	2	GE	µg/L	
Uranium, total recoverable							µg/L								µg/L
Zinc, total recoverable	<3.33	1					GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 43TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107275.8 E49281.8	33.343410 °N 81.745460 °W	40.3-35.0 ft msl	357.5 ft msl	4" CS	S	CBA

SAMPLE DATE 01/30/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		204.4	ft msl
pH		4.9	pH
Sp. conductance		18	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃			mg/L
Turbidity		9.9	NTU
Volume purged		4.79	well volumes
Sampling code			
Synchronous water level	203.6 (12/20/94)	204.5 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								7.78	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								79.2	1	J			0	GE	µg/L
Nonvolatile beta								7.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 44A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103296.5 E51106.9	33.337600 °N 81.732920 °W	134.6-124.6 ft msl	376.9 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/27/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		219.0	ft msl
pH		4.7	pH
Sp. conductance		22	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.2	NTU
Volume purged		3.07	well volumes
Sampling code			
Synchronous water level	218.7 (12/20/94)	219.3 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								90.3	1	VV			2	WA	µg/L
Arsenic, total recoverable								1.50	1	JVVY			0	WA	µg/L
Barium, total recoverable								3.40	1	J			0	WA	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.0E+00	1	J1			0	TM	pCi/L
Lead, total recoverable								2.70	1	JY			0	WA	µg/L
Mercury, total recoverable								0.144	1	JVV			0	WA	µg/L
Nickel, total recoverable								1.00	1	JY			0	WA	µg/L
Nitrate-nitrite as nitrogen								259	1				0	GE	µg/L
Nonvolatile beta								2.6E+00	1				0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	TM	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<1.40	1	V			0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate								2,520	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								1.91	1	J			0	WA	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								5.40	1	JVV			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 44B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103296.2 E51096.4	33.337580 °N 81.732940 °W	184.6-174.6 ft msl	377 ft msl	4" PVC	S	L(UD)

SAMPLE DATE 01/18/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.4	ft msl
pH		5.1	pH
Sp. conductance		31	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.4	NTU
Volume purged		3.27	well volumes
Sampling code			
Synchronous water level	225.6 (12/20/94)	226.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.5E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								80.5	1	J			0	GE	µg/L
Nonvolatile beta								3.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								0.0E+00	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,710	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 44C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103296.3 E51106.6	33.337600 °N 81.732920 °W	239.4-229.4 ft msl	376.8 ft msl	2" PVC	B	MGCL

SAMPLE DATE 01/18/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		235.8	ft msl
pH		5.9	pH
Sp. conductance		102	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		19	mg/L
Turbidity		1000.0	NTU
Volume purged		1.90	well volumes
Sampling code			
Synchronous water level	235.8 (12/20/94)	236.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								7,190	1		■		2	GE	µg/L
Arsenic, total recoverable								2.35	1	J			0	GE	µg/L
Barium, total recoverable								124	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								8.44	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.3E+01	1		■		2	GP	pCi/L
Lead, total recoverable								41.0	1				1	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								17.1	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen								374	1				0	GE	µg/L
Nonvolatile beta								1.4E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.1E+01	1		■		2	GP	pCi/L
Selenium, total recoverable								2.13	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								10,800	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								174	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 45A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103998.1 E50554.7	33.338250 °N 81.735730 °W	139.2-129.2 ft msl	380.8 ft msl	4" PVC	S	LL

SAMPLE DATE 01/20/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		217.5	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged		0.0518	well volumes
Sampling code		P	
Synchronous water level	217.2 (12/20/94)	217.9 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 45B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103987.9 E50555.3	33.338230 °N 81.735710 °W	190.0-180.0 ft msl	380.9 ft msl	4" PVC	S	UL

SAMPLE DATE 01/04/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		227.0	ft msl
pH		5.4	pH
Sp. conductance		36	µS/cm
Water temperature		17.6	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.3	NTU
Volume purged		3.89	well volumes
Sampling code			
Synchronous water level	226.9 (12/20/94)	227.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								148	1				0	GE	µg/L
Nonvolatile beta								5.0E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								5,840	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 45C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103997.7 E50554.7	33.338250 °N 81.735730 °W	243.7-233.4 ft msl	380.8 ft msl	2" PVC	B	MGC

SAMPLE DATE 01/04/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		D	
Synchronous water level			ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 46A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103098.6 E50548.3	33.336250 °N 81.734000 °W	130.0-120.0 ft msl	372.6 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/19/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		217.0	ft msl
pH		8.5	pH
Sp. conductance		145	μS/cm
Water temperature		17.9	°C
Alkalinity as CaCO ₃		44	mg/L
Turbidity		1.0	NTU
Volume purged		0.707	well volumes
Sampling code		X	
Synchronous water level	217.0 (12/20/94)	217.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								94.6	1				2	GE	μg/L
Arsenic, total recoverable								<3.33	1				0	GE	μg/L
Barium, total recoverable								17.0	1				0	GE	μg/L
Cadmium, total recoverable								<3.33	1				0	GE	μg/L
Chloride															μg/L
Chlorobenzene								<1.67	1				0	GE	μg/L
Chromium, total recoverable								<6.67	1				0	GE	μg/L
Cobalt, total recoverable															μg/L
Copper, total recoverable															μg/L
Cyanide								<8.33	1				0	GE	μg/L
1,1-Dichloroethane								<1.67	1				0	GE	μg/L
1,1-Dichloroethylene								<1.67	1				0	GE	μg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	μg/L
Gross alpha								1.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	μg/L
Mercury, total recoverable								<0.333	1				0	GE	μg/L
Nickel, total recoverable								<6.67	1				0	GE	μg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	μg/L
Nonvolatile beta								4.0E+00	1				0	GP	pCi/L
PCB 1254															μg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	μg/L
Silver, total recoverable								<3.33	1				0	GE	μg/L
Sodium, total recoverable															μg/L
Sulfate								10,700	1			■	0	GE	μg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	μg/L
Tetrachloroethylene								<1.67	1				0	GE	μg/L
Total phosphates (as P)															μg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	μg/L
Trichloroethylene								<1.67	1				0	GE	μg/L
Uranium, total recoverable															μg/L
Zinc, total recoverable								<3.33	1				0	GE	μg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 46B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103102.4 E50557.5	33.336270 °N 81.733980 °W	189.8-179.8 ft msl	373.6 ft msl	4" PVC	S	UL

SAMPLE DATE 01/18/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		228.0	ft msl
pH		5.3	pH
Sp. conductance		43	µS/cm
Water temperature		19.5	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.4	NTU
Volume purged		3.29	well volumes
Sampling code			
Synchronous water level			ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								<5.00	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								363	1				0	GE	µg/L
Nonvolatile beta								2.6E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								4,700	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 46C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103098.5 E50548.7	33.336250 °N 81.734000 °W	247.0-237.0 ft msl	372.6 ft msl	2" PVC	B	MGC

SAMPLE DATE 01/18/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		238.3	ft msl
pH		5.2	pH
Sp. conductance		33	µS/cm
Water temperature		19.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		378.0	NTU
Volume purged		4.58	well volumes
Sampling code			
Synchronous water level	239.3 (12/20/94)	240.7 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								3,370	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								11.6	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								5.49	1	J			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.4E+01	1				1	GP	pCi/L
Lead, total recoverable								8.80	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								4.22	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen								2,580	2		■		0	GE	µg/L
Nonvolatile beta								8.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.9E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								1.00	1	J			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								27.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 47B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106978.5 E52207.2	33.347530 °N 81.737180 °W	171.5-165.9 ft msl	368.7 ft msl	4" PVC	S	LL

SAMPLE DATE 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.7	ft msl
pH		6.1	pH
Sp. conductance		62	µS/cm
Water temperature		17.6	°C
Alkalinity as CaCO ₃		9	mg/L
Turbidity		0.5	NTU
Volume purged		3.87	well volumes
Sampling code			
Synchronous water level	225.7 (12/20/94)	226.3 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								61.8	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								47.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.6E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3.030	2		■		0	GE	µg/L
Nonvolatile beta								4.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.9E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,570	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								2.91	1				1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								2,030	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 47BB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106999.7 E52234.4	33.347630 °N 81.737150 °W	120.3-115.6 ft msl	368.8 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/03/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.4	ft msl
pH		6.8	pH
Sp. conductance		39	µS/cm
Water temperature		18.1	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		2.1	NTU
Volume purged		3.43	well volumes
Sampling code			
Synchronous water level	220.5 (12/20/94)	221.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								28.5	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								25.9	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.7E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1.170	1				0	GE	µg/L
Nonvolatile beta								1.0E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								33.3	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 47C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106969.2 E52195.5	33.347490 °N 81.737190 °W	202.6-197.0 ft msl	369 ft msl	4" PVC	S	UL

SAMPLE DATE 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		232.9	ft msl
pH		5.7	pH
Sp. conductance		46	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		7	mg/L
Turbidity		0.5	NTU
Volume purged		6.16	well volumes
Sampling code			
Synchronous water level	233.0 (12/20/94)	233.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								26.6	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<167	100				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<167	100				0	GE	µg/L
1,1-Dichloroethylene								<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene								<167	100				0	GE	µg/L
Gross alpha								2.0E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,620	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,600	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<167	100				0	GE	µg/L
Tetrachloroethylene								<167	100				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<167	100				0	GE	µg/L
Trichloroethylene								10,600	250		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.70	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 47D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N106960.1 E52184.0	33.347460 °N 81.737210 °W	246.1-226.5 ft msl	368.8 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/03/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		234.0	ft msl
pH		5.4	pH
Sp. conductance		75	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.7	NTU
Volume purged		12.6	well volumes
Sampling code			
Synchronous water level	233.9 (12/20/94)	234.3 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								28.0	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								28.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.0E+01	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.372	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								4,440	4		■		0	GE	µg/L
Nonvolatile beta								3.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.4E+00	1		■		0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								1.00	1	J			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.12	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 47TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106987.7 E52219.0	33.347570 °N 81.737170 °W	55.1-50.1 ft msl	368.7 ft msl	4" CS	S	CBA

SAMPLE DATE 01/26/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		217.4	ft msl
pH		5.5	pH
Sp. conductance		22	µS/cm
Water temperature		18.3	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		20.7	NTU
Volume purged		2.37	well volumes
Sampling code			
Synchronous water level	217.4 (12/20/94)	218.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								19.5	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<16.7	10				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene								<16.7	10				0	GE	µg/L
Gross alpha								2.4E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,060	1				0	GE	µg/L
Nonvolatile beta								2.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,520	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L
Tetrachloroethylene								<16.7	10				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<16.7	10				0	GE	µg/L
Trichloroethylene								740	10		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								14.6	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 48A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107936.6 E54099.8	33.352740 °N 81.734060 °W	129.4-124.7 ft msl	361.6 ft msl	4" PVC	S	CBC

SAMPLE DATE 01/09/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		223.2	ft msl
pH		6.3	pH
Sp. conductance		26	µS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃		4	mg/L
Turbidity		1.2	NTU
Volume purged		2.66	well volumes
Sampling code			
Synchronous water level	223.3 (12/20/94)	223.7 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								13.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								3.06	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,460	1				0	GE	µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								25.6	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 48B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107945.0 E54112.2	33.352780 °N 81.734040 °W	158.3-153.6 ft msl	361.4 ft msl	4" PVC	S	CBC

SAMPLE DATE 01/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.5	ft msl
pH		6.6	pH
Sp. conductance		35	µS/cm
Water temperature		18.3	°C
Alkalinity as CaCO ₃		7	mg/L
Turbidity		2.0	NTU
Volume purged		3.37	well volumes
Sampling code			
Synchronous water level	224.6 (12/20/94)	225.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	Unit	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								µg/L	47.9	1				1	GE	µg/L
Arsenic, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Barium, total recoverable								µg/L	11.5	1				0	GE	µg/L
Cadmium, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Chloride								µg/L								
Chlorobenzene								µg/L	<16.7	10				0	GE	µg/L
Chromium, total recoverable								µg/L	<6.67	1				0	GE	µg/L
Cobalt, total recoverable								µg/L								
Copper, total recoverable								µg/L								
Cyanide								µg/L	<8.33	1				0	GE	µg/L
1,1-Dichloroethane								µg/L	<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								µg/L	<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene								µg/L	<16.7	10				0	GE	µg/L
Gross alpha								pCi/L	2.0E+00	1				0	GP	pCi/L
Lead, total recoverable								µg/L	<5.00	1				0	GE	µg/L
Mercury, total recoverable								µg/L	<0.333	1				0	GE	µg/L
Nickel, total recoverable								µg/L	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								µg/L	1,310	1				0	GE	µg/L
Nonvolatile beta								pCi/L	1.7E+00	1				0	GP	pCi/L
PCB 1254								µg/L								
Radium, total alpha-emitting								pCi/L	1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Silver, total recoverable								µg/L	<3.33	1				0	GE	µg/L
Sodium, total recoverable								µg/L								
Sulfate								µg/L	<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								µg/L	<16.7	10				0	GE	µg/L
Tetrachloroethylene								µg/L	<16.7	10				0	GE	µg/L
Total phosphates (as P)								µg/L								
1,1,1-Trichloroethane								µg/L	<16.7	10				0	GE	µg/L
Trichloroethylene								µg/L	88.0	10			■	2	GE	µg/L
Uranium, total recoverable								µg/L								
Zinc, total recoverable								µg/L	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 48C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107917.5 E54077.0	33.352660 °N 81.734080 °W	180.2-175.4 ft msl	362.3 ft msl	4" PVC	S	LL

SAMPLE DATE 01/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.0	ft msl
pH		7.2	pH
Sp. conductance		55	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		14	mg/L
Turbidity		11.2	NTU
Volume purged		4.68	well volumes
Sampling code			
Synchronous water level	225.1 (12/20/94)	225.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								69.8	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								15.7	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.8E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,340	1				0	GE	µg/L
Nonvolatile beta								3.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,360	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								6.00	1			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 48D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107914.4 E54056.3	33.352620 °N 81.734130 °W	243.5-222.0 ft msl	362.6 ft msl	4" PVC	S	UL

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		233.0	ft msl
pH		9.2	pH
Sp. conductance		206	µS/cm
Water temperature		7.8	°C
Alkalinity as CaCO ₃		52	mg/L
Turbidity		21.4	NTU
Volume purged		0.554	well volumes
Sampling code		X	
Synchronous water level	233.1 (12/20/94)	233.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								474	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.82	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								5.81	1	J			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.7E+00	1				1	GP	pCi/L
Lead, total recoverable								19.2	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								67.8	1	J			0	GE	µg/L
Nonvolatile beta								7.2E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,840	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								7.01	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 48TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107925.8 E54089.2	33.352700 °N 81.734070 °W	107.8-102.5 ft msl	361.9 ft msl	4" CS	S	CBA

SAMPLE DATE 01/09/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		223.1	ft msl
pH		6.4	pH
Sp. conductance		35	µS/cm
Water temperature		19.3	°C
Alkalinity as CaCO ₃		9	mg/L
Turbidity		3.6	NTU
Volume purged		2.66	well volumes
Sampling code			
Synchronous water level	223.1 (12/20/94)	223.5 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								22.1	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.18	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,500	1				0	GE	µg/L
Nonvolatile beta								1.3E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 49A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N99759.0 E45864.6	33.321220 °N 81.739840 °W	76.7-72.0 ft msl	334.7 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		198.3	ft msl
pH		5.3	pH
Sp. conductance		23	µS/cm
Water temperature		18.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.7	NTU
Volume purged		2.80	well volumes
Sampling code			
Synchronous water level	198.3 (12/20/94)	198.8 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								22.2	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.97	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride													0	GE	µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable													0	GE	µg/L
Copper, total recoverable													0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								419	1				0	GE	µg/L
Nonvolatile beta								2.2E+00	1				0	GP	pCi/L
PCB 1254													0	GP	µg/L
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable													0	GE	µg/L
Sulfate								2,780	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)													0	GE	µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								1.79	1				0	GE	µg/L
Uranium, total recoverable													0	GE	µg/L
Zinc, total recoverable								5.46	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 49B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N99737.8 E45868.2	33.321180 °N 81.739790 °W	116.3-110.7 ft msl	334.1 ft msl	4" PVC	S	LL

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		204.2	ft msl
pH		7.5	pH
Sp. conductance		66	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		19	mg/L
Turbidity		0.2	NTU
Volume purged		2.45	well volumes
Sampling code			
Synchronous water level	204.2 (12/20/94)	204.4 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								56.7	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								23.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.5E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3,110	4		■		0	GE	µg/L
Nonvolatile beta								2.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								20.7	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								149	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.59	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 49D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N99724.9 E45856.4	33.321130 °N 81.739790 °W	236.4-216.7 ft msl	334.3 ft msl	4" PVC	S	M

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		229.7	ft msl
pH		5.9	pH
Sp. conductance		28	µS/cm
Water temperature		15.2	°C
Alkalinity as CaCO ₃		5	mg/L
Turbidity		2.4	NTU
Volume purged		1.77	well volumes
Sampling code		X	
Synchronous water level	229.7 (12/20/94)	229.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								100	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								10.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.1E+00	1				0	GP	pCi/L
Lead, total recoverable								5.40	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								729	1				0	GE	µg/L
Nonvolatile beta								1.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								19.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 50B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N96433.0 E51053.5	33.322340 °N 81.719710 °W	155.2-149.6 ft msl	223.7 ft msl	4" PVC	S	UL

SAMPLE DATE 01/06/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		202.2	ft msl
pH		5.4	pH
Sp. conductance		34	µS/cm
Water temperature		17.4	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.4	NTU
Volume purged		4.81	well volumes
Sampling code			
Synchronous water level	201.9 (12/20/94)	202.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								22.9	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.16	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.2E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,470	1				0	GE	µg/L
Nonvolatile beta								2.4E+00	1	J			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								9.90	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								15.3	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 50D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N96416.7 E51044.1	33.322290 °N 81.719700 °W	210.9-190.8 ft msl	223.2 ft msl	4" PVC	S	M

SAMPLE DATE 01/06/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		202.4	ft msl
pH		5.8	pH
Sp. conductance		90	µS/cm
Water temperature		17.9	°C
Alkalinity as CaCO ₃		22	mg/L
Turbidity		0.5	NTU
Volume purged		14.2	well volumes
Sampling code			
Synchronous water level	202.2 (12/20/94)	203.1 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								23.6	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								85.1	1				0	GE	µg/L
Nonvolatile beta								2.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.6E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								5,480	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 51B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N96992.7 E52818.0	33.326460 °N 81.716150 °W	160.0-154.4 ft msl	263.2 ft msl	4" PVC	S	L(UD)

SAMPLE DATE 01/06/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		204.9	ft msl
pH		5.8	pH
Sp. conductance		30	µS/cm
Water temperature		17.4	°C
Alkalinity as CaCO ₃		6	mg/L
Turbidity		0.4	NTU
Volume purged		3.95	well volumes
Sampling code			
Synchronous water level	204.6 (12/20/94)	205.6 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								16.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.0E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								234	1				0	GE	µg/L
Nonvolatile beta								3.0E+00	1	J			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 51D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97015.7 E52816.2	33.326500 °N 81.716200 °W	218.5-198.8 ft msl	262.2 ft msl	4" PVC	S	GC

SAMPLE DATE 01/06/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		210.6	ft msl
pH		4.6	pH
Sp. conductance		24	µS/cm
Water temperature		16.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		34.0	NTU
Volume purged		0.906	well volumes
Sampling code		X	
Synchronous water level	210.3 (12/20/94)	211.2 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								203	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.60	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								254	1				0	GE	µg/L
Nonvolatile beta								1.7E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 52B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103077.7 E53418.4	33.340890 °N 81.726400 °W	171.4-165.8 ft msl	321.7 ft msl	4" PVC	S	LL

SAMPLE DATE 02/01/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		219.2	ft msl
pH		5.5	pH
Sp. conductance		46	µS/cm
Water temperature		18.2	°C
Alkalinity as CaCO ₃		8	mg/L
Turbidity		2.3	NTU
Volume purged		4.60	well volumes
Sampling code			
Synchronous water level	220.1 (12/20/94)	220.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								47.4	1				1	GE	µg/L
Arsenic, total recoverable								1.80	1	JY			0	WA	µg/L
Barium, total recoverable								9.20	1	Y			0	WA	µg/L
Cadmium, total recoverable								0.790	1	JY			0	WA	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								4.40	1	JY			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.8E+00	1	J			0	GP	pCi/L
Lead, total recoverable								3.00	1	JY			0	WA	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								4.60	1	JVVY	■		0	WA	µg/L
Nitrate-nitrite as nitrogen								792	1				0	GE	µg/L
Nonvolatile beta								2.2E+00	1	J1			0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	TM	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								0.170	1	JY			0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate								300	1	JY			0	WA	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								7.31	1	Y	■		2	WA	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								5.50	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								5.40	1	JY			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 52D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103062.7 E53416.8	33.340850 °N 81.726380 °W	250.8-231.1 ft msl	321.6 ft msl	4" PVC	S	M

SAMPLE DATE

01/20/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		237.5	ft msl
pH		4.7	pH
Sp. conductance		22	µS/cm
Water temperature		15.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.2	NTU
Volume purged		0.948	well volumes
Sampling code		I	
Synchronous water level	238.6 (12/20/94)	239.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.07	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable								4.51	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								123	1				0	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,330	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								12.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 53B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106443.6 E54574.3	33.350220 °N 81.729910 °W	152.3-147.6 ft msl	344.3 ft msl	4" PVC	S	LL

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		223.1	ft msl
pH		5.1	pH
Sp. conductance		17	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.4	NTU
Volume purged		3.01	well volumes
Sampling code			
Synchronous water level	223.0 (12/20/94)	223.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.20	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.6E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								159	1				0	GE	µg/L
Nonvolatile beta								6.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								5.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 53C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106456.2 E54540.5	33.350190 °N 81.730020 °W	192.6-187.8 ft msl	345.2 ft msl	4" PVC	S	UL

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.0	ft msl
pH		5.0	pH
Sp. conductance		23	µS/cm
Water temperature		18.2	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.7	NTU
Volume purged		5.10	well volumes
Sampling code			
Synchronous water level	223.9 (12/20/94)	224.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.37	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.0E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								660	1				0	GE	µg/L
Nonvolatile beta								2.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								1.64	1	J			0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								2.87	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.98	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 53D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N106448.2 E54553.1	33.350190 °N 81.729970 °W	244.9-223.6 ft msl	344.8 ft msl	4" PVC	S	MGC

SAMPLE DATE 01/12/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		234.0	ft msl
pH		4.7	pH
Sp. conductance		24	µS/cm
Water temperature		18.3	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.7	NTU
Volume purged		7.48	well volumes
Sampling code			
Synchronous water level	233.9 (12/20/94)	234.3 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.44	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.6E-01	1				0	GP	pCi/L
Lead, total recoverable								16.9	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								798	1				0	GE	µg/L
Nonvolatile beta								7.3E-01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 54B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108446.8 E52970.5	33.352030 °N 81.738030 °W	136.4-130.8 ft msl	373.4 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/04/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		222.9	ft msl
pH		6.0	pH
Sp. conductance		20	µS/cm
Water temperature		18.5	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		0.7	NTU
Volume purged		2.48	well volumes
Sampling code			
Synchronous water level	222.9 (12/20/94)	223.3 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								20.4	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.78	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.7E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								896	1				0	GE	µg/L
Nonvolatile beta								1.8E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 54C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108447.4 E52955.7	33.352000 °N 81.738070 °W	175.6-170.0 ft msl	373.4 ft msl	4" PVC	S	LL

SAMPLE DATE 01/05/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		231.1	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	227.2 (12/20/94)	227.6 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 54D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108461.5 E52984.5	33.352080 °N 81.738020 °W	244.8-223.8 ft msl	373.6 ft msl	4" PVC	S	GCL

SAMPLE DATE 01/04/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		233.7	ft msl
pH		5.3	pH
Sp. conductance		18	µS/cm
Water temperature		17.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.9	NTU
Volume purged		16.0	well volumes
Sampling code			
Synchronous water level	233.7 (12/20/94)	233.7 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.53	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.3E+00	1				0	GP	pCi/L
Lead, total recoverable								5.28	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,490	1				0	GE	µg/L
Nonvolatile beta								2.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 54TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108446.3 E52985.8	33.352050 °N 81.737990 °W	80.9-75.3 ft msl	373.5 ft msl	4" CS	S	CBA

SAMPLE DATE 01/04/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		220.3	ft msl
pH		8.2	pH
Sp. conductance		36	µS/cm
Water temperature		18.8	°C
Alkalinity as CaCO ₃		8	mg/L
Turbidity		4.1	NTU
Volume purged		3.44	well volumes
Sampling code			
Synchronous water level	220.3 (12/20/94)	220.7 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								27.3	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.18	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								858	1				0	GE	µg/L
Nonvolatile beta								7.2E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								28.5	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 55B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N108342.4 E52006.2	33.350220 °N 81.740370 °W	152.7-148.0 ft msl	368.7 ft msl	4" PVC	S	CBC

SAMPLE DATE 01/04/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		222.7	ft msl
pH		4.2	pH
Sp. conductance		57	µS/cm
Water temperature		18.3	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.3	NTU
Volume purged		2.90	well volumes
Sampling code			
Synchronous water level	222.6 (12/20/94)	223.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								363	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.24	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.7E+00	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								15.1	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	µg/L
Nonvolatile beta								5.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.9E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								9,840	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.95	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 55C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N108324.6 E52029.7	33.350220 °N 81.740270 °W	189.3-184.6 ft msl	369.4 ft msl	4" PVC	S	LL

SAMPLE DATE 01/04/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		229.9	ft msl
pH		5.5	pH
Sp. conductance		23	µS/cm
Water temperature		17.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.4	NTU
Volume purged		5.96	well volumes
Sampling code			
Synchronous water level	229.8 (12/20/94)	230.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.77	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,320	1				0	GE	µg/L
Nonvolatile beta								6.3E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								5.53	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 55D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108391.4 E52032.5	33.350370 °N 81.740390 °W	245.9-224.7 ft msl	367.7 ft msl	4" PVC	S	GCL

SAMPLE DATE 01/04/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		233.7	ft msl
pH		5.1	pH
Sp. conductance		17	µS/cm
Water temperature		17.7	°C
Alkalinity as CaCO ₃		10	mg/L
Turbidity		2.2	NTU
Volume purged		23.7	well volumes
Sampling code			
Synchronous water level	233.6 (12/20/94)	233.7 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.94	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.2E+00	1				0	GP	pCi/L
Lead, total recoverable								8.60	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1.610	1				0	GE	µg/L
Nonvolatile beta								3.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.8E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.31	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 55HC

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108338.7 E52020.1	33.350240 °N 81.740320 °W	218.8-214.1 ft msl	368.7 ft msl	4" PVC	S	UL

SAMPLE DATE 01/27/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		233.6	ft msl
pH		12.5	pH
Sp. conductance		807	µS/cm
Water temperature		15.2	°C
Alkalinity as CaCO ₃		245	mg/L
Turbidity		5.1	NTU
Volume purged		0.704	well volumes
Sampling code		X	
Synchronous water level	233.3 (12/20/94)	233.4 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								629	10		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								655	10				0	GE	µg/L
Cadmium, total recoverable								<33.0	10				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<66.7	10				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.6E+00	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<66.7	10				0	GE	µg/L
Nitrate-nitrite as nitrogen								624	1				0	GE	µg/L
Nonvolatile beta								5.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<33.0	10				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								3,090	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<33.0	10				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 55TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108322.8 E52014.7	33.350190 °N 81.740300 °W	91.6-86.2 ft msl	368.7 ft msl	4" CS	S	CBA

SAMPLE DATE 01/06/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		215.0	ft msl
pH		5.7	pH
Sp. conductance		20	µS/cm
Water temperature		18.9	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		1.3	NTU
Volume purged		2.66	well volumes
Sampling code			
Synchronous water level	214.9 (12/20/94)	215.4 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1						<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Barium, total recoverable	3.79	1						3.79	1	J			0	GE	µg/L
Cadmium, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<1.67	1						<1.67	1				0	GE	µg/L
Chromium, total recoverable	<6.67	1						<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1						<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.67	1						<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.67	1						<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1						<1.67	1				0	GE	µg/L
Gross alpha	1.4E+00	1						1.4E+00	1	UI			0	GP	pCi/L
Lead, total recoverable	<5.00	1						<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1						<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1						<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	419	1						419	1				0	GE	µg/L
Nonvolatile beta	2.2E+00	1						2.2E+00	1	J			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	1.0E-01	1						1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Silver, total recoverable	<3.33	1						<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate	1,740	1						1,740	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1						<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.67	1						<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.67	1						<1.67	1				0	GE	µg/L
Trichloroethylene	<1.67	1						<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	5.08	1						5.08	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 56D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108463.5 E44207.9	33.337750 °N 81.761140 °W	232.4-211.1 ft msl	279.5 ft msl	4" PVC	S	M

SAMPLE DATE 01/05/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		220.6	ft msl
pH		5.4	pH
Sp. conductance		17	µS/cm
Water temperature		16.4	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		4.1	NTU
Volume purged		9.99	well volumes
Sampling code			
Synchronous water level	220.7 (12/20/94)	222.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								34.1	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.85	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								5.3E+00	1				0	GP	pCi/L
Lead, total recoverable								4.60	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								399	1				0	GE	µg/L
Nonvolatile beta								3.2E+00	1	J			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.5E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1.670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 61C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106091.1 E55406.6	33.350800 °N 81.727030 °W	179.7-174.1 ft msl	317.3 ft msl	4" PVC	S	UL

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.4	ft msl
pH		5.0	pH
Sp. conductance		23	µS/cm
Water temperature		17.6	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.4	NTU
Volume purged		3.36	well volumes
Sampling code			
Synchronous water level	224.4 (12/20/94)	224.9 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.62	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.4E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.239	1	J			0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								534	1				0	GE	µg/L
Nonvolatile beta								1.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								2.05	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 61D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106094.6 E55390.6	33.350780 °N 81.727080 °W	234.2-214.3 ft msl	317.8 ft msl	4" PVC	S	GCL

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		226.3	ft msl
pH		5.2	pH
Sp. conductance		25	µS/cm
Water temperature		18.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		29.4	NTU
Volume purged		1.40	well volumes
Sampling code		X	
Synchronous water level	226.3 (12/20/94)	227.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								299	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								8.20	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.4E+00	1				0	GP	pCi/L
Lead, total recoverable								17.6	1				0	GE	µg/L
Mercury, total recoverable								0.208	1	J			0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								512	1				0	GE	µg/L
Nonvolatile beta								2.2E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable								2.56	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1.670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								40.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 65D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101915.5 E49413.7	33.331780 °N 81.734690 °W	243.9-224.4 ft msl	349.2 ft msl	4" PVC	S	M

SAMPLE DATE 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		234.5	ft msl
pH		4.3	pH
Sp. conductance		28	µS/cm
Water temperature		16.8	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		6.2	NTU
Volume purged		0.151	well volumes
Sampling code		X	
Synchronous water level	233.7 (12/20/94)	234.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								65.3	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.97	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.0E+00	1				0	GP	pCi/L
Lead, total recoverable								17.9	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								882	1				0	GE	µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,610	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								67.0	1				2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								8.49	1				0	GE	µg/L
Trichloroethylene								26.4	1				2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								110	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 66B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N105842.0 E51064.6	33.343160 °N 81.737980 °W	143.9-139.2 ft msl	383.4 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		220.1	ft msl
pH		11.0	pH
Sp. conductance		107	µS/cm
Water temperature		20.3	°C
Alkalinity as CaCO ₃		44	mg/L
Turbidity		0.6	NTU
Volume purged		2.88	well volumes
Sampling code			
Synchronous water level	220.0 (12/20/94)	220.6 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								145	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								31.0	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,150	1				0	GE	µg/L
Nonvolatile beta								1.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								3.54	1				1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								12.4	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 66C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105842.1 E51053.5	33.343140 °N 81.738010 °W	170.9-166.2 ft msl	383.4 ft msl	4" PVC	S	LL

SAMPLE DATE 01/11/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		229.1	ft msl
pH		5.7	pH
Sp. conductance		25	µS/cm
Water temperature		20.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.7	NTU
Volume purged		3.25	well volumes
Sampling code			
Synchronous water level	229.2 (12/20/94)	229.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.45	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.6E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,870	2				0	GE	µg/L
Nonvolatile beta								3.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.2E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								12.2	1				2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								294	5				2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								6.54	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 66TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N105842.6 E51096.7	33.343210 °N 81.737900 °W	35.5-30.8 ft msl	382.7 ft msl	4" PVC	S	CBA

SAMPLE DATE 01/11/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		207.2	ft msl
pH		5.9	pH
Sp. conductance		18	µS/cm
Water temperature		19.1	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.2	NTU
Volume purged		2.71	well volumes
Sampling code			
Synchronous water level	207.2 (12/20/94)	208.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.37	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.5E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								673	1				0	GE	µg/L
Nonvolatile beta								1.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,240	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								5.32	1			■	2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								3.62	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.57	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 67B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106842.0 E51989.6	33.346880 °N 81.737490 °W	134.9-130.1 ft msl	365.1 ft msl	4" PVC	S	MCBC

SAMPLE DATE 02/07/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		220.4	ft msl
pH		9.3	pH
Sp. conductance		80	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		27	mg/L
Turbidity		0.2	NTU
Volume purged		4.17	well volumes
Sampling code			
Synchronous water level	219.8 (12/20/94)	220.3 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								32.2	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								16.7	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.0E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,050	1				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								36.1	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 67C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106819.8 E51988.6	33.346830 °N 81.737450 °W	174.9-170.1 ft msl	364.8 ft msl	4" PVC	S	LL

SAMPLE DATE 02/07/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		228.2	ft msl
pH		5.7	pH
Sp. conductance		44	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		6	mg/L
Turbidity		0.4	NTU
Volume purged		3.33	well volumes
Sampling code			
Synchronous water level	227.1 (12/20/94)	227.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								13.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															
Copper, total recoverable															
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.5E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.298	1	J			0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,820	2				0	GE	µg/L
Nonvolatile beta								5.3E+00	1				0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								4.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								1.60	1	J			0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								50.4	1		■		2	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 67D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>									
N106830.7 E51971.5	33.346820 °N 81.737510 °W	241.0-221.5 ft msl	365 ft msl	4" PVC	S	MGC									
SAMPLE DATE		10/27/94		01/30/95											
FIELD DATA															
<u>Parameter</u>	<u>4Q94</u>				<u>1Q95</u>	<u>Unit</u>									
Water elevation	233.4				233.5	ft msl									
pH	5.6				6.0	pH									
Sp. conductance	50				44	µS/cm									
Water temperature	19.8				19.0	°C									
Alkalinity as CaCO ₃	9				9	mg/L									
Turbidity	0.9				0.4	NTU									
Volume purged	4.23				4.85	well volumes									
Sampling code															
Synchronous water level	233.3 (12/20/94)				233.7 (03/22/95)	ft msl									
ANALYTICAL DATA															
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								31.0	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride													0	GE	µg/L
Chlorobenzene	<200	200			0		GE	<83.5	50				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable													0	GE	µg/L
Copper, total recoverable													0	GE	µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<200	200			0		GE	<83.5	50				0	GE	µg/L
1,1-Dichloroethylene	<200	200			0		GE	<83.5	50				0	GE	µg/L
trans-1,2-Dichloroethylene	<200	200			0		GE	<83.5	50				0	GE	µg/L
Gross alpha								1.8E+00	1				0	GP	pCi/L
Lead, total recoverable								8.23	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,590	1				0	GE	µg/L
Nonvolatile beta								1.3E+00	1	UI			0	GP	pCi/L
PCB 1254													0	GP	µg/L
Radium, total alpha-emitting								2.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable													0	GE	µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<200	200			0		GE	<83.5	50				0	GE	µg/L
Tetrachloroethylene	<200	200			0		GE	<83.5	50				0	GE	µg/L
Total phosphates (as P)													0	GE	µg/L
1,1,1-Trichloroethane	<200	200			0		GE	<83.5	50				0	GE	µg/L
Trichloroethylene	3,880	200		■	2		GE	2,810	50		■		2	GE	µg/L
Uranium, total recoverable													0	GE	µg/L
Zinc, total recoverable								39.6	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 68B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106744.9 E52308.5	33.347180 °N 81.736460 °W	133.0-128.3 ft msl	356.9 ft msl	4" PVC	S	MCBC

SAMPLE DATE 02/07/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		219.8	ft msl
pH		4.8	pH
Sp. conductance		26	µS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.2	NTU
Volume purged		3.36	well volumes
Sampling code			
Synchronous water level	220.3 (12/20/94)	220.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								56.3	1	JVVY			2	WA	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.80	1	JY			0	WA	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.8E+00	1				0	TM	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								0.860	1	JY			0	WA	µg/L
Nitrate-nitrite as nitrogen								1,670	1				0	GE	µg/L
Nonvolatile beta								2.9E+00	1				0	TM	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.7E+00	1				0	TM	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<1.40	1	Y			0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate								354	1	JY			0	WA	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								12.4	1	Y	■		2	WA	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								113	1	Y	■		2	WA	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.20	1	JVVY			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 68C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106730.5 E52304.9	33.347150 °N 81.736440 °W	171.7-167.0 ft msl	356.7 ft msl	4" PVC	S	LL

SAMPLE DATE 01/30/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.5	ft msl
pH		5.1	pH
Sp. conductance		27	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.9	NTU
Volume purged		3.23	well volumes
Sampling code			
Synchronous water level	225.3 (12/20/94)	225.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit	
Aluminum, total recoverable								<33.3	1				0	GE	µg/L	
Arsenic, total recoverable								<3.33	1				0	GE	µg/L	
Barium, total recoverable								6.35	1				0	GE	µg/L	
Cadmium, total recoverable								<3.33	1				0	GE	µg/L	
Chloride															µg/L	
Chlorobenzene								<16.7	10				0	GE	µg/L	
Chromium, total recoverable								<6.67	1				0	GE	µg/L	
Cobalt, total recoverable															µg/L	
Copper, total recoverable															µg/L	
Cyanide								<8.33	1				0	GE	µg/L	
1,1-Dichloroethane								<16.7	10				0	GE	µg/L	
1,1-Dichloroethylene								<16.7	10				0	GE	µg/L	
trans-1,2-Dichloroethylene								<16.7	10				0	GE	µg/L	
Gross alpha								4.1E+00	1				0	GP	pCi/L	
Lead, total recoverable								<5.00	1				0	GE	µg/L	
Mercury, total recoverable								<0.333	1				0	GE	µg/L	
Nickel, total recoverable								<6.67	1				0	GE	µg/L	
Nitrate-nitrite as nitrogen								1,610	1				0	GE	µg/L	
Nonvolatile beta								3.4E+00	1				0	GP	pCi/L	
PCB 1254															µg/L	
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L	
Selenium, total recoverable								<3.33	1				0	GE	µg/L	
Silver, total recoverable								<3.33	1				0	GE	µg/L	
Sodium, total recoverable															µg/L	
Sulfate								<1,670	1				0	GE	µg/L	
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L	
Tetrachloroethylene								23.8	10				■	2	GE	µg/L
Total phosphates (as P)															µg/L	
1,1,1-Trichloroethane								<16.7	10				0	GE	µg/L	
Trichloroethylene								1,100	25				■	2	GE	µg/L
Uranium, total recoverable															µg/L	
Zinc, total recoverable								<3.33	1				0	GE	µg/L	

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 68D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106741.4 E52293.6	33.347150 °N 81.736490 °W	239.9-220.4 ft msl	357 ft msl	4" PVC	S	MGC

SAMPLE DATE 10/27/94 01/30/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	234.3	233.2	ft msl
pH	5.2	5.4	pH
Sp. conductance	38	35	µS/cm
Water temperature	18.7	18.5	°C
Alkalinity as CaCO ₃	2	1	mg/L
Turbidity	0.7	0.6	NTU
Volume purged	10.0	8.10	well volumes
Sampling code			
Synchronous water level	234.2 (12/20/94)	234.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								10.2	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<25.0	25				0	GE	<83.5	50				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<25.0	25				0	GE	<83.5	50				0	GE	µg/L
1,1-Dichloroethylene	<25.0	25				0	GE	<83.5	50				0	GE	µg/L
trans-1,2-Dichloroethylene	<25.0	25				0	GE	<83.5	50				0	GE	µg/L
Gross alpha								1.2E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,300	1				0	GE	µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<25.0	25				0	GE	<83.5	50				0	GE	µg/L
Tetrachloroethylene	<25.0	25				0	GE	<83.5	50				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<25.0	25				0	GE	<83.5	50				0	GE	µg/L
Trichloroethylene	3,120	100				2	GE	2,190	50				2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.41	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 69B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107776.1 E52432.9	33.349670 °N 81.738140 °W	144.5-139.8 ft msl	381.5 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/09/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		221.7	ft msl
pH		6.1	pH
Sp. conductance		26	µS/cm
Water temperature		18.8	°C
Alkalinity as CaCO ₃		4	mg/L
Turbidity		0.8	NTU
Volume purged		2.98	well volumes
Sampling code			
Synchronous water level	221.7 (12/20/94)	222.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.09	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.5E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								492	1				0	GE	µg/L
Nonvolatile beta								2.5E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,050	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 69C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107780.1 E52447.5	33.349700 °N 81.738110 °W	175.7-171.0 ft msl	381.6 ft msl	4" PVC	S	LL

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		228.0	ft msl
pH		6.4	pH
Sp. conductance		47	µS/cm
Water temperature		14.9	°C
Alkalinity as CaCO ₃		5	mg/L
Turbidity		2.7	NTU
Volume purged		0.937	well volumes
Sampling code		X	
Synchronous water level	227.9 (12/20/94)	228.3 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								28.5	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								14.5	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<8.35	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<8.35	5				0	GE	µg/L
1,1-Dichloroethylene								<8.35	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.35	5				0	GE	µg/L
Gross alpha								5.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,570	2		■		0	GE	µg/L
Nonvolatile beta								2.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.35	5				0	GE	µg/L
Tetrachloroethylene								<8.35	5				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<8.35	5				0	GE	µg/L
Trichloroethylene								95.5	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								11.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 69D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107784.3 E52462.0	33.349730 °N 81.738080 °W	239.8-220.3 ft msl	382 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		233.8	ft msl
pH		4.6	pH
Sp. conductance		23	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		3.9	NTU
Volume purged		6.20	well volumes
Sampling code			
Synchronous water level	233.8 (12/20/94)	234.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								64.4	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								6.57	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+01	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,780	1				0	GE	µg/L
Nonvolatile beta								4.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.4E+00	1			■	0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.48	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 69TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107772.5 E52418.4	33.349630 °N 81.738170 °W	80.3-74.6 ft msl	381.4 ft msl	4" PVC	S	CBA

SAMPLE DATE 01/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		216.1	ft msl
pH		6.0	pH
Sp. conductance		23	µS/cm
Water temperature		19.2	°C
Alkalinity as CaCO ₃		4	mg/L
Turbidity		28.1	NTU
Volume purged		3.57	well volumes
Sampling code			
Synchronous water level	216.0 (12/20/94)	216.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.60	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								922	1				0	GE	µg/L
Nonvolatile beta								9.9E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.41	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 70C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101785.2 E45012.0	33.324300 °N 81.746020 °W	178.8-174.1 ft msl	361.8 ft msl	4" PVC	S	UL

SAMPLE DATE 01/17/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		218.5	ft msl
pH		5.6	pH
Sp. conductance		206	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		5	mg/L
Turbidity		0.4	NTU
Volume purged		3.43	well volumes
Sampling code			
Synchronous water level	218.5 (12/20/94)	218.6 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								45.7	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<16.7	10				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								85.0	10		■		2	GE	µg/L
trans-1,2-Dichloroethylene								<10.0	10				0	GE	µg/L
Gross alpha								5.3E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.463	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								15,900	40		■		2	GE	µg/L
Nonvolatile beta								4.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								2.02	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,270	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L
Tetrachloroethylene								217	10		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								25.0	10				0	GE	µg/L
Trichloroethylene								220	10		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.33	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 70D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101781.8 E44997.3	33.324270 °N 81.746060 °W	228.3-208.2 ft msl	362.2 ft msl	4" PVC	S	M

SAMPLE DATE 01/17/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		221.4	ft msl
pH		4.9	pH
Sp. conductance		44	µS/cm
Water temperature		17.0	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		19.1	NTU
Volume purged		0.463	well volumes
Sampling code		X	
Synchronous water level	222.0 (12/20/94)	222.1 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								94.7	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.53	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								1.90	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.4E+00	1				1	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2,130	1				0	GE	µg/L
Nonvolatile beta								8.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.7E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,320	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								7.40	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								8.09	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 71B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103801.6 E44054.7	33.327200 °N 81.752470 °W	135.9-131.1 ft msl	344.7 ft msl	4" PVC	S	L(UD)

SAMPLE DATE 01/13/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		217.8	ft msl
pH		11.4	pH
Sp. conductance		457	µS/cm
Water temperature		20.3	°C
Alkalinity as CaCO ₃		190	mg/L
Turbidity		251.0	NTU
Volume purged		1.00	well volumes
Sampling code		X	
Synchronous water level	217.7 (12/20/94)	217.9 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	1,020	1		■		2	GE	µg/L
Arsenic, total recoverable	4.86	1				0	GE	µg/L
Barium, total recoverable	86.1	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1				0	GE	µg/L
Chloride								µg/L
Chlorobenzene	<1.67	1				0	GE	µg/L
Chromium, total recoverable	5.58	1	J			0	GE	µg/L
Cobalt, total recoverable								µg/L
Copper, total recoverable								µg/L
Cyanide	<8.33	1				0	GE	µg/L
1,1-Dichloroethane	<1.67	1				0	GE	µg/L
1,1-Dichloroethylene	<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1				0	GE	µg/L
Gross alpha	8.7E+00	1				1	GP	pCi/L
Lead, total recoverable	11.0	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	215	1				0	GE	µg/L
Nonvolatile beta	7.8E+00	1				0	GP	pCi/L
PCB 1254								µg/L
Radium, total alpha-emitting	2.4E+00	1				0	GP	pCi/L
Selenium, total recoverable	6.38	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	µg/L
Sodium, total recoverable								µg/L
Sulfate	2,170	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.67	1				0	GE	µg/L
Total phosphates (as P)								µg/L
1,1,1-Trichloroethane	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.67	1				0	GE	µg/L
Uranium, total recoverable								µg/L
Zinc, total recoverable	47.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 72B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N96387.6 E48350.3	33.317820 °N 81.726740 °W	156.7-152.0 ft msl	328.2 ft msl	4" PVC	S	LL

SAMPLE DATE 01/18/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		200.2	ft msl
pH		6.6	pH
Sp. conductance		47	µS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃		7	mg/L
Turbidity		0.5	NTU
Volume purged		3.16	well volumes
Sampling code			
Synchronous water level	200.0 (12/20/94)	200.8 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								53.4	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								16.9	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.7E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								329	1				0	GE	µg/L
Nonvolatile beta								4.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,100	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.37	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 73B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N99270.3 E45694.0	33.319860 °N 81.739340 °W	135.5-130.8 ft msl	339.6 ft msl	4" PVC	S	LL

SAMPLE DATE 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		202.7	ft msl
pH		4.6	pH
Sp. conductance		32	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		1.0	NTU
Volume purged		3.05	well volumes
Sampling code			
Synchronous water level	202.6 (12/20/94)	203.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								59.0	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.57	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.9E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,260	1				0	GE	µg/L
Nonvolatile beta								1.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								3,830	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								3.30	1				1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								44.4	1			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.03	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 74B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N99197.4 E50443.2	33.327450 °N 81.726690 °W	147.5-142.8 ft msl	314.5 ft msl	4" PVC	S	LL/CBC

SAMPLE DATE 01/25/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		211.6	ft msl
pH		6.9	pH
Sp. conductance		38	µS/cm
Water temperature		17.7	°C
Alkalinity as CaCO ₃		11	mg/L
Turbidity		0.6	NTU
Volume purged		3.06	well volumes
Sampling code			
Synchronous water level	211.2 (12/20/94)	212.1 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								22.6	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								35.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<16.7	10				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<16.7	10				0	GE	µg/L
1,1-Dichloroethylene								<16.7	10				0	GE	µg/L
trans-1,2-Dichloroethylene								<16.7	10				0	GE	µg/L
Gross alpha								4.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								705	1				0	GE	µg/L
Nonvolatile beta								9.2E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								2,460	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<16.7	10				0	GE	µg/L
Tetrachloroethylene								<16.7	10				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<16.7	10				0	GE	µg/L
Trichloroethylene								729	10		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 74C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N99191.1 E50457.1	33.327460 °N 81.726640 °W	177.8-173.1 ft msl	315 ft msl	4" PVC	S	UL

SAMPLE DATE 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		210.6	ft msl
pH		10.7	pH
Sp. conductance		403	µS/cm
Water temperature		16.9	°C
Alkalinity as CaCO ₃		123	mg/L
Turbidity		5.7	NTU
Volume purged		0.854	well volumes
Sampling code		X	
Synchronous water level	211.2 (12/20/94)	212.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								161	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								38.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	µg/L
Nonvolatile beta								8.2E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								10,800	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								48.2	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								6.89	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 74D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N99185.3 E50469.7	33.327470 °N 81.726600 °W	237.1-217.1 ft msl	315.1 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		231.5	ft msl
pH		5.7	pH
Sp. conductance		67	µS/cm
Water temperature		16.6	°C
Alkalinity as CaCO ₃		20	mg/L
Turbidity		6.3	NTU
Volume purged		0.845	well volumes
Sampling code		X	
Synchronous water level	232.8 (12/20/94)	231.3 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								74.7	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								10.5	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								6.67	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								909	1				0	GE	µg/L
Nonvolatile beta								3.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,950	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								3.31	1				1	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								2.39	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								52.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 75B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N98937.4 E48875.5	33.324320 °N 81.730310 °W	161.7-156.9 ft msl	326.7 ft msl	4" PVC	S	LL

SAMPLE DATE 01/20/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		210.9	ft msl
pH		6.2	pH
Sp. conductance		61	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		11	mg/L
Turbidity		7.4	NTU
Volume purged		3.10	well volumes
Sampling code			
Synchronous water level	210.5 (12/20/94)	211.5 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								44.0	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								23.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<8.35	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<8.35	5				0	GE	µg/L
1,1-Dichloroethylene								<8.35	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.35	5				0	GE	µg/L
Gross alpha								1.5E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3.420	4		■		0	GE	µg/L
Nonvolatile beta								2.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								3,000	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.35	5				0	GE	µg/L
Tetrachloroethylene								<8.35	5				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<8.35	5				0	GE	µg/L
Trichloroethylene								1,110	50		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.04	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 75C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N98942.3 E48859.7	33.324300 °N 81.730360 °W	193.5-188.8 ft msl	327.5 ft msl	4" PVC	S	UL

SAMPLE DATE 01/19/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		209.1	ft msl
pH		5.1	pH
Sp. conductance		84	µS/cm
Water temperature		16.9	°C
Alkalinity as CaCO ₃		8	mg/L
Turbidity		6.4	NTU
Volume purged		0.527	well volumes
Sampling code		X	
Synchronous water level	210.2 (12/20/94)	210.9 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								27.8	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								17.9	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.7E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								7.95	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	µg/L
Nonvolatile beta								3.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								14,000	1			■	0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								12.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 76C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103061.6 E45344.0	33.327670 °N 81.747630 °W	186.0-181.3 ft msl	352.4 ft msl	4" PVC	S	UL

SAMPLE DATE 01/19/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		221.7	ft msl
pH		6.4	pH
Sp. conductance		52	µS/cm
Water temperature		18.4	°C
Alkalinity as CaCO ₃		16	mg/L
Turbidity		6.3	NTU
Volume purged		3.36	well volumes
Sampling code			
Synchronous water level	221.6 (12/20/94)	221.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								131	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								13.9	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<418	250				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<418	250				0	GE	µg/L
1,1-Dichloroethylene								<418	250				0	GE	µg/L
trans-1,2-Dichloroethylene								<418	250				0	GE	µg/L
Gross alpha								2.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,600	1				0	GE	µg/L
Nonvolatile beta								5.1E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,760	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<418	250				0	GE	µg/L
Tetrachloroethylene								<418	250				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<418	250				0	GE	µg/L
Trichloroethylene								12,200	250		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								10.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 77B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>		
N107065.8 E54217.4	33.351010 °N 81.732060 °W	145.1-140.4 ft msl	357.2 ft msl	4" PVC	S	MCBC		
SAMPLE DATE			01/12/95					
FIELD DATA								
<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>			<u>Unit</u>			
Water elevation		222.6				ft msl		
pH		6.9				pH		
Sp. conductance		50				µS/cm		
Water temperature		18.3				°C		
Alkalinity as CaCO ₃		9				mg/L		
Turbidity		0.9				NTU		
Volume purged		4.86				well volumes		
Sampling code								
Synchronous water level	222.6 (12/20/94)	223.2 (03/22/95)				ft msl		
ANALYTICAL DATA								
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								µg/L
Arsenic, total recoverable								µg/L
Barium, total recoverable								µg/L
Cadmium, total recoverable								µg/L
Chloride								µg/L
Chlorobenzene								µg/L
Chromium, total recoverable								µg/L
Cobalt, total recoverable								µg/L
Copper, total recoverable								µg/L
Cyanide								µg/L
1,1-Dichloroethane								µg/L
1,1-Dichloroethylene								µg/L
trans-1,2-Dichloroethylene								µg/L
Gross alpha								pCi/L
Lead, total recoverable								µg/L
Mercury, total recoverable								µg/L
Nickel, total recoverable								µg/L
Nitrate-nitrite as nitrogen								µg/L
Nonvolatile beta								pCi/L
PCB 1254								µg/L
Radium, total alpha-emitting								pCi/L
Selenium, total recoverable								µg/L
Silver, total recoverable								µg/L
Sodium, total recoverable								µg/L
Sulfate								µg/L
1,1,2,2-Tetrachloroethane								µg/L
Tetrachloroethylene								µg/L
Total phosphates (as P)								µg/L
1,1,1-Trichloroethane								µg/L
Trichloroethylene								µg/L
Uranium, total recoverable								µg/L
Zinc, total recoverable								µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 77C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107078.3 E54225.9	33.351050 °N 81.732060 °W	173.2-168.5 ft msl	357.2 ft msl	4" PVC	S	LL

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		224.7	ft msl
pH		6.0	pH
Sp. conductance		41	µS/cm
Water temperature		18.1	°C
Alkalinity as CaCO ₃		8	mg/L
Turbidity		2.4	NTU
Volume purged		5.00	well volumes
Sampling code			
Synchronous water level	224.6 (12/20/94)	225.2 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								35.5	1				1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.94	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<8.35	5				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<8.35	5				0	GE	µg/L
1,1-Dichloroethylene								<8.35	5				0	GE	µg/L
trans-1,2-Dichloroethylene								<8.35	5				0	GE	µg/L
Gross alpha								1.7E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,340	1				0	GE	µg/L
Nonvolatile beta								2.0E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								5.62	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<8.35	5				0	GE	µg/L
Tetrachloroethylene								<8.35	5				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<8.35	5				0	GE	µg/L
Trichloroethylene								106	5		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 77D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107090.7 E54233.4	33.351090 °N 81.732060 °W	236.2-216.2 ft msl	357.4 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/12/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		234.7	ft msl
pH		11.4	pH
Sp. conductance		758	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		185	mg/L
Turbidity		30.9	NTU
Volume purged		0.822	well volumes
Sampling code		X	
Synchronous water level	234.4 (12/20/94)	234.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								2,040	1		■		2	GE	µg/L
Arsenic, total recoverable								4.24	1				0	GE	µg/L
Barium, total recoverable								52.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								4.94	1	J			0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.9E+00	1				0	GP	pCi/L
Lead, total recoverable								3.92	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								211	1				0	GE	µg/L
Nonvolatile beta								2.3E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								8.30	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								3,640	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.03	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 77TA

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107053.8 E54208.9	33.350970 °N 81.732060 °W	82.9-77.6 ft msl	356.9 ft msl	4" CS	S	CBA

SAMPLE DATE 01/12/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		222.3	ft msl
pH		6.7	pH
Sp. conductance		48	µS/cm
Water temperature		19.5	°C
Alkalinity as CaCO ₃		15	mg/L
Turbidity		24.5	NTU
Volume purged		2.15	well volumes
Sampling code			
Synchronous water level	222.4 (12/20/94)	222.8 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								60.4	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								12.1	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.4E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								484	1				0	GE	µg/L
Nonvolatile beta								3.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								4.29	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								190	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 79B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N99296.9 E47300.2	33.322540 °N 81.735160 °W	140.8-136.1 ft msl	347.9 ft msl	4" PVC	S	LL

SAMPLE DATE 01/18/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		209.1	ft msl
pH		12.0	pH
Sp. conductance		2,650	µS/cm
Water temperature		16.7	°C
Alkalinity as CaCO ₃		631	mg/L
Turbidity		9.6	NTU
Volume purged		0.981	well volumes
Sampling code		X	
Synchronous water level	208.9 (12/20/94)	209.1 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								2,860	10		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								507	10				0	GE	µg/L
Cadmium, total recoverable								<33.0	10				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<66.7	10				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.4E+01	1				1	GP	pCi/L
Lead, total recoverable								10.9	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<66.7	10				0	GE	µg/L
Nitrate-nitrite as nitrogen								614	1				0	GE	µg/L
Nonvolatile beta								1.0E+02	1		■		2	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.3E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<33.3	10				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								9.81	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								20.1	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<33.0	10				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 79C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N99290.2 E47286.8	33.322500 °N 81.735180 °W	199.6-194.9 ft msl	347.8 ft msl	4" PVC	S	UL

SAMPLE DATE 01/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		211.0	ft msl
pH		6.9	pH
Sp. conductance		97	µS/cm
Water temperature		18.6	°C
Alkalinity as CaCO ₃		14	mg/L
Turbidity		4.8	NTU
Volume purged		15.9	well volumes
Sampling code			
Synchronous water level	210.9 (12/20/94)	211.3 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								169	1		■		2	GE	µg/L
Arsenic, total recoverable								2.78	1	J			0	GE	µg/L
Barium, total recoverable								10.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.1E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3,690	4		■		0	GE	µg/L
Nonvolatile beta								1.4E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.5E+00	1				0	GP	pCi/L
Selenium, total recoverable								2.16	1	J			0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,960	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								31.4	1		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								54.2	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.30	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 81B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103762.7 E55230.4	33.345360 °N 81.722960 °W	146.1-141.4 ft msl	267 ft msl	4" PVC	S	LL

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		220.7	ft msl
pH		6.1	pH
Sp. conductance		25	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		6	mg/L
Turbidity		0.6	NTU
Volume purged		3.13	well volumes
Sampling code			
Synchronous water level	220.8 (12/20/94)	221.4 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable	<33.3	1											0	GE	µg/L
Arsenic, total recoverable	<3.33	1											0	GE	µg/L
Barium, total recoverable	26.0	1											0	GE	µg/L
Cadmium, total recoverable	<3.33	1											0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<1.67	1											0	GE	µg/L
Chromium, total recoverable	<6.67	1											0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1											0	GE	µg/L
1,1-Dichloroethane	<1.67	1											0	GE	µg/L
1,1-Dichloroethylene	<1.67	1											0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1											0	GE	µg/L
Gross alpha	8.6E-01	1											0	GP	pCi/L
Lead, total recoverable	<5.00	1											0	GE	µg/L
Mercury, total recoverable	4.18	1											2	GE	µg/L
Nickel, total recoverable	<6.67	1											0	GE	µg/L
Nitrate-nitrite as nitrogen	240	1											0	GE	µg/L
Nonvolatile beta	1.2E+00	1											0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting	4.0E-01	1											0	GP	pCi/L
Selenium, total recoverable	<3.33	1											0	GE	µg/L
Silver, total recoverable	<3.33	1											0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate	<1,670	1											0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1											0	GE	µg/L
Tetrachloroethylene	<1.67	1											0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.67	1											0	GE	µg/L
Trichloroethylene	<1.67	1											0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<3.33	1											0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 82A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107529.5 E51978.4	33.348380 °N 81.738860 °W	126.1-121.4 ft msl	374.3 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/27/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		222.5	ft msl
pH		12.0	pH
Sp. conductance		666	µS/cm
Water temperature		16.3	°C
Alkalinity as CaCO ₃		190	mg/L
Turbidity		4.0	NTU
Volume purged		0.844	well volumes
Sampling code		X	
Synchronous water level	223.2 (12/20/94)	221.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								893	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								161	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<33.3	20				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<33.3	20				0	GE	µg/L
1,1-Dichloroethylene								<33.3	20				0	GE	µg/L
trans-1,2-Dichloroethylene								<33.3	20				0	GE	µg/L
Gross alpha								2.0E+00	1				0	GP	pCi/L
Lead, total recoverable								9.09	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								102	1				0	GE	µg/L
Nonvolatile beta								6.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.6E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								26,800	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<33.3	20				0	GE	µg/L
Tetrachloroethylene								<33.3	20				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<33.3	20				0	GE	µg/L
Trichloroethylene								94.6	20		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								5.26	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 82B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107533.4 E51993.3	33.348410 °N 81.738820 °W	148.2-143.5 ft msl	374.2 ft msl	4" PVC	S	LL/CBC

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		221.1	ft msl
pH		4.2	pH
Sp. conductance		36	µS/cm
Water temperature		18.8	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.2	NTU
Volume purged		2.95	well volumes
Sampling code			
Synchronous water level	221.1 (12/20/94)	221.5 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								105	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								7.37	1				0	GE	µg/L
Cadmium, total recoverable								2.85	1	J			1	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.9E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								95.6	1				0	GE	µg/L
Nonvolatile beta								6.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.1E+01	1		■		1	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								6,340	1		■		0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								12.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 82C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107521.9 E51949.4	33.348310 °N 81.738920 °W	177.7-173.0 ft msl	373.9 ft msl	4" PVC	S	LL

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		228.6	ft msl
pH		5.9	pH
Sp. conductance		28	µS/cm
Water temperature		18.8	°C
Alkalinity as CaCO ₃		2	mg/L
Turbidity		0.7	NTU
Volume purged		3.24	well volumes
Sampling code			
Synchronous water level	228.6 (12/20/94)	229.0 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								26.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.1E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,450	1				0	GE	µg/L
Nonvolatile beta								6.0E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								2.42	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

☛ = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 82D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107518.1 E51934.6	33.348280 °N 81.738950 °W	236.9-216.8 ft msl	373.6 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/11/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		233.5	ft msl
pH		6.1	pH
Sp. conductance		25	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		0.7	NTU
Volume purged		4.85	well volumes
Sampling code			
Synchronous water level	233.5 (12/20/94)	233.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								5.32	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.9E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.331	1	J			0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,390	1				0	GE	µg/L
Nonvolatile beta								2.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.7E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								12.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 82TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107525.7 E51964.2	33.348350 °N 81.738890 °W	93.8-88.4 ft msl	373.7 ft msl	4" CS	S	CBA

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		215.3	ft msl
pH		5.6	pH
Sp. conductance		23	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		4	mg/L
Turbidity		20.0	NTU
Volume purged		3.14	well volumes
Sampling code			
Synchronous water level	215.2 (12/20/94)	215.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.80	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.7E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								475	1				0	GE	µg/L
Nonvolatile beta								1.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,940	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								45.0	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								7.07	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 83B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N108426.7 E52421.4	33.351090 °N 81.739440 °W	146.3-141.6 ft msl	371.8 ft msl	4" PVC	S	MCBC

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		222.5	ft msl
pH		6.2	pH
Sp. conductance		19	µS/cm
Water temperature		18.5	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		0.7	NTU
Volume purged		3.34	well volumes
Sampling code			
Synchronous water level	222.5 (12/20/94)	223.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<33.3	1					GE						0	GE	µg/L
Arsenic, total recoverable	<3.33	1					GE						0	GE	µg/L
Barium, total recoverable	8.24	1					GE						0	GE	µg/L
Cadmium, total recoverable	<3.33	1					GE						0	GE	µg/L
Chloride							µg/L								
Chlorobenzene	<1.67	1					GE						0	GE	µg/L
Chromium, total recoverable	<6.67	1					µg/L						0	GE	µg/L
Cobalt, total recoverable							µg/L								
Copper, total recoverable							µg/L								
Cyanide	<8.33	1	J1				GE						0	GE	µg/L
1,1-Dichloroethane	<1.67	1					GE						0	GE	µg/L
1,1-Dichloroethylene	<1.67	1					GE						0	GE	µg/L
trans-1,2-Dichloroethylene	<1.67	1					GE						0	GE	µg/L
Gross alpha	3.3E+00	1					GP						0	GP	pCi/L
Lead, total recoverable	<5.00	1					GE						0	GE	µg/L
Mercury, total recoverable	<0.333	1					GE						0	GE	µg/L
Nickel, total recoverable	<6.67	1					GE						0	GE	µg/L
Nitrate-nitrite as nitrogen	396	1					GE						0	GE	µg/L
Nonvolatile beta	3.9E+00	1					GP						0	GP	pCi/L
PCB 1254							µg/L								
Radium, total alpha-emitting	5.7E+00	1					GP						0	GP	pCi/L
Selenium, total recoverable	<3.33	1					GE						0	GE	µg/L
Silver, total recoverable	<3.33	1					GE						0	GE	µg/L
Sodium, total recoverable							µg/L								
Sulfate	1,240	1	J				GE						0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1.67	1					GE						0	GE	µg/L
Tetrachloroethylene	<1.67	1					GE						0	GE	µg/L
Total phosphates (as P)							µg/L								
1,1,1-Trichloroethane	<1.67	1					GE						0	GE	µg/L
Trichloroethylene	<1.67	1					GE						0	GE	µg/L
Uranium, total recoverable							µg/L								
Zinc, total recoverable	2.10	1	J				GE						0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 83C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N108405.3 E52384.7	33.350980 °N 81.739490 °W	182.8-178.0 ft msl	372 ft msl	4" PVC	S	LL

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		228.7	ft msl
pH		10.4	pH
Sp. conductance		63	µS/cm
Water temperature		18.2	°C
Alkalinity as CaCO ₃		23	mg/L
Turbidity		0.7	NTU
Volume purged		4.60	well volumes
Sampling code			
Synchronous water level	228.8 (12/20/94)	225.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								131	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								13.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.9E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,510	1				0	GE	µg/L
Nonvolatile beta								1.0E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								8.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 83D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N108418.4 E52391.2	33.351020 °N 81.739500 °W	236.1-216.7 ft msl	371.6 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/11/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		233.7	ft msl
pH		7.3	pH
Sp. conductance		263	µS/cm
Water temperature		8.0	°C
Alkalinity as CaCO ₃		44	mg/L
Turbidity		3.4	NTU
Volume purged		0.897	well volumes
Sampling code		X	
Synchronous water level	233.8 (12/20/94)	233.9 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								119	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								10.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.3E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								589	1				0	GE	µg/L
Nonvolatile beta								4.7E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,140	1	J			0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								11.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 83TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N108416.3 E52410.9	33.351050 °N 81.739440 °W	75.7-70.2 ft msl	371.7 ft msl	4" PVC	S	CBA

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		216.4	ft msl
pH		6.1	pH
Sp. conductance		16	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		0.3	NTU
Volume purged		2.43	well volumes
Sampling code			
Synchronous water level	216.3 (12/20/94)	216.9 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								3.52	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								679	1				0	GE	µg/L
Nonvolatile beta								2.5E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								8.62	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 84A

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N108982.1 E51971.2	33.351580 °N 81.741700 °W	129.4-124.5 ft msl	361.5 ft msl	4" PVC	S	MCBC

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level		194.1 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 84C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N108967.9 E51973.7	33.351550 °N 81.741670 °W	194.9-190.2 ft msl	361.9 ft msl	4" PVC	S	LL

SAMPLE DATE 01/30/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		228.9	ft msl
pH		5.5	pH
Sp. conductance		33	µS/cm
Water temperature		18.1	°C
Alkalinity as CaCO ₃		1	mg/L
Turbidity		0.2	NTU
Volume purged		6.22	well volumes
Sampling code			
Synchronous water level	230.1 (12/20/94)	230.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								1.20	1	J			0	WA	µg/L
Barium, total recoverable								5.40	1	J			0	WA	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								1.90	1	J3			0	WA	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.7E-01	1				0	GP	pCi/L
Lead, total recoverable								<1.30	1				0	WA	µg/L
Mercury, total recoverable								0.150	1	JVV			0	WA	µg/L
Nickel, total recoverable								0.700	1	J			0	WA	µg/L
Nitrate-nitrite as nitrogen								1.450	1				0	GE	µg/L
Nonvolatile beta								7.5E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<1.40	1				0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate								6,940	1			■	0	WA	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								8.80	1	JV			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 85B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107827.0 E53122.7	33.350900 °N 81.736420 °W	137.3-132.6 ft msl	380.3 ft msl	4" PVC	S	CBA

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		222.3	ft msl
pH		6.3	pH
Sp. conductance		24	µS/cm
Water temperature		18.7	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		2.7	NTU
Volume purged		2.69	well volumes
Sampling code			
Synchronous water level	222.3 (12/20/94)	222.8 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								9.86	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								8.1E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1.370	1				0	GE	µg/L
Nonvolatile beta								8.9E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								1.70	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								15.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 85C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107835.2 E53151.4	33.350970 °N 81.736360 °W	173.6-168.8 ft msl	380.9 ft msl	4" PVC	S	LL

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.4	ft msl
pH		9.2	pH
Sp. conductance		77	µS/cm
Water temperature		16.3	°C
Alkalinity as CaCO ₃		20	mg/L
Turbidity		3.5	NTU
Volume purged		0.809	well volumes
Sampling code		X	
Synchronous water level	225.3 (12/20/94)	225.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								84.7	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								53.8	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.6E+00	1				0	GP	pCi/L
Lead, total recoverable								3.39	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								3,280	2		■		0	GE	µg/L
Nonvolatile beta								2.3E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								71.2	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								3.79	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 85D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N107822.8 E53108.8	33.350870 °N 81.736450 °W	236.3-216.2 ft msl	380.8 ft msl	4" PVC	S	MGCL

SAMPLE DATE 01/10/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		233.6	ft msl
pH		7.2	pH
Sp. conductance		79	µS/cm
Water temperature		17.2	°C
Alkalinity as CaCO ₃		30	mg/L
Turbidity		10.1	NTU
Volume purged		0.879	well volumes
Sampling code		X	
Synchronous water level	233.5 (12/20/94)	233.6 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								65.5	1				2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								13.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.1E+00	1				0	GP	pCi/L
Lead, total recoverable								4.40	1	J			0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								2.010	2				0	GE	µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								1,680	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								37.9	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 85TA

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N107831.2 E53137.2	33.350940 °N 81.736390 °W	88.2-82.8 ft msl	380.4 ft msl	4" Steel	S	CBA

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		221.8	ft msl
pH		9.2	pH
Sp. conductance		54	µS/cm
Water temperature		16.3	°C
Alkalinity as CaCO ₃		36	mg/L
Turbidity		50.0	NTU
Volume purged		0.417	well volumes
Sampling code		X	
Synchronous water level	221.8 (12/20/94)	222.2 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								23.8	1	J			0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								18.4	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	J1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.2E-01	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								<83.3	1				0	GE	µg/L
Nonvolatile beta								4.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								4.60	1				1	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.71	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 86C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N108500.4 E54560.5	33.354740 °N 81.733940 °W	164.8-160.1 ft msl	357 ft msl	4" PVC	S	LL

SAMPLE DATE 01/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		225.6	ft msl
pH		6.5	pH
Sp. conductance		32	µS/cm
Water temperature		17.6	°C
Alkalinity as CaCO ₃		9	mg/L
Turbidity		44.8	NTU
Volume purged		3.82	well volumes
Sampling code			
Synchronous water level	225.6 (12/20/94)	226.0 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								266	1		■		2	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								13.3	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.9E+00	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,080	1				0	GE	µg/L
Nonvolatile beta								2.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								6.0E-01	1				0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								7.70	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 87B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101276.0 E51607.0	33.333950 °N 81.727670 °W	174.1-169.1 ft msl	336 ft msl	2" PVC	V	LL

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		218.7	ft msl
pH		6.5	pH
Sp. conductance		56	µS/cm
Water temperature		19.0	°C
Alkalinity as CaCO ₃		15	mg/L
Turbidity		0.9	NTU
Volume purged		2.58	well volumes
Sampling code			
Synchronous water level	218.8 (12/20/94)	219.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								29.0	1	J			1	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								36.0	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.3E-01	1				0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								564	1				0	GE	µg/L
Nonvolatile beta								1.2E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								2,740	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								4.65	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 87C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101277.0 E51596.3	33.333930 °N 81.727700 °W	246.6-241.6 ft msl	336.6 ft msl	2" PVC	V	UL

SAMPLE DATE 01/10/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation		242.7	ft msl
pH		5.5	pH
Sp. conductance		27	µS/cm
Water temperature		19.1	°C
Alkalinity as CaCO ₃		3	mg/L
Turbidity		0.9	NTU
Volume purged		70.8	well volumes
Sampling code			
Synchronous water level	242.9 (12/20/94)	243.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable								4.61	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<8.33	1	1			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.1E-02	1	UI			0	GP	pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable								<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen								1,090	1				0	GE	µg/L
Nonvolatile beta								9.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable								<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate								<1,670	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene								<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<1.67	1				0	GE	µg/L
Trichloroethylene								<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable								66.4	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 88B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97013.0 E50774.2	33.323160 °N 81.721570 °W	75.8-70.8 ft msl	238.1 ft msl	2" PVC	V	MCBC

SAMPLE DATE	01/11/95
-------------	----------

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		201.5	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	201.3 (12/20/94)	202.2 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 88C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97012.7 E50784.0	33.323180 °N 81.721540 °W	127.2-122.2 ft msl	237.2 ft msl	2" PVC	V	UL

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		204.1	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	203.8 (12/20/94)	205.2 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 88D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N97012.3 E50793.5	33.323190 °N 81.721520 °W	212.2-192.1 ft msl	236.9 ft msl	2" PVC	V	MGC

SAMPLE DATE 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		205.3	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	205.0 (12/20/94)	206.3 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 89B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N98374.1 E47889.9	33.321460 °N 81.731810 °W	162.0-157.0 ft msl	339.4 ft msl	2" PVC	V	LL

SAMPLE DATE 01/17/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation		208.2	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	207.5 (12/20/94)	208.6 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															µg/L
PCB 1254															pCi/L
Radium, total alpha-emitting															µg/L
Selenium, total recoverable															pCi/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL MSB 89C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N98379.4 E47881.6	33.321460 °N 81.731840 °W	222.6-217.6 ft msl	339.8 ft msl	2" PVC	V	UL

SAMPLE DATE

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code		P	
Synchronous water level	229.7 (12/20/94)	229.9 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 1

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103776.7 E41407.0	33.322820 °N 81.759390 °W	230.2-200.2 ft msl	315.2 ft msl	4" PVC	V	M

SAMPLE DATE 11/09/94 02/14/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	213.1	212.5	ft msl
pH	4.9	4.2	pH
Sp. conductance	35	35	µS/cm
Water temperature	22.2	20.6	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	4.5	2.5	NTU
Volume purged	2.59	7.44	well volumes
Sampling code			
Synchronous water level	212.9 (12/20/94)	212.7 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								26.4	1	J			1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	11.0	1				0	GE	10.8	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	49.3	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.6E+00	1				0	GP	pCi/L
Lead, total recoverable	21.4	1				0	GE	5.51	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	4.04	1	J	■		0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.2E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.90	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	245	1				0	GE	64.8	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 1BB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103772.2 E41415.2	33.322820 °N 81.759360 °W	129.3-119.3 ft msl	316.3 ft msl	4" PVC	S	LL

SAMPLE DATE 11/09/94 02/14/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	207.9	207.7	ft msl
pH	5.5	5.3	pH
Sp. conductance	26	25	µS/cm
Water temperature	19.1	18.4	°C
Alkalinity as CaCO ₃	3	3	mg/L
Turbidity	32.6	22.2	NTU
Volume purged	4.44	5.09	well volumes
Sampling code			
Synchronous water level	207.7 (12/20/94)	208.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								101	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	8.72	1				0	GE	7.77	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.0E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	4.96	1				0	GE	4.05	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 2

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103721.8 E41627.2	33.323050 °N 81.758700 °W	228.6-198.6 ft msl	320.6 ft msl	4" PVC	S	M

SAMPLE DATE 11/04/94 02/14/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	215.0	211.4	ft msl
pH	4.5	4.3	pH
Sp. conductance	60	63	µS/cm
Water temperature	19.0	18.7	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.7	0.5	NTU
Volume purged	8.28	9.14	well volumes
Sampling code			
Synchronous water level	214.7 (12/20/94)	214.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								124	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	10.7	1				0	GE	10.2	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	26.4	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.3E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	3.19	1	J			0	GE	µg/L
Mercury, total recoverable	0.236	1	J			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.1E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.05	1	J			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	3.20	1				1	GE	1.80	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	3.46	1				0	GE	3.86	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 2A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103720.8 E41634.6	33.323060 °N 81.758680 °W	98.4-88.6 ft msl	320.6 ft msl	4" PVC	S	MCBC

SAMPLE DATE 11/04/94 02/14/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	206.9	206.7	ft msl
pH	4.7	4.5	pH
Sp. conductance	19	21	µS/cm
Water temperature	18.9	18.7	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.3	0.4	NTU
Volume purged	3.03	3.15	well volumes
Sampling code			
Synchronous water level	206.9 (12/20/94)	207.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								20.8	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.60	1				0	WA	4.37	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	41.8	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.2E-01	1				0	GP	pCi/L
Lead, total recoverable	4.40	1				0	WA	3.62	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1	J3			0	GE	µg/L
Nickel, total recoverable	4.20	1				0	WA	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								7.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	19.9	1				0	WA	6.99	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 2B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103729.7 E41631.7	33.323080 °N 81.758710 °W	162.6-152.8 ft msl	320.6 ft msl	4" PVC	S	UL

SAMPLE DATE 11/04/94 02/14/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	208.2	207.9	ft msl
pH	4.9	4.5	pH
Sp. conductance	18	19	µS/cm
Water temperature	18.6	18.4	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.2	0.2	NTU
Volume purged	7.55	3.35	well volumes
Sampling code			
Synchronous water level	207.9 (12/20/94)	209.1 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.90	1	J			0	GE	5.10	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	11.9	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable	4.34	1	J			0	GE	6.32	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	3.58	1				0	GE	3.14	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 3A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103516.4 E41851.2	33.322970 °N 81.757710 °W	193.1-163.1 ft msl	332.1 ft msl	4" PVC	S	GCL

SAMPLE DATE 11/02/94

02/13/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	214.1	213.1	ft msl
pH	5.0	4.9	pH
Sp. conductance	18	20	µS/cm
Water temperature	18.4	18.3	°C
Alkalinity as CaCO ₃	0	1	mg/L
Turbidity	0.2	0.2	NTU
Volume purged	3.08	3.08	well volumes
Sampling code			
Synchronous water level	213.9 (12/20/94)	213.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								12.5	1	JVV			0	WA	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	1.60	1	J			0	WA	µg/L
Barium, total recoverable	4.12	1	J			0	GE	4.60	1	J			0	WA	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.7E+00	1				0	TM	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1	JV2			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	0.970	1	J			0	WA	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								2.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<1.40	1				0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	44.6	1	V			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 3BB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103526.6 E41845.6	33.322980 °N 81.757750 °W	130.3-120.2 ft msl	332.3 ft msl	4" PVC	S	LL

SAMPLE DATE 11/02/94 02/13/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	208.9	208.8	ft msl
pH	5.8	5.9	pH
Sp. conductance	25	29	µS/cm
Water temperature	18.5	18.4	°C
Alkalinity as CaCO ₃	5	4	mg/L
Turbidity	32.9	21.6	NTU
Volume purged	5.58	5.47	well volumes
Sampling code			
Synchronous water level	208.9 (12/20/94)	209.9 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								43.5	1				1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	12.5	1				0	GE	17.0	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.2E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1	JV2			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								4.2E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	8.04	1				0	GE	2.81	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 4

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103359.9 E41612.4	33.322230 °N 81.758040 °W	230.1-200.1 ft msl	320.1 ft msl	4" PVC	S	M

SAMPLE DATE	11/10/94	02/15/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	213.7	213.2	ft msl
pH	4.5	5.1	pH
Sp. conductance	86	80	µS/cm
Water temperature	19.6	19.2	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.6	0.3	NTU
Volume purged	6.72	8.01	well volumes
Sampling code			
Synchronous water level	213.5 (12/20/94)	213.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								75.0	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1	J			0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	23.5	1				0	GE	24.3	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	85.8	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.2E+00	1				0	GP	pCi/L
Lead, total recoverable	11.2	1				0	GE	10.9	1				0	GE	µg/L
Mercury, total recoverable	0.319	1	J			0	GE	0.234	1	J			0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								3.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.3E+00	1				0	GP	pCi/L
Selenium, total recoverable	3.34	1				0	GE	2.38	1	J			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	18.3	1				0	GE	21.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 4BB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103347.9 E41609.2	33.322200 °N 81.758020 °W	134.1-124.0 ft msl	320.6 ft msl	4" PVC	S	LL

SAMPLE DATE 11/10/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	207.7	207.6	ft msl
pH	5.1	5.7	pH
Sp. conductance	25	24	µS/cm
Water temperature	18.9	18.3	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.1	0.9	NTU
Volume purged	4.97	3.65	well volumes
Sampling code			
Synchronous water level	207.5 (12/20/94)	208.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1	J			0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.40	1				0	GE	7.50	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								7.1E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								7.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	6.97	1				0	GE	5.59	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 5

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103418.2 E41240.0	33.321750 °N 81.759130 °W	224.6-194.6 ft msl	309.4 ft msl	4" PVC	S	M

SAMPLE DATE 11/10/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	211.9	211.4	ft msl
pH	4.8	5.4	pH
Sp. conductance	43	42	µS/cm
Water temperature	19.3	18.6	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.7	0.7	NTU
Volume purged	12.8	10.6	well volumes
Sampling code			
Synchronous water level	211.7 (12/20/94)	211.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1	J			0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	11.7	1				0	GE	10.9	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	303	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	22.1	1				0	GE	23.8	1	JVV			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	4.48	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.4E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.20	1	J			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	57.0	1				0	GE	64.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 6

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103602.7 E41243.9	33.322170 °N 81.759480 °W	222.6-192.6 ft msl	307.7 ft msl	4" PVC	S	M

SAMPLE DATE 11/10/94 02/14/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	212.7	208.3	ft msl
pH	4.7	4.8	pH
Sp. conductance	46	40	µS/cm
Water temperature	19.3	18.9	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.6	0.3	NTU
Volume purged	7.22	8.18	well volumes
Sampling code			
Synchronous water level	212.5 (12/20/94)	212.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1	J			0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	8.51	1				0	GE	7.33	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								
Copper, total recoverable	72.3	1				0	GE								
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable	10.4	1				0	GE	6.40	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	0.245	1	J			0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								4.5E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								4.1E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	11.0	1				0	GE	8.49	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 7

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103541.5 E40926.2	33.321510 °N 81.760200 °W	217.5-197.5 ft msl	299.1 ft msl	4" PVC	S	M

SAMPLE DATE 11/09/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	211.4	210.6	ft msl
pH	5.0	5.4	pH
Sp. conductance	24	30	µS/cm
Water temperature	20.2	17.1	°C
Alkalinity as CaCO ₃	2	1	mg/L
Turbidity	17.5	30.5	NTU
Volume purged	0.879	0.813	well volumes
Sampling code	X	X	
Synchronous water level	211.1 (12/20/94)	211.0 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								91.2	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.47	1	J			0	GE	4.02	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	117	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.9E+00	1				0	GP	pCi/L
Lead, total recoverable	24.4	1				0	GE	31.9	1				1	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.6E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	1.20	1	J			0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.50	1	J			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	35.2	1				0	GE	47.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 8

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103470.0 E40455.9	33.320580 °N 81.761300 °W	215.7-195.7 ft msl	288.1 ft msl	4" PVC	S	M

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	208.8	208.3	ft msl
pH	5.2	5.1	pH
Sp. conductance	25	26	µS/cm
Water temperature	18.7	18.4	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.5	0.9	NTU
Volume purged	7.69	6.17	well volumes
Sampling code			
Synchronous water level	208.7 (12/20/94)	208.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								99.0	1	VV			2	WA	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	3.10	1	JVV3			0	WA	µg/L
Barium, total recoverable	3.31	1	J			0	GE	4.00	1	J			0	WA	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	60.7	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.3E+00	1				0	TM	pCi/L
Lead, total recoverable	8.50	1				0	GE	12.5	1	J			0	WA	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	5.60	1	J	■		0	WA	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								2.0E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.2E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	2.40	1	JVV			0	WA	µg/L
Silver, total recoverable	<2.00	1				0	GE	<1.40	1				0	WA	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	1.28	1	J			0	WA	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	4.57	1				1	WA	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	21.4	1				0	GE	39.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 8BB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103468.0 E40464.9	33.320590 °N 81.761270 °W	130.3-120.2 ft msl	289.5 ft msl	4" PVC	S	LL

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation			ft msl
pH	7.0	7.0	pH
Sp. conductance	50	50	µS/cm
Water temperature	18.9	18.3	°C
Alkalinity as CaCO ₃	8	13	mg/L
Turbidity	2.3	2.9	NTU
Volume purged			well volumes
Sampling code			
Synchronous water level			ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								133	1		■	2		GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1			0		GE	µg/L
Barium, total recoverable	11.5	1				0	WA	11.4	1			0		GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1			0		GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1			0		GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1			0		GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								<8.33	1			0		GE	µg/L
1,1-Dichloroethane								<1.67	1			0		GE	µg/L
1,1-Dichloroethylene								<1.67	1			0		GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1			0		GE	µg/L
Gross alpha								1.4E+00	1			0		GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1			0		GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1			0		GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1			0		GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.8E+00	1			0		GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.5E+00	1			0		GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1			0		GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1			0		GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1			0		GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1			0		GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1			0		GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1			0		GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	7.90	1				0	WA	<3.33	1			0		GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 9

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103259.8 E39688.4	33.318870 °N 81.762910 °W	196.3-166.3 ft msl	253.4 ft msl	4" PVC	S	M

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	198.9	199.0	ft msl
pH	5.1	4.9	pH
Sp. conductance	19	20	µS/cm
Water temperature	18.5	17.9	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.1	0.5	NTU
Volume purged	6.17	8.40	well volumes
Sampling code			
Synchronous water level	198.7 (12/20/94)	200.5 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	3.96	1	J			0	GE	4.03	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								
Copper, total recoverable	11.8	1				0	GE								
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								4.5E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	2.40	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	<2.00	1				0	GE	2.74	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 9A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103251.1 E39692.9	33.318850 °N 81.762880 °W	124.3-114.4 ft msl	253.3 ft msl	4" PVC	S	MGC

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	198.7	199.0	ft msl
pH	5.1	4.9	pH
Sp. conductance	21	21	µS/cm
Water temperature	18.8	18.4	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.3	0.3	NTU
Volume purged	3.62	4.29	well volumes
Sampling code			
Synchronous water level	198.7 (12/20/94)	200.4 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	3.17	1	J			0	GE	3.28	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	28.6	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.2E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	4.18	1	J			0	GE	4.30	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								9.5E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	4.60	1				0	GE	6.15	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 9B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103241.6 E39697.6	33.318840 °N 81.762850 °W	162.4-152.6 ft msl	253.4 ft msl	4" PVC	S	M

SAMPLE DATE	11/08/94	02/09/95
-------------	----------	----------

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	199.6	199.8	ft msl
pH	5.2	5.1	pH
Sp. conductance	20	20	µS/cm
Water temperature	18.6	18.0	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.4	0.2	NTU
Volume purged	8.56	6.08	well volumes
Sampling code			
Synchronous water level	199.6 (12/20/94)	201.5 (03/23/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	7.19	1				0	GE	7.48	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.1E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.8E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.5E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	18.9	1				0	GE	16.7	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 10

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103387.9 E40944.3	33.321200 °N 81.759850 °W	223.0-193.0 ft msl	303.4 ft msl	4" PVC	S	M

SAMPLE DATE 11/09/94 02/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation			ft msl
pH	4.7	5.3	pH
Sp. conductance	24	24	µS/cm
Water temperature	19.1	18.6	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.3	1.5	NTU
Volume purged			well volumes
Sampling code			
Synchronous water level	(12/20/94)	(03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								12.3	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	4.11	1	J			0	GE	4.13	1	V			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	60.6	1				0	GE								µg/L
Cyanide								2.14	1	JVV			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.2E+00	1	UI			0	GP	pCi/L
Lead, total recoverable	8.22	1				0	GE	7.81	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	0.0420	1	J			0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<10.0	1	V			0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								8.7E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	1.55	1	JVV			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<0.650	1	V			0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	7.38	1				0	GE	7.56	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 10BB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103399.1 E40940.5	33.321220 °N 81.759880 °W	126.7-116.6 ft msl	302.8 ft msl	4" PVC	S	LL

SAMPLE DATE	11/09/94	02/17/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	205.6	205.8	ft msl
pH	5.3	5.6	pH
Sp. conductance	27	24	µS/cm
Water temperature	19.2	18.7	°C
Alkalinity as CaCO ₃	5	2	mg/L
Turbidity	9.3	6.6	NTU
Volume purged	4.68	3.97	well volumes
Sampling code			
Synchronous water level	205.5 (12/20/94)	207.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								52.5	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	6.73	1				0	GE	6.09	1	V			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								2.58	1	JVV			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.200	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<10.0	1	V			0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								3.9E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								-1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<5.00	1	V			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<0.650	1	V			0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	2.61	1	J			0	GE	8.50	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 11

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103693.2 E40874.2	33.321760 °N 81.760630 °W	220.6-190.6 ft msl	295.8 ft msl	4" PVC	S	M

SAMPLE DATE 11/09/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	211.0	210.2	ft msl
pH	4.8	5.3	pH
Sp. conductance	23	22	µS/cm
Water temperature	19.3	18.3	°C
Alkalinity as CaCO ₃	0	1	mg/L
Turbidity	0.8	0.4	NTU
Volume purged	5.54	5.14	well volumes
Sampling code			
Synchronous water level	210.7 (12/20/94)	210.6 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	3.12	1	J			0	GE	3.39	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	68.3	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1				0	GP	pCi/L
Lead, total recoverable	8.57	1				0	GE	8.58	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								3.4E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	2.10	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	2.10	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	6.56	1				0	GE	7.78	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 11BB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103703.4 E40871.2	33.321780 °N 81.760660 °W	129.5-119.5 ft msl	296.5 ft msl	4" PVC	S	LL

SAMPLE DATE 11/09/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	206.0	206.1	ft msl
pH	5.5	6.1	pH
Sp. conductance	28	27	µS/cm
Water temperature	19.2	18.2	°C
Alkalinity as CaCO ₃	5	4	mg/L
Turbidity	10.6	4.8	NTU
Volume purged	2.08	3.79	well volumes
Sampling code			
Synchronous water level	205.8 (12/20/94)	207.1 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								28.9	1	J			1	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	8.30	1				0	GE	7.30	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								9.4E-01	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.6E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	8.10	1				0	GE	5.01	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 12A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103710.3 E39013.3	33.318760 °N 81.765560 °W	113.7-103.9 ft msl	236.3 ft msl	4" PVC	S	M

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	193.6	194.7	ft msl
pH	4.8	4.7	pH
Sp. conductance	22	22	µS/cm
Water temperature	18.6	18.0	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	0.3	0.2	NTU
Volume purged	4.40	3.76	well volumes
Sampling code			
Synchronous water level	193.5 (12/20/94)	196.4 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								21.7	1	J			0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.67	1				0	GE	5.72	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	17.7	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								-1.9E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	2.45	1	J			0	GE	3.02	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 12B

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103702.7 E39020.3	33.318750 °N 81.765530 °W	156.1-146.3 ft msl	236.3 ft msl	4" PVC	S	M

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	187.9	189.6	ft msl
pH	5.4	5.1	pH
Sp. conductance	15	15	µS/cm
Water temperature	18.4	17.8	°C
Alkalinity as CaCO ₃	2	4	mg/L
Turbidity	0.3	0.3	NTU
Volume purged	4.58	3.98	well volumes
Sampling code			
Synchronous water level	187.9 (12/20/94)	192.2 (03/22/95)	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.04	1	J			0	GE	4.36	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								
Copper, total recoverable	7.08	1				0	GE								
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								-3.7E-02	1	UI			0	GP	pCi/L
Lead, total recoverable	6.11	1				0	GE	6.08	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								6.4E-01	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								-3.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	2.20	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	29.2	1				0	GE	26.6	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 12C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103712.5 E39023.1	33.318780 °N 81.765540 °W	198.9-179.1 ft msl	236.3 ft msl	4" PVC	S	M

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	194.8	196.0	ft msl
pH	5.2	5.1	pH
Sp. conductance	16	16	µS/cm
Water temperature	18.6	18.1	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.1	2.0	NTU
Volume purged	11.1	11.6	well volumes
Sampling code			
Synchronous water level	194.6 (12/20/94)	199.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.35	1	J			0	GE	4.59	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	80.0	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.5E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	10.8	1				0	GE	9.61	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	4.38	1	J			0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								4.8E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								0.0E+00	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	132	1				0	GE	127	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 13A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103001.0 E40668.2	33.319890 °N 81.759830 °W	103.6-93.8 ft msl	297.7 ft msl	4" PVC	S	LL

SAMPLE DATE	11/08/94	02/09/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	201.4	201.9	ft msl
pH	4.9	4.6	pH
Sp. conductance	22	22	µS/cm
Water temperature	19.5	18.0	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	0.5	0.2	NTU
Volume purged	3.78	3.46	well volumes
Sampling code			
Synchronous water level	201.5 (12/20/94)	202.9 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	3.69	1	J			0	GE	3.77	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								
Copper, total recoverable	23.6	1				0	GE								
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								-2.7E-02	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	3.30	1	J			0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 13B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102993.6 E40675.8	33.319890 °N 81.759790 °W	163.2-153.3 ft msl	297.7 ft msl	4" PVC	S	MCBC

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	203.4	203.4	ft msl
pH	4.9	4.6	pH
Sp. conductance	20	20	µS/cm
Water temperature	19.4	18.3	°C
Alkalinity as CaCO ₃	1		mg/L
Turbidity	0.4	0.2	NTU
Volume purged	3.41	3.41	well volumes
Sampling code			
Synchronous water level	203.5 (12/20/94)	204.7 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.49	1	J			0	GE	4.84	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	85.1	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								7.9E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	11.1	1				0	GE	10.7	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								5.2E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.7E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	13.4	1				0	GE	14.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 13C

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>						<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>						
N102986.5 E40682.7	33.319890 °N 81.759760 °W	225.4-195.8 ft msl						297.7 ft msl	4" PVC	S	M						
SAMPLE DATE		11/08/94						02/09/95									
FIELD DATA																	
<u>Parameter</u>	<u>4Q94</u>						<u>1Q95</u>						<u>Unit</u>				
Water elevation	210.1						209.4						ft msl				
pH	5.1						4.9						pH				
Sp. conductance	25						23						µS/cm				
Water temperature	19.2						18.0						°C				
Alkalinity as CaCO ₃	1						1						mg/L				
Turbidity	0.5						0.4						NTU				
Volume purged	5.55						15.6						well volumes				
Sampling code																	
Synchronous water level	209.8 (12/20/94)						210.0 (03/22/95)						ft msl				
ANALYTICAL DATA																	
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>		
Aluminum, total recoverable								<33.3	1				0	GE	µg/L		
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L		
Barium, total recoverable	5.04	1				0	GE	4.95	1	J			0	GE	µg/L		
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L		
Chloride															µg/L		
Chlorobenzene								<1.67	1				0	GE	µg/L		
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L		
Cobalt, total recoverable	<4.00	1				0	GE								µg/L		
Copper, total recoverable	114	1				0	GE								µg/L		
Cyanide								<8.33	1				0	GE	µg/L		
1,1-Dichloroethane								≤1.67	1				0	GE	µg/L		
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L		
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L		
Gross alpha								1.3E-01	1	UI			0	GP	pCi/L		
Lead, total recoverable	16.5	1				0	GE	15.3	1				0	GE	µg/L		
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L		
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L		
Nitrate-nitrite as nitrogen															µg/L		
Nonvolatile beta								3.4E-01	1	UI			0	GP	pCi/L		
PCB 1254															µg/L		
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L		
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L		
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L		
Sodium, total recoverable															µg/L		
Sulfate															µg/L		
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L		
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L		
Total phosphates (as P)															µg/L		
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L		
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L		
Uranium, total recoverable															µg/L		
Zinc, total recoverable	60.0	1				0	GE	75.9	1				0	GE	µg/L		

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 14A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102831.3 E41538.6	33.320940 °N 81.757200 °W	123.7-113.9 ft msl	327 ft msl	4" PVC	S	CBC

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	203.6	203.6	ft msl
pH	5.1	5.1	pH
Sp. conductance	25	25	µS/cm
Water temperature	19.2	18.6	°C
Alkalinity as CaCO ₃	1	2	mg/L
Turbidity	0.4	0.2	NTU
Volume purged	3.09	3.40	well volumes
Sampling code			
Synchronous water level	203.8 (12/20/94)	204.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.33	1	J			0	GE	4.43	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	35.8	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.8E+00	1				0	GP	pCi/L
Lead, total recoverable	4.30	1	J			0	GE	3.87	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.5E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	6.05	1		■		2	GE	13.9	1		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	5.14	1				0	GE	4.16	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 14B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102836.1 E41548.1	33.320970 °N 81.757190 °W	162.9-153.1 ft msl	326.9 ft msl	4" PVC	S	UL

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	205.6	205.2	ft msl
pH	5.2	5.1	pH
Sp. conductance	24	23	µS/cm
Water temperature	19.0	18.5	°C
Alkalinity as CaCO ₃	2	3	mg/L
Turbidity	0.3	0.2	NTU
Volume purged	3.42	3.39	well volumes
Sampling code			
Synchronous water level	205.5 (12/20/94)	206.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.91	1	J			0	GE	5.16	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								
Copper, total recoverable	104	1				0	GE								
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								4.0E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	12.0	1				0	GE	11.3	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								1.1E+00	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	2.46	1				0	GE	6.20	1		■		2	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	18.4	1				0	GE	20.3	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 14C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102824.2 E41546.4	33.320940 °N 81.757170 °W	228.3-198.6 ft msl	326.9 ft msl	4" PVC	S	M

SAMPLE DATE 11/08/94 02/09/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation			ft msl
pH	5.2	5.1	pH
Sp. conductance	17	17	µS/cm
Water temperature	19.0	18.2	°C
Alkalinity as CaCO ₃	1	2	mg/L
Turbidity	0.4	0.4	NTU
Volume purged			well volumes
Sampling code			
Synchronous water level			ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	3.03	1	J			0	GE	3.20	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	22.0	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								6.8E-01	1	UI			0	GP	pCi/L
Lead, total recoverable	10.0	1				0	GE	8.84	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								9.5E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	56.3	1				0	GE	63.2	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 15A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104778.0 E41234.7	33.324750 °N 81.761790 °W	107.6-97.8 ft msl	319.1 ft msl	4" PVC	S	MCBC

SAMPLE DATE 11/02/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	209.4	209.5	ft msl
pH	5.8	6.1	pH
Sp. conductance	25	32	µS/cm
Water temperature	18.3	18.1	°C
Alkalinity as CaCO ₃	3	4	mg/L
Turbidity	0.5	0.3	NTU
Volume purged	4.36	3.09	well volumes
Sampling code			
Synchronous water level	209.4 (12/20/94)	210.5 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	8.65	1				0	GE	12.1	1	Y			0	WA	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								
Copper, total recoverable	17.3	1				0	GE								
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.3E+00	1	J1			0	TM	pCi/L
Lead, total recoverable	3.75	1	J			0	GE	4.60	1	JY			0	WA	µg/L
Mercury, total recoverable	<0.200	1	JV2			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	2.60	1	JY			0	WA	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								1.2E+00	1	UI			0	TM	pCi/L
PCB 1254															
Radium, total alpha-emitting								9.0E-01	1				0	TM	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	0.530	1	JY			0	WA	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	11.9	1				0	GE	13.4	1	VY			0	WA	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 15B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104772.9 E41252.5	33.324770 °N 81.761740 °W	161.6-151.8 ft msl	319.1 ft msl	4" PVC	S	UL

SAMPLE DATE 11/02/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	208.2	209.5	ft msl
pH	5.3	5.4	pH
Sp. conductance	16	18	µS/cm
Water temperature	18.0	17.8	°C
Alkalinity as CaCO ₃	1	0	mg/L
Turbidity	0.2	0.2	NTU
Volume purged	1.92	3.49	well volumes
Sampling code			
Synchronous water level	209.7 (12/20/94)	210.7 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.00	1				0	WA	4.77	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	7.00	1				0	WA								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.6E+00	1				0	GP	pCi/L
Lead, total recoverable	6.00	1				0	WA	5.30	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1	JV2			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								6.2E-01	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								1.9E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	3.59	1				0	GE	2.42	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 15C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104774.9 E41245.1	33.324760 °N 81.761760 °W	217.3-187.7 ft msl	319.1 ft msl	4" PVC	S	M

SAMPLE DATE 11/02/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	213.4	212.4	ft msl
pH	5.2	5.3	pH
Sp. conductance	19	20	µS/cm
Water temperature	18.2	17.9	°C
Alkalinity as CaCO ₃	1	0	mg/L
Turbidity	0.3	0.3	NTU
Volume purged	5.94	6.84	well volumes
Sampling code			
Synchronous water level	213.0 (12/20/94)	212.8 (03/23/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	4.14	1	J			0	GE	3.93	1	J			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	20.7	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.7E+00	1				0	GP	pCi/L
Lead, total recoverable	5.57	1				0	GE	4.69	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1	JV2			0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.0E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	7.47	1				0	GE	6.07	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 16A

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103763.4 E42830.9	33.325110 °N 81.755620 °W	144.1-119.4 ft msl	346.8 ft msl	4" PVC	S	LL/CBC

SAMPLE DATE 11/09/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	214.8	214.1	ft msl
pH	10.8	11.6	pH
Sp. conductance	237	216	µS/cm
Water temperature	18.9	17.7	°C
Alkalinity as CaCO ₃	80	58	mg/L
Turbidity	13.1	5.8	NTU
Volume purged	0.448	0.451	well volumes
Sampling code	X	X	
Synchronous water level	214.5 (12/20/94)	214.6 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								540	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	2.49	1	J			0	GE	µg/L
Barium, total recoverable	32.0	1				0	GE	29.7	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	14.4	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.5E+00	1				0	GP	pCi/L
Lead, total recoverable	5.80	1				0	GE	3.45	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	7.38	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								1.2E+00	1	UI			0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								4.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.30	1	J			0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	13.7	1				0	GE	6.85	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 16B

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103772.0 E42825.8	33.325120 °N 81.755650 °W	169.9-160.1 ft msl	346.8 ft msl	4" PVC	S	L

SAMPLE DATE 11/08/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	215.3	214.8	ft msl
pH	4.6	5.3	pH
Sp. conductance	21	21	µS/cm
Water temperature	18.8	18.0	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.5	0.4	NTU
Volume purged	3.73	4.40	well volumes
Sampling code			
Synchronous water level	215.0 (12/20/94)	215.3 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	5.63	1				0	GE	5.87	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								
Copper, total recoverable	22.5	1				0	GE								
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.1E+00	1				0	GP	pCi/L
Lead, total recoverable	8.15	1				0	GE	7.58	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								1.4E+00	1	UI			0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								1.4E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	1.09	1	J			0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	15.1	1				0	GE	13.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 16C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103772.4 E42841.8	33.325150 °N 81.755600 °W	235.7-205.7 ft msl	346.6 ft msl	4" PVC	S	MGC

SAMPLE DATE 11/08/94 02/15/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	215.8	215.3	ft msl
pH	4.9	5.4	pH
Sp. conductance	18	19	µS/cm
Water temperature	18.7	17.8	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	1.0	0.4	NTU
Volume purged	9.64	11.2	well volumes
Sampling code			
Synchronous water level	215.7 (12/20/94)	215.8 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								<33.3	1				0	GE	µg/L
Arsenic, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Barium, total recoverable	6.97	1				0	GE	7.26	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	51.3	1				0	GE								µg/L
Cyanide								<8.33	1				0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								3.5E+00	1				0	GP	pCi/L
Lead, total recoverable	11.8	1				0	GE	16.7	1				0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								2.2E+00	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E+00	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	15.0	1				0	GE	16.0	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 17BB

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103956.1 E42463.8	33.324940 °N 81.756960 °W	132.3-122.2 ft msl	333.4 ft msl	4" PVC	S	LL

SAMPLE DATE 11/09/94 02/17/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	212.8	212.4	ft msl
pH	9.6	6.7	pH
Sp. conductance	94	47	µS/cm
Water temperature	18.7	18.2	°C
Alkalinity as CaCO ₃	33	11	mg/L
Turbidity	55.6	80.0	NTU
Volume purged	2.91	7.46	well volumes
Sampling code			
Synchronous water level	212.5 (12/20/94)	213.1 (03/22/95)	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								209	1		■		2	GE	µg/L
Arsenic, total recoverable	<2.00	1	J			0	GE	1.51	1	J			0	GE	µg/L
Barium, total recoverable	19.4	1				0	GE	13.1	1	V			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Chloride															
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								
Copper, total recoverable	<4.00	1				0	GE								
Cyanide								0.810	1	JVV			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								2.4E+00	1				0	GP	pCi/L
Lead, total recoverable	<3.00	1				0	GE	1.25	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	<0.200	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<10.0	1	V			0	GE	µg/L
Nitrate-nitrite as nitrogen															
Nonvolatile beta								2.3E+00	1				0	GP	pCi/L
PCB 1254															
Radium, total alpha-emitting								9.0E-01	1				0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	1.66	1	JVV			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<0.650	1	V			0	GE	µg/L
Sodium, total recoverable															
Sulfate															
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															
Zinc, total recoverable	5.68	1				0	GE	<5.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 17C

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N103965.9 E42465.5	33.324960 °N 81.756970 °W	161.3-151.2 ft msl	333.6 ft msl	2" PVC	V	LL									
SAMPLE DATE	11/09/94		02/17/95												
FIELD DATA															
Parameter	4Q94		1Q95			Unit									
Water elevation	212.9		212.6			ft msl									
pH	5.8		5.8			pH									
Sp. conductance	31		26			µS/cm									
Water temperature	20.4		19.3			°C									
Alkalinity as CaCO ₃	10		6			mg/L									
Turbidity	17.7		6.4			NTU									
Volume purged	3.06		3.97			well volumes									
Sampling code															
Synchronous water level	212.8 (12/20/94)		213.3 (03/22/95)			ft msl									
ANALYTICAL DATA															
Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								93.1	1				2	GE	µg/L
Arsenic, total recoverable	<2.00	1	J			0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	18.6	1				0	GE	20.3	1	V			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<1.67	1				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	5.39	1	J			0	GE								µg/L
Cyanide								<20.0	1	V			0	GE	µg/L
1,1-Dichloroethane								<1.67	1				0	GE	µg/L
1,1-Dichloroethylene								<1.67	1				0	GE	µg/L
trans-1,2-Dichloroethylene								<1.67	1				0	GE	µg/L
Gross alpha								1.1E+00	1				0	GP	pCi/L
Lead, total recoverable	5.13	1				0	GE	2.11	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	0.169	1	J			0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<10.0	1	V			0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta								2.4E+01	1				0	GP	pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting								2.0E-01	1	UI			0	GP	pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<5.00	1	V			0	GE	µg/L
Silver, total recoverable	<2.00	1				0	GE	<0.650	1	V			0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<1.67	1				0	GE	µg/L
Tetrachloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Trichloroethylene	<1.00	1				0	GE	<1.67	1				0	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	7.30	1				0	GE	<5.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL SRW 17D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103975.9 E42468.7	33.324990 °N 81.756980 °W	220.4-200.4 ft msl	333.7 ft msl	2" PVC	V	LL

SAMPLE DATE 11/09/94 02/17/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code	D	D	
Synchronous water level			ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

Table 5. Groundwater Monitoring Results for Recovery Wells

WELL RWM 1

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102599.1 E48575.1	33.331920 °N 81.738230 °W	232.3-172.3 ft msl	364.7 ft msl	8" CS	S	MGCL

SAMPLE DATE 10/13/94 11/07/94

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation			ft msl
pH	4.5	4.4	pH
Sp. conductance	107	106	µS/cm
Water temperature	19.2	19.1	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.8	0.4	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable								103	1		■		2	GE	µg/L
Arsenic, total recoverable								<2.00	1	J			0	GE	µg/L
Barium, total recoverable	39.6	1				0	GE	40.5	1				0	GE	µg/L
Cadmium, total recoverable								<2.00	1				0	GE	µg/L
Chloride								2,350	1				0	GE	µg/L
Chlorobenzene	<1,000	1000			0		GE	<500	500				0	GE	µg/L
Chromium, total recoverable								<4.00	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1			0		GE	<4.00	1				0	GE	µg/L
Copper, total recoverable	<4.00	1			0		GE	<4.00	1				0	GE	µg/L
Cyanide	<5.00	1			0		GE	<5.00	1				0	GE	µg/L
1,1-Dichloroethane	<1,000	1000			0		GE	<500	500				0	GE	µg/L
1,1-Dichloroethylene	<1,000	1000			0		GE	<500	500				0	GE	µg/L
trans-1,2-Dichloroethylene	<1,000	1000			0		GE	<500	500				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1			0		GE	<3.00	1				0	GE	µg/L
Mercury, total recoverable								0.210	1	J			0	GE	µg/L
Nickel, total recoverable	<4.00	1			0		GE	<4.00	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	8,240	10		■	1		GE	8,600	10		■		1	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1			0		GE	<2.00	1				0	GE	µg/L
Silver, total recoverable								<2.00	1				0	GE	µg/L
Sodium, total recoverable								4,750	1		■		0	GE	µg/L
Sulfate								<1,000	1				0	GE	µg/L
1,1,2,2-Tetrachloroethane	<1,000	1000			0		GE	<500	500				0	GE	µg/L
Tetrachloroethylene	16,900	1000		■	2		GE	17,300	500		■		2	GE	µg/L
Total phosphates (as P)								<50.0	1				0	GE	µg/L
1,1,1-Trichloroethane	<1,000	1000			0		GE	<500	500				0	GE	µg/L
Trichloroethylene	41,000	1000		■	2		GE	39,300	500		■		2	GE	µg/L
Uranium, total recoverable								<20.0	1				0	GE	µg/L
Zinc, total recoverable	3.95	1			0		GE	3.34	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 2

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104434.1 E49205.5	33.337010 °N 81.740140 °W	208.3-198.3 ft msl	371.3 ft msl		S	L

SAMPLE DATE	10/13/94	11/14/94
-------------	----------	----------

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation			ft msl
pH	4.3	4.6	pH
Sp. conductance	94	95	µS/cm
Water temperature	19.0	19.7	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	1.1	0.7	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	22.4	1				0	GE	22.0	1				0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	< 500	500				0	GE	< 500	500				0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	< 4.00	1				0	GE	< 4.00	1				0	GE	µg/L
Copper, total recoverable	< 4.00	1				0	GE	< 4.00	1				0	GE	µg/L
Cyanide	< 5.00	1				0	GE	< 5.00	1				0	GE	µg/L
1,1-Dichloroethane	< 500	500				0	GE	< 500	500				0	GE	µg/L
1,1-Dichloroethylene	< 500	500				0	GE	< 500	500				0	GE	µg/L
trans-1,2-Dichloroethylene	< 500	500				0	GE	< 500	500				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	< 3.00	1				0	GE	< 3.00	1				0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	7.95	1				0	GE	< 4.00	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	6,970	10				1	GE	7,330	4				1	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	< 2.00	1				0	GE	< 2.00	1				0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	< 500	500				0	GE	< 500	500				0	GE	µg/L
Tetrachloroethylene	12,200	500				2	GE	13,700	500				2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	< 500	500				0	GE	< 500	500				0	GE	µg/L
Trichloroethylene	17,400	500				2	GE	19,100	500				2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	3.18	1	J			0	GE	2.50	1	J			0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 3

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104730.2 E49680.0	33.338440 °N 81.739460 °W	214.0-204.0 ft msl	377 ft msl	8" CS	S	GCL

SAMPLE DATE	10/13/94	11/14/94
-------------	----------	----------

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation			ft msl
pH	4.9	4.7	pH
Sp. conductance	61	63	µS/cm
Water temperature	19.0	19.5	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	1.0	0.5	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	13.7	1				0	GE	13.4	1				0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<200	200				0	GE	<250	250				0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cyanide	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
1,1-Dichloroethane	<200	200				0	GE	<250	250				0	GE	µg/L
1,1-Dichloroethylene	<200	200				0	GE	<250	250				0	GE	µg/L
trans-1,2-Dichloroethylene	<200	200				0	GE	<250	250				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<3.00	1				0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	3,710	5		■		0	GE	4,010	2		■		0	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<200	200				0	GE	<250	250				0	GE	µg/L
Tetrachloroethylene	2,290	200		■		2	GE	3,250	250		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<200	200				0	GE	<250	250				0	GE	µg/L
Trichloroethylene	6,640	200		■		2	GE	8,850	250		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 4

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103719.3 E48948.2	33.335010 °N 81.739420 °W	211.9-201.6 ft msl	366.5 ft msl	8" CS	S	MGC

SAMPLE DATE	10/13/94	11/14/94
-------------	----------	----------

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation	209.8	209.2	ft msl
pH	4.6	4.7	pH
Sp. conductance	25	25	µS/cm
Water temperature	19.1	17.7	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.4	0.5	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	<3.00	1				0	GE	<3.00	1				0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<100	100				0	GE	<100	100				0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cyanide	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
1,1-Dichloroethane	<100	100				0	GE	<100	100				0	GE	µg/L
1,1-Dichloroethylene	<100	100				0	GE	<100	100				0	GE	µg/L
trans-1,2-Dichloroethylene	<100	100				0	GE	<100	100				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<3.00	1				0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	523	1				0	GE	575	1				0	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<100	100				0	GE	<100	100				0	GE	µg/L
Tetrachloroethylene	1,080	100		■		2	GE	1,070	100		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<100	100				0	GE	<100	100				0	GE	µg/L
Trichloroethylene	6,780	100		■		2	GE	6,570	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 5

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103502.2 E49628.0	33.335640 °N 81.737210 °W	216.8-206.4 ft msl	366.9 ft msl	8" CS	S	GCL

SAMPLE DATE 10/13/94 11/14/94

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation	212.7	212.5	ft msl
pH	4.6	4.8	pH
Sp. conductance	31	33	µS/cm
Water temperature	19.2	19.7	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	1.1	0.4	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	6.22	1				0	GE	58.5	1				0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<20.0	20				0	GE	<50.0	50	V			0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cyanide	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
1,1-Dichloroethane	<20.0	20				0	GE	<50.0	50	V			0	GE	µg/L
1,1-Dichloroethylene	<20.0	20				0	GE	<50.0	50	V			0	GE	µg/L
trans-1,2-Dichloroethylene	<20.0	20				0	GE	<50.0	50	V			0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<3.00	1				0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,600	1				0	GE	1,540	1				0	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<20.0	20				0	GE	<50.0	50	V			0	GE	µg/L
Tetrachloroethylene	899	20		■		2	GE	505	50	V	■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<20.0	20				0	GE	<50.0	50	V			0	GE	µg/L
Trichloroethylene	1,330	20		■		2	GE	1,120	50	V	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 6

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102001.5 E50107.4	33.333100 °N 81.733030 °W	218.7-208.4 ft msl	349.1 ft msl	8" CS	S	GCL

SAMPLE DATE	10/13/94	11/14/94
-------------	----------	----------

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation	178.6	177.6	ft msl
pH	4.8	4.8	pH
Sp. conductance	35	40	µS/cm
Water temperature	19.3	19.0	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.6	0.3	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit	
Aluminum, total recoverable															µg/L	
Arsenic, total recoverable															µg/L	
Barium, total recoverable	5.01	1				0	GE	4.92	1	J			0	GE	µg/L	
Cadmium, total recoverable															µg/L	
Chloride															µg/L	
Chlorobenzene	<200	200				0	GE	<100	100				0	GE	µg/L	
Chromium, total recoverable															µg/L	
Cobalt, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L	
Copper, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L	
Cyanide	<5.00	1				0	GE	<5.00	1				0	GE	µg/L	
1,1-Dichloroethane	<200	200				0	GE	<100	100				0	GE	µg/L	
1,1-Dichloroethylene	<200	200				0	GE	<100	100				0	GE	µg/L	
trans-1,2-Dichloroethylene	<200	200				0	GE	<100	100				0	GE	µg/L	
Gross alpha															pCi/L	
Lead, total recoverable	<3.00	1				0	GE	<3.00	1				0	GE	µg/L	
Mercury, total recoverable															µg/L	
Nickel, total recoverable	<4.00	1				0	GE	4.33	1	J	■		0	GE	µg/L	
Nitrate-nitrite as nitrogen	1,320	1				0	GE	1,290	1				0	GE	µg/L	
Nonvolatile beta															pCi/L	
PCB 1254															µg/L	
Radium, total alpha-emitting															pCi/L	
Selenium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L	
Silver, total recoverable															µg/L	
Sodium, total recoverable															µg/L	
Sulfate															µg/L	
1,1,2,2-Tetrachloroethane	<200	200				0	GE	<100	100				0	GE	µg/L	
Tetrachloroethylene	6,680	200				■	2	GE	6,030	100			■	2	GE	µg/L
Total phosphates (as P)															µg/L	
1,1,1-Trichloroethane	<200	200				0	GE	<100	100				0	GE	µg/L	
Trichloroethylene	6,040	200				■	2	GE	5,450	100			■	2	GE	µg/L
Uranium, total recoverable															µg/L	
Zinc, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L	

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 7

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N101904.6 E49449.5	33.331810 °N 81.734570 °W	216.3-206.0 ft msl	349 ft msl	8" CS	S	GCL

SAMPLE DATE 10/13/94 11/14/94

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation	198.0	194.9	ft msl
pH	4.5	4.6	pH
Sp. conductance	82	81	µS/cm
Water temperature	18.7	19.2	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.9	0.4	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	23.3	1				0	GE	22.8	1				0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<100	100				0	GE	<100	100				0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cyanide	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
1,1-Dichloroethane	<100	100				0	GE	<100	100				0	GE	µg/L
1,1-Dichloroethylene	<100	100				0	GE	<100	100				0	GE	µg/L
trans-1,2-Dichloroethylene	<100	100				0	GE	<100	100				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<3.00	1				0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	12.5	1		■		0	GE	6.64	1	J	■		0	GE	µg/L
Nitrate-nitrite as nitrogen	5,350	5		■		1	GE	5,410	4		■		1	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<100	100				0	GE	<100	100				0	GE	µg/L
Tetrachloroethylene	6,880	100		■		2	GE	6,630	100		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<100	100				0	GE	<100	100				0	GE	µg/L
Trichloroethylene	7,060	100		■		2	GE	7,120	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 8

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101948.2 E47353.3	33.328490 °N 81.740180 °W	197.2-186.9 ft msl	348.3 ft msl	8" CS	S	LCBC

SAMPLE DATE	10/13/94	11/14/94
-------------	----------	----------

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>4Q94</u>	<u>Unit</u>
Water elevation	200.3	213.9	ft msl
pH	4.8		pH
Sp. conductance	129		µS/cm
Water temperature	19.7		°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	0.8		NTU
Volume purged			well volumes
Sampling code	C	P	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	6.17	1				0	GE								µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<20.0	20				0	GE								µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE								µg/L
Copper, total recoverable	<4.00	1				0	GE								µg/L
Cyanide	<5.00	1				0	GE								µg/L
1,1-Dichloroethane	<20.0	20				0	GE								µg/L
1,1-Dichloroethylene	<20.0	20				0	GE								µg/L
trans-1,2-Dichloroethylene	<20.0	20				0	GE								µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE								µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	14.5	1		■		0	GE								µg/L
Nitrate-nitrite as nitrogen	10,200	10		■		2	GE								µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE								µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<20.0	20				0	GE								µg/L
Tetrachloroethylene	589	20		■		2	GE								µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<20.0	20				0	GE								µg/L
Trichloroethylene	1,120	20		■		2	GE								µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE								µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 9

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>						<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>						
N104099.8 E50400.0	33.338220 °N 81.736340 °W	220.6-210.2 ft msl						380.6 ft msl	8" CS	S	GCL						
SAMPLE DATE		10/13/94						11/14/94									
FIELD DATA																	
<u>Parameter</u>	<u>4Q94</u>							<u>4Q94</u>							<u>Unit</u>		
Water elevation	231.5							231.0							ft msl		
pH															pH		
Sp. conductance															µS/cm		
Water temperature															°C		
Alkalinity as CaCO ₃															mg/L		
Turbidity															NTU		
Volume purged															well volumes		
Sampling code	P							P									
Synchronous water level	N/A							N/A							ft msl		
ANALYTICAL DATA																	
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>		
Aluminum, total recoverable															µg/L		
Arsenic, total recoverable															µg/L		
Barium, total recoverable															µg/L		
Cadmium, total recoverable															µg/L		
Chloride															µg/L		
Chlorobenzene															µg/L		
Chromium, total recoverable															µg/L		
Cobalt, total recoverable															µg/L		
Copper, total recoverable															µg/L		
Cyanide															µg/L		
1,1-Dichloroethane															µg/L		
1,1-Dichloroethylene															µg/L		
trans-1,2-Dichloroethylene															µg/L		
Gross alpha															pCi/L		
Lead, total recoverable															µg/L		
Mercury, total recoverable															µg/L		
Nickel, total recoverable															µg/L		
Nitrate-nitrite as nitrogen															µg/L		
Nonvolatile beta															pCi/L		
PCB 1254															µg/L		
Radium, total alpha-emitting															pCi/L		
Selenium, total recoverable															µg/L		
Silver, total recoverable															µg/L		
Sodium, total recoverable															µg/L		
Sulfate															µg/L		
1,1,2,2-Tetrachloroethane															µg/L		
Tetrachloroethylene															µg/L		
Total phosphates (as P)															µg/L		
1,1,1-Trichloroethane															µg/L		
Trichloroethylene															µg/L		
Uranium, total recoverable															µg/L		
Zinc, total recoverable															µg/L		

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 10

SRS Coord.	Lat/Longitude	Screen Zone Elevation						Top of Casing		Casing	Pump	Screen Zone					
N102000.9 E48244.1	33.330060 °N 81.737930 °W	215.5-205.1 ft msl						355.5 ft msl		8" CS	S	GCL					
SAMPLE DATE		10/13/94						11/14/94									
FIELD DATA																	
Parameter		4Q94						4Q94						Unit			
Water elevation		183.0						178.4						ft msl			
pH		4.7						4.7						pH			
Sp. conductance		103						90						µS/cm			
Water temperature		19.2						18.8						°C			
Alkalinity as CaCO ₃		0						0						mg/L			
Turbidity		0.4						0.3						NTU			
Volume purged														well volumes			
Sampling code		C															
Synchronous water level		N/A						N/A						ft msl			
ANALYTICAL DATA																	
Parameter		4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit	
Aluminum, total recoverable																µg/L	
Arsenic, total recoverable																µg/L	
Barium, total recoverable		19.6	1				0	GE	17.7	1				0	GE	µg/L	
Cadmium, total recoverable																µg/L	
Chloride																µg/L	
Chlorobenzene		<100	100				0	GE	<100	100				0	GE	µg/L	
Chromium, total recoverable																µg/L	
Cobalt, total recoverable		<4.00	1				0	GE	<4.00	1				0	GE	µg/L	
Copper, total recoverable		<4.00	1				0	GE	<4.00	1				0	GE	µg/L	
Cyanide		<5.00	1				0	GE	<5.00	1				0	GE	µg/L	
1,1-Dichloroethane		<100	100				0	GE	<100	100				0	GE	µg/L	
1,1-Dichloroethylene		<100	100				0	GE	<100	100				0	GE	µg/L	
trans-1,2-Dichloroethylene		<100	100				0	GE	<100	100				0	GE	µg/L	
Gross alpha																pCi/L	
Lead, total recoverable		<3.00	1				0	GE	<3.00	1				0	GE	µg/L	
Mercury, total recoverable																µg/L	
Nickel, total recoverable		<4.00	1				0	GE	<4.00	1				0	GE	µg/L	
Nitrate-nitrite as nitrogen		7,510	10		■		1	GE	6,680	4		■		1	GE	µg/L	
Nonvolatile beta																pCi/L	
PCB 1254																µg/L	
Radium, total alpha-emitting																pCi/L	
Selenium, total recoverable		<2.00	1				0	GE	<2.00	1				0	GE	µg/L	
Silver, total recoverable																µg/L	
Sodium, total recoverable																µg/L	
Sulfate																µg/L	
1,1,2,2-Tetrachloroethane		<100	100				0	GE	<100	100				0	GE	µg/L	
Tetrachloroethylene		8,970	100		■		2	GE	7,420	100		■		2	GE	µg/L	
Total phosphates (as P)																µg/L	
1,1,1-Trichloroethane		<100	100				0	GE	<100	100				0	GE	µg/L	
Trichloroethylene		5,360	100		■		2	GE	5,160	100		■		2	GE	µg/L	
Uranium, total recoverable																µg/L	
Zinc, total recoverable		2.38	1	J			0	GE	2.00	1	J			0	GE	µg/L	

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 11

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104875.0 E50400.2	33.339930 °N 81.737850 °W	214.6-204.2 ft msl	383.3 ft msl	8" CS	S	L

SAMPLE DATE 10/13/94 11/14/94

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation	213.8	213.0	ft msl
pH	4.5	4.6	pH
Sp. conductance	37	36	µS/cm
Water temperature	19.7	20.1	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.5	0.3	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	4.38	1	J			0	GE	4.47	1	J			0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<50.0	50				0	GE	<100	100				0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cyanide	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
1,1-Dichloroethane	<50.0	50				0	GE	<100	100				0	GE	µg/L
1,1-Dichloroethylene	<50.0	50				0	GE	<100	100				0	GE	µg/L
trans-1,2-Dichloroethylene	<50.0	50				0	GE	<100	100				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<3.00	1				0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Nitrate-nitrite as nitrogen	1,760	2				0	GE	1,770	1				0	GE	µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<50.0	50				0	GE	<100	100				0	GE	µg/L
Tetrachloroethylene	200	50		■		2	GE	390	100		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<50.0	50				0	GE	<100	100				0	GE	µg/L
Trichloroethylene	2,310	50		■		2	GE	4,460	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 12

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N106879.2 E52500.1	33.347790 °N 81.736220 °W	210.4-189.9 ft msl	359.4 ft msl	6" CS/SS	S	L

SAMPLE DATE 10/13/94 11/14/94

FIELD DATA

Parameter	4Q94	4Q94	Unit
Water elevation	213.3	213.0	ft msl
pH	4.4	4.9	pH
Sp. conductance	44	45	µS/cm
Water temperature	18.4	18.9	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.4	0.4	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	4Q94	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	6.06	1				0	GE	6.03	1				0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<50.0	50				0	GE	<50.0	50				0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cyanide	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
1,1-Dichloroethane	<50.0	50				0	GE	<50.0	50				0	GE	µg/L
1,1-Dichloroethylene	<50.0	50				0	GE	<50.0	50				0	GE	µg/L
trans-1,2-Dichloroethylene	<50.0	50				0	GE	<50.0	50				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<3.00	1				0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	6.60	1	J	■		0	GE	<4.00	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<50.0	50				0	GE	<50.0	50				0	GE	µg/L
Tetrachloroethylene	<50.0	50				0	GE	<50.0	50				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<50.0	50				0	GE	<50.0	50				0	GE	µg/L
Trichloroethylene	2,430	50		■		2	GE	2,600	50		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 1

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>						<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>					
N102599.1 E48575.1	33.331920 °N 81.738230 °W	232.3-172.3 ft msl						364.7 ft msl	8" CS	S	MGCL					
SAMPLE DATE		12/16/94						01/11/95								
FIELD DATA																
<u>Parameter</u>	<u>4Q94</u>							<u>1Q95</u>							<u>Unit</u>	
Water elevation	224.3							223.7							ft msl	
pH															pH	
Sp. conductance															µS/cm	
Water temperature															°C	
Alkalinity as CaCO ₃															mg/L	
Turbidity															NTU	
Volume purged															well volumes	
Sampling code	P							P								
Synchronous water level	N/A							N/A							ft msl	
ANALYTICAL DATA																
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>	
Aluminum, total recoverable															µg/L	
Arsenic, total recoverable															µg/L	
Barium, total recoverable															µg/L	
Cadmium, total recoverable															µg/L	
Chloride															µg/L	
Chlorobenzene															µg/L	
Chromium, total recoverable															µg/L	
Cobalt, total recoverable															µg/L	
Copper, total recoverable															µg/L	
Cyanide															µg/L	
1,1-Dichloroethane															µg/L	
1,1-Dichloroethylene															µg/L	
trans-1,2-Dichloroethylene															µg/L	
Gross alpha															pCi/L	
Lead, total recoverable															µg/L	
Mercury, total recoverable															µg/L	
Nickel, total recoverable															µg/L	
Nitrate-nitrite as nitrogen															µg/L	
Nonvolatile beta															pCi/L	
PCB 1254															µg/L	
Radium, total alpha-emitting															pCi/L	
Selenium, total recoverable															µg/L	
Silver, total recoverable															µg/L	
Sodium, total recoverable															µg/L	
Sulfate															µg/L	
1,1,2,2-Tetrachloroethane															µg/L	
Tetrachloroethylene															µg/L	
Total phosphates (as P)															µg/L	
1,1,1-Trichloroethane															µg/L	
Trichloroethylene															µg/L	
Uranium, total recoverable															µg/L	
Zinc, total recoverable															µg/L	

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 2

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104434.1 E49205.5	33.337010 °N 81.740140 °W	208.3-198.3 ft msl	371.3 ft msl		S	L

SAMPLE DATE 12/16/94 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation			ft msl
pH	4.3	4.4	pH
Sp. conductance	94	97	µS/cm
Water temperature	17.1	18.1	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	1.5	0.4	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable	23.3	1				0	GE	24.6	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<250	250				0	GE	<835	500				0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane	<250	250				0	GE	<835	500				0	GE	µg/L
1,1-Dichloroethylene	<250	250				0	GE	<835	500				0	GE	µg/L
trans-1,2-Dichloroethylene	<250	250				0	GE	<835	500				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<250	250				0	GE	<835	500				0	GE	µg/L
Tetrachloroethylene	10,600	250		■		2	GE	11,700	500		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<250	250				0	GE	<835	500				0	GE	µg/L
Trichloroethylene	15,300	250		■		2	GE	17,400	1000	Y	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	3.36	1				0	GE	3.75	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 3

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104730.2 E49680.0	33.338440 °N 81.739460 °W	214.0-204.0 ft msl	377 ft msl	8" CS	S	GCL

SAMPLE DATE	12/16/94	01/31/95
-------------	----------	----------

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation			ft msl
pH	4.3	4.6	pH
Sp. conductance	61	59	µS/cm
Water temperature	16.5	17.9	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	0.7	0.6	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable	14.9	1				0	GE	14.7	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<250	250				0	GE	<835	500	Y			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane	<250	250				0	GE	<835	500	Y			0	GE	µg/L
1,1-Dichloroethylene	<250	250				0	GE	<835	500	Y			0	GE	µg/L
trans-1,2-Dichloroethylene	<250	250				0	GE	<835	500	Y			0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<250	250				0	GE	<835	500	Y			0	GE	µg/L
Tetrachloroethylene	4,530	250		■		2	GE	2,900	500		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<250	250				0	GE	<835	500	Y			0	GE	µg/L
Trichloroethylene	9,050	250		■		2	GE	8,170	500	Y	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 4

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>						<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>						
N103719.3 E48948.2	33.335010 °N 81.739420 °W	211.9-201.6 ft msl						366.5 ft msl	8" CS	S	MGC						
SAMPLE DATE		12/16/94						01/11/95									
FIELD DATA																	
<u>Parameter</u>	<u>4Q94</u>							<u>1Q95</u>							<u>Unit</u>		
Water elevation	222.9							222.3							ft msl		
pH															pH		
Sp. conductance															µS/cm		
Water temperature															°C		
Alkalinity as CaCO ₃															mg/L		
Turbidity															NTU		
Volume purged															well volumes		
Sampling code	P							P									
Synchronous water level	N/A							N/A							ft msl		
ANALYTICAL DATA																	
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>		
Aluminum, total recoverable															µg/L		
Arsenic, total recoverable															µg/L		
Barium, total recoverable															µg/L		
Cadmium, total recoverable															µg/L		
Chloride															µg/L		
Chlorobenzene															µg/L		
Chromium, total recoverable															µg/L		
Cobalt, total recoverable															µg/L		
Copper, total recoverable															µg/L		
Cyanide															µg/L		
1,1-Dichloroethane															µg/L		
1,1-Dichloroethylene															µg/L		
trans-1,2-Dichloroethylene															µg/L		
Gross alpha															pCi/L		
Lead, total recoverable															µg/L		
Mercury, total recoverable															µg/L		
Nickel, total recoverable															µg/L		
Nitrate-nitrite as nitrogen															µg/L		
Nonvolatile beta															pCi/L		
PCB 1254															µg/L		
Radium, total alpha-emitting															pCi/L		
Selenium, total recoverable															µg/L		
Silver, total recoverable															µg/L		
Sodium, total recoverable															µg/L		
Sulfate															µg/L		
1,1,2,2-Tetrachloroethane															µg/L		
Tetrachloroethylene															µg/L		
Total phosphates (as P)															µg/L		
1,1,1-Trichloroethane															µg/L		
Trichloroethylene															µg/L		
Uranium, total recoverable															µg/L		
Zinc, total recoverable															µg/L		

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 5

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103502.2 E49628.0	33.335640 °N 81.737210 °W	216.8-206.4 ft msl	366.9 ft msl	8" CS	S	GCL

SAMPLE DATE 12/16/94 01/31/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	213.1	213.4	ft msl
pH	4.3	4.7	pH
Sp. conductance	32	41	µS/cm
Water temperature	16.6	18.2	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	0.7	0.2	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable	6.38	1				0	GE	6.29	1				0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<25.0	25				0	GE	<83.5	50	Y			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane	<25.0	25				0	GE	<83.5	50				0	GE	µg/L
1,1-Dichloroethylene	<25.0	25				0	GE	<83.5	50	Y			0	GE	µg/L
trans-1,2-Dichloroethylene	<25.0	25				0	GE	<83.5	50	Y			0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<25.0	25				0	GE	<83.5	50	Y			0	GE	µg/L
Tetrachloroethylene	1,110	25		■		2	GE	995	50		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<25.0	25				0	GE	<83.5	50	Y			0	GE	µg/L
Trichloroethylene	941	25		■		2	GE	1,460	50	Y	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 6

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N102001.5 E50107.4	33.333100 °N 81.733030 °W	218.7-208.4 ft msl	349.1 ft msl	8" CS	S	GCL

SAMPLE DATE 12/16/94 01/11/95

FIELD DATA

Parameter	4Q94	1Q95	Unit
Water elevation	175.9	175.7	ft msl
pH	4.3	4.3	pH
Sp. conductance	35	33	µS/cm
Water temperature	14.7	17.2	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.5	0.4	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	5.26	1				0	GE	4.88	1	J			0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<100	100				0	GE	<418	250	Y			0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane	<100	100				0	GE	<418	250	Y			0	GE	µg/L
1,1-Dichloroethylene	<100	100				0	GE	<418	250	Y			0	GE	µg/L
trans-1,2-Dichloroethylene	<100	100				0	GE	<418	250	Y			0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254								<8,330	10	Y			0	GE	µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<100	100				0	GE	<418	250	Y			0	GE	µg/L
Tetrachloroethylene	5,320	100		■		2	GE	5,220	250	Y	■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<100	100				0	GE	<418	250	Y			0	GE	µg/L
Trichloroethylene	5,100	100		■		2	GE	4,670	250	Y	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 7

SRS Coord.	Lat/Longitude	Screen Zone Elevation						Top of Casing	Casing	Pump	Screen Zone						
N101904.6 E49449.5	33.331810 °N 81.734570 °W	216.3-206.0 ft msl						349 ft msl	8" CS	S	GCL						
SAMPLE DATE		12/16/94						01/31/95									
FIELD DATA																	
Parameter		4Q94						1Q95						Unit			
Water elevation		195.9						194.7						ft msl			
pH		4.2						4.5						pH			
Sp. conductance		81						77						µS/cm			
Water temperature		16.0						18.0						°C			
Alkalinity as CaCO ₃		0												mg/L			
Turbidity		0.6						0.7						NTU			
Volume purged														well volumes			
Sampling code		C						C									
Synchronous water level		N/A						N/A						ft msl			
ANALYTICAL DATA																	
Parameter		4Q94	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit	
Aluminum, total recoverable																µg/L	
Arsenic, total recoverable									<3.33	1				0	GE	µg/L	
Barium, total recoverable		22.3	1				0	GE	24.0	1				0	GE	µg/L	
Cadmium, total recoverable									<3.33	1				0	GE	µg/L	
Chloride																µg/L	
Chlorobenzene		<100	100				0	GE	<418	250	Y			0	GE	µg/L	
Chromium, total recoverable									<6.67	1				0	GE	µg/L	
Cobalt, total recoverable		<4.00	1				0	GE	<6.67	1				0	GE	µg/L	
Copper, total recoverable		<4.00	1				0	GE	<6.67	1				0	GE	µg/L	
Cyanide		<5.00	1	V			0	GE	<8.33	1	Y			0	GE	µg/L	
1,1-Dichloroethane		<100	100				0	GE	<418	250	Y			0	GE	µg/L	
1,1-Dichloroethylene		<100	100				0	GE	<418	250	Y			0	GE	µg/L	
trans-1,2-Dichloroethylene		<100	100				0	GE	<418	250	Y			0	GE	µg/L	
Gross alpha																pCi/L	
Lead, total recoverable		<3.00	1				0	GE	<5.00	1				0	GE	µg/L	
Mercury, total recoverable									0.242	1	J			0	GE	µg/L	
Nickel, total recoverable		4.95	1	J	■		0	GE	<6.67	1				0	GE	µg/L	
Nitrate-nitrite as nitrogen																µg/L	
Nonvolatile beta																pCi/L	
PCB 1254																µg/L	
Radium, total alpha-emitting																pCi/L	
Selenium, total recoverable		<2.00	1				0	GE	<3.33	1				0	GE	µg/L	
Silver, total recoverable									<3.33	1				0	GE	µg/L	
Sodium, total recoverable																µg/L	
Sulfate																µg/L	
1,1,2,2-Tetrachloroethane		<100	100				0	GE	<418	250	Y			0	GE	µg/L	
Tetrachloroethylene		5,580	100		■		2	GE	6,450	500		■		2	GE	µg/L	
Total phosphates (as P)																µg/L	
1,1,1-Trichloroethane		<100	100				0	GE	<418	250	Y			0	GE	µg/L	
Trichloroethylene		6,320	100		■		2	GE	6,600	250	Y	■		2	GE	µg/L	
Uranium, total recoverable																µg/L	
Zinc, total recoverable		<2.00	1				0	GE	<3.33	1				0	GE	µg/L	

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 8

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>									
N101948.2 E47353.3	33.328490 °N 81.740180 °W	197.2-186.9 ft msl	348.3 ft msl	8" CS	S	LCBC									
SAMPLE DATE		12/16/94		01/11/95											
FIELD DATA															
<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>			<u>Unit</u>										
Water elevation	215.3	216.4			ft msl										
pH					pH										
Sp. conductance					µS/cm										
Water temperature					°C										
Alkalinity as CaCO ₃					mg/L										
Turbidity					NTU										
Volume purged					well volumes										
Sampling code	P	P													
Synchronous water level	N/A	N/A			ft msl										
ANALYTICAL DATA															
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 9

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104099.8 E50400.0	33.338220 °N 81.736340 °W	220.6-210.2 ft msl	380.6 ft msl	8" CS	S	GCL

SAMPLE DATE 12/16/94 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	230.4	230.2	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code	P	P	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 10

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>						<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>						
N102000.9 E48244.1	33.330060 °N 81.737930 °W	215.5-205.1 ft msl						355.5 ft msl	8" CS	S	GCL						
SAMPLE DATE		12/16/94						01/11/95									
FIELD DATA																	
<u>Parameter</u>	<u>4Q94</u>							<u>1Q95</u>							<u>Unit</u>		
Water elevation	217.8							218.4							ft msl		
pH															pH		
Sp. conductance															µS/cm		
Water temperature															°C		
Alkalinity as CaCO ₃															mg/L		
Turbidity															NTU		
Volume purged															well volumes		
Sampling code	P							P									
Synchronous water level	N/A							N/A							ft msl		
ANALYTICAL DATA																	
<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>		
Aluminum, total recoverable															µg/L		
Arsenic, total recoverable															µg/L		
Barium, total recoverable															µg/L		
Cadmium, total recoverable															µg/L		
Chloride															µg/L		
Chlorobenzene															µg/L		
Chromium, total recoverable															µg/L		
Cobalt, total recoverable															µg/L		
Copper, total recoverable															µg/L		
Cyanide															µg/L		
1,1-Dichloroethane															µg/L		
1,1-Dichloroethylene															µg/L		
trans-1,2-Dichloroethylene															µg/L		
Gross alpha															pCi/L		
Lead, total recoverable															µg/L		
Mercury, total recoverable															µg/L		
Nickel, total recoverable															µg/L		
Nitrate-nitrite as nitrogen															µg/L		
Nonvolatile beta															pCi/L		
PCB 1254															µg/L		
Radium, total alpha-emitting															pCi/L		
Selenium, total recoverable															µg/L		
Silver, total recoverable															µg/L		
Sodium, total recoverable															µg/L		
Sulfate															µg/L		
1,1,2,2-Tetrachloroethane															µg/L		
Tetrachloroethylene															µg/L		
Total phosphates (as P)															µg/L		
1,1,1-Trichloroethane															µg/L		
Trichloroethylene															µg/L		
Uranium, total recoverable															µg/L		
Zinc, total recoverable															µg/L		

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 11

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104875.0 E50400.2	33.339930 °N 81.737850 °W	214.6-204.2 ft msl	383.3 ft msl	8" CS	S	L

SAMPLE DATE 12/16/94 01/31/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	212.1	212.3	ft msl
pH	4.3	4.4	pH
Sp. conductance	34	34	µS/cm
Water temperature	16.5	18.7	°C
Alkalinity as CaCO ₃	0		mg/L
Turbidity	0.6	0.5	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable								<3.33	1				0	GE	µg/L
Barium, total recoverable	4.24	1	J			0	GE	4.47	1	J			0	GE	µg/L
Cadmium, total recoverable								<3.33	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<25.0	25				0	GE	<167	100	Y			0	GE	µg/L
Chromium, total recoverable								<6.67	1				0	GE	µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane	<25.0	25				0	GE	<167	100	Y			0	GE	µg/L
1,1-Dichloroethylene	<25.0	25				0	GE	<167	100	Y			0	GE	µg/L
trans-1,2-Dichloroethylene	<25.0	25				0	GE	<167	100	Y			0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable								<0.333	1				0	GE	µg/L
Nickel, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L
Silver, total recoverable								<3.33	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<25.0	25				0	GE	<167	100	Y			0	GE	µg/L
Tetrachloroethylene	115	25				2	GE	160	100	JY			2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<25.0	25				0	GE	<167	100	Y			0	GE	µg/L
Trichloroethylene	898	25				2	GE	2,030	100	Y			2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 12

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N106879.2 E52500.1	33.347790 °N 81.736220 °W	210.4-189.9 ft msl	359.4 ft msl	6" CS/SS	S	L

SAMPLE DATE 12/14/94 01/11/95

FIELD DATA

<u>Parameter</u>	<u>4Q94</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	213.3	212.6	ft msl
pH	4.0	4.5	pH
Sp. conductance	44	44	µS/cm
Water temperature	16.9	18.0	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.4	0.5	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>4Q94</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable	6.24	1				0	GE	6.24	1				0	GE	µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene	<50.0	50				0	GE	<83.5	50	Y			0	GE	µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Copper, total recoverable	<4.00	1				0	GE	<6.67	1				0	GE	µg/L
Cyanide	<5.00	1	V			0	GE	<8.33	1	Y			0	GE	µg/L
1,1-Dichloroethane	<50.0	50				0	GE	<83.5	50				0	GE	µg/L
1,1-Dichloroethylene	<50.0	50				0	GE	<83.5	50	Y			0	GE	µg/L
trans-1,2-Dichloroethylene	<50.0	50				0	GE	<83.5	50	Y			0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<3.00	1				0	GE	<5.00	1	Y			0	GE	µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable	<4.00	1				0	GE	9.16	1		■		0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<2.00	1				0	GE	<3.33	1	Y			0	GE	µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<50.0	50				0	GE	<83.5	50	Y			0	GE	µg/L
Tetrachloroethylene	<50.0	50				0	GE	<83.5	50	Y			0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<50.0	50				0	GE	<83.5	50	Y			0	GE	µg/L
Trichloroethylene	2,450	50		■		2	GE	2,440	50	Y	■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable	<2.00	1				0	GE	<3.33	1				0	GE	µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 1

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102599.1 E48575.1	33.331920 °N 81.738230 °W	232.3-172.3 ft msl	364.7 ft msl	8" CS	S	MGCL

SAMPLE DATE 02/27/95 03/13/95

FIELD DATA

<u>Parameter</u>	<u>1Q95</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	214.9		ft msl
pH	5.3	4.7	pH
Sp. conductance	39	93	µS/cm
Water temperature	20.2	19.0	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	3.0	0.7	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	10.0	1	V			0	GE	36.1	1	V			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<2.00	1	V			0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<167	100				0	GE	<1,670	1000				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<20.0	1				0	GE	<20.0	1	VV			0	GE	µg/L
1,1-Dichloroethane	<167	100				0	GE	<1,670	1000				0	GE	µg/L
1,1-Dichloroethylene	<167	100				0	GE	<1,670	1000				0	GE	µg/L
trans-1,2-Dichloroethylene	<167	100				0	GE	<1,670	1000				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	3.44	1		■		2	GE	0.870	1	V			0	GE	µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Silver, total recoverable	<0.650	1				0	GE	<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<167	100				0	GE	<1,670	1000				0	GE	µg/L
Tetrachloroethylene	2,390	100		■		2	GE	8,740	1000		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<167	100				0	GE	<1,670	1000				0	GE	µg/L
Trichloroethylene	2,250	100		■		2	GE	29,700	1000		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 2

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104434.1 E49205.5	33.337010 °N 81.740140 °W	208.3-198.3 ft msl	371.3 ft msl		S	L

SAMPLE DATE 02/13/95 03/13/95

FIELD DATA

Parameter	1Q95	1Q95	Unit
Water elevation			ft msl
pH	4.0	4.6	pH
Sp. conductance	97	99	µS/cm
Water temperature	17.6	20.2	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.3	0.4	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	1Q95	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable	<3.33	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	23.9	1				0	GE	25.2	1	V			0	GE	µg/L
Cadmium, total recoverable	<3.33	1				0	GE	<2.00	1	V			0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<1,670	1000				0	GE	<417	250				0	GE	µg/L
Chromium, total recoverable	<6.67	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1	V			0	GE	0.980	1	JVV			0	GE	µg/L
1,1-Dichloroethane	<1,670	1000				0	GE	<417	250				0	GE	µg/L
1,1-Dichloroethylene	<1,670	1000				0	GE	<417	250				0	GE	µg/L
trans-1,2-Dichloroethylene	<1,670	1000				0	GE	<417	250				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.202	1	J			0	GE	0.247	1	VV			0	GE	µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	2.11	1	J			0	GE	<5.00	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<1,670	1000				0	GE	<417	250				0	GE	µg/L
Tetrachloroethylene	10,200	1000		■		2	GE	10,200	250		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<1,670	1000				0	GE	<417	250				0	GE	µg/L
Trichloroethylene	15,700	1000		■		2	GE	14,000	250		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 3

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N104730.2 E49680.0	33.338440 °N 81.739460 °W	214.0-204.0 ft msl	377 ft msl	8" CS	S	GCL

SAMPLE DATE 02/13/95

03/13/95

FIELD DATA

Parameter	1Q95	1Q95	Unit
Water elevation			ft msl
pH	4.0	4.7	pH
Sp. conductance	59	59	µS/cm
Water temperature	17.3	20.0	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.9	0.5	NTU
Volume purged			well volumes
Sampling code	C		
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	1Q95	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable	<3.33	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	14.4	1				0	GE	14.3	1				0	GE	µg/L
Cadmium, total recoverable	<3.33	1				0	GE	<2.00	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<834	500				0	GE	<834	500				0	GE	µg/L
Chromium, total recoverable	<6.67	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1	V			0	GE	<20.0	1	VV			0	GE	µg/L
1,1-Dichloroethane	<834	500				0	GE	<834	500				0	GE	µg/L
1,1-Dichloroethylene	<834	500				0	GE	<834	500				0	GE	µg/L
trans-1,2-Dichloroethylene	<834	500				0	GE	<834	500				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1				0	GE	0.159	1	JVV			0	GE	µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<3.33	1				0	GE	<5.00	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<834	500				0	GE	<834	500				0	GE	µg/L
Tetrachloroethylene	2,920	500		■		2	GE	2,380	500		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<834	500				0	GE	<834	500				0	GE	µg/L
Trichloroethylene	7,980	500		■		2	GE	7,330	500		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 4

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N103719.3 E48948.2	33.335010 °N 81.739420 °W	211.9-201.6 ft msl	366.5 ft msl	8" CS	S	MGC

SAMPLE DATE 02/27/95 03/13/95

FIELD DATA

<u>Parameter</u>	<u>1Q95</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	220.1	207.9	ft msl
pH	5.8	5.1	pH
Sp. conductance	24	26	µS/cm
Water temperature	19.9	19.5	°C
Alkalinity as CaCO ₃	1	1	mg/L
Turbidity	0.7	0.5	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	3.92	1	V			0	GE	2.55	1	JV			0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<2.00	1	V			0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<417	250				0	GE	<167	100				0	GE	µg/L
Chromium, total recoverable	23.0	1				0	GE	4.01	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<20.0	1				0	GE	1.40	1	JVV			0	GE	µg/L
1,1-Dichloroethane	<417	250				0	GE	<167	100				0	GE	µg/L
1,1-Dichloroethylene	<417	250				0	GE	<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene	<417	250				0	GE	<167	100				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE	0.830	1	J			0	GE	µg/L
Mercury, total recoverable	<0.200	1				0	GE	0.0660	1	JVV			0	GE	µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Silver, total recoverable	<0.650	1				0	GE	<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<417	250				0	GE	<167	100				0	GE	µg/L
Tetrachloroethylene	1,540	250		■		2	GE	1,360	100		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<417	250				0	GE	<167	100				0	GE	µg/L
Trichloroethylene	5,730	250		■		2	GE	5,880	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 5

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N103502.2 E49628.0	33.335640 °N 81.737210 °W	216.8-206.4 ft msl	366.9 ft msl	8" CS	S	GCL

SAMPLE DATE 02/13/95

03/13/95

FIELD DATA

Parameter	1Q95	1Q95	Unit
Water elevation	213.5	212.0	ft msl
pH	4.5	5.1	pH
Sp. conductance	64	39	µS/cm
Water temperature	18.1	20.1	°C
Alkalinity as CaCO ₃	0	1	mg/L
Turbidity	0.3	0.3	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

Parameter	1Q95	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable	<3.33	1						<5.00	1					GE	µg/L
Arsenic, total recoverable	7.22	1				0	GE	28.4	1				0	GE	µg/L
Barium, total recoverable	<3.33	1				0	GE	<2.00	1				0	GE	µg/L
Cadmium, total recoverable	<41.7	25				0	GE	<167	100				0	GE	µg/L
Chloride	<6.67	1				0	GE	<4.00	1				0	GE	µg/L
Chlorobenzene															
Chromium, total recoverable															
Cobalt, total recoverable															
Copper, total recoverable															
Cyanide	<8.33	1	V			0	GE	<20.0	1	VV			0	GE	µg/L
1,1-Dichloroethane	<41.7	25				0	GE	<167	100				0	GE	µg/L
1,1-Dichloroethylene	<41.7	25				0	GE	<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene	<41.7	25				0	GE	<167	100				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	<0.333	1				0	GE	0.128	1	JVV			0	GE	µg/L
Nickel, total recoverable								<10.0	1				0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															pCi/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<3.33	1				0	GE	<5.00	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<41.7	25				0	GE	<167	100				0	GE	µg/L
Tetrachloroethylene	823	25		■		2	GE	929	100		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<41.7	25				0	GE	<167	100				0	GE	µg/L
Trichloroethylene	1,300	25		■		2	GE	1,470	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 6

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102001.5 E50107.4	33.333100 °N 81.733030 °W	218.7-208.4 ft msl	349.1 ft msl	8" CS	S	GCL

SAMPLE DATE 02/13/95 03/13/95

FIELD DATA

<u>Parameter</u>	<u>1Q95</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	223.6	222.9	ft msl
pH			pH
Sp. conductance			µS/cm
Water temperature			°C
Alkalinity as CaCO ₃			mg/L
Turbidity			NTU
Volume purged			well volumes
Sampling code	P	P	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 7

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N101904.6 E49449.5	33.331810 °N 81.734570 °W	216.3-206.0 ft msl	349 ft msl	8" CS	S	GCL

SAMPLE DATE 02/13/95 03/13/95

FIELD DATA

<u>Parameter</u>	<u>1Q95</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	194.3	193.5	ft msl
pH	4.3	4.8	pH
Sp. conductance	79	77	µS/cm
Water temperature	17.3	20.7	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.3	0.5	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable	<3.33	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	23.5	1				0	GE	22.9	1	V			0	GE	µg/L
Cadmium, total recoverable	<3.33	1				0	GE	<2.00	1	V			0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<167	100				0	GE	<167	100				0	GE	µg/L
Chromium, total recoverable	<6.67	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1	V			0	GE	1.40	1	JVV			0	GE	µg/L
1,1-Dichloroethane	<167	100				0	GE	<167	100				0	GE	µg/L
1,1-Dichloroethylene	<167	100				0	GE	<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene	<167	100				0	GE	<167	100				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.276	1	J			0	GE	0.288	1	VV			0	GE	µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<3.33	1				0	GE	<5.00	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<167	100				0	GE	<167	100				0	GE	µg/L
Tetrachloroethylene	5,130	100		■		2	GE	5,320	100		■		2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<167	100				0	GE	<167	100				0	GE	µg/L
Trichloroethylene	5,910	100		■		2	GE	5,990	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 8

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone									
N101948.2 E47353.3	33.328490 °N 81.740180 °W	197.2-186.9 ft msl	348.3 ft msl	8" CS	S	LCBC									
SAMPLE DATE		02/27/95		03/13/95											
FIELD DATA															
Parameter	1Q95	1Q95			Unit										
Water elevation	208.3	213.7			ft msl										
pH	4.9				pH										
Sp. conductance	250				µS/cm										
Water temperature	19.5				°C										
Alkalinity as CaCO ₃	1				mg/L										
Turbidity	3.7				NTU										
Volume purged					well volumes										
Sampling code	C	P													
Synchronous water level	N/A	N/A			ft msl										
ANALYTICAL DATA															
Parameter	1Q95	DF	Mod	ST	H	Flag	Lab	1Q95	DF	Mod	ST	H	Flag	Lab	Unit
Aluminum, total recoverable															µg/L
Arsenic, total recoverable	<5.00	1				0	GE								µg/L
Barium, total recoverable	10.0	1	V			0	GE								µg/L
Cadmium, total recoverable	<2.00	1				0	GE								µg/L
Chloride															µg/L
Chlorobenzene	<41.7	25				0	GE								µg/L
Chromium, total recoverable	<4.00	1				0	GE								µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<20.0	1				0	GE								µg/L
1,1-Dichloroethane	<41.7	25				0	GE								µg/L
1,1-Dichloroethylene	<41.7	25				0	GE								µg/L
trans-1,2-Dichloroethylene	<41.7	25				0	GE								µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE								µg/L
Mercury, total recoverable	<0.200	1				0	GE								µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	2.25	1	J			0	GE								µg/L
Silver, total recoverable	<0.650	1				0	GE								µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<41.7	25				0	GE								µg/L
Tetrachloroethylene	1,050	25		■		2	GE								µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<41.7	25				0	GE								µg/L
Trichloroethylene	1,570	25		■		2	GE								µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

- = exceeded holding time.
- = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 9

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>									
N104099.8 E50400.0	33.338220 °N 81.736340 °W	220.6-210.2 ft msl	380.6 ft msl	8" CS	S	GCL									
SAMPLE DATE		02/13/95		03/13/95											
FIELD DATA															
<u>Parameter</u>	<u>1Q95</u>	<u>1Q95</u>			<u>Unit</u>										
Water elevation	230.3	230.4			ft msl										
pH					pH										
Sp. conductance					µS/cm										
Water temperature					°C										
Alkalinity as CaCO ₃					mg/L										
Turbidity					NTU										
Volume purged					well volumes										
Sampling code	P	P													
Synchronous water level	N/A	N/A			ft msl										
ANALYTICAL DATA															
<u>Parameter</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable															µg/L
Barium, total recoverable															µg/L
Cadmium, total recoverable															µg/L
Chloride															µg/L
Chlorobenzene															µg/L
Chromium, total recoverable															µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide															µg/L
1,1-Dichloroethane															µg/L
1,1-Dichloroethylene															µg/L
trans-1,2-Dichloroethylene															µg/L
Gross alpha															pCi/L
Lead, total recoverable															µg/L
Mercury, total recoverable															µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable															µg/L
Silver, total recoverable															µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane															µg/L
Tetrachloroethylene															µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane															µg/L
Trichloroethylene															µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 10

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N102000.9 E48244.1	33.330060 °N 81.737930 °W	215.5-205.1 ft msl	355.5 ft msl	8" CS	S	GCL

SAMPLE DATE 02/13/95 03/13/95

FIELD DATA

<u>Parameter</u>	<u>1Q95</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	219.7	177.1	ft msl
pH		4.9	pH
Sp. conductance		124	µS/cm
Water temperature		20.2	°C
Alkalinity as CaCO ₃		0	mg/L
Turbidity		0.4	NTU
Volume purged			well volumes
Sampling code	P	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable								<5.00	1				0	GE	µg/L
Barium, total recoverable								22.4	1	V			0	GE	µg/L
Cadmium, total recoverable								<2.00	1	V			0	GE	µg/L
Chloride															µg/L
Chlorobenzene								<83.4	50				0	GE	µg/L
Chromium, total recoverable								<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide								<20.0	1	VV			0	GE	µg/L
1,1-Dichloroethane								<83.4	50				0	GE	µg/L
1,1-Dichloroethylene								<83.4	50				0	GE	µg/L
trans-1,2-Dichloroethylene								<83.4	50				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable								<5.00	1				0	GE	µg/L
Mercury, total recoverable								0.183	1	JVV			0	GE	µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable								1.57	1	J			0	GE	µg/L
Silver, total recoverable								<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane								<83.4	50				0	GE	µg/L
Tetrachloroethylene								11,100	250			■	2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane								<83.4	50				0	GE	µg/L
Trichloroethylene								4,380	50			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 11

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N104875.0 E50400.2	33.339930 °N 81.737850 °W	214.6-204.2 ft msl	383.3 ft msl	8" CS	S	L

SAMPLE DATE 02/13/95

03/13/95

FIELD DATA

<u>Parameter</u>	<u>1Q95</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	211.6	212.3	ft msl
pH	4.3	4.6	pH
Sp. conductance	34	34	µS/cm
Water temperature	18.5	21.9	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.3	0.4	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable	<3.33	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	4.53	1	J			0	GE	4.47	1	V			0	GE	µg/L
Cadmium, total recoverable	<3.33	1				0	GE	<2.00	1	V			0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<41.7	25				0	GE	<83.4	50				0	GE	µg/L
Chromium, total recoverable	<6.67	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<8.33	1	V			0	GE	<20.0	1	VV			0	GE	µg/L
1,1-Dichloroethane	<41.7	25				0	GE	<83.4	50				0	GE	µg/L
1,1-Dichloroethylene	<41.7	25				0	GE	<83.4	50				0	GE	µg/L
trans-1,2-Dichloroethylene	<41.7	25				0	GE	<83.4	50				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE	0.840	1	J			0	GE	µg/L
Mercury, total recoverable	<0.333	1				0	GE	0.168	1	JVV			0	GE	µg/L
Nickel, total recoverable															µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<3.33	1				0	GE	<5.00	1				0	GE	µg/L
Silver, total recoverable	<3.33	1				0	GE	<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<41.7	25				0	GE	<83.4	50				0	GE	µg/L
Tetrachloroethylene	160	25			■	2	GE	175	50			■	2	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<41.7	25				0	GE	<83.4	50				0	GE	µg/L
Trichloroethylene	1,630	25			■	2	GE	1,760	50			■	2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

WELL RWM 12

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N106879.2 E52500.1	33.347790 °N 81.736220 °W	210.4-189.9 ft msl	359.4 ft msl	6" CS/SS	S	L

SAMPLE DATE	02/24/95	03/13/95
-------------	----------	----------

FIELD DATA

<u>Parameter</u>	<u>1Q95</u>	<u>1Q95</u>	<u>Unit</u>
Water elevation	213.4	214.4	ft msl
pH	4.5	4.6	pH
Sp. conductance	41	43	µS/cm
Water temperature	18.2	19.7	°C
Alkalinity as CaCO ₃	0	0	mg/L
Turbidity	0.3	0.4	NTU
Volume purged			well volumes
Sampling code	C	C	
Synchronous water level	N/A	N/A	ft msl

ANALYTICAL DATA

<u>Parameter</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>1Q95</u>	<u>DF</u>	<u>Mod</u>	<u>ST</u>	<u>H</u>	<u>Flag</u>	<u>Lab</u>	<u>Unit</u>
Aluminum, total recoverable															µg/L
Arsenic, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Barium, total recoverable	6.75	1				0	GE	6.30	1				0	GE	µg/L
Cadmium, total recoverable	<2.00	1				0	GE	<2.00	1				0	GE	µg/L
Chloride															µg/L
Chlorobenzene	<83.4	50				0	GE	<167	100				0	GE	µg/L
Chromium, total recoverable	<4.00	1				0	GE	<4.00	1				0	GE	µg/L
Cobalt, total recoverable															µg/L
Copper, total recoverable															µg/L
Cyanide	<20.0	1				0	GE	0.780	1	JVV3			0	GE	µg/L
1,1-Dichloroethane	<83.4	50				0	GE	<167	100				0	GE	µg/L
1,1-Dichloroethylene	<83.4	50				0	GE	<167	100				0	GE	µg/L
trans-1,2-Dichloroethylene	<83.4	50				0	GE	<167	100				0	GE	µg/L
Gross alpha															pCi/L
Lead, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Mercury, total recoverable	0.461	1				0	GE	0.305	1	VV			0	GE	µg/L
Nickel, total recoverable	<10.0	1				0	GE	3.05	1	J			0	GE	µg/L
Nitrate-nitrite as nitrogen															µg/L
Nonvolatile beta															pCi/L
PCB 1254															µg/L
Radium, total alpha-emitting															pCi/L
Selenium, total recoverable	<5.00	1				0	GE	<5.00	1				0	GE	µg/L
Silver, total recoverable	<0.650	1	V			0	GE	<0.650	1				0	GE	µg/L
Sodium, total recoverable															µg/L
Sulfate															µg/L
1,1,2,2-Tetrachloroethane	<83.4	50				0	GE	<167	100				0	GE	µg/L
Tetrachloroethylene	<83.4	50				0	GE	<167	100				0	GE	µg/L
Total phosphates (as P)															µg/L
1,1,1-Trichloroethane	<83.4	50				0	GE	<167	100				0	GE	µg/L
Trichloroethylene	4,810	50		■		2	GE	2,340	100		■		2	GE	µg/L
Uranium, total recoverable															µg/L
Zinc, total recoverable															µg/L

Note: See Appendix A for standards. See Appendix B for flagging criteria.

● = exceeded holding time.

■ = exceeded groundwater protection standard, background concentration, or drinking water standard.

Table 6. Constituents Exceeding Standards or Background Concentrations in Point-of-Compliance Wells

M-Area Aquifer Zone

<u>Well</u>	<u>SZ^a</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q95</u>	<u>Mod</u>
MSB 1D	MGCL ^b	Radium, tot. alpha-emitting	pCi/L	5.4E+00	JV
		Sodium	µg/L	5,650	
		Tetrachloroethylene	µg/L	27.6	
		Trichloroethylene	µg/L	14.3	
MSB 2D	MGCL	Aluminum	µg/L	191	
		Gross alpha	pCi/L	1.6E+01	
		Nitrate	µg/L	2,830	
		Radium, tot. alpha-emitting	pCi/L	1.1E+01	
		Tetrachloroethylene	µg/L	997	
		Trichloroethylene	µg/L	944	
MSB 4D	M	Aluminum	µg/L	190	
		Nitrate	µg/L	6,160	
		Radium, tot. alpha-emitting	pCi/L	6.8E+00	
		Sodium	µg/L	7,540	
		Sulfate	µg/L	4,020	
		Tetrachloroethylene	µg/L	105	
		Trichloroethylene	µg/L	125	
MSB 5A	M	Nitrate	µg/L	2,760	
		Sodium	µg/L	6,240	
MSB 6A	M	Chloride	µg/L	4,820	
		Sodium	µg/L	5,600	
MSB 8A	M	Nitrate	µg/L	2,630	
		Selenium	µg/L	19.0	
		Tetrachloroethylene	µg/L	88.4	
		Trichloroethylene	µg/L	16.4	
MSB 13D	MGC	1,1-Dichloroethylene	µg/L	9.10	
		Nitrate	µg/L	54,300	
		Sodium	µg/L	107,000	
		Sulfate	µg/L	3,100	
		Tetrachloroethylene	µg/L	38.7	
		Trichloroethylene	µg/L	20.6	
MSB 57D	M	Sodium	µg/L	4,850	
		Tetrachloroethylene	µg/L	309	
		Trichloroethylene	µg/L	96.9	
MSB 58D	M	Aluminum	µg/L	111	
		Chloride	µg/L	4,890	
		Lead	µg/L	50.9	
		Nickel	µg/L	9.09	
		Tetrachloroethylene	µg/L	780	
		Trichloroethylene	µg/L	1,820	

Table 6 (cont.)

M-Area Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q95</u>	<u>Mod</u>
MSB 59D	M	Aluminum	µg/L	226	
		Nitrate	µg/L	4,520	
		Sodium	µg/L	6,990	
		Tetrachloroethylene	µg/L	65,700	J2
		Trichloroethylene	µg/L	19,700	J2
MSB 60D	M	Nitrate	µg/L	3,150	
		Radium, tot. alpha-emitting	pCi/L	5.6E+00	
		Tetrachloroethylene	µg/L	168	
		Trichloroethylene	µg/L	83.5	
MSB 62D	M	Aluminum	µg/L	1,860	
		Nitrate	µg/L	7,200	
		Sodium	µg/L	45,900	
		Sulfate	µg/L	6,680	
		Tetrachloroethylene	µg/L	178	
		Trichloroethylene	µg/L	60.0	
MSB 63D	MGC	Aluminum	µg/L	908	
		Nitrate	µg/L	2,840	
		Sodium	µg/L	5,550	
		Tetrachloroethylene	µg/L	183	
		Trichloroethylene	µg/L	28.0	
MSB 64D	MGC	Nitrate	µg/L	5,680	
		Sodium	µg/L	17,900	
		Sulfate	µg/L	3,440	

Upper Lost Lake Aquifer Zone

<u>Well</u>	<u>SZ</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q95</u>	<u>Mod</u>
MSB 1C	UL	Aluminum	µg/L	3,500	
		Nitrate	µg/L	9,820	
		Sodium	µg/L	37,000	
		Sulfate	µg/L	5,170	
		Tetrachloroethylene	µg/L	345	
		Trichloroethylene	µg/L	66.0	
MSB 1CC	UL	Nitrate	µg/L	5,640	
		Sodium	µg/L	16,100	
		Tetrachloroethylene	µg/L	22.6	
		Trichloroethylene	µg/L	30.6	
MSB 2C	UL	Aluminum	µg/L	535	
		Nitrate	µg/L	11,800	
		Sodium	µg/L	63,900	
		Tetrachloroethylene	µg/L	13,000	
		Trichloroethylene	µg/L	11,400	

Table 6 (cont.)

Upper Lost Lake Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q95</u>	<u>Mod</u>
MSB 4C	UL	Nitrate	µg/L	15,000	
		Sodium	µg/L	23,000	
		Tetrachloroethylene	µg/L	2,460	
		Trichloroethylene	µg/L	2,480	
MSB 5C	UL	Aluminum	µg/L	131	
		1,1-Dichloroethylene	µg/L	26.0	
		Nitrate	µg/L	19,700	
		Sodium	µg/L	27,100	
		Tetrachloroethylene	µg/L	214	
		Total phosphates	µg/L	469	
		Trichloroethylene	µg/L	11.0	J
MSB 6C	UL	Aluminum	µg/L	187	
		Nitrate	µg/L	45,500	
		Radium, tot. alpha-emitting	pCi/L	7.0E+00	
		Sodium	µg/L	128,000	
		Sulfate	µg/L	4,680	
		Tetrachloroethylene	µg/L	138	
		Total phosphates	µg/L	1,560	
		Trichloroethylene	µg/L	35.4	
MSB 7C	GCL	Aluminum	µg/L	290	
		Nitrate	µg/L	32,100	
		Nonvolatile beta	pCi/L	8.1E+01	
		Radium, tot. alpha-emitting	pCi/L	6.7E+00	
		Sodium	µg/L	48,100	
		Tetrachloroethylene	µg/L	44.7	
		Trichloroethylene	µg/L	16.8	
MSB 8C	UL	Chloride	µg/L	4,990	
		1,1-Dichloroethylene	µg/L	13.5	
		Nitrate	µg/L	25,800	
		Radium, tot. alpha-emitting	pCi/L	5.8E+00	
		Sodium	µg/L	20,900	
		Tetrachloroethylene	µg/L	104	
		Trichloroethylene	µg/L	57.5	
MSB 13CC	GCL	Nitrate	µg/L	15,600	
		Sodium	µg/L	16,500	
		Sulfate	µg/L	4,370	
		Tetrachloroethylene	µg/L	13.6	
		Trichloroethylene	µg/L	12.1	
MSB 62C	UL	1,1-Dichloroethylene	µg/L	15.0	
		Nitrate	µg/L	12,100	
		Sodium	µg/L	25,500	
		Tetrachloroethylene	µg/L	262	
		Trichloroethylene	µg/L	122	

Table 6 (cont.)

Upper Lost Lake Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q95</u>	<u>Mod</u>
MSB 63C	UL	Tetrachloroethylene	µg/L	15.2	J1
		Trichloroethylene	µg/L	5.80	J1
MSB 64C	UL	Aluminum	µg/L	182	
		Nitrate	µg/L	14,300	
		Radium, tot. alpha-emitting	pCi/L	5.4E+00	
		Sodium	µg/L	11,900	
		Tetrachloroethylene	µg/L	471	
		Trichloroethylene	µg/L	73.2	

Lower Lost Lake Aquifer Zone

<u>Well</u>	<u>SZ</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q95</u>	<u>Mod</u>
MSB 1B	LL	Trichloroethylene	µg/L	548	
MSB 2B	LL	Aluminum	µg/L	1,550	
		Nitrate	µg/L	6,810	
		Sodium	µg/L	56,400	
		Tetrachloroethylene	µg/L	2,720	
		Trichloroethylene	µg/L	7,310	
MSB 4B	LL	Nitrate	µg/L	3,530	
		Sodium	µg/L	5,410	
		Tetrachloroethylene	µg/L	4,820	
		Trichloroethylene	µg/L	2,440	
MSB 6B	LL	Nitrate	µg/L	2,580	
		Tetrachloroethylene	µg/L	48.8	
		Trichloroethylene	µg/L	1,610	
MSB 7B	LL	Aluminum	µg/L	182	
		Nitrate	µg/L	5,920	
		Sodium	µg/L	9,820	
		Tetrachloroethylene	µg/L	83.5	
		Total phosphates	µg/L	1,290	
		Trichloroethylene	µg/L	56.1	
MSB 8B	LL	Trichloroethylene	µg/L	17.5	
MSB 13A	LL	Trichloroethylene	µg/L	706	
MSB 62B	LL	Tetrachloroethylene	µg/L	42.1	
		Trichloroethylene	µg/L	60.4	
MSB 63B	LL	Tetrachloroethylene	µg/L	15.0	J1
		Trichloroethylene	µg/L	300	J1

Table 6 (cont.)

Lower Lost Lake Aquifer Zone (cont.)

<u>Well</u>	<u>SZ</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q95</u>	<u>Mod</u>
MSB 64B	MCBC	Nitrate	µg/L	3,520	
		Tetrachloroethylene	µg/L	58.0	J1
		Trichloroethylene	µg/L	2,960	J1

Notes: Total phosphates were measured as phosphorous. The groundwater samples are unfiltered; thus, the results for metals are for total recoverable metals. None of the POC wells were sampled fourth quarter 1994.

^a SZ = screen zone.

^b MGCL screen zone assignments are tentative. According to the Lewis and Aadland (1993) study, these well screens cross from the M-Area Aquifer Zone through the green clay zone and into the Upper Lost Lake Aquifer Zone.

Table 7. Maximum Results for Appendix IX Constituents Not Currently Used to Determine Compliance

<u>Well</u>	<u>Constituent</u>	<u>3Q94^a Result ($\mu\text{g/L}$)</u>	<u>1Q95^b Result ($\mu\text{g/L}$)</u>
MSB 8A	Zinc	18.7	5.0
MSB 8B	Zinc	23.2	5.35
MSB 8C	Mercury	0.344	0.294
	Tin	2.64	<3.33
	Zinc	6.21	5.71
MSB 58D	Tin	NS ^c	4.0
	Zinc	NS	144
MSB 64B	Zinc	12.4	13.2
MSB 64C	Mercury	0.399	0.341
MSB 64D	Zinc	11.4	20.2

Notes: The concentrations reported third quarter 1994 exceeded the method detection limits for the constituents listed. The first quarter 1995 results are confirmation results. The M-Area HWMF RCRA Part B permit application requires that wells MSB 3B, 8A, 8B, 8C, 58D, 64B, 64C, and 64D (20 percent of the POC wells) be analyzed for Appendix IX constituents. During third quarter 1994, wells MSB 3B and 58D were not sampled because of mechanical problems. Well MSB 3B was not sampled first quarter 1995 because of mechanical problems.

^a Sample dates were 7/11/94 through 8/9/94.

^b Sample dates were 1/30/95 through 2/16/95.

^c NS = not sampled.

Table 8. CUSUM Analysis of Trichloroethylene Concentrations in Selected Monitoring Wells

<u>Well</u>	<u>SZ^a</u>	<u>1Q95 Trend</u>	<u>Long-Term Trend</u>
M-Area Aquifer Zone			
MSB 3A	M	No Data	No Trend
MSB 4A	M	No Data	Upward
MSB 9B	GCL	Upward	Upward
MSB 9C	M	Upward	Upward
MSB 12D	MGC	No Data	Upward
MSB 13C	M	No Data	Upward
MSB 16C	M	No Data	Downward
MSB 18B	GCL	Upward	Upward
MSB 19C	M	Upward	Upward
MSB 20C	M	No Data	Downward
MSB 25	M	No Data	Upward
MSB 26	M	No Data	Downward
MSB 34C	MGCL	No Data	Downward
MSB 39D	MGC	Upward	Upward
Upper Lost Lake Aquifer Zone			
MSB 12B	UL	Upward	Upward
MSB 15A	UL	Upward	Upward
MSB 16A	UL	No Data	Upward
MSB 18A	UL	Upward	Upward
MSB 19B	UL	Downward	Downward
MSB 20A	L(UD)	No Data	Upward
MSB 26A	UL	No Data	Upward
MSB 27B	UL	No Data	Downward
MSB 33C	UL	No Data	No Trend
MSB 34B	UL	No Data	Downward
MSB 36C	UL	Upward	Upward
MSB 37C	UL	No Data	Downward
MSB 39C	UL	Downward	Downward
Lower Lost Lake Aquifer Zone			
ASB 8B	(LL)/MCBC	Upward	Upward
MSB 9A	LL/CBC	No Trend	Upward
MSB 12A	LL	Upward	Upward
MSB 13A	LL	No Data	Upward
MSB 21A	LL	Upward	Upward
MSB 25A	LL	No Data	Downward
MSB 33B	LL/CBC	No Data	Upward
MSB 39B	LL	Downward	Downward
Middle Sand Aquifer Zone of CBCU			
MSB 19A	MCBC	Upward	Upward
MSB 33A	MCBC	No Data	Downward
MSB 34A	MCBC	No Data	Upward
MSB 37B	MCBC	No Data	Upward
MSB 41B	MCBC	No Data	Upward

^a SZ = screen zone.

Table 9. CUSUM Analysis of Trichloroethylene Concentrations in Recovery Wells

<u>Well</u>	<u>1Q95 Trend</u>	<u>Long-Term Trend</u>
RWM 1	Downward	Downward
RWM 2	Downward	Downward
RWM 3	Downward	Downward
RWM 4	Downward	Downward
RWM 5	Upward	Upward
RWM 6	Downward	Downward
RWM 7	Upward	Upward
RWM 8	Upward	Upward
RWM 9	No Data	Upward
RWM 10	Upward	Upward
RWM 11	Downward	Downward

Table 10. Summary of Water-Elevation Drawdowns in the M-Area Aquifer Zone

<u>Well</u>	Static Water Elevation (ft above msl)	Drawdown Water Elevation (ft above msl)	Drawdown (ft)
	<u>1Q85</u>	<u>1Q95</u>	
ABP 1A	229.0	224.9	4.1
ABP 1DD	- ^a	225.6	-
ABP 2A	228.4	223.7	4.7
ABP 2DD	-	223.4	-
ABP 3	229.8	225.2	4.6
ABP 4	227.5	223.4	4.1
ABP 4DD	-	224.3	-
ABP 6D	-	223.5	-
ABP 7D	-	224.4	-
ABP 8D	-	223.1	-
AC 1B	222.9	214.1	8.8
AC 2B	240.8	227.5	13.3
AC 3B	221.1	213.0	8.1
ACB 1A	247.8	238.7	9.1
ACB 2A	247.4	239.8	7.6
ACB 3A	247.3	239.6	7.7
ACB 4A	248.1	239.8	8.3
AMB 4D	-	234.4	-
AMB 5	-	234.8	-
AMB 6	-	234.9	-
AMB 7	-	235.2	-
AMB 8D	-	234.9	-
AMB 9D	-	235.3	-
AMB 10D	-	236.6	-
AMB 10DD	-	359.2	-
AMB 11D	-	237.2	-
AMB 12D	-	235.8	-
AMB 14D	-	233.7	-
AMB 15D	-	235.0	-
AMB 16D	-	234.4	-
AOB 1	246.5	237.6	8.9
AOB 2	246.7	238.3	8.4
AOB 3	-	239.1	-
ARP 1A	224.5	217.4	7.1
ARP 2	227.1	219.7	7.4
ARP 3	227.8	222.0	5.8
ARP 4	224.2	219.7	4.5
ASB 1A	244.4	238.3	6.1
ASB 2A	244.7	-	-
ASB 2AR	-	239.7	-
ASB 3A	244.4	-	-
ASB 3AR	-	240.3	-
ASB 4	243.4	239.4	4.0
ASB 5A	244.0	-	-
ASB 5AR	-	237.7	-
ASB 6A	243.9	237.8	6.1
ASB 7	242.4	-	-
ASB 8	240.7	235.0	5.7
ASB 9	244.2	242.6	1.6
MCB 2	-	225.2	-
MCB 4	-	225.4	-

Table 10 (cont.)

Well	Static Water Elevation (ft above msl) <u>1Q85</u>	Drawdown Water Elevation (ft above msl) <u>1Q95</u>	Drawdown (ft)
MCB 5	—	225.7	—
MCB 6	—	220.5	—
MCB 8D	—	226.0	—
MCB 9D	—	223.8	—
MSB 1A	244.2	232.1	12.1
MSB 1D	—	231.6	—
MSB 2A	244.4	232.7	11.7
MSB 2D	—	232.4	—
MSB 3A	244.3	—	—
MSB 3D	—	—	—
MSB 4A	243.9	231.3	12.6
MSB 4D	—	230.5	—
MSB 5A	241.2	228.4	12.8
MSB 6A	239.4	228.0	11.4
MSB 7A	240.5	229.0	11.5
MSB 7C	—	223.5	—
MSB 8A	242.3	230.1	12.2
MSB 9B	244.6	230.9	13.7
MSB 9C	244.9	230.9	14.0
MSB 10C	243.5	230.2	13.3
MSB 10D	—	—	—
MSB 11D	244.9	231.2	13.7
MSB 11E	—	239.8	—
MSB 11F	245.0	231.4	13.6
MSB 12D	242.3	234.0	8.3
MSB 13C	—	229.6	—
MSB 13CC	—	225.7	—
MSB 13D	—	229.1	—
MSB 14B	231.1	219.0	12.1
MSB 14C	245.1	232.4	12.7
MSB 15C	—	245.1	—
MSB 15D	—	233.2	—
MSB 16C	245.2	231.7	13.5
MSB 17B	238.4	226.4	12.0
MSB 17C	240.9	—	—
MSB 17D	—	227.5	—
MSB 18B	231.8	222.6	9.2
MSB 18C	238.5	228.5	10.0
MSB 19C	245.0	239.4	5.6
MSB 20C	239.9	227.6	12.3
MSB 21C	242.5	229.8	12.7
MSB 22	244.2	—	—
MSB 23	247.7	—	—
MSB 24	244.2	235.3	8.9
MSB 25	243.9	—	—
MSB 26	246.5	237.6	8.9
MSB 27	248.2	236.3	11.9
MSB 27A	243.6	230.2	13.4
MSB 28	244.1	231.2	12.9
MSB 29D	241.8	233.1	8.7
MSB 29DD	—	233.4	—
MSB 30C	243.5	231.5	12.0

Table 10 (cont.)

<u>Well</u>	Static Water Elevation (ft above msl)	Drawdown Water Elevation (ft above msl)	Drawdown (ft)
	<u>1Q85</u>	<u>1Q95</u>	
MSB 31C	246.0	235.9	10.1
MSB 32	226.5	225.6	0.9
MSB 33	220.2	219.2	1.0
MSB 34C	242.2	230.8	11.4
MSB 35D	-	243.5	-
MSB 36D	245.7	237.9	7.8
MSB 37D	242.5	233.0	9.5
MSB 38D	-	234.4	-
MSB 39D	244.7	232.8	11.9
MSB 40D	233.5	227.8	5.7
MSB 41D	241.9	241.0	0.9
MSB 42D	243.5	234.2	9.3
MSB 43D	242.2	232.2	10.0
MSB 43DD	-	232.1	-
MSB 44C	247.4	236.3	11.1
MSB 45C	243.6	-	-
MSB 46C	247.0	240.7	6.3
MSB 47D	-	234.3	-
MSB 49D	-	229.5	-
MSB 50D	-	203.1	-
MSB 51D	-	211.2	-
MSB 51DD	-	211.6	-
MSB 52D	-	239.4	-
MSB 53D	-	234.3	-
MSB 54D	-	233.7	-
MSB 55D	-	233.7	-
MSB 56D	-	222.0	-
MSB 57D	-	232.4	-
MSB 58D	-	232.3	-
MSB 59D	-	231.1	-
MSB 60D	-	231.3	-
MSB 61D	-	227.0	-
MSB 62D	-	230.3	-
MSB 63D	-	230.4	-
MSB 64D	-	227.9	-
MSB 65D	-	234.5	-
MSB 66D	-	232.1	-
MSB 67D	-	233.7	-
MSB 68D	-	234.5	-
MSB 69D	-	234.0	-
MSB 70D	-	222.1	-
MSB 74D	-	231.3	-
MSB 77D	-	234.7	-
MSB 78D	-	224.9	-
MSB 82D	-	233.7	-
MSB 83D	-	233.9	-
MSB 85D	-	233.6	-
MSB 88D	-	206.3	-
SRW 1	-	212.7	-
SRW 2	-	214.5	-
SRW 3A	-	213.9	-
SRW 4	-	213.5	-

Table 10 (cont.)

Well	Static Water Elevation (ft above msl) <u>1Q85</u>	Drawdown Water Elevation (ft above msl) <u>1Q95</u>	Drawdown (ft)
SRW 5	—	211.6	—
SRW 6	—	212.4	—
SRW 7	—	211.0	—
SRW 8	—	208.8	—
SRW 9	—	200.5	—
SRW 9A	204.9	200.4	4.5
SRW 9B	206.6	201.5	5.1
SRW 10	—	—	—
SRW 11	—	210.6	—
SRW 12A	199.3	196.4	2.9
SRW 12B	193.1	192.2	0.9
SRW 12C	200.6	199.7	0.9
SRW 13C	217.0	210.0	7.0
SRW 14C	221.3	—	—
SRW 15C	221.5	212.8	8.7
SRW 16C	225.7	215.8	9.9

Average Drawdown (ft) = 8.60

^a — = no data available.

Table 11. Summary of Water-Elevation Drawdowns in the Upper Lost Lake Aquifer Zone

Well	Static Water Elevation (ft above msl)	Drawdown Water Elevation (ft above msl)	Drawdown (ft)
	1Q85	1Q95	
ABP 3C	- ^a	198.8	-
ABP 8C	-	198.6	-
ABW 1	229.4	226.8	2.6
AC 1A	222.7	214.1	8.6
AC 2A	232.1	221.9	10.2
AC 3A	220.3	211.1	9.2
AMB 11B	-	224.4	-
AMB 18C	-	234.5	-
AMB 19C	-	232.5	-
ASB 2C	-	-	-
ASB 3C	-	-	-
ASB 6C	-	224.8	-
ASB 8C	229.4	224.6	4.8
ASB 9C	-	222.2	-
ASB 10C	-	-	-
MCB 5C	-	196.5	-
MCB 6C	-	197.0	-
MCB 7C	-	195.5	-
MSB 1C	-	217.5	-
MSB 1CC	-	219.5	-
MSB 2C	-	219.2	-
MSB 3C	-	220.5	-
MSB 4C	-	215.4	-
MSB 5C	-	224.2	-
MSB 6C	-	224.9	-
MSB 8C	-	221.3	-
MSB 11B	234.5	218.7	15.8
MSB 11C	237.0	221.2	15.8
MSB 12B	234.1	215.4	18.7
MSB 12C	236.6	224.2	12.4
MSB 13B	-	192.8	-
MSB 15A	235.4	221.7	13.7
MSB 16A	236.7	220.6	16.1
MSB 17A	227.8	217.9	9.9
MSB 18A	221.6	213.9	7.7
MSB 19B	223.6	218.5	5.1
MSB 20A	230.3	219.7	10.6
MSB 23B	239.2	225.4	13.8
MSB 24A	241.6	227.9	13.7
MSB 26A	238.5	225.0	13.5
MSB 27B	240.1	227.9	12.2
MSB 28A	236.2	224.8	11.4
MSB 29C	239.5	231.2	8.3
MSB 30CC	-	226.2	-
MSB 31CC	-	220.8	-
MSB 32C	-	218.0	-
MSB 33C	213.0	211.6	1.4
MSB 34B	240.6	228.2	12.4
MSB 35B	230.0	221.9	8.1
MSB 36C	223.0	216.0	7.0
MSB 37C	238.8	229.4	9.4

Table 11 (cont.)

Well	Static Water Elevation (ft above msl) <u>1Q85</u>	Drawdown Water Elevation (ft above msl) <u>1Q95</u>	Drawdown (ft)
MSB 39C	225.9	216.9	9.0
MSB 40C	210.7	205.7	5.0
MSB 42B	235.8	227.0	8.8
MSB 42C	244.7	232.6	12.1
MSB 43B	239.6	230.2	9.4
MSB 44B	235.4	226.3	9.1
MSB 45B	238.1	227.7	10.4
MSB 46B	235.3	—	—
MSB 47C	—	233.4	—
MSB 48D	—	233.2	—
MSB 50B	—	202.8	—
MSB 53C	—	224.4	—
MSB 55C	—	230.0	—
MSB 55HC	—	233.4	—
MSB 61C	—	224.9	—
MSB 62C	—	224.3	—
MSB 63C	—	221.7	—
MSB 64C	—	223.7	—
MSB 70C	—	218.6	—
MSB 74C	—	212.0	—
MSB 75C	—	210.9	—
MSB 76C	—	221.7	—
MSB 79C	—	211.3	—
MSB 87C	—	243.6	—
MSB 88C	—	205.2	—
MSB 89C	—	229.9	—
SRW 2B	216.0	209.1	6.9
SRW 14B	213.3	206.6	6.7
SRW 15B	217.7	210.7	7.0

Average Drawdown (ft) = 9.91

^a — = no data available.

Table 12. Summary of Water-Elevation Drawdowns in the Lower Lost Lake Aquifer Zone

<u>Well</u>	Static Water Elevation (ft above msl) <u>1Q85</u>	Drawdown Water Elevation (ft above msl) <u>1Q95</u>	Drawdown (ft)
AMB 4B	— ^a	225.8	—
AMB 7B	—	226.1	—
AMB 10B	—	224.6	—
ASB 2CR	—	224.4	—
ASB 3CR	—	224.0	—
ASB 5C	—	224.0	—
ASB 8B	225.2	221.8	3.4
ASB 9B	—	221.9	—
ASB 10CR	—	224.3	—
MSB 1B	—	209.3	—
MSB 2B	—	211.6	—
MSB 3B	—	—	—
MSB 4B	—	206.6	—
MSB 5B	—	211.0	—
MSB 6B	—	208.4	—
MSB 7B	—	209.0	—
MSB 8B	—	210.5	—
MSB 9A	225.8	210.4	15.4
MSB 10B	225.8	214.4	11.4
MSB 11A	226.0	213.2	12.8
MSB 12A	220.7	211.6	9.1
MSB 13A	220.2	211.0	9.2
MSB 14A	229.4	216.8	12.6
MSB 15AA	—	215.0	—
MSB 17BB	—	214.0	—
MSB 21A	232.6	222.0	10.6
MSB 21B	—	221.3	—
MSB 25A	231.9	219.9	12.0
MSB 26B	—	219.9	—
MSB 29B	233.7	225.4	8.3
MSB 30B	233.4	226.3	7.1
MSB 31B	230.2	220.8	9.4
MSB 32B	—	212.9	—
MSB 33B	210.3	208.6	1.7
MSB 36B	224.9	215.9	9.0
MSB 38B	—	217.6	—
MSB 38C	—	221.1	—
MSB 39B	222.5	213.4	9.1
MSB 40B	209.4	205.7	3.7
MSB 41C	222.4	219.3	3.1
MSB 43A	—	230.0	—
MSB 45A	224.7	217.9	6.8
MSB 47B	—	226.3	—
MSB 48C	—	225.5	—
MSB 49B	—	204.4	—
MSB 51B	—	205.6	—
MSB 52B	—	220.8	—
MSB 53B	—	223.5	—
MSB 54C	—	227.6	—
MSB 55C	—	230.0	—
MSB 62B	—	210.3	—

Table 12 (cont.)

<u>Well</u>	Static Water Elevation (ft above msl) <u>1Q85</u>	Drawdown Water Elevation (ft above msl) <u>1Q95</u>	Drawdown (ft)
MSB 63B	-	210.9	-
MSB 66C	-	229.7	-
MSB 67C	-	227.5	-
MSB 68C	-	225.8	-
MSB 69C	-	228.3	-
MSB 71B	-	217.9	-
MSB 72B	-	200.8	-
MSB 73B	-	203.0	-
MSB 74B	-	212.1	-
MSB 75B	-	211.5	-
MSB 77C	-	225.2	-
MSB 79B	-	209.1	-
MSB 81B	-	221.4	-
MSB 82C	-	229.0	-
MSB 83C	-	225.0	-
MSB 84C	-	230.4	-
MSB 85C	-	225.7	-
MSB 86C	-	226.0	-
MSB 87B	-	219.8	-
MSB 89B	-	208.6	-
SRW 1BB	-	208.7	-
SRW 3BB	-	209.9	-
SRW 4BB	-	208.5	-
SRW 8BB	-	-	-
SRW 10BB	-	207.7	-
SRW 11BB	-	207.1	-
SRW 13A	208.4	202.9	5.5
SRW 16A	224.5	214.6	9.9
SRW 16B	224.7	215.3	9.4
SRW 17BB	-	213.1	-
SRW 17C	-	213.3	-
SRW 17D	-	-	-

Average Drawdown (ft) = 8.55

^a - = no data available.

Table 13. Summary of Water-Elevation Drawdowns in the Middle Sand Aquifer Zone of the CBCU

<u>Well</u>	Static Water Elevation (ft above msl) <u>1Q85</u>	Drawdown Water Elevation (ft above msl) <u>1Q95</u>	Drawdown (ft)
AMB 4A	— ^a	220.4	—
AMB 7A	—	220.4	—
AMB 10A	—	219.5	—
AMB 13AR	—	220.3	—
AMB 17A	—	220.4	—
AMB 18A	—	220.2	—
ASB 6AA	—	219.8	—
ASB 8A	—	220.4	—
MSB 10A	223.8	211.8	12.0
MSB 12TA	—	194.1	—
MSB 19A	219.5	216.0	3.5
MSB 29A	—	221.2	—
MSB 30AA	—	224.8	—
MSB 33A	207.3	205.8	1.5
MSB 34A	226.4	220.2	6.2
MSB 34TA	—	204.0	—
MSB 35A	223.0	218.3	4.7
MSB 36A	219.1	211.7	7.4
MSB 37B	226.4	220.7	5.7
MSB 39A	219.0	210.8	8.2
MSB 40A	207.1	204.0	3.1
MSB 41A	221.5	218.6	2.9
MSB 41B	221.6	218.8	2.8
MSB 42A	226.3	220.7	5.6
MSB 44A	224.7	219.3	5.4
MSB 46A	225.0	217.0	8.0
MSB 47BB	—	221.0	—
MSB 48A	—	223.7	—
MSB 48B	—	225.0	—
MSB 49A	—	198.8	—
MSB 54B	—	223.3	—
MSB 55B	—	223.0	—
MSB 64B	—	210.1	—
MSB 66B	—	220.6	—
MSB 67B	—	220.3	—
MSB 68B	—	220.8	—
MSB 69B	—	222.2	—
MSB 77B	—	223.2	—
MSB 82A	—	221.2	—
MSB 82B	—	221.5	—
MSB 83B	—	223.0	—
MSB 84A	—	194.1	—
MSB 88B	—	202.2	—
SRW 2A	214.8	207.8	7.0
SRW 13B	210.7	204.7	6.0
SRW 14A	211.4	204.8	6.6

Table 13 (cont.)

<u>Well</u>	Static Water Elevation (ft above msl)	Drawdown Water Elevation (ft above msl)	Drawdown (ft)
	<u>1Q85</u>	<u>1Q95</u>	
SRW 15A	217.4	210.5	6.9

Average Drawdown (ft) = 5.75

^a - = no data available.

Table 14. 1994 Summary of Downtime for the M-1 Air Stripper, the A-1 Air Stripper, and the Integrated Demonstration Vadose Zone Unit

M-1 AIR STRIPPER

<u>Month</u>	<u>Hours</u>	<u>Description</u>
January	36.9	Equipment maintenance and repair, inclement weather, training
February	7.4	Maintenance
March	28.3	Equipment repair, maintenance, power outage
April	29.1	Preventive maintenance
May	1.9	Housekeeping, inclement weather
June	12.8	Inclement weather, preventive maintenance, training
July	13.6	Inclement weather, instrument air compressor problem, power outage, preventive maintenance
August	172.8	Instrument air compressor problem
September	25.7	Equipment repair, preventive maintenance
October	7.9	Preventive maintenance
November	1.9	Flow restrictions
December	<u>87.1</u>	Equipment repair, flow restriction, preventive maintenance
TOTAL	425.4	

A-1 AIR STRIPPER

<u>Month</u>	<u>Hours</u>	<u>Description</u>
January	98.5	Equipment repair, inclement weather, maintenance, training
February	0.0	
March	201.2	Equipment repair, maintenance
April	2.4	Maintenance
May	36.8	Equipment repair, training
June	161.9	Equipment repair, power outage, preventive maintenance
July	43.8	Instrument air compressor problem
August	202.9	Equipment repair
September	289.7	Equipment repair, preventive maintenance
October	0.0	
November	0.0	
December	<u>17.8</u>	Preventive maintenance
TOTAL	1,055.0	

Table 14. 1994 Summary of Downtime for the M-1 Air Stripper, the A-1 Air Stripper, and the Integrated Demonstration Vadose Zone Unit (cont.)

INTEGRATED DEMONSTRATION VADOSE ZONE UNIT

<u>Month</u>	<u>Hours</u>	<u>Description</u>
January	NA ^a	
February	NA	
March	NA	
April	NA	
May	NA	
June	NA	
July	NA	
August	97.0	Startup requiring temperature equilibrium, system electrical analysis
September	35.0	Power outage, startup requiring temperature equilibrium
October	469.5	Equipment malfunctions
November	720.0 ^b	Equipment malfunctions
December	<u>744.0</u>	Equipment malfunctions
TOTAL	2,065.5	

^aNA = Not applicable. The Integrated Demonstration Vadose Zone Unit (IDU) began operating in August 1994.

^bThe IDU did not operate during November and December.

Table 15. 1994 Operating and Performance Summary of the M-1 Air Stripper

<u>Operation Parameter</u>	<u>January</u>	<u>February</u>	<u>March</u>	<u>April</u>	<u>May</u>	<u>June</u>	<u>July</u>
Operating Time (hours)	707.1	664.6	715.7	690.9	742.1	707.2	730.4
Downtime (hours)	36.9	7.4	28.3	29.1	1.9	12.8	13.6
Average Utility (%)	95.0	98.9	96.2	96.0	99.7	98.2	98.2
Throughput (gal)	19,620,840	18,143,530	19,502,710	18,899,360	20,265,940	19,098,050	19,615,520
Average Water Feed Rate (gpm)	462	455	454	456	455	450	448
Average Air Feed Rate (cfm)	2,500	2,500	2,500	2,500	2,500	2,500	2,500
Total Solvent Removed (lbs)	1,850	1,290	1,592	1,574	1,627	1,420	1,360
Emission Rate (lbs/hr)	2.62	1.94	2.22	2.28	2.19	2.01	1.86
Average Concentration ($\mu\text{g/L}$)							
<u>Stripper Influent</u>							
Tetrachloroethylene	4,470	2,873	3,615	3,628	3,484	3,300 ^a	3,198
Trichloroethylene	6,843	5,655	6,176	6,360	6,147	5,618 ^a	5,118
Total	11,313	8,528	9,791	9,988	9,631	8,918 ^a	8,316
<u>Stripper Effluent</u>							
Tetrachloroethylene	<2.5	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Trichloroethylene	<5.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Total	<7.5	<2.0	<2.0	<2.0	<2.0	<2.0	<2.0

Table 15. 1994 Operating and Performance Summary of the M-1 Air Stripper (cont.)

<u>Operation Parameter</u>	<u>August</u>	<u>September</u>	<u>October</u>	<u>November</u>	<u>December</u>	<u>Yearly Total/Average</u>
Operating Time (hours)	571.2	694.3	736.1	718.1	656.9	8,334.6
Downtime (hours)	172.8	25.7	7.9	1.9	87.1	425.4
Average Utility (%)	76.8	96.4	98.9	99.7	88.3	95.2
Throughput (gal)	15,118,000	18,231,310	19,248,980	17,933,370	11,909,790	217,587,400
Average Water Feed Rate (gpm)	441	438	436	416	302	434
Average Air Feed Rate (cfm)	2,501	2,500	2,500	2,500	2,500	2,500
Total Solvent Removed (lbs)	1,424	1,280	1,719	1,444	823	17,403
Emission Rate (lbs/hr)	2.49	1.84	2.34	2.01	1.25	2.09
<u>Average Concentration (µg/L)</u>						
<u>Stripper Influent</u>						
Tetrachloroethylene	4,673 ^{b,c}	3,660 ^b	4,508 ^b	3,693	3,180	3,690
Trichloroethylene	6,620 ^{b,c}	4,758 ^b	6,203 ^b	5,962	5,104	5,880
Total	11,293	8,418	10,711	9,655	8,284	9,571
<u>Stripper Effluent</u>						
Tetrachloroethylene	<1.0 ^b	<1.0 ^b	<1.0 ^b	<1.0	<1.0	<1.1 ^d
Trichloroethylene	<1.0 ^b	<1.0 ^b	<1.0 ^b	<1.0	<1.0	<1.3
Total	<2.0	<2.0	<2.0	<2.0	<2.0	<2.5

^aThese numbers are based on averages that include estimated values.

^bThis value is an average including one or more results obtained from unpreserved or improperly preserved samples. Data may not be accurate.

^cThis value is an average including one or more results that are estimated because quantitation in the sample or in associated quality control samples did not meet specifications, that may underestimate the true value due to analytical bias, and whose sample exceeded holding time.

^dThe full detection limit is used to calculate the yearly averages.

Table 16. 1985-1994 Operating and Performance Summary of the M-1 Air Stripper

<u>Operation Parameter</u>	<u>1985</u>	<u>1986</u>	<u>1987</u>	<u>1988</u>	<u>1989</u>	<u>1990</u>	<u>1991</u>	<u>1992</u>	<u>1993</u>	<u>1994</u>	<u>Cumulative Total/Average</u>
Average Operating Time (hours)	2,339.5	8,419.3	8,388.8	8,632.2	8,194.2	8,313.1	8,133.0	8,558.5	8,444.2	8,334.6	77,757.4
Downtime (hours)	96.5	652.8	419.2	151.7	566.2	446.9	627.0	229.7	315.8	425.4	3,931.2
Average Utility (%)	96.0	92.8	95.2	98.3	93.5	94.9	92.8	97.4	96.4	95.2	95.3
Throughput (millions of gal)	67.46	186.70	188.96	199.73	189.75	226.67	238.05	257.56	243.01	217.59	2,015.48
Average Water Feed Rate (gpm)	400	370	375	375	386	454	501	502	479	434	427.6
Average Air Feed Rate (cfm)	2,000	2,000	2,000	2,000	2,000	2,167	2,500	2,500	2,489	2,500	2,215.6
Total Solvent Removed (lbs)	19,523	48,756	44,346	36,790	26,024	28,323	24,581	25,445	19,505	17,403	290,696
Emission Rate (lbs/hr)	8.34	5.79	5.29	4.26	3.18	3.41	3.02	2.97	2.31	2.09	4.07
Average Concentration ($\mu\text{g/L}$)											
<u>Stripper Influent</u>											
Tetrachloroethylene	11,225	9,896	7,932	6,964	4,918	4,684	4,039	3,981	3,414	3,690	6,074
Trichloroethylene	25,200	21,239	20,347	15,141	11,570	10,367	8,372	7,813	6,212	5,880	13,214
Total	36,425	31,135	28,279	22,105	16,488	15,051	12,411	11,794	9,626	9,571	19,289
<u>Stripper Effluent</u>											
Tetrachloroethylene	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.1	<1.0 ^a
Trichloroethylene	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.1	<1.3	<1.0
Total	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<2.1	<2.5	<1.3

^aHalf of the detection limit was used to calculate the cumulative averages through the first quarter of 1993. Since the second quarter of 1993, the full detection limit has been used to calculate the cumulative averages.

Table 17. 1994 Operating and Performance Summary of the A-1 Air Stripper

<u>Operation Parameter</u>	<u>January</u>	<u>February</u>	<u>March</u>	<u>April</u>	<u>May</u>	<u>June</u>	<u>July</u>
Operating Time (hours)	645.5	672	542.8	717.6	707.2	558.1	700.2
Downtime (hours)	98.5	0	201.2	2.4	36.8	161.9	43.8
Average Utility (%)	86.8	100.0	73.0	99.7	95.1	77.5	94.1
Throughput (gal)	2,050,384	2,213,802	1,783,984	2,343,290	2,295,633	1,807,823	2,215,201
Average Water Feed Rate (gpm)	53	55	55	54	54	54	53
Average Air Feed Rate (cfm)	351	350	350	351	350	350	350
Total Solvent Removed (lbs)	48	44	40	50	51	43	44
Emission Rate (lbs/hr)	0.07	0.07	0.07	0.07	0.07	0.08	0.06
Average Concentration ($\mu\text{g/L}$)							
<u>Stripper Influent</u>							
Tetrachloroethylene	< 120	< 175	< 75	< 75	< 65	< 70	< 68 ^a
Trichloroethylene	2,665	2,228	2,613	2,505	2,590	2,782	< 2,308 ^a
Total	< 2,785	< 2,403	< 2,688	< 2,580	< 2,655	< 2,852	< 2,376
<u>Stripper Effluent</u>							
Tetrachloroethylene	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0 ^a
Trichloroethylene	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0 ^a
Total	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0

Table 17. 1994 Operating and Performance Summary of the A-1 Air Stripper (cont.)

<u>Operation Parameter</u>	<u>August</u>	<u>September</u>	<u>October</u>	<u>November</u>	<u>December</u>	<u>Yearly Total/Average</u>
Operating Time (hours)	541.1	430.3	744.0	720.0	726.2	7,705.0
Downtime (hours)	202.9	289.7	0.0	0.0	17.8	1,055.0
Average Utility (%)	72.7	59.8	100.0	100.0	97.6	88.0
Throughput (gal)	1,765,142	1,392,513	2,448,802	2,372,951	2,406,307	25,095,832
Average Water Feed Rate (gpm)	54	54	55	55	55	54
Average Air Feed Rate (cfm)	350	350	350	350	350	350
Total Solvent Removed (lbs)	40	29	55	47	43	534
Emission Rate (lbs/hr)	0.07	0.07	0.07	0.07	0.06	0.07
<u>Average Concentration (µg/L)</u>						
<u>Stripper Influent</u>						
Tetrachloroethylene	<68 ^a	<48 ^{a,b,c}	<75 ^a	<75	<50	<80 ^a
Trichloroethylene	<2,670 ^a	<2,413 ^a	<2,624 ^a	2,292	2,118	<2,484
Total	<2,738	<2,461	<2,699	<2,367	<2,168	<2,564
<u>Stripper Effluent</u>						
Tetrachloroethylene	<1.0 ^a	<1.0 ^a	<1.0 ^{a,b,d}	<1.0 ^{b,d}	<1.0	<1.0
Trichloroethylene	<1.0 ^a	<1.0 ^a	<1.0 ^{a,b,d}	<1.0 ^{b,d}	<1.0	<1.0
Total	<2.0	<2.0	<2.0	<2.0	<2.0	<2.0

^aThis value is an average including one or more results obtained from unpreserved or improperly preserved samples. Data may not be accurate.

^bThis value is an average including one or more results that are estimated because quantitation in the sample or in associated quality control samples did not meet specifications.

^cThis value is an average including one or more results that may underestimate the true value due to analytical bias and whose sample exceeded holding time.

^dAn analytical factor caused poor precision; the associated result may be of high variability.

^eThe full detection limit is used to calculate cumulative averages.

Table 18. 1992-1994 Operating and Performance Summary of the A-1 Air Stripper

<u>Operation Parameter</u>	<u>1992</u>	<u>1993</u>	<u>1994</u>	<u>Cumulative Total/Average Since 3/92</u>
Operating Time (hours)	6,671.3	8,028.7	7,705.0	22,405.0
Downtime (hours)	145.4	731.3	1,055.0	1,931.7
Average Utility (%)	98.0	91.7	88.0	92.6
Throughput (gal)	21,727,472	25,699,542	25,095,832	72,522,846
Average Water Feed Rate (gpm)	54	53	54	54
Average Air Feed Rate (cfm)	350	349	350	350
Total Solvent Removed (lbs)	524	588	534	1,646
Emission Rate (lbs/hr)	0.08	0.07	0.07	0.07
<u>Average Concentration (µg/L)</u>				
<u>Stripper Influent</u>				
Tetrachloroethylene	<203	<74	<80	<119
Trichloroethylene	3,198	2,670	<2,484	<2,784
Total	<3,401	<2,744	<2,564	<2,903 ^a
<u>Stripper Effluent</u>				
Tetrachloroethylene	<1.3	<1.1	<1.0	<1.1
Trichloroethylene	<1.3	<1.2	<1.0	<1.2
Total	<2.6	<2.3	<2.0	<2.3

^aHalf the detection limit was used to calculate the cumulative averages through the first quarter of 1993. Since the second quarter of 1993, the full detection limit has been used to calculate the cumulative averages.

Table 19. 1994 Operating and Performance Summary of the Integrated Demonstration Vadose Zone Unit

<u>Operation Parameter</u>	<u>August^a</u>	<u>September</u>	<u>October</u>	<u>November^b</u>	<u>December</u>	<u>Yearly Total/Average</u>
Operating Time (hours)	647.0	685.0	274.5	0.0	0.0	1,606.5
Downtime (hours)	97.0	35.0	469.5	720.0	744.0	2,065.5
Percent Utility (%)	87.0	95.1	36.9	0.0	0.0	43.8
Average Air Feed Rate (cfm)	247.10	240.00	233.06	0.00	0.00	144.03
Total Solvent Removed (lbs)	778.0	879.1	445.7	0.0	0.0	2,102.8
Total Solvent Destroyed (lbs)	752.8	798.5	416.4	0.0	0.0	1,967.7
Emission Rate (lbs/hr)						
Hydrogen chloride	0.99	1.01	1.32	0.00	0.00	0.66
Tetrachloroethylene	0.03	0.11	0.09	0.00	0.00	0.05
Trichloroethylene	0.01	0.01	0.01	0.00	0.00	0.01
Average Concentration (ppmv)						
<u>Influent</u>						
Tetrachloroethylene	91.8	152.4	202.7	0.0	0.0	89.4
Trichloroethylene	122.1	69.1	84.8	0.0	0.0	55.2
Total	213.9	221.5	287.5	0.0	0.0	144.6
<u>Effluent</u>						
Tetrachloroethylene	5.0	17.1	15.5	0.0	0.0	7.5
Trichloroethylene	1.4	2.4	2.8	0.0	0.0	1.3
Total	6.4	19.5	18.3	0.0	0.0	8.8

^aThe Integrated Demonstration Vadose Zone Unit (IDU) began operating in August 1994.

^bThe IDU did not operate during November and December.

Table 20. 1994 Summary of Volume Pumped and Average Flow from Individual Recovery Wells

Well	January	Cumulative	Average	Well	February	Cumulative	Average	Well	March	Cumulative	Average	Well
	Monthly Volume (gal)	Volume since 4/85 (gal)	Flow Rate (gpm)	Operation (hours)	Monthly Volume (gal)	Volume since 4/85 (gal)	Flow Rate (gpm)	Operation (hours)	Monthly Volume (gal)	Volume since 4/85 (gal)	Flow Rate (gpm)	Operation (hours)
RWM 1	953,402	94,139,325	22	707 ^a	865,830	95,005,155	22	662 ^a	891,046	95,896,201	21	703
RWM 2	993,151	80,143,590	23	707	922,624	81,066,214	23	658	1,000,601	82,066,815	23	714 ^a
RWM 3	2,672,699	212,988,803	63	707	2,461,448	215,450,251	63	656 ^a	2,687,036	218,137,287	63	716 ^a
RWM 4	1,937,075	126,109,651	46	705	1,831,313	127,940,964	46	661 ^a	1,932,599	129,873,563	46	703
RWM 5	2,007,158	118,768,959	47	707	1,883,046	120,652,005	47	661 ^a	2,034,917	122,686,922	47	714
RWM 6	2,934,449	188,835,976	69	707 ^a	2,760,314	191,596,290	70	659 ^a	2,951,764	194,548,054	69	708
RWM 7	1,701,692	113,864,972	40	707 ^a	1,608,060	115,473,032	41	659 ^a	1,711,498	117,184,530	40	708
RWM 8	1,948,008	124,974,143	46	706	1,857,260	126,831,403	47	665	1,946,693	128,778,096	46	703
RWM 9	2,085,554	149,689,766	49	707 ^a	1,967,479	151,657,245	49	665 ^a	2,094,072	153,751,317	49	716 ^a
RWM 10	0	162,250,933	0	0	0	162,250,933	0	0	0	162,250,933	0	0
RWM 11	3,079,223	218,462,383	73	707 ^a	2,897,211	221,359,594	73	661 ^a	3,089,437	224,449,031	73	708 ^a
RWM 12	2,050,384	47,351,064	53	646	2,213,802	49,564,866	55	672	1,783,984	51,348,850	55	543 ^a

Table 20. 1994 Summary of Volume Pumped and Average Flow from Individual Recovery Wells (cont.)

Well	April				May				June			
	Monthly Volume (gal)	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)	Monthly Volume (gal)	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)	Monthly Volume (gal)	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)
RWM 1	895,943	96,792,144	22	690	935,082	97,727,226	21	742	866,934	98,594,160	21	697
RWM 2	961,083	83,027,898	23	690	1,033,910	84,061,808	23	742	962,860 ^b	85,024,668	23	696
RWM 3	2,598,073	220,735,360	63	691 ^a	2,812,401	223,547,761	63	742 ^a	2,556,793	226,104,554	63	681 ^a
RWM 4	1,898,611	131,772,174	46	691	2,060,008	133,832,182	46	742	1,917,569	135,749,751	46	698
RWM 5	1,974,723	124,661,645	48	691	2,139,110	126,800,755	48	742	1,985,497	128,786,252	48	696
RWM 6	2,864,631	197,412,685	69	690	3,069,192	200,481,877	69	742	2,886,884	203,368,761	69	697
RWM 7	1,677,562	118,862,092	40	691	1,754,974	120,617,066	39	742	1,684,137	122,301,203	40	698
RWM 8	1,912,635	130,690,731	46	690	2,078,897	132,769,628	47	742	1,952,671	134,722,299	47	698
RWM 9	2,042,990	155,794,307	49	691 ^a	2,219,038	158,013,345	50	742 ^a	2,064,818	160,078,163	49	707 ^a
RWM 10	0	162,250,933	0	0	0	162,250,933	0	0	0	162,250,933	0	0
RWM 11	3,011,477	227,460,508	73	691	3,268,968	230,729,476	73	742	3,047,102	233,776,578	73	697
RWM 12	2,343,290	53,692,140	54	718	2,295,633	55,987,773	54	707	1,807,823	57,795,596	54	558

Table 20. 1994 Summary of Volume Pumped and Average Flow from Individual Recovery Wells (cont.)

Well	July	Cumulative	Average	Well	August	Cumulative	Average	Well	September	Cumulative	Average	Well
	Monthly Volume (gal)	Volume since 4/85 (gal)	Flow Rate (gpm)	Operation (hours)	Monthly Volume (gal)	Volume since 4/85 (gal)	Flow Rate (gpm)	Operation (hours)	Monthly Volume (gal)	Volume since 4/85 (gal)	Flow Rate (gpm)	Operation (hours)
RWM 1	887,681	99,481,841	20	727	721,887 ^b	100,203,728	21	560 ^a	719,605 ^b	100,923,333	22	550 ^a
RWM 2	1,000,288 ^b	86,024,956	23	725	773,519 ^b	86,798,475	23	557 ^a	946,879 ^b	87,745,354	23	683 ^a
RWM 3	2,652,438	228,756,992	61	730 ^a	1,923,379 ^b	230,680,371	56	571 ^a	2,471,374 ^b	233,151,745	60	686 ^a
RWM 4	1,949,642	137,699,393	45	730	1,457,144 ^b	139,156,537	43	560 ^a	1,867,014 ^b	141,023,551	45	694 ^a
RWM 5	2,053,946	130,840,198	47	730	1,442,236 ^b	132,282,434	46	527 ^a	1,962,762 ^b	134,245,196	47	694 ^a
RWM 6	2,915,819	206,284,580	67	730	2,167,244 ^b	208,451,824	65	559 ^a	2,798,225 ^b	211,250,049	67	694 ^a
RWM 7	1,676,448	123,977,651	38	729	1,181,869 ^b	125,159,520	35	560 ^a	1,648,680 ^b	126,808,200	40	694 ^a
RWM 8	1,943,183	136,665,482	44	730	1,009,885 ^b	137,675,367	43	391 ^a	1,851,480 ^b	139,526,847	44	694 ^a
RWM 9	2,118,818	162,196,981	48	730 ^a	1,135,236 ^b	163,332,217	46	411 ^a	0	163,332,217	0	0
RWM 10	297,098 ^b	162,548,031	34	148 ^a	2,877,840 ^b	165,425,871	84	571 ^a	2,102,660 ^b	167,528,531	66	531 ^a
RWM 11	3,094,682	236,871,260	71	730	2,298,261 ^b	239,169,521	69	558 ^a	3,017,084 ^b	242,186,605	72	694 ^a
RWM 12	2,215,201	60,010,797	53	700	1,765,142 ^b	61,775,939	54	541	1,392,513 ^b	63,168,452	54	430

Table 20. 1994 Summary of Volume Pumped and Average Flow from Individual Recovery Wells (cont.)

Well	October	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)	November	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)	December	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)
	Monthly Volume (gal)				Monthly Volume (gal)				Monthly Volume (gal)			
RWM 1	888,640	101,811,973	20	728	835,990	102,647,963	20	695	7,680 ^b	102,655,643	21	6 ^a
RWM 2	1,003,539	88,748,893	23	728	978,439	89,727,332	23	715	913,276	90,640,608	23	657
RWM 3	2,647,943	235,799,688	62	709	2,657,653	238,457,341	64	692 ^a	2,660,470	241,117,811	68	657 ^a
RWM 4	1,972,485	142,996,036	45	733	1,980,784	144,976,820	46	718	17,342 ^b	144,994,162	48	6 ^a
RWM 5	2,062,081	136,307,277	47	733 ^a	2,054,707	138,361,984	48	712 ^a	1,959,394	140,321,378	50	657
RWM 6	2,947,272	214,197,321	67	736	2,989,635	217,186,956	70	717	2,878,352	220,065,308	73	657
RWM 7	1,722,252	128,530,452	39	736	1,749,055	130,279,507	41	717	1,673,309	131,952,816	42	657
RWM 8	1,489,244	141,016,091	44	566	0	141,016,091	0	0	0	141,016,091	0	0
RWM 9	0	163,332,217	0	0	0	163,332,217	0	0	0	163,332,217	0	0
RWM 10	2,030,155	169,558,686	60	564 ^a	1,807,153	171,365,839	45	666 ^a	25,432 ^b	171,391,271	71	6 ^a
RWM 11	3,239,204	245,425,809	73	736	3,166,451	248,592,260	74	717	3,093,175	251,685,435	78	657
RWM 12	2,448,802	65,617,254	55	744	2,372,951	67,990,205	55	720	2,406,307	70,396,512	55	726

^aOperating hours are partial estimates due to failed totalizers. Estimates are based on flow rate and throughput.

^bMonthly volumes are partial estimates due to failed totalizers. Estimates are based on flow rate and time.

Table 21. 1994 Summary of Tetrachloroethylene and Trichloroethylene Concentrations

Well	January <u>Solvent Concentrations</u>			February <u>Solvent Concentrations</u>			March <u>Solvent Concentrations</u>			April <u>Solvent Concentrations</u>		
	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)
RWM 1	N ^a	N	N	20,000	40,800	60,800	N	N	N	21,000	38,700	59,700
RWM 2	N	N	N	8,400	14,700	23,100	N	N	N	11,200	16,600	27,800
RWM 3	N	N	N	4,380	11,500	15,880	N	N	N	3,200	9,280	12,480
RWM 4	N	N	N	975	6,850	7,825	N	N	N	11 ^c	70 ^c	81
RWM 5	N	N	N	1,210	1,670	2,880	N	N	N	995	1,470	2,465
RWM 6	N	N	N	7,050	6,780	13,830	N	N	N	5,710	5,610	11,320
RWM 7	N	N	N	7,000	7,150	14,150	N	N	N	5,650	6,250	11,900
RWM 8	N	N	N	525	950	1,475	N	N	N	318	540	858
RWM 9	N	N	N	7	163	170	N	N	N	<10	149	<159
RWM 10	N	N	N	NA ^b	NA	NA	N	N	N	NA	NA	NA
RWM 11	N	N	N	270	3,090	3,360	N	N	N	205	2,360	2,565
RWM 12	N	N	N	<100	2,310	<2,410	N	N	N	<100	2,520	<2,620

Table 21. 1994 Summary of Tetrachloroethylene and Trichloroethylene Concentrations (cont.)

Well	May Solvent Concentrations			June Solvent Concentrations			July Solvent Concentrations			August Solvent Concentrations		
	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)
RWM 1	17,700	37,900	55,600	16,600	33,700 ^c	50,300	18,500	31,900	50,400	17,600 ^c	37,250 ^c	54,850
RWM 2	10,400	16,800	27,200	8,700	16,700	25,400	10,400	14,000	24,400	10,600	16,700	27,300
RWM 3	2,600	8,950	11,550	2,650	9,230	11,880	2,680 ^o	7,550 ^o	10,230	3,330	9,550	12,880
RWM 4	1,050	7,330	8,380	880	6,020	6,900	825	5,600	6,425	1,000	7,060	8,060
RWM 5	1,160	1,660	2,820	1,030	1,560 ^c	2,590	960	1,330	2,290	1,120	1,670	2,790
RWM 6	7,080	6,540	13,620	6,300	6,150	12,450	6,550	5,230	11,780	6,580	6,420	13,000
RWM 7	6,180	6,700	12,880	6,280	6,940	13,220	6,480	5,830	12,310	6,130	7,010	13,140
RWM 8	550	1,000	1,550	520	930	1,450	525	843	1,368	1,110 ^o	1,820 ^o	2,930
RWM 9	8 ^d	162	170	6	165	171	7 ^f	149	156	<5	141	<146
RWM 10	NA	NA	NA	NA	NA	NA	NA	NA	NA	10,200	4,140	14,340
RWM 11	200	2,190	2,390	430	4,870	5,300	180	2,080	2,260	160 ^f	1,990	2,150
RWM 12	<50	2,530	<2,580	<50	2,710	<2,760	<50	2,300	<2,350	<100	2,300	<2,400

Table 21. 1994 Summary of Tetrachloroethylene and Trichloroethylene Concentrations (cont.)

Well	September Solvent Concentrations			October Solvent Concentrations			November Solvent Concentrations			December Solvent Concentrations		
	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)
RWM 1	10,800 ^o	27,800 ^{c,o}	38,600	16,900	38,600 ^c	55,500	16,600 ^c	37,350 ^c	53,950	NA	NA	NA
RWM 2	8,950 ^o	14,800 ^o	23,750	12,200	17,400	29,600	13,700	19,100	32,800	10,600	15,300	25,900
RWM 3	2,250 ^o	6,950 ^o	9,200	2,290	6,640	8,930	3,250	8,850	12,100	4,530	9,050	13,580
RWM 4	700 ^o	5,450 ^o	6,150	1,080	6,780	7,860	1,070	6,570	7,640	NA	NA	NA
RWM 5	863 ^o	1,270 ^{c,o}	2,133	899	1,330	2,229	505	1,023 ^c	1,528	1,110	941	2,051
RWM 6	5,520 ^o	4,960 ^o	10,480	6,680	6,040	12,720	6,030	5,450	11,480	5,320	5,100	10,420
RWM 7	6,010 ^o	6,260 ^o	12,270	6,880	7,060	13,940	6,630	7,120	13,750	5,580	6,115 ^c	11,695
RWM 8	489 ^o	895 ^o	1,384	589	1,120	1,709	NA	NA	NA	NA	NA	NA
RWM 9	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
RWM 10	7,090 ^o	4,020 ^o	11,110	8,970	5,360	14,330	7,420	5,160	12,580	NA	NA	NA
RWM 11	170 ^o	1,850 ^o	2,020	200	2,310	2,510	390	4,460	4,850	115	898	1,013
RWM 12	50 ^o	2,710 ^o	<2,760	<50	2,430	<2,480	<50	2,600	<2,650	<50	2,450	<2,500

Table 21. 1994 Summary of Tetrachloroethylene and Trichloroethylene Concentrations (cont.)

Well	Yearly Average Solvent Concentrations		
	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)
RWM 1	17,300	36,000	53,300
RWM 2	10,515	16,210	26,725
RWM 3	3,116	8,755	11,871
RWM 4	843	5,748	6,591
RWM 5	985	1,392	2,377
RWM 6	6,282	5,828	12,110
RWM 7	6,282	6,644	12,926
RWM 8	578	1,012	1,590
RWM 9	<7	155	<162
RWM 10	8,420	4,670	13,090
RWM 11	232	2,610	2,842
RWM 12	<65	2,486	<2,551

^aN = No measurement. WSRC missed two months (January and March) of first quarter 1994 analytical sampling at the 12 recovery wells due to scheduling error.

^bNA = Not applicable.

^cThis value represents an average of monthly stripper influent analyses.

^dThis number represents an estimated value.

^eThis result was obtained from an unpreserved or improperly preserved sample. Data may not be accurate.

^fThis value is estimated because quantitation in the sample or in associated quality control samples did not meet specifications. Also, an analytical factor caused poor precision, and the associated result may be of high variability.

Table 22. Summary of Downtime for the M-1 Air Stripper, the A-1 Air Stripper, and the Integrated Demonstration Vadose Zone Unit

M-1 AIR STRIPPER

<u>Month</u>	<u>Hours</u>	<u>Description</u>
January	60.8	Equipment repair, lightning damage, preventive maintenance
February	42.9	Cold weather, equipment failure
March	<u>12.9</u>	Cold weather, equipment failure, preventive maintenance
TOTAL	116.6	

A-1 AIR STRIPPER

<u>Month</u>	<u>Hours</u>	<u>Description</u>
January	30.6	Equipment failure, lightning damage, preventive maintenance
February	554.1	Equipment failure
March	<u>8.3</u>	Equipment failure
TOTAL	593.0	

INTEGRATED DEMONSTRATION VADOSE ZONE UNIT

<u>Month</u>	<u>Hours</u>	<u>Description</u>
January	470.6	Equipment failure, lightning damage
February ^a	672.0	
March	<u>744.0</u>	
TOTAL	1,886.6	

^aThe Integrated Demonstration Vadose Zone Unit did not operate during February and March.

Table 23. Summary of Monthly Operation and Performance of the M-1 Air Stripper

<u>Operation Parameter</u>	<u>January</u>	<u>February</u>	<u>March</u>	<u>Quarterly Results</u>
Operating Time (hours)	683.2	629.1	731.1	2,043.4
Downtime (hours)	60.8	42.9	12.9	116.6
Percent Utility (%)	91.8	93.6	98.3	94.6
Throughput (gal)	11,521,800	9,493,920	15,717,810	36,733,530
Water Feed Rate (gpm)	281	252	358	297
Average Air Feed Rate (cfm)	2,500	2,500	2,500	2,500
Total Solvent Removed (lbs)	785	596	1,544	2,925
Emission Rate (lbs/hr)	1.15	0.95	2.11	1.40
<u>Average Concentration ($\mu\text{g/L}$)</u>				
<u>Stripper Influent</u>				
Tetrachloroethylene	3,031 ^a	2,775	4,602 ^b	3,469
Trichloroethylene	5,144 ^a	4,755	7,180 ^b	5,693
Total	8,175	7,530	11,782	9,162
<u>Stripper Effluent</u>				
Tetrachloroethylene	< 1.67 ^c	< 1.67	< 1.67	< 1.67 ^d
Trichloroethylene	< 1.67 ^{a,c}	< 1.67	< 1.67	< 1.67
Total	< 3.34	< 3.34	< 3.34	< 3.34

^aThis value is an average including one or more results obtained from unpreserved or improperly preserved samples. Data may not be accurate.

^b Sample held beyond the normal holding time. The analytical result is an estimated quantity. The actual value of the analysis is not known, but is known to be greater than the value shown.

^cThis value is an average including one or more results for which surrogate spike recoveries are out of specification.

^dQuarterly averages including detection limit values are for full detection limits.

Table 24. Summary of Monthly Operation and Performance of the A-1 Air Stripper

<u>Operation Parameter</u>	<u>January</u>	<u>February</u>	<u>March</u>	<u>Quarterly Results</u>
Operating Time (hours)	713.4	117.9	735.7	1,567.0
Downtime (hours)	30.6	554.1	8.3	593.0
Percent Utility (%)	95.9	17.5	98.9	72.5
Throughput (gal)	2,344,493	389,964	2,209,975	4,944,432
Water Feed Rate (gpm)	55	55	50	53
Average Air Feed Rate (cfm)	350	350	350	350
Total Solvent Removed (lbs)	47	15	48	110
Emission Rate (lbs/hr)	0.07	0.12	0.07	0.08
<u>Average Concentration ($\mu\text{g/L}$)</u>				
<u>Stripper Influent</u>				
Tetrachloroethylene	<104 ^a	<250	<142	<165 ^c
Trichloroethylene	2,293 ^a	4,210	2,491 ^d	2,998
Total	<2,397	<4,460	<2,633	<3,163
<u>Stripper Effluent</u>				
Tetrachloroethylene	<1.67 ^b	<1.67	<1.67 ^a	<1.67 ^c
Trichloroethylene	<1.67 ^{a,b}	<1.67	<1.67 ^a	<1.67
Total	<3.34	<3.34	<3.34	<3.34

^aThis value is an average and includes one or more results obtained from unpreserved or improperly preserved samples. Data may not be accurate.

^bThis value is an average including one or more results for which surrogate spike recoveries are out of specification.

^cQuarterly averages including detection limit values are for full detection limits.

^dSample held beyond the normal holding time. The analytical result is an estimated quantity. The actual value of the analysis is not known, but is known to be greater than the value shown.

Table 25. Volume Pumped and Average Flow from Individual Recovery Wells

Well	January Monthly Volume (gal)	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)	February Monthly Volume (gal)	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)	March Monthly Volume (gal)	Cumulative Volume since 4/85 (gal)	Average Flow Rate (gpm)	Well Operation (hours)
RWM 1	0	102,655,643	0	0	50,514	102,706,157	19	44	792,780	103,498,937	18	723
RWM 2	935,976	91,576,584	23	680	860,256	92,436,840	23	625	968,269	93,405,109	22	721
RWM 3	2,746,835 ^a	243,864,646	74	622 ^b	2,508,713 ^a	246,373,359	69	602	2,806,879	249,180,238	65	720
RWM 4	0	144,994,162	0	0	120,507	145,114,669	46	44	2,033,090	147,147,759	47	722
RWM 5	2,030,483	142,351,861	50	680	1,885,297	144,237,158	50	626	2,136,080	146,373,238	49	722
RWM 6	1,832,617	221,897,925	72	424	0	221,897,925	0	0	0	221,897,925	0	0
RWM 7	1,645,574	133,598,390	40	678	1,698,365	135,296,755	45	628	1,906,285	137,203,040	44	723
RWM 8	0	141,016,091	0	0	121,276	141,137,367	46	44	137,763	141,275,130	47	49
RWM 9	0	163,332,217	0	0	0	163,332,217	0	0	0	163,332,217	0	0
RWM 10	0	171,391,271	0	0	0	171,391,271	0	0	2,398,770 ^a	173,790,041	59	681
RWM 11	3,188,075	254,873,510	78	677	2,980,330	257,853,840	79	628	3,341,122	261,194,962	77	723
RWM 12	2,344,493	72,741,005	55	713	389,964 ^a	73,130,969	55	118	2,209,975	75,340,944	50	736

^aMonthly volumes are partial estimates due to failed totalizers. Estimates are based on flow rate and time.

^bOperating hours are partial estimates due to failed totalizers. Estimates are based on flow rate and throughput.

Table 26. Average Monthly Tetrachloroethylene and Trichloroethylene Concentrations in Individual Recovery Wells

Well	January <u>Solvent Concentration</u>			February <u>Solvent Concentration</u>			March <u>Solvent Concentration</u>			Quarterly Average <u>Solvent Concentration</u>		
	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)	Tetrachloro- ethylene ($\mu\text{g/L}$)	Trichloro- ethylene ($\mu\text{g/L}$)	Total ($\mu\text{g/L}$)
RWM 1	NA ^a	NA	NA	2,390	2,250	4,640	8,740 ^c	29,700 ^c	38,440	5,565	15,975	21,540
RWM 2	11,350 ^{b,c}	16,600 ^{b,c}	27,950	10,200	15,700	25,900	10,200 ^c	14,000 ^c	24,200	10,583	15,433	26,016
RWM 3	2,855 ^{b,c}	7,760 ^{b,c}	10,615	2,920	7,980	10,900	2,380 ^c	7,330 ^c	9,710	2,718	7,690	10,408
RWM 4	NA	NA	NA	1,540	5,730	7,270	1,360 ^c	5,880 ^c	7,240	1,450	5,805	7,255
RWM 5	921 ^{b,c}	1,145 ^{b,c}	2,066	823	1,300	2,123	929 ^c	1,470 ^c	2,399	891	1,305	2,196
RWM 6	5,220 ^b	4,670 ^b	9,890	NA	NA	NA	NA	NA	NA	5,220	4,670	9,890
RWM 7	6,305 ^{b,c}	6,550 ^{b,c}	12,855	5,130	5,910	11,040	5,320 ^c	5,990 ^c	11,310	5,585	6,150	11,735
RWM 8	NA	NA	NA	1,050	1,570	2,620	NA	NA	NA	1,050	1,570	2,620
RWM 9	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
RWM 10	NA	NA	NA	NA	NA	NA	11,100 ^c	4,380 ^c	15,480	11,100	4,380	15,480
RWM 11	130 ^{b,c,d}	1,440 ^{b,c}	1,570	160	1,630	1,790	175 ^c	1,760 ^c	1,935	155	1,610	1,765
RWM 12	<84 ^b	2,440 ^b	<2,524	<83	4,810	<4,893	<167 ^c	2,297 ^c	<2,464	<111	3,182	<3,293

^aNA = Not applicable.^bThis result is reported for an unpreserved or improperly preserved sample. Data may not be accurate.^cThis value represents an average of monthly stripper influent analyses.^dThe detected result is between the sample-specific Estimated Quantitation Limit and the method detection limit. The analytical result is an estimated quantity.

Table 27. Summary of Monthly Operation and Performance of the Integrated Demonstration Vadose Zone Unit

<u>Operation Parameter</u>	<u>January</u>	<u>February^a</u>	<u>March</u>	<u>Quarterly Results</u>
Operating Time (hours)	273.4	0.0	0.0	273.4
Downtime (hours)	470.6	672.0	744.0	1,886.6
Percent Utility (%)	36.7	0.0	0.0	12.7
Average Air Feed Rate (cfm)	207.9	0.0	0.0	69.3
Total Solvent Removed (lbs)	344.9	0.0	0.0	344.9
Total Solvent Destroyed (lbs)	325.1	0.0	0.0	325.1
Emission Rate (lbs/hr)				
Hydrogen chloride	1.03	0.00	0.00	0.3431
Tetrachloroethylene	0.07	0.00	0.00	0.0217
Trichloroethylene	0.01	0.00	0.00	0.0025
Average Concentration (ppmv)				
<u>Influent</u>				
Tetrachloroethylene	170.63	0.00	0.00	56.88
Trichloroethylene	81.37	0.00	0.00	27.12
Total	252.00	0.00	0.00	84.00
<u>Effluent</u>				
Tetrachloroethylene	12.15	0.00	0.00	4.05
Trichloroethylene	1.74	0.00	0.00	0.58
Total	13.89	0.00	0.00	4.63

^aThe Integrated Demonstration Vadose Zone Unit did not operate during February and March.

Table 28. Horizontal Gradients and Flow Rates in the Five Aquifer Zones

Fourth Quarter 1994

Aquifer Zone	Transect	Horizontal Gradient	Flow Rate (ft/day)	Flow Rate (ft/year)
M-Area	A-A' ^a	0.0029	0.39	140
	B-B'	0.0024	0.32	120
	C-C'	0.0069	0.93	340
Upper Lost Lake	A-A'	0.0053	1.20	440
	B-B'	0.0029	0.65	240
	C-C'	0.0043	0.97	350
Lower Lost Lake	A-A'	0.0028	0.63	230
Middle Sand of the CBCU	A-A'	0.0030	0.68	250
Crouch Branch	A-A'	0.0038	0.76	280

First Quarter 1995

Aquifer Zone	Transect	Horizontal Gradient	Flow Rate (ft/day)	Flow Rate (ft/year)
M-Area	A-A' ^b	0.0029	0.39	140
	B-B'	0.0025	0.34	120
	C-C'	0.0087	1.2	440
Upper Lost Lake	A-A'	0.0032	0.72	260
	B-B'	0.0029	0.65	240
	C-C'	0.0046	1.0	370
Lower Lost Lake	A-A'	0.0029	0.65	240
Middle Sand of the CBCU	A-A'	0.0038	0.86	310
Crouch Branch	A-A'	0.0036	0.72	260

^a Transects are identified on the piezometric and potentiometric maps in Appendix C of WSRC (1994).

^b Transects are identified on the piezometric and potentiometric maps in Appendix I (Volume III) of this report.

Appendix E

Data Quality/Usability Assessment

THIS PAGE LEFT BLANK INTENTIONALLY.

Data Quality/Usability Assessment

Quality assurance/quality control (QA/QC) procedures relating to accuracy and precision of analyses performed on groundwater samples are followed in the field and laboratory and are reviewed prior to publication of results. The review by the Environmental Protection Department/Environmental Monitoring Section (EPD/EMS) of the volume of analytical data acquired each quarter and presented in various reports is an ongoing process; EMS's review of the QA/QC data cannot be completed in time to meet the deadlines for the groundwater monitoring reports required by the Resource Conservation and Recovery Act and associated regulations. Other site and regulatory personnel can obtain further information on the data quality and usability in a variety of ways, including those described below.

Results Below Detection

For radiological analyses, the analytical result field contains the result recorded on the analytical instrument and reported by the laboratory, even if it is negative. For non-radiological analyses, if the analyte is not detected, the sample-specific estimated quantitative limit (EQL) is entered into the result field (with a less than [$<$] sign). The EQL is defined as the lowest concentration that can be achieved reliably within specified limits of precision and accuracy during routine laboratory operating conditions. The sample-specific EQL is modified for sample concentration or dilution or unusual aliquot size that affects analytical sensitivity.

Data Qualification

The contract laboratories continually assess their own accuracy and precision according to U.S. Environmental Protection Agency (EPA) guidelines. They submit sample- or batch-specific QA/QC information either at the same time as analytical results or in quarterly summaries. Properly defined and used modifiers (also referred to as qualifiers) can be a key component in assessing data usability. Modifiers designed by EPD/EMS and used by the primary laboratories are presented in Appendix D.

Assessment of Accuracy of the Data

Accuracy, or the nearness of the reported result to the true concentration of a constituent in a sample, can be assessed in several ways.

A laboratory's general accuracy can be judged by analysis of results obtained from known samples. The non-radionuclide contract laboratories analyze commercial reference samples every quarter at EPD/EMS' request. The results of these analyses are presented in the EPD/EMS groundwater monitoring quarterly reports. The primary laboratories also seek or maintain state certification by participating periodically in performance studies; reference samples and analysis of results are provided by EPA. Results of these studies also are published in the EPD/EMS quarterly reports.

Analysis of blanks provides a tool for assessing the accuracy of both sampling and laboratory analysis. Results for all field blanks for the quarter can be found in the EPD/EMS quarterly reports. Any field or laboratory blanks that exceed established minimums are identified in the same reports, in tables associating them with groundwater samples analyzed in the same batches. In these regulatory reports, the modifier V is applied to every result that is run in the same batch as a laboratory blank with positive results for that analyte. A second V qualifier is added if the analyte concentration is less than five times the concentration in the blank (or, for common laboratory contaminants, less than ten times.)

Surrogates, organic compounds similar in chemical behavior to the compounds of interest but not normally found in environmental samples, are used to monitor the effect of the matrix on the accuracy of analyses for organic parameters. For example, for analyses of volatile organics by EPA Method 8240, three surrogate compounds are added to all samples and blanks in each analytical batch. In analyses of semivolatile organics, three acid compounds and three base/neutral compounds are used. Two surrogates are used in organochlorine pesticides analyses. Percent recoveries for surrogate analyses are calculated by laboratory personnel, reported to EPD/EMS, reviewed, and entered into the database, but they are not published. If recoveries are not within specified limits, the laboratory is expected to reanalyze the samples or attach qualifiers to the data identifying the anomalous results.

Sample-specific accuracy for both organic and inorganic parameters can be assessed by examination of matrix spike/matrix spike duplicate results. A sample is analyzed unspiked to determine a baseline set of values. A second portion of the sample is spiked with known concentrations of compounds appropriate to the analyses being performed, typically five volatile organic compounds for volatile organics analyses, eleven semivolatile compounds for semivolatiles, six pesticide compounds for pesticides, all metals for metals analyses by SW-846 methods (EPA, 1986), and a known quantity of cyanide for cyanide analysis. The percentage of the spike compound that is recovered (i.e., measured in excess of the value obtained for the unspiked sample) is a direct measure of analytical accuracy. EPA requires matrix spike/matrix spike duplicates to be run at least once per 20 samples of similar matrix.

Matrix spike/matrix spike duplicate results are reported to EPD/EMS but are not published. For organic compounds, according to EPA guidelines, no action is taken on the basis of matrix spike/matrix spike duplicate data alone (i.e., no result modifiers are assigned solely on the basis of matrix spike results); however, the results can indicate if a laboratory is having a systematic problem in the analysis of one or more analytes.

In the case of inorganic compounds, such as metals, the matrix spike sample analysis provides information about the effect of each sample matrix on the digestion and measurement methodology. Data qualifiers assigned by the laboratories on the basis of the percentage of spike recovery are reported in the EPD/EMS results tables.

Assessment of Precision

Precision of the analyses, or agreement of a set of replicate results among themselves, is assessed through the use of duplicates initiated by the laboratory and blind replicates provided by EPD/EMS. The results of duplicate and replicate analyses are presented in results tables that report only one quarter of data, usually during first, second, and third quarters. Duplicate and replicate results are not presented in results tables that report more than one quarter of data, generally provided in fourth quarter reports. In this case, the results tables instead present only the highest result for each analyte for each quarter of the year.

The laboratories assess precision by calculating the relative percent difference (RPD) for each pair of laboratory-initiated duplicate results. The contract laboratories use a data qualifier to modify metals analyses when the RPD for laboratory duplicates is greater than 20 percent. This qualifier is published in the EPD/EMS quarterly reports.

Additional statistical comparisons of laboratory duplicate and blind replicate results, both intra- and interlaboratory, are presented in the EPD/EMS quarterly reports. The calculation used for these reports is the mean relative difference (MRD) which is similar to EPA's RPD except that the MRD is the average of all the RPD values from one laboratory for each compound (intralab-

oratory MRD) or all the RPD values from all laboratories for each compound (interlaboratory MRD), during one quarter. Because detection limits may vary among samples, the MRD requires calculation of a reference detection limit, which is the detection limit at the 90th percentile of the array of limits in the population of all duplicate and replicate analyses for a given analyte during a particular quarter. The MRD is not method-specific.

Method-Specific Accuracy and Precision

The contract laboratories' EPA-approved laboratory procedures include QA/QC requirements as an integral part of the methods. Thus, knowledge of the method used in obtaining data is an important component of determining data usability. EPA has conducted extensive research and development on the methods approved for the analysis of water and waste water. Information on the accuracy and precision of a method is available from EPA publications, as is full information on required QA/QC procedures. A listing of the methods used by the primary laboratories during fourth quarter 1993 is given below along with the source for the method description. Many, if not all, of these sources include presentations of representative accuracy and precision results.

Methods Used by the Contract Laboratories

<u>Method</u>	<u>Used to Analyze</u>	<u>Source</u>
EPA120.1	Specific conductance	EPA EMSL, 1983
EPA150.1	pH	EPA EMSL, 1983
EPA160.1	Total dissolved solids	EPA EMSL, 1983
EPA160.2	Total dissolved solids, total suspended solids	EPA EMSL, 1983
EPA180.1	Turbidity	EPA EMSL, 1983
EPA200.7	Metals	EPA EMSL, 1983
EPA204.2	Antimony	EPA EMSL, 1983
EPA206.2	Arsenic	EPA EMSL, 1983
EPA239.2	Lead	EPA EMSL, 1983
EPA245.1	Mercury	EPA EMSL, 1983
EPA270.2	Selenium	EPA EMSL, 1983
EPA279.2	Thallium	EPA EMSL, 1983
EPA300.0	Chloride, nitrite, sulfate	EPA EMSL, 1991
EPA310.1	Alkalinity	EPA EMSL, 1983
EPA325.2	Chloride	EPA EMSL, 1983
EPA335.3	Cyanide	EPA EMSL, 1983
EPA340.2	Fluoride	EPA EMSL, 1983
EPA353.1	Nitrogen, nitrate-nitrite	EPA EMSL, 1983
EPA353.2	Nitrogen, nitrate, nitrite, or combined	EPA EMSL, 1983
EPA365.1	Phosphorus, all forms (reported as total phosphates)	EPA EMSL, 1983
EPA365.2	Phosphorus, all forms (reported as total phosphates)	EPA EMSL, 1983
EPA376.2	Sulfide	EPA EMSL, 1983
EPA413.1	Oil & grease	EPA EMSL, 1983
EPA415.1	Dissolved organic carbon, total inorganic carbon, total organic carbon	EPA EMSL, 1983
EPA418.1	Total petroleum hydrocarbons	EPA EMSL, 1983
EPA420.2	Phenols	EPA EMSL, 1983
EPA900.0	Gross alpha, nonvolatile beta	EPA EMSL, 1980
EPA900.1	Total alpha-emitting radium	EPA EMSL, 1980
EPA906.0	Tritium	EPA EMSL, 1980
EPA6010	Metals	EPA, 1986
EPA7041	Antimony	EPA, 1986
EPA7060	Arsenic	EPA, 1986

<u>Method</u>	<u>Used to Analyze</u>	<u>Source</u>
EPA7421	Lead	EPA, 1986
EPA7470	Mercury	EPA, 1986
EPA7740	Selenium	EPA, 1986
EPA7841	Thallium	EPA, 1986
EPA8010	Chlorinated volatile organics	EPA, 1986
EPA8080	Organochlorine pesticides and-PGBs	EPA, 1986
EPA8150	Chlorinated herbicides	EPA, 1986
EPA8240	GCMS volatiles	EPA, 1986
EPA8270	GCMS semivolatiles	EPA, 1986
EPA8280	Dioxins and furans	EPA, 1986
EPA9012	Cyanide	EPA, 1986
EPA9020	Total organic halogens	EPA, 1986
EPA9020A	Total organic halogens	EPA, 1986
EPA9030	Sulfide	EPA, 1986
EPA9060	Dissolved organic carbon, total inorganic carbon, total organic carbon	EPA, 1986

An example of available method-specific QA/QC information is that for the analysis of metals by EPA Method 6010/200.7 (EPA, 1986/EPA EMSL, 1983). The primary laboratories, General Engineering Laboratories (GE) and Roy F. Weston, Inc. (Weston), use this inductively coupled plasma (ICP) atomic emission spectrometric method.

The following precision and accuracy data are based on the experience of seven laboratories that applied the ICP technique to acid-distilled water matrices that had been spiked with various metal concentrates. (Note: Not all seven laboratories analyzed all 14 elements.) The references give results for samples having three concentration ranges; the results here are for samples having the lowest values, similar to actual groundwater results for SRS.

ICP Precision and Accuracy Data

<u>Element</u>	<u>True value ($\mu\text{g/L}$)</u>	<u>Mean reported value ($\mu\text{g/L}$)</u>	<u>Mean percent RSD^a</u>
Aluminum	60	62	33
Arsenic	22	19	23
Beryllium	20	20	9.8
Cadmium	2.5	2.9	16
Chromium	10	10	18
Cobalt	20	20	4.1
Copper	11	11	40
Iron	20	19	15
Lead	24	30	32
Manganese	15	15	6.7
Nickel	30	28	11
Selenium	6	8.5	42
Vanadium	70	69	2.9
Zinc	16	19	45

^a Relative standard deviation. In EPA (1986), the column heading is Mean Standard Deviation (%).

As another example, EPA Method 601/8010 (EPA, 1991/EPA, 1986) is used by both GE and Weston for analyses of halogenated volatile organics. In the presentation of the method in both references, the following table gives method-specific accuracy and precision as functions of concentration. Contract laboratories are expected to achieve or at least approach these limits.

Accuracy and Precision as Functions of Concentration for EPA Method 601/8010

Parameter	Accuracy as recovery, X^a ($\mu\text{g/L}$)	Single analyst precision ($\mu\text{g/L}$) ^b	Overall precision ($\mu\text{g/L}$) ^c
Bromodichloromethane	$1.12C - 1.02^d$	$0.11\bar{X} + 0.04^e$	$0.20\bar{X} + 1.00$
Bromoform	$0.96C - 2.05$	$0.12\bar{X} + 0.58$	$0.21\bar{X} + 2.41$
Bromomethane	$0.76C - 1.27$	$0.28\bar{X} + 0.27$	$0.36\bar{X} + 0.94$
Carbon tetrachloride	$0.98C - 1.04$	$0.15\bar{X} + 0.38$	$0.20\bar{X} + 0.39$
Chlorobenzene	$1.00C - 1.23$	$0.15\bar{X} - 0.02$	$0.18\bar{X} + 1.21$
Chloroethane	$0.99C - 1.53$	$0.14\bar{X} - 0.13$	$0.17\bar{X} + 0.63$
2-Chloroethyl vinyl ether ^f	$1.00C$	$0.20\bar{X}$	$0.35\bar{X}$
Chloroform	$0.93C - 0.39$	$0.13\bar{X} + 0.15$	$0.19\bar{X} - 0.02$
Chloromethane	$0.77C + 0.18$	$0.28\bar{X} - 0.31$	$0.52\bar{X} + 1.31$
Dibromochloromethane	$0.94C + 2.72$	$0.11\bar{X} + 1.10$	$0.24\bar{X} + 1.68$
1,2-Dichlorobenzene	$0.93C + 1.70$	$0.20\bar{X} + 0.97$	$0.13\bar{X} + 6.13$
1,3-Dichlorobenzene	$0.95C + 0.43$	$0.14\bar{X} + 2.33$	$0.26\bar{X} + 2.34$
1,4-Dichlorobenzene	$0.93C - 0.09$	$0.15\bar{X} + 0.29$	$0.20\bar{X} + 0.41$
1,1-Dichloroethane	$0.95C - 1.08$	$0.09\bar{X} + 0.17$	$0.14\bar{X} + 0.94$
1,2-Dichloroethane	$1.04C - 1.06$	$0.11\bar{X} + 0.70$	$0.15\bar{X} + 0.94$
1,1-Dichloroethene	$0.98C - 0.87$	$0.21\bar{X} - 0.23$	$0.29\bar{X} - 0.40$
trans-1,2-Dichloroethene	$0.97C - 0.16$	$0.11\bar{X} + 1.46$	$0.17\bar{X} + 1.46$
Dichloromethane (Methylene chloride)	$0.91C - 0.93$	$0.11\bar{X} + 0.33$	$0.21\bar{X} + 1.43$
1,2-Dichloropropane ^f	$1.00C$	$0.13\bar{X}$	$0.23\bar{X}$
cis-1,3-Dichloropropene ^f	$1.00C$	$0.18\bar{X}$	$0.32\bar{X}$
trans-1,3-Dichloropropene ^f	$1.00C$	$0.18\bar{X}$	$0.32\bar{X}$
1,1,2,2-Tetrachloroethane	$0.95C + 0.19$	$0.14\bar{X} + 2.41$	$0.23\bar{X} + 2.79$
Tetrachloroethylene	$0.94C + 0.06$	$0.14\bar{X} + 0.38$	$0.18\bar{X} + 2.21$
1,1,1-Trichloroethane	$0.90C - 0.16$	$0.15\bar{X} + 0.04$	$0.20\bar{X} + 0.37$
1,1,2-Trichloroethane	$0.86C + 0.30$	$0.13\bar{X} - 0.14$	$0.19\bar{X} + 0.67$
Trichloroethylene	$0.87C + 0.48$	$0.13\bar{X} - 0.03$	$0.23\bar{X} + 0.30$
Trichlorofluoromethane	$0.89C - 0.07$	$0.15\bar{X} + 0.67$	$0.26\bar{X} + 0.91$
Vinyl chloride	$0.97C - 0.36$	$0.13\bar{X} + 0.65$	$0.27\bar{X} + 0.40$

^a X' = expected recovery for one or more measurements of a sample containing a concentration of C , in $\mu\text{g/L}$.

^b Expected single analyst standard deviation of measurements.

^c Expected interlaboratory standard deviation of measurements.

^d C = true value for the concentration, in $\mu\text{g/L}$.

^e $\bar{X}$ = average recovery found for measurements of samples containing a concentration of C , in $\mu\text{g/L}$.

^f Estimates based on performance of a single laboratory.

References Cited

EPA (U.S. Environmental Protection Agency), 1986. **Test Methods for Evaluating Solid Waste (SW-846)**, Volumes IA-IC. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. *Guidelines Establishing Test Procedures*

for the Analysis of Pollutants, **Code of Federal Regulations**, Title 40, Part 136, Appendix A. Washington, DC.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1980. **Prescribed Procedures for Measurement of Radioactivity in Drinking Water**, EPA-600/4-80-032. Cincinnati, OH.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1983. **Methods for Chemical Analysis of Water and Wastes**. Cincinnati, OH.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1991. **Test Method, The Determination of Inorganic Anions in Water by Ion Chromatography—Method 300.0**. Cincinnati, OH.