1 of 1

**DIRECT AROMATIZATION OF METHANE
QUARTERLY TECHNICAL PROGRESS REPORT No. 4**

Prepared for the U.S. Department of Energy Under
Contract No. DE-AC22-92PC92109

by

ALTAMIRA INSTRUMENTS, INC.

2090 William Pitt Way
Pittsburgh, PA 15238

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Date of Report: October 8, 1993
Date of Contract: September 26, 1992
Anticipated Completion: May 25, 1995

Program Manager: George Marcelin
COR: Arun C. Bose
Reporting Period: 7-1-93 to 9-30-93

MASTER

TABLE OF CONTENTS

Abstract	i
Objectives	1
Technical Report	1
Introduction	1
Experimental	1
Results and Discussion	2
Current Status	3
Work Planned for Next Quarter	3

LIST OF FIGURES

Figure 1. Conversion and product selectivities for methane pyrolysis at 900°C and 80 Scc/min.	4
Figure 2. Conversion and product selectivities for methane pyrolysis at 1050°C and 100 Scc/min	5
Figure 3. Conversion and product selectivities for methane pyrolysis at 1050°C. Flow rates: 100 and 200 Scc/min	6
Figure 4. Chromatogram and peak identification of high molecular weight products	7

ABSTRACT

The pyrolysis of methane in the absence of a quench was studied at temperatures between 900 and 1050°C and methane flows of 80-200 Scc/min. At 1050°C and a methane flow rate of 100 Scc/minute, methane conversion ranged between 15 - 19% with the major products being benzene, acetylene, and ethylene. The benzene molar selectivity was ca. 50%, corresponding to molar yield of ca. 7.5 - 10%.

The reaction resulted in the formation of visible amounts of solid carbon, particularly at 1050°C. The resulting solid consisted partly of carbon and partly of a yellowish tar-like material which was soluble in toluene and contained various heavy hydrocarbons and poly-ring aromatics.

OBJECTIVE

The thermal decomposition of methane shows significant potential as a process for the production of higher unsaturated and aromatic hydrocarbons when the extent of the reaction is limited. Preliminary experiments have shown that cooling the product and reacting gases as the reaction proceeds can significantly reduce or eliminate the formation of solid carbon and heavier (C_{10+}) materials. Much work remains in optimizing the quenching process and this is one of the goals of this program. We will also study means to lower the temperature of the reaction as this will result in a more feasible commercial process due to savings realized in energy and material of construction costs. The use of free-radical generators and catalysts will be investigated as a means of lowering the reaction temperature thus allowing faster quenching. It is highly likely that such studies will lead to a successful direct methane to higher hydrocarbon process.

TECHNICAL REPORT

INTRODUCTION

During the fourth quarter work we initiated experimental work into the pyrolysis of methane. Two significant accomplishments were the development of an analytical technique for gas chromatographic analysis of the reactor effluent using a single GC column and the successful completion of baseline experimental runs in the absence of a quench.

EXPERIMENTAL

The pyrolysis of methane in the absence of a quench was studied at temperatures between 900 and 1050°C and methane flows of 80-200 Scc/min. The experimental procedure was as follows: The reactor furnace was brought up to the desired temperature while helium flowed through the outer tube of the reactor. Once the desired temperature was reached, methane flow was started, but bypassing the reactor. At least three analyses of the methane feed were obtained. The methane was then diverted into the reactor and the helium flow cut-off. After five minutes of reaction an effluent sample was taken.

In early experiments the methane was allowed to continually flow through the reactor while the analysis was proceeding. This led to a considerable amount of solids being formed, however; thus in latter experiments the methane was switched off and helium flowed through the reactor during the analysis period.

Analysis was performed by on-line gas chromatography using a Varian 3400 GC equipped with an Alumina-GS Microbore capillary column. This arrangement is suitable for resolving all hydrocarbons of interest between methane and naphthalene. Individual components were identified by comparison of retention times with known standards. Peak area was taken to be proportional to the number of carbons in each component times a response factor taken from the literature.

RESULTS AND DISCUSSION

Experiments were performed at 900 and 1050°C in the absence of quench. Over 20 different products were identified in the reactor effluent by gas chromatography.

A summary of the results at 900°C are presented in Figure 1. Methane conversion at this temperature was low, i.e., less than 1%, but a number of products were identified. The principal product at this temperature was ethylene. Smaller amounts of propylene and benzene were also identified.

Figure 2 shows the conversion and selectivities for two separate runs at 1050°C and total methane flow rate of 100 Scc/minute. Methane conversions were 15 and 19%. The major products detected were benzene, acetylene, and ethylene. The benzene molar selectivity was ca. 50%, this is the equivalent of a benzene molar yield of ca. 7.5 - 10%. Figure 3 shows the effect of methane flow rate, i.e., space time, on the reaction. As would be expected, total methane conversion dropped with increasing flow rate. Conversion fell from 15% to 9% when the flow rate was increased from 100 to 200 Scc/minute. Changes in selectivities were also noted. Benzene selectivity decreased and ethylene selectivity increased with increased flow rate. Flow rate seemed to have little effect in the acetylene selectivity, but this may be fortuitous. Other aromatics, including toluene and naphthalene were observed in small amounts at these conditions.

It is interesting that one of the major products observed was ethylene. This is contrary to the results of the thermodynamic calculations reported in the Second Quarterly Technical Report, suggesting that the reaction is far from thermodynamic equilibrium under our reaction conditions. Similarly, the measured conversion was far below that predicted by thermodynamics for this temperature.

Reaction in the absence of a quench resulted in the formation of visible amounts of solid carbon, particularly at 1050°C. At this temperature, the formation of solids became evident after only a few minutes of reaction and, in one experiment, was sufficiently heavy to completely plug the reactor after only 100 minutes of operation. The resulting solid consisted partly of carbon and partly of a yellowish tar-like material which was soluble in toluene. GC-MS analysis was performed on the toluene solution. Figure 4 shows the relevant portion of the chromatogram and the identification of numbered peaks.

CURRENT STATUS

Project is proceeding slightly behind schedule but we expect to make up the time in the next few months.

WORK PLANNED FOR NEXT QUARTER

Next quarter we will continue the experimental work on the aromatization of methane by quenched-pyrolysis. We will concentrate on studying the influence of the various experimental parameters on conversions and selectivities.

FIGURE 1.

Methane Pyrolysis

T= 900 C, P= 1 atm, Pure Methane

FIGURE 2.
Methane Pyrolysis

T= 1050 C, Flow= 100 CC/min, P= 1 atm, Pure Methane

FIGURE 3.
Methane Pyrolysis

T = 1050 C, P = 1 atm, Pure Methane

Figure 4. Chromatogram and peak identification of high molecular weight products formed during methane pyrolysis. 9: $C_{16}H_{34}$; 10: penanthrene; 11, 12, 13, 17, 18: eicosanes (various isomers); 14: pyrene; 15: fluoranthene; 16: benzo[c]phenanthrene; 19: 3-methylheneicosane.

**DATE
FILMED**

4 / 19 / 94

END