Quarterly Environmental Radiological Survey Summary

Third Quarter 1995 100, 200,
300, and 600 Areas

S. M. McKinney

Date Published
September 1995

Prepared for the U.S. Department of Energy
Office of Environmental Restoration and
Waste Management

**Westinghouse
Hanford Company**

P.O. Box 1970
Richland, Washington

Management and Operations Contractor for the
U.S. Department of Energy under Contract DE-AC06-87RL10930

Approved for Public Release

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED ^{JK}

MASTER

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

RELEASE AUTHORIZATION

Document Number: WHC-SP-0665-18

Document Title: Quaterly Environmental Radiological Survey Summary -
Third Quarter 1995 100, 200, 300 and 600 Areas

Release Date: 10/26/95

**This document was reviewed following the
procedures described in WHC-CM-3-4 and is:**

APPROVED FOR PUBLIC RELEASE

WHC Information Release Administration Specialist:

Kara M. Broz

October 26, 1995

QUARTERLY
ENVIRONMENTAL RADIOLOGICAL SURVEY SUMMARY
100, 200, 300, 400, and 600 Areas

3rd Quarter 1995

S. M. McKinney
B. M. Markes

ENVIRONMENTAL MONITORING AND INVESTIGATIONS
NEAR-FIELD MONITORING

APPROVAL PAGE

PREPARED BY

S. M. McKinney

10-23-95
Date

B. M. Markes

10/23/95
Date

REVIEWED BY

A. R. Johnson

10/23/95
Date

APPROVED BY:

J. J. Dorian

10/23/95
Date

EXECUTIVE SUMMARY

This report provides a summary of the radiological surveys performed in support of the operational environmental monitoring program at the Hanford Site. The Third Quarter 1995 survey results and the status of actions required from current and past reports are summarized below:

- All the routine environmental radiological surveys scheduled during July, August, and September 1995 were completed with the exception of the following waste sites:
 - 116-D-3 Inaccessible due to Pump and Treat in progress.
 - 166-H-6 Active Decommissioning in progress.
 - UN-100-F-1 Inaccessible posted "danger do not enter."
- One hundred and three environmental radiological surveys were performed during this period, forty at the active waste sites and sixty three at the inactive waste sites. Contamination above background levels was found at seven of the active waste sites and six of the inactive waste sites. Contamination levels as high as 500,000 disintegrations per minute (dpm) were reported. Of these contaminated surveys one was in a Surface Contamination (SC) area and twelve were in Underground Radioactive Material (URM) areas or unposted. The contamination found within three of the URM areas was immediately cleaned up and no further action was required. In the remaining nine sites the areas were posted and will require decontamination. Radiation Problem Reports (RPR's) were issued and the sites were turned over to the landlord for further action if required.
- No Compliance Assessment Reports (CARs) were issued for sites found out of compliance with standards identified in WHC-CM-7-5, Environmental Compliance.
- One Surveillance Compliance/Inspection Report (SCIR) was closed during the Third Quarter of 1995.
- Six open SCIRs had not been resolved.

Responsibilities for the unresolved SCIRs are as follows:

<u>LANDLORD</u>	<u>OPEN SCIR/CAR</u>
B-Plant	0
PUREX	1
Tank Farm Operations (TF0)	5

TOP TEN PRIORITY RANKING

Below is a listing of the top ten waste sites in order of highest priority ranking for contamination control. The waste site may have an open SCIR of CAR identifying the contamination. An explanation of the prioritization system is on page 12 of this report. Priority rankings of the open SCIRs and CARs are listed in Table 1.

	<u>SITE</u>	<u>CUSTODIAN</u>	<u>SCIR/CAR</u>
1.	241-C Tank Farm Perimeters	TF0	9008EP200-068
2.	241-B Tank Farm Perimeters	TF0	8909EP200-036
3.	241-BX-BY Tank Farm Perimeters	TF0	9007EP200-056
4.	241-S, SX, SY Tank Farm Perimeters	TF0	9208ERI-006
5.	UN-216-E-16 TC-4 R.R. Spur	TF0/PUREX	8901EP200-001
6.	241-U Tank Farm Perimeters	TF0	9203ERI-002
7.	UN-216-E-6 241-BX-155 DIVERSION BOX	TF0	NONE
8.	UN-216-W-35 207-U RETENTION BASIN	TF0	NONE
9.	207-T RETENTION BASIN	TF0	NONE
10.	216-B-64 Basin.	B-Plant	NONE

TABLE OF CONTENTS

EXECUTIVE SUMMARY	i
TOP TEN PRIORITY RANKING	ii
1.0 INTRODUCTION	1
AREA RADIOLOGICAL CONTAMINATION ILLUSTRATIONS	2-11
2.0 PROGRAM DESCRIPTION	12
2.1 ENVIRONMENTAL RADIOLOGICAL SURVEY PROGRAM OBJECTIVES . . .	12
2.2 PRIORITY RANKING SYSTEM	12
2.3 ENVIRONMENTAL STANDARDS	13
2.4 COMPLIANCE ASSESSMENT REPORTS	15
2.5 SURVEY METHODS AND PROCEDURES	15
2.5.1 ROAD SURVEYS	15
2.5.2 WASTE SITES AND OTHER RADIATION AREA SURVEYS	16
3.0 SURVEY RESULTS	17
3.1 ENVIRONMENTAL RADIOLOGICAL SURVEY SUMMARY	17
3.2 COMPLIANCE ASSESSMENT REPORTS ISSUED	18
3.3 COMPLIANCE/SURVEILLANCE REPORTS CLOSED	18
3.4 STATUS OF OPEN SURVEILLANCE AND COMPLIANCE REPORTS	18
4.0 SUMMARY	20

1.0 INTRODUCTION

Routine radiological surveys are part of the near-facility environmental monitoring program which monitors and helps direct the reduction of the radiologically controlled areas at the Hanford Site. The routine radiological surveys are performed by the Southern Area Remediation Support Group and the Site Surveillance Radiological Control Group as directed by Near-Field Monitoring. The surveys included in this program consist of inactive waste sites; outdoor radiological control areas; tank farm perimeters and associated diversion boxes, lift stations, and vent stations; perimeters of active or uncovered waste sites such as burial grounds, retention basins, ponds, process trenches, and ditches; and road and rail surfaces (Figures 1 through 10). This report provides a summary of the radiological surveys performed during the Third Quarter of 1995. The status of corrective actions required from current and past reports are also discussed.

A waste site survey schedule, WHC-SP-0098-6, is developed by Near-Field Monitoring and approved by the Southern Area Remediation Support Group and the Site Surveillance Radiological Control Group. Near-Field Monitoring reviews the radiological survey reports and files a copy for historical purposes and reference. Radiological conditions are tracked and trends noted. All sites are surveyed at least once each year. The survey frequencies for particular sites are based on site history, radiological conditions, and general maintenance. Special surveys may be conducted at irregular frequencies if conditions warrant (e.g., growth of deep-rooted vegetation is noted at a waste site). Radiological surveys are conducted to detect surface contamination and document changes in vegetation growth, biological intrusion, erosion, and general site maintenance conditions. Survey data are compared with standards identified in WHC-CM-7-5, Environmental Compliance, as well as previous surveys to recognize possible trends, assess environmental impacts, and help determine where corrective actions are needed.

Landlords of the sites found out of compliance may be issued a Radiological Problem Report (RPR) from the Environmental Restoration Site Investigative Survey and Site Surveillance Radiological Control Groups. Should the landlord fail to respond to the identified problem in a timely manner, or if the corrective action will require a long-term commitment, Near-Field Monitoring will issue a Compliance Assessment Report (CAR). The Compliance Assessment Report, formerly called Surveillance Compliance Inspection Report (SCIR), is tracked to completion by Near-Field Monitoring. Open SCIRs and CARs are listed in Table 1 of this report.

The surveys scheduled for this program consist of inactive waste sites; outdoor radiological control areas; tank farm perimeters and associated diversion boxes, lift stations, and vent stations; perimeters of active or uncovered waste sites such as burial grounds, retention basins, ponds, process trenches, and ditches; and road and rail surfaces. Surveillance of the active nuclear facilities and inside the tank farms is the responsibility of the facility. These radiological surveys are to determine surface radiological conditions and do not constitute a release survey. Therefore, surveys that detect no contamination in radiologically controlled areas do not release the site from control but may result in a posting status change.

Figure 1

Figure 2

Figure 3

WHCUTS6NFM1D-951KCZNBW

Figure 5

WHC-SP-0665-18

Figure 6

WHC/TSN/FM10-952ECZNBW

Figure 7

WHC/HTSN/WM/10-85/2WCZNBW

Figure 8

WHC/HTSNFM/MD-953CZNBV

Figure 9

Figure 10

2.0 PROGRAM DESCRIPTION

2.1 ENVIRONMENTAL RADIOLOGICAL SURVEY PROGRAM OBJECTIVES

Environmental radiological surveys are performed to:

- Identify priorities for environmental cleanup or stabilization of surface contamination.
- Determine compliance with Department of Energy requirements and applicable policies and standards regarding operational control and environmental and radiological protection.
- Identify trends in radioactive contamination levels and radioactive migration at waste sites and other radiation areas.
- Assess the surface integrity of solid and liquid waste disposal sites.
- Monitor for unplanned releases of radioactivity to the operations area environment.

2.2 PRIORITY RANKING SYSTEM

A numerical ranking system is used for sorting contaminated waste sites relative to environmental radiological concerns. This system provides a priority guideline to responsible landlords for clean-up or stabilization of surface-contaminated areas.

A numerical value is assigned based on the level of contamination, site accessibility, and contamination mobility. Site histories are examined by reviewing past and present radiological surveys. Contamination levels from 1,000 counts per minute (cpm) to greater than 10 mrad/hr (as measured on Radiological Control's field survey instruments) are considered and assigned a numerical value of 1 (lowest value) to 5 (greatest value). Any removable alpha contamination will be considered a high priority and will receive a contamination value of 5. Location is evaluated for accessibility. A restricted area would receive the lowest point value of 1 progressing up to a value of 5 where the public could have access. Mobility refers to contamination that can be or has a history of being transported from where it was originally identified to places outside of the radiologically posted area. Fixed contamination would receive a value of 1 progressing to contamination that is blown by the wind or the result of biological uptake receiving a value of 5. The rankings (a maximum of 15 points is possible) are noted on Table 1.

It should be noted that this system is not intended to be a total risk assessment, but rather a way of communicating environmental significance to the landlords and their program offices. Other elements of the site clean-up process are considered such as costs, location, political emphasis and engineering strategies before a site is actually remediated.

2.3 ENVIRONMENTAL STANDARDS

Radiation survey data are used to determine compliance of Radioactive Waste Sites with WHC-CM-7-5, Environmental Compliance, Section 6.0 (Rev. 1) and BHI-EE-02, Environmental Requirements, Section 7.0 (Rev. 0), requirements.

Applicable requirements include the following:

1. Engineered barriers shall be provided, where applicable, over the disposal site to inhibit radionuclide transport to the surface.
2. Inactive waste site boundaries shall be accurately and permanently marked with Hanford plant standard (AC-5-40) approved concrete marker posts. Sites never used and those that are no longer contaminated do not require marker posts.
3. Facility effluent lines which are potential discharge points shall be isolated, capped, or sealed off to prevent accidental releases to inactive sites. This shall be verified and documented.
4. Active and inactive waste sites shall be inspected and surveyed at least annually.
5. One or more of the following actions shall be taken when contamination of any type is detected (either new or in excess of action limits) to prevent the migration or mobilization of the contamination:
 - * Small-scale stabilization (<5 acres)
 - * Vegetation removal
 - * Radioactive hot-spot removal
 - * Fencing
 - * Posting
 - * Herbicide spraying
 - * Immediate spill response
 - * Other corrective measures
6. Information regarding all suspect waste sites or newly identified waste sites shall be provided for documentation into the Waste Identification Data System (WIDS) database.
7. Inactive waste sites shall be maintained to control deep-rooted vegetation that could provide transport of contamination to the surface through plant uptake. The application of herbicides or pesticides may be required.

Near-Field Monitoring is responsible for:

1. Establishing radiological survey schedules of active and inactive radiological waste sites.
2. Conducting compliance assessments of active and inactive waste sites to determine compliance with the physical and radiological requirements.
3. Compiling and maintaining copies of historical records, including radiological survey reports, compliance assessment reports (CARs), surveillance/compliance inspection reports (SCIRs), and other information for each active and inactive radioactive waste site.
4. Trending radiological data, and issuing reports on the status of radiological surveys and compliance assessments for active and inactive radioactive waste sites.
5. Reviewing any proposed activity, other than routine inspections, that may impact or may be impacted by any active and inactive waste site.
6. Issuing a compliance assessment report or notifying the facility manager or area landlord, as appropriate, when violations of the requirements occur.

The above mentioned requirements apply to all active and inactive radioactive waste sites which include cribs, trenches, ditches, ponds, French drains, burial grounds and other areas of concern such as tank farm perimeters and radioactive contamination due to spills or releases. Interiors of tank farms and radiation areas where operations are ongoing are not included, because monitoring and tracking is done by Tank Waste Remediation System and other requirements are applicable to these areas.

In order to compare standards [as established in WHC-CM-7-5, Section 6.0] and field instrument values, a conversion factor is necessary. This conversion factor has been established where 20,000 disintegrations per minute (dpm) (2,000 cpm) are approximately equivalent to one millirem per hour for beta-emitting radionuclides. It must be understood that converting field instrument values, which include both beta and gamma energies, is approximate and does not allow for absolute precision.

2.4 COMPLIANCE ASSESSMENT REPORTS

When it is determined that conditions at a site are not in compliance with the standards established in WHC-CM-7-5, the appropriate area landlord is notified. If the noncompliance is not corrected as a result of Radiological Control's Radiation Problem Report (RPR) Near-Field Monitoring may issue a Compliance Assessment Report. Resolution of a CAR is considered initiated when a formal corrective action plan is provided to and accepted by Near-Field Monitoring. However, for tracking purposes it will remain on file and appear in subsequent Environmental Radiological Survey Reports until satisfactory completion of the plan is demonstrated. A visual inspection by Near-Field Monitoring and/or a post-corrective action radiation survey by Radiological Control is required before closing a CAR. If a compliance plan is not provided to Near-Field Monitoring within one month, a second notice is issued.

A CAR may be issued for conditions which pose a probable threat of radiological contamination to uncontrolled areas. These conditions include the presence of deep-rooted vegetation, animal intrusion, or obvious migrating contamination. Once the contamination is contained on or removed from a site for which a CAR has been issued, the report will be closed after a follow-up radiation survey has indicated that no further adverse environmental impact is evident.

2.5 SURVEY METHODS AND PROCEDURES

Surveys documented by this report include road/railroad surfaces, cribs, stabilized burial grounds, covered ponds and ditches, tank farm perimeters, active burial ground perimeters, unplanned release sites and other radiation areas. Methods and procedures for these surveys can be found in WHC-CM-7-4, Operational Environmental Monitoring; WHC-CM-1-6, WHC Radiation Control Manual; HSRM-1, Hanford Site Radiological Control Manual; and WHC-IP-0718, Health Physics Procedures.

2.5.1 ROAD/RAILROAD SURVEYS

Road Surveys are performed with a Mobile Surface Contamination Monitor (MSCM) vehicle equipped with sodium iodide detectors or plastic scintillators. Railroad Surveys are conducted with a vehicle equipped with "high railers", which allows the vehicle to travel both on the roads or railroads, and sodium iodide detectors. The detector height is adjustable in all cases and the average survey height is one foot.

The vehicles are driven at less than five miles per hour. If activity above background is detected, the vehicle is stopped and a thorough survey is made with an Eberline Model BNW-1 portable survey instrument equipped with a pancake type probe to identify the extent of the contamination. Appropriate management is notified if road/railroad contamination is identified, and corrective actions are initiated.

2.5.2 WASTE SITES AND OTHER RADIATION AREA SURVEYS

Surveys at waste sites and other radiation areas may be conducted with vehicles equipped with radiation detection instruments or with hand-held field instruments. Field instrument survey results are reported in disintegrations per minute (using a conversion factor of 10 dpm/cpm) as detected by using a Geiger-Mueller detector for beta/gamma radiation equipped with a pancake type probe. Alpha survey results are reported in disintegrations per minute as measured with a portable alpha meter (PAM) or a portable alpha counter (PAC-6). Surveys include the perimeter and portions of the ground surface of radiation areas. Wherever possible, smear surveys are made on the surface of exposed equipment and other hard surfaces within a radiation area. Vegetation, animal burrows, and animal feces are also monitored to detect biological transport. Detailed survey practices and procedures are described in WHC-CM-7-4, Operational Environmental Monitoring; WHC-CM-1-6, WHC Radiation Control Manual; HSRCM-1, Hanford Site Radiological Control Manual; and WHC-IP-0718, Health Physics Procedures.

3.0 SURVEY RESULTS

All the routine environmental radiological surveys scheduled during July, August, and September 1995 were completed with the exception of the following waste sites:

<u>Waste Site</u>	<u>Reason for Deviation</u>
116-D-3	Inaccessible due to Pump and Treat in progress.
166-H-6	Active Decommissioning in progress.
UN-100-F-1	Inaccessible area posted "DANGER DO NOT ENTER"

These surveys will be rescheduled and be completed at a later date. Surveys of active and inactive waste disposal sites included cribs, trenches, burial grounds, covered ponds and covered ditches. The survey schedule for environmental sites is outlined in WHC-CM-7-4, Section 12, and in WHC-SP-0098-5, Rev. 0.

One hundred and three environmental radiological surveys were performed during the third quarter of 1995. Contamination above background levels was found at six of the surveyed active waste site areas and seven of the inactive waste site areas. Contamination levels ranging from a low of 2,000 dpm to a high of 500,000 dpm were reported. Of the contamination found, one was located in an SC area and twelve were located in URM or unposted areas.

The contamination found in three of the URM areas was immediately cleaned up and no further action was required. The contamination found in the remaining URM areas was posted and will require decontamination. Radiation Problem Reports (RPR's) were issued and the remaining sites were turned over to the landlord for further action.

3.1 RADIOLOGICAL SURVEY SUMMARY

This report provides a synopsis of the radiological survey results conducted in July, August, and September 1995. The stabilization and clean-up efforts for the 105-KE/KW basins; 216-T-4-2 ditch; 241-T Tank Farms; 241-TX-155 and 241-UX-151/241-UX-152 Diversion Boxes; 241-EW-151 Vent Station; 241-A and 241-U Tank Farm Perimeters; and portions of the TC-4 Railroad Spur, 241-A, 241-AY, 241-AZ, 241-C, 241-TY, and 241-U Tank Farms were completed during this period.

3.2 COMPLIANCE ASSESSMENT REPORTS ISSUED

No unsatisfactory CARs were issued during the third quarter of 1995.

3.3 SURVEILLANCE/COMPLIANCE REPORTS CLOSED

SCIRs closed during the third quarter of 1995 are as follows:

<u>SCIR</u>	<u>CUSTODIAN</u>	<u>SITE</u>
8910EP200-043	TFO	UN-216-E-5, 241-B-154 Diversion Box

3.4 STATUS OF OPEN SURVEILLANCE AND COMPLIANCE REPORTS

Six SCIRs, from past activities, remained open at the end of the third quarter of 1995. These reports are summarized on Table 1 to include the referenced site number, priority ranking points (maximum of 15 points based on contamination levels, location and mobility), responsible custodian, SCIR report number, and estimated completion date.

Abbreviations used on Table 1 include:

CAR - Compliance Assessment Report

SCIR - Surveillance/Compliance Inspection Report

ECD - Estimated Completion Date

ERC - Environmental Restoration Contractor

TFO - Tank Farm Operations

PTS - Points

TBD - To Be Determined

TABLE 1
OPEN SCIRs AND CARs
 (maximum 15 points)

SCIR/CAR	SITE	DATE INITIATED	MONTHS OPEN	ECD	SITE RANKING	CUSTODIAN
8901EP200-001	UN-216-E-16 TC-4 RR SPUR	01/01/89	74	11/31/95	8	PUREX
8909EP200-036	241-B FARM PERIMETERS	09/01/89	66	09/30/95	13	TFO
9007EP200-056	BX-BY TANK FARM PERIMETERS	07/20/90	54	12/30/95	13	TFO
9008EP200-068	C-TANK FARM PERIMETERS	08/13/90	53	12/30/95	13	TFO
9110ERI-001	UN-216-E-36 216-B-64 BASIN	12/25/91	36	CLOSED	12	B-PLANT
9203ERI-002	241-U TANK FARM PERIMETERS	03/17/92	32	09/30/95	8	TFO
9208ERI-006	241-S, SX, SY TANK FARM PERIMETERS	08/14/92	28	09/30/95	12	TFO

4.0 SUMMARY

All the routine outdoor radioactive surveys were completed during the third quarter of 1995 in the 100, 200-East/West, 300 and 600 areas with the exception of three inactive waste sites.

No unsatisfactory CARs were issued (Section 3.2)

One SCIR was closed (Section 3.3)

Six SCIRs remained open (Table 1). Open reports have been addressed and clean-up plans with completion dates are being developed or are to be provided to Near-Field Monitoring.

RADIOLOGICAL POSTING CHANGES

During the third quarter of 1995, 14.1 hectares (34.9 acres) were radiologically down posted from SC to URM or released from posting and 5.9 hectares (14.7 acres) were found to be contaminated and reposted as a soil contamination area (SCA).

Radiological posting changes, by waste site, noted during the third quarter of 1995 are as follows:

The 105-KE/KW Basins were stabilized and down posted from SC to URM, 8.1 hectares (20 acres).

The 216-T-4-2 Ditch was backfilled, stabilized, and down posted from SC to URM, 0.93 hectares (2.29 acres).

The 241-T Tank Farm was surface stabilized and down posted from SC to URM, 2.56 hectares (6.3 acres).

The 241-TX-155 and 241-UX/151/241-UX-152 Diversion Boxes were surface stabilized and down posted from SC to URM, 50.5 square meters, (0.01 acres).

The 241-EW-151 Vent Station was surface stabilized and down posted from SC to URM, 37.2 square meters (400 Square feet).

The 241-A and 241-U Tank Farm Parameters were stabilized and down posted from SC to URM or released, 0.2 hectares (0.5 acres).

Portions of the 241-A, 241-AY, 241-AZ, 241-C, 241-TY, AND 241-U Tank Farms were surface stabilized and down posted from SC to URM, 1.96 hectares (4.83 acres).

A portion of the TC-4 Rail Spur was stabilized and down posted from SC to URM, 0.4 hectares (0.9 acres).

Spotty contamination was found in areas to the south and to north of the 241-EW-151 Vent Station and posted SCA, 5.9 hectares (14.7 acres). The cause of the contamination is suspected to be from biotic intrusion.

DISTRIBUTION

Number of CopiesONSITE

41

WESTINGHOUSE HANFORD COMPANY

I. J. Austin	T4-01
H. A. Besel	T1-27
D. M. Bogen	R3-50
D. E. Bullock	T4-08
D. L. Chase	X3-85
D. A. De Lucchi	R1-51
L. P. Diediker	S3-95
J. J. Dorian	S3-24
R. E. Elder	T7-37
D. P. Ellingson	T1-27
R. F. Giddings	S3-24
R. D. Gustavson	R1-51
G. S. Hauger	T4-01
A. R. Johnson	H6-20
B. H. Lueck Jr.	S7-81
C. L. Looney	S3-24
B. M. Markes	H6-20
A. K. McDowell	R1-51
S. M. McKinney (6)	S3-95
D. L. Mitchell	H6-32
D. J. Newland	T7-37
J. L. Parson	S5-66
B. L. Poorman	S5-10
O. L. Rasmussen	R1-51
M. P. Rung	S8-07
J. W. Schmidt	H6-20
J. L. Shelor	T7-37
R. A. Schieffer	T1-27
J. E. Thrasher	S6-70
R. J. Thomas	R3-12
R. R. Thompson	H6-32
D. J. Watson	X3-79
R. L. Watts	T7-37
O.S.T.I. (2)	A3-36
Central Files	A3-88

DISTRIBUTION (continued)

Number of Copies

5	<u>U.S. DEPARTMENT OF ENERGY - Richland</u>	
	G. M. Bell	A5-52
	M. J. Furman	H4-83
	J. B. Hall	A5-55
	P. M. Pak	H4-83
	D. C. Ward	A5-55
2	<u>PACIFIC NORTHWEST LABORATORY</u>	
	R. L. Dirkes (2)	K6-75
1	<u>KAISER ENGINEERS</u>	
	P. I. Thakkar	G3-06
18	<u>BECHTEL HANFORD, INC.</u>	
	A. I. Davis	X0-21
	L. A. Dietz	H6-07
	D. B. Erb	H6-01
	J. R. Freeman-Pollard (2)	H6-04
	J. T. Hadley	H4-79
	W. M. Hayward	T7-05
	J. E. Hodgson	T7-12
	R. A. Hughes	H4-87
	W. L. Osborne	T7-05
	R. A. Lewis	H4-79
	L. A. Mihalik	H4-79
	J. E. Parsons	X0-23
	W. H. Price	H6-04
	K. A. Smith	H4-88
	C. D. Wade	T7-05
	S. R. Weil	H4-79
	D. C. Weekes	X0-37