UNCLASSIFIED

CF. 11/1/50

IN. EX. ORED.
10-11-50

IC 11/1/50

INVENTORIED
11/1/50

INV. 9-54 MSW

ALFORD 10. MLM-172
This document contains 10 pages
This is copy 157 of 167 Series.ISSUED TO: J.L. RichardsonTHIS IS A CLASSIFIED DOCUMENT

1. This document contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sec. 793 and 794, and the transmission or the disclosure of its contents in any manner to an unauthorized person is prohibited and may result in severe penalties or forfeiture under applicable Federal Laws.

2. This document contains information which is classified in the Atomic Energy Act of 1946, as amended, and the regulations thereunder, and the transmission or the disclosure of its contents in any manner to an unauthorized person is prohibited and may result in severe penalties or forfeiture under applicable Federal Laws.

3. This document contains information which is classified in the Atomic Energy Act of 1946, as amended, and the regulations thereunder, and the transmission or the disclosure of its contents in any manner to an unauthorized person is prohibited and may result in severe penalties or forfeiture under applicable Federal Laws.
4. This document contains information which is classified in the Atomic Energy Act of 1946, as amended, and the regulations thereunder, and the transmission or the disclosure of its contents in any manner to an unauthorized person is prohibited and may result in severe penalties or forfeiture under applicable Federal Laws.

5. This document contains information which is classified in the Atomic Energy Act of 1946, as amended, and the regulations thereunder, and the transmission or the disclosure of its contents in any manner to an unauthorized person is prohibited and may result in severe penalties or forfeiture under applicable Federal Laws.

6. This document contains information which is classified in the Atomic Energy Act of 1946, as amended, and the regulations thereunder, and the transmission or the disclosure of its contents in any manner to an unauthorized person is prohibited and may result in severe penalties or forfeiture under applicable Federal Laws.

TO	DATE BY	INITIALS	REMARKS (Signature)

UNCLASSIFIED

MASTER

Excluded from automatic
downgrading and
declassification

RECEIVED
OCT 11 1950
OSTI

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

UNCLASSIFIED

THIS DOCUMENT CONSISTS OF 10 PAGES
THIS IS COPY 157 OF 161 #

DATE ~~SECRET~~ INITIALS HR

MEM-172

Contract Number AF-33-1-GEN-53

Classification changed to Unclassified by 6/24/79

authority of P.B. Rowland, Jr. 4/26/70

MONSANTO CHEMICAL COMPANY - URBANA, Illinois, V. Weininger, 7/14/70

DAYTON, OHIO

M. M. Harding
Laboratory Director

SCREENING STUDIES AT MONROE LABORATORY
(Information Report)

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Date: August 24, 1948

Prepared by: John E. Bradley

Distributed: Aug 27 1948

John L. Richmond

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

UNCLASSIFIED

~~SECRET~~

MEM-172

DISTRIBUTION

- 1-190. - L. H. Williams
Oak Ridge National Laboratory
- 151. - M. H. Gearing
- 152. - J. J. Durbage
- 153. - Area Manager
- 154. - Area Manager
- 155. - Area Manager
- 156. - C. E. Bradley
- 157. - J. L. McDonald
- 158. - Central Files
- 159. - Central Files
- 160. - Central Files
- 161. - Central Files

~~SECRET~~

UNCLASSIFIED

~~SECRET~~

UNCLASSIFIED

MEM-172

PART I - SCOPE OF ALPHA CONTAMINATION

At the present time, our work entails a very limited use of shielding for protection from beta and gamma radiation. In the few instances where it has been necessary to incorporate such protection into our laboratory design, operations are easily performed by valve handles extending through a lead or concrete barrier. Preliminary studies in neutron protective barriers have been made at this site, and will be discussed by Mr. John L. Johnson.

Our most pressing problem is the prevention of the spread of alpha contamination, for which purpose the "elephant" is an all-purpose, yet, not over-designed. The basic function of this hood is to protect the operator from alpha irradiation and the ingestion or inhalation of alpha contaminants.

Design of the "elephant" is based on two major premises.

1. A impenetrable barrier is placed between the chemist and the system in which the active material is handled.

A positive differential is maintained at all times between the interior of the hood and the system in which the active material is handled. It is assumed that in the event of a casual leak from the higher pressure of the system containing the chemist will cause a flow of air away from the chemist to the system already containing the active material. A rapid air flow is maintained through each system. The incoming air is tempered, fresh air from which the dust has been removed. The exhaust air is filtered to remove activity and then vented through a high stack.

The hood are so designed that as many tasks as possible are accomplished from the clean or "outside" side of the barrier. These include the use of service piping, auxiliary potential controllers, cold traps, and process reagents. As many operations as possible are performed by use of extension handles extending through the barrier. More delicate tasks are performed through air-ports sealed with plastic sleeves attached to rubber gloves.

Extensive alterations or repairs are made from a contaminated service corridor situated at the rear of each row of hoods. Personnel gain access and/or egress to this service corridor through an air lock and a change room. These personnel must wear full protective clothing while they are present in the service corridor.

UNCLASSIFIED

~~SECRET~~

UNCLASSIFIED

~~SECRET~~

MEM-172

PART II - NEUTRON SHIELDING

ABSTRACT

Neutron shielding is done to protect workers from excessive radiation and to keep a low neutron background for research in neutron counting. To meet health standards the total neutron flux allowable is 150 n./cm.²/sec. per eight hours, or 50 n./cm.²/sec. per twenty-four hours.

Literature values for the absorption coefficients of paraffin and water are considered, and some experimental data is presented which approximately confirms them.

A description of barriers at Mound Laboratory is given.

Plans for future work on slowing-down of fast neutrons and capture of slow neutrons are included.

A. INTRODUCTION

Neutron shielding is important principally to two groups at Mound Laboratory. The group prepares various types of neutron sources and must either work behind barriers or at considerable distance to meet health standards. The other group is engaged in research in neutron counting and must keep the neutron background low.

In this report barriers at Mound Laboratory are described and data on which the design is based are given. It is realized that there are inaccuracies in neutron counting and absorption coefficients and that they are subject to revision.

In addition to neutron shielding, control of alpha contamination as outlined in Part I of this report must be considered at the same time. However, the combination is a major engineering problem and is only partially solved at the present time.

B. TYPES OF RADIATION AND SOURCES

The radiations encountered are fast neutrons from alpha-neutron and gamma-neutron reactions and the gamma radiation accompanying neutron emission or from gamma active isotopes.

UNCLASSIFIED

~~SECRET~~

UNCLASSIFIED

MEM-172

The Roentgen equivalents for some radiations and the tolerances for neutrons of varying energies are listed below:
A dosage of 0.1 Roentgen per eight hours is considered tolerance.

<u>Radiation Equivalent to 0.1</u> <u>Roentgen per Eight Hours</u>	<u>Neutron Energy</u>	<u>Tolerance</u> <u>Neutrons/cm.²/sec.</u>
50 2 Mev. betas/cm. ² /sec.	0.1 Mev.	1000
200 2 Mev. neutrons/cm. ² /sec.	0.5 Mev.	360
3300 2 Mev. photons/cm. ² /sec.	1.0 Mev.	230
6600 1 Mev. photons/cm. ² /sec.	2.0 to 3.0 Mev.	200

Our problem is primarily one of neutron shielding, since the proportion of gamma is low enough that neutron barriers will reduce gamma below tolerance.

Until about one year ago the neutron tolerance used at this site was 200 n./cm.²/sec. for eight hours exposure. The figure is now 150 n./cm.²/sec. per eight hours, or 50 n./cm.²/sec. per twenty-four hours. In calculating tolerance distance and time of exposure the inverse square law is assumed, that is, the time permissible at one-half of a given tolerance distance is one-fourth the time at the given distance.

2. ABSORPTION OF NEUTRONS IN PARAFFIN AND WATER

Any radiation emitted from a point will be reduced in intensity at a distance x from that point by a factor of $4/\pi x^2$. In addition, it will be reduced by some factor which is a function of the medium through which it passes. This is referred to as the absorption coefficient of the substance. The decrease in intensity may be expressed mathematically as

$$dI = -\mu I \, dx, \text{ or}$$

$$\ln I = -\mu x, \text{ and}$$

$I = I_0 e^{-\mu x}$, where I_0 is the original intensity and I the intensity after traversing x centimeters of the substance in question.

UNCLASSIFIED

~~SECRET~~

UNCLASSIFIED

MCM-172

When $I = \frac{I_0}{2}$,

$$\ln \frac{I_0}{I} = \ln 2 = 0.693 = \mu X_{1/2}$$

where $X_{1/2}$ = thickness to stop 1/2 the radiation. The radiation at a distance X from its origin would then be affected by distribution and absorption and would be

$$I = \frac{I_0}{4 \pi X^2} e^{-\mu X}$$

This may also be written $I = \frac{I_0}{4 \pi X^2} \times \frac{1}{2^{X/X_{1/2}}}$

Diffusion is not taken into account by this equation, as pointed out by Rich.³ He developed an equation of the form

$I = \text{const.} \times X^{-1} e^{-\mu X}$ and calculated absorption coefficients, which differed less than five per cent from those determined experimentally. Measurements by the Physics Group⁴ of the fast neutrons have passed through paraffin and the thermal neutrons counted backed calculations. For most purposes it is sufficient, therefore, to neglect diffusion.

The absorption coefficient for fast neutrons in paraffin is given by Fesetti⁵ as 0.124 cm^{-1} . Substitution of this value in the proper equation above gives an $X_{1/2}$ for paraffin of 5.6 centimeters. Information obtained at Oak Ridge⁶ indicated that $X_{1/2}$ for paraffin may be 5.0 centimeters.

Of course, absorption coefficients should be different for neutrons of varying energy. This was found to be the case in measurements made by the Physics Group, as shown in the following tabulation.⁷

Type of Source	Absorption Coefficient in Paraffin	$X_{1/2}$
Polonium-beryllium	0.0975 cm^{-1}	7.11 cm.
Radium-beryllium	0.124	5.59
Polonium-fluoborate	0.148	4.44
Polonium-toron	0.148	4.44

UNCLASSIFIED

~~SECRET~~

UNCLASSIFIED

~~SECRET~~

NLM-172

Thus far, absorption in paraffin only has been considered. The effect of paraffin is essentially one of slowing the neutrons to thermal energies. For capture of thermal neutrons, boron in the form of such compounds as borax, boric acid and boron carbide may be used. A thin layer of boron compound on the side of the shield away from the source is sufficient to capture thermal neutrons, but mixing uniformly is more efficient for gamma absorption.⁶ Because of difficulty in getting uniform mixtures of boron compounds in paraffin water is used, though it is less effective than paraffin. Work done at Oak Ridge showed the $X_{1/2}$ values for paraffin and water to be in the ratio 5 to 6, and calculations by Rich³ confirm this ratio.

An experiment in which varying percentages of borax were dissolved in water and the fast and slow neutrons and gammas from polonium-beryllium measured showed two per cent borax to be most effective for stopping slow neutrons and gammas and to have little effect on fast neutrons.⁸

A number of cylindrical storage containers have been designed, using an $X_{1/2}$ for water of 6.71 cm. These were filled with water-borax solution, neutron sources placed at the centers, and neutron counts made at the side. In every instance the count was somewhat below the calculated flux.

D. BARRIERS AT MOUND LABORATORY

The $X_{1/2}$ value for water of 6.71 cm. was used in designing barriers at Mound Laboratory. They will be filled with water containing two per cent of borax by weight. Each barrier will be two feet in thickness, three feet in width and six feet in height, with a glass panel 18 by 24 inches. There are two barriers in front of each hood, which are independently operated by hydraulic lifts, so that they can be positioned at any height from floor level to six feet.

A neutron flux of 3.7×10^9 will be reduced to the tolerance level of 150 n./cm.²/sec., or a flux of 10^7 will be reduced to 0.4 n./cm.²/sec. if the absorption coefficient for water is correct.

A water-borax filled storage tank is also provided in which neutron sources will be at least three feet from the wall. On the same basis this will reduce a neutron flux of 3.7×10^9 to 3 n./cm.²/sec.

The effectiveness of water as an absorber of neutrons is shown graphically in Figure 1 in which tolerance distance is plotted against neutron flux for air and water.

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

MLM 172

~~SECRET~~

UNCLASSIFIED

MLM-172

E. FUTURE WORK

Research on shielding will be done in connection with other work and will receive the attention of two men part time.

It is planned to determine the absorption coefficients of several hydrates which have a water density above one. Several compounds of interest are $\text{Al AsO}_4 \cdot 8 \text{H}_2\text{O}$, $\text{Mg B}_2\text{O}_4 \cdot 8 \text{H}_2\text{O}$, and $\text{Na}_2\text{PO}_4 \cdot 10 \text{H}_2\text{O}$ in which the water has densities of 1.40, 1.31, and 1.32 gm./cc., respectively. Magnesium borate should be especially effective, as the boron will serve to capture slow neutrons and gammas.

The number of collisions required to decrease the energy of a neutron from E_0 to E is given by

$$n = \frac{M+1}{2} \ln \frac{E_0}{E}$$

where M = mass number of the element concerned. Two factors in this equation will tend to make the number of collisions a minimum. If M is small, n will be small. Hydrogen is the lightest element, and for this reason paraffin and water are used because they are rich in hydrogen.

The other method of reducing n is to capture the neutron at as high an energy as possible, thereby making E_0/E small. Boron has a resonance capture in the thermal range, 0.025 ev., which gives a high value of E_0/E . Iodine is reported to have resonance captures at 20.6, 37 and 42 ev., manganese at 300 ev., and cobalt at 1000 to 10,000 ev. It is intended to determine the effect of such elements on barrier thickness.

REFERENCES

1. C. W. J. Wende, The Computation of Radiation Hazards, Project Report M-1324.
2. J. M. Cork, Radioactivity and Nuclear Physics, D. Van Nostrand Company, Inc. (1947).
3. Joe Rich, Determination of the Number of Thermal Neutrons Leaving a Spherical Tank of Water of Radius R , Information Report No. 33, (5/29/47). (See Report LA-24, p. 290).

UNCLASSIFIED

~~SECRET~~

~~SECRET~~

UNCLASSIFIED

MLM-172

4. Physics Progress Report, September 16-30, 1946.
5. Franco Basetti, Elements of Nuclear Physics, Prentice-Hall, Inc. (1936).
6. G. O. Gatzert, A Summary of Information Obtained from an Inspection of Clinton Laboratories Concerning Barrier Systems and Remote Controls, Information Report No. 27, (8/30/46).
7. Physics Progress Report, September 1-15, 1946.
8. Physics Progress Report, February 1-15, 1947.
9. Wi, Rainwater, and Ravens, Slow Neutron Velocity Spectrometer Studies, MDDC-480 and MDDC-405.

JEE:JIR/rec

~~Cautions~~

~~This document contains information affecting the National Defense of the United States within the meaning of the espionage laws of the United States and the transmission or the disclosure of its contents in any manner to an unauthorized person is prohibited and may result in severe criminal penalties under applicable Federal laws.~~

~~Restricted Data~~

~~This document contains restricted data as defined in the Atomic Energy Act of 1946.~~

UNCLASSIFIED

~~SECRET~~