BNL-61103
Informal Report

RECEIVED

DEC 27 1995

OSTI

das

SOLVING INCOMPRESSIBLE FLOW PROBLEMS WITH
PARALLEL SPECTRAL ELEMENT METHODS

HONG MA

OCTOBER 1994

DEPARTMENT OF APPLIED SCIENCE

BROOKHAVEN NATIONAL LABORATORY
UPTON, LONG ISLAND, NEW YORK 11973

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED 85

BNL 61103
Informal Report

**SOLVING INCOMPRESSIBLE FLOW PROBLEMS WITH
PARALLEL SPECTRAL ELEMENT METHODS**

Hong Ma

October 1, 1994

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ANALYTICAL SCIENCES DIVISION
DEPARTMENT OF APPLIED SCIENCE
BROOKHAVEN NATIONAL LABORATORY
ASSOCIATED UNIVERSITIES, INC.

Under Contract No. DE-AC02-76CH00016 with
the U.S. Department of Energy

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency, contractor, or subcontractor thereof.

Abstract

Parallel spectral element models are built for the Navier-Stokes equations and the shallow water equations with nonstaggered grid formulations. The optimized computational efficiency of these parallel spectral element models comes not only from the exponential convergence of their numerical solutions, but also from their efficient usage of the powerful vector-processing units of the latest parallel architectures. Furthermore, the communication cost of the spectral element model is lower than that of the h-type finite element model, partly because many fewer redundant nodal values have to be stored. The nonstaggered grid formulations perform well in iterative procedures which are highly in parallel. Implementations of these models are carried out on the Connection Machine systems. The present work shows that the high-order domain decomposition methods can be efficiently applied in a data parallel programming environment.

Table of Contents

Abstract	iii
List of Figures	vi
List of Tables	vi
Introduction	1
Governing Equations	3
Spectral Element Discretizations	4
Spectral Element Iteration Solver	9
Parallel Algorithm and Implementation	11
Model Tests	21
Conclusions	23
Acknowledgments	23
References	37

List of Figures

A spectral element mesh for the Atlantic Ocean	2
Flow diagram of the parallel execution of a spectral element matrix operation ...	12
Symbolic diagrams for direct stiffness summation	16
Plots of maximum pointwise errors	25
Plots of the two-dimensional driven cavity problem with $R_e = 1$	27
Plots of the two-dimensional driven cavity problem with $R_e = 100$	30
Plots of the number of pressure iterations per time step for the two-dimensional Navier-Stokes equation model	33

List of Tables

CM-5 timing results per pressure iteration (2D)	20
CM-5 timing results per pressure iteration (3D)	20
CM-5 timing results per time step for the spectral element shallow water equation model	20
Equivalent performance for CM-5 for the spectral element shallow water equation model	21
CM-5 timing results per time step for the 2D N-S model	24

1 Introduction

With the rapid advancement of parallel computers, there is an increasing need for new numerical algorithms which can fully exploit the potential of modern parallel architectures. This need is especially keen in the field of computational fluid dynamics (CFD) where current techniques are challenged by the enormous degrees of freedom required to solve large-scale, three-dimensional, laminar and turbulent flows. Partly due to this reason, domain decomposition methods recently have received much attention because they are natural choices for parallelism [1, 2].

The development of the spectral element algorithms and their applications in solving incompressible flow problems [3, 5, 7, 10, 11] have demonstrated the enormous potential of the p-type of finite element method in improving computational efficiency. Like the spectral method, the spectral element method uses high-order polynomials as trial functions, but like the finite element method, it decomposes the computational domain into many elements and defines local trial functions. The hybrid character of the spectral element method enables it to overcome the shortcomings of both the spectral method and the finite element method but still retains their advantages. Since the trial functions of the spectral element method are local, it can handle complex geometry easily (Figure 1). On the other hand, it still is a high-order weighted residual method, so the exponential convergence rate is achieved as the order of polynomials is increased. Therefore, it is more efficient than low-order numerical methods, such as the finite difference and finite element methods.

Another important aspect which greatly enhances the computational efficiency of the spectral element method is the natural fit of this method to parallel computing. The main difference between the spectral element method and the spectral multi-domain method is that the C^0 and C^1 boundary conditions at the interface of the

Figure 1 A spectral element mesh for the Atlantic Ocean.

elements have to be enforced explicitly in the latter. By contrast, the spectral element method uses the variational principle to guarantee C^0 and C^1 (weakly) continuity at the interface, therefore, parallel algorithms can be implemented conveniently. Fischer and Patera [3] successfully implemented their spectral element model on MIMD (Multiple Instructions, Multiple Data) type of computers.

This paper is about the development and application of the parallel spectral element models for the Navier-Stokes equations and the shallow water equations with nonstaggered grid formulations. The performance of these models on the Connection Machine systems (CM-2 and CM-5), which are SIMD architectures, are analyzed through numerical examples. The present work shows that the spectral element models are very well suited for data parallel programming.

2 Governing Equations

In the present work, we study irrotational and rotational flows, which are governed by the following two sets of equations, respectively.

2.1 Incompressible Navier-Stokes Equations

Three-dimensional, incompressible Navier-Stokes equations in nondimensionalized form can be written as

$$\frac{\partial \mathbf{u}}{\partial t} + (\mathbf{u} \cdot \nabla) \mathbf{u} = -\nabla p + \frac{1}{R_e} \nabla^2 \mathbf{u} \quad (2.1)$$

$$\nabla \cdot \mathbf{u} = 0 \quad (2.2)$$

where $\mathbf{u} = (u, v, w)$ is the velocity vector (u , v , and w are the velocity components in the x , y , and z directions, respectively); p is the pressure; $R_e = UL/\mu$ is the Reynolds

number, which is based on the characteristic values of the velocity (U), the spatial scale (L), and the viscosity parameter (μ) of the fluid.

2.2 Shallow Water Equations

When the horizontal scale of the flow is very large, the earth's rotational effect has to be considered. Then, Coriolis force terms have to be added to the Navier-Stokes equations above. For large-scale motions in the thin layer of fluid surrounding the earth's surface, the atmosphere, and the ocean, the governing equations often times can be simplified as the so-called shallow water equations, where horizontal velocities are independent of the vertical coordinate, z , and the vertical momentum equation does not appear explicitly. With an equatorial nondimensionalization scheme [6], the shallow water equations can be written as

$$\frac{\partial \mathbf{u}}{\partial t} + (\mathbf{u} \cdot \nabla) \mathbf{u} + \omega \times \mathbf{u} = -\nabla h + \frac{1}{R_e} \nabla^2 \mathbf{u} \quad (2.3)$$

$$\frac{\partial h}{\partial t} + (\mathbf{u} \cdot \nabla)(1 + h) + (1 + h) \nabla \cdot \mathbf{u} = 0 \quad (2.4)$$

where $\mathbf{u} = (u, v, 0)$, $\omega = (0, 0, y)$.

3 Spectral Element Discretizations

The basis functions used in the present work, $h_i(s)$ ($s \in [-1, 1]$), are the so-called Gauss-Lobatto-Legendre polynomials [11] defined by

$$h_i(s) = -\frac{(1-s^2)L'_N(s)}{N(N+1)L_N(s_i)(s-s_i)} \quad (i = 0, 1, \dots, N) \quad (3.1)$$

where L_N is the N^{th} order Legendre polynomial, L'_N is its first derivative and the collocation point s_i ($i=1,2,\dots,N-1$) is the i^{th} root of $L'_N(s)$ and $s_0 = -1$, $s_N = 1$.

By this definition we know that $h_i(s_j)$ is a Kronecker delta function, i.e.,

$$h_i(s_j) = \delta_{ij} \quad \forall i, j \in \{0, 1, \dots, N\}^2 \quad (3.2)$$

Then a basis set can be defined as follows

$$\psi_{lm}^e(\xi, \eta) = h_l(\xi)h_m(\eta) \quad l, m \in \{0, 1, \dots, N\}^2 \quad (2D) \quad (3.3)$$

$$\psi_{lmn}^e(\xi, \eta, \zeta) = h_l(\xi)h_m(\eta)h_n(\zeta) \quad l, m, n \in \{0, 1, \dots, N\}^3 \quad (3D) \quad (3.4)$$

Let domain Ω be decomposed into K elements Ω^e , $e=1, 2, \dots, K$, in such a way that Ω^e has the following properties:

- $\bigcup_{e=1}^K \Omega^e = \Omega$;
- $\Omega^i \cap \Omega^j = \partial\Omega^{ij}$ if Ω^i and Ω^j are connected, and $\partial\Omega^{ij}$ is their common boundary;
- $\Omega^i \cap \Omega^j = \emptyset$ if Ω^i and Ω^j are not connected.

Let $\mathcal{G}$ be a continuous one-on-one mapping such that $\mathcal{G}(\Omega) = \mathcal{G}(\bigcup_{e=1}^K \Omega^e) = \bigcup_{e=1}^K \hat{\Omega}_e = \hat{\Omega}$. The adjacent properties among Ω^e are retained by $\mathcal{G}$, i.e., $\hat{\Omega}_e$ have the same adjacent properties. In addition, $\hat{\Omega}_e$ are assumed to be squares (for two-dimensional problems) or cubes (for three-dimensional problems), which can be achieved by properly choosing $\mathcal{G}$. In fact, with the three-dimensional basis set (3.4), for example, a mapping between Ω^e and $\hat{\Omega}_e$ can be defined in the following tensor-product format

$$(x, y, z) = (x_i, y_j, z_k) \psi_{ijk}^e(\xi, \eta, \zeta) \quad (3.5)$$

Where $(x, y, z) \in \Omega^e$ and $(\xi, \eta, \zeta) \in \hat{\Omega}_e$. We used the convention of tensor product that if a subscript is repeated it means a summation over all the components represented by that subscript. Similar conventions of tensor product summation will be used later

in this paper. The above definition, in particular, sets a one-on-one mapping between the interpolation points (x_i, y_j, z_k) ($\forall i, j, k \in \{0, 1, \dots, N\}^3$) on the subdomain Ω^e and the Gauss-Lobatto points (ξ_i, η_j, ζ_k) on $\hat{\Omega}_e$, because $(x, y, z) = (x_i, y_j, z_j)$ when $(\xi, \eta, \zeta) = (\xi_i, \eta_j, \zeta_k)$.

If we use a single subscript, q ($q \in \{1, 2, \dots, (N+1)^d\}$), (3.5) can be simplified as

$$\mathbf{x} = \mathbf{x}_q \psi_q^e(\xi) \quad (3.6)$$

(for the sake of convenience, we adopt two subscript systems for numbering the $(N+1)^d$ elements of a set, i.e., a system with a single subscript, and a system with d subscripts. These two systems are equivalent, and are used alternatively according to convenience throughout the rest of this paper).

With well distributed interpolation points on Ω^e , it can be proved that $\{\psi_q^e\}$ is complete (when $N \rightarrow \infty$) and orthogonal. Therefore, if $\mathcal{M}^e$ is the subspace spanned by $\{\psi_q^e\} \in \mathcal{H}^1$, then there is a projection Π_e , such that $\forall u^e(\mathbf{x} \mid \mathbf{x} \in \Omega^e) \in \mathcal{H}^1$

$$\Pi_e[u^e(\mathbf{x})] = u_h^e[\xi(\mathbf{x})] = u_q^e \psi_q^e[\xi(\mathbf{x})] \in \mathcal{M}^e \quad (3.7)$$

where u_h^e is the numerical approximation of u^e .

Then, it follows that there is a projection Π , such that $\forall u(\mathbf{x} \mid \mathbf{x} \in \Omega) \in \mathcal{H}^1$

$$\Pi[u(\mathbf{x})] = u_h = \bigcup_{e=1}^K u_h^e[\xi(\mathbf{x})] \in \bigcup_{e=1}^K \mathcal{M}^e \quad (3.8)$$

where u_h is the numerical approximation of u by the piecewise polynomials, and

$$\bigcup_{e=1}^K u_h^e \rightarrow u \quad \text{when } N^d \rightarrow \infty, \text{ or } \Delta_{max} \rightarrow 0 \quad (3.9)$$

where N^3 is the dimension of $\mathcal{M}^e$ and Δ_{max} is the maximum size of the subdomains Ω^e .

Thus, there are two ways to achieve better numerical precision with the spectral element method, i.e., by increasing the dimensions of the subspaces, N^3 , and/or the

number of the elements, K . It can be very flexible, and the optimum choice for these two parameters depends on each individual problem to be solved. This flexibility of the spectral element method is one of its most attractive features compared with the spectral method and the finite element method.

We use a semi-implicit temporal discretization scheme for the Navier-Stokes equations, i.e., the advection terms are treated with the third-order Adams-Bashforth scheme, and the mixing terms with the Crank-Nicolson scheme. Then, the resulting equations are

$$\frac{\mathbf{u}^* - \mathbf{u}^n}{\Delta t} = \sum_{i=0}^2 \alpha_i (\mathbf{u}^{n-i} \cdot \nabla) \mathbf{u}^{n-i} \quad (3.10)$$

$$\frac{\mathbf{u}^{n+1} - \mathbf{u}^*}{\Delta t} = -\nabla p^{n+\frac{1}{2}} + \frac{1}{R_e} \nabla^2 \mathbf{u}^{n+1} \quad (3.11)$$

$$\nabla^2 p^{n+\frac{1}{2}} = \frac{1}{\Delta t} \nabla \cdot \mathbf{u}^* \quad (3.12)$$

where $\alpha_0 = -\frac{23}{12}$, $\alpha_1 = \frac{4}{3}$, and $\alpha_2 = -\frac{5}{12}$.

Let solution $\mathbf{u}$ at time $n\Delta t$ on each subdomain Ω^e be expanded as

$$\mathbf{u}^e(\mathbf{x}, n\Delta t) = \mathbf{u}_q^e(n\Delta t) \psi_q^e[\xi(\mathbf{x})] \quad (3.13)$$

where $f_q^e(t)$ is the value of function f at the collocation point $\mathbf{x}_q \in \Omega^e$ at time t .

Applying the above spectral element discretization scheme to the weak forms of the Navier-Stokes equations, we derive the following matrix formulae

$$[B][\mathbf{u}^*] = [B][\mathbf{u}^n] + \Delta t \sum_{i=0}^2 \alpha_i \sum_{j=1}^d [C_j^{n-i}] [\mathbf{u}_j^{n-i}] \quad (3.14)$$

$$[B][\mathbf{u}^{n+1}] = [B][\mathbf{u}^*] - \Delta t \left\{ \mathbf{D}^T [p^{n+\frac{1}{2}}] + \frac{1}{R_e} [A][\mathbf{u}^{n+1}] \right\} \quad (3.15)$$

$$[A][p^{n+\frac{1}{2}}] = -\frac{1}{\Delta t} [\mathbf{D}] \cdot [\mathbf{u}^*] \quad (3.16)$$

where $[A]$ and $[B]$ are the stiffness matrix and mass matrix, respectively; $[C_j^n]$ and $[\mathbf{D}]$ are generalized vectors whose m^{th} components, $[C_{j,m}^n]$ and $[D_m]$, are the advection matrix and gradient matrix, respectively.

The boundary conditions used in the above derivations are:

$$\mathbf{u}(\mathbf{x}, t) = \mathbf{f}(\mathbf{x}, t) \quad \mathbf{x} \in \partial\Omega \quad (3.17)$$

$$p(\mathbf{x}, t) = g_1(\mathbf{x}, t) \quad \text{or} \quad \nabla p(\mathbf{x}, t) \cdot \mathbf{n} = g_2(\mathbf{x}, t) \quad \mathbf{x} \in \partial\Omega \quad (3.18)$$

where $\partial\Omega$ is the boundary of the computational domain, Ω .

The global matrix $[G]$ is obtained by directly assembling its elemental matrices $[G^e]$, i.e.

$$[G] = \sum_{e=1}^K [G^e] \quad (3.19)$$

The elemental matrices of the global matrices $[A]$, $[B]$, $[C_{m,j}^n]$, $[D_m]$ in Eqs.(3.14)-(3.16) are defined as follows

$$A^e(p, q) = \int_{\hat{\Omega}^e} \frac{\partial \psi_p^e}{\partial x_i} \frac{\partial \psi_q^e}{\partial x_i} |J^e| d\hat{\Omega}^e \quad p, q \in \{1, 2, \dots, (N+1)^d\}^2 \quad (3.20)$$

$$B^e(p, q) = \int_{\hat{\Omega}^e} \psi_p^e \psi_q^e |J^e| d\hat{\Omega}^e \quad p, q \in \{1, 2, \dots, (N+1)^d\}^2 \quad (3.21)$$

$$C_{m,j}^{n,e}(p, q) = \int_{\hat{\Omega}^e} \sum_{s=1}^{(N+1)^d} u_m^{n,e}(s) \frac{\partial \psi_s^e}{\partial x_j} \psi_p^e \psi_q^e |J^e| d\hat{\Omega}^e \quad p, q \in \{1, 2, \dots, (N+1)^d\}^2, \quad j, m \in \{1, \dots, d\}^2 \quad (3.22)$$

$$D_m^e(p, q) = \int_{\hat{\Omega}^e} \psi_p^e \frac{\partial \psi_q^e}{\partial x_m} |J^e| d\hat{\Omega}^e \quad p, q \in \{1, 2, \dots, (N+1)^d\}^2, \quad m \in \{1, \dots, d\} \quad (3.23)$$

where $u_m^{n,e}(s)$ is the s^{th} element of the vector $[u_m^n]$ at $t = n\Delta t$.

We chose the isoparametric spectral element discretization scheme, namely, using nonstaggered grids, for the present numerical model. The nonstaggered formulation avoids spurious pressure modes as staggered schemes do, and, at the same time, has the advantage that pressure is continuous across boundaries of the spectral elements. Only one set grids is required for both interpolation and quadrature, hence simplifying operations. In section 6, we show that the nonstaggered grid formulations do not

necessarily entail high costs for the iterative pressure solver as one might expect, and the two types of pressure boundary conditions in (3.18) make little difference in terms of computational efficiency.

The discretized shallow water equations have the following form

$$[B][\mathbf{u}^{n+1}] = [B][\mathbf{u}^n] + \Delta t \sum_{i=0}^2 \alpha_i \left\{ \sum_{j=1}^2 [C_j^{n-i}][u_j^{n-i}] - [D^T][p^{n-i}] - \frac{1}{R_\epsilon} [A][\mathbf{u}^{n-i}] \right\} \quad (3.24)$$

$$[B][h^{n+1}] = [B][h^n] + \Delta t \sum_{i=0}^2 \alpha_q \left\{ [D_1][u^{n-i}(1 + h^{n-i})] + [D_2][v^{n-i}(1 + h^{n-i})] \right\} \quad (3.25)$$

Details of deriving Eqs.(3.24) and (3.25) were given in [6].

4 Spectral Element Iteration Solver

For large-scale problems, iterative approaches are almost necessary to solve the matrix problems of (3.15) and (3.16) at a practical computational cost. A preconditioned conjugate gradient iterative method was used in the present work to solve the elliptic equation $[A][x] = [b]$, which has the following algorithm

$$\begin{aligned} [x_0] &= \textit{initial guess}; \quad [r_0] = [b] - [A][x_0]; \quad [q_0] = [P^{-1}][r_0]; \quad [s_0] = [q_0]; \\ \alpha_m &= [r_m] \cdot [s_m] / [q_m] \cdot \{[A][q_m]\}; \quad [x_{m+1}] = [x_m] + \alpha_m [q_m]; \\ [r_{m+1}] &= [r_m] - \alpha_m [A][q_m]; \quad [s_{m+1}] = [P^{-1}][r_{m+1}]; \\ \beta_m &= [r_{m+1}] \cdot [s_{m+1}] / [r_m] \cdot [s_m]; \quad [q_{m+1}] = [s_{m+1}] + \beta_m [q_m] \end{aligned} \quad (4.1)$$

where P is the Jacobi preconditioner.

Evaluation of the matrix-vector product, $[A][u]$, constitutes the operation count kernel of the spectral element iteration solver. Inherited from the properties of the spectral method, the number of operations for the matrix-vector product $[A][u]$ in the

present spectral element model would be proportional to KN^{2d} (d is the number of spatial dimensions) if a simple-minded algorithm were applied. Although the problem is less severe for the spectral element method than it is for the spectral method, it still hinders the efficiency of the 3-D model. Fortunately, the partial summation algorithm, which was first proposed by Orszag (1980) for the spectral method, can drastically reduce the cost of solving the matrix-vector product problem.

As an example, we analyze the three-dimensional case. Assume $[A]$ is the global stiffness matrix for the Laplacian operator. The straightforward spectral element formulation gives the tensor product form

$$[A][u](q, r, s) = \sum_{k=1}^K \sum_{l=0}^N \sum_{m=0}^N \sum_{n=0}^N A^k(q, r, s, l, m, n) u^k(l, m, n) \quad (q, r, s \in \{0, \dots, N\}^3) \quad (4.2)$$

where $[A][u](q, r, s)$ are elements of $[A][u]$; $A^k(q, r, s, l, m, n)$ are elements of the local stiffness matrix $[A^k]$ and $\sum'$ is the direct stiffness matrix summation. The evaluation of $[A][u]$, therefore, requires $O(KN^6)$ operations.

The present work uses the partial summation algorithm at the elemental level to evaluate $[A][u]$ more efficiently. $A^k(q, r, s, l, m, n)$ can be evaluated in the form of

$$A^k(q, r, s, l, m, n) = H^x(l, q) H^y(m, r) H^z(n, s) \quad (4.3)$$

where $H^p(i, j)$ are functions of i and j .

Therefore, the auxiliary matrices $[B]$ and $[C]$ can be constructed in the following way:

$$B(l, m, s) = \sum_{n=0}^N u^k(l, m, n) H^z(n, s) \quad (4.4)$$

$$C(l, r, s) = \sum_{m=0}^N B(l, m, s) H^y(m, r) \quad (4.5)$$

Then $[A^k][u^k]$ can be evaluated by

$$[A^k][u^k](q, r, s) = \sum_{l=0}^N C(l, r, s) H^x(l, q) \quad q, r, s \in \{0, 1, \dots, N\}^3 \quad (4.6)$$

Now, the total operation count in computing B , C , and $[A][u]$ is $O(KN^4)$; this is N^2 times less expensive than using the straightforward algorithm to evaluate the matrix-vector product. Generally, on sequential computers, the number of clock cycles needed to evaluate a matrix-vector product is $O(KN^{d+1})$. On distributed-memory parallel computers, however, this number of clock cycles is only a fraction of that needed by a sequential machine (see next section).

The greatly reduced operation count resulting from the partial summation algorithm is not the only advantage of the spectral element model in evaluating the matrix-vector product; it also has a much smaller storage requirement. In fact, the storage required to evaluate $[A][u]$ for a 3-D model would be $O(KN^3)$ instead of $O(K^2N^6)$ because the stiffness matrix elements are “computed on the fly” rather than stored in the memory.

5 Parallel Algorithm and Implementation

For a distributed-memory, massively parallel computer, which is the chosen architecture for the present model, remote memory access usually is much slower than local memory access. To efficiently implement the spectral element model on this type of computer, we must create a data parallelism which minimizes communication among processing nodes. This goal is achieved through a data-mapping scheme that allows for all the information related to a given spectral element to be collected in the memory of a single processor (Figure 2). On the Connection Machine system (CM-2 and CM-5), we pursue data parallelism by designing the layout of the arrays of the

Figure 2 Flow diagram of the parallel execution of a typical spectral element matrix operation.

spectral element model in such a way that the axes along the number of elements are assigned as parallel dimensions, and those along intra-element degrees of freedom as serial ones. The following is a three-dimensional example in CM Fortran syntax

```
REAL A(N,N,N,K1,K2,K3)
```

```
CMF$LAYOUT A(:SERIAL,:SERIAL,:SERIAL,:NEWS,:NEWS,:NEWS)
```

where K_1, K_2, K_3 are numbers of elements in each spatial dimension, separately, and N is the order of polynomials.

Basically, there are four types of algebraic computations involved in solving the discretized Navier-Stokes Equations (3.14)-(3.16), when the preconditioned conjugated gradient iteration method, (4.1), is applied

$$[r] = [A][u] \quad (5.1)$$

$$[s] = [B][u] \quad \text{or} \quad [B]^{-1}[u] \quad (5.2)$$

$$[t] = [C_{m,j}^n][u] \quad (5.3)$$

$$\alpha = [u] \cdot [v] \quad (5.4)$$

Operations in (5.1)–(5.3) are all matrix-vector products, except that the matrices in (5.2) and (5.3) are diagonal ones. The elements of $[A]$ and $[B]$ are constants which only need to be calculated once; those of $[C_{m,j}^n]$ are not, and they need to be evaluated at each time step. (5.4) is the inner product of two vectors.

Matrices in (5.1)–(5.3) are global ones, which means that they are the results of the direct stiffness summation. The way in which the direct stiffness summation is performed can significantly affect the efficiency of the parallel implementation of the model. In serial spectral element algorithms, direct stiffness summation usually is carried out automatically by using local and global node numbering systems. How-

ever, in data parallel programs we have to treat direct stiffness summation separately to avoid explicit message-passing.

We split the procedure of calculating matrix-vector products into two steps, each of which admits concurrency. At the first step, the matrix-vector products are carried out at the elemental level with, for example, the elemental Laplacian and mass matrices defined in (3.20) and (3.21)

$$r^k(i) = \sum_{q=1}^{(N+1)^d} A^k(i, q) u^k(q) \quad i \in \{1, 2, \dots, (N+1)^d\}, \quad k \in \{1, 2, \dots, K\} \quad (5.5)$$

$$s^k(i) = B^k(i) u^k(i) \quad i \in \{1, 2, \dots, (N+1)^d\}, \quad k \in \{1, 2, \dots, K\} \quad (5.6)$$

The array layout described at the beginning of this section defines a one-to-one correspondence between the spectral elements and the virtual processors. All data related to a given element are stored in the memory of a single processor. Therefore, there is no communication among neighboring processors during these elemental level computations, and they are performed concurrently across all virtual processors.

After applying tensor-product factorization, the computational complexities to evaluate (5.5) and (5.6) would be $C_1 K N^{d+1}/Q$ and $C_2 K N^d/Q$, respectively, where Q is the number of physical processors involved. On the Connection Machine systems, parallel data structure allows (5.6) to be performed in an array operation, which means that thousands of simultaneous multiplications are made across all the array elements. Hence, C_2 is a small number. Consequently, diagonal preconditioning (5.2) is especially efficient in the data parallel environment: it does not require direct stiffness summation, and only local computation is involved, which is very fast. Iteration counts can be reduced by twenty to thirty percent with about a one percent increase in cost.

The processing nodes on the latest CM-5 model are equipped with powerful vector-processing units that can further reduce the cost of elemental level computation.

These vector-processing units are most efficient when the order of the spectral elements is high.

The second step is to carry out direct stiffness summation, $\sum_{k=1}^K$, in which contributions from local nodes that share the same physical coordinates are first accumulated, and then assigned back to those local nodes. In a serial spectral element model, this procedure can be accomplished by using global and local index systems, and is automatically done as the matrix computation is made for each spectral element (Figure 3a). In the parallel spectral element model, however, it is more efficient to use a separate step for the direct stiffness summation. Since each spectral element has at least one edge (two-dimensional case) or one surface (three-dimensional case) that is shared by a neighboring element, the direct stiffness summation can be carried out simultaneously along these edges or surfaces enabling structured message exchange, i.e., edge-based message exchange for two-dimensional problems, and surface-based message exchange for three-dimensional ones. Since this kind of information exchange takes place along the linkages of the "macro-element-skeleton", it can be easily synchronized for all elements in the entire domain. The work per processor that is required in this procedure is $C_3 d K N^{d-1} / Q$. The structured message exchange mostly avoids explicit short messages, and it considerably improves the parallel efficiency of the spectral element model [3]. Figure 3b illustrates direct stiffness summation with surface-based message-passing.

With parallel prefix of the CM Fortran, MATMUL and SUM, the inner product (5.4) is executed completely in parallel. Its computational complexity is $C_4 K N^d / Q$. Due to the high level of concurrency afforded by the parallel prefixes, C_4 is a small number.

Eq.(3.14) only requires a direct method to solve. The computation kernel here is

Serial Direct Stiffness Summation For $[A][X]$

Figure 3 Symbolic diagrams for direct stiffness summation. (a) with the serial algorithm; (b) with the parallel algorithm.

Parallel Direct Stiffness Summation For $[A][X]$

Figure 3 (Continued)

the evaluation of the advection term (3.22) where concurrency can be achieved at different levels of the computation. We first evaluate the shears of velocities at all nodal points

$$\frac{\partial u_m^{n,e}(l)}{\partial x_j} = \sum_{s=1}^{(N+1)^d} u_m^{n,e}(s) \frac{\partial \psi_s^e}{\partial x_j} \\ l \in \{1, 2, \dots, (N+1)^d\}, \quad m, j \in \{1, 2, \dots, d\}^2, \quad e \in \{1, 2, \dots, K\} \quad (5.7)$$

This operation is executed concurrently across all virtual processors. With the partial summation method, the computational complexity for (5.7) is $C_5 K(N+1)^{d+1}/Q$.

(3.22) also can be written as

$$C_{m,j}^{n,e}(p, q) = \sum_{s=1}^{(N+1)^d} u_m^{n,e}(s) \frac{\partial \psi_s^e(q)}{\partial x_j} \int_{\hat{\Omega}^e} \psi_p^e \psi_q^e |J^e| d\hat{\Omega}^e \\ p, q \in \{1, 2, \dots, (N+1)^d\}^2, \quad j, m \in \{1, \dots, d\}^2 \quad (5.8)$$

Therefore, once the shears of velocities are obtained, the remaining operation to evaluate the advection terms is the same as that of (5.6). Hence, the total computational complexity of (5.8) is $C_2 K(N+1)^d/Q + C_5 K(N+1)^{d+1}/Q$.

We can undertake similar parallelization analysis for solving the discretized shallow water equations (3.24) and (3.25). In this case, the computational complexity for matrix-vector product and that for the convection term are the same as those derived for the Navier-Stokes equations, except $d = 2$. Since no iterative procedures are involved, the model for the shallow water equations is relatively inexpensive compared to a “true” three-dimensional model.

As spectral elements are of high-order, most of the costly operations are at the elemental level, and they are executed concurrently. The spectral granularity at the elemental level can take full advantage of the computing power that the latest processing units provide. The structured message exchange, combined with parallel

prefix, makes inter-element communication a lower-order rather than a high-order cost, compared to that of elemental level computation. This communication cost should be much smaller than that of the h-type finite element model, partially because many fewer redundant model values, shared by more than one element, have to be stored.

Tables I and II show the CM-5 timing results per pressure iteration in solving the two-dimensional and three-dimensional Navier-Stokes equations, respectively. We find that for a fixed order of the basis functions (N), expanding the size of the problem by increasing K (the number of the spectral elements) and, at the same time, increasing the number of processing nodes by the same proportion, hardly changes the computational cost in terms of CPU time per pressure iteration. Due to the high parallel efficiency, the spectral element models can fully take advantage of the highly scalable performance of the massively parallel architectures.

Table III shows the parallel performance for the spectral element model for the shallow water equations. To compare the performance of the spectral element model on the CM-5 with that on a sequential computer, say, RISC/6000, we made Table IV for “equivalent performance”, η_{EP} , which is defined as $\eta_{EP} = 28MFLOPS \times K \times \frac{T_{RISC}}{T_{CM5}}$. K is the number of spectral elements, T_{RISC} is the double precision timing on the RISC/6000 (model 560) which has a LINPACK performance rating of 28 MFLOPS ($T_{RISC}=0.012$ s per spectral element per time step), and T_{CM5} is the double-precision timing on the CM-5.

Table I CM-5 Timing Results per Pressure Iteration (2-D)

N	K	Num. Grid Pts.	Num. Nodes ^a	CPU (s)
7	1024	50625	32	0.062
7	4096	201601	128	0.063
15	1024	231361	32	0.317
15	4096	923521	128	0.318

a. Each cm-5 node has 4 vector-processing units and a peak performance rating of 128 MFLOPS.

Table II CM-5 Timing Results per Pressure Iteration (3-D)

N	K	Num. Grid Pts.	Num. Nodes	CPU (s)
4	4096	274625	64	0.106
4	32768	2146689	512	0.108
7	4096	1442897	64	0.473
7	32768	11390625	512	0.475

Table III CM-5 Timing Results (in seconds) per Time Step for the
Spectral Element Shallow Water Equation Model (N=16)

K	128 nodes	256 nodes	512 nodes
100	0.31	0.31	0.31
256	0.32	0.31	0.31
4900	0.66	0.48	0.32
10000	0.83	0.48	0.32
22500	1.71	0.97	0.66
40000	2.33	1.29	0.80
90000	-	-	1.6

Table IV Equivalent Performance^b for CM-5 (in MFLOPS) for the
Spectral Element Shallow-Water-Equation Model (N=16)

K	128 nodes	256 nodes	512 nodes
100	115	115	115
256	2789	2789	2879
4900	2650	3644	5466
10000	4301	7437	11156
22500	4725	8280	12170
40000	6208	10984	17850
90000	-	-	20081

b. See text for definition.

6 Model Tests

The exact solutions

$$u(x, y, t) = -\cos(x)\sin(y)\exp^{-2t} \quad (6.1)$$

$$v(x, y, t) = \sin(x)\cos(y)\exp^{-2t} \quad (6.2)$$

$$p(x, y, t) = -0.25[\cos(2x) + \cos(2y)]\exp^{-4t} \quad (6.3)$$

of the two-dimensional, incompressible Navier-Stokes equations [4] are used as a test for the parallel spectral element model (3.14)-(3.18).

The computational domain is $(x, y) \in [0, \pi] \times [0, \pi]$. The initial condition is given by the exact velocity solutions u and v at $t = 0$, and the exact solutions are used as boundary conditions for the velocity terms. We tried the Dirichlet pressure boundary condition

$$p^n(x, y) = -0.25[\cos(2x) + \cos(2y)]\exp^{-4n\Delta t} \quad (x, y) \in \partial\Omega \quad (6.4)$$

and the Neumann pressure boundary condition

$$\nabla p^n(x, y) = \frac{1}{\Delta t} \mathbf{u}^*(x, y, n\Delta t) \cdot \mathbf{n} \quad \mathbf{x} \in \partial\Omega \quad (6.5)$$

where $\mathbf{u}^*$ is computed by (3.14).

When the Neumann boundary condition (6.5) is applied, the Poisson equation (3.16) is singular but solvable. Pressure is determined within a constant. If we know the value of pressure at one spatial location, then pressure is fully determined.

Figures 4a and 4b show that the difference between pressure solutions under boundary condition (6.4) and (6.5) diminishes as the order of polynomials increases. Velocity solutions are hardly affected by these changes of pressure boundary conditions. The convergence behavior of the current nonstaggered scheme is better than that of the staggered ones (Ronquist, 1988) for the velocity terms, but worse for the pressure term. There is a somewhat larger error for pressure at the domain boundary, which is introduced by the splitting procedure [9]; this error can be reduced by either a larger Reynolds number, or a smaller time step.

The two-dimensional driven-cavity problem also was used as a test for the model of the Navier-Stokes equations. The Neumann pressure boundary condition is applied in this case. Figures 5a–5c and Figures 6a–6c show the results with $R_e = 1$ and $R_e = 100$, respectively.

The tests for accuracy for the parallel spectral element model of the shallow water equations (3.24) and (3.25) are the same as those in [6]. The same solutions are obtained by the present parallel model.

One advantage of the high-order domain decomposition numerical model is that it can take better advantage of the vector-processing units than can low-order models. Table V shows that the difference between the performance of the spectral element model with vectorization and that without vectorization increases as the order of the

basis functions, N , increases.

With the nonstaggered grid formulation, the maximum number of pressure iterations per time step for a given iteration error is significantly affected by K , the number of the spectral elements. However, the average number of pressure iterations per time step is much less sensitive to K (Figures 7a–7d) because the lengths of the gaps, where there are few the number of pressure iterations per time step, also increase with K .

7 Conclusions

In present work, we have shown that high-order domain decomposition methods can be efficiently applied in a data parallel programming environment. The optimized computational efficiency of the parallel spectral element model comes not only from the exponential convergence of its numerical solutions, but also from its efficient usage of the powerful vector-processing units of the latest parallel architectures which have a highly scalable performance. The nonstaggered grid formulation is convenient for, and shows no disadvantage in, these parallel spectral element models.

8 Acknowledgments

This work was supported by the DOE Global Change Distinguished Postdoctoral Fellowship administered by Oak Ridge Institute for Science and Education, by The U. S. Department of Energy under contract No. DE-AC02-76CH00016, and by The National Science Foundation through grant OCE-9312324. Most of the computation was performed on the CM-5 at ACL of Los Alamos National Laboratory.

Table V CM-5 Timing Results per Time Step for the 2-D N-S Model (32 nodes)

With an Iteration Error of $O(10^{-6})$

N	K	CPU (s)	
		With Vectorization	Without Vectorization
3	576	2.2	3.2
4	100	2.1	4.8
5	16	1.9	7.9
6	4	2.6	11.4

Figure 4 Plots of maximum pointwise errors ($\|u - u_n\|_{L_\infty}$ (□), $\|v - v_n\|_{L_\infty}$ (△), and $\|p - p_n\|_{L_\infty}$ (*)) as a function of the order of the basis functions, N , for the two-dimensional incompressible Navier-Stokes equations. The exact solutions are given in (6.1)-(6.3). $t=0.5$. Domain $[0, \pi] \times [0, \pi]$ is divided into 16 elements (4×4) of the same size. The error of temporal discretization is negligible compared to that of the spatial discretization. (a) With Dirichlet pressure boundary condition; (b) with Neumann pressure boundary condition.

Figure 4 (Continued)

(a)

Figure 5 Plots of the two-dimensional driven cavity problem with $R_e = 1$. The computational domain is $[0, 1] \times [0, 1]$. $K=16$, $N=7$. (a) Velocity; (b) vorticity; (c) pressure.

(b).

Figure 5 (Continued)

(c)

Figure 5 (Continued)

Figure 6 Same as Figure 5 but with $R_e = 100$. (a) Velocity; (b) vorticity; (c) pressure.

(b)

Figure 6 (Continued)

(c)

Figure 6 (Continued)

Figure 7 Plots of the number of pressure iterations per time step (solid) for the two-dimensional Navier-Stokes equation model (dashed line is the averaged number of pressure iterations per time step). Relative error (stopping criterion) = 10^{-5} ; $N = 6$.
 (a) $K = 16$; (b) $K = 64$; (c) $K = 256$; (d) $K = 1024$.

Figure 7 (Continued)

Figure 7 (Continued)

Figure 7 (Continued)

References

1. Babuska, I., H. C. Elman, and K. Markley *SIAM J. Sci. Stat. Comput.* **13**, 1433 (1992).
2. Behr, M., A. Johnson, J. Kennedy, S. Mittal, and T. Tezduyar Computation of Incompressible Flows With Implicit Finite Element Implementations on the Connection Machine. Preprint (1992).
3. Fischer, P. F. and A. T. Patera *J. Comput. Phys.* **92**, 380 (1991).
4. Kim, J. and P. Moin *J. Comput. Phys.* **59**, 308 (1985).
5. Korczak, K. Z. and A. T. Patera *J. Comput. Phys.* **62**, 361 (1986).
6. Ma, H. *J. Comput. Physics* **109**, 133 (1993).
7. Maday, Y. and A. T. Patera in *State-Of-The-Art Surveys on Computational Mechanics*, Ed. by A.D. Noor and J. T. Oden (ASME, New York, 1989), p. 71.
8. Orszag, S. A. *J. Comput. Phys.* **37**, 70 (1980).
9. Orszag, S. A., M. Israeli, and M. O. Deville *J. Sci. Computing* **1**, 75 (1986).
10. Patera, A. T. *J. Comput. Phys.* **54**, 468 (1984).
11. Ronquist, E. M. *Optimal Spectral Element Methods for the Unsteady Three Dimensional Navier-Stokes Equations*, Ph.D. Thesis, The Massachusetts Institute of Technology (1988).