For: 11th ANNUAL TOPICAL CONF. High-TEMP Plasma Diagnostics May 12-16, 96

FINAL Draft: 5/2/96 18³⁰

SAND 96-0350C
CONF-960543--4

Time-dependent electron temperature diagnostics for high-power, aluminum z-pinch plasmas*

T. W. L. Sanford, T. J. Nash, R. C. Mock, R. B. Spielman, J. F. Seamen,
J. S. McGurn, T. L. Gilliland, and M. Vargas
Sandia National Laboratories, Albuquerque, New Mexico 87185-1193

K. G. Whitney, J. W. Thornhill, P. E. Pulsifer, and J. P. Apruzese
Naval Research Laboratory, Washington, DC 20375-5000

ABSTRACT

Time-resolved x-ray pinhole photographs and time-integrated radially-resolved x-ray crystal spectrometer measurements of azimuthally-symmetric aluminum-wire implosions suggest that the final pinch is composed of a hot dense plasma core surrounded by a cooler plasma halo. The slope of the free-bound x-ray continuum measured using filtered photoconducting diodes, provides a time-resolved, model-independent diagnostic of the core electron temperature. A simultaneous measurement of the time-resolved K-shell line spectra provides a diagnostic to indirectly measure the electron temperature of the plasma halo. Together, measurements from the two diagnostics lend support to a picture that also emerges from a 1-D Rad-Hydro model; namely, that of a plasma whose thermalization on axis produces steep radial gradients in temperature, where the temperatures are substantially in excess of a kilovolt in the core and below a kilovolt in the surrounding plasma halo.

*This work is supported by U. S. Department of Energy Contract No. DE-AC04-94AL85000.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

I. INTRODUCTION

Knowledge of the time-dependent electron temperature in z pinches is required for the understanding of pinch dynamics and radiation generation. In this paper, two time-dependent diagnostics to measure the electron temperature are discussed and applied to ~ 30 -TW aluminum z-pinch plasmas generated on the 10-MA Saturn accelerator,¹ from imploding wire arrays containing large numbers of wires.² The use of large wire numbers reduces the azimuthal asymmetry of the initial plasma, improves shot-to-shot repeatability, and permits for the first time details of wire implosions to be meaningfully compared with 2D-numerical simulations over the full span of the x-ray emission.³

For the plasmas discussed here, our measurements indicate that the implosion is characterized by a hot plasma core that is surrounded by a cooler plasma halo. A similar model was proposed to explain temperature differences seen in recent Mg/Al mixture experiments.⁴ In this paper, we show firstly that the measurement of the free-bound (FB) x rays from the highly-stripped, K-shell aluminum ions provides a model-independent measurement of the core electron temperature owing to the long mean-free-path of that radiation and because the FB x rays are observed to originate predominantly from the core. Secondly, we show that the simultaneous measurement of the softer line spectra, which is sensitive to effects of opacity, provides a measurement of the electron temperature in the plasma halo. Before these two diagnostics are discussed, the overall experimental arrangement and global characteristics of the implosion are reviewed.

II. EXPERIMENTAL ARRANGEMENT

The experimental arrangement was identical to that of Ref. 2 and similar to that of Ref. 5, except for the number of wires in the array and diagnostics used. Here, the load consisted of an annular array of 90 or 136 aluminum wires mounted at a radius of 8.6 mm, having a length of 20 mm, and a total mass of ~ 615 mg. Eight current-return posts located at a radius of 17.3 mm permitted the radiation from the load to be measured in detectors located at the ends of three vacuum lines-of-sight positioned 55° off the pinch axis. With this load, a peak current of 6.9 ± 0.2

MA with a 35-ns 10-to-90% rise time was measured 45-mm upstream of the load. These detectors included a spatially-integrating time-resolved bolometer, filtered x-ray diodes (XRDs) and photoconducting detectors (PCDs), a time-resolved x-ray pinhole camera (PHC) (with 1-ns and 150- μ m temporal and spatial resolution, respectively) filtered by Be of 25- μ m thickness, a time-resolved KAP-crystal spectrometer (with 1-ns and 3-eV temporal and energy resolution, respectively), and a radially-resolved time-integrating KAP-crystal spectrometer (with better than 200- μ m and 3-eV spatial and energy resolution, respectively). The PHC was sensitive to x rays greater than ~ 1 keV, and the bolometer, XRDs, PCDs, and time-resolved spectrometer spatially integrated the radiation generated from over 70% of the implosion.

III. GLOBAL IMPLOSION CHARACTERISTICS

In general, the radial profiles measured near stagnation in the PHC are well fit by the sum of two Gaussian distributions as illustrated in Fig. 1A. This figure shows the profile measured within 1 ns of peak compression for one of the three 90-wire shots measured. It illustrates the presence of an intense Gaussian-like core having a 0.62-mm FWHM (full-width half-maximum) surrounded by a Gaussian-like halo with a 3.2-mm FWHM. The radiation from one of the shots together with the time evolution of the widths of the core and halo measured for the three shots are shown in Fig. 2A and 2B, respectively. The data show that the strong and weak radiation pulses correlate well with the strong and weak pinches of the core. Near-peak compression (Fig. 1), the energy radiated from the core and halo are about equal, as measured from the PHC. The radially-resolved spectrometer indicates that the FB radiation originates predominantly from the core; whereas, the spectrometer shows that the source of the K-line emission includes core plasma as well as plasma well into the halo region (Fig. 1B and 3), suggesting that the core is hotter than the halo. Additionally, because the measured x-ray yield generated during the second compression relative to that generated during the first compression decreases as the energy of the x ray increases (Fig. 2A), the data also imply that the core of the second compressions is cooler than that of the first.

The next two sections support these observations. They describe how the PCD and the spectrometer diagnostics are used to determine the electron temperature of the core and halo, respectively.

IV. CORE-TEMPERATURE DIAGNOSTIC

For a Maxwellian plasma of electron temperature T , the energy spectrum of the FB x rays is proportional to $\exp(-E/T)$, where E is the energy of the given x ray. Here, the slope of this FB spectrum and thus the associated electron temperature is measured with a set of filtered PCDs,⁶ as shown, for example, in Fig. 4 for a 136-wire shot. For this shot, the data give an electron temperature of 1.5 ± 0.2 keV at peak power (i.e., at 0 ns). In the detector, the given filter is mounted upstream of the PCD diamond element. The x-ray energy sensitivity of the filtered PCDs used is calculated using XRDNEW,⁷ an x-ray detector design code, and is shown in Fig. 5, with the mean energy and bandwidth response tabulated in Table I. Even though the PCDs lack the ability to resolve the radiation spatially, because the time-integrated crystal-spectrometer data show that the bulk of the FB radiation originates at radii less than 1 mm (Figs. 1C and 3), the temperature extracted is thus assumed to be that associated with the core.

Before and after the measurements discussed in this paper, the relative sensitivity of each PCD diamond element was established to a precision of $\pm 13\%$ by exposing each element to the same filtered x-ray fluence on dedicated aluminum-wire shots. The absolute response of a given element is tied back (via this relative technique) to detectors calibrated at the Brookhaven National Synchrotron Light Source to a precision of 20%. The time integrated spectrum (determined from the crystal spectrometer over the measured energy range 0.9 to 3.5 keV) and its extension to high x-ray energies when convoluted with the detector sensitivity (Fig. 5) is used to evaluate the energy response function of the given detector shown in Table I. Between 3.0 and 3.5 keV, the slope of the FB spectra for typical aluminum wire shots is measured to be ~ 1.3 keV, which is that used to estimate the filtered PCD response above 3 keV. Although each detector's response at a given time is dependent on the exact spectrum at that time, because the detector response varies simultaneously in a similar fashion for all the detectors used, the fitted slope (as shown in Fig. 4)

is relatively insensitive to the exact spectrum used to estimate the ensemble of responses. The resulting uncertainty in temperature, caused by not iterating the detector response, is estimated to be substantially less than the typical 12% uncertainty of the fit itself and, thus, response iteration is ignored.

Using this technique, the temperature extracted from one of the 90-wire shots as a function of time is shown in Fig. 2C. In Fig. 2C, the two peak temperatures correlate well with the times of the two pinches and radiation peaks, as might be expected. For the 90-wire shots, PCD (3.5 keV) and PCD (4.2 keV) were not available and accordingly were not used in extracting the temperatures shown. Additionally, in Fig. 2C beyond 24 ns, the signals from the highly filtered PCDs become too weak to be measured above background, and thus only PCD (2.5 keV), PCD (2.7 keV), and PCD (3.1 keV) were fit, resulting in a 23% systematic uncertainty in extracting the temperature beyond 24 ns. The temperature measured at peak compression for the three shots is 1.4 ± 0.1 keV in agreement with that measured for the 136-wire shot. The uncertainty refers to the RMS shot-to-shot variation and reflects on the excellent reproducibility of the implosions.

V. HALO-TEMPERATURE DIAGNOSTIC AND MODEL

The time-resolved pinhole pictures show a shell of plasma imploding to the axis (with an axial precursor), merging to form a cylinder of plasma. As shown in Figs. 1A and 2B, the core of this cylinder pinches to a diameter of less than 1 mm and rebounds to a diameter of 3 mm before undergoing a secondary pinch to a diameter of 2 mm. The pinhole pictures record the entire kilovolt spectrum of emitted x rays, so they give no direct measure of the size of the temperature and density gradients that may be present in the plasma; however, they do give a quantitative measure of the size of the K-shell emission region.

In the presence of temperature gradients that are suggested by the radially-resolved, but time-integrated spectrometer (Figs. 1B and 3), the inference of a single temperature from any one spectral feature is, at best, an average-value inference. One can get a sense of the presence and magnitude of the temperature gradients, however, by using different spectral measurements to infer temperature. One-D simulations⁸ of the 90-wire implosions that produced the best agreement with

the experimental data suggest that gradients in temperature are formed when a shell of plasma implodes on a precursor plasma, which sweeps up and compresses the precursor into a core that is then heated to much higher temperatures than the surrounding halo. The precursor is ionized in advance of the shell along with the resulting core to mostly fully stripped aluminum. Continuum emission is expected to originate from the hotter regions in this gradient. Optically-thick lines, on the other hand, that are emitted from hot regions will be absorbed and re-emitted from cooler regions. Thus, when time-resolved line spectra are used to infer spatially-averaged temperatures, a comparison of these temperatures with those inferred from continuum-slope measurements should provide information on the temperature gradients present in the plasma.

A procedure for inferring both temperatures and densities from line emission data like that of Fig. 3 is described in Ref. 9 and further evaluated in Ref. 10. A unique determination of both quantities is possible if one requires that the calculated power output from K-shell emissions as well as the calculated energy ratio of hydrogen-like Lyman-alpha to helium-like $n=2$ to $n=1$ emissions be simultaneously in agreement with the corresponding measured values of these quantities. The calculations are done with a minimum of assumptions about the spatial structure or temporal history of the plasma. Specifically, a uniform plasma is assumed, which is taken to be the size of the measured plasma, and the plasma is assumed to be in collisional-radiative equilibrium (CRE). The equilibrium calculation self-consistently includes the effects of photo-excitations, deexcitations, and ionizations.

The radial size used for this analysis corresponds to that measured for the core in Fig. 2B and the K-shell power used is that shown in Fig. 2A corresponding to PCD (2.5 keV). The Ly-alpha/(He-alpha+He-IC) line energy ratios obtained from the time-resolved spectra of the three 90-wire shots are shown in Fig. 2D together with the K-shell power pulse measured for one of the shots (similar to that of Fig. 2A). These data show that helium-like line emission dominates over hydrogen-like line emission up until peak compression, which coincides with the peak of the power pulse (i.e., 0 ns). After this time, as the plasma begins to expand, hydrogen-like emissions rise rapidly. The plasma either stays hot throughout the time interval of expansion and

recontraction (in contradiction with the electron temperature measured from the continuum slope (Fig. 2C)), or it expands and cools too quickly for the totally ionized and hydrogen-like ionization stages to recombine significantly. That is, the data shows that the hydrogen-like lines continue to dominate the helium-like lines even as the plasma expands, cools, recompresses, and heats. Because this line behavior implies recombination of the highly ionized states is slow, the continuum emission into hydrogenic aluminum must remain strong and concentrated in the highly ionized core of the plasma. However, its slope reflects the electron temperature. Thus, because Fig. 2C shows that the electrons are cooling due to heat conduction, radiation losses, and expansion, it also implies that the ions and electrons are not remaining in CRE as the plasma expands.

The average temperatures and densities inferred from the CRE analysis are shown in Figs. 2E and 2F. The analysis indicates that line emission is characterized by electron temperatures that remain low up until the peak of the power pulse, (~ 400 eV), while the ion density emitting the K-shell radiation rises with the power pulse to a peak value of $\sim 3.5 \times 10^{20} \text{ cm}^{-3}$. The low electron temperature inferred from the optically-thick line emission compared to the high temperature that is inferred from the optically-thin free-bound emission indicates that the hot plasma core, from which the free-bound emissions emanate, is surrounded by a cooler plasma halo. In this halo, line emission from hotter, inner regions can be absorbed and reemitted, in which case the line emission reflects the lower average temperature of the halo. After the peak of the power pulse when expansion occurs, the ion density drops back to the values it had just before plasma assembly on axis. During this period, the electron temperatures that are inferred from the CRE analysis are seen to rise rapidly to $\sim 1.2 \pm 0.2$ keV, a value that is comparable to the peak temperature measured from the continuum slope. The drop in ion density during expansion implies a corresponding drop in plasma opacity. The inferred rise in electron temperature is thus correlated to a drop in opacity, which, in turn, would imply that line emissions from the hot core would more readily escape the plasma and be seen. This behavior appears to confirm an ionization lag; that is, in the hot but now less dense core, the ionization state of the plasma does not stay in equilibrium with the electrons

due to long recombination times. Thus, the ionization state reflects the high electron temperatures that were present earlier at the time of peak compression. If plasmas the size of the radial halo widths are used in the above analysis, then the temperatures inferred up to peak power are ~ 450 eV, while the peak density is reduced to $\sim 10^{20}$. Similarly, the temperatures inferred after peak power rise by 100 to 200 eV too 1.3 to 1.4 keV.

VI. SUMMARY

Although the results of the line analysis are somewhat flawed by the CRE assumption, the interpretation that can be drawn from the combined line plus-continuum analysis suggests that a lag in recombination following peak compression does occur. In particular, it suggests that the electrons cool faster than the ionization stages can recombine to remain in equilibrium. Thus, the line analysis itself supports the idea that its equilibrium assumption has broken down. In spite of some uncertainties in the size of the plasma to be used in the analysis, it also supports the results of the continuum analysis. Namely, it produces a peak temperature that is comparable to that derived from the continuum-slope measurements. Furthermore, it implies the existence of subkilovolt temperatures in the plasma at a time when superkilovolt temperatures are present; that is, the combined analysis shows the existence of kilovolt temperature differences over submillimeter distances that suggests the presence of perhaps magnetically-inhibited heat flow. In conclusion, this analysis shows the utility of the two diagnostics to infer electron temperatures from high-power z-pinch implosions.

ACKNOWLEDGMENTS

We thank J. E. Maenchen, M. K. Matzen, D. H. McDaniel, and J. Davis (NRL) for vigorous programmatic support; G. A. Allshouse for reviewing and L. O. Peterson for typing the paper.

References

- ¹D. D. Bloomquist, R. M. Stinnett, D. H. McDaniel, J. R. Lee, A. W. Sharpe, J. A. Halbleib, L. G. Shlitt, P. W. Spence, and P. Corcoran, in *Proceedings 6th IEEE Pulsed Power Conference* Arlington, VA, edited by P. J. Truchi and B. H. Bernstein (IEEE, New York, 1987), p. 310.
- ²T. W. L. Sanford, T. J. Nash, B. M. Marder, R. Humphreys, C. Deeney, R. B. Spielman, J. F. Seamen, R. C. Mock, J. S. McGurn, D. Jobe, T. L. Gilliland, M. Vargas, K. Struve, W. A. Stygar, J. H. Hammer, J. L. Eddleman, J. S. De Groot, D. Mosher, K. G. Whitney, J. P. Apruzese, P. Pulsifer, Y. Maron, *Bull. Am Phys. Soc.* **40**, 1846 (1995).
- ³J. H. Hammer, *Bull. Am. Phys. Soc.* **40**, 1863 (1995) and to be published *Phys. Plasmas* (1996).
- ⁴C. Deeney, P. D. LePell, B. H. Failor, S. L. Wong, J. P. Apruzese, K. G. Whitney, J. W. Thornhill, J. Davis, E. Yadlowsky, R. C. Hazelton, J. J. Moschella, T. Nash, and N. Loter, *Phys. Rev. E* **51**(5), 4823 (1995).
- ⁵R. B. Spielman, J. S. De Groot, T. J. Nash, J. McGurn, L. Ruggles, M. Vargas, and K. G. Estabrook, *Dense z-Pinches* (3rd International Conference, London, UK, 1993), AIP Conference Proceedings 299, editors H. Haines and A. Knight, American Institute of Physics, New York 1994, L.C. Catalog Card No. 93-74569, pages 404-420.
- ⁶R. B. Spielman, *Rev. Sci. Instrum.* **66**, 867 (1995).
- ⁷R. B. Spielman, Sandia National Laboratories Technical Report SAND85-0699 (1990).
- ⁸1D simulation reference

⁹M. C. Coulter, K. G. Whitney, and J. W. Thornhill, *J. Quant. Spectrosc. Radiat. Transfer* **44**, 443 (1990).

¹⁰J. P. Apruzese, K. G. Whitney, J. Davis, and P. C. Kepple, *J. Quant. Spectrosc. Radiat. Transfer* (to be submitted).

Figure Captions

- 1A. Radial profile measured in the PHC near peak compression showing the plasma core and halo spatial distribution.
- 1B. Relative comparison of the radial profile of the free-bound continuum between 4 and 5.4 Å with the radial profile of the hydrogen alpha line, as measured in the radially-resolved crystal spectrometer (see also Fig. 3).
- 2A. Relative comparison of the radiation measured in XRD(0.25 keV), PCD(2.5 keV), and PCD(6.2 keV) for one of the 90-wire shots, showing that the second pulse has a lower temperature than the first. See Table I for detector definitions.
- 2B. Comparison of the FWHM of the core and halo for the three 90-wire shots measured in the PCD, showing a strong and weak compression of the core, which merges with the halo after the first and second compression.
- 2C. The electron temperature of the core extracted from the filtered PCD measurements for the 90-wire shot shown in Fig. 2A. The small percentage error-bar corresponds to the typical $\pm 12\%$ error of the fit. The large percentage error-bar corresponds to the systematic 23% uncertainty in extracting the temperature associated with the limited number of PCDs used.
- 2D. Measured line ratios of the hydrogen-like Lyman-alpha to helium-like $n=2$ to $n=1$ resonance lines are shown for each of the three 90-wire shots as a function of time, together with the radiation measured from PCD(2.5 keV) for one of the 90-wire shots.

- 2E. The electron temperatures that are inferred from the data in Figs. 2A corresponding to PCD(2.5 keV), Fig. 2B corresponding to core FWHM, and Fig. 2D are shown for each of the three 90-wire shots.
- 2F. The ion densities that are inferred from the data in Figs. 2A corresponding to PCD(2.5 keV), Fig. 2B corresponding to the core FWHM, and Fig. 2D are shown for each of the three 90-wire shots.
- 3. Comparison of the spectra on axis and 3-mm off axis measured in the radially-resolved crystal spectrometer.
- 4. The slope of the free- bound continuum as measured in the filtered PCD for the 136-wire shot 2239. The horizontal error bars correspond to the $\pm 25\%$ energy response band about the given average-energy response and the vertical error bars correspond to the $\pm 13\%$ relative PCD calibration uncertainty.
- 5. Relative response of the XRD and PCDs shown in Fig. 2A and used in extracting the core electron temperature (see also Table I).

Table I

Mean energy response $\bar{E}$ and associated band width $\pm\Delta E$ over which $\pm 25\%$ of the x rays are observed about $\bar{E}$ in the filtered (XRD) shown in Fig. 2A and the filtered PCDs used to extract the electron temperature of Fig. 4.

Name	Filter	$\bar{E}$ (keV)	$+\Delta E$ (keV)	$-\Delta E$ (keV)
XRD (0.25 keV)	1- μm Kimfol	~ 0.25	~ 0.35	~ 0.12
PCD (2.5 keV)	8- μm Be	2.5	0.75	0.64
PCD (2.7 keV)	8.5- μm Kapton	2.7	0.80	0.56
PCD (3.1 keV)	25- μm Kapton	3.1	0.74	0.56
PCD (3.5 keV)	50- μm Kapton	3.5	0.91	0.65
PCD (4.2 keV)	127- μm Kapton	4.2	0.90	0.70
PCD (4.8 keV)	254- μm Kapton	4.8	0.90	0.70
PCD (6.2 keV)	25- μm Ge	6.2	1.00	0.80

Fig 1A

Fig. 1A

Fig 2A

Fig 2B

Fig. 2B

Fig 2c

Fig. 2C

Fig 2D

Fig. 2D

Fig. 2E

Fig 21=

Fig. 2F

Fig. 3

Fig. 3

Fig. 4

Fig 5