ORNL/M-4602

RECEIVED

FEB 21 1996

OSTI

**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

**Neutronic Methods, Models,
and Applications at the
Idaho National Engineering Laboratory
for the Advanced Neutron Source
Reactor Three-Element Core Design**

C. A. Wemple
B. G. Schnitzler
J. M. Ryskamp

August 1995

Advanced Neutron Source

MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**NEUTRONICS METHODS, MODELS, AND APPLICATIONS AT THE
IDAHO NATIONAL ENGINEERING LABORATORY FOR THE
ADVANCED NEUTRON SOURCE REACTOR
THREE-ELEMENT CORE DESIGN**

C. A. Wemple
B. G. Schnitzler
J. M. Ryskamp

Idaho National Engineering Laboratory
Lockheed Martin Idaho Technologies, P.O. Box 1625
Idaho Falls, Idaho 83415-3885

August 1995

Prepared by
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37931-8218
managed by
LOCKHEED MARTIN ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under contract DE-AC05-84OR21400

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

LIST OF FIGURES	v
LIST OF TABLES	vii
ACRONYMS	ix
ACKNOWLEDGMENTS	xi
ABSTRACT	.xiii
1. INTRODUCTION	1
2. CODES AND METHODS	3
2.1 MCNP COMPUTER CODE DESCRIPTION	3
2.2 DKPOWR COMPUTER CODE DESCRIPTION	3
2.3 MOCUP COMPUTER CODE DESCRIPTION	4
3. MCNP CROSS SECTION DEVELOPMENT AND VALIDATION	7
3.1 EXTERNALLY DEVELOPED CROSS SECTION SETS	7
3.2 INTERNALLY DEVELOPED CROSS SECTION SETS	9
4. MCNP MODEL DESCRIPTION	11
4.1 CORE AND CENTRAL HOLE	11
4.1.1 Core	11
4.1.2 Core Support Structures	15
4.1.3 Core Pressure Boundary Tube	15
4.1.4 Control Rods	15
4.1.5 In-Core Targets	19
4.1.5.1 Upper Irradiation Targets	19
4.1.5.2 Transplutonium Production Targets	19
4.1.6 Piping and Other Components	19
4.2 REFLECTOR COMPONENTS	23
4.2.1 Safety Rods	23
4.2.2 Beam Tubes	23
4.2.2.1 Thermal Beam Tubes	23
4.2.2.2 Through-Tube	23
4.2.2.3 Large Slant Beam Tube	23

4.2.3	Irradiation Facilities	29
4.2.3.1	Hydraulic Tubes	29
4.2.3.2	Slant Holes	29
4.2.3.3	Pneumatic Tubes	35
4.2.3.4	Pneumatic Facilities	35
4.2.4	Isotope Production Facilities	35
4.2.5	Cold Sources	35
4.2.6	Slant Cold Guide Tubes	44
4.2.7	Positron Hydraulic Tube	44
4.2.8	Hot Source	44
4.3	REFLECTOR VESSEL AND BIOLOGICAL SHIELD	44
5.	CALCULATIONS AND RESULTS	51
5.1	COMPONENT REACTIVITY WORTHS	51
5.2	CENTRAL CONTROL ROD BANK WORTH	51
5.3	SAFETY SHUTDOWN ROD BANK WORTH	51
5.4	REACTIVITY COEFFICIENTS	60
5.4.1	Void Reactivity Worth	60
5.4.2	Coolant Level Drop Reactivity Worth	71
5.4.3	Light Water Ingress Reactivity Worth	71
5.5	BEAM TUBE STUDIES	71
5.6	HEAT LOAD DISTRIBUTIONS	81
5.6.1	Thermal Power in the Primary System	81
5.6.2	Heat Load Distributions in the Entire Reactor	81
5.6.2.1	Base Calculation	84
5.6.2.2	Fission Product Decay	85
5.6.2.3	Aluminum-28 Beta Decay	86
5.6.2.4	Additional Heat Load Contributions	87
5.7	FUEL CYCLE DEPLETION	87
6.	UNRESOLVED ISSUES	91
6.1	LIGHT WATER INGRESS IN PRIMARY SYSTEM	91
6.2	VOID WORTH IN BYPASS FLOW REGION	91
6.3	CALIFORNIUM AND EINSTEINIUM PRODUCTION	91
6.4	REACTIVITY WORTHS THROUGH THE CYCLE	91
6.5	FLUXES IN REACTOR THROUGH THE CYCLE	92
7.	REFERENCES	93

LIST OF FIGURES

Figure	Page
4.1 Three-dimensional view of the ANS MCNP three-element core reactor model	12
4.2 Axial view of the reactor model geometry	13
4.3 Axial view of the geometry inside the core pressure boundary tube (not to scale)	14
4.4 Radial view of the upper core support structures	16
4.5 Radial view of the lower core support structures and the central control rod guide assembly	17
4.6 Radial view of the in-core target locations and the central control rods	18
4.7 Axial view of an instrumented in-core irradiation target	20
4.8 Axial view of an uninstrumented in-core irradiation target	21
4.9 Axial view of a transplutonium production target	22
4.10 Radial view of the reactor model at the core midplane ($z=0$)	24
4.11 Radial view of the safety shutdown rod locations	25
4.12 Axial view of a safety shutdown rod	26
4.13 Axial view of a thermal beam tube	27
4.14 Axial view of the through-tube	28
4.15 Axial view of the large slant beam tube	30
4.16 Axial view of hydraulic tube HT-1	31
4.17 Axial view of hydraulic tube HT-2	32
4.18 Axial view of the target assembly in hydraulic tube HT-2	33
4.19 Axial view of slant tube SH-1	34
4.20 Axial view of pneumatic tube PT-1	36
4.21 Axial view of pneumatic tube PT-2	37
4.22 Axial view of pneumatic tube PT-3	38
4.23 Axial view of pneumatic facility PF-1	39
4.24 Radial view of the pneumatic facilities	40
4.25 Axial view of vertical isotope production facility VH-1	41
4.26 Radial view of cold source CS-1	42
4.27 Axial view of the very cold guide tube and the liquid D_2 lines in cold source CS-1	43
4.28 Axial view of slant cold guide SCG-1	45
4.29 Axial view of the positron hydraulic tube	46
4.30 Axial view of the target assembly in the positron hydraulic tube	47
4.31 Radial view of the hot source	48
4.32 Radial view of the hot source graphite moderator	49

LIST OF FIGURES (continued)

Figure	Page
5.1 Three-element core central control rod bank worth at beginning of cycle	55
5.2 Three-element core central control rod differential worth at beginning of cycle . . .	56
5.3 Three-element core safety shutdown rod bank worth at beginning of cycle	58
5.4 Three-element core safety shutdown rod differential worth a beginning of cycle . . .	59
5.5 Three-element core reflector void reactivity worth at beginning of cycle	62
5.6 Three-element core reflector void differential worth at beginning of cycle	63
5.7 Void reactivity worth in the lower fuel element at beginning of cycle	69
5.8 Void reactivity worth in all three fuel elements at beginning of cycle	70
5.9 Reactivity worth of a drop in the primary coolant level at beginning of cycle	76
5.10 Differential worth of a drop in the primary coolant level at beginning of cycle	77
5.11 Reactivity worth of a dilute light water ingress into the reflector at beginning of cycle	79
5.12 Differential worth of a dilute light water ingress into the reflector at beginning of cycle	80

LIST OF TABLES

Table	Page
2.1 Top 50 absorbers from ANS ORIGEN2 calculations as determined by end of cycle absorption rates	5
3.1 MCNP cross section data sets used in the INEL MCNP model of the ANS reactor	7
3.2 INEL-developed MCNP cross section data sets	10
5.1 Component reactivity worths for the three-element baseline MCNP model at beginning of cycle	52
5.2 Core reactivity balance and component reactivity worths at beginning of cycle for the three-element baseline MCNP model	53
5.3 Central control rod reactivity worth at beginning of cycle for the baseline three-element MCNP model	54
5.4 Safety rod reactivity worth at beginning of cycle for the three-element baseline MCNP model	57
5.5 Uniformly distributed void worth in the reflector at beginning of cycle for the three-element baseline MCNP model	61
5.6 Uniformly distributed void worth in the central hole at beginning of cycle for the three-element baseline MCNP model	64
5.7 Uniformly distributed void worth in the inner upper fuel element at beginning of cycle for the three-element baseline MCNP model (coolant channels above this element were also voided)	65
5.8 Uniformly distributed void worth in the lower fuel element at beginning of cycle for the three-element baseline MCNP model (coolant channels above this element were also voided)	66
5.9 Uniformly distributed void worth in the outer upper fuel element at beginning of cycle for the three-element baseline MCNP model (coolant channels above this element were also voided)	67
5.10 Uniformly distributed void worth in all three fuel elements at beginning of cycle for the three-element baseline MCNP model (coolant channels above the elements were also voided)	68
5.11 Reactivity worth of void region in the bypass channel and in the reflector along the upper fuel elements at beginning of cycle for the three-element baseline MCNP model	72

LIST OF TABLES (continued)

Table	Page
5.12 Reactivity worth of void region in the bypass channel and in the reflector along both upper and lower fuel elements at beginning of cycle for the three-element baseline MCNP model	73
5.13 Reactivity worth of drop in the primary system coolant level at beginning of cycle for the three-element baseline MCNP model	74
5.14 Reactivity worth of drop in the reflector heavy water level at beginning of cycle for the three-element baseline MCNP model	75
5.15 Reactivity worth of dilute light water ingress into the reflector at beginning of cycle for the three-element baseline MCNP model	78
5.16 Results of calculations for various beam tube configurations normalized to 330 MWF. Cases ANS1053-ANS1056 use the 100 × 100 mm beam tube regions for tallies	82
5.17 Relative and absolute power deposited in the primary system coolant and structures at beginning of cycle	83
5.18 Results of ANS MOCUP depletion calculations for the G1294 fuel grading	89
5.19 Results of ANS MOCUP depletion calculations for the G395 fuel grading	89

ACRONYMS

ANS	Advanced Neutron Source
BOC	beginning of cycle
CCR	central control rod
CPBT	core pressure boundary tube
CSAR	conceptual safety analysis report
EOC	end of cycle
HT	hydraulic tube
HTP	positron hydraulic tube
INEL	Idaho National Engineering Laboratory
IUFE	inner upper fuel element
LANL	Los Alamos National Laboratory
LFE	lower fuel element
LSBT	large slant beam tube
MOC	middle of cycle
MOCUP	MCNP-ORIGEN2 Coupling Utility Program
ORNL	Oak Ridge National Laboratory
OUFE	outer upper fuel element
PF	pneumatic facility
PT	pneumatic tube
SCCP	software configuration control package
SCG	slant cold guide
SH	slant hole
SSR	safety shutdown rod
UFE	upper fuel element
VCG	very cold guide
VH	vertical hole

ACKNOWLEDGMENTS

We would like to thank C. D. West, the Advanced Neutron Source (ANS) project director, and D. L. Selby, ANS research and development manager, both of Oak Ridge National Laboratory, for providing the necessary funding over the years to support this and prior work. It has been a pleasure working with them.

We would also like to thank the various other ANS project personnel with whom we have interacted frequently over the years. Specifically, thanks are owed to Brian Worley, Jess Gehin, John-Paul Renier, Alan Smith, Dick Lillie, and Tom McManamy for their input to these analyses. We sincerely appreciate the help these scientists provided.

ABSTRACT

A summary of the methods and models used to perform neutronics analyses on the Advanced Neutron Source reactor three-element core design is presented. The applications of the neutral particle Monte Carlo code MCNP are detailed, as well as the expansion of the static role of MCNP to analysis of fuel cycle depletion calculations. Results to date of these applications are presented also. A summary of the calculations not yet performed is also given to provide a "to-do" list if the project is resurrected.

1. INTRODUCTION

The Advanced Neutron Source (ANS) is a world-class research reactor and experimental center for neutron research presently being designed at Oak Ridge National Laboratory (ORNL). The reactor consists of a 330 MWf highly enriched uranium core, which is cooled, moderated, and reflected with heavy water. The reactor was designed to be the preeminent ultrahigh neutron flux reactor in the world, with facilities for research programs in biology, materials science, chemistry, fundamental and nuclear physics, and analytical chemistry. Irradiation facilities are provided for a variety of isotope production capabilities, as well as materials irradiation.

At the time of this report, the conceptual design phase is completed, and the advanced conceptual design phase is nearly completed. This report is part of an effort to document fully the analysis methods and results for the three-element core version of the advanced conceptual design; it details the methods and models used at the Idaho National Engineering Laboratory (INEL) for analysis of the three-element core design and presents the results of analyses completed at the time of the project closeout.

2. CODES AND METHODS

2.1 MCNP COMPUTER CODE DESCRIPTION

Transport calculations were performed using the MCNP three-dimensional, continuous-energy, coupled neutron-photon Monte Carlo code, version 4a.¹ MCNP has been developed at Los Alamos National Laboratory (LANL) over the past four decades and is one of the most sophisticated Monte Carlo transport codes in general use today. Geometric descriptions are defined by combinatorial geometries, using any combination of one-, two- and special four-dimensional surfaces. The code can perform neutral particle transport in either continuous or discrete energy modes, with a variety of physics options available to the user. Tallies of desired output parameters (flux, current, etc.) can be freely defined by the user over any spatial, energy, angular, or time domain. Various methods of statistical variance reduction are available. Computations may be performed in either the eigenvalue or fixed source mode. More detail is available in the MCNP code users manual.¹

The MCNP code has been used in the ANS design project to predict criticality, compute reactivity coefficients and effects, calculate component heat loads, and generate limited sets of group-wise cross sections for use in other discrete transport and diffusion codes. All computations were run using continuous-energy cross sections, which provides a clear superiority over discrete transport and diffusion codes. Consequently, MCNP has been used as a benchmark for other calculations and methods. Computations were run until a sufficient degree of certainty was obtained in the results. For eigenvalue calculations, the statistical uncertainty was less than 0.4%, and for other quantities the uncertainty was generally less than 5% and usually less than 1%. However, when appropriate for specific applications, greater or lesser uncertainty was obtained in the results.

Cross sections for MCNP were obtained from the controlled source distributed with the MCNP4a code by the Radiation Shielding Information Center at ORNL. These cross sections were processed by various methods from several sources. A detailed listing of the cross section sets and their origins is given in Appendix G of the MCNP users manual.¹ In accordance with project quality assurance specifications, a software configuration control package (SCCP) was prepared for MCNP4a at INEL.² This maintains strict control over the code version and cross section data used for ANS project analyses.

2.2 DKPOWR COMPUTER CODE DESCRIPTION

The DKPOWR² code computes decay powers, energies, activities, and beta and photon spectra for fission products resulting from fission in light water reactor fuel. The fission product photon spectra data in DKPOWR were gathered from experimental data compiled for the decay heat power standard ANSI/ANS-5.1-1979.³ Further details of this code are available in ref. 2. It has been assumed that the fission product yields will not be significantly different for heavy water fuels. Comparison of yields, activities, and total decay powers with results from the ORIGEN2.1 code,⁴ which performs a similar calculation based

on ENDF/B version 4 data, provides confirmation of this. Details of the ORIGEN2.1 code are available in ref. 4.

The MCNP and DKPOWR codes were externally coupled to provide component heat load computations. An initial eigenvalue computation was made with MCNP to calculate the fission, neutron, and prompt photon heat loads and the fission and aluminum absorption rates in each component of the reactor. The fission rates yielded a source of photons from the decay of fission products and their daughters and the local heat load from fission product decay beta particles. This source was evaluated using DKPOWR, which provided the energy split between the photon and beta decays associated with the fission products and daughters.

2.3 MOCUP COMPUTER CODE DESCRIPTION

The MOCUP code system⁵ provides automated data communication between the MCNP and ORIGEN2.1 codes to allow depletion analyses to be performed with Monte Carlo transport-calculated, exposure-dependent fluxes and reaction rates. Neutronics calculations are performed using MCNP at selected points through the irradiation cycle. Results obtained from MCNP include fluxes and neutron reaction rates for radiative capture, fission, (n,2n), and (n,3n) processes for user-selected nuclides in user-selected regions of the reactor model. Nuclide compositions in the same regions are calculated using the ORIGEN2.1 isotopic generation and depletion code. Initial compositions, neutron fluxes, and one-group spectrum-averaged cross sections for the previous reaction processes in the cells of interest are passed from MCNP to the ORIGEN2.1 calculations. Following the ORIGEN2.1 calculations for each region, new isotopic concentrations are passed back to MCNP for the next neutronics calculation.

The validity of results obtained using this methodology depends on a number of important modeling decisions. Significant MCNP-related issues include the frequency at which the MCNP transport calculations are performed during the fuel cycle, the number of discrete fuel and boron regions considered, and the allowable statistical uncertainties in the MCNP-calculated fluxes and reaction rates from which cross sections are determined. The most significant ORIGEN2.1-related issue is the number of time steps employed in each irradiation interval connecting subsequent MCNP calculations. Although the ORIGEN2.1 calculation includes a relatively complete set of 858 fission products, absorption is explicitly treated in the MCNP calculation for a much smaller number of nuclides.

A list of the top 50 fission product absorbers was examined based on ORIGEN2.1 calculations for a 17-d ANS cycle at 330 MW; this list is shown in Table 2.1. These 50 fission products account for 99% of the fission product absorptions at each time step through the ANS cycle, which was deemed sufficient for the transport calculations. An ORIGEN2.1 fission product cross section library developed for the Advanced Test Reactor at INEL was used to establish this initial set. Although some sensitivity to reactor spectrum is anticipated, this approach provides a reasonable basis. These 50 fission products were tracked explicitly in the MCNP transport calculations at each time step.

**Table 2.1. Top 50 absorbers from ANS ORIGEN2.1 calculations
as determined by end of cycle absorption rates**

Nuclide	MCNP Identifier	Nuclide	MCNP Identifier
⁸⁶ Kr	36083.50c	¹⁵¹ Pm	61151.60c
⁹³ Zr	40092.50c	¹⁴⁹ Sm	62149.50c
⁹⁵ Zr	40095.60c	¹⁵⁰ Sm	62150.50c
⁹⁶ Zr	40096.60c	¹⁵¹ Sm	62151.50c
⁹⁷ Mo	42097.60c	¹⁵² Sm	62152.50c
⁹⁸ Mo	42098.50c	¹⁵³ Sm	62153.50c
⁹⁹ Mo	42099.50c	¹⁵³ Eu	63153.50c
¹⁰⁰ Mo	42100.50c	¹⁵⁴ Eu	63154.50c
⁹⁹ Tc	43099.50c	¹⁵⁵ Eu	63155.50c
¹⁰¹ Ru	44101.50c	¹⁵⁶ Eu	63156.60c
¹⁰² Ru	44102.60c	¹⁵⁷ Gd	64157.50c
¹⁰³ Ru	44103.50c	¹⁴³ Ce	58143.60c
¹⁰³ Rh	45103.50c	¹⁴¹ Pr	59141.50c
¹⁰⁵ Rh	45105.50c	¹⁴³ Pr	59143.60c
¹⁰⁵ Rd	45105.50c	¹⁴³ Nd	60143.50c
¹⁰⁹ Ag	47109.50c	¹⁴⁵ Nd	60145.50c
¹¹³ Cd	48113.60c	¹⁴⁷ Nd	50147.50c
¹¹⁵ In	49115.60c	¹⁴⁸ Nd	60148.50c
¹²⁹ I	53129.60c	¹⁴⁷ Pm	61147.50c
¹³¹ Xe	54131.50c	^{148m} Pm	61148.50c
¹³³ Xe	54133.60c	¹⁴⁸ Pm	61148.60c
¹³⁵ Xe	54125.50c	¹⁴⁹ Pm	61194.50c
¹³³ Cs	55133.50c		
¹³⁴ Cs	55134.60c		
¹⁴⁰ Ba	56140.60c		
¹³⁹ La	57139.60c		
¹⁴⁰ La	57140.60c		
¹⁴¹ Ce	58141.60c		

3. MCNP CROSS SECTION DEVELOPMENT AND VALIDATION

3.1 EXTERNALLY DEVELOPED CROSS SECTION SETS

The MCNP continuous-energy cross sections used for the ANS design project were processed from evaluated data files, generally using the NJOY⁶ nuclear data processing code. Most of the isotopes used for these analyses were developed from ENDF/B-V,⁷ which contains the most thoroughly tested MCNP-format cross sections. A few were processed from ENDL-85 data,⁸ which were evaluated at Lawrence Livermore National Laboratory. A list of the nuclides used for the MCNP analyses of the ANS three-element core design with their sources is given in Table 3.1; this includes the externally developed fission product sets.

Table 3.1. MCNP cross section data sets used in the INEL MCNP model of the ANS reactor

Isotope	Cross section		
	Identifier	Library	Data source
¹ H	1001.50c	rmccs2	ENDF/B-V
² H	1002.55c	rmccs2	ENDF/B-V
¹⁰ B	5010.50c	rmccs2	ENDF/B-V
¹¹ B	5011.56c	rmccs2	ENDF/B-V
C	6012.50c	rmccs2	ENDF/B-V
O	8016.50c	rmccs2	ENDF/B-V
Mg	12000.50c	endf5u2	ENDF/B-V
²⁷ Al	13027.50c	rmccs2	ENDF/B-V
Si	14000.50c	endf5p2	ENDF/B-V
Ti	22000.50c	endf5u2	ENDF/B-V
Cr	24000.50c	rmccs2	ENDF/B-V
⁵⁵ Mn	25055.50c	endf5u2	ENDF/B-V
Fe	26000.50c	rmccs2	ENDF/B-V
Ni	28000.50c	rmccs2	ENDF/B-V
Cu	29000.50c	rmccs2	ENDF/B-V
⁸³ Kr	36083.50c	rmccsa2	ENDF/B-V
Zr	40000.35c	endl852	ENDL-85
⁹³ Zr	40093.50c	kidman2	ENDF/B-V
Mo	42000.50c	endf5u2	ENDF/B-V
⁹⁹ Tc	43099.50c	kidman2	ENDF/B-V
¹⁰¹ Ru	44101.50c	kidman2	ENDF/B-V

Table 3.1 (continued)

Isotope	Cross section		
	Identifier	Library	Data source
¹⁰³ Ru	44103.50c	kidman2	ENDF/B-V
¹⁰³ Rh	45103.50c	rmccsa2	ENDF/B-V
¹⁰⁵ Rh	45105.50c	kidman2	ENDF/B-V
¹⁰⁵ Pd	46105.50c	kidman2	ENDF/B-V
¹⁰⁹ Ag	47109.50c	rmccsa2	ENDF/B-V
Sn	50000.35c	endl852	ENDL-85
¹³¹ Xe	54131.50c	kidman2	ENDF/B-V
¹³⁵ Xe	54135.50c	eprixs2	ENDF/B-V
¹³³ Cs	55133.50c	kidman2	ENDF/B-V
¹⁴¹ Pr	59141.50c	kidman2	ENDF/B-V
¹⁴³ Nd	60143.50c	kidman2	ENDF/B-V
¹⁴⁵ Nd	60145.50c	kidman2	ENDF/B-V
¹⁴⁷ Nd	60147.50c	kidman2	ENDF/B-V
¹⁴⁸ Nd	60148.50c	kidman2	ENDF/B-V
¹⁴⁷ Pm	61147.50c	kidman2	ENDF/B-V
¹⁴⁸ Pm	61148.50c	kidman2	ENDF/B-V
¹⁴⁹ Pm	61149.50c	kidman2	ENDF/B-V
¹⁴⁹ Sm	62149.50c	endf5u2	ENDF/B-V
¹⁵⁰ Sm	62150.50c	kidman2	ENDF/B-V
¹⁵¹ Sm	62151.50c	kidman2	ENDF/B-V
¹⁵² Sm	62152.50c	kidman2	ENDF/B-V
¹⁵³ Eu	63153.50c	rmccs2	ENDF/B-V
¹⁵⁴ Eu	63154.50c	endf5u2	ENDF/B-V
¹⁵⁵ Eu	63155.50c	kidman2	ENDF/B-V
¹⁵⁷ Gd	64157.50c	endf5u2	ENDF/B-V
Hf	72000.35c	endl852	ENDL-85
W	74000.35c	endl852	ENDL-85
Pb	82000.50c	endf5u2	ENDF/B-V
²³⁴ U	92234.35c	endl852	ENDL-85
²³⁵ U	92235.50c	rmccs2	ENDF/B-V
²³⁶ U	92236.50c	rmccs2	ENDF/B-V
²³⁸ U	92238.50c	rmccs2	ENDF/B-V

Table 3.1 (continued)

Isotope	Cross section		
	Identifier	Library	Data source
²³⁸ Pu	94238.50c	endf5p2	ENDF/B-V
²³⁹ Pu	94239.55c	rmccs2	ENDF/B-V
²⁴⁰ Pu	94240.50c	rmccs2	ENDF/B-V
²⁴¹ Pu	94241.50c	endf5p2	ENDF/B-V
²⁴² Pu	94242.50c	endf5p2	ENDF/B-V
²⁴¹ Am	95241.50c	endf5u2	ENDF/B-V
²⁴³ Am	95243.50c	endf5u2	ENDF/B-V
²⁴³ Cm	96243.35c	endl852	ENDL-85
²⁴⁴ Cm	96244.50c	endf5u2	ENDF/B-V
²⁴⁵ Cm	96245.35c	endl852	ENDL-85
²⁴⁶ Cm	96246.35c	endl852	ENDL-85
²⁴⁷ Cm	96247.35c	endl852	ENDL-85
²⁴⁸ Cm	96248.35c	endl852	ENDL-85

The cross section sets supplied with MCNP, as well as those acquired later from the National Energy Research Software Center and the LANL common file server, were included in the SCCP (see Sect. 2.1) and are subject to configuration control along with the controlled version of MCNP. Validation of the MCNP cross sections was performed as part of the Software Quality Assurance Plan for MCNP4a at INEL. A set of standard MCNP benchmark calculations, many of which are models of existing experimental facilities, was run using a subset of the previously mentioned cross sections. These results were compared with the results of MCNP cases run on the Cray Y-MP at LANL, which had been optimized to best reproduce the initial experimental results. The general results showed almost no deviation from the LANL Cray results.

3.2 INTERNALLY DEVELOPED CROSS SECTION SETS

To supplement the limited number of fission product cross section data sets provided with MCNP, and the 25 sets available in the Kidman fission product library data set, 22 additional fission product data sets were produced at INEL for use in the MCNP-ORIGEN2 Coupling Utility Program (MOCUP) depletion analyses. These cross sections were processed using the NJOY code, with all but three isotopes using evaluated data from ENDF/B-VI.⁹ Two of these three were from ENDF/B-V, and the third was the zinc evaluation from the Chinese library, CENDL-2.¹⁰

Processing of these cross section sets involved first linearizing the evaluated data, then Doppler-broadening the resolved resonances to 300K. Where included in the evaluation, the unresolved resonance data was then processed and Doppler-broadened, and the heating, damage, and photon production data were included. The data were then converted to the Los Alamos ACE format for use in MCNP. A complete list of the locally developed data sets is given in Table 3.2.

Table 3.2. INEL-developed MCNP cross section data sets

Nuclide	MCNP identifier	Data source
Zn	30000.99c	CENDL-2
⁹⁵ Zr	40095.60c	ENDF/B-VI
⁹⁶ Zr	40096.60c	ENDF/B-VI
⁹⁷ Mo	42097.60c	ENDF/B-VI
⁹⁸ Mo	42098.50c	ENDF/B-V
⁹⁹ Mo	42099.60c	ENDF/B-VI
¹⁰⁰ Mo	42100.50c	ENDF/B-V
¹⁰² Ru	44102.60c	ENDF/B-VI
¹¹³ Cd	48113.60c	ENDF/B-VI
¹¹⁵ In	49115.60c	ENDF/B-VI
¹²⁹ I	53129.60c	ENDF/B-VI
¹³³ Xe	54133.60c	ENDF/B-VI
¹³⁴ Cs	55134.60c	ENDF/B-VI
¹⁴⁰ Ba	56140.60c	ENDF/B-VI
¹³⁹ La	57139.60c	ENDF/B-VI
¹⁴⁰ La	57140.60c	ENDF/B-VI
¹⁴¹ Ce	58141.60c	ENDF/B-VI
¹⁴³ Ce	58143.60c	ENDF/B-VI
¹⁴³ Pr	59143.60c	ENDF/B-VI
¹⁴⁸ Pm	61148.60c	ENDF/B-VI
¹⁵¹ Pm	61151.60c	ENDF/B-VI
¹⁵³ Sm	62153.60c	ENDF/B-VI
¹⁵⁶ Eu	63156.60c	ENDF/B-VI

4. MCNP MODEL DESCRIPTION

The MCNP model used for the heat load calculations is described in this chapter. The MCNP coordinate system employed, and the reference point for defining radial and axial positions, is a three-dimensional Cartesian system with the origin at the core axial midplane and core radial centerline. All components were subdivided into small segments, except where noted. A three-dimensional representation of the ANS reactor model is shown in Fig. 4.1. All dimensions for construction of the model came from the ANS conceptual safety analysis report¹¹ (CSAR) and the ORNL design team.

4.1 CORE AND CENTRAL HOLE

4.1.1 Core

The ANS reactor core was modeled by three radially and axially offset annular fuel elements, each with an active height of 418 mm. The inner upper fuel element (IUFE) has an inner radius of 102 mm and an outer radius of 162 mm. The lower fuel element (LFE) has inner and outer radii of 169 mm and 224 mm, respectively, and the outer upper fuel element (OUFE) has inner and outer radii of 231 mm and 281 mm, respectively. Each fuel element has a 1.143-mm-thick unfueled radial zone inside and outside. The lower end of the active regions of the IUFE and OUFE are 58 mm above the core midplane, and the top of the LFE active region is 58 mm below the core midplane. The active regions of the fuel elements are each subdivided into 16 homogeneous material regions, with the continuous axial and radial fuel density grading represented by varied fuel density in these regions. The fuel densities for these 16 regions were computed from the much finer representation used for fuel grading studies at ORNL. The core is divided into 270 spatial regions, with 90 in each fuel element, including 70 in the active fueled zones. The axial spatial arrangement of the reactor as a whole is shown in Fig. 4.2. A closeup axial view of the primary system is shown in Fig. 4.3. The total core loading is 27.6 kg of ^{235}U .

A second core loading was considered for the three-element design after the initial depletion analyses for the 27.6-kg core (G1294 loading) described previously. This second loading pattern contained 31.0 kg of ^{235}U , with a similar two-dimensional density grading (G395 loading). Because most of the calculations for characterization of the model were completed with the G1294 loading, the bulk of the results presented in Sect. 5 of this report were calculated using this loading. However, a series of calculations undertaken to provide a detailed comparison between the MCNP and VENTURE¹² models used the G395 loading.

The fuel elements are bordered inside and outside by aluminum alloy Al-6061 sideplates, which serve as anchor points and support structure for the circular involute fuel plates. Each sideplate is 7 mm thick and extends 10 mm beyond the top and bottom of the fuel elements.

The boron ends in the core are modeled as homogeneous regions of boron carbide, aluminum alloy Al-6061, and heavy water. The ends have the same inner and outer radii as the active portions of the fuel elements and are 10 mm thick. The total boron loading in the core is 16.5 g of ^{10}B .

Fig. 4.1. Three-dimensional view of the ANS MCNP three-element core reactor model.

Fig. 4.2. Axial view of the reactor model geometry.

Fig. 4.3. Axial view of the geometry inside the core pressure boundary tube (not to scale).

4.1.2 Core Support Structures

Also shown in Fig. 4.3 are the core support structures inside the core pressure boundary tube (CPBT), comprised of the extensions of the fuel element sideplates, both above and below the core. The core support tube is an annulus of inner radius 95 mm and outer radius 102 mm and attaches to the IUFE inner sideplate. The inner support tube is an annulus of inner radius 162 mm and outer radius 169 mm, which connects with the IUFE outer and LFE inner sideplates. The middle support tube is an annulus of inner radius 224 mm and outer radius 231 mm, which connects with the LFE outer and OUFE inner sideplates. All structures are made of the aluminum alloy Al-6061.

The gaps between the structures are filled with pressurized heavy water and with structural supports for the support tubes above and below the fuel elements. These upper and lower support structures are shown in Figs. 4.4 and 4.5, respectively. These vanes (radial fins) and v-ribs physically connect the tubes, greatly increasing the structural stability and strength of the assembly.

4.1.3 Core Pressure Boundary Tube

The CPBT is a double-walled pressure vessel separating the pressurized primary coolant from the unpressurized reflector. The inner wall is an annulus of inner radius 281 mm and outer radius 286 mm, which extends above and below the OUFE outer sideplate to the reflector vessel. The outer wall is an annulus of inner and outer radii 291 mm and 301 mm, respectively. Both walls are composed of Al-6061. The gap between the walls is filled with heavy water. The CPBT is shown in Fig. 4.3.

4.1.4 Control Rods

The central control rods (CCRs) are three hafnium annuli of 1.06-m length with inner and outer radii of 23 mm and 28.25 mm, respectively. The CCRs are supported by the rod support tubes, which are Ti-5Al-2.5Sn titanium alloy annular sleeves around the hafnium. These sleeves have inner and outer radii of 32.5 mm and 35.5 mm, respectively. A titanium alloy retainer at the top of the rod connects the hafnium and support sleeve. The control rods are driven from below the core, and a zirconium alloy drive tube connects the rods with the drive mechanism. These drive tubes have inner and outer radii of 32 mm and 35.5 mm, respectively, and extend from the bottom of the hafnium to the bottom of the vessel. The gaps between the absorbers and support sleeves are filled with pressurized heavy water, as are the interiors of the hafnium tubes. In this beginning of cycle (BOC) configuration, the CCRs are positioned with the bottom of the hafnium tubes 52.2 mm above the core midplane. The rods are located inside the core support tube, at a radius of 52.07 mm from the core centerline. The CCRs are surrounded with pressurized heavy water. The CCRs are shown in Fig. 4.3, with a radial depiction in Fig. 4.6.

The guide assembly for the control rod drive rods below the core was also included in the model. The guide assembly also contains the springs to insert the control rods during emergency shutdown. The guide is a triangular slab of Al-6061 with truncated apexes and holes bored out for the drive rods. A radial view of the guide assembly is shown in Fig. 4.5.

Fig. 4.4. Radial view of the upper core support structures.

Fig. 4.5. Radial view of the lower core support structures and the central control rod guide assembly.

Fig. 4.6. Radial view of the in-core target locations and the central control rods.

To accommodate the guide assembly, the central hole radius was increased below the core from 95 to 129.5 mm, with accompanying changes in the inner and outer radii of the core support and inner support tubes. This expansion of the central hole is shown in Fig. 4.3.

4.1.5 In-Core Targets

4.1.5.1 Upper Irradiation Targets

The upper irradiation targets, or in-core material irradiation targets, are a set of ten targets, composed of 87% aluminum and 13% SS-316, located between the upper fuel elements (UFEs). The targets are located at a radius of 196.5 mm from the core centerline and 58 mm above the core centerline. The instrumented targets are 43 mm in diam and 600 mm long, and the uninstrumented targets are 16 mm in diam and 507 mm in length. Both target types are clad with a 3-mm annular Al-6061 tube. The instrumented target tubes extend to the top of the reflector vessel and have a hemispherical endcap; this helps protect the instrumentation cables. The uninstrumented target tubes are the same length as the targets. The target clad tubes are attached to the inner and middle support tubes by radial fins. The targets are ganged with the transplutonium production targets by azimuthal fins. In the model, these fins (radial and azimuthal) are smeared into the surrounding pressurized heavy water. The targets are located symmetrically about the core centerline. The radial layout of the targets is shown in Fig. 4.6. A sample instrumented target is shown in Fig. 4.7, and a sample uninstrumented target is shown in Fig. 4.8.

4.1.5.2 Transplutonium Production Targets

The transplutonium production targets are a set of up to 30 locations between the UFEs at a radius of 196.5 mm from the core centerline. These targets are 58 mm above the core midplane. The targets are composed of actinide oxide/aluminum powder pellets of 2.4756 mm radius clad with a thin layer of Al-1100 acting as cladding. The targets are 508 mm in length. Each target sits inside an Al-6061 tube with inner radius 3.3274 mm and outer radius 4.7625 mm. These 30 target locations are located symmetrically about the LFE, as shown in Fig. 4.6. The targets are designed for the production of californium and einsteinium for industrial and experimental uses. A sample target is shown in Fig. 4.9, with two targets in their axial position shown in Fig. 4.3.

4.1.6 Piping and Other Components

The inlet and outlet piping and supports are also included in the MCNP model. The pipes are stainless steel, and the general structure of the piping, seals, and support pads can be seen in Fig. 4.2. In the reflector is a hafnium shield to reduce the neutron and photon flux on the primary system inlet piping (also seen in Fig. 4.2). This shield is formed of a 15-mm-thick disk with a 10-mm-thick, 50-mm-high annulus. The inner and outer radii of the disk are 301 and 500 mm, respectively, and the bottom of the disk is 2012.2 mm below the core midplane. The inner radius of the annular section is 310 mm.

04/27/95 09:35:15
ans1074 - INPUT DECK FOR MCNP
FOR THE ADVANCED NEUTRON SOURCE

probid = 04/27/95 09:09:34
basis:
(0.000000, 1.000000, 0.000000)
(0.000000, 0.000000, 1.000000)
origin:
(19.65, 0.00, 40.00)
extent = (2.50, 40.00)

Fig. 4.7. Axial view of an instrumented in-core irradiation target.

04/27/95 09:36:45
 mns1074 - INPUT DECK FOR MCP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/27/95 09:09:38
 basis:
 (0.000000, 1.000000, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (-19.65, 0.00, 32.00)
 extent = (2.50, 30.00)

Fig. 4.8. Axial view of an uninstrumented in-core irradiation target.

04/27/95 09:38:58
 4441074 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/27/95 09:09:34
 basis:
 (0.000000, 1.000000, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (19.22, 4.09, 49.00)
 extent = (0.50, 45.00)

Fig. 4.9. Axial view of a transplutonium production target.

4.2 REFLECTOR COMPONENTS

The reflector components of the ANS model are described in this section. Figure 4.10 shows a view of the reflector at the core midplane level. All vertically oriented facilities extend upward to the reflector vessel top, and all horizontally oriented facilities extend outward to the reflector vessel walls. All locations were provided by the ANS design team at ORNL, and the facility shapes and dimensions were obtained from ref. 11.

4.2.1 Safety Rods

The safety shutdown rods (SSRs) are eight rods arranged symmetrically outside the CPBT at a radius of 340 mm. Each rod is composed of a 600-mm-long hafnium annulus with inner and outer radii of 38.48 and 42.545 mm, respectively, supported by an Al-6061 support tube. The support tube has inner and outer radii of 34.55 and 38.48 mm, respectively, inside the hafnium, and 34.55 and 42.545 mm, respectively, above the hafnium. Each SSR has a 64.77-mm-thick Al-6061 leader, on which the hafnium annulus rests. Surrounding each SSR in the parked position is an annular Al-6061 sheath with inner and outer radii of 44.45 and 51.625 mm, respectively. The sheaths act to attenuate the neutron and photon flux impinging on the SSRs when in the parked position. The SSRs are driven from above the reflector vessel. The radial layout of the safety rods is shown in Fig. 4.11; a typical SSR is shown in Fig. 4.12.

4.2.2 Beam Tubes

4.2.2.1 Thermal Beam Tubes

There are three different beam tube types in the present ANS design. The thermal beam tubes (a typical one is shown in Fig. 4.13), are centered at the core midplane, with the tip of the beam tube nose at a radius of 470 mm from the core centerline; this arrangement is shown in Fig. 4.6. Each of the seven thermal beam tubes is a cylindrical annulus with outer radius 54 mm and inner radius 50 mm. Each tube has a hemispherical endcap with inner and outer radii of 51 and 53 mm, respectively. The walls and endcaps are composed of Al-6061, and the tubes are evacuated within.

4.2.2.2 Through-Tube

The second beam tube type is the through-tube, which is a cylindrical Al-6061 tube of inner and outer radii 98 and 106 mm, respectively. The tube is evacuated within. The through-tube is shown in Fig. 4.14.

4.2.2.3 Large Slant Beam Tube

The third beam tube type is the large slant beam tube (LSBT). The LSBT is two concentric cylindrical slanted tubes of Al-6061, with heavy water between the tubes, and air

Fig. 4.10. Radial view of the reactor model at the core midplane ($z=0$).

Fig. 4.11. Radial view of the safety shutdown rod locations.

04/27/95 09:31:05
 mas1074 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/27/95 09:09:36
 basis:
 (1.000000, 0.000000, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (37.84, 14.15, 145.00)
 extent = (6.00, 85.00)

Fig. 4.12. Axial view of an SSR.

04/14/95 14:29:59
 mas1063 - INPUT DECK FOR HEXP
 FOR THE ADVANCED NEUTRON SOURCE
 probid = 04/14/95 14:16:37
 basis:
 (-0.927184, -0.374607, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (-99.91, -81.08, 0.00)
 extent = (96.00, 7.00)

Fig. 4.13. Axial view of a thermal beam tube.

04/14/95 15:19:58
 ms1063 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 14:16:37
 basis:
 (-0.484810, 0.874620, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (69.97, 38.78, -30.00)
 extent = (200.00, 11.00)

Fig. 4.14. Axial view of the through-tube.

inside the inner tube. The inner tube has inner radius of 100 mm, and the outer tube has an inner radius of 110 mm. Both have a 5-mm wall thickness. The tubes are capped with hemispherical Al-6061 endcaps with 5-mm wall thickness. The LSBT is located at radius 801.75 mm, and the nose of the outer endcap is 365.24 mm above midplane. The LSBT is shown in Fig. 4.15.

4.2.3 Irradiation Facilities

The reflector irradiation facilities consist of the four hydraulic tubes (HT), the two slant holes (SH), five pneumatic tubes (PT), and two pneumatic facilities (PFs) outside the reflector vessel in the biological shield. A description of each follows.

4.2.3.1 Hydraulic Tubes

The HTs are facilities formed by two concentric cylindrical Al-6061 tubes. The outer tube has inner and outer radii of 17.5 and 21.1 mm, respectively, and the inner (flight) tube has inner and outer radii of 7.1 and 9.5 mm, respectively. The gap between the tubes is filled with heavy water, as is the remainder of the space in the flight tube outside of the sample. Samples in three of the four HTs are composed of 50% aluminum and 50% SS-316 and are 585.8 mm long with outer radius of 50 mm. The target in HT-2 has a very detailed structure within these dimensions, with nine individual target capsule assemblies. Each capsule is composed of aluminum and ^{249}Cf , with the assembly structure of Al-6061.

Two of the HTs, HT-1 and HT-3, are vertical tubes at radius 1064 mm, with the bottom of the tubes 366.65 mm below the core midplane. The other two, HT-2 and HT-4, are curved above the top of the UFE, with the bottom of HT-2 at radii 360 and 88.2 mm below the core midplane, and the bottom of HT-4 at radii 500 and 366.65 mm below the midplane. In both of these HTs, the irradiation zone at the core level is vertical. The curved section is modeled as the abutment of the vertical section with a slanted section. Typical HTs are shown in Figs. 4.16 and 4.17, with a closeup view of the target in HT-2 shown in Fig. 4.18.

4.2.3.2 Slant Holes

The SHs are facilities formed by two concentric cylindrical Al-6061 tubes. The outer tube has inner and outer radii of 36.5 and 40.0 mm, respectively, and the inner tube has radii 26.15 and 27.75 mm, respectively. The gap between the tubes is filled with heavy water, and the space outside the sample in the inner tube is evacuated. Both tubes are located at a radius of 380 mm, with the bottom of the tubes 27.77 mm below the midplane. For HT-2 and HT-4, the approach from above the core to the irradiation zone is curved. This curved section is modeled as the abutment of the vertical section with a slanted section. A typical SH (upper and lower sections) is shown in Fig. 4.19.

04/27/95 10:25:30
ms1074 - INPUT DECK FOR MWP
FOR THE ADVANCED NEUTRON SOURCE

probid = 04/27/95 10:01:20

basis:

(0.924309, -0.170210, 0.341587)

(-0.361192, -0.369131, 0.848040)

origin:

(21.27, -90.48, 121.33)

extent = (12.00, 105.00)

Fig. 4.15. Axial view of the large slant beam tube.

04/14/95 15:29:37
 #1063 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 14:16:37
 basis:
 (1.000000, 0.000000, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (99.99, 36.39, 90.00)
 extent = (2.15, 210.00)

Fig. 4.16. Axial view of hydraulic tube HT-1. Hydraulic tube HT-3 is similar.

04/14/95 15:44:11
ans1063 - INPUT DECK FOR MCNP
FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 14:16:37
basis:
(0.386051, 0.922477, 0.000000)
(0.000000, 0.000000, 1.000000)
origin:
(13.51, 60.29, 105.00)
extent = (40.00, 115.00)

Fig. 4.17. Axial view of hydraulic tube HT-2. Hydraulic tube HT-4 is similar.

04/14/95 15:46:50
ans1063 - INPUT DECK FOR MCNP
FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 16:16:37
basis:
(0.316051, 0.922477, 0.000000)
(0.000000, 0.000000, 1.000000)
origin:
(0.00, 36.00, 22.00)
extent = (2.15, 35.00)

Fig. 4.18. Axial view of the target assembly in hydraulic tube HT-2.

04/16/95 15:56:15
ms1063 - INPUT DECK FOR MCNP
FOR THE ADVANCED NEUTRON SOURCE

probid = 04/16/95 14:16:37
basis:
(-0.937193, 0.374608, 0.000000)
(0.000000, 0.000000, 1.000000)
origin:
(-65.65, 14.73, 110.00)
extent = (35.00, 110.00)

Fig. 4.19. Axial view of slant tube SH-1. Slant tube SH-2 is similar.

4.2.3.3 Pneumatic Tubes

The PTs are four short slanted tubes and one long vertical tube with a rabbit transfer tube and four air tubes inside. The outer tube and transfer tube are concentric, and the air tubes are arranged at the four "compass points" about the transfer tube. The vertical tube (PT-1) is at radius 1650 mm, and the bottom is 304.8 mm below midplane. Two of the slanted tubes, PT-3 and PT-4, have their lower ends at radii 1012.11 and 1206.33 mm above midplane, with the other two slanted tubes, PT-2 and PT-5, at radii 1190.81 and 1419.25 mm above midplane. PT-1, PT-2, and PT-3 are shown in Figs. 4.20 to 4.22.

4.2.3.4 Pneumatic Facilities

The PFs, PF-1 and PF-2, are two adjoining rectangular cross section shells with a cylindrical air tube on each side. The shells and tube walls are composed of Al-6061; these are located at radii 1822.7 and 1848.1 mm, respectively, and terminate 67 mm above and 60 mm below midplane, respectively. The rectangular shell has outside dimensions of 44.45×127 mm. The wall thickness of three of the walls is 6.35 mm, and the fourth wall is 11.11 mm thick. The air tubes have an outer radius of 6.35 mm and wall thickness of 1.65 mm. The PFs are shown in Figs. 4.23 and 4.24.

4.2.4 Isotope Production Facilities

The four isotope production facilities [vertical holes (VHs)] are made of three concentric cylindrical tubes composed of Al-6061, with each facility containing an aluminum/iridium target. Three of the VHs are located at radius 1384 mm, with the fourth at radius 1070.7 mm, and all terminate 496.96 mm below midplane. The outer tube has outer radius 30.15 mm, and the inner tube has outer radius 21.1 mm. Both have a wall thickness of 4.8 mm. The target holder, the innermost tube, is 3.175 mm thick with an inner radius of 9.525 mm. The aluminum/iridium targets are 8.9535 mm in radius and 1.07 m long and contain 7.5 g of natural iridium. A typical VH is shown in Fig. 4.25.

4.2.5 Cold Sources

A typical cold source is shown in Figs. 4.26 and 4.27. The moderator vessel is a spherical shell filled with liquid deuterium. This is surrounded by a helium-filled inner thimble, an outer thimble, and a cooling jacket outside. The space between thimbles is evacuated, and the gap between cooling jacket and outer thimble is filled with heavy water. The cold source thimble contains the moderator vessel, two tie rods to support it, a liquid deuterium feed line and return line for cooling the moderator vessel, and a very cold guide (VCG) tube for extracting cold neutrons from the reentrant cavity in the moderator vessel. All components are composed of Al-6061. The cold sources are located at 750 mm radius and 25 mm above the midplane. These locations are also shown in Fig. 4.6.

04/14/95 16:16:29
 mes1063 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 16:16:37
 basis:
 (1.000000, 0.000000, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (135.16, 94.64, 75.00)
 extent = (6.00, 110.00)

Fig. 4.20. Axial view of pneumatic tube PT-1.

04/19/95 09:56:55
 ms1074 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/19/95 08:02:36
 basis:
 (0.405943, 0.649642, -0.642718)
 (0.340626, 0.545115, 0.766044)
 origin:
 (71.96, 116.16, 161.84)
 extent = (0.00, 37.00)

Fig. 4.21. Axial view of pneumatic tube PT-2. Pneumatic tube PT-5 is similar.

04/19/95 09:58:43
 ms1074 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/19/95 08:02:36
 basis:
 (0.185322, 0.743290, -0.642788)
 (0.155504, 0.623694, 0.766044)
 origin:
 (30.71, 123.15, 151.27)
 extent = (8.00, 45.00)

Fig. 4.22. Axial view of pneumatic tube PT-3. Pneumatic tube PT-4 is similar.

04/14/95 17:02:06
 mas1063 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 14:16:37
 basis:
 (-0.515047, 0.857162, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (156.24, 93.88, 123.00)
 extent = (10.00, 135.00)

Fig. 4.23. Axial view of pneumatic facility PF-1. Pneumatic facility PF-2 is similar.

04/14/95 17:05:26
 mas1063 - INPUT DECK FOR NEWP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 14:16:37

Axis:

(-0.515038, 0.857167, 0.000000)

(0.857167, 0.515038, 0.000000)

origin:

(160.52, 96.45, 123.00)

extent = (10.00, 10.00)

Fig. 4.24. Radial view of the pneumatic facilities.

04/14/95 16:28:16
 ans1063 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 14:16:37
 basis:
 (1.000000, 0.000000, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (125.94, 57.39, 70.00)
 extent = (3.10, 125.00)

Fig. 4.25. Axial view of vertical isotope production facility VH-1. Facilities VH-2, VH-3, and VH-4 are similar.

04/14/95 16:06:18
 ms1063 - INPUT DECK FOR MEMP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/14/95 16:16:37
 basis:
 (-0.777146, 0.639320, 0.000000)
 (0.639320, 0.777146, 0.000000)
 origin:
 (-68.32, 109.56, 2.50)
 extent = (90.00, 40.00)

Fig. 4.26. Radial view of cold source CS-1. Cold source CS-2 is similar.

04/14/95 16:24:42
 ms1063 - INPUT DECK FOR NEWP
 FOR THE ADVANCED NEUTRON SOURCE
 probid = 04/14/95 14:16:37
 base: (-0.772869, 0.635957, 0.104771)
 (0.624566, 0.762262, 0.127606)
 origin: (-82.52, 121.86, 21.31)
 extent = (70.00, 25.00)

Fig. 4.27. Axial view of the very cold guide tube and the liquid D_2 lines in cold source CS-1. The components in cold source CS-2 are similar.

4.2.6 Slant Cold Guide Tubes

The slant cold guide (SCG) tubes are two concentric, cylindrical, slanted Al-6061 tubes extending from each cold source to the reflector vessel top. The inner and outer radii of the inner tubes are 77.1 and 84.2 mm, respectively, and 88.9 and 95.25 mm, respectively, for the outer tubes. The gap between the tubes is evacuated, as is the inner tube. The centerline of each tube points at the center of the moderator vessel of the respective cold source. A typical SCG tube (SCG-1) is shown in Fig. 4.28.

4.2.7 Positron Hydraulic Tube

The positron hydraulic tube (HTP) is similar in shape size to the slant tubes. The HTP is located at a radius of 609.1 mm, and the bottom of the outer tube endcap is 100 mm below core midplane. The HTP is formed of three concentric tubes, with a curved section linking the slanted upper section with the vertical lower (irradiation) section. The outer tube has an outer radius of 41.275 mm and an inner radius of 34.925 mm, with a hemispherical endcap of the same thickness. The inner tube has inner and outer radii of 26.925 and 28.575 mm, respectively, and terminates 334 mm above core midplane. The target sleeve has inner and outer radii of 194 and 20.6325 mm, respectively, and terminates 55.55 mm below core midplane. The section of the sleeve exposed below the inner tube is the irradiation zone, where the target assembly is positioned. The gaps between the tubes are filled with heavy water. The HTP is shown in Fig. 4.29.

The target assembly, shown in detail in Fig. 4.30, houses four capsules composed of aluminum and copper pellets, with pressurized helium filling the gaps. The target structure is composed of Al-6061, with heavy water coolant.

4.2.8 Hot Source

The ANS hot source is shown in Figs. 4.31 and 4.32. The moderator is a sphere of graphite surrounded by a graphite wool insulating material. This is surrounded by three Zircaloy-4 shells with light water between the first two and helium between the second two, a helium-filled inner thimble, and an outer thimble. The space between thimbles is filled with heavy water. All components, other than the two Zircaloy-4 shells and graphite moderator/insulator, are composed of Al-6061. The hot source is located at a radius of 1000 mm from the core centerline and is at the core midplane. This location is also shown in Fig. 4.6.

4.3 REFLECTOR VESSEL AND BIOLOGICAL SHIELD

The reflector vessel is divided into three major sections: the vessel top, vessel wall, and vessel bottom (see Fig. 4.2). All are composed of Al-6061. The top and bottom are each 50.8 mm thick, with the top section having an outer radius of 723.9 mm and the bottom section an outer radius of 476.25 mm. Both the top and bottom are penetrated by the CPBT.

04/10/95 16:56:56
 #1063 - INPUT DATA FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/10/95 16:16:37
 basis:
 (-0.809054, 0.448884, -0.379853)
 (-0.332229, 0.184165, 0.925044)
 origin:
 (-61.56, 93.90, 113.50)
 extent = (10.00, 100.00)

Fig. 4.28. Axial view of slant cold guide SCG-1. Slant cold guide SCG-2 is similar.

04/17/95 09:29:58
ans1063 - INPUT DECK FOR MCNP
FOR THE ADVANCED NEUTRON SOURCE

probid = 04/17/95 09:02:28
basis:
(0.993572, 0.113203, 0.000000)
(0.000000, 0.000000, 1.000000)
origin:
(73.93, -42.70, 95.00)
extent = (40.00, 110.00)

Fig. 4.29. Axial view of the positron hydraulic tube.

04/17/95 09:33:26
 ***1063 - INPUT DECK FOR MCNP
 FOR THE ADVANCED NEUTRON SOURCE

probid = 04/17/95 09:02:28
 basis:
 (0.993572, 0.112203, 0.000000)
 (0.000000, 0.000000, 1.000000)
 origin:
 (39.15, -46.66, 14.20)
 extent = (5.00, 25.00)

Fig. 4.30. Axial view of the target assembly in the positron hydraulic tube.

```

04/17/95 09:43:12
anal063 - INPUT DECK FOR MCNP
FOR THE ADVANCED NEUTRON SOURCE

prebid = 04/17/95 09:03:38
base:
( 0.173548,-0.988808, 0.000000)
( 0.988808, 0.173548, 0.000000)
origin:
( 70.22, -122.46, 0.00)
extent = ( 75.00, 36.00)

```

Fig. 4.31. Radial view of the hot source.

04/19/95 10:01:50
ans1074 - INPUT DECK FOR MCNP
FOR THE ADVANCED NEUTRON SOURCE

probid = 04/19/95 08:02:36
basis:
(1.000000, 0.000000, 0.000000)
(0.000000, 1.000000, 0.000000)
origin:
(62.40, -78.14, 0.00)
extent = (25.00, 25.00)

Fig. 4.32. Radial view of the hot source graphite moderator.

The wall is a cylindrical annulus with a 27-mm-thick wall and truncated conical annuli connecting the wall with the top and bottom sections. Attached to the wall are bosses for the beam tubes, cold sources, through-tube, and hot source; some of these are shown in Figs. 4.1 and 4.2.

The biological shield is a vessel of light water in which the reflector vessel sits. This shield is several meters in diameter and is not necessary to the model. Thus, only a small section (300 mm radially and 200 mm axially) is included in this model.

5. CALCULATIONS AND RESULTS

This section describes the calculations performed for analysis of the three-element core configuration. All calculations were performed at BOC, except where noted.

5.1 COMPONENT REACTIVITY WORTHS

A series of MCNP cases was run to determine the reactivity worth of the various components of the three-element baseline model. To accomplish this, the major core and reflector components were individually removed from the baseline model. Additionally, cases were also run to determine the reactivity impact of the limiting events shown in Table 4.3-10 of the ANS CSAR.¹³ The results of these cases are summarized in Table 5.1. These show that although the CCR worth is significantly less than for the two-element core, the core structures are worth much more. This is because of the increased amount of structural material in the three-element core and to the close proximity of the CCRs to the IUFE. This results in a slightly harder spectrum in the central hole, reducing the worth of the primarily thermal absorber used for control.

A reactivity balance similar to that shown in Table 4.3-3 of the ANS CSAR was also constructed, with components being sequentially added to the model, beginning with the core alone at 293K (20°C) in the reflector vessel. These results are shown in Table 5.2. There is one noteworthy difference from the two-element core in these results. These results show that addition of the hot source to the reflector is a positive reactivity effect. This is because of the replacement of heavy water with a large chunk of graphite, which is a more efficient moderator than heavy water.

5.2 CENTRAL CONTROL ROD BANK WORTH

A series of cases was run to determine the integral and differential reactivity worth of the three CCR bank at BOC for the three-element baseline MCNP model. These results are shown in Table 5.3 and Figs. 5.1 and 5.2. In all cases, the rod position given is the position of the leading tip of the hafnium in the CCRs. These results are very similar in nature to the rod bank worths for the two-element core.

5.3 SAFETY SHUTDOWN ROD BANK WORTH

A series of cases was run to determine the integral and differential reactivity worth of the eight SSR bank at BOC for the three-element baseline MCNP model. These results are shown in Table 5.4 and Figs. 5.3 and 5.4. In all cases, the rod position given is the position of the leading tip of the hafnium in the SSRs. Note that the integral bank worth passes through a maximum at about -350 mm from the core midplane, but the differential bank

Table 5.1. Component reactivity worths for the three-element baseline MCNP model at beginning of cycle

Case	Description	k_{eff}	Reactivity (%) ^a
ANS1073	Base case	0.9993 ± 0.0019	—
ANS1080	Reflector elements removed	1.0487 ± 0.0023	4.71
ANS1081	Safety rods removed	1.0062 ± 0.0026	0.69
ANS1082	In-core targets and structures removed	1.0185 ± 0.0027	1.89
ANS1083	CCRs fully withdrawn	1.0492 ± 0.0022	4.76
ANS1084	Beam tubes and through-tube removed	1.0088 ± 0.0034	0.94
ANS1085	Cold sources removed	1.0184 ± 0.0029	0.88
ANS1086	Hot source removed	0.9986 ± 0.0020	-0.07
ANS1087	Slant tubes removed	1.0126 ± 0.0024	1.31
ANS1088	Hydraulic tubes removed	1.0070 ± 0.0024	0.77
ANS1089	Positron facility removed	1.0023 ± 0.0021	0.30
ANS1090	Core support and CCR structures removed	1.0002 ± 0.0025	0.09
ANS1091	Borated endplates removed	1.1025 ± 0.0031	9.37
ANS1092	Primary system temperature at 20°C ^b	0.9952 ± 0.0026	-0.41
ANS1093	CPBT assembly removed	1.0534 ± 0.0030	5.14
ANS1094	Core supports and structures removed	1.0414 ± 0.0030	4.05
ANS1095	CCRs totally removed	1.0696 ± 0.0022	6.58
ANS1096	CCR fully inserted	0.9303 ± 0.0027	-7.42
ANS1097	Safety rods inserted to core midplane	0.9186 ± 0.0038	-8.79
ANS1098	Core alone, at 20°C, in reflector vessel	1.4479 ± 0.0023	31.00
ANS1099	15% H ₂ O in primary system	0.9607 ± 0.0035	-4.02

^aBecause of MCNP statistics, reactivity worths less than ~0.5% may not be accurate.

^bDoes not include fuel Doppler.

Table 5.2. Core reactivity balance and component reactivity worths at beginning of cycle for the three-element baseline MCNP model

Case	Description	k_{eff}	Reactivity	
			(pcm) ^a	$\Delta\rho(\text{pcm})$
ANS1098	Core alone at 20°C in reflector vessel	1.4479 $\pm$ 0.0023	30904	--
ANS1100	ANS1098 with temperature effect ^b	1.4382 $\pm$ 0.0026	30439	-465
ANS1101	ANS1100 with borated endplates	1.2732 $\pm$ 0.0024	21428	-9011
ANS1102	ANS1101 with CPBT and core supports	1.1568 $\pm$ 0.0018	13525	-7903
ANS1103	ANS1102 with in-core irradiation facilities	1.1308 $\pm$ 0.0016	11537	-1988
ANS1104	ANS1103 with beam tubes	1.1233 $\pm$ 0.0027	10947	-590
ANS1105	ANS1104 with cold sources	1.0926 $\pm$ 0.0022	8445	-2502
ANS1106	ANS1105 with hot source	1.0936 $\pm$ 0.0031	8529	+84
ANS1107	ANS1106 with remainder of reflector elements	1.0730 $\pm$ 0.0021	6773	-1756
ANS1108	ANS1107 with CCR inserted to +52.2 mm from core midplane	1.0003 $\pm$ 0.0032	0	-6773
ANS1109	ANS1107 with SSR inserted to core midplane	0.9650 $\pm$ 0.0038	-3657	-10430
ANS1110	ANS1109 with CCR fully inserted	0.7979 $\pm$ 0.0032	-25359	-21702

^aPercent mille.

^bDoes not include fuel Doppler.

Table 5.3. CRR reactivity worth at beginning of cycle for the baseline three-element MCNP model

Case	Control rod position (mm from midplane)	k_{eff}	Reactivity		Differential worth (pcm/mm)
			(pcm) ^a	$\Delta\rho(\text{pcm})$	
ANS1083	+530	1.0492 $\pm$ 0.0022	+4659	—	—
ANS1122	+476	1.0471 $\pm$ 0.0028	+4468	-191	-3.54
ANS1123	+400	1.0386 $\pm$ 0.0022	+3687	-781	-10.28
ANS1124	+300	1.0328 $\pm$ 0.0024	+3146	-541	-5.41
ANS1125	+200	1.0201 $\pm$ 0.0022	+1940	-1206	-12.06
ANS1126	+100	1.0017 $\pm$ 0.0037	+140	-1800	-18.00
ANS1108	+52.2	1.0003 $\pm$ 0.0032	0	-140	-2.93
ANS1127	0	0.9908 $\pm$ 0.0029	-959	-959	-18.37
ANS1128	-100	0.9756 $\pm$ 0.0024	-2531	-1572	-15.72
ANS1129	-200	0.9531 $\pm$ 0.0025	-4951	-2420	-24.20
ANS1130	-300	0.9440 $\pm$ 0.0033	-5962	-1011	-10.11
ANS1131	-400	0.9344 $\pm$ 0.0031	-7051	-1089	-10.89
ANS1132	-476	0.9294 $\pm$ 0.0034	-7626	-575	-7.57
ANS1096	-530	0.9303 $\pm$ 0.0027	-7527	+99	+1.83

^aPercent mille.

Fig. 5.1. Three-element core central control rod bank worth at beginning of cycle.

Fig. 5.2. Three-element core central control rod differential worth at beginning of cycle.

**Table 5.4. Safety rod reactivity worth at beginning of cycle for the
three-element baseline MCNP model**

Case	Safety rod position (mm from midplane)	k_{eff}	Reactivity		Differential worth (pcm/mm)
			(pcm) ^a	$\Delta\rho$ (pcm)	
ANS1108	+744	1.0003 $\pm$ 0.0032	0	—	—
ANS1111	+476	0.9846 $\pm$ 0.0020	-1594	-1594	-5.95
ANS1112	+400	0.9770 $\pm$ 0.0027	-2384	-790	-10.40
ANS1113	+300	0.9658 $\pm$ 0.0027	-3571	-1187	-11.87
ANS1114	+200	0.9483 $\pm$ 0.0032	-5482	-1911	-19.11
ANS1115	+100	0.9323 $\pm$ 0.0029	-7292	-1810	-18.10
ANS1097	0	0.9186 $\pm$ 0.0038	-8891	-1599	-15.99
ANS1116	-100	0.8872 $\pm$ 0.0045	-12744	-3853	-38.53
ANS1117	-200	0.8650 $\pm$ 0.0033	-15637	-2893	-28.93
ANS1118	-300	0.8435 $\pm$ 0.0035	-18584	-2947	-29.47
ANS1133	-350	0.8418 $\pm$ 0.0036	-18823	-239	-4.78
ANS1119	-400	0.8423 $\pm$ 0.0043	-18753	+70	+1.40
ANS1120	-476	0.8615 $\pm$ 0.0033	-16107	+2646	+34.82
ANS1121	-600	0.8799 $\pm$ 0.0044	-13679	+2428	+19.58

^aPercent mille.

Fig. 5.3. Three-element core safety shutdown rod bank worth at beginning of cycle.

Fig. 5.4. Three-element core safety shutdown rod differential worth at beginning of cycle.

worth occurs near the midplane. It is easily seen from this that the SSRs have a much greater effect on the core reactivity when they are inserted to be even with the upper half of the LFE. This is because in this region, the SSRs are absorbing neutrons in the reflector that influence both the OUFE and the LFE.

5.4 REACTIVITY COEFFICIENTS

5.4.1 Void Reactivity Worth

A series of MCNP cases was run to determine the reactivity worth of uniformly distributed void in the reflector. These results are shown in Table 5.5 and Figs. 5.5 and 5.6. The results show that the core is relatively sensitive to the void content, or density, of the reflector, which is very similar to the two-element core behavior.

A second series was run to determine the reactivity worth of uniformly distributed void in the central hole. These results are shown in Table 5.6. For the low void contents ($>20\%$), the reactivity effects are too small to be determined accurately with Monte Carlo and are influenced greatly by statistical fluctuations. Only the large void contents, or density reductions, show any meaningful results. However, these tend to imply that voiding in the central hole is not very important to the core reactivity, as even completely voiding the region produces a reactivity drop of less than 2000 pcm.

A series of MCNP calculations was run to determine the void reactivity worth in the fuel elements, both separately and together. For the individual fuel elements, only the individual element and coolant channel above the element were subjected to changes in the uniformly distributed void content of the coolant. For the cases with all three fuel elements, all the fuel elements and coolant channels above were voided. In all cases, the central hole and reflector contained no voids in the coolant. The results of these calculations are shown in Tables 5.7 to 5.10; selected data sets are displayed in Figs. 5.7 and 5.8. These results show that the UFEs (Tables 5.7 and 5.9) are relatively insensitive to void content, while voiding the LFE caused a much greater negative reactivity insertion. This is because of the voiding of the coolant channel above the lower element, which passes between the two upper elements and provides moderation for the fission neutrons in both elements. This decrease in moderation results in the greater loss of core reactivity.

Note that the differential worths for the UFEs may not be accurate because of the small reactivity differences. The statistics on the k_{eff} results are insufficient to allow accurate differential worths to be determined. It is recommended that these be examined more closely using the ORNL VENTURE model to get a more accurate quantification of these effects. A series of MCNP cases using the three-element reactor model was run to determine the reactivity worth of voiding the core bypass region and, simultaneously, a thin region of the reflector adjacent to the fuel elements. The bypass region was voided in the same axial region as the reflector in all cases. Two sets of computations were performed, one adjacent to the UFEs only and one adjacent to both the UFEs and LFEs. The thickness of the void region in the reflector was varied from 5 to 30 mm in thickness from the CPBT wall. The core eigenvalue was computed in each case.

**Table 5.5. Uniformly distributed void worth in the reflector at beginning of cycle
for the three-element baseline MCNP model**

Case	Void (%)	k_{eff}	Reactivity		Void worth (pcm/mm)
			(pcm) ^a	$\Delta\rho$ (pcm)	
ANS1108	0	1.0003 ± 0.0032	0	--	--
ANS1134	5	0.9869 ± 0.0033	-1357	-1357	-271.5
ANS1135	10	0.9794 ± 0.0027	-2133	-776	-155.3
ANS1136	20	0.9577 ± 0.0033	-4447	-2314	-231.4
ANS1137	50	0.8552 ± 0.0030	-16962	-12515	-417.2
ANS1138	75	0.7149 ± 0.0030	-39910	-22948	-917.9
ANS1139	100	0.4952 ± 0.0059	-101969	-62059	-2482.3

^aPercent mille.

Fig. 5.5. Three-element core reflector void reactivity worth at beginning of cycle.

Fig. 5.6. Three-element core reflector void differential worth at beginning of cycle.

**Table 5.6. Uniformly distributed void worth in the central hole at beginning of cycle
for the three-element baseline MCNP model**

Case	Void (%)	k_{eff}	Reactivity		Void worth (pcm/%)
			(pcm) ^a	$\Delta\rho$ (pcm) ^a	
ANS1108	0	1.0003 ± 0.0032	0	--	--
ANS1140	5	1.0039 ± 0.0029	+358	+358	+71.7
ANS1141	10	0.9997 ± 0.0021	-60	-418	-83.6
ANS1142	20	0.9948 ± 0.0033	-553	-493	-49.3
ANS1143	50	0.9960 ± 0.0034	-432	+121	+4.0
ANS1144	75	0.9921 ± 0.0031	-826	-394	-15.8
ANS1145	100	0.9837 ± 0.0028	-1687	-861	-34.4

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~500 pcm (percent mille) may not be accurate.

**Table 5.7. Uniformly distributed void worth in the IUFE at beginning of cycle
for the three-element baseline MCNP model (coolant channels above this element were also voided)**

Case	Void (%)	k_{eff}	Reactivity		Void worth (pcm/%)
			(pcm) ^a	$\Delta\rho$ (pcm) ^a	
ANS1108	0	1.0003 $\pm$ 0.0032	0	---	---
ANS1146	5	0.9984 $\pm$ 0.0028	-190	-190	-38.0
ANS1147	10	0.9959 $\pm$ 0.0032	-442	-252	-50.4
ANS1148	20	0.9950 $\pm$ 0.0024	-533	-91	-9.1
ANS1149	50	0.9926 $\pm$ 0.0023	-776	-243	-8.1
ANS1150	75	0.9948 $\pm$ 0.0034	-553	+223	+8.9
ANS1151	100	0.9884 $\pm$ 0.0029	-1204	-651	-26.0

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~ 500 pcm (percent mille) may not be accurate.

Table 5.8. Uniformly distributed void worth in the LFE at beginning of cycle for the three-element baseline MCNP model (coolant channels above this element were also voided)

Case	Void (%)	k_{eff}	Reactivity		Void worth (pcm/%)
			(pcm) ^a	$\Delta\rho$ (pcm) ^a	
ANS1108	0	1.0003 ± 0.0032	0	—	—
ANS1152	5	0.9955 ± 0.0030	-482	-482	-96.4
ANS1153	10	0.9919 ± 0.0029	-847	-365	-73.0
ANS1154	20	0.9886 ± 0.0029	-1183	-336	-33.6
ANS1155	50	0.9681 ± 0.0025	-3325	-2142	-71.4
ANS1156	75	0.9592 ± 0.0028	-4284	-959	-38.4
ANS1157	100	0.9428 ± 0.0032	-6097	-1813	-72.5

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~500 pcm (percent mille) may not be accurate.

Table 5.9. Uniformly distributed void worth in the OUFE at beginning of cycle for the three-element baseline MCNP model (coolant channels above this element were also voided)

Case	Void (%)	k_{eff}	Reactivity		Void worth (pcm/%)
			(pcm) ^a	$\Delta\rho$ (pcm) ^a	
ANS1108	0	1.0003 ± 0.0032	0	—	—
ANS1158	5	0.9950 ± 0.0022	-533	-533	-106.6
ANS1159	10	0.9967 ± 0.0025	-361	+172	+34.4
ANS1160	20	0.9923 ± 0.0032	-806	-445	-44.5
ANS1161	50	0.9882 ± 0.0032	-1224	-418	-13.9
ANS1162	75	0.9853 ± 0.0027	-1522	-298	-11.9
ANS1163	100	0.9783 ± 0.0030	-2248	-726	-29.0

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~500 pcm (percent mille) may not be accurate.

Table 5.10. Uniformly distributed void worth in all three fuel elements at beginning of cycle for the three-element baseline MCNP model (coolant channels above the elements were also voided)

Case	Void (%)	k_{eff}	Reactivity		Void worth (pcm/%)
			(pcm) ^a	$\Delta\rho$ (pcm) ^a	
ANS1108	0	1.0003 $\pm$ 0.0032	0	—	—
ANS1164	5	0.9949 $\pm$ 0.0027	543	-543	-108.6
ANS1165	10	0.9875 $\pm$ 0.0028	-1296	-753	-150.6
ANS1166	20	0.9787 $\pm$ 0.0027	-2206	-910	-91.0
ANS1167	50	0.9554 $\pm$ 0.0032	-4698	-2492	-83.1
ANS1168	75	0.9344 $\pm$ 0.0024	-7051	-2353	-94.1
ANS1169	100	0.9051 $\pm$ 0.0036	-10515	-3464	-138.6

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~ 500 pcm (percent mille) may not be accurate.

Fig. 5.7. Void reactivity worth in the lower fuel element at beginning of cycle.

Fig. 5.8. Void reactivity worth in all three fuel elements at beginning of cycle.

The results for the UFE are shown in Table 5.11 and for both fuel elements in Table 5.12. These results show that the worth of the bypass region alone (as observed from the 5 mm cases) is either nearly zero, or too small to be determined accurately with Monte Carlo methods. As expected, voiding along both fuel elements produces a larger negative reactivity than voiding along the upper element only. In general, the trend was for increasing negative reactivity insertion with increasing void region thickness, with some minor statistical fluctuations. These statistical fluctuations are caused by the small magnitude of the reactivity effects.

5.4.2 Coolant Level Drop Reactivity Worth

A series of MCNP calculations was run to determine the reactivity worth of a drop in the primary system coolant level and for a drop in the reflector coolant level. For the primary system cases, the coolant level in the entire primary system, including the central hole, was gradually lowered from the top of the vessel. The results from this series are shown in Tables 5.13 and 5.14 and for the primary system in Figs. 5.9 and 5.10. These show that, for small drops in the coolant level, the reactivity effects are small and generally negative. For larger coolant level drops, the reactivity effects become quite large. These results are quite similar to those for the two-element core design.

The first case in the reflector series, ANS1177, shows a small positive reactivity effect from the coolant level drop. Because of the statistics of the MCNP k_{eff} results, it is not ensured that this is truly a positive effect, which would be somewhat counter-intuitive. A more accurate statement is that this drop in reflector coolant level has almost no effect on the core reactivity.

5.4.3 Light Water Ingress Reactivity Worth

A series of MCNP calculations was run to determine the reactivity worth of a dilute light water ingress into the reflector. These results are shown in Table 5.15 and Figs. 5.11 and 5.12. As expected, even very low levels of light water contamination in the reflector have a significantly negative effect on the core reactivity, and this effect increases with increasing light water content. This effect is caused by the larger absorption cross section of hydrogen, which increases the neutron loss in the reflector.

5.5 BEAM TUBE STUDIES

A series of MCNP cases was run to examine six beam tube configurations. The first was the new baseline model, which has seven 100×100 mm cylindrical cross section horizontal beam tubes placed at the core midplane (ANS1051). These beam tubes had a 4-mm-wall thickness with a 2-mm-thick hemispherical endcap. The second case (ANS1052) was the old baseline beam tube design, 200×100 mm elliptical cross section tubes with a 14-mm-wall thickness and a 3-mm-thick cooling jacket. The third case was the same as ANS1051 with the seven horizontal beam tubes removed (ANS1053). The fourth case left the seven

Table 5.11. Reactivity worth of void region in the bypass channel and in the reflector along the UFEs at beginning of cycle for the three-element baseline MCNP model

Case	Reflector void thickness (mm)	k_{eff}	Reactivity		Differential worth (pcm/mm)
			(pcm) ^a	$\Delta\rho(\text{pcm})^a$	
ANS1108	0	1.0003 ± 0.0032	0	—	—
ANS1209	5	1.0003 ± 0.0028	0	0	0
ANS1210	10	0.9908 ± 0.0025	-959	-959	-192
ANS1211	15	0.9960 ± 0.0023	-432	+527	+105
ANS1212	20	0.9963 ± 0.0027	-401	+31	+6
ANS1213	25	0.9908 ± 0.0033	-959	-558	-112
ANS1214	30	0.9898 ± 0.0039	-1061	-102	-20

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~500 pcm (percent mille) may not be accurate.

Table 5.12. Reactivity worth of void region in the bypass channel and in the reflector along both upper and lower fuel elements at beginning of cycle for the three-element baseline MCNP model

Case	Reflector void thickness (mm)	k_{eff}	Reactivity		Differential worth (pcm/mm)
			(pcm) ^a	$\Delta\rho$ (pcm) ^a	
ANS1108	0	1.0003 $\pm$ 0.0032	0	—	—
ANS1209	5	1.9934 $\pm$ 0.0026	-694	-694	-139
ANS1210	10	0.9909 $\pm$ 0.0024	-948	-254	-51
ANS1211	15	0.9848 $\pm$ 0.0031	-1573	-625	+125
ANS1212	20	0.9787 $\pm$ 0.0029	-2206	-633	-127
ANS1213	25	0.9838 $\pm$ 0.0027	-1677	+529	+106
ANS1214	30	0.9804 $\pm$ 0.0027	-2029	-352	-70

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~ 500 pcm (percent mille) may not be accurate.

Table 5.13. Reactivity worth of drop in the primary system coolant level at beginning of cycle for the three-element baseline MCNP model

Case	Void (%)	k_{eff}	Reactivity		Void worth (pcm/%)
			(pcm) ^a	$\Delta\rho$ (pcm) ^a	
ANS1108	2523.27	1.0003 ± 0.0032	0	—	—
ANS1170	1634.	0.9999 ± 0.0030	-40	-40	-0.04
ANS1171	1259.	0.9976 ± 0.0030	-270	-230	-0.72
ANS1172	884.	0.9924 ± 0.0020	-796	-520	-1.39
ANS1173	687.	0.9918 ± 0.0036	-857	-61	-0.31
ANS1174	486.	0.9864 ± 0.0033	-1409	-552	-2.75
ANS1175	48.	0.9502 ± 0.0027	-5271	-3862	-8.82
ANS1176	-476.	0.8190 ± 0.0038	-22130	-16859	-32.17

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~500 pcm (percent mille) may not be accurate.

Table 5.14. Reactivity worth of drop in the reflector heavy water level at beginning of cycle for the three-element baseline MCNP model

Case	Void (%)	k_{eff}	Reactivity		Void worth (pcm/%)
			(pcm) ^a	$\Delta\rho$ (pcm) ^a	
ANS1108	2281.9	1.0003 ± 0.0032	0	—	—
ANS1177	1259.	1.0022 ± 0.0024	+190	+190	+0.19
ANS1178	413.5	0.9527 ± 0.0036	-4995	-5185	-6.13
ANS1179	-219.25	0.6943 ± 0.0036	-44060	-39065	-61.74
ANS1180	-2042.2	0.4997 ± 0.0047	-100150	-56090	-30.77

^aBecause of MCNP statistics, reactivities and changes in reactivity less than ~500 pcm (percent mille) may not be accurate.

Fig. 5.9. Reactivity worth of a drop in the primary coolant level at beginning of cycle.

Fig. 5.10. Differential worth of a drop in the primary coolant level at beginning of cycle.

Table 5.15. Reactivity worth of dilute light water ingress into the reflector at beginning of cycle for the three-element baseline MCNP model

Case	Molecular H ₂ O (%)	k _{eff}	Reactivity		Differential worth (pcm/%)
			(pcm) ^a	Δρ(pcm)	
ANS1108	0.2	1.0003 ± 0.0032	0	—	—
ANS1181	1.0	0.9828 ± 0.0029	-1780	-1780	-2225
ANS1182	2.5	0.9673 ± 0.0029	-3411	-1631	-1087
ANS1183	5.0	0.9375 ± 0.0031	-6697	-3286	-1314
ANS1184	10.0	0.9101 ± 0.0027	-9908	-3211	-642
ANS1185	25.0	0.8608 ± 0.0030	-16201	-6293	-420
ANS1186	50.0	0.8123 ± 0.0031	-23137	-6936	-277
ANS1187	100.0	0.7735 ± 0.0037	-29312	-6175	-124

^aPercent mille.

Fig. 5.11. Reactivity worth of a dilute light water ingress into the reflector at beginning of cycle.

Fig. 5.12. Differential worth of a dilute light water ingress into the reflector at beginning of cycle.

horizontal beam tubes in place but removed all other reflector components except the SSRs (ANS1054). The fifth case was the unperturbed case, with all reflector components and beam tubes removed, except for the SSRs (ANS1055). The final case was the same as the baseline design except that the through-tube was removed (ANS1056). For all cases, the peak reflector thermal flux, the flux and current at the entrance to the beam proper (just inside the hemispherical endcap), and the heat load in the endcap were tallied.

The results of these calculations are shown in Table 5.16 and clearly show the advantages of the 100×100 mm cylindrical beam tubes. The peak reflector and beam tube fluxes are larger, and the beam tube current per unit area is larger. The endcap heat load is slightly higher but is still significantly lower than the corresponding heat load for the two-element core design. Additionally, the reactivity effects of the 100×100 mm cylindrical beam tubes is nearly nonexistent compared to the 2% change introduced by the larger elliptical tubes. This prevents any large positive reactivity insertions caused by flooding, collapse, or destruction of the beam tubes. Finally, the thermal-to-fast flux ratio in the cylindrical beam tubes for the baseline case (ANS1051) was 98, which is well within the ANS reactor design criteria.

5.6 HEAT LOAD DISTRIBUTIONS

5.6.1 Thermal Power in the Primary System

An MCNP calculation to determine the relative and absolute power in the components and coolant of the primary coolant system was undertaken to provide the heat loads for input to the ANS RELAP5 model.¹⁴ Communications with personnel at ORNL indicated that only gross power determinations were desired for each component, so no axial segmentation was performed for the power tallies. The procedure followed is described in detail in Sect. 5.6.2. Results are shown in Table 5.17.

5.6.2 Heat Load Distributions in the Entire Reactor

The methods used for determination of the heat loads in the ANS design are well documented.¹⁵⁻¹⁹ As part of the three-element core analysis, heat load distributions were determined in all components of the primary and reflector systems at BOC, middle of cycle (MOC), and end of cycle (EOC). The results of these calculations are presented elsewhere and are not repeated here. A review of the methods, assumptions, and codes used is given in the following.

There are five significant components to the heat load in the ANS reactor: the prompt energy deposited from fission and fission neutron-induced reactions, denoted as the prompt neutron and photon component; the energy deposited from decay of the fission products, denoted as the fission product photon component and the fission product beta component; and the energy deposited from decay of the capture product ^{28}Al , denoted as the ^{28}Al decay beta component and the ^{28}Al beta decay photon component. Of these five components, only one, the fission product beta component, is limited to the fuel only. The others are distributed throughout the reactor, and require MCNP calculations to determine the spatial distribution.

**Table 5.16. Results of calculations for various beam tube configurations normalized to 330 MWF.
Cases ANS1053-ANS1056 use the 100 × 100 mm beam tube regions for tallies**

Case/description	k_{eff}	Peak reflector thermal flux ($\times 10^{19} \text{m}^{-2} \text{s}^{-1}$)	Average beam tube thermal flux ($\times 10^{19} \text{m}^{-2} \text{s}^{-1}$)	Average beam tube outward thermal current ($\times 10^{16} \text{s}^{-1}$)	Prompt heat load (W/g)
ANS1051 100 × 100 mm tubes	0.9929 ± 0.0024	5.3217 ± 2.08%	3.9397 ± 1.57%	8.2285 ± 1.79%	8.54
ANS1052 200 × 100 mm tubes	0.9806 ± 0.0025	4.9317 ± 1.98%	2.6662 ± 1.35%	11.7502 ± 1.47%	7.87
ANS1053 No tubes	0.9964 ± 0.0031	5.7904 ± 2.00%	4.9256 ± 1.75%	9.6709 ± 2.03%	N/A
ANS1054 No reflector components	1.0360 ± 0.0021	5.5562 ± 1.92%	4.0359 ± 1.54%	8.1597 ± 1.79%	7.91
ANS1055 Unperturbed	1.0425 ± 0.0017	5.4609 ± 2.09%	4.8293 ± 1.76%	9.5171 ± 2.01%	N/A
ANS1056 No through-tube	0.9958 ± 0.0021	5.3099 ± 1.91%	3.9177 ± 1.59%	8.1937 ± 1.82%	8.62

Table 5.17. Relative and absolute power deposited in the primary system coolant and structures at beginning of cycle

Component/description	Relative power	Absolute power (MW)
Outer fuel element	0.33917	112.130
Inner fuel element	0.13319	44.033
Middle fuel element	0.43521	143.882
Inner fuel element endplates and unheated zones	0.00080	0.264
Outer fuel element endplates and unheated zones	0.00140	0.462
Middle fuel element endplates and unheated zones	0.00140	0.463
Inner support tube	0.00072	0.238
Middle support tube	0.00039	0.129
Outer support tube	0.00050	0.166
Inner CPBT	0.00115	0.380
Outer CPBT	0.00391	1.291
Inner fuel element sideplates	0.00129	0.426
Outer fuel element sideplates	0.00258	0.852
Middle fuel element sideplates	0.00263	0.868
Central hole D ₂ O (inside inner support)	0.00327	1.081
Inner D ₂ O channel (between inner and middle support) (includes support structures)	0.00561	1.854
Middle D ₂ O channel (between middle and outer support) (includes support structures and targets)	0.00777	2.570
Outer D ₂ O channel (between outer support and ICPBT) (includes support structures)	0.00660	2.182
Core Bypass (between CPBT walls)	0.00093	0.306
Central control rods and structures	0.00406	1.342
Reflector vessel wall	0.00206	0.682
Reflector (D ₂ O + components)	0.04537	14.999
TOTAL	1.00000	330.600

A few assumptions are implicit in the heat load determinations. First, it is assumed that all beta decay energy associated with the beta particles is deposited locally, i.e., there is no significant electron transport through the reactor. This is not a major approximation, as the mean free path of electrons in the core is small, and little energy will be transported away from the fuel by this mechanism. Since the ^{28}Al beta decay reactions are well distributed, the transport would be a minor effect on the local heat loads and would result in reduced heat load in the components. This is a conservative assumption and thus acceptable.

Another assumption is that the only significant exothermic reaction resulting from decay of capture products is from the decay of ^{28}Al . The only exception to this is for the iridium targets in the VHs, which have the iridium decay included. This was done because a major energy deposition mechanism in iridium targets is from beta decay of the iridium capture products. This is a good assumption for a relatively clean core. However, after several cycles of exposure, activation products build up in the reactor structures, and the decay power of these activation products increases accordingly. Thus, after many cycles of exposure, this increase in decay power for the structures must be considered. However, for the conditions examined in this report (first fuel cycle), this is a minimal effect.

The remainder of this chapter explains in detail the calculational path for the heat load determinations.

5.6.2.1 Base Calculation

The base calculation is used to calculate three of the five components of the total heat load: the prompt neutron and photon, ^{28}Al decay beta, and fission product beta components. It also determines the spatial distribution of the fixed sources for the fission product photon and ^{28}Al beta decay photon components.

The base calculation is a coupled neutron-photon eigenvalue calculation. Tallies are taken in each component for the neutron and photon energy deposition (F6:N,P tally), the capture rate in all aluminum elements (F4:N tally), the iridium capture rate in the VH targets (F4:N tally), the fission rate in the fuel (F4:N tally), and the fission energy production in the fuel (F7:N tally).

Because all MCNP tallies are normalized per fission neutron, some normalization for these tallies is necessary. Each of the heat load components has a slightly different normalization factor, but each is based on the total fission neutron source in the reactor. This normalization factor is computed by the following formulation, which directly yields the normalization for the prompt neutron and photon component:

$$P_n = \frac{P \bar{\nu}}{Q k_{\text{eff}} C_Q} \quad (1)$$

where

- P = reactor power (W),
- $\bar{\nu}$ = average number of neutrons/fission,
- Q = 202.47 MeV/fission,
- k_{eff} = core eigenvalue,
- C_Q = 1.602×10^{13} J/MeV.

The recoverable energy released per fission, Q , is taken from the ENDF/B-V cross section files for ^{235}U (MF=1, MT=458). The division by the core eigenvalue is necessary to adjust the total fission source by the amount necessary to have a critical reactor. Equation (1) is used as the basis for all subsequent normalization factors for the other heat load components.

5.6.2.2 Fission Product Decay

The fission product decay components of the heat load required special treatment, as the information on the buildup and decay of fission products is not available in the MCNP calculation results. Thus, an outside code had to be used to provide these data; that code was the DKPOWR code from LANL. DKPOWR accepts fission rates in various fissile and fertile isotopes and computes fission product decay spectra, rates, and powers for desired times during the burnup and decay history. Other quantities, such as the average fission product decay photon energy per fission, can be derived from these output quantities. The DKPOWR code uses decay data from ENDF/B-V supplemented heavily with provisions of ANSI/ANS-5.1-1979, *American National Standard for Decay Heat Power in Light Water Reactors*.⁴

An obvious assumption is that these data for light water reactors are applicable to the ANS reactor, which is a heavy water system. Because the DKPOWR code calculates the decay powers from fission "pulse" functions and then integrates these functions over the input fission history, this assumption essentially is that there is little effect on the fission product yields from the reactor core spectrum. For thermal reactors in general, this is fairly true, as there is only about a 10% difference in the fission product yields between fission energies of 0.0253 eV and 500 keV.⁹ This suggests that DKPOWR is applicable to the ANS reactor without significant error.

The DKPOWR code evaluates the total reactor fission product decay power for both the fission product betas and photons. These results are used with the fission rate history to determine the average beta and photon decay energies. In practice, it is much simpler to use the fission energy production tally results to determine the fission product beta component. This involves dividing this quantity by the average energy released per fission used in the MCNP code. This gives the normalization factor for the fission product beta component as

$$P_{nFP\beta} = \frac{P_n \bar{E}_\beta}{\bar{E}_F}, \quad (2)$$

where

P_n = total fission neutron source from Eq. (1),

$\bar{E}_\beta$ = average beta energy/fission (MeV),

$\bar{E}_F$ = average energy released/fission (MeV),

which removes the uncertainty introduced by using the fuel density, a quantity which must be computed external to this process. This allows the normalization factor to remain relatively constant with changes in the core fuel grading. There is necessarily a unit conversion factor to convert the MeV/g from the MCNP tallies to W/g.

The fission energy production tally results are also weighted with the cell mass and normalized to unit integral to yield the spatial source for the fission product photon transport calculation. This spatial source, coupled with the fission product photon spectrum computed by DKPOWR, gives a complete definition of the fixed source for MCNP. This source is used in a fixed source mode photon-only calculation to perform the fission product photon transport and calculate the fission product photon heat load component for each reactor structural element. This uses the F6:P tally in MCNP. This tally, normalized to one source photon, is normalized by

$$P_{nFP} = \frac{P_n \gamma_{FP}}{\bar{\nu}} , \quad (3)$$

where

$$\begin{aligned} P_n &= \text{total fission neutron source from Eq. (1),} \\ \gamma_{FP} &= \text{average number of fission product photons/fission,} \\ \bar{\nu} &= \text{average number of neutrons/fission,} \end{aligned}$$

which is the total fission product photon source. A separate fission product photon spectrum, and accompanying average number of fission product photons per fission, was determined at BOC, MOC, and EOC to include the effects of the changing fission product inventory.

5.6.2.3 Aluminum-28 Beta Decay

The treatment of the ^{28}Al beta decay components is more straightforward. To compute the heat load component from ^{28}Al decay beta, the recoverable energy per decay is obtained from the ORIGEN2 decay libraries.⁵ This is then used to determine the normalization factor for the aluminum capture rate tally to produce the ^{28}Al decay beta heat load component. The normalization factor is given by

$$P_{n\beta} = \frac{P_n \cdot E_\beta}{\rho} , \quad (4)$$

where

$$\begin{aligned} P_n &= \text{total fission neutron source from Eq. (1),} \\ E_\beta &= \text{average beta energy/decay,} \\ \rho &= \text{density of aluminum (g/cm}^3\text{).} \end{aligned}$$

The aluminum density is needed because the normalized MCNP F4 tally results in a reaction rate, given in $\text{cm}^{-3} \text{ s}^{-1}$, which must be converted to specific heat load units of

MeV/g. There is also necessarily a unit conversion factor to convert the resulting MeV/s/g to W/g.

The ^{28}Al beta decay photon component is treated in a similar fashion to the fission product photon component. The aluminum capture rate tally is weighted with the cell volumes and then normalized to unit integral. This produces the spatial source for the MCNP fixed source photon-only transport calculation. The energy spectrum is simply a delta-function at an energy of 1.7787 MeV.²⁶ As in the fission product photon case, the heat load is calculated using the F6:P tally. This tally, normalized to one source photon, is normalized by

$$P_{n\beta\gamma} = P_n \sum_{\text{cells}} (F4 - V) , \quad (5)$$

where

- P_n = total fission neutron source from Eq. (1),
- $F4$ = aluminum capture rate tally results from base case,
- V = cell volume,

which is the total ^{28}Al beta decay photon source.

5.6.2.4 Additional Heat Load Contributions

The iridium/aluminum samples in the reflector isotope production facilities (VH-1 to VH-4) will generate extra heat in the samples because of beta decay of the capture products ^{194}Ir and ^{192}Ir . The contribution to the heat load was determined from an ORIGEN2.1 calculation. A constant flux irradiation was performed in the sample, with the total flux in the sample calculated by the base MCNP case. The heat load at 1 d was used to simulate near-BOC conditions for the BOC heat load determination, and the appropriate exposure time was used for the MOC and EOC calculations.

5.7 FUEL CYCLE DEPLETION

The methodology for ANS depletion calculations for a single fuel cycle employs the ORIGEN2 and MOCUP codes in addition to MCNP to provide exposure-dependent compositions at selected points in the cycle. Neutronics calculations are performed using MCNP at selected points through the irradiation cycle. Results obtained from MCNP include fluxes and neutron reaction rates for radiative capture, fission, (n,2n), and (n,3n) processes for user-selected nuclides in user-selected regions of the reactor model. Nuclide compositions in the same regions are calculated using the ORIGEN2 isotopic generation and depletion code. Initial compositions, neutron fluxes, and one-group spectrum-average cross sections for the previous reaction processes in the cells of interest are passed from MCNP to the ORIGEN2 calculations. Following an ORIGEN2 calculation for each region, new isotopic

compositions are passed back to MCNP for the next neutronics calculation. Automated data communication between the two codes is handled by the MOCUP code.⁵

The validity of results obtained using this methodology depends on a number of important modeling decisions. Significant MCNP-related issues include the frequency at which the MCNP transport calculations are performed during the fuel cycle, the number of discrete fuel and boron regions considered, and the allowable statistical uncertainties in the MCNP-calculated fluxes and reaction rates from which cross sections are determined. The most significant ORIGEN2-related issue is the number of time steps employed in each irradiation interval connecting subsequent MCNP calculations. Although the ORIGEN2 calculation includes a relatively complete set of 858 fission products, absorption is explicitly treated in the MCNP calculation for a much smaller number of nuclides.

The MCNP-ORIGEN2-MOCUP system was applied to the 17-d ANS cycle at 330 MW. The MCNP model described in this report was adapted for these calculations. The fuel elements were modeled using 48 homogeneous fuel regions in each element. Fuel densities in each region, averaged over the appropriate volumes, corresponded closely to regions of approximately constant fuel density. A single region was used to model each borated endplate.

The cycle was examined using MCNP transport calculations at 0 d (BOC), 1 d, 4.25 d, 8.5 d (MOC), 12.75 d, and 17 d (EOC). The SSRs were assumed to be parked with the bottom of the absorber 744 mm above the core midplane in all cases. The CCRs were positioned using ORNL VENTURE results¹² to maintain a critical configuration throughout the cycle. The CCRs were positioned at 52.2, 451.4, 402.7, 301.8, 425.3, and 530 mm above the core midplane, respectively. Depletion of ¹⁰B in the fuel element endplates was also explicitly modeled.

The ORIGEN2 calculations performed for each fuel region cover irradiation intervals of 1, 3.25, or 4.25 d. The irradiation intervals were modeled using 10, 13, and 17 ORIGEN2 time steps, respectively.

The top 50 fission product absorbers were determined based upon ORIGEN2 calculations for a 17-d ANS cycle at 330 MW. An ORIGEN2 fission product cross section library developed for the Advanced Test Reactor at INEL was used to establish this initial set. Although some sensitivity to reactor spectrum is anticipated, this approach provides a reasonable basis. These 50 fission products were tracked explicitly in the MCNP transport calculations at each time step.

Selected results of the ANS MOCUP depletion calculations are shown in Table 5.18 for the G1294 loading and in Table 5.19 for the G395 loading for the critical rod positions calculated in VENTURE. The most noticeable feature of these calculations is that the EOC core eigenvalue is 1.29% below critical with the control rods fully withdrawn. This implies that the G1294 loading is insufficient to produce the desired 17-d cycle length, either because of too little ²³⁵U loading or excessive boron residue. This inspired the creation of the G395 loading, which contains 31.0 kg of ²³⁵U. As the results show, this was a sufficient additions of fissile material. The remaining results shown are consistent with expectations and the ORNL VENTURE calculations.

Table 5.18 Results of ANS MOCUP depletion calculations for the G1294 fuel grading

	Time (d)					
	0.0	1.0	4.25	8.5	12.75	17.0
k_{eff}	0.9982	1.0012	0.9955	0.9908	0.9964	0.9871
^{235}U mass (kg)	27.600	27.177	25.812	24.067	22.345	20.659
^{10}B mass (g)	16.500	14.525	8.986	4.302	1.991	1.013
^{135}Xe mass (g)	0.000	0.389	0.401	0.383	0.357	0.311
^{149}Sm mass (g)	0.000	0.167	1.173	1.871	2.131	2.058
Control rod position (m from midplane)	0.0522	0.4514	0.4027	0.3018	0.4253	0.5300

Table 5.19 Results of ANS MOCUP depletion calculations for the G395 fuel grading

	Time (d)					
	0.0	1.0	4.25	8.5	12.75	17.0
k_{eff}	1.0005	1.0057	0.9977	0.9990	1.0014	1.0060
^{235}U mass (kg)	31.000	30.574	29.201	27.433	25.698	23.984
^{10}B mass (g)	16.500	14.709	9.391	4.852	2.415	1.308
^{135}Xe mass (g)	0.000	0.452	0.476	0.456	0.427	0.383
^{149}Sm mass (g)	0.000	0.178	1.312	2.165	2.511	2.520
Control rod position (m from midplane)	-0.0474	0.3309	0.2910	0.2533	0.3016	0.5120

6. UNRESOLVED ISSUES

This section describes some of the significant analyses not performed on the three-element conceptual design model that should be considered major goals for future work, if the ANS Project is resurrected.

6.1 LIGHT WATER INGRESS IN PRIMARY SYSTEM

Several cases were run to analyze the effects of a dilute light water ingress into the primary coolant system. These results are not presented here because much more study is needed before presentation, which time and funding levels did not permit. The ANS reactor design project should pursue this issue with great vigilance if the project is resurrected. Initial evidence suggests that it may be possible, at a fairly large penalty in performance, to cool the primary system with light water. It should be cautioned that these studies looked at BOC only and that these effects are likely to be quite different at EOC.

6.2 VOID WORTH IN BYPASS FLOW REGION

Although cases have been run with MCNP to determine the effect of voiding in the bypass region, the statistics involved in the reactivity worth calculation did not permit meaningful conclusions to be drawn. Future work should use either DORT or VENTURE to quantify this effect or use the recently updated KCORR modification to MCNP to make this analysis.

6.3 CALIFORNIUM AND EINSTEINIUM PRODUCTION

Because one of the base criteria for the ANS reactor design was to equal or better the californium and einsteinium production from the High Flux Isotope Reactor, a detailed analysis of the transplutonium isotope production rates is necessary for full characterization of the three-element core design. Plans had been made to perform this analysis at INEL using the MOCUP code system, and these calculations should be performed upon resurrection of the project.

6.4 REACTIVITY WORTHS THROUGH THE CYCLE

To complete the characterization of this core design, it is necessary to determine the reactivity worth of all components, the control and safety rod worth curves, and the total component worth at each stage of the fuel cycle. These MCNP calculations must be completed to verify fully the VENTURE/BURNER depletion results and to verify that the most limiting reactivity accidents can occur only at BOC.

6.5 FLUXES IN REACTOR THROUGH THE CYCLE

A full, detailed characterization of the flux in all component locations, similar to that performed for the two-element design, must be carried out for the three-element core design. This should include fluxes in the beam tubes at various locations along the beam path, as well as cold and hot source fluxes at the entrance to the guides.

7. REFERENCES

1. J. F. Briesmeister, Ed., *MCNP—A General Monte Carlo N-Particle Transport, Version 4a*, LA-12625-M, Los Alamos National Laboratory, Los Alamos, New Mexico, November 1993.
2. W. B. Wilson et al., *DKPOWR: A Code for Calculating Decay Power, Energy, Activity, and Beta and Gamma Spectra in LWR Fuel Using Fission Pulse Functions*, LA-UR-85-157, Los Alamos National Laboratory, Los Alamos, New Mexico, January 1985.
3. American Nuclear Society, *American National Standard for Decay Heat Power in Light Water Reactors*, ANSI/ANS-5.1-1979, August 1979.
4. A. G. Croff, *ORIGEN2.1—Isotope Generation and Depletion Code Matrix Exponential Method*, ORNL/TM-7175 (CCC-371), Martin Marietta Energy Systems, Inc., Oak Ridge National Laboratory, July 1980.
5. R. S. Babcock et al., *The MOCUP Interface: A Coupled Monte Carlo/Depletion System*, 1994 Topical Meeting on Advances in Reactor Physics, Knoxville, Tennessee, April 11–15, 1994, Vol. III, p. 368.
6. R. E. MacFarlane et al., *The NJOY Nuclear Data Processing System*, LA-9303-M(ENDF-324), Los Alamos National Laboratory, Los Alamos, New Mexico, May 1982.
7. R. Kinsey, *Data Formats and Procedures for the Evaluated Nuclear Data File, ENDF*, BNL-NCS-50496 (ENDF-102), 2nd ed. (ENDF/B-V), Brookhaven National Laboratory, Long Island, New York, October 1979.
8. R. J. Howerton et al., *The LLL Evaluated Nuclear Data Library (ENDL): Evaluation Techniques, Reaction Index, and Descriptions of Individual Reactions*, UCRL-50400, vol. 15, Part A, Lawrence Livermore National Laboratory, Livermore, California, September 1975.
9. P. F. Rose and C. L. Dunford, Ed., *Data Formats and Procedures for the Evaluated Nuclear Data File ENDF-6*, Rev. 1, BNL-NCS-44945 (ENDF-102), Brookhaven National Laboratory, Long Island, New York, October 1991.
10. Liu Tingjin et. al., “CENDL-2, Chinese Evaluated Nuclear Data Library, Version 2,” *Proceedings of the International Conference on Nuclear Data for Science and Technology*, Julich, Germany, May 1991, p. 804.

11. *ANS Conceptual Design Drawings*, ORNL/ANS/INT-26/S10/R0, Martin Marietta Energy Systems, Inc., Oak Ridge National Laboratory, June 1992.
12. D. R. Vondy et al., *VENTURE: A Code Block for Solving Multigroup Neutronics Problems Applying the Finite-Difference Diffusion-Theory Approximation to the Neutron Transport, Version III*, ORNL-5062/R1, Martin Marietta Energy Systems, Inc., Oak Ridge National Laboratory, November 1977.
13. *Advanced Neutron Source Conceptual Safety Analysis Report*, ORNL/ANS/INT-33/V1, Martin Marietta Energy Systems, Inc., Oak Ridge National Laboratory, June 1992.
14. V. H. Ransom et. al., *RELAP5/MOD2 Code Manual*, NUREG/CR-4312, EGG-2396, Rev. 1, Idaho National Engineering Laboratory, Idaho Falls, Idaho, March 1987.
15. C. A. Wemple and S. N. Jahshan, "Tracking the Energy Deposition Processes in a Reactor Using MCNP," *Trans. Am. Nucl. Soc.* **64**, 574 (1991).
16. C. A. Wemple, *Detailed Heat Load Calculations for the Conceptual Design of the Advanced Neutron Source Reactor*, ORNL/M-3207, Martin Marietta Energy Systems, Inc., Oak Ridge National Laboratory, December 1993.
17. C. A. Wemple, *Detailed Heat Load Calculations at the Beginning, Middle, and End of Cycle for the Conceptual Design of the Advanced Neutron Source Reactor*, ORNL/M-3993, Martin Marietta Energy Systems, Inc., Oak Ridge National Laboratory, February 1995.
18. C. A. Wemple, *Detailed Heat Load Calculations for the Three-Element Core Design of the Advanced Neutron Source Reactor* (draft), Martin Marietta Energy Systems, Inc., Oak Ridge National Laboratory.
19. J. C. Gehin et. al., *Reactor Physics Methods, Models, and Applications Used to Support the Conceptual Design of the Advanced Neutron Source* (draft), ORNL/TM-12996, Martin Marietta Energy Systems, Inc., Oak Ridge National Laboratory.
20. *Chart of the Nuclides*, 13th ed., GET-6504, General Electric Company, 1984.

Internal Distribution

1. B. R. Appleton	13. B. A. Worley
2. F. X. Gallmeier	14. ORNL Patent Office
3. J. C. Gehin	15. Central Research Library,
4. D. T. Ingersoll	Document Reference Section
5-8. R. L. Johnson	16. Y-12 Technical Library
9. R. A. Lillie	17-18. Laboratory Records
10-11. D. L. Selby	19. Laboratory Records (RC)
12. C. D. West	

External Distribution

20. J. A. Lake, Manager, Nuclear Engineering and Reactor Design, Idaho National Engineering Laboratory, P.O. Box 1625, Idaho Falls, ID 83415.
21. R. C. Little, Los Alamos National Laboratory, Group X6, P.O. Box 1663, Los Alamos, NM 87545.
- 22-31. J. M. Ryskamp, Idaho National Engineering Laboratory, P.O. Box 1625, Idaho Falls, ID 83415-3885.
32. B. G. Schnitzler, Idaho National Engineering Laboratory, P.O. Box 1625, Idaho Falls, ID 83415
33. U.S. Department of Energy, ANS Project Office, Oak Ridge Operations Office, FEDC, MS-8218, P.O. Box 2009, Oak Ridge, TN 37831-8218.
34. C. A. Wemple, Idaho National Engineering Laboratory, P.O. Box 1625, Idaho Falls, ID 83415.
- 35-36. Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831.