Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

EARTH SCIENCES DIVISION

Estimation of Hydrologic Properties of Heterogeneous Geologic Media with an Inverse Method Based on Iterated Function Systems

C. Doughty
(Ph.D. Thesis)

December 1995

RECEIVED
FEB 15 1996
OSTI

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor The Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or The Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof, or The Regents of the University of California.

Ernest Orlando Lawrence Berkeley National Laboratory
is an equal opportunity employer.

LBL-38136
UC-403

**ESTIMATION OF HYDROLOGIC PROPERTIES OF HETEROGENEOUS
GEOLOGIC MEDIA WITH AN INVERSE METHOD
BASED ON ITERATED FUNCTION SYSTEMS**

CHRISTINE DOUGHTY
Ph.D. Thesis

DEPARTMENT OF MATERIALS SCIENCE AND MINERAL ENGINEERING
University of California

and

EARTH SCIENCES DIVISION
Lawrence Berkeley National Laboratory
University of California
Berkeley, CA 94720

DECEMBER 1995

This work was supported by the Director, Office of Energy Research, Office of Health and Environmental Research, Subsurface Science Program, and by the Assistant Secretary for Fossil Energy, Office of Oil, Gas and Shale Technologies, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED
D C

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

Estimation of Hydrologic Properties of Heterogeneous Geologic Media
with an Inverse Method Based on Iterated Function Systems

by

Christine Allison Doughty

B.S. (University of California, Berkeley) 1978

M.S. (University of California, Berkeley) 1991

A dissertation submitted in partial satisfaction of the

requirements for the degree of

Doctor of Philosophy

in

Engineering – Material Science
and Mineral Engineering

in the

GRADUATE DIVISION

of the

UNIVERSITY OF CALIFORNIA, BERKELEY

Committee in charge:

Professor Paul A. Witherspoon, Chair

Professor Neville G. W. Cook

Professor William E. Dietrich

Dr. Jane C. S. Long

1995

Abstract

Estimation of Hydrologic Properties of Heterogeneous Geologic Media with an Inverse Method Based on Iterated Function Systems

by

Christine Allison Doughty

Doctor of Philosophy in Engineering

University of California, Berkeley

Professor Paul A. Witherspoon, Chair

The hydrologic properties of heterogeneous geologic media are estimated by simultaneously inverting multiple observations from well-test data. A set of pressure transients observed during one or more interference tests is compared to the corresponding values obtained by numerically simulating the tests using a mathematical model. The parameters of the mathematical model are varied and the simulation repeated until a satisfactory match to the observed pressure transients is obtained, at which point the model parameters are accepted as providing a possible representation of the hydrologic property distribution.

Restricting the search to parameters that represent fractal hydrologic property distributions can improve the inversion process. Far fewer parameters are needed to describe heterogeneity with a fractal geometry, improving the efficiency and robustness of the inversion. Additionally, each parameter set produces a hydrologic property distribution with a hierarchical structure, which mimics the multiple scales of heterogeneity often seen in natural geological media.

The fractal hydrologic property distributions are created using iterated function systems (IFS's), which generate a fractal set known as an attractor. The attractor is then mapped to a distribution of transmissivity and storativity in the mathematical model used to simulate the well test. During the inversion, the parameters of the IFS are varied, thus enabling different hydrologic property distributions to be tested. In contrast to traditional inverse methods, which search for the hydrologic property distribution directly (typically 100's to 1000's of unknown parameters), the IFS inverse method searches only for the parameters of the IFS (typically 10's of unknown parameters).

Application of the IFS inverse method to synthetic interference-test data shows that the method reproduces the synthetic heterogeneity successfully for idealized heterogeneities, for

geologically-realistic heterogeneities, and when the pressure data includes noise. Application to field data from an interference test conducted in a shallow aquifer within a sand/clay sedimentary sequence at Kesterson Reservoir agrees well with an independent analysis using traditional well-test analysis methods. Application to a series of interference tests conducted in a fluvial sedimentary formation consisting of several permeable layers at the Gypsy Pilot Site produces a detailed picture of the subsurface, which compares favorably with cross-well seismic imaging studies.

TABLE OF CONTENTS

List of Figures	vi
List of Tables	xv
Notation	xvi
Acknowledgement	xvii
1. INTRODUCTION	1
1.1 MOTIVATION	1
1.2 ALTERNATIVE APPROACHES FOR DEVELOPING HYDROLOGIC MODELS	2
1.2.1 Forward Versus Inverse Models	2
1.2.2 The Use of a Forward Model in an Inverse Method	3
1.2.3 Approaches to Inverse Modeling	4
1.2.4 Addressing Non-Uniqueness	6
1.3 OVERVIEW OF THE PRESENT APPROACH	7
1.3.1 Creation of Trial Hydrologic Property Distributions as Fractals	8
1.3.2 Comparison to Other Uses of Fractal Concepts in Subsurface Heterogeneity	9
Characterization	
2. BASICS OF ITERATED FUNCTION SYSTEMS	10
2.1 MATHEMATICAL FOUNDATION	10
2.2 VARIATION OF THE ATTRACTOR WITH THE PARAMETERS OF THE IFS	15
3. USINGS IFS'S IN A HYDROLOGIC INVERSION	25
3.1 MAPPING THE ATTRACTOR TO A HYDROLOGIC PROPERTY DISTRIBUTION	25
3.1.1 The Step Map	27
3.1.2 The Distributed Map	29
3.1.3 The Plus-Minus Algorithm	30
3.1.4 Other Possible Mappings	30
3.2 THE OBJECTIVE FUNCTION	31
3.2.1 Constructing the Objective Function to be Sensitive to Heterogeneities	31
3.2.2 Determining Base Values of Hydrologic Properties by Curve Shifting	33
3.2.3 Determining Base Value of Diffusivity by Optimization	34
3.3 THE OPTIMIZATION ALGORITHM	35
3.3.1 Optimization Algorithms Considered	35
3.3.2 Assessing Optimization Algorithms with Synthetic Energy Surfaces	36
3.3.3 Visualization of the Energy Surface for a Simple Heterogeneity	49
3.4 INTERPRETATION OF RESULTS	49
3.4.1 Alternate Displays of Hydrologic Property Distributions	49
3.4.2 Analyzing an Ensemble of Solutions	51
3.5 CONSTRAINING THE INVERSION WITH GEOLOGICAL OR OTHER INFORMATION	55
4. INVERSION OF SYNTHETIC DATA	57
4.1 LINEAR HIGH-TRANSMISSIVITY FEATURE	57
4.1.1 Inversions with Four Unknown Parameters	59
4.1.2 Inversions with Twelve Unknown Parameters	62
4.2 SQUARE ZONE OF CONTRASTING TRANSMISSIVITY AND STORATIVITY	68
4.2.1 High T and S Anomaly	70
4.2.2 Low T and S Anomaly	77

4.2.3 Alternate Well Locations	79
4.3 GEOLOGICALLY REALISTIC HETEROGENEITIES	81
4.3.1 Introduction	81
4.3.2 Creation of Realistic Synthetic Data	81
4.3.3 Inversion of Realistic Synthetic Data	91
4.3.4 Conclusions from Realistic Synthetic Data Inversion	92
4.4 NOISY SYNTHETIC DATA	100
4.4.1 Random Noise	100
4.4.2 Systematic Noise	108
4.5 CONCLUSIONS OF SYNTHETIC-DATA ANALYSIS	108
5. INVERSION OF KESTERSON DATA	109
5.1 INTRODUCTION TO THE INVERSION OF REAL DATA	109
5.2 THE KESTERSON RESERVOIR SITE	109
5.3 QUASI-THREE-DIMENSIONAL ANALYSIS OF AN INTERFERENCE TEST	110
5.4 COMPARISON WITH PREVIOUS ANALYSIS	116
5.5 POTENTIAL FURTHER STUDIES AT KESTERSON	116
6 INVERSION OF GYPSY PILOT-SITE DATA	118
6.1 INTRODUCTION	118
6.1.1 Gypsy Sites and Data	118
6.1.2 Pilot-Site Well Log Interpretation	122
6.1.3 Pilot-Site Well Tests	122
6.2 REVIEW AND ASSESSMENT OF WELL-TEST DATA	124
6.2.1 Matrix Display of Well-Test Results	124
6.2.2 Assessment of Existing Data and Analyses	132
6.2.3 Strategy for Inversion	133
6.3 LOWER SAND CHANNEL ANALYSES	134
6.3.1 Conceptual and Numerical Model	134
6.3.2 Homogeneous-Medium Simulations	134
6.3.3 Single-Test Inversions of Test 90/S4/T1	143
6.3.4 Single-Test Inversions of Test 90/S3/T1	147
6.3.5 Multiple-Test Co-Inversions of Tests 90/S3/T1 and 90/S4/T1	152
6.3.6 Cross-Validation Studies	161
6.4 UPPER AND MIDDLE SAND CHANNEL ANALYSES	165
6.4.1 Conceptual and Numerical Model	165
6.4.2 Assessment of Upper and Middle Sand Channel Well-Test Data	168
6.4.3 Single-Test Inversions of Test 90/S1/T2	170
6.4.4 Single-Test Inversions of Test 90/S2/T2	175
6.4.5 Single-Test Inversions of Test 90/S2/T3	179
6.4.6 Single-Test Inversions of Test 90/S3/T2	182
6.4.7 Single-Test Inversions of Test 90/S4/T2	182
6.4.8 Multiple-Test Co-Inversions of Tests 90/S1/T2, 90/S2/T2, and 90/S3/T2	183
6.4.9 Incorporating Well-Log Lithology in Well-Test Analysis	192
6.4.10 Building a Three-Dimensional Model with Sequential Two-Dimensional Inversions	198
6.4.11 Cross-Validation Studies	204
6.5 COMPARISON OF HYDROLOGIC INVERSION WITH CROSS-WELL SEISMIC IMAGING	207
6.5.1 Overview of Cross-Well Seismic Data	207

6.5.2 First Arrival-Time Inversions	208
6.5.3 Reflection Studies	212
6.5.4 Guided Wave Analyses	212
6.6 COMPARISON WITH TRADITIONAL GEOSTATISTICAL ANALYSIS	215
6.6.1 Introduction	215
6.6.2 Estimation of Variograms	215
6.6.3 Generation of Transmissivity Distribution	216
6.6.4 Simulation of Well Tests	224
6.6.5 Conclusions from Traditional Analysis Comparison	226
6.7 CONCLUSIONS OF GYPSY ANALYSES	231
7. SUMMARY, CONCLUSIONS, AND FUTURE WORK	234
7.1 SUMMARY	234
7.1.1 Development of the IFS Inverse Method	234
7.1.2 Application of the IFS Inverse Method	234
7.2 CONCLUSIONS	235
7.2.1 The Value of Hydrologic Inversion	235
7.2.2 Advantages of a Fractal Approach to Hydrologic Inversion	236
7.2.3 Limitations of a Fractal Approach to Hydrologic Inversion	237
7.3 FUTURE WORK	237
7.3.1 Further Development of the IFS Inverse Method	237
7.3.2 Further Applications of the IFS Inversion Method	238
REFERENCES	243
APPENDIX A: THE NUMERICAL MODEL TRINET	246
A.1 BASIC FORMULATION	246
A.2 TWO-DIMENSIONAL POROUS MEDIUM (CONFINED AQUIFER)	247
A.3 QUASI THREE-DIMENSIONAL POROUS MEDIUM (LEAKY AQUIFER)	252
A.4 USE OF TRINET FOR HIGHLY HETEROGENEOUS MEDIA	256

LIST OF FIGURES

Figure 2.1	The effect of various affine transforms on a set of points.	12
Figure 2.2	Generation of Sierpinski's gasket using an IFS with $k = 3$ and a set A_0 forming a cross.	13
Figure 2.3	Generation of an attractor using an IFS with $k = 4$ and a set A_0 consisting of a single point.	14
Figure 2.4	A sequence of attractors generated by IFS's with $k = 3$ whose parameters differ by a small amount. For the m th frame, $\mathbf{P}_m = \mathbf{P}_{m-1} + \Delta\mathbf{P}$, where $\Delta\mathbf{P}$ is a vector with random increments and $ \Delta\mathbf{P} = 0.2$.	16
Figure 2.5	The variation in attractor as parameters of the IFS change. For the m th frame in each series, $\mathbf{P}_m = \mathbf{P}_1 + \Delta\mathbf{P}_m$, where $\Delta\mathbf{P}_m$ is a vector with random increments.	18
Figure 2.6	The variation in attractor as parameters of the IFS change, using the rotation-matrix form for $\mathbf{B}$, Equation (2.12). For the m th frame $\mathbf{P}_m = \mathbf{P}_1 + \Delta\mathbf{P}_m$, where $\Delta\mathbf{P}_m$ is a vector with random increments and $ \Delta\mathbf{P}_m = 0.4$.	22
Figure 3.1	The equivalence between the TRINET lattice and a block model. The black lines show the one-dimensional finite elements comprising the TRINET lattice; head is calculated at the nodal points (black dots). The dashed lines show block boundaries in the equivalent block model, in which block center locations correspond to TRINET nodal points.	26
Figure 3.2	Schematic diagram of the mapping from attractor points to lattice element hydrologic properties. In the frame at the right, element thickness is proportional to transmissivity.	27
Figure 3.3	Example of the mapping from attractor points to transmissivity distribution: a) the attractor superposed on the lattice; b) the transmissivity distribution for the step map, c) and d) the transmissivity distribution for the distributed map with $s = 0.025$ and $s = 0.05$, respectively. In frames b-d, element thickness is proportional to T/T_0 . The solid circles mark the well locations for synthetic problem 1.	28
Figure 3.4	Energy surface for a two-dimensional polynomial objective function.	38
Figure 3.5	The search for a minimum of the objective function using the direction set method. The grey point is the starting point for the search and the black point is the final point. Points connected by lines are accepted points.	39
Figure 3.6	The search for a minimum of the objective function using the downhill simplex method. The grey points are the starting points for the search and the black point is the final point. Points connected by lines are accepted points.	42
Figure 3.7	The search for a minimum of the objective function using simulated annealing. The grey point is the starting point for the search and the black point is the final point. Points connected by lines are accepted points.	45
Figure 3.8	The search for a minimum of the objective function using simplex annealing. The grey points are the starting points for the search and the black point is the final point. Points connected by lines are accepted points.	47

Figure 3.9	Several of the trial transmissivity distributions for an $n = 2$ dimensional inversion (solid line segments), and the correct transmissivity distribution (dashed line segment). The black dots show the well locations. The (x,y) coordinates of the moving end of the line segment are determined by the two unknown parameters of the inversion.	50
Figure 3.10	The energy surface created by varying the location of one end of the high-transmissivity feature over the entire region shown in Figure 3.9. The white dots show the locations in parameter space where the end point of the high-transmissivity feature coincides with a well. The black dot shows the location in parameter space which produces the correct transmissivity distribution (the dashed line in Figure 3.9).	51
Figure 3.11	Various ways to represent the results of an inversion. a) the attractor itself, a set of points (in this image blue points increase transmissivity and red points decrease transmissivity); b) TRINET lattice with element thickness proportional to transmissivity; and c) color-coded plot of transmissivity distribution.	52
Figure 3.12	Illustration of the algorithm used to construct the grey-scale image of transmissivity distribution. a) a lattice with just a few diamonds drawn; b) a lattice with all the diamonds representing elements drawn, the remaining gaps will be filled in by averaging adjacent transmissivity values.	53
Figure 4.1	Transient drawdowns at the four observation wells for synthetic problem 1. The arrangement of the plots on the page follows the locations of the observation wells in the well field.	58
Figure 4.2	The final attractors for six inversions of synthetic problem 1, using IFS's with $k = 2$ with only the b terms of the affine transforms varying. Well locations are marked with open circles.	60
Figure 4.3	Energy variation during the inversion for Case 1E. The minimum energy so far is shown as a dotted line in both frames.	61
Figure 4.4	The final attractors for six inversions of synthetic problem 1, using IFS's with $k = 2$ with all parameters of the affine transforms varying.	63
Figure 4.5	A schematic diagram showing the regions of an aquifer in which heterogeneities tend to have the most affect on well-test results; these are the regions directly between pumping wells and observation wells.	64
Figure 4.6	The transmissivity distributions for the six inversions of synthetic problem 1 which used twelve unknown parameters. Element thickness is proportional to T/T_0 .	66
Figure 4.7	The mean and standard deviation of the transmissivity distribution for the six distributions shown in Figure 4.6, and for 30 inversions all using the same parameters, but different random seeds. Element thickness is proportional to T/T_0 .	67
Figure 4.8	Model for synthetic problem 2, showing the lattice, well locations (solid circles), and the central square anomaly, which may have transmissivity and storativity either 100 times greater or 100 times less than the background values. The pumping well is the middle well on the left.	68

Figure 4.9	Synthetic data at the five observation wells for synthetic problem 2, compared to the response for a uniform medium. The arrangement of the plots on the page follows the locations of the observation wells in the well field.	69
Figure 4.10	The initial attractor for the $k = 3$ inversions of synthetic problem 2.	71
Figure 4.11	Transient drawdowns for synthetic problem 2 with the high anomaly when attractor points increase properties.	72
Figure 4.12	The final attractors for three $k = 3$ inversions of synthetic problem 2 with the high anomaly, when attractor points increase properties.	73
Figure 4.13	The final attractors for three $k = 3$ inversions of synthetic problem 2 with the high anomaly, when attractor points decrease properties.	73
Figure 4.14	The final attractors for two $k = 4$ inversions of synthetic problem 2 with the high anomaly, when attractor points decrease properties.	74
Figure 4.15	Transient drawdowns for synthetic problem 2 with the high anomaly when attractor points decrease properties.	75
Figure 4.16	The final attractor for a $k = 4$ inversion of synthetic problem 2 with the high anomaly, using the plus-minus algorithm. Attractor points which increase transmissivity and storativity are shown as pluses and points which decrease properties are shown as open circles. Only one quarter of the attractor points used are plotted (256 out of 1024), in order for the symbols to be more readily distinguishable.	76
Figure 4.17	Transient drawdowns for synthetic problem 2 with the low anomaly when attractor points decrease properties.	78
Figure 4.18	The final attractors for three $k = 3$ inversions of synthetic problem 2 with the low anomaly, when attractor points decrease properties.	79
Figure 4.19	The well locations used for the inversions of synthetic problem 2 that are summarized in Table 4.4.	80
Figure 4.20	Perspective view of the original Gypsy outcrop-site channel model. The channels and other lithofacies are identified by color.	82
Figure 4.21	Vertical cross-sections through the original Gypsy outcrop-site channel model. The vertical to horizontal scale ratio is 2:1. The vertical bars on the upper cross-section identify the locations at which core measurements of permeability were made. From bottom to top, the bars correspond to $y = 0, 5$, and 32 m ($0, 16$, and 105 feet), where y is the distance perpendicular to the cross-section.	83
Figure 4.22	Vertical cross-sections through the new lower-resolution Gypsy outcrop-site channel model. The vertical to horizontal scale ratio is 2:1. The arrows identify the elevations of the two single-layer models used to create synthetic well-test data.	85
Figure 4.23	Lithofacies proportions of channel fill deposits at the Gypsy outcrop site, calculated from core descriptions and road-cut profiles [after Doyle and Sweet, 1992]. See Table 4.5 for the meaning of the abbreviated lithofacies names given here.	86
Figure 4.24	Channel models for $z = 47$ feet and $z = 23$ feet. The vertical bars separate the real blocks from the added dummy blocks.	87
Figure 4.25	Lithofacies models for $z = 47$ feet and $z = 23$ feet, derived from the channel models shown in Figure 4.24. The vertical bars separate the real blocks from the added dummy blocks.	89

Figure 4.26	Transmissivity distributions for $z = 47$ feet and $z = 23$ feet, derived from the lithofacies models shown in Figure 4.25. This range of $\ln T$ (for T in m^2/s) corresponds to $\ln k$ between -8.6 and $+8.4$, for k in millidarcies.	90
Figure 4.27	Synthetic well-test data created using the models shown in Figure 4.26. (dots) and a uniform-medium model (lines). The arrangement of plots on the page mimics the well field layout shown in Figure 4.26.	93
Figure 4.28	Three transmissivity distributions returned by inversions of the $z = 23$ well-test data.	95
Figure 4.29	Pressure transients for one of the inversions of the $z = 23$ well-test data. The arrangement of plots on the page mimics the well field layout shown in Figure 4.26.	96
Figure 4.30	Three transmissivity distributions returned by inversions of the $z = 47$ well-test data, which used the step map.	97
Figure 4.31	Three transmissivity distributions returned by inversions of the $z = 47$ well-test data, which used the distributed map.	98
Figure 4.32	Pressure transients for one of the inversions of the $z = 47$ well-test data. The arrangement of plots on the page mimics the well field layout shown in Figure 4.26.	99
Figure 4.33	Pressure transients for noisy synthetic data, with $\sigma = 0.1$. The arrangement of plots on the page follows the locations of observations wells in the well field.	101
Figure 4.34	Pressure transients for noisy synthetic data, with $\sigma = 1$.	102
Figure 4.35	Pressure transients for noisy synthetic data, with $\sigma = 5$.	103
Figure 4.36	Pressure transients for noisy synthetic data, with $\sigma = 10$.	104
Figure 4.37	Pressure transients for noisy synthetic data, with $\sigma = 100$.	105
Figure 4.38	Attractors returned by the inversions of noisy pressure-transient data for the linear high-transmissivity feature. The mean attractor for each case is shown as a dashed line.	106
Figure 5.1	The nested TRINET lattice used for the Kesterson inversion. Frame (a) shows the central portion of the lattice; the pumping well is at $x = 0, y = 0$, the locations of the observation wells are shown as solid circles. Frame (b) shows the entire lattice; head is held constant at $x = \pm 600, y = \pm 600$.	111
Figure 5.2	Observed and calculated transient drawdowns for Kesterson. The arrangement of the plots on the page follows the locations of the observation wells in the well field.	113
Figure 5.3	Results of three decreased-transmissivity inversions for Kesterson: top row – the final attractor for each case; middle row – the TRINET lattice plotted with element thickness proportional to transmissivity; bottom row – a grey-scale plot of effective aquifer transmissivity $\bar{T}$. The minimum transmissivity level shown is $T_0/100$, although several elements have even lower T values.	115
Figure 5.4	The final attractors for the increased-transmissivity inversions for Kesterson.	116
Figure 6.1	Orthophotograph of the main Gypsy outcrop and illustration of the geological mapping used to analyze it.	119
Figure 6.2	Plan view of the Gypsy outcrop-site borehole array.	120

Figure 6.3	Gypsy pilot-site well field layout.	121
Figure 6.4	Cross-sections through the Gypsy formation at the subsurface pilot site, showing simplified lithologies as inferred from well logs and core studies. The dark bands indicate clay or shale and the remainder is sand. The horizontal bars mark the upper limit of the logged interval.	123
Figure 6.5	Schematic illustration of the Gypsy pilot-site well tests conducted in 1989 and 1990, and the screened intervals (shown as black bars) in the wells.	125
Figure 6.6	Matrix display summarizing hydrologic tests done at the Gypsy subsurface pilot site. Entries grouped by well.	127
Figure 6.7	Matrix display summarizing hydrologic tests done at the Gypsy subsurface pilot site. Entries grouped by sand channel.	128
Figure 6.8	Matrix display summarizing hydrologic tests done at the Gypsy subsurface pilot site. Entries grouped by sand channel, contradictory entries removed.	130
Figure 6.9	The lattice used for the numerical model of the lower sand channel at the Gypsy subsurface pilot site. The wells are shown as open circles.	135
Figure 6.10	The Gypsy pilot-site well field showing a schematic view of the lower sand channel well tests. The shaded lines connect the observation and pumping wells for a given test.	136
Figure 6.11	The observed and modeled observation-well drawdowns for test 90/S4/T1. The model consists of a uniform medium with T_0 and S_0 values that minimize the energy for test 90/S4/T1.	138
Figure 6.12	The observed and modeled observation-well drawdowns for test 90/S3/T1. Same uniform-medium model as in Figure 6.11.	139
Figure 6.13	The observed and modeled observation-well drawdowns for test 90/S1/T1. Same uniform-medium model as in Figure 6.11.	140
Figure 6.14	The observed and modeled observation-well drawdowns for test 89/S2/T2. Same uniform-medium model as in Figure 6.11.	141
Figure 6.15	The observed and modeled observation-well drawdowns for test 89/S1/T1. Same uniform-medium model as in Figure 6.11.	142
Figure 6.16	The returned transmissivity distribution for test 90/S4/T1. The upper frame shows the attractor returned by the inversion. The lower frame shows a grey-scale map of transmissivity with darker shades corresponding to higher transmissivity.	144
Figure 6.17	The observed and modeled observation-well drawdowns for test 90/S4/T1, corresponding to the transmissivity distribution shown in Figure 6.16.	145
Figure 6.18	Grey-scale transmissivity distributions for eight inversions of test 90/S4/T1. Darker shades correspond to higher transmissivity.	146
Figure 6.19	Energy decrease during the inversion of test 90/S3/T1. The open circles mark the points at which background-diffusivity optimizations were done.	148
Figure 6.20	The observed and modeled observation-well drawdowns for test 90/S3/T1.	149

Figure 6.21	The returned transmissivity distribution for test 90/S3/T1. The upper frame shows the attractor returned by the inversion (horizontal dashes identify attractor points that decrease transmissivity and vertical dashes identify attractor points that increase transmissivity). The lower frame shows a grey-scale map of transmissivity with darker shades corresponding to higher transmissivity.	150
Figure 6.22	Transmissivity distributions for four other inversions of test 90/S3/T1.	151
Figure 6.23	Observed drawdowns for the co-inversion of tests 90/S3/T1 and 90/S4/T1. Calculated drawdowns are reset to zero at 11.5 hours.	153
Figure 6.24	The observed and modeled drawdowns for a co-inversion of tests 90/S3/T1 and 90/S4/T1 using an IFS with $k = 4$ affine transforms.	154
Figure 6.25	Transmissivity distribution returned by a co-inversion of tests 90/S3/T1 and 90/S4/T1 using an IFS with $k = 4$ affine transforms.	155
Figure 6.26	Attractors for a co-inversion of tests 90/S3/T1 and 90/S4/T1 using an IFS with $k = 6$ affine transforms. The upper frame shows an intermediate result after allowing limited variability of attractors during the first stage of the inversion, and the lower frame shows the final attractor. Horizontal dashes identify attractor points that decrease transmissivity and vertical dashes identify attractor points that increase transmissivity.	157
Figure 6.27	Drawdown versus time plots corresponding to the final attractor shown in Figure 6.26.	158
Figure 6.28	Grey-scale plot of the transmissivity distribution corresponding to the final attractor shown in Figure 6.26. Darker shades correspond to higher transmissivity.	159
Figure 6.29	Transmissivity distributions inferred from additional co-inversions of tests 90/S3/T1 and 90/S4/T1. Darker shades correspond to higher transmissivity.	160
Figure 6.30	Transmissivity distribution inferred from the co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1.	163
Figure 6.31	A portion of the pressure transients for the co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1.	164
Figure 6.32	Conceptual model of the Gypsy pilot site. Each horizontal layer represents a sand channel. The lack of communication between the middle and lower sand channels is represented by no elements connecting these two layers. The partial hydrologic communication between the upper and middle sand channels is represented by some vertical connections.	165
Figure 6.33	Lithologic information on the location of the upper clay layer, and possible inversion schemes.	166
Figure 6.34	Central portion of one layer of the lattice used to model the upper and middle sand channels. Each layer of the lattice extends a total of 2400 m in the x and y directions, with steadily increasing lattice spacing.	167
Figure 6.35	The Gypsy pilot-site well field showing a schematic view of the upper and middle sand channel well tests. The shaded lines connect the observation and pumping wells for a given test.	169
Figure 6.36	Observed and modeled pressure transients for one inversion of test 90/S1/T2.	171

Figure 6.37	Final attractor for one inversion of test 90/S1/T2. Attractor points identify locations of high permeability in the intermediate layer between the upper and middle sand channels.	172
Figure 6.38	Permeability distribution corresponding to the attractor shown in Figure 6.37.	173
Figure 6.39	Series of permeability distributions for the inversions of test 90/S1/T2.	174
Figure 6.40	Observed and modeled pressure transients for an inversion of test 90/S2/T2 before observed data had been edited.	176
Figure 6.41	Observed and modeled pressure transients for an inversion of test 90/S2/T2 after observed data had been edited.	177
Figure 6.42	The final attractor for an inversion of test 90/S2/T2. Attractor points identify locations of high permeability (gaps in the clay layer) in the intermediate layer between the upper and middle sand channels.	178
Figure 6.43	Observed and modeled pressure transients for an inversion of test 90/S2/T3.	180
Figure 6.44	The final attractor for an inversion of test 90/S2/T3. Attractor points identify locations of high permeability (gaps in the clay layer) in the intermediate layer between the upper and middle sand channels.	181
Figure 6.45	The observed data for the three-test co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2.	184
Figure 6.46	Attractor at the end of each stage of a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. Attractor points identify locations of high permeability (gaps in the clay layer) in the intermediate layer between the upper and middle sand channels.	186
Figure 6.47	Observed and modeled pressure transients for a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. Only one third of the observed data points used in the match are shown, to enable the calculated curves to be more visible.	187
Figure 6.48	Permeability distributions for three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 in which the inversion searched for gaps in the upper clay layer.	188
Figure 6.49	Permeability distributions for three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 in which the inversion searched for the upper clay layer.	189
Figure 6.50	Observed and modeled pressure transients for the lowest-energy co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. The permeability distribution is shown as the left frame in Figure 6.49. Only one third of the observed data points used in the match are shown, to enable the calculated curves to be more visible.	191
Figure 6.51	Nine possible interpolations of the point lithologic data obtained from well-logs. The dark regions represent gaps in the clay layer between the upper and middle sand channels. The energy values show the mismatch between pressures calculated for each of these models and the observed data for tests 90/S1/T2, 90/S2/T2, and 90/S3/T2, shown in Figure 6.45.	193
Figure 6.52	The initial attractor, the first 19 accepted attractors, and the corresponding energies for a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. Attractor points identify locations of high permeability (gaps in the clay layer) in the intermediate layer between the upper and middle sand channels.	194

Figure 6.53	Two-dimensional energy surface as a function of the height and width parameters of a triangular gap in the upper clay layer centered on well 5. The black line outlines the portion of the energy surface which is consistent with the borehole lithology. The circles show the results of co-inversions using the direction-set method (black), simulated annealing (grey), and simplex annealing (white). To convert from parameter space to physical space, multiply height and width parameters by 1600 m.	195
Figure 6.54	Observed and modeled pressure transients for a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2, using a triangular-gap model with a 1173-m-wide, 240-m-high gap in the upper clay layer (corresponding to $w = 0.733$, $h = 0.15$ in the parameter space shown in Figure 6.53).	196
Figure 6.55	Transmissivity distributions for three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 in which the inversion searched for heterogeneities within the middle sand channel.	199
Figure 6.56	Observed and modeled pressure transients corresponding to the transmissivity distribution shown in the left frame of Figure 6.55. Only one third of the observed data points used in the match are shown, to enable the calculated curves to be more visible.	200
Figure 6.57	Transmissivity distributions for three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 in which the inversion searched for heterogeneities within the upper sand channel.	202
Figure 6.58	Observed and modeled pressure transients corresponding to the transmissivity distribution shown in the left frame of Figure 6.57. Only one third of the observed data points used in the match are shown, to enable the calculated curves to be more visible.	203
Figure 6.59	Schematic lithologic cross-sections of the Gypsy pilot site for well pairs 1 and 5, 1 and 7, and 5 and 7, for which cross-well seismic surveys were conducted by BP.	208
Figure 6.60	Seismic velocity distributions for the plane containing wells 5 and 7, obtained by a computer inversion of first arrival times [Vasco <i>et al.</i> , 1996].	211
Figure 6.61	Common source/multiple receiver gathers for the 0.6-m (two-foot) cross-well seismic survey between wells 1 and 5; some interpretations made in conjunction with the geologic and hydrologic data are noted.	213
Figure 6.62	Example of possible guided waves at the depth of the lower sand channel at the Gypsy pilot site.	214
Figure 6.63	Variograms of log permeability from the Gypsy outcrop site road-cut (R.C.) and boring (B.) data.	216
Figure 6.64	Variogram combining $y = 0$ m road-cut data and omni-directional boring data. Grey points are the original points; black points are equally spaced points used by CRFGEN. The solid curve is a power law fit to the data, used for kriging.	217
Figure 6.65	Lower-sand-channel transmissivity distribution generated by kriging.	218
Figure 6.66	Lower-sand-channel transmissivity distributions generated by the correlated random field generator CRFGEN, using the variogram shown in Figure 6.64.	219
Figure 6.67	Variogram for the $y = 5$ m road-cut data and a power-law curve fit to it.	220

Figure 6.68	Lower-sand-channel transmissivity distribution generated by the correlated random field generator CRFGEN, using a power-law fit to the $y = 5$ m variogram shown in Figure 6.67.	221
Figure 6.69	Ad hoc variogram constructed from pilot-site pressure buildup data.	222
Figure 6.70	Lower-sand-channel transmissivity distributions generated by the correlated random field generator CRFGEN, using the pilot-site variogram shown in Figure 6.69.	223
Figure 6.71	Observed and modeled pressure transients for a co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, in which all observed data was used.	225
Figure 6.72	Observed and modeled pressure transients for a co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, in which all observed data for well 5 was omitted. The open circles showing the observed data for well 5 were not used in the inversion, but are shown here to illustrate how well the model can predict additional data.	227
Figure 6.73	Transmissivity distribution returned by the co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, in which all observed data for well 5 was omitted.	228
Figure 6.74	A comparison of the transmissivity distributions returned by a geostatistical model (left frame), a co-inversion omitting well 5 data (middle frame), and a co-inversion of all available data (right frame).	230
Figure 6.75	Three-dimensional representation of the subsurface heterogeneity at the Gypsy pilot site.	232
Figure 7.1	Extrapolation of a hydrologic characterization using either the assumption of stationarity for scales greater than that of the well field, or the assumption that fractal geometry applies at scales both larger and smaller than the scale of the well field.	242
Figure A.1	Schematic diagram of a two-dimensional TRINET lattice.	247
Figure A.2	TRINET lattice used for verification calculations.	250
Figure A.3	TRINET comparison with <i>Theis</i> [1935] solution: a) using the lattice shown in Figure A.2; b) using a finer lattice.	251
Figure A.4	Schematic diagram of a quasi three-dimensional TRINET lattice.	252
Figure A.5	TRINET comparison with <i>Hantush and Jacob</i> [1955] solution: a) using the lattice spacing shown in Figure A.2; b) using a finer lattice.	255

LIST OF TABLES

Table 4.1	Synthetic problem 1 inversions with $k = 2$, b 's only varying, and $E_{\min} = 3.6$.	59
Table 4.2	Synthetic problem 2 (high anomaly) inversions with $k = 3$, attractor points that increase properties, and $E_{\min} = 1.6$.	70
Table 4.3	Synthetic problem 2 (low anomaly) inversions with $k = 3$, attractor points that decrease properties, and $E_{\min} = 1.6$.	77
Table 4.4	Synthetic problem 2 inversions for various well locations. Three $k = 3$ inversions were done for each problem, using different random seeds.	79
Table 4.5	Mean and standard deviation of log-permeability at the Gypsy Outcrop site (permeability in millidarcies). Taken from Doyle [1989] except as noted.	86
Table 4.6	Summary of inversions of noisy synthetic data. Six inversions were done for each case. In all cases $E_{\min} = 1.6$.	108
Table 5.1	Kesterson Reservoir inversions with $k = 4$ and attractor points that decrease transmissivity.	112
Table 6.1	Well tests conducted at the Gypsy pilot site in 1989 and 1990.	124
Table 6.2	Gypsy well-test data eliminated from consideration due to inconsistencies or problems.	129
Table 6.3	Reciprocity checks for Gypsy Pilot-site well-test data.	132
Table 6.4	Production and observation well combinations for the Gypsy lower sand channel well tests.	136
Table 6.5	Summary of parameters used for eight inversions of test 90/S4/T1.	143
Table 6.6	Energies for lower sand channel cross-validation studies.	162
Table 6.7	Production and observation well combinations for the Gypsy upper and middle sand channel well tests.	168
Table 6.8	Energies for cross-validation studies among upper/middle sand channel tests using common wells.	204
Table 6.9	Energies for cross-validation studies using various models for all upper/middle sand channel tests.	206
Table 6.10	Energies for a simulation of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, using various transmissivity distributions.	224
Table A.1	Parameters for Theis [1935] solution verification.	252
Table A.2	Parameters for Hantush and Jacob [1955] solution verification, in addition to those given in Table A.1.	254

NOTATION

A	set of points $\mathbf{x}$
a	coarsening factor for a nested lattice
$\mathbf{B}$	matrix of affine transform
$\mathbf{b}$	vector of affine transform
b	thickness of TRINET lattice element
C	rotation-matrix contractivity factor (Equation (2.12))
E	energy, the value of the objective function to be minimized by inversion
$E_{\min}$	stopping criterion for the inversion
f	iterated function system (IFS)
g	affine transform
h	head or drawdown (m)
I	number of iterations used to generate attractor
$\mathbf{I}$	identity matrix
j	level of nesting for a nested lattice
K	hydraulic conductivity (m/s)
k	the number of affine transforms in an IFS
L	lattice spacing, for a nested lattice the lattice spacing is $a^j L$ at the j th level of nesting (m)
M	number of attractor points affecting a lattice element
M_0	total number of attractor points ($M_0 \sim k^I$)
N	number of observed drawdowns included in the objective function
N_0	a constant to keep E a convenient magnitude (currently $N_0 = 100$)
n	dimension of parameter space
$\mathbf{P}$	vector of unknown parameters (entries of $\mathbf{B}$'s and $\mathbf{b}$'s)
$\Delta\mathbf{P}$	vector of random increments
$ \Delta\mathbf{P} $	magnitude of vector $\Delta\mathbf{P}$ (square root of sum of squares of components of $\Delta\mathbf{P}$)
S	storativity
ΔS	contribution of attractor point to storativity
S_s	specific storage (m^{-1})
s	extent of effect of attractor point in distributed map
T	transmissivity (m^2/s)
ΔT	contribution of attractor point to transmissivity
t	time (s)
τ	temperature in simulated annealing algorithm
w	aperture of TRINET lattice element (m)
X_0	scale factor to map the attractor from the unit square to the TRINET lattice (m)
$\mathbf{x}$	coordinates of point (m)
x	distance (m)
y	distance (m)
Δ_1, Δ_2	amount of curve shift along the $\ln t$ or $\ln h$ axis, respectively, to minimize E
θ	rotation-matrix angle (Equation (2.12))

Subscripts and modifiers

c	calculated
o	observed
0	base value (unaffected by attractor points) or initial value
$'$	leaky confining layer property or trial value
$-$	effective porous medium property
$-$	average value

ACKNOWLEDGEMENT

One of the benefits of taking many years to write a dissertation (perhaps the only one) is the opportunity to interact with so many people with so many good ideas. I am most grateful to the following colleagues for their contributions to this work: Jane Long, my research supervisor, for her unflagging enthusiasm, support, and insightful comments, including consistently pointing out the forest to me, while I am caught up examining the structure of the pine cones; Paul Wither- spoon, my thesis advisor, for his excellent motivation and encouragement; Neville Cook and Bill Dietrich, thesis committee members, for their careful reviews of this work; Kevin Hestir, for developing the first version of IFS inverse method, and keeping me at least somewhat mathemati- cally rigorous; Ann Thompson, for her enthusiastic help in organizing the Gypsy data; Jennifer Horsman, for the beautiful AVS visualizations of the Gypsy Outcrop site; John Peterson and Tom Daley, for teaching me enough about cross-well seismology so that I can answer hydrologists' questions on the subject; Don Vasco, for developing techniques for inversion of seismic data that I happily appropriated for hydrologic inversion; and Akhil Datta-Gupta for providing the corre- lated random field generator. In addition, I have greatly enjoyed and learned much from discus- sions with many other members of the Earth Sciences Division at Lawrence Berkeley Laboratory.

The early development of the IFS inverse method and the application to Kesterson Reser- voir data was supported by the Director, Office of Energy Research, Office of Health and Environmental Research, Subsurface Science Program, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098. Thanks are due to Sally Benson for providing the Kesterson data. Later development of the method and the application to the Gypsy data was supported by the Assistant Secretary for Fossil Energy, Office of Oil, Gas and Shale Technologies, of the U.S. Department of Energy under Contract No. DE-AC03-76SF00098. Thanks are due to BP Explora- tion (in particular Gary Crawford and Ed Witterholt) and the University of Oklahoma Center for Reservoir Characterization for providing the Gypsy data.

1. INTRODUCTION

1.1 MOTIVATION

The highly heterogeneous nature of most geologic media, coupled with the restricted view of the subsurface available through boreholes, makes it difficult to determine the spatial distribution of subsurface hydrologic properties. Without such a description one cannot predict how fluid flow or solute transport will occur through permeable geologic media, and these predictions are critically needed to address many important environmental problems, including toxic chemical spills, leaking underground storage tanks, and long-term radioactive waste isolation. A common concern of these problems is the possible existence of 'fast paths', high-permeability pathways connecting the problem to the biosphere. An understanding of flow and transport behavior is also necessary to optimize energy extraction from petroleum or geothermal reservoirs, where identifying low-permeability barriers that compartmentalize reservoirs and hamper efficient resource utilization is a key problem.

The present work describes the development and application of a new inverse method for determining the spatial distribution of hydrologic properties (permeability and specific storage) in heterogeneous geologic media, using pressure transients from interference well tests. The method employs fractal concepts to improve efficiency and reliability. It is applicable to any sort of heterogeneous geologic medium in which wells communicate with each other, whether it be porous, fractured, or a combination thereof.

The remainder of Chapter 1 considers the differences between the forward and inverse approaches to hydrologic characterization, describes the use of forward models within inverse methods, reviews some alternate approaches to hydrologic inversion, and then outlines the present approach, which is called the Iterated Function System (IFS) inverse method. Chapter 2 presents the mathematical basis of the IFS, which is used to generate a fractal set, and Chapter 3 describes how IFS's are incorporated in the hydrologic inverse method (the fractal sets represent trial hydrologic property distributions). The IFS inverse method is tested by using it with synthetic data (Chapter 4), and is then applied to field data (Chapters 5 and 6). Chapter 7 summarizes the present work, draws some general conclusions on the strengths and weaknesses of the IFS inverse method, and describes possible areas for future research.

1.2 ALTERNATIVE APPROACHES FOR DEVELOPING HYDROLOGIC MODELS

1.2.1 Forward Versus Inverse Models

With the widespread use of computers over the past twenty years, numerous techniques for characterizing heterogeneous hydrologic property distributions have been developed. These techniques can be broadly divided into two groups, depending on whether they use a forward or inverse approach. Formally, these approaches differ as follows: in a forward method, boundary conditions and hydrologic properties are specified as input, and drawdowns are the calculated output; in an inverse method, boundary conditions and drawdowns are specified as input, and hydrologic properties are the calculated output. Whereas drawdowns can be determined uniquely in a forward method, hydrologic properties generally cannot be determined uniquely in an inverse method. Practically, in the forward approach, the hydrologic model is developed using information gained from basic studies of the site, including geological observations and geochemical, geophysical, petrophysical measurements. In the inverse approach, the general form of the hydrologic model is specified *a priori*, based on information from these basic studies, but the details of the model are determined by matching the predictions of the model to observed hydrologic behavior. Although both methods have advantages, each has drawbacks as well [Yeh, 1986; Ouenes *et al.*, 1994]. The present approach attempts to incorporate some of the strengths of a geologically-based forward approach within the context of an inverse method.

The principal advantage of using hydrologic inverse methods is that rather than determining the distribution of a parameter such as geological facies, core-scale permeability, or seismic-wave velocity and then attempting to relate it to a field-scale map of hydrologic properties, one analyzes well-test data, which depends on field-scale hydrologic properties explicitly. The method inherently emphasizes features that are important for flow and disregards the rest. In effect one develops equivalent media that do not have all the details of reality, but produce the same hydrologic response. In contrast, there is no guarantee that a flow model constructed by kriging core-sample permeability measurements will be able to reproduce the well-test response in the wells from which the the core samples were taken.

The principal disadvantage of using inverse methods for hydrologic characterization is that the fluid flow equation is a diffusion equation, and as such cannot be uniquely inverted to determine model parameters. Several practical means to address non-uniqueness are described in Section 1.2.4. A further practical disadvantage is that inverse methods tend to be computationally intensive. This should not be considered a fundamental limitation of the method, however, as

rapid developments in both computer hardware and software make more complicated inverse problems tractable.

1.2.2 The Use of a Forward Model in an Inverse Method

The inversion procedure consists of running a forward model repeatedly, using different parameter values, and comparing the results of each simulation to field observations. The result of the inversion is a model comprised of the parameter set which gives the best match between simulated and observed data. In principle, any forward model that contains adjustable parameters can be incorporated into an inverse method. In practice, some forward models are more amenable to inclusion in an inversion than others, as described in the paragraphs below.

Analytical Models. Before the widespread use of computers made numerical methods practical for solving subsurface fluid flow and solute transport problems, a vast number of analytical solutions were developed and adapted from other disciplines [e.g., *Theis*, 1935; *Hantush and Jacob*, 1955; *Neuman and Witherspoon*, 1969; *Gringarten*, 1971; *Cinco-Ley et al.*, 1978]. With only a few parameters and very short times required for calculation, analytical solutions are well suited to use in an inversion. However, the heterogeneities that can be treated with analytical solutions are limited to geometrically regular features such as linear vertical boundaries, horizontally layered media, and equally spaced fractures. Such simple geometries can only represent highly idealized models of geological media; to solve problems with heterogeneities that resemble the geometric irregularity observed in the field, numerical modeling is needed.

Numerical Models. In a numerical model of a geologic medium, space can be discretized into irregularly shaped regions with different hydrologic properties. Both the number of parameters to be determined and the computational time for each forward simulation of the model increases drastically (typically by several orders of magnitude) compared to inversions using analytical solutions. Hence, inverse methods based on numerical forward calculations must be carefully designed to make use of computer time efficiently. The multiplicity of scales on which heterogeneities are observed in the field complicates the discretization, and at some scale heterogeneities cannot be treated individually but must be modeled as an effective medium. In an effective medium approach, a homogeneous region is used to represent a heterogeneous one by assigning hydrologic properties that incorporate the effects of the heterogeneities. The appropriate level of discretization depends on the nature of the heterogeneity, the number and location of observation wells from which data is available, and the ultimate purpose of the characterization. In general, a numerical analysis should begin with the simplest model possible (probably a

homogeneous medium), and add heterogeneity only as needed to match the observed data.

Stochastic Models. In contrast to the deterministic treatment of heterogeneities based on large-scale geological observations (e.g., clay layer overlying aquifer, permeable fracture zone separating intact blocks of low-permeability rock), which form the basis for the analytical and numerical forward models described above, geostatistics provides an alternate way to construct a hydrologic model. In geostatistics, the spatial distribution of a hydrologic property is described as a correlated random field. A large number of (usually small-scale) measurements are made to determine the statistics (mean, variance, correlation structure) of the probability distribution of the property. A hydrologic model is then constructed either by drawing a realization from that probability distribution, or by using the correlation structure to interpolate between known values of the property (kriging). One way to incorporate geostatistics into a hydrologic inverse method is to use inverted hydraulic head data along with permeability measurements to determine the statistics of the probability distribution for permeability [Kitanidis and Vomvoris, 1983]. This approach to inversion has the advantage that relatively few unknown parameters need to be determined. Another way to incorporate a geostatistical model into an inverse method is to create many realizations of the random field, all consistent with the statistical properties inferred from the small-scale measurements, then use each realization to simulate a well test. The match to the well-test data provides the basis for choosing among the realizations.

Mechanistic Models. Another basis for creating a hydrologic model is to model the mechanisms involved in the creation of the geological medium, rather than to merely make observations or measurements of the medium itself. Such mechanistic models are generally very computationally intensive [e.g., Koltermann and Gorelick, 1992], making them ill-suited to incorporation in a hydrologic inversion in which the forward model must be run many times. Recently however, several investigators have developed computationally efficient mechanistic-based models by retaining only the key aspects of the physical mechanisms in a simple statistical way [Webb, 1992; Long et al., 1993; Hestir, et al., 1995]. Such models are amenable to incorporation in an inverse method by creating a series of realizations of the physical process, and testing each one to see how well it reproduces the hydrologic behavior. An optimization process would therefore find realizations which both match the hydrologic data and honor the physical process.

1.2.3 Approaches to Inverse Modeling

A useful way of categorizing hydrologic inverse methods is by the assumptions they make on the structure of heterogeneities. At one extreme, no assumptions are made and the inverse

method searches for the structure of the heterogeneity. At the other extreme, the structure of the heterogeneity is specified *a priori*, and the inverse method searches only for the property values within that structure. In between are inverse methods that search for structure and/or properties within user-specified constraints. The optimal method to use depends on the nature of the hydrogeologic setting and the amount of existing information on it, the type of observed data available, and the ultimate purpose of doing the hydrologic inversions.

Unstructured Models. The most general form of an unstructured model would use a three-dimensional regular grid to represent the flow system, and the inversion would search for the permeability value of each node on the grid independently. This approach places no *a priori* assumptions on the permeability distribution (other than ignoring heterogeneity on scales smaller than the grid spacing), and typically results in a huge number of unknown parameters to be determined by the inversion. A modest constraint would be to assume that flow is restricted to an aquifer layer or planar fracture zone, and look only for heterogeneities within a two-dimensional model of the flow system. An example of unstructured hydrologic inversion method that has been widely used to characterize fractured flow systems is lattice annealing [Long *et al.*, 1991; Mauldon *et al.*, 1993; Datta-Gupta *et al.*, 1994], in which a lattice of one-dimensional conductors (pipes) of porous medium is used to represent a fracture network. Elements of the lattice are randomly turned on and off one at a time, to model different patterns of connectivity within the fracture network, in order to match the well-test data.

Partially-Structured Models. Constraints incorporating geologic understanding about a site may be imposed on unstructured inversions, to produce partially-structured models. In one simple extension of the lattice annealing algorithm described above, elements are not turned on and off one at a time, but rather the transmissivity of a cluster of elements is assigned a random value drawn from a user-specified distribution [Najita and Karasaki, 1995]. The centers of the clusters are chosen at random during the inversion, but the extent of the cluster is specified by the user, and may be chosen to reflect the conceptual model of the hydrogeology. Another possibility is to replace the regular lattice of conductors with a lattice specifically constructed to incorporate geological information. A simple way to achieve this is to orient the grid along the direction of major fracture sets or along the paleoflow direction in a fluvial system. A more sophisticated approach is embodied in the fracture genesis algorithm [Vail, 1993], in which the lattice is created by a stochastic fracture growth process that is based on fracture mechanics principles. Random numbers within the growth algorithm are varied in order to match the well-test data. The resulting fracture network honors both the fracture genesis process and the well-test data. In

general, the number of unknown parameters for which the inversion searches is greatly reduced in partially-structured models compared to unstructured models.

Fixed-Structure Models. A fixed-structure model is one in which the structure of heterogeneity is specified *a priori* and the inverse method searches only for properties values within that structure. This method is appropriate if there is information supporting the existence of the structure, so that the locations of key features are known with certainty. It is also appropriate if very little is known about a system, in which case a simple structure is used, and only one or a few parameters are sought to provide an average picture of the system. In either case, the number of unknown parameters for which the inversion searches is drastically reduced compared to unstructured or partially structured inverse methods. The inverse method of *Carrera and Neuman* [1986a, 1986b, 1986c] is one well-known example of a fixed-structure model. Another, perhaps more flexible, inverse model is ITOUGH2 [*Finsterle*, 1993], which can be used in either unstructured or fixed-structured mode and has the powerful feature of including a forward model that calculates multi-phase, multi-component fluid and heat flow.

1.2.4 Addressing Non-Uniqueness

For unstructured or partially-structured inversions, with many unknown parameters, non-uniqueness is likely to be unavoidable. That is, starting inversions from different initial guesses or using different random seeds will result in different values of the unknown parameters. For fixed-structure inversions, because more assumptions are made about the structure of heterogeneity, fewer unknown parameters are needed, and it is more likely that the solution to the inverse problem will be unique. However, such a solution may be considered 'locally unique,' but not 'globally unique,' because with a different heterogeneity structure imposed, a different 'locally unique' solution would be obtained. Hence, for all sorts of hydrologic inversion methods, non-uniqueness must be acknowledged.

The following techniques may be used to mitigate the effect of non-uniqueness. Conditioning the inversion on additional information, such as prior estimates of model parameters [*Carrera and Neuman*, 1986a, 1986b, 1986c] or other geological or geophysical observations can lessen non-uniqueness. Another approach is to do multiple inversions and study the statistics of the ensemble of results, such as the mean and variance of the returned permeability distributions. The reliability of the result of an inversion may be assessed by a technique known as cross-validation, in which rather than using all available data to develop a hydrological model, some of the data is not used in the inversion process, and the inferred hydrological model is subsequently

used to try to match it. The strengths and weaknesses of an inversion method may also be assessed by using the method on synthetic data, for which the underlying property distribution is known.

At a more philosophical level, one can accept the non-uniqueness inherent in hydrologic inversion, and use it as a means to assess the information content of well-test data. By doing multiple inversions and studying the ensemble of results one can identify portions of the system to which the well-test response is sensitive (regions which show consistent features in all inversions) and regions to which the well-test response is not sensitive (regions which differ from inversion to inversion). This information can be of great use in developing more effective well-test techniques.

The conventional wisdom on inverse methods is that the number of unknown parameters should be minimized. This philosophy is known as the 'parsimonious approach' *Carrera and Neuman* [1986a; 1986c], and favors the fixed-structure approach. Although decreasing the number of unknown parameters certainly makes the inverse problem more tractable, and the fixed-structure approach may be appropriate under certain circumstances, it is not necessarily always the method of choice. As described above, the fixed-structure approach does not guarantee true uniqueness. Additionally, the information-content analysis is more difficult to do for fixed-structure models, as one must specify the series of structures to examine explicitly. In contrast, for unstructured or partially-structured inverse approaches, multiple inversions can be done easily by changing a random seed.

1.3 OVERVIEW OF THE PRESENT APPROACH

The present approach to the hydrologic characterization of heterogeneous geologic media involves the inversion of well-test data. A significant advantage of this approach compared to geological or geophysical investigations is that a well test directly investigates the phenomenon of interest: field-scale fluid flow through the system. The observed data to be inverted is typically transient pressure data obtained from multiple observation wells during one or more interference tests. A numerical model is used to calculate the head distribution and fluid flow in the forward problem (simulation of the well test).

The model parameters that are varied during the inversion specify a deterministic spatial distribution of hydrologic properties. Thus each forward calculation uses a geometric description of the hydrologic property distribution, rather than modeling the physical processes leading to its formation. The translation of the unknown parameters of the inversion to a heterogeneous

hydrologic property distribution (described below) puts only general constraints on the structure of heterogeneity, making this a partially structured approach.

1.3.1 Creation of Trial Hydrologic Property Distributions as Fractals

During the inversion process the search for model parameters is restricted to those which represent self-similar (or hierarchical) hydrologic property distributions, by generating the model parameters using an iterated function system (IFS) [Barnsley, 1988]. The IFS's used are composed of two to four affine transforms. An affine transform is a function which may rotate, reflect, deform, contract, and translate a set of points. When multiple transforms are applied iteratively (as is done in an IFS), a set of points with a fractal geometry, known as an attractor, results. Chapter 2 describes the mathematical formulation of IFS's in detail, and illustrates the creation of attractors. The attractor can be mapped to a distribution of transmissivity or storativity in a mathematical model. The mathematical model then simulates the well test and the calculated drawdowns are compared to those observed during the test. If the match is not satisfactory, the parameters of the IFS are varied, a new attractor is generated and mapped to a hydrologic property distribution, and the simulation is repeated. This procedure continues until the IFS creates an attractor which yields a hydrologic property distribution that produces a good match to observed drawdowns. A variety of optimization algorithms may be used to vary the parameters of the IFS during the course of the inversion. Chapter 3 describes each component of the IFS inverse method more fully.

One of the primary strengths of the IFS inversion compared to other inverse methods is that far fewer parameters are needed to describe a self-similar medium than a medium with unstructured heterogeneities, making the inversion more efficient and more robust (inverse methods which assume other kinds of structured heterogeneities share this advantage). Furthermore, by limiting the variation of parameters of the IFS, one can restrict the shape of the trial attractors to resemble observed hydrogeological features, or to reflect information gained from geological mapping or geophysical imaging work. In addition to these practical (or operational) advantages, the IFS inverse method is philosophically pleasing because it produces a hydrologic property distribution with a hierarchical structure, which mimics the multiple scales of heterogeneities often seen in natural geological media.

1.3.2 Comparison to Other Uses of Fractal Concepts in Subsurface Heterogeneity Characterization

Many researchers have used fractal concepts to study the effect of heterogeneity in subsurface hydrology in the past 5-10 years (see *Sahimi and Yortsos* [1990] for an early review). These works are largely divided into two groups: those which explain general features of observed hydrogeological behavior with a fractal model (e.g., scale-dependent dispersion [*Neuman*, 1990; *Wheatcraft and Tyler*, 1988], soil water properties [*Rieu and Sposito*, 1991a, 1991b; *Tyler and Wheatcraft*, 1990], well-test responses in fractured media [*Barker*, 1988]), and those which describe fractal interpolation schemes for generating complete hydrologic property distributions from sparse data [e.g., *Chung*, 1992; *Molz and Boman*, 1993]. The present work has the same goals as those in the latter category, but the distinction between the inversion of well-test data and the interpolation of point property measurements is very important, as outlined in Section 1.2.1.

2. BASICS OF ITERATED FUNCTION SYSTEMS

2.1 MATHEMATICAL FOUNDATION

An IFS is a standard way to model self-similar geometrical structures [Barnsley, 1988], which was developed for use in computer graphics in order to find efficient means for storing the information describing a complex picture. In this application, one identifies an iterative process that creates the picture rather than storing the information for each pixel. The iterative process is defined by an IFS which has a relatively small number of parameters. The use of an IFS essentially exchanges the use of computer storage for the use of computer time. In our application, it is necessary to create a model of a complex heterogeneous geologic system. Instead of trying to describe this system 'pixel by pixel,' we look for an IFS that can describe the geometry of the system with a small number of parameters.

To create a picture of a spatially variable hydrologic property distribution using an IFS, one starts with an initial set of points and iteratively adds new points to the set by the application of multiple affine transforms. After several iterations, the points coalesce towards an 'attractor,' a set of points with self-similar geometry. The shape of this attractor depends on the parameters of the affine transforms that make up the IFS, but is independent of the locations of the initial points. This procedure is described in detail below, followed by two examples of its use.

Mathematically, the creation of an attractor can be described as follows. One first specifies a function f , which maps sets to sets:

$$f(A_0) = A_1, \quad (2.1)$$

where A_0 and A_1 are (compact) subsets of two (or three) dimensional space. The attractor of f is then defined as the set A_∞ such that

$$A_{n+1} = f(A_n) \quad n = 0, 1, \dots \quad (2.2)$$

$$A_\infty = \lim_{n \rightarrow \infty} A_n.$$

Given certain restrictions on the set function f , one can show [Barnsley, 1988] that A_∞ exists, is independent of the starting set A_0 , and generally has a fractional Hausdorff dimension. That is, the attractor that f creates is a fractal. If the function f is easily parameterized, then the fractal A_∞ is parameterized as well. This leads to an efficient setup for modeling real-world problems, because a small number of parameters can be used to characterize a complex geometry.

One important example of an IFS used extensively by *Barnsley* [1988] is the union of k affine transforms:

$$f(A) = g_1(A) \cup g_2(A) \cup \dots \cup g_k(A), \quad (2.3)$$

where each affine transform is given by

$$g_i(A) = \bigcup_{x \in A} g_i(x) \quad (2.4)$$

$$g_i(x) = \mathbf{B}_i x + \mathbf{b}_i,$$

where $\mathbf{B}_i$ is a matrix, $\mathbf{b}_i$ a vector, and x identifies the coordinates of a point in the set A . The parameters, $\mathbf{P}$, characterizing f are the entries in the $\mathbf{B}_i$'s and $\mathbf{b}_i$'s. The matrix $\mathbf{B}_i$ may rotate, reflect, deform, or contract the set A and the vector $\mathbf{b}_i$ translates it, as illustrated in Figure 2.1 for a two-dimensional set.

Figure 2.2 shows an example of the construction of a two-dimensional attractor for a case where k , the number of affine transforms, equals three. The affine transforms contract and translate, and result in an attractor which is a well-known fractal called Sierpinski's gasket [Barnsley, 1988]. The IFS is specified by

$$\mathbf{B}_1 = \mathbf{B}_2 = \mathbf{B}_3 = \begin{bmatrix} 0.5 & 0.0 \\ 0.0 & 0.5 \end{bmatrix} = 0.5\mathbf{I}, \quad (2.5)$$

$$\mathbf{b}_1 = (0.0, 0.0), \quad \mathbf{b}_2 = (0.5, 0.0), \quad \mathbf{b}_3 = (0.0, 0.5),$$

where $\mathbf{I}$ denotes the identity matrix. To create three-dimensional attractors, 3×3 $\mathbf{B}$ matrices and three-dimensional $\mathbf{b}$ vectors would be used. The initial set of points used in Figure 2.2 form a cross, but it is apparent that after only a few iterations the triangular symmetry inherent in Equation (2.5) dominates the picture.

Figure 2.3 shows the construction of another two-dimensional attractor, this time for an IFS with $k = 4$, with parameters given by

$$\begin{aligned} \mathbf{B}_1 &= \begin{bmatrix} 0.66 & 0.26 \\ -0.32 & 0.26 \end{bmatrix} & \mathbf{b}_1 &= \begin{bmatrix} 0.01 \\ 0.35 \end{bmatrix} & \mathbf{B}_2 &= \begin{bmatrix} 0.28 & -0.09 \\ 0.25 & 0.44 \end{bmatrix} & \mathbf{b}_2 &= \begin{bmatrix} 0.13 \\ 0.29 \end{bmatrix} \\ \mathbf{B}_3 &= \begin{bmatrix} 0.58 & 0.42 \\ 0.18 & 0.62 \end{bmatrix} & \mathbf{b}_3 &= \begin{bmatrix} 0 \\ 0.20 \end{bmatrix} & \mathbf{B}_4 &= \begin{bmatrix} 0.39 & 0.01 \\ 0.25 & 0.48 \end{bmatrix} & \mathbf{b}_4 &= \begin{bmatrix} 0.56 \\ 0.02 \end{bmatrix}. \end{aligned} \quad (2.6)$$

The less regular geometric shape and subtler expression of self-similarity of this attractor compared to the Sierpinski gasket reflect the greater variability of the parameters of its IFS, and make

Untransformed set

Translation

$$B = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \quad \mathbf{b} = \begin{bmatrix} 0.4 \\ 0.2 \end{bmatrix}$$

Contraction in y

$$B = \begin{bmatrix} 1 & 0 \\ 0 & 0.5 \end{bmatrix} \quad \mathbf{b} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

Rotation by 30°

$$B = \begin{bmatrix} 0.87 & -0.5 \\ 0.5 & 0.87 \end{bmatrix} \quad \mathbf{b} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

Reflection and translation

$$B = \begin{bmatrix} -1 & 0 \\ 0 & 1 \end{bmatrix} \quad \mathbf{b} = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

Distortion

$$B = \begin{bmatrix} 1 & 0.5 \\ 0.5 & 1 \end{bmatrix} \quad \mathbf{b} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

Figure 2.1. The effect of various affine transforms on a set of points.

Untransformed set

After one iteration

After two iterations

After three iterations

After four iterations

After five iterations

Figure 2.2. Generation of Sierpinski's gasket using an IFS with $k = 3$ and a set A_0 forming a cross.

Untransformed set

After one iteration

After two iterations

After three iterations

After four iterations

After five iterations

Figure 2.3. Generation of an attractor using an IFS with $k = 4$ and a set A_0 consisting of a single point.

it more suitable for the representation of natural geologic media than are the 'round numbers' and geometric symmetry of the Sierpinski gasket. For example, if the final frame in Figure 2.3 represents a plan view of an aquifer, one could imagine that the black attractor points delineate low-permeability clay lenses while the surrounding white space represents high-permeability sand (details involved in mapping an attractor to a hydrologic property distribution are given in Chapter 3, Section 1).

In order for an IFS to converge to an attractor, each affine transform must be a contraction mapping [Barnsley, 1988]. By definition, an affine transform is a contraction mapping if the distance between any two transformed points is less than the distance between the two original points. One can guarantee that the affine transform $g(\mathbf{x}) = \mathbf{B}\mathbf{x} + \mathbf{b}$ is a contraction mapping by restricting the entries of $\mathbf{B} = \begin{bmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{bmatrix}$ according to

$$|B_{11}| + |B_{12}| < 1 \quad (2.7)$$

$$|B_{21}| + |B_{22}| < 1.$$

There are other means of obtaining contraction mappings, which impose less stringent constraints on the $\mathbf{B}$ matrices, but they are more complicated to use. For convenience, $\mathbf{b}$ is restricted so that the attractor is confined to the unit square $0 < x < 1$, $0 < y < 1$. The constraints on $\mathbf{b} = (b_1, b_2)$ depend on the entries of $\mathbf{B}$, and may be written as

$$-\min(0, B_{11}) - \min(0, B_{12}) < b_1 < 1 - \max(0, B_{11}) - \max(0, B_{12}) \quad (2.8)$$

$$-\min(0, B_{21}) - \min(0, B_{22}) < b_2 < 1 - \max(0, B_{21}) - \max(0, B_{22}).$$

Note that under no conditions may the components of $\mathbf{b}$ lie outside the range zero to one.

2.2 VARIATION OF THE ATTRACTOR WITH THE PARAMETERS OF THE IFS

During an inversion many different values of $\mathbf{P}$, the unknown parameters of the IFS, are used in the forward model. When designing or choosing an algorithm to find the optimal values of $\mathbf{P}$, it is helpful to understand how changes in $\mathbf{P}$ change the attractor (and hence the hydrologic property distribution). Figure 2.4 shows the attractors generated by a sequence of IFS's with $k = 3$. These are $f_1, f_2, \dots, f_6$, where f_1 is Sierpinski's gasket, and for frames $m = 2, 6$ every parameter of f_m differs from the corresponding parameter of f_{m-1} by a small increment:

$$\mathbf{P}_m = \mathbf{P}_{m-1} + \Delta\mathbf{P}. \quad (2.9)$$

The components of $\Delta\mathbf{P}$ are random numbers drawn from a uniform distribution between -1 and 1,

Figure 2.4. A sequence of attractors generated by IFS's with $k = 3$ whose parameters differ by a small amount. For the m th frame, $\mathbf{P}_m = \mathbf{P}_{m-1} + \Delta\mathbf{P}$, where $\Delta\mathbf{P}$ is a vector with random increments and $|\Delta\mathbf{P}| = 0.2$.

normalized so that the magnitude of $\Delta \mathbf{P}$, $|\Delta \mathbf{P}|$ (the square root of the sum of squared components of $\Delta \mathbf{P}$), equals 0.2. The continuous small change in $\mathbf{P}$ from frame to frame is manifested as a continuous gradual change in the attractors. A larger value of $|\Delta \mathbf{P}|$ would produce a more rapid variation in attractors.

The most general affine transforms that operate in two dimensions have four arbitrary entries in each $\mathbf{B}_i$ matrix, and two arbitrary values in each $\mathbf{b}_i$ vector, which makes $\mathbf{P}$ an $n = 6k$ dimensional vector for an IFS composed of k affine transforms. By holding some components of $\mathbf{P}$ fixed or limiting their variation, one can limit the variability of the corresponding attractors so that all trial hydrologic property distributions have features in common. As well as making the inversion procedure more efficient by reducing the extent of the parameter space to be searched, these constraints can be used to make the inversion more robust by conditioning it on known geological conditions, as illustrated below. Formally, $\mathbf{P}$ is defined as the vector composed of all the parameters characterizing the IFS, but in practice $\mathbf{P}$ is used to denote only those parameters that are varied during the inversion.

A simple two-dimensional heterogeneity that can have a large impact on flow is a long thin region of high or low permeability in a plane of otherwise uniform permeability. A high-permeability linear feature could represent a segment of a buried stream channel or the trace of a permeable fracture through an aquifer, whereas a low-permeability linear feature could represent the trace of a mineralized or gouge-filled fracture which blocks flow through an aquifer. Such a permeability distribution can be created by using an IFS with $k = 2$ which has constant matrices of the form

$$\mathbf{B}_1 = \mathbf{B}_2 = \begin{bmatrix} 0.5 & 0.0 \\ 0.0 & 0.5 \end{bmatrix} = 0.5 \mathbf{I} \quad (2.10)$$

and variable vectors $\mathbf{b}_1$ and $\mathbf{b}_2$, which results in a vector $\mathbf{P}$ which has only four components. All the attractors produced by such an IFS are line segments with endpoints determined by the values of $\mathbf{b}_1$ and $\mathbf{b}_2$. Six such attractors are illustrated in Figure 2.5a. For the first frame of Figure 2.5a, $\mathbf{b}_1 = (0.0, 0.5)$ and $\mathbf{b}_2 = (0.5, 0.0)$; for the other frames, $\mathbf{b}_1$ and $\mathbf{b}_2$ are modified by random numbers drawn from a uniform distribution. For Figure 2.5, in contrast to Figure 2.4, the original value of $\mathbf{P}$ and a different value of $\Delta \mathbf{P}$ are used for each frame:

$$\mathbf{P}_m = \mathbf{P}_1 + \Delta \mathbf{P}_m \quad (2.11)$$

For each frame of Figure 2.5a, the magnitude of the vector of random increments, $|\Delta \mathbf{P}_m|$, equals 0.6, a relatively large value, therefore each of frames 2-6 differs significantly from frame 1.

a) $k = 2$ $|\Delta \mathbf{P}_m| = 0.6$ b's only vary

b) $k = 2$ $|\Delta \mathbf{P}_m| = 0.2$

Figure 2.5. The variation in attractor as parameters of the IFS change. For the m th frame in each series, $\mathbf{P}_m = \mathbf{P}_1 + \Delta \mathbf{P}_m$, where $\Delta \mathbf{P}_m$ is a vector with random increments.

c) $k = 2$ $|\Delta P_m| = 0.6$

d) $k = 3$ $|\Delta P_m| = 0.6$

Figure 2.5. continued.

e) $k = 4$ $|\Delta P_m| = 0.6$

Figure 2.5. continued.

For greater variety in the population of trial hydrologic property distributions, an IFS in which both the $\mathbf{B}$'s and $\mathbf{b}$'s are allowed to vary may be used. For $k = 2$, curvilinear attractors are formed, as shown in Figures 2.5b and 2.5c. For the small value of $|\Delta P_m| = 0.2$ used in Figure 2.5b, all the attractors look similar to the original one. This would be a useful constraint if the attractor represented a region of enhanced permeability whose orientation was known *a priori*, such as a fracture that is part of a regional fracture set or a buried stream channel in a region where the overall paleoflow direction is known. In Figure 2.5c, the variation in parameters is larger, $|\Delta P_m| = 0.6$, and the attractors differ greatly, which would be useful for an inversion in which no prior information on permeability directionality is available.

Despite the large variability between the attractors, they all share the characteristic of being rather 'stringy', that is, they do not fill up the plane very well. This characteristic is quantified by a measure known as the fractal dimension. A straight line has a fractal dimension of one, whereas a curve that doubles back on itself so much that it covers the entire plane has a fractal dimension of two. Figures 2.5d and 2.5e show attractors created by IFS's with $k = 3$ and $k = 4$, and large variations in parameters ($|\Delta P_m| = 0.6$). Although there is a large variability amongst the attractors, they tend to be more 'blocky' and less stringy as k increases, that is, fractal dimension tends to increase with k . Regional geologic mapping can be used to estimate the fractal

dimension of features likely to be important for fluid flow (e.g., fractures, clay lenses), thus providing guidelines for choosing the value of k to use in an IFS inversion.

As an alternative to considering each $\mathbf{B}_i$ as composed of four independent entries, one can construct $\mathbf{B}_i$ as a rotation matrix

$$\mathbf{B}_i = C_i \begin{bmatrix} \cos \theta_i & -\sin \theta_i \\ \sin \theta_i & \cos \theta_i \end{bmatrix}, \quad (2.12)$$

where C_i is a contractivity factor ($0 < C_i < 1$) and θ_i is a rotation angle. This formulation reduces the dimension of $\mathbf{P}$ from six to four per affine transformation, but still allows a great variety of attractors, illustrated in Figure 2.6, frame (a). By holding some components of $\mathbf{P}$ constant, the effect of C , θ , and $\mathbf{b}$ can be demonstrated, as shown in frames (b) through (d). By allowing changes in θ and $\mathbf{b}$ while holding C fixed, a wide variety of attractor shapes can be created (frame (e)), with a further reduction in the dimension of $\mathbf{P}$ from four to three per affine transform.

There are two advantages to constructing the $\mathbf{B}$ matrices as rotation matrices. First, it decreases the number of unknown parameters, making the inversion more efficient. Second, it makes it easier to incorporate geological information by constraining the variation of some parameters, because the effect of each parameter is readily identified in the attractors, as illustrated in Figure 2.6.

a) C's, θ 's, and b's vary

b) C 's only vary

Figure 2.6. The variation in attractor as parameters of the IFS change, using the rotation-matrix form for $\mathbf{B}$, Equation (2.12). For the m th frame $\mathbf{P}_m = \mathbf{P}_1 + \Delta\mathbf{P}_m$, where $\Delta\mathbf{P}_m$ is a vector with random increments and $|\Delta\mathbf{P}_m| = 0.4$.

c) θ 's only vary

d) b 's only vary

Figure 2.6. continued.

e) θ 's and b 's vary

XBL 935-4330

Figure 2.6. continued.

3. USINGS IFS'S IN A HYDROLOGIC INVERSION

3.1 MAPPING THE ATTRACTOR TO A HYDROLOGIC PROPERTY DISTRIBUTION

To use the IFS attractors in a hydrologic inversion one needs to prescribe exactly how the attractor determines the spatial distribution of hydrologic properties in the mathematical model used to simulate the well test, a procedure called mapping the attractor to a hydrologic property distribution. The numerical model TRINET [Karasaki, 1987] is used to solve the forward problem (i.e., model the well test) within the IFS inversion. TRINET is a finite element model which calculates fluid flow in a lattice of one-dimensional finite elements (i.e., pipes) of porous or fractured medium. Although TRINET was originally developed to study fracture networks [Long *et al.*, 1991], its lattice structure is completely equivalent to a block model, as shown in Figure 3.1, and TRINET can also model porous media, as described in Appendix A. TRINET is well suited for use in a hydrologic inversion for several reasons:

- the one-dimensional finite element formulation is efficient computationally, enabling many forward calculations to be done,
- the lattice structure can be used effectively to represent highly channeled flow typical of fractured or strongly heterogeneous porous media, as well as to represent a homogeneous porous medium,
- forward calculations for a wide variety of hydrologic settings can be done without changing the underlying lattice, by modifying the lattice properties in accordance with the attractor mappings described below.

Although TRINET is convenient to use in IFS inversions, other forms of numerical models could be used as well, including finite-difference network models and finite-difference or finite-element continuum models composed of blocks of porous or fractured medium. All that is required is that space be discretized into flow domains, each with its own value of hydrologic properties and with a unique spatial location specified by a global coordinate system.

According to Equation (2.2) an attractor is formed by an infinite number of iterations, so it contains an infinite number of points. In practice a computer can only treat a finite number of points, so an attractor is created by a finite number of iterations I of Equation (2.2). If the starting set A_0 contains just one point, then the number of attractor points is $M_0 = k^I$. For typical applications $M_0 \approx 1000$ is large enough to resolve attractors adequately, implying that for $k = 4$, $I = 5$ is a sufficient number of iterations.

Figure 3.1. The equivalence between the TRINET lattice and a block model. The black lines show the one-dimensional finite elements comprising the TRINET lattice; head is calculated at the nodal points (black dots). The dashed lines show block boundaries in the equivalent block model, in which block center locations correspond to TRINET nodal points.

The attractor is defined on the unit square: $0 < x < 1$, $0 < y < 1$, and the first step required to map the attractor to a hydrologic property distribution is to choose a scale factor to map the unit square to the spatial domain where hydrologic-property variations affect the well-test response, that is, the region near the wells. The attractor is then superimposed on the lattice and the T and S_s values of the lattice elements adjacent to each attractor point are modified, according to one of two algorithms. With the 'step map,' illustrated in Figure 3.2, the properties of the single element whose midpoint is closest to a given attractor point are modified. Alternatively, with the 'distributed map' the hydrologic properties of all elements near an attractor point are modified, with the magnitude of the change decreasing as distance from the attractor point grows. Figure 3.3 illustrates the step and distributed maps

for a simple linear attractor and a uniform lattice. The choice of step or distributed map should reflect the geologic setting represented by the model. For example, the step map would be more appropriate for a fractured medium where contrasts in hydraulic conductivity are sharp, whereas the distributed map would be better for lenses that grade from sand to gravel.

Figure 3.2. Schematic diagram of the mapping from attractor points to lattice element hydrologic properties. In the frame at the right, element thickness is proportional to transmissivity.

3.1.1 The Step Map

The transmissivity and storativity that are unaffected by any attractor points are referred to as the base values T_0 and S_0 , whereas the transmissivity and storativity values that include the effect of the attractor points are denoted T and S . The effect of attractor points can be additive or multiplicative. If M attractor points are closest to a given lattice element, the step map using the additive algorithm gives

$$T = T_0 + M\Delta T \quad S = S_0 + M\Delta S, \quad (3.1)$$

and the multiplicative algorithm gives

$$T = T_0\Delta T^M \quad S = S_0\Delta S^M, \quad (3.2)$$

where ΔT and ΔS are the contribution for each attractor point. With the additive algorithm, choosing a positive value of ΔT or ΔS means that the attractor points increase T or S , whereas choosing a negative value means that attractor points decrease T or S . With the multiplicative algorithm, a value of ΔT or ΔS greater than one increases T or S , and a value less than one decreases T or S . The choice of additive or multiplicative algorithm and the sign and magnitude of ΔT and ΔS are arbitrary, but may be used to incorporate features of

Figure 3.3. Example of the mapping from attractor points to transmissivity distribution: a) the attractor superposed on the lattice; b) the transmissivity distribution for the step map, c) and d) the transmissivity distribution for the distributed map with $s = 0.025$ and $s = 0.05$, respectively. In frames b-d, element thickness is proportional to T/T_0 . The solid circles mark the well locations for synthetic problem 1.

the geological setting in the mathematical model. For example, for a fractured rock T and S generally increase or decrease together, along with fracture aperture. In contrast, for a sand/clay aquifer system, increases in S are accompanied by decreases in T , as clay content increases. Furthermore, using the multiplicative algorithm for a parameter is equivalent to using the additive algorithm for the log of the parameter, making the additive algorithm for S and the multiplicative algorithm for T a natural choice for typical geologic media in which the variability of T is greater than the variability of S .

Note that the value of M for each lattice element is proportional to M_0 , the total number of points in the attractor, so one way to allow bigger contrasts in hydrologic properties is to increase M_0 , or equivalently, I , the number of iterations of Equation (2.2), since $M_0 \sim k^I$. However, it is preferable to increase ΔT and ΔS rather than M_0 because the mapping of attractor points to lattice elements is computationally intensive. As illustrated in Figure 2.3, increasing I provides a more refined image of an attractor. Because mapping the attractor to the lattice smears out details on scales less than the length of a lattice element, the value M_0 must only be large enough to allow sufficient resolution of the attractor on the lattice.

For a variable-density lattice, the contribution of an attractor point to the overall hydrologic property distribution tends to be greater in coarse regions of the lattice than in fine regions. Thus, a given attractor will not produce the same hydrologic property distribution for two different lattices. This does not cause a problem in the inversion because only one lattice is used, but it means that a picture of the attractor provides only a qualitative representation of the hydrologic property distribution and a quantitative measure must come from the T or S distribution itself, such as is shown in Figure 3.3b.

3.1.2 The Distributed Map

For the distributed map, an attractor point at $\mathbf{x}_a$ modifies the properties of a lattice element with its midpoint at $\mathbf{x}_e$ according to

$$T = T_0 + \Delta T \exp\left[-\left[\frac{\mathbf{x}_e - \mathbf{x}_a}{X_0 a^j s}\right]^2\right] \quad S_s = S_{s0} + \Delta S_s \exp\left[-\left[\frac{\mathbf{x}_e - \mathbf{x}_a}{X_0 a^j s}\right]^2\right] \quad (3.3)$$

for the additive algorithm. The expressions for the multiplicative algorithm are identical except multiplication replaces addition:

$$T = T_0 \Delta T \exp\left[-\left[\frac{\mathbf{x}_e - \mathbf{x}_a}{X_0 a^j s}\right]^2\right] \quad S_s = S_{s0} \Delta S_s \exp\left[-\left[\frac{\mathbf{x}_e - \mathbf{x}_a}{X_0 a^j s}\right]^2\right] \quad (3.4)$$

inversion method to different geological settings. A natural extension would be to use independent attractors to represent transmissivity and storativity distributions, if the geological model did not provide any information on the relation between these properties.

3.2 THE OBJECTIVE FUNCTION

The objective function quantifies the mismatch between the calculated and observed drawdowns for a given value of $\mathbf{P}$. That is, it measures how well a model with a hydrologic property distribution mapped from an attractor generated by an IFS with parameters $\mathbf{P}$ matches the observed data.

3.2.1 Constructing the Objective Function to be Sensitive to Heterogeneities

The value of the objective function is known as the energy E , and is defined as

$$E = \frac{N_0}{N} \sum_1^N (\ln h_c - \ln h_o)^2, \quad (3.5)$$

where h_c and h_o are calculated and observed drawdowns, respectively, N is the number of observations available, and N_0 is a constant introduced to make the energy a convenient magnitude (usually taken to be 100). The sum from 1 to N in Equation (3.5) runs over all observation wells (including the pumping well if drawdown is measured there) and all observation times for a transient well test. For a steady-state well test, there is just one observation per well and all dependence on storativity drops out, leaving the transmissivity distribution as the only unknown to be determined by the inversion. Following the traditional practice of well-test analysis using type-curve matching, log drawdown is included in E rather than drawdown itself, which has the effect of placing relatively greater emphasis on small drawdowns and less on large drawdowns. Small early-time drawdowns generally reflect near well-field hydrologic properties, whereas large late-time drawdowns also include the effect of hydrologic properties far from the well field. This objective function form therefore makes the inversion more sensitive to well-field scale heterogeneities, which have a chance of being resolved using multiple observation wells, than to regional-scale heterogeneities, which probably could be sensed, but not effectively located, by an interference test.

In typical analyses of transient well tests, the observed drawdowns that are included in the energy for each well are uniformly distributed in log time, but the form of Equation (3.5) makes it easy to account for a variety of special conditions. For example, if early-time drawdowns are thought to be controlled by well-bore effects or late-time drawdowns by

distant boundaries not included in the model, they can simply be eliminated from the sum. If some observed data points are deemed more reliable than others due to differences in instrumentation, the energy can be weighted in their favor by including only a fraction of the less reliable points. Similarly, if certain responses are presumed to illustrate a key system feature, the inversion can be encouraged to find it by increasing the number of such observation points.

One potential difficulty with formulating the objective function in terms of $\ln h$, rather than h itself, arises when the drawdown response for one or more wells is very small (which could occur if the observation well were separated from the pumping well by a low-permeability region). Taking the log of a near-zero drawdown results in a large negative number, so even if both calculated and observed data show essentially no response, the contribution to the energy could be very large. In practice, this difficulty can usually be overcome by not including any non-responses or near non-responses in the observed data. Thus the earliest-time data included in the sum in Equation (3.5) will vary from well to well, with the earliest data included for the quickest responders. There is also an option in the IFS inverse method to formulate the objective in terms of h rather than $\ln h$, if it is desirable to include non-responses for a particular application, which can be critical for certain applications such as waste isolation.

The sum in Equation (3.5) can include drawdowns from multiple steady-state or transient well tests, a procedure called co-inversion. Multiple transient tests are treated as though they were one long test, with variable flow rates at the pumping well or wells. Co-inverting multiple well tests which use different pumping wells requires that the returned transmissivity distribution yields the proper pressure response at observation wells under a variety of flow conditions, which greatly enhances the reliability of the inversion results. Additionally, as the observed data becomes sensitive to a greater portion of the flow system, by sampling properties along additional flow paths, the inversion has a chance to provide information on a greater portion of the system as well. The primary practical limitation to the number of well tests included in a co-inversion is that the forward calculation becomes more computationally intensive with the addition of each test. However, there may be little information content gained in including multiple tests involving the same pumping and observation wells. Chapter 6 shows two examples of choosing among multiple well tests for a combination to create an efficient co-inversion.

Mathematically, if one assumes independent identically distributed Gaussian random errors in the term $(\ln h_c - \ln h_o)$, which is known as the residual, E is directly proportional to the log likelihood of the well response. Hence minimization of E corresponds to the statistical procedure of maximum likelihood estimation. Although it is reasonable to expect that errors in measured drawdowns are purely random errors and are thus likely to be normally distributed and uncorrelated, this is probably not a good assumption for the residual as a whole, as an error in the model will tend to produce highly correlated residuals (e.g., ignoring leakage into an aquifer from an overlying layer will cause the model to systematically overpredict late-time drawdowns). See *Carrera and Neuman* [1986a and 1986b] for a discussion of these ideas and a more general formulation of E as a quadratic form based on the correlation structure of the residual errors.

3.2.2 Determining Base Values of Hydrologic Properties by Curve Shifting

One advantage of formulating E as a function of $\ln h$ rather than h itself is that if the flow rate is held constant at the pumping well, determining the base values of transmissivity T_0 and storativity S_0 in the lattice can be done easily within the matching procedure by curve shifting, in much the same way as transmissivity and storativity for a uniform medium can be determined by shifting observed $\ln h$ versus $\ln t$ curves until they overlie a Theis type curve. During curve-matching, the drawdown versus time curves, plotted on log-log scales, are shifted along the $\ln t$ and $\ln h$ axes until the mismatch between the observed and calculated values is minimized. As described below, a shift along the $\ln h$ axis determines T_0 , and a shift along the $\ln t$ axis determines the base value of diffusivity (T_0/S_0). Thus the inversion can search for heterogeneities in transmissivity and storativity without needing to know the actual base values.

In the calculation of the energy E , the drawdown curves calculated with trial values of T_0 and S_0 (and the contribution from the attractor) are shifted along the $\ln t$ axis by an amount Δ_1 and along the $\ln h$ axis by an amount Δ_2 , with Δ_1 and Δ_2 chosen to minimize E . Then multiplying the trial value of T_0 by e^{Δ_2} yields the best-fit base transmissivity, and multiplying the trial value of T_0/S_0 by e^{Δ_1} yields the best-fit value of that ratio. Finally, multiplying the trial value of S_0 by $e^{\Delta_2 - \Delta_1}$ yields the best-fit base value of storativity. For steady-state drawdowns arising from a constant-flow test, a shift of the $\ln h$ values may be used to determine T_0 .

3.2.3 Determining Base Value of Diffusivity by Optimization

When variable flow-rate boundary conditions are imposed during a well test, such as during a pulse test in which flow is turned on and off in a single well, or during a co-inversion of multiple tests, in which flow is turned on and off in different wells, it is not possible to shift along the $\ln t$ axis to determine the base value of diffusivity. This is because shifting in $\ln t$ is equivalent to stretching or shrinking the time scale of a well test, and for a variable-rate test, the actual time schedule of the flow-rate changes fixes the time scale. Thus if shifting along the $\ln h$ axis is done, a shift in transmissivity must be accompanied by a corresponding shift in storativity so that diffusivity remains unchanged. However, it is highly desirable not to be limited to a single value of base diffusivity during an inversion, but to have the IFS inversion code search for the optimal base value of diffusivity in addition to looking for transmissivity and storativity heterogeneities. Unlike the optimization for the parameters determining heterogeneities, which is a multi-dimensional minimization which usually takes thousands of forward calculations and great care in the choice of optimization algorithm (see Section 3.3), the determination of the base value of diffusivity is a one-dimensional minimization which typically takes only about ten forward calculations, and uses a standard one-dimensional minimization routine known as Brent's Method [Press *et al.*, 1986].

The key question is when (i.e., how often) to do the diffusivity optimization during the search for parameters of the IFS. In general, changes in base values of properties (transmissivity, storativity, or diffusivity) affect all the drawdown curves in a consistent manner (e.g., a lower base value of transmissivity will increase all drawdowns), whereas heterogeneities (as specified by the parameters of the IFS) determine more localized features (e.g., a high-permeability channel between a pumping well and observation well will produce a larger pressure response in that observation well only). Thus it makes sense to do the diffusivity optimization less frequently than the IFS parameter optimization. Usually one diffusivity optimization is done for a uniform medium (no attractor), and another for the initial attractor tried during the inversion. Thereafter, diffusivity optimizations are only done every so often during the IFS parameter inversion, with the exact frequency depending on the optimization algorithm chosen. This procedure seems to work well, and typically base diffusivity does not change much after the early stages of the inversion.

3.3 THE OPTIMIZATION ALGORITHM

The optimization algorithm determines how new trial values of the n -dimensional vector $\mathbf{P}$ are chosen during the IFS inversion. Four optimization algorithms from standard numerical libraries are included in the IFS inverse method. For all the optimization algorithms, the inversion is halted when the energy E drops below a specified value $E_{\min}$. Theoretically, the choice of $E_{\min}$ could be made to reflect the precision of drawdown measurements, but in practice, oversimplification of the conceptual and numerical models usually contributes greatly to the discrepancy between modeled and observed drawdowns. Hence $E_{\min}$ is generally chosen rather heuristically, by requiring that the corresponding match between model and observed drawdowns is deemed 'good enough' by the user.

3.3.1 Optimization Algorithms Considered

The downhill-simplex and direction-set methods [Press *et al.*, 1986] both choose new values of $\mathbf{P}$ by interpolating or extrapolating toward lower values of E . In the downhill-simplex method an $(n + 1)$ -sided 'amoeba' flows across the n -dimensional parameter space until it finds a minimum value of $E(\mathbf{P})$. In the direction-set method a set of n orthogonal directions that span the n -dimensional parameter space is chosen randomly, then successive one-dimensional minimizations are done along each direction. For both these methods, computation time increases dramatically as the the number of unknown parameters n increases.

In contrast to the above methods, which make 'intelligent' choices for the values of $\mathbf{P}$ to try, simulated annealing [Metropolis *et al.*, 1953] tries new values of $\mathbf{P}$ randomly. The energy E' obtained using parameters $\mathbf{P}' = \mathbf{P} + \Delta\mathbf{P}$, where $\Delta\mathbf{P}$ is a random vector, is compared to the energy E obtained with the original $\mathbf{P}$. If $E' < E$, then $\mathbf{P}'$ replaces $\mathbf{P}$ as the current best set of parameters, another random $\Delta\mathbf{P}$ is chosen and the procedure is repeated. If $E' > E$, the $\mathbf{P}'$ might replace $\mathbf{P}$, with the probability of replacement given by

$$e^{(E - E')/\tau}, \quad (3.6)$$

where τ is a parameter known as the temperature, which determines how difficult it is to accept an increase in energy. Both $|\Delta\mathbf{P}|$ and τ start large and decrease during the course of the inversion. Thus early in the inversion, highly varied attractors are tested and it is easy to get out of local minima of the energy function. Later, when E is smaller, subtle changes in attractors are tested, and minima are not escaped easily.

Simulated annealing seems to work well for hydrologic inversions [e.g., Long *et al.*, 1991; Datta-Gupta *et al.*, 1994], and it has an advantage over the previously described methods in that computation time does not directly increase with dimension n . However, as energy E decreases, more and more unaccepted values of $\mathbf{P}$ are tried, making the method inefficient. An approach known as simplex annealing [Press and Teukolsky, 1991] combines features of the downhill-simplex method and simulated annealing, in an effort to improve efficiency by making more intelligent choices for new values of $\mathbf{P}$ while at the same time including a random component to maintain the ability to jump out of local minima. This method appears very promising.

To ensure that an IFS converges to a finite attractor all of whose points lie within the unit square, the restrictions on the components of $\mathbf{P}$ given in Equations (2.7) and (2.8) are imposed. This is easily done when simulated annealing is used, by simply rejecting any trial $\mathbf{P}'$ that does not satisfy Equations (2.7) and (2.8) and using a different random $\Delta\mathbf{P}$ to create another trial $\mathbf{P}'$. This rejection algorithm cannot be so easily accommodated in the other optimization algorithms because trial values of $\mathbf{P}$ are chosen intelligently rather than randomly. Instead of rejecting a trial value of $\mathbf{P}$ entirely, the components of $\mathbf{P}$ violating Equations (2.7) or (2.8) are set to the bounding values. This approach has not been totally satisfactory, because the optimization algorithm tends to get stuck in corners of parameter space (especially for artificially simple synthetic problems). Further work to improve this procedure would be useful, because the addition of intelligence to the choices of $\mathbf{P}$ is a highly desirable feature.

The incorporation of the diffusivity optimization depends on the optimization algorithm chosen. Using Simulated Annealing or Simplex Annealing, in which the value of E generally decreases as the inversion progresses, but can also increase in the short term, a diffusivity optimization is done each time the value of E reaches a new low. For the direction-set method, a diffusivity optimization is done after each one-dimensional optimization along a given direction is completed.

3.3.2 Assessing Optimization Algorithms with Synthetic Energy Surfaces

In order to study how various optimization algorithms work, it is useful to construct an objective function that is related to the unknown parameters $\mathbf{P}$ in a very simple way. Then forward calculations are very quick and the entire optimization process takes only a few minutes, enabling many optimizations to be done under different conditions, and the

results compared.

A very simple well-test could be designed, which would require only a coarse discretization of space and a few time steps to simulate, making each forward calculation fast, but an even simpler approach is to eliminate any numerical simulation and create an objective function which is an analytical expression of the unknown parameters. One convenient method is to define the objective function as a polynomial function of the vector $\mathbf{P}$. For a two-dimensional $\mathbf{P}$, the value of the objective function for a range of $\mathbf{P}$'s forms a two-dimensional energy surface, which may be plotted as a contour map, as shown in Figure 3.4 for the objective function given by (D. Vasco, personal communication, 1993)

$$E(x,y) = 4x^2 - 2.1x^4 + 0.333x^6 + xy - 4y^2 + 4y^4. \quad (3.7)$$

With such an energy surface, the progress of the optimization can be directly observed by tracking the trial values of $\mathbf{P}$ on the surface. The energy surface given by Equation (3.7) has a minimum value of $E < -1$, which occurs in two places, four local minima ($E \approx -0.3$ and $E \approx 2$), and two local maxima, providing several interesting features for the optimization algorithms to deal with. If the stopping criterion for the inversion is chosen as $E_{\min} = -1$, a successful optimization will converge to one of the two global minima, rather than getting stuck in one of the local minima. An efficient optimization will find the global minimum without a great number of wasted steps.

Figures 3.5 through 3.8 illustrate the behavior of the four optimization algorithms available in the IFS inverse method as they search for the minimum of the energy surface defined by Equation (3.7). For each algorithm several different starting points (shown as grey dots) and random seeds have been used. In each frame, the white dots show all the trial values of parameters picked during the inversion, the dots which are connected by line segments show the trial values which are accepted during the inversion, and the black dot identifies the final parameter values returned by the inversion.

Figure 3.5 illustrates the direction-set method, which works very simply for two-dimensional minimizations. It picks a direction at random, and does a one-dimensional minimization along that direction. From the point which yields the minimum energy, it then does a one-dimensional minimization in the orthogonal direction. From the new minimum energy point, it does a one-dimensional minimization in the original direction. This procedure continues until a point is found which yields the minimum energy along both directions. The first frame of Figure 3.5 shows an inversion starting (and remaining

Figure 3.4. Energy surface for a two-dimensional polynomial objective function.

stuck) in a deep local minimum. None of the trial parameter values in either direction yield a lower energy than the initial parameters do, so none are accepted. Several other inversions were done starting from this deep local minimum, using different random seeds to determine the direction along which to minimize, but all failed to escape the minimum. The second through fourth frames show inversions that start in the same shallow local minimum, but use different random seeds. The second and third frames show successful inversions, which end when values of $E < E_{\min}$ are found. The final frame shows an inversion which gets stuck in a deep local minimum. It is apparent that the direction-set method is not a reliable optimization technique for energy surfaces with relatively deep local minima, as a successful inversion requires not starting in a deep local minimum, and picking a good direction in which to minimize, neither of which can be guaranteed without having detailed knowledge of the energy surface.

Figure 3.6 illustrates the downhill-simplex method. In this method, a two-dimensional inversion starts with a set of three points, known as a simplex, shown in grey. The user picks one initial point and a scale factor describing how far apart the points of the

Figure 3.5. The search for a minimum of the objective function using the direction set method. The grey point is the starting point for the search and the black point is the final point. Points connected by lines are accepted points.

Figure 3.5. continued.

simplex should be, then the remaining points of the simplex are chosen at random. In some frames of Figure 3.6, all three points of the simplex do not fall within the range of the plot. During the optimization, the simplex is extended, contracted, and reflected, in search of lower energy values. The constraint of always moving in orthogonal directions, which seemed to hinder the direction-set method, is removed here, but the simplex still tends to get stuck in local minima, as shown in the second and fourth frames. It is important to specify the initial size of the simplex as bigger than the extent of local minima features, but without knowledge of the characteristic length scales on the energy surface, this is difficult to do.

Figure 3.7 illustrates simulated annealing. All of the frames show inversions that converge, and in general, one of the major strengths of simulated annealing is its ability to escape local minima, making the starting point of the inversion nearly irrelevant. The number of trials tends to be much larger than for either the direction-set or downhill-simplex method, although there is a great deal of variability in the number trials required. In the first frame, convergence is quite rapid, but it is clear that the parameter space has not been thoroughly sampled, and rapid convergence has been a matter of luck. The second frame shows an inversion with reasonable coverage in the central portion of the parameter space, and relatively rapid convergence. The third and fourth frames show more typical simulated annealing results, involving many trials, and accepted parameter values for energies well outside the local minima. The third frame shows an inversion which starts in the upper right shallow local minimum, takes big steps over much of the parameter space early on, spends a lot of time in the deep local minimum in the upper right, then finally reaches the upper global minimum. In the fourth frame the inversion starts at the local maximum in the lower left quadrant, meanders over most of the low-energy region, then hones in on the lower global maximum. In both cases, the steps between accepted trial values are large early in the inversions, and steadily become smaller as the inversion proceeds. This shortening of steps is a consequence of the decreasing temperature τ in Equation (3.6), and smaller parameter increments $|\Delta P|$ tried at the later stages of the inversion. The initial values and rates at which τ and $|\Delta P|$ decrease can therefore determine how successful the inversion will be. Overly large values of these parameters lead to highly inefficient inversions in which almost every trial is accepted (if τ is too big) or a region with low energy is abandoned (if $|\Delta P|$ is too big). Overly small values of τ or $|\Delta P|$ (or values that decrease too rapidly) minimize the random character of simulated annealing, and may lead to getting

Figure 3.6. The search for a minimum of the objective function using the downhill simplex method. The grey points are the starting points for the search and the black point is the final point. Points connected by lines are accepted points.

Figure 3.6. continued.

stuck in local minima.

Figure 3.8 illustrates simplex annealing, which is designed to combine the intelligence of the downhill simplex method with the random features of simulated annealing that make it more robust. From the examples shown in Figure 3.8 it is apparent that simplex annealing is reasonably successful in meeting these goals. The first frame shows an inversion which nearly gets stuck in the upper left deep local minimum, but manages to escape and find the nearby global minimum. The inversion shown in the second frame samples much of the low-energy region of parameter space, before converging at the lower global minimum. Again, a large number of trials are clustered near a local minimum (this time in the lower right corner) before the global minimum is found. Both the third and fourth frames shows inversions in which only a portion of the parameter space is sampled ($y > 0.4$), but within that region the inversion proceeds efficiently. As in simulated annealing, simplex annealing requires a reasonable temperature schedule to work well.

In conclusion, the simple two-dimensional energy surface studies have shown that there are strengths and weaknesses inherent in all the optimization algorithms considered. The random methods (simulated annealing in particular) tend to require far more trials, but are more robust in that they don't get stuck as easily. It is important to remember that typically very little is known about the structure of the energy surface (or hyper-surface for higher dimensional inversion problems), making it difficult (and perhaps even counter-productive) to use optimization algorithms that rely on special features of the energy surface, such as the absence of deep local minima.

Figure 3.7. The search for a minimum of the objective function using simulated annealing. The grey point is the starting point for the search and the black point is the final point. Points connected by lines are accepted points.

Figure 3.7. continued.

Figure 3.8. The search for a minimum of the objective function using simplex annealing. The grey points are the starting points for the search and the black point is the final point. Points connected by lines are accepted points.

Figure 3.8. continued.

3.3.3 Visualization of the Energy Surface for a Simple Heterogeneity

While the polynomial objective function described in the previous section provides an efficient means of illustrating the behavior of optimization algorithms, it is reasonable to ask if the energy surface shown in Figure 3.4 has any resemblance to an energy surface for an IFS-based hydrologic inversion. In order to investigate this issue, an extremely simplified inversion can be constructed for the heterogeneity shown in Figure 3.3a, by assuming that the location of one end of the linear high-transmissivity feature is known. The optimization searches for the location of the other end, which is specified by its x and y coordinates, forming a two-dimensional vector $\mathbf{P}$. Synthetic well-test data is created by numerically simulating a well test in which water is pumped from the central point in Figure 3.3a and drawdowns are calculated at the four surrounding points. The objective function is then given by Equation (3.5), where the drawdowns h_o are calculated using the high-transmissivity feature as shown in Figure 3.3a, and the drawdowns h_c are calculated using a trial location for one end of the high-transmissivity feature, as shown in Figure 3.9.

Figure 3.10 shows the energy surface created by varying the location of the end of the high-transmissivity feature over the entire well field. The strong minimum in the region near the actual location is a good indication that this simple inversion problem is relatively well posed. However, the striking reflection of the well field in the energy surface as a series of localized maxima is a vivid reminder of the limited, even distorted, picture of the subsurface provided by the observations available during a well test.

3.4 INTERPRETATION OF RESULTS

3.4.1 Alternate Displays of Hydrologic Property Distributions

There are several ways to display the transmissivity distribution returned by the IFS inversion method, as shown in Figure 3.11. The upper frame shows the attractor, whose shape is controlled by the parameters which are optimized by the inversion. To create a heterogeneous transmissivity distribution for the simulation of a well test, the attractor is superimposed on the lattice used to discretize space, and the points in the attractor either increase or decrease the transmissivity of the lattice element nearest them, as described in Section 3.1. The middle frame shows the resulting lattice, in which the transmissivity of each element is proportional to the thickness of the element. The lower frame shows the transmissivity distribution of the numerical model as a color-coded image, with bluer shades corresponding to higher transmissivities.

Figure 3.9. Several of the trial transmissivity distributions for an $n = 2$ dimensional inversion (solid line segments), and the correct transmissivity distribution (dashed line segment). The black dots show the well locations. The (x,y) coordinates of the moving end of the line segment are determined by the two unknown parameters of the inversion.

The attractor itself is the fundamental result of the inversion, but is the least useful display in terms of understanding the hydrology of the system. The lattice representation gives a direct view of the flow problem being solved by the numerical model, but the color-coded image provides a clearer representation of how the numerical model represents a heterogeneous porous medium.

The algorithm for creating a color-coded or grey-scale image from the lattice distribution of transmissivities is quite simple, and is illustrated in Figure 3.12. A diamond is drawn centered on each lattice element, with the diagonal length of the diamond equal to the length of the element. The diamond is filled in with a grey-scale intensity proportional to element transmissivity. The upper frame of Figure 3.12 shows part of a lattice, with just a few of the diamonds drawn, to illustrate the technique. As shown in the lower frame of Figure 3.12, this algorithm fills up space with shaded diamonds wherever the lattice spacing

Figure 3.10. The energy surface created by varying the location of one end of the high-transmissivity feature over the entire region shown in Figure 3.9. The white dots show the locations in parameter space where the end point of the high-transmissivity feature coincides with a well. The black dot shows the location in parameter space which produces the correct transmissivity distribution (the dashed line in Figure 3.9).

is uniform, but in regions where lattice spacing increases, the algorithm leaves gaps. The gaps are filled in by averaging transmissivity values of adjacent elements. The user can choose either arithmetic, harmonic, or geometric averaging. For color displays, color hue can easily replace grey-scale intensity, as illustrated in Figure 3.11.

3.4.2 Analyzing an Ensemble of Solutions

In contrast to the energy surface shown in Figure 3.10, which has a well-defined minimum, a typical hydrologic inversion with more unknown parameters will have an

 

Figure 3.11. Various ways to represent the results of an inversion. a) the attractor itself, a set of points (in this image blue points increase transmissivity and red points decrease transmissivity); b) TRINET lattice with element thickness proportional to transmissivity; and c) color-coded plot of transmissivity distribution.

Figure 3.12. Illustration of the algorithm used to construct the grey-scale image of transmissivity distribution. a) a lattice with just a few diamonds drawn; b) a lattice with all the diamonds representing elements drawn, the remaining gaps will be filled in by averaging adjacent transmissivity values.

energy surface with more than one minimum, implying that the inverse problem does not have a unique solution. One way to address this problem is to solve the inverse problem several times, using different starting points, different optimization algorithms, or different random seeds, then compare the ensemble of solutions. Variations in transmissivity which are shared by all members of the ensemble are likely to represent real features of the system, which have a strong impact on the pressure transients. In contrast, variations which appear in only one or a few solutions are likely to be spurious, and identify regions where there is insufficient data to resolve heterogeneity. The ensemble analysis can be simply a visual inspection of the different transmissivity distributions or it can be a more formal statistical process.

One simple statistical technique is to create the mean or median transmissivity distribution from the ensemble of transmissivity distributions. The mean transmissivity distribution is generated by calculating the mean transmissivity $\bar{T}_j$ of the j th lattice element over the ensemble of inversions, then displaying all the $\bar{T}_j$ values on one lattice. For an ensemble of n inversions, the mean transmissivity of the j th element is given by

$$\bar{T}_j = \frac{1}{n} \sum_{k=1}^n T_{j,k} \quad (3.8)$$

where $T_{j,k}$ is the transmissivity of the j th element in the k th member of the ensemble. The median transmissivity distribution is generated by determining the median transmissivity $\hat{T}_j$ of the j th lattice element for the ensemble of inversions, then displaying all the $\hat{T}_j$ values on one lattice. For an ensemble of n inversions, the median transmissivity of the j th element is determined by ordering the n values of T_j from smallest to largest, then taking the mid-ranked value to be $\hat{T}_j$. Features which are common to most members of the ensemble of solutions will be emphasized in the mean or median distributions, whereas features which only appear in a few solutions will be damped out.

The variance of the transmissivity distribution also provides information on the reliability of the results of an inversion. For an ensemble of n inversions, the variance of the j th element is defined as $\overline{T_j^2} - \bar{T}_j^2$, where $\bar{T}_j$ is defined in Equation (3.8) and the mean square-transmissivity $\overline{T_j^2}$ is given by

$$\overline{T_j^2} = \frac{1}{n} \sum_{k=1}^n T_{j,k}^2 \quad (3.9)$$

The square root of the variance, the standard deviation, for each element is then plotted on

one lattice. In general, regions of high standard deviation identify regions to which the well-test data is not sensitive, and may be used to guide the design of future well tests or the drilling of additional wells.

An example of the ensemble analysis is given in Section 4.1. One of the surprising outcomes is how much better visual inspection works to identify common features of multiple inversions than do the formal statistical methods. This suggests that more formal pattern-recognition algorithms might prove worthwhile to investigate.

3.5 CONSTRAINING THE INVERSION WITH GEOLOGICAL OR OTHER INFORMATION

It is apparent from the preceding sections that to use the IFS inversion method one must specify a number of parameters that are not modified during the course of the inversion, but rather control the way the inversion operates. These parameters, known as control parameters, include such choices as the design of the lattice, the scale factor to map the attractor to the lattice, the number of affine transforms k , which components of the affine transforms may vary, the parameters of the map from attractor to property distribution, and the total number of attractor points M_0 . Choosing the control parameters provides an opportunity to condition the inversion on geological or other additional information, so that it will produce a model that is consistent with all known information about the system, as well as matching the hydrologic response.

Lattice design. The overall hydrogeological conceptual model of a site provides the primary constraints on the lattice design, including the far-field boundary conditions (closed, constant pressure, or far enough away to not be felt) and the number of layers and lateral resolution required to represent the suspected type of heterogeneity. If a preferred flow direction is known (e.g., direction of a regional fracture set, paleoflow direction in a fluvial system) lattice elements may be aligned along it.

Scale factor. The portion of the lattice to which the attractor is mapped is determined by the scale factor. The most common situation is to make the scale factor large enough to encompass the well field, on the grounds that this is the only part of the system where well-test data provides enough information to resolve heterogeneities. However, if a particular sub-region of the well field were suspected to contain unique features (e.g., based on wellbore lithological information), a smaller scale factor could be used to limit the attractor points to that region.

Affine transforms. As described in Chapter 2, the fractal dimension of the attractor tends to increase with k , the number of affine transforms composing the IFS. Even without a formal determination of the fractal dimension of the features of a site, one often has an intuitive notion of the sort of heterogeneities to be expected that can be associated qualitatively with fractal dimension, leading to a reasonable choice for k . Furthermore, with the construction of the affine transform matrices as rotation matrices, one can choose a small value of $|\Delta P|$ to limit the variability of the rotation angle θ , so the near-linear features of low- k attractors can have preferred orientations.

The Mapping Algorithm. The mapping algorithm provides a key way to condition the inversion with hydrological information. As described in Section 3.1, the step map and distributed map may create very different property distributions for a given attractor, with the step map generally providing sharper property variations, as shown in Figure 3.2. While a diffuse property variation can be achieved with the step map, by an uneven distribution of attractor points, a sharp property distribution cannot be achieved by the distributed map, unless the value of s is very small, making the step map the practical choice for situations in which the user does not want to impose any bias on the nature of the heterogeneity returned by the inversion. By choosing the sign (for the additive algorithm) or magnitude (for the multiplicative algorithm) of the transmissivity increment ΔT , one controls whether the inversion looks for permeability barriers or fast paths. If it is not known which feature is more important for a given problem, inversions may be done both ways. Which method performs better may provide valuable insight into the hydrological behavior of the system.

Number of attractor points. The total number of attractor points M_0 determines the number of generations used to construct the attractor (Equation (2.2), which in combination with the scale factor, determines the resolution of heterogeneity. If a low-resolution picture is desired (which would be appropriate if there are only a few observation wells, or broad regions with different permeabilities are suspected), a low value of M_0 may be specified, along with the distributed map and a large value of s , to create a heterogeneity composed of a few broad regions of increased or decreased permeability.

4. INVERSION OF SYNTHETIC DATA

The only direct way to check if a hydrologic inverse method works is to generate synthetic well-test data from a known model and see if the inversion recovers the hydrologic property distribution of the model. In the first two sections of this chapter, models containing very simple heterogeneities are used, to clearly illustrate how the inversion works. To more fully test the method, more realistic synthetic data is considered in the final two sections, first by using models that represent geologically realistic heterogeneities, then by including noise in the pressure-transient data.

4.1 LINEAR HIGH-TRANSMISSIVITY FEATURE

The first synthetic problem is a well test conducted in an aquifer with a single highly permeable linear feature, which might represent a buried stream channel or the trace of a conductive fault. The transmissivity of the linear feature is about 500 times greater than the background value and its storativity is unchanged from the background value. The transmissivity distribution and the lattice used to create the synthetic well-test data are shown in Figure 3.3b.

As described in the Section 2.2.1, a linear heterogeneity can be described by an IFS with $k = 2$ of the form

$$f(A) = g_1(A) \cup g_2(A), \quad (4.1)$$

where

$$g_i(x) = 0.5 I x + b_i. \quad (4.2)$$

This IFS has only four parameters, the components of b_1 and b_2 , which determine the length and orientation of the line segment. The attractor shown in Figure 3.3a was created using an IFS with P given by Equation (4.2) with $b_1 = (0.35, 0.45)$ and $b_2 = (0.19, 0.19)$, and a total of $M_0 = 1024$ attractor points. Using the additive algorithm with $\Delta T = 10T_0$ produces the transmissivity distribution shown in Figure 3.3b. During the well test, a central well was pumped at a constant rate and transient drawdowns were calculated for four surrounding observation wells. The head was held constant at the outer boundary of the lattice. Well locations are marked by solid circles in Figure 3.3. Figure 4.1 shows the transient drawdowns calculated for this transmissivity distribution (the synthetic data), and the drawdowns that would occur for a uniform medium, for comparison. The effect of the high-transmissivity feature is clearly seen in the earlier, larger response of the upper well in Figure 4.1.

Figure 4.1. Transient drawdowns at the four observation wells for synthetic problem 1. The arrangement of the plots on the page follows the locations of the observation wells in the well field.

4.1.1 Inversions with Four Unknown Parameters

Because the synthetic hydrologic data was created using an IFS, it is straightforward to specify a very 'easy' problem for the IFS inversion: use the same values of the control parameters (T_0 , S_0 , ΔT , ΔS , M_0 , k , etc.) as were used to create the data, then, if the inversion can find the correct values of $\mathbf{P}$, the resulting model will be identical to that used to create the synthetic data, and the energy E will be identically zero. For inversions with $k = 2$ affine transforms in which only the components of the vectors $\mathbf{b}$ vary, there are $n = 4$ unknown parameters, and all the trial attractors are line segments, as shown in Figure 2.5a. Table 4.1 summarizes the results of six such inversions done using simulated annealing with different random seeds; the attractors found for the six cases are shown in Figure 4.2.

Table 4.1. Synthetic problem 1 inversions with $k = 2$, $\mathbf{b}$'s only varying, and $E_{\min} = 3.6$.

Case	Number of Forward Calculations	Number of Accepted Attractors	$\mathbf{P}$ ($\mathbf{b}_1, \mathbf{b}_2$)	E
1A	184	21	(0.29,0.47), (0.27,0.25)	3.2
1B	169	43	(0.20,0.20), (0.36,0.46)	2.8
1C	449	67	(0.36,0.46), (0.19,0.20)	0.3
1D	387	50	(0.21,0.21), (0.33,0.41)	1.5
1E	244	35	(0.19,0.18), (0.34,0.45)	1.7
1F	316	47	(0.28,0.26), (0.17,0.42)	3.4
Mean‡	292	44	(0.22,0.22), (0.31,0.45)	2.2
Standard deviation‡			(0.04,0.03), (0.07,0.02)	
Correct $\mathbf{P}$			(0.35,0.45), (0.19,0.19)	10^{-10}
			(0.19,0.19), (0.35,0.45)	1.1
Uniform medium				46

CPU time per iteration is 10 sec on a Solbourne 500 series workstation

‡order of $\mathbf{b}_1$ and $\mathbf{b}_2$ interchanged for Cases A and C before mean or standard deviation calculated

In all cases, the initial annealing temperature was $\tau = 3.6$, the initial random increment in parameters had $|\Delta \mathbf{P}| = 0.6$, τ and $|\Delta \mathbf{P}|$ were decreased 1% each time a trial attractor was accepted, and the inversion was halted when $E \leq E_{\min} = 3.6$. For comparison, the energy for a uniform medium with no attractor is $E = 46$ and the energy for the first attractor tried, a horizontal line segment through the center well, is $E = 860$. Figure 4.3 shows the energy variation over the course of the inversion for Case 1E. The energy decline for accepted iterations is far from monotonic,

Figure 4.2. The final attractors for six inversions of synthetic problem 1, using IFS's with $k = 2$ with only the $\mathbf{b}$ terms of the affine transforms varying. Well locations are marked with open circles.

reflecting the relatively large value of τ being used. Figure 4.1 shows the calculated drawdowns versus time for the final iteration of Case 1E, which yields an energy $E = 1.7$. The drawdowns returned by the inversion are deemed to match the key features of the synthetic data adequately, in effect justifying the choice of $E_{\min}$ *a posteriori*. Four of the six attractors shown in Figure 4.2 closely match the input attractor (Figure 3.3a), whereas 1A and 1F differ somewhat, illustrating the variability in transmissivity distribution that yields essentially the same well-test response. When interpreting the standard deviation values given in Table 4.1, note that for the present affine transforms, varying the value of a component of $\mathbf{b}$ from 0.0 to 0.5 moves the end of the attractor all the way across the unit square (which moves the end of the high-transmissivity feature all the way across the region shown in Figure 4.2). Hence, a standard deviation of 0.05

Figure 4.3. Energy variation during the inversion for Case 1E. The minimum energy so far is shown as a dotted line in both frames.

represents an uncertainty of 10% in the location of that end of the high-transmissivity feature.

Of the attractors shown in Figure 4.2, the two that least resemble the correct transmissivity distribution (1A and 1F) are in fact the two with the highest energy, suggesting that specifying a smaller value of $E_{\min}$ would yield a more unique attractor. While this is true in the present case (the four inversions which yield $E < 3$ return $\mathbf{P}$'s with a standard deviation of only (0.01,0.01),(0.01,0.02)), using an overly small a value of $E_{\min}$ can be problematical. For real-world problems, in which the mathematical model is generally an extremely simplified representation of reality and well-test data contains noise, using a relatively large value of $E_{\min}$ ensures that effort spent during the inversion is used to match the main features of the drawdown curves, rather than small variations in observed data which may not reflect the overall hydrologic behavior of the system, or small variations in calculated data which are due to the discretization of the problem into finite elements. For synthetic data, instrument noise and conceptual-model errors can be eliminated, but computer round-off error cannot, so even in this case an overly small value of $E_{\min}$ can be counterproductive. For example, an attractor given by $\mathbf{P} = (0.19, 0.19), (0.35, 0.45)$, which is mathematically identical to the correct attractor $\mathbf{P} = (0.35, 0.45), (0.19, 0.19)$, yields an energy $E = 1.1$, because a few attractor points located nearly midway between lattice elements are mapped to different elements. Hence, specifying a value of $E_{\min} < 1.1$ would require that effort be spent during the inversion to reproduce round-off errors rather than hydrologic behavior.

4.1.2 Inversions with Twelve Unknown Parameters

For a less constrained inversion, all entries of the affine transforms are allowed to vary, increasing the dimension of the parameter space from $n = 4$ to $n = 12$. As shown in Figures 2.5b and 2.5c, the trial attractors are no longer constrained to be line segments. As before, six inversions were done using simulated annealing with $E_{\min} = 3.6$, using different random seeds. The range of computer times used was about the same as before; the final attractors are shown in Figure 4.4. In contrast to the previous case (Figure 4.2), there is now significant variability among the attractors. All the attractors succeed in identifying a high-transmissivity channel between the middle and upper wells, but most show fictitious high-transmissivity channels elsewhere as well. A careful examination of Figure 4.4 indicates that none of the spurious high-transmissivity channels are located along pathways connecting the pumping well and the observation wells. The model can include these spurious high-transmissivity channels and still yield a low energy because the observation-well drawdowns are not very sensitive to these regions of the model.

Figure 4.4. The final attractors for six inversions of synthetic problem 1, using IFS's with $k = 2$ with all parameters of the affine transforms varying.

This insensitivity is a common problem when analyzing well tests involving a single pumping well and a limited number of observation wells, and doing multiple inversions is a powerful technique for identifying regions for which the well test provides no information. Rather than indicating a failure of the inversion method, non-uniqueness illustrates the limited nature of the information contained in the well-test response. The concept of assessing the information content of well-test (and tracer-test) data has been formalized by Vasco *et al.*, [1995], who use a sensitivity matrix to identify regions to which the observed data is most sensitive.

Figure 4.4 suggests that the response at an observation well is most sensitive to the region directly between the pumping well and observation well. This observation has been demonstrated mathematically by Oliver [1993] for heterogeneous media in which variability in $\ln T$ or S is small, using Frechet derivatives. Therefore, a straightforward way to create well-test data that is sensitive to larger areas of the aquifer is to use more observation wells. Unfortunately, drilling many wells may be economically or physically impossible. An alternate approach is to do a series of flow tests using different wells as the pumping well, as shown schematically in Figure

4.5, and then combine all the drawdown responses in the objective function.

Figure 4.5. A schematic diagram showing the regions of an aquifer in which heterogeneities tend to have the most affect on well-test results; these are the regions directly between pumping wells and observation wells.

By visually filtering out those features not common to all the attractors in Figure 4.4, one can obtain a reasonable representation of the actual high-transmissivity feature. This visual filtering operation can be formalized by looking at the mean of the transmissivity distributions returned by multiple inversions. For the simple relationship between parameters $\mathbf{P}$ and attractors

for the case in which only the b 's vary (i.e., the b 's determine the end points of the line-segment attractors), the mean of the b 's themselves was calculated (Table 4.1). With more general affine transforms, this approach is impractical, and it is preferable to take the mean of the returned transmissivity fields directly. Figure 4.6 shows the transmissivity distributions for each of the six inversions, corresponding to the attractors shown in Figure 4.4. Figure 4.7 shows the mean transmissivity distribution, formed by calculating the mean transmissivity $\bar{T}$ of each lattice element over the six inversions. The mean transmissivity distribution compares favorably with the actual distribution (Figure 3.3b), although the spurious high-transmissivity channels are still apparent. If the spurious channels represent random errors, averaging over more inversions should minimize their effect. The mean transmissivity distribution for 30 inversions, also shown in Figure 4.7, better replicates the synthetic data, supporting this hypothesis. The standard deviation distributions for 6 and 30 inversions are also shown in Figure 4.7. The standard deviation of each lattice element is given by $(\bar{T^2} - \bar{T}^2)^{1/2}$ where $\bar{T}$ and $\bar{T^2}$ are the mean transmissivity and mean square-transmissivity, respectively, of that lattice element. Regions of high standard deviation are concentrated both around the high-transmissivity channel and in the regions shown unshaded in the upper left frame of Figure 4.5. The high standard deviations around the channel arise because different inversions put the channel in slightly different locations. The remaining regions of high standard deviation indicate the regions to which the well-test data are not sensitive. In general, all regions of high standard deviation identify beneficial locations for placing additional wells for future well tests.

Figure 4.6. The transmissivity distributions for the six inversions of synthetic problem 1 which used twelve unknown parameters. Element thickness is proportional to T/T_0 .

Figure 4.7. The mean and standard deviation of the transmissivity distribution for the six distributions shown in Figure 4.6, and for 30 inversions all using the same parameters, but different random seeds. Element thickness is proportional to T/T_0 .

4.2 SQUARE ZONE OF CONTRASTING TRANSMISSIVITY AND STORATIVITY

The second synthetic problem considers an aquifer with a central square region whose transmissivity and storativity are either 100 times greater ('high anomaly') or 100 times less ('low anomaly') than the values of the surrounding area. Six wells surround the anomaly, as shown in Figure 4.8.

Figure 4.8. Model for synthetic problem 2, showing the lattice, well locations (solid circles), and the central square anomaly, which may have transmissivity and storativity either 100 times greater or 100 times less than the background values. The pumping well is the middle well on the left.

One well is pumped and transient drawdowns are measured in the other five. Head is held fixed at the outer boundary of the lattice. Figure 4.9 shows the transient drawdowns at the observation well locations for the high and low anomalies, and for a uniform medium. Compared to the uniform medium response, the high anomaly strongly affects the drawdown curves at all observation

wells, whereas the low anomaly primarily affects the wells across the anomaly from the pumping well.

Figure 4.9. Synthetic data at the five observation wells for synthetic problem 2, compared to the response for a uniform medium. The arrangement of the plots on the page follows the locations of the observation wells in the well field.

4.2.1 High T and S Anomaly

Table 4.2 summarizes the results of three inversions with $k = 3$ done for the high anomaly, using simulated annealing with different random seeds. In each case, the additive algorithm was used with $\Delta T = 10T_0$ and $\Delta S = 10S_0$, and $E_{\min} = 1.6$. The energy for a uniform medium with no attractor is $E = 92$, the energy for the first attractor tried, the Sierpinski Gasket shown in Figure 4.10, is $E = 85$. The Sierpinski gasket is not expected to provide a good description of the square zone of contrasting properties (or for that matter of any geological heterogeneity), it is merely used as a convenient starting point for the inversion. In fact, when inverting synthetic data it is preferable not to use too good a guess for an initial attractor, to assure a rigorous test of the inverse method. (In contrast, for real data a good initial guess is generally desirable, and can provide a means of conditioning the inversion on additional information. Under some conditions it may be preferable not to impose any preconceived notion on the inversion, and either a randomly chosen or uniform initial attractor may be used.) The drawdowns for Case 2A are shown in Figure 4.11; the agreement with the synthetic data is very good. The attractors for each case, shown in Figure 4.12, all succeed in concentrating points within the anomaly.

Table 4.2. Synthetic problem 2 (high anomaly) inversions with $k = 3$, attractor points that increase properties, and $E_{\min} = 1.6$.

Case	Number of Forward Calculations	Number of Accepted Attractors	E
2A	795	71	1.4
2B	87	20	1.6
2C	2,606	181	1.2
Uniform medium			92

CPU time per iteration is 17 sec on a Solbourne 500 series workstation

Three inversions with $k = 3$ were also done for the high anomaly using attractors that decrease transmissivity and storativity. For this case an ideal attractor would have points uniformly distributed around the outside of the anomaly. Although the energies for these inversions ($E = 47$ to 58) are only about a factor of two lower than the energy for a uniform medium, the attractors, shown in Figure 4.13, all succeed in concentrating points outside the anomaly.

Figure 4.10. The initial attractor for the $k = 3$ inversions of synthetic problem 2.

Figure 4.11. Transient drawdowns for synthetic problem 2 with the high anomaly when attractor points increase properties.

An attractor generated by an IFS composed of k affine transforms tends to have k 'extreme' or corner-like points. These are the points created by repeated application of just one of the k affine transforms that make up the IFS. For example, the lower left corner point of the Sierpinski Gasket shown in Figure 4.10 results from repeated application of just one of the three affine transforms that make up the IFS. For example, the lower left corner point of the Sierpinski Gasket shown in Figure 4.10 results from repeated application of just one of the three affine transforms that make up the IFS. For example, the lower left corner point of the Sierpinski Gasket shown in Figure 4.10 results from repeated application of just one of the three affine transforms that make up the IFS. For example, the lower left corner point of the Sierpinski Gasket shown in Figure 4.10 results from repeated application of just one of the three affine transforms that make up the IFS. (All the points along the lines connecting these corner points arise from application of just two of the three affine transforms, while interior points arise from application of all three of the affine transforms). The k corner points may be thought of as pinning down the attractor's extreme values, while the rest of the attractor flows between them. This k -fold pinning is consistent with the increase in attractor fractal dimension with k observed in Figure 2.5, and implies that the attractors tend to contain k -fold features (i.e., for $k = 2$, attractors tend to be composed of line segments; for $k = 3$, triangular shapes abound, etc.). This implies that higher values of k should be used to mimic more complicated structures. In particular, it is natural to try to outline a square anomaly using an IFS with $k = 4$. The attractors for two such inversions using the multiplicative algorithm with $\Delta T = \Delta S = 0.5$ are shown in Figure 4.14.

Figure 4.14. The final attractors for two $k = 4$ inversions of synthetic problem 2 with the high anomaly, when attractor points decrease properties.

Despite the appealing shape of the attractors, the energies are still rather high ($E = 38$ for both cases) reflecting only a qualitative match to the drawdowns, as shown in Figure 4.15.

Figure 4.12. The final attractors for three $k = 3$ inversions of synthetic problem 2 with the high anomaly, when attractor points increase properties.

Figure 4.13. The final attractors for three $k = 3$ inversions of synthetic problem 2 with the high anomaly, when attractor points decrease properties.

Several inversions using the plus-minus algorithm were also done for the high anomaly, using an IFS with $k = 4$. Not surprisingly, the returned energies ($E = 6-20$) were better than for the inversions in which properties were only decreased, but worse than for the inversions in which properties were only increased. The attractors tend to concentrate the points which increase T and S within the anomaly, while putting points which decrease T and S outside it, as is illustrated in Figure 4.16.

Figure 4.16. The final attractor for a $k = 4$ inversion of synthetic problem 2 with the high anomaly, using the plus-minus algorithm. Attractor points which increase transmissivity and storativity are shown as pluses and points which decrease properties are shown as open circles. Only one quarter of the attractor points used are plotted (256 out of 1024), in order for the symbols to be more readily distinguishable.

Figure 4.15. Transient drawdowns for synthetic problem 2 with the high anomaly when attractor points decrease properties.

4.2.2 Low T and S Anomaly

Table 4.3 summarizes the results of three inversions with $k = 3$ for the low anomaly, with attractor points that decrease properties. The multiplicative algorithm was used, with $\Delta T = \Delta S = 0.5$. Although the energies ($E = 4-8$) are not as low as for the high-anomaly inversions with increased properties (Table 4.2), the drawdowns, shown in Figure 4.17 for Case 2L, reproduce the main features of the synthetic data reasonably well.

Table 4.3. Synthetic problem 2 (low anomaly) inversions with $k = 3$, attractor points that decrease properties, and $E_{\min} = 1.6$.

Case	Number of Forward Calculations when Best Energy Found	Total Number of Forward Calculations	Lowest E	E After 3000 Forward Calculations
2K	2,929	3,497	8.4	8.4
2L	10,929	13,562	5.6	9.0
2M	5,271	26,164	3.9	4.9
Uniform medium			91	

Because the energies never reached the specified value of $E_{\min} = 1.6$, an alternate stopping criterion was used, in which an inversion was halted when E did not decrease after many (usually several thousand) iterations. The attractors, shown in Figure 4.18, all succeed in concentrating the points within the anomaly.

Figure 4.17. Transient drawdowns for synthetic problem 2 with the low anomaly when attractor points decrease properties.

Figure 4.18. The final attractors for three $k = 3$ inversions of synthetic problem 2 with the low anomaly, when attractor points decrease properties.

4.2.3 Alternate Well Locations

In order to investigate the sensitivity of the inversion process to well location, inversions with $k = 3$ were done considering wells located inside and outside the anomaly, in both regular and irregular patterns, as shown in Figure 4.19. Table 4.4 summarizes the results of the inversions and indicates that in all cases the IFS inversion method matches the hydrologic response. The high-anomaly inversions use an attractor which increases properties using the additive algorithm and $\Delta T = 10T_0$ and $\Delta S = 10S_0$. The low-anomaly inversions use an attractor which decreases properties using the multiplicative algorithm and $\Delta T = \Delta S = 0.5$.

Table 4.4. Synthetic problem 2 inversions for various well locations. Three $k = 3$ inversions were done for each problem, using different random seeds. In all cases $E_{\min} = 1.6$.

Well Locations	Anomaly	Number of Forward Calculations†	E
Outer	High	1,900-2,900	1.3-1.5
	Low	6,000-13,200	0.8-1.4
Inner	High	700-2,600	1.2-1.6
	Low	6,100-12,400	1.3-1.6
Random	High	1,100-2,100	0.9-1.6
Random‡	High	500-1,100	1.0-1.6

†Rounded to nearest hundred

‡Alternate pumping well, location shown in Figure 4.19.

The attractors (not shown) successfully concentrate points within the anomaly. Intuitively, one would expect that if an anomaly produces a small signal in the drawdown curves (for example, because it has similar properties to the surrounding area, or is of very small or very large spatial extent compared to the dimensions of the well field), the IFS inversion method would have less success identifying it.

Figure 4.19. The well locations used for the inversions of synthetic problem 2 that are summarized in Table 4.4.

4.3 GEOLOGICALLY REALISTIC HETEROGENEITIES

4.3.1 Introduction

Sections 4.1 and 4.2 illustrated the application of the IFS inversion method to synthetic data from highly idealized geologic settings. Use of more realistic synthetic data, although more expensive computationally, and less illustrative of special features of the inversion process, provides a more stringent test of the method. It is generally difficult to create realistic synthetic well-test data for the very reason it is difficult to characterize subsurface heterogeneity: variability is large, it occurs on many scales, and sampling is sparse. However, an unusual opportunity to create realistic synthetic well-test data exists at the Gypsy outcrop site in northeastern Oklahoma, where a detailed geological analysis of a highly heterogeneous fluvial sand and shale sequence known as the Gypsy formation has been done [Doyle and Sweet, 1992]. The geological analysis makes use of a road cut which extensively exposes the Gypsy formation and a suite of boreholes drilled behind the road cut. Using the results of this analysis, a detailed mathematical model of the subsurface hydrology has been created, and used to generate synthetic well-test data.

At the outcrop site, the Gypsy formation is above the water table, precluding the possibility of doing real well tests there, however at the pilot site, about 32 km (20 miles) away, the Gypsy formation lies at depths below the water table. Chapter 6 describes the analysis of a series of interference test done at the pilot site, and provides more information on the geological setting of the Gypsy formation.

4.3.2 Creation of Realistic Synthetic Data

The starting point for the creation of synthetic well-test data is a channel model of the outcrop site, developed by BP Exploration [Doyle and Sweet, 1992]. In the channel model the outcrop site is discretized into 40 X 70 X 32 blocks of dimension 20 X 20 X 2 feet[†], each of which is assigned a code number to act as a channel identifier. Figure 4.20 shows a perspective view of the channel model, including the 25 boreholes drilled behind the road cut, and four cross-section lines. Figure 4.21 shows vertical cross-sections through the channel model at the locations of the lines shown in Figure 4.20. Cross-section line 1 coincides with the road cut. Six sand channels were mapped at the outcrop site. In addition, the model contains much lower permeability flood-plain siltstones and mudstones, and flood-plain sands and crevasse complexes of intermediate permeability.

[†]The channel model was originally developed using feet as the unit of length; no conversions to meters will be done at this point.

Figure 4.20. Perspective view of the original Gypsy outcrop-site channel model. The channels and other lithofacies are identified by color.

Figure 4.21. Vertical cross-sections through the original Gypsy outcrop-site channel model. The vertical to horizontal scale ratio is 2:1. The vertical bars on the upper cross-section identify the locations at which core measurements of permeability were made. From bottom to top, the bars correspond to $y = 0, 5$, and 32 m ($0, 16$, and 105 feet), where y is the distance perpendicular to the cross-section.

The original channel model shown in Figures 4.20 and 4.21 is composed of $40 \times 70 \times 32 = 89,600$ blocks, each of which is 20 X 20 feet in planar area and 2 feet thick. Figure 4.21 shows that most variability occurs on larger scales than 20 feet in horizontal directions and 2 feet in the vertical direction. Therefore, a new lower-resolution channel model was created by lumping together sets of eight adjacent blocks (that is, blocks taken two at a time in each direction). The resulting blocks are 40 X 40 feet in planar area and 4 feet thick. The new channel model is composed of $20 \times 35 \times 16 = 11,200$ blocks. The code number (the channel or other facies identifier) of each new block is taken to be the code number that occurred most often among the original eight blocks making up the new block. In 73% of the blocks in the new model, the eight corresponding blocks of the original model all had the same code number, indicating that for these blocks no resolution is lost in using the new model. Figure 4.22 shows four cross-sections through the new model, and illustrates that overall, the character of the heterogeneity is maintained by the new lower-resolution channel model. The new model, with eight times fewer blocks, can be much more readily converted to a numerical model for doing flow calculations than the original channel model could have been.

Before the channel model can do flow calculations, it must be converted into a hydrological model, in which each block is assigned a permeability and specific storage value. Doyle [1989] has tabulated the mean and standard deviation of log-permeability for six lithofacies identified within the Gypsy formation, using measurements from 876 core samples taken at the outcrop site (Table 4.5). Some components of the channel model are identified by lithofacies (the flood-plain deposits and crevasse complexes), however the sand channels themselves are all comprised of multiple lithofacies. Doyle and Sweet [1992] identified the proportion of the various lithofacies within each of the six sand channels, as shown in Figure 4.23.

For the present exercise, only one layer of the channel model is used at a time, to create two-dimensional hydrological models. To minimize the effect of too-close boundary conditions, each layer was extended by adding 15 'dummy' blocks in the narrow (20 block) direction, making the model a 35 X 35 block square. Figure 4.24 shows two such layers through the channel model. The layer at $z = 47$ feet shows a single channel (channel 6) surrounded by flood-plain mudstones and siltstones and a crevasse splay. The layer at $z = 23$ feet shows four meandering channels (channels 1, 2, 2.5, and 3) along with a small amount of flood-plain deposits. The code numbers for the blocks at the edges of the original model (shown by vertical lines in Figure 4.24) were assigned to the dummy blocks outside the original model.

Figure 4.22. Vertical cross-sections through the new lower-resolution Gypsy outcrop-site channel model. The vertical to horizontal scale ratio is 2:1. The arrows identify the elevations of the two single-layer models used to create synthetic well-test data.

Table 4.5. Mean and standard deviation of log-permeability for various lithofacies at the Gypsy Outcrop site (permeability in millidarcies). Taken from *Doyle* [1989] except as noted.

Lithofacies ID Number	Lithofacies Description	Mean Log-Permeability	Standard Deviation
1	Cross bed	6.38	1.27
2	Soft sediment deformation	4.65	1.74
3	Ripple lamination	4.03	1.55
4	Plane bed	5.96	1.42
5	Mudstone/Siltstone	-3.79	2.09
6	Mudclast	2.40	2.70
7	Flood-plain sandstone†	-1	1
8	Crevasse complex†	0	1

†Numerical value not quoted in *Doyle* [1989]; values here estimated based on qualitative descriptions.

Figure 4.23. Lithofacies proportions of channel fill deposits at the Gypsy outcrop site, calculated from core descriptions and road-cut profiles [after *Doyle and Sweet*, 1992]. See Table 4.5 for the meaning of the abbreviated lithofacies names given here.

66666666	666766667777777777	77777777	11111111	1222222222111118888	88888888
66666666	676666666667777777	77777777	2222222	2222222242211111888	88888888
66666666	666666666666677777	77777777	2222222	2222222444411111118	88888888
66666666	666666666666667777	77777777	11111111	12222244444444411111	11111111
77777777	766666666666666777	77777777	88888888	82222444444444411111	11111111
77777777	776666666666666777	77777777	33333333	3222244444444441111	11111111
77777777	777**66666666666777	77777777	33333333	3322444444444444111	11111111
77777777	777***666666666677	77777777	33333333	3322444444444444411	11111111
77777777	7777****66666666677	77777777	33333333	3333444444444444441	11111111
77777777	7777*****6666666677	77777777	33333333	3333444444444444441	11111111
77777777	7777*****6666666677	77777777	33333333	3333444444444444441	11111111
77777777	7777*****6666666667	77777777	33333333	3333244444444444441	11111111
77777777	7777*****6666666667	77777777	33333333	3333344444444444441	11111111
77777777	7777*****6666666666	77777777	33333333	3333344444444444441	11111111
77777777	7777*****6666666667	77777777	33333333	3333244444444444444	44444444
77777777	7777*****6666666677	77777777	33333333	3333324444444422441	11111111
77777777	7777*****6666666677	77777777	33333333	3333322444444222448	88888888
77777777	7777*****66666*77	77777777	33333333	3333322244444222248	88888888
77777777	7777*****66666*77	77777777	33333333	3333332244444222248	88888888
77777777	7777*****66666677	77777777	88888888	8333333224444224418	88888888
77777777	7777*****666666777	77777777	88888888	833333332242444411	11111111
77777777	7777*****666666777	77777777	88888888	833333333224444111	11111111
77777777	77777777***66666777	77777777	2222222	2333333332244441111	11111111
77777777	77777777***66666777	77777777	2222222	2233333333244444111	11111111
77777777	77777777***66666777	77777777	2222222	2233333332244441111	11111111
77777777	77777777***66666777	77777777	2222222	22333333322444411411	11111111
77777777	77777777***666667777	77777777	2222222	2233333332244444411	11111111
77777777	77777777***666667777	77777777	2222222	2233333332244444411	11111111
77777777	77777777***666667777	77777777	2222222	2332333332244444411	11111111
77777777	77777777***666667777	77777777	2222222	23323333322444414411	11111111
77777777	77777777***666677777	77777777	33333333	3333333222444444411	11111111
77777777	77777777***666677777	77777777	33333333	3223333222444444111	11111111
77777777	77777***66666777777	77777777	2222222	222232322884411111	11111111
77777777	77777***66666777777	77777777	2222222	2222222228841111111	11111111

Symbol	Description
1	Sand channel 1
2	Sand channel 2
3	Sand channel 2.5
4	Sand channel 3
5	Sand channel 4
6	Sand channel 6 ~
7	Flood-plain mud/silt
8	Flood-plain mud/silt
9	Flood-plain sand
0	Flood-plain sand
*	Crevasse splay

Figure 4.24. Channel models for $z = 47$ feet and $z = 23$ feet. The vertical bars separate the real blocks from the added dummy blocks.

Each block in the channel model layer is then assigned a lithofacies based on its code number. For blocks representing a sand channel (numbers 1-6 in Figure 4.24), a lithofacies is assigned at random, according to the proportions shown in Figure 4.23. Although there is some suggestion of spatial correlation among the lithofacies making up a sand channel (J. Doyle, personal communication, 1992), it has not been quantified well enough to be incorporated in the present model-building procedure. For blocks representing flood-plain deposits or crevasse complex (symbols 7, 8, 9, 0, and * in Figure 4.24) the code number uniquely identifies a lithofacies. Figure 4.25 shows the lithofacies distribution for layers at $z = 47$ feet and $z = 23$ feet. Next a log-permeability value is drawn from a Gaussian distribution using the mean and standard deviation for the appropriate lithofacies. Because the model is two-dimensional, permeability is converted to transmissivity, assuming unit thickness for each layer. A uniform value of storativity is assigned to all blocks. The dummy blocks are assigned lithofacies and permeability values in the same manner as are the real blocks.

The final step is to convert the block model to a lattice that can be used by TRINET. The block center points are used to define the nodal points of the lattice. Thus each nodal point has associated with it the transmissivity of a particular block. Nearest neighbor nodal points are connected by elements whose transmissivity is calculated as the harmonic mean of the values associated with the nodes at either end of the element. Figure 4.26 shows the transmissivity distribution for the hydrologic models at $z = 47$ feet and $z = 23$ feet. The character of the heterogeneity for the two models differs greatly. The $z = 47$ model shows a single continuous high-permeability feature, in some ways similar to the first idealized synthetic case described in Section 4.1. In contrast, the $z = 23$ model shows a low-contrast short-range variability in permeability over the well field.

Note that TRINET expects spatial dimensions given in meters, whereas the channel model dimensions are given in feet. Rather than converting the round integer values of the channel model to their messy metric equivalents, values that really represent feet are simply taken to be meters, thus effectively enlarging the size of the channel model by a factor of 3.28. Furthermore, the conversion given in Appendix A between the transmissivity T_0 of TRINET elements of length L and the effective transmissivity $\tilde{T}$ of a rectangular lattice of such elements, $T_0 = \tilde{T}L$, was not applied, thus giving the model an effective transmissivity value L (≈ 40) times smaller than it should be. Recall that the goal is to study the performance of the IFS inverse method in a realistic hydrogeologic setting, rather than creating an exact representation of the Gypsy Outcrop site. The above simplifications will not detract from that purpose.

z = 47

z = 23

1111131	11153414455555555555	55555555	4566146	66111661116666665555	55555555
4111111	15611431111155555555	55555555	6411166	16116661166136616555	55555555
1111611	11111111441441555555	55555555	4111651	61161161311666611335	55555555
1141116	31116664111141155555	55555555	1165166	14646611124141516656	36615136
5555555	51141131114111145555	55555555	5555555	51616313611114246334	66336636
5555555	55141111141441161555	55555555	4334441	66116134412141116166	61634316
5555555	5558814111111111555	55555555	4344341	44441414411111311153	16666665
5555555	55588881113414411155	55555555	1443344	4311111124141111511	65666156
5555555	5558888811141144155	55555555	4444433	44141141151245443444	66661615
5555555	5558888881111111155	55555555	4444414	61441614441412411216	11166666
5555555	5558888883111141345	55555555	5411143	44111444114111113443	61364116
5555555	5558888888114111415	55555555	4113433	44413113111334344216	66646165
5555555	5558888888414141416	55555555	4443333	34344111441331111161	66166365
5555555	5558888888111311115	55555555	4313431	36131113314431311414	52131451
5555555	5558888888113411155	55555555	1144111	44141616311616611246	56666536
5555555	5558888888131111355	55555555	4141113	36434111131361511415	55555555
5555555	5558888888111418855	55555555	3443154	34333114124121611445	55555555
5555555	5558888888131118855	55555555	6413534	51643464111412111615	55555555
5555555	5558888888163311855	55555555	5555555	54411546413111611365	55555555
5555555	5558888888341143555	55555555	5555555	53164124111161143165	55555555
5555555	5558888888133331555	55555555	5555555	51444111114162141166	66646616
5555555	555888888813131555	55555555	5555555	53442443311663161514	16131166
5555555	5555555888811144555	55555555	6141166	14133141441653111166	66666136
5555555	5555555588814131555	55555555	1661111	41314411416114436166	46656541
5555555	5555555588814311555	55555555	1116411	11341431316164351661	33631616
5555555	5555555588811111555	55555555	6161611	16433413411131416666	34511416
5555555	5555555588811415555	55555555	1666166	66414144546611166466	16613136
5555555	5555555588811434555	55555555	6111111	66344164411141131166	56366116
5555555	5555555588813136555	55555555	1616116	65423111416241411146	55161361
5555555	5555555888411155555	55555555	4166446	13414434411444413166	65661155
5555555	5555555888131445555	55555555	6461141	61363414416132331166	46363646
5555555	5555558888114155555	55555555	3414144	31114411111611131266	16316116
5555555	5555558884113555555	55555555	4134311	46643541116114113356	56463134
5555555	5555888811411555555	55555555	6611116	16161511615513216665	15113615
5555555	5555888511115555555	55555555	6661211	61412666615564566616	66366646

Symbol	Lithofacies
1	Cross bed
2	Soft sediment
3	Ripple lamination
4	Planar bed
5	Mudstone/siltstone
6	Mudclast
7	Flood-plain sandstone
8	Crevasse splay

Figure 4.25. Lithofacies models for $z = 47$ feet and $z = 23$ feet, derived from the channel models shown in Figure 4.24. The vertical bars separate the real blocks from the added dummy blocks.

Gypsy Outcrop $z=47$

Gypsy Outcrop $z=23$

Figure 4.26. Transmissivity distributions for $z = 47$ feet and $z = 23$ feet, derived from the lithofacies models shown in Figure 4.25. This range of $\ln T$ (for T in m^2/s) corresponds to $\ln k$ between -8.6 and +8.4, for k in millidarcies.

4.3.3 Inversion of Realistic Synthetic Data

A synthetic well test was conducted for each layer, using the central well shown in Figure 4.26 as the pumping well and the four surrounding wells as observation wells. A constant pressure boundary condition was applied at the outermost nodes of the lattice. Figure 4.27 shows the pressure transients for the synthetic well tests, along with the pressure transients obtained using a uniform-medium model. The pressure transients for the $z = 47$ model show much greater variation between wells than do those for the $z = 23$ model, which is reflected in a higher energy for the uniform-medium model of the $z = 47$ well test. This difference is hardly surprising, considering the very different characters of the two transmissivity distributions. However, in both cases, high permeability paths between pumping and observation wells are reflected by earlier, larger pressure responses.

Three inversions of the $z = 23$ well test were done, using the same control parameters but different random seeds. The inversions used $k = 4$ affine transforms of the rotation matrix form, in which θ and b were allowed to vary, for a total of 12 unknown parameters. The step map was used with the multiplicative algorithm, and a value of $\Delta T = 1.5$. Hence the attractor identifies locations of high transmissivity. Figure 4.28 shows the three resulting transmissivity distributions, and Figure 4.29 shows one of the pressure-transient matches. The low energies returned by all the inversions indicate a good match to the main features of the pressure transients. A comparison of the returned transmissivity distributions (Figure 4.28) with the $z = 23$ transmissivity distribution (Figure 4.26) shows that high-transmissivity channels between the central well and two of the four observations wells have been correctly identified by the inversion. None of the transmissivity variations beyond the well field have been found, indicating that they do not significantly affect the pressure responses at the observation wells.

Six inversions of the $z = 47$ well test were done, three using the step map and three using the distributed map. The two types of inversions yielded comparable final energies, but transmissivity distributions of a rather different character, as shown in Figures 4.30 and 4.31. The distributed-map inversions used large values of s , the parameter which controls the extent of the effect of each attractor point, leading to smoother transmissivity distributions. A typical pressure-transient match is shown in Figure 4.32. The higher energies of the $z = 47$ inversions compared to the $z = 23$ inversions, which arise from the poorer pressure-transient matches, are due to the far greater transmissivity contrasts present in the $z = 47$ model. Despite the imperfect matches, the returned transmissivity distributions all successfully identify a high-transmissivity

channel cutting through the right side of the well field.

4.3.4 Conclusions from Realistic Synthetic Data Inversion

Two very different sorts of synthetic heterogeneities are represented by the $z = 23$ and $z = 47$ models. The fact that well-test data from both models can be successfully inverted lends significant credibility to the IFS inverse method.

The $z = 23$ model contains multiple irregularly-shaped zones with slightly different transmissivities, making it look like an uncorrelated random field. The inverse method singles out the features that have an impact on the well-test response, which are difficult to identify *a priori* by looking at Figure 4.26. Because the transmissivity contrasts are small, the pressure transients are only subtly different from those which would occur for a uniform medium, making it relatively easy to obtain a low value of energy E . Despite the small contrasts in transmissivity, multiple inversions produce similar results, indicating that these subtle variations do have a noticeable effect on pressure transients.

In contrast, the $z = 47$ model contains transmissivity contrasts of a factor of 10^7 , much larger than used in previous synthetic examples. With these large contrasts, it is difficult to get good matches to the pressure transients. However, even with relatively high values of E , the inversion is still successful in identifying the heterogeneity. The fact that multiple inversions return consistent pictures of heterogeneity for relatively large energy values (i.e., for imperfect fits) is an important, and necessary, result for application of the method to real data. When analyzing real data, it is likely that use of an oversimplified conceptual model will preclude a perfect fit to observations. Results of the $z = 47$ model support the use of the IFS inverse method under such conditions.

$z=47$ Uniform Medium $E=63$

Figure 4.27. Synthetic well-test data created using the models shown in Figure 4.26. (dots) and a uniform-medium model (lines). The arrangement of plots on the page mimics the well field layout shown in Figure 4.26.

$z=23$ Uniform Medium $E=42$

Figure 4.27. continued.

go09a E=1.61

go10 E=2.22

go11 E=2.27

Figure 4.28. Three transmissivity distributions returned by inversions of the $z = 23$ well-test data.

go10 $E=2.22$

Figure 4.29. Pressure transients for one of the inversions of the $z = 23$ well-test data. The arrangement of plots on the page mimics the well field layout shown in Figure 4.26.

go15a E=10.15

go08a E=12.99

go19 E=20.47

Figure 4.30. Three transmissivity distributions returned by inversions of the $z = 47$ well-test data, which used the step map.

 

Figure 4.31. Three transmissivity distributions returned by inversions of the $z = 47$ well-test data, which used the distributed map.

go08a $E=12.99$

Figure 4.32. Pressure transients for one of the inversions of the $z = 47$ well-test data. The arrangement of plots on the page mimics the well field layout shown in Figure 4.26.

4.4 NOISY SYNTHETIC DATA

The first idealized synthetic case, the linear high-transmissivity feature, is again examined here, but noise is added to the synthetic pressure transients before trying to match them. If the inverse method is not robust enough to match noisy data, it will be of little use in real-world applications, where noise arising from instrumentation and oversimplified conceptual models is unavoidable. Additionally, understanding the impact of different kinds of noise on the inversion process will enable more effective treatment real-world, noisy data.

4.4.1 Random Noise

To simulate the random noise arising from instrument error, normally-distributed random numbers with a mean of zero and a standard deviation of σ are added to each point of the pressure transients which serve as observed data. Figure 4.33 to 4.37 show the noisy pressure transients for five values of σ (0.1, 1, 5, 10, and 100), and the energy obtained for the correct transmissivity distribution (which would be zero for $\sigma = 0$). For $\sigma = 0.1$, the noise is barely visible, whereas for $\sigma = 100$, the signal is barely discernible. For the $\sigma = 5$ case, two different noisy pressure data sets were created, to compare the effects of different realizations of noise of the same overall magnitude.

Note that by plotting the pressure transients on a log scale, noise is much more noticeable for early-time data, where pressure changes are small. Because the calculation of the objective function also uses the log of pressure change, rather than pressure change itself, if the addition of noise makes the pressure change at a particular time negative, that point must be thrown out.

Inversions were done for $\sigma = 1, 5$, and 10 , using $k = 2$ affine transforms in which only the b 's vary, and the same control parameters used in the noise-free inversions described in Section 4.1.1. Six inversions were done for each case, using simulated annealing with different random seeds. In each case, the value of $E_{\min}$ was chosen to be slightly larger than the value of E obtained for the correct $\mathbf{P}$. Table 4.6 summarizes the calculations, including the mean and standard deviation of $\mathbf{P}$ for each case. Figure 4.38 shows the attractors returned by the individual inversions, and illustrates how a large variation between the returned attractors for a given case corresponds to a large standard deviation of $\mathbf{P}$.

Figure 4.33. Pressure transients for noisy synthetic data, with $\sigma = 0.1$. The arrangement of plots on the page follows the locations of observations wells in the well field.

Figure 4.34. Pressure transients for noisy synthetic data, with $\sigma = 1$.

Figure 4.35. Pressure transients for noisy synthetic data, with $\sigma = 5$.

Figure 4.36. Pressure transients for noisy synthetic data, with $\sigma = 10$.

Figure 4.37. Pressure transients for noisy synthetic data, with $\sigma = 100$.

Figure 4.38. Attractors returned by the inversions of noisy pressure-transient data for the linear high-transmissivity feature. The mean attractor for each case is shown as a dashed line.

The effect of the choice of $E_{\min}$ is illustrated for the $\sigma = 1$ case. While the mean values of $\mathbf{P}$ do not differ too much for the two values of $E_{\min}$, the standard deviation is notably larger for the larger value of $E_{\min}$, suggesting less certainty in the correctness of the returned transmissivity distribution. However, the average number of forward calculations required for $E_{\min} = 17$ is only one-third the number required for $E_{\min} = 15$. Hence, instead of doing just a few slow inversions with a small value of $E_{\min}$, for comparable computational effort, one can do many inversions with a somewhat larger value of $E_{\min}$, and have the benefit of comparing the multiple returned transmissivity distributions.

The impact of different noisy data sets is shown for the $\sigma = 5$ case. A few early-time points in the first realization of $\sigma = 5$ noise strongly influence the pressure matching, leading to a rather different cluster of attractors than obtained for the other cases (Figure 4.38). The corresponding standard deviation of $\mathbf{P}$ is also larger, suggesting that the inferred transmissivity distribution should be viewed cautiously.

In general, as σ gets bigger, the value of $E_{\min}$ also increases, leading to easier inversions (fewer forward calculations required), with less confidence in the correctness of the returned attractors (larger standard deviation). Although the standard deviation can be used as a guideline to judge the reliability of a set of transmissivity distributions returned by multiple inversions, it is not a foolproof indicator; noise can mimic the effect of a heterogeneity in pressure data, leading to a set of consistently erroneous attractors, with a small standard deviation.

The need to eliminate negative values of pressure change tends to bias noisy early-time pressure data to large values of pressure change, which could lead to erroneously identified high-permeability pathways. It is tempting, therefore, to simply throw out all early-time data which shows a large scatter. However, several recent studies [Oliver, 1993; Butler and Liu, 1993] have shown that early-time pressure-transient data contain most of the information on near-well-field heterogeneities, so it is important to keep as much early-time data as possible. One potential remedy to this problem, which is not addressed in the present work, would be to curve-fit the noisy observed pressure data, constraining the curve fitting procedure to produce results which are physically possible for the diffusion of a pressure signal between wells (e.g., for a constant flow rate test, pressure response must be monotonically increasing).

Table 4.6. Inversions of noisy synthetic data. Six inversions were done for each case.

σ	E_{correct}	E_{min}	Mean E	Mean $\mathbf{P}^\dagger$	Std. Dev. $\mathbf{P}$	Mean No. Fwd. Calcs.
1	13.7	15	14.5	(0.34,0.42), (0.16,0.15)	(0.02,0.03), (0.03,0.05)	12,830
1	13.7	17	15.8	(0.30,0.43), (0.19,0.18)	(0.05,0.04), (0.06,0.06)	4,210
5	25.5	26	25.4	(0.19,0.45), (0.32,0.15)	(0.12,0.02), (0.08,0.05)	1,018
5‡	44.8	45	43.9	(0.31,0.41), (0.13,0.17)	(0.03,0.02), (0.02,0.03)	984
10	37.9	38	35.8	(0.22,0.43), (0.23,0.11)	(0.05,0.02), (0.08,0.06)	178

† Correct value of $\mathbf{P}$ is (0.35,0.45), (0.19,0.19)

‡ Different noisy data

4.4.2 Systematic Noise

Using the wrong conceptual model often has the effect of introducing systematic errors into the calculated pressure transients. For example, if a leaky aquifer is modeled with impermeable upper and lower boundaries, late-time pressure changes will be consistently overpredicted. The inversion may then erroneously identify a high-permeability zone beyond the well field, in order to produce smaller late-time pressure changes. The best way to avoid such errors is to carefully construct the conceptual model, using all available information about the system. Conversely, if information on hydrologic setting is incomplete, careful comparison of calculated and observed pressure transients can provide insights into important features of the system. Thus the process of conceptual model development and hydrologic inversion need not be separate, but can proceed iteratively.

4.5 CONCLUSIONS OF SYNTHETIC-DATA ANALYSIS

In this chapter, the use of the IFS inverse method has been demonstrated by applying it to synthetic well-test data. The method has been shown to work well, in that it reproduces the main features of artificial heterogeneities, even in the presence of noise in the pressure-transient data. One key shortcoming of the model has been identified: it is dangerous to do just one inversion, because it is likely that not all features of the returned permeability distribution play a role in matching the pressure-transient data. This shortcoming can be overcome by doing multiple inversions, and identifying the features which are common to all the returned permeability distributions. Furthermore, the locations of spurious features may be used to identify the regions to which the pressure-transient data is not very sensitive. Knowledge of which parts of the system have not been probed by the characterization effort is a very important result in itself.

5. INVERSION OF KESTERSON DATA

5.1 INTRODUCTION TO THE INVERSION OF REAL DATA

The previous chapter described the use of synthetic data to test the IFS inverse method. One limitation of this approach is that the ability to successfully invert synthetic data is a necessary but not sufficient condition to ensure successful inversion of real data, because one cannot systematically examine how the method will work under all real-world conditions. At best, one can use experience with real-world problems to design synthetic cases that will expose the model to potential difficulties encountered in analyzing real data. The application to real data, described in this chapter and the following one, is therefore a necessary step in the development and testing of the method.

The key difference between inverting synthetic data and real data, is that when inverting real data there is often no real way of knowing how well the method has worked. Of course, a failure to match the pressure transients indicates a failure of the method, but a successful match does not guarantee that the corresponding permeability distribution is correct. In fact, it is overwhelmingly likely to be incorrect in the sense that it is a great over-simplification of reality. The more relevant question is whether the returned permeability distribution is correct in the sense that it will be of value in predicting the future behavior of the system. For this reason, it is useful to test the inverse method by applying it to a site where there is some means of checking the results of the inversion. This could be the existence of independent characterizations of the site, perhaps using other methods than well-test analysis, or enough well-test data so that some of it can be omitted from the inversion process, and used to test the resulting model.

5.2 THE KESTERSON RESERVOIR SITE

A variety of well tests have been conducted on a shallow aquifer system composed of interbedded sands, silts, and clays at Kesterson Reservoir, located in the San Joaquin Valley in central California [Yates, 1988]. Both steady-state and transient single-well tests and multi-well pulse tests have also been conducted at the site, as well as cross-well seismic imaging. The hydrologic properties of the aquifer/aquitard system are needed in order to study the transport of various forms of selenium and other salts between surface waters and underlying aquifers. The original plan for applying the IFS inverse method was to develop a model of the system using one interference test, then use the model to predict the responses to other well tests and assess the model. This plan could not be carried out, however, due to a termination of funding for the project. Instead, the results of the inversion of one interference test are compared to the results of an

independent analysis of the same interference test.

5.3 QUASI-THREE-DIMENSIONAL ANALYSIS OF AN INTERFERENCE TEST

The aquifer being studied is about 18 m thick, and is underlain by an impermeable clay layer and overlain by a leaky aquitard. A multi-well interference test was analyzed to infer the spatial distribution of transmissivity in the aquifer. In the test under consideration, a central well was pumped at a constant rate of $6 \times 10^{-3} \text{ m}^3/\text{s}$ and transient drawdowns were measured at eight observation wells located 15 to 107 m away from the pumping well. All the wells were screened over the middle third of the aquifer thickness. The test lasted 5 hours, with the first observations made about 5 seconds after pumping commenced.

Initial studies used the two-dimensional nested lattice shown in Figure 5.1 to represent the aquifer. The well-field is shown by the solid circles, with the pumping well at the center ($x = 0$, $y = 0$). The nested lattice design is practical for modeling flow in porous media, where fine resolution is needed to represent flow near wells adequately, but the lattice must extend far beyond the well field to realistically implement pressure boundary conditions. Fine resolution is undesirable beyond the well field, because it greatly increases the size of the calculation without improving the ability of the model to predict flow or pressure at the well field. At the outer boundary of the lattice the head was held constant, with the extent of the lattice chosen so that the cone of depression would not reach the boundary during the duration of the well test.

Use of a two-dimensional lattice requires that the wells be modeled as fully penetrating and that the upper and lower confining layers be considered impermeable. The late-time slopes of the drawdown versus time curves calculated by this model were consistently steeper than observed slopes. Because geological information and other hydrologic inversion studies [Yates, 1988] suggested that leakage occurred through the upper confining layer, it was decided to use a quasi-three-dimensional model in which leakage from an overlying aquitard could be included in an approximate way, as described in Appendix A, which required the addition of approximately 700 nodes and elements to the lattice shown in Figure 5.1. The ratio of the aquitard vertical permeability to the base value of the aquifer horizontal permeability was estimated to be 10^{-3} by matching the slopes of the late-time portion of the drawdown curves to observed values. The specific storage of the aquitard was assumed to correspond to the base value of storativity of the aquifer. These parameters did not vary during the inversion (i.e., they were unaffected by the location of attractor points). Vertical flow within the aquifer itself was not included in this model, so partial penetration effects were not accounted for.

Figure 5.1. The nested TRINET lattice used for the Kesterson inversion. Frame (a) shows the central portion of the lattice; the pumping well is at $x = 0, y = 0$, the locations of the observation wells are shown as solid circles. Frame (b) shows the entire lattice; head is held constant at $x = \pm 600, y = \pm 600$.

Figure 5.2 shows the observed drawdown versus time curves and those calculated assuming a medium with uniform transmissivity and storativity (no attractor). The energy of the uniform-medium solution is $E = 25$. Note from Figure 5.1a that the observation wells are divided into two groups: four 'inner' wells are located between 14 and 16 m away from the pumping well, and four 'outer' wells are located between 60 and 107 m away. Figure 5.2 shows that the worst match between the uniform medium calculation and the observed data is for the outer well on the left, and among the inner wells the worst match is again found for the well on the left. These qualitative observations suggest that the attractor might show some special characteristics on the left side.

The attractor was scaled to lie in the region of the lattice given by $-150 < x < +150$ m and $-150 < y < +150$ m. Geological information and previous well-test analysis [Yates, 1988] indicate that storativity is far less variable than transmissivity in the Kesterson setting, so attractor points represent changes in transmissivity only. Table 5.1 summarizes the results of three inversions with $k = 4$ using attractors that decrease transmissivity. The multiplicative algorithm was used, with $\Delta T = 0.5$. Case K1 used simplex annealing with $n = 12$ parameters (the rotation form of the **B** matrix given by Equation (2.12), with only θ 's and **b**'s variable) for most of the inversion. The inversion stopped at $E = 1.7$ and was restarted with all parameters variable ($n = 16$). Cases K2 and K3 used simulated annealing with $n = 12$ and $n = 16$, respectively. The drawdowns calculated for Case K3 are shown in Figure 5.2, the agreement with the observed drawdowns is very good.

Table 5.1. Summary of Kesterson Reservoir inversions with $k = 4$ and attractor points that decrease transmissivity.

Case	Number of Forward Calculations	Number of Accepted Attractors	E
K1	10,579	-	1.6
K2	14,993	349	2.1
K3	7,600	354	1.7
Uniform medium			25

CPU time per iteration is 77 sec on a Solbourne 500 series workstation

Figure 5.2. Observed and calculated transient drawdowns for Kesterson. The arrangement of the plots on the page follows the locations of the observation wells in the well field.

Figure 5.3 illustrates the attractors for Cases K1, K2, and K3. Although they by no means produce a unique picture of the transmissivity distribution, they do show a number of features in common. The attractors are all relatively compact structures overlying the inner observation wells. In each case there is a point-free region between the pumping well and the inner left observation well, providing a high-permeability path between them, which accounts for the large, early response of that observation well. Additionally, each case shows a strong concentration of points between the inner and outer wells on the left side, which accounts for the small, late response of the outer left observation well.

Because of the nested nature of the lattice used for the calculations the attractors themselves provide only a qualitative picture of the transmissivity distributions. Two quantitative representations are shown in Figure 5.3. The first displays the central portion of the lattice with the thickness of each element proportional to the transmissivity of that element. This is a straightforward representation of the transmissivity distribution used for the flow calculation, but the increase in element transmissivity that occurs as the lattice gets coarser tends to overshadow the variations in transmissivity caused by the attractor points, making the pictures cumbersome to interpret. The final display in Figure 5.3 attempts to alleviate this problem, by eliminating the lattice from the picture and plotting the effective transmissivity of the aquifer that the lattice represents. For each element in the lattice, transmissivity T is divided by element length L to give effective transmissivity $\tilde{T}$, as described in Appendix A. Then a square centered on the element is filled with a dot pattern whose density is proportional to $\tilde{T}$.

It turns out that for the mapping algorithm used, attractor points have a greater effect on transmissivity in the coarser regions of the lattice than in the finer central region around the inner wells. Thus each of the attractors shown in the top row of Figure 5.3 yields a transmissivity distribution with an annular low transmissivity region between the inner and outer observation wells. Some inversions using attractors that increased transmissivity were also done. These yielded higher energies than the decreased-transmissivity inversions for comparable numbers of forward calculations, suggesting that a geological model consisting of local low-permeability features (e.g., clay lenses) embedded in a high-permeability background may be more appropriate than local high-permeability features (e.g., gravel bars) embedded in a low-permeability background. Figure 5.4 shows the three attractors that yielded the lowest energies ($E \approx 9$) of the increased-transmissivity inversions. For the most part, attractor point locations are complementary to those for the decreased-transmissivity inversions, yielding a consistent picture of the aquifer transmissivity distribution, with a low-permeability region just beyond the inner

Figure 5.3. Results of three decreased-transmissivity inversions for Kesterson: top row – the final attractor for each case; middle row – the TRINET lattice plotted with element thickness proportional to transmissivity; bottom row – a grey-scale plot of effective aquifer transmissivity $\tilde{T}$. The minimum transmissivity level shown is $T_0/100$, although several elements have even lower T values.

observation wells, and a high-permeability region further away.

Figure 5.4. The final attractors for the increased-transmissivity inversions for Kesterson.

5.4 COMPARISON WITH PREVIOUS ANALYSIS

Yates [1988] used a two-dimensional axisymmetric porous medium model to analyze the interference test considered here. Her model differed from the present one by accounting for well partial penetration, allowing vertical variations in permeability in the aquifer, and requiring horizontal permeability variations to be radially symmetric and centered at the pumping well. She did not use a formal optimization algorithm, but ran repeated forward simulations of the interference test with different permeability distributions chosen by hand, using results of a series of single-well tests to guide the choices. Her best match to the observed drawdown curves is comparable to that shown in Figure 5.2, and was obtained using a composite aquifer model with a high-permeability zone in the vicinity of the inner wells, with a permeability about ten times that of the rest of the aquifer. The present results are consistent with this model in the vicinity of the inner wells. Yates used a ratio of aquitard vertical permeability to inner-zone-aquifer horizontal permeability of about 2×10^{-3} , twice as large as that used for the present study. The additional leakage provided by the higher permeability of the aquitard may eliminate the need for the high-permeability outer zone found in the present study.

5.5 POTENTIAL FURTHER STUDIES AT KESTERSON

The Kesterson Reservoir site provides several opportunities for further development and testing of the IFS inversion method. To rigorously analyze the present interference test, a fully three-dimensional model should be used, with the transmissivities of both the aquifer and leaky

aquitard allowed to vary. The IFS inversion method could be applied to three-dimensional problems with only minor modifications, but the computational effort of an inversion would be greatly increased. Not only will the forward calculations require far more computational time due to a larger lattice, but a three-dimensional attractor has 12 parameters for each affine transformation, compared to 6 for a two-dimensional attractor, doubling the dimension of the parameter space that must be searched by the inversion. One possibility would be to use a three-dimensional lattice to properly account for vertical flows arising from well partial penetration, but to limit the attractor and corresponding transmissivity variations to two-dimensional structures within the aquifer to minimize the number of parameters. Before embarking on three-dimensional inversions, all aspects of the IFS inversion code need to be streamlined.

It would be very interesting to condition the inversion of the interference test by the results of the single-well tests, as was done by *Yates* [1988]. Such conditioning could be done in a straightforward way by co-inverting all the available well tests, however, this would be computationally intensive as each forward calculation would have to include the interference test and all the single-well tests. A more efficient approach might be to simulate just the interference test but to add a penalty term to the objective function if the transmissivity in the neighborhood of a well contradicted the value inferred from that well's individual well test.

One of the appealing features of a fractal model for a hydrologic property distribution is its ability to scale up the model from a relatively small-scale well test to a large-scale regional model, which arises naturally from the self-similar nature of fractals. A second interference test was done at Kesterson, studying the same aquifer/aquitard system at a nearby well field. It could be worthwhile to invert this second test independently of the present work, and then co-invert them both, using a larger lattice encompassing both well fields, to determine whether a fractal model of the transmissivity distribution is appropriate at this larger scale.

6 INVERSION OF GYPSY PILOT-SITE DATA

6.1 INTRODUCTION

In contrast to the analysis of the Kesterson data described in the previous chapter, in which a single interference test was inverted to determine the properties of a single aquifer, here a multi-layered system is analyzed using a large number of interference tests. The tests are inverted individually and in combination, and some are omitted from the inversion process, and subsequently used to assess the models developed through inversion. Results of the IFS inverse method are compared to results of cross-well seismic imaging, and to a more traditional geostatistical analysis.

6.1.1 Gypsy Sites and Data

The Gypsy formation is a Pennsylvanian age fluvial sandstone and shale sequence located in northeast Oklahoma, which was deposited as a mixed-load meander belt system [Doyle, 1989]. The Gypsy site was originally developed by British Petroleum (BP) as a test site at which to develop and assess reservoir characterization methods [Doyle, 1989; Doyle and Sweet, 1992], and is currently under the care of the University of Oklahoma (OU). The Gypsy site is being used by LBL to study the characterization of heterogeneous reservoirs using a combination of geophysical methods (cross-well seismic surveys) and hydrologic analyses (interference tests).

The Gypsy site consists of two suites of boreholes and several outcrops. The main Gypsy outcrop is a 300-m (1000 ft) long, 15-m (50 ft) high road cut which reveals six fluvial channels. Over 1,100 permeability and porosity measurements have been made at the outcrop, along with detailed geologic mapping, as is illustrated in Figure 6.1. Three-dimensional information has been obtained by drilling 25 shallow boreholes near the outcrop, above the water table (Figure 6.2). At the subsurface pilot site, located about 32 km (20 miles) away, six wells have been drilled into the Gypsy formation, which lies between 275 and 300 m (900 and 1000 feet) deep, and is saturated with brackish water. Figure 6.3 shows the pilot-site well field layout. The pilot-site data set includes an extensive set of well logs, core-information, pressure-transient well tests (interference, buildup, and vertical tests), 3-D surface seismic, VSP, and cross-well seismic.

The detailed geologic mapping done at the outcrop site was used to develop a numerical model of the Gypsy formation, which was then used to create synthetic well-test data, as described in Section 4.3. In this chapter, the inversion of the real data from the pilot-site well tests is described.

Figure 6.1. Orthophotograph of the main Gypsy outcrop and illustration of the geological mapping used to analyze it.

Figure 6.2. Plan view of the Gypsy outcrop-site borehole array.

Figure 6.3. Gypsy pilot-site well field layout.

6.1.2 Pilot-Site Well Log Interpretation

A conceptual geological model of the pilot site was developed by BP based on well-log and core data from three wells [Dowdle *et al.*, 1990]. The model is comprised of three sand channels (denoted the lower, middle, and upper channel) separated vertically by clay layers. The lower clay layer (the dense red clay) appears in all three wells and is inferred to be continuous while the upper clay layer only appears in two of the three wells. The Gypsy formation is underlain by a marine layer known as the Tallant formation.

In the present work, the well-log analysis was extended to consider all six pilot-site wells and three nearby wells. Neutron-density and gamma-ray logs were used to identify sand and clay (or mudstone, siltstone, or other fine-grained material) layers. The well-log study led to the following conclusions:

1. The base-of-Gypsy/Tallant contact looks like a continuous clay layer ranging from 2 to 8 m (6 to 25 ft) thick.
2. Some contacts between sand and silt are gradational rather than sharp.
3. The dense red clay layer appears in all wells, separating the lower and middle sand channels.
4. The clay layer separating the upper and middle sand channels appears in some wells, but is missing in wells 5 and 8. Hence the sand channel above the dense red clay layer is referred to as upper/middle (U/M) for these wells.

Figure 6.4 shows east-west and north-south cross-sections based on the well-log study. The various lithofacies have been grouped into two categories which are expected to have distinct hydrologic properties, low-permeability clays and shales and high-permeability sands.

6.1.3 Pilot-Site Well Tests

Two series of well tests were conducted at the Gypsy pilot site in 1989 and 1990 as part of BP's integrated reservoir description effort. The 1989 tests used just three of the wells (wells 1, 5, and 7) whereas the 1990 tests used all six wells. Figure 6.5 shows the wells used for each test in plan view. Each of the wells was screened over two or three sand intervals and the various intervals were isolated by packers for the well tests, as shown in Figure 6.5. Three types of well-tests were conducted: interference tests, in which one packed-off interval of a well was flowed and pressures were monitored in surrounding wells; buildup tests, in which one packed-off interval of a well was flowed, then shut in and pressure was monitored in that interval; and vertical

Figure 6.4. Cross-sections through the Gypsy formation at the subsurface pilot site, showing simplified lithologies as inferred from well logs and core studies. The dark bands indicate clay or shale and the remainder is sand. The horizontal bars mark the upper limit of the logged interval.

tests, in which one packed-off interval of a well was flowed and pressures were monitored in other intervals of that well. The interference tests are of primary interest for characterizing reservoir heterogeneity. Each consisted of three or four short constant flow-rate pulses, followed by a longer pulse and recovery period. Each test lasted about 12 hours altogether. Table 6.1 summarizes the well-tests done, which are identified by year, sequence number (which groups together the tests in which the same well was pumped), and test number.

Table 6.1. Well tests conducted at the Gypsy pilot site in 1989 and 1990.

Year	Sequence	Pumped Well	Test	Pumped Interval	Comments
1989	S0	1			
			T0	lower and upper	
	S1	7			
			T0	lower	data unreliable repeat of S1/T0
			T1	lower	
1990	S2	5			
			T2	lower	
			T3	upper/middle	
			T4	upper/middle	
	S1	11			
			T1	lower	
			T2	middle	
			T3	upper	data unreadable
	S2	9			
			T1	lower	
			T2	middle	
			T3	upper	
	S3	8			
			T1	lower	
			T2	upper/middle	
	S4	1			
			T1	lower	
			T2	middle	

6.2 REVIEW AND ASSESSMENT OF WELL-TEST DATA

6.2.1 Matrix Display of Well-Test Results

A matrix display of well-test results provides a concise way to assess the consistency, precision, and coverage of a large number of well tests. Each entry in the matrix describes the response between a pair of pumping and observation well intervals. Diagonal elements of the matrix represent buildup tests or in-zone vertical tests. Based on the principle of reciprocity

Figure 6.5. Schematic illustration of the Gypsy pilot-site well tests conducted in 1989 and 1990, and the screened intervals (shown as black bars) in the wells.

[Barker, 1991], the response at Well A during a test in which Well B is pumped should be the same as the response at Well B during a test in which Well A is pumped, if the same pumping rates are used in both tests. This relationship even holds when different flow rates are used, if each drawdown response is normalized by the flow rate used. Asymmetric matrix entries identify contradictory well-test responses, which suggest some sort of instrument failure (e.g., packer failure, packer placed at the wrong depth, electrical power outage). The matrix may also be used to identify gaps in coverage, that is, combinations of wells which have not been tested together, which would be useful locations for future well tests.

A matrix of well-test responses is shown in Figure 6.6, with rows specifying observation well interval and columns specifying pumping well interval. If there was a pressure response, the kH value calculated by BP using the program PIE is shown (PIE determines the kH value by fitting each pressure-transient individually to an analytical model which considers a uniform aquifer, with the possible inclusion of a lateral boundary [Dowdle *et al.*, 1990; Papadopoulos *et al.*, 1991].) Where contradictory responses exist (e.g., row 1M, column 9L and row 9L, column 1M) it must be decided which response is more likely to be correct. This can be done more readily by re-ordering the matrix entries as shown in Figure 6.7, so that instead of being grouped by well, the intervals are grouped according to upper, middle, and lower sand channels. Figure 6.7 suggests a model in which all lower sand channel intervals are in communication and all upper and middle sand channels are in communication, but no lower sand channel interval communicates with any upper or middle channel interval. All of the entries which contradict this model either violate reciprocity directly, or represent observations made during a test with other problems. Each such entry is listed in Table 6.2, along with a justification for eliminating it from the matrix. Thus all reliable tests support the model. A complete list of the production and observation intervals used to create the matrices is given in Doughty and Thompson [1993].

Figure 6.8 shows the final matrix, which includes only internally consistent responses. It clearly illustrates the lack of communication across the dense red clay layer above the lower sand channel, and the good communication between the upper and middle sand channels. Within each sand channel the PIE responses show a wide range of values for the permeability-thickness (kH) product, as would be expected when applying a homogeneous-medium model to a heterogeneous medium, but overall the lower sand channel consistently gives greater kH values than do the upper and middle sand channels.

PUMPING WELL																			
		1L	1M	1U	5L	5U/M	7L	7M	7U	8L	8U/M	9L	9M	9U	11L	11M	11U		
	1L	29,000			44,000	D.M.						38,000			29,000		D.M.	1L	
	1M		4,900			7,000						11,000	5,600	9,800		7,100	D.M.	1M	
	1U					D.M.						8,500	4,000	7,600		5,500	D.M.	1U	
	5L	40,000			35,000					28,000		35,000			39,000		D.M.	5L	
	5U/M		5,400			4,000					6,400	13,000	6,300	11,000		6,800	D.M.	5U/M	
	7L	39,000			27,000		45,000 38,000			36,000	D.M.	36,000			D.M.		D.M.	7L	
	7M		5,500			5,000					5,500	11,000	5,400	4,900		7,500	D.M.	7M	
OBSERVATION WELL	7U		4,700			11,000					6,100	11,000	5,800	5,000		7,200	D.M.	7U	OBSERVATION WELL
	8L									30,000								8L	
	8U/M										6,400							8U/M	
	9L	40,000								34,000		29,000						9L	
	9M										6,800		8,100					9M	
	9U										5,700			5,800				9U	
	11L	39,000								D.M.		43,000			31,000			11L	
	11M		4,800								5,400	11,000	5,800	10,000		6,100		11M	
	11U		3,900								5,600	9,000	6,100	7,200			D.M.	11U	
		1L	1M	1U	5L	5U/M	7L	7M	7U	8L	8U/M	9L	9M	9U	11L	11M	11U		
PUMPING WELL																			

	Response, kH (md-ft) from PIE
	No response
	Buildup test
	Red border: violates reciprocity
D.M.	Data missing or garbled

Figure 6.6. Matrix display summarizing hydrologic tests done at the Gypsy subsurface pilot site. Entries grouped by well.

Figure 6.7. Matrix display summarizing hydrologic tests done at the Gypsy subsurface pilot site. Entries grouped by sand channel.

Table 6.2. Gypsy well-test data eliminated from consideration due to inconsistencies or problems.

Data Eliminated	Comments
All observation intervals for test 90/S2/T1	Pump from well 9 lower interval, all intervals of all wells respond. One test (S3/T2) directly contradicts the response via reciprocity. All other well tests show no communication across the dense red clay layer. The reservoir engineer running the well tests cited experimental evidence for packer failure in materials recovered from the well after the test, and an anomalously high storage value calculated for the test that would be consistent with an unpacked hole (Ed Payne, personal communication, 1992). Infer packer failure.
All well 9 observation intervals for test 90/S4/T2	Pump from well 1 middle interval, no response from any well 9 interval. Reciprocal tests (S2/T2 and S2/T3) show a response in upper and middle layers. Infer instrument failure in well 9.
Lower Well 1 observation interval for test 89/S1/T0	Pump from well 7 lower interval, no response from well 1 lower interval. Reciprocal tests (89/S1/T1 and 90/S4/T1) show a response. Infer instrument failure in well 1.
All observation intervals for test 89/S1/T0	Data unreliable due to poor experimental control.
All observation intervals for test 89/S0/T0	Multiple intervals were used for pumping, not analyzable with 2-D model.
All middle and lower observation intervals for test 89/S2/T4	Multiple intervals were used for observation, not analyzable with 2-D model.
Some observation intervals for tests 89/S1/T0, 89/S2/T3, 89/S2/T4, 90/S1/T1, 90/S1/T3, 90/S3/T1, 90/S3/T2	Data missing or garbled.

Additionally, Figure 6.8 shows five pairs of matrix entries with responses which are the transpose of each other; these potentially may be used test the principle of reciprocity. The tests in question are listed in Table 6.3, along with the kH values obtained from PIE [Dowdle *et al.*, 1990; Papadopoulos *et al.*, 1991]. One way to quantify the comparison between two test's kH values is to compute their ratio. If the kH ratio is very different from one, it may mean that the pressure transients do not show reciprocity, but it could also indicate that the uniform medium model assumed by PIE is simply inadequate to match the pressure transients and the returned kH

		PUMPING WELL																	
OBSERVATION WELL		1L	5L	7L	8L	9L	11L	1M	7M	9M	11M	5U/M	8U/M	1U	7U	9U	11U		
	1L	29,000	44,000	37,000		P.F.	29,000					D.M.					D.M.	1L	
	5L	40,000	35,000		28,000	P.F.	39,000										D.M.	5L	
	7L	39,000	27,000	45,000 38,000	36,000	P.F.	D.M.						D.M.				D.M.	7L	
	8L				30,000													8L	
	9L	40,000			34,000	P.F.		I.F.										9L	
	11L	39,000			D.M.	P.F.	31,000											11L	
	1M					P.F.		4,900		5,800	7,100	7,000				9,800	D.M.	1M	
	7M					P.F.		5,500		5,400	7,500	5,000	5,500			4,900	D.M.	7M	
	9M							I.F.		5,100			6,800					9M	
	11M					P.F.		4,800		5,800	6,100		5,400			10,000		11M	
	5U/M					P.F.		5,400		6,300	6,800	4,000	6,400			11,000	D.M.	5U/M	
	8U/M												6,400					8U/M	
	1U					P.F.				4,000	5,500	D.M.				7,600	D.M.	1U	
	7U					P.F.		4,700		5,800	7,200	11,000	6,100			5,000	D.M.	7U	
	9U							I.F.					5,700			5,800		9U	
	11U					P.F.		3,900		6,100			5,600			7,200	D.M.	11U	
		1L	5L	7L	8L	9L	11L	1M	7M	9M	11M	5U/M	8U/M	1U	7U	9U	11U		
		PUMPING WELL																	

	Response, kH (md-ft) from PIE
	No response
	Buildup test
P.F.	Packer Failure
I.F.	Instrument Failure
D.M.	Data missing or garbled

Figure 6.8. Matrix display summarizing hydrologic tests done at the Gypsy subsurface pilot site. Entries grouped by sand channel, contradictory entries removed.

 

values are not meaningful. Only the first two pairs of tests in Table 6.3 give kH ratios close enough to one to suggest reciprocity on this basis.

Comparing the pressure transients of two tests directly, without trying to match them with any particular model, provides a straightforward check on reciprocity. For two tests with different flow rates, the pressure response must be divided by the flow rate to make the comparison. This reciprocity test is difficult to apply to the Gypsy data because different pulse durations were used for the various well tests, different flow rates were used for pulses within a given well test, and the observed pressure record is incomplete. A rigorous comparison can be made if the observed response to the first pulse is available for both tests, by normalizing pressure by the first-pulse flow rate. An approximate comparison can be made by comparing the responses for later pulses, by normalizing by an average flow rate for previous pulses.

Checking for reciprocity is done by plotting the pressure transients on a log scale and shifting the curves vertically until they match, then checking that the amount shifted, $\Delta \ln P$, corresponds to the log of the flow rate ratio between the two tests. Because pressure response is directly proportional to flow rate and inversely proportional to some effective kH value, $\Delta \ln P$ and the flow-rate ratio can be combined to determine a ratio of the kH values for the two tests:

$$\begin{aligned} \Delta \ln P &= \ln P_A - \ln P_B = \ln \left[\frac{P_A}{P_B} \right] \\ &= \ln \left[\frac{q_A/kH_A}{q_B/kH_B} \right]. \end{aligned} \quad (6.1)$$

Rearranging to isolate kH_A/kH_B gives:

$$\frac{kH_A}{kH_B} = \frac{q_A}{q_B} e^{-\Delta \ln P}. \quad (6.2)$$

Using this technique, the third pair in Table 6.3 shows good reciprocity, while the second pair is not too bad (flow rate variations make it very difficult to determine the appropriate flow rate by which to normalize). The fourth and fifth pairs show a definite lack of reciprocity. The fourth pair match considers only very early-time data, which may be masked by wellbore effects or early-time instrumentation instabilities. In contrast, the fifth pair match considers the long pulse, which should provide a reliable comparison. The large discrepancy suggests that either the flow rates or pressure response or both were incorrectly recorded for one of the tests. Since test 90/S4/T2 occurs in both pairs, it is most suspicious.

Table 6.3. Reciprocity checks for Gypsy Pilot-site well-test data.

Pair No.	Test A (pumping interval)	Test B (pumping interval)	PIE Comparison			Pressure Transient Comparison			Comments
			kH_A (md)	kH_B (md)	$\frac{kH_A}{kH_B}$	$\Delta \ln P$	$\ln \left[\frac{q_A}{q_B} \right]$	$\frac{kH_A}{kH_B}$	
1	90/S4/T1 (1 lower)	89/S2/T2 (5 lower)	40,000	44,000	0.9				Not enough data
2	90/S4/T1 (1 lower)	89/S1/T1 (7 lower)	39,000	37,000	1.1	0.36	0.39 to 0.56†	1.03 to 1.22	3rd and 4th pulses, possible reciprocity
3	90/S4/T1 (1 lower)	90/S1/T1 (11 lower)	40,000	29,000	1.4	-0.16	-0.15	1.01	2nd and 3rd pulses, good reciprocity
						-0.56	-0.51	1.05	Long pulse, good reciprocity
4	90/S4/T2 (1 middle)	89/S2/T3 (5 middle)	5,400	7,000	0.8	-1.50	-1.16	1.4	1st pulse, no reciprocity
5	90/S4/T2 (1 middle)	90/S1/T2 (11 middle)	4,800	7,100	0.7	0.16	-0.92	0.3	1st pulse, no reciprocity
						-0.38	-0.86	0.6	Long pulse, no reciprocity

†Range of values depending on which flow rates averaged together

The matrix display of well-test responses shown in Figure 6.8 also identifies the following gaps in coverage, which are possible locations for future well tests.

- No tests were done between wells 1 and 8.
- Only two cross-zone vertical tests (same well, different intervals) were done.
- No well 7 buildup tests were done for the middle or upper layers.
- There is little well 9 lower level information due to the packer failure.
- Only partial information is available for wells 1 and 11 upper layers.

6.2.2 Assessment of Existing Data and Analyses

Based on our evaluation of the data, we find that the well-test data as a whole supports the conceptual geological model of the pilot site presented in Dowdle *et al.* [1990]. This model is comprised of three sand channels (denoted the lower, middle, and upper channels) separated vertically by two clay layers. The lower clay layer (the dense red clay) is inferred to be continuous while the upper clay layer is discontinuous.

Plotting the pressure transients and studying the matrix displays of the well-test responses indicates that a total of 90 pressure transients from 12 tests are directly usable, out of a total of

130 pressure transients from 16 tests. The remaining 40 pressure transients fall into one of five categories:

- twelve pressure transients which qualitatively satisfy the reciprocity principle or involve duplicate tests. Of these, five show a response while seven show no response; the five responders are useful for checking the consistency of the data.
- four pressure transients which qualitatively contradict the reciprocity principle; these have been used to identify three occurrences of instrument failure.
- twelve pressure transients which were measured during one of the tests with instrument failure.
- eight pressure transients for which the data was missing or garbled.
- four pressure transients from tests that were designed in such a way as to make the results uninterpretable with our inverse method.

Overall, 102 out of 130 pressure transients are usable, either directly in the inversions, or indirectly to check the precision of the data.

6.2.3 Strategy for Inversion

The following strategy was used for doing the hydrological inversions.

1. Initially, just the lower sand channel was modeled, using a two-dimensional areal model. There are 17 pressure transients between lower-layer intervals. Of these, two are from vertical tests, five are from buildup tests, and ten are from interference tests. The interference tests are most amenable to use in the inversion.
2. After assessment of the results of the two-dimensional inversion, three-dimensional effects such as leakage through the dense red clay layer were considered, as was done in the Kesterson analysis. It was found that inclusion of such effects was unnecessary because the late-time pressure response was adequately matched by a model in which the dense red clay layer was impermeable.
3. Next, the feasibility of combining the upper and middle sand channels into a single layer in a two-dimensional model was considered and eliminated, because the two sand channels showed distinct pressure responses. Therefore, the upper and middle sand channels were each modeled as a separate layer within a three-dimensional model. The inversion looks for the location and extent of the upper clay layer, which partially separates the middle and upper sand channels.

4. Finally, because the results indicated that there was little leakage across the dense red clay layer, it was concluded that a three-dimensional model including all three sand channels and intervening clay layers was not needed.

Sections 6.3 and 6.4 describe the analyses of the lower sand channel, and the upper/middle sand channels, respectively. The results of the hydrologic analyses are then compared with cross-well seismic imaging (Section 6.5) and a traditional geostatistical analysis (Section 6.6).

6.3 LOWER SAND CHANNEL ANALYSES

6.3.1 *Conceptual and Numerical Model*

The two-dimensional nested lattice shown in Figure 6.9 is used to represent the lower sand channel. The central region of the lattice, which covers the area of the well field, is finely discretized, with a lattice spacing of 10 meters, to enable adequate resolution of heterogeneities. The lattice extends far beyond the well field so that spurious boundary conditions are not imposed on the flow calculation. The extent of the lattice (about 1000 m from the center of the well field in all directions) was chosen so that the outer boundary would not be felt during the course of the longest well tests (about 12 hours). Beyond the well field, the lattice spacing steadily increases, as fine resolution is not necessary there. Because the model is two-dimensional, no vertical variations in flow or hydrologic properties can be modeled, making transmissivity and storativity, which represent depth-integrated properties, the appropriate variables to use. In fact, the thickness of the lower sand channel inferred from cores and well logs varies from about 3 m to about 11 m, implying that variations in transmissivity might reflect a combination of thickness and permeability changes.

6.3.2 *Homogeneous-Medium Simulations*

Five of the lower-channel well tests conducted by BP yield consistent drawdown data (a sixth test produced anomalous results which suggested packer failure; none of that data is included in the analysis). The data available for the five tests are summarized in Table 6.4, and shown schematically on a well-field diagram in Figure 6.10.

Lower Channel Model

Figure 6.9. The lattice used for the numerical model of the lower sand channel at the Gypsy sub-surface pilot site. The wells are shown as open circles.

Table 6.4. Production and observation wells for the Gypsy lower sand channel well tests.

Test	Well					
	1	5	7	8	9	11
90/S4/T1	Pump	Observe	Observe		Observe	Observe
90/S3/T1		Observe	Observe	Pump	Observe	
90/S1/T1	Observe†	Observe				Pump
89/S2/T2	Observe†	Pump	Observe			
89/S1/T1	Observe†		Pump			

†limited data available

Figure 6.10. The Gypsy pilot-site well field showing a schematic view of the lower sand channel well tests. The shaded lines connect the observation and pumping wells for a given test.

Before any inversions searching for heterogeneities are done, it makes sense to first simulate the well tests assuming a uniform medium. If a uniform-medium model adequately matches the drawdowns, then no information on heterogeneities is available from the hydrologic data and any hydrologic inversion which searches for heterogeneities is doomed to failure. The results of a forward calculation of each well test (drawdown as a function of time at the observation wells) using transmissivity $T = 9.7 \times 10^{-5} \text{ m}^2/\text{s}$ (equivalent to $kH = 32,000 \text{ md-ft}$) and storativity $S = 9.3 \times 10^{-6}$ ($2.1 \times 10^{-5} \text{ ft/psi}$) are shown in Figures 6.11-6.15, along with the observed drawdowns. The values of T and S used in the model fall within the range reported by *Papadopoulos et al.* [1991] ($27,000 < kH < 44,000 \text{ md-ft}$, $0.3 \times 10^{-5} < S < 3.2 \times 10^{-5} \text{ ft/psi}$), and were chosen to minimize the energy for test 90/S4/T1, the test for which the most observed data is available. Curve-shifting was disabled for these calculations, to force the model to use the same uniform values of transmissivity and storativity for each well-test simulation. After some experimentation with the design of the lattice shown in Figure 6.9, it was decided not to include the drawdown response at the pumping well in the objective function for any inversion, because the numerical model is too coarse to accurately predict near-wellbore flows.

Figure 6.11 shows that a uniform model does a good job matching the drawdowns from wells 5, 7, and 9 (except for very early times) when well 1 is pumped (test 90/S4/T1), but that drawdowns at well 11 are consistently underpredicted. This suggests that the lower sand channel may be relatively homogeneous between wells 1, 5, 7, and 9, but include some heterogeneity between wells 1 and 11. Figure 6.12 shows that the match becomes steadily worse from well 7 to well 5 to well 9 when well 8 is pumped (test 90/S3/T1), suggesting that hydrologic properties may gradually change from east to west in the region between wells 5, 7, 8, and 9. Figure 6.13 (test 90/S1/T1) shows small mismatches comparable to those of Figure 6.11. Figures 6.14 and 6.15 show that the data from the 1989 tests (89/S2/T2 and 89/S1/T1) are either of limited duration (the well 1 drawdowns for both tests) or show anomalous behavior (the 'flattened responses' of well 7 drawdowns for test 89/S2/T2), therefore these data cannot be used as the basis of independent inversions, but could be used in co-inversions with other data. Overall, the uniform-medium forward calculations indicate that there are heterogeneities in the lower sand channel that have an effect on hydrological behavior.

90/S4/T1 $E=3.5$

Figure 6.11. The observed and modeled observation-well drawdowns for test 90/S4/T1. The model consists of a uniform medium with T_0 and S_0 values that minimize the energy for test 90/S4/T1.

90/S3/T1 E=28.1

Figure 6.12. The observed and modeled observation-well drawdowns for test 90/S3/T1. Same uniform-medium model as in Figure 6.11.

90/S1/T1 E=5.8

Figure 6.13. The observed and modeled observation-well drawdowns for test 90/S1/T1. Same uniform-medium model as in Figure 6.11.

89/S2/T2 E=26.9

Figure 6.14. The observed and modeled observation-well drawdowns for test 89/S2/T2. Same uniform-medium model as in Figure 6.11.

89/S1/T1 E=5.4

Figure 6.15. The observed and modeled observation-well drawdowns for test 89/S1/T1. Same uniform-medium model as in Figure 6.11.

6.3.3 Single-Test Inversions of Test 90/S4/T1

In general, for inversions of lower sand channel well tests, in which rather subtle property variations between sand lithofacies are expected, relatively small values of ΔT and ΔS are appropriate. Additionally, ΔT and ΔS are chosen so that transmissivity and storativity vary together (i.e., a transmissivity increase accompanies a storativity increase and vice versa), as for sand facies it is expected that an increase in porosity (which contributes to an increase in storativity) will be associated with an increase in permeability. This variation is accomplished by making ΔT and ΔS the same sign for the additive algorithm, and both greater than one or both less than one for the multiplicative algorithm.

In test 90/S4/T1, well 1 was pumped and drawdowns were observed in wells 5, 7, 9, and 11, as illustrated schematically in Figure 6.10. The first inversion of test 90/S4/T1 used an IFS with $k = 4$ affine transforms, the step map with the additive algorithm, $\Delta T = -0.1T_0$, and $\Delta S = -0.1S_0$. Figure 6.16 shows the final attractor and the transmissivity distribution returned by the inversion (the storativity distribution shows the same pattern since $\Delta T/T_0 = \Delta S/S_0$), and Figure 6.17 shows the observed and modeled drawdowns. Although the uniform-medium match was quite good for this test, the inversion yields a modest decrease in energy ($E = 3.5 \rightarrow E = 2.09$). The introduction of several regions with low T and S enhances the communication between wells 1 and 11, and slightly decreases communication between well 1 and wells 5, 7, and 9, leading to better matches for the early-time drawdowns in wells 5, 7, and 9 and the entire response in well 11.

Figure 6.18 shows the returned transmissivity distributions and energies for eight inversions of test 90/S4/T1, which use different mapping parameters or different random seeds, as summarized in Table 6.5.

Table 6.5. Summary of parameters used for eight inversions of test 90/S4/T1.

Energy	T Mapping Algorithm	ΔT	S Mapping Algorithm	ΔS	Δ_2
2.09	Additive	$-0.1 T_0$	Additive	$-0.1 S_0$	0†
2.11	Multiplicative	± 1.6	Additive	$\pm 0.2 S_0$	-4.E-4
2.12	Multiplicative	± 1.2	Multiplicative	± 1.2	0.017
2.13	Multiplicative	± 1.2	Multiplicative	± 1.2	0.026
2.27	Multiplicative	± 1.6	Multiplicative	± 1.6	-0.27
2.32	Multiplicative	± 1.2	Multiplicative	± 1.2	0.035
2.94	Multiplicative	$+1.6$	Multiplicative	$+1.6$	-0.53
3.18	Additive	$+0.1 T_0$	Additive	$0.1 S_0$	0†

†Curve-shifting disabled

Figure 6.16. The returned transmissivity distribution for test 90/S4/T1. The upper frame shows the attractor returned by the inversion. The lower frame shows a grey-scale map of transmissivity with darker shades corresponding to higher transmissivity.

Curve-shifting along the $\ln h$ axis was enabled for most of the inversions, but because of the variable flow rate, curve-shifting along the $\ln t$ axis was not. The six inversions with final energies below $E = 2.4$ provide a consistent picture of the northern half of the well field (the region between wells 1, 5, 7, 9, and 11), in which there is higher transmissivity between wells 1 and 11, and lower transmissivity between wells 11 and 7. The inversions do not return consistent transmissivity distributions for the region beyond these five wells, indicating that the well-test data is less sensitive to transmissivity values there. This finding is consistent with the notion

90/S4/T1 E=2.1

Figure 6.17. The observed and modeled observation-well drawdowns for test 90/S4/T1, corresponding to the transmissivity distribution shown in Figure 6.16.

illustrated in Figure 4.5 that the well-test data is primarily sensitive to the region between pumping and observation wells.

Figure 6.18. Grey-scale transmissivity distributions for eight inversions of test 90/S4/T1. Darker shades correspond to higher transmissivity.

6.3.4 Single-Test Inversions of Test 90/S3/T1

Figure 6.10 suggests that an inversion of test 90/S3/T1, in which well 8 was pumped and drawdowns were observed in wells 5, 7, and 9, will complement the inversion of test 90/S4/T1 by providing information about the southern half of the well field. The inversions of 90/S4/T1 described above could be done successfully without time-shifting because the observed data could be simulated moderately well with a uniform-medium model ($E = 3.5$), for which it is easy to determine background diffusivity (by simply repeating the forward calculation for a variety of diffusivity values). This is not the general case, however, and in particular is not true for test 90/S3/T1, for which a uniform-medium model gives an energy of $E = 28.1$. The inversion of 90/S3/T1 requires a diffusivity optimization, as described in Section 3.2.3. The application of this algorithm is illustrated in Figure 6.19, which shows the energy as a function of iteration number for one inversion of test 90/S3/T1. The plus-minus algorithm was used for this inversion, with multiplicative increments $\Delta T = \Delta S = \pm 1.2$, $k = 4$ affine transforms and $n = 12$ unknown parameters (the rotation form of the **B** matrix given by Equation (2.12), with only θ 's and **b**'s variable). The observed and modeled pressure transients corresponding to the final energy of $E = 2.66$ are shown in Figure 6.20, and Figure 6.21 shows the attractor and the transmissivity distribution. The low-transmissivity region between wells 8 and 7 delays the pressure response at well 7, whereas the high transmissivity localized around well 5 lessens the magnitude of the pressure change there. Although there are no attractor points in the region between wells 8 and 9, the transmissivity along the pathway from well 8 to well 9 is higher than that along the pathway from well 8 to well 5 or along the pathway from well 8 to well 7, resulting in the earlier pressure response at well 9.

Four other inversions of test 90/S3/T1 using the same control parameters yielded energies around $E = 3$ to $E = 4$, and showed reasonably consistent transmissivity variations in the southern half of the well field, as shown in Figure 6.22. The lower the energy is, the more features the transmissivity distributions have in common. As was the case for test 90/S4/T1, the various inversions of test 90/S3/T1 do not provide a consistent transmissivity distribution for the region of the well field beyond the wells involved in the test.

Figure 6.19. Energy decrease during the inversion of test 90/S3/T1. The open circles mark the points at which background-diffusivity optimizations were done.

90/S3/T1 E=2.66

Figure 6.20. The observed and modeled observation-well drawdowns for test 90/S3/T1.

Figure 6.21. The returned transmissivity distribution for test 90/S3/T1. The upper frame shows the attractor returned by the inversion (horizontal dashes identify attractor points that decrease transmissivity and vertical dashes identify attractor points that increase transmissivity). The lower frame shows a grey-scale map of transmissivity with darker shades corresponding to higher transmissivity.

bp23 $E=3.25$

bp24 $E=3.15$

bp255 $E=3.87$

bp256 $E=4.10$

$-2 \quad 2$
 $\ln T/T_0$

Figure 6.22. Transmissivity distributions for four other inversions of test 90/S3/T1.

6.3.5 Multiple-Test Co-Inversions of Tests 90/S3/T1 and 90/S4/T1

As shown in the schematic diagram of the lower sand channel tests (Figure 6.10), a co-inversion of tests 90/S3/T1 and 90/S4/T1 should provide information on flow properties throughout the well field. In the co-inversion, the two tests are treated as one long test, with one set of long pressure transients. The first part of the long test corresponds to test 90/S3/T1, in which well 8 is pumped, and the second part of the long test corresponds to test 90/S4/T1, in which well 1 is pumped. Figure 6.23 illustrates the observed drawdowns used for the co-inversion. Each forward calculation in the inversion includes the twelve-hour periods of the two tests, but the intervening time between the two tests (two days) is not modeled; instead, the pressure changes are reset to zero at the end of the first test.

Despite the straightforward method of setting up the co-inversion problem and the apparently minor conceptual difference from inverting a single test, several surprising results have emerged from initial attempts at co-inversion. Typical results for observed and modeled drawdowns and transmissivity distributions are shown in Figures 6.24 and 6.25, respectively. The inversion used an IFS with $k = 4$ affine transforms, the step map with the multiplicative algorithm, $\Delta T = 1.6$, and $\Delta S = 1.0$. It is notable that the drawdown matches do not look appreciably better for the final result than do those for a uniform medium, despite the decrease in energy from $E = 11.3$ to $E = 3.6$. This is because the observed data points are equally spaced in log time for each of the individual tests, but since they are plotted against linear time, casual examination of the mismatch between observed and modeled pressures does not properly reflect the energy. Two consecutive tests cannot be plotted on one log time scale, because the second test would be too compressed to show anything. The log-time weighting was chosen to emphasize early time behavior, which should reflect near well-field heterogeneities, however, its use in co-inversion of sequences of tests makes it hard to readily visualize decreases in energy.

Another problem with the co-inversion of multiple tests is that the inversion seems to get stuck addressing either one part of the co-inversion or the other. In Figure 6.25, the transmissivity distribution has primarily been modified between well 8 and the observation wells, in effect addressing the 90/S3/T1 part of the pressure transients. Individual inversions of tests 90/S3/T1 and 90/S4/T1 yielded comparably low energies around $E = 2.5$, but the starting point for these inversions, a uniform medium, gave substantially higher energy for 90/S3/T1 ($E = 28$) than for 90/S4/T1 ($E = 3.5$). Hence a co-inversion of the two tests sees a much larger decrease in energy by making permeability changes to which the 90/S3/T1 portion of the test is sensitive (i.e., the

Tests 90/S3/T1 and 90/S4/T1: Observed Data

Figure 6.23. Observed drawdowns for the co-inversion of tests 90/S3/T1 and 90/S4/T1. Calculated drawdowns are reset to zero at 11.5 hours.

90/S3/T1 and 90/S4/T1 BP29a

Figure 6.24. The observed and modeled drawdowns for a co-inversion of tests 90/S3/T1 and 90/S4/T1 using an IFS with $k = 4$ affine transforms.

bp29a $E=3.63$

-2 2
ln T/T_0

Figure 6.25. Transmissivity distribution returned by a co-inversion of tests 90/S3/T1 and 90/S4/T1 using an IFS with $k = 4$ affine transforms.

region between well 8 and the observation wells).

Using IFS's composed of greater numbers of affine transforms provide transmissivity distributions with more distinct regions of variability. This should be helpful for matching the composite well-test data used in a co-inversion, which reflects information about many flow paths through the reservoir. A co-inversion of well tests 90/S3/T1 and 90/S4/T1 using $k = 6$ affine transforms instead of the $k = 4$ used previously was done to test this notion. The co-inversion was done in two stages. In the first stage a rotation-matrix form was specified for the affine transforms composing the IFS, which requires only $n = 18$ unknown parameters (three for each of the six affine transforms: one rotation angle, and two components of a translation vector. In the second stage, which starts with the final attractor from the first stage, the most general form of the affine transforms was used, allowing more variability and requiring $n = 36$ unknown parameters. This two-stage approach was used in order to try to initially determine the general features of the transmissivity distribution relatively quickly, then refine it later. The plus-minus algorithm for mapping the attractor to the transmissivity distribution was used, with multiplicative increments $\Delta T = \pm 1.5$ and $\Delta S = 1.0$.

The attractors resulting at the end of the first and second stages are shown in Figure 6.26. The energy for a uniform medium is $E = 13.5$, at the end of the first stage it has decreased to $E = 3.4$, and at the end of the second stage it has further decreased to $E = 2.5$. The observed and modeled drawdowns at the end of the second stage are shown in Figure 6.27. They show quite a good match between the model and the observed data, indicating that an inversion returning $E = 2.5$ may have gone as far as is necessary. Figure 6.28 shows a grey-scale plot of the transmissivity distribution corresponding to the final attractor for the second stage of the inversion. (Note that because $\Delta S = 1.0$, the storativity distribution is uniform.) The transmissivity distribution successfully combines features seen in individual inversions of 90/S3/T1 and 90/S4/T1. The key features are the high transmissivity region in the southwest quadrant, medium transmissivity values in the southeast, and the generally low transmissivities in the northern half, with the lowest values in the northwest. These features recur in the other co-inversions which yielded low energies (Figure 6.29), and can be traced to specific features in the pressure transients for the two tests which were co-inverted.

Figure 6.26. Attractors for a co-inversion of tests 90/S3/T1 and 90/S4/T1 using an IFS with $k = 6$ affine transforms. The upper frame shows an intermediate result after allowing limited variability of attractors during the first stage of the inversion, and the lower frame shows the final attractor. Horizontal dashes identify attractor points that decrease transmissivity and vertical dashes identify attractor points that increase transmissivity.

90/S3/T1 and 90/S4/T1 BP32a E=2.48

Figure 6.27. Drawdown versus time plots corresponding to the final attractor shown in Figure 6.26.

BP32a $E=2.48$

Figure 6.28. Grey-scale plot of the transmissivity distribution corresponding to the final attractor shown in Figure 6.26. Darker shades correspond to higher transmissivity.

bp33 $E=2.29$

bp35 $E=2.48$

Figure 6.29. Transmissivity distributions inferred from additional co-inversions of tests 90/S3/T1 and 90/S4/T1. Darker shades correspond to higher transmissivity.

6.3.6 Cross-Validation Studies

In order to assess how well a hydrologic inversion is working and to judge how much and what kind of information is contained in the well-test data, a procedure known as cross-validation may be used. In cross-validation, rather than using all available data to develop a hydrological model, some of the available data is not used in the inversion process, and the inferred hydrological model is subsequently used to try to match it. If the model cannot match the held-out data, it suggests that there is a significant amount of new information in that data which is not contained in the original observations used to develop the model.

Of the five lower sand channel well-tests illustrated schematically in Figure 6.10, only two of the tests, 90/S4/T1 and 90/S3/T1, provide complete enough drawdown records to do independent inversions. Two other tests, 90/S1/T1 and 89/S2/T2, provide enough partial information (early-time drawdowns only) to be used in conjunction with other tests. Test 89/S1/T1 provides only a short segment of early-time data from one observation well, and probably cannot add much to the analysis.

The results of single-test inversions for tests 90/S4/T1 and 90/S3/T1 described in Sections 6.3.3 and 6.3.4 show that no single-test inversion provides a reliable transmissivity distribution for the entire well field, eliminating the need to use any of the returned transmissivity distributions to try to model the remaining well tests. On the other hand, because repeated co-inversions of tests 90/S4/T1 and 90/S3/T1 yield similar patterns of transmissivity throughout the well field, it is reasonable to use transmissivity distributions returned by the co-inversion to model the remaining well tests. Accordingly, the transmissivity distribution shown in the top frame in Figure 6.29 was used to model all the well tests individually, and the returned energies were compared to the energies obtained using a uniform-medium model with a single value of transmissivity. The results are summarized in Table 6.6, which also shows the results of the best single-test inversion of each well test.

Both tests 89/S2/T2 and 90/S1/T1 show nearly a factor of two decrease in energy for the co-inversion model compared to the uniform medium model. Test 89/S1/T1 shows an increase in energy, but the reciprocity checks shown in Table 6.3 suggest that there may be problems comparing the results of test 89/S1/T1 to other tests. The overall conclusion is that the cross-validation exercise is successful.

It is of interest to note that a single-test inversion of test 90/S1/T1 yields a much lower energy than does the co-inversion model, suggesting that there is extra information to be gained

Table 6.6. Energies for lower sand channel cross-validation studies.

Test	Pumping Interval	Uniform Medium Model†	Model Based on Co-Inversion of 90/S3/T1 and 90/S4/T1	Best Single-test Inversion
90/S4/T1	1L	10	3	2
90/S3/T1	8L	14	2	3
90/S1/T1	11L	17	10	1
89/S2/T2	5L	50	25	-
89/S1/T1	7L	1	4	-

†Transmissivity and storativity taken from base values for best co-inversion of tests 90/S3/T1 and 90/S4/T1: $T_0 = 8.86 \times 10^{-4} \text{ m}^2/\text{s}$, $S_0 = 3.3 \times 10^{-5}$.

by a co-inversion of all three of 90/S4/T1, 90/S3/T1, and 90/S1/T1 (test 89/S2/T2 shows rather odd flattened pressure responses which suggest instrumentation problems, so it has not been included in further analysis). A co-inversion of the three 1990 tests has been done, using the transmissivity distribution shown in the top frame of Figure 6.29 as its starting point. The initial energy is $E = 3.8$ (Because energy is normalized by the number of observed data points, a simple arithmetic average of the energies for the three tests does not yield the co-inversion energy. There are about twice as many observed pressures for tests 90/S4/T1 and 90/S3/T1 as there are for 90/S1/T1, yielding $E = [2(2.0+2.8)+9.6]/5 = 3.8$). At the end of the inversion, the energy has been reduced to $E = 2.3$. The resulting transmissivity distribution is shown in Figure 6.30 and the 90/S1/T1 portions of the pressure transients are shown in Figure 6.31. The main difference in the calculated drawdowns is the smaller response at well 5 when well 11 is pumped, which occurs because the low-transmissivity region between wells 5 and 11 extends further around well 5 after the inversion.

This procedure of sequential model building, in which first the well tests with the most observed data available are inverted individually, then co-inverted together, then co-inverted with additional information to fine tune the transmissivity distribution, appears to be successful. Because the computational effort of the calculations increases dramatically as more tests are added to the co-inversion, it makes sense to try to infer the major features of the transmissivity distribution with the minimum number of tests possible first, then use this distribution as a starting point for further inversions.

BP45 E=2.34

Figure 6.30. Transmissivity distribution inferred from the co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1.

90/S1/T1, 90/S3/T1, 90/S4/T1 BP45

Figure 6.31. A portion of the pressure transients for the co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1.

6.4 UPPER AND MIDDLE SAND CHANNEL ANALYSES

6.4.1 Conceptual and Numerical Model

Based on the matrix display of the pilot-site well tests described in Section 6.2.1, it appears that the lower sand channel is hydrologically separated from the upper and middle sand channels by the dense red clay layer, whereas the upper clay layer observed in some but not all of the pilot-site wells does not hydrologically separate the upper and middle sand channels, as is illustrated conceptually in Figure 6.32. The conceptual model of the upper/middle sand channel system consists of two horizontal sand layers, separated by a heterogeneous intermediate layer (made up of vertical elements), which is composed of low-permeability clay some places and high-permeability sand other places. In Figure 6.32 the vertical elements which are composed of clay are not shown, to indicate that there is no vertical flow at those locations. The hydrologic inversion assumes that the upper and middle sand layers have uniform high permeabilities, while the permeability of the vertical elements varies strongly, to represent either sand or clay. Thus, although the flow calculation is three-dimensional, the attractor created by the IFS is two-dimensional and is confined to the intermediate layer of vertical elements. A two-dimensional attractor requires fewer parameters to specify it than does a three-dimensional attractor, and is easier to visualize.

Figure 6.32. Conceptual model of the Gypsy pilot site. Each horizontal layer represents a sand channel. The lack of communication between the middle and lower sand channels is represented by no elements connecting these two layers. The partial hydrologic communication between the upper and middle sand channels is represented by some vertical connections.

In most of the inversions the intermediate layer has low (clay-like) background permeability and the effect of the attractor is to increase the permeability, thus the attractor shows locations where the upper clay layer is missing. An alternative approach is to give the intermediate layer a high (sand-like) background permeability and let the attractor act to decrease the permeability and thus represent the region where the upper clay layer is present. Lithologies inferred from well-log information suggest that the clay layer is present the western, northern, and eastern portions of the well field (wells 1, 7, 9, and 11), but absent in the central and southern portions (wells 5 and 8), as shown in the first frame of Figure 6.33. Thus, a gap in the clay layer can be represented simply as a convex polygon, while the clay layer itself requires a more complicated shape, as illustrated schematically in the second and third frames of Figure 6.33. Having the attractor represent the gap therefore enables IFS's with fewer parameters to be used, which simplifies the inversion, as fewer unknown parameters must be searched for.

Figure 6.33. Lithologic information on the location of the upper clay layer, and possible inversion schemes.

The multi-layer model of the upper and middle sand channels requires substantially more nodes and elements than does the single layer model used for the lower sand channel inversions. The lower sand channel model has a lattice spacing of 10 m in the finest region, and a total of 945 nodes and 1807 elements. If this spacing were used for the multi-layer model, the number of nodes would be 1890 (double the single layer value) and the number of elements would be 4535 (approximately 2.5 times the single-layer value). In order to try to make the forward calculations

as efficient as possible, different lattice spacings were studied to see if accurate calculations could be made using larger lattice spacings. Lattice spacings of 10 m, 16.67 m, and 25 m were used in both two-dimensional (confined aquifer) and quasi-three dimensional (leaky aquifer) models of constant-flow-rate well tests, and compared to the analytical solutions shown in Appendix A. It was found that the model using a lattice with 16.67 m spacing in the finest region calculates acceptable drawdowns for the locations corresponding to the Gypsy wells. Hence this model (shown in Figure 6.34) was used as the basis for the multi-layer model of the upper and middle sand channels. The layer shown has 521 nodes and 980 elements and the multi-layer model has a total of 1042 nodes and 2449 elements. The CPU times required for one forward calculation of the multi-layer model and the lower-channel model are comparable.

Figure 6.34. Central portion of one layer of the lattice used to model the upper and middle sand channels. Each layer of the lattice extends a total of 2400 m in the x and y directions, with steadily increasing lattice spacing.

6.4.2 Assessment of Upper and Middle Sand Channel Well-Test Data

Seven well tests were done among upper and middle channel intervals. The data available for the seven tests are summarized in Table 6.7, and shown schematically on a well-field diagram in Figure 6.35.

Table 6.7. Production and observation well combinations for the Gypsy upper and middle sand channel well tests.

Test	Well 1	Well 5	Well 7	Well 8	Well 9	Well 11
90/S1/T2	Observe	Observe	Observe			Pump middle
90/S2/T2	Observe	Observe	Observe		Pump middle	Observe
90/S2/T3	Observe	Observe	Observe		Pump upper	Observe
90/S3/T2		Observe	Observe	Pump upper/middle	Observe	Observe
90/S4/T2	Pump middle	Observe	Observe			Observe
89/S2/T3	Observe middle‡	Pump upper/middle	Observe middle‡			
89/S2/T4		Pump upper/middle	Observe upper‡			

‡limited data available

In all the 1990 tests, observed data is available for both upper and middle layers if the observation well has separate screened intervals there. In Figure 6.35, the lines connecting the pumping and observations wells for each test illustrate the portion of the system to which the well-test data is most sensitive. As in the analysis of the lower sand channel, it appears that co-inversion of several tests will be necessary to obtain a reliable permeability distribution over the entire well field. For all of the 1990 tests there is sufficient data to do independent inversions of each test. For the 1989 tests there is not enough data available to do independent inversions, but the data could be used in co-inversions with other data.

For two of the tests, 90/S2/T2 and 90/S2/T3, the reported flow rates for the second pulse were about twice the size of the other pulses, but the pressure responses in the pumping well were not consistent with a larger second pulse for either test. For test 90/S2/T2 the pressure response to the second pulse was unusually small and for test 90/S2/T3 the pressure response to the second pulse was comparable to that for the other pulses. For these two tests, it was assumed that the second-pulse flow rates were recorded incorrectly, and these flow rates were modified as shown

6.4.3 Single-Test Inversions of Test 90/S1/T2

Eleven inversions have been done of test 90/S1/T2, in which well 11 was pumped from the middle sand channel and drawdowns were observed in the upper and middle sand channels of wells 1 and 7, and in the upper/middle sand channel of well 5. Some of the inversions look for a gap in the clay layer by using an attractor that increases permeability, with an additive increment $\Delta T \approx 10^3 T_0$, while others look for the clay layer itself by using an attractor that decreases permeability, with a multiplicative increment $\Delta T \approx .01$. Because the permeability contrasts are so great, essentially no flow occurs through the low-permeability portion of the intermediate layer, making it unnecessary to modify storativity there. Various values of the permeability increments or decrements were used, along with different numbers of affine transforms (either $k = 4$ or $k = 6$), and different optimization algorithms (either simulated annealing or simplex annealing). Most of the inversions successfully match the main features in the pressure transients for the three observation wells, which requires that the clay layer be present between wells 1, 7, and 11, yielding distinct responses in the upper and lower model layers, but absent around well 5, yielding the same pressure response in the upper and lower model layers. Observed and modeled pressure transients are displayed in Figure 6.36 for one inversion. The solid lines and solid dots correspond to the middle sand channel and the dashed lines and open dots correspond to the upper sand channel. The effect of the intermittency of the upper clay layer is striking. Where the clay layer is present there are two widely separated pressure transients, and where it is missing the upper and middle sand channels respond in unison. The model captures the main features of the observed data very well. The final attractor for this inversion is shown in Figure 6.37; the attractor acts to increase permeability, and thus shows locations where the clay layer is missing. The corresponding permeability distribution for the intermediate layer is shown in Figure 6.38. The energy for successful inversions ranges from about $E=14.5$ to $E=16.5$; some of the permeability distributions for the intermediate clay layer are shown in Figure 6.39. Recall that only wells 1, 5, 7, and 11 were used for test 90/S1/T2, so the permeability distribution is only reliable for the northeast quadrant of the well field.

Figure 6.35. The Gypsy pilot-site well field showing a schematic view of the upper and middle sand channel well tests. The shaded lines connect the observation and pumping wells for a given test.

below to give the correct relative magnitude for the pressure response in the pumping well.

Test	Pulse	Reported Flow Rate	Modified Flow Rate
90/S2/T2	1	230	230
	2	575	57.5
	3	287	287
	4	282	282
90/S2/T3	1	263	263
	2	430	230
	3	240	240
	4	288	288

90/S1/T2 gum09 E=14.53

Figure 6.37. Final attractor for one inversion of test 90/S1/T2. Attractor points identify locations of high permeability in the intermediate layer between the upper and middle sand channels.

90/S1/T2 gum09 E=14.53

Figure 6.36. Observed and modeled pressure transients for one inversion of test 90/S1/T2.

gum09 $E=14.53$

Figure 6.38. Permeability distribution corresponding to the attractor shown in Figure 6.37.

gum05a $E=13.73$
 -65 0
 $\ln T/T_0$

gum06a $E=15.50$
 -65 0
 $\ln T/T_0$

gum11 $E=14.41$
 0 10
 $\ln T/T_0$

gum10 $E=14.57$
 0 10
 $\ln T/T_0$

Figure 6.39. Series of permeability distributions for the inversions of test 90/S1/T2.

6.4.4 Single-Test Inversions of Test 90/S2/T2

In test 90/S2/T2, well 9 was pumped and pressures were observed in wells 1, 5, 7, and 11. Early inversions of test 90/S2/T2 yielded energies over $E=100$, with pressure transients that grossly mismatched the observed values, as illustrated in Figure 6.40. After some study, it was determined that the inversion program was not broken, but that strongly scattered early-time observed pressures were dominating the matching procedure. In general, not all the observed pressure data is used for the well-test analysis, as pressures are recorded far more frequently than is necessary to discern most trends. A preprocessing program is used to select enough points to resolve pressure variations that correspond to the step flow rate changes which occur during the tests. However, this program is not very sophisticated and tends to include too many data points when there is a lot of scatter in the observed pressure data. Therefore, for all the well tests, the observed pressure transients to be inverted were edited by hand to remove many of the widely scattered data points, making the density of points similar for early and late times. With these changes the inversions of test 90/S2/T2 improve significantly, yielding energies around $E=10$. Figure 6.41 shows the pressure transients for a typical example, in which $\Delta T = 10^3 T_0$, and Figure 6.42 shows the corresponding attractor, which represents gaps in the upper clay layer. The match is acceptable for all the wells except well 1, for which the calculation shows the same response for the upper and middle sand channels, whereas the observed data shows a significant difference. This comparison suggests that the high permeability region shown in Figure 6.42 just to the north of well 1 should not be present. None of the inversions show the correct difference between upper-sand-channel response and the middle-sand-channel response for all four observation wells.

90/S2/T2 gum15 E=100.86

Figure 6.40. Observed and modeled pressure transients for an inversion of test 90/S2/T2 before observed data had been edited.

90/S2/T2 gum39a E=8.72

Figure 6.41. Observed and modeled pressure transients for an inversion of test 90/S2/T2 after observed data had been edited.

90/S2/T2 gum39a E=8.72

Figure 6.42. The final attractor for an inversion of test 90/S2/T2. Attractor points identify locations of high permeability (gaps in the clay layer) in the intermediate layer between the upper and middle sand channels.

6.4.5 Single-Test Inversions of Test 90/S2/T3

In test 90/S2/T3, well 9 was pumped and pressures were observed in wells 1, 5, 7, and 11. Test 90/S2/T3 is the only test in which the upper sand channel interval of the pumping well was pumped. In all the other upper/middle tests, the middle sand channel was pumped and a greater pressure change was observed in the middle channel interval of the observation wells than in the upper channel interval, as would be expected for two partially connected channels. Unexpectedly, test 90/S2/T3 also showed pressure changes that were greater in the middle sand channel than in the upper sand channel, for observation wells 1, 7, and 11. This suggests that the transmissivity of the upper sand channel is less than that of the middle sand channel, and that a model which assigns the equal values of transmissivity to each sand layer is inadequate. After some trial and error, a transmissivity ten times greater in the middle sand channel than in the upper sand channel was chosen for the inversion of test 90/S2/T3. This modification is at least qualitatively supported by the well log information, which suggests that the upper sand channel is thinner and/or produces a weaker 'sand' signal than the middle sand channel for wells 1, 9, and 11. With this change in the conceptual model, several inversions successfully matched the difference between the middle and upper sand channel pressure transients. Figure 6.43 shows the pressure transients for a typical example, in which $\Delta T = 10^3 T_0$, and Figure 6.44 shows the corresponding attractor, which represents gaps in the intermediate layer. This modified conceptual model, with different transmissivities for the upper and middle sand channels, was used for all subsequent inversions of the upper/middle well tests.

90/S2/T3 gum21 E=15.16

Figure 6.43. Observed and modeled pressure transients for an inversion of test 90/S2/T3.

90/S2/T3 gum21 E=15.16

Figure 6.44. The final attractor for an inversion of test 90/S2/T3. Attractor points identify locations of high permeability (gaps in the clay layer) in the intermediate layer between the upper and middle sand channels.

6.4.6 Single-Test Inversions of Test 90/S3/T2

In test 90/S3/T2, well 8 was pumped and pressures were observed in wells 5, 7, 9, and 11. In all the observation wells there was no difference between the upper and middle sand channel responses. This is not surprising, as the upper clay layer is absent in well 8, leaving no distinction between the upper and middle sand channels there. Four inversions of this test successfully matched this pressure response, however, they did not yield consistent permeability distributions. Placing gaps in the clay layer either at the pumping well (as the well-log lithology suggests), at each of the observation wells (in contradiction to the well-log lithologies), or both places allows the pressure responses to be matched equally well. Including the pressure response at the pumping well as part the observed data to be inverted would help the inversion to place gaps at the pumping well, but there would still be no reason to avoid placing gaps other places as well. In conclusion, the pressure responses for test 90/S3/T2 do not provide enough information about the reservoir to be useful in single-test inversions, but they can be an important contribution to a co-inversion of multiple well tests.

6.4.7 Single-Test Inversions of Test 90/S4/T2

In test 90/S4/T2, well 1 was pumped and pressures were observed in wells 5, 7, and 11. This is the same set of wells used in test 90/S1/T2, and not surprisingly, the results are similar. All three inversions yielded good matches to the pressure transients and placed a gap in the clay layer between the pumping well and well 5, or a gap localized around well 5.

6.4.8 Multiple-Test Co-Inversions of Tests 90/S1/T2, 90/S2/T2, and 90/S3/T2

The goal of co-inversion is to use multiple tests which provide complementary information about the reservoir. However, because the forward calculation becomes slower as more tests are added, it is also desirable to minimize the number of tests to be co-inverted. For example, it would not be worthwhile to co-invert tests 90/S1/T2 and 90/S4/T2, because they both contain information about the northwest quadrant of the well field. Similarly, we needn't co-invert tests 90/S2/T2 and 90/S2/T3 when the inversion is looking for gaps in the clay layer, although if the inversion were searching for variability within each sand layer, a co-inversion of tests 90/S2/T2 and 90/S2/T3 would be useful. Two pairs of tests have been co-inverted (tests 90/S1/T2 and 90/S3/T2 and tests 90/S2/T3 and 90/S4/T2) and co-inversion of three tests (90/S1/T2, 90/S2/T2, and 90/S3/T2) has been done. The co-inversions of two tests were done for practice, as Figure 6.35 suggests that three tests is really the minimum number needed to include all independent information about the reservoir. Figure 6.45 shows the observed data for the three-test co-inversion. If only one pressure transient is shown for a given segment of the test, it means that the upper and middle sand channels responded identically. In inversions that look for clay-layer gaps, the key features to try to match are the differences between middle and upper sand channel responses for each observation well. For example, there is a large difference in upper and middle responses in wells 1 and 7 when well 11 pumps, but a much smaller difference when well 9 pumps.

A three-stage sequence was followed for the first co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. In the first stage, simulated annealing was used with simple attractors determined by only six unknown parameters ($k = 3$ affine transforms of the rotation matrix form, with $C_i = 0.667$ and $\theta_i = 0$ fixed, and two components of b_i variable), to get a rough picture of heterogeneity. Attractors of this form will always have a triangular shape, with the b_i specifying the coordinates of the triangle's corners. The attractor points act to increase permeability ($\Delta T = 10^3 T_0$) and hence represent gaps in the upper clay layer. The initial attractor, a triangle with its apex near well 5 and its base near well 8, produced an energy of $E = 42$. With simulated annealing, permeability distributions are tried at random so a great variety of distributions may be considered. The final energy of the first stage was $E = 26.2$. Next, the inversion was restarted using the final attractor of the first stage, but considering nine parameters as unknowns (θ_i variable), which allows more variability in the permeability distribution. The second stage resulted in an energy decrease to $E = 23.0$. In the final stage, the inversion was restarted using

Tests 90/S1/T2, 90/S2/T2, 90/S3/T2: Observed Data

Figure 6.45. The observed data for the three-test co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2.

the final attractor of the second stage, using simplex annealing rather than simulated annealing as the optimization algorithm. Simplex annealing makes small non-random changes in the trial permeability distributions, which are specifically designed to move to lower energy values. The final stage produced a further slight decrease in energy, to $E = 22.9$. Figure 6.46 shows the attractors resulting from each stage for the three-test co-inversion. Figure 6.47 shows the pressure transients at the end of the final stage. With the exception of the response in well 11 when well 8 is pumped, the difference between upper and middle sand channel responses is matched adequately.

Three other co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 were done in which the attractor represented gaps in the upper clay layer. As before, $\Delta T = 10^3 T_0$. The inversions used $k = 6$ affine transforms of the rotation matrix form, with three unknown parameters each (θ_i and two components of b_i). The resulting energies range from $E = 20.7$ to $E = 21.7$. The decrease in energy over the previous inversion using $k = 3$ affine transforms is not surprising, as 18 degrees of freedom are available to match heterogeneities rather than the nine of the previous inversion. Figure 6.48 shows the resulting permeability distributions, which consistently locate the gap in the upper clay layer as an east-west trending band centered on well 5, which extends closer to well 9 than to well 7. Although the well lithologies suggest that the gap in the clay layer extends to the south as far as well 8, it is apparent that the well-test data, which does not include any observations from well 8, does not contain this information. This shortcoming points out the value of using the pressure response from the pumping well in addition to that from observation wells, which was not possible in the present work due to computational limitations (the 16.67 meter lattice spacing used is too coarse to adequately model the pressure response in the pumping well, and using a finer mesh around each pumping well would have slowed down the calculations excessively).

Three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 were done in which the attractor points decrease permeability and hence the attractor represents the clay layer itself, rather than gaps in it. For these cases, $\Delta T = 0.01$ and $\Delta S = 0.5$. As above, $k = 6$ affine transforms with three unknown parameters each were used. The resulting energies range from $E = 20.6$ to $E = 23.5$, which are comparable to the previous $k = 6$ inversions, indicating that there is little advantage in looking for a gap in the clay layer rather than the clay layer itself. The resulting permeability distributions, shown in Figure 6.49, nicely complement those in which the attractor represents gaps in the clay layer.

Figure 6.46. Attractor at the end of each stage of a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. Attractor points identify locations of high permeability (gaps in the clay layer) in the intermediate layer between the upper and middle sand channels.

s123 gum36b E=22.86

Figure 6.47. Observed and modeled pressure transients for a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. Only one third of the observed data points used in the match are shown, to enable the calculated curves to be more visible.

gum38 E=20.7

gum40 E=21.03

gum43 E=21.68

Figure 6.48. Permeability distributions for three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 in which the inversion searched for gaps in the upper clay layer.

Figure 6.49. Permeability distributions for three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 in which the inversion searched for the upper clay layer.

The pressure transients for the lowest-energy co-inversion, corresponding to the permeability distribution shown in the left frame of Figure 6.49, are shown in Figure 6.50. Although the main features of the observed pressure transients, in particular the differences between the upper and middle sand channel responses, are well matched, significant discrepancies remain. It appears that a more sophisticated conceptual model, which allows variability in both the upper clay layer and the upper and middle sand channels themselves is necessary to achieve this. In light of the lower sand channel inversions, which required significant heterogeneity within one sand channel to match all pressure responses, this is not an unreasonable expectation. A simple means of examining this more elaborate conceptual framework is explored below in Section 6.4.10.

s123 gum45a E=20.60

Figure 6.50. Observed and modeled pressure transients for the lowest-energy co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. The permeability distribution is shown as the left frame in Figure 6.49. Only one third of the observed data points used in the match are shown, to enable the calculated curves to be more visible.

6.4.9 Incorporating Well-Log Lithology in Well-Test Analysis

In view of the difficulty in achieving good matches to the observed pressure responses described above, an alternate approach, making use of both well-log lithologic data and interference data has been explored. The well-log data indicates the presence or absence of the upper clay layer at six points, the well locations, only. There are a variety of ways this point information can be interpolated to create a complete picture of the clay layer and its gaps, as suggested in Figure 6.51. Each of these interpolations (with additive increment $\Delta T = 10^3 T_0$) has been used to simulate the sequence of three tests 90/S1/T2, 90/S2/T2, and 90/S3/T2, and the resulting energy, the integrated mismatch between the observed and calculated pressure transients, is shown in Figure 6.51. The strong variation in energy suggests that a large clay gap is much more likely than a small one. The configuration with the lowest energy also provides guidelines for a good starting shape for further inversions or co-inversions. The first few accepted attractors and the corresponding energies for one such co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 are shown in Figure 6.52.

The display of energies for various clay gaps shown in Figure 6.51 suggests that the inversion can be posed with only two unknown parameters, the width and height of a triangular gap in the upper clay layer. This simplification enables the energies to be presented as a two-dimensional surface, the minimum of which represents the optimal solution to the inverse problem. Such an energy surface is shown in Figure 6.53. It is a contoured representation of the energies for the configurations shown in Figure 6.51, with the addition of more extreme gap configurations, which are not necessarily consistent with the borehole lithologies. The black line outlines the portion of the energy surface which is consistent with the borehole lithology. An ideal energy surface would have a single minimum which is consistent with geologic information (i.e., within the outlined region) but is much more localized, effectively singling out one correct way to interpolate between boreholes.

In the y (height) direction, the minimum in the energy surface is rather narrow, and is consistent with the borehole lithology. Thus, the height (north-south extent) of the gap in the clay layer is well-constrained by the co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. In contrast, in the x (width) direction, the minimum in the energy surface is very broad, and is not confined to gap configurations consistent with the borehole lithologies. The energy minimum is sharply defined on the low-width side, and its location does rule out a range of narrow gaps. The extent of the energy minimum is not well-defined on the high-width side, as energies remain low

Figure 6.51. Nine possible interpolations of the point lithologic data obtained from well-logs. The dark regions represent gaps in the clay layer between the upper and middle sand channels. The energy values show the mismatch between pressures calculated for each of these models and the observed data for tests 90/S1/T2, 90/S2/T2, and 90/S3/T2, shown in Figure 6.45.

as wider and wider gaps are considered. This means that the well-test data being inverted can be comparably well matched with or without an upper clay layer present in wells 7 and 9, although the borehole lithologies suggest the layer exists in both wells. Comparing the observed and modeled pressure transients for a wide-gap model (Figure 6.54) confirms this notion. Of all the observed data for wells 7 and 9, only the response at well 7 when well 11 pumps shows a significant difference between upper and middle channel responses. Given the other mismatches

Figure 6.52. The initial attractor, the first 19 accepted attractors, and the corresponding energies for a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. Attractor points identify locations of high permeability (gaps in the clay layer) in the intermediate layer between the upper and middle sand channels.

Figure 6.53. Two-dimensional energy surface as a function of the height and width parameters of a triangular gap in the upper clay layer centered on well 5. The black line outlines the portion of the energy surface which is consistent with the borehole lithology. The circles show the results of co-inversions using the direction-set method (black), simulated annealing (grey), and simplex annealing (white). To convert from parameter space to physical space, multiply height and width parameters by 1600 m.

for this simplistic model, not reproducing this difference does not disqualify wide-gap configurations. However, if a more complicated model with greater variability can produce a better match overall (for example, closely matching the well 5 pressure transients, not just showing the upper and middle channel responses as identical), then the lower energy ranges being considered will disqualify a model that does not show distinct upper and middle channel responses at well 7 when well 11 is pumped. Development of such a model is described in Section 6.4.10.

Overall, the technique of incorporating borehole lithologic information into the well-test analysis can be of great value. One starts with information known about the system at a series of points, and uses the well-test data to provide information on the interpolation of that information to inter-well regions. By constraining the inversion in this way, the number of unknown parameters can be greatly reduced, because much of the structure of the heterogeneity is specified by the point values obtained from the boreholes. If the number of parameters can be reduced to two, an energy surface can be constructed, the features of which can provide great insight into the information content of the well-test data.

s123 III E=26

Figure 6.54. Observed and modeled pressure transients for a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2, using a triangular-gap model with a 1173-m-wide, 240-m-high gap in the upper clay layer (corresponding to $w = 0.733$, $h = 0.15$ in the parameter space shown in Figure 6.53).

With an energy surface, it is also possible to compare the performance of various optimization algorithms. The returned energies for several inversions using different optimization algorithms are shown in Figure 6.53. The simulated-annealing inversions all end up somewhere in the minimum of the energy surface, whereas the simplex-annealing and direction-set methods sometimes get stuck in high-energy regions, and cannot find the minimum. However, the simulated-annealing inversions require far more forward calculations (several thousand) than do the simplex-annealing (around 50) or direction-set (around 100) inversions. For the present problem it is more efficient overall to do a series of quick simplex-annealing or direction-set inversions using different random seeds, to enable identification of inversions that are stuck at high energy values, than it is to do one simulated annealing inversion. However, as the number of unknowns increases, the simplex-annealing and direction-set methods both get expensive more rapidly than does simulated annealing. Furthermore, increasing the number of unknowns greatly increases the complexity of the energy surface, so the greater ability of simulated annealing to avoid getting stuck often makes it the method of choice.

6.4.10 Building a Three-Dimensional Model with Sequential Two-Dimensional Inversions

The initial inversion strategy for upper/middle sand channel well tests was to assume that the only heterogeneity in the system was in the discontinuous intermediate clay layer, because it was presumed to have a dominant effect on the pressure transients. Various inversions yielded a consistent picture of the clay layer with a large gap in it, centered on well 5. Because none of the corresponding models perfectly matched the pressure transients, it was decided to consider more subtle heterogeneities within the upper and middle sand channels in the model as well. Although the present version of the IFS inversion method is restricted to creating two-dimensional attractors (and therefore searching for two-dimensional heterogeneities), it is possible to sequentially look for heterogeneities in different layers of the model. The heterogeneous permeability distribution in the intermediate clay layer can be held fixed while the inversion looks for heterogeneities within either the upper or middle sand channel.

The procedure followed was to use the permeability distribution from the best co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2, shown in the left frame in Figure 6.49, then look for variability within the middle sand channel while co-inverting these same three tests. An IFS with $k = 6$ affine transforms in the rotation matrix form was used, with the plus-minus mapping algorithm, and multiplicative increments $\Delta T = \pm 1.6$ and $\Delta S = 1.0$. The inversion resulted in an energy decrease from $E = 20.6$ to $E = 11$, and a transmissivity distribution for the middle sand channel as shown in the left frame of Figure 6.55. The corresponding pressure transients are shown in Figure 6.56. Several other inversions looking for middle-sand channel variability were done, using different starting permeability distributions for the intermediate clay layer; the transmissivity distributions are also shown in Figure 6.55. The common features of all the inversions are the high-transmissivity region around well 8, and the low-transmissivity region to the northeast of well 5. The impact of these features is readily apparent by comparing the pressure transients shown in Figure 6.56 with those for a uniform middle sand channel (Figure 6.50). The larger response of wells 5, 9, and 11 when well 8 pumps is due to increased transmissivity in the paths between these wells, compared to adjacent regions. Conversely, the smaller response of well 5 when well 11 pumps is due a region of decreased transmissivity between these two wells.

The transmissivity distributions shown in the left frames of Figures 6.49 and 6.55 were then held fixed while the transmissivity in the upper sand channel was allowed to vary in a co-inversion of tests 90/S2/T2, 90/S2/T2, and 90/S3/T2. Again an IFS with $k = 6$ affine transforms was used, with the plus-minus mapping algorithm, and multiplicative increments $\Delta T = \pm 1.6$ and

gum50 E=11.0

gum48 E=13.11

gum46 E=17.31

Figure 6.55. Transmissivity distributions for three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 in which the inversion searched for heterogeneities within the middle sand channel.

Figure 6.56. Observed and modeled pressure transients corresponding to the transmissivity distribution shown in the left frame of Figure 6.55. Only one third of the observed data points used in the match are shown, to enable the calculated curves to be more visible.

$\Delta S = 1.0$. The inversion resulted in an energy decrease from $E = 11$ to $E = 8.5$, and a transmissivity distribution for the upper sand channel as shown in the left frame of Figure 6.57. The corresponding pressure transients are shown in Figure 6.58. Several other inversions looking for upper-sand-channel variability were done, using alternate random seeds; the transmissivity distributions are also shown in Figure 6.57. The common features of all the inversions are a high-transmissivity region around well 5, especially toward the west, and a region of low transmissivity between wells 5 and 8. Two of the three distributions also show low transmissivity around well 11, especially toward well 1. The impact of these features may be seen by comparing the pressure transients shown in Figure 6.58 with those for a uniform upper sand channel (Figure 6.56). The larger upper-channel response in well 5 when well 9 pumps is due to increased transmissivity between the two wells, whereas the unchanged response in well 5 when well 8 pumps reflects the balance of low and high transmissivity regions between these two wells. The low-transmissivity region between wells 1 and 11 decreases the response at well 1 when well 11 pumps.

Overall, the final product of the sequential model-building produces a reasonable match to most of the features of the pressure transients for the three well tests. The decrease in energy from $E = 20.6$ to $E = 8.5$ as variability is allowed in the middle and upper sand channels suggests that heterogeneity within sand channels has a noticeable effect on the flow behavior of the Gypsy formation, although the dominant effect remains the presence or absence of the extremely low-permeability clay layers.

gum55 $E=8.46$

gum67 $E=8.90$

gum61 $E=9.19$

Figure 6.57. Transmissivity distributions for three co-inversions of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 in which the inversion searched for heterogeneities within the upper sand channel.

Figure 6.58. Observed and modeled pressure transients corresponding to the transmissivity distribution shown in the left frame of Figure 6.57. Only one third of the observed data points used in the match are shown, to enable the calculated curves to be more visible.

6.4.11 Cross-Validation Studies

Of the upper/middle sand channel well tests, two pairs of tests were done using the same subset of the six pilot-site wells but with different pumping wells, which makes them good candidates for a simple cross-validation study in which the model developed by analyzing one test is used to predict the other. As summarized in Table 6.8, each of the four predictions yields a much higher energy than does the model calibrated using that particular test. Some increase in energy is expected, as different flow fields are set up by the different pumping wells, however, for three of the four tests the prediction made with the opposite model is no better than that obtained using a uniform-medium model. The lack of reciprocity between the pressure responses of tests 90/S4/T2 and 90/S1/T2, shown in Table 6.3, provides a possible explanation for the mediocre predictions for this pair of tests. The data required to check reciprocity are not available for tests 90/S2/T2 and 90/S2/T3. If reciprocity does hold, the poor predictions for these tests suggests that the simple model used for single-test inversions (uniform sand channels above and below a heterogeneous clay/sand layer) is fundamentally inadequate to represent the upper/middle sand channel system.

Table 6.8. Energies for cross-validation studies among upper/middle sand channel tests using common wells.

Test	Pumping Interval	Observation Wells	Best Single-test Inversion	Predicted Using Other Best Model†	Uniform Medium Model‡
90/S1/T2	11m	1, 5, 7	14	32	76
90/S4/T2	1m	5, 7, 11	7	26	29
90/S2/T2	9m	1, 5, 7, 11	9	23	17
90/S2/T3	9u	1, 5, 7, 11	15	80	30

†Model from 90/S1/T2 used to predict 90/S4/T2 and vice versa; model from 90/S2/T2 used to predict 90/S2/T3 and vice versa.

‡Middle sand transmissivity and storativity taken from base values for best co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2: $T_0 = 2.71 \times 10^{-5} \text{ m}^2/\text{s}$, $S_0 = 4.4 \times 10^{-5}$, upper sand 1/10th as transmissive as middle sand, no intermediate clay layer.

The large decrease in energy obtained for the co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2 when variability in the upper and middle sand channels was considered (Section 6.4.10) suggests that this variability is an important feature of the system as a whole. If this is the case, then the more complicated model developed in the sequential model building exercise should do a better job predicting responses to individual tests than did the simple models used above for cross-validation. Table 6.9 summarizes a cross-validation study in which three models of

steadily increasing complexity are used to predict the pressure responses of all the single-well tests involving upper/middle channel intervals. The simplest model considers the upper and middle sand channels to be a single uniform layer. The second model is based on interpolating borehole lithologic information, as described in Section 6.4.9. It considers uniform upper and middle sand channels which are separated by a discontinuous clay layer with a triangular shaped gap in it. The third model is the result of the sequential model building process described in Section 6.4.10. It considers heterogeneities in all three layers, as inferred from a co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2.

In general there is a decrease in energy as one progresses from the uniform-medium model, to the triangular-gap model, to the sequentially-co-inverted model, supporting the conceptual model and approach to inversion being taken. The sequential model is expected to improve the results for tests 90/S1/T2, 90/S2/T2, and 90/S3/T2, since their responses were used in the co-inversion from which it was derived. The rigorous cross-validation check is for tests 90/S2/T3, 90/S4/T2, 89/S2/T3, and 89/S2/T4. Compared to a uniform-medium model, the energy for test 90/S2/T3 decreases significantly using the sequential model, whereas it increases for the triangular-gap model. Recalling that test 90/S2/T3 is the only test which pumped from the upper sand channel, and that it did poorly in the common-well cross validation study shown in Table 6.8, these results suggest that variability in the upper sand channel is important, and is reasonably represented by the sequential model. In contrast, the energy for 90/S4/T2 does not decrease for the sequential model. This is not too surprising considering that the reciprocity check shown in Table 6.3 indicated that tests 90/S1/T2 and 90/S4/T2 did not produce consistent results.

The energy for the 1989 tests is much greater for the sequential model than for either of the two simpler models. It is problematic to include these tests in the inversion process because each test has such limited observed data available (for test 89/S2/T3 there are two observed pressure transients in the middle sand channel and for test 89/S2/T4 there is one observed pressure transient in the upper sand channel). Thus neither test can be used alone to obtain any information on vertical variability, or much information on lateral heterogeneities. In fact, both tests can be very well matched using a uniform-medium model, as shown in the final column of Table 6.9. A further complication is that well 5, the pumping well for the 1989 tests, is screened over both the upper and middle sand channels so it is not clear how to specify where fluid is pumped from in the model. For the triangular-gap model, where fluid is pumped from makes little difference, as the vertical permeability at well 5 is very high. For the sequential model, on the other hand, a factor of two difference in energy is possible. Finally, the reciprocity check shown in Table 6.3

suggests that there may be problems associated with test 89/S2/T3, although other evidence supports test 90/S4/T2 as the unreliable one. In spite of all these problems, the huge energies obtained for the 1989 tests using the sequential model indicate that there is something wrong with the sequential model in the vicinity of well 5. This finding suggests that using well 5 as an observation well does not provide as much information as using it as a pumping well would. In hindsight, perhaps this should not be too surprising in light of the lithologic evidence that the character of the upper and middle sand channels changes strongly around well 5, going from two separate channels to a single channel.

Table 6.9. Energies for cross-validation studies using various models for all upper/middle sand channel tests.

Test	Pumping Intervals Model†	Uniform Medium Model‡	Triangular Gap Model§	Sequentially Co-inverted Inversion	Best Single-test
90/S1/T2	11m	76	32	9	14
90/S2/T2	9m	17	28	10	9
90/S2/T3	9u	30	47	14	15
90/S3/T2	8u/m	29	23	6	10
90/S4/T2	1m	29	18	24	7
89/S2/T3	5u/m	14	22	118	1
89/S2/T4	5u/m	8	1	95	0.3

†Middle sand transmissivity and storativity taken from base values for best co-inversion of tests 90/S1/T2, 90/S2/T2, and 90/S3/T2: $T_0 = 2.71 \times 10^{-5} \text{ m}^2/\text{s}$, $S_0 = 4.4 \times 10^{-5}$, upper sand 1/10th as transmissive as middle sand, no intermediate clay layer.

‡Best lithology-constrained model described in Section 6.4.9.

§Based on the co-inversion of 90/S1/T2, 90/S2/T2, and 90/S3/T2 described in Section 6.4.10.

6.5 COMPARISON OF HYDROLOGIC INVERSION WITH CROSS-WELL SEISMIC IMAGING

6.5.1 Overview of Cross-Well Seismic Data

BP conducted a series of cross-well seismic surveys at the Gypsy pilot site, using well pairs 1 and 5, 1 and 7, and 5 and 7, and source and receiver spacings of either 0.6 or 3 m (two or ten feet). We have interpreted data from the 0.6-m-spacing surveys for each well pair in light of the lithological model, shown in schematic form in Figure 6.59, and the implications from the well-test analyses that the dense red clay layer is a continuous barrier to flow while the upper clay layer is only a local barrier. The upper clay layer is present in wells 1 and 7 but absent in well 5, and its extent between the three wells is unknown. The layers shown in Figure 6.59 are just linear interpolations between the sand-clay transition depths observed in the wells.

The cross-well seismic data for each of the three well pairs have been displayed as both common source gathers and common receiver gathers. The data quality is good, with features such as refractions, tube waves, and possible reflections readily apparent. These displays provide a good view of near-well lithologic variations (the common source gathers illustrate variation at the receiver while the common receiver gathers illustrate variation at the source), and all the variations in borehole lithology shown in Figure 6.59 can be identified. The cross-well seismic data is also consistent with the digital array sonic logs conducted in each well, and corresponds most closely to the variations in shear wave component, though no sheer waves exist in the data.

While it is useful to verify that lithological, geophysical-log, and cross-well data provide consistent information at well locations, the real purpose of cross-well surveying is to interpolate to regions between wells. First-arrival-time inversions, reflection studies, and guided wave analyses may be used to attempt this.

6.5.2 First Arrival-Time Inversions

A computerized inversion of first arrival times for well pair 5 and 7 [Vasco *et al.*, 1996] indicates a pronounced low-velocity zone over the Gypsy sand interval, depths of 280 to 300 m (930 to 990 feet), as shown in Figure 6.60. The presence of the intervening clay layers cannot be ascertained from this analysis of the first arrival times. As shown in Figure 6.59, these layers are probably only about 1 to 2.5 m thick, which is small compared to the cross-well source and receiver spacing of 0.6 m and the dominant seismic wavelength of about 3 m, making it possible that these layers are too thin to resolve. Another limitation of first-arrival-time inversion arises from the difficulty in picking first arrivals. In many cases the first arrival is probably not the direct arrival. In a low velocity layer the first arrival will be the refracted or head wave.

Figure 6.59. Schematic lithologic cross-sections of the Gypsy pilot site for well pairs 1 and 5, 1 and 7, and 5 and 7, for which cross-well seismic surveys were conducted by BP.

Figure 6.59. continued.

Figure 6.59. continued.

Figure 6.60. Seismic velocity distributions for the plane containing wells 5 and 7, obtained by a computer inversion of first arrival times [Vasco *et al.*, 1996].

6.5.3 Reflection Studies

We have examined reflection signatures in the common source/multiple receiver gathers from the cross-well seismic survey from well 5 to well 1, in conjunction with hydrologic results. Reflections show up as 'V' shapes in the common source/multiple receiver gathers, with the apex of the V at the depth of the layer off which seismic waves reflect. There is a strong reflection from the Tallant/Gypsy interface at depths of about 300 m (990 feet) when the source and receivers are above the interface (Figure 6.61), and a weaker signal when the source and receivers are below it. We also see some indication of reflections off the boundary between the top of the Gypsy and the overlying flood plain deposits at a depth of about 287 m (942 feet). Figure 6.61 also suggests that there are reflections off the dense red clay layer at the 295 m (970 foot) depth, but shows no evidence of any reflections at the depth of the upper clay layer, 290 m (950 feet). This suggests that the gap in the upper clay layer observed at well 5 is an extensive rather than highly localized feature, which is consistent with the results of the hydrologic inversions of the upper/middle sand channels. However, these conclusions must be categorized as tentative because the aspect ratio of the Gypsy seismic surveys (well spacing 100 m or more compared to formation thickness of 15-20 m) makes interpretation of reflection signals difficult, as most rays arrive nearly parallel to one another.

6.5.4 Guided Wave Analyses

If there are continuous low-velocity paths between wells, it may be possible for guided seismic waves to propagate. These waves show less attenuation than do conventional seismic waves, and can be identified in common source or common receiver gathers as high-amplitude high-frequency signals which last a long time and occur when both the source and receiver are at the depth of the wave guide. Figure 6.62 shows a possible guided wave between wells 5 and 7, at the depth of the lower sand channel. No such signals were found at the depths of the upper and middle sand channels. These findings are consistent with the well-test findings that the lower sand channel is a continuous, isolated channel which supports propagation of a guided wave whereas the upper and middle channels are intermittently connected, so do not allow propagation of guided waves.

Figure 6.61. Common source/multiple receiver gathers for the 0.6-m (two-foot) cross-well seismic survey between wells 1 and 5; some interpretations made in conjunction with the geologic and hydrologic data are noted.

Figure 6.62. Example of possible guided waves at the depth of the lower sand channel at the Gypsy pilot site.

6.6 COMPARISON WITH TRADITIONAL GEOSTATISTICAL ANALYSIS

6.6.1 Introduction

The use of interference tests to help build hydrological models, as described in the present work, is not the only way to characterize heterogeneous reservoirs. Another approach, examined in this section, is to estimate transmissivity values at various locations in the reservoir from single-well tests (most often buildup tests), then interpolate between these locations using geostatistical information derived from core-scale measurements of permeability. Permeabilities measured on core plugs taken from the Gypsy outcrop-site are used to construct variograms, and transmissivity values inferred from pilot-site pressure buildup tests are used as conditioning points for the generation of a two-dimensional areal transmissivity distribution for the lower sand channel at the pilot site. This transmissivity distribution is then used to model several lower-sand-channel interference tests, and the results are compared with previous inversion results.

6.6.2 Estimation of Variograms

The outcrop site provides two extensive permeability data sets. The first is from the road-cut exposure (Figure 6.1), and consists of 990 permeability values. The second is from 22 of the boreholes drilled behind the road cut, which are spaced 30 to 60 m (100 to 200 feet) apart in a rectangular array (Figure 6.2), and consists of 1051 permeability values. Because of the large size of these two data sets, and the different coordinate systems used to identify data locations in each one, they were analyzed separately. A public-domain set of computer codes known as Geostat Toolbox was used for the variography analysis. The log of permeability, rather than permeability itself, is used as the basis for calculating the variograms. Because the variograms will be used to estimate lateral variability in a two-dimensional model, no vertical-direction variograms were constructed.

The road-cut permeability data points are identified by (x,y,z) coordinates, where x increases from west to east along the road cut, which runs nearly east-west, y increases from south to north (the road cut is nearly vertical, but is divided into sections with three different y values by two benches), and z increases upward. To make the large data set more manageable, x -direction variograms for each of the three y values were created separately, as shown in Figure 6.63. The three variograms all show rather different sill values, but similar correlation lengths of about 30 meters.

Road-Cut and Boring Variograms

Figure 6.63. Variograms of log permeability from the Gypsy outcrop site road-cut (R.C.) and boring (B.) data.

The boring permeability data points also use x increasing from west to east, y increasing from north to south, and z increasing upward. In this case, there are enough different x and y values to create both x - and y -directional variograms, in addition to an omni-directional variogram, as shown in Figure 6.63. The variograms for the different directions are similar. A comparison of the road-cut variograms and boring variograms suggests a continuous variogram can be constructed by using the $y = 0$ m road-cut data for small lags and the omni-directional boring data for large lags. Such a combination variogram is shown in Figure 6.64, along with a fitted curve, given by $\gamma = 4h^{0.25}$.

6.6.3 Generation of Transmissivity Distribution

Two methods were used to generate transmissivity distributions for the lower sand channel of the Gypsy pilot site. In both cases transmissivity values inferred from matching analytical solutions to lower-sand-channel buildup tests in wells 1, 5, 7, 8, and 11 [Dowdle *et al.*, 1990;

Combined Road-Cut and Boring Variogram

Figure 6.64. Variogram combining $y = 0$ m road-cut data and omni-directional boring data. Grey points are the original points; black points are equally spaced points used by CRFGEN. The solid curve is a power law fit to the data, used for kriging.

Papadopoulos *et al.*, 1991] were used as conditioning points at which the transmissivity was held fixed. Results from the buildup test for well 9 were not included because of the suspected packer failure in that well. Figure 6.65 shows a kriged transmissivity distribution, which provides a smooth interpolation between the five fixed points. The kriging interpolation uses a log permeability distribution with a mean of 7.15 ($e^{7.15}$ is the permeability in millidarcies corresponding to the arithmetic average of the five buildup-test transmissivities, assuming a lower-sand-channel thickness of 8 m (26.3 feet)) a standard deviation of 3.7 (the square root of the sill of the road-cut variogram for $y = 0$ m), and the power-law approximation to the observed variogram shown in Figure 6.64. Figure 6.66 shows two transmissivity distributions created with a correlated-random-field generator (here called CRFGEN), which uses simulated annealing to match user-specified variograms [A. Datta-Gupta, personal communication, 1994]. CRFGEN uses the same mean and standard deviation as the kriging interpolation, but can use the actual observed

Figure 6.65. Lower-sand-channel transmissivity distribution generated by kriging.

variogram, rather requiring a closed-form curve fit to it, so it is able to include the suggestion of a hierarchical structure shown by the multiple sill structure of the points in Figure 6.64. The two distributions shown in Figure 6.66 were generated using different random seeds to start the matching process.

The striking difference between the three transmissivity distributions shown in Figures 6.65 and 6.66 is not altogether unexpected, as a kriged field will always be much smoother than a random field generated to match a variogram. However, in this case the small-scale variability of the transmissivity distribution created by CRFGEN, which is necessary to be consistent with the variogram shown in Figure 6.64, overwhelms any conditioning information provided by the buildup tests, thus precluding any overall resemblance between the three transmissivity distributions. If the variogram given in Figure 6.64 is assumed to be representative of the lower sand channel at the pilot site, then the highly variable character of the transmissivity distributions created by CRFGEN is more realistic than the smooth character of the kriged field. However, there is no reason to suspect that the actual locations of high and low permeability features are correct, as demonstrated by comparing the two different fields generated with CRFGEN.

Two attempts were made to generate random fields with more variability than the kriged field, but which would show a greater sensitivity to the conditioning points. The first used a

Figure 6.66. Lower-sand-channel transmissivity distributions generated by the correlated random field generator CRFGEN, using the variogram shown in Figure 6.64.

power-law curve fit to the $y = 5$ m road-cut variogram, shown in Figure 6.67, which has a somewhat lower sill than the boring variograms have.

Road-Cut Variogram for $y = 5$ m

Figure 6.67. Variogram for the $y = 5$ m road-cut data and a power-law curve fit to it.

Log permeability values from the $y = 5$ m section of the road cut have a higher mean and smaller variance than do values from the $y = 0$ m or $y = 32$ m sections, because they correspond to a middle range of z values which are composed almost entirely of channel sands, rather than combining channel and flood plain deposits as do the higher and lower level samples (see Figure 6.2). If one assumes that the model of the lower sand channel at the pilot site is likewise comprised predominantly of channel sands, with the overlying and underlying low-permeability layers providing no-flow boundary conditions, rather than being part of the model, then it may be more appropriate to use this variogram in the construction of a lower-sand-channel model. Figure 6.68 shows two transmissivity distributions generated with CRFGEN using different random seeds. While there is substantially less variability than in Figure 6.66, the conditioning points still have a negligible effect.

Figure 6.68. Lower-sand-channel transmissivity distribution generated by the correlated random field generator CRFGEN, using a power-law fit to the $y = 5$ m variogram shown in Figure 6.67.

The second attempt to create a less variable transmissivity distribution abandons any attempt to use core-scale permeability measurements from the outcrop site, and instead uses the variogram shown in Figure 6.69, which was constructed using information from the pilot-site buildup tests.

Figure 6.69. Ad hoc variogram constructed from pilot-site pressure buildup data.

The variogram sill is equal to the variance of the five transmissivity values inferred from the pilot-site buildup tests. The correlation distance is about 50 m, half the distance between the pilot-site wells. This value was chosen based on the notion that a buildup test integrates transmissivity values from a large area around the well. Figure 6.70 shows two transmissivity distributions generated by CRFGEN using the variogram shown in Figure 6.69 and two different random seeds. There is substantially less variability than in the previous CRFGEN fields, and the conditioning points now have a noticeable effect.

Figure 6.70. Lower-sand-channel transmissivity distributions generated by the correlated random field generator CRFGEN, using the pilot-site variogram shown in Figure 6.69.

6.6.4 Simulation of Well Tests

Simulating tests 90/S1/T1, 90/S3/T1, and 90/S4/T1 provides a stringent test of a model, as the model must reproduce the three different flow fields that arise because a different pumping well is used for each test. Table 6.10 summarizes the energies for simulations of these three tests using the geostatistically-derived models shown in the previous section, using a uniform-medium model, and using models inferred from IFS inversions that include varying amounts of observed data. The IFS co-inversion of all three tests which used all the available observed data was described in Section 6.3.6; it provides a baseline against which the other models can be compared. This co-inversion yields an energy of $E = 2.3$ and, as shown in Figure 6.71, produces noticeably better match to all the main features of the pressure transients than does a uniform-medium model ($E = 11$), indicating that heterogeneity does play a significant role in controlling flow behavior in the reservoir.

Table 6.10. Energies for a simulation of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, using various transmissivity distributions.

Model	Transmissivity Distribution	Energy‡
Uniform Medium	-	11
<i>Geostatistical Models†</i>		
Kriged Field ($\sigma = 3.7$)	Figure 6.65	11
CRFGEN ($\sigma = 3.7$)	Figure 6.66 top frame	17
CRFGEN ($\sigma = 3.7$)	Figure 6.66 bottom frame	43
CRFGEN ($\sigma = 2.4$)	Figure 6.68 top frame	24
CRFGEN ($\sigma = 2.4$)	Figure 6.68 bottom frame	44
CRFGEN ($\sigma = 0.14$)	Figure 6.70 top frame	10
CRFGEN ($\sigma = 0.14$)	Figure 6.70 bottom frame	11
<i>Hydrologic Inversions</i>		
Inversion of test 90/S4/T1	Figure 6.18 third frame in top row	11
Inversion of test 90/S3/T1	Figure 6.21	20
Co-inversion of tests 90/S3/T1, 90/S4/T1	Figure 6.29 top frame	4
Co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, well 5 data omitted	Figure 6.73	3
Co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1	Figure 6.30	2

†All geostatistical models use a mean log permeability of 7.15. The standard deviation σ equals the square root of the sill of the variogram.

‡Rounded off to integral values

Table 6.10 shows that neither the kriged model ($E = 11$) nor the CRFGEN models (lowest $E = 10$) yields an energy significantly lower than that obtained with a uniform-medium model ($E = 11$), suggesting that the nature of the heterogeneity cannot be adequately captured using

90/S1/T1, 90/S3/T1, 90/S4/T1 BP45

Figure 6.71. Observed and modeled pressure transients for a co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, in which all observed data was used.

single-well test results and a geostatistical approach. Interestingly, the highly variable CRFGEN models that were created using variograms based on core-scale log-permeability measurements with $\sigma = 2.4$ and 3.7 produce higher energies ($E = 17 - 44$) than do models created using variograms based on single-well-tests with $\sigma = 0.14$ ($E = 10 - 11$), pointing out the uncertainties involved in upscaling.

Neither of the models obtained from an IFS inversion of a single well test, with observation wells covering only a part of the well field (tests 90/S4/T1, with $E = 11$ and 90/S3/T1, with $E = 20$) produces a lower energy than does the uniform-medium model ($E = 11$). This reiterates the conclusion that to predict flow conditions throughout a heterogeneous reservoir, it is beneficial to use interference data from as much of the reservoir as possible.

Two models obtained from co-inversions which omitted some of the data for tests 90/S1/T1, 90/S3/T1, and 90/S4/T1 do improve on the uniform-medium model. The relatively low energies obtained from these models ($E = 3.2$ and 3.8) suggests that most of the key features of the transmissivity distribution have been accounted for. The first model was created by co-inverting all observation well data for just two of the three well tests (90/S3/T1 and 90/S4/T1, the co-inversion is described in Section 6.3.5). The second model was created by co-inverting all three tests (90/S1/T1, 90/S3/T1, and 90/S4/T1) but omitting all observation data for well 5 (Figure 6.72 shows the pressure transients obtained by the co-inversion and Figure 6.73 shows the corresponding transmissivity distribution). Both types of data exclusion mimic a possible sequence of reservoir characterization. In the first case, one has a given number of wells and wants to know how many well tests need to be run. When the inclusion of an additional test in the co-inversion procedure does not result in a significant energy increase, enough tests have been conducted. In the second case, one wants to know how many more wells need to be drilled. When the inclusion of data from a new well in the co-inversion procedure does not result in a significant energy increase, enough wells have been drilled.

6.6.5 Conclusions from Traditional Analysis Comparison

The ability of a hydrologic model developed with one set of data to make predictions about another data set is a critical attribute for any model being used as a tool to address real-world problems. In general, Table 6.10 shows that the models developed by hydrologic inversion are more successful than the geostatistical models in predicting new behavior. The reason for this is illustrated in Figure 6.74, which compares the transmissivity distributions obtained by inverting all available data (the 'true' picture of the subsurface), the best geostatistical model (the

s134 no5_3 E=3.18

Figure 6.72. Observed and modeled pressure transients for a co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, in which all observed data for well 5 was omitted. The open circles showing the observed data for well 5 were not used in the inversion, but are shown here to illustrate how well the model can predict additional data.

no5_3 E=3.18

Figure 6.73. The transmissivity distribution returned by a co-inversion of tests 90/S1/T1, 90/S3/T1, and 90/S4/T1 which omitted all observation data from well 5.

CRFGEN model with $\sigma = 0.14$, $E = 9.8$) and the best inverse-based model which omitted some data (the no well 5 inversion, $E = 3.2$). Clearly, the geostatistical model does not capture as many features of the 'true' transmissivity distribution as does the inverse-based model.

It must be pointed out that the present comparison is biased in favor of the inverse-based models because the new behavior being predicted is so similar to the behavior used in their model development (the addition of one more test or one more observation well to a set of interference-test data). In contrast, the geostatistical models are based on single-well tests and small-scale permeability measurements, and then must predict interference-test responses. However, rather than pointing out a flaw in the inverse-based models, the similarity between behavior used for model development and processes occurring during model application is a major strength of inverse-based models, and should be actively considered when designing the tests to be conducted as part of a reservoir characterization.

gt11 $E=9.85$

no5_3 $E=3.18$

bp45 $E=2.34$

Figure 6.74. A comparison of the transmissivity distributions returned by a geostatistical model (left frame), a co-inversion omitting well 5 data (middle frame), and a co-inversion of all available data (right frame).

6.7 CONCLUSIONS OF GYPSY ANALYSES

Combining the sequential inversion results for the upper/middle sand channel analyses along with the results of the lower sand channel co-inversions produces a three-dimensional picture of subsurface heterogeneity at the Gypsy pilot site, as shown in Figure 6.75, which reproduces all the key features of the observed pressure data for lower sand channel tests 90/S1/T1, 90/S3/T1, and 90/S4/T1, and upper/middle sand channel tests 90/S1/T2, 90/S2/T2, and 90/S3/T2. The permeability of the dense red clay layer, separating the lower and middle sand channels is not determined by the inverse process, but is assumed to be negligibly small, based on the results of the matrix display of well-test responses shown in Figure 6.8.

A number of specific conclusions can be made regarding the hydrologic and seismic analyses of the Gypsy pilot site. The matrix display of well-test responses, in conjunction with the borehole lithology, clearly identifies those portions of the Gypsy system which act independently and those which are interconnected, and guides development of the conceptual model of the site. Because the lower sand channel is hydrologically isolated from the upper and middle sand channels, it can be analyzed separately, using a two-dimensional model. The lower-sand-channel hydrologic inversions predict gradual, relatively small-magnitude variations in sand properties, within a hydrologically isolated layer. This is corroborated in the seismic data by the suggestion of guided waves at the depth of the lower sand channel, and by reflections off the top and bottom of this layer (the dense red clay and the Gypsy/Tallant contact, respectively). On the other hand, the upper and middle sand channels are strongly connected, as indicated in the well-bore lithologies by the lack of an upper clay layer in wells 5 and 8, and by the strong responses in both channels during upper/middle sand channel interference tests. The upper/middle sand channel inversions, which idealize the upper part of the Gypsy interval as a three-layer system (upper sand, middle sand, and an intervening layer representing the discontinuous upper clay layer), require sharp, large-magnitude variations in the hydrologic properties of the intervening layer in order to match pressure transients. The seismic data supports the finding that the upper clay layer is strongly discontinuous, by showing no evidence of guided waves through the upper or middle sand channels nor reflections off the upper clay layer. Overall, a largely consistent picture of subsurface variability has emerged, by making use of an understanding of the geological processes which created the formation, considering the well tests individually and as a group, incorporating borehole lithologic data, and comparing results to geophysical images. This approach, which emphasizes well-field scale observations, is more successful than the traditional geostatistical approach, which makes use of hundreds of small-scale permeability measurements.

Figure 6.75. Three-dimensional representation of the subsurface heterogeneity at the Gypsy pilot site.

Several more general implications for effective use of the IFS inverse method have been brought out by the Gypsy analysis as well. Firstly, it is very useful to co-invert multiple tests using different pumping wells, in order to include information from as much of the well field as possible, and under different flow conditions. Secondly, in order to meaningfully invert pressure data for a highly heterogeneous system, one must carefully choose which observations to include in the objective function, and evaluate the pressure transient matches during the course of the inversion, rather than merely judging the success or failure of an inversion based on the returned energy value. Thirdly, it would be desirable to include the pressure response at the pumping well, especially if there are few observations wells with analyzable data. This can be done in a straightforward way only if the computational grid is fine enough around the pumping well to properly represent the sharp pressure gradients which occur there. Such a fine resolution greatly increases computation time, by not only increasing the size of the grid, but also by decreasing the length of time step that can be taken. An alternative approach would be to not include pressure data at the pumping well directly, but to add a penalty term to the objective function if some key feature of the pumping-well response were not matched. For example, in the upper/middle sand channel well test in which well 8 pumps (90/S3/T2), the pressure responses in the upper and middle layers of well 8 should be identical, because the upper clay layer is missing there and well 8 has only one screened zone over the upper/middle sand channel intervals. With a coarse grid, the pressure response would not be accurately simulated, but the difference between upper and middle sand channel layers could easily be calculated.

Finally, the Gypsy analysis has illustrated that code development and code application need not be isolated events, but can proceed iteratively. The first step necessary for the Gypsy analysis, the modification of TRINET to allow time-varying flow rates, enabled the co-inversion of multiple tests, and also required the introduction of the diffusivity optimization. The upper/middle sand channel interconnectedness required use of a three-dimensional flow model, and led to the concept of sequential inversions using two-dimensional attractors. All of these options greatly enhance the applicability of the method.

7. SUMMARY, CONCLUSIONS, AND FUTURE WORK

7.1 SUMMARY

7.1.1 *Development of the IFS Inverse Method*

An inverse method to estimate heterogeneous hydrologic property distributions based on well-test analysis has been developed. A numerical model is used to simulate transient draw-downs at multiple observation wells during one or more interference tests. The trial hydrologic property distributions considered during the inversion process are generated using iterated function systems (IFS's), and are constructed to have self-similar or fractal geometry, which greatly decreases the number of unknown parameters that must be determined by the inversion. A variety of standard optimization algorithms may be used to search for the parameters of the IFS which minimize the mismatch between the simulated and observed well-test response. The objective function, which quantifies this mismatch, is constructed to be most sensitive to early-time pressure data, which contains most of the information on well-field-scale heterogeneities.

7.1.2 *Application of the IFS Inverse Method*

The IFS inverse method has been applied to synthetic data to study its strengths and weaknesses and to real data from two field sites. Application to synthetic data has illustrated that the method does work successfully in that it provides a hydrologic property distribution which reproduces the observed well-test response. However, caution must be used so as not to infer more information about the distribution than the well-test data contains. In particular, regions away from the flow path between the pumping and observation wells are not well-constrained. Use of an ensemble of inversions provides a convenient way to assess the reliability of various features of the returned property distributions. Application to field data has motivated development of many of the features of the IFS inverse method that are necessary to make it work in a practical way (e.g., the diffusivity optimization necessary for time-dependent flow rates), and pointed out a number of difficulties associated with the use of real data that must be accounted for. Most importantly, comparison with other well-test analysis methods (Kesterson) and other types of geophysical data (Gypsy) has demonstrated that the IFS inverse method is a useful tool for characterizing heterogeneous geologic media.

Two other applications of the IFS inverse method to field data have been carried out to date. The first [Hestir *et al.*, 1991] used an early version of the method to examine well-test data from a fractured tuff at the Nevada Test Site. Although only three observation wells were available,

making it relatively easy to obtain a good match to the pressure transients, the development of a plausible-looking fracture pattern as the inversion proceeded encouraged further development of the IFS inverse method. The second application [Doughty *et al.*, 1994] used an interference test conducted in a shear zone of a fractured granitic rock at the Stripa mine in Sweden to develop several models of transmissivity variations within the fracture zone. The models were then checked by using them to predict the inflow to a drift after the conclusion of the interference test. This verification exercise not only demonstrated the ability of the IFS inverse method to successfully identify heterogeneities, but provided insight into the nature of the transmissivity distribution within the fracture zone.

7.2 CONCLUSIONS

7.2.1 The Value of Hydrologic Inversion

Geologic media are highly heterogeneous on many overlapping scales, making it very difficult to take laboratory measurements of flow or transport properties on core or outcrop samples (typically on a scale of a few centimeters), and upscale them so that they can be applied at a field-wide scale (typically tens to thousands of meters, depending on the application). A variety of idealized conceptual models are available for upscaling, ranging from the assumption of stationarity and ergodicity at some scale, above which a stochastic treatment may be used, to the assumption of a fractal geometry in which variability repeats itself at all scales. Rather than relying on such idealizations, an alternative approach is to use hydrologic inversion to attempt to determine effective properties at the scale of interest in the first place, and eliminate any need to scale up. This approach requires that the scale at which parameter identification is done be chosen specifically for the application at hand. For example, for the clean-up of a contaminant plume in a groundwater aquifer, inverting interference-test or tracer-test data using wells in the vicinity of the plume would make sense. For understanding regional variability of a water-supply aquifer, an inversion of regional head data would be appropriate.

Inverting pressure or flow data to obtain permeability is in fact just what permeameters do, albeit at a much smaller scale, where flow through a homogeneous medium in a known geometry permits the direct inversion of the flow equation to determine permeability. At the larger scales of interest, heterogeneities preclude knowledge of exact flow geometry, so the flow equation must be inverted indirectly. The indirect inversion procedure described in the present work consists of numerically simulating an interference test using a mathematical model of the subsurface,

assuming some distribution of hydrological properties (the parameters of the model), then comparing the calculated and observed pressure responses, and based on this comparison, modifying the parameters of the model and repeating the simulation. This procedure continues until a satisfactory match between the observed and calculated data is obtained, and the corresponding model parameters are accepted as providing a possible representation of the hydrological property distribution. An analogous procedure can be applied invert to tracer-test data or regional hydraulic head data.

A common complaint about hydrologic or tracer inversion methods, that they do not provide a unique representation of the subsurface property distribution, is mitigated if the test used for parameter identification is similar enough to the ultimate application for which the characterization is being done. In this case, while it is true that the model may not contain the 'true' permeability distribution, it contains one that will produce the correct response for the problem at hand, which is just what is needed. It is therefore necessary that the test used for parameter identification be as relevant to the ultimate application as possible. A straightforward way to achieve this condition is to use the ultimate application itself as the 'test' to be inverted. Thus parameter estimation and ultimate application proceed concurrently in a prediction/correction mode, each becoming more effective as they progress and exchange information.

Another way to alleviate non-uniqueness is to constrain the inversion process with geological or other external information. Not surprisingly, one useful piece of information in this regard is how heterogeneity varies with scale, which is embodied in the self-similar character of the IFS attractor (in rotation-matrix form, the parameter C controls the scaling behavior of an attractor). Thus, constructing a heterogeneous permeability distribution with an IFS means that we end up invoking an idealized scaling model after all. However, this approach differs from classical upscaling in one fundamental way: rather than studying behavior at a small scale and upscaling to the application scale, we study behavior at the application scale, and invoke a model for downscaling only as necessary to reproduce that large-scale behavior.

7.2.2 Advantages of a Fractal Approach to Hydrologic Inversion

Fewer parameters are needed to describe a self-similar geometry than a general heterogeneous geometry, improving the efficiency and robustness of the inversion. Equally important is that the final parameter set produces a hydrologic property distribution with a hierarchical structure, which is consistent with the wide range of scales of heterogeneities seen in natural geological media. Constraining the parameters of the IFS during the inversion constrains the resulting

attractor shapes, which may make it possible to limit the search for hydrologic property distributions to those consistent with conceptual geological models or with other additional information.

The IFS inversion method does not always return a uniquely determined hydrologic property distribution. This is not a failure of the method itself, but rather reflects on the limitations of the information contained in the well-test response. In fact, one of the significant uses of hydrologic inversion (not limited to the IFS method) is to assess the information content of the well-test data. By making multiple inversions of a given well test, and comparing the returned hydrologic property distributions, one can discern from the common features those regions which have the greatest influence on the well test and their hydrologic properties, and from the contradictory features those regions to which the well-test response is not sensitive, a process which can help identify where to drill additional wells for improved testing.

7.2.3 Limitations of a Fractal Approach to Hydrologic Inversion

Despite the advantages described above, the full mathematical and philosophical beauty of fractals cannot be fully exploited for hydrologic inversion. One problem is that the use of finite-resolution and finite-extent numerical models limits the representation of fractals to only a few scales. This is more of a problem in practice rather than in principle, however, as arbitrarily high-resolution and spatially-extensive grids can be designed. A more severe problem arises from the diffusive nature of the flow equation coupled with the scarcity of observation locations during a well test, which severely limits the information content of the observed well-test data. It appears unrealistic to hope to glean from such information more than a glimpse into the true underlying geometry of a site. However, the ultimate goal of these studies is not complete knowledge about the multiplicity of scales of heterogeneity present at a site, but a mathematical model that may be used to predict flow and transport at the well-field scale. By construction, the models developed inverting well-test data do just that.

7.3 FUTURE WORK

7.3.1 Further Development of the IFS Inverse Method

Application of a two-dimensional version of the IFS inversion method to synthetic and field data has shown its promise, but further work to improve code efficiency and robustness would greatly enhance its value. A more efficient code would allow problems of the present level of complexity (single-phase flow, two-dimensional attractors) to be solved much more rapidly, making the method more widely useful outside a purely research environment. Improved efficiency

would also allow much more computationally intensive problems (e.g., multi-phase multi-component flow, fully three-dimensional models) to be addressed. Code efficiency could be improved in three ways: 1) doing the forward calculation more efficiently; 2) searching through unknown parameter space more effectively; and 3) decreasing the size of the parameter space to be searched. Each of these areas is briefly discussed below.

Because the IFS inverse method typically does thousands of forward calculations during the course of an inversion, the numerical simulation of the forward problem must be as efficient as possible. One exciting possibility for improving the efficiency of the numerical solution of the flow equation is to take the Laplace transform of the governing equations, and thus eliminate time from the numerical model [Moridis and Reddell, 1991]. Spatial discretization of heterogeneities remains unchanged, but the solution is reached via a single step, rather than marching through a series of time steps. Therefore, the more time steps a conventional solution requires, the greater the speedup achieved by using the Laplace transform; the break-even point is for a calculation requiring 10 time steps. Because the flow problem is solved in the Laplace domain rather than in the time domain, the observed pressure responses must also be Laplace transformed, which requires that they be approximated by analytical forms. Rather than being an impediment to a successful inversion, this step is readily achieved with commercially available graphical software, and provides an opportunity for an experienced user to choose which parts of the response curves to emphasize, or to clean up noisy data.

Another possibility for improving efficiency of the forward calculation is to replace the flow calculations with a trained artificial neural network. Such an approach has been used to determine optimal placement of remediation wells in groundwater clean-up operations [Rogers and Dowla, 1993]. The problem of characterizing heterogeneous media is more demanding than that of optimally locating remediation wells, because there are more unknown parameters to deal with, but the potential savings in computational time could be significant, making this a worthwhile approach to consider.

Another means of improving the overall efficiency of the inverse method is to improve the optimization algorithm. Optimization algorithms such as simplex annealing, which combine intelligent choices for new parameter values with the ability to escape local minima seem very promising, and should be investigated further. Typical hydrologic inversions using IFS's require many unknown parameters, making direct visualization of a two-dimensional energy surface as was done in Section 3.3.2 impossible. However, an n -dimensional polynomial objective function

could be constructed in order to assess the strengths and weaknesses of various optimization algorithms under high-dimensional conditions.

One of the frustrating aspects of using an automated inversion method is that while monitoring the progress of the inversion, it is common to look at the trial permeability distributions being considered and think that better choices could be made by hand. User intuition is a valuable component of successful hydrologic analysis, and not one readily transportable to computers. A possible solution to this problem would be to make the inversion a more interactive process, which would allow convenient user intervention to implement intuitive choices.

Both the efficiency and robustness of an inverse method can be improved by decreasing the size of the unknown parameter space. This is already achieved in the IFS inverse method to a great extent by making use of the self-similarity of fractal attractors to represent hydrologic property distributions. Constraining the form of the attractors considered during the inversion to conform to geologic information further improves the situation, and should be developed more extensively. In a related area, alternate methods for mapping the attractor to the lattice could be used to better represent geological structure or features observed in geophysical imaging. For example, the distributed map could be modified to create elliptical rather than circular regions of altered permeability, with the long axes aligned with paleoflow direction in a fluvial system, or the dominant fracture orientation in a fractured system. This approach would be especially valuable used in conjunction with well tests involving only a few observation wells, in which heterogeneity resolution is intrinsically limited. Attractors composed of relatively few points (created by fewer iterations of Equation (2.2)) could be mapped to broad, geologically-based shapes, yielding a low-resolution picture of heterogeneity consistent with the information content of the well test.

Improving the robustness of the inverse method (that is, making the returned property distribution more reliable) would be very useful, as it would allow less experienced users to run the code effectively. One method of enhancing robustness would be to couple the hydrologic inversion process more closely to analysis of other kinds of data. As illustrated in Figure 4.5, co-inverting multiple well tests can make the analysis sensitive to greater portions of the flow region. This concept can be extended by co-inverting different kinds of data, for example adding seismic or electromagnetic measurements to the objective function, and adding the corresponding simulations to the forward calculation. A more economical means of improving uniqueness is to condition the inversion of a hydrologic interference test by adding penalty terms to the objective

function to reflect mismatches to known hydrologic property data. Another possibility would be to do a geostatistical analysis of each trial hydrologic property distribution and reject those which contradict observed geostatistical parameters.

7.3.2 *Further Applications of the IFS Inversion Method*

One of the strengths of the hydrologic inversion method is that it uses observations of pressures and fluid flow to develop models that will be used to predict pressure and fluid flow – no subsidiary relation to the process of interest is required as is the case when geological mapping or geophysical imaging is used to build a flow model. Current studies have focused on well-test analysis, but regional flow problems should be amenable to IFS inversion as well. Predicting fluid flow is the ultimate goal for applications such as estimating water supply or optimizing oil recovery. For studies involving remediation of contaminated aquifers or storage of nuclear waste, understanding solute transport via fluid flow is the ultimate goal, rather than studying the flow itself, making the inversion of solute transport data desirable. Such inversion can be incorporated in the IFS framework in a straightforward manner, and may yield noteworthy results because the equation governing solute transport contains an advective as well diffusive term, which may strongly impact the inversion process.

The ability to treat problems in which both the flow domain and the attractor are three-dimensional will require only minor modifications to the IFS inverse method, as described in Section 2.1. However, treating fully three-dimensional problems will be computationally intensive not only because of the larger computational grids required, but because of the increase in the number of unknown parameters. Additionally, the use of three-dimensional attractors may cause some practical problems as it becomes more difficult to visualize the attractor during the course of the inversion.

So far, the IFS inverse method has only been applied to isothermal, single-phase liquid flow problems. By using a numerical simulator such as TOUGH2 [Pruess, 1987, 1991] for the forward calculation, non-isothermal, multi-phase, multi-component flow problems could also be tackled. It would be straightforward to replace TRINET with TOUGH2 in the IFS inverse method. However, TOUGH2 has already been embedded in an inverse method, ITOUGH2 [Finstler, 1993], which incorporates powerful features for analyzing the results of an inversion, as well as a flexible user interface for constructing the objective function. It would therefore make more sense to add the IFS method of generating trial property distributions to ITOUGH2. This modification would greatly increase the range of applicability of the IFS inverse method,

allowing analysis of hydrologic data from a great range of environments, including the use of history data from producing geothermal and petroleum reservoirs.

It is common to do a hydrogeologic characterization of one location, then try to extrapolate the results to a neighboring region. This situation may arise in a contaminant cleanup operation, where a well test cannot be conducted using wells within a contaminant plume for fear of spreading the plume to previously clean locations, or in characterization of a potential waste storage site, where drilling additional wells could compromise the integrity of the site. No inverse method can make deterministic predictions about an area beyond the region to which well-test responses are sensitive. However, statistical predictions can be used for extrapolation. One common procedure is to make the statistical assumption of stationarity, that is, a pattern found at one location is repeated indefinitely in all directions away from that location, as suggested schematically in the left column of Figure 7.1. The fractal character of the IFS-generated property distributions provides a means for upscaling results without invoking the stationarity assumption. Instead, the assumption is made that the fractal property distribution found for the studied region is actually a just a part of a larger fractal. That is, the process of starting with a pattern at one scale, and then repeating it at smaller and smaller scales through the IFS construction of an attractor (as in Figures 2.2 and 2.3), can also be applied in reverse, creating larger and larger versions of the pattern, as suggested in the right column of Figure 7.1. Figure 7.1 shows that after only two iterations, the two upscaling assumptions produce markedly different property distributions. The fractal method of extrapolation presumes that the fractal geometry inherent in the IFS construction of an attractor continues to apply at larger scales than the well-field in which the original hydrologic characterization was done. In contrast, the stationarity assumption invokes the notion of an upper-limit scale, above which fractal geometry ceases to apply. Regional geological information can be used to help decide which is the more appropriate assumption for a given problem.

Figure 7.1. Extrapolation of a hydrologic characterization using either the assumption of stationarity for scales greater than that of the well field, or the assumption that fractal geometry applies at scales both larger and smaller than the scale of the well field.

REFERENCES

- Barker, J.A., A generalized radial flow model for hydraulic tests in fractured rock, *Water Resour. Res.*, 24(10), 1796-1804, 1988.
- Barker, J.A., The reciprocity principle and an analytical solution for Darcian flow in a network, *Water Resour. Res.*, 27(5), 743-746, 1991.
- Barnsley, M., *Fractals Everywhere*, pp. 1-117, 334-380, Academic Press, Boston, 1988.
- Butler, J.J. Jr. and Liu, W., Pumping tests in nonuniform aquifers – the radially asymmetric case, *Water Resour. Res.*, 29(2), 259-269, 1993.
- Carrera, J. and Neuman, S.P., Estimation of aquifer parameters under transient and steady state conditions: 1. Maximum likelihood method incorporating prior information, *Water Resour. Res.*, 22(2), 199-210, 1986a.
- Carrera, J. and Neuman, S.P., Estimation of aquifer parameters under transient and steady state conditions: 2. Uniqueness, stability, and solution algorithms, *Water Resour. Res.*, 22(2), 211-227, 1986b.
- Carrera, J. and Neuman, S.P., Estimation of aquifer parameters under transient and steady state conditions: 3. Application to synthetic and field data, *Water Resour. Res.*, 22(2), 228-242, 1986c.
- Chung, S.Y., Development of inverse fractal interpolation functions for modeling hydraulic conductivity distributions, Ph.D. Dissertation, 207 pp., Hydrology/Hydrogeology Program, University of Nevada, Reno, 1992.
- Cinco-Ley, H., Samaniego, V.F., and Dominguez, A.N., Transient pressure behavior for a well with a finite-conductivity vertical fracture, *Journal of the Society of Petroleum Engineers*, 253-264, (August) 1978.
- Doughty, C. and Thompson, A., LBL/industry heterogeneous reservoir performance definition project: Review and assessment of Gypsy pilot-site hydrologic data, *Rep. LBL-1987*, 16 pp., Lawrence Berkeley Lab., Berkeley, Calif., 1993.
- Datta-Gupta, A., Vasco, D.W., and Long, J.C.S., Detailed characterization of a fractured limestone formation using stochastic inverse approaches, *SPE/DOE-27744*, presented at the SPE/DOE Ninth Symposium on Improved Oil Recovery, Tulsa, Oklahoma, 17-20 April, 1994 (also available as *LBL-35888*, Lawrence Berkeley Lab., Berkeley, Calif., 1994).
- Doughty, C., Long, J.C.S., Hestir, K., and Benson, S.M., Hydrologic characterization of heterogeneous geologic media with an inverse method based on iterated function systems, *Water Resour. Res.*, 30(6), 1721-1745, 1994.
- Dowdle, Fairchild, and Ancell, Inc., Pressure transient test analysis of three IRD Gypsy subsurface pilot wells Dallas 1-7, 5-7, and 7-7, Report to BP Exploration, November, 1990.
- Doyle, J.D., Geological setting and initial 2D reservoir characterization of the Gypsy outcrop, *Rep. HO89.0192*, BP Exploration, July, 1989.
- Doyle, J.D., and Sweet, M.L., Geological characterization of the IRD Gypsy study sites, *Rep. HO920072*, BP Exploration, June, 1992.
- Finsterle, S., ITOUGH2 user's guide version 2.2, *Rep. LBL-34581*, 102 pp., Lawrence Berkeley Lab., Berkeley, Calif., 1993.
- Gringarten, A.C., Unsteady-state pressure distributions created by a well with a single horizontal fracture, partial penetration, or restricted entry, Ph.D. dissertation, Department of Petroleum Engineering, Stanford University, Stanford, Calif., 1971.
- Hantush, M.S. and Jacob, C.E., Non-steady radial flow in an infinite leaky aquifer, *Trans., Amer. Geophys. Union*, 36(1), 95-100, 1955.
- Hestir, K., Long, J.C.S., and Martel, S.J., The use of iterated function systems in fracture hydrology, Earth Sciences Division 1990 Annual Report, *Rep. LBL-29700*, pp. 36-40, Lawrence Berkeley Lab., Berkeley, Calif., 1991.
- Hestir, K., Long, J.C.S., Martel, S.J., D'Onfro, P., Queen, J.H., Rizer, W.D., and Vail, S., Inverse

- Hydrologic Modeling Using Stochastic Growth Algorithms, Lawrence Berkeley Lab. Report, Berkeley, Calif, 1995.
- Karasaki, K., A new advection-dispersion code for calculating transport in fracture networks, Earth Sciences Division 1986 Annual Report, *Rep. LBL-22090*, pp. 55-58, Lawrence Berkeley Lab., Berkeley, Calif., 1987.
- Kitanidis, P.K. and Vomvoris, E.G., A geostatistical approach to the inverse problem in groundwater modeling (steady state) and one-dimensional simulations, *Water Resour. Res.*, 19(3), 677-690, 1983.
- Koltermann, C.E. and Gorelick, S.M., Paleoclimatic signature in terrestrial flood deposits, *Science*, 256, 1775-1782, 1992.
- Long, J.C.S., Mauldon, A.D., Nelson, K., Martel, S., Fuller, P. and Karasaki, K., Prediction of flow and drawdown for the site characterization and validation site in the Stripa mine, *Rep. LBL-31761*, 105 pp. Lawrence Berkeley Lab., Berkeley, Calif., 1991.
- Long, J.C.S., Doughty, C., Hestir, K., and Martel, S., Modeling heterogeneous and fractured reservoirs with inverse methods based on iterated function systems, in *Reservoir Characterization III*, Bill Linville, Ed., pp. 471-503, PennWell Books, Tulsa, Oklahoma, 1993.
- Mauldon, A.D., Karasaki, K., Martel, S.J., Long, J.C.S., Landsfield, M., Mensch, A., and Vomvoris, S., An inverse technique for developing models for fluid flow in fractured systems using simulated annealing, *Water Resour. Res.*, 29(11), 3775-3789, 1993.
- Metropolis, N., Rosenbluth, A., Rosenbluth, M., Teller, A., and Teller, E., *J. Chem. Phys.*, 21, 1087-1092, 1953.
- Molz, F.J. and Boman, G.K., A fractal-based stochastic interpolation scheme in subsurface hydrology, *Water Resour. Res.*, 29(11), 3769-3774, 1993.
- Moridis, G.J., and Reddell, D.L., The laplace transform finite difference method for simulation of flow through porous media, *Water Resour. Res.*, 27(8), 1873-1884, 1991.
- Najita, J.S. and Karasaki, K., Inversion of hydrologic well tests using cluster variable aperture simulated annealing, report in preparation, Lawrence Berkeley Lab., Berkeley, Calif., 1995.
- Neuman, S.P., Universal scaling of hydraulic conductivities and dispersivities in geologic media, *Water Resour. Res.*, 26(8), 1749-1758, 1990.
- Neuman, S.P. and Witherspoon, P.A., Theory of flow in a confined two aquifer system, *Water Resour. Res.*, 5(4), 803-816, 1969.
- Oliver, D.S., The influence of nonuniform transmissivity and storativity on drawdown, *Water Resour. Res.*, 29(1), 169-178, 1993.
- Ouenes, A., Bhagavan, S., Bunge, P.H., and Travis, B.J., Application of simulated annealing and other global optimization methods to reservoir description: Myths and realities, *SPE-28415*, presented at the 1994 SPE Annual Technical Conference and Exhibition, New Orleans, La., Sept. 25-28, 1994.
- Papadopoulos, S.S. and Associates, Inc., Results of the single well and pulse tests IRD Gypsy subsurface site, Oklahoma, Report to BP Exploration, February, 1991.
- Press, W.H. and Teukolsky, S.A., Simulated annealing optimization over continuous spaces, *Computers in Physics*, 5(4), 426-429, 1991.
- Press, W.H., Flannery, B.P., Teukolsky, S.A., and Vetterling, W.T., *Numerical Recipes: The art of scientific computing*, Ch. 10, pp. 274-334, Cambridge University Press, New York, 1986.
- Pruess, K., TOUGH user's guide, *Rep. LBL-20700*, 78 pp., Lawrence Berkeley Lab., Berkeley, Calif, 1987.
- Pruess, K., TOUGH2 - A general-purpose numerical simulator for multiphase fluid and heat flow, *Rep. LBL-29400*, 102 pp., Lawrence Berkeley Lab., Berkeley, Calif, 1991.
- Rieu, M. and Sposito, G., Fractal fragmentation, soil porosity, and soil water properties: I. Theory, *Soil Sci. Soc. Am. J.*, 55, 1231-1238, 1991a.
- Rieu, M. and Sposito, G., Fractal fragmentation, soil porosity, and soil water properties: II.

- Applications, *Soil Sci. Soc. Am. J.*, 55, 1239-1244, 1991b.
- Rogers, L.L. and Dowla, F.U., Optimization of groundwater remediation using artificial neural networks with parallel solute transport modeling, *Water Resour. Res.*, 30(2), 457-481, 1994.
- Sahimi, M. and Yortsos, Y.C., Applications of fractal geometry to porous media: A review, *SPE-20476*, presented at the 1990 Annual Fall Meeting of the Soc. of Pet. Eng., New Orleans, La., Sept. 23-26, 1990.
- Theis, C.V., The relation between the lowering of the piezometric surface and the rate and duration of discharge of a well using ground-water storage, *Trans., Amer. Geophys. Union*, 16, 519-524, 1935.
- Turpening, W.R., Chon, Y.-T., Pepper, R.E.F., Szerbiak, R., Schultz, T., Thielmier, G., and Ballard, R., Detection of bed continuity using crosswell data: A Gypsy pilot site study, *SPE-24711*, presented at the 67th Annual Technical Conference and Exhibition of the Society of Petroleum Engineers held in Washington, DC, October 4-7, 1992.
- Tyler, S.W. and Wheatcraft, S.W., Fractal processes in soil water retention, *Water Resour. Res.*, 26(5), 1047-1054, 1990.
- Vail, S., An inverse approach to a probability model for fractured networks, M.Sc. Thesis, 84 pp., Dept. of Mathematics and Statistics, Utah State University, Logan, 1993.
- Vasco, D.W., Datta-Gupta, A., and Long, J.C.S., Resolution and uncertainty in hydrologic characterization, submitted to *Transport in Porous Media*, 1995.
- Vasco, D.W., Peterson, J.E. Jr., and Majer, E.L., Beyond ray tomography: ensemble inference and cluster analysis, *Geophysics*, in press, 1996.
- Webb, E.K., Simulating the spatial heterogeneity of sedimentological and hydrogeological characteristics for braided stream deposits, Ph.D. Dissertation, 241 pp., Dept. of Geology, University of Wisconsin, Madison, 1992.
- Wheatcraft, S.W. and Tyler, S.W., An explanation of scale-dependent dispersivity in heterogeneous aquifers using concepts of fractal geometry, *Water Resour. Res.*, 24(4), 566-578, 1988.
- Yates, C.C., Analysis of Pumping Test Data of a Leaky and Layered Aquifer with Partially Penetrating Wells, M.Sc. Thesis, 198 pp., Dept. of Material Sciences and Mineral Engineering, University of Calif., Berkeley, 1988.
- Yeh, W.W.-G., Review of parameter identification procedures in groundwater hydrology: The inverse problem, *Water Resour. Res.*, 22(2), 95-108, 1986.

APPENDIX A: THE NUMERICAL MODEL TRINET

A.1 BASIC FORMULATION

The finite element model TRINET [Karasaki, 1987] calculates fluid flow and solute transport on a lattice of one-dimensional finite elements (i.e., pipes) of porous medium. TRINET incorporates an adaptive gridding algorithm to minimize numerical dispersion for transport calculations, but the present application uses a fixed grid and calculates fluid flow only. The flow equation between the two nodes at either end of a one-dimensional finite element may be written as

$$S_s w \frac{\partial h}{\partial t} = T \frac{\partial^2 h}{\partial x^2}, \quad (\text{A.1})$$

where h is hydraulic head and S_s , w , and T are the specific storage, aperture, and transmissivity, respectively, of the element. The product of specific storage and aperture is storativity: $S_s w = S$. The height of each element b is taken to be one. The lattice of elements need not be uniformly spaced; it can be two- or three-dimensional, and rectangular, triangular, or a combination thereof. A square lattice such as is shown in Figure 3.3 provides a neutral template on which to build heterogeneities by attractor mapping, but geological information can be incorporated by using less regular lattices as well. For example, a non-orthogonal lattice, with elements aligned with regional fracture sets, would provide enhanced permeability in those directions. Although TRINET was originally developed to study fracture networks it can also model porous media, as described in Section A.2 below.

Constant head or constant flow boundary conditions can be specified for any node. In this way, wells can be modeled as point sources or sinks located at nodal points, the intersections between elements of the lattice. The version of TRINET embedded in the IFS inversion algorithm has been modified so that pumping-well flow rate can vary with time (in the standard version of TRINET it has to be constant). A time-varying flow rate at a pumping well is approximated as a series of constant flow-rate periods. Each period can be made as short as necessary to achieve a desired accuracy for a highly variable flow rate. However, for pulse well tests, in which the pumping schedule is a series of on-off pulses, the constant-flow periods need be no shorter than the pulse lengths. Each time a flow-rate change occurs, the next few time steps of the numerical simulation must be small, to properly account for flow transients. This means that simulations involving variable flow rates will be more computationally intensive than those with constant flow rates.

The ability to model time-varying flow rates makes co-inversion of multiple well tests straightforward. Each test using a different pumping well is considered to be part of one long test in which initially only the first well pumps, then after a time the first well is shut in and only the second well pumps, etc. A feature to allow re-initialization of heads when flow rate changes has been included, eliminating the need to simulate the period of time between tests when the system is re-equilibrating, allowing multiple tests which occurred at widely separated times to be co-inverted more efficiently.

A.2 TWO-DIMENSIONAL POROUS MEDIUM (CONFINED AQUIFER)

When applying the IFS inversion method to a porous medium, TRINET may be used with a two-dimensional rectangular lattice to represent an areal view of an aquifer. Figure A.1 shows a schematic view of a portion of such a lattice. The distance L gives the lattice spacing, and w and b are the aperture and height, respectively, of each element in the lattice. The region marked by the dashed line represents the unit cell of the lattice. The following algorithm provides a basis for choosing S_s , w , and T , the properties of the elements, so that the lattice as a whole acts like an aquifer with storativity $\tilde{S}$ and transmissivity $\tilde{T}$. Although TRINET always uses $b = 1$, keeping b as a variable helps make the following derivations clearer.

Figure A.1. Schematic diagram of a two-dimensional TRINET lattice.

From Equation (A.1), it is apparent that the hydraulic conductivity of an element is $K = T/w$, and therefore its conductance (hydraulic conductivity times cross-sectional area) may be written as Kwb . Figure A.1 shows that the conductance through a unit cell of the lattice is exactly this value, whereas the conductance through an equal volume of aquifer would be $\tilde{K}Lb$,

where $\tilde{K}$ is the equivalent aquifer hydraulic conductivity. Equating these expressions for conductance gives

$$\tilde{K} = K \left[\frac{w}{L} \right]. \quad (\text{A.2})$$

Writing this expression in terms of the input variable of TRINET $T = Kw$ and the desired output variable $\tilde{T} = \tilde{K}b$, and recalling that $b = 1$, gives the desired relationship for transmissivity for a lattice with spacing L :

$$\tilde{T} = \frac{T}{L}. \quad (\text{A.3})$$

The storage of a unit cell of the lattice is given by the element specific storage times the volume of the elements within the unit cell. Since half of four elements (each with length L and cross-sectional area wb) lie within the unit cell, storage capacity is given by $S_s 2wbL$. The storage of an equal volume of aquifer would be $\tilde{S}_s bL^2$. Equating these expression for storage gives

$$\tilde{S}_s = S_s \left[\frac{2w}{L} \right]. \quad (\text{A.4})$$

Writing this expression in terms of the desired output variable $\tilde{S} = \tilde{S}_s b$, and recalling that $b = 1$, gives the desired relationship for storativity for a lattice with spacing L :

$$\tilde{S} = S_s \left[\frac{2w}{L} \right]. \quad (\text{A.5})$$

For a lattice with variable spacing to behave as a uniform porous medium, element properties must vary with lattice spacing. A convenient variable lattice is a nested lattice in which a central fine region with spacing L is surrounded by a region with spacing aL , which in turn is surrounded by a region with spacing a^2L , and so on, so that the j th nested region has lattice spacing a^jL . In Figure A.1, $a = 2$ and portions of the $j = 0$ and $j = 1$ regions are shown. One consistent prescription for lattice element properties is to require that as lattice spacing increases from L to a^jL , the element properties are modified as follows:

$$S_s \rightarrow a^j S_s, \quad T \rightarrow a^j T, \quad w \rightarrow w. \quad (\text{A.6})$$

These modifications can be easily derived by examining Figure A.1 and equating conductance and storage for regions of the lattice with different values of j . Equations (A.3) and (A.5)

relating effective porous medium properties to lattice properties may be generalized for a nested lattice as follows:

$$\tilde{T} = \frac{T}{a^j L} \quad \tilde{S} = S_s \frac{2w}{a^j L} . \quad (\text{A.6.5})$$

The ability of TRINET to properly model flow through a porous medium has been verified by comparing its results to the Theis solution for transient radial flow in a confined homogeneous isotropic aquifer, in which a fully-penetrating well is pumped at a constant flow rate [Theis, 1935]. The lattice used for the calculation, shown in Figure A.2, was developed to model an aquifer with a well-field shown by the solid circles, with the pumping well at the center ($x = 0$, $y = 0$). The spacing in the central region of the lattice is $L = 3$ m, and the aperture throughout the lattice is $w = 1$ m. The nested lattice design is practical for modeling flow in porous media, where fine resolution is needed to represent flow near wells adequately, but the lattice must extend far beyond the well field to realistically implement pressure boundary conditions. Fine resolution is undesirable beyond the well field, because it greatly increases the size of the calculation without improving the ability of the model to predict flow or pressure at the well field.

Figure A.3a compares the Theis solution to the dimensionless drawdown calculated by TRINET using the material properties and boundary conditions shown in Table A.1. Overall, the match is excellent. The open circles in Figure A.2 show the locations where the drawdowns are compared. An equally good match is obtained if the drawdowns are compared along a line parallel to the x - or y - axis. The calculation was also done with a finer nested lattice, in which $L = 3$ m throughout the region defined by $-120 < x < +120$ and $-120 < y < +120$ m, beyond which lattice spacing was successively doubled. A comparison of the calculated drawdowns to the Theis solution is shown in Figure A.3b. Although the match is even better than in Figure A.3a, the fine lattice contains about 9,000 nodes and 17,000 elements as compared to 800 nodes and 1,500 elements for the lattice shown in Figure A.2. Computer time roughly increases by a factor $2m$ when the number of nodes and elements increases by a factor m , making the fine lattice highly impractical for use in an inversion. The nested lattice shown in Figure A.2 provides a good compromise between accuracy and efficiency to model flow in porous media within an inverse method.

Figure A.2. TRINET lattice used for verification calculations.

Figure A.3. TRINET comparison with *Theis* [1935] solution: a) using the lattice shown in Figure A.2; b) using a finer lattice.

Table A.1. Parameters for Theis solution verification.

TRINET Input Parameters	Equivalent Porous Medium Properties
Material Properties and System Dimensions	
$T = 3 \times 10^{-3} \text{ m}^2/\text{s}^\dagger$	$\tilde{T} = \frac{T}{L} = 1 \times 10^{-3} \text{ m}^2/\text{s}$
$S_s = 5.6 \times 10^{-5} \text{ m}^{-1}^\dagger$	$\tilde{S}_s = S_s \frac{2w}{L} = 3.73 \times 10^{-5}$
$w = 1 \text{ m}$	
$b = 1 \text{ m}$	$b = 1 \text{ m}$
Initial and Boundary Conditions	
$h = 0$ for all x and y at $t = 0$	$h = 0$ for all r at $t = 0$
$h = 0$ at $x = y = \pm 600 \text{ m}^\ddagger$	$h = 0$ as $r \rightarrow \infty$
$Q = 0.333 \times 10^{-3} \text{ m}^3/\text{s}$ at $x = y = 0$	$Q = 0.333 \times 10^{-3} \text{ m}^3/\text{s}$ at $r = 0$

† Used in the finest region of the lattice, where $L = 3 \text{ m}$; where lattice spacing is $a^j L$, $T \rightarrow a^j T$ and $S_s \rightarrow a^j S_s$.

‡ Calculation time is short enough so that a finite lattice acts like an infinite medium.

A.3 QUASI THREE-DIMENSIONAL POROUS MEDIUM (LEAKY AQUIFER)

The two-dimensional aquifer model described in the previous section has completely impermeable confining layers above and below it. It is straightforward to extend the model to include small vertical flows into the aquifer through a leaky confining layer. Figure A.4 shows a schematic view of the quasi three-dimensional lattice that is used to accomplish this.

Figure A.4. Schematic diagram of a quasi three-dimensional TRINET lattice.

One new element and one new constant-head node are added for each non-boundary node in the original two-dimensional lattice. Each new element has specific storage S_s' , aperture w' , transmissivity T' , and length L' . Due to the requirement that TRINET elements have height $b = 1$, the cross-sectional area of the new elements is $wb = w$, whereas Figure A.4 indicates that it should actually be w^2 . This limitation is circumvented by using $w = b = 1$ throughout the lattice.

In order for the confining layer as a whole to have vertical hydraulic conductivity $\tilde{K}'$ and specific storage $\tilde{S}_s'$, vertical conductance and storage for a unit cell of the TRINET lattice are equated to those of a unit cell of the porous medium, as before. For lattice spacing L ,

$$K'wb = \tilde{K}'L^2 \rightarrow \tilde{K}' = \frac{T'}{L^2} \quad (\text{A.7})$$

$$S_s'bwL' = \tilde{S}_s'L^2L' \rightarrow \tilde{S}_s' = S_s' \left[\frac{w}{L^2} \right] \quad (\text{A.8})$$

where $b = 1$ and $T' = K'w$ have been used.

To account for the variable lattice density, when the lattice spacing increases from L to a^jL , the TRINET properties are modified as follows:

$$T' \rightarrow a^{2j}T', \quad S_s' \rightarrow a^{2j}S_s', \quad w' \rightarrow w'. \quad (\text{A.9})$$

At the boundaries between regions of the lattice with different densities, intermediate values of T' and S_s' are used, with a^{2j} in Equation (A.9) replaced by $0.375a^{2j}$ along the edges of the regions, and $0.5625a^{2j}$ at the corners. These coefficients are chosen to make the conductance and storage as uniform as possible across the density-boundaries in the lattice. For the lattice shown in Figure A.2 this correction is not exact, because the different density regions are of very different extents (e.g., the $L = 6$ m region of the lattice is only one element wide, while the $L = 12$ m region is eight elements wide). For a lattice with continuously increasing density (each region of the lattice is only one element wide), the appropriate correction factors would be $0.333a^{2j}$ for edges and $0.2857a^{2j}$ for corners. Equations (A.7) and (A.8) can be generalized for a nested lattice as follows:

$$\tilde{K}' = \frac{T'}{(a^jL)^2} \quad \tilde{S}_s' = S_s' \left[\frac{w}{(a^jL)^2} \right] \quad (\text{A.9.5})$$

Figure A.5a compares the results of TRINET using the quasi three-dimensional nested lattice described above to an analytical solution for transient radial flow in a homogeneous isotropic

aquifer with a slightly leaky confining layer, in which a fully-penetrating well is pumped at a constant flow rate [Hantush and Jacob, 1955]. In the confining layer, flow is taken to be purely vertical, storage is assumed to be negligible, and head is held fixed, making the leakage into the aquifer act like a source term proportional to aquifer drawdown. Tables A.1 and A.2 summarize the material properties and boundary conditions used. The parameter B , which is used to scale radial distance from the pumping well, is given by $B = (\bar{K}bb'/\bar{K}')^{1/2} = 170$ m. The TRINET drawdowns for the locations marked by the open circles in Figure A.2 reproduce the analytical solution quite well, especially for the values of $r/B \leq 1.0$. Use of the alternate edge and corner correction factors improves the match for large values of r/B at the expense of the smaller ones, which is undesirable for the intended purpose of this lattice to model the drawdown at the wells shown as solid circles in Figure A.2. The calculation was repeated using the finer nested lattice described above, and Figure A.5b shows that a better match to the analytical solution can be obtained. As in the case of the two-dimensional lattice, the increased computation time for the fine lattice makes its use impractical in an inverse method, and the accuracy of the lattice shown in Figure A.2 provides an adequate representation of a slightly leaky aquifer.

Table A.2. Parameters for Hantush and Jacob [1955] solution verification, in addition to those given in Table A.1.

TRINET Input Parameters	Equivalent Porous Medium Properties
Confining Layer Properties and Dimensions	
$T' = 1.9 \times 10^{-6} \text{ m}^2/\text{s}^\dagger$	$\bar{K}' = \frac{T'}{L^2} = 2.11 \times 10^{-7} \text{ m/s}$
$S_s' = 5.6 \times 10^{-13} \text{ m}^{-1} \dagger \ddagger$	$\tilde{S}_s' = S_s' \frac{w}{L^2} = 6.22 \times 10^{-14} \text{ m}^{-1} \ddagger$
$b' = 6.1 \text{ m}$	$b' = 6.1 \text{ m}$
Boundary Condition in Confining Layer	
$h = 0$ for all x and y at $z = b'$	$h = 0$ for all r at $z = b'$

† Used in the finest region of the lattice, where $L = 3$ m; where lattice spacing is $a^j L$, $T' \rightarrow a^{2j} T'$ and $S_s' \rightarrow a^{2j} S_s'$.

$\ddagger \tilde{S}_s'$ is assumed to be zero in the analytical solution.

Figure A.5. TRINET comparison with *Hantush and Jacob* [1955] solution: a) using the lattice spacing shown in Figure A.2; b) using a finer lattice.

A.4 USE OF TRINET FOR HIGHLY HETEROGENEOUS MEDIA

In a highly heterogeneous medium, it is likely that some observation wells will respond to a pumped well much sooner than others, due to low-permeability regions separating some observation wells from the pumping well. A TRINET calculation requires a small enough initial time step to resolve the early-time behavior at the quickest responding observation well, at which time the slower responding observation wells may show almost no response. Under these conditions, the TRINET solution for the slow-responding observation wells tends to oscillate slightly, and may predict small negative drawdowns (pressure increases) when there should in fact be no or a very small positive drawdown. If TRINET is being used to simply perform a forward calculation, this oscillation causes no trouble, as its magnitude is so small as to be nearly invisible on a plot of drawdown versus time.

However, when TRINET is used in the IFS inverse method, the log of drawdown ($\ln h$) is generally used in formulating the objective function, as described in Chapter 3, Section 3.2. Therefore something must be done to allow for the possibility that the calculated drawdown may have a small negative value, and thus no logarithm. One approach (used for the present calculations) is to take the absolute value of calculated drawdown before taking the logarithm ($\ln |h|$). The philosophy behind this choice comes from examining plots of drawdown versus time for slow-responding wells, and noting that while the sign of the earliest calculated drawdown is certainly wrong, its magnitude is probably about right. Another possibility that has also been used is to assign any negative drawdown an arbitrary small positive value. The difficulty of this method is knowing how small a value to use. A better approach would probably be to estimate the smallest observable drawdown for a particular problem, then assign any negative calculated drawdown a slightly smaller value than that.

The choice of method used to treat negative calculated drawdowns is not expected to have much impact on the success of an inversion unless early-time observed data that does not show much pressure response is included in the objective function. The reason for this follows from the construction and use of the objective function as described in Section 3.2. Without the inclusion of non-responding observed data, one of two things will happen: 1) if time-shifting is not allowed, the corrected negative drawdowns will not appear in the objective function because there is no observed data corresponding to the time of the negative drawdown, or 2) if time-shifting is allowed, the corrected negative drawdowns will be compared to drawdown data that does show a response, yielding a large contribution to the energy, and a rejection of the

diffusivity value corresponding to that time-shift. On the other hand, if non-responding observed data is included in the objective function, the choice of method for treating negative calculated drawdowns may completely control the inversion process. However, as discussed in Section 3.2, if it is desired to include non-responding observed data, the objective function should be formulated in terms of h rather than $\ln h$, eliminating the need to correct negative calculated drawdowns at all.