A CHARACTERIZATION AND EVALUATION OF COAL LIQUEFACTION PROCESS STREAMS

Quarterly Technical Progress Report

Reporting Period: 07/01/1997 through 09/30/1997

Authors: G. A. Robbins
S. D. Brandes
R. A. Winschel

Report Issue Date: 06/09/1998

DE-AC22-94PC93054 --13

CONSOL Inc.
Research & Development
4000 Brownsville Road"
Library, PA 15129

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ABSTRACT

This is the Technical Progress Report for the thirteenth quarter of activities under DOE Contract No. DE-AC22-94PC93054. It covers the period July 1 through September 30, 1997. Described in this report are the following activities:

- CONSOL characterized 38 process stream samples from HTI Run PB-04, in which Black Thunder Mine Coal, Hondo vacuum resid, automobile shredder residue (ASR), and virgin plastics were used as liquefaction feedstocks with dispersed catalyst.
- A paper on kinetic modeling of resid reactivity was presented at the DOE Coal Liquefaction and Solid Fuels Contractors Review Conference, September 3-4, 1997, in Pittsburgh, PA. The paper, "The Reactivity of Direct Coal Liquefaction Resids", is appended (Appendix 1).
- Three papers on characterization of samples from coal/resid/waste plastics co-liquefaction were presented or submitted for presentation at conferences. Because of their similarity, only one of the papers is appended to this report. The paper, "Characterization of Process Samples From Co-Liquefaction of Coal and Waste Polymers", (Appendix 2) was presented at the DOE Coal Liquefaction and Solid Fuels Contractors Review Conference, September 3-4, 1997, in Pittsburgh, PA.
- The paper, "Characterization of Process Stream Samples From Bench-Scale Co-Liquefaction Runs That Utilized Waste Polymers as Feedstocks" was presented at the 214th National Meeting of the American Chemical Society, September 7-11, 1997, in Las Vegas, NV.
- The paper, "Characterization of Process Oils from Coal/Waste Co-Liquefaction" was submitted for presentation at the 14th Japan/U.S. Joint Technical Meeting on Coal Liquefaction and Materials for Coal Liquefaction on October 28, 1997, in Tokyo, Japan.
- A joint Burns and Roe Services Corp. and CONSOL paper on crude oil assays of product oils from HTI Run PB-03 was presented at the DOE Coal Liquefaction and Solid Fuels Contractors Review Conference, September 3-4, 1997, in Pittsburgh, PA. The paper, "Characterization of Liquid Products from All-Slurry Mode Liquefaction", is appended (Appendix 3).

TABLE OF CONTENTS

	<u>Page</u>
EXECUTIVE SUMMARY	1
Characterization of Samples From HTI Run PB-04	1
Technical Transfer	3
INTRODUCTION	4
Contract Overview	4
Contract Activities This Period	4
Activities in Progress	5
RESULTS AND DISCUSSION	6
Characterization of Samples from HTI Run PB-04	6
Introduction	6
Description of Plant and Co-Liquefaction Conditions	6
Characterization Methods and Analytical Approach	8
Characteristics of Process Streams Samples	9
Effect of Replacing Coal by ASR	10
Effect of Replacing Coal by Hondo Resid	12
Effect of Replacing Coal by Virgin Plastics	13
Product Oil Analyses and Hydrotreater Performance	15
Fate of PS	16
Fate of HDPE and PP	17
CONCLUSIONS	19
REFERENCES	20
LIST OF ABBREVIATIONS AND ACRONYMS	21

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1 HTI Operating Conditions and Process Performance Summary for Run PB-04 (227-95)	22
2 HTI Analyses of Feedstocks for Run PB-04	23
3 Components Found in Process Stream Samples from Co-Liquefaction of Waste Polymers with Coal, HTI Run PB-04	24
4 Component Distribution of Whole Samples, HTI Run PB-04 (227-95)	25
5 Proton Distribution of Whole Samples, HTI Run PB-04 (227-95)	26
6 Proton Distribution of Distillate Samples and Resid Samples, HTI Run PB-04 (227-95)	27
7 Phenolic -OH Concentration in Samples, HTI Run PB-04 (227-95)	28
8 Microautoclave Solvent Quality Tests, HTI Run PB-04 (227-95)	29
9 Results of Hot Decalin Extractions of Samples, HTI Run PB-04 (227-95)	30
10 Aromatic and Paraffinic Hydrogen Content of Samples, HTI Run PB-04 (227-95)	31
11 GC-MS Chromatographic Data from SOH Oils, Run PB-04 (227-95)	32

LIST OF TABLES

<u>Table</u>		<u>Page</u>
12	PS Liquefaction Products Found in First-Stage Oils, Run PB-04	33
13	Overall Conversion of Feed and Polymer Feed Components, HTI Runs PB-04 and CMSL-11	33

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Simplified Schematic of HTI's Bench Unit as Configured for Run PB-04	34
2	GC-MS Total Ion Chromatograms of First-Stage SOH Oils, Run PB-04	35
3	Polystyrene Liquefaction Products Found in Net Product Oils (SOH1 and SOH2 Oils)	36
4	FTIR Spectra of Decalin Extracts from Feed Slurry and Filter Cake (PFS) Produced in Condition 5 of HTI Run PB-04	36

LIST OF APPENDICES

<u>Appendix</u>		<u>Page</u>
1	The Reactivity of Direct Coal Liquefaction Resids	A1-1
2	Characterization of Process Samples from Co-Liquefaction of Coal and Waste Polymers	A2-1
3	Characterization of Liquid Products from All-Slurry-Mode Direct Liquefaction	A3-1

Section 1

EXECUTIVE SUMMARY

CHARACTERIZATION OF SAMPLES FROM HTI RUN PB-04

CONSOL characterized 38 process stream samples from HTI Run PB-04, in which h Black Thunder Mine Coal, Hondo vacuum resid, automobile shredder residue (ASR), and virgin plastics were used as liquefaction feedstocks with dispersed catalyst. The major conclusions from CONSOL's analyses of samples from HTI Run PB-04 follow.

- Several components of the waste polymers in the ASR were identified and, in some cases, quantified in co-liquefaction process stream samples. Different characterization strategies are needed to accommodate different polymers. Based on combined results from several methods, the estimated overall composition of the ASR feed was 68% HDPE + PP, 12% PS, and 20% ash. The ASR feed had a lower concentration of polyolefins, and higher concentrations of polystyrene and ash than the municipal solid waste (MSW) plastics fed in other HTI runs. There is no indication that the ASR contains an unreactive PS component.
- Polystyrene (PS) and polypropylene (PP) appear to be reactive. High-density polyethylene (HDPE) is less reactive and requires a substantial recycle to convert it. Ultimately, nearly all of the HDPE is converted. These results with authentic waste polymers generally confirm relative polymer reactivities previously observed with virgin polymers.
- CONSOL ash-balanced conversions of the MAF fresh feed components indicate high conversions (~95-99%) of the total waste/polymer stream and of the decalin extractable polyolefins. The conversions of these components were about 5% higher than HTI's conversions of the total fresh feed.
- Marker compounds that appear to be primary PS products were observed in the light product. Little gas yield is required to balance the observed PS product distribution, suggesting that little gas production is associated with PS liquefaction.

- L-892 feed blends of Hondo resid and ASR from periods 9B and 12B of Condition 3 showed considerable variation in composition. Notably, the amount of plastics in the Period 9B blend is low, and the amount of insolubles in it is high. Perhaps the composition is related to process changes at that time; HTI considered Period 8B-9 as transitional.
- On replacing 25% of the feed coal by auto shredder residue, several process streams decreased in aromatic hydrogen content and phenolic -OH content, and increased in paraffinic hydrogen content. These changes were consistent with replacement of a portion of the feed coal by ASR that is primarily polyolefinic. Microautoclave donor solvent quality of several oils decreased, primarily due to increased paraffinic hydrogen content of the oils. As expected, the concentration of extractable polyolefin plastic in several streams increased with the use of ASR, relative to coal alone.
- Process stream characteristics that changed upon partial and complete replacement of coal by Hondo resid as a co-feed with ASR were generally as expected. These included decreases in aromatic hydrogen content and increases in paraffinic hydrogen content, an increase in distillate content, and a decrease in phenolic -OH concentration in some samples. Relative to the Black Thunder Mine coal, the Hondo resid is expected to be paraffinic and lower in phenolic -OH and oxygen content. The donor solvent quality improvement that occurred appears to result from improvement in liquefaction resid quality, although the reason for this is unclear.
- Process stream characteristics that changed upon replacement of a portion of the coal by virgin plastics (simulated wastes) as a co-feed with ASR were generally as expected. Most changes resulted from the increased concentration of HDPE in the feed. These included increased paraffinic hydrogen content, decreased aromatic hydrogen content, increased concentrations of decalin-extractable polyolefin plastic, and decreased donor solvent quality. Phenolic -OH concentrations of all streams tested decreased, because the virgin plastics do not contain or contribute phenolic -OH. An increase in aromatic hydrogen content of the soluble portion of the feed slurry with the addition of virgin plastic may be related to the increased PS concentration in the feed.
- Although HTI observed nearly no removal of N and S in the hydrotreater in the last two conditions of Run PB-04, some hydrogenation had occurred, as evidenced by CONSOL

and HTI data. Hydrogenation activity was good early in the run. Phenolics were completely removed by hydrotreating throughout the run.

- It is recommended that methods be developed for speciation of more polymers (e.g., polyurethane), if ASR and other complex mixtures of municipal or industrial waste polymers continue to be evaluated as possible co-liquefaction feedstocks.

TECHNICAL TRANSFER

- A paper on kinetic modeling of resid reactivity was presented at the DOE Coal Liquefaction and Solid Fuels Contractors Review Conference, September 3-4, 1997, in Pittsburgh, PA. The paper, "The Reactivity of Direct Coal Liquefaction Resids", is appended (Appendix 1).
- Three papers on characterization of samples from coal/resid/waste plastics co-liquefaction were presented or submitted for presentation at conferences. Because of their similarity, only one of the papers is appended to this report. The paper, "Characterization of Process Samples From Co-Liquefaction of Coal and Waste Polymers", (Appendix 2) was presented at the DOE Coal Liquefaction and Solid Fuels Contractors Review Conference, September 3-4, 1997, in Pittsburgh, PA.
- The paper, "Characterization of Process Stream Samples From Bench-Scale Co-Liquefaction Runs That Utilized Waste Polymers as Feedstocks", was presented at the 214th National Meeting of the American Chemical Society, September 7-11, 1997, in Las Vegas, NV.
- The paper, "Characterization of Process Oils from Coal/Waste Co-Liquefaction" was submitted for presentation at the 14th Japan/U.S. Joint Technical Meeting on Coal Liquefaction and Materials for Coal Liquefaction on October 28, 1997, in Tokyo, Japan.
- A joint Burns and Roe Services Corp. and CONSOL paper on crude oil assays of product oils from HTI Run PB-03 was presented at the DOE Coal Liquefaction and Solid Fuels Contractors Review Conference, September 3-4, 1997, in Pittsburgh, PA. The paper, "Characterization of Liquid Products from All-Slurry Mode Liquefaction", is appended (Appendix 3).

Section 2

INTRODUCTION

This is the Technical Progress Report for the thirteenth quarter of activities under DOE Contract No. DE-AC22-94PC93054. It covers the period July 1 through September 30, 1997.

CONTRACT OVERVIEW

The objectives of this project are to support the DOE direct coal liquefaction process development program and to improve the useful application of analytical chemistry to direct coal liquefaction process development. This project builds on work performed in DOE Contract No. DE-AC22-89PC89883. Independent analyses by well-established methods are obtained on samples produced in direct coal liquefaction processes under evaluation by DOE. Additionally, new analytical instruments and techniques to examine coal-derived samples are being evaluated. The data obtained from this study are used to guide process development and to develop an improved data base on coal and coal liquids properties. A sample bank, established and maintained for use in this project, is available for use by other researchers. The reactivity of the non-distillable resid toward hydrocracking at liquefaction conditions (i.e., resid reactivity) is being examined. From the literature and experimental data, a kinetic model of resid conversion is being constructed. Such a model will provide insights to improve process performance and the economics of direct coal liquefaction.

CONTRACT ACTIVITIES THIS PERIOD

- CONSOL characterized 38 process stream samples from HTI Run PB-04, in which Black Thunder Mine Coal, Hondo vacuum resid, automobile shredder residue, and virgin plastics were used as liquefaction feedstocks with dispersed catalyst. Those results are described in the Results and Discussion section of this report.
- A paper on kinetic modeling of resid reactivity was presented at the DOE Coal Liquefaction and Solid Fuels Contractors Review Conference, September 3-4, 1997, in Pittsburgh, PA. The paper, "The Reactivity of Direct Coal Liquefaction Resids", is appended (Appendix 1).
- Three papers on characterization of samples from coal/resid/waste plastics co-liquefaction were presented or submitted for presentation at conferences. Because of their similarity, only one of the papers is appended to this report. The paper, "Characterization of Process

Samples From Co-Liquefaction of Coal and Waste Polym ers", (Appendix 2) was presented at the DOE Coal Liquefaction and Solid Fuels Contractors Review Conference , September 3-4, 1997, in Pittsburgh, PA.

- The paper, "Characterization of Process Stream Samples From Bench-Scale Co - Liquefaction Runs That Utilized Waste Polymers as Feedstocks" was presented at th e 214th National Meeting of the American Chemical Society, September 7-11, 1997, in Las Vegas, NV.
- The paper, "Characterization of Process Oils from Coal/Waste Co-Liquefaction" wa s submitted for presentation at the 14th Japan/U.S. Joint Technical Meeting on Coal Liquefaction and Materials for Coal Liquefaction on October 23, 1997, in Tokyo, Japan.
- A joint Burns and Roe Services Corp. and CONSOL paper on crude oil assays of product oils from HTI Run PB-03 was presented at the DOE Coal Liquefaction and Solid Fuel s Contractors Review Conference, September 3-4, 1997, in Pittsburgh, PA. The paper , "Characterization of Liquid Products from All-Slurry Mode Liquefaction", is appende d (Appendix 3).

ACTIVITIES IN PROGRESS

- Characterization work is under way on samples from HTI Runs PB-06 and PB-01.

Section 3

RESULTS AND DISCUSSION

CHARACTERIZATION OF SAMPLES FROM HTI RUN PB-04

INTRODUCTION

Since 1994, CONSOL has characterized feed, recycle, and product samples from DOE - sponsored co-liquefaction experiments with polymers and coal.¹⁻⁵ The objectives have been to understand the process chemistry and the fate of the polymer components during continuous operations. CONSOL used conventional liquefaction process stream characterization methods, supplemented by methods specifically developed for polymer components. In the earliest Hydrocarbon Technologies, Inc. (HTI) co-liquefaction runs, virgin polymers were used to simulate municipal waste polymers (Proof-of-Concept scale in Run POC-2, bench scale in Runs CMSL-8 and CMSL-9). More recently, HTI began using authentic municipal solid waste polymers (Run CMSL-11⁶) and auto shredder residue (Run PB-04⁷) as co-liquefaction feedstocks in various combinations with coal, petroleum resid, and virgin polymers. CONSOL characterized 38 process stream samples from HTI Run PB-04, in which Black Thunder Mine Coal, Hondo vacuum resid, automobile shredder residue, and virgin plastics were used as liquefaction feedstocks with dispersed catalyst. Run PB-04 represents the first use of the auto shredder residue, an authentic industrial waste, as a co-liquefaction feedstock at HTI.

DESCRIPTION OF PLANT AND CO-LIQUEFACTION CONDITIONS

The co-liquefaction Run PB-04 (227-95) was performed in HTI's bench unit 227, a diagram of which is shown in Figure 1. Run PB-04 covered five operating conditions in about 30 days of operation from June 3 through June 28, 1996 (May 31 start-up). Fresh feed materials (catalyst precursors, coal, waste feedstocks, petroleum resid, and/or virgin polymers) were mixed batch-wise with process recycle materials in a tank and transferred to a feed slurry tank that continuously fed the slurry to the liquefaction process. The feed slurry was fed to a preheater that also conditioned the dispersed catalyst. The slurry was subsequently fed to two successive stages of liquefaction. No supported catalysts were used in the liquefaction reactors; only disposable dispersed catalysts were used. A high-pressure (interstage) separator after the first reactor allows light products to be taken off, and the hydrogen concentration to be increased in the second reactor. The first-stage oil, called the first-stage separator overhead (SOH) oil, referred to here as the SOH1 oil, is sent with second-stage light oils and light distillate to an in-line fixed-bed hydrotreater. The in-line hydrotreater upgrades the product using the liquefaction reactor

system off gases. The second stage of liquefaction is followed by high- and low-pressure separators. The separator overheads are fed to the in-line product hydrotreater, and the separator bottoms to batch pressure filtration. The distillate (ca. IBP-371 °C) is sent to the product hydrotreater, and the resid is filtered to provide a liquid for recycle and solids to reject ash. The hydrotreated product oil is called the second-stage separator overhead (SOH) oil, referred to here as the SOH2 oil. The pressure filter liquid (PFL) is sent to a batch vacuum still. In Run PB-04, Periods 1-10, the pressure filter cake (PFC) was extracted with toluene to produce extracted oil and extracted cake. Extinction recycle was performed by recycling all of the 454 °C+ vacuum still bottoms (VSB) from the PFL and as much 454 °C+ vacuum still overheads (VSO) from the PFL as needed for total recycle. After ten periods, PFL and PFC were recycled directly.

Operating conditions and HTI process performance data for Run PB-04⁷ are shown in Table 1. HTI's analyses of the feedstocks are shown in Table 2. In this run, co-liquefaction operation was successfully demonstrated using the industrial waste feedstock automobile shredder residue (ASR). ASR is the non-metallic residue from automobiles after the recyclable metals are removed. Relative to the municipal solid waste (MSW) plastics fed in other runs, ASR generally was not as beneficial to liquefaction process performance. For example, when MSW was fed with coal in Condition 3B of Run CMSL-11, hydrogen consumption and gas yield were reduced and distillate yield was increased. In Run PB-04 (Table 1, cf. Condition 1 and Condition 4), only the hydrogen consumption was lower when ASR was used with coal. Operating difficulties were encountered throughout Run PB-04, including repeated feed pump problems attributed to ASR use. HTI observed that the resid conversion was lower when ASR was fed (relative to feeding coal only), and that ASR lowered the hydrogen consumption, distillate yield, and light gas yield. HTI speculated that polyurethane and (cross-linked) high-impact polystyrene in the ASR were less reactive than polymers previously processed (including the MSW). For this reason, it is important to determine the relative reactivity of the polymers that could be identified in the ASR.

HTI personnel prepared the ASR feed by hand-sorting it to remove metal pieces and other large inorganic components. They mixed 181 kg (400 lb) of the hand-sorted ASR with 136 kg (300 lb) of Hondo vacuum resid at 249 °C (480 °F) and withdrew the resid/plastics blend from the top of the mixing tank. This ASR feed blend, designated L-892, was reported to contain 40% ASR and was used in Conditions 2 and 3. For Conditions 4 and 5, the hand-sorted ASR was dissolved in recycle PFL. A 1.5:1 PFL:ASR blend could not be removed from the mix tank, but HTI was successful with a 2:1 PFL:ASR blend.

The plant was operated with recycle of 454 °C⁺ PFL material in an extinction recycle mode for the first ten periods. The objective was to completely convert the material in this range. This resulted in a very high MAF C₄-524 °C distillate yield (67.5%). After ten periods, ashy recycle was used. The dispersed catalyst used was a phosphorous-modified iron catalyst prepared by HTI's proprietary procedure. Molyvan A was the form of the molybdenum catalyst precursor used.

HTI found that early in the run the in-line hydrotreater catalyst (Criterion C-411 trilobe) had become deactivated from an unidentified source. The hydrotreated oil contained about 1000 mg/kg nitrogen and sulfur early in the run, and the concentration increased to about 2000 mg/kg by Condition 4. Under normal circumstances, the hydrotreated oil should contain about 50 mg/kg or less each of nitrogen and sulfur. An unhydrotreated oil would typically contain about 2000 mg/kg each of nitrogen and sulfur.

The major variable during Run PB-04 was the co-liquefaction feedstock blend. The feedstocks in each of the run conditions are given below. Reactor temperatures were constant throughout the run. The space velocity was higher in Condition 1 (718 kg MF fresh feed/h/m³ reactor volume) than in the remaining conditions (602-635 kg MF fresh feed/h/m³ reactor volume).

Condition 1: 100% Black Thunder Mine Coal

Condition 2: 70% Hondo Resid, 30% ASR

Condition 3: 50% Black Thunder Mine Coal, 30% Hondo Resid, 20% ASR

Condition 4: 75% Black Thunder Mine Coal, 25% ASR

Condition 5: 50% Black Thunder Mine Coal, 25% ASR, 25% virgin plastics (60:40 HDPE:PS)

CHARACTERIZATION METHODS AND ANALYTICAL APPROACH

Three analytical techniques supplemented the standard liquefaction work-up procedures (which included distillation to 454 °C, tetrahydrofuran (THF) extraction, ashing, and determinations of phenolic -OH concentration by FTIR spectroscopy and proton distribution by NMR spectroscopy). When polymers are present in co-liquefaction samples, hot decalin extraction, FTIR spectroscopy, and GC-MS characterization are the supplementary techniques. The decalin extraction and FTIR are used for resid- and solids-containing samples, and GC-MS is used for light net product oils. The hot decalin extraction method was described previously;⁵ it generates a solubles fraction, a "plastic" fraction, and an insolubles fraction from a liquefaction sample. The

"plastic" fraction consists of polyolefins (primarily high-density polyethylene (HDPE) and polypropylene (PP)) that are soluble in hot decalin, but insoluble in THF or room-temperature decalin. The polymers are subsequently characterized by FTIR spectroscopy. The GC-MS total ion chromatograms and individual mass spectra are usually examined for information on n-paraffins from polyethylene and other feedstocks, and for marker compounds from PS liquefaction. Various sample preparation techniques were used for qualitative FTIR examination of polymeric materials. Unsupported and supported thin films and thin slices were used for transmission IR measurements. Powder, or fine cuttings or filings were mixed with KBr (1-10% polymer) for diffuse reflectance measurements.

Most of the methods described above are aimed at determining the nature and fate of specific polymer components. Since HTI observed poorer performance with ASR than with MSW, it would be useful to identify any problematic components. However, there were differences in both feed compositions and process conditions (e.g. catalyst types and doses and reactor temperatures) between ASR run conditions and MSW run conditions, which could confound the results.

Samples and background information were supplied by Dr. V. Pradhan and Dr. J. Hu of HTI.^{7,8} Major process streams analyzed included the feed slurry, some of the individual fresh feeds or feed blends, the unhydrotreated first-stage separator overhead (SOH 1) oil, the separator bottoms (flashed liquefaction product), the filter liquid (recycle), filter cake (solids), and the hydrotreated net product (SOH2) oil.

CHARACTERISTICS OF PROCESS STREAMS SAMPLES

Table 3 is a summary of the overall characterization results of the various process streams analyzed, components found or expected, and special methods used. Ash, polyethylene, polypropylene, and polystyrene were components of the ASR feedstock that were directly or indirectly identified. PS was identified via marker PS-derived compounds found in product oils using GC-MS. Ash was determined by CONSOL indirectly on the ASR, using the ash content of the feed slurry. A polyolefin component was extracted from the ASR-containing feed slurry and feed blend samples and was identified as HDPE and PP using FTIR spectroscopy. Spectroscopic features suggest the presence of low-density polyethylene (LDPE), or some unidentified polyethylene, in some samples. Based on combined results from several of these methods, overall composition of the ASR feed was estimated, and is provided below.

Specific characterization data from the standard analytical tests and decalin extractions are provided in Tables 4-9. Table 10 provides proton distributions combined to give aromatic hydrogen content and paraffinic hydrogen content of the samples.

CONSOL received and analyzed two samples labeled as L-892, the Hondo resid/ASR feed blend that HTI indicated was 40% ASR. These were both from Condition 3; one was from period 9B, the other was from period 12B (the last sub-period of the work-up period). This stream represents the purest form in which the ASR was provided to CONSOL. These samples were characterized by decalin extraction, by FTIR (plastic extract, see next paragraph), and by ashing. Although the THF-solubles content of the two samples was similar (68% in period 9, and 75% in period 12), the concentrations of plastics (5% in period 9, and 18% in period 12), ash (8.3% in period 9, and 4.5% in period 12), and THF- and cold decalin-insolubles (including ash, 27% in period 9, and 7% in period 12) were substantially different for the two samples. Assuming that the samples are representative of the feed blends during those periods, these data indicate considerable variation in feed composition. Notably, the amount of plastics in the period 9 blend is low, and the amount of insolubles is high. HTI reported periods 8B-9 as transitional; perhaps the observed feed blend composition is related to changes occurring in the process at that time.

ASR ash was determined indirectly by calculation from the measured ash content of the feed slurry. A polyolefin component was extracted from the feed slurry and feed blend samples and was identified as HDPE and PP using FTIR spectroscopy. Spectroscopic features also suggest the presence of low-density polyethylene (LDPE), or some unidentified polyethylene, in the feed ASR. The presence of specific PS-derived components in the product oils indirectly indicated the presence of PS in the ASR feed. Based on combined results from several methods, the estimated overall composition of the ASR feed was 68% HDPE+PP, 12% PS, 20% ash (ash as reported by HTI⁷, Table 2). This differs substantially from the overall composition of the municipal solid waste (MSW) plastic feed that HTI used in several prior co-liquefaction runs. The composition of that MSW material was estimated by similar means to be approximately 96% HDPE+PP, 2% PS, and 1.6% ash.

EFFECT OF REPLACING COAL BY ASR

Comparisons of results that may be useful are those between Condition 1 and Condition 4 (showing the effect of replacing coal by ASR), between Conditions 4, 3, and 2 (showing the effect

of replacing coal+ASR by resid+ASR), and between Condition 4 and Condition 5 (simulating the effect of feeding non-ASR recycle plastics with ASR and coal).

By examination of differences in process stream characteristics from Condition 1 to Condition 4, it is possible to observe the effect of replacing 25% of the feed coal by ASR (100% coal in Condition 1, 75% coal/25% ASR in Condition 4). This change was confounded by a change from 454 °C⁺ extinction recycle to ashy recycle. There was a decrease in aromaticity and an increase in paraffinicity in the whole O-6 bottoms and PFL samples in Condition 4 (Table 10). The microautoclave coal conversions (O-6 bottoms whole and distillate, PFL whole and distillate) was lower in Condition 4 (Table 8), evidently as a result of increased paraffinicity. These differences are not surprising, since most the ASR feedstock consists of polyolefins that produce a lot of paraffinic products. Furthermore, the unconverted paraffin-like HDPE is usually found in the PFL recycle stream when HDPE is a liquefaction feedstock. In the product oils (SOH1 and SOH2), however, the aromaticity increased and the paraffinicity decreased (Table 10) in Condition 4. The reason for this change in the SOH1 is not clear. The hydrotreater performance was poorest in the last two conditions, so the increased SOH2 aromaticity is probably a result of declining hydrotreater performance.

In distillates, there was a small (ca. 0.2 meq/g) but consistent reduction in phenolic -OH in Condition 4 (Table 7). Because it is unlikely that the ASR feedstock produces phenolic products, this appears to result from displacement of phenolics in the product and intermediate (i.e., recycle) streams. The resids gave a mixed response (+0.3 meq/g in O-6 bottoms, no change in PFL), but the Condition 1 O-6 bottoms resid value of 0.66 meq/g seems suspiciously low. The 454 °C⁻ distillate content decreased in Condition 4. There was an IOM increase in Condition 4, small in the whole PFL, but larger in the other whole streams (PFS and O-6 bottoms).

Several sample streams tested showed increases in the decalin -extracted plastic fraction content in Condition 4 (Table 9), consistent with the addition of plastics to the feed. The whole feed slurry, the whole PFS, the PFL 454 °C⁺ resid, and the O-6 bottoms 454 °C⁺ resid showed increases in plastics concentrations from 1% or less in Condition 1 to 2.6-6.1% in Condition 4. The whole feed slurry and the PFL 454 °C⁺ resid also showed decreases in THF/decalin insolubles concentrations in Condition 4.

CONSOL data show that removal of phenolics from the product oil by the hydrotreater was complete throughout the run. Removal of nitrogen and sulfur was poor and declined throughout the run. CONSOL and HTI data indicate that the hydrotreater maintained some hydrogenation activity throughout the run, but it also seemed to worsen in the last two run conditions.

EFFECT OF REPLACING COAL BY HONDO RESID

By examination of stream characteristics from Condition 4 as compared to Condition 3 and from Condition 3 as compared to Condition 2, it is possible to observe the effect of replacing about one-third of the coal by Hondo resid (75% coal/25% ASR in Condition 4, 50% coal/30% resid/20% ASR in Condition 3), and then replacing the remainder of the coal by Hondo resid (50% coal/30% resid/20% ASR in Condition 3, 0% coal/70% resid/30% ASR). The ASR content of the feed was approximately constant, ranging from 20% to 30% during these conditions.

Most streams and samples (SOH1, SOH2, and 454 °C⁻ distillates and 454 °C⁺ resids from O-6 bottoms and PFL samples) decreased in aromatic hydrogen content and increased in paraffinic hydrogen content (Table 10) as coal was replaced by Hondo resid. This is the direction in properties that one would expect with partial and complete replacement of coal by Hondo resid in the liquefaction feed.

The 454 °C⁻ distillate content of the whole PFL and O-6 bottoms samples increased in Condition 3 as compared to Condition 4. In Condition 2 as compared to Condition 3, it increased only in the PFL (Table 4). The THF-soluble 454 °C⁺ resid content of these same samples correspondingly decreased with one or both condition changes. This appears to result from replacement of the feed coal by the Hondo resid, which may be more easily converted to distillate material. This is consistent with HTI's results (Table 1); they reported that C₄ - 454 °C distillate yields increased substantially (from 56.6% in Condition 4, as compared to 66.8% in Condition 3) and increased a small amount (to 69.1%) in Condition 2 relative to Condition 3.

On comparing Condition 4 with Condition 3 and Condition 3 with Condition 2, the donor solvent quality (as determined by microautoclave test) of the whole PFL and O-6 bottoms oil samples improved from about 50% conversion in Condition 4 to 70-75% conversion in Condition 2 (Table 8). The corresponding 454 °C⁻ distillates showed worsened solvent qualities from 77% in Condition 3 to 57-70% in Condition 2. It is unclear why the whole oils improved in solvent quality with an increased percentage of Hondo resid in the liquefaction plant feed. It implies that

the resid quality must have improved, since the distillate quantity increased and the corresponding distillate quality stayed the same or decreased.

On comparing results from Conditions 4 to 3 to 2, there was a general decrease in phenolic -OH concentration in the SOH1 oils, and in the PFL and O-6 bottoms 454 °C⁻ distillate and 454 °C⁺ resid THF-soluble fractions (Table 7). Since the Hondo resid is relatively low in phenolic -OH (0.29 meq/g), and in oxygen (HTI data shows 0.6 wt% in Table 2) , this was expected.

In Conditions 4, 3, and 2, the decalin-extracted plastic fraction (Table 9) found in the samples tested (whole feed slurry, whole PFS, and the 454 °C⁺ resids from PFL and O-6 bottoms) represented only 6% or less of those samples, with one exception. The O-6 bottoms 454 °C⁺ resid from Condition 2 contained a 20% plastic fraction. This sample from Condition 2 contained less of the THF/decalin insolubles fraction (9% compared to 19% in Conditions 3 and 4), and of the THF/decalin solubles fraction (71% compared to 76-79% in Conditions 3 and 4). The concentration of the THF/decalin solubles fraction of the PFS in Condition 3 (41%) was higher than in Conditions 2 and 4 (33-34%). There was a corresponding lower concentration of the Condition 3 PFS THF/decalin insolubles fraction. The concentration of the THF/decalin solubles fraction in the 454 °C⁺ resids from PFL was higher in Conditions 2 and 3 (95-98%) than in Condition 4 (91%). These changes observed do not appear to be directly attributable to specific feedstock differences, since operating difficulties and other process variables can easily induce some variation in process stream properties.

EFFECT OF REPLACING COAL BY VIRGIN PLASTICS

By examination of stream characteristics that changed from Condition 4 to Condition 5 , it is possible to observe the effect of replacing about one-third of the coal by virgin plastics, which was intended to simulate addition of a non-ASR MSW waste plastics stream to the coal and ASR feed (75% coal/25% ASR in Condition 4, 50% coal/25% ASR/15% HDPE/10% PS in Condition 5). The concentration of the very reactive PS (4.0%) in the simulated waste is higher than might normally be expected in a municipal waste stream. Furthermore, the use of only HDPE (the least reactive common polymer), and not PP (a more-reactive common polymer) as the remainder of the simulated waste may limit the overall reactivity of the feed. The simulated MSW waste feed thus has a very reactive component, and a relatively unreactive component. The total plastic concentration in the feed was 50%, which is rather high. Considering these factors, Condition 5 may not have tested a very realistic feed scenario.

From Condition 4 to Condition 5, fewer changes in aromatic hydrogen content were observed than changes in paraffinic hydrogen content (Table 10). Most process stream samples and their distillate and resid fractions showed increases of 4-15% paraffinic hydrogen from Condition 4 to Condition 5. The few process stream samples that decreased aromatic hydrogen content by 5-15% were the PFL 454 °C⁻ distillate and the PFL and O-6 bottoms 454 °C⁺ resid fractions. These changes were consistent with the increased concentration of HDPE in the feed. The soluble portion of the feed slurry stream showed the opposite trend by decreasing from 38% to 32 % paraffinic hydrogen content and increasing from 26% to 33% aromatic hydrogen content. It is possible that this results partly from the 10% PS in the feed in Condition 5. It is likely that the PS is entirely soluble in the feed slurry, and would contribute to an increase in the aromatic hydrogen (particularly uncondensed aromatic hydrogen) content. The proton distribution (Table 5) shows that more than half of the aromatic hydrogen content increase in the soluble portion of the feed slurry in Condition 5 was in the uncondensed aromatic category.

The whole O-6 bottoms sample contained about 11% less 454 °C⁻ distillate and 8% more THF-soluble 454 °C⁺ resid in Condition 5 than in Condition 4 (Table 4). The feed slurry contained about 11% less total THF-solubles (distillable and non-distillable) in Condition 5. The IOM content of several streams increased from Condition 4 to Condition 5 (HDPE reports as IOM, as do fresh and unconverted coal). The feed slurry increased from 28% to 33% IOM, the whole PFL increased from 6% to 35% IOM, and the whole PFS increased from 36% to 45% IOM. The large increase in the IOM concentration in the PFL evidently results from the addition of 15% HDPE in the feed in Condition 5, since previous work has shown that the PFL stream is the primary recycle stream for unconverted HDPE.^{3,4,9}

The donor solvent quality of the whole O-6 bottoms stream and of the 454 °C⁻ distillate portions of both the PFL and the O-6 bottoms streams decreased by 13-30% in Condition 5 (Table 8). The whole PFL already had poor solvent quality in Condition 4 (as did the whole O-6 bottoms), but the PFL did not decrease further in solvent quality. The extremely low value of about 22% conversion for the whole O-6 bottoms sample is reproducible. Rarely do the microautoclave tests give such low conversion values. Higher paraffinic hydrogen content of the distillates is expected to cause or contribute to lower solvent quality.

Because the virgin plastics fed in Condition 5 do not contain or contribute phenolic -OH, the phenolic -OH concentrations of the samples characterized from Condition 5 were consistently lower by 0.2-0.5 meq/g than their Condition 4 counterparts (Table 7).

The decalin-extracted plastic fraction made up a larger portion of the feed slurry and PFL streams in Condition 5 than in Condition 4 (Table 9). The plastic content of the PFL 454 °C⁺ resid increased from 6% plastic in Condition 4 to 51% plastic in Condition 5. The feed slurry increased in plastic concentration from 6% to 12%. These changes were consistent with the increased concentration of HDPE in the feed, since unconverted HDPE reports to the plastic fraction. There were decreases in the THF/decalin solubles content of the feed slurry (from 62% to 52 % solubles), the whole PFS (from 33% to 28% solubles), and of the PFL 454 °C⁺ resid (from 91% to 48% solubles). The THF/decalin solubles content of the O-6 bottoms 454 °C⁺ resid increased from 76% in Condition 4 to 85% in Condition 5. The THF/decalin insolubles content of the O-6 bottoms 454 °C⁺ resid decreased from 19% in Condition 4 to 12% in Condition 5.

PRODUCT OIL ANALYSES AND HYDROTREATER PERFORMANCE

Data from characterization of the SOH1 and SOH2 oils by gas chromatography-mass spectrometry (GC-MS) are given in Table 11. Integration data are provided there for several possible markers for coal and PS liquefaction products. Figure 2 shows the GC-MS total ion chromatograms of the SOH1 oils from Condition 1 (coal feed) and Condition 4 (coal/ASR feed); PS liquefaction product markers are identified. The PS liquefaction markers and integration data are discussed in more detail in the next section.

The dissimilarity between the Condition 1 SOH1 and SOH2 samples proton distributions, but similarity between the Condition 4 SOH1 and SOH2 samples proton distributions and between the Condition 5 SOH1 and SOH2 samples proton distributions reflect the decline in hydrotreater performance through the run (Table 5). Although HTI observed nearly no removal of N and S in the hydrotreater in Conditions 4 and 5, there was some hydrogenation activity evident in HTI's data, as well as in the data shown here (Tables 4 and 10). The CONSOL phenolic -OH data (Table 7) show that all of the SOH2 samples were devoid of phenolics, although the SOH1 oils were moderately high in phenolic content. Thus, all of the phenolics were removed by hydrotreating throughout the run.

FATE OF PS

Earlier work with samples from Runs POC-2, CMSL-8, and CMSL-9, in which virgin polystyrene (PS) was a feedstock, indicated that ~70% of the PS fed could be identified as components (toluene, ethylbenzene, and cumene) in the unhydrotreated product oil and ~50% in the hydro-treated product oil.¹⁻⁴ Cumene alone accounted for ~16% of the PS fed in the unhydrotreated product oil, and ~10% in the hydrotreated product oil. Cumene is a good marker for PS-derived products, because it is found principally in product oil samples from co-liquefaction with PS as a feed component. In the unhydrotreated first-stage product oils from Run PB-04, 1,3-diphenyl propane was also identified as a unique PS marker. However, this compound seems to be clearly identifiable and quantifiable primarily when the product oil is unhydrotreated. The components used for identification and quantification by CONSOL contain aromatic rings, because these components are readily identified by their mass spectra using automated searches of spectral databases.

Concentrations of four PS-derived compounds identified by GC-MS in the SOH1 samples from Run PB-04 are shown in Table 12. The presence of cumene in products from liquefaction of MSW in Run CMSL-11 and ASR in Run PB-04 demonstrates the presence of PS as a feed component. The ASR and MSW feed materials are heterogeneous and are difficult to characterize directly to quantify individual polymer components. Based on earlier work with virgin plastics, the amount of PS in the waste feedstocks can be estimated for Run PB-04. Assuming the same degree of conversion takes place, and knowing the yield of the product oils,^{7,8} it is estimated that PS constitutes about 12 wt % of the MF feed ASR in Conditions 3 and 4 of Run PB-04.

The four PS marker compounds (Table 12, Figure 3) constituted about 11-42% of the SOH1 samples in Conditions 3-5 of Run PB-04. In contrast, the Condition 1 (coal-only) SOH1 contained only 2% of three of these markers (1,3 diphenyl propane was not present). These marker compounds seem to represent primary fragments of PS liquefaction, as shown in Figure 3. Benzene, methane, and ethane could also be primary products, but they also are produced from coal. Hydrotreating toluene and the larger components may cause cracking or ring hydrogenation. Any products that elute before toluene, or do not contain an aromatic ring, are less-readily identified or quantified because they are not unique to PS liquefaction.

The observed distribution of these four components on a relative weight percent basis is : toluene - $12.6 \pm 2.7\%$, ethylbenzene - $63.7 \pm 4.9\%$, cumene - $21.4 \pm 2.8\%$, and 1,3-diphenylpropane - $2.4 \pm 0.5\%$. On a mol percent basis, the distribution becomes: toluene - 14.7% , ethylbenzene - 64.8% , cumene - 19.2% , and 1,3-diphenylpropane - 1.3% . An uneven distribution of alkyl vs. phenyl groups in the products (ethylbenzene has the proper distribution) would imply that these products are accompanied by the production of some (unaccounted) combination of methane, ethane, benzene, and cyclohexane (in the simplest possible molecules). The observed distribution indicates that $3.2 \text{ mol } \% \text{ benzene} + 3.2 \text{ mol } \% \text{ methane}$ would account for the imbalance (i.e., there is more cumene than toluene plus 1,3-diphenylpropane). Thus, little gas yield is required to balance the observed PS product distribution. Although the data may not support a rigorous conclusion, the results suggest that the production of light gases such as methane and ethane from liquefaction of polystyrene is minor. These estimates leave about 20% of the PS as unaccounted. In addition to benzene, the unaccounted portion of the product could be naphthenic hydrogenation products that are not readily identified.

FATE OF HDPE AND PP

Previous work demonstrated that polyolefins, primarily HDPE and PP, could be extracted from co-liquefaction stream samples. The amount of this material rejected from the process represents the amount that is not converted to liquid products. FTIR spectroscopy (Figure 4) was used to identify PP and HDPE (and perhaps LDPE) in polyolefin material extracted from feed slurries and L-892 feed blends (not shown) from Run PB-04. These results indicate that PP was a significant component of the feed ASR. The material extracted from the pressure-filter cake stream that is used to reject solids from the process consists entirely of polyethylene (Figure 4), apparently only HDPE, although some could be LDPE or other PE. This is consistent with earlier observations that PP is more reactive than the HDPE at the liquefaction conditions.

Table 13 presents the ash-balanced, overall conversions of the total MAF feed, the total MAF waste/polymer feed, and the decalin-extracted polyolefins. The overall conversion is calculated from the compositions and flow rates^{7,8} of the net product and fresh feeds. However, decalin-extracted polyolefins were determined on the Run PB-04 feed slurry samples, since no ASR sample was available. The recycled ash and polyolefins contributions were backed out to determine the relative concentrations of fresh polyolefins and ash. In turn, this allowed the percentage polyolefins in the ASR to be estimated at 79-90% MAF, or 62-73% (average of 68%) MF.

The CONSOL MAF fresh feed conversion results are compared with HTI results in Table 13 to demonstrate that the ash balance technique typically gives conversions very similar to those of HTI. The exception in these data are the results for Conditions 4 and 5, for which the CONSOL conversions were ~3-5% lower than those obtained by HTI, possibly due to the difference between the solvents used. CONSOL used THF to define conversion (THF does not dissolve the unconverted polyolefins). HTI used hot quinoline to define conversion (hot quinoline does dissolve the unconverted polyolefins). The same ash balance method was used to calculate conversions of the total wastes and the decalin-extracted polyolefins. The results indicate high conversion of the total waste/polymer stream and of the polyolefins, ~95-99%. The conversions of these components were typically about 5% higher than HTI's conversions of the total fresh feed. The lower conversions observed by CONSOL for the total waste/polymer component and for the decalin-extracted polyolefins corresponded to Conditions 4 and 5 of Run PB-04, in which HTI also observed the lowest fresh feed conversions. Recycle of unconverted polyolefins (apparently chiefly HDPE) is required to achieve these high conversions. Evidently, conditions used in Conditions 4 and 5 of Run PB-04 were not optimal to convert all of the ASR or polyolefin component of the ASR. In Run CMSL-11, HTI used higher reactor temperatures, higher Mo and Fe catalyst concentrations (and different catalyst precursors) to achieve high conversion of the MSW polymers.

Section 4

CONCLUSIONS

Conclusions are provided in the Executive Summary section of the report.

Section 5

REFERENCES

1. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P., "A Characterization and Evaluation of Coal Liquefaction Process Streams, Quarterly Technical Progress Report, October 1 through December 31, 1994", DOE/PC 93054-10, May 1995.
2. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P., "A Characterization and Evaluation of Coal Liquefaction Process Streams, Quarterly Technical Progress Report, April 1 through June 30, 1995", DOE/PC 93054-18, September 1995.
3. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P., "A Characterization and Evaluation of Coal Liquefaction Process Streams, Quarterly Technical Progress Report, October 1 through December 31, 1995", DOE/PC 93054-25, May 1996.
4. Robbins, G. A.; Brandes, S. D.; Winschel, R. A., "A Characterization and Evaluation of Coal Liquefaction Process Streams, Quarterly Technical Progress Report, April 1 through June 30, 1996", DOE/PC 93054-34, March 1997.
5. Robbins, G. A.; Winschel, R. A.; Burke, F. P. "Determination of Unconverted HDPE in Coal/Plastics Co-Liquefaction Stream Samples", *Prepr. ACS Div. Fuel Chem.* **1996**, *41* (3), 1069.
6. Draft internal HTI report on Run CMSL-11.
7. Comolli, A. G.; Pradhan, V. R.; Lee, T. L. K.; Karolkiewicz, W. F.; Popper, G. "Direct Liquefaction Proof-of-Concept Program, Topical Report, Bench Run 4 (227-95)", DOE Report DE-92148-TOP-06, March 1997, and an earlier internal draft report dated August 7, 1996.
8. Material balance data provided by J. Hu of HTI, July 2, 1997.
9. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P., "A Characterization and Evaluation of Coal Liquefaction Process Streams, Quarterly Technical Progress Report, January 1 through March 31, 1996", DOE/PC 93054-29, July 1996.

Section 6

LIST OF ABBREVIATIONS AND ACRONYMS

ASTM	American Society for Testing and Materials
CMSL	Run designation used by HTI for catalytic multi-stage liquefaction
DOE	Department of Energy
FTIR	Fourier-transform infrared
GC-MS	Gas chromatography-mass spectrometry
HDPE	High density polyethylene
HTI	Hydrocarbon Technologies, Inc.
HTU	Hydrotreater unit
IBP	Initial boiling point
IOM	Insoluble organic matter
L-814	HTI oil used for run start-up and, occasionally, as a make-up oil
MAF	Moisture and ash free
MF	Moisture free
NMR	Nuclear magnetic resonance
PB	POC bench option, HTI run designation
PFC	Pressure filter cake
PFL	Pressure filter liquid
POC	Proof of concept
PP	Polypropylene
PS	Polystyrene
SOH	Separator overhead
SOH1	First-stage SOH; a component of the HTU feed
SOH2	Second-stage SOH; the hydrotreated net product
THF	Tetrahydrofuran
TNPS	Di-tertiary-nonyl polysulfide
VSB	Vacuum still bottoms
VSO	Vacuum still overhead
VTB	Vacuum tower bottoms
LDPE	Low-density polyethylene

TABLE 1

**HTI OPERATING CONDITIONS AND PROCESS PERFORMANCE SUMMARY
FOR RUN PB-04 (227-95)**

Date, 1996 Condition Period Number	6/8 1 5	6/17 2 14-15	6/15 3 12	6/24 4 21	6/26 5 23
Process Conditions					
Space Velocity, MF fresh feed/reactor volume K-1 (kg/h/m ³)	718	635	602	632	621
Reactor Temperatures, °C					
K-1	441	442	441	442	441
K-2	449	451	451	450	449
Recycle Ratio (a)	1.2(a)	1.2	1.2	1.5	1.5
Feed Composition, wt %					
Black Thunder Mine Coal	100	None	50	75	50
Hondo VTB Oil	None	70	30	None	None
ASR	None	30	20	25	25
Virgin Plastics (Simulated Waste)	None	None	None	None	25*
Net Normalized Yields, wt % MAF Fresh Feed					
C ₁ -C ₃ in Gases	9.89	6.97	8.56	6.91	7.83
C ₄ -C ₇ in Gases	3.47	3.09	3.32	6.57	8.15
IBP-177 °C (IBP-350 °F)	16.78	18.32	22.17	8.12	12.56
177-260 °C (177-260 °F)	10.37	10.88	11.99	9.35	9.56
260-343 °C (260-343 °F)	15.34	12.07	10.85	7.20	9.98
343-454 °C (343-454 °F)	18.47	18.03	13.57	18.32	16.79
454-524 °C (454-524 °F)	3.12	6.70	4.90	7.05	4.38
524 °C ⁺ (975 °F ⁺)	3.73	15.95	10.47	18.03	13.99
Unconverted Coal	6.82	3.61	5.97	9.55	8.78
Water Yield by Forced Oxygen Balance	12.08	4.37	9.01	11.32	8.11
CO _x	6.53	0.62	2.64	3.90	4.01
NH ₃	0.88	1.46	1.33	0.55	0.47
H ₂ S	-0.34	2.70	0.95	-0.88	-0.63
Process Performance, wt % MAF Fresh Feed					
Material Recovery Balance	100.80	100.55	102.74	104.35	104.06
Ash Recovery	100.21	99.36	99.43	99.98	99.90
Hydrogen Consumption	7.21	4.76	5.71	5.99	3.97
Total Feed Conversion (SO ₃ Free)	93.21	96.41	94.07	90.49	91.25
524 °C ⁺ Conversion	89.45	80.45	83.57	72.42	77.23
C ₄ -524 °C Distillates	67.53	69.09	66.80	56.61	61.41
524 °C ⁺ Resid Yield	3.73	15.95	10.47	18.03	13.99

(a) Recycle was non-ashy extinction recycle of 454 °C⁺ portion PFL during periods 1-10, ashy recycle via PFC was used for the remainder of the run.

Process Conditions Used for Entire Run

Dispersed Catalyst Loading, mg/kg

Unit Back Pressure, 2500 psig

Iron = 1000; Molybdenum = 50; Phosphorous = 100

*60% HDPE + 40% PS

Source: Reference 7

TABLE 2
HTI ANALYSES OF FEEDSTOCKS FOR RUN PB-04

Feed	Black Thunder Mine Feed Coal, HTI 6213	Hondo VTB Resid	ASR (a)
Moisture Content, wt %	10.01	ND	ND
Gravity API °	NA	6.2	NA
524 °C ⁺ Resid Content, vol %	NA	82.0	100
<u>Proximate Analysis, wt % Dry</u>			
Volatile Matter	43.48	NA	NA
Fixed Carbon	50.52	NA	NA
Mineral Matter	6.00	NA	NA
<u>Ultimate Analysis, wt % Dry</u>			
Carbon	70.12	83.84	48.87
Hydrogen	5.11	10.13	3.83
Nitrogen	0.99	0.90	3.60
Sulfur	0.35	4.39	0.72
Ash	6.19	0.15	19.68
Oxygen (Diff.)	17.24	0.59	23.32

(a) Obtained from Camden Metal and Recycling in New Jersey

NA = Not applicable

ND = Not Determined

Source: Reference 7

TABLE 3

**COMPONENTS FOUND IN PROCESS STREAM SAMPLES
FROM CO-LIQUEFACTION OF WASTE POLYMERS WITH COAL
HTI RUN PB-04**

	Component						
Stream Sample from Process	HDPE	PP	LDPE or Other PE	PS	Ash	Other Polymers	Methods
Feed MSW	X	X		I	X	E	DE, FTIR
Feed ASR	I	I		I	X	E	
MSW Feed Slurry	X	X		I	X	E	DE, FTIR
ASR Feed Slurry	X	X	S	I	X	E	DE, FTIR
Separator Bottoms	X	C			X		DE, FTIR
Filter Liquid	X	C	S				DE, FTIR
Filter Solids	X	C	S		X		DE, FTIR
First-Stage Oil	P	E		P			GC-MS
Product Oil	P	E		P			GC-MS
Legend: X = Direct evidence I = Indirect evidence P = Evidence for a product E = Expected, but not identified S = Suspected, i.d. uncertain C = Contrary evidence (i.e., that it is not present) DE = Hot decalin extraction							

TABLE 4
COMPONENT DISTRIBUTION OF WHOLE SAMPLES,
HTI RUN PB-04 (227-95)

Sample	Condition	Period	wt % of Sample			
			454 °C ⁻ Dist.	454 °C ⁺ Resid THF Sols	IOM	Ash
O-6 bottom	1	6A	43.4	44.2	5.1	3.9
O-6 Bottoms	2	15A	39.4	38.4	17.0	1.5
O-6 Bottoms	3	12B	39.8	44.2	6.1	5.8
O-6 Bottoms	4	21A	34.5	47.0	9.5	4.9
O-6 Bottoms	5	23A	26.1	54.6	5.6	3.9
PFL	1	6B	48.5	40.5	4.5	2.9
PFL -235 unit	2	14, 15, 17	47.5	47.5	1.3	0.5
PFL	3	12B	42.9	49.4	3.4	<.1
PFL	4	21B	35.9	53.7	6.0	<.1
PFL	5	23B	35.3	23.1	34.6	<.1
PFS	1	6B	ND	51.7 (a)	23.3	25.0
PFS-235 unit	2	14, 15, 17	ND	35.0 (a)	28.0	37.0
PFS	3	12B	ND	40.2 (a)	21.4	38.4
PFS	4	21B	ND	33.5 (a)	36.3	30.2
PFS	5	23B	ND	27.3 (a)	45.1	27.6
Sample			Moisture	THF Sols	IOM	Ash
Feed Slurry	1	6A	5.1	47.3 (b)	44.0	3.6
Feed Slurry	3	12A	2.4	66.3 (b)	26.8	4.5
Feed Slurry	4	21A	4.4	64.0 (b)	28.3	3.3
Feed Slurry	5	23B	1.9	61.5 (b)	33.3	3.3

ND = Not Determined

(a) Determined on the whole sample by difference from IOM and ash.

(b) Determined on the whole sample by difference from moisture (oven method), IOM, and ash.

TABLE 5

PROTON DISTRIBUTION OF WHOLE SAMPLES, HTI RUN PB-04 (227-95)

	Condi- tion	Period	% of Protons						
			Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
Hondo VTB resid			4.3	3.1	12.1	7.8	18.0	33.8	21.0
L-892 Feed Blend (a)	3	9B	6.2	6.2	11.7	7.9	16.9	31.8	19.4
L-892 Feed Blend (a)	3	12B	4.7	5.0	9.6	7.4	18.1	34.4	20.7
SOH First-Stage Oil	1	6B	4.8	9.0	7.1	10.5	14.9	28.3	25.4
SOH First-Stage Oil	3	12B	4.0	6.3	5.1	7.7	14.7	30.1	32.1
SOH First-Stage Oil	4	21B	7.4	12.3	8.5	11.5	12.7	28.0	19.6
SOH First-Stage Oil	5	23B	8.9	9.5	8.0	9.7	11.4	31.4	21.1
SOH Second-stage Oil	1	5A	0.6	3.1	5.1	5.1	21.2	34.8	30.0
SOH Second-stage Oil	1	5B	0.7	3.4	3.6	4.1	20.9	35.3	32.1
SOH Second-stage Oil	2	15A	1.4	2.8	2.8	3.7	13.7	36.0	39.6
SOH Second-stage Oil	3	12A	1.3	3.4	4.0	4.2	17.8	35.2	34.2
SOH Second-stage Oil	3	12B	1.1	3.3	3.6	4.1	17.2	35.8	34.8
SOH Second-stage Oil	4	20A	6.3	11.4	8.1	10.1	13.4	29.6	21.2
SOH Second-stage Oil	5	22A	6.0	9.9	7.0	9.3	13.3	31.2	23.3
O-6 Bottoms	1	6A	20.4	13.4	15.1	11.7	11.3	17.7	10.4
O-6 Bottoms	2	15A	12.5	6.5	10.7	8.9	12.0	31.4	18.0
O-6 Bottoms	3	12B	19.9	9.3	13.6	10.6	11.1	22.9	12.7
O-6 Bottoms	4	21A	17.4	6.9	12.7	9.8	10.7	29.5	13.1
O-6 Bottoms	5	23A	16.7	6.2	11.6	9.4	10.8	29.6	15.7
PFL	1	6B	22.0	11.5	15.7	11.6	11.2	18.5	9.6
PFL -235 unit	2	14, 15, 17	16.6	10.6	10.6	11.9	10.8	24.9	14.6
PFL	3	12B	19.5	10.2	12.8	11.0	11.0	23.1	12.4
PFL	4	21B	15.6	6.4	11.8	9.3	10.8	31.8	14.5
PFL	5	23B	17.1	5.9	11.9	9.6	10.9	29.4	15.2
Feed Slurry	1	6A	22.1	7.8	18.4	10.4	11.5	20.1	9.7
Feed Slurry	3	12A	16.8	5.4	13.9	9.3	13.9	26.8	13.9
Feed Slurry	4	21A	20.8	5.2	14.1	9.5	12.5	25.9	12.0
Feed Slurry	5	23B	23.8	8.8	14.2	8.9	12.7	21.6	10.1
PFS (a)	1	6B	28.6	6.8	17.0	11.5	12.1	17.4	6.5
PFS (a)	3	12B	25.9	5.9	15.1	10.2	11.2	20.1	11.5
PFS (a)	4	21B	28.6	5.6	16.2	10.6	11.3	17.3	10.4
PFS (a)	5	23B	32.1	6.1	16.2	10.2	10.3	16.5	8.6
Interstage (b,c)	1	6B	21.0	10.5	16.0	11.4	12.1	18.9	10.2
Interstage (b,c)	3	12B	20.5	6.5	15.6	10.8	11.6	23.2	11.8
First- Stage Slurry (b,c)	3	12B	14.9	6.3	12.6	9.8	12.7	28.1	15.5

- (a) Dissolved in 99.96% d₅-pyridine and filtered prior to running NMR spectrum. All other samples were dissolved in 99.8% CDCl₃ and filtered prior to running NMR spectrum, except that SOH samples were unfiltered.
- (b) Interstage and First-Stage Slurry are alternative names for the same type of sample. Names listed in the table are those that appeared on sample labels as received from HTI.
- (c) HTI reported successful interstage sampling only for Condition 1. ⁷

TABLE 6

**PROTON DISTRIBUTION OF DISTILLATE SAMPLES AND RESID SAMPLES, HTI RUN
PB-04 (227-95)**

	Condi- tion	Period	% of Protons						
			Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
454 °C ⁻ Distillates									
O-6 Bottoms	1	6A	17.4	9.2	15.6	12.1	12.3	22.6	10.9
O-6 Bottoms	2	15A	11.2	5.9	10.3	9.0	12.7	32.1	18.8
O-6 Bottoms	3	12B	16.1	7.7	12.9	10.7	11.5	26.5	14.7
O-6 Bottoms	4	21A	18.3	8.6	13.4	11.6	11.1	24.9	12.1
O-6 Bottoms	5	23A	22.3	2.5	11.4	11.0	10.7	28.0	14.1
PFL	1	6B	18.7	9.2	15.9	11.8	12.0	22.6	9.9
PFL -235 unit	2	14, 15, 17	16.3	6.3	11.9	10.1	11.4	28.7	15.3
PFL	3	12B	17.0	6.9	13.3	10.7	11.4	26.9	13.7
PFL	4	21B	18.7	7.7	13.7	11.4	11.2	25.4	11.9
PFL	5	23B	15.7	5.8	11.3	9.5	11.1	31.6	15.0
454 °C ⁺ Resids									
O-6 Bottoms	1	6A	34.5	9.6	17.9	10.3	10.5	10.4	6.7
O-6 Bottoms	2	15A	33.3	8.0	16.0	10.7	9.6	14.4	8.0
O-6 Bottoms	3	12B	28.8	9.1	15.4	10.1	10.7	16.2	9.7
O-6 Bottoms	4	21A	30.5	9.9	16.9	11.3	10.4	13.1	7.8
O-6 Bottoms	5	23A	20.7	4.8	12.6	8.7	12.8	26.7	13.8
PFL	1	6B	41.1	2.6	18.6	10.3	10.4	10.5	6.5
PFL -235 unit	2	14, 15, 17	26.1	5.3	13.9	9.7	11.4	21.4	12.2
PFL	3	12B	31.9	6.8	16.8	10.2	10.8	15.5	8.0
PFL	4	21B	33.1	7.3	18.1	10.7	10.7	12.9	7.3
PFL	5	23B	26.7	3.7	14.3	8.9	11.0	23.3	12.0

Note: Resids were dissolved in 99.96% d₅-pyridine and filtered prior to running NMR spectrum. Distillate samples were dissolved in 99.8% CDCl₃ and not filtered.

TABLE 7

PHENOLIC -OH CONCENTRATION IN SAMPLES, HTI RUN PB-04 (227-95)

Sample			Phenolic -OH	
Type	Condition	Period	Concentration, meq/g	Peak Pos., cm ⁻¹
454 °C Distillates				
O-6 Bottoms	1	6A	1.01	3305
O-6 Bottoms	2	15A	0.41	3307
O-6 Bottoms	3	12B	0.67	3305
O-6 Bottoms	4	21A	0.82	3305
O-6 Bottoms	5	23A	0.62	3305
PFL	1	6B	0.94	3305
PFL -235 unit	2	14, 15, 17	0.49	3305
PFL	3	12B	0.66	3304
PFL	4	21B	0.77	3305
PFL	5	23B	0.42	3305
454 °C Resid THFS				
O-6 Bottoms	1	6A	0.66	3300
O-6 Bottoms	2	15A	0.69	3292
O-6 Bottoms	3	12B	0.73	3294
O-6 Bottoms	4	21A	0.97	3291
O-6 Bottoms	5	23A	0.55	3296
PFL	1	6B	0.89	3292
PFL -235 unit	2	14, 15, 17	0.45	3293
PFL	3	12B	0.79	3292
PFL	4	21B	0.97	3292
PFL	5	23B	0.50	3294
Whole Samples				
Hondo VTB resid			0.29	3311
SOH First-Stage Oil	1	6B	1.50	3309
SOH First-Stage Oil	3	12B	0.83	3309
SOH First-Stage Oil	4	21B	1.34	3309
SOH First-Stage Oil	5	23B	1.02	3309
SOH Second-stage Oil	1	5A	ND	ND
SOH Second-stage Oil	1	5B	ND	ND
SOH Second-stage Oil	2	15A	ND	ND
SOH Second-stage Oil	3	12A	ND	ND
SOH Second-stage Oil	3	12B	ND	ND

ND = None Detected

TABLE 8
MICROAUTOCLAVE SOLVENT QUALITY TESTS,
HTI RUN PB-04 (227-95)

HTI Run PB-04	Condition	Period	Coal Conversion
454 °C ⁻ Distillates			
O-6 Bottoms	1	6A	82.5
O-6 Bottoms	2	15A	57.9
O-6 Bottoms	3	12B	76.9
O-6 Bottoms	4	21A	79.0
O-6 Bottoms	5	23A	65.8
PFL	1	6B	85.3
PFL -235 unit	2	14, 15, 17	70.4
PFL	3	12B	77.0
PFL	4	21B	78.2
PFL	5	23B	61.5
Whole Samples			
Hondo VTB resid (a)			39.8
O-6 Bottoms	1	6A	68.2
O-6 Bottoms	2	15A	74.9
O-6 Bottoms	3	12B	69.9
O-6 Bottoms	4	21A	52.6
O-6 Bottoms	5	23A	22.8/20.3
PFL	1	6B	70.8
PFL -235 unit	2	14, 15, 17	69.4
PFL	3	12B	61.9
PFL	4	21B	48.7
PFL	5	23B	48.8

Standard test conditions: 9 g solvent, 6 g Old Ben (Indiana 5) coal, 399 °C, 30 min, MAF conversion to THF solubles reported.

(a) Used in place of solvent in test.

TABLE 9

**RESULTS OF HOT DECALIN EXTRACTIONS OF SAMPLES,
HTI RUN PB-04 (227-95)**

	Condi- tion	Period	% of Sample, Normalized			% Recovery
			THF/ Decalin Insolubles	THF/Decalin Solubles	Plastic	
454 °C+ Resids						
O-6 Bottoms	1	6A	17.4	81.6	1.0	102.9
O-6 Bottoms	2	15A	8.9	71.4	19.7	100.5
O-6 Bottoms	3	12B	19.1	79.2	1.8	104.1
O-6 Bottoms	4	21A	19.1	76.3	4.5	101.5
O-6 Bottoms	5	23A	12.4	84.6	3.0	102.2
PFL	1	6B	15.3	84.7	0.0	103.6
PFL -235 unit	2	14, 15, 17	2.0	97.7	0.3	103.7
PFL	3	12B	2.9	95.0	2.1	103.2
PFL	4	21B	3.2	90.9	5.8	102.7
PFL	5	23B	1.5	48.0	50.5	99.7
Whole Samples						
PFS	1	6B	51.7	48.3	0.0	104.2
PFS-235 unit	2	14, 15, 17	65.9	34.0	0.1	103.0
PFS	3	12B	58.6	41.0	0.5	98.2
PFS	4	21B	64.2	33.2	2.6	97.7
PFS	5	23B	68.4	27.7	3.8	96.3
Feed Slurry	1	6A	47.5	52.1 (a)	0.4	97.4
Feed Slurry	3	12A	31.3	65.1 (a)	3.6	100.8
Feed Slurry	4	21A	31.7	62.3 (a)	6.1	102.7
Feed Slurry	5	23B	36.4	51.8 (a)	11.8	104.4
L-892 Feed Blend (b)	3	9B	26.8	68.0	5.1	98.0
L-892 Feed Blend (c)	3	12B	6.8	74.9	18.3	103.4

- (a) May include unremoved moisture (see Table 4).
 (b) This sample contains 8.3% ash, as-determined.
 (c) This sample contains 4.5% ash, as-determined.

TABLE 10

**AROMATIC AND PARAFFINIC HYDROGEN CONTENT OF SAMPLES,
HTI RUN PB-04 (227-95)**

Condition	1	2	3	4	5
Period	1-6	15-17	9-12	18-21	22-23
Hydrogen Aromaticity (a), % of Protons					
SOH1	13.8	-	10.3	19.7	18.4
SOH2	3.9	4.2	4.6	17.7	15.9
O-6 Bottoms 454 °C ⁻ Distillate	26.6	17.1	23.8	26.9	24.8
PFL 454 °C ⁻ Distillate	27.9	22.6	23.9	26.4	21.5
Feed Slurry Whole	29.9	-	22.2	26.0	32.6
O-6 Whole	33.8	19.0	29.2	24.3	22.9
PFL Whole	33.5	27.2	29.7	22.0	23.0
PFS Whole	35.4	-	31.8	34.2	38.2
O-6 Bottoms 454 °C ⁺ Resid	44.1	41.3	37.9	40.4	25.5
PFL 454 °C ⁺ Resid	43.7	31.4	38.7	40.4	30.4
Hydrogen Paraffinicity (b), % of Protons					
SOH1	53.7	-	62.2	47.6	52.5
SOH2	66.1	75.6	70.0	50.8	54.5
O-6 Bottoms 454 °C ⁻ Distillate	33.5	50.9	41.2	37.0	42.1
PFL 454 °C ⁻ Distillate	32.5	44.0	40.6	37.3	46.6
Feed Slurry Whole	29.8	-	40.7	37.9	31.7
O-6 Whole	28.1	49.4	35.6	42.6	45.3
PFL Whole	28.1	39.5	35.5	46.3	44.6
PFS Whole	23.9	-	31.6	27.7	25.1
O-6 Bottoms 454 °C ⁺ Resid	17.1	22.4	25.9	20.9	40.5
PFL 454 °C ⁺ Resid	17.0	33.6	23.5	20.2	35.3

- (a) Aromatic hydrogen content defined as the sum of uncondensed and condensed aromatic proton categories, as reported in Tables 5 and 6.
- (b) Paraffinic hydrogen content defined as the sum of alkyl beta and gamma aliphatic proton categories, as reported in Tables 5 and 6.

TABLE 11
GC-MS CHROMATOGRAPHIC DATA FROM SOH OILS,
RUN PB-04 (227-95)

Sample		Stage 1 SOH Oil				Stage 2 SOH Oil		
Condition		1	3	4	5	1	2	3
Period		6B	12B	21B	23B	5B	15A	12B
Compound	Ret. Time, min.	Area % of Integrated Signal						
Cyclohexane (a)	4.28-4.74	1.08	0.73	0.99	0.57	3.56	0.53	0.91
Methyl Cyclohexane (a)	7.23-7.53	ND	0.78	1.10	0.59	4.87	ND	1.22
Toluene	9.99- 10.70	0.32	1.29	3.95	4.43	0.25	0.70	0.33
Ethyl Benzene	17.38-18.73	1.66	7.49 (b)	15.8	26.82	ND	2.25	2.04 (b)
Cumene	22.52-23.29	0.18	1.85	5.13	9.40	0.35	0.84	0.10
1,3 Diphenyl Propane	66.40-66.44	ND	0.18	0.59	0.98	ND	ND	ND

- (a) Cyclohexane and methyl cyclohexane are potential markers for products of coal, and are potential markers for hydrotreated products of liquefied PS. In some cases, the peaks integrated represent poor match quality for these compounds in a spectral search against a library of standard spectra.
- (b) Manually computed from overlapping peaks by using ion 91 data to resolve the ethylbenzene contribution.

Ethylbenzene peak area obtained by:

$$\text{Area}_{\text{EB}} = (A_{91}/A_{\text{Tot}}) \times (A_{\text{EB}}/A_{91\text{EB}})$$

Area_{EB} is ethyl benzene peak area

A₉₁ is Ion 91 abundance in unresolved sample peak

A_{Tot} is Total ion abundance in unresolved sample peak

A_{EB} is Total ion abundance in EB

A_{91EB} is Ion abundance in EB

TABLE 12

PS LIQUEFACTION PRODUCTS FOUND IN FIRST-STAGE OILS, RUN PB-04

Component	Toluene	Ethylbenzene	Cumene	1,3-Diphenyl propane	Sum
Concentration in SOH1, wt %					
Condition 1	0.3	1.7	0.2	0.0	2.2
Condition 3	1.3	7.5	1.9	0.2	10.8
Condition 4	4.0	15.8	5.1	0.6	25.5
Condition 5	4.4	26.8	9.4	1.0	41.6
Concentration in SOH1 as wt % of ASR fed, adjusted to eliminate coal contribution					
Condition 3	1.4	8.0	2.1	0.2	11.7
Condition 4	1.1	4.2	1.6	0.2	7.1
Condition 5	3.0	18.2	6.6	0.7	28.5
Average Relative Distribution					
wt %	12.6 $\pm$ 2.7	63.7 $\pm$ 4.9	21.4 $\pm$ 2.8	2.4 $\pm$ 0.5	100.0
mol%	14.7	64.8	19.2	1.3	100.0
C Balance	+1CH ₂	0	-1CH ₂	+1CH ₂	
Net C Balance	-3.2 mol% CH ₂ , or +3.2 mol% (benzene +CH ₂)				

TABLE 13

OVERALL CONVERSION OF FEED AND POLYMER FEED COMPONENTS,
HTI RUNS PB-04 AND CMSL-11

	Overall Conversion, %					
Source	PB-04 Cond. 1	PB-04 Cond. 2	PB-04 Cond. 3	PB-04 Cond. 4	PB-04 Cond. 5	CMSL-11 Cond. 3B
Basis: MAF Fresh Feed, Ash-Balanced						
CONSOL	93.7	95.0	95.7	87.1	85.5	94.3
HTI (a)	93.2	96.4	94.1	90.5	91.3	94.7
Basis: MAF Fresh Waste/Polymer, Ash-Balanced						
CONSOL	NA	99.9 (b)	99.4 (b)	95.8 (b)	96.8 (b)	99.1 (c)
Basis: Fresh Decalin-Extractable Polyolefins in Feed, Ash-Balanced						
CONSOL	NA	NA	99.3(c,d)	95.4(c,d)	NA	NA

- (a) SO₃-free ash basis, data from Reference 7.
 (b) % MAF ASR in feed (+ virgin polymers in feed in Condition 5).
 (c) % Decalin-extracted polyolefin in feed (d) Back-calculation from Condition 3 results indicates that the feed ASR contains 79% MAF decalin-extracted polyolefin (63% on MF basis). From Condition 4 results, the feed ASR contains 90% MAF decalin-extracted polyolefin (72% on MF basis).

Figure 2. GC-MS Total Ion Chromatograms of First-Stage SOH Oils, Run PB-04.
(T = toluene; EB = ethyl benzene; C = cumene; DPP = 1,3 diphenylpropane)

Figure 3. Polystyrene Liquefaction Products Found in Net Product Oils (SOH1 and SOH2 Oils).

Figure 4. FTIR Spectra of Decalin Extracts From Feed Slurry and Filter Cake (PFS) Produced in Condition 5 of HTI Run PB-04

APPENDIX 1

THE REACTIVITY OF DIRECT COAL LIQUEFACTION RESIDS

For presentation at the

DOE Coal Liquefaction and Solid Fuels Contractors Review Conference
Pittsburgh, PA

September 3-4, 1997

THE REACTIVITY OF DIRECT COAL LIQUEFACTION RESIDS

Brandes, S. D.,^a Winschel, R. A.,^a Calkins, W. H.,^b Klein, M. T.,^b Huang, H.,^{b,c} Campbell, D.,^b Wang, S.,^b Wang, K.^b

a) 412-854-6568

412-854-6613 (fax)

CONSOL Inc.

4000 Brownsville Rd

Library, PA 15129

b) 302-831-2213

302-831-1048 (fax)

Dept of Chemical Engineering

University of Delaware

Newark, DE 19716-3110

c) Current Address

860-565-4321

United Technologies

411 Silver Lane

East Hartford, CT 06108

SUMMARY

An empirical test for determining the relative reactivity of coal liquefaction resid was developed using the University of Delaware short contact time batch reactor and applied to a suite of fifteen coal liquefaction distillation resid. Conversions of resid to distillate obtained thermally and catalytically are significantly different. Kinetic data, although limited, indicate that a component of the resid is not convertible. An unconvertible insoluble resid component was isolated and its role in resid reactivity is being investigated. A structural model of distillation resid was developed that models the characteristics of the soluble portion of the resid. A reaction model was developed that produces a conversion value for each resid that is within two standard deviations of the experimentally determined values.

BACKGROUND

In the first stage of current two-stage direct coal liquefaction processes, coals are readily converted to non-distillable products (resid) and some distillate. The resid is partially converted to distillate in the second stage of the process. The resid is combined with fresh coal (in a ratio often greater than 1:1, resid:coal) and some vacuum gas oil. This mixture is recycled to the first stage to further convert the resid. Recycled resid is thus a major component of the feed to the process. Its conversion to distillate is a key reaction. Understanding the chemistry of resid and resid reactivity is important to improve direct liquefaction processes design and to reduce production costs for coal liquids.

OBJECTIVES

The three objectives of this study are to understand the chemical characteristics of coal liquefaction resid, the formation of coal liquefaction resid, and the reactivity of coal liquefaction resid. Two questions which were addressed to attain these objectives are: 1) What makes one resid more reactive than another? and 2) What are the effects of process conditions (residence time, temperature, H₂ pressure, catalyst type and loading, coal feed, etc.) on the resid formation and the resid reactivity? The development of an empirical test of relative resid reactivity and the construction of a quantitative model of resid conversion were undertaken to answer these questions.

APPROACH

A suite of 15 coal liquefaction distillation resid samples (Table 1) chosen to represent a wide range of feed coal properties and liquefaction process conditions were characterized with a number of analytical techniques. Elemental analysis, field ionization mass spectrometric analysis, ¹H- and ¹³C- nuclear magnetic resonance spectroscopic analysis, vapor phase osmometry, and Fourier transform infrared spectroscopic analysis were obtained for most samples. Solubility class separations were accomplished by open column liquid chromatography. A number of other analytical techniques were used and results were reported previously.^{1,2}

The relative reactivity of the resids was determined using an empirical test developed for this purpose.² A short contact time batch reactor (SCTBR) was used to react the samples and a thermogravimetric analysis (TGA) method was developed to evaluate the products of reaction and allow for derivation of a conversion value. Design of the SCTBR system and TGA-based analytical procedures were reported in detail previously.³⁻⁷ Tests were made with and without catalyst. All tests were made in tetralin. Heat-up and cool-down times of the resid/tetralin feed mixtures are ca. 0.3 s. Agitation of the slurry is accomplished by an upflow of reacting gas (H₂ or N₂) at 1500 psi (cold). A homogeneous catalyst (Molybdenum naphthenate) was chosen for catalytic tests after trials with heterogeneous catalyst (presulfided Shell 324 Ni/Mo on alumina) proved difficult to use because the required high catalyst loadings resulted in viscous reaction mixtures and poor ash balances. Dimethyldisulfide (DMDS) was used to sulfide the Mo in situ. Tests were made under a range of solvent/resid ratios, residence times, and reaction temperatures. Reported here are results of tests made at 420 °C, 30 min, and tetralin/resid = 3/1. Conversion values were determined by separating Tetralin-soluble and insoluble fractions of the reaction products by filtration. The insoluble fraction was subjected to a simulated distillation method which uses thermogravimetric analysis (TGA) techniques to determine the amount of material boiling below 454 °C. The soluble fraction was distilled to remove most of the tetralin, analyzed by gas chromatography to determine the quantity of tetralin remaining, and analyzed by TGA to determine the amount of material boiling below 454 °C. Conversion was calculated as follows:

$$\text{Conversion} = \text{tetralin soluble fraction} \times \left(1 - \frac{\text{fraction boiling above } 454^{\circ}\text{C}}{\text{resid soluble fraction}}\right)$$

where the tetralin soluble fraction was determined by ash content of the insoluble resid after hydroprocessing. Resid soluble fraction is the amount of material soluble in tetralin prior to hydroprocessing. Conversion values for all 15 resids are given in Table 2. Values presented in Table 2 were replicated with a standard deviation of 4 wt% (abs.). The large differences (as much as 15 wt% abs.) in conversion among the resids are therefore considered bona fide.

Two of the fifteen resid samples were chosen to study the kinetics of hydroprocessing the resids. The two samples (W259 V131B and W260 V131B) were chosen because they gave the highest and lowest conversion under the standard test conditions (420 °C, 30 min, tetralin/resid = 3/1). Tests were made at 435 °C to augment tests made at 420 °C. Reaction times selected were 5 min and 10 min in addition to the 30 min data already acquired. Conversion leveled off with time, consistent with the presence of a non-convertible component (Figure 1).

Results obtained with the SCTBR indicate that the resid must be soluble in the reaction solvent for hydroprocessing (conversion to 454 °C- distillate) to occur. The resids contain ca. 5 to 15 wt% (ash-free basis) tetralin insolubles. This insoluble component is in part responsible for the unconvertible nature of the resid and the leveling off of conversion with time. Several resids were extracted with tetralin to obtain the insoluble fraction. These fractions were hydroprocessed under the same conditions (420 °C, 30 min, tetralin/insolubles= 3/1) as the resids. Less than 1 wt% of the insoluble fraction converted to 454 °C- product. The study of the insoluble fraction of the resid was expanded by looking at resids and the process streams from which the resids are derived to determine if the insoluble fraction of the resids formed as an artifact of the high temperature laboratory distillation used to make them. Petrographic analysis and elemental analyses of the insoluble materials indicate that they are, in part composed of unconverted coal macerals. The study of the insoluble portions of the resids is ongoing.

No 1:1 correlation of conversion with product characteristics such as elemental composition, aromatic carbon content or molecular weight were found; nor were correlations found with feed coal rank, sampling location, or other processing conditions. The question of what makes one resid more reactive than another can not be answered by this kind of simple analysis. A computer model capable of testing the sensitivity of resid conversion to the many different characteristics and processing parameters was developed to better determine the effects of resid characteristics and processing parameters on the resid reactivity.

The chemical characterization data and the resid conversion data from catalytic tests made in the SCTBR were used to construct a model of resid reactivity. A structural model was first constructed that represents the soluble portion of the resids. The structural model builds a representative set of molecules using a Monte Carlo technique. In this technique, each molecule is considered to be a set of building blocks or attributes (Table 3). Each of these attributes is described by a probability density function (pdf). The pdf's represent a quantitative probability that the attribute they represent will be less than or equal to a certain value. The pdf's were optimized to produce a set of representative molecules which closely match the experimentally determined soluble resid properties.

A deterministic reaction model was constructed using the optimized pdf's. Each reactive attribute undergoes reaction under a set of reaction rules (Table 4). The reactions result in a change in the relative concentration of the various attributes which, in turn, shifts the pdf's. At any chosen reaction time, the new pdf's can be used to construct a new molecular representation for comparison to the experimentally determined product properties. In the model, any low-boiling (<454°C) component of the resid was accounted for in the prediction of resid conversion. Conversions predicted from resid properties are within two experimental standard deviations of the experimentally determined conversions. (Table 5).

Recommendations

Several avenues of research are recommended to further an understanding of resid conversion. These include determining the impact of different liquefaction catalysts and residence times in different process steps of the liquefaction plant. Determining if catalytically and thermally produced conversion products of resids are chemically different may lead to a better understanding of the reaction pathways for resid conversion. Continued work is recommended to determine if the presence and concentration of insoluble, unreactive compounds in resids can be correlated with resid reactivity. The kinetic studies of resid conversion should be expanded and the data should be used to broaden the applicability of the reaction model.

The structural model and the reaction model incorporate a number of assumptions. More work needs to be done to verify the assumptions and correct or eliminate them. The structural model should be expanded to include terms associated with additional characterization data and should be expanded to include the insoluble portion of the resid. It is recommended that the reaction model be expanded to include terms associated with additional process conditions.

References

1. Brandes, S.D.; Robbins, G.A.; Winschel, R.A.; Burke, F. P. "The Chemical Nature of Coal Liquid Resids and the Implications for Process Development" Prepr. ACS Div. of Fuel Chem. **1992**, 37 (3), 1233.
2. Brandes, S.D.; Robbins, G.A.; Winschel, R.A., Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Volume II" Final Report, DOE/PC 89883-93, May 1994.

3. Huang, H.; Calkins, W. H.; Klein, M.T. "A Novel Short-time Reactor System for Studying the Initial Stages of Direct Coal Liquefaction" Prepr. ACS Div. of Fuel Chem. **1993**, 38 (3), 1080.
4. Huang, H. ; Wang, K. ; Wang, S.; Klein, M.T.; Calkins, W. H. "A Novel Method for the Determination of the Boiling Range of Liquid Fuels by Thermogravimetric Analysis" Prepr. ACS Div. of Fuel Chem. **1995**, 40 (3), 485.
5. Huang, H.; Wang, K. ; Wang, S.; Klein, M.T.; Calkins, W. H. "Applications of the Thermogravimetric Analysis in the Study of Fossil Fuels" Prepr. ACS Div. of Fuel Chem. **1996**, 41 (1), 1.
6. Huang, H.; Wang, K.; Wang, S.; Klein, M.T.; Calkins, W. H. "A Novel Smoothing Routine for the Data Processing in Thermogravimetric Analysis" Prepr. ACS Div. of Fuel Chem. **1996**, 41 (1), 27.
7. Huang, H.; Wang, K.; Wang, S.; Klein, M.T.; Calkins, W. H. "Kinetics of Hydroprocessing of Coal-Derived Vacuum Resids" Prepr. ACS Div. of Fuel Chem. **1997**, 42 (1), 125.

Figure 2. Catalytic Conversion of W259 V131B vs Time at 420 °C and 435 °

**Table 1. Sample Set for Resid Reactivity Testing and Sample Analyses
(Moisture and SO₃-Free Ash-Free Basis)**

Plant Run No.	HTI POC01	HTI POC02	Wilsonville Run 259			Wilsonville Run 260		
Feed Coal	Illinois No.6 Burning Star #2 Mine	Wyodak & Anderson Black Thunder Mine	Pittsburgh seam Ireland Mine			Wyodak & Anderson seam Black Thunder Mine		
Sampling location ^a	O-43	O-43	V1067	R1235	V131B	V1067	R1235	V131B
C, wt%	90.70	92.85	90.10	89.99	90.92	86.77	86.61	87.43
H, wt%	8.58	8.72	6.38	6.18	6.50	6.25	5.89	6.35
N, wt%	0.66	0.32	1.05	1.15	1.04	1.10	1.09	1.10
S, wt%	0.34	0.22	1.49	1.50	1.24	1.95	1.82	1.53
O, wt% (by diff)	0.10	2.13	0.98	1.18	0.30	3.93	4.59	3.59
f _a ^b	20.6	18.8	31.6	33.3	31.5	34.0	24.6	33.3
Plant Run No.	Wilsonville Run 261			Wilsonville Run 262			Wilsonville Run 258	
Feed Coal	Illinois No. 6 seam Burning Star # 2 Mine			Wyodak & Anderson seam Black Thunder Mine			Wyodak & Anderson Black Thunder Mine	
Sampling location ^a	V1067	R1235	V131B	V1067	R1235	V131B	V131B	
C, wt%	88.14	87.44	88.39	86.03	85.34	85.84	88.30	
H, wt%	6.53	6.59	6.57	6.75	6.59	6.77	5.61	
N, wt%	1.11	1.19	1.05	0.93	0.99	0.93	1.19	
S, wt%	1.54	1.57	1.05	1.94	1.74	1.73	1.74	
O, wt% (by diff)	2.68	3.21	2.94	4.35	5.34	4.73	3.16	
f _a ^b	30.4	29.4	29.2	24.3	26.0	25.9	38.9	

a) Sampling Location: V1067 = second stage product
R1235 = interstage
V131B = recycle

b) f_a = fraction of aromatic carbon

Table 2. Resid Conversion Data; 420°C, 30 min; tetralin/resid = 3/1

Resid	Conversion, wt%		Resid	Conversion, wt%	
	Thermal	Catalytic ^a		Thermal	Catalytic ^a
HRI ^b POC1 O-43	27.0	47.6	W261 V1067	19.4	42.7
HRI POC2 O-43	22.1	34.3	W261 R1235	16.0	35.3
W ^c 258 V131B	15.0	35.0	W261 V131B	17.1	32.9
W259 V1067	12.9	42.1	W262 V1067	17.7	37.4
W259 R1235	15.9	38.1	W262 R1235	19.6	32.1
W259 V131B	17.7	33.1	W262 V131B	18.2	35.8
W260 V1067	17.8	35.0	a. 3 wt% Mo b. W=Wilsonville pilot plant c. HRI = Hydrocarbon Technologies Inc		
W260 R1235	19.7	35.2			
W260 V131B	21.3	44.6			

Table 3. Some of the Coal Resid Molecular Attributes used in the Structural Model

- Paraffin Length
- Number of Naphthenic Rings
- Number of Sidechains
- Length of Sidechains
- Number of Aromatic Rings
- Number of Naphthenic Rings on an Aromatic Core
- Degree of Polymerization
- Fraction of Heteroatom Cores
- Fraction of Internal Naphthenics
- Fraction of Cores with Phenolic Groups
- Type of Intersheet Linkages

**Table 4. Reaction Rules for Resid Reactivity
(Reaction Carried out in H₂ with Hydrogenation Catalyst)**

- Paraffins crack at the middle of chains.
- Sidechains can crack at ring, alpha to ring, beta to ring, or at middle of chain.
- Sulfur can be removed from bridges and rings to form H₂S.
- Nitrogen can be removed from five-membered rings to form NH₃.
- Oxygen can be removed from bridges and rings to form H₂O.
- Methane can be removed from internal naphthenics.
- Methylene and biphenyl bridges can react.

Table 5. Experimental and Predicted Resid Conversion, wt%

Resid	Conversion, wt%		Difference (absolute)
	Experimental	Predicted	
HTI POC1 O-43	47.6	48.7	1.1
HTI POC2 O-43	34.3	32.8	1.5
W 258 V131B	35.0	37.3	2.3
W259 V1067	42.1	36.6	5.5
W259 R1235	38.1	40.2	2.1
W259 V131B	33.1	34.4	1.3
W260 V1067	35.0	36.9	1.9
W260 R1235	35.2	29.2	6.0
W260 V131B	44.6	36.8	7.8
W261 V1067	42.7	40.4	2.3
W261 R1235	35.3	35.3	0.0
W261 V131B	32.9	39.5	6.6
W262 V1067	37.4	39.8	2.4
W262 R1235	32.1	33.1	1.0
W262 V131B	35.8	38.9	3.1

APPENDIX 2

CHARACTERIZATION OF PROCESS SAMPLES FROM CO-LIQUEFACTION OF COAL AND WASTE POLYMERS

For presentation at the

DOE Coal Liquefaction and Solid Fuels Contractors Review Conference
Pittsburgh, PA

September 3-4, 1997

Note: Similar papers with the same authors (versions not presented here) were prepared for or presented at two other conferences. The paper, "Characterization of Process Stream Samples From Bench-Scale Co-Liquefaction Runs That Utilized Waste Polymers as Feedstocks" was presented at the 214th National Meeting of the American Chemical Society, September 7-11, 1997, in Las Vegas, Nevada. The paper, "Characterization of Process Oils from Coal/Waste Co-Liquefaction" was submitted for presentation at the 14th Japan/U.S. Joint Technical Meeting on Coal Liquefaction and Materials for Coal Liquefaction on October 28, 1997 in Tokyo, Japan.

Title: Characterization of Process Samples from Co-Liquefaction of Coal and Waste Polymers

Authors: Gary A. Robbins and Richard A. Winschel

grobbins@telerama.lm.com

Telephone 412-854-6748

Fax 412-854-6613

CONSOL Inc.

Research & Development

4000 Brownsville Road

Library, PA 15129-9566

INTRODUCTION

Since 1994, CONSOL has characterized feed, recycle, and product samples from DOE-sponsored co-liquefaction experiments with polymers and coal.¹⁻⁵ The objective is to understand the process chemistry and the fate of the polymer components in continuous unit runs. CONSOL used conventional liquefaction process stream characterization methods, supplemented by methods developed specifically for polymer components. In the earliest Hydrocarbon Technologies, Inc. (HTI) runs, virgin polymers were used to simulate municipal waste polymers. More recently, HTI began using authentic municipal solid waste polymers (Run CMSL-11⁶) and auto shredder residue (Run PB-04⁷) as co-liquefaction feedstocks in various combinations with coal, petroleum resid, and virgin polymers. Process stream samples were characterized from HTI runs in which these authentic waste polymers were liquefied with coal and petroleum resid. The conversion of relatively unreactive polyolefins was determined by an extraction procedure. The fate of polystyrene was determined by gas chromatography-mass spectrometry of net liquid products.

BRIEF DESCRIPTION OF PLANT AND CO-LIQUEFACTION RUNS

The co-liquefaction runs were performed in HTI's bench unit 227. Fresh feed materials (catalyst precursors, coal, waste feedstocks, petroleum resid, and/or virgin polymers) were mixed batchwise with process recycle materials in a tank and transferred to a feed slurry tank that continuously fed the slurry to the liquefaction process. The feed slurry was fed to a preheater that also conditioned the dispersed catalyst. Next, the slurry was fed to two successive stages of liquefaction. No supported catalysts were used in the liquefaction reactors; only disposable dispersed catalysts were used. A high-pressure separator after the first reactor allows light products to be taken off, and the hydrogen concentration to be increased in the second reactor. The first-stage oil, called the first-stage separator overhead oil, or SOH1, is sent with second-stage light oils and light distillate to an in-line fixed-bed hydrotreater. The in-line hydrotreater upgrades the product using the liquefaction reactor system off gases. The second stage of liquefaction is followed by high- and low-pressure separators. The separator overheads are fed to the in-line product hydrotreater, and the separator bottoms to distillation. The distillate (ca. IBP-371 °C) is sent to the product hydrotreater, and the resid is filtered to provide a liquid for recycle and solids to reject ash. Major streams analyzed typically included the feed slurry, individual fresh feeds, the unhydrotreated first-stage separator overhead (SOH1) oil, the separator bottoms (flashed liquefaction product), the filter liquid (recycle), filter cake (solids), and the hydrotreated net product oil.

Operating conditions for relevant portions of Runs CMSL-11⁶ and PB-04⁷ are shown in Table 1. In both runs, co-liquefaction operation was successfully demonstrated using the municipal or industrial waste feedstocks (municipal solid waste (MSW) plastics in Run CMSL-11, and automobile shredder residue (ASR) in Run PB-04). When MSW was fed with coal, Condition 3B of Run CMSL-11, H consumption and gas yield were reduced and distillate yield increased. In general, ASR was not as beneficial as MSW to liquefaction process performance. Operating difficulties were encountered throughout the ASR run. HTI observed that: 1) ASR caused repeated feed pump problems; 2) the resid conversion was lower when ASR was fed (relative to feeding coal only); and 3) ASR lowered the H consumption, distillate yield, and light gas yield. HTI speculated that polyurethane and (cross-linked) high impact polystyrene in the ASR were less reactive than polymers previously processed (including the MSW). It is important to determine the relative reactivity of the polymers that could be identified in the ASR.

Table 1. Conditions and Yields for HTI Runs PB-04 (227-95) and CMSL-11 (227-89)

Run	PB-04					CMSL-11	
Condition	1	2	3	4	5	2	3B
<u>Feed, wt % MF</u>							
Black Thunder Coal	100	-	50	75	50	100	75
Hondo resid	-	70	30	-	-	-	-
ASR (PB-04) or MSW (CMSL-11)	-	30	20	25	25	-	25
HDPE/PS (60:40)	-	-	-	-	25	-	-
Temp. Stage 1/Stage 2, °C	440/450					450/460	
Disp. Cat. Loading, mg/kg	Fe :1000, Mo:50, P:100					Fe:5000, Mo:100	
Yields, wt % MAF Fresh Feed							
C ₁ -C ₃ Gases	9.9	7.0	8.6	6.9	7.8	18.2	7.4
C ₄ -343 °C	46.0	44.4	48.3	31.2	40.3	49.4	39.5
343-524 °C	21.6	24.7	18.5	25.4	21.2	13.5	28.1
524 °C+	3.7	16.0	10.5	18.0	14.0	6.0	11.2
Unconverted Feed	6.8	3.6	6.0	9.6	8.8	4.9	5.3
H ₂ O+CO _x	18.6	5.0	11.6	15.2	12.1	14.5	13.6
NH ₃ +H ₂ S	0.6	4.2	2.3	-0.3	-0.8	0.4	-0.2
H ₂ Consumption	7.2	4.8	5.7	6.0	4.0	6.9	4.9
MAF Feed Conv., wt % (SO ₃ -Free)	93.2	96.4	94.1	90.5	91.3	95.1	94.7

DESCRIPTION OF CHARACTERIZATION METHODS

Three analytical techniques supplemented the normal liquefaction work-up procedures (which usually include distillation, tetrahydrofuran (THF) extraction, ashing, and determinations of phenolic -OH concentration and proton distribution). When polymers are present in co-liquefaction samples, hot decalin extraction, FTIR spectroscopy, and GC-MS characterization are the supplementary techniques. The decalin extraction and FTIR are used typically for resid- and solids-containing samples, and GC-MS is used typically for light net product oils. The hot decalin extraction method was described previously;⁵ it generates a solubles fraction, a “plastic” fraction, and an insolubles fraction from a liquefaction sample. The “plastic” fraction consists of polyolefins (primarily high-density polyethylene (HDPE) and polypropylene (PP)) that are soluble in hot decalin, but insoluble in THF or room-temperature decalin. The polymers are subsequently characterized by FTIR spectroscopy. The GC-MS total ion chromatograms and individual mass spectra are usually examined for information on n-paraffins from polyethylene and other feedstocks, and for marker compounds from polystyrene (PS) liquefaction. Various sample preparation techniques have been used at CONSOL for qualitative FTIR examination of polymeric materials. Unsupported and supported thin films and thin slices have been used for transmission IR measurements. Powder, or fine cuttings or filings have been mixed with KBr (1-10% polymer) for diffuse reflectance measurements.

CHARACTERISTICS OF PROCESS STREAMS SAMPLES

Table 2 is a summary of the overall characterization results of the various process streams analyzed, components found or expected, and methods used. Ash, polyethylene, polypropylene, and polystyrene were components of the MSW and ASR feedstocks that were directly or indirectly identified. PS was identified via marker PS-derived compounds found in product oils using GC-MS. Ash was determined directly on the MSW and indirectly on the ASR, using the ash content of the feed slurry. A polyolefin component was extracted from the feed slurry samples, and identified as HDPE and PP using FTIR spectroscopy. Spectroscopic features suggest the presence of low-density polyethylene (LDPE), or some unidentified polyethylene, in some samples. Based on combined results from several of these methods, overall composition of the MSW feed is approximately 96% HDPE+PP, 2% PS, and 1.6% ash. Using the same procedure, the estimated composition of the ASR feed was 68% HDPE+PP, 12% PS, and 20% ash (as reported by HTI⁷).

Table 2. Components Found in Process Stream Samples From Co-Liquefaction of Waste Polymers With Coal

Stream Sample from Process	Component						Methods
	HDPE	PP	LDPE or Other PE	PS	Ash	Other Polymers	
Feed MSW	X	X		I	X	E	DE, FTIR
Feed ASR	I	I		I	X	E	
MSW Feed Slurry	X	X		I	X	E	DE, FTIR
ASR Feed Slurry	X	X	S	I	X	E	DE, FTIR
Separator Bottoms	X	C*			X		DE, FTIR
Filter Liquid	X	C*	S*				DE, FTIR
Filter Solids	X	C*	S*		X		DE, FTIR
First Stage Oil*	P	E		P			GC-MS
Product Oil	P	E		P			GC-MS
Legend: X = Direct evidence I = Indirect evidence P = Evidence for a product E = Expected, but not identified S = Suspected, i.d. uncertain C = Contrary evidence (i.e., that it is not present) DE = Hot decalin extraction							

* Applies to Run PB-04 samples only.

FATE OF HDPE AND PP

Previous work demonstrated that polyolefins, primarily HDPE and PP, could be extracted from co-liquefaction stream samples. The amount of this material rejected from the process represents the amount that is not converted to liquid products. FTIR spectroscopy (Figure 1) was used to identify PP and HDPE in polyolefin material extracted from feed slurries from Run PB-04. These results indicate that PP was a significant component of the feed ASR. The material extracted from the pressure-filter cake stream that is used to reject solids from the process consists entirely of polyethylene (Figure 1, apparently HDPE). This indicates that the PP is more reactive than the HDPE at reaction conditions.

Table 3 presents the ash-balanced, overall conversions of the total MAF feed, the total MAF waste/polymer feed, and the decalin-extracted polyolefins. The overall conversion is calculated from the compositions and flow rates of the net product and fresh feeds. However, decalin-extracted polyolefins were determined on the (Run PB-04) feed slurry samples, since no ASR sample was available. The recycled ash and polyolefins contributions were backed out to determine the relative concentrations of fresh polyolefins and ash. In turn, this allowed the percentage polyolefins in the ASR to be estimated at 79-90% MAF, or 63-72% (average of 68%) MF.

The CONSOL MAF fresh feed conversion is compared with HTI results in Table 3 to demonstrate that the ash balance technique typically gives conversions very similar to those of HTI. The exception in these data are the results for Conditions 4 and 5, for which the CONSOL conversions were ~3-5% lower than those obtained by HTI, possibly due to the difference between the solvents used. CONSOL used THF to define conversion (THF does not dissolve the unconverted polyolefins). HTI used hot quinoline to define conversion (hot quinoline does dissolve the unconverted polyolefins). The same ash balance method was used to calculate conversions of the total wastes and the decalin-extracted polyolefins.

Figure 1. FTIR Spectra of Decalin-Extracts From Feed Slurry and Filter Cake Produced in Condition 5 of HTI Run PB-04.

The results indicate high conversion of the total waste/polymer stream and of the polyolefins, ~95-99%. The conversions of these components were typically about 5% higher than HTI's conversions of the total fresh feed. The lower conversions observed by CONSOL for the total waste/polymer component and for the decalin-extracted polyolefins corresponded to Conditions 4 and 5 of Run PB-04, in which HTI also observed the lowest fresh feed conversions. Recycle of unconverted polyolefins (apparently chiefly HDPE) is required to achieve these high conversions. Evidently, conditions used in Conditions 4 and 5 of Run PB-04 were not optimal to convert all of the ASR or polyolefin component of the ASR. In Run CMSL-11, HTI used higher reactor temperatures, higher Mo and Fe catalyst concentrations (and different catalyst precursors) to achieve high conversion of the MSW polymers.

FATE OF PS

Earlier work with samples from Runs POC-2, CMSL-8, and CMSL-9, in which virgin polystyrene was a feedstock, indicated that ~70% of the PS fed could be identified as components (toluene, ethylbenzene, and cumene) in the unhydrotreated product oil and ~50% in the hydrotreated product oil.¹⁴ Cumene alone accounted for ~16% of the PS fed in the unhydrotreated product oil, and ~10% in the hydrotreated product oil. Cumene is a good marker for PS-derived products, because it is found in product oil samples from co-liquefaction with PS as a feed component. In the unhydrotreated first-stage product oils from Run PB-04, 1,3-dimethyl propane was also identified as a unique PS marker. However, this compound seems to be clearly identifiable and quantifiable primarily when the product oil is unhydrotreated. The components used for identification and quantification by CONSOL contain aromatic rings, because these components are readily identified by their mass spectra using automated searches of spectral databases.

Concentrations of four PS-derived compounds identified by GC-MS in the SOH1 samples from Run PB-04 and in the Run CMSL-11 product oil from Condition 3B are shown in Table 4. The presence of cumene in products from liquefaction of MSW in Run CMSL-11 and ASR in Run PB-04 demonstrates the presence of PS as a feed component. The ASR and MSW feed materials are very heterogeneous and are difficult to characterize directly to quantify individual polymer components. Based on earlier work with virgin plastics, the amount of PS in the waste feedstocks can be estimated for Runs CMSL-11 and PB-04. If the same degree of conversion takes place, and the yield of the product oils are known or estimated, it is estimated that PS constitutes about 2 wt % of the MF feed MSW in Condition 3B of Run CMSL-11. Similarly, it is estimated that PS constitutes about 12 wt % of the MF feed ASR in Conditions 3 and 4 of Run PB-04.

Table 3. Overall conversion of Feed and Polymer Feed Components in HTI Runs PB-04 and CMSL-11

Source	Overall Conversion, %					
	PB-04 Cond. 1	PB-04 Cond. 2	PB-04 Cond. 3	PB-04 Cond. 4	PB-04 Cond. 5	CMSL-11 Cond. 3B
Basis: MAF Fresh Feed, Ash-Balanced						
CONSOL	93.7	95.0	95.7	87.1	85.5	94.3
HTI(a)	93.2	96.4	94.1	90.5	91.3	94.7
Basis: MAF Fresh Waste/Polymer, Ash-Balanced						
CONSOL	NA	99.9(b)	99.4(b)	95.8(b)	96.8(b)	99.1(c)
Basis: Fresh Decalin-Extractable Polyolefins in Feed, Ash-Balanced						
CONSOL	NA	NA	99.3(c,d)	95.4(c,d)	NA	NA

(a) SO₃-free ash basis

(b) % MAF ASR in feed (+ virgin polymers in feed in Condition 5)

(c) % Decalin-extracted polyolefin in feed (d) Back-calculation from Condition 3 results indicates that the feed ASR contains 79% MAF decalin-extracted polyolefin (63% on MF basis). From Condition 4 results, the feed ASR contains 90% MAF decalin-extracted polyolefin (72% on MF basis).

The four marker compounds (Table 4, Figure 2) constituted about 11-42% of the SOH1 samples in Conditions 3-5 of Run PB-04. In contrast, the Condition 1 (coal-only) SOH1 contained only 2% of three of these markers (1,3 diphenyl propane was not present). In general, these marker compounds seem to represent the lowest-boiling primary fragments of PS liquefaction, as shown in Figure 1. Benzene, methane, and ethane could also be primary products, but they also are produced from coal. Hydrotreating these components may cause cracking or ring hydrogenation. Any products that elute before toluene, or do not contain an aromatic ring, are less-readily identified or quantified because they are not unique to PS liquefaction.

The observed distributions of these four components on relative weight percent and mol percent bases are given in Table 4. An uneven distribution of alkyl vs. phenyl groups in the products (ethylbenzene has the proper distribution) would imply that these products are accompanied by the production of some (unobserved) combination of methane, ethane, benzene, and cyclohexane (in the simplest possible molecules). The observed distribution indicates that 3.2 mol % benzene + 3.2 mol % methane would account for the imbalance (i.e., there is more cumene than toluene plus 1,3-diphenylpropane). Although the data may not support a rigorous analysis like this, qualitatively the results suggest that the production of light gases such as methane and ethane from liquefaction of polystyrene is minor. These estimates leave about 20% of the PS as unaccounted. In addition to benzene, the unaccounted portion could be cyclic alkyls that are hydrogenation products and not readily identified.

Figure 2. PS Liquefaction Products Found in Net Product Oils.

Table 4. PS Liquefaction Products Found in Run PB-04 First-Stage Oils

Component	Toluene	Ethylbenzene	Cumene	1,3-Diphenyl propane	Sum
Conc. in SOH1, wt %					
Condition 1	0.3	1.7	0.2	0.0	2.2
Condition 3	1.3	7.5	1.9	0.2	10.8
Condition 4	4.0	15.8	5.1	0.6	25.5
Condition 5	4.4	26.8	9.4	1.0	41.6
Conc. in SOH1 as wt % of ASR fed, adjusted to eliminate coal contribution					
Condition 3	1.4	8.0	2.1	0.2	11.7
Condition 4	1.1	4.2	1.6	0.2	7.1
Condition 5	3.0	18.2	6.6	0.7	28.5
Avg. Relative Distribution					
wt %	12.6 ±2.7	63.7 ±4.9	21.4 ±2.8	2.4 ±0.5	100.0
mol%	14.7	64.8	19.2	1.3	100.0
C Balance	+1CH ₂	0	-1CH ₂	+1CH ₂	
Net C Balance	-3.2 mol% CH ₂ , or +3.2 mol% (benzene +CH ₂)				

CONCLUSIONS AND FUTURE NEEDS

These results show that several components of authentic waste polymers can be identified and sometimes quantified in co-liquefaction process stream samples. Different characterization strategies are needed to accommodate different polymers. PS and PP appear to be reactive, and there is no hint that the ASR contains an unreactive PS component, as was speculated based on Run PB-04. HDPE is less reactive and requires a substantial recycle rate to convert it. Ultimately, nearly all of the HDPE is converted. Marker compounds that appear to be primary PS products were observed in the light product range. The distribution of these light PS products suggests that little gas production is associated with PS liquefaction.

It is desirable to develop methods for speciation of more polymers (e.g., polyurethane). Quantitative FTIR methods would allow the determination of relative or absolute amounts of PP and HDPE present. Other information, such as molecular weight distributions, would be informative; however, their expense usually cannot be justified for a large number of process samples.

ACKNOWLEDGMENTS

This work was supported by the U.S. Dept. of Energy under Contract No. DE-AC22-94PC93054. Samples and background information were supplied by Dr. V. Pradhan and Dr. J. Hu of HTI.

REFERENCES

1. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P., DOE/PC 93054-10, May 1995.
2. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P., DOE/PC 93054-18, September 1995.
3. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P., DOE/PC 93054-25, May 1996.
4. Robbins, G. A.; Brandes, S. D.; Winschel, R. A., DOE/PC 93054-34, March 1997.
5. Robbins, G. A.; Winschel, R. A.; Burke, F. P., Prepr. ACS Div. Fuel Chem. 1996, 41 (3), 1069.
6. Draft internal HTI report on Run CMSL-11.
7. Comolli, A. G.; Pradhan, V. R.; Lee, T. L. K.; Karolkiewicz, W. F.; Popper, G., Final Topical Report, Bench Run 4, DE-92148-TOP-6, March 1997.

APPENDIX 3

CHARACTERIZATION OF LIQUID PRODUCTS FROM ALL-SLURRY-MODE DIRECT LIQUEFACTION

For presentation at the

1997 DOE Coal Liquefaction and Solid Fuels Contractors Review Conference
Pittsburgh, PA

September 3-4, 1997

Title: **Characterization of Liquid Products from All-Slurry-Mode Direct Liquefaction**

Authors: Peizheng Zhou*, Rameshwar D. Srivastava, and R. A. Winschel**

Burns and Roe Services Corporation
Federal Energy Technology Center
Pittsburgh, PA 15236
Telephone: 412-892-4473; Fax 412-892-4604

**CONSOL Inc., Research & Development
4000 Brownsville Road
Library, PA 15129-9566
Telephone: 412-854-6683; Fax: 412-854-6613

*Currently with Hydrocarbon Technologies, Inc.

BACKGROUND

The state-of-the-art coal liquefaction technology in the U.S. can now produce, at historically low costs, premium distillate products that can be co-refined with petroleum in existing refineries. The value of modern direct liquefaction liquid products can be determined using refinery linear programming (LP) models, such as the Process Industry Modeling System (PIMS) developed by Bechtel Corporation. To perform refinery LP studies, crude assay data of coal liquids are needed. Supported by the U.S. Department of Energy (U.S. DOE) Federal Energy Technology Center (FETC), CONSOL Inc., and Burns and Roe Services Corporation have coordinated the characterization of nine representative direct coal liquefaction products generated from Wilsonville operation and Hydrocarbon Technologies, Inc. (HTI) facilities.

Two all-slurry-mode coal liquefaction liquid products were recently analyzed by Inchcape Testing Services (ITS).¹ The coal liquid samples were collected from HTI's Run PB-03, a continuous bench-scale operation with Black Thunder mine subbituminous coal as feed and dispersed catalysts in both reactor stages. One sample, designated as PB3a, was produced while a fixed-bed, in-line hydrotreater unit (HTU) was on-stream and the other, PB3b, was generated while the HTU was by-passed. This is the first time that all-slurry-mode liquefaction products were analyzed using ASTM procedures and methods and the first time that the effect of the HTU on product quality could be determined.

This paper summarizes the two coal liquid assays on the all-slurry-mode PB-03 coal liquids and compares them with an assay conducted by Conoco Inc.² on an ebullated-bed reactor product collected from HTI's Run POC-2 (a Proof-of-Concept operation also using Black Thunder Mine coal and employing an HTU). The comparison provides information on the effect of catalyst types and reactor configurations. Operating conditions of Runs PB-03 and POC-2 from which samples were collected are listed in Table 1.

DISTILLATION AND YIELD STRUCTURE (MILD HYDROCRACKING IN HTU)

Figure 1 is the simulated true-boiling-point (TBP) curves of coal liquids PB3a and b, with POC-2 for comparison. Clearly, PB3a, which was processed in the in-line hydrotreater, is much lighter than PB3b, which did not pass through the HTU. A comparison of the yield structure of the two liquids follows:

	PB3a	PB3b
IBP, °C	42.3	69.7
Yield, vol %		
Light naphtha (IBP-82 °C)	5.3	2.0
Medium naphtha (82-177 °C)	32.7	22.7
Heavy naphtha (177-204 °C)	10.7	9.3
Light distillate (204-288 °C)	29.7	33.7
Heavy distillate (288-350 °C)	16.5	19.8
EP, °C	420.9	485.5

The in-line hydrotreatment decreased the initial boiling point (IBP) and end point (EP) of the coal liquid by 28 and 65 °C, respectively, and increased the yields of light, medium, and heavy naphthas by 3.3, 10, and 1.4 vol % (absolute), respectively. The total yield of <350 °C fractions increased by 7.3 vol % (abs.). In addition to its highly efficient hydrogenation activity, which is discussed in the following sections, the in-line hydrotreater also performed mild hydrocracking; it converted approximately 20 vol % of the >204 °C material into naphtha range products.

Figure 1 also shows that the distillation curve of the POC-2 coal liquid (also produced with Black Thunder coal and an in-line HTU, but with two-stage ebullated-bed reactors) is close to that of the PB3a liquid; demonstrating the similarity in vaporization characteristics of coal liquids produced via two-stage liquefaction with in-line hydrotreating.

PROPERTIES OF PB-03 LIQUID PRODUCTS

For the sake of simplification, only the primary properties of the PB3a and PB3b liquids are tabulated (Tables 2 and 3). Additional data on these liquids and on the POC-2 liquid ² are available elsewhere.

The specific gravities of various fractions of the three coal liquids are plotted against the TBP mid-boiling points (T50) of their fractions in Figure 2. The figure shows that the hydrotreated PB3a fractions have lower specific gravities than the corresponding untreated PB3b fractions, due to hydrogen enrichment that occurred during hydrotreating. Figure 2 also shows that the specific gravities of PB3a and POC-2 fractions are almost coincident; both of them were produced using an in-line hydrotreater. Properties of the POC-2 coal liquid, reported elsewhere, ² are very close to those of PB3a. Different reactor and catalyst types were used for Runs PB-03 (slurry-bed and Fe/Mo lyvan A) and POC-2 (ebullated-bed and Akzo AO-60); however, the in-line hydrotreater apparently eliminated the effects of differences between reactor and catalyst types in these two runs.

The PB3a total liquid, which was hydrotreated in the HTU, has a higher hydrogen content (12.9 wt %) than the PB3b liquid (11 wt %), which was not hydrotreated. The in-line hydrotreater effectively enriched the liquid product with about 2 wt % of additional hydrogen. The POC-2 coal liquid contains 13.1 wt % of hydrogen, which is close to that of PB3a.

The in-line hydrotreating also reduced dramatically the heteroatom contents of the coal liquid, from 3100 mg/kg sulfur and 6716 mg/kg nitrogen in the untreated PB3b to 600 mg/kg sulfur and 42 mg/kg nitrogen in the hydrotreated coal liquid PB3a. The POC-2 coal liquid contains less sulfur (80 mg/kg) and a similar amount of nitrogen (60 mg/kg). These coal liquids, obtained from a state-of-the-art direct liquefaction process, have an excellent quality.

HYDROGENATION FUNCTION OF THE IN-LINE HYDROTREATER

A closer look at the compositions of the various fractions of these two coal liquid samples reveals clearly that the in-line hydrotreater was very efficient in hydrodesulfurization (HDS) and hydrodenitrogenation (HDN). The HDS efficiency on various fractions is in the range of 82-95%, and the HDN efficiency is

99% consistently. The hydrodeoxygenation (HDO) is close to complete. Unsaturated hydrocarbons were effectively saturated during hydrotreating. Figure 3 shows that cycloalkanes were greatly increased, and Figure 4 indicated that aromatics were dramatically reduced in the coal liquid fractions, in accordance with the increase in cycloalkanes. Aromatic hydrocarbons were hydrogenated in the range of 41 to 62%, while olefins were saturated from 74 to 99% for the naphtha fractions. There is an increase, seemingly, in the olefin content of the distillates after hydrotreating. The olefin analysis for heavier fractions, however, is subject to great uncertainty. These results are summarized in Table 4.

The very efficient hydrotreating made the PB3a coal liquid fairly rich in hydrogen and very low in heteroatoms. The in-line hydrotreater removed 80% of the sulfur and 99% of nitrogen and saturated most of the olefins and a substantial part of the aromatics. The PB3a liquid is, therefore, low in aromatics; its gasoline fraction (IBP-177 °C) contains only 6.5 vol % of aromatics and its diesel fuel fraction (177-288 °C) contains 32.7 vol % of aromatics. Mild hydrocracking made the coal liquid rich in light materials, mostly in the gasoline boiling range. This is in dramatic contrast with the common perception that coal liquids are highly aromatic, heavy, and viscous.

Overall, the properties of the PB3a coal liquid are similar to those of the POC-2 coal liquid. The lower sulfur content (60 wppm) in the latter may be attributed to the use of supported catalyst in Run POC-2.

CONCLUSIONS

The in-line hydrotreater is highly effective in removing heteroatoms, saturating olefins and aromatics, and boosting gasoline yield in modern direct coal liquefaction. The hydrotreater enriched the coal liquid with 2% hydrogen and provided a mild hydrocracking function, converting a significant amount of the heavier materials into light fractions, mostly in the gasoline range. As a result, the coal liquefaction product that has been processed in the HTU is rich in hydrogen and very low in heteroatoms and aromatics. The hydrotreated coal liquid has a high gasoline yield (38 vol %), which contains very low levels of aromatics (6.5 vol %) and heteroatoms (less than 300 mg/kg sulfur).

The properties of PB3a coal liquid are close to those of the POC-2 coal liquid, which was produced in ebullated-bed reactors with a supported catalyst. The highly effective hydrotreating and mild hydrocracking effects of the in-line hydrotreater eliminated, to a large extent, the effects of differences in reactor and catalyst types. The use of a supported catalyst in Run POC-2 may contribute to the lower sulfur level.

ACKNOWLEDGMENT

This work is supported by the U.S. Department of Energy FETC under contract numbers DE-AC22-94PC93054 and DE-AC22-94PC92100.

REFERENCES

1. Kelly, R. "Crude Assay on HTI PB-03-6,7,8 Received in September 1996" and "Crude Assay on HTI PB-03-9,10,11. Received in September 1996" in DOE/PC 93054-41 "A Characterization and Evaluation of Coal Liquefaction Process Streams, Quarterly Technical Progress Report, June - September, 1996" by G. A. Robbins, S. D. Brandes, and R. A. Winschel, to be issued.
2. Cabiness, D. "Light Oil Assay of C95029, Syn Products of CONSOL" in DOE/PC 93054-20, "A Characterization and Evaluation of Coal Liquefaction Process Streams, Quarterly Technical Progress Report, June - September, 1995" by G. A. Robbins, S. D. Brandes, R. A. Winschel, and F. P. Burke, December 1995.

Table 1. Operating Conditions for Coal Liquid Samples

Run	Process Conditions*
PB-03 (sample a)	Catalytic/Catalytic Slurry HTI-Fe/Molyvan A 441 °C/449 °C Criterion C-411/379 °C Distillate Yield 57 wt % MAF coal
PB-03 (sample b)	Catalytic/Catalytic Slurry HTI-Fe/Molyvan A 442 °C/451 °C HTU bypassed Distillate Yield 55 wt % MAF coal
POC-2	Catalytic/Catalytic Ebullated Akzo AO-60 407-414 °C/426-440 °C Criterion C-411/357-382 °C Distillate Yield 62-66 wt % MAF coal

*First-stage/second-stage reactor type

Liquefaction catalyst

First-stage/second-stage reactor temperature

HTU catalyst/temperature

Distillate yield

Table 2. Properties of PB3a Coal Liquid^d

Fractions, °C	Total Liquid	IBP-21	21-82	82-177	177-204	204-288	288-343	343+
API Gravity	38.0	111.3	65.7	49.8	36.2	27.5	20.9	21.4
Sp. Gr. @15.6 °C	0.8347	0.5830	0.7175	0.7804	0.8437	0.8898	0.9285	0.9254
<u>Elemental, wt %</u>								
Carbon	84.57		84.48	85.92	86.38	87.79	88.65	87.69
Hydrogen	12.92		15.51	14.44	13.17	12.14	12.19	12.29
Sulfur	0.06		<0.01	0.03	0.03	0.02	0.02	0.61
Nitrogen	0.0042		0.0036	0.0023	0.0056	0.0032	0.0019	0.0079
Oxygen (diff)	2.45		0.01	-0.39	0.41	0.05	-0.86	-0.60
<u>Viscosity, cSt</u>								
@ -20 °C					3.832	12.65		
@ 100 °C					0.569	0.952	1.938	3.791
Freezing Pt., °C	-3.9				-60.0	-42		
Smoke Pt., mm					18	11		
<u>HC Group, vol %</u>								
Paraffins		98.7	42.98	18.56	13.13	11.52	20.89	
Olefins		0.6	0.33	<0.01	2.40	13.50	23.10	
Naphthenes		0.7	52.54	74.10	60.58	39.10	8.26	
Aromatics		0.0	1.15	7.34	23.89	35.88	47.75	
Benzene			1.03					
Naphthalenes					0.36	5.11		
<u>Thermal Stability (D3241)</u>								
Tube Rating					4.0	>4.0		
Pressure Drop, mmHg					>125	>125		
Oxid. Stability, min			>240	>240	>240			
RON		106	76.1	60.2	54.7			
MON			73.6	58.0	52.1			
Cetane Number					30	32	35	
Net Heat Comb., kJ/kg					42516	41632		

Table 3. Properties of PB3b Coal Liquid¹

Fractions, °C	Total Liquid	IBP-21	21-82	82-177	177-204	204-288	288-343	343+
API Gravity	24.1	111.3	65.7	43.7	21.2	16.8	12.9	6.4
Sp. Gr. @15.6 °C	0.9091	0.5830	0.7175	0.8076	0.9268	0.9540	0.9800	1.0261
<u>Elemental, wt %</u>								
Carbon	83.53		84.39	80.45	81.77	83.85	88.72	88.13
Hydrogen	10.99		15.35	12.74	10.54	10.15	10.58	9.44
Sulfur	0.31		0.19	0.21	0.17	0.12	0.25	0.62
Nitrogen	0.6716		0.3542	0.2005	0.5897	0.8159	0.7197	0.8584
Oxygen (diff)	4.50		-0.28	6.40	6.93	5.06	-0.27	0.95
<u>Viscosity, cSt</u>								
@ -20°C					12.42	73.47		
@ 100°C					0.750	1.199	7.456	7.456
Freezing Pt. °C	too dark				-49	-28		
n-C ₇ Ins., wt %	0.09							
Smoke Pt., mm					13	9		
<u>HC Group, vol %</u>								
Paraffins		90.7	42.20	22.15	21.46	13.95	15.57	
Olefins		7.1	7.23	5.01	9.20	4.40	4.40	
Naphthenes		1.9	47.51	55.26	11.83	20.97	5.59	
Aromatics		0.02	3.06	17.58	57.51	60.68	74.44	
Benzene			2.55					
Naphthalenes					6.34	14.92		
<u>Ther. Stability (D3241)</u>								
Tube Rating					4.0	4.0		
Pressure Drop, mmHg					>125	<1.0		
Oxid. Stability, min			>240	>240	>240			
RON		107	75.7	65.6	107			
MON			72.2	66.5	91.2			
Cetane Number					<18.3	<18.3	<18.3	
Net Heat Comb., kJ/kg					42145	42219		

Table 4. Hydrogenation Efficiency of the In-Line Hydrotreater

Fraction	% H Increase, absolute	% HDS	% HDN	%HDO	% Olefin Saturation	% Aromatics Saturation
Light Naphtha	0.16	95	99	*	95	62
Medium Naphtha	1.7	86	99	*	99	58
Heavy Naphtha	2.6	82	99	94	74	58
Light Distillate	2.0	83	99	99	**	41
Heavy Distillate	1.6	92	99	*	**	36
Atm. Resid	2.9	2	99	*	n.d.	n.d.

*Negative oxygen by difference prevents calculation

**Higher concentration of olefins determined in hydrotreated product fraction

n.d = not determined

Figure 1. Simulated Distillation Curves of PB3a, PB3b, and POC-2 Coal Liquids.

Figure 2. Specific Gravity of PB3a, PB3b, and POC-2 Coal Liquid Fractions.

Figure 3. Distribution of Saturated Hydrocarbons in Coal Liquids.

Figure 4. Distribution of Aromatics and Olefins in Coal Liquids.