SANDIA REPORT

SAND96-1185 • UC-802

Unlimited Release

Printed April 1996

Development of Green Box Sensor Module Technologies for Rail Applications

Dan Rey, Roger Breeding, Jim Hogan, Jim Mitchell, R. Gordon McKeen, Jim Brogan

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550
for the United States Department of Energy
under Contract DE-AC04-94AL85000

Approved for public release; distribution is unlimited.

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
Office of Scientific and Technical Information
PO Box 62
Oak Ridge, TN 37831

Prices available from (615) 576-8401, FTS 626-8401

Available to the public from
National Technical Information Service
US Department of Commerce
5285 Port Royal Rd
Springfield, VA 22161

NTIS price codes
Printed copy: A04
Microfiche copy: A01

Development of Green Box Sensor Module Technologies for Rail Applications

Dan Rey
Instrumentation Development Department

Roger Breeding
Assessment Technologies Department

Sandia National Laboratories
Albuquerque, NM 87185

Jim Hogan and Jim Mitchell
Advanced Systems Engineering
Sandia National Laboratories
Livermore, CA 94551

R. Gordon McKeen, P.E.
New Mexico Engineering Research Institute
Albuquerque, NM 87131

Jim Brogan
University of New Mexico
Albuquerque, NM 87131

Abstract

Results of a joint Sandia National Laboratories, University of New Mexico, and New Mexico Engineering Research Institute project to investigate an architecture implementing real-time monitoring and tracking technologies in the railroad industry is presented. The work, supported by the New Mexico State Transportation Authority, examines a family of smart sensor products that can be tailored to the specific needs of the user. The concept uses a strap-on sensor package, designed as a value-added component, integrated into existing industry systems and standards. Advances in sensor microelectronics and digital signal processing permit us to produce a class of smart sensors that interpret raw data and transmit inferred information. As applied to freight trains, the sensors' primary purpose is to minimize operating costs by decreasing losses due to theft, and by reducing the number, severity, and consequence of hazardous materials incidents. The system would be capable of numerous activities including: monitoring cargo integrity, controlling system braking and vehicle acceleration, recognizing component failure conditions, and logging sensor data. A cost-benefit analysis examines the loss of revenue resulting from theft, hazardous materials incidents, and accidents. Customer survey data are combined with the cost benefit analysis and used to guide the product requirements definition for a series of specific applications. A common electrical architecture is developed to support the product line and permit rapid product realization. Results of a concept validation, which used commercial hardware and was conducted on a revenue-generating train, are also reported.

Acknowledgments

The project team thanks the New Mexico State Transportation Authority for providing the support and funding for this project. Thanks to Delta Group Inc., Albuquerque, NM, for providing the private industry viewpoint and performing a manufacturing study of the Green Box technologies. Thanks also to David Albright, President, Alliance for Transportation Research; Joseph Stever, Vice President, Amtech Systems Corporation; and Chuck Gibbon, Manager, Sandia National Laboratories, for their support in planning and initiating this technology transfer project.

CONTENTS

1. Introduction	1
2. Roles and Responsibilities	3
3. Concept of Operation	5
3.1 Theft and Vandalism Alarm Operations	6
3.2 Hazmat Alarm Operations	6
3.3 Preventive Maintenance Operations	7
4. Cost-Benefit Analysis of Using the Green Box in the Railroad Industry	9
4.1 Benefit of Equipping All Freight Cars	9
4.2 Costs Averted if All Railcars are Equipped	13
4.3 Benefit of Equipping Only Hazmat Tank Cars	14
4.4 Costs Averted if Only Hazmat Railcars are Equipped	16
4.5 Benefit of Equipping Only Railcars with High-Value Cargo	17
5. System Design and Validation	19
6. Circuit Implementation	23
6.1 Sensor Inputs	23
6.2 GPS Receiver Interface	24
6.3 Communications Interface	24
6.4 Power Supply	25
7. Product Realization	27
7.1 Manufacturing Costs	27
8. Market Potential	31
9. Conclusion	33
10. References	35
Appendix A: Statement of Work	37
Appendix B: Supplemental Hazardous Materials Shipment Information: Rail Incidents	41
Appendix C: Green Box Circuit Schematic	45
Appendix D: Manufacturing Study	49

Figures

1. Green Box Concept Functional Block Diagram	2
2. Concept of Operations	5
3. Proof-of-Concept Hardware	22
4. Green Box Reconfigurable Product Line	32

Tables

1. Summary of Train Accidents by Cause (1994)	9
2. Summary of Train Accidents Resulting from Car and Locomotive Equipment Failures by Cause (1994)	11
3. Summary of Train Accidents Resulting from Car Air Brake and Axle and Journal Bearing Failures by Cause (1994)	11
4. Summary of Train Accidents by Type (1989 - 1994)	12
5. Summary of Train Accidents Caused by Car and Locomotive Equipment Failures (1989 - 1994)	13
6. Summary of Accidents Involving Trains with Cars Containing Hazardous Materials by Type (1994)	15
7. Sensor Input Connector Pin Definitions	24
8. List of Costs for Producing the Green Box in Quantities of 1000	28
9. Range of Prices for Possible Green Box Sensors	30

Development of Green Box Sensor Module Technologies for Rail Applications

1. Introduction

Pursuant to DOE's 1993 Technology Transfer Initiative, representatives of Sandia National Laboratories and the Association of American Railroads (AAR) met to discuss potential technology transfer to the rail industry. Several areas were identified including a train-mounted sensor system, which later became known as the Green Box. The Green Box was believed to be an application that could have immediate impact, especially for the security of cargo. Among the attractive features of the Green Box was its potential for integration into the Automated Train Control System (ATCS) currently being developed by the AAR in cooperation with railroad companies.

In April 1995, the New Mexico State Transportation Authority (STA) established this project to help develop a real-time monitoring and notification product for railroads in North America. This technology transfer project was also established to assess the commercialization potential of electronic modules mounted on railcars to reduce operational costs by: (1) reporting in real time, events crucial to the safety and security of railcars or cargo, (2) alarming cars to reduce loss of revenue due to theft or vandalism, and (3) monitoring cargo to mitigate threats to public safety associated with incidents involving hazardous materials.

The concept consists of sensors which, under normal operating conditions, communicate to the railroad dispatchers via wayside reader stations or through the train's voice/data radio. In an emergency, the module will transmit a distress message identifying the location of the event, a description of the cargo, and condition of the vehicle/container. To test the concept, a cellular phone was used to provide the data transmission function. Figure 1 is a block diagram of the Green Box concept.

Figure 1. Green Box Concept Functional Block Diagram.

Based on preliminary information gathered for the cost-benefit analysis activities, a system architecture that accommodates three different applications was developed. The three applications, in the order of implementation, are security of cargo, safety of hazardous materials cargo, and a monitor of safety critical railcar components. For the initial application, only those cars with “valuable” cargo would use the hardware. This lowers the cost of implementation since only selected cars are equipped and inter-car communications are not needed. As more cars are equipped with the hardware, accident prevention and maintenance scheduling applications become feasible.

2. Roles and Responsibilities

The purpose of this project was to determine the feasibility of applying smart sensor technology to enhance rail transportation. The team members were assembled from the University of New Mexico (UNM), Sandia National Laboratories, and Delta Group Inc. Project management was provided by UNM's New Mexico Engineering Research Institute (NMERI). The project was divided into two tasks: user requirements identification and cost-benefit analysis (see Appendix A). Team composition and individual responsibilities are listed below.

Gordon McKeen	UNM/NMERI	Project manager
Jim Brogan	UNM	Cost benefit analysis
Roger Breeding	Sandia Labs	Cost benefit analysis
Jim Hogan	Sandia Labs	Systems design
Jim Mitchell	Sandia Labs	Software design
Dan Rey	Sandia Labs	Circuit design
Dominic Isbell	Delta Group	Manufacturing engineering

Requirements identification was broken down into several subtasks: develop preliminary conceptual design, determine specific requirements decisions, develop customer wants questionnaire, survey customers and stakeholders, analyze results of survey and draw conclusions, develop final design, determine costs of the design, and (with private industry participation) write design specifications.

The benefit analysis subtasks were as follows: determine sources of railroad loss data, acquire railroad loss data bases, extract information from railroad loss data bases and analyze it, determine costs of losses the Green Box can mitigate or prevent, summarize benefits for the Green Box design, compare benefits to costs, and draw conclusions.

The proposed work was to be completed in 18 months.

Intentionally Left Blank

3. Concept of Operation

The Green Box concept can address a variety of applications (see Figure 2). Based on a preliminary cost-benefit analysis, we focused on applications that would not require a Green Box module on every car in the train. This approach would reduce the cost of implementing a Green Box system by limiting stand-alone modules to cars carrying “valuable” cargo and eliminating the need for inter-car communication.

Three applications are considered: (1) Because of the high losses incurred by theft and vandalism, the security application is attractive. (2) A module designed to monitor the integrity of hazmat cargo shipped by rail also has appeal; however, it is a slightly more expensive proposition. Hazmat modules could be attached to individual cars and state-of-health information reported. (3) The Green Box used as a monitor of safety-critical equipment is less attractive because it would require a module be attached to every car. Modules could not be limited to selected cars since breakdowns on any car in the train could lead to an accident. Some form of inter-car communication would be required.

Figure 2. Concept of Operations.

3.1 Theft and Vandalism Alarm Operations

In this application, the Green Box would monitor high-value cargo transported by rail and send an alarm if someone attempts to steal or damage the protected items. The system would consist of two parts: a railcar-mounted sensor module and a central workstation to display the status of multiple modules. A personal computer or workstation, located at the company headquarters or railroad dispatcher's office, would receive messages via modem, process the information, and sound the alarm as appropriate. A small sensor module would be mounted on the railcars or attached directly to the cargo containers. The modules would contain a power supply, transceiver, processor unit, global positioning system (GPS) receiver (optional), and intrusion sensors: door switches, area sensors (IR, RF), etc. The sensor module would be operational from point of origin to the delivery point and could be activated and deactivated by unique code control over the communications link or directly through an I/O connector. The processor unit would poll the sensors and report any changes via the communications channel. Conflicts in sensor readings would be resolved by the processor and the results transmitted to the base station.

To conserve power, the transmitter could be placed in the sleep mode and be turned on only when an alarm condition was detected or a scheduled report was due. By reducing the frequency of transmissions, one can prolong battery life. Low power consumption would permit the alarm system to function if the protected cargo/railcar were left sitting in a storage configuration at a railroad yard or siding for long periods of time. Sensors would be selected by the customer to match the needs of the applications. A microcontroller-based design would facilitate sensor interfacing and signal processing. To minimize false alarm rates and maintain high system reliability, only high-probability events based on data fusion of all sensor inputs would trigger the alarm.

The base station would track and display the location and status of multiple platforms. Two-way communication would permit the base station operator to remotely check the status of the sensors, activate and deactivate the alarm, set the timing interval and conditions for periodic status reports by the remote units, and communicate with the train operator.

3.2 Hazmat Alarm Operations

This product could provide the railroad industry with a cost-effective way to monitor the material condition of hazardous cargo during shipment and to send immediate notification if containment of the cargo is in peril. The concept is to place an electronic sensor/tag on the hazardous material container programmed to assess the vital signs of the cargo. A self-contained electronics module (i.e., processor, power pack, transceiver, and sensors), for example, could be attached to a tank car used to transport petrochemicals at the plant. Sensors, which monitor the liquid level in the tank, internal and external temperature, exhaust gas sniffer, container integrity, and GPS location could be used. The processor could be loaded with a set of instructions defining the normal operating conditions and the protocol to follow in the event the limits were exceeded. Additional

information regarding the cargo type, class of hazard, handling cautions, emergency procedures, and point of contact for the response team might also be included.

In the event that hazardous material leaked from the container or if an unsafe condition developed (i.e., rollover of a tank car or a tank car engulfed in a fire), the alarm would be triggered. The module would transmit a message to a receiving station, notifying the operator of the situation. Remedial action could then be initiated. To conserve power, the system would be operated with a very low duty cycle until the alarm was sounded. Prompt notification could include the train conductor as well as the company headquarters.

3.3 Preventive Maintenance Operations

The concept for this product is to provide an after-market, strap-on electronics module to monitor the material condition of safety-critical components on railcars (e.g., wheel bearings, brakes, etc.), and to identify high-repair-cost items requiring maintenance or other high-consequence event-related items needing service. Under ideal conditions, the warning would be early enough to permit orderly, scheduled repair of the out-of-spec item. A slow leak from a tank car, for instance, might prompt the dispatcher to instruct a service team at the next scheduled stop to inspect the car. On the other hand, immediate action might be required to ensure a controlled response to an in-progress event. For example, the onboard system might warn the engineer that a wheel had jumped the rail and was cutting ties, a condition that unattended might eventually lead to a derailment. The excessive vibration would be picked up by the Green Box and reported as an out-of-normal condition.

For each of these situations, the device would analyze the signals from a suite of sensors and identify the characteristic signature of deteriorated performance. Two approaches are available: one based on predictive models and the other on adaptive models. These two approaches lead to very different functional implementations but both can be accommodated by the flexible software/hardware architecture proposed for the Green Box.

The predictive or deterministic approach (e.g., expert system) is based on acoustic signal data produced by the Association of American Railroads [Ref. 1]. These models describe the distinctive signature of failed bearings under a variety of conditions and would be used to set thresholds for the detector. The adaptive model, on the other hand, would use a learning algorithm (e.g., neural network) to compare signals measured in real-time with a baseline signature learned during normal operation. When a significant departure is identified, the device determines whether this indicates a deteriorated condition or merely a greater variation from the norm than previously observed. In either case, once a failure is predicted, the device will transmit the distress signal to the base station. The resulting information can then be used to schedule repair and maintenance operations.

The benefit is that repairs can be scheduled for items requiring specific attention. Periodic preventative maintenance will not interrupt the operation of equipment in good condition, but keeps it in the revenue mode. Problems would be identified under operating conditions and therefore better diagnosed. As a result, the repairs will likely be more

effective in correcting the true cause of the deficiency and avoiding unwanted effects associated with the catastrophic failure of parts. To ensure acceptable reliability, continuous improvement in understanding the underlying phenomena is essential. Since the failure prediction algorithms and unique precursor signatures have not been established, the task of correlating this information is the subject of additional research and development.

4. Cost-Benefit Analysis of Using the Green Box in the Railroad Industry

To assess the cost/benefit of the Green Box and to estimate the cost of the accidents the Green Box might prevent, we consulted the data compiled by the Federal Railroad Administration, U.S. Department of Transportation [Ref. 2].

- First we will consider costs associated with accidents that could be avoided if all the cars in all freight trains were equipped with the Green Box.
- Second, we will examine the case in which the Green Boxes are attached only to tank cars carrying hazardous materials.
- Third, we will consider the application in which the Green Box is used solely to monitor shipments of high-value cargo.

4.1 Benefit of Equipping All Freight Cars

Reportable train accidents by cause are summarized in Table 1 [Ref. 2, pg. 41].

This table and the following tables include damage to railroad equipment (cars and locomotives) and track (rail, ties, switches, grade, bridges, signal systems, etc.). The ratio of equipment damage to track damage is approximately 3:1 for main line accidents and about 4:1 for yard accidents [Ref. 2, pg. 34].

Table 1. Summary of Train Accidents by Cause (1994).

Cause of accident	Number	Damage (M\$)
Track, Roadbed, and Structures	947	56.2
Equipment Failures - Locomotive	29	2.9
Equipment Failures - Car	264	28.9
Train Operation - Human Factors	911	44.3
Miscellaneous	518	48.3
Total	2,669	180.6

In Table 1, the “Track, Roadbed, and Structures” category of accident causes includes washouts, wide gauge, broken rails, damaged switches (not due to vandalism), and signal failures. “Train Operation - Human Factors” includes failure to use the brakes correctly, employee impairment due to drugs, alcohol, or sleep, communication failures, coupling at excessive speeds, and so on. The “Miscellaneous” category includes avalanches, landslides, floods, shifted loads, highway-rail grade crossing accidents, harmonic rock off, vandalism, and accidents under investigation. Of the five categories of accidents, the Green Box can affect those associated with car equipment failures directly and to a lesser extent those resulting from train operator error or miscellaneous causes. In the latter two cases, the Green Box could provide critical information, not otherwise available, that affects accident-avoidance decisions.

We see from Table 1 that slightly less than 10% of the accidents, and somewhat more than 15% of the damages, are due to car equipment failures. However, not all the car equipment failures are preventable by using the Green Box. The major categories of car and locomotive equipment (mechanical and electrical) failures are shown in Table 2 [Ref. 2, pgs. 44-45]. Structural failure of doors, trailer/containers, or car body (sill, center plate, etc.) represent a small fraction of the accidents and are items probably not worth monitoring by the Green Box. Nonetheless, for structural members, the Green Box sensors could be used to measure the stresses in the material. Candidates for monitoring include coupler and draft gear failures and truck and wheel failures (which include broken wheels — broken flange, broken rim, etc. — damaged wheels, worn wheels, and thermal cracks). A vibration sensor in the Green Box might be able to eliminate some derailments caused by wheel failures.

Of the ten categories in Table 2, accidents listed in the “Brakes” and “Axles and Journal Bearings” categories appear preventable by application of the Green Box. Table 3 lists the specific causes of accidents in the “Brakes” and “Axles and Journal Bearings” categories. “Broken or Bent Axle” means broken or bent between the wheel seats; a broken or bent axle at the wheel seat is considered to be a journal or bearing failure. Seven accidents due to hand brake failures and nine locomotive axle and journal failures that are included in the figures in Table 2 are excluded from Table 3. (The hand brake failures caused \$0.1M in damages and the locomotive axle and journal failures caused \$1.4M in damages.)

Table 2. Summary of Train Accidents Resulting from Car and Locomotive Equipment Failures by Cause (1994).

Cause of accident	Number	Damage (M\$)
Brakes	26	5.5
Trailer or Container on Flat Car	2	0.1
Body (Structural)	18	0.6
Coupler and Draft System	34	2.0
Truck Components	75	5.6
Axles and Journal Bearings	59	8.6
Wheels	46	7.6
Locomotives	9	1.2
Doors	7	0.2
General (Other)	17	0.5
Total	293	31.7

Table 3. Summary of Train Accidents Resulting from Car Air Brake and Axle and Journal Bearing Failures by Cause (1994).

Cause of accident	Number	Damage (M\$)
Air Hose Uncoupled or Burst	2	0.06
Obstructed Brake Pipe	1	4.0
Brake Valve	3	0.6
Other Brake Components	1	0.3
Brake Rigging Down or Dragging	8	0.3
Other Brake Failures	4	0.08
Broken or Bent Axle	4	0.3
Plain Journal Overheating Failure	5	0.2
Roller Bearing Overheating Failure	40	6.6
Other Axle and Journal Failures	1	0.02
Total	69	12.5

Nineteen brake failures and 50 axle and journal failures are listed in Table 3, and the average damages of these accidents is \$181K. Table 3 has divided the accidents for one year so finely that the results may be skewed by one or two accidents. In particular, note that the one accident due to an obstructed brake pipe resulted in almost 75% of the damages for all 19 accidents caused by air brake failures. That one failure resulted in a collision; 15 of the 19 air brake failures resulted in derailments; and 3 caused "Other" accidents. Of the 50 accidents due to railcar axle and journal bearing failures, all but 2 were derailments.

Because of the one very expensive accident due to an obstructed brake pipe, it is instructive to compare the average equipment and track damage value from Table 3 — \$181K — with the averages for several years as shown in Table 4 [Ref. 2, pg. 15]. Table 4 shows results for all accidents, collisions, and derailments, and the last line is the average of the annual values over the six years. (The other two accident categories included in the total are highway-rail crossing accidents and "Other.") Note that variations occur from year to year for all three categories for the number of accidents, damage, and average damage. The average accident damage from Table 3 — \$181K — is significantly greater than any of the three average damage values for the six years shown in Table 4.

Table 4. Summary of Train Accidents by Type (1989 - 1994).

Year	Total number of accidents	Total damage (M\$)	Average damage (K\$)	Number of collisions	Collision damage (M\$)	Collision average damage (K\$)	Number of derailments	Derailment damage (M\$)	Derailment average damage (K\$)
1989	3,081	212.0	68.8	305	22.8	74.7	2,129	152.7	71.7
1990	3,045	211.8	69.6	315	27.8	88.3	2,146	159.3	74.2
1991	2,814	222.9	79.2	261	37.9	145.3	1,936	153.1	79.1
1992	2,531	127.0	50.2	207	14.0	67.6	1,734	91.5	52.8
1993	2,785	190.9	68.5	205	26.2	127.6	1,930	139.8	72.4
1994	2,669	180.6	67.6	240	30.7	127.8	1,825	125.2	68.6
Total	16,925	1,145.1	403.9	1,533	159.4	631.3	11,700	821.6	418.8
Average	2,821	190.9	67.3	255.5	26.6	105.2	1,950	136.9	69.8

Table 5 [Ref. 2, pg. 16] shows that the average equipment and track damage for an accident caused by equipment failures for the years 1989 - 1994 is \$98K, and the average annual equipment and track damages due to all accidents caused by equipment failures is \$38M. (All highway-rail crossing accidents are excluded from the data on which Table 5 is based, even if they were due to equipment failure.)

Table 5. Summary of Train Accidents Caused by Car and Locomotive Equipment Failures (1989 - 1994).

Year	Total number	Total damage (M\$)	Average damage (K\$)
1989	501	43.4	86.5
1990	425	43.6	102.6
1991	415	48.1	116.0
1992	353	24.7	69.9
1993	360	36.7	101.8
1994	293	31.7	108.4
Average	391	38.0	97.5

4.2 Costs Averted if All Railcars are Equipped

The data presented in the previous section allows us to estimate the annual equipment and track damages that might be avoided if the Green Box were installed on all railcars. To bound the damage avoided, we will assume that accidents due to all causes listed in Table 3 (compiled for calendar year 1994) can be prevented by the Green Box.

- If we take the ratio of the “number of accidents prevented” to the “total number of accidents” and multiply by the “total equipment and track damage,” we get an annual value of \$4.7M.
- Alternatively, the value of \$4.8M is obtained by multiplying the “number of accidents prevented” by the “average cost of a derailment.”
- A third method results in \$6.7M, obtained by multiplying the “number of accidents prevented in 1994” by the “average cost of an accident caused by an equipment failure.”
- Finally, we could just use the \$12.5M figure from Table 3, realizing that this is skewed by the one collision due to an obstructed brake pipe; the estimate drops to \$8.5M if we omit this event.

These estimates represent only damages to equipment and track and do not include all the costs of an accident. There are additional costs such as environmental restoration and penalties, medical and death benefits, overtime for operating crews, fees paid to other railroads for detours, damages paid to evacuees, penalties paid to shippers for lost and delayed cargoes, etc. These costs can be substantial. In the case of the July 1991 Southern Pacific derailment near Dunsmuir, California, the initial cost for clean up, compensation to residents, and loss of product was \$4.2M. In February 1994, Southern Pacific reported a cost of \$50M associated with this event. Nonetheless, equipment and track losses provide the basis for an estimate of the range for total costs. At the low end we could argue that the Green Box will not prevent all the accidents listed in Table 2 and that \$5M should cover those accidents that are prevented plus the related "public sector" costs. At the other extreme, we could take the high estimate, \$12.5M, multiply by a factor of four, say, to account for environmental and other costs, and argue that \$50M is a reasonable upper bound for all annual averted costs due to equipment failures that the Green Box could prevent if installed on all railcars. The nominal estimate of annual averted costs is approximately \$25M.

There are approximately 1.2 million railcars in North America [Ref. 3]. Our range of averted costs is from \$4 to \$40 per railcar per year plus annual operating costs associated with the Green Box. This compares to the cost of a standard railcar of \$50K to \$80K, tank cars of \$50K to \$100K, and specialized cars from \$150K to \$250K each.

4.3 Benefit of Equipping Only Hazmat Tank Cars

If putting the Green Box on all railcars is difficult to justify on the basis of equipment and track damages averted, what additional benefit can be realized if one considers the higher losses if hazmat cars are involved in an accident? Alternatively one might consider the benefit if only hazmat cars were monitored. Table 6 presents hazmat accident data for calendar year 1994 by type of accident [Ref. 2, pgs. 49-50]. There were 537 accidents involving 558 consists (trains) that included hazmat cars. Table 6 shows that 680 of the 4,377 hazmat cars in these consists were damaged and only 43 cars released hazardous material. Note: as a precaution, since the integrity of the tank car is unknown, evacuations may occur even if hazardous material is not released.

Table 6. Summary of Accidents Involving Trains with Cars Containing Hazardous Materials by Type (1994).

Accident	Number of consists	Number of cars in the consists	Number of cars containing hazmat	Damaged cars containing hazmat	Damaged cars releasing hazmat	People evacuated	Equipment damage (\$M)
Derailment	395	24,020	3,339	571	37	5,336	22.4
Collision	74	3,740	495	53	2	10,000	11.9
Hwy-Rail	26	1,621	217	4	3	12	3.9
Other	63	2,440	326	52	1	0	0.9
Total	558	31,821	4,377	680	43	15,348	39.2

In eighty-five of the 558 consists with one or more hazmat cars, the accidents were due to equipment (mechanical and electrical) failures. And of these, the Green Box might be expected to avert only 32 consist accidents due to brake and axle and journal failures. These accidents accounted for \$4.2M of the \$39M in equipment damage. We again exclude structural failures, coupler and draft gear failures, etc., from failures the Green Box could detect in time to prevent an accident.

Table 6 shows that slightly less than 14% of the cars in the trains carrying hazardous materials that were involved in accidents actually contained hazardous materials. It is not clear from *Bulletin 163* whether the cars listed as containing hazmat includes all cars that might contain hazmat, loaded or empty, or just cars that were actually loaded with hazmat at the time of the accident. We will assume the latter since an empty car that is used to transport hazmat would not pose a danger of a hazmat release, and the shipper would not notify the railroad of a hazmat shipment for an "empty" car.

The next step is to estimate the number of hazmat railcars. Hazardous material carried in tank cars constitutes a substantial portion of the hazmat shipped by rail. Petrochemicals, flammable gases, and molten metals, for example, are transported in tank cars. We can estimate what fraction of hazmat trains might contain hazmat cars by taking the ratio of hazmat cars involved in hazmat-consists accidents (4,377) to the number of cars in the hazmat-consists involved in hazmat accidents (31,821) from Table 6. From Table 1, we know that 2,992 consists were involved in all the reportable accidents in calendar year 1994, and from Table 5 we know that 558 hazmat-consists were involved in accidents, so the fraction of consists that included hazmat cars is approximately the ratio 558/2,992. The numbers in both of these ratios are large enough that they can be assumed to be representative for all trains, not just those involved in accidents. *Railroad Facts* [Ref. 5, pg. 51] lists the total number of railcars as 1,190K, so the number of loaded hazmat cars is $(4,377/31,821) \times (558/2,992) \times 1,190K \approx 30,000$ cars. Since hazmat tank cars cannot be used for other purposes, one must double the estimate to account for empty cars being returned for replenishment. The total hazmat tank car inventory is therefore $\sim 60,000$ tank cars.

4.4 Costs Averted if Only Hazmat Railcars are Equipped

Nominal values for the equipment and track damages averted by the Green Box in hazmat accidents are based on 1994 data. To bound the total costs we will rely on subjective cost multipliers based on best engineering judgment. The derailment of a hazmat car might be caused by a brake, axle, or journal failure on the hazmat car itself, or some other car ahead of the hazmat car in the train.

Based on the above analysis, one can expect 28% of the equipment and track equipment losses in accidents involving hazmat-carrying trains can be averted by using Green Boxes on hazmat tank cars. This amounts to about \$1.2M and assumes that all accidents due to the causes listed in Table 3 are indeed prevented by the Green Box. We conclude that equipping about 60,000 hazmat tank cars with the Green Box will avert \$1.2M of equipment and track damage every year. This works out to about \$20 of averted equipment and track damage per year per car equipped with the Green Box.

To determine the total costs that might be averted by placing the Green Box on hazmat tank cars, we need to estimate the accident costs other than damage to the railcars, locomotives, track, and related railway structures. These costs include: loss of the cargo, property damage, highway closings, local emergency services, traffic delays, loss of wages to residents and businesses, public evacuations, cleanup and remediation of hazmat, casualties, fines, litigation, etc. We know that some hazmat railroad accidents run up tens of millions of dollars and higher in environmental costs.

A study conducted in 1991 for the National Transportation Research Board [Ref. 4] looked at 45 hazmat rail accidents that occurred between March 1988 and February 1989 (see Appendix B) and estimated the per year costs based on 25-50 incidents per year.

The results:

- Property damage — \$50M - \$100M
- Highway closing — \$20M - 40M
- Public evacuation — \$25M - \$50M.

A study by Wizig and Shillen in 1987 [Ref. 5] estimated the cost of evacuation (accounting for direct evacuation costs and lost wages and earnings by residents and business) to be \$600-\$1,000 per evacuee. From 1980-1989, the railroad industry spent \$100M on cleanup and remediation for major hazmat spills [Ref. 6]. Hazmat incident reports collected by the State of California and the State of Illinois suggest that between \$12.5 and \$25M may be related to transportation (this includes both trucks and railroad). Since we lack detailed information about these expenses, we will account for these costs by use of a multiplier on the equipment and track damages.

Although some railroad hazmat accidents are very expensive, Table 6 indicates that only about 1% of the hazmat cars in trains containing hazmat cargoes that are involved in accidents actually release their cargoes. Thus, while a multiplier of 100 on equipment and track damage to account for environmental and other costs may be reasonable for a few

specific accidents, a multiplier that large is not appropriate for all accidents involving trains with hazmat cars. For all accidents involving trains with hazmat cars, a factor of 10 on equipment damage to account for environmental and other damage is a reasonable upper bound. A lower bound would be a multiplier of 1; half of the accidents due to brake and axle and journal failures on a car equipped with the Green Box will be eliminated and the environmental multiplier is ~ 2 .

The implication of an environmental damage multiplier of 100 is that there would have been environmental costs of about \$360M from the 537 accidents involving trains with loaded hazmat cars in calendar year 1994 (which caused about \$40M in equipment and track damage). This is twice the equipment and track damages for all accidents (\$180M, Table 1). This may be compared to a total of about \$100M for all freight loss and damage payments for an entire year due to all causes. We conclude that an estimate of the average annual hazmat environmental (and other) costs of \$400M are not reasonable, although the costs might run that high for one exceptional year.

With these bounds on the multiplier to account for environmental and other costs, it appears the Green Box might be expected to avert between \$20 and \$200 of accident costs per car per year. This value assumes that all the hazmat cars in the U.S. and Canada are equipped with Green Boxes. It is technically feasible to equip just a small fraction of the hazmat tank cars with the Green Box, but then fixed costs will have to be spread over a smaller number of cars. Still, placing Green Boxes on a small number of hazmat tank cars might be feasible where specific routes are involved.

4.5 Benefit of Equipping Only Railcars with High-Value Cargo

As much as one-third of goods lost in the wholesale industry are lost during the transportation phase. The security of merchandise is particularly acute in the high-tech and automotive industry. Automobiles, once shipped by rail on open flat cars, are now transported in closed railcars. Containerized cargo, which now replaces truck-trailers as the preferred form of inter-modal packaging, is being equipped with sensor systems to counter theft and vandalism losses. The estimated annual cost of robbery, theft, and pilferage from and damage to railcars, for example, is about \$10 million [Ref. 7]. The size of this fleet is $\sim 100,000$ cars. As a result, equipping these cars alone can be justified on the basis of cost avoidance of \$100 per car per year.

In summary, the benefits of Green Box railway applications are primarily the costs of events avoided: thefts, hazmat incidents, and accidents (in that order). Additional benefits may be found in the areas of reduced railcar maintenance costs and improved accident response.

- **Thefts.** The first product should target the security market for protecting high-value cargo from theft and vandalism. To be cost effective, the units should be in the few hundred dollar range.

- **Hazmat incidents.** When only tank cars that carry hazardous material are considered, the next most attractive application of the Green Box is to monitor hazmat shipments. When hazmat is involved, in addition to equipment and track damage, one must add the cost of public evacuation, cleanup, and remediation. Evacuations which average about \$1 million per event (figures for calendar year 1987) are often conducted as a precautionary measure whether or not hazmat has been released. The accident costs averted by placing Green Boxes on all hazmat cars appears to be in the \$20 to \$200 range per tank car per year.
- **Accidents.** It appears to be very difficult to justify placing a Green Box on every car in the North American railcar fleet on the basis of annual accident costs averted. Although the average accident incurs about \$60K of equipment and track damage, there are over one million railcars. But most importantly, only a fraction of equipment and track damage typically results from accidents that the Green Box could prevent. Accidents caused by floods, landslides, train crew errors and the like are clearly beyond the capability of the Green Box to avert. Using the highest estimates the averted accident costs are only on the order of \$40 per railcar per year.

The decision to implement a Green Box system will depend on a comparison of the costs averted with the original cost of the Green Box itself, the annual maintenance costs, and the apportioned per car costs for providing monitoring and communications equipment. The Green Box by itself will be useless in preventing accidents unless the means are provided to stop the train in time when a Green Box indicates a potential problem. This could be accomplished by direct communication between the Green Box and the locomotive or by a communication link that goes from the Green Box to a monitoring network, then to the railroad dispatcher, and finally to the engineer. The costs of this portion of the system cannot be overlooked.

5. System Design and Validation

The system design effort for the Green Box is based on a strategy suggested by the market research and the cost-benefit studies. The idea is to introduce a product with modest capabilities, establish a performance record with the customers, and later expand to additional capabilities. As a result, the technical goal was to design a system architecture for the first product with built-in expansion capability. The initial design will focus on the security application and will be extended to the other options with degrees of detail consistent with their cost-benefit ranking. By adapting existing Sandia designs [Ref. 8], we propose to develop a common system architecture for the three applications in a single, software and hardware reconfigurable module.

Based on this approach, the security application will be specified to the chip sets level. The resulting design will be delivered to our commercial partner for resolving product realization issues and estimating production cost. The hazmat application will follow a similar development but will stop short of specifying chip sets. The preventive maintenance scheduler will not be developed past the system block diagram.

The Green Box system consists of two parts: a remote unit (strap-on module) mounted on a train car and a base station located at company headquarters. We have assumed that the base station can be assembled from commercial hardware: personal computers (PCs) and modems common in business offices today and Green Box-specific software, compatible with PC operating systems. Validating these crucial assumptions is treated at the end of this section. We will first concentrate on the unique features of the strap-on module.

The concept of operations defines the primary functions of the Green Box system as acquisition, processing, communication, and display of data. Together with independent power and location information these form the basic building blocks of the Green Box system (see Figure 1). The computing power of the controller makes for a robust system in which changes are easily made in software. The system is both software and hardware modular. The sensor suite, the alarm threshold conditions, the specific response algorithm, power supply technology, and communication system are all selectable. Components can be matched to the specific application from a pre-approved/qualified list.

Sensor issues: Based on two, two-axle trucks and one strap-on unit per railcar, we estimate eight data channels are required to provide information on each bearing. If we consider the applications for monitoring either the security of cargo or state-of-health of hazmat, eight channels also appear adequate. For containerized cargo, carried on double-stack railcars, four sensor pairs (one internal and one external per container) would suffice. For a tanker car transporting hazardous material, eight sensors channels could provide information on the temperature of the product, amount of product (e.g., fluid level), orientation of the car in 3-axes, and acceleration in 3-axes. Based on these considerations, we set the requirement for an eight-channel, eight-bit analog-to-digital converter. One could easily expand to sixteen channels by multiplexing inputs if necessary.

Communication issues: Reporting real-time events identified by the strap-on unit is essential to realizing improvements in operational performance and operating cost. The Green Box module will be configured with a serial port to permit adaptation to a variety of communications devices including RF, IR, and acoustic. As a result, data collected and processed by the Green Box could be passed to an automated equipment identification device such as the Amtech tag for transmission to wayside monitor stations. In this manner, information about the status of the car and cargo could be reported through existing communication systems. In situations requiring immediate response (e.g., failed bearing, broken axle), direct transmission to the engineer or dispatcher could be accommodated by a connection to a voice/data radio. To validate the communication strategy, we selected the cellular telephone technology to test the essential features.

Power issues: The issues for this design characteristic are independence of operation and serviceability. If the electric-controlled braking system, currently under development, is fielded [Refs. 9 and 10], a source of power for the Green Box would be available. In the meantime, the strap-on module must be stand-alone on most freight cars. Extracting power from the air brake system was rejected because it would introduce a serious failure mode in the safety system. A caboose-style power pick-up concept was also discarded because it was judged too expensive to install and maintain and had low reliability. As a result, we settled on a battery-operated system with the goal of three months independent operation. A solar panel recharging system was considered but the additional cost outweighed any potential benefit we could identify.

Controller and Processor issues: Processing the data collected by the sensors and extracting the information is the essence of the Green Box. Depending on the application, several different sensors could be needed. To accommodate the variety of possible customer applications, we established an input standard of 0-5 volts. The processor would calibrate the signal values and interpret the corresponding measurement in a look-up table. To hold conversion tables and scratch pad information for the specific applications, we augmented the processor with a memory chip. To reduce power consumption, the processor should control the transmitter duty cycle. The system should be designed to report "by-exception" only. To minimize false alarms (limits to be established by discussions with customer), polling techniques and signal averaging should be employed. As much as practicable the design should be processor independent.

Packaging issues: The packaging must provide protection for the strap-on module when exposed to environmental conditions: -40°C to $+80^{\circ}\text{C}$, humidity 0-100%, shock (5% min-max absolute shock bounded between 20 and 100 g's over the frequency range 10 to 1,000 Hz), and vibration (bounded between 0.01 and 0.1 g^2/Hz over the frequency range 10 to 1,000 Hz). If post-accident survival is required, these specifications can be supplemented with immersion in a fuel fire (~ a few minutes) and static crush load (~ 1000 lb). Previous designs have considered this survivability option but the current product performance characteristics do not support the added expense of a stronger housing.

Location issues: In some instances the customer may desire location information. If hazmat is being monitored or the railcar is serving as temporary storage on a siding, independent location information might be useful. Since the initial Green Box market targets

high-value cargo and hazmat, it is conceivable that the strap-on module's owner might not be the railroad company. In the case of certain shipments (e.g., containerized cargo), the tags are not on the railcar; and in the case of some hazmat (e.g., the phosphorous producers), the tank cars are owned by the shipper or car leasing companies. The GPS receiver is therefore included as an option for the security and hazmat applications but not for the maintenance scheduler product.

Display issues: The information collected by the strap-on unit can be displayed on a standard personal computer found in today's business office. If augmented with modem capability and configured with a minimum of 8 Meg RAM and 80 Meg disk space, the office PC can run a compiled version of the display software.

Validating the System Design Assumptions: We assumed from the outset that commercial hardware and software could be used to configure a typical office personal computer to receive and display the information transmitted from the Green Box strap-on units. In addition, we assumed that any common communication system could be used to transmit data from the remote unit to the base station. Both these assumptions are crucial, for they significantly impact the cost of implementing a Green Box monitoring system. The major cost of a Green Box system is associated with the communications system. If we can demonstrate that the proposed design was adaptable to common equipment, the concept is sound.

The Green Box remote unit was assembled from a collection of parts salvaged from other experiments (see Figure 3). The base station software was written in LabView (commercial virtual instrument software product used at the laboratory) and down-loaded to a Gateway 2000 personal computer adapted with a MicroCom modem. With this configuration, periodic temperature and position data was transmitted from a railcar on the Santa Fe Southern Railroad during a round trip run from Santa Fe to Lamy, New Mexico. The data was sent via cellular telephone to the Green Box base station at Sandia National Laboratories/California.

This simple test validated the assumptions. Two-way communication was also demonstrated. Independent assessment of similar communication strategies used in other projects at the laboratory reinforced these conclusions.

SL-24563A

Figure 3. Proof-of-Concept Hardware

Manufacturing issues: In addition to the operational characteristics, the system requirements also reflect choices driven by manufacturing issues, the desire to produce a reliable product at the lowest reasonable cost, as well as low life-cycle costs (installation ease, serviceability, reparability, durability, etc.). The key is produceability at low cost. To achieve this, we require designs insensitive to part tolerance. Commercial parts and standard production processes must be specified. Based on the benefits analysis, we established a cost target of \$500 per unit for the strap-on module produced in lots of 1,000.

6. Circuit Implementation

The Green Box circuit implementation is a low-cost, low-power, flexible design. A flexible design allows for a wide variety of potential applications. Sensors were not included in the cost, since the exact sensor suite will be determined by the customer. In addition, a communications capability was not costed because data transmission is application-specific. Although these functions were not included in the cost estimate, the interface for different types of sensors and for data communications was included. Appendix C gives a schematic of the Green Box data processor printed circuit board.

At the heart of the Green Box is the Motorola MC68HC811E2 microcontroller. This device family is widely used in the automobile industry. The MC68HC811E2 device is an advanced 8-bit microcontroller with highly sophisticated on-chip peripheral capabilities. An alternative design uses the Intel 87C196 microcontroller, which is a 16-bit device with higher speed processing capabilities but a slightly higher cost. For the initial Green Box application, the Motorola device was chosen.

The microcontroller is a fully static design that allows operation at frequencies down to DC. Operating at lower frequencies reduces power consumption, which is a desirable characteristic for battery operation. An eight-channel analog-to-digital (A/D) converter is included on-chip with eight bits of resolution. A low-power stop mode capability allows the Green Box to be put into a sleep mode to conserve power. The Green Box can be programmed to run in a "pulsed" mode, i.e., turned on for 10 milliseconds, turned off for 990 milliseconds. In this mode, a sensor can be checked for possible alarm conditions once per second with only a 1% duty cycle.

6.1 Sensor Inputs

The sensor interface includes eight differential inputs that can accept single-ended inputs by grounding the inverting (or noninverting) input pin. The input amplifiers can be configured for gain and anti-aliasing filters by the proper selection of resistors and capacitors. A differential input interface was selected to allow sensors with either single-ended or differential outputs to be connected. Table 7 gives the pinout to the DB 25-pin connector, which provides the sensor inputs to the amplifiers.

Table 7. Sensor Input Connector Pin Definitions

Pin No.	Input name	Pin No.	Input name	Pin No.	Input name
1	Channel 0+	10	Channel 3+	19	Channel 6+
2	Channel 0-	11	Channel 3-	20	Channel 6-
3	ground	12	ground	21	ground
4	Channel 1+	13	Channel 4+	22	Channel 7+
5	Channel 1-	14	Channel 4-	23	Channel 7-
6	ground	15	ground	24	ground
7	Channel 2+	16	Channel 5+	25	+5 volts
8	Channel 2-	17	Channel 5-		
9	ground	18	ground		

6.2 GPS Receiver Interface

The GPS receiver integrated into the Green Box is a VP Encore receiver manufactured by Motorola. It is delivered as a fully assembled printed circuit board with dimensions 2.00 in. x 3.25 in. x 0.64 in. The GPS serial communications has a TTL level interface and receives commands to provide the appropriate output messages. Also included with the receiver module is an on-board keep-alive battery and an active antenna. Ten pin headers on both the GPS board and the Green Box processor board are used to connect the two modules with a ribbon cable.

6.3 Communications Interface

As we described in the concept of operations section, the communications system for the Green Box module will be determined by the operational requirements of the customer. We therefore designed the communications interface to accommodate several options. A cellular telephone concept was validated in a field test. Another option might be to use the railroad's radio network or similar RF system. For the purpose of this design, we investigated using an FCC part 15 spread spectrum radio with 1/3-watt output power. The radio includes a 32-bit CRC error detection with retransmission capability. Information is supplied and received over an asynchronous RS232 interface. This device is manufactured by FreeWave Technologies, Inc. of Boulder, Colorado. FreeWave Technologies has applied for FCC approval for converting the radio RF output power to 1 watt.

The FreeWave Technologies DGR-115 spread spectrum transceivers are capable of data rates of 115.2 kBaud over distances of 20 miles or more. Unlike cellular and land line data communications, this transceiver sets up quickly and has no ongoing access fees. When used in conjunction with other data links such as the Internet, it is possible to combine wireless and wireline data communications, essentially making remote data available around the world.

6.4 Power Supply

A 7-volt dual-cell 1.6 ampere-hour lithium battery provides the power for the entire Green Box processor board. A 5-volt output DC/DC converter provides power regulation to all circuits, including analog signal conditioning, RS232 transceiver, and digital devices. As described earlier, the Green Box has a sleep mode of operation for prolonging battery life. For the security application, the Green Box could operate in an interrupt driven mode with the security sensor output providing an interrupt to “wake up” the processor, which provides the alarm. In this mode, power is conserved until needed.

Intentionally Left Blank

7. Product Realization

There are some requirements uncertainties due to the large quantity and diversity of potential customers. For the initial product focus, the security of cargo application is targeted. The unresolved issues are the customer's choice of data communication and types of sensors needed. It is not known whether an application is desired that provides information directly to a base station owned by the customer or transmits an alarm condition to the train engineer for relaying via the railroad company's voice communications system. Other unknowns include sensor type, sensor sampling rate, required signal conditioning and anti-aliasing filters, and signal processing.

The cargo burglar alarm system operates as follows: The Green Box is mounted on a railcar, or possibly connected directly to the cargo container. The security module contains a processor, GPS receiver (if needed), and communications transceiver, and is attached to one or more (up to eight) sensors to monitor door switches, temperature, orientation, or fluid levels. The processor could monitor the sensors once per second (or seconds) or be placed in an interrupt mode, then put to sleep to conserve power. A sensor threshold, when exceeded, would provide the interrupt to the processor, which "awakens," takes sensor and GPS readings, then communicates information to the train engineer or dispatcher. The information could then be relayed to the appropriate agencies. An alternative design would incorporate a cellular phone and modem to allow the owner of the cargo to query the Green Box for information when needed.

For this application, a single printed circuit board will contain all Green Box data processing electronics. In addition to the processor board, the GPS receiver electronics and the communications transceiver are on separate boards designed by the respective supplier. All three boards can be stacked inside the Green Box enclosure. To keep costs low, commercial surface-mount parts were used where possible. Printed circuit board fabrication costs are proportional to the quantity of hole drilling needed to produce the boards. To reduce labor and wiring costs, we must consolidate as many functions as possible into a single container. CMOS technology is used to keep power consumption low.

7.1 Manufacturing Costs

Delta Group Inc. of Albuquerque, New Mexico, performed a manufacturing study of the Green Box design. Delta Group's findings are summarized in the report found in Appendix D. The one-time costs associated with a receiving station (located at company headquarters or at the railroad dispatcher office) to display the alarm message information, software modifications to adapt the Green Box to a specific application, and the purchase of a communications transceiver were not included in the Delta Group estimate. These costs will be included with the non-recurring engineering (NRE) cost estimates.

An itemized list of costs to manufacture the Green Box is provided in Table 8. NRE costs, which include software and manufacturing engineering, are given first. The manufacturing engineering NRE costs are included twice, once as a total and listed with the

associated item but not included in the materials and labor total. The item numbers given in Table 2 correspond to the numbers in the drawing included in the Delta Group report in Appendix D. The NRE costs can be amortized over several thousand units produced.

Table 8. List of Costs for Producing the Green Box in Quantities of 1000.

Item	Description	Part number	Supplier	Qty	Price
	NRE software engineering				8,000.00
	NRE manufacturing engineering				2,025.00
1	enclosure	95F6395	BUD	1	14.85
	tooling (175.00)	TBD			NRE
2	GPS antenna connector	TBD	HEYCO	1	2.34
3	hardware		TBD	1	20.00
4	VP Encore GPS receiver with active antenna	N/A	MOTOROLA	1	245.00
	assembly labor				13.00
5	battery pack stack 2 AA 7V 1.6Ahr		TBD	1	3.80
	cable assembly (sensors)				
6		747052-2	AMP	1	4.18
7		746290-6	AMP	1	0.81
8		499252-3	AMP	1	0.09
9		3365/25	3M	1	0.40
	assembly labor				2.16
	cable assembly (communications)				
10		747052-4	AMP	1	2.68
11		746290-1	AMP	1	0.41
12		499252-5	AMP	1	0.07
13		3365/09	3M	1	0.40
	assembly labor				2.16
	cable assembly (GPS logic)				
14		746290-1	AMP	2	0.82
15		499252-5	AMP	2	0.14

Table 8 (continued).

Item	Description	Part number	Supplier	Qty	Price
16		3365/09	3M	1	0.40
	assembly labor				2.16
	cable assembly (GPS antenna)				
17	OSX microminiature		M/A COM	2	7.30
18	coaxial cable (RG-58U)		BELDON	10 ft	1.20
	assembly labor				6.48
	PC board fabrication, 4 layer				
19	4" × 6" silk-screen/mask		TBD	1	16.00
	CAD/CAM (\$600.00)		TBD	1	NRE
	PC board fab tooling (\$900.00)		TBD	1	NRE
	PCB test (included w/tooling)		TBD	1	NRE
	solder stencil (\$250.00)		TBD	1	NRE
	surface-mount engineering (\$100.00)		TBD	1	NRE
	PC board assembly labor			1	8.75
20	microcontroller	MC68HC811E2	MOTOROLA	1	9.17
21	alternative microcontroller (\$22.00)	N87C196KC-16	INTEL	1	N/A
22	J-lead decoder	74HC138			0.24
23	RS232 transceiver	LT1081	LINEAR	1	1.63
24	latch	74HCT573			1.71
25	inverter	74HCT04			0.21
26	triple OR gate	74HCT32			0.68
27	DC/DC converter	MT3-0505SI	VOLGEN	1	23.13
28	oscillator	CTX157-ND	DIGIKEY	1	1.96
29	power-up reset	MAX694	MAXIM	1	2.48
30	operational amplifier	OP490S	ANALOG DEV	2	7.70
31	128K × 8 static RAM	HM628128CFP7	HITACHI	1	10.73
32	capacitors			TBD	10.00
33	resistors			TBD	5.00
34	battery header	22-29-2021	MOLEX	1	0.11
35	communications and GPS headers	499206-1	AMP	2	1.16
36	sensors header	499206-6	AMP	1	1.17

Table 8 (concluded).

Item	Description	Part number	Supplier	Qty	Price
37	comm transceiver, including antenna and cable	DGR-115	FREEWAVE	1	400.00
	Total materials and labor:				\$832.68

Neither the cost of sensors nor the cost to install the sensors is included in Table 8. The price of sensors can vary significantly even among sensors of the same type. Each type of sensor has a range of prices, which depend on the sensor's required sensitivity, robustness, and signal processing capabilities. Table 9 gives a sampling of the range of prices for a given type of sensor, which could be used with the Green Box.

Table 9. Range of Prices for Possible Green Box Sensors.

Type of sensor	Range of prices
door sensors	
balanced magnetic switch	\$60 - \$300
regular magnetic switch	\$5 - \$25
motion sensors	
passive infrared	\$40 - \$800
monostatic microwave	\$150 - \$1200
boundary sensors	
active infrared	\$200 - \$2000
exterior active infrared	up to \$5000
breakwire sensors	\$100 - \$1000
temperature sensors	
thermocouples	\$5 - \$40
resistive temperature devices (RTDs)	\$40 - \$100
strain gages for detecting weight changes	\$15 - \$20

8. Market Potential

A marketing study was conducted for the Green Box project by the School of Business and Economics, California State University, Hayward. The study [Ref. 11] concluded that three issues are important for the successful marketing of the Green Box: industry awareness of the product capabilities, the existence of a broad customer base, and the cost of the product. Of these the cost is paramount; "cost should be kept low." Our product costs were therefore kept as low as possible.

To further reduce the cost of a Green Box system, one might therefore consider applications that offer alternatives to radio message traffic. For example, ultrasonic or audio alarms rather than radio transmitters might serve the basic needs of a security application by simply bringing attention to the situation. Coded ultrasonic bursts picked up by wayside monitors or battery-power receivers on the locomotive are a possibility. In terms of product awareness, the observation was made that the railroad industry is wary of new technologies; testing and data supporting product claims is needed. For this reason, the benefits analysis was based on published industry data and the communication system validation test was included in this project.

Finally, the multiple product types, which the software/hardware reconfigurable design makes feasible, can be used to satisfy the needs of a variety of customers. The result is a robust capability that strengthens the marketability of the product (see Figure 4).

Figure 4. Green Box Reconfigurable Product Line

In addition, the business research project recommended two strategies for launching the Green Box product:

- First, the research recommended a joint venture or licensing agreement. This is the approach we have taken. Through the contacts provided by the Alliance for Transportation Research (ATR), the Delta Group and SAIC were approached with this intent. At this time, the Delta Group indicated an interest in proceeding further with the concept by producing prototypes of the Green Box based on the manufacturing process we have jointly developed.
- Second, the market research group suggested we enlist large insurance firms with the intent of convincing them to offer premium credits for the use of the Green Box. In this strategy, the data collected on losses associated with accidents, incidents, and environmental liabilities are very important. If damage claims continue to climb, this may be a very fruitful avenue to pursue.

9. Conclusion

The Green Box strap-on sensor package has the potential for providing significant savings for the railroad companies or for individual shippers of high-value or hazardous material cargo. The initial application provides security of the cargo and tracking capability at a reasonable price. Future applications can extend benefits to include emergency transmissions during a hazardous material transport incident and railcar maintenance scheduling. We believe that the best entry into the marketplace is a tiered approach, which allows the initial Green Box modules to have a low initial cost. The feasibility for other applications of the Green Box is improved once the market is penetrated and an infrastructure is put in place.

Intentionally Left Blank

10. References

- [1] Personal communications with R. L. Smith of Mechanical Technology Inc. Chicago, IL, regarding acoustic signature of bearing failure detection per his published results, "Railroad Bearing End-life Failure Distances and Acoustic Censuring Methods," ASME Winter Annual Meeting, paper WA RT3, Dec. 1988.
- [2] Federal Railroad Administration, U.S. Department of Transportation, *Accident/Incident Bulletin No. 163, Calendar Year 1994*.
- [3] *Railroad Facts*, Association of American Railroads, Washington, D.C., 1992.
- [4] National Research Council, Transportation Research Board, Special Report 239, "Hazardous Materials Shipment Information for Emergency Response," 1993.
- [5] Witzig, W. F., and J. K. Shillen. 1987. *Evaluation of Protective Action Risks*. Report NUREG/CR-4726. U.S. Nuclear Regulatory Commission.
- [6] Barkan, C., T. Glickman, and A. Harvey. 1991. Benefit-Cost Evaluation Using Different Specification Tank Cars To Reduce the Risk of Transporting Environmentally Sensitive Chemicals. In *Transportation Research Record 1313*, TRB National Research Council, Washington, D.C., pp. 33-43.
- [7] AAR 1993 Freight Loss and Damage Payment Records, Report No. 1193-DPFC-1, Association of American Railroads, Customer Service Division, Washington, D.C., 1994.
- [8] Sandia Modular Airborne Reconfigurable Telemetry System (SMARTS) is a high-performance telemetry package developed by Sandia, which utilizes a strategy of software and hardware design flexibility to accommodate a wide variety of electrical and system interfaces. Advanced Electrical System Architecture (AESAs) is a weapon system design strategy which uses commercial off-the-shelf hardware to perform numerous data acquisition, interpretation, and information reporting functions.
- [9] Zimmerman, R. M. Sandia National Laboratories, pre-publication draft: "The Case for Systems Level Consideration in Upgrading the U.S. Rail Freight Industry," Feb. 1995, submitted to Railway Age.
- [10] Zimmerman, R. M. Sandia National Laboratories, pre-publication draft: "Economic Considerations in Integrating Electronic Communications, Information and Control Systems on to U.S. Freight Cars." April 1995, submitted to Railway Age.
- [11] Christina, J. D., D. Carmichael, H. Gilman, M. Lewis, M. Beeby, and S. Fernandez, "The Green Box Marketing Feasibility Study," Technology Marketing 4450-30, New Ventures Research Project Report, Fall Quarter 1994, California State University, Hayward, California.

Intentionally Left Blank

APPENDIX A

Statement of Work

Intentionally Left Blank

The University of New Mexico

New Mexico Engineering Research Institute
Albuquerque, NM 87131-1376
USA

June 20, 1994

Domingo Sanchez Director
State Transportation Authority
Montoya Building
1100 St. Francis Drive
Santa Fe, NM 87503

Dear Mr. Sanchez:

At your request I have processed the contracts which we received earlier today. The contract will be with the Regents of the University of New Mexico. This change has been made and initialed on the copies our representative has signed. The statement of work is as follows which is an abbreviated version of the statement of work previously sent to you in our proposal.

Statement of Work:

Technical Content:

Task One - User Requirements

Planning activities to identify user requirements are critical to the entire program. During this process, the project team will work with the customers -- including the State Transportation Authority, U.S. Department of Transportation, railroad companies, and emergency response coordinators -- to identify functional/operation requirements for the Green Box automated monitoring and tracking system. Deliverables include identification of electrical and mechanical interfaces for integrating the Green Box into the demonstration rail platforms. A description of the range of operational situations that may be adequately handled will be developed. This task will provide guidelines for installation interfaces for application to rail rolling stock.

Task Two - Benefit Analysis

Objective of the benefit analysis is to evaluate the economics of operating such a system on a large scale (fleet-wide). Potential benefits include cost savings associated with scheduled versus unscheduled maintenance of safety critical components, reduced loss due to theft and pilferage, and reduced environmental remediation costs of hazmat incidents. The project team

Letter—Domingo Sanchez
 State Transportation Authority
 June 20, 1994

will work with emergency response agencies to identify the proper metrics, methodology, and problem statement for the assessment. The following outline is a preliminary starting point.

1. Obtain general information on the cost to the railroad industry of problems the Green Box may mitigate.
2. Select applications with the best cost-benefit ratio for the Green Box.
3. Develop detailed information on the problems selected.
4. Confirm cost-benefit analysis for selected potential application, and estimate annual benefits that would be realized by implementing the Green Box.

Schedule:

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
Phase I Tasks																		
Requirements																		
Cost-Benefit Analysis																		
Phase I Report																		
Phase II Tasks																		
Engineering Integration	To be scheduled in the future																	
Operational Demo																		
Environmental Testing																		
Commercialization Anal.																		
Final Report																		

An itemized budget is also attached for the Phase I funding we discussed. Please let me know if you require anything additional pertaining this contract.

Sincerely,

R. Gordon McKeen, P. E.

Manager, Civil Systems & Safety Division

APPENDIX B

Supplemental Hazardous Materials Shipment Information: Rail Incidents

Intentionally Left Blank

Supplemental Hazardous Materials Shipment Information: Rail Incidents

1. Dunsmuir, California, July 14, 1991. A 97-car freight train had 6 of its cars and rear locomotives derail on a bridge over the Sacramento River. A derailed tank car was damaged and released 19,500 gal. of the pesticide metam sodium into the river. Metam sodium is not designated by DOT as a hazardous material, and placards were not displayed on the tank car. Shipping papers for the car listed the material as a weed killer but did not specify potential hazards. In addition, the material is not listed in the DOE Emergency Response Guidebook. As a result, fire and police officials responding to the derailment were uncertain of the hazards associated with the material and did not have information indicating its toxicity to fish and other water life. Because of the uncertainty about the chemical, responders treated the spill as potentially hazardous and contacted CHEMTREC for safety data. More than 3 hours passed before responders were able to obtain basic information about the chemical's hazards (unpublished NTSB rail accident investigation documentation).

2. Freeland, Michigan, July 22, 1989. A freight train had 14 of its cars derail. Six tank cars were damaged and released all or part of their loads and caught fire. The tank cars contained styrene, monomer, acrylonitrile, acrylic acid, naphtha, and a mixture of chlorosilanes. After the accident, the conductor radioed the rail yard dispatcher, who notified the local fire department. Fire officials arriving on the scene were immediately provided with the train consist and waybills. Shippers of the materials were notified, and many sent representatives to the scene within 2 hours. Railroad employees and a shipper representative assisted fire officials in reviewing the shipping documents and identifying the hazardous materials. The materials involved in the wreck were quickly identified. However, because the tank cars were jumbled in the pileup and placards and car markings were not visible due to smoke and fire, fire officials could not determine which materials were burning. Without this information, fire fighters could not determine the appropriate extinguishing agent and were forced to let the fire burn longer than they otherwise might have. About 1,000 residents were evacuated almost immediately after the derailment (NTSB 1991b).

3. Seacliff, California, July 28, 1991. Twelve cars of a freight train derailed under a freeway overpass. Many of the cars were flatbeds that had been carrying intermodal containers. In the pileup caused by the derailment, many of the intermodal containers were ejected. Fifteen 55-gal. drums escaped from the containers and were punctured, spilling 440 gal. of hydrazine. A 5,000-gal. tank of naphthalene was also ejected near the drums, although it was not breached. Because fire units had to approach the train from the rear, they did not have access to the train's consist and waybills, which were located at the front end. The only access road leading to the front of the train passed through the accident site. This logistical problem resulted in a delay before fire officials were able to determine which materials were involved in the derailment. However, because many of the intermodal containers and their contents (drums) had been ejected from the cars and scattered, fire officials could not determine the origin and contents of each drum. To obtain this information, fire fighters in protective equipment had to visually inspect the labels on each of the damaged drums (unpublished NTSB rail accident investigation documentation).

4. Miamisburg, Ohio, July 8, 1986. Fifteen cars of a 44-car freight train derailed. Three of the derailed cars were tank cars containing yellow phosphorus, molten sulfur, and tallow. The tank cars, which derailed on a bridge, were extensively damaged, lost product, and were involved in the resulting fire. Local fire and police officials were alerted by witnesses to the derailment. The first responders could only see two of the tank cars because of the smoke and fire. The more visible car had lost its placards in the crash; therefore, first responders were not immediately aware that hazardous materials were involved. After surveying the damage, the conductor met the emergency responders, alerted them to the presence of hazardous materials, and presented them with the train consist. The conductor had to return to the locomotive to retrieve the waybills, which he had inadvertently left behind. The waybills were not in order and had to be reassembled to identify all the cars in the derailment. In addition, the conductor left behind in the locomotive an emergency guide that accompanied the phosphorus shipment. To confidently identify all of the cars involved, fire fighters were sent into the derailment site in full protective equipment to visually inspect each car (NTSB 1987).

APPENDIX C

Green Box Circuit Schematic

Intentionally Left Blank

C. O. LAMORON
SANDIA NATIONAL LABORATORIES
DEPARTMENT 2664, MS 0987
ALBUQUERQUE, NM 87185-0987

File: GREEN BOX PROCESSOR
Size: Document Number
C
Date: March 28, 1996 Sheet 1 of 1

Intentionally Left Blank

APPENDIX D

Manufacturing Study

Intentionally Left Blank

2105 Aztec Road NE, Albuquerque, NM 87107

Green Box Manufacturing Study

Prepared by
Dominic J. Isbell
Manufacturing Engineer

for
Dan Rey
Electrical Engineer
Sandia National Laboratories

March 19, 1996

March 19,1996

I. INTRODUCTION

Delta Group, Inc. has prepared this report for the Sandia National Laboratories feasibility study on railroad car instrumentation for the transportation industry. The attached depicts the costs associated with the complete manufacturing of a sensor box, known as the Greenbox and details costs breakdowns for parts, labor and engineering (NRE) as of Q1 1996 pricing.

II. COSTS

Part costs are based on one thousand piece quantities and obtained from best vendor pricing where applicable.

Labor pricing is based on a standard labor rate per hour currently used by Delta Group. Labor costs do not reflect microprocessor/EEPROM programming, or, tooling charges for factory programming of this part. Factory programming would be a feasible alternative after firmware revisions have matured and future requirements have been proven and satisfied. Tooling cost can then be amortized over several thousand units.

Engineering (NRE) reflects outside costs required to complete manufacturing engineering to satisfy production requirements. This is a one time charge and can be amortized into the initial production run of one thousand pieces.

Alternative pricing reflects the use of an INTEL microprocessor in place of the originally specified MOTOROLA microprocessor.

III. CONCLUSION

The attached report details the following:

Materials costs:	\$419.97	
Alternative Materials (Intel)		\$432.80
Labor:	\$34.71	\$34.71
NRE:	\$2025.00	
Total unit cost	\$454.68	
Total unit cost alternative materials		\$467.51

NOTES:

Circled numbers represent Bill of Materials line numbers.

2105 AZTEC RD. NE ALBUQUERQUE, NM 87107 (505) 883 7674 FAX 883 8888

LTR	DATE	REVISION NO.	APVD

TITLE GREEN BOX ASSY DRAWING				SHEET 1 OF 1
DATE 03MAR96	PART NUMBER DGI0319	REV -	DRAWN DI	FILE C:GBMFG

Notes:
Dim = inches
7v @ 1.6Ahr

LTR	DATE	REVISION NO.	APVD

2105 AZTEC RD. NE ALBUQUERQUE, NM 87107 (505) 885 7674 FAX 885 5888

TITLE				SHEET
BATTERY ASSY, LITHIUM 7 VOLT				1 of 1
DATE	PART NUMBER	REV	DRAWN	FILE
3/8/96	SAND-01-1	-	DI	SAND.DWG

SANDIA LABORATORIES GREEN BOX PROJECT EVALUATION									
MANUFACTURING REQUIREMENT/COSTS									
CODES:		M = MATERIALS COSTS			N = NRE (TOOLING)		L = LABOR (ASSEMBLY)		
		TBD = TO BE DETERMINED			A = ALTERNATIVE REQUIREMENT				
1000 PIECE QTY									
ITEM		PART NUMBER	MANUFACTURER	QTY	PRICE	EXTENSION			
					CODE	M	N	L	A
GREEN BOX STRAP ON SENSOR MODULE									
1	ENCLOSURE	95F6395	BUD	1	14.85	14.85			
		TOOLING	TBD	1	175		175.00		
2		TBD	HEYCO	1	2.34	2.34			
3		HARDWARE	TBD	1	20	20.00			
VP ONCORE GPS									
4		RECEIVER/ANTENNA		1	245	245.00			
		ASSEMBLY						13.00	
BATTERY PACK									
5		2 STACK AA 7V 1.6Ahr	TBD	1	3.8	3.80			
CABLE ASSY, SENSOR TO PCB									
6		747052-2	AMP	1	4.18	4.18			
7		746290-6	AMP	1	0.81	0.81			
8		499252-3	AMP	1	0.09	0.09			
9		3365/25	3M	1	0.4	0.40			
		ASSEMBLY						2.16	
CABLE ASSY, COMM									
10		747052-4	AMP	1	2.68	2.68			
11		746290-1	AMP	1	0.41	0.41			
12		499252-5	AMP	1	0.07	0.07			
13		3365/09	3M	1	0.4	0.40			
		ASSEMBLY						2.16	
CABLE ASSY, GPS									
14		746290-1	AMP	2	0.41	0.82			

1000 PIECE QTY												
ITEM		PART NUMBER	MANUFACTURER	QTY	PRICE	EXTENSION						
					CODE	M	N	L	A			
15		499252-5	AMP	2	0.07	0.14						
16		3365/09	3M	1	0.4	0.40						
		ASSEMBLY								2.16		
		CABLE ASSY, GPS ANTENNA										
		OSX										
17		MICROMINATURE	M/A COM	2	3.65	7.30						
18		COAX	BELDON RG-58U	10FT	1.2	1.20						
		ASSEMBLY								6.48		
		PC BOARD 4 LAYER										
19		4x6" SILKSCREEN/MASK	TBD	1	16	16.00						
		CAD/CAM	TBD	1						600.00		
		PCB FAB TOOLING (INCL. TEST)	TBD	1						900.00		
		SOLDER STENCIL	TBD	1						250.00		
		SMT ENGINEERING	TBD	1						100.00		
		ASSEMBLY		1						8.75		
20		MC68HC11E2	MOTOROLA	1	9.17	9.17						
21		N87C196KC-16	INTEL	1	22	22.00					22.00	
22	J-LEAD	74HC138		1	0.24	0.24						
23		LT1081	LINEAR TECHNOLOGY	1	1.63	1.63						
24		74HCT573		3	0.57	1.71						
25		74HCT04		1	0.21	0.21						
26		74HCT32		1	0.68	0.68						
27		MT3-0505SI	VOLGEN	1	23.13	23.13						
28		CTX157-ND	DIGIKEY	1	1.96	1.96						
29		MAX694	MAXIM	1	2.48	2.48						
30		OP490S	ANALOG DEVICES	2	3.85	7.70						
31		HM628128CFP7	HITACHI	1	10.73	10.73						
32		CAPACITORS		TBD	10	10.00						
33		RESISTORS		TBD	5	5.00						
34		22-29-2021	MOLEX	1	0.11	0.11						
35		499206-1	AMP	2	0.58	1.16						
36		499206-6	AMP	1	1.17	1.17						

DELTA GROUP
2105 AZTEC NE
ALBUQUERQUE, NM 87107

1000	PIECE QTY	PART NUMBER	MANUFACTURER	QTY	PRICE	EXTENSION	N	L	A
ITEM					CODE	M			
TOTALS						419.97	2025.00	34.71	22.00
	TOTAL ASSY/W LABOR								454.68
	TOTAL ASSY W/LABOR AND INTEL PROCESSOR								467.51

DISTRIBUTION

18	Leroy Sandoval, Chairman,
State Transportation Authority
New Mexico State Highway &
Transportation Department
P.O. Box 1149
South Building 1
Santa Fe, NM 87504-1149	1	Joyce W. Koeneman
Association of American Railroads
Communications Department
Library, Room 5800
50 F Street, N.W.
Washington, D.C. 20001
1	Jack E. Thompson, Director
New Mexico State Transportation
Authority
P.O. Box 23106
Santa Fe, NM 87502	1	Warren B. Peterson
Association of American Railroads
Transportation Test Center
P.O. Box 11130
Pueblo, CO 81001
2	R. Gordon McKeen, P.E.
Director, Pavement Materials
Research Center
Alliance for Transportation
Research
University of New Mexico
1001 University Blvd., SE
Suite 103
Albuquerque, NM 87106-4342	1	James R. Lundgren
Association of American Railroads
Transportation Test Center
P.O. Box 11130
Pueblo, CO 81001
1	John F. Wagner
Alliance for Transportation
Research
University of New Mexico
1001 University Blvd., SE
Suite 103
Albuquerque, NM 87106-4342	1	Professor Lawrence J. Udell
Center for New Venture Alliance
School of Business and Economics
California State University
Hayward, CA 94542
1	Joseph D. Stever
Amtech Systems Corporation
Technology & Manufacturing
Division
8600 Jefferson Street, N.E.
Albuquerque, NM 87113	1	Charles W. Till
Chevron Chemical Company
6001 Bollinger Canyon Road
San Ramon, CA 94583
		2	Steven E. Klein
Delta Group Inc.
2105 Aztec Road, NE
Albuquerque, NM 87107
		1	Phillip E. Schell
Monsanto
The Chemical Group
800 N. Lindbergh Boulevard
St. Louis, MO 63167

- 1 George W. Muncaster
Motorola Inc.
Strategic Electronics Division
Government Electronics Group
2501 South Price Road
Chandler, AZ 85248-2899
- 1 F. S. Friedman
New Mexico State Highway &
Transportation Department
State Railroad Planning & Projects
P.O. Box 1149
Santa Fe, NM 87504
- 1 Paul W. King
Special Projects Section
Railroad Safety Branch,
Safety Division
State of California
Public Utilities Commission
505 Van Ness Avenue
San Francisco, CA 94102
- 1 William H. Well
Chief, Railroad Safety Branch,
Safety Division
State of California
Public Utilities Commission
1145 Market Street, 2nd Floor
San Francisco, CA 94103
- 1 Ted A. Kauffman
Manager Industrial Development
The Atchison, Topeka and Santa Fe
Railway Company
7412 Jefferson, N.E.
Albuquerque, NM 87109
- 1 William C. Thompson
Director, Engineering Research
Union Pacific Railroad
1415 Dodge Street
Omaha, NE 68179

- 1 Philip J. Daum
Union Tank Car Company
151st Street & Railroad Avenue
East Chicago, IN 46312
- 1 Bruce M. Fine
U.S. Department of Transportation
Federal Railroad Administration
Room 8320A
400 Seventh Street, S.W.
Washington, D.C. 20590
- 1 Jerry Diely
U.S. Department of Transportation
Federal Railroad Administration
400 Seventh Street, S.W.
Washington, D.C. 20590
- 1 Richard C. Hannon, Director of
Hazardous Materials, Planning
and Analysis
U.S. Department of Transportation
Federal Railroad Administration
400 Seventh Street, S.W.
Washington, D.C. 20590
- 1 Robert J. McCown
Director, Technology Development
U.S. Department of Transportation
Federal Railroad Administration
400 Seventh Street, S.W.
Washington, D.C. 20590
- 1 Jolene Molitoris, Administrator
U.S. Department of Transportation
Federal Railroad Administration
400 Seventh Street, S.W.
Washington, D.C. 20590
- 1 Dr. Noah Rifkin, Director for
Transportation Technology
U.S. Department of Transportation
Federal Railroad Administration
400 Seventh Street, S.W.
Washington, D.C. 20590

1	Claire L. Orth Chief, Equipment and Operating Practices, Research Division Office of Research & Development, RDV-32 U.S. Department of Transportation Federal Railroad Administration 400 Seventh Street, S.W. Washington, D.C. 20590	1 MS 0523	Charles F. Gibbon, 1204
		1	0457 Heinz W. Schmitt, 2000
		1	9005 James B. Wright, 2200
		1	9005 William G. Wilson, 2204
		1	9015 Carolyn Pura, 2221
		1	9014 Thomas R. Harrison, 2271
		10	9014 Jim Hogan, 2271
		1	9014 Brad M. Mickelsen, 2271
		2	9014 Jim Mitchell, 2271
2	Professor James D. Brogan University of New Mexico Department of Civil Engineering Albuquerque, NM 87131	1	0309 Roger Zimmerman, 2418
		1	0985 John H. Stichman, 2600
		10	0986 Dan Rey, 2663
		1	0986 Stephen C. Roehrig, 2663
1	Sean P. Bellew Zeneca Ag Products P.O. Box 751 Wilmington, DE 19897	1	1393 John Didlake, 5209
		1	0763 Jayne W. Williams, 5521
		1	0970 James R. Kelsey, 5700
		1	0656 J. Lee Schoeneman, 5749
		1	0755 Arthur E. Verardo, 6612
		1	0717 Glenn F. Hohnstreiter, 6642
		1	0901 Jon Cashwell, 7907
		1	9001 Thomas O. Hunter, 8000
		1	9004 Mim E. John, 8100
		1	9103 Gregory A. Thomas, 8111
		1	9007 Richard C. Wayne, 8400
		1	9407 Mike Hardwick, 8414
		1	0631 William Nickell, 12300
		2	0405 Roger Breeding, 12333
		1	0405 David D. Carlson, 12333
		1	9018 Central Technical Files, 8523-2
		5	0899 Technical Library, 4414
		1	0619 Print Media, 12615
		2	0100 Document Processing, 7613-2 For DOE/OSTI