THE CARNOL SYSTEM FOR METHANOL PRODUCTION AND CO₂ MITIGATION FROM COAL FIRED POWER PLANTS AND THE TRANSPORTATION SECTOR

by
Meyer Steinberg*
Brookhaven National Laboratory
Upton, N.Y. 11973

February 1996

RECEIVED

MAR 05 1996

OSTI

ABSTRACT

The Carnol System consists of methanol production by CO₂ recovered from coal fired power plants and natural gas and the use of the methanol as an alternative automotive fuel. The Carnol process produces hydrogen by the thermal decomposition of natural gas and reacting the hydrogen with CO₂ recovered from the power plant. The carbon produced can be stored or used as a materials commodity. A design and economic evaluation of the process is presented and compared to gasoline as an automotive fuel. An evaluation of the CO₂ emission reduction of the process and system is made and compared to other conventional methanol production processes including the use of biomass feedstock and methanol fuel cell vehicles. The CO₂ for the entire Carnol System using methanol in automotive IC engines can be reduced by 56% compared to conventional system of coal plants and gasoline engines and by as much as 77% CO₂ emission reduction when methanol is used in fuel cells in automotive engines. The Carnol System is shown to be an environmentally attractive and economically viable system connecting the power generation sector with the transportation sector which should warrant further development.

INTRODUCTION

Coal and natural gas are abundant fuels. Because of their physical and chemical properties, coal and natural gas are difficult to handle and utilize in mobile as well as stationary engines. The infrastructure is mainly geared to handle clean liquid fuels. In order to convert coal to liquid fuel, it is generally necessary to increase its H/C ratio either by increasing its hydrogen content or decreasing its carbon content. On the other hand, in order to convert natural gas to liquid fuels it becomes necessary to decrease its hydrogen content. Thus, by coprocessing the hydrogen-rich natural gas with hydrogen deficient coal, it should be possible to produce liquid fuels in an economically attractive manner. For environmental purposes of decreasing CO₂ greenhouse gas emissions, several approaches can be taken. The CO₂ emission from central power stations can be removed, recovered and disposed of in deep ocean⁽¹⁾. Alternatively, carbon can be extracted from coal and natural gas and only the hydrogen-rich fractions can be utilized from both of these fuels to reduce CO₂ emissions while storing the carbon⁽²⁾. Because of its physical properties, carbon is much easier to dispose of either by storage or used as a materials commodity than sequestering CO₂⁽¹⁾. A third alternative CO₂ mitigation method is to utilize the stack gas CO₂ from coal burning plants with hydrogen obtained from natural gas to produce methanol, which is a well-known liquid automotive fuel. In this paper, we describe and evaluate the Carnol process⁽³⁾, which connects the power generation sector with the transportation sector resulting in an overall CO₂ mitigation system.

* This work was performed under the auspices of the U.S. Department of Energy.

THE CARNOL PROCESS

The Carnol Process is composed of three unit operations described in the following.

1. Carbon dioxide is extracted from the stack gases of coal fired power plants using monoethanolamine (MEA) solvent in an absorption-stripping operation. The technology for this operation is well known in the chemical industry for CO₂ recovery and has recently been significantly improved upon for use in extracting CO₂ from power plant stack gases⁽⁴⁾. The power required to recover CO₂ from an integrated coal fired power plant to recover 90% of the CO₂ from the flue gas can be reduced to about 10% of the capacity of the power plant. However, this energy requirement can be reduced to less than 1% when the CO₂ recovery operation is integrated with a methanol synthesis step described in plant 3 below.

2. The hydrogen required to react with CO₂ for producing methanol can be obtained from either of two methods involving natural gas. In the conventional method for producing hydrogen natural gas is reformed with steam.

This process produces CO₂ and, thus, CO₂ emission is increased. However, hydrogen can be produced without CO₂ emission by the non-conventional method of thermally decomposing methane to carbon and hydrogen.

The energy requirement in conducting this process is less than that required by the above conventional process. A fluidized bed reactor has been used to thermally decompose methane and more recently we are attempting to improve reactor design by utilizing a molten metal bath reactor⁽⁵⁾. The carbon is separated and either stored or can be sold in the market as a materials commodity, such as in strengthening rubber for tires. The temperatures required for this operation are 800°C or above and pressures of less than 10 atm and preferably about 1 atm.

3. The third step in the process consists of reacting the hydrogen from step 2 with the CO₂ from step 1 in a conventional gas phase catalytic methanol synthesis reactor.

This is an exothermic reaction so that the heat produced in this operation can be used to recover the CO₂ from the absorption/stripping operation described in step 1, thus reducing the energy required to recover the CO₂ from the power plant to less than 1% of the power plant capacity. This is an advantage compared to the energy cost in terms of derating the power plant when CO₂ is disposed of by pumping into the ocean in which case more than 20% of the power plant capacity is consumed. The gas phase methanol synthesis usually takes place at temperatures of 260°C and pressure of 50 atm using a copper catalyst. The synthesis can also be conducted in the liquid phase by using a slurry zinc catalyst at lower temperature of 120°C and 30 atm of hydrogen pressure.

CARNOL PROCESS DESIGN

A computer process simulation equilibrium model has been developed for the Carnol Process based on the flow sheet shown in Figure 1. A material and energy balance is shown in Table 1 selected from a number of computer runs. This run shows that 112.1 kg of methanol can be produced from 100 kg of natural gas (CH_4) and 171.1 kg CO_2 with a net emission of only 25.8 lbs CO_2 /MMBTU of methanol energy including combustion of the methanol. This is an 85.7% reduction in CO_2 emission compared to the conventional emission from a steam reforming methanol plant which emits 182 lbs CO_2 /MMBTU which includes the CO_2 from combustion of the methanol. The power plant at the same time has a 90% reduction in CO_2 because only 10% of the CO_2 from the MEA solvent absorption plant remains unrecovered and is emitted to the atmosphere.

Methanol As An Automotive Fuel

The Carnol Process can be considered as a viable coal CO_2 mitigation technology because the resulting large production capacity of liquid methanol can be used in the large capacity automotive fuel market. Most processes which utilize CO_2 produce chemical products which tend to swamp the market and thus cannot be used. Methanol as an alternative automotive fuel has been used in internal combustion (IC) engines as a specialty racing car fuel for a long time. More recently, the EPA has shown that methanol can be used in IC engines with reduced CO and HC emissions and at efficiencies exceeding gasoline fuels by 30%. Methanol can also be used either directly or indirectly in fuel cells at several times higher efficiency for automotive use. A great advantage of methanol is that as a liquid it fits in well with the infrastructure of storage and distribution compared to compressed natural gas and gaseous or liquid hydrogen which are being considered as alternative transportation fuels. Compared to gasoline, the CO_2 emission from methanol in IC engines is 40% less.

It should also be pointed out that removal and ocean disposal of CO_2 is only possible for large central power stations. For the dispersed domestic and transportation (industry and automobiles) sectors the Carnol Process provides the capability of CO_2 reduction by supplying liquid methanol fuel to these smaller diverse CO_2 emitting sources.

Economics of Carnol Process

A preliminary economic analysis of the Carnol process has been made based on the following assumptions:

1. 90% recovery of CO_2 from a 900 MW(e) coal fired power plant.
2. Capital investment based on an equivalent 3 step conventional steam reforming plant which amounts to \$100,000/ton MeOH/day⁽⁸⁾.
3. Production cost which includes 19% financing, 1% labor, 3% maintenance, and 2% process catalyst and miscellaneous adding up to a fixed charge of 25% of the capital investment (IC) on an annual basis.
4. Natural gas varies between \$2 and \$3/MSCF.
5. Carbon storage is charged at \$10/ton. Market value for carbon black is as high as \$1000/ton.

6. Methanol market price is \$0.45/gal but has varied historically from \$0.45/gal to \$1.30/gal in the last few years.

At \$18/bbl oil and 90% recovery as gasoline and \$10/bbl for refining cost, gasoline costs \$0.78/gal, and methanol being 30% more efficient than gasoline competes with gasoline at \$0.57/gal methanol.

Table 2 summarizes the economics of production cost factors and income factors for a range of cost conditions. In terms of reducing CO₂ cost from power plants, with \$2/MSCF natural gas, and a \$0.55/gal methanol income CO₂ reduction cost is zero. At \$3/MSCF natural gas and \$0.45/gal income from methanol, the CO₂ disposal cost is \$47.70/ton CO₂, which is less than the maximum estimated for ocean disposal⁽⁷⁾. More interesting, without any credit for CO₂ disposal from the power plant, methanol at \$0.55/gal can compete with gasoline at \$0.76/gal (- \$18/bbl oil) when natural gas is at \$2/MSCF. Any income from carbon makes the economics look even better.

CO₂ Emission Evaluation of Entire Carnol System

Although we can show 90% or more CO₂ emission reduction for the coal fired power plant, the other two parts of the system, methanol production and automotive emissions, have relatively less CO₂ emission reduction compared to conventional systems. Therefore, the entire Carnol System must be evaluated as shown in Figure 2.

Alternative methanol production processes are evaluated in Table 3. The yield of methanol per unit of methane feedstock is shown for 1) conventional process in two parts; A) steam reforming of natural gas process, and B) using CO₂ addition in conventional steam reforming process; 2) Carnol process, in two parts; A) using methane combustion to decompose methane for hydrogen in MDR, and B) hydrogen combustion to decompose the methane in MDR, and 3) a steam gasification of biomass process. The Carnol Process with H₂ and the biomass process (solar energy) reduces CO₂ to zero emission compared to conventional, but with a loss of 35% and 47% methanol yield respectively. The Carnol process when using methane combustion in the decomposer reduces CO₂ emission by 43% while the production yield is only reduced by 26% compared to conventional. The conventional process with CO₂ addition (1B) is interesting because there is an increase of 32% in production although the CO₂ emission is only reduced by 23%.

For purposes of comparison and clarification, the overall stoichiometry for the Carnol Process is shown in the following together with the conventional processes, and with CO₂ addition.

Carnol Process

Conventional Steam Reforming Methane

Conventional Steam Reforming of Methane With CO₂ Addition

It is noted that in the Carnol process a maximum amount of CO₂ is utilized and an excess of carbon is produced. In the conventional process, no CO₂ is used and an excess of hydrogen is produced. With CO₂

addition to the conventional process, no excess of carbon or hydrogen is formed and methanol per unit natural gas is maximized.

Methanol can also be produced using biomass and since the net CO₂ emission is zero with CO₂ being converted to biomass by solar photosynthesis, the biomass process must also be included in the evaluation.

Biomass Steam Gasification Process for Methanol Synthesis

The entire Carnol System is evaluated in table 4 in terms of CO₂ emissions and compared to the alternative methanol processes and to the base line case of conventional coal fired power plant and gasoline driven automotive IC engines. Methanol in fuel cell engine is also evaluated. All the cases are normalized to emissions from 1MMBTU of coal fired power plant which produces CO₂ for a Carnol methanol plant equivalent to 1.27 MMBTU for use in an automotive IC engine. The assumptions made are listed at the bottom of table 4. The conclusions drawn from table 4 are as follows:

1. The use of conventional methanol reduces CO₂ by 13% compared to the gasoline base case and is mainly due to the 30% improved efficiency of the use of methanol in IC engines.

2. By addition of CO₂ recovered from the coal fired power plant to the conventional methanol process, the CO₂ from the power plant is reduced by about 25% (161 lbs/MMBTU compared to 215 lb CO₂/MMBTU) and the CO₂ emissions for the entire system is reduced by 24%. It should be pointed out that the CO₂ can also be obtained from the flue gas of the reformer furnace of the methanol plant and does not need to be obtained from the coal fired plant.

3. The Carnol Process reduced the coal fired power plant CO₂ emission by 90% and the overall system emission is reduced by 56%.

4. Since the use of biomass is a CO₂ neutral feedstock, there is no emission from the power plants because the production of biomass feedstock comes from an equivalent amount of CO₂ in the atmosphere which has been generated from the coal fired power plant. Thus, the only net emission comes only from burning methanol in the automotive IC engine and thus, the CO₂ emission for the entire system is reduced by 57%, only slightly more than the Carnol System. However, the main point is that at present the cost of supplying biomass feedstock is higher than that of natural gas feedstock.

5. Another future system involves the use of fuel cells in automotive vehicles. The efficiency of fuel cells is expected to be 2.5 times greater than gasoline driven engines⁽¹¹⁾. Applying the Carnol process to produce methanol for fuel cell engines reduces the CO₂ emission for the entire system by a maximum of 77%. Furthermore, because of the huge increase in efficiency, the capacity for driving fuel cell engines can be increased by 92% over that for Carnol Process using the same 90% of the CO₂ emissions from the coal burning power plant.

CONCLUSIONS

The Carnol Process can reduce CO₂ emissions from coal fired power plant while producing methanol for automotive IC engines with virtually no derating of the power plant. With natural gas at \$2/MSCF, the

methanol cost appears to be competitive with gasoline for IC engines at \$18/bbl oil. The CO₂ emission for the entire Carnol System is reduced by 56%. Compared to the conventional system, steam reformed natural gas with CO₂ addition from the power plant, reduces CO₂ emissions by only 13%, but can have a higher production capacity per unit natural gas than the Carnol Process. Biomass as a methanol feedstock can reduce CO₂ by 57%. The development of methanol fuel cell engines can reduce CO₂ emissions by 77% for the entire system with a large increase in production capacity. The use of methanol as an automotive fuel produced from coal fired power plant CO₂ emissions and natural gas appears to be an environmentally attractive and economically viable system connecting the power generation sector with the transportation sector and, therefore, should warrant further development effort.

REFERENCES

1. H. Cheng and M. Steinberg, "A System Study for the Removal, Recovery and Disposal of Carbon Dioxide from Fossil Fuel Power Plants in the U.S.," DOE/CH-0016-2 TRO16, U.S. Dept. Of Energy, Washington, D.C. (December 1984).
2. M. Steinberg, "Coal to Methanol to Gasoline by the Hydrocarb Process," BNL 43555, Brookhaven National Laboratory, Upton, N.Y. 11973, (August 1989).
3. M. Steinberg, "The Carnol Process for Methanol Production and Utilization with Reduced CO₂ Emissions" BNL 60575, Brookhaven National Laboratory, Upton, N.Y. 11973, (October 1993).
4. O. Suda, et.al., "Development of Fuel Gas Carbon Dioxide Recovery Technology," Chapter in Carbon Dioxide Chemistry Environment Issues, Eds, T. Paul and C.M. Pradies, pp. 222-35, the Royal Society of Chemistry, Hemovan, Sweden, (1994) and T. Mimura, Kansai Electric Power Co., Osaka, Japan, Private communication, (June 1995).
5. M. Steinberg, "The Carnol Process for CO₂ Mitigation from Power Plants and the Transportation Sector," to be published as EPA report NMRL-RTP-015. USEPA, Research Triangle Park, N.C. 27711, (1996).
6. Motor Vehicle Emissions Laboratory (MVEL), "An Analysis of the Economic and Environmental Effects of Methanol as an Automotive Fuel," EPA report No. 0730, Ann Arbor, Michigan, (Sept. 1989).
7. IEA Greenhouse Gas R and D Programs, "Greenhouse Issues," No. 7, Cheltenham, U.K., (March 1993).
8. J. Korchnak, John Brown Engineers Co., Houston, Texas, Private Communication, (1994).
9. C.E. Wyman, et.al., "Ethanol and Methanol from Cellulosic Biomass," pp. 866-923, in Renewable Energy, Eds., T.B. Johansson, et.al., Island Press, Washington, D.C., (1993).
10. E.D. Larson and R.E. Katofsky, "Production of Hydrogen and Methanol via Biomass Gasification, in Advance in Thermochemical Biomass Conversion," Elsevier Applied Science, London, U.K., (1992).
11. World Car Conference '96, Bourns College of Engineering, Center for Environmental Research and Technology, University of California, Riverside, CA, (Jan. 21-24, 1996).

Table 1
Carnol Process VI Design
Process Simulation - Mass and Energy Balances

UNIT (See Fig. 1)	CARNOL VI MDR and Liquid Phase MSR
<u>MDR</u>	
Pressure, atm	1
Temp. °C	900
CH ₄ Feedstock, Kg	100
Preheat Temp. °C	837
CH ₄ Fuel for MDR, Kg	6.6
CH ₄ Conversion, %	96.3
Carbon Produced, Kg	72.1
Heat Load, Kcal	65,006
Purge Gas from Fuel, Kmol	2.1
<u>MSR - Liquid Phase</u>	
Pressure, atm	50
Temp. °C	120
Recycle Ratio	0.5
CO ₂ Feedstock, Kg	171.1
CO ₂ Conversion, %	90.3
Methanol Prod., Kg	112.1
Water Cond., Kg	63.2
<u>Energy for Gas Compression to MSR</u>	
Primary, Kcal	53,306
Secondary for Recycle, Kcal	694
<u>Performance</u>	
Ratio MeOH/CH ₄ , Kg/Kg	1.12
Carbon Efficiency, MeOH, %	56.0
Thermal Eff., MeOH, %	42.9
Thermal Eff., C+MeOH, %	85.7
CO ₂ Emission Lbs/MMBTU	25.8
Co ₂ Emission Kg/GJ	11.1

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Table 2
ADVANCED CARNOL VI PRELIMINARY PROCESS ECONOMICS

Plant Size - To Process 90% Recovery of CO₂ from 900 MW(e) Nominal Coal Fired Power Plant

90% Plant Factor, CO₂ Rate = 611 T/Hr. = 4.82×10^6 Tons CO₂/Yr.

Feedstock: Natural Gas Rate = 2.82×10^6 T/Yr. = 407,000 MSCF/D

Carbon Production = 2.03×10^6 T/Yr.

Methanol Production = 3.16×10^6 T/Yr. = 69,300 Bbl/D

Plant Capital Investment (IC) = 9607 T/D $\times$ \$10⁵ = \$961 $\times$ 10⁶

Production Cost Factors							=	Income Factors				
0.25 IC	Natural Gas		C Storage		CO ₂ Cost		C Income		MeOH Income		Cost for Reducing CO ₂	
\$10 ⁸ /Yr	\$10 ⁸ /Yr	(\$/MSCF)	\$10 ⁸ /Yr	(\$/Ton)	\$10 ⁸ /Yr	(\$/Ton)	\$10 ⁸ /Yr	(\$/Ton)	\$10 ⁸ /Yr	(\$/Gal)	\$10 ⁸ /Yr	(\$/Ton)
2.40	2.67	(2)	0.20	(10)	0	(0)	0	(0)	5.27	(0.55)	0	(0)
2.40	4.00	(3)	0.20	(10)	0	(0)	0	(0)	5.27	(0.55)	-1.34	(-27.60)
2.40	2.67	(2)	0.20	(10)	0	(0)	0	(0)	5.27	(0.55)	0	(0)
2.40	4.00	(3)	0	(0)	0	(0)	1.13	(55.60)	5.27	(0.55)	0	(0)
2.40	2.67	(2)	0.20	(10)	0	(0)	0	(0)	4.30	(0.45)	-0.97	(-20.00)
2.40	2.67	(2)	0	(0)	0	(0)	0.77	(37.90)	4.30	(0.45)	0	(0)
2.40	4.00	(3)	0.20	(10)	0	(0)	0	(0)	4.30	(0.45)	-2.30	(-47.70)
2.40	4.00	(3)	0	(0)	0	(0)	2.10	(103.00)	4.30	(0.45)	(0)	(0)

Table 3
METHANOL PRODUCTION AND CO₂ EMISSION
PROCESS COMPARISON

PROCESS	PRODUCTION YIELD		CO ₂ EMISSION ⁽⁴⁾	
	<u>Moles MeOH</u> Mole Feedstock	% Reduction from Conventional	<u>Lbs CO₂</u> MMBTU (MeOH)	% Reduction from Conventional
1A Conventional Process Steam Reforming of CH ₄	0.76 ⁽¹⁾	0%	44	0%
1B Conventional Process with CO ₂ Addition	1.00	(32%) ⁽²⁾	34	23%
2A Carnol Process Heating MDR with CH ₄	0.56	26%	25	43%
2B Carnol Process Heating MDR with H ₂	0.50	35%	0	100%
3 Steam Gasification of Biomass	0.40 ⁽³⁾	47%	43	100%

- (1) Based on thermal efficiency of 64% (Ref. 9).
(2) This represents a 32% increase in yield vs conventional.
(3) Based on BCL process (Ref. 10).
(4) CO₂ emission only from fuel production plant.

**Table 4 CO₂ EMISSION COMPARISON FOR SYSTEMS CONSISTING OF
COAL FIRED POWER PLANT, FUEL PROCESS PLANT AND AUTOMOTIVE POWER PLANT**

Basis: 1 MMBTU for coal fired 900 MW(e) power plant

1.27 MMBTU of liquid fuel for IC engine - other fuel efficiencies proportions energy up and down

CO₂ Emission units in Lbs CO₂/MMBTU (multiply by 0.43 for KG/GJ)

System Unit	Coal Fired Power Plant	Fuel Process Plant	IC Automotive Power Plant	Total System Emission	CO ₂ Emission Reduction
Baseline Case: Coal Fired Power Plant and Gasoline Driven IC Engine	215	15	285	515	0%
Case 1A Coal Fired Power Plant With Conventional Steam Reformed Methanol Plant	215	56	175 ⁽²⁾	448	13%
Case 1B Coal Fired Power Plant With CO ₂ Addition to Conventional Methanol Plant	161 ⁽⁴⁾	54	175	390	24%
Case 2 Coal Fired Power Plant with CARNOL Process Methanol Plant	21 ⁽¹⁾	32	175	228	56%
Case 3 Coal Fired Power Plant with Biomass for Methanol Plant	0	43	175	219	57%
Case 4 Coal Fired Power Plant with CARNOL Methanol and Fuel Cell Automotive Power	11 ⁽⁵⁾	17	Fuel Cell 89 ⁽³⁾	117	77%

1) 90% recovery of CO₂ from coal fired plant,

3) Fuel cell as 2.5 times more efficient than conventional gasoline IC engine.

5) Only 52% emissions of coal plant CO₂ is assigned to Carnol for fuel cells

2) Methanol is 30% more efficient than gasoline in IC engines,

4) Only 25% recovery of CO₂ from coal plant is necessary for supply CO₂ to conventional methanol plant.

Figure 1
Carnol VI Process
Methanol Production From Power Plant CO₂ and Natural Gas
Process Simulation

Figure 2

CARNOL System Configuration For CO₂ Emission Mitigation