Columbia River System Operation Review

Final Environmental Impact Statement

RECEIVED
JAN 30 1996
OSTI

Appendix J Recreation

MASTER

US Army Corps
of Engineers
North Pacific Division

DOE/EIS-0170-App. J

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

November 1995

PUBLIC INVOLVEMENT IN THE SOR PROCESS

The Bureau of Reclamation, Corps of Engineers, and Bonneville Power Administration wish to thank those who reviewed the Columbia River System Operation Review (SOR) Draft EIS and appendices for their comments. Your comments have provided valuable public, agency, and tribal input to the SOR NEPA process. Throughout the SOR, we have made a continuing effort to keep the public informed and involved.

Fourteen public scoping meetings were held in 1990. A series of public roundtables was conducted in November 1991 to provide an update on the status of SOR studies. The lead agencies went back to most of the 14 communities in 1992 with 10 initial system operating strategies developed from the screening process. From those meetings and other consultations, seven SOS alternatives (with options) were developed and subjected to full-scale analysis. The analysis results were presented in the Draft EIS released in July 1994. The lead agencies also developed alternatives for the other proposed SOR actions, including a Columbia River Regional Forum for assisting in the determination of future SOSs, Pacific Northwest Coordination Agreement alternatives for power coordination, and Canadian Entitlement Allocation Agreements alternatives. A series of nine public meetings was held in September and October 1994 to present the Draft EIS and appendices and solicit public input on the SOR. The lead agencies received 282 formal written comments. Your comments have been used to revise and shape the alternatives presented in the Final EIS.

Regular newsletters on the progress of the SOR have been issued. Since 1990, 20 issues of *Streamline* have been sent to individuals, agencies, organizations, and tribes in the region on a mailing list of over 5,000. Several special publications explaining various aspects of the study have also been prepared and mailed to those on the mailing list. Those include:

- The Columbia River: A System Under Stress
- The Columbia River System: The Inside Story
- Screening Analysis: A Summary
- Screening Analysis: Volumes 1 and 2
- Power System Coordination: A Guide to the Pacific Northwest Coordination Agreement
- Modeling the System: How Computers are Used in Columbia River Planning
- Daily/Hourly Hydrosystem Operation: How the Columbia River System Responds to Short-Term Needs

Copies of these documents, the Final EIS, and other appendices can be obtained from any of the lead agencies, or from libraries in your area.

Your questions and comments on these documents should be addressed to:

SOR Interagency Team
P.O. Box 2988
Portland, OR 97208-2988

PREFACE: SETTING THE STAGE FOR THE SYSTEM OPERATION REVIEW

WHAT IS THE SOR AND WHY IS IT BEING CONDUCTED?

The Columbia River System is a vast and complex combination of Federal and non-Federal facilities used for many purposes including power production, irrigation, navigation, flood control, recreation, fish and wildlife habitat and municipal and industrial water supply. Each river use competes for the limited water resources in the Columbia River Basin.

To date, responsibility for managing these river uses has been shared by a number of Federal, state, and local agencies. Operation of the Federal Columbia River system is the responsibility of the Bureau of Reclamation (Reclamation), Corps of Engineers (Corps) and Bonneville Power Administration (BPA).

The System Operation Review (SOR) is a study and environmental compliance process being used by the three Federal agencies to analyze future operations of the system and river use issues. The goal of the SOR is to achieve a coordinated system operation strategy for the river that better meets the needs of all river users. The SOR began in early 1990, prior to the filing of petitions for endangered status for several salmon species under the Endangered Species Act.

The comprehensive review of Columbia River operations encompassed by the SOR was prompted by the need for Federal decisions to (1) develop a coordinated system operating strategy (SOS) for managing the multiple uses of the system into the 21st century; (2) provide interested parties with a continuing and increased long-term role in system planning (Columbia River Regional Forum); (3) renegotiate and renew the Pacific Northwest Coordination Agreement (PNCA), a contractual arrangement among the region's major hydroelectric-generating utilities and affected Federal agencies to provide for coordinated power generation on the Columbia River system; and (4) renew or develop

new Canadian Entitlement Allocation Agreements (contracts that divide Canada's share of Columbia River Treaty downstream power benefits and obligations among three participating public utility districts and BPA). The review provides the environmental analysis required by the National Environmental Policy Act (NEPA).

This technical appendix addresses only the effects of alternative system operating strategies for managing the Columbia River system. The environmental impact statement (EIS) itself and some of the other appendices present analyses of the alternative approaches to the other three decisions considered as part of the SOR.

WHO IS CONDUCTING THE SOR?

The SOR is a joint project of Reclamation, the Corps, and BPA—the three agencies that share responsibility and legal authority for managing the Federal Columbia River System. The National Marine Fisheries Service (NMFS), U.S. Fish and Wildlife Service (USFWS), and National Park Service (NPS), as agencies with both jurisdiction and expertise with regard to some aspects of the SOR, are cooperating agencies. They contribute information, analysis, and recommendations where appropriate. The U.S. Forest Service (USFS) was also a cooperating agency, but asked to be removed from that role in 1994 after assessing its role and the press of other activities.

HOW IS THE SOR BEING CONDUCTED?

The system operating strategies analyzed in the SOR could have significant environmental impacts. The study team developed a three-stage process—scoping, screening, and full-scale analysis of the strategies—to address the many issues relevant to the SOR.

At the core of the analysis are 10 work groups. The work groups include members of the lead and cooperating agencies, state and local government agencies, representatives of Indian tribes, and members

of the public. Each of these work groups has a single river use (resource) to consider.

Early in the process during the screening phase, the 10 work groups were asked to develop an alternative for project and system operations that would provide the greatest benefit to their river use, and one or more alternatives that, while not ideal, would provide an acceptable environment for their river use. Some groups responded with alternatives that were evaluated in this early phase and, to some extent, influenced the alternatives evaluated in the Draft and Final EIS. Additional alternatives came from scoping for the SOR and from other institutional sources within the region. The screening analysis studied 90 system operation alternatives.

Other work groups were subsequently formed to provide projectwide analysis, such as economics, river operation simulation, and public involvement.

The three-phase analysis process is described briefly below.

- **Scoping/Pilot Study**—After holding public meetings in 14 cities around the region, and coordinating with local, state, and Federal agencies and Indian tribes, the lead agencies established the geographic and jurisdictional scope of the study and defined the issues that would drive the EIS. The geographic area for the study is the Columbia River Basin (Figure P-1). The jurisdictional scope of the SOR encompasses the 14 Federal projects on the Columbia and lower Snake Rivers that are operated by the Corps and Reclamation and coordinated for hydropower under the PNCA. BPA markets the power produced at these facilities. A pilot study examining three alternatives in four river resource areas was completed to test the decision analysis method proposed for use in the SOR.
- **Screening**—Work groups, involving regional experts and Federal agency staff, were

created for 10 resource areas and several support functions. The work groups developed computer screening models and applied them to the 90 alternatives identified during screening. They compared the impacts to a baseline operating year—1992—and ranked each alternative according to its impact on their resource or river use. The lead agencies reviewed the results with the public in a series of regional meetings in September 1992.

- **Full-Scale Analysis**—Based on public comment received on the screening results, the study team sorted, categorized, and blended the alternatives into seven basic types of operating strategies. These alternative strategies, which have multiple options, were then subjected to detailed impact analysis. Twenty-one possible options were evaluated. Results and tradeoffs for each resource or river use were discussed in separate technical appendices and summarized in the Draft EIS. Public review and comment on the Draft EIS was conducted during the summer and fall of 1994. The lead agencies adjusted the alternatives based on the comments, eliminating a few options and substituting new options, and reevaluated them during the past 8 months. Results are summarized in the Final EIS.

Alternatives for the Pacific Northwest Coordination Agreement (PNCA), the Columbia River Regional Forum (Forum), and the Canadian Entitlement Allocation Agreements (CEAA) did not use the three-stage process described above. The environmental impacts from the PNCA and CEAA were not significant and there were no anticipated impacts from the Regional Forum. The procedures used to analyze alternatives for these actions are described in their respective technical appendices.

For detailed information on alternatives presented in the Draft EIS, refer to that document and its appendices.

WHAT SOS ALTERNATIVES ARE CONSIDERED IN THE FINAL EIS?

Seven alternative System Operating Strategies (SOS) were considered in the Draft EIS. Each of the seven SOSs contained several options bringing the total number of alternatives considered to 21. Based on review of the Draft EIS and corresponding adjustments, the agencies have identified 7 operating strategies that are evaluated in this Final EIS. Accounting for options, a total of 13 alternatives is now under consideration. Six of the alternatives remain unchanged from the specific options considered in the Draft EIS. One is a revision to a previously considered alternative, and the rest represent replacement or new alternatives. The basic categories of SOSs and the numbering convention remains the same as was used in the Draft EIS. However, because some of the alternatives have been dropped, the numbering of the final SOSs are not consecutive. There is one new SOS category, Settlement Discussion Alternatives, which is labeled SOS 9 and replaces the SOS 7 category. This category of alternatives arose as a consequence of litigation on the 1993 Biological Opinion and ESA Consultation for 1995.

The 13 system operating strategies for the Federal Columbia River system that are analyzed for the Final EIS are:

SOS 1a Pre Salmon Summit Operation represents operations as they existed from around 1983 through the 1990–91 operating year, prior to the ESA listing of three species of salmon as endangered or threatened.

SOS 1b Optimum Load–Following Operation represents operations as they existed prior to changes resulting from the Regional Act. It attempts to optimize the load–following capability of the system within certain constraints of reservoir operation.

SOS 2c Current Operation/No–Action Alternative represents an operation consistent with that specified in the Corps of Engineers' 1993 Supplemental EIS. It is similar to system operation that occurred

in 1992 after three species of salmon were listed under ESA.

SOS 2d [New] 1994–98 Biological Opinion represents the 1994–98 Biological Opinion operation that includes up to 4 MAF flow augmentation on the Columbia, flow targets at McNary and Lower Granite, specific volume releases from Dworshak, Brownlee, and the Upper Snake, meeting sturgeon flows 3 out of 10 years, and operating lower Snake projects at MOP and John Day at MIP.

SOS 4c [Rev.] Stable Storage Operation with Modified Grand Coulee Flood Control attempts to achieve specific monthly elevation targets year round that improve the environmental conditions at storage projects for recreation, resident fish, and wildlife. Integrated Rules Curves (IRCs) at Libby and Hungry Horse are applied.

SOS 5b Natural River Operation draws down the four lower Snake River projects to near river bed levels for four and one–half months during the spring and summer salmon migration period, by assuming new low level outlets are constructed at each project.

SOS 5c [New] Permanent Natural River Operation operates the four lower Snake River projects to near river bed levels year round.

SOS 6b Fixed Drawdown Operation draws down the four lower Snake River projects to near spillway crest levels for four and one–half months during the spring and summer salmon migration period.

SOS 6d Lower Granite Drawdown Operation draws down Lower Granite project only to near spillway crest level for four and one–half months.

SOS 9a [New] Detailed Fishery Operating Plan includes flow targets at The Dalles based on the previous year's end–of–year storage content, specific volumes of releases for the Snake River, the drawdown of Lower Snake River projects to near spillway crest level for four and one–half months, specified spill percentages, and no fish transportation.

SOS 9b [New] Adaptive Management establishes flow targets at McNary and Lower Granite based on runoff forecasts, with specific volumes of releases to meet Lower Granite flow targets and specific spill percentages at run-of-river projects.

SOS 9c [New] Balanced Impacts Operation draws down the four lower Snake River projects near spillway crest levels for two and one-half months during the spring salmon migration period. Refill begins after July 15. This alternative also provides 1994–98 Biological Opinion flow augmentation, integrated rule curve operation at Libby and Hungry Horse, a reduced flow target at Lower Granite due to drawdown, winter drawup at Albeni Falls, and spill to achieve no higher than 120 percent daily average for total dissolved gas.

SOS PA Preferred Alternative represents the operation proposed by NMFS and USFWS in their Biological Opinions for 1995 and future years; this SOS operates the storage projects to meet flood control rule curves in the fall and winter in order to meet spring and summer flow targets for Lower Granite and McNary, and includes summer draft limits for the storage projects.

WHAT DO THE TECHNICAL APPENDICES COVER?

This technical appendix is 1 of 20 prepared for the SOR. They are:

- A. River Operation Simulation
- B. Air Quality
- C. Anadromous Fish & Juvenile Fish Transportation
- D. Cultural Resources
- E. Flood Control
- F. Irrigation/Municipal and Industrial Water Supply
- G. Land Use and Development
- H. Navigation

- I. Power
- J. Recreation
- K. Resident Fish
- L. Soils, Geology, and Groundwater
- M. Water Quality
- N. Wildlife
- O. Economic and Social Impacts
- P. Canadian Entitlement Allocation Agreements
- Q. Columbia River Regional Forum
- R. Pacific Northwest Coordination Agreement
- S. U. S. Fish and Wildlife Service Coordination Act Report
- T. Comments and Responses

Each appendix presents a detailed description of the work group's analysis of alternatives, from the scoping process through full-scale analysis. Several appendices address specific SOR functions (e.g., River Operation Simulation), rather than individual resources, or the institutional alternatives (e.g., PNCA) being considered within the SOR. The technical appendices provide the basis for developing and analyzing alternative system operating strategies in the EIS. The EIS presents an integrated review of the vast wealth of information contained in the appendices, with a focus on key issues and impacts. In addition, the three agencies have prepared a brief summary of the EIS to highlight issues critical to decision makers and the public.

There are many interrelationships among the different resources and river uses, and some of the appendices provide supporting data for analyses presented in other appendices. This Recreation appendix relies on supporting data contained in Appendices C, K, N, and O. For complete coverage of all aspects of recreation, readers may wish to review all five appendices in concert.

Figure P-1. Projects in the System Operation Review.

1 million acre feet = 1.234 billion cubic meters
 1 cubic foot per second = 0.028 cubic meters per second

TABLE OF CONTENTS

<u>Chapter/Para</u>	<u>Page</u>
xix LIST OF ACRONYMS	xix
1 RECREATION STUDIES SCOPE AND PROCESSES	1-1
1.1 THE SOR RECREATION WORK GROUP	1-1
1.1.1 Objectives	1-1
1.1.2 Formation	1-1
1.1.3 Participants	1-2
1.1.4 Coordination With Other Work Groups	1-3
1.2 PUBLIC INVOLVEMENT AND AGENCY COORDINATION	1-4
1.2.1 Objectives	1-4
1.2.2 Key Publics	1-4
1.2.3 Public Meetings	1-4
1.3 RECREATION ISSUES AND CONCERNS RAISED DURING SCOPING	1-6
1.3.1 Overview	1-6
1.3.2 General Issues	1-6
1.3.3 Site-specific Issues	1-6
1.4 GEOGRAPHIC SCOPE OF RECREATION STUDIES	1-8
1.4.1 Federal Projects	1-8
1.4.2 Downstream River Reaches	1-8
1.4.3 Non-Federal Projects	1-9
1.5 RECREATION PILOT MODELS	1-9
1.6 SCREENING PROCESS	1-9
1.6.1 General	1-9
1.6.2 Recreation Optimization Alternatives	1-9
1.6.3 Summary of Screening Evaluations	1-11
1.6.4 Participation in Development of SOS 4c: Enhanced Storage Operations	1-12
1.7 FULL-SCALE ANALYSIS	1-12
1.7.1 Description of Existing Conditions	1-12
1.7.2 Recreation Impact Assessment	1-13
1.7.3 Recreation Mitigation	1-14
2 RECREATION IN THE COLUMBIA RIVER BASIN TODAY	2-1
2.1 GENERAL OVERVIEW	2-1
2.2 RECREATION OPPORTUNITIES AT DIFFERENT TYPES OF SYSTEM ELEMENTS	2-2
2.2.1 Free Flowing Rivers and Streams	2-2
2.2.2 Storage Projects	2-2

TABLE OF CONTENTS

Recreation Appendix

TABLE OF CONTENTS – CONT

<u>Chapter/Para</u>		<u>Page</u>
2.2.3	Run-of-River Projects	2-3
2.2.4	Controlled Downstream River Reaches	2-4
2.3	RECREATION PARTICIPATION ALONG THE COLUMBIA RIVER AND TRIBUTARIES	2-4
2.3.1	Visitation Estimates	2-4
2.3.2	Major Activities and Use Areas	2-5
2.3.3	Future Recreation Demand	2-9
2.4	RECREATIONAL USER CHARACTERISTICS; RESULTS OF PHASE IA SURVEY	2-10
2.4.1	Participation Rates in Water-Based Recreation	2-11
2.4.2	Characteristics of Non-Recreators	2-12
2.4.3	Participation Rates in Specific Activities	2-13
2.4.4	Federal Project Visitation	2-14
2.4.5	Substitution Across Projects	2-17
2.4.6	Recreator Attitudes	2-18
2.4.7	Conclusions	2-20
2.5	FACTORS INFLUENCING RECREATIONAL USE IN THE COLUMBIA BASIN	2-21
2.5.1	Seasonality of Visitor Use	2-21
2.5.2	Accessibility to Water	2-22
2.5.3	Water-Surface Area (Recreational Carrying Capacity)	2-25
2.5.4	Recreational Safety Hazards	2-25
2.5.5	Other Physical Effects	2-28
2.5.6	Water Quality	2-28
2.5.7	Fishing Success	2-30
2.5.8	Wildlife Hunting and Viewing Opportunities	2-31
2.5.9	Aesthetic Quality	2-31
2.5.10	Summary: Influence of System Operations on Recreation	2-31
2.6	MANAGING AGENCIES/ENTITIES ROLES AND RESPONSIBILITIES	2-32
2.6.1	Federal Agencies	2-33
2.6.2	Oregon State Agencies	2-35
2.6.3	Washington State Agencies	2-35
2.6.4	Idaho State Agencies	2-36
2.6.5	Public Utility Districts	2-36
2.6.6	Native American Indian Tribes	2-36

TABLE OF CONTENTS – CONT

<u>Chapter/Para</u>		<u>Page</u>
2.7	RIVER REACH OR SUBBASIN DESCRIPTIONS	2-36
2.7.1	Kootenai River (Libby Project/Lake Koocanusa and Kootenai River downstream)	2-37
2.7.2	Upper Columbia Reach (Canada above Grand Coulee to Hugh Keenleyside Dam)	2-45
2.7.3	Flathead River Subregion (Hungry Horse Project, Flathead River, and Flathead Lake)	2-50
2.7.4	Grand Coulee (Lake Roosevelt) Subregion	2-57
2.7.5	Albeni Falls (Lake Pend Oreille)	2-63
2.7.6	Middle Columbia River (Chief Joseph and PUD Projects)	2-69
2.7.7	Middle Snake River (Brownlee, Hells Canyon, and Oxbow Projects and the Snake River through Hells Canyon)	2-78
2.7.8	Clearwater River (Dworshak Project and Clearwater River Downstream)	2-85
2.7.9	Lower Snake River Subregion (Ice Harbor, Lower Monumental, Little Goose, and Lower Granite Projects)	2-91
2.7.10	Lower Columbia River Subregion (McNary, The Dalles, John Day, and Bonneville Projects, and Columbia River below Bonneville Dam)	2-98
3	RECREATION ANALYSIS PROCEDURES AND METHODOLOGY	3-1
3.1	INTRODUCTION	3-1
3.2	PUBLIC ISSUES AND CONCERNS	3-1
3.3	CONCEPTUAL FRAMEWORK	3-2
3.4	ANALYTICAL SCOPE FOR DRAFT EIS	3-2
3.4.1	Model Development	3-2
3.4.2	Methodological Assumptions	3-4
3.4.3	Sensitivity and Probability Analysis	3-6
3.4.4	Screening Analysis	3-6
3.4.5	Full-scale Analyses for Draft EIS	3-8
3.5	TRANSITION FROM DRAFT TO FINAL EIS MODEL	3-9
3.6	FINAL EIS RECREATION DEMAND MODEL	3-11
3.6.1	General Theory	3-11
3.6.2	Actual Behavior Model	3-11
3.6.3	Contingent Behavior Model	3-12
3.6.4	Predicting Future Demand	3-13
3.6.5	Estimating Recreation Values	3-13

TABLE OF CONTENTS – CONT

<u>Chapter/Para</u>		<u>Page</u>
3.7	DATA SOURCES AND ASSUMPTIONS	3-13
3.7.1	Corps of Engineers	3-13
3.7.2	Bureau of Reclamation/National Park Service/U.S. Forest Service	3-16
3.7.3	Mid Columbia Public Utility District River Projects	3-16
3.7.4	Clearwater River Below Dworshak Dam	3-17
3.7.5	Hells Canyon National Recreation Area	3-17
3.7.6	Columbia River – Hugh Keenlyside Dam to International Boundary	3-17
4	ALTERNATIVES AND THEIR IMPACTS	4-1
4.1	GENERAL DESCRIPTION OF ALTERNATIVES	4-1
4.1.1	SOS 1-Pre-ESA Operation	4-14
4.1.2	SOS 2-Current Operations	4-14
4.1.3	SOS 4-Stable Storage Project Operation	4-15
4.1.4	SOS 5-Natural River Operation	4-15
4.1.5	SOS 6-Fixed Drawdown	4-15
4.1.6	SOS 9-Settlement Discussion Alternatives	4-16
4.1.7	SOS PA-Preferred Alternative	4-16
4.1.8	Rationale for Selection of the Final SOSs	4-17
4.2	IMPACTS OF THE ALTERNATIVES (BY PROJECT/RIVER REACH)	4-20
4.2.1	General Overview	4-20
4.2.2	Libby Project/Lake Koocanusa	4-23
4.2.3	Kootenai River Below Libby Dam	4-30
4.2.4	Columbia River In Canada	4-38
4.2.5	Hungry Horse Reservoir	4-47
4.2.6	Albeni Falls Project/Lake Pend Oreille	4-56
4.2.7	Grand Coulee Project/Lake Roosevelt	4-63
4.2.8	Chief Joseph Project/Rufus Woods Lake	4-73
4.2.9	Middle Columbia River Public Utility District Projects	4-75
4.2.10	Hanford Reach	4-78
4.2.11	Snake River: Hells Canyon Reach	4-80
4.2.12	Dworshak Dam and Lake	4-88
4.2.13	Clearwater River Below Dworshak Dam	4-97
4.2.14	Lower Granite Lock and Dam – Lower Granite Lake	4-103
4.2.15	Ice Harbor Lock and Dam/Lake Sacajawea, Lower Monumental Lock and Dam/Lake West, and Little Goose Lock and Dam/Lake Bryan	4-110

TABLE OF CONTENTS – CONT

<u>Chapter/Para</u>		<u>Page</u>
4.2.16	McNary Lock and Dam/Lake Wallula	4-123
4.2.17	John Day Project/Lake Umatilla	4-124
4.2.18	The Dalles Project (Lake Celilo)	4-141
4.2.19	Bonneville Project/Lake Bonneville	4-146
4.2.20	Columbia River Below Bonneville Dam	4-151
5	COMPARISON OF ALTERNATIVES	5-1
5.1	SYSTEM-WIDE VISITATION COMPARISON	5-1
5.1.1	Average Water Conditions	5-1
5.1.2	Low-Water Conditions	5-6
5.1.3	High-Water Conditions	5-6
5.2	VISITATION RELATIVE TO BASELINE CONDITIONS	5-7
5.2.1	Comparison to SOS 1a	5-7
5.2.2	Comparison to SOS 2c	5-15
5.3	KEY TRADEOFF RELATIONSHIPS	5-16
5.3.1	Sensitivity of Aggregate Visitation	5-16
5.3.2	Key Factors in Determining Visitation Levels	5-16
5.3.3	Project or Resource-Specific Observations	5-17
5.4	MITIGATION	5-18
5.4.1	General Types of Recreation Mitigation	5-18
5.4.2	Recommended Recreation Mitigation Plan for the Preferred Alternative	5-19
6	LIST OF PREPARERS	6-1
7	REFERENCES	7-1
A	RECREATION WORK GROUP	A-1
A.1	TIER 1 PARTICIPANTS	A-1
A.2	TIER 2 PARTICIPANTS	A-1
B	GLOSSARY OF TERMS AND ACRONYMS	B-1
C	DRAFT EIS RECREATION MODEL	C-1
C.1	Methodology	C-1
C.2	Sources and Assumptions	C-2
C.2.1	Hungry Horse – Hungry Horse Lake:	C-3
C.2.2	Libby – Lake Koocanusa:	C-3
C.2.3	Libby – Kootenai River:	C-3

TABLE OF CONTENTS

Recreation Appendix

TABLE OF CONTENTS – CONT

<u>Chapter/Para</u>		<u>Page</u>
C.2.4	Albeni Falls – Lake Pend Oreille	C-4
C.2.5	Chief Joseph – Rufus Woods Lake:	C-4
C.2.6	Grand Coulee – Lake Roosevelt:	C-4
C.2.7	Dworshak/Dworshak Lake – Lower Clearwater River:	C-4
C.2.8	Lower Snake River Projects:	C-5
C.2.9	Lower Columbia River Projects:	C-5
C.2.10	Columbia River – Hugh Keenlyside Dam to International Boundary	C-5
D	BREAK POINT TABLES	D-1

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
2-1	Summary of Historic Recreation Visitation to Columbia River Basin Reservoirs and Rivers, 1987 – 1993	2-5
2-2	Percent of Visitor Participation by Activity, 1991	2-6
2-3	Estimated Future Recreation Demand in the Columbia River Basin (Oregon, Washington and Idaho)	2-10
2-4	Phase IA Survey Participation Rates for Water Based Recreation	2-12
2-5	Phase IA Survey Participants Reasons for Not Participating in Water Based Recreation	2-12
2-6	Phase IA Survey: Demographic Characteristics of Recreators and Non-Recreators	2-13
2-7	Phase IA Survey: Number of Recreators Taking Trips by Activity	2-14
2-8	Phase IA Survey: Average Number of Trips by Activity	2-15
2-9	Phase IA Survey; Participation at Federal Projects for the 565 Participants in Water Based Recreation	2-16
2-10	Phase IA Survey: Number of Households Visiting Each Project by State/Province	2-16
2-12	Attitudes About Importance of Recreation Site Features (All Numbers are Percentages) ..	2-19
2-13	Seasonality of Columbia River Recreation Use, 1989	2-21
2-14	Existing Recreation Sites and Facilities Lake Koocanusa and Kootenai River	2-42
2-15	Lake Koocanusa/Kootenai River visitation summary, 1987-1993	2-43
2-16	Existing Recreation Sites and Facilities in the Upper Columbia Reach	2-47
2-17	Person Day Estimate Of Recreational Activity In The Upper Columbia Reach	2-50
2-18	Hungry Horse Reservoir Recreation Facilities	2-54

LIST OF TABLES – CONT

<u>Table</u>	<u>Title</u>	<u>Page</u>
2-19	Hungry Horse Lake Visitation Summary, 1987 – 1993	2-55
2-20	Lake Roosevelt Visitation Summary, 1987 – 1993	2-58
2-21	Lake Roosevelt Recreation Facilities	2-61
2-22	Existing Recreation Sites and Facilities, Lake Pend Oreille Subregion	2-67
2-23	Lake Pend Oreille Visitation Summary, 1987-1993	2-68
2-24	Existing Recreation Sites and Facilities, Middle Columbia River	2-75
2-25	Middle Columbia River Visitation Summary, 1987-1993	2-77
2-26	Recreation Facilities, Hells Canyon National Recreation Area	2-83
2-27	Hells Canyon National Recreation Area Visitation Summary, 1987-1991	2-85
2-28	Dworshak Lake Recreation Sites and Facilities	2-89
2-29	Dworshak Lake Visitation Summary, 1987-1991	2-90
2-30	Lower Snake River Recreation Facilities	2-94
2-31	Lower Snake River Visitation Summary; 1987-1993	2-96
2-32	Lower Columbia River Recreation Sites and Facilities	2-106
2-33	Lower Columbia River Visitation Summary, 1987-1993	2-109
4-1	System Operating Strategy Alternatives	4-2
4-2	Summary of Alternatives in the Draft and Final EIS	4-18
4-3	Lake Koocanusa Predicted Summer End-of-Month Pool Elevations for Low, Average and High Water Years	4-23
4-4	Lake Koocanusa, Estimated Recreation Days by Activity	4-24
4-5	Lake Koocanusa, Estimated Total Recreation Days Under Alternative SOSs	4-26
4-6	Average Monthly Kootenai River Flows (KCFS) During Summer Under Alternative SOSs	4-31
4-7	Kootenai River, Estimated Total Annual Recreation Days Under Alternative SOSs	4-32
4-8	Upper Columbia River, Canada -- Average Monthly Outflows (KCFS) for Alternative SOSs (Combined Releases from Keenleyside and Brilliant Dams)	4-38
4-9	Upper Columbia River, Canada, Estimated Annual Recreation Days by Activity	4-41
4-10	Estimated Total Annual Recreation Days and Percent Change from No Action (2c) and Base Case (1a) SOSs, Upper Columbia River, Canada	4-43
4-11	Hungry Horse Reservoir -- Average Monthly Pool Elevations	4-47
4-12	Hungry Horse Reservoir -- Percent Probability of Refill to Selected Pool Elevations	4-48
4-13	Hungry Horse Reservoir, Estimated Annual Recreation Days by Activity Under Alternative SOSs	4-49

TABLE OF CONTENTS

Recreation Appendix

LIST OF TABLES – CONT

<u>Table</u>	<u>Title</u>	<u>Page</u>
4-14	Hungry Horse Reservoir, Estimated Total Annual Recreation Days Under Alternative SOSs	4-51
4-15	Lake Pend Oreille -- Monthly Pool Elevations for Low, Average and High Water Years Under Alternative SOSs	4-56
4-16	Lake Pend Oreille, Estimated Recreation Days by Activity for Alternative SOSs	4-57
4-17	Lake Pend Oreille, Estimated Total Recreation Days for Alternative SOSs	4-59
4-18	Grand Coulee Dam/Lake Roosevelt -- Average Monthly Pool Elevations	4-63
4-19	Grand Coulee Dam/Lake Roosevelt -- Percent Probability of Refill to Selected Pool Elevations	4-64
4-20	Lake Roosevelt, Estimated Annual Recreation Days by Activity for Alternative SOSs	4-65
4-21	Grand Coulee Project/Lake Roosevelt, Estimated Total Recreation Days Under Alternative SOSs	4-67
4-22	Average Monthly Summer Flows (KCFS), Priest Rapids Dam	4-75
4-23	Average Monthly Summer Flows (CFS), Snake River Hells Canyon	4-80
4-24	Percent of Years Average Monthly Summer Snake River Hells Canyon Flows Fall Within the "Acceptable" Recreation Range	4-81
4-25	Dworshak Lake -- Average Monthly Pool Elevations, Ft. NGVD	4-89
4-26	Dworshak Lake -- Percent Probability of Refill to Selected Pool Elevations	4-89
4-27	Dworshak Lake, Estimated Annual Recreation Days by Activity Under Alternative SOSs	4-90
4-28	Dworshak Lake, Estimated Total Annual Recreation Days Under Alternative SOSs	4-92
4-29	Clearwater River, Estimated Total Annual Fishing Days Under Alternative SOSs	4-98
4-30	Lower Granite Lock and Dam/Lower Granite Lake -- Average Monthly Pool Elevations for Alternative SOSs	4-103
4-31	Lower Granite Lake, Estimated Annual Recreation Days by Activity Under Alternative SOSs	4-104
4-32	Lower Granite Lake, Estimated Total Annual Recreation Days Under Alternative SOSs	4-105
4-33	Little Goose, Lower Monumental and Ice Harbor Projects, Average Monthly Pool Elevations (ft. NGVD) under Alternative SOSs	4-110
4-34	Lower Snake River Projects, Estimated Annual Recreation Days by Activity Under Alternative SOSs	4-113
4-35	Little Goose Lock and Dam/Lake Bryan, Estimated Total Annual Recreation Days Under Alternative SOSs	4-114
4-36	Lower Monumental Lock and Dam/Lake West, Estimated Total Annual Recreation Days Under Alternative SOSs	4-115

LIST OF TABLES – CONT

<u>Table</u>	<u>Title</u>	<u>Page</u>
4-37	Ice Harbor Lock and Dam/Lake Sacajawea, Estimated Total Annual Recreation Days Under Alternative SOSs	4-117
4-38	John Day Lock and Dam/Lake Umatilla, Average Monthly Pool Elevations (ft. NGVD) for Alternative SOSs	4-124
4-39	John Day Lock & Dam/Lake Umatilla -- Average Monthly Outflows (KCFS) for Alternative SOSs	4-126
4-40	John Day Lock & Dam/Lake Umatilla, Summer Average Monthly Flows (KCFS) and Percent of Years Within Optimum Recreation Range	4-126
4-41	John Day Lock and Dam/Lake Umatilla, Estimated Annual Recreation Days by Activity Under Alternative SOSs	4-128
4-42	John Day Lock and Dam/Lake Umatilla, Estimated Total Annual Recreation Days Under Alternative SOSs	4-130
4-43	John Day Drawdown to MOP; Recreation Site Impacts Assessment and Recommended Mitigation Actions (Site evaluations base on 1994/95 hydrosurvey data)	4-138
4-44	The Dalles Lock & Dam/Lake Celilo -- Average Monthly Outflows (KCFS) for Alternative SOSs	4-141
4-45	The Dalles Lock & Dam/Lake Celilo, Summer Average Monthly Flows (KCFS) and Percent of Years Within Optimum Recreation Range	4-142
4-46	Bonneville Lock and Dam/Lake Bonneville, Average Monthly Outflows (KCFS) for Alternative SOSs	4-146
4-47	Bonneville Lock & Dam/Lake Bonneville, Summer Average Monthly Flows (KCFS) and Percent of Years Within Optimum Recreation Range (150-250 KCFS)	4-147
4-48	Columbia River Below Bonneville Dam, Average Monthly Pool Elevations (ft. NGVD) for Alternative SOSs	4-151
4-49	Columbia River Below Bonneville Dam, Summer Average Monthly Flows (KCFS) and Percent of Years Within Optimum Recreation Range (150 - 250 KCFS)	4-152
5-1a	Columbia Basin System Recreation Use Summary (Annual Recreation Days), Average Water Year (50-Year Period of Record)	5-2
5-1b	Columbia Basin System Recreation Use Summary (Annual Recreation Days), Low Water Year (1941)	5-3
5-1c	Columbia Basin System Recreation Use Summary (Annual Recreation Days), High Water Year (1976)	5-4
5-2a	Comparison of Recreational Impacts of Alternatives to SOS 2c, the "No Action" Alternative (Differences in Annual Recreation Days)	5-8
5-2b	Comparison of Recreational Impacts of Alternatives to SOS 1a, the "Base Case" Alternative (Differences in Annual Recreation Days)	5-9
5-3	Relative Change in Visitor Use of Alternative SOSs Compared Against SOS 1a (Base Case)	5-11
5-4	Relative Change in Visitor Use of Alternative SOSs Compared Against SOS 2c (No Action)	5-13

TABLE OF CONTENTS

Recreation Appendix

LIST OF TABLES – CONT

<u>Table</u>	<u>Title</u>	<u>Page</u>
6-1	List of Preparers, Recreation Appendix	6-1
D-1	Hungry Horse Reservoir Break Points	D-1
D-2	Lake Koocanusa Break Points	D-2
D-3	Kootenai River Break Points	D-3
D-4	Lake Pend Oreille Break Points	D-4
D-5	Rufus Woods Lake Break Points	D-5
D-6	Lake Roosevelt Break Points	D-6
D-7	Dworshak Lake Break Points	D-7
D-8	Lower Clearwater River Steelhead Fishing Break Points (Based on Dworshak Outflows)	D-8
D-9	Lower Granite Lake Break Points	D-9
D-10	Little Goose/Lake Bryan Break Points	D-10
D-11	Lower Monumental/Lake West Break Points	D-11
D-12	Ice Harbor/Lake Sacajawea Break Points	D-12
D-13	McNary/Lake Wallula Break Points	D-13
D-14	John Day/Lake Umatilla Break Points	D-14
D-15	The Dalles/Lake Celilo Break Points	D-15
D-16	Canadian Columbia River Reach Break Points	D-16

LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
2-1	Destinations of People Who Engaged in Water-Based Recreation	2-18
2-2	Typical Effects of Drawdown on Boating Facilities at Storage Reservoirs (Lake Koocanusa)	2-23
2-3	Typical Effects of Drawdown on Swimming Beaches at Storage Reservoirs (Lake Koocanusa)	2-23
2-4	Typical Effects of Extreme Drawdown at Run-of-River Reservoirs (Lower Granite)	2-24
2-5	Typical Exposed Shoreline Hazards Following Drawdown	2-26
2-6	Changes in Flows Released from Dams Creates Boating Safety Hazards	2-27
2-7	Bank Protection is Needed to Prevent Shoreline Erosion at Many Recreation Sites	2-29
2-8	Lake Koocanusa	2-37

LIST OF FIGURES – CONT

<u>Figure</u>	<u>Title</u>	<u>Page</u>
2-9	Map of Lake Koocanusa – USA	2-38
2-10	Map of Lake Koocanusa – CANADA	2-39
2-11	Columbia River Above Lake Roosevelt	2-44
2-12	Map of the Upper Columbia River, Canada	2-46
2-13	Hungry Horse Reservoir	2-51
2-14	Map of Hungry Horse Reservoir	2-52
2-15	Keller Ferry Recreation Area at Lake Roosevelt (Coulee Dam National Recreation Area)	2-57
2-16	Map of Lake Roosevelt/Coulee Dam National Recreation Area	2-60
2-17	Priest River Recreation Area at Lake Pend Oreille	2-64
2-18	Map of Lake Pend Oreille	2-66
2-19	Waterskiing on Rufus Woods Lake	2-69
2-20	Map of Chief Joseph Project	2-70
2-21	Map of Middle Columbia PUD Projects	2-71
2-22	Rafting on the Snake River in Hells Canyon	2-78
2-23	Map of Snake River Hells Canyon Reach	2-82
2-24	Dent Acres Recreation Area at Dworshak Lake	2-86
2-25	Map of Dworshak Lake	2-87
2-26	Lewiston Levee at Lower Granite Lake	2-91
2-27	Lower Snake River	2-92
2-28	LePage Park at the mouth of the John Day River	2-98
2-29	Map of Lower Columbia River	2-99
3-1	Conceptual Framework for Recreation Impact Assessment Models	3-3
3-2	Grand Coulee/Lake Roosevelt Break Points	3-5
3-3	Example of Recreation Sensitivity Analysis and “Tornado” Diagram at Dworshak Reservoir under a Base Case Scenario	3-7
3-4	Example of Probability Analysis applied to Recreation Pilot Model	3-8
4-1	Lake Koocanusa, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years	4-25
4-2	Kootenai River, Estimated Fishing Use for Alternative SOSs (Low, Average & High Water Years)	4-34
4-3	Columbia River, Canada, Estimated Visitation for Alternative SOSs (Low, Average, & High Water Years)	4-42
4-4	Hungry Horse Reservoir, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-50

LIST OF FIGURES – CONT

<u>Figure</u>	<u>Title</u>	<u>Page</u>
4-5	Lake Pend Oreille, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-58
4-6	Lake Roosevelt, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-66
4-7	Dworshak Lake, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-91
4-8	Clearwater River, Estimated Fishing Use for Alternative SOSs (Low, Average & High Water Years)	4-100
4-9	Lower Granite Lake, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-105
4-10	Little Goose Project, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-119
4-11	Lower Monumental Project, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-120
4-12	Ice Harbor Project, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-121
4-13	John Day Project, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)	4-129
5-1.	Estimated System-Wide Visitation for Alternative SOSs (Average, Low and High Water Years)	5-5
5-2	System-Wide Recreation Use; Estimated Change in use Under Alternatives Compared to SOS 1a	5-12
5-3	System-Wide Recreation Use; Estimated Change in Use Under Alternatives Compared to SOS 2c	5-14

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

LIST OF ACRONYMS

ACEC	Areas of Critical Environmental Concern	FWPRA	Federal Water Projects Recreation Act (1964)
AFWG	Anadromous Fish Work Group	FWS	United States Fish and Wildlife Service
ARD	Annual Recreation Days	HCNRA	Hells Canyon National Recreation Area
BC	British Columbia	IAM	Recreation Impact Assessment Models
BLM	United States Bureau of Land Management	IDFG	Idaho Department of Fish and Game
BoR	United States Bureau of Reclamation (also referred to as Reclamation)	IPC	Idaho Power Company
BPA	Bonneville Power Administration	IWR	Institute for Water Resources (Corps)
CBFWA	Columbia Basin Fish and Wildlife Authority	KAF	Thousand Acre—feet
CFS	Cubic Feet per Second	KCFS	Thousand Cubic Feet per Second
CMS	Cubic Meters per Second	Km	Kilometers
CRGNSA	Columbia River Gorge National Scenic Area.	MAF	Million Acre—feet
COE	U.S. Army, Corps of Engineers (also referred to as the Corps)	MDFWP	Montana Department of Fish, Wildlife and Parks
CBM	Contingent Behavior Method	MOP	Minimum Operating Pool
CVM	Contingent Valuation Method	NGVD	National Geodetic Vertical Datum
DEIS	Draft Environmental Impact Statement	NMFS	National Marine Fisheries Service
EAG	Economic Analysis Group	NPPC	Northwest Power Planning Council
EIS	Environmental Impact Statement	NPS	National Park Service
EPA	United States Environmental Protection Agency	NRCS	United States Natural Resource Conservation Service
ESA	Endangered Species Act	NRMS	Natural Resource Management System
FERC	United States Federal Energy Regulatory Commission	NWED	Northwest Environmental Data Base
FCRPS	Federal Columbia River Power System	NWR	National Wildlife Refuge
		ODFW	Oregon Department of Fish and Wildlife
		ONA	Outstanding Natural Area

ORRRC	Outdoor Recreation Resources Review Commission	SOS	System Operating Strategy
OSMB	Oregon State Marine Board	TCM	Travel Cost Method
OSP	Oregon State Parks Department	URC	Upper Rule Curve (see flood control rule curves).
PL	Public Law	USFS	United States Forest Service
PNCA	Pacific Northwest Coordination Agreement	USFWS (FWS)	United States Fish and Wildlife Service
PNUCC	Pacific Northwest Utilities Conference Committee	USGS	United States Geological Survey
PUD	Public Utility District	VERS	Visitation Estimation and Reporting System (Corps)
RCG	RCG, Hagler/Bailly, Inc.	WDW	Washington Department of Wildlife
RFWG	Resident Fish Work Group	WES	Waterways Experiment Station (Corps)
RM	River Mile	WIAC	Washington State Interagency Committee for Outdoor Recreation
SCORP	Statewide Comprehensive Outdoor Recreation Plan	WSP	Washington State Parks
SOR	(Columbia River) System Operation Review	WTP	Willingness to Pay

CHAPTER 1

RECREATION STUDIES SCOPE AND PROCESSES

This appendix contains the results, findings, and conclusions of the detailed studies undertaken by the Recreation Work Group (RWG) through the Columbia River System Operation Review (SOR). Chapter 1 presents a brief, general description of the technical and geographic scope and study process followed by the RWG including: formation of the work group; coordination efforts with the public, agencies and other work groups; recreation issues and concerns raised during the SOR public scoping process; and work group methodologies and findings during major study phases (pilot, screening, and full-scale analysis). Each of these items is described in detail in subsequent chapters and technical exhibits to this appendix.

1.1 THE SOR RECREATION WORK GROUP

1.1.1 Objectives

Through the process of the Columbia SOR, the objectives of the RWG have been as follows:

- a. To identify the programs, goals, and objectives of Federal, state, and local agencies and entities with recreation resource management responsibilities in the Columbia River Basin that influence or may be influenced by changes in operation of the system of Federal dams in the Columbia River Basin (the system).
- b. To identify the past, present, and potential future recreational users of Columbia Basin reservoirs and rivers and their needs, concerns, and desires regarding system operations.
- c. To identify trends in water-dependent and water-related recreation use, including both reservoir and instream, that presently influence, or could in the future influence or be influenced by, Columbia River system operations.

- d. To identify and analyze the potential effects of changes in system operations on recreational participation in the Columbia Basin, including predicted impacts of alternatives and selection of preferred alternatives.
- e. To identify recreation research and study needs, and to develop and implement recreation research designs, methodologies, and results, including surveys and models, required to accurately evaluate potential recreation impacts.
- f. To develop recreation mitigation plans for alternatives selected under the SOR.

1.1.2 Formation

The RWG was one of four work groups initially established to participate in the pilot modeling phase of the SOR (described in more detail under section 1.5). Initial participants on the RWG included representatives from the three sponsoring agencies, U.S. Army Corps of Engineers (Corps), U.S. Bureau of Reclamation (Reclamation) and Bonneville Power Administration (BPA). Throughout the study process, the sponsoring agency representatives had administrative oversight for the work accomplished by the RWG, including:

- a. coordination with SOR study management/analysis group
- b. scheduling work group activities
- c. administration of contracts
- d. obtaining and managing funding
- e. preparing written materials for SOR documentation
- f. implementation of the public involvement plan.

As the SOR moved into the scoping and screening phases, other Federal, state, and local agencies and others with authorities and responsibilities for managing recreation facilities or resources in the basin, as well as private citizens, were invited to join the RWG.

1.1.3 Participants

1.1.3.1 Tier 1

The RWG has two levels of participation; tiers 1 and 2. Tier 1 is comprised of a core group of representatives who were able to attend and participate in RWG meetings on a regular basis. The RWG met on an average of about once a month beginning in November 1990 with the pilot phase of the SOR and continuing through the completion of the full-scale analysis phase. Most of the meetings were held in Portland, Oregon, which was the most convenient locale for the majority of RWG tier 1 participants. However, meetings were held periodically at other locations throughout the region, including Spokane and Grand Coulee, Washington; Sandpoint and Boise, Idaho; and Libby, Montana, to provide an opportunity for other agencies' representatives and interested members of the public to participate.

Tier 1 participants were also primarily responsible for producing this appendix and other interim products required of the RWG during the SOR process. Individual members of tier 1 determined the appropriate scope of SOR recreation studies. They collected, evaluated, and consolidated information and data, and wrote sections of the appendix. Finally, tier 1 participants reviewed and provided comments on materials produced by other members and consultants of the RWG, and other SOR work groups.

Tier 1 of the RWG included representatives of the following agencies and organizations: (See Exhibit A for complete list):

Federal Agencies

Corps of Engineers
Portland District

Seattle District
Walla Walla District
Waterways Experiment Station
Institute for Water Resources

Bureau of Reclamation

Pacific Northwest Region
Denver Service Center

Bonneville Power Administration
Forest Service, Region 6
National Park Service, Coulee Dam
National Recreation Area

State Agencies

Oregon

Oregon State Parks and Recreation
Department
Oregon State Marine Board

Washington

Washington State Parks and Recreation
Commission
Washington Interagency Committee
for Outdoor Recreation

Idaho State Parks

Other Public Entities

Chelan County Public Utility District
No. 1
Northwest Power Planning Council
Pacific Northwest Utilities Conference
Committee
British Columbia Hydro and Power
Authority (B.C. Hydro)

1.1.3.2 Tier 2

Tier 2 consists of all agencies, entities, and individuals that have expressed an interest/concern regarding recreation issues in the SOR, but by their own

choice have been unwilling or unable to be direct, active participants in tier 1 of the RWG. In general, tier 2 consists of many state and local agency representatives with an interest in the relationship of SOR to recreation at a specific reservoir, subregion or locale, rather than to the system as a whole. These individuals include marina operators, park managers, port directors, and recreation user groups.

Coordination with tier 2 was accomplished primarily through mail. Tier 2 participants were provided copies of all RWG meeting notices, meeting minutes, and other interim work products. The RWG objective was to keep the tier 2 participants informed of the research efforts, results and conclusions of the tier 1 participants. Exhibit A to this appendix provides a complete tier 2 list.

1.1.4 Coordination With Other Work Groups

In order to fully evaluate the potential impacts of changes in operation of the Columbia River system on recreation resources and opportunities, it has been necessary for the RWG to coordinate closely with several other work groups during the SOR process.

1.1.4.1 Resident and Anadromous Fish Work Groups

The Resident and Anadromous Fish Work Groups were responsible for determining the potential effects of changes in system operations on the habitat and biology of their respective species. The RWG coordinated closely with these work groups to translate those changes into effects on fish catching success and fishing participation.

1.1.4.2 Wildlife Work Group

Similar to fish, changes in Columbia River system operations will affect habitat and biology of certain wildlife species. The RWG coordinated with the SOR Wildlife Work Group to attempt to translate wildlife impacts into changes in hunting success and wildlife viewing opportunities.

1.1.4.3 Economic Analysis Group

Recreation is an important sector of the Pacific Northwest economy. Significant local economic infrastructures have developed to support the recreational use of the reservoirs and rivers of the Columbia Basin. Changes in system operation that affect the rates of participation of users will have corresponding impacts on local and regional economies. In general terms, the division of responsibility calls for the RWG to estimate the impacts of SOR alternatives on recreation participation (as defined as changes in visitor days of use). The Economic Analysis Group (EAG) translated those potential changes in recreation participation into economic effects.

The two work groups worked closely to develop tools to evaluate the economic impacts of recreation. The most important of these tools was derived from regionwide recreation user surveys (described in section 3.10) undertaken during the fall of 1993. The results and analytical models developed from the survey are presented in this Final EIS. The RWG had the lead role in developing the survey, but coordinated the effort closely with the EAG. The data collected in the survey included information on both the way recreationists change their recreation participation in response to different operational scenarios, as well as the effect of those changes on the welfare (economic) value of their recreation experience. The user survey also obtained data regarding recreationists expenditures that were used by the EAG to assist in developing estimates of regional economic impacts.

1.2 PUBLIC INVOLVEMENT AND AGENCY COORDINATION

1.2.1 Objectives

During the scoping phase of the SOR, the RWG developed a public involvement program for the recreation element. The objectives were to:

- a. Provide a forum for interested publics, including private users, public interest groups, and resource management agencies to express their needs, interests, and concerns regarding management, operation, and development of Columbia Basin reservoirs and rivers for recreation.
- b. Identify the programs, goals, and objectives of Federal, state, and local agencies and entities with recreation resource management responsibilities in the Columbia River Basin that influence or may be influenced by system operations.
- c. Validate the technical methodologies and approaches used in recreational studies and analysis undertaken through the SOR process from recreation peers and professionals in the region.

1.2.2 Key Publics

This program was targeted at key "publics", including other Federal, state, and local agencies and private entities with recreation resource management responsibilities, state and local political interests, local civic groups, public interest and user groups, professional peers in recreation and related fields, and interested individuals. As previously described in Section 1.1.3.2, most of these key publics were incorporated into the tier 2 mailing list (attached as Exhibit A).

The public involvement objective for tier 2 was to keep these publics informed of the research efforts,

results, and conclusions of the RWG tier 1. Coordination with this group was mostly passive. Minutes of the regular RWG meetings were mailed to tier 2 along with other interim documents produced by RWG and other SOR elements.

Rather than attempting to cover the entire Columbia River Basin, public involvement efforts of the RWG were targeted at those specific geographic regions or project areas where recreation issues or concerns were expected to be created, relieved, or exacerbated by the outcomes of the SOR. Generally, impacts were expected to be relatively minor along the run-of-river reservoirs of the lower Columbia River. Impacts were expected to be more significant at the storage reservoirs on the upper reaches of the Columbia River and its tributaries, and under some alternatives for the lower Snake River. Therefore, public involvement efforts for the recreation element were targeted for communities/projects in the upper reaches.

1.2.3 Public Meetings

As previously described, the RWG held regular coordination meetings. The schedule for these meetings was established in advance and meeting notices were mailed to everyone on both the tier 1 and tier 2 mailing lists. RWG meetings were part of an open public process, and members of the public and other interested agencies and organizations were encouraged to participate. Meeting locations were primarily in Portland, Oregon, but were periodically rotated around the region and frequently included field trips to the project sites with agency or group representatives.

In addition to these regular RWG working sessions, RWG members held numerous other meetings around the study area with specific groups, organizations and agencies specifically interested in recreation issues and concerns related to the SOR.

Those meetings are listed below:

<u>Date</u>	<u>Location</u>	<u>Host/Sponsor/Participants</u>
May 16, 1991	Sandpoint, WA	Sandpoint Chamber of Commerce/local agencies
June 4, 1991	Grand Coulee, WA	Lake Roosevelt Forum
November 12, 1991	Sandpoint, ID	Albeni Falls Project
November 13, 1991	Kalispell, MT	Flathead Basin Commission
November 14, 1991	Libby, MT	Libby Dam Project
November 19, 1991	Orofino, ID	Dworshak Dam Project
November 20, 1991	Kennewick, WA	McNary Dam Project
November 21, 1991	Grand Coulee, WA	Grand Coulee Dam
February 5, 1992	Umatilla, OR	Port of Umatilla
February 6, 1992	Crow Butte, WA	Park Manager, Washington State Parks
	Rooster Rock, OR	Park Manager, Oregon State Parks
February 11, 1992	Clarkston, WA	State, county & local agencies/organizations in the Lewiston/Clarkston area:
February 13, 1992	Dworshak Dam, ID	City of Orofino, Orofino Chamber of Commerce and other local business and agency representatives
February 19, 1992	Grand Coulee, WA	Lake Roosevelt Forum, Grand Coulee Chamber of Commerce, local businesses, other Federal agencies
February 21, 1992	Libby Dam, MT	Kootenai N. F., MT. Dept. of Fish, Wildlife and Game, local representatives and business interests from Libby and Eureka
February 25, 1992	Seattle, WA	University of Washington
February 27, 1992	Sandpoint, ID	Sandpoint Chamber of Commerce
August 18, 1992	Libby, MT	Kootenai NF/Libby Chamber/Lincoln County Economic Development
September 8, 1992	Boise, ID	SOR Public Meeting
September 10, 1992	Kennewick, WA	"
September 14, 1992	Clarkston, WA	"
September 15, 1992	Grand Coulee, WA	"
September 21, 1992	Sandpoint, ID	"
September 22, 1992	Libby, MT	"
September 23, 1992	Eureka, MT	"
September 24, 1992	Kalispell, MT	"
September 14, 1992	Wenatchee, WA	Chelan, Douglas and Grant County Public Utility Districts
September 15, 1992	Spokane, WA	Lake Roosevelt Forum
June 7, 1993	Boise, ID	Idaho State Parks

1.3 RECREATION ISSUES AND CONCERNS RAISED DURING SCOPING

1.3.1 Overview

The SOR scoping process and results are described in detail in the Columbia River System Operation Review Scoping Document, published in May 1991. The process is also described in the Preface to this Appendix. This section focuses on specific recreation and recreation-related issues and concerns that were raised during the scoping process. Those issues form the basis for the scope of work undertaken by the RWG through the SOR and described in this Appendix.

The scoping process began in July 1990 with the public announcement by the sponsoring agencies of their intent to prepare the SOR EIS. Public notices were sent to approximately 11,000 groups and individuals, who were asked to comment on the scope of the SOR in writing and/or to attend one of the 15 scoping meetings held in locations throughout the region during August 1990.

1.3.2 General Issues

1.3.2.1 Recreation

In general, comments from participants in the scoping process focused on the importance of recreation to the overall quality of life in the Pacific Northwest, as well as to local and regional economies. Many participants were concerned about the detrimental effects of water releases during peak recreation seasons on recreation suitability of the lakes in the system. Most of those comments were site-specific, with concerns about operation of the upper end storage projects, especially Libby Reservoir and the Kootenai River the most numerous. Site-specific issues and concerns are described in more detail in Section 1.3.3.

1.3.2.2 Geographic Scope

A majority of scoping participants recommended that the SOR study area be expanded to encompass the entire Columbia River Basin, including the upper Snake River and Canadian parts of the basin.

Participants felt that a comprehensive review of system operations was impossible without looking at the entire system. This view tended to be supported by state and Federal agencies, particularly those with fish and wildlife interests, Tribes, and fishing-oriented recreation groups. Section 1.4 describes the geographic scope of the SOR as it relates to the work performed by the RWG.

1.3.2.3 Fish

Many scoping participants supported the preservation and enhancement of the system's fish resources as an important new priority of system management, citing their regional, national, and international economic importance. The majority of these comments were related to anadromous fish species. However, trout, kokanee, and other resident fish were also seen as important to many local and regional recreation-dependent economies. This concern was noted frequently in Montana.

1.3.3 Site-specific Issues

The following site-specific recreation issues and concerns were raised during the SOR scoping process.

1.3.3.1 Lower Columbia River

Relatively few issues were raised specific to recreation on the lower Columbia River. Port authorities, marina operators, and park managers expressed concern about the effects of high flows on boating and swimming facilities on the run-of-river projects on the lower Columbia River, as well as on the free flowing reach below Bonneville Dam. State and local agencies and organizations identified windsurfing as a particularly important activity to local economies in the Columbia River gorge that could be affected by changes in system operations.

1.3.3.2 Tri-Cities Area

The Tri-Cities area is a major population center in the Columbia Basin. Changes in operation of the mid- and lower-Columbia and lower Snake River projects could affect recreational opportunities and regional economies in this area.

1.3.3.3 Mid-Columbia Projects

Chelan, Grant and Douglas County Public Utility Districts (PUDs) expressed concern about the effects of system operations on the recreational suitability of the mid-Columbia run-of-river projects. Most of the facilities on these reservoirs are usable over the normal three to four-foot (0.9 to 1.2m) operating ranges. These projects have very limited storage space; high-volume flows released from Grand Coulee and Chief Joseph Projects create unsafe swimming and boating conditions and can temporarily flood out recreation facilities.

1.3.3.4 Grand Coulee/Chief Joseph Projects

By virtue of its status as a National Recreation Area, Lake Roosevelt is especially important to the scope of the SOR. The National Park Service, marina operators, boating clubs, user groups, Colville Confederated Tribes, and Lake Roosevelt Forum all expressed concerns about recreation issues related to operation of Grand Coulee Dam. Use of the reservoir has increased rapidly over the last several years and houseboating is very popular.

Local interests are concerned about any changes in operation that could affect use of the lake. Water quality is also a problem in the lake and may affect safe consumption of fish. Public information about low water elevations and water quality problems may be more detrimental to use than the actual conditions dictate.

Local groups and residents are very interested in improving the resident game fish populations in the lake. Two new hatcheries are expected to greatly increase the kokanee population. Groups and private citizens participate in a very active net pen rearing program for rainbow trout and other species. The impact of reservoir operation on water retention time in the lake may be critically important for determining the health and size of resident fish populations.

Many of the facilities on the lake are usable over a wide range of operations. However, large drawdowns make access to boating facilities difficult, especially to commercial houseboat moorages.

Drawdowns of over 8 feet (2.4 m) make swimming beaches unusable.

1.3.3.5 Libby

Business and civic interests, marina operators, commercial fishing guides, Montana Department of Fish, Wildlife and Parks, Kootenai National Forest, and other interests from communities around Lake Koocanusa voiced strong concern about the negative impacts of current operation of the reservoir on recreation, fisheries, and the local economy both within the reservoir and on the Kootenai River downstream.

Residents of Libby and Eureka, Montana, and neighboring communities in British Columbia agreed to the construction of the project based on promises that it would become an important recreation resource. They believe that Federal agencies have reneged on those promises by operating the project primarily for purposes other than recreation. They point out that many of the recreation facilities that were planned on the lake have never been constructed.

Low water elevations have frequently made many of the boating and swimming facilities unusable for long periods during peak recreation seasons. This is especially true in upper reaches of the lake in Canada. Drawdowns also expose large mudflats in the vicinity of Eureka, which have resulted in a dust problem. The kokanee fishery that was once nationally recognized has declined severely in recent years, possibly due in part to reservoir operations.

A blue ribbon trout fishery has developed in the Kootenai River downstream from Libby Dam; trophy size rainbow trout attract anglers from across the nation. Fishing guides and other services that support the fishery are an important sector of the local economy. Severe fluctuations in releases from the dam affect fish biology and fishing success rates.

1.3.3.6 Hungry Horse

Operational concerns similar to those at Libby occur at Hungry Horse, but site-specific scoping comments were limited. There are no communities nearby with large sectors of their economies directly related to recreational use of Hungry Horse.

1.3.3.7 Albeni Falls

Recreational fishing is an extremely important activity at Lake Pend Oreille. A large sector of the local economy is dependent upon fishing and boating use of the lake. Reservoir operations may have an impact on resident game fish biology, particularly kokanee. Local interests would like to see reservoir operations changed to include a higher minimum drawdown level.

1.3.3.8 Dworshak

Recreational use of Dworshak Lake is very important to the local economy of the city of Orofino, Idaho. Drawdowns during the peak recreation season severely constrain use and access to the lake and the usability of facilities. The popular dispersed mini-camps around the lake are very difficult to use if drawdown exceeds about 10 feet (3 m).

The Clearwater River downstream of Dworshak Dam is an important fishery, especially for steelhead. The peak of the steelhead run occurs during the winter and early spring.

1.4 GEOGRAPHIC SCOPE OF RECREATION STUDIES

The SOR Scoping Document (May 1991) describes the geographic scope of the SOR. The geographic scope of recreation studies is based on this overall scope, with some modifications.

1.4.1 Federal Projects

The focus of the SOR recreation analysis is on the 14 Federal projects on the Columbia and lower Snake Rivers and tributaries. Under most of the alternative system operating strategies under consideration, recreational suitability of the five storage projects would be affected to the largest degree by changes in the timing and extent of filling and drawdown (see Chapter 4 for a description of the alternatives and their impacts). These projects are: Hungry Horse, Libby, Grand Coulee, Albeni Falls, and Dworshak.

The remaining 9 Federal projects are run-of-river projects. Four of them are on the lower Snake River: Ice Harbor, Little Goose, Lower Monumental, and Lower Granite. Several of the alternative system operating strategies call for drawing down some or all of these projects for various periods, with potentially significant effects on recreation.

The 5 remaining run-of-river projects are on the middle and lower Columbia River: Chief Joseph, McNary, John Day, The Dalles, and Bonneville. With the exception of John Day, none of the SOR alternatives call for direct changes in these projects. Recreational use of these projects could be affected, however, by changes in timing and velocity of flows released from the Federal storage projects. John Day does have some storage capacity and would be drawn down to minimum operating pool during the summer under several alternatives.

For each of the 14 Federal projects, the RWG performed detailed technical evaluations, including:

- a. Inventory of existing recreation sites, facilities, and activities (see Section 1.6.2)
- b. Inventory of historical recreation visitation patterns & trends (see Section 1.6.3)
- c. Development of recreation impact assessment models to provide quantitative estimates of impacts of the SOR alternatives (see Section 1.6.5)
- d. Supplemental qualitative evaluation of the impact of alternatives.

1.4.2 Downstream River Reaches

Undammed river reaches below Federal projects in the system provide critical recreation opportunities throughout the region. The timing and quantity of flows released from storage and run-of-river projects can both benefit and harm recreation resources and opportunities downstream. Important recreational river reaches that may be affected by system operations include:

- Kootenai River below Libby Dam
- Flathead River below Hungry Horse Dam

- Clearwater River below Dworshak Dam
- Snake River below Hells Canyon Dam
- Columbia River (Canada) below Hugh Keenleyside Dam
- Columbia River, Hanford Reach below Priest Rapids Dam
- Columbia River below Bonneville Dam.

All of these river reaches were included in the inventory of recreation sites, and visitation and potential impacts on recreational suitability stemming from changes in system operations are qualitatively described for each. In addition, the RWG prepared models to assess the impact of alternatives on recreation participation on the Columbia River in Canada, the Kootenai, and the Clearwater Rivers. There was adequate visitation data and knowledge of the relationship between flows and recreation participation to allow development of models for these river reaches.

1.4.3 Non-Federal Projects

Recreation impact assessment models were not developed to estimate the effects of SOR alternatives on recreation use of the five PUD run-of-river projects in the Mid-Columbia reach of the river, including Wells Dam, Rocky Reach Dam, Rock Island Dam, Wanapum Dam, and Priest Rapids Dam. However, the RWG worked with Chelan, Grant and Douglas PUDs to inventory recreation sites and visitation and to qualitatively describe the recreational impacts of alternatives. In addition, models were not developed for IPC's Hells Canyon, Oxbow and Brownlee Dams.

1.5 RECREATION PILOT MODELS

The initial phase of the SOR was the Pilot Modeling Phase. From November 1990 to around April 1991, the RWG and several other work groups were formed and asked to develop first cut "pilot" simulation models that could be used as tools to quantitatively estimate the sensitivity of various resources in the Columbia River Basin to changes in system operations. The Recreation Impact Assessment

models developed by the RWG in the pilot model phase and further refined in the later study phases are described in detail in chapter 3. The basic "value measure" used by the pilot models to describe impacts of operations on recreation use was impact to visitation as expressed in terms of "recreation days" of use. In summary, the pilot models did show that water-related recreation activities in the Columbia River Basin are affected by changes in reservoir elevations and downstream flows resulting from operation of the dams in the system. The information gathered in the pilot model phase was carried forward into the screening phase.

1.6 SCREENING PROCESS

1.6.1 General

The second major phase of the SOR was the screening process. This process is described in detail in the document entitled Columbia System Operation Review Screening Analysis (August 1992). In summary, during this phase the SOR work groups had two major tasks. First, they developed alternative strategies for operating the Columbia River system of Federal dams. Second, work groups evaluated the impacts of all of the alternatives developed under screening. RWG efforts under each of these tasks are described in more detail below.

1.6.2 Recreation Optimization Alternatives

During the screening phase, RWG and many of the other work groups developed alternative system operating scenarios that would theoretically provide the greatest benefit to their individual river uses. In other words, the RWG was asked to describe system operating strategies that came as close as possible to maximizing benefits for recreation. The work groups were also asked to develop other alternatives that, while perhaps not ideal, would provide an acceptable environment for their river use.

The purpose of developing these alternatives was to learn more about the operating relationships of the various reservoirs and river reaches that make up the Columbia Basin system, to define which river uses are compatible and which conflict, and to determine under what conditions and to what extent

the conflicts occur. The goal of the screening phase was ultimately to use these data to come up with combinations or variations of the alternatives that would define alternative strategies for a multiple-use river system to be evaluated in the final SOR phase, full-scale analysis.

A total of approximately 90 different alternative operating strategies were developed and evaluated during the screening phase (SOR Screening Analysis 1992). The RWG developed three alternatives summarized below.

1.6.2.1 Optimum Recreation Pools (REC-OPTP)

Description. The purpose of REC-OPTP was to maintain optimum lake elevations for recreation in the storage and run-of-river reservoirs. The alternative is expressed in terms of target end-of-month pool elevations for every project in the system. Generally, the target elevation is full pool or within 2 feet (0.6 m) of full during the entire peak summer recreation season. For some storage projects, this involves changing the flood control rule curve to extend the recreation season out to spring/early summer and late summer/fall. Under this alternative, optimum reservoir elevations have priority over downstream flow requirements; draw-down below optimum elevation is not allowed. If pool elevations cannot be achieved due to low water conditions, then pool elevations follow flood control rule curves.

Impacts. Analysis of REC-OPTP showed that, as expected, it would result in significant benefits for recreation at all storage and run-of-river projects. Stable pool elevations would also benefit resident fish and wildlife populations. However, there would be some major tradeoffs associated with this alternative. REC-OPTP would have extreme negative impacts on power peaking capacity in the system. In addition, modification of flood control rule curves would mean some loss of flood control during spring high flow periods with the potential for increased flood damage. Resulting higher spring and early summer flows, as well as lower late summer flows,

would negatively affect recreational use of the river reaches downstream of dams in the system.

1.6.2.2 Optimum Recreation Flows (REC-OTPF)

Description. REC-OTPF is similar to REC-OPTP. Its purpose was to provide optimum flows for downstream recreation while maintaining pool elevations in the storage and run-of-river reservoirs as close as possible to the targets specified in REC-OPTP. The alternative is expressed as a target range of desired average monthly flows needed to optimize important recreational opportunities in downstream river reaches. This alternative is based on a recognition that maintaining the target reservoir elevations specified under REC-OPTP could have some negative impacts on downstream recreation under certain conditions. Under this alternative, for projects with target downstream flows, flows have priority over reservoir target elevations. If flows cannot be achieved under flood conditions, flows are kept below flood stage.

Impacts. Analysis of REC-OTPF showed that, as expected, it would result in significant benefits for recreation on downstream river reaches. High quality recreation conditions would be maintained at all of the run-of-river reservoirs and at most of the storage reservoirs. However, there would be significant recreational losses at Grand Coulee (Lake Roosevelt) and Dworshak Reservoir resulting from drafting required to fulfill the downstream target flows.

Tradeoffs of REC-OTPF would be similar to those for REC-OPTP. Modification of flood control rule curves would mean some loss of flood control during spring high flow periods with the potential for increased flood damage. Resulting higher spring and early summer flows would negatively affect recreational use of the Columbia River downstream of Bonneville Dam. In addition, the desired target flows for recreation in the Columbia River below Bonneville would be much higher than average, with extreme impacts on power generating capacity. Stable pool elevations would benefit wildlife populations. However, impacts to resident and anadromous fish species would be mixed.

1.6.2.3 Acceptable Recreation Targets (REC-ACC)

Description. REC-ACC is an alternative that attempts to provide a compromise for reservoir and downstream recreation with other project purposes. It stipulates target ranges of pool elevations and downstream flows in which recreational facilities and opportunities are not seriously impacted. REC-ACC target flows and pool elevations are intended to allow more flexibility in meeting other purposes of the system, while still protecting recreation. For example, target storage reservoir elevations may be anywhere within the top 10 feet (3 m) of the pool during the summer recreation season. Under these conditions, recreation would not be optimum, but most facilities would remain usable while water and storage space in the lake could be made available for other purposes.

Impacts. While REC-ACC was intended to be more flexible than the other two recreation optimization alternatives, it ultimately resulted in much lower recreation use than either of the other two, while still having negative impacts on power and other purposes.

1.6.3 Summary of Screening Evaluations

The results and findings of screening are described in the SOR Screening Analysis. Insights gained to recreation and other closely related project purposes are summarized below.

1.6.3.1 Recreation

The Recreation Impact Assessment models developed in the SOR pilot phase (section 3.4) were used to develop quantitative estimates of the impacts of all 90 screening alternatives on recreation visitation to the projects. For screening, pilot models were developed for only four representative storage projects. The models estimated the impacts of alternative end-of-month pool elevations on participation in four water-related recreation activities; boating, fishing, swimming, and camping/picnicking. For the remaining storage and run-of-river projects and downstream river reaches, the RWG qualitatively described the impacts based on

professional knowledge and familiarity with the operating characteristics and recreational facilities in those areas. The overall ranking of the 90 alternatives was based on a combination of both quantitative model results and qualitative evaluations.

Of the 90 screening alternatives, 27 generated good or very good overall recreation benefits. The majority of these included operations which maintained storage projects at or near full pool and run-of-river projects within normal operating ranges during the primary recreation season without adversely affecting downstream flows. Alternatives which achieved these conditions included those which modified the flood control rule curve to increase early spring refill probabilities. This category of alternatives basically maintains projects within normal operating ranges so that all recreation facilities remain usable and accessible.

Under some alternatives, full-pool elevations were achieved at the expense of extremely high or low downstream flows. These involved operating alternatives which significantly modified or adjusted flood control rule curves and returned streamflows to a more natural environment. Several alternatives designed to optimize irrigation and to determine the flexibility in existing flood control rule curves produced positive recreation benefits at storage projects. However, in some cases, these alternatives created high spring/early summer and low late summer/early fall flows in downstream river reaches, particularly the Columbia River below Bonneville Dam, that were frequently outside of the desired range for recreation. This group of alternatives demonstrated a tradeoff between reservoir and downstream recreation which must be balanced when considering multi-purpose objectives.

Recreation at the storage and run-of-river reservoirs in the system were most severely affected under the 42 screening alternatives which included elements of reservoir drawdown and flow augmentation. When reservoir storage was used during the spring and summer to augment flows for anadromous fish, refill probability declined. Under these scenarios, recreation facilities at the storage reservoirs became unusable during the peak summer recreation season

due to very low water levels. Similarly, alternatives that lowered the Snake River run-of-river projects to below minimum operating pool (MOP) to increase river velocities during downstream anadromous fish migration rendered virtually all of the recreation facilities at those projects unusable (during the drawdown time period).

The remaining 21 screening alternatives were ranked as fair for recreation because participation results as indicated by the pilot models did not differ significantly from the base case. In these cases, reservoir levels did not always refill to optimum levels, but elevations remained relatively stable throughout the primary recreation season. Correspondingly, these alternatives tended to maintain downstream river flows and run-of-river pool elevations within ranges that were generally acceptable for recreation.

1.6.3.2 Resident Fish

During the screening process it was discovered that very little information exists to translate the effects of alternatives on resident fish biological values into impacts on recreational fishing success. The Resident Fish Work Group and RWG will continue to work together through full-scale analysis to qualitatively describe the potential impacts of alternative System Operating Strategies (SOSs) on fish habitat and on the numbers and size of fish that might be caught by anglers.

The Recreation and Resident Fish Work Groups went into screening analysis under the assumption that alternatives designed to maximize either recreation or resident fish would be largely mutually beneficial to the other. However, screening results showed that the target pool elevations under the recreation optimization alternatives may be counterproductive to some resident fish species.

1.6.3.3 Wildlife

Two of the recreation optimization alternatives described above (section 1.6.2) also benefited wildlife by reducing seasonal drawdowns, stabilizing pool elevations, and passing natural streamflows.

1.6.4 Participation in Development of SOS 4c: Enhanced Storage Operations

Based on the results of the screening process, the 90 screening alternatives were blended into six alternative SOSs by the SOR Interagency Team. The alternative SOSs and their impacts to recreation are described in more detail in Chapter 4 of this appendix. The RWG was particularly involved in development of one of those alternatives, SOS 4c -- Enhanced Storage Operation. RWG worked jointly with the Resident Fish and Wildlife Work Groups to develop SOS 4c.

Recreation, resident fish, and wildlife all benefit from reservoir operations in which pool elevations are held as stable as possible without wide seasonal or shorter term fluctuations. SOS 4 seeks to minimize reservoir fluctuations at the five Federal storage projects in the system by setting monthly elevation targets year-round. Water levels would remain highest during the summer months. Pools that are brought up to full in mid-summer under existing flood control rule curves may be brought up in late spring to benefit recreation, resident fish, and wildlife. SOS 4 also attempts to provide a compromise with system requirements for other purposes, including flood control, power generation, and anadromous fish flows.

1.7 FULL-SCALE ANALYSIS

The final phase of the SOR is analysis of 13 alternative SOSs produced as an outcome of the draft EIS. Analytical methodologies incorporated by the RWG to perform the screening and full-scale analyses are described in Chapter 3. The results of the full-scale analysis, and an assessment of the impacts on recreation resulting from each of the alternative SOSs are presented in Chapter 4 and Chapter 5.

1.7.1 Description of Existing Conditions

The initial step in analyzing the recreational impacts of the SOSs was to inventory existing recreation conditions in the Columbia River Basin. Chapter 2 presents a general description of the outdoor recreation resources, opportunities and facilities that are available in the basin. Although the basin provides a wide variety of high-quality outdoor recreation

experiences, the focus of the evaluations for the SOR was on water-related recreation resources and facilities directly related to the Columbia River and its tributaries that may be affected by operation of the Columbia River system of 14 Federal dam projects. Key elements of the description of existing recreation conditions include:

- a. A discussion of the importance of water-related recreation in the Columbia Basin
- b. A description of recreation participation along the Columbia River and tributaries, including major activities and use areas
- c. A description of the users and user characteristics
- d. An analysis of the factors influencing recreational use along the river, focusing on those factors related to system operations

Two major tasks undertaken by RWG as part of the description of existing recreation conditions in the Columbia Basin were to complete detailed inventories of existing sites and facilities in the basin and to estimate total visitor use to the projects and river reaches in the basin.

1.7.1.1 Recreation Site Inventory

RWG completed an inventory of all developed recreation sites and facilities located along the storage projects, run-of-river reservoirs and downstream river reaches within the geographic scope of the SOR. The inventory includes data on the name, location, managing agency, size, number, and type of facilities at every known developed recreation site with direct access to the lakes and rivers. Approximately 250 individual recreation sites are included in the inventory.

The results of the site inventory are summarized in Chapter 2. The complete data base is maintained at the Army Corps of Engineers, Portland District Office, Planning Branch.

1.7.1.2 Recreation Visitation Inventory

RWG also completed a detailed inventory of historic visitation data for water-related recreation activities along the Columbia River and tributaries. These data are critical variables in the recreation impact assessment models used in the screening and full-scale analysis phases. Chapter 2 summarizes the estimated numbers of visitors to the reservoirs and rivers of the Columbia River Basin (within the scope of the SOR) from 1987 to 1991. The methodologies used to collect and consolidate the data are described in detail in Chapter 3 of this appendix. Chapter 3 also describes in detail the problems and limitations associated with this data base.

1.7.2 Recreation Impact Assessment

The purpose of the SOR full-scale analysis phase was to undertake a complete analysis of the potential impacts of the six alternative SOSs. The results of the recreation impact assessment undertaken in this phase are presented in Chapters 4 and 5. Chapter 4 describes the effects of the alternative SOSs individually on each affected project or river reach. Chapter 5 compares and evaluates the trade-offs between the alternatives.

In the screening phase, assessment of recreation impacts of 90 alternatives was keyed primarily to the pilot models for only four storage projects combined with limited qualitative analysis for run-of-river and downstream river reaches. In comparison, full-scale analysis attempts to assess the full range of potential impacts of the SOSs on all affected reservoirs and river reaches in the system. The key components of full-scale analysis are: (1) quantitative results of recreation impact assessment models and (2) supplemental qualitative evaluations.

1.7.2.1 Quantitative Model Results

The Impact Assessment Models (IAMs) developed by the RWG and used to estimate the quantitative impacts of the alternative SOSs on recreation visitation for the DEIS have been replaced in this FEIS. As early as 1991, the RWG had concluded that the validity of the break-point curves that formed the basis for the IAMs was questioned because evidence

of users actual response to changes in lake elevations and streamflows was absent. Although the lake elevation (streamflow)/activity relationships may approximate reality, for the most part they are not based upon empirical user behavioral response (demand) curves. Other important limitations of the draft EIS modeling approach was: (1) it did not correlate visitation to fishing and hunting success as it may be influenced by the effects of alternative SOSs on fish and wildlife populations; and (2) it does not address shifts in participation across substitutes in the region under the alternative SOSs.

To remedy these concerns, the RWG determined that recreation user surveys should be conducted at a number of Federal projects to enhance the predictability and credibility of the SOR recreation IAMs applied in the draft EIS. To this end, a comprehensive study plan was developed to improve upon the draft EIS analytical tools and to accomplish the following objectives for the final EIS : 1) implement visitor use surveys throughout the Columbia River Basin; 2) apply a Contingent Valuation Method (CVM) to elicit the public's participation and economic valuation response to changes in lake elevations and/or streamflows; 3) estimate contingent valuation and participation user responses to alternative hydrologic conditions; and 4) develop a simulation model that will statistically predict changes in recreation demand and social welfare values under various hydrological (pool levels and streamflow rates), substitution, resource quality, and social, demographic, and economic conditions in the basin.

A survey of Columbia River Basin recreationists was carried out in fall 1993 and designed to provide data needed for the developing the revised models. The statistical estimation tasks and development of a Basinwide simulation demand model were subsequently completed and the results incorporated into the final EIS. The simulation modeling results predict changes in recreation participation for the final set of SOSs and replace the quantitative estimates that were provided in the draft EIS. Chapter 3 describes the conceptual framework of the model development while Appendix J-1 provides a detailed technical description. Chapter 4 of this appendix

presents the quantitative estimates of changes in trip taking behavior resulting from changes in the alternative operating alternatives (SOSs) . The monetized non-market value of these changes in visitation to Federal hydro projects are presented in Appendix O (Economic and Social Impacts).

1.7.2.2 Qualitative Evaluations

As in the screening phase, quantitative model results are combined with a qualitative description of the recreational impacts of the alternatives. The purpose of the qualitative analysis is to explain, expand, and clarify the quantitative results of the recreation impact assessment models. In other words, if the models predict a decline in recreation participation over the summer recreation season under a given alternative, the qualitative assessment should clearly describe why the RWG expects the decline to occur.

The qualitative evaluation assesses the impacts of each alternative SOS on the following recreation characteristics:

- Effects on Recreation Facilities/Activities
- Effects on Fish Habitat and Fishing Success
- Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success
- Effects on Recreational Safety and Physical Characteristics
- Effects on Water Quality Parameters Influencing Recreation
- Effects on Aesthetics

1.7.3 Recreation Mitigation

The RWG considered mitigation for recreation impacts as part of the full-scale analysis process. For each final alternative, RWG assessed the level of impact that could be expected. Following that assessment, RWG identified and evaluated opportunities for "avoidance" and/or "minimization" of recreational impacts. Appropriate mitigation measures are recommended in Chapter 4 for each project or river reach under each alternative SOS. A conceptual plan for mitigating the recreation impacts of the Preferred Alternative (PA) is presented in Chapter 5.

CHAPTER 2

RECREATION IN THE COLUMBIA RIVER BASIN TODAY

This chapter presents a general description of the outdoor recreation resources, opportunities, and facilities that are available in the Columbia River basin (the basin). Although the region provides a wide variety of high-quality outdoor recreation experiences, the focus of this chapter is on those water-related recreation resources and facilities directly related to the Columbia River and its tributaries that may be affected by operation of the Columbia River system of 14 Federal dam projects (the system) that are being considered under the SOR. A discussion of the factors related to system operation that influence recreation participation is included.

2.1 GENERAL OVERVIEW

Water and outdoor recreation have an important and direct relationship. In order to understand the effects on recreation that result from operating the Federal water resource projects in the basin, it is necessary to understand this relationship.

Water is used for recreation in two ways. First, it is a resource necessary to perform a wide variety of recreation activities, including boating, swimming, fishing, waterskiing, and windsurfing. Second, in addition to being the medium for some recreation activities, water provides an "aesthetic complement" to many other land-based activities that do not require a body of water to be performed, but are generally enhanced by association with it. People are attracted to landscapes that include aesthetically pleasing bodies of water. They frequently prefer water-related settings for camping, picnicking, sightseeing, hiking, hunting, and nature study.

It is difficult to overestimate the importance of water as a recreation resource, especially in the Basin where opportunities for water-related recreation are so diverse and varied. Recreation is one of the most rapidly growing demands for water in this

country. As early as 1962, the Outdoor Recreation Resources Review Commission (ORRRC) reported that "the major portion of outdoor recreation activities take place in water or adjacent thereto...and 44 percent of the population prefers water-based recreation over any other." It is evident that this trend continues in the basin today; Section 2.4 describes the characteristics of recreationists in the region, including their preferences for water-related recreation activities.

The basin is blessed with a diverse landscape that offers a wide variety of outdoor recreation opportunities. It is characterized by several mountain ranges, plateaus, and large river valleys. Recreationists have a choice of settings for water-related recreation ranging from wilderness mountain lakes and streams to urban waterfront parks. The forests and mountains of the Pacific Northwest, many in public ownership, provide some of the most outstanding outdoor recreation opportunities in the country. The abundant and diverse fish and wildlife resources and many outstanding natural and man-made scenic wonders help support a tourist industry that is important to the regional economy.

The principal source of water in the basin is snow-melt from mountain ranges. Streams flowing rapidly out of the mountains provide opportunities for fishing, kayaking, rafting, and other activities in dispersed wilderness and semi-wilderness settings. A large percentage of the land area along headwaters lakes and streams in the region is located in National Forests; the U.S. Forest Service (USFS) has developed an extensive system of recreation sites and facilities along them.

Free-flowing streams and rivers provide important opportunities for recreation activities in settings different from the slack water of lakes. They are an important scenic resource as well, adding to the aesthetically pleasing diversity of the basin's landscape. Many streams have attained national signifi-

cance. The Hell's Canyon reach of the Snake River, Salmon River, Middle Fork of the Clearwater River, Imnaha River, St. Joe River, North and Middle Forks of the Flathead River, Deschutes River, and John Day River are all designated National Wild and Scenic Rivers.

Eventually, these streams flow into the Columbia and Snake Rivers. For a substantial portion of their lengths, the Columbia and Snake Rivers flow through the arid and semi-arid plains and valleys east of the Cascade Mountains. In this part of the basin, the rivers have been highly developed through water resource projects designed to accomplish a variety of purposes. Large man-made lakes bisect the Columbia and Snake River plains, providing expanses of slack water for recreation. In many parts of the basin, these reservoirs are the only water resources available for recreation. Consequently, they are extremely popular with residents.

Recreation is a specifically authorized purpose at several of the projects in the system. In addition, recreation use and development is authorized at all of the projects under generic Federal legislation, including the Federal Water Projects Recreation Act of 1965 (Public Law 89-72) and the Flood Control Act of 1944. Under these authorities, the U. S. Army Corps of Engineers (Corps) and the U. S. Department of Interior, Bureau of Reclamation (Reclamation) are the Federal agencies primarily responsible for providing recreation facilities at the respective lakes which they manage. Recreation facilities are provided at all of the Federal projects being considered under the scope of the SOR.

The Corps and Reclamation also cooperate with other Federal agencies, including the USFS, the National Park Service (NPS), and the U.S. Fish and Wildlife Service (FWS), as well as Idaho, Oregon, and Washington state park departments and other local entities such as counties, cities, and port districts, to build and manage a system of water-related recreation facilities. These include boat ramps, swimming beaches, marinas, campgrounds, picnic areas, and interpretive sites.

Recreational use of the reservoirs occurs year-round but peaks from late spring through early fall. Where compatible with other project purposes, the reservoirs are operated to maintain recreation benefits. Normal operation of the projects for flood control, power generation, and other purposes sometimes conflicts with optimum conditions for recreation.

2.2 RECREATION OPPORTUNITIES AT DIFFERENT TYPES OF SYSTEM ELEMENTS

This section provides a generic description of the operation of the Columbia Basin system, focusing on the different types of elements in the system and the effects of system operations on recreation suitability of each.

In very simplified terms, the Columbia River system is comprised of four types of elements, including free flowing rivers and streams, storage reservoirs, run-of-river reservoirs, and controlled downstream river reaches. The role of each of these elements in operation of the system, the different spectrum of recreation opportunities they provide, and the effects of operations on their recreation suitability are summarized below. In this document, the terms "reservoir" and "lake" are used interchangeably to refer to the bodies of water behind dams.

2.2.1 Free Flowing Rivers and Streams

The free flowing rivers and streams in the basin provide critical water-related recreation opportunities. They are located in headwaters above the Federal water resource projects in the system and, therefore, are not directly affected by operation of those projects. For that reason, free flowing rivers and streams are outside of the scope of the SOR.

2.2.2 Storage Projects

Most of the larger tributaries in the basin have storage projects near their headwaters. The main purpose of the storage projects is to adjust the natural flow patterns of the river to closely conform to water uses; they are characterized by large seasonal fluctuations in water level over a year's operation. They generally store spring and summer runoff to

control floods and to provide flows for power and other purposes when it is needed. The reservoirs are drawn down in mid to late fall and/or before the spring runoff to make storage space available for flood control.

The suitability of the storage reservoirs for recreation is directly related to the degree and timing of seasonal drawdown. Storage reservoirs are at their optimum for recreation suitability when they are at or near full pool. The spring and summer storage season approximately corresponds to the warmest summer months when demand for water-related recreation activities is at its peak in the Northwest. This peak period traditionally occurs between the Memorial Day and Labor Day holidays. The storage reservoirs in the Columbia Basin support an average of 50 to 60 percent of their annual total visitation during that period (Table 2-13).

Operations that delay filling the storage reservoirs until later in the summer or cause them to be drawn down earlier in the fall will have a more severe effect on recreation suitability than similar operations at other times of the year.

Federal storage projects that may be directly affected by operational alternatives considered in the scope of the SOR include:

- Dworshak Dam and Lake on the Clearwater River
- Albeni Falls Dam (Lake Pend Oreille) on the Pend Oreille River
- Libby Dam (Lake Koocanusa) on the Kootenai River
- Hungry Horse Dam and Lake on the Flathead River
- Grand Coulee Dam (Lake Roosevelt) on the Columbia River.

Grand Coulee, the largest storage project in the system, is located on the mainstem of the Columbia. The other Federal storage projects are located near the headwaters of the major tributary streams in the basin.

Recreation resources and opportunities at several non-Federal storage projects in the basin may be

indirectly affected by changes in operation of the Federal system. They include:

- Corra Linn Dam and Kootenay Lake on the Kootenai River (Canada)
- Kerr Dam and Flathead Lake on the Flathead River
- Brownlee Dam and Lake on the Snake River.

2.2.3 Run-of-River Projects

The run-of-river projects on the main stems of the lower Snake and middle Columbia Rivers were constructed to serve two major purposes: (1) to provide for power generation, and (2) to provide adequate water depth for navigation over rapids and other obstacles. With the exception of John Day, the run-of-river projects in the basin have only minor amounts of storage space, which is used for hourly regulation of powerhouse discharges to follow daily and weekly load patterns.

Run-of-river projects do not experience the large seasonal fluctuations in pool elevations that characterize storage reservoirs. Most of the water-related recreation facilities along these projects are designed to be usable throughout the normal narrow range of daily and weekly fluctuations. As long as pool elevations are held within that normal range, recreation facilities at run-of-river projects generally remain fully usable.

On the other hand, recreation suitability of the run-of-river projects can be influenced by the velocity and timing of flows passing through them. For example, high-velocity flows can create turbulence and safety hazards for boaters and swimmers or cause downstream erosion.

Federal run-of-river projects that may be directly affected by operational alternatives considered in the scope of the SOR include four projects on the lower Snake River:

- Lower Granite Dam and Lake
- Little Goose Dam and Lake Bryan
- Lower Monumental Dam and Lake Herbert G. West
- Ice Harbor Dam and Lake Sacajawea

And five projects on the Middle and Lower Columbia River:

- Chief Joseph Dam and Lake Rufus Woods
- McNary Dam and Lake Wallula
- John Day Dam and Lake Umatilla
- The Dalles Dam and Lake Celilo
- Bonneville Dam and Lake.

In addition, changes in operation of the system considered under the SOR could affect the recreation resources and opportunities at the series of non-Federal run-of-river projects operated by public utility districts (PUDs) in the middle Columbia River, including:

- Wells Dam
- Rocky Reach Dam
- Rock Island Dam
- Wanapum Dam
- Priest Rapids Dam

2.2.4 Controlled Downstream River Reaches

Undammed river reaches below Federal projects provide critical recreation opportunities throughout the region. The timing and quantity of flows released from storage and run-of-river projects can both benefit and harm recreation resources and opportunities downstream. Important recreational river reaches that may be affected by system operations:

- Kootenai River (Kootenay River in Canada) below Libby Dam
- Clearwater River below Dworshak Dam
- Snake River below Hells Canyon Dam
- Columbia River (Canada) below Hugh Keenleyside Dam
- Columbia River, Hanford Reach below Priest Rapids Dam
- Columbia River below Bonneville Dam.

- Flathead River below Hungry Horse Dam.

2.3 RECREATION PARTICIPATION ALONG THE COLUMBIA RIVER AND TRIBUTARIES

2.3.1 Visitation Estimates

Table 2--1 presents a summary of the estimated visitation to the reservoirs and rivers of the Columbia River Basin (within the scope of the SOR) from 1987 to 1993 (as measured in terms of visitor days). The methodologies used to collect and consolidate the data are described in detail in Chapter 3 of this appendix. Chapter 3 also describes in detail the problems and limitations associated with this data base.

The visitor data includes estimates of use for water-dependent and water-related recreation activities only. Only those developed recreation sites with direct access to the Columbia River and its tributaries are included in the data base. Numerous other upland recreation sites in the Basin without direct access to the rivers and lakes have been excluded.

The Federal agency primarily responsible for managing each lake or river is the primary source of visitation data. Visitation data for all 12 Corps projects in the Basin are contained in the Natural Resource Management System (NRMS) data base maintained by Portland, Seattle, and Walla Walla Districts. NRMS includes all of the recreation facilities that are located on Federal project lands administered by the Corps. Reclamation maintains a similar data base for Hungry Horse and Grand Coulee projects.

Supplemental data were obtained for recreation sites administered by other agencies, including the NPS (Coulee Dam National Recreation Area); USFS (Hells Canyon National Recreation Area and National Forest recreation sites at several lakes and streams); FWS (Umatilla National Wildlife Refuge); state parks departments for Oregon, Washington, Idaho, and Montana; public utility districts along the mid-Columbia River; the Spokane and Colville Confederated Tribes for reservation lands at Lake Roosevelt; and numerous local port districts.

Table 2-1. Summary of Historic Recreation Visitation to Columbia River Basin Reservoirs and Rivers, 1987 – 1993

VISITOR (RECREATION) DAYS (x1,000)								
PROJECT / RIVER REACH	1993	1992	1991	1990	1989	1988	1987	7-YR AVG
Hungry Horse Dam/Reservoir	93.5	92.4	92.3	88.3	77.0	35.9	75.0	79.2
Libby Dam/Lake Koocanusa	204.7	202.0	188.9	193.0	145.8	172.7	121.0	175.4
Kootenai River below Libby Dam	--	--	--	--	33.9	--	--	33.9
Albeni Falls Dam/Lake Pend Oreille	320	381.4	1337.8	1219.2	1249.3	1242.0	1241.4	998.7
Columbia River, Canada	--	--	154.9	--	--	--	--	154.9
Grand Coulee Dam/Lake Roosevelt	1766.7	1680.1	2347.5	2045.7	1579.8	1706.9	1509.8	1805.2
Chief Joseph Dam/Woods Lake	46.9	46.3	46.7	51.6	48.1	--	--	47.9
Rock Island Dam/Lake	--	--	1368.9	852	586.3	633	N/A	860.1
Rocky Reach Dam/Lake	--	--	730.2	790.7	575.6	529	483.4	621.8
Snake River/Hells Canyon NRA	--	--	50.2	48.7	42.1	39.1	37.4	43.5
Dworshak Dam/Dworshak Lake	150.8	164.7	221.2	198.9	237	239.8	260.4	210.4
Lower Granite Dam/ Lake	1656.5	1866.7	1691.2	1613.7	1422.6	1209.2	1248.7	1529.8
Little Goose Dam/Lake Bryan	250.1	258.2	202.8	191.3	232.3	323.9	242.2	243.0
Lower Monumental /Lake West	140.5	129.5	136.0	120.9	131.3	161.3	157.5	139.6
Ice Harbor Dam/Lake Sacajawea	524.2	516	502.8	446.4	454.3	458.6	472.9	482.2
McNary Dam/Lake Wallula	--	--	2747.5	2779.0	3097.2	2956.2	3276.2	2971.2
The Dalles Dam/Lake Celilo	1411.3	1614.7	2920.1	2802.8	2809.6	1334.2	1038.8	1990.2
John Day Dam/Lake Umatilla	2518.3	2650.9	2545.5	2540.8	2559.4	2257.8	1596.5	2381.3
Bonneville Dam/Lake Bonneville	3164.6	2769.2	3041.7	4910.6	3250.8	2694.8	3325.1	3308.1
TOTAL	12248.1	12372.1	20326.2	20893.6	18532.4	15994.4	15086.3	18076.4

Wherever possible, average annual visitation was obtained over the last seven complete years of record (1987–1993). For sites where less than seven years of record are available, the most recent year of data was used as a proxy for average annual use.

2.3.2 Major Activities and Use Areas

Table 2-2 displays the breakdown of recreation participation by activity at three typical project areas

in the basin. These three project areas were chosen to illustrate the differences in the mix of activities that occur at the lakes in the system. Lake Umatilla (John Day Dam) is typical of the large run-of-river projects on the lower Columbia and Snake Rivers. Lake Dworshak (Dworshak Dam) and Koocanusa are typical of the relatively remote storage reservoirs located on the upper tributary streams. It is interesting to note that, despite their similarity in size

and physical and operational characteristics, the ratio of activity use at lakes Dworshak and Koocanusa varies considerably.

2.3.2.1 Boating

Boating is the most popular water-related recreation activity occurring at most of the lakes and rivers in the system. As shown in Table 2-2, between 13 percent of visitors to Lake Koocanusa and 40 percent of users at Dworshak Lake participate in boating activities.

This category encompasses a variety of different types of boating activities. The types of boating uses vary between the lakes and rivers. A high percent-

age of boating use at all areas in the system is associated with fishing. At the reservoirs, waterskiing, sailing and cruising, make up the balance of boating use. Houseboating is a popular activity at some of the lakes in the system, particularly Lake Roosevelt, where demand for houseboating has risen dramatically over the last 10 years. Dworshak Lake has over 70 mini-camps scattered around the shoreline and boat-in camping is popular.

In some of the downstream river reaches, kayaking, canoeing, and whitewater rafting are popular. The Hells Canyon reach of the Snake River is a world-class whitewater boating river. Whitewater jetboating and rafting in Hells Canyon is supported by a

Table 2-2. Percent of Visitor Participation by Activity, 1991

<u>Activity</u>	<u>Lake Umatilla 1/</u>	<u>Lake Dworshak 2/</u>	<u>Lake Koocanusa 3/</u>
Camping	12.0	3.2	33.3
Picknicking	25.2	8.4	2.0
Boating	33.0	40.0	13.0
Fishing	31.7	30.5	13.3
Hunting	6.7	2.1	7.0
Sightseeing	15.6	14.1	33.3
Waterskiing	9.9	1.6	0.5
Swimming	14.5	2.8	2.0
Windsurfing	5.0	0.0	0.0
Other	<u>14.8</u>	<u>56.0</u>	<u>7.0</u>
Total 4/	164.0	158.6	111.4
1/ Corps of Engineers, Portland District			
2/ Corps of Engineers, Walla Walla District			
3/ Corps of Engineers, Seattle District			
4/ Total is greater than 100% because visitors participate in more than one activity (ratio of duplication)			

substantial guide and outfitter industry in the Lewiston Clarkston area. Most of the downstream river reaches, such as the Clearwater below Dworshak Dam, the Kootenai below Libby Dam, and the Flathead below Hungry Horse Dam, provide outstanding fisheries and support high numbers of driftboats and other fishing-related boating.

Most boating use in the system is highly localized; boaters launch from marinas and boat ramps in the vicinity of where they would like to fish or ski and within that particular area. All of the reservoirs in the system have several boat ramps, courtesy docks and other facilities, and most have at least one marina to provide a complete range of boating services. A small amount of upriver and downriver cruising between reservoirs does occur on the lower Snake and Columbia rivers. Recreational craft can pass through navigation locks at the dams free of charge. In 1989, 634 recreational craft locked through Bonneville Dam.

There are a number of commercial cruise lines that operate on the lower Columbia and lower Snake Rivers. It is difficult to categorize this activity as boating or sightseeing. For example, several commercial operators offer cruises along the entire Columbia River from Portland to the Lewiston/Clarkston area from the spring through the fall. These are typically eight day/seven night trips. The cruise ships will make stops at communities such as Cascade Locks, Hood River, The Dalles, Umatilla and Lewiston/Clarkston, and at other points of interest such as Bonneville Dam along the way. Approximately 95 percent of passengers on the cruise ships also take a side trip up the Hells Canyon by guided jetboat services. Obviously, the cruise ship lines are important to local economies along the rivers.

2.3.2.2 Waterskiing

Waterskiing is a relatively minor activity at most of the lakes in the system in terms of total numbers of participants. As shown in table 2-2, nearly 10 percent of visitors to Lake Umatilla waterski, but only 1.6 percent and 0.5 percent of visitors to lakes Dworshak and Koocanusa waterski. In most cases, however, the reservoirs in the Columbia Basin

provide the only large slack-water bodies available to support the activity.

2.3.2.3 Fishing

Fishing is probably second only to boating as the most popular recreational activity on the reservoirs and rivers of the basin. As shown on Table 2-2, annual average participation in fishing ranges from 13 percent of all visitors to Lake Koocanusa up to 30 percent at Lake Umatilla. Although visitation data are less complete or consistent, it appears that the percentage of visitors participating in fishing at downstream rivers is even higher than the lakes. Fishing is the primary purpose for many of the recreational trips taken to facilities in the system. The Columbia River Basin recreational fishery has high seasonal impacts on local economies.

Fishing takes place at numerous and widely dispersed locations throughout the basin, at storage reservoirs, run-of-river reservoirs, and along rivers. A high percentage of the fishing is from boats, although substantial shoreline fishing does occur. A diversity of game fish species are available. Anadromous fish (salmon, steelhead) are caught in the lower Columbia and lower Snake Rivers and many of their tributaries, including the Clearwater River. Different species of warmwater game fish (bass, walleye, sunfish) and coldwater game fish (kokanee, rainbow trout, cutthroat trout, sturgeon) populate all of the rivers and streams in the basin.

2.3.2.4 Hunting

Hunting is a relatively minor activity at most of the lakes and rivers in the system in terms of total numbers of visitors participating. Target game species include big game (deer, elk), upland gamebirds, small mammals, and waterfowl. Most wildlife game species are not significantly affected by changes in operations of the projects in the system. The exception is waterfowl; changes in pool elevations and flows can significantly affect waterfowl habitat with resulting impacts to hunting (and wildlife viewing) success.

Waterfowl hunting is a very important activity at the Umatilla National Wildlife Refuge, located along Lake Umatilla. Hunters use boats on Dworshak

Lake to access deer and elk hunting grounds in the remote areas along the lake.

2.3.2.5 Swimming

Swimming is a relatively minor recreational activity in the system in terms of total visitor use. However, this activity has the potential to be more seriously impacted by project operations than other water-related activities due to the constraints of developed swimming beaches. A certain percentage of swimming also occurs at dispersed or unimproved beaches. Almost all swimming in the basin occurs during the summer months of June, July, and August when water and air temperatures are warmest.

2.3.2.6 Windsurfing

In the few years since windsurfing was introduced to the Columbia River Gorge, it has grown dramatically in importance as a recreation activity and as a source of local economic growth. The activity yearly draws hundreds of thousands of participants, and tens of thousands of spectators have witnessed professional racing events. In 1990, there were an estimated 231,600 windsurfing visitor days in the gorge. Windsurfer expenditures were estimated at \$16.5 million (Povey, 1990).

Windsurfing is an extremely important activity at the lower Columbia River reservoirs, including lakes Bonneville, Celilo and, to a lesser extent, Umatilla. Minor amounts of windsurfing do occur at other lakes in the region.

2.3.2.7 Camping

The importance of overnight camping varies by lake or river reach. Nearly all of the lakes and rivers in the system have campgrounds to support overnight use by visitors. Camping facilities range from highly developed, multiple-use parks with paved roads, utility hookups, and flush toilets, to more primitive "forest-type" campgrounds. The lakes and rivers in the system are important destination recreation sites for overnight visitors, who travel to the sites to camp in addition to participating in a variety of other water-related activities. Many campers choose destinations based on their proximity to other recreation activities, particularly boating and fishing.

Camping facilities can also be affected by system operations. For example, low water levels can render pumped irrigation facilities and water systems inoperable.

Some campers at the lakes and rivers in the system are travelers passing through the region, who make use of the camping facilities available. This is especially true at the lakes and rivers located near major highways.

2.3.2.8 Picnicking

Picnicking activity is similar to camping in many ways. It is land-based, but most picnickers participate in a "package" of activities which may include water-based recreation such as swimming. All of the lakes and rivers in the system have facilities to support picnicking and related day-use activities. Picnickers tend to be day-use visitors who live in close proximity to the lake or river reach and are making a one-day trip from their home. The importance of picnicking varies by lake or river reach. Picnicking tends to be a more important activity at those project areas with a substantial population center nearby, such as Lake Umatilla, at which 25.5 percent of visitors picnic. This is compared to more remote lakes and rivers such as Lake Koocanusa, at which only 2 percent of visitors are picnickers.

2.3.2.9 Sightseeing

Roads and highways paralleling the rivers and reservoirs of the Columbia Basin provide access to majestic vistas of natural features such as forests, mountains, cliffs, rivers and streams, and waterfalls. The study region has innumerable parks, rest areas, and viewpoints available for sightseers to enjoy these scenic amenities.

Many visitors are attracted to impressive manmade features such as Grand Coulee, Bonneville, and other dams and associated features, including fish hatcheries. Most of the project areas have visitor centers and other facilities designed to interpret project history, operations, and purposes for visitors. Table 2-2, shows that an annual average of from 15 to 33 percent of all visitors to Corps recreation sites

on the Columbia and Snake Rivers participate in sightseeing.

Many historic and prehistoric features are located along the shorelines of the Columbia River and tributaries, including the Lewis and Clark trail, evidence of the Oregon Trail and early pioneer settlement, and historic engineering features such as the dams and navigation locks, and the Columbia River Highway. Petroglyphs and other artifacts provide evidence of the prehistoric importance of the basin.

Some of these cultural resources are inundated by the reservoirs of the Columbia River. Opportunities to view these features actually increase during low water periods. However, as access to these cultural resource sites improves, so do opportunities for illegal vandalism and artifact collection.

2.3.3 Future Recreation Demand

Contemporary literature on the subject of recreation predicts an increased demand for recreation facilities and services throughout the northwestern United States and southwestern Canada. A large part of the attractiveness of the region for both residents and visitors is the quantity and variety of public and private year-round recreation facilities and opportunities. The regional population on both sides of the border has evolved with a societal expectation that this variety of public and private recreation opportunities will be available at all times. As the regional population continues to grow through both the expansion of the existing population base and immigration from outside the region, this expectation will remain and likely strengthen, resulting in a significant increased demand for recreation sites and facilities.

The Columbia River and its tributaries provide a large and varied portion of the fresh water recreation opportunities for residents and visitors in the region. Recreation opportunities available in the Columbia River watershed range from passive, low

impact experiences to consumptive, high impact activities. With public ownership of the water surface and a portion of the surrounding lands a norm, significant opportunities exist to meet the increased regional demand for a variety of fresh water recreation facilities and sites.

The Pacific Northwest Outdoor Recreation Committee, comprised of the parks and recreation departments of Oregon, Washington and Idaho and six Federal land management agencies completed the "Pacific Northwest Outdoor Recreation Consumption Projection Study: Tri-State Summary Project" (Hospodarsky, 1989). The Tri-State Summary assessed the future recreation demands for the three state area. Based upon the demographic similarities found throughout the region and the presumption that most of the potential SOR recreation impacts will occur within the three northwestern states, demand results from the Tri-State Summary were used to estimate future recreation demand.

The Tri-State Summary breaks recreation participation into a total of 60 different activities. Eleven of those activities encompass the water-dependent and water-related recreation activities that occur most frequently at the lakes in the SOR. Predicted low, average and high growth rates (scenarios) for these activities, from 1989 through 2010 are listed on Table 2-3.

Although no foolproof method is available to predict the future demand for recreation sites and facilities in the Columbia River Basin, the Tri-State Summary provides some valid estimates of the probable growth of various recreation activities. The growth of these activities is a direct influence on the demand for suitable recreation facilities and sites. The demand for several of the activities supported by recreation facilities and sites at the Federal projects in the Columbia River Basin is expected to more than double by 2010. Demand for many of the other significant recreation activities will come close to doubling during this same 20-year period.

**Table 2-3. Estimated Future Recreation Demand in the Columbia River Basin
(Oregon, Washington and Idaho)**

Activity	Predicted Growth Rates: 1989 – 2010		
	Low	High	Average
Waterskiing	32	92	62
Sailing (not including sailboarding)	40	188	114
Sailboarding	24	88	56
River Boating (non-motorized)	34	149	92
Lake Boating (non-motorized)	51	176	114
Lake Boating (motorized)	29	89	59
River Boating (motorized)	22	67	45
Freshwater Fishing (boat)	25	78	52
Freshwater Fishing (bank or dock)	20	61	41
Swimming	39	117	78
Picnicking	44	121	83
Sightseeing	46	109	78
Recreational Vehicle Camping	39	112	76
Tent Camping with vehicle	46	124	85
Boat Camping	24	62	43

2.4 RECREATIONAL USER CHARACTERISTICS; RESULTS OF PHASE IA SURVEY

This section presents a summary of the results of the Phase IA user survey sponsored by the Columbia River SOR Recreation Work Group (RWG). The Phase IA survey is described in detail in Estimation of Recreation Impacts for the Columbia River System Operation Review: Methods for Phase II (RCG/Hagler, Bailly, Inc., 1993). Its primary purpose was to acquire information about the patterns of water-related recreation use in the region. This information was used to establish sampling strategies for the Phase II full-scale user survey implemented during the summer of 1993. The Phase II survey allowed RWG to construct scientifically and statistically defensible recreation impact assessment model specifications for the final analysis of the SOR alternatives. The results of the Phase II survey were not available in time for inclusion in the draft EIS

but have been incorporated into this final EIS. The Phase II User Surveys and resulting recreation impact assessment models are described in detail in Chapter 3 (Section 3.9).

The results of the Phase IA survey are useful in characterizing who uses the Columbia River Basin system, where they come from, and what activities they participate in. These results were derived using the 831 complete or partially complete telephone surveys administered in December 1992. The Phase IA survey gathered information on water-based recreation activities from residents in the Columbia River Basin, which includes regions of the U.S. Pacific Northwest and southwest Canada. Four categories of information were sought: (1) participation rates for water-based recreation; (2) demographic characteristics; (3) trip information by destination (reservoirs, federal projects, and rivers)

and activity (fishing, swimming); and (4) attitudes towards site characteristics.

2.4.1 Participation Rates in Water-Based Recreation

Participation rates are important for a number of reasons. First, they indicate the overall level of demand and therefore the importance of water-based recreation in the region. Second, comparison of the Phase IA survey participation rates with those resulting from other studies allow a gauging of the accuracy of the results. Finally, they can be used in conjunction with the demographic characteristics (e.g., age, gender, income) to identify which personal characteristics are more likely to affect the decision to participate in water-based recreation activities.

Respondents who agreed to take part in the survey were asked if they had participated in water-based recreation in the past 12 months. A total of 565 individuals responded positively (hereafter referred to as "recreators"), leaving 266 respondents who did not participate ("non-recreators"). This gives an overall participation rate in the Columbia River Basin of 68 percent.

Comparisons were made between Phase IA survey participation rate results and recreation participation statistics reported elsewhere to ascertain if the results are reasonable. Unfortunately, these comparisons are tenuous at best since the other statistics do not specifically measure overall participation in water-based recreation. Instead they report participation rates for individual activities or narrowly defined groups of activities, e.g., fishing, waterskiing, motorboating. And the degree of overlap in activities is unknown.

For example, in 1987, 57 percent of Washington households engaged in fishing and 72 percent engaged in water-related activities, encompassing a diversity of activities, ranging from boating to beachcombing, (Washington Outdoors, 1987). Clearly some boaters must also fish, but the degree of overlap is unknown so we cannot estimate the overall participation rate for water-based activities such as boating or fishing. Similarly, the 1988

Oregon Statewide Comprehensive Outdoor Recreation Plans (SCORP) reports that 52 percent of Oregon households fished and 43 percent engaged in water activities such as boating and windsurfing. The 1988 Montana Statewide Comprehensive Outdoor Plans (MDFWP, 1990) also reports rates for activities: 56.4 percent of households fish, 32.6 percent motorboat, 11.4 percent canoe and 42.3 percent swim in lakes.

To the extent that the data can be disaggregated into similar categories, Phase IA survey participation rates were consistently lower than in the SCORP reports for the various states. For example, the information that survey respondents gave for fishing trips suggest angler participation rates of 25.44 percent in Washington, 39.57 percent in Oregon, and 45.83 percent in Montana. Activity-specific rates from the survey are lower than rates predicted in the SCORPs.

There are some important features of the Phase IA survey that would tend to produce lower participation rates for specific activities such as fishing. First, respondents to the survey recorded fishing trips only if fishing was the primary purpose of one or more of their recreation trips. Second, fishing trip data was only collected for trips to freshwater sites in the region. Any saltwater anglers who didn't also take a freshwater fishing trip would be excluded from the total number of anglers. Finally, respondents were asked to only consider their recreation activities for the past 12 months. Consequently, the survey would have excluded people who considered themselves anglers, but haven't actually fished in the past 12 months.

Recreation participation rates from the Phase IA survey are reported by state or province of residence in Table 2-4. Participation rates for Idaho, Montana, and Alberta are somewhat higher than the 68 percent participation rate for all regions. This may be due to some type of sampling bias or to actual differences in participation rates. While a participation rate of 68 percent cannot be verified through comparison with other reported statistics, it doesn't appear to be unreasonably high.

Table 2-4. Phase IA Survey Participation Rates for Water Based Recreation

State/Province	Yes	%	No	%
Washington	267	66%	134	34%
Oregon	155	67%	75	33%
Idaho	68	73%	25	27%
British Columbia	38	66%	20	34%
Alberta	19	76%	6	24%
Montana	18	75%	6	25%
TOTAL	565	68%	266	32%

2.4.2 Characteristics of Non-Recreators

The survey gathered a variety of information from non-recreators in order to identify which factors influence the recreation participation decision. First, specific reasons for not participating were explored and second, demographic characteristics were requested. The 266 non-recreators were asked to respond to a list of eight possible reasons for their lack of participation. Table 2-5 shows these reasons and the number of times a yes response was recorded, along with the percentage of the 266 respondents who answered yes. The most common reason for not participating was that the

respondent was too busy. The second most common reason was not owning a boat. This result was not anticipated, so it prompted additional analysis. It was found that although these respondents were located throughout the region, this was the most frequent reason among persons living in counties adjacent to the federal projects. Furthermore, "lack of time" was also relatively less important to this group of respondents than it was to all non-recreators. Finally, fewer than 10 percent of all non-recreators and 5 percent of those living in proximate counties said that fluctuating water levels in lakes and rivers was a reason for non-participation. This may indicate that operating changes aren't necessarily an important factor in the decision to participate or not participate. However, this outcome has no bearing on the importance of water levels to the destination decision of recreators.

Non-recreators were then given an opportunity to state their own reasons for not participating. Out of 116 people responding, 40 indicated that they were too old. This suggests a point that will be reiterated below: age is an important determinant of participation in water based recreation. Furthermore, 16 respondents cited reasons relating to health, some of which could be age-related, e.g., arthritis. Lack of interest in water-based activities is the only other response which occurred with some frequency (22 responses).

Table 2-5. Phase IA Survey Participants Reasons for Not Participating in Water Based Recreation

Reason	Number of Yes Responses	Percentage of Non-recreators
You are too busy	136	51.1
You don't own a boat	129	48.5
You do not enjoy water based activities	97	36.5
You live too far from the water	64	24.1
It is usually too crowded	54	20.3
It is too expensive	49	18.4
The water quality is poor	45	16.9
The levels reservoir and river levels change too much	21	7.9

There are a number of demographic differences between recreators and non-recreators, as shown in Table 2-6. First, non-recreators are on average older than the recreators. This is to be expected since some forms of water-based recreation are physically demanding. Second, non-recreators in the survey also tended to have smaller households, due primarily to the absence of children (household members aged 18 or younger). These results are consistent with the differences in ages between the two groups.

Table 2-6. Phase IA Survey: Demographic Characteristics of Recreators and Non-Recreators

Characteristic	Recreators (s.d.)*	Non-recreators (s.d.)*
Mean Age	39.7 (13.1)	52.3 (18.0)
Median Age	39	53
Average Household Size	3.07 (1.45)	2.34 (1.33)
Average Number of Children in Household	1.06 (1.23)	0.46 (0.96)
Mean Income	\$42,939 (22,162)	\$32,963 (22,261)
Median Income	\$35,000	\$25,000

*s.d. = Standard Deviation

Finally, mean 1992 household income for the non-recreators is about \$10,000 below the mean income for recreators. Fewer than 20 percent of the non-recreators cited expense as one of the reasons they didn't participate in water-based recreation. It ranked sixth out of the eight reasons for yes responses (see Table 2-5). This suggests that income may not be very important. It is possible that this ambiguous result is due to the relatively high incomes indicated by the survey. A comparison of median

income figures from the survey results and median income figures from Statistical Abstract of the United States: 1992 shows that the survey is consistently higher. This may be due to some form of self-reporting bias or it may be due to survey participation bias. For example, if a disproportionately large number of higher income people responded to the survey, that could diminish the importance of income to recreation participation in the results.

The survey results also indicate that gender influences the participation decision. Female respondents, who accounted for 47.7 percent of the completed surveys, comprised 59.3 percent of the non-recreators. This is due to the different participation rate between men and women. Almost 75 percent of the men surveyed were recreators, while only 60 percent of the women were recreators. As noted earlier, differential male/female survey participation rates and recreation participation rates may be producing the higher recreation participation rates for Idaho, Montana, and Alberta that were reported in Table 2-4.

2.4.3 Participation Rates in Specific Activities

Collecting data on the number of trips that were taken for a specific recreation activity is important for two reasons. First, it indicates what type of recreation activities are more important than others. Second, it illustrates the degree to which individuals currently substitute across activities.

Trip information was collected for the following activities: fishing, boating, swimming, other water-based, nonwaterbased, and multiple activities. The last activity category was included to identify recreational trips that were primarily multi-purpose. For each of the six activities, a respondent was asked how many trips he took in the past 12 months where the main purpose of the trip was to engage in that activity.

This type of trip information was requested in the two different branches of the survey. The 377 recreators who followed the reservoir branch of the survey gave activity information for their reservoir trips. In the river branch, 314 people gave activity information in for their river trips.

Table 2-7 shows, for each of the six activity categories, the number of respondents who took at least one trip. The results are divided into three columns. The first shows how many of the 565 total number of recreators engaged in each activity regardless of whether the trip was a reservoir trip or a river trip. The second column shows these results for the subset of people who made reservoir trips. Finally, the third column contains the people who took river trips and the activities they engaged in on those trips. The percent is reported next to each number.

Recreation trip modeling is difficult when trips involve multiple activities; it is less complicated when trips are activity specific, e.g., waterskiing trips or fishing trips. The information of particular interest in Table 2-7 is the large number of respondents who took multiple purpose trips; in fact, more people took multiple purpose trips (316) than any other kind.

Table 2-8 shows that recreators engage in a variety of activities. This table demonstrates the variety that occurs across trips rather than during trips. The numbers in the left column indicate how many different "types" of trips an individual reported taking.

The averages are conditional means; e.g., given the subset of recreators who took at least one fishing

trip to reservoirs, the number indicates the average number of reservoir angling trips this group took in the past 12 months.

The median number of trips per person are also reported since the averages tend to be biased upwards by recreators who reported large numbers of trips. Two conclusions can be drawn: trips to reservoirs are fairly evenly distributed across the six activities, whereas trips to rivers are less evenly distributed; and more trips per person are taken to reservoirs. As the results show, the average number of reservoir trips is almost everywhere higher than average number of river trips. The two numbers are similar only for fishing and non-waterbased activities. The range of average trips across activities is smaller for reservoirs (Two trips) than for rivers (Four trips). These results suggest that recreation at reservoirs is more intensive, i.e., visitors take more trips on average. Furthermore, no activities routinely dominate reservoir recreation.

2.4.4 Federal Project Visitation

This section discusses two important categories of results pertaining to the trip data gathered for each of the Federal projects. First, overall participation rates are reported. These indicate which projects attract more visitor and trips. Second, origin/destination results are presented.

Table 2-7. Phase IA Survey: Number of Recreators Taking Trips by Activity

Primary Activity	Total ^{2/}	Reservoir	River ^{1/}
Fishing	258 (45.6%)	197 (52.4%)	189 (60.6%)
Boating	248 (43.9%)	198 (52.6%)	123 (39.4%)
Swimming	240 (42.5%)	178 (47.3%)	141 (45.2%)
Other Water Based	181 (32.0%)	121 (32.3%)	113 (36.2%)
Non-waterbased	279 (49.4%)	206 (55.2%)	174 (56.1%)
Several Activities	316 (55.9%)	236 (63.6%)	186 (59.8%)
^{1/} All numbers exclude outlier ^{2/} Reservoir and river numbers will not sum the total since some respondents will be reflected in numbers at both locations.			

Table 2-8. Phase IA Survey: Average Number of Trips by Activity

Primary Activity	Reservoir		River	
	Mean (s.d.)*	Median	Mean (s.d.)*	Median
Fishing	8.7 (13.46)	5	8.9 (11.55)	5
Boating	7.5 (12.36)	4	4.7 (5.8)	3
Swimming	9.1 (14.27)	5	7.9 (12.99)	3
Other Water Based	7.6 (10.46)	4	5.3 (5.91)	3
Non-water based	7.1 (9.92)	4	6.9 (15.38)	3.5
Several Activities	8.6 (10.06)	5	6.9 (7.39)	4

*s.d. = Standard Deviation

2.4.4.1 Participation Rates

The trip information should indicate two things. First, it should indicate which locations and activities are relatively more important in terms of water-based recreation, if indeed any are. Second, the trip information provided by each respondent should indicate whether there is a propensity to substitute across recreation sites and/or activities. Furthermore, since it is also known where the respondents live and which Federal projects they have visited, conclusions can be derived regarding travel patterns to the projects.

Trip information for the Federal projects was collected from the 377 respondents who answered questions in the reservoir branch of the survey. For each project, they were asked to give the number of trips they had taken to that project in the past 12 months. A total of 234 (62 percent) respondents took at least one trip to a project (project users).

The demographic characteristics of project users were compared with other recreators who did not visit the projects. The results indicate that two

groups are quite similar in terms of age and household characteristics. The one exception is that project users have slightly lower household incomes.

Project-specific trip results are reported in Table 2-9, which shows the number of respondents who visited each project. The third column reports the mean number of trips per person to each project. The mean trip figure is a conditional mean, i.e., the average "conditioned" on the fact that the individuals visited the project at least once.

Among the projects drawing the most visitors in the sample were Bonneville and The Dalles. This not surprising given their proximity to large population centers and major highways. The Snake River between Brownlee and Lewiston/Clarkston, which is relatively more isolated, also drew a large number of visitors. As expected, those with the fewest visitors were Dworshak, Libby, and Hungry Horse, which are relatively remote headwaters reservoirs.

The recreation patterns of the former will dominate the results. Consequently, if they are more likely to visit the closest projects such as Bonneville and less likely to visit distant projects such as Dworshak, then the final results will show more visitors for Bonneville and fewer for Dworshak.

2.4.4.2 Destinations and Origins for Water-Based Recreators

A fundamental assumption economists make in travel cost/recreation demand models is that the further an individual lives from a recreation site, the less likely (other things held constant) that individual is to visit the site. This is based on the idea that a recreator faced with two alternative destinations that are equal in every other respect will maximize net benefits by visiting the closer site, i.e., by minimizing travel costs. Travel, including the cost of travel time, can make up a large share of the overall cost for recreation activities, such as fishing and boating, which require travel to specific locations. Origin and destination relationships for trips to the Federal projects were studied to verify that travel cost is indeed a factor in recreation site decisions.

Table 2-9. Phase IA Survey; Participation at Federal Projects for the 565 Participants in Water Based Recreation

Project	Participants	Mean Trips per Person (s.d.)
Grand Coulee/Lake Roosevelt	56	3.5 (5.96)
Chief Joseph/Rufus Woods Lake	59	2.5 (5.20)
McNary Dam/Lake Wallula	49	4.1 (7.08)
John Day/Lake Umatilla	60	3.3 (6.40)
The Dalles/Lake Celilo	72	2.8 (3.12)
Bonneville/Lake Bonneville	83	3.7 (3.66)
Snake Between Lewiston and Brownlee	79	2.7 (3.07)
Snake Between Lewiston and Tri-Cities	52	3.1 (3.38)
Dworshak/Dworshak Reservoir	18	2.0 (1.41)
Hungry Horse/Hungry Horse Reservoir	18	2.1 (2.08)
Libby Dam/Lake Koocanusa	16	6.8 (13.6)
Albeni Falls/Lake Pend Oreille	37	3.2 (5.96)

Project visitation data is shown disaggregated by state or province in Tables 2-10 and 2-11. The first table contains information regarding the number of respondents who visited each project. Table 2-11 reports the total number of trips that were recorded for each of the projects by state or province of origin. In spite of the large region

involved, these results still suggest that location is an important determinant for trip-taking behavior. For example, households in western Montana were more likely to visit Hungry Horse, Libby, or Albeni Falls than the other projects, while Oregon residents were less inclined to visit these projects than the ones on the Columbia River.

Table 2-10. Phase IA Survey: Number of Households Visiting Each Project by State/Province

Project	Total	Idaho	Montana	Oregon	Washington	Alberta	British Columbia
Grand Coulee	56	4	0	8	43	0	1
Chief Joseph	59	11	0	17	29	0	2
McNary	49	4	0	17	25	0	3
John Day	60	4	2	29	24	0	1
The Dalles	72	10	2	31	27	0	2
Bonneville	83	8	1	39	33	1	1
Middle Snake	79	2	1	17	31	0	1

Table 2-10. Phase IA Survey: Number of Households Visiting Each Project by State/Province – CONT

Project	Total	Idaho	Montana	Oregon	Washington	Alberta	British Columbia
Lower Snake	52	9	1	9	32	0	1
Dworshak	18	7	0	2	9	0	0
Hungry Horse	18	2	6	3	7	0	0
Libby Dam	16	5	4	0	6	1	0
Albeni Falls	37	10	4	3	18	1	1

Table 2-11. Phase IA Survey: Total Number of Trips to Each Project by State/Province

Project	Total	Idaho	Montana	Oregon	Washington	Alberta	British Columbia
Grand Coulee	193	9	0	11	172	0	1
Chief Joseph	145	15	0	29	99	0	2
McNary	201	51	0	34	113	0	3
John Day	200	48	2	81	68	0	1
The Dalles	198	29	2	108	56	0	3
Bonneville	304	17	1	207	77	1	1
Middle Snake	212	86	1	38	86	0	1
Lower Snake	159	45	1	22	90	0	1
Dworshak	36	20	0	2	14	0	0
Hungry Horse	38	3	19	5	11	0	0

The importance of location is evident in data disaggregated at the county level. People living in adjacent counties are twice as likely to visit a project as the average recreator in the region. County-level data also reveal that major urban populations are another important source of project visits. Residents in counties with populations of more than 100,000 took 50.1 percent of the project visits.

2.4.5 Substitution Across Projects

Substitution across the projects (and more generally across all recreation locations) is important because it influences the degree to which welfare measures will be affected by changes in system operation.

Recreation demand literature shows that changes that impact recreation at a project which does not have substitutes will have greater welfare impacts than those at one with substitutes, all other things being equal. The reason for this is simple. If access to the only recreation outlet nearby is lost, an individual is willing to pay a great deal to prevent that loss. If many alternative outlets exist, an individual would be willing to pay less to avoid the loss.

Substitution across projects is indicated in that almost two-thirds of the 234 project users surveyed visited more than one project; 156 (66.7 percent) recreators took trips to two or more of the projects. The following details how this breaks down by

number of projects visited: 60 people visited two projects; 36 people visited three projects; 27 people visited four projects; 20 people visited five projects; 6 people visited six projects; 4 people visited seven projects; and 3 people visited eight projects. This means that if operating changes affect some projects but not others which may act as substitutes, then welfare changes will be diminished.

Evidence of substitution across locations isn't limited to the federal projects, as Figure 2-1 shows. This chart summarizes the trip behavior of the 565 recreators by destination category. One group of interest is the 101 recreators (left-side path) who took reservoir trips—to both project reservoirs and other reservoirs—and river trips. All together, 160 or 68 percent of the project users also visited other reservoirs or rivers.

An anomaly in Figure 2-1 is the 111 recreators who didn't visit reservoirs or rivers (right-side path). One possible explanation is that these respondents didn't understand some section of the survey. Another

is that they engage in water-based recreation, but not at any of the sites included in the survey. For example, they may swim at public or private pools. Given that most of these individuals live near coastal waters also suggests that some may be saltwater recreators rather than fresh water recreators.

2.4.6 Recreator Attitudes

An ideal recreation demand model should include all factors that determine the choice of recreation site. Among these factors are site characteristics which affect the quality of recreation. As previously indicated, economists presume that recreators will prefer a site which offers a higher quality recreational experience to one of lesser quality, all other factors, including distance, being equal. For example, a boater located equidistant between two lakes will prefer to visit the lake that offers better boating. Site characteristics that distinguish the better lake could include the number and quality of boat ramps, docks, and marinas; water conditions such as temperature, surface area and turbidity; degree of

Figure 2-1. Destinations of People Who Engaged in Water-Based Recreation

congestion; and availability of amenities such as fuel. Section 2.3 includes a more detailed discussion the site characteristics which are relevant to different water-based activities.

The Phase I survey was designed to gather information that would indicate the importance of certain site characteristics. In both the reservoir branch and the river branch of the survey, the respondents were asked to indicate how important a site characteristic is in terms of their destination choice. The scale they were given comprised the following response choices: very important, somewhat important, somewhat unimportant, very unimportant, and don't know.

Table 2-12 shows the number of times the very important and very unimportant responses were recorded for each characteristic. Comparing the responses of all reservoir users with those of river

users reveals some similarities. First, the most important characteristic, regardless of destination, is that a site have a high environmental quality. Other characteristics drawing similar responses addressed the cost of the site and whether it was not very crowded (which are relatively important), how close the site was to home (which was considered very important by fewer than one third of the respondents) and novelty of the site (the least important characteristic).

A number of characteristics are more important for reservoir trips than for river trips: large water surface, good boat ramp access, recreational activity variety, good public facilities, and good beach area. Since these amenities are more likely to be available at reservoirs than rivers, one would expect them to be more important to reservoir visitors. The one characteristic that was relatively more important to river visitors was the quality of fishing. This is

**Table 2-12. Attitudes About Importance of Recreation Site Features
(All Numbers are Percentages)**

Characteristic	Users of Reservoirs, Lakes, Columbia & Snake Rivers						Users of Other Rivers	
	All Users		Project Users		Project Non-users		All Users	
	Very Import.	Very Unimp.	Very Import.	Very Unimp.	Very Import.	Very Unimp.	Very Import.	Very Unimp.
Close to Home	29%	07%	25%	08%	35%	05%	28%	09%
Large Water Surface	19	11	22	12	14	11	12	18
Good Fishing	40	23	45	16	31	33	46	15
Good Boat Ramp Access	43	14	46	11	37	17	26	22
Variety of Recreational Activities	49	05	55	05	40	06	32	09
New Place	08	18	11	17	04	20	8	17
Good Facilities	52	05	49	06	57	05	40	10
Good Beach Area	35	09	34	08	37	10	23	16
Not Very Crowded	44	02	46	03	40	01	48	04
Inexpensive	43	05	43	04	42	07	40	05
High Environmental Quality	76	02	78	00	73	01	76	01

consistent with the activity results reported in Table 2–7, where fishing was the most popular river activity but fourth in popularity among reservoir activities.

The results for the reservoir branch are further disaggregated into project users and non–users to see if there are any differences. In many respects the answers for these two groups are similar. Again there is agreement on the importance of environmental quality, cost, and degree of crowding. Furthermore, the presence of good beach area is relatively important to both groups. Some characteristics appear to be somewhat more important to the project users: whether a site is a new place to visit, good boat ramp access, and large water surface. Since one group that would consider boat ramps and large surface areas important are pleasure boaters, these results indicate the possibility that the projects are attracting a larger share of pleasure boaters than other reservoirs or lakes in the region. Two site characteristics are slightly more important to non–users: good public facilities and proximity to home.

The most noticeable differences between project users and non–users include the importance of good fishing and recreational variety. A larger share of the project users than non–users considered these attributes very important, and in the case of fishing quality, one–third of the non–users considered this to be very *unimportant* compared to only 16 percent of the users. First, this outcome indicates that catch rates are an important factor in the project users' choice of an angling recreation site. Second, returning to the issue of substitution across activities, the responses show this to be particularly important for project users.

2.4.7 Conclusions

The Phase IA survey resulted in a number of important conclusions about water–based recreation patterns in the Columbia River Basin.

- Non–recreators are different from recreators; they tend to be older, have smaller households, fewer children living at home, and lower incomes. This suggests that demo-

graphic characteristics are important variables that influence participation.

- Recreators engage in a variety of water–based activities as evidenced by the large proportions taking multiple purpose trips and by the large number who took more than one type of trip (i.e., trips in more than one of the six activity categories). Furthermore, whether a site supports a variety of recreational activities is found to be relatively important among the recreators who took at least one trip to a project.
- A large share of the recreators engage in substitution across location. Of the 565 recreators, 237 (41.9 percent) reported trips to both reservoir and rivers. Of the 234 project users, 66.5 percent reported visiting more than one of the projects. Furthermore, 59.4 percent of the project users visited other reservoirs, and 68.4 percent of them also took river trips.
- Demographic differences between recreators who use the federal projects and those who do not are minimal. This suggests that other factors play a more important role in the decision of whether to visit a project. These include site characteristics and location.
- A majority of the project trips recorded originated either in adjacent counties (44.5 percent) or in major population areas (50.1 percent; 17.3 percent from counties that are also adjacent to projects). These results reflect the large share of urban respondents in the general population survey.
- Recreator attitudes towards site characteristics are consistent with a number of expectations. For example, large surface area and good boat ramps are more important for reservoir trips than for river trips. The reverse is true for catch rates, which is consistent with the activity data results where fishing is relatively more popular vis a vis other activities for river trips than for reservoir trips. Some characteristics are more important to people who reported using at

least one of the federal projects than they are to people who only visited other lakes and reservoirs. These include good boat ramp access, large surface area, good fishing, and recreational variety.

2.5 FACTORS INFLUENCING RECREATIONAL USE IN THE COLUMBIA BASIN

2.5.1 Seasonality of Visitor Use

Table 2-13 summarizes the 1989 monthly visitation to three typical projects in the region, lakes Umatilla, Dworshak and Koocanusa. The seasonality of recreational use is a very important consideration in analyzing the potential effects of reservoir operations. While pool elevations and river flows are important factors influencing the seasonality of recreational use, they are not the only factors. Other factors that must be considered include weather conditions and the availability of other similar recreation resources. The primary recreational activities, including sightseeing, fishing, boating, and waterskiing occur year round at most of the project areas in the basin. However, the peak period of use occurs during the warm, dry summer months.

Annual visitation typically builds slowly, beginning in April and continuing in May. This corresponds to

the period during which the storage projects are beginning to refill. The weather at that time of year is variable; it is improved over the winter but can still be very cool and damp, particularly at the upper elevation storage projects such as Libby and Hungry Horse. Much of the visitation to the projects during the spring can be directly attributed to the opening of fishing seasons.

Visitation tends to increase rapidly from the end of May through June and July, and peaks in August. As shown, the projects typically receive over 50 percent of average annual visitation during this period. The term "peak recreation season" roughly corresponds to the period between Memorial Day and Labor Day weekends. During this period, weather is most amenable for water-dependent and water-related recreation activities throughout the Pacific Northwest. Most students are out of school for the summer, and families take their vacations during this period. During the summer, the storage projects are generally refilled and held as high as possible to promote and support recreation use.

Visitation generally begins to decline in September. This decline occurs regardless of reservoir operations. For example, pool elevations at John Day Project/Lake Umatilla, stay relatively stable year-round; like most run-of-river projects, it does not experience large seasonal drawdowns. Nonetheless,

Table 2-13. Seasonality of Columbia River Recreation Use, 1989

	Monthly Use as a Percent of Total Annual Use		
	Lake Umatilla 1/	Lake Dworshak 2/	Lake Koocanusa 3/
January	3.4	2.4	1.2
February	3.6	3.5	1.6
March	5.8	6.6	3.6
April	7.7	6.3	5.5
May	8.6	9.6	8.8
June	11.3	16.6	11.6
July	13.5	20.2	20.4
August	15.2	17.7	23.4
September	12.8	7.2	13.3
October	9.6	4.8	6.0
November	5.1	2.6	2.9
December	3.5	2.6	1.6
1/	Corps of Engineers, Portland District		
2/	Corps of Engineers, Walla Walla District		
3/	Corps of Engineers, Seattle District		

approximately 45 percent of average annual visitation occurs during the three peak summer months. In comparison, Lake Koocanusa, a storage project with large seasonal pool fluctuations, receives approximately 55 percent of its total visitation from June through August.

Weather is the most important factor influencing the seasonal use and demand for water-related outdoor recreation in the basin. Climatic effects (such as temperature and precipitation) have direct short and long-term effects on visitor use. During wet years, there generally is adequate water to maintain high pool elevations in the storage reservoirs across the basin. Because such a high percentage of visitation occurs during the short summer season, a cool, wet summer can have low annual total visitation no matter at what elevation the reservoirs are maintained. This is especially true if the weather is poor during one or more of the three important summer holiday weekends (Memorial Day, Fourth of July, or Labor Day).

By the same token, during hot, dry summers, demand for water-related recreation can be very high. Visitation to rivers and reservoirs may be high in spite of low pool elevations or flows. This is especially true if there are few or no other similar recreation resources near the users.

2.5.2 Accessibility to Water

Accessibility to water is a critical factor in influencing recreation use; the more accessible a water body is to users, the higher the recreation use will be. Access to water is directly influenced by reservoir pool elevations and downstream flows.

2.5.2.1 Usability of Water-Based Recreation Facilities

One of the primary effects of large seasonal drawdowns in storage reservoirs is a reduction in the usability of recreation facilities. Most of the recreation facilities at the reservoirs are designed to remain operational during the summer recreation season. During low water years, water levels may drop so many of the facilities remain unusable for some or all of the peak recreation season.

This effect may also occur at run-of-river reservoirs and downstream river segments but is generally

less pronounced since the smaller physical variations in pool elevations and flows allow facilities to remain usable across the full range of normal operations.

Types of facilities that are directly affected by reservoir operations include boat ramps, fixed and floating boat docks and moorage, and swimming beaches. Certain land-based facilities, including picnic and camping sites, trails, and parking areas may also be indirectly affected.

Boat ramps generally become unusable as water levels drop near or below the end of the ramp. Most ramps require a minimum water depth of 3 feet at the toe to be fully usable. Depths of less than 3 feet limit the functional use of a ramp by restricting the size of boats that can be launched and also create safety hazards. In some cases, even 3 feet of depth may not be adequate to allow launching of larger boats, particularly fixed-keel sailboats.

At the larger storage reservoirs, many of the ramps are located on steep slopes. Large drawdowns may require boat launchers to negotiate long and steep ramps. This greatly increases the difficulty and time required to launch each boat. This is especially true at those ramps where there is not enough room to provide a turnaround or low water parking lots. Without low water parking, boaters may have to transport their vehicle and boat trailer long distances from shoreline to boat and back again. Even where boat ramps remain in the water, these impacts of drawdown may discourage many users, particularly the elderly and disabled.

As noted above, most of the ramps on the run-of-river reservoirs on the Columbia and Snake Rivers are designed to remain usable over the normal (average) operational range of the reservoirs. Relatively few ramps are designed to remain usable at pool elevations below the minimum operating pools at any of the lakes. Some of the ramps become only marginally usable at minimum pool with inadequate depth for safe launching of larger trailered boats.

Marinas and Fixed and Floating Boat Docks generally are designed to remain usable over the normal operational range of the reservoirs during peak recreation seasons. However, as water levels fall,

water depths in sheltered marinas and boat basins become shallower, restricting boat access to facilities. Fixed and floating boat docks may become increasingly unusable as the amount of moorage or float space remaining in water decreases. At some marinas, shallow water conditions limit the use of a certain number of moorage spaces close to shore.

Shallow depths within protected boat basins, often caused by sedimentation and shoaling, can be a problem at low pool elevations.

Dredging may be an acceptable option for mitigating low-flow impacts at some of the boat ramp, marinas and boat moorage sites in the study area.

Figure 2-2. Typical Effects of Drawdown on Boating Facilities at Storage Reservoirs (Lake Koocanusa)

Figure 2-3. Typical Effects of Drawdown on Swimming Beaches at Storage Reservoirs (Lake Koocanusa)

Figure 2-4. Typical Effects of Extreme Drawdown at Run-of-River Reservoirs (Lower Granite)

Swimming Beaches. Swimming occurs at developed swimming beaches as well as at dispersed locations around the entire shorelines of the Columbia River Basin's lakes and rivers. Developed swimming beaches are generally more sensitive to water level fluctuations than other types of facilities. Beaches are most usable within at least 5 feet of full pool. There is usually a rapid degradation in usability after that level. This is because most swimming beaches are used by families with children. The beaches are generally designed to provide safe swimming opportunities up to about 6 to 7 feet in depth. After around 5 feet of drawdown, beach areas become marginal for swimming by even small children.

Adults and older children can swim anywhere in the lake and are not necessarily constrained to a safe beach area. To some extent, as water levels are lowered a greater amount of shore area becomes

available and access to a water body may be improved. This is important because sunbathing, socializing and shore-play are often important components of the activity "swimming." Larger sand beach areas are also desired by windsurfers and waterskiers who use the shoreline for takeoffs and landings. When beach areas are limited, some of these activities may be restricted. On the other hand, if beach substrates are muddy, rocky, stumpy, or otherwise unappealing, their exposure from drawdown or low flows may have a negative impact on swimmers.

In some river reaches and run-of-river projects, high flows may also impact swimming beaches by inundating facilities and eroding swimming beach areas. High flows may also create unsafe swimming conditions.

Irrigation Intakes. Many larger parks and recreation areas use either river water or well water to irrigate grass areas and other plantings. This is particularly true along the run-of-river projects on the Columbia and Snake Rivers. Most park irrigation intakes are designed to remain operational over the full range of reservoir operations. However, most of the irrigation systems operate less efficiently at low pool levels since the water has to be drawn up higher distances. In addition, because of local physical constraints, some irrigation intakes are located high enough so that they will not be able to draw water at minimum operating pool.

Short-term drying of park irrigation intakes is not a serious problem; long-term drying of intakes could result in either serious damage to park landscaping and plant materials, or to requirements for costly alternatives.

2.5.2.2 Land-based Facilities

Camping and picnicking facilities, trails, parking areas, and other land-based recreation facilities are not directly affected by water-level fluctuations. However, indirect impacts include an increased distance from the facilities to water, and large drawdowns decrease aesthetic quality.

Visitation to these facilities is primarily affected insofar as visitor use patterns may change in response to effects on associated water-based recreation activities such as boating or fishing. Many of the major recreation sites on the river were designed and built as destination sites; recreationists are attracted to them because of the full complement of recreation opportunities that they provide. As swimming beaches, boat ramps, moorage and other water-dependent facilities become unusable, recreationists will begin to use other alternative sites within the region that provide the full range of activities desired.

2.5.3 Water-Surface Area (Recreational Carrying Capacity)

As the water levels fluctuate in reservoirs and rivers, the amount of surface area available for water-based recreational use changes. At the large storage

reservoirs where large seasonal drawdowns substantially diminish lake surface areas, the impact on recreational carrying capacity can be significant.

As a result of these effects, boaters, waterskiers, anglers, windsurfers, and swimmers may be concentrated into smaller areas. The numbers of recreationists and types of activities that may be safely accommodated at a water body may be reduced. Congestion is not a serious problem in the basin except during peak use periods at popular access points such as Hood River during windsurfing events. Generally, surface area is not as critical a factor in constraining recreational carrying capacity as are other factors such as access facilities.

Because of the steep, confined topography of the Columbia River and Snake River channels, a drop in pool elevation will not cause a correspondingly large reduction in lake surface area except at a few locations where the lakes inundate former terraces or bottomlands and the bottom is flat or shallow. However, these locations tend to be popular sites for water-based recreation.

An existing safety concern at Hood River, The Dalles, and other locations in the region is the potential for conflicts between windsurfers and barges and other commercial craft in the navigation channel. Decreases in the size of the pool at high-use areas, such as Hood River and The Dalles, may shorten the reach that windsurfers have to sail, concentrating more participants into a smaller area in the channel. Under present operations, and at present levels of windsurfing and navigation use this has not been a serious problem; education and coordination between commercial navigators and windsurfers appears to have solved most of the issues.

In some cases, reduced water area in lakes and rivers concentrates fish, possibly improving chances for fishing success.

2.5.4 Recreational Safety Hazards

Reservoir operations and the resulting fluctuations in pool elevations and stream flows can cause a variety of different safety hazards for recreationists.

2.5.4.1 Exposed Hazards

Low water levels may expose dangerous tree stumps, rocks, and shoals that are hazardous to activities such as boating, waterskiing, and windsurfing. The rocky shoreline of the Columbia River is dangerous under normal operating conditions; most recreationists are aware of the normal hazards. A change of operations, such as dropping reservoir pools or river flows below normal operating conditions, will expose

new rocks, shoals, stumps and other hazards with which recreationists are not familiar.

Sandy shorelines on the Columbia River downstream from Bonneville Dam, particularly those around Government, Reed, Lemon, and other islands, become very popular in summer for boating, waterskiing, and camping. As water levels drop, the beaches in this area of the river become larger and more appealing. Eventually, however, as water levels become extremely low, sediments and large shoals restrict boat access to side channels and islands.

Figure 2-5. Typical Exposed Shoreline Hazards Following Drawdown

2.5.4.2 Water Velocity and Flow-Related Hazards

High water velocities are an existing hazard in the system. The powerful hydrodynamics associated with operation of the dams can be particularly dangerous for small craft. Safety hazards for recreational navigation occur both above and below the dams during releases. For example, releases from the navigation lock at The Dalles Dam create significant turbulence in the tailwater area downstream.

High velocity flows from some of the dams in the system may also result in undesirably low water temperatures downstream. This occurs at Hungry Horse Dam, where releases create low temperature flows in the Flathead River downstream. In addition to being unappealing for swimmers, rafters, and possibly fishermen, this may also be a safety hazard.

River velocities vary considerably with natural river flows. Most recreationists are prepared to deal with a wide range of water velocities as a natural hazard. There are some special hazards, however, that must be considered. Jetties and other in-water obstacles in the vicinity of the projects create special flow-related hazards. Boating, swimming, or other recreation accidents, injuries and fatalities may occur as a result of high flow velocities.

One special hazard involves the anchoring of fishing boats in high flow areas, particularly in tailrace areas below Bonneville and the other dams. The river below Bonneville Dam is a very popular sturgeon fishing location. There have been numerous cases of capsized boats and drownings in that area over recent years by boaters attempting to anchor with inadequate equipment or knowledge.

Figure 2-6. Changes in Flows Released from Dams Creates Boating Safety Hazards

Oregon State Marine Board has recommended that safety zones and navigational barriers near the dams should be established and signed, and the possibility of providing sound warnings during releases should be considered.

2.5.5 Other Physical Effects

2.5.5.1 Shoreline Erosion

Shoreline erosion caused by wind-driven wave action has impacted recreation facilities and made access difficult in some places around the shorelines of the reservoirs. Wave-cut erosion at the low pool line has contributed to significant damage around the shoreline of many lakes and may impact facilities such as the toes of boat ramps. Erosion at the maximum pool level has created precipitous slopes along the edge of some of the lakes. During the winter at high pool periods, wind-driven waves may cause significant bank erosion problems.

In addition to impacting facilities at developed recreation sites, erosion also impacts general recreational use and access at dispersed locations along the shoreline. Erosion can also severely impact cultural resource sites.

2.5.5.2 Shoaling

Deposition of sediments and creation of shoals creates difficulties for recreational navigation. Shoaling is a particular problem at the mouths of smaller tributary streams entering the run-of-river project on the Columbia and lower Snake Rivers. Construction of shoreline facilities at many sites on these lakes requires special designs to prevent severe sediment deposition. Some parks and marinas have continuing dredging requirements due to sedimentation.

2.5.5.3 Seep Lakes and Embayments

Along the lower Columbia and Snake Rivers there are numerous small lakes separated from the main stems of the river by railroad and highway embankments. These water bodies fluctuate up and down with the run-of-river reservoirs. Some of these lakes are connected directly to the river by culvert or

channel, while others are fed directly by seepage or groundwater. Drawing the reservoirs down causes a corresponding drop in depth and surface area of the lakes with potentially negative effects on the recreational fishery and riparian wildlife habitat.

2.5.6 Water Quality

Water quality has a direct effect on the suitability of water bodies for many recreation activities. Complicating any assessment of the effects of water quality on recreation is the fact that, while many of the individual parameters of water quality (turbidity, clarity, odor, or aquatic growths) are easily perceived by human sensory organs, many others (coliform bacteria, Ph, and toxic chemicals) are generally perceived only through scientific measurement techniques not available to the ordinary recreationist.

The Environmental Protection Agency (EPA, 1978) distinguishes between objective and perceived characteristic of water quality. Objective characteristics are those, like water temperature, which can be measured using known accurate and reliable techniques. Perceived characteristics reflect how people perceive the water to be. The perception involves an assessment—possibly erroneous—of the objective characteristics and a reaction to that assessment. Recreational demand may be more closely related to perceived characteristics than the ones only a scientist can measure. The EPA has separated variables of water quality into three categories: (1) hygienic factors, (2) aesthetic factors, and (3) indirect nuisance factors.

2.5.6.1 Hygienic Factors

Hygienic factors basically are pollutants that pose direct health hazards through contact or ingestion. An important characteristic of variables in this category is that they do not change the perceived desirability of water. Since a recreationist ordinarily cannot perceive these pollutants, there is no effect on the desirability of a water body. Variables included in this category are coliform bacteria and other pathogenic pollutants, concentrations of toxic substances such as pesticides and herbicides, pH, and alkalinity.

Figure 2-7. Bank Protection is Needed to Prevent Shoreline Erosion at Many Recreation Sites

Since these hygienic factors directly affect health and safety, they are most important to participants in direct-contact recreation activities, such as swimming, waterskiing, or windsurfing, where the risk is greatest for disease, illness, or injury through ingestion or contact. To a lesser extent, knowledge of the existence of hygienic factors may also influence other activities as well.

These variables are usually imperceptible to human sensory organs, and they don't directly influence water-related, non-contact activities. However, the knowledge or belief that a water body is clean or

the fear that it is dirty may affect the psychological enjoyment of water-related activities.

System operations do not add to pathogen populations in the rivers and reservoirs of the Columbia Basin, but reduced flows or pool elevations may concentrate existing pollutants. Ingestion or direct contact with concentrations of toxic substances such as pesticides, herbicides, heavy metals, and other pollutants can also lead to injury or illness. In addition, many of these substances are carcinogenic. Substances such as pesticides and herbicides used in agriculture can be carried into the drainage system by return irrigation flows.

2.5.6.2 Aesthetic Factors

Aesthetic parameters of water quality are primarily those which can be detected by human senses and therefore alter a water body's perceived suitability for recreation use. These parameters include water temperature, odor, color, turbidity, oil and grease slicks, foam, litter and other debris, algae, aquatic weeds, and dead fish. Because the general appearance of a water body is an important factor in its acceptance for recreation use, these parameters are closely related to recreation demand. Humans are not likely to recreate in water openly perceived as dirty, so these factors are important to both direct and indirect-contact activities. In cases where water is grossly polluted, land-based activities may also be affected. The most obvious example is the negative impact of obnoxious odors emanating from an adjacent water body on camping or picnicking facilities.

One of the most important water quality variables is temperature. Excessively warm or cold water temperature has an adverse effect on the enjoyment of swimming and may be unhealthy. Perhaps more importantly, high or low water temperatures often create biological conditions unsuitable for recreation or game fish habitat (EPA, 1978). Warm water temperatures in combination with nutrients may stimulate growths of obnoxious aquatic weeds and algae. The color and clarity of water are also important for both aesthetic and safety reasons.

2.5.6.3 Indirect Nuisance Factors

Indirect nuisance factors are parameters of water quality that may stimulate or cause a nuisance or undesirable environment in waters used for recreation. Two major subcategories under this heading include conditions that stimulate undesirable aquatic growths and factors that directly and indirectly have adverse effects on aquatic life.

One potentially important water quality problem for recreationists in the Columbia River Basin is growths of algae and higher order aquatic plants.

Such growths are aesthetically unpleasant and, if excessive enough, may hinder participation in water-based activities such as swimming, boating, fishing, or water skiing. High water temperatures and nutrients (especially nitrogen and phosphorus) may stimulate growth of aquatic plants, especially when found in combination. Factors that directly or indirectly impact aquatic life include toxic pollutants, oxygen-consuming substances, temperature, and silt-forming materials.

2.5.7 Fishing Success

Fishing is an extremely important recreational activity in the basin. It is the primary activity driving a large percentage of the recreation trips to the reservoirs and rivers in the system. As shown on Table 2-2, between 13 and 33 percent of all visitors to different Corps lakes in the basin go fishing.

Fishing success is a very important influence on recreation participation. Any change in fishing success will ultimately affect overall recreation participation. Lakes or rivers with reputations as high-quality fishing locations attract increasing numbers of anglers. Correspondingly, as fishing success declines, anglers can be expected to look for alternative sites where success may be better.

If fishing success at a given lake or river declines over time, there may be a delay in the corresponding decline in visitation of several years or seasons, as anglers continue to return based on past success. Likewise, it may take several years for the reputation of an improved fishery to build to a point where visitation increases are observed.

Fishing success can be defined in terms of several variables, the most important of which are fish numbers and size. The importance of fish numbers is obvious. Fishing success is most often defined in terms of the numbers of fish caught per unit of effort (time). Fish size may not be important to some anglers. However, it is particularly important at those lakes and rivers in the Columbia Basin that support trophy sport fisheries.

The diversity of game fish species available in any given reservoir or river reach may be important and attracts fishermen. Some anglers target anadromous species such as salmon or steelhead. Others may target specific resident coldwater or warmwater game fish and still others may be interested in catching a variety of fish on any given trip. The peak seasons for fishing for different species vary, allowing anglers to target different species at different times of the year.

The reservoir elevations and river flows that are outcomes of system operation directly affect fish and fish habitat. Any operation that affects game fish species, positively or negatively, can be expected to have a corresponding effect on fishing success. Technical Appendices C, Anadromous Fish and K, Resident Fish, describe the sport fisheries available throughout the region and the impacts of operations on them. Section 2.7 summarizes angling opportunities on a project or river reach basis.

2.5.8 Wildlife Hunting and Viewing Opportunities

Wildlife is an important recreation resource in the basin. Hunting is one of the single most popular activities to occur on public and private lands throughout the basin. Although, as shown on Table 2-2, hunting comprises a relatively small proportion of the total water-related recreational use at lakes and rivers in the system. Wildlife viewing is a popular activity in its own right. In addition, the opportunity to view wildlife adds to the enjoyment of most visitors. As with fish, wildlife hunting and viewing success can be defined in terms of wildlife diversity, numbers, and size. Appendix N describes wildlife resources of the system in more detail.

2.5.9 Aesthetic Quality

Aesthetically pleasing views are a critical component of most outdoor recreation activities. Visual quality can be directly affected by operation of the system. The aesthetic appearance of the reservoirs in the system is directly related to pool elevation. In

general, a lake will appear more aesthetically appealing when it is at or near full pool than when it is drawn down. Visual quality is reduced as drawdowns expose views of mudflats, eroded slopes, and water-bleached rocks and stumps.

Visual impact of drawdown is generally most significant at the storage reservoirs, where seasonal drawdowns up to 155 vertical feet expose large zones. Exposed shorelines in the storage projects contrast significantly in color and texture with the adjacent forested uplands.

In comparison, the run-of-river reservoirs on the Columbia and Snake Rivers experience only a 3 to 5-foot daily fluctuation. The resulting drawdown does not have a significant visual impact.

2.5.10 Summary: Influence of System Operations on Recreation

Previous sections of this chapter have described the potential physical effects of river flows and reservoir elevation on recreation resources. The following section will attempt to describe the influence of these potential physical effects on recreation participation trends.

Moderate shifts in river flows and reductions in reservoir pool elevations probably have little or no effect on water-related recreation. Water-based facilities on the rivers and reservoirs of the basin usually, although not always, are designed to be usable within the normal range of water level fluctuations. Recreationists will remain relatively insensitive to moderate water level reductions as long as the capabilities of the resource and water-based recreation facilities to support such activities are not impaired.

However, as pool elevations or stream flows continue to drop, a point will be reached where the ability of a water-based recreation resource to provide quality recreation experiences begins to decline. This decline occurs as the physical effects of system operations discussed in the preceding sections become more apparent. As access to the water is

impaired, as facilities become unusable, as safety hazards become more pronounced, or as aesthetics decline, there will probably be a corresponding decline in recreation attendance.

To determine the point at which the quality of a river or reservoir for recreation begins to decline because of lowered water levels, a variety of factors need to be considered. Factors that influence the recreation characteristics of a water body include: 1) the range of acceptable operations for boat ramps and other facilities, 2) water surface area, 3) reservoir or stream-bed cross-section, 4) slope of beaches, 5) soil character of beaches, and 6) types of activities to be accommodated.

These factors are interrelated and will differ for each river and reservoir. For example, the recreation use of a wide and shallow river or reservoir would probably be more adversely affected by a 10-foot drop in water surface elevation than would a narrow and deep river or reservoir. Eventually, as water levels continue to decline, a point may be reached where the quality of recreation experiences provided by a water body, and therefore recreation demand, will drop to zero. Logically, this situation will most likely occur when the physical resources can no longer support recreation activities. The most obvious example is that water-based activities must cease when all the water in a river or lake is withdrawn.

Under present operating conditions, there is generally enough water in all of the lakes and rivers to meet recreation needs throughout the basin during wet and normal water years. However, in dry years, natural water shortages may drop water levels of rivers and reservoirs in the basin to the point that recreation demand is affected.

In order to accurately assess the effects of water level reductions on recreation participation, some other factors need to be considered. Sensitivity to water withdrawals varies between different activities. Water-based recreation activities, such as boating,

swimming, and fishing, will obviously be more sensitive than land-based activities, such as picnicking or sightseeing, since the former are directly related to water on a performance level while merely providing an aesthetic complement for the latter.

Even among water-based activities, performance requirements vary. Certain types of boating activities such as waterskiing and sailboating require large, unobstructed water surfaces, while others, such as canoeing, kayaking, and rafting, are best done on small water surfaces and swift-moving streams. For example, during low water years, navigation in the Hells Canyon reach of the Snake River may become very difficult for some of the large tour boats that normally travel it while it remains accessible to smaller craft, such as rafts, drift boats and kayaks.

The level of sensitivity of various activities to water level fluctuations is an important consideration because it may help to determine the change in the mix of recreation activities that may occur as a result of proposed changes in operation of the Columbia River system. A related point is that recreationists engage in a combination of activities. Few people go on a trip only for boating, swimming, or picnicking; they frequently combine several activities. The distribution of time among those activities may change in response to changes in system operations.

In other words, in addition to influencing total numbers of recreation participants, low water levels may also influence the ways in which people choose to recreate. Most likely, as the level of drawdown becomes more severe and effects on recreation resources more apparent, there may be a shift away from water-based activities while land-based activities become relatively more important.

2.6 MANAGING AGENCIES/ENTITIES ROLES AND RESPONSIBILITIES

This section provides a brief description of the authorities and responsibilities of agencies and entities managing recreation facilities or resources in the region.

2.6.1 Federal Agencies

2.6.1.1 Corps of Engineers

The Corps constructed and operates 12 projects in the SOR study area. The Corps is the Federal agency primarily responsible for managing recreation resources and providing recreation facilities at those projects. Historically the Corps has relied on the assistance of non-Federal sponsors to assist in the construction, operation, and management of its recreation areas and programs.

The Flood Control Act of 1944 gave the Corps specific authority to provide public outdoor recreation facilities at its projects. Section 4 of the Act states, in part:

“The Chief of Engineers is authorized to construct, maintain and operate public park and recreational facilities in reservoir areas under control of (the Department of the Army), and to permit the construction, maintenance and operation of such facilities”.

Public Law (P.L.) 89–72, the Federal Water Project Recreation Act of 1965, mandated that full consideration be given to outdoor recreation and fish and wildlife enhancement as equal project purposes; that planning relative to the development of recreation potential be coordinated with existing and planned Federal, state and local public recreation developments; and that non-Federal public agencies be encouraged to provide not less than 50 percent of the recreation facilities development costs and assume all operations, maintenance, and replacement of recreation facilities after construction was completed.

Although P.L. 89–72 was Congressionally applied to projects authorized during or after 1965, an agreement was formulated between the Corps and the Office of Management and Budget applying the cost-sharing provisions of P.L. 89–72 retroactively to all projects authorized prior to 1965.

The Corps currently administers 12 projects in the basin. In 1991, there were approximately 220 recreation sites at these lakes. Some sites are managed directly by the Corps. However, most of the sites are managed by other Federal agencies, including USFS and the USFWS, the states of Oregon, Washington, and Idaho, and a variety of other local entities such as counties, cities, and port districts,

Other agencies manage large natural resource areas for recreation along with other purposes. The USFWS, and Idaho, Oregon and Washington state fish and wildlife agencies manage a number of wildlife refuges along the Columbia River. These areas have some facilities such as access, parking, trails, and boat ramps that support generally dispersed public use consistent with fish and wildlife objectives. Most of the numerous state and Federal fish hatcheries along the river also allow public access and provide facilities to promote and interpret their missions.

2.6.1.2 Bureau of Reclamation

Reclamation constructed and operates two storage projects within the Columbia River Basin, Grand Coulee Dam and Hungry Horse Dam. Reclamation is authorized to manage recreation resources and provide recreation facilities at those projects. Similar to the Corps, Reclamation has relied on the assistance of non-Federal sponsors to assist in the construction, operation, and management of its recreation areas and programs under Public Law 89–72 (see Section 2.6.1.1).

Hungry Horse Dam and Reservoir were authorized by P.L. 329 on June 5, 1944. Project construction was completed in July 1953. Authorized project purposes include flood control, power, recreation, and fish and wildlife. The dam, powerplant, and visitor center are operated by Reclamation. Remaining project lands surrounding the lake are operated by the USFS.

Grand Coulee Dam was authorized under the Rivers and Harbors Act of August 30, 1935. Construction began in 1933 and was completed in 1942. The third

powerplant was authorized by P.L. 89-561 in September 1966. Construction was completed in 1980. Congress authorized NPS to administer Franklin D. Roosevelt (FDR) Lake behind Grand Coulee Dam as a National Recreation Area in August 1946.

2.6.1.3 Forest Service

The USFS administers six National Forest units within the SOR study area. National Forest lands are managed for recreation as well as for range, timber, watershed, and fish and wildlife purposes. The National Forests offer a diversity of recreation opportunities in a wide range of settings, from primitive to developed. The USFS operates a variety of developed recreation facilities located on rivers and reservoirs in the system. These facilities include campgrounds, picnic areas, boat launches, and trails. In addition, dispersed recreational use occurs in numerous undeveloped water-related sites.

Recreational use of USFS sites and facilities is influenced by the operation of the river system to a greater or lesser extent. Much depends upon the type and purpose of the adjacent project. The Columbia River Gorge National Scenic Area and the Hells Canyon National Recreation Area are impacted somewhat by the present operation of the river. Recreation sites on Lake Pend Oreille in the Idaho Panhandle National Forests, behind Albeni Falls Dam, experience only slight effects at present. Recreation use at sites and facilities on Lake Koocanusa (Libby Dam) in the Kootenai National Forest and on Hungry Horse Reservoir (Hungry Horse Dam) in the Flathead National Forest are directly impacted by operation of the river system.

2.6.1.4 National Park Service

The NPS manages three units of the National Park System that are on or near the Columbia River. The units are Fort Clatsop, Fort Vancouver, and Coulee Dam National Recreation Area. The two forts are historically linked to the river, but they are not affected by the present operation of the system. Coulee Dam National Recreation Area, located on

Lake Roosevelt behind Grand Coulee Dam, was established in 1946 to provide water-based recreation to the general public. The operation of the river system directly impacts the recreation use of Lake Roosevelt.

Recreation and other interests on Lake Roosevelt are managed under an agreement that spells out the management authority and geographic areas that are under the jurisdiction of each entity. The managing entities are Reclamation, the NPS, the Colville Confederated Tribes, and the Spokane Tribe of Indians. The NPS manages approximately 55 percent of the total reservoir and related lands under the title of Coulee Dam National Recreation Area. The NPS is authorized by Congress to administer federal project areas for recreation use pursuant to cooperative agreements. In 1970, Congress redefined the National Park System and included these areas as full units of the Park System.

2.6.1.5 Fish and Wildlife Service

The FWS, as the Federal focal point for national fish and wildlife concerns, is responsible for migratory wild birds, mammals (except certain marine mammals), inland sport fisheries, and fish and wildlife research. The objective of the FWS is to assure that the American people have the maximum opportunity to benefit from fish and wildlife resources as part of their environmental stewardship responsibilities based on ecological principles, scientific knowledge and management of the nation's fish and wildlife resources. FWS also administers a national education program to promote understanding, appreciation, and wise use of resources (U. S. Department of Interior, 1979).

The FWS is authorized to administer Federal lands that are managed as habitat refuges for the nation's fish and wildlife resources. There are two National Wildlife Refuges within the SOR study area, Saddle Mountain along the Hanford Reach of the Columbia River, and Umatilla along the John Day Project. Umatilla National Wildlife Refuge contains twenty miles of the Columbia River and adjacent uplands on both the Oregon and Washington sides of the

river managed primarily for waterfowl habitat. National Wildlife Refuge lands are open for hunting, wildlife viewing, fishing and other activities consistent with wildlife management objectives.

The FWS also manages 14 National Fish Hatcheries within the basin. Most of the hatcheries present interpretive programs and some have facilities to provide public access to rivers.

2.6.2 Oregon State Agencies

2.6.2.1 Oregon State Parks and Recreation Department

The Oregon State Parks and Recreation Department is responsible for acquisition, improvement, maintenance, and operation of Oregon's state park system. There are eight Oregon State Parks located on rivers and reservoirs in the system. Most of these are on Lake Bonneville (Bonneville Dam) and Lake Celilo (The Dalles Dam) in the Columbia River Gorge.

In addition to operating state parks, the Department gives technical assistance to local government agencies on park matters, develops and maintains the Statewide Comprehensive Outdoor Recreation Plan (SCORP), and administers the Federal Land and Water Conservation Fund matching grant program in Oregon. The Department also administers several special programs, including the State Historic Preservation Program, Oregon Recreational Trails System, and the State Scenic Waterways.

2.6.2.2 Oregon State Marine Board

The Oregon State Marine Board issues certificates of numbers and titles to approximately 180,000 undocumented vessels in the state. Marine Board revenues received from boat registrations and fuel taxes are used to enforce boating laws, for boating safety programs, and to develop, maintain, and improve public boating facilities.

The Marine Board does not operate or administer any boating facilities but cooperates with Federal,

state and local agencies to provide facilities in the state for the benefit of boaters. It also promotes uniform laws and regulations relating to boating; provides funding and training to county sheriffs and the state police to enforce those laws; publishes brochures, provides boating safety courses, and otherwise promotes safe boating practices. The Marine Board also regulates recreational boating, places waterway markers on state waters, and regulates the use of sanitary facilities on vessels to prevent pollution.

2.6.2.3 Oregon Department of Fish and Wildlife (ODFW)

ODFW formulates the general programs and policies of the state concerning the management of fish and wildlife resources and establishes seasons, methods, and bag limits for recreational and commercial take of the resource. Sport license and tag fees are deposited in the state Fish and Wildlife Fund for use by the department. In 1990 about two million sport licenses and tags were issued in the state.

ODFW also operates a variety of facilities designed to enhance fish and wildlife resources. Along the reservoirs and rivers of the system, ODFW operates and maintains fish hatcheries, wildlife areas, public shooting grounds, and hunting and fishing access areas.

2.6.3 Washington State Agencies

2.6.3.1 Washington State Parks and Recreation Commission

The State Parks and Recreation Department is responsible for acquisition, improvement, maintenance, and operation of Washington's state park system. There are a total of over 100 state parks, of which 12 are located on rivers and reservoirs in the system. The Commission also administers several special programs, including State Scenic Rivers, and boating and water safety.

2.6.3.2 Washington Interagency Committee for Outdoor Recreation

The Interagency Committee for Outdoor Recreation (IAC) facilitates investments in outdoor recreation and natural resources. IAC administers grant programs for the acquisition and development of lands and facilities for parks, water access, trails, natural areas, and wildlife habitat. IAC also conducts Statewide Comprehensive Outdoor Recreation Planning and provides technical assistance, coordination, and advocacy.

2.6.3.3 Washington Department of Wildlife

The Washington Department of Wildlife is responsible for preserving, protecting, and perpetuating the state's wildlife. The department sets times, places, manners, and quantities in which wildlife can be taken, and researches the habits and distribution of various species of wildlife in the state.

2.6.4 Idaho State Agencies

The Idaho State Parks Department is responsible for acquisition, improvement, maintenance and operation of Idaho's state park system. Idaho State Parks within the SOR study area include Dworshak at Dworshak Lake, Farragut at Lake Pend Oreille, and Hells Gate at Lower Granite Lake. The Idaho State Parks Department also administers the State Wild and Scenic rivers program.

Idaho Department of Fish and Game (IDFG) is responsible for preserving, protecting and perpetuating the state's fish and wildlife resources. IDFG also develops and manages dispersed recreational access points and facilities.

2.6.5 Public Utility Districts

Within the middle Columbia River in Washington are five run-of-river projects operated by Chelan, Douglas, and Grant County Public Utility Districts (PUDs). As part of their licensing from the Federal Energy Regulatory Commission (FERC), the PUDs were required to prepare and implement an "Exhibit R", which is a statement and plan regarding steps taken to provide public recreation in conjunction with their projects. The PUDs, in conjunction with the State of Washington and local municipalities have developed and manage extensive recreation facilities along that reach of the river.

2.6.6 Native American Indian Tribes

Tribal reservation lands adjacent to (and in some cases encompassing portions thereof) the lakes and rivers of the Columbia Basin include the Nez Perce Reservation along the Clearwater River and Dworshak Lake, and the Colville Confederated Tribes and the Spokane Tribe reservations along Lake Roosevelt. Reservation lands provide substantial recreation opportunities for Native Americans and the public. Some reservation lands are open to the public for hunting, fishing and other activities through permit systems managed by the tribes. The tribes cooperate with FWS and state fish and wildlife management agencies to increase sport fish and wildlife management efforts. The tribes have also participated in the development of marinas, resorts and other commercial recreation facilities.

2.7 RIVER REACH OR SUBBASIN DESCRIPTIONS

For purposes of describing the existing recreation condition, the basin has been subdivided into nine different subbasins or river reaches which are directly influenced by operation of the Federal dams in the system.

Figure 2-8. Lake Koocanusa

2.7.1 Kootenai River (Libby Project/Lake Koocanusa and Kootenai River downstream)

This subregion encompasses Lake Koocanusa (Libby Dam) and the Kootenai River downstream. Lake Koocanusa is located on the Kootenai River in the extreme northwest corner of Montana and southeastern corner of British Columbia (B.C.), Canada (known as the Kootenay River in Canada). Formed behind Libby Dam, Lake Koocanusa is about 90 miles (145km) long and extends nearly 42 miles (68km) into Canada with a total of 5 million acre-feet (6,170 m³) of usable storage (Figures 2-9 and 2-10). The U.S. portion of the reservoir is entirely contained within the Kootenai National Forest.

The project location is fairly remote, but accessible from regional population centers. It is approximately 140 miles (225 km) west of Kalispell, Montana; 211 miles (339 km) northwest of Missoula, Montana; and 160 miles (257 km) from Spokane, Washington. The upper end of the reservoir is approximately 20 miles (32 km) southeast of Cranbrook, B.C.

Downstream of Libby Dam, the Kootenai River follows a free-flowing meandering course, dropping about 5 feet per mile. Nine miles (14 km) west of the town of Libby, Montana the river passes over scenic Kootenai Falls, which forms a natural barrier to upstream fish migration.

Figure 2-9. Map of Lake Koocanusa - USA

Figure 2-10. Map of Lake Koocanusa – CANADA

2.7.1.1 Aesthetics

The slopes of the Purcell and Kootenai mountains adjacent to Lake Koocanusa and the Kootenai River are steep and rugged. Nearby peaks and ridges rise as much as 3,000 to 4,000 feet (900 to 1200 m) above the reservoir and river. The reservoir section of the river valley is generally linear and narrow (from 3 to 4 miles or 5 to 6 km wide) in Montana, but opens up to from 5 to 10 miles (8 to 16 km) wide in British Columbia. Due to the relatively lineal nature of the reservoir, north/south views of the reservoir and valley can extend as far as 3 to 5 miles (5 to 8 km). East/west views, on the other hand, are generally restricted by the narrow valley and the nearby steep terrain.

The valley hillsides and nearby mountains are covered with stands of coniferous trees such as ponderosa pine, western larch, and Douglas fir. A variety of riparian plants are found along the river, and to a lesser extent along the shores of the reservoir.

Most of the land adjacent to the U.S. section of the reservoir and along the Kootenai River below Lake Koocanusa is part of the Kootenai National Forest. These lands are generally managed for timber production, wildlife, and recreation. Privately owned parcels of land in the U.S. section are concentrated near the town of Libby. Most of the private land near Libby that overlooks the Kootenai River is residential. In the Canadian section of Lake Koocanusa, much of the land adjacent to the reservoir is Crown land and is managed for timber production. Private lands are concentrated near the towns of Newgate and Wardner, B.C. Land uses on these private lands include residential, recreational, and commercial. Some residential properties have views of the lake.

Most of the potential viewers of the reservoir and river are residents of nearby towns. Residents can view the reservoir and river from a number of locations including private property, local roads, and recreation facilities. Recreationists and tourists from outside the immediate area can also

view the reservoir and river from nearby roads and recreational facilities.

Most of Lake Koocanusa is physically and visually accessible by road. Montana State Highway 37 parallels the east side of the reservoir for over 20 miles (32 km) and nearly the entire west side of the U.S. section of the reservoir is paralleled by USFS roads. In British Columbia, B.C. Provincial Highway 3 crosses over the reservoir near Wardner, B.C.

2.7.1.2 Existing Parks And Recreation Facilities

Lake Koocanusa is an important regional recreational resource on both sides of the U.S./Canadian border. As shown in Table 2-14, there are over 15 developed recreational sites on both sides of the border and a number of dispersed sites. With the exception of day-use facilities administered by the Corps, all recreational facilities on the U.S. side of the lake are managed by the USFS. These include 10 developed and nine dispersed sites located primarily on the east side of the lake. Features found at USFS facilities include developed and dispersed campgrounds, picnic areas, fishing access points, boat ramps, and swimming beaches.

Lake Koocanusa Resort and Marina is located approximately 6 miles upstream from Libby Dam on the east bank. This resort is privately managed and has a special use permit from the USFS. It is the most extensively developed recreational facility on the lake and has features that include moorage slips, rental cabins, a cafe-bar-convenience store, rental boats, and a service shop. Mariners Haven Marina and Resort Campground, located at Rexford, Montana, also provides overnight and day-use facilities, a marina, and convenience store. On the Canadian side of the lake, Koocanusa Lake Campsite & Marina provides similar facilities.

The Corps manages a visitors center, viewpoint observation tower, fishing access site, boat moorage, and a day-use area.

In the Canadian section of the reservoir, there are two provincial parks located adjacent to the reservoir, Wardner and Kikomun Creek. Kikomun Creek Provincial Park is the more developed of the two and has boat ramps and a campground. Both have picnic areas and swimming beaches. The B. C. Ministry of Forests, Forest Service, operates two recreation sites with campgrounds and boat access facilities at Newgate and Englishman Creek.

Kootenay River Cruises, a private facility on the Canadian section of the project operates a campground with 15 camp sites and a charter boat service. The facility is located approximately 1 mile north of the town of Wardner. A commercial campground, boat launch ramp, marina and store is located on the west shore of the reservoir, opposite Kikomun Creek.

2.7.1.3 Principal Managing Agencies/Entities

Corps of Engineers. The Corps is the Federal agency primarily responsible for providing day-use facilities in the immediate area of the dam, both upstream and downstream. Visitor facilities include a visitor center, viewpoints, boat ramp and moorage, and several dispersed fishing access sites downstream.

The U.S. Forest Service. USFS is the major land management agency around Lake Koocanusa; Kootenai National Forest encompass the lake including the Rexford and Fisher River Ranger Districts, respectively. The USFS administers 15 recreation sites. All of the USFS recreation areas are located adjacent to the lake, including campgrounds, picnic areas, swimming beaches, boat launches, trails and trailheads, viewpoints, and historic and prehistoric sites.

British Columbia Provincial Government. The Ministry of Environment, Lands and Parks is the management authority for Kikomun and Wardner parks. These parks are well maintained and show an increase in visitation over the last five years. The Ministry of Forests manages Forest Service

recreation sites at Newgate and Englishman Creek.

Montana Department of Fish, Wildlife, and Parks. The State of Montana has jurisdiction over the fisheries in the reservoir and the river downstream. The department, under cooperative agreement with the Corps, operates and maintains the fish hatchery at Murray Springs near Rexford, Montana.

2.7.1.4 Major Activities and Use Areas

Recreational activities at Lake Koocanusa are water oriented. Fishing is perhaps the most popular activity, with 45 percent of all visitors reporting fishing and related activities as their primary recreational activity (Corps NRMS data, 1989–1993). A factor in the reservoir's popularity is that the U.S. portion is open to fishing year-round. Most anglers fish during the spring and summer from boats; however, ice fishing occurs during some winters. In the Canadian section of the reservoir and near creek mouths and large bays, anglers often fish from shore. Important game fish include westslope cutthroat, bull and rainbow trout, kokanee, Rocky Mountain whitefish, and burbot. According to NDFWP creel surveys, in 1985, kokanee accounted for 96 percent of all fish harvested from the lake. The kamloops strain of trout has been introduced by MDFWP to feed on kokanee. A reduction in the number of kokanee in Lake Koocanusa may increase their average size. Stocked Kamloops trout will provide a trophy fishery as they reach their ultimate large size.

Other recreation activities at Lake Koocanusa include picnicking, swimming, sightseeing, power boating, sailing, canoeing, camping, and hiking. Swimming and picnicking were the second most popular activities, with 25 percent of recreationists surveyed reporting the two activities to be their primary activity while at the reservoir. Swimming is particularly popular with residents from Libby, Eureka, and Rexford.

Table 2-14. Existing Recreation Sites and Facilities Lake Koocanusa and Kootenai River

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
^{1/} — Alexander Creek						3		3		
Barron Creek	1	1						1		
^{1/} — Blackwell Flats	1	1				4		4		
^{2/} — Canyon Creek								10		
^{1/} — Dunn Creek						9		9		
Downstream Vista						3		1		
Headrich RV	1	1	8	80				10		
Kikomun Provincial Park	1	2				51	1	98		
Koocanoosa Marina and Resort (Cripple Horse)	1	2	50	1500		3		50	45	1
Mariner's Haven	1	1	30	300				52	30	1
McGillvary	2	2				24	2	53		
Newgate	1	1						40		
Ostrich RV	1	1	60	500				25	55	
Rexford Bench	1	2				7		103		
Rocky Gorge	1	1						0		
Souse Gulch	1	2	5	196		44	3	0		
Tobacco Plains	1	1				12		0		
Visitor Center						2		0		
Wardner Provincial Park	1	2				7		0		
Peck Gulch	2	2				7		75		
Lake Koocanusa Marine	1	2	65	620			1	192		
^{2/} — Warland Flats	1	1				6		24		
^{2/} — Yarnell Islands						5		5		
TOTAL	19	25	218	3196	0	187	7	755	130	2

^{1/} Kootenai River below Libby Dam^{2/} Undeveloped or minimally developed sites

The Kootenai River below Libby Dam has developed into an excellent rainbow trout fishery, with success rates that are comparable to the best blue-ribbon streams in Montana. Although fishing is frequently restricted by water level fluctuations caused by hydro-power peaking operations at the dam, it is far superior to that which existed in the free-flowing river prior to dam construction. In recent years, a large but underused whitefish population has developed in the river and this population is assumed to be a factor contributing to smaller rainbow trout sizes now characterizing the catch (Skaar, 1992).

Normal minimum discharge from Libby Dam into the Kootenai River is 4,000 cfs, although under certain conditions the minimum discharge might be

reduced to 3,000 cfs. Discharges below 8,000 cfs are provided on weekends and holidays from May 1 to September 15 when practical to enhance fishing opportunities. An effort is made to maintain these flows from three hours before sunrise to one hour after sunset on weekdays. The purpose of this is to benefit anglers by improving fishing in the river.

2.7.1.5 Visitor Use

Table 2-15 summarizes visitor use at Lake Koocanusa from 1987 to 1993. Only one complete year of census data is available for the Kootenai River downstream of Libby Dam. Recreation at Lake Koocanusa is primarily summer oriented. Approximately 85 percent of the recreational use of the reservoir occurs during July, August and September.

Table 2-15. Lake Koocanusa/Kootenai River visitation summary, 1987-1993.

CORPS OF ENGINEERS RECREATION SITES								
MONTH	VISITOR-DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	7-YR AVG
Jan	7.5	7.2	5.4	5.0	1.4	1.3	1.8	4.2
Feb	8.5	9.9	7.2	7.5	1.4	2.1	2.8	5.6
Mar	9.2	11.2	8.6	8.2	6.1	5.7	5.3	7.8
Apr	18.9	14.8	17.2	11.4	15.7	19.0	11.8	15.5
May	14.5	17.4	19.8	16.1	16.2	22.2	11.9	16.9
Jun	26.7	27.1	28.9	21.4	21.5	29.4	24.5	25.6
Jul	24.8	32.3	31.0	35.2	31.7	29.2	24.2	29.8
Aug	28.4	30.5	25.2	29.9	17.5	33.5	17.5	26.1
Sep	20.6	15.6	14.8	27.7	15.6	13.5	9.6	16.8
Oct	12.0	12.7	9.8	11.5	8.4	7.3	4.7	9.5
Nov	16.6	13.2	12.2	10.4	4.4	6.9	3.9	9.7
Dec	17.0	10.1	8.7	8.7	5.9	2.6	2.9	8.0
Subtotal	204.7	202.0	188.9	193.0	145.8	172.7	121.0	175.4
OTHER RECREATION SITES								
US Forest Service	n/a	n/a	n/a	n/a	257.4	n/a	n/a	
Canadian Parks	n/a	n/a	117.0	135.8	128.6	n/a	n/a	
Kootenai River Creel Census	n/a	n/a	n/a	n/a	33.3	n/a	n/a	
TOTAL	204.7	202.0	305.9	328.8	565.1	172.7	121.0	

Approximately one-half of the recreational users of Lake Koocanusa are from Montana, with 65 percent from Flathead or Lincoln counties (Corps, 1985).

Out-of-state visitors tend to come from Idaho, eastern Washington, or British Columbia and Alberta. Recreationists can be categorized into two main groups: nonresident anglers without children who stay in campgrounds between one week and two months, and local residents who fish, picnic and swim for the day or camp for the weekend.

Fishing guide services are available on the downstream reaches of the river. This is a popular and growing aspect of the local recreation economy; records from the local guide services indicate that these anglers come from all parts of the country including the midwest, west coast and the northeast.

Creel surveys indicate that the greatest fishing occurs during the month of June.

2.7.1.6 Regional Facility Needs

Local interests believe the lack of stable pool elevations and the negative publicity associated with such operations have hindered the development of Lake Koocanusa as a recreation destination. The lake is between two highly developed recreation areas, Lake Pend Oreille in Idaho and Flathead Lake in Montana. Both of these areas offer better transportation facilities (regular air service and major highways), and operations vary only 10 feet throughout the season on the lakes. Lake Koocanusa can be drawn down over 160 feet through the season, with summer refill never assured.

Figure 2-11. Columbia River Above Lake Roosevelt

2.7.2 Upper Columbia Reach (Canada above Grand Coulee to Hugh Keenleyside Dam)

2.7.2.1 General Overview

The Upper Columbia Reach stretches approximately 80 kilometers (50 miles) from the Hugh Keenleyside Dam in B.C., to the northern tip of Lake Roosevelt near the mouth of Onion Creek in Washington State (Figure 2-12).

The scenic and recreational resources of the Upper Columbia Reach are unique in the Columbia River Basin. This reach still possesses much of the grandeur and environmental quality the river displayed before the era of industrialization. It possesses a unique sport fishery, is part of a critical winter range for wildlife, has several ancient Indian village sites along its shores, and is part of the longest navigable inland waterway in western North America.

While the Upper Columbia reach in B.C. possesses a unique set of recreational resources, it is virtually unknown to outdoor enthusiasts from outside of the immediate region. Though tourist traffic is low, it is used intensively for recreation by local residents. In 1991 local residents expended approximately 150,000 person days of outdoor recreation on the reach (Mallette, 1991).

The most popular form of in-stream recreation is fishing for a wide variety of species, especially trophy sized rainbow trout. The most popular near-stream recreation activities are sightseeing and picnicking. Hiking and swimming are also popular as access to the reach and surrounding area is excellent. Boating, both by local residents and those traveling up from Lake Roosevelt, is also popular. Each year, the reach plays host to river-boat and drag-boat races held during the summer festivals at Trail and Castlegar.

There are a number of specific sites and facilities used for recreation throughout the reach. However, a significant amount of recreation use is not site

specific. There is also a need for upgrading and construction of more infrastructure, especially a marina with boat mooring capacity.

2.7.2.2 Existing Parks and Recreation Facilities

While there is a significant amount of recreation pursued on the Upper Columbia Reach, good quality facilities and sites are limited. From river kilometer 1,192 (mile 745) at the Canada-United States International Boundary to kilometer 1,247 (mile 779.5) at the Hugh Keenleyside Dam, there are 9 identified recreation sites that may be impacted by the operation of the Columbia River System. The facilities range from developed day use facilities and boat ramps to virtually undeveloped and unmanaged recreation areas. These sites are listed and described on Table 2-16, which includes the site name, the managing agency and a summary of the facilities at each location.

While some recreational activities pursued in the reach are site specific, such as most swimming and sightseeing, a significant amount is not. For example, virtually all of the fishing is done at sites other than those listed in Table 2-16. Easy access makes the pursuit of recreation throughout the reach common place. There are a number of upland recreation sites within the study area, but they have been excluded from further analysis in the SOR because it is assumed that these sites without a direct relationship to the river will not be impacted by project operations.

2.7.2.3 Managing Authorities

There are a number of different agencies responsible for managing the recreation sites on the Upper Columbia Reach. Such agencies can be broken down into three categories. The first is service clubs. The second is municipal and regional governments. The final category is comprised of the agents and representatives of the Provincial and Federal Governments of Canada.

Figure 2-12. Map of the Upper Columbia River, Canada

Table 2-16. Existing Recreation Sites and Facilities in the Upper Columbia Reach

(River Kilometer 1192-1247 - River Mile 745-779.5)			
Number	Site Name	River Kilometer	Management Agency
1	Beaver Creek Provincial Park	km. 1198-1201 mi. 749-750.5	Ministry of Environment, Lands, and Parks
2	Rock Island	km. 1205 mi. 753	Unmanaged
3	Canada Customs Dock	km. 1208 mi. 755	Canada Customs
4	Indian Eddy Boat Launch	km. 1209 mi. 755.8	City of Trail
5	Gyro Park	km. 1209.5 mi. 756	City of Trail
6	Waterloo Eddy	km. 1230 mi. 769	Unmanaged
7	Zuckerberg Island Historical Park	km. 1237 mi. 773	Castlegar Historical
8	Robson Boat Launch	km. 1247 mi. 779.5	Unknown

The Castlegar Historical Society operates and maintains the Zuckerberg Island Historical Park (Number 7 on Figure 2-12) in Castlegar. Zuckerberg Island possesses significant historical resources, including a turn of the century Russian Mission and several ancient Indian archaeological sites.

The cities of Trail and Castlegar manage the parks and recreational facilities within their jurisdiction. These parks provide day use areas with extensive walkways and boat launching facilities (4,5).

B.C. Hydro, a Crown Corporation of the British Columbia Government, maintains and operates a lock in the Hugh Keenleyside Dam (9). There is no charge for using this bypass facility which operates year round from 8 a.m. to 4 p.m. daily. The Ministry of Environment, Lands and Parks is the management authority for Beaver Creek Provincial Park (1). This park has been poorly maintained in the last few years and the overnight campsite was recently closed.

Canada Customs maintained a boat dock (3) at the city of Trail 16 kilometers (10 miles) upstream of the Canada-United States International Boundary where boaters traveling up from Lake Roosevelt stop and phone Canada Customs to register their entrance into Canada. The dock is presently not functional and there are plans to move the facility to Indian Eddy.

2.7.2.4 Special Recreation, Preservation and Natural Resource Areas

The land-use pattern adjacent to the Upper Columbia Reach is diverse. It includes heavy and light industrial, urban cityscapes; residential, rural, small scale agricultural plots; and undeveloped natural areas. Outside of the specific recreation sites mentioned in Table 2-7, none of the adjacent land has been designated as a special recreation, preservation or natural resource area.

2.7.2.5 Major Activities and Use Areas

Fishing. The Upper Columbia Reach contains a unique and robust recreational fishery. The Columbia is considered to be one of the last, large rivers with a significant rainbow trout population left in Western North America (Malette, 1992) and is said to be the “most productive” inland fishery in British Columbia (Hume, 1991). In addition to the natural state of the fishery, it is also the benefactor of the large fish enhancement program being undertaken on Lake Roosevelt. Since Lake Roosevelt is actually a reservoir and has limited spawning habitat, a number of kokanee and rainbow trout released into the lake spend part of their life cycle in the Upper Columbia Reach feeding and spawning. Catch rates for trout and kokanee have increased significantly on the reach since the enhancement program on Lake Roosevelt got underway in the mid 1980’s (Malette, 1991).

Fishing is the most popular in-stream use of the Upper Columbia Reach. It comprises approximately 10 percent of the total recreation days. Most of the fishing activity is dispersed throughout the region. The Columbia River recreational fishery supports populations of wild and stocked rainbow trout, walleye, white sturgeon, kokanee, Dolly Varden char (bull trout), mountain and lake whitefish, burbot, brook trout, brown trout and some Chinook salmon.

The fishery is presently used almost exclusively by local residents in the evening. Since access to the river is excellent, with most areas less than a 5 minute walk from paved or good quality gravel roads, people see fishing the Columbia as part of their daily routine. In recent years the unique nature of this fishery has begun to be recognized with a number of guiding licenses being issued for the reach.

Sightseeing and Picknicking. Sightseeing and picnicking are the most popular forms of near-stream recreation use in the reach area. They comprise approximately 77 percent of total recreational days. Sightseeing is accomplished both from vehicles as well as on foot. The area is marked by many distinct natural and manmade vistas. These include an

excellent view of area mountains and high rock bluffs, old abandoned orchards and semi-rural landscapes, waterfalls, park land, forested hills and the sight of one of the few, accessible, big free-flowing rivers left in Western North America. Many people take advantage of the numerous opportunities to see wildlife in its natural habitat. Observing kokanee and rainbow trout in area creeks during spawning time is growing in popularity.

Bird-watching is also very popular as opportunities exists to view osprey, bald and golden eagles, turkey vultures, great blue herons, many species of ducks, as well as numerous other species of birds throughout the year. Due to the large number of dam projects in the Upper Columbia River Basin, the lowlands along the Upper Columbia reach have become a very important winter habitat for deer and elk in the region. While large groups of deer (up to 50) have been spotted moving along the river shore throughout the region, Fort Shepherd Flats is their prime wintering habitat. Mule deer, white-tailed deer and elk are readily seen here throughout the winter, as well as in the summer months.

Swimming. Swimming is a popular recreational activity in the Upper Columbia Reach, comprising approximately 5 percent of total recreation days. While swimming occurs throughout the area, it is concentrated at Gyro Park in Trail and at areas such as Pass Creek Park near Castlegar.

Boating. The Columbia River offers one of the few river boating opportunities in the Upper Columbia River Basin and in British Columbia as a whole. Boating occurs throughout the reach area and makes up about 2.5 percent of total recreation days. While most of the boating is done in conjunction with fishing, people do boat for the sheer pleasure of experiencing the excitement of this large free-flowing river. Access for boaters to the river is good as there are cement boat ramps which are usable to varying degrees at high, medium and low water levels at Beaver Creek, Indian Eddy and Robson. There is also a gravel boat ramp across the river from Fort Shepherd Flats and a “natural” boat access point at Waterloo Eddy.

The bulk of the boating done on the reach is done by local residents, but it is growing in popularity for tourist boaters originating from Lake Roosevelt. Boaters from Lake Roosevelt often travel up across the Canada–United States International Boundary, through the reach, and onto the Arrow Lakes via the lock in the Hugh Keenleyside Dam. The stretch of water between the Grand Coulee Dam and the northern terminus of the Arrow Lakes at Revelstoke, B.C., is 480 kilometers long (300 miles). As Lake Roosevelt grows in popularity as a tourist destination point, traffic between Lake Roosevelt and the reach is likely to increase significantly.

In addition to boating for pleasure there are two major boating events that take place on the reach each summer. In conjunction with the Castlegar Sun Festival each June, high-powered drag-boat races are held just below the Hugh Keenleyside Dam. The water conditions for drag boats are said to be optimal and speeds in excess of 240 kph (150 mph) are attained. There are also high-powered white water riverboat races held on the reach every summer.

Canoeing, kayaking, waterskiing and rafting are also pursued on the reach each summer. The waterskiing and kayaking experiences are unique to this portion of the Columbia. Local waterskiers claim that skiing on the deep, wide, portion of the river downstream of Blueberry Creek is better than on a lake. The river flows so quickly that it dissipates waves rapidly leaving waterskiers with a smooth water surface most of the time.

As the river flows past Rock Island it forms a large whirlpool from 2.5 to 4.5 meters in depth (8 to 15 feet) and a large back eddy. Kayakers can ride the large waves that range from .9 to 1.2 meters (3 and 4 feet) of this back eddy in a circular motion, spending several hours on this massive piece of rotating water.

The Upper Columbia Reach is also the site of a number of other outdoor activities. These include hunting, camping, hiking and climbing along the river and its tributary streams, as well as artifact

collecting, picnicking, berry picking and mountain bike riding.

Most of the hunting pursued along the reach is concentrated at Fort Shepherd Flats. The bulk of the picnicking is concentrated at the designated parks, but does occur randomly throughout the area. Artifacts of the Interior Salashin Indians have been found at every major creek entering this portion of the Columbia River. Picking wild huckleberries and asparagus is also pursued at different places. As previously noted, while the Upper Columbia Reach is virtually unknown to people from outside the region, it offers as diverse an amount of recreational pursuits as any river in Western North America.

2.7.2.6 Visitor Use

Table 2–17 summarizes person day estimates of outdoor recreation use in the Upper Columbia Reach (Stephenson 1984). There is no government agency or legislation that dictates the ongoing collection of recreation data in British Columbia.

Limited visitation data are available for the identified recreation sites and facilities on the Upper Columbia Reach. Information exists for Pass Creek Park which accommodated 5,000 visitors in the summer of 1981. Beaver Creek Provincial Park had 43,239 day use visitors in 1992, and as stated earlier, a significant portion of recreation activity is dispersed within the reach.

Clearly, the Upper Columbia Reach is used heavily by local residents for recreation. While it does not entertain many tourists at this point in time, the potential to do so is strong. There has traditionally been a steady, if not large, amount of boat traffic between Lake Roosevelt and the reach. As tourist traffic builds on Lake Roosevelt, it will likely translate into an increase in transboundary tourist traffic. As the impact of the fish enhancement program on the lake has acted to bolster an already strong sport fishery, this will likely act as a magnet for fishermen from across North America in the future.

Table 2-17. Person Day Estimate Of Recreational Activity In The Upper Columbia Reach

(River Kilometer 1192-1247 -- River Mile 745-779.5)		
ACTIVITY	PERSON DAY ESTIMATE	YEAR
Sport Fishing	14,850	1991
Boating (Local Boaters)	3,544	1991
Boating (Via Lake Roosevelt)	Not Available	
Swimming	7,600	1991
Picknicking & Sightseeing	119,146	1991
River-Boat Racing	3,500*	1990
Drag-Boat Racing	6,250*	1990
TOTAL	154,890	

* only includes those viewing the events

2.7.2.7 Regional Facility Needs

There is a need for a marina and mooring facilities on the Upper Columbia Reach. The construction of a marina could be incorporated into the plans to develop the Twin Rivers Park area in Castlegar. Mooring facilities could also be constructed at the boat ramps at Beaver Creek, Indian Eddy and Robson. Indian Eddy, Robson or the potential marina site in Castlegar would likely be the best sites for larger facilities.

2.7.2.8 Seasonal Nature of Visitor Use

Virtually all of the recreational activities pursued on the reach occurs from April through October. The only exception is some winter fishing and hunting which are not greatly affected by water levels.

2.7.3 Flathead River Subregion (Hungry Horse Project, Flathead River, and Flathead Lake)

2.7.3.1 General Overview

Hungry Horse Dam and Reservoir and the Flathead River lie within the Flathead Basin. The basin covers about 8,400 square miles (13,516 km²) in northwestern Montana and includes about 450 square miles (724 km²) in Canada along the west slope of the Continental Divide. Scenic mountains, canyons, and broad valleys are the major land forms in the basin. Major mountains include the Whitefish, Salish, Livingston, Flathead, Swan, and the Mission Ranges. Forests cover about 82 percent of the land area of the basin. The Flathead River drainage, most northeasterly of basins within the Columbia River system, has some 3,500 miles (5,632 km) of streams. Hungry Horse reservoir is among the 450 lakes in the basin.

The Flathead River originates at the confluence of its South and Middle Forks along the western edge of Glacier National Park in northwest Montana. From there it flows south for 9 miles (15 km) before being joined by the South Fork near the town of Hungry Horse. It then flows through a narrow canyon before reaching the town of Columbia Falls, 5 miles farther downstream. Below Columbia Falls, the river spills out into the Flathead Valley. As it progresses downstream, it meanders increasingly before spilling into Flathead Lake some 55 miles from the river's origin.

Figure 2-13. Hungry Horse Reservoir

The Middle Fork of the Flathead River originates at the northern end of the Bob Marshall Wilderness and flows in a general northwesterly direction through the Great Bear Wilderness before reaching the confluence with the North Fork. From Bear Creek downstream it forms most of the southern boundary of Glacier National Park.

The South Fork of the Flathead River originates at the southeast end of the Bob Marshall Wilderness and runs north through the heart of the wilderness before entering Hungry Horse Reservoir. The South Fork flows for 5 miles below the dam before reaching the mainstem confluence.

Hungry Horse Dam, built in 1953, is located on the

South Fork Flathead River, 15 miles south of the west entrance to Glacier National Park and 20 miles (32 km) northeast of Kalispell. The reservoir, with an active capacity of 2,982,000 acre-feet, is the farthest upstream and the third largest reservoir in the Federal Columbia River power system. The reservoir is roughly 35 miles (56 km) long and surrounded by the Flathead National Forest. (Figure 2-14)

Over 60 percent of the land in the Flathead Basin is in public ownership, with 5 percent managed by the state of Montana. The Flathead Indian Reservation covers one-fourth of the basin, which takes in the Pablo and Ninepipe National Wildlife Refuges and the National Bison Range.

Figure 2-14. Map of Hungry Horse Reservoir

2.7.3.2 Aesthetics

Hungry Horse Reservoir is located in the South Fork Flathead River Valley between the Swan and Flathead mountain ranges. The mountainous terrain adjacent to the reservoir is steep with peaks ranging up to approximately 8,000 feet in elevation. The slopes adjacent to the reservoir and river are covered with coniferous forest, while riparian vegetation is found along the river. Views from the shores and pool of Hungry Horse Reservoir are confined to the river valley and adjacent mountains. Views can extend 10 to 12 miles (19 km) up and down the reservoir.

Access to Hungry Horse Reservoir is from a local, mostly gravel road that circles the reservoir and connects to U.S. Highway 2. Because the reservoir is not visible from U.S. Highway 2, it is not seen by the numerous travelers using this route to access Glacier National Park. The primary viewers of the reservoir are recreationists using the lake or traveling by the reservoir on their way to locations upstream in the South Fork Flathead drainage. To some extent, the Hungry Horse campgrounds serve as overflow facilities when campgrounds at Glacier National Park are full.

The mainstem of the Flathead River is visible to many more people than is Hungry Horse Reservoir. The river is adjacent to U.S. Highway 2 in the Badrock Canyon reach, just below the confluence with the South Fork, and flows under the highway at the town of Columbia Falls. From Columbia Falls to Flathead Lake, the river flows through the Flathead Valley. Views near the river, however, are in some places restricted due to adjacent terrain and trees lining the river. Land uses adjacent to the river include scattered rural residential developments, and long stretches of natural appearing undeveloped lands. Primary viewers of the mainstem in this area consist of local residents, river recreationists, and motorists traveling on U.S. Highway 2.

2.7.3.3 Recreation and Natural Resources

Major recreation resources in the basin include Glacier National Park; the National Bison Range; Flathead Lake; Jewel Basin Hiking Area; Flathead National Forest, which includes the Bob Marshall, Great Bear, and Mission Mountains Wilderness Areas, and Flathead river units of the National Wild and Scenic River System; portions of Kootenai and Lolo National Forests; and Hungry Horse Reservoir. All of these resources are regionally or nationally significant.

The relatively pristine nature of the area is one of the primary recreation attractions. In addition to the area's high scenic quality, visitors have an opportunity to view an abundance of wildlife. Several threatened or endangered species are present in the area, including the gray wolf, grizzly bear, bald eagle, and the peregrine falcon. Big game species include deer, elk, and moose. Other wildlife includes migratory waterfowl, fur bearing animals, and nongame species.

The fishery of the Flathead River–Lake system is nationally renowned, attracting thousands of anglers annually. Although the system includes perch, bass, whitefish, and several species of trout, the kokanee fishery is the most important, though it has declined significantly in recent years. Most of the kokanee spawn in the mainstem Flathead River from the South Fork confluence downstream to the inlet. Hungry Horse Reservoir has one of two fishable lake bull trout populations in Montana.

2.7.3.4 General Visitation

Overall, visitation is increasing in the Flathead basin. The Montana Statewide Comprehensive Outdoor Recreation Plan (SCORP, MDFWP, 1990) predicts that visitor use will continue to increase with population growth. Out-of-state visitor use contributes to the rise in use, and the area draws international tourists to such attractions as Glacier Park as well.

Major recreation activities which occur in the basin are camping, picnicking, fishing, swimming, sightseeing, boating, waterskiing, hunting, horseback riding, and snow related activities.

Hungry Horse Reservoir is not considered a primary recreation destination spot in the basin. As pressure increases on surrounding recreation sites, overflow use goes to Hungry Horse Reservoir. Approximately 50 percent of the visitors to Hungry Horse Reservoir live within 50 miles of the reservoir. Roughly 8 percent come from a 50 to 250 mile (80 to 400 km) radius of the reservoir. The remaining visitors come from outside the region, claiming Hungry Horse as an incidental stop on there way to their primary destination within the Flathead Basin (Ben-Zvi, 1990).

2.7.3.5 Recreation Sites, Facilities and Opportunities

Hungry Horse Reservoir. The USFS manages 6,729 acres of land around Hungry Horse Reservoir by a Memorandum of Agreement with Reclamation dated March 12, 1969. At Hungry Horse Reservoir, there are seven developed recreation sites along the west side of the reservoir and eight developed sites along the east side, including two reservoir island sites. Total facilities presently include 174 single camp units, one group camp site with a 150 person capacity, 27 picnic units, 11 single boat ramps, three interpretive signs, and associated sanitary facilities. Table 2-18 lists recreation facilities at Hungry Horse Reservoir.

Table 2-18. Hungry Horse Reservoir Recreation Facilities

Site	Camping Units ^{1/}	Boat Ramp ^{2/}	Picnic Units ^{3/}
<u>West Side</u>			
1. Doris Creek	Dispersed	Yes	Dispersed
2. Lost Johnny C.G.	Yes	Yes	Dispersed
3. Lost Johnny Point	Yes	Yes	Dispersed
4. Wounded Bear Ob. Pt.	Dispersed	No	Dispersed
5. Lid Creek	Yes	Yes	Dispersed
6. Lakeview	Yes	No	Dispersed
7. Graves Creek	Yes	Yes	Dispersed
<u>East Side</u>			
1. Abbot Bay	Dispersed	Yes	Dispersed
2. Emery Bay	Yes	Yes	Dispersed
3. Riverside	Dispersed	Yes	Dispersed
4. Murray Bay	Yes	Yes	Yes
5. Canyon Creek	Dispersed	Yes	Dispersed
6. Devil's Corkscrew	Yes	Yes	Dispersed
7. Fire Island	Boat in	N/A	Dispersed
8. Elk Island	Boat in	N/A	Dispersed
^{1/} Vault toilet sanitary facilities generally provided at all sites.			
^{2/} All boat ramps single lane.			
^{3/} In addition to developed picnic sites, picnicking occurs at campgrounds and other sites on a dispersed basis.			

The primary recreation activities at Hungry Horse Reservoir are camping, fishing, boating, and sight-seeing. Use is increasing in non-reservoir dependent activities, such as huckleberry picking and hunting. Recreation visitation at Hungry Horse Reservoir has fluctuated significantly in the last five years. Table 2-19 presents annual visitor use from 1987 through 1991.

Flathead River. The USFS also manages lands above and below Hungry Horse Dam and Reservoir along the South, Middle and North Forks of the Flathead River. There are several developed recreation sites on the Middle Fork Flathead River, all of them are off of Highway 2, within 30 miles (48 km) of West Glacier. There are also several developed sites along the South Fork Flathead River at the southern end of Hungry Horse Reservoir. All of these are river access sites, including put in/take out points, sanitary facilities, and parking areas. Camping occurs on a dispersed basis only. There are no

developed sites along the South Fork below Hungry Horse Dam.

Results of a 1989 statewide survey (MDFWP, 1989) indicated that the economic value of the Flathead River fishery from the confluence of the South Fork to Flathead Lake was \$1.4 million annually. Fishing pressure has steadily increased, although there are no creel census numbers presently available.

Angler use and success is seasonal, depending on the river fishery. Lake Superior white fish provide a tremendous fishery from early November through the end of December. Bull trout are fished from April through early May, then again from late June through July, on a catch and release basis. Kokanee, which historically provided excellent sport fishing opportunities, has declined drastically in abundance in recent years, most notably since 1986. The most prized fishery presently is bull trout, west slope cutthroat, and kokanee.

Table 2-19. Hungry Horse Lake Visitation Summary, 1987 - 1993.

MONTH	VISITOR - DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	AVG
Jan	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Feb	0.5	0.5	0.5	0.4	0.4	0.2	0.4	0.4
Mar	1.4	1.4	1.4	1.3	1.1	0.5	1.1	1.2
Apr	3.2	3.2	3.2	3.0	2.6	1.3	2.6	2.7
May	3.7	3.7	3.7	3.5	3.0	1.4	3.0	3.2
Jun	14.9	14.7	14.7	14.0	12.2	5.7	12.0	12.6
Jul	27.6	27.3	27.3	26.5	22.4	10.6	22.1	23.4
Aug	29.4	29.0	29.1	27.7	23.9	11.3	23.6	24.9
Sep	8.2	8.1	7.9	7.5	7.5	3.1	6.4	6.9
Oct	2.8	2.7	2.8	2.6	2.3	1.1	2.2	2.4
Nov	1.4	1.4	1.4	1.3	1.1	0.5	1.1	1.2
Dec	.5	0.5	0.5	0.4	0.4	0.2	0.4	0.4
TOTAL	93.5	92.4	92.3	88.3	77.0	35.9	75.0	79.2
For 1993 and 1992, estimated visitation by month is based on historical use patterns.								

Other recreation use which occurs along the river consists primarily of floating, sightseeing and dispersed camping and picnicking. Although recreation use figures are not available along the Flathead River, the USFS indicates that use is steadily increasing.

2.7.3.6 Regional Recreation Problems and Needs

Recreation related problems at Hungry Horse Reservoir and along the Flathead River are primarily due to reservoir operations. The quality and quantity of recreation use at Hungry Horse Reservoir is dependent to a large extent on summer reservoir levels. Use of the recreation facilities is directly or indirectly affected by reservoir levels. In general, low reservoir levels can isolate camping and picnicking facilities, leave some boat ramps out of water, and greatly reduce the reservoir area aesthetics. This has a negative impact on recreation management, and visitor use and enjoyment.

As reservoir levels drop and land based facilities become isolated, visitors move with the shoreline. Since these areas are not equipped with waste or sanitary facilities, trash and sanitary waste is often left along the shoreline, creating unsanitary and unsightly conditions. In 1988, Hungry Horse Reservoir experienced one of the driest water years and lowest reservoir levels on record. This left many of the boat ramps inoperable throughout the recreation season. This also corresponded with one of the lowest seasons of use, with only 36,000 recreation days recorded for that year.

Without access to the water due to inoperable boat ramps, visitors go elsewhere for water based recreation use. All of the 11 available ramps are oper-

able at full pool (3560 feet), nine ramps are operable at 3552 feet, six ramps are operable at 3532 feet, and a single ramp is operable at 3500 feet. As reservoir levels decline so does use.

Aesthetic quality is important since one of the primary recreation activities at Hungry Horse Reservoir is sightseeing. Low or fluctuating reservoir levels that affect the resident fishery are also important; decline in angler success reduces overall use of the area.

Reservoir operations also affect recreation use on the Flathead River. Erratic releases from the dam, cold water temperatures, and poor angler opportunities reduce visitor enjoyment along the Flathead River. On occasion, erratic water releases have stranded anglers and created problems for river floaters. Cold water released from the dam is undesirable for water contact sports; use increases as the water warms to natural conditions. Generally, flows have not been compatible with downstream fishery maintenance needs. The river fishery, primarily the kokanee, has declined significantly, reducing angler opportunities.

A higher quality recreation experience could be achieved at Hungry Horse if reservoir levels were maintained between elevations 3552 feet and 3532 feet throughout the recreation season. This would ensure good boater access, convenient use of associated land-based facilities, high quality reservoir aesthetics, and would reduce recreation management problems. To the extent that high, stable reservoir levels would improve the resident fishery, it would also benefit recreation use. A change in downstream flows to support the river fishery, raise water temperatures, and moderate erratic flows would all improve conditions for downstream recreation use.

Figure 2-15. Keller Ferry Recreation Area at Lake Roosevelt (Coulee Dam National Recreation Area)

2.7.4 Grand Coulee (Lake Roosevelt) Subregion

2.7.4.1 General Overview

This subregion begins at Grand Coulee Dam and extends to the upstream limits of Lake Roosevelt, a distance of approximately 130 miles (209 km). Lake Roosevelt lies within semi-arid eastern Washington on the leeward side of the Cascades. Clouds have lost much of their moisture as they have passed over mountain ranges to reach the Columbia Basin, and arctic fronts typically pass to the east of the area, which results in winters that are mild by inland Northwest standards. Summer winds are moderate, allowing the lake surface to be reasonably calm during the recreation season. The large surface area and relatively warm water temperature of the reservoir provide water-oriented recreation opportunities to a growing number of visitors each year.

Access to Lake Roosevelt is by point access such as old road endings or by continuous access provided by roads that parallel the shoreline. Except for point access, the southern half of the reservoir is

inaccessible by roads due to steep banks and rock outcroppings. The northern half of the reservoir is paralleled by Highway 25 on the east bank and by paved county roads and Highways 20 and 395 on the west bank; however, intermittent steep banks and intervening private property preclude continuous public access to the lakeshore.

Vegetation within the Lake Roosevelt area ranges from grasslands and sagebrush in the southern section to forest communities in the north. Grasslands dominate the reservoir shorelines from the dam up to the Spokane River confluence. From this point, the grasslands begin to yield to forest species until the upper reservoir reaches are predominately forested. Due to the fluctuating nature of Lake Roosevelt, very few perennial marshes exist along the shoreline. More common are intermittent wetland areas which seasonally flood and provide temporary wildlife habitat.

Most of the reservoir shoreline is composed of clay, silt and sand. The remainder of the shoreline is glacial till, basalt, granite, sedimentary and metamorphic rocks. Wave action has exposed numerous

sandy beaches that are particularly suited to recreation use.

Wildlife is plentiful. Animals most frequently sighted are coyotes, porcupines, marmots, and squirrels. Black bear are present but seldom seen. Located on a secondary flyway, the lake attracts a variety of waterfowl. Bald eagles and ospreys are frequently sighted in the area.

Cultural sites within the area include Fort Spokane, established in 1880 at the confluence of the Columbia and Spokane Rivers. St. Paul's Mission, a restored log church originally constructed by Jesuits in

1847, is located near the town of Kettle Falls. The inundated site of a Hudson Bay Company trading post is located in the same vicinity. The Kettle Falls archaeological district, dating back 9,000 years, is one of the most significant sites in the Northwest.

The primary attraction for visitors to the Lake Roosevelt area is water based recreation. Annual visitation for the last several years has exceeded 1.5 million visitor days. The most popular activities are camping, sightseeing, fishing, hiking, boating, and picnicking. Table 2-20 summarizes project visitation from 1987 to 1991.

Table 2-20. Lake Roosevelt Visitation Summary, 1987 – 1993.

NATIONAL PARK SERVICE RECREATION SITES								
MONTH	VISITOR-DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	AVG
Jan	10.7	11.8	15.4	26.7	15.3	19.4	3.2	14.6
Feb	14.5	18	37.2	24.9	20.4	27.3	3.9	20.9
Mar	19	36.9	65.7	74.7	37.8	47.6	22.9	43.5
Apr	43.3	54.5	108.6	104.6	49.2	81.5	34.8	68.1
May	95.1	91.5	122	156.8	133.6	110.5	88.2	114.0
Jun	212.6	183	174	157.7	155.1	164.8	149.2	170.9
Jul	275.3	263.8	281.8	306.9	232.5	338	253.9	278.9
Aug	315.7	287.5	434.8	318.7	268.4	331.3	261.8	316.9
Sep	85.2	78.6	341.8	185.8	104.2	157.6	140.1	156.2
Oct	71.3	58.7	132.5	103.4	50.1	67.5	61.3	77.8
Nov	46.5	37.8	49.5	64.2	30.9	21.3	34.1	40.6
Dec	27.5	17.9	26.2	35.6	18.2	17.5	13.8	22.4
Subtotal	1216.7	1140.0	1789.5	1560.0	1115.7	1384.3	1067.2	1324.8
OTHER RECREATION SITES								
Colville Reservation	35	32.8	40	n/a	n/a	n/a	n/a	
Spokane Reservation	8.8	8.2	10	n/a	n/a	n/a	n/a	
Grand Coulee Visitor Center (USBR)	506.2	499.1	508	485.7	464.1	322.6	442.6	
Subtotal	550	540.1	558	485.7	464.1	322.6	442.6	
TOTAL	1766.7	1680.1	2347.5	2045.7	1579.8	1706.9	1509.8	

2.7.4.2 Aesthetics

The landscape adjacent to Lake Roosevelt is relatively natural and undeveloped except for occasional farms and small communities. One of the unique landscape features of Lake Roosevelt is the marked difference in topography and vegetation types between the northern and southern portions of the 130 mile long reservoir.

In the northern section of the reservoir, the river valley is shallow and visitors to the reservoir are afforded views of both the valley and the mountains beyond. Stands of coniferous forests cover the hills and line the shores. Most of the northern half of the reservoir is easily accessible by roads. Washington Route 25 parallels 70 miles of the east shore from Fort Spokane to the headwaters. The west shore has good road access from Inchliem north to Barstow via paved county roads, State Highway 20, and U.S. Highway 395.

In the southern section of the reservoir (Fort Spokane to the dam) the forested areas thin out and the predominant vegetation turns to sagebrush, bitterbrush, and other arid species. In this portion of the reservoir, the canyon walls rise from the shoreline and views from the reservoir are frequently restricted to basalt cliffs and narrow terraces within the canyon rim. Road access is limited with no parallel roads and only infrequent point access to the last 50 miles of reservoir above Grand Coulee Dam. Views of the lake are possible from a few small communities, including Grand Coulee and Seven Bays in the south section of the reservoir and Kettle Falls and Marcus to the north.

Recreationists visiting the lake are key viewers of the lake. Because much of the recreation at Lake Roosevelt occurs on the lake in boats, a large number of recreationists view the lake and adjacent landscape from the waters of the lake. Many recreationists view the lake from the shoreline at the numerous overnight and day-use recreation facilities located along the reservoir.

2.7.4.3 Recreation Sites and Facilities

Reclamation provides visitor facilities and guided tours at the dam. Facilities include a large visitor

center, picnic and turf areas below the dam, and various overlooks and parking areas. A popular laser light show is played nightly across the face of the dam during the tourist season. The visitor center is open year-round.

The majority of recreation facilities on Lake Roosevelt are provided by the NPS, the Colville Confederated Tribes and the Spokane Tribe. The two tribes and the NPS provide a wide array of visitor facilities along the 600 miles (965 km) of shoreline on Lake Roosevelt. These sites range from highly developed and intensively used campgrounds and day-use areas to primitive sites that can only be accessed by boat.

There are also commercial facilities available at several privately run marinas that are under the jurisdiction of the managing agencies. Rental houseboats are very popular at the marinas. Plans for extensive additional marina facilities are under way by all three managing agencies. The recreation sites are listed and described in Table 2-21.

All of the recreation facilities and recreation activities on Lake Roosevelt are directly impacted by reservoir operations. Excessive drawdown during the recreation season has a particularly negative impact on recreation use.

2.7.4.4 Managing Authorities

Coulee Dam National Recreation Area was established in 1946 by the Secretary of the Interior's (Interior) approval of the Tri-Party Agreement which included the NPS, Reclamation, and Bureau of Indian Affairs. NPS operations under such agreements are authorized by Public Law 79-633. Reclamation operates Grand Coulee Dam in accordance with established criteria developed to meet authorized purposes. Reclamation administers lands in the immediate vicinity of the dam and at other sites that are necessary for project operations. Even though Reclamation directly administers a small percentage of the total project lands, the legislated project operations take priority over the other land uses administered by the tribes and NPS.

Figure 2-16. Map of Lake Roosevelt/Coulee Dam National Recreation Area

Table 2-21. Lake Roosevelt Recreation Facilities

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
Bradbury Beach	1	1		40		2		5		
China Bend	1	1		20						
Cloverleaf				40		4		7		
Crystal Cove								3		
Detillion				40				12		
Enterprise								13		
Evans	1	2		140		15		34		
FortSpokane	1	4	15	420		64		67		2
French Rock	1	1		20						
Gifford	1	4	10	400				47		
Goldsmith								3		
Haag Cove				20		6		16		
Halverson Canyon								1		
Hanson Harbor	1	1		20						
Hawk Creek	1	1		60				28		
Hunters	1	4		200		6		39		3
Jones Bay	1	1		40				6		
Kamloops				20				17		
Keller Ferry Marina	1	4	51			20	1	55		2
Kettle Falls Marina	1	4	70			46	1	89		1
Kettle River			2	20				12		
Lincoln Mill	1	2		60		3				
Marcus Island	1	1		20		3		27		
NapoleanBridge	1	1		20						
North Daisy	1	1		20						
North George	1	1		40				12		
Penix Canyon								3		
Plum Point								4		
Ponderosa								8		
Porcupine Bay	1	4		240		20		32		
Seven Bays Marina	1	4	180							
Snag Cove	1	1		20				9		
Spring Canyon Marina	1	4	15			61	1	87		1
Sterling Point								5		
Summer Island				40				6		
TOTAL	23	49	353	1960	0	250	3	647	0	9

The reservoir and related lands were administered under the 1946 Tri-Party Agreement until 1974 when Interior directed that the agreement be expanded to include the Colville Confederated Tribes and the Spokane Tribe. The Secretary's directive was the result of an Interior Solicitor's opinion that the two tribes have exclusive rights to hunting, boating, and fishing for those areas of the reservoir that are within the two reservations. A new management agreement was signed by Interior and the new managing entities on April 5, 1990. The agreement confirms and establishes management authority for the two tribes for project lands within their respective reservations. The tribes administer approximately 45 percent of the project lands and waters. The remaining lands and waters continue as the Coulee Dam National Recreation Area, a unit of the National Park System.

2.7.4.5 Major Activities and Use Areas

Camping. The most popular form of outdoor recreation on the reservoir is camping. The use of recreational vehicles is the most popular form of camping, with tent camping and houseboats also very popular for overnight stays on the reservoir. The NPS provides most of the camping opportunities with over 650 developed campsites at 29 campground locations. The tribes have five developed campgrounds that contain over 60 campsites. The tribes also maintain several primitive sites that are approved for camping. In addition to the approved sites, a good deal of random camping occurs within undeveloped areas along the lakeshore.

Sightseeing. Scenic overlooks, an attractive visitor center, and a spectacular laser light show attracts well over one-half million visitors to the immediate vicinity of the Grand Coulee Dam. Sightseeing on Lake Roosevelt takes place by boat or along roadways on the northern end of the reservoir. Sightseeing by vehicle is restricted on the southern end of the reservoir due to limited access.

Fishing. Primary sportfish species in Lake Roosevelt include rainbow trout, walleye, sturgeon, kokanee, smallmouth bass and perch. The trout fishery at Lake Roosevelt steadily improved in recent years

due to the effort of volunteers who raise fish in net pens for release into the reservoir. In addition, BPA has recently constructed two new fish hatcheries for the reservoir as part of its fish and wildlife mitigation program. The hatchery program will produce primarily kokanee. As a result of these efforts, the fishing use at Lake Roosevelt has increased substantially and is expected to continue to increase over the next several years, if reservoir operations allow. The operation of the reservoir, particularly drawdown, can be detrimental to the resident fish population. (See SOR Appendix K, Resident Fish).

Boating. Powerboating is a major recreation activity on Lake Roosevelt. Sailboating is somewhat limited due to the lack of consistent winds during the summer months. The continuing popularity of boating can be confirmed through the statistics for boat launches within the National Recreation Area. The boat launches recorded in 1991 indicates that boating use has more than doubled since 1988. With the recent addition of several new launch ramps and with more marina facilities in the planning stage, this increase is likely to continue.

Houseboating. There has been a steady rise in demand for luxury houseboat rentals since the first 10 boats were introduced in 1987. The rental houseboat fleet grew to 50 boats by 1993, and the number will rise as new marinas currently in the planning stage come on-line in future years. The Concession Management Plan for Lake Roosevelt sets the maximum allowable number of rental houseboats at 200 for the entire reservoir. A specific number of boats are allocated to each marina site in order to spread the boats throughout the reservoir.

Swimming and Picnicking. Day use activities, primarily swimming and picnicking, account for a significant portion of visitor use. NPS maintains six swimming beaches with life guards at popular day-use sites. Picnicking is frequently a companion activity with swimming, as turf areas and picnic tables are provided near the swim beaches. Adults bring their children to the swim areas and then watch the children from the adjoining turf/picnic areas. Swimming and related activities are highly affected by reservoir levels. As the reservoir level is

reduced, the swimming areas become separated from the turf/picnic areas. With lake elevations of 10 feet or more below high water, the swim areas become unusable due to unsafe topography and bottom composition.

2.7.4.6 Visitor Use

Visitation at Coulee Dam National Recreation Area for 1986 – 1993 is shown on Table 2–20. The visitation at the portion of the reservoir within the two Indian reservations is estimated at 50,000 visitors per year. Visitation statistics for the reservoir are understated since accurate counts of dispersed, non-site specific recreation use are not included. Visitation at Reclamation facilities at Grand Coulee Dam is approximately 500,000 per year. Over 75 percent of the annual visitation occurs from June through October, with the highest monthly visitation occurring in August.

2.7.4.7 Facility Needs

As visitation continues to increase, new facilities will be needed at Lake Roosevelt. A straight line projection of existing trends (1985 to present) would indicate a future increase of approximately 200,000 visitors per year. Even if the rise in visitation does not continue as sharply as it has over the last several years, there is still reason to expect a continuing rise in visitation.

The increase in fishing success and increased advertising by concessionaires have contributed to the sharp rise in visitation in recent years. With the completion of two new fish hatcheries, the fishing is likely to improve, thereby continuing the need to increase boat launching and parking facilities. In addition, plans are already being prepared for significant increases in concessionaire facilities. Both of the Indian Tribes are proposing major new marinas for their reservation shorelines, and the NPS has plans to add a new marina near the dam.

Regardless of any projected increases in visitation, new facilities are needed to accommodate existing

visitation. All major launching facilities on Lake Roosevelt receive overflow use on summer weekends. The existing demand for campsites and day use facilities exceed available facilities on most summer weekends. All facilities are overused on warm weather holidays.

Three new launch ramps and parking areas were constructed in the spring of 1993. Three additional ramps were completed in 1994. Existing campgrounds and parking lots are being evaluated for expansion potential.

2.7.5 Albeni Falls (Lake Pend Oreille)

2.7.5.1 General Overview

Albeni Falls Dam lies within one of the most scenic areas of northern Idaho and the Northwest. Its long, narrow reservoir extends 25 miles (40 km) from the dam to connect with the state's largest natural lake, Lake Pend Oreille, which itself is 43 miles (69 km) long and over 1,000 feet deep. Totally encircled by mountains, this lake has a renowned fishery. Over fourteen species of game fish inhabit the lake, including kamloops, kokanee, whitefish, perch, crappie, bluegill, largemouth bass, rainbow, brown, and brook trout. A 32-pound bull trout, the state's largest, was taken from this lake.

Nearby Lake Coeur d'Alene, Priest Lake, Upper Priest Lake, the Kaniksu National Forest, and the Coeur d'Alene National Forest are other attractions in the area. Winter activities are close by at Schweitzer Basin, a major destination ski resort.

Albeni Falls/Lake Pend Oreille is easily accessible, located only 50 miles from Spokane, Washington, and 48 miles from Coeur d'Alene, Idaho. Washington State Highway 2 provides access from the dam to north Spokane and Interstate 90 and Washington State Highway 95 provide access from Coeur d'Alene. Amtrak service is available at Sandpoint, Idaho, as is jet service at the Spokane Airport.

Figure 2-17. Priest River Recreation Area at Lake Pend Oreille

2.7.5.2 Aesthetics

Although Lake Pend Oreille is surrounded by mountains, the dominant visual feature is the large reservoir itself. Views of opposite shores 2 to 18 miles (3 to 29 km) away are possible along the main body of the reservoir. From Sandpoint to Albeni Falls Dam, the reservoir is much narrower (approximately .25 to .5 mile wide) than it is in the main body of the reservoir and is riverine in character. Viewing is limited by nearby forested hills to the river valley itself.

Most of Lake Pend Oreille is located adjacent to the Coeur d'Alene and Kaniksu National Forests and is undeveloped. Development has been concentrated on private land near the communities of SandPoint, Priest River, and small communities on the lake such as Hope and Bayview. Developed uses include

residential and recreational single family homes, condominiums, marinas, and campgrounds. Many residences and facilities near the reservoir have been located to take advantage of views of the water.

The primary viewers of the reservoir include residents of local communities, recreationists and tourists, travelers on U.S. Highways 2 and 95 and Idaho State Highway 200, and Amtrak riders who can view the north and east sides of the reservoir. The reservoir can be seen from several local roads, such as the East River Road. Residential and vacation homes located on or near the reservoir have often been sited to take advantage of water views. The lake is very popular for recreation, which provides campers, boaters, and other users with opportunities to enjoy views of the reservoir.

2.7.5.3 Existing Parks And Recreation Facilities

Pend Oreille Lake is a major regional recreational resource for the northern Idaho area. As shown in Table 2-22, there are 27 developed recreation sites scattered around the shoreline. The Corps operates four campgrounds and two day use parks on the lower reservoir portion of the project. USFS operates three campgrounds and day-use sites on the main lake. Idaho State Parks operates the largest public campground and day-use park at Bayview at the southern tip of the lake. There are also several Corps' owned dispersed sites managed by Idaho Department of Fish and Game. There are private marinas and private resorts which offer a full range of facilities, including RV campgrounds, cabins, condominiums, and hotel rooms. The Corps manages a visitors center and viewpoint observation areas at the main dam site.

2.7.5.4 Principal Managing Agencies/Entities

Corps of Engineers. The Corps is the Federal agency primarily responsible for providing facilities on the 25 mile (40 km) stretch of the the reservoir impounded by the dam. This includes four campgrounds at Albeni Cove, Priest River, Riley Creek, and Springy Point; two day-use areas at the visitors center and Trestle Creek; and 13 wildlife management areas. Two wildlife areas that offer passive recreation opportunities, including wildlife and scenic observation, are Mallard Bay and Oden Bay.

The U.S. Forest Service (USFS). USFS is the major Federal land management agency around Lake Pend Oreille. Kaniksu National Forest and the Coeur d'Alene National Forest encompass the lake on the south and east sides, respectively. The USFS administers three recreation sites adjacent to the lake, including campgrounds, picnic areas, swimming beaches, boat launches, trails and trailheads, and viewpoints.

Idaho Department of Fish and Game. The department manages two areas at Morton Slough and at Johnson Creek, which include camping, picnicking, and boat launch areas.

Idaho Department of Parks and Recreation. This state department operates and manages the largest public park on the lake, Farragut State Park near Bayview. This park has over 200 campsites and includes day-use areas, a marina, and unique museum of old Navy photographs.

City of Sandpoint. The Sandpoint Parks Department operates and maintains a large intensively developed city park on the north shore of the lake, within the city limits. This facility includes a beach, playing fields, and boat launch ramps, and it is adjacent to a large private marina.

2.7.5.5 Major Activities and Use Areas

Recreation and tourism are significant economic activities at Lake Pend Oreille and are likely to become more important with increased population growth. The primary market area is within a 100-mile radius or a two-hour drive of the lake and includes parts of Washington, Idaho, Montana, British Columbia and southern Alberta. User data show swimming, boating, fishing, camping, sightseeing, picnicking, hiking, horseback riding, hunting, and snowmobiling to be popular. Swimming, boating, outdoor games (including golf), cycling, and skiing are experiencing rapid growth.

Native sport fishes in Lake Pend Oreille are west-slope cutthroat trout, bull trout and mountain whitefish. Other sport fishes have been stocked or have been introduced into the lake over the years. These species include kokanee, rainbow trout, Gerrard (Kamloops) trout, lake whitefish, brook trout, brown trout, lake trout, yellow perch, black crappie, largemouth bass, brown bullhead, pumpkinseed and northern pike.

The Gerrard rainbow trout of Lake Pend Oreille attracts a large share of the angling effort. Native to Kootenay Lake, British Columbia, this fish lives longer than other trout species and grows to an unusually large size on a diet of kokanee. A world record rainbow trout, weighing 37 pounds was caught in Lake Pend Oreille in 1947.

Figure 2-18. Map of Lake Pend Oreille

Table 2-22. Existing Recreation Sites and Facilities, Lake Pend Oreille Subregion

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
Dam Site Vista						10				
Albeni Cove	1	1				8		13		
Bayview Marina	1	2	200	—						
Beyond Hope Resort	1	2	244	—						
Bottle Bay Resort & Marina	1	2	100	—			4			
Dock N' Shop	1	2	16	—						
Edgewater Resort										
Evans Landing	1	1								
Farragut State Park	1	2						137		
Fox Farm Resort	1	2								
Garfield Bay	1	2	30	—				27		
Green Bay Marina	1	1	70	—						
Idaho Country Resort	1	2	100	—						
Johnson Creek	1	1				5		5		
Maiden Rock										
Morton Slough	1	1								
Pend Oreille Landing	1	1								
Priest River	1	1				15		20		
Rainbow Resort	1	2								
Red Fir Resort	1	2	15	—						
Riley Creek	1	1				47	2	69		
Samowen	1	1								
Sandpoint City Beach	1	2	26	—						
Sandpoint Marina			130	—						
Springy Point	1	1				10		40		
Trestle Creek	1	1				6				
Windbag Marina	1	2	75	—						
Whiskey Rock Bay	1	1						9		
TOTAL	21	38	2088	—	0	101	6	320	0	0

From 1951 to 1965, the Lake Pend Oreille Kokanee fishery was the most popular in Idaho. Kokanee harvest began to decline in the 1960's and reached a low in 1986. The current kokanee harvest is only 10 to 20 percent of historic levels. Idaho Department of Fish and Game believes that several factors have caused the fishery decline in Lake Pend Oreille, including fluctuations in lake levels due to operation of Albeni Falls Dam. (See Technical Appendix K, Resident Fish).

Numerous private resorts and marinas are located around the lake, including sites near Sandpoint, Trestle Creek, Hope, Lakeview, Bayview (Scenic Bay), Ellisport Bay, Garfield Bay, Bottle Bay, Marin Bay, Camp Bay, and Glengary Bay. These sites

provide camping, swimming, picnicking, boat launches and moorage, food, gas, and lodging.

The local business organizations are working hard to promote the region as a year-round destination resort. The development of Schweitzer Basin just north of the lake over the last several years has included significant capital investment in facilities which have increased winter visitation greatly.

2.7.5.6 Visitor Use

Table 2-23 summarizes visitation to Lake Pend Oreille from 1987 to 1993. Recreation at Lake Pend Oreille is primarily summer oriented. Approximately 75 percent of the recreation use of the lake occurs during May, June, July, August, and September.

Table 2-23. Lake Pend Oreille Visitation Summary, 1987-1993.

CORPS OF ENGINEERS RECREATION SITES								
MONTH	VISITOR-DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	AVG
Jan	0.7	2.6	2.0	1.3	0.8	0.8	0.7	1.3
Feb	0.1	2.2	1.5	0.4	0.9	1.2	1.4	1.1
Mar	2.6	3.9	3.6	2.4	4.1	3.2	3.4	3.3
Apr	10.2	5.6	9.9	14.1	11.0	12.0	11.3	10.6
May	38.4	38.8	25.7	16.2	29.0	28.2	32.8	29.9
Jun	50.9	73.5	48.3	43.8	62.4	57.7	79.8	59.5
Jul	72.6	106.2	197.8	107.0	110.9	106.0	95.0	113.7
Aug	87.6	99.4	104.7	91.6	88.6	95.3	84.6	93.1
Sep	43.4	32.9	43.6	40.9	43.2	38.5	36.5	39.9
Oct	8.6	11.4	12.5	13.3	9.3	10.4	7.9	10.5
Nov	2.6	4.1	4.3	4.2	4.8	4.8	4.9	4.2
Subtotal	204.7	202.0	188.9	193.0	145.8	172.7	121.0	175.4
OTHER RECREATION SITES								
Sandpoint City Beach	n/a	n/a	n/a	573.3	n/a	n/a	n/a	
Farragut State Park	n/a	n/a	n/a	250.0	n/a	n/a	n/a	
US Forest Service	n/a	n/a	n/a	55.6	n/a	n/a	n/a	
Subtotal	n/a	n/a	n/a	878.9	n/a	n/a	n/a	
TOTAL	320.0	381.4	456.9	1217.2	368.4	361.1	360.5

Figure 2-19. Waterskiing on Rufus Woods Lake

2.7.6 Middle Columbia River (Chief Joseph and PUD Projects)

2.7.6.1 General Overview

The middle Columbia River subregion stretches from the upper end of the McNary Project, Lake Wallula in the south to the upper end of Chief Joseph Project (Rufus Woods Lake) just below Grand Coulee Dam. This reach of the river is characterized by a series of six run-of-river projects, including five Public Utility District (PUD) reservoirs (Priest Rapids, Wanapum, Rocky Reach, Rock Island, and Wells), and one Corps project (Chief Joseph) (Figure 2-20). Also included in this subregion is the stretch of the Columbia River known as the Hanford Reach. Located downstream from Priest Rapids Dam, it is the last free-flowing stretch of the Columbia River in the United States above Bonneville Dam.

This subregion is located in a relatively remote portion of central Washington and, consequently,

does not cater to an immediate large metropolitan population as do the projects below the Snake River confluence. The scenic and recreational amenities of the mid-Columbia River are measurably different than those of the Lower Columbia and can be further divided into the upper and lower basins, and the Hanford Reach. The projects are also significantly smaller in size than the lower Columbia projects and are more diverse in nature.

Upper Basin. The upper part of this subregion encompasses the Chief Joseph, Wells, Rocky Reach, and Rock Islands reservoirs. The city of Wenatchee is the largest city within this area and is the largest population base for visitors to the region. Consequently, the two projects closest to the city, Rock Island and Rocky Reach, feature a highly developed infrastructure of parks and visitor-use facilities (Figure 2-21). Facilities are less developed at Wells Dam and sparsely developed at Chief Joseph project.

Figure 2-20. Map of Chief Joseph Project

- 1 MANSON BAY PARK**
Location: Downtown Manson
Lake overview, swimming, picnic area, restrooms, 3 boat docks, winter only boat launch. 6 acres.
Managing Agency: Manson Park and Recreation District
P.O. Box 248 Manson, WA 98831
(509) 687-9635
- 2 OLD MILL PARK**
Location: 2 miles east of Manson, Highway 150
One boat launch, short-term moorage, rest area, restrooms, marine dump station, boat trailer parking. 20 acres.
Managing Agency: Manson Park and Recreation District
P.O. Box 248 Manson, WA 98831
(509) 687-9635
- 3 CHELAN RIVERWALK PARK**
Location: Chelan River, City of Chelan
(7) mile scenic river loop trail, boat launch, short-term moorage, boat trailer parking, grass playground, restrooms, picnic areas, picnic shelter, 12 acres.
Managing Agency: Chelan County Public Utility District
P.O. Box 1231, Wenatchee, WA 98807
(509) 663-8121
- 4 CHELAN FALLS PARK**
Location: Community of Chelan Falls
One boat launch, short-term boat moorage, parking, extensive day use facilities, picnic shelters, restrooms, showers, shoreline trail, a tennis court, playground equipment, swimming area. 53 acres.
Managing Agency: Chelan County Public Utility District
P.O. Box 1231, Wenatchee, WA 98807
(509) 663-8121
Picnic shelter reservations accepted. Call the number above for more information.
Note: Opening date Fall, 1992.
- 5 BEEBE BRIDGE PARK**
Location: 21 miles north of Orondo, Highway 97
Camping, 27 tent/R.V. sites with electricity and water, restrooms, showers, parking, day use facilities, picnic shelters, swimming area, 2-lane boat launch, short-term boat moorage, tennis courts, playground equipment, shoreline trail, R.V. dump station. 56 acres.
Managing Agency: Chelan County Public Utility District
P.O. Box 1231, Wenatchee, WA 98807
(509) 663-8121
Picnic shelter reservations accepted. Call the number above for more information.
Note: Opening date Fall, 1992
- 6 DAROGA STATE PARK**
Location: 8 miles upriver from Orondo, Highway 97
Camping, 25 tent/R.V. sites with electricity and water, 17 walk-in or boat-in sites, baseball/soccer field, 2-lane boat launch, boat trailer parking, combination tennis & basketball court, short-term moorage, swimming, restrooms, showers, picnic shelters, volleyball, tennis, 2.5 mile shoreline trail, R.V. dump station. 140 acres.
Managing Agency: Washington State Parks & Recreation Commission
HCR Box 38A Orondo, WA 98843
(509) 684-8702
Reserve picnic shelters and group camp. Camping available on a "first come-first served" basis.
(509) 664-6380 (General Information)
- 7 ORONDO RIVER PARK**
Location: 3 miles upriver from Orondo, Highway 97
10 RV sites (5 with electricity and water), showers, swimming, 1-lane boat launch, boat trailer parking, short-term moorage, picnic shelters, concessions, JetSki rentals & marine gas available. 5 acres.
Managing Agency: Port of Douglas County
P. O. Box 122 Orondo, WA 98843
(509) 684-4700 or (509) 784-1796
Reservations for camping and picnic shelters accepted. Write above address.
- 8 ENTIAI PARK**
Location: City of Entiat, Highway 97A
Camping (103 tent sites and 31 RV sites with complete hookups), boat launch, boat trailer parking, short-term moorage, swimming, restrooms, showers, RV dump station, playground equipment, picnic shelter, picnic areas. 40 acres.
Managing Agency: City of Entiat, Park & Recreation Department
P. O. Box 228 Entiat, WA 98822
(509) 784-1500
Camping reservations for RV sites accepted. Write above address
- 9 TURTLE ROCK ISLAND**
Location: 1/2 mile upriver from Lincoln Rock State Park
Limited day use facilities for boaters, boat dock for short-term moorage, beach area, picnic tables, sanitary facilities. 1/2 acre.
Note: Presently under design. Opening date 1994.
- 10 ROCKY REACH DAM**
Location: 7 miles north of Wenatchee, Highway 97A
Extensive "award winning" landscaping, picnic areas, picnic shelter, playground equipment, horseshoes, Visitor Center, fish viewing room, historical galleries, restrooms. 38 acres.
Managing Agency: Chelan County Public Utility District
P. O. Box 1231 Wenatchee, WA 98807
(509) 663-8121
Picnic shelter reservations accepted.
Call the number listed above.
- 11 LINCOLN ROCK STATE PARK**
Location: 7 miles north of East Wenatchee, Highway 2
Camping (94 tent/RV sites: 35 with electricity and water, 32 with electricity, water and sewer, 27 standard), baseball/soccer field, 3-lane boat launch, boat trailer parking, short-term moorage, swimming, restrooms, showers, picnic shelters, playground equipment, volleyball, tennis, horseshoes, amphitheatre, RV dump station. 60 acres.
Managing Agency: Washington State Parks & Recreation Commission
Route 3, Box 3137 East Wenatchee, WA 98802
(509) 884-8702
Camping reservations accepted in person or write above address.
- 12 WENATCHEE CONFLUENCE STATE PARK**
Location: North Wenatchee on both sides of the Wenatchee River where it joins the Columbia River.
Camping (59 tent/RV sites: 51 with electricity, water and sewer, 8 standard), baseball/soccer field, 2-lane boat launch, boat trailer parking, swimming, restrooms, showers, picnic shelter, volleyball, tennis, playground equipment, Wenatchee River pedestrian bridge, 4.5 miles of trail, wildlife areas, interpretive graphics, RV dump station. 200 acres.
Managing Agency: Washington State Parks & Recreation Commission
Camping available on a "first come-first served" basis (no reservations accepted).
For information on availability, call (509) 664-6373.
- 13 WALLA WALLA POINT PARK**
Location: City of Wenatchee, (adjoins Wenatchee Riverfront Park), entrance on Walla Walla Street.
"Fourplex" soccer/softball complex (each with field lights), swimming, 1.1 miles of trail, tennis, volleyball, horseshoes, restrooms, picnic areas. 10 acres.
Managing Agency: City of Wenatchee, Parks & Recreation Department
P. O. Box 519, Wenatchee, WA 98807
(509) 664-5980
- 14 WENATCHEE RIVERFRONT PARK**
Location: City of Wenatchee (entrances, Worthen and Fifth Streets)
1.2 miles of shoreline trail, "special event" mini-railroad, ice rink, 2-lane boat launch, short-term moorage, boat trailer parking, restrooms. 31 acres.
Managing Agency: City of Wenatchee, Parks & Recreation Department
P. O. Box 519 Wenatchee, WA 98807
(509) 664-5980
- 15 ROCK ISLAND HYDRO PARK**
Location: 2 miles south of East Wenatchee, Highway 28
Baseball/soccer fields (1 with lights), picnic areas, picnic shelter, swimming, boat launch, boat trailer parking, tennis, volleyball, 1.1 miles of trail, restrooms. 70 acres.
Managing Agency: Chelan County Public Utility District
P. O. Box 1231, Wenatchee, WA 98807
(509) 663-8121
Picnic reservations accepted.
Call the number listed above.

Figure 2-21. Map of Middle Columbia PUD Projects

Transportation in this portion of the subregion is limited, with U.S. Highway 2 providing the main link to the heavily populated west slope of the Cascade Mountains. U.S. State Route 97 parallels the river from Wenatchee north almost to Bridgeport through the middle of the prime apple growing region of the state, providing direct access to many of the river's amenities. Residents from metropolitan Seattle and Tri-Cities, and residents of Wenatchee, Chelan and other local communities create a significant demand for water-related recreation in this area.

The most popular form of recreation in the upper part of the subregion is scenic driving. The highways provide access to vistas of natural features, such as the east Cascade Mountains, cliffs paralleling the river canyon, tributary rivers and streams, and the famed Washington fruit orchards. This activity drops off significantly as the visitors move toward Chief Joseph Dam.

Many visitors are attracted to the impressive engineered features of the area. Most of the dams have visitor facilities and viewpoints, and Chief Joseph Dam is the second largest power producing dam in the United States. There are also numerous fish hatcheries and fish ladders located at the PUD projects, which are also popular visitor attractions.

The subregion is popular for its water-related recreation opportunities. The upper subregion and adjacent streams and lakes have long been popular for fishing, swimming, and boating. The growth in population of inland communities such as Wenatchee and Chelan has increased visitation significantly. The spectacular growth of the coastal cities of Seattle, Tacoma, and Everett has also contributed to higher usage as more and more people seek to escape the urban environment.

Lower Basin. Land uses within and adjacent to the lower basin are notably different than the upper basin since the river moves east away from the mountains, and the climate is drier. Facilities range from the hydroelectric dams, small suburban residential areas, resorts, wildlife areas, an Indian village, an Army base, agricultural acreage, and a variety of recreational developments. The Wanapum Indian

village at Priest Rapids Dam and the Army's Yakima Firing Center occupies much of the west shore of the river between Priest Rapids Dam and Sentinel Gap. Interstate 90, the link between Seattle and Spokane, bisects the area on the north near the remote project of Wanapum. It provides the best access to the lower basin. Various other Washington state highways provide intermediate access to other sections of the subregion. Lack of good highways will constrain future development of facilities to meet public demand, particularly along the lower stretches of the river from Quincy down to Richland, where access is very limited.

Thousands of visitors from various parts of the country visit the lower basin and use its resources for recreation at such sites as Gingko/Wanapum State Park. Boating on the river is accommodated by nine boat launches and the marina at Crescent Bar. Hunting and fishing occur by boat and are accessed by roads that serve the shoreline at various points, primarily along the east shore. Camping is also a major activity and occurs both at developed facilities and in unregulated areas.

Hanford Reach. The Hanford Reach, located between Priest Rapids Dam on the north and the upper end of Lake Wallula (McNary pool) on the south, is unique in being the last undammed reach of the Columbia River in the United States above Bonneville Dam. The Hanford Reach and adjacent wildlife refuge/recreation areas provide year-round recreational opportunities. Sport fishing, flatwater boating, and waterfowl hunting are the primary recreation activities. Other activities include waterskiing, upland hunting, and nature viewing. The greatest recreation use occurs during September and October in conjunction with peak waterfowl hunting and salmon (e.g. fall chinook) fishing seasons. Hunting begins during October and extends through January.

The Hanford Nuclear Reservation, operated by the U.S. Department of Energy (DOE), encompasses almost the entire south and west shorelines of the Hanford Reach. Public use and access is restricted in the Hanford Reservation and in the Saddle Mountain National Wildlife Refuge, located north of the river.

The Wahluke Wildlife Recreation Area, operated by the Washington Department of Wildlife (WDW), is the primary public use recreation area along the Hanford Reach. WDW estimates that 91 percent of visits to the Wahluke Recreation Area are for sports fishing and hunting.

Salmon, steelhead, sturgeon, and smallmouth bass are the primary sport fish for anglers using the Hanford Reach. The abundance of fall chinook in the Hanford Reach makes it a very important area along the Columbia mainstem and tributaries for sport harvest of salmon. Summer-run steelhead are fished nearly as heavily as salmon. The majority of fishing occurs between Vernita Bridge and the Priest Rapids Dam, downstream of the Ringold Hatchery, and in the vicinity of White Bluffs.

Waterfowl hunting is the primary hunting activity in the Hanford Reach. Hunters do not confine themselves to the shoreline; they venture into sloughs and onto islands throughout the reach. Large populations of resting and migrating waterfowl use the reach between August and April.

In addition to accommodating hunting and fishing access, the Hanford Reach provides opportunities for flatwater boating. Jet and propeller-driven boats are able to access the entire Hanford Reach. Non-motorized boats stay primarily in the vicinity of Vernita Bridge, White Bluffs Ferry Landing, and Ringold Hatchery. Most recreational boating is a day-use activity. The Vernita Bridge boat launch, maintained by the Washington Department of Fisheries, is the most frequently used boat launch along the reach.

2.7.6.2 Aesthetics

The middle Columbia subregion is composed of two physically and visually distinct areas. The four upstream projects (Chief Joseph, Wells, Rocky Reach, and Rock Island) are located in a narrower section of the Columbia River valley than the downstream section. Views from these upper reservoirs are limited primarily to the steep canyon walls covered with grass and sagebrush. Because the projects are run-of-river projects located in a

relatively narrow canyon (from approximately 0.25 to 0.5 mile wide in most places), the project pool is not as wide or the views as expansive as in many parts of the two lower basin projects

The terrain adjacent to the two downstream projects, Wanapum and Priest Rapids, is flatter, and the river canyon is wider compared to the upstream projects. Due to the wider canyon, the reservoir's pools are generally wider than the pools of the upstream projects. Both pools extend to approximately 2 miles in width near the dams.

A variety of uses occur on lands adjacent to the middle Columbia projects. Most of the land adjacent to the reservoirs is undeveloped. Several state parks and state wildlife areas are located on or near the reservoirs. Some areas are developed for agriculture, including numerous orchards on the valley floor and lower terraces. The largest communities near the reservoirs are Wenatchee and East Wenatchee, which are separated by the pool of the Rock Island project. Other smaller communities along the reservoirs include Bridgeport, Brewster, Pateros, Entiat, Rock Island, Vantage, and Schwana. The adjacent communities have various combinations of residential, recreational, commercial, and industrial areas near the reservoirs.

Although long segments of the reservoirs are not accessible by road, there are some locations where highways and/or local roads allow views of the reservoirs. Major roads from which the river can be viewed include: U.S. Highway 97 which follows the river from Brewster to Wenatchee; U.S. Highway 2, which crosses the river at Wenatchee and follows it (in conjunction with U.S. 97) to Orondo; U.S. 97 Alternate along the west bank from Wenatchee to near Lake Chelan; Washington State 28 from Wenatchee to below Rock Island Dam; U.S. Interstate 90, which crosses the river at Vantage; and Washington State 243, which generally parallels the river from Interstate 90 to below Priest Rapids.

2.7.6.3 Recreation Sites and Facilities

To support the high levels of recreational use that occur in the subregion, a system of parks and recreation sites has been developed, particularly on the

Chelan County PUD projects (Rock Island and Rocky Reach) in and near Wenatchee. From river mile 125 below Priest Rapids Dam to river mile 620 at the upper end of Rufus Woods Lake, water-related recreation sites or areas have been identified that may be impacted by operation of the Columbia Riversystem dams (Table 2-24). These sites range from highly developed and intensively used urban parks with facilities to support a variety of recreational activities, to minimally improved fishing access sites.

Next to sightseeing, fishing is the second most popular recreational activity on the mid-Columbia reservoirs. Fishing takes place at developed recreation sites and at numerous dispersed locations throughout the study region. The Columbia River recreational fishery for anadromous species, sturgeon, and more recently, for walleye, is of particular importance. Surveys of resident fish communities in Lake Rufus Woods show fish abundance to be very low with only a few sportfish species present. Enough walleye are entrained through Grand Coulee Dam to support a walleye sport fishery in the lake. Resident game fish abundance is also relatively low in the other mid-Columbia reservoirs. (See Appendix K: Resident Fish).

The mouths of Columbia River tributary streams, including the Yakima, Wenatchee, Chelan, Methow, Okanogan, and Nez Perce Rivers, are particularly important recreational fishing sites. A number of the recreation facilities are located adjacent to these rivers and were provided largely to promote fishing access. The tailrace areas below the dams are also important recreational fishery sites. Facilities have been provided by the Corps and PUDs at each of these project areas to provide fishing access.

The majority of boating use occurring within the subregion, is associated with fishing. Waterskiing is the second most popular activity. Most boating use on all six lakes is highly localized; boaters launch from boat ramps in the vicinity of where they would like to fish or ski and stay within that particular area. Unlike the lower Columbia, there are no locks in any of these projects so boating is restricted to a single lake at a time.

Swimming is a relatively minor recreational activity at the mid-Columbia reservoirs. However, this activity has the potential to be more seriously impacted by project operations than other water-related activities due to the constraints of developed swimming beaches. These areas are very "flow sensitive" so that extreme flows are detrimental to use. Almost all swimming in the Columbia River occurs during the summer months of June, July, and August when water and air temperatures warm.

There are approximately 10 developed swimming beaches at parks along the mid-Columbia River within this subregion. An unknown percentage of swimming also occurs at dispersed or unimproved beaches.

2.7.6.4 Managing Authorities

Corps of Engineers. The Corps is the Federal agency primarily responsible for providing recreation facilities on Lake Rufus Woods. Visitor facilities include a visitor center, viewpoints, and fishing access sites.

Washington State Parks. The Corps cooperates with Washington State Park Department in the operation of Bridgeport State Park, the only major recreation site at the Chief Joseph project that includes a campground, day-use park, and golf course on the lake. Other local entities such as Douglas County, and the town of Bridgeport cooperate in the management of limited water-related recreation facilities, including boat ramps, swimming beaches, campgrounds, picnic areas, golf course, and interpretive sites.

Public Utility Districts. There are three Public Utility Districts (PUDs) within the subregion that operate and manage the hydroelectric facilities on the river. They are Chelan, Douglas, and Grant County PUDs. Chelan PUD operates the most extensive and urban facilities on the river, ranging from baseball and soccer fields to campgrounds on the Rock Island and Rocky Reach projects. Douglas PUD owns and manages Wells Dam, which also has several campgrounds and boating access areas.

Table 2-24. Existing Recreation Sites and Facilities, Middle Columbia River

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
**PROJECT: PRIEST RAPIDS DAM										
Priest Rapids HMA	1	1								
**PROJECT: ROCK ISLAND DAM										
Rock Island Hydro Park	1	1				20	1			
Walla Walla Point Park							1			
Wenatchee Confluence State Park	1	2				20	2	59	51	1
Wenatchee Riverfront Park	1	2				27				
SUBTOTAL	3	5	0	0	0	67	4	59	51	1
**PROJECT: ROCKY REACH DAM										
Beebe Bridge Park	1	3				36	1	27	27	
Chelan Falls Park		2				39	1			
Daroga State Park	1	2	2			75	2	42	25	2
Entiat Park	1	1				81	1	134	31	
Lincoln Rock State Park	1	3	4			60	3	94	67	
Orando River Park	1	1	5		1	12	1	10	5	
Rocky Reach						30	2			
SUBTOTAL	6	12	11		1	333	11	307	155	2
**PROJECT: WANAPUM DAM										
Ginkgo State Park	1	2	11		3	52		50	50	
**PROJECT: WELLS DAM										
Boat Launch	1	1								
Bridgeport	1	1				5	1	33	12	
Chief Joe State Park	1	2				20		20	20	1
Columbia River Boat Launch	1	1								
Dam Overlook										
Pateros						3	3			
SUBTOTAL	4	5				28	4	53	32	1
**PROJECT: CHIEF JOSEPH DAM										
Bridgeport State Park	1	1				5	1	33	12	
TOTAL	16	26	11	0	4	485	20	502	300	4

Grant County PUD owns and operates the lower two projects, Wanapum and Priest Rapids, which are the least developed in the subregion.

The Corps licenses the management of the lands on both shores of Lake Rufus Woods. The Bureau of Land Management has jurisdiction on the south bank and the Colville Indian Tribe on the north bank.

2.7.6.5 Special Recreation, Preservation and Natural Resource Areas

Much of the land along the mid-Columbia River adjacent to Priest Rapids and Wanapum Reservoirs, and Lake Rufus Woods are dedicated natural resource preservation and management areas. These lands are managed by Federal and state agencies for natural resource values. In addition to supporting some of the developed recreation sites described above, these lands are also available for dispersed and low-density recreation activities consistent with other resource management objectives.

Wildlife Refuges. This category includes both federally and state managed areas that have been set aside for the management, conservation, preservation, and enhancement of fish and wildlife resources. These areas are generally located along the Columbia River and are especially important in the habitat for migratory waterfowl. They generally have some public access facilities such as parking, trails and boat ramps that support dispersed public use consistent with fish and wildlife objectives. Most of the numerous state and Federal fish hatcheries along the river also allow public access and provide facilities to promote and interpret their missions.

Saddle Mountain National Wildlife Refuge, located along the north side of the Columbia River is administered by the FWS. The refuge is managed for public use; there are several developed public access points with parking, restrooms, trails, interpretive displays, small boat ramps, and waterfowl blinds. The refuge is very popular for waterfowl hunting.

Other activities include, fishing, boating, hiking, and wildlife viewing.

State Wildlife Areas and Habitat Management Areas managed by the WDW along the mid-Columbia River include Priest Rapids, Crab Creek, Quilomene, Quincy, and Colockum. Many of these lands are licensed from the PUDs, which also manage specially designated lands along all five reservoirs for fish and wildlife purposes.

Wild and Scenic Rivers. The purpose of Federal and Washington state wild and scenic rivers programs is to maintain rivers in a free flowing state; maintain, protect, and enhance existing scenic/recreation values; and to make these values accessible to the public. The Hanford Reach of the Columbia River is currently under study by the NPS. The study area extends from 1 mile below Priest Rapids Dam (river mile 396) downstream approximately 51 miles to Lake Wallula (McNary pool) to north of Richland, Washington (river mile 345). The study was authorized by Public Law 100-605 was conducted by NPS with the support of the USFWS and DOE. These three agencies comprised the study team.

A three-agency study team developed a draft EIS that called for the area to be designated a National Wildlife Refuge with Wild and Scenic River overlay. This proposal would combine a Wild and Scenic River designation of the river and its immediate corridor with National Wildlife Refuge designation of upland areas north and east of the river. The refuge would incorporate two parcels which are currently in an administrative refuge status under the administration of the USFWS and WDW.

2.7.6.6 Visitor Use

Table 2-25 summarizes visitor use to the Columbia River in this subregion. No visitation data are currently available for the dispersed, non-site specific recreational use that occurs at all of the reservoirs. For this reason, the visitation statistics from the table underestimate the total use.

Table 2-25. Middle Columbia River Visitation Summary, 1987-1993.

MONTH	VISITOR-DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	AVG
CHIEF JOSEPH PROJECT/LAKE RUFUS WOODS								
Corps of Engineers Recreation Sites								
Jan	0.3	0.66	0.6	0.6	0.4	0.3	0.3	0.5
Feb	0.7	0.8	0.8	0.6	0.3	0.5	0.4	0.6
Mar	1.4	1.4	1.2	0.9	0.8	0.4	0.4	0.9
Apr	1.7	2.3	2.1	2.2	1.8	1.3	3.3	2.1
May	3.9	3.9	4.4	3.5	3.5	4.7	4.8	4.1
Jun	4.6	4.5	4.8	5.2	5.2	3.3	4.3	4.6
Jul	5.4	5.1	5.5	5.9	6.0	5.4	4.8	5.4
Aug	5.3	5.3	5.4	7.0	6.6	4.9	3.9	5.5
Sep	4.1	3.5	3.9	4.8	4.1	3.6	3.1	3.9
Oct	2.7	2.1	2.0	1.5	2.2	1.6	1.1	1.9
Nov	1.0	1.1	0.9	0.9	0.8	0.6	0.3	0.8
Dec	.6	0.3	0.7	0.5	0.7	0.4	0.3	0.5
Subtotal	31.9	30.9	32.3	33.7	32.5	26.9	27.2	30.8
Other Recreation Sites								
Bridgeport State Pk.	15.0	15.5	14.4	17.9	15.6	--	--	
TOTAL	46.9	46.3	46.7	51.6	48.1	--	--	
ROCK ISLAND DAM AND LAKE								
TOTAL	--	--	1368.9	852.0	586.3	--	--	
ROCKY REACH DAM AND LAKE								
TOTAL	--	--	730.2	790.7	575.6	529.0	483.4	
Visitation data are not available for privately operated recreation sites on Rock Island and Rocky Reach Reservoir. Most visitation occurs on Chelan PUD sites; including those operated by Washington State Parks and other local entities.

Figure 2–22. Rafting on the Snake River in Hells Canyon

2.7.7 Middle Snake River (Brownlee, Hells Canyon, and Oxbow Projects and the Snake River through Hells Canyon)

2.7.7.1 General Overview

The recreational resources of the middle Snake River are those from the Washington–Oregon border (river mile 176) upstream to approximately Weiser, Idaho (river mile 345). This 170 mile stretch of river offers a rich and diverse array of outdoor recreation opportunities that are important from a national, regional, and local perspective. From river mile 247 downstream to the Washington–Oregon border, the Snake River is within the Hells Canyon National Recreational Area (HCNRA). Upstream of HCNRA, the middle Snake River is impounded by a series of three non–Federal hydroelectric dams known as the Hells Canyon Complex (Complex).

2.7.7.2 Aesthetics

The Hells Canyon Complex of dams is located in the spectacularly steep and narrow Hells Canyon. The slopes adjacent to the projects are generally covered with grasses and sagebrush, with patches of riparian vegetation found along reservoir edges and up side canyons. Due to the narrow and steep canyon walls, views within the canyon are very restricted. Near Brownlee Dam, the canyon begins to widen and remains fairly consistent in width for the length of the reservoir. Views at Brownlee are still restricted to within the canyon, but the width allows for more panoramic views.

Most of the land adjacent to the middle Snake subregion is undeveloped. There are some parcels of private property adjacent to the project, but most are located in the more agricultural southern end of the reservoir near Weiser. Use of public and private lands near the reservoir includes livestock grazing, recreation, and scattered rural residential.

Access to most of the Brownlee project is limited to the Snake River Road which is a 42-mile-long (68 km), narrow, winding gravel road located on the western side of the reservoir. The road is used by recreationists and local residents, and offers a range of views of the reservoir that include panoramic views from high above the reservoir and close views from the shores. Most viewers at Brownlee would likely be recreationists. Due to the area's sparse population and lack of major highways, the number of local residents and travelers viewing Brownlee from nearby roads is not large.

Below the Complex, the Snake River flows through the HCNRA. Views in the canyon are very restricted, and are generally only of the immediate river, riverside environment, and adjacent steep, high slopes and cliffs. There is very limited road access to the canyon between Hells Canyon Dam and Rodgersburg, Oregon. Most viewers in the HCNRA see the canyon from private or commercial watercraft.

2.7.7.3 Hells Canyon Complex

The Complex consists of three dams and associated reservoirs—Brownlee, Oxbow, and Hells Canyon—constructed, owned, and operated by Idaho Power Company (IPC). Although it is not part of the Federal system of hydroelectric projects, the Complex is indirectly linked to the operation of the 14 Federal projects under study in the SOR. The effects of a new system operating strategy may be reflected in IPC operations that respond to additional Water Budget requests, flood control shifts, and storage requirements. For the purposes of this study, it is assumed, however, that the IPC projects will not be affected by changes in system operations considered under SOR. Thus, this section only briefly discusses the type and nature of recreational facilities and resources found in the Complex to provide a perspective on the diverse local and regional outdoor recreational opportunities available in the Middle Snake region.

Brownlee Dam is the largest of the three hydroelectric projects and is the only storage project, with a capacity of 980,250 acre-feet. The dam and reservoir extend about 60 miles, from River Mile 285 to the pool headwaters at Weiser, Idaho. The two remaining dams, Oxbow and Hells Canyon, are run-of-river projects with storage capacity of 5,420 acre-feet and 98,820 acre-feet, respectively. IPC operates the dams within guidelines set in the Federal Energy Regulatory Commission (FERC) license for the Hells Canyon Project, No. 1971.

Recreation Facilities. Recreation is one of the primary authorized project purposes, along with power generation, flood control, and navigation. IPC has developed an array of recreation sites to promote recreation opportunities in the Complex. IPC recreational sites in the Complex include Hells Canyon and Copperfield Parks located at the Hells Canyon pool, McCormick Park at the Oxbow pool, and Woodhead Park at the Brownlee pool. These parks are all fully equipped day-night use facilities, with RV electrical hookups, showers, and boat ramps available at all but Woodhead Park. Because Brownlee reservoir has increasingly been used as a primary regional recreation area in recent years, IPC requested FERC permission to expand, upgrade, and improve recreational facilities at its Woodhead Park facility on Brownlee reservoir.

In addition to IPC's private facilities, there are six recreational developments located on or near reservoirs in the Complex that are managed by various Federal, state, and county park and land management agencies, including USFS, Bureau of Land Management (BLM), and Oregon State Parks. Over the years, IPC has contributed substantial funding to help improve and expand these publicly operated recreational areas. Some non-IPC facilities, such as Hewitt Park, Steck Park, and Farewell Bend State Park, are highly developed and offer the public complete day-night use opportunities and boat launching capability. For the most part, however, reservoir access is limited and several primitive, undeveloped park facilities occur throughout the Complex.

Recreational Activities. Recreation is an important use of the middle Snake River. There are many outstanding recreational opportunities, including boating, fishing, waterskiing, camping, picnicking, backpacking, hiking, sightseeing, hunting, and wildlife viewing. In recent years, recreational use, especially at Brownlee, has continued to increase because an extremely popular warm-water fishery for smallmouth bass, channel catfish, and panfish now exists in the reservoir.

This increased recreational demand is reflected by comparing 1982 and 1991 estimated visitation statistics reported for IPC recreation sites in the Complex. Over that time, use increased almost 300 percent, from 302,777 annual visitor days in 1982, to 890,500 in 1991. Similarly, angler creel census data collected at Brownlee reservoir by Idaho Department of Fish and Game and Oregon Department of Fish and Wildlife reveal an exponential growth in angling activity over the last 20 years. In 1970, only 64,068 angler-hours were spent fishing at Brownlee, compared to 2,942,553 angler-hours in 1989 (BLM, 1991).

2.7.7.4 Hells Canyon National Recreation Area (HCNRA)

The HCNRA straddles the middle Snake River and includes 652,488 acres in the Hells Canyon Wilderness (194,132 acres) and the Snake River segment of the National Wild and Scenic River system. Hells Canyon is the deepest gorge in North America and is rated as one of America's scenic wonders and natural heritages (CH2M Hill, 1984). The scenic river flows through the Hells Canyon Corridor, forming the boundary between Oregon and Washington, and includes portions of the Nez Perce, Payette, and Wallowa-Whitman National Forests. HCNRA extends through three national forests, but is managed by the USFS Wallowa-Whitman National Forest, headquartered in Clarkston, Washington.

This approximately 70 mile (113km) river stretch was preserved to maintain its unique and remarkable free flowing characteristics under the Hells Canyon

National Recreation Area Act of 1975 and Wild and Scenic River Act of 1968. The HCNRA boundary originates at river mile 180, about 33 miles (53 km) upstream from Asotin, Washington (river mile 147) and stretches to Hells Canyon Dam at river mile 247. The 31.5 mile (51 km) section of river between Hells Canyon Dam and Pittsburg landing (river mile 214.5) is designated "Wild" under the Wild and Scenic Rivers Act. From Pittsburg landing to the Wallowa-Whitman National Forest, the 36-mile (58 km) section of the river is classified "Scenic". Downstream of HCNRA to the upper end of the Lower Granite pool, the Snake River has also been studied by the NPS for inclusion in the National Wild and Scenic Rivers system because of the numerous recreational activities that occur along this 33-mile (53 km) section.

HCNRA is a nationally significant recreational resource that may be directly affected by changes in the operation of Federal projects. The extent to which changes in system operations may cause IPC operations to vary could indirectly impact the quality of flow dependant recreational activities occurring in HCNRA. Specifically, depending on the amount and timing of water volumes stored, released, and passed downstream through the Complex, HCNRA flows may become extremely variable during the important recreational season. HCNRA river managers have expressed concerns about the boating, navigation, and environmental hazards caused by radical fluctuations in flows, which apparently occurred with some regularity in May and June, 1991 (Seamans, 1991). Severe fluctuations in flows (6-24 kcfs) washed out rapids, stranded boaters, led to boating accidents, dewatered prime fish and wildlife habitat, caused excessive sandy beach erosion, and resulted in high nitrogen supersaturation levels occurring below Hells Canyon Dam. Flows falling below 8,000 cfs (227 cms) have stranded commercial tour boats in the Rush Creek stretch of HCNRA.

2.7.7.5 Recreation Facilities

Due to the wild and scenic character of the river, most of the recreation sites found in HCNRA are

largely primitive, remote, or only semi-developed camping and boating beaches (Table 2-27). There are 88 such sites in HCNRA, of which only three, Pittsburg Landing, Kirby Creek Resort, and Kirkwood Historic Ranch, are considered to be semi-developed public or private recreation sites. Most of the remote sites are small and provide multi-day boating recreationists with overnight camping and day-use access to HCNRA. They may accommodate up to 30 people, generally have a beach and chemical toilet, and may contain water and a picnic table. In some cases, the semi-developed locations offer boat launching and landing ramps to accommodate power boat users of HCNRA (i.e. Pittsburg Landing, Hells Canyon Creek). The USFS monitors the use of these sites to ensure that crowding, noise, pollution, visibility, and other aesthetically unappealing attributes are effectively controlled or eliminated where possible.

There are only a handful of what are considered to be more developed recreation sites located within, and in one instance outside the HCNRA boundary (Table 2-26). The most developed site is found downstream of the HCNRA at the Grand Ronde boat launch. It is considered an important site since it provides the only public launch usable by big power boats between the HCNRA boundary and Asotin, Washington, and it is the major take-out point for float boat traffic originating in HCNRA. The few remaining developed or semi-developed sites (i.e., Pittsburg Landing, Dug Bar, and Hells Canyon Creek) provide the only passenger car access to HCNRA, but overnight camping facilities are limited.

2.7.7.6 Recreation Activities

HCNRA is nationally renowned for its unique and challenging whitewater float and power boat recreation opportunities. Float boat recreation occurs primarily in the form of private and commercial rafting and kayaking excursions through the many challenging rapids in HCNRA. Float trips usually originate at Hells Canyon Creek launch site (at the

base of Hells Canyon Dam) and typically involve multi-day trips through Hells Canyon Gorge. A recent survey of HCNRA visitors found that 80 percent of commercial floaters and 76 percent of private floaters spent 2 to 6 days on the river (Krumpe et. al., 1989). Float boaters also enter the "Scenic" river section from the lower Salmon River, originating at Graves Creek/Pine Bar or Hammer Creek/White Bird on the main Salmon.

Power boats are typically private or commercial jet boats (20-to 30-foot private and up to 50 feet commercial) which most frequently launch in the downstream sections of the gorge and make single or multi-day round-trips through HCNRA. Krumpe (1989) found that the majority of commercial power boat trips (85 percent) were one to two days, while 40 percent of private jet boat spent 3 to 4 days on the river. Private jet boaters also launch and take-out in the most upstream section of HCNRA (Hells Canyon Creek).

Many diverse activities are important to those visitors who access HCNRA via private and commercial float and jetboats. For example, the preferred activities for a typical private float visitor to HCNRA are, in order of priority: rafting, camping, viewing wildlife, photography, swimming, fishing, visiting historic or cultural sites, hiking, kayaking, and hunting (Krumpe et. al., 1989). Similarly, the most important activities for commercial floaters were rafting, camping, viewing wildlife, visiting cultural sites, and photography. In contrast, private jet boaters view power boating, fishing, viewing wildlife, photography, and camping as the most important reasons for recreating in HCNRA. Commercial jet boat users value power boating, visiting cultural sites, viewing wildlife, and photography. These survey statistics indicate, that visitors who access the river on private jet boats place a greater emphasis on camping, fishing, and swimming activities because this group spends a generally longer time recreating on the river. Moreover, float boat and commercial jet boat recreationists appear to be orientated more to camping and sightseeing activities.

Figure 2-23. Map of Snake River Hells Canyon Reach

Table 2-26. Recreation Facilities, Hells Canyon National Recreation Area

Map Key	Name	Owner	State and River Mile	Picnic Tables	Camp-sites	Beach	Boat Ramp	Boat Dock	Drinking Water	Toilets	Other Facilities
1	Swallow Park & Marina	COE	W-141	Y	N	Y	Y	Y	Y	Y	Coast guard station, bike trail
2	Southway Snake River Access	COE	I-142	N	N	N	Y	N	N	N	Bike path to Wells Park
	Greenbelt Launch Site	COE	W-138	N	N	N	Y	N	N	Y	Greenbelt bike path
3	Wells Gate Marina	Private	I-144	N	N	N	N	Y	Y	Y	
4	Hells Gate Park (960 acres)	IDPR	I-144	55	93	1,200 ft	Y	N	Y	Y	Trails (foot, bike, horse), visitor center, horse control
5	Chief Looking Glass Park & Marina	COE	W-145.5	N	N	N	N	Y	Y	Y	Showers
6	Grande Ronde Boat Ramp	WDOG	W-168.5	N	N	N	Y	N	N	Y	
7	Copper Creek Resort	Private	O-205.5	N	N	N	N	Y	Y	Y	Several buildings for housing guests
8	Lower Pittsburg Landing	HCNRA	I-215	I	U	N	Y	N	Y	Y	Fuel tanks nearby
9	Kirby Creek Resort	Private	I-219	N	N	Y	N	Y	Y	Y	Lodge for guests and owner's home
10	Kirkwood Historic Ranch	HCNRA	I-220.5	N	N	N	N	Y	N	N	Restored historic ranch, museum, interpretive program Ranger station (trailer)

Table 2-26. Recreation Facilities, Hells Canyon National Recreation Area – CONT

Map Key	Name	Owner	State and River Mile	Picnic Tables	Camp sites	Beach	Boat Ramp	Boat Dock	Drinking Water	Toilets	Other Facilities
11	Hells Canyon Creek Launch	HCNRA	O-247	I	N	N	Y	Y	N	Y	Ranger station (trailer)
12	Hells Canyon Park (10 acres)	IPCo	I-263.5	4	44	200 ft	Y	Y	Y	Y	Showers, trailer hook-ups
13	Cooperfield Park	IPCo	O-258(e)	N	100	Y	Y	N	Y	Y	Showers, trailer hook-ups
14	McCormick Park (7.3 acres)	IPCo	I-284	3	3B	Y	Y	Y	Y	Y	Trailer hook-ups
15	Woodhead Park (68.1 acres)	IPCo	I-287	10	Y	150 ft	2	Y	Y	Y	
16	Hewett Park	Baker Co.	O-293(e)	Y	35	N <u>a/</u>	2	Y	Y	Y	
17	Spring Recreation	BLM Vale	O-327	Y	U <u>b/</u>	N	Y	?	Y	Y	
18	Steck Recreation Site (12 acres)	BLM Boise	I-328	33	38	Y	Y	Y	Y	Y	Fish cleaning station
19	Farewell Bend State Park (72 acres)	ODOT	O-333-5	73	94	Y	Y	Y	Y	Y	Showers, trailer hook-ups, trailer dump station

FOOTNOTES

a/ Swimming in undesignated area. Rocky shoreline.

b/ Gravel parking area has capacity for 40 RV's.

GUIDE TO ABBREVIATIONS

COE Corps of Engineers

IDPR Idaho Department of Parks and Recreation

WDOG Washington Department of Game

IPCo Idaho Power Company

BLM Bureau of Land Management and District name

ODOT Oregon Department of Transportation

IDFG Idaho Department of Fish and Game

N - No Y - Yes # - of sites or linear feet of beach

Table 2-27. Hells Canyon National Recreation Area Visitation Summary, 1987-1991

Project:	HELLS CANYON NATIONAL RECREATION AREA				
	VISITOR DAYS (in 1,000's)				
	<u>U.S. Forest Service Recreation Sites</u>				
1991	1990	1989	1988	1987	AVERAGE
50.2	48.7	42.1	39.1	37.4	43.5

The popularity of HCNRA and its unique combination of activities and resource attributes cannot be overstated. Float and jet boat users state that they value most highly the scenery, the excitement, the natural splendor, the historic and cultural attractions, and escape from routine that a river trip in Hells Canyon provides (Krumpe et. al., 1989). Moreover, the river offers excellent fishing opportunities for steelhead trout and world-class sturgeon. In recent years, hunting for upland game bird (chukar) and mule deer has increased in popularity especially during the unregulated fall season.

2.7.7.7 Visitor Use

Evidence that the demand for boating related recreation in HCNRA is increasing in popularity is reflected by the annual visitation statistics compiled by the USFS. Table 2-27 provides visitation data for private and commercial float and power boat use (in service days) during the regulated season (the first Friday before Memorial Day weekend through September 15) from 1987-1991. A distinct upward trend in visitation is evident, with visitation increasing 38.3 percent over the last five years. Because of this increasing demand and the potential for heightened user conflicts in HCNRA, USFS recently completed a Limits of Acceptable Change (LAC) planning process to address the desire and need for the USFS to change the Recreation Management Plan for the Snake River in HCNRA (Krumpe and McCoy, 1991). Several recommendations to improve management of recreational use in HCNRA were proposed through this LAC process. USFS has recently implemented new regulations to manage recreation visitor use of HCNRA by amending the River Management Plan.

2.7.8 Clearwater River (Dworshak Project and Clearwater River Downstream)

2.7.8.1 Overview

This subregion includes Dworshak Dam and lake, located on the North Fork of the Clearwater River, the North Fork of the Clearwater River below Dworshak Dam, and approximately 40 miles (64 km) of the Clearwater River from its confluence with the North Fork to Lower Granite Lake at Lewiston, Idaho. Dworshak Dam impounds a lake which extends 54 miles (87 km) up the North Fork of the Clearwater River.

This region has a typical western interior climate. Summers are warm with little precipitation while winters are cold and wet with precipitation falling as rain or often snow. The subregion consists of the mixed coniferous forest surrounding the Dworshak pool and then transitions into the arid grasslands of the Columbia Plateau at Lewiston. The Clearwater River corridor below Dworshak Dam contains significant riparian vegetation adjacent to the river until it reaches the impoundment area of Lower Granite Lake just above Lewiston.

The population density of this subregion is low with only one major population center, Lewiston, Idaho, and Clarkston, Washington, located at the western edge of the region. The combined population of these two adjacent towns is approximately 40,000. The economic base for the region is primarily agriculture, with wheat farming predominant on the western end and wood products production on the eastern end.

Figure 2-24. Dent Acres Recreation Area at Dworshak Lake

Access to the Clearwater River is fair with a number of river access sites constructed adjacent to U.S. Highway 12, which follows along the river in this reach. Public access at Dworshak is fair, though limited to the vicinity of the dam, two upstream road crossings, and several road ends. All other access to public land at Dworshak is, for the most part, limited to those visitors using a boat or other water craft.

The major recreation activities in the region are sightseeing, fishing, boating, camping, and hunting. With limited public land and water access in the subregion, except along the Dworshak/Clearwater River corridor, most visitors are attracted to the variety of public resources and the activities avail-

able in the corridor. A number of visitor access sites have been developed at Dworshak and on the Lower Clearwater River. Recreation on Dworshak is primarily a summer activity while the Clearwater River is nationally known for excellent fall and winter steelhead fishing.

2.7.8.2 Aesthetics

Dworshak Reservoir winds through remote, forested foothills of the Bitterroot Range. The reservoir generally ranges from 0.5 to 1 mile wide. Views from the water and the shoreline are of the reservoir itself and the adjacent foothills. Views up and down the reservoir range from 1 to 5 miles (1.6 to 8 km).

Figure 2-25. Map of Dworshak Lake

Land uses on and adjacent to the reservoir include forestry, log rafting, recreation, power generation, and fish and wildlife management. Forestry is the primary land use near Dworshak, and it occurs on both private and public land. Harvest activities are evident from several parts of the reservoir. The USFS, BLM, Idaho State Land Board, Burlington Northern Railroad, and the Potlatch Corporation are the major owners and managers of adjacent lands.

There are no roads that follow Dworshak Reservoir for any appreciable distance. Several local roads, most of which are gravel or dirt, provide access to Dworshak. Most go to specific places along the reservoir, usually developed recreational facilities. Viewing opportunities from shore are limited to those areas of the reservoir with roaded access and/or developed facilities.

Recreationists are the primary viewers of Dworshak Reservoir. The majority of recreationists in the area travel specifically to Dworshak to recreate. Because Dworshak is approximately 4 miles from the area's only major highway (U.S. Highway 12) and not visible from it, travelers not specifically driving to Dworshak can not see the reservoir.

The North Fork of the Clearwater River flows into and out of Dworshak Reservoir. From Dworshak Dam the river flows approximately 1.5 miles (2.4 km) to the southwest where it joins the mainstem of the Clearwater River. The mainstem flows through very scenic sections of Clearwater Canyon and merges with the Snake River at Lewiston, Idaho. The winding river canyon and steep hillsides restrict views within the canyon. Generally only the river and adjacent hillsides can be seen from the river. The mainstem Clearwater River between the confluence and Lewiston is visible from U.S. Highway 12. As a result, it is viewed by many more people than is Dworshak Reservoir. Viewers include local

residents, recreationists, and travelers. Highway turnouts and recreational parking areas allow relatively easy access to the river.

Land ownership along the river is mixed and includes ownership by the Nez Perce Indian Tribe, the Federal government (managed by the U.S. Forest Service), and private entities. Land uses along the river include forestry, recreation, fish and wildlife management, agriculture, industry, and residential development. The lands adjacent to the river are generally undeveloped until approximately 5 to 10 miles east of Lewiston.

2.7.8.3 Recreation Sites and Facilities

Numerous recreation sites and facilities have been developed along the lower Clearwater River corridor and on the public land surrounding Dworshak Reservoir. A number of different agencies and organizations have been instrumental in the planning, construction, and maintenance of these recreation areas and sites. Table 2-28 provides information on specific recreation sites.

At Dworshak, the Corps and State of Idaho manage recreation facilities ranging from fully developed vehicle access camping areas, picnic areas, and boat launching facilities to numerous primitive boat access mini-camps. The marina at Big Eddy was damaged by a storm in June 1992 and has not operated since.

On the lower Clearwater River, recreation sites have been developed by the State of Idaho (Fish and Game and DOT), local counties, the NPS and the Corps. Most recreation sites along this section of the Clearwater River are not highly developed and provide only toilet and trash facilities and river access. Approximately half of the 19 recreation sites along the river have boat ramps.

Table 2-28. Dworshak Lake Recreation Sites and Facilities

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAM SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
Big Eddy	1	2				4				
Bruces Eddy		4								
Canyon Creek	1	1				2		12		
Dent Acres	1	3				6	1	50	50	1
Dworshak Visitor Center										
Freeman Creek— Dworshak State Park	1	2			3	25	1	92	52	3
Grandad Creek		1								
Merrys Bay						3				
Mini—Camps								76		4
Powerhouse Road and N.F. River										
Three Meadows Group Camp										
Viewpoint #2										
TOTAL	4	13	0	0	3	40	2	230	102	4

2.7.8.4 Major Activities

Recreation use in this subregion includes both overnight and day—use activities. On the lower Clearwater River, fishing is by far the major recreation activity. Over 80 percent of the visitation on this section of river occurs during steelhead season, which runs from October to April. Boating use during the steelhead season is high, but this activity is in conjunction with fishing use. During the summer season, uses on the Clearwater River include sightseeing, power boating, trout fishing,

swimming, camping, and rafting. The Clearwater Recreation Survey (Krump, 1987) found that 74 percent of the recreation users on the Clearwater River were from Idaho and 37 percent of those were from the local area.

Along the lower Clearwater River, summer use of the river for rafting, tubing (floating the river on an inner tube) and swimming is increasing. Traditionally summer is the season of lowest use on this section of the Clearwater, due to the high numbers of fall and winter steelhead anglers. A continued increase

in summer usage will bring additional impacts to the recreation sites along the river.

For those visitors interested in history, human use in the corridor extends from the earliest Native American settlement to pre-European contact with Nez Perce communities, to early Euro-American explorations, including the Lewis and Clark Expedition, to the gold mining boom of the late 19th century. At several sites, interpretation of the Nez Perce presence along the river is provided by the NPS as part of that agency's Nez Perce Parkway.

Located near the confluence of the North Fork of the Clearwater River and the main fork of the Clearwater are the Dworshak National Fish Hatchery and the Clearwater Fish Hatchery. The former is operated by the USFWS, the latter by Idaho Department of Fish and Game. Interpretive facilities at both hatcheries provide visitors with information on the purpose for the hatchery and how it operates.

2.7.8.5 Visitor Use

Table 2-29 shows visitor use at Dworshak Lake from 1987 through 1993. There is no current, con-

solidated visitor use data available for the Clearwater River.

Recreation use at Dworshak Lake is more varied than on the Clearwater, and the significant recreation season occurs during the summer months. Sightseeing, boating, fishing, camping, and picnicking are the most popular recreation activities at Dworshak. In the summer, water-contact activities, including swimming and water skiing, are very popular and become an important part of the recreation mix on the reservoir. In the fall months, sightseeing, fishing, and hunting are the recreation activities most common on the lake and the surrounding public land. Recreation surveys by the Corps in the mid-1980's indicated that the majority of visitors to Dworshak were from within a 100-mile radius of the lake.

The lake has a regionally important fishery. Kokanee are currently the most sought after game fish species and are known for their large size in Dworshak Lake relative to other lakes and reservoirs in Idaho. Other sports species include rainbow trout, bull trout and smallmouth bass. The bass population appears to be healthy and has increased over time.

Table 2-29. Dworshak Lake Visitation Summary, 1987-1991.

CORPS OF ENGINEERS AND IDAHO STATE PARKS RECREATION SITES								
MONTH	VISITOR-DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	AVG
Jan	3.0	3.5	6.2	6.5	4.8	5.8	4.5	4.9
Feb	3.8	5.2	8.8	7.3	7.7	9.0	8.2	7.1
Mar	7.8	9.1	13.1	14.8	13.7	15.6	18.7	13.3
Apr	9.0	5.4	12.8	14.4	14.7	16.4	15.1	12.5
May	19.4	20.8	19.9	18.4	20.5	24.6	27.6	21.6
Jun	26.3	38.3	29.4	31.5	39.9	42.4	48.3	36.6
Jul	40.2	30.1	50.5	42.5	45.6	52.5	42.7	43.4
Aug	22.8	26.7	46.5	33.4	46.8	34.7	43.2	36.3
Sep	7.9	7	15.4	12.9	19.0	16.1	19.8	14.0
Oct	4.7	8.2	8.2	6.7	10.3	10.7	19.8	9.8
Nov	3.4	3.9	3.9	5.8	6.9	6.2	6.7	5.3
Dec	2.5	6.5	6.5	4.7	7.1	5.8	5.8	5.6
TOTAL	150.8	164.7	221.2	198.9	237.0	239.8	260.4	210.4

Figure 2-26. Lewiston Levee at Lower Granite Lake

On Dworshak, the boat access mini-camps provide a unique recreation opportunity for lake visitors. At the Dworshak Visitor Center, visitors find information on the recreation opportunities at the lake and the surrounding region, the history of the region, and details on construction and operation of Dworshak Dam. Visitors may also tour the dam and powerhouse.

2.7.9 Lower Snake River Subregion (Ice Harbor, Lower Monumental, Little Goose, and Lower Granite Projects)

2.7.9.1 Overview

This subregion includes the four Corps run-of-river projects on the lower Snake River between its confluences with the Clearwater and Columbia Rivers. The projects are Ice Harbor (Lake Sacajawea), Lower Monumental (Lake West), Little Goose (Lake Bryan), and Lower Granite (Lower Granite Lake) (Figure 2-27). This region includes approximately 140 total river miles (225 km), including the Snake and part of the Palouse and Tucannon Rivers. The major portion of this river subregion is located in the narrow gorge formed by the Snake River and is characterized by basalt cliffs and steep talus slopes. The climate is characterized by relatively low

precipitation, wide temperature variations, low humidity, high evaporation, and abundant sunshine. Trees are scarce, and the vegetative cover consists mainly of grasses, forbs, and low shrubs.

Population density in the immediate area of the lower Snake River corridor is low. The major population centers in the region are located at the extreme west and east ends of the river corridor. The Tri-Cities area, with a combined population of 120,000 in Richland, Kennewick, and Pasco, lies within a 25 mile driving distance of Lake Sacajawea on the Columbia River. At the opposite end are the two communities of Lewiston and Clarkston with a combined population of 40,000. These towns are typical to the region, having an agricultural socio-economic base generated largely by the surrounding wheatlands and forests.

The steep, rugged character of the Snake River Canyon has limited both the recreational development and road access to the water. A large part of the river corridor is currently inaccessible by road. Because of the limited public land base in the region, the majority of the recreational demand is water oriented, and comes from within a 100-mile radius of the river corridor.

Figure 2-27. Lower Snake River

The most popular recreation activities are day—use activities: swimming, picnicking, boating, fishing, and sightseeing. Camping and hunting account for a smaller percentage of the total recreational use primarily due to the lack of appropriate facilities and limited access. Recreational use is very seasonal with the high—use period during the summer months and lower use during the remaining three seasons.

2.7.9.2 Aesthetics

The lower Snake River passes through the Blue Mountains and Columbia basalt plain of Oregon and Washington. The landscape in the western, downstream end of the subregion is characterized by low hills covered with steppe vegetation. Upstream in the central and eastern sections of the subregion, the river valley is deeper as the side walls of the canyons rise from between 200 to 2,000 feet above the reservoirs. The steep, rugged buttes and canyon walls framing the reservoir are the dominant landscape features in the central and eastern sections of the subregion. Views within the river valley are contained by the steep hillsides that form the walls of the canyon. Due to the twisting nature of the river valley, views within the valley rarely extend beyond 2 to 3 miles (3 to 5 km). Reservoir pool width generally varies from 1 to 1.25 miles (1.6 to 2 km).

Land uses near and adjacent to the project pools include agriculture, port facilities, recreation, and residential. Development near the reservoirs is fairly intensive at the eastern and western ends (Lewiston—Clarkston and the Tri—Cities, respectively). Parks, marinas, and housing developments adjacent to the river create a suburban/urban character in places. By contrast, the remote interior portions of the subregion are less developed and relatively difficult to access.

With two exceptions, the lower Snake projects are not visible for any great length from major roads or

highways. Wawawai River Road (a county highway) and State 193 follow the north side of Lower Granite, and U.S. 12 follows Lower Granite approximately 7 miles (11 km) on the south side from Clarkston to Silcott. Near Pasco, U.S. 12 crosses the river again and offers views of the river near its confluence with the Columbia. The river is also crossed in six locations (including at all four dams) by state or county highways.

Most viewers of the projects are recreationists using the projects; local residents, primarily of Lewiston—Clarkston and the Tri—Cities, and travelers on U.S. 12 at either end of the lower Snake reach.

2.7.9.3 Recreation Sites and Facilities

The Corps manage both sides of the river from the Tri—Cities, Washington, to Lewiston, Idaho. Recreation facilities on the Snake River vary from full—service state parks to primitive boat launching areas. These areas are primarily water oriented and are developed where public roads come down to or cross the river. Developed facilities in this subregion include 28 boat ramps and 11 swimming beaches. Development on the shoreline is designed to be usable during the full range of the operating pool, normally five feet or less. A large number of the recreation sites are leased to state and local entities for operation and maintenance. Specific site information is available in Table 2—30.

Due to the rural agricultural nature of land ownership in southeastern Washington, northeastern Oregon, and northern Idaho, the majority of the developed recreation facilities in this region are located on the Snake River corridor, on public land managed by the Corps. These facilities are an important economic as well as recreational resource to the region. The operation of the Snake River dams and lakes may have a very significant impact on this recreation resource.

Table 2-30. Lower Snake River Recreation Facilities

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
**PROJECT: LOWER GRANITE DAM AND LAKE										
Blyton Landing		1								
Chief Looking Glass Park	1	2				4				
Chief Timothy State Park	2	4				32		33	33	
Clearwater Park										
Clearwater Ramp	1	2								
Greenbelt Ramp		2								
Hells Gate State Park	1	6				60	1	93	64	
Lewiston Leree Parkway						4				
Lower Granite Dam						4				
Nisqually John Landing		1								
Offield Landing		1								
Red Wolf Marina	1	1				6				
Southway Ramp	1	2								
Swallows Park	2	6				22				
Wawawai County park						10	2	9		
Wawawai Landing		1								
SUBTOTAL	9	29	0	0	0	142	3	135	97	0
**PROJECT: LOWER MONUMENTAL DAM/LAKE WEST										
Ayer Boat Basin	1	2				2	2			
Devils Bench										
Lower Monumental Dam	1	2				3				
Lyons Ferry Marina	1	1				4		43	18	
Lyons Ferry State	1	2				19		52		
Riparia										
Texas Rapids	1	1				4				
SUBTOTAL	5	8				32	2	95	18	
**PROJECT: LITTLE GOOSE DAM/LAKE BRYAN										
Boyer Park & Marina	1	3				16		28	28	
Central Ferry State Park	1	4				30		62	30	
Garfield County	1	2								
Illia Dunes										
Illia Landing		1				2				

Table 2-30. Lower Snake River Recreation Facilities – CONT

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
Little Goose Dam						3				
Willow Landing	1	1				2				
SUBTOTAL	4	11				53		90	58	
**PROJECT: ICE HARBOR/LAKE SACAJAWEA										
Big Flat										
Charbonneau Park	1	2				88	1	54	54	1
Fishhook Park	1	2				72	1	101	42	
Hollebeke										
Ice Harbor Dam	1	2				3				
Lake Emma										
Levey Park	1	1				123	1			
Lost Island (Votau)										
Matthews										
Walker										
Windust Park	1	1				32		28		
SUBTOTAL	5	8				318	3	183	96	1
TOTAL	23	56	0	0	0	545	8	503	269	1

2.7.9.4 Special Recreation

Visitor centers are available at all the Corps dams on the Snake River. These centers generally include information on power production, navigation, archaeology, geology of the canyons, history of the river, recreation opportunities, and fish transportation and passage facilities. There is a fish hatchery at Lyons Ferry operated by the State of Washington that has interpretive facilities.

2.7.9.5 Major Activities

The most popular forms of recreation in this river subregion are day-use related. Sightseeing, picnicking, boating, swimming, fishing, and camping is the ranking of preference. Demand for camping is low because of the lack of developed facilities, the limitations of the road network, and the attractiveness of higher elevation camping during the warmer summer months. Very few of the existing campgrounds are on a major highway, and they are used

primarily by the local population living within 100 miles.

Because of the hot, dry summers, swimming is a very important seasonal activity. The swimming facilities available are all developed on the river banks and are very dependent on the lake elevation. At minimum operating pool, most of the swimming beaches are not usable and support facilities are long distances from the water. There are some excellent natural beaches in the mid-section of the river; however, very few support facilities have been provided at these areas.

Day-use activities are primarily centered around the developed, landscaped, and irrigated recreation areas. Areas without irrigation are used more heavily in the early spring and fall, when the weather is milder. In this subregion, where there are few native shade trees, summer is too warm for much extended recreational use in undeveloped areas with little shade structure.

2.7.9.6 Visitor Use

Table 2-31 shows visitor use to the lower Snake River projects from 1987 to 1993. Lower Granite Lake supports approximately 60 percent of the total use of the four projects combined, reflecting its

proximity to the Lewiston/Clarkston population center. Ice Harbor project receives the next highest use due to its proximity to the Tri-cities area. Lower Monumental and Little Goose projects are relatively inaccessible to major population centers and, consequently, support low levels of visitor use.

Table 2-31. Lower Snake River Visitation Summary; 1987-1993

VISITORS (x 1,000)								
MONTH	1993	1992	1991	1990	1989	1988	1987	AVG
LOWER GRANITE LOCK & DAM / LOWER GRANITE LAKE								
Jan	42.4	65.7	95.5	70.2	39.2	62.3	40.3	59.4
Feb	68.5	82.7	89.4	82.4	37.8	69.7	52.4	69.0
Mar	112.3	197.3	14.5	109.9	84.7	75.9	89.2	97.7
Apr	116.7	125.8	130.1	118.7	99.9	108.3	100.1	114.2
May	174.2	183.1	160.1	161.5	129.0	164.3	98.1	152.9
Jun	195.5	304.0	211.6	273.0	187.1	171.9	176.7	217.1
Jul	232.0	227.6	228.7	200.2	203.6	107.5	190.3	198.6
Aug	251.6	236.5	294.1	224.0	167.5	173.7	160.2	215.4
Sep	169.9	129.5	152.7	99.3	158.9	71.7	125.7	129.7
Oct	142.5	149.5	149.5	99.5	132.1	76.5	86.9	119.5
Nov	103.0	93.6	93.6	104.6	123.5	80.6	82.2	97.3
Dec	47.9	71.4	71.4	70.4	59.3	46.8	46.6	59.1
Subtotal	1656.5	1866.7	1691.2	1613.7	1422.6	1209.2	1248.7	1529.8
LOWER MONUMENTAL & DAM / LAKE BRYAN								
Jan	3.0	3.3	3.8	3.0	5.7	3.7	7.3	4.3
Feb	3.7	6.0	5.5	2.5	4.2	6.7	4.5	4.7
Mar	3.2	3.3	3.8	3.2	5.1	4.8	4.8	4.0
Apr	9.6	7.6	9.4	8.9	10.4	11.6	13.9	10.2
May	18.1	13.8	14.4	14.7	15.4	15.1	15.8	15.3
Jun	20.2	23.1	22.5	19.8	20.0	22.1	19.3	21.0
Jul	23.6	22.2	19.4	23.2	21.9	28.8	18.5	22.5
Aug	23.1	17.8	24.0	17.4	21.8	34.3	31.2	24.2
Sep	15.6	16.1	16.9	16.6	16.0	14.9	16.6	16.1
Oct	9.6	7.6	7.6	5.7	5.0	9.0	9.6	7.7
Nov	5.7	4.8	4.8	3.6	3.4	6.5	12.2	5.9
Dec	5.1	3.9	3.9	2.3	2.4	3.8	3.8	3.6
Subtotal	140.5	129.5	136.0	120.9	131.3	161.3	157.5	139.6
LITTLE GOOSE LOCK & DAM / LAKE WEST								
Jan	3.8	4.6	3.2	6.1	4.6	3.1	5.8	4.5
Feb	3.5	4.9	4.8	4.4	4.1	4.7	5.5	4.6
Mar	9.1	22.7	8.5	8.2	7.6	2.6	8.0	9.5
Apr	12.8	21.3	16.3	9.2	22.9	23.1	21.0	18.1
May	34.6	30.7	18.9	20.9	25.8	30.0	27.7	26.9
Jun	44.5	45.2	32.8	33.1	37.4	51.8	38.3	40.4
Jul	35.8	44.4	35.9	37.0	47.9	83.0	39.7	46.2
Aug	42	33.5	41.4	38.3	37.4	68.8	44.8	43.7
Sep	26.2	27.1	17.2	15.6	26.3	22.0	22.3	22.4
Oct	17.6	11.8	11.8	8.4	7.5	13.1	12.8	11.9
Nov	15.4	7	7.0	6.4	6.7	15.8	10.4	9.8
Dec	4.8	5	5.0	3.7	4.1	5.9	5.9	4.9
Subtotal	250.1	258.2	202.8	191.3	232.3	323.9	242.2	243.0

Table 2-31. Lower Snake River Visitation Summary; 1987-1993 - CONT

VISITORS (x 1,000)								
MONTH	1993	1992	1991	1990	1989	1988	1987	AVG
ICE HARBOR LOCK & DAM / LAKE SACAJAWEA								
Jan	4.5	3.7	4.3	5.2	7.5	6.3	4.8	7.3
Feb	5.7	10.5	4.9	3.9	5.2	17.1	6.0	10.7
Mar	35.8	27.8	39.5	22.3	17.1	12.3	16.5	34.3
Apr	25.8	46.2	25.9	33.3	36.1	39.7	29.9	47.4
May	69.6	59.3	57.5	51.8	48.8	49.0	71.7	81.5
Jun	62.9	100.1	101.5	79.4	73.3	91.2	78.2	117.3
Jul	143.3	116.7	79.3	106.3	102.1	84.0	104.2	147.2
Aug	96.9	88.2	102.3	87.1	98.4	82.6	101.8	131.5
Sep	33.9	29.6	53.7	26.9	34.9	33.3	33.5	49.2
Oct	24.5	18.5	18.5	18.1	19.1	27.2	13.7	27.9
Nov	10.3	8.8	8.8	8.5	5.9	9.0	6.7	11.6
Dec	11	6.6	6.6	3.6	5.9	6.9	5.9	9.3
Subtotal	524.2	516.0	502.8	446.4	454.3	458.6	472.9	675.0
Total	2571.3	2770.4	2532.8	2372.3	2240.5	2153.0	2121.3	2587.4

Figure 2-28. LePage Park at the mouth of the John Day River

2.7.10 Lower Columbia River Subregion (McNary, The Dalles, John Day, and Bonneville Projects, and Columbia River below Bonneville Dam)

2.7.10.1 Overview

This subregion encompasses the four Corps run-of-river reservoir projects on the lower Columbia River, including McNary (Lake Wallula), John Day (Lake Umatilla), The Dalles (Lake Celilo), and Bonneville (Lake Bonneville) Projects. Also included in this region is the Columbia River below Bonneville Dam (Figure 2-29). A large percentage of the water surface area in the region available for recreational use is contained in the impoundments behind the four Columbia River dams.

The scenic and recreational amenities of the lower Columbia River have gained national and international renown. In recognition of those amenities, Congress created the Columbia River Gorge National Scenic Area (CRGNSA) in 1986.

Interstate 84 in Oregon and Washington State 14 parallel the river providing direct access to its amenities. National and international travelers, residents from the metropolitan Portland and Tri-Cities, and residents of Hood River, The Dalles and other local communities create a significant demand for water-related recreation along Lakes Wallula, Umatilla, Celilo, and Bonneville. Those highways constrain development of additional facilities to meet future public demand.

The most popular form of recreation in the region is scenic driving. The highways provide access to majestic vistas of natural features such as forests, mountains, cliffs, rivers and streams, and waterfalls. Many visitors are attracted to impressive constructed features such as Bonneville and The Dalles Dams, fish hatcheries, and fish ladders, which are also popular visitor attractions. The region is also rich in history and prehistory. Features such as Native American petroglyphs, the route of the Lewis and Clark Expedition and the Oregon Trail, and historic navigation locks can be viewed and interpreted.

Figure 2-29. Map of Lower Columbia River

The region is also popular for its water-related recreation opportunities. The Columbia River and adjacent streams and lakes have long been popular for fishing, swimming, and boating. In the few years since windsurfing was introduced to the Columbia River gorge, it has grown dramatically in importance as a recreation activity and as a source of economic growth.

2.7.10.2 Aesthetics

The eastern section of the lower Columbia River subregion starts at the confluence of the Snake River and continues west to approximately Hood River, Oregon. The eastern section passes through the arid Columbia basalt plain and is characterized by cliffs and rock outcroppings that line the gorge interspersed with arid vegetation such as grasses and sage brush. The gorge in the eastern section is sufficiently deep that views from the reservoirs and adjacent highways are generally confined to the gorge. The reservoirs in the eastern section are generally from 1 to 2 miles wide, although parts of Lake Umatilla are as wide as 5 miles.

The western section of the lower Columbia subregion starts at approximately Hood River, Oregon, and continues west through the South Cascades and the CRGNSA to the northeastern edge of the Willamette Valley, and to the Pacific Ocean. The Columbia Gorge section of the subregion is characterized by high, steep, sidewalls, relatively narrow reservoir pool widths (1 to 3 miles) and lush, tree-covered slopes. Views are generally contained within the gorge by the adjacent topography. West of the foothills of the South Cascades, the Columbia River Valley becomes broader and much more open. The free flowing Columbia flows through the wide valley as it continues to the ocean.

There are a number of different land uses adjacent to the four reservoirs in this subregion that influence their aesthetic character. Although most of the shoreline is undeveloped and natural in appearance, there are adjacent uses such as agricultural, urban, recreational, residential, and wildlife habitat, that influence visual quality and access. A number of communities are located adjacent to the river between

stretches of undeveloped lands. Among the larger communities are Pasco, Kennewick, The Dalles, Hood River, Portland, and Vancouver.

Visual and physical access to the reservoirs is plentiful from adjacent highways, towns and recreational sites. Highways are adjacent to most of the reservoirs and the free flowing lower section of the river. Viewers include travelers on the interstates and local roads that are adjacent to or cross the river, local residents, tourists, and recreational users. Due to their proximity to major population centers, reknown of the CRGNSA, abundant recreational facilities, and visual access from travel routes, projects on the lower Columbia subregion are viewed by more people than dams in any of the other subregions.

2.7.10.3 Recreation Sites and Facilities

To support the high levels of recreational use that occur in the region, an extensive system of parks and recreation sites has been developed. From river mile 125 below Bonneville Dam to river mile 350 at the upper end of Lake Wallula, approximately 75 water-related recreation sites or areas have been identified that may be impacted by operation of the Columbia system dams. These sites range from highly developed and intensively used parks with facilities to support a variety of recreational activities, to minimally improved fishing access sites and windsurfing beaches. These sites are listed in Table 2-32.

Recreation sites below Bonneville Dam down to the lower end of the Columbia River Gorge are included in the inventory because they may be directly impacted by project operations. Below the mouth of the Sandy River, the Columbia River widens and operational impacts on recreation are less significant. There are many other upland recreation sites within the study area, but they have been excluded from further analysis in this EIS because it is assumed that sites without a direct relationship to the river will not be impacted by project operations.

2.7.10.4 Managing Authorities

Corps of Engineers. The Corps is the Federal agency primarily responsible for providing recreation

facilities on lakes Bonneville, Celilo, Umatilla, and Wallula. Visitor facilities, including visitor centers, viewpoints, and fishing access sites are located at all four of the dams. The Corps also cooperates with Oregon and Washington state park departments and a variety of other local entities such as counties, cities and port districts, to build and manage a system of water-related recreation facilities, including boat ramps, swimming beaches, marinas, campgrounds, picnic areas, and interpretive sites

U.S. Forest Service. USFS is the major land management agency in the Columbia Gorge; Mount Hood and Gifford Pinchot National Forests encompass the gorge on the Oregon and Washington sides, respectively. The USFS administers 15 recreation sites within the Columbia Gorge National Scenic Area. Most of the USFS recreation areas are located at upland sites and are related to forest recreation, including campgrounds, picnic areas, trails and trailheads, viewpoints, and historic and prehistoric sites.

2.7.10.5 Special Recreation, Preservation and Natural Resource Areas

Much of the land along the mid-Columbia River adjacent to Lakes Bonneville, Celilo, Umatilla, and Wallula are dedicated natural resource preservation and management areas. These lands are managed by Federal and state agencies for natural resource values. In addition to supporting some of the developed recreation sites described above, these lands are also available for dispersed and low-density recreation activities consistent with other resource management objectives.

Columbia River Gorge National Scenic Area. In 1986, Congress created the CRGNSA. It covers 253,500 acres (102,600 hectares) along both sides of the Columbia River, encompassing Lake Bonneville and Lake Celilo up to the mouth of the Deschutes River. The CRGNSA has two primary purposes: 1) to protect and enhance the scenic, cultural, recreational, and natural resources of the Gorge, and 2) to protect and support the economy of the Gorge by encouraging growth to occur in existing urban areas.

The Scenic Area Act creates a partnership among the six counties within the Columbia River Gorge (Clark, Skamania, and Klickitat in Washington and Multnomah, Hood River, and Wasco in Oregon), a bi-state Commission, and the USFS. Each partner has important but different responsibilities in the Scenic Area. Together these agencies provide the overall coordination and management to achieve the purposes of the Act.

CRGNSA is divided into three types of management areas: Urban, General Management, and Special Management Areas. The thirteen communities in Oregon and Washington within the Scenic Area are designated as Urban Areas and are exempt from most aspects of the legislation. The Scenic Area Act allows for a variety of land uses and activities in the General Management Areas while the Special Management Areas are generally the most environmentally sensitive or scenic, and activities are more restricted. All Federal lands administered by the Corps within the CRGNSA are within the General and Urban Area zones.

The Management Plan for Special Management Areas within the CRGNSA identify the following goal pertaining to recreation:

“Ensure that all recreation development protects the scenic, cultural, and natural resources”.

The plan presents recreation policies and guidelines for implementing this goal. These guidelines need to be factored into the formulation of policy and management plans for Bonneville and The Dalles Lands.

Wildlife Refuges. This category includes both federally and state managed areas which have been set aside to manage, conserve, preserve, and enhance fish and wildlife resources. These areas are generally located along the Columbia River and are especially important in the management of migratory waterfowl. These areas generally have some facilities such as access, parking, trails, and boat ramps that support generally dispersed public use consistent with fish and wildlife objectives. Most of the numerous state and Federal fish hatcheries along the

river also allow public access and provide facilities to promote and interpret their missions.

Umatilla National Wildlife Refuge, located along both sides of Lake Umatilla near its upper end, is administered by the USFWS. The refuge is managed for public use; there are several developed public access points with parking, restrooms, trails, interpretive displays, small boat ramps, and waterfowl blinds. The refuge is very popular for waterfowl hunting. Other activities include, fishing, boating, hiking, and wildlife viewing.

State Wildlife Areas and Habitat Management Areas, managed by the ODFW along the mid-Columbia River include Irrigon, Willow Creek, and McNary Management Areas. WDW management areas include Klickitat and Shillapoo. Many of these lands are licensed from the Corps, which also manages specially designated lands along all three lakes for fish and wildlife purposes.

Lands along the Oregon side of the Columbia River and north of the railroad tracks from Celilo to Boardman fall within the state's Columbia River Refuge. Washington has a corollary refuge extending from Wishram to the Klickitat County line. Hunting on these lands is controlled primarily to protect nesting waterfowl. Pierce Island is owned and managed as a natural area by the Nature Conservancy.

Wild and Scenic Rivers. The purpose of Federal and Oregon and Washington state wild and scenic rivers programs is to maintain rivers in a free flowing state, maintain and protect and enhance existing scenic/recreation values, and to make these values accessible to the public. The CRGNSA Act designated a portion of the Klickitat River as a Recreation River, and a portion of the White Salmon River as a Scenic River. Other portions of these two rivers are under study as candidates for wild and scenic river designation. The Klickitat River and the Wind River are potential Washington State Wild, Scenic, or Recreation Rivers. The Oregon Scenic Waterways Act, passed by Congress in 1989, designated segments of the Sandy, Deschutes and John Day Rivers as Federal Wild and Scenic rivers.

BLM Special Management Areas. Lands under this category include Areas of Critical Environmental Concern (ACEC), Research Natural Areas (RNA), and Outstanding Natural Areas (ONA) inventoried by the BLM. ACECs are areas where special management attention is required to protect and prevent irreparable damage to important historic, cultural, or scenic values, natural resources and systems, or to protect life and provide safety from natural hazards. RNAs contain plant communities and other natural features that are preserved for scientific and educational purposes. ONAs have unusual natural characteristics and management of recreational activities is necessary to reserve those characteristics. Special Management Areas along the mid-Columbia River include the Horn Butte Curlew Area, Governor. Tom McCall Preserve at Rowena (managed by the Nature Conservancy), Botanical and Scenic Areas within the Columbia River Gorge, the Deschutes and John Day River Canyons, and the Yakima and Columbia River Islands (Lake Wallula).

National Trails. The National Trails System Act of 1968 established a system of national, recreational, scenic, and historic trails. The Pacific Crest National Scenic Trail, which transverses the United States from Mexico to Canada passes through both National Forests in the study region and crosses over the Columbia River via Bridge of the Gods at Cascade Locks. The Lewis and Clark National Historic Trail parallels the Columbia River through the study region.

2.7.10.6 Major Activities and Use Areas

Driving for Pleasure and Sightseeing. The most popular form of recreation in the region is scenic driving. Interstate Highway 84 and the old Columbia River Scenic Highway in Oregon, and Washington State 14 provide access to majestic vistas of natural features such as forests, mountains, cliffs, rivers and streams, and waterfalls. The study region has innumerable parks, rest areas, and viewpoints available to view these scenic amenities. Multnomah Falls is the most popular visitor attraction in Oregon.

Many visitors are attracted to impressive features such as Bonneville, The Dalles, John Day, and McNary dams. Each of these project areas have

- o visitor centers, fish hatcheries, fish ladders, and other facilities designed to interpret project operations and purposes for visitors. An annual average of 32.6 percent of all visitors to Corps recreation sites on the mid-Columbia River participate in sightseeing (Corps NRMS data, 1987–1993).

Many historic and prehistoric features are located along the shoreline of the Columbia River, including the Lewis and Clark Trail, evidence of the Oregon Trail and early pioneer settlement, and historic engineering features such as navigation locks and the Columbia River Highway. Petroglyphs and other artifacts provide evidence of the prehistoric importance of the region. Some of these cultural resources are inundated by the Columbia River lakes. Opportunities to view these features actually increase during low water periods. However, as access to these cultural resource sites improves, so do opportunities for illegal vandalism and artifact collection.

Fishing. Fishing is the second most popular recreational activity on the lower Columbia River lakes, contributing an annual average of 21.4 percent of visitor use to Corps recreation sites (Corps NRMS data, 1987–1993). In addition to occurring at the developed recreation sites described above, fishing takes place at numerous dispersed locations throughout the study region. The Columbia River recreational fishery for anadromous species, sturgeon, and more recently, walleye is of particular importance to management of Bonneville, The Dalles, and John Day projects. Where opportunities are unique or abundant, fishing has high seasonal impacts on local economies.

The mouths of Columbia River tributary streams, including the Deschutes, John Day, White Salmon, Little White Salmon, Wind and Klickitat Rivers, and Tanner Creek are particularly important recreational fishing sites. A number of the recreation facilities identified in Table 2–32 are located adjacent to these rivers and were provided largely to promote fishing access. The tailrace areas below Bonneville, The Dalles, John Day and McNary dams are important recreational fishery sites. Facilities have been provided by the Corps at each of these project areas to provide fishing access.

Along the entire length of the four projects are numerous small lakes separated from the main stem of the river by the railroad and highway embankments. Some of these are natural lakes and sloughs, others were formed by seepage between the railroad and highway embankments and the main stem of the river. These seep lakes fluctuate with the level of the Columbia River. Recreational fisheries, particularly warm water species such as bass, have developed in these lakes and provide important fishing opportunities, especially for local residents. At some of these lakes, including Horse Thief Lake, Drano Lake, Taylor Lake, Rock Creek Park and McNary Wildlife Park, facilities have been provided to promote fishing access. In addition, boat access is available from some of the lakes to the main stem of the river, particularly those formed at the mouths of small tributary streams. These lakes provide emergency “harbors of refuge” from high wind conditions that frequently occur along the Columbia River. The majority of these lakes remain undeveloped, however.

Windsurfing. The reason for the growth of windsurfing in the gorge is simple, the water and wind conditions are considered ideal for the sport. This activity yearly draws hundreds of thousands of participants. Tens of thousands of spectators have witnessed professional racing events. In 1990, the economic impact of windsurfing recreation to the area was estimated at 16.5 million dollars a year (Povey, 1990).

Due to climatic and geologic conditions, the wind is nearly always blowing somewhere in the gorge. In addition, the wind blows consistently in the 20 to 35 miles per hour (40 to 60 kph) range which is the best speed for windsurfing. Also, the wind generally blows from west to east, the opposite direction of the river current. Therefore, windsurfers do not have to struggle to return to beaches from where they started.

Experienced windsurfers indicate that higher flows in the river provide better, more exciting wave conditions. They prefer using the mainstem of the Columbia River while beginners and novices make use of sheltered embayments and coves. The increasing number of windsurfers on the water has resulted in one potential safety problem; conflicts

between windsurfers and commercial tugboat/barge traffic on the river.

Also, there are relatively few sites along the river that have the necessary land—base for windsurfers and spectators and there are few access points. In Oregon, popular windsurfing sites include Cascade Locks Park, Viento State Park, “The Hook” at Hood River, Hood River Marina Park, Koberg Beach State Park, Mayer State Park, Mosier, The Dalles Riverfront Park, Celilo Park, and Biggs Junction. In Washington, popular windsurfing sites include Stevenson, Home Valley Park, “Swell City,” Spring Creek Fish Hatchery, Bingen, Doug’s Beach, Horsethief Lake State Park, Avery, and Maryhill State Park.

Boating. The Oregon side of the river has more facilities to support boating use than does Washington. The majority of boating use occurs in the counties in the study region with larger urban populations. The huge boating numbers for Multnomah County reflect the population of the metropolitan Portland area. However, most of the Multnomah County boating use occurs below the mouth of the Sandy River and outside of the study region. Hood River, Wasco, and Umatilla Counties also have relatively high boating use, reflecting the populations of the cities of Hood River, The Dalles, and Umatilla, respectively.

There are approximately 60 individual boat ramps along the Columbia River and associated lakes within the subregion. These facilities range from paved, multiple lane ramps with courtesy docks and other support facilities, to minimally improved gravel launch sites. There are also approximately 75 parks and marinas within the subregion with temporary, seasonal, or year—round boat moorage facilities. Most of the communities along the Columbia River have at least one municipal boat marina to support recreational boating. Boating, along with fishing, has high seasonal impacts on local economies.

The majority of boating use within the study region, (61 percent) is associated with fishing. Waterskiing is the second most popular activity, (27 percent); high winds tend to constrain this activity. Other

boating activities, including sailing and cruising, make up the balance of boating use. Most boating use on all four lakes is highly localized; boaters launch from marinas and boat ramps in the vicinity of where they would like to fish or ski and within that particular area. However, a small amount of upriver and downriver cruising between lakes does occur. Recreational craft can pass through navigation locks in the dams free of charge. In 1989, 634 recreational craft locked through Bonneville Dam.

Swimming. Approximately 8 percent of visitors to recreational areas at the four lower Columbia River projects participate in swimming. Compared with other activities, swimming has the potential to be more seriously impacted by project operations than other water—related activities due to the constraints of developed swimming beaches.

Almost all swimming in the Columbia River occurs during the summer months of June, July and August when water and air temperatures warm. There are approximately 25 developed swimming beaches at parks along the Columbia River within this subregion. A certain percentage of swimming also occurs at dispersed or unimproved beaches.

2.7.10.7 Visitor Use

Table 2—33 summarizes estimated visitation to the four Corps projects for the years 1987 through 1993. The source for the majority of those data is the Corps’ Natural Resource Management System (NRMS). Under NRMS, visitation estimates are collected and stored for all developed recreation sites on Federal lands administered by the Corps. Where it is available, visitation data for non—Corps sites are included into the totals.

No visitation data are currently available for the dispersed, non—site specific recreational use that occurs at all of the lakes. For this reason, visitation statistics may underestimate the total use at these projects. The visitor statistics can be used, however, to identify general trends and relationships that occur at the four lakes.

As shown, the four projects combined received an average of approximately 5.56 million visitors annually over the period from 1987 to 1991. Bonneville Dam and Lake Bonneville were the most heavily used of the three. That use reflects the close proximity of Bonneville Dam to the large urban population of the Portland/Vancouver metropolitan area and the popularity of the Bonneville Dam visitor facilities; 47 percent of the average annual visitation to Lake Bonneville is for sightseeing. Likewise, the moderately large urban population of the Tri-Cities area (Richland, Kennewick, and Pasco) directly affects visitation to Lake Wallula. Lake Umatilla and Lake Celilo are less heavily used. However, visitation to both of those projects has increased steadily and dramatically from 1987 through 1993. The increase in use probably reflects a number of factors, including the increasing population of the region, increasing interest and demand for windsurfing in the Columbia River Gorge, and designation of the gorge as a National Scenic Area.

2.7.10.8 Regional Facility Needs

The Statewide Comprehensive Outdoor Recreation Plans (SCORP) for Oregon and Washington reveal a need for additional recreation resources and facilities within the lower Columbia region. For example, the Draft Background Document for the Oregon State Parks, Columbia Gorge District (1991, Oregon State Parks and Recreation Division, Master Planning Unit) states:

"The projected future demand for recreational facilities in the gorge is virtually limitless as the population grows and interest in outdoor recreation increases. All of the sources of recreation statistics for the gorge predict a very high percentage of recreational needs growth for the area. Unfortunately, resources are limited and can only support a finite level of recreation and associated facilities. As a result, supplying the needed amount of facilities to satisfy a particular demand is often difficult, if not impossible".

South of the Columbia River in Oregon all types of boating facilities are needed, including access,

ramps, transient tie-up facilities, and sewage dump stations for larger boats. Demand currently exists for additional campsites, designated trail facilities for walking, hiking, biking, and horseback riding, and for parks of all types. This demand is expected to continue through the year 2000.

North of the Columbia River in Washington the region lacks sufficient boat ramps and moorage slips, picnic sites, swimming beaches, camping areas, RV areas, and hiking trails. In addition, hunting and fishing access as well as increased opportunities for snow activities are needed. These conditions are projected to persist through the year 2000.

As noted above, windsurfing is one of the fastest growing sports in the region. Although the river and wind conditions in the Columbia River Gorge are ideal for windsurfing, only a few sites have the necessary land-based facilities for windsurfers and spectators. The Columbia Gorge Windsurfing Study, (Oregon State Parks, 1986) reported that there was only one public park in the gorge that provides adequate parking, restrooms, picnicking facilities, and areas for rigging, launching and landing the boards; and that park was often filled beyond its capacity during racing events. Some additional new facilities have been developed specifically to meet windsurfing needs. However, demand for those facilities continues to exceed supply.

Access and development of additional recreational facilities in the gorge is constrained by a number of factors. The naturally steep and rugged topography in the Columbia River Gorge limits the land base suitable for intensive use recreation sites. The highway and railroad rights-of-way on both sides of the river take up much of the developable land area or closely follow the shoreline. In many areas, those rights-of-way also prevent safe pedestrian and vehicle access to the river. In addition, there are many other conflicting uses and purposes to be considered. For example, planned expansion of Maryhill State Park in 1988 to provide facilities for windsurfing was stopped due to archeological concerns.

Table 2-32. Lower Columbia River Recreation Sites and Facilities

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
**PROJECT: MCNARY DAM/ LAKE WALLULA										
Burbank Island										
Chiawana Park and Road 54 Park	1	2				30	1			
Columbia Park	3	9				150	1	36	18	
Hat Rock State Park	1	2				180				
Hood Park	2	5				78	1	69	69	
Hover Park										
Howard Amon Park	2	4				43	1			
Leslie R. Groves Park	1	3				16				
Locust Grove Martindale						20				
Madame Doron Memorial Park	1	1				5		15		
McNary Beach Park						20				
McNary Dam	2	3				50	2			
McNary National Wildlife Refuge										
McNary Yacht Club	1	1				10				
Paco Boat Basin	1	2				5				
Peninsula Habitat Management Unit										
Sacajawea State Park	1	2				106	1			
Two Rivers Habitat Management Unit										
Two Rivers Park	2	4				3				
Walla Walla Yacht Club	1	1				5				
Warehouse Beach Rec. Area						10		20		
Warehouse Beach Sand Station Rec. Area						10		20		
Wye Park	1	2				5	1			
Yakima River Delta Wildlife Nature Area										
SUBTOTAL	20	41	0	0	0	746	8	160	87	0

Table 2-32. Lower Columbia River Recreation Facilities – CONT

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
**PROJECT: JOHN DAY DAM/LAKE UMATILLA										
Arlington Park	1	2	10	200		8				
Boardman Park	1	2				12	1	63	31	
Crow Butte State Park	1	2	10	150		20		50	50	
Irrigon Park	1	2				14	1			
LePage Park	1	2		200		23		30		
Unatilla Marina and Park	1	4	40	500				5		
Philippi Park			10	200		20		20		
Plymouth Park	1	2	3			15	1	32	32	
Quesnel Park	1	1				5		20		
Railroad Island		2				5				
Rock Creek Park	1	2				12		12		
Roosevelt Park	1	2	5	50		8		10		
Sundale Park	1	1				3				
Umatilla National Wildlife Refuge	1	1								
Nugent Park	1	1				15	1			
Willow Creek										
Alderdale Park										
SUBTOTAL	13	26	78	1300	0	160	4	242	113	
**PROJECT: THE DALLES LOCK & DAM/LAKE CELILO										
Celilo Park	1	2				36				
Hess Park						4				
Horsetheif Lake	2	2				27		25		
Maryhill Park	1	2				10	1	50	25	
Seufert Visitor Area										
Slearfish Lake		1				3				
Biggs Park										
Cliffs Area	1	1				5	1	10		
Avery Park	1	1				3				
Deschutes State Park	1	2				25		34		
Rufus	1	1				48				
SUBTOTAL	8	12	0	0	0	161	2	119	25	0

Table 2-32. Lower Columbia River Recreation Facilities – CONT

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
**PROJECT: BONNEVILLE DAM/LAKE BONNEVILLE										
Wind River Boat River	1	2	0	0	0	0	0	0	0	0
Bonneville Dam Visitor Center	0	0	0	0	0	0	0	0	0	0
Rock Creek Park	0	0	0	0	0	0	0	0	0	0
Bonneville Hatchery	0	0	0	0	0	0	0	0	0	0
Overlook Park	0	0	0	0	0	0	0	0	0	0
Bingen Boat Basin	1	3	25	300	0	12	0	0	0	0
Crates Point	0	0	0	0	0	0	0	0	0	0
Doug's Beach	0	0	0	0	0	6	0	0	0	0
Drano Lake	1	1	0	0	0	0	0	0	0	0
Hood River Boat Basin & Marina	1	3	0	0	0	0	0	0	0	0
Hood Vista Sail Park	0	0	0	0	0	0	0	0	0	0
Koberg Beach State Wayside	0	0	0	0	0	6	0	0	0	0
Mayer State Park	1	3	0	0	0	26	0	0	0	0
Memaloose State Park	0	0	0	0	0	1	1	110	43	0
Rowland Lake Boat Ramp	1	2	0	0	0	0	0	0	0	0
Spring Creek Fish Hatchery	0	0	0	0	0	0	0	0	0	0
The Dalles Boat Basin	1	3	0	900	0	0	0	0	0	0
Viento State Park	0	0	0	0	0	19	0	75	0	0
Bonneville Dam WA Shore Visitor Fac.	0	0	0	0	0	10	0	0	0	0
SUBTOTAL	7	18	25	1200	0	80	1	185	43	0
**PROJECT: COLUMBIA RIVER BELOW BONNEVILLE DAM										
Barsteads Landing	1	1	0	200	0	0	0	0	0	0
Beacon Rock State Park	1	3	0	200	0	70	0	30	0	0
Benson Park	0	0	0	0	0	105	0	0	0	0
Coverts Landing	1	1	0	0	0	0	0	0	0	0
Dalton Point	1	1	0	0	0	0	0	0	0	0
Hankens Landing	1	1	0	300	0	0	0	0	0	0
Multnomah County Park	4	2	10	120	5	100	5	200	45	8

Table 2-32. Lower Columbia River Recreation Facilities – CONT

SITE NAME	BOAT RAMPS	BOAT LAUNCH LANES	BOAT MOOR SPACES	BOAT MOOR FEET	MOOR BUOYS	PICNIC SITES	PICNIC SITES GROUP	CAMP SITES INDIV	CAMP SITES HOOKUP	CAMP SITES GROUP
Corbett Launch Ramp	1	1	0	0	0	0	0	0	0	0
Sandy River	2	1	5	30	2	40	4	100	5	5
Rooster Rock State Park	1	2	0	0	1	229	0	0	0	0
SUBTOTAL	13	13	15	850	8	544	9	230	50	13
TOTAL	60	109	143	3350	8	1688	24	936	298	13

Table 2-33. Lower Columbia River Visitation Summary, 1987-1993

MONTH	VISITOR-DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	AVG
McNARY LOCK & DAM / LAKE WALLULA								
Corps of Engineers Recreation Sites1/								
Jan	n/a	n/a	89.5	112.9	100.4	92.4	81.1	95.3
Feb	n/a	n/a	123.9	91.6	80.3	123.1	106.0	105.0
Mar	n/a	n/a	160.5	255.1	258.4	171.4	212.6	211.6
Apr	n/a	n/a	206.3	246.2	345.0	302.4	278.8	275.7
May	n/a	n/a	265.2	228.0	322.4	330.4	436.5	316.5
Jun	n/a	n/a	387.1	316.5	411.5	377.5	495.7	397.7
Jul	n/a	n/a	467.7	407.4	560.6	485.4	505.8	485.4
Aug	n/a	n/a	349.8	588.3	393.0	440.3	430.0	440.3
Sep	n/a	n/a	300.9	208.6	290.5	250.4	350.9	280.3
Oct	n/a	n/a	147.0	142.1	139.0	191.3	167.5	157.4
Nov	n/a	n/a	141.9	112.2	102.7	96.8	117.0	114.1
Dec	n/a	n/a	107.7	70.1	93.4	94.8	94.3	92.1
Project Total	n/a	n/a	2747.5	2779.0	3097.2	2956.2	3276.2	2971.2
JOHN DAY LOCK & DAM / LAKE UMATILLA								
Corps of Engineers Recreation Sites1/								
Jan	43.7	77.6	74.5	103.3	98.6	56.9	56.6	73.0
Feb	67.4	100.9	100.7	93.8	72.7	80.2	61.9	82.5
Mar	210.2	165.8	133.5	123.0	197.6	126.5	73.5	147.2
Apr	263.0	271.8	230.9	176.8	200.6	164.0	105.3	201.8
May	311.0	334.2	133.5	227.9	270.4	198.4	140.7	230.9
Jun	276.3	363.4	246.2	270.6	296.9	264.0	203.8	274.5
Jul	322.4	353.2	364.2	310.3	312.4	315.8	228.4	315.2

Table 2-33. Lower Columbia River Visitation Summary, 1987-1993 - CONT.

MONTH	VISITOR-DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	AVG
JOHN DAY LOCK & DAM / LAKE UMATILLA - CONT								
Corps of Engineers Recreation Sites1/ - CONT								
Aug	342.9	322.9	363.1	414.2	379.3	333.1	239.1	342.1
Sep	279.3	263.9	306.4	366.4	317.0	292.5	174.1	285.7
Oct	223.1	192.4	253.0	253.0	229.0	197.8	156.7	215.0
Nov	102.4	113.8	122.2	122.2	107.2	128.3	94.5	112.9
Dec	76.6	91.0	79.3	79.3	77.7	100.3	61.8	80.9
Corps Subtotal	2518.3	2650.9	2407.5	2540.8	2559.4	2257.8	1596.5	2361.6
Umatilla NWR 6/								
	n/a	n/a	138.0	n/a	n/a	n/a	n/a	138.0
Project Total								2499.6
THE DALLES LOCK & DAM / LAKE CELILO								
Corps of Engineers Recreation Sites1/								
Jan	13.0	35.4	74.5	103.3	98.6	27.5	21.0	53.3
Feb	27.6	51.5	100.7	93.8	72.7	49.1	30.0	60.8
Mar	60.3	86.0	133.5	123.0	197.5	43.5	37.5	97.3
Apr	125.9	106.0	230.9	176.8	200.6	67.6	73.5	140.2
May	154.9	171.7	133.5	227.9	270.2	73.8	59.9	156.0
Jun	160.1	172.6	246.2	270.6	296.9	99.1	97.5	191.9
Jul	149.0	214.3	610.6	310.3	312.4	136.6	117.2	264.3
Aug	140.1	178.3	363.1	414.2	379.3	172.3	114.6	251.7
Sep	146.2	157.7	306.4	366.4	317.0	151.5	92.7	219.7
Oct	95.4	102.4	253.0	229.5	197.8	133.7	80.3	156.0
Nov	74.1	51.2	122.2	107.2	128.3	61.9	46.1	84.4
Dec	40.6	33.7	79.3	77.7	100.3	50.5	33.0	59.3
Corps Subtotal	1187.2	1360.8	2653.9	2500.7	2571.6	1067.1	803.3	1734.9
Other Recreation Sites								
Deschutes Rec. Area 2/	121.5	135.7	130.0	141.3	130.8	135.0	111.5	
Heritage Landing /2	102.6	118.2	113.2	139.8	107.2	132.1	113.5	
Misc. Windsurf Sites 3/	n/a	n/a	23.0	21.0	n/a	n/a	10.5	
Subtotal	224.1	253.9	266.2	302.1	238.0	267.1	235.5	
Project Total	1411.3	1614.7	2920.1	2802.8	2809.6	1334.2	1038.8	

Table 2-33. Lower Columbia River Visitation Summary, 1987-1993 - CONT.

MONTH	VISITOR-DAYS (in 1,000's)							
	1993	1992	1991	1990	1989	1988	1987	AVG
BONNEVILLE LOCK & DAM / LAKE BONNEVILLE								
Corps of Engineers Recreation Sites ^{1/}								
Jan	43.3	53.2	37.7	58.2	73.9	67.6	44.8	54.1
Feb	43.8	55.7	90.8	51.1	52.3	85.5	195.7	82.1
Mar	93.8	113.0	159.2	114.1	98.0	106.3	116.4	114.4
Apr	171.7	167.2	145.3	181.8	171.0	173.6	227.9	176.9
May	279.2	231.7	253.4	304.8	255.5	263.1	259.0	263.8
Jun	441.6	427.7	311.2	507.4	420.4	306.1	266.7	383.0
Jul	557.4	435.4	453.7	558.9	483.0	403.5	371.7	466.2
Aug	457.8	366.7	657.4	597.9	631.1	405.6	740.0	550.9
Sep	308.0	278.8	331.1	359.0	457.0	355.2	303.0	341.7
Oct	248.2	175.1	173.3	210.6	195.4	195.3	237.9	205.1
Nov	141.9	78.5	100.2	105.0	99.3	99.2	161.3	112.2
Dec	63.6	54.0	50.7	76.9	52.9	52.9	106.7	65.4
Corps Subtotal	2850.3	2437.0	2764.0	3125.7	2989.8	2513.9	3031.1	2816.0
Oregon State Parks								
Viento St. Pk. 2/	198.8	192.9	163.3	136.7	135.3	123.0	143.7	
Mayer St. Pk. 2/	115.5	139.3	114.4	89.5	125.7	57.9	125.3	
State Parks Subtotal	314.3	332.2	277.7	226.2	261.0	180.9	269.0	
Other Recreation Sites								
Dalles Riverfront 3/	n/a	n/a	n/a	270.2	n/a	n/a	n/a	
Hood River Marina 4/	n/a	n/a	n/a	115.2	n/a	n/a	n/a	
Cascade Locks Park 5/	n/a	n/a	n/a	274.7	n/a	n/a	n/a	
Koberg Wayside 2/	n/a	n/a	n/a	82.2	n/a	n/a	n/a	
Spring Cr. Hatchery 7/	n/a	n/a	n/a	315.0	n/a	n/a	n/a	
Misc. Windsrf Sites 8/	n/a	n/a	n/a	49.0	n/a	n/a	25.0	
Other Sites Subtotal	n/a	n/a	n/a	1558.7	n/a	n/a	25.0	
PROJECT TOTAL	3164.6	2769.2	3041.7	4910.6	3250.8	2694.8	3325.1	
SOURCES 1/ U.S. Army Corps of Engineers, Portland District. Portland, Oregon 2/ Oregon State Parks and Recreation Department, Salem, Oregon 3/ Port of The Dalles, The Dalles, Oregon 4/ Port of Hood River, Hood River, Oregon 5/ Port of Cascade Locks, Cascade Locks, Oregon 6/ U.S. Fish and Wildlife Service, Umatilla NWR 7/ U.S. Fish and Wildlife Service, Spring Creek Hatchery, White Salmon, Washington 8/ Estimated from data presented in "Columbia River Gorge Windsurf Economics: 1990 Season" David Povey, 1990. University of Oregon, Community Planning Workshop.								

CHAPTER 3

RECREATION ANALYSIS PROCEDURES AND METHODOLOGY

3.1 INTRODUCTION

The general objectives and functions of the RWG were previously described in section 1.1. This chapter describes and documents the quantitative methods that were developed and applied to calculate recreation participation impacts for the final EIS. The primary analytical objective throughout the course of the SOR study was to identify and evaluate the potential effects of changes in system operations on recreational use patterns in the Columbia River Basin (Basin), including predicted direct, indirect, and cumulative impacts of alternatives. A secondary goal was to estimate changes in net social welfare attributable to changes in mainstream hydrosystem operations. Such effects are manifested by how outdoor recreationist's behavior, preferences, and willingness to pay change as operation of the Federal Columbia River Power System (FCRPS) varies over time.

This chapter proceeds with a brief discussion of the recreational concerns and issues that shaped the decision to develop an analytical model needed to quantify changes in recreation participation (trips) and welfare (monetary values) within the Basin in section 3.2. A generalized conceptual framework underlying recreation demand modeling is suggested in section 3.3. The methodology and analyses developed to calculate recreation impacts for the different phases of SOR leading to the final EIS are reviewed in section 3.4. Section 3.5 provides the rationale for transitioning from the modeling approach used in the draft EIS to a theoretically more rigorous recreation demand and non-market valuation model applied in the final EIS. The methodology and theoretical construct underlying the final EIS recreation demand (participation) model is summarized in section 3.6 (Appendix J-1 presents a detailed description of the methodology and theoretical construct underlying the models, including the

basinwide recreation survey upon which the models are based). Finally, a description of the reliability, limitations, and assumptions associated with the recreation visitation data that were used to calibrate the final recreation demand model is provided in section 3.7.

3.2 PUBLIC ISSUES AND CONCERNS

Throughout the SOR public scoping process, several issues were raised pertaining to the effects of FCRPS hydropower system operations on the quantity and quality of outdoor recreation opportunities at Columbia River federal and non-federal hydro projects. Readers should refer to section 1.3 for a description of site-specific public issues that were raised about recreation resources in the Basin. It was recognized that any recreation impact modeling effort needed to adequately capture and reflect these public concerns and opinions since outdoor recreation is extremely important to local economies and the quality of life throughout the Pacific Northwest. There are innumerable forms of water and land based leisure activities available at many different projects and, within a project, at many different sites. The Basin's abundant and diverse outdoor recreation opportunities continue to be used more intensively and frequently by an expanding regional population; the demand for high-quality outdoor recreation experiences is expected to continue climbing into the next century.

Most of the issues surfaced by the public concern the deleterious effect of water releases and reservoir drawdowns during peak recreation seasons. Severe reservoir drawdowns render boat launching ramps and marina facilities unusable, eliminate shore access, and can dramatically alter the natural scenery and aesthetic value of storage and run-of-river projects. Excessive or inadequate water releases from Federal hydro projects can also influence the

quality of recreation experiences in downstream river reaches by altering instream flows. Such changes in streamflow can adversely impact those river users who engage in fishing, power boating, and white-water float boating activities among others. Similarly, radical fluctuations in daily and weekly system operations can disrupt popular recreation activities that are typically not affected under normal operating conditions, such as wind surfing in the Columbia Gorge National Recreation Area or float boating in the Hells Canyon National Recreation Area.

It was clear from public commentary that any change in FCRPS operations that causes reservoir elevations and in-river flows to fluctuate severely is perceived to have a significant negative effect on the quantity and quality of recreational activities available on the Columbia River. These insights, particularly the direct relationship between recreation use and changes in hydrological conditions, were especially important information used to help formulate a conceptual framework for the recreation impact assessment models developed for the draft and final EIS.

3.3 CONCEPTUAL FRAMEWORK

Decision analysis procedures were applied and used to translate these public concerns into a conceptual framework to model the recreation and social welfare effects of alternative SOSs. Recreation demand (participation) models are conceptually needed because outdoor recreation is very popular and valuable in the region, a Basin-wide recreation demand model was previously lacking in the region, and changes in Columbia River recreation participation rates and recreational social welfare (monetary) values could not be easily quantified. A theoretically correct and properly specified recreation model statistically explains how recreation participation (and values) at the numerous projects and sites, and in activities throughout the Basin, changes under various FCRPS operating conditions. Recreation demand models estimated statistically are based on the economic theory of recreation demand and accepted non-market valuation techniques. New empirical research techniques which had not previously been attempted in the Basin were needed to

estimate and apply such a theoretical recreation demand model to the SOR.

The primary inputs into a fully-integrated recreation demand model and their conceptual linkage to recreational user behavioral responses (outputs) are presented in Figure 3-1. This diagram shows the relationship between the physical, chemical, and biological components of a hydrologic system, the different forms of recreation activities available to participants, and the resultant effects which are to be measured. The recreation model is driven by reservoir lake elevations and streamflows. Fluctuations in lake hydrology and riverine flows alter the suitability of recreational opportunities in terms of access, aesthetics, safety, and water quality. Changes in hydrologic conditions impact the productivity of biological resources at various levels of the trophic food chain extant in fluvial and lacustrine systems. The diversity and composition of fish and wildlife populations vary in abundance and distribution in direct response to such changes in biological trophic relationships. The quality and quantity of recreational experiences for such activities as fishing, boating, and camping are influenced directly by these variations in resource abundance (i.e., fishing catch rates) and system hydrologic conditions. Such effects on recreation are measured as a change in recreation participation rates, expressed as visitor or recreation days. The final measure of impacts (visitor days) can be translated into monetary terms to quantify the non-market value of various recreational activities.

3.4 ANALYTICAL SCOPE FOR DRAFT EIS

3.4.1 Model Development

Recreation pilot simulation models were developed and applied in the first phase of SOR leading up to the Draft EIS issued in 1994. The underlying methodology applied in this initial pilot model development phase is described in Columbia System Operation Review Screening Analysis: Description and Conclusions (SOR, 1992). These initial pilot models were a first-cut analytical tool used to quantitatively estimate impacts on recreation resources under various system operating strategies.

Figure 3-1. Conceptual Framework for Recreation Impact Assessment Models

Pilot models were initially constructed for a representative sample of Federal projects which were thought to best characterize the recreation effects that could be expected from altering system operations. It was not necessary to develop models for every Federal project to satisfy the requirements of pilot and screening analysis. Rather, a representative subset of projects were selected to facilitate analyses of the 91 screening alternatives that were analyzed in phase 1. This analytical scope adequately characterized the range of preliminary impacts that were expected to occur as a result of altering system operations.

Pilot recreation models were initially developed for three federal storage projects: Dworshak, Libby, and Grand Coulee. These models were based on existing visitation data sources and professional judgment of recreational professionals in the region. A fourth storage model, Hungry Horse, was adapted from a statistical contingent valuation model estimated from recreational user survey data collected on-site (Ben-Zvi 1990). These storage projects are very popular recreation areas that are geographically dispersed throughout the Basin and are considered to attract a representative sample of recreationists throughout the region. In addition, the Corps and Reclamation maintain good historical databases on recreation usage, facilities, and lake elevations at these reservoirs, another factor that influenced the decision to develop initial pilot models for these projects.

Free-flowing river stretches were not included in the initial pilot modeling efforts. Data on recreational activities on free-flowing river reaches that are or could be affected by Federal dam operations (i.e. Clearwater River below Dworshak, Kootenai River below Libby, Flathead River below Hungry Horse, and Snake River Hells Canyon National Recreation Area) were unavailable at the time pilot analysis was completed. In addition, the hydroregulation outputs for screening alternatives provided end-of-month pool elevations and flows, but not hourly or daily fluctuations in streamflows. At this time, it was felt that an end-of-month streamflow

model would not adequately characterize impacts on water-dependant river recreation activities.

The pilot recreation models were structured to simulate the effect of changes in FCRPS operations. EXCEL spreadsheet models for each sample project were constructed to estimate how variations in reservoir pool levels affect participation rates in various forms of outdoor recreation activities. These pilot models estimated participation (use) effects for the following four common recreational activities: fishing, boating, camping/picnicking, and swimming. Impacts on all forms of recreation available at these reservoirs were not estimated; therefore, the visitation numbers generated by the pilot models understate total recreation participation at these projects. These recreational activities, however, accounted for the largest percentage of visitation occurring at these four reservoirs and represented the most important component of the public's overall recreation experience. Alternatively, the Hungry Horse model that was adapted did not distinguish by activity, rather it generated an aggregate estimate of impacts across all types of recreation activities.

3.4.2 Methodological Assumptions

The methodological structure of the initial pilot models was based on a simple relationship between lake elevation and expected participation (usage) in each recreation activity. Drawdowns in lake levels are known to produce undesirable physical effects that adversely impact a user's ability to recreate at a reservoir, such as exposing mud flats, rendering boat ramps unusable, limiting shore access, and impairing overall lake aesthetics. Consequently, use (visitation) in a particular recreation activity was assumed to decline in direct response to, and correlate with, reductions in reservoir elevations. Such "break-point" relationships were established or adopted (i.e., Hungry Horse) for each recreational activity at each project. Break-points are points at which the relationship between an elevation and recreation usage are quantified. At each break-point, a percentage reduction in visitation was estimated and established at various lake elevations as they dropped from full pool. Figure 3-2, for example,

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	1290 ft.	1285.0 ft.	1280.0 ft.	1250.0 ft.	1234.0 ft.
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Low Pool	Minimum Operating Pool
General Comments	Full pool not optimum as debris lodged at high water line is refloated and becomes a problem to boaters. More sandy beaches available with minor drawdown. Optimum pool is 1288 ft.	Drawdown is five feet from full, debris is stranded at high pool, swimming beaches are impacted, natural beaches are exposed.	Drawdown 10.0 ft. is at lower end of historic summer fluctuation. Major negative impacts begin to occur.	Drawdown 40.0 ft. below full pool. All recreation facilities and marina service severely impacted.	Drawdown 56 ft. from full pool. Most water based facilities are out of service.
Boating (all types)	All boat ramps and docks are fully usable. Floating debris is a deterrent to boating Boating Use: 95%	All boat facilities available; shoreline beaches exposed. Boating Use: 100%	Three small launch ramps inoperable; all other boating facilities usable. Some minor inconvenience at launching and parking sites. Boating Use: 85%	Launch lanes are reduced by more than half. Most docks out of service. One major marina is out of business. Boating Use: 50%	Only four narrow launch ramps in service. Docks and marina services unavailable. Boating Use: 15%
Fishing (boat or shore)	Floating debris is a minor deterrent to fishing. All facilities usable. Fishing Use: 95%	Minimum debris on water surface; shoreline easily accessible; all facilities available. Fishing Use: 100%	Lake access is impacted for shore and boat anglers. Fishing Use: 85%	Water access severely hampered for boat and shore anglers. Resident fish stocks diminished. Fishing Use: 50%	Lake access very difficult. Negative impacts on resident fish populations. Marinas are inoperable. Fishing Use: 10%
Camping/Picnicking	All water-related recreation facilities are fully usable. Some minor detriment due to floating debris and not as many sandy beaches. Camping/Picnicking Use: 100%	All facilities operable; lakeshore easily accessible from camping and day use areas. Camping/Picnicking Use: 100%	Water surface is farther away from developed camping and picnicking areas. Negative effect on aesthetics. Camping/Picnicking Use: 90%	Water surface long distance from camping and picnic facilities. Aesthetics adversely affected by large drawdown band. Camping/Picnicking Use: 60%	Long distance from camping and day use facilities to lake. No developed swim areas in service. Poor aesthetic quality. Few boating facilities. Camping/Picnicking Use: 50%
Swimming	All designated swimming areas fully usable. Swimming Use: 90%	Some swim hazards at developed swim areas. Shallow water under swim floats hazardous to divers. Swim areas within boom floats diminished. Swimming Use: 75%	Designated swimming areas are greatly diminished in size; swim platforms unusable. Long distance from turf and shaded areas to water surface. Swimming Use: 25%	All developed swimming areas are exposed and essentially unusable. Swimming Use: 0%	All developed swim areas are unusable and high and dry. Swimming Use: 0%

Figure 3-2. Grand Coulee/Lake Roosevelt Break Points

shows that at Grand Coulee a drawdown of 5 feet is assumed to reduce participation in boating activities by 5 percent from historical visitation levels. Similarly, a 10-foot drawdown is assumed to reduce boating usage by 15 percent. The activity break-points were quantified in this way for all of the projects.

In general, the physical break-points were estimated based on the best professional judgment and knowledge of RWG members, resource managers, and recreation planners familiar with the project areas. The assumptions, justification, rationale, and data used to develop recreation activity break-point relationships for these four project areas are documented in the Screening Analysis (SOR, 1992).

Such break point relationships were translated into linear curves, where the percent reduction in visitation is a function of variable lake levels as they progressively decline from full (SOR, 1992, 1994). This basic methodological structure of the pilot models was also applied to estimate recreation impacts for the draft EIS. The pilot models measured effects on recreation activities by estimating from these break-point curves gains or losses in recreation visitation or participation rates, expressed in visitor days (or hours), in response to changes in end-of-month lake elevations. Monthly lake elevations were based on outputs generated by SOR hydrological simulation models. The total annual impact on recreation usage by project was computed as the sum of the monthly changes in visitation for each recreational activity.

3.4.3 Sensitivity and Probability Analysis

Sensitivity analysis was carried out to explain which variables impact the value measure (i.e., total visitor hours, or days, at each reservoir) most significantly. Each parameter in the model was varied around a range of high and low values, and was then entered into the Decision Analysis Sensitivity software program to test the resulting change in visitation. The larger the spread or deviation in the value measure (i.e. visitor hours or days), the more sensitive the input variable is in explaining a change in visitation. These variables were ranked according to their level of importance in "tornado" diagrams that were gener-

ated by the Decision Analysis software package. An example of a tornado diagram for the Dworshak pilot model is shown in Figure 3-3. From the sensitivity analyses, the variables considered most important for modeling purposes were hydrologic conditions and break-point/activity relationship curves for each recreation activity (SOR, 1992).

Those input variables that explained the largest variation in visitation were selected for the subsequent probability analyses of alternatives evaluated in the screening phase of SOR. The Supertree software program generates a decision tree to calculate the expected value (weighted average) of all possible outcomes defined by the tree structure. Each branch of a decision tree is assigned a certain probability of occurrence in order to execute the probability analysis (SOR, 1992). An example of a Supertree probability analysis performed on the Dworshak pilot model is provided in Figure 3-4. The output is: 1) a cumulative probability distribution that plots the likelihood that participation will be less than or equal to a certain number of visitor hours (days) for three alternatives evaluated simultaneously, and 2) the expected value of recreation visitation at the project. From the Dworshak probability distribution, it can be concluded, for example, that the FLOW alternative analyzed in this instance affects visitation much more significantly than the STORAGE and BASE alternatives. That is, for every probability level, the expected value of visitation is much higher under BASE and STORAGE than under the FLOW alternative.

3.4.4 Screening Analysis

The four recreation models developed during the pilot phase were executed to analyze 91 hydrological alternatives evaluated during the SOR screening phase. Each pilot model was structured to capture the effect of uncertainty in break-point relationships (i.e. changes in use given variable water conditions) and the variability in hydrological conditions using the Supertree software. The uncertainty in break-point relationships was reflected by establishing a "high" and "low" range of values around the original break-points which establish a point estimate for percentage of visitation at a particular lake

Figure 3-3. Example of Recreation Sensitivity Analysis and "Tornado" Diagram at Dworshak Reservoir under a Base Case Scenario

Figure 3-4. Example of Probability Analysis applied to Recreation Pilot Model

elevation. High, mid-range, and low activity break-points curves were assigned a probability of 5 percent, 95 percent, and 5 percent, respectively, to conduct the probability analyses.

The primary output of each Supertree probability run was the expected value of recreation—hours or days, summed across all four recreation activities, for each of four reservoir projects — Dworshak, Libby, Grand Coulee, and Hungry Horse. The expected value of recreation—hours or days was ranked against two base cases to compare the effects of the alternatives evaluated in screening. The recreational impacts for 91 screening alternatives are provided in Screening Analysis (SOR, 1992).

3.4.5 Full-scale Analyses for Draft EIS

The recreation pilot models developed for screening were considered to be preliminary analytical tools

and were not specified to explain with statistical confidence changes in recreational demand and value as a function of system hydrological conditions. The pilot modeling approach was, however, a constructive first-step attempt at developing an analytical tool needed to estimate Basin-wide recreation impacts. By incorporating uncertainty in parameter estimates, the pilot models were capable of generating reliable measures of gains or losses in recreation use under varying hydrological conditions. At the time the draft EIS was completed, the pilot model was considered to be the best tool available to analyze the quantitative effects of alternative SOSs on Basin recreational resources. Consequently, the methodological approach developed in screening was also applied to conduct full-scale analysis for the draft EIS.

Full-scale analyses focused on all 14 Federal projects being evaluated under SOR (see section 1.4.1.). Recreation impact assessment models (IAM) were

developed for each Federal project inextricably linked to the operation of the FCRPS. In addition, IAMs were constructed for three free-flowing river reaches that are affected by changes in Federal system operations. These include: 1) the Clearwater River below Dworshak Dam, 2) Kootenai River below Libby Dam, and 3) the Columbia River in Canada, below Keenleyside and Brilliant dams to the international boundary.

The Streamflow IAMs were developed, despite the limitations imposed by the availability of average monthly streamflows, to serve as a proxy for the range of impacts that could be expected to occur on free-flowing reaches of the Columbia River. Because of severe data limitations, quantitative models were not developed to estimate indirect effects on non-Federal project areas (e.g. mid-Columbia Public Utility District dams) and other nationally renowned or important free-flowing river recreation areas on the Snake River and tributaries to the Columbia River, such as Hells Canyon National Recreation Area and the Flathead River below Hungry Horse Dam.

Quantitative analyses were complemented with an extensive qualitative evaluation of the direct and indirect effects of each SOS. The results of the full-scale IAMs, combined with professional knowledge of the characteristics of project areas, sites, and recreational attributes, were used to quantitatively and qualitatively estimate effects on Basin recreation participation and quality. Technical Exhibit C describes the detailed modeling methodology used to conduct pilot and full-scale analyses for the draft EIS.

The full-scale IAMs were designed to estimate use by recreational activity for each of 14 Federal storage and run-of-river projects. As in pilot analysis, the primary recreational activities that accounted for the majority of the recreation use occurring on an annual basis were incorporated into each IAM model. For all storage and run-of-river projects, four activities were modeled: boating, fishing, swimming, and camping/picnicking. A fifth recreation activity, windsurfing, was also included in the models developed for the Bonneville and The Dalles proj-

ects, since it is an extremely popular activity in the Columbia River Gorge National Recreation Area.

The full-scale IAM generated an estimate of recreation participation (visitation) rates, measured in recreation days, for the most important water-dependent recreational activities available in each project area. Recreation days, instead of recreation-hours, was selected as the primary value measure for calculating effects because it was the value measure used to monetize the value of public outdoor recreation in the Basin. From information gained during the pilot phase, the full-scale models were executed using variables for hydrology, including the 50-year streamflow record, and break-point/activity curves developed for each recreation activity. The Super-tree software program was used to produce the final value measure, the expected value of recreation days, in order to evaluate the effects of alternative SOS's in the draft EIS.

3.5 TRANSITION FROM DRAFT TO FINAL EIS MODEL

The RWG convened a workshop in February 1991 to allow scientists to review and critique the recreation pilot modeling concept that was developed for screening and which was ultimately carried forward to conduct full-scale analysis for the draft EIS. The conclusions of this workshop helped guide, shape, and design the research program which was undertaken to expand upon and enhance the initial IAM capability. The most important conclusion of the workshop was that the validity of the break-point curves was questioned because evidence of users actual response to changes in lake elevations and streamflows was absent. Although the lake elevation (streamflow)/activity relationships may approximate reality, for the most part they are not based upon empirical user behavioral response (demand) curves. Other important limitations of the draft EIS modeling approach were: (1) it did not correlate visitation to fishing and hunting success as it may be influenced by the effects of alternative SOSs on fish and wildlife populations; and (2) it did not address shifts in participation across substitutes in the region under the alternative SOSs.

To remedy these concerns, the RWG determined that recreation user surveys should be conducted at a number of Federal projects to enhance the predictability and credibility of the SOR recreation IAMs applied in the draft EIS. To this end, a comprehensive study plan was developed to improve upon the draft EIS analytical tools and to accomplish the following objectives for the final EIS : 1) implement visitor use surveys throughout the Columbia River Basin; 2) apply a Contingent Valuation Method (CVM) to elicit the public's participation and economic valuation response to changes in lake elevations and/or streamflows; 3) estimate contingent valuation and participation user responses to alternative hydrologic conditions; and 4) develop a simulation model that will statistically predict changes in recreation demand and social welfare values under various hydrological (pool levels and streamflow rates), substitution, resource quality, and social, demographic, and economic conditions in the Basin.

The first phase of this long-term research plan was implemented by conducting an initial (phase I) recreation survey in the Basin during April 1993, as described in section 2.4. The survey was designed to obtain basic information about the patterns of water-related recreation use in the region (RCG/Hagler Bailly, Inc. 1993). The RCG (1993) phase I survey also recommended that specific empirical modeling approaches, the CVM and contingent behavior elicitation format, be implemented to provide defensible estimates of economic value and changes in visitation rates (demand) as pool elevations or flow rates vary at the projects under study and elsewhere in the Basin. In addition, the phase I survey information was used to develop sampling strategies in order to conduct a comprehensive regional CVM survey of recreation users in phase II of the research plan.

Following the phase I survey, several focus group meetings were convened in September 1993 to begin to test the feasibility of conducting a Basinwide CVM/contingent behavior survey of recreational users and to design the phase II sampling plan.

Focus group participants were provided with several examples of potential survey questions to determine whether or not the contingent behavior and CVM elicitation questions were understandable and free of bias problems that can occur in traditional CVM surveys. The responses generated by the focus group participants were evaluated to determine whether unbiased contingent behavior and valuation responses could be provided by respondents. Based on the outcome of these focus group discussions, and further pre-testing of the survey instrument in October 1993, it was concluded that the CVM/contingent behavior approach should not be administered as originally planned. A revised approach, the Travel Cost/Contingent Behavior (TC/CB) survey format, was instead adopted to model Columbia River Basin recreation in phase II of the research (see Appendix j-1, Chapter 3).

The Phase II survey of Columbia River Basin recreationists was carried out in fall 1993 and designed to provide data parameters needed for the TC/CB modeling task. The TC/CB statistical estimation tasks and development of a basin-wide simulation demand model were subsequently completed and incorporated into the final EIS. The associated simulation modeling results were used to predict changes in recreation participation for the final set of SOSs and replace the quantitative estimates provided in the draft EIS. In particular, the recreation model was designed to meet the RWG's fundamental objectives to: 1) predict how frequently individuals take trips to each of several Federal projects under existing and hypothetical water levels or streamflows as manifested by each SOS, and 2) predict recreation values for these trips, and subsequently predict changes in those values as water levels or streamflows at the projects change. Chapter 4 of this appendix presents the quantitative estimates of changes in trip taking behavior resulting from changes in FCRPS operating alternatives (SOSs). The monetized non-market values of these changes in visitation to Federal hydro projects are presented in Appendix O (Economic and Social Impacts).

3.6 FINAL EIS RECREATION DEMAND MODEL

3.6.1 General Theory

This section briefly outlines the important theoretical features of the TC/CB modeling approach developed for the final EIS. The specific details of the phase II research effort, including survey design, data collection, theoretical construct, empirical issues, econometric estimating procedures and simulation model development are presented in Appendix J-1.

TC can be used, along with a contingent behavior participation model, to estimate the effects of changes in pool elevations and flow rates at recreation sites for Federal projects on individual economic value and participation. As stated in the economics literature, the CVM/CB technique was developed in recent years to measure users willingness-to-pay (WTP) for an improvement in, or prevent the further loss of, the quality of natural resource commodities that do not have established market prices. It is, along with the TC and Hedonic methods, a tool for estimating the non-market value and demand for such natural resources as fish, wildlife, recreation, water quality and air quality.

The TC/CB method is used in the final EIS to estimate the effects of changes in, for example, reservoir operating policies for Federal hydro projects in the Basin on recreational participation at these projects and on the monetary benefits derived by the users of these sites. TC/CB modeling requires both actual behavioral data on individual recreation trips and behavioral responses to hypothetical changes in a system operations, such as changed pool elevations or streamflows outside the range experienced by individuals recreating at Federal projects. The TC/CB approach generates demand models of recreation trips. The benefits of a change in an operating policy to, for example, increase water levels at one or more Federal projects may be estimated from the TC/CB demand functions.

The TC/CB model predicts the destinations and frequency of water-based recreation trips taken by an individual to both Federal projects and other substitute sites as a function of travel costs incurred,

social and economic characteristics of an individual, and the qualitative characteristics of the recreation site. A TC model that fails to include substitute sites typically results in biased estimates of the benefits of recreation, unless there are no good substitutes for the recreation sites being considered. Data on the number of trips that an individual takes to the waters in his/her region were collected using the phase II mail survey questionnaire. Four regions in the Northwest were defined based on existing origin-destination data collected at the Federal projects. The generalized version of the TC demand equation can be written as:

$$(5) \quad (5) \quad Q_{ij} = f(P_{ij}, Z, S_i, W_j, W_k)$$

where,

- Q = number of trips by an individual i to project j ,
- P = a vector of the implicit prices of the trips from an individual's origin i to various destinations j ,
- Z = a vector of other time-varying variables,
- S = a vector of individual social, economic and demographic characteristics,
- W = the water level for the own project j ,
- W_k = a vector of alternative water levels k that may affect demand for own project j ,
- i = 1, . . . , I an index denoting the individual to whom the equation applies,
- j = 1, . . . , J an index denoting the project for which projections will be made using the equation

3.6.2 Actual Behavior Model

The TC demand model whose parameters are to be estimated is a model of an individual's actual recreation trip-taking behavior. The unit of measurement is a recreation "trip." A recreation trip is defined as the activity of leaving from home, for any length of time, for the primary purpose of engaging in recreation. That is, an individual visiting the local creek for 2 hours or traveling to a distant lake 100 miles away from their residence is taking only 1 trip irrespective of time and distance to the site.

The phase II recreation survey collected data on the individual's actual trips taken to Federal projects

during the 1993 water-based recreation season. Recreators were asked whether they have taken any water-based recreation trips to waters, including lakes and rivers, in the Basin both in and outside their region. Survey respondents are also asked several questions to determine the costs to the individual of a typical trip to one of the projects. This cost information is used to construct "implicit prices" for trips, which can be viewed in the same way as market prices for goods: as recreation prices increase, individuals switch to closer sites, or take fewer trips.

An individual's demand for a particular water, project, or recreation site also is a function of the characteristics of that water. Qualitative site characteristics have long been used to help explain the demand for a recreation site (Greig, 1983; Morey, 1981). Many characteristics such as surface acreage, flow rates, water levels, fish catch rates, type of bank vegetation, and availability of boat ramps have been shown to be important variables that explain or influence recreation demand, but this importance varies according to the user's type of recreation. Finally, the demand for trips is influenced by various social, demographic and economic characteristics, such as age, sex, marital status, and income. The exact set of variables included in the above vectors may vary from project demand equation to equation and the rationale for their development are discussed at length in Appendix J-1. TC recreation demand models for water-based recreation in the Pacific Northwest were estimated using the trip, characteristics (for sites and individuals), and cost data for each individual in the phase II survey sample. The parameters of the travel cost recreation model were estimated by carefully considering very complex mathematical, econometric, and statistical estimating procedures using a sample of cross-sectional data such as collected in the phase II survey.

3.6.3 Contingent Behavior Model

The parameters of the TC model may also be estimated using information about "contingent" trips. These "contingent behavior" responses are the stated number of trips that a recreator says s/he will take under a hypothetical set of changes in system

operations. Contingent behavior responses are needed to explain behavior in response to conditions outside the bounds of conditions that correspond to actual ones. That is, several of the SOSs under consideration in the SOR have not been experienced by recreators in the Basin. Models of actual behavior may not do a particularly good job of explaining and predicting recreation trips and value under widely different conditions than the ones actually experienced.

Contingent behavior modeling applications to recreation demand are growing rapidly, and the concept is well-grounded in economic theory (Cameron 1990; Englin and Cameron 1993). The approach used in the phase II survey depicted hypothetical conditions through computer enhanced photographs of two different water levels (at reservoirs) or flow rates (streams and rivers) at three to four projects in the region. The two different water levels/flow rates reflected conditions for the summer of 1993 and for a hypothetical period, with a lower or higher water level/flow rate. Each respondent looked at these pictures and was asked how many more or fewer trips s/he would have taken to the different projects if the water levels had changed to those depicted in the photographs representing hypothetical conditions.

Contingent behavior responses were tested to be sure that they are consistent with logic and the economic theory that explains recreation participation and site allocation. For example, if an angler states that s/he will take 14 more trips per year if water levels double at a close site, it is necessary to test to see whether this number of new trips is highly improbable given his or her preferences, as revealed from actual behavior. Income constrains individuals from taking more trips than they can afford, and preferences that illustrate that the angler wants variety in species and across waters will limit the number of trips to the same water that we expect to observe.

3.6.4 Predicting Future Demand

Once the parameters for the TC model shown in equation 5 are estimated, it can be used to predict trip-taking behavior under a wide variety of scenarios. Scenarios, represented by each SOS, will vary

primarily according to changes in site characteristics, including water elevations and flow rates. Trips to specific sites are estimated for each individual in the sample, first, under base conditions. Next, the site characteristics are altered to fit a specific scenario and the model is used to predict the change in the number of trips to each site. The difference in the number of trips and the distribution of trips to destinations reflects the impact of the scenario on recreation participation and is expressed in terms of total recreation days expended at a particular project. This process is repeated for every individual in the sample and these results are then "blown up" or extrapolated to the population as a whole, using population weights. Changes in the size and socioeconomic characteristics of the population over time can also be taken into account by systematically changing the values of individual characteristics variables in the model. The simulated results of each SOS and the associated estimates of recreation days spent at each Federal project are presented in Chapter 4 of this appendix.

3.6.5 Estimating Recreation Values

Changes in the welfare of recreators are defined in terms of an individual's maximum willingness to pay (WTP) to prevent conditions from becoming worse. The difference between an individual's maximum WTP and the amount s/he actually has to pay for a change in conditions is known as consumer's surplus and is the economist's preferred measure of net benefits. Recreation TC demand models reveal the consumer's surplus without asking the individual any direct question about his or her WTP (See Technical Appendix O, Economics and Social Impacts, for a more complete discussion). Put simply, the consumer surplus measure is derived from the travel cost demand equation by mathematical integration over the change in conditions.

Without the contingent behavior questions discussed above, the recreation TC demand model estimated for the final EIS will reveal the total consumers surplus for recreation in the Basin. By combining contingent behavior responses the impacts of water elevations and flows to changes or consumer surplus could be estimated. Using this approach along with

actual behavioral responses, the net benefits from preventing water level decreases at any of the Federal projects can be estimated. The associated consumer surplus estimates of value by SOS are presented in Appendix O (Economics and Social Impacts).

3.7 DATA SOURCES AND ASSUMPTIONS

The draft EIS IAM and final EIS recreation demand model estimate gains or losses in recreation visitation rates, expressed as recreation or visitor days, under each SOS. The accuracy of these effects depends, of course, upon the quality of the recreation data that are integrated into the models. Seven years of monthly visitation data for each project, collected from 1987–1993, was the primary input used in the draft recreation demand models. The data were supplied by federal, state, and local agencies with primary recreation management responsibility at the respective projects. The primary source of data for the impact assessment models used for the final report was the recreational user survey performed in 1993. Historic visitation data from 1992 and 1993 was used to aggregate and calibrate the final models.

3.7.1 Corps of Engineers

The primary source of visitation data for Federal projects administered by the Corps is the Natural Resource Management System (NRMS) database maintained by the Corps District offices. Corps visitation data supplied to NRMS is usually collected through a combination of actual vehicle count and visitor surveys. The NRMS database supplied annual recreation visitation data over the last five complete years of record (1987–1993) for each Corps project. Average annual visitation was computed for each project using NRMS records. For sites where less than five years of record are available, the most recent year(s) of data was used as a proxy for average annual use.

NRMS data were also used to determine the percent of total visitation by specific recreation activity and the percent of activity participation by month for each project area, referred to as load factors in the NRMS. The NRMS maintains this information for nine sets of unique activities: camping, picnicking, boating, fishing, hunting, sightseeing, waterskiing, swimming and other activities.

The NRMS visitor data for the most part includes water dependent and water-related recreation activities at developed sites. It also may include some "dispersed use" which is an additive number used to account for those visitors who gain access to Corps projects outside developed recreation areas and are not included in traditional visitation counting methods.

The term "visitor" as used in this analysis is equal to the term "visit." A visitor means the entry of one person into a recreation area or site to carry on one or more recreation activities. Average annual visitor days by activity were determined by multiplying the average percent of total participation by activity times average days per visit by activity. The total equals average annual visitor days of recreation use at the project area.

3.7.1.1 Libby Reservoir/Kootenai River

NRMS data includes only the small portion of the recreation facilities that are located on administrative lands at Libby and lands immediately downstream also under Corps jurisdiction. This includes the downstream segments of the Kootenai River. The NRMS data are based on a visitor survey that was conducted in 1985. A weighting factor was derived from the survey results to establish final visitation figures. In addition to NRMS data sources, two years of visitation data were also available for the Canadian parks on the north half of the reservoir.

Visitation data does not include the six major parks that are administered by the USFS. The data collected by the USFS was not reliable enough to be accurately used in the evaluation. Visitors to the three private resort/marinas on the reservoir are likewise not included. Therefore, the Corps' visitation data supplied for full-scale modeling purpose under estimates the total number of visitors that historically come to the reservoir.

3.7.1.2 Albeni Falls Dam/Lake Pend Oreille

NRMS includes all of the recreation facilities that are located on the lake and lands that are administered by the Corps. This also includes land adminis-

tered by Idaho Department of Fish and Game under lease from the Corps. The last visitor survey was conducted in 1985, and from the results, a weighting factor was determined to establish final visitation figures.

At least one year of data were available for the six USFS sites, for Sandpoint City Beach, and for Farragut State Park. Visitation to private facilities is not normally collected and is not included in the visitation figures. There are nine private lakefront resorts, local hotels and motels, and 2,289 lakefront parcels (Bonners County County Tax Office, 1991) that surround the lake. Consequently, the visitation numbers used in full-scale modeling will underestimate the total visitation that occurs at the lake.

3.7.1.3 Chief Joesph Dam/Rufus Woods Lake

NRMS includes all of the recreation facilities that are located on the lake and administrative lands that are under Corps jurisdiction. This also includes park lands administered by Washington State Parks under lease from the Corps. The last time that a visitor survey was conducted was in 1990, and from the results, a weighting factor was determined to establish final visitation figures.

3.7.1.4 Dworshak Reservoir

The visitation data for Dworshak Reservoir on the Middle Fork of the Clearwater River includes water-dependent and water-related recreation activities. Only visitation to developed recreation sites with direct access to the shoreline are included in the database. The NRMS data base includes all of the recreation facilities and sites operated by the Corps of Engineers and Idaho State Parks on Dworshak.

NRMS visitation data for 1987 was incomplete, with visitation available in "visitor hours," but not in "visitors." To convert data to the appropriate unit of measure for 1987 the ratio of visitors to visitor hours for a known month and year were calculated. The resulting multiplier was then applied to the available 1987 visitor hours for the same month. The result of this calculation is the estimated 1987 visitors (recreation days).

3.7.1.5 Lower Snake River and McNary Projects

The visitation data for lakes on the lower Snake River (Lake Sacajawea, Lake West, Lake Bryan, and Lower Granite Lake) and Lake Wallula (McNary project) on the Columbia River include water-dependent and water-related recreation activities. Only visitation to developed recreation sites with direct access to the shoreline are included in the database. The NRMS database includes all of the recreation facilities and sites operated by the Corps, Washington State Parks, and local government agencies on the lower Snake River and that portion of the Columbia River included in Lake Wallula.

In four cases the visitation data was incomplete or unavailable for several or all months of particular years, and it was necessary to use two different methods to create data that serves as a proxy for visitation in the missing periods. For Lake Wallula, the July and August 1988 estimated visitation was estimated by averaging the available four years of monthly data to fill in those two missing months. July through December 1988 visitation for Lake Bryan and Lower Granite Lake, and July through December 1988 and all of 1987 at Lake West; was incomplete; visitation was available in "visitor hours," but not in "visitors." To convert data to the appropriate unit of measure for these areas, the ratio of visitors to visitor hours for a known month and year were calculated. The resulting multiplier was then applied to the available visitor hours for the same month. The result of this calculation is the estimated visitors for the missing months.

3.7.1.6 Lower Columbia River Projects

John Day Dam/Lake Umatilla. Only developed recreation sites with direct access to the river are included in the NRMS database. Other upland recreation sites near the river but without direct access to it have been excluded.

Supplemental data were obtained for Umatilla National Wildlife Refuge, administered by the U.S. Fish and Wildlife Service. The Corps' NRMS data

also includes some "general reservoir" visitor use that occurs at undeveloped recreation sites on Lake Umatilla. There do not appear to be any significant gaps in visitor use for the project area.

The Dalles Dam/Lake Celilo. The visitor data for Lake Celilo includes water-dependent and water-related recreation activities. Only those developed recreation sites with direct access to the river are included in the database. Numerous other upland recreation sites in the Columbia River Gorge National Scenic Area without direct access to the river have been excluded.

NRMS includes all of the recreation facilities that are located on The Dalles Lock and Dam Project lands that are administered by the Corps and by Washington State Parks (under lease from the Corps). Supplemental data were obtained for recreation sites administered by Oregon State Parks, the only other recreation management agency on Lake Celilo. The Corps NRMS data also includes some "reservoir general" visitor use occurring at undeveloped recreation sites on Lake Celilo.

Because of the importance of windsurfing in the Columbia River Gorge, use of undeveloped but heavily used windsurf sites was estimated from data collected in a 1990 study on the economic importance of windsurfing in the Columbia River Gorge (Povey, 1990). Of the 231,600 estimated windsurfing visits in 1990, approximately 30 percent of the use occurred in the three sub-areas of The Dalles project area (the remaining 70 percent was on Lake Bonneville). Of that, an estimated 70 percent occurred at developed recreation sites for which visitor data is collected. The estimated remaining 30 percent occurred at undeveloped sites for which no specific data is kept (i.e., Rufus, Biggs).

At least one year of visitor data was available for almost all of the developed recreation sites on Lake Celilo; there do not appear to be any significant gaps in visitor use for the project area. No recent visitor use surveys have been completed for The Dalles project. Therefore, average days per visit for the project are based on national averages at Corps projects.

Bonneville Dam/Lake Bonneville. The NRMS visitor data excludes numerous other upland recreation sites in the Columbia River Gorge National Scenic Area without direct access to this section of the river. NRMS includes all of the recreation facilities that are located on Bonneville Lock and Dam Project lands that are administered by the Corps. Supplemental data was obtained for recreation sites administered by other agencies, including the U.S. Fish and Wildlife Service, Oregon State Parks, and several local port districts. The NRMS data also includes some "general reservoir" visitor use occurring at undeveloped recreation sites on Lake Bonneville.

Windsurfing recreation data were estimated from Povey (1990). Of the 231,600 estimated windsurfing visits in 1990, approximately 70 percent of the use occurred in the three sub-areas of the Bonneville Project area (the remaining 30 percent was on Lake Celilo). Of that, an estimated 70 percent occurred at developed recreation sites for which visitor data is collected. The estimated remaining 30 percent occurred at undeveloped sites for which no specific data is kept (i.e., Bob's Beach, Stevenson, Swell City, Mosier, and Doug's Beach). Average percent of total use for windsurfing was based on a comparison of total project visitation with windsurfing visitation presented in Povey (1990). Average use per visit for windsurfing was a professional estimate of 3.4 hours.

3.7.2 Bureau of Reclamation/National Park Service/U.S. Forest Service

3.7.2.1 Hungry Horse Dam/Reservoir

Reclamation supplied monthly visitation data from 1987 to 1993. These recreation use data are collected by the USFS, Hungry Horse Ranger Station, and are based on campground receipts and recreation use observations at the location. Due to staff limitations and the size of the district, the recreation use data are not extremely accurate. Moreover, recreation data are not collected by activity.

3.7.2.2 Grand Coulee Dam/Lake Roosevelt

The National Park Service (NPS) at Coulee Dam National Recreation Area collects most visitor data using traffic counters. The counters are located on park roads that receive little or no local use that is unrelated to recreation visits. Traffic counts are reduced by the number of vehicle trips attributable to employees of the concessionaires and the NPS. The NPS uses a multiplier of average number of vehicle occupants to determine the number of visitors to the park. In addition to traffic counts, the concessionaires provide accurate counts of houseboat rentals, which includes the total number of people in each party.

The NPS also makes actual counts of the numbers of boat trailers at launch ramps, which translates into a reasonably accurate figure for total numbers of boat launches. Camping figures are acquired by actual count of the numbers of tents and recreational vehicles at the campgrounds. All figures are collected and tallied on a monthly basis.

Figures given for the portions of Lake Roosevelt within the two Indian reservations are estimates made by the recreation staff of the Spokane and Colville Confederated Tribes. These estimates are the best figures available. These figures account for a small percentage of the total recreation use at Lake Roosevelt.

3.7.3 Mid Columbia Public Utility District River Projects

The main source of visitation data for mid-Columbia PUD projects is a combination of data collected by Washington State Parks and the data collected by the PUDs. The data includes all of the recreation facilities that are located on the lakes and lands that are administered by either the State of Washington or the PUDs. This also includes land administered by Washington Department of Fish and Game.

Average annual visitation was obtained over the last five complete years of record (1987–1991). Visitation is based on actual vehicle counts. At least one year of visitor data was available for the PUD sites, and for the Washington State Parks sites. For the

sites where less than five years of record was available, the most recent year of data was used as a proxy for average annual use.

3.7.4 Clearwater River Below Dworshak Dam

The visitation data for the Clearwater River from below the Orofino bridge to the upper end of Lower Granite Lake includes water-dependent and water-related recreation activities. The source of base-line visitation data for the Clearwater River is a Clearwater River Recreation Study (Krumpe, 1987), covering the period September 1986 through August 1987. Therefore, one year of data is being used as a proxy for historical average use. Although it is considered by some to be dated, the (Krumpe, 1987) study provides valid recreation use estimates for the lower Clearwater River. There is no other visitation/use data available for the Clearwater that has the degree of accuracy and validity found in this study.

The Clearwater River Recreation Study surveyed and estimated visitation on six river segments. Two of the six segments are above Orofino on the main fork of the Clearwater. These segments would not be impacted by changes in operation of Dworshak Dam, therefore visitation estimates from the upper two segments (Kooskia to river mile 59 and river mile 59 to Orofino bridge) of the Krumpe study are not included in the use estimates input to the full-scale IAM.

3.7.5 Hells Canyon National Recreation Area

The USFS, Hells Canyon National Area Field Office, maintains an historical database on recre-

ation use for floatboat and powerboat recreationists. Both commercial and private recreation use data are collected. The data provides information which reflects general trends in overall use patterns rather than an exact count of yearly river users. The figures provided in table 2.28 represent private and commercial float and powerboat use during the regulated season, which runs from about the end of May to September 15.

3.7.6 Columbia River – Hugh Keenleyside Dam to International Boundary

A seven-year time series of annual visitation data is not available for recreation use on the Canadian stretch of the Columbia River between the Keenleyside Dam and the International Boundary. Boat and shore fishing estimates were accurately collected in a creel census conducted in the 1990/91 season (British Columbia Hydro, 1991).

Annual visitation data for swimming, non-motorized boating, and sightseeing were not available. The numbers used in modeling analysis were gleaned from a 1984 recreation and tourism survey (Stephenson, 1984) in combination with the 1990/91 creel census survey data collected for the river system. The fishing data generated in the 1990/91 study was divided by the numbers for fishing generated in the Stephenson (1984) survey to estimate a percentage or ratio. The numbers for swimming, non-motorized boating and sightseeing generated by Stephenson (1984) were then multiplied by the above percentage to give estimates used in full-scale analysis.

CHAPTER 4

ALTERNATIVES AND THEIR IMPACTS

4.1 GENERAL DESCRIPTION OF ALTERNATIVES

Seven alternative System Operating Strategies (SOS) were considered in the Draft EIS. Each of the 7 SOSs contained several options, bringing the total number of alternatives considered to 21. This Final EIS also evaluates 7 operating strategies, with a total of 13 alternatives now under consideration when accounting for options. Section 4.1 of this chapter describes the 13 alternatives and provides the rationale for including these alternatives in the Final EIS. Operating elements for each alternative are summarized in Table 4-1. Later sections of this chapter describe the effects of these alternatives on recreation.

The 13 final alternatives represent the results of the third analysis and review phase completed since SOR began. In 1992, the agencies completed an initial effort, known as "Screening" which identified 90 possible alternatives. Simulated operation for each alternative was completed for five water year conditions ranging from dry to wet years, impacts to each river use area were estimated using simplified analysis techniques, and the results were compared to develop 10 "candidate SOSs." The candidate SOSs were the subject of a series of public meetings held throughout the Pacific Northwest in September 1992. After reviewing public comment on the candidate strategies, the SOR agencies further reduced the number of SOSs to seven. These seven SOSs were evaluated in more detail by performing 50-year hydroregulation model simulations and by determining river use impacts. The impact analysis was completed by the SOR workgroups. Each SOS had several options so, in total, 21 alternatives were evaluated and compared. The results were presented in the Draft EIS, published in July, 1994. As was done after Screening, broad public review and comment was sought on the Draft EIS. A series of nine public meetings were held in September and

October 1994, and a formal comment period on the Draft EIS was held open for over 4 1/2 months. Following this last process, the SOR agencies have again reviewed the list of alternatives and have selected 13 alternatives for consideration and presentation in the Final EIS.

Six options for the alternatives remain unchanged from the specific options considered in the Draft EIS. One option (SOS 4c) is a revision to a previously considered alternative, and the rest represent replacement or new alternatives. The basic categories of SOSs and the numbering convention remains the same as was used in the Draft EIS. However, because some of the alternatives have been dropped, the final SOSs are not numbered consecutively. There is one new SOS category, Settlement Discussion Alternatives, which is labeled SOS 9 (see Section 4.1.6 for discussion).

The 13 alternatives have been evaluated through the use of a computerized model known as HYDROSIM. Developed by BPA, HYDROSIM is a hydro-regulation model that simulates the coordinated operation of all projects in the Columbia River system. It is a monthly model with 14 time periods. April and August are split into two periods each because major changes can occur in streamflows in the first and second half of each of these months. The model is based on hydrologic data for a 50-year period of record from 1928 through 1978. For a given set of operating rule inputs and other project operating requirements, HYDROSIM will simulate elevations, flows, spill, storage content and power generation for each project or river control point for the 50-year period. For more detailed information, please refer to Appendix A, River Operation Simulation.

The following section describes the final alternatives and reviews the rationale for their inclusion in the Final EIS.

Table 4-1. SOS Alternative-1

Summary of SOS

SOS 1 Pre-ESA Operation	SOS 2 Current Operations	SOS 4 Stable Storage Project Operation
SOS 1 represents system operations before changes were made as a result of the ESA listing of three Snake River salmon stocks. SOS 1a represents operations from 1983 through the 1990-91 operating year, influenced by Northwest Power Act; SOS 1b represents how the system would operate without the Water Budget and related operations to benefit anadromous fish. Short-term operations would be conducted to meet power demands while satisfying nonpower requirements.	SOS 2 reflects operation of the system with interim flow improvement measures in response to the ESA salmon listings. It is consistent with the 1992-93 operations described in the Corps' 1993 Interim Columbia and Snake River Flow Improvement Measures Supplemental EIS. SOS 2c represents the operating decision made as a result of the 1993 Supplemental EIS and is the no action alternative for the SOS. Relative to SOS 1a, primary changes are additional flow augmentation in the Columbia and Snake Rivers and modified pool levels at lower Snake and John Day reservoirs during juvenile salmon migration. SOS 2d represents operations of the 1994-98 Biological Opinion issued by NMFS, with additional flow augmentation measures compared to SOS 2c.	SOS 4 would coordinate operation of storage reservoirs to benefit recreation, resident fish, wildlife, and anadromous fish, while minimizing impacts to power and flood control. Reservoirs would be managed to specific elevations on a monthly basis; they would be kept full longer, while still providing spring flows for fish and space for flood control. The goal is to minimize reservoir fluctuations while moving closer to natural flow conditions. SOS 4c attempts to accommodate anadromous fish needs by shaping mainstem flows to benefit migrations and would modify the flood control operations at Grand Coulee.

Actions by Project

	SOS 1	SOS 2	SOS 4
LIBBY	SOS 1a Normal 1983-1991 storage project operations	SOS 2c Operate on system proportional draft as in SOS 1a	SOS 4c <ul style="list-style-type: none"> • Meet specific elevation targets as indicated by Integrated Rule Curves (IRCs); IRCs are based on storage content at the end of the previous year, determination of the appropriate year within the critical period, and runoff forecasts beginning in January • IRCs seek to keep reservoir full (2,459 feet) June-Sept; minimum annual elevation ranges from 2,399 to 2,327 feet, depending on critical year determination • Meet variable sturgeon flow targets at Bonners Ferry during May 25-August 16 period; flow targets peak as high as 35 kcfs in the wettest years
	SOS 1b <ul style="list-style-type: none"> • Minimum project flow 3 kcfs • No refill targets • Summer draft limit of 5-10 feet 	SOS 2d <ul style="list-style-type: none"> • Provide flow augmentation for salmon and sturgeon when Jan. to July forecast is greater than 6.5 MAF • Meet sturgeon flows of 15, 20, and 12.5 kcfs in May, June, and July, respectively, in at least 3 out of 10 years 	

KAF = 1.234 million cubic meters

MAF = 1.234 billion cubic meters

Table 4-1. SOS Alternative-1

SOS 5 Natural River Operation	SOS 6 Fixed Drawdown	SOS 9 Settlement Discussion Alternatives	SOS PA
SOS 5 would aid juvenile salmon by increasing river velocity. The four lower Snake River projects would have new outlets installed, allowing the reservoirs to be drawn down to near the original river elevation. The "natural river" operation would be done for 4 1/2 months in SOS 5b and year-round in SOS 5c. John Day would also be operated at MOP for 4 months, and flow augmentation measures on the Columbia River portion of the basin would continue as in SOS 2c.	SOS 6 involves drawing down lower Snake River projects to fixed elevations below MOP to aid anadromous fish. SOS 6b provides for fixed drawdowns for all four lower Snake projects for 4 1/2 months; SOS 6d draws down Lower Granite only for 4 1/2 months. John Day would also be operated at MOP for 4 months, and flow augmentation measures on the Columbia River portion of the basin would continue as in SOS 2c.	SOS 9 represents operations suggested by the USFWS, NMFS, the state fisheries agencies, Native American tribes, and the Federal operating agencies during the settlement discussions in response to the <i>IDFG v. NMFS</i> court proceedings. This alternative has three options, SOSs 9a, 9b, and 9c, that represent different scenarios to provide increased river velocities for anadromous fish by establishing flow targets during migration and to carry out other actions to benefit ESA-listed species. The three options are termed the Detailed Fishery Operating Plan (9a), Adoptive Management (9b), and the Balanced Impacts Operation (9c).	SOS PA represents the operation recommended by NMFS and the USFWS Biological Opinions issued March 1, 1995. This SOS supports recovery of ESA-listed species by storing water during the fall and winter to meet spring and summer flow targets, and protects other resources by setting summer draft limits to manage negative effects, by providing flood protection, and by providing for reasonable power generation.

SOS 5	SOS 6	SOS 9	SOS PA
<p>SOS 5b</p> <p>Operate on system proportional draft as in SOS 1a</p> <p>SOS 5c</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 6b</p> <p>Operate on system proportional draft as in SOS 1a</p> <p>SOS 6d</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 9a</p> <ul style="list-style-type: none"> Operate on minimum flow up to flood control rule curves year-round, except during flow augmentation period Provide sturgeon flow releases April-Aug. to achieve up to 35 kcfs at Bonner's Ferry with appropriate ramp up and ramp down rates <p>SOS 9b</p> <ul style="list-style-type: none"> Operate on minimum flow up to flood control rule curves year-round, except during flow augmentation Provide sturgeon flow releases similar to SOS 2d Can draft to elevation 2,435 by end of July to meet flow targets <p>SOS 9c</p> <ul style="list-style-type: none"> Operate to the Integrated Rule Curves and provide sturgeon flow releases as in SOS 4c 	<p>SOS PA</p> <ul style="list-style-type: none"> Operate on minimum flow up to flood control rule curves beginning in Jan., except during flow augmentation period Strive to achieve flood control elevations in Dec. in all years and by April 15 in 75 percent of years Provide sturgeon flows of 25 kcfs 42 days in June and July Provide sufficient flows to achieve 11 kcfs flow at Bonner's Ferry for 21 days after maximum flow period Draft to meet flow targets, to a minimum end of Aug. elevation of 2,439 feet, unless deeper drafts needed to meet sturgeon flows

1 kcfs = 28 cms

1 ft = 0.3048 meter

Table 4-1. SOS Alternative-2

Actions by Project

	SOS 1	SOS 2	SOS 4
HUNGRY HORSE	SOS 1a Normal 1983-1991 storage project operations	SOS 2c Operate on system proportional draft as in SOS 1a	SOS 4c <ul style="list-style-type: none"> • Meet specific elevation targets as indicated by Integrated Rule Curves (IRCs), similar to operation for Libby • IRCs seek to keep reservoir full (3,560 feet) June-Sept.; minimum annual elevation ranges from 3,520 to 3,450 feet, depending on critical year
	SOS 1b <ul style="list-style-type: none"> • No maximum flow restriction from mid-Oct. to mid-Nov. • No draft limit; no refill target 	SOS 2d Operate on system proportional draft as in SOS 1a	

	SOS 1	SOS 2	SOS 4
ALBENI FALLS	SOS 1a Normal 1983-1991 storage project operations	SOS 2c Operate on system proportional draft as in SOS 1a	SOS 4c Elevation targets established for each month, generally 2,056 feet Oct.-March, 2,058 to 2,062.5 feet April-May, 2,062.5 feet (full) June, 2,060 feet July-Sept. (but higher if runoff high); Oct.-March draw-down to 2,051 feet every 6th year
	SOS 1b No refill target	SOS 2d Operate on system proportional draft as in SOS 1a	

KAF = 1.234 million cubic meters

MAF = 1.234 billion cubic meters

Table 4-1. SOS Alternative-2

SOS 5	SOS 6	SOS 9	SOS PA
<p>SOS 5b</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 6b</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 9a</p> <ul style="list-style-type: none"> Operate on minimum flow up to flood control rule curves year-round, except during flow augmentation period 	<p>SOS PA</p> <ul style="list-style-type: none"> Operate on minimum flow up to flood control rule curves year-round, except during flow augmentation period Strive to achieve flood control elevations by April 15 in 75 percent of the years Draft to meet flow targets, to a minimum end-of-August elevation of 3,540 feet
<p>SOS 5c</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 6d</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 9b</p> <ul style="list-style-type: none"> Operate on minimum flow up to flood control rule curves year-round, except during flow augmentation Can draft to meet flow targets, to a minimum end-of-July elevation of 3,535 feet <p>SOS 9c</p> <ul style="list-style-type: none"> Operate to the Integrated Rule Curves as in SOS 4c 	

SOS 5	SOS 6	SOS 9	SOS PA
<p>SOS 5b</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 6b</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 9a</p> <p>Operate on minimum flow up to flood control rule curves year-round, except during flow augmentation period</p>	<p>SOS PA</p> <ul style="list-style-type: none"> Operate to flood control elevations by April 15 in 90 percent of the years Operate to help meet flow targets, but do not draft below full pool through Aug.
<p>SOS 5c</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 6d</p> <p>Operate on system proportional draft as in SOS 1a</p>	<p>SOS 9b</p> <ul style="list-style-type: none"> Operate on minimum flow up to flood control rule curves year-round, except during flow augmentation period Can draft to meet target flows, to a minimum end-of-July elevation of 2,060 feet <p>SOS 9c</p> <ul style="list-style-type: none"> Elevation targets established for each month, generally no lower than 2,056 feet Dec.—April, no lower than 2,057 feet end of May, full (2,062.5 feet) June—Aug., 2,056 feet Sept.—Nov. 	

1 kcfs = 28 cms

1 ft = 0.3048 meter

Table 4-1. SOS Alternative-3

Actions by Project

	SOS 1	SOS 2	SOS 4
GRAND COULEE	SOS 1a	SOS 2c	SOS 4c
	<ul style="list-style-type: none"> • Operate to meet Water Budget target flows of 134 kcfs at Priest Rapids in May ^{1/} • Meet minimum elevation of 1,240 feet in May 	<ul style="list-style-type: none"> • Storage of water for flow augmentation from January through April • Supplemental releases (in conjunction with upstream projects) to provide up to 3 MAF additional (above Water Budget) flow augmentation in May and June, based on sliding scale for runoff forecasts • System flood control space shifted from Brownlee, Dworshak 	<ul style="list-style-type: none"> • Operate to end-of-month elevation targets, as follows: <ul style="list-style-type: none"> 1,288 Sept.-Nov 1,287 Dec. 1,270 Jan. 1,260 Feb. 1,270 Mar. 1,272 Apr. 15 1,275 Apr. 30 1,280 May 1,288 Jun.-Aug. • Meet flood control rule curves only when Jan.-June runoff forecast exceeds 68 MAF
	SOS 1b	SOS 2d	
	<ul style="list-style-type: none"> • No refill target of 1,240 feet in May • Maintain 1,285 feet June-Sept.; minimum 1,220 feet rest of year • No May-June flow target 	<ul style="list-style-type: none"> • Contribute, in conjunction with upstream storage projects, up to 4 MAF for additional flow augmentation • Operate in summer to provide flow augmentation water and meet downstream flow targets, but draft no lower than 1,280 feet 	

	SOS 1	SOS 2	SOS 4
PRIEST RAPIDS	SOS 1a	SOS 2c	SOS 4c
	<ul style="list-style-type: none"> • Meet May-June flow targets ^{1/} • Maintain minimum flows to meet Vernita Bar Agreement ^{2/} 	Operate as in SOS 1a	Operate as in SOS 1a
	SOS 1b	SOS 2d	
	<ul style="list-style-type: none"> • No May flow target • Meet Vernita Bar Agreement 	Operate as in SOS 1a	

^{1/} Flow targets are weekly averages with weekend and holiday flows no less than 80 percent of flows over previous 5 days.

^{2/} 55 kcfs during heavy load hours October 15 to November 30; minimum instantaneous flow 70 kcfs December to April

KAF = 1.234 million cubic meters

MAF = 1.234 billion cubic meters

Table 4-1. SOS Alternative-3

SOS 5	SOS 6	SOS 9	SOS PA
<p>SOS 5b</p> <p>Operate on system proportional draft and provide flow augmentation as in SOS 2c</p>	<p>SOS 6b</p> <p>Operate on system proportional draft and provide flow augmentation as in SOS 2c</p>	<p>SOS 9a</p> <ul style="list-style-type: none"> • Operate to meet flood control requirements and Vernita Bar agreement • Provide flow augmentation releases to help meet targets at The Dalles of 220-300 kcfs April 16-June 15, 200 kcfs June 16-July 31, and 160 kcfs Aug. 1-Aug.31, based on appropriate critical year determination • In above average runoff years, provide 40% of the additional runoff volume as flow augmentation 	<p>SOS PA</p> <ul style="list-style-type: none"> • Operate to achieve flood control elevations by April 15 in 85% of years • Draft to meet flow targets, down to minimum end-of-Aug. elevation of 1,280 feet • Provide flow augmentation releases to meet Columbia River flow targets at McNary of 220-260 kcfs April 20-June 30, based on runoff forecast, and 200 kcfs July-Aug.
<p>SOS 5c</p> <p>Operate on system proportional draft and provide flow augmentation as in SOS 2c</p>	<p>SOS 6a</p> <p>Operate on system proportional draft and provide flow augmentation as in SOS 2c</p>	<p>SOS 9b</p> <ul style="list-style-type: none"> • Operate on minimum flow up to flood control rule curves year-round, except during flow augmentation period • Can draft to meet flow targets, bounded by SOS 9a and 9c targets, to a minimum end-of-July elevation of 1,265 feet <p>SOS 9c</p> <ul style="list-style-type: none"> • Operate to meet McNary flow targets of 200 kcfs April 16-June 30 and 160 kcfs in July • Can draft to meet flow targets, to a minimum end-of-July elevation of 1,280 feet • Contribute up to 4 MAF for additional flow augmentation, based on sliding scale for runoff forecasts, in conjunction with other upstream projects • System flood control shifted to this project 	
SOS 5	SOS 6	SOS 9	SOS PA
<p>SOS 5b</p> <p>Operate as in SOS 1a</p>	<p>SOS 6b</p> <p>Operate as in SOS 1a</p>	<p>SOS 9a</p> <p>Operate as in SOS 1a</p>	<p>SOS PA</p> <p>Operate as in SOS 1a</p>
<p>SOS 5c</p> <p>Operate as in SOS 1a</p>	<p>SOS 6a</p> <p>Operate as in SOS 1a</p>	<p>SOS 9b</p> <p>Operate as in SOS 1a</p> <p>SOS 9c</p> <p>Operate as in SOS 1a</p>	
1 kcfs = 28 cms		1 ft = 0.3048 meter	

Table 4-1. SOS Alternative-4

Actions by Project

	SOS 1	SOS 2	SOS 4
SNAKE RIVER ABOVE BROWNLEE	SOS 1a Normal 1990-91 operations; no Water Budget flows	SOS 2c Release up to 427 KAF (190 KAF April 16-June 15; 137 KAF Aug.; 100 KAF Sept.) for flow augmentation	SOS 4c Same as SOS 1a
	SOS 1b Same as SOS 1a	SOS 2d <ul style="list-style-type: none"> • Release up to 427 KAF, as in SOS 2c • Release additional water obtained by purchase or other means and shaped per Reclamation releases and Brownlee draft requirements; simulation assumed 927 KAF available 	

	SOS 1	SOS 2	SOS 4
BROWNLEE	SOS 1a <ul style="list-style-type: none"> • Draft as needed (up to 110 KAF in May) for Water Budget, based on target flows of 85 kcfs at Lower Granite • Operate per FERC license • Provide system flood control storage space 	SOS 2c Same as SOS 1a except for additional flow augmentation as follows: <ul style="list-style-type: none"> • Draft up to 137 KAF in July, but not drafting below 2,067 feet; refill from the Snake River above Brownlee in August • Draft up to 100 KAF in Sept. • Shift system flood control to Grand Coulee • Provide 9 kcfs or less in November; fill project by end of month • Maintain November monthly average flow December through April 	SOS 4c Same as SOS 1a except slightly different flood control rule curves
	SOS 1b <ul style="list-style-type: none"> • No maximum flow restriction from mid-Oct. to mid-Nov. • No draft limit; no refill target 	SOS 2d Same as SOS 2c, plus pass additional flow augmentation releases from upstream projects	

KAF = 1.234 million cubic meters

MAF = 1.234 billion cubic meters

Table 4-1. SOS Alternative-4

SOS 5	SOS 6	SOS 9	SOS PA
SOS 5b Same as SOS 1a	SOS 6b Same as SOS 1a	SOS 9a Provide up to 1.927 MAF through Brownlee for flow augmentation, as determined by Reclamation	SOS PA Provide 427 KAF through Brownlee for flow augmentation, as determined by Reclamation
SOS 5c Same as SOS 1a	SOS 6d Same as SOS 1a	SOS 9b Provide up to 927 KAF through Brownlee as determined by Reclamation	
		SOS 9c Provide up to 927 KAF through Brownlee as determined by Reclamation	
SOS 5	SOS 6	SOS 9	SOS PA
SOS 5b Same as SOS 4c	SOS 6b Same as SOS 4c	SOS 9a <ul style="list-style-type: none"> • Draft up to 110 KAF in May, 137 KAF in July, 140 KAF in Aug., 100 KAF in Sept. for flow augmentation • Shift system flood control to Grand Coulee 	SOS PA Draft to elevation 2,069 feet in May, 2,067 feet in July, and 2,059 feet in Sept., passing inflow after May and July drafts
SOS 5c Same as SOS 4c	SOS 6d Same as SOS 4c	SOS 9b <ul style="list-style-type: none"> • Draft up to 190 KAF April-May, 137 KAF in July, 100 KAF in Sept. for flow augmentation • Shift system flood control to Grand Coulee • Provide an additional 110 KAF in May if elevation is above 2,068 feet and 110 KAF in Sept. if elevation is above 2,043.3 feet 	
		SOS 9c Same as SOS 9b	

1 kcfs = 28 cms

1 ft = 0.3048 meter

Table 4-1. SOS Alternative-5

Actions by Project

	SOS 1	SOS 2	SOS 4
DWORSHAK	SOS 1a <ul style="list-style-type: none"> • Draft up to 600 KAF in May to meet Water Budget target flows of 85 kcfs at Lower Granite • Provide system flood control storage space 	SOS 2c <p>Same as SOS 1a, plus the following supplemental releases:</p> <ul style="list-style-type: none"> • 900 KAF or more from April 16 to June 15, depending on runoff forecast at Lower Granite • Up to 470 KAF above 1.2 kcfs minimum release from June 16 to Aug. 31 • Maintain 1.2 kcfs discharge from Oct. through April, unless higher required • Shift system flood control to Grand Coulee April-July if runoff forecasts at Dworshak are 3.0 MAF or less 	SOS 4c <p>Elevation targets established for each month: 1,599 feet Sept.-Oct.; flood control rule curves Nov.-April; 1,595 feet May; 1,599 feet June-Aug.;</p>
	SOS 1b <ul style="list-style-type: none"> • Meet minimum project flows (2 kcfs, except for 1 kcfs in August); summer draft limits; maximum discharge requirement Oct. to Nov. (1.3 kcfs plus inflow) • No Water Budget releases 	SOS 2d <ul style="list-style-type: none"> • Operate on 1.2 kcfs minimum discharge up to flood control rule curve, except when providing flow augmentation (April 10 to July 31) • Provide flow augmentation of 1.0 MAF plus 1.2 kcfs minimum discharge, or 927 KAF and 1.2 kcfs, from April 10-June 20, based on runoff forecasts, to meet Lower Granite flow target of 85 kcfs • Provide 470 KAF from June 21 to July 31 to meet Lower Granite flow target of 50 kcfs • Draft to 1,520 feet after volume is expended, if Lower Granite flow target is not met; if volume is not expended, draft below 1,520 feet until volume is expended 	

KAF = 1.234 million cubic meters

MAF = 1.234 billion cubic meters

Table 4-1. SOS Alternative-5

SOS 5	SOS 6	SOS 9	SOS PA
<p>SOS 5b</p> <ul style="list-style-type: none"> • Operate to local flood control rule curve • No proportional draft for power • Shift system flood control to lower Snake projects • Provide Water Budget flow augmentation as in SOS 1a • Draft to refill lower Snake projects if natural inflow is inadequate <p>SOS 5c</p> <ul style="list-style-type: none"> • Operate to flood control during spring • Refill in June or July and maintain through August • Draft for power production during fall 	<p>SOS 6b</p> <p>Same as SOS 5b</p> <p>SOS 6d</p> <p>Same as SOS 5b</p>	<p>SOS 9a</p> <ul style="list-style-type: none"> • Remove from proportional draft for power • Operate to local flood control rule curves, with system flood control shifted to Grand Coulee • Maintain flow at 1.2 kcfs minimum discharge, except for flood control or flow augmentation discharges • Operate to meet Lower Granite flow targets (at spillway crest) of 74 kcfs April 16-June 30, 45 kcfs July, 32 kcfs August <p>SOS 9b</p> <ul style="list-style-type: none"> • Similar to SOS 9a, except operate to meet flow targets at Lower Granite ranging from 85 to 140 kcfs April 16-June 30 and 50-55 kcfs in July • Can draft to meet flow targets to a min. end-of-July elevation of 1,490 feet <p>SOS 9c</p> <ul style="list-style-type: none"> • Similar to SOS 9a, except operate to meet Lower Granite flow target (at spillway crest) of 63 kcfs April-June • Can draft to meet flow targets to a min. end-of-July elevation of 1,520 feet 	<p>SOS PA</p> <ul style="list-style-type: none"> • Operate on minimum flow-up to flood control rule curve year-round, except during flow augmentation period • Draft to meet flow targets, down to min. end-of-Aug. elevation of 1,520 feet • Sliding-scale Snake River flow targets at Lower Granite of 85 to 100 kcfs April 10-June 20 and 50 to 55 kcfs June 21-Aug. 31, based on runoff forecasts

1 kcfs = 28 cms

1 ft = 0.3048 meter

Table 4-1. SOS Alternative-6

Actions by Project

	SOS 1	SOS 2	SOS 4
LOWER SNAKE	SOS 1a	SOS 2c	SOS 4c
	<ul style="list-style-type: none"> • Normal operations at 4 lower Snake River projects (within 3 to 5 feet of full pool, daily and weekly fluctuations) • Provide maximum peaking capacity of 20 kcfs over daily average flow in May 	<ul style="list-style-type: none"> • Operate reservoirs within 1 foot above MOP from April 16 to July 31 • Same as SOS 1a for rest of year 	Same as SOS 2c
	SOS 1b	SOS 2d	
	Same as 1a, except: <ul style="list-style-type: none"> • No minimum flow limit (11,500 cfs) during fall and winter • No fish-related rate of change in flows in May 	Same as SOS 2c	

	SOS 1	SOS 2	SOS 4
LOWER COLUMBIA	SOS 1a	SOS 2c	SOS 4c
	<ul style="list-style-type: none"> • Normal operations at 4 lower Columbia projects (generally within 3 to 5 feet of full pool, daily and weekly fluctuations) • Restricted operation of Bonneville second powerhouse 	Same as SOS 1a except: lower John Day to minimum irrigation pool (approx. 262.5 feet) from April 15 to Aug. 31; operate within 1.5 feet of forebay range, unless need to raise to avoid irrigation impacts	Same as SOS 2c, except operate John Day within 2 feet of elevation 263.5 feet Nov. 1 through June 30
	SOS 1b	SOS 2d	
	Same as 1a, except no restrictions on Bonneville second powerhouse	Same as SOS 2c	

KAF = 1.234 million cubic meters

MAF = 1.234 billion cubic meters

Table 4-1. SOS Alternative-6

SOS 5	SOS 6	SOS 9	SOS PA
<p>SOS 5b</p> <ul style="list-style-type: none"> • Draft 2 feet per day starting Feb. 18 • Operate at natural river level, approx. 95 to 115 ft below full pool, April 16-Aug. 31; drawdown levels by project as follows, in feet: <ul style="list-style-type: none"> Lower Granite 623 Little Goose 524 L. Monumental 432 Ice Harbor 343 • Operate within 3 to 5 ft of full pool rest of year • Refill from natural flows and storage releases <p>SOS 5c</p> <p>Same as SOS 5b, except drawdowns are permanent once natural river levels reached; no refill</p>	<p>SOS 6b</p> <ul style="list-style-type: none"> • Draft 2 feet per day starting April 1 • Operate 33 feet below full pool April 16-Aug. 31; drawdown levels by project as follows, in feet: <ul style="list-style-type: none"> Lower Granite 705 Little Goose 605 L. Monumental 507 Ice Harbor 407 • Operate over 5-foot forebay range once drawdown elevation reached • Refill from natural flows and storage releases • Same as SOS 1a rest of year <p>SOS 6d</p> <ul style="list-style-type: none"> • Draft Lower Granite 2 feet per day starting April 1 • Operate Lower Granite near 705 ft for 4 1/2 months, April 16-Aug. 31 	<p>SOS 9a</p> <ul style="list-style-type: none"> • Operate 33 feet below full pool (see SOS 6b) April 1-Aug. 31 to meet L. Granite flow targets (see Dworshak); same as SOS 1a rest of year • Spill to achieve 80/80 FPE up to total dissolved gas cap of 120% daily average; spill cap 60 kcfs at all projects <p>SOS 9b</p> <ul style="list-style-type: none"> • Operate at MOP, with 1 foot flexibility April 1-Aug. 31; same as SOS 1a rest of year • Spill to achieve 80/80 FPE up to total dissolved gas cap of 120% daily average; spill caps range from 18 kcfs at L. Monumental to 30 kcfs at L. Granite <p>SOS 9c</p> <ul style="list-style-type: none"> • Operate 35 to 45 feet below full pool April 1-June 15 to meet L. Granite flow targets (see Dworshak), refill by June 30; same as SOS 1a rest of year • Spill to achieve 80/80 FPE, as in SOS 9b 	<p>SOS PA</p> <ul style="list-style-type: none"> • Operate at MOP with 1 foot flexibility between April 10 - Aug. 31 • Refill three lower Snake River pools after Aug. 31, Lower Granite after Nov. 15 • Spill to achieve 80% FPE up to total dissolved gas cap of 115% 12-hour average; spill caps range from 7.5 kcfs at L. Monumental to 25 kcfs at Ice Harbor
SOS 5	SOS 6	SOS 9	SOS PA
<p>SOS 5b</p> <p>Same as SOS 2, except operate John Day within 1.5 feet above elevation 257 feet (MOP) from May 1 through Aug. 31; same as SOS 2c rest of year</p> <p>SOS 5c</p> <p>Same as SOS 5b</p>	<p>SOS 6b</p> <p>Same as SOS 5</p> <p>SOS 6d</p> <p>Same as SOS 5</p>	<p>SOS 9a</p> <ul style="list-style-type: none"> • Same as SOS 5, except operate John Day within 1 foot above elevation 257 feet April 15-Aug. 31 • McNary flow targets as described for Grand Coulee • Spill to achieve 80/80 FPE, up to total dissolved gas cap of 120% daily average, as derived by agencies <p>SOS 9b</p> <ul style="list-style-type: none"> • Same as SOS 2, except operate John Day at minimum irrigation pool or 262.5 feet with 1 foot of flexibility from April 16-Aug. 31 • McNary flow targets as described for Grand Coulee • Spill to achieve 80/80 FPE, up to total dissolved gas cap of 120% daily average, as derived by Corps <p>SOS 9c</p> <p>Same as SOS 9b, except operate John Day at minimum operating pool</p>	<p>SOS PA</p> <ul style="list-style-type: none"> • Pool operations same as SOS 2c, except operate John Day at 257 feet (MOP) year-round, with 3 feet of flexibility March-Oct. and 5 feet of flexibility Nov.-Feb. • Spill to achieve 80% FPE up to total dissolved gas cap of 115% 12-hour average; spill caps range from 9 kcfs at John Day to 90 kcfs at The Dalles

1 kcfs = 28 cms

1 ft = 0.3048 meter

4.1.1 SOS 1-Pre-ESA Operation

This alternative represents one end of the range of the SOR strategies in terms of their similarity to historical system operations. This strategy reflects Columbia River system operations before changes were made as a result of the ESA listing of three Snake River salmon stocks. This SOS has two options:

- **SOS 1a (Pre-Salmon Summit Operation)** represents operations as they existed from 1983 through the 1990–91 operating year, including Northwest Power Act provisions to restore and protect fish populations in the basin. Specific volumes for the Water Budget would be provided from Dworshak and Brownlee reservoirs to attempt to meet a target flow of 85 kcfs (2,380 cms) at Lower Granite Dam in May. Sufficient flows would be provided on the Columbia River to meet a target flow of 134 kcfs (3,752 cms) at Priest Rapids Dam in May. Lower Snake River projects would operate within 3 to 5 feet (0.9 to 1.5 m) of full pool. Other projects would operate as they did in 1990–91, with no additional water provided from the Snake River above Brownlee Dam.
- **SOS 1b (Optimum Load–Following Operation)** represents operations as they existed prior to changes resulting from the Northwest Power Act. It is designed to demonstrate how much power could be produced if most flow–related operations to benefit anadromous fish were eliminated including: the Water Budget; fish spill requirements; restrictions on operation of Bonneville's second powerhouse; and refill targets for Libby, Hungry Horse, Grand Coulee, Dworshak, and Albeni Falls. It assumes that transportation would be used to the maximum to aid juvenile fish migration.

4.1.2 SOS 2-Current Operations

This alternative reflects operation of the Columbia River system with interim flow improvement measures made in response to ESA listings of Snake

River salmon. It is very similar to the way the system operated in 1992 and reflects the results of ESA Section 7 consultation with NMFS then. The strategy is consistent with the 1992–93 operations described in the Corps' *1993 Interim Columbia and Snake Rivers Flow Improvement Measures Supplemental EIS* (SEIS). SOS 2 also most closely represents the recommendations issued by the NMFS Snake River Salmon Recovery Team in May 1994.

Compared to SOS 1, the primary changes are additional flow augmentation in the Columbia and Snake Rivers and modified pool levels at lower Snake and John Day reservoirs during juvenile salmon migration. This strategy has two options:

- **SOS 2c (Final SEIS Operation- No Action Alternative)** matches exactly the decision made as a result of the 1993 SEIS. Flow augmentation water of up to 3.0 MAF (3.7 billion m³) on the Columbia River (in addition to the existing Water Budget) would be stored during the winter and released in the spring in low–runoff years. Dworshak would provide at least an additional 300 KAF (370 million m³) in the spring and 470 KAF (580 million m³) in the summer for flow augmentation. System flood control shifts from Dworshak and Brownlee to Grand Coulee would occur through April as needed. It also provides up to 427 KAF (527 million m³) of additional water from the Snake River above Brownlee Dam.
- **SOS 2d (1994–98 Biological Opinion)** matches the hydro operations contained in the 1994–98 Biological Opinion issued by NMFS in mid–1994. This alternative provides water for the existing Water Budget as well as additional water, up to 4 MAF, for flow augmentation to benefit the anadromous fish migration. The additional water of up to 4 MAF would be stored in Grand Coulee, Libby and Arrow, and provided on a sliding scale tied to runoff forecasts. Flow targets are established at Lower Granite and McNary.

In cases such as the SOR, where the proposed action is a new management plan, the No Action Alterna-

tive means continuing with the present course of action until that action is changed (46 FR 13027). Among all of the strategies and options, SOS 2c best meets this definition for the No Action Alternative.

4.1.3 SOS 4-Stable Storage Project Operation

This alternative is intended to operate the storage reservoirs to benefit recreation, resident fish, wildlife, and anadromous fish while minimizing impacts of such operation to power and flood control. Reservoirs would be kept full longer, but still provide spring flows for fish and space for flood control. The goal is to minimize reservoir fluctuations while moving closer to natural flow conditions. For the Final EIS, this alternative has one option:

- **SOS 4c (Stable Storage Operation with Modified Grand Coulee Flood Control)** applies year-round Integrated Rule Curves (IRCs) developed by the State of Montana for Libby and Hungry Horse. Other reservoirs would be managed to specific elevations on a monthly basis; they would be kept full longer, while still providing spring flows for fish and space for flood control. The goal is to minimize reservoir fluctuations while moving closer to natural flow conditions. Grand Coulee would meet elevation targets year-round to provide acceptable water retention times; however, upper rule curves would apply at Grand Coulee if the January to July runoff forecast at the project is greater than 68 MAF (84 billion m³).
- **SOS 5b (Four and One-half Month Natural River Operation)** provides for a lower Snake River drawdown lasting 4.5 months, beginning April 16 and ending August 31. Dworshak would be drafted to refill the lower Snake River projects if natural inflow were inadequate for timely refill.
- **SOS 5c (Permanent Natural River Operation)** provides for a year-round drawdown, and projects would not be refilled after each migration season.

4.1.4 SOS 5-Natural River Operation

This alternative is designed to aid juvenile salmon migration by drawing down reservoirs (to increase the velocity of water) at four lower Snake River projects. SOS 5 reflects operations after the installation of new outlets in the lower Snake River dams, permitting the lowering of reservoirs approximately 100 feet (30 m) to near original riverbed levels. This operation could not be implemented for a number of years, because it requires major structural modifications to the dams. Elevations would be: Lower Granite – 623 feet (190 m); Little Goose – 524 feet

(160 m); Lower Monumental – 432 feet (132 m); and Ice Harbor – 343 feet (105 m). Drafting would be at the rate of 2 feet (0.6 m) per day beginning February 18. The reservoirs would refill again with natural inflows and storage releases from upriver projects, if needed. John Day would be lowered as much as 11 feet (3.3 m) to minimum pool, elevation 257 feet (78.3 m), from May through August. All other projects would operate essentially the same as in SOS 1a, except that up to 3 MAF (3.7 billion m³) of water (in addition to the Water Budget) would be provided to augment flows on the Columbia River in May and June. System flood control would shift from Brownlee and Dworshak to the lower Snake River projects. Also, Dworshak would operate for local flood control. This alternative has two options:

4.1.5 SOS 6-Fixed Drawdown

This alternative is designed to aid juvenile anadromous fish by drawing down one or all four lower Snake River projects to fixed elevations approximately 30 to 35 feet (9 to 10 m) below minimum operating pool. As with SOS 5, fixed drawdowns depend on prior structural modifications and could not be instituted for a number of years. Draft would be at the rate of 2 feet (0.6 m) per day beginning April 1. John Day would be lowered to elevation 257 feet (78.3 m) from May through August. All other projects would operate essentially the same as under SOS 1a, except that up to 3 MAF (3.7 billion m³) of water would be provided to augment flows on the Columbia River in May and June. System flood control would shift from Brownlee and Dworshak to the lower Snake projects. Also, Dwor-

shak would operate for local flood control. This alternative has two options:

- **SOS 6b (Four and One-half Month Fixed Drawdown)** provides for a 4.5-month drawdown at all four lower Snake River projects beginning April 16 and ending August 31. Elevations would be: Lower Granite – 705 feet (215 m); Little Goose – 605 feet (184 m); Lower Monumental – 507 feet (155 m); and Ice Harbor – 407 feet (124 m).
- **SOS 6d (Four and One-half Month Lower Granite Fixed Drawdown)** provides for a 4.5-month drawdown to elevation 705 feet at Lower Granite beginning April 16 and ending August 31.

4.1.6 SOS 9-Settlement Discussion Alternatives

This SOS represents operations suggested by USFWS and NMFS (as SOR cooperating agencies), the State fisheries agencies, Native American tribes, and the Federal operating agencies during the settlement discussions in response to a court ruling in the *IDFG v. NMFS* lawsuit. The objective of SOS 9 is to provide increased velocities for anadromous fish by establishing flow targets during the migration period and by carrying out other actions that benefit ESA-listed species. The specific options were developed by a group of technical staff representing the parties in the lawsuit. The group was known as the Reasonable and Prudent Alternatives Workgroup. They developed three possible operations in addition to the 1994–98 Biological Opinion. This strategy has three options:

- **SOS 9a (Detailed Fishery Operating Plan [DFOP])** establishes flow targets at The Dalles based on the previous year's end-of-year storage content, similar to how PNCA selects operating rule curves. Grand Coulee and other storage projects are used to meet The Dalles flow targets. Specific volumes of releases are made from Dworshak, Brownlee, and upper Snake River to try to meet Lower

Granite flow targets. Lower Snake River projects are drawn down to near spillway crest level for 4 1/2 months. Specific spill percentages are established at run-of-river projects to achieve no higher than 120 percent daily average total dissolved gas. Fish transportation is assumed to be eliminated.

- **SOS 9b (Adaptive Management)** establishes flow targets at McNary and Lower Granite based on runoff forecasts. Grand Coulee and other storage projects are used to meet the McNary flow targets. Specific volumes of releases are made from Dworshak, Brownlee, and the upper Snake River to try to meet Lower Granite flow targets. Lower Snake River projects are drawn down to minimum operating pool levels and John Day is at minimum irrigation pool level. Specific spill percentages are established at run-of-river projects to achieve no higher than 120 percent daily average for total dissolved gas.
- **SOS 9c (Balanced Impacts Operation)** draws down the four lower Snake River projects to near spillway crest levels for 2 1/2 months during the spring salmon migration period. Full drawdown level is achieved on April 1. Refill begins after June 15. This alternative also provides 1994–98 Biological Opinion flow augmentation (as in SOS 2d), IRC operation at Libby and Hungry Horse, a reduced flow target at Lower Granite due to drawdown, limits on winter drafting at Albeni Falls, and spill to achieve no higher than 120 percent daily average for total dissolved gas.

4.1.7 SOS PA-Preferred Alternative

This SOS represents the operation recommended by NMFS and USFWS in their respective Biological Opinions issued on March 1, 1995. SOS PA is intended to support recovery of ESA-listed species by storing water during the fall and winter to meet spring and summer flow targets, and to protect other resources by managing detrimental effects through maximum summer draft limits, by

providing public safety through flood protection, and by providing for reasonable power generation. This SOS would operate the system during the fall and winter to achieve a high confidence of refill to flood control elevations by April 15 of each year, and use this stored water for fish flow augmentation. It establishes spring flow targets at McNary and Lower Granite based on runoff forecasts, and a similar sliding scale flow target at Lower Granite and a fixed flow target at McNary for the summer. It establishes summer draft limits at Hungry Horse, Libby, Grand Coulee, and Dworshak. Libby is also operated to provide flows for Kootenai River white sturgeon. Lower Snake River projects are drawn down to minimum operating pool levels during the spring and summer. John Day is operated at minimum operating pool level year-round. Specific spill percentages are established at run-of-river projects to achieve 80-percent FPE, with no higher than 115-percent 12-hour daily average for total dissolved gas measured at the forebay of the next downstream project.

4.1.8 Rationale for Selection of the Final SOSs

Table 4-2 summarizes the changes to the set alternatives from the Draft EIS to the Final EIS. SOS 1a and 1b are unchanged from the Draft EIS. SOS 1a represents a base case condition and reflects system operation during the period from passage of the Northwest Power Planning and Conservation Act until ESA listings. It provides a baseline alternative that allows for comparison of the more recent alternatives and shows the recent historical operation. SOS 1b represents a limit for system operation directed at maximizing benefits from development-oriented uses, such as power generation, flood control, irrigation and navigation and away from natural resources protection. It serves as one end of the range of alternatives and provides a basis for comparison of the impacts to power generation from all other alternatives. Public comment did not recommend elimination of this alternative because it serves as a useful milepost. However, the SOR agencies recognize it is

unlikely that decisions would be made to move operations toward this alternative.

In the Draft EIS, SOS 2 represented current operation. Three options were considered. Two of these options have been eliminated for the Final EIS and one new option has been added. SOS 2c continues as the No Action Alternative. Maintaining this option as the No Action Alternative allows for consistent comparisons in the Final EIS to those made in the Draft EIS. However, within the current practice category, new operations have been developed since the original identification of SOS 2c. In 1994, the SOR agencies, in consultation with the NMFS and USFWS, agreed to an operation, which was reflected in the 1994-98 Biological Opinion. This operation (SOS 2d) has been modeled for the Final EIS and represents the most "current" practice. SOS 2d also provides a good baseline comparison for the other, more unique alternatives. SOS 2a and 2b from the Draft EIS were eliminated because they are so similar to SOS 2c. SOS 2a is identical to SOS 2c except for the lack of an assumed additional 427 KAF of water from the upper Snake River Basin. This additional water did not cause significant changes to the effects between SOS 2a and 2c. There is no reason to continue to consider an alternative that has impacts essentially equal to another alternative. SOS 2b is also similar to SOS 2c, except it modified operation at Libby for Kootenai River white sturgeon. Such modifications are included in several other alternatives, namely SOS 2d, 9a, 9c, and the Preferred Alternative.

SOS 3a and 3b, included in the Draft EIS, have been dropped from consideration in the Final EIS. Both of these alternatives involved anadromous fish flow augmentation by establishing flow targets based on runoff forecast on the Columbia and Snake Rivers. SOS 3b included additional water from the upper Snake River Basin over what was assumed for SOS 3a. This operation is now incorporated in several new alternatives, including SOS 9a and 9b. Public comment also did not support continued consideration of the SOS 3 alternatives.

Table 4-2. Summary of Alternatives in the Draft and Final EIS

Draft EIS Alternatives	Final EIS Alternatives
SOS 1 Pre-ESA Operation	SOS 1 Pre-ESA Operation
SOS 1a Pre-Salmon Summit Operation	SOS 1a Pre-Salmon Summit Operation
SOS 1b Optimum Load Following Operation	SOS 1b Optimum Load Following Operation
SOS 2 Current Practice	SOS 2 Current Practice
SOS 2a Final Supplemental EIS Operation	SOS2c Final Supplemental EIS Operation – No-Action Alternative
SOS 2b Final Supplemental EIS with Sturgeon Operations at Libby	SOS 2d 1994-98 Biological Opinion Operation
SOS2c Final Supplemental EIS Operation – No-Action Alternative	
SOS 3 Flow Augmentation	
SOS 3a Monthly Flow Targets	
SOS 3b Monthly Flow Targets with additional Snake River Water	
SOS 4 Stable Storage Project Operation	SOS 4 Stable Storage Project Operation
SOS 4a1 Enhanced Storage Level Operation	SOS 4c Enhanced Operation with modified Grand Coulee Flood Control
SOS 4a3 Enhanced Storage Level Operation	
SOS 4b1 Compromise Storage Level Operation	
SOS 4b3 Compromise Storage Level Operation	
SOS 4c Enhanced Operation with modified Grand Coulee Flood Control	
SOS 5 Natural River Operation	SOS 5 Natural River Operation
SOS 5a Two Month Natural River Operation	SOS 5b Four and One Half Month Natural River Operation
SOS 5b Four and One Half Month Natural River Operation	SOS 5c Permanent Natural River Operation
SOS 6 Fixed Drawdown	SOS 6 Fixed Drawdown
SOS 6a Two Month Fixed Drawdown Operation	SOS 6b Four and One Half Month Fixed Drawdown Operation
SOS 6b Four and One Half Month Fixed Drawdown Operation	SOS 6d Four and One Half Month Lower Granite Drawdown Operation
SOS 6c Two Month Lower Granite Drawdown Operation	
SOS 6d Four and One Half Month Lower Granite Drawdown Operation	
SOS 7 Federal Resource Agency Operations	SOS 9 Settlement Discussion Alternatives
SOS 7a Coordination Act Report Operation	SOS 9a Detailed Fishery Operating Plan
SOS 7b Incidental Take Statement Flow Targets	SOS 9b Adaptive Management
SOS 7c NMFS Conservation Recommendations	SOS 9c Balance Impacts Operation
	SOS Preferred Alternative

Bold indicates a new or revised SOS alternative

SOS 4 originally included 5 options in the Draft EIS. They were similar in operation and impact. In SOS 4a and 4b, the primary feature was the use of Biological Rule Curves for Libby and Hungry Horse reservoirs. SOS 4c also included these rule curves but went further by optimizing the operation of the other storage projects, particularly Grand Coulee and Dworshak. For the Final EIS, the SOR agencies have decided to update the alternative by substituting the IRC for the Biological Rule Curves and by eliminating SOS 4a and 4b. The IRCs are a more recent, acceptable version of minimum elevations for Libby and Hungry Horse. Significant public comment in support of this alternative with IRCs was received. Similar to SOS 2 above, SOS 4a and 4b were not different enough in operation or impacts to warrant continued consideration.

The Natural River (SOS 5) and the Spillway Crest Drawdown (SOS 6) alternatives in the Draft EIS originally included options for 2 months of drawdown to the appropriate pool level and 4 1/2 months of drawdown. The practicality of 2-month drawdowns was questioned during public review, particularly for the natural river. It did not appear that the time involved in drawing down the reservoirs and later refilling them provided the needed consideration for other uses. Flows are restricted to refill the reservoirs at a time when juvenile fall chinook are migrating downstream and various adult species are returning upstream. The 2 1/2 month drawdown strategies (SOS 5a, 6a, and 6c) have been dropped from the Final EIS. However, 2 1/2 month spillway crest drawdown at all four lower Snake projects is still an element in SOS 9c, so the impacts associated with this type of operation are assessed in the Final EIS.

A new option was added to SOS 5, namely SOS 5c. This option includes natural river drawdown of the lower Snake River projects on a permanent, year-round basis. The Corps received comment on this type of alternative during the review of Phase I of the SCS, a reconnaissance assessment of potential physical modifications for the system to enhance fish passage. Many believe the cost for such modification would be less than that required for periodic, temporary drawdowns, which would require special-

ized facilities to enable the projects to refill and operate at two different pool elevations.

SOS 7 Federal Resource Agencies Operations, which included 3 options in the Draft EIS, has been dropped from the Final EIS and replaced with an alternative now labeled as SOS 9 that also has 3 options. SOS 7a was suggested by the USFWS and represented the State fishery agencies and tribes' recommended operation. Since the issuance of the Draft EIS, this particular operation has been revised and replaced by the DFOP (SOS 9a). The SOR agencies received comment that the DFOP was not evaluated, but should be. Therefore, we have included this alternative exactly as proposed by these agencies; it is SOS 9a. SOS 7b and 7c were suggested by NMFS through the 1993 Biological Opinion. This opinion suggested two sets of flow targets as a way of increasing flow augmentation levels for anadromous fish. The flow targets came from the Incidental Take Statement and the Conservation Recommendation sections of that Biological Opinion. The opinion was judged as arbitrary and capricious as a result of legal action, and these operational alternatives have been replaced with other alternatives that were developed through settlement discussions among the parties to this lawsuit. SOS 7b and 7c have been dropped, but SOS 9b and 9c have been added to represent operations stemming from NMFS or other fishery agencies. In particular, SOS 9b is like DFOP but has reduced flow levels and forgoes drawdowns. It is a modification to DFOP. SOS 9c incorporates elements of operation supported by the State of Idaho in its "Idaho Plan." It includes a 2 1/2-month spillway crest drawdown on the lower Snake River projects and several other elements that attempt to strike a balance among the needs of anadromous fish, resident fish, wildlife and recreation.

Shortly after the alternatives for the Draft EIS were identified, the Nez Perce Tribe suggested an operation that involved drawdown of Lower Granite, significant additional amounts of upper Snake River water, and full pool operation at Dworshak (i.e., Dworshak remains full year round). It was labeled as SOS 8a. Hydroregulation of that operation was completed and provided to the Nez Perce Tribe. No technical response has been received from the Nez

Perce Tribe regarding the features or results of this alternative. However, the elements of this operation are generally incorporated in one or more of the other alternatives, or impose requirements on the system or specific projects that are outside the range considered reasonable. Therefore, this alternative has not been carried forward into the Final EIS.

The Preferred Alternative represents operating requirements contained in the 1995 Biological Opinions issued by NMFS and USFWS on operation of the FCRPS. These opinions resulted from ESA consultation conducted during late 1994 and early 1995, which were a direct consequence of the lawsuit and subsequent judgement in *Idaho v. NMFS*. The SOR agencies are now implementing this operating strategy and have concluded that it represents an appropriate balance among the multiple uses of the river. This strategy recognizes the importance of anadromous fish and the need to adjust river flows to benefit the migration of all salmon stocks, as well as the needs of resident fish and wildlife species at storage projects.

4.2 IMPACTS OF THE ALTERNATIVES (BY PROJECT/RIVER REACH)

4.2.1 General Overview

In this section, the recreational impacts of each of the alternative SOSs are described by project or river reach. Wherever possible, descriptions of similar alternative SOSs and suboptions are combined within each river reach or project area. If there are any significant differences in the way an SOS or suboption affects recreation resources, it is described separately.

The following parameters affecting or influencing recreational suitability are described for each SOS or suboption (individually or in similar sets) for each project or river reach.

4.2.1.1 Description/Hydrologic Characteristics

The hydrologic characteristics of each alternative SOS that influence recreation resources are described by project and river reach. This information is based on the results of the SOR hydroregulations which

predict end-of-month pool elevations and average monthly outflows over the 50-year hydrologic period of record for each project in the system.

For storage reservoirs and most run-of-river reservoirs, end-of-month pool elevation is the most critical information for determining recreational suitability. This information can be used to determine the degree and timing of seasonal draw-down and refill at those projects.

Short-term operation (hourly, daily and weekly pool elevations and outflows) is important information for determining the recreational suitability of some run-of-river reservoirs and downstream river reaches. This information, however, was not available as an output of the hydregulation models. Therefore, unless a specific short-term operation was stipulated as specific operational criteria for a given SOS, it was assumed that the projects would operate under base case (SOS 2c) criteria.

Average monthly outflows from upstream projects were used to determine recreational impacts on free-flowing downstream river reaches.

4.2.1.2 Quantitative Results of Impact Assessment Models

The results of the recreational impact assessment models summarized in Chapter 3 and described in detail in Appendix J1, are presented for the 13 projects and river reaches for which models were prepared. If a model was not prepared for a project/river reach, only qualitative descriptions of impacts were provided.

For most projects/river reaches, two tables are presented. The first presents a quantitative estimate of visitor use in recreation days for key water-related recreation activities during low, average and high water years under each of the alternative SOS's (four or five activities for most projects, although some only included one key activity). The second table presents a cumulative total recreational use for all activities and compares the estimated total recreation use for each SOS against the base case (SOS 1a), the no action alternative (SOS 2c) and the baseline visitation (October 1992 through November 1993) for the project/river reach.

In most cases, the results of the recreation impact assessment models for the individual projects and river reaches directly reflect the effects of the hydroregulation at that individual site. However, as described in chapter 3, the model estimates regional recreation demand and does take into consideration the effects of substitute and complement recreation areas. Consequently, some situations do occur, for example, where although the hydroregulation results indicate poor recreation conditions at a particular lake or river reach, recreation demand for that site may increase if conditions are equally poor or worse at substitute lakes or rivers in the region.

4.2.1.3 Effects on Recreation Facilities/Activities

This section provides a qualitative description of how drawdowns or flows under each SOS affect the usability of recreation facilities at that lake or reservoir.

4.2.1.4 Effects on Fish Habitat and Fishing Success

This section provides a qualitative description of the effects of alternative SOSs on fish populations and, therefore, on fishing and fish catching success. This analysis is based on the impact assessments presented in SOR Appendix C, Anadromous Fish, and Appendix K, Resident Fish.

There is some concern that the recreation impact assessment models previously described may not accurately estimate the effects on recreation demand attributable to changes in fish biology and fish production associated with alternative system operations. The models are based on a survey in which anglers and other users were presented with visual and narrative depictions of alternative pool elevations at seven reservoirs and flows at two rivers in the basin. Survey participants were asked to respond regarding how those elevations would influence their recreational use. Although no information on fisheries was provided, it is assumed that anglers would form an assumption of the effects of lake elevations on the enjoyment of their fishing experience (including fish-catching success). Their stated

preferences under alternative operations are based in part on these assumptions.

The models, however, do not contain any direct correlations between recreation demand and expected changes in catch rates due to changes in fish biology resulting from alternative operations. A catch rate parameter was considered for inclusion in the model but ultimately was excluded because it did not appear that adequate data exists to allow catch rates to be statistically significant in explaining recreational demand. The decision to exclude this parameter was based on the following:

- a. Catch rate data currently available is of mixed quality and is available for different years at different projects. Little, if any catch rate data was available for 1993, the year in which the recreation survey was implemented. The survey is based on reported recreational trips in 1993. To explain the fishing demand for 1993 would require complete 1993 catch rate data. In theory, the models could have used previous year catch rates but this would be an accurate determinant of angler demand only if catch rates had not changed over time. Fish catching rates at many of the projects have changed substantially over time due to factors such as changing stocking programs.
- b. Catch rate data is available for different species at different projects. In theory, it would be possible to include in the model different catch rates for different species for different projects. However, doing so would require knowledge of a specific angler's target species. An alternative approach would be to assume the catch rate for a single species as the proxy for all fishing trip demand. This is probably not a safe assumption given that most of the projects have more than one target gamefish species which anglers may pursue with varying degrees of effort during different seasons of the year. Further, different species respond differently to alternative operational changes affecting their habitat. Attempting to place more than one catch rate in the model would make the model estimation process much

more complicated and would probably have made the model estimation intractable.

- c. Finally, the modeling efforts and analysis completed by the Anadromous Fish (Appendix C) and Resident Fish (Appendix K) Work Groups have not been able to determine how alternative system operations affect fish habitat and fish stocks in a manner that is suitable for use in a recreation demand model based on fish catching rates.

Given these data limitations, it was believed at the time the SOR recreation impact assessment models were prepared that the most important determinant of fishing demand would be the effects of changing operations (pool elevations or river flows) on accessibility and use.

4.2.1.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

This section qualitatively describes the potential impacts of alternative SOSs to wildlife habitat and corresponding impacts to hunting and wildlife viewing success. This section is based on impacts described in SOR Technical Appendix N, Wildlife.

4.2.1.6 Effects on Recreational Safety and Physical Characteristics

This section qualitatively describes the effects of the alternatives on the recreational safety and physical

characteristics. The focus here is to describe any existing problems under alternatives 1a (base case) or 2c (no action). Under the other alternatives, these existing problems could be exacerbated, reduced or not significantly affected.

4.2.1.7 Effects on Water Quality Parameters Influencing Recreation

This section qualitatively describes the effects of this alternative on the water quality parameters. The focus here is to describe any existing problems under alternatives 1a (base case) or 2c (no action). Under the other alternatives, these existing problems could be exacerbated, reduced or not significantly affected.

4.2.1.8 Effects on Aesthetics

This section qualitatively describes the effects of the alternatives on aesthetics, primarily visual quality.

4.2.1.9 Mitigation Opportunities

This section describes any mitigation opportunities that could be enacted to reduce or eliminate the impact of the alternatives on recreation. Also described is any mitigation that may have been recently implemented at the individual projects, particularly those implemented following salmon summit actions. Chapter 5 presents a comprehensive mitigation plan for the Preferred Alternative.

4.2.2 LIBBY PROJECT/LAKE KOOCANUSA

4.2.2.1 Description/Hydrologic Characteristics

At full pool, Lake Koocanusa is about 90 miles long, with about 42 of those miles in Canada. Boating, fishing, and swimming are the most important recreation activities. The success of these activities is directly related to stable reservoir levels in the peak recreation season. The lake can be drawn down over 160 feet — refill anytime during the recreation season is never certain.

Table 4-3 shows the predicted end-of-month pool elevations for low (1941), average, and high (1976) water years during the four peak recreation months under the alternative SOSs. Full pool is 2459 feet NGVD.

High and low water years can produce a significant change over the 50-year average projected by the

hydroregulations. Generally speaking, during wet water years when winter forecasts predict high spring runoff, the lake is drawn down lower during the late winter and early spring to provide additional flood control storage. Consequently, under most of the alternatives, the lake is lower during May and early June of high water years than average and low water years. However, the likelihood that the lake can refill and be held fuller during late summer and early fall is higher during wet years.

The summer recreational suitability of Lake Koocanusa under each of the alternative SOSs in an average water year over the 50-year period of record is briefly described below from best to worse.

SOS 4c and 9c are the best alternatives for recreation in an average water year. With end-of-May elevations about 35 feet below full pool, they refill early to within 6 feet of full pool in June and stay at that level through August.

Table 4-3. Lake Koocanusa Predicted Summer End-of-Month Pool Elevations for Low, Average and High Water Years

ALT	MAY			JUNE			JULY			AUG		
	low	average	high	low	average	high	low	average	high	low	average	high
1a	2423.3	2389.5	2385.6	2429.2	2439.0	2429.6	2429.1	2451.4	2459.0	2421.6	2449.8	2459.0
1b	2410.5	2387.4	2385.6	2426.3	2439.6	2431.0	2422.8	2450.6	2459.0	2416.3	2449.0	2459.0
2c	2419.6	2390.3	2400.0	2440.6	2441.5	2440.0	2437.5	2453.5	2459.0	2432.0	2452.7	2459.0
2d	2409.3	2387.3	2400.0	2431.5	2439.0	2427.0	2439.1	2451.6	2452.7	2429.6	2448.9	2459.0
4c	2429.9	2424.2	2436.5	2450.0	2452.8	2455.6	2456.8	2454.6	2459.0	2458.9	2454.0	2459.0
5b	2423.3	2386.0	2385.6	2429.2	2437.3	2429.6	2429.1	2450.8	2459.0	2421.6	2449.8	2459.0
5c	2423.3	2386.0	2385.6	2429.2	2437.3	2429.6	2429.1	2450.8	2459.0	2421.6	2449.8	2459.0
6b	2423.3	2386.0	2385.6	2429.2	2437.3	2429.6	2429.1	2450.8	2459.8	2421.6	2449.8	2459.0
6d	2426.3	2386.0	2385.6	2429.2	2437.3	2429.6	2429.1	2450.8	2459.0	2421.6	2449.8	2459.0
9a	2334.9	2370.8	2400.0	2310.1	2395.1	2402.9	2287.0	2392.7	2416.2	2287.0	2390.4	2423.6
9b	2424.6	2398.4	2400.0	2435.5	2436.1	2435.5	2435.5	2441.6	2446.6	2435.5	2442.4	2459.0
9c	2429.9	2424.2	2436.5	2450.0	2452.8	2455.6	2456.8	2454.5	2459.0	2458.9	2453.8	2459.0
PA	2414.3	2391.2	2400.0	2403.2	2423.4	2439.0	2405.4	2439.2	2459.0	2408.1	2436.8	2459.0

SOS 1a (the Base Case Alternative) and SOS 2c (the No-Action Alternative) both start at between 69 and 72 feet below full pool at the end of May in an average water year. They refill more slowly to within about 10 feet of full pool in July and remain there through August. SOS 1b and 2d are operated in a similar manner.

SOS 5b, 5c, 6b, and 6d are very similar to the previous group. These four alternatives start out at about the same level (about 73 feet below full pool) in an average water year. They fill slightly more slowly, reaching a bit higher level – about eight feet below full pool – in July and August.

SOS 9b starts out higher in an average water year than the previous two groups – about 61 feet below full pool in May. It fills to about 23 feet below full pool in June, then doesn't get above 17 feet below full pool for the rest of the season.

The **Preferred Alternative** starts out in May at about the same level as the previous three groups. But it begins to refill very late, with the June level at 36 feet below full pool. It tops at 20 feet below full pool in July and then drops 2 feet in August.

SOS 9a, the worst alternative for recreation, has a May elevation of 88 feet below full pool in an average water year. It fills to 64 feet below full pool in June, then drops 2 feet in July and another 3 feet in August. This alternative would also feature very deep summer drawdowns—during 10 percent of years the lake would be drawn down at least 170 feet.

4.2.2.2 Quantitative Results of Impact Assessment Models

Table 4-4 and Figure 4-1 present the results of the SOR recreation impact assessment model for Lake Koocanusa. The model provides a quantitative estimate of recreation use in recreation days for key water related recreation activities during low, average and high water years under each of the alternative SOSs. The model shows that for key recreation activities for the 50-year average, there is no significant difference in visitation for all categories between the base case alternative (1a) and the no-action alternative (2c), though the base case is slightly lower. The basic trend in all categories is as follows: alternatives 2d, 4c, and 9c improve visitation; 5b, 5c, 6b, and 6d keep it about the same as (or slightly worse than) 1a and 2c; 9b somewhat worsens it; and 9a significantly worsens it. High and low water years can accentuate the trend in some instances, and diminish it in others.

Table 4-4. Lake Koocanusa, Estimated Recreation Days by Activity

SOS	Boating			Fishing			Camping			Picnicking			Swimming		
	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976
1a	80509	80592	80955	239534	239780	240862	196410	196613	197500	75013	75090	75429	12502	12515	12571
1b	79095	80486	81022	235326	239465	241061	192960	196354	197663	73695	74991	75491	12283	12499	12582
2c	81144	80946	82099	241424	240834	244266	197961	197477	200290	75605	75420	76495	12601	12570	12749
2d	80377	80648	81457	239141	239948	242353	196089	196750	198723	74890	75142	75896	12482	12524	12649
4c	80455	82630	83879	239374	245844	249560	196279	201584	204632	74963	76989	78153	12494	12831	13025
5b	80509	80363	80955	239534	239098	240862	196410	196053	197500	75013	74876	75429	12502	12479	12571
6b	80509	80363	80955	239534	239099	240862	196410	196054	197500	75013	74877	75429	12502	12479	12571
6d	80509	80363	80955	239534	239099	240862	196410	196054	197500	75013	74877	75429	12502	12479	12571
9a	63533	72807	79267	189026	216617	235837	154996	177620	193379	59196	67836	73855	9866	11306	12309
9b	78364	79559	81376	233153	236707	242115	191179	194092	198527	73015	74128	75821	12169	12355	12637
9c	82439	82435	83848	245275	245265	249468	201118	201110	204556	76811	76808	78124	12802	12801	13021
PA	78858	80199	82255	234622	238610	244729	192383	195653	200670	73475	74724	76640	12246	12454	12773

Figure 4-1. Lake Koocanusa, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Table 4-5 compares the estimated total recreation use for each SOS against the base case (SOS 1a), the no action alternative (SOS 2c) and the baseline 1992 – 1993 visitation for Lake Koocanusa. The baseline visitation data does not include the six major parks that are administered by the USFS. The data collected by the USFS was not considered reliable enough to be accurately used in the evaluation. Visitors to the three private resort/marinas on the reservoir are likewise not included. Therefore, the Corps visitation data supplied for full-scale modeling purpose under-estimates the total number of visitors that historically come to the reservoir. The

data is considered accurate, however, for predicting trends across the alternative SOSs

Empirical estimation of the model is described in more detail in Appendix J-1. The model estimates recreational use at Lake Koocanusa based on changes in operation of the system. Recreational use is influenced not only by changes in pool elevation at Lake Koocanusa, but also by changes in pool elevations of other projects in the western Montana/northern Idaho region of the user survey. Both the Hungry Horse and the Kootenai River models include Lake Koocanusa as a first stage complement.

Table 4-5. Lake Koocanusa, Estimated Total Recreation Days Under Alternative SOSs

Average Visitation (1987–1993): 593,200 Baseline Visitation (11/92–10/93): 579,000		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	603968	604590	607318
	% change from 2c	–0.78%	–0.44%	–1.39%
	% change from Preferred Alternative	2.09%	0.49%	–1.58%
	% change from 92–93		4.42%	
SOS 1b	Total	593359	603795	607818
	% change from 1a	–1.76%	–0.13%	0.08%
	% change from 2c	–2.53%	–0.57%	–1.31%
	% change from Preferred Alternative	0.30%	0.36%	–1.50%
SOS 2c:	Total	608735	607247	615899
	% change from 1a	0.79%	0.44%	1.41%
	% change from Preferred Alternative	2.90%	0.93%	–0.19%
	% change from 92–93		4.88%	
SOS 2d	Total	602979	605012	611078
	% change from 1a	–0.16%	0.07%	0.62%
	% change from 2c	–0.95%	–0.37%	–0.78%
	% change from Preferred Alternative	1.93%	0.56%	–0.97%
SOS 4c	Total	603565	619879	629248
	% change from 1a	–0.07%	2.53%	3.61%
	% change from 2c	–0.85%	2.08%	2.17%
	% change from Preferred Alternative	2.03%	3.03%	1.97%
SOS 5b	Total	603968	602870	607318
	% change from 1a	0.00%	–0.28%	0.00%
	% change from 2c	–0.78%	–0.72%	–1.39%
	% change from Preferred Alternative	2.09%	0.20%	–1.58%
SOS 5c	Total	603968	602871	607318
	% change from 1a	0.00%	–0.28%	0.00%
	% change from 2c	–0.78%	–0.72%	–1.39%
	% change from Preferred Alternative	2.09%	0.20%	–1.58%
SOS 6b	Total	603968	602871	607318
	% change from 1a	0.00%	–0.28%	0.00%
	% change from 2c	–0.78%	–0.72%	–1.39%
	% change from Preferred Alternative	2.09%	0.20%	–1.58%
	% change from 92–93		4.12%	

Table 4-5. Lake Koocanusa, Estimated Total Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 593,200 Baseline Visitation (11/92–10/93): 579,000		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 6d	Total	603968	602871	607318
	% change from 1a	0.00%	–0.28%	0.00%
	% change from 2c	–0.78%	–0.72%	–1.39%
	% change from Preferred Alternative	2.09%	0.20%	–1.58%
	% change from 92–93		4.12%	
SOS 9a	Total	476616	546186	594648
	% change from 1a	–21.09%	–9.66%	–2.09%
	% change from 2c	–21.70%	–10.06%	–3.45%
	% change from Preferred Alternative	–19.43%	–9.22%	–3.63%
	% change from 92–93		–5.67%	
SOS 9b	Total	587880	596840	610476
	% change from 1a	–2.66%	–1.28%	0.52%
	% change from 2c	–3.43%	–1.71%	–0.88%
	% change from Preferred Alternative	–0.63%	–0.80%	–1.07%
	% change from 92–93		3.08%	
SOS 9c	Total	618443	618419	629016
	% change from 1a	2.40%	2.29%	3.57%
	% change from 2c	1.59%	1.84%	2.13%
	% change from Preferred Alternative	4.54%	2.79%	1.94%
	% change from 92–93		6.81%	
PA	Total	591582	601640	617068
	% change from 1a	–2.05%	–0.49%	1.61%
	% change from 2c	–2.82%	–0.92%	0.19%
	% change from 92–93		3.91%	

This means that, based on the results of the user survey in the region, it is possible that a higher water level at Lake Koocanusa might increase a recreator's propensity to visit Hungry Horse or the Kootenai River because the higher water levels might produce a more satisfying recreation experience, thereby increasing the likelihood of future trips. This relationship is described in more detail in Appendix J–1, Chapter 5.

Average Water Years. In an average water year, estimated total recreation days for both SOS 1a and 2c are very similar, within one-half percentage point of each other and about 5 percent over the 1992–93 average. SOS 2c would have similar visita-

tion. In comparison with the base case and no action alternative, SOS 4c and 9c show a slight increase of about 2 percent (plus or minus 0.5 percent) while SOS 5b, 5c, 6b, 6d and the PA all show a very slight decrease of less than 1 percent in estimated total visitor use. SOS 9b is slightly worse with an estimated decrease of between 1 and 2 percent. According to the recreation impact assessment models, SOS 9a is by far the worst alternative for recreation, with an approximately 10 percent decrease in visitation when compared with SOS 1a and 2c.

Low Water Years. During an extreme low water year, total estimated visitation to Lake Koocanusa actually increases slightly (no more than 2,000

visitors) over average water years under SOS 2c, 5b, 5c, 6b, and 9c. The increased total visitation can largely be attributed to increased visitation in May when the lake can be filled earlier in response to low flood runoff forecasts. In some cases under these alternatives, water levels in Lake Koocanusa will be lower than in average water years. However, the model does take into consideration the affects of substitution on visitor use of the lake. While lake elevations in Lake Koocanusa during a dry year may be lower, other alternative water-based recreation sites in the region may also be low due to the same hydrologic conditions, encouraging more visitors to use the lake.

In comparison SOS 1a, 1b, 2d, 4c, 9a, 9b, and the PA in a low water year all show slight to moderate declines in visitation when compared to average water conditions in the region. These declines are most significant under SOS 4c and 9a, where the loss in visitation from an average to a dry year is estimated at about 16,000 and 70,000 total annual visitors, respectively.

High Water Years. Under all of the alternatives estimated visitation in an extreme wet year (1976), when the probability is greater that the lake can be refilled and maintained high through the recreation season, is higher than for either average or low water conditions. This is despite the fact that lake elevations are often considerably lower during May of wet years under most of the alternatives due to high flood forecasts.

4.2.2.3 Effects on Recreation Facilities/Activities

Boating. Alternatives 2d, 4c, and 9c improve boating suitability over the base case (1a) and the no-action (2c) alternatives, while 9a, 9b, and the preferred alternative (PA) worsen it. The other alternatives – 1b, 5b, 5c, 6b, and 6d – vary little from 1a and 2c. This is because most boat ramps on the United States side of Lake Koocanusa are useable down to 80 feet below full pool. The negative impacts of lower water elevations on boating are greater for private marinas with floating and fixed docks which have a more limited range of flexibility.

Boating facilities on the Canadian side of the lake will also be more severely impacted by lower water levels.

Camping and Picnicking. Use is more constant for all alternatives because these activities are less contingent on water levels. Alternatives 2d, 4c, and 9c could slightly increase camping and picnicking use. Visitation for these activities is slightly reduced under 9B, while 9A reduces it substantially. This is probably due to the diminished aesthetic qualities of the lake at lower elevations. The other alternatives all have about the same predicted visitation for camping and picnicking.

Swimming. This activity stays fairly constant for all elevations except for a marked decline for 9a, with its consistently low elevations. Even though many established swimming beaches are only useable down to from 5 to 10 feet below full pool, swimmers make use of other areas that become exposed as the water elevation drops. Thus, swimming use is projected to remain fairly constant.

4.2.2.4 Effects on Fish Habitat and Fishing Success

SOR Technical Appendix K, Resident Fish, describes the potential impacts of the alternatives on fish biology in Lake Koocanusa. Changes in fish populations and growth affect fishing success and, subsequently, fishing demand. Thus, estimated visitation under the alternatives correlates to potential impacts to resident fish and fishing success.

Generally, deep drawdowns and refill failure result in lost aquatic production with slower annual growth in gamefish and prey species. Thus, alternatives 1b, 5b, 5c, 6b, 6d, 9b, and the preferred alternative (PA) should provide no significant change from the base case (1a) and the no-action (2c) alternatives. Fishing success will remain less than optimal for all gamefish, including kokanee, rainbow trout, cut-throat trout, and whitefish. The higher refill levels and lower pool fluctuations for alternatives 2d, 4c, and 9c are projected to improve fish biology and therefore fishing success when compared with the no action alternative. Alternative 9a will likely decrease fishing use.

4.2.2.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

Impacts of the alternatives on wildlife and wildlife habitat are fully addressed in Technical Appendix N.

The more stable pool levels of alternatives 4c and 9c may provide long-term benefits for wildlife by re-establishing a narrow band of riparian vegetation in places along the lake's shoreline. Increased hunting and wildlife viewing opportunities could provide a small recreational benefit. None of the other alternatives would be likely to have a significant effect on wildlife when compared with 1a and 2c, and no change in wildlife hunting or viewing opportunities is expected.

4.2.2.6 Effects on Recreational Safety and Physical Characteristics

All alternatives except SOS 4c and 9c may have negative impacts on safety under low pool conditions. Most developed beaches will have no water. Under these conditions, people tend to swim in other exposed areas where they have access to the water. These areas may have safety hazards, such as steep banks and exposed rocks.

4.2.2.7 Effects on Water Quality Parameters Influencing Recreation

During certain periods of the year, as the pool is rapidly filling, temporary turbidity problems develop in the upper reservoir. No significant change in this condition from the base case (1a) and the no-action (2c) alternatives would be expected under 1b, 2d, 5b, 5c, 6b, 6d, 9a, 9b, and the preferred alternative (PA).

Water quality should improve in the reservoir under the stable pool targets of SOS 4c and 9c since the pools are held at a higher level for more of the season. This should reduce turbidity and erosion of the banks.

4.2.2.8 Effects on Aesthetics

Lake Koocanusa is in a narrow river canyon for most of its length. Small vertical drawdowns of the pool expose large expanses of unvegetated banks, mudflats, and debris deposits, which are unsightly. During deep drawdowns, large sandy plains are exposed along the upper half of the reservoir. Wind-driven dust develops along the eastern shore of the lake around Tobacco Flats and Rexford. These effects can occur under all alternatives. But the timing, extent, and duration will vary. Aesthetics of the reservoir should improve under the longer, stable pools of SOS 4c and 9c. Alternative 9a would likely produce the most adverse effect on aesthetics.

4.2.2.9 Mitigation Opportunities

Many of the recreational facilities at Lake Koocanusa – including boat docks, moorages, and swimming beaches – can be modified to make them usable over a wider operational range. Some boat ramps have already been extended to their lowest practical limits. Modification of recreation facilities should be considered for all alternatives except SOS 4c and 9c. Due to physical constraints, it isn't possible to modify all the existing sites on the lake, especially those on the upper end which are exposed by drawdowns exceeding 20 feet.

The most important mitigation would be extending or relocating the developed swimming beaches at Rexford Bench and McGillvray Recreation Areas to lower pool elevations, providing safe swimming when the pool is drawn down 20 ft below full pool. If these facilities are extended into lower pool elevations, the recreational season at Libby could be increased. Alternative swimming areas could also be developed at nearby lakes, or a swimming pool could be built.

Revegetation of the varial zone around the upper end of the reservoir and on the flats around Rexford and Eureka would improve aesthetic quality and fish and wildlife habitat conditions, and would reduce dust problems.

4.2.3 KOOTENAI RIVER BELOW LIBBY DAM

4.2.3.1 Description/Hydrologic Characteristics

Fishing is the primary recreational activity on the Kootenai River below Libby Dam. So fishing is used in this analysis to represent the impact of the alternatives to all recreational activities. There are two optimum flow ranges for fishing – one for shoreline fishing and one for boat fishing.

Shoreline fishing. The preferred flows for bank fishing are from 4,000 to 8,000 cfs (110 to 220 cms), although angling up to 10,000 cfs (280 cms) remains good. This range narrowly channels the water, allowing fishers access to fishing holes. Higher flows fill the river from bank to bank, severely limiting access to bank fishing. Higher flows will also drive the trout fisher's lure right into bank upon casting. Flows much above this range will drive most shoreline fishers away.

Boat fishing. Boat anglers prefer higher flows ranging from 8,000 to 14,000 cfs (220 to 400 cms), preferring those at the top of the range. Flows below that range, down to the minimum release from Libby Dam of 3,000 cfs (85 cms), become increasingly more difficult and dangerous for boating. Flows above 15,000 cfs also become increasingly difficult and dangerous for boating and for holding over fishing holes. Boat angling can continue to occur at much higher flows, however. The upper limit for successful boat fishing is probably around 25,000 cfs (510 cms).

The optimum flow for all water-related activities on the Kootenai river below Libby Dam is probably a steady flow in the range of about 6,000 to 8,000 cfs. A key element for both shoreline and boat fishing is stable flows over the longest possible period. The historically high daily and weekly fluctuations in releases from Libby Dam associated with power peaking have been detri-

mental to angling success and other activities in the past.

Fishing guides in the Libby area have reported to Corps project staff that the high flows released in the summer of 1994 to promote sturgeon spawning in the Kootenai River created some of the best boat fishing they have ever seen in the section of the river immediately below the dam. This improvement is attributed to the fact that, while the flows were extremely high (greater than 18,000 cfs), they were released at a constant rate. The success experienced under these faster flows was applicable to boat fishing only – conditions were no good at all for shore fishing. In addition, the benefits of the higher flow applies more to experienced boat fishers with more powerful and better equipped boats.

Average monthly flows (in kcfs) under each of the alternatives during the peak recreation season are shown on Table 4–6. These flows reflect releases from Libby Dam under the alternatives. As shown average monthly flows will vary substantially under the alternative, particularly in June when they range from a low of 7,800 cfs to a high of 26,800 cfs.

Creel surveys on the Kootenai River show that the peak use period for fishing is in June and July. The base case (1a) and no-action (2c) alternatives, as well as 1b, 2d, 5b, 5c, 6b, and 6d – should keep flows within a range that could be used by either shoreline or boat fishers (and sometimes both). The preferred alternative (PA) would be suitable for boat fishing in all months but June.

Estimated flows for 4c, 9a, 9b, and 9c within this period are well above the optimum range for June and July. The preferred alternative (PA) is well above the range in June. These alternatives could have significant negative impacts on shoreline fishing in the Kootenai River below Libby Dam.

Table 4-6. Average Monthly Kootenai River Flows (KCFS) During Summer Under Alternative SOSs

SOS	Average Monthly Kootenai River Flows			
	May	June	July	August 31
1a	7.0	9.3	12.1	9.3
1b	6.4	7.8	13.0	9.6
2c	7.0	8.3	12.3	9.1
2d	7.7	8.5	12.1	8.1
4c	4.3	19.2	19.6	7.7
5b, 5c, 6b, 6d	6.3	8.8	11.4	9.1
9a	16.4	26.8	21.2	8.8
9b	8.3	17.0	17.0	7.2
9c	4.5	19.3	19.7	7.7
PA	12.0	21.0	10.9	11.2

4.2.3.2 Quantitative results of Impact Assessment Models

Table 4-7 and Figure 4-2 present the results of the SOR recreation impact assessment model for the Kootenai River below Libby Dam. The model pro-

vides a quantitative estimate of fishing use in recreation days during low, average and high water years under each of the alternative SOSs. The table also compares the estimated fishing use for each SOS against the base case (SOS 1a), the no-action alternative (SOS 2c) and the historic 1992 to 1993 angling use at the Kootenai River.

Table 4-7. Kootenai River, Estimated Total Annual Recreation Days Under Alternative SOSs

Average Visitation (1987-1993): 33300 Baseline Visitation (11/92-10/93): 33300		Low Water Year (1941)	50 - Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a:	Total % change from 2c % change from Preferred Alternative % change from 92-93	36500 -19.61% 44.17%	34316 -3.71% 37.48% 3.05%	35064 5.16% 6.84%
SOS 1b:	Total % change from 1a % change from 2c % change from Preferred Alternative % change from 92-93	41996 15.06% -7.50% 65.87% 4.84%	34912 1.74% -2.03% 39.87% 4.84%	35431 1.05% 6.26% 7.96%
SOS 2c:	Total % change from 1a % change from Preferred Alternative % change from 92-93	45402 24.39% 79.33%	35636 3.85% 42.77% 7.02%	33343 -4.91% 1.59%
SOS 2d:	Total % change from 1a % change from 2c % change from Preferred Alternative % change from 92-93	46639 27.78% 2.73% 84.21% 5.29%	35062 2.17% -1.61% 40.47% 5.29%	26921 -23.22% -19.26% -17.97%
SOS 4c:	Total % change from 1a % change from 2c % change from Preferred Alternative % change from 92-93	54794 50.12% 20.69% 116.42%	34006 -0.90% -4.57% 36.24% 2.12%	30394 -13.32% -8.84% -7.39%
SOS 5b:	Total % change from 1a % change from 2c % change from Preferred Alternative % change from 92-93	36500 0.00% -19.61% 44.17%	34989 1.96% -1.82% 40.18% 5.07%	35064 0.00% 5.16% 6.84%
SOS 5c:	Total % change from 1a % change from 2c % change from Preferred Alternative % change from 92-93	36500 0.00% -19.61% 44.17%	34998 1.99% -1.79% 40.22% 5.10%	35064 0.00% 5.16% 6.84%
SOS 6b:	Total % change from 1a % change from 2c % change from Preferred Alternative % change from 92-93	36500 0.00% -19.61% 44.17%	34998 1.99% -1.79% 40.22% 5.10%	35064 0.00% 5.16% 6.84%
SOS 6d:	Total % change from 1a % change from 2c % change from Preferred Alternative % change from 92-93	36500 0.00% -19.61% 44.17%	34998 1.99% -1.79% 40.22% 5.10%	35064 0.00% 5.16% 6.84%

Table 4-7. Kootenai River, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 33300 Baseline Visitation (11/92–10/93): 33300		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 9a:	Total	7541	14270	19128
	% change from 1a	–79.34%	–58.41%	–45.45%
	% change from 2c	–83.39%	–59.96%	–42.63%
	% change from Preferred Alternative	–70.21%	–42.83%	–41.72%
	% change from 92–93		–57.15%	
SOS 9b:	Total	40965	28942	31495
	% change from 1a	12.23%	–15.66%	–10.18%
	% change from 2c	–9.77%	–18.79%	–5.54%
	% change from Preferred Alternative	61.80%	15.95%	–4.04%
	% change from 92–93		–13.09%	
SOS 9c:	Total	54794	33881	30394
	% change from 1a	50.12%	–1.27%	–13.32%
	% change from 2c	20.69%	–4.93%	–8.84%
	% change from Preferred Alternative	116.42%	35.74%	–7.39%
	% change from 92–93		1.74%	
PA	Total	25318	24960	32820
	% change from 1a	–30.64%	–27.26%	–6.40%
	% change from 2c	–44.24%	–29.96%	–1.57%
	% change from 92–93		–25.05%

Figure 4-2. Kootenai River, Estimated Fishing Use for Alternative SOSs (Low, Average & High Water Years)

Empirical estimation of the model is described in more detail in Appendix J-1. The model estimates angling use at the Kootenai River based on changes in operation of the system. Recreational use of the Kootenai River is influenced not only by changes in flows in the Kootenai River, but also by changes in pool elevations of other projects in the western Montana/northern Idaho region of the user survey. Both the Hungry Horse and the Kootenai River Models include Lake Koocanusa as a first stage complement. Meaning that based on the results of the user survey in the region, it is possible that a higher water level at Lake Koocanusa might increase a recreator's propensity to visit Hungry Horse or the Kootenai River because the higher water levels might produce a more satisfying

recreation experience, thereby increasing the likelihood of future trips. This relationship is described in more detail in Appendix J-1, Chapter 5.

The model also has some limitations. Predictions for the Kootenai River model tend to overestimate demand for instream flows that fall below the optimum range (i.e. below 4,000 cfs). This is a function of the "own water parameters" in the two-stage model (see Appendix J-1, chapters 4, 5 and 6 for a more detailed description of model parameters and estimation techniques). The parameter in the first stage of the model is negative, which means that based on the survey results, lower flow rates on the Kootenai River tend to increase the number of people who take trips. The

parameter in the second stage is positive, which means that higher flow rates tend to increase the average number of trips per person, conditional on taking at least one trip. At low flow rates, the net effect of these conflicting tendencies is that the model predicts a steady increase in visitation, even when the flow rate falls below an optimum level. However, at high flow rates, the tendency for fewer people to take trips outweighs the increasing average number of trips, so total visitation falls.

As described in Section 4.2.1.4, the model may not completely predict fish growth potential associated with changing operations and its affect on fishing demand.

Average Water Year. During an average water year, the relatively stable flows through the summer under SOS 2c, the No-Action alternative, provide better conditions for recreation on the Kootenai River than any other alternative, resulting in the highest estimated angling use. SOS 1a, the Base Case alternative, is similar with only an estimated 4 percent decline in use. The model results also show SOS 1b, 2d, 5b, 5c, 6b, and 6d to also be very similar, falling between SOS 2c and 1a in estimated visitation.

SOS 4c and 9c both result in slight to moderate decreases in visitation during average water years when compared with SOS 1a and 2c (approximately 1 to 5 percent, respectively). These declines are attributable to the relatively high flows in June and July under SOS 4c and 9c. In the case of SOS 4c, there would be a direct tradeoff with the recreational use of Lake Koocanusa; under that alternative, the lake would be filled in early spring to improve lake recreation conditions. The downstream impact would be increased flows during the spring freshet.

SOS 9b, the PA, and 9a all feature very high average flows in May, June and/or July. As a result, they would have moderate to severe recreational impacts with estimated losses in fishing use ranging from about 19, 30 and 60 percent, respectively, when compared with SOS 2c.

Low Water Years. During an extreme low water year (1941), slight to significant improvements in recreation conditions on the Kootenai River are expected under all of the alternative SOSs with the exception of SOS 9a. This is attributable to the fact that lower runoffs can be more easily maintained within the preferred range of flows for recreation. The most significant improvement would be under SOS 4c, 9b and 9c, which would all show an estimated increase of about 62, 42 and 62 percent, respectively, in total fishing use when compared with an average water year. The increase under these alternatives results from far lower and more stable flows released from Libby Dam during the spring and summer freshets of low water years. SOS 2c and 2d also result in moderate increases (approximately 30 percent) in total fishing use when compared with average water conditions. The remaining alternatives, including SOS 1a, 1b, 5b, 5c, 6c, 6d, and the PA, would result in a slight increase in total fishing use on the Kootenai River during a low water year as opposed to average water conditions.

In comparison, SOS 9a, which is the worst alternative for recreation under average water conditions, would be even poorer during low water conditions. The estimated loss in fishing use during a low water year when compared with SOS 2c is over 80 percent.

High Water Years. Under most of the alternative, including SOS 1a, 1b, 5b, 5c, 6b, 6d, 9a, 9b and the PA, high water conditions would be slightly better than average conditions, but not quite as good as low water conditions. Under SOS 9a and the PA, estimated fishing use would be substantially higher during wet years than either average or dry years.

Under SOS 2c, 2d, 4c, and 9c, estimated fishing use would decline significantly during wet years. Loss of visitation in wet water years may be greater for these alternatives because flows are kept higher and longer in the season to accommodate for increased inflows. This is detrimental to both boat and bank fishermen. In wet years, these flows can exceed 14,000 cfs (400 cms) for 8 months.

4.2.3.3 Effects on Recreation Facilities/Activities

River flows have a much more direct affect on use of the river for shoreline and boat angling and on angling success than on the usability of recreation facilities. The only recreation sites on the Kootenai River downstream from Libby Dam are primitive, with minimal boating facilities consisting of gravel boat ramps. Most of the ramps remain fully usable from high to low flows. No fixed or floating boat docks, marinas, or developed swimming beaches are effected by changing flows.

Alternatives 4c, 9a, 9b, 9c, and the preferred alternative (in June only) will substantially increase flows in peak fishing season. It is difficult to estimate the impact of these changes on all recreational use and facilities without more detailed information concerning short-term peak flow magnitude and duration. But they will definitely have a negative impact on fishing-related recreation during these two critical months.

4.2.3.4 Effects on Fish Habitat and Fishing Success

The timing and duration of releases from Libby Dam have a significant effect on fish feeding habits and, consequently, on fishing success on the Kootenai River. The rapid changes in flow typically followed for power peaking change the feeding patterns of fish, making them difficult to catch. Historically, Libby Dam operations have tried to drop flows to 8,000 cfs (225 cms) on weekends and holidays. These flows were maintained from 3 hours before sunrise to 1 hour after sunset from May 1 to September 15, when practicable, to enhance fishing below the dam. Even under these special operations, anglers expressed concern that flows must remain stable for 24 hours or more before trout will settle back into feeding lanes and allow reasonable fishing success. In recent years, anglers have expressed concern that reducing flows over the entire weekend still did not provide adequate time to allow fish to settle into feeding patterns.

The hydroregulation models used for all alternatives are average monthly outflows from Libby Dam. They cannot be used to forecast information for shorter term weekly and daily operations.

The flows for alternatives 1a, 1b, 2c, 2d, 5b, 5c, 6b, and 6d should be beneficial for the fish habitat in the river because they show a more stable flow pattern. This allows the fish to keep a more normal feeding pattern without the excessive increases and decreases that can happen under other alternatives.

The flows for SOS 4c, 9a, 9b, 9c, and the preferred alternative (PA) may all have a negative impact on fishing success because of the potentially very high flows in the river during the peak recreation season. However, SOS 4c and 9c are designed to restore the high spring and early summer freshets that naturally occurred on the river prior to construction of Libby Dam. These flows are expected to improve fish habitat.

4.2.3.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

As discussed in SOR Technical Appendix N, there would be no significant difference between any of the alternatives for wildlife habitat. Thus, no significant impacts to wildlife hunting and viewing opportunities on the river are anticipated.

4.2.3.6 Effects on Recreational Safety and Physical Characteristics

The stable flows under SOS 1a, 1b, 2c, 2d, 5b, 5c, 6b, and 6d would be positive for recreation safety on the river because anglers, boaters, and rafters would not be subject to the radical shifts in flows which can be very unsafe. This is especially true downstream at Kootenai Falls, a popular fishing area.

The less stable flows under SOS 2d, 4c, 9a, 9b, 9c, and the PA would have a negative effect on recreation safety on the river because anglers, boaters, and rafters would be subject to greater shifts in the flows.

4.2.3.7 Effects on Water Quality Parameters Influencing Recreation

Radical changes in flows from Libby Dam can significantly increase turbidity downstream, with negative effects on fishing success and aesthetics. The more stable flows under SOS 1a, 1b, 2c, 2d, 5b, 5c, 6b, and 6d could benefit water quality by reducing turbidity.

But the more radical swings in releases under the other alternatives could increase turbidity.

4.2.3.8 Effects on Aesthetics

The aesthetics of the river would be neutral or may slightly improve under most alternatives because

the river is being managed in a naturally occurring pattern, allowing flows to occur during the appropriate seasons. This creates the image of a natural river rather than a regulated river.

4.2.3.9 Mitigation Opportunities

Improved boating access areas could be built at several of the Corps' undeveloped sites just downstream from the dam, such as Blackwell Flats. It's also possible at other sites closer to the town of Libby.

Fishing piers could also be built out into the river to provide better access for the bank fishermen who are now detoured because of high water levels.

4.2.4 COLUMBIA RIVER IN CANADA

4.2.4.1 Descriptive/Hydrologic Characteristics

The Columbia River below the confluence of the Kootenay River is one of only three remaining undammed river reaches on the mainstem Columbia (the others are the 120 mile (200 Km) reach in Canada above Kinbasket Lake from Donald Station to the headwaters at Canal Flat, and the Hanford Reach). This reach is regulated by the outflow of Hugh Keenleyside Dam on the Columbia River and Brilliant Dam on the Kootenay River. Operation of these dams by B.C. Hydro is influenced by operation of the Federal system covered under the SOR. Hence, while this reach is outside of the geographic scope of the SOR, potential recreational impacts of the alternative SOSs are evaluated.

Keenleyside Dam bisects the original Lower Arrow Lake approximately 10 kilometers (6 miles) upstream from the lake's natural hydraulic control

point. Water discharged from Keenleyside Dam flows 10 kilometers through the original Lower Arrow Lake before entering the free-flowing portion of the Columbia River. About a half kilometer downstream the Columbia is joined by the Kootenay River. Brilliant Dam is located on the Kootenay River approximately 2 kilometers upstream from where it joins the Columbia. After the confluence this stretch of the Columbia flows another 44 kilometers (27.5 miles) before it is joined by the Pend Oreille River. One half kilometer below the confluence with the Pend Oreille River, the Columbia River crosses the Canada/United States International Boundary. Approximately 24 kilometers downstream (15 miles) the Columbia River enters lake Roosevelt in Washington State. The analysis undertaken in Section 4.2.4 covers to the portion of the free-flowing Columbia River between the Hugh Keenleyside Dam and the International Boundary.

Table 4-8. Upper Columbia River, Canada — Average Monthly Outflows (KCFS) for Alternative SOSs (Combined Releases from Keenleyside and Brilliant Dams)

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	86.6	69.0	63.4	50.6	72.3	75.0	80.5	73.9	62.4	51.3	36.5	51.4
1b	102.0	84.8	55.9	47.7	76.0	86.5	91.5	76.6	55.7	55.3	53.6	70.6
2c	107.0	87.1	51.6	51.3	84.1	87.2	83.6	77.2	56.6	47.8	56.5	68.3
2d	81.1	69.6	62.2	44.9	69.2	108.2	106.8	76.6	58.0	47.9	56.1	69.1
4c	95.3	82.0	65.2	54.4	78.4	88.1	94.2	73.9	48.9	47.5	48.4	76.5
5b	107.7	87.1	51.9	51.0	83.8	87.3	83.0	77.2	55.7	47.7	56.4	68.8
5c	107.7	87.1	51.9	51.0	83.8	87.3	83.0	77.1	55.7	47.7	56.4	69.4
6b	107.7	87.1	51.9	51.0	83.8	87.3	83.0	77.2	55.7	47.7	56.4	69.4
6d	107.7	87.1	51.9	51.0	83.8	87.3	83.0	77.2	55.7	47.7	56.4	69.4
9a	101.8	86.4	50.5	50.8	90.2	103.4	98.0	78.1	47.6	42.2	44.7	65.7
9b	81.3	75.6	68.9	80.9	74.4	103.2	105.7	76.1	41.4	44.3	43.0	78.5
9c	83.3	74.7	63.4	47.1	70.6	102.5	108.9	76.9	48.8	45.1	52.9	77.7
PA	88.9	79.1	64.9	45.9	72.1	106.5	100.8	81.4	49.9	43.1	49.6	74.2

The optimum flow of the Columbia River for recreation use varies depending on the recreation activity under consideration. The estimated optimum flows for the different types of recreation activities are as follows:

swimming	—	78,000 to 99,288 cfs (2,200 to 2,800 cms)
sightseeing	—	14,184 to 102,834 cfs (400 to 2,900 cms)
boat fishing	—	70,920 to 156,024 cfs (2,000 to 4,400 cms)
shore fishing	—	60,282 to 99,288 cfs (1,700 to 2,800 cms)
nonmotorized boating	—	70,920 to 102,834 cfs (2,000 to 2,900 cms)

Flows ranging between 70,920 and 99,288 cfs (2000 to 2,800 cms) constitute the optimal range for general recreation use on the river.

The average combined monthly flows from the Hugh Keenleyside and Brilliant dams under the alternative SOSs are shown on Table 4–8. Under all strategies, flows are lowest in November and peak in June or July.

Under **SOS 1a**, average monthly flows are at their lowest in April. They are held relatively stable between about 72 and 80 kcfs (2000 and 2300 cms) during the four month peak recreation season of May through August, with peak flow in July. Flows drop off somewhat in September and October, and then substantially in November. The major difference between **SOS 1a** and **SOS 1b** during the recreation season is that under the latter, average flows are substantially higher (11 kcfs; 300 cms) in June and July, and lower (7 kcfs; 200 cms) in September.

In comparing **SOS 2c**, the no-action alternative, with **SOS 1a**, the base case alternative, average flows under 2c are substantially higher (12 kcfs; 340 cms) in May and June and slightly higher in July and August. Flows drop off considerably in September and October, which is the minimum flow month under the strategy.

SOS 2d varies considerably from any of the other alternatives and would range substantially across the summer recreation season. Flows would be lower than any other alternatives in April and

May, and then higher than any other alternatives in June and July. These unstable flows would have significant negative impacts on recreation as described in following sections.

SOS 4c would be similar to **SOS 1a** and **1b** except for moderately higher flows in April, May and June, and moderately lower flows in September and October. These differences reflect the operation of Libby Dam on the Kootenai River in the US. Under **SOS 4c**, that project is brought up earlier in spring to improve its recreation condition, resulting in less flood control storage space and slightly higher downstream flows during the peak spring runoff. Likewise, Lake Koocanusa is held up longer during the summer, resulting in lower downstream releases in late summer and early fall. The resulting flows have some negative impacts on recreation conditions on the upper Columbia River. These impacts would be slight during low flow years, but would be more significant in average to high flow years.

Flows in the upper Columbia River are the same under **SOS 5b**, **5c**, **6b**, and **6d**. All of these options are very similar to **SOS 2c**.

The most significant feature of **SOS 9a** would be a very large jump (40 kcfs; 1100 cms) in average monthly flows from April to May. Flows would remain high from May through August and then would take another large jump (30 kcfs; 850 cms) back down in September. Flows in September, October and November would be lower than most of the other alternative SOSs.

SOS 9b is characterized by much higher flows in March and April than any of the other alternatives (30 kcfs; 850 cms in April compared with **SOS 1a** and **2c**). Flows would be dropped slightly in May, and then increased rapidly again in June. High flows would be maintained in June and July. Flows from September through November would be very low. September would have lower flows than any other alternative SOS. During average water years, this operation would have slightly negative impacts on recreational suitability of the reach. Impacts would be more severe during either high or low water years when river flows would fluctuate more wildly.

SOS 9c would be similar to SOS 9b with the exception of much lower flows (33 kcfs; 900 cms) in April and somewhat higher flows in September. SOS 9c would feature the highest average July flows of any of the alternative SOSs, nearly 30 kcfs (850 cms) higher than either SOS 1a or 2c. The extremely high summer flows would have some significant negative impacts on recreation. This is probably the worst alternative for recreation during high flow years.

The **Preferred Alternative** would be similar to SOS 2d, featuring relatively low flows in April with large jumps in May and again in June. High monthly flows would be retained June through August. Under the PA, average flows in August flows would be higher than under any other alternative.

4.2.4.2 Summary of Quantitative Impacts

The recreation survey and impact assessment models described in Appendix J-1 did not include the reach of the Columbia River in Canada. A separate model was, however, developed for this reach. The Columbia River recreation impact assessment model (IAM) was designed to estimate use by primary water-based recreational activity (boating, fishing, swimming, and camping/picnicking) on an annual basis. The methodological structure of this model is based on a simple relationship between stream flows and expected participation (usage) in each recreation activity. Changes in flow above and below preferred flow ranges for each activity are known to produce undesirable effects (i.e. velocity hazards and inundation of facilities at extreme high flows vs. dewatering of facilities and exposure of rocks, shoals and other hazards at extreme low flows. Use (visitation) in a particular recreation activity was assumed to decline in direct response to, and correlate with changes in flow above and below optimum. Such "break-point" relationships were established or adopted for flow ranges at which the relationship between an flow and recreation usage are quantified.

In general, the break-points were estimated based on the best professional judgment and knowledge of RWG members and resource managers familiar

with the project areas. The assumptions, justification, rationale, and data applied in developing recreation activity break-point relationships for the Columbia River are documented in the SOR Draft EIS, Appendix J (July 1994).

Break-points were developed for boat fishing, shore fishing, swimming, non-motorized boating, and sightseeing for this Canadian stretch of the Columbia River. Local fishers participating in a fishing diary project sponsored by the Trail (Canada) Wildlife Association were instrumental in developing the break-points for shore and boat fishing. Boat and shore fishing break-points are based on access considerations (usability of launching facilities, hazards, and the availability of shore fishing perches) and an indicator for fishing quality (back eddy structures). Since the bulk of the swimming occurs at the Gyro Park swim rapids, local swimmers who frequent the area were consulted to develop appropriate swimming break-points. Similarly, non-motorized boating and sightseeing break-points were developed through discussions with local river sightseers and nonmotorized boaters in conjunction with hydrologic records.

Table 4-9 and Figure 4-3 present the results of the SOR recreation impact assessment model developed for the Columbia River in Canada. The model provides a quantitative estimate of recreation use in recreation days for key water related recreation activities during low, average and high water years under each of the alternative SOSs. Table 4-10 compares the estimated total recreation use for each SOS against the base case (SOS 1a), and the no action alternative (SOS 2c).

Generally speaking, for most of the alternative SOSs, recreation conditions on the upper Columbia River are expected to be best under average water years, followed by low water years, then by high water years. This relationship is supported by the model results, which predict that visitation will be highest under average water years. Low water years tend to have a higher suitability for recreation than do high water years because lower flows during those conditions typically are more conducive to recreation activities occurring in this reach.

Table 4-9. Upper Columbia River, Canada, Estimated Annual Recreation Days by Activity

SOS	Estimated Annual Recreation Days by Activity					
	Swimming	Sightseeing	Boating	Boat Fishing	Shore Fishing	Total
SOS 1a						
Low Water Year	4761	12362	3767	3564	12540	36994
50-Year Average	7727	12362	3959	3818	12787	40653
High Water Year	3048	11595	3065	3771	11186	32665
SOS 1b						
Low Water Year	3659	12362	3814	3555	12336	35726
50-Year Average	8758	12362	3959	3783	12658	41520
High Water Year	3048	11595	2820	3720	10601	31784
SOS 2c						
Low Water Year	4761	12362	3837	3624	12508	37092
50-Year Average	8758	12362	3959	3797	12708	41584
High Water Year	3047	11595	2994	3797	10933	32366
SOS 2d						
Low Water Year	2856	12106	3650	3628	12179	34419
50-Year Average	5817	11982	3708	3763	11902	37172
High Water Year	3048	11024	2261	3660	9226	29219
SOS 4c						
Low Water Year	2627	12362	3640	3260	11871	33760
50-Year Average	7727	12362	3960	3756	12556	40361
High Water Year	3048	11309	2624	3733	10322	31036
SOS 5b						
Low Water Year	5411	12362	3837	3606	12304	37520
50-Year Average	8758	12362	3959	3780	12647	41506
High Water Year	3048	11595	3191	3813	11317	32964
SOS 5c						
Low Water Year	5411	12362	3837	3608	12310	37528
50-Year Average	8758	12362	3960	3782	12653	41515
High Water Year	3048	11595	3191	3810	11307	32951
SOS 6b						
Low Water Year	5411	12362	3837	3606	12304	37520
50-Year Average	8758	12362	3959	3780	12647	41506
High Water Year	3048	11595	3191	3813	11317	32964
SOS 6d						
Low Water Year	5411	12362	3837	3606	12304	37520
50-Year Average	8758	12362	3959	3780	12647	41506
High Water Year	3048	11595	3191	3813	11317	32964
SOS 9a						
Low Water Year	6091	11978	3707	3705	11765	37246
50-Year Average	8373	12362	3960	3725	12303	40723
High Water Year	3048	11429	2804	3756	10471	31508
SOS 9b						
Low Water Year	2094	11978	3566	3597	11928	33163
50-Year Average	7340	12238	3904	3779	12144	39405
High Water Year	914	11226	2715	3798	10345	28998
SOS 9c						
Low Water Year	2856	12106	3650	3590	12039	34241
50-Year Average	6650	12114	3797	3727	11911	38198
High Water Year	914	11024	2424	3657	9481	27500
SOS PA						
Low Water Year	3659	12362	3818	3687	12812	36338
50-Year Average	7270	12234	3876	3724	12027	39131
High Water Year	914	11309	2668	3624	9760	28275

Figure 4-3. Columbia River, Canada, Estimated Visitation for Alternative SOSs (Low, Average, & High Water Years)

Table 4-10. Estimated Total Annual Recreation Days and Percent Change from No Action (2c) and Base Case (1a) SOSs, Upper Columbia River, Canada

SOS	Total/Percent Change	Low Water (1941)	50-Year Average	High Water (1976)
1a	Total Δ from 2c	36993 -0.3	40653 -2.3	32664 0.9
1b	Total Δ from 1a Δ from 2c	35725 -3.4 -3.7	41521 2.1 -0.2	31784 -2.7 -1.8
2c	Total Δ from 1a	37092 0.3	41584 2.3	32368 -0.9
2d	Total Δ from 1a Δ from 2c	34418 -7 -7.2	37174 -8.6 -10.6	29218 -10.6 -9.7
4c	Total Δ from 1a Δ from 2c	33761 -8.7 -9.0	40359 -0.7 -2.9	31035 -5.0 -4.1
5b	Total Δ from 1a Δ from 2c	37520 1.4 1.6	41507 2.1 -0.2	32964 0.9 1.8
5c	Total Δ from 1a Δ from 2c	37527 1.4 1.2	41513 2.1 -0.2	32950 0.9 1.8
6b	Total Δ from 1a Δ from 2c	37520 1.4 1.2	41507 2.1 -0.2	32964 0.9 1.8
6d	Total Δ from 1a Δ from 2c	37520 1.4 1.2	41507 2.1 -0.2	32964 0.9 1.8
9a	Total Δ from 1a Δ from 2c	37246 0.7 0.4	40727 0.2 -2.1	31507 -3.5 -2.7
9b	Total Δ from 1a Δ from 2c	33162 -10.4 -10.6	39046 -3.1 -5.2	28999 -11.2 -10.4
9c	Total Δ from 1a Δ from 2c	34241 -7.4 -7.7	38198 -6.0 -8.1	27500 -15.8 -15.0
PA	Total Δ from 1a Δ from 2c	36338 -1.7 -2.0	39131 -3.8 -5.9	28275 -13.4 -12.7

The models, however, are based on considerations for access to the river and the usability of recreation facilities under various flow conditions. They do not address the effects of flow on fish habitat and the subsequent effects on fishing and fish catching success. High water years generally provide better conditions for fish habitat and hatching success of fish in the river which can influence catch rates by fishermen and ultimately impact recreation activity.

Based in the model results, the alternative SOS under consideration can be separated into five groups in which the degree of recreational impacts will be similar. These groups are:

slight improvement	SOS 5b, 5c, 6b, and 6d
minimal impact	SOS 1a and 2c
slight negative impact	SOS 1b and 9a
moderate negative impact	SOS 4c, 9b, and PA
severe impact	SOS 2d, and 9c

SOS 1a and 2c are the base case and no action alternatives, respectively. These alternatives are very similar for recreation in the upper Columbia River. The model predicts a slight improvement in recreation conditions under SOS 2c in comparison to SOS 1a, except for high water years when SOS 1a is better by a very slight margin.

During average water years, **SOS 5b, 5c, 6b, and 6d** would all be a slight improvement over SOS 1a and would be worse than SOS 2c by a very slight margin. However, during either high or low water years, these alternatives would have more stable flows throughout the peak recreation season and would result in slight improvements in recreation conditions compared to both SOS 1a and 2c.

SOS 1b is very similar to SOS 2c during average water years and slightly better than SOS 1b. However, water levels during the peak recreation season would fluctuate more wildly during either low or high water years and there would be some slight negative impacts to recreation suitability at those times in comparison with the base case and no action alterna-

tive. The same is true of SOS 9a, but negative impacts would occur during high flow years only.

Moderate negative recreational impacts would occur under **SOS 4c, 9b and the PA** during average water years. SOS 4c and the PA would have only slight negative impacts during low flow years when flood control operations in Lake Koocanusa are less impacted. During average and high flow years, high spring and early summer releases followed by low late summer and early fall flows would have moderate to severe impacts on the recreational suitability of the reach. In comparison, SOS 9b impacts would be moderate during average flow years, but would become much more severe during both high and low flow conditions. SOS 9b would be the worst overall alternative during low flow conditions, primarily due to very low flows in all months except June.

SOS 2d and 9c would have the most severe impacts on recreation along the upper Columbia River. SOS 2d is the worst alternative for average water years, followed closely by 9c. SOS 9c is the worst alternative for recreation during high water years, followed closely by the PA. The main detractor under these SOSs would be extremely high flows during the entire summer recreation season during wet years.

4.2.4.3 Effects on Recreation Facilities/Activities

In average water years SOS 1a, 1b, 2c, 5b, 5c, 6b, 6d, and 9a, would all have little or no impact on recreation facilities and activities in the upper Columbia River reach. During average water years under these SOSs, flows are generally within in the optimal band of 70 to 100 kcfs (2000 to 2800 cms) for recreation facilities and all boat ramps, boat docks and swim beaches are not impacted. Conditions for "floatability", "experience" and "shore fishing access" are also within their optimal range. In comparison, flows under SOS 2d, 9b, 9c and the PA all substantially exceed the optimum during June and/or July and have more severe impacts on these characteristics.

In high water years all 13 SOSs would considerably exceed the optimum flow for recreation for more than one summer month. Boating facilities (ramps and boat docks) are generally less sensitive to high flows than other facilities in the reach and would not be seriously impacted by high water levels. Other facilities, including swim beaches, floatability of the river, experience and shore fishing access, are adversely impacted in July and August by river flows in excess of 100 kcfs. Poor alternatives for recreation under high flows are SOS 9c, PA, 9b, 2d and 4c, in that order. July and August flows under SOS 9c in a high water year (1976) would run approximately 50 percent higher than optimum.

Recreation conditions in the upper Columbia River reach are generally more conducive during low water years. The impacts of the alternative SOS on recreation facilities and activities under low water vary depending on the month. In general SOS 9b, 9c, and 2d are the only alternatives that would result in moderate impacts to recreation during a low water year (1941). Under all alternatives, in June all three of the boat ramps and both of the boat docks, as well as the swim beaches, are fully usable. In addition, the conditions for floatability, experience and shore fishing access are good. By July, only two of the three boat ramps and one of the two mooring docks are fully usable and conditions for floatability and swim beaches are sub-optimal. Conditions for experience and shore fishing access remain good. In the month of August there are no impacts on recreation activities and facilities, but the swim beaches are not fully usable because of low flows.

4.2.4.4 Effects on Fish Habitat and Fishing Success

In analyzing the effects of the alternative SOSs on fish habitat, a strategy was deemed to be positive in terms of fish if river flows were either stable or increasing during the spawning, incubation, and rearing time period for rainbow trout of April 15 to August 15. Declining water levels during the identified critical period for trout were assumed to cause the dewatering of rainbow trout redds and/or fry. The effects of all SOSs on fish habitat in the mainstem Columbia and Kootenay rivers above their confluence was negative in

low, average and high water years. Under all system operating strategies water levels would decline at various times during the critical period at the identified spawning areas of the Norns Creek fan located just downstream of the Hugh Keenleyside Dam and the Kootenay River below the Brilliant Dam.

During low water years portions of the braided channel spawning area, located adjacent to the village of Genelle, B.C., are dewatered at different times during the critical time period of April 15 to August 15. But, during average and high water years, with the exception of SOS 1b, all system operating strategies generally provided enough flow to protect the mainstem fish habitat. During the spawning, incubation and rearing period water levels are either generally stable or increasing. Under average and high water years the areas of fish spawning, incubation and rearing at the braided channel are thought to remain covered with water.

SOS 1b is the only system operating strategy that may have a negative impact on fish habitat below the confluence of the Columbia and Kootenay rivers in high water years. Under SOS 1b water levels decline roughly 10,000 cfs from April 15 to 30 which may dewater some rainbow trout redds in the mainstem of the river. Under SOS 1b, flows during the rest of the critical period are increasing so the negative impacts occur only in the month of April.

This assumes a straight line relationship between the end of month outflows from the Hugh Keenleyside and Brilliant dams. For example, if the outflow for the end of May is 2,000 cms and for the end of June is 2,500 CMS, it is assumed that there are not wide swings in discharge only a steady increase between the two. If wide swings are the reality on a daily and weekly basis then it is likely that all the system operating strategies in low, average and high water years have a negative impact on fish habitat.

4.2.4.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

There appears to be no significant difference between any of the alternative SOSs in terms of impacts on wildlife habitat or hunting or wildlife viewing success.

4.2.4.6 Effects on Recreational Safety and Physical Characteristics

There are no negative effects of the SOSs on recreational safety and physical characteristics in low and average water years. In high water years during the months of July and August flows may be sufficiently high under all the strategies to pose safety problems for boaters. This would also be a particular problem under SOS 9c, PA, 9b, 2d and 4c.

4.2.4.7 Effects on Water Quality Parameters Influencing Recreation

Water quality parameters indirectly affect recreation on this reach. Depending upon whether or not water is spilled, or passed through the "low level ports" at Keenleyside Dam or powerhouse at Brilliant Dam, total gas pressure (TGP) readings downstream can exceed provincial water quality objectives. High TGP levels have a detrimental effect on fish and in some cases can be lethal. Local anglers claim that high TGP levels affect where fish hang in the water column. The impact of reduced fish health and altering the fish locations in the river is reduced fish catch rates.

4.2.4.8 Effects on Aesthetics

In the month of August in high water years flows are sufficient to inundate most of the islands, beaches and foot paths along the river which detracts from its aesthetics. These impact would be exacerbated under SOS 9c, PA, 9b, 2d and 4c.

Low flows may expose a number of derelict vehicles in the river downstream of the city of Trail. Algae growths on the west bank of the river immediately downstream of the city of Trail, is also an aesthetic problem in low water years.

4.2.4.9 Mitigation Opportunities

In order to reduce the impacts of the alternative SOSs, some mitigating actions could be undertaken. The extension of the concrete boat ramp at Indian Eddy would increase the use of this important facility at low river flows. In conjunction with the

ramp extension, the mooring docks could also be reconfigured and extended to improve the use of this facility. Dredging of some large river cobbles at the entrance to Indian Eddy would improve general access to the facility at low flows.

The construction of mooring docks at the Beaver Creek boat launch would improve the use of this facility at high river flows. The mooring docks would improve the ease of loading and unloading boats during high flows when river currents complicate the use of this facility.

The Canada Customs dock at Trail, which was destroyed by the high flows of 1991, could be rebuilt in a manner that allows it to accommodate high river flows. Low flows do not pose a problem for a dock at this site.

In order to reduce the impacts of the system operating strategies on fish habitat, and consequently on fishing success, certain mitigation opportunities may be undertaken. Given that the flow alternatives will impact mainstem spawning, incubation, emergence and rearing habitat these effects may be partially offset by improving like habitat on the tributary streams downstream of the Hugh Keenleyside and Brilliant dams. The construction of regulated flow spawning channels using water from the major tributary streams should be undertaken. Opportunities to construct these channels exist at Murphy, Blueberry and Beaver Creek. As a means of reducing the dewatering of fry at the Norns Creek fan, this structure could be reconfigured to reduce the pooling of water and fry that occurs as water levels drop. The improvement of fish habitat and the reduction of blockages to upstream migration in the other tributary streams should also be pursued.

While the dewatering of mainstem fish habitat below the confluence of the Columbia and Kootenay rivers does not appear to occur in average and high water years, the stabilization of daily flows from upstream dams to limit rapid fluctuations must also occur. Given the heavy use of this habitat by Lake Roosevelt fish stocks, the implications of these flows and this mitigation package will be felt downstream of this stretch of the Columbia in Washington State.

4.2.5 HUNGRY HORSE RESERVOIR

4.2.5.1 Description of Hydrologic Characteristics

Recreational suitability of Hungry Horse Reservoir is primarily affected by the timing of drawdown and refill. The suitability of the reservoir for recreation is at its optimum when the reservoir is at or near full pool (elevation 3,560 feet). Most of the recreational facilities (all boat ramps on the lake) lake remain fully usable within the upper eight feet of the pool (above elevation 3,552 feet). Drawdowns in excess of that level will begin to reduce the recreational suitability of the reservoir. Extreme drawdown during the peak summer recreation season will substantially reduce anticipated recreational use.

Table 4-11 shows the average monthly pool elevations (as measured at the forebay of Hungry Horse Dam) under the 13 alternative SOSs. As shown, under all of the alternatives, the reservoir is at its minimum in March or April and then is gradually refilled, reaching its peak in July. Drawdown of the reservoir generally begins by August and by the end

of September the reservoir is well below full pool with the exception of SOS 4c and 9c.

Table 4-12 compares the percent probability (over the fifty year period of record) that Hungry Horse Reservoir will be refilled to selected elevations ranging from the optimum recreation pool of 3,558 feet (two feet below full) down to elevation 3,540 feet over the peak recreation months of May through August.

SOS 1a is the Base Case alternative. This SOS is not a particularly good operation for recreation at Hungry Horse Lake. The average pool elevations during June through August range from 20 to 25 feet below full. The probability of refill to within two feet of full pool at any time during the summer is only approximately 60 percent.

SOS 1b optimizes power production across the system with only minimal constraints on reservoir operation. It is similar to SOS 1a, with pool elevations generally about four to six feet (1.2 to 1.8 meters) lower during the summer. The timing of the refill and drawdown for both strategies is identical. The two operations are within 2 percent of each other when comparing refill timing end of month pool elevation and number of years (probability) of refill.

Table 4-11. Hungry Horse Reservoir — Average Monthly Pool Elevations

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	3481	3468	3456	3459	3505	3535	3540	3534	3514	3506	3504	3497
1b	3479	3463	3449	3451	3499	3532	3537	3531	3509	3506	3503	3498
2c	3482	3470	3462	3465	3506	3537	3542	3534	3517	3510	3508	3500
2d	3482	3470	3462	3465	3506	3537	3542	3534	3517	3510	3508	3500
4c	3517	3507	3497	3503	3533	3559	3560	3559	3557	3552	3549	3536
5b	3481	3468	3456	3457	3502	3533	3540	3534	3514	3506	3504	3497
5c	3481	3468	3456	3457	3502	3533	3540	3534	3514	3506	3504	3497
6b	3481	3468	3456	3457	3502	3533	3540	3534	3514	3506	3504	3497
6d	3481	3468	3456	3457	3502	3533	3540	3534	3514	3506	3504	3497
9a	3471	3467	3461	3449	3471	3507	3501	3481	3480	3478	3478	3476
9b	3530	3521	3508	3492	3525	3550	3550	3542	3541	3540	3538	3536
9c	3517	3507	3497	3503	3533	3559	3560	3559	3557	3552	3549	3536
PA	3530	3522	3509	3493	3526	3553	3550	3541	3539	3538	3538	3536

Table 4-12. Hungry Horse Reservoir — Percent Probability of Refill to Selected Pool Elevations

Pool Elevation (ft. NGVD)	Month															
	May				June				July				August			
	3558	3555	3550	3540	3558	3555	3550	3540	3558	3555	3550	3540	3558	3555	3550	3540
SOS	Percent Probability of Refill to Selected Pool Elevations															
1a	0	0	2	12	16	46	70	76	62	64	72	74	54	58	70	72
1b	0	0	2	12	16	42	68	70	60	64	72	72	52	56	64	70
2c	0	0	0	2	12	42	70	76	54	62	76	78	40	54	64	70
2d	0	0	0	0	2	12	42	70	56	56	64	80	38	42	54	64
4c	0	0	4	32	82	90	96	96	100	100	100	100	100	100	100	100
5b	0	0	0	4	6	34	68	76	56	62	72	74	50	56	70	72
5c	0	0	0	0	4	12	34	66	56	56	62	72	42	48	54	70
6b	0	0	0	4	6	34	68	76	56	62	72	74	50	56	70	72
6d	0	0	0	4	6	34	68	76	56	62	72	74	50	56	70	72
9a	0	0	0	0	4	10	22	28	18	18	20	28	4	4	10	20
9b	0	0	0	20	20	34	58	82	48	54	60	74	4	4	20	46
9c	0	0	2	34	82	94	96	100	90	98	100	100	86	94	98	100
PA	0	0	2	18	30	42	76	94	44	46	46	50	2	2	4	4

SOS 2c is also very similar to SOS 1a, with average pool elevations during the summer months running approximately one to two feet (0.3 to 0.6 meters) higher. The probability of Hungry Horse Reservoir refilling to within two feet of full in any given summer is about 54 percent.

SOS 4c and 9c are the two best alternatives for recreation at Hungry Horse Reservoir. Those are the only two alternatives in which during average water years the reservoir would be retained at or near full pool through the summer. SOS 4c is the stable storage operation with modified flood control at Grand Coulee. The probabilities that the reservoir would remain full in June, July and August any given year under this alternative are 82, 100 and 100 percent, respectively. The probabilities of refill in those months under SOS 9c are only slightly less. Both of those alternatives would be preferable to

either SOS 1a (Base Case) or 2c (No Action) for recreation purposes.

SOS 5b, 5c, 6b, and 6d are all very similar to SOS 1a and 2c in terms of recreational impacts. Under all of these alternatives, the average lake elevation by the end of August would be approximately 26 feet (8 meters) below full pool. The probability of refill to within two feet of full pool at any time during the summer is only approximately 56 percent.

SOS 9a would be by far the worst alternative for recreation at Hungry Horse Reservoir. During an average water year the lake would not reach within 50 feet of being full at any time. The probability that it would refill to within 20 feet (6 meters) of being full during the summer of any given year is only 28 percent and the probability of the reservoir refilling to within two feet (0.6 meters) of full is only 18 percent.

SOS 9b and the PA would be similar alternatives. Both would provide somewhat improved recreation conditions when compared with either the Base Case (SOS 1a) or No Action (SOS 2c) alternatives.

Under both, average pool elevations during June and July would be within ten feet (3 meters) of full, but would drop off to about 20 feet (6 meters) below full by the end of August. The probabilities that the reservoir will refill to within two feet of full during the summer of any given year are 48 and 44 percent for SOS 9b and the PA, respectively.

4.2.5.2 Summary of Quantitative Impacts

Table 4-13 and Figure 4-4 present the results of the SOR recreation impact assessment model for Hungry Horse Reservoir. The model provides a quantitative estimate of recreation use in recreation days for key water related recreation activities during low, average and high water years under each of the alternative SOSs. Table 4-14 compares the estimated total recreation use for each SOS against the base case (SOS 1a), the no action alternative

(SOS 2c) and the historic five year visitation (1987 to 1991).

Empirical estimation of the model is described in more detail in Appendix J-1). The model estimates recreational use at Hungry Horse Reservoir based on changes in operation of the system. Recreational use is influenced not only by changes in pool elevation at Hungry Horse, but also by changes in pool elevations of other projects in the western Montana/northern Idaho region of the user survey. Both the Lake Koocanusa and Kootenai River models include Hungry Horse Lake as a first stage complement. What this means is that, based on the results of the user survey in the region, it is possible that a higher water level at Lake Koocanusa might increase a recreator's propensity to visit Hungry Horse or the Kootenai River because the higher water levels might produce a more satisfying recreation experience, thereby increasing the likelihood of future trips. This relationship is described in more detail in Appendix J-1, Chapter 5.

Table 4-13. Hungry Horse Reservoir, Estimated Annual Recreation Days by Activity Under Alternative SOSs

SOS	Boating			Fishing			Camping			Picnicking			Swimming		
	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976
1a	6011	9533	10693	6132	9725	10909	63298	100384	112597	4442	7044	7901	1019	1617	1813
1b	4390	9337	10707	4478	9526	10923	46224	98324	112745	3243	6899	7911	744	1583	1816
2c	7002	9604	11027	7143	9798	11250	73733	101130	116121	5174	7096	8148	1187	1629	1870
2d	6899	9553	10834	7038	9746	11052	72645	100596	114081	5097	7059	8005	1170	1620	1837
4c	10851	11338	11510	11070	11567	11743	114263	119395	121207	8018	8378	8505	1840	1923	1952
5b	6011	9401	10693	6132	9591	10909	63298	98999	112597	4442	6947	7901	1019	1594	1813
5c	6011	9401	10693	6132	9591	10909	63298	98999	112597	4442	6947	7901	1019	1594	1813
6b	6011	9401	10693	6132	9591	10909	63298	98999	112597	4442	6947	7901	1019	1594	1813
6d	6011	9401	10693	6132	9591	10909	63298	98999	112597	4442	6947	7901	1019	1594	1813
9a	2728	6764	10065	2783	6901	10268	28723	71227	105982	2015	4998	7437	463	1147	1707
9b	9400	10058	10541	9590	10261	10754	98987	105911	110999	6946	7432	7789	1594	1706	1788
9c	10851	11337	11510	11070	11566	11743	114263	119379	121207	8018	8377	8505	1840	1923	1952
PA	9093	9921	11017	9277	10122	11240	95754	104474	116014	6719	7331	8141	1542	1682	1868

Figure 4-4. Hungry Horse Reservoir, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Table 4-14. Hungry Horse Reservoir, Estimated Total Annual Recreation Days Under Alternative SOSs

Average Visitation (1987-1993): 79200 Baseline Visitation (11/92-10/93): 93600		Low Water Year (1941)	50 - Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	80903	128303	143913
	% change from 2c	-14.15%	-0.74%	-3.03%
	% change from Preferred Alternative	-33.89%	-3.91%	-2.94%
	% change from 92-93		37.08%	
SOS 1b	Total	59080	125670	144101
	% change from 1a	-26.97%	-2.05%	0.13%
	% change from 2c	-37.31%	-2.77%	-2.91%
	% change from Preferred Alternative	-51.73%	-5.89%	-2.82%
SOS 2c	Total	94240	129257	148416
	% change from 1a	16.49%	0.74%	3.13%
	% change from Preferred Alternative	-23.00%	-3.20%	0.09%
	% change from 92-93		38.09%	
SOS 2d	Total	92848	128574	145809
	% change from 1a	14.77%	0.21%	1.32%
	% change from 2c	-1.48%	-0.53%	-1.76%
	% change from Preferred Alternative	-24.13%	-3.71%	-1.67%
SOS 4c	Total	146042	152601	154917
	% change from 1a	80.52%	18.94%	7.65%
	% change from 2c	54.97%	18.06%	4.38%
	% change from Preferred Alternative	19.33%	14.28%	4.48%
SOS 5b	Total	80903	126532	143913
	% change from 1a	0.00%	-1.38%	0.00%
	% change from 2c	-14.15%	-2.11%	-3.03%
	% change from Preferred Alternative	-33.89%	-5.24%	-2.94%
SOS 5c	Total	80903	126533	143913
	% change from 1a	0.00%	-1.38%	0.00%
	% change from 2c	-14.15%	-2.11%	-3.03%
	% change from Preferred Alternative	-33.89%	-5.24%	-2.94%
SOS 6b	Total	80903	126533	143913
	% change from 1a	0.00%	-1.38%	0.00%
	% change from 2c	-14.15%	-2.11%	-3.03%
	% change from Preferred Alternative	-33.89%	-5.24%	-2.94%
SOS 6b	Total	80903	126533	143913
	% change from 1a	0.00%	-1.38%	0.00%
	% change from 2c	-14.15%	-2.11%	-3.03%
	% change from Preferred Alternative	-33.89%	-5.24%	-2.94%

Table 4-14. Hungry Horse Reservoir, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 79200 Baseline Visitation (11/92–10/93): 93600		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 6d	Total	80903	126533	143913
	% change from 1a	0.00%	–1.38%	0.00%
	% change from 2c	–14.15%	–2.11%	–3.03%
	% change from Preferred Alternative	–33.89%	–5.24%	–2.94%
	% change from 92–93		35.18%	
SOS 9a	Total	36712	91036	135458
	% change from 1a	–54.62%	–29.05%	–5.88%
	% change from 2c	–61.04%	–29.57%	–8.73%
	% change from Preferred Alternative	–70.00%	–31.82%	–8.65%
	% change from 92–93		–2.74%	
SOS 9b	Total	126517	135367	141869
	% change from 1a	56.38%	5.51%	–1.42%
	% change from 2c	34.25%	4.73%	–4.41%
	% change from Preferred Alternative	3.38%	1.38%	–4.32%
	% change from 92–93		44.62%	
SOS 9c	Total	146042	152580	154917
	% change from 1a	80.52%	18.92%	7.65%
	% change from 2c	54.97%	18.04%	4.38%
	% change from Preferred Alternative	19.33%	14.27%	4.48%
	% change from 92–93		63.01%	
PA	Total	122384	133530	148279
	% change from 1a	51.27%	4.07%	3.03%
	% change from 2c	29.86%	3.31%	–0.09%
	% change from 92–93		42.66%	

In summary, all of the alternative SOSs with the exception of 9c would provide an increase in visitation over the average annual visitation from 1987 to 1993. This may be misleading, however, because that period encompasses a historic dry period in the Columbia Basin and includes several years when Hungry Horse Reservoir was drawn down severely during the summer, substantially lowering average annual use.

In comparing estimated visitor use across the alternatives during an average water year, the recreation-

al suitability of the SOSs could be characterized as follows:

Very Good	SOS 4c, 9c
Good	SOS 9b, Preferred Alternative
Average	SOS 1a, 2c, 2d
Poor	SOS 5b, 5c, 6b, 6d
Very Poor	SOS 9a

Recreational conditions at Hungry Horse Reservoir are generally much better during wet and average water years than during dry years. Estimated visitation during 1941, the last year of the driest five-year period across the Columbia River basin, would decline under all 13 alternative SOSs. Lost visitation would range from severe under SOS 9a, in which estimated use would be about one-third of that during an average water year, to slight under SOS 9c where the decline would only be about four percent. In comparing the effects of the alternatives against the No Action alternative SOS 2c, in a dry year, the "good" recreation alternatives become even better. SOS 4c, 9b, 9c and the PA would all result in very large increases in estimated visitor use ranging from about 54 percent (SOS 4c) to 30 percent (the PA). Similarly, the "poor" recreation alternatives, SOS 1a, 1b, 2d, 5b, 5c, 6b, 6d, and 9A become even worse with visitation losses ranging from about 14 percent under SOS 1a, 5b, 5c, 6b, and 6d, to 61 percent under SOS 9a.

During wet years, there is enough water in the system to bring Hungry Horse Reservoir up to or near full and retain it there during the summer peak recreation season under all of the alternatives. Consequently, all of the SOSs would show an increase in visitation when compared with average water years. In addition, the range of impacts across the alternative SOSs is much lower. There is relatively little difference between the "good" and "poor" recreation alternative.

4.2.5.3 Effects on Recreation Facilities/Activities

The eleven existing boat ramps are the only water-dependent recreation facilities at Hungry Horse Reservoir that would be affected by drawdowns (there are no boat marinas, moorages, swimming beaches or other water-dependent recreation facilities on the lake). Only eight ramps are usable below elevation 3,552 feet, six below elevation 3,532 feet, and only a single ramp is usable at elevation 3,500. The number of ramps usable during June, July and August of an average water year under each SOS are:

Alternative	June	July	August
1a	6	6	6
1b	6	6	6
2c	6	6	6
SD	6	6	6
4c	11	11	11
5b	6	6	6
5c	6	6	6
6b	6	6	6
6d	6	6	6
9a	8	3	1
9b	8	8	6
9c	11	11	11
PA	11	8	6

Under SOS 4c and 9c, all eleven of the boat ramps on the reservoir would be usable during the peak recreation months of July and August. Early filling and maintenance of the full or nearly full pools into November keeps all facilities usable during low, average, and high water years.

SOS 9b and the PA would also provide good use of boating access early in the summer but the number of usable facilities would decline later in summer.

Under SOS 1a, 2c, 2d, 5b, 5c, 6b, and 6d, during June through August of average water year conditions, 6 boat ramps would be usable. However, during low water years (1941), only one ramp would be usable during August. All boat ramps would be usable during high water years (1976).

The worst alternative for impacts to recreation facilities at Hungry Horse Lake would be SOS 9a, under which during an average water year, only three of the eleven ramps on the lake would be usable at any time during the summer, and only one would be usable by the end of August.

Recent patterns of summertime drawdown have exposed mudflats to dispersed recreation use. Associated with this use are a number of management problems, including litter and a lack of sanitation

facilities below the drawdown line. The dispersed, unmanaged visitor use is having negative affects on developed use around the reservoir. The Forest Service has expressed concern regarding a lack of staff to adequately control use occurring in the drawdown zone. These management problems would be expected to continue and possibly be exacerbated under those alternatives that result in increased summer drawdown, including SOS 1a, 2c, 2d, 5b, 5c, 6b, and 6d, and particularly 9a. SOS 4c, 9b, 9c and the PA all would result in higher summer pool elevations than either the Base Case and No Action alternatives and, therefore, would reduce this problem.

4.2.5.4 Effects on Fish Habitat and Fishing Success

SOR Technical Appendix K, Resident Fish, describes potential impacts of the alternative SOSs on game fish species in Hungry Horse Reservoir. Under historic conditions, an operating regime featuring frequent annual deep drawdowns combined with refill failure has caused the reservoir fishery to decline. On the Flathead River downstream, the lack of temperature control facilities at Hungry Horse Dam results in rapid temperature fluctuations and released water is generally of lower temperature than required for optimum fish habitat. Due in part to these reasons, trout growth and fishing success are suboptimal.

Under SOS 1a, the increased frequency of deep drawdown and refill failure would cause a continued decline in the health of the reservoir fishery as compared to historic conditions. Consequently, a long term decline in reservoir sports fishery could be expected. SOS 1b, 2c, 2d, 5b, 5c, 6b, and 6d would have similar impacts on the recreational fishery.

Of all of the strategies under consideration SOS 9a, 9b, and the PA would have the most severe impacts on west slope cutthroat trout, especially during dry years.

Under SOS 4c and 9c the reduced frequency and duration of deep drawdowns and increased probability of refill would significantly improve fish habitat conditions at Hungry Horse Reservoir. Fish produc-

tion, and consequently fishing success, would be maintained at a higher level under these alternatives than any others under consideration.

4.2.5.5 Effects on Wildlife Habitat/Hunting and Wildlife Viewing Success

SOR Technical Appendix N, Wildlife, describes potential impacts of the alternative SOSs on wildlife species and habitat at Hungry Horse Reservoir.

Under historic operating conditions at Hungry Horse Reservoir, development of wildlife habitat is constrained by deep annual drawdowns. With the exception of SOS 4c and, to a slightly lesser extent, SOS 9c, the alternatives are not expected to significantly positively or negatively change (in comparison with the no action and base case alternatives) wildlife conditions at the reservoir to the point that there would be a noticeable change in wildlife hunting and viewing opportunities.

SOS 4c and 9c would produce significantly less drawdown and exposure of barren areas at the reservoir with corresponding improvements development of riparian vegetation. These alternatives would promote increased fish productivity and would support those wildlife species foraging on fish. Despite these improvements, no substantial increase in wildlife hunting or viewing opportunities is expected.

4.2.5.6 Effects on Recreational Safety and Physical Characteristics

Several safety hazards, such as stumps and rock outcrops, emerge when the water elevation in Hungry Horse Reservoir drops below 3550 feet. These features continue to increase as the water levels decline further. For example, at 3520 feet a cliff appears in the reservoir bottom at Lost Johnny Camp. The cliff is used by some as a jump-off point into the reservoir which becomes increasingly more dangerous as the reservoir drops further. This illegal activity is difficult to control.

Under SOS 1a, the Base Case alternative, with the average water elevation of 3540 feet at the end of July, numerous safety hazards occur. Some floating

debris would be present in the reservoir. Impacts would be very similar under SOS 2c, the No Action alternative, as well as SOS 1b, 5b, 5c, 6b, 6d, 9b and the PA. The severity of these impact will increase substantially during dry years as pool elevations are drawn down further. These conditions would increase dramatically under SOS 9a due to the extremely low summer lake elevations.

Under SOS 4c and 9c high pool elevations maintained throughout the summer recreation season will greatly reduce the safety hazards exposed during drawdown. Some floating debris may be present in the reservoir.

4.2.5.7 Effects on Water Quality Parameters Influencing Recreation

There is no known turbidity problems at Hungry Horse Reservoir. Although sedimentation is occurring within the reservoir, it is not a severe problem nor does it significantly impact recreation. The cold water temperatures and annual drawdowns preclude algae blooms and/or aquatic plant growth. No known pollutants occur in the reservoir.

No significant changes on water quality parameters affecting recreational suitability at Hungry Horse Reservoir are expected under any of the alternative SOSs.

4.2.5.8 Effects on Aesthetics

Under SOS 1a, the highest reservoir elevation during July in the average water year is 3540 feet. Under those conditions, a substantial "bathtub ring" of exposed mudflats is visible around the entire reservoir which detracts from the visual quality. Early summer elevations of 3504 feet expose 60 feet of drawdown. Reservoir drafting begins in early August continuing to expose substantial drawdown area and shorelines. The visual impact is very slightly less severe under SOS 1b.

Under SOS 4c and 9c, Hungry Horse Reservoir will be at or very near full pool for the entire summer recreation season. Only small beaches areas are exposed and the water surface is close to and visible from the developed facilities. The result will be a highly desirable scenic setting around the entire reservoir and very substantial improvement in scenic quality in comparison with all other SOSs.

All other alternative SOSs would have aesthetic impacts similar to those experienced under SOS 1a. The degree of visual impact would vary with the timing and duration of drawdown, being slightly less severe under SOS 1b, SOS 2c and 2d in average water years, and slightly more severe under SOS 5b. The most severe aesthetic impacts would occur under SOS 9a, when the lake is drawn down significantly for the entire recreation season during an average water year. The severity of the impacts would increase under dry conditions.

4.2.5.9 Mitigation Opportunities

The lack of usable boat ramps during low and average water years could be remedied by extending 5 of the 11 boat ramps on the reservoir to make them usable at lower pool elevations. This mitigation action would be appropriate under all of the alternatives, with the exception of SOS 4c and possibly SOS 9c. This should be accompanied by modified parking, restroom and picnic facilities associated with the lengthened ramps.

The most pressing mitigation need at Hungry Horse Lake would be to implement actions for controlling increased use of the drawdown zone under all of the alternatives except SOS 4c and 9c. This may require increased on-site personnel to manage litter, sanitation, safety, and uncontrolled off-road vehicle use problems. Presently, the Forest Service does not have either the funds or manpower to adequately monitor use in the drawdown zone.

4.2.6 ALBENI FALLS PROJECT/LAKE PEND OREILLE

4.2.6.1 Description/Hydrologic Characteristics

Historically Albeni Falls has had a fairly stable pool with a maximum fluctuation of 11 feet. Most recreation facilities on the lake were designed to be used in the very upper end of the operating range. Thus, small reductions in pool elevation can have sizable adverse impacts to recreation in the area. A drop in pool elevation of 2.5 feet makes many recreation facilities less usable or unusable.

Table 4-15 shows the predicted end-of-month elevations at Lake Pend Oreille during peak summer recreation months of low, average, and high water years under the alternative SOSs. Full pool is 2062.5 feet.

SOS 1a (base case), 1b, 2c (no-action), 2d, 5b, 5c, 6b, 6d, and the preferred alternative (PA) are similar. Water elevations in May are no less than 2.5 feet below full pool in all water years, then refill to full pool from June through August. In some water years, lake elevations may actually exceed full pool, possibly flooding some recreation facilities.

Under SOS 4c and 9c, more stable year-round pool levels are traded for summer elevations in the lake will be up to 2.5 feet lower during July and August.

Under SOS 9a and 9b, summer pool elevations are kept much lower. The worst scenario for recreation on Lake Pend Oreille, SOS 9a starts out at about 2 feet below full pool in May, then drops steadily to an August elevation of 7.5 feet below full pool. Alternative 9b is slightly better, keeping pool elevations within 2.5 feet of full, but at levels that will negatively impact use of recreation facilities.

Table 4-15. Lake Pend Oreille — Monthly Pool Elevations for Low, Average and High Water Years Under Alternative SOSs

SOS	May			June			July			Aug		
	low	average	high	low	average	high	low	average	high	low	average	high
1a	2060.3	2060.7	2062.8	2062.5	2062.7	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5
1b	2060.4	2060.6	2062.7	2062.5	2062.7	2062.7	2062.5	2062.5	2062.5	2062.1	2062.5	2062.5
2c	2060.3	2061.0	2062.8	2062.5	2062.7	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5
2d	2060.3	2061.0	2062.8	2062.5	2062.7	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5
4c	2060.0	2062.3	2062.7	2060.0	2062.5	2062.5	2060.0	2061.4	2062.5	2060.0	2060.0	2060.0
5b	2060.3	2060.7	2062.8	2062.5	2062.7	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5
5c	2060.3	2060.7	2062.8	2062.5	2062.7	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5
6b	2060.3	2060.7	2062.7	2062.5	2062.7	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5
6d	2062.3	2062.7	2062.7	2062.5	2062.7	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5
9a	2059.1	2060.6	2062.7	2062.5	2058.5	2062.5	2056.0	2058.5	2062.5	2050.9	2055.5	2062.5
9b	2057.8	2060.8	2062.7	2062.1	2061.8	2061.7	2060.0	2061.6	2062.5	2060.0	2060.3	2062.5
9c	2060.3	2060.9	2063.2	2062.0	2062.4	2062.0	2062.0	2062.0	2062.0	2062.0	2062.0	2062.0
PA	2060.3	2061.0	2062.7	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5	2062.5

4.2.6.2 Summary of Quantitative Impacts

Table 4-16 and Figure 4-5 present the results of the SOR recreation impact assessment model for Lake Pend Oreille. The model provides a quantitative estimate of recreation use in recreation days for key water related recreation activities during low, average and high water years under each of the alternative SOSs. Table 4-17 compares the estimated total recreation use for each SOS against the base case (SOS 1a), the no action alternative (SOS 2c) and actual baseline visitation from November 1992 through October 1993.

The baseline data includes all of the recreation facilities that are located on the lake and lands that are administered by the Corps. This also includes land administered by Idaho Department of Fish and Game under lease from the Corps. The last visitor survey was conducted in 1985, and from the results, a weighting factor was determined to establish final visitation figures. At least one year of data were available for the six USFS sites, for Sandpoint City Beach, and Farragut State Park. Visitation to private facilities is not normally collected and is not included in the visitation figures. There are nine private lakefront resorts, several local hotels and

motels, and 2,289 lakefront parcels (Bonners County County Tax Office, 1991) that surround the lake. Consequently, the visitation numbers used in full-scale modeling will underestimate the total visitation that occurs at the lake. The data is considered accurate, however, for comparing impacts across alternatives.

Average Water Year. In an average water year, the model estimates that there would be no significant difference in visitation to Lake Pend Oreille between the base case (SOS 1a) and no-action (SOS 2c) alternatives, with 1a having only slightly lower use. Estimated visitation would remain virtually the same (within + or - 1%) for alternatives 1b, 2d, 5b, 5c, 6b, and 6d as 1a and 2c. The model estimates an increase in visitation under the PA. For alternatives 4c, 9b and 9c, estimated visitation would drop slightly (approximately 3, 6 and 3 percent, respectively) in comparison with SOS 2c. This decline is attributed primarily to lower pool elevations in late summer under these alternatives, as much as 2.5 feet from full under SOS 4c and 9c. According to the models, SOS 9a is by far the worst alternative, with losses in visitor use during an average water year estimated at about 18 percent compared to SOS 2c.

Table 4-16. Lake Pend Oreille, Estimated Recreation Days by Activity for Alternative SOSs

SOS	Boating			Fishing			Camping			Picnicking			Swimming		
	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976
1a	101495	103232	106418	89540	91073	93883	357443	363561	374782	470056	478101	492857	176809	179835	185385
1b	101495	103316	106418	89540	91147	93883	357443	363858	374782	470056	478492	492857	176809	179982	185385
2c	101495	103791	106418	89540	91566	93883	357443	365531	374782	470056	480691	492857	176809	180809	185385
2d	101495	103791	106418	89540	91566	93883	357443	365531	374782	470056	480691	492857	176809	180809	185385
4c	86967	100447	103663	76723	88616	91453	306279	353755	365080	402772	465205	480099	151500	174984	180587
5b	101495	103389	106418	89540	91211	93883	357443	364114	374782	470056	478828	492857	176809	180109	185385
5c	101495	103389	106418	89540	91211	93883	357443	364114	374782	470056	478828	492857	176809	180109	185385
6b	101495	103389	106418	89540	91211	93883	357443	364114	374782	470056	478828	492857	176809	180109	185385
6d	101495	103389	106418	89540	91211	93883	357443	364114	374782	470056	478828	492857	176809	180109	185385
9a	71936	84995	107520	63463	74984	94855	253343	299335	378662	333159	393641	497960	125316	148066	187305
9b	86078	97467	105639	75939	85987	93196	303147	343259	372039	398654	451403	489250	149951	169793	184029
9c	98113	100853	103764	86556	88974	91542	345532	355183	365434	454392	467084	480564	170917	175691	180761
PA	103128	105547	107480	90981	93115	94821	363196	371714	378523	477622	488822	497777	179655	183868	187236

Figure 4-5. Lake Pend Oreille, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Table 4-17. Lake Pend Oreille, Estimated Total Recreation Days for Alternative SOSs – CONT

Average Visitation (1987–1993): 1,235,500 Baseline Visitation (11/92–10/93): 1,198,900		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 6d	Total	1195462	1217773	1253451
	% change from 1a	0.00%	0.15%	0.00%
	% change from 2c	–1.58%	–0.39%	–0.99%
	% change from Preferred Alternative		–2.04%	
	% change from 92–93		1.57%	
SOS 9a	Total	847301	1001121	1266429
	% change from 1a	–29.12%	–17.67%	1.04%
	% change from 2c	–30.25%	–18.11%	0.04%
	% change from Preferred Alternative		–19.47%	
	% change from 92–93		–16.50%	
SOS 9b	Total	1013870	1148023	1244277
	% change from 1a	–15.19%	–5.58%	–0.73%
	% change from 2c	–16.53%	–6.09%	–1.71%
	% change from Preferred Alternative		–7.66%	
	% change from 92–93		–4.24%	
SOS 9c	Total	1155626	1187905	1222186
	% change from 1a	–3.33%	–2.30%	–2.49%
	% change from 2c	–4.86%	–2.83%	–3.46%
	% change from Preferred Alternative		–4.45%	1265964
	% change from 92–93		–0.92%	
PA	Total	1214704	1243190	1265964
	% change from 1a	1.61%	2.24%	1.00%
	% change from 2c	1.61%	1.69%	1.00%
	% change from 92–93		3.69%	

Low Water Year. When compared with conditions in an average water year, most of the alternatives, including SOS 1a, 1b, 2c, 2d, 5b, 5c, 6b, 6d, 9c and the PA all show slight declines in visitor use during an extreme low water year. SOS 4c shows a moderate (approximately 13 percent) decline in estimated use between low and average water years, due principally to the lake level being held about 2.5 feet below full through the entire summer recreation season. SOS 9A and 9B are the worst alternatives during low water years, with estimated decline in visitation of about 15 and 12 percent from an average water year.

High Water Year. During high water years, estimated visitation to Lake Pend Oreille would be very similar under all of the alternatives and, in all cases, would be higher than during either low or average water years. SOS 1a, 1b, 2c, 2d, 5b, 5c, 6b, and 6d have identical estimated recreation use. The PA and SOS 9a are the best alternatives under high water conditions with slight increases of about one percent over the others. SOS 4c, 9b and 9c would have slightly lower estimated visitor use of between about one and three percent compared with the other alternatives. Again, the estimated decline in visitor use is attributed to lower pool elevations during late summer.

4.2.6.3 Effects on Recreation Facilities/Activities

Boating. The recreation impact assessment model shows that for boating activities in an average year, alternatives 1b, 2d, 5b, 5c, 6b, and 6d will have very nearly the same visitor use as the base case (1a) and no-action (2c) alternatives. The preferred alternative should increase boating activity over all alternatives. Somewhat less use is projected for 4C and 9C due to the lower pool elevations. The model indicates much less boating use for 9a and 9b. As the water levels drop, various hazards to boats (such as old pilings, logs, and rocks) are closer to the surface.

Camping and Picnicking. These activities are not as sensitive to water levels as boating, fishing, and swimming. So the recreation model doesn't project any real drop in recreation use for any of the alternatives except in the case of 9a. Here the water levels are becoming so low that water-related activities associated with camping and fishing have declined substantially, decreasing demand. The aesthetic qualities of the area are also diminished, discouraging these activities. The preferred alternative, on the other hand, may increase camping and picnicking use.

Swimming. Recreation use of the lake for swimming is subject to the same constraints as boating. Small decreases in water elevation rapidly make many swimming areas unusable. Thus, alternatives 1a, 1b, 2c, 2d, 5b, 5c, 6b, and 6d are projected to have about the same swimming use because the pool elevations are similar — close to full. The model shows the preferred alternative as slightly increasing swimming activity. As the elevations drop for 4c and 9c, swimming use is shown as decreasing. It decreases further with 9a and 9b.

4.2.6.4 Effects on Fish Habitat and Fishing Success

Lake Pend Oreille supports a very popular sports fishery that attracts anglers from throughout the region. This fishery has been declining over the last 40 years. SOR Technical appendix H describes in detail the potential impacts of the alternatives on

fish biology. Changes in fish populations and growth affect fishing success and fishing demand.

The recreation impact assessment model predicts fishing activity at Lake Pend Oreille in an average water year to be virtually the same for 1a, 1b, 2c, 2d, 5b, 5c, 6b, and 6d, with a possible increase for the preferred alternative. It also predicts that alternatives 4c and 9c may have somewhat less fishing use and that 9a and 9b will have substantially less.

There is some concern, however, that the impact assessment model for Lake Pend Oreille may not have accurately captured the beneficial effects of some of the alternatives, particularly SOS 4c, on fish habitat, and therefore fishing success and demand. The models are based on a survey in which anglers and other users were presented with visual and narrative depictions of alternative pool elevations and at Lake Pend Oreille and six other reservoirs, plus flows at two rivers in the basin and asked to respond regarding how those elevations would influence their recreational use. Although, no information on fisheries was provided, it was assumed that anglers would form an assumption of the effects of lake elevations on the enjoyment of their fishing experience (including fish-catching success). Their stated preferences under alternative operations are based in part on these assumptions. The models, however, do not contain any direct correlation between recreation demand and expected changes in catch rates due to changes in fish biology resulting from alternative operations. A catch rate parameter was considered for inclusion in the model but ultimately was excluded because it did not appear that adequate data exists that would allow catch rates to be statistically significant in explaining recreational demand. The relationship between recreation demand model considerations and fish catch rates is explained in more detail in Section 4.2.1.4.

The user surveys showed that reduced lake elevations under SOS 4c and several other alternatives would lead to reduced recreational demand. However, the lower, more stable year round pool elevations under SOS 4c are designed to restore habitat conditions for sport fish, particularly kokanee. The fishery for bull trout and Kamloops could also be

expected to increase in response to the added prey base. A long-term improvement in game fish populations at Lake Pend Oreille could substantially increase sport fishing demand and participation. Based on a comparison of historic creel census data for Lake Pend Oreille, there appears to be a strong connection between the kokanee population in the lake and fishing demand.

Increased fishing demand resulting from improved habitat conditions under SOS 4c may offset some if not all of the loss in visitation attributable to lower pool elevations. Idaho Department of Fish and Game (Maiolie, 1995) estimates that under SOS 4c, the Lake Pend Oreille could reach an annual harvest goal of 750,000 kokanee. They expect the boost in harvest from a current level of 227,000 to result from an approximately 300 percent increase in annual fishing trips for kokanee. IDFG also expects the increase in prey base to improve the fishery for bull and Kamloops trout and thereby increase angling demand for those species. Finally, SOS 4c will improve habitat conditions for eagles and waterfowl, possibly resulting increased demand for wildlife viewing and waterfowl hunting at Lake Pend Oreille.

However, with the catch rate data currently available, it is impossible to quantify the increased demand resulting from improved catch rates for kokanee at Lake Pend Oreille.

4.2.6.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

Impacts of the alternatives on wildlife and wildlife habitat are fully addressed in Technical Appendix N. The recreation impact model does not foresee any of the alternatives as having any significant negative impacts on wildlife habitat or species at Lake Pend Oreille. Alternatives 4c, 9a, 9b, and 9c may actually provide some benefits. The stable, lower pool elevation maintained during summer would allow re-establishment of riparian and emergent vegetation around the shoreline. This could benefit waterfowl hunting and wildlife viewing opportunities – like eagle watching – at Lake Pend Oreille.

4.2.6.6 Effects on Recreational Safety and Physical Characteristics

Under all alternatives, flooding may occur in May and June. Recreational facilities could be at least partially flooded, creating safety and access concerns.

The lower summer pool elevations experienced under alternatives 4c, 9a, 9b, and 9c would expose (or bring closer to the surface) old pilings, logs, and rocks. These could create a hazard for boaters.

4.2.6.7 Effects on Water Quality Parameters Influencing Recreation

Short-term turbidity and other water quality problems could occur with flooding above normal full pool during May and June. No new conditions are expected to result from any of the alternatives.

4.2.6.8 Effects on Aesthetics

In comparison with the base case (1a) and no-action (2c) alternatives, 1a, 2d, 5b, 5c, 6b, 6d, and the preferred alternative (PA) would not have any significant effect on the visual quality of Lake Pend Oreille.

The lower, more stable pool elevations of 4c, 9a, 9b, and 9c will expose a small “bathtub ring” around the lake during the summer. This amount of exposure is well within the normal operational range of the lake and would not have any significant affect on visual quality.

4.2.6.9 Mitigation Opportunities

No mitigation is needed for 1a, 1b, 2c, 2d, 5b, 5c, 6b, 6d, and the preferred alternative(PA).

The impact of lower summer pool elevations under alternatives 4c, 9a, 9b, and 9c could be mitigated by extending or modifying existing recreation facilities. It would be relatively simple (though costly) to modify or extend existing boat ramps, fixed and floating docks, and swimming beaches to make them fully usable through the summer. This type of mitigation could greatly reduce the severity of visitation losses estimated by the recreation impact assessment model. The highest priority for mitigation would be extending swimming beaches at the major reservoir parks such as Riley Creek and Springy Point.

4.2.7 GRAND COULEE PROJECT/LAKE ROOSEVELT

4.2.7.1 Description/Hydrologic Characteristics

Variation between SOSs at Lake Roosevelt is reflected in the timing of drawdown and refill for flood control storage. Table 4-18 shows the average monthly pool elevations (as measured at the forebay of Grand Coulee Dam) under the 13 alternative SOSs. As shown, under all of the alternatives, the lake is at its minimum in April and then is gradually refilled, reaching its peak in June or July. The lake is generally held as full as possible through December or January, and then is drawn down slowly.

Average monthly pool elevations from June through December vary only slightly (within the upper five feet of the lake) across SOS 1a, 1b, 2c, 2d, 4c, 5b, 5c, 6b, and 6d. Somewhat more variation would occur under SOS 9a, 9b, 9c, and the PA.

Table 4-19 compares the percent probability (over the fifty year period of record) that Lake Roosevelt be refilled to selected elevations ranging from the optimum recreation pool of 1,288 feet (two below full) down to elevation 1,277 feet over the peak recreation months of May through . As shown, the probabilities of refill during any given month vary somewhat more across the e SOSs than do average pool.

Table 4-18. Grand Coulee Dam/Lake Roosevelt — Average Monthly Pool Elevations

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	1264	1251	1239	1231	1244	1285	1290	1290	1289	1289	1289	1287
1b	1264	1250	1237	1229	1247	1285	1290	1290	1289	1289	1289	1287
2c	1271	1261	1248	1238	1254	1285	1290	1290	1289	1289	1289	1287
2d	1287	1273	1251	1243	1258	1286	1287	1288	1288	1288	1288	1287
4c	1270	1260	1264	1260	1269	1287	1288	1288	1288	1288	1288	1287
5b	1271	1261	1248	1238	1254	1285	1290	1290	1289	1289	1289	1287
5c	1271	1270	1247	1238	1254	1285	1290	1290	1289	1289	1289	1287
6b	1271	1261	1248	1238	1254	1285	1290	1290	1289	1289	1289	1287
6d	1271	1270	1248	1238	1254	1285	1290	1290	1289	1289	1289	1287
9a	1285	1284	1267	1236	1244	1276	1265	1249	1252	1256	1272	1278
9b	1289	1287	1270	1242	1254	1279	1281	1271	1269	1278	1286	1289
9c	1287	1273	1250	1234	1249	1284	1286	1281	1285	1288	1288	1287
PA	1287	1284	1265	1238	1253	1284	1286	1281	1282	1287	1289	1288

Table 4-19. Grand Coulee Dam/Lake Roosevelt — Percent Probability of Refill to Selected Pool Elevations

Pool Elevation (ft. NGVD)	Month															
	May				June				July				August			
	1288	1285	1280	1270	1288	1285	1280	1270	1288	1285	1280	1270	1288	1285	1280	1270
SOS	Percent Probability of Refill to Selected Pool Elevations															
1a	0	0	2	12	62	92	96	98	98	100	100	100	96	100	100	100
1b	0	0	4	16	66	92	96	98	94	100	100	100	94	100	100	100
2c	0	18	26	36	56	92	98	98	96	100	100	100	96	100	100	100
2d	2	4	14	22	58	70	88	98	68	74	100	100	70	100	100	100
4c	0	0	68	68	86	90	96	100	100	100	100	100	100	100	100	100
5b	2	4	14	22	58	70	88	98	68	74	100	100	70	100	100	100
5c	0	0	18	24	38	86	94	98	94	100	100	100	94	100	100	100
6b	2	4	14	22	58	70	88	98	68	74	100	100	70	100	100	100
6d	2	4	14	22	58	70	88	98	68	74	100	100	70	100	100	100
9a	2	10	26	36	72	76	90	98	42	70	78	82	64	68	68	74
9b	4	8	20	28	56	62	70	80	54	58	64	70	26	34	50	56
9c	2	4	12	22	48	50	90	98	62	62	100	100	32	40	98	98
PA	2	4	8	16	40	48	94	98	58	60	100	100	4	4	100	100

SOS 1a, the Base Case alternative, would provide very good recreation conditions at Lake Roosevelt. There is a 92 percent probability that the lake will be filled to within five feet of full (elevation 1,285) by the end of June in any given year. The probability that the reservoir would fill to within two feet of full (elevation 1,288) by the end of July and remain there through August is 98 and 96 percent respectively. **SOS 1b** would be very similar to the Base Case with the exception of slightly lower probability (94 percent) that the lake could be retained within two feet of full through July and August.

SOS 2c, the No-Action alternative, would also be a good strategy for recreation at Lake Roosevelt, featuring spring refill earlier in the year than **SOS 1a**. At the end of May, the average pool elevations under **SOS 2c** and **1a** are 1,254 and 1,244 feet respectively. The probabilities that the lake would be within 10 feet of full (elevation 1,280) by the end

of May are 36 percent and 2 percent, respectively. During other periods of the year, **SOS 2c** would be very similar to the Base Case.

In comparison, **SOS 2d** would be a poor alternative for recreation in May and June, when the probability of refill to within 10 feet of full pool is only 70 percent. Conditions would be better in July and August, when the probability that the lake will fill to within five feet of full is 74 and 84 percent, respectively). **SOS 5b, 6b, and 6d** would provide essentially the same as **SOS 2d**.

SOS 5c, would provide relatively good recreation conditions similar to **SOS 2c** with the exception that refill to full pool occurs later. This alternative has a much lower probability of refill in May and June.

In terms of hydrologic characteristics, **SOS 4c** would be the best alternative for recreation at Lake Roosevelt. This alternative would provide a higher proba-

bility that lake levels would be within 10 feet of full by the end of May than any other alternative; 68 percent versus 2 and 26 percent for SOS 1a and 2c, respectively. There would be a 100 percent probability that lake elevations be at their optimum of 1,288 feet from June through November.

SOS 9a, 9b & 9c all would provide poor recreation conditions for end of May use and marginal conditions throughout the remainder of the recreation season. The probability that that Lake Roosevelt could be refilled and maintained near the optimum recreation pool of 1,288 feet by the end of August is much lower under all three of these alternatives than any of the previous SOSs (64, 26 and 32 percent for 9a, 9b, and 9c, respectively). Under SOS 9a and 9b, average end of August pool elevations would be well below the optimum for recreation (1,249 and 1,271 feet, respectively). In comparing the three alternatives, SOS 9c would be slightly better, followed by 9b and 9a.

The **Preferred Alternative** would also be a poor alternative for recreation at Lake Roosevelt. It is slightly worse than SOS 9c, but slightly better than

SOS 9b and SOS 9a. The Preferred Alternative would provide poor recreation conditions throughout May, improving somewhat in June. In July and August, there would be a relatively low probability that the lake would ever fill to the optimum pool elevation of 1,288 feet. The probability is relatively high, however, that the lake would remain within 10 feet of being full throughout the summer. In general, the PA would be an undesirable alternative for recreation at Lake Roosevelt.

4.2.7.2 Summary of Quantitative Impacts

Table 4-20 and Figure 4-6 present the results of the SOR recreation impact assessment model for Lake Roosevelt. The model provides a quantitative estimate of recreation use in recreation days for key water related recreation activities during low, average and high water years under each of the alternative SOSs. Table 4-21 compares the estimated total recreation use for each SOS against the base case (SOS 1a), the no action alternative (SOS 2c) and the baseline visitation (1992-93) for Lake Roosevelt.

Table 4-20. Lake Roosevelt, Estimated Annual Recreation Days by Activity for Alternative SOSs

SOS	Boating			Fishing			Camping			Picnicking			Swimming		
	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976
1a	439714	426010	439421	311099	301403	310892	365811	354410	365568	406382	393716	406112	160600	155595	160493
1b	449060	427632	439810	317712	302551	311168	373587	355759	365891	415020	395215	406471	164014	156187	160635
2c	467225	436222	440336	330563	308629	311540	388698	362906	366329	431807	403155	406957	170648	159325	160827
2d	419004	434326	444717	296447	307288	314639	348582	361329	369973	387242	401403	411006	153036	158632	162427
4c	411532	433974	429674	291160	307038	303996	342365	361035	357458	380336	401077	397103	150307	158503	156933
5b	467225	435141	440336	330563	307864	311540	388698	362007	366329	431807	402156	406957	170648	158930	160827
5c	467225	435141	440336	330563	307864	311540	388698	362007	366329	431807	402156	406957	170648	158930	160827
6b	467225	435141	440336	330563	307864	311540	388698	362007	366329	431807	402156	406957	170648	158930	160827
6d	467225	435141	440336	330563	307864	311540	388698	362007	366329	431807	402156	406957	170648	158930	160827
9a	294373	328376	445460	208270	232327	315164	244898	273186	370591	272059	303484	411692	107516	119935	162698
9b	347215	387123	430806	245656	273891	304797	288858	322059	358400	320895	357778	398149	126816	141392	157346
9c	393847	410256	429693	278648	290258	304010	327653	341304	357474	363992	379157	397121	143848	149841	156940
PA	406113	421271	445460	287327	298050	315164	337858	350467	370591	375328	389337	411692	148328	153864	162698

Figure 4-6. Lake Roosevelt, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Table 4-21. Grand Coulee Project/Lake Roosevelt, Estimated Total Recreation Days Under Alternative SOSs

Average Visitation (11/92-10/93): 1,746,300 Baseline Visitation (1987-1993): 2,207,100		Low Water Year (1941)	50 - Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	1683439	1630971	1682318
	% change from 2c	-5.89%	-2.34%	-0.21%
	% change from Preferred Alternative	8.27%	1.12%	-1.36%
	% change from 92-93		-6.71%	
SOS 1b:	Total	1719220	1637181	1683807
	% change from 1a	2.13%	0.38%	0.09%
	% change from 2c	-3.89%	-1.97%	-0.12%
	% change from Preferred Alternative	10.58%	1.51%	-1.27%
	% change from 92-93		-6.36%	
SOS 2c:	Total	1788762	1670069	1685820
	% change from 1a	6.26%	2.40%	0.21%
	% change from Preferred Alternative	15.05%	3.55%	-1.15%
	% change from 92-93		-4.47%	
SOS 2d:	Total	1604149	1662812	1702592
	% change from 1a	-4.71%	1.95%	1.21%
	% change from 2c	-10.32%	-0.43%	0.99%
	% change from Preferred Alternative	3.17%	3.10%	-0.17%
	% change from 92-93		-4.89%	
SOS 4c:	Total	1575542	1661461	1644998
	% change from 1a	-6.41%	1.87%	-2.22%
	% change from 2c	-11.92%	-0.52%	-2.42%
	% change from Preferred Alternative	1.33%	3.02%	-3.54%
	% change from 92-93		-4.97%	
SOS 5b:	Total	1788762	1665931	1685820
	% change from 1a	6.26%	2.14%	0.21%
	% change from 2c	0.00%	-0.25%	0.00%
	% change from Preferred Alternative	15.05%	3.29%	-1.15%
	% change from 92-93		-4.71%	
SOS 5c:	Total	1788762	1665931	1685820
	% change from 1a	6.26%	2.14%	0.21%
	% change from 2c	0.00%	-0.25%	0.00%
	% change from Preferred Alternative	15.05%	3.29%	-1.15%
	% change from 92-93		-4.71%	
SOS 6b:	Total	1788762	1665931	1685820
	% change from 1a	6.26%	2.14%	0.21%
	% change from 2c	0.00%	-0.25%	0.00%
	% change from Preferred Alternative	15.05%	3.29%	-1.15%
	% change from 92-93		-4.71%	

Table 4-21. Grand Coulee Project/Lake Roosevelt, Estimated Total Recreation Days Under Alternative SOSs – CONT

Average Visitation (11/92–10/93): 1,746,300 Baseline Visitation (1987–1993): 2,207,100		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 6d:	Total	1788762	1665931	1685820
	% change from 1a	6.26%	2.14%	0.21%
	% change from 2c	0.00%	–0.25%	0.00%
	% change from Preferred Alternative	15.05%	3.29%	–1.15%
	% change from 92–93		–4.71%	
SOS 9a:	Total	1127004	1257182	1705435
	% change from 1a	–33.05%	–22.92%	1.37%
	% change from 2c	–37.00%	–24.72%	1.16%
	% change from Preferred Alternative	–27.51%	–22.05%	0.00%
	% change from 92–93		–28.09%	
SOS 9b:	Total	1329307	1482095	1649332
	% change from 1a	–21.04%	–9.13%	–1.96%
	% change from 2c	–25.69%	–11.26%	–2.16%
	% change from Preferred Alternative	–14.50%	–8.11%	–3.29%
	% change from 92–93		–15.23%	
SOS 9c:	Total	1507837	1570658	1645073
	% change from 1a	–10.43%	–3.70%	–2.21%
	% change from 2c	–15.70%	–5.95%	–2.42%
	% change from Preferred Alternative	–3.02%	–2.61%	–3.54%
	% change from 92–93		–10.16%	
PA	Total	1554798	1612827	1705435
	% change from 1a	–7.64%	–1.11%	1.37%
	% change from 2c	–13.08%	–3.43%	1.16%
	% change from 92–93		–7.75%	

Based on the model results, during average water years there would be no significant difference in visitation under **SOS 1a, 1b, 2c, 2d, 4c, 5b, 5c, 6b and 6d**. SOS 2c would provide the highest estimated visitation, but none of the other alternatives would vary by more than about 2.4 percent. **SOS 9c and the PA** would have only slightly lower visitation, an estimated decline of 5.95 and 3.43 percent in total visitor use, respectively, compared with SOS 2c. **SOS 9a and 9b** would have the most significant impact on visitor use, with losses of 24.72 and 11.26, respectively when compared with SOS 2c.

Generally, recreation conditions at Lake Roosevelt improve during high water years as the lake is held

at higher elevations for longer periods. For example, in 1976, a very high water year across the region, estimated visitation would be expected to increase slightly to moderately under all alternatives except SOS 4c. In addition, the relative differences between the alternative SOSs is much smaller during high water years. In 1941, estimated visitation to Lake Roosevelt would vary no more than –2.42 percent from SOS 2c. SOS 4c shows a slight decrease in total visitor use in 1976 which is attributed to the fact that under that alternative, the lake is normally brought up to near full and retained there during the summer recreation season. Therefore, under high water years, a full pool produces no

advantage and forecast spring flood flows result in lake elevations being held lower than normal.

During dry years estimated visitor use would decrease under seven of the SOSs but would increase under the remaining six SOSs. sos 1a, 1b, 2c, 5b, 5c, 6b, and 6d all show slight to moderate increases in visitor use during 1941, a very low water year. SOS 2d, 4c, 9a, 9b, 9c, and the PA all show slight to moderate decreases in estimated visitor use. The range of potential impact varies much more across the alternatives during a dry year than a normal or wet year. For example, under when compared with SOS 2c, the range of impacts is from no change under SOS 5b and 5c, all the way to a 37 percent loss in visitor use under SOS 9a.

Annual recreation visitation at the reservoir would be similar under SOS 1a, the base case, and SOS 1b. In comparison, SOS 2c, the no-action alternative, resulted in estimates of slightly higher visitation. Visitation under SOS 5b, 5c, 6b and 6d would be very similar. In all of these cases, the slight increase in visitation over the base case is attributed to higher average pool elevations in May.

4.2.7.3 Effects on Recreation Facilities/Activities

There are 40 developed recreation sites on Lake Roosevelt containing over 700 campsites and more than 20 launch ramps. All facilities are operable from full pool to five feet of drawdown. If drawdown goes beyond five feet, high water facilities such as swim areas and some launch ramps become inoperable.

SOS 1a, the Base Case, and 1b are compatible with the operation of all recreation facilities. Facilities become operable when the reservoir comes up in the spring and remain operable for most water years throughout the summer season. SOS 2c, 5b, 6b, and 6d are similar in their effects on recreation facilities. Within this group, facilities would become operable in June and remain functional throughout the summer season. SOS 5c and 2d are similar to, though slightly worse than, the SOS 2c group. Under 5c and 2d facilities would be fully functional from June through August. Under SOS 4C, all facilities would

be operable throughout the primary recreation season. Facilities would come on-line in the spring earlier than the projections for the Base Case.

SOS 9c, the Preferred Alternative, 9b, and 9a are the worst recreation alternatives, in descending order. Facility use and activities would be negatively affected, requiring some mitigation to restore facilities to full functional levels. SOS 9a is the worst alternatives for recreation.

4.2.7.4 Effects on Fish Habitat and Fishing Success

Lake Roosevelt is a popular destination for anglers. Recreation visitation at the reservoir increases and decreases with fishing success. Fishing success is a strong indicator of the public's enjoyment of the reservoir and the quality of the recreation experience.

There are no anadromous fish runs at Lake Roosevelt; all fishing success depends upon the health of the resident fishery. For a full evaluation of the impact of the various alternatives on the resident fishery at Lake Roosevelt, refer to the Resident Fish Work Group Technical Appendix N.

Reservoir operations may have detrimental effects on resident fish by impacting the food source, fish entrainment through the dam, and by disrupting fish propagation.

SOS 2d would result in deep drawdowns combined with high outflows and decreased water retention times from January through May for most water years. This operation is detrimental to spring spawning fish species, including walleye and yellow perch. Long term impacts include an adverse impact on fisheries, as food resources decrease and entrainment increases. Fishing success would be expected to decline.

SOS 4c would provide better water retention times in Lake Roosevelt than any other alternative. It provides the most stable environment for fish production of all the alternatives and would be expected to result in improved fish catching success when compared with SOS 1a and 2c. However, this operation is not without some negative impacts to fish. Changes in reservoir elevations would be

gradual, except in April and May when they would be large and rapid enough to decrease spawning success of spring spawning fish by inundating eggs with cool water and silt. Unavoidable impacts to Grand Coulee fisheries would include the loss of nutrients and zooplankton, and fish through entrainment, decreasing fish spawning and feeding habitat and loss of benthic invertebrates.

SOS 5c would feature deep annual drawdowns, combined with high outflows. There would be negative impacts to spring spawning. The severe drawdowns would also negatively impact net-pen rearing operations. With outflows and reduced water retention times, primary and secondary productivity decreases and entrainment increases. The resulting low zooplankton density and biomass values and high numbers of salmonids entrained would be reflected by reduced fish growth and decreased fish populations. Fishing success would decline.

SOS 9a, 9b, and 9c would produce very poor conditions for Lake Roosevelt fisheries. Spring drawdown will cause high entrainment of plankton and fish. In all three alternatives, the percent of kokanee remaining and growth for 2, 4 and 10 year intervals produce the lowest fish growth numbers for all of the alternatives analyzed. Consequently, these are expected to be the worst alternatives for fishing success in Lake Roosevelt.

The PA would produce alternatives which increase outflows in the spring, cause entrainment, decrease spawning success, and increase habitat loss. Drastic changes in pool elevations could cause fish to pool up at the dam with increased chances for entrainment, increased sediment, harming eggs and causing temperature problems, which affect eggs and plankton production.

4.2.7.5 Effects on Wildlife Habitat/Hunting and Wildlife Viewing Success

Hunting is allowed on most of Lake Roosevelt. Hunting does not account for a high percentage of recreation use of the reservoir. Wildlife viewing is a popular activity that generally occurs incidental to other recreation activities. The viewing of bald

eagles in the winter months, however, is gaining in popularity and may become a primary activity in future years.

Negative impacts on wildlife hunting and viewing can occur when reservoir drawdown dewater wetlands and other vegetation that has become established at the high water line. Holding the reservoir at low levels for long periods of time during the hot dry summers can stress or kill trees and other vegetation that depend on reservoir water at the root zones.

The SOSs that do not deviate greatly from the historic operation of the reservoir are not likely to have a negative effect on the wildlife and habitat at Lake Roosevelt.

4.2.7.6 Effects on Recreational Safety and Physical Characteristics

Reservoir levels have a direct effect on the safety and convenience of recreation use at Lake Roosevelt. Many of the floating recreating facilities are anchored to concrete bulkheads at the high water line. As the reservoir is drawn down, the gangways between the bulkheads and the floating facilities become too steep for pedestrian use. With reservoir drawdown, the water depth under the swim floats becomes shallow and unsafe for diving. Boating is impacted by low water levels as vehicle backing distances are lengthened for boat launching and retrieval. Rocks, shoals and other obstructions that are well below the high water mark become boating hazards as the lake elevation is lowered. Extreme high water elevations can also introduce boating hazards as stranded debris is refloated back into the reservoir pool. Optimum elevation for boating use is two feet below full pool. With lake elevations at 10 feet or more from full pool swim beaches become unusable due to unsafe topography and bottom composition. Most major facilities, however, will remain operable through 20 feet of drawdown (1270').

SOS 1a, 1b and SOS 2c, 2d & 5b, 5c, 6d would have minimum effects on recreation safety and physical characteristics of the reservoir. These strategies are not much different than historic operations of the reservoir. However, SOS 5b and SOS 6b and d have deep spring drawdowns that would have some detri-

mental effect on boaters. Summer season effects for these strategies would be similar to historic conditions, as lake elevations would be at or near full pool.

The SOS 4c strategy would be the best for recreation accessibility and safe use of the reservoir. Pool levels would be up during the recreation season, but not so high as to refloat the stranded debris.

4.2.7.7 Effects on Water Quality Parameters Influencing Recreation

There are water quality concerns that effect recreation at Lake Roosevelt. The concerns are primarily associated with pollutants entering the reservoir from industrial operations in Canada. The operation of the reservoir under any of the SOS strategies is not likely to affect water quality to the extent that recreation on Lake Roosevelt is impaired or enhanced.

4.2.7.8 Effects on Aesthetics

The operation of the reservoir under the SOS alternatives will have an effect on aesthetics, particularly visual, due to exposed barren lake bottom during periods of drawdown. The historic operation of the reservoir has not greatly impacted the visitors visual enjoyment of Lake Roosevelt, as the annual spring drawdown occurs prior to the primary visitor season.

4.2.7.9 Mitigation Opportunities

Recreation facilities on Lake Roosevelt have been constructed to accommodate recreation use under the historic operating conditions of the reservoir. For those strategies that are similar to historic operations, no mitigation measures would be needed.

SOS 9a and 9b would introduce new operating conditions during the summer season that would negatively impact all facilities and render some facilities inoperable during certain times of the year. Extensive modifications to existing facilities or construction of replacement facilities at new locations would be needed in order to offset the impact of summer drawdowns. The aesthetic degradation could not be mitigated and the recreation experience

would be greatly diminished. Modification of swim beaches would have to be explored to reduce safety hazards found at lower reservoir levels.

SOS 2c, 2d, 5b, 5c, 6b, and 6d may require some changes to make all facilities operable during the summer season, but would not be as damaging to reservoir recreation as the SOS 9a and 9b. SOS 9c and the Preferred Alternative may require some mitigation to assure that all high water facilities are useable at elevation 1280 feet, which is maintained nearly 100 percent of the time from June through August.

Four launch ramps would need to be retrofitted to remain usable should lake levels go below 1,280 feet. Boat moorings, anchored to the lake bottom, would have to be moved to accommodate the lower lake levels. In some cases, exposure to high winds would not allow modification of the mooring facilities to remain usable below elevation 1,280 feet and the facilities would be lost. Similar impacts and modifications to both fuel and sanitation (boat pump out) stations may be required. Courtesy docks associated with launch ramps would have to be modified to accommodate lower lake levels. In some cases, new dock locations would have to be developed.

The entire system of navigational aids in Lake Roosevelt should be modified to accommodate lower lake levels. Additional aids may be required.

Marina facilities would experience increased difficulty in operations at lower lake levels. In some cases, lower levels would reduce the size of harbors, with fewer moorage slips usable. In the case of Kettle Falls, the harbor is unusable for large boat mooring below 1,275 feet. Presently, there is no alternative location for this activity and docks go out of service until water levels increase. Due to the physical limitations of the Kettle Falls boat basin, it may not be possible to mitigate for these impacts on site.

There are also several swimming beaches that would require excavation so that they could continue to provide safe conditions at lower operating levels. Log booms would have to be extended from their current anchors.

4.2.7.10 Recreational Impacts to Banks Lake

Banks Lake is a 27 mile long pump storage/irrigation supply reservoir that is located approximately 300 feet above Lake Roosevelt. The sole water supply for Banks Lake is from pumps at Grand Coulee Dam. Since the water level at Banks Lake relies on pumps rather than natural inflow, the reservoir is retained at a relatively stable pool elevation through the entire summer recreation season. Consequently, Banks Lake has developed into a very popular recreation area. It supports high levels of use for boating, fishing, swimming, waterskiing, hunting and other activities. Steamboat Rock State Park is located on the shoreline of Banks Lake.

The water levels of Banks Lake can potentially be affected by low water levels in Lake Roosevelt. As Lake Roosevelt drops in elevation, water must be pumped to greater heights to reach Banks Lake, which lowers the efficiency of the pumps. When Lake Roosevelt falls to elevation 1,208 feet (92 feet of drawdown from full pool) or more, the pump intakes cannot pick up water. During those periods when irrigation demands exceed the capacity of the pumps to provide water, Banks lake will be drawn

down to a point where recreation and other uses are negatively affected.

The potential for this condition to occur is especially high under SOS 9a, in which the Lake Roosevelt is drawn down to extreme low pools during July and August in about 16 percent of years. At those times, Banks Lake may be drawn down from 25 to 37 feet. Water-dependent facilities on Banks Lake would be inoperable. Since Banks Lake is located in a shallow basin, all of the recreation sites would be located long distances from the shoreline. The aesthetics of the reservoir from recreation sites and from Highway 155, a designated scenic byway, would be negatively impacted. The recreational suitability of Banks Lake would be effectively eliminated during those periods.

Some long-term impacts could also be expected. The fact that Banks lake has historically remained at or near full pool has allowed the development of extensive riparian vegetation and perennial marsh areas to become established along the shallow shoreline. Summer drawdown of the magnitude projected under SOS 9a, b, c and the Preferred Alternative would have an extremely detrimental effect on fish and wildlife habitat.

4.2.8 CHIEF JOSEPH PROJECT/RUFUS WOODS LAKE

4.2.8.1 Description/Hydrologic Characteristics

All SOS alternatives have the same operational criteria. There are no significant differences between these alternatives in terms of recreation for Rufus Woods Lake, which has an average pool elevation of 953.2 for the entire year. This constant pool elevation should not deviate under wet or dry years.

The hydrologic models used for the evaluations do not provide data for short-term (daily or weekly) operations. This evaluation assumes that the lake will continue to fluctuate daily for power peaking between the minimum operating pool of 950 feet and the maximum pool of 965 feet NGVD.

Outflows from Chief Joseph will, however, change substantially under the alternatives to accommodate the different inflows caused by manipulation of the much larger Grand Coulee Dam upstream. Flows will range from a low of 56,402 cfs in a dry year to a high of 229,043 cfs in a wet year. These flows would effect the water retention time within the reservoir.

4.2.8.2 Summary of Quantitative Impacts

No recreation impact assessment models were prepared for Rufus Woods Lake because there is no change in operation (lake elevations) across the alternative SOS. Historic visitation (1987–1991) to Lake Woods was about 210,000 visitors annually. No significant change in use would be expected between any of the alternatives.

4.2.8.3 Effects on Recreation Facilities/Activities

The recreation potential of Rufus Woods Lake is optimized at or near an elevation of 954 feet. But unlike other run-of-river reservoirs with limited operational range, the recreation facilities at Rufus Woods are easily accessible down to 950 feet. The one developed beach is sandy down to 950 feet and has a gentle bottom down to 945 feet, giving it a

wide operational range. The main boat ramp is usable down to 945 feet, 9 feet below full pool, and it has paved concrete strips down to 937 feet. All facilities at the lake remain well within the operational ranges anticipated under all alternatives.

4.2.8.4 Effects on Fish Habitat and Fishing Success

The impacts of the alternatives on resident fish in Rufus Woods Lake are described in SOR Technical Appendix K. Because this project acts as a run-of-river reservoir, effects on resident fish are likely to be similar to those in Lake Roosevelt, immediately upstream. Impacts from operation of Grand Coulee Dam under all alternatives include loss of nutrients, loss of zooplankton, loss of benthos invertebrates, decreases in fish spawning and feeding habitat, and entrainment of kokanee and rainbow trout. All alternatives are poor for resident fish, though none would significantly affect existing conditions. Thus, none of the alternatives would be expected to significantly improve or decrease fishing success or demand at Rufus Woods Lake.

4.2.8.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

The effects on wildlife habitat, and consequently hunting and wildlife viewing opportunities, should not vary under any of the alternatives.

4.2.8.6 Effects on Recreational Safety and Physical Characteristics

None of the strategies propose any changes. Therefore, effects on recreational safety and physical characteristics should be neutral.

4.2.8.7 Effects on Water Quality Parameters Influencing Recreation

No changes would be expected as a result of any of the alternatives.

4.2.8.8 Effects on Aesthetics

Aesthetic quality at Rufus Woods Lake should not change as a result of any of the alternatives.

4.2.8.9 Mitigation Opportunities

No mitigation is recommended because all proposed alternatives have little impact on recreational facilities or suitability. Visitation to Lake Woods is currently very low, and there is only one highly developed

recreation site on the lake. Since all alternatives maintain a stable pool, Rufus Woods Lake may provide opportunities for developing new recreation sites or facilities to mitigate for the impacts of changed project operations on recreation at other projects in the system.

4.2.9 MIDDLE COLUMBIA RIVER PUBLIC UTILITY DISTRICT PROJECTS

4.2.9.1 Description/Hydrologic Characteristics

The five mid-Columbia River PUD projects below Chief Joseph Dam are Wells, Rocky Reach, Rock Island, Wanapum, and Priest Rapids Dams in that order from upstream to downstream.

These projects are cold-water tailwaters to the Grand Coulee Dam storage reservoir. They are run-of-the-river projects operated for hydropower. Releases from Chief Joseph Dam dictate how they will operate. PUD projects coordinate operations (along with Chief Joseph) to maximize power generation. They have virtually no storage capacity, passing whatever water comes into them from upstream. Their objective is to keep all reservoirs close to full all of the time. Consequently, each has essentially no fluctuation at the forebay of the dam.

Because the reservoirs are relatively small with limited storage capacity, they have substantial backwater curves that are influenced by flow volume and river cross-sections. The further upstream, the more dramatic the river fluctuations may be at each of these projects. For example, tailwater fluctuations vary as much as three to four feet per day at Rock Island Project.

Unlike most of the other reservoirs in the system, low flow periods at these projects do not adversely effect recreation. Recreational suitability is influenced more strongly by the magnitude and duration of peak flow periods and the ramping rates of daily fluctuations. The normal peak flow period is in the flood season – May and June.

The hydroregulation models used to evaluate the alternatives only provide average monthly flows. The average monthly flows (in kcfs) during the peak recreation season from the lowest dam on the system, Priest Rapids, are shown in Table 4–22 as a proxy for all of the mid Columbia PUD projects. Flow volumes will vary slightly at the other dams, but basic trends in volume remain the same, allowing a general comparison of the relative impacts of the alternatives on recreational suitability across the system.

Flows for SOS 1a and 2c follow the natural hydrograph of the system, peaking in May and then declining rapidly through the summer. Average monthly flows in June are significantly higher under alternative 2c than under 1a. Alternatives 1b, 5b, 5c, 6b, and 6d would not significantly change this flow relationship. The flow relationship for alternative 9a is similar, but at a much higher rate throughout the summer.

Table 4–22. Average Monthly Summer Flows (KCFS), Priest Rapids Dam

SOS	Month						
	May	June	July	Aug 15	Aug 30	Sep	Oct
1a	168	146	126	102	89	67	67
1b	162	150	131	103	90	80	86
2c	171	161	123	104	91	80	80
2d	159	174	141	104	90	80	80
4c	168	180	140	108	86	62	77
5b,5d	170	160	122	103	90	79	80
6b,6d	170	160	122	103	90	79	80
9a	191	180	161	122	123	53	56
9b	169	188	150	119	106	54	58
9c	159	173	154	112	95	56	68
PA	166	182	147	117	98	64	67

Under SOS 2d, 4c, 9b, 9c, and PA (preferred alternative) the peak average monthly flows would shift from May to June, increasing substantially in comparison with SOS 1a.

4.2.9.2 Quantitative Results of Impact Assessment Models

Data about short-term operations — daily and weekly flow ramp rates and peak flow magnitudes — is needed to accurately estimate the impacts of operation of the mid-Columbia dams on recreational suitability in this reach. Because this data was not available, no quantitative recreation impact assessment models were developed for this section of the river.

4.2.9.3 Effects on Recreation Facilities/Activities

Impacts to the usability of most recreation facilities will be minor under these alternatives. Many facilities — like ball fields, campgrounds, and bike paths — operate independently of river operations. But swimming areas, marinas, and boat launches could be affected as their use changes in response to increased water velocities.

Rapidly increasing flows and high-volume flows can negatively affect some recreational uses on the consecutive lakes. Under high spring flow conditions, tailwater fluctuations flood some recreation facilities. This is particularly true at Rock Island, which has a high degree of recreational development and use around the city of Wenatchee. Because this project is short and located in a narrow portion of the river, it is especially sensitive to high-volume flows.

Thus no significant change in recreational conditions at mid-Columbia River Projects is expected under alternatives 1a, 1b, 2c, 5b, 5c, 6b, and 6d because they maintain the existing flow relationships during the peak flow periods in May and June.

Alternatives 2d, 4c, 9b, 9c, and PA shift peak average monthly flows from May to June, substantially increasing flows in June. And 9a increases flows substantially throughout the summer. Without more detailed information about short-term, peak-flow magnitude and duration, it is difficult to accurately assess exactly how these alternatives will affect recre-

ation. They could exacerbate the existing negative effects that high-volume flows have on recreation use and facilities. But the effects shouldn't significantly alter recreation access and participation.

4.2.9.4 Effects on Fish Habitat and Fishing Success

None of the alternatives under consideration is expected to significantly alter existing conditions. Consequently, there should be no significant change in fishing success under any of the alternatives.

The principal resident sport fish in the Mid-Columbia River are walleye, northern squawfish, and small-mouth bass. Anadromous fish species — salmon and steelhead — are also available up to Chief Joseph Dam. Under existing conditions, reduced water temperature and high water velocity (low water retention time) are the most likely factors limiting the success of resident fish at all these projects. Reduced spring and summer water temperatures could limit the spawning opportunities for non-native warm water species, such as sunfish, bass, and catfish, which can spawn only in atypical warm backwaters. High water velocities can lead to entrainment of resident fish species, negatively impacting fish habitat and reducing fish populations and fishing success.

4.2.9.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

None of the alternatives affect present wildlife habitat, hunting, and wildlife viewing conditions.

4.2.9.6 Effects on Recreational Safety and Physical Characteristics

Spilling from all of the mid-Columbia dams creates turbulence and whitewater in the tailwater zones. This is a hazard for swimmers and boaters. Although most recreation sites along this reach have been hardened, high velocity flows result in some shoreline erosion.

No significant effects on recreational safety and physical conditions are anticipated under alternatives 1a, 1b, 2c, 5b, 5c, 6b, and 6d. But since 2d, 4c, 9b, 9c, and PA will substantially increase flows in

both May and June in comparison with SOS 1a and 2c, existing recreational safety and physical problems may worsen. This may also be true of 9a. These effects, however, would not be expected to significantly alter recreation participation in the reach.

4.2.9.7 Effects on Water Quality Parameters Influencing Recreation

No known water quality problems or concerns affecting recreational suitability are known to exist at these projects. No change is expected under any of the alternatives.

4.2.9.8 Effects on Aesthetics

Impacts on the aesthetics of the project should not be significant. Some recreation sites and facilities and other shoreline areas may be flooded more frequently under SOS 2d, 4c, 9a, 9b, 9c, and PA, but this won't significantly alter the aesthetic qualities.

4.2.9.9 Mitigation Opportunities

There are few mitigation opportunities. It would be difficult and costly to modify the existing recreation sites and facilities to reduce the impacts of flooding and high-volume flows that may occur with more frequency under SOS 2d, 4c, 9a, 9b, 9c, and PA.

4.2.10 HANFORD REACH

4.2.10.1 Description/Hydrologic Characteristics

The Hanford Reach is the last free-flowing, non-tidal reach of the Columbia River in the United States. It has extraordinary natural, cultural, historical, and recreational resources. A team from the National Park Service, Fish and Wildlife Service, and Department of Energy is currently studying the reach to determine the best way to preserve those values. A draft EIS issued in 1993 recommended that the reach be designated a National Wild and Scenic River. This would overlay the National Wildlife Refuge on the river and approximately 90,000 acres of adjacent land.

Although not impounded, the flows and fluctuating water levels of the Hanford Reach are highly influenced by operations at Priest Rapids Dam. Under existing conditions, daily fluctuations in water level in the tailwater area below the dam range from 8 to 12 feet, depending on inflow to the dam and peak power demands.

The hydropower regulation models used to evaluate the alternatives provide only average monthly flows. The average monthly outflows (in kcfs) from Priest Rapids Dam during the peak recreation season are shown on Table 4-22 above. Data on the effect of short-term operations of Priest Rapids Dam on outflows and water surface elevations in the Hanford Reach was not available. So assessment of the recreational impacts associated with operation under the alternatives is limited to comparing average monthly flows to determine possible generic impacts or trends. It is assumed that daily fluctuations in downstream water surface elevation would not vary significantly from the current condition for any of the proposed alternatives.

Under SOS 1a and SOS 2c, flows follow the natural hydrograph of the system. They peak in spring and early summer, then they decline rapidly through the summer and fall, reaching minimum flows by the end of October. Average monthly flows are somewhat higher in June and in September/October under SOS 2c than under SOS 1a. Flow relationships are

similar for alternatives 1a, 1b, 2c, 5b, 5c, 6b, and 6d. The flow relationship for alternative 9A is similar, but at a much higher rate throughout the summer. Under alternatives 2d, 4c, 9a, 9c, and PA (preferred alternative) the peak average monthly flows would shift from May to June, increasing substantially.

4.2.10.2 Quantitative Results of Impact Assessment Models

Data for short-term operations — daily and weekly flow ramp rates and peak flow magnitudes — is needed to accurately estimate the impacts of operation of the Priest Rapids Dam on recreation in the Hanford Reach. Since this data was not available, no quantitative recreation impact assessment models were developed for this section of the river.

4.2.10.3 Effects on Recreation Facilities/Activities

There are few highly developed recreation sites on the Hanford Reach. Most recreation use is on the east side of the reach in Franklin county, where there are low-density public access facilities. The Hanford Nuclear Reservation, which is along much of the west side of the Hanford Reach, is closed to the public.

The peak recreation season is during September and October, which corresponds to the waterfowl hunting and salmon (fall Chinook) fishing seasons. Access to these activities is primarily by boat. Fishing is concentrated in three areas: the upstream end of the reach between Priest Rapids Dam and Vernita Bridge, downstream of the Ringold Hatchery, and around White Bluffs. Most hunting occurs in the sloughs and island habitats throughout the reach and within the shoreline and upland areas of Wahluke Wildlife Recreation Area.

The Vernita Bridge Boat Ramp is the most heavily used boat ramp in the reach. Most facilities will remain usable over a wide range of river fluctuations. None of the alternatives under consideration should affect the usability of boat ramps or other developed recreation facilities along the river.

However, boating in the reach has been observed to decline markedly during periods of high flow (in excess of 120 kcfs). This may be caused by changes

in physical access and boating safety or by changes in fishing and hunting success. Similarly, during periods of low flow (below 70 kcfs), changes in current, channel morphology, and bottom substrates constrain boating use.

The range of average monthly flows anticipated under most alternatives is not expected to significantly change access to the river for these activities. However, increased peak average monthly flows during May and June could exacerbate existing difficulties associated with boating at high-flow periods. This impact would be most significant under alternatives 2d, 4c, 9a, 9b, 9c, and the preferred alternative (PA).

Alternatives 1b, 2c, 2d, 5b, 5c, 6b, and 6d provide higher average September and October flows than under SOS 1a. The moderate increases in flow at the normal low flow period should generally improve accessibility to the river and benefit recreation. This corresponds to the peak use period for the river. The other alternatives provide lower flow averages for these months.

4.2.10.4 Effects on Fish Habitat and Fishing Success

The Resident Fish Work Group was unable to determine the potential effects of the alternatives on resident fish species in Appendix K because they lacked data for short-term operations. Consequently, the effect of these alternatives on fishing success is not known.

4.2.10.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

Appendix N describes the effects of the alternatives on wildlife species and habitat. Hunting and wildlife viewing opportunities would not change significantly from present conditions under any of the alternatives.

4.2.10.6 Effects on Recreational Safety and Physical Characteristics

No significant effect on recreational safety and physical conditions is anticipated under SOS 1a, 1b, 2c, 5b, 5c, 6b, and 6d. Since SOS 2d, 4c, 9a, 9b, 9c, and the preferred alternative (PA) will substantially increase flows in both May and June in comparison with SOS 1a and 2c, existing recreational safety and physical problems may be exacerbated. These effects, however, would not be expected to significantly alter recreation participation in the reach.

4.2.10.7 Effects on Water Quality Parameters Influencing Recreation

No water quality problems affecting recreational suitability are known to exist in the Hanford Reach. No change is expected under any of the alternative SOSs.

4.2.10.8 Effects on Aesthetics

The White Bluffs area is a very scenic section of the Hanford Reach where the lightly colored bluffs drop steeply into the river. Under existing operations, there is considerable erosion at the toe of the bluffs. This has a negative effect on aesthetics. The impact of the alternatives on the existing erosion problem is unknown. It is possible, however, that increased flow periods associated with several alternatives could exacerbate this problem. Otherwise, the impacts on the aesthetics of the Hanford Reach would not be significant.

4.2.10.9 Mitigation Opportunities

There would be few recreational mitigation opportunities on the Hanford Reach. No mitigation is recommended for any of the alternatives.

4.2.11 SNAKE RIVER: HELLS CANYON REACH

The Hells Canyon National Recreation Area (HCNRA) is a nationally renowned wild and scenic river managed by the US Forest Service (USFS) and protected by Federal statute under the Wild and Scenic Rivers Act. It is an approximately 75-mile unobstructed, free flowing river reach located on the middle Snake River and is situated downstream of the Hells Canyon Complex of dams owned and operated by Idaho Power Company (IPC). Therefore, instream flows in HCNRA are influenced by the extent to which changes in Federal hydrosystem operations may alter outflows from IPC's Hells Canyon Dam Complex (i.e. Hells Canyon, Oxbow, and Brownlee Dams).

This analysis assumes that outflows from the non-Federal Brownlee project, as computed by the SOR hydroregulation models, are passed downstream and are not attenuated (peaks discharges flattened) through HCNRA. This assumption was applied to qualitatively assess the potential effects of SOS's on HCNRA recreational activities.

4.2.11.1 Hydrological Characteristics

Table 4-23 displays the expected average monthly

outflows from Brownlee Dam during June, July and August, the peak months for float and jet boat recreation on the Snake River in Hells Canyon, under each of the alternative SOSs. The most desirable range of flows for those activities is from 10,000 to 15,000 cfs (280 to 425 cms). However, a range of flows from 10,000 to 25,000 cfs (280 to 700 cms) is acceptable for most recreation. Table 4-24 displays the percent of time across the 50 year period of record that flows would fall within this acceptable range under each of the alternative SOSs.

SOS 1a and 1b (Base Case): As shown on Table 4-23, average monthly outflows from Brownlee over the 50-year hydrologic record range from about 16,000 cfs during June to 10,600 cfs through August, the peak months. In an extreme low water year such as 1941, Brownlee outflows range from 13,300 cfs to 11,700 cfs from June through August. Extreme high water conditions such as those experienced in 1976 allow more water to be stored in Brownlee Reservoir so that almost constant outflows downstream range from 11,000 cfs to 12,500 cfs during the peak season. Over the 50-year water record, flows fall within the desirable (10-15 kcfs) and acceptable ranges (10-25 kcfs) through the entire summer season a high proportion of times compared with the other alternatives.

Table 4-23. Average Monthly Summer Flows (CFS), Snake River Hells Canyon

SOS	Month		
	June	July	August
1a, 1b	15,900	12,300	10,600
2c	18,000	12,300	8,500
2d	18,600	9,800	10,500
4c, 5b, 5c, 6b, 6d	16,000	12,300	8,500
9a	27,400	17,600	21,300
9b,9c	20,700	10,200	14,200
PA	19,400	13,200	10,900

Table 4–24. Percent of Years Average Monthly Summer Snake River Hells Canyon Flows Fall Within the “Acceptable” Recreation Range

SOS	Month		
	June	July	August
1a, 1b	68	96	78
2c,	56	80	20
2d	76	32	58
4c, 5b, 5c, 6b, 6d	56	80	20
9a	50	94	86
9b,9c	74	64	100
PA	78	94	80

SOS 2c (No Action): The range of average flows is more dispersed than in SOS 1a and 1b, with flows somewhat higher in early summer (June) and noticeably lower (19.6 percent) in August. In low water years (1941), the range of outflow varies from 15,300 cfs in June to about 9,900 cfs in August and is somewhat less stable than the low water range under SOS 1. High water conditions (1976) produce optimal flows for float and jet boat activity, ranging from 14,000 cfs to 10,200 cfs during the peak season. Over the 50–year water record, flows fall within the desired (10–15 kcfs) or acceptable range (10–25 kcfs) proportionately fewer times than under the Base Case, particularly during the primary boating period in mid–summer.

SOS 4c, 5b, 5c, 6b and 6d: These alternatives are hydrologically similar to SOS 2c, varying only in having slightly lower June flows.

SOS 2d: The range of average summer flows is more variable than under either SOS 1a or SOS 2c. Compared to the Base Case, flows are somewhat higher in early summer (June), noticeably lower than optimum (below 10 kcfs) in July, and are relatively stable in the desirable flow range (10–15 kcfs) in August. During low water conditions (1941), outflow varies from 15,300 cfs in June to a generally low monthly average of 7,000 cfs in July, when recreational boating is at its peak. Flows tend to depart

from the desirable range to a greater extent during the important mid–summer float and jet boat season when low water conditions prevail, as compared to the Base Case. High water conditions (1976) provide optimal flows for float and jet boat use, ranging from 13,200 cfs to 10,100 cfs during the peak season. Over the 50–year water record, flows fall within the desired or acceptable range more frequently than under SOS 1a or SOS 2c during June and August, but less frequently in July.

SOS 9a: This system strategy calls for releases of large volumes of Upper Snake water to meet anadromous spring and summer flow targets established at Lower Granite Dam. Consequently, Hells Canyon flows are the highest of any SOS throughout the primary float and jet boat recreation season (assuming Brownlee flows are not attenuated as they pass through the Hells Canyon complex). Flows would be extremely high in June, dropping off in July, and then increasing again in August. Average June flows are approximately 78 percent higher than the Base Case and 57 percent higher than the No–Action alternative. Similarly, August flows on average are substantially greater than either Base Case or No–Action alternative. In the representative low (1941) and high (1976) water years, August outflows from Brownlee average 23,000 cfs and 25,300 cfs respectively.

Over the 50–year record, average June flows exceed acceptable levels (greater than 25,000 cfs) in 50

percent of water years. The high July flows remain within the high-end of the acceptable range in 94 percent of water years, although the most desirable flow range is attained in only 12 percent of the time. By August, average flow conditions are by far the highest of any SOS; flows are predicted to fall within the upper end of the acceptable range (20–25 kcfs) in 86 percent of water years and at no times do they fall within the desirable flow range.

SOS 9b and 9c: Average monthly flows are relatively high in June, and then remain very stable within the optimum flow range throughout the remainder of the summer (i.e. 10,200 cfs to 14,200 cfs). These are modified flow target operating strategies and are not nearly as extreme as 9a during the peak boating season in HCNRA. Average 50-year June flows are somewhat higher than the Base Case or No-Action alternatives, but they still remain in the acceptable flow range. Similarly, average July and August flows stay within the HCNRA optimal range, similar to Base Case operations, however average July flows (10,200 cfs) are at the low end of the desirable range.

In a low water year (1941), July flows drop to a relatively low 7,000 cfs under SOS 9b and 9c, but remain in the desirable range under the PA. These SOSs produce near optimal flow levels in June and August. High water conditions results in flows that are close to the optimal range throughout the summer recreation season.

Over the 50-year record, flows remain within the desirable or acceptable range a higher proportion of times than the Base Case in June and in August. In July, SOS 9b and 9c flow conditions are generally poorer than the Base Case since flows are predicted to be below the acceptable range. In only extreme low flow years, however, are such low flow conditions expected to be below 6,500 cfs.

Preferred Alternative: Average monthly flows are relatively high in June, and then remain very stable within the optimum flow range throughout the remainder of the summer (i.e. 11,200 cfs to 16,400 cfs). This modified flow target strategy is not nearly as extreme as 9a during the peak boating season in HCNRA, and is quite similar in character to 9b and 9c except during the July flow period.

Average 50-year June flows are somewhat higher than the Base Case or No-Action alternatives, but they still remain in the acceptable flow range. Similarly, average July and August flows stay within the HCNRA optimal range, similar to Base Case operations. In a low water year (1941), flows remain at or near the desirable range under the PA during the entire summer. Similarly, high water conditions results in very favorable summer flow conditions that remain in the optimal range. Over the 50-year record, flows remain within the desirable or acceptable range a higher proportion of times than the Base Case or No-Action alternative.

4.2.11.2 Quantitative Results of Impact Models

No recreation impact assessment models were prepared for this reach due to a lack of information concerning the relationship between flows and recreation participation. Therefore, quantitative estimates of visitation effects of the alternative SOSs are not provided.

4.2.11.3 Effects on Recreation Facilities/Activities

SOS 1 (Base Case): Flows under SOS 1a and SOS 1b do not adversely effect boat ramp access at either Pittsburgh landing or Hells Canyon Dam. Primary water dependent activities encounter generally ideal flow conditions that do not impede commercial or private jet boats ability to gain upstream access or to degrade the quality of downstream floatboat recreation opportunities. Flows remain relatively constant from month to month, thus minimizing debris accumulation and do not appear to exacerbate beach erosion problems that occurs when flows vacillate between extremely high and low levels. Instream river flows are maintained at or very near optimum levels (10,000 – 15,000 cfs) for the bulk of the float and jet boat summer use season.

SOS 2c (No Action), 4c, 5b, 5c, 6b and 6d: Instream flows provide generally acceptable floatboat and jetboat recreational conditions in June, optimal conditions in July, and less than optimal in August, based upon 50-year average water conditions. Since these SOSs involves the release of 427 KAF of upper Snake water during the springtime, June flows tend

to be higher on average compared to the base case. In 18 percent of the water years, June flows exceed the maximum acceptable flow (25,000 cfs) that is considered to be safe for float boating (25,000 cfs) and that precludes jet boat access (30,000 cfs); therefore a significant loss in float and jet boat use could occasionally be expected during years in which high flow conditions exist. For the most part, however, early summer flows are acceptable or optimal, ensuring high quality float and jet boat opportunities in most water years.

Late-summer (August) flows are somewhat lower on average than the base case and may adversely affect particularly commercial jet boat activities in some years. Average 50-year Brownlee outflows drop below the level (8,000 cfs) that allows commercial jetboats apparently to safely navigate upstream channels in 20 years (40 percent) out of the historical 50-year record. It is expected that summer commercial jetboat activity may be partially curtailed when such flow conditions persist, either by stranding boats attempting to navigate through shallow channels or keeping boats tied to the dock because of access problems. Private jetboat access is only occasionally impaired in August. In only 5 (10 percent) out of 50-years, flows fall below the 6,500 cfs minimum considered necessary to permit private jetboats to safely navigate channels upstream of Pittsburgh landing. The uppermost boat ramp access at Hells Canyon Dam is potentially affected in 5 out of 50-years, when flows decline to less than 6,500 cfs.

Average summer flows decline gradually over a relatively short period of time from June through August. Debris tends to accumulate most and congest beaches when flows drop to low levels following periods of higher flows, a more likely occurrence than under the base case. Beach erosion is not expected to be any more of a serious problem than what has existed historically, as high natural spring flows combined with dams act as a sediment trap and alter natural deposition rates on beaches occurring along HCNRA.

SOS 2d: Instream flows provide generally acceptable floatboat and jetboat recreational conditions in June and August and less than optimal in July, based

upon 50-year average water conditions. Compared to the base case summer flows fluctuate more with higher flows in June (18,600 cfs), lower than optimum flows in July (9,800 cfs), and stable flows in August (10,500 cfs). In low water conditions, outflows decline as much as 7,700 cfs from June to July, when recreational boating is at its peak, which would bring an expected decline in commercial jetboat activity. High water years provide optimal conditions for float and jet boat use.

SOS 9a: Instream flows are the highest of any SOS throughout the primary float and jet boat recreation season due to the release of large volumes of Upper Snake water to meet flow targets at Lower Granite dam. These high flows could cause a significant loss in both float and jet boat use. Both June and August flows are substantially higher than the No-Action or Base Case alternatives. June averages unacceptably high flows (above 25,000 cfs) which can be expected to curtail floatboat activities during 50 percent of water years. Despite the higher average July flow levels, float and jet boaters will encounter generally acceptable flow conditions that can be characterized by somewhat higher instream flow levels than what occurs under either SOS 2c or the Base Case.

In 86 percent of the water years, August flows fall within the upper end of the acceptable range and at no times fall within the desirable flow range for recreational boating activities.

High summer flows hold steady from June through mid-August. Debris may tend to accumulate for a longer period in the summer as more water is flushed through HCNRA over a longer period of time. Beach erosion could be more frequent over the summer periods.

SOS 9b and 9c: Instream flows provide generally acceptable floatboat and jetboat recreational conditions in July and August, and are on the high end of optimal in June, based upon 50-year average water conditions. June flows average on the higher end with 20,000 cfs, going down to an average July and August flow of between 10,200 cfs to 14,200 cfs. In a low water year, July flows drop below optimum float and jet boat levels to 7,000 cfs. In extreme low waters, upstream access is impaired for jet boat use

when flows fall to below 6,500 cfs. However, summer flows are acceptable or optimal for ensuring high quality float and jet boat opportunities in most water years.

PA: Instream flows provide optimal floatboat and jetboat recreational conditions in July and August and somewhat high but still acceptable conditions in June, based upon 50-year average water conditions. This strategy is similar to 9b and 9c except for July flows which remain within the HCNRA optimal range for boating. In high and low water years, flows remain within the desirable range for float and jet boat activities throughout the summer months.

4.2.11.4 Effects on Fish Habitat and Fishing Success

SOS 1a and SOS 1b: The most important recreational fisheries occurring in HCNRA are for sturgeon, steelhead, and warm water species such as smallmouth bass. These SOS's provide quite stable flows which promote good float and jetboat access to primary fishing grounds during the summer peak use period. Moreover, there are no excessively high flows which may tend to adversely affect fish behavior and, in theory, potentially these species fishing success rates. Thus, fishing success presumably is not significantly impacted under the base case.

SOS 2c, 4c, 5b, 5c, 6b, 6d: As in SOS 1, the effects on fishing success rates were qualitatively evaluated based on some very limiting assumptions. Under this SOS, high flows occur with greater frequency in early summer (June). This could create some early-season access problems for boaters and, therefore, reduce fishing success rates if angling pressure declines. For the balance of the peak summer boat use season, fishing success is not expected to be significantly affected.

SOS 9a: The substantially higher flows in early summer (June) will create potential access problems for early-summer boaters and is assumed to have some negative affect on fish behavior at the same time. Early season fishing success rates can be expected to fall due to these combined effects. As in SOS 2c, fishing success is not expected to be significantly

affected for the balance of the peak summer boat use season.

SOS 2d: The generally high, sustained flows over a two and one-half month summer period is not expected to preclude jet boat access to salmon and sturgeon fishing grounds in HCNRA. As in SOS 2c and the Base Case, fishing success is not expected to be significantly affected during the peak summer boat use season.

SOS 9b, 9c and PA: The greater frequency of high flows in early summer (June) could create access problems for boaters and, therefore, reduce fishing success rates if angling pressure declines. For the balance of the peak summer boat use season, however, fishing success is not expected to be significantly affected by these SOS's.

4.2.11.5 Effects on Wildlife Habitat/Hunting and Wildlife Viewing Success

SOS 1a, 1b, 2c, 5b, 5c, 6b, 6d, 9b, 9c and PA: No significant effect on game, nongame, and waterfowl wildlife resources is expected.

SOS 2d: Wildlife resources are not expected to be adversely affected during the June – July period. Nesting and foraging habitat is predicted to decrease slightly for wildlife resources that are distributed on emergent and submerged wetlands, riparian areas, and island areas within HCNRA. Consequently, opportunities to view wildlife along the river corridor may be impaired to some degree especially during the early part of the regulated boating season.

SOS 9a: Wildlife resources within HCNRA are expected to be slightly affected by the particularly high flows in June. Nesting and foraging habitat is predicted to decrease slightly for wildlife resources that are distributed on emergent and submerged wetlands, riparian areas, and island areas within HCNRA. Consequently, opportunities to view wildlife along the river corridor may be impaired to some degree especially during the early part of the regulated boating season.

4.2.11.6 Effect on Recreational Safety and Physical Characteristics

SOS 1a and SOS 1b: Unsafe river conditions occur when rapidly fluctuating low or high flow conditions prevail during peak use periods. Unstable flow regimes can strand boaters, cause power and float boating accidents, expose rocks and shoals in jetboat navigation channels, and create excessive sandy beach erosion problems. Flows that drop to below 8,000 cfs begin to create navigational and environmental hazards for commercial jetboat excursions that need particularly wider and deeper river channels to access HCNRA upstream. Private jetboat users start to have difficulty gaining upstream access through narrow channels in the upper reaches of HCNRA when flows drop to below 6,500 cfs. Unsafe conditions begin for inexperienced float boaters at flows above 20,000 cfs and river conditions become extremely hazardous for all float and powerboat activities when flows exceed 25,000 cfs. The river becomes totally inaccessible when flows surpass 30,000 cfs.

SOS 1a and SOS 1b provide relatively stable flows throughout the prime summer recreation season. In only 6 out of 50 water years (12 percent) do flows exceed 25,000 cfs, the level considered unsafe for floatboat and jetboat recreation. Recreational safety and physical characteristics appear not to be significantly affected under this operation.

SOS 2c, 4c, 5b, 5c, 6b, and 6d: In early summer, June flows exceeding 25,000 cfs (18 percent of years) may create safety hazards for floatboat and jetboat participants, but water conditions are generally favorable or optimal for floaters and jet boaters and do not adversely affect recreational safety. Brownlee outflows (HCNRA instream flows) tend to drop below 8,000 cfs in 40 percent of the years, creating potential navigation and environmental hazards for commercial jetboat excursions that need particularly wider and deeper river channels to access HCNRA upstream. Less of an upstream access problem is rarely encountered by private jetboat users, since flows drop close to or below the 6,500 cfs minimum level required for safe private jetboat conditions in

just 10 percent of the years. At low flows below 7,000 cfs, float boat users may begin to encounter exposed rocks in some of the more challenging Class IV rapid stretches.

SOS 2d: Water conditions are generally acceptable for floaters and jet boaters in June through August. However, in 68 percent of the July water years, flows fall below the level (8,000 cfs) that is considered to be relatively safe for navigation of commercial jet boat excursions. Environmental hazards also begin to occur as beaches and rocks are exposed. Thus, there could be some drop off in use during the peak summer jetboat season when low flows persist.

SOS 9a: Early summer flows exceed 25,000 cfs in 50 percent of the water years (compared to 20 percent under SOS 2c) making river conditions unsafe for boating recreation. Overall this SOS poses the greatest safety hazards for floatboat and jetboat participants in the early part of the regulated use season.

Water conditions are generally favorable or optimal for floaters and jet boaters in July and safety is not significantly affected. During August, Brownlee outflows (HCNRA instream flows) in the representative low (1941) and high (1976) water years increase to 23,000 cfs and 25,300 cfs respectively. These flows create unsafe conditions for inexperienced float boaters and at the high end, become extremely hazardous for all float and powerboat activities.

SOS 9b and 9c: The modified flow targets are not nearly as extreme as 9a during the peak boating season in HCNRA. June average monthly flows of approximately 20,000 cfs creates challenging to unsafe conditions for inexperienced float boaters. July Brownlee outflows (HCNRA instream flows) tend to drop to 7,000 cfs in low water years, potentially creating navigational and environmental hazards for commercial jetboat excursions that need particularly wider and deeper river channels to access HCNRA upstream. Private jetboat users will occasionally encounter flows that are low enough (i.e. 6,500 cfs) to create upriver access problems as well.

Preferred Alternative: This modified flow target strategy provides relatively stable flows throughout the prime summer recreation season and is quite similar in character to 9b and 9c except during the July flow period. Unlike 9b and 9c, July flows remain very stable within the optimum flow range.

4.2.11.7 Effects on Water Quality Factors Influencing Recreation

SOS 1a and SOS 1b: Water quality parameters (i.e. turbidity, sedimentation, aquatic plants, pollutants, and temperature) are similarly affected by rapid changes in the volume of water flowing through HCNRA. These SOS's provide a relatively stable and predictable flow pattern that is not expected to significantly alter water quality conditions.

SOS 2c, 4c, 5b, 5c, 6b, and 6d: Water quality parameters (i.e. turbidity, sedimentation, aquatic plants, pollutants, and temperature) are affected by rapid changes in the volume of water flowing through HCNRA. Average monthly flows decline gradually from an average of 18,000 cfs to 8,500 cfs in August; therefore water quality is not expected to be significantly affected. However, when high water flow years (over 25,000 cfs) occur in June and then decline more rapidly into July and August, turbidity and sedimentation effects are likely to become more problematic.

SOS 2d: Water quality parameters (i.e. turbidity, sedimentation, aquatic plants, pollutants, and temperature) may be affected by the rapid changes in the volume of water flowing through HCNRA in June through July. Sedimentation due to rock sheering effects and beach erosion may also increase during the summer flow augmentation period.

SOS 9a: Water quality parameters (i.e. turbidity, sedimentation, aquatic plants, pollutants, and temperature) are expected to be significantly affected by the radical change in the volume of water flowing through HCNRA from June–August. Average monthly flows decline from 27,400 cfs in June to 17,600 cfs in July, but then increases to 21,300 cfs during August; therefore water quality is assumed to be degraded to some degree because of high turbu-

lence. Sedimentation due to rock sheering effects and beach erosion will likely increase in early summer.

SOS 9b and 9c: Water quality parameters (i.e. turbidity, sedimentation, aquatic plants, pollutants, and temperature) may be affected during only those years in which the flow conditions fluctuate from approximately 20,000 cfs in June and then rapidly decline in July to a relatively low 10,000 cfs in a low water year. The overall effect on water quality is expected to be only minor.

Preferred Alternative: Water quality parameters (i.e. turbidity, sedimentation, aquatic plants, pollutants, and temperature) are not expected to be significantly affected. Average monthly flows remain very stable within the optimum flow range throughout the summer.

4.2.11.8 Effects on Aesthetics

SOS 1a and SOS 1b: The key aesthetic feature potentially affected by the different SOS's is primarily changes in the waterscape character. The following waterscape characteristics are key elements that enhance the aesthetic or visual quality of HCNRA: free-flowing stream, deep pools, and alternating white water rapids. This SOS is not expected to significantly alter these waterscape characteristics and, therefore, aesthetic quality because of the stable flow regime.

SOS 2c, 4c, 5b, 5c, 6b, and 6d: The key aesthetic feature potentially affected is primarily changes in the waterscape character caused by the particularly higher flows in June. In those years in which flows exceed 25,000 cfs, even the most prominent white water rapids could be washed out temporarily in early summer. Thus, the aesthetic quality of HCNRA's unique waterscape characteristics could be adversely impacted in early summer.

SOS 2d: The waterscape character of HCNRA could be significantly affected by the drop in flows from June to July. There are many more years in which flows could potentially exceed 25,000 cfs in June than under SOS 2c and the Base Case. Consequently, the most prominent white water rapids could be inundated more frequently during the peak summer recreation season. Average monthly August flows maintain aesthetic features.

SOS 9a: The waterscape character of HCNRA is expected to be more significantly affected by the higher flows in June and August than in SOS 2c. In 50 percent of water years June flows will exceed 25,000 cfs. Consequently, the most prominent white water rapids will be inundated more frequently during early summer.

SOS 9b and 9c: The somewhat higher flows in June may have minor effects on the waterscape characteristics and, therefore, aesthetic quality of HCNRA.

July and August flows are stable and provide consistent high quality waterscape characteristics.

Preferred Alternative: This SOS is not expected to significantly alter these waterscape characteristics and, therefore, aesthetic quality because of the stable flow regime.

4.2.11.9 Mitigation Opportunities

No mitigation needed or identified for any SOS.

4.2.12 DWORSHAK DAM AND LAKE

4.2.12.1 Description/Hydrologic Characteristics

Recreational suitability of Dworshak Lake is primarily affected by the timing of drawdown and refill. The suitability of the reservoir for recreation is at its optimum when the reservoir is at or near full pool (elevation 1,600 feet). Most of the recreational facilities on the lake, including all boat ramps, remain usable within the upper ten feet of the pool (above elevation 1,590 feet). Drawdowns in excess of that level will begin to reduce the recreational suitability of the reservoir. Extreme drawdown (greater than 20 feet, below elevation 1,980 feet) during the peak summer recreation season will substantially reduce anticipated recreational use.

Table 4-25 shows the average monthly pool elevations (as measured at the forebay of Dworshak Dam) under the 13 alternative SOSs. As shown, under all of the alternatives, the reservoir is at its minimum in March or April and then is gradually refilled, reaching its peak in either June or July. From there the lake is held as high as possible from August through October, although drawdown begins in July or August under most of the SOSs. By the end of September, the lake would be drawn down more than 20 feet under all of the alternatives with the exception of SOS 4c.

Table 4-26 compares the percent probability (over the fifty year period of record) that Dworshak Lake will be refilled to within two, ten and twenty feet of full over the peak recreation months of June through August.

For purposes of characterizing the recreational impacts of the alternative SOSs at Dworshak Lake, they can be combined into the following four groups based on the relative degree of probability that the lake will be at or near full during the summer recreation season of June, July and August.

Overall Recreational Suitability	System Operating Strategy	% Probability Dworshak Lake will remain within 10 ft. of full through June, July and August
Good	4c	100
	5b	100
	5c	100
	6b	100
	6d	100
Moderate	1b	86
	1a	78
	9a	62
Poor	9c	24
	2c	22
	2d	12
Very Poor	9b	2
	PA	0

SOS 1a, the Base Case Alternative, SOS 1b and SOS 9a, would have 78, 86 and 62 percent probability, respectively, that pool elevations during June, July and August will remain within ten feet of full. Consequently, these alternatives are characterized as having moderate impacts on the recreational suitability of Dworshak Lake.

SOS 2c, the No Action alternative, has only a 22 percent probability that pool elevations during June, July and August will be within ten feet of full. It is characterized as a relatively poor alternative for recreation at Dworshak Lake. SOS 9c and 2d are similar.

SOS 4c, 5b, 5c, 6b and 6d are the best alternatives for recreation at Dworshak Lake. All of these alternatives will provide early refill of the reservoir and will maintain it at a high pool elevation through the summer. Under each of these alternatives, Dworshak Lake will remain within ten feet of full from the end of June through the end of August during at least 40 years out of the 50 year period of record (80 percent probability).

Table 4-25. Dworshak Lake — Average Monthly Pool Elevations, Ft. NGVD

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	1527	1509	1493	1507	1557	1589	1591	1584	1571	1567	1554	1543
1b	1523	1505	1490	1504	1563	1593	1594	1592	1570	1566	1551	1538
2c	1543	1528	1517	1514	1553	1585	1581	1568	1564	1566	1559	1555
2d	1533	1520	1511	1502	1549	1576	1537	1538	1538	1540	1541	1540
4c	1539	1523	1519	1528	1570	1597	1599	1599	1599	1599	1569	1558
5b	1531	1517	1515	1526	1571	1598	1600	1600	1560	1579	1563	1549
5c	1532	1517	1515	1526	1571	1598	1600	1600	1550	1551	1549	1542
6b	1533	1518	1516	1526	1571	1598	1600	1600	1580	1575	1559	1544
6d	1533	1518	1516	1526	1571	1598	1600	1600	1580	1575	1559	1544
9a	1533	1518	1505	1498	1558	1584	1572	1569	1556	1554	1546	1545
9b	1528	1515	1504	1470	1509	1546	1524	1525	1526	1528	1531	1534
9c	1537	1522	1509	1505	1563	1583	1574	1563	1563	1563	1555	1553
PA	1532	1521	1511	1507	1557	1589	1552	1520	1521	1524	1529	1536
(full pool = 1,600 ft. NGVD)												

Table 4-26. Dworshak Lake — Percent Probability of Refill to Selected Pool Elevations

SOS	Pool Elevation Feet NGVD)											
	May			June			July			August		
	>1598	>1590	>1580	>1598	>1590	>1580	>1598	>1590	>1580	>1598	>1590	>1580
1a	0	4	14	32	66	84	62	78	82	46	68	78
1b	0	12	30	48	76	88	74	82	88	54	76	86
2c	4	16	28	22	42	72	0	26	52	0	0	22
2d	2	4	24	38	60	68	0	0	12	0	4	18
4c	0	30	52	80	94	100	100	100	100	98	100	100
5b	18	28	52	80	94	100	100	100	100	98	100	100
5c	16	30	52	80	94	100	100	100	100	98	100	100
6b	18	30	52	80	94	100	100	100	100	98	100	100
6d	18	30	52	80	94	100	100	100	100	98	100	100
9a	4	8	26	48	70	76	42	52	64	38	52	62
9b	0	0	6	4	10	22	0	2	8	0	2	4
9c	6	14	40	50	70	78	2	28	50	2	2	24
PA	6	10	30	42	70	86	18	22	28	0	0	0

In comparison, **SOS 9b and the PA** are the worst alternatives for recreational suitability at Dworshak Lake with the probability of June, July and August pool elevations being within ten feet of full at less than 10 percent.

4.2.12.2 Quantitative Results of the Impact Assessment Models

Table 4-27 and Figure 4-7 present the results of the SOR recreation impact assessment model for Lake Dworshak. The model provides a quantitative estimate of recreation use in recreation days for key water related recreation activities during low, average and high water years under each of the alternative SOSs. Table 4-28 compares the estimated total recreation use for each SOS against the base case (SOS 1a), the no action alternative (SOS 2c) and the historic 1992 to 1993 visitation for Dworshak Lake.

An important aspect of the recreation impact model for Dworshak Lake is that a statistically significant number of the survey respondents indicated that

lower water levels at Lower Granite Lake would increase their propensity to visit Dworshak Lake (although the reverse was not found to be true; low water levels at Dworshak Lake did not increase the propensity of visitors to travel to Lower Granite Lake). Therefore, the model results for SOS 5b, 5c, 6b, 6d, and 9a, and to a lesser extent 9c, which feature deep drawdowns at Lower Granite Lake during some or all of the peak summer recreation season, do reflect some of the visitors shifting trips from that project to Dworshak Lake.

With the exception of SOS 2c and 5c, estimated visitation to Dworshak Lake would be higher under high and average water conditions than under low water conditions. Under those two alternatives, the lake would be refilled earlier in spring under low water runoff conditions, providing improved recreation conditions in May and June. Consequently, estimated visitor use under those two SOSs is higher during an extreme low water year (1941), than under average conditions or a high water year (1976).

Table 4-27. Dworshak Lake, Estimated Annual Recreation Days by Activity Under Alternative SOSs

SOS	Boating			Fishing			Camping			Picnicking			Swimming		
	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976
1a	38772	39001	40834	34704	34909	36550	36866	37083	38826	64651	65033	68088	6610	6649	6962
1b	31106	39631	41022	27843	35473	36718	29576	37682	39004	51868	66083	68401	5303	6757	6994
2c	47715	43002	45498	42708	38490	40725	45368	40887	43260	79561	71703	75866	8135	7331	7757
2d	29402	34086	48373	26317	30510	43298	27956	32410	45994	49025	56837	80660	5013	5811	8247
4c	40739	44315	47442	36464	39666	42465	38735	42136	45109	67930	73893	79108	6946	7555	8089
5b	35948	45627	50857	32176	40840	45521	34180	43383	48356	59941	76081	84801	6129	7779	8671
5c	49642	48450	48895	44433	43367	43765	47200	46067	46491	82775	80788	81530	8464	8260	8336
6b	39422	42455	47089	35286	38001	42149	37484	40367	44773	65735	70792	78519	6721	7238	8028
6d	39422	42455	47089	35286	38001	42149	37484	40367	44773	65735	70792	78519	6721	7238	8028
9a	23621	38507	44000	21143	34467	39383	22459	36613	41836	39387	64208	73367	4027	6565	7502
9b	23601	28439	33196	21125	25455	29713	22440	27040	31563	39353	47420	55353	4024	4849	5660
9c	35572	39090	48412	31840	34989	43333	33823	37168	46031	59315	65181	80725	6065	6665	8254
PA	32914	31949	39333	29461	28597	35206	31295	30378	37399	54882	53274	65586	5612	5447	6706

Figure 4-7. Dworshak Lake, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Table 4-28. Dworshak Lake, Estimated Total Annual Recreation Days Under Alternative SOSs

Average Visitation (1987–1993): 210,400 Baseline Visitation (11/92–10/93): 155,300		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	181604	182676	191260
	% change from 2c	–18.74%	–9.30%	–10.25%
	% change from Preferred Alternative	17.80%	22.07%	3.82%
	% change from 92–93		17.63%	
SOS 1b	Total	145697	185625	192138
	% change from 1a	–19.77%	1.61%	0.46%
	% change from 2c	–34.81%	–7.84%	–9.84%
	% change from Preferred Alternative	–5.49%	24.04%	4.29%
SOS 2c	Total	223487	201413	213106
	% change from 1a	23.06%	10.26%	11.42%
	% change from Preferred Alternative	44.97%	34.59%	15.67%
	% change from 92–93		29.69%	
SOS 2d	Total	137712	159655	226572
	% change from 1a	–24.17%	–12.60%	18.46%
	% change from 2c	–38.38%	–20.73%	6.32%
	% change from Preferred Alternative	–10.67%	6.69%	22.98%
SOS 4c	Total	190814	207566	222212
	% change from 1a	5.07%	13.63%	16.18%
	% change from 2c	–14.62%	3.05%	4.27%
	% change from Preferred Alternative	23.77%	38.70%	20.62%
SOS 5b	Total	168373	213711	238205
	% change from 1a	–7.29%	16.99%	24.55%
	% change from 2c	–24.66%	6.11%	11.78%
	% change from Preferred Alternative	9.22%	42.81%	29.30%
SOS 5c	Total	232514	226932	229017
	% change from 1a	28.03%	24.23%	19.74%
	% change from 2c	4.04%	12.67%	7.47%
	% change from Preferred Alternative	50.82%	51.65%	24.31%
SOS 6b	Total	184648	198854	220558
	% change from 1a	1.68%	8.86%	15.32%
	% change from 2c	–17.38%	–1.27%	3.50%
	% change from Preferred Alternative	19.77%	32.88%	19.72%
SOS 6b	% change from 92–93		28.05%	

Table 4-28. Dworshak Lake, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 210,400 Baseline Visitation (11/92–10/93): 155,300		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 6d	Total	184648	198854	220558
	% change from 1a	1.68%	8.86%	15.32%
	% change from 2c	–17.38%	–1.27%	3.50%
	% change from Preferred Alternative	19.77%	32.88%	19.72%
	% change from 92–93		28.05%	
SOS 9a	Total	110637	180361	206088
	% change from 1a	–39.08%	–1.27%	7.75%
	% change from 2c	–50.50%	–10.45%	–3.29%
	% change from Preferred Alternative	–28.23%	20.53%	11.86%
	% change from 92–93		16.14%	
SOS 9b	Total	110543	133202	155485
	% change from 1a	–39.13%	–27.08%	–18.70%
	% change from 2c	–50.54%	–33.87%	–27.04%
	% change from Preferred Alternative	–28.29%	–10.99%	–15.60%
	% change from 92–93		–14.23%	
SOS 9c	Total	166616	183092	226756
	% change from 1a	–8.25%	0.23%	18.56%
	% change from 2c	–25.45%	–9.10%	6.41%
	% change from Preferred Alternative	8.08%	22.35%	23.08%
	% change from 92–93		17.90%	
PA	Total	154163	149645	184230
	% change from 1a	–15.11%	–18.08%	–3.68%
	% change from 2c	–31.02%	–25.70%	–13.55%
	% change from 92–93		–3.64%	

As shown, the estimated visitor use of Dworshak Lake would be about 10 percent higher under SOS 2c (the No Action alternative) than SOS 1a (the Base Case) during average water years. Estimated visitation to Dworshak under SOS 1A would be relatively close under low, average or high water conditions.

SOS 4c, 5b and 5c would all provide moderate increases in recreation use in comparison with SOS 2c in the average water year. There is not a substantial difference between any of these alternatives, but based on the model results, SOS 5c would provide the highest increase in visitor use (12.7 percent compared to SOS 2c), followed by 5b and 4c. All

three alternatives would also provide better recreation conditions than SOS 2c during a typical high water year. During a typical dry year, however, estimated visitation under both SOS 4c and 5b would be lower than SOS 2c.

SOS 1b, 6b, 6d, and 9a all result in small to moderate losses (ten percent or less) in recreation use during average water years in comparison with SOS 2c. As may be expected, these four alternative would all result in severe decreases in estimated visitation during low water years.

SOS 2d, 9b and the Preferred Alternative would all result in severe recreational impacts at Dworshak Lake under average water conditions. SOS 9b

would have the most severe impacts, resulting in an estimated loss in visitation of 34 percent in comparison with SOS 2c during an average water year. The impacts would be somewhat lower in a high water year and somewhat higher in a low water year.

4.2.12.3 Effects on Recreation Facilities/Activities

Under the base case alternative, SOS 1a and SOS 6b, most recreation facilities at Dworshak Lake remain usable during the peak summer recreation season. Exceptions to this generalization include loss of 100 percent of the swimming beaches any time the lake elevation is more than ten feet below full and loss of two out of seven launch ramps when the lake elevation drops to the range of 1555 to 1560 feet. Most of the boat-in mini-camps are only marginally usable when the lake drops below ten feet of full. Under these three alternatives loss of swimming beaches in June, July and August will occur up to 36 percent of years. All other facilities will remain usable, although it should be noted that with elevation fluctuations, financial and personnel requirements are increased to operate and maintain recreation facilities in and adjacent to the drawdown zone.

Under SOS 1b, 4c, 5b and 5c, all recreation facilities at Dworshak Lake remain usable during the peak recreation months of all years, except under SOS 1b where the swimming beaches would be dewatered in approximately 14 percent of years.

Under SOS 2c, many of the water based recreation facilities at Dworshak will be impacted during the peak recreation months. Loss of swimming beaches will occur in June, July and August in 78 percent years. Loss of one or two of the seven launch ramps will occur infrequently under this option. All other facilities will remain usable.

SOS 2d, 9a, 9b, 9c and the PA would all result in moderate to severe impacts to recreational facilities at Dworshak Lake. No swimming beaches will be available in June, July and August during 88 to 100 percent of year. The 76 boat-in mini-camps would be usable only for recreationists willing to cross large and sometimes steep drawdown zones. Under all five alternatives, the majority of years will see a loss

of four out of seven launch ramps. All other facilities will remain usable.

4.2.12.4 Effects on Fish Habitat and Fishing Success

SOR Technical Appendix K, Resident fish, describes the potential impacts of the alternative SOSs on resident game fish species in Dworshak Lake.

Under all SOS alternatives routine annual drawdowns of 50 to more than 100 feet restrict the long-term reservoir productivity due to a lack of macrophytes in the littoral zone, dewatering of the shoreline benthic production, and increased distance between permanent upland vegetation and the water surface. This constitutes a cumulative and long-term loss of available food for game fish species, including bull trout, rainbow trout, cutthroat trout and smallmouth bass. Effects on kokanee for most alternatives is neutral to slightly positive.

Under all SOS alternatives which increased outflows to providing water for downstream anadromous fish, there will be increased kokanee entrainment with deleterious effects on populations and fishing success. These alternatives will also have chronic negative effects on smallmouth bass, rainbow trout, cutthroat trout, and bull trout.

SOS 1b, 2c, 4c, 5b, 5c, 6b and 6d all provide relatively good conditions for all species of resident fish at Dworshak Lake. Fish catching success would be expected to be positive under these alternatives.

4.2.12.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

Due to the fact that Dworshak Lake is a storage reservoir, the impacts to wildlife associated with the loss of native habitat occurred with project construction and are maintained by its continued operation. Steep, rugged topography and lack of major tributaries provides very little area for vegetation to develop in proximity to the shoreline. Also, precipitation is adequate to allow riparian vegetation to develop without being dependent on reservoir elevations. Few, if any, wildlife species are dependent on the reservoir elevation. Consequently, no significant impact on wildlife viewing or hunting opportunities are anticipated under any of the alternatives.

Any operation with a declining lake elevation in the winter will create an ice crusted muddy shoreline or ice jammed shorelines both of which can easily trap large hoofed mammals. The effect on wildlife viewing is neutral to slightly negative, with the worst impacts for viewing occurring during the winter drawdowns.

For game birds, those years with lower summer elevations will create the hazard of the birds crossing the exposed drawdown zone for water.

4.2.12.6 Effects on Recreational Safety and Physical Characteristics

Due to its location in a narrow canyon with steep shorelines, a large amount of vertical drawdown exposes only relatively small areas of exposed mudflats. Exposed rocks, stumps and shoals do create small hazards for boaters. The 76 boat-in mini-camps located around the lake are accessible only by climbing the exposed shoreline. With drawdown greater than approximately 10 feet, access to the sites is severely constrained. Many users are unwilling and unable to carry camping equipment up the shoreline to use these facilities. Floating debris can be a safety hazard during high water periods of the summer season in most years following the low water levels of winter. Floating debris can be expected to move from the shoreline into boating corridors and recreation sites. In many years the present swimming beaches at Dworshak would not be usable during the recreation season. These lower levels will encourage swimming in areas not maintained for that purpose.

There would be no discernible change in recreational safety or physical characteristics of Dworshak Lake under the base case alternative, SOS 1a and 6d.

SOS 1b, 2c, 4c, 5b, 5c, 6b and 6d all feature high, relatively stable summer lake elevations. The impacts to recreational safety and physical characteristics of the shoreline should be reduced under all of these options with the exception of floating debris, which represents little change from the current situation.

SOS 1a, 2d, 9a, 9b, 9c and the PA would all result in increased impacts to recreational safety. Severe drawdown during the summer recreation season would expose extensive areas of rocks, stumps, shoals and other boating hazards. Swimming beaches would frequently not be available in June, July and August under these alternatives, forcing swimmers to use unimproved and less safe swimming areas. The boat-in mini-camps would be usable only for recreationists willing to cross long, rocky and sometimes steep drawdown zones.

4.2.12.7 Effects on Water Quality Parameters Influencing Recreation

Increased turbidity can be expected as a result of the lake elevation fluctuations expected under SOS 1a, 2d, 9a, 9b, 9c and the preferred alternative. None of the other alternatives would be expected to significantly impact water quality parameters affecting recreation activities during the recreation season.

4.2.12.8 Effects on Aesthetics

Dworshak Lake is located in a narrow river canyon for most of its length. Small vertical drawdowns of the lake expose large expanses of "bathtub ring". Exposed unvegetated banks, mudflats and debris deposits can be viewed from the shoreline, recreation sites and roads and have a negative visual effect. These effects will occur under all alternative SOSs, including the base case, SOS 1a, and no action alternative, SOS 2c. However, the timing, extent and duration will vary between SOSs.

SOS 1b, 2c, 4c, 5b, 5c, 6b and 6d all feature high, stable summer lake elevations. The impacts to visual quality should improve over the base case alternative.

In comparison, SOS 1a, 2d, 9a, 9b, 9c and the PA would all substantially increase the extent and duration of drawdown during the summer recreation season when the Dworshak receives its highest visitation, thereby exposing more visitors to the visual impacts of drawdown.

4.2.12.9 Mitigation Opportunities

No mitigation actions are necessary under SOS 1b, 4c, 5b, 5c, 6b and 6d, since these alternatives will

lead to improved recreational conditions at Dworshak Lake in comparison to both the base case alternative, SOS 1a, and the no action alternative, SOS 2c.

Under the base case alternative, SOS 1a, as well as 2c, existing operational impacts to recreational facilities would continue. It may be feasible to modify or extend some recreational facilities to make them usable under the wider range of operating conditions that might occur under these. Where feasible, most of the existing boat ramps on the lake have already been extended to minimum lake elevations; it is not likely that the ramps could be further extended. Given the steepness of the shoreline, it also may not be feasible to modify the existing boat

docks and moorage facilities. Some expansion of swimming facilities may be possible. However, again, these facilities are constrained by the physical characteristics of the site.

SOS 2d, 9a, 9b, 9c and the PA result in severe impacts to recreational facilities at Dworshak Lake. Due to the severity of these impacts, it may no longer be feasible to operate major multi-use recreation sites such as Dworshak State Park. Since on-site mitigation of these impacts might not be feasible, the possibility should be investigated for providing off-site mitigation. One alternative may be the development of a new state park elsewhere in the Clearwater River drainage.

4.2.13 CLEARWATER RIVER BELOW DWORSHAK DAM

4.2.13.1 Description/Hydrologic Characteristics

The optimum flows for steelhead fishing occur when releases from Dworshak Dam are in the range of 3,000 to 7,000 cfs (85 to 198 cms). For determining impacts on winter steelhead fishing, the alternative SOSs can be divided into two groups: (1) those that provide a high probability of flow releases in the optimum range during the peak use period; and (2) those that provide a low probability of flows in the optimum range.

Additionally, it must be recognized that the identified Dworshak releases or flows produced in the hydroregulations and presented in this analysis are monthly averages. The actual daily average flow as well as the instantaneous flows in the lower Clearwater River will be higher and lower than those shown in this report.

SOS 2c (No action alternative), as well as SOS 2d, 4c, 5c, 5b, 9a, 9b, 9c and the preferred alternative (PA), would all have a low probability of providing optimum average monthly flows from Dworshak Dam from November through February (optimum flows in fewer than ten years of out of the 50 year period of record). The month with the lowest probability for optimum flows and the probability that average monthly flows during the four month period will fall into the optimum range are compared below:

SOS	Low Flow Month	Percent Probability Flows will Fall within Optimum Range
2c	February	31
2d	February	20
4c	November	31
5b	February	37
5c	February	40
9a	February	27
9b	November	17
9c	February	30
PA	November	12

For the 50 year hydrologic period of study, under these eight alternatives the month of November will see average releases from Dworshak Dam at the optimum range (3,000 to 7,000 cfs) in a high of 32 years and a low of zero years. In December the optimum average Dworshak outflows will occur in a range from 38 years out of 50 to seven years out of 50. For January optimum Dworshak outflows will occur in the 50 years of study within a range from a high of 17 to a low of eight. The February average release under all of these eight alternatives will provide between 11 and seven years of optimum flows for steelhead fishing.

In comparison, SOS 1a (the Base Case alternative), as well as 1b, 6b and 6d would all have a relatively higher probability of flows falling within the optimum range during the November through February steelhead fishing season (at least 10 out of 50 year period of record). The month with the lowest probability for optimum flows and the probability that average monthly flows during the four month period will fall into the optimum range are compared below:

SOS	Low Flow Month	Percent Probability Flows will Fall within Optimum Range
1a	February	42
1b	February	45
6b	February	47
6d	February	47

For the 50 years of study under these four alternatives, the month of November average releases from Dworshak Dam will be within the optimum range for at least 32 out of the 50 years, with a high of 35 years. In December the alternatives will result in average Dworshak releases within the optimum of between 3,000 cfs and 7,000 cfs in as few as 25 years out of 50 years or as high as 29 years. In January optimum average flows will occur in as few as 14 out of 50 years or in as many as 19 years. The February average Dworshak optimum release will occur in a range from a low of ten years to a high of 14 years out of the 50 years of study.

4.2.13.2 Quantitative Results of the Impact Assessment Models

Table 4-29 and Figure 4-8 present the results of the SOR recreation impact assessment model for fishing on the Clearwater River below Dworshak Dam. The model provides a quantitative estimate of annual fishing use in recreation days during low,

average and high water years under each of the alternative SOSs. The results of the model for each alternative SOS are compared against the Base Case, SOS 1a, No Action alternative, SOS 2c, and the 1992-1993 baseline visitation. The modeling methodology is summarized in Chapter 3 and described in detail in Appendix J-1.

Table 4-29. Clearwater River, Estimated Total Annual Fishing Days Under Alternative SOSs

Average Visitation (1987-1993): 210400 Baseline Visitation (11/92-10/93): 171775		Low Water Year (1941)	50 - Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	124969	109147	102636
	% change from 2c	-3.34%	-14.88%	-24.45%
	% change from Preferred Alternative	44.99%	-27.86%	-48.28%
	% change from 92-93		-36.46%	
SOS 1b	Total	159583	105285	102299
	% change from 1a	27.70%	-3.54%	-0.33%
	% change from 2c	23.43%	-17.89%	-24.70%
	% change from Preferred Alternative	85.15%	-30.41%	-48.45%
SOS 2c	Total	129289	128224	135859
	% change from 1a	3.46%	17.48%	32.37%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	50.01%	-15.25%	-31.53%
SOS 2d	Total	112769	198900	134892
	% change from 1a	-9.76%	82.23%	31.43%
	% change from 2c	-12.78%	55.12%	-0.71%
	% change from Preferred Alternative	30.84%	31.46%	-32.02%
SOS 4c	Total	103898	147346	118452
	% change from 1a	-16.86%	35.00%	15.41%
	% change from 2c	-19.64%	14.91%	-12.81%
	% change from Preferred Alternative	20.55%	-2.61%	-40.31%
SOS 5b	Total	111363	126711	106457
	% change from 1a	-10.89%	16.09%	3.72%
	% change from 2c	-13.87%	-1.18%	-21.64%
	% change from Preferred Alternative	29.21%	-16.25%	-46.35%
SOS 5b	Total	111363	126711	106457
	% change from 1a	-10.89%	16.09%	3.72%
	% change from 2c	-13.87%	-1.18%	-21.64%
	% change from Preferred Alternative	29.21%	-16.25%	-46.35%

Table 4-29. Clearwater River, Estimated Total Annual Fishing Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 210400 Baseline Visitation (11/92–10/93): 171775		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 5c	Total	103539	141589	118100
	% change from 1a	–17.15%	29.72%	15.07%
	% change from 2c	–19.92%	10.42%	–13.07%
	% change from Preferred Alternative	20.13%	–6.42%	–40.48%
	% change from 92–93		–17.57%	
SOS 6b	Total	178242	133905	111428
	% change from 1a	42.63%	22.68%	8.57%
	% change from 2c	37.86%	4.43%	–17.98%
	% change from Preferred Alternative	106.80%	–11.49%	–43.85%
	% change from 92–93		–22.05%	
SOS 6d	Total	178242	133905	111428
	% change from 1a	42.63%	22.68%	8.57%
	% change from 2c	37.86%	4.43%	–17.98%
	% change from Preferred Alternative	106.80%	–11.49%	–43.85%
	% change from 92–93		–22.05%	
SOS 9a	Total	119213	136247	100830
	% change from 1a	–4.61%	24.83%	–1.76%
	% change from 2c	–7.79%	6.26%	–25.78%
	% change from Preferred Alternative	38.32%	–9.95%	–49.19%
	% change from 92–93		–20.68%	
SOS 9b	Total	91491	135271	299870
	% change from 1a	–26.79%	23.93%	192.17%
	% change from 2c	–29.24%	5.50%	120.72%
	% change from Preferred Alternative	6.15%	–10.59%	51.12%
	% change from 92–93		–21.25%	
SOS 9c	Total	100026	143327	105741
	% change from 1a	–19.96%	31.32%	3.03%
	% change from 2c	–22.63%	11.78%	–22.17%
	% change from Preferred Alternative	16.05%	–5.27%	–46.71%
	% change from 92–93		–16.56%	
PA	Total	86189	151296	198435
	% change from 1a	–31.03%	38.62%	93.34%
	% change from 2c	–33.34%	17.99%	46.06%
	% change from 92–93		–11.92%

Figure 4-8. Clearwater River, Estimated Fishing Use for Alternative SOSs (Low, Average & High Water Years)

The predominant recreational activity on the Clearwater River is fishing. In 1987, the most recent thorough study of recreation use of the Clearwater River, from the confluence of the North Fork with the mainstem 1.9 miles below Dworshak Dam, downstream to Lower Granite Lake, reported that over 80 percent of the annual recreation use occurred during the steelhead fishing season from November through February (Krumpe, 1987). Natural resource managers in the area are now reporting a more even mix of recreation use between steelhead fishing in the winter months and the other summer river recreation activities. The model presents estimates of total annual fishing use on the river. It focuses on the

winter steelhead fishing activity, but recognizes both winter and summer visitation.

The baseline visitation data used in the model is based on an estimate of 79,352 steelhead angler days for the fall of 1992 through the spring of 1993, which runs roughly from September through April (McArthur, IDFG, personal communication). This estimate was combined with the SOR Recreation survey results (see Appendix J-1) of actual the trips reported by Clearwater River users during the summer of 1993 to obtain an estimate of annual fishing use. About 46 percent of the trips reported in the survey occurred during nonsummer months which roughly coincides

with the steelhead season. Assuming that multiple-day trips comprise similar proportions in the summer and nonsummer seasons, the estimated total annual fishing use is approximately 171,775 trips.

The model also has one important limitation. Predictions for the Clearwater River model tend to overestimate demand for those alternative SOSs which have instream flows that increase above the maximum optimum (7,000 cfs). At high flow rates, the model predicts a steady increase in visitation, even when the flow rate is above the optimum level. As shown, for an average water year, the model estimates that annual fishing use on the Clearwater River would be approximately 15 percent higher under SOS 1a than under SOS 2c. For SOS 2d, 4c, 5c, 6b, 6d, 9a, 9b, 9c, and the PA, the model predicts substantial increases in fishing when compared to both SOS 1a and 2c. SOS 5b shows a moderate increase over SOS 1A but a slight decrease from SOS 2c. SOS 1b is the only alternative that shows a substantial decrease in use when compared with both SOS 1a and 2c.

However, due to limitations of the impact assessment model that is used to provide the visitation estimates in this report, those alternatives with high summer Dworshak fish flushing flows show estimates with unrealistic increases in annual use over alternatives 1a and 2c. This model limitation is especially significant in alternative 2d, which shows a 82 percent increase over SOS 1a and a 55 percent increase over SOS 2c, but also is reflected in the estimates for alternatives 9a, 9b, 9c and the preferred alternative.

Except for the increase shown under SOS 6b and 6d these higher levels of use are the result of the model limitation previously discussed. The best alternatives for recreation on the Clearwater River appears to be SOS 6b and 6d, when the model limitation is factored in. SOS 6b and 6d would allow a 23 percent increase in visitation in comparison SOS 1a.

4.2.13.3 Effects on Recreation Facilities/Activities

Releases from Dworshak Dam affect both the ability of anglers to gain shoreline and boat access to the river, and fish catching success. As previously described, the optimum flows for steelhead fishing

occur when releases from Dworshak Dam are in the range of 3,000 to 7,000 cfs (85 to 198 cms). Flows below 3,000 cfs expose rocks and shoals, making boating difficult. Low flows also dewater fishing holes. Flows above 7,000 cfs begin to flood out boat ramps, make it difficult for drift boats to hold over fishing holes, and inundate shoreline access areas.

Most of the recreation sites along the lower Clearwater River are minimally developed. Boat ramps and other facilities are designed to remain usable under a range of normal flows. All of the on shore recreation facilities on the lower Clearwater River remain usable during the peak steelhead fishing season in all of the alternative SOSs. Launch ramps will be impacted in many years and months during the lower and higher daily releases from Dworshak Dam.

4.2.13.4 Effects on Fish Habitat and Fishing Success

None of the alternative SOSs are expected to have a significant effect on winter steelhead populations in the Clearwater River. The varying flow regimes under the alternatives will affect fish catching success by impacting the ability of anglers to gain access to the fish and to accustomed fishing holes. Changes in flow may also affect whether or not fish are biting. These impacts are at least partially reflected in the impact assessment model results.

4.2.13.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

None of the alternatives under consideration are expected to have any significant effects on wildlife viewing or hunting opportunities along the Clearwater River.

4.2.13.6 Effects on Recreational Safety and Physical Characteristics

All SOS alternatives provide minor to major changes from current (SOS 1a) lower Clearwater River flows. Major changes in recreation safety and physical characteristics will occur over the course of normal operations of Dworshak Dam. Initially users will need to become familiar with any changes in the current river flows. Significantly higher flows from the main fork of the Clearwater River, which is not

influenced by Dworshak Dam and/or flood releases from Dworshak will still occur at times. During these events, the inherent safety hazards of a free flowing river will increase in the lower Clearwater River.

4.2.13.7 Effects on Water Quality Parameters Influencing Recreation

The overall effects of these alternatives on water quality parameters affecting recreation are neutral.

4.2.13.8 Effects on Aesthetics

None of the alternative SOSs under consideration is expected to have a significant impact on visual quality or other aesthetic parameters along the lower Clearwater River.

4.2.13.9 Mitigation Opportunities

Little in the way of mitigation will be possible in these alternatives. Some launch ramps can be extended to provide availability during lower flow periods. Coordination of timing and ramping of Dworshak releases may provide additional mitigation opportunities.

4.2.14 LOWER GRANITE LOCK AND DAM – LOWER GRANITE LAKE

4.2.14.1 Description/Hydrologic Characteristics

Variation between SOSs at Lower Granite is reflected in the timing of drawdown and refill. Table 4–30 shows the average monthly pool elevations (as measured at the forebay of Lower Granite Dam) under the 13 alternative SOSs.

Under SOS 1a, 1b, 2c, 2d, 4c, 9b and the Preferred Alternative (PA), Lower Granite Lake would remain within the five foot normal operational range of the dam (between full pool at elevation 738 feet and minimum normal operating pool of 733 feet) year–

round with no significant impacts on recreational use of the lake.

In comparison, all of the remaining alternatives, including SOS 5b, 5c, 6b, 6d, and 9a, feature deep drawdowns during the entire peak summer recreation season. Under these alternatives, May through August elevations for Lower Granite Lake will range from 33 feet to more than 110 feet below full every year. Consequently, these alternatives would have severe impacts on recreational use of the reservoir. The most severe impacts would occur under SOS 5c, under which the reservoir would be drawn down over 110 feet year–round.

SOS 9c would draw Lower Granite Lake down approximately 40 feet during April and May, but the lake would be refilled by the end of June and would remain there.

Table 4–30. Lower Granite Lock and Dam/Lower Granite Lake — Average Monthly Pool Elevations for Alternative SOSs

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	735.3	735.3	735.3	735.3	725.1	735.3	735.3	735.3	735.3	735.3	735.3	735.3
1b	735.3	735.3	735.3	735.3	735.3	735.3	735.3	735.3	735.3	735.3	735.3	735.3
2c	735.3	735.3	735.3	733.5	733.5	733.5	733.5	735.3	735.3	735.3	735.3	735.3
2d	735.3	735.3	735.3	733.5	733.5	733.5	733.5	735.3	735.3	735.3	735.3	735.3
4c	735.3	735.3	735.3	733.5	733.5	733.5	733.5	735.3	735.3	735.3	735.3	735.3
5b	735.3	715	653	623	623	623	623	623	735.3	735.3	735.3	735.3
5c	623	623	623	623	623	623	623	623	624.1	623	623	623
6b	735.3	735.3	735	705	705	705	705	705	735.3	735.3	735.3	735.3
6d	735.3	735.3	735.3	705	705	705	705	705	735.3	735.3	735.3	735.3
9a	732.9	732.9	732.9	704.9	704.9	704.9	704.9	704.9	732.9	732.9	732.9	732.9
9b	735.3	735.3	735.3	733.5	733.5	733.5	733.5	735.3	735.3	735.3	735.3	735.3
9c	735.3	735.3	735.3	695	695	735.3	735.3	735.3	735.3	735.3	735.3	735.3
PA	735.3	735.3	735.3	733.5	733.5	733.5	733.5	735.3	735.3	735.3	735.3	735.3

= Outside of normal operating pool; significant recreational impacts

4.2.14.2 Quantitative Results of the Impact Assessment Models

Table 4-31 and Figure 4-9 present the results of the SOR recreation impact assessment model for Lower Granite Lake. The model provides a quantitative estimate of recreation use in recreation days for key water related recreation activities during low, average and high water years under each of the alternative SOSs. Table 4-32 compares the estimated total recreation use for each SOS against the base case (SOS 1a), the no action alternative (SOS 2c) and the baseline visitation (October 1992 through September 1993) for Lower Granite Lake. Results are shown for the 50-year average, as well as for an extreme low-water year (1941) and extreme high water year (1976).

Based on the model results, **SOS 1b** would be the best alternative for recreation at Lower Granite Lake under average, low or high water conditions. It shows a slight increase in visitation (2 percent) over both the

Base Case, SOS 1a, as well as the average annual visitation over the actual 1987 through 1993 visitation (1 percent). For the alternatives under consideration, the recreation impact analysis for Lower Granite Lake is simple. For those SOS under which the pool elevation would remain within their normal operating range, there would be little or no recreational impact. For those alternatives under which deep drawdowns would be implemented, recreational impacts would be moderate to severe.

SOS 2c, 2d, 4c, 9b and the PA all result in an estimated slight gain or loss in visitation when compared with SOS 1a (plus or minus 3.2 percent). The slight differences between these alternatives is attributable to the relatively stable lake elevations under them all.

SOS 9c would result in a moderate loss (approximately 10 percent) in recreation visitation when compared to SOS 1a. This decline is attributable to deep drawdowns in April and May.

Table 4-31. Lower Granite Lake, Estimated Annual Recreation Days by Activity Under Alternative SOSs

SOS	Boating			Fishing			Camping			Picnicking			Swimming		
	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976
1a	297469	327303	339333	171657	188873	195815	70346	77402	80247	731271	804612	834187	232383	255690	265088
1b	330813	333877	339333	190899	192667	195815	78232	78956	80247	813241	820774	834187	258432	260826	265088
2c	325249	329048	333501	187688	189880	192450	76916	77814	78867	799563	808903	819849	254085	257053	260532
2d	325249	329048	333501	187688	189880	192450	76916	77814	78867	799563	808903	819849	254085	257053	260532
4c	306540	326490	330752	176892	188404	190863	72492	77209	78217	753572	802614	813092	239470	255055	258384
5b	169827	170053	170415	98000	98131	98339	40161	40215	40300	417487	418044	418932	132669	132846	133128
5c	128861	129088	129449	74361	74492	74700	30474	30527	30613	316781	317339	318227	100667	100844	101126
6b	245587	247380	250333	141718	142753	144457	58077	58501	59200	603729	608137	615398	191853	193254	195561
6d	245587	247380	250333	141718	142753	144457	58077	58501	59200	603729	608137	615398	191853	193254	195561
9a	222133	232599	251227	128184	134224	144973	52531	55006	59411	546072	571802	617595	173531	181707	196259
9b	302817	320265	331918	174743	184812	191536	71611	75737	78493	744419	787312	815958	236561	250192	259295
9c	291170	293976	296606	168022	169642	171159	68857	69520	70142	715786	722685	729151	227462	229655	231710
PA	327316	331178	334529	188881	191109	193043	77405	78318	79110	804646	814138	822376	255700	258717	261335

Figure 4–9. Lower Granite Lake, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Table 4–32. Lower Granite Lake, Estimated Total Annual Recreation Days Under Alternative SOSs

Average Visitation (1987–1993): 1529800 Baseline Visitation (11/92–10/93): 1670600		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	1503126	1653879	1714670
	% change from 2c	–8.54%	–0.53%	1.75%
	% change from Preferred Alternative	–9.12%	–1.17%	1.44%
	% change from 92–93		–1.00%	
SOS 1b	Total	1671616	1687100	1714670
	% change from 1a	11.21%	2.01%	0.00%
	% change from 2c	1.71%	1.47%	1.75%
	% change from Preferred Alternative	1.07%	0.82%	1.44%
	% change from 92–93		0.99%	

Table 4-32. Lower Granite Lake, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 1529800 Baseline Visitation (11/92–10/93): 1670600		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 2c	Total	1643500	1662699	1685198
	% change from 1a	9.34%	0.53%	–1.72%
	% change from Preferred Alternative	–0.63%	–0.64%	–0.31%
	% change from 92–93		–0.47%	
SOS 2d	Total	1643500	1662699	1685198
	% change from 1a	9.34%	0.53%	–1.72%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	–0.63%	–0.64%	–0.31%
SOS 4c	Total	1548965	1649772	1671309
	% change from 1a	3.05%	–0.25%	–2.53%
	% change from 2c	–5.75%	–0.78%	–0.82%
	% change from Preferred Alternative	–6.35%	–1.42%	–1.13%
SOS 5b	Total	858143	859290	861114
	% change from 1a	–42.91%	–48.04%	–49.78%
	% change from 2c	–47.79%	–48.32%	–48.90%
	% change from Preferred Alternative	–48.12%	–48.65%	–49.06%
SOS 5c	Total	651144	652290	654115
	% change from 1a	–56.68%	–60.56%	–61.85%
	% change from 2c	–60.38%	–60.77%	–61.18%
	% change from Preferred Alternative	–60.63%	–61.02%	–61.30%
SOS 6b	Total	1240964	1250024	1264949
	% change from 1a	–17.44%	–24.42%	–26.23%
	% change from 2c	–24.49%	–24.82%	–24.94%
	% change from Preferred Alternative	–24.97%	–25.30%	–25.17%
SOS 6d	Total	1240964	1250024	1264949
	% change from 1a	–17.44%	–24.42%	–26.23%
	% change from 2c	–24.49%	–24.82%	–24.94%
	% change from Preferred Alternative	–24.97%	–25.30%	–25.17%
SOS 9a	Total	1122451	1175338	1269465
	% change from 1a	–25.33%	–28.93%	–25.96%
	% change from 2c	–31.70%	–29.31%	–24.67%
	% change from Preferred Alternative	–32.14%	–29.77%	–24.90%
SOS 9b	Total	1530151	1618319	1677201
	% change from 1a	1.80%	–2.15%	–2.19%
	% change from 2c	–6.90%	–2.67%	–0.47%
	% change from Preferred Alternative	–7.48%	–3.30%	–0.78%
SOS 9b	Total	1530151	1618319	1677201
	% change from 1a	1.80%	–2.15%	–2.19%
	% change from 2c	–6.90%	–2.67%	–0.47%
	% change from Preferred Alternative	–7.48%	–3.30%	–0.78%

Table 4-32. Lower Granite Lake, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 1529800 Baseline Visitation (11/92–10/93): 1670600		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 9c	Total	1471296	1485478	1498768
	% change from 1a	–2.12%	–10.18%	–12.59%
	% change from 2c	–10.48%	–10.66%	–11.06%
	% change from Preferred Alternative	–11.04%	–11.23%	–11.34%
	% change from 92–93		–11.08%	
PA	Total	1653949	1673460	1690393
	% change from 1a	10.03%	1.18%	–1.42%
	% change from 2c	0.64%	0.65%	0.31%
	% change from Preferred Alternative	0.00%	0.00%	0.00%
	% change from 92–93		0.17%	

The remaining alternatives, including **SOS 5b, 5c, 6b, 6d, and 9a** would all have severe effects on recreational use of Lower Granite Lake due to extreme drawdown during the summer recreation season. The severity of the loss in visitation is dependent primarily on the length of the period in which the reservoir is drawn down, rather than on the depth of drawdown. The most severe impacts would occur under SOS 5c, with an estimated 61 percent loss of visitation compared to SOS 1a. Under this alternative, the lake would be drawn down year round. Under SOS 5b, the drawdown would occur over a seven month period, visitation losses estimated at about 48 percent. Under SOS 6b, 6d and 9a, the lake would be drawn down for a five month period with corresponding estimated losses in visitation ranging from about 25 to 30 percent. Each of these alternatives feature drawdown for almost the entire summer recreation season, May through August.

4.2.14.3 Effects on Recreation Facilities/Activities

Existing recreation facilities at Lower Granite Lake were designed to remain usable under normal operating conditions, which involved daily and weekly fluctuations of one to three feet in the upper five feet of the pool. The facilities remain usable down to five feet of drawdown. Swimming beaches and launch ramps will be slightly impacted at the lowest average lake elevations (five feet below full). Past that point,

most of the facilities on the lake become rapidly unusable.

Under **SOS 1a, 1b, 2c, 2d, 4c, 9b** as well as the preferred alternative, most recreation facilities remain fully usable during the entire peak recreation season except for the May drawdowns under alternative 1a for 13 out of 50 years described in section 4.2.14.1. The recreation impact assessment model show a slight decline in visitation for all these alternative. This impact is attributable to the fact that some facilities, particularly swimming beaches, will become marginally less usable at lower lake elevations.

Under **SOS 5b, 5c, 6b, 6d, 9a, and 9c**, impacts to recreation facilities will be severe. Under all these alternatives except 9c, lake elevations would range from 33 to 115 feet down in May through August. Virtually none of the recreation facilities, including boat ramps, boat docks, marinas, moorage's or swimming beaches are usable at that level of drawdown. Alternative 9c provides a May elevation 43 feet below full, that elevation would rise to 2.7 feet from full for June, July and August.

During deep drawdowns (anything greater than 5 feet), boat access to the lake would be virtually eliminated for anything other than small hand carry craft. The lake could be accessed by boats entering either the Clearwater or Snake Rivers and then traveling downstream. However, no boat ramps or other facilities on the lake proper would be usable.

4.2.14.4 Effects on Fish Habitat and Fishing Success

Sports fish species at Lower Granite Lake include anadromous species (salmon and steelhead) and resident species (smallmouth bass, walleye, sturgeon). No significant change in anadromous fish populations is expected under any of the alternatives. Under SOS 1a, daily and weekly fluctuations in lake elevations result in a loss of spawning habitat, reduction in food production from dewatering of shoreline benthos, and stranding of fry in the in-shore habitat with negative impacts on smallmouth bass. Since elevations are held somewhat more constant under SOS 1b, 2A, 2c, 2d, 4c, 9b, and the PA, these alternatives would all provide better habitat for that species and some improvement in fishing success may be expected.

Overall, SOS 5b, 6b, 6d, 9a and 9c are not very good for resident fish species because of extreme seasonal fluctuations in reservoir. Some decline in resident fish populations, particularly smallmouth bass, could be expected. The impact of this decline is not incorporated into the impact assessment model for Lower Granite Lake due to a lack of data connecting pool elevations to fish populations to fish catching success per unit of effort. However, the models do reflect impacts to fishing access under these alternatives which are consistent with potential impacts to fish populations.

Alternative 5c provides a stable lake elevation, 115 feet below the current full lake elevation. This SOS would eventually lead to optimal habitat conditions for resident and anadromous species, but stabilization of the existing in water sediment deposits would be disruptive in the beginning.

4.2.14.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

In comparison with SOS 1a, the stable pool elevations under alternatives 1b, 2c, 2d, 4c, 5c, 9b and the preferred alternative may be expected to provide an increase in development of riparian habitat along the shoreline with a small increase in opportunities for

viewing a variety of wildlife species. Hunting for waterfowl is not a major activity along Lower Granite Lake and no significant change would be expected.

Alternatives 5b, 6b, 6d, 9a and 9c would exert the greatest impact on Lower Granite Lake, eliminating or at least significantly reducing utilization of the reservoir and adjacent habitat for nearly all species with any aquatic or riparian habitat dependency, including a local reproducing population of mallard, great blue heron, spotted sandpiper, beaver, river otter, and Canada goose. Substantial loss of wildlife viewing opportunity would be expected.

4.2.14.6 Effects on Recreational Safety and Physical Characteristics

Under SOS 1a, 1b, 2c, 2d, 4c, 9b and the preferred alternative, there would be little change from current Lower Granite Lake elevations. No significant effects on recreation safety and physical characteristics are expected.

During periods of severe drawdown under SOS 5b, 6b, 6d, 9a and 9c, the lake would provide a completely different recreation experience than currently exists. The lake will be drawn down further into its natural canyon. At extreme drawdowns, the Snake and Clearwater River sections at the upper ends of the lake will be returned to free-flowing river conditions. This may provide opportunities for rafting and other whitewater activities that do not presently exist, but access into and out of the canyon will be difficult since the existing boat ramps will be unusable.

Extensive mudflats within the former pool will be exposed. The disturbance of former in-water sediment deposits from past operations will create new and shifting shoaling as the deposits adjust to the changed operation.

Under SOS 5c, Lower Granite Lake would be stable, 115 feet below the current full lake. This will result in significant public safety problems as sediment deposits and the dewatered shoreline adjusts to the changed operation.

4.2.14.7 Effects on Water Quality Parameters Influencing Recreation

Under SOS 1a, 1b, 2c, 2d, 4c, 9b and the preferred alternative, stable or relatively stable pool elevations will not increase sedimentation and turbidity from current operations.

Alternative 5c will result in significant initial water quality degradation due to the drawdown to a stable elevation of 115 feet below current lake levels.

In comparison, SOS 5b, 6b, 6d, 9a and 9c will create negative impacts on water quality due to an increase in sedimentation and turbidity as a result of the lower lake elevations and exposure of former in-water sediment deposits. The negative impacts on recreational water quality will be especially severe under alternative 5a which results in a water level over 100 feet below full for several spring through summer months.

4.2.14.8 Effects on Aesthetics

Under SOS 1a, 1b, 2c, 2d, 4c, 9b and the preferred alternative, there will be no significant effect on visual quality or other aesthetic parameters.

SOS 5b, 6b, 6d, 9a and 9c would result in significant negative impacts to the existing aesthetics of Lower Granite Lake. Under all of these alternatives, large drawdown zones within the Snake River Canyon will be exposed for varying periods of time during the year. In its natural state, the canyon and unpounded river were quite scenic. However, the inundation by Lower Granite Lake has left sediment deposits and eliminated vegetation. Under these alternatives, mudflats and steep canyon walls will be exposed for varying periods of time. Seasonal fluctuation of the lake elevation back to full pool would prevent the aesthetic from being softened through revegetation over time.

SOS 5c would result in a permanent year-round drawdown of Lower Granite Lake 115 feet below full pool. The short term impacts on aesthetic quality would be similar to those described above for the other drawdown alternatives. The long-term aesthetic impacts of SOS 5c are harder to determine. It is expected that the Snake River Canyon

would eventually be restored to historic natural scenic qualities as sediment is washed back into the river and natural vegetation is restored. It is unknown how long it will take this process to occur.

4.2.14.9 Mitigation Opportunities

Under SOS 1a, 1b, 2c, 2d, 4c, 9b and the preferred alternative, little in the way of mitigation will be necessary. Some swim beaches and launch ramps may need to be extended or dredged to provide a full range of availability to visitors down to minimum operating pool. The May elevations under alternative 1a will effectively eliminate recreation use in 13 out of 50 years.

Extensive mitigation would be necessary under alternatives SOS 5b, 5c, 6b, 6d, 9a and 9c. Swim beaches and launch ramps will need to be extended to provide a full range of availability to visitors. Under alternatives 5b, 6b, 6d, 9a and 9c the facilities will need to transition through the entire range of the lake operation, which is over 100 vertical feet. With alternative 5c, most of the recreation facilities would need to be relocated to the lower operating level.

For more severe drawdown ranges, the degree of difficulty and costs for structural modification of facilities increases dramatically. In a study undertaken as part of the 1992 Options EIS, the Corps Walla Walla District estimated that the cost of modifying recreation facilities at Lower Granite Lake and Lake Sacajawea under the drawdown alternative considered was in the neighborhood of \$15 million.

The severity of impacts to recreation facilities and activities at Lower Granite Lake may be so severe that it is infeasible to modify recreational facilities onsite to mitigate for impacts. It may be physically impossible to modify facilities to accommodate the range of fluctuations considered. However, a point can also be reached where drawdown diminishes aesthetics and other parameters of recreational suitability to a point where modification of facilities at that project is not a reasonable mitigation option. When drawdowns result in impacts that are severe, the only feasible mitigation options may include relocation or replacement of facilities in-kind elsewhere in the region.

4.2.15 ICE HARBOR LOCK AND DAM/LAKE SACAJAWEA, LOWER MONUMENTAL LOCK AND DAM/LAKE WEST, AND LITTLE GOOSE LOCK AND DAM/LAKE BRYAN

4.2.15.1 Description/Hydrologic Characteristics

Recreational impact assessments for these three run-of-river projects have been combined because the three projects are very similar in terms of physical and operational characteristics and in terms of the level of recreational development and use. Also, the alternative SOSs under consideration as well as the preferred alternative will have very similar impacts at each.

Variation between SOSs at these three lower Snake River reservoirs is reflected in the timing of drawdown and refill. Table 4-33 shows the average monthly pool elevations (as measured at the forebays of Little Goose, Lower Monumental and Ice Harbor Dams) under the 13 alternative SOSs.

Under SOS 1a, 1b, 2c, 2d, 4c, 9b and the Preferred Alternative (PA), The three reservoirs would all remain within their three to five foot normal operational ranges year-round with no significant impacts

on recreational use of the lake. Under SOS 1a, 1b, and 2c, all three lakes would be operated in the upper two feet of pool elevation with daily and weekly fluctuations in that range. Under SOS 2d, 4c, 6d, 9b and the PA, lakes Bryan, West and Sacajawea would be stable within the upper seven and a half feet of the normal operational range of the dams for the entire peak summer recreation season of May, June, July and August. The minor variations in pool elevation under these alternatives would result in insignificant impacts to the recreational use of the lakes.

Similarly to Lower Granite Lake, all of the remaining alternatives, including SOS 5b, 5c, 6b, 6d, and 9a, feature deep drawdowns during the entire peak summer recreation season at all three lakes. Under these alternatives, May through August elevations for Lower Granite Lake will range from around 25 feet to more than 100 feet below full every year. Consequently, these alternatives would have severe impacts on recreational use of the reservoir. The most severe impacts would occur under SOS 5c, under which the reservoirs would be drawn down year-round.

SOS 9c would draw the lakes down approximately 30 to 40 feet for three to four months during March to June, but the lake would be refilled by the end of June and would remain there through the balance of summer.

Table 4-33. Little Goose, Lower Monumental and Ice Harbor Projects, Average Monthly Pool Elevations (ft. NGVD) under Alternative SOSs

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Little Goose Lock and Dam/Lake Bryan												
1a,1b,2c	636	636	636	636	636	636	636	636	636	636	636	636
2d,4c,6d,9b, PA	636	636	636	636	634	634	634	636	636	636	636	636
5b	636	616	554	524	524	524	524	524	636	636	636	636
5c	525	524	524	524	524	524	524	524	524	524	524	524
6b	636	636	635	605	605	605	605	605	636	636	636	636
9a	633	633	633	605	605	605	605	605	633	633	633	633
9c	636	636	595	595	595	536	636	636	636	636	636	636

Table 4-33. Little Goose, Lower Monumental and Ice Harbor Projects, Average Monthly Pool Elevations (ft. NGVD) under Alternative SOSs – CONT

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Lower Monumental Lock and Dam/Lake West												
1a,1b,2c	539	539	539	539	539	539	539	539	539	539	539	539
2d,4c,6d,9b,PA	539	539	539	538	538	538	538	539	539	539	539	539
5b	539	524	462	432	432	432	432	432	539	539	539	539
5c	433	432	432	432	432	432	432	432	432	432	432	432
6b	539	539	537	507	507	507	507	507	539	539	539	539
9a	537	537	537	507	507	507	507	507	537	537	537	537
9c	539	539	495	498	499	539	539	539	539	539	539	539
Ice Harbor Lock and Dam/Lake Sacajawea												
1a,1b,2c	439	439	439	439	439	439	439	439	439	439	439	439
2d,4c,6d,9b,PA	439	439	439	438	438	438	438	439	439	439	439	439
5b	439	435	373	343	343	343	343	343	439	439	439	439
5c	344	343	343	343	343	343	343	343	343	343	343	343
6b	439	439	437	407	407	407	407	407	439	439	439	439
9a	437	437	437	407	407	407	407	407	437	437	437	437
9c	439	439	405	405	405	439	439	439	439	439	439	439

= Pool elevations outside of the normal operating range of the lakes; substantial recreation impacts

4.2.15.2 Quantitative Results of the Impact Assessment Models

During initial phases of development of the SOR recreation impact assessment models, a decision was made to conduct recreation surveys and construct an impact assessment for Lower Granite Lake only on the lower Snake River and extrapolate the results to the other three projects. This decision was based on the fact Lower Granite Lake receives approximately 64 percent of the total visitation to the four projects combined. In addition, the four projects are very similar in terms of size, physical characteristics and type and extent of existing recreational facilities and activities. Most of the alternative SOSs will have similar impacts at the four projects because the drawdown ranges under consideration are similar at all four projects.

The expectation of similar impacts allows the average monthly demand results from the Lower Granite models to be imputed for the other three lower Snake projects. Essentially, the Lower Granite results have been calibrated to the baseline 1993 visitation levels at each of the other three projects. This extrapolation requires the assumption that recreators at the other three projects have preferences over water levels that are comparable to recreator preferences at Lower Granite. Additional adjustments had to be made in three of the alternatives where Lower Granite Lake would be operated differently than the other three projects, SOS 1b, 5c and 6a. These adjustments are described in detail in Appendix J-1, Chapter 6. The four run-of-river projects on the lower Snake River, these three plus Lower Granite.

Table 4-34 presents the results of the SOR recreation impact assessment models for lakes West, Bryan, and Sacajawea. The results provide quantitative estimates of recreation use in recreation days for key water related recreation activities during low, average and high water years under each of the alternative SOSs. Tables 4-35, 4-36, and 4-37 compare the estimated total recreation use for each SOS against the base case (SOS 1a), the no action alternative (SOS 2c) and the historic 5 year visitation (1987 to 1991) for the three lakes, respectively. Figures 4-10, 4-11, and 4-12 graphically display these same results.

SOS 1a and 1b would be the best alternatives for recreation at all three lakes. At lakes West, Bryan and Sacajawea, these alternatives show a slight increase in visitation over SOS 2c (ranging between 2.2 and 1.7 percent), while SOS 2c, 2d, 4c, 6d, 9b and the preferred alternative result in a small estimated decrease in visitation (less than six percent) in comparison with the No Action alternative, SOS 1a.

The remaining alternatives would all have severe effects on recreational use of all three lakes due to extreme drawdown during the summer recreation season. The severity of the loss in visitation is dependent primarily on the length of the period in which the lakes are drawn down, rather than on the depth of drawdown. The most severe impacts would occur under **SOS 5b and 5c**, with an estimated loss of 60 to 75 percent of visitation compared to SOS 1a. **SOS 6b, 5a and 6a** would have lesser, but still severe impacts on estimated recreational use at all three lakes.

4.2.15.3 Effects on Recreation Facilities/Activities

Under SOS 1a, 1b, and the PA, all recreation facilities at lakes West, Bryan and Sacajawea would remain fully usable throughout the entire year.

The slight decline in visitation at Lakes West and the moderate decline in visitation at Lake Bryan shown by the impact assessment models for **SOS 2c, 2d, 4c, 6d and 9b** in comparison with SOS 1a, reflects the fact that swimming beaches and launch ramps will be impacted at the lowest average lake elevations (three to seven and a half feet below full) maintained during the summer recreation season at the lakes.

Under SOS 5b, 5c, 6b, 9a and 9c impacts to recreation facilities will be severe. Under these alternatives, pool elevations would range from 30 to 116 feet down in May at all three lakes. Virtually none of the recreation facilities, including boat ramps, boat docks, marinas, moorages or swimming beaches are usable at that level of drawdown at either lake. Only alternative 9c provides relief from these severe drawdowns in June, July and August with lake elevations within 2 feet of full at all lakes for the last three months of the peak recreation season.

4.2.15.4 Effects on Fish Habitat and Fishing Success

Sports fish species at lakes West, Bryan and Sacajawea include anadromous species (salmon and steelhead) and resident species (smallmouth bass, walleye, sturgeon). No change in anadromous fish populations is expected under any of the alternatives. Under most of these SOS alternative, daily and weekly fluctuations in lake elevations result in a loss of spawning habitat, reduction in food production from dewatering of shoreline benthos, and stranding of fry in-shore habitat with negative impacts on smallmouth bass. Since the lakes are held somewhat more constant under SOS 1a and 1b these alternatives would all provide better habitat for that species and some improvement in fishing success may be expected. Alternative 5c provides a stable lake elevation at all three lakes at an elevation between 90 and 120 feet below the current full lake.

Overall, SOS 5c, 5b, 6b, 9a and 9c are not very good for resident fish species because of extreme seasonal fluctuations in the reservoirs. Some decline in resident fish populations, particularly smallmouth bass, is expected. Consequently, fish catching success would also be expected to decline. The impact of this decline is not directly incorporated into the recreation impact assessment models for the three lakes due to a lack of data connecting pool elevations to fish populations to fish catching success per unit of effort. However, the models do reflect impacts to fishing access under these alternatives which are consistent with potential impacts to fish populations.

Table 4-34. Lower Snake River Projects, Estimated Annual Recreation Days by Activity Under Alternative SOSs

SOS	Boating			Fishing			Camping			Picnicking			Swimming		
	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976
Little Goose Lock and Dam/Lake Bryan															
1a	42683	43231	44295	26973	27319	27991	22961	23256	23828	106732	108102	110762	42369	42913	43969
1b	42683	43242	44295	26973	27327	27991	22961	23262	23828	106732	108131	110762	42369	42924	43969
2c	41755	42455	43316	26387	26829	27373	22462	22838	23302	104412	106162	108315	41448	42142	42998
2d	41755	42455	43316	26387	26829	27373	22462	22838	23302	104412	106162	108315	41448	42142	42998
4c	38917	42315	42955	24593	26741	27145	20935	22763	23107	97314	105812	107411	38631	42004	42639
5b	16324	16366	16436	10316	10342	10387	8781	8804	8842	40820	40923	41100	16204	16245	16315
5c	12522	12564	12635	7913	7940	7984	6736	6759	6797	31313	31417	31594	12430	12471	12542
6b	28707	29033	29607	18141	18347	18710	15443	15618	15927	71783	72600	74034	28496	28820	29389
6d	41755	42455	43316	26387	26829	27373	22462	22838	23302	104412	106162	108315	41448	42142	42998
9a	25197	26827	29763	15923	16953	18808	13554	14431	16011	63006	67083	74424	25011	26630	29544
9b	38146	41161	43077	24106	26011	27222	20520	22142	23173	95388	102926	107717	37866	40858	42760
9c	35408	35906	36453	22375	22690	23036	19047	19315	19610	88539	89785	91153	35147	35641	36185
PA	42149	42853	43517	26635	27080	27500	22673	23052	23410	105396	107157	108818	41838	42538	43197
Lower Monumental Lock and Dam/Lake West															
1a	23729	23998	24494	32326	32692	33368	32299	32664	33340	37019	37438	38213	13069	13217	13490
1b	23729	24005	24494	32326	32702	33368	32299	32674	33340	37019	37450	38213	13069	13221	13490
2c	23242	23584	23983	31663	32129	32672	31636	32102	32644	36260	36794	37416	12801	12989	13209
2d	23242	23584	23983	31663	32129	32672	31636	32102	32644	36260	36794	37416	12801	12989	13209
4c	21672	23426	23785	29524	31913	32403	29499	31886	32375	33810	36546	37108	11936	12902	13100
5b	9848	9869	9901	13416	13444	13488	13405	13433	13477	15364	15396	15447	5424	5435	5453
5c	7530	7551	7583	10258	10286	10330	10250	10277	10321	11748	11780	11830	4147	4159	4176
6b	16377	16539	16803	22311	22531	22891	22292	22512	22872	25550	25802	26215	9020	9109	9255
6d	23242	23584	23983	31663	32129	32672	31636	32102	32644	36260	36794	37416	12801	12989	13209
9a	14438	15316	16885	19670	20865	23002	19653	20847	22982	22525	23894	26342	7952	8435	9299
9b	21339	22868	23854	29071	31154	32497	29046	31127	32469	33291	35677	37215	11753	12595	13138
9c	20193	20443	20680	27509	27850	28173	27485	27826	28149	31502	31893	32263	11121	11259	11390
PA	23439	23784	24086	31931	32402	32812	31903	32374	32784	36566	37106	37576	12909	13099	13265
Ice Harbor Lock and Dam/Lake Sacajawea															
1a	66789	67547	68801	88930	89940	91610	35239	35640	36301	256291	259202	264013	72558	73382	74744
1b	66789	67580	68801	88930	89984	91610	35239	35657	36301	256291	259329	264013	72558	73418	74744
2c	65181	66143	67130	86790	88070	89385	34391	34899	35420	250124	253813	257602	70812	71856	72929
2d	65181	66143	67130	86790	88070	89385	34391	34899	35420	250124	253813	257602	70812	71856	72929
4c	59462	65152	66477	79175	86751	88515	31374	34376	35075	228177	250013	255096	64598	70780	72219
5b	21034	21093	21171	28007	28085	28189	11098	11129	11170	80714	80941	81240	22851	22915	23000
5c	16295	16354	16432	21697	21776	21880	8598	8629	8670	62530	62757	63056	17703	17767	17852
6b	42622	43088	43739	56752	57372	58240	22489	22734	23078	163557	165342	167843	46304	46810	47517
6d	65181	66143	67130	86790	88070	89385	34391	34899	35420	250124	253813	257602	70812	71856	72929
9a	35861	38753	43976	47749	51601	58554	18921	20447	23203	137611	148710	168750	38959	42101	47774
9b	58976	63587	66612	78528	84667	88695	31117	33550	35146	226313	244004	255615	64071	69079	72366
9c	57003	57774	58253	75900	76927	77565	30076	30483	30736	218740	221700	223538	61927	62765	63285
PA	65727	66719	67421	87516	88837	89773	34679	35203	35573	252217	256024	258720	71404	72482	73245

Table 4-35. Little Goose Lock and Dam/Lake Bryan, Estimated Total Annual Recreation Days Under Alternative SOSs

Average Visitation (1987–1993): 243100 Baseline Visitation (11/92–10/93): 241900		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	241693	244797	250820
	% change from 2c	2.22%	1.83%	2.26%
	% change from Preferred Alternative	1.27%	0.88%	1.79%
	% change from 92–93		1.20%	
SOS 1b	Total	241693	244861	250820
	% change from 2c	2.22%	1.85%	2.26%
	% change from Preferred Alternative	1.27%	0.91%	1.79%
	% change from 92–93		1.22%	
SOS 2c	Total	236440	240402	245280
	% change from 1a	–2.17%	–1.80%	–2.21%
	% change from Preferred Alternative	–0.93%	–0.93%	–0.46%
	% change from 92–93		–0.62%	
SOS 2d	Total	236440	240402	245280
	% change from 1a	–2.17%	–1.80%	–2.21%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	–0.93%	–0.93%	–0.46%
SOS 4c	Total	220368	239610	243233
	% change from 1a	–8.82%	–2.12%	–3.02%
	% change from 2c	–6.80%	–0.33%	–0.83%
	% change from Preferred Alternative	–7.67%	–1.25%	–1.29%
SOS 5b	Total	92436	92671	93072
	% change from 1a	–61.75%	–62.14%	–62.89%
	% change from 2c	–60.90%	–61.45%	–62.05%
	% change from Preferred Alternative	–61.27%	–61.81%	–62.23%
SOS 5c	Total	70908	71143	71543
	% change from 1a	–70.66%	–70.94%	–71.48%
	% change from 2c	–70.01%	–70.41%	–70.83%
	% change from Preferred Alternative	–70.29%	–70.68%	–70.97%
SOS 6b	Total	162553	164402	167649
	% change from 1a	–32.74%	–32.84%	–33.16%
	% change from 2c	–31.25%	–31.61%	–31.65%
	% change from Preferred Alternative	–31.89%	–32.25%	–31.97%
SOS 6b	% change from 92–93		–32.04%	

Table 4-35. Little Goose Lock and Dam/Lake Bryan, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 243100 Baseline Visitation (11/92–10/93): 241900		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 6d	Total	236440	240402	245280
	% change from 1a	–2.17%	–1.80%	–2.21%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	–0.93%	–0.93%	–0.46%
	% change from 92–93		–0.62%	
SOS 9a	Total	142677	151909	168534
	% change from 1a	–40.97%	–37.94%	–32.81%
	% change from 2c	–39.66%	–36.81%	–31.29%
	% change from Preferred Alternative	–40.22%	–37.40%	–31.61%
	% change from 92–93		–37.20%	
SOS 9b	Total	216005	233075	243924
	% change from 1a	–10.63%	–4.79%	–2.75%
	% change from 2c	–8.64%	–3.05%	–0.55%
	% change from Preferred Alternative	–9.50%	–3.95%	–1.01%
	% change from 92–93		–3.65%	
SOS 9c	Total	200496	203317	206416
	% change from 1a	–17.05%	–16.94%	–17.70%
	% change from 2c	–15.20%	–15.43%	–15.84%
	% change from Preferred Alternative	–15.99%	–16.21%	–16.23%
	% change from 92–93		–15.95%	
PA	Total	238668	242655	246418
	% change from 1a	–1.25%	–0.87%	–1.75%
	% change from 2c	0.94%	0.94%	0.46%
	% change from 92–93		0.31%	

Table 4-36. Lower Monumental Lock and Dam/Lake West, Estimated Total Annual Recreation Days Under Alternative SOSs

Average Visitation (1987–1993): 139500 Baseline Visitation (11/92–10/93): 138400		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	138442	140009	142904
	% change from 2c	2.09%	1.75%	2.13%
	% change from Preferred Alternative	1.24%	0.90%	1.69%
	% change from 92–93		1.16%	
SOS 1b	Total	138442	140052	142904
	% change from 2c	2.09%	1.78%	2.13%
	% change from Preferred Alternative	1.24%	0.93%	1.69%
	% change from 92–93		1.19%	

Table 4-36. Lower Monumental Lock and Dam/Lake West, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 139500 Baseline Visitation (11/92–10/93): 138400		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 2c	Total	135603	137598	139925
	% change from 1a	–2.05%	–1.72%	–2.08%
	% change from Preferred Alternative	–0.84%	–0.84%	–0.43%
	% change from 92–93		–0.58%	
SOS 2d	Total	135603	137598	139925
	% change from 1a	–2.05%	–1.72%	–2.08%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	–0.84%	–0.84%	–0.43%
SOS 4c	Total	126441	136673	138772
	% change from 1a	–8.67%	–2.38%	–2.89%
	% change from 2c	–6.76%	–0.67%	–0.82%
	% change from Preferred Alternative	–7.54%	–1.51%	–1.25%
SOS 5b	Total	57458	57577	57766
	% change from 1a	–58.50%	–58.88%	–59.58%
	% change from 2c	–57.63%	–58.16%	–58.72%
	% change from Preferred Alternative	–57.98%	–58.51%	–58.89%
SOS 5c	Total	43933	44052	44241
	% change from 1a	–68.27%	–68.54%	–69.04%
	% change from 2c	–67.60%	–67.98%	–68.38%
	% change from Preferred Alternative	–67.87%	–68.25%	–68.52%
SOS 6b	Total	95550	96492	98036
	% change from 1a	–30.98%	–31.08%	–31.40%
	% change from 2c	–29.54%	–29.87%	–29.94%
	% change from Preferred Alternative	–30.13%	–30.46%	–30.24%
SOS 6d	Total	135603	137598	139925
	% change from 1a	–2.05%	–1.72%	–2.08%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	–0.84%	–0.84%	–0.43%
SOS 9a	Total	84238	89356	98510
	% change from 1a	–39.15%	–36.18%	–31.07%
	% change from 2c	–37.88%	–35.06%	–29.60%
	% change from Preferred Alternative	–38.40%	–35.61%	–29.90%
SOS 9a	Total	84238	89356	98510
	% change from 1a	–39.15%	–36.18%	–31.07%
	% change from 2c	–37.88%	–35.06%	–29.60%
	% change from Preferred Alternative	–38.40%	–35.61%	–29.90%

Table 4-36. Lower Monumental Lock and Dam/Lake West, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 139500 Baseline Visitation (11/92–10/93): 138400		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 9b	Total	124500	133421	139172
	% change from 1a	–10.07%	–4.71%	–2.61%
	% change from 2c	–8.19%	–3.04%	–0.54%
	% change from Preferred Alternative	–8.96%	–3.85%	–0.96%
	% change from 92–93		–3.60%	
SOS 9c	Total	117810	119271	120655
	% change from 1a	–14.90%	–14.81%	–15.57%
	% change from 2c	–13.12%	–13.32%	–13.77%
	% change from Preferred Alternative	–13.85%	–14.05%	–14.14%
	% change from 92–93		–13.82%	
PA	Total	136747	138766	140524
	% change from 1a	–1.22%	–0.89%	–1.67%
	% change from 2c	0.84%	0.85%	0.43%
	% change from 92–93		0.26%	

Table 4-37. Ice Harbor Lock and Dam/Lake Sacajawea, Estimated Total Annual Recreation Days Under Alternative SOSs

Average Visitation (1987–1993): 482200 Baseline Visitation (11/92–10/93): 518300		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	519755	525658	535416
	% change from 2c	2.47%	2.12%	2.49%
	% change from Preferred Alternative	1.62%	1.24%	2.05%
	% change from 92–93		1.42%	
SOS 1b	Total	519755	525916	535416
	% change from 1a	0.00%	0.05%	0.00%
	% change from 2c	2.47%	2.17%	2.49%
	% change from Preferred Alternative	1.62%	1.29%	2.05%
	% change from 92–93		1.47%	
SOS 2c	Total	507249	514730	522412
	% change from 1a	–2.41%	–2.08%	–2.43%
	% change from Preferred Alternative	–0.83%	–0.86%	–0.43%
	% change from 92–93		–0.69%	
SOS 2d	Total	507249	514730	522412
	% change from 1a	–2.41%	–2.08%	–2.43%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	–0.83%	–0.86%	–0.43%
	% change from 92–93		–0.69%	

Table 4-37. Ice Harbor Lock and Dam/Lake Sacajawea, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 482200 Baseline Visitation (11/92–10/93): 518300		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 4c	Total	462740	507022	517331
	% change from 1a	–10.97%	–3.55%	–3.38%
	% change from 2c	–8.77%	–1.50%	–0.97%
	% change from Preferred Alternative	–9.53%	–2.35%	–1.40%
	% change from 92–93		–2.18%	
SOS 5b	Total	163687	164147	164753
	% change from 1a	–68.51%	–68.77%	–69.23%
	% change from 2c	–67.73%	–68.11%	–68.46%
	% change from Preferred Alternative	–68.00%	–68.39%	–68.60%
	% change from 92–93		–68.33%	
SOS 5c	Total	126811	127270	127877
	% change from 1a	–75.60%	–75.79%	–76.12%
	% change from 2c	–75.00%	–75.27%	–75.52%
	% change from Preferred Alternative	–75.21%	–75.49%	–75.63%
	% change from 92–93		–75.44%	
SOS 6b	Total	331691	335312	340383
	% change from 1a	–36.18%	–36.21%	–36.43%
	% change from 2c	–34.61%	–34.86%	–34.84%
	% change from Preferred Alternative	–35.15%	–35.42%	–35.13%
	% change from 92–93		–35.31%	
SOS 6d	Total	507249	514730	522412
	% change from 1a	–2.41%	–2.08%	–2.43%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	–0.83%	–0.86%	–0.43%
	% change from 92–93		–0.69%	
SOS 9a	Total	279073	301583	342223
	% change from 1a	–46.31%	–42.63%	–36.08%
	% change from 2c	–44.98%	–41.41%	–34.49%
	% change from Preferred Alternative	–45.44%	–41.92%	–34.77%
	% change from 92–93		–41.81%	
SOS 9b	Total	458960	494838	518384
	% change from 1a	–11.70%	–5.86%	–3.18%
	% change from 2c	–9.52%	–3.86%	–0.77%
	% change from Preferred Alternative	–10.27%	–4.69%	–1.20%
	% change from 92–93		–4.53%	
SOS 9c	Total	443601	449605	453333
	% change from 1a	–14.65%	–14.47%	–15.33%
	% change from 2c	–12.55%	–12.65%	–13.22%
	% change from Preferred Alternative	–13.27%	–13.41%	–13.60%
	% change from 92–93		–13.25%	
PA	Total	511493	519212	524681
	% change from 1a	–1.59%	–1.23%	–2.01%
	% change from 2c	0.84%	0.87%	0.43%
	% change from 92–93		0.18%

Figure 4-10. Little Goose Project, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Figure 4-11. Lower Monumental Project, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Figure 4-12. Ice Harbor Project, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

4.2.15.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

SOS 1a, 1b, 2c, 2d, 4c, 6d, 9b and the PA all would be expected to maintain the existing riparian habitat along the shorelines of the lakes with no change in opportunities for viewing the resident wildlife species. Hunting for waterfowl, upland game and big game are not major activities along lakes West, Bryan and Sacajawea and no significant changes would be expected.

Alternatives 5b and 5c would exert the greatest impact on wildlife resources of the three lakes, eliminating or at least significantly reducing utiliza-

tion of the reservoirs and adjacent habitat for nearly all species with any aquatic or riparian habitat dependency, including a local reproducing population of mallard, great blue heron, spotted sandpiper, beaver, river otter, and Canada goose. Substantial loss of wildlife viewing opportunity would be expected. Impacts of SOS 6b, 9a and 9c would be similar, but less severe at all three lakes.

4.2.15.6 Effects on Recreational Safety and Physical Characteristics

Under SOS 1a, 1b, 2c, 2d, 4c, 6d, 9b and the preferred alternative, there would be little change from current lake elevations. No significant effects on

recreation safety and physical characteristics are expected.

During periods of severe drawdown under SOS 5b, 6b, 9a and 9c the lakes would provide a completely different recreation experience than currently exists. The lakes would be drawn down further into their natural canyon. Some shoals, mudflats and sediment deposits within the former pools will be exposed. The disturbance of former in-water sediment deposits from past operations will create new and shifting shoaling as the deposits adjust to the changed operation.

Alternative 5c will provide, at the three lakes, a stable lake elevation 90 to 120 feet lower than the current full lake elevation. Until the existing sediments stabilize and visitors become adjusted to the changed operation, this alternative will present significant recreational safety hazards.

4.2.15.7 Effects on Water Quality Parameters Influencing Recreation

SOS 1a and 1b would create a positive impact on water quality due to a decrease in sedimentation and turbidity as a result of the stable lake elevations of these two alternatives. SOS 2c, 2d, 4c, 9b and the PA are likely to create some increases, though minor, in both sedimentation and turbidity.

SOS 5b, 5c, 6b, 9a, and the PA may create negative impacts on water quality due to an increase in sedimentation and turbidity as a result of the lower lake elevations exposure of former in-water sediment deposits.

4.2.15.8 Effects on Aesthetics

Under SOS 1a, 1b, 2c, 2d, 4c, 6d, 9b and the preferred alternative, there will be no significant effect on visual quality or other aesthetic parameters at lakes West, Bryan or Sacajawea.

SOS 5b, 5c, 6b, 9a and 9c would result in significant negative impacts to the existing aesthetics of both lakes during periods of drawdown. Under all of these alternatives, large drawdown zones within the former Snake River Canyon would be exposed for varying periods of time. In its natural state, the

canyon and unimpounded river were quite scenic. However, the inundation by the lakes has left sediment deposits and eliminated vegetation. Under these alternatives, mudflats and steep canyon walls will be exposed for varying periods of time. Seasonal fluctuation of the lake elevations under most of these alternative, back to full pool would prevent the aesthetics from being softened through revegetation over time.

SOS 5c would result in a permanent year-round drawdown of the three lakes of over 100 feet below full pool. The short term impacts on aesthetic quality would be similar to those described above for the other drawdown alternatives. The long-term aesthetic impacts of SOS 5c are harder to determine. It is expected that the Snake River Canyon would eventually be restored to historic natural scenic qualities as sediment is washed back into the river and natural vegetation is restored. It is unknown how long it will take this process to occur.

4.2.15.9 Mitigation Opportunities

Under SOS 1a, 1b, 2c, 2d, 4c, 6d, 9b, as well as the PA, little in the way of mitigation will be necessary. Some swim beaches and launch ramps may need to be extended or dredged to provide a full range of availability to visitors down to minimum operating pool. A higher priority should be placed on modifying the facilities at Little Goose Lake, where slightly lower pool elevations during the summer would have moderate effects on the usability of recreation facilities.

Extensive mitigation would be necessary under SOS 5b, 5c, 6b, 9a and 9c. Swim beaches and launch ramps will need to be extended to provide a full range of availability to visitors. For more severe drawdown ranges, the degree of difficulty and costs for structural modification of facilities increases dramatically. In a study undertaken as part of the 1992 Options EIS, the Corps Walla Walla District estimated that the cost of modifying recreation facilities on the Lower Granite and Ice Harbor pools under the drawdown alternative considered was in the neighborhood of \$15 million (Lake Bryan and Lake West were not included in that study).

The severity of impacts to recreation facilities and activities at the three lakes may be so severe that it is infeasible to modify recreational facilities onsite to mitigate for impacts. It may be physically impossible to modify facilities to accommodate the range of fluctuations considered. However, a point can also be reached where drawdown diminishes aesthetics and other parameters of recreational suitability to a point where modification of facilities at that project is not a reasonable mitigation option. When drawdowns result in impacts that are severe, the only feasible mitigation options may include relocation or replacement of facilities in-kind elsewhere in the region.

4.2.16 McNARY LOCK AND DAM/LAKE WALLULA

Under all 12 SOS alternatives, as well as the preferred alternative, operation of McNary Lock and Dam will be essentially the same. Lake Wallula will average within one foot of a full lake all months of the year, including the peak recreation season. Normal daily and weekly lake fluctuations will occur within the upper three feet of Lake Wallula with occasional maintenance drawdowns of five feet below full. Because this operation does not differ from historic operation of Lake Wallula, no impacts to recreation facilities, features or activities will occur. For this reason no analysis of SOR effects has been included for McNary Lock and Dam, Lake Wallula.

4.2.17 JOHN DAY PROJECT/LAKE UMATILLA

4.2.17.1 Description/Hydrologic Characteristics

Seasonal pool elevations. Variation between SOSs at John Day is reflected in the timing of drawdown and refill for flood control storage. Table 4–38 shows the average monthly pool elevations (as measured at the forebay of John Day Dam) under the 13 alternative SOSs.

Under **SOS 1a and 1b**, John Day Project would be operated seasonally in accordance with the flood control rule curve. The pool is raised from July through October to benefit other purposes, including recreation; the average pool elevation of from 265 to 266.5 ft. is considered to be about the optimum for recreation. The pool is maintained at a lower elevation from November through June to provide downstream flood control. It is regularly fluctuated

up to near elevation 265 on a cyclic basis during early spring months to discourage goose nesting at lower operating levels. From 1 March through 15 May the normal pool is held at 262.0 ft. to protect nesting waterfowl.

Under **SOS 4c**, the operations would be slightly different, featuring pool elevations approximately 1.5 feet lower during summer than SOS 1a and 1b. From November through June the lake would have an average elevation of 263.5 ft. From July through October it would be raised to 265.0 ft.

Under **SOS 2c, 2d, and 9b** Lake Umatilla would be brought down to the minimum irrigation pool elevation 262.5 at the end of April and held steady through August with no daily peaking fluctuations during that period. Operation would be similar to SOS 1a and 1b over the remainder of the year.

Table 4–38. John Day Lock and Dam/Lake Umatilla, Average Monthly Pool Elevations (ft. NGVD) for Alternative SOSs

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	263.5	263.5	263.5	263.5	263.5	263.5	266.5	266.5	266.5	266.5	263.5	263.5
1b	263.5	263.5	263.5	263.5	263.5	263.5	266.5	266.5	266.5	266.5	263.5	263.5
2c	263.5	263.5	263.5	262.5	262.5	262.5	262.5	262.5	266.5	266.5	263.5	263.5
2d	263.5	263.5	263.5	262.5	262.5	262.5	262.5	262.5	266.5	266.5	263.5	263.5
4c	263.5	263.5	263.5	263.5	263.5	263.5	265	265	265	265	263.5	263.5
5b	263.5	263.5	263.5	262.5	257	257	257	257	266.5	265.5	263.5	263.5
5c	263.5	263.5	263.5	262.5	257	257	257	257	266.5	265.5	263.5	263.5
6b	263.5	263.5	263.5	262.5	257	257	257	257	266.5	265.5	263.5	263.5
6d	263.5	263.5	263.5	262.5	257	257	257	257	266.5	265.5	263.5	263.5
9a	263.5	263.5	263.5	257.5	257.5	257.5	257.5	257.5	266.5	265	263.5	263.5
9b	263.5	263.5	263.5	262.5	262.5	262.5	262.5	262.5	266.5	265	263.5	263.5
9c	263.5	263.5	263.5	257	257	257	257	257	266.5	265	263.5	263.5
PA	257	257	257	257	257	257	257	257	257	257	257	257

= Minimum Operating Pool with significant recreational impacts

SOS 5b, 5c, 6b, 6d, 9a, and 9c would significantly affect recreation at John Day Project due to Lake Umatilla being drawn down to the Minimum Operating Pool (MOP) of elevation 257 ft. beginning in May and held steady through August with no daily peaking fluctuations during that period. Operation is similar to SOS 1 over the remainder of the year.

The **Preferred Alternative (PA)** SOS would have the most drastic effects on recreation at Lake Umatilla as the lake would be drawn down to MOP and held there constantly, year round except during periodic flood control operations when the lake may fill to higher elevations for short durations.

River flows. In addition to pool elevations, the level of flows running through the John Day Project also affect recreational suitability. Although it varies depending upon a number of factors, including pool elevations and the recreational activities being participated in, the estimated optimum range of flows for recreation on Lake Umatilla are from 150 to 250 kcfs (4248 to 7080 cms). Effects of high and low flows above and below this range are described in succeeding sections.

Average monthly flows at John Day Project are strongly influenced by the natural hydrograph of the Columbia River basin. Table 4-39 displays average monthly flows released through John Day Dam under the 13 alternative SOSs. As shown, under all of the SOSs, actual flows vary considerably with the natural hydrograph through the summer recreation season, generally peaking in May or June, and declining through the summer to a low in August or September. The major effect of the alternative SOSs would be to shift the peak and low flow periods around during the summer recreation season. Table 4-40 compares the average flows during June, July and August and displays the percentage of years that flows would be greater than, less than, or within the preferred range for recreation in those months.

Under **SOS 1a and 1b**, flows would peak during May with averages of about 270 kcfs (7700 cms) and then drop slightly in June to about 250 kcfs (7080 cms). By July, they fall significantly to 170 kcfs (4800 cms) when they are within the preferred recreation range 44 percent of years in SOS 1a as compared to only 34

percent for SOS 1b. Under both SOSs, minimum annual flows are reached during August, September and October when they remain pretty stable at an average of around 110 kcfs (3100 cms). During August, flows are lower than the preferred minimum for recreation during 96 percent of years.

Under **SOS 2c** flows are similar to those under SOS 1b and 1a, peaking during May. They remain greater than the maximum preferred flow for recreation in June during 46 percent of years. The only significant difference between these three alternatives is that flows are slightly higher in June under SOS2c. August flows average 116 kcfs (3300 cms) and are below the preferred minimum for recreation during 94 percent of years.

SOS 2d and 4c are similar, with peak flows shifted from May to June. Flows during the months of June and July would average approximately 25 to 30 cfs (700 to 850 cms) higher than under SOS 1a, 1b, or 2c. June flows would be higher than the preferred maximum during 52 and 60 percent of years for 2d and 4c, respectively, but would fall within the preferred range in July during 56 and 61 percent of years. In August, flows would be lower than the preferred minimum for recreation during 94 and 96 percent of years. The only significant difference between SOS 2d and 4c occurs in September when average flows are 88 and 104 kcfs, respectively. However, September flows for both fall well below the minimum for recreation nearly 100 percent of years.

Flows under **SOS 5b, 5c, 6b and 6d** would be similar to those under SOS 2c. The biggest difference between these alternatives and the other SOSs is that they substantially shift higher peaks to earlier in spring. Flows peak at an average of 281 kcfs (7958 cms) during May and are greater than the maximum preferred flow for recreation about 54 percent of years. Flows drop off slightly by June. In July, a significant drop would result in flows within the preferred recreation range during only 38 percent of years, compared to the 46 percent of years that they would be below the preferred minimum of 150 kcfs. By August, flows under SOS 5b and 6b fall to an average of 85 kcfs (2400 cms), well below the preferred minimum. Under SOS 5c and 6d, conditions in August are somewhat better for recreation, averaging 112 and 101 kcfs (3172 and 2860 cms), respectively.

Table 4–39. John Day Lock & Dam/Lake Umatilla — Average Monthly Outflows (KCFS) for Alternative SOSs

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	210	194	185	219	277	248	169	115	108	112	124	148
1b	210	196	176	213	267	254	174	115	111	116	127	150
2c	205	193	172	219	279	267	171	116	105	112	122	147
2d	166	188	195	216	264	282	195	114	104	112	120	145
4c	201	189	166	222	276	286	185	108	88	109	117	156
5b	206	202	188	218	281	266	168	112	84	113	121	149
5c	208	194	171	218	281	265	168	112	105	114	124	150
6b	206	194	182	218	281	266	168	112	85	114	124	150
6d	206	194	171	218	281	266	168	112	101	115	124	151
9a	161	177	182	282	298	297	216	157	70	81	91	128
9b	151	172	205	289	277	296	199	134	78	84	97	147
9c	165	187	212	237	262	267	200	125	76	95	115	121
PA	164	176	190	252	272	289	204	127	89	97	107	141

Table 4–40. John Day Lock & Dam/Lake Umatilla, Summer Average Monthly Flows (KCFS) and Percent of Years Within Optimum Recreation Range

SOS	June			July			August	
	Average Flows (kcfs)	% Years Flows in Optimum Range	Average Flows (kcfs)	Percent of Years Flows			Average Flows (kcfs)	% Years Flows in Optimum Range
				>250 kcfs	Optimum Range	<150 kcfs		
1a	248	54	169	16	44	40	115	4
1b	254	48	174	14	34	52	115	4
2c	267	54	171	12	32	46	116	6
2d	282	52	195	20	56	24	114	6
4c	286	40	185	22	44	34	108	4
5b	266	52	168	16	38	46	112	2
5c	265	52	168	16	38	46	112	2
6b	266	52	168	16	38	46	112	2
6d	266	52	168	16	38	46	86	2
9a	297	36	216	24	70	6	157	80
9b	296	34	199	20	64	16	134	50
9c	267	52	200	24	54	22	125	24
PA	289	40	204	18	68	14	127	26

The predominant feature of **SOS 9a** would be much higher flows during May through August than any of the other alternatives. June flows would be above the preferred maximum for recreation during about 72 percent of years. This effect would be balanced, however, by more consistent flows during the remainder of the summer recreation season. For example, during July, the average drops to 233 kcfs (6600 cms) and would be within the preferred range during 76 percent of years. During August, flows remain above the preferred minimum during 100 percent of years. By September, however, average monthly flows drop well below that month under **SOS 1a** or **2c**.

SOS 9b would also feature higher flows during the summer recreation season than either **SOS 1a** or **2c**. They would start out slightly higher than under **SOS 9a** in April, remaining relatively constant through June. By July and August, flows drop considerably lower than under **SOS 9a**. However, in comparison with the other **SOSs**, July and August flows would still be relatively good for recreation, remaining within the preferred range 64 and 50 percent of years during those months, respectively. September flows would also be well below those of **SOS 1a** or **2c**.

SOS 9c would begin the summer recreation season with slightly lower flows in May than any of the other **SOSs**. Peak flows would be shifted to June and would remain relatively high in July. Flows would be reduced during the remainder of the summer.

The **PA** would feature higher flows during the summer recreation season than either **SOS 1a** or **2c**. They peak in June when they would be higher than the preferred maximum during 60 percent of years. Flows would remain relatively high in July and August. In comparison with the other **SOSs**, July and August flows would be relatively good for recreation, remaining within the preferred range 66 and 68 percent of years during those months, respectively.

Short-term operations. For short term operations, John Day project generation reaches a maximum about 8:00 AM and then fluctuates at the upper limits throughout the day to follow the load demand. Load starts decreasing in the late evening, reaching minimum flows about midnight. With this type of

operation, the forebay and tailwater of John Day Dam fluctuate less than 2 feet (0.61 m) per day throughout the year. Operating limits for John Day Dam under all **SOSs** include a maximum change per hour of 3 feet (0.91 m) or 200,000 cfs (5664 cms).

Daily pool fluctuations over the lower 60 miles (96.54 km) of pool are normally less than 1/2 to 1 foot (0.15 to 0.30 m) daily during all seasons of the year with some days experiencing fluctuations in the 2 to 3 feet (0.61 to 0.91 m) range. The upper 10 miles (16.1 km) of the pool are strongly influenced by McNary Project releases and experience fluctuations of 3 to 5 feet (0.91 to 1.5 m) immediately below the dam, diminishing to less than one foot (0.3 m) 10 miles (16.1 km) downstream.

4.2.17.2 Summary of Quantitative Impacts

The results of the recreation impact assessment model for John Day Project are summarized on Table 4-41 and Figure 4-13. They show the estimated participation (in Recreation Days) for major recreational activities including boating, fishing, camping, picnicking and swimming. Table 4-42 displays the estimated total annual recreation participation for each **SOS** and presents estimated percent changes in visitation in comparison **SOS 1a** (Base Case) and **2C** (No Action Alternative). Results are shown for the 50-year average, as well as for an extreme low-water year (1941) and extreme high water year (1976). However, unlike many of the other reservoirs in the system, at Lake Umatilla there would be no variation in operations (pool elevations) between low, average and high water years under any of the **SOSs**. Therefore, the model results do not vary across different water years.

One important goal of the recreation survey used to develop the SOR recreation impact assessment models (Appendix J-1 provides a detailed description of the survey and model estimation techniques) was to determine the extent to which water level changes at one project or river reach in the system would affect recreation visitation at other projects or river reaches. In other words, to what extent would changes in operations at one project cause people to use substitute or alternative recreation sites. John Day Project was one of two out of the nine sites in

the survey that had no cross water effects. That is, based on the survey results, there is no statistically valid correlation between changes in system operations and people using substitutes for Lake Umatilla for more or fewer recreation trips.

Based in the model results, the alternative SOS under consideration can be separated into five

groups in which the degree of recreational impacts will be similar. These groups are:

minimal impact	SOS 1a and 1b
slight impact	SOS 4c
moderate impact	SOS 2c, 2d, and 9b
severe impact	SOS 5b, 5c, 6b, 6d, 9a, and 9c
highest impact	Preferred Alternative

Table 4-41. John Day Lock and Dam/Lake Umatilla, Estimated Annual Recreation Days by Activity Under Alternative SOSs

SOS	Boating			Fishing			Camping			Picnicking			Swimming		
	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976	Low Water 1941	50 Year Avg.	High Water 1976
1a	756472	756472	756472	649222	649222	649222	573432	573432	573432	570858	570858	570858	310025	310025	310025
1b	756472	756472	756472	649222	649222	649222	573432	573432	573432	570858	570858	570858	310025	310025	310025
2c	675900	675900	675900	580073	580073	580073	512355	512355	512355	510056	510056	510056	277004	277004	277004
2d	675900	675900	675900	580073	580073	580073	512355	512355	512355	510056	510056	510056	277004	277004	277004
4c	730030	730030	730030	626529	626529	626529	553388	553388	553388	550904	550904	550904	299188	299188	299188
5b	560993	560993	560993	481458	481458	481458	425252	425252	425252	423343	423343	423343	229912	229912	229912
5c	560993	560993	560993	481458	481458	481458	425252	425252	425252	423343	423343	423343	229912	229912	229912
6b	560993	560993	560993	481458	481458	481458	425252	425252	425252	423343	423343	423343	229912	229912	229912
6d	560993	560993	560993	481458	481458	481458	425252	425252	425252	423343	423343	423343	229912	229912	229912
9a	556468	556468	556468	477574	477574	477574	421822	421822	421822	419928	419928	419928	228057	228057	228057
9b	675900	675900	675900	580073	580073	580073	512355	512355	512355	510056	510056	510056	277004	277004	277004
9c	547061	547061	547061	469500	469500	469500	414691	414691	414691	412829	412829	412829	224202	224202	224202
PA	397300	397300	397300	340972	340972	340972	301167	301167	301167	299815	299815	299815	162826	162826	162826

Figure 4-13. John Day Project, Estimated Visitation for Alternative SOSs (Low, Average & High Water Years)

Table 4-42. John Day Lock and Dam/Lake Umatilla, Estimated Total Annual Recreation Days Under Alternative SOSs

Average Visitation (1987-1993): 2420700 Baseline Visitation (11/92-10/93): 2682200		Low Water Year (1941)	50 - Year Average	High Water Year (1976)
System Operating Strategies				
SOS 1a	Total	2860009	2860009	2860009
	% change from 2c	11.92%	11.92%	11.92%
	% change from Preferred Alternative	90.40%	90.40%	90.40%
	% change from 92-93		6.63%	
SOS 1b	Total	2860009	2860009	2860009
	% change from 2c	11.92%	11.92%	11.92%
	% change from Preferred Alternative	90.40%	90.40%	90.40%
	% change from 92-93		6.63%	
SOS 2c	Total	2555389	2555389	2555389
	% change from 1a	-10.65%	-10.65%	-10.65%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	70.12%	70.12%	70.12%
	% change from 92-93		-4.73%	
SOS 2d	Total	2555389	2555389	2555389
	% change from 1a	-10.65%	-10.65%	-10.65%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	70.12%	70.12%	70.12%
	% change from 92-93		-4.73%	
SOS 4c	Total	2760038	2760038	2760038
	% change from 1a	-3.50%	-3.50%	-3.50%
	% change from 2c	8.01%	8.01%	8.01%
	% change from Preferred Alternative	83.75%	83.75%	83.75%
	% change from 92-93		2.90%	
SOS 5b	Total	2120958	2120958	2120958
	% change from 1a	-25.84%	-25.84%	-25.84%
	% change from 2c	-17.00%	-17.00%	-17.00%
	% change from Preferred Alternative	41.20%	41.20%	41.20%
	% change from 92-93		-20.92%	
SOS 5c	Total	2120958	2120958	2120958
	% change from 1a	-25.84%	-25.84%	-25.84%
	% change from 2c	-17.00%	-17.00%	-17.00%
	% change from Preferred Alternative	41.20%	41.20%	41.20%
	% change from 92-93		-20.92%	
SOS 6b	Total	2120958	2120958	2120958
	% change from 1a	-25.84%	-25.84%	-25.84%
	% change from 2c	-17.00%	-17.00%	-17.00%
	% change from Preferred Alternative	41.20%	41.20%	41.20%
	% change from 92-93		-20.92%	

Table 4-42. John Day Lock and Dam/Lake Umatilla, Estimated Total Annual Recreation Days Under Alternative SOSs – CONT

Average Visitation (1987–1993): 2420700 Baseline Visitation (11/92–10/93): 2682200		Low Water Year (1941)	50 – Year Average	High Water Year (1976)
System Operating Strategies				
SOS 6d	Total	2120958	2120958	2120958
	% change from 1a	–25.84%	–25.84%	–25.84%
	% change from 2c	–17.00%	–17.00%	–17.00%
	% change from Preferred Alternative	41.20%	41.20%	41.20%
	% change from 92–93		–20.92%	
SOS 9a	Total	2103849	2103849	2103849
	% change from 1a	–26.44%	–26.44%	–26.44%
	% change from 2c	–17.67%	–17.67%	–17.67%
	% change from Preferred Alternative	40.06%	40.06%	40.06%
	% change from 92–93		–21.56%	
SOS 9b	Total	2555389	2555389	2555389
	% change from 1a	–10.65%	–10.65%	–10.65%
	% change from 2c	0.00%	0.00%	0.00%
	% change from Preferred Alternative	70.12%	70.12%	70.12%
	% change from 92–93		–4.73%	
SOS 9c	Total	2068283	2068283	2068283
	% change from 1a	–27.68%	–27.68%	–27.68%
	% change from 2c	–19.06%	–19.06%	–19.06%
	% change from Preferred Alternative	37.69%	37.69%	37.69%
	% change from 92–93		–22.89%	
PA	Total	1502081	1502081	1502081
	% change from 1a	–47.48%	–47.48%	–47.48%
	% change from 2c	–41.22%	–41.22%	–41.22%
	% change from 92–93		–44.00%	

SOS 1a and 1b would be the best alternatives for recreation at Lake Umatilla. SOS 1a is the Base Case, reflecting operation of the project prior to initiation of salmon recovery operations in 1992. Under both strategies Lake Umatilla would be held within three feet of the maximum operating pool during the entire year. Estimated average annual visitation would be approximately 2,834,500 recreation days.

Under **SOS 4c**, estimated visitation is slightly lower than **SOS 1a**, at approximately 2,753,000 recreation days, a difference of 2.88 percent. This slight difference results from Lake Umatilla being held a foot and a half lower during July and August than under

SOS 1a. Visitation is estimated at approximately 8 percent higher than under **SOS 2C**.

Under **SOS 2c**, the **No Action** alternative, as well as **SOS 2d** and **SOS 9b**, the level of Lake Umatilla is lowered by four feet to elevation 262.5 through the summer recreation season (May through August). Consequently, the model estimates annual visitation at approximately 2,549,000 recreation days for all three of these alternatives, a reduction of about 10 percent in use from **SOS 1a**, the Base Case alternative.

SOS 5b, 5c, 6b, 6d, 9a, and 9c would all result in a severe impact on recreational use at Lake Umatilla. Under each of these alternatives, Lake Umatilla would be drawn down to or near MOP through the

peak summer recreation season, May through August. For SOS 5b, 5c, 6b, and 6d, estimated annual visitation is approximately 2,064,000 recreation days, a decline of about 27 percent from SOS 1A and 19 percent from SOS 2C. Under SOS 9a, the lake would be drawn down for five months (April through August), but would be held one-half foot higher than MOP. Consequently, estimated visitation would be approximately 2,043,000 recreation days, a decline of about 28 and 20 percent from SOS 1a and 2c, respectively. Under SOS 9c, impacts would be slightly more severe since the lake would be drawn to MOP for five months. Estimated average annual visitation under SOS 9c is approximately 2,005,000 recreation days, or about 29 and 21 percent lower than SOS 1a and 2c, respectively.

The **Preferred Alternative** would have the highest degree of impact to recreation at Lake Umatilla due to yearround drawdown to MOP. Estimated average annual visitation under is approximately 1,974,000 recreation days, or about 30 and 23 percent lower than SOS 1a and 2c, respectively.

4.2.17.3 Effects on Recreation Facilities/Activities

Section 2.7.7 describes the existing recreational condition at the John Day Project. There are 17 existing recreation sites or areas on Lake Umatilla. The optimum recreation pool at Lake Umatilla is approximately 266.5 ft. Most of the recreation facilities on the lake are designed to remain usable over the normal operational range of the reservoir of from 268 to 262.5 ft. As long as the normal fluctuation of the pool stays within that range, impacts to recreation facilities are small.

Under **SOS 1a, 1b and 4c** the average summer pool elevation of 266.5 feet would be about optimum for recreation at Lake Umatilla. Consequently, no significant impacts on recreational facilities or activities would be expected. The 1.5 foot (0.46 m) drop from full pool (elev. 268 ft.) exposes beach areas for dispersed recreational use and promotes access. Maintaining the lake at or near this elevation for the entire summer season enhances the lake's recreation suitability.

Under **SOS 2c, 2d, and 9b** the major operational change influencing recreation at Lake Umatilla is lowering the lake down to a stable pool elevation of 262.5 for the duration of the peak summer recreation season, May through August. While this elevation is near the lower end of the normal operational range for the project, it is still approximately two feet (0.61 m) above the elevation at which most of the recreation facilities on the lake begin to be significantly impacted. Most of the recreation facilities on the lake are designed to remain partially usable over the normal operational range of the reservoir of from 268 to 260 ft. so the recreational impacts of this alternative are slight.

Boat ramps at all of the major marinas and parks on Lake Umatilla would remain usable at elevation 262.5 ft., including Plymouth Park, Umatilla Marina, Irrigon Park, Boardman Park, Arlington Park and LePage Park. Sites where boat ramps have been significantly damaged by wave cut erosion at the low pool level under existing operations (260 ft.), including Quesnel and Roosevelt Parks, would be usable at the intermediate pool.

Most swimming areas on Lake Umatilla would be reduced in size but would remain usable. Impacts to other facilities (picnic sites and campgrounds) would be insignificant.

Under **SOS 5b, 5c, 6b, 6d, 9a, 9c and the Preferred Alternative**, the average pool elevation through the summer (year round for the PA) would be at or near MOP. MOP is well below the optimum pool elevation for recreation. Consequently, all of these SOS's would have significant impacts on the usability of recreational facilities at Lake Umatilla during the entire peak recreation season. The impacts to individual recreation sites at Lake Umatilla at the Minimum Operating Pool of 257.0 ft. are described in detail in the Corps' report Columbia River Salmon Mitigation Analysis System Configuration Study: Phase I Interim Status Report, Technical appendix B, John Day Reservoir Minimum Operating Pool (November 1992). These impacts are summarized below for most of the existing developed recreation sites on the lake.

Railroad Island Park, Washington: The boat ramp and courtesy dock would have only approximately 1 ft. (0.3 m) of floating clearance, restricting use to small boats. The park is located on a small embayment, the access culvert to the river would be accessible to only shallow draft boats with drafts of 3 ft. (0.9 m) or less.

Phillipi Park, Oregon: The reduction in the pool level would reduce access to this boat—in site by reducing the size of the John Day River channel. Dock space available for moorage would be reduced: the northern boat dock would have approximately 3 ft. (0.9 m) of floating clearance) and the southern dock would be partly grounded at the shallow end, with 2 to 4 ft. (0.6 to 1.2 m) at the deep end. Grounding could damage the dock. The size of the swimming area would be significantly reduced.

LePage Park, Oregon: The swimming area located in a shallow embayment would be nearly entirely dewatered. There are no other safe swimming beaches at this park since the river channel drops away quite steeply. The boat ramp would remain usable but the northern courtesy dock would be grounded. The large mooring docks at would remain accessible to large boats, but the access ramps from the shoreline would be very steep.

Rock Creek Park, Washington: The swimming area would be only one foot deep at the warning floats. Since it drops off quite steeply toward the stream channel, it would probably not be possible to extend the beach area. The toe of the boat ramp would be above water.

Blalock Canyon Boat Ramp, Oregon: This site is located in a small embayment with access via a culvert under the railroad. At MOP, the culvert would be accessible only to small boats with a draft of three feet (0.9 m) or less. The only amenity at this site is an unpaved boat ramp; the toe of the ramp would be three feet above water.

Sundale Park, Washington: The swimming area inside the swim beach floats would be substantially reduced and would have a maximum depth of 2 ft. (0.6 m). The toe of the boat ramp would be above

water level and the boat dock would be grounded, possibly damaging the dock units.

Roosevelt Park, Washington: The swimming beach would be dewatered. The boat ramp and docks would remain usable to boats with a draft of less than three feet.

Arlington Park, Washington: The toe of the boat ramp would be approximately 1.5 ft. (0.46 m) above water and the shallow end of the dock would be grounded. The swimming area would be reduced by about one-half of its size. The floating bandstand used by the city for a summer concert series would be grounded and could possibly be unusable depending on the angle of the bottom slope.

Quesnel (Threemile Canyon) Park: The only amenity at this site is a boat ramp. At MOP the toe of the ramp would be 2 ft. (0.6 m) above water. The east channel entrance to the embayment would be dry.

Crow Butte State Park, Washington: The boat ramp toe would be approximately 4 ft. (1.2 m) above water and the bottom of the boat basin near the tie-up docks would dewatered at 2.5 ft. (0.76 m) above the river elevation. The swimming beach area would be substantially reduced in size, with depths ranging from 0 to 4 ft. (0 to 1.2 m). The irrigation pump intake would be above water and therefore useless.

Plymouth Park, Washington: The boat ramp to would be approximately one ft. (0.3 m) above water. Depths along the boat ramp and tie-up docks would be reduced to from 2 to 4 ft. (0.6 to 1.2 m).

Nugent Park, Oregon: This site is located on the Umatilla River arm of Lake Umatilla. At MOP, the boat ramp toe would be approximately 3 ft. (0.9 m) above water level. The Umatilla River channel would be reduced to a very small size, not passable to anything other than hand-carry craft.

Boardman Park, Oregon: The swimming area would be reduced but could be extended by moving floats outwards. The boat ramp toe would be approximately 2 ft. (0.6 m) above water. The shallow ends of the courtesy tie-up docks at the boat ramp, as well as the year round moorage docks would be grounded. Maximum depths at the end of the moorage docks would be approximately 5 to 6 ft. (1.5

to 1.8 m) which is not deep enough for some of the larger craft (such as fixed-keel sailboats) moored there. The tie-up docks and moorage docks would require longer access gangways.

Irrigon Park, Oregon: At MOP, the swimming area would be dewatered. The toe of the boat basin would be approximately three feet above water level. Since the bottom of the entrance channel is at elevation 255.6 ft., the boat basin would be inaccessible to all but very shallow draft boats. The depth of the boat basin along the courtesy docks and year-round moorages would be a maximum of approximately 5 ft. (1.5 m), which is not deep enough for most of the larger craft using this site.

Umatilla Park, Oregon: The water depth at the toe of the boat ramp would be approximately one foot. Water depths along the eastern moorage dock of the marina would be reduced to approximately three feet, restricting use by larger boats. The swimming area would be reduced in size.

4.2.17.4 Effects on Fish Habitat and Fishing Success

Preliminary results from the SOR Anadromous Fish Work Group indicate that none of the alternative SOS's under consideration would result in significant benefits or impacts to anadromous fish species (see SOR Technical Appendix C). Consequently, none of the alternatives would be expected to have any significant effect on fishing or fishing success for anadromous fish in Lake Umatilla, including salmon, steelhead and sturgeon.

The SOR Resident Fish Work Group modelled potential impacts to two key resident sport fish species at Lake Umatilla, walleye and smallmouth bass (see SOR Technical Appendix K). For bass, SOS 1a, 1b, 2c, 2d, 4c, and 9b would not have any significant impacts. In comparison, under SOS 5b, 5c, 9a and 9c, drawdown of John Day Pool to MOP will reduce the amount of shallow water habitat by approximately 6000 acres for four to five months of the year. The greater range of pool elevations and the lower average pool elevation would negatively affect spawning success, fry rearing and over-wintering survival. Consequently, reduced fish catching

success and fishing participation would be expected under these alternatives. A high percentage of the fishing for resident species on Lake Umatilla occurs in shallow backwaters and embayments. At MOP under these SOSs, the areal extent of the backwaters would be greatly reduced and access to many preferred fishing areas would be eliminated during the drawdown period.

Under the PA, drawdown of John Day Pool to MOP would reduce the shallow water habitat by the same amount year-round. Ultimately, however, year round drawdown to MOP may allow some shallow water habitat to reestablish at the lower elevation. It is estimated that it would take at least 3–5 years for aquatic vegetation and food base to develop in new shallow water areas. This would allow for some re-establishment of habitat over several years. It is unknown at this time to what extent habitat would develop or if acreage of shallow water habitat would be comparable to present conditions. From limited available data on pool topography it appears that the amount of shallow water areas (potential habitat development) at elevation 257' will be substantially less than current conditions due to configuration of the river channel. Therefore, it is assumed that initial impacts to recreational fishing under the PA would be severe. Some fishing habitat and fishing access may be restored over time but probably not to the extent of existing habitat.

For walleye, none of the alternatives would be particularly beneficial. SOS 1A would be slightly better than the other SOSs. No significant change in fishing or fishing success for walleye would be expected as a result of any of the SOSs.

4.2.17.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

The Umatilla National Wildlife Refuge, operated by the USFWS, and the Irrigon and Willow Creek Wildlife Management Areas, operated by ODFW, are located on the upper half of the John Day pool. Waterfowl hunting, fishing, wildlife viewing and other refuge associated activities are very important at Lake Umatilla.

The SOR wildlife appendix (Appendix N) describes impacts of the alternative SOS's to species and

habitats at Lake Umatilla. These impacts may correspondingly affect wildlife-related recreational activities.

Under SOS 1a, 1b, 2c, 2d, 4c, and 9b operational limits are designed take waterfowl habitat and associated recreation into consideration and benefit them. The lake is held at a lower pool (maximum of elevation 263.5 ft.) in the spring through the end of June for flood control purposes, and also to protect nesting waterfowl. After October 31, the maximum pool elevation is dropped back down to elevation 263.5 ft. Maintaining this elevation during waterfowl hunting season allows access to the shoreline for hunters and other users and provides good waterfowl hunting opportunities.

Under SOS 5b, 5c, 9a and 9c, the annual drawdown of Lake Umatilla to MOP from May through August would perch marshes and riparian habitat areas well above the actual water level. The amount of shallow water habitat at Lake Umatilla would be reduced by approximately 6000 acres for four to five months of the year. Drawdown and subsequent loss of standing water in marsh habitats would result in loss of nesting, foraging, escape and hiding cover for waterfowl and other species using those areas.

The predominant wildlife-related recreational activity on Lake Umatilla is waterfowl hunting in the fall and winter. Under these strategies, the reduction in waterfowl species for hunting would be minimal because the local duck population comprises only a very small percentage of the total wintering population. Migrant waterfowl form the majority of birds available for hunting. These populations arrive in the fall after the elevation of Lake Umatilla has been brought back up and are not directly affected by the summer drawdown. After October 31, the maximum pool elevation is back down to elevation 263.5 ft. This is considered the optimum pool elevation during waterfowl hunting season because it allows access to the shoreline and duck blinds. For comparison, local production is roughly estimated at 2,000 ducks annually, while wintering waterfowl populations range from 100,000 ducks and 100,000 Canada geese, depending upon crop patterns and other factors (Dorsey, 1993). Loss

of local waterfowl production might be noticeable in the very early portion of the hunting season when local birds comprise most of the harvest.

On the other hand, wildlife viewing opportunities during the spring and summer would probably decline. The mix of species available for viewing would change. Loss of water from McCormick Slough, Patterson Slough, Irrigon and other developed wildlife viewing areas at Umatilla Refuge would have the most profound effect on wildlife viewing. Ducks, rails and other species associated with emergent marsh, riparian and submergent aquatic plant communities would be adversely affected. Other species which take advantage of mudflats and shallow ponds, primarily shorebirds, would have improved habitat conditions.

Under the PA, year-round drawdown would result in more severe impacts to hunting, wildlife viewing and other recreational activities. In addition to the loss of local waterfowl populations, the habitat that supports the large wintering populations that provide the bulk of waterfowl hunting opportunities would be greatly reduced. Consequently, it is anticipated that hunting success and demand would suffer.

Ultimately, however, year round drawdown to MOP may allow some shallow water habitat supporting waterfowl and other species to reestablish at the lower elevation. It is estimated that it would take at least 3–5 years for emergent marsh/aquatic vegetation to develop in new shallow water areas. This would allow for some re-establishment of habitat over several years. It is unknown at this time to what extent habitat would develop or if acreage of shallow water habitat would be comparable to present conditions. From data on pool topography it appears that the amount of shallow water areas (potential habitat development) at elevation 257 feet will be substantially less than current conditions due to configuration of the river channel. Therefore, it is assumed that initial impacts to waterfowl hunting under the PA could be severe. The level of impact would be very severe if the irrigated crop base, particularly field corn, is reduced or lost as a result of drawdown. Some waterfowl habitat and hunting access may be restored over time but probably not to the extent of existing habitat.

4.2.17.6 Effects on Recreational Safety and Physical Characteristics

High water velocities. High water velocities are an existing hazard in the Columbia River; the powerful hydrodynamics associated with operation of the dams can be particularly dangerous for small craft. Safety hazards occur for recreational navigation occur both above and below the dams during releases. River velocities vary considerably with natural river flows.

Flows in Lake Umatilla under SOS 1a and 1b would remain within the normal range; most recreationists are prepared to deal with a wide range of water velocities as a natural hazard.

All other SOSs (particularly 9a and 9b) would result in significantly higher average flows during the spring flood period (May and June), but flows would remain well within the normal range for the project and would not create any new or more serious hazards.

Shoaling. Shoaling is an existing problem at Lake Umatilla which is exacerbated at low pool. Deposition of sediments and creation of shoals creates difficulties for recreational navigation. Construction of shoreline facilities at most sites on this lake requires special designs to prevent severe sediment deposition. Arlington Park and Crow Butte State Park both have continuing dredging requirements due to sedimentation.

The mouths of many of the small tributary streams form small embayments on Lake Umatilla, including Sundale, Rock, Willow and Alder Creeks. At these sites minimal recreation facilities, including boat ramps, have been provided. In addition to being used as recreation sites, they provide an important safety component for recreational navigation as "harbors of refuge" under high wind conditions. At these locations sedimentation and shoaling are major problems. Most of the sediments are brought in by the tributary streams and are trapped in the embayments by highway and railroad embankments. At each of these sites, the sedimentation problem is considered a major constraint to development additional of facilities to meet future needs. At one time, Rock Creek

Park was a moderately developed recreation site; it is now semi-closed and minimally used due to severe sedimentation in the Rock Creek Arm.

Sediments carried in by the John Day River have also created a shoaling problem 2 miles upstream of Phillipi Park on the John Day Arm of the lake. Continued shoaling could impede recreational navigation upstream to "the Narrows" a popular fishing spot on the John Day arm. Sedimentation could also fill in the boat basins and moorage facilities at both Phillipi and LePage Parks. Sedimentation also occurs in the Columbia River at the John Day River mouth but is not currently a problem for recreational boating.

By maintaining pools at or near full throughout the summer recreation season, SOS 1a, 1b and 4c, would be expected to minimize recreational problems associated with shoaling and sedimentation in Lake Umatilla. Under SOS 2c, 2d and 9b, the pool would be maintained at a lower elevation (262.5 ft) throughout the summer, possibly exacerbating sedimentation problems. However, this intermediate pool is still several feet above the minimum operating pool for Lake Umatilla, so impacts to recreational navigation would be slight. Under SOS 5b, 5c, 9a, 9c and the PA, Lake Umatilla would be held at MOP for extended periods, increasing the severity of existing sedimentation problems.

Shoreline erosion caused by wind-driven wave action has impacted recreation facilities and made access difficult in some places around the shorelines of the reservoirs, particularly Lake Umatilla. Wave cut erosion at the low pool line has contributed to significant damage at the toes of boat ramps at Alderdale, Roosevelt Park, Crow Butte State Park, and Quesnel Park. Under 5b, 5c, 9a, 9c and the PA, the lakes would be held at minimum pool for longer durations resulting in increased opportunity for erosion at these and other sites.

In addition, erosion at the maximum pool level has created precipitous slopes along the edge of Lake Umatilla, reaching a height of 10 feet in some places. During the winter at high pool periods, wind-driven waves cause significant bank erosion problems at Irrigon Park. In addition to impacting facilities at developed recreation sites, erosion also impacts

general recreational use and access at dispersed locations along the shoreline. Erosion can also severely impact cultural resource sites. Under 5b, 5c, 9a, 9c and the PA, the lakes would be held at low elevations for longer durations, perhaps reducing the potential for erosion at the high pool level.

4.2.17.7 Effects on Water Quality Parameters Influencing Recreation

There are no known significant water quality issues or concerns that affect or influence recreation at Lake Umatilla under any of the alternative SOSs.

4.2.17.8 Effects on Aesthetics

Operation of John Day Project under SOS 1a, 1b or 4c would not have a significant effect on the scenic amenities of the region. In general, visual quality along Lake Umatilla under SOS 2c, 2d and 9b, would be slightly decreased during the five months of the summer when the lake is held at a lower pool (elevation 262.6 ft.). Low water levels create a "bathtub ring" effect around the shoreline of the lakes; dried algae appears white against the dark basalt rocks of the region. More beaches and shoals are also exposed during low pool periods. This is a negative visual affect but to a certain extent is naturally occurring and is not particularly noticeable in comparison with the grand scale of other scenic amenities. Also, since

river levels fluctuate daily within the normal operational range, there is no long-term visual impact.

Operation of John Day Project under SOS 5b, 5c, 6b, 6d, 9a, 9c, and the PA could have a significant effect on the scenic amenities of the region. An estimated 6,000 acres of shallow embayments and backwater areas along Lake Umatilla are dewatered at MOP. These aesthetic impacts would remain constant over the drawdown periods.

4.2.17.9 Mitigation Opportunities

No recreation mitigation actions are needed at Lake Umatilla under SOS 1a, 1b, 2c, 2d, 4c, or 9b.

Under SOS 5b, 5c, 9a, 9c and the PA, operation of John Day project at MOP during some or all of the year would have severe impacts on the usability of many of the recreation facilities on Lake Umatilla. Many of these facilities could be modified to improve their usability at MOP.

Through the John Day Drawdown Advanced Planning and Design (AP&D) Study, authorized by the Energy and Water Development Appropriations Act of 1993 (Public Law 102-377, October 2, 1992), the Corp of Engineers, Portland District has undertaken advanced planning and design of modifications to public and private facilities, including recreation facilities of John Day Dam at MOP. Table 4-43 presents a summary of recreation site impacts and the actions possible to mitigate those impacts.

Table 4-43. John Day Drawdown to MOP; Recreation Site Impacts Assessment and Recommended Mitigation Actions (Site evaluations base on 1994/95 hydrosurvey data)

River Mile	MANAGING ENTITY	SITE ELEMENTS – MODIFICATIONS					Backwater Elevation	SCS Phase 1 Cost (\$000)
		BOAT RAMP	BOAT DOCK(S)	MOORAGE, FUELING & SANITARY DOCKS	SWIM BEACH	COMMENTS **Include trash cleanup at all sites		
216	Railroad Island, WA (North Shore) / COE	35 ft. extension	Add two 20 ft. segments	N/A	N/A		257	\$67.20
218	Le Page Park, OR / COE	36.4 ft. extension	Add two 20 ft. segments @ N. side boat ramp dock w/1 U-pile.	Modify gangways to Docks #1-4	Sign shallow Areas		257	\$177.60
JD RM 4	Philippi Park, OR / COE	no existing ramp	Modify gangway skid Plates.	a) S. Dock – move short hinged dock out one dock segment. b) N. Dock – OK but consider dredging.	N/A	a) Check gangway skids b) Dredging/excavation required adjacent to docks to remove silt buildup	257.3	\$105.70
229	Rock Creek Park, WA / COE	16.1 ft. extension		No others	Beach is dry	Hydro survey indicates channel dredging required.	257	\$40.20
233.5	Blalock Canyon, OR / COE	100 ft. extension (fill only, no concrete planks)	none	N/A	N/A	Fill required to extend boat ramp; very shallow within launch area and at culvert.	257	\$37.10
236.5	Sundale Park, WA / COE to BIA	55 ft. extension	60-80 ft. extension w/ 3 piles	N/A	Add buoys		257	\$80.30
241	Roosevelt Park, WA / COE	no impact	Modify Gangway skid plate.		Need more information		257	\$152.80
241	Arlington Marina / Park, OR / Port of Arlington / City of Arlington	22.4 ft extension	a) 20 ft. extension w/ U-piling. b) Modify gangway skid plates for all docks.	a) Excavate under small dock. b) Modify gangway skid plate. c) Excavate under band-stand approach pad to Elev. 255 (2' depth).	Dredging required		257.1	\$285.00
255	Three Mile Canyon, OR / COE	51.2 ft. extension	Previously existing dock removed; new dock if to be replaced, piles.			a) Mark channel at West entrance. b) Sign East entrance as "Shallow Channel"	257.1	\$142.94
261	Crow Butte St. Park, WA / Washington State Parks	a) Consider high water use only. b) Extend boat basin ramp 46.4 ft.	a) Add two/three 20 ft. segments w/ 1-2 piles. b) Modify gangway skid Plates.	Boat basin courtesy/waste dump dock has inadequate draft; excavate under or relocate.	Dredge / excavate	Embayment Boat Ramp – Requires fill for extension. 7.5 ft depth of rock excavation required in embayment to accommodate 10 ft. draft vessels (12 ft draft required).	257.2	\$244.60

Table 4-43. John Day Drawdown to MOP; Recreation Site Impacts Assessment and Recommended Mitigation Actions (Site evaluations base on 1994/95 hydrosurvey data) – CONT

River Mile	MANAGING ENTITY	SITE ELEMENTS – MODIFICATIONS					Backwater Elevation	SCS Phase 1 Cost (\$000)
		BOAT RAMP	BOAT DOCK(S)	MOORAGE, FUELING & SANITARY DOCKS	SWIM BEACH	COMMENTS **Include trash cleanup at all sites		
269	Boardman Park, OR / Boardman Park & Rec. District	49.7 ft extension	a) Add 20 ft. segment w/ 1 pile. b) Modify gangway skid plates.	a) Floating Dock – Dredge under high corner and rotate 45 degrees, add 1 pile. b) Moorage dock #1 – excavate to prevent torque. c) Moorage dock #2 – modify access by relocating gangway anchor block.	Dredge / excavate		257.3	\$5,882.4
282	Irrigon Park, OR / Irrigon Park & Rec. District	62.4 ft extension (verify hydro survey)	Modify gangway skid plates.	Blast in rock approx. 4 feet to achieve 10 ft draft.	Repair bank erosion	At El. 264 /buoy area, depth is 6.2', just beyond slope changes to 1v:5h, dredging required, SEE NOTE 4	258	\$174.02
289	Plymouth Park, WA / COE	no impact	a) Two 20 ft. segments each side w/ 1 piling each side. b) Modify gangway skid plates	Tie-up dock needs 25' extension w/ 5 piles (SEE NOTE 1).	Major excavation required (SEE NOTE 2)	Approach channel to Swim Beach needs to be opened up to allow fresh water exchange including removal of gravel bar at slough entrance.	260.2	\$192.62
289	Umatilla Park, OR / Port of Umatilla	no impact	a) Boat ramp south dock – extend two 20 ft. segments, Add one U-Pile. b) Replace 22 piles. c) Swap deep & shallow docks. d) Modify gangway skid plates.	a) Fuel Dock connection OK; temporarily relocate during excavation. b) Swap shallow & deep draft docks. c) Excavate a minimum of 3 ft deep to provide a 10 ft draft (See Note 5)	Major excav. required (SEE NOTE 3)	Blasting is required to provide 10' draft from the marina entrance to a point approx. 50' beyond the relocated deep draft dock (SEE NOTE 4).	260.7	\$5,731.90
289, UR 0.5	Nugent Park, OR / City of Umatilla	Consider relocation of ramp and HC fishing access facility	Add gangway to existing dock, may require driving 1 pile			ALL FEATURES HIGH AND DRY! COE – Leasing HC Fishing Platform only	260.7	\$227.14
(1995 indexed cost)								\$13,800

NOTES:

1. The gangway for the Tie-up Dock will be partially on dry land at Elev. 258 (Elev. 257 plus backwater) and will require an extension of approx. 25 feet. This can be accomplished by saving the existing gangway and skid plate, connecting the remaining skid plate dock segment to the existing piles adjacent to the dock segment, connecting a new 25 ft. gangway to the remaining skid plate dock, and moving the remaining portion of existing dock to the new gangway. This design utilizes two existing piles but requires that 5 new piles be drilled. Will evaluate excavation as a solution.
2. The Swim Beach is basically dry at Elev. 258. The available swimming area will be approx. 2ft. deep and too small for swimming activity. The team suggests that the North bank of the swim basin be excavated to a Elev. 253. This would allow a 5 ft. depth considering the backwater elevation at JD MOP Elev. 257. In addition, the basin entrance channel should be regraded and excavated to the same depth. This may require cofferdaming the entrance to the swimming basin.

Table 4-43. John Day Drawdown to MOP; Recreation Site Impacts Assessment and Recommended Mitigation Actions (Site evaluations base on 1994/95 hydrosurvey data) – CONT

NOTES:

3. The Swim Beach at Umatilla Park requires dredging/excavation to provide adequate swimming area. This can be accomplished by steepening the beach slope to 1v:12h from Elev. 264 to Elev. 252. The hydro survey information indicates dredgeable material to Elev. 252.
4. The study team has inadequate data on the entrances to the Umatilla and Irrigon Boat Basins. This information will need to be obtained in order to design cofferdams used for dewatering during construction.
5. Boat basin (Umatilla Marina, Irrigon Marina, Crow Butte State Park, and Boardman Marina) bottom surface is rock. It is believed that excavation may be accomplished by utilizing a D-10 ripper in the dry. Blasting may be required.

4.2.18 THE DALLES PROJECT (LAKE CELILO)

4.2.18.1 Description/Hydrologic Characteristics

The Dalles Project is a run-of-river dam. The recreational suitability of Lake Celilo is affected by both pool elevations (as measured as forebay elevation at The Dalles Dam) and flows (as measured by average monthly releases from John Day Dam). The optimum pool elevation of Lake Celilo for recreation is 159 feet NGVD. The Dalles Dam can be operated from a minimum pool of 155.0 feet up to a maximum pool of 160.0 feet. However, the normal operational range is narrower, from 157 to 160 feet. Elevations within this normal range of operations have minimum impacts to recreation facilities. Under all of the alternative SOSs, the pool elevation would be maintained within this normal operating range. Therefore, the only significant difference between the alternative SOS's would be in terms of the flows passing through Lake Celilo. Although it

varies depending upon a number of factors, including the recreational activities being participated in, the optimum range of flows for recreation at Lake Celilo is generally considered to be from 150 to 250 kcfs (4230 to 7050 cms).

Average monthly flows at The Dalles Project are strongly influenced by the natural hydrograph of the Columbia River basin. Table 4-44 displays average monthly flows released through The Dalles Dam under the 13 alternative SOSs. As shown, under all of the SOSs, actual flows vary considerably through the summer recreation season with the natural hydrograph, generally peaking in May or June, and declining through the summer to a low in August or September. The major effect of the alternative SOSs would be to shift the peak and low flow periods around during the summer recreation season. Table 4-45 compares the average flows during June, July and August and displays the percentage of years that flows would be greater than, less than or within the preferred range for recreation in those months.

Table 4-44. The Dalles Lock & Dam/Lake Celilo — Average Monthly Outflows (KCFS) for Alternative SOSs

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	216	200	191	225	282	253	173	119	112	116	129	154
1b	217	202	182	219	273	259	179	119	115	120	132	156
2c	212	200	178	225	285	272	175	121	109	117	127	153
2d	172	195	201	223	269	287	199	118	109	117	125	151
4c	208	195	172	229	281	291	190	112	93	113	122	163
5b	213	209	194	224	286	271	172	116	88	118	126	155
5c	214	201	177	224	286	271	172	116	109	118	129	156
6b	213	201	178	224	286	271	172	116	94	119	129	157
6d	213	201	117	224	286	271	172	116	105	119	129	157
9a	148	172	207	283	292	302	237	166	82	88	89	133
9b	158	181	212	296	283	300	203	138	82	88	102	153
9c	172	194	219	243	267	272	205	130	80	99	125	163
PA	170	182	196	259	278	295	209	131	93	102	112	148

Table 4-45. The Dalles Lock & Dam/Lake Celilo, Summer Average Monthly Flows (KCFS) and Percent of Years Within Optimum Recreation Range

SOS	June			July			August	
	Average Flows (Kcfs)	% Years Flows in Optimum Range	Average Flows (Kcfs)	Percent of Years Flows			Average Flows (Kcfs)	% Years Flows in Optimum Range
				> 250 kcfs	Optimum Range	< 150 kcfs		
1a	253	48	173	16	36	48	119	6
1b	259	48	179	20	30	50	119	8
2c	272	52	175	16	42	42	121	10
2d	287	46	199	22	54	24	118	6
4c	291	36	190	26	44	30	112	4
5b	271	50	172	16	42	42	116	4
5c	271	50	172	16	42	42	116	4
6b	271	50	172	16	42	42	116	4
6d	271	50	172	16	42	42	116	4
9a	302	28	237	26	74	0	166	100
9b	300	30	203	22	64	14	138	48
9c	272	48	205	26	52	22	130	24
PA	295	32	209	20	66	14	131	30

Under **SOS 1a and 1b**, flows peak during May and then drop quickly through June and July. During July, flows under SOS 1a are within the preferred recreation range 36 percent of years as compared to only 30 percent for SOS 1b. Under both SOSs, minimum annual flows are reached during August, September and October during which time they remain relatively stable between 110 and 120 kcfs (3300 cms). During August, flows are lower than the preferred minimum for recreation during 94 percent of years.

Recreation conditions at Lake Celilo under SOS 1a and 1B are expected to be slightly better under high water years than average water years, while average water years are slightly better than low water years. This is attributable to the fact that, while pool elevations at the project are maintained within a relatively narrow range under all water conditions, low flow conditions combined with low pool elevations during late summer and early fall would negatively impact some recreation facilities.

Average monthly flows under **SOS 2c** are similar to those under SOS 1b and 1a. Peak annual flows in May are greater than the maximum preferred flow for recreation in June during 48 percent of years. The only significant difference between these three alternatives is that flows are slightly higher in June under SOS2c. August flows are below the preferred minimum flows for recreation during 90 percent of years.

Under **SOS 2d**, peak flows are shifted from May to June. Higher flows during the months of June and July would average approximately 40 cfs (1130 cms) higher than under SOS 1a, 1b, or 2c. June flows would be higher than the preferred maximum during 58 percent of years but would fall within the preferred range in July during 52 percent of years.

SOS 4c is similar to SOS 2d. Flows peak in June when they would be greater than the maximum preferred flow at during 64 percent of years. Flows decline sharply in July and would fall within the preferred range during 44 percent of years. In

August, flows would be lower than the preferred minimum for recreation during 96 percent of years. By September average flows fall well below the minimum preferred flow for recreation nearly 100 percent of years.

Flows under **SOS 5b, 5c, 6b and 6d** would be similar to those under **SOS 2c**. The biggest difference between these alternatives and the other SOSs is that they shift higher peak flows to May and have lower average flows in June, July and August. In July, flows would fall within the preferred recreation range during 42 percent of years, compared to the 42 percent of years that flows would be below the preferred minimum of 150 kcfs. By August, flows under these SOS fall below the preferred minimum flow during 96 percent of all years.

SOS 9a features much higher flows during May through August than any of the other alternatives. June flows would be above the preferred maximum for recreation during about 72 percent of years. This effect would be balanced, however, by more consistent flows during the remainder of the summer recreation season. For example, during July, the average flow would be within the preferred range during 74 percent of years. During August, flows remain above the preferred minimum during 100 percent of years. By September, however, average monthly flows drop to 82 kcfs well below flows for that month under **SOS 1a** or **2c**.

SOS 9b would also feature higher flows during the summer recreation season than either **SOS 1a** or **2c** but not as high as **9a**. They would start out slightly higher than under **SOS 9a** in April, remaining relatively constant through June at 300 kcfs (8500 cms). By July and August, flows drop considerably lower than under **SOS 9a**. However, in comparison with the other SOSs, July and August flows would still be relatively good for recreation, remaining within the preferred range 64 and 52 percent of years during those months, respectively. September flows would also be well below those of **SOS 1a** or **2c**.

SOS 9c would begin the summer recreation season with slightly lower flows in May than any of the

other SOSs. Peak flows would be shifted to June. Flows would be reduced during the remainder of the summer.

The **PA** would feature higher flows during the summer recreation season than either **SOS 1a** or **2c**. They peak in June when flows would be higher than the preferred maximum during 68 percent of years. Flows would remain relatively high in July and August. In comparison with the other SOSs, July and August flows would be relatively good for recreation, remaining within the preferred range 66 and 62 percent of years during those months, respectively.

4.2.18.2 Quantitative Results of Impact Assessment Models

No recreation impact assessment models were developed for this FEIS for estimating quantitative changes in visitation at Lake Celilo. Pool elevations will remain stable within the normal five foot operating range of The Dalles Dam across all months for all alternatives. Although average monthly flows through Lake Celilo will vary across the SOSs, they will remain within normal historic ranges. Under these circumstances, it is believed that none of the alternative SOSs will significantly affect recreational use of Lake CELILO in terms of total annual visitation. Average annual visitation to Lake Celilo from 1987 through 1993 was 2,191,200 recreation days. No measurable change in average annual visitation is expected under any of the alternative SOSs.

The SOR Draft EIS (DEIS) and Draft Appendix J did present the results of models used to estimate changes in annual recreation visitation to Lake Celilo. Total estimated annual visitation under the 21 alternative SOSs considered in the DEIS varied no more than 5 percent. Those models were based on average monthly flows and did not consider the impacts of short term operations (weekly and daily) on recreation. The RWG decided that the models used in the DEIS were not accurate enough for use in the final EIS and they have been deleted in the FEIS and final Appendix J.

4.2.18.3 Effects on Recreation Facilities/Activities

Of the four lower Columbia projects, Lake Celilo is the least sensitive to fluctuations. The Dalles is a run-of-river project that normally experiences daily 1 to 3 foot fluctuations in pool elevation year-round. However, most recreation facilities at the lake are designed to remain usable over the entire normal 5 foot operational range of the lake. The recreational suitability of Lake Celilo is maximized at about 159 ft. NGVD, one foot below full operating pool of 160 feet. From maximum pool down to 157 feet, levels of recreational impact are small.

As the lake approaches the minimum operating pool of 155 feet, some impacts to recreational facilities do occur. Some boat ramps become only marginally usable at minimum pool with inadequate depth for safe launching of larger trailered boats, including Maryhill State Park, Celilo Park, and Horsethief Lake State Park. Also, swimming beaches become only marginally usable at minimum operating pool.

There would be no significant variation in pool elevations of Lake Celilo as measured at the forebay of the Dalles Dam under any of the alternative SOS's. However, since Lake Celilo is the shortest of the lower Columbia River reservoirs, releases from John Day Dam can create a backwater curve in which pool elevations are higher at the upper end of the reservoir. The backwater curve is not significantly noticeable at low flows under 150 kcfs and impacts to recreational facilities are marginal.

4.2.18.4 Effects on Fish Habitat and Fishing Success

Preliminary results from the Anadromous Fish Work Group indicate that none of the alternative SOS's under consideration would result in significant benefits or impacts to anadromous fish species (salmon and steelhead). Consequently, none of the alternative SOS's are expected to have any significant effect on fishing success for anadromous fish at Lake Celilo.

None of the alternative SOSs are expected to have any significant effects on resident game fish species,

including walleye, smallmouth bass, largemouth bass, or white sturgeon.

4.2.18.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

None of the alternative SOS's is expected to have any significant impact on existing wildlife habitat conditions along Lake Celilo. Consequently, no significant impacts to wildlife viewing or hunting would occur.

4.2.18.6 Effects on Recreational Safety and Physical Characteristics

Under all of the alternative SOS's, flows in the river peak in May or June and decline rapidly over the summer and early fall. As flows and water levels drop in Lake Celilo, the amount of surface area available for water-based recreational use declines. Because of the steep, confined topography of the Columbia River channel, a small drop in pool elevation would not cause a correspondingly large reduction in lake surface area except at a few locations where the lakes inundate former terraces or bottomlands and the bottom is flat or shallow. These locations tend to be popular sites for water-based recreation, including swimming and windsurfing.

Low water levels may expose dangerous tree stumps, rocks and shoals that are hazardous to activities such as boating, waterskiing and windsurfing. Under SOS 1a, 1b, 2c, 2d, 5c and 6d, the low flow period occurs in September at about 110 to 115 kcfs (3100 to 3250 cms). In comparison, September flows under SOS 4c, 5b, 6b, 9a, 9b, and 9c are all considerably lower, ranging from 80 kcfs (1800 cms) to 95 kcfs (2700 cms). Each of these would exacerbate low flow hazards. However, the average flows are all within the normal historical operating range of the reservoir. Since the rocky shoreline of the Columbia River is dangerous under any operating conditions; most recreationists are aware of those normal hazards.

In Lake Celilo, significant sedimentation occurs in the reservoir arms of the Wind, Klickitat, White Salmon, Little White Salmon and Hood Rivers, each of which is a popular fishing and boating location. Low pool elevations increase navigation difficulties

in these shoal areas. Again, low flow conditions in September under SOS 4c, 5b, 6b, 9a, 9b, 9c, and the PA could exacerbate these conditions.

Several of the alternatives, particularly SOS 2d, 4c, 9a, 9b, 9c, and the PA, would result in higher average flows during the spring flood (May–June) period than are experienced under SOS 1a or 2c, increasing slightly the safety hazards associated with river flows and velocities. These higher spring and late summer flows may, however, reduce constraints to recreational navigation caused by shoaling and sedimentation.

4.2.18.7 Effects on Water Quality Parameters Influencing Recreation

There are no known significant water quality issues or concerns that affect or influence recreation at Lake Celilo under any of the alternative SOS's.

4.2.18.8 Effects on Aesthetics

Operation of The Dalles Dam under all of the alternative SOS's does not have a significant effect on the scenic amenities of the region. In general, visual quality along Lake Celilo is increased when the river is at a higher level. Low water levels create a "bathtub ring" effect around the shoreline of the lakes; dried algae appears white against the dark basalt rocks of the region. This is a negative visual affect but to a certain extent is naturally occurring and is not particularly noticeable in comparison with the grand scale of other scenic amenities in the region. Also, since river levels fluctuate daily within the normal operational range, there is no long-term visual impact.

4.2.18.9 Mitigation Opportunities

No recreation mitigation actions are recommended at Lake Celilo under any of the alternative SOS's under consideration.

4.2.19 BONNEVILLE PROJECT / LAKE BONNEVILLE

4.2.19.1 Description/Hydrologic Characteristics

Bonneville Project is a run-of-river dam. The recreational suitability of Lake Bonneville is affected by both pool elevations (as measured as forebay elevation at Bonneville Dam) and flows (as measured by average monthly releases from Bonneville Dam). The optimum pool elevation of Lake Bonneville for recreation is 76.5 ft. While the operational range of Bonneville Dam is from a minimum pool of 70.0 ft. up to a maximum pool of 77.0 feet, normal operations are narrower, ranging from 71.5 to 76.5 feet. Forebay elevations within the normal range of operations would have minimum impacts to recreation facilities on Lake Bonneville.

During summer months, the project typically releases low flows in early morning hours up to maximum value 10:00 AM and holds the high value until about 11:00 PM. This normally occurs on a daily basis except on weekends and results in tailwater fluctuations of 2–6 feet (0.6 to 1.8 m). Weekend

fluctuations are usually significantly less because power demands are at a lower level.

Although it varies depending upon a number of factors, including the types of recreational activities being participated in, the estimated optimum range of flows for recreation on Lake Bonneville are from 150 to 250 kcfs (4300 to 7100 cms). Effects of high and low flows above and below this range are described in succeeding sections.

Average monthly flows at Bonneville Project are strongly influenced by the natural hydrograph of the Columbia River basin. Table 4–46 displays average monthly flows released through the dam under the 13 alternative SOSs. As shown, under all of the SOSs, actual flows vary considerably with the natural hydrograph through the summer recreation season, generally peaking in May or June, and declining through the summer to a low in August or September. The major effect of the alternative SOSs would be to shift the peak and low flow periods around during the summer recreation season. Table 4–47 compares the average flows during June, July and August and displays the percentage of years that flows would be greater than, less than, or within the preferred range for recreation in those months.

Table 4–46. Bonneville Lock and Dam/Lake Bonneville, Average Monthly Outflows (KCFS) for Alternative SOSs

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	225	209	198	233	287	256	176	121	114	119	134	162
1b	225	211	190	227	278	262	182	121	117	123	137	164
2c	220	208	186	233	290	275	178	123	112	120	132	161
2d	181	203	209	230	274	290	202	120	111	120	130	159
4c	216	204	179	237	286	294	193	114	95	116	127	171
5b	221	217	201	232	291	274	175	119	91	121	131	163
5c	222	209	185	232	291	274	175	119	112	121	135	165
6b	221	209	185	232	291	274	175	119	97	122	135	165
6d	221	209	185	232	291	274	175	119	108	122	135	165
9a	157	180	215	290	297	305	240	168	84	90	94	141
9b	166	188	219	304	288	303	206	140	84	91	107	161
9c	181	202	226	251	272	275	208	132	83	102	131	171
PA	179	191	203	267	283	297	212	133	96	105	117	156

Table 4-47. Bonneville Lock & Dam/Lake Bonneville, Summer Average Monthly Flows (KCFS) and Percent of Years Within Optimum Recreation Range (150–250 KCFS)

SOS	June			July			August	
	Average Flows (Kcfs)	% Years Flows in Optimum Range	Average Flows (Kcfs)	Percent of Years Flows			Average Flows (Kcfs)	% Years Flows in Optimum Range
				>250 kcfs	Optimum Range	<150 kcfs		
1a	256	48	176	18	38	44	121	8
1b	262	46	182	22	56	22	121	10
2c	275	42	178	16	42	42	123	12
2d	290	42	202	22	58	20	120	10
4c	294	34	193	28	44	28	115	8
5b	274	42	175	16	40	44	119	8
5c	274	44	175	16	40	44	119	6
6b	274	44	175	16	40	44	119	8
6d	274	44	175	16	40	44	119	8
9a	305	26	240	30	70	0	168	100
9b	303	30	206	22	56	22	140	52
9c	275	42	208	26	52	22	132	28
PA	297	34	212	22	64	14	133	38

Under **SOS 1a and 1b**, flows peak during May with averages of about 280 kcfs (8000 cms) and then drop slightly in June to about 260 kcfs (7100 cms). By July, they fall significantly to about 180 kcfs (4900 cms) when they are within the preferred recreation range only 38 percent of years in SOS 1a as compared to 56 percent for SOS 1b. Under both SOSs, minimum annual flows are reached during August, September and October when they remain pretty stable at an average of around 121 kcfs (3200 cms). During August, flows are lower than the preferred minimum for recreation during approximately 90 percent of years.

Under **SOS 2c** flows are similar to those under SOS 1b and 1a, peaking during May. They remain greater than the maximum preferred flow for recreation in June during 42 percent of years. The only significant difference between these three alternatives is that flows are slightly higher in June under SOS2c. August flows average 123 kcfs (3400 cms) and are

below the preferred minimum for recreation during 88 percent of years.

SOS 2d and 4c are similar, with peak flows shifted from May to June. Flows during the months of June and July would average approximately 25 to 30 cfs (700 to 850 cms) higher than under SOS 1a, 1b, or 2c. June flows would be higher than the preferred maximum during 42 and 34 percent of years for 2d and 4c, respectively, but would fall within the preferred range in July during 58 and 44 percent of years. In August, flows would be lower than the preferred minimum for recreation during 90 and 92 percent of years. The only significant difference between SOS 2d and 4c occurs in September when average flows are 111 and 95 kcfs, respectively. However, September flows for both fall well below the minimum for recreation nearly 100 percent of years.

Flows under **SOS 5b, 5c, 6b and 6d** would be similar to those under SOS 2c. The biggest difference

between these alternatives and the other SOSs is that they substantially shift higher peaks to earlier in spring. Flows peak at an average of 291 kcfs (8000 cms) during May and drop off slightly by June when they are greater than the maximum preferred flow for recreation about 56 percent of years. In July, a significant drop would result in flows within the preferred recreation range during only 40 percent of years, compared to the 44 percent of years that they would be below the preferred minimum of 150 kcfs. By August, flows fall to an average of 119 kcfs (3400 cms), well below the preferred minimum.

The predominant feature of SOS 9a is much higher flows during May through August than any of the other alternatives. June flows would be above the preferred maximum for recreation during about 70 percent of years. This effect would be balanced, however, by more consistent flows during the remainder of the summer recreation season. For example, during July, the average drops to 240 kcfs (6800 cms) and would be within the preferred range during 70 percent of years. During August, flows remain above the preferred minimum during 100 percent of years. By September, however, average monthly flows drop well below that month under SOS 1a or 2c.

SOS 9b would also feature higher flows during the summer recreation season than either SOS 1a or 2c. They would start out slightly higher than under SOS 9a in April, remaining relatively constant through June. By July and August, flows drop considerably lower than under SOS 9a. However, in comparison with the other SOSs, July and August flows would still be relatively good for recreation, remaining within the preferred range 56 and 52 percent of years during those months, respectively. September flows would also be well below those of SOS 1a or 2c.

SOS 9c would begin the summer recreation season with slightly lower flows in May than any of the other SOSs. Peak flows would be shifted to June and would remain relatively high in July. Flows would be reduced during the remainder of the summer.

The PA would feature higher flows during the summer recreation season than either SOS 1a or 2c. They peak in June when they would be higher than the preferred maximum during 66 percent of years. Flows would remain relatively high in July and August. In comparison with the other SOSs, July and August flows would be relatively good for recreation, remaining within the preferred range 64 and 32 percent of years during those months, respectively.

4.2.19.2 Summary of Quantitative Impacts

No recreation impact assessment models were developed for this FEIS for estimating quantitative changes in visitation at Lake Bonneville. Pool elevations will remain stable within the normal five foot operating range of Bonneville Dam across all months for all alternatives. Although average monthly flows through Lake Bonneville will vary across the SOSs, they will remain within normal historic ranges. Under these circumstances, it is believed that none of the alternative SOSs will significantly affect recreational use of Lake Bonneville in terms of total annual visitation. Average annual visitation to Lake Bonneville from 1987 through 1993 was 2,191,200 recreation days. No measurable change in average annual visitation is expected under any of the alternative SOSs.

The SOR Draft EIS (DEIS) and Draft Appendix J did present the results of models used to estimate changes in annual recreation visitation to Lake Bonneville. Total estimated annual visitation under the 21 alternative SOSs considered in the DEIS varied no more than 5 percent. Those models were based on average monthly flows and did not consider the impacts of short term operations (weekly and daily) on recreation. The RWG decided that the models used in the DEIS were not accurate enough for use in the final EIS and they have been deleted in the FEIS and final Appendix J.

4.2.19.3 Effects on Recreation Facilities/Activities

Lake Bonneville is a run-of-river project. Most recreation facilities at the lake are designed to remain usable over the entire normal 5 foot operational range of the lake. The recreation potential of

Lake Bonneville is at its peak at full operating pool, elevation 76.5 ft, and when flows are within the range of 150 to 250 kcfs. Impacts are minimal down to elevation 72.5 ft. Maintenance of pool elevations within that range during the peak summer recreation season would maximize recreational use.

The normal (average) minimum pool for Lake Bonneville (71.5 ft.) is significantly higher than the actual minimum pool (70.0 ft.). The additional 1.5 foot (0.5 m) drop in pool elevation from the average minimum pool occurs during low flow periods of summer and late fall can have moderate impacts on recreation. When the lake is at or near Minimum Operating Pool elevation during low flow periods, many of the facilities are only marginally usable.

Boat ramps, moorages, docks and other facilities at Hood River Boat Basin and Marina and Mayer State Park are unusable during shallow water conditions under any of the alternative SOSs (combined low flow and low pool elevations). Other ramps at Drano Lake and Wind River are affected by shoaling and shallow water conditions. Boat ramps at The Dalles Boat Basin and Marina and at Cascade Locks Marine Park remain usable for launching smaller boats at minimum pool. However, water depths would be just marginally over 3 feet in depth, restricting launching of larger boats such as fixed-keel sailboats which are popular at the site.

Shallow depths within protected boat basins, often caused by sedimentation and shoaling, can be a problem at low pool elevations. For example, the channel and boat basin at Mayer State Park has a design depth of 67.7 feet. At minimum operating pool, the depth of the boat basin and channel is about 5 feet. Nevertheless, under normal operating conditions, Mayer Park is a popular moorage for deep keel sailboats. In 1990, Oregon State Parks added new dock facilities at the park to promote this and other boating uses.

Siltation at the mouth of Hood River also causes a shallow entrance to the Hood River Boat Basin, estimated at about 4 feet in depth at minimum operating pool. The Port of Klickitat Boat Basin at

Bingen is also impacted by shallow water with low summer flows under existing operations.

At Mayer State Park the lower end of beach sand is at elevation 71.5 feet, leaving the entire beach area high and dry at minimum operating pool. At the Dalles Riverfront Park, at minimum operating pool, the swimming floats and buoys would have a water depth of only about 3 feet, which is inadequate for full enjoyment of the activity. Swimmers could be expected to move further out into the channel to reach an acceptable depth, possibly conflicting with other uses.

At the Port of Hood River "events area", the most heavily used windsurfing site in the Columbia Gorge, it is necessary for windsurfers to carry their boards and equipment across approximately 300 feet of beach to reach the river at minimum operating pool. Similar conditions exist at The Dalles Riverfront Park, where the shore of the river is be moved out about 75 feet at minimum pool. River wash stone placed on the beach at this park to cover a mud substrate is be exposed, forcing users to cross an unappealing beach.

Decreases in the size of the pool at high use areas such as Hood River and The Dalles shorten the reach that windsurfers have to sail, concentrating more participants into a smaller area in the channel.

In Lake Bonneville, significant sedimentation occurs in the reservoir arms of the Wind, Klickitat, White Salmon, Little White Salmon and Hood Rivers, each of which is a popular fishing and boating location. Low pool elevations increase navigation difficulties in these shoal areas.

4.2.19.4 Effects on Fish Habitat and Fishing Success

Results from the SOR Anadromous and Resident Fish Work Groups indicate that none of the alternative SOSs under consideration would result in significant benefits or impacts to anadromous or resident fish species in Lake Bonneville (see SOR appendices C and K, respectively). Consequently, no significant change in fish catching success or fishing is expected under any of the SOSs.

4.2.19.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

Results from the SOR Wildlife Work Group indicate that none of the alternative SOSs under consideration would result in significant benefits or impacts to wildlife species at Lake Bonneville (see SOR Appendix N). Consequently, no significant change in hunting or wildlife viewing success is expected under any of the SOSs.

4.2.19.6 Effects on Recreational Safety and Physical Characteristics

Under all 13 SOSs, as flows and water levels drop naturally in Lake Bonneville over the course of the summer recreation season, the amount of surface area available for water-based recreational use declines. Because of the steep, confined topography of the Columbia River channel, a small drop in pool elevation would not cause a correspondingly large reduction in lake surface area except at a few locations where the lakes inundate former terraces or bottomlands and the bottom is flat or shallow. These locations tend to be popular sites for water-based recreation, including swimming and windsurfing.

Low water levels may expose dangerous tree stumps, rocks and shoals that are hazardous to activities such as boating, waterskiing and windsurfing. The rocky shoreline of the Columbia River is dangerous under normal operating conditions; most recreationists are aware of the normal hazards.

As a result of these effects, the numbers of recreationists and types of activities that may be safely accommodated at a water body may be reduced. Congestion is not a serious problem on the Columbia River except during windsurfing events and other peak use periods at popular access points such as Hood River. At present, mostly only experienced

windsurfers frequent the navigation channel; beginners and novices make use of embayments, coves and other protected areas.

An existing safety concern at Hood River, The Dalles, and other locations in the region is the potential for conflicts between windsurfers and barges and other commercial craft in the navigation channel. Under present operations, and at present levels of windsurfing and navigation use this has not been a serious problem; education and coordination between commercial navigators and windsurfers appears to have solved most of the issue.

4.2.19.7 Effects on Water Quality Parameters Influencing Recreation

None of the 13 alternative SOSs would have any significant affect on water quality parameters, issues or concerns that affect or influence recreation at Lake Bonneville.

4.2.19.8 Effects on Aesthetics

None of the 13 SOSs would have a significant effect on the scenic amenities of the region. In general, visual quality along Lake Bonneville is increased when the river is at a higher level. Low water levels create a "bathtub ring" effect around the shoreline of the lakes; dried algae appears white against the dark basalt rocks of the region. This is a negative visual affect but to a certain extent is naturally occurring and is not particularly noticeable in comparison with the grand scale of other scenic amenities in the region. Also, since river levels fluctuate daily within the normal operational range, there is no long-term visual impact.

4.2.19.9 Mitigation Opportunities

No recreation mitigation actions are recommended at Lake Bonneville under any of the alternative SOSs.

4.2.20 COLUMBIA RIVER BELOW BONNEVILLE DAM

4.2.20.1 Description/Hydrologic Characteristics

The focus of this analysis is on flow-related recreational impacts downstream from Bonneville Dam. The further downstream from the dam the less significant those impacts become. Recreation sites below Bonneville Dam down to the lower end of the Columbia River Gorge are included in this analysis because they may be directly impacted by project operations. Below approximately the mouth of the Sandy River, the Columbia River widens and operational impacts on recreation are less significant.

Although it varies depending upon a number of factors, including the types of recreational activities being participated in, the estimated optimum range of flows for recreation on the Columbia River below

Bonneville Dam are from 150 to 250 kcfs (4300 to 7100 cms). Effects of high and low flows above and below this range are described in succeeding sections.

Average monthly flows released from Bonneville Dam are strongly influenced by the natural hydrograph of the Columbia River basin. Table 4-48 displays average monthly flows released through the dam under the 13 alternative SOSs. As shown, under all of the SOSs, actual flows vary considerably with the natural hydrograph through the summer recreation season, generally peaking in May or June, and declining through the summer to a low in August or September. The major effect of the alternative SOSs would be to shift the peak and low flow periods around during the summer recreation season. Table 4-49 compares the average flows during June, July and August and displays the percentage of years that flows would be greater than, less than, or within the preferred range for recreation in those months.

Table 4-48. Columbia River Below Bonneville Dam, Average Monthly Pool Elevations (ft. NGVD) for Alternative SOSs

SOS	Month											
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1a	225	209	198	233	287	256	176	121	114	119	134	162
1b	225	211	190	227	278	262	182	121	117	123	137	164
2c	220	208	186	233	290	275	178	123	112	120	132	161
2d	181	203	209	230	274	290	202	120	111	120	130	159
4c	216	204	179	237	286	294	193	114	95	116	127	171
5b	221	217	201	232	291	274	175	119	91	121	131	163
5c	222	209	185	232	291	274	175	119	112	121	135	165
6b	221	209	185	232	291	274	175	119	97	122	135	165
6d	221	209	185	232	291	274	175	119	108	122	135	165
9a	157	180	215	290	297	305	240	168	84	90	94	141
9b	166	188	219	304	288	303	206	140	84	91	107	161
9c	181	202	226	251	272	275	208	132	83	102	131	171
PA	179	191	203	267	283	297	212	133	96	105	117	156

Table 4-49. Columbia River Below Bonneville Dam, Summer Average Monthly Flows (KCFS) and Percent of Years Within Optimum Recreation Range (150 – 250 KCFS)

SOS	June			July			August	
	Average Flows (Kcfs)	% Years Flows in Optimum Range	Average Flows (Kcfs)	Percent of Years Flows			Average Flows (Kcfs)	% Years Flows in Optimum Range
				> 250 kcfs	Optimum Range	< 150 kcfs		
1a	256	48	176	18	38	44	121	8
1b	262	46	182	22	56	22	121	10
2c	275	42	178	16	42	42	123	12
2d	290	42	202	22	58	20	120	10
4c	294	34	193	28	44	28	115	8
5b	274	42	175	16	40	44	119	8
5c	274	44	175	16	40	44	119	6
6b	274	44	175	16	40	44	119	8
6d	274	44	175	16	40	44	119	8
9a	305	26	240	30	70	0	168	100
9b	303	30	206	22	56	22	140	52
9c	275	42	208	26	52	22	132	28
PA	297	34	212	22	64	14	133	38

Under **SOS 1a and 1b**, flows peak during May with averages of about 280 kcfs (8000 cms) and then drop slightly in June to about 260 kcfs (7100 cms). By July, they fall significantly to about 180 kcfs (4900 cms) when they are within the preferred recreation range only 38 percent of years in SOS 1a as compared to 56 percent for SOS 1b. Under both SOSs, minimum annual flows are reached during August, September and October when they remain pretty stable at an average of around 121 kcfs (3200 cms). During August, flows are lower than the preferred minimum for recreation during approximately 90 percent of years.

Under **SOS 2c** flows are similar to those under SOS 1b and 1a, peaking during May. The only significant difference between these three alternatives is that flows are about 15 to 20 kcfs (400 to 570 cms) higher in June under SOS2c when they remain greater than the maximum preferred flow for recreation during 42 percent of years.

SOS 2d and 4c are similar to each other and vary from SOS 1a and 2c, in that peak flows are shifted

from May to June. June and July flows run approximately 20 to 25 kcfs (700 to 850 cms) higher. June flows would be higher than the preferred maximum during 42 and 34 percent of years for 2d and 4c, respectively, but would fall within the preferred range in July during 58 and 44 percent of years. In August, flows would be lower than the preferred minimum for recreation during 90 and 92 percent of years. The only significant difference between SOS 2d and 4c occurs in September when average flows are 111 and 95 kcfs, respectively. However, September flows for both fall well below the minimum for recreation nearly 100 percent of years.

Flows under **SOS 5b, 5c, 6b and 6d** would be similar to those under SOS 2c. The biggest difference between these alternatives and the other SOSs is that they substantially shift higher peaks to earlier in spring. Flows peak at an average of 291 kcfs (8000 cms) during May but drop off only slightly (16 kcfs; 450 cms) by June when they are greater than the maximum preferred flow for recreation about 56

percent of years. In July, a significant drop would result in flows within the preferred recreation range during only 40 percent of years, compared to the 44 percent of years that they would be below the preferred minimum of 150 kcfs. By August, flows fall to an average of 119 kcfs (3400 cms), well below the preferred minimum. Under SOS 5b and 6b, flows continue to fall substantially through September, when they average 91 and 97 kcfs (2600 and 2750 cms), respectively, compared to 112 and 108 kcfs (3200 and 3060 cms) under SOS 5c and 6d.

The predominant feature of SOS 9a is much higher flows during May through August than any of the other alternatives. June flows would be above the preferred maximum for recreation during about 70 percent of years. This effect would be balanced, however, by more consistent flows during the remainder of the summer recreation season. For example, during July, the average drops to 240 kcfs (6800 cms) and would be within the preferred range during 70 percent of years. During August, flows remain above the preferred minimum during 100 percent of years. By September, however, average monthly flows drop well below that month under SOS 1a or 2c.

SOS 9b would also feature higher flows during the summer recreation season than either SOS 1a or 2c. They would start out slightly higher than under SOS 9a in April, remaining relatively constant through June. By July and August, flows drop considerably lower than under SOS 9a. However, in comparison with the other SOSs, July and August flows would still be relatively good for recreation, remaining within the preferred range 56 and 52 percent of years during those months, respectively. September flows would also be well below those of SOS 1a or 2c.

SOS 9c would begin the summer recreation season with slightly lower flows in May than any of the other SOSs. Peak flows would be shifted to June and would remain relatively high in July. Flows would be reduced during the remainder of the summer and would be the lowest of any of the alternative SOSs during September.

The PA would feature higher flows during the summer recreation season than either SOS 1a or 2c. They

peak in June when they would be higher than the preferred maximum during 66 percent of years. Flows would remain relatively high in July and August. In comparison with the other SOSs, July and August flows would be relatively good for recreation, remaining within the preferred range 64 and 32 percent of years during those months, respectively.

4.2.20.2 Summary of Quantitative Impacts

No recreational impact assessment models were developed for the reach of the Columbia River below Bonneville Dam due to a lack of consistent visitation data and comparable quantitative information regarding the impacts of operations on visitor use.

4.2.20.3 Effects on Recreation Facilities/Activities

Extreme Low Flow Conditions. The natural low flow levels typically experienced at the end of most summer recreation seasons negatively impact developed recreation sites downstream of the Bonneville Dam. During 1994, average monthly flows released from Bonneville Dam for July, August, and September during were 152, 95 and 92 kcfs (4300, 2700 and 2600 cms), respectively. Average flows in those ranges would occur under most of the alternatives, particularly during low flow years, but would be particularly exacerbated under a number of different alternatives SOSs in which flows would be increased during spring and early summer to improve fish passage, resulting in less water available in upstream storage for release in later months. SOS 4c, 5b, 6b, 9a, 9b, 9c, and the PA would have particularly significant low flow impacts on the Columbia River below Bonneville Dam during late August, September and October. Under each of these alternatives, average September flows would be below 100 kcfs (2800 cms).

An example of the types of impacts that are experienced along the Columbia River below Bonneville Dam under low flow conditions occurred during 1994. Emergency operations for anadromous fish passage during the spring and early summer contributed to particularly low flows during late summer and early fall. Significant impacts were reported by the marina manager at the Port of Camas/Washougal (Ermis, 1994). The river staff gauge at the marina read a

minus 0.6 feet Columbia River Datum (CRD), the week before Labor Day, reportedly the first time the reading had ever been that low at that time. Shallow water moorage spaces along the shoreline became unusable. Of 350 boats normally moored at the marina, 10 boats went hard aground. Another 15 moorage spaces were landlocked, usually on weekends, by shallow water barriers between them and the river. The header dock (main walkways) along the shoreline were aground for most of the weekends in August and September. In at least six places, walkways and docks were misaligned, causing safety hazards. The boat ramp at the marina remained usable, but fewer lanes were available. Some boaters were forced to leave after unsuccessful launches and more boaters needed help in pulling their boats and trailers out of the mud after backing clear of the concrete launch ramp. Finally, there was a higher reported incidence of dock cleats being torn from the dock which the marina staff attributes to the possibility of shallower water magnifying the effect of wave frequency and amplitude. The Port of Camas/Washougal reported that these effects had a significant impact in the form of lost moorage revenues and increased staff time in dealing with problems.

Similar impacts occur at many other developed recreation sites along the river below Bonneville Dam. At Rooster Rock State Park in Oregon, late summer flows below 100,000 cfs leave the protected swimming beach, including jetties, floats and buoys completely out of the water. Swimmers are forced to go beyond the safe swimming area out into the channel. The boat ramps, boat basin, and moorage docks also become marginally usable during late summer and early fall periods of low water years. Similar impacts also occur across the river at Beacon Rock State Park in Washington.

Benson Lake State Park in Oregon features a very popular swimming beach in a seep lake that is connected to the Columbia River by culvert. As water levels in the river drop there is a corresponding drop in Benson Lake. Below a river elevation of approximately 2 to 4 feet, NGVD, there is a decline in the usability of this beach.

Low flow impacts also occur at undeveloped recreation areas. The sandy beaches and islands along the river from Bonneville Dam down to the Portland/Vancouver metropolitan area are very popular for boaters, campers, swimmers and other recreationists. These beaches tend to become larger and more accessible as water levels drop during the summer. However, during very low flow conditions, shoals and shallow water areas become so extensive that they become a boating hazard and access to the river is restricted. Side channels along the river that are popular for swimming, boating and waterskiing typically dry up during late summer.

Extreme High Flow Conditions. Extreme high flow conditions also impact recreation facilities below Bonneville Dam. For example, at Rooster Rock State Park, late spring and early summer flood events erode away beach sand at this popular swimming and sunbathing beach. High flow conditions related to the natural hydrograph of the Columbia river basin will occur under all of the alternative SOSs. However, those alternatives that tend to increase average peak flows or to shift peak flows from May until later in the peak recreation season in June will exacerbate high flow impacts on recreation. Those alternatives include SOS 2d, 4c, 9a, 9b, and the PA.

4.2.20.4 Effects on Fish Habitat and Fishing Success

Results from the SOR Anadromous and Resident Fish Work Groups indicate that none of the alternative SOSs under consideration would result in significant benefits or impacts to anadromous or resident fish species in the Columbia River below Bonneville Dam (see SOR appendices C and K, respectively). Consequently, no significant change in fish catching success or fishing is expected under any of the SOSs.

4.2.20.5 Effects on Wildlife Habitat/Hunting & Wildlife Viewing Success

Results from the SOR Wildlife Work Group indicate that none of the alternative SOSs under consideration would result in significant benefits or impacts to wildlife species along the Columbia River below Bonneville Dam (see SOR Appendix N). Conse-

quently, no significant change in hunting or wildlife viewing success is expected under any of the SOSs.

4.2.20.6 Effects on Recreational Safety and Physical Characteristics

Flows downstream from Bonneville Dam may affect the sandy shorelines of the river, and consequently patterns of use. These shorelines, particularly those around Government, Reed, Lemon and other islands, become very popular in late summer for boating, waterskiing, and camping. As water levels drop, the beaches in this area of the river become larger and more appealing. Eventually, however, as water levels become extremely low, sediments and large shoals restrict boat access to side channels and islands. Close to Bonneville Dam, flows of 250,000 cfs or more inundate natural beaches.

Low water levels may expose dangerous tree stumps, rocks and shoals that are hazardous to activities such as boating, waterskiing and windsurfing. The rocky shoreline of the Columbia River is dangerous under normal operating conditions; most recreationists are aware of the normal hazards.

High water velocities are an existing hazard in the Columbia River; the powerful hydrodynamics associated with operation of the dams can be particularly dangerous for small craft. Safety hazards occur for recreational navigation occur both above and below the dams during releases. One special existing flow-related hazard involves the anchoring of fishing boats in high flow areas, particularly in tailrace areas below Bonneville and the other dams. The river below Bonneville Dam is a very popular sturgeon fishing location. There have been numerous cases of capsized boats and drownings in that

area over recent years by boaters attempting to anchor with inadequate equipment or knowledge.

Oregon State Marine Board has recommended that safety zones and navigational barriers near the dams should be established and signed, and the possibility of providing sound warnings during releases should be considered.

4.2.20.7 Effects on Water Quality Parameters Influencing Recreation

There are no known significant water quality issues or concerns that affect or influence recreation at Lake Bonneville under any of the alternative SOS's.

4.2.20.8 Effects on Aesthetics

Operation of Bonneville Dam under any of the alternative SOS's would not have a significant effect on the scenic amenities of the region. In general, visual quality along Columbia River below Bonneville is increased when the river is at a higher level. Low water levels create a "bathtub ring" effect around the shoreline of the lakes; dried algae appears white against the dark basalt rocks of the region and large sand banks and shoals are exposed. This is a negative visual affect but to a certain extent is naturally occurring and is not particularly noticeable in comparison with the grand scale of other scenic amenities in the region. Also, since river levels fluctuate daily within the normal operational range, there is no long-term visual impact.

4.2.20.9 Mitigation Opportunities

No recreation mitigation actions are needed for the Columbia River below Bonneville Dam under any of the alternative SOS's.

CHAPTER 5

COMPARISON OF ALTERNATIVES

Chapter 4 presented a detailed description of expected recreation impacts for each alternative SOS on each individual project or river reach in the system. The objectives of Chapter 5 are to summarize those impacts, compare them across the range of alternatives, and present key conclusions and observations concerning potential tradeoffs. This chapter also addresses potential cumulative effects of the SOS alternatives, and discusses the short-term versus long-term aspects of the impact relationships. Finally, a preliminary mitigation plan for the Preferred Alternative is presented.

Because Chapter 5 is primarily a comparative analysis, the focus throughout the chapter is on the total recreation visitation estimates generated through model analysis of the SOS alternatives. These quantitative results are the central measure for the recreation analysis, and the primary means by which the impacts of the SOS alternatives can be uniformly compared. Chapter 4 included qualitative assessment of a number of other recreation attributes or issues. While these are not explicitly addressed in Chapter 5, these types of impacts are assumed to be the forces that ultimately translate into changes in visitation captured by the recreation impact assessment models (Chapter 3 presents a summary of the parameters included in the recreation impact assessment models, which are described in detail in Appendix J-1).

5.1 SYSTEM-WIDE VISITATION COMPARISON

The projected visitation effects for a given project or river reach can vary considerably in both magnitude and direction among the SOS alternatives. Because there are large differences in existing and projected visitation among the projects, the most significant comparison to be made involves total estimated visita-

tion for the entire system by SOS. These aggregate visitation figures indicate how the positive and negative changes at the individual projects balance out across the entire system, and represent the overall visitation impact of each SOS. The impacts also vary in magnitude and direction depending on hydrologic conditions in a given year.

Tables 5-1a, 5-1b and 5-1c summarize the results of the recreation impact assessment models for the entire Columbia basin system. They display estimated visitation by project and river reach for all of the alternative SOSs, under low, average, and high water conditions respectively. Figure 5-1 graphically displays the aggregate results for each SOS under low, average and high water conditions. The following discussions of estimated absolute visitation levels are based on these tables and figure.

5.1.1 Average Water Conditions

The recreation models estimated that system-wide recreational visitation for the no action alternative (SOS 2c) would average about 18 million recreation days under average water conditions over the 50-year period of record. The model analysis for the other SOSs resulted in system-wide use figures that differed to varying degrees. Most of the model results indicated lower visitation, although SOS 1, SOS 2d, and SOS 4c generated slightly higher visitation estimates compared to SOS 2c.

Among the SOSs, the highest estimate of average visitation is about 18.3 million for SOS 1b, or 262,000 recreation days more than the corresponding figure for SOS 2c. In other words, the model estimates suggest that, over the long term, operation according to SOS 1b would maximize recreational use of the system.

**Table 5–1a. Columbia Basin System Recreation Use Summary (Annual Recreation Days),
Average Water Year (50–Year Period of Record)**

SOS	HUNGRY HORSE DAM & LAKE	LIBBY DAM/ LAKE KOOCAN–USA	KOOTENAI RIVER	ALBENI FALLS DAM/ LAKE PEND OREILLE	COLUMBIA RIVER CANADA	GRAND COULEE DAM/ LAKE ROOSEVELT	CHIEF JOSEPH DAM/ RUFUS WOODS LAKE *	MID–COLUMBIA PUDs*	SNAKE RIVER HELLS CANYON*	DWORSHAK DAM & LAKE
1a	128,303	604,590	34,316	1,215,923	40,653	1,630,971	47,900	1,481,900	43,500	182,676
1b	125,670	603,795	34,912	1,216,917	41,520	1,637,181	47,900	1,481,900	43,500	185,625
2c	129,257	607,247	35,636	1,222,511	41,584	1,670,069	47,900	1,481,900	43,500	201,413
2d	128,574	605,012	35,062	1,222,511	37,172	1,662,812	47,900	1,481,900	43,500	159,655
4c	152,601	619,879	34,006	1,183,126	40,361	1,661,461	47,900	1,481,900	43,500	207,566
5b	126,532	602,870	34,989	1,217,773	41,506	1,665,931	47,900	1,481,900	43,500	213,711
5c	126,533	602,871	34,989	1,217,773	41,515	1,665,931	47,900	1,481,900	43,500	226,932
6b	126,533	602,871	34,989	1,217,773	41,506	1,665,931	47,900	1,481,900	43,500	198,854
6d	126,533	602,871	34,989	1,217,773	41,506	1,665,931	47,900	1,481,900	43,500	198,854
9a	91,036	546,186	14,270	1,001,121	40,723	1,257,182	47,900	1,481,900	43,500	180,361
9b	135,367	596,840	28,942	1,148,023	39,405	1,482,095	47,900	1,481,900	43,500	133,202
9c	152,580	618,419	33,881	1,187,905	40,199	1,570,658	47,900	1,481,900	43,500	183,092
PRE ALT	133,530	601,640	24,960	1,243,190	39,131	1,612,827	47,900	1,481,900	43,500	149,645

SOS	CLEAR–WATER RIVER	LOWER GRANITE DAM AND LAKE	LITTLE GOOSE DAM/ LAKE BRYAN	LWR. MONU–MENTAL DAM / LAKE WEST	ICE HARBOR DAM/ LAKE SACAJA–WEA	MENARY DAM/ LAKE WALLULA	JOHN DAY DAM/ LAKE UMATILLA	THE DALLES DAM/ LAKE CEILO*	BONNE–VILLE DAM/ LAKE BONNE–VILLE*	SYSTEM TOTAL
1a	109,147	1,653,879	244,797	140,009	525,658	2,747,500	2,860,009	1,411,300	3,164,600	18,267,631
1b	105,285	1,687,100	244,861	140,052	525,916	2,747,500	2,860,009	1,411,300	3,164,600	18,305,543
2c	128,224	1,662,699	240,402	137,598	514,730	2,747,500	2,555,389	1,411,300	3,164,600	18,043,459
2d	198,900	1,662,699	240,402	137,598	514,730	2,747,500	2,555,389	1,411,300	3,164,600	18,057,216
4c	147,346	1,649,772	239,610	136,673	507,022	2,747,500	2,760,038	1,411,300	3,164,600	18,236,161
5b	126,711	859,290	92,671	57,577	164,147	2,747,500	2,120,958	1,411,300	3,164,600	16,221,366
5c	141,589	652,290	71,143	44,052	127,270	2,747,500	2,120,958	1,411,300	3,164,600	15,970,546
6b	133,905	1,250,024	164,402	96,492	335,312	2,747,500	2,120,958	1,411,300	3,164,600	16,886,250
6d	133,905	1,250,024	240,402	137,598	514,730	2,747,500	2,120,958	1,411,300	3,164,600	17,182,774
9a	136,247	1,175,338	151,909	89,356	301,583	2,747,500	2,103,849	1,411,300	3,164,600	15,985,861
9b	135,271	1,618,319	233,075	133,421	494,838	2,747,500	2,555,389	1,411,300	3,164,600	17,630,887
9c	143,327	1,485,478	203,317	119,271	449,605	2,747,500	2,068,283	1,411,300	3,164,600	17,152,715
PRE ALT	151,296	1,673,460	242,655	138,766	519,212	2,747,500	1,502,081	1,411,300	3,164,600	16,929,093

* Quantitative recreation impact assessment models were not prepared for these projects/river reaches; visitation was assumed to be equal to average historic visitation (1987–1993)

**Table 5-1b. Columbia Basin System Recreation Use Summary (Annual Recreation Days),
Low Water Year (1941)**

SOS	HUNGRY HORSE DAM & LAKE	LIBBY DAM/ LAKE KOOCAN-USA	KOOTENAI RIVER	ALBENI FALLS DAM/ LAKE PEND OREILLE	COLUMBIA RIVER CANADA	GRAND COULEE DAM/ LAKE ROOSEVELT	CHIEF JOSEPH DAM/ RUFUS WOODS LAKE *	MID-COLUMBIA PUDs*	SNAKE RIVER HELLS CANYON*	DWORSHAK DAM & LAKE
1a	80,903	603,968	36,500	1,195,462	36,994	1,683,439	47,900	1,481,900	43,500	181,604
1b	59,080	593,359	41,996	1,195,462	35,726	1,719,220	47,900	1,481,900	43,500	145,697
2c	94,240	608,735	45,402	1,195,462	37,092	1,788,762	47,900	1,481,900	43,500	223,487
2d	92,848	602,979	46,639	1,195,462	34,419	1,604,149	47,900	1,481,900	43,500	137,712
4c	146,042	603,565	54,794	1,024,343	33,760	1,575,542	47,900	1,481,900	43,500	190,814
5b	80,903	603,968	36,500	1,195,462	37,520	1,788,762	47,900	1,481,900	43,500	168,373
5c	80,903	603,968	36,500	1,195,462	37,528	1,788,762	47,900	1,481,900	43,500	232,514
6b	80,903	603,968	36,500	1,195,462	37,520	1,788,762	47,900	1,481,900	43,500	184,648
6d	80,903	603,968	36,500	1,195,462	37,520	1,788,762	47,900	1,481,900	43,500	184,648
9a	36,712	476,616	7,541	847,301	37,246	1,127,004	47,900	1,481,900	43,500	110,637
9b	126,517	587,880	40,965	1,013,870	33,163	1,329,307	47,900	1,481,900	43,500	110,543
9c	146,042	618,443	54,794	1,155,626	34,241	1,507,837	47,900	1,481,900	43,500	166,616
PRE ALT	122,384	591,582	25,318	1,214,704	36,338	1,554,798	47,900	1,481,900	43,500	154,163

SOS	CLEAR-WATER RIVER	LOWER GRANITE DAM AND LAKE	LITTLE GOOSE DAM/ LAKE BRYAN	LWR. MONU-MENTAL DAM / LAKE WEST	ICE HARBOR DAM/ LAKE SACAJA-WEA	M McNARY DAM/ LAKE WALLULA	JOHN DAY DAM/ LAKE UMATILLA	THE DALLES DAM/ LAKE CELILO*	BONNE-VILLE DAM/ LAKE BONNE-VILLE*	SYSTEM TOTAL
1a	124,969	1,503,126	241,693	138,442	519,755	2,747,500	47,900	1,411,300	3,163,600	15,290,455
1b	159,583	1,671,616	241,693	138,442	519,755	2,747,500	47,900	1,411,300	3,163,600	15,465,229
2c	129,289	1,643,500	236,440	135,603	507,249	2,747,500	47,900	1,411,300	3,163,600	15,588,861
2d	112,769	1,643,500	236,440	135,603	507,249	2,747,500	47,900	1,411,300	3,163,600	15,293,370
4c	103,898	1,548,965	220,368	126,441	462,740	2,747,500	47,900	1,411,300	3,163,600	15,034,871
5b	111,363	858,143	92,436	57,458	163,687	2,747,500	47,900	1,411,300	3,163,600	14,138,175
5c	103,539	651,144	70,908	43,933	126,811	2,747,500	47,900	1,411,300	3,163,600	13,915,571
6b	178,242	1,240,964	162,553	95,550	331,691	2,747,500	47,900	1,411,300	3,163,600	14,880,362
6d	178,242	1,240,964	236,440	135,603	507,249	2,747,500	47,900	1,411,300	3,163,600	15,169,860
9a	119,213	1,122,451	142,677	84,238	279,073	2,747,500	47,900	1,411,300	3,163,600	13,334,309
9b	91,491	1,530,151	216,005	124,500	458,960	2,747,500	47,900	1,411,300	3,163,600	14,606,953
9c	100,026	1,471,296	200,496	117,810	443,601	2,747,500	47,900	1,411,300	3,163,600	14,960,427
PRE ALT	86,189	1,653,949	238,668	136,747	511,493	2,747,500	47,900	1,411,300	3,163,600	15,269,934

- * Quantitative recreation impact assessment models were not prepared for these projects/river reaches; visitation was assumed to be equal to average historic visitation (1987-1993)

**Table 5-1c. Columbia Basin System Recreation Use Summary (Annual Recreation Days),
High Water Year (1976)**

SOS	HUNGRY HORSE DAM & LAKE	LIBBY DAM/ LAKE KOOCAN-USA	KOOTENAI RIVER	ALBENI FALLS DAM/ LAKE PEND OREILLE	COLUMBIA RIVER CANADA	GRAND COULEE DAM/ LAKE ROOSEVELT	CHIEF JOSEPH DAM/ RUFUS WOODS LAKE *	MID-COLUMBIA PUDs*	SNAKE RIVER HELLS CANYON*	DWORSHAK DAM & LAKE
1a	143,913	607,318	35,064	1,253,451	32,665	1,682,318	47,900	1,481,900	43,500	191,260
1b	144,101	607,818	35,431	1,253,451	31,784	1,683,807	47,900	1,481,900	43,500	192,138
2c	148,416	615,899	33,343	1,253,451	32,266	1,685,820	47,900	1,481,900	43,500	213,106
2d	145,809	611,078	26,921	1,253,451	29,219	1,702,592	47,900	1,481,900	43,500	226,572
4c	154,917	629,248	30,394	1,221,005	31,036	1,644,998	47,900	1,481,900	43,500	222,212
5b	143,913	607,318	35,064	1,253,451	32,964	1,685,820	47,900	1,481,900	43,500	238,205
5c	143,913	607,318	35,064	1,253,451	32,951	1,685,820	47,900	1,481,900	43,500	229,017
6b	143,913	607,318	35,064	1,253,451	32,964	1,685,820	47,900	1,481,900	43,500	220,558
6d	143,913	607,318	35,064	1,253,451	32,964	1,685,820	47,900	1,481,900	43,500	220,558
9a	135,458	594,648	19,128	1,266,429	31,508	1,705,435	47,900	1,481,900	43,500	206,088
9b	141,869	610,476	31,495	1,244,277	28,998	1,649,332	47,900	1,481,900	43,500	155,485
9c	154,917	629,016	30,394	1,222,186	27,500	1,645,073	47,900	1,481,900	43,500	226,756
PRE ALT	148,279	617,068	32,820	1,265,964	28,275	1,705,435	47,900	1,481,900	43,500	184,230

SOS	CLEAR-WATER RIVER	LOWER GRANITE DAM AND LAKE	LITTLE GOOSE DAM/ LAKE BRYAN	LWR. MONU-MENTAL DAM / LAKE WEST	ICE HARBOR DAM/ LAKE SACAJA-WEA	MENARY DAM/ LAKE WALLULA	JOHN DAY DAM/ LAKE UMATILLA	THE DALLES DAM/ LAKE CELELO*	BONNEVILLE DAM/ LAKE BONNEVILLE*	SYSTEM TOTAL
1a	102,636	1,714,670	250,820	142,904	535,416	2,747,500	47,900	1,411,300	3,163,600	15,636,033
1b	102,299	1,714,670	250,820	142,904	535,416	2,747,500	47,900	1,411,300	3,163,600	15,638,240
2c	135,859	1,685,198	245,280	139,925	522,412	2,747,500	47,900	1,411,300	3,163,600	15,654,675
2d	134,892	1,685,198	245,280	139,925	522,412	2,747,500	47,900	1,411,300	3,163,600	15,666,950
4c	118,452	1,671,309	243,233	138,772	517,331	2,747,500	47,900	1,411,300	3,163,600	15,566,506
5b	106,457	861,114	93,072	57,766	164,753	2,747,500	47,900	1,411,300	3,163,600	14,223,497
5c	118,100	654,115	71,543	44,241	127,877	2,747,500	47,900	1,411,300	3,163,600	13,947,010
6b	111,428	1,264,949	167,649	98,036	340,383	2,747,500	47,900	1,411,300	3,163,600	14,905,132
6d	111,428	1,264,949	245,280	139,925	522,412	2,747,500	47,900	1,411,300	3,163,600	15,206,681
9a	100,830	1,269,465	168,534	98,510	342,223	2,747,500	47,900	1,411,300	3,163,600	14,881,854
9b	299,870	1,677,201	243,924	139,172	518,384	2,747,500	47,900	1,411,300	3,163,600	15,684,083
9c	105,741	1,498,768	206,416	120,655	453,333	2,747,500	47,900	1,411,300	3,163,600	15,264,355
PRE ALT	198,435	1,690,393	246,418	140,524	524,681	2,747,500	47,900	1,411,300	3,163,600	15,726,121

* Quantitative recreation impact assessment models were not prepared for these projects/river reaches; visitation was assumed to be equal to average historic visitation (1987-1993)

Figure 5-1. Estimated System-Wide Visitation for Alternative SOSS (Average, Low and High Water Years)

Visitation estimates for SOSs 1a, 2d, and 4c are also higher than the average figure for SOS 2c. The increases in visitation range from about 224,000 recreation days for SOS 1a to 13,757 recreation days for SOS 2d. Operating the system with any of these three SOSs would, according to the model, increase recreational visitation compared to SOS 2c.

At the other extreme, the minimum estimated visitation level is about 16 million recreation days for SOS 5c. The latter figure is about 2 million recreation days lower than the estimate for SOS 2c. The average-condition model results for SOSs 5b, 6b, 6d, 9a, 9b, 9c, and the PA are all also well below the SOS 2c estimate.

5.1.2 Low-Water Conditions

The year 1941 was chosen as the sample low-water year for evaluating recreation impacts because it was the last year of the worst critical 4-year period across the basin (which should not be mistaken as the driest year on record). The low-water visitation estimates for the various SOSs range from a high of about 15,888,900 recreation days for SOS 2c to a low of 13,334,300 with SOS 9a.

Across the range of SOSs, the visitation estimates for low-water conditions are generally very similar to those for average water conditions. Under SOSs 2c, 5c, 6b, and 6d, estimated visitation would actually increase very slightly across the system under low-water conditions compared to average-water conditions (in the range of 0.1 to 0.4 percent). On face value, increased visitation across the system under low water conditions may seem counterintuitive. Increases under some alternatives, however, can be attributed at least partially to the hydroregulation models used to determine the impacts of the alternative SOSs. In modeling the alternatives, forecasts of low-water conditions in the snowpack of the basin allowed hydroregulators to fill most of the storage reservoirs in the system in accordance with upper flood control rule curves, thereby filling the lakes earlier in the summer and, consequently, providing longer overall recreation seasons. Forecasting in actual conditions may not be as easy as under the

hypothetical scenarios presented by the SOSs; hydroregulators are less likely to minimize flood control storage by filling in accordance with the upper rule curves. Therefore, the benefits of these SOSs may not be realized under actual circumstances.

SOS 4c, 9a and 9b result in slight losses in estimated visitation when compared to the average water (2.7, 3.7 and 3.9 percent, respectively). The most significant variation in estimated visitation from average to low water conditions occurs under SOS 9a. This alternative is by far the worst for recreation in low water years. SOSs 9a and 9b include considerable flow augmentation for improving fish passage. As expected, use of water stored in the reservoirs for flow augmentation would have a more severe impact on recreational use of those projects during low-water years.

As a result of these variations in visitation with different water conditions, the rank ordering of the SOSs under low-water conditions changes little from the average results discussed previously. The SOS 1 options again rank at the top, followed relatively closely by the two SOS 2 options and SOS 4c. SOSs 6b, 6d, 9b, 9c, and PA form a fourth tier, and SOS 5 and 9a are grouped relatively closely at the bottom of the visitation estimates.

5.1.3 High-Water Conditions

The year 1976 was chosen as the sample high-water year for evaluating recreation impacts because it was the last year of the wettest four-year period across the basin (which should not be mistaken as the wettest year on record). As expected, estimated visitation during a wet year would be slightly to substantially higher for all alternatives than during average or low-water conditions. More water in the system ensures that the reservoirs can be filled earlier and maintained longer for recreation. Also, there is generally adequate water to maintain instream flows for recreation and other uses. The visitation estimates in this case range from a high of about 18.2 million for SOS 1a and 1b, to a low of approximately 16 million for SOS 5c. The estimates for high-water years for each SOS are larger than

the corresponding average figures. The differential ranges from 42,500 recreation days for SOS 4c to nearly 952,000 recreation days for SOS 9a.

SOS 9a and 9b are the only alternatives which show significant increases in visitation during high water years compared to average water. This is attributed to the fact that release of stored water for flow augmentation would have less impact on the recreation suitability of reservoirs during wet years.

5.2 VISITATION RELATIVE TO BASELINE CONDITIONS

The following discussion summarizes the general direction and magnitude of the projected visitation impacts for the respective SOS alternatives relative to baseline conditions. The two benchmarks or baseline conditions that are relevant points of reference for comparative analysis include:

- project-specific model estimates for SOS 1a (the "base case" alternative); and
- project-specific model estimates for SOS 2c (the No Action Alternative).

Tables 5-2a and 5-2b presents the results of the recreation impact assessment models in terms of the estimated numbers of visitors gained or lost at each project or river reach under all of the alternatives when compared with SOS 2c and SOS 1a, respectively. Tables 5-3 and 5-4 convert those changes in absolute visitation into a graphic representation of the percentage differences.

For each baseline condition, the respective SOSs are broadly characterized according to which areas of the system show significant differences in visitation in the comparison, and the direction (positive or negative) and general size of those differences. The following terms are used throughout this discussion to characterize the relative degree of change in visitation that could be expected under the alternative SOSs. The terminology corresponds to the symbols shown on Tables 5-3 and 5-4.

+25%	=	Major increase or benefit
+10 to +25%	=	Moderate increase or benefit
+5 to 10%	=	Minor increase or benefit
±5%	=	No significant impact
-5 to -10%	=	Minor decrease or negative impact
-10 to -25%	=	Moderate decrease or negative impact
-25 to -50%	=	Major decrease or negative impact
-50%	=	Severe decrease or negative impact

5.2.1 Comparison to SOS 1a

SOS 1a is considered the "base case" alternative for recreation analysis. It represents system operations as they existed from 1983 through the 1990-91 operating year, prior to river management actions undertaken in response to the ESA listings. Many recreationists in the region think of the operating pattern portrayed in SOS 1a as the "old" or "normal" way of operating the system. SOS 1a therefore serves as one baseline or a point of reference in comparing recreational visitation estimates developed for SOS 1b through SOS PA. Table 5-3 summarizes the recreation model estimates of visitation for each project or river reach by SOS, relative to SOS 1a while Figure 5-2 graphically illustrates those relative differences (based on average water conditions over the 50-year simulation period).

SOS 1b is very similar to SOS 1a in terms of water management actions. The visitation estimates are within 5 percent of the corresponding estimates for all projects with SOS 1a, and indicate little or no change in visitation levels. On a system-wide basis, the recreation impact assessment models indicate that SOS 1b is the best alternative for recreation, showing a very slight 0.2-percent increase over SOS 1a, the next best alternative.

Table 5–2a. Comparison of Recreational Impacts of Alternatives to SOS 2c, the “No Action” Alternative (Differences in Annual Recreation Days)

SOS	HUNGRY HORSE DAM & LAKE	LIBBY DAM/ LAKE KOOCANUSA	KOOTENAI RIVER	ALBENI FALLS DAM/ LAKE PEND OREILLE	COLUMBIA RIVER CANADA	GRAND COULEE DAM/ LAKE ROOSEVELT	CHIEF JOSEPH DAM/ RUFUS WOODS LAKE *	MID-COLUMBIA PUDs*	SNAKE RIVER HELLS CANYON*	DWORSHAK DAM & LAKE
1a	-954	-2657	-1320	-6588	-931	-39098	0	0	0	-18737
1b	-3587	-3452	-724	-5594	-64	-32888	0	0	0	-15788
2c	0	0	0	0	0	0	0	0	0	0
2d	-683	-2235	-574	0	-4412	-7257	0	0	0	-41758
4c	23344	12632	-1630	-39385	-1223	-8608	0	0	0	6153
5b	-2725	-4377	-647	-4738	-78	-4138	0	0	0	12298
5c	-2724	-4376	-647	-4738	-69	-4138	0	0	0	25519
6b	-2724	-4376	-647	-4738	-78	-4138	0	0	0	-2559
6d	-2724	-4376	-647	-4738	-78	-4138	0	0	0	-2559
9a	-38221	-61061	-21366	-221390	-861	-412887	0	0	0	-21052
9b	6110	-10407	-6694	-74488	-2179	-187974	0	0	0	-68211
9c	23323	11172	-1755	-34606	-1385	-99411	0	0	0	-18321
PRE ALT	4273	-5607	-10676	20679	-2453	-57242	0	0	0	-51768

SOS	CLEAR-WATER RIVER	LOWER GRANITE DAM AND LAKE	LITTLE GOOSE DAM/ LAKE BRYAN	LOWER MONUMENTAL DAM / LAKE WEST	ICE HARBOR DAM/ LAKE SACAJAWEA	M McNARY DAM/ LAKE WALLULA	JOHN DAY DAM/ LAKE UMATILLA	THE DALLES DAM/ LAKE CELILO*	BONNEVILLE DAM/ LAKE BONNEVILLE*	SYSTEM TOTAL
1a	-19077	-8820	4395	2411	10928	0	304620	0	0	224172
1b	-22939	24401	4459	2454	11186	0	304620	0	0	262084
2c	0	0	0	0	0	0	0	0	0	0
2d	70676	0	0	0	0	0	0	0	0	13757
4c	19122	-12927	-792	-925	-7708	0	204649	0	0	192702
5b	-1513	-803409	-147731	-80021	-350583	0	-434431	0	0	-1822093
5c	13365	-1010409	-169259	-93546	-387460	0	-434431	0	0	-2072913
6b	5681	-412675	-76000	-41106	-179418	0	-434431	0	0	-1157209
6d	5681	-412675	0	0	0	0	-434431	0	0	-860685
9a	8023	-487361	-88493	-48242	-213147	0	-451540	0	0	-2057598
9b	7047	-44380	-7327	-4177	-19892	0	0	0	0	-412572
9c	15103	-177221	-37085	-18327	-65125	0	-487106	0	0	-890744
PRE ALT	23072	10761	2253	1168	4482	0	-1053308	0	0	-1114366

* Quantitative recreation impact assessment models were not prepared for these projects/river reaches; visitation was assumed to be equal to average historic visitation (1987–1993)

Table 5–2b. Comparison of Recreational Impacts of Alternatives to SOS 1a, the “Base Case” Alternative (Differences in Annual Recreation Days)

SOS	HUNGRY HORSE DAM & LAKE	LIBBY DAM/ LAKE KOOCANUSA	KOOTENAI RIVER	ALBENI FALLS DAM/ LAKE PEND OREILLE	COLUMBIA RIVER CANADA	GRAND COULEE DAM/ LAKE ROOSEVELT	CHIEF JOSEPH DAM/ RUFUS WOODS LAKE *	MID-COLUMBIA PUDs*	SNAKE RIVER HELLS CANYON*	DWORSHAK DAM & LAKE
1a	0	0	0	0	0	0	0	0	0	0
1b	-2633	-795	596	994	867	6210	0	0	0	2949
2c	954	2657	1320	6588	931	39098	0	0	0	18737
2d	271	422	746	6588	-3481	31841	0	0	0	-23021
4c	24298	15289	-310	-32797	-292	30490	0	0	0	24890
5b	-1771	-1720	673	1850	853	34960	0	0	0	31035
5c	-1770	-1719	673	1850	862	34960	0	0	0	44256
6b	-1770	-1719	673	1850	853	34960	0	0	0	16178
6d	-1770	-1719	673	1850	853	34960	0	0	0	16178
9a	-37267	-58404	-20046	-214802	70	-373789	0	0	0	-2315
9b	7064	-7750	-5374	-67900	-1248	-148876	0	0	0	-49474
9c	24277	13829	-435	-28018	-454	-60313	0	0	0	416
PRE ALT	5227	-2950	-9356	27267	-1522	-18144	0	0	0	-33031
SOS	CLEAR-WATER RIVER	LOWER GRANITE DAM AND LAKE	LITTLE GOOSE DAM/ LAKE BRYAN	LOWER MONUMENTAL DAM / LAKE WEST	ICE HARBOR DAM/ LAKE SACAJAWEA	M McNARY DAM/ LAKE WALLULA	JOHN DAY DAM/ LAKE UMATILLA	THE DALLES DAM/ LAKE CELILO*	BONNEVILLE DAM/ LAKE BONNEVILLE*	SYSTEM TOTAL
1a	0	0	0	0	0	0	0	0	0	0
1b	-3862	33221	64	43	258	0	0	0	0	37912
2c	19077	8820	-4395	-2411	-10928	0	-304620	0	0	-224172
2d	89753	8820	-4395	-2411	-10928	0	-304620	0	0	-210415
4c	38199	-4107	-5187	-3336	-18636	0	-99971	0	0	-31470
5b	17564	-794589	-152126	-82432	-361511	0	-739051	0	0	-2046265
5c	32442	-1001589	-173654	-95957	-398388	0	-739051	0	0	-2297085
6b	24758	-403855	-80395	-43517	-190346	0	-739051	0	0	-1381381
6d	24758	-403855	-4395	-2411	-10928	0	-739051	0	0	-1084857
9a	27100	-478541	-92888	-50653	-224075	0	-756160	0	0	-2281770
9b	26124	-35560	-11722	-6588	-30820	0	-304620	0	0	-636744
9c	34180	-168401	-41480	-20738	-76053	0	-791726	0	0	-1114916
PRE ALT	42149	19581	-2142	-1243	-6446	0	-1357928	0	0	-1338538

* Quantitative recreation impact assessment models were not prepared for these projects/river reaches; visitation was assumed to be equal to average historic visitation (1987–1993)

The model results indicate that visitation with SOS 2c and SOS 2d would be about the same as SOS 1a for most of the projects, with the exception of moderate negative impacts to the recreational suitability of the John Day Project due to spring–summer operation of the pool several feet below full. Visitation at the John Day Project would be reduced by approximately 11 percent. Average visitation at Dworshak would be higher with SOS 2c, compared to SOS 1a, as would visitation at the Clearwater River with SOSs 2c and 2d. There would be a slight decrease in system–wide visitation (approximately 1% under both SOS 2c and SOS 2d) compared to SOS 1a.

SOS 4c, the stable storage alternative, was designed primarily to provide more stable pool elevations at the storage reservoirs to promote recreation, wildlife and resident fish resources. Visitation estimates for SOS 4c at most storage reservoirs range from insignificant change to minor increases compared to SOS 1a. The greatest positive effect on visitation would occur at Hungry Horse, Dworshak, and the Clearwater River, while Grand Coulee and Libby reservoirs would have slight increases.

Conversely, with SOS 4c the visitation estimates for the four lower Snake River projects, the lower Columbia River projects, Albeni Falls, and the Kootenai River are slightly lower than under SOS 1a, offsetting recreational gains at the storage reservoirs. As a result, visitation system–wide with SOS 4c would be slightly reduced (1.1 percent) compared to SOS 1a.

SOS 5b and 5c, the natural river alternatives, and SOS 6b and 6d, fixed drawdown alternatives, would all primarily affect the recreational suitability of the lower Snake run–of–river projects. Visitation estimates for Lower Granite, Little Goose, Lower Monumental, and Ice Harbor with SOS 5 would be severely reduced (by 60 percent, 71 percent, 68 percent, and 76 percent, respectively) compared to SOS 1a. SOS 5 also includes a drawdown action at John Day, with an estimated corresponding decrease in visitation of approximately 25 percent. Visitation at Dworshak and the Clearwater River would be higher with SOS 5 than with SOS 1a. This increase

is attributable to earlier filling and higher probability for refill during the recreation season under SOS 5 compared to SOS 1a. System–wide visitation estimates for SOS 5b and 5c are considerably lower overall (12.6 and 14.4 percent, respectively) than the visitation figures of SOS 1a. In fact, SOS 5c would be the worst alternative for recreation across the system compared to SOS 1a.

The model results for SOS 6 follow a pattern similar to SOS 5, but decreases in visitation would not be as severe. They indicate large decreases in use, compared to SOS 1a, for the four lower Snake River projects and John Day Project with SOS 6b and 6d. These decreases would be limited to John Day, Lower Granite, Little Goose (only a slight decrease with 6d), and Lower Monumental. Dworshak visitation would experience minor increases in visitation for both SOS 6 options. Visitation at the Clearwater River is expected to increase 23 percent with both options. As with SOS 5, SOS 6 would have no significant effects on the recreational suitability of any of the other projects or river reaches in the system other than the projects mentioned above, compared to SOS 1a. In comparison with SOS 1a, both SOS 6 options would result in a minor decrease in recreational use across the system. SOS 6b would result in a 5.8 percent decrease and 6d would result in a 4.3 percent decrease in visitation.

SOS 9a would have a moderate negative effect on visitation across the system, and would have the second greatest decrease in visitation of all the SOSs compared to SOS 1a. Projects where there would be a major (25 to 50 percent) or severe (more than 50 percent) reduction in visitation include the four lower Snake projects, John Day, and the Kootenai River. Visitation at Grand Coulee and Albeni Falls would be moderately reduced.

SOS 9b and 9c would cause moderate decreases in visitation across the system. SOS 9b would result in significant to moderate reductions in visitation at John Day, Dworshak, and the Kootenai River as well as minor reductions at Ice Harbor, Grand Coulee, Albeni Falls, and Libby. SOS 9c would have significant impacts on John Day, moderate to minor impacts on the lower Snake projects, and neutral

impacts on the other projects. Because of the significant reduction in visitation at John Day, the system-wide reduction in visitation would be minor compared to SOS 1a.

The Preferred Alternative would have a minor negative impact on visitation system-wide compared to SOS 1a. Projects that would experience visitation declines include John Day and Grand

Coulee, which would be severely affected; Dworshak; the Kootenai River; Libby; and Albeni Falls. John Day would be the only project that would be very severely affected. SOS PA would have the greatest negative impact on John Day of all the SOSs. By drafting John Day to MOP year-round except during floods, visitation would be reduced about 52 percent.

Table 5-3. Relative Change in Visitor Use of Alternative SOSs Compared Against SOS 1a (Base Case)

PROJECT/ RIVER REACH	1a	1b	2c	2d	4c	5b	5c	6b	6d	9a	9b	9c	PA
Bonneville	0	0	0	0	0	0	0	0	0	0	0	0	0
The Dalles	0	0	0	0	0	0	0	0	0	0	0	0	0
John Day	0	0	--	--	0	▲	▲	▲	▲	▲	--	▲	X
McNary	0	0	0	0	0	0	0	0	0	0	0	0	0
Ice Harbor	0	0	0	0	0	X	X	▲	0	▲	-	--	0
Lower Monumental	0	0	+	0	0	X	X	▲	▲	▲	0	-	0
Little Goose	0	0	0	0	0	X	X	▲	0	▲	0	--	0
Lower Granite	0	0	0	0	0	▲	X	--	--	▲	0	--	0
Dworshak	0	0	++	-	++	++	++	+	+	0	▲	0	--
Clearwater River	0	0	++	+++	++	++	++	++	++	++	++	++	++
Chief Joseph	0	0	0	0	0	0	0	0	0	0	0	0	0
Grand Coulee	0	0	0	0	0	0	0	0	0	--	-	0	0
Columbia R., Canada	0	0	0	--	-	0	0	0	0	0	-	-	-
Albeni Falls	0	0	0	0	0	0	0	0	0	--	-	0	0
Libby	0	0	0	0	0	0	0	0	0	-	0	0	0
Kootenai River	0	0	0	0	0	0	0	0	0	X	--	0	▲
Hungry Horse	0	0	0	++	0	0	0	0	0	-	0	+	0
System-Wide	0	0	0	0	0	--	--	-	-	--	0	-	-

LEGEND: % change in total visitation in comparison with SOS 1a

+++ = > +26%, major increase or benefit
 ++ = > +25 to +11%, moderate increase or benefit
 + = > +10% to +6%, minor increase or benefit
 0 = +5%, no significant impact
 - = > -6% to -10%, minor decrease or loss
 -- = > -11% to -25%, moderate decrease or loss
 ▲ = > -26% to -50%, major decrease or loss
 X = > -51%, severe decrease or loss

Figure 5-2. System-Wide Recreation Use; Estimated Change in use Under Alternatives Compared to SOS 1a

Table 5-4. Relative Change in Visitor Use of Alternative SOSs Compared Against SOS 2c (No Action)

PROJECT/ RIVER REACH	1a	1b	2c	2d	4c	5b	5c	6b	6d	9a	9b	9c	PA
Bonneville	0	0	0	0	0	0	0	0	0	0	0	0	0
The Dalles	0	0	0	0	0	0	0	0	0	0	0	0	0
John Day	++	++	0	0	+	---	---	---	---	---	0	---	0
McNary	0	0	0	0	0	0	0	0	0	0	0	0	0
Ice Harbor	0	0	0	0	0	X	X	▲	0	▲	0	---	0
Lower Monumental	0	0	0	0	0	X	X	▲	0	▲	0	---	0
Little Goose	0	0	0	0	0	X	X	▲	0	▲	0	---	0
Lower Granite	0	0	0	0	0	▲	X	---	---	▲	0	-	0
Dworshak	-	-	0	+++	++	++	++	++	+	0	▲	-	▲
Clearwater River	---	---	0	0	+++	++	++	++	0	+	+	++	++
Chief Joseph	0	0	0	0	0	0	0	0	0	0	0	0	0
Grand Coulee	0	0	0	0	0	0	0	0	0	---	---	-	0
Columbia R., Canada	0	0	0	---	0	0	0	0	0	0	-	-	-
Albeni Falls	0	0	0	0	0	0	0	0	0	0	-	0	0
Libby	0	0	0	0	0	0	0	0	0	0	0	0	0
Kootenai River	0	0	0	0	0	0	0	0	0	X	---	0	---
Hungry Horse	0	0	0	++	0	0	0	0	0	-	0	+	0
System-Wide	0	0	0	0	0	---	---	-	-	---	0	-	-

LEGEND: % change in total visitation in comparison with SOS 2c

+++ = > +26%, major increase or benefit
 ++ = > +25 to +11%, moderate increase or benefit
 + = > +10% to +6%, low increase or benefit
 0 = + 5%, no significant impact
 - = > -6% to -10%, low decrease or loss
 --- = > -11% to -25%, moderate decrease or loss
 ▲ = > -26% to -50%, major decrease or loss
 X = > -51%, severe decrease or loss

Figure 5-3. System-Wide Recreation Use; Estimated Change in Use Under Alternatives Compared to SOS 2c

5.2.2 Comparison to SOS 2c

As of the writing of this EIS, the actions included in SOS 2c represent the most likely future operation of the system in the absence of a new strategy developed through the SOR. Therefore, SOS 2c is considered the No Action Alternative. Because operation of the system differs somewhat under SOS 2c compared to SOS 1a, it provides a somewhat different baseline condition with which to compare impacts. A summary of visitation estimates by project for all other SOSs relative to SOS 2c is presented in Table 5-4. As with the comparison with SOS 1a, Table 5-4 is based on average conditions over the 50-year simulation period. Figure 5-3 graphically illustrates those relative differences (based on average water conditions over the 50-year simulation period).

In general, the patterns described in Section 5.2.1 for the comparison to SOS 1a also apply here for the comparison to SOS 2c. For most projects in the system, SOS 2c provides better recreation conditions than does SOS 1a. The opposite is true for three of the lower Snake River run-of-river projects (Little Goose, Lower Monumental, and Ice Harbor) and John Day, all of which are operated somewhat below full pool during part of the spring and the summer for fish. Under SOS 2c, the three lower Snake River projects show minor decreases in visitation, while John Day experiences moderate decreases, compared to SOS 1a.

SOS 2c shows a slight decline in visitation across the system (-1.2 percent) compared to SOS 1a. Because of this difference, those alternative SOSs having a negative impact on estimated recreation visitation system-wide would be slightly to moderately more severe in comparison with SOS 1a than SOS 2c. For example, since Little Goose and John Day Reservoirs are operated at minimum operating pool and minimum irrigation pool during the summer months under SOS 2c, a comparison with other SOSs featuring that operation would show no significant change in visitation. Alternatively, those SOSs having a positive impact on recreation visitation system-wide would be slightly greater compared to SOS 2c than SOS 1a. Again, since Little Goose and

John Day Reservoirs are operated at low-pool elevations during the summer months under SOS 2c, a comparison with other SOSs featuring full pool for those lakes would show increases in visitation.

SOS 2d would have virtually the same effect on visitation system-wide as SOS 2c. The primary exceptions would be at Dworshak, where visitation with SOS 2d would be moderately less than 2c. SOS 2c would increase visitation at the Clearwater River, but not to the extent that the model indicates. A limitation in the model produced an estimate for the Clearwater River that was too high (see Section 4.2.13.1). System-wide, SOS 2d would produce a minor, almost imperceptible, increase in visitation compared to SOS 2c.

Analysis of SOS 4c indicated little change in visitation estimates for most projects. Visitation estimates for Hungry Horse and John Day are moderately and slightly higher than SOS 2c, respectively. Visitation at Lake Pend Oreille and the lower Snake projects would be slightly lower than SOS 2c. Overall, SOS 4c would result in a system-wide increase in visitation of about one percent compared to SOS 2c.

The observations made in Section 5.2.1 for SOSs 5b and 5c, and 6b and 6d also apply to the comparison of these alternatives with SOS 2c. SOSs 5 and 6 generally result in significantly lower visitation estimates for the lower Snake River projects and John Day, and higher figures for Dworshak and the Clearwater River. Visitation at the rest of the projects changes very little. SOS 6d has less of a negative effect on visitation compared to SOS 2c than SOS 5b, 5c or 6b, because only Lower Granite and John Day are drawn down during the spring and summer. Other projects would be insignificantly affected. Visitation would be reduced moderately at John Day and severely at Lower Granite. System-wide, visitation would be reduced 11.2 percent with SOS 5b, 13.0 percent with SOS 5c, 6.9 percent with SOS 6b, and 5.0 percent with SOS 6d.

SOS 9a would result in severe reductions in visitation at the lower Snake projects and moderate to minor impacts on Dworshak, Grand Coulee, Hungry Horse and the Kootenai River. System-wide,

visitation would be moderately reduced compared to SOS 2c. SOS 9b would cause insignificant changes to system-wide visitation. Visitation at Dworshak would be severely reduced, while visitation at Grand Coulee and Albeni Falls would experience moderate to minor decreases. SOS 9c would affect visitation similar to, but less severely than SOS 9a. John Day would continue to have visitation severely reduced. The lower Snake projects would experience moderate to minor drops in visitation. Overall, visitation would be decreased moderately compared to SOS 2c.

The impact of the PA on visitation compared to SOS 2c is virtually the same as the SOS PA impact on visitation compared to SOS 1a. The primary reason SOS PA would result in a moderate reduction in system-wide visitation is that visitation at John Day would be severely reduced because of the year-round operation near MOP.

5.3 KEY TRADEOFF RELATIONSHIPS

One of the important objectives for Chapter 5 is to highlight significant aspects of the impact results that may merit consideration in the overall evaluation of the SOSs. The analytical results discussed in Sections 5.1 and 5.2 support a number of general conclusions or observations that lend perspective to the assessment of recreation impacts. They generally help to identify the tradeoffs in recreational outputs that would implicitly be involved in favoring one SOS over another, or the potential significance of recreation in the overall evaluation.

5.3.1 Sensitivity of Aggregate Visitation

On a system-wide basis, recreation demand does not appear too sensitive to changes in operations under the alternative SOSs. This sensitivity is moderated by high levels of visitation to projects in the system in which recreation suitability will not be strongly affected by the alternative SOSs. For example, Bonneville, The Dalles and Chief Joseph Projects all have the same estimated visitation under all alternatives.

The relative differences in projected visitation among the SOSs compared to the No Action Alter-

native (SOS 2c) are not great. The maximum percentage difference in recreation days is approximately 13 percent, reflecting the comparison of average conditions for SOSs 1a and 5c. Accounting for the slight gain in expected visitation from SOS 2c to SOS 1b, the visitation estimates range from about 1.4 percent above to 13.0 percent below the result for SOS 2c. In absolute terms, the difference between the maximum and minimum estimates is approximately 2,072,913 recreation days, or about 13 percent of the expected total for SOS 2c. That represents a rather narrow band of potential outcomes, and suggests that aggregate system-wide visitation is not highly sensitive to change with the types of operational measures included in the SOS alternatives.

Aside from the "old" pattern of operations represented by SOSs 1a and 1b, SOS 4c would have the most beneficial effect on recreation compared to SOS 2c. This option would essentially allow system-wide visitation to increase by slightly more than 1 percent over the baseline visitation level that was modeled for SOS 2c. SOS 4c reflects a specific attempt to benefit recreation, along with resident fish, wildlife, and cultural resources, by operating with more stable pool levels in the storage reservoirs. The fact that estimated visitation with SOS 4c is only slightly higher than the baseline condition suggests that the ability to increase system-wide visitation through operational measures is limited. In fact, other variables besides pool elevation and river flows manifested by system operations have a stronger influence on recreation use of the system's reservoirs.

5.3.2 Key Factors in Determining Visitation Levels

The aggregate system-wide visitation estimates reported in Figure 5-2 reflect a varying mix of positive and negative effects on visitation among the SOS alternatives when compared to the No Action Alternative (SOS 2c). The following discussion attempts to highlight the key tradeoffs among the different portions of the system that are responsible for the net system results indicated in the table.

The system-wide visitation patterns, particularly the relatively narrow range across the SOS alternatives, are largely determined by the distribution of existing use and potential operational measures. As a group, the four lower Columbia River projects comprise the most heavily used portion of the system. The operation of three of these projects (Bonneville, The Dalles, and McNary) would remain the same in all SOSs, while significant operational changes would occur at John Day only with SOSs 5, 6, 9a, 9c, and SOS PA. Consequently, a large portion of the system-wide visitation total would be unaffected from one SOS to another. Similarly, operations would change little or not at all at Albeni Falls under all but one of the SOSs, and little at the lower Snake River projects under approximately half of the SOSs. The net result is that a relatively small portion of system-wide visitation is subject to change due to differing operations.

SOS 4c would result in high-pool elevations at storage reservoirs during the prime summer recreation season. As a result, visitation at these reservoirs would be higher compared to SOS 2c. Visitation numbers at some storage reservoirs are higher than the baseline condition with some SOSs, yet lower with other SOSs. These differences in visitation at different storage and run-of-river projects tend to cancel out gains at specific storage reservoirs.

For example, visitation at Dworshak would be highest, relative to SOS 2c, with SOS 5c. Despite these increases at Dworshak, there would be a significant system-wide decrease in recreational visitation because of impacts of drawdowns on the more heavily used lower Snake River projects and John Day. Visitation during average water years at Dworshak with SOS 2c is estimated at about 201,400 recreation days. By contrast, Lower Granite alone receives 1,662,700 recreation days with SOS 2c. With SOSs 4c, 5b, and 5c, the comparatively small increases in visitation at Dworshak would be more than offset by decreases at the lower Snake River projects and John Day, resulting in a net system-wide loss in recreation days. Similar tradeoffs between upstream and downstream projects also apply to other alternatives.

5.3.3 Project or Resource-Specific Observations

Aside from system-wide patterns, there are some other tendencies in the impact results that apply more to specific projects or types of resources. For example, SOSs 5, 6, and 9c would have moderate to severe adverse effects on visitation at one or more run-of-river projects, but would have neutral effects on the storage reservoirs. The model results also indicate there can be localized tradeoffs near the storage reservoirs. Operations that would improve recreational conditions and thus visitation at storage reservoirs could also affect visitation at downstream river reaches. At Libby, for example, holding water during the summer would maintain high-pool elevations but result in low outflows into the Kootenai River. As a result, recreation at the reservoir would be benefited, but visitation along the Kootenai River would be diminished due to lower flows. At Dworshak, on the other hand, holding water in the summer would actually help recreation on the Clearwater River. Releases from late fall through early spring would be particularly beneficial to steelhead anglers, who are the most numerous recreationists using the Clearwater. Some SOSs would increase visitation at certain storage reservoirs compared to SOS 2c, but would reduce visitation at others. For example, SOS 9c would increase visitation at Hungry Horse and Libby by a total of 34,500 recreation days relative to SOS 2c. However, visitation at Dworshak would decrease almost 18,300, while visitation at Grand Coulee would decrease by about 99,400.

Several SOSs were devised to protect or enhance certain resource values, or to concentrate operations at certain projects. SOS 4c was intended to promote recreation, resident fish, and wildlife needs at the storage projects. By attempting to maintain consistent and relatively high-pool elevations at storage reservoirs, it was believed that recreationists would find projects more attractive and usable. Recreational visitation at most storage reservoirs with most of the SOS 4c options would increase or stay essentially the same as with SOS 2c. At Albeni Falls, however, visitation estimates for SOS 4c indicate an insignificant decrease in visitation compared to

SOS 2c. The slight decrease in visitation at Albeni Falls would be attributed to late summer pool elevations that would be 2.5 feet below full pool.

Although there is not a great deal of difference between the SOSs in terms of impacts to system-wide recreation, Tables 5-2a, 5-2b and 5-3 indicate there would be significant impacts on visitation at specific projects. Changes in visitation at projects that receive the most use would affect the greatest number of recreationists, and have the greatest impacts system-wide. Sizable relative changes at projects such as the lower Snake River projects, John Day, or Grand Coulee would affect many more people than an equivalent change at a project that receives comparatively little visitation, such as Hungry Horse. Nevertheless, considerations such as the local economic significance of a recreation resource at projects that receive relatively small numbers of visitors from a system-wide perspective must be factored into evaluations.

5.4 MITIGATION

5.4.1 General Types of Recreation Mitigation

Mitigation would include any action that could be implemented by the agencies sponsoring SOR to help avoid or minimize impacts to recreational resources resulting from changes in operation of the system considered under SOR. The following general types or categories of recreation mitigation concepts could be applied to any of the individual projects or to the system as a whole, depending upon the location and severity of impacts.

- 1) Improve Public Information
 - a. provide better information about operations (i.e., provide a "flow phone")
 - b. plan and identify annual operations in advance
 - c. promote alternative activities (not impacted by operations)
- 2) Operational Modifications
 - a. improve/stabilize short-term (daily/weekly) operations

- b. increased sensitivity by operators/hydroregulators to recreational impacts

3) Structural Modifications

- a. modify facilities (in place) for wider range of operations (i.e., extend boat ramps)
- b. replace facilities
 - on site
 - elsewhere on project

4) Relocation/Replacement

- a. develop new facilities at alternative water resource projects in the region
- b. acquire and develop alternative facilities off-project

5) Construct additional storage reservoirs

These mitigation concepts are listed in increasing order of cost and difficulty to implement. Improvement of public information and operational refinements are relatively easy to implement and probably ought to be considered under any of the alternative SOSs.

Structural modification of facilities ranges in cost and difficulty to implement depending upon the operational ranges being considered. As long as the reservoirs are maintained within their "normal" operational ranges, structural modifications of recreation facilities can probably be accommodated at a relatively low cost. Several agencies are currently expanding their facilities to make them more usable over a wider range of fluctuations. For example, the National Park Service recently extended 10 boat ramps at Lake Roosevelt.

For more severe drawdown ranges, the degree of difficulty and costs for structural modification of facilities increases dramatically. For example, the Walla Walla District Corps estimated that the cost of modifying recreation facilities on the Lower Granite and Ice Harbor pools under the drawdown alternatives considered in the 1992 OA/EIS was in the neighborhood of \$15 million.

Ultimately, a point will be reached at the reservoirs where drawdown is so severe that it is infeasible to modify recreational facilities onsite to mitigate for impacts. This point most clearly occurs where it becomes physically impossible to modify facilities to accommodate the range of fluctuations considered. However, a point can also be reached where drawdown diminishes aesthetics and other parameters of recreational suitability to a point where modification of facilities at that project is not a reasonable mitigation option.

When drawdowns result in severe impacts, additional mitigation measures such as relocation or replacement of facilities in-kind elsewhere in the region may be considered. For example, some of alternatives under consideration under SOR may result in severe to very severe decreases in visitation at the Lower Granite and John Day Reservoirs during the summer recreation season. Under those alternatives it may be necessary for Federal agencies to consider mitigating for the loss of recreational opportunities by constructing a new recreation facilities elsewhere in the region.

5.4.2 Recommended Recreation Mitigation Plan for the Preferred Alternative

Following is a description of the recommended recreation mitigation actions under the preferred alternative for each reservoir or river reach in the system.

5.4.2.1 Libby Project/Lake Koocanusa

The PA would result in drawdowns at the Libby Project in excess of those experienced under the no-action alternative. These drawdowns would affect facilities around the lake to varying degrees. The potential exists at Libby to modify many of the existing recreational facilities to make them usable over a wider operational range than they currently are so that they would be operational with SOS PA. However, because of physical and cost constraints, it would not be possible to modify all of the existing sites, particularly facilities at the upper end of the

project. These facilities are dewatered when drawdowns exceed 20 feet.

Mitigation efforts at Libby should focus on improving the use of swimming beaches at Rexford Beach and the McGillivray Recreation Area. Extending or relocating the developed swimming beaches to make them usable at pool elevations as low as 20 feet below full pool elevation would make swimming safer and would allow both beaches to remain open longer. Extending the beaches would allow use of them for an average of 4 months under the PA. Alternative mitigation measures include developing swimming areas at other nearby lakes or building a swimming pool at a local community.

Revegetation of the varial zone around the upper end of the reservoir and on the flats around Rexford and Eureka would improve aesthetic quality and fish and wildlife habitat conditions, and would reduce dust problems.

5.4.2.2 Kootenai River Below Libby Dam

SOS PA would result in higher summer flows (except in July) on the Kootenai River below Libby Dam. The higher flows would affect recreational access to the river. To improve boating access, several undeveloped Corps sites just downstream from Libby Dam, such as Blackwell Flats, could be developed to provide access at high flows. Fishing piers that extend into the river channel could be constructed to allow safer access to bank anglers during periods of high flow.

5.4.2.3 Upper Columbia River in Canada

The extension of the concrete boat ramp at Indian Eddy would increase the use of this important facility at low flows. In conjunction with the ramp extension, the mooring docks could also be reconfigured and extended to improve the use of this facility. Dredging some large river cobbles at the entrance of Indian Eddy would improve general access to the facility at low flows.

Constructing mooring docks at the Beaver Creek boat launch would improve the use of this facility at high river flows. The mooring docks would improve

the ease of loading and unloading boats during high flows when river currents complicate the use of this facility.

The Canada Customs dock at Trail was destroyed by the high flows of 1991, but could be rebuilt in a manner that allows it to accommodate high flows. Low flows do not pose a problem for a dock at this site.

In order to reduce the impacts of the SOSs on fish habitat and, consequently, on fishing success, certain mitigation opportunities may be undertaken. Given that the flow alternatives would diminish mainstem spawning, incubation, emergence and rearing habitat, these effects may be partially offset by improving like habitat on the tributary streams downstream of the Keenleyside and Brilliant Dams. The construction of regulated flow spawning channels using water from the major tributary streams should be undertaken. Opportunities to construct these channels exist at Murphy, Blueberry, and Beaver Creeks. To reduce the dewatering of fry at the Norns Creek fan, this structure could be reconfigured to reduce the pooling of water and fry that occurs as water levels drop. The improvement of fish habitat and the reduction of blockages to upstream migration in the other tributary streams should also be pursued.

While dewatering mainstem fish habitat below the confluence of the Columbia and Kootenai Rivers does not appear to occur in average and high-water years, the stabilization of daily flows from upstream dams to limit rapid fluctuations must also occur. Given the heavy use of this habitat by Lake Roosevelt fish stocks, the implications of these flows and this mitigation package would be felt downstream of this stretch of the Columbia River in Washington State.

5.4.2.4 Hungry Horse Reservoir

The PA would provide pool elevations at the reservoir that would be as high or higher than SOS 2c. Recreation facilities would therefore remain usable for longer periods of the summer than with SOS 2c, and no mitigation measures are recommended.

5.4.2.5 Albeni Falls/Lake Pend Oreille

SOS PA would allow a full, stable pool, which would be almost identical to that associated with SOS 2c, the recreation season. Therefore, no mitigation measures are recommended.

5.4.2.6 Grand Coulee/Lake Roosevelt

Recreation facilities at Lake Roosevelt have been constructed to accommodate recreation at reservoir elevations that are near full pool. Under SOS 2c, Lake Roosevelt reaches full pool by the end of July and remains there through the fall. The PA would result in summer pool elevations that would be from 6 to 9 feet below full pool. Therefore, some mitigation measures, generally at swimming beaches, are recommended.

5.4.2.7 Chief Joseph Project/Lake Woods

The PA would maintain a stable pool elevation, similar to that of SOS 2c, at the Chief Joseph Project. Therefore, no mitigation measures are recommended.

5.4.2.8 Middle Columbia Public Utility District Projects

There are few opportunities to mitigate for the higher flows, compared to SOS 2c, that would occur under the PA. It would be difficult and costly to modify existing recreation sites and facilities. No mitigation measures are recommended.

5.4.2.9 Hanford Reach

There are few opportunities to mitigate for the higher flows that would occur with the PA compared to SOS 2c. It would be difficult and costly to modify existing recreation sites and facilities. Therefore, no mitigation measures are recommended.

5.4.2.10 Snake River: Hells Canyon Reach

Under the PA, flows would remain within the desirable or acceptable range for summer recreation for longer periods than with SOS 2c. Therefore, no mitigation is recommended.

5.4.2.11 Dworshak Project and Lake

If may be feasible to modify or extend some recreational facilities to make them usable under the wider range of operating conditions that might occur under these. Where feasible, most of the existing boat ramps on the lake have already been extended to minimum lake elevations; it is not likely that the ramps could be further extended. Given the steepness of the shoreline, it also may not be feasible to modify the existing boat docks and moorage facilities. Some expansion of swimming facilities may be possible. However, again, these facilities are constrained by the physical characteristics of the site.

The PA would result in moderate to severe impacts to recreational facilities at Dworshak during the prime recreation season. Because of the severity of these impacts, mitigation measures at Dworshak might not be practical or feasible. Instead, opportunities for off-site mitigation should be explored. One alternative would be to develop a new state park elsewhere in the Clearwater River drainage.

5.4.2.12 Clearwater River Below Dworshak Dam

Most of the recreation sites along the lower Clearwater River are minimally developed and are designed to remain usable under a range of flows. The PA would result in river flows during the winter steelhead season and the summer recreation season that would be more beneficial to recreation, compared to SOS 2c. Therefore, no mitigation measures are recommended.

5.4.2.13 Lower Snake River Projects

Pool elevations at the lower Snake River projects would be higher during the prime summer recreation season relative to SOS 2c. Therefore, no mitigation measures would be necessary.

5.4.2.14 John Day Project/Lake Umatilla

Under the PA, operation of John Day project at MOP during some or all of the year would have severe impacts on the usability of many of the recreation facilities on Lake Umatilla. Many of

these facilities could be modified to improve their usability at MOP. Through the John Day Drawdown Advanced Planning and Design (AP&D) Study, authorized by the Energy and Water Development Appropriations Act of 1993 (Public Law 102-377, October 2, 1992), the Corps of Engineers, Portland District has undertaken advanced planning and design of modifications to public and private facilities, including recreation facilities of John Day Dam at MOP. Table 4-43 presents a summary of recreation site impacts and the actions possible to mitigate those impacts.

Railroad Island (WA), RM 216. This Corps of Engineers site was officially closed in the 1980's as a result of low public use. Mitigation is required however for Treaty Fishing Access until the proposed North Shore site construction is completed in 2001. Possible mitigation actions include: 1) removal of approximately 75 cubic yards (cy) of sediment from the boat ramp to make it operational at MOP; 2) addition of one 20 foot dock segment and; 3) installation of a depth gauge at the boat ramp. Modification of the culvert access would require extensive coordination with Burlington Northern Railroad and is considered prohibitively expensive, considering existing use of the site.

Le Page Park (OR), RM 217 (at the mouth of the John Day River). At this Corps site, the north boat ramp will need to be extended 40 feet to Elev. 253 to continue to be fully operational at MOP. One new U-pile will be required. The swimming beach would require excavation of approximately 14,000 cy, recontouring, and approximately 3,400 cy of sand fill. The moorage landward of the docks cannot be excavated because the riprap will prohibit dredging. Excavation of approximately 20 cy of sediment covering the toe of the south boat ramp and repair of the gangway wheels, angle plates, and anchor block connections would also be required to make this site operational at MOP. A depth gauge will be installed at the boat ramp.

Albert Philippi Park (OR), John Day RM 3.5. No mitigation effort be made at this site until a permanent solution to the existing sedimentation problem

in the John Day River is found and implemented. In the event further deposition of sediment can be controlled on a permanent basis the following mitigation efforts are recommended: 1) The short handling dock section at the south dock would be moved riverward one dock segment; 2) Approximately 135 cy (as of June 1994) of material would be removed from under the gangways at the north and south docks to allow the gangways to lay flat on the river bank as the water level lowers; 3) areas adjacent to both docks and below the north dock would be dredged to make this site operational at MOP; and, 4) a depth gauge would be installed at the dock. No pile driving would be required.

Rock Creek (WA), RM 229. Removal of approximately 145 cy of deposited material from the boat ramp would be required to make the boat ramp operational at MOP. No piles are required. A depth gauge would be installed at the boat ramp. Dredging of a passage channel to the river would be required. No work is proposed at the swimming beach to avoid disturbance of the developing wetland.

Blalock Canyon Harbor—Of—Refuge (OR), RM 233.5. This harbor—of—refuge is separated from Lake Umatilla by the Interstate 80 grade and is accessible via a culvert under the freeway. To make the existing gravel boat ramp useable at MOP would require an extension of approximately 130 feet and placement of approximately 290 cy of material. A depth gauge could be installed at the culvert. However, no mitigation actions are recommended for this site due to limited access through the culvert. The site will still provide refuge for small vessels with very shallow drafts during storm or periods of high winds.

Sundale Park (WA), RM 236.5. At this Corps site, removal of approximately 40 cubic yards of sediment at the toe of the ramp would be required to make the boat ramp operational at MOP. The boat dock would require an 80 foot extension (4 dock segments) and the addition of three piles.

Roosevelt Park (WA), RM 241. At this Corps site, the downstream handling dock segments (2 segments) could be relocated to the boat ramp dock area and

connected to the existing dock to increase boat ramp docking facilities. One single pile would have to be installed. A depth gauge would be installed at the boat ramp. The downstream handling area would be abandoned and the existing gangway removed and stored at the John Day Project for possible use at another facility. It appears that a groin extension would be required to allow recontouring of the swim beach. Major excavation and sand fill would be required to reestablish the swimming beach. Yearly maintenance is anticipated to replace lost sand and remove sediment build up behind the groin. Based on the minimal use by swimmers (reported by the John Day Recreation Resource Manager) that this beach receives, the cost of renovating is not considered economical for the benefits. It is recommended that the swim beach be abandoned.

Arlington Marina (OR), RM 241. At this site managed by the Port of Arlington, removal of approximately 80 cy of sediment from the toe of the boat ramp would be required to make the ramp operational at MOP. The boat ramp dock would not need be modified as the existing courtesy handling dock and moorage docks provide adequate tie up for all boat ramp users (this approach was coordinated with the Port during a June 1995 site reconnaissance trip). If excavation or pile driving becomes necessary in the future, it will be done through at least 35.0 feet of medium dense alluviums as revealed in a recent boring near the end of the boat ramp.

Snell Park, Arlington (OR), RM 241. At this city of Arlington Park, excavation of approximately 16,000 cy of sediment, resloping the beach, and placing approximately 5,600 cy of sand fill would be required to provide an adequate area for swimming and access to the beach. This excavation would also ensure that the floating bandstand will not be resting on the river bottom. A low wall, approximately 3 feet high and 400 feet long, would be required to prevent wave wash and erosion. It is not possible to recontour the area in front of the diving platform to provide a minimum of 12 feet in depth, the COE minimum requirement for diving from a 0 to 9 feet (3 meter) high platform, without exceeding the COE maximum beach slope of one vertical on 10 horizontal. The proposed recontouring scheme provides a minimum

water depth at the bandstand of seven feet. For this reason, diving from the bandstand should not be allowed. Excavation would be required under the small handling dock gangway to prevent the dock from resting on the reveted slope.

Three Mile Canyon (Quesnel) (OR), RM 255. No mitigation is recommended at this site other than signing the east entrance as a "SHALLOW CHANNEL" and adding a depth gauge. It is proposed that the boat ramp not be repaired as the gravel ramp is adequate to handle the volume of launching activity until construction of new ramps, as proposed under the Treaty Fishing Access Sites Phase 2 report. A recent boring in the channel indicates that any future work in the channel would encounter loose sand with some gravel at the river bottom grading to medium dense silty fine-grained sand below a depth of about 3.0 feet, medium dense sandy gravel below 8.5 feet and dense silty sand below 14.0 feet. No rock was encountered at the bottom of the hole at 16.5 feet.

Crow Butte State Park (WA), RM 262. At this Washington State Park, removal of approximately 700 cubic yards of sediment from the toe of the river boat ramp and excavation of approximately 1170 cubic yards of material to provide clear access to the ramp would be required to make the river boat ramp operational at MOP. It is believed that wave action in this area would be minimal as the flow around the back of the island would be disrupted at MOP. Two additional 20 foot dock sections with one pile would be required for the river side handling dock. Excavation totaling 40,400 cubic yards and placement of 10,600 cubic yards of sand will be required to make the swimming area useable. Excavation of approximately 165 cy of sediment will be required to provide a minimum water depth of 3 feet at the boat basin courtesy dock. It is believed this is preferable to relocation of the dock access gangway and the first landward section of dock. A channel running from the entrance of the marina to the courtesy dock and the areas adjacent to the dock would be excavated to a minimum depth. It is assumed the marina boat ramp would remain in use for small, shallow draft boats. Approximately 170 cy of silt would be removed from the toe of the ramp. Marine safety devices,

such as buoys or floating booms, would be required along the irrigation pump intake piping to deter boat travel between the pipe support pilings.

Boardman Park and Marina (OR), RM 269. At this site, operated by the Boardman Park and Recreation District, removal of approximately 75 cubic yards of sedimentation would be required at the toe of the boat ramp to make it fully useable at MOP. The boat ramp dock would require an extension of one 20 foot segment with one pile. Excavation would be required under the two moorage docks to allow the gangways to lay on the slope during MOP. Moorage dock #1, the westerly dock, would require 85 cy of excavation. Moorage dock #2, the east dock, would require 320 cy of excavation. If the floating dock is moved back to its original location, approximately 125 cy of material would be excavated to allow it to float.

Deeper-draft docking facilities could be provided by either: 1) extending the existing west moorage dock to deeper areas within the marina (larger slips would be required); or, by 2) relocating one of the existing docks to a location adjacent to the breakwater. Both alternatives would require additional piling. Alternative #1 would require excavation to Elev. 248, a 90 foot dock extension to provide 12 new boat slips, and three single piles. Alternative #2 would require developing access for pedestrians and carts through the existing campground area, addition of an anchor block to attach the gangway, and additional piling. Utilities would also have to be routed to the new dock location. Park district representatives prefer alternative #1. No modification to the existing swimming beach is recommended because access to water will still be available at MOP and unless water quality can be improved swimming will remain a low use public activity in the park.

Irrigon Park & Marina (OR), RM 282. Extensive modification would be required to make this site, operated by the Irrigon Park and Recreation District, fully operational at MOP. Three alternative mitigation scenarios have been considered. These include: Alternative No. 1 – excavation of the entire marina bottom to Elevation 249.5 would involve approximately 9,750 cubic yards of excavation; Alternative No. 2 – excavation of only the western half of the marina would involve excavation of approximately

4,600 cubic yards of material, and; Alternative No. 3 – construction of a floating break water outside the marina with no deepening required in the marina. Entrance depth required will be 8.5 feet.

The entrance will require widening to accommodate the lower elevation for MOP and most large boats. A large excavation would also be required to reestablish an area with adequate depth for swimming. Once the excavation is complete, the wave action that is causing the current bank erosion would continue and the newly excavated beach slope would be eroded and refill the excavated area. A breakwater to protect the newly excavated slope would be very expensive. For this reason, it is recommended that the swimming area be abandoned.

Removal of approximately 250 cy of sediment at the toe of the boat ramp is required to make the site operational at MOP. The courtesy dock and the east moorage dock would also require excavation under their gangways.

Umatilla Park And Marina(OR), RM 289. Mitigation in the marina would require removal of approximately 40 cy of sediment from the toe of the boat ramp and deepening the bottom of the marina to Elev. 246.5 to provide a total clearance of 11.5 feet at MOP. This would provide adequate depth for deep draft vessels in the marina. Total depth for the entrance would be 12.5 feet, Elev. 245.5, to provide for wave and bottom clearance for larger ships using the marina. Two alternatives could provide the necessary clearance for deep draft vessels utilizing the marina. There is one alternative for constructing a floating break water structures outside the marina without excavation in the marina. Up to 37 piles could require removal and replacement.

Alternative 1 – Excavate east side under deeper draft moorage docks; west side including entrance channel, boat ramp, and fueling dock; and access channel from the marina entrance to the east side moorage area. A total of approximately 71,000 cubic yards of overburden material and 350 cubic yards of rock excavation would be planned. Twenty replacement piles would be installed.

Alternative 2 – Excavate west half of marina and deepening the entrance area, fuel dock area, and the area to the east a minimal depth to provide the access and moorage of shallower draft vessels. Approximately 43,200 cubic yards of material would be excavated and 37 piles would require replacement.

Alternative 3 – Construct floating breakwater with rubble mound breakwater on the ? side for wind/wave protection.

The boat ramp south dock would require an extension of (2) 20-foot segments with (1) new U-pile. Gangways would not require modification because they would not exceed a 33% slope more than 10% of the time. Excavation at the toe of the reveted slopes behind all docks would be required. No mitigation at the swimming beach is proposed as it is not used by the public because of the poor water quality, sediment build up, and the lack of maintenance by the lessee.

Mitigation at the swimming beach would require 15,000 cubic yards of excavation and placement of 14,000 cubic yards of sand to achieve a maximum water depth of seven feet. Because of low use by the public, poor water quality, sedimentation build up, and lack of maintenance it is recommended that the swimming beach be abandoned.

Plymouth Park (WA), RM 289. At this Corps park, two dock segments with one pile would be added to each of the handling docks. The courtesy dock would be reduced by two dock segments on the shallow end. There would be a minimum of 2 foot depth under the landward edge of the remaining segments. The removed segments could be added onto the deeper (east) end of the dock. Approximately 490 cy of material consisting of very dense sandy gravels and cobbles would be excavated from under the courtesy dock. An alternative was considered that would require installing additional gangway segments, pushing the existing dock out with additional dock segments and piling. If additional piling is added at the courtesy dock it would require driving in very dense sandy gravels and cobbles to a depth of 18 feet below river bottom and into very hard, fractured basalt to a depth of 22.0. The swimming beach would require extensive excavation of approximately 43,400 cubic yards, reshaping and the addition of 10,400 cubic

yards of sand to provide adequate swimming area, four to six feet deep.

Nugent Park (OR) (on the Umatilla River near the mouth). Extension of the boat ramp to Elev. 254 and excavation of the area in front of the boat ramp to Elev. 253 would be required to provide launching for boats that currently use the ramp. Extensive excavation, which is partially in rock, within the Umatilla River channel would be required to provide boat access downstream of the boat ramp. Excavation

would be required directly in front of the fishing structure to provide fishing opportunities for handicapped persons. This excavation would also be in

rock. Based on the extensive rock excavation required to mitigate the boat ramp and fishing structure to maintain existing use at MOP, and the close proximity of boat launching facilities at Umatilla Marina, it is recommended that impacts at this site not be mitigated.

5.4.2.15 Other Lower Columbia Projects

None of the alternative SOSs under consideration involve any specific operational changes at McNary, The Dalles, or Bonneville project. Therefore, no recreation mitigation actions are recommended at Lake Bonneville, Lake Celilo, or Lake Wallula under any of the alternative SOSs.

CHAPTER 6

LIST OF PREPARERS

The SOR Recreation Technical Appendix was prepared by the Recreation Work Group (RWG). Initial participants on the RWG included representatives from the three sponsoring agencies, U.S. Army Corps of Engineers (Corps), U.S. Bureau of Reclamation (Reclamation) and Bonneville Power Administration (BPA). Throughout the study process, the sponsoring agency representatives had administrative oversight for the work accomplished by the RWG, including:

- a. coordination with SOR study management/analysis group
- b. scheduling work group activities
- c. administration of contracts
- d. obtaining and managing funding
- e. preparing written materials for SOR documentation

- f. implementation of the public involvement plan.

As the SOR moved into the scoping and screening phases, other Federal, state, and local agencies and others with authorities and responsibilities for managing recreation facilities or resources in the basin, as well as private citizens, were invited to join the RWG.

RWG members were primarily responsible for producing this appendix and other interim products required of the RWG during the SOR process. RWG collectively determined the appropriate scope of SOR recreation studies. Individual RWG members collected, evaluated, and consolidated information and data, and wrote sections of the appendix. Finally, RWG participants reviewed and provided comments on materials produced by other members and consultants of the RWG, and other SOR work groups.

Table 6-1 identifies the RWG members who played an active role in preparation of this appendix.

Table 6-1. List of Preparers, Recreation Appendix

Name	Education/Years of Experience	Experience and Expertise	Role In Preparation
Phil Benge	B.S. Natural Resource Management 17 years	Outdoor Recreation Planning Park Management	Inventory and Impact Assessment, Dworshak, Lower Snake, McNary Projects and Clearwater River
Jimmy Brown	B.S. Landscape Architecture, 26 yrs	Recreation Planning	Inventory and Impact Assessment for Dworshak, Lower Snake, and McNary Projects, and Clearwater River
Jim Budolfson	B.S. Forestry 22 years	Outdoor Recreation Planning Natural Resource Management	Inventory and Impact Assessment, Hungry Horse and Grand Coulee Projects

Table 6-1. List of Preparers, Recreation Appendix – CONT

Name	Education/Years of Experience	Experience & Expertise	Role In Preparation
John Callaway	B.A./M.A.History M.S. Agriculture and Resource Economics 15 years	Economics	Phase I Recreation User Survey Implementation and Results
Kelly Cash	B.A. English A.I.C.P 26 years	Outdoor Recreation Planning Natural Resource Management	Inventory and Impact Assessment for Grand Coulee Project
Steven Cosgrave	B.A. Humanities/English MBA International Management	Writer/Editor Public Relations Recreation Planning and Management	Inventory and Impact assessment for Libby, Albeni Falls and Chief Joseph projects
Jeff Frost	B.S./M.S. Recreation Resource Management 13 years	Outdoor Recreation Planning	Review and Coordination
Mark Greenig	M.U.P. Urban Planning B.S. Landscape Arch. 13 years	Visual Resources Recreation Planning and Design Site Planning and Design	Aesthetic Resource Inventory and Impact Assessment and Alternative Trade-Off Analysis
Scott Jackson	B.S. Conservation M.S. Natural Resource Planning Development 17 years	Outdoor Recreation	Review and Coordination
Mark Johnston	B.S. Geography 23 years	Outdoor Recreation Planning Site planning & Design Resource Management	Review and Coordination
Debbie Kitchin	B.A. Economics 15 years	Regional Economics	Review and Coordination
Chuck Korson	M.S. Natural Resource Management/Economics B.A. Biology B.A. Economics 14 years	Fisheries Management Environmental Analysis	Impact Assessment Model Development: Inventory and Impact Assessment for Middle Snake River
Chris Jansen Lute	B.S. Recreation Resource Management 18 years	Outdoor Recreation Planning, Natural Resource Management	Impact Assessment and Inventory for Hungry Horse Reservoir
Gregg Mallette	B.A. Economics M.A. Geography/Resource Management, 5 years	Watershed Management, Resource Economics Intergovernmental Coord.	Inventory and Impact Assessment for Upper Columbia River (Canada)
Mike McElhatton	B.A. Park and Recreation Management 15 years	Park and Recreation Management	Inventory and Impact Assessment for Dworshak Lake and Clearwater River

Table 6-1. List of Preparers, Recreation Appendix – CONT

Name	Education/Years of Experience	Experience & Expertise	Role in Preparation
John Platt	M.S. Natural Resource Economics 7 years	Natural Resource Issues: Recreation, Fisheries, Water	Review and Coordination
Jim Pope			Review and Coordination
Matthew Rea	B.S. Outdoor Recreation Planning 15 years	Study Management Outdoor Recreation Planning Environmental Assessment	Work Group Chairman and Coordination; Inventory and Impact Assessment for John Day, The Dalles, Bonneville Projects
Shannon Ragland	Ph.D. Economics M.A./B.A Economics 9 years	Economics	Phase I Recreation User Survey Implementation and Results Analysis
William Shaw	B.A. Geography Ph.D. Economics 9 years	Economics	Phase I Recreation User Survey Implementation and Results Analysis
Wayne Shuyler	B.P.E. M.S. Parks and Recreation Administration 19 years	Statewide/Comprehensive Planning	Review and Coordination
Gail Throop			Review and Coordination
Kelly Wallace	B.A. International Studies 5 years	Review and Coordination	Review and Coordination
Jeff White	B.S. Business Administration M.L.A. Landscape Architecture 15 years	Outdoor Recreation Planning Landscape Architecture	Inventory and Impact Assessment for Libby, Albeni Falls and Chief Joseph Projects and Kootenai River

CHAPTER 7

REFERENCES

- Allen, Stewart. 1988. Montana Bioeconomics Study: Results of the Trout Stream Angler Preference Survey. Prepared for Montana Department of Fish, Wildlife, and Parks.
- Ben-Zvi, Samuel and Associates. 1990. Evaluation of Nonpower Impacts from Reservoir Drawdown at Hungry Horse Reservoir. Final Report to the U.S. Bureau of Reclamation, Contract N. 9-CS-10-10140, Fort Collins, Colorado.
- Cameron, A.C. and P. Trivedi. 1986. Econometric Models Based on Count Data: "Comparisons and Applications of Some Estimators and Tests." *J. of Applied Econometrics*, 1:29-53.
- Cameron, T.A. 1992. "Combining Contingent Valuation and Travel Cost Data for the Valuation of Nonmarket Goods." *Land Economics*, 3:302-317.
- Ch2M Hill. 1985. Hells Canyon Environmental Investigation, prepared for Bonneville Power Administration, DOE/BP-11548-1, Portland, Oregon.
- Columbia Gorge Access Committee. 1987. Wind-surfing Development and Potential on the Washington Shore of the Columbia River Gorge.
- Coyle, John. 1991. Conversation with Natural Resource Manager, Corps of Engineers, Libby/Albeni Falls Projects.
- Dorsey, Geoff. 1993. Personal Communication with Wildlife Biologist, Corps of Engineers, Portland District.
- Englin, J. and T.A. Cameron. 1993. "Comparing Observed and Multiple-Scenario Contingent Behavior: A Panel Analysis Utilizing Poisson Regression Techniques." In *Western Regional Research Publication, W-133: Benefits and Costs Transfer in Natural Resource Planning, Sixth Interim Report*, J.C. Bergstrom (ed.).
- Ermis, Greg. 1994. Letter from Mariha Manager, Port of Camas, Washougal.
- Greig, P.J. 1983. "Recreation Evaluation Using a Characteristics Theory of Consumer Behavior." *American J. of Agricultural Econ.*, February: 90-97.
- Hausman, J., B. Hall and Z. Griliches. 1984. "Econometric Models for Count Data with an Application to the Patents-R&D Relationship." *Econometrica*, 52: 909-938.
- Hellerstein, D.M. 1991. "Using Count Data Models in Travel Cost Analysis with Aggregate Data." *American J. of Agricultural Econ.*, August, 860-66.
- Hospodarsky, Denver. 1989. "The Pacific Northwest Outdoor Recreation Consumption Projection Study: Tri-State Summary." Final report to the Pacific Northwest Outdoor Recreation Committee, Oregon State University, Corvallis, Oregon.
- Hume, Mark. 1991. "Two-dam Columbia Plan Assailed," *Vancouver Sun*.
- Idaho Power Company. 1991. Idaho Power Fall Chinook Interim Recovery Plan and Study IV & 28 pp.
- Krumpe, Allen, and McCoy. 1989. Hells Canyon Visitor Profile and Recreation Use Study, Department of Wildland Recreation Management, College of Forestry, Wildlife and range Sciences. University of Idaho, Moscow, Idaho.
- Krumpe, Allen, and McCoy, editors. 1991. Hells Canyon Limits of Acceptable Change Planning Task Force, Recommended Limits of Acceptable Change Recreation Management Plan for the Snake River Hells Canyon National Recreation Area. Wallowa-Whitman National Forest, Clarkston, Washington.
- McArthur. 1995. Idaho Department of Fish and Game. Personal Communication.
- Maiolie, Melo. 1995. Idaho Department of Fish and Game. Personal Communication.

- Mallette, Gregory F. 1991. "An Investigation of Some Aspects of the Dollar Value of the Environmental Resources of the Columbia River in South-Central British Columbia." M.A. Thesis, University of Waterloo, Waterloo, Ontario, Canada.
- Mallette, Gregory F. 1992. "Remnant of a Great River." Salmon-Trout-Steelheader. April-May: 34-37.
- Montana Department of Fish, Wildlife and Parks. 1990. Montana Statewide Comprehensive Outdoor Recreation Plan.
- Morey, E.R. 1981. "The Demand for Site-specific Recreational Activities: A Characteristics Approach." J. of Environ. and Econ. Management, 8:345-71.
- National Park Service. June 1992. Draft Comprehensive River Conservation Study and Environmental Impact Statement. Hanford Reach of the Columbia River.
- Oregon Parks and Recreation Department. 1993. Draft Master Plan for the Columbia River Gorge District. Salem, Oregon.
- Oregon State Parks and Recreation Department. 1986. Columbia Gorge Windsurfing Study. Salem, Oregon.
- Oregon State Parks and Recreation Department. 1988. Comprehensive Statewide Outdoor Recreation Plan. Salem, Oregon.
- Oregon State Marine Board. 1993. 1993 Statewide Boating Survey. Salem, Oregon.
- Pope, Jim. 1992. Recreation Planner, Chelan Public Utility District, Wenatchee, Washington. Personal Conversation.
- Povey, David. 1990. Columbia River Gorge Windsurf Economics: 1990 Season. University of Oregon Community Planning Workshop. Eugene, Oregon.
- Propst, Dennis B., et al. 1992. A Summary of Spending Profiles for Recreation Visitors to Corps of Engineers Projects. U.S. Army Corps of Engineers, Waterways Experiment Station, Huntsville, Alabama.
- RCG/Hagler, Bailly, Inc. 1993. Estimation of Recreation Impacts for the Columbia River System Operation Review: Methods for Phase II. Final Report to the Army Corps of Engineers. Contract DAAL003-91-C-0034.
- Seamans, Art. 1991. Personal conversation with Hells Canyon National Recreation Area River Manager, Wallowa-Whitman National Forest, Clarkston, Washington.
- Skaar, Don. 1992. Skaar, Letter to Area Fisheries Biologist with Montana Department of Fish, Wildlife and Parks.
- Stephenson, James B. 1984. Murphy Creek Project Recreation and Tourism Impact Assessment. Era Business Consultants, Vancouver, B.C. 91 p.
- Werdham, Dick. 1991. Werdham, Conversation with Supervisory Park Ranger, Corps of Engineers, Libby Dam Project.
- U.S. Army Corps of Engineers. 1985. A preliminary investigation of recreation, fisheries, and cultural resources and impacts on those resources of the reservoir is drafted deeper. Seattle District.
- U.S. Army Corps of Engineers. 1992. Draft EIS Interim Columbia and Snake Rivers Flow Improvement Measures for Salmon. ACOE/10-8-92/03258A. Portland, Oregon.
- U.S. Army Corps of Engineers. 1992. Columbia River Salmon Mitigation Analysis System Configuration Study: Phase I Interim Status Report, Technical appendix B, John Day Reservoir Minimum Operating Pool. Portland, Oregon.
- U.S. Bureau of Land Management. 1991. Draft Recreation Management Plan Environmental Assessment for Snake River Reservoirs - Brownlee, Oxbow, and Hells Canyon Reservoirs, Baker Resource Area, Oregon.
- U.S. Department of Interior, Heritage Conservation and Recreation Service. 1979. The Third Nationwide Outdoor Recreation Plan.
- U.S. Environmental Protection Agency. 1978. Region 10 Water Quality Assessment.

U.S. Forest Service. 1991. Columbia River Gorge National Scenic Area: Final Draft Management Plan for General and Special Management Areas. Hood River, Oregon.

U.S. Outdoor Recreation Resources Review Commission. 1962. Water for Recreation—Values and Opportunities: Study Report No. 10. U.S. Government Printing Office.

TECHNICAL EXHIBIT A

RECREATION WORK GROUP

A.1 TIER 1 PARTICIPANTS

Phil Benge, U.S. Army Corps of Engineers, Walla Walla District

Jim Budolfson, Bureau of Reclamation, Pacific Northwest Region

Kelly Cash, National Park Service, Coulee Dam National Recreation Area

Don Eixenburger, Oregon State Parks and Recreation Department

Steve Starlund, Wild and Scenic Rivers Program, Washington State Department of Parks and Recreation

Jeff Frost, Washington Interagency Committee for Outdoor Recreation

Mark Greenig, Foster-Wheeler Environmental

John Platt, Bureau of Reclamation, Engineering and Research Center

Scott Jackson, Army Corps of Engineers, Waterways Experiment Station

Chris Jansen Lute, Bureau of Reclamation, Pacific Northwest Region

Mark Johnston, Recreation Planner, British Columbia Hydropower Authority

Debbie Kitchin, Northwest Power Planning Council

Chuck Korson, Bureau of Reclamation, Lower Columbia Area Office

Gregg Mallette, Canadian Citizen

Mike McElhatton, Dworshak State Park, Idaho State Parks Department

Marguerite Nabeta, Oregon State Parks and Recreation Department

Kelly Wallace, Bonneville Power Administration

Jim Pope, Chelan County PUD #1

Matthew Rea, U.S. Army Corps of Engineers, Portland District

Wayne Shuyler, Oregon State Marine Board

John Stevenson, Pacific Northwest Utilities Conference Committee

Gail Throop, USDA Forest Service, Pacific Northwest Region 6

Jeff White, U.S. Army Corps of Engineers, Seattle District

Steve Cosgrove, U.S. Army Corps of Engineers, Seattle District

A.2 TIER 2 PARTICIPANTS

Dwight Affleck, Charbonneau Marina

Duane Annis, Resource Assistant, North Fork Ranger District, Orofino

Frank Arnold, Park Manager, Rooster Rock State Park

Rod Bailey, Lyons Ferry Marina

Fred Beruschi, Revelstoke, BC

British Columbia, Ministry of Environment

British Columbia, Ministry of Energy, Mines and Petroleum Resources

British Columbia, Ministry of Environment, Lands and Parks

British Columbia, Ministry of Tourism

British Columbia Wildlife Federation

Ehor Boyanowski, Steelhead Society of British Columbia, Vancouver, BC

Jerry Brobst, Flathead Electrical Cooperative	Idaho Panhandle National Forests, Forest Supervisor
Ralph Burris, Manager, Chiawana Park, Pasco	Eugene Johnson, Tri-Cities Rivershore Enhancement Committee
Russ Burtner, City of Kennewick	Recreation Committee
Bill Butts, Lake Roosevelt Recreational Enterprises	Stu Kestner, Riverside sport Shop, Orofino
Bill Byrone, Manager, Lyons Ferry State Park	Brian Kinnear, US Fish and Wildlife Service, Columbia River Coordination Office
Castlegar District Development Board, Castlegar, BC	Kootenai National Forest, Forest Supervisor
Dave Chambers, Water World Marina, Pasco	Kootenay County Tourism Association, Nelson, BC
Jerry Chicheti, Manager, Boat Shop Marina, Richland	Jim Kosciuk, Army Corps of Engineers, Resource Manager, Dworshak Project
Rich Clark, U.S. Bureau of Reclamation, Hungry Horse Project Office	Loring Larson, Park Manager, Deschutes River Recreation Area,
Jonathan Coe, Sandpoint Chamber of Commerce	Oregon State Parks
Harry Connell, Trail, BC	Libby Chamber of Commerce, Libby, MT
Confederated Salish and Kootenai Tribes of the Flathead Reservation	Gary Long, Chief Timothy State Park
Brian Connors, Planning Department, Hood River County	Shana Louthierback, Chairman, Water Quality Subcommittee, Lake Roosevelt Forum
Rich Curren, Interim Director, Skamania County Parks	Jon Matthews, Pullman, WA
Susan Daggett, Director of Operations, Port of Umatilla	Kerry McIntyre, Fruitvale, BC
Ti Dahlseide, PNW Power Planning Council	Linda McClure, Mariner's Haven Marina, Eureka, MT
John Drake, United States Forest Service, Region 1, Missoula, MT	Gary Medley, Medley's Marina, Orofino
Gary Field, Commodore, Lake Roosevelt Boat Club	Kay Metz, Metz Marina, Kennewick
Bob Gilchrist, Red Wolf Marina, Clarkston, WA	Elouise Miller, Columbia River Intertribal Fish Commission
Golden Chamber of Commerce, Golden, BC	Montana Department of Natural Resources and Conservation
Larry Goodrow, Spokane Tribe	Bob Montgomery, General Manager, Port of Cascade Locks
Scott Hage, Director, Port of The Dalles	Lee Morris, High Country Tourism Association, Kamloops, BC
Gordon Haugen, U.S. Forest Service, Pacific Northwest Region	Jim Obanion, Executive Director, Port of Hood River
Steve Holberg, Boyer Park Marina, Colfax, WA	Yvonne Passmore, Colville Confederated Tribes, Parks Department
Idaho Department of Parks and Recreation	John Patrick, Asst. Manager, Central Ferry State Park

C. Vernon Peugh, U.S. Bureau of Land Management	Tobacco Valley Board of Commerce, Eureka, MT
Bill Profili, Rossland, BC	Margie Todd, Lincoln County Economic Council, Libby, MT
John Ridlington	Robert Turner, Special Asst. for Policy, State of Washington
John Ridzik, U.S. Bureau of Indian Affairs, Colville Agency	Sheldon Tyler, Manager, Port of Camas/Washougal
Doug Robinson, Golden, BC	University of Waterloo, Department of Geography, Waterloo, Ontario
Sandpoint Ranger District, Sandpoint WA	Jim Vasrow, Montana Dept. of Fish Wildlife and Parks
Sandy Santori, Trail, BC	Louise Watson, Lake Roosevelt Forum
John Scarola, Park Manager, Maryhill State Park	West Kootenay Parks Branch, British Columbia
Larry Schluntz, Bureau of Reclamation, Engineering and Research Center, Denver	Jack Wiles, Supervisor, Region 1, Oregon State Parks and Recreation Department
Scotties Marina, Castlegar, BC	Del Williams, Hells Gate State Park
Brian Short, Manager, Bingen Boat Basin, Port of Klickitat	Jenny Wilson, Bonneville Power Administration
Dave Smith, Bureau of Reclamation, Engineering and Research Center, Denver	Ed Wimberly, Lake Roosevelt Vacations
Kristin Sycamore, National Park Service, Wild and Scenic Rivers Program	Bob Writer, Park Planner, Washington State Parks
Gary Szabo, Trout Unlimited, Calgary, BC	Earl Yoes, Commodore, Walla Walla Yacht Club
Susan Tanska, Director, Benton County Parks	Frank T. Yuse
Rick Terway, Manager, Sacajawea State Park	

TECHNICAL EXHIBIT B

GLOSSARY OF TERMS AND ACRONYMS

Activity Day or Activity Occasion: A measure of recreation use by one person on one facility or area for one day or part of a day. One person may exert more than one activity day per day. The activity day is probably most useful for apportioning total use to single uses and for sizing various parts of a given recreational development.

Activity—Hour: The participation by one person or more in a recreation activity during continuous, intermittent, or simultaneous periods of time aggregating 60 minutes.

Activity Participation Rates: A percentage of day—use activity occasions, expressing an individual's desire to participate in one of various activities.

Anadromous Fish: Species which migrate from the sea to spawn in fresh water. Their offspring return to the sea and spend most of their adult lives there (e.g., salmon and steelhead).

Annual Recreation Days: A measure of the estimated or actual visitation of a site or area in a given year in terms of recreation days (see also Recreation Days).

BLM: United States Department of Interior, Bureau of Land Management.

BoR: United States Department of Interior, Bureau of Reclamation (also referred to as Reclamation).

BPA: Bonneville Power Administration.

Big game: A designation for large animals, some of which are hunted; e.g. deer, elk, bear.

CBFWA: Columbia Basin Fish and Wildlife Authority.

CFS: Cubic Feet per Second; a measurement of the volume of flow of water.

Corps: United States Army Corps of Engineers.

CRGNSA: Columbia River Gorge National Scenic Area.

Critical Period: That portion of the historical 50—year streamflow record that would produce the least amount of energy with all reservoirs drafted from full to empty. For the purposes of this appendix, the critical period is the four—year period ending in 1941.

Cost—Sharing Agreement: An agreement between the Federal Government and a local agency or other public entity to share costs of constructing recreation facilities or wildlife enhancement developments. Such agreements usually require the local sponsor to lease the developments and provide for their operations and maintenance.

Cultural Resources: Significant objects, structures, buildings and other evidences of past human behavior; historical and archeological artifacts.

Day—Use Area: A site or portion of a recreation area designated for recreation use by recreationists remaining on an area for one day or less. Does not include overnight use. Commonly, a day—use area will be developed to accommodate a number of recreation activities; e.g., picnicking, sightseeing, water sports, etc.

Design Load: The theoretical number of people developed recreation sites or facilities can accommodate at a given moment or over a period of time.

Diversity: The relative degree of abundance of plant and/or animal species in specified unit area, habitat type or other specified dimension.

Dispersed Recreation: Non-site oriented recreation activities that tend to spread randomly over a given area; e.g., hunting, snowmachining, etc.

Draft: Release of water from a storage reservoir.

Drawdown: The distance a water surface of a reservoir is lowered from a given elevation as water is released from the reservoir. Drawdown is generally measured as feet down from the full pool level of a given reservoir.

EIS: Environmental Impact Statement

Endangered Species: A plant or animal species which is in danger of extinction throughout some significant portion or all of its range because its habitat is threatened with destruction, drastic modification, or severe curtailment because of overexploitation, disease, predation or other factors. Federally endangered species are designated by the USFWS and published in the Federal Register.

Enhancement: Project facilities or modifications developed for improving fish and wildlife resources. Typically, the Corps may not undertake fish and wildlife enhancement unless a non-federal public body agrees to administer the land and water areas and cost-share (or provide development) for such projects.

ESA: Endangered Species Act.

Flood Control Rule Curves: A curve, or family of curves, showing the seasonal or monthly reservoir drawdowns required to control flood flows (also called Mandatory or Upper rule curves).

Flows: The volume of water passing a given point per unit of time.

Forebay: The portion of a reservoir at a reservoir project that is immediately upstream of the dam.

Full Pool: The maximum level of a reservoir under its established normal operating range.

FWS: United States Fish and Wildlife Service.

HCNRA: Hells Canyon National Recreation Area.

Habitat: The sum total of environmental conditions of a specific place occupied by a wildlife species or a population of such species.

High-Density (or Intensive Use) Recreation: Recreation activities characterized by high levels of use or numbers of visitors at a relatively small site or facility such as a developed campground, picnic area, swimming beach or visitor center. Synonymous with intensive-use recreation.

IGFG: Idaho Department of Fish and Game

Intensive-Use Recreation: See high-density recreation.

Interpretive Area: An area developed for educational purposes to explain and enhance unique historical, natural, or visual aspects of a project site and its surrounding area. Such development could include: trails and viewing points, informational displays, other appropriate graphics and signing.

IPC: Idaho Power Company

KAF: Thousand Acre-feet

Low-Density Recreation: Recreation activities characterized by low levels of use or numbers of visitors dispersed throughout a relatively large area or at a minimally developed recreation site. Includes most trails activities such as hiking and cross-country skiing and dispersed uses such as hunting.

Low Pool: At or near the minimum level of a reservoir under its established normal operating range.

MAF: Million Acre-feet.

MDFWP: Montana Department of Fish, Wildlife and Parks.

Mitigation: Actions to avoid, minimize, reduce, eliminate, or rectify the impact of a project or development on the environment.

Monitoring: When pertaining to wildlife management, includes actions undertaken to assess the survival

success of a species over time, or to evaluate the results of a management action or activity upon the species' habitat.

MOP: Minimum Operating Pool; the minimum elevation of the established operating range of a reservoir.

NGVD: National Geodetic Vertical Datum.

NMFS: National Marine Fisheries Service.

NPS: National Park Service.

NWR: National Wildlife Refuge.

Overlook: A sightseeing and/or observation area so located and constructed that visitors can view the dam, project area, lake, surrounding countryside or other objects or areas of interest.

Passive Management: Natural resource management strategy oriented toward allowing natural processes to continue their course with a minimum of human manipulation.

PNCA: Pacific Northwest Coordination Agreement. A binding agreement among BPA, the Corps, BoR, and the major generating utilities in the Pacific Northwest that stemmed from the Columbia River Treaty. The Agreement specifies a multitude of operating rules, criteria, and procedures for coordinating operation of the system for power production. It directs operation of major generating facilities as though they belonged to a single owner.

Pool: Reservoir; a body of water impounded by a dam.

PUD: Public Utility District

Public Domain: Federally-owned lands typically managed by the Bureau of Land Management.

Raptor: Any predatory bird, such as falcons, hawks, eagles, or owls, that has feet with sharp talons or claws adapted for seizing prey and a hooked beak for tearing flesh.

Recreation Day: A standard unit of use consisting of one visit by one individual to a recreation area or development for recreation purposes during any measurable portion, or all, of a 24-hour day.

Reservoir elevations: The levels of the water stored behind dams, stated in reference to mean sea level.

Reservoir storage: The volume of water in a reservoir at a given time.

Resident fish: Fish species that reside in fresh water throughout their lives.

Riparian: Related to or living or located on a natural water-course or lake. Riparian vegetation are plant communities requiring free or unbound water or conditions more moist than normally found in the area. Riparian "zones" are terrestrial areas where the vegetation and microclimate are influenced by perennial or intermittent water, associated with high water tables and soils which exhibit some wetland characteristics. Riparian "habitats" occupy the transitional zone between true bottomland wetlands and upland terrestrial habitats and, while associated with water courses, may extend inland for some distance.

RM: River Mile.

RNA: Research Natural Areas

Rule curves: Water levels over time, represented graphically as curves, that guide reservoir operations.

Run-of-river dams: Hydroelectric generating plants that operate based only on available streamflow and some shortterm storage (hourly, daily, or weekly).

Run-of-river reservoirs: The pools or impoundments formed behind run-of-river dams.

Salmonids: Of or pertaining to fish of the family Salmonidae, including salmon, trout, and steelhead.

SCORP: Statewide Comprehensive Outdoor Recreation Plan.

SCS: United States Soil Conservation Service.

Sediment: Any material transported by water, which will ultimately settle to the bottom.

Species: A unit of classification of plants and animals consisting of the largest, most inclusive array of sexually-reproducing and cross-fertilizing individuals which share a common gene pool.

Species Richness and Diversity: A term denoting the generally desirable management strategy of obtaining a relatively high number of species per unit area.

SOR: (Columbia River) System Operation Review

Spill: Water passed over or through a spillway or through regulating outlets without going through turbines to produce electricity. Spill can be forced, when there is no storage capability and flows exceed turbine capacity, or planned, for example, when water is spilled to enhance juvenile fish survival.

Storage reservoirs: Reservoirs that provide space for retaining water from springtime snowmelts. Retained water is released as necessary for multiple uses—power production, fish passage, irrigation, recreation and navigation.

Streamflow: The rate at which water passes a given point in a stream, usually expressed in cubic feet per second (cfs).

Trailhead: A developed site designed to provide and promote access to a designated trail or system of trails. Facilities should include parking, sanitary facilities and signing. Other facilities are dependent upon the trails' uses to occur, e.g. corrals and loading ramps for equestrian trails.

Trespass: The illegal intrusion upon the property of another; see also "encroachment."

URC: Upper Rule Curve (see flood control rule curves).

USFS: United States Forest Service

USFWS (or FWS): United States Fish and Wildlife Service.

USGS: U.S. Geological Survey

VERS: The Corps of Engineers Visitation Estimation and Reporting System, a family of microcomputer-based programs designed to estimate and report recreation use on Corps projects.

Visit: The entry of one person into a recreation area or site to carry on one or more recreation activity (Visit is often confusingly expressed as "visitor").

Visitor—hour: The presence of one or more persons on an area of land or water for the purpose of engaging in one or more recreation activities during continuous, intermittent, or simultaneous periods of time aggregating 60 minutes.

Visitor—day: Twelve visitor hours, which may be aggregated continuously, intermittently, or simultaneously by one or more persons. (The term visitor—day is used by the Bureau of Reclamation (BOR) to report use but the data are collected according to the definition of recreation day.)

Water Budget: A part of the Northwest Power Planning Council's Fish and Wildlife Program calling for a volume of water to be reserved and released during the spring, if needed, to assist in the downstream migration of juvenile salmon and steelhead.

Water—Dependent Recreation: Recreation activities for which a body of water is a physical requirement; activities in which water is the medium, e.g., swimming, fishing and boating.

Water—Related Recreation: Recreation activities which do not require a body of water to be undertaken but which are enhanced by association with water; picnicking, sightseeing, nature study, etc. Developing facilities for such activities with a water orientation generally enhances visitors' recreation experiences.

WDW: Washington Department of Wildlife.

Wetlands: Lands that are periodically inundated with the water table at, near or above the soil surface.

TECHNICAL EXHIBIT C

DRAFT EIS RECREATION MODEL

C.1 Methodology

The Impact Assessment Models (IAMs) developed for Federal project sites for the draft EIS assumed that the relationship between reservoir pool elevations (or streamflow) and recreational use is positively correlated. It is hypothesized that as lake elevations decline from full pool, recreation use falls correspondingly. Similarly, full (equivalent to 100 percent of an historical baseline visitation rate) participation is assumed to occur at an optimum flow level unique to a particular river reach and declines as flow either increases/decreases at above/below the optimum level. A simple linear relationship was formulated as:

$$(1) y = fn(x),$$

where,

y = percentage decrease in recreation use,

and,

x = lake elevation (ft) or streamflow (cfs).

As described, break-points in pool elevations or flow levels were established or adopted in, where a physical effect on recreational activities or project attributes is anticipated. These break-points relate changes in reservoir pool elevations (streamflow) to the expected percentage reduction in visitor usage. At or near full pool levels, use is calibrated at 100 percent or a zero percent reduction in participation. For the stream model, optimum flow is the calibrated 100 percent use level.¹ The slope of the line segment between each break-point is then calculated to estimate the percent reduction in use for any given lake elevation or streamflow as follows:

$$(2) y = m(x) + b,$$

where,

y = percent reduction in recreation use,

x = specified lake elevation,

m = slope of line segment $\frac{(y_2 - y_1)}{(x_2 - x_1)}$

and,

b = intercept between line segments.

For a specified lake elevation (or flow level), the estimated reduction in visitor-days can be interpolated from the slope of the graph corresponding to the appropriate line segment (Figure 3-1). Using this percentage from equation (2), an estimate of visitation rates, weighted for seasonality of use, is computed as:

$$(3) v\text{-day} = (h\text{-use}) * (m\text{-use}) * (y)$$

where,

v-day = percent reduction in recreation days for a given type of recreation activity by month and project site,

h-use = historical recreation usage recreation-days for a given recreation activity by month and project site,

m-use = average distribution of historical use for a given recreation activity by month and project site, and

y = percent reduction in recreation usage estimated from equation (2).

The simulation component of the model functions by evaluating the monthly use reduction levels at a specified lake elevation or streamflow against the monthly recreation usage that is estimated to occur

¹ Because of the limited data points, a slope algorithm was thought to reasonably approximate the fit of a linear or curvilinear curve that could alternatively been estimated

if historical average lake elevation levels were to prevail. In this way, a positive or negative monthly change in visitation resulting from any specified lake elevation (or streamflow) can be computed as:

◇ The simulation component of the model functions by evaluating the monthly use reduction levels at a specified lake elevation or streamflow against the monthly recreation usage that is estimated to occur if historical average lake elevation or streamflow levels were to prevail. In this way, a positive or negative monthly change in visitation resulting from any specified lake elevation (or streamflow) can be computed as:

$$(4) \Delta y = y - y^*$$

where,

y = monthly percentage change in recreation usage between historical (1987±1991) and seasonally adjusted use levels for a given elevation or streamflow,

y = monthly percent decrease in recreation usage from (2), and

y^* = estimated monthly percent decrease in usage at historical (1987±1991) lake elevations or streamflows.

By converting y into an absolute number and substituting it into equation (3), the corresponding estimate seasonally adjusted of the monthly recreation visitation (visitor±days) rate is computed. This provides the means to evaluate the positive or negative effects of either drawdowns (curtailments) or refills (enhancements) in reservoir capacity (streamflows) on recreation participation rates. The model computes the estimated monthly visitation rate and corresponding percent reduction and monthly change in visitation, by type of recreation activity. By summing the monthly changes in visitation the model computes the total impact on recreation participation at each project. Such break point curves were developed by project for each of the recreation activities described in ◇. above.

Each SOS was evaluated by incorporating the variability of the 50-year hydrological record in the

appropriate IAM. A designated end-of-month lake elevation or average monthly streamflow was specified by month for each of 49 consecutive water years in the 50-year hydrological record (January 1929 through December 1977). Each model is also structured to capture the effect of uncertainty in the RWG's break-point estimates by allowing the curve in (2) to vary between high and low values (see Figure 3-4), equal to a 50 percent deviation (+ or -) from each of the values established for y . The Supertree probability software was used to execute each IAM, incorporating the uncertainty in hydrological conditions and break-point curves in the probability tree structure. Supertree uses the IAM to compute an estimated expected value of total visitation, expressed as total recreation days at the project being evaluated. To demonstrate the impacts due to extreme hydrological conditions, the IAMs were also executed using the most wet (1976) and fifth-year of the most severe critical period (1941) water years during the 50-year hydrologic cycle used in this analysis.

C.2 SOURCES AND ASSUMPTIONS

The methodology for the recreation IAMs was explained in section C.1. The relationship between lake elevation/streamflow and participation in a particular recreation activity which underlie these models is based on the best professional judgment and knowledge of RWG members, regional recreation planners, and resource managers familiar with each of the project areas. A considerable amount of time and effort was spent to develop and revise the break-point relationships in order to enhance the predictability and credibility of the IAMs. While this approach is not based upon empirical user response (demand) curves that are statistically estimated, the RWG took great care to approximate reality.

This section provides the sources and assumptions applied to develop break-point relationships for each project. The actual break-points developed for each project and their rationale and justification are presented in Technical Exhibit D.

C.2.1 Hungry Horse – Hungry Horse Lake:

The original break-points developed for the Hungry Horse pilot model were based on data from a 1989 Contingent Valuation recreation survey conducted for Reclamation (Ben-Zvi, 1990). One of the primary survey objectives was to estimate a statistical relationship between reservoir levels and recreation use. Reclamation reviewed the Ben-Zvi (1990) results to determine their adequacy and suitability for use in the SOR full-scale analysis. The report, while extremely helpful, was not setup to determine break-points by activity, nor to handle the level of detail being considered in the SOR. Therefore, the Ben-Zvi results were refined and new break-points were developed to apply in full-scale analysis (see Technical Exhibit table D.1). Reclamation considered the following factors in determining new break-points:

A. Access: Drawdown was considered as it affects visitors' ability to access the water and engage in water-based as well as land based uses, such as camping and picnicking. Large drawdown isolates land-based facilities and prompts users to move with the shoreline rather than use the facilities. This has created management problems such as litter, sanitation, site damage, and reductions in visitor use and enjoyment.

B. Proximity to the town of Hungry Horse: According to the US Forest Service, facilities closest to the town of Hungry Horse are heavily used. The shorter the distance traveled the heavier the use. Therefore, Reclamation identified facilities closest to the dam, or the town of Hungry Horse, as most desirable. The condition of the road was also considered a factor that influences site use. Generally, sites along the west side of the reservoir are more heavily used because the access road is paved for 11 miles from the dam along the reservoir. This allows for easier access.

C. Site Facility Composition: US Forest Service information indicates that boat ramps coupled with complementary land-based facilities, such as camping and picnicking, are more desirable and more heavily used than ramps which stand

alone. Therefore, Reclamation noted sites with the most desirable mix of facilities.

D. Slope: Shoreline slope was considered, primarily as it affects swimming. As the reservoir level drops, the shoreline becomes steeper making swimming conditions less safe and less desirable (swimming accounts for roughly 2 percent of the overall use at Hungry Horse, therefore, it is not considered to be a significant activity. The reservoir temperatures are generally considered too cold for enjoyable swimming.)

C.2.2 Libby – Lake Koocanusa:

Original break-points were developed for the initial pilot model that was applied in screening. They were based upon the best professional knowledge and information furnished by project personnel at the Corps Seattle District Office. Empirical data on the effect of low water levels on recreation usage were provided in a Corps document summarizing Lake Koocanusa project operations (Corps, 1988). Additional break-point information was collected from a preliminary document that investigated the effects of reservoir drawdown at Libby (Corps, 1985).

In August 1992 the RWG hosted a public meeting in Libby, Montana, to discuss recreational issues/concerns with the local public and to review the original break-points developed for the Libby pilot model. Representatives from Montana Department of Fish, Wildlife, and Parks, US Forest Service Kootenai National Forest, Libby Chamber of Commerce, and Mariners Haven Resort attended the public information meeting. Based upon public comment, the pilot model break-points were refined to enhance the utility of the Libby IAM applied in full-scale analysis. These revised break-points are presented in Technical Exhibit table D.2.

C.2.3 Libby – Kootenai River:

The Corps Seattle District personnel contacted fishing guides, project operators, and biologists from Montana Department of Fish, Wildlife and Parks to determine appropriate break-points for river recreation occurring on the Kootenai River below

Libby dam. The RWG also received feedback on possible break-point levels for the Kootenai River at the August 1992 meeting in Libby, Montana. Access issues and consideration of the quality of bank fishing and river boating activities were factors influencing the break-points selected for the Kootenai River (see Technical Exhibit table D.3)

C.2.4 Albeni Falls – Lake Pend Oreille

Break-points used in full-scale analysis were established by the Corps in consultation with local agency staff. They were formulated according to specific limitations that are imposed on existing public recreation facilities.

In the case of Lake Pend Oreille, all of the facilities are built for maximum use at full pool. Anything above or below full pool would impact the maximum use of these facilities which is reflected in the restricted range of the break-points. Additional break-point information was collected from the Corps preliminary drawdown investigation at Lake Pend Oreille (Corps, 1985). The full-scale break-points established for Lake Pend Oreille are shown in Technical Exhibit table D.4.

C.2.5 Chief Joseph – Rufus Woods Lake:

Break-points for Rufus Woods Lake were established by the Corps in consultation with the local agency staff. Because the project operates as a run-of-river facility, the lake pool elevations rarely deviate from full pool. Therefore, the range of break-points applied in full-scale modeling reflects this narrow range of pool operations. However, unlike many facilities of a similar nature, the ramps and beaches at the park on Rufus Woods Lake can withstand a greater drawdown than one would anticipate.

The Corps Seattle District Office developed break-points based upon the best professional knowledge and experience of project personnel. Technical Exhibit table D.5 provides the break-points and associated rationale for their development.

C.2.6 Grand Coulee – Lake Roosevelt:

Break-points for pilot analysis were established by Reclamation in consultation with the National Park Service (NPS). They were formulated from studies that determined the types of limitations imposed on existing recreation facilities that accommodate public use (NPS, 1985; Reclamation, 1989). Reclamation and NPS were consulted in summer 1992 to further revise the pilot model break-points to better reflect access and quality issues. The revised break-points were validated in discussions with members of the Lake Roosevelt Forum. The break-points selected for full-scale analysis are given in Technical Exhibit table D.6.

C.2.7 Dworshak/Dworshak Lake – Lower Clearwater River:

Dworshak break-points were developed through the merging of information obtained from several separate reports together with the observations of Dworshak reservoir natural resource managers. Recreation access break point criteria were originally developed by the Corps Walla Walla office and are based upon empirical data on recreation use observed during periods of low pool (Corps, 1988). The access data were further refined during the subsequent 1992 drought season and consequent drawdown at Dworshak. This updated access information was combined with observations and insights on public use provided by Dworshak Lake park managers.

Lower Clearwater River break-points were developed by the Corps Walla Walla office with assistance from on-site managers. This information was supplemented with details provided by the US Forest Service, local retail fishing supply outlets, and biologists from Idaho Department of Fish and Game. Since steelhead fishing accounts for the primary portion of the annual recreational use of the Clearwater River, only one fishing (steelhead) break point activity relationship was estimated and applied in full-scale analysis.

All break-points were reviewed, refined, and finalized by Dworshak reservoir natural resource managers and Corps Walla Walla district staff. Technical

Exhibit table D.7 summarizes full-scale break-points for each recreational activity at Dworshak Lake. Lower Clearwater River break-points for steelhead fishing can be found in Technical Exhibit table D.II.8.

C.2.8 Lower Snake River Projects:

The break-points for recreation activities that occur at the Lower Snake River Projects were developed jointly by the Corps Walla Walla District Office staff and on-site recreation managers. Break-points are based on the physical constraints of the existing facilities and professional knowledge of the preferences and desires of current users. Existing recreation facilities on Lower Snake River reservoirs were constructed and have been further developed to operate within a very narrow range of elevations necessary to maintain navigation and hydroelectric capabilities. The recreation facilities are fully functional and provide public access to the reservoirs at minimal drawdowns of five feet or less. The recreation activity break-points for each Lower Snake River project are found in Technical Exhibit tables D.9 through D.13.

C.2.9 Lower Columbia River Projects:

RWG team members consulted with agencies having primary management responsibility at Bonneville, The Dalles, and John Day reservoirs. Break-points

were established in coordination with resource management staff, project operators, and facility operators (i.e. marina owners) at the respective projects. Technical Exhibit tables D.14 through D.16 present the full-scale break-points for Bonneville, The Dalles, and John Day projects.

C.2.10 Columbia River – Hugh Keenlyside Dam to International Boundary

Break-points were developed for boat fishing, shore fishing, swimming, non-motorized boating, and sightseeing for this Canadian stretch of the Columbia River. Local fishers participating in a fishing diary project sponsored by the Trail (Canada) Wildlife Association were instrumental in developing the break-points for shore and boat fishing. Boat and shore fishing break-points are based on access considerations (usability of launching facilities, hazards, and the availability of shore fishing perches) and an indicator for fishing quality (back eddy structures). Since the bulk of the swimming occurs at the Gyro Park swim rapids, local swimmers who frequent the area were consulted to develop appropriate swimming break-points. Similarly, non-motorized boating and sightseeing break-points were developed through discussions with local river sightseers and nonmotorized boaters in conjunction with hydrologic records. See Technical Exhibit table D.17 for the detailed break-points.

TECHNICAL EXHIBIT D

BREAK POINT TABLES

Table D-1. Hungry Horse Reservoir Break Points

Activity	Optimum	Low Impact	Moderate Impact	High Impact	Severe Impact
General Comments	Full pool 3560'; All facilities on the lake are 100% usable.	Drawdown is noticeable; users may be inconvenienced or have some minor reduction in quality of recreation experience.	There is a significant reduction in water levels but facilities remain useable; effects on aesthetics, quality of recreation experience are significant.	Many recreation facilities become unusable; there is a substantial decline in aesthetics and the quality of recreation experience.	Inaccessible/unusable facilities, safety hazards, poor aesthetics, and other physical constraints nearly or entirely prevent participation in water-related recreation activities.
Boating (All Types)	0 to 2 ft. drawdown All ramps operable; Exposed small beaches provide optimum shoreline access for boats. Boating Use: 100%	> 8 ft. drawdown Nine of eleven boat ramps remain useable. Drawdown becomes noticeable. Boating Use: 98%	> 28 ft. drawdown Six of eleven ramps remain useable. Access down steep ramps become difficult, access to land-based facilities from shoreline becomes inconvenient. Boating Use: 80%	> 60 ft. drawdown Three of eleven ramps remain useable. Access is difficult, aesthetic quality greatly reduced, land-based facilities isolated. Boating Use: 20%	> 130 ft. drawdown All boat ramps on lake unusable. Boating Use: 0%
Fishing (from boat or shore)	0 to 2 ft. drawdown Fishing from shoreline and boats optimum. Fishing Use: 100%	> 8 ft. drawdown Fishing access mostly tied to boating conditions. Shoreline fishing remains good. Fishing Use: 98%	> 28 ft. drawdown Fishing access available by six useable ramps. Shoreline access is more difficult. Fishing Use: 80%	> 60 ft. drawdown Only three of eleven ramps remain operable, restricting fishing use. Shoreline use inconvenient and undesirable. Fishing Use: 20%	> 130 ft. drawdown All boat ramps unusable. No shoreline fishing available. Fishing Use: 0%
Camping & Picnicking	0 to 8 ft. drawdown All day use & campgrounds & beaches are fully useable. Shoreline access at optimum. Aesthetic quality very high. Camp/Picnicking Use: 100%		> 28 ft. drawdown Exposed banks & mudflats leave land based facilities a substantial distance from water. General aesthetic appearance declines. Camp/Picnicking Use: 70%	> 60 ft. drawdown Exposed banks and mudflats isolate land based facilities. Aesthetic appearance substantially reduced. Camp/Picnicking Use: 25%	> 130 ft. drawdown Land based facilities completely isolated from shoreline. Aesthetic quality severely reduced. Remaining camping/day use not directly reservoir dependent. Camp/Picnicking Use: 15%
Swimming	0 to 8 ft. drawdown Swimming beaches and land based facilities fully useable. Optimum shoreline access and high aesthetic quality. Swim Use: 100%		> 28 ft. drawdown Swimming areas are steep and less useable. Access to shoreline difficult. Swim Use: 40%	> 60 ft. drawdown Swimming areas largely unusable. Access to shoreline very difficult. Swim Use: 5%	> 130 ft. drawdown No swimming areas remain. Swim Use: 0%

Table D-2. Lake Koocanusa Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	2459.0 ft.	2434.0 ft.	2409.0 ft.	2384.0 ft.	2287.0 ft.
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Minimum Pool	Minimum Operating Pool
General Comments	Optimum pool elevation for recreation. All recreation facilities are fully usable.	Drawdown is 25 ft. from full. All recreational facilities are impacted.	Drawdown 50 ft. from full pool. Most facilities are marginal usable. Significant impacts.	Drawdown 75 ft. from full. All facilities are severely impacted at this stage.	Drawdown 172 ft. from full. Significant impact to recreation and natural resources
Boating (all types)	All boat ramps are fully usable. Boating Use: 100%	All boat ramps, and all but one marina boat ramp, are fully usable. Boating Use: 80%	3 out of 5 marina boat ramps unusable; 11 of 14 public ramps remain usable Boating Use: 60%	Significant impacts to boating facilities. Only 5 of 14 public ramps are usable. 3 out of 5 marina ramps unusable. Boating Use: 30%	Significant impacts to boating facilities. Only 4 of 14 public ramps are usable. All 5 marina ramps are unusable. Boating Use: 5%
Fishing (boat or shore)	Most fishing occurs from boats, all facilities at full use. Fishing Use: 100%	Normal fluctuation exposes natural beaches & promotes shore access for fishing. Fishing Use: 85%	Low water exposes significant bank areas, beaches and mud flats. Fishing Use: 65%	Some boating facilities unusable; access for fishing constrained. Fishing Use: 55%	Significant impact to boating facilities; fishing access severely constrained. Fishing Use: 5%
Camping/ Picnicking	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Minor reduction in use due to distance from water. Camping/Picnicking Use: 75%	All water-related recreation facilities are fully usable. Major reduction in use due to impacts on ramps & fishing Camping/Picnicking Use: 45%	Significant reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 15%	Continued reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 15%
Swimming	All swimming beaches usable at full pool; natural beaches are at a minimum. Swimming Use: 100%	All developed beaches are unusable. Swimming occurs only at natural beaches. Swimming Use: 10%	All developed beaches are unusable. Swimming occurs only at natural beaches. Swimming Use: 10%	All developed beaches are unusable. Swimming occurs only at natural beaches. Swimming Use: 10%	All developed beaches are unusable. Swimming occurs only at natural beaches. Swimming Use: 10%

Table D-3. Kootenai River Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
River Flows	26,000 CFS	18,000 CFS	12,000 CFS	8,000 CFS	3,000 CFS
Description	Maximum Flows	High Intermediate Flows	Intermediate Flows	Low Intermediate Flows	Minimum Flows
General Comments	This is 14,000 cfs above normal flows. Recreation activities are significantly impacted.	This is 6,000 cfs above normal flows. Boating and bank fishing is significantly impacted.	Optimum flows for recreation. All facilities are fully usable. Minor peaking exposes beaches and improves shoreline access.	All facilities are fully usable. Minor reduction in flows exposes beaches and improves shoreline access.	Minor impact to recreation facilities and natural resources. Extensive shoreline and islands favors shore fishing.
Boating (all types)	All boat ramps, docks, and moorages are unusable. Flows are too high for safe boating. Boating Use: 0%	All boat ramps and docks are still usable. High flows impact boating. Boating Use: 70%	All boat ramps and docks are fully usable. Boating Use: 100%	Several boating facilities become marginally usable due to shallow water conditions. Boating Use: 90%	Low flows make boating and access more difficult. Boating Use: 70%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access extremely difficult from full banks. Fishing Use: 0%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 100%	River and shore fishing is at its maximum in this range. Fishing Use: 100%	Power peaking exposes small beaches & promotes shore access for fishing. Fishing Use: 90%	Significant impact to boating facilities; fishing access is best due to ease of access Fishing Use: 70%
Camping/Picnicking	All water-related recreation facilities are fully usable. Height flows discourage bank fishing and boating. Camping/Picnicking Use: 25%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	Minor reduction in land-based recreation due to impacts to boating, fishing. Camping/Picnicking Use: 90%	Continued reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 80%

Table D-4. Lake Pend Oreille Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	2067.5 ft.	2062.5 ft.	2056.7 ft.	2051.0 ft.	2049.7 ft.
Description	Maximum Pool	Normal Maximum Operating Pool	Intermediate Pool	Normal Minimum Pool	Minimum Operating Pool
General Comments	This is 5.0 ft. above the normal maximum operation pool. Most recreation facilities submerged.	Optimum pool elevation for recreation. All facilities fully usable.	Drawdown 5.8 ft. from full; Most facilities remain fully usable. Impact on fixed facilities.	Drawdown 11.5 ft. from full; bottom end of normal daily fluctuation. Significant effects on recreation facilities & resources.	Drawdown 12.8 ft. from full; Significant impact to recreation facilities and resources. Extensive exposure of bank areas potential dust problems.
Boating (all types)	All boat ramps, docks, moorages & marinas are unusable. Minor use by boaters doing walk-ins. Boating Use: 10%	All boat ramps, docks, moorages & marinas fully usable. Boating Use: 100%	All boat ramps, moorages & marinas fully usable. However, fixed docks are unusable at this elev. Boating Use: 75%	Several boating facilities become marginally usable due to shallow water conditions; All docks become unusable. Boating Use: 25%	Significant impacts to boating facilities. Only 2 out of 10 ramps are usable. No marina facilities usable Boating Use: 25%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access more difficult at full pool. Fishing Use: 50%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 100%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 70%	Most boating facilities unusable; access for fishing slightly constrained. Fishing Use: 30%	Significant impact to boating facilities; fishing access severely constrained. Fishing Use: 15%
Camping/Picnicking	 Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. However, facilities are much further from the water. Camping/Picnicking Use: 30%	Continued impacts to recreation facilities, however, visitation has stabilized at a much reduced rate. Significant ring effect. Camping/Picnicking Use: 30%	Continued impacts to recreation activities, however, visitation still stable. Camping/Picnicking Use: 30%
Swimming	All swimming beaches unusable at max pool. Natural beaches do not exist. Swimming Use: 25%	All 9 public beaches are fully usable. Swimming Use: 100%	All 9 public beaches are marginally usable. Swimming Use: 30%	All 9 public beaches are now unusable; too far from water. Swimming use confined to undeveloped beaches. Swimming Use: 20%	All 9 public beaches remain unusable. Extensive mud flats visible. Swimming Use: 10%

Table D-5. Rufus Woods Lake Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	958.8 ft.	956.0 ft.	951.0 ft.	2051.0 ft.	2049.7 ft.
Description	Maximum Pool	Normal Maximum Operating Pool	Intermediate Pool	Normal Minimum Pool	Minimum Operating Pool
General Comments	This is 2.8 ft. above maximum operating pool. All recreation facilities fully usable.	Optimum pool elevation for recreation. All facilities fully usable. Minor drawdown exposes beaches and improves shoreline access.	Drawdown 5.0 ft. from full. Most facilities remain fully usable; no significant effect.	Drawdown 10.0 ft. from full. Significant effects on recreation facilities & resources.	Drawdown 26 ft. from full pool. Significant impact on recreation facilities.
Boating (all types)	All boat ramps and docks are fully usable. Boating Use: 100%	All boat ramps, docks, moorages & marinas fully usable. Boating Use: 100%	All boat ramps and docks are fully usable. Longer backing down ramps causes slight reduction of use. Boating Use: 95%	Several boating facilities become marginally usable due to shallow water conditions. Boating Use: 90%	Significant impacts to boating facilities. No ramps are available. Boating Use: 30%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access more difficult at full pool. Fishing Use: 90%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 100%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 80%	Some boating facilities unusable; access for fishing slightly constrained. Fishing Use: 30%	Significant impact to boating facilities; fishing access severely constrained. Fishing Use: 20%
Camping/ Picnicking	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	Minor reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 80%	Major reduction of activities reservoir at levels not normally seen. Bank exposure extreme and unsightly. Camping/Picnicking Use: 25%
Swimming	The swimming beach is usable; however, high water reduces beach area. Swimming Use: 90%	Swimming beach at State Park remains usable. Swimming Use: 100%	Swimming beach at State Park remains usable. Swimming Use: 90%	Swimming beach at State Park remains usable; water depths in some are near minimum. Swimming Use: 50%	One developed beach is totally unusable. Swimming may occur at newly exposed natural beaches. Swimming Use: 10%

Table D-6. Lake Roosevelt Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	1290.0 ft.	1285.0 ft.	1280.0 ft.	1250.0 ft.	1234.0 ft.
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Minimum Pool	Minimum Operating Pool
General Comments	Full pool not optimum as debris lodged at high water line is refloated and becomes a problem to boaters. More sandy beaches available with minor drawdown. Optimum pool is 1288 ft.	Drawdown is five feet from full, debris is stranded at high pool, swimming beaches are impacted, natural beaches are exposed.	Drawdown 10.0 ft. is at lower and of historic summer fluctuation. Major negative impacts begin to occur.	Drawdown 40.0 ft. below full pool. All recreation facilities and marina service severely impacted.	Drawdown 56 ft. from full pool. Most water based facilities are out of service.
Boating (all types)	All boat ramps and docks are fully usable. Floating debris is a deterrent to boating. Boating Use: 95%	All boat facilities available; shoreline beaches exposed. Boating Use: 85%	Three small launch ramps in—operable; all other boating facilities usable. Some minor inconvenience at launching and parking sites. Boating Use: 85%	Launch lanes are reduced by more than half. Most docks out of service. One major marina is out of business. Boating Use: 50%	Only four narrow launch ramps in service. Docks and marina services unavailable. Boating Use: 15%
Fishing (boat or shore)	Floating debris is a minor deterrent to fishing. All facilities usable. Fishing Use: 95%	Minimum debris on watersurface; shoreline easily accessible; all facilities available. Fishing Use: 100%	Lake access is impacted for shore and boat anglers. Fishing Use: 85%	Water access severely hampered for boat and shore anglers. Resident fish stocks diminished. Fishing Use: 50%	Lake access very difficult. Negative impacts on resident fish populations. Marinas are inoperable. Fishing Use: 10%
Camping/Picnicking	All water—related recreation facilities are fully usable. Some Camping/Picnicking Use: 100%	All facilities operable; lakeshore easily accessible from camping and day use areas. Camping/Picnicking Use: 100%	Water surface is farther away from developed camping and picnicking areas. Negative effect on aesthetics. Camping/Picnicking Use: 90%	Water surface long distance from camping and picnic facilities. Aesthetics adversely affected by large drawdown band. Camping/Picnicking Use: 60%	Long distance from camping and day use facilities to lake. No developed swim areas in service. Poor aesthetic quality. Few boating facilities. Camping/Picnicking Use: 50%
Swimming	All designated swimming areas fully usable. Swimming Use: 90%	Some swim hazards at developed swim areas. Shallow water under swim floats hazardous to divers. Swim areas within boom floats diminished. Swimming Use: 75%	Designated swimming areas are greatly diminished in size; swim platforms unusable. Long distance from turf and shaded areas to water surface. Swimming Use: 25%	All developed swimming areas are exposed and essentially unusable. Swimming Use: 0%	All developed swim areas are unusable and high and dry. Swimming Use: 0%

Table D-7. Dworshak Lake Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	1600 ft. NGVD	1585 ft. NGVD	1575 ft. NGVD	1550 ft. NGVD	1445 ft. NGVD
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Minimum Pool	Minimum Operating Pool
General Comments	Optimum lake elevation for recreation. All recreation facilities are fully usable.	Drawdown is 15 ft. from full. Some impact to specific recreation activities and uses. Use by persons with disabilities severely impacted.	Drawdown 25 ft. from full. Most recreation facilities are impacted. Significant impact to most water related recreation uses.	Drawdown 50 ft. from full. All recreation facilities are significantly impacted at this lake elevation.	Drawdown 155 ft. from full. All recreation facilities are fully impacted, resulting in minimal public recreation value.
Boating (all types)	All boat ramps, docks, and marina moorage fully usable. Boating Use: 100%	All boat ramps, docks and marina moorage fully usable. Boating Use: 85%	All boat ramps, docks and marina moorage fully usable. Access to docks difficult. Long back-up required on all ramps. Boating Use: 70%	All docks unusable, 2 of 7 boat ramps are dry and unusable. Marina moorage usable, with access difficult. Boating Use: 25%	Only 1 boat ramp usable (Big Eddy), requires long backup down steep slope. Many hazards - stumps, shoals, islands - exposed. Boating Use: 0%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access slightly impaired at highest lake elevation. Fishing Use: 100%	Exposed shoreline hazards and mudflats, not a serious constraint at this point. Fishing Use: 90%	Boat access more difficult. Shoreline access requires crossing exposed mudflats. Fishing Use: 70%	Boat access difficult, shoreline fishing requires crossing exposed mudflats and/or steep slopes. Fishing Use: 25%	Only 1 boat ramp usable. Shoreline fishing access severely constrained. Fishing Use: 10%
Camping/ Picnicking	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	About half of mini-camps unusable due to steep, muddy shoreline. Access from land-based facilities to shoreline impaired. Camping/Picnicking Use: 80%	Majority of mini-camps unusable. Access from land-based facilities constrained. Camping/Picnicking Use: 50%	Access to all mini-camps is eliminated. Minimal boat-in camping occurs. Camping/Picnicking Use: 25%	Boating-related camping and access from shoreline facilities is virtually eliminated. Camping/Picnicking Use: 10%
Swimming	All swimming beaches usable at maximum lake elevation. Swimming Use: 100%	Both swim beaches unusable at lake elevations below 10 feet of full. Swimming Use: 20%	Swimming beaches unusable, shoreline swimming access difficult. Swimming Use: 10%	Minimal swimming use. Swimming Use: 0%	Minimal swimming use. Swimming Use: 0%

Table D-8. Lower Clearwater River Steelhead Fishing Break Points (Based on Dworshak Outflows)

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Outflow	12,000 CFS	10,000 CFS	7,000 CFS	3,000 CFS	2,000 CFS
Description	Maximum Recreation Flow	Highest Optimum Flow	High Optimum Recreation Flow	Low Recreation Flow	Minimum Recreation Flow
General Comments	Maximum recreation outflow from Dworshak Dam. Higher flows cause severe impacts to recreation facilities and use.	High end of optimum outflow for recreation. Some constraints on access and facilities.	High optimum outflow for recreation. Facilities and access fully usable.	Optimum outflow for recreation. Facilities and access fully usable.	Minimum recreation outflow for public use. Lower outflows impact recreation facilities and access.
Fishing (boat or shore)	Shoreline access difficult at high flows. Significantly increased hazards to both boat and shore anglers. Fishing Use: 10%	Exposed shoreline and small beaches promotes shore access for fishing. Good conditions for boat fishing. Fishing Use: 60%	Good exposure for shoreline access. Conditions good for shoreline and boat steelhead fishing. Fishing Use: 90%	Excellent conditions for both boat and shoreline fishing. Fishing Use: 100%	Significant impact to boating facilities. Shoreline access excellent with few constraints. Fishing Use: 40%

Table D-9. Lower Granite Lake Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	738 ft. NGVD	736 ft. NGVD	735 ft. NGVD	734 ft. NGVD	733 ft. NGVD
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Minimum Pool	Minimum Operating Pool
General Comments	Normal maximum lake operating elevation. All recreation facilities fully usable.	Optimum lake elevation for recreation. All facilities fully usable. Minor drawdown exposes beaches and improves shoreline access.	Drawdown 3 feet from full. Within normal operations. Most facilities remain fully usable, no significant effect.	Drawdown 4 feet below full. Low end of normal range of fluctuations. Some effects on recreation facilities and resources.	Elevations lower than 5 feet below full have significant ties. Severe impact on use by persons with disabilities.
Boating (all types)	All boat ramps, docks, and marinas fully usable. Boating Use: 100%	All boat ramps, docks and marina moorage fully usable. Boating Use: 100%	All boat ramps, docks and marina moorage fully usable. Boating Use: 80%	Several boating facilities become marginally usable due to shallow water conditions. Boating Use: 80%	Significant impacts to boating facilities. All but one boat ramp unusable. Channels into marinas are partially blocked below elevation 733 feet. Boating Use: 10%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access is good at full lake level. Fishing Use: 100%	Normal fluctuation exposes small beaches and promotes shore access for fishing. Fishing Use: 100%	Normal fluctuation exposes small beaches and promotes shore access for fishing. Fishing Use: 80%	Some boating facilities unusable. Access for fishing slightly constrained. Fishing Use: 80%	Significant impact to boating facilities. Fishing access using boats is highly impacted. Fishing Use: 10%
Camping/ Picnicking	All water--related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water--related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water--related recreation facilities are fully usable. Camping/Picnicking Use: 95%	Minor reduction in land--based recreation due to impacts to boating, fishing, swimming and waterskiing. Camping/Picnicking Use: 95%	Continued reduction in land--based recreation due to impacts to boating, fishing, swimming and waterskiing. Camping/Picnicking Use: 80%
Swimming	Developed swimming beaches usable at full lake, most natural beaches are covered with water. Swimming Use: 100%	Developed swim beaches remain fully usable. Natural beaches are exposed and usable. Swimming Use: 100%	All developed and natural beaches are fully usable. Swimming Use: 75%	Developed and natural beaches remain usable. Exposed mud--flats at developed beaches create marginal conditions. Swimming Use: 75%	Developed swimming beaches are unusable. Natural beaches remain usable, although access is poor. Swimming Use: 0%

Table D-10. Little Goose/Lake Bryan Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	638 ft. NGVD	636 ft. NGVD	635 ft. NGVD	634 ft. NGVD	633 ft. NGVD
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Minimum Pool	Minimum Operating Pool
General Comments	Normal maximum lake operating elevation. All recreation facilities fully usable.	Optimum lake elevation for recreation. All facilities fully usable. Minor drawdown exposes beaches and improves shoreline access.	Drawdown 3 feet from full. Within normal operations. Most facilities remain fully usable; no significant effect.	Drawdown 4 feet below full. Low end of normal range of fluctuations. Some effects on recreation facilities and resources.	Elevations lower than 5 feet below full have significant effects on recreation facilities. Severe impact to use by persons with disabilities.
Boating (all types)	All boat ramps, docks and marinas fully usable. Boating Use: 100%	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 100%	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 70%	Several boating facilities become marginally usable due to shallow water conditions. Boating Use: 70%	Significant impacts to boating facilities. All boat ramps unusable. Channel entrance to both marinas partially blocked at 633 ft. Boating Use: 25%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access is good at full lake level. Fishing Use: 100%	Normal fluctuation exposes small beaches and promotes shore access for fishing. Fishing Use: 100%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 70%	Some boating facilities unusable. Access for fishing slightly constrained Fishing Use: 70%	Significant impact to boating facilities. Fishing access using boats is highly impacted. Fishing Use: 25%
Camping/Picnicking	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 95%	Minor reduction in land-based recreation due to impacts to boating, fishing, swimming and waterskiing. Camping/Picnicking Use: 95%	Continued reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 80%
Swimming	Developed swim beaches remain fully usable. Natural beaches are exposed and usable. Swimming Use: 100%	All developed and natural beaches are fully usable. Swimming Use: 100%	All developed and natural beaches are fully usable Swimming Use: 75%	Developed and natural beaches remain usable. Exposed mud-flats at developed beaches create marginal conditions. Swimming Use: 75%	Developed swimming beaches are unusable. Natural beaches remain usable, although access is poor. Swimming Use: 0%

Table D-11. Lower Monumental/Lake West Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	540 ft. NGVD	539 ft. NGVD	538 ft. NGVD	537 ft. NGVD	536 ft. NGVD
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Minimum Pool	Minimum Operating Pool
General Comments	Normal maximum lake operating elevation. All recreation facilities fully usable.	Optimum lake elevation for recreation. All facilities fully usable. Minor drawdown exposes beaches and improves shoreline access.	Drawdown 2 feet from full. Within normal operations. Most facilities remain fully usable; no significant effect.	Drawdown 3 feet below full. Low end of normal range of fluctuations. Some effects on recreation facilities and resources.	Elevations any lower than 4 feet below full have significant effects on recreation facilities. Severe impact to use by persons with disabilities.
Boating (all types)	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 100%	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 100%	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 90%	Several boating facilities become marginally usable due to shallow water conditions. Boating Use: 90%	Significant impacts to boating facilities. All boat ramps unusable. Marina hoist not usable below 536 ft., marina starts grounding at 531. Boating Use: 25%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access is good at full lake level. Fishing Use: 100%	Normal fluctuation exposes small beaches and promotes shore access for fishing. Fishing Use: 100%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 90%	Some boating facilities unusable. Access for fishing slightly constrained. Fishing Use: 90%	Significant impact to boating facilities. Fishing access using boats is highly impacted. Fishing Use: 25%
Camping/ Picnicking	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 90%	Minor reduction in land-based recreation due to impacts to boating, fishing, swimming and waterskiing. Camping/Picnicking Use: 90%	Continued reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 75%
Swimming	Swim beach at Lyons Ferry usable at full lake, most natural beaches are covered with water. Swimming Use: 100%	Developed swim beach remains fully usable. Natural beaches are exposed and usable. Swimming Use: 95%	All developed and natural beaches are fully usable Swimming Use: 70%	Developed and natural beaches remain usable. Some exposed mud-flats at developed beaches create poor conditions. Swimming Use: 70%	Developed swimming beach is unusable. Natural beaches remain usable, although access is poor. Swimming Use: 20%

Table D-12. Ice Harbor/Lake Sacajawea Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	440 ft. NGVD	439 ft. NGVD	438 ft. NGVD	437 ft. NGVD	436 ft. NGVD
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Minimum Pool	Minimum Operating Pool
General Comments	Normal maximum lake operating elevation. All recreation facilities fully usable.	Optimum lake elevation for recreation. All facilities fully usable. Minor drawdown exposes beaches and improves shoreline access.	Drawdown 2 feet from full. Within normal operations. Most facilities remain fully usable; no significant effect.	Drawdown 3 feet below full. Low end of normal range of fluctuations. Some effects on recreation facilities and resources.	Elevations any lower than 4 feet below full have significant effects on recreation facilities. Severe impact to use by persons with disabilities.
Boating (all types)	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 100%	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 100%	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 85%	Several boating facilities become marginally usable due to shallow water conditions. Boating Use: 85%	Significant impacts to boating facilities. All boat ramps unusable. Sandbar blocks boats from marina at 6' below full. Boating Use: 20%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access is good at full lake. Fishing Use: 100%	Normal fluctuation exposes small beaches and promotes shore access for fishing. Fishing Use: 100%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 85%	Some boating facilities unusable. Access for fishing slightly constrained. Fishing Use: 85%	Significant impact to boating facilities. Fishing access using boats is highly impacted. Fishing Use: 25%
Camping/ Picnicking	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 90%	Minor reduction in land-based recreation due to impacts to boating, fishing, swimming and waterskiing. Camping/Picnicking Use: 90%	Continued reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 75%
Swimming	All swimming beaches usable at full lake, natural beaches are at a minimum.. Swimming Use: 100%	All developed swimming beaches remain fully usable. Natural beaches are exposed. Swimming Use: 100%	All developed and natural beaches are fully usable Swimming Use: 90%	Developed and natural beaches remain usable. Some exposed mud-flats at developed beaches create poor conditions. Swimming Use: 90%	All developed swimming beaches are unusable. Natural beaches remain usable, although access is poor. Swimming Use: 20%

Table D-13. McNary/Lake Wallula Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	340 ft. NGVD	339 ft. NGVD	338 ft. NGVD	337 ft. NGVD	336 ft. NGVD
Description	Maximum Pool	Intermediate Pool	Lower Intermediate Pool	Minimum Pool	Minimum Operating Pool
General Comments	Normal maximum lake operating elevation. All recreation facilities fully usable.	Optimum lake elevation for recreation. All facilities fully usable. Minor drawdown exposes beaches and improves shoreline access.	Drawdown 3 feet from full. Within normal operations. Most facilities remain fully usable; no significant effect.	Drawdown 4 feet below full. Low end of normal range of fluctuations. Some effects on recreation facilities and resources.	Significant impact to recreation facilities and resources. Severe impact to use by persons with disabilities.
Boating (all types)	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 100%	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 100%	All boat ramps, docks, moorages and marinas fully usable. Boating Use: 100%	Several boating facilities become marginally usable due to shallow water conditions. Boating Use: 100%	Significant impacts to boating facilities. All boat ramps unusable. Boating Use: 20%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access is good at full lake. Fishing Use: 100%	Normal fluctuation exposes small beaches and promotes shore access for fishing. Fishing Use: 100%	Normal fluctuation exposes small beaches & promotes shore access for fishing. Fishing Use: 100%	Some boating facilities unusable. Access for fishing slightly constrained. Fishing Use: 100%	Significant impact to boating facilities. Fishing access using boats is highly impacted. Fishing Use: 20%
Camping/Picnicking	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 100%	Minor reduction in land-based recreation due to impacts to boating, fishing, swimming and waterskiing. Camping/Picnicking Use: 100%	Continued reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 65%
Swimming	All swimming beaches usable at full lake, natural beaches are at a minimum.. Swimming Use: 100%	All developed swimming beaches remain fully usable. Natural beaches are exposed. Swimming Use: 100%	All developed and natural beaches are fully usable Swimming Use: 60%	Developed and natural beaches remain usable. Some exposed mud-flats at developed beaches create poor conditions. Swimming Use: 60%	All developed swimming beaches are unusable. Natural beaches remain usable, although access is poor. Swimming Use: 0%

Table D-14. John Day/Lake Umatilla Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Pool Elev.	268.0 ft. NGVD	265.0 ft. NGVD	262.0 ft. NGVD	260 ft. NGVD	257 ft. NGVD
Description	Normal Maximum Pool (Summers)	Normal Summer Minimum Pool and Winter Maximum Pool	Intermediate Pool; drawdown 6 feet from full.	Normal Minimum Winter Pool; drawdown 6 ft from full Minimum Pool	Minimum Operating Pool
General Comments	All recreation facilities on lake are 100% usable using boats is highly impacted.	Bottom end of normal range of summer operations; all recreation facilities remain 100% usable.	Most recreation facilities initially designed to be operational at this pool; Some impacts begin to appear.	Significant impacts to recreation facilities occur below elev. 262.	Most existing recreation facilities are unusable below elevation 257.
Boating (all types)	All boat ramps, marinas, docks & other facilities fully usable Boating Use: 100%	All boating facilities remain usable. Boating Use: 100%	2 of 13 boat ramps & 2 of 17 boat docks become unusable. Boating Use: 90%	Significant impact to boating facilities; only 2 of 13 boat ramps and 11 of 17 boat docks remain usable. Boating Use: 70%	Severe impact to boating facilities; only 2 of 13 boatramps; 8 of 17 boat docks; & 2 of 3 marinas remain usable. Boating Use: 50%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access more difficult at full pool. Fishing Use: 90%	Normal fluctuation exposes small beaches and promotes shore access for fishing. Fishing Use: 100%	Some boating facilities unusable. Access for fishing slightly constrained. Fishing Use: 90%	Significant impact to boating facilities. Fishing access moderately constrained. Fishing Use: 70%	Significant impact to boating facilities. Fishing access severely constrained. Fishing Use: 50%
Camping/ Picnicking	All water--related recreation facilities are fully usable. Camping/Picnicking Use: 100%	All water--related recreation facilities are fully usable. Camping/Picnicking Use: 100%	Some reduction in land--based recreation associated with loss in usability of water--based facilities. Camping/Picnicking Use: 90%	Continued reduction in land--based recreation with loss in usability of water--based facilities. Camping/Picnicking Use: 80%	Reduction in land--based recreation with loss in usability of water--based facilities. Camping/Picnicking Use: 80%
Swimming	All swimming beaches usable at full pool, natural beaches are at a minimum. Swimming Use: 90%	All 11 developed beaches remain fully usable. Swimming Use: 100%	10 of 11 swimming beaches remain usable. Swimming Use: 90%	7 of 11 swimming beaches remain usable; water depths in some are near minimum. Swimming Use: 70%	All 11 swimming beaches unusable. Swimming Use: 50%

Table D-15. The Dalles/Lake Celilo Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Flows (from JOHN DAY Dam)	Greater than 350,000 CFS Spring Flood Flows	250,000 to 350,000 CFS Typ. Spring/Early Summer Flows	150,000 to 250,000 CFS Optimum Recreation Flows	100,000 to 150,000 CFS Normal Late Summer Flows	Less than 100,000 CFS Very Low Late Summer Flows
General Comments	High Spring Flood Flows. High flows may flood out some recreation facilities and create boating and other safety hazards.	Typical spring/early summer flood flows. Most facilities fully usable. Flows toward the high end of this range may inundate beaches and constrain some access.	Typical mid-summer flows; optimum for recreation with all facilities fully usable and good shoreline access less marginally usable.	Typical late summer/early fall flows. Some minor impacts to recreation use and access.	Very low late summer or fall flows.
Boating (all types)	Some boating facilities, i.e. boat ramps, docks, moorages & marinas, may be inundated. High flows create boating hazard. Boating Use: 75%	All boat ramps, docks, moorages & marinas fully usable. Flows toward the high end of this range may create some boating hazards. Boating Use: 90%	All boat ramps, docks, moorages & marinas fully usable. No special hazards related to flows. Rocks, trees, stumps & shoals create navigation hazards. Boating Use: 100%	Several boating facilities become marginally usable due to shallow water conditions; Some boating hazards exposed. Boating Use: 95%	Significant impacts to boating facilities; ramps, docks, marinas become marginally usable or unusable. Boating Use: 70%
Fishing (boat or shore)	Most fishing occurs from boats. Shoreline access difficult and hazardous full. Fishing Use: 100%	Flows toward the high end of this range may inundate some shoreline fishing access areas. Fishing Use: 100%	Normal flows expose beaches and access points & promotes shore access for fishing. Fishing Use: 100%	Some boating facilities unusable; access for fishing slightly constrained. Fishing Use: 95%	Significant impact to boating facilities; fishing access constrained. Fishing Use: 70%
Camping/Picnicking	All water-related recreation facilities are fully usable. Some decline associated with impacts to water-related activities. Camping/Picnicking Use: 90%	All water-related recreation facilities are fully usable. Camping/Picnicking Use: 90%	All water-related recreation facilities are fully usable. Impacts to boating, fishing, swimming, & windsurfing. Camping/Picnicking Use: 90%	Minor reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 90%	Continued reduction in land-based recreation due to impacts to boating, fishing, swimming, & waterskiing. Camping/Picnicking Use: 90%
Swimming	Most improved and unimproved swimming beaches inundated; high flows and cold water create swimming hazards. Swimming Use: 10%	All 8 developed beaches fully usable at low end of this range; may be inundated at higher end. Swimming Use: 10%	All 8 developed beaches fully usable; good access from unimproved shoreline beaches. Swimming Use: 10%	Low flows may leave some swimming beaches marginally usable. Swimming Use: 10%	Many developed and unimproved beaches unusable. Swimming Use: 10%
Windsurfing	Experts desire high flows, however, many beaches/access points inundated. Safety hazards for novice and beginner windsurfers. Windsurfing Use: 90%	Most windsurf beaches usable at high flows. High pool and high velocity flow conditions preferred. Windsurfing Use: 100%	All windsurf beaches remain fully usable. Areas constrained by shallow water. Rocks, stumps, shoals and other hazards appear. Windsurfing Use: 100%	Reduced pool elevations and/or velocities less desirable. Rocks, stumps, shoals and debris exposed. Windsurfing Use: 100%	Reduced pool elevations and/or velocities less desirable. Rocks, stumps, shoals and debris exposed. Windsurfing Use: 100%

Table D-16. Canadian Columbia River Reach Break Points

Degree of Recreational Impact at Varying Operational Ranges (Break Points) (i.e., Timing/Degree of Reservoir Fluctuation/Downstream Flow)					
Flows (from Keenleyside Dam)	LOW IMPACT 1/	MODERATE IMPACT 2/	HIGH IMPACT 3/	SEVERE IMPACT 4/	GENERAL COMMENTS
Swimming	2,200 to 2,800 cms No significant impact. Optimal flows at Gyro Park swim rapids. Swimming Use: 100%	2,900 cms Swimming Use: 100%	2,000 to 2,100 cms Swimming Use: 65% 3,000 to 3,100 cms Swimming Use: 100%	Below 2,000 cms Swimming Use: 30% Above 3,100 cms Swimming Use: 100%	Camping/Picnicking Use: 90%
Sightseeing	400 to 2,900 cms No significant effect on boating use.	3,000 to 3,700 cms Sightseeing Use: 90%	4,100 to 6,000 cms Sightseeing Use: 75%		Higher flows flood walking trails and islands.
Boating (unmotorized canoeing, etc)	2,000 to 2,900 cms No significant effect on boating use.	1,900 cms and below Boating Use: 90%	3,200 cms Boating Use: 80%	4,400 cms and above Flows are dangerously high. Boating Use: 0% Boat Fish Use: 90%	Unmotorized boating affected mostly by hazards associated with high flows.
Boat Fishing	2,000 to 4,400 cms No significant effect on boating use.	1,700 to 1,900 cms Partial loss of access to boat launch at Indian Eddy. Boat Fish Use: 90%	Flows of 1,400 and 4,800 cms Boat Fish Use: 90%	1,100 cms Boat Fish Use: 50% 5,100 cms Boat Fish Use: 90%	Boat fishing affected by boat access.
Shore Fishing	1,700 to 2,800 cms No significant effect on boating use.	Flow of 1,500 cms Shore Fish Use: 85% Flows of 3,300 cms Shore Fish Use: 83%	Flow of 1,000 cms Shore Fish Use: 47.5% Flows of 4,300 cms Shore Fish Use: 4.8%	800 cms and below Shore Fish Use: 32.5% Shore Fish Use: 4.8%	Shore fishing is affected by access to fishing perches along the river bank.
1/ Low Impact – Recreation users may be inconvenient or have minor reduction in the quality of recreation experiences. 2/ Moderate Impact – Significant reduction or increase in flows, but facilities remain usable; some effects on aesthetics and quality of experience. 3/ High Impact – Some project facilities (boat ramps, docks, marinas, swim beaches) become unusable; significant reduction in quality of experience and aesthetics. 4/ Severe Impact – Inaccessible facilities, safety hazards, or other physical constraints may nearly or entirely prevent participation in water-related recreation.					