CONTRACTOR REPORT

SAND98-2372

Unlimited Release

Faraday Rotation Measurements on Z-Pinches Final Report

John B. Greenley
Laboratory of Plasma Studies
Cornell University
369 Upson Hall
Ithaca, NY 14853

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia is a multiprogram laboratory operated by Sandia Corporation,
a Lockheed Martin Company, for the United States Department of
Energy under Contract DE-AC04-94AL85000.

Approved for public release; distribution is unlimited.

Printed October 1998

Sandia National Laboratories

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831

Prices available from (615) 576-8401, FTS 626-8401

Available to the public from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Rd
Springfield, VA 22161

NTIS price codes
Printed copy: A03
Microfiche copy: A01

DISCLAIMER

**Portions of this document may be illegible
electronic image products. Images are
produced from the best available original
document.**

SAND98-2372
Unlimited Release
Printed October 1998

Faraday Rotation Measurements on Z-Pinches Final Report*

John B. Greenley

Laboratory of Plasma Studies
Cornell University
369 Upson Hall
Ithaca, NY 14853

Abstract

The Campus Executive Program sponsored this research at Cornell University. The research was directed toward the implementation of laser-based diagnostics for wire-array Z-pinches. Under this contract we were able to carry out all the necessary preparations to set up the laser diagnostics to complement our x-ray backlighting measurements of the early phase of exploding wire z-pinch plasma formation.

*The work described in this report was performed for Sandia National Laboratories under Contract No. AX2329.

Introduction

The Campus Executive Program sponsored this research at Cornell University. The work carried out under this contract from May 1998 through September 1998 was directed toward the implementation of laser-based diagnostics for wire-array Z-pinches. These new diagnostics will augment the capabilities of our present x-ray backlighting diagnostic to allow simultaneous laser illumination and x-ray backlighting of wire plasmas. Initially, schlieren imaging and interferometry with the laser will allow measurement of lower plasma densities than the x-ray backlighter. Eventually we hope to implement polarimetry ("Faraday rotation") to determine the magnetic field profile and therefore the current density profile flowing in the wire plasmas. This contract funded the initial steps toward these goals.

Diagnostic Development

We first determined the laser parameters needed for these laser-based techniques in combination. We next compared commercially available Nd-YAG lasers within our budget, and ordered a laser from Continuum Corp., model Surelite1, 400 mJ. Although the nominal minimum laser pulse width is 4 ns, we were able to arrange with the manufacturer for an operating procedure which permits a 2 ns pulse in frequency-tripled light to be included within the warranted operating conditions because of our low intended pulse repetition rate (1pps).

Beginning in June, the laboratory space around our z-pinch experimental system was reorganized to allow the laser diagnostics to be added. Optical tables were installed for the laser and several required optical trains. Laser safety requirements necessitated modification of the lab space to install a full light shield around the experimental area.

The Nd-YAG laser arrived in mid-July while the laboratory preparation was in progress. The laser was first pulsed before the end of July. It is set up to operate in either the fundamental, first or second harmonic modes, and we can also use any of them in combination. After satisfactory laser operation in the first harmonic was established, measurements of laser trigger throughput delay were made to determine possible approaches for the design of a system to trigger the laser with minimum possible time jitter with respect to the wire array current pulse and the x-ray backlighter. This design was not straightforward because this laser, which was the only one available within our budget constraint having the required optical parameter for our applications, is supplied only in a configuration which is intended to be used in a free-run, repetitive pulse mode of operation. However, we must synchronize a single laser pulse with the x-ray backlighter pulsed power system. A design for the trigger system was decided upon which selects a pulse from the free-running repetitive firing of the laser flashlamp to trigger the wire array current pulse and the x-ray backlighter driver when both are fully charged. The trigger for the laser Q-switch (Pockels cell) is then generated from a current monitor located after the main output switch of the x-ray backlighter driver, which minimizes jitter between the backlighter and the laser. We have determined that

the Pockels cell trigger throughput delay is just short enough to allow this ideal low-jitter mode of operation. This system was designed in September, and is presently being constructed. First testing of the integrated system will be done shortly.

Conclusion

Under this contract we were able to carry out all the necessary preparations to set up the laser diagnostics to complement our x-ray backlighting measurements of the early phase of exploding wire z-pinch plasma formation. We are now taking the initial steps to integrate the laser into the existing experimental system.

Distribution

2 Cornell University
Laboratory of Plasma Studies
Attn: D. A. Hammer
 J. B. Greenly
369 Upson Hall
Ithaca, NY 14853

1	MS0151	G. Yonas, 9000
1	MS1190	D. Cook, 9500
1	MS1191	J. Quintenz, 9502
1	MS1194	R. Spielman, 9544
1	MS1187	M. Matzen, 9570
1	MS9018	Central Technical Files, 8940-2
2	MS0899	Technical Library, 4916
1	MS0619	Review & Approval Desk, 15102 For DOE/OSTI