~~XXXX~~ RMIS View/Print Document Cover Sheet ~~XXXX~~

This document was retrieved from the Boeing ISEARCH System.

Accession #: D196055030

Document #: SD-WM-ER-512

Title/Desc:

TANK 241U203 HEADSPACE GAS & VAPOR
CHARACTERIZATION RESULTS FOR SAMPLES COLLECTED IN
8/1995

SEP 28 1995

ENGINEERING DATA TRANSMITTAL

Page 1 of 1

1. EDT No 613583

2. To: (Receiving Organization) DISTRIBUTION		3. From: (Originating Organization) TWRS/CHARACTERIZATION PROJECT		4. Related EDT No.: N/A	
5. Proj./Prog./Dept./Div.: TWRS/CHAR PROJECT		6. Cog. Engr.: D. R. BRATZEL		7. Purchase Order No.: N/A	
8. Originator Remarks: N/A				9. Equip./Component No.: N/A	
11. Receiver Remarks:				10. System/Bldg./Facility: 2704HV/200E	
				12. Major Assm. Dwg. No.: N/A	
				13. Permit/Permit Application No.: N/A	
				14. Required Response Date: 09/27/95	

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Approval Designator	Reason for Transmittal	Originator Disposition	Receiver Disposition
1	WHC-SD-WM-ER-512		0	TANK 241-U-203 HEADSPACE GAS AND VAPOR CHARACTERIZATION RESULTS FOR SAMPLES COLLECTED IN AUGUST 1995	<i>N/A</i> <i>9/21/95</i>	1	1	

16. KEY					
Approval Designator (F)		Reason for Transmittal (G)		Disposition (H) & (I)	
E, S, Q, D or N/A (see WHC-CM-3-5, Sec. 12.7)		1. Approval 2. Release 3. Information	4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)	1. Approved 2. Approved w/comment 3. Disapproved w/comment	4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged

17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)									
(G)	(H)	(J) Name	(K) Signature	(L) Date	(M) MSIN	(J) Name	(K) Signature	(L) Date	(M) MSIN
Reason	Disp.								
1	1	Cog. Eng. D. R. BRATZEL	<i>DRB</i>	<i>9/25/95</i>					
1	1	Cog. Mgr. T. J. KELLEY	<i>TJK</i>	<i>9/25/95</i>					
		QA							
		Safety							
		Env.							

18. D. R. BRATZEL <i>DRB</i> Signature of EDT Originator		19. N/A Authorized Representative Date for Receiving Organization		20. <i>TJK</i> Cognizant Manager Date		21. DOE APPROVAL (if required) Ctrl. No. ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments	
---	--	---	--	---	--	---	--

RELEASE AUTHORIZATION

Document Number: WHC-SD-WM-ER-512, REV 0

Document Title: Tank 241-U-203 Headspace Gas and Vapor
Characterization Results for Samples Collected in
August 1995

Release Date: 9/28/95

**This document was reviewed following the
procedures described in WHC-CM-3-4 and is:**

APPROVED FOR PUBLIC RELEASE

WHC Information Release Administration Specialist:

Kara Broz

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

This report has been reproduced from the best available copy. Available in paper copy. Printed in the United States of America. To obtain copies of this report, contact:

Westinghouse Hanford Company - Document Control Services
P.O. Box 1970, Mailstop H6-08, Richland, WA 99352
Telephone: (509) 372-2420; Fax: (509) 376-4989

SUPPORTING DOCUMENT

1. Total Pages 13

2. Title

TANK 241-U-203 HEADSPACE GAS AND VAPOR
CHARACTERIZATION RESULTS FOR SAMPLES COLLECTED IN
AUGUST 1995

3. Number

WHC-SD-WM-ER-512

4. Rev No.

0

5. Key Words

CHARACTERIZATION OBJECTIVES, TANK HEADSPACE,
SAMPLING EVENT, INORGANIC GASES, ORGANIC VAPORS

6. Author

Name: D. R. BRATZEL

Signature

DR Bratzel 9/25/95

Organization/Charge Code 75640/N4AB1

7. Abstract

Significant changes have been made to all of the original vapor characterization reports. This report documents specific headspace gas and vapor characterization results for all vapor sampling events to date. In addition, changes have been made to the original vapor reports to qualify the data based on quality assurance issues associated with the performing laboratories.

8. RELEASE STAMP

Tank 241-U-203 Headspace Gas and Vapor Characterization Results for Samples Collected in August 1995

J. L. Huckaby
Pacific Northwest Laboratories

D. R. Bratzel
Westinghouse Hanford Company

Date Published
September 1995

Prepared for the U.S. Department of Energy
Office of Environmental Restoration and
Waste Management

Westinghouse
Hanford Company

P.O. Box 1970
Richland, Washington

Management and Operations Contractor for the
U.S. Department of Energy under Contract DE-AC06-87RL10930

Approved for Public Release

Contents

1.0 INTRODUCTION	1
1.1 Characterization Objectives	1
1.2 Characterization Data Criteria	1
1.3 Sampling Overview	2
1.4 Tank Headspace Dynamics	2
2.0 SAMPLING EVENT	3
3.0 INORGANIC GASES AND VAPORS	4
3.1 Ammonia, Hydrogen, and Nitrous Oxide	4
3.2 Carbon Monoxide and Carbon Dioxide	4
3.3 Nitric Oxide, Nitrogen Dioxide, Water and Tritium	5
3.4 Discussion of Inorganic Gases and Vapors	5
4.0 ORGANIC VAPORS	6
4.1 Positively Identified Organic Compounds	6
4.2 Tentatively Identified Organic Compounds	7
4.3 Total Nonmethane Organic Carbon	8
4.4 Discussion of Organic Compounds	8
5.0 SUMMARY	9
6.0 REFERENCES	10

Acronyms and Abbreviations

CES	consensus exposure standard
EPA	Environmental Protection Agency
GC	gas chromatograph
GC/MS	gas chromatograph/mass spectrometer
LFL	lower flammability limit
MS	mass spectrometer
NFPA	National Fire Protection Association
NPH	normal paraffinic hydrocarbon
PNL	Pacific Northwest Laboratory
ppmv	parts per million by volume, 1 ppmv = 10 ⁻⁴ vol%
TNMOC	total nonmethane organic carbon
TST	triple sorbent trap
TO-12	task order 12
TO-14	task order 14
vol%	percent by volume, 1 vol% = 10,000 ppmv
VSS	vapor sampling system
WHC	Westinghouse Hanford Company

Acknowledgements

The authors wish to thank Chris Simonen for her work verifying data and generating tables, and Shas Mattigod for his help with the construction and reviews of this document. The authors also wish to thank Luther Buckley, Clarence Homi, and Tom Kunthara for their contributions to the final reviews and publication of this document.

**Tank 241-U-203 Headspace Gas and Vapor Characterization Results
for Samples Collected in August 1995**

1.0 INTRODUCTION

1.1 Characterization Objectives

Tank U-203 headspace gas and vapor samples were collected and analyzed to help determine the potential risks of fugitive emissions to tank farm workers. The drivers and objectives of waste tank headspace sampling and analysis are discussed in *Program Plan for the Resolution of Tank Vapor Issues* (Osborne and Huckaby 1994). Tank U-203 was vapor sampled in accordance with *Data Quality Objectives for Generic In-Tank Health and Safety Issue Resolution* (Osborne et al. 1995). Results presented here represent the best available data on the headspace constituents of tank U-203.

1.2 Characterization Data Criteria

Data Quality Objectives for Generic In-Tank Health and Safety Issue Resolution describes parameters for data collection to ensure appropriate conclusions can be drawn from the data. Tank headspace characterization data were collected to help in the evaluation of 1) headspace flammability, and 2) identification and quantification of compounds of toxicological concern.

Single Shell Tank Interim Operational Safety Requirements (Dougherty 1995) specifies that combustible constituents in tank headspaces be maintained below 25 % of the lower flammability limit (LFL). This essentially agrees with National Fire Protection Association requirements that combustible concentrations be maintained at or below 25 % of the LFL (NFPA 1992). However, current governing operating specifications for single shell Watchlist waste tanks, such as tank U-203, specify that combustible constituents be maintained at or below 20 % of the LFL (WHC 1995a).

Headspace characterization data are used by Westinghouse Hanford Company (WHC) Tank Waste Remediation Systems Industrial Hygiene as source term data in the industrial hygiene strategy to protect workers from tank fugitive emissions. Because selection of worker protective equipment must be based on industrial hygiene monitoring of the work place and not on source term data (29 CFR 1910.120), tank headspace characterization data can not be used for this purpose. Furthermore, because there are mechanisms by which headspace constituents can be either diluted or concentrated as they are released to the atmosphere, the headspace characterization data should not be considered to be representative of emissions at the point of emission.

These statements notwithstanding, the data quality objectives document specifies that the industrial hygiene group be advised if constituents with toxicological properties exceed 50 % of the appropriate consensus exposure standard (CES) for non-carcinogens, or 10 % of the appropriate CES for carcinogens. A CES is defined as the most stringent of known regulatory or recommended toxicological values for the workplace (Osborne et al. 1995).

1.3 Sampling Overview

Tank U-203 headspace characterization data presented here are from a single sampling event. Samples collected are thought to have been representative of the tank headspace when the tank was sampled (Meacham et al. 1995), and sample analyses were designed to provide a reasonably accurate and complete characterization of the significant headspace constituents. No assessment has been made of how the tank U-203 headspace composition changes with time, though studies of tank C-103 suggest that composition changes probably occur very slowly in passively ventilated tanks, such as tank U-203 (Huckaby and Story 1994).

1.4 Tank Headspace Dynamics

Tank U-203 is passively ventilated, which means that it is allowed to exhale air, waste gases, and vapors as the barometric pressure falls, and inhale ambient air as the barometric pressure rises. Tank U-203 has its own filtered breather riser. Barometric pressure typically rises and falls on a diurnal cycle, producing an average daily exchange of air equal to about 0.46 % of the tank headspace (Huckaby 1994). Changes in the concentrations of tank U-203 headspace constituents due to barometric pressure changes are consequently very slow.

2.0 SAMPLING EVENT

Headspace gas and vapor samples were collected from tank U-203 using the vapor sampling system (VSS) on August 9, 1995 by WHC Sampling and Mobile Laboratories (WHC 1995b). Sample collection and analysis were performed as directed by *Tank 241-U-203 Tank Characterization Plan* (Homi 1995a). The tank headspace temperature was determined to be 17.7 °C. Air from the U-203 headspace was withdrawn from a single elevation via a 6.1-m long heated sampling probe mounted in riser 2, and transferred via heated tubing to the VSS sampling manifold. All heated zones of the VSS were maintained at approximately 60 °C. All tank air samples were collected between 8:54 a.m. and 9:46 a.m., with no anomalies noted.

Sampling media were prepared and analyzed by WHC and Pacific Northwest Laboratories (PNL). The 36 tank air samples and 2 ambient air control samples collected are listed in Table 2-1 by analytical laboratory. Table 2-1 also lists the 14 field blanks and 2 trip blanks provided by the laboratories.

A general description of vapor sampling and sample analysis methods is given by Huckaby et al. (1995). The sampling equipment, sample collection sequence, sorbent trap sample air flow rates and flow times, chain of custody information, and a discussion of the sampling event itself are given in WHC (1995b).

3.0 INORGANIC GASES AND VAPORS

Analytical results of sorbent trap and SUMMATM¹ canister tank air samples for selected inorganic gases and vapors are given in Table 3-1 in parts per million by volume (ppmv) in dry air. The concentration of water vapor reported in Table 3-1 has been adjusted to tank conditions as given in Section 3.3. Inorganic analyte sorbent traps and SUMMATM canisters were prepared and analyzed by PNL at PNL quality assurance impact level 2 (Pool et al. 1995a).

Analyses of inorganic analytes in sorbent traps and SUMMATM canisters were performed within 13 and 6 days, respectively, after sample collection. This was within the allowed 60-day holding time of the WHC quality assurance project plan (Keller 1994). It should be noted that the 60-day holding time was administratively chosen, and that analytical holding times have not been established by an appropriate study of analyte stabilities in the sampling devices and in the chemical matrix of the tank air samples.

3.1 Ammonia, Hydrogen, and Nitrous Oxide

The reported ammonia concentration, 0.9 ppmv, is among the lowest measured in any of the passively ventilated waste tanks that have been sampled. Ammonia has been observed in virtually all of the passively ventilated waste tanks that have been sampled at concentrations as high as 1040 ppmv in BY-108 (McVeety et al. 1995). Given the LFL of ammonia in air is about 15 by volume (vol%), the measured 0.9 ppmv corresponds to about 0.0006 % of the LFL, and does not contribute appreciably to the flammability of the headspace.

The concentration of hydrogen in tank U-203 was determined to be < 25 ppmv. Hydrogen in the waste tanks is of concern as a fuel. Given that the LFL for hydrogen in air is about 4 vol%, < 25 ppmv of hydrogen corresponds to < 0.06 % of its LFL. At this level, hydrogen is not a flammability concern in tank U-203.

The nitrous oxide concentration in tank U-203 was also determined to be < 25 ppmv. Nitrous oxide has been detected in other passively ventilated waste tanks at average concentrations as low as about 12 ppmv in tank TX-105 (Klinger et al. 1995), and as high as 868 ppmv in tank U-103 (Ligothe et al. 1995). Under the proper conditions, nitrous oxide can serve as an oxidizer to support combustion. However, Cashdollar et al. (1992) found that nitrous oxide had no significant effect on the flammability of hydrogen and air mixtures for hydrogen concentrations less than 20 vol%, and that "small amounts of nitrous oxide (relative to air) do not appear to have much effect on the flammability". Their results suggest the measured nitrous oxide concentration is much too low to have a significant effect on the flammability of the tank U-203 headspace.

3.2 Carbon Monoxide and Carbon Dioxide

Carbon monoxide in the tank U-203 headspace was measured to be < 25 ppmv. In ambient air it typically ranges from 0.05 to 0.15 ppmv. Because different analytical methods have been used to measure carbon monoxide in the waste tanks sampled to date, the information on carbon monoxide has varied from tank to tank. However, elevated waste tank headspace carbon monoxide concentrations are common, and are thought to be due to the decomposition of organic waste in the tanks. Carbon monoxide has not been

¹ SUMMA is a trademark of Moleetrics, Inc., Cleveland, Ohio.

measured at very high levels in any of the waste tanks, the highest level measured to date was [26.7 ppmv] in tank C-103² (Huckaby and Story 1994).

The reported average carbon dioxide concentration in tank U-203 headspace SUMMA™ samples, < 25 ppmv, is much lower than it is in ambient air. Carbon dioxide is normally present in the ambient air at a concentration of 350 to 400 ppmv, and is typically lower than ambient in the waste tank headspaces. Carbon dioxide introduced by air exchange with the atmosphere is readily absorbed by caustic supernatant and interstitial liquids of the waste tanks, and converted to carbonate in solution. Typical waste tank carbon dioxide concentrations are in the 20 to 200 ppmv range.

3.3 Nitric Oxide, Nitrogen Dioxide, Water and Tritium

Nitric oxide and nitrogen dioxide concentrations in the tank U-203 headspace were both determined to be ≤ 0.05 ppmv. These are both acid gases that would have very low equilibrium concentrations above the high pH sludge in tank U-203. The measurable presence of nitric oxide may be due to its formation from oxygen and nitrogen in the radiation field of the headspace. These constituents could potentially serve as oxidizers to support combustion, but at the measured concentrations would have a negligible effect on the flammability of the tank U-203 headspace.

The water vapor concentration of tank U-203 was determined to be about 9.9 mg/L, at the measured tank headspace temperature of 15.2 °C and pressure of 1000 mbar (750.2 torr), (WHC 1995b). This corresponds to a water vapor partial pressure of 13.2 mbar (9.9 torr), to a dew point of 11.1 °C, and to a relative humidity of 76 %.

Silica gel sorbent traps were used to sample for tritium. It is assumed that tritium produced by the waste combines with hydroxide ions to form tritium-substituted water. Evaporation of the tritium-substituted water would then result in airborne radioactive contamination. Silica gel sorbent traps adsorb virtually all (normal and tritium-substituted) water vapor from the sampled tank air, and are analyzed at the WHC 222-S laboratory. Radiochemical analysis of the silica gel trap indicated the total activity of the headspace to be less than 50 pCi/L (WHC 1995b).

3.4 Discussion of Inorganic Gases and Vapors

Aside from water vapor and carbon dioxide, the most abundant waste constituents in the tank U-203 headspace are nitrous oxide and ammonia. These have been detected in most tank headspaces sampled to date, and along with hydrogen, are usually the dominate waste species.

The relative standard deviations of the inorganic gas and vapor results given in the last column in Table 3-1 are very good. Relative standard deviations range from less than 1 % for carbon dioxide to 13 % for nitrous oxide results. Because the precision reported depends both on sampling parameters (e.g., sample flow rate and flow time for sorbent traps) and analytical parameters (e.g., sample preparation, dilutions, etc.), the small relative standard deviations suggest proper control was maintained both in the field and in the laboratories.

² The carbon monoxide measurement in tank C-103 was made by Oregon Graduate Institute of Science and Technology, and placed in brackets to emphasize it should be considered secondary data.

4.0 ORGANIC VAPORS

Organic vapors in the tank U-203 headspace were sampled using SUMMA™ canisters and triple sorbent traps (TSTs), which were analyzed by PNL. Gas chromatographs (GCs) equipped with mass spectrometer (MS) detectors were used to separate, identify, and quantitate the analytes. SUMMA™ canisters were also analyzed according to the Environmental Protection Agency (EPA) task order 12 (TO-12) method, for total nonmethane organic carbon (EPA 1988). The EPA TO-12 method employs a GC equipped with a flame ionization detector.

Sample preparation and analyses were performed at PNL quality assurance impact level 2. Analyses of SUMMA™ and TST samples were completed 21 and 27 days, respectively, after sample collection, and within the allowed 60-day holding time (Keller 1994). However, no holding time study has been performed to determine the stability of analytes in SUMMA™ canisters in the chemical matrix of the tank samples. Descriptions of sample device cleaning, sample preparations, and analyses are given by Pool et al. (1995a).

All TSTs were prepared with 3 surrogate compounds added to evaluate sample matrix effects, potential handling, storage, and shipment problems. A statistical treatment of surrogate recoveries has not been performed in part because of insufficient data. Surrogates have been used by PNL only as indicators of gross sample matrix, handling, storage, or shipment problems, and no such problems were indicated in the tank U-203 TST samples.

4.1 Positively Identified Organic Compounds

Positive identification of organic analytes using the methods employed by PNL involves matching the GC retention times and MS data from a sample with that obtained when known compounds were analyzed. The concentration of an analyte in the sample is said to be quantitatively measured if the response of the GC/MS has been established at several known concentrations of that analyte (i.e., the GC/MS has been calibrated for that analyte), and the MS response to the analyte in the sample is between the lowest and highest responses to the known concentrations (i.e., the analyte is within the calibration range).

PNL was assigned a list of organic compounds, or target analytes, to positively identify and measure quantitatively. This list included 39 compounds in the EPA task order 14 (TO-14) method, which are primarily halocarbons and common industrial solvents (EPA 1988), plus 14 analytes selected mainly from a toxicology panel's review of vapor data from tank C-103 (Mahlum et al. 1994). This list of target analytes was used for both SUMMA™ canister and TST sample analyses, in part to allow comparison of results.

Table 4-1 lists the 3-sample average concentrations of the 3 organic compounds positively identified and quantitated in SUMMA™ samples. Also given in Table 4-1 is the SUMMA™ sample result for methane, which was analyzed with the inorganic gases. 4-Methyl-2-pentanone was detected in only 1 of the SUMMA™ canister samples. Its existence is also questionable because it was detected in the ambient air sample that was collected through the VSS heated manifold. The TO-14 method quantitation limit was 0.005 ppmv.

The TST target analyte results are given in Table 4-2. Like the SUMMA™ canister analyses, the TST analytical quantitation limit was 0.005 ppmv. Two compounds were detected in TST samples above the quantitation limit that were not detected in SUMMA™ samples, and 1 compound was detected in SUMMA™ samples that was not found in the TSTs.

A comparison of results from these 2 methods is given in Table 4-3. The methods appear to agree reasonably well on the concentrations of the 2 primary constituents, trichlorofluoromethane and toluene. The other 3 analytes were not detected in both types of samples, but were at low levels.

4.2 Tentatively Identified Organic Compounds

In addition to the target analytes, the ORNL and PNL analytical procedures allow the tentative identification of other organic compounds. Tentative identification of analytes was performed by comparing the MS molecular fragmentation patterns with a library of known MS fragmentation patterns. This method allows an organic analyte to be identified (with reasonable certainty) as an alkane, a ketone, an aldehyde, etc., and may also determine its molecular weight. The method usually does not, however, allow the unambiguous identification of structural isomers, and this ambiguity increases with analyte molecular weight. Using this method, many analytes can be tentatively identified with reasonable confidence without having to inject each into the GC/MS to determine their GC retention times or specific MS patterns.

By the nature of the sampling devices, virtually all organic vapors present in the tank headspace are collected by both TST and SUMMATM samples. Analyses of the samples are designed to recover, separate, and identify the organic vapors in the samples. TSTs are not good for collecting highly volatile compounds (i.e., molecules more volatile than propane), but are quite good for most others. In contrast, the recovery of very low volatility compounds (e.g., molecules with more than about 15 carbon atoms) and some polar compounds with moderate volatility (e.g., butanal) from SUMMATM samples has been problematic.

The lists of tentatively identified compounds, with estimated concentrations, recovered from SUMMATM and TST samples are given in Tables 4-4 and 4-5, respectively. Estimated concentrations in Tables 4-4 and 4-5 are in mg/m³, based on dry air at 0 °C and 1.01 bar. Though only 1 non-target compound (acetone) was detected in the SUMMATM canister samples, there were 10 non-target compounds (including acetone) detected in TSTs. The 7 unknown or partially identified compounds detected in the TST samples (Cmpd # 3 through 9 in Table 4-5) were all observed in the semivolatile region of the gas chromatogram. A comparison of the non-quantitated, tentatively identified compounds for which a complete chemical name could be assigned, is given in Table 4-6. Note the estimated concentrations given in Table 4-6 are in ppmv³.

Tributyl phosphate was detected in 1 of the TST samples, however, there is good reason to doubt the validity of this result. Specifically, relatively high levels of tributyl phosphate have been associated with the number 1 port of the sorbent trap sampling station of the VSS, both in TSTs analyzed by Oak Ridge National Laboratory (Jenkins et al. 1995), and by PNL (Pool et al. 1995b).

The PNL methods used to tentatively identify and estimate concentrations are described by Pool et al. (1995a), and should be reviewed before these data are used for decision making. Concentrations given in Tables 4-4 through 4-6 should be considered estimates.

³ In the methods used, it is necessary to know the molecular weight of an analyte to calculate its concentration in ppmv. Molecular weight is not always known for tentatively identified compounds.

4.3 Total Nonmethane Organic Carbon

The TNMOC in the tank U-203 headspace was determined by analysis of 3 SUMMA™ canister samples using the EPA TO-12 method. The average measured TNMOC concentration was 1.98 mg/m³. For comparison, the ambient air SUMMA™ canister collected upwind of tank U-203 at the start of the sampling event was found to have a TNMOC concentration of 0.63 mg/m³. The average TNMOC concentration of the tank air samples is much lower than the sum of quantitated and estimated organic vapors in SUMMA™ canisters by GC/MS (10.1 mg/m³), and that in TST samples by GC/MS (14.6 mg/m³). The primary reason for these differences is that the flame ionization detector employed in the EPA TP-12 method is insensitive to halocarbons (or any nonflammable constituent), and these represent a majority of the organic material on a mass concentration basis.

4.4 Discussion of Organic Compounds

The primary organic compounds identified in tank U-203 were halocarbons. The source of these is unknown, but trichlorofluoromethane has been associated with the urethane foam used to seal concrete pits on the single shell tanks. The plausibility of this explanation for the freons tank U-203 has not been confirmed.

Aside from the halocarbons, tank U-203 is relatively devoid of organic vapors. Most of the semivolatile compounds found in TSTs (Table 4-5) are tentatively identified as cycloalkanes or alkenes, and there is no clear indication that these are associated with the semivolatile normal paraffinic hydrocarbons (NPHs) that have been detected in virtually every other passively ventilated tank that has been vapor sampled. Though tributyl phosphate was detected in 1 TST sample, it is very likely that its presence in that TST is due to contamination of the sampling port of the VSS at which it was collected. Another reason to doubt the existence of tributyl phosphate is the fact that 1-butanol, a commonly observed hydrolysis product of tributyl phosphate, was not detected in any of the samples.

The tank U-203 headspace has low levels of organic vapors compared to other waste tanks sampled to date. The most abundant constituents (halocarbons) are nonflammable, and none of the other organic constituents, individually or cummulative, are present at high enough concentrations to pose a flammability hazard.

5.0 SUMMARY

The tank U-203 headspace was sampled in August 1995 for gases and vapors to address flammability and industrial hygiene concerns. Collection and analysis of samples has been reported. It was determined that no headspace constituents exceeded the flammability or industrial hygiene notification limits specified in the current *Vapor Sampling and Analysis Plan* (Homi 1995b).

6.0 REFERENCES

- 29 CFR 1910.120, 1993, "Hazardous Waste Operations and Emergency Response", *Code of Federal Regulations*.
- Burnum, S. T., 1995, *Qualification of Reported WHC Vapor Program Data*, (letter 95-CHD-065 to president, Westinghouse Hanford Company, August 18), Department of Energy, Richland Operations Office, Richland, Washington.
- Cashdollar, K. L., M. Hertzberg, I. A. Zlochower, C. E. Lucci, G. M. Green, and R. A. Thomas, 1992, *Laboratory Flammability Studies of Mixtures of Hydrogen, Nitrous Oxide, and Air*, WHC-SD-WM-ES-219 Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Dougherty, L. F., 1995, *Single Shell Tank Interim Operational Safety Requirements*, WHC-SD-WM-OSR-005 Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- EPA 1988, *Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air*, PB90-127374, U.S. Environmental Protection Agency, Washington, D.C.
- Homi, C. S., 1995a, *Tank 241-U-203 Tank Characterization Plan*, WHC-SD-WM-TP-310, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Homi, C. S., 1995b, *Vapor Sampling and Analysis Plan*, WHC-SD-WM-TP-335 Rev. 0G, Westinghouse Hanford Company, Richland, Washington.
- Huckaby, J. L., 1994, *Tank 241-C-103 Headspace Flammability*, WHC-EP-0734 Rev. 1, Westinghouse Hanford Company, Richland, Washington.
- Huckaby, J. L., H. Babad, and D. R. Bratzel, 1995, *Headspace Gas and Vapor Characterization Summary for the 43 Vapor Program Suspect Tanks*, WHC-SD-WM-ER-514 Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Huckaby, J. L., and M. S. Story, 1994, *Vapor Characterization of Tank 241-C-103*, WHC-EP-0780 Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Jenkins, R. A., A. B. Dindal, C. Y. Ma, M. A. Palausky, J. T. Skeen, and C. K. Bayne, 1995, *Analysis of Tank 241-A-101 Headspace Components*, ORNL-CASD-FR-241A101.95 Rev. 0, Oak Ridge National Laboratory, Oak Ridge, Tennessee.
- Keller, K. K., 1994, *Quality Assurance Project Plan for Tank Vapor Characterization*, WHC-SD-WM-QAPP-013 Rev. 2, Westinghouse Hanford Company, Richland, Washington.
- Klinger, G. S., T. W. Clauss, M. W. Ligothe, K. H. Pool, R. B. Lucke, B. D. McVeety, O. P. Bredt, J. S. Young, M. McCulloch, J. S. Fruchter, and S. C. Goheen, 1995, *Vapor Space Characterization of Waste Tank 241-TX-105: Results from Samples Collected Through the Vapor Sampling System on 12/20/94*, PNL-10594 UC-606, Pacific Northwest Laboratory, Richland, Washington.
- Ligothe, M. W., K. H. Pool, T. W. Clauss, B. D. McVeety, G. S. Klinger, K. B. Olsen, O. P. Bredt, J. S. Fruchter, and S. C. Goheen, 1995b, *Vapor Space Characterization of Waste Tank 241-U-103*:

Results from Samples Collected on 2/15/95, PNL-10812 UC-606, Pacific Northwest Laboratory, Richland, Washington.

Mahlum, D. D., J. Y. Young, and R. E. Weller, 1994, *Toxicologic Evaluation of Analytes from Tank 231-C-103*, PNL-10189, Pacific Northwest Laboratory, Richland, Washington.

McVeety, B. D., T. W. Clauss, M. W. Ligothke, K. H. Pool, R. B. Lucke, G. S. Klinger, J. S. Young, M. McCulloch, J. S. Fruchter, and S. C. Goheen, 1995, *Vapor Space Characterization of Waste Tank 241-BY-108: Results from Samples Collected on 10/27/94*, PNL-10495 UC-606, Pacific Northwest Laboratory, Richland, Washington.

Meacham, J. E., H. Babad, R. J. Cash, G. T. Dukelow, S. J. Eberlein, D. W. Hamilton, G. D. Johnson, J. W. Osborne, M. A. Payne, D. J. Sherwood, D. A. Turner, and J. L. Huckaby, 1995, *Approach for Tank Safety Characterization of Hanford Site Waste*, WHC-EP-0843 Rev. 0, UC-2070, Westinghouse Hanford Company, Richland, Washington.

NFPA 1992, *Standard on Explosion Prevention Systems*, NFPA 69, National Fire Protection Association, Quincy, Massachusetts.

Osborne, J. W., and J. L. Huckaby, 1994, *Program Plan for the Resolution of Tank Vapor Issues*, WHC-EP-0562 Rev. 1, Westinghouse Hanford Company, Richland, Washington.

Osborne, J. W., J. L. Huckaby, T. P. Rudolph, E. R. Hewitt, D. D. Mahlum, J. Y. Young, and C. M. Anderson, 1995, *Data Quality Objectives for Generic In-Tank Health and Safety Issue Resolution*, WHC-SD-WM-DQO-002 Rev. 1, Westinghouse Hanford Company, Richland, Washington.

Pool, K. H., T. W. Clauss, J. C. Evans, B. D. McVeety, K. B. Olsen, J. S. Fruchter, and M. W. Ligothke, 1995a, *Vapor Space Characterization of Waste Tank 241-U-203: Results from Samples Collected on 8/9/95*, PNL-10812 UC-606, Pacific Northwest Laboratory, Richland, Washington.

Pool, K. H., T. W. Clauss, M. W. Ligothke, B. D. McVeety, J. C. Evans, K. B. Olsen, J. S. Fruchter, and S. C. Goheen, 1995b, *Vapor Space Characterization of Waste Tank 241-A-101: Results from Samples Collected on 6/8/95*, PNL-10808 UC-606, Pacific Northwest Laboratory, Richland, Washington.

WHC 1995a, *Operating Specifications for Watchlist Tanks*, OSD-T-151-00030, Rev. B-9, Westinghouse Hanford Company, Richland, Washington.

WHC 1995b, *Vapor and Gas Sampling of Single-Shell Tank 241-U-203 Using the Vapor Sampling System*, WHC-SD-WM-RPT-154, Westinghouse Hanford Company, Richland, Washington.

Table 2-1
Tank U-203 Gas and Vapor Sample Type and Number

Laboratory	Sampling Device	Nominal Sample Volume (L)	Target Analytes	Number of Samples
Pacific Northwest Laboratories	Acidified Carbon Sorbent Trap	3.0	Ammonia	6 tank air samples + 3 field blanks
	Triethanolamine Sorbent Trap	3.0	Nitrogen Dioxide	6 tank air samples + 3 field blanks
	Oxidation Bed + Triethanolamine Sorbent Trap	3.0	Nitric Oxide	6 tank air samples + 3 field blanks
	Silica Gel Sorbent Trap	3.0	Water vapor	8 tank air samples + 3 field blanks
	SUMMA™ Canister	6.0	Carbon dioxide, Carbon monoxide, Hydrogen, Methane, Nitrous oxide, Organic vapors	3 tank air samples + 2 ambient air samples
	Triple Sorbent Trap	1.0	Organic vapors	6 tank air samples + 2 trip blanks + 2 field blanks
WHC 222-S Laboratory	Silica Gel Sorbent Trap	1.0	Tritium-Substituted Water Vapor	1 tank air sample

Table 3-1
Tank U-203 Inorganic Gas and Vapor Concentrations

Compound	CAS ¹ Number	Sample Type	Number of Samples	Average (ppmv)	Standard Deviation (ppmv)	RSD ² (%)
Ammonia, NH ₃	7664-41-7	Sorbent Trap	6	0.9	0.1	11
Carbon Dioxide, CO ₂	124-38-9	SUMMA TM	3	< 25	—	—
Carbon Monoxide, CO	630-08-0	SUMMA TM	3	< 25	—	—
Hydrogen, H ₂	1333-74-0	SUMMA TM	3	< 25	—	—
Nitric Oxide, NO	10102-43-9	Sorbent Trap	6	≤ 0.05	—	—
Nitrogen Dioxide, NO ₂	10102-44-0	Sorbent Trap	6	≤ 0.05	—	—
Nitrous Oxide, N ₂ O	10024-97-2	SUMMA TM	3	< 25	—	—
Water Vapor, H ₂ O	7732-18-5	Sorbent Trap	6	15,800 (11.7 mg/L)	350 (0.3 mg/L)	2.2

¹ CAS = Chemical Abstracts Service.

² RSD = relative standard deviation. Burnum (1995) specifies the RSD should be less than 25 %.

Table 4-1
Tank U-203 Quantitatively Measured Organic Compounds in SUMMA™ Samples --
Analyses by Pacific Northwest Laboratory

Cmpd #	Compound	CAS ¹ Number	Average ² (ppmv)	Standard Deviation (ppmv)	RSD ³ (%)
1	Trichlorofluoromethane	75-69-4	1.62	0.12	7
2	4-Methyl-2-pentanone ⁴ (methyl isobutyl ketone)	108-10-1	0.012	--	--
3	Toluene	108-88-3	0.013	0.0003	2
4	Methane	74-82-8	< 25	--	--
Sum of positively identified compounds:			10.0	mg/m ³	

1 CAS = Chemical Abstract Service.

2 Average of 3 samples.

3 RSD = relative standard deviation. Burnum (1995) specifies the RSD should be less than 25 %.

4 This compound was detected in only 1 sample.

Table 4-2
Tank U-203 Quantitatively Measured Organic Compounds in TST Samples --
Analyses by Pacific Northwest Laboratory

Cmpd #	Compound	CAS ¹ Number	Average ² (ppmv)	Standard Deviation (ppmv)	RSD ³ (%)
1	Dichlorodifluoromethane	75-71-8	0.009	0.0056	62
2	Trichlorofluoromethane	75-69-4	1.35	0.01	1
3	Dichloromethane (methylene chloride)	75-09-2	0.008	0.003	36
4	Toluene	108-88-3	0.021	0.0002	1
Sum of positively identified compounds:			8.45	mg/m ³	

1 CAS = Chemical Abstract Service.

2 Average of 3, 1-L samples.

3 RSD = relative standard deviation. Burnum (1995) specifies the RSD should be less than 25 %.

Table 4-3
Tank U-203 Comparison of TST and SUMMA™ Sample Quantitative Results --
Analyses by Pacific Northwest Laboratory

Compound	CAS ¹ Number	TST Average ² (ppmv)	SUMMA™ Average ³ (ppmv)	RPD ⁴ (%)
Dichlorodifluoromethane	75-71-8	0.0090	< 0.005	--
Trichlorofluoromethane	75-69-4	1.35	1.62	-18
Dichloromethane (methylene chloride)	75-09-2	0.0078	< 0.005	--
4-Methyl-2-pentanone ⁵ (methyl isobutyl ketone)	108-10-1	< 0.005	0.012	--
Toluene	108-88-3	0.021	0.013	45

1 CAS = Chemical Abstract Service.

2 Average of 3 TST, 1-L samples.

3 Average of 3 SUMMA™ samples.

4 RPD = relative percent difference. Keller (1994) requires the RPD to be less than 20 %.

5 This compound was detected in only 1 sample.

Table 4-4
Tank U-203 Tentatively Identified Organic Compounds in SUMMA™ Samples --
Analyses by Pacific Northwest Laboratory

Cmpd #	Compound	CAS ¹ Number	Average ² (mg/m ³)	Standard Deviation (mg/m ³)	RSD ³ (%)
1	Propanone (acetone)	67-64-1	0.57	0.02	4
Sum of tentatively identified compounds:			0.57		

1 CAS = Chemical Abstract Service.

2 Based on analyses of 3 samples. Values given are estimates.

3 RSD = relative standard deviation. Burnum (1995) specifies the RSD should be less than 25 %.

Table 4-5
Tank U-203 Tentatively Identified Organic Compounds in TST Samples
Analyses by Pacific Northwest Laboratory

Cmpd #	Compounds	CAS ¹ Number	Average ² (mg/m ³)	Standard Deviation ³ (mg/m ³)	RSD ⁴ (%)
1	Ethane, 1-chloro-1,1-difluoro-	75-68-3	0.17	0.10	59
2	Propanone (acetone)	67-64-1	0.083	0.006	7
3	Unknown		0.044	0.009	20
4	Unknown C9 Alkene/Cycloalkane ⁵		0.060	< 0.01	< 2
5	Unknown C10 Alkene/Cycloalkane ⁵		0.063	< 0.01	< 2
6	Unknown C10 Alkene/Cycloalkane ⁵		0.067	< 0.01	< 2
7	Unknown		0.041	0.007	17
8	Unknown C10 Alkene/Cycloalkane ⁵		0.066	0.006	18
9	Unknown		0.028	0.011	39
10	Tributyl phosphate ⁶	126-73-8	0.58	—	—
Sum of tentatively identified compounds:			1.20		

1 CAS = Chemical Abstract Service.

2 Based on analysis of 3 samples. Values given are estimates.

3 When the analyte was detected in only 2 samples, the entry is the average difference (i.e., their difference divided by 2).

4 RSD = relative standard deviation. Burnum (1995) specifies the RSD should be less than 25 %. When detected in only 2 samples, the entry is the relative percent difference (i.e., their difference divided by their means times 100%).

5 Detected in only 2 samples.

6 Detected in only 1 sample.

Table 4-6
Tank U-203 Comparison of Tentatively Identified Organic Compounds
in SUMMA™ and TST Samples
Analyses by Pacific Northwest Laboratory

Compound	CAS ¹ Number	TST Average ² (ppmv)	SUMMA™ Average ³ (ppmv)	RPD ⁴ (%)
Propanone (acetone)	67-64-1	0.032	0.22	-149
Ethane, 1-chloro-1,1-difluoro-	75-68-3	0.038	< 0.010	--
Tributyl phosphate ⁵	126-73-8	0.049	< 0.010	--

1 CAS = Chemical Abstract Service.

2 Average of 3 TST, 1-L samples. Values given are estimates.

3 Average of 3 SUMMA™ samples. Values given are estimates.

4 RPD = relative percent difference. Keller (1994) requires the RPD to be less than 20 %.

5 Detected in only 1 sample.