Non-equilibrium Energy Loss for Very Highly Charged Ions in Insulators

M. A. Briere
T. Schenkel
P. Bauer
A. Arnau

This paper was prepared for submittal to the
Proceeding of Eighth International Conference on
Physics of Highly Charged Ions
Omiya, Saitama, Japan
September 23-26, 1996

October 30, 1996

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

Non-equilibrium Energy Loss for Very Highly Charged Ions in Insulators

M.A. Briere and T. Schenkel

Lawrence Livermore National Laboratory, Livermore CA 94550 USA

P. Bauer

Johannes-Kepler-Universität Linz, A-4040 Linz, Austria

A. Arnau

Departamento de Física de Materials, UPV/EHU, Donostia, Spain

The energy loss of 144 keV Ar^{16+} ions on a bilayer structure of C-CaF₂ has been measured. An asymmetry in the results is found depending on which layer is passed by the ion first: the energy loss is about four times larger when the CaF₂ layer is traversed by the ion first. We interpret this as an indication of the existence of a nonequilibrium charge state of the Ar ions inside the solid in the case of the insulator.

At present, it is unknown how long very slow (keV/u) highly charged ions (i.e. Ar^{16+} , Kr^{34+} , Th^{80+}) can retain a non-equilibrium charge state in solids. In fact, there is no evidence that even the inner shell vacancies of such ions exist beyond the first few monolayers below the solid surface. Recently, it has been predicted that an increased nuclear-nuclear energy transfer, due to long range Coulomb interactions in insulators, is expected for these ions[1]. The object of our experiment is to demonstrate that such an effect actually occurs. This is accomplished through differential transmission energy loss spectroscopy using ion time of flight, as shown in Figure 1. Previous attempts to measure such energy loss effects in SiO_2 , through highly sensitive RBS measurements of the projected range of Xe^{q+} , where $1 \leq q \leq 44$, have produced negative results[2]. It is believed that this is due to the covalent nature of the insulator and therefore its screening of the ionic charge through strong polarization of the target atoms. A better candidate for the effect is a strong ionic solid such as MgO or CaF_2 . Furthermore, enhanced sensitivity to the effect would be achieved for transmission energy loss measurements through thin films, where the non-equilibrium state may exist over a large fraction of the ion's path length in the solid.

The differential technique is based upon the idea that the increased energy loss is expected only in ionic insulators (i.e. CaF_2) and not in metallic solids (i.e. C), since the valence electrons should efficiently screen the ion's potential at distances greater than the order of the lattice spacing. As depicted in Figure 2, a sandwich target structure is created under UHV conditions using thermal evaporation of several nanometers of CaF_2 on a thin (10 nm) carbon foil backing, supported by a Cu TEM grid. Both AFM and TEM microscopic investigations indicate that the film is continuous for thickness of at least 2 to 4 nm. The transmitted energy loss spectrum of highly charged ions (i.e. Ar^{16+}) incident on the ionic solid (i.e. CaF_2) side of the two layer target structure is compared to that for ions incident on the metallic (carbon) side. Measurements of the charge state distribution of the ions transmitted through 100 nm C foils indicate that charge state equilibrium is achieved within the foil

(predominantly neutral and singly charged ions). Therefore, ions first passing through the C foil will interact with the CsF₂ film in equilibrium, whereas ions first entering the insulator will experience non-equilibrium effects. An asymmetry in the results for the two cases, therefore, indicates the existence of a non-equilibrium charge state inside the solid. It should be noted that, energy loss measurements of Ar¹⁶⁺ through various thickness of C foils are in excellent agreement with equilibrium data[3], confirming one of the basic assumptions of the technique. However, a significant increase in the transited energy loss for highly charged ions incident on ionic insulating targets has been observed. In the case of 144 keV Ar¹⁶⁺ ions cm a 5 nm CaF₂ film, shown in Figure 3, the average energy loss for non-equilibrium charge states, δE_2 , is a factor of four greater than that for the equilibrium charge state, δE_1 , as achieved through initial transmission through a 10 nm C foil. Additionally, a significant increase in the energy loss straggling is observed for the case of highly charged ions in ionic solids. Both the increased energy loss and the enhanced straggling are thought due to the influence of reduced screening for small impact parameter collisions on energy transfer cross sections, due to hollow atom formation in the solid. These results represent evidence for the existence of very slow highly charged ions inside solids and suggest several techniques to study the formation and decay of hollow atoms in solids. Measurements of this asymmetry in the energy loss can be used to determine the average decay process of non-equilibrium charge states in solids.

Acknowledgements

This work was performed under the auspices of the U.S. Dept. of Energy by the Lawrence ~~Livermore~~ **National** Laboratory *under* contract **W-7405-ENG-48**. **One** of us (**A.A.**) acknowledges partial **financial** support by **Eusko Jauriaritza** and the **spanish** **D.G.I.C.Y.T.**

References

- [1] J.P. Biersack, Nucl. Instrum. Methods **B80/81**, 12 (1993).
- [2] M.A. Briere et al., LLNL EBIT Annual Report 1993, p. 33-35.
- [3] R. Herrmann, CL. Cocke, J. Ullrich, S. Hagmann, M Stoeckli, and H. Schmidt-1% uecking, Phys. Rev. **A50**, 1435 (1994).

Figure captions

Figure 1: **Experimental** arrangement for **the** time-of-flight measurements of transmitted energy loss for **incident** highly charged ions. **The** annular micro-channel plate (MCP) detector, located in front of the sample, **is** used to **detect** electrons emitted at ion **impact** and **provide** a start signal to the time-to-amplitude converter (TAC). The **large** area MCP **detector** located beyond the **target** provides the stop signal **for the** time-of-flight of the ion and has a position sensitive anode, allowing for measurements of the scattered angle-energy **correlation**. **The** flight path **is** 0.75 m with a solid **angle** for the **PS-MCP** detector of ± 1.5 degrees.

Figure 2: A schematic representation of the experimental **technique** for the **differential energy loss** determination. **First, the** transmitted energy (time-of-flight) is measured for the bare 10 nm C foil. Then a **film of** CaF_2 is deposited under **UHV** conditions. The transmitted **energy is** then **measured** for the ions incident on each of the two sides of the resulting hi-layer structure. The energy **loss is** determined directly from each side by subtraction of the bare C foil result,

Figure 3: Transmission time-of-flight results (converted into energy loss) for Ar^{16+} incident on the bare 10 nm C-foil (ΔE_0 , equilibrium) and the hi-layer structure: C-side first ($\delta E_1 = \Delta E_1 - \Delta E_0$) and CaF_2 -side first ($\delta E_2 = \Delta E_2 - \Delta E_0$). A clear asymmetry exists between the results for the different incident sides of the same hi-layer structure, indicating non-equilibrium effects in the insulator.

*Annular Microchannelplate
Detector: Start-Signal*

Grid + 0 V
Front +60 V
Rear +1 kV
Anode +2 kV

*Target
" 2kV
10 nm C-foil
CaF₂ film*

*Position Sensitive
Micro Channelplate
Detector: Stop-Signal*

Front - 50 V
Mid +800 V
Rear +1.9 kV
Anode +2 kV

10 nm C Foil

CaF_2 Deposition

10 nm C / 5 nm CaF_2

5 nm CaF_2 / 10 nm C

Technical Information Department • Lawrence Livermore National Laboratory
University of California • Livermore, California 94551