AUG 21 1997

ENGINEERING DATA TRANSMITTAL

Page 1 of 1

1. EDT 161471

2. To: (Receiving Organization) Distribution		3. From: (Originating Organization) J. G. Field, LMHC, R2-12		4. Related EDT No.: NA	
5. Proj./Prog./Dept.: Tank 241-T-201		6. Design Authority/ Design Agent/Cog. Engr.: M. J. Kupfer		7. Purchase Order No.: NA	
8. Originator Remarks: Approval/Release				9. Equip./Component No.: NA	
				10. System/Bldg./Facility: NA	
11. Receiver Remarks: 11A. Design Baseline Document? ☐ Yes ☒ No				12. Major Assm. Dwg. No.: NA	
				13. Permit/Permit Application No.: NA	
				14. Required Response Date:	

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Approval Design- nator	Reason for Trans- mittal	Origin- ator Dispo- sition	Receiv- er Dispo- sition
1	HNF-SD-WM-ER-726	-	0	Preliminary Tank Characterization Report for Single- Shell Tank 241-T-201: Best-Basis Inventory	NA	1,2		

16. KEY						
Approval Designator (F)		Reason for Transmittal (G)			Disposition (H) & (I)	
E, S, Q, D or N/A (see WHC-CM-3-5, Sec.12.7)		1. Approval 2. Release 3. Information	4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)		1. Approved 2. Approved w/comment 3. Disapproved w/comment	4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged

17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)											
(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN	(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN
		Design Authority				3		Central Files		A3-88	
		Design Agent			H5-49	3		DOE Reading Room		H2-53	
1	1	Cog.Eng. M. J. Kupfer	<i>M. J. Kupfer</i>	8-15-97		3		J. G. Field		R2-12	
1	1	Cog. Mgr. K. M. Hodgson	<i>K. M. Hodgson</i>	8-15-97		3		TCSRC		R1-10	
		QA			R2-11	3		M. D. LeClair (4)		H0-50	
		Safety				3		K. M. Hall		R2-12	
		Env.				3		R. T. Winward		H5-49	

18. M. J. Kupfer <i>M. J. Kupfer</i> 8-15-97 Signature of EDT Originator		19. Authorized Representative Date for Receiving Organization		20. K. M. Hodgson <i>K. M. Hodgson</i> 8-15-97 Design Authority/ Cognizant Manager		21. DOE APPROVAL (if required) Ctrl. No. ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments	
---	--	--	--	---	--	---	--

Preliminary Tank Characterization Report for Single-Shell Tank 241-T-201: Best-Basis Inventory

J. G. Field and R. T. Winward (Meier Associates)
Lockheed Martin Hanford Corporation, Richland, WA 99352
U.S. Department of Energy Contract DE-AC06-96RL13200

EDT/ECN: 161471 UC: 712
Org Code: 74610 Charge Code: N4G3A
B&R Code: EW3120074 Total Pages: 21

Key Words: TCR, best-basis inventory

Abstract: An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities. As part of this effort, an evaluation of available information for single-shell tank 241-T-201 was performed, and a best-basis inventory was established. This work follows the methodology that was established by the standard inventory task.

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: Document Control Services, P.O. Box 950, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

Janis Bishop
Release Approval

8-21-97
Date

Approved for Public Release

**PRELIMINARY TANK
CHARACTERIZATION REPORT
FOR SINGLE-SHELL TANK
241-T-201:
BEST-BASIS INVENTORY**

June 1997

J. G. Field
Lockheed Martin Hanford Corporation

R. T. Winward
Meier and Associates
Richland, Washington

Prepared for
U.S. Department of Energy
Richland, Washington

This page intentionally left blank.

**PRELIMINARY TANK CHARACTERIZATION REPORT
FOR SINGLE-SHELL TANK 241-T-201:
BEST-BASIS INVENTORY**

This document is a preliminary Tank Characterization Report (TCR). It only contains the current best-basis inventory (Appendix D) for single-shell tank 241-T-201. No TCRs have been previously issued for this tank, and current core sample analyses are not available. The best-basis inventory, therefore, is based on an engineering assessment of waste type, process flowsheet data, early sample data, and/or other available information.

The *Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes* (Kupfer et al. 1997) describes standard methodology used to derive the tank-by-tank best-basis inventories. This preliminary TCR will be updated using this same methodology when additional data on tank contents become available.

REFERENCE

Kupfer, M. J., A. L. Boldt, B. A. Higley, K. M. Hodgson, L. W. Shelton, and R. A. Watrous (LMHC), S. L. Lambert, and D. E. Place (SESC), R. M. Orme (NHC), G. L. Borsheim (Borsheim Associates), N. G. Colton (PNNL), M. D. LeClair (SAIC), R. T. Winward (Meier Associates), and W. W. Schulz (W²S Corporation), 1997, *Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes*, HNF-SD-WM-TI-740, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.

This page intentionally left blank.

APPENDIX D

EVALUATION TO ESTABLISH BEST-BASIS INVENTORY FOR SINGLE-SHELL TANK 241-T-201

This page intentionally left blank.

APPENDIX D**EVALUATION TO ESTABLISH BEST-BASIS INVENTORY FOR
SINGLE-SHELL TANK 241-T-201**

An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities (Hodgson and LeClair 1996). As part of this effort, an evaluation of available information for single-shell tank 241-T-201 was performed, and a best-basis inventory was established. This work, detailed in the following sections, follows the methodology that was established by the standard inventory task.

D1.0 CHEMICAL INFORMATION SOURCES

There is not a tank characterization report for this tank. The information provided in Appendix B of Conner et al. (1997) provides characterization results for tank 241-B-201 which contains the same type of waste as tank 241-T-201.

D2.0 COMPARISON OF COMPONENT INVENTORY VALUES

The engineering-based inventories listed in Tables D2-1 and D2-2 were calculated by multiplying the sample-based inventories for tank 241-B-201 (Conner et al. 1997) by the ratio of the waste volume in tank 241-T-201 to the waste volume in tank 241-B-201 (1.00). (The chemical species are reported without charge designation per the best-basis inventory convention). Tank 241-T-201 is reported to contain 110 kL (29 kgal) of waste and tank 241-B-201 is reported to contain 110 kL (29 kgal) (Hanlon 1997). The HDW (Hanford Defined Waste) model (Agnew et al. 1997a) inventory also is derived using this same waste volume and is also given in Tables D2-1 and D2-2.

Table D2-1. Engineering and Hanford Defined Waste-Based Inventory Estimates for Tank 241-T-201 Nonradioactive Components.

Analyte	Engineering ^a inv. estimate (kg)	HDW ^b inv. estimate (kg)	Analyte	Engineering ^a inv. estimate (kg)	HDW ^b inv. estimate (kg)
Al	473	0.00	Na	5,250	10,300
Bi	13,000	1,230	Ni	65.9	8.85
Ca	1,680	1,040	NO ₂	121	15.6
Ce	9.57	NR	NO ₃	6,780	8,050
Cl	227	89.1	oxalate	NR	9,900
Cr	459	33.3	P as PO ₄	2,300	846
Cu	6.63	NR	Si	2,780	0
F	802	2,030	SO ₄	47.9	27.2
Fe	1,840	2,150	Sr	127	0
K	799	851	TIC as CO ₃	NR	1,550
La	2,080	49.8	Zn	29.8	NR
Mg	208	NR	H ₂ O (wt%)	60.7	69.5
Mn	2,640	26.4	density (g/mL)	1.25	1.20

HDW = Hanford Defined Waste

NR = Not reported

^a Conner et al. (1997), ratioed to the volume of tank 241-T-201

^b Agnew et al. (1997a).

Table D2-2. Engineering and Hanford Defined Waste-based Inventory Estimates for Radioactive Components for Tank 241-T-201, Decayed to January 1, 1994.

Analyte	Engineering ^a inv. estimate (Ci)	HDW ^b inv. estimate (Ci)	Analyte	Engineering ^a inv. estimate (Ci)	HDW ^b inv. estimate (Ci)
¹⁴ C	0.0435	1.75 E-04	^{239/240} Pu	155	0.0505
⁹⁰ Sr	275	18.2	²⁴¹ Am	4.25	3.80 E-04
¹³⁷ Cs	105	20.7	Total α	180	NR
¹⁵⁴ Eu	0.512	8.99 E-04			

HDW = Hanford Defined Waste

^a Conner et al. (1997), decayed to January 1, 1994

^b Agnew et al. (1997a), decayed to January 1, 1994.

D3.0 COMPONENT INVENTORY EVALUATION

The following evaluation provides a best-basis inventory estimate for chemical and radionuclide components in tank 241-T-201.

D3.1 CONTRIBUTING WASTE TYPES

The following abbreviations were used to designate waste types:

- 224 = LaF₃ final plutonium decontamination and concentration waste from the BiPO₄ process
- 1C = First decontamination cycle BiPO₄ waste, operational 1944 to 1956.

Agnew et al. (1997b) first shows waste in the 200 series tanks in 1952 for B and T Tank Farms and in 1956 for U Tank Farm. However, Borsheim (1994) reports that originally the 224 wastes were routed to the 6.1 m (20 ft) diameter concrete settling tank (241-361) and overflowed from there to a dry well. The dry well was replaced with a crib by June 1945.

Cell drainage (5 to 6 waste) was also routed to the 241-361 tank. High activity cell drainage was supposed to be routed to tanks 241-B-107 and 241-T-107 in the 1C waste cascades. Borsheim (1994) also notes that the 200 series tanks were each provided with two inlet lines, were not cascaded, and had no overflow lines. Experiments (as of November 1944) indicated that the 224 wastes should contain 3 percent solids by volume.

Borsheim (1994) notes that the "Hanford Works Monthly Reports" show a plan to provide a separate crib for the B Plant cell drainage. The cell drainage was then being disposed to tank 241-B-201 along with the 224 waste. Tank 241-B-201 and the T tanks were in service as sludge settling tanks for 224-B and T wastes, respectively. The remaining 200 series tanks (202, 203, 204) were being excavated and piped in series to increase settling capacity.

Borsheim (1994) reports that by July 1950, tank 241-B-204, which had been in service since November 1948, was filled to a depth of 6.1 m (20 ft) with sludge. The tank overflowed to tank 241-B-203 which had received 10.2 cm (4 in.) of sludge by that time. This suggests that tanks 241-B-201 and 241-T-201 received 224 waste before the other B-200 and T-200 series tanks, and that when the other B-200 series tanks received waste it overflowed from tank 241-B-204 to tank 241-B-203 and to tank 241-B-202. The T-200 series tanks received 224 waste in a similar fashion.

The waste volumes in tanks 241-B-204, 241-B-203, and 241-B-202 are 189 kL (50 kgal), 193 kL (51 kgal), and 102 kL (27 kgal), respectively (Hanlon 1997). Tank 241-B-201 contains 110 kL (29 kgal) and is piped separately from the other B-200 series

tanks, indicating that it received waste independent of the other three B-200 series tanks. The T-200 series tank waste volumes show the same trends.

Expected Types of Solids in the Waste

Hill et al. (1995):	224
Agnew et al (1997a):	224

D3.2 EVALUATION OF FLOWSHEET INFORMATION

Technical flowsheet information (Kupfer et al. 1997) for 224 streams is shown in Table D3-1. The comparative Los Alamos National Laboratory (LANL)-defined waste streams are also shown in Table D3-1.

Table D3-1. Technical Flowsheet and Hanford Defined Waste Defined Waste Streams.

Analyte	Flowsheet 224 ^a (M) (Place)	Flowsheet 224 ^a (M) (Schneider)	HDW 224 ^b (M)
Bi	0.00595	0.00565	0.006
C ₂ O ₄	0.0458	0.0147	0.046
Cr	0.00362	0.00327	0.0068
F	0.272	0.295	0.27
K	0.223	0.218	0.231
La	0.00376	0.00353	0.0038
Mn	0.00514	0.00601	0.0051
Na	1.62	1.60	1.60
NO ₃	1.06	0.684	1.38
PO ₄	0.0322	0.0321	0.038
SO ₄	0.00140	0.00364	0.003
NH ₄	NR	0.0067	NR

HDW = Hanford Defined Waste

NR = Not Reported

^a Appendix C of Kupfer et al. (1997), Bismuth Phosphate Process Flowsheet

^b Agnew et al. (1997a).

D3.3 ASSUMPTIONS FOR RECONCILING WASTE INVENTORIES

Reference inventories in tank 241-T-201 were estimated using an engineering assessment that is based on the results of a sampling event from a tank (241-B-201) that has a nearly identical history and contains the same waste type. The inventories were then compared with the HDW model inventories. The assumptions and observations for the engineering assessment were based on best technical judgement pertaining to input information that can significantly influence tank inventories. This includes: (1) correct prediction of contributing waste types, and correct relative proportions of the waste types, (2) accurate predictions of flowsheet conditions, fuel processed, and waste volumes, (3) accurate predictions of partitioning of components, and (4) accurate predictions of physical parameters such as density, percent solids, etc. By using this evaluation, the assumptions can be modified as necessary to provide a basis for identifying potential errors and/or missing information that could influence the sample- and model-based inventories. Following are the simplified assumptions and observations used for the evaluation.

- Tank waste mass is calculated using the measured density and the tank volume listed in Hanlon (1997). Both engineering assessment-based and model-based inventories are derived using this volume. As a result, inventory comparisons are made on the same volume basis.
- Only the 224 waste stream contributed to solids formation. It is assumed that tanks with the same waste type will have the same concentrations of individual analytes.
- Bulk component (chemical species) information is sufficient for comparing the computed data sets. This information can be obtained from technical flowsheets (see Table D3-1).

D3.4 BASIS FOR CALCULATIONS USED IN THIS ENGINEERING EVALUATION

Because analytical data from a sampling event does not exist for tank 241-T-201, sample data cannot be compared to flowsheet derived data. A review of waste transfer transaction records (Agnew et al. 1997b) confirms that the waste in tank 241-T-201 is from the 224 process. Hill et al. (1995) and Anderson (1990) agree with the designation of the waste in tank 241-T-201 as 224 waste.

The best-basis evaluation for tank 241-B-201 (Appendix D of Conner et al. 1997) includes a comparison of the sample data to flowsheet predictions for 224 waste and shows good agreement between the sample data and the flowsheet predictions. Since tanks 241-B-201 and 241-T-201 received the same waste, in the same time period, and are located in the same position in their respective cascades, it is appropriate to use the tank 241-B-201 sample results to estimate the inventories for tank 241-T-201.

The inventories for tank 241-T-201 were estimated using the inventories for tank 241-B-201 and adjusting them by a factor equal to the ratio of the volumes of waste (1.0) in the two tanks. Estimated component inventories from this engineering evaluation are compared with the HDW-estimated based inventories in Table D3-2. Observations regarding these inventories are noted by component in the following text.

Table D3-2. Comparison of Selected Component Inventory Estimates for Tank 241-T-201.

Component	This evaluation (kg)	HDW estimated ^a (kg)
Bi	13,000	1,230
K	799	851
La	2,080	49.8
NO ₃	6,780	8,050
Mn	2,640	26.4
SO ₄	47.9	27.2
Cr	459	33.3
PO ₄	2,300	846
F	802	2,030
Na	5,250	10,300
H ₂ O %	60.7	69.5

HDW = Hanford Defined Waste

^a Agnew et al. (1997a).

Bismuth. The HDW (Agnew et al. 1997a) estimate is about ten times lower than the engineering inventory estimate. This appears to be caused by the incorrect assumption in the HDW that bismuth is partially soluble.

Nitrate. The HDW estimate is higher than the engineering assessment result. The HDW estimated inventory is derived from the HDW model defined 224 waste stream, in which the nitrate concentration is about 30 percent higher than the Place flowsheet (Appendix C of Kupfer et al. 1997).

Sulfate. The HDW estimated inventory is smaller than the engineering assessment-based inventory. Schneider's waste stream estimate is about three times higher for sulfate than is Place's (Kupfer et al. 1997). If the Schneider value is used in the HDW model, the HDW would probably more closely agree with the assessment value.

Chromium. The HDW-estimated inventory is considerably lower than the sample-based inventory. The data for tank 241-B-201 (Appendix D of Conner et al. 1997)

suggests that about 24 percent of the chromium precipitated; the HDW model assumes a much smaller percent.

Phosphate. The engineering assessment phosphate value is 2.7 times the HDW value. The HDW model defined waste stream phosphate concentration is approximately three times the flowsheet value used. Based on this the phosphate value for the HDW should be larger than the engineering assessment value would be close.

Fluoride. The engineering assessment is based on water soluble fluoride only. The assessment value is about 2.5 times lower than the HDW value. Until a sample is analyzed by a methodology that measures total fluoride, these differences cannot be reconciled.

Sodium. The HDW value is approximately twice the value from this evaluation.

Potassium. The HDW and sampling values for potassium agree fairly well.

Lanthanum. Based on the tank 241-B-201 (Appendix D of Conner et al. 1997) data lanthanum appears to partition between the phases in the tank. The partition factor for lanthanum was 38 percent indicating that less than half of lanthanum would remain in the tanks.

Manganese. The value from this evaluation is much larger than that predicted by Agnew et al. (1997a). The HDW model treats manganese as highly soluble for the B and T-200 series tanks, and predicts much less manganese in the waste.

Total Hydroxide. Once the best-basis inventories were determined, the hydroxide inventory was calculated by performing a charge balance with the valences of other analytes. In some cases this approach requires that other analyte (e.g., sodium or nitrate) inventories be adjusted to achieve the charge balance. During such adjustments the number of significant figures is not increased. This charge balance approach was consistent with that used by Agnew et al. (1997a). The calculated total hydroxide inventories based on engineering assessments and HDW model estimates were 7,600 kg and 1,990 kg, respectively.

Comments On Other Analytes

Strontium. The HDW model assumes there is no strontium in the 224 waste. However, the engineering analysis indicated that tank 241-T-201 contains 127 kg of strontium.

Plutonium. The amount of plutonium is much higher than predicted by the HDW model. The process flowsheet did not contain plutonium values, so plutonium could not be evaluated in the engineering analysis.

D4.0 DEFINE THE BEST-BASIS AND ESTABLISH COMPONENT INVENTORIES

Information about chemical, radiological, and/or physical properties is used to perform safety analyses, engineering evaluations, and risk assessment associated with waste management activities and to address regulatory issues. These activities include overseeing tank farm operations and identifying, monitoring, and resolving safety issues associated with these operations and with the tank wastes. Disposal activities include designing equipment, processes, and facilities for retrieving wastes, and processing them into a form suitable for long-term storage/disposal.

Chemical and radiological inventory information are generally derived using three approaches: (1) component inventories are estimated using the results of sample analyses, (2) component inventories are predicted using the HDW model based on process knowledge and historical information, or (3) a tank-specific process estimate is made based on process flowsheets, reactor fuel data, essential material usage, and other operating data. The information derived from these different approaches is often inconsistent.

As part of this effort, an evaluation of available chemical information for tank 241-T-201 was performed, including the following:

- Data from two 1991 core samples of tank 241-B-201 (Conner et al. 1997).
- An inventory estimate generated by the HDW model (Agnew et al. 1997a).

The calculations based on flowsheet information and factors determined from the bismuth analytical data from tank 241-B-201 have been compared to analytical data (Conner et al. 1997) and the HDW model (Agnew et al. 1997a). These calculations compare well with the analytical data and, in some cases, with the HDW model. Given current resources, the best source of inventory data appears to be the analytical data which was obtained during the 1991 core sampling and analysis event from tank 241-B-201. One analyte, for which the analytical data is suspect is fluoride. Only the water soluble forms of fluoride are reported in the analytical data, because water insoluble fluoride was not measured. Tables D4-1 and D4-2 present the best-basis inventory estimates for the nonradioactive and radioactive waste components, respectively. The inventory values reported in Tables D4-1 and D4-2 are subject to change. Refer to the Tank Characterization Database (TCD) for the most current inventory values.

Best-basis tank inventory values are derived for 46 key radionuclides (as defined in Section 3.1 of Kupfer et al. 1997), all decayed to a common report date of January 1, 1994. Often, waste sample analyses have only reported ^{90}Sr , ^{137}Cs , $^{239/240}\text{Pu}$, and total uranium (or total beta and total alpha), while other key radionuclides such as ^{60}Co , ^{99}Tc , ^{129}I , ^{154}Eu , ^{155}Eu , and ^{241}Am , etc., have been infrequently reported. For this reason it has been necessary to derive most of the 46 key radionuclides by computer models. These models estimate radionuclide activity in batches of reactor fuel, account for the split of radionuclides to

various separations plant waste streams, and track their movement with tank waste transactions. (These computer models are described in Kupfer et al. 1997, Section 6.1 and in Watrous and Wootan 1997.) Model generated values for radionuclides in any of 177 tanks are reported in the HDW Rev. 4 model results (Agnew et al. 1997a). The best-basis value for any one analyte may be either a model result or a sample or engineering assessment-based result if available. (No attempt has been made to ratio or normalize model results for all 46 radionuclides when values for measured radionuclides disagree with the model.) For a discussion of typical error between model derived values and sample derived values, see Kupfer et al. 1997, Section 6.1.10. The radionuclide inventories shown in Table D4-1 are based primarily on Agnew et al. (1997a) HDW model estimates for tank 241-T-201.

Table D4-1. Best-Basis Inventory Estimates for Nonradioactive Components in Tank 241-T-201 (Effective May 31, 1997). (2 Sheets)

Analyte	Total inventory (kg)	Basis (S, M, C, or E) ¹	Comment
Al	473	E	
Bi	13,000	E	
Ca	1,680	E	
Cl	227	E	
TIC as CO ₃	1,550	M	
Cr	459	E	
F	802	E	Only the water soluble forms of fluoride are reported in the analytical data.
Fe	1,840	E	
Hg	0	M	
K	799	E	
La	2,080	E	
Mn	2,640	E	
Na	5,250	E	
Ni	65.9	E	
NO ₂	121	E	
NO ₃	6,780	E	
OH _{TOTAL}	7,600	C	Calculated from charge balance
Pb	0	M	
P as PO ₄	2,300	E	

Table D4-1. Best-Basis Inventory Estimates for Nonradioactive Components in Tank 241-T-201 (Effective May 31, 1997). (2 Sheets)

Analyte	Total inventory (kg)	Basis (S, M, C, or E) ¹	Comment
Si	2,780	E	
S as SO ₄	47.9	E	
Sr	127	E	
TOC	325	E	
U _{TOTAL}	8.13	M	
Zr	1.47	E	

¹S = Sample-based

M = Hanford Defined Waste model-based, Agnew et al. (1997a)

E = Engineering assessment-based

C = Calculated by charge balance; includes oxides as hydroxides, not including CO₃, NO₂, NO₃, PO₄, SO₄, and SiO₃.

Table D4-2. Best-Basis Inventory Estimate for Radioactive Components in Tank 241-T-201, Decayed to January 1, 1994 (Effective July 2, 1996). (2 Sheets)

Analyte	Total Inventory (Ci)	Basis (S, M, or E) ¹	Comment
³ H	5.63 E-04	M	
¹⁴ C	0.0435	E	
⁵⁹ Ni	4.96 E-05	M	
⁶⁰ Co	5.60 E-05	M	
⁶³ Ni	0.00457	M	
⁷⁹ Se	3.68 E-05	M	
⁹⁰ Sr	275	E	
⁹⁰ Y	275	E	Referenced to ⁹⁰ Sr.
^{93m} Nb	1.45 E-04	M	
⁹³ Zr	1.75 E-04	M	
⁹⁹ Tc	0.00121	M	
¹⁰⁶ Ru	4.20 E-11	M	
^{113m} Cd	4.89 E-04	M	
¹²⁵ Sb	6.46 E-05	M	
¹²⁶ Sn	5.55 E-05	M	
¹²⁹ I	2.29 E-06	M	
¹³⁴ Cs	2.78 E-06	M	
^{137m} Ba	99.3	E	Referenced to ¹³⁷ Cs.
¹³⁷ Cs	105	E	
¹⁵¹ Sm	0.139	M	
¹⁵² Eu	1.82 E-04	M	
¹⁵⁴ Eu	0.512	E	
¹⁵⁵ Eu	0.0164	M	
²²⁶ Ra	8.22 E-09	M	
²²⁷ Ac	4.34 E-08	M	
²²⁸ Ra	5.28 E-13	M	
²²⁹ Th	1.02 E-10	M	
²³¹ Pa	1.00 E-07	M	
²³² Th	4.62 E-14	M	
²³² U	5.36 E-08	M	

Table D4-2. Best-Basis Inventory Estimate for Radioactive Components in Tank 241-T-201, Decayed to January 1, 1994 (Effective July 2, 1996). (2 Sheets)

Analyte	Total Inventory (Ci)	Basis (S, M, or E) ¹	Comment
²³³ U	2.45 E-09	M	
²³⁴ U	0.00267	M	
²³⁵ U	1.19 E-04	M	
²³⁶ U	2.33 E-05	M	
²³⁷ Np	7.51 E-06	M	
²³⁸ Pu	3.21 E-04	M	
²³⁸ U	0.00271	M	
^{239/240} Pu	155	E	
²⁴¹ Am	4.25	E	
²⁴¹ Pu	0.0135	M	
²⁴² Cm	3.70 E-06	M	
²⁴² Pu	6.23 E-08	M	
²⁴³ Am	3.08 E-09	M	
²⁴³ Cm	7.98 E-08	M	
²⁴⁴ Cm	7.84 E-08	M	

¹S = Sample-based

M = Hanford Defined Waste model-based, Agnew et al. (1997a)

E = Engineering assessment-based.

D5.0 APPENDIX D REFERENCES

- Agnew, S. F., J. Boyer, R. A. Corbin, T. B. Duran, J. R. FitzPatrick, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997a, *Hanford Tank Chemical and Radionuclide Inventories: HDW Model Rev. 4*, LA-UR-96-3860, Los Alamos National Laboratory, Los Alamos, New Mexico.
- Agnew, S. F., R. A. Corbin, T. B. Duran, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997b, *Waste Status and Transaction Record Summary (WSTRS Rev. 4)*, LA-UR-97-311, Rev. 0, Los Alamos National Laboratory, Los Alamos, New Mexico.
- Anderson, J. D., 1990, *A History of the 200 Area Farms*, WHC-MR-0132, Westinghouse Hanford Company, Richland, Washington.
- Borsheim, G. L., 1994, *Bismuth Phosphate 224 Building Waste Data*, Memo to Distribution, Westinghouse Hanford Company, Richland, Washington.
- Conner, J. M., K. M. Hodgson, L. C. Amato, J. L. Stroup, S. R. Wilmarth, and R. T. Winward, 1997, *Tank Characterization Report for Single-Shell Tank 241-B-201*, HNF-SD-WM-ER-550, Rev. 1, Lockheed Martin Hanford Corporation, Richland, Washington.
- Hanlon, B. M., 1997, *Waste Tank Summary Report for Month Ending March 31, 1997*, WHC-EP-0182-108, Lockheed Martin Hanford Corporation, Richland, Washington.
- Hill, J. G., G. S. Anderson, and B. C. Simpson, 1995, *The Sort on Radioactive waste Type Model: A Method to Sort Single-Shell Tanks into Characteristic Groups*, PNL-9814, Rev. 2, Pacific Northwest Laboratory, Richland, Washington.
- Hodgson, K. M., and M. D. LeClair, 1996, *Work Plan for Defining a Standard Inventory Estimate for Wastes Stored in Hanford Site Underground Tanks*, WHC-SD-WM-WP-311, Rev. 1, Lockheed Martin Hanford Corporation, Richland, Washington.
- Kupfer, M. J., A. L. Boldt, B. A. Higley, K. M. Hodgson, L. W. Shelton, and R. A. Watrous (LMHC), S. L. Lambert, and D. E. Place (SESC), R. M. Orme (NHC), G. L. Borsheim (Borsheim Associates), N. G. Colton (PNNL), M. D. LeClair (SAIC), R. T. Winward (Meier Associates), and W. W. Schulz (W²S Corporation), 1997, *Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes*, HNF-SD-WM-TI-740, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.

Watrous, R. A., and D. W. Wootan, 1997, *Activity of Fuel Batches Processed Through Hanford Separations Plants, 1944 Through 1989*, HNF-SD-WM-TI-794, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.