LA-UR- 98 - 3261

Approved for public release;
distribution is unlimited.

Title: Data Mining

Author(s): Kenneth Lee, Hillol Kargupta,
Brian G. Stafford,
Kevin L. Buescher,
Binoy Ravindran,

X-CM

Submitted to: DOE OFFICE OF SCIENTIFIC AND TECHNICAL
INFORMATION (OSTI)

RECEIVED

APR 13 1999

OSTI

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Los Alamos
NATIONAL LABORATORY

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the University of California for the U.S. Department of Energy under contract W-7405-ENG-36. By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. The Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Data Mining

Kenneth Lee*, Hillol Kargupta, Brian G. Stafford,
Kevin L. Buescher and Binoy Ravindran

Abstract

This is the final report of a one-year, Laboratory Directed Research and Development (LDRD) project at the Los Alamos National Laboratory (LANL). The objective of this project was to develop and implement data mining technology suited to the analysis of large collections of unstructured data. This has taken the form of a software tool, PADMA (PARallel Data Mining Agents), which incorporates parallel data accessing, parallel scalable hierarchical clustering algorithms, and a web-based user interface for submitting Structured Query Language (SQL) queries and interactive data visualization. We have demonstrated the viability and scalability of PADMA by applying it to an unstructured text database of 25,000 documents running on an IBM SP2 at Argonne National Laboratory. The utility of PADMA for discovering patterns in data has also been demonstrated by applying it to laboratory test data for Hepatitis C patients and autopsy reports in collaboration with the University of New Mexico School of Medicine.

Background and Research Objectives

Data mining refers to the process of extracting useful information from data. In recent years, it has become apparent that the increasing quantity of data gathered by organizations is a resource that must be exploited by computerized analysis in the same way that natural resources have traditionally been utilized by chemical and physical processing. Such analysis is becoming critical to decision making in business settings. Data mining has been routinely employed on *moderate* quantities (gigabytes) of *structured* data in the

*Principal Investigator, email: ken_lee@lanl.gov

commercial sector to predict consumer behavior by associating known conditions with known responses. For example, financial institutions may use past account information to predict credit card usage and responses to marketing campaigns. The objective of this project is to develop and implement data mining technology suited to the exploration and analysis of *large* collections (hundreds of gigabytes, terabytes, etc.) of *unstructured* data.

Existing work in the literature has addressed various aspects of mining large quantities of unstructured data. The goal of this project was to integrate these pieces for the special case of textual data and to perform experiments to investigate the scalability of the resulting system. The first element of such a system is the capability to access data in a parallel, distributed fashion. There are two reasons for using parallel data access. First, the data may be collected and maintained in a variety of locations. For instance, a consortium of banks may be willing to have a third party access and analyze their data in order to prevent fraud, but each bank would be unwilling to release control of their data. Second, it may not be feasible to store and analyze a large collection of data on a single computer system. The advantages of accessing data in parallel are discussed in [1].

The second element of such a data mining system is a mechanism for performing distributed analysis on the data and coordinating the results. This is a fairly recent line of research. Software programs that autonomously perform tasks have come to be known as "agents," and have seen use for tasks such as filtering email and internet bargain hunting (see [2] and [3] for further information). Coordinating the efforts of such agents amounts to a parallel search and optimization problem. Stochastic search procedures such as Genetic Algorithms are well-suited to solving such problems (see, for example, [4]).

The third element of such a data mining system is the ability for the user to interpret the results and provide feedback that guides the analysis (see [3] and [5] for examples). This is necessary because data mining on unstructured data often starts with a vague inquiry that develops into a more specific search based on patterns that emerge during the analysis. Although iteratively performing keyword searches on text data can be viewed as a form of user feedback, such probing can prove ineffective because a large number of keywords may be needed to distinguish between the various *contexts* in which these words occur. Consider the following two phrases, which might occur in a collection of medical records:

“...flu shot wound up being critical condition for immunity...”

“...gun shot wound, critical condition...”

Although these phrases share several words, the context in which they occur is entirely different. This points to the need for more general feedback mechanisms to separate such cases according to the user's interpretation.

The goal of this project was to select or create methods to satisfy all of the three needs listed above. These pieces were integrated to form a new software tool, PArallel Data Mining Agents (PADMA), suited to mining large collections of text documents. Additionally, we required that the system be robust to spelling errors in the documents. Another objective of the research was to test the scalability of PADMA and to demonstrate the usefulness of its interface for incorporating the user's interpretation of the data.

Importance to LANL's Science and Technology Base and National R&D Needs

This research and the associated software tools developed in this project impact the analysis and assessment aspects of the Laboratory's nonproliferation and stockpile stewardship missions. In addition, these tools have applications in the commercial sector for increasing economic competitiveness by enhancing decision-making capabilities. In each of these application areas, there exist large, distributed repositories of unstructured data from which it is desired to extract summary information or information related to a specific topic. Frequently, such data consists of unorganized text documents filled with inconsistent terminology, spelling errors, transcription errors, or errors introduced by electronic scanning. The PADMA system assembled in this project is ideal for exploring such data. The basic PADMA system is designed for text documents; however, the low-level operation of its agents could conceivably be adapted to other domains such as still images, strip charts, CAD files, audio records, etc.

As a specific, detailed example, consider the problem of extracting information from archived nuclear weapons data. Such data is not only distributed around the DOE complex, but resides at and is maintained in scattered locations within each site as well. Although the scanned images of documents are retained for reference purposes, a character recognition process is performed to produce documents that can be searched

electronically. Such documents contain numerous spelling errors. Further, the document contents span a large time frame and author base, resulting in inconsistent or ambiguous terminology. The widely varied uses of such an archive precludes a high-level organization suitable to browsing of the information. Novice users will most likely be unaware of appropriate keywords to use in searching the database. The ongoing experiments, analyses, and simulations associated with Science-Based Stockpile Stewardship will further increase the size and variety of nuclear weapons data, making tools such as PADMA vital for accessing our corporate memory.

Other examples of problem domains suitable for PADMA abound. For instance, equipment-servicing logs could be examined to determine common failure modes. The diagnostic data produced in the course of allocating computer resources could be mined to determine bottlenecks. Archives of simulation dumps could be mined to determine what types of simulations have been performed previously and which input parameters are appropriate for particular situations. Medical records can be explored to help determine causes of known diseases (see (4) for an example) or to detect the outbreak of new or suspicious health problems (this has application to biological and chemical warfare defense).

Scientific Approach and Accomplishments

The research approach was to develop and integrate the following elements into the PADMA tool:

- (a) parallel data access and query processing;
- (b) distributed analysis by mining agents to perform hierarchical analysis, such as clustering, on the data; and
- (c) a user interface to facilitate interpretation of the results and to allow user feedback to direct the analysis.

Each of these areas will be described below, followed by a summary of experimental results on PADMA's performance. Finally, modifications that allow PADMA to mine data other than text documents will be described.

At the most basic level, data mining agents must be able to access data and to communicate results to a central location. This is achieved in PADMA by using PPFS

(Parallel Portable File System—see [6]) for parallel data access and MPI (Message Passing Interface) for interprocess communication. Each data-mining agent maintains its own disk subsystem to perform input/output operations locally. Using the PPFS library, a subset of SQL (Structured Query Language) was implemented for PADMA. This allows the user to speed up the analysis by selecting a subset of the entire dataset, such as files containing a combination of keywords. Details about these basic functions can be found in (1) and (3).

The real power of PADMA comes from the distributed analysis performed by the data mining agents. The primary analysis method used for text data is *hierarchical clustering* (see [7]). Clustering is a general technique for partitioning data points into groups, or clusters, so that all points within a cluster are near each other and far from points in other clusters. Hierarchical clustering then groups these low-level clusters (which may consist of isolated data points) into larger clusters. This process continues until, at the highest level, one cluster contains all data points. Each level compresses information by only passing the location of the center of each cluster and the number of points in each cluster to the next level. As an illustrative example, suppose that the data points consist of the geographical location of all the chairs in the United States. Then the lowest-level clusters would consist of individual houses and buildings (and some isolated chairs). Clusters in the next level would correspond to towns and cities. The next level would consist of metropolitan areas, etc. In PADMA, each agent performs hierarchical clustering on its local data and passes the greatly condensed information about its highest-level clusters to a central location, where clustering continues. Specific details about how this is performed can be found in (1) and (3).

The preceding discussion suppressed one crucial detail: how does one compute “distances” between text documents so they can be clustered? This is accomplished by using *n-gram vectors* (see [8]). An *n-gram* of text is a pattern consisting of *n* adjacent characters. For example, the 2-grams of the string “It bit” are “it” (twice), “t_”, “_b”, and “bi”. For an entire document, one computes a vector consisting of the number of times each *n-gram* appears ($n=4$ or 5 usually suffices). Thus, documents are mapped to points in a high-dimensional space, allowing clustering to be performed. A consequence of

representing documents by n-gram vectors is that the representation is robust to spelling errors: randomly perturbing words in a document has little impact on its n-gram vector.

The final element of PADMA is its user interface. Analysis results from the agents are fed to a central location where the user can visualize the clusters using a Java-sensitive browsing tool that represents the clusters graphically. During the clustering operation, the n-gram vectors are also used to associate each cluster with a list of *central words*. These are words which are common to documents within a cluster and which differentiate documents from separate clusters. The central words serve two purposes. First, they provide summary information to the user about the documents in each cluster. By selecting a cluster with the browser, the user can view its central words as well as the lower-level clusters that make up that cluster. By navigating down through the hierarchy, the user can eventually reach the individual documents. Observing the structure of the clusters and their central words gives a sense of how the documents are related. The second purpose of the central words is to provide a feedback mechanism that allows the user to change the underlying distance measure, which determines the clusters. The user can edit the list of central words associated with each cluster to remove irrelevant words or words that serve to falsely distinguish clusters. This information is then used to weight the components of the n-gram vectors, changing the way in which distances between documents are computed. Upon re-clustering the documents, the user obtains more relevant groupings. This process can be iterated as many times as desired. Sample results of using this feature of PADMA to analyze autopsy reports are presented in (4).

Experiments were performed with PADMA to assess its scalability [see (1) and (3)]. In these experiments, the number of agents was increased and the decrease in processing time was observed. The experimental data consisted of over 25,000 text documents from the TIPSTER database ([9]), each about 1,000 characters long. Two types of experiment were performed. In the first, the raw data was clustered. In the second, a parallel database operation (e.g., selection of a subset with an SQL query) was performed and the resulting documents were clustered. The computation was performed on a 128-node IBM SP2 at Argonne National Laboratory. In each case, *linear scaling* was observed; the execution time decreased in proportion to the number of agents

employed. Thus, PADMA shows promise for mining very large datasets by increasing the number of agents and computers.

The preceding discussion described the mining of text documents using n-gram vectors and hierarchical clustering. This is an important, but small, subset of the possible range of data types and analysis techniques. Part of our research involved finding ways to make PADMA applicable to other data types, such as numeric data in tabular form, and other analysis techniques, such as linear classifiers and decision trees. Genetic Algorithms (GAs) are a generic technique for performing search and optimization that work well in concert with data mining agents.

A GA performs a search in a manner that is analogous to the selective breeding of organisms. The algorithm maintains a population of individuals, each represented by a binary gene sequence, and evolves individuals whose fitness increases from generation to generation. In each generation, the least fit individuals are eliminated, the most fit individuals are duplicated, and a new population is formed by crossbreeding the survivors. As an example, suppose that it is desired to locate variables in vector-valued data (or columns in a spreadsheet) which are highly correlated with one another. Then each individual in the GA would correspond to a fixed group of variables, and this information would be encoded in the binary gene by placing a 1 in the positions corresponding to those variables and placing 0s in the remaining positions of the gene. The fitness of each individual could then be evaluated from the data by computing the norm of the correlation matrix for that individual's variables.

Our research indicates that GAs are ideal for distributed analysis. Each agent maintains its own population and, at certain time intervals, broadcasts the gene strings of its best individuals so other agents may profit from that agent's experience. The parallelism introduced by the communication of genes can be further extended by allowing the agents to also communicate information about which crossbreeding strategies are best. Thus, the agents can also transmit information about transformations of the underlying space that allow more effective search (see [4] and (2) for more detail). In (4), we report the results of applying a modified version of PADMA to the analysis of tabular data pertaining to Hepatitis C patients using correlation matrices and decision trees in order to determine risk factors for this disease.

As a final note, several corporations have expressed interest in licensing the PADMA technology. The Civilian and Industrial Technologies Program Office CIT-PO at LANL is currently handling the copyright process and the transfer of this technology.

Publications

1. Kargupta, H.; Stafford, B.; and Hamzaoglu, I., "Parallel Data Mining Agents for Scalable Text Classification," Proceedings, Symposium on High Performance Computing, The Society for Computer Simulation International, pp. 290-295, (1997)..
2. Kargupta, H. and Stafford, B., "From DNA to Protein: Transformations and Their Possible Role in Linkage Learning," Proceedings, International Conference on Genetic Algorithms, Morgan Kaufmann, San Francisco, p. 409, (1997).
3. Kargupta, H.; Stafford, B.; and Hamzaoglu, I., "Scalable, Distributed Data Mining Using an Agent Based Architecture," Proceedings, 3rd International Conference on Knowledge Discovery and Data Mining (KDD-97), AAAI Press, Menlo Park, CA, pp. 211-214, (1997).
4. Kargupta, H.; Stafford, B., and Hamzaoglu, I., "Web Based Parallel/Distributed Medical Data Mining Using Software Agents," Tutorial presented at American Medical Informatics Fall Symposium, Nashville, TN (1997).

References

- [1] Dewitt, D. and Gray, J., "Parallel Database Systems: The Future of High Performance Database Systems," *Communications of the ACM* **35**, pp. 85-98, (1992).
- [2] Maes, P., "Agents that Reduce Work and Information Overload," *Communications of the ACM* **37**, pp. 31-40, (1994).
- [3] Moukas, A., "Amalthaea: Information Discovery and Filtering using a Multiagent Evolving Ecosystem," *Applied Artificial Intelligence* **11**, pp. 437-457, (1996).
- [4] Kargupta, H., "The Gene Expression Messy Genetic Algorithm," Proceedings of the IEEE International Conference on Evolutionary Computation, IEEE Press, pp. 814-819, (1996).
- [5] McElligott, M. and Sorensen, H., "An Evolutionary Connectionist Approach to Personal Information Filtering," Proceedings, Fourth Irish Neural Network Conference, pp. 141-146, (1994).

- [6] Huber, J., et al., "PPFS: A High Performance Portable Parallel File System," Technical Report UIUCDCS-R-95-1903, Dept. of Computer Science, University of Illinois at Urbana-Champaign, (1995).
- [7] Rasmussen, E., "Clustering Algorithms," in Information Retrieval: Data Structures and Algorithms (Frakes, W. and Baeza-Yates, R. Editors), Prentice-Hall, pp. 419-442, (1992).
- [8] Damashek, M., "Gauging Similarity via n-grams: Language Independent Categorization of Text," *Science* **267**, pp. 843-848, (1995).
- [9] http://www ldc.upenn.edu/ldc/catalog/html/text_html/tipster.html