doeqtr.dec/sc#9a

DDE/PC/92543-T

DOE/PC: DE-FG22-92PC92543

MICRO-AGGLOMERATE FLOTATION FOR DEEP CLEANING OF COAL

Quarterly Progress Report: October 1 - December 30, 1995

by

S. Chander

R. Hogg

April 1996

Work Performed Under Contract No.
DE-FG22-92PC92543

For

U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, PA

by

Penn State University
University Park, PA 16802

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

OBJECTIVES

The goals of this research program are to demonstrate the technical and economic feasibility of a micro-agglomerate flotation process and to establish the essential criteria for reagent selection and system design and operation.

1. Introduction

The development of practical technologies for the deep cleaning of coal has been seriously hampered by the problems of carrying out efficient coal/mineral separations at the very fine sizes (often finer than 10 μm) needed to achieve adequate liberation of the mineral matter from the coal matrix. It is generally recognized that surface-based separation processes such as froth flotation or selective agglomeration offer considerable potential for such applications but there remain many problems in obtaining the required selectivity with acceptable recovery of combustible matter. In froth flotation, selectivity is substantially reduced at fine sizes due, primarily, to overloading of the froth phase which leads to excessive carryover of water and entrained mineral matter. Oil agglomeration, on the other hand, can provide good selectivity at low levels of oil addition but the agglomerates tend to be too fragile for separation by the screening methods normally used. The addition of larger amounts of oil can yield large, strong agglomerates which are easily separated but the selectivity is reduced and reagent costs can become excessive.

We are investigating the use of a hybrid process - Micro-agglomerate flotation - which is a combination of oil-agglomeration and froth flotation. The basic concept is to use small quantities of oil to promote the formation of dense micro-agglomerates with

minimal entrapment of water and mineral particles, and to use froth flotation to extract these micro-agglomerates from the water/dispersed-mineral phase. Since the floating units are agglomerates (about 30-50 mm in size) rather than individual coal particles (1-10 mm) the problems of froth overload and water/mineral carryover should be significantly alleviated.

Micro-agglomerate flotation has considerable potential for the practical deep cleaning of coal on a commercial scale. In principle, it should be possible to achieve both high selectivity and high yield at reasonable cost. The process requires only conventional, off-the-shelf equipment and reagent usage (oil, surfactants, etc.) should be small. There are, however, complications. The process involves at least five phases: two or more solids (coal and mineral), two liquids (oil and water) and one gas (air). It is necessary to maintain precise control over the chemistry of the liquid phases in order to promote the interfacial reactions and interactions between phases necessary to ensure selectivity. Kinetics as well as thermodynamic factors may be critical in determining overall system response.

The research program has been organized into several specific tasks as indicated below.

Task 1. Interfacial Studies

In order to provide a rational basis for reagent selection, fundamental studies of the various interfaces involved in Micro-Agglomerate Flotation are being conducted. In particular, data are being obtained on:

- liquid/air and liquid/liquid interfacial tensions for aqueous solution/hydrocarbon systems.
- solid/liquid/air and solid/liquid/liquid contact angles for coals and important minerals (quartz, pyrite, etc.).

Task 2. Emulsification

The emulsification of oil in the presence of fine particles plays a critical role in the development of micro-agglomerate properties and in the rejection of pyritic sulfur and ash during agglomerate formation. The process is being investigated by measurement of emulsion droplet size distributions in agitated vessels of standard design. The effects of:

- coal type (especially hydrophobicity)
- surfactant type and concentration
- hydrodynamics

are of particular concern.

Task 3. Agglomerate Growth and Structure

In order to achieve the degree of selectivity required for effective deep cleaning of fine coal it is desirable to produce agglomerates which are large enough to be separated from the dispersed, refuse material and have sufficiently high density to minimize the inclusion of water and dispersed mineral particles. Studies of size/density relationships for oil-agglomerated fine coal are an important part of the research program. The role of hydrodynamics in agglomerate densification is of particular interest.

research program. The role of hydrodynamics in agglomerate densification is of particular interest.

Task 4 - Agglomerate Flotation

The final separation of selectively aggregated fine coal particles from mineral matter is to be achieved using froth flotation. Standard procedures for flotation testing are being used to evaluate the floatability of micro-agglomerates formed under various conditions. Specific studies being carried out include determination of the effects of micro-agglomerate size and structure on the kinetics of flotation and evaluation of the potential for further cleaning of the floated material in multi-stage flotation circuits.

PROJECT STATUS

Experimental work and data analysis on Tasks 1 and 2 (Interfacial Studies, Emulsification) have been completed. This aspect of the work has been written up as part of a Ph.D. thesis (H. Polat 1995) and will be presented in detail in the final project report.

Data analysis and evaluation for Tasks 3 and 4 are continuing.

H.Polat, 1995, "The Use of PEO/PPO Block Copolymers to Enhance Fine Coal Cleaning by Flotation," Ph.D. Thesis, The Pennsylvania State University, PA.