DOE/ER/ 40112--T2

FINAL TECHNICAL REPORT FY/93

FOCUSED TRANSPORT OF INTENSE CHARGED PARTICLE BEAMS

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

HH
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DE-AIOS-83ER 40112 U.S. DEPARTMENT OF NAVY

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

CONTENTS

Introduction.....	1
Review of Research Accomplishments.....	2
Description of Research During Current Performance Period.....	11
References.....	16
Appendix I - Longitudinal Envelope Equation.....	22
Appendix II - Initial Shaping of a Parabolic Bunch.....	24
Appendix III - Experiment and Simulation of an Expanding Parabolic Bunch.....	27
Figures.....	33

INTRODUCTION

Many recent developments in accelerator technology have increased the need for a better understanding of the physics of intense-beam transport. Of particular interest to the work described here is the appearance, as beam intensities are increased, of a class of nonlinear phenomena which involve the collective interaction of the beam particles. Beam intensity, used as a measure of the importance of space-charge collective behavior, depends on the ratio of current to emittance. The nonlinear beam dynamics, and any resulting emittance growth, which are characteristic of the intense-beam regime, can therefore occur even at low currents in any accelerator system with sufficiently high intensity, especially in the low beta section. Furthermore, since emittance of a beam is difficult to reduce, the ultimate achievement of necessary beam luminosities requires the consideration of possible causes of longitudinal and transverse emittance growth at every stage of the beam lifetime.

The research program described here has addressed the fundamental physics which comes into play during the transport, acceleration and focusing of intense beams. This program has been in place since FY78, and has enjoyed support during that period from the Division of High Energy Physics, as well as support for closely related research during the same period, that has also been provided by the Department of Energy in connection with the Heavy Ion Fusion research effort. As will be discussed below, this research has been performed in close collaboration with the experimental and theoretical effort at the University of Maryland, as well as at the Lawrence Berkeley and Lawrence Livermore National Laboratories of the Department of Energy. It is also important to note that support from the Division of High Energy Physics has continued after the expiration of the particular contract discussed here, so that this is actually a continuing research effort.

Because of the long term and ongoing nature of the research program discussed here, this report is divided into two sections. The first section constitutes a long term review of the accomplishments which have resulted from the research effort reported, especially in pioneering the use of particle-in-cell (PIC) computer simulation techniques for simulation of the dynamics of space-charge-dominated beams in particle accelerators. The following section emphasizes, in more detail, the accomplishments of the FY 92/93 period immediately prior to the termination of this particular avenue of support.

II REVIEW OF RESEARCH ACCOMPLISHMENTS

Introduction

Applications of accelerators in which space charge collective behavior can become significant span a diverse range of parameters. These range from high quality beams with inherently high beam power, such as those required for heavy ion fusion drivers, particle beam weapons, high power free electron laser sources, and spallation neutron accelerators, to the low energy beam transport in SSC, and even to the low current but very low emittance beams necessary for ion beam projection lithography. Space charge collective behavior can also influence beam characteristics other than the emittance of the bulk of the beam. Examples of this are beam halo formation, the threshold for onset of the longitudinal microwave instability, and the equipartitioning of the beam energy between dimensions, all of which can be substantially influenced by space charge.

Though a considerable body of theoretical work has now been built using computer simulations to predict intense particle beam dynamics, and there have now been several instances of the experimental verification of theoretical predictions, few experiments have systematically investigated the behavior of highly space-charge-dominated beams. Over a wide range of parameters, the full nonlinear system of equations necessary to describe the transport and bunching dynamics can be written, in the beam frame, using normalized variables characterized by a relatively small number of free parameters. It is therefore possible to experimentally investigate the full range of nonlinear dynamics on a small experiment, when the appropriate ratio of beam current to emittance and the externally applied fields are scaled accordingly. The electron beam transport experiment at the University of Maryland is a small experiment which has been designed so that a wide range of scaled parameter-space can be explored by varying the experimental parameters. In addition to research into the basic linear and nonlinear physics of space-charge-dominated transport, the research program described below has therefore also emphasized understanding the scaled behavior of the University of Maryland Transport Experiment and how the lessons learned on that experiment can be extended to much larger, and more expensive, accelerator transport systems.

Transverse Dynamics

Because of the complexity of studying the nonlinear dynamics of a space-charge-dominated beam in a complex accelerating structure, early studies were conducted under a number of simplifying assumptions. The longitudinal and transverse dynamics were treated separately in a manner likely to be appropriate at the center of a long beam bunch. Also various complications such as those due to lens nonlinearities and beam acceleration were neglected. As will be discussed below, such complications have been gradually incorporated into the models, but in a sufficiently systematic way that understanding their consequences could be built upon the previous results. The first studies in this progression were conducted in order to understand the transverse equilibrium and stability of a space-charge-dominated beam in a linear focusing channel with periodic focusing elements.

For sufficiently low currents, the beam evolution in a particle accelerator can be described by integrating the non-interacting orbits of an ensemble of particles which sample the beam phase space, and then averaging over those orbits to obtain measurable macroscopic beam characteristics. As the beam current is increased, the space charge forces become significant, and must be included in the integration of particle orbits. If the current is sufficiently low it may still be sufficient to represent the space charge forces by some simple average over the beam, as for example, calculating these forces by assuming a uniform elliptical beam whose density is the total current divided by the beam area.

However, as the current is further increased, nonlinear collective space charge modes become possible in the beam system and a more complex description, such as is represented by the Vlasov equation, becomes necessary to adequately represent all the degrees of freedom of the dynamical system. Though a particle beam system usually consists of one predominant species of particles, and so is not charge-neutral, the external focusing forces act in very much the same way as a species of very heavy positive ions would act in an electron plasma. That is, the focusing forces act to "neutralize" the beam in the same way as a background of immobile particles of charge opposite to the beam particles. The beam system can therefore behave in a manner very similar to a neutral plasma. For example, a focused electron beam can support

oscillations, in the beam frame, at the plasma frequency, $\omega_p^2 = \frac{ne^2}{m\epsilon_0}$, where n is the particle density, e the electron charge, m the electron mass and ϵ_0 the permittivity of free space.

Another concept from plasma physics which becomes applicable to high current beams is the Debye length, $\lambda_D = v_{th}/\omega_p$, where v_{th} is the local rms average, or thermal, velocity of the beam. Because thermal particles generally travel a Debye length during a plasma period, a plasma cannot generally support plasma oscillations on a scale-length shorter than a Debye length.

It is a characteristic of the matched high current beam equilibrium in a periodic focusing system that, viewed in the beam frame, the lens period is of the order of the beam plasma period and that, if the beam emittance is low enough so that the phase advance per period becomes substantially depressed, the Debye length becomes comparable to, or smaller than, the beam radius. Such beam systems can therefore support plasma oscillations and the wavelengths of those oscillations can become, for very low emittance beams, substantially smaller than the beam radius. In this regime, the beam requires a self-consistent treatment of the space charge to adequately model the collective modes which can be present.

In addition, for a beam which is long compared with the radius of the transport system, plasma electrostatic waves can propagate along the beam. As will be discussed below, if the longitudinal thermal velocity of the beam particles is less than the wave propagation velocity, propagation of these waves can be nonlinear and dispersive. There is also some evidence, although it is not yet well understood, of space-charge equipartition of thermal energy between the longitudinal and transverse directions, even in the long beam limit.

The difficulty of analytic calculation of the full self-consistent, nonlinear, collective dynamics of a bounded plasma, have made numerical simulation an important tool for quantitative investigation of intense-beam accelerators. The beams of interest have lifetimes of only tens or hundreds of plasma periods and are generally measured in distances of tens or hundreds of Debye lengths. As will be discussed below, PIC simulation techniques developed for plasma simulations¹ have proved to be particularly suitable for simulating intense beam systems.

Early studies using simulations in the study of intense beams emphasized fundamental questions of equilibrium and stability during the propagation of a space-charge-dominated beam. To facilitate these studies, simplifying assumptions were made about accelerator characteristics, and longitudinal and transverse physics were treated separately. This has resulted in a large body of work in which simulations were used to examine the stability of a low emittance beam in an alternating gradient focusing system.²⁻¹⁰ These simulations both agreed with theoretical predictions^{2,3} of the growth rates and instability thresholds, and were also verified experimentally.¹¹⁻¹⁴

Improvements in understanding basic intense-beam transport physics and the gradual development of confidence in numerical methods, have more recently led to the development of increasingly sophisticated techniques which permit relaxation of the early simplifying assumptions. This has resulted in the attainment of a high level of detailed agreement between simulation and experiment¹⁵ which has, in turn, further increased confidence in the numerical techniques.

Advances in computer simulation code development, as well as the reduced cost of running codes on modern computer hardware, have made it feasible to run realistic full scale multi-dimensional simulations of intense-beam accelerator systems. This is especially true of the University of Maryland experiment where the apparatus is azimuthally symmetric, and this substantially simplifies the simulations required for accurate modeling. However, it is worth emphasizing that the research program detailed here aspires to a more ambitious aim than end-to-end simulation of the Maryland transport experiments. If simulations are to be useful for reliable extrapolation beyond the region where agreement to experiment has been obtained, it is important to understand which details in the numerical model are important for the representation of the underlying physics which is responsible for specific features of the experimental behavior. A major component of the research program is therefore to use the experiment and simulations, in concert, to refine that understanding. This is facilitated by the design of the Maryland experiment, which because of its flexibility, relatively low cost and extensive diagnostic capability, is explicitly appropriate to the study of the nonlinear physics of intense space-charge-dominated beams.

In our examination of the transverse dynamics, for example, it was desired to differentiate between nonlinearities in the external magnet system, and nonlinearities due to space charge, as a cause of beam emittance growth. It was therefore possible to simply turn off the magnet nonlinearities in the simulation and examine the consequences. This numerical experiment would have been difficult to duplicate in the experimental apparatus.

Another example which illustrates the interplay between simulation and experiment is our study of the downstream emittance on the Maryland transport experiment. The focusing magnet characteristics in this experiment, including the nonlinearities in the focusing fields, have been carefully measured.¹⁶ However, simulations which included careful modeling of the lens nonlinearities did not reproduce the measured level of downstream emittance growth when the simulated beam was matched and centered in the focusing system.¹⁷ Simulations with a level of beam mismatch and misalignment comparable to what was expected in the experiment did, however, succeed in reproducing emittance-growths of approximately the measured values. The experiment was therefore disassembled, carefully aligned and matched, and the gun structure was redesigned so that controlled misalignments could be introduced by adjusting the gun mount, in order to compare with predictions from the simulation code. Experimental measurements of downstream emittance and beam profile were then found to agree well with simulation.¹⁸

A similar process of the simultaneous refinement of both simulation and experiment was employed in the five beamlet experiment,¹⁹ and eventually resulted in very detailed agreement between simulation and the experiment,¹⁵ as well as verification of the theory^{20,21} of conversion of the field energy in a nonuniform beam to rms emittance. Several iterations involved both the modification of the simulation code, such as in the development of new rendering methods, as well as new measurements of the beam in the vicinity of the source and new data on the magnet characteristics.

The five beamlet experiment investigated the inherently nonlinear homogenization of five beamlets into a single beam with nearly uniform cross section. Despite the nonlinear nature of the process, the simulations were able to reproduce, in striking detail, complex fluorescent screen images of the formation of downstream images of the initial beam cross section. The degree of agreement obtained between the simulation experiment and theory has lent very strong

credibility to the ability of these simulation techniques to predict the nonlinear dynamics of space charge limited beams provided the model is an accurate representation of the physical system.

What has emerged from our experience in comparing simulation to experiment is that the best agreement will be obtained if both techniques can be continuously refined. The simulations must be improved to contain an adequately detailed model of the experimental apparatus and the experimental measurements must be flexible enough to reexamine those parameters where there is disagreement with the simulations. This capability to make new measurements has been used to resolve potential discrepancies, and to thereby establish whether the model contained in the simulations indeed is an adequate description of the experiment.

Longitudinal Dynamics

The work described so far has emphasized the transverse dynamics of a beam which is long compared to its diameter. Considerable progress has been made in understanding the transverse dynamics, and in comparing to experiment, in large measure because it can be treated independently of the longitudinal beam evolution. By contrast, even in those cases where the longitudinal physics is expected to be one-dimensional and largely independent of the transverse dynamics, the degree to which simulation and experiment have been systematically compared is less advanced than for physics involving the transverse direction. This is particularly true for beams with small energy spread, so that, in the beam frame, particles move slowly compared to the plasma wave velocity. In this regime both simulation and experiment have proved to be more difficult than in the study of the transverse dynamics, especially for high currents transported for long distances, in which case the plasma waves have enough time to traverse distances comparable to the length of the beam.

Simulations to examine the fundamental longitudinal dynamics and stability of transported beams²²⁻²⁵ have been performed, and a wealth of nonlinear phenomena has been found to be significant. However, even fundamental questions still remain unanswered, as will be discussed below, and these are the subject of ongoing investigation.

Close agreement between experiment and simulations has been reported in the MBE-4 multi-beam transport and acceleration experiment at LBL.²⁶ Here too, however, many questions important to explaining the experimental observations have not been answered. This experiment does have a small energy spread, but the beam lifetime is too short to permit the examination of

many nonlinear issues relevant to plasma wave propagation. The Maryland transport experiment, on the other hand, has the potential to perform low cost experiments which can examine important questions relevant to beam bunching and stability, as well as plasma wave propagation in longitudinally cold beam systems. And because of the azimuthally symmetric geometry, this economical experiment is well suited to comparisons with simulations in r, z geometry which exploit the azimuthal symmetry, and are somewhat more economical than the fully three-dimensional simulations required to describe a transport system with alternating gradient focusing. These issues will be discussed in more detail below.

As mentioned above, theoretical and experimental investigation of the longitudinal dynamics of a space-charge-dominated bunch is somewhat less advanced than investigation of the transverse dynamics. This is particularly true in the regime where the longitudinal velocity spread is small compared with the plasma wave velocity, $v_p = (q^2 g \lambda / m)^{1/2}$, where q and m are the particle charge and mass, λ is the line density. In this expression, g is a geometry factor, of order unity, which depends on the logarithm of the ratio of the beam radius to chamber radius, but whose exact form depends on the assumed nature of the wave eigenfunctions.²⁷ In this "cold beam" case, the propagation of space charge waves on the beam column can be a significant feature of the beam dynamics because the beam particles are too slow to Landau damp these waves.

Of particular interest here, is a beam long compared with its diameter. Though both the experimental apparatus and the multi-dimensional computer codes can be used to study beams with length comparable to diameter, the long beam has been chosen for first study because it is more amenable to descriptions which treat the longitudinal and transverse dynamics separately. In this case, the longitudinal dynamics can often be described by a one-dimensional longitudinal model where the longitudinal electric field is proportional to the derivative of the line charge density.²⁸ As will be discussed below, the nature of the beam dynamics depends, in a manner analogous to what occurs in the transverse direction, on the extent to which the space charge force dominates the pressure, or emittance, force. In the "cold beam" regime, the beam dynamics are dominated by the self-consistent electric fields, the physics can be inherently nonlinear and, for perturbations comparable to the transverse dimensions of the system, wave

dispersion can also be important.²³ In addition, particle simulations in this regime are subject to numerical constraints which can render even simple one-dimensional simulations difficult and sometimes expensive in computer time.²⁹

A fundamental, and difficult to rectify, factor which limits the systematic experimental investigation of longitudinal physics in the space-charge-dominated regime where plasma wave propagation can be significant, is the difficulty of scaling to a small inexpensive system. Because of constraints imposed by the requirement for transverse stability, the maximum beam density which can be propagated is limited. As a consequence, the velocity of longitudinal waves, which depends on the beam density per unit length, is at most a few beam diameters per magnet period. It is therefore difficult to design a short system where waves can propagate a substantial distance. If ions are to be employed in an experiment, as in a scaled down Heavy Ion Fusion experiment, a test of the longitudinal physics could cost tens of millions of dollars. The scaled-electron approach central to the Maryland transport experiment is, however, a promising avenue for progress on this front, and at substantially reduced cost. The hardware required to conduct experiments on the longitudinal dynamics is currently in place and measurements which utilize that hardware are currently underway.

Overview of Recent Experiments

A whole family of experiments are part of the program to investigate intense beam physics which is planned on the Maryland Transport Experiment, however, emphasis here will be placed on work which has already progressed to the point where direct comparisons to simulation have been possible. Planned extensions to these experiments, such as work on longitudinal stability and energy equipartition will be relegated to discussion in the context of work in progress or to be performed. First experimental results, to be discussed here, concentrate on the longitudinal dynamics of a beam bunch with a parabolic current profile. This case, as will be discussed below, was chosen because of the simplicity of its analytical description.

A mechanical drawing of the upstream section of the experiment is presented in Fig. 1. The characteristics of the apparatus which are relevant to the discussion here are the capability, by adjusting the grid voltage, to control the beam current waveform, and by energizing the induction module, to impose a longitudinal energy gradient which can cause the beam to bunch.

Also important to the experimental apparatus, but not shown, are downstream diagnostic ports which are available to measure, at a particular plane, the time-resolved beam current or energy.

In view of the success which has been achieved in obtaining detailed agreement between simulation and experiments on the transverse dynamics, it is reasonable to strive for a similar level of agreement which includes the longitudinal dynamics. In addition to the possibility of answering long-standing questions in plasma and beam physics, such a detailed agreement could be instrumental as a step in ultimately validating fully three-dimensional numerical simulations as an important tool for the design of intense-beam accelerator systems. As discussed above, for simulations to become a reliable tool for predicting the behavior of intense beam accelerator systems, especially if this requires extrapolation to parameters beyond those accessible to the Maryland experiment, it is important to stress a level of understanding beyond what is found necessary to conduct end-to-end simulations which agree with observation. The method adopted here for accomplishing that purpose is to conduct simulations employing a variety of numerical tools with different levels of comprehensiveness, so as to understand how various enhancements in the representation contribute to explaining the observed beam dynamics. As will be discussed below, this approach is particularly important because of the difficulty of measuring time-resolved transverse beam characteristics, and the consequent necessity to infer the possible transverse dynamics by understanding the underlying physics.

III. DESCRIPTION OF RESEARCH DURING CURRENT PERFORMANCE PERIOD

Dynamics of a Parabolic Bunch

Perhaps the simplest description of the longitudinal dynamics of a beam bunch, is obtained by assuming that the bunch has a parabolic profile with the appropriate velocity distribution, as described by Neuffer.³⁰ If it is further assumed that the beam self-electric field is proportional to the derivative of the line density,²⁸ then the beam dynamics will be described by an envelope equation very much like the K-V envelope equation^{4,31,32} which is often used to calculate the transverse dynamics. One of the early sets of experiments, therefore, has been to examine the dynamics of an initially parabolic bunch as it propagates down the transport system.

The form of the longitudinal distribution function which is a solution to the longitudinal envelope equation is presented for reference in Appendix I. It is also shown there that, if the emittance term is less than the space charge term in the envelope equation, it is also true that the beam thermal velocity is less than the wave velocity. That is, the condition for space charge dominance in the envelope equation is the same as the "cold beam" condition for wave propagation discussed above.

In practice it has been found, using simulation, that the bunch dynamics in the space-charge-dominated regime do not depend strongly on the detailed form of the velocity distribution. Therefore, the beam behavior is not strongly affected, if the functional form of the velocity distribution presented in Appendix I can be replaced by a, more physical, Gaussian distribution with the same rms velocity.

It is important to mention here that the envelope equation is one-dimensional and the self-electric field is assumed described by $E_z \propto \partial\lambda / \partial z$ where λ is the line density and g is a geometry factor which depends on the ratio of the beam radius to the pipe radius. Because of the parabolic shape of the line density, the self-electric fields are a linear function of z . Any applied electric fields are also assumed to vary linearly with the distance along the beam, so that all the forces seen by the beam are linear.

An early, and particularly useful, experimental diagnostic which has been performed, is the measurement of both the beam current and energy profiles a short distance after the beam

emerges from the gun. Because the beam current profile does not have time to evolve on this short a time scale, the energy variation is a direct measure of the longitudinal electric field. This can then be used in conjunction with the beam current profile data to infer the functional relation between the λ and the longitudinal electric field.

Appendix II describes simulations which have been performed to compare against this upstream beam data. It should be noted that the experimental conditions used were well below the maximum current which can be extracted from the gun structure. This is because it is possible, by varying the grid voltage, to exercise better control on the current waveform in this low-current regime. It is therefore possible to achieve the near parabolic profile used in these measurements, however because of the low current, the equilibrium beam only fills a small portion of the beam pipe.

From these preliminary measurements it is shown that, at least away from the very front and back edges of the beam, a $\partial\lambda/\partial z$ dependence of the self-electric field can be used to describe the beam. Since the beam equilibrium radius is expected to be somewhat smaller than the diameter of the beam pipe, however, this behavior cannot be extrapolated, without further verification, to beams which occupy a larger portion of the pipe cross section. Nevertheless a conclusion which will affect the interpretation of further experimental results, is that small deviations from the initial parabolic shape are present in the experiment and can have a measurable effect on the beam dynamics. Furthermore, at least in the case of the relatively low beam currents employed during production of the parabolically shaped bunches, the deviations from initial parabolic shape are more significant than the corrections to the self-electric field which arise from the fact the beam system is not one-dimensional. Another tentative conclusion reached, by virtue of the consistency between the energy waveform and beam current profile, is that varying the grid voltage is not directly affecting the beam energy. This is important in using the grid to launch waves on the beam, since the relation between the deviation in current and energy caused by a perturbing grid voltage determines the extent to which forward and backward waves are launched.

A difficult to measure, but nevertheless potentially important, beam characteristic is the evolution of the beam radius along the bunch as the bunch propagates down the transport line.

For example, the fluorescent screen used previously to measure the transverse dynamics has too slow a response to measure anything but the time-averaged beam characteristics.

The beam current, and therefore the beam equilibrium radius, can vary substantially during propagation down the transport line. Furthermore as the beam evolves, the beam energy can be different at each location along the bunch. This affects the frequency of the local mismatch oscillations, so that the relationship between beam radius and location along the bunch can change constantly as the beam propagates. Even in the simple one-dimensional description of the beam, the relationship between the line charge density and the self-electric field depends on the local beam radius through the g factor.

Lacking the ability to conduct detailed measurements of the initial transverse beam conditions, it is difficult to predict the transverse beam dynamics. This is especially true when the beam is not precisely matched to the transport system. Even if the matching lenses are adjusted to match the beam center, and in view of the lack of detailed diagnostics on the transverse dynamics even matching the beam center can be quite difficult, these matching lens settings are not likely to be correct away from the beam center. The full beam dynamics of even a simple parabolic bunch are therefore potentially quite complex and inherently multi-dimensional especially since the initial conditions are not accurately known. Since accurate prediction of the beam evolution from first principles is difficult under these conditions, the approach adopted is to use the simulation codes to study the sensitivity of the longitudinal dynamics to details of the transverse beam characteristics for a parameter range that brackets what is expected experimentally.

The details of this procedure applied to a parabolic bunch are described in Appendix III. In addition to presenting surprisingly good agreement between r,z simulations and the measurements of bunch dynamics, several preliminary, but unexpected conclusions are described there. For example, at least in the parameter range studied, the longitudinal dynamics are surprisingly insensitive to a transverse beam mismatch. Also unexpected is the degree to which the simple longitudinal envelope model accurately describes the rms bunch dynamics. A consequence however of the comparisons of the beam measurements and the r,z simulations to the one-dimensional longitudinal envelope model is that the "g-factor" which is appropriate to describing the bunch dynamics reflects an "average" radius in the bunch. This gives a

prescription for calculating the depth of the longitudinal bucket fields required to trap a space-charge dominated bunch.

Other Recent Research

Several aspects of the research described here are directly relevant to the intense beam physics which is important to the use of a heavy ion beam to ignite a thermonuclear pellet. This work is jointly supported by the Division of Advanced Physics and Technology, Office of Fusion Energy, Office of Energy Research, of the United States Department of Energy, and is conducted jointly with personnel at LLNL and LBL. Thus the code development and physics research on both programs are directly available to both programs. Duplication of effort is therefore avoided and the efficiency of both programs enhanced. Recent work in this joint effort has been primarily on WARP code development and on the use of the r,z WARP module to study the equilibrium characteristics and stability of long bunches.

One example of work relevant to both the program of basic research on space-charge-dominated transport described here and the Heavy Ion Fusion program, is the simulation studies of multi-dimensional equilibria and beam stability³³ which are relevant to a Heavy Ion Fusion driver accelerator as well as to interpretation of the current and planned experiments using Maryland apparatus. More recent results on this subject will be reported³⁴ at the 1993 Particle Accelerator Conference and published in the proceedings of that conference.

Also relevant to both programs is work³⁵ which describes the current status of the WARP codes which have been jointly supported by this program and are currently being used to examine the multi-dimensional beam dynamics appropriate to the current research effort. A report on WARP code development and the use of the code in simulating intense beam transport was also presented at the 1992 Linac Conference.³⁶ More recent progress reports will be presented at the Particle Accelerator Conference³⁷ and the International Symposium on Heavy Ion Fusion.³⁸

In addition, the acquisition of data on the Maryland Transport Experiment and the use of simulations to compare to that data, are areas of active research. Progress is currently rapid and

ongoing. Papers will be presented at both the Particle Accelerator Conference^{39,40} and the International Symposium on Heavy Ion Fusion⁴¹ on the research effort described here, as well as on work too recent to be included.

REFERENCES

1. Charles K. Birdsall and A. Bruce Langdon, Plasma Physics via Computer Simulation, (McGraw Hill, New York, 1985).
2. L. J. Laslett and L. Smith, "Stability of Intense Transported Beams", IEEE Trans. on Nucl. Sci. NS-26, 3080 (1979).
3. I. Hofmann, L. J. Laslett, L. Smith and I. Haber, "Stability of the Kapchinskij-Vladimirskij (K-V) Distribution in Long Periodic Transport Systems", Particle Accelerators 13, 145 (1983).
4. I. M. Kapchinskij and V. V. Vladimirskij, "Limitations of Proton Beam Current in a Strong Focusing Linear Accelerator with Beam Space Charge," Proc. Int. Conf. on High Energy Accelerators and Instrumentation, ed. by L. Kowarski, p. 274 (CERN, Geneva, 1959).
5. I. Haber, "Space Charge Limited Transport and Bunching of Non K-V Beams", IEEE Trans. on Nucl. Sci. NS-26, 3090 (1979).
6. J. Struckmeier, J. Klabunde and M. Reiser, "On the Stability and Emittance Growth of Different Phase-Space Distributions in a Long Magnetic Quadrupole Channel", Particle Accelerators 15, 1344 (1984).
7. I. Haber and A. W. Maschke, "Steady State Transport of High Current Beams in a Focused Channel", Phys. Rev. Lett. 42, 1479 (1979).
8. I. Hofmann, "Emittance Growth of Beams Close to the Space Charge Limit", IEEE Trans. on Nucl. Sci. NS-28, 2399 (1981).

9. I. Haber, "Simulation of Low Emittance Transport", Proc. of the INS International Symposium on Heavy Ion Accelerators and Their Applications to Inertial Fusion, Jan 23-27, 1984, Institute for Nuclear Study, Univ. of Tokyo, p. 451.
10. I. Haber, "Threshold for Emittance Growth of A-G Focused Intense Beams", Heavy Ion Inertial Fusion, AIP Conf. Proc. 152, ed. George H. Gillespie, Yu-Yun Kuo, Denis Keefe, Thomas P. Wangler, p. 236, (AIP, New York, 1986).
11. A. W. Maschke, J. Brodowski and E. Meier, "Space Charge Limits in ESQ Transport Systems", IEEE Trans. on Nucl. Sci. NS-30, 2558 (1983).
12. M. G. Tiefenback and D. Keefe, "Measurements of Stability Limits for a Space-Charge-Dominated Ion Beam in a Long A. G. Transport Channel," IEEE Trans. on Nucl. Sci., NS-32, 2483 (1985).
13. M. G. Tiefenback, "Space Charge Limits on the Transport of Ion Beams in a Long Alternating Gradient System", Ph.D. Thesis, LBL-22465, Nov. 1986.
14. D. Keefe, "Experiments and Prospects for Induction Linac Drivers", AIP Conf. Proc. 152, Heavy Ion Inertial Fusion, p. 63, (AIP, New York, 1986).
15. I. Haber, D. Kehne, M. Reiser, and H. Rudd, "Experimental, Theoretical and Numerical Investigation of the Homogenization of Density Nonuniformities in the Periodic Transport of a Space-Charge Dominated Beam," Phys. Rev. A15, 44, 5194 (Oct. 15, 1991).
16. P. Loschialpo, W. Namkung, M. Reiser, J. D. Lawson, "Effects of Space Charge and Lens Aberrations in the Focusing of an Electron Beam by a Solenoid Lens", J. Appl. Phys. 57, 10, (Jan. 1985).

17. H. Rudd, I. Haber and M. Reiser, "Simulation Studies of Emittance Growth from Image-Charge and Focusing-Field Nonlinearities in a Periodic Solenoidal Channel," 1987 Particle Accel. Conf. op. cit. p. 1120.
18. H. Rudd, I. Haber, C. R. Chang, D. Kehne, K. Low, M. Reiser, T. Shea, "Comparison of Simulation, Theory and Measurement for the Maryland Transport Experiment," Nucl. Instr. and Methods in Phys. Res. A278 (1989) p. 198.
19. M. Reiser, C. R. Chang, D. Kehne, K. Low, T. Shea, H. Rudd, and I. Haber, "Emittance Growth and Image Formation in a Nonuniform Space-Charge-Dominated Electron Beam," Phys Rev. Lett. 61, 2933 (Dec. 26, 1988).
20. T. P. Wangler, K. R. Crandall, R. S. Mills, and M. Reiser, "Relation between Field Energy and RMS Emittance in Intense Particle Beams," IEEE Trans. Nuc. Sci. NS-32, 2196 (1985).
21. O. A. Anderson, "Some Mechanisms and Time Scales for Emittance Growth," AIP Conf. Proc. 152, Heavy Ion Inertial Fusion, op. cit. p. 253.
22. I. Hofmann, "Suppression of Microwave Instabilities," Proceedings of the Symposium on Accelerator Aspects of Heavy Ion Fusion, held at GSI, Darmstadt, West Germany, March 29-April 2, 1982, GSI-82-8, p. 238.
23. J. Bisognano, I. Haber, L. Smith and A. Sternlieb, "Non-Linear and Dispersive Effects in the Propagation and Growth of Longitudinal Waves on a Coasting Beam", IEEE Trans. Nucl. Sci. NS-28, 2513 (June 1981).
24. I. Haber, "Simulation of the Longitudinal Dynamics of a Cold Bunched Beam", Proceedings of the Symposium on Accelerator Aspects of Heavy Ion Fusion Held at GSI, Darmstadt, West Germany, March 29 - April 2, 1982, GSI-82-8, p. 372.

25. J. Bisognano, I. Haber and L. Smith, "Threshold Behavior for Longitudinal Stability of Induction Linac Bunches", IEEE Trans. Nucl. Sci. NS30, 2501, (Aug 1983).
26. H. Meuth, T.J. Fessenden, D. Keefe, and A.I. Warwick, "Accelerator Research on MBE-4, an Experimental Multi-beam Induction Linac," Nucl. Instr. and Methods in Phys. Res. A278, 153, (1989).
27. Lloyd Smith, "Longitudinal Perturbation of a Cold Beam", HIFAR-Note-98, LBL, Oct. 1986.
28. A. Hofmann, "Single-Beam Collective Phenomena - Longitudinal," CERN 77-13, 139 (CERN, Geneva, 1977).
29. I. Haber, "High Current Simulation Codes," High Current, High Brightness, and High Duty Factor Ion Injectors, AIP Conf. Proc. 139, (AIP, New York, 1986) p. 107.
30. David Neuffer, "Longitudinal Motion in High Current Ion Beams - A Self-Consistent Phase Space Distribution with an Envelope Equation," IEEE Tran. Nucl. Sci. NS26, 3031, (1979).
31. P. M. Lapostolle, "Possible Emittance Increase Through Filamentation Due to Space Charge in Continuous Beams," IEEE Trans. Nucl. Sci. NS-18, 1101 (1971).
32. Frank J. Sacherer, "RMS Envelope Equations with Space Charge," IEEE Trans. Nucl. Sci. NS-18, 1105 (1971).
33. Debra A. Callahan, A. Bruce Langdon, Alex Friedman and Irving Haber, "Longitudinal Beam Dynamics for Heavy Ion Fusion Using WARPrz," presented at Computational Accelerator Physics Conference 1993 and published in Computational Accelerator Physics AIP Conf. Proc. 297, Ed. Robert Ryne, 347 (AIP, New York, 1993).

34. D. Callahan, A. Langdon, A. Friedman, I. Haber, "Longitudinal Beam Dynamics for Heavy Ion Fusion," presented at 1993 Particle Accelerator Conf., May 17-20, Washington DC, and published in Proceedings 1993 Particle Accel. Conf., 730.
35. Alex Friedman, David P. Grote, Debra A. Callahan, A. Bruce Langdon, and Irving Haber, "Overview of WARP, A Particle Code for Heavy Ion Fusion," presented at Computational Accelerator Physics Conference 1993 and to be published in Computational Accelerator Physics AIP Conf. Proc. 297, Ed. Robert Ryne, 347 (AIP, New York, 1993).
36. Alex Friedman, David P. Grote, Debra A. Callahan, A. Bruce Langdon, and Irving Haber, "3d and r,z Particle Simulations of Heavy ion Fusion Beams," 1992 Linear Accelerator Conf. Proc., AECL-10728, Ed C. R. Hoffmann, 784 (AECL, Chalk River, Ontario, Canada, 1992).
37. D. Grote, A. Friedman, I. Haber, "Three Dimensional PIC Simulations of Heavy Ion Fusion Beams: Recent Improvements To and Applications of Warp," to be presented at 1993 Particle Accelerator Conf., May 17-20, Washington DC, and published in Proc. of the 1993 Particle Accel. Conf., 727, IEEE Catalog No. 93CH327779-7 (IEEE, NJ 1993).
38. Alex Friedman, Debra A. Callahan, David P. Grote A. Bruce Langdon, Steven M. Lund, and Irving Haber, "What We've Learned from 3-D and R,Z Simulations Using the WARP Code," to be presented at 1993 International Symposium on Heavy Ion Fusion, Frascati, Italy, May 25-28, 1993, and published in Il Nuovo Cimento, **106 A**, N. 11, 1649 (Nov. 1993).
39. I. Haber, D. A. Callahan, A. B. Langdon, M. Reiser, D. X. Wang, and J. G. Wang, "Computer Simulation of the Maryland Transport Experiment," to be presented at 1993 Particle Accelerator Conf., May 17-20, Washington DC, and published in Proc. of the 1993 Particle Accel. Conf., 3660, IEEE Catalog No. 93CH327779-7 (IEEE, NJ 1993)..
40. D. X. Wang, J. G. Wang, D. Kehne, M. Reiser, I. Haber, "Experimental Studies of Longitudinal Beam Dynamics of Space-Charge Dominated Beams," to be presented at 1993

Particle Accelerator Conf., May 17-20, Washington DC, and published Proc. of the 1993 Particle Accel. Conf., 3627, IEEE Catalog No. 93CH327779-7 (IEEE, NJ 1993).

41. D. X. Wang, J. G. Wang, M. Reiser, I. Haber, "Longitudinal Compression and Expansion of Electron Bunches with Parabolic and Rectangular Density Profiles," to be presented at 1993 International Symposium on Heavy Ion Fusion, Frascati, Italy, May 25-28, 1993, and published in *Il Nuovo Cimento*, **106 A**, N. 11, 1739 (Nov. 1993).

APPENDIX I

Longitudinal Envelope Equation

A simple and widely utilized tool for describing the transverse dynamics is the K-V envelope equation.²⁹⁻³¹ A similar equation has been obtained by Neuuffer³³ and is described here for reference because of its utility in describing the longitudinal dynamics of a parabolic bunch, and it can also be useful in estimating the dynamics of a long bunch with a parabolic end cap. As will be described in Appendix III, this equation can be useful even for space-charge-dominated beams.

The longitudinal distribution function described by the envelope equation is assumed to be:

$$f(z, z') = \frac{3N}{2\pi\epsilon_l} \left[1 - \frac{z^2}{z_m^2} - \frac{z_m^2}{\epsilon_l^2} \left(z' - \frac{z'_m}{z_m} z \right)^2 \right]^{1/2}, \quad (1)$$

where N is the number of particles in the bunch, and can be expressed in terms of the peak line density by $N = 4/3 \lambda_0 z_m$, z_m is the bunch half-length, $z'_m = v_{zm}/\beta c$, where v_{zm} is the maximum particle velocity, $\epsilon_l = z_m z'_m$ is the longitudinal emittance and $z' = v_z/\beta c$. Note that this is the distribution in the frame moving with the beam so that z is measured relative to the beam center and v_z and z' are measured relative to the velocity of the beam.

If the beam is long compared with its diameter, the longitudinal electric field can be approximated by

$$E_z \approx -qeg \frac{\partial \lambda}{\partial z}, \quad (2)$$

where the factor g is a geometric factor traditionally calculated as $g = 1 + 2 \ln(b/a)$, b and a are the pipe and beam radii, and λ is the line density which can be expressed in terms of the current, I , by $\lambda = I/qe\beta c$.

The distribution function described in Eq. (1) is characterized by a parabolic line density distribution whose derivative, and therefore self-electric field as described in Eq. (2), is linear with z . In the presence of a linear external force the evolution of such a distribution is described by the (non-relativistic) envelope equation for z_m

$$\frac{d^2 z_m}{ds^2} = -K_z(s)z_m + \frac{\epsilon_i^2}{z_m^3} + \frac{3}{2} \frac{AN}{z_m^2} \quad , (3)$$

where $A = \frac{q^2 e^2}{m \beta^2 c^2} \frac{g}{4\pi\epsilon_0}$, $K_z(s) = \frac{qe}{m \beta^2 c^2} \frac{dE_{ext}(z)}{dz}$, and E_{ext} is an externally applied z-electric field which is assumed to vary linearly with z . Note that the independent variable s is the distance the beam has propagated along the transport line. This is therefore a description of the beam dynamics at a particular time for all spatial coordinates.

As discussed above, a long beam can support space charge waves whose velocity is given, in the long wavelength limit, by

$$v_p^2 = \beta^2 c^2 \lambda .$$

The condition for the coefficient of the space charge term in Eq. (2) to dominate the emittance term can then be written as:

$$2v_p^2 \gg \beta^2 c^2 z_m^2 .$$

The condition that the space charge term dominate the emittance in the envelope is therefore algebraically equivalent to the condition that the wave velocity exceeds the particle thermal speeds. This is the parameter regime in which undamped wave propagation can be important. It is also the parameter range of increasing importance to a range of high luminosity accelerators and the physics regime being explored, on a scaled basis, by the Maryland Transport Experiment.

APPENDIX II

Initial Shaping of a Parabolic Bunch

Even though the envelope description described above is strictly valid only in the one-dimensional beam frame description of the parabolic bunch where the electric field can be described as proportional to $\partial\lambda/\partial z$, nevertheless, because of the simplicity of the description, investigation of such a parabolic bunch would appear to be a good area for initial experimental investigation. As will be detailed in Appendix III, the actual dynamics of such a bunch, at least in the rms sense, appears in actuality to be better described by this model than might be expected. However, the purpose of this section is to explore the extent to which varying the grid voltage appropriately actually results in the desired bunch shape. This will provide guidance in interpreting the later experimental data by facilitating differentiation between effects which result from slight imperfections in the initial conditions and those aspects of the beam dynamics which are appropriate to the general multi-dimensional behavior of a parabolic bunch.

Figure 2 is a plot of the beam current vs. time taken a short distance downstream from the gun output. It is apparent from both consideration of the envelope predictions and also from simulation that the beam does not have time to evolve significantly over so short a distance and that these measurement therefore accurately reflect the beam initial conditions. Also plotted in Fig. 2 is a parabolic fit to the initial data. It is apparent from examining the raw data that one of the questions raised here and one that recurs in the interpretation of later data is the differentiation between systematic behavior of the beam and effects caused by ripples in the initial waveforms. It is not unreasonable to argue that the observed ripples as well as some shot-to-shot scatter in the data limit the quantitative accuracy of any comparisons to theory and simulation to a few percent.

Figure 3 is a plot of the energy variation along the beam which is also measured close to the gun. Since the beam density has not had time to evolve this is a direct measurement of the longitudinal electric field experienced by the beam. In addition to some scatter in the points there is a slight droop in the beam ends. Also noteworthy is the lack of any evidence of a multi-dimensional correction to the acceleration. Simulations using r,z WARP show, for the approximate parameters in this experiment, an increase in the acceleration at the two ends of the beam. This is presumably due to the smaller equilibrium beam radius at the beam ends and a

consequent increase in the "g-factor". This "essing" of the beam phase space may not occur for the experiment if the beam radius does not decrease toward the beam ends. However, as will be discussed in the next section, the mismatch that this implies does not seem to substantially alter the beam dynamics.

Another possible reason for a deviation of the beam energy profile from linearity would be some influence of the grid voltage on the beam energy, and some evidence that this can occur has been seen in experiments to launch waves by using the grid to produce a small perturbation in the beam density. Under some experimental conditions, mostly thought to be related to deviation from space-charge-limited emission at the cathode, modulating the grid produced both a density and current modulation.

In order to examine the magnitude of a deviation from linearity which would be produced by an initial deviation from the ideal initial parabolic shape, a series of simulations was run using the SHIFT-Z one-dimensional longitudinal code which calculates the longitudinal electric field by assuming a $\partial\lambda/\partial z$ dependence on the line density. The appropriate density to give any energy variation could be obtained in such a model simply by integrating the energy profile. However, what was done in the code was to simply add a displacement proportional to the fourth power of the distance from beam center to each of the particles in the initial load.

Figure 4 is a phase space particle scatter plot and a plot of the beam line density showing a nominal parabolic bunch. Two potential sources of small deviation from linearity in the phase space can arise because the particles positions are plotted vs. energy and not velocity and because the diagnostics shown are effected at a fixed plane to mimic what is measured experimentally. The diagnoses at a fixed plane rather than at all planes for a fixed time can also affect the shape of the beam density or current plots, however, these effects are small here because of the proximity of the diagnostic to the injection plane.

Figure 5 is a phase space and beam line density plot when a displacement which varies as the fourth power of the distance from the beam center is added to perturb the initially parabolic shape. The magnitude of the perturbation was chosen to give a small droop at the two ends of the phase space plot that approximates what is seen experimentally.

Figure 6 is a copy of the plot of current vs. time taken experimentally. However, the density plot from Fig. 5 has been rescaled and is overlaid onto the experimental data. While

the scatter on the experimental data is sufficient to prevent a clear determination of what the shape of the current should be, it is clear that the perturbed density plot is consistent with the general features of the data and it is easy to argue that this curve is a better representation of the current shape than the original experimental data.

The purpose of this comparison between simulation and experiment is not to determine what initial beam distribution can duplicate the measured energy vs. time curve. Since a one-dimensional model was used, an initial density could have been established by integrating the energy curve to fit that curve with arbitrary accuracy. It is likely that deviations from the one-dimensional model can significantly affect the validity of that procedure. If a full measurement of the beam shape, including its transverse characteristics were available, the r,z code could then be used to do a first principles simulation. However, the transverse data is difficult to measure with the existing apparatus. What is intended instead is to provide some measure for which features of the experiment are likely to be explained by the more detailed simulations described below.

APPENDIX III

Experiment and Simulation of an Expanding Parabolic Bunch

A simple but important early experiment which has been performed on the Maryland Transport Experiment is to examine the free longitudinal expansion of a bunch whose initial current profile is parabolic in the axial direction. The measured behavior can then be compared against the predictions of r,z simulations without any uncertainty associated with characterization of the accelerating module. As will be discussed below, the physics of even this simple case is quite rich. It is, therefore, appropriate to understand this simple case before seeking simulation agreement with a more complex experimental undertaking, one which may involve a number of uncertain parameters.

Figure 7 is a plot of current vs. time measured at the first current monitor which is positioned 0.624 m downstream from the gun output. Also drawn on the same plot is a "best fit" parabola obtained by doing a least squares fit to the bulk of the data, ignoring the small tail of the experimental curve. Figure 8 is a plot of beam velocity vs. time from the energy analyzer data taken 0.473 m from the gun. Figure 9 is a current plot, including the parabolic fit, 5.25 m downstream, and Fig. 10 is a plot of the energy analyzer data 5.42 m downstream. Also available, but not shown here, are data from current monitors at 2.39 m, 3.48 m, and 4.30 m, and an energy analyzer at 3.746 m.

No direct data is available on the transverse beam data. However, the beam is approximately matched to the transport line by adjusting the matching lens until some current loss is observed, presumably associated with the mismatched beam hitting the beam pipe, and then setting the matching lens values in the middle of the range for which no loss is observed.

If the beam is assumed matched to the transport line, previously obtained experimental data on the magnet characteristics,^{15,16} as well as the extensive data on transverse beam dynamics,¹⁷⁻¹⁹ allow confident prediction of the matched beam radius, if the average magnetic field is known. The average magnetic field can, in turn, be accurately related to the coil currents. Starting from the measured initial beam current waveform, it is therefore possible to run an r,z WARP simulation using a matched beam with the calculated equilibrium radius. For the 26.3 mA peak beam current, and the 1.91 A coil current used in this experiment, the calculated

matched beam radius at the peak current is 6 mm. The beam pipe radius is 19 mm, so that the beam does not fill a large percentage of the pipe.

Lacking time-resolved data about the transverse beam characteristics, some assumption must be made however regarding the axial variation of transverse beam conditions away from the beam center. The beam in the simulation is assigned a local emittance proportional to current and is assumed to have a constant tune depression along the beam. The beam is then matched along its length by adjusting the local radius so that the charge density is a constant. The data from this simulation can then be compared to the experiment to test the assumption that, as the beam undergoes transverse mismatch oscillations, the longitudinal beam dynamics are affected only by the local beam radius averaged over these oscillation, and the beam is relatively insensitive to any transverse mismatch. This ansatz can then be examined by comparing the dynamics of a simulated beam with a mismatch introduced to the matched case.

It is worth noting that the beam current magnitude and waveform are based on experimentally measured quantities. The matched beam radius, as well as the magnitude applied focusing, is also based on the actual applied magnetic field. So there are no free parameters that can be adjusted in performing the simulation. Because the simulation is performed with an applied "electrostatic equivalent" constant focusing force to transversely contain the beam, there is some difference between the mismatch oscillation frequencies that particles with deviations from the nominal beam energy experience. However, as will be seen below this does not significantly affect the longitudinal dynamics.

Figure 11 is a plot, from the simulation, of the evolution of the rms bunch length as the beam propagates down the transport line. Also plotted on the same axes are the experimental beam widths at each of the five current monitors, measured by the least squares fitted parabola as discussed above. Note that the bunch length used to initialize the beam is actually what is measured at the first current monitor 0.624 m downstream, but that this only represents a small error, can easily be seen from the plot. Considering the uncertainties in measuring the beam profile and the slightly different methods for determining bunch length in the simulation compared to the experiment, the agreement is reasonably good. For example, by slightly decreasing the beam current which was used in the simulation, it would be possible to substantially improve the agreement to the measured downstream bunch length.

Figure 12 is a particle scatter plot, from the simulation, of z - V_z phase space after the beam has propagated one meter. It should be noted that the z thermal velocity in the simulation is somewhat larger than that in the experiment. However, the cold beam the inequality discussed in Appendix I is still quite well satisfied, and both the bunch dynamics and the wave characteristics are not substantially influenced by the added thermal pressure. For example the emittance or pressure contribution to the beam expansion after six meters of propagation is somewhat less than one percent. The relatively large axial thermal spread in velocities is necessary in order to thermally damp a longitudinal numerical instability.²⁹ It is possible to run axially colder beams but these simulations would be somewhat more expensive. What can be noted in Fig. 12 is that the beam average velocity is slightly "es" shaped. That is, the outer edges of the beam are initially accelerated more than the center. This is qualitatively different from what is seen experimentally, as discussed in Appendix II, and is an indication that the detailed transverse beam variation does not strongly affect the longitudinal dynamics.

Figure 13 is a phase z - V_z phase space plot 5.5 m downstream of the gun. The essing of the beam phase space is somewhat decreased. The phase space slope, which is a measure of the rate of beam expansion is approximately $\Delta\beta/\beta = 3.7 \times 10^{-4}$ per ns compared to the measured value of 3.35×10^{-4} as shown in Fig. 10. Figure 14 is a plot of the current variation along the beam, after the same 5.5 m propagation distance. Note that there is a small flaring out of the current at the front and back edges of the beam, presumably caused by the initial es shape in the expansion which implies that the ends of the beam will expand at a faster than average rate. This effect is difficult to resolve in the experiment because of the ripple in the measured current waveform. Included for later reference are Figs. 15 and 16, which are x - z particle scatter plots of the beam density initially and after 5.5 m respectively. The main difference observed between the two plots is, besides the increased axial beam size, that the beam edge has become diffuse. This is normally expected for an initially semi-Gaussian beam as a sheath is formed at the beam edge. There is also usually a certain amount of numerical scatter which also can spread out the edge of the beam.

The agreement in the dynamics of the bunch expansion between simulation and experiment despite some evidence that the variation initial transverse profile differs substantially

between the two cases suggests that the bunch dynamics are largely insensitive to beam mismatch. This sensitivity is much easier to examine in a controlled manner using the simulation code than the experiment. A simulation was therefore run where the beam radius is initially mismatched away from the beam center. Figure 17 is an x-z scatter plot of the beam initial conditions, showing the substantial increase to the off-center beam radius. Figure 18 is an x-z plot after 1.0 m of propagation. Note that the shape of the beam has changed slightly and some halo has been generated. Because of the differential in beam velocity between the front and rear ends of the beam, the betatron frequency is different. The mismatch oscillations are therefore at a different phase so that the front and back ends of the beam differ. Figure 19, which is an x-z plot after 5.5 m, shows the continuation of this process. Figure 20 is a plot of the rms bunch length as the mismatched beam propagates down the transport line. Despite the very substantial differences in the transverse dynamics between the matched and mismatched runs, the differences in the expansion of the rms bunch radius are quite small. Comparison of the curves in Figs. 20 and 11 shows that the two are quite similar. If the two curves are overlayed only small differences are observed. The major difference is that the rms bunch length after 6 m of expansion is about 1% greater in the mismatched run. The longitudinal dynamics, as measured by the rms bunch expansion, is therefore seen to be relatively unaffected by the complexities of the transverse dynamics which result from the initial mismatch.

In the experimental conditions which were examined, and also in the simulation shown, the beam with a radius of approximately 6 mm fills only a small portion of the 19 mm beam pipe. To test whether the observed insensitivity to the longitudinal dynamics still is observed even when more of the pipe is filled a simulation was run using a beam with the same peak current, but with a decreased focusing force so that the equilibrium radius was doubled. The curve of rms bunch length vs. distance down the pipe is shown in Fig. 21. A simulation was also run with these conditions, but the beam radius increased by about half of the previous mismatch run. The smaller mismatch in this case was dictated by a desire to avoid beam loss from the outer particles hitting the beam pipe. The resulting variation in the rms bunch radius as the beam propagates is shown in Fig. 22. As in the previous case discussed, evolution of the rms beam bunch length is insensitive to the transverse match.

The degree to which the longitudinal bunch expansion is insensitive to the details of the transverse match suggests that it is appropriate to compare the beam expansion to the one-dimensional envelope equation described in Appendix I. Since it is difficult to calculate what the appropriate g -factor is for a nonuniform bunch whose radius varies with time as the beam expands, the procedure which was employed was to consider g to be a free parameter, and to find the value of g which would result in the beam expansion which matches the r,z simulation at the end points of the 6 m runs which have been performed. The curves of rms bunch length from the simulation and the bunch length calculated using the g value which matches the end points were then plotted on the same set of axes as shown in Figs. 23 and 24 for the 6 mm and 12 mm maximum radius bunches respectively. As can be seen from the curves, this procedure predicts the intermediate points with surprising accuracy. If the value of g is written in the form $g = C + 2 \ln(b/a)$, then the value of C was found to be 0.790 and 0.775 for the large and small bunches respectively. This weak dependence means that the rms bunch dynamics for an initially parabolic bunch may be accurately predictable using a simple envelope model, although whether this procedure remains true over a larger range of parameters or whether it breaks down if the beam is given an initial inward (bunching) velocity remains to be tested.

While the rms bunch length of an expanding length has been found to behave predictably, other features of the beam dynamics are still potentially quite complex. Figure 25 is a plot of the experimentally measured beam current variation, as well as a parabolic fit, for the data taken at a point 4.3 m downstream from the injector. An asymmetry in the beam shape can be observed which seems to indicate a local mismatch within the bunch. Such a localized deviation in the beam shape may in fact be due to some coupling with the transverse dynamics.

Another complication in predicting the bunch dynamics can be seen in Fig. 26, which is a plot of beam phase space and current variation taken from the SHIFT-Z one-dimensional code. This code has the capability to inject and diagnose the beam at a fixed spatial location rather than, as is true of the r,z WARP, following the entire beam as a function of time. The back end of the beam, which is traveling slower than the front end has more time to expand so that an asymmetry around the peak current is introduced. While the asymmetry is small in this case, when the effect of the accelerating module is added to the simulation the differences in representation can become more significant.

The code enhancements necessary to treat this level of detail as well as plans for further comparisons of the simulation code results to experimental measurements are discussed above in the section on proposed future work.

FIGURE CAPTIONS

- Fig. 1. Mechanical drawing of the electron beam injector system, showing the gun, the induction accelerator module and the first three magnets. Not shown are the remainder of the periodic array of magnets, as well as the numerous diagnostic ports which can be used to measure beam current and energy.
- Fig. 2. Current distribution as a function of time measured a short distance from the electron gun and a least squares parabolic fit to the data. Downstream distance is short enough (~ 0.5 m) so that distribution accurately reflects the gun output.
- Fig. 3. Plot of variation in energy vs. time measured close to the gun. Plot is therefore a measure of the beam longitudinal self-electric field.
- Fig. 4. Phase space particle scatter plot and beam density plot from a SHIFT-Z simulation, showing the linearity of the phase space variation of a nominal parabolic bunch diagnosed near the gun output.
- Fig. 5. Phase space particle scatter plot and beam density plot under conditions similar to Fig. 4. However, the initial distribution is perturbed by giving each particle in the initial load a displacement proportional to the fourth power of the distance from the beam center. Droop in phase space is similar to what is seen in the experimental data. Note that the experimental data on energy variation does not include the ends of the beam so that only the phase space away from the ends is matched to experimental observation.
- Fig. 6. Copy of plot of current vs. time with the perturbed beam density plot from the SHIFT-Z simulation rescaled and overlayed on the experimental data in addition to the original parabolic fit. The perturbed density plot is consistent with the measured data and is closer to some features of the experimental curve than the original fit.

- Fig. 7. Plot of current (mA) vs. time (ns) measured at the first current monitor 0.624 m downstream from the gun. This is part of a set of experimental data measured with the full transport system, but the induction module not energized. Also shown is an rms "best fit" parabola used to estimate the bunch width.
- Fig. 8. Retarding energy analyzer data 0.47 m from the gun showing beam velocity vs. time. A straight line is also plotted for comparison.
- Fig. 9. Plot of current vs. time and rms parabolic fit at the current monitor 5.25 m downstream from gun. Bunch has been allowed to expand freely.
- Fig. 10. Retarding energy analyzer data 5.42 m from the gun showing beam velocity vs. time and linear fit.
- Fig. 11. Plot of rms beam duration vs. propagation distance from a RZ WARP simulation with the beam radius matched to the nominal average focusing force in the experiment. Also shown on the same plot are beam durations at the five current monitors in the experiment. The measured beam widths are obtained from the least square parabolas fitted to the data.
- Fig. 12. Particle scatter plot, from the simulation, of z - V_z phase space after the beam has propagated 1.0 m, showing an increase in beam spread velocity at the bunch ends. It should be noted that the z thermal velocity in the simulation is somewhat larger than that in the experiment, but because the emittance spreading is still negligible compared to the space charge expansion this does not affect the bunch dynamics.
- Fig. 13. Particle scatter plot of v - V_z phase space 5.5 m downstream. The phase space has evolved to a somewhat more linear shape.

- Fig. 14. Plot of the current variation along the beam after 5.5 m propagation distance. Note that a small flaring out of the current at the front and back edges of the beam.
- Fig. 15. x-z particle scatter plot of the beam initial density. Note that the beam is assumed to have a constant depression in the phase advance so that the radius decrease out from the beam center.
- Fig. 16. x-z particle scatter plots of the beam density after 5.5 m. Beam length has increased so that radius has decreased. The diffuseness of the beam edge is characteristic of the evolution of an initial semi-Gaussian distribution, but may also have a numerical component.
- Fig. 17. x-z scatter plot of the initial distribution of a beam which is purposely given a substantial mismatch to test the sensitivity of the longitudinal dynamics to such a mismatch.
- Fig. 18. x-z scatter plot of the mismatched beam after 1.0 m of propagation. Note that the shape of the beam has changed slightly and some halo has been generated. Because of the differential in beam velocity between the front and rear ends of the beam, the betatron frequency and therefore the phase of the transverse mismatch is different along the beam.
- Fig. 19. x-z scatter plot after 5.5 m showing a continuation of the consequences of the differential in betatron frequencies along the beam.
- Fig. 20. Plot of rms bunch duration vs. distance propagated for the mismatched beam. Comparison to Fig. 11 shows that the longitudinal rms bunch evolution is somewhat insensitive to a transverse mismatch.

Fig. 21. Plot of rms bunch duration vs. distance propagated for a matched bunch with the same length and current as previously but with the external focusing decreased so that the equilibrium radius has doubled.

Fig. 22. Plot of rms bunch duration vs. distance propagated for the larger radius beam but mismatched. The factor of 1.25 mismatch in this case is about half of the previous mismatch so that the beam edge does not intercept the beam pipe. As in the previous case the rms bunch expansion is largely insensitive to the transverse mismatch.

Fig. 23. Plot of the rms bunch length vs. distance propagated for the smaller radius matched simulation as shown in Fig 11. Also drawn on the same plot is the rms bunch length, which tracks the simulation very closely, calculated from the envelope equation, with the g-factor adjusted to match the simulation value at 6 m.

Fig. 24. Plot of rms bunch length vs. distance propagated for the larger radius matched beam as shown in Fig. 21. Here too the envelope equation solution closely tracks the rms bunch length found from the simulation.

Fig. 25. Plot of the experimentally measured beam current variation, as well as a parabolic fit, for the data taken at a point 4.3 m downstream from the injector. An asymmetry in the beam shape can be observed which seems to indicate a local mismatch within the bunch.

Fig. 26. Plot of beam phase space and current variation, taken from the SHIFT-Z one dimensional code, for a beam diagnosed 5.43 m from the gun. Unlike RZ WARP runs which follow the entire beam at a single time, the beam in this simulation is injected and diagnosed at a single location. An asymmetry in the current waveform is introduced because the back end of the beam, which is traveling slower than the front end has more time to expand.

Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5

Fig. 6

Fig. 7

Fig. 8

Fig. 9

Fig. 10

Fig. 11

Step 192, $T = .2031 \times 10^{-6}$ s, $Z_{beam} = 6.0000$ m

Expanding Parabolic Bunch 20.62mA

Comparison to expt 32x512.

Irv Haber

warp r1 03/17/93 18.43.04

ba08

VZ vs Z

33

Fig. 12

Step 32, $T = .0338 \times 10^{-6}$ s, $Z_{\text{beam}} = 1.0000$ m

Expanding Parabolic Bunch 20.62mA

Comparison to expt 32x512.

Inv Haber

warp r1

03/16/93

12.57.15

ba08

Fig. 13

Step 176, $T = .1861 \times 10^{-6}$ s, $Z_{beam} = 5.5000$ m

Expanding Parabolic Bunch 20.62mA

Comparison to expt 32x512.

Irv Haber

warp r1 03/16/93 12.57.15

ba08

Fig. 14

Step 176, $T = .1861 \times 10^{-6}$ s, $Z_{beam} = 5.5000$ m

Expanding Parabolic Bunch 20.62mA

Comparison to expt 32x512.

Irv Haber

warp r1 03/16/93 12.57.15

ba08

Fig. 15

Step 0, T = .00000 $\times 10^{-6}$ s, Zbeam = .00000 m

Expanding Parabolic Bunch 20.62mA
Comparison to expt 32x512.

Irv Haber

warp r1 03/16/93 16.21.17

ba08

Subset 3, nominal np = 5000

Fig. 16

Step 176, $T = .1861 \times 10^{-6}$ s, $Z_{beam} = 5.5000$ m

Expanding Parabolic Bunch 20.62mA

Comparison to expt 32x512.

Irv Haber

warp r1 03/16/93 16.21.17

ba08

Subset 3, nominal np = 5000

Fig. 17

Step 0, T = .0000x10⁻⁶ s, Zbeam = .0000 m

Expanding Parabolic Bunch 20.62mA

1.5 mismatch 32x512.

Irv Haber

warp r1 03/21/93 13.24.00

ba10

Subset 3, nominal np = 5000

Fig. 18

Step 32, T = .0338x10⁻⁶ s, Zbeam = 1.0000 m

Expanding Parabolic Bunch 20.62mA

1.5 mismatch 32x512.

Irv Haber

warp r1

03/21/93

13.24.00

ba10

Subset 3, nominal np = 5000

Fig. 19

Step 176, T = $.1861 \times 10^{-6}$ s, Zbeam = 5.5000 m

Expanding Parabolic Bunch 20.62mA

1.5 mismatch 32x512.

Irv Haber

warp r1 03/21/93 13.24.00

ba10

Fig. 20

Step 192, T = $.2031 \times 10^{-6}$ s, Zbeam = 6.0000 m

Expanding Parabolic Bunch 20.62mA

1.5 mismatch 32x512.

Irv Haber

warp r1 03/21/93 13.24.00

ba10

Fig. 21

Step 192, $T = .2031 \times 10^{-6}$ s, $Z_{\text{beam}} = 6.0000$ m

Expanding Parabolic Bunch 20.62mA

Rematched double radius.

Irv Haber

warp r1 03/23/93 03.24.47

ba11

Fig. 22

Step 192, $T = .2031 \times 10^{-6}$ s, $Z_{beam} = 6.00000$ m

Expanding Parabolic Bunch 20.62mA

Rematched double radius.

Irv Haber

warp r1 03/24/93 06.00.32

ba12

Fig. 23

Step 192, $T = .2031 \times 10^{-6}$ s, $Z_{beam} = 6.0000$ m

Expanding Parabolic Bunch 20.62mA

Comparison to expt 32x512.

Irv Haber

warp r1 03/17/93 18.43.04

ba08

Fig. 24

Step 192, $T = .2031 \times 10^{-6}$ s, $Z_{beam} = 6.0000$ m

Expanding Parabolic Bunch 20.62mA

Rematched double radius.

Irv Haber

warp r1 03/23/93 03.24.47

ba11

Fig. 25

Fig. 26