AUG 25 1997

ENGINEERING DATA TRANSMITTAL

Page 1 of 1

1. EDT 161484

2. To: (Receiving Organization) Distribution		3. From: (Originating Organization) M. J. Kupfer, LMHC, H5-49		4. Related EDT No.: NA	
5. Proj./Prog./Dept./Div.: Tank 241-TX-105		6. Design Authority/ Design Agent/Cog. Engr.: MJ Kupfer		7. Purchase Order No.: NA	
8. Originator Remarks: For Release gm8/26/97				9. Equip./Component No.: NA	
				10. System/Bldg./Facility: NA	
11. Receiver Remarks: 11A. Design Baseline Document? ☐ Yes ☒ No				12. Major Assm. Dwg. No.: NA	
				13. Permit/Permit Application No.: NA	
				14. Required Response Date:	

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Approval Designator	Reason for Transmittal	Originator Disposition	Receiver Disposition
1	HNF-SD-WM-ER-655	-	0	Preliminary Tank Characterization Report for Single-Shell Tank 241-TX-105: Best-Basis Inventory	NA	1,2	1	1

16. KEY

Approval Designator (F)	Reason for Transmittal (G)		Disposition (H) & (I)	
E, S, Q, D or N/A (see WHC-CM-3-5, Sec.12.7)	1. Approval 2. Release 3. Information	4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)	1. Approved 2. Approved w/comment 3. Disapproved w/comment	4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged

17. SIGNATURE/DISTRIBUTION
(See Approval Designator for required signatures)

(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN	(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN
		Design Authority				3	—	Central Files		A3-88	
		Design Agent				3	—	DOE Reading Room		H2-53	
1	1	Cog.Eng. M. J. Kupfer	<i>MJ Kupfer</i>	8-15-97		3	—	TCSR		R1-10	
1	1	Cog. Mgr. K. M. Hodgson	<i>K.M. Hodgson</i>	8-18-97		3	—	M. D. LeClair (4)		H0-50	
		QA				3	—	K. M. Hall		R2-12	
		Safety				3	—	T. E. Jones		H5-49	
		Env.				3	—	R. T. Winward		H5-49	

18. M. J. Kupfer Signature of EDT Originator		19. <i>MJ Kupfer</i> Authorized Representative Date for Receiving Organization		20. K. M. Hodgson Design Authority/Cognizant Manager		21. DOE APPROVAL (if required) Ctrl. No. ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments	
---	--	---	--	---	--	--	--

Preliminary Tank Characterization Report for Single-Shell Tank 241-TX-105: Best-Basis Inventory

T. E. Jones (Meier Associates), R. T. Winward (Meier Associates), and
M. J. Kupfer, Lockheed Martin Hanford Corporation, Richland, WA 99352
U.S. Department of Energy Contract DE-AC06-96RL13200

EDT/ECN: 161484 UC: 712
Org Code: 74610 Charge Code: N4G3A
B&R Code: EW3120074 Total Pages: 20 26 25
gm 8/25/97

Key Words: TCR, best-basis inventory

Abstract: An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities. As part of this effort, an evaluation of available information for single-shell tank 241-TX-105 was performed, and a best-basis inventory was established. This work follows the methodology that was established by the standard inventory task.

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: Document Control Services, P.O. Box 950, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

Mahan
Release Approval

8/25/97
Date

Approved for Public Release

**PRELIMINARY TANK
CHARACTERIZATION REPORT
FOR SINGLE-SHELL TANK
241-TX-105:
BEST-BASIS INVENTORY**

August 1997

M. J. Kupfer
Lockheed Martin Hanford Corporation
Richland, Washington

T. E. Jones
R. T. Winward
Meier Associates
Richland, Washington

Prepared for
U.S. Department of Energy
Richland, Washington

This page intentionally left blank.

**PRELIMINARY TANK CHARACTERIZATION REPORT
FOR SINGLE-SHELL TANK 241-TX-105:
BEST-BASIS INVENTORY**

This document is a preliminary Tank Characterization Report (TCR). It only contains the current best-basis inventory (Appendix D) for single-shell tank 241-TX-105. No TCRs have been previously issued for this tank, and current core sample analyses are not available. The best-basis inventory, therefore, is based on an engineering assessment of waste type, process flowsheet data, early sample data, and/or other available information.

The *Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes* (Kupfer et al. 1997) describes standard methodology used to derive the tank-by-tank best-basis inventories. This preliminary TCR will be updated using this same methodology when additional data on tank contents become available.

REFERENCE

Kupfer, M. J., A. L. Boldt, B. A. Higley, K. M. Hodgson, L. W. Shelton, B. C. Simpson, and R. A. Watrous, (LMHC), S. L. Lambert, and D. E. Place (SESC), R. M. Orme (NHC), G. L. Borsheim (Borsheim Associates), N. G. Colton (PNNL), M. D. LeClair (SAIC), R. T. Winward (Meier Associates); and W. W. Schulz (W'S Corporation), 1997, *Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes*, HNF-SD-WM-TI-740, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.

This page intentionally left blank.

APPENDIX D

**EVALUATION TO ESTABLISH BEST-BASIS
INVENTORY FOR SINGLE-SHELL
TANK 241-TX-105**

This page intentionally left blank.

APPENDIX D**EVALUATION TO ESTABLISH BEST-BASIS INVENTORY
FOR SINGLE-SHELL TANK 241-TX-105**

An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities (Hodgson and LeClair 1996). As part of this effort, an evaluation of available information for single-shell tank 241-TX-105 was performed, and a best-basis inventory was established. This work, detailed in the following sections, follows the methodology that was established by the standard inventory task.

D1.0 CHEMICAL INFORMATION SOURCES

There is no previous Tank Characterization Report (TCR) for single-shell tank 241-TX-105. Available waste (chemical) information for tank 241-TX-105 includes the following:

- The TCRs from tank 241-U-102 (Hu et al. 1997) and tank 241-U-105 (Brown and Franklin 1996) discuss waste layers within those tanks that are believed to contain Supernatant Mixing Model from 242-T Evaporator salt cake generated from 1965 until 1976 (SMMT2) waste type.
- Letter Report on tank 241-TX-116 (Horton 1977)
- The inventory estimate for this tank generated from the Hanford Defined Waste model (HDW) (Agnew et al. 1996).

D2.0 COMPARISON OF COMPONENT INVENTORY VALUES

HDW model inventories are shown in Tables D2-1 and D2-2. The nonradioactive components are listed in Table D2-1 on a kilogram (kg) basis. The radioactive component estimates are listed in Table D2-2 on a curie (Ci) basis. The HDW model document (Agnew et al. 1996) provide tank content estimates, derived from process records. No sample-based inventories are available for this tank. The chemical species are reported without charge designation per the best-basis inventory convention.

The waste volume used for the best basis calculations is 2,310 kL (609 kgal). Hanlon (1996) lists the tank as containing 2,310 kL (609 kgal) of salt cake, whereas

Agnew et al. (1996) reports the tank contents to be 2,275 kL (601 kgal) of salt cake and 30.3 kL (8 kgal) of metal waste (MW). The potential 30.3 kL (8 kgal) of sludge would only make a significant contribution to inventory values for uranium (approximately 70 percent of total) and iron (approximately 20 percent of total).

Table D2-1. Hanford Defined Waste Model-Predicted Inventory Estimates for Nonradioactive Components in Tank 241-TX-105.

Analyte	HDW ^a inventory estimate (kg)	Analyte	HDW ^a inventory estimate (kg)
Al	70,600	Ni	767
Bi	946	NO ₂	167,000
Ca	2,830	NO ₃	626,000
Cl	13,900	OH	201,000
Cr	4,650	oxalate	2.68 E-04
F	4,890	Pb	468
Fe	1,040	P as PO ₄	23,900
Hg	5.01	Si	3,800
K	4,130	S as SO ₄	47,900
Mn	323	TIC as CO ₃	54,000
Na	490,000	TOC	11400
H ₂ O (wt%)	46.5	U _{TOTAL}	19,700
density (kg/L)	1.43	Zr	306

HDW = Hanford Defined Waste

^a Agnew et al. (1996).

Table D2-2. Hanford Defined Waste Model Predicted Inventory Estimates for Radioactive Components in Tank 241-TX-105.

Analyte	HDW ^a inventory estimate (Ci)
¹³⁷ Cs	450,000
⁹⁰ Sr	177,000

^a Agnew et al. (1996), decayed to January 1, 1994.

D3.0 COMPONENT INVENTORY EVALUATION

The following evaluation was conducted to assess various estimates of tank contents.

D3.1 WASTE HISTORY TANK 241-TX-105

Tank 241-TX-105, the first in a 4-tank cascade, began receiving MW and tributyl phosphate waste (also referred to as uranium recovery waste) in the second quarter of 1952. The tank was sluiced during 1955 and 1956 and declared empty (Rodenhizer 1987). The tank began receiving Reduction and Oxidation (REDOX) waste in 1957. In 1971, the tank began receiving evaporator bottoms (EB) from the 242-T Evaporator. From 1959 until 1976, the tank received waste water. It was removed from service in 1976. In 1977 the tank was declared an assumed leaker. The tank was jet pumped interim stabilized in April 1983 with intrusion prevention completed in August 1984. The tank is classified as an assumed leaker stabilized tank. For a more complete history of the waste in this tank see Brevick (1995).

D3.2 EXPECTED TYPE OF WASTE BASED ON THIS ASSESSMENT

Expected waste types in tank 241-TX-105 based on the various source documents are as follows:

Agnew et al. (1996): SMMT2 and MW

Hanlon (1996): salt cake

Hill et al. (1995): R, EB, and MIX

MW	=	Metal waste
SMMT2	=	A mixture of concentrated supernatant coming from the 242-T Evaporator that is a blend of other waste types that upon cooling precipitated as a salt cake
R	=	High-level REDOX waste
EB	=	Evaporator bottoms
MIX	=	Mixture of several miscellaneous wastes

Agnew et al. (1996), Hanlon (1996) and Hill et al. (1995) agree that the tank 241-TX-105 contains 2,310 kL (609 kgal) of wastes and that it is essentially all salt cake. Hanlon and Hill et al. identify the waste as all salt cake. Agnew et al. lists the tank as containing 30.3 kL (8 kgal) of MW and 2,275 kL (601 kgal) of salt cake. Rodenhizer (1987) states that the tank was sluiced and declared empty of MW in the first quarter of 1957. The tank then began receiving R waste in 1957 (Anderson 1990). After a major transfer of R waste out of the tank in the last quarter of 1970, the tank began receiving EB from the 242-T Evaporator. It is likely that some solids precipitated from the R wastes over the, approximately, 14 years that it was stored in the tank. Thus, it may be more appropriate to

identify any sludge in the tank to be a REDOX-based sludge rather than MW. Until the tank is sampled this cannot be evaluated.

As shown by the HDW model data, the inclusion of 30.3 kL (8 kgal) of MW in the tank inventory estimate is insignificant except for uranium and iron. As discussed in Section D3.3, this engineering assessment fails to define a concentration value for uranium so the HDW model value is used as the best-basis value. The Fe value developed in this engineering assumption is larger than the HDW model value. Thus, given the uncertainty in the identity of any sludge that may be in tank 241-TX-105 and its mathematical insignificance to the overall tank inventory, no attempt has been made to quantify its contribution. This engineering assessment follows Hanlon's (1996) assumption that all of the material in the tank is salt cake.

D3.3 ASSUMPTIONS USED

The following evaluation provides an engineering assessment of tank 241-TX-105 contents. For this evaluation, the following assumptions and observations are made:

- Component inventories can be calculated by multiplying the concentration of an analyte from similar tanks by the current tank volume and density of the waste.
- Only salt cake from the 242-T Evaporator contribute to solids formation.
- The radiolysis of nitrate to nitrite is not factored into this evaluation.

There is limited chemical characterization data for tanks in the TX Tank Farm and few currently sampled tanks are projected to contain salt cake similar to that expected to be found in tank 241-TX-105. The salt cake in this tank came from the 242-T Evaporator. Salt cake produced in Evaporator 242-T between 1965 and 1976 is identified as T2 salt cake. The HDW model refers to this salt cake as T2 Slck on a global basis or as SMMT2 when calculated with the SMM for an individual tank. Thus, the HDW model identifies waste in tank 241-TX-105 to be SMMT2. The only chemical characterization data for SMMT2 waste appear to be from three tanks (241-U-102 [Hu et al. 1997], 241-U-105 [Brown and Franklin 1996], and 241-TX-116 [Horton 1977]). It is assumed these materials adequately represent SMMT2 salt cake.

D3.4 BASIS FOR SALT CAKE CALCULATIONS USED IN THIS ENGINEERING EVALUATION

Table D3-1 shows the engineering approaches used for tank 241-TX-105.

Table D3-1. Engineering Approaches Used for Tank 241-TX-105.

Type of waste	How calculated	Check method
Supernatant	No supernatant	None
Salt cake Volume = 2,310 kL (609 kgal) Density = 1.70 g/mL for SMMT2	Used sample-based concentrations from other tanks with SMMT2 salt cake waste. See Table D3-2.	None, no sample-based information available for this tank.
Sludge volume = assumed to be zero in this assessment	None expected	None

SMMT2 = Supernatant Mixing Model 242-T Evaporator salt cake generated from 1965 until 1976.

The general approach in this engineering assessment is to utilize all available information to formulate the best-basis estimate of the tank's contents. The sources of information may include analytical data from samples taken from the tank of interest, analytical data from other tanks believed to contain waste types similar to those believed to be in the tank of interest, and data from models utilizing historical process records. The confidence level assigned to the best-basis inventory values then depends on the level of agreement among the various information sources. This approach is best suited for cases where extensive analytical data exist for multiple sampling events from the tank of interest and from a number of other tanks containing similar waste types. However, for tank 241-TX-105, no tank-specific analytical data and very little analytical data for the SMMT2 salt cake projected to be in that tank are available.

Agnew et al. (1996) identified the salt cake in tank 241-TX-105 as SMMT2. A review of existing TCRs identified two tanks (241-U-102 [Hu et al. 1997] and 241-U-105 [Brown and Franklin 1996]) that contained analytical characterization data that could be ascribed to layers of SMMT2 salt cake. In addition, limited characterization data were available from core samples taken from tank 241-TX-116 in the mid-1970's (Horton 1977).

Analytical data from segments 4 through 6 of tank 241-U-102 cores and segment 8 of tank 241-U-105 cores were selected as being representative of SMMT2 salt cake. For almost all selected analytes, there were 14 data points from tank 241-U-102 and 4 data points from tank 241-U-105.

The mean was calculated from selected data from each U Tank Farm tank after including a weighting factor to correct for material recovery during sampling. The weighted means for each tank are listed in columns 2 and 3 of Table D3-2. The U Tank Farm means were calculated from each tank mean after including a factor to correct for the mass of material recovered during sampling and are listed in column 4 of Table D3-2. The means from tank 241-TX-116 are also listed in column 5 of Table D3-2. The tank 241-TX-116 means were calculated after removing high silica values resulting from the addition of diatomaceous earth to the tank.

Table D3-2. Composition of T2 Salt Cakes (2 Sheets).

Analyte	241-U-102 T2 salt cake wt. avg. ^{a,b} (µg/g)	241-U-105 T2 salt cake wt. avg. ^{a,c} (µg/g)	U Tank Farm T2 salt cake wt. avg. ^a (µg/g)	241-TX-116 T2 salt cake mean ^{d,e} (µg/g)	T2 salt cake prediction ^f (µg/g)	HDW T2 SlitCk ^g (µg/g)
Ag	11.6	19.7	13.1	NR	13.1	NR
Al	18,000	12,900	17,100	38,000	27,500	17,912
Bi	<70.5	<47.2	<66.2	NR	<66.2	220.81
Ca	308	253	298	NR	298	1,462
Cd	<5.94	12.8	<7.21	NR	<7.21	NR
Cl	5,100	5,790	5,230	NR	5,230	3,327.8
CO ₃	53,500	36,500	50,300	58,000	54,200	17,093
Cr	2,310	2,100	2,270	353	1,310	4,259.6
F	<125	1,110	<307	3,540	<1,920	930.79
Fe	391	2,270	737	23,900	12,300	620.58
Hg	NR	NR	NA	NR	NA	1.1338
K	1750	1,470	1,700	NR	1,700	1060.7
La	<35.2	29.7	<34.2	NR	<34.2	0.0001
Mn	123	743	237	NR	237	160.31
Na	262,600	220,500	254,800	166,700	210,800	192,764
Ni	91.5	89.5	91.1	NR	91.1	405.82
NO ₂	56,700	40,100	53,600	7,840	30,700	46,096
NO ₃	284,700	395,700	305,200	308,700	306,946	268,197
OH	NR	NR	NA	NA	NA	68,079
Pb	<119	214	<136	NR	<136	109.91
P as PO ₄	5,050	14,100	6,720	8,620	7,670	7,707.9
Si	152	232	167	NR	167	1,817.7

Table D3-2. Composition of T2 Salt Cakes (2 Sheets).

Analyte	241-U-102 T2 salt cake wt. avg. ^{a,b} (μg/g)	241-U-105 T2 salt cake wt. avg. ^{a,c} (μg/g)	U Tank Farm T2 salt cake wt. avg. ^a (μg/g)	241-TX-116 T2 salt cake mean ^{d,e} (μg/g)	T2 salt cake prediction ^f (μg/g)	HDW T2 SlitCk ^g (μg/g)
S as SO ₄	17,900	8,350	16,200	16,400	16,300	13,823
Sr	<7.04	<4.72	<6.61	NR	<6.61	0
TOC	8,810	11,000	9,210	NR	9,210	5,191
U	<353	545	<388	NR	<388	2,174.3
Zr	10.8	45.4	17.2	NR	17.2	14.707
Radionuclide ^h (μCi/g)						
²⁴¹ Am	<37.0	<0.95	<30.3	NR	<30.3	0.0285
⁶⁰ Co	<0.155	0.086	<0.142	NR	<0.142	0.027
¹³⁴ Cs	NR	NR	NA	9.64 E-04	9.64 E-04	0.0016
¹³⁷ Cs	197	145	188	34.8	111	163.24
¹⁵⁴ Eu	<0.475	0.61	<0.499	NR	<0.499	0.431
¹⁵⁵ Eu	<1.10	0.82	<1.05	NR	<1.05	0.1849
Density (g/mL)	1.66	1.73	1.70 ⁱ	NR	1.70	1.634

HDW = Hanford Defined Waste

NA = Not applicable

NR = Not reported

^a Weighted average based on the weight of each partial core segment analyzed^b Hu et al. (1997)^c Brown and Franklin (1996)^d Silica-free basis due to the addition of diatomaceous earth to this tank^e Horton (1977)^f Average of U Tank Farm and tank 241-TX-116 data^g Agnew et al. (1997)^h Decayed to January 1, 1994ⁱ A simple average is used for the density.

When both a U Tank Farm weighted mean and a tank 241-TX-116 mean were available, the predicted composition for the SMMT2 salt cake was calculated as the average of the two. However, when only one value was available it was used as the predicted SMMT2 composition. The predicted SMMT2 composition is listed in column 6 of Table D3-2. The major impact of including characterization data from tank 241-TX-116 in the predicted SMMT2 salt cake composition is to significantly increase values for the aluminum and iron.

In comparing the engineering estimates based on SMMT2 salt cake (Table D3-2, column 6) with the HDW model T2SltCk estimates (Table D3-2, column 7), there are significant differences for Fe. Less significant differences are noted for Al, Ca, carbonate, K, Mn, Na, and nitrate. The Fe values used in the developing the SMMT2 formulation exhibited large variations. There is close to an order of magnitude difference in Fe between the two U Tank Farm tanks. The Fe value for tank 241-TX-116 is an order of magnitude higher than the larger U Tank Farm tank value. The HDW model predicts an Fe value comparable with the lower U Tank Farm tank value. Since the analytical values span almost two orders of magnitude, there will be considerable uncertainty in the projected Fe value for tank 241-TX-105. The value developed through this evaluation appears unreasonably high. Since the value developed for Fe appears to be unreasonably high when tank 241-TX-116 data are included, this engineering assessment utilizes the value developed from U Tank Farm tank data.

The three analytically determined carbonate values used to develop the SMMT2 formulation are reasonably consistent. However, these values are significantly higher than the value determined by the HDW model. It is likely that the highly basic tank wastes have absorbed atmospheric carbon dioxide. Absorption of carbon dioxide would convert hydroxide to carbonate.

Table D3-3 lists the inventory estimates calculated using the predicted SMMT2 composition and the U Tank Farm composition. The HDW model estimates are also included. The bulk density value used in the engineering assessment estimates (1.70 g/mL) is approximately 20 percent higher than the value used in the HDW model estimates (1.43 g/mL). This leads to proportionally higher estimates in the engineering estimate.

Table D3-3. Tank 241-TX-105 Inventory Estimates. (2 Sheets)

Analyte	Inventory estimates using T2SltCk (kg)	Inventory estimates using U Tank Farm (kg)	HDW model values* (kg)
Al	108,000	67,100	70,600
Bi	<260	<260	946
Ca	1,170	1,170	2,830
Cd	28	28	NR
Cl	20,500	20,500	13,900

Table D3-3: Tank 241-TX-105 Inventory Estimates. (2 Sheets)

Analyte	Inventory estimates using T2SItCk (kg)	Inventory estimates using U Tank Farm (kg)	HDW model values ^a (kg)
CO ₂	213,000	198,000	54,000
Cr	5,150	8,900	4,650
F	<7,550	<1,200	4,890
Fe	48,400	2,900	1,040
K	6,670	6,670	4,130
La	<134	<134	4.9 E-04
Mn	932	932	323
Na	828,000	1,000,000	490,000
Ni	358	358	767
NO ₂	121,000	211,000	167,000
NO ₃	1,210,000	1,200,000	626,000
OH	NR	NR	201,000
Pb	536	536	468
P as PO ₄	30,100	26,400	23,900
Si	656	656	3,800
S as SO ₄	64,000	63,500	47,900
Sr	<26	<26	1.04 E-04
TOC	36,200	36,200	11,400
U	<1,520	<1,520	19,700
Zr	68	68	306
Radionuclides ^b (Ci)			
¹³⁷ Cs	437,000	737,000	450,000
⁹⁰ Sr	NR	NR	177,000

HDW = Hanford Defined Waste

NR = Not reported

^a Agnew et al. (1996)^b Radionuclides decayed to January 1, 1994.

This page intentionally left blank.

D4.0 DEFINE THE BEST-BASIS AND ESTABLISH COMPONENT INVENTORIES

Information about chemical, radiological, and/or physical properties is used to perform safety analyses, engineering evaluations, and risk assessment associated with waste management activities, as well as regulatory issues. These activities include overseeing tank farm operations and identifying, monitoring, and resolving safety issues associated with these operations and with the tank wastes. Disposal activities involve designing equipment, processing, and facilities for retrieving wastes and processing them into a form that is suitable for long-term storage. Chemical and radiological inventory information are generally derived using three approaches: (1) component inventories are estimated using results of sample analyses, (2) component inventories are estimated using the HDW model based on process knowledge and historical information, or (3) a tank-specific process estimate is made based on process flowsheets, reactor fuel data, essential material usage, and other operating data. The information derived from these different approaches is often inconsistent.

An evaluation of available chemical information for tank 241-TX-105 was performed, including the following:

- An inventory estimate generated by the HDW model (Agnew et al. 1996)
- Evaluation of SMMT2 data from two U Tank Farms tanks (241-U-102 [Hu et al. 1997] and 241-U-105 [Brown and Franklin 1996]) and older characterization data from tank 241-TX-116 (Horton 1977).

Based on this evaluation, an engineering assessment-based inventory was developed for tank 241-TX-105 (for which sample information was not available). Where available, the engineering assessment-based inventory was chosen as the best-basis inventory for the following reasons:

- No analytical data are available for tank 241-TX-105.
- No methodology is available to fully predict SMMT2 salt cake from process flowsheets or historical records.

For those analytes where no values could be calculated from the engineering assessment-based inventory the HDW model values were used.

The SMMT2 salt cake formulation was extrapolated from limited characterization data available from two U Tank Farm tanks (containing similar wastes) and from tank 241-TX-116. However, since no post-1989 analytical data were available from tank 241-TX-105 or any other tank with similar wastes within the TX Tank Farm, the reliability of these estimates (in either this engineering assessment or the HDW model inventory estimate) are suspect. Substantial uncertainty exists with these estimates.

Best-basis tank inventory values were derived for 46 key radionuclides (as defined in Section 3.1 of Kupfer et al. 1997), all decayed to a common report date of January 1, 1994. Often, waste sample analyses were only reported for total beta, total alpha, ^{90}Sr , ^{137}Cs , $^{239/240}\text{Pu}$, and total uranium, while other key radionuclides such as ^{60}Co , ^{99}Tc , ^{129}I , ^{154}Eu , ^{155}Eu , and ^{241}Am , etc., were infrequently reported. For this reason it has been necessary to derive most of the 46 key radionuclides by computer models. These models estimate radionuclide activity in batches of reactor fuel, account for the split of radionuclides to various separations plant waste streams, and track their movement with tank waste transactions. (These computer models are described in Kupfer et al. 1997, Section 6.1 and in Watrous and Wootan 1997.)

Model generated values for radionuclides in any of 177 tanks are reported in the HDW Rev. 4 model results (Agnew et al. 1997). The best-basis value for any one analyte may be either a model result or a sample or engineering assessment-based result if available. (No attempt has been made to ratio or normalize model results for all 46 radionuclides when values for measured nuclides disagree with the model.) For a discussion of typical error between model derived values and sample derived values, see Kupfer et al. 1997, Section 6.1.10.

Best-basis tables for chemicals and only four radionuclides (^{90}Sr , ^{137}Cs , Pu, and U) were being generated in 1996, using values derived from an earlier version (Rev. 3) of the HDW model. When values for all 46 radionuclides became available in Rev. 4 of the HDW model, they were merged with draft best-basis chemical inventory documents. Defined scope of work in FY 1997 did not permit Rev. 3 chemical values to be updated to Rev. 4 chemical values.

Once the best-basis inventories were determined, the hydroxide inventory was calculated by performing a charge balance with valences of other analytes. In some cases, this approach required that other analyses (e.g., sodium or nitrate) inventories be adjusted to achieve the charge balance. No adjustments were required in this best-basis estimate. This charge balance approach is consistent with that used by Agnew et al. (1997).

The best-basis values are listed in Tables D4-1 and D4-2. The inventory values reported in Tables D4-1 and D4-2 are subject to change. Refer to the Tank Characterization Database (TCD) for the most current inventory values.

Table D4-1. Best-Basis Inventory Estimates for Nonradioactive Components in Tank 241-TX-105 (Effective January 31, 1997).

Analyte	Total inventory (kg)	Basis (S, M, E, or C) ¹	Comment
Al	108,000	E	
Bi	<260	E	
Ca	1,170	E	
Cl	20,500	E	
TIC as CO ₃	213,000	E	
Cr	5,150	E	
F	<7,550	E	
Fe	2,900	E	U Tank Farm estimate used for Fe
Hg	5.01	M	
K	6,670	E	
La	<134	E	
Mn	932	E	
Na	828,000	E	
Ni	358	E	
NO ₂	121,000	E	
NO ₃	1.21 E+06	E	
OH _{TOTAL}	268,000	C	
Pb	536	E	
PO ₄	30,100	E	
Si	656	E	
SO ₄	64,000	E	
Sr	< 26	E	
TOC	36,200	E	
U _{TOTAL}	19,700	M	Engineering estimate <1,520
Zr	68	E	

¹S = Sample-based

M = Hanford Defined Waste model-based, Agnew et al. (1996)

E = Engineering assessment-based

C = Calculated by charge balance; includes oxides as "hydroxide" not including CO₃, NO₂, NO₃, PO₄, SO₄, and SiO₃.

Table D4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-TX-105 Decayed to January 1, 1994 (Effective January 31, 1997). (2 Sheets)

Analyte	Total inventory (Ci)	Basis (S, M, or E) ¹	Comment
³ H	354	M	
¹⁴ C	50.5	M	
⁵⁹ Ni	3.85	M	
⁶⁰ Co	55.3	M	
⁶³ Ni	378	M	
⁷⁹ Se	5.20	M	
⁹⁰ Sr	168,000	M	
⁹⁰ Y	168,000	M	
⁹³ Zr	25.5	M	
^{93m} Nb	18.5	M	
⁹⁹ Tc	360	M	
¹⁰⁶ Ru	0.00988	M	
^{113m} Cd	132	M	
¹²⁵ Sb	235	M	
¹²⁶ Sn	7.84	M	
¹²⁹ I	0.694	M	
¹³⁴ Cs	4.05	M	
¹³⁷ Cs	437,000	E	
^{137m} Ba	413,000	E	From ¹³⁷ Cs
¹⁵¹ Sm	18,300	M	
¹⁵² Eu	5.67	M	
¹⁵⁴ Eu	891	M	
¹⁵⁵ Eu	336	M	
²²⁶ Ra	2.51 E-04	M	
²²⁷ Ac	0.00163	M	
²²⁸ Ra	0.409	M	
²²⁹ Th	0.00948	M	
²³¹ Pa	0.00717	M	
²³² Th	0.0251	M	
²³² U	2.05	M	

Table D4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-TX-105 Decayed to January 1, 1994 (Effective January 31, 1997). (2 Sheets)

Analyte	Total inventory (Ci)	Basis (S, M, or E) ¹	Comment
²³³ U	7.84	M	
²³⁴ U	5.83	M	
²³⁵ U	0.254	M	
²³⁶ U	0.0808	M	
²³⁷ Np	1.30	M	
²³⁸ Pu	2.09	M	
²³⁸ U	6.25	M	
²³⁹ Pu	75.4	M	
²⁴⁰ Pu	12.5	M	
²⁴¹ Am	94.4	M	
²⁴¹ Pu	137	M	
²⁴² Cm	0.219	M	
²⁴² Pu	7.49 E-04	M	
²⁴³ Am	0.00318	M	
²⁴³ Cm	0.0203	M	
²⁴⁴ Cm	0.21	M	

¹S = Sample-based

M = Hanford Defined Waste model-based, Agnew et al. (1997)

E = Engineering assessment-based.

This page intentionally left blank.

D5.0 APPENDIX D REFERENCES

- Agnew, S. F., J. Boyer, R. A. Corbin, T. B. Duran, J. R. FitzPatrick, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1996, *Hanford Tank Chemical and Radionuclide Inventories: HDW Model Rev. 3*, LA-UR-96-858, Los Alamos National Laboratory, Los Alamos, New Mexico.
- Agnew, S. F., J. Boyer, R. A. Corbin, T. B. Duran, J. R. FitzPatrick, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997, *Hanford Tank Chemical and Radionuclide Inventories: HDW Model Rev. 4*, LA-UR-96-3860, Los Alamos National Laboratory, Los Alamos, New Mexico.
- Anderson, J. D., 1990, *A History of 200 Area Tank Transfers*, WHC-MR-0132, Westinghouse Hanford Company, Richland, Washington
- Brevick, C. H., 1995, *Supporting Document for the Historical Tank Content Estimate for TX Tank Farm*, WHC-SD-WM-ER-321, Westinghouse Hanford Company, Richland, Washington
- Brown, T. M., and J. D. Franklin, 1996, *Tank Characterization Report for Single-Shell Tank 241-U-105*, WHC-SD-WM-ER-617, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Hanlon, B. M., 1996, *Waste Tank Summary Report for Month Ending June 30, 1996*, WHC-EP-0182-99, Westinghouse Hanford Company, Richland, Washington.
- Hill, J. G., G. S. Anderson, and B. C. Simpson, 1995, *The Sort on Radioactive Waste Type Model: A Method to Sort Single-Shell Tanks into Characteristic Groups*, PNL-9814, Rev. 2, Pacific Northwest National Laboratory, Richland, Washington.
- Hodgson, K. M., and M. D. LeClair, 1996, *Work Plan for Defining a Standard Inventory Estimate for Wastes Stored in Hanford Site Underground Tanks*, WHC-SD-WM-WP-311, Rev. 1, Lockheed Martin Hanford Corporation, Richland, Washington.
- Horton, J. E., 1977, *Physical and Chemical Characterization of 116-TX*, Letter Report to G. K. Allen, Atlantic Richfield Hanford Company, Richland, Washington.
- Hu, T. A., L. C. Amato, R. T. Winward, and R. D. Comar, 1997, *Tank Characterization Report for Single-Shell Tank 241-U-102*, HNF-SD-WM-ER-618, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.

Kupfer, M. J., A. L. Boldt, B. A. Higley, K. M. Hodgson, L. W. Shelton, B. C. Simpson, and R. A. Watrous (LMHC), S. L. Lambert, and D. E. Place (SESC), R. M. Orme (NHC), G. L. Borsheim (Borsheim Associates), N. G. Colton (PNNL), M. D. LeClair (SAIC), R. T. Winward (Meier Associates), and W. W. Schulz (W²S Corporation), 1997, *Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes*, HNF-SD-WM-TI-740, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.

Rodenhizer, D. G., 1987, *Hanford Waste Tank Sluicing History*, WHC-SD-WM-TI-302, Westinghouse Hanford Company, Richland, Washington.

Watrous, R. A., and D. W. Wootan, 1997, *Activity of Fuel Batches Processed Through Hanford Separations Plants, 1944 Through 1989*, HNF-SD-WM-TI-794, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.