DOE/BC/14938--2

TITLE: ADVANCED RESERVOIR CHARACTERIZATION IN THE ANTELOPE SHALE TO ESTABLISH THE VIABILITY OF CO₂ ENHANCED OIL RECOVERY IN CALIFORNIA'S MONTEREY FORMATION SILICEOUS SHALES

Cooperative Agreement No.: DE-FC22-95BC14938

Contractor Name and Address: Chevron USA Inc., Production Company (CPDN), 5001 California Avenue, Bakersfield, California 93309

Date of Report: June 30, 1996

Award Date: February 7, 1996

Anticipated Completion Date: June 11, 1998

Government Award for Current Fiscal Year: \$ 2, 334,048

Principal Investigator: Stephen C. Smith, CPDN

Project Manager: Edith Allison, Bartlesville Project Office

Reporting Period: April 1, 1996 - June 30, 1996

RECEIVED

SEP 10 1996

OSTI

RECEIVED
USDOE/PETC
26 JUL 26 AM 9:27
COMMUNITY & ASSISTANCE DIV.

Objective

MASTER

The primary objective of this research is to conduct advanced reservoir characterization and modeling studies in the Antelope Shale reservoir. Characterization studies will be used to determine the technical feasibility of implementing a CO₂ enhanced oil recovery project in the Buena Vista Hills field. The Buena Vista Hills pilot CO₂ project will demonstrate the economic viability and widespread applicability of CO₂ flooding in fractured siliceous shales reservoirs of the San Joaquin Valley. The research consists of four primary work processes: Reservoir Matrix and Fluid Characterization; Fracture Characterization; Reservoir Modeling and Simulation; and, CO₂ Pilot Flood and Evaluation. Work done in these areas can be subdivided into two phases or budget periods. The first phase of the project will focus on the application of a variety of advanced reservoir characterization techniques to determine the production characteristics of the Antelope Shale reservoir. Reservoir models based on the results of the characterization work will be used to evaluate how the reservoir will respond to secondary recovery and EOR processes. The second phase of the project will include the implementation and evaluation of an advanced EOR pilot in the West Dome of the Buena Vista Hills field.

Summary of Technical Progress

The Buena Vista Hills project realized it's first major milestone in the second quarter of 1996 with the pending drilling of proposed project injection well. Regional fracture characterization work was also initiated in the second quarter. This report will summarize the status of those efforts.

Proposed Project Injection Well

The 653Z-26B well, located in Section 26, T31S-R23E, Kern County, California is scheduled to spud on July 1, 1996 after a fairly lengthy environmental review and permitting process. This well is being drilled in a position to serve as an injection well for any future enhanced oil recovery pilot project. The well is planned to be drilled to a total depth of 5000 feet and penetrate the entire productive Antelope Shale reservoir. It is anticipated that it will take 30 days to drill and complete this well. The well will be cased and will remain inactive pending the results of the reservoir characterization and modeling studies.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

Extensive data collection will take place in this project well. The well will be deviated to increase the chance of intersecting natural fractures. Approximately 900-1000 feet of core will be cut and recovered in the Antelope Shale utilizing "low-invasion" and "soft" core handling techniques. After coring operations are completed, the wellbore will be logged with "state-of-the-art" open hole logging tools to collect data that will assist in the reservoir characterization process. Core Laboratories, Terra Tek, Dowell-Schlumberger, Chevron Petroleum Technology Company, and Horizon Mud Logging will all assist with the wellsite data collection process.

Regional Fracture Characterization

Regional fracture characterization studies are underway. Advanced Resources International (ARI) and Stanford University are assisting with these project tasks. ARI has gathered regional gravity, magnetic, and remote sensing data and begun reviewing that data. ARI will assist by integrating micro-, meso-, and macro-scale fracture data to better understand field-scale reservoir fracture data. This analysis will then also be analyzed within a basin-scale tectonic framework. The results of this work will provide a fracture characterization analog for other fields in the San Joaquin Valley with similar structural/strain and depositional histories.

Stanford has been working on core and outcrop studies to better characterize fracture zone geometries and distribution. Dholakia¹ summarized the role that faulting appears to play in hydrocarbon migration. Dholakia also noted and documented a relationship or association between fractures related to shearing processes and hydrocarbon transport. Additional work will be done with the core from 653-26B to further characterize fractures and their relationship to hydrocarbon production.

Technology Transfer

Chevron was very active in the 1996 National American Association of Petroleum Geologists (AAPG) Meeting in San Diego. Steve Smith, Principle Investigator, co-chaired oral and poster sessions on the topic of "Low Permeability, Fractured Reservoirs". Several of the papers in these sessions addressed issues of reservoir and fracture characterization in siliceous shale reservoirs such as the Antelope Shale. Dholakia, et al² presented their work on "Hydrocarbon Transport and Shearing Processes in the Antelope Shale, Monterey Formation, San Joaquin Valley, California".

In addition to the National AAPG Convention, Stanford University hosted a technical session and field trip as part of their "Rock Fracture Project". The field trip focused on siliceous shales of the Monterey Formation and included stops to view outcrop analogs to the Antelope Shale³. Dholakia¹ also presented a paper based on work done on Antelope Shale core from Buena Vista Hills and nearby outcrop analogs.

References

1. S. K. Dholakia, *Outcrop to Reservoir: Importance of Faulting to Hydrocarbon Migration in the Monterey Formation, California*, Stanford Rock Fracture Project, Vol. 7, M1-14, Stanford University, Stanford, CA., 1996.
2. S. K. Dholakia, Aydin, A., Pollard, D. D., and Zoback, M. D., *Hydrocarbon Transport and Shearing Processes in the Antelope Shale, Monterey Formation, San Joaquin Valley, California*, presented at the 1996 Annual American Association of Petroleum Geologists Convention, San Diego, California, May 19-22, 1996.
3. S. K. Dholakia, Lore, J., Brankman, M., and Roznovsky, T., *Fault Control on Hydrocarbon Migration in the Monterey Formation, California*, Field Trip Guidebook, Stanford Rock Fracture Project, Stanford University, Stanford, CA., 1996.

TITLE: ADVANCED RESERVOIR CHARACTERIZATION IN THE ANTELOPE SHALE TO ESTABLISH THE VIABILITY OF CO₂ ENHANCED OIL RECOVERY IN CALIFORNIA'S MONTEREY FORMATION SILICEOUS SHALES

Cooperative Agreement No.: DE-FC22-95BC14938

Contractor Name and Address: Chevron USA Inc., Production Company (CPDN), 5001 California Avenue, Bakersfield, California 93309

Date of Report: June 30, 1996

Award Date: February 7, 1996

Anticipated Completion Date: June 11, 1998

Government Award for Current Fiscal Year: \$ 2, 334,048

Principal Investigator: Stephen C. Smith, CPDN

Project Manager: Edith Allison, Bartlesville Project Office

Reporting Period: April 1, 1996 - June 30, 1996

RECEIVED
USD OE/PETC
96 JUL 26 AM 9:27
ACQUISITION & ASSISTANCE DIV.

Objective

The primary objective of this research is to conduct advanced reservoir characterization and modeling studies in the Antelope Shale reservoir. Characterization studies will be used to determine the technical feasibility of implementing a CO₂ enhanced oil recovery project in the Buena Vista Hills field. The Buena Vista Hills pilot CO₂ project will demonstrate the economic viability and widespread applicability of CO₂ flooding in fractured siliceous shales reservoirs of the San Joaquin Valley. The research consists of four primary work processes: Reservoir Matrix and Fluid Characterization; Fracture Characterization; Reservoir Modeling and Simulation; and, CO₂ Pilot Flood and Evaluation. Work done in these areas can be subdivided into two phases or budget periods. The first phase of the project will focus on the application of a variety of advanced reservoir characterization techniques to determine the production characteristics of the Antelope Shale reservoir. Reservoir models based on the results of the characterization work will be used to evaluate how the reservoir will respond to secondary recovery and EOR processes. The second phase of the project will include the implementation and evaluation of an advanced EOR pilot in the West Dome of the Buena Vista Hills field.

Summary of Technical Progress

The Buena Vista Hills project realized it's first major milestone in the second quarter of 1996 with the pending drilling of proposed project injection well. Regional fracture characterization work was also initiated in the second quarter. This report will summarize the status of those efforts.

Proposed Project Injection Well

The 653Z-26B well, located in Section 26, T31S-R23E, Kern County, California is scheduled to spud on July 1, 1996 after a fairly lengthy environmental review and permitting process. This well is being drilled in a position to serve as an injection well for any future enhanced oil recovery pilot project. The well is planned to be drilled to a total depth of 5000 feet and penetrate the entire productive Antelope Shale reservoir. It is anticipated that it will take 30 days to drill and complete this well. The well will be cased and will remain inactive pending the results of the reservoir characterization and modeling studies.

Extensive data collection will take place in this project well. The well will be deviated to increase the chance of intersecting natural fractures. Approximately 900-1000 feet of core will be cut and recovered in the Antelope Shale utilizing "low-invasion" and "soft" core handling techniques. After coring operations are completed, the wellbore will be logged with "state-of-the-art" open hole logging tools to collect data that will assist in the reservoir characterization process. Core Laboratories, Terra Tek, Dowell-Schlumberger, Chevron Petroleum Technology Company, and Horizon Mud Logging will all assist with the wellsite data collection process.

Regional Fracture Characterization

Regional fracture characterization studies are underway. Advanced Resources International (ARI) and Stanford University are assisting with these project tasks. ARI has gathered regional gravity, magnetic, and remote sensing data and begun reviewing that data. ARI will assist by integrating micro-, meso-, and macro-scale fracture data to better understand field-scale reservoir fracture data. This analysis will then also be analyzed within a basin-scale tectonic framework. The results of this work will provide a fracture characterization analog for other fields in the San Joaquin Valley with similar structural/strain and depositional histories.

Stanford has been working on core and outcrop studies to better characterize fracture zone geometries and distribution. Dholakia¹ summarized the role that faulting appears to play in hydrocarbon migration. Dholakia also noted and documented a relationship or association between fractures related to shearing processes and hydrocarbon transport. Additional work will be done with the core from 653-26B to further characterize fractures and their relationship to hydrocarbon production.

Technology Transfer

Chevron was very active in the 1996 National American Association of Petroleum Geologists (AAPG) Meeting in San Diego. Steve Smith, Principle Investigator, co-chaired oral and poster sessions on the topic of "Low Permeability, Fractured Reservoirs". Several of the papers in these sessions addressed issues of reservoir and fracture characterization in siliceous shale reservoirs such as the Antelope Shale. Dholakia, et al² presented their work on "Hydrocarbon Transport and Shearing Processes in the Antelope Shale, Monterey Formation, San Joaquin Valley, California".

In addition to the National AAPG Convention, Stanford University hosted a technical session and field trip as part of their "Rock Fracture Project". The field trip focused on siliceous shales of the Monterey Formation and included stops to view outcrop analogs to the Antelope Shale³. Dholakia¹ also presented a paper based on work done on Antelope Shale core from Buena Vista Hills and nearby outcrop analogs.

References

1. S. K. Dholakia, *Outcrop to Reservoir: Importance of Faulting to Hydrocarbon Migration in the Monterey Formation, California*, Stanford Rock Fracture Project, Vol. 7, M1-14, Stanford University, Stanford, CA., 1996.
2. S. K. Dholakia, Aydin, A., Pollard, D. D., and Zoback, M. D., *Hydrocarbon Transport and Shearing Processes in the Antelope Shale, Monterey Formation, San Joaquin Valley, California*, presented at the 1996 Annual American Association of Petroleum Geologists Convention, San Diego, California, May 19-22, 1996.
3. S. K. Dholakia, Lore, J., Brankman, M., and Roznovsky, T., *Fault Control on Hydrocarbon Migration in the Monterey Formation, California*, Field Trip Guidebook, Stanford Rock Fracture Project, Stanford University, Stanford, CA., 1996.

TITLE: ADVANCED RESERVOIR CHARACTERIZATION IN THE ANTELOPE SHALE TO
ESTABLISH THE VIABILITY OF CO₂ ENHANCED OIL RECOVERY IN CALIFORNIA'S
MONTEREY FORMATION SILICEOUS SHALES

Cooperative Agreement No.: DE-FC22-95BC14938

Contractor Name and Address: Chevron USA Inc., Production Company (CPDN), 5001 California
Avenue, Bakersfield, California 93309

Date of Report: June 30, 1996

Award Date: February 7, 1996

Anticipated Completion Date: June 11, 1998

Government Award for Current Fiscal Year: \$ 2, 334,048

Principal Investigator: Stephen C. Smith, CPDN

Project Manager: Edith Allison, Bartlesville Project Office

Reporting Period: April 1, 1996 - June 30, 1996

RECEIVED
USDOE/PETC
96 JUL 26 AM 9:27
NATIONAL & ASSISTANCE DIV.

Objective

The primary objective of this research is to conduct advanced reservoir characterization and modeling studies in the Antelope Shale reservoir. Characterization studies will be used to determine the technical feasibility of implementing a CO₂ enhanced oil recovery project in the Buena Vista Hills field. The Buena Vista Hills pilot CO₂ project will demonstrate the economic viability and widespread applicability of CO₂ flooding in fractured siliceous shales reservoirs of the San Joaquin Valley. The research consists of four primary work processes: Reservoir Matrix and Fluid Characterization; Fracture Characterization; Reservoir Modeling and Simulation; and, CO₂ Pilot Flood and Evaluation. Work done in these areas can be subdivided into two phases or budget periods. The first phase of the project will focus on the application of a variety of advanced reservoir characterization techniques to determine the production characteristics of the Antelope Shale reservoir. Reservoir models based on the results of the characterization work will be used to evaluate how the reservoir will respond to secondary recovery and EOR processes. The second phase of the project will include the implementation and evaluation of an advanced EOR pilot in the West Dome of the Buena Vista Hills field.

Summary of Technical Progress

The Buena Vista Hills project realized it's first major milestone in the second quarter of 1996 with the pending drilling of proposed project injection well. Regional fracture characterization work was also initiated in the second quarter. This report will summarize the status of those efforts.

Proposed Project Injection Well

The 653Z-26B well, located in Section 26, T31S-R23E, Kern County, California is scheduled to spud on July 1, 1996 after a fairly lengthy environmental review and permitting process. This well is being drilled in a position to serve as an injection well for any future enhanced oil recovery pilot project. The well is planned to be drilled to a total depth of 5000 feet and penetrate the entire productive Antelope Shale reservoir. It is anticipated that it will take 30 days to drill and complete this well. The well will be cased and will remain inactive pending the results of the reservoir characterization and modeling studies.

Extensive data collection will take place in this project well. The well will be deviated to increase the chance of intersecting natural fractures. Approximately 900-1000 feet of core will be cut and recovered in the Antelope Shale utilizing "low-invasion" and "soft" core handling techniques. After coring operations are completed, the wellbore will be logged with "state-of-the-art" open hole logging tools to collect data that will assist in the reservoir characterization process. Core Laboratories, Terra Tek, Dowell-Schlumberger, Chevron Petroleum Technology Company, and Horizon Mud Logging will all assist with the wellsite data collection process.

Regional Fracture Characterization

Regional fracture characterization studies are underway. Advanced Resources International (ARI) and Stanford University are assisting with these project tasks. ARI has gathered regional gravity, magnetic, and remote sensing data and begun reviewing that data. ARI will assist by integrating micro-, meso-, and macro-scale fracture data to better understand field-scale reservoir fracture data. This analysis will then also be analyzed within a basin-scale tectonic framework. The results of this work will provide a fracture characterization analog for other fields in the San Joaquin Valley with similar structural/strain and depositional histories.

Stanford has been working on core and outcrop studies to better characterize fracture zone geometries and distribution. Dholakia¹ summarized the role that faulting appears to play in hydrocarbon migration. Dholakia also noted and documented a relationship or association between fractures related to shearing processes and hydrocarbon transport. Additional work will be done with the core from 653-26B to further characterize fractures and their relationship to hydrocarbon production.

Technology Transfer

Chevron was very active in the 1996 National American Association of Petroleum Geologists (AAPG) Meeting in San Diego. Steve Smith, Principle Investigator, co-chaired oral and poster sessions on the topic of "Low Permeability, Fractured Reservoirs". Several of the papers in these sessions addressed issues of reservoir and fracture characterization in siliceous shale reservoirs such as the Antelope Shale. Dholakia, et al² presented their work on "Hydrocarbon Transport and Shearing Processes in the Antelope Shale, Monterey Formation, San Joaquin Valley, California".

In addition to the National AAPG Convention, Stanford University hosted a technical session and field trip as part of their "Rock Fracture Project". The field trip focused on siliceous shales of the Monterey Formation and included stops to view outcrop analogs to the Antelope Shale³. Dholakia¹ also presented a paper based on work done on Antelope Shale core from Buena Vista Hills and nearby outcrop analogs.

References

1. S. K. Dholakia, *Outcrop to Reservoir: Importance of Faulting to Hydrocarbon Migration in the Monterey Formation, California*, Stanford Rock Fracture Project, Vol. 7, M1-14, Stanford University, Stanford, CA., 1996.
2. S. K. Dholakia, Aydin, A., Pollard, D. D., and Zoback, M. D., *Hydrocarbon Transport and Shearing Processes in the Antelope Shale, Monterey Formation, San Joaquin Valley, California*, presented at the 1996 Annual American Association of Petroleum Geologists Convention, San Diego, California, May 19-22, 1996.
3. S. K. Dholakia, Lore, J., Brankman, M., and Roznovsky, T., *Fault Control on Hydrocarbon Migration in the Monterey Formation, California*, Field Trip Guidebook, Stanford Rock Fracture Project, Stanford University, Stanford, CA., 1996.