~~XXXX~~ RMIS View/Print Document Cover Sheet ~~XXXX~~

This document was retrieved from the Boeing ISEARCH System.

Accession #: D196054892

Document #: SD-WM-ER-496

Title/Desc:

THE CONTACT TEMP IGNITION CRITERIA FOR PROPAGATING
CHEMICAL REACTIONS INCLUDING THE EFFECT OF
MOISTURE & APPLICATION TO HANFORD WASTE

ENGINEERING DATA TRANSMITTAL

Page 1 of 1

1. EDT No 612312

2. To: (Receiving Organization) Distribution	3. From: (Originating Organization) TWRS Safety Basis	4. Related EDT No.: N/A
5. Proj./Prog./Dept./Div.: TWRS Safety Basis/TWRS	6. Cog. Engr.: R. J. Cash	7. Purchase Order No.: N/A
8. Originator Remarks: This EDT is for approval of WHC-SD-WM-ER-496, Rev. 0. This document describes the theory and experiments used to delineate fuel and moisture criteria necessary to support condensed phase exothermic propagating reactions.		9. Equip./Component No.: N/A
		10. System/Bldg./Facility: N/A
11. Receiver Remarks:		12. Major Assm. Dwg. No.: N/A
		13. Permit/Permit Application No.: N/A
		14. Required Response Date: 09/26/95

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Approval Designator	Reason for Trans- mittal	Originator Dispo- sition	Receiver Dispo- sition
1	WHC-SD-WM-ER-496		0	The Contact-Temperature Ignition (CTI) Criteria for Propagating Chemical Reactions Including the Effect of Moisture and Application to Hanford Waste	N/A	1	1	

16. KEY		
Approval Designator (F)	Reason for Transmittal (G)	Disposition (H) & (I)
E, S, Q, D or N/A (see WHC-CM-3-5, Sec.12.7)	1. Approval 2. Release 3. Information 4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)	1. Approved 2. Approved w/comment 3. Disapproved w/comment 4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged

17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)										(G)	(H)
Reason	Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN	(J) Name	(K) Signature	(L) Date	(M) MSIN	Reason	Disp.
1	1	Cog.Eng. R.J. Cash		9/26/95							
1	1	Cog. Mgr. E.J. Lipke		9/27/95							
		QA									
		Safety									
		Env.									

18. Signature of EDT Originator R. J. Cash 9/26/95	19. Authorized Representative for Receiving Organization Date	20. Cognizant Manager E. J. Lipke 9/27/95	21. DOE APPROVAL (if required) Ctrl. No. ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments
---	--	--	---

THIS PAGE INTENTIONALLY
LEFT BLANK

347 21 1993

RELEASE AUTHORIZATION

Document Number: WHC-SD-WM-ER-496, REV 0

Document Title: The Contact-Temperature Ignition (CTI) Criteria for Propagating Chemical Reactions Including the Effect of Moisture and Application to Hanford Waste

Release Date: 9/27/95

This document was reviewed following the procedures described in WHC-CM-3-4 and is:

APPROVED FOR PUBLIC RELEASE

WHC Information Release Administration Specialist:

Kara Broz

9/27/95

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

This report has been reproduced from the best available copy. Available in paper copy. Printed in the United States of America. To obtain copies of this report, contact:

Westinghouse Hanford Company - Document Control Services
P.O. Box 1970, Mailstop H6-08, Richland, WA 99352
Telephone: (509) 372-2420; Fax: (509) 376-4989

THIS PAGE INTENTIONALLY
LEFT BLANK

SUPPORTING DOCUMENT

1. Total Pages *24*

2. Title

The Contact-Temperature Ignition (CTI) Criteria for Propagating Chemical Reactions Including the Effect of Moisture and Application to Hanford Waste

3. Number

WHC-SD-WM-ER-496

4. Rev No.

Rev. 0

5. Key Words

CTI, Criteria, Ferrocyanide, Fuel, Moisture, Propagating, Waste

6. Author

Name: R. J. Cash

[Signature]
Signature

Organization/Charge Code 74200/N211C

7. Abstract

To assure the continued absence of uncontrolled condensed-phase chemical reactions in connection with the Hanford waste materials, efforts have been underway including both theoretical and experimental investigations to clarify the requirements for such reactions. This document defines the differences and requirements for homogeneous runaway and propagating chemical reactions including a discussion of a general contact-temperature ignition (CTI) condition for propagating reactions that includes the effect of moisture. The CTI condition implies that the contact temperature or interface temperature between reacted and unreacted materials must exceed the ignition temperature and is compared to experimental data including both synthetic ferrocyanide and surrogate organic materials. In all cases, the occurrences of ignition accompanied by self-propagating reactions are consistent with the theoretical anticipations of the CTI condition.

8. RELEASE STAMP

THIS PAGE INTENTIONALLY
LEFT BLANK

CONTENTS

1.0 INTRODUCTION AND SUMMARY	1-1
2.0 CHEMICAL REACTION TYPES AND THEORETICAL REQUIREMENTS INCLUDING MOISTURE CONSIDERATIONS	2-1
2.1 THERMAL RUNAWAY	2-1
2.2 PROPAGATING REACTION	2-2
3.0 COMPARISON WITH EXPERIMENTAL DATA	3-1
3.1 IGNITION TEMPERATURE	3-1
3.2 COMBUSTION TEMPERATURE	3-6
4.0 APPLICATION OF DATA AND CTI CONDITION	4-1
4.1 FERROCYANIDE-NITRITE/NITRATE REACTION	4-1
4.2 ORGANIC-NITRITE/NITRATE REACTIONS	4-1
4.3 GENERALIZED SAFETY CRITERIA	4-6
5.0 NOMENCLATURE	5-1
6.0 REFERENCES	6-1

APPENDICES

A CTI CRITERION FOR A DRY REACTIVE POWDER	A-1
B CTI CRITERION FOR A MOIST REACTIVE POWDER	B-1
C MODEL OF HOT SPOT INITIATED REACTION WAVE IN MOIST REACTIVE WASTE	C-1
D NUMERICAL EXAMPLE AND COMPARISON WITH CTI CRITERION FOR REACTION PROPAGATION	D-1

LIST OF FIGURES

3-1	Reactive System Screening Tool Containment and Test Cell	3-2
3-2	Transition From a Homogeneous Runaway Reaction to a Self-propagating Reaction Occurring at About 300 °C	3-3
3-3	Transition to a Self-propagating Reaction Occurring at About 250 °C	3-4
3-4	Illustration of Tube Propagation Test Cell	3-8
3-5	Illustration of Combustion Temperatures for a 28 wt% NaAc (dry basis) with 15% Moisture (wet basis)	3-9
3-6	Illustration of Combustion Temperatures for 35 wt% $\text{Na}_2\text{NiFe}(\text{CN})_6$ (dry basis) and 15 wt% Moisture (wet basis)	3-10
3-7	Comparison Between Surrogate Data (Measured Fuel Concentration Times Theoretical Heat of Reaction) Including the Effect of Moisture and Inequality (2-14) Evaluated for Sodium Acetate	3-11
4-1	Propagation Envelope for Ferrocyanide and Comparison with Flow Sheet Materials and the Most Energetic Samples from C-109 and C-112	4-2
4-2	Comparison Between Measured TOC Values and the Proposed Safety Criteria, Inequality	4-4
4-3	Relationship Between Water-NaOH and Water- NaNO_3 Equilibrium Solutions and Relative Humidities	4-7

LIST OF TABLES

3-1 Measured Ignition Temperatures (RSST), Lower Propagation Limit (LPL) at 30 °C (Tube Propagation Tests) and Combustion Temperatures (Tube Propagation Tests) and Comparison with CTI Condition	3-5
3-2 Effect of Moisture Concentration Upon Propagation at 30 °C (Tube Propagation Tests)	3-7
4-1 Margin of Safety Provided By the Proposed Safety Criteria; % TOC > 4.5	4-3
4-2 Measured Solubilities of Organic Complexants, TOC Measurements and Requirements for Propagation	4-5

LIST OF TERMS

CTI	contact-temperature ignition
DBP	dibutyl phosphate
EDTA	ethylenediamine tetra acetate
HEDTA	hydroxyethylenediamine triacetate
LPL	lower propagation limit
RSST	reactive system screening tool
TOC	total organic carbon

1.0 INTRODUCTION AND SUMMARY

The assessment of chemical safety vulnerabilities in connection with Hanford site waste includes concerns related to potential uncontrolled condensed-phase chemical reactions involving ferrocyanide and various organic substances. The waste forms of concern include sludges and salt cakes which contain ample amounts of sodium nitrate and sodium nitrite ($\text{NaNO}_3/\text{NaNO}_2$) oxidizer material and various quantities of water.

Ferrocyanide-bearing sludge waste resulted from the need to reduce storage volume; ferrocyanide [$\text{Na}_4\text{Fe}(\text{CN})_6$] along with nickel sulfate (NiSO_4) were added to the liquid waste to precipitate ^{137}Cs out of solution. Sodium nitrate is a major waste component, resulting from the addition of sodium hydroxide (NaOH), added to the liquid waste to neutralize the nitric acid (HNO_3). Given the right conditions, an intimate mixture of such chemicals could react, resulting in heat release and gas production.

Organic-bearing sludge and salt cake waste resulted from the need to remove ^{137}Cs and other fission products from the various waste streams. Organics added to the high level wastes included non-salt volatile organic substances such as tributyl phosphate, normal paraffin hydrocarbon, and the non-volatile salt organic complexants such as tetra-sodium ethylenediamine tetra acetate (EDTA), tri-sodium hydroxyethylenediamine triacetate (HEDTA), sodium citrate, and sodium hydroxyacetate. Degradation of some of these compounds has occurred over time to produce substances like dibutyl phosphate (DBP) and sodium oxalate. Again, these organic-bearing wastes contain large amounts of oxidizer material ($\text{NaNO}_3/\text{NaNO}_2$) and various quantities of water.

In order to assure the continued absence of uncontrolled condensed-phase chemical reactions in connection with the Hanford waste materials, efforts have been underway including both theoretical and experimental investigations to clarify the requirements for such reactions. We begin by defining the differences and requirements for homogeneous runaway and propagating chemical reactions including a discussion of a general contact-temperature ignition (CTI) condition for propagating reactions which includes the effect of moisture (Section 2.0). The CTI condition implies that the contact temperature or interface temperature between reacted and unreacted materials must exceed the ignition temperature and is compared to experimental data including both synthetic ferrocyanide and surrogate organic substances in Section 3.0. These include measured ignition temperatures obtained with the Reactive System Screening Tool (RSST), (Creed and Fauske 1993)¹ and measured combustion temperatures obtained with dedicated tube propagation tests (Fauske 1992). In all cases, the occurrences of ignition accompanied by self-propagating reactions are consistent

¹The RSST is a widely-used industry tool implementing the AIChE-DIERS (Design Institute for Emergency Relief Systems) methods to quantify runaway reactions to support safe design and operation in the commercial chemical industry.

with the theoretical anticipations of the CTI condition. Finally, in Section 4, preliminary propagation envelopes are suggested that are applicable to ferrocyanide and organic-bearing waste, and include the effect of moisture.

The suggested lower bound theoretical fuel concentration value (x_f) for $\text{Na}_2\text{NiFe}(\text{CN})_6$ based upon satisfying the CTI condition is

$$x_f > 0.10 + 0.47 x_w ; \quad x_w \leq 0.2 \quad (1-1)$$

where x_w is the moisture weight fraction. In the absence of free moisture, $x_f = 0.10$ as compared to the measured value of approximately 0.15 required for sustained combustion at ambient waste temperature.

Since total organic carbon (TOC) values are commonly measured for tank waste and are available for many tanks, the envelope for the organic bearing waste is also discussed in terms of TOC content. The early selection of sodium acetate as a safe surrogate material (Babad and Turner 1993) is confirmed by the extensive additional surrogate data summarized in Section 3 and further discussed in Section 4. As such, using the relevant data for this system and satisfying the CTI condition, the suggested lower bound theoretical TOC envelope is

$$\% \text{ TOC} > 4.5 + 17 x_w ; \quad x_w \leq 0.2 \quad (1-2)$$

In the absence of free moisture, the TOC value is 4.5 wt% as compared to the lowest measured value of about 6 wt% required for sustained combustion at ambient temperature for the non-volatile salt organic complexants tested to date including Na_3HEDTA . While their theoretical heat of reaction values are higher, the volatile organic substances, including their salts such as sodium and aluminum DBPs, were found not to exhibit propagating characteristics. The proposed safety criteria [Inequality (1-2)] represents a safety margin of at least 30%, which is well in excess of measurement uncertainties ($< 5\%$).

Consistent with the above observations, the following lower bound theoretical chemical energy release ($\Delta H_{\min}$) envelope is suggested

$$\Delta H_{\min} \text{ (MJ/kg)} > 1.2 + 4.5 x_w \quad (1-3)$$

In the absence of free moisture, the threshold value is about 1200 J/gm (~ 290 cal/gm) as compared to the value of 1600 J/gm (~ 380 cal/gm) derived from the measured combustion threshold temperature of approximately 800 °C. Again the margin of safety is about 30%.

Finally, both theoretical and experimental considerations show that the presence of about 20 wt% moisture is sufficient to eliminate the potential for sustained combustion altogether, including stoichiometric fuel-oxidizer mixtures. As such, since typical ferrocyanide-bearing sludge has been shown to be inherently capable of retaining moisture in excess of 20 wt%,

including after interim stabilization (Epstein et al. 1994), propagating reactions in this waste form can be ruled out as being independent of the fuel types and concentration levels. In the case of salt cakes, on the other hand, draining in connection with interim stabilization may result in moisture levels well below 20 wt%. However, the non-volatile sodium salt organic complexants of concern appear to be highly soluble in saturated $\text{NaNO}_3/\text{NaNO}_2$ - water solutions (Barney 1994), implying that drained salt cakes are also largely lacking such fuels - the exception being the possibility of sodium oxalate. This salt is essentially insoluble, but according to the CTI condition and experimental observations, its heat of reaction is also too low to support combustion, even for stoichiometric conditions in the complete absence of moisture.

This page intentionally left blank.

2.0 CHEMICAL REACTION TYPES AND THEORETICAL REQUIREMENTS INCLUDING MOISTURE CONSIDERATIONS

In terms of a chemical safety vulnerability assessment, it is essential to differentiate between so-called homogeneous thermal runaway reactions and propagating reactions. These are discussed below, including specific minimum requirements for such reactions and the important role of moisture in preventing propagating reactions.

2.1 THERMAL RUNAWAY

This type of reaction is generally a bulk phenomenon and the reaction rates normally have an Arrhenius type dependence on temperature (such as doubling for every 10 °C temperature rise). The potential for runaway is generally assessed by comparing adiabatic runaway and characteristic cooling response times to the storage or exposure time.

If the following inequality is satisfied:

$$t_a > t_s \quad (2-1)$$

where t_a is the characteristic time of adiabatic runaway and t_s is the storage time, the situation can immediately be judged to be safe, i.e., a thermal runaway reaction cannot take place. Unfortunately, since the value of t_s is not known for the materials in the Hanford waste tanks and t_s is very large (tens of years), Inequality (2-1) is of little use.

However, thermal runaway can also be ruled out if the following inequality is satisfied

$$t_a > t_c \quad (2-2)$$

where t_c is the characteristic passive cooling response time of the system. In case of the waste tanks, t_c can be estimated from

$$t_c \approx \frac{L^2}{\alpha} \quad (2-3)$$

where L can be set equal to the total nonconvective waste height in the tank and α is the thermal diffusivity of the waste material. The values of t_c for the Hanford waste tanks are generally less than a year (small compared with the time that has already elapsed without runaway having occurred), providing proof that Inequality (2-2) is indeed satisfied at the present time. *This conclusion can be made without requiring a knowledge of t_a or the actual chemical composition and water content.* For the passively cooled tanks² (decay and

²We note that a Kyshtym type explosion (Fisher 1990) can be ruled out for passively cooled waste tanks.

reaction heat are removed by natural phenomena such as conduction and free convection) which are clearly cooling down, if a thermal chemical runaway reaction could take place, it would have occurred many years ago when the tanks were at higher temperatures.

2.2 PROPAGATING REACTION

Since homogeneous runaway reaction scenarios can be ruled out for the existing Hanford waste conditions, the necessary conditions for a propagating reaction through cold waste material becomes of principal interest. In contrast to homogeneous runaway reactions, a propagating reaction occurs as a reaction zone traveling through the solid or liquid phase (similar to a flame propagating through a flammable vapor cloud), and the rate shows no simple dependence on temperature.

Given the presence of an adequate amount of oxidizer ($\text{NaNO}_3/\text{NaNO}_2$) and an ignition source such as a hot spot or flame to locally bring the temperature up to the required ignition temperature T_{ig} , sustained deflagration or propagation depends on the fuel concentration and the presence of diluents such as water. It is important to note that the ignition temperature T_{ig} is entirely different from the temperature sought in the theory of thermal runaway reactions, which is based on an imbalance between chemical heat produced by an Arrhenius type reaction mechanism and the heat removal by conduction [reflected by Inequality (2-2)]. T_{ig} is essentially a temperature threshold separating two entirely different condensed phase reaction-mechanism regimes. For ($T > T_{ig}$) the reactant consumption rate and the concomitant temperature rise rate can be extremely high.

Suppose a region of the reactive material exceeds its ignition temperature and is essentially instantaneously and uniformly chemically heated to its adiabatic reaction temperature T_{ad} . The lower bound value of the necessary chemical energy release or adiabatic reaction temperature T_{ad} that will initiate a propagating reaction through the surrounding cold reactive material of temperature T_o can be related to the basic requirement that the contact or interface temperature T_i between the reacted hot material and unreacted cold material must be greater than the ignition temperature T_{ig} .

$$T_i > T_{ig} \quad (2-4)$$

If Inequality (2-4) is not satisfied, the reaction will slow down and be quenched by the much colder unreacted material.

The conduction problem that arises immediately following the local, instantaneous chemical heating of the reactive medium resembles the classical thermal contact problem that results from suddenly bringing together two semi-infinite slabs with different initial temperatures, namely T_o and T_{ad} . The temperature T_i at the plane of separation of the reacted and unreacted regions is

$$\frac{T_i - T_o}{T_{ad} - T_o} = \frac{1}{1 + \sigma} \quad (2-5)$$

$$\sigma = \frac{k_u}{k_r} \left(\frac{\alpha_r}{\alpha_u} \right)^{1/2} \quad (2-6)$$

where k is the thermal conductivity, α is the thermal diffusivity and subscripts r and u represent reacted and unreacted materials, respectively. (For further details see Appendix A.) The value of T_i is reached instantaneously, or as soon as the two regions contact one another. If the products of the physical properties are assumed to be the same for both regions (ρck), where ρ is the density and c is the specific heat, the contact temperature is simply the arithmetic mean of the adiabatic reaction temperature and the initial temperature, $T_i = (T_{ad} + T_o)/2$.

In writing Equation (2-5), it is assumed that no heat is transmitted from the reacting region to the surrounding unreacted region before the reacted region is chemically heated to T_{ad} . In most applications of interest, some heat will "leak" from the reacting region to the surroundings before the reaction is complete. The energy supplied to locally raise the reactive material temperature to its ignition temperature will also result in a reacted-region-peak temperature that exceeds T_{ad} . If these departures from the ideal situation of an adiabatically and purely chemically heated region up to T_{ad} are treated in full detail, then the conduction theory for the prediction of T_i becomes complicated and the CTI condition would be difficult to apply. Separate computer solutions would be needed for each case considered and the CTI condition would not result in a useful rule for ignition and reaction propagation. To avoid this complexity, Equation (2-5) is selected for calculating T_i . The fidelity of this approximation must be judged by comparison of the CTI criterion with experimental results.

The problem of predicting the onset of ignition or, equivalently, the existence of a self-propagating reaction front from the reaction free state can now be approached. If thermal conditions for the reactive material are such that Equation (2-5) predicts a contact temperature T_i that is below the ignition temperature T_{ig} , then according to Inequality (2-4) ignition or reaction propagation is thermally impossible. Thus, assuming the physical properties are the same for both regions, a necessary condition for propagating reactions in dried reactive powder is simply that the adiabatic combustion temperature must be high enough to satisfy the inequality

$$T_{ad} > 2 T_{ig} - T_o \quad (2-7)$$

A more general contact-temperature ignition condition for reaction propagation accounting for moisture can now be obtained by subtracting away from the contact temperature T_i the

effective temperature difference taken up by evaporation of the water, namely $x_w \lambda / c_w$, to arrive at

$$T_{ad} > 2 \left(T_{ig} + \frac{x_w \lambda}{c_w} \right) - T_o \quad (2-8)$$

where x_w is the water mass fraction, λ is the latent heat of evaporation and c_w is the water specific heat³. (For further details on equation development see Appendix B.)

A lower bound theoretical value for the chemical energy release ΔH_{min} to sustain a propagating reaction can now be obtained by assessing the reaction enthalpy required to raise the temperature of a unit mass of reacting mixture from T_o to T_{ad}

$$\Delta H_{min} = (T_{ad} - T_o) \bar{c} + x_w \lambda \quad (2-9)$$

where $\bar{c}$ is an effective average specific heat value of the reacting mixture and its products over the temperature range of interest that also accounts for heat of melting and sensible heats of water and its vapor. Applying the CTI condition together with Equation (2-9), the following is obtained:

$$\Delta H_{min} > 2 \left[T_{ig} - T_o + \frac{x_w \lambda}{c_w} \right] \bar{c} + x_w \lambda \quad (2-10)$$

The corresponding lower bound theoretical fuel fraction x_f can be obtained from

$$x_f \Delta H_R = \Delta H_{min} \quad (2-11)$$

where ΔH_R is the ideal heat of reaction based on a unit mass of fuel. Again applying the CTI condition and solving for x_f , Inequality (2-12) is obtained:

$$x_f > \frac{2 \left[T_{ig} - T_o + \frac{x_w \lambda}{c_w} \right] \bar{c} + x_w \lambda}{\Delta H_R} \quad (2-12)$$

It can be noted that for typical values of T_{ig} ($\sim 250^\circ \text{C}$), T_o ($\sim 30^\circ \text{C}$) and $\bar{c}$ ($\sim 2000 \text{ J kg}^{-1} \text{ K}^{-1}$), Inequalities (2-8), (2-10) and (2-12) can be simplified to

³Supportive detailed theoretical discussions including a numerical analysis of combustion front propagation from a dried hot spot region into a wet region and comparisons with Inequality (2-8) are provided in Appendices C and D.

$$T_{ad} > 2 \left[T_{ig} + \frac{x_w \lambda}{c_w} \right] \quad (2-13)$$

$$\Delta H_{min} > 2 [T_{ig} \bar{c} + x_w \lambda] \quad (2-14)$$

$$x_f > \frac{2 [T_{ig} \bar{c} + x_w \lambda]}{\Delta H_R} \quad (2-15)$$

with little loss of accuracy. The claim of lower bound values is still well justified by comparisons to experimental data provided in Section 3.0.

Finally, it can be noted that the above Inequalities become non-physical for values of x_w greater than about 0.2 since the liquid phase now becomes the continuous phase as illustrated below. For such conditions the contact temperature T_i will not exceed the boiling point of the salt solution ($\sim 120^\circ\text{C}$) which is well below T_{ig} values of interest ($\sim 250^\circ\text{C}$).

Considering that randomly packed spheres occupy about 60 volume %, liquid volume fractions in excess of 40% imply that the particles need not be in contact, i.e., the liquid phase is continuous. In estimating the moisture concentration that will result in the liquid being the continuous phase, it is important to also consider that the interstitial liquid contains dissolved salts; this has the effect of adding additional solution volume. As such, the liquid fraction, α_l , can be estimated from

$$\alpha_l = \frac{\frac{x_w}{\rho_w} + \frac{x_s}{\rho_s}}{\frac{x_w}{\rho_w} + \frac{x_s}{\rho_s} + \frac{(1 - x_w - x_s)}{\rho_{in}}} \quad (2-16)$$

where ρ_w is the water density, ρ_s is the density of the soluble salt, ρ_{in} is the density of insoluble material, and x_s is the weight fraction of soluble salts. Using the following property values of $\rho_w = 1 \text{ g/cm}^3$, $\rho_s = \rho_{in} = 2.2 \text{ g/cm}^3$ and setting $x_w = 0.2$ and $x_s = 0.1$ (this is about half the solubility value of $\text{NaNO}_3/\text{NaNO}_2$ in water at typical waste temperatures), $\alpha_l = 0.435 > 0.4$ is obtained, suggesting that for a moisture concentration of approximately 20 wt%, the interstitial liquid solution is the continuous phase. Note that for a saturated interstitial liquid solution ($x_s \approx 0.2$), the value of α_l is 0.52 which clearly implies that the sludge or salt cake liquid phase is continuous.

The results of ongoing experiments to study the propagation of combustion waves through dry and wet synthetic ferrocyanide/salt and organic surrogate/salt powders are summarized in

Section 3. The occurrences of ignition accompanied by self-propagating reactions are found to be consistent with the theoretical anticipation of the CTI condition [e.g. Inequality (2-8)].

3.0 COMPARISON WITH EXPERIMENTAL DATA

In this section, the CTI condition is compared to measurements obtained to date with various organic waste surrogate and synthetic ferrocyanide materials⁴. Measured quantities of key interest include ignition and combustion temperatures, the fuel concentration required to support propagating reactions, and the moisture concentration that will inhibit such reactions. A summary of key data are provided below; further details, including all data obtained to date will be provided in (Fauske 1995a) and (Fauske 1995b).

3.1 IGNITION TEMPERATURE

The Reactive System Screening Tool (RSST) is being used to measure the ignition temperature. The RSST (Figure 3-1) consists of a spherical glass reaction vessel, its surrounding jacket heater and insulation, a thermocouple (imbedded in sample), a pressure transducer, a stainless steel containment vessel, and, not shown, a magnetic stirrer base, a control box containing the heater power supply, temperature/pressure amplifiers, and a data acquisition and control panel. The sample cell volume is 10 ml and the containment volume is 350 ml. A key feature of the apparatus is its low effective heat capacity relative to that of the sample whose value, expressed as the capacity ratio, is ~ 1.04 (i.e., quite adiabatic).

Typically, a sample (~ 10 gm) is heated at a constant rate of approximately 1°C per minute and the sample self-heat rate dT/dt is found as a function of sample temperature under an essentially zero heat loss condition. Figure 3-2 is an example of reaction kinetics for an initially solid waste surrogate of sodium acetate, sodium nitrate, and sodium hydroxide, with a sodium acetate concentration of 24 wt% (or 7 wt% TOC content). Significant exothermic activity is noted at about 200°C which leads to a runaway reaction exhibiting an Arrhenius type dependence on temperature up to approximately 300°C ; at this temperature, a dramatic step change in the rate of temperature rise is observed. This is interpreted as a threshold for rapid wave-like reaction propagation, and the temperature of 300°C is referred to as the ignition temperature. Another example of the dramatic change in the rate of temperature rise is illustrated in Figure 3-3 for the synthetic In Farm flow sheet material with a ferrocyanide concentration of about 26 wt% (dry basis).

⁴In lieu of precise knowledge of chemical forms and variety of possible mixtures of organic fuels actually in the single shell tanks, surrogate materials of known composition are sought that exhibit similar chemical reaction characteristics and similar or greater reaction energies. Surrogate materials considered to date include sodium oxalate and sodium HEDTA which are believed to represent lower and upper bound reaction energies for the non-volatile salt organic complexants, and sodium and aluminum dibutyl phosphate which are believed to represent upper bound reaction energies for the volatile organic compounds.

Figure 3-1. Reactive System Screening Tool Containment and Test Cell.

Figure 3-2. Transition From a Homogeneous Runaway Reaction to a Self-propagating Reaction Occurring at About 300 °C.

Figure 3-3. Transition to a Self-propagating Reaction Occurring at About 250 °C.

It is important to note that the onset of propagating reactions in the RSST tests occur when the entire sample has essentially reached the ignition temperature. This is in contrast to the dedicated tube propagation tests discussed below in which propagation can occur at ambient waste temperature given an adequate ignition source. Measured ignition temperatures for synthetic ferrocyanide simulant and relevant organic surrogate compounds are summarized in Table 3-1. The organic surrogate tests included a 4:1 mass ratio of NaNO_3 and NaNO_2 . Table 3-1 shows that the lowest ignition temperature of about 220 °C is about 200 °C higher than typical waste temperatures. It may also be noted from Table 3-1 that the onset of propagating reactions were not observed with any of the non-salt volatile organic compounds like dibutyl and tributyl phosphates or their salts such as aluminum and sodium DBPs. This behavior can be related to early decomposition of these compounds (in the 150-200 °C temperature range) both with and without the presence of the nitrate-nitrite oxidizer. The absence of propagating reaction with the sodium oxalate system is also worth noting, and is consistent with the CTI criterion as discussed later.

Table 3-1. Measured Ignition Temperatures (RSST), Lower Propagation Limit (LPL) at 30 °C (Tube Propagation Tests) and Combustion Temperatures (Tube Propagation Tests) and Comparison with CTI Condition.

Fuel	Formula	M	T_{ig} °C	LPL wt%	T_{meas} °C	$> 2 T_{ig}$ °C
Na Acetate	$\text{NaC}_2\text{H}_3\text{O}_2$	82	300	~20.5 (~6)	~800	> 600
Na Oxalate	$\text{Na}_2\text{C}_2\text{O}_4$	134	No	-	-	-
Na Citrate	$\text{Na}_3\text{C}_6\text{H}_5\text{O}_7$	258	230	~28.9 (~8)	~800	> 460
Na Stearate	$\text{NaC}_{18}\text{H}_{35}\text{O}_2$	306	260	> 12.75 (> 9)	-	-
Na_3HEDTA	$\text{Na}_3\text{C}_{10}\text{H}_{15}\text{O}_7\text{N}_2$	344	220	~17.2 (~6)	~800	> 440
Dibutyl Phosphate	$(\text{C}_4\text{H}_9)_2\text{HPO}_4$	210	No	-	-	-
Tributyl Phosphate	$(\text{C}_4\text{H}_9)_3\text{PO}_4$	266	No	-	-	-
Al Dibutyl Phosphate	$\text{Al}[(\text{C}_4\text{H}_9)_2\text{PO}_4]_3$	654	No	-	-	-
Na Dibutyl Phosphate	$\text{Na}(\text{C}_4\text{H}_9)_2\text{PO}_4$	232	No	-	-	-
Na Ferrocyanide	$\text{Na}_2\text{NiFe}(\text{CN})_6$	316	250	~15.5 (~3.5)	~800	> 500

Note: Total carbon content reported in parentheses

3.2 COMBUSTION TEMPERATURE

Dedicated tube propagation tests are being carried out that provide measurements of reaction or combustion temperatures in connection with sustained propagation through cold waste surrogate material. In these tests (see Figure 3-4), a confined low heat capacity stainless steel cylinder containing simulated waste (50-70 gm) is ignited at the open upper end and the rate of propagation (if any) is measured by noting the time when the reaction front passes imbedded thermocouples. The ignition energy is about 20 watts and the igniter is left on until sustained propagation is observed (~ 15-20 seconds). In case of no propagation, the igniter is usually left on for at least 1 minute. A heavy 4-liter steel containment vessel and various instrumentation and data acquisition equipment, are not shown in Figure 3-4. These data also provide the necessary fuel concentration to sustain propagating reactions, namely the lower propagation limit (LPL) in absence of free water, and the moisture content that will inhibit propagations including stoichiometric fuel-oxidizer mixtures at ambient waste temperature.

An example of the relevant temperature data for a successful propagation test is illustrated in Figure 3-5. The sample included about 35 wt% sodium acetate (dry basis) and 15% moisture (wet basis)⁵. Another example is illustrated in Figure 3-6; this sample included about 35 wt% $\text{Na}_2\text{NiFe}(\text{CN})_6$ (dry basis) and 15 wt% moisture (wet basis).

Measured LPL values and corresponding combustion temperatures in the absence of free moisture are listed in Table 3-1. It is of particular interest to note that while the ignition temperature T_{ig} appears to decrease with increasing molecular weight (Table 3-1), the measured combustion temperature corresponding to measured LPL values appears to remain constant at about 800 °C. For temperatures below this value, which also is the approximate low temperature limit of most hydrocarbon flames (Beitel 1976a), sustained combustion is not possible. Using the theoretical values for heat of reaction (Burger 1993) the measured LPL fuel concentration values suggest an approximate chemical energy release threshold for sustained combustion of approximately 1600 J/gm (380 cal/gm).

The effect of moisture on propagation is illustrated in Table 3-2, including both successful and unsuccessful propagation events. In all cases of sustained propagation, the measured combustion temperatures exceed the lower bound values required by the CTI condition [Inequality (2-13)]. The effect of moisture is further illustrated in Figure 3-7 where the ignition temperature [Inequality (2-14)] for sodium acetate ($T_{ig} = 300$ °C and $\bar{C} = x_{LPL}$ $\Delta H_R/T_{m,calc} = 0.205 \cdot 7.9 \cdot 10^6/800 \approx 2000 \text{ J kg}^{-1} \text{ K}^{-1}$) is compared to the experimental observations (measured fuel concentration times the theoretical heat of reaction). The sodium acetate surrogate is seen to provide a safe but not overly conservative envelope of the data. Especially noteworthy and also consistent with Equation (2-16) and the related discussion is the absence of sustained combustion for moisture a concentration of 20 wt%

⁵The moisture in this case may actually be bound rather than free water, as $\text{NaAc} \cdot 3\text{H}_2\text{O}$ is known to be stable below about 150°C.

including stoichiometric fuel-oxidizer mixtures. This observation is also consistent with similar findings related to combustion potential of charcoal and black powder (Beitel 1976b).

Table 3-2. Effect of Moisture Concentration Upon Propagation at 30 °C
(Tube Propagation Tests)

Fuel	Fuel Conc. wt% (Dry Basis)	Water Conc. wt% (Wet Basis)	T_{mcs} °C	$> 2 \left[T_{ig} + \frac{x_w \lambda}{c_w} \right]$ °C
Na Acetate ($NaC_2H_3O_2$)	18.8	0	~ 30	-
Na Acetate	20.5	0	~ 800	> 600
Na Acetate	25.5	10	~ 900	> 704
Na Acetate	22.5	10	~ 30	-
Na Acetate	35.0	15	~ 900	> 757
Na Acetate	28.0	15	~ 30	-
Na Acetate	37.5 Stoichiometric	17	~ 900	> 778
Na Acetate	37.5	20	~ 30	-
Na HEDTA ($Na_3C_{10}H_{15}O_7N_2$)	15.5	0	~ 30	-
Na HEDTA	17.2	0	~ 800	> 440
Na HEDTA	28.0	10	~ 850	> 545
Na HEDTA	31.5 Stoichiometric	13	~ 800	> 576
Na HEDTA	31.5	15	~ 30	-
Na Ferrocyanide ($Na_2NiFe(CN)_6$)	26	8	~ 850	> 584
Na Ferrocyanide	26	12	~ 30	-
Na Ferrocyanide	35	15	~ 950	> 657
Na Ferrocyanide	35	20	~ 30	-

Figure 3-4. Illustration of Tube Propagation Test Cell.

Figure 3-5. Illustration of Combustion Temperatures for a 28 wt% NaAc (dry basis) with 15% Moisture (wet basis).

Figure 3-6. Illustration of Combustion Temperatures for 35 wt% $\text{Na}_2\text{NiFe}(\text{CN})_6$ (dry basis) and 15 wt% Moisture (wet basis).

Figure 3-7. Comparison Between Surrogate Data (Measured Fuel Concentration Times Theoretical Heat of Reaction) Including the Effect of Moisture and Inequality (2-14) Evaluated for Sodium Acetate.

Note that the moisture content in case of sodium acetate may actually be bound rather than free water, as $NaAc \cdot 3H_2O$ is known to be stable below $150\text{ }^{\circ}\text{C}$.

This page intentionally left blank.

4.0 APPLICATION OF DATA AND CTI CONDITION

In this section, the data obtained to date with the use of the CTI condition are presented in formats that readily allow the assessment of chemical safety vulnerability of Hanford wastes. The presentation includes both ferrocyanide and organic bearing waste as well as a generalized chemical energy threshold for propagating reactions.

4.1 FERROCYANIDE-NITRITE/NITRATE REACTION

The propagation envelope for this system including the effect of moisture is shown in Figure 4-1. The solid part of the envelope represents experimental data which did not result in sustained propagation, i.e. no burn. The dotted part of the envelope (equivalent to the upper flammability curve) represents estimates based upon stoichiometric requirements of the oxidizer and treating the excess fuel as inerts. Compositions corresponding to the In Farm 1, U Plant 2, and T Plant flow sheet materials and the most energetic sample withdrawn from tanks C-112 and C-109 (Simpson 1993) are also shown in Figure 4-1. Since significant global water loss approaching the 20% moisture level as well as local dryout can be ruled out for the ferrocyanide containing sludges (Epstein et al. 1994) it appears reasonable to conclude that propagating reactions do not represent a safety issue.

Not shown in Figure 4-1 is the conservative theoretical estimate based upon the CTI condition and setting $T_{ig} = 250\text{ }^{\circ}\text{C}$, $\bar{c} \approx 2000\text{ J kg}^{-1}\text{ K}^{-1}$ and $\Delta H_R = 9.5 \cdot 10^6\text{ J kg}^{-1}$

$$x_f > 0.10 + 0.47 x_w ; \quad x_w \leq 0.2 \quad (4-1)$$

It is noted that application of Inequality (4-1) and ignoring the presence of moisture altogether, would leave only tanks C-108 and C-111 in the Conditionally Safe category; all other ferrocyanide tanks of concern would fall in the Safe category (see Table 7-1 of Postma et al. 1994).

4.2 ORGANIC-NITRITE/NITRATE REACTIONS

Sodium acetate was selected early in the testing campaign to be a representative organic waste surrogate for estimating the energetics of tank waste relative to potential condensed phase propagating organic-nitrite/nitrate reactions (Babad and Turner 1993). Preliminary RSST tests with sodium acetate led to a recommended TOC value of 5 wt% as a reasonable upper limit for non-propagating fuel-oxidizer mixtures.

The early selection of sodium acetate as a safe surrogate material is confirmed by the extensive additional surrogate data discussed in Section 3.0. We note that non-salt volatile organics such as DBP, tributyl phosphate and their salts with higher theoretical

Figure 4-1. Propagation Envelope for Ferrocyanide and Comparison with Flow Sheet Materials and the Most Energetic Samples from C-109 and C-112.

HF94N017.CDR 11-7-94

heat of reaction values than sodium acetate were found to not exhibit propagating reactions (see Table 3-1). As such, inspection of Figure 3-7 clearly supports the selection of sodium acetate as a reasonable enveloping organic surrogate compound for investigating the organic-nitrate/nitrite tank waste energetics potential.

It follows that a safe but not overly conservative theoretical TOC envelope including the effect of moisture is given by the CTI condition [Inequality (2-15)] and using the relevant information for the sodium acetate system ($T_{ig} = 300\text{ }^{\circ}\text{C}$, $\bar{c} \approx 2000\text{ J/kg-K}$ and $\Delta H_c = 27.1\text{ MJ/kg}$ is the corresponding theoretical carbon reaction energy value).

$$\% \text{ TOC} > 4.5 + 17 x_w ; \quad x_w \leq 0.2 \quad (4-2)$$

Inequality (4-2) is compared to measured % TOC values in Figure 4-2.

For zero free moisture ($x_w = 0$), Inequality (4-2) predicts a lower bound value of 4.5% TOC for sustained propagation - this compares to the lowest measured value of about 6% TOC, i.e., the use of 4.5% TOC represents a margin of safety of about 33% which is well in excess of experimental measurement uncertainties ($< 5\%$). A further illustration of the margin of safety provided by Inequality (4-2) is provided in Table 4-1.

Table 4-1. Margin of Safety Provided By the Proposed Safety Criteria; % TOC > 4.5

Fuel	Formula	% TOC, LPL	% Margin of Safety
Acetic Acid	$\text{NaC}_2\text{H}_3\text{O}_2$	6 (Measured)	~33
Formic Acid	NaCHO_2	11 (380 cal/gm)	~144
Oxalic Acid	$\text{Na}_2\text{C}_2\text{O}_4$	230 cal/gm $<$ 290 cal/gm	No burn
Citric Acid ¹	$\text{Na}_3\text{C}_6\text{H}_5\text{O}_7$	8 (Measured)	~78
Hydroxyacetic Acid ¹	$\text{NaC}_2\text{H}_3\text{O}_3$	7.7 (380 cal/gm)	~71
EDTA ¹	$\text{Na}_4\text{C}_{10}\text{H}_{12}\text{O}_8\text{N}_2$	6 (380 cal/gm)	~33
HEDTA ¹	$\text{Na}_3\text{C}_{10}\text{H}_{15}\text{O}_7\text{N}_2$	6 (Measured)	~33
Tributyl Phosphate	$(\text{C}_4\text{H}_9)_3\text{PO}_4$	Decompose	No burn
Dibutyl Phosphate	$(\text{C}_4\text{H}_9)_2\text{HPO}_4$	Decompose	No burn
Na Dibutyl Phosphate	$\text{Na}(\text{C}_4\text{H}_9)_2\text{PO}_4$	Decompose	No burn
Al Dibutyl Phosphate	$\text{Al}[(\text{C}_4\text{H}_9)_2\text{PO}_4]_3$	Decompose	No burn

Note: ¹Disposed non-volatile organic chemicals in Hanford waste.

Figure 4-2. Comparison Between Measured TOC Values and the Proposed Safety Criteria, Inequality.

Note that the moisture content in case of Na Acetate may actually be bound rather than free water, as NaAc · 3H₂O is known to be stable below about 150 °C.

Again, a moisture concentration greater than 20 wt% will prevent combustion for all fuel-oxidizer concentrations. However, in contrast to the noted sludge behavior, moisture levels well below 20 wt% may be possible with salt cakes as a result of draining. As such, it is important to note that the non-volatile sodium salt organic complexants of concern appear to be highly soluble (Barney 1994) implying that drained salt cakes are therefore also largely lacking such fuels - the exception being the possibility of sodium oxalate ($\text{Na}_2\text{C}_2\text{O}_4$).

Since sodium oxalate is largely insoluble in the supernate solution, it could be present in the salt cake in the form of solids. In the absence of other organic compounds, the worst case scenario would be a stoichiometric condition (1 M $\text{Na}_2\text{C}_2\text{O}_4$ and 0.4 M NaNO_3). However, based upon our experiments such a condition would not sustain a propagation even in the complete absence of water. The theoretical energy release value for the stoichiometric mixture is 230 cal/gm (Burger 1993), which is well below the suggested energy threshold value of 380 cal/gm for sustained combustion as well as the recommended lower bound value of 290 cal/gm (see Table 4-1).

On the other hand, our measured solubilities of sodium citrate and NaHEDTA in initially saturated salt solutions listed in Table 4-2 are considerably larger than the highest measured TOC content in the Hanford supernatants of about 40 gm/liter (see Figure 7 of Barney 1994). It therefore seems reasonable to assume that no solid precipitates exist of these salts given that the initial interstitial supernate has not been dried out. However, assuming water removal by evaporation and filling up the porosity space (~40%) with completely dried-out supernate would clearly represent a rather extreme case. Assuming no other solid precipitates such as sodium oxalate, this translates to a salt cake TOC value of about 2 wt%. As indicated in Table 4-2, this value is well below the required TOC content for propagation for these salts and is also well below the proposed safety criteria value of 4.5% TOC.

Table 4-2. Measured Solubilities of Organic Complexants, TOC Measurements and Requirements for Propagation

Organic Salt	TOC Solubility gm/liter	Highest Supernate TOC Measurement gm/liter	Worst Case Salt Cake % TOC	Required for Propagation % TOC
Na Oxalate	~0 (0)	~40 (5)	Stoichiometric	Not Possible ¹
Na Citrate	~52.4 (7)	~40 (5)	~2	~8
NaHEDTA	~66 (8.3)	~40 (5)	~2	~6.0

Notes: Wt% dry basis reported in parentheses

¹0.96 MJ/kg (maximum energy release) < 1.6 MJ/kg (required for propagation).

Finally, the information summarized in Table 4-2 can be used to construct the worst case scenario by considering a completely dried-out salt cake consisting of 2 wt% soluble TOC and the remaining part a stoichiometric mixture of sodium oxalate and NaNO_3 (Column 4 in Table 4-2). This results in total available energy releases of approximately 1.2 and 1.3 MJ/kg of dry salt cake for sodium citrate and NaHEDTA, respectively, which are all less than the required value of about 1.6 MJ/kg for sustained combustion. It should be noted that the concentration of sodium oxalate in these cases are about 67 and 65 wt% for sodium citrate and NaHEDTA, respectively. Clearly such concentrations of sodium oxalate in the salt cakes would not appear to be credible.

In summary, given the solubilities of the various organic compounds discussed above, it would appear impossible to construct a credible completely dried-out salt cake scenario that would support combustion given a sufficient ignition source.

4.3 GENERALIZED SAFETY CRITERIA

Based on the CTI condition [Inequality (2-14)] and using the relevant data for sodium acetate as discussed in Section 3.0, the following theoretical safe energy threshold envelope is suggested

$$\Delta H_{\min} > 1.2 + 4.5 x_w ; \quad x_w \leq 0.2 \quad (4-3)$$

where the units of $\Delta H_{\min}$ is MJ/kg of reactant mixture. Inequality (4-3) is compared to the experimental data in Figure 3-7. It follows that any exothermic activities must exceed endothermic activities such as water evaporation by an amount at least equal to 1200 J/gm (~ 290 cal/gm) actual waste mixture.

Finally, we note that the CTI condition rules out propagation independent of fuel type and concentration when the moisture value in the sludge or salt cake exceeds a value of about 20%. Moisture values in excess of 20% result in the water/nitrate solution becoming the continuous phase (volume fraction > 0.4) implying that the contact temperature cannot exceed the boiling temperature ($\sim 130^\circ\text{C}$), which is well below the ignition temperature of about 250°C . This observation is consistent with the experimental data (see Table 3-2).

An estimate of the lower bound moisture content in organic containing salt cakes can be related to the relative humidity in the tank head space. For relative humidity values below 75%, our laboratory experiments show that the moisture level can be related to the amount of NaOH present. Above 75%, the equilibrium moisture can be related to $\text{NaNO}_3/\text{NaNO}_2$. Equilibrium values are provided in Figure 4-3.

As such, consider a Hanford site seasonal average relative humidity of 55%; the presence of about 7 wt% NaOH would result in an equilibrium moisture value of about 20%. It is also noted that a tank head space relative humidity in excess of 75% would assure an equilibrium moisture level at least equal to the wt% ($\text{NaNO}_3/\text{NaNO}_2$) present in the waste. Such a moisture level would again rule out self-propagation for all fuel-oxidizer combinations.

Figure 4-3. Relationship Between Water-NaOH and Water-NaNO₃ Equilibrium Solutions and Relative Humidities.

This page intentionally left blank.

5.0 NOMENCLATURE

A	integration constant
B	integration constant
C	integration constant
c	specific heat
$\bar{c}$	effective specific heat of reacting mixture and its products
D	integration constant
k	thermal conductivity of waste material
L	nonconvective waste height
m	node identification number
N	outermost node
q	constant and known step function chemical heating rate
$q_{\text{chem}}(T)$	chemical volumetric heating rate
Q	power density in hot spot
r	radial coordinate measured from center of hot spot
R_{HS}	radius of hot spot
R_{∞}	the outer radial boundary of the spatial domain for numerical calculation
t	time
t_1	characteristic adiabatic runaway time
t_c	characteristic cooling time of waste tank
t_{comb}	time to adiabatically consume fuel in reacting waste material
t_s	waste storage time

T	temperature
T_{ad}	adiabatic combustion temperature
T_{bp}	boiling point of interstitial water
T_i	contact or interface temperature between the reacted and unreacted waste
T_{ig}	ignition temperature of waste material
T_o	initial temperature of cold waste material
x	distance measured from reacted/unreacted material interface
x_f	fuel mass fraction
x_s	soluble salt mass fraction
x_w	moisture mass fraction
X	location of evaporation front

Greek Letters

α	thermal diffusivity of waste material
α_l	volume fraction of liquid in waste
β	evaporation constant
δ	node thickness
ΔH_{min}	lower bound theoretical chemical energy release
ΔH_R	heat of reaction per unit mass of fuel
ϵ	fraction of the total volume of waste material
λ	latent heat of evaporation of water
ρ	density
σ	$k/\alpha^{1/2}$ ratio (see Equation 2-6)
ϕ	mass fraction of fuel in dry reactive material

Subscripts

f	fuel
in	insoluble material
m	node number
r	reacted material
s	soluble salt
u	unreacted material
u,w	unreacted moist material
w	pertains to water

This page intentionally left blank.

6.0 REFERENCES

- Babad, H., and Turner, D. A., 1993, *Interim Criteria for Organic Watch List Tanks at the Hanford Site*, WHC-EP-0681, Westinghouse Hanford Company, Richland, Washington.
- Barney, G. S., 1994, *The Solubilities of Significant Organic Compounds in HLW Tank Supernate Solutions*, WHC-SA-2565-FP, Westinghouse Hanford Company, Richland, Washington.
- Beitel, G. A., 1976a, *Chemical Stability of Salt Cake in the Presence of Organic Materials*, ARH-LD-119, Atlantic Richfield Hanford Company, Richland, Washington.
- Beitel, G. A., 1976b, *Final Report on Investigation of Stability of Organic Materials in Salt Cake*, ARH-LD-126, Atlantic Richfield Hanford Company, Richland, Washington.
- Burger, L. L., 1993, *Calculation of Reaction Energies and Adiabatic Temperatures for Waste Tank Reactions*, PNL-8557, Battelle, Pacific Northwest Laboratories, Richland, Washington.
- Carslaw, H. S., and Jaeger, J. C., 1959, *Conduction of Heat in Solids*, 2nd ed., Oxford University Press, London.
- Creed, M. J., and Fauske, H. K., 1993, "An Easy, Inexpensive Approach to the DIERS Procedure," *Chemical Engineering Progress*, March.
- Dietz, P. W., 1979, "Effective Thermal Conductivity of Packed Beds," *Ind. Eng. Chem. Fundamentals*, vol. 18, pp. 283-286.
- Epstein, M., and Fauske, H. K., 1993, *Conditions for Reaction Propagation in Dried Ferrocyanide/Nitrate-Nitrite Powders*, WHC-SD-WM-TI-619, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Epstein, M., Fauske, H. K., Crippen, M. D., Dickinson, D. R., McCormack, J. D., Cash, R. J., Meacham, J. E., and Simmons, C. S., 1994, *Ferrocyanide Safety Program: An Assessment of the Possibility of Ferrocyanide Sludge Dryout*, WHC-EP-0816, Westinghouse Hanford Company, Richland, Washington.
- Epstein, M., 1995, *Contact Temperature Ignition Criterion for a Saturated Consolidating Sludge* (internal memo, March 22), Fauske & Associates, Inc., Burr Ridge, Illinois.

- Fauske, H. K., 1992, *Adiabatic Calorimetry and Reaction Propagation Tests with Synthetic Ferrocyanide Materials Including U Plant 1, U Plant 2, In Farm 1, In Farm 2 and Vendor-Procured Sodium Nickel Ferrocyanide*, WHC-SD-WM-RDT-054, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Fauske, H. K., 1995a, *Adiabatic Calorimetry and Tube Propagation Tests With Synthetic Ferrocyanide Materials*, FAI/94-93, Fauske & Associates, Inc., Burr Ridge, Illinois, to be issued.
- Fauske, H. K., 1995b, *Adiabatic Calorimetry and Tube Propagation Tests of Organic Waste Surrogate Materials*, FAI/94-87, Fauske & Associates, Inc., Burr Ridge, Illinois, to be issued.
- Fisher, F. D., 1990, *The Kyshtym Explosion and Explosion Hazards with Nitrate-Nitrite Bearing Wastes with Acetates and Organic Salts*, WHC-SD-CP-LB-033, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Gear, C. W., 1971, *Numerical Initial Value Problems in Ordinary Differential Equations*, Prentice Hall, Englewood Cliffs, New Jersey.
- Hindmarsh, A. C., 1972, *Linear Multistep Methods for Ordinary Differential Equations: Method Formulation, Stability, and the Methods of Nordsieck and Gear*, UCRL-51185, Ewc, 1, Lawrence Livermore National Laboratory, Livermore, California.
- Jeppson, D. W., and Wong, J. J., 1993, *Ferrocyanide Waste Simulant Characterization*, WHC-EP-0631, Westinghouse Hanford Company, Richland, Washington.
- Postma, A. K., Meacham, J. E., Barney, G. S., Borsheim, G. L., Cash, R. J., Crippen, M. D., Dickinson, D. R., Grigsby, J. M., Jeppson, D. W., Kummerer, M., McLaren, J. M., Simmons, C. S., and Simpson, B. C., 1994, *Ferrocyanide Safety Program: Safety Criteria for Ferrocyanide Watch List Tanks*, WHC-EP-0691, Westinghouse Hanford Company, Richland, Washington.
- Simpson, B. C., 1993, *Tank Characterization Report: Tank 241-C-109*, WHC-EP-0668, Westinghouse Hanford Company, Richland, Washington.

APPENDIX A
CTI CRITERION FOR A DRY REACTIVE POWDER

This page intentionally left blank.

APPENDIX A

CTI CRITERION FOR A DRY REACTIVE POWDER

Consider a highly exothermic material that occupies the infinite space $-\infty < x < \infty$. Suppose that somehow the temperature within the region $x < 0$ is raised uniformly to the material's ignition temperature T_{ig} , and as a result, the temperature within this region jumps essentially instantaneously to the adiabatic combustion temperature T_{ad} and all the reactants are consumed. The situation is illustrated in Figure A-1. The plane $x = 0$ now becomes a "contact plane" that separates the reacted region ($x < 0$) from the unreacted region ($x > 0$). If the combustion process in region $x < 0$ is not capable of raising the temperature T_i of the contact plane from the initial temperature T_o to the ignition temperature T_{ig} (see Figure A-1), the combustion process will not spread beyond $x < 0$.

The conduction problem that arises immediately following the combustion event within the domain $x < 0$ resembles the classical thermal contact problem that results from suddenly bringing together two semi-infinite slabs with different initial temperatures (Carslaw and Jaeger 1959). Specifically, the unreacted region $x > 0$ is one semi-infinite slab with thermal conductivity k_u , thermal diffusivity α_u , and initial temperature T_o ; while the reacted region $x < 0$ is the other semi-infinite slab with thermal conductivity k_r , thermal diffusivity α_r , and initial temperature T_{ad} . The boundary conditions at the plane of separation $x = 0$ are

$$T_u(0,t) = T_r(0,t) \quad (A-1)$$

$$k_u \frac{\partial T_u}{\partial x}(0,t) = k_r \frac{\partial T_r}{\partial x}(0,t) \quad (A-2)$$

where the temperature in the unreacted region is denoted by $x > 0$ by $T_u(x,t)$, and by $T_r(x,t)$ for the reacted region $x < 0$. Of course, the temperature profile in each of the two regions obeys a partial differential equation of the form

$$\frac{\partial^2 T}{\partial x^2} = \frac{1}{\alpha} \frac{\partial T}{\partial t} \quad (A-3)$$

and are subject to the following conditions as $|x|$ goes to infinity:

$$T_u(\infty,t) = T_o \quad (A-4)$$

$$T_r(-\infty,t) = T_{ad} \quad (A-5)$$

Figure A-1. Temperature Profile Some Time After Combustion Event in Domain $x < 0$. Temperature T_i at "Contact" Plane $x = 0$ Falls Below T_{ig} .

ME957007.CDR 7-24-95

The quantity α is the thermal diffusivity of the unreacted or reacted region (see below). As is usual in the solution of heat-conduction problems in semi-infinite regions, solutions are sought in the form of error functions:

$$T_u(x,t) = T_o + A \operatorname{erfc} \left[\frac{x}{2(\alpha_u t)^{1/2}} \right] \quad (\text{A-6})$$

$$T_r(x,t) = T_{ad} + B \operatorname{erfc} \left[- \frac{x}{2(\alpha_r t)^{1/2}} \right] \quad (\text{A-7})$$

where A and B are constants to be determined by imposing the boundary conditions. These functional forms already satisfy the differential equations of heat conduction [Equation (A-3)] and the boundary conditions [Equations (A-4) and (A-5)].

The symbols α_u and α_r in Equations (A-6) and (A-7) stand for the thermal diffusivity of the unreacted and reacted powder, respectively. If the heat capacity and mass of vapor or gas (void) present in the interstices of the solid component of the waste is ignored, we have

$$\alpha_u = \frac{k_u}{\rho_u \epsilon_u c_u} \quad (\text{A-8})$$

and

$$\alpha_r = \frac{k_r}{\rho_r \epsilon_r c_r} \quad (\text{A-9})$$

where ρ_u and ρ_r are the densities of the unreacted and reacted solid materials, respectively, c_u and c_r are the specific heats of the unreacted and reacted solid, respectively, and ϵ_u and ϵ_r are the fractions of the total volume (solid + void) occupied by the solid unreacted and reacted materials, respectively.

Substitution of the functions defined by Equations (A-6) and (A-7) in Equation (A-1) and (A-2), leads to two algebraic equations for the unknown constants A and B; namely,

$$\frac{k_u}{\alpha_u^{1/2}} A = - \frac{k_r}{\alpha_r^{1/2}} B \quad (\text{A-10})$$

$$T_o + A = T_{ad} + B \quad (\text{A-11})$$

Solving these equations for A and B and substituting the results into Equation (A-6) and (A-7) gives the desired temperature profiles

$$T_u(x,t) = T_o + \frac{1}{1 + \sigma} (T_{ad} - T_o) \operatorname{erfc} \left[\frac{x}{2(\alpha_u t)^{1/2}} \right] \quad (\text{A-12})$$

$$T_r(x,t) = T_{ad} - \frac{\sigma}{1 + \sigma} (T_{ad} - T_o) \operatorname{erfc} \left[-\frac{x}{2(\alpha_r t)^{1/2}} \right] \quad (\text{A-13})$$

where

$$\sigma = \frac{k_u}{k_r} \left(\frac{\alpha_r}{\alpha_u} \right)^{1/2} \quad (\text{A-14})$$

Evaluating Equations (A-12) or (A-13) at $x = 0$ yields the temperature T_i at the plane of separation of the reacted and unreacted regions, which is

$$\frac{T_i - T_o}{T_{ad} - T_o} = \frac{1}{1 + \sigma} \quad (\text{A-15})$$

The temperature at $x = 0$ reaches this value instantaneously, that is, as soon as the two regions contact one another. The quantity T_i is referred to here as the contact temperature. If the physical properties are the same for both regions ($k_u = k_r$, $\alpha_u = \alpha_r$), the contact temperature is simply the arithmetic mean of the adiabatic combustion temperature and the initial temperature, $T_i = (T_{ad} + T_o)/2$.

Armed with Equation (A-15), the problem can now be approached of predicting the onset of ignition or, equivalently, the existence of self-propagating reaction fronts from the reaction-free state. If thermal conditions for the reactive material are such that Equation (A-15) predicts a contact temperature T_i that is below the ignition temperature T_{ig} , then ignition or reaction propagation is thermally impossible. This situation is illustrated in Figure A-1. Thus, a necessary condition for propagation reactions in dried reactive material is $T_i \geq T_{ig}$, or from Equation (A-15),

$$T_{ig} \leq T_o + \frac{T_{ad} - T_o}{1 + \sigma} \quad (\text{A-16})$$

An alternative way of expressing this condition for a given T_{ig} is that the adiabatic combustion temperature must be high enough to satisfy the inequality

$$T_{ad} \geq (1 + \sigma)(T_{ig} - T_o) + T_o \quad (\text{A-17})$$

A similar contact temperature condition for reaction propagation in a wet reactive waste can now be obtained by deriving the expression for the contact temperature at a plane separating a hot reacted region from a wet unreacted region.

This page intentionally left blank.

APPENDIX B

CTI CRITERION FOR A MOIST REACTIVE POWDER

This page intentionally left blank.

APPENDIX B

CTI CRITERION FOR A MOIST REACTIVE POWDER

Consider the infinite composite region in which unreacted material u in the half-space $x > 0$ is initially cold, wet with water, and at temperature T_o ; and reacted material r in the half-space $x < 0$ is initially hot at the adiabatic combustion temperature T_{ad} . At time zero, a water evaporation front appears at the plane of separation $x = 0$ and moves in the positive x -direction into material u . The instantaneous thickness of the dry unreacted region (or, equivalently, the location of the evaporation front) is represented by $X(t)$, where t is time. We desire to calculate the interface (contact) temperature T_i that is established early in time at $x = 0$. For the short-time problem under consideration, it is permissible to ignore the influence of steam and water flow on the temperature profiles within the reacted and unreacted regions. In addition, all physical properties are assumed constant and known.

The temperature profile in each of the three regions must obey a partial differential equation given by Equation (A-3), where $T(x,t) = T_{u,w}(x,t)$ in the cold unreacted wet region $X(t) < x < \infty$, $T(x,t) = T_u(x,t)$ in the cold unreacted dry region $0 < x < X(t)$, and $T(x,t) = T_r(x,t)$ in the hot reacted region $-\infty < x < 0$. At the evaporation front $x = X(t)$, the following boundary conditions apply:

$$T_{u,w}(X,t) = T_u(X,t) = T_{bp} \quad (B-1)$$

$$k_{u,w} \frac{\partial T_{u,w}}{\partial x} - k_u \frac{\partial T_u}{\partial x} = \rho_w \epsilon_w \lambda \frac{dX}{dt} \quad \text{at } x = X(t) \quad (B-2)$$

Equation (B-1) demands that the temperature of the evaporation front is maintained at the boiling point temperature (T_{bp}) of water, while Equation (B-2) represents the absorption of latent heat λ at this front. In Equation (B-2), $k_{u,w}$ is the thermal conductivity of the wet region, ρ_w is the density of liquid water, and ϵ_w is the volume fraction of water in the unreacted wet region. The boundary conditions to be satisfied at $x = 0$ are represented by Equations (A-1) and (A-2). The boundary condition at $x = -\infty$ is given by Equation (A-5) and that at $x = \infty$ is

$$T_{u,w}(\infty,t) = T_o \quad (B-3)$$

Again, solutions are sought in the form of error functions:

$$T_u(x,t) = A + \text{Berf} \left[\frac{x}{2(\alpha_u t)^{1/2}} \right] \quad (B-4)$$

$$T_{u,w}(x,t) = T_o + \text{Cerfc} \left[\frac{x}{2(\alpha_{u,w} t)^{1/2}} \right] \quad (B-5)$$

$$T_r(x,t) = T_{ad} + \text{Derfc} \left[- \frac{x}{2(\alpha_r t)^{1/2}} \right] \quad (\text{B-6})$$

and, as usual in the solution of heat-conduction limited phase change problems, a square-root evaporation front versus time law is assumed:

$$X = 2\beta(\alpha_u t)^{1/2} \quad (\text{B-7})$$

where A, B, C, D and β are constants to be determined by satisfying the boundary conditions. Clearly, Equations (A-3), (A-5), and (B-3) are already satisfied. The thermal diffusivity of the unreacted wet region $\alpha_{u,w}$ that appears in Equation (B-5) is

$$\alpha_{u,w} = \frac{k_{u,w}}{\rho_u \epsilon_u c_u + \rho_w \epsilon_w c_w} \quad (\text{B-8})$$

where c_w is the specific heat of liquid water.

Substitution of Equations (B-4) to (B-6) in Equations (A-1), (A-2), (B-1), and (B-2) leads to a set of five algebraic equations for the unknown constants. These are

$$T_o + \text{Cerfc} [\beta(\alpha_u/\alpha_{u,w})^{1/2}] = T_{bp} \quad (\text{B-9})$$

$$A + \text{Berf}(\beta) = T_{bp} \quad (\text{B-10})$$

$$-k_{u,w} \frac{C}{\alpha_{u,w}^{1/2}} e^{-\beta^2 \alpha_u / \alpha_{u,w}} - k_u \frac{B}{\alpha_u^{1/2}} e^{-\beta^2} = \pi^{1/2} \rho_f \epsilon \lambda \alpha_u^{1/2} \beta \quad (\text{B-11})$$

$$A = T_{ad} + D \quad (\text{B-12})$$

$$\frac{k_r}{\alpha_r^{1/2}} \cdot D = \frac{k_u}{\alpha_u^{1/2}} \cdot B \quad (\text{B-13})$$

By suitable algebraic manipulation, this set of equations is reduced to the following transcendental equation for the "evaporation constant" β :

$$\frac{(T_{ad} - T_{bp}) e^{-\beta^2}}{\sigma + \operatorname{erf}(\beta)} - \frac{k_{u,w}}{k_u} \left(\frac{\alpha_u}{\alpha_{u,w}} \right)^{1/2} \cdot \frac{(T_{bp} - T_o)}{e^{\beta^2 \alpha_u / \alpha_{u,w}} \operatorname{erfc} [\beta (\alpha_u / \alpha_{u,w})^{1/2}]} = \pi^{1/2} \frac{\rho_w}{\rho_u} \cdot \frac{\epsilon_w \lambda}{c_u} \cdot \beta \quad (\text{B-14})$$

where c_u is the specific heat of the unreacted material and σ is defined by Equation (A-14). When Equation (B-14) has been solved for β , the temperature profiles can be obtained from Equations (B-4) to (B-6). For example, the temperature profile in the reacted region is

$$T_r(x,t) = T_{ad} - \frac{\sigma (T_{ad} - T_{bp})}{\sigma + \operatorname{erf}(\beta)} \operatorname{erfc} \left[- \frac{x}{2(\alpha_r t)^{1/2}} \right] \quad (\text{B-15})$$

From this equation, the temperature T_i at the plane of separation $x = 0$ is given by

$$\frac{T_{ad} - T_i}{T_{ad} - T_{bp}} = \frac{\sigma}{\operatorname{erf}(\beta) + \sigma} \quad (\text{B-16})$$

It can readily be shown that Equations (B-14) and (B-16) reduce to Equation (A-15) in the zero moisture limit $\epsilon_w \rightarrow 0$.

As discussed previously, T_i must be greater than or equal to T_{ig} in order to sustain a propagating reaction, and from Equation (B-16), the necessary condition for reaction propagation is

$$T_{ig} \leq T_{bp} + \frac{\operatorname{erf}(\beta)}{\operatorname{erf}(\beta) + \sigma} (T_{ad} - T_{bp}) \quad (\text{B-17})$$

where, again, β is determined by solving Equation (B-14). Note from Equation (B-14) that β is a function of T_{ad} and T_o .

Equation (B-17) is not easy to use because Equation (B-14) must first be solved numerically for β . An approximate but much simpler contact-temperature criterion can be developed from Equation (A-15) in the practical limit $\sigma \approx 1.0$. This is accomplished by subtracting the effective temperature difference taken up by evaporation of the water, namely, $x_w \lambda / c_w$, from the contact temperature T_i , to arrive at

$$T_i = \frac{1}{2} (T_{ad} - T_o) + T_o - \frac{x_w \lambda}{c_w} \quad (B-18)$$

In the above equation x_w is the water mass fraction (water mass divided by total mass); it is related to the water volume fraction ϵ_w in the unreacted zone by the expression

$$x_w = \frac{\rho_f \epsilon_w}{\rho_u \epsilon_u + \rho_f \epsilon_w} \quad (B-19)$$

From the contact-temperature criterion $T_i \geq T_{ig}$, the following approximate, necessary condition for reaction propagation in the presence of moisture is obtained:

$$T_{ad} \geq 2 \left(T_{ig} + \frac{x_w \lambda}{c_w} \right) - T_o \quad (B-20)$$

The above approximate solution is compared to the detailed numerical solutions in Appendix D and results in good agreement for moisture levels of interest ($x_w < 0.2$).

APPENDIX C

**MODEL OF HOT SPOT INITIATED REACTION
WAVE IN MOIST REACTIVE WASTE**

This page intentionally left blank.

APPENDIX C

MODEL OF HOT SPOT INITIATED REACTION WAVE IN MOIST REACTIVE WASTE

The purpose of the analytical work reported in this section is to compare the CTI criterion, the most basic form of which is given by Equation (B-20), with detailed numerical predictions of the conditions for ignition in moist reactive porous media (cake or powder). To accomplish this comparison, a specific igniter/reactor material configuration must be chosen. A postulated ignition mechanism that has generated considerable attention is the "hot spot mechanism". This mechanism requires that heat-generating material become highly-concentrated, and thereby sufficient to raise the temperature of some local region above the ignition temperature of the reactive waste material. While strong evidence has been presented for discounting the existence of hot spots (Epstein et al. 1994), the hot spot will be treated here as a means of evaluating the CTI criterion.

For purposes of mathematical tractability, a spherical hot spot form is assumed of radius R_{HS} and power density Q (in $W\ m^{-3}$). A spatial coordinator is introduced that is the radial distance measured from the center of the hot spot. Outside the hot spot, in the semi-infinite spherical region $R_{HS} < r < \infty$, the power density is very small compared with Q and it is neglected. Initially, moisture partially fills the interstices of the porous reactive waste and the initial water mass fraction is denoted by the symbol x_w . The initial temperature of the reactive waste is T_o . At time $t = 0$, the decay heat power density is turned on and the temperature of the medium begins to increase. The temperature at the center of the hot spot ultimately exceeds the boiling point T_{bp} of the interstitial water and an evaporation front appears at this location and begins to propagate outward. Figure C-1 illustrates the hot spot at a time when the temperature at the center is between the boiling point T_{bp} and the ignition temperature T_{ig} of the reactive medium. A central spherical region of dry reactive material is now apparent. If the hot spot power density Q is high enough to increase its center temperature to T_{ig} , a combustion front may be established within the dried zone and begin to propagate toward the spherical boundary of the surrounding moist region. An extinction of the combustion wave may occur once the wave reaches the wet zone. In the process of preheating and vaporizing the moisture, the temperature of the leading edge of the combustion front may drop below the ignition temperature so that the propagating reaction can no longer be sustained. It is worth mentioning here that the gradually heated hot spot problem represents a most stringent test of the CTI criterion; once combustion begins at the center of the hot spot, the initial temperature in the surrounding unreacted region is higher than the initial temperature T_o as assumed in the derivation of the criterion.

The analysis of the rate of propagation of the evaporation and combustion fronts is made with the assumption that the thermophysical properties of the materials involved in the reaction are independent of temperature. Note that the contact-temperature ignition criteria discussed in the previous sections are also based on the assumption of constant thermophysical properties. The thermal conductivities of the unreacted dry region k_u , the

Figure C-1. Model of Spherical Hot Spot in Initially Moist Reactive Medium Illustrating Temperature Profile and Location of Evaporation Front Before Ignition Occurs at Center of Hot Spot.

ME957009.CDR 8-1-95

unreacted wet region, $k_{u,w}$, and the reacted region, k_r , are taken to be equal to one another ($k_u = k_{u,w} = k_r = k$). The equality $k_{u,w} = k_u$ is based on the assumption that the moisture content within the wet region is sufficiently small so that it exerts little influence on the conductivity of the porous waste material. Finally, radiative and convective-heat losses from the combustion zone are ignored.

The numerical simulation of the moving evaporation and combustion fronts is carried out with the simplest of spatial finite difference procedures. The spatial domain $0 < r < R_\infty$ for numerical calculations is divided into concentric spherical shells (or "nodes") of thickness δ . These shells are considered to be perfect conductors. A contact thermal resistance k/δ is assigned to the spherical boundaries between shells.

Let N equal the total number of nodes so that $N\delta = R_\infty$. The temperature T_m of arbitrary node m is determined by the ordinary differential equation

$$\frac{dT_m}{dt} = \frac{1}{\rho_u \epsilon_u c_u + \rho_w \epsilon_{w,m} c_w} \cdot \left\{ \frac{3k}{\delta^2} \left[\frac{(m-1)^2 (T_{m-1} - T_m) - m^2 (T_m - T_{m+1})}{m^3 - (m-1)^3} \right] + q_{chem}(T_m) + Q \right\} \quad (C-1)$$

for $1 \leq m \leq N-1$. Note that in writing Equation (C-1) it was assumed that the volumetric heat capacity of the unreacted solid $\rho_u \epsilon_u c_u$ is constant and equal to that of the reacted solid $\rho_r \epsilon_r c_r$. Also note that for nodes outside the hot spot ($m > R_{HS}/\delta$), the hot spot power density Q is set equal to zero.

The quantity $q_{chem}(T_m)$ in Equation (C-1) is the chemical heat source (in $W\ m^{-3}$) in the reactive solid mixture. When the adiabatic combustion temperature exceeds about $800\ ^\circ C$, we assume a step function kinetic rate of the form

$$q_{chem}(T_m) = \begin{cases} 0 & ; \quad T_m < T_{ig} \\ q & ; \quad T_m \geq T_{ig} \end{cases} \quad (C-2)$$

In the above equation, q is a constant and known chemical heating rate per unit spatial volume. Measurements obtained via adiabatic RSST calorimetry (Fauske 1992) indicate that the self-heat rate histories of highly exothermic powder mixtures are reasonably well represented by Equation (C-2). At this stage, it is emphasized that Equation (C-2) is only valid for highly exothermic, reactive waste materials. During the course of the numerical calculation of T_m in each node, the total time that T_m remains above T_{ig} is tracked. When this accumulated reaction time exceeds the "combustion" time (t_{comb}) required for the reaction to consume all the fuel in node m , the chemical heat source is cut off. The combustion time

t_{comb} multiplied by the chemical heating rate equals the energy required to chemically and adiabatically heat the dry reactive medium from its initial temperature T_o to its adiabatic temperature T_{ad} . Thus,

$$t_{\text{comb}} = \frac{\rho_u \epsilon_u c_u (T_{\text{ad}} - T_o)}{q} \quad (\text{C-3})$$

Equation (C-3) may be regarded as our definition of the adiabatic combustion temperature for highly exothermic mixtures.

When the fuel concentration falls below a threshold value which corresponds to an adiabatic combustion temperature of about 800 °C, a reaction regime transition from step function kinetics [Equation (C-2)] to Arrhenius behavior takes place (Fauske 1992). The following zero-order kinetic law appears to be appropriate for this regime (Fauske 1992 or Epstein and Fauske 1993):

$$q_{\text{chem}}(T_m) = \begin{cases} 0 & ; T_m < T_{\text{ig}} \\ 8.6 \times 10^6 \rho_u c_u \epsilon_u \exp\left(-\frac{10^4}{T_m}\right) & ; T_m \geq T_{\text{ig}} \end{cases} \quad (\text{C-4})$$

where $\rho_u c_u \epsilon_u$ is in units of $\text{J m}^3 \text{s}^{-1}$ and T is in degrees Kelvin. In each node, the fuel fraction ϕ_m obeys the equation

$$\frac{d\phi_m}{dt} = - \frac{q_{\text{chem}}(T_m)}{\rho_u c_u \epsilon_u (T_{\text{ad}} - T_o)} \quad (\text{C-5})$$

and the chemical heat source is turned off at the instant ϕ_m is reduced to zero.

Equation (C-1) is solved when the temperature of node m is less than the boiling point of water ($T_m < T_{\text{bp}}$). When the boiling point of water is achieved, the temperature of the node is held constant at $T_m = T_{\text{bp}}$, and the rate at which water is evaporated is determined by the energy balance

$$\frac{d\epsilon_{w,m}}{dt} = - \frac{1}{\rho_w \lambda} \left\{ \frac{3k}{\delta^2} \left[\frac{(m-1)^2 (T_{m-1} - T_m) - m^2 (T_m - T_{m+1})}{m^3 - (m-1)^3} \right] + Q \right\} \quad (\text{C-6})$$

where $\epsilon_{w,m}$ is the instantaneous volume fraction of water in node m . When the evaporation process is complete, as denoted by the condition $\epsilon_{w,m} = 0$, the final stage of the node's self-heat process is calculated using Equation (C-1) where $\epsilon_{w,m} = 0$.

While the reactive medium is regarded as infinite, there is a physical limit to the number of nodes that can be used to represent the region. In all numerical simulations, the outermost node N was always sufficiently far from the center of the hot spot so that it remained unaffected by the thermal effects of the approaching evaporation or combustion fronts before the calculation was terminated. The initial conditions for Equations (C-1), (C-5) and (C-6) are

$$T_m = T_o, \quad \phi_m = 0, \quad \epsilon_{w,m} = \epsilon_w \quad \text{at} \quad t = 0 \quad (C-7)$$

where ϵ_w is the initial moisture volume fraction in the unreacted wet material. The wet material's moisture content is normally expressed in terms of mass fraction x_w rather than volume fraction ϵ_w [see Equation (B-19)].

In order to ensure an accurate numerical solution, the node size δ must be smaller than the thickness δ_c of a combustion wave. The combustion wave thickness can now be represented by the expression $\delta_c \approx \alpha_u/u_c$, where u_c is the velocity of the combustion wave. Since $\alpha_u \approx 10^{-7} \text{ m}^2 \text{ s}^{-1}$ and $u_c \approx 10^{-3} \text{ m s}^{-1}$ for highly exothermic mixtures, the node size should be less than $\delta_c \approx 10^{-4} \text{ m}$. The node thickness in all the calculations for highly exothermic mixtures ($T_{ad} > 800^\circ \text{C}$) did not exceed $5 \times 10^{-5} \text{ m}$. As shown in Appendix D, the Arrhenius reaction given by Equation (C-4) can "break away" from large hot spots and spread through the surrounding waste. The reaction spreading velocity u_c is approximately 10^{-4} m s^{-1} , and accordingly, the node size used was less than the approximate combustion wave thickness ($\delta_c \approx 10^{-3} \text{ m}$) when $T_{ad} < 800^\circ \text{C}$. The numerical approach employed here is not a pure numerical analysis in that the time derivatives in the system of N equations were not replaced, as represented in Equations (C-1) and (C-6) by differences. Instead, the system of ordinary differential equations was solved by an available subroutine. Specifically, numerical integration in the time "direction" was performed using a forward integration procedure based on the Gear (1971) method (see also Hindmarsh 1972).

This page intentionally left blank.

APPENDIX D

NUMERICAL EXAMPLE AND COMPARISON WITH CTI CRITERION FOR REACTION PROPAGATION

This page intentionally left blank.

APPENDIX D

NUMERICAL EXAMPLE AND COMPARISON WITH CTI CRITERION FOR REACTION PROPAGATION

As mentioned at the beginning of the previous section, the governing equations describe the spherically symmetric propagation of a drying front, and perhaps a reaction front, in an infinite medium composed of a moist, potentially reactive, porous solid mixture (fuel and oxidizer salt). The reaction, if it occurs, is initiated at the center of a postulated hot spot (at $r = 0$), where the temperature is gradually raised from the initial temperature T_0 to the ignition temperature T_{ig} . Since the ignition temperature is higher than the boiling point of water, a dry, inner, spherical region will be created before chemical reaction begins. This region is surrounded by a semi-infinite region of moist reactive powder (see Figure C-1). According to the contact-temperature criterion, a traveling reaction front may appear in the dry part of the spherical composite dry/wet system if the ignition temperature T_{ig} of the reactive medium obeys Equation (A-16) or Equation (B-17) in the limit $\epsilon_w = 0$. The traveling wave will penetrate the boundary of the surrounding moist region and propagate in the wet part of the system if T_{ig} satisfies Equation (B-17). A self-propagating reaction is predicted not to exist in the dry or wet region if the contact-temperature criterion is not satisfied in the limit $\epsilon_w = 0$. Wave extinction in the wet region is inferred if the contact-temperature condition is violated for the moisture content ϵ_w of interest. The predictions of the CTI criterion by comparison with numerically predicted reaction wave behavior can now be tested.

Values for the various physical parameters used in the calculations are given in Table D-1. We note from the table that the specific heat, density, and porosity of the unreacted material are assumed to be identical to those properties of the reacted material. The thermal conductivity of the dry reactive medium is taken to be similar to that of sodium chloride (NaCl) powder and interstitial air. The estimate in Table D-1 is based on a solid NaCl thermal conductivity of $3.2 \text{ W m}^{-1} \text{ K}^{-1}$ (International Critical Tables) and the correlation of Dietz (1979) for the effective thermal conductivity of packed beds. The thermal conductivity $k_{u,w}$ of a moist reactive medium is assumed to be equal to the dry medium value for reasons mentioned previously. The density of the solid component is based on the room temperature value for sodium nitrate salt, which is a major solid component of reactive sludge mixtures. The specific heat of the solid component corresponds to the sodium nitrate salt at its melting temperature. The volume fraction of the dry reactive medium is based on a porosity value of 0.7 reported for ferrocyanide sludge (Jeppson and Wong 1993). The ignition temperature and step function heating rate are inferred from the results of adiabatic calorimetry experiments with In-Farm synthetic waste materials (Fauske 1992).

Table D-1. Parameter Values Used in the Numerical Reaction Wave Simulations

Thermal Conductivity of Reactive Medium	$k = k_u = k_r = k_{u,w} = 0.2 \text{ W m}^{-1} \text{ K}^{-1}$
Density of Reactive Medium	$\rho_u = \rho_r = 2.3 \times 10^3 \text{ kg m}^{-3}$
Specific Heat of Reactive Medium	$c_u = c_r = 1.83 \times 10^3 \text{ J kg}^{-1} \text{ K}^{-1}$
Density of Water	$\rho_w = 10^3 \text{ kg m}^{-3}$
Specific Heat of Water	$c_w = 4.2 \times 10^3 \text{ J kg}^{-1} \text{ K}^{-1}$
Volume Fraction of Dry Reactive Medium	$\epsilon_u = \epsilon_r = 0.3$
Ignition Temperature of Reactive Medium	$T_{ig} = 260 \text{ }^\circ\text{C} (533 \text{ K})$
Initial Temperature of Reactive Medium	$T_o = 47 \text{ }^\circ\text{C} (320 \text{ K})$
Boiling Point of Water	$T_{bp} = 100 \text{ }^\circ\text{C} (373 \text{ K})$
Heat of Evaporation of Water	$\lambda = 2.2 \times 10^6 \text{ J kg}^{-1}$
Step Function Chemical Heating Rate	$q = 1.52 \times 10^9 \text{ J m}^{-3} \text{ s}^{-1}$

Equations (B-14) and (B-17), together with the ignition temperature value $T_{ig} = 260 \text{ }^\circ\text{C}$, were used to construct the $T_{ad} - x_w$ locus for incipient reaction zone propagation, with the results shown by the continuous curve in Figure D-1. The approximate closed form CTI criterion, Equation (B-20), is also shown in Figure D-1 as the dotted line for moisture levels of practical interest (see below), and it is in excellent agreement with the numerical results obtained from the more complex algebraic formulation given by Equations (B-14) and (B-17). According to the contact-temperature criterion, self-sustained reaction wave propagation is possible only for T_{ad} , x_w points that lie above these curves. This predicted boundary for reaction propagation was then tested by performing numerical reaction wave calculations for several T_{ad} , x_w points. Step function reaction kinetics, represented by Equation (C-2), was employed when $T_{ad} \geq 800 \text{ }^\circ\text{C}$, whereas Arrhenius kinetics, Equation (C-4) was used when $T_{ad} < 800 \text{ }^\circ\text{C}$. Three different hot spot diameters ($2R_{HS}$) were chosen: 2, 10, and 100 mm. The corresponding hot spot power densities Q were 10^8 , 4×10^6 , and $4 \times 10^4 \text{ W m}^{-3}$. In the absence of chemical heating, these power densities are capable of gradually raising the temperature of the center of the hot spot to about $300 \text{ }^\circ\text{C}$, which is roughly $40 \text{ }^\circ\text{C}$ above the ignition temperature.

Figure D-2 displays the temperature profile-time history for $x_w = 0.3$ and $T_{ad} = 1005 \text{ }^\circ\text{C}$. The hot spot power density is $Q = 10^8 \text{ W m}^{-3}$ and the hot spot radius $R_{HS} = 1.0 \text{ mm}$. The combination $x_w = 0.3$ and $T_{ad} = 1005 \text{ }^\circ\text{C}$, when plotted in Figure D-1, lies well above the CTI criterion curve in Figure D-1 and indeed, as can be seen from Figure D-2, the exothermic reaction generates enough heat to be self-sustaining in both the dry and wet regions of the reactive medium. Figure D-3 shows different behavior by retaining the

Figure D-1. Adiabatic Combustion Temperature Versus Water Mass Fraction Curve Separating the Reaction Extinction Region From the Reaction Propagation Region as Determined by the Contact-Temperature Criterion [Equations (B-14) and (B-16)] and $T_{ig} = 260^\circ\text{C}$.

Figure D-2. Temperature Profile History Produced by 2.0-mm Diameter Hot Spot Generating $10^8 \text{ W m}^{-3} \text{ s}^{-1}$, Indicating Ignition and Sustained Wave Propagation in the Wet Region Containing 30 wt% Water.

Figure D-3. Temperature Profile History Produced by 2.0-mm Diameter Hot Spot Generating $10^8 \text{ W m}^{-3} \text{ s}^{-1}$, Indicating Ignition and Reaction Wave Extinction in the Wet Region Containing 30 wt% Water.

Moisture Content $x_w = 0.3$, but decreasing the adiabatic combustion temperature from $T_{ad} = 1005^\circ\text{C}$ to 1000°C . The x_w, T_{ad} combination still lies well above the reaction propagation boundary of Figure D-1. In this case, however, a permanent extinction process occurs once the wave reaches the wet zone, indicating that the contact-temperature criterion for reaction propagation is a rather conservative criterion for this case. Additional reaction-wave calculations were performed for x_w values in the range 0-0.4 and the results are summarized in Figure D-1. The dark circles in Figure D-1 refer to a sustained propagating reaction regime and the open circles indicate extinction. The numbers next to the numerical data points in Figure D-1 convey the diameter of the hot spot in millimeters. Note that in the Arrhenius reaction regime ($T_{ad} < 800^\circ\text{C}$) only the 100-mm diameter hot spot can initiate a spreading reaction zone, whereas small hot spots can produce reaction waves in highly exothermic waste ($T_{ad} \geq 800^\circ\text{C}$).

It can be seen from Figure D-1 that the CTI criterion represents the lower boundary of the propagating reaction regime for all but one of the cases investigated. The criterion fails when the hot spot size is 100 mm in diameter and the moisture concentration is below 5 wt %. Our concern about this violation of the CTI criterion is tempered by the knowledge that in low-moisture-content waste (i.e., unsaturated waste) there is no convective mechanism for concentrating the radionuclides in a hot spot⁶. Thus, the spreading reaction associated with the numerical data point $x_w = 0, T_{ad} = 450^\circ\text{C}$ in Figure D-1 can only be achieved by the application of a dedicated heat source (igniter) which gradually heats a 100 mm diameter region of dry waste from its initial temperature of 47°C to its ignition temperature of 260°C . Because of heat leakage into the surrounding waste, it takes the assigned power density of $Q = 4 \times 10^4 \text{ W m}^{-3}$ about $1.2 \times 10^5 \text{ sec}$ to accomplish this temperature rise. The corresponding required igniter energy is a rather incredible 2.5 MJ. One may argue that less energy would be required if the applied heat flux generated by the igniter were large enough to rapidly heat the waste region to its ignition temperature without incurring significant heat loss to the surroundings. Recall, however, that the CTI criterion is based on a rapid waste-heating mode and, indeed, extinction is predicted following the instantaneous heating of the 100-mm diameter region to its ignition temperature unless the fuel content is such that $T_{ad} > 550^\circ\text{C}$ or, equivalently, unless the CTI criterion is satisfied (see diamond-shaped data points along $x_w = 0$ in Figure D-1).

One additional point relative to Figure D-1 that is worthy of discussion has to do with the actual morphology of moist reactive waste (powder). In the calculations summarized in Figure D-1, the moisture mass fraction was allowed to range between 0 and 0.5. The reason

⁶Hot spots can not result in local dryout in water saturated waste because of the tenacity with which the sludge precipitate particles "hold" the water (Epstein et al. 1994).

for this is that the predicted mass fraction of water required for saturation (no voids) in the sample problem waste powder is

$$x_w = \frac{1}{1 + \frac{\rho_u}{\rho_f} \left(\frac{\epsilon_u}{1 - \epsilon_u} \right)} = 0.504 \quad (D-2)$$

In actual precipitate waste powders, however, the saturated state is achieved at a much lower value of $x_w \approx 0.2$ due to strong electrostatic forces established between the precipitate waste particles and water. A large portion of the $T_{ad} - x_w$ parameter space in Figure D-1 is, therefore, nonphysical. This means that even the predicted ignition conditions for $x_w = 0.25$ and 0.3 are not correct even though $T_{ad} > 800$ °C. This is because at these moisture concentration levels, water completely fills the interstices of the waste powder. Much higher adiabatic combustion temperatures would be required to sustain reaction wave propagation into the wet region surrounding the hot spot. In order to treat water saturated wastes, the physical model presented here would have to be revised to account for the flow of interstitial liquid toward the reaction front through a zone of waste consolidation and through a zone of capillary flow just ahead of the reaction front. Preliminary theoretical work (Epstein 1995) suggests that the process of waste consolidation alone would result in adiabatic combustion temperatures required for reaction propagation that are more than a factor of two higher than those predicted by assuming an unsaturated reactive waste morphology.

In summary, it may be said that the CTI criterion provides a conservative and simple means of predicting the conditions for reaction propagation in waste powders under ignition conditions of practical interest. The criterion underpredicts the adiabatic combustion temperature required for propagation at low moisture concentration levels ($x_w < 0.2$) because of the relatively slow Arrhenius-type reaction kinetics that dominates this regime. The CTI criterion is very conservative and, perhaps, unnecessary at high moisture contents because of the tenacity with which water is held within the sludge solid precipitate structure.

This page intentionally left blank.

DISTRIBUTION

Number of copies

OFFSITE

7

U.S. Department of Energy
EM-36, Trevion II
12800 Middlebrook Road
Germantown, MD 20874

James V. Antizzo, EM-36
Charles O'Dell, EM-36 (5)

U. S. Department of Energy
Forrestal Building
1000 Independence Avenue SW
Washington, DC 20585

Shirley Campbell, EH-71

1

U.S. Department of Energy
656 Quince Diamond Road
Room 235, EM-20.1
Gaithersburg, MD 20879

Cynthia Hilland

1

U.S. Department of Energy
Savannah River Operations Office
P.O. Box A
Aiken, SC 29808

Thomas C. Temple

1

Charles S. Abrams
1987 Virginia
Idaho Falls, ID 83404

1

David O. Campbell
102 Windham Road
Oak Ridge, TN 37830

DISTRIBUTION (Continued)

Number of copies

OFFSITE

1	Fred N. Carlson 6965 North 5th West Idaho Falls, ID 83401
1	Billy C. Hudson 202 Northridge Court Lindsborg, KA 67456
1	Thomas S. Kress 102-B Newridge Road Oak Ridge, TN 37839
1	William R. Prindle 1556 Crestline Drive Santa Barbara, CA 93105
1	Alfred Schneider 5005 Hidden Branches Drive Dunwoody, GA 30338
1	<u>Air Products & Chemicals, Inc.</u> 7201 Hamilton Blvd Allentown, PA 18195-1501
	George E. Schmauch
1	<u>Brookhaven National Laboratory</u> Upton, NY 11973
	Kamal K. Bandyopadhyay
1	<u>Design Science, Inc.</u> 163 Witherow Road Sewickley, PA 15143
	Gary Powers

DISTRIBUTION (Continued)

Number of copies

OFFSITE

2

Fauske and Associates, Inc.
16W070 W. 83rd St.
Burr Ridge, IL 60521

Michael Epstein
Hans K. Fauske

1

Florida State University
Department of Chemistry B-164
Tallahassee, FL 32306

Greg R. Choppin

2

G & P Consulting, Inc.
3640 Ballard Road
Dallas, OR 97338

J. Michael Grigsby
Arlin K. Postma

1

Harvard University
295 Upland Avenue
Newton Highlands, MA 02161

Melvin W. First

1

Hazards Research Corporation
200 Valley Road, Suite 301
Mt. Arlington, NJ 07856

Chester Grelecki

2

Los Alamos National Laboratory
P.O. Box 1663
Los Alamos, NM 87545

Steve F. Agnew
Thomas E. Larson

DISTRIBUTION (Continued)

Number of copies

OFFSITE

1

MIT/Department of Nuclear Engineering
77 Massachusetts Ave.
Room 24-102
Cambridge, MA 02139

Mujid S. Kazimi

1

Nuclear Consulting Services, Inc.
P.O. Box 29151
Columbus, OH 43229-0151

J. Louis Kovach

Oak Ridge National Laboratory

1

Emory D. Collins
P.O. Box 2008
7930, MS-6385
Oak Ridge, TN 37831-6385

1

Charles W. Forsberg
P.O. Box 2008
MS-6495
Oak Ridge, TN 37831-6495

1

Rice University
5211 Paisley
Houston, TX 77096

Andrew S. Veletsos

2

Sandia National Laboratories
P.O. Box 5800
Albuquerque, NM 87185

Dana A. Powers, MS-0744
Scott E. Slezak, MS-0741

DISTRIBUTION (Continued)

Number of copies

OFFSITE

3	<u>Science Applications International Corporation</u> 20300 Century Blvd, Suite 200-B Germantown, MD 20874 Ray S. Daniels (3) <u>State of Washington - Department of Ecology</u>
1	Michael T. Gordon P. O. Box 47600 Olympia, WA 98504-7600
1	Alex Stone 1315 W. 4th Avenue Kennewick, WA 99336
1	<u>University of South Carolina</u> Department of Electrical and Computer Engineering Swearingen Engineering Center Columbia, SC 29208 Joseph S. Byrd
1	<u>University of Washington</u> Center for Process Analytical Chemistry Chemistry Department BG-10 Seattle, WA 98195 Bruce R. Kowalski
1	<u>Vanderbilt University</u> P.O. Box 1596, Station B Nashville, TN 37235 Frank L. Parker

DISTRIBUTION (Continued)
Number of copiesOFFSITE

1

Waste Policy Institute
 555 Quince Orchard Road, Suite 600
 Gaithersburg, MD 20878-1437

Donald T. Oakley

ONSITE

10

U.S. Department of Energy
Richland Operations Office

R. E. Gerton	S7-54
R. G. Harwood	S7-54
W. F. Hendrickson	S7-54
D. H. Irby (2)	S7-54
M. F. Jarvis	S7-54
A. G. Krasopoulos	A4-81
Public Reading Room	H2-53
RL Docket File (2)	B1-17

7

Pacific Northwest Laboratory

S. A. Bryan	P7-25
R. T. Hallen	P8-38
M. A. Lilga	P8-38
R. D. Scheele	P7-25
C. S. Simmons	K6-77
C. W. Stewart	K7-15
Hanford Technical Library	P8-55

37

Westinghouse Hanford Company

H. Babad	S7-30
J. B. Billetdeaux	S7-16
D. C. Board	T4-08
W. S. Callaway	S3-90
R. J. Cash (5)	S7-15
M. D. Crippen	L5-31

DISTRIBUTION (Continued)Westinghouse Hanford Company (Continued)

R. D. Crowe	H0-38
D. R. Dickinson	L5-31
G. T. Dukelow	S7-15
M. N. Islam	R3-08
D. W. Jeppson	L5-31
N. W. Kirch	R2-11
C. A. Kuhlman	B3-30
E. J. Lipke	S7-14
L. L. Lockrem	S3-90
J. M. McLaren	H0-34
J. E. Meacham (2)	S7-15
N. J. Milliken	H4-62
S. R. Moreno	B3-06
T. V. Rebagay	T6-30
F. R. Reich	L5-63
E. F. Riedel	S3-90
B. C. Simpson	R2-12
H. Toffer	H0-38
W. T. Watson	H0-38
W. D. Winkelman	L5-55
W. D. Wittekind	H0-38
Central Files	A3-88
EDMC	H6-08

This page intentionally left blank.