sta 4③

AUG 07 1997

ENGINEERING DATA TRANSMITTAL

Page 1 of 1
1. EDT 621264

2. To: (Receiving Organization) DISTRIBUTION	3. From: (Originating Organization) SPECIAL ANALYTICAL SUPPORT 8C530	4. Related EDT No.: N/A
5. Proj./Prog./Dept./Div.: VAPOR/AS/SPECIAL/ANALYTICAL/ SUPPORT	6. Design Authority/ Design Agent/Cog. Engr.: RICKY MAHON 3-7437	7. Purchase Order No.: N/A
8. Originator Remarks: SST-241-B-202. SAMPLING USING THE VAPOR SAMPLING SYSTEM		9. Equip./Component No.: N/A
		10. System/Bldg./Facility: 622G
11. Receiver Remarks: 11A. Design Baseline Document? ☐ Yes ☒ No		12. Major Assm. Dwg. No.: N/A
		13. Permit/Permit Application No.: N/A
		14. Required Response Date:

15. DATA TRANSMITTED					(F)	(G)	(H)	(I)
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	Approval Designator	Reason for Transmittal	Originator Disposition	Receiver Disposition
1	HNF-SD-WM-RPT-256		0	VAPOR AND GAS SAMPLING OF SST-241-B-202	Q	2		
16. KEY								
Approval Designator (F)		Reason for Transmittal (G)			Disposition (H) & (I)			
E, S, Q, D or N/A (see WHC-CM-3, Sec.12.7)		1. Approval 2. Release 3. Information 4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)			1. Approved 2. Approved w/comment 3. Disapproved w/comment 4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged			
17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)								
(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN	(G) Reason	(H) Disp.	(J) Name
		Design Authority						
		Design Agent						
2	1	Cog. Eng. R.D. Mahon	<i>R.D. Mahon</i>	7/30/97				
2	1	Cog. Mgr. L.L. Lockrem	<i>L.L. Lockrem</i>	7/12/97				
2	1	QA Mike Barnes	<i>Mike Barnes</i>					
		Safety						
		Env.						
18. <i>Glen S. Caprio</i> Signature of EDT Originator			19. <i>Glen S. Caprio</i> Authorized Representative Date for Receiving Organization			20. <i>L.L. Lockrem</i> Design Authority/ Cognizant Manager		
Date: <i>7/30/97</i>			Date: <i>7/12/97</i>			21. DOE APPROVAL (if required) Ctrl. No. ☐ Approved ☐ Approved w/comments ☐ Disapproved w/comments		

VAPOR AND GAS SAMPLING OF SINGLE-SHELL TANK 241-B-202 USING the in Situ Vapor Sampling System

G.S. Caprio

SGN Eurisys Services Company, Richland, WA 99352

U.S. Department of Energy Contract DE-AC06-96RL13200

EDT/ECN: 621264

UC: 2070

Org Code: 8C530

Charge Code: E62000

B&R Code: EW3120074

Total Pages: 30

Key Words: 241-B-202, ISVS, SUMMA™, TST, SORBENT, TANK

Abstract: THIS DOCUMENT PRESENTS SAMPLING DATA RESULTING FROM THE JULY 18, 1996 SAMPLING OF SST 241-B-202

SUMMA is a trademark of Molectrics, Inc.

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: Document Control Services, P.O. Box 950, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

Release Approval

Date

Approved for Public Release

APPROVALS

Document title: Vapor and Gas Sampling of Single-Shell Tank 241-B-202
Using the In Situ Vapor Sampling System

Approved by:

G. S. Caprio, Field Scientist
Vapor Sampling Project
Special Analytical Studies

Date

Approved by:

R. D. Mahon, Project Lead
Vapor Sampling Project
Special Analytical Studies

Date

Approved by:

L. L. Lockrem, Manager
Special Analytical Studies

7/11/97

Date

CONTENTS

1.0	SCOPE	1
2.0	SAMPLING EQUIPMENT DESCRIPTION	1
2.1	IN SITU VAPOR SAMPLING SYSTEM	1
3.0	SAMPLING EVENT DESCRIPTION	2
3.1	SPECIFICATIONS	2
3.2	OPERATIONS AND SAMPLING PERSONNEL	2
3.3	INDUSTRIAL HYGIENE FIELD RESULTS	2
3.4	AMBIENT CONDITIONS	3
3.5	SAMPLE COLLECTION	3
3.6	RADIATION SCREENING	3
4.0	SAMPLE CHAIN OF CUSTODY: RECEIPT, STORAGE, AND SHIPMENT	4
5.0	QUALITY ASSURANCE AND CONTROLS	4
5.1	CLEANLINESS OF SYSTEM	4
5.2	INSTRUMENT CALIBRATION	5
5.3	BLANK SAMPLES	6
6.0	ANOMALIES	6
7.0	REFERENCES	7

APPENDICES

SAMPLE LOG SHEETS	A-1
AMBIENT CONDITIONS	B-1
CHAIN-OF-CUSTODY FORMS	C-1

LIST OF TABLES

1. Radionuclide Analysis Results	4
2. Calibration Data	5
3. Totalizer Calibration Data	6

LIST OF TERMS

CGI	Combustible Gas Indicator
COC	Chain Of Custody
DOT	U.S. Department of Transportation
GEA	Gamma Energy Analysis
ISVS	In Situ Vapor Sampling System
NH ₃	Ammonia
H ₂ O	Water Vapor
OPC	Offsite Property Control
OVN	Organic Vapor Meter
PNNL	Pacific Northwest National Laboratory
SAS	Special Analytical Studies
SHA	Sample Head Assembly
SML	Sampling and Mobile Laboratories
SST	Single-Shell Tank
TCP	Tank Characterization Plan
TOC	Total Organic Carbon
TST	Triple Sorbent Trap
VT	Vapor Team, personnel from Sampling and Mobile Laboratories and Special Analytical Studies
WHC	Westinghouse Hanford Company

This page intentionally left blank.

VAPOR AND GAS SAMPLING OF SINGLE-SHELL TANK 241-B-202 USING THE IN SITU VAPOR SAMPLING SYSTEM

1.0 SCOPE

The Vapor Issue Resolution Program tasked the Vapor Team (VT) to collect representative headspace samples from Hanford Site single-shell tank (SST) 241-B-202. This document presents In Situ Vapor Sampling System (ISVS) data resulting from the July 18, 1996 sampling of SST 241-B-202. Analytical results will be presented in separate reports issued by the Pacific Northwest National Laboratory (PNNL) which supplied and analyzed the sample media.

2.0 SAMPLING EQUIPMENT DESCRIPTION

2.1 IN SITU VAPOR SAMPLING SYSTEM

The VT, consisting of Sampling and Mobile Laboratories (SML) and Special Analytical Studies (SAS) personnel, used the ISVS to collect representative samples of the air, gases, and vapors from the headspace of SST 241-B-202 on July 18, 1996. WHC-SD-WM-SDD-068 Rev. 0, *System Design Description for the In Situ Vapor Sampling System* (Blanchard 1996a) describes, in detail the ISVS performance, its characteristics, and its operation.

In situ sampling is a method designed to collect vapor samples of the homogeneous headspace of waste tanks. Sample media, consisting of sorbent traps and radiological filters, are lowered into the tank headspace. Tank gases are drawn through the media by means of the ISVS manifold, which measure the volume of gas drawn through the system. The sample media are collected together in a sample head assembly (SHA). The SHA provides for twelve sorbent or triple sorbent trap (TST) samples (single sample each) to be sampled in sets of four, one SUMMA[™] sampling line, and one line for radiological filtration.

The SHA is protected from external contamination and breakage by a transparent plastic tube. The plastic tube is cut, formed, and connected to the SHA. The plastic tube also prevents any part of the SHA from accidentally falling into the tank.

A set of 1/4 or 5/16 inch diameter flexible tubes, approximately 50 feet long, are held together with spiral wrap to form a "tube bundle", which connects the ISVS to the SHA. The tube bundle and SHA are assembled prior to sampling and are referred to as the "sample assembly".

Sorbent traps are pencil-size stainless steel or glass tubes that contain vapor-adsorbing media. The sorbent traps may be used singly or may be prepared with several individual traps joined in series (a sorbent train). A known amount of sample vapor is passed through the tube, which traps (by adsorption) virtually all the target analytes. The concentration of analytes in the vapor sampled is calculated from the quantity of analyte found in the sorbent media and the volume of vapor passed through the sorbent trap. In addition to the sorbent traps, SUMMA[™] canisters are also used to collect samples.

SUMMA[™] canisters are stainless steel vessels with internal surfaces that have been prepared by the SUMMA[™] process, which passivates active sites on the canister walls to minimize adsorption of gases and vapors. An analytical laboratory must clean and evacuate SUMMA[™] canisters before each use. The

evacuated canister is filled with sample vapor through a valve, which is then closed to seal the sample inside. SUMMA[®] canisters allow collection and transfer of whole-air samples from location to an analytical laboratory where the sample is analyzed. The standard capacity of each SUMMA[®] canister is 6 liters.

The ISVS consists of five sample stations, (four for sorbent trap sampling and one for SUMMA[®] sampling) terminating in 1/4 inch outside diameter stainless steel tubing. Each sorbent sample station is independently operable at the selected flow rate, from 50 to 500 standard cubic centimeters per minute (scm).

The system is a portable sampling system. It is designed to allow setup and preparation to be performed outside of the tank farm, with a minimum number of steps to be performed inside the farm. It operates on 110V AC power. The ISVS was designed to meet the requirements of National Fire Protection Association 70 - 1993 (the National Electrical Code) for general industrial use. Before the ISVS can be used in any tank, procedures require a flammability check of the waste tank which shows that concentrations of flammable materials are well below lower flammability limits.

Tank gases passing through the ISVS will either pass through a sorbent trap and then a backup line dryer, or through the on-board activated charcoal/drierite cartridge. A check valve is installed in the system to prevent any possibility of siphoning materials into the waste tanks.

3.0 SAMPLING EVENT DESCRIPTION

3.1 SPECIFICATIONS

The Vapor Issue Resolution Program specifies sampling requirements in WHC-SD-WM-TP-335 Rev. 2A, *Vapor Sampling and Analysis Plan* (Buckley 1996b). The Sampling and Analysis Plan also specifies the types and number of samples to be collected, flow rates, and durations. These key sampling parameters are summarized on the sample log sheets in Appendix A. In addition to the sample log sheets, check sheets for each individual sample help ensure correct sampling procedures. The VT retains these documents in the project file. The project specific number for this sampling event is S6-073.

3.2 OPERATIONS AND SAMPLING PERSONNEL

Steve Carter was the Tank Farm Operations person-in-charge. The VT members included:

G. S. Caprio, Field Scientist
R. D. Mahon, Lead Scientist

The ISVS was set up at SST 241-B-202 on July 18, 1996 and was allowed to warm up for approximately 15 minutes. Sampling began at approximately 1015 on July 18, 1996, and was completed by 1140 the same day.

3.3 INDUSTRIAL HYGIENE FIELD RESULTS

Prior to inserting the tube bundle into SST 241-B-202, an industrial hygiene technician field tested tank vapors. The technician purged the instrument with tank gas for 5 minutes and then field measured vapor stream contents using a combustible gas indicator (CGI) and an organic vapor meter (OVM). The technician measured the tank vapors at the breather filter, three feet down

the riser, and twenty feet down the riser. The measurements reported at the breather filter: LEL 0%, NH_3 5 ppm, O_2 20.9%, and TOC 0 ppm. The measurements approximately three feet down were: LEL 0%, NH_3 5 ppm, O_2 20.9%, and TOC 1 ppm. The measurements approximately twenty feet down were: LEL 0%, NH_3 5 ppm, and TOC 1.8 ppm.

3.4 AMBIENT CONDITIONS

The weather the day of the sampling event, July 18, 1996, was sunny with some clouds and a light wind, 1-5 mph from the northwest. Graphs of ambient temperatures and pressures taken at the Hanford Meteorological Station, which is about 5.5 miles west of B-Farm, are provided in Appendix B.

3.5 SAMPLE COLLECTION

One analytical laboratory provided sample media. PNNL provided SUMMA[™] canisters, sorbent traps for organic vapors, ammonia (NH_3), NO_x , and water vapor (H_2O).

The VT began inserting the sample media into the SHA at 1215 on July 17, 1996, and finished at approximately 1320. The SHA was connected to tube bundle 14E. The top collar used in this event is described in ECN # 634005. The sample assembly was transported to 241-B-202 on July 18, 1996, and connected to ISVS #1 for the sampling event.

Prior to sample collection, a leak check of the ISVS sampling manifold and transfer tubing was performed. Pressure gauge readings were recorded at the beginning of the leak check. The gauge readings were used for the leak check calculations but for report purposes will be converted to absolute pressure. The system was evacuated to approximately 118.5 mbar (3.5 inHg) and leakage of ambient air into the system was observed by monitoring system pressure for 5 minutes. Leakage resulted in an increase of 0 mbar (0 inHg) in system pressure during the 5 minute test.

The tank flange was opened and the tube bundle was lowered 6.1 meters (20 feet). Tank vapor was drawn through each TST, sorbent, and SUMMA[™] line for a specified period of time. Appendix A indicates the exact times and volumes of tank gas that was drawn through each sample.

After the final sample was collected, the sample assembly was removed from the tank. Following the HPT survey, the SHA was transported to WSCF and stored in a custody secure RMA, then disassembled in a hood the following day. Plugs were placed in the c-flex inlets and c-flex clamps on the 1/4 inch Tygon tubing coming out of the Top Collar to isolate the samples from ambient conditions. The in-line filters were transported to 222-S for analysis.

The next several sampling events were scheduled in B farm and therefore the ISVS was left inside the farm.

3.6 RADIATION SCREENING

Radiological screening results are used to determine (1) if the samples must be shipped as radioactive or nonradioactive in accordance with U.S. Department of Transportation (DOT) regulations and (2) if the samples meet the laboratory acceptance criteria.

The DOT limits for shipping a nonradioactive sample are 2000 combined pCi/g of beta-gamma activity and alpha activity. Samples exceeding these DOT limits may be shipped as radioactive material if the samples do not exceed the following laboratory acceptance criteria:

PNNL: Beta-gamma activity <15 pCi/g of sample media.
Alpha activity <5 pCi/g of sample media.

The sample media was not filtered for radiological particulates. The idea of unfiltered samples was to provide better analytical data for the laboratories. The samples were released for shipment based on the analytical results of the series of two filters and tritium trap collected through one of the 1/4 inch flexible lines. Based on the radiological results for the filters and tritium trap it is believed that the same concentration of radiological contaminants passed through the other 13 lines. The filters were analyzed by 222-S Laboratory. Based on the analytical results provided in Table 1 the samples were shipped to PNNL and delivered to J. A. Edwards. The VT scientists use the activity results in Table 1 to calculate pCi/g of sample media. The VT maintains this information in the project-specific file.

Table 1. Radionuclide Analysis Results.

Filter	Sample Identifier	Activity Results ^a (pCi/sample)	Activity ^b (pCi/L of tank gas)
Upstream filter	S6073-A21.OU1	Total Alpha =<0.097 Total Beta =<1.02 GEA = <detectable	= <detectable = <detectable =detectable
Downstream filter	S6073-A22.OD1	Total Alpha = <.160 Total Beta = <1.09 GEA = <detectable	= <detectable = <detectable = <detectable
Tritium Trap	S6073-A03.OT1	Total Activity=<2.69	= <detectable

NOTES:

The samples are nonradioactive. These results were evaluated against laboratory acceptance criteria and DOT limits.

^aAll less than (<) values represent the minimum detection limits at Laboratory 222-S.

^bNumbers based on 1 liter for the total volume of tank vapor through the filters.

4.0 SAMPLE CHAIN OF CUSTODY: RECEIPT, STORAGE, AND SHIPMENT

All sorbent trains, TSTs, and SUMMA[®] canisters received from PNNL are kept in a custody locked storage area maintained by SML. Sorbent trains and TSTs were maintained at 4 ± 2 °C in a refrigeration unit. SUMMA[®] canisters were stored in the same locked storage area, but were not refrigerated. The sample media was picked up from PNNL by SAS and transported in a government vehicle to a custody locked storage area. Appendix C lists the sample identifiers, sample types, and COC form numbers for the sampling event.

From the time that samples are received by SAS until they are shipped back to the analytical laboratory, all COCs are maintained by SAS in accordance with WHC-IP-1127-1.3, *Chain-of-Custody/Special Analysis Request for RCRA and CERCLA Protocol Samples* (WHC 1995a).

5.0 QUALITY ASSURANCE AND CONTROLS

5.1 CLEANLINESS OF SYSTEM

Immediately prior to sampling of SST 241-B-202, the ISVS manifold was purged with ambient air for 5 minutes at 1 L/min. After this purge an ambient air

SUMMA™ sample was drawn through the ISVS manifold and the 1/4 inch SUMMA™ sampling line. A second ambient air SUMMA™ sample was collected 10 meters upwind from the tank breather filter. The ambient air samples were then collected to confirm by laboratory analysis that the ISVS sampling manifold was free of trace organic contaminants (or to determine which contaminants were present and at what concentration). For further details, refer to WHC-IP-1127-4.8 (WHC 1995b) and the project-specific file located with the VT.

5.2 INSTRUMENT CALIBRATION

The ISVS uses mass flow meters to measure the flow rate and totalizers to measure the total volume of sample vapor drawn through the sample media. Errors associated with the mass flow meters and totalizers were determined by the Westinghouse Hanford Company (WHC) Standards Laboratory before the SST 241-B-202 sampling event. Duration of flow are specified by the analytical laboratories that supply and analyze the sorbent traps.

The flow measurements for this sampling event may have an error of 6 percent to 14 percent due to the mass flow measuring devices recalibration discrepancies. A detailed description of this discrepancy can be found in internal memo 75-820-96-028 (Trible 1996c).

Instruments located in the ISVS are calibrated on an annual basis at the WHC Standards Laboratory. ISVS instrumentation calibration data, maintained in files by the VT, are summarized in Table 2. According to the calibration schedule shown in Table 2, all instrumentation was within its calibration period during the SST 241-B-202 sampling event.

Table 2. Calibration Data.

Element	Calibration Date	Expiration Date	WHC Standards Laboratory Code
Rotameter AALBORG 102-05	8/8/95	8/8/96	518-28-13-001
Digital Thermometer HH22	1/11/96	1/11/97	518-79-06-003
Vacuum Gauge ASHCROFT	8/7/95	8/7/96	518-31-05-003
Headspace Thermocouple	5/31/96	5/31/97	518-78-02-010
Mass Flowmeters Sierra 822-13-OV1 FM-1/FT-1	8/8/95	8/8/96	518-28-03-015
Mass Flowmeters Sierra 822-13-OV1 FM-2/FT-2	8/8/95	8/8/96	518-28-03-016
Mass Flowmeters Sierra 822-13-OV1 FM-3/FT-3	8/8/95	8/8/96	518-28-03-017
Mass Flowmeters Sierra 822-13-OV1 FM-4/FT-4	8/8/95	8/8/96	518-28-03-018

The totalizers were calibrated in conjunction with the mass flow meters and the calibration data is summarized in Table 3.

Table 3. Totalizer Calibration Data.

Number	Calibration Date	Expiration Date	Flow Rate (stdcm ³ /min)	Time (min)	Calc. Total	UUT	Deviation
3494-1 FT-1	8/8/95	8/8/96	247.1	5.833	1441.2	1500	3.9%
3494-2 FT-2	8/8/95	8/8/96	253.8	7.065	1793.1	1800	0.4%
3494-3 FT-3	8/8/95	8/8/96	262.7	5.081	1334.7	1300	2.6%
3494-4 FT-4	8/8/95	8/8/96	25.2	5.186	1302.8	1300	0.2%

5.3 BLANK SAMPLES

Trip blanks are samples that accompany the sample media from the point of generation through sample analysis. They are transported to the field with the sample collection media but remain unopened during the sampling event. Analysis of trip blanks is used to assess cross-contamination of sample media during field transport and storage.

Field blanks are sampling devices similar to trip blanks. They are prepared and handled in the same manner as the sampling media, but no tank vapors are drawn through them.

Spiked blanks are prepared as regular sampling media but also contain a known amount of special analyte. Tank vapors are drawn through these blanks and they are handled and analyzed just like any other sample. Analysis of the spiked blanks is used to evaluate potential sample loss during shipment or storage.

Ambient blanks are samples of ambient air collected at the sampling location. Analysis of ambient blanks is used to assess contamination that may be present in the atmosphere or in the transfer tubing or sampling manifold of the ISVS immediately prior to sampling operations.

6.0 ANOMALIES

The VT used the Sampling and Analysis Plan and WHC-IP-1127-4.8, *Vapor Sampling of Waste Tanks Using In Situ Vapor Sampling System (ISVS)*, (1995b) to guide the sample collection. There were no reportable anomalies noted during the sampling of 241-B-202.

7.0 REFERENCES

- 49 CFR 100-177, 1992, "Transportation," Code of Federal Regulations, as amended.
- Blanchard, R. J., 1996a, *System Design Description for the In Situ Vapor Sampling System*, WHC-SD-WM-SDD-068 Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Buckley, L.L., 1996b, *Vapor Sampling and Analysis Plan*, WHC-SD-WM-TP-335 Rev. 2A, Westinghouse Hanford Company, Richland, Washington.
- Tribble, T. C., Viswanath, R. S., 1996c, *Recommendation concerning the ISVS/VSS comparison study data with respect to calibration errors in Mass flow monitors and controllers*, (internal memo 75820-96-028 to L.D. Pennington, August 28), Westinghouse Hanford Company, Richland, Washington.
- WHC, 1995a, *Chain-of-Custody/Special Analysis Request for RCRA and CERCLA Protocol Samples*, Procedure WHC-IP-1127-1.3, Rev. 1, Westinghouse Hanford Company, Richland, Washington.
- WHC, 1995b, *Vapor Sampling of Waste Tanks Using In Situ Vapor Sampling System (ISVS)*, Procedure WHC-IP-1127-4.8, Westinghouse Hanford Company, Richland, Washington.

This page intentionally left blank.

APPENDIX A
SAMPLE LOG SHEETS

This page intentionally left blank.

ISVS Sampling of B-202

Set up ISVS (Section 8.1)

Date: 7/18/96

Ensure particulate filters are installed

ISVS Personnel: Caprio, Mahon

LEAK CHECK (APPENDIX I) Leak Rate: 0 inch Hg in 5 min

Tank Temperature 16.5 C

Trailer Personnel: None

Ambient Temp. 17.7 C

WHC Sample ID	PNNL Sample ID	Probe Sample Line	Cart Port	Description	Desired Flow Rate SCCM	Desired Duration (min.)	Desired Total Flow SCC	Actual Flow Rate SCCM	Actual Start Time	Actual End Time	Actual Total Time (min.)	Actual Total Flow SCC
Purge SUMMA line of sample line with ambient air					1000	5	5000	1000	1015	1020	5	
S6073 A01 054	054	NA	NA	Upwind SUMMA #1		1			1017	1018	1	
S6073 A02 074	074	S	SUMMA	Ambient #2		1			1020	1021	1	
Uncap and insert sample bundle into tank									1021	1023		
Connect bundle lines:		1	1									
S6073 A21 0U1	0U1	1	1	UPSTREAM FILTER	200	5	1000	213	1032	NA	NA	999
A22 0D1	0D1			DOWNSTRM FILTER								
A03 0T1	0T1			TRITIUM								
Connect bundle lines:		S	SUMMA									
		2	1									
		3	2									
		4	3									
		5	4									
Purge Summa line /w tank					1000	5	5000	1000	1042	1047	5	5000
S6073 A04 094	094	S	SUMMA	Summa #3		1			1047	1048	1	6000
S6073 A05 116	116	S	SUMMA	Summa #4		1			1053	1054	1	6000
S6073 A06 235	235	S	SUMMA	Summa #5		1			1100	1101	1	6000

ISVS Sampling of B-202

WHC Sample ID	PNNL Sample ID	Probe		Description	Desired	Desired	Desired	Actual	Actual	Actual	Actual	Actual
		Sample Line	Cart Port		Flow	Duration	Total	Flow	Start	End	Total	Total
					Rate	(min.)	Flow	Rate	Time	Time	Time	Flow
					SCCM		SCC	SCCM			(min.)	SCC
S6073 A07 40R	40R	2	1	NH3/NOx/H2O	200	10	2000	207	1105	NA	NA	1996
S6073 A08 41R	41R	3	2	NH3/NOx/H2O	200	10	2000	199	1105	NA	NA	1998
S6073 A09 42R	42R	4	3	NH3/NOx/H2O	200	10	2000	197	1106	NA	NA	1999
S6073 A10 43R	43R	5	4	NH3/NOx/H2O	200	10	2000	197	1106	NA	NA	2000

Connect bundle lines:

6	1
7	2
8	3
9	4

S6073 A11 932	932	6	1	PNNL TST #1	200	1	200	260	1127	NA	NA	202
S6073 A12 968	968	7	2	PNNL TST #2	200	1	200	243	1127	NA	NA	199
S6073 A13 975	975	8	3	PNNL TST #3	200	1	200	212	1127	NA	NA	200
S6073 A14 976	976	9	4	PNNL TST #4	200	1	200	230	1127	NA	NA	200

Remove sample bundle from tank and cap

1140 1146

Dismantle sample bundle

S6073 A21 OU1	S96WV0098	1	1	Bundle line 1 Upstream filter
S6073 A22 OD1	S96WV0099	1	1	Bundle line 1 Downstream filter
S6073 A03 OT1	S96WV0100	1	1	Bundle line 1 tritium trap
S6073 A15 44R	44R	10	NA	Bundle store NH3/NOx/H2O FIELD BLANK #1
S6073 A16 45R	45R	11	NA	Bundle store NH3/NOx/H2O FIELD BLANK #2
S6073 A17 978	PNNL #978	12	NA	Bundle store PNNL TST FIELD BLANK #1
S6073 A18 980	PNNL #980	13	NA	Bundle store PNNL TST FIELD BLANK #2
S6073 A19 981	PNNL #981	NA	NA	Bundle store PNNL TST TRIP BLANK #1
S6073 A20 983	PNNL #983	NA	NA	Bundle store PNNL TST TRIP BLANK #2

Remove filters from cart manifold ports 1, 2, 3, 4, and SUMMA to release cart.

ISVS Sampling of B-202

WHC Sample ID	PNNL Sample ID	Probe		Description	Desired	Desired	Desired	Actual	Actual	Actual	Actual	Actual
		Sample	Cart		Flow	Duration	Total	Flow	Start	End	Total	Total
		Line	Port		Rate	(min.)	Flow	Rate	Time	Time	Time	Flow
					SCCM		SCC	SCCM			(min.)	SCC
					BUNDLE TOTAL TANK GAS USED DURING SAMPLING RUNS							32.79

Note: SCCM for the ISVS is reported at 760 torr, 21 C

HNF-SD-MM-RPT-256, Rev. 0

B-202 ISVS SAMPLING RADIOLOGICAL SCREENING RESULTS

Note: #VALUE! = <Detectable

S6073-A21.0U1 / S96WV0088

PARALLEL UPSTREAM FILTER

TOTAL VOLUME

Liters

pCi / liter

pCi / liter

ALPHA

BETA

GEA -

Co-60

Cs-134

Cs-137

Eu-152

Eu-154

Eu-155

<0.097

#VALUE!

<1.02

#VALUE!

<10.24

<10.24

<7.927

<7.927

<24.31

<24.31

<50.52

<50.52

<32.94

<32.94

<29.88

<29.88

S6073-A22.0D1 / S96WV0099

PARALLEL DOWNSTREAM FILTER

TOTAL VOLUME

Liters

pCi / liter

pCi / liter

ALPHA

BETA

GEA -

Co-60

Cs-134

Cs-137

Eu-152

Eu-154

Eu-155

<0.160

#VALUE!

<1.09

#VALUE!

<8.921

<8.921

<8.407

<8.407

<27.39

<27.39

<42.18

<42.18

<34.51

<34.51

<31.78

<31.78

S6073-A03.0T1 / S96WV0100

TRITIUM TRAP

TOTAL VOLUME

TOTAL ACTIVITY

Liters

pCi / liter

pCi / liter

1.00

<2.69

#VALUE!

SAMPLE EXPOSURE ANALYSIS, USING TOTAL OF BOTH UPSTREAM AND DOWNSTREAM FILTER ANALYSIS AS POSSIBLE EXPOSURE LEVEL

= BETA and ALPHA Less than DOT shipping limits

Total Alpha (pCi / liter) =

#VALUE!

Total Beta (pCi / liter) =

#VALUE!

Total GEA Cs-137 (pCi / liter) =

#VALUE!

SORBENT SAMPLING Used 5 g for sorbent mass

TOTAL VOLUME PER SAMPLE

2.00 Liters

Tritium per SAMPLE

NH3 (5 gram)

H2O (5 gram)

ALPHA per SAMPLE

NH3 (5 gram)

H2O (5 gram)

BETA per SAMPLE

NH3 (5 gram)

H2O (5 gram)

GEA per SAMPLE

NH3 (5 gram)

H2O (5 gram)

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

TST SAMPLING Used 4.5 g for TST mass

TOTAL VOLUME PER SAMPLE

0.20 Liter

Tritium per Sample

TST (4.5 gram)

ALPHA per Sample

TST (4.5 gram)

BETA per Sample

TST (4.5 gram)

GEA per Sample

TST (4.5 gram)

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

#VALUE! pCi per gram

SUMMA SAMPLING

TOTAL VOLUME PER CANISTER

6 Liters (air at 300K, 1 bar = 1.161 g/L)

Tritium PER SAMPLE

#VALUE! pCi per gram

ALPHA PER SAMPLE

#VALUE! pCi per gram

BETA PER SAMPLE

#VALUE! pCi per gram

GEA PER SAMPLE Cs-137

#VALUE! pCi per gram

APPENDIX B
AMBIENT CONDITIONS

This page intentionally left blank.

WEATHER DURING ISVS SAMPLING OF 241-B-202

This page intentionally left blank.

APPENDIX C
CHAIN-OF-CUSTODY FORMS

This page intentionally left blank.

Battelle Pacific
National Northwest Lab

CHAIN OF CUSTODY

WHC 100256

Custody Form Initiator J. A. Edwards - PNNL

Telephone (509) 373-0141

Page 85-3009 / FAX 376-2329

Company Contact R. D. Mahon - WHC

Telephone (509) 373-2891

Page 85-3656 / FAX 373-3793

Project Designation/Sampling Locations 200 West Tank Farm
241-B-202 Tank Vapor Sample SAF S6073
(ISVS Cart)

Collection date 07 - 18 - 96

Preparation date 07 - 16 - 96

Ice Chest No.

Field Logbook No. WHC- N 647-8

Bill of Lading/Airbill No. N/A

Offsite Property No. N/A

Method of Shipment Government Truck

Shipped to PNNL

Possible Sample Hazards/Remarks Unknown at time of sampling

Sample Identification

S6073 - A01 . 054 Collect Ambient Air Sample SUMMA #1
 S6073 - A02 . 074 Collect Ambient Air Sample SUMMA #2 (through tube bundle)

S6073 - A04 . 094 Collect SUMMA #3
 S6073 - A05 . 116 Collect SUMMA #4
 S6073 - A06 . 235 Collect SUMMA #5

[] Field Transfer of Custody		[X] Chain of Possession		(Sign and Print Names)	
Relinquished By	Date	Time	Received By	Date	Time
J A Edwards <i>J A Edwards</i>	07-16-96	1615	SMIST <i>SMIST</i>	07-16-96	1615
ETMIST <i>ETMIST</i>	7-17-96	1330	GS CAPRID <i>GS CAPRID</i>	07-17-96	1330
GS CAPRID <i>GS CAPRID</i>	7-19-96	1300	RD Mahon <i>RD Mahon</i>	07-18-96	1300
RD Mahon <i>RD Mahon</i>	07-22-96	1020	GS CAPRID <i>GS CAPRID</i>	07-22-96	1020
GS CAPRID <i>GS CAPRID</i>	07-22-96	1150	J A Edwards <i>J A Edwards</i>	07-22-96	1150

Final Sample Disposition

Comments:

<u>PNNL (only) Checklist</u>	<u>Pick-up / Delivery</u>	<u>Comments:</u>
Media labeled and checked?	☒ Y / ☒ N	
Letter of instruction?	☒ Y / ☒ N	
Media in good condition?	☒ Y / ☒ N	
COC info/signatures complete?	☒ Y / ☒ N	
Rad release stickers on samples?	☒ Y / ☒ N	
Activity report from 222S?	☒ Y / ☒ N	
RSR/release? (a ≤100/B ≤400 pCi/g)	☒ Y / ☒ N	
COC copy for LRB, RIDS filed?	☒ Y / ☒ N	

(WHC-SD-WM-TP-335, REV. 2, Table 2b)

(Revised 05/30/96 PNNL)

Battelle Pacific National Northwest Lab	CHAIN OF CUSTODY	WHC 100258
--	------------------	------------

Custody Form Initiator J. A. Edwards - PNNL

Telephone (509) 373-0141
Page 85-3009 / FAX 376-2329

Company Contact R. D. Mahon - WHC

Telephone (509) 373-7437
Page 85-9656 / FAX 373-3793Project Designation/Sampling Locations 200 West Tank Farm
241-B-202 Tank Vapor Sample SAF S6073
(ISVS Cart)Collection date 07 - 18 - 96
Preparation date 07 - 18 - 96

Ice Chest No.

Field Logbook No. WHC- N 647-8

Bill of Lading/Airbill No. N/A

Offsite Property No. N/A

Method of Shipment Government Truck

Shipped to PNNL

Possible Sample Hazards/Remarks Unknown at time of sampling

Sample Identification

S6073 - A07 . 40R · Collect NH₃/NO_x/H₂O Sorbent Trap
 S6073 - A08 . 41R · Collect NH₃/NO_x/H₂O Sorbent Trap
 S6073 - A09 . 42R · Collect NH₃/NO_x/H₂O Sorbent Trap
 S6073 - A10 . 43R · Collect NH₃/NO_x/H₂O Sorbent Trap

S6073 - A15 . 44R · Open, close and store NH₃/NO_x/H₂O field blank #1
 S6073 - A16 . 45R · Open, close and store NH₃/NO_x/H₂O field blank #2

[] Field Transfer of Custody		[X] Chain of Possession		(Sign and Print Names)	
Relinquished By	Date	Time	Received By	Date	Time
G W Dennis <i>G.W. Dennis</i>	07-16-96	1430	J A Edwards <i>J A Edwards</i>	07-16-96	1430
J A Edwards <i>J A Edwards</i>	07-16-96	1600	ES MAST <i>ES MAST</i>	07-16-96	1600
ES MAST <i>ES MAST</i>	7-17-96	1830	GS CAPRIO <i>GS CAPRIO</i>	07-17-96	1830
GS CAPRIO <i>GS CAPRIO</i>	7-18-96	1300	RD Mahon <i>RD Mahon</i>	07-18-96	1300
RD Mahon <i>RD Mahon</i>	07-22-96	1020	GS CAPRIO <i>GS CAPRIO</i>	07-22-96	1020
GS CAPRIO <i>GS CAPRIO</i>	07-22-96	1150	J A Edwards <i>J A Edwards</i>	07-22-96	1150

Final Sample Disposition

Comments:

<u>PNNL (onlv) Checklist</u>	<u>Pick-up / Delivery</u>	<u>Comments:</u>
Media labeled and checked?	☒ Y	
Letter of instruction?	☒ Y	
Media in good condition?	☒ Y	
COC info/signatures complete?	☒ Y	
Rad release stickers on samples?	☒ Y	
Activity report from 222S?	☒ Y	
RSR/release? (a ≤100/B ≤400 pCi/g)	☒ Y	
COC copy for LRB, RIDS filed?	☒ Y	

(WHC-SD-WM-TP-335, REV. 2, Table 2b)
A-6000-407 (12/92) WEF061

POC

POC

1 of 1

(Revised 05/30/96 PNNL)

Battelle Pacific
Northwest Laboratory

CHAIN OF CUSTODY

WHC 100257

Custody Form Initiator J. A. Edwards - PNL

Telephone (509) 373-0141
Page 85-3009 / P8-08 / FAX 376-0418

Company Contact R. D. Mahon - WHC

Telephone (509) 373-7437
Page 85-9656 / S3-27 / FAX 373-7076Project Designation/Sampling Locations 200 West Tank Farm
241-B-202 Tank Vapor Sample SAF S6073
(ISVS Cart)Collection date 07-12-96
Preparation date 07-12-96

Ice Chest No.

Field Logbook No. WHC-N-6478

Ertco HI/Lo thermometer No. PNL-T-00__

Bill of Lading/Airbill No. N/A

Offsite Property No. N/A

Method of Shipment Government Truck

Shipped to WHC

Possible Sample Hazards/Remarks Unknown at time of sampling

Sample Identification

S6073 - A11 . 932 * PNL Triple Sorbent Trap (TST) Sample # 1
 S6073 - A12 . 968 * PNL TST Sample # 2
 S6073 - A13 . 975 * PNL TST Sample # 3
 S6073 - A14 . 976 * PNL TST Sample # 4

S6073 - A17 . 978 * Open, close & store TST Field Blank # 1
 S6073 - A18 . 980 * Open, close & store TST Field Blank # 2

S6073 - A19 . 981 * Store TST Trip Blank #1
 S6073 - A20 . 983 * Store TST Trip Blank #2

[] Field Transfer of Custody		[X] Chain of Possession		(Sign and Print Names)	
Relinquished By	Date	Time	Received By	Date	Time
JL Julia	07-12-96	1400	JA Edwards	07-12-96	1400
JA Edwards	07-16-96	1600	ES Mahon	07-16-96	1600
ES Mahon	7-17-96	1330	GS CAPRIO AS C/L	07-17-96	1330
GS CAPRIO AS C/L	7-18-96	1300	RD Mahon	07-18-96	1300
RD Mahon	07-22-96	1020	GS CAPRIO AS C/L	07-22-96	1020
GS CAPRIO AS C/L	07-22-96	1150	JA Edwards	07-22-96	1150

Final Sample Disposition

Comments:

- PNL (only) Checklist
- Media labeled and checked? ☒ Y/N
 - Letter of instruction? ☒ Y/N
 - Media in good condition? ☒ Y/N
 - COC info/signatures complete? ☒ Y/N
 - Sorbents shipped on ice? (<5°C) ☒ Y/N
 - HI/Lo thermometer - Keep upright! ☒ Y/N
 - HI/Lo thermometer ☒ Y/N
 - Rad release stickers on samples? ☒ Y/N
 - Activity report from 222S? ☒ Y/N
 - COC copy for LRB, RIDS filed? ☒ Y/N

POC (R)POC (R)

Comments:

Cooler Temperature Status

HI -15°C / Lo -15°C (pick up at PNL to WHC)

HI 9°C / Lo -14°C (delivery at WHC from PNL)

HI °C / Lo °C (at return to PNL from WHC)

HI 10°C / Lo -14°C (at delivery from WHC to PNL)

(Revised 06/21/95 PNL)

DISTRIBUTION SHEET

To Distribution	From Special Analytical Support, Numatec Hanford	Page 1 of 1
		Date 8/7/97
Project Title/Work Order VAPOR AND GAS SAMPLING USING THE IN SITU VAPOR SAMPLING SYSTEM		EDT No. <u>621264</u>
		ECN No.

Name	MSIN	Text With All Attach.	Text Only	Attach./ Appendix Only	EDT/ECN Only
<u>Lockheed Martin Hanford Company</u>					
L. L. Buckley	R2-12	X			
<u>Lockheed Martin Services, Inc.</u>					
Central Files	A3-88	X			
<u>SGN Eurisys Services Corporation</u>					
E. S. Mast	S3-90	X			
<u>PNNL</u>					
J. L. Huckaby	K6-80	X			