DOE/CH/10584--1

SUSTAINABLE BIOMASS ENERGY PROGRAM HAMAKUA PROJECT

"Sustainable Biomass Products Development And Evaluation"

FINAL DRAFT REPORT

**Prepared by
The Pacific International Center For High Technology Research
Honolulu, Hawaii
October, 1994**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

This report was prepared by The Pacific International Center For High Technology Research for the United States Department of Energy (USDOE) with funding from the USDOE; the Electric Power Research Institute (EPRI); the Governor's Agriculture Coordinating Committee (GACC), State of Hawaii, the Office of State Planning (OSP), State of Hawaii; and the Department of Business, Economic Development and Tourism (DBEDT), State of Hawaii.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible electronic image products. Images are produced from the best available original document.

ACKNOWLEDGMENTS

The completion of this evaluation would not have been possible without extensive assistance from many individuals and organizations, particularly those listed below:

AMFAC/JMB Hawaii, Inc.

George St. John, Vice President of Plant Operations and Planning for AMFAC/JMB, contributed numerous hours assisting in evaluating potential options associated with using the sugar crop for ethanol and evaluating energy use in the mills and plantations.

Amoco Corporation

Joe Masin, Project Engineer with the Alternative Feedstock Development Department of Amoco, provided assistance with cost estimates and development of the economic evaluation procedures. He reviewed process flow diagrams and designs of facilities for processing biomass to ethanol. His assistance was fundamental in refining the capital and operating cost evaluations.

Applied Power Concepts, Inc.

William Farone, President provided continuing assistance with many aspects of the technical considerations that are the basis of this report.

C. Brewer & Company, Ltd.

Alan Kennett, Former Director of Sugar Technology and Engineering for C. Brewer, contributed substantially to providing an understanding of the operating considerations and costs associated with the production and processing of sugarcane in Hawaii. Tommy Crabb, VP and Manager of the BioEnergy Development Corporation, contributed the information and data used to develop the costs of producing short-rotation trees in Hawaii.

Cargill, Inc.

Loren Luppés and Tom Geiger of Cargill's Ethanol Division have been most helpful in providing technical information on manufacturing ethanol from sugars. Cargill brought an agriculture perspective to the analyses.

Electric Power Research Institute (EPRI)

Personnel with EPRI's Biomass Program expressed interest in the possibility that Hawaii might serve as a location for a 3,000 to 5,000-acre biomass to energy demonstration site. Jane Turnbull, Project Manager for the EPRI Biomass Program, assembled a technical team to visit Hawaii during May, 1993. The group consisted of Jane Turnbull, Jack Ranney with Oak Ridge National Laboratory, Pam Sydelko with Argonne National Laboratory, and Dave Schlagel with the University of California Agricultural Research Station. Interactions during the visit provided a perspective for the evaluations presented in this report.

The Governor's Agricultural Coordinating Committee (GACC)

GACC is charged with the responsibility of maintaining an overview of agriculture in Hawaii. The decline of the sugar industry has been an area of primary concern. For these reasons, GACC has been an active participant in the PICHTR program. Jo-Anna Nakata served as an active member of the program and GACC provided \$30,000 in financial support to the program.

The Hawaii Office of State Planning (OSP)

This program has benefited substantially from financial contributions and technical assistance from OSP. Harold Matsumoto, Director of OSP, assisted in providing an orientation of the program to the needs of community. Dennis Teranishi, special consultant with OSP, assisted with the evaluation of the crop biomass section of the project.

Hawaii Natural Energy Institute (HNEI)

HNEI has been extensively involved in evaluating the potential of using crops for energy production. Dr. Charly Kinoshita made substantial contributions to the program and has continually reviewed and evaluated technical data developed. His previous work on biomass crops in Hawaii was exceptionally valuable in this evaluation.

Hawaiian Sugar Planters' Association (HSPA)

HSPA was exceptionally helpful in providing production data on sugarcane and other potential energy crops. Dr. Robert Osgood and Mr. Lee Jakeway contributed substantial time and information to clarify issues on crops and energy, including a detailed summary of all costs associated with the planting, production, maintenance, harvesting, and transporting of sugarcane and alternative biomass crops which appear to have potential for energy conversion in Hawaii. HSPA also provided yield data on potential energy crops based on previous studies conducted in Hawaii.

National Renewable Energy Laboratory (NREL)

NREL has had a long term involvement in the development of technology for producing energy from biomass. Work conducted in the laboratory of Dr. Charles Wyman has been exceptionally useful in developing a format for the technical evaluations. Dr. Ralph Overend of Dr. Wyman's program has been particularly helpful in providing technical information and referrals to other individuals and laboratories for technical assistance.

State Department of Business, Economic Development & Tourism, Energy Division

Maria Tome, Transportation Energy and Fuels Specialist, was also a major contributor to the to the development and completion of this report. Over the course of a year, Maria spent weeks assisting in acquisition of technical information, redefinition and refinement of the topics, analysis and evaluation of the data, and assisting with refinement of numerous drafts of this document. Without Ms. Tome's assistance and inputs, this report would not be possible.

Tennessee Valley Authority (TVA)

TVA was contracted to evaluate the design and assist in determining the financial performance of alternative technologies for the production of ethanol from biomass. Wayne Barrier and Millicent Bulls assisted in the creation of process flow diagrams, and financial projections on capital and operating costs for the various technologies under review. Ms. Bulls contributed to the development of an economic model that was used in parts of the evaluations.

The authors also wish to acknowledge the assistance of the individuals associated with each of the private sector technology developers who patiently contributed technical information for the report. They include:

Laszlo Paszner - ACOS

Mark Carver - Arkenol

David Fowler - Bioenergy

John Taylor - Staketech

George Lightsey - Mississippi State University

Roger Hester - University of Southern Mississippi

EXECUTIVE SUMMARY

The PICHTR Sustainable Biomass Energy Program was developed to evaluate the potential to cultivate crops for energy production as an alternative use of lands made available by the closing of large sugar plantations. In particular, the closing of the Hamakua Sugar Company on the island of Hawaii brought a great deal of attention to the future of agriculture in this region and in the state. Many options were proposed. Several promising alternatives had been proposed for cane lands. These included dedicated feedstock supply systems (DFSS) for electrical energy production, cultivation of sugarcane to produce ethanol and related by-products, and the production of feed and crops to support animal agriculture.

Implementation of some of the options might require preservation of large tracts of land and maintenance of the sugar mills and sugar infrastructure. An analysis of the technical, financial, and other issues necessary to reach conclusions regarding the optimal use of these lands was required.

At the request of the Office of State Planning and Senator Akaka's office, the Pacific International Center for High Technology Research (PICHTR) established and coordinated a working group composed of state, county, federal, and private sector representatives to identify sustainable energy options for the use of idle sugar lands on the island of Hawaii. The program is based on inputs from the State of Hawaii's Department of Agriculture (DOA), Department of Business, Economic Development and Tourism (DBEDT), Department Office of State Planning, and the Department of Land and Natural Resources (DLNR); the University of Hawaii's College of Tropical Agriculture and Human Resources (CTAHR), and Hawaii Natural Energy Institute (HNEI); the Hawaiian Sugar Planters' Association (HSPA); the Pacific International Center for High Technology Research (PICHTR); the county of Hawaii; and other private sector companies, individuals, experts, and researchers, with recommendations from the National Renewable Energy Laboratory (NREL), U.S. Department of Energy (USDOE), and U.S. Department of Agriculture (USDA).

The Sustainable Biomass Energy Program's Hamakua Project was established to complete a comprehensive evaluation of the most viable alternatives and assess the options to grow crops as a source of raw materials for the production of transportation fuel and/or electricity on the island of Hawaii.

The motivation for evaluating biomass to energy conversion embraced the considerations that Hawaii's energy security would be improved by diversifying the fuels used for transportation and reducing dependency on imported fossil fuels. Local production of transportation fuels and feedstocks could also improve Hawaii's economic security and provide jobs for Hawaii's people. The use of waste products as feedstocks could divert wastes from landfills and/or reduce the pollution potential of those wastes and maintain scarce and valuable land resources for agriculture, housing, and business.

This report reviews issues and provides a detailed perspective on biomass energy production in Hawaii. Key topics to be reviewed in this report are:

- ◆ Selection of biomass material - comparing feedstocks;
- ◆ Evaluation of process technologies - processing into usable forms;
- ◆ Identification and evaluation of possible conversion options.
- ◆ Consideration of environmental and community related concerns.
- ◆ Evaluation of financial performance of conversion options.
- ◆ Identification of potential markets for products produced.

The central question this study addresses is:

Can energy be produced from biomass competitively in Hawaii, and can we develop the markets necessary for the products produced?

An extensive list of crops and other sources of biomass was reviewed to identify the most promising candidates. Starting with a list of twenty crops and sources of biomass in Hawaii, a short list of feedstocks was developed. Ethanol and electricity production options were evaluated independently. The most promising crops were sugarcane, leucaena, eucalyptus, napier grass, and sweet sorghum. Waste paper and green waste were also identified as potentially promising feedstocks for energy production.

ETHANOL

Emerging technologies allow for the production of ethanol from agricultural by-products such as corn stover, bagasse, yard and wood waste, etc. This is very significant: for example, where one acre of sugarcane produces about ten tons of edible sugar and a half ton of molasses, it also produces an additional twenty to twenty-five tons of materials in the form of leaves and stalks, that can be processed to ethanol. On the basis of available data, it was concluded that sweet sorghum, sugarcane and green wastes were the biomass sources with the greatest potential to provide fermentable sugars for ethanol production or as sustainable sources of biomass for electricity. It is also possible to produce ethanol from energy grasses or tree crops.

A collaborative effort with the Energy Division of the Department of Business Economic Development and Tourism was established to evaluate the performance of technical options for producing ethanol from biomass. A combination of direct inquiry and literature review was used to compare and contrast the capital and operating costs of a variety of technologies with traditional fermentation. Due to the proprietary nature of many of the approaches evaluated, in many cases it was necessary to rely on estimates made by owners of the technologies. In most cases, these individuals were the developers of the technologies and the owners of the patent rights, and therefore, may have been somewhat biased in their claims.

Seven different systems were felt to be representative of the range of technologies but should not be construed to be specifically representative of any one company or developer.

- 1) Simultaneous saccharification and fermentation;
- 2) Concentrated acid hydrolysis, neutralization and fermentation;
- 3) Ammonia disruption, hydrolysis and fermentation;
- 4) Steam disruption, hydrolysis and fermentation;
- 5) Acid disruption and transgenic microorganism fermentation;
- 6) Concentrated acid hydrolysis, acid recycle and fermentation; and
- 7) Acidified acetone extraction, hydrolysis and fermentation.

Estimated capital costs for plants producing 25 million gallons of ethanol per year ranged from 30 to 130 million dollars. At this scale, ethanol production costs ranged from less than \$0.50 per gallon to almost \$3.00 per gallon, depending on the technology and cost assumed for the feedstock.

ETHANOL FEEDSTOCK AND PRODUCTION COSTS

BIOMASS MATERIAL	\$/gallon for feedstock cost alone (high end of range)	\$/gallon for feedstock cost alone (low end of range)	\$/gallon processing cost (high end of range)	\$/gallon processing cost (low end of range)	total (high end of range)	total (low end of range)
Sugarcane	\$0.83	\$0.61	\$1.14	\$0.52	\$1.97	\$1.12
Leucaena	\$2.06	\$1.80	\$1.14	\$0.52	\$2.42	\$2.15
Eucalyptus	\$1.78	\$0.75	\$1.14	\$0.52	\$2.92	\$1.26
Napier grass	\$1.26	\$0.78	\$1.14	\$0.52	\$2.40	\$1.30
Sweet sorghum	\$0.72	\$0.51	\$1.14	\$0.52	\$1.86	\$1.03
Newspaper	\$0.14	\$0.05	\$1.14	\$0.52	\$1.28	\$0.56
Municipal Solid Waste	\$0.42	\$0.00	\$1.14	\$0.52	\$1.56	\$0.52
Molasses	\$0.50	\$0.50	\$1.14	\$0.52	\$1.64	\$1.01
Bagasse	\$0.84	\$0.44	\$1.14	\$0.52	\$1.98	\$0.96
Unburned sugarcane	\$0.98	\$0.52	\$1.14	\$0.52	\$2.12	\$1.04
Assuming 25 million gallon-per-year ethanol production facility						

Since the level of uncertainty associated with the analyses may be greater than the apparent differences between the technologies, it is not clear from this analysis what process is the "best." All technologies evaluated displayed innovations which, if combined in one integrated system, might out-perform any one individual approach. A detailed analysis of each step indicated that additional technical innovations were possible. In spite of the previously-described uncertainties, and variations in levels of optimism, the analyses resulted in similar cost projections. This similarity lends a

degree of confidence that, as the technologies mature, ethanol production costs in Hawaii will fall within this range.

Simultaneous saccharification and fermentation technology was among the more promising approaches evaluated. Based on the extensive information available, the costs developed for this technology were used for a more detailed analysis of the potential to direct the sugar crop to ethanol production. This was contrasted with the performance of the sugar industry and combinations of producing sugar and ethanol. As a stand alone business, production of ethanol from the sugar crop is marginal. Processing the sugarcane to produce sugar from the juice and ethanol from the bagasse appears to be the most promising option at this time. However, tax benefits are required to produce ethanol from cultivated crops at a price that is competitive with gasoline in Hawaii. If paper and green waste are used as part of the feedstock the economic performance is substantially improved. If \$1.03 in federal and state tax benefits per gallon of ethanol use can be applied, the opportunity is more promising.

ELECTRICITY

The evaluation of using biomass for electricity production focused on the potential of utilizing some or all of the power generating equipment at the sugar mills in the process. These evaluations showed that the existing facilities did not have the efficiency to produce power at a competitive price. It was concluded that the Hamakua Sugar Company system was unsuitable for retrofit. The results of this preliminary analysis suggested that, from a technical standpoint and in its present condition, the Hilo Coast Processing Company facility had the potential to operate as-built as a dedicated power station that can produce approximately 13 to 19 MW of exportable electrical power at moderate efficiency burning either biomass, No. 6 fuel oil, or coal.

Two options were proposed for the HCPC facility: 1) continue operation with no modifications other than those required by the bagasse handling system to accommodate different biomass fuels; exportable power is 18 MW; and 2) increase net capacity to 32 MW with the addition of a new low-pressure turbine-generator and condenser. In addition to the two retrofit options, an option to implement a biomass gasifier was also reviewed. The gasifier option would increase net capacity to approximately 26 MW. Upgrading the boilers and generator was contrasted with the addition of newly developed gasification technology to produce methane gas for generator fuel. A sensitivity analysis of biomass cost to cost of electricity showed that as the price of biomass increased, the addition of the gasifier technology could have a positive impact on lowering the production cost of electricity.

SENSITIVITY OF ELECTRICITY PRODUCTION COST TO BIOMASS COST

COMPARISONS

The economic performance of using biomass for ethanol production was contrasted with use of the material to produce electricity. After consideration of the economy of scale, income from operations per acre was the only common basis of comparison that could be used. Producing combinations of sugar and electricity offers some promise. If existing tax benefits are considered, producing a combination of sugar and ethanol also appears to present an opportunity. The cost of biomass is the single most important factor influencing the cost of production. If biomass can be supplied at a lower cost, the options for competitive production of ethanol and electricity are increased as the price declines. The table below provides a synopsis of the various scenarios for using prepared sugarcane supplied at the current cost of \$31.00 per wet ton to produce sugar, ethanol, and electricity.

PROCESS ECONOMIC SUMMARY
(VALUES PER HARVESTED ACRE PREPARED CANE)

Scenario	Products Using Prepared Cane	Sales Value	Production Costs/Acre	Profit per acre	Tax Benefits Concessions	Profit After Tax
1	Prep. Cane to Sugar & Molasses & Energy	\$4,904	(\$4,706)	\$197	\$0	\$197
2	Juice to Ethanol Bagasse to Ethanol SSF	\$3,647	(\$7,161)	(\$3,513)	\$347	(\$3,167)
3	Juice to Sugar & Molasses Bagasse to Ethanol	\$6,411	(\$6,288)	\$123	\$167	\$291
4	Juice to Ethanol- Bagasse to Electricity	\$2,141	(\$5,553)	(\$3,413)	\$179	(\$3,223)
5	Juice to Sugar & Molasses Bagasse to Electricity	\$4,990	(\$5,522)	(\$532)	\$123	(\$409)
6	Power Plant Retrofit	\$5,756	(\$5,400)	\$355	\$352	\$708
7	Addition of Gassifier	\$6,187	(\$6093)	\$94	\$481	\$575

There are specific opportunities to develop biomass to energy businesses in Hawaii. These will be dependent on location, feedstock, technology, and product forms. Conclusions emerging from this evaluation are as follows:

- a) In order to be economically competitive for energy production in Hawaii, biomass must be delivered at less than \$50 per dry ton.
- b) On a stand alone basis, cultivation of crops as dedicated feedstocks for energy production in Hawaii is marginal at this time.
- c) Initially, subsidies will be needed to establish infrastructure and sustain the energy industry.
- d) Multiple output products are essential to the economic viability of any dedicated process.
- e) The use of dedicated feedstocks holds promise when integrated with appropriate waste streams.
- f) Further development of ethanol technology should be directed to constructing engineering development units for one or more technologies appropriate for promising feedstocks.
- g) The Hamakua Sugar facilities are not practical as a biomass energy system, however, many of the components have potential to be used in new systems.
- h) The Hilo Coast Processing Company should be considered for upgrading to augment the power supply on the island of Hawaii.
- i) Coupling ethanol and electric production by using advancing technologies such as saccharification of lignocellulosic material for ethanol and biomass gasification for electricity looks promising; however, this will require further evaluation and demonstration.

TABLE OF CONTENTS

ACKNOWLEDGEMENTS	i
EXECUTIVE SUMMARY	v
TABLE OF CONTENTS	xii
LIST OF FIGURES	xx
LIST OF TABLES	xxiv
LIST OF ACRONYMS	xxviii
I. INTRODUCTION, BACKGROUND AND APPROACH	1
A. BACKGROUND	1
1. Agriculture	1
2. Energy	1
3. Current Situation in Hamakua and the Island of Hawaii	2
4. Previous and Related Work	2
B. THE HAMAKUA PROJECT	4
C. OBJECTIVES AND APPROACH	4
1. Tasks Defined	5
2. Modular Approach	6
3. Sources of Data	7
D. PROJECT TEAM	7
1. Participants	7
2. Subcontractors	10
II. CROP AND BIOMASS ASSESSMENT [TASK 2]	13
A. CROP YIELD AND COMPOSITION	14

B. SUGARCANE AS A SOURCE OF BIOMASS.....	14
1. Definitions.....	15
2. Potential Biomass Yield From Sugarcane	15
3. Sugarcane Components and Products.....	17
4. Yield Potential from Unburned Fields.....	18
5. Yield Potential from Irrigated Versus Unirrigated Fields.....	19
6. Cost of Sugarcane Production	19
7. Sugarcane Hybrids ("Energy Cane").....	22
C. ALTERNATIVE CROPS	22
1. Eucalyptus and Leucaena	23
2. Napier Grass (Banagrass).....	24
3. Sweet Sorghum and Sweet Sorghum-Sudan Grass Hybrid ...	26
4. Corn	27
5. Alfalfa	27
6. Production Costs	28
D. WASTES AS A SOURCE OF BIOMASS.....	29
1. Organic Material.....	30
2. Municipal Solid Waste and Organic Waste.....	30
3. Municipal Solid Waste - (Hawaii County Case Study)	32
4. Newspaper and Mixed Waste Paper	32
III. LAND AND FACILITIES [TASKS 3 AND 4].....	35
A. LAND CAPABILITIES.....	35
1. Zoning.....	36
2. Usage.....	36
3. Ownership.....	36
4. Elevation.....	36

5. Soil Type	36
6. Temperature	37
7. Rainfall.....	37
8. Insolation.....	37
9. Potentially Available Land	38
B. FACILITIES IN THE HAMAKUA/HILO COAST REGION.....	47
1. Hamakua Sugar Company.....	47
2. Hilo Coast Processing Company.....	49
3. Ka'u Agribusiness.....	49
IV. ETHANOL OPTIONS [TASKS 5 AND 7]	51
A. ETHANOL FOR HAWAII?.....	51
B. "LIGNOCELLULOSIC BIOMASS" AND SYSTEM ECONOMICS.....	52
C. POTENTIAL GALLONS OF ETHANOL PER TON OF BIOMASS.....	53
D. POTENTIAL GALLONS OF ETHANOL PER ACRE.....	54
1. Potential Yields of Ethanol from Agricultural Crops	54
2. Potential Yields of Ethanol from Sugarcane Components.....	54
E. FEEDSTOCK COST PER GALLON OF ETHANOL.....	55
1. Agricultural Crops.....	55
3. Sugarcane Components.....	56
2. Municipal Solid Waste, Organic Waste and Newspaper.....	57
3. Summary of Feedstock Costs.....	57
F. LAND REQUIREMENTS.....	58
G. STEPS IN THE ETHANOL PRODUCTION PROCESS.....	59
H. OPTIONS AT EACH STEP IN THE ETHANOL PRODUCTION PROCESS.....	60
I. APPROACH TO EVALUATION OF SYSTEMS.....	61
J. ASSUMPTIONS USED IN EVALUATIONS.....	62

K. REVIEW OF ETHANOL TECHNOLOGIES.....	62
1. Simultaneous Saccharification and Fermentation	63
2. Concentrated Acid Hydrolysis, Neutralization, and Fermentation.....	64
3. Ammonia Disruption, Hydrolysis, and Fermentation	66
4. Steam Disruption, Hydrolysis, and Fermentation	67
5. Acid Disruption and Transgenic Microorganism Fermentation.....	68
6. Concentrated Acid Hydrolysis, Acid Recycle, and Fermentation.....	69
7. Acidified Acetone Extraction, Hydrolysis and Fermentation	70
8. Traditional Fermentation of Sugars to Ethanol.....	71
L. SUMMARY OF TECHNOLOGY COMPARISONS.....	71
1. Developmental Status of Technology Options	71
2. Ethanol Production Costs and Sensitivity Analysis.....	71
M. CONCLUSIONS REGARDING ETHANOL OPTIONS.....	74
V. ELECTRICITY OPTIONS [TASKS 5 AND 6]	79
A. POWER CYCLE THERMOECONOMIC ANALYSIS.....	79
B. POWER GENERATION FROM BAGASSE ON THE ISLAND OF HAWAII.....	81
1. Percentage of Big Island Electrical Production Represented by HSC and HCPC.....	81
2. HSC & HCPC Cogeneration Systems Overview	82
3. HSC and HCPC Electrical Power Generation Capabilities.....	84
4. Hamakua Sugar Company Assessment.....	84
5. Baseline Plant Performance.....	85
6. Hilo Coast Processing Company Assessment.....	86

C. OPTIONS FOR FUTURE POWER GENERATION FROM BIOMASS IN THE REGION.....	87
1. Options for Electricity Production AT HAMAKUA	87
2. Options for Electricity Production At Hilo Coast Processing Company	89
3. Options Summary	100
C. TECHNOLOGY FOR FUTURE CONSIDERATION: GASIFICATION.	100
VI. ECONOMIC ANALYSIS [TASK 9].....	105
A. SUMMARY OF RESULTS AND BASIS FOR THE ECONOMIC PERFORMANCE EVALUATIONS.....	105
B. TECHNOLOGY PERFORMANCE	105
1. Sensitivity Analysis.....	108
2. Biomass Cost.....	108
3. Production Scenarios	109
4. Options for Producing Electricity From Biomass at the Sugar Mill.	115
VII. REGULATIONS, PERMITS, AND BENEFITS [TASK - 8].....	121
A. ENVIRONMENTAL AND COMMUNITY RELATED CONCERNS AND BENEFITS.....	121
1. Environmental Issues - Benefits Versus Costs.....	121
2. Biodiversity.....	122
B. REGULATIONS.....	123
1. Federal.....	123
2. State.....	123
3. County.....	123
C. PERMITS AND APPROVALS.....	123
1. Federal Permits.....	124
2. State Permits	124

3. County Permits.....	124
D. APPROVALS.....	128
1. Electricity Versus Ethanol Option:.....	128
E. RECOMMENDATIONS FOR SUCCESSFUL PERMITTING.....	133
F. BENEFITS.....	135
1. Social Acceptability and Community Support.....	135
2. Employment.....	135
3. Economic Advantages.....	136
VIII. MARKETS, PRODUCTS, & CO-PRODUCTS [TASK - 10].....	139
A. MARKETS FOR ETHANOL.....	139
1. State Demand.....	139
2. Potential Markets for Fuel-Grade Ethanol.....	139
3. Theoretical Market Size and Market Constraints:.....	140
4. Practical Considerations:.....	141
B. MARKETS FOR ELECTRICITY.....	152
C. MARKETS FOR CO-PRODUCTS AND BY-PRODUCTS.....	153
1. Protein.....	156
2. Lignin.....	156
3. Furfural.....	157
4. Carbon dioxide.....	157
5. Algae.....	158
6. Microbial Biomass.....	158
7. Stillage.....	158
8. Methane.....	158
9. Electricity.....	159

IX. CONCLUSIONS AND RECOMMENDATIONS.....	161
A. Perspective	161
1. General Conclusions.....	161
B. BIOMASS.....	162
1. Gasoline Competition.....	162
2. Reducing Capital Costs	163
3. Reducing Crop Production Costs and Improving Yields.....	163
4. Using Wastewater for Irrigation.....	163
5. Using Waste as a Primary Source or to Augment Biomass Supplies	163
6. Process Cost Reduction.....	163
C. ELECTRICITY.....	164
1. Future.....	164
D. IMPLEMENTATION.....	164
1. The Next Step	164
2. What Can The Government Do?.....	165
3. Concluding Remarks	166
E . VISION FOR THE FUTURE - A HAWAII INTEGRATED BIOMASS ENERGY PROGRAM.....	166

APPENDIX

LIST OF FIGURES

Figure I-1 Hawaii Biomass Programs.....	3
Figure I-2 Biomass To Energy Assessment Process.....	6
Figure I-2 Hawaii Biomass Programs.....	8
Figure II-1 Sugarcane Production In The State Of Hawaii, 1981-1992.....	16
Figure II-2 Sugarcane Component Yields.....	19
Figure II-3 Experimental and Projected Yields For Biomass Crops.....	28
Figure II-4 Primary Categories of Organic Material In Hawaii.....	30
Figure II-5 MSW Composition.....	31
Figure II-6 Refuse Hauled On The Island of Hawaii.....	32
Figure II-7 Newspaper Composition Ethanol Potential.....	33
Figure III-1 Sugar Plantations on the Island of Hawaii.....	35
Figure III-2 Zoning.....	39
Figure III-3 Usage.....	40
Figure III-4 Ownership.....	41
Figure III-5 Elevation.....	42
Figure III-6 Soil.....	43
Figure III-7 Temperature.....	44
Figure III-8 Rainfall.....	45
Figure III-9 Insolation.....	46
Figure IV-1 Potential Gallons of Ethanol Per Ton Biomass	53
Figure IV-2 Potential Gallons of Ethanol Per, Acre Per Year.....	54

Figure IV-3	Prepared Cane To Ethanol Diagram	55
Figure IV-4	Estimated Biomass Cost Per Potential Ethanol Gallon.....	58
Figure IV-5	Biomass Conversion Products.....	59
Figure IV-6	Ethanol Production Technology Options.....	60
Figure IV-7	Simultaneous Saccharification and Fermentation	63
Figure IV-8	Concentrated Acid Hydrolysis, Neutralization, and Fermentation	65
Figure IV-9	Ammonia Disruption, Hydrolysis and Fermentation	66
Figure IV-10	Steam Disruption, Hydrolysis, and Fermentation	67
Figure IV-11	Acid Disruption and Transgenic Microorganism Fermentation.....	68
Figure IV-12	Concentrated Acid Hydrolysis, Acid Recycle, and Fermentation.....	69
Figure IV-13	Acidified Acetone Extraction, Hydrolysis, and Fermentation	70
Figure IV-14	Ethanol Production Cost Summary For 7 Technologies.....	73
Figure V-1	Power Conversion Process Representation.....	80
Figure V-2	HCPC Full-Condensing Mode Operation Schematic.....	90
Figure V-3	HCPC Electric Power Generation Option No. 1.....	92
Figure V-4	HCPC Electric Power Generation Option No. 2a.....	94
Figure V-5	HCPC Electric Power Generation Option No. 2b.....	95
Figure V-6	Sensitivity of Electricity Production Cost To Biomass Cost.....	104
Figure VII-1	Permit Timing.....	130
Figure VIII-1	On Highway Use of Gasoline, 1980-1992, by County.....	140
Figure VIII-2	On Highway Use of Diesel, 1980-1992, by County.....	140
Figure VIII-3	Crop Refinery.....	154

Figure VIII-4 Potential Product Development Through Commercial Substitution	155
Figure VIII-5 Xylose to Furfural	157
Figure IX-1 A Vision for the Future-Hawaii Integrated Biomass Energy System	167

LIST OF TABLES

Table I-1	Hamakua Project Advisory Group	8
Table I-2	Hamakua Project Technical Team.....	8
Table II-1	Composition of Potential Crops and Waste Materials	14
Table II-2	Hawaii Sugar Industry Statistics.....	16
Table II-3	Production Data For Two Hawaii Plantations.....	21
Table II-4	Experimental Biomass Yields and Calculations of Expected Commercial Yields	28
Table II-5	Estimated Costs of Biomass Feedstock at the Conversion Plant.	29
Table II-6	Quantities of Municipal Solid Waste Available In Hawaii.....	31
Table III-1	Estimated Biomass Yield from Potentially Available Lands on the Island of Hawaii	38
Table IV-1	Conversion Efficiencies Assumed For Sucrose, Cellulose, and Hemicellulose To Ethanol.....	53
Table IV-2	Possible Approaches To Ethanol From Sugarcane.....	54
Table IV-3	Cultivated Feedstocks: Estimated Cost Per Dry Ton and Per Ethanol Gallon.....	56
Table IV-4	Range of Estimated Biomass Costs Per Potential Ethanol Gallon.....	57
Table IV-5	Acreage Required To Produce Biomass For A 25 Million Gallon Per Year Ethanol Production Facility.....	58
Table IV-6	Evaluation Assumptions.....	62
Table IV-7	Ethanol Plant Capital and Process Costs	72
Table IV-8	Ethanol Plant Performance Summary.....	72
Table V-1	Power Equipment at HSC and HCPC.....	83

Table V-2	Electrical Power Generation and Fuel Inventories for 1986 and 1991.....	84
Table V-3	HSC Stream Turbine-Generators.....	84
Table V-4	Estimated Operating Parameters for Biomass Options for HSC.....	89
Table V-5	Power Equipment Information.....	91
Table V-6	Operating Parameters for HCPC Option No. 1.....	93
Table VI-8	Operating Parameters for HCPC Options No. 2A and 2B.....	95
Table V-8	Turbine-Generator and Surface Condenser Descriptions.....	96
Table V-9	Estimated Operating Parameters For Biomass Options For HCPC.....	96
Table V-10	Capital and Operating Costs For Retrofit Option 2B (Biomass Costs = \$0 Per Dry Ton.....)	97
Table V-11	Capital and Operating Costs For Retrofit Option 2B (Biomass Costs = \$50 per dry ton).....	98
Table V-12	Capital and Operating Costs For Retrofit Option 2B (Biomass Costs = \$106 per dry ton).....	99
Table V-13	Capital and Operating Costs For A Biomass Gasifier (Biomass Costs = \$0 per dry ton).....	101
Table V-14	Capital and Operating Costs For A Biomass Gasifier (Biomass Costs = \$50 per dry ton).....	102
Table V-15	Capital and Operating Costs For A Biomass Gasifier (Biomass Costs = \$106 per dry ton).....	103
Table VI-1	Parameters for Ethanol And Electricity Production.....	106
Table VI-2	25 Million Gallons Ethanol Per Year From Prepared Cane.....	107
Table VI-3	Factors Used In The Sensitivity Analysis.....	108
Table VI-4	Economic Performance of SSF Based On Biomass Cost.....	108

Table VI-5	Estimated Income From Operations Per Harvested Acre-Prepared Cane to Sugar & Molasses, Bagasse to Electricity (Business As Usual).....	111
Table VI-6	Estimated Income From Operations Per Harvested Acre-Prepared Cane to Ethanol by SSF, Bagasse to Ethanol by SSF, Lignin to Electricity.....	112
Table VI-7	Estimate of Income From Operations Per Harvested Acre-Prepared Cane to Sugar & Molasses, Bagasse to Ethanol by SSF, Lignin to Electricity.....	113
Table VI-8	Estimated Income From Operations Per Harvested Acre-Prepared Cane to Ethanol by Simple Fermentation, Bagasse, to Electricity.....	114
Table VI-9	Business As Usual With Conventional Steam Combustion Option.....	117
Table VI-10	Business As Usual With Retrofit- Option 2b.....	118
Table VI-11	Business As Usual With Biomass Gasifier	119
Table VI-12	Process Economic Summary	120
Table VII-1	Estimated Maximum Number of Permits and Agencies.....	124
Table VII-2	List of Possible Permits and Approvals.....	126
Table VII-3	Likely Permits and Approvals	129
Table VIII-1	Ethanol as a Transportation Fuel.....	141
Table VIII-2	Estimated "Competitive Price" for Fuel-Grade Ethanol in Various Hawaii Applications.....	151
Table VIII-3	HELCO's 20-Year Preferred Plan as of October, 1993.....	152
Table VIII-4	HELCO's Planned Capacity Additions and Retirements.....	153
Table VIII-5	Protein Content of Selected Plant Materials.....	156

LIST OF ACRONYMS

ACOS	Acid-Catalyzed Organosolv Saccharification
ATC	Authority To Construct
BGF	Biomass Gasifier Facility
Btu	British thermal unit
CAP	Consolidated Application Process
CCA	Central Coordinating Agency
CTAHR	College of Tropical Agriculture and Human Resources (University of Hawaii)
DBEDT	Department of Business, Economic Development and Tourism (State of Hawaii)
DFSS	Dedicated Feedstock Supply System
DLNR	Department of Land and Natural Resources (State of Hawaii)
DOA	Department Of Agriculture (State of Hawaii)
DOT	Department Of Transportation (State of Hawaii)
EA	Environmental Assessment
EIS	Environmental Impact Statement
EPA	Environmental Protection Agency
EPRI	Electric Power Research Institute
ETBE	Ethyl Tertiary Butyl Ether
GIS	Geographic Information System
GACC	Governor's Agriculture Coordinating Committee (State of Hawaii)
HCPC	Hilo Coast Processing Company
HSPA	Hawaiian Sugar Planters' Association
HECO	Hawaiian Electric Company
HELCO	Hawaii Electric Light Company
HITAHR	Hawaii Institute of Tropical Agriculture and Human Resources (University of Hawaii)
HNEI	Hawaii Natural Energy Institute (University of Hawaii)
HSC	Hamakua Sugar Company

HSPA	Hawaiian Sugar Planters' Association
LOI	Letter of Interest
MBI	Michigan Biotechnology Institute
MECO	Maui Electric Company
MSW	Municipal Solid Wastes
NPS	National Park Service
NREL	National Renewable Energy Laboratory
OEQC	Office of Environmental Quality Control (State of Hawaii)
OSP	Office of State Planning (State of Hawaii)
PICHTR	Pacific International Center for High Technology Research
SSF	Simultaneous Saccharification and Fermentation
TVA	Tennessee Valley Authority
UH	University of Hawaii
USDA	United States Department of Agriculture
USDOE	United States Department of Energy
USFWS	United States Fish and Wildlife Service
VLC	Very Low Color

I. INTRODUCTION, BACKGROUND AND APPROACH

The closing of the Hamakua Sugar Company on the island of Hawaii has brought a great deal of attention to the future of agriculture in this region and in the state. State, county, and federal agencies, as well as a variety of task forces and working groups, have been assembled to propose solutions. Many options have been proposed. Each level of input provides a unique and important perspective on this complex problem. Some of the alternatives are site sensitive and at present lack analysis of the technical, financial, and other issues necessary to reach conclusions regarding the optimal sustainable use of the lands that may be available. In order to assess the problems and issues, a comprehensive evaluation effort was undertaken to identify the most viable alternatives.

A. BACKGROUND

1. Agriculture

The cultivation of sugarcane and the plantation life style has been a long standing agricultural tradition along the Hilo/Hamakua Coast of the island of Hawaii and in the entire state of Hawaii. This one hundred and fifty year history has also been an economic mainstay in many of Hawaii's rural communities. Families in these regions have been employed by the sugar industry for several generations. The traditional agriculture industry in Hawaii is in crisis.

Historically, agriculture has been the primary industry and still represents approximately 10% of the economic base on the island of Hawaii. However, the traditional role of the large plantations as an economic base on the island of Hawaii is diminishing. This situation places considerable pressure on the economy, the future of agriculture, the generation of electricity, and the traditional lifestyle of many rural areas. This economic decline is reaching a crisis situation in many of these communities.

2. Energy

The state is dependent on imported petroleum to meet more than 90% of its energy needs.¹ This condition results in an outflow of capital at a time when energy development opportunities may provide a means of rebuilding Hawaii's rural economy and expanding jobs in the agriculture sector.

There are significant energy issues which are directly tied to the closing of sugar mills on the island. In 1992, electricity generation on the island of Hawaii was comprised of the following: oil, 78.6%; biomass, 18.3%; wind, 1.7%; hydroelectric, 1.2%; and coal, less than 0.1%.² All electricity produced from biomass was generated from burning bagasse at the sugar mills. Unfortunately, due to the continuing decline of the sugar industry, the amount of excess electricity produced from sugar plantations on the island of Hawaii has decreased from a high of 40 MW in 1988 to the current 28 MW.³

3. Current Situation in Hamakua and the Island of Hawaii

Much of the land previously cultivated for sugarcane is either no longer in use or will be taken out of cultivation soon. There are presently three operating sugar companies employing approximately 1350 people on the island of Hawaii.⁴ Hamakua Sugar Company is, under a bankruptcy court order, harvesting its final crop. Seven hundred and fifty people will be unemployed by the end of 1994. Mauna Kea Agribusiness Company (Hilo Coast Processing Company) is scheduled to close sugar operations by the end of 1994 resulting in further layoffs. Approximately 1,100 direct jobs are at immediate risk along the Hamakua Coast. Ka'u Agribusiness Sugar Division is committed to sugar operations only through 1994. Approximately 250 people are employed at this location. Elsewhere in the state, Oahu Sugar Company, which employs 355 people, has announced the closure of sugar operations by June 1995. Waialua Sugar Company directly employs about 450 workers and is likely to go a similar route soon.⁵ Many of these difficulties are due to the inevitable forces of low sugar prices and intense international competition.

The scheduled closing of the sugar plantations on the island of Hawaii has brought this situation to focus in the state of Hawaii. One promising alternative for utilizing the land being taken out of sugar production is Dedicated Feedstock Supply System (DFSS) for the production of electrical energy and transportation fuels. If the growing of energy crops were shown to be economically viable, it is possible that more than 40,000 acres on the Big Island could be available to cultivate biomass for energy. Development of these options may require preservation of large tracts of land, maintenance of the sugar mills and sugar industry infrastructure, detailed economic evaluations of promising technologies, and long-term cooperation of various groups. The successful development of a biomass energy program would allow the state of Hawaii to reduce its dependence on imported petroleum, thereby, increasing its energy security. A primary goal of this work was to complete a comprehensive evaluation of the most viable alternatives for biomass energy production before opportunities for contributing to a promising sustainable energy and agricultural future are lost. Sustainable, in this regard, includes economic, environmental, and social sustainability. Biomass-based energy businesses may offer the potential to reduce the dependence on fuel imports and establish new agriculture enterprises.

4. Previous and Related Work

The efforts of this program build upon work previously completed in studies sponsored by the State of Hawaii's Department of Business, Economic Development and Tourism (DBEDT)⁶ and the US Department of Energy (USDOE). Figure I-1 below provides a representation of the flow of information into the present study and between related work, including follow-on programs which will carry potential opportunities identified in this study on to the next phase of development. The primary studies that contributed to this work are described below:

A Statewide Inventory of Organic Waste was completed in 1991 by UNISYN Corporation under a contract with DBEDT.⁷ The draft report provided a

comprehensive survey of the composition and locations of organic wastes produced in Hawaii. This information provided a basis for further evaluation of the potential to use organic waste materials to produce ethanol and electricity in the Hamakua Project.

An Investigation of Biomass for Energy Production on Molokai was completed by the Hawaii Natural Energy Institute (HNEI) in 1993⁸ with input from the Hawaiian Sugar Planters' Association (HSPA) and the Hawaiian Electric Company (HECO). This study provided a substantial amount of information on the performance of crop alternatives for biomass production for the Hamakua Project.

A Comparative Study of Biomass Yields for Tree and Grass Crops Grown for Conversion to Energy was completed by HSPA in 1993 under a contract with DBEDT. Results of this study were used to develop the data base on crop alternatives for the Hamakua Project.⁹

A report on *Ethanol Production in Hawaii - Feedstocks, Processes, and Current Economic Feasibility of Fuel-grade Ethanol Production in Hawaii* was completed in 1994 under a contract with DBEDT with funding from the USDOE. This report provided a preliminary review of the potential of crops that could be grown in Hawaii to provide sources of feedstock for ethanol production.¹⁰ This report also provided a comparative review of technologies for the conversion of lignocellulosic biomass to ethanol. The *Ethanol Production in Hawaii* report was developed in parallel with the Hamakua Project report. Through a collaborative effort with DBEDT, a common data base was developed to support both activities, and the Hamakua Project report duplicates some material presented previously in the DBEDT ethanol report.

FIGURE I-1
HAWAII BIOMASS PROGRAMS

The *Maui LOI* and *Hawaii LOI* Projects and Proposals are currently ongoing studies which will be completed after the Hamakua Project. While the Hamakua Project was in progress, the National Renewable Energy Laboratory solicited Letters of Interest (LOIs) for Economic Development Through Biomass Systems Integration. The LOIs were to evaluate the potential for cost-shared field demonstrations or pre-commercial developments of integrated systems in anticipation of future joint ventures to commercialize these systems.

In July, 1993, with the cooperation of the Sustainable Biomass to Energy Program Team, PICHTR submitted two proposals to perform research under the Economic Development Through Biomass Systems Integration Project. The proposals were accepted by NREL and PICHTR was awarded two contracts, commonly referred to as "the Maui LOI" and "the Hawaii LOI."

The Maui LOI, to be conducted jointly with AMFAC, Maui Electric, DBEDT and Maui County, concentrates on conversion of biomass to electricity at AMFAC's Pioneer Mill Site. The Hawaii LOI, to be conducted jointly with AMOCO, Cargill, C. Brewer, Hawaii Electric Light Company, DBEDT and Hawaii County, concentrates on evaluating the potential to convert biomass to ethanol at C. Brewer's Ka'u Mill site on the island of Hawaii.

B. THE HAMAKUA PROJECT

Responding to concerns about the decline of the sugar industry, potential shortages of electrical energy, and dependence on imported petroleum, in December of 1992 Senator Akaka's Office and the Office of State Planning requested the Pacific International Center for High Technology Research (PICHTR) to establish the Hamakua Project.

The intent of the project was to refine the list of options and conduct preliminary economic evaluations of the most promising opportunities to convert biomass to energy. To accomplish this, the Hamakua Project, together with related projects comprising PICHTR's Sustainable Biomass Energy Program, have been successfully integrated into the National Biofuels Program. This allows Hawaii to leverage a development pathway which could lead to the successful commercialization of a sustainable biomass energy industry for the state.

As project manager, PICHTR's responsibility was to coordinate all activities relating to the development of sustainable biomass to energy options, establish and maintain communication with all interested parties, and make available the information gathered by the various projects to potential commercial developers.

C. OBJECTIVES AND APPROACH

The primary objectives of the Hamakua Project were to define options for crops and land uses which could possibly be made available for the production of energy and complementary higher value co-products and determine if viable business opportunities could be developed along the Hamakua/Hilo Coast. This would be accomplished by analyzing the technical and financial performance of promising

options to convert crops and available organic materials into fuel, electricity, or energy related products.

The associated objectives included:

- Definition of possible economically viable and sustainable biomass energy options for sugarcane lands which may become available due to the closing of sugar companies on the island of Hawaii and the state of Hawaii in general.
- Coordination of the activities of various groups relating to the development of potential biomass energy options for the state of Hawaii.
- Determination of the potential of the defined options to provide the basis for realistic business opportunities.

This report attempts to answer the following questions:

- 1) Which sources of biomass would be best suited to the production requirements of this region?
- 2) Is there sufficient land available to develop a dedicated feedstock supply system in the region?
- 3) What technologies would be best suited for the specific conditions of this region?
- 4) Is there a sustainable biomass to energy option for the Hilo/Hamakua Coast? Are there options for biomass to energy elsewhere in the region?

1. Tasks Defined

In order to answer the questions posed above, tasks were defined as follows:

- **Task 1 - Program Coordination and Development:** Establish communication with all parties interested in the development of a sustainable biomass energy program for the state of Hawaii. Present results to government, community, and business leaders for review and participation in formulating policy necessary for development;
- **Task 2 - Crop Assessment:** Identify a short list of crops and agricultural practices that may be appropriate under the physical and economic conditions that exist in the region;
- **Task 3 - Land Capability:** Identify land areas that are most suitable for production of potential biomass crops;
- **Task 4 - Identification of Facilities:** Evaluate the suitability of the facilities which may be available for the purposes of demonstrating and ultimately developing the appropriate technologies;

- **Task 5 - Identify Applicable Biomass to Energy Technologies:** Establish communication with interested private sector entities that are leaders in the biomass energy industry;
- **Task 6 - Electricity Options:** Evaluate current biomass-fueled electricity production facilities in the region; evaluate options for continued or expanded production of electricity from these facilities;
- **Task 7 - Ethanol Options:** Evaluate promising technology options for the conversion of biomass to ethanol;
- **Task 8 - Environmental and Community Concerns:** Consolidate information on permit requirements; discuss environmental and community related issues such as environmental concerns, biodiversity, aesthetic value, and social acceptability as they relate to sustainable biomass energy industries;
- **Task 9 - Economic Analysis:** Conduct detailed analyses of the financial performance of various options which may have application on the island of Hawaii and in the state in general;
- **Task 10 - Market Development:** Outline potential markets options; identify primary products, co-products, and potential higher value products which may result from conversion of biomass;
- **Task 11 - Requirements for Sustainability:** Examine the environmental and social impacts of the proposed options to ensure that they are in the widest sense sustainable in the area;
- **Task 12 - Identification of Potential Barriers:** Identify potential barriers to development; and
- **Conclusions and Recommendations:** Summarize conclusions and make recommendations for implementation.

2. Modular Approach

The approach taken in the project involved separating the various processes into modules and then evaluating the technical and economic performance of the various options at each stage of the process. Spreadsheets showing the relationships of sources of biomass to their potential to produce ethanol and electrical energy were developed. A modular approach was used to allow several aspects of an integrated biomass energy process to be interchangeable. This modular approach partitioned the integrated process into major categories as illustrated in Figure I-2.

**FIGURE I-2
BIOMASS TO ENERGY ASSESSMENT PROCESS**

3. Sources of Data

Project management relied on experts and previously completed work whenever possible. Members of both the technical team and the advisory group provided valuable assistance throughout the project by attending meetings, reviewing data, offering guidance in their respective areas of expertise, and providing information and pertinent reports where required. Fortunately, substantial amounts of information were available from the technical literature and field experiences embodied in the technical team.

D. PROJECT TEAM

The Hamakua Project was initiated by the concern over the announced closing of Hamakua Sugar Company. This project created interest at the federal, state, county, and private sector levels.

1. Participants

This project provided a focus for a diverse group which was interested in the potential of using sustainable sources of biomass for the production of electricity and/or transportation fuel. This interest resulted in both technical and economic support and active participation by many of the interested parties.

a) Advisory Group and Technical Team

PICHTR assembled technical and advisory teams representing the technical skills, political perspective, and business interests that were considered essential to develop the project. federal, state, county, and private sector representatives were assembled into an advisory group and a technical team. Both groups met periodically throughout the study period. The advisory group addressed issues relating to policy and overall direction of the program while the technical team was responsible for the work effort. It was the objective of both groups to reach a

consensus regarding the information presented in this report. Members of the advisory group and the technical team are listed in Tables I-1 and I-2 respectively.

**TABLE I-1
HAMAKUA PROJECT ADVISORY GROUP**

GROUP MEMBER	ORGANIZATION
Gary Doi	Governor's Agriculture Coordinating Committee
Rick Egged	State of Hawaii DBEDT
H. M. Hubbard	Pacific International Center For High Technology Research
Maurice Kaya	State of Hawaii DBEDT - Energy Division
Yukio Kitagawa	State of Hawaii Board of Agriculture
Michael Kitamura	Senator Daniel Akaka's Office
Ralph Overend	National Renewable Energy Laboratory - Biofuels Program
Victor Phillips	HITAHR, CTAHR, University of Hawaii
Diane Quitiquit	County of Hawaii
Bob Shleser	Pacific International Center For High Technology Research
Patrick Takahashi	Hawaii Natural Energy Institute, University of Hawaii
Dennis Teranishi	State of Hawaii Office of State Planning
Andrew Trenka	Pacific International Center For High Technology Research

**TABLE I-2
HAMAKUA PROJECT TECHNICAL TEAM**

TEAM MEMBER	ORGANIZATION
David Harada	BHP Petroleum
Celia Hildebrand	State of Hawaii DBEDT - Business Development & Marketing
Alan Kennett	C. Brewer and Company/Olokele Sugar Company
Charly Kinoshita	Hawaii Natural Energy Institute, University of Hawaii
Warren Lee	Hawaii Electric Light Company
Tung Liang	Department of Engineering, University of Hawaii
Lynn Maunakea	State of Hawaii DBEDT - Business Services Division
Jim McElvaney	McElvaney and Associates
Bob Osgood	Hawaiian Sugar Planters' Association
Art Seki	Hawaiian Electric Company
Bob Shleser	Pacific International Center For High Technology Research
John Sprague	Pacific International Center For High Technology Research
George St. John	AMFAC/JMB Agricultural Operations
Maria Tome	State of Hawaii DBEDT - Energy Division
Andrew Trenka	Pacific International Center For High Technology Research
Robert Tsuyemura	State of Hawaii Department of Agriculture
Larry Zestar	Chevron, USA

b. Federal Participation

NREL - The National Renewable Energy Laboratory (NREL) has had a long term involvement in the development of technology for producing energy from biomass. Work conducted in the laboratory of Dr. Charles Wyman has been exceptionally

useful in developing a format for the technical evaluations. Dr. Ralph Overend of Dr. Wyman's program has been particularly helpful in providing technical information and referrals to other individuals and laboratories for technical assistance.

TVA - The Biomass R&D Program of the Tennessee Valley Authority (TVA), coordinated by Wayne Barrier, provided the services of Millicent Bulls as a consultant to the project. Her work contributed to the development of an economic model which served as the basis for financial analyses.¹¹

c. State Participation

DBEDT - The Energy Division of the Department of Business, Economic Development & Tourism (DBEDT) became a very active participant. DBEDT has had a long standing interest in the potential of alternative fuels as a partial substitute for the petroleum that Hawaii imports to meet about 90% of its energy needs. In particular, the opportunity to substitute ethanol produced from locally grown sources of biomass was a key area of concern. During 1993, DBEDT sponsored an analysis of the opportunities to produce ethanol from biomass.¹² The results of that study provided a foundation for aspects of this work. In addition, DBEDT provided the services of Maria Tome, Energy Division engineer, to serve as co-manager of the project; and assist in data acquisition assistance.

GACC - The Governor's Agriculture Coordinating Committee (GACC) is charged with the responsibility of maintaining an overview of agriculture in Hawaii. The decline of the sugar industry has been an area of primary concern. For these reasons, GACC has been an active participant in the PICHTR program. Jo-Anna Nakata served as an active member of the project and GACC provided \$30,000 in financial support to the project.

HNEI - The Hawaii Natural Energy Institute (HNEI) of the University of Hawaii has had extensive involvement in evaluating the potential of using crops for energy production. Dr. Charly Kinoshita made substantial contributions to the program and has continually reviewed and evaluated technical data developed.

CTAHR - Dr. Victor Phillips and staff of the College of Tropical Agriculture and Human Resources (CTAHR) at the University of Hawaii provided background on tree crops and land use options.

d. Private Sector Participation

AMFAC/JMB HAWAII, INC. - George St. John, Vice President of Plant Operations and Planning for AMFAC/JMB, contributed numerous hours assisting in evaluating potential options associated with using the sugar crop for ethanol and electricity production.

AMOCO CORPORATION - Joe Masin, Project Engineer with the Alternative Feedstock Development Department of Amoco, provided assistance with cost estimates and development of the economic evaluation procedures. He reviewed

process flow diagrams and designs of facilities for processing biomass to ethanol. His assistance was fundamental in refining the capital and operating cost evaluations in Chapter IV, Sections IV D, and IV G.

C. BREWER & COMPANY, LTD. - Alan Kennett, Former Director of Sugar Technology and Engineering for C. Brewer, contributed substantially to providing an understanding of the operating considerations and costs associated with the production and processing of sugarcane in Hawaii.

CARGILL - Cargill brought an agriculture perspective to the analyses. Loren Luppés and Tom Geiger of Cargill's Ethanol Division were most helpful in providing technical information on manufacturing ethanol from sugars.

EPRI - The Electric Power Research Institute (EPRI) expressed interest in the possibility that Hawaii might serve as a location for a 3,000 to 5,000 acre biomass to energy demonstration site. Jane Turnbull, Project Manager for the EPRI Biomass Program, assembled a technical team to visit Hawaii during May, 1993. The group consisted of Jane Turnbull, Jack Ranney with Oak Ridge National Laboratory, Pam Sydelko with Argonne National Laboratory, and Dave Schlagel with the University of California Agricultural Research Station. These individuals are members of the National Biofuels Roundtable, an organization whose focus is on developing principles for producing biomass energy in the United States.¹³ The group was able to visit several facilities on various islands and meet with a variety of interested parties. During a very short stay, they were able to acquire an overview of the biomass and energy related programs under way in Hawaii and the support for such programs. Interactions during the visit provided a perspective for the evaluations presented in this report. As a result of their interest, EPRI provided financial support to the program.

HSPA - The Hawaii Sugar Planters' Association (HSPA) was exceptionally helpful in providing production data on sugarcane and other potential energy crops. Dr. Robert Osgood and Mr. Lee Jakeway contributed substantial time and information to clarify issues on crops and energy.

2. Subcontractors

A series of subcontracts were awarded in order to address the various tasks associated with this report.

The Hawaiian Sugar Planters' Association (HSPA) was awarded a subcontract to provide a detailed summary of all costs associated with the planting, production, maintenance, harvesting, and transporting of sugarcane and alternative biomass crops which appear to have potential for energy conversion in Hawaii. The HSPA was also asked to provide yield data on all potential energy crops based on previous studies conducted in Hawaii. This information was used to develop much of the discussion in Chapter IV., Section A.-Crop Assessment.

The Hawaii Natural Energy Institute (HNEI), through the University of Hawaii, was awarded a subcontract to provide data, relevant reports, and analysis regarding

biomass to energy crops. HNEI was also responsible for review of data, calculations, and projections developed by the Hamakua Project pertaining to this report. Maps and information, used as the basis for the discussion on land capability were also provided by HNEI.

The Tennessee Valley Authority (TVA) was contracted to evaluate the design and assist in determining the economic performance of alternative technologies for the production of ethanol from biomass. They assisted in the creation of process flow diagrams, and financial projections on capital and operating costs for the various technologies under review. Assistance from TVA enabled the Sustainable Biomass Energy Team to further refine the economic analysis models.

Bechtel Corporation was awarded a subcontract to complete an analysis of the technical and economic performance of approaches to convert cultivated biomass into electrical energy. This analysis provided the fundamental basis of the cost evaluations in the section on electricity options.

-
- 1 Department of Business, Economic Development & Tourism. 1991. *Hawaii Integrated Energy Policy*.
 - 2 Department of Business, Economic Development & Tourism. 1991. *Hawaii Integrated Energy Policy*.
 - 3 Lee, Warren. President, Hawaii Electric Light Company, Presentation to Federal Panel. January 1993.
 - 4 Hawaiian Sugar Planters' Association. Personal communication. 1994.
 - 5 *Honolulu Advertiser*. March 4, 1994.
 - 6 It should be noted that since the DBEDT report was developed in parallel with this study that a common data base was established for both activities. In some instances material presented in the DBEDT report is duplicated in the present study.
 - 7 UNISYN Bioconversion Technology. 1991. *An Inventory of and Potential Uses for Organic Waste in Hawaii*. Draft report to the Department of Business and Economic Development, State of Hawaii, June 1991.
 - 8 Hawaii Natural Energy Institute. 1993. *Investigation of Biomass for Energy Production on Molokai*. September 1993.
 - 9 Department of Business, Economic Development & Tourism. 1993. *Comparative Study of Biomass Yields for Tree and Grass Crops Grown for Conversion to Energy*. November 1993.
 - 10 Department of Business, Economic Development & Tourism. 1994. *Ethanol Production in Hawaii*. Draft report. April 1994.
 - 11 Bulls, Millicent. 1993. Consultation to PICHTR on Biomass Process Costs and Performance. Tennessee Valley Authority. November 1993.
 - 12 Department of Business, Economic Development & Tourism. 1994. *Ethanol Production in Hawaii*. Draft report. April 1994.
 - 13 Electric Power Research Institute. 1992. "EPRI and the National Audubon Society Establish the National Biofuels Roundtable." Announcement. December 1992.

II. CROP AND BIOMASS ASSESSMENT [TASK 2]

Economic and environmental conditions in Hawaii differ from most locations on the U.S. mainland. A year-round growing season, high levels of solar insolation, and a knowledgeable agriculture community offer a unique opportunity to grow biomass with potential for energy production. However, costs of fuel, fertilizer, energy, and labor are greater than in most other locations in the United States. Therefore, the first challenge was to determine what can be grown, or what may be available, that can produce the greatest amount of biomass, appropriate for conversion to fuel or other forms of energy, at the least cost. If the cost of biomass is too high, no technology can establish an industry! Identification and evaluation of biomass feedstocks' availability, suitability, and costs were the objectives of this part of the project.

Crop yield is very location specific since environmental conditions such as sunlight, water, and soil must be consistent with the needs of the crop. Economic factors including production, harvesting, and transportation costs were evaluated. Contiguous land areas of sufficient size within a reasonable distance from the processing plant had to be available. Processing technologies appropriate to converting the biomass to desired intermediates and product forms had to be available. All these factors must be considered in selecting the crop with the most potential for conversion to energy. The potential of any feedstock to be used for energy production depends on:

- The energy content or composition of the crop;
- Yield of biomass per harvest;
- Time required to produce a harvestable crop;
- Delivered cost of the biomass to the plant;
- Cost of processing the biomass material to the desired product forms; and
- Efficiency of the conversion technology on the particular feedstock.

The selection of crops or alternative sources of biomass to be evaluated was based on the following criteria:

- Production or availability has been demonstrated in Hawaii;
- Production requirements and yields are well known;
- Energy or lignocellulose content (cellulose, hemicellulose & lignin content) is consistent with objectives; and
- Yields and production costs are consistent with objectives.

A. CROP YIELD AND COMPOSITION

In order to evaluate the potential of feedstocks for production of electrical energy or liquid fuel, data on the energy content and content of sugars and sugar containing compounds that can be processed was obtained from technical publications and direct discussions with researchers who had unpublished information on the composition of promising feedstocks. The promising crops and materials and their corresponding content of cellulose, hemicellulose, and lignin (dry weight basis) are shown in Table II-1.

TABLE II-1
COMPOSITION OF POTENTIAL CROPS AND WASTE MATERIALS
(% DRY WEIGHT)

Biomass Source	Sugars	Cellulose	Hemicellulose	Lignin	Other
Bagasse ^{1, 2}	3	38	27	20	12
Eucalyptus grandis ^{3, 4}	--	38	13	37	12
Eucalyptus saligna ⁵	--	45	12	25	18
Leucaena leucocephala ⁶	--	43	14	25	18
Molasses ⁷	61	--	--	--	39
Napier grass ⁸	--	32	20	9	39
Sweet sorghum ⁹	34	36	16	10	3
Sugarcane hybrids ¹⁰	28	37	14	15	6
Sugarcane (whole plant) ¹¹	33	25	17	12	13
Sugarcane leaves ¹²	--	36	21	16	27
Sugarcane ("prepared" cane) ¹³	43	22	15	11	9
Municipal Solid Waste ¹⁴	--	33	9	17	41
Newspaper	--	62	16	21	1

As can be seen in Table II-1, some non-crop materials also show promise. Municipal solid waste (MSW) and newspaper are exceptional sources of cellulose and hemicellulose and will be discussed later in this chapter.

B. SUGARCANE AS A SOURCE OF BIOMASS

At one time, there were almost 200,000 acres of sugarcane cultivated in Hawaii.¹⁵ Considering the historic significance and extensive local experience and success with growing this crop, it was not surprising that the question of continuing to cultivate sugarcane to produce ethanol and electricity at Hamakua and other locations would be of significant interest.

1. Definitions

The following definitions are taken from the *HSPA Sugarcane Factory Analytical Control Methods Manual*, a standard in the Hawaiian Sugar Industry:¹⁶

Field Cane— Crop material as harvested, including field trash.

Prepared Cane— Harvested material after preparation for extraction, including field trash not removed in the cleaner and adhering water.

Net Cane— The clean cane stalks, from which sugar can be recovered, from the stool to the growing point (the region at the distal end of the stalk where new leaves and new internodes are being formed by cell division).

96DA Sugar— The raw unrefined sugar resulting from the milling process.

2. Potential Biomass Yield From Sugarcane

Sugarcane is considered to be among the highest yielding crops. However, the modern hybrids of sugarcane in commercial production are selected for high sugar content at some detriment to the potential for maximum biomass production. Sugarcane grown exclusively for dry matter production for biomass would require the use of higher fiber varieties and changes in the cropping cycle and harvesting methods. HSPA estimates that yield of dry biomass from Hawaii's sugarcane crop could be increased by 30 to 40 percent with such changes resulting in recovered biomass yields on the order of 20 to 22 dry matter tons per harvested acre per year. This could result in approximately 160 wet weight tons of biomass per harvested acre.¹⁷

In 1991, the average net cane yield per acre was reported to be 86.4 tons per harvested acre (wet weight basis). The average prepared cane yield for the Hawaii's sugar industry was 1.2 times this amount per acre or approximately 104 tons of prepared cane per harvested acre. Field cane reported in industry figures averaged about 124 tons per acre which usually represents burned, standing cane (a significant amount of soil and rocks may be included in this figure).

Hawaiian cane production is considered to be among the highest in the world.¹⁸ Data for the years 1981 through 1992 is presented in Table II-2 and Figure II-1. For the purposes of this study, the biomass production from sugarcane was estimated from unpublished sugar industry statistics. Biomass production for the sugar industry for these years averaged approximately 14 dry matter tons per acre per year.¹⁹

TABLE II-2
HAWAII SUGAR INDUSTRY STATISTICS*

YR	Acres in crop	acres harvested	Crop time	96 DA sugar produced (total)	Prep'd cane, wet	96 DA sugar	Fiber produced	Molasses solids	Dry matter produced **	Dry matter produced	Est. unburned cane dry matter
			yr	tons	t/a/hrv	t/a/hrv	t/a/hrv	t/a/hrv	t/a/hrv	t/a/yr	t/a/yr
81	216,100	97,570	2.2	1,047,520	101	10.7	14.9	2.7	28.3	12.8	16
82	204,749	89,260	2.3	982,910	111	11.0	17.4	2.8	31.2	13.6	18
83	194,258	92,820	2.1	1,044,190	108	11.2	15.6	2.8	29.7	14.2	18
84	188,396	89,540	2.1	1,061,814	108	11.9	15.8	3.0	30.6	14.6	19
85	187,858	83,029	2.3	1,012,249	112	12.2	17.0	2.8	32.0	14.1	18
86	184,181	83,584	2.2	1,042,452	117	12.5	17.8	3.0	33.3	15.1	19
87	180,966	79,497	2.3	979,209	120	12.3	18.4	3.0	33.7	14.8	19
88	177,693	78,862	2.3	928,195	113	11.8	18.6	2.9	33.3	14.8	19
89	170,813	74,660	2.3	871,614	112	11.7	17.2	2.7	31.5	13.8	18
90	162,000	71,999	2.3	819,632	108	11.4	16.5	2.6	30.5	13.6	18
91	155,600	69,439	2.2	724,100	102	10.4	15.9	2.5	28.8	12.9	17
92	—	61,734	2.2	652,304	105	10.6	16.8	2.7	30.1	13.5	18
HIGH	—	97,570	2.3	1,061,814	120	12.5	18.6	3.0	33.7	15.1	19
LOW	—	61,734	2.1	652,304	101	10.4	14.9	2.5	28.3	12.8	16
AVG.	—	—	2.2	—	110	11.5	16.8	2.8	31.1	14.0	18

* From production statistics of Hawaii's Sugar Industry as reported to the USDA and DOA, and unpublished HSPA data

** Total dry matter is the sum of sugar, fiber, and molasses soluble solids produced.

FIGURE II-1
SUGARCANE PRODUCTION IN THE STATE OF HAWAII, 1981-1992

Sugarcane yield trials are continuously installed and harvested by the HSPA. A summary of these data is out of the scope of this report; however, a small sampling of some recent trials reported in the *HSPA Variety Report Series* shows the type of data available and the procedure for calculating biomass from the data gathered. The best estimate of actual commercial yields for sugarcane in Hawaii come from the sugar factory records. Biomass produced is estimated by summing the production of 96DA sugar (although, to be more accurate, 96DA sugar should be reduced by 5% to reflect true commercial sugar production), fiber, and the dry solids in molasses.

Sample Variety Test - Variety H73-6110 planted on Maui and harvested at 23.6 months yielded 132.5 tons of net cane per harvested acre (fresh weight basis). The fiber as a percent of cane (fresh weight basis) was 13.1% and the yield of refractometer solids as a percent of cane (fresh weight basis) was 20.6%. Adding the fiber percent and the refractometer solids percent provides a good estimate of percent dry weight. In the Maui case, the dry matter is estimated to be 33.6% (taken from the fiber and refractometer solids); therefore, the potential yield of dry matter produced in this test was $(132.5 \times 0.336 = 44.5)$ tons per harvested acre). Since the crop was grown for 23.6 months, the dry matter produced per month was 1.89 tons per acre per month. Annualized, the yield of dry matter is, therefore, 22.7 tons per acre per year. Commercial yield, using the 25% discount is estimated to be 17.4 dry matter tons per acre per year. The conversion from gross acres to net acres is performed as part of the model for the variety test yield calculations.

Another example from Ka'u shows Variety H82-1600 planted at Ka'u Sugar Company and harvested at 28 months, yielded 138 tons of net cane per harvested acre (fresh weight basis). The fiber was 11.8% and the refractometer solids were 17.5 percent of the cane fresh weight. Therefore, dry matter was estimated to be 29.3%. The cane yield multiplied by the estimated dry weight percent gives a dry matter yield of 40.4 tons per harvested acre. The dry matter produced is therefore, 1.44 tons per acre per month. Annualized, the yield is 17.3 dry matter tons per acre per year. Variety tests are burned before harvest; therefore, yields of whole cane are higher than reported in the variety tests. However, not all the additional biomass can be recovered in a real commercial harvesting operation. Commercial yield of dry matter at this location is estimated to be 13 tons per acre per year after applying the 25% discount.

3. Sugarcane Components and Products

Stalks. "Prepared cane" is primarily the stalk of the sugarcane plant, with some leaves and some water remaining from the washing process. Sugar (sucrose), the primary commercial product of the sugar industry, is contained in the stalk. The sugarcane stalks are processed to sugar, bagasse, and molasses. Most of the raw sugar is sent to California to be refined; most of the bagasse is burned in boilers to produce process steam and electricity; and most of the molasses is shipped to California and sold as cattle feed.²⁰

Leafy trash. Prior to harvesting the sugarcane, the fields are usually burned (weather and other conditions permitting) to reduce the harvesting, transporting,

and processing costs associated with hauling in excess material (primarily leafy trash). Most reported amounts of "field cane" and "prepared cane" do not include the total amount of biomass that was available before the fields were burned.

4. Yield Potential from Unburned Fields

The Hawaii sugar industry burns its fields, whenever possible, prior to harvesting so field cane would not include the potential amount of biomass that would be there if sugarcane was left unburned. Studies have been performed by HSPA on the effects to a sugar factory should sugarcane be harvested unburned. Sloane and Rhodes, in 1972, reported that harvesting and hauling requirements would go up significantly coupled with a reduction in factory processing rates and sugar quality.²¹ An internal sugar industry study performed in 1983 showed that ceasing burning of sugarcane fields would be economically distressing to the sugar industry despite increased revenue from power sales.

A study of the composition of unburned cane performed by Kinoshita in 1988 showed that the amount of bagasse would increase 54% over burned cane. Twenty-one plots of unburned cane, on eleven plantations, were hand-cut prior to field burning to determine total biomass available in unburned cane. Figure II-2 shows reported and projected yields for burned and unburned sugarcane.

Using the Hawaii sugar industry average net cane yield of 86.4 tons per harvested acre, and assuming that net cane is presently 30% dry matter (=25.9 dry matter tons), the amount of dry matter that can be commercially produced per acre is projected to be about 39 tons per harvested acre.

Santo reported, in 1991, that the amount of additional dry matter expected from agricultural residue left behind after hand harvesting in unburned conditions would be about 12 metric tons per hectare for one year cane (5.4 tons per acre-year). When added to the dry matter production from two year net cane, this would yield approximately 36 tons dry matter per harvested acre.

Assuming the potential biomass dry matter yield is about 35 tons per harvested acre for a two-year sugarcane crop, the potential increase in biomass in unburned sugarcane fields would be about 35% $[(35-26)/26*100]$. This is equivalent to 17.3 tons per acre-year for commercial sugarcane. The actual amount of dry matter recovery will more than likely be less because of fiber losses experienced during harvesting, transporting, and pre-processing as discussed earlier. Figure II-2 shows reported and projected yields for burned and unburned sugarcane.

FIGURE II-2
SUGARCANE COMPONENT YIELDS

5. Yield Potential from Irrigated Versus Unirrigated Fields

The distinction must also be made between irrigated and unirrigated plantations because operations are quite different for the two. Unirrigated, rain-fed plantations do not require irrigation from an established source of water which, for irrigated plantations, represents an additional cost. Sugar yields are normally lower on a per acre-month basis for unirrigated plantations. Historically, in Hawaii, unirrigated plantations have usually shown higher overall operating costs compared to irrigated plantations. This is attributed, in part, to the lower sugar yields and higher productions costs of mechanized field equipment which in most cases has to be track-type-tractors due to the steep terrain and wet field conditions associated with unirrigated plantations (the fields are generally wetter in unirrigated conditions due to the heavy rains in these areas). However, if the Hawaii sugar industry did not provide its own power to pump its irrigated water and/or it had to pay "market" rates for irrigation water, the situation would be reversed.

6. Cost of Sugarcane Production

Cost data was obtained for two commercial sugarcane grower/processors located on the island of Hawaii. Production cost data for 1991 was used as this represented the most up-to-date costs for normal operations in this region.²² The two plantations analyzed were unirrigated plantations and were very similar in terms of sugar production although operations were quite different because of terrain and weather conditions which are known to have significant affects on the cost of operations. The combined costs for the two plantations studied should represent mid-range costs for an unirrigated plantation on the island of Hawaii under conditions such as those

experienced in 1991. It should be noted that, as illustrated in Figure II-1, statewide reported sugarcane and sugar yields in 1991 were lower than the "average" for the 1981-1992 period. This was true for the island of Hawaii as well (e.g. in 1985, a more "average" year, the Hawaii island plantations harvested 28,673 acres and produced 319,441 tons of sugar, or an average of 11.1 tons per acre. In 1991, the Hawaii island plantations harvested 18,134 acres and produced 181,825 tons of sugar, or an average of 10.0 tons per acre.) Since costs for a given acre are generally the same regardless of yields, years of relatively low yields show a correspondingly higher cost per ton.

It should also be noted that these costs are not representative of other sugar plantations operating in Hawaii. The range of production costs varies considerably from one plantation to the next, especially between irrigated and unirrigated plantations. The average cost to produce a ton of sugar in 1991 for the Hawaii sugar industry was reported to be \$417 dollars per ton of 96DA sugar which includes by-product credits for molasses and power revenue. The average production cost per ton of sugar for all plantations operating on the Big Island in 1991 was \$455 per ton of sugar.²³ This reflects the higher costs usually associated with operating irrigated plantations as discussed earlier.

A summary of the production cost information adjusted to reflect the cost of prepared cane is given in Table II-3 for the 1991 production year. Cultivation, harvesting, transporting, and preparation costs with appropriately applied general and administrative costs are itemized for labor, materials, equipment service charges, and other costs. Costs not pertaining to producing sugarcane for strictly biomass (such as ripener application costs which maximizes sucrose production and sugar/molasses marketing expenses) were not included. Production costs and credits were excluded for the boiling house and power generation, respectively, since it was not assumed that the infrastructure from an existing sugar factory would be available. If power must be purchased from the utility to run operations, costs would, in all probability, be higher than those presented here. This would be especially true at locations where irrigation water must be pumped.

The accounting system utilized by the two sugar companies studied, provides cost data which includes costs for other operations such as the cultivation of macadamia nuts. This made it difficult to delineate actual labor, materials, and other charges as they applied to these two specific sugarcane operations.

The values given for each column listed in Table II-3 reflect our best ability to extract these numbers for sugar operations alone. However, the values given for the column listing net operating expense represents actual costs due to sugarcane operations. This data was then utilized to make cost comparisons.

TABLE II-3
PRODUCTION DATA FOR TWO HAWAII PLANTATIONS

	Labor (5)	Materials	Equipment / Service Charges (6)	Other Direct Costs (7)	Total Indirect Costs (8)	TOTAL NET OPERATING EXPENSES (9)
CULTIVATION:						
Land Preparation	87,348	75	307,943	14,753	40,488	450,607
Planting	219,328	1,493	725,145	4,281	51,660	1,001,907
Ratoon Preparation	63,200	190	207,746	13,618	33,552	318,306
Ratoon Replanting	424,673	7,010	1,413,173	11,942	12,600	1,869,398
Weed Control	652,419	1,482,833	340,210	95,263	102,372	2,673,097
Fertilization (1)	106,556	3,709,869	232,238	315,651	51,011	4,415,325
Agriculture Overhead	847,056	87,923	91,745	233,116	125,632	1,385,472
HARVEST/TRANSPORT:						
Mechanical Harvesting	909,291	1,165	2,595,358	93	353,416	3,859,323
Trucking	1,373,070	4,692	3,682,805	10,574	190,462	5,261,603
General	550,072	22,106	129,216	4,911	40,454	746,759
OTHER FIELD:						
Road Maintenance	1,270	56,968	1,036,023	-2,048	221,811	1,314,024
CANE PREPARATION:						
General (2)	220,783	15,781	227,978	8,849	93,283	566,674
Millyard	201,302	76,427	381,481	3,933	59,739	722,882
Cleaning Plant	282,374	394,597	331,285	11,154	160,630	1,180,040
Other Factory	143,157	310,008	153,203	30,432	68,574	705,374
APPLIED G&A	2,510,021	115,117	-1,081,702	6,447,522	1,990,574	9,981,532
TOTAL COSTS (4)	8,591,920	6,286,254	10,773,847	7,204,044	3,596,258	36,452,323

Table II-3 notes:

- (1) Ripener application cost excluded @ \$40 dollars per harvested acre
- (2) Expenses prorated for cane preparation only, includes 15% of crushing plant expenses (fire room and boiling house/laboratory expenses excluded)
- (3) Expenses prorated according to combined field and factory cane preparation cost only
- (4) Total excludes sugar and molasses marketing expense
- (5) All costs in columns include expenses from other operations such as macadamia nut, etc.
- (6) Includes equipment R&M costs including repair labor, fuel and lubrication, equipment rental, and service credits from other operations
- (7) Outside services, employee benefits, corporate service charge and other costs
- (8) Taxes, insurance, depreciation and amortization, and other equipment/land rental costs
- (9) Represents the true operating cost due to sugarcane operations

The basis for comparison used by the Hawaiian sugar industry is dollars per ton of sugar. Production figures for sugar and types of cane were taken from the HSPA Summary of Factory Results (an internal report distributed within the sugar industry) for 1991. The results shown in Table II-3 indicate that, for the two

plantations considered, the cost of producing sugar exceeds \$360 dollars per ton. From production data provided for net cane and prepared cane, costs are about \$37 dollars per ton of net cane and \$31 dollars per ton of prepared cane. This results in a production cost per ton of dry biomass for sugarcane of \$115 dollars for delivered prepared cane. Once again, these costs are not considered to be representative of the Hawaii sugar industry costs on the whole.

Production costs per harvested acre and per acre-year are also presented so that comparisons can be made with other published data. Information published by HNEI in the report "Investigation of Biomass for Energy Production on Molokai" indicated that total delivered cost for sugarcane for an irrigated plantation was \$1,367/acre-year.²⁴ By comparison, the cost presented in Table II-3 is \$1,381/acre-year which includes processing costs for prepared cane. Sugarcane production cost figures published by the USDA Economic Research Service for operating year 1991 showed that, for Hawaii, average growing cost per net ton of sugarcane was about 35 dollars excluding cane transportation and processing to prepared cane costs. Using the USDA figures for transportation costs of \$2.86 per ton and processing costs determined from Table II-3 of \$3.18 per ton, the adjusted USDA production costs would be over \$40 per ton net cane which compares to \$37 per ton net cane in Table II-3. From these comparisons, it is possible that the cost of production figures presented in Table II-3 might actually be a low estimate of what the projected production costs would be for a sugarcane biomass to energy operation on the island of Hawaii, especially when considering the rugged terrain of the Hamakua Coast.

Costs will be affected significantly by the amount of dry matter produced per acre which has not been the emphasis of the sugarcane breeding program in Hawaii to date. With more emphasis on fiber production, for example, the total dry matter production for sugarcane could be increased. This approach, often referred to as the "energy cane" concept, implies harvesting the total amount of biomass produced by the sugar crop including tops and leaves which are currently burned before harvest.

7. Sugarcane Hybrids ("Energy Cane")

One possible approach in the development of sugarcane as a feedstock for energy and fuels, is the development and improvement of varieties of sugarcane optimized for the production of all components of the biomass – including sucrose, cellulose, hemicellulose, and lignin – rather than optimized for the production of sucrose alone. Several varieties of sugarcane, including varieties for energy production, have been grown and evaluated in Hawaii.²⁵

C. ALTERNATIVE CROPS

The Hawaii sugar industry has been in existence for over 150 years and has detailed cost information for growing and processing sugarcane. The Hawaiian Sugar Planters' Association (HSPA) had previously developed information on alternative crops and was asked to develop a report to identify production costs and yields for the various biomass crops under consideration. Their report provided the foundation of the material found in this section.

A short list of crops and agricultural practices that may be appropriate under the physical and economic conditions that exist in the Hamakua/Hilo region are identified in Table II-4.

1. Eucalyptus and Leucaena

Eucalyptus and leucaena are tree crops that show potential for biomass production in Hawaii. Production has been demonstrated at several locations in Hawaii.²⁶ A range of experimental and projected commercial yields for eucalyptus and leucaena are shown in Figure II-3 below.

The State of Hawaii Department of Business, Economic Development and Tourism has sponsored several tree biomass tests.^{27,28} Two categories of tree yield tests were conducted in five locations. During small plot, closely-spaced species trials, yields of dry biomass were determined for the Kilohana and Mountain View sites on the Big Island. These trials were part of the HSPA Biomass to Energy Project. The highest yielding trees were *Eucalyptus grandis*, *Eucalyptus urophylla*, and *Acacia mearnsii*. Averaged over two sites, yields for these species were: *E. grandis* : 15.9 dry matter tons per acre per year; *E. urophylla* : 18.6 dry matter tons per acre per year; and *A. mearnsii*: 17.1 dry matter tons per acre per year. Using the 25% discount, commercial production of trees (averaged) on a gross acre basis is estimated to be about 13 dry matter tons per acre per year. Converted to a net acre basis, the commercial yield is expected to be approximately 11 dry matter tons per acre per year. Yields for the individual tree species are given in Table II-4.

Large plot demonstration trials were also conducted as a part of the HSPA Biomass to Energy Project. The yield of dry biomass from the highest yielding trees harvested from large replicated plots at five sites was approximately 9 dry matter tons per acre per year for *E. grandis* at the Mountain View site, approximately 14 dry matter tons per acre per year for *E. urophylla* at the Honokaa site, approximately 11 dry matter tons per acre per year for *Leucaena leucocephala* at the Puunene site, approximately 9.5 dry matter tons per acre per year for *L. leucocephala* at the Hoolehua site, and approximately 8 dry matter tons per acre per year for *L. leucocephala* at the Kilohana site. Yields for the best performing trees averaged over the five sites was about 10 dry matter tons per acre per year. Commercial yield on a gross area basis was estimated to be about 8 dry matter tons per acre per year. On a net area basis, the commercial yields are expected to be about 6.5 dry matter tons per acre per year. Yields for individual species are given in Table II-4.

One of the best attributes of tree crops for biomass production is their adaptability to upland rain-fed sites not well suited for other crops. Biomass stored in trees is directly usable after felling and chipping, since it has a higher dry matter content. Grass crops require natural drying or dewatering in a mill to produce a suitable boiler feed stock at about 50% moisture. The yield potential for trees in rain-fed sites can be substantially improved by first selecting elite trees in existing plots and cloning them by either conventional procedures or by micropropagation. These selected trees along with germplasm from other sources could be the basis for a breeding program with the aim of producing more productive trees. The

development of higher yielding trees will substantially reduce the cost per ton of tree biomass. Based on work in Brazil, the HSPA is confident that a considerably greater yield from trees can be obtained by simply selecting elite types and planting vegetatively propagated cuttings in commercial fields. In the future, production from 12 to 14 tons of dry matter per acre may be achievable commercially.²⁹

The costs of production for eucalyptus were primarily developed at BioEnergy Development Corporation, a subsidiary of C. Brewer Company, in Hilo, Hawaii. This information was extracted and formed the basis of a spreadsheet model for eucalyptus production costs for the island of Hawaii. The costs were modified by the HSPA to include additional costs of production such as land costs, other field costs (i.e. road maintenance, etc.), general and administration costs, and research costs. Costs are summarized in Table II-4 below.

2. Napier Grass (*Banagrass*)

One of the "energy grasses" which has been demonstrated and studied in Hawaii is napier grass (banagrass, also commonly discussed as a potential energy crop, is a variety of napier grass). A range of experimental and projected commercial yields for napier grass is shown in Figure II-3 below.

The yield potential of napier grass (banagrass) was studied in two types of experiments: an environment by yield study including two ratoon crops; and a longer term four year yield trial at a single location on Molokai. The environment by yield study for napier grass was conducted by HNEI. This study evaluated the yield potential of napier grass in five locations. The average yield of biomass in the combined plant and ratoon crops was 31.8 dry matter tons per acre per year, demonstrating the high yield potential of this crop. Yield in the ratoon crop, primarily summer-grown, was 3 times the yield in the plant crop, primarily a winter-grown crop. Yield in the ratoon crop was double that of sugarcane grown in the same experiments. After applying the 25% discount, commercial yield on a gross acreage basis was estimated to be approximately 24 dry matter tons per acre per year. Conversion to a net acre basis results in an estimated yield of approximately 20 dry matter tons per acre per year (see Table II-4).

TABLE II-4
EXPERIMENTAL BIOMASS YIELDS AND CALCULATIONS OF EXPECTED
COMMERCIAL YIELDS (1)

BIOMASS CROP	Experi- mental Yields	Estimated Commerci al Yields	Estimated Commerci al Yields	Harvest Cycle	Estimated Commerci al Yields
	dry tons/gross acre/yr	dry tons /gross acre/yr (2)	dry tons/net acre/yr (3)	years	dry tons gross yield/ harvest
Sweet Sorghum (6 cult.; avg. 2 crops)	23.2	17.4	14.8	0.38	6.67
Sweet Sorghum (MN 1500; 2 crops)	32.7	24.5	20.8	0.38	9.41
Sorghum-Sudan grass	17.6	13.2	11.2	0.33	4.30
Corn (Avg. 2 crops)	20.0	15.0	12.8	0.25	3.82
Alfalfa (Avg. of 2 Experiments; 22 harvests)	11.8	8.9	7.5	0.08	0.73
Napier grass (Avg. 2 crops; 5 locations)	31.8	23.9	20.3	0.55	13.07
Napier grass (Avg. 7 crops; 1 location)	19.6	14.7	12.5	0.67	9.91
Eucalyptus grandis (close spacing trial)	15.9	11.9	10.1	2.00	23.85
Eucalyptus urophylla (close spacing trial)	18.6	14.0	11.9	2.00	27.90
Acacia mearnsii (close spacing trial)	17.1	12.8	10.9	2.00	25.65
Eucalyptus grandis (large plots - Mt. View)	9.1	6.8	5.8	5.00	34.13
Eucalyptus urophylla (large plots - Honokaa)	14.2	10.7	9.1	5.00	53.25
Leucaena leucocephala (large plots - Maui)	11.0	8.3	7.0	5.00	41.25
Leucaena leucocephala (large plots - Molokai)	9.6	7.2	6.1	5.00	36.00
Eucalyptus urophylla (large plots - Kauai)	7.8	5.9	5.0	5.00	29.25
Sugarcane Maui (from HSPA Variety Tests) (4)	22.2	16.7	16.7	1.95	32.39
Sugarcane Ka'u (from HSPA Variety Tests) (4)	16.7	12.5	12.5	2.33	29.17
Sugarcane (5 locations; 2 harvests)	19.5	14.6	14.6		
Commercial Sugarcane (recovered biomass) (5)					
Commercial Sugarcane (recovered biomass)1991			14.1		
Commercial Sugarcane (recovered biomass)1990			14.2		
Commercial Sugarcane (recovered biomass)1989			14.7		
Commercial Sugarcane (recovered biomass)1988			15.2		
Commercial Sugarcane (recovered biomass)1987			15.7		

Notes:

(1) Information taken from HSPA experiments (1982-1993).

(2) Experimental Yields Discount (%) 25%

(3) Gross to Net Acreage Conversion (%) 15%

(4) Based on HSPA net acre (Sq. Ft.) 37,026

(5) Includes sugar, fiber, soluble molasses solids. Yields based on crop age rather than crop rotation time. Commercial Sugarcane Data obtained from HSPA reports and unpublished HSPA reports.

The long-term napier grass study on Molokai was supported with funding from DBEDT. In this study, napier grass vs. banagrass was grown on Molokai for 4.3 years and harvested 7 times without replanting. The average yield obtained over this

period was 19.6 dry matter tons per acre per year. The expected commercial yield on a gross acreage basis was estimated to be approximately 15 dry matter tons per acre per year. Conversion to a net acre basis results in an estimated commercial yield of 12.5 dry matter tons per acre per year (see Table II-4).

The primary constraints to biomass production with banagrass is the propensity to flower, thus limiting winter growth potential. Breeding and selection on non-flowering or reduced flowering types would be a primary research goal. Another research project which could result in increased winter yields would involve the treatment of napier grass with the growth regulator gibberellic acid. Gibberellin has been successfully applied to sugarcane for increasing winter growth and ethephon is presently used commercially to inhibit sugarcane flowering. Both gibberellin and ethephon have considerable potential to increase the biomass production of grass crops in the winter.

The HSPA and the HNEI have estimated the cost of production to be lower than for sugarcane owing to its ability to produce a large number of high yielding ratoon crops and its greater yield potential as a result of greater partitioning of its biomass to fiber which is more efficiently recovered than the soluble carbohydrates produced by sugarcane. The cost of production of napier grass vs. banagrass for an irrigated site on Molokai was estimated in a collaborative project including HSPA, HNEI, and Hawaiian Electric Company (HECO) personnel. These costs, modified to reflect different assumptions, are summarized in Table II-5.

3. Sweet Sorghum and Sweet Sorghum-Sudan Grass Hybrid

Sweet sorghum is currently grown in small quantities in Hawaii. Although not studied as extensively recently as some other potential energy crops (e.g. napier grass, eucalyptus, and leucaena), it has demonstrated good yields in Hawaii and elsewhere, its sucrose content makes it attractive from an ethanol production standpoint, and its protein content could provide an animal feed by-product of some value. A range of experimental and projected commercial yields for sweet sorghum is shown in Figure II-3.

In 1982, preliminary biomass trials were cooperatively established by the USDA and the HSPA at the HSPA Kunia substation, a leeward, high sunlight location with deep soil and adequate irrigation. Kunia is considered a prime agricultural location. In these trials, six cultivars of sweet sorghum produced an average summer-grown yield of 14.1 tons per acre dry matter in 144 days (See Table II-4). A ratoon crop of these cultivars produced only 3.9 tons per acre when grown during the winter (only 28% of the summer yield).³⁰ The extreme yield difference for the summer and winter-grown crops of sweet sorghum is an important consideration for biomass production in Hawaii. The combined winter and summer yield of the sweet sorghum produced in 283 days was about 18 tons of dry matter per acre. On an annualized basis, the yield is estimated to be approximately 23 tons per acre per year. One cultivar of sweet sorghum, MN1500, yielded over 40 percent more than the average of the other six cultivars studied. Since these yields are from small, hand harvested plots, they were discounted by 25% to estimate commercial yield of

mechanically harvested biomass and further discounted by 15% to account for the difference between gross and net acreage.

Forage Project. In 1984, the HSPA was supported with funding from the GACC to conduct several large scale forage yield trials with corn and sorghum-sudan grass hybrids. The work was conducted in the Ewa region of Oahu in shallow soil. The site was considered marginal for commercial sugarcane production. Like the earlier sweet sorghum trials, HSPA grew both a summer plant crop and a winter ratoon crop of sorghum-sudan grass hybrid. The summer yield was 4.3 dry matter tons per acre and the winter crop yield was 2.6 dry matter tons per acre (only 60% of the summer yield). The total time of growing the sorghum-sudan grass crops was only 144 days. This results in an annualized yield of 17.6 dry matter tons per acre per year. If this is discounted by 25%, the expected commercial yield for this location would be 13.2 dry matter tons per acre per year (Table II-4).

4. Corn

Corn experiments at the same location yielded 12.9 tons per acre in 185 days not including a winter cycle. The annualized yield including a winter cycle at 50% of the summer yield would be 20 dry matter tons per acre per year. Discounting this by 25% would yield a commercial estimate of 15 dry matter tons per acre per year. Discounting these yields further to account for differences in gross versus net acres would result in estimates of commercial production for sorghum-sudan grass and corn to be 11.2 and 12.8 tons per acre per year respectively (see Table II-4).

5. Alfalfa

Alfalfa yield potential was studied over a three year period, from 1985 to 1987, by the HSPA. The data is included in this report for comparison with more traditional biomass crops. Alfalfa yield was also substantially affected by the season in which the harvest took place. Yield was reduced by 50% during the winter months compared to peak summer yields. The most productive variety, FLA 77, averaged over two experiments, where harvests were made monthly for two years, yielded about 12 tons dry matter per acre per year. Applying the 25% discount to these yields results in an expected commercial yield on a gross acre basis for alfalfa of about 9 tons dry matter per acre per year. Further discounting for gross to net acreage yields an expected commercial production of 7.5 dry matter tons per acre per year (see Table II-4).

Experiments on alternative crops were usually installed on prime agricultural land and the yield data was obtained from hand harvested experimental plots. As a result, higher yields than could be expected from commercial operations are obtained. To adjust, HSPA initially discounts the yields obtained in experimental plots by 25% to account for selection of prime sites for experimental plots, losses in mechanical harvesting, and other production losses. An additional discount of 15%

is made to account for gross versus net acres under production, where gross area is occupied by in-field roads, irrigation equipment, etc. (see notes, Table II-4 above).

Yield data is presented for a wide variety of crops grown under widely varying conditions in Table II-4. After discounting for the above mentioned losses, to reflect expected commercial production, crop yields are annualized and presented on both experimental and an adjusted basis. The crops with the highest yield potential were the grasses including sugarcane, sweet sorghum, and napier grass. For comparison, biomass yields for the commercial sugarcane crops harvested between 1986 and 1991 are included. Yield data has been presented on a dry weight basis in short tons (2,000 lbs.) per acre, unless otherwise stated.

A word of caution regarding comparisons of crop yields. The choice of biomass crop, crop yields, and delivered costs is highly site-specific. For example, some crops do better in sunnier, warmer locations while others flourish in cooler, wetter conditions. Although grasses generally achieve higher dry matter yields per acre per year than do trees, in specific locations (the eucalyptus plantings in Hamakua, for example) the trees out-performed the grasses. This illustrates the importance of using these estimates as a general guide from a statewide perspective rather than as an absolute relationship for all sites.

FIGURE II-3
EXPERIMENTAL AND PROJECTED YIELDS FOR BIOMASS CROPS

6. Production Costs

Estimated cost projections for selected potential alternative energy crops are shown in Table II-5. The crops included are napier grass (banagrass), haole koa (*Leucaena leucocephala* - K636), and *Eucalyptus*. Costs of production are estimated for both irrigated and rain-fed sites. For the purposes of these analyses, the land costs were kept constant at \$100 dollars per acre per year. This represents the cost of renting the

land. General and administration was set at 10% of overall operating costs. It should be noted that labor costs and harvesting practices differ from conventional sugarcane operations for these alternative energy crops which is reflected by the lower projected delivered costs per dry ton of biomass. The cost of water, set at \$0.10 per 1000 gallons, represents a considerable hurdle for production of biomass in areas requiring irrigation. This water cost can partially be offset by higher yield potentials for irrigated lands, however. Water costs vary substantially by site and may be charged at a low internal rate for companies who have developed their own water supply and delivery system or at a very high rate for new operations required to purchase water or install new irrigation systems. Actual water costs for specific sites must be determined.

TABLE II-5
ESTIMATED COSTS OF BIOMASS FEEDSTOCK AT THE CONVERSION PLANT
(1)

COST CENTER	Sugar-cane	Napier grass	Leucaena	Sugar-cane	Napier grass	Eucalyptus	Eucalyptus (2)
(\$/acre)	Irrigated	Irrigated	Irrigated	Rainfed	Rainfed	Rainfed	Rainfed
Land Holding	100	100	100	100	100	100	100
Soil Preparation	53	27	5	53	27	49	42
Planting/Ratooning (Includes Nursery)	135	67	16	135	67	16	22
Weed Control	92	46	64	92	46	41	33
Irrigation	260	371	328	0	0	0	0
Fertilizer	115	148	40	115	148	40	54
Other Field	179	89	89	179	89	30	30
Harvesting	123	115	238	123	115	251	209
Hauling	155	180	36	155	180	48	40
G&A (Field) (3)	121	114	92	95	77	58	53
Total Delivered Costs (\$/acre)	1,333	1,257	1,008	1,047	849	633	583
Total Delivered Costs (\$/Dry Ton)	83	70	101	75	57	74	69
Assumptions:							
G&A (Field)	10%	10%	10%	10%	10%	10%	10%
Harvests Per Planted Crop	1	7	4	1	7	1	1
Harvests Per Year	0.5	1.5	0.2	0.5	1.5	0.2	0.17
Average Crop Cycle (Mo.)	24	8	60	24	8	60	72
Dry Matter (tons/acre/yr)	16	18	10	14	15	8.5	8.5
Irrigation Costs (\$ / 1000 gal)	0.1	0.1	0.1		0	0	0
Irrigation Reqmt (gal/acre/day)	6,000	6,000	5,000		0	0	0

Notes:

- (1) Modified From Hubbard And Kinoshita (1993) Investigation of Biomass for Energy Production on Molokai
- (2) Modified from BioEnergy Development Corporation's work on Eucalyptus
- (3) G&A estimated at 10% of total cost

D. WASTES AS A SOURCE OF BIOMASS

Organic wastes and municipal solid wastes (MSW) also represent targets of opportunity. Agricultural wastes, green wastes from landscaping and households, and materials

directed to landfills contain significant amounts of cellulose, hemicellulose, and lignin. Diversion of these materials from landfills to energy production could make raw material available at a reasonable cost (in some instances subsidized by tipping fees), and contribute to reductions in the waste disposal problem.

In a sense, wastes such as paper and MSW will be available as long as there is a population and for this reason should be considered as sustainable as – and may be even more dependable a supply source than – cultivated biomass. These sources can also be considered as renewable since they are originally derived from crops and trees.

1. Organic Material

As described earlier, an inventory of organic material produced in the state of Hawaii was carried out in 1991. This survey provided an overview of material in the state and identified the amounts available by county and region. A summary of the inventory results is presented in Figure II-4 below.

2. Municipal Solid Waste and Organic Waste

a. Composition

The composition of MSW varies substantially depending on location. In Hawaii, MSW contains almost 32% green material from yards, hotels, golf courses, parks, and construction sites. Paper and food wastes also contain significant amounts of lignocellulosic material. A detailed analysis of wastes deposited in the Kauai County landfill in 1990 was used as the basis for projections (see Figure II-5). The detailed evaluation showed that almost 64% of the material disposed (wood, yard, green waste, food waste, and paper) had the potential to be used for ethanol or to produce electricity.

b. Quantity

As shown in Table II-6, significant amounts of lignocellulose-containing materials are produced statewide.

**FIGURE II-5
MSW COMPOSITION**

**TABLE II-6
QUANTITIES OF MUNICIPAL SOLID WASTE AVAILABLE IN HAWAII**

ISLAND Population 1991	OAHU 836,231	MAUI 100,504	HAWAII 120,317	KAUAI 51,177
PAPER (tons per year)				
Old corrugated cardboard	71,200	26,500	15,200	7,800
Old newspaper	65,500	9,500	5,500	2,800
High-grade paper	26,500	23,500		700
Mixed paper	120,400	10,400	19,500	3,000
TOTAL PAPER	283,600	69,900	40,200	14,300
Other organics	244,300	58,100	36,100	14,000
Green waste	200,600	53,800	13,900	15,800
TOTAL OTHER	444,900	111,900	50,000	29,800
MSW with ethanol potential	708,500	181,800	90,200	44,100
Other solid waste				
Glass	61,800	12,300	7,000	3,600
Aluminum	15,900	2,500	1,400	800
Tin		5,000		1,400
Metals (ferrous/non ferrous)	153,900	11,200	13,900	3,300
Mixed plastics	74,000	13,600	11,100	5,500
Batteries	12,000			
Tires	6,000	1,300		400
Construction demolition	93,200			
Others	335,900	45,300	15,500	21,200
TOTAL MSW (tons per year)	1,481,200	273,000	139,100	80,300

3. Municipal Solid Waste - (Hawaii County Case Study)

As part of evaluating the opportunities in the Hamakua area we have evaluated the MSW resource. A detailed evaluation showed that almost 64% of the material disposed (wood, yard, green waste, food waste, and paper) had the potential to be used for energy production, as shown in Figure II-5. In the Hilo/Hamakua region alone, almost 136,000 tons of wastes per year are potentially available.³¹ Much of this material is not disposed of in the landfill. Data on the Hawaii County landfills was provided by Hawaii County (See Figure II-6).

FIGURE II-6
REFUSE HAULED ON THE ISLAND OF HAWAII (TONS PER MONTH)

4. Newspaper and Mixed Waste Paper

An independent study of magazine mail and newspaper volume in Hawaii estimated that we produce almost 2 pounds per capita of paper products per day. Much of this material does not presently enter the disposal system, but is potentially available. Almost 77% of the material in paper products is made up of sugars that can be converted to ethanol (see Figure II-7). The opportunity to use newspaper as a source of material for ethanol production should also be given a great deal of attention.

FIGURE II-7

At present, much of the newspaper collected in Hawaii is sold to Asian markets for about \$8.00 per ton (FOB Hawaii).

- 1 Roberts, R.R. and H.W. Hilton. 1988. "Sugarcane Bagasse as a Potential Source of Ethanol and Methanol Biofuels," *Final Report of the Feasibility and Production of Alcohol Fuels from Sugarcane Bagasse Project*, Prepared for the Department of Business and Economic Development, State of Hawaii, 1:53.
- 2 Kinoshita, C. K. 1988. "Composition and Processing of Burned and Unburned Cane in Hawaii." *International Sugar Journal*. Volume 90, Number 1070.
- 3 Osgood, Robert V. and Dudley, Nicklos S. 1993. *Comparative Study of Biomass Yields for Tree and Grass Crops Grown for Conversion to Energy*. Final report from the Hawaiian Sugar Planters' Association under State of Hawaii contracts 18817, 20033, 22823, 27626, and 32116 from September 1985 to November 1993.
- 4 Merriam, B. 1994. Personal communication.
- 5 Mok, William Shu-Lai and Antal, Michael Jerry. 1992. "Uncatalyzed Solvolysis of Whole Biomass Hemicellulose by Hot Compressed Liquid Water." *Hawaii Integrated Biofuels Research Program, Final Subcontract Report Phase III*.
- 6 Mok, William Shu-Lai and Antal, Michael Jerry, 1992, previously cited.
- 7 Hawaii Natural Energy Institute. 1980. *Hawaii Ethanol From Molasses Project. Phase I - Final Report*.
- 8 Dale, Bruce E. 1983. Biomass Refining: Protein and Ethanol from Alfalfa. *I&EC Research and Development*. 22, 466.
- 9 Farone, Dr. William. 1994. Correspondence with Dr. Robert Shleser dated March 26, 1994.
- 10 Alexander, A.G. 1985. *The Energy Cane Alternative*. Sugar Series #6. Elsevier Science Publishing Co., Inc. New York, New York. pp. 1- 479.
- 11 Kinoshita, C. K. 1988. "Composition and Processing of Burned and Unburned Cane in Hawaii." *International Sugar Journal*. Volume 90, Number 1070.

- 12 Jakeway, Lee, HSPA. 1993 correspondence with Shleser, Robert A. Also Dillewijn, C. Van, 1952, Botany of Sugarcane.
- 13 Sugar content of prepared cane = sugar sold, plus sugar in molasses, plus sugar in bagasse.
- 14 US Environmental Protection Agency.
- 15 Hawaiian Sugar Planters' Association. 1991. 1992. *Hawaiian Sugar Manual*. HSPA, 99-193 Aiea Heights Drive, Aiea, Hawaii, 96701.
- 16 Hawaiian Sugar Planters' Association. "HSPA Sugarcane Factory Analytical Control Methods Manual, a Standard in the Hawaiian Sugar Industry
- 17 Hawaiian Sugar Planters' Association. Personal communication, 1994.
- 18 United States Department of Agriculture. 1993. *Sugar and Sweetener-Situation Outlook Report*. Page 10. December 1993.
- 19 Hawaiian Sugar Planters' Association. *Energy Report 27*. Unpublished HSPA data for calendar years 1988-1991.
- 20 Hawaiian Sugar Planters' Association.
- 21 Sloane, George. 1979. HSPA/HNEI *HSPA Molasses and Alcohol Stillage Characterization Project - Final Report*. HNEI- 79-03.
- 22 Hawaiian Sugar Planters' Association. *Energy Report 31*. Unpublished HSPA data for calendar year 1991. L.A. Jakeway, M. H. Bagley, and W. K. Hashimoto. October 1992.
- 23 Hawaiian Sugar Planters' Association. *Energy Report 31*. Unpublished HSPA data for calendar year 1991. L.A. Jakeway, M. H. Bagley, and W. K. Hashimoto. October 1992.
- 24 Hawaii Natural Energy Institute. 1993. *Investigation of biomass for Energy Production on Molokai*. September 1993.
- 25 Osgood, R. V. and Dudley, N. S. 1987. "Comparative Yield Trials with Tree and Grass Energy Crops in Hawaii: a Preliminary Report on Current Research" report 88-04 of *Cane Energy Utilization Symposium Proceedings*.
- 26 Osgood and Dudley, previously cited.
- 27 Crabb Thomas B. , T. H. Schubert and C. D. Whitesell. 1992. *Eucalyptus Plantations for Energy Production in Hawaii*. Sponsored by USDOE, HNEI, DBEDT, GACC, HSPA.
- 28 Whitesell, Craig D., D. S DeBell, T. H.Schubert, R.F.Strand and T. B. Crabb. 1992. *Short Rotation Management of Eucalyptus: Guidelines for Plantations in Hawaii*. US Department of Agriculture, Forest Service General Technical Report PSW-GTR-137. November 1992.
- 29 Osgood, Robert. 1993. Hawaiian Sugar Planters' Association, personal communication.
- 30 Plucknett, D. L., O. R. Younge, T. Izuno, Y. N. Tamimi, S. M. Ishizaki. (1972) "Sorghum Production in Hawaii." University of Hawaii, Hawaii Agricultural Experiment Station, Research Bulletin 143. April 1972.
- 31 Hildebrand, C. "Preliminary Report on Waste Streams State Wide for 1993." Department of Business, Economic Development and Tourism, State of Hawaii, August, 1993.

III. LAND AND FACILITIES [TASKS 3 AND 4]

A. LAND CAPABILITIES

The Hamakua/Hilo Coast region is located on the island of Hawaii. Both sugar operations, Hamakua Sugar Company and Hilo Coast Processing Company, in this region are expected to discontinue production soon. The remaining sugar operation on the island of Hawaii, Ka'u Sugar Company, is also discontinuing sugar operations. The possibility to convert up to 60,000 acres of potentially available lands to the production of dedicated feedstocks for conversion to ethanol and/or electricity exists (See Figure III-1). These lands include the areas of the Big Island that are most suitable for the production of biomass crops.

FIGURE III-1
SUGAR PLANTATIONS ON THE ISLAND OF HAWAII

The island of Hawaii is the largest island and youngest in the state of Hawaii, covering approximately 4,035 square miles or 63 per cent of the total land area in the state.¹ The most outstanding climatic features are remarkable differences in rainfall over short distances, mild temperatures, persistent northeasterly trade winds and

distinct climatic regimes in localities sheltered from the prevailing wind. The topography contributes to a diversity of micro-climates.

Lands on the island of Hawaii were assessed by Geographic Information Systems developed by the Hawaii Natural Energy Institute of the University of Hawaii. Lands were classified broadly by zoning, usage, ownership, elevation, soil type, temperature, rainfall, insolation, and slope. Various parameters conducive to biomass production and potential availability of lands were then overlaid to provide an approximation of the amount of land suitable for biomass to energy production on the island of Hawaii.

1. Zoning

Over 95 per cent of the lands on the island of Hawaii are zoned either conservation (50%) or agriculture (46%) (see Figure III-2). There are approximately 1,225,000 acres of agricultural zoned lands on the island of Hawaii.²

2. Usage

Current agricultural usages include commercial sugarcane, papaya, banana, coffee, and macadamia nut production; cattle grazing; and small areas of diversified agriculture production (see Figure III-3).

3. Ownership

Lands which are zoned agriculture on the island of Hawaii are owned by several different entities. These include, but are not limited to: the State of Hawaii, the Hawaiian Homes Commission, Bishop Estate, Hamakua Sugar Company, C. Brewer and Company, Samuel M. Dale Estate, and Richard Smart (see Figure III- 4).

4. Elevation

The elevations are the highest in the state. They range from sea level along the coast to nearly 14,000 feet on Mauna Loa and Mauna Kea (see Figure III-5). Elevations ranging from 2,000 to 4,000 feet in the region between Laupahoehoe and Waipio Valley have been designated as "prime" forest lands by the State of Hawaii Department of Land and Natural Resources. These elevations are suitable for the production of Short Rotation Intensive Crop (trees) production. Lands below this elevation are currently under sugarcane production and could be utilized for the production of grass varieties.

5. Soil Type

The island of Hawaii has a variety of soils due to the variations in climate, vegetation, geologic history, relief, and drainage. The soil types most conducive to biomass production are found in the Andisol order (formerly Inceptisol order) (see Figure III-6).

The sugarcane lands of Hamakua consist of moderately fine textured soils (silty clay loams) that developed in geologically recent volcanic ash. The majority of these

soils belong to the Hydrud and Great Group of the Andisol order (formerly Hydrandepts in the Inceptisol order) in the U.S. Soil Taxonomy System. Hydrudands are high in organic matter concentration, very porous, and continuously wet, but well-drained. The average topsoil (0 to 8 inch soil depth) organic carbon concentrations (5 to 6%), in Hamakua Coast Hydrudands presently under sugarcane production, compare favorably with the average organic carbon concentration (2%) of other agricultural soils in the humid tropics. However, the effective cation exchange capacity (sum of exchangeable cations) of Hamakua soils is generally low.

Major soil fertility concerns with the sugarcane lands of Hamakua are phosphorus (P) fixation (retention of fertilizer P in forms unavailable to plants), soil acidity, and potassium (K) and nitrogen (N) leaching. The extraordinarily high phosphorus-fixing capacity of Hamakua soils has been associated with the presence of high concentrations of allophane and hydrous oxides of iron (Fe) and aluminum (Al). For most crops, this requires the application of high rates of phosphorus fertilizer to obtain acceptable yields. Because of leaching, split applications of N and K are recommended during the growing season. Near complete depletion of exchangeable K from Hamakua soils can occur if it is not reapplied periodically. Periodic applications of liming materials also are needed to maintain a pH of approximately 6.0.³

6. Temperature

The mean annual temperature of the island of Hawaii varies between 72° and 75°F. along the coastal region and decreases by approximately 3°F. for each 1,000 feet of elevation. The daily range between high and low temperatures is 10° to 20°F (see Figure III-7). August and September are the warmest months; December, January, and February are the coolest. The seasonal range in temperature is only 4° to 8°F. Although the tropical temperatures of the Hawaiian Islands do not vary as dramatically as temperatures on the mainland, they do vary enough to reflect significant differences in seasonal growth rates for crops under consideration. This factor must be taken into consideration when projecting biomass yields.

7. Rainfall

Rainfall on the island of Hawaii ranges from 8 inches to over 300 inches per year.⁴ The principal cause of this extreme variability is the rain that forms within the moist trade wind air as it ascends and traverses the mountains. Generally speaking, the dry arid regions show more of a seasonal variation than the wetter regions which derive their rainfall from winter storms as well as year-round trade wind showers (see Figure III-8).

8. Insolation

The solar insolation levels on the Big Island range from 300 to over 570 langleys and are therefore among the highest recorded in the United States (see Figure III-9). This contributes significantly to the yield potentials of biomass crops in this region.

9. Potentially Available Land

The predominant land use in the Hilo/Hamakua area is forest reserve and unused open space. The County of Hawaii's Land Use Inventory identifies over 400,000 acres as "Unused Open Space". Agricultural uses in the area occupy over 250,000 acres with the majority dedicated to ranching. Sugar operations currently account for approximately 45,000 acres of the lands zoned agriculture. As recently as 1990, approximately 51,000 acres were dedicated to sugarcane production along the Hilo/Hamakua Coast (34,000 acres at Hamakua Sugar Company and 17,000 acres at Mauna Kea Agribusiness & United Cane Planters' Cooperative) (see Figure III-1).

Table III-1 shows the potential yield of biomass on a dry tons per year basis that could be produced if lands at the sites identified in the table were committed to dedicated biomass production.

TABLE III-1
ESTIMATED BIOMASS YIELD FROM POTENTIALLY AVAILABLE LANDS ON
THE ISLAND OF HAWAII⁵

LOCATION:	Type of Biomass Considered	Total Acres Considered	Commercial Yields (dry tons/net acre/yr)	Potential Biomass Production (dry tons/year)
Paaukau	Trees	11,400	8.3	94,620
Pepeekeo	Trees	19,100	8.3	158,530
Pahala	Trees	2,200	8.3	18,260
Ka'u Agribusiness	Grasses	18,200	14.6	265,720
Mauna Kea Agribusiness	Grasses	14,700	14.6	214,620
Hamakua Sugar Company	Grasses	27,800	14.6	405,880
TOTALS		93,400		1,157,630

Notes: * Commercial yields were estimated by averaging the tree and grass crop yields respectively.

Although sugar production at Hamakua has historically represented some of the most productive yields in the state, some of the potentially available lands have slope, temperature, and rainfall characteristics that may not be supportive of short rotation biomass crops. These marginal lands should be considered for longer rotation crops such as tree species that may not require high energy inputs to be sustainable. This would be a less destructive use of these lands.

FIGURE III-2
ZONING

FIGURE III-3
USAGE

**FIGURE III-4
OWNERSHIP**

FIGURE III-5
ELEVATION

FIGURE III-6
SOIL

FIGURE III-7
TEMPERATURE

FIGURE III-8
RAINFALL

FIGURE III-9
INSOLATION

B. FACILITIES IN THE HAMAKUA/HILO COAST REGION

Suitable facilities which may have application for the purposes of demonstrating and ultimately developing the appropriate technologies are discussed.

1. Hamakua Sugar Company

The Hamakua Sugar Company mill at Haina follows the general operations of the sugar industry in Hawaii. A general overview of this process and specific equipment involved at Hamakua Sugar Company follows.

a. Cane Handling Process

All cane is trucked to the factory and weighed on a 50-ton Howe platform scale with Fairbanks Morse strain gauge type readout. Trucks equipped with cargo nets are unloaded by hoists, using the side dump method which delivers the cane to the cane cleaner/feeder tables, either directly or by means of a mobile stacker which handles cane from a ground storage unloading area.

b. Milling Equipment

The field cane is first processed in a wet cleaning plant which removes dirt, trash, rocks, and other foreign material prior to milling. A system incorporated in early 1979 and modified in 1992 allows the recovery of all washed trash, which is then simultaneously processed with the cane.

c. Extraction Plant

The extraction plant is preceded by a motor driver leveler and a Hamakua designed and built 2,500 hp shredder installed in 1985. The cane then passes under an Eriez belt type tramp iron magnet located above a 300 feet per minute belt conveyor. The extraction plant was erected and commissioned in 1976. It consists of four Walkers 84" x 42" mills, each equipped with a heavy-duty continuous two-roll pressure feeder. Each mill is driven by a 700 hp Terry steam turbine reducer and a Welsh gear reducer connected to Walkers spur gearing which is equipped with anti-friction bearings.

d. Steam Plant

One Foster Wheeler steam generator commissioned in 1978 and capable of 288,000 lbs. of steam per hour at 800°F and 610 p.s.i.g. when fired with bagasse at 50% moisture. The boiler is equipped with a stationary water-cooled pinhole grate; one 1,776 hp Combustion Engineering, two-drum type VU-50X water tube boiler, 610 lbs. working pressure, 750°F total temperature, and 17,780 sq. ft. heating surface with dumping grate on line. For air pollution control, the boiler is equipped with two UOP Air Correction division Type 6P high-efficiency multiclone mechanical collectors in series.

e. Electric Plant

One 6,000 kW, 13.8 kv back pressure turbo generator, inlet pressure 600 psig, exhaust 235 psig. The exhaust is used for all other prime movers, including a 1,500 kW G.E. turbine and a 7.5 MW condensing turbo-generator which was commissioned in early 1981. An 800 kW hydro generator is used to generate power on the off season as well as during the grinding season. A 4 MW generator moved from the Ookala Factory to Haina and commissioned in early 1987 uses steam at 450 psig from the Combustion Engineering boiler.

f. Bagasse Drying and Densifying Plant

System commissioned in 1980 employing boiler stack gases to dry all bagasse from approximately 50% to 35% moisture. The densification plant has been removed as there is insufficient surplus bagasse to warrant densification.

g. Clarification

The clarification section consists of two juice heaters in parallel on primary heating, 2,422 and 2,486 sq. ft. respectively, followed by two heaters of 2,875 sq. ft. each in parallel on secondary heating with vapor from the pre-evaporator, and one Graver clarifier 30' diameter by 17'8" high.

h. Evaporation

First effects are two pre-evaporators in series 26,000 and 24,000 sq. ft.. These are followed by three sets of triple effects. The first set of triples has units of the following h.s.: 17,317, 10,000, and 7,000 sq. ft. each. The second set of triples has units of the following h.s.: 8,000, 7,000, and 7,000 sq. ft. each. The third set of triples has units of 6,500 sq. ft. each. Vapor from the preevaporator serves all the pans and secondary juice heater, and first vapor from the two triples serves the primary heater.

i. Pan Storage Tanks

For syrup, tank storage of 8,756 cu. ft.; for A molasses, 2,800 cu. ft.; and for B molasses, 1,700 cu. ft..

j. Vacuum Pans

For raw VLC (very low color) sugar, one 18-1/2" diameter calandria pan of 2,000 cu. ft. capacity and 4,215 sq. ft. h.s.; one 2,000 cu. ft. pan with 4,200 sq. ft. h.s. calandria pan of 1,600 cu. ft. capacity and 2,396 sq. ft. h.s.. For B sugar, one Hamill 10'/11'6" diameter calandria pan of 900 cu. ft. capacity with 1,200 sq. ft. h.s. and one 16'10" diameter calandria pan of 2,000 cu. ft. capacity and 3,000 sq. ft. h.s.. For low grade sugar, one H.I.W. 12' diameter calandria of 1,100 cu. ft. capacity with 1,755 sq. ft. h.s. and one 17'6" diameter calandria of 2,000 cu. ft. capacity with 4,035 sq. ft. h.s..

k. Evaporators and All Pans

Individual vacuum pumps (Nash Hytor) and individual stainless steel condensers, 12,000 gpm of water at 115 F° is recirculated and cooled to 90 F°.

l. B Crystallizers

Four Honolulu Iron Works-type crystallizers of 900 cu. ft.; two installed in 1948, converted to B massecuite in 1988.

m. Crystallizers

Five Honolulu Iron Works-type crystallizers of 900 cu. ft., two installed in 1948, three in 1970. Individual drive on the last three. Two Ducasse/Unice continuous crystallizers of 900 cu. ft. each.

n. Centrifugals

For raw sugar, six 48 x 36 automatic Western States centrifuges. For B station, two BMA k1100 (1988) and one CC-4 (1969) Western States continuous centrifugals. For low grade, one 34" x 34" Western States (1985) and BMA k1100 (1988) continuous centrifuges.

o. Sugar Storage

The sugar is elevated from the centrifugals into two steel bulk sugar bins, one of 350 tons and the other of 400 tons. The bins are located adjacent to the milling building.

p. Molasses Storage

The final molasses is pumped through a cooler, temperature reduced to 105 F° and into a 500-ton molasses storage tank which was installed at the factory in 1959. All molasses is hauled by tank truck to the 10,000-ton receiving and storage tanks at the port of Kawaihae.

q. Waste Water Treatment

Cane wash water and boiler ash water are treated prior to being discharged from the factory. The waters pass through a screening conveyor with 1/4" diameter holes, then through a grit separator before being distributed to two 60' diameter Dorr-Oliver clarifiers. Underflow from the clarifiers is dewatered by two 10' diameter x 20' long Dorr-Oliver vacuum filters. The mud is then removed by truck to land disposal.

2. Hilo Coast Processing Company

The sugar mill at Hilo Coast Processing Company follows the general process flow of the Hawaii sugar industry and will be further detailed in the efforts of the NREL LOI Hawaii Project.

3. Ka'u Agribusiness

The sugar mill at Ka'u follows the general process flow of the Hawaii sugar industry and will be further detailed in the efforts of the NREL LOI Hawaii Project.

-
- 1 State of Hawaii, Department of Business, Economic Development & Tourism, *DATA BOOK 1992*.
 - 2 HNEI, Personal communication.
 - 3 Bruce W. Mathews, Agronomy and Soils, College of Agriculture, University of Hawaii at Hilo. Paper presented at the Symposium on Alternative Crops to Sugar for Hilo/Hamakua Land. November 20, 1993.
 - 4 Atlas of Hawaii 1992 Second Edition University of Hawaii Press pp 62-63 extrapolation
 - 5 Adapted from the Renewable Energy Resource Assessment Project of the Hawaii Energy Strategy, 1994, *Phase I Report - Biomass Resources*, by the College of Tropical Agriculture and Human Resources, University of Hawaii, for R. Lyneete & Associates, Inc.

IV. ETHANOL OPTIONS [TASKS 5 AND 7]

A. ETHANOL FOR HAWAII?

This section of the report is devoted to evaluating the potential to produce ethanol from the sources of biomass described previously. There are several reasons for interest and support for the production of ethanol in Hawaii. These include:

- The potential to establish a local industry to substitute for some portion of the approximately 50 million barrels of petroleum that we currently import each year to meet our energy needs.
- Use of ethanol in a 10% blend with gasoline is being done nation-wide (in forty-four other states), and all auto makers approve the use of properly blended ethanol fuels in their vehicles.
- Cultivation of crops for ethanol might provide a basis for establishing alternative uses for agriculture lands that are coming out of production and may generate new sources of employment in the agriculture sector.
- Use of municipal solid waste to produce ethanol could reduce the flow of material to the landfill and provide a low cost source of feedstock.
- Ethanol production from local feedstocks may offer an opportunity to develop new businesses and provide some economic diversification in rural areas.

The possibility of producing ethanol in Hawaii has been of interest for decades. Numerous studies have been completed and several attempts at commercial production have been made with less than positive results. Advances in technology in recent years provided the basis for a re-evaluation of the potential to produce ethanol from biomass in Hawaii. Technical progress has been accompanied by economic improvement. Much progress has been made by government, universities, and the private sector in advancing the technology for hydrolyzing biomass to sugars fermentable to ethanol. Experts in the field have stated that, "over the past ten years, efficiencies have improved and costs have decreased to the point that an ethanol plant built today may cost as little as a third as much (in constant dollars) as a comparably sized ethanol plant built ten or fifteen years ago."¹ Significant progress has been made in the areas of feedstock preparation, hydrolysis, fermentation of the sugars, and distillation.

The costs of ethanol production are highly sensitive to the cost of the feedstock delivered to the processing site and the volume and composition of the material. The success of any plan to grow crops for ethanol production will be dependent on the selection of appropriate crops, production methods, and locations. A system established around the lowest cost starting material and fully integrated to "squeeze out" the greatest economic outputs by utilizing all of the by-products in the system, will present the best opportunity for economic success.

B. "LIGNOCELLULOSIC BIOMASS" AND SYSTEM ECONOMICS

Historically, production of ethanol was limited to using sources of sugar that were available in soluble forms, such as sugar (sucrose), molasses from sugarcane, or fructose from the corn plant. Since these soluble sugars are edible², their relative value tends to be higher than for the rest of the plant (leaves, stalks, etc.) which is inedible and usually has a much lower value. In many cases, the inedible portions of the plants are considered to be waste materials. New technologies have developed that make it possible to produce ethanol from the other plant components or "lignocellulosic biomass." Lignocellulosic biomass is made up of the leafy or woody part of plants: corn stover, bagasse, yard and wood waste, paper pulp, etc.

Biomass is principally composed of the compounds **cellulose**, **hemicellulose**, and **lignin**. **Cellulose**, a primary component of most plant cell walls, is made up of long chains of the **6-carbon sugar, glucose**, arranged in bundles. Cellulose is a primary component of paper. In the plant cell wall, the cellulose molecules are interlinked by another molecule, **hemicellulose**. The **hemicellulose** is primarily composed of the **5-carbon sugar, xylose**. Another molecule, called **lignin**, is also present in significant amounts and gives the plant its structural strength. Improvements in technology have recently provided a variety of methods of extracting and dissolving the cellulose and hemicellulose to produce the component sugars in a form that can be converted to ethanol. Appropriate pre-treatment can free the cellulose and hemicellulose from the plant material. Further treatment using chemicals, enzymes or microorganisms can be used to liberate simple sugars from the cellulose and hemicellulose making them available to microorganisms for fermentation to ethanol. ^{3,4,5,6,7,8,9,10,11,12,13} A recent technology brief published by NREL stated: "Many of the recent advances in biomass fuel technology relate to the breakdown of lignocellulosic material so it can be fermented to ethanol. Conversion of lignocellulosic material could substantially reduce ethanol costs and enormously expand available feedstocks. In addition to specially grown grasses and trees, other potential feedstocks include agricultural and forestry residues, along with paper and other municipal solid waste."¹⁴

The nature of the feedstock puts certain constraints on the technology required for the manufacture of ethanol. For example, molasses or sugar solutions can be fermented directly by yeast, using traditional and well-established technology. However, lignocellulosic feedstocks such as wood or bagasse must be hydrolyzed into component molecules and sugars before fermentation by one or more specifically selected microorganisms. Though currently requiring increased capital investment, technologies for conversion of lignocellulosic materials are near-term and have the potential for dramatic improvements of ethanol yields.

If the cost of a feedstock is sufficiently low, more expensive conversion technology may be justified.

C. POTENTIAL GALLONS OF ETHANOL PER TON OF BIOMASS

On the basis of composition of each type of biomass, it is possible to estimate the ethanol potential per ton for the materials identified above. Figure IV-1 provides a comparison of the potential ethanol yields, based on fermentable sugars and assumed conversion efficiencies presented in Table IV-1.

TABLE IV-1
CONVERSION EFFICIENCIES ASSUMED
FOR SUCROSE, CELLULOSE, AND HEMICELLULOSE TO ETHANOL

CONVERSION EFFICIENCIES ASSUMED	LOW END OF RANGE	HIGH END OF RANGE	USED IN CALCULATIONS
Sucrose to glucose & fructose	99%	100%	99.5%
Cellulose to glucose	95%	100%	97.5%
Hemicellulose to xylose	50%	90%	70.0%
Glucose to ethanol	95%	100%	97.5%
Fructose to ethanol	95%	100%	97.5%
Xylose to ethanol	40%	90%	65.0%
Sucrose to ethanol	94%	100%	97.0%
Cellulose to ethanol	90%	100%	95.1%
Hemicellulose to ethanol	20%	81%	50.5%

FIGURE IV-1
POTENTIAL GALLONS OF ETHANOL PER DRY TON BIOMASS

D. POTENTIAL GALLONS OF ETHANOL PER ACRE

1. Potential Yields of Ethanol from Agricultural Crops

Crop productivities, results from experimental plantings, and projected commercial yields for several crops were discussed in Chapter 2. Figure IV-2 presents the resultant ethanol potential from various crops on an annualized basis, using biomass yield reported in Chapter 2.

FIGURE IV-2
POTENTIAL GALLONS OF ETHANOL PER ACRE, PER YEAR

2. Potential Yields of Ethanol from Sugarcane Components

Sugarcane has been grown in Hawaii for over 150 years; as such, yields and costs of commercial production are well known within the industry. However, the question of "ethanol from sugarcane" requires consideration of a number of variables, each of which has its own associated costs and side-effects. The relative costs and returns of any of these scenarios are site and technology specific. Possible approaches are shown in Table IV-2.

TABLE IV-2
POSSIBLE APPROACHES TO ETHANOL FROM SUGARCANE

HARVESTING	PRODUCTS	ETHANOL FROM
Burned fields	Sugar, bagasse, and molasses	No ethanol produced
Burned fields	Sugar, bagasse, and ethanol	Molasses
Burned fields	Sugar and ethanol	Bagasse and molasses
Burned fields	Ethanol	Sugar, bagasse and molasses
Unburned fields	Sugar, bagasse, molasses, and unburned leafy trash (leafy trash used for electricity generation)	No ethanol produced
Unburned fields	Sugar, bagasse, molasses, and ethanol	Unburned leafy trash
Unburned fields	Sugar, bagasse, and ethanol	Molasses and unburned leafy trash
Unburned fields	Sugar and ethanol	Bagasse, molasses and unburned leafy trash
Unburned fields	Ethanol	Sugar, bagasse, molasses and unburned leafy trash

Potential ethanol from the conversion of one harvested acre of sugarcane ("prepared cane") is shown in Figure IV-3. The quantities shown are per harvested acre and have not been adjusted on an annualized basis. Potential additional biomass from unburned cane (see discussion on burned vs. unburned sugarcane in Chapter 2) is not shown.

FIGURE IV-3
PREPARED CANE TO ETHANOL DIAGRAM

E. FEEDSTOCK COST PER GALLON OF ETHANOL

1. Agricultural Crops

Table IV-3 shows biomass costs per ethanol gallon based on information presented in Chapter 2 and conversion efficiencies presented earlier.

TABLE IV-3
CULTIVATED FEEDSTOCKS:
ESTIMATED COST PER DRY TON AND PER ETHANOL GALLON

CROP	Estimated cost per ton (\$/ton dry matter)	Estimated feedstock cost (\$/gallon ethanol)
Sugarcane (irrigated)	\$83	\$0.73
Napier grass (irrigated)	\$70	\$1.04
Leucaena (irrigated)	\$101	\$1.26
Sugarcane (rainfed)	\$75	\$0.65
Eucalyptus (rainfed)	\$74	\$1.11
Napier grass (rainfed)	\$57	\$0.72

3. Sugarcane Components

For the purposes of this section, the costs of the various sugarcane-derived materials were considered separately, as described below:

a. Bagasse

The cost per ton of bagasse was based on the cost that would be incurred in replacing the bagasse with #2 diesel, #6 fuel oil, or coal for electricity production (the low end of the range is for coal at \$60 per ton; the high end of the range is for #2 diesel at \$32.00 per barrel).

b. Molasses

Molasses cost per ton was based on the 1991 average return to growers of \$40.00 per wet ton.¹⁵ If the molasses was to be shipped to another location, rather than used at the point of production, the assumption of \$40.00 per ton, which does not include consideration of transport costs, would be low.

c. Prepared cane

The cost per ton of "prepared cane" was based on Osgood and Dudley (1993) estimated sugarcane costs per acre, thus are consistent with napier grass, leucaena, and eucalyptus estimated costs obtained from the same source¹⁶. In subsequent calculations (such as those used to generate Figure IV-4), an average of 50% irrigated and 50% unirrigated acreage was assumed.

d. Sugarcane trash

"Sugarcane trash" refers to unburned leaves and trash not counted in prepared cane. These costs were based on an estimate of an increase of 50% in harvesting costs and an increase of 40% in hauling costs per acre,¹⁷ using estimates of cost centers from Osgood and Dudley (1993). There is some concern that harvesting without burning may lower recoverable sucrose yields by some percentage. The cost of reduction in recoverable sucrose yield has not been taken into account in the comparison below.

e. Unburned sugarcane

The cost per ton of "unburned sugarcane" is the sum of the costs of "prepared cane" and the "unburned leaves," determined on a per-acre basis then reduced back to a per-ton basis to maintain the relative proportions of the various parts of the plant.

2. Municipal Solid Waste, Organic Waste and Newspaper

As discussed in Chapter 2, significant quantities of MSW and organic wastes are available in the study region. Although some waste-to-ethanol studies have included tipping fees (i.e., a fee is collected from the person(s) disposing of the organic waste at the collection site) in their cost analyses, such tipping fees may reduce the amount of material coming to the facility if there are cheaper (or free) alternatives such as public landfills, composting or disposing of the waste by illegal dumping. Therefore, although the potential may exist to collect fees for taking these waste materials, such fees were not assumed in this analysis. Almost 5 million gallons of ethanol per year, or about 13% of the gasoline consumption of the island of Hawaii, could (theoretically) be produced from these materials.

3. Summary of Feedstock Costs

Estimated feedstock costs per ton and on a per-gallon-ethanol basis are shown in Table IV-4 and in Figure IV-4. The ranges shown are intended to indicate a range of costs which may be expected due to variations in yields between locations (assuming costs per acre to be relatively constant). Sweet sorghum costs were assumed to be similar, on an annual acre basis, to irrigated sugarcane.

TABLE IV-4
RANGE OF ESTIMATED BIOMASS COSTS PER POTENTIAL ETHANOL GALLON

BIOMASS	Estimated upper end of range, feedstock cost per dry ton	Estimated lower end of range, feedstock cost per dry ton	Estimated upper end of range, feedstock cost per potential ethanol gallon	Estimated lower end of range, feedstock cost per potential ethanol gallon
Sugarcane	\$95.20	\$69.18	\$0.83	\$0.61
Leucaena	\$165.25	\$144.00	\$2.06	\$1.80
Eucalyptus	\$126.60	\$53.19	\$1.78	\$0.75
Napier grass	\$84.76	\$52.19	\$1.26	\$0.78
Sweet sorghum	\$90.07	\$64.09	\$0.72	\$0.51
Newspaper	\$15.00	\$5.00	\$0.14	\$0.05
Municip Solid Waste	\$25.00	\$0.00	\$0.42	\$0.00
Molasses	\$47.20	\$47.20	\$0.50	\$0.50
Bagasse	\$72.23	\$38.05	\$0.84	\$0.44
Unburned sugarcane	\$110.29	\$58.66	\$0.98	\$0.52

On the basis of the assumptions and information presented thus far, sugarcane varieties, sweet sorghum, MSW and paper wastes appear to have the most immediate potential to serve as sources of biomass for ethanol production.

FIGURE IV-4
ESTIMATED BIOMASS COST PER POTENTIAL ETHANOL GALLON

F. LAND REQUIREMENTS

A critical consideration in a state the size of Hawaii is the number of acres in production required to meet the needs of a specific size processing plant or the needs of an identified market. Production on each island, to meet the local demand and eliminate the cost of shipping, may present the best opportunity. Extensive discussions with developers of technology suggest that a plant producing 25 million gallons of ethanol per year might provide the optimal economy of scale for commercial production. This size plant corresponds to the acreages shown in Table IV-5 below.

TABLE IV-5
ACREAGE REQUIRED TO PRODUCE BIOMASS FOR A 25 MILLION GALLON PER YEAR ETHANOL PRODUCTION FACILITY

BIOMASS MATERIAL	TONS BIOMASS required (dry, per year) for 25 million gallon-per-year facility	ACRES REQUIRED for biomass for 25 million gallon-per-year facility
Sugarcane ("prepared cane")	218,933	15,270
Sugarcane - whole plant (no open field burning)	238,655	12,709
Sugarcane varieties (Puerto Rico & Hawaii)	219,768	7,578
Napier Grass	372,670	17,257
Sweet Sorghum	200,290	8,231
Eucalyptus	327,054	31,547
Leucaena	312,397	33,956
Newspaper	226,260	--
Municipal Solid Waste	417,282	--

G. STEPS IN THE ETHANOL PRODUCTION PROCESS

Production of ethanol from biomass involves a series of steps that liberate constituent sugars making them available for fermentation to ethanol. The technologies described in this section share the capability of liberating the cellulose and hemicellulose from the plant material and producing the component sugars for fermentation to ethanol. Figure IV-5 shows the various steps in a lignocellulosic biomass-to-ethanol conversion process. The starting material, "organic biomass," is in the top row on the left. This material is processed by treatments such as "crushing" and "grinding," with the resulting product being "prepared biomass."

Next, the prepared biomass, shown in the second row, is subjected to a hydrolysis process, with the resultant products being cellulose, hemicellulose, and lignin. Cellulose and hemicellulose are shown in the third and fourth row, with their semi-hydrolyzed counterparts, hexosans and pentosans, and so forth. Intermediate products and process by-products (such as lignin, stillage, carbon dioxide, methane, algae, pharmaceuticals, feed ingredients, etc.) will be discussed in the section of this report which deals with markets and by-products.

FIGURE IV-5
BIOMASS CONVERSION PRODUCTS

MATERIAL	TREATMENT	PRODUCTS	VALUE/USE
ORGANIC BIOMASS	→ Crushing Grinding →	Prepared Biomass	Raw Feedstock for Processing
Prepared Biomass	→ Hydrolysis →	Cellulose Lignin Hemicellulose	6 carbon sugars fuel/chemicals 5 carbon sugars
Cellulose Hexosans	→ Continued Hydrolysis →	Glucose	6 Carbon Sugars for Fermentation
Hemicellulose Pentosans	→ Continued Hydrolysis →	Xylose Pentose Sugars	5 Carbon Sugars for Fermentation
Glucose	→ Yeast or Bacterial Fermentation →	Stillage ETHANOL CO ₂	Feed Ingredients Fuel Feedstock
Xylose Pentose Sugars	→ Bacterial Fermentation →	Stillage ETHANOL CO ₂	Feed Ingredients Fuel Feedstock
CO ₂	→ Bioconversion →	METHANE ALGAE	ENERGY Pharmaceuticals Commodities
ETHANOL	→ Chemical Conversion →	ETBE	OCTANE ENHANCER
ALGAE	→ Processing Extraction →	Pharmaceuticals β CAROTENE Feed Ingredients	MEDICINE ANIMAL FEEDS

H. OPTIONS AT EACH STEP IN THE ETHANOL PRODUCTION PROCESS

There are many options available at each of the steps shown in Figure IV-5. Several government laboratories, academic institutions and private sector companies have devised various techniques to accomplish each of the steps required to process the biomass to ethanol. In many instances, organizations select a particular combination of steps and consider the sequence to be "their" system. The options at each step of the biomass-to-ethanol processes are illustrated in Figure IV-6. "Systems" described in the following section deal with various combinations of these options. The material presented largely duplicates information contained in the DBEDT Report, *Ethanol Production in Hawaii*. For more detailed information on the following section, the reader is encouraged to review the detailed appendices in the *Ethanol Production in Hawaii* report.

FIGURE IV-6
ETHANOL PRODUCTION TECHNOLOGY OPTIONS

I. APPROACH TO EVALUATION OF SYSTEMS

Caution is recommended in interpreting the information in this section. Because only limited information was provided by the developers of technologies, the evaluations are only approximations of the costs and yields from processes that appear to be ready for commercial scale development. The evaluations are only as good as the process information available. In no case was there sufficient information to conduct a rigorous comparison of the technologies. Material presented in this section indicates that a variety of approaches have potential to produce ethanol from biomass in Hawaii, although an assessment of the time frames to commercialization was beyond the scope of this report.

The first step in system and technology comparisons was the development of a questionnaire. This questionnaire was forwarded to a comprehensive list of experts and technology owners. Quantitative, factual information was requested for each step of each of the systems. The success of this approach was limited for four primary reasons:

- The slow response to questions from technology developers;
- A reluctance to provide details that are considered proprietary;
- The processes are at different stages of development, making extrapolations to commercial scale inconsistent across all processes; and
- Different information sources and assumptions are used by the developers, providing no common base for comparison.

Questionnaire responses were not sufficient enough on any key points to enable detailed comparative analysis of the process or even to compare the approaches to each step outlined in Figure IV-6. In the process of trying to obtain the specific details of each system it became clear that many of the technologies had not yet been demonstrated on a commercial scale and that much of the design information provided previously was based on laboratory or limited pilot data.

The limited success with the first questionnaire led to the development of a second survey requesting non-proprietary numbers. The results provided additional information; however, there was still insufficient information on key points to complete the detailed comparison. In order to make comparisons, it was necessary to make extrapolations to fill in missing pieces.

Due to the nature of this study, it was necessary to rely on claims made by those most familiar with the various technologies. In most cases, these individuals were the developers of the technologies and the owners of the patent rights, and therefore may have been somewhat biased in their claims; it should be expected that some individuals may have been more conservative in their projections, and others may have been more optimistic.

J. ASSUMPTIONS USED IN EVALUATIONS

Dr. Hans Grethlein, at the Michigan Biotechnology Institute (MBI), has developed an approach using data from the more complete systems to fill in missing parts from less complete technologies. This method was of great help in these evaluations, and in some cases this information was used directly.^{18, 19} Grethlein compared performance of systems producing 25 million gallons per year using corn stover as the source of biomass substrate.

A similar approach was used in this study. Information provided by the questionnaire respondents was for plants of many different sizes and capacities. Scaling factors of 0.7 and 0.9 were used for the plant and personnel, respectively. For the purposes of the comparison, prepared cane was identified as the baseline feedstock. Other assumptions common to the evaluations are shown in Table IV-6.

TABLE IV-6
EVALUATION ASSUMPTIONS

Power Law Scaling Factor	0.7		Process cost only (biomass (\$0)	0
Contingency	10%		Biomass Cost 1	\$50
Start-up factor	5%		Biomass cost 2	\$108
Working Capital	7.50%		Denaturant cost, \$/gal	\$0.87
Operating Days per Year	330		Denaturant Use	5%
Personnel Scaling Factor	0.9		Fringe Benefits	25%
Property Tax & Insurance	1.50%		Capital Charge, %/yr.	0

K. REVIEW OF ETHANOL TECHNOLOGIES²⁰

The material below is presented primarily as a comparative review of technology. Although most of the technologies described below are associated with a specific company, additional information from the technical literature and projections on capital and operating costs in Hawaii were used to complete the comparative evaluations. Because much of the information provided was incomplete, the extrapolations below cannot be used to reach final conclusions regarding economic performance of a specific technology in Hawaii. The results should not be considered representative of the current status of this technology.

NOTE: The information below is for comparative purposes only, and may not represent the actual performance of any specific proprietary technology in Hawaii.

1. Simultaneous Saccharification and Fermentation

This technology is largely associated with the research and development program of the National Renewable Energy Laboratory (NREL) in Golden, Colorado. This institution has had a long history of involvement in developing technology for producing ethanol from lignocellulosic biomass. In a succession of development steps, they have settled on the process of Simultaneous Saccharification and

Fermentation (SSF).^{21, 22, 23} A 1988 paper by Wright, Wyman, and Grohman²⁴ provides a useful overview. Quoting selectively from this publication:

"...All enzymatic processes consist of four major steps that may be combined in a variety of ways — pre treatment, enzyme production, hydrolysis and fermentation. · The key to increasing the digestibility of lignocellulose lies in increasing the cellulose surface area that is accessible to enzymes · by carrying out a pre hydrolysis (dilute 1.1% sulfuric acid at 160°C for 10 minutes) the hemicellulose fraction is removed (93% of the xylan is hydrolyzed resulting in fully digestible cellulose pulp) enlarging pore size and thus opening the structure to attack by enzymes · the degree of digestibility is almost directly proportional to the fraction of xylan removed. Cellulose is then broken down by enzymes. In the SSF process enzymes that break down cellulose are produced separately by the fungus *T. reesei*. Yeast and the enzymes are added to the remaining material where the enzymes digest the cellulose to produce glucose. Glucose is then fermented by yeast or other microorganisms to produce ethanol."

Essential elements of the SSF approach are presented in Figure IV-7. As presented, this is not a complete system; however, it describes an approach to pre-treating and processing biomass that distinguishes this process from the others evaluated. The unique aspect of the NREL approach is that the microorganisms and the enzymes are present in the same system. By converting the sugars to ethanol as they are formed, the inhibitory effect of sugar build-up on enzyme performance is reduced. Wright et al comment (28):

"...simultaneous saccharification and fermentation systems offer large advantages over separate saccharification and fermentation systems for the production of ethanol from lignocellulosic materials because of their great reduction of the cellulase enzyme complex."

FIGURE IV-7
SIMULTANEOUS SACCHARIFICATION AND FERMENTATION

A very important issue is identified by the statement:

"The performance of SSF appears to be limited by the performance (combined temperature and ethanol tolerance) of the yeast rather than by the performance of the enzyme."

A solution to this problem will be discussed under the section "Technology for Hawaii."

Information provided and available was for a facility producing about 58 million gallons per year, as shown in the Appendix. Cost savings may be possible on the basis of scale and financing mechanisms. Scaling factors for facilities and personnel were used to generate the performance estimates for systems producing 5 and 25 million gallons per year; results are presented in Tables IV-7 and IV-8.

2. Concentrated Acid Hydrolysis, Neutralization, and Fermentation

The Tennessee Valley Authority (TVA) began developing technology for conversion of cellulosic feedstock to fuel ethanol in the 1950s. TVA focused on developing dilute and concentrated acid hydrolysis technologies.²⁵ Much of the work at TVA focused on processing biomass feedstocks and effluent to multiple products. The TVA programs have developed and evaluated many of the technical options for converting cellulose bound in biomass to sugars, bioconversion of those sugars to ethanol and other chemicals, and waste utilization for conversion of co-products from waste effluent.^{26, 27, 28, 29} Although the work at TVA has progressed to include approaches for acid recovery, (discussed later in this section) the use of a base to neutralize acid is presented here to provide a contrast with other technologies. A simplified summary of the process follows:

FIGURE IV-8
CONCENTRATED ACID HYDROLYSIS, NEUTRALIZATION, AND
FERMENTATION

The biomass is collected, dried, and milled to pass through a 4 mesh screen. Next, the material is transferred to a first stage hydrolyzer or large vat. Sulfuric acid (7.65% by weight) is added to the vat which is heated to 100°C for 2 hours. About 75% of the hemicellulose is hydrolyzed to xylose. The remaining solids (lignin and cellulose) are removed in a screw press and transferred to a separate vessel where additional acid and much of the acidified xylose are added back to increase the sugar concentration. The temperature is again raised which results in the hydrolysis of the remaining cellulose to glucose.

The result is a mixture of 5 carbon (pentose) and 6 carbon (hexose) sugars in acid solution. Lime is added to neutralize the acid, producing gypsum, which is removed in a rotary filter. The remaining solution stream contains both glucose (11.6%) and xylose (9.0%) The fermentation is also conducted in steps. First, glucose

is fermented to ethanol by the yeast *Sacromyces cerevisiae*. The mixture is then distilled to remove the ethanol leaving the unconverted xylose behind.

A second yeast *Pachysolen tannophilus* which ferments xylose to ethanol is added to the remaining solution. Ethanol produced from xylose is then distilled. Lignin and cellular material remaining is dried and burned in a boiler to provide process energy or produce electricity. The process is shown in Figure IV-8.

Grethlein et al. made a number of assumptions in their theoretical cost evaluation of the TVA process.³⁰ Further assumptions have been made in this study regarding financing, start up time, and working capital. Estimated costs for plants producing 5 and 25 million gallons per year using the acid hydrolysis and fermentation process are presented in Tables IV-7 and IV-8.

3. Ammonia Disruption, Hydrolysis, and Fermentation

The development of this technology and its application in converting lignocellulosic material to animal feed was described in the technical literature in the late 1980s. Ammonia is used to pre-treat the lignocellulosic biomass.^{31, 32, 33} The biomass is ground and milled into small particles. Ammonia is then infused at high pressures for about 30 minutes at temperatures ranging from 25-90°C (Figure IV-9).

FIGURE IV-9
AMMONIA DISRUPTION, HYDROLYSIS AND FERMENTATION

In this process, ammonia infused at elevated pressure and temperature swells and de-crystallizes the cellulose/hemicellulose complex so the biomass is very accessible to the enzyme cellulase. When the pressure is released the ammonia virtually explodes or gasifies. It is then recaptured in a surge tank and recycled. Hydrolysis of cellulose and hemicellulose to sugars is accomplished by adding enzymes that are produced separately on site to the ammonia treated biomass. This process does not

degrade protein which can be recovered as an animal feed ingredient. Fermentation is accomplished sequentially as with the concentrated acid hydrolysis process above.

Information provided by Grethlein,³⁴ technical publications,^{35, 36} and local cost estimates were used to complete the economic projections in Tables IV-7 and IV-8.

4. Steam Disruption, Hydrolysis, and Fermentation

Stake Technology Limited, of Norval, Ontario, Canada has been one of the pioneering firms involved with processing of lignocellulosic biomass. The company initially was involved with preparing cattle feed from wood chips using steam to disrupt the crystalline cellulose structure in a fashion similar to ammonia explosion. The Stake Tech people have been involved in sustaining an interest in ethanol in Hawaii for decades and have provided a great deal of information.^{37, 38} Figure IV-10 below summarizes the key elements of the process.

FIGURE IV-10
STEAM DISRUPTION, HYDROLYSIS, AND FERMENTATION

In the steam explosion process, biomass is chopped to an appropriate size and fed into a high pressure reaction cylinder. The solids are moved continuously through the steam reactor tube with an auger and pushed through an orifice where the material literally explodes into a flash tank, where the exploded biomass and steam are recovered. When the pressure is released it causes the deacetylation and auto hydrolysis of the hemicellulose to xylose. The lignin is also melted in this treatment and the remaining biomass becomes a viscous slurry of cellulose and polysaccharides that are available for enzyme digestion to component sugars (primarily glucose).

When the biomass exits the recovery tank it can be fermented and distilled to produce ethanol. It should be noted that volatile organics such as furfural, an inhibitor of microbial fermentation, are also formed. In order to compare the performance of this approach, information provided by Stake Tech was combined

with estimates of the costs elements not described by the company and estimates of costs in Hawaii. The projections for a steam disruption, hydrolysis, and fermentation plant producing 5 and 25 million gallons of ethanol per year are presented in Tables IV-7 and IV-8.

5. Acid Disruption and Transgenic Microorganism Fermentation

BioEnergy International, L.C., is a subsidiary of Quadrex Corporation, a publicly held company. They have the exclusive worldwide license for a constructed set of genes that when inserted into a microorganism has the ability to ferment both pentose (5-carbon) sugars and hexose (6-carbon sugars).^{39, 40, 41, 42, 43} This genetic construct, developed by Dr. Lonnie Ingram and co-workers at the University of Florida, was issued U. S. Patent No. 5,000,000 in 1991. This patent outlines the methodology for constructing a unique portable operon for ethanol production, which consists of alcohol dehydrogenase II, and pyruvate decarboxylase genes from *Zymomonas mobilis*, which is inserted into the genome of a host cell such as *E. coli*, *Erwinia* or *Klebsiella*.^{44, 45} This system is designed to enhance ethanol production by diverting pyruvate to ethanol during growth under either aerobic or anaerobic conditions. This allows lactose, glucose, xylose, arabanose, galactose and mannose to be converted to ethanol without producing organic acids.

FIGURE IV-11
ACID DISRUPTION AND TRANSGENIC MICROORGANISM FERMENTATION

Bioenergy also has the exclusive worldwide rights to all improvements under an on-going research agreement. A simplified view of the downstream process is shown in Figure IV-11 (feed preparation and hydrolysis are not shown).

BioEnergy states that its "...new organisms offer, for the first time, the ability to economically ferment five-carbon sugars to ethanol as well as offering the opportunity to hydrolyze economically the cellulose with enzymes." Complete data on the BioEnergy system and associated costs were not available. Again, Grethlein's

approach was used to project performance of a 5 and 25-million gallon per year ethanol plant in Hawaii, shown in Tables IV-7 and IV-8.

6. Concentrated Acid Hydrolysis, Acid Recycle, and Fermentation

Recognizing that the cost of acid, chemicals for neutralizing the acid, and gypsum disposal costs were constraints to using concentrated acid to hydrolyze lignocellulosic biomass, several laboratories have been investigating methods for separating and recovering acid from the hydrolysis mixture.^{46, 47} This approach contrasts with those described previously in that it uses concentrated acid hydrolysis with almost 100% acid recycle. Some of the most notable work in developing this technology has been the work done at the Tennessee Valley Authority and the University of Southern Mississippi.^{48, 49} Also active in this area is Arkenol Inc., a Nevada corporation, formed in 1992, to develop "thermal host" industrial applications and facilities for the co-generation electric power industry. Biomass-to-ethanol was selected as one of the complementary activities⁵⁰ for development.

FIGURE IV-12
CONCENTRATED ACID HYDROLYSIS, ACID RECYCLE, AND FERMENTATION

The process is made up of six basic unit operations: (1) feedstock preparation; (2) hydrolysis; (3) separation of the acid and sugars; (4) acid recovery and recycle; (5) fermentation of the sugars; and (6) distillation. A schematic of the concentrated acid hydrolysis, recycle, and fermentation process is provided in Figure IV-12.

Incoming biomass feedstocks are ground to reduce the particle size for introduction into the process equipment. The pre-treated material is then dried to a moisture content consistent with the acid concentration requirements for de-crystallization

(separation of the cellulose and hemicellulose from the lignin), then de-crystallized and hydrolyzed (degrading the chemical bonds of the cellulose) to produce hexose and pentose sugars at the high concentrations necessary for fermentation. Insoluble materials, principally lignin, are separated from the hydrolysate, by filtering and pressing, and then further processed into fuel or other uses.^{51, 52}

Commercially available resins are used to separate the acid from the sugar without diluting the sugar. The separated sulfuric acid is re-circulated and re-concentrated to the level required by the de-crystallization step. Any acid left in the sugar solution is neutralized with lime to make hydrated gypsum, $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, an insoluble precipitate that is separated from the sugar solution. In some cases this material can be sold as an agricultural soil conditioner.

At this point, the process yields a stream of mixed sugars (both C-6 and C-5) for fermentation. The sugars are mixed with nutrients and inoculated with yeast that converts both C-6 and C-5 sugars to fermentation beer (an ethanol, yeast and water mixture) and carbon dioxide. Yeast is separated from the fermentation beer by a centrifuge and returned to the fermentation tanks for reuse. Ethanol is separated from the beer by conventional distillation technology and dehydrated to 200 proof with conventional molecular sieve technology.

Much of the basic process and financial information was provided by Arkenol⁵³ although, as in other analyses, Hawaii-specific information was included as well. Evaluations of the 5 and 25 million gallon per year production systems are presented in Tables IV-7 and IV-8.

7. Acidified Acetone Extraction, Hydrolysis and Fermentation

Dr. Laszlo Paszner has developed a unique approach to the pre-treatment and hydrolysis of biomass for ethanol production.^{54, 55, 56, 57} The process, known as ACOS (Acid-Catalyzed Organosolv Saccharification), involves pre-treatment and grinding of biomass to make the material available for processing. The Organosolv process is shown in Figure IV-13.

FIGURE IV-13
ACIDIFIED ACETONE EXTRACTION, HYDROLYSIS, AND FERMENTATION

The lignin in the biomass is extracted by subjecting the material to acidified acetone at elevated temperature and pressure. Acetone is distilled from the lignin acetone mixture, leaving the lignin available for generation of electricity or process heat. The remaining residue consists of cellulose and hemicellulose that are now easily hydrolyzed to produce sugars for fermentation. The process has been designed to allow continuous extraction of the lignin, hydrolysis of the cellulosic material and fermentation of the sugars to ethanol^{58 59}. Based on information provided by Paszner, and estimates for system capital and operating costs in Hawaii, projections for an ACOS type facility producing 5 and 25 million gallons of ethanol per year are shown in Tables IV-7 and IV-8.

8. Traditional Fermentation of Sugars to Ethanol

Fermentation of sugars to ethanol, using commercially-available fermentation technology, provides a fairly simple, straightforward means of producing ethanol with little technological risk. The system modeled assumes the molasses is clarified, then fermented via cascade fermentation with yeast recycle. The stillage is concentrated by multi-effect evaporation and a molecular sieve is used to dehydrate the ethanol.⁶⁰

L. SUMMARY OF TECHNOLOGY COMPARISONS

1. Developmental Status of Technology Options

Although some of the steps in each process have been demonstrated at the pilot-scale or even commercial-scale level (e.g. grinding, screening, pre-hydrolysis, fermentation, distillation, etc.), the integrated systems described in subsections 1 through 7 of the previous section have not yet been demonstrated at a commercial scale. The newly developed steps in the technologies evaluated are generally at the early or late pilot scale stage of development.

The information below is for comparative purposes only, and may not represent the actual performance of any specific proprietary technology in Hawaii. As described earlier in this chapter, data from more complete systems was used to fill in missing parts from less completely described technologies. Due to uncertainties associated with pilot-scale results, and subsequent efforts to evaluate the technologies on a comparative basis, the extrapolations below should not be taken as final conclusions regarding performance of specific technologies in Hawaii.

2. Ethanol Production Costs and Sensitivity Analysis

As stated above, the purpose of these evaluations is to estimate the relative economic performance and appropriateness of the various technologies and to develop a rough estimate of the costs of production of ethanol from biomass sources in Hawaii. Tables IV-7 and IV-8 and Figure IV-14 provide summaries of the evaluation results and indicate the relative sensitivities of the processes to facility size and feedstock cost. Since the costs used in these comparisons are best estimates and may not be consistent for all technologies and processes, these estimates cannot be taken as an endorsement of one process over another. A more detailed site- and technology-specific analysis would be required for a detailed comparison of the processes.

TABLE IV-7
ETHANOL PLANT CAPITAL AND PROCESS COSTS
(BIOMASS COSTS NOT INCLUDED)

PROCESS	PROCESS COST ONLY (biomass = \$0 /ton)					
	25 MILLION GALLONS PER YEAR			5 MILLION GALLONS PER YEAR		
	CAPITAL (million \$)	\$/gallon ethanol	Biomass tons/day	CAPITAL (million \$)	\$/gallon ethanol	Biomass tons/day
Simultaneous saccharification and fermentation	\$81	\$0.52	820	\$26	\$0.65	164
Concentrated acid hydrolysis, neutralization and fermentation	\$99	\$1.14	952	\$32	\$1.29	190
Ammonia disruption hydrolysis and fermentation	\$124	\$0.60	863	\$40	\$0.83	173
Steam disruption, hydrolysis and fermentation	\$110	\$0.52	814	\$36	\$1.78	163
Acid disruption and transgenic microorganism fermentation	\$127	\$0.64	838	\$41	\$0.83	168
Concentrated acid hydrolysis, acid recycle and fermentation	\$72	\$0.94	833	\$23	\$1.04	167
Acidified acetone extraction, hydrolysis and fermentation	\$88	\$0.73	779	\$29	\$0.87	156

TABLE IV-8
ETHANOL PLANT PERFORMANCE SUMMARY
(BIOMASS COST INCLUDED)⁶¹

PROCESS	Biomass cost: \$50 / ton (dry matter)		Biomass cost: \$109/ ton (dry matter)	
	Ethanol \$/gallon, 25 million gallon-per-year plant	Ethanol \$/gallon, 5 million gallon-per-year plant	Ethanol \$/gallon, 25 million gallon-per-year plant	Ethanol \$/gallon, 5 million gallon-per-year plant
Simultaneous saccharification and fermentation	\$1.06	\$1.19	\$1.70	\$1.83
Concentrated acid hydrolysis, neutralization and fermentation	\$1.77	\$1.92	\$2.51	\$2.66
Ammonia disruption hydrolysis and fermentation	\$1.17	\$1.35	\$1.84	\$2.02
Steam disruption, hydrolysis and fermentation	\$1.06	\$1.22	\$1.69	\$1.86
Acid disruption and transgenic microorganism fermentation	\$1.20	\$1.38	\$1.85	\$2.03
Concentrated acid hydrolysis, acid recycle and fermentation	\$1.49	\$1.59	\$2.14	\$2.24
Acidified acetone extraction, hydrolysis and fermentation	\$1.24	\$1.39	\$1.85	\$1.99

Table IV-8 above shows the cost projection when the delivered cost of biomass⁶² is \$50 and \$108 per dry ton respectively.

FIGURE IV-14
ETHANOL PRODUCTION COST SUMMARY FOR 7 TECHNOLOGIES
(Feedstock Costs Ranging from \$0 to \$108 per Ton)

Figure IV-14 provides a graphic representation of the performance of the seven technologies in a 25 million-gallon-per-year plant, with biomass costs shown at \$0, \$50 and \$109 per dry ton.

The analysis does indicate that there are a variety of technologies that may produce ethanol, depending on amounts paid for feedstock, at costs ranging from less than \$1.00 to over \$2.60 per gallon. This is represented graphically in Figure IV-14. These ethanol production cost estimates do not take into account any potential revenues from by-products. By-products and markets for those products are discussed later in this report.

NOTE: In constructing this chart it was necessary to rely on claims made by those most familiar with the various technologies. It should be expected that some individuals may have been more conservative in their projections, and others may have been more optimistic. Also, these analyses were not site-specific, and significant differences would be expected for different sites, feedstocks, financing costs, labor costs, and so forth. These costs should be viewed as first-cut estimates only.

M. CONCLUSIONS REGARDING ETHANOL OPTIONS

As described in the previous sections, there are several approaches to the production of ethanol from lignocellulosic biomass. However, since the level of uncertainty associated with the analyses may be greater than the apparent differences between the technologies, it is not clear from this analysis what process is the "best." In spite of the previously-described uncertainties, variations in levels of optimism, etc., the analyses resulted in similar cost projections. This similarity lends a degree of confidence that, as the technologies mature, ethanol production costs in Hawaii will fall within this range.

-
- 1 Statement made by an engineer who has been building ethanol plants for over twenty years. He was referring to corn-based ethanol; however, many of the cost reductions and efficiency improvements would be valid for non-corn-based ethanol as well.
 - 2 "Edible" as used here means for human consumption.
 - 3 Bioenergy International, 1901 N.W. 67th Place, Suite E, Gainesville, FL 32606. Personal Communication, August 3, 1992.
 - 4 ARKENOL Inc., Mark Carver, 23293 S. Pointe Dr., Laguna Hills, CA 92653. Personal Communication, May 13, 1993.
 - 5 Paszner Technologies, Inc., Dr. Lazlo Paszner, 2683 Parkway Drive, Surrey, B.C., V4P 1C2 Canada. Description of the ACOS Process. Personal communication. November 20, 1993.
 - 6 Tigney Technology Inc. "A Technical Analysis of Partitioning and Transformations of Sugarcane Bagasse and Leaves by the Tigney Refinery System." Prepared for the Hawaiian Sugar Planters' Association, Aiea, Hawaii, January 28, 1991.
 - 7 Clausen, E.C. and J. L. Gaddy, (1987) "The Production of Chemicals and Fuels from Municipal Solid Waste," in *Global Bioconversions*, Vol. II, Donald L. Wise, Ed. CRC Press, Inc. Boca Raton, Fla. 62:73.
 - 8 Grethlein, H.W. and T. B. Nelson. (1992) "Projected Process Economics for Ethanol Production from Corn." Final Report under Agreement No. 58-1935-2-020, July 17, 1992 to the United States Department of Agriculture, Agricultural Research Service, North Atlantic Area, Eastern Regional Research Center, Philadelphia, Pennsylvania.
 - 9 Goldstein, I. S. and J. M. Easter. "An Improved Process for Converting Cellulose to Ethanol." *Technical Association of Pulp and Paper Industry Journal*, August, 1992, 135-140.
 - 10 Dale, B. and M. Holtzapfle. "Technical Summary of Ammonia Freeze Explosion." Report, Dept. of Chem. Engineering, Texas A&M University, March 1989.

- 11 Stuart, Dorsey, President Neugenesis, 2800 Woodlawn Drive, Honolulu, Hawaii 96822, personal communication.
- 12 Holtzapple, M. (1988) "Conversion of Grass to Highly-Digestible Animal Feed, Protein Concentrate, and Ethanol." Report, Dept. of Chem. Engineering, Texas A&M University, June, 1988.
- 13 Paszner, L. et al, (1986) "High-Yield Organosolv Process for Conversion of Cellulosic Biomass to Ethanol" in *Energy from Biomass and Wastes* (D. L. Klass, ed.), Institute of Gas Technology, Chicago, 1279: 1318.
- 14 National Renewable Energy Laboratory, Golden Colorado October 1993 Technology Brief NREL/MK-336-5674
- 15 Personal communication, Hawaiian Sugar Planters' Association, 1994.
- 16 Osgood and Dudley (1993), previously cited.
- 17 Kinoshita (1988), previously cited.
- 18 Grethlein, H.W. and T. B. Nelson. (1992) "Projected Process Economics for Ethanol Production from Corn." Final Report under Agreement No. 58-1935-2-020, July 17, 1992 to the United States Department of Agriculture, Agricultural Research Service, North Atlantic Area, Eastern Regional Research Center, Philadelphia, Pennsylvania.
- 19 Grethlein, H.E. and T. Dill. (1993) "The Cost of Ethanol Production from Lignocellulosic Biomass - A Comparison of Selected Alternative Processes." Final Report to the U. S. Department of Agriculture, Agricultural Research Service, under Specific Cooperative Agreement No. 58-1935-2-050, April 30, 1993.
- 20 The material presented in this section largely duplicates an analysis that was presented, in the DBEDT Report "Ethanol Production in Hawaii which was developed from the same data base.
- 21 Wyman, C. E., and N. D. Hinman. (1990) "Ethanol - Fundamentals of Production from Renewable Feedstocks and Use as a Transportation Fuel" in *Applied Biochemistry and Biotechnology*, The Humana Press Inc., 24/25, 735:753.
- 22 Wright, J. D. (1988) "Economics of Enzymatic Hydrolysis Processes," Prepared for the National AIChE Meeting 6-10 March 1988, New Orleans, SERI/TP-231-3310, UC Category: 246 DE88001134, 1:47.
- 23 Wright, J. D. (1989) "Evaluation of Enzymatic Hydrolysis Processes," in *Energy from Biomass and Wastes* (D. L. Klass, ed.) Institute of Gas Technology, Chicago, 1247: 1276.
- 24 Wright, J.D., et al. (1988) "Simultaneous Saccharification and Fermentation of Lignocellulose" in *Applied Biochemistry and Biotechnology*, The Humana Press Inc., 75:90.
- 25 Goldstein, I. S. and J. M. Easter. "An Improved Process for Converting Cellulose to Ethanol." *Technical Association of Pulp and Paper Industry Journal*, August, 1992, 135-140.
- 26 Bulls, M.M., T.M. Shipley, J.W. Barrier, R.O. Lambert and J.D. Broder. "Comparison of MSW Utilization Technologies - Ethanol Production, RDF Combustion, and Mass Burning." Tennessee Valley Authority Biotechnical Research Dept., Muscle Shoals, Alabama, Presented at the Southern Biomass Conference, Baton Rouge, Louisiana.
- 27 Barrier, J. W., M. R. Moore, and J. D. Broder. "Integrated Production of Ethanol and Co-Products from Agricultural Biomass." Tennessee Valley Authority Biomass Program, Muscle Shoals, Alabama, April, 1986.
- 28 Broder, J. D. and J. W. Barrier. "Producing Ethanol and Coproducts from Multiple Feedstocks." Tennessee Valley Authority, Muscle Shoals, Alabama, for the International Summer Meeting of the American Society of Agricultural Engineers, Rapid City, S. D., June 26-29, 1988.
- 29 Broder, J. D., J. Wayne Barrier and M. M. Bulls. "Producing Fuel Ethanol and Other Chemicals from Municipal Solid Wastes." Tennessee Valley Authority Biotechnical Research Dept., Muscle Shoals, Alabama, Prepared for the 1991 International Summer Meeting of The American Society of Agricultural Engineers, June 1991.

- 30 Grethlein, H.E. and T. Dill. (1993) "The Cost of Ethanol Production from Lignocellulosic Biomass - A Comparison of Selected Alternative Processes." Final Report to the U. S. Department of Agriculture, Agricultural Research Service, under Specific Cooperative Agreement No. 58-1935-2-050, April 30, 1993.
- 31 Dale, B. and M. Holtzapple. "Technical Summary of Ammonia Freeze Explosion." Report, Dept. of Chem. Engineering, Texas A&M University, March 1989.
- 32 Dale, B.E. "Biomass Refining: Protein and Ethanol from Alfalfa." *I&EC Product Research & Development*, 1983, vol. 22, p. 446.
- 33 Óoltzapple, M. (1988) "Conversion of Grass to Highly-Digestible Animal Feed, Protein Concentrate, and Ethanol." Report, Dept. of Chem. Engineering, Texas A&M University, June, 1988.
- 34 Grethlein, H.E. and T. Dill. (1993) "The Cost of Ethanol Production from Lignocellulosic Biomass - A Comparison of Selected Alternative Processes." Final Report to the U. S. Department of Agriculture, Agricultural Research Service, under Specific Cooperative Agreement No. 58-1935-2-050, April 30, 1993.
- 35 Dale, B. and M. Holtzapple. "Technical Summary of Ammonia Freeze Explosion." Report, Dept. of Chem. Engineering, Texas A&M University, March 1989.
- 36 Dale, B. E. "Biomass Refining: Protein and Ethanol from Alfalfa." *I&EC Product Research & Development*, 1983, vol. 22, p. 446.
- 37 StakeTech, Program Description. Stake Technology Limited, 2838 Highway 7, Norval, Ontario, Canada, L0P 1K0, 1993.
- 38 Taylor, John D. June 3, 1993, questionnaire response from StakeTech.
- 39 Grethlein, H.E. and T. Dill. (1993) "The Cost of Ethanol Production from Lignocellulosic Biomass - A Comparison of Selected Alternative Processes." Final Report to the U. S. Department of Agriculture, Agricultural Research Service, under Specific Cooperative Agreement No. 58-1935-2-050, April 30, 1993.
- 40 BioEnergy International, Project Information.
- 41 Derrickson, W.B. and D.E. Fowler. "Ethanol from Biomass Technology." presented to Pacific International Center for High Technology Research, May 14, 1992.
- 42 Derrickson, William B., President, Quadrex, personal communication, May 21, 1992.
- 43 BIOENERGY. "Ethanol from Biomass Technology." View Graph copies presented to PICHTR. May 14, 1992.
- 44 BioEnergy International, Project Information.
- 45 Derrickson, W.B. and D.E. Fowler. "Ethanol from Biomass Technology." presented to Pacific International Center for High Technology Research, May 14, 1992.
- 46 Numan, R. P., S. R. Rudge, and M. R. Ladish. (1987) "Sulfuric acid-sugar separation by ion exclusion." *Reactive Polymers*, 5: 55-61.
- 47 Nanguneri, S. R. and R. D. Hester. (1990) "Acid / Sugar separation using ion exclusion chromatography resins, A process analysis and design." *Separation Science and Tech.* 25, 1829-42.
- 48 Hartfield, S. and R. Hester. (1993) "Separation of acid and sugar by ion exclusion chromatography, An application in the conversion of cellulose to ethanol." *Proceedings, First Biomass Conference of the Americas*, Burlington Vermont, August, 1993: 1078-1083.
- 49 Hester, R. D., S. Hartfield, and G. E. Farina. (1993) "A process for separating acid - sugar mixtures using ion exclusion chromatography." *Proceedings, Tenth International Symposium on Alcohol Fuels*, Colorado Springs, Colorado. November, 1993: 716-723.
- 50 ARKENOL Inc., Mark Carver, 23293 S. Pointe Dr., Laguna Hills, CA 92653. Personal Communication, May 13, 1993.
- 51 ARKENOL Inc. View Graph copies presented to PICHTR. April, 1993.
- 52 Carver, Mark. (1993) General Manager, ARKENOL Inc. response to questionnaire. August 1993.

-
- 53 ARKENOL Inc. Concentrated Acid Hydrolysis. "History, Technology and Projects" Corporate publication, 1993.
 - 54 Paszner Technologies, Inc., Dr. Lazlo Paszner, 2683 Parkway Drive, Surrey, B.C., V4P 1C2 Canada. Description of the ACOS Process. Personal communication. November 20, 1993.
 - 55 Paszner Technologies, Inc. Dr. Laszlo Paszner, 2683 Parkway Drive, Surrey, B.C., V4P 1C2 Canada, Description of the ACOS Process. Technical Literature, 1993.
 - 56 Paszner, Laszlo. Paszner Technologies, Inc., response to questionnaire, November 1993.
 - 57 Prasner, L. et al, (1986) "High-Yield Organosolv Process for Conversion of Cellulosic Biomass to Ethanol" in *Energy from Biomass and Wastes* (D. L. Klass, ed.), Institute of Gas Technology, Chicago, 1279: 1318.
 - 58 Paszner Technologies, Inc., (1993) Dr. Lazlo Paszner, 2683 Parkway Drive, Surrey, B.C., V4P 1C2 Canada, Description of the ACOS Process. Technical Literature Provided,
 - 59 Paszner Lazlo., (1993) Paszner Technologies, Inc, 2683 Parkway Drive, Surrey, B.C., V4P 1C2 Canada, Response to Questionnaire , November 1993.
 - 60 Personal correspondence, Carroll R. Keim, April 1994.
 - 61 In constructing these tables it was necessary to rely on claims made by those most familiar with the various technologies. It should be expected that some individuals may have been more conservative in their projections, and others may have been more optimistic. Also, these analyses were not site-specific, and significant differences would be expected for different sites, feedstocks, financing costs, labor costs, and so forth. These costs should be viewed as first-cut estimates only.
 - 62 For the purposes of this evaluation, "prepared cane" provided the chemical composition assumed for "biomass."

V. ELECTRICITY OPTIONS [TASKS 5 AND 6]

At the onset of this program it was not clear if directing biomass to produce electricity, liquid fuels, or a combination of these options would provide the greatest benefits in energy recovery or economic performance. The sugar mills in the state of Hawaii are co-generation facilities which use bagasse biomass as boiler fuel to produce steam for factory operations and electricity for factory operations and sale into the existing grid. An evaluation of the status of facilities in the Hilo/Hamakua region was conducted to determine the feasibility of implementing possible biomass to electricity options. This analysis reviewed the electricity generating capacity of these facilities and defined potential options for stand alone electric generating facilities and/or increasing the efficiencies of these facilities.

The existing power generating facilities at Hilo Coast Processing Company (HCPC) and Hamakua Sugar Company (HSC) were reviewed in terms of process flow and operations, and power equipment and specifications for such equipment. An electric power generation and fuel inventories review was also conducted for both plants. From the information attained during these reviews, a preliminary thermoeconomic analysis for the existing facilities at both plants was conducted.

This analysis provided the basis for defining possible retrofitting options for the existing facilities at HSC and HCPC. The description and results of the analysis of possible retrofit options are presented in this chapter.

Information was then provided to the Bechtel Corporation on the most viable retrofit option and the defined biomass gasification option. A subcontract was awarded Bechtel to conduct an approximate cash flow analysis for these two possible stand alone electric options. The Bechtel report provided the foundation for determining capital costs and costs of operations for stand alone electric options.

A preliminary financial analysis for the three electric options - existing conventional steam option, retrofit option, and biomass gasifier option - as they affected the sugar mill's overall total income from operations was then conducted. Complete costs of operations for HSC and HCPC were not available due to the existing shut down mode of these facilities. In order to conduct an income from operations comparative analysis, complete costs of operations were obtained from a sugar mill which desired to remain anonymous.

A. POWER CYCLE THERMOECONOMIC ANALYSIS

A rudimentary thermodynamic analysis was conducted to infer values of boiler, cycle, and equipment efficiencies from gross operating data. A simplified representation of the energy conversion process of a combustion power system is given in Figure V-1. The chemical energy of the fuel, $Q_{\text{fuel}} = \text{mass of fuel} \times \text{HHV}$ (higher heating value), is released by combustion in the boiler. A portion of this energy, Q_b , is transferred to the working fluid of the power cycle, in the present application, steam, while the balance, Q_{loss1} , is lost to the environment in the form

of thermal and chemical energy of the discharged flue gases and solid residue (leaving losses), or by heat transfer to the surroundings (stray losses). Heat recovery techniques such as air preheat, bagasse drying, and the use of economizers reduce both leaving losses and the amount of fuel that must be burned to achieve a given value of Q_b . To characterize performance, a boiler efficiency, η_b , is defined as the fraction of fuel energy transferred to the power cycle working fluid.

FIGURE V-1
POWER CONVERSION PROCESS REPRESENTATION

$$\eta_b \equiv Q_b / Q_{\text{fuel}} . \quad (1)$$

The power cycle is a 2T heat engine that converts a portion of the energy input from the boiler to usable (exported) work, W_{out} . The difference between Q_b and W_{out} , Q_{loss2} , is rejected as waste heat to the environment. In conventional steam power systems, heat transfer in condensers accounts almost entirely for Q_{loss2} . In sugar factory cogeneration facilities, however, Q_{loss2} represents the sum of the steam energy that leaves the system by heat transfer to cooling water in the T-G condensers and during the sugar production process (i.e., as a result of the condensation of extracted process steam). Q_{loss2} must also account for the energy generated by mechanical drive units that is consumed in-house by plant equipment.

To assess the ability of the power cycle to produce exportable electrical energy, a cycle efficiency, η_c , is defined as the fraction of thermal energy input from the boiler that is converted to electricity that can be output to the utility grid:

$$\eta_c \equiv W_{\text{out}} / Q_b . \quad (2)$$

While, in the present analysis, it typically is assumed that W_{out} represents the energy or power measured at the T-G output terminals, in certain applications, it may be more useful to reduce this quantity by the amount of energy consumed by plant parasitics, such as fans and pumps, that are electrically-driven.

In addition to the parameters η_b and η_c , power system performance often is characterized by a heat rate, HR, that expresses the number of BTU's (British thermal units) that must be supplied, either from the fuel directly or as heat transfer

from the boiler, to produce 1 kWh of electrical energy. Following the convention employed by Hubbard et al. (1993), a heat rate based on fuel energy content is defined:

$$HR \equiv Q_{\text{fuel}}/W_{\text{out}} = \text{fuel Btu content/kWh exported} = 3412/(\eta_b \times \eta_c) . \quad (3)$$

From an operational standpoint, it also may be of interest to determine the quantity of fuel, M , required to produce 1 kWh of exportable electricity:

$$M \equiv \text{quantity of fuel/kWh exported} = HR/HHV . \quad (4)$$

If, for example, the units of HHV are [Btu/lb biomass (dry)], then M yields the lbs biomass (dry) that must be burned in the boiler to produce 1 kWh of electricity.

Finally, to determine the fuel cost associated with the production of 1 kWh of exportable electrical energy, FC , multiply M by the unit cost (say, \$/lb (dry) biomass or \$/bbl oil) of fuel delivered, in combustible condition, to the boiler:

$$FC \equiv \$/\text{kWh} = UC \times M = (UC \times 3412)/(HHV \times \eta_b \times \eta_c) , \quad (5)$$

where UC is the unit cost (delivered) of fuel in \$/lb (dry) (for biomass) or \$/bbl (for oil) and HHV must then be given as BTU/lb or BTU/bbl, respectively.

Heating values of boiler fuels of interest to the present investigation are available in the literature. The cost of fuel oil and coal delivered to the HSC and HCPC factories are documented in the HSPA database and studies have been undertaken to determine delivered costs of different varieties of prepared biomass fuel stocks. Examination of equations (3), (4), and (5) suggest, therefore, that a preliminary assessment of the viability of power generation options based at the HSC and HCPC factories may be completed if values of plant electrical output capacities and the parameters, η_b and η_c , can be estimated.

B. POWER GENERATION FROM BAGASSE ON THE ISLAND OF HAWAII

An evaluation of the existing steam power generation facilities at the Hamakua Sugar Company (HSC) and Hilo Coast Processing Company (HCPC) has been completed. A first-cut analysis was conducted to estimate power generation potential and conversion efficiencies of several alternatives for stand-alone operation, employing all or part of the installed equipment. Results are presented that can be applied to an economic assessment of these biomass electricity options.

1. Percentage of Big Island Electrical Production Represented by HSC and HCPC

The Hamakua Sugar Company (HSC) and Hilo Coast Processing Company (HCPC) cogeneration facilities located on the eastern coast of the island of Hawaii are scheduled to cease operation within the next two years. They make an important contribution to electricity production on the Big Island. Compounding the loss to the local economy, closure of these factories is expected to impact electric utility

services in the near term by reducing the reserve margin of installed power generation capacity. At present, HSC is capable of producing up to about 20 MW using three steam turbine-generators and a 5.4 MW diesel generator. The single HCPC turbine-generator is rated at 23.8 MW. In 1993, the combined firm capacity commitment of these two factories to HELCO (Hawaii Electric Light Company), the local utility, was 26 MW (8 MW from HSC; 18 MW from HCPC), or approximately 12.6% of the total 205.6 MW installed on the island. This 26 MW represents more than 50% of the 1993 reserve margin of 50.6 MW. Moreover, HCPC and HSC have been major power exporters since 1974 and 1982, respectively. For example, in 1991 HCPC and HSC exported a total of 181×10^6 kWh to the utility grid, representing about 22% of the electrical energy distributed to the general public that year.

HCPC exported and sold 77.3% (110.13×10^6 kWh) and 79.2% (118.92×10^6 kWh) of the electricity generated in 1986 and 1991, respectively, to the local utility, Hilo Electric Light Company (HELCO). In 1986, HSC exported and sold approximately 65% of the electricity generated by its cogeneration system. The value for total power exported to the utility grid by HSC in 1991 (62.06×10^6 kWh) provided by HSPA, however, also includes a substantial portion generated by a 5.400 MW diesel generator placed on-line that year. It is difficult, therefore, to determine precisely what percentage of the electricity produced by the steam cogeneration system was sold to HELCO in 1991 (HSC diesel-generated electricity was 19.16×10^6 kWh in 1991; hence 70.8% of steam- and diesel-generated electricity was exported). In 1991, the combined electricity sold into the grid by HSC and HCPC was 180.98×10^6 kWh. This represented approximately 20% of the total Big Island net electrical generation for 1991.³

Although HELCO has taken steps to minimize the effects of the announced closures, benefits associated with maintaining partial or full operation of the HSC and HCPC power generation facilities recommend that a study be conducted to evaluate the possibility of converting these sugar factories to dedicated power stations. Since both facilities were designed to burn bagasse as a primary fuel, and in consideration of the traditional agricultural base of the community, biomass would be the energy resource of choice for these power stations.

2. HSC & HCPC Cogeneration Systems Overview

The cogeneration systems installed at the HSC and HCPC factories are described in a report by Kinoshita (1990). The primary source for recent (through 1991) operating data was the Hawaiian Sugar Planters' Association (HSPA). The present investigation assesses the stand-alone power generating potential of the HSC and HCPC factories. Several operating options are proposed that involve moderate investments in the form of new or upgraded equipment. This strategy of utilizing existing equipment (and, hence, minimizing capital expenditures) results in favorable energy costs and can be implemented almost immediately; it is believed to represent the most viable near-term alternative.

Table V-1 provides a summary of information on the power boilers and related equipment.

TABLE V-1
POWER EQUIPMENT AT HSC AND HCPC

	HSC	HCPC
Boiler Manufacturer	Foster-Wheeler, Comb. Eng.	Babcock & Wilcox
Boiler Capacity (1000 lb/hr)	290, 100	330
Steam Pressure (psig)	610, 610	1260
Steam Temperature (°F)	800, 800	825
Heat Recovery Devices	A, D	A, D, E
Boiler Efficiency (%)	68-70	68-70
Emissions Control Devices	D, M, S	D, M
T-G Capacity (MVA)	5.0, 7.5, 9.4	28.0
Extraction Pressures (psig)	15	160, 12

Notes: Boiler Efficiency is for bagasse ($\leq 48\%$ moisture before dryer).

Heat Recovery Devices: A: air preheater; D: bagasse dryer; E: economizer

Emissions Control Devices: D: bagasse dryer; M: multicyclone dust collector; S: wet scrubber

The two HSC boilers can be fired with bagasse or No. 6 fuel oil, while the single HCPC boiler also burns coal. Both facilities employ high-, intermediate-, and low-pressure headers to distribute steam between turbine-generator (T-G) modules, mechanical drive units, and the sugarcane processing factory. At HSC, three T-Gs rated at 5.0, 7.5, and 9.4 MVA (17.5 kW total rated capacity, based on a power factor of 0.8) generate approximately 14.4 MW of electrical power under typical processing operation. Mechanical drives produce a nominal power output of 7,100 hp (5.3 MW), which is consumed internally by sugar factory equipment and power plant parasitics (i.e., IDFs, cooling water pumps, etc.). Approximately 73% of the steam is extracted at 15 psig (0.205 MPa) for factory processing use.

The HCPC cogeneration system employs a single 28.0 MVA T-G that produces between 23 and 24 MW of electrical power. Mechanical drives provide about 4600 hp (3.4 MW) to operate plant equipment and 48% of the steam is extracted at 12 psig (0.184 MPa) for processing use. Unlike the HSC power loop, which essentially comprises a simple Rankine cycle, the HCPC system utilizes regeneration (i.e., feedwater heating) to improve thermal efficiency. Approximately 15% of the total steam flow is extracted from the intermediate-pressure header at 160 psig (1.2 MPa) and is diverted through a closed feedwater heater.

From an (exportable) electrical power generation perspective, the HSC cogeneration system is poorly configured. A large fraction of the steam energy is expended in the plant mechanical drive units or is lost in sugar processing operations. Moreover, the multiple T-G modules complicate operation and probably compromise thermal efficiency. In comparison, the HCPC facility has a higher ratio of generated electrical power to plant mechanical drive output (6.8:1 vs. 2.7:1 for HSC) and a smaller extracted process steam fraction (48% vs. 73%).

3. HSC and HCPC Electrical Power Generation Capabilities

Table V-2 presents data on total electrical energy generated and fuels burned by the HSC and HCPC steam cogeneration systems for 1986 (Kinoshita, 1990) and 1991 (unpublished HSPA data).

TABLE V-2
ELECTRICAL POWER GENERATION AND FUEL INVENTORIES FOR 1986 AND 1991

	HSC 1986	HSC 1991	HCPC 1986	HCPC 1991
Generated (10^6 kWh)	63.25	68.47	142.43	150.22
Boiler Bagasse (dry tons)	246,008	159,606	135,986	104,951
Boiler Fuel Oil Equivalent (bbl)	54,708	90,018	129,480	234,886
Bagasse Heat. Value (10^9 Btu)	4,035	2,650	2,230	1,744
Fuel Oil Heat. Value (10^9 Btu)	345	567	816	1,480
Total Heat. Value (10^9 Btu)	4,379	3,217	3,046	3,224

Notes: In 1991, HCPC burned 8,318 tons of coal @ 0.3 ton coal equivalent to 1 bbl No. 6 fuel oil.

HHV of bagasse ranges from 8,200 to 8,300 Btu/lb.

Both HSC and HCPC burn No. 6 fuel oil w/HHV of 6.3×10^6 Btu/bbl.

4. Hamakua Sugar Company Assessment

In its current condition, the HSC steam cogeneration system is poorly configured to supply exportable electric power to the utility grid. Although the combined rating of the three turbine-generators exceeds 17 MW, they apparently have been designed or modified to operate at flows and pressures defined by the steam requirements of the sugar processing plant. These flow rates and inlet and outlet pressures are summarized in Table V-3. As a consequence, integrating these three prime movers into a dedicated steam power cycle would require that a number of the units be operated significantly off-design, with a resulting degradation in performance and an increased possibility of damage. It should be noted that efficiencies of the turbine-generators (inferred from operating data) are rather low even when employed as-designed. Furthermore, since a large fraction of steam (73%) was intended to be extracted for sugar processing use, the existing system lacks adequate condensing capacity. The single surface condenser is capable of handling only about 80,000 lb/hr of the 390,000 lb/hr of steam that the boilers can produce.

TABLE V-3
HSC STEAM TURBINE-GENERATORS

Nameplate Rating (MVA)	Steam Flow Rate (lb/hr)	Inlet Pressure (psig)	Outlet Pressure (psig)	Inferred T-G Efficiency (%)
9.4	80,000	235	2" Hg abs.	70
7.5	250,000	610	235	60
5.0	85,000	480	15	59

The HSC facility utilizes two steam generators: a 290,000 lb/hr Foster-Wheeler unit and a 100,000 lb/hr Combustion Engineering boiler. Both can produce steam at 610 psig and 800°F and are fired with bagasse or No. 6 fuel oil. The Combustion Engineering boiler is the older of the two steam generators. It was decommissioned once and later brought back into service. Discussions with sugar industry personnel suggest that its condition is marginally poor. The Foster-Wheeler boiler was damaged by a major fuel fire in 1991 and its current condition is unknown. Industry personnel have mentioned that, after the fire, problems occurred with fluctuating drum water levels, boiler tube failures, and air leaks into the combustion chamber. Given the relatively low operating pressures of these steam generators (which limit the attainable cycle efficiency) and the high probability that major repairs will be required in the near future, the long-term potential for utilizing the Foster-Wheeler and Combustion Engineering units as part of a dedicated biomass combustion power system does not appear to be good.

A final factor that argues against retrofitting the HSC facility to operate as a dedicated biomass power station is the poor condition of the bagasse handling system. Ideally, this system would be retained in a retrofitted plant, although modifications might be required to accommodate different biomass feed stocks. Over the past few years, failures in the HSC bagasse handling system (usually related to conveyers and carriers) have resulted in significant downtime. It is believed that correcting the existing problems would require a substantial capital investment.

Based on the difficulty of integrating the existing turbine-generators into a dedicated power system, the lack of condensing capacity, and the marginal condition of the steam generators and bagasse handling system, it is recommended that retrofit options not be considered for the HSC facility. In the long-term, it probably would be more cost-effective to consider the alternative of installing a new biomass gasifier/combined-cycle plant at this location.

5. Baseline Plant Performance

The HSC cogeneration cycle has installed T-G capacity (nameplate) of 21.9 MVA (approx. 18 MW). The two 610 psig boilers can produce 390,000 lb/hr of superheated steam at 800°F. At 100% availability, the system can generate approximately 153×10^6 kWh per year.

Kinoshita (1990) recommends $\eta_b = 0.68$ (68%) as an average value for the two HSC boilers burning bagasse with a moisture content of 48.5% upstream of the bagasse dryer units. It is estimated that flue gas drying reduces the moisture fraction to about 45% at the furnace inlet. While discussions suggest that the existing boilers can be employed successfully to burn other biomass fuels such as banagrass, eucalyptus chips, or leucaena, it should be emphasized that modifications may be required to utilize the existing dryer units. This is an important consideration since studies indicate that h_b decreases by about 0.6 percentage points for each 1 percentage point increase in fuel moisture content. HSPA operating data, which provide values of Q_{fuel} and Q_b , confirm that h_b lies in the range of 68% to 70%.

HSPA data indicate that η_b increases to 80% when No. 6 fuel oil is substituted for bagasse. This value is comparable, albeit slightly low, to typical boiler performance in conventional fossil fuel power plants.

Power cycle efficiency was estimated using annual generated electricity given in Table V-2 (taken as equal to W_{out}) and calculated values of Q_b obtained by multiplying the heating values of all bagasse and fuel oil burned during the year by the appropriate boiler efficiency. It should be observed that η_c determined in this fashion reflects a weighted average of the HSC electrical generation system being run in both a sugar processing mode (full process steam extraction and mill equipment operation) and a much more efficient weekend, or full-condensing, mode (minimal process steam extraction and plant parasitics). The 1986 data yield $\eta_c = 7.2\%$; 1991 data correspond to $\eta_c = 10.1\%$.

Medium capacity conventional fossil fuel power stations typically operate with a steam cycle efficiency of between 30% and 40%. The very low value of η_c calculated above was confirmed by a more detailed cycle analysis and reflects the large fraction of the available energy carried away by the process steam as well as the substantial internal parasitics of the mill.

6. Hilo Coast Processing Company Assessment

In contrast to the HSC factory, the HCPC cogeneration facility appears to offer good potential to operate as a dedicated biomass power station. The major components of the fuel handling and steam power generation systems are fairly new and efficient and have been well-maintained; hence, they are in good operating condition. Moreover, the HCPC facility was designed originally to satisfy a primary function of exporting electric power.

During sugar processing, the turbine-generator produces about 24 MW, with 48% of the steam being extracted for factory use. Off-season, the facility is operated in a full-condensing (no extraction) mode to generate 21 MW of power, of which 18 MW is exported to the utility grid. In order not to exceed the rated capacities of the L.P. turbine stages and the condenser, steam production and flow rate through the H.P./I.P. turbine stages is reduced from about 325,000 lb/hr to 200,000 lb/hr. An analysis conducted utilizing data provided by plant personnel indicates that the system heat rate corresponding to full-condensing mode operation is reasonably good. It is proposed, therefore, that one viable option may be to use the plant without modification as a dedicated biomass power station. A second option would fully exploit the power production potential of the boiler and the H.P./I.P. turbine stages by installing a second L.P. turbine-generator and surface condenser to utilize the additional steam.

The single HCPC cogeneration cycle T-G has a nameplate capacity of 28.0 MVA (approx. 23 MW). The 1260 psig boiler can produce 330,000 lb/hr of superheated steam at 825°F. At 100% availability, the system can generate approximately 208×10^6 kWh per year.

Kinoshita (1990) recommends $\eta_b = 0.68$ (68%) when burning bagasse with a moisture content of 48.6% upstream of the bagasse dryer unit. HSPA operating data indicate that η_b lies in the range $68\% \leq \eta_b \leq 71\%$. It is emphasized, once again, that fuel moisture content will strongly impact this parameter. As in the case of the HSC boilers, the high-pressure HCPC boiler appears to be able to accommodate other biomass fuel stocks. When burning fossil fuels such as No. 6 fuel oil or coal, η_b increases to 85%.

Following the procedure described in the Power Cycle Thermo-economic Analysis discussion, a weighted average of power cycle efficiency during sugar production and full-condensing mode operation of approximately 22% was calculated. This comparatively high η_c results from a number of factors, including relatively low fractions of extracted process steam and mill parasitics and also the use of regeneration to increase the average temperature at which energy is transferred in the boiler.

C. OPTIONS FOR FUTURE POWER GENERATION FROM BIOMASS IN THE REGION

An evaluation of the existing steam power generation facilities at the Hamakua Sugar Company (HSC) and Hilo Coast Processing Company (HCPC) has been completed. A first-cut analysis was conducted to estimate power generation potential and conversion efficiencies of several alternatives for stand-alone operation, employing all or part of the installed equipment.

This phase of the work focused on the evaluation of options for improving the capacity for electricity production in the Hilo/Hamakua region. The evaluations involved the following tasks :

- 1) Evaluate the option for a stand alone, co-fired, generating station based on biomass resources with backup capacity by a co-fired fossil fuel system to meet the electricity supply needs of HELCO in the next 5 to 10 years.
- 2) Determine the timing, type, size, and location(s) of biomass power plant(s) best suited to integrate into HELCO's resource needs for energy and capacity.

The analysis considers several options for producing exportable electrical power from biomass combustion, utilizing all or part of the equipment currently installed at the HSC and HCPC factories.

1. OPTIONS FOR ELECTRICITY PRODUCTION AT HAMAKUA

The three options for the Hamakua Sugar Company electricity production facility are:

a. HSC Option 1: Pseudo Processing Mode (Baseline)

To maximize capacity (MW) without modification of equipment, the cogeneration facility will be run in a "pseudo-processing" mode where the steam production in the boilers is essentially unchanged from the current operation. Process steam is extracted and condensed in the boiling house using water instead of cane juice as a coolant. Mechanical drives are run as necessary to ensure full steam flow rate through the T-Gs, and as required to power essential equipment such as IDFs, pumps, etc. This option clearly is not practical due to the large amount of wasted energy and is considered primarily to establish a baseline; however, such a pseudo-process may be required for brief periods of time when electrical output must be increased above the limits of operation for the full-condensing mode described below.

b. HSC Option 2: Full Condensing Mode (Minimal Modifications)

To maximize cycle efficiency utilizing the existing or slightly modified equipment, steam production in the boilers will be reduced to a value that results in no significant degradation of performance of any T-G stage or condenser, while, at the same time, bypassing the mechanical drives and steam extraction loop. All steam produced in the boiler will be condensed in the existing low pressure (about 1.5 psia) condensers. Since flow rates through the high-pressure turbine stages typically will be reduced significantly (by roughly the amount that currently is extracted), gross output power will fall. This full-condensing mode operation will have improved cycle efficiency at the cost of reduced capacity.

c. HSC Option 3: Utilize Existing Boilers; Upgrade Other Equipment

A preliminary assessment of the existing power equipment suggests that the most salvageable items are the boiler units (although the Combustion Engineering boiler at HSC is somewhat marginal). Since boilers typically represent the major capital cost item of a combustion power plant, it may be feasible to consider replacing the other power cycle equipment (i.e., T-Gs and condensers) with state-of-the-art units that will yield a significant increase in η_c . For this option, the maximum output capacity of a biomass power station utilizing the existing boilers is estimated.

d. Summary of HSC options

Table V-4 summarizes the results of the analysis of the three biomass electricity options for HSC.

TABLE V-4
ESTIMATED OPERATING PARAMETERS FOR BIOMASS OPTIONS FOR HSC

Option	Capacity (MW)	η_b (biomass/oil)	η_c	HR (biomass/oil)
1	14.4	0.70/0.80	0.11	44,300/38,800
2	7 - 9	0.70/0.80	0.24	20,300/17,800
3	30 - 40	0.70/0.80	0.30	16,200/14,200

Notes: Capacity is electrical power available for export after reduction by in-house parasitics.

η_b for biomass is for approx. 45% moisture at the furnace inlet w/heat recovery.

Units for Heat Rate, HR, are [Btu/kWh].

2. OPTIONS FOR ELECTRICITY PRODUCTION AT HILO COAST PROCESSING COMPANY

The two options for the Hilo Coast Processing Company electricity production facility are:

a. HCPC Option 1: Full Condensing Mode, No Modifications

A schematic diagram which identifies the major components of the HCPC biomass (bagasse) power cycle that are presently being utilized during full-condensing mode operation is presented in Figure V-2. Superheated steam is generated in a traveling-grate Babcock & Wilcox (BW) stoker furnace that can be fired with bagasse, coal, or No. 6 fuel oil. Boiler capacity is 345,000 lb/hr of steam (upgraded from an original value of 330,000 lb/hr) at 1260 psig and 825°F. Combustion air is supplied to the furnace by a 350 hp forced-draft (FD) fan and two overfire air fans having a combined motor rating of approximately 300 hp. Flue gases are exhausted using a 1000 hp induced-draft (ID) fan. Approximately 60% of these gases are diverted through a rotary drum bagasse dryer, designed originally for use with wood chips, and pass through a series of cyclones to remove entrained bagasse fines before being exhausted from a stack. A mechanically-driven 800 hp fan is employed to sustain the flow through this fuel drying system.

FIGURE V-2
HCPC FULL-CONDENSING MODE OPERATION SCHEMATIC

In addition to fuel drying, the HCPC plant pursues flue gas heat recovery through the use of an economizer and air preheater. Tests performed in the late 1980s indicate that the HCPC Babcock & Wilcox unit has a boiler efficiency, η_b , of between 68% and 71% when burning bagasse with a moisture content of about 48% upstream of the dryer. Biomass fuel moisture content strongly affects boiler efficiency: typically, efficiency decreases by approximately 0.6 percentage points for each 1 percentage point increase in fuel moisture. When burning conventional fossil fuels such as coal or oil, η_b increases to 85%.

The steam power cycle utilizes regeneration (i.e., closed feedwater heating) to improve thermodynamic performance. Superheated steam from the boiler expands through the high- and intermediate-pressure stages of a 16 stage, axial flow De Laval turbine before a portion (up to about 48,500 lb/hr) is extracted at about 160 psig to be condensed in the Yuba feedwater heater. The balance expands through the low-pressure turbine stages and is condensed in a titanium shell-and-tube De Laval surface condenser. The turbine is rated at 32,000 hp for 325,000 lb/hr of steam (1250 psig and 825°F at the inlet flange; 2" Hg absolute exit pressure) through the H.P. and I.P. sections and 155,000 lb/hr through the L.P. section. The turbine shaft is coupled to a 3600 rpm, TEFC, synchronous generator manufactured by Electric Machinery. This generator is rated at 28,000 kVA at a power factor of 0.85.

Thermal duty of the two pass surface condenser is 147.25 million Btu/hr, which corresponds to 155,000 lb/hr of steam at 950 Btu/lb. To satisfy this heat load, 14,750 gpm of 70°F cooling water must be provided. At HCPC, brackish cooling water is pumped from deep wells near the coastline and passes through the surface condenser once before being discharged. No cooling towers are employed to recycle this water. The salt and dissolved mineral content of the cooling water to date has posed only minor corrosion and fouling problems to the heat exchanger.

Power consumption by the fans and pumps comprises the primary parasitic losses in this system. Since the FD, ID, and overfire fans are damper controlled, their loads, totaling about 1.23 MW, do not scale with generator output.

Table V-5 summarizes information on the major components of the HCPC steam power cycle that would be employed for dedicated electricity generation.

As a first option, it is proposed that the HCPC facility be operated without modification in full-condensing mode to produce approximately 20.83 MW of electrical power at the generator terminals. If biomass is burned as a fuel, total back-work, including the fuel dryer fans and biomass conveyers and carriers, is estimated to be 2.83 MW, resulting in 18.0 MW exportable power. Figure V-3 shows the steam power loop corresponding to this option. Here, power output is limited by the flow capacities of the turbine low pressure stages and the surface condenser.

TABLE V-5
POWER EQUIPMENT INFORMATION

Component	Description	Comments
Steam Generator	Babcock & Wilcox traveling-grate stoker furnace; 345,000 lb/hr steam at 1260 psig, 825°F; brought into service 1973	
Turbine	De Laval axial flow turbine; 16 stages; 3600 rpm; 1250 psig, 825°F rated conditions at inlet flange; 2" Hg rated exhaust pressure; 32,000 hp rated output; brought into service 1973	
Electric Generator	Electric Machinery TEFC synchronous generator; 3600 rpm; 28,000 kVA @ 0.85 p.f.; brought into service 1973	rewound 1985 new rotor 1990
Surface Condenser	De Laval shell and tube cylindrical surface condenser; DWB; two pass; shop tubed; 13,700 ft ² cooling surface; 147.25 x 10 ⁶ Btu/hr thermal duty; 14,750 gpm cooling water supplied by 15,000 gpm pumps; brought into service 1973	B-111 Al. Brass tubes upgraded to titanium
Fans	1000 hp electric ID fan; 350 hp electric FD fan; (2) electric overfire air fans (approx. 300 hp total); 800 hp mech. drive bagasse dryer fan	
Feedwater Heater	Yuba shell and tube; approx. 48,500 lb/hr steam at 160 psig; brought into service 1973	replaced 1985

FIGURE V-3
HCPC ELECTRIC POWER GENERATION OPTION NO. 1

A thermodynamic analysis based on HCPC operating data was conducted to estimate the efficiency of the proposed steam power cycle. This efficiency then was employed to calculate heat rates and other relevant parameters for both biomass and fossil fuel combustion scenarios. Results are summarized in Table V-6.

The principal advantages of this option is that it requires minimal or no additional capital investment and that reliable operation has been demonstrated. Moreover, substitution of candidate biomass fuels such as banagrass, eucalyptus chips, or leucaena for bagasse probably can be performed without extensive modification of the fuel handling system or furnace (caution must be exercised, however, if the fuel is known to produce large quantities of slag when burned). Although conversion of the HCPC facility to utilize 100% coal or oil may be advantageous from the perspective of reducing the fuel cost of the generated electrical power, additional pollution control devices, such as scrubbers, may need to be installed. The associated costs could offset any potential benefits. Furthermore, a fossil fuel combustion plant does not provide a means to sustain agriculture in the host community.

TABLE V-6
OPERATING PARAMETERS FOR HCPC OPTION NO. 1

Parameter	Biomass Fuel	Coal or Fuel Oil
Steam generated [lb/hr]	203,500	203,500
Feedwater steam [lb/hr]	48,500	48,500
L.P. turbine steam [lb/hr]	155,000	155,000
Condenser duty [Btu/hr]	138.7×10^6	138.7×10^6
Gross power [MW]	20.83	20.83
Back-work [MW]	2.83	2.24
Back-work ratio [%]	13.6	10.8
Net power (exportable) [MW]	18.0	18.58
Steam cycle efficiency based on net power and heat transferred to steam in the boiler [%]	29.05	29.99
Boiler efficiency [%]	70	85
Heat rate [Btu/kWh exported]	16,789	13,385
Fuel required to produce 1 kWh exported	lb/kWh: bagasse: 2.023 banagrass: 2.125 Eucalyptus: 1.999 Leucaena: 2.023	No. 6 oil: 2.125×10^{-3} bbl/kWh Coal (@ 10,500 Btu/lb): 6.374×10^{-4} [ton/kWh]
Annual kWh generated @ 100% availability (kWh)	157,680,000	162,760,800
Max. annual fuel requirement	157,680 to 167,535 dry tons	345,800 bbl oil 103,740 tons coal

2. HCPC Retrofit Options 2a and 2b: Additional Low Pressure Turbine

The option described in the preceding section fails to exploit fully the power generation potential of the boiler and H.P./I.P. turbine rows. Due to limitations imposed by the existing L.P. turbine stages and surface condenser, less than two-thirds of the steam that could be produced is generated. A second option is proposed that would maximize the capacity of the HCPC facility by adding an additional low-pressure turbine-generator and condenser. Bechtel was contracted to conduct a more detailed analysis of this alternative.

Figures VI-4. and VI-5 present two variations of this option that produce essentially the same exportable power. The difference lies in the division of steam between the two L.P. turbines. In option 2a (Figure V-4), 323,500 lb/hr of steam flows into the existing turbine and 155,000 lb/hr expands through its low pressure stages resulting in an estimated output of 26.25 MW at the generator terminals. Since this exceeds the 23.8 MW generator rating, modifications may be required. In option 2b (Figure V-5), the 23.8 MW generator is operated at its rated capacity by reducing the L.P. stage steam flow rate to 122,437 lb/hr and redirecting the difference to the new turbine. Although this alternative avoids the cost and system downtime of a generator upgrade, it requires a larger (new) turbine-generator and condenser than option 2a.

FIGURE V-4
HCPC ELECTRIC POWER GENERATION OPTION NO. 2A

Increasing steam generation from 203,500 lb/hr to 323,500 lb/hr results in exportable power increasing by 78% to about 32 MW. Although feedwater and condenser cooling water pumping losses increase, the back-work ratio will decrease due to the fact that the fixed fan power consumption becomes a smaller fraction of the generated power. Estimated cycle efficiencies and heat rates change negligibly. Operating parameters for this option are shown in Table V-7.

The principal benefit of this option is the substantial increase in power generation capability. Since thermodynamic performance remains essentially unchanged from option no. 1, no reduction in the fuel cost of electricity is anticipated to be available to offset the penalty associated with the required capital investments. Specifically, an additional low-pressure turbine generator and surface condenser, as well as cooling water and feedwater pumps and pipelines must be procured and installed. Modifications also may be required to upgrade the utility interface and system controls.

FIGURE V-5
HCPC ELECTRIC POWER GENERATION OPTION NO. 2B

TABLE V-7
OPERATING PARAMETERS FOR HCPC OPTIONS NO. 2A AND 2B

Parameter	Biomass Fuel	Coal or Fuel Oil
Steam generated [lb/hr]	323,500	323,500
Feedwater steam [lb/hr]	48,500	48,500
Existing L.P. turb. steam [lb/hr]	155,000 (2a); 122,437 (2b)	155,000 (2a); 122,437 (2b)
New L.P. turb. steam [lb/hr]	120,000 (2a); 152,563 (2b)	120,000 (2a); 152,563 (2b)
Existing cond. duty [MBtu/hr]	138.7 (2a); 109.6 (2b)	138.7 (2a); 109.6 (2b)
New cond. duty [MBtu/hr]	107.4 (2a); 136.5 (2b)	107.4 (2a); 136.5 (2b)
Gross power [MW]	35.26	35.26
Back-work [MW]	3.52	2.92
Back-work ratio [%]	10.0	8.3
Net power (exportable) [MW]	31.74	32.34
Steam cycle efficiency based on net power and heat transferred to steam in the boiler [%]	29.3	29.9
Boiler efficiency [%]	70	85
Heat rate [Btu/kWh exported]	16,622	13,434
Fuel required to produce 1 kWh exported	lb/kWh: bagasse: 2.003 banagrass: 2.104 Eucalyptus: 1.979 Leucaena: 2.003	No. 6 oil: 2.132×10^{-3} [bbl/kWh] Coal @ 10,500 Btu/lb: 6.397×10^{-4} [ton/kWh]
Annual kWh generated @ 100% availability [kWh]	278,042,400	283,298,400
Max. annual fuel requirement	275,120 to 292,500 dry tons	603,990 bbl oil; 181,230 tons coal

Finally, it must be confirmed that the existing wells can supply the additional cooling water for the new condenser. Estimates of the costs of the turbine and condenser, based on recent vendor quotes for comparable items, are provided for reference in Table V-8. Total capital investment to upgrade net capacity from 18 MW to 32 MW is estimated to be approximately \$18 million.

TABLE V-8
TURBINE-GENERATOR AND SURFACE CONDENSER DESCRIPTIONS

Quantity	Option 2a	Option 2b
Turbine inlet press. [psig]	160	160
Turbine inlet temp. [°F]	426.3	426.3
Turbine exit press. [inHg]	2.0	2.0
Turbine steam flow [lb/hr]	120,000	152,600
Turbine isentropic eff. [%]	78.5% (min.)	78.5% (min.)
Turb./gen. speed [rpm]	3600	3600
Turbine rating [hp]	12,580 (min.)	16,000 (min.)
Generator rating [kVA]	10,600 @ 0.85 power factor	13,500 @ 0.85 power factor
Condenser duty [Btu/hr]	107.4×10^6	136.5×10^6
Condenser press. [inHg]	2.0	2.0
Est. cond. h-t surf. area [ft ²]	10,000	12,700
Est. cool. water flow [gpm]	10,700	13,600
Condenser tube material	Titanium	Titanium
Estimated T-G cost (complete incl. oil skid, control panel, sealing system)	\$3,600,000 (based on \$400,000/MW)	\$4,600,000 (based on \$400,000/MW)
Estimated surface condenser cost	\$500,000 (based on \$50/ft ²)	\$640,000 (based on \$50/ft ²)

TABLE V-9
ESTIMATED OPERATING PARAMETERS FOR BIOMASS OPTIONS FOR HCPC

Option	Capacity (MW)	η_b (biomass/oil)	η_c	HR (biomass/oil)
1	23 - 24	0.70/0.85	0.22	22,200/18,300
2	13 - 19	0.70/0.85	0.31	15,700/12,900
2a, 2b	27 - 37	0.70/0.85	0.33	14,800/12,200

Notes: Capacity is electrical power available for export after reduction by in-house parasitics.

η_b for biomass is for approx. 45% moisture at the furnace inlet w/heat recovery.

Units for Heat Rate, HR, are [Btu/kWh].

Evaluation of the economic viability of Options 2a and 2b require an estimate of the capital cost of replacement power components. In the near term, depending on the availability and price of suitable (i.e., prepared and dried) biomass fuel stocks, it appears that full-condensing mode operation, Option 1, might provide adequate performance and capacity at a minimal level of investment.

Specifications, as defined by PICHTR, for retrofit option 2b were provided to the Bechtel Corporation for a cash flow analysis. This analysis provided the foundation for determining capital and operational costs for retrofit option 2b. These costs are presented in Tables V-10 through V-12.

TABLE V-10
CAPITAL AND OPERATING COSTS FOR RETROFIT OPTION 2B
(BIOMASS COSTS = \$0 PER DRY TON)

Plant Feed Rate (dry tons/day)	709	Annualized Capacity Factor	85%	
Biomass Required (dry tons/yr)	220,000	Days of Operations Per Year	310	
Biomass Costs (\$/dry ton)	0	Depreciation Period (years)	25	
Gross Power Output (MWe)	35.3	Gross Electricity (kWh/yr)	262,843,800	
Exportable Electricity (kWh/yr)	236,038,200	Net Power Output (MWe)	31.7	
CAPITAL COSTS	\$	COST OF OPERATIONS	\$/Yr	\$/kWh
<u>Fuel Handling & Processing</u>				
Truck Unloader	250,000	<u>VARIABLE COSTS</u>		
Trucks	225,000			
Hoppers For Storage Silos	81,650	Subtotal Biomass	0	0.0000
Belt Conveyors	388,080			
Screen With Magnet	182,180	<u>Plant Operations</u>		
Cane Press	395,500	Direct Labor	978,000	0.0037
Shredder	200,000	Supplies	302,000	0.0011
Conveyor to Dryer	92,320	Maintenance and Repairs	270,000	0.0010
Dryer	978,820	Repair Reserves	100,000	0.0004
Conveyor to Hoppers	184,640	Miscellaneous	100,000	0.0004
Instrumentation & Controls	100,000	Subtotal Plant Operations	1,750,000	0.0067
Subtotal Fuel Handling Block	3,078,190			
		<u>Utilities</u>		
<u>Power Block</u>		Water	80,000	0.0003
Steam Turbine	4,187,000	Electricity	20,000	0.0001
Condenser/Cooling Tower	5,000,000	Subtotal Utilities	100,000	0.0004
Instrumentation & Controls	500,000			
Other Equipment & Materials	500,000	<u>Other</u>		
Subtotal Power Block	10,187,000	Waste Disposal	280,000	0.0011
		Subtotal Other	280,000	0.0011
<u>Other</u>				
Construction & Start-up	1,500,000	TOTAL VARIABLE COSTS	2,130,000	0.0081
Engineering	1,500,000			
Subtotal Other	3,000,000	<u>FIXED COSTS</u>		
		Management	360,000	0.0014
Contingency/Fee @ 15%	2,439,779	Lease Fees	0	0.0000
		Property Tax & Insurance	500,000	0.0019
TOTAL POWER PLANT COSTS	18,704,969	Depreciation	530,608	0.0020
		TOTAL FIXED COSTS	1,390,608	0.0071
		TOTAL COST OF OPERATIONS	3,520,608	0.0152

TABLE V-11
CAPITAL AND OPERATING COSTS FOR RETROFIT OPTION 2B
(BIOMASS COSTS = \$50 PER DRY TON)

Plant Feed Rate (dry tons/day)	709	Annualized Capacity Factor	85%	
Biomass Required (dry tons/yr)	220,000	Days of Operations Per Year	310	
Biomass Costs (\$/dry ton)	50	Depreciation Period (years)	25	
Gross Power Output (MWe)	35.3	Net Power Output (MWe)	31.7	
Gross Electricity (kWh/yr)	262,843,800	Exportable Electric (kWh/yr)	236,038,200	
CAPITAL COSTS	\$	COST OF OPERATIONS	\$/Yr	\$/kWh
<u>Fuel Handling & Processing</u>		<u>VARIABLE COSTS</u>		
Truck Unloader	250,000	Subtotal Biomass	10,999,991	0.0418
Trucks	225,000			
Hoppers For Storage Silos	81,650	<u>Plant Operations</u>		
Belt Conveyors	388,080	Direct Labor	978,000	0.0037
Screen With Magnet	182,180	Supplies	302,000	0.0011
Cane Press	395,500	Maintenance and Repairs	270,000	0.0010
Shredder	200,000	Repair Reserves	100,000	0.0004
Conveyor to Dryer	92,320	Miscellaneous	100,000	0.0004
Dryer	978,820	Subtotal Plant Operations	1,750,000	0.0067
Conveyor to Hoppers	184,640			
Instrumentation & Controls	100,000	<u>Utilities</u>		
Subtotal Fuel Handling Block	3,078,190	Water	80,000	0.0003
		Electricity	20,000	0.0001
<u>Power Block</u>		Subtotal Utilities	100,000	0.0004
Steam Turbine	4,187,000			
Condenser/Cooling Tower	5,000,000	<u>Other</u>		
Instrumentation & Controls	500,000	Waste Disposal	280,000	0.0011
Other Equipment & Materials	500,000	Subtotal Other	280,000	0.0011
Subtotal Power Block	10,187,000			
		TOTAL VARIABLE COSTS	13,129,991	0.0500
<u>Other</u>				
Construction & Start-up	1,500,000	<u>FIXED COSTS</u>		
Engineering	1,500,000	Management	360,000	0.0014
Subtotal Other	3,000,000	Lease Fees	0	0.0000
		Property Tax & Insurance	500,000	0.0019
Contingency/Fee @ 15%	2,439,779	Depreciation	530,608	0.0020
		TOTAL FIXED COSTS	1,390,608	0.0071
TOTAL POWER PLANT COSTS	18,704,969			
		TOTAL COST OF OPERATIONS	14,520,599	0.0571

TABLE V-12
CAPITAL AND OPERATING COSTS FOR RETROFIT OPTION 2B
(BIOMASS COSTS = \$106 PER DRY TON)

Plant Feed Rate (dry tons/day)	709	Annualized Capacity Factor	85%	
Biomass Required (dry tons/yr)	220,000	Days of Operations Per Year	310	
Biomass Costs (\$/dry ton)	106	Depreciation Period (years)	25	
Gross Power Output (MWe)	35.3	Net Power Output (MWe)	31.7	
Gross Electricity (kWh/yr)	262,843,800	Exportable Electric(kWh/yr)	236,038,200	
CAPITAL COSTS	\$	COST OF OPERATIONS	\$/Yr	\$/kWh
Fuel Handling & Processing		VARIABLE COSTS		
Truck Unloader	250,000	Subtotal Biomass	23,319,982	0.0887
Trucks	225,000			
Hoppers For Storage Silos	81,650	<u>Plant Operations</u>		
Belt Conveyors	388,080	Direct Labor	978,000	0.0037
Screen With Magnet	182,180	Supplies	302,000	0.0011
Cane Press	395,500	Maintenance and Repairs	270,000	0.0010
Shredder	200,000	Repair Reserves	100,000	0.0004
Conveyor to Dryer	92,320	Miscellaneous	100,000	0.0004
Dryer	978,820	Subtotal Plant Operations	1,750,000	0.0067
Conveyor to Hoppers	184,640			
Instrumentation & Controls	100,000	<u>Utilities</u>		
Subtotal Fuel Handling Block	3,078,190	Water	80,000	0.0003
		Electricity	20,000	0.0001
<u>Power Block</u>		Subtotal Utilities	100,000	0.0004
Steam Turbine	4,187,000			
Condenser/Cooling Tower	5,000,000	<u>Other</u>		
Instrumentation & Controls	500,000	Waste Disposal	280,000	0.0011
Other Equipment & Materials	500,000	Subtotal Other	280,000	0.0011
Subtotal Power Block	10,187,000			
		TOTAL VARIABLE COSTS	25,449,982	0.0968
<u>Other</u>				
Construction & Start-up	1,500,000	FIXED COSTS		
Engineering	1,500,000	Management	360,000	0.0014
Subtotal Other	3,000,000	Lease Fees	0	0.0000
		Property Tax & Insurance	500,000	0.0019
Contingency/Fee @ 15%	2,439,779	Depreciation	530,608	0.0020
		TOTAL FIXED COSTS	1,390,608	0.0071
TOTAL POWER PLANT COSTS	18,704,969			
		TOTAL COST OF OPERATIONS	26,840,589	0.1040

3. OPTIONS SUMMARY

The HSC and HCPC cogeneration facilities were evaluated to identify possible retrofit options to convert operations to dedicated electric power generation using biomass as the primary fuel. It was concluded that the HSC system is unsuitable for retrofit. It probably would be more practicable to salvage the HSC Foster Wheeler Boiler and procure new turbines and condensers. Two options were proposed for the HCPC facility: 1) continue operation with no modification other than those required by the bagasse handling system to accommodate different biomass fuels; exportable power is 18 MW; and 2) increase net capacity to 32 MW by the addition of a new low-pressure turbine-generator and condenser. The HCPC cogeneration facility has the potential to operate as-built as a dedicated power station that can produce approximately 13 to 19 MW of exportable electrical power at moderate efficiency burning either biomass, No. 6 fuel oil, or coal. The required capital investment for this upgrade is estimated to be approximately \$18 million.

D. TECHNOLOGY FOR FUTURE CONSIDERATION: GASIFICATION

Excluding the cost of biomass, the cost of producing electricity in the retrofitted HCPC plant is approximately 1.5 cents per kWh. The capital costs for implementing the biomass gasifier option is estimated at \$52.8 million. Excluding the cost of biomass, this would result in a cost of about 2 cents per kWh. We estimate that the gasifier option would increase net capacity to approximately 26 MW and would cost approximately \$53 million.

NOTE: At a biomass cost of \$0 per dry ton, the production costs of electricity for retrofit option 2b is approximately 1.5 cents per kWh while that of the gasifier option is approximately 2 cents per kWh. This apparent anomaly can be explained by the higher capital costs attributed to the biomass gasifier. When the biomass cost is \$0, the cost of electricity production is more greatly influenced by depreciation and direct labor, thus resulting in a higher production cost per kWh for the gasifier option than for the retrofit option.

Because of the high level of interest in evaluating the potential of continuing to use the sugar crop as a source of biomass, an evaluation of the two technologies was carried out using the cost of \$106 per dry ton as the cost of biomass. As shown in Figures VI-6, when the biomass cost is \$106 per dry ton (the current cost of prepared cane) the production costs of electricity for retrofit option 2 b is approximately 10 cents per kWh while that of the gasifier option is approximately 8 cents per kWh. At the current avoided rate of approximately 5 cents per kWh, prepared cane is not economically feasible as a source of biomass for producing electricity. However, there may be a variety of scenarios that involve production of multiple products and integration of waste resources that could present opportunities to produce electricity at near the avoided cost. These are presented in the economic summary (Section VII).

TABLE V-13
CAPITAL AND OPERATING COSTS FOR A BIOMASS GASIFIER
(BIOMASS COSTS = \$0 PER DRY TON)

Plant Feed Rate (dry tons/day)	400	Annualized Capacity Factor	85%	
Biomass Required (dry tons/yr)	124,100	Days of Operations Per Year	310	
Biomass Costs (\$/dry ton)	0	Depreciation Period (years)	25	
Gross Power Output (MWe)	29.0	Net Power Output (MWe)	26.2	
Gross Electricity (kWh/yr)	215,934,000	Exportable Electricity (kWh/yr)	195,085,200	
CAPITAL COSTS	\$	COST OF OPERATIONS	\$/Yr	\$/kWh
<u>Gasification Block</u>		<u>VARIABLE COSTS</u>		
Site Improvements	1,851,120	Subtotal Biomass	0	0.0000
Electric Power/Area Lighting	992,400			
Truck Unloader/Trucks	1,225,000	<u>Gasification</u>		
Circular Storage Silo System	4,248,190	Direct Labor	1,000,000	0.0046
Screen With Magnet	121,450	Supplies	300,000	0.0014
Cane Press/Shredder	363,660	Maintenance and Repairs	270,000	0.0013
Dryer System	535,570	Repair Reserves	300,000	0.0014
Fuel Feed Hopper System	613,310	Miscellaneous	100,000	0.0005
Gasifiers	1,211,330	Subtotal Gasification	1,970,000	0.0091
N2 Instrumentation Purge	20,000			
Cyclone Separators	916,590	<u>Utilities</u>		
Ash Collection & Disposal	300,520	Water	80,000	0.0004
Tar Crackers	559,060	Electricity	20,000	0.0001
Hot Gas Filter	125,360	Subtotal Utilities	100,000	0.0005
Alkali Getter	123,550			
Spray Quench	10,000	<u>Other</u>		
Exhaust Stack	70,780	Waste Disposal	150,000	0.0007
Processing Piping	536,140	Subtotal Other	150,000	0.0007
Instrumentation & Controls	350,000			
Subtotal Gasification Block	14,174,030	TOTAL VARIABLE COSTS	2,220,000	0.0103
<u>Power Block</u>				
Gas & Steam Turbines	13,250,000	<u>FIXED COSTS</u>		
HRSG	2,000,000	Management	300,000	0.0014
Instrumentation & Controls	775,000	Lease Fees	0	0.0000
Other Equipment & Materials	4,000,000	Property Tax & Insurance	500,000	0.0023
Subtotal Power Block	20,025,000	Depreciation	1,367,961	0.0063
<u>Other</u>		TOTAL FIXED COSTS	2,167,961	0.0100
Construction & Start-up	6,195,000			
Engineering	5,522,000	TOTAL COST OF OPERATIONS	4,387,961	0.0203
Subtotal Other	11,717,000			
Contingency/Fee @ 15%	6,887,405			
TOTAL POWER PLANT COST	52,803,435			

TABLE V-14
CAPITAL AND OPERATING COSTS FOR A BIOMASS GASIFIER
(BIOMASS COSTS = \$50 PER DRY TON)

Plant Feed Rate (dry tons/day)	400	Annualized Capacity Factor	85%	
Biomass Required (dry tons/yr)	124,100	Days of Operations Per Year	310	
Biomass Costs (\$/dry ton)	50	Depreciation Period (years)	25	
Gross Power Output (MWe)	29.0	Net Power Output (MWe)	26.2	
Gross Electricity (kWh/yr)	215,934,000	Exportable Electricity (kWh/yr)	195,085,200	
CAPITAL COSTS	\$	COST OF OPERATIONS	\$/Yr	\$/kWh
<u>Gasification Block</u>		<u>VARIABLE COSTS</u>		
Site Improvements	1,851,120	Subtotal Biomass	6,205,000	0.0287
Electric Power/Area Lighting	992,400			
Truck Unloader/Trucks	1,225,000	<u>Gasification</u>		
Circular Storage Silo System	4,248,190	Direct Labor	1,000,000	0.0046
Screen With Magnet	121,450	Supplies	300,000	0.0014
Cane Press/Shredder	363,660	Maintenance and Repairs	270,000	0.0013
Dryer System	535,570	Repair Reserves	300,000	0.0014
Fuel Feed Hopper System	613,310	Miscellaneous	100,000	0.0005
Gasifiers	1,211,330	Subtotal Gasification	1,970,000	0.0091
N2 Instrumentation Purge	20,000			
Cyclone Separators	916,590	<u>Utilities</u>		
Ash Collection & Disposal	300,520	Water	80,000	0.0004
Tar Crackers	559,060	Electricity	20,000	0.0001
Hot Gas Filter	125,360	Subtotal Utilities	100,000	0.0005
Alkali Getter	123,550			
Spray Quench	10,000	<u>Other</u>		
Exhaust Stack	70,780	Waste Disposal	150,000	0.0007
Processing Piping	536,140	Subtotal Other	150,000	0.0007
Instrumentation & Controls	350,000			
Subtotal Gasification Block	14,174,030	TOTAL VARIABLE COSTS	8,425,000	0.0390
<u>Power Block</u>				
Gas & Steam Turbines	13,250,000	<u>FIXED COSTS</u>		
HRSG	2,000,000	Management	300,000	0.0014
Instrumentation & Controls	775,000	Lease Fees	0	0.0000
Other Equipment & Materials	4,000,000	Property Tax & Insurance	500,000	0.0023
Subtotal Power Block	20,025,000	Depreciation	1,367,961	0.0063
<u>Other</u>		TOTAL FIXED COSTS	2,167,961	0.0100
Construction & Start-up	6,195,000			
Engineering	5,522,000	TOTAL COST OF OPERATIONS	10,592,961	0.0491
Subtotal Other	11,717,000			
Contingency/Fee @ 15%	6,887,405			
TOTAL POWER PLANT COST	52,803,435			

TABLE V-15
CAPITAL AND OPERATING COSTS FOR A BIOMASS GASIFIER
 (BIOMASS COSTS = \$106 PER DRY TON)

Plant Feed Rate (dry tons/day)	400	Annualized Capacity Factor	85%	
Biomass Required (dry tons/yr)	124,100	Days of Operations Per Year	310	
Biomass Costs (\$/dry ton)	106	Depreciation Period (years)	25	
Gross Power Output (MWe)	29.0	Net Power Output (MWe)	26.2	
Gross Electricity (kWh/yr)	215,934,000	Exportable Electricity (kWh/yr)	195,085,200	
CAPITAL COSTS	\$	COST OF OPERATIONS	\$/Yr	\$/kWh
<u>Gasification Block</u>		<u>VARIABLE COSTS</u>		
Site Improvements	1,851,120	Subtotal Biomass	13,154,600	0.0609
Electric Power/Area Lighting	992,400			
Truck Unloader/Trucks	1,225,000	<u>Gasification</u>		
Circular Storage Silo System	4,248,190	Direct Labor	1,000,000	0.0046
Screen With Magnet	121,450	Supplies	300,000	0.0014
Cane Press/Shredder	363,660	Maintenance and Repairs	270,000	0.0013
Dryer System	535,570	Repair Reserves	300,000	0.0014
Fuel Feed Hopper System	613,310	Miscellaneous	100,000	0.0005
Gasifiers	1,211,330	Subtotal Gasification	1,970,000	0.0091
N2 Instrumentation Purge	20,000			
Cyclone Separators	916,590	<u>Utilities</u>		
Ash Collection & Disposal	300,520	Water	80,000	0.0004
Tar Crackers	559,060	Electricity	20,000	0.0001
Hot Gas Filter	125,360	Subtotal Utilities	100,000	0.0005
Alkali Getter	123,550			
Spray Quench	10,000	<u>Other</u>		
Exhaust Stack	70,780	Waste Disposal	150,000	0.0007
Processing Piping	536,140	Subtotal Other	150,000	0.0007
Instrumentation & Controls	350,000			
Subtotal Gasification Block	14,174,030	TOTAL VARIABLE COSTS	15,374,600	0.0712
<u>Power Block</u>				
Gas & Steam Turbines	13,250,000	<u>FIXED COSTS</u>		
HRSG	2,000,000	Management	300,000	0.0014
Instrumentation & Controls	775,000	Lease Fees	0	0.0000
Other Equipment & Materials	4,000,000	Property Tax & Insurance	500,000	0.0023
Subtotal Power Block	20,025,000	Depreciation	1,367,961	0.0063
<u>Other</u>		TOTAL FIXED COSTS	2,167,961	0.0100
Construction & Start-up	6,195,000			
Engineering	5,522,000	TOTAL COST OF OPERATIONS	17,542,561	0.0812
Subtotal Other	11,717,000			
Contingency/Fee @ 15%	6,887,405			
TOTAL POWER PLANT COST	52,803,435			

Figure V-6 provides a summary of the sensitivity to biomass cost of biomass combustion and biomass gasification systems.

FIGURE V-6
SENSITIVITY OF ELECTRICITY PRODUCTION COST TO BIOMASS COST

Specific References (this section)

Hubbard, H.M., C.M. Kinoshita, Y. Wang, M. Staackmann, D. Ishimura, R.V. Osgood, L.A. Jakeway, N.S. Dudley, and A. Seki, "Investigation of Biomass-for-Energy Production on Molokai", Hawaii Natural Energy Institute Report, September, 1993.

Kinoshita, C.M., "Cogeneration in the Hawaiian Sugar Industry," Hawaii Natural Energy Institute Report, HNEI 90-1002, January, 1990.

Unpublished HSPA data.

Shleser, Dr. Robert, "Ethanol Production In Hawaii Report," Department of Business, Economic Development & Tourism, State of Hawaii Report, July 1994.

Personal Communication, Anonymous Sugar Mill

VI. ECONOMIC ANALYSIS [TASK 9]

A. SUMMARY OF RESULTS AND BASIS FOR THE ECONOMIC PERFORMANCE EVALUATIONS

The analysis of crops with potential to be used for ethanol production indicated that the sugarcane crop and sweet sorghum offered the most potential to supply biomass for ethanol production in Hawaii. Newspaper and municipal solid waste were also identified as reliable low cost sources of biomass to produce electricity or as a feedstock for ethanol production. A detailed analysis showed that Hawaii produces sufficient lignocellulosic waste biomass to produce ethanol volumes equal to 10% of the gasoline consumed annually.¹

Since the sugar crop was one of the most promising sources of biomass and information on the industry was abundant, this information was used to make projections on supply costs and potential for energy production. Although the analysis of ethanol production technology did not conclusively identify the best system, the Simultaneous Saccharification and Fermentation (SSF) approach showed sufficient promise to be used as the basic format for conducting sensitivity analyses. Prepared cane was selected as the crop component to be used on the cost comparisons. The specific assumptions for estimating ethanol and electricity production using prepared cane as the feedstock are outlined in Table VI-1.

B. TECHNOLOGY PERFORMANCE

For many years there has been a sustained interest in Hawaii in the comparison of the performance of using prepared cane for the production of sugar with using the same material to produce ethanol. Based on this information it is possible to evaluate a variety of scenarios for using prepared cane to produce various combinations of ethanol, sugar, and electricity.

Once all the costs of providing specific substrates were identified, it was possible to develop estimates of the cost of producing ethanol or any electricity based on selected technologies. As stated previously, there was insufficient information to make a definitive comparison of technologies for production of ethanol or electricity.

A format was developed to outline the economic performance of each of the technologies for ethanol production. As the basis for overall comparison, the simultaneous saccharification and fermentation (SSF) technology was selected as the base case.

TABLE VI-1
PARAMETERS FOR ETHANOL AND ELECTRICITY PRODUCTION

PARAMETER	PER HARV. ACRE	PARAMETER	PER HARV. ACRE
Crop Production time (years)	2.20	Fermentable Sugars Potential (tons/harv. acre)	25.48
Prepared Cane (wet tons/harv. acre)	109.82	Sugars-Annual Pot. (tons/acre/year)	11.58
Prep. Cane Cost/ton After Washing (wet)	\$31.35	TONS SUGARS/DRY TON BIOMASS	0.80
Prep. Cane Dry Wgt (%)	29%	Ethanol tons /ton sugar (theoretical)	0.50
Prep. Cane-dry Weight (tons/harv. acre)	31.85	Ethanol (pounds/gal)	6.58
Cost/ton After Washing (dry weight)	\$108.1	Ethanol Theo. Pot. (gal./harv. acre)	3,872
ALTERNATIVE COST 1 \$0.00/DRY TON	\$0.00	Sucrose to Ethanol- Conversion	92%
ALTERNATIVE COST 2 \$25.00/DRY TON	\$25.00	Released Sugars- Conversion efficiency	76%
ALTERNATIVE COST 3 \$50.00/DRY TON	\$50.00	Est. Ethanol Pot. (gal./harv acre)	2,943
Prepared Cane Yield (dry tons/harv. acre)	31.85	Est. Ethanol Pot. (gal./ton ferm sugars)	115.50
Sucrose (% dw in prepared cane)	43%	Ethanol Potential (gal./acre/year)	1,338
Sucrose (total dry tons/harv acre)	13.69	Ethanol Gal/wet ton processed	26.80
Sugar Current Sales Price (\$ per ton)	\$360.0	Ethanol Gal/dry ton processed	92.40
Sugar Production Cost (\$ per ton)	\$449.74	Ethanol Sales Price per gallon	\$0.90
Bagasse Dry (tons /harv. acre)	18.15	Bagasse (lbs/ton wet weight)	2,000
Bagasse % Dry Weight	52%	Bagasse wet (BTU/Lb)	4,200
Bagasse Wet (tons / harv. acre)	35	Bagasse (BTU/ dry ton)	16,153,846
Bagasse Value (\$/wet ton)	\$16.00	Boiler Efficiency %	60%
Molasses from Prep. cane (tons/acre)	3.40	Bagasse Effective BTU/pound (wet)	2,520
Molasses value (\$/ton)	\$42.00	Lignin BTU/pound (dry)	12,700
Sugar Content of molasses	40%	Lignin BTU/ton (dry)	25,400,000
Sugar in molasses (tons/acre)	1.36	Steam (BTU/lb)	1,300
Sucrose produced (tons/harv. acre)	12.33	Steam (lbs/lb bagasse)850 psig 730°F	1.94
Cellulose (% dw in prepared cane)	22%	Oil (BTU/ No.6 barrel)	6,300,000
Hemicellulose (% dw in prepared cane)	15%	BTU/kWh	12,600
Lignin (% dw in prepared cane)	11%	HECO (BTU /kWh)	10,500
Cellulose (tons/harvested acre)	7.01	Bagasse pounds/kWh electricity	2.50
Hemicellulose (tons/harv. acre)	4.78	kWh / wet ton Bagasse	666.67
Lignin (tons/harvested acre)	3.50	Electricity Generation Cost /kWh	\$0.02
Glucose (tons/harvested acre)	13.85	Bagasse used for factory %	50%
Fructose(tons/harvested acre)	6.85	Electricity Avoided Cost /kWh	\$0.05
Xylose (tons/harvested acre)	4.78		

Table VI-2 shows the capital and operating costs of a SSF plant using prepared cane as the substrate to produce 25 million gallons of ethanol per year. The format summarizes the costs of building a plant capable of processing prepared cane to ethanol. (Note: since the same format was used to compare all technologies are elements not required for the SSF process are displayed as 0.000.) For the purpose of presenting the format used in the analysis, the value of the biomass is arbitrarily set at \$50 per dry ton.

TABLE VI-2
25 MILLION GALLONS ETHANOL PER YEAR FROM PREPARED CANE

Plant feed rate (dry tons/day)		820	Biomass Source		Prepared cane
Million gallons /year production		25	Cost/dry ton		\$50
AREA	CAPITAL COSTS	MM\$	PRODUCTION COSTS	\$M/Yr	\$/gal
100	Biomass Preparation	3.609	Biomass	13,528	0.54
200	Pretreatment	11.461			
210	Recovery & Recycle	0.000	Denaturant	1,088	0.04
300	Hydrolysis	0.000	Acid	0	0.00
400	Fermentation (Unallocated)	0.000	Ammonia	0	0.00
410	Hexose Fermentation	11.239	Nutrients	0	0.00
420	Pentose Fermentation	3.134	Enzymes	0	0.00
500	Distillation & Dehydration	1.963	Yeast	0	0.00
600	By-Product Preparation	0.000	Other Chemicals	3,341	0.13
610	Stillage Evaporation	0.000	Total Raw Materials	17,957	0.72
700	Product Storage & Denature	1.583			
800	Utilities & General	0.000	Electricity/ Energy	-1,390	(0.06)
810	Boiler	10.009	Water	52	0.00
820	Non-Boiler Utilities	16.780	By-products	173	0.01
830	Environmental	2.074	Total Utilities	-1,166	(0.05)
840	Miscellaneous & Control	3.213			
900	Enzyme Production	1.361	Operators	1,520	0.06
			Laborers	1,000	0.04
1,000	Total Fixed Capital	66.426	Technicians	210	0.01
			Maintenance	800	0.03
1,010	Contingency	6.643	Fringe Benefits	882	0.04
1,020	Startup	3.321	TOTAL LABOR	4,412	0.18
1,030	Working Capital	4.982			
			VARIABLE COST TOTAL	34,732	1.39
	TOTAL CAPITAL	81.372	GEN. & ADMIN.	1,590	0.06
			Property Tax & Insur.	1,220	0.05
			TOTAL CASH	36,322	1.45
			ANNUAL CAPITAL COST	0	0.00
			Depreciation	2,441	0.10
			TOTAL PRODUCTION	36,322	1.06

The example presented does not include any financing costs in calculating the cost to produce a gallon of ethanol. The complete set of spreadsheets for all technologies is included in the Appendix.

1. Sensitivity Analysis

A sensitivity analysis was carried out to evaluate the impact of system size and biomass cost on the economic performance. The scaling factors used to evaluate the economic performance of systems sized for 5 and 25 million gallons per year are presented in Table VI-3.

TABLE VI-3
FACTORS USED IN THE SENSITIVITY ANALYSIS

Power Law Scaling Factor	0.7	Feedstock Cost, \$/ dry Ton	0, 25, 50,109
Contingency	10 %	Denaturant Cost, \$/gal	0.87
Start-up factor	5 %	Denaturant Use	5 %
Working Capital	7.50%	Fringe Benefits	25 %
Operating Days per Year	330	Capital Charge, %/yr.	0%
Personnel Scaling Factor	0.9		
Property Tax & Insurance	1.50%		

2. Biomass Cost

Varying the cost of prepared cane biomass at \$0, \$25, \$50, and \$109 per dry ton provided a way of looking at the impact of biomass cost on economic performance. An analysis of production costs in the sugar industry indicated that the cost of producing a ton of prepared cane was \$31.04 per wet ton or \$109 per dry ton. An analysis in which the biomass is valued at \$0 per ton provides a means of looking at the process costs exclusive of the cost of biomass. These results are presented in Table VI-4 below.

TABLE VI-4
ECONOMIC PERFORMANCE OF SSF BASED ON BIOMASS COST

	5 MILLION GALLON PER YEAR SSF PLANT				25 MILLION GALLON PER YEAR SSF PLANT			
CAPITAL COST	\$26,000,000				\$81,000,000			
Biomass (tons /day)	164				820			
PREPARED CANE	BIOMASS COST(\$/dry ton)				BIOMASS COST(\$/dry ton)			
	\$0	\$25	\$50	\$109	\$0	\$25	\$50	\$109
Ethanol Cost (\$/gallon)	\$0.65	\$0.92	\$1.19	\$1.83	\$0.52	\$0.79	\$1.06	\$1.70

Assumes equity funding -no capital charges

Varying the cost of biomass from \$25 to \$109/dry ton showed a cost of production ranging from \$0.92 to \$1.83 per gallon for an ethanol plant producing 5 million gallons per year. In contrast, a plant producing 25 million gallons per year resulted in production costs ranging from \$0.79 to \$1.70 per gallon.

3. Production Scenarios

As previously discussed, both HSC and HCPC have generated electricity using the steam generated by burning bagasse. It was of great interest to contrast the economic performance of the sugar industry as now operated, "business as usual", with the performance of a plant utilizing the harvested sugar crop to produce ethanol or various combinations of ethanol, electricity.

The section below provides a comparison of the financial performance per harvested acre of converting prepared cane to sugar, ethanol, and electricity with the performance of using prepared cane to produce electricity and sugar with three configurations: the existing electric generating facilities; a retrofit of the HCPC plant; and the addition of a biomass gasifier.

The following scenarios were evaluated using the costs developed for a plant producing 25 million gallons of ethanol annually using prepared cane valued at \$109.00 per dry ton as the feedstock. In order to achieve a common basis of comparison we used net income from operations per harvested acre as the basis of comparison. The scenarios are as follows:

Ethanol Scenarios

- a. Prepared cane to sugar - bagasse to electricity (business as usual).
- b. Prepared cane juice to ethanol (by simple fermentation), and fiber to ethanol (using SSF) - lignin to electricity.
- c. Sucrose to sugar and molasses - bagasse to ethanol (using SSF) - lignin to electricity.
- d. Sucrose to ethanol (by simple fermentation) - bagasse to electricity (by conventional combustion).

Electricity Scenarios

- e. Prepared cane to sugar - bagasse to electricity via conventional steam combustion (business as usual).
- f. Prepared cane to sugar - bagasse to electricity via retrofit option 2b.
- g. Prepared cane to sugar - bagasse to electricity using biomass gasifier.

a. Prepared cane to sugar, molasses, and energy (business as usual).

This represents the performance of the sugar industry as it is now practiced. Prepared cane supplied at a cost of \$38.00 per wet ton (or \$109.82 per dry ton²) is the source of biomass. Prepared cane is produced by burning the sugar crop in the field, harvesting, and washing. The resulting product is prepared cane. The cane is then crushed and squeezed to produce juice containing sucrose that is in turn processed to sugar. The remaining fiber or bagasse is then burned as boiler fuel to produce steam and electricity. Steam energy is used as processed heat and electricity for the mill and plantation. Any remaining electricity is sold to the utility at the avoided rate of 5 cents per kW hour.³ At current sugar prices, these assumptions result in a profit of about \$197 per harvested acre. A synopsis is presented in Table VI-5 below.

b. Prepared cane to ethanol by simple fermentation and SSF; lignin to electricity .

In this case, the prepared cane is produced as in the sugar industry. A cost of \$38.00 is applied to each ton of wet prepared cane biomass (or \$109.82 per dry ton). The cane is then crushed and squeezed to produce juice containing sucrose. The sucrose is fermented to ethanol in a conventional fermenter. The remaining fiber or bagasse is then treated with enzymes in a SSF system to release the sugars bound in the cellulose and hemicellulose. The released sugars in the mixture is then fermented by microorganisms to produce ethanol. Lignin, originally present in the fiber, largely remains intact and is used as boiler fuel to make process heat and electricity. In this case, additional fuel is required to provide enough energy for the operation. This approach results in a before tax loss of about \$3,500 per harvested acre. The results are summarized in Table VI-6.

c. Juice to sugar and molasses; bagasse to ethanol by SSF; lignin to electricity

Prepared cane is the raw material. The cane is crushed and squeezed to produce juice containing sucrose. The sucrose containing juice is processed to produce crystalline sugar (DA 96 sugar) and molasses. The remaining fiber (bagasse) is processed using the SSF technology to produce ethanol and lignin. The lignin is then used as a fuel to produce process heat and electricity. Once again, additional fuel is required to meet the energy needs of the process. This approach results in a profit of about \$123 per acre. If existing tax benefits are applied the net income is a positive \$291 per acre. The results are presented in Table VI-7.

TABLE VI-5

ESTIMATED INCOME FROM OPERATIONS PER HARVESTED ACRE				
Prepared Cane to Sugar & Molasses, Bagasse to Electricity (Business As Usual)			Scenario 1	
Total Cane Costs \$ 38/wet ton				
	YIELD tons, kWh or gallons	COST OF OPERATION \$ per ton of prepared cane	VALUE OF PRODUCT \$ per ton, kWh or gallon	NET VALUE \$ per harvested acre
REVENUES				
DA96 Sugar (tons/harvested acre)	12.16		\$360.00	\$4,377
Molasses (tons/harvested acre)	2.95		\$40.00	\$118
Ethanol-SF (gals/harvested acre)	0		\$0.90	\$0
Ethanol-SSF (gals/harvested acre)	0		\$0.90	\$0
Electricity sold (kWh/harvested acre)	8,181		\$0.05	\$409
TOTAL REVENUES				\$4,904
COSTS				
Prepared Cane (wet tons)	123.04			
Cultivation		\$18.96		(2,332)
Harvesting/Hauling		\$3.31		(407)
Cleaning/Shredding		\$2.17		(268)
Diffusion/Dewatering		\$0.29		(36)
Waste Disposal		\$0.01		(2)
Boiling House/Sugar Processing		\$1.62		(199)
Ethanol Production (SSF)				0
Ethanol Production (SF)				0
Additional Fuel Costs				0
Electricity production		\$2.69		(331)
Other Factory		\$3.40		(418)
G&A		\$5.80		(714)
TOTAL COSTS OF OPERATIONS		\$38.25		(\$4,706)
TOTAL INCOME FROM OPERATIONS (Per Harvested Acre)				\$197
	YIELD gallons or kWh		VALUE \$ per gal or kWh	NET VALUE \$ per harv. acre
CREDITS				
Federal Small Producer Credit	0		\$0.10	\$0
State Indigenous Fuels Prod Credit	0		\$0.00	\$0
Ethanol Tax Credits				\$0
Dedicated Feedstock Electric Credit	0		\$0.015	\$0
Electricity Tax Credits				\$0
TOTAL CREDITS				\$0
TOTAL VALUE WITH CREDITS				\$197

TABLE VI-6

ESTIMATED INCOME FROM OPERATIONS PER HARVESTED ACRE				Scenario 2
Prepared Cane Juice to Ethanol by Simple Fermentation, Bagasse to Ethanol by SSF, Lignin to Electricity				
Total Cane Costs \$ 38/wet ton				
	YIELD tons, kWh or gallons	COST OF OPERATIONS \$ per ton of prepared cane	VALUE OF PRODUCT \$ per ton, kWh or gallon	NET VALUE \$ per harvested acre
REVENUES				
DA96 Sugar (tons/harvested acre)	0.00		\$360.00	0
Molasses (tons/harvested acre)	2.95		\$40.00	118
Ethanol-SF (gals/harvested acre)	1,793		\$0.90	1,613
Ethanol-SSF (gals/harvested acre)	1,674		\$0.90	1,507
Electricity (kWh/harvested acre)	8,181		\$0.05	409
TOTAL REVENUES				\$3,647
COSTS OF OPERATIONS				
Prepared Cane (wet tons/cost)	123.04			
Cultivation		\$18.96		(2,332)
Harvesting/Hauling		\$3.31		(407)
Cleaning/Shredding		\$2.17		(268)
Diffusion/Dewatering		\$0.29		(36)
Waste Disposal		\$0.01		(2)
Boiling House/Sugar Processing		\$1.62		(199)
Ethanol Production (SSF)		\$7.79		(959)
Ethanol Production (SF)		\$6.88		(847)
Additional Fuel Costs		\$5.06		(622)
Electricity production		\$2.90		(357)
Other Factory		\$3.40		(418)
G&A		\$5.80		(714)
TOTAL COSTS		\$58.20		(\$7,161)
TOTAL INCOME FROM OPERATIONS (Per Harvested Acre)				(\$3,513)
	YIELD gallons or kWh		VALUE \$ per gal or kWh	NET VALUE \$ per harv. acre
CREDITS				
Federal Small Producer Credit	3,467		\$0.10	\$347
State Indigenous Fuels Production Credit	3,467		\$0.00	\$0
Ethanol Tax Credits				\$347
Dedicated Feedstock Electric Credit	0		\$0.015	\$0
Electricity Tax Credits				\$0
TOTAL CREDITS				\$347
TOTAL VALUE WITH CREDITS				(\$3,167)

TABLE VI-7

ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE				Scenario 3
Prepared Cane to Juice to Sugar & Molasses, Bagasse to Ethanol by SSF, Lignin to Electricity				
Total Cane Costs \$ 38/wet ton				
	YIELD tons, kWh or gallons	COST OF OPERATIONS \$ per ton of prepared cane	VALUE OF PRODUCT \$ per ton, kWh or gallon	NET VALUE \$ per harvested acre
REVENUES				
DA96 Sugar (tons/harvested acre)	12.16		\$360.00	\$4,377
Molasses (tons/harvested acre)	2.95		\$40.00	\$118
Ethanol-SF (gals/harvested acre)	0		\$0.90	\$0
Ethanol-SSF (gals/harvested acre)	1,674		\$0.90	\$1,507
Electricity (kWh/harvested acre)	8,181		\$0.05	\$409
TOTAL REVENUES				\$6,411
COSTS OF OPERATIONS				
Prepared Cane (wet tons)	123.04			
Cultivation		\$18.96		(2,332)
Harvesting/Hauling		\$3.31		(407)
Cleaning/Shredding		\$2.17		(268)
Diffusion/Dewatering		\$0.29		(36)
Waste Disposal		\$0.01		(2)
Boiling House/Sugar Processing		\$1.62		(199)
Ethanol Production (SSF)		\$7.79		(959)
Ethanol Production (SF)				0
Additional Fuel Costs		\$5.06		(622)
Electricity production		\$2.69		(331)
Other Factory		\$3.40		(418)
G&A		\$5.80		(714)
TOTAL COSTS		\$51.10		(\$6,288)
TOTAL INCOME FROM OPERATIONS (Per Harvested Acre)				\$123
	YIELD gallons or kWh		VALUE \$ per gal or kWh	NET VALUE \$ per harvested acre
CREDITS				
Federal Small Producer Credit	1,674		\$0.10	\$167
State Indigenous Fuels Production Credit	1,674		\$0.00	\$0
Ethanol Tax Credits				\$167
Dedicated Feedstock Electric Credit	0		\$0.015	\$0
Electricity Tax Credits				\$0
TOTAL CREDITS				\$167
TOTAL VALUE WITH CREDITS				\$291

Table VI-8

ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE				Scenario 4
Prepared Cane Juice to Ethanol by Simple Fermentation, Bagasse to Electricity				
Total Cane Costs \$ 38/wet ton				
	YIELD tons, kWh or gallons	COST OF OPERATIONS \$ per ton of prepared cane	VALUE OF PRODUCT \$ per ton, kWh or gallon	NET VALUE \$ per harvested acre
REVENUES				
DA96 Sugar (tons/harvested acre)	0.00		\$360.00	0
Molasses (tons/harvested acre)	2.95		\$40.00	118
Ethanol-SF (gals/harvested acre)	1,793		\$0.90	1,613
Ethanol-SSF (gals/harvested acre)	0		\$0.90	0
Electricity (kWh/harvested acre)	8,181		\$0.05	409
TOTAL REVENUES				\$2,141
COSTS OF OPERATIONS				
Prepared Cane (wet tons/cost)	123.04			
Cultivation		\$18.96		(2,332)
Harvesting/Hauling		\$3.31		(407)
Cleaning/Shredding		\$2.17		(268)
Diffusion/Dewatering		\$0.29		(36)
Waste Disposal		\$0.01		(2)
Boiling House/Sugar Processing		\$1.62		(199)
Ethanol Production (SSF)				0
Ethanol Production (SF)		\$6.88		(847)
Additional Fuel Costs				0
Electricity production		\$2.69		(331)
Other Factory		\$3.40		(418)
G&A		\$5.80		(714)
TOTAL COSTS		\$45.13		(\$5,553)
TOTAL INCOME FROM OPERATIONS (Per Harvested Acre)				(\$3,413)
	YIELD gallons or kWh		VALUE \$ per gal or kWh	NET VALUE \$ per harvested acre
CREDITS				
Federal Small Producer Credit	1,793		\$0.10	\$179
State Indigenous Fuels Production Credit	1,793		\$0.00	\$0
Ethanol Tax Credits				\$179
Dedicated Feedstock Electric Credit	0		\$0.015	\$0
Electricity Tax Credits				\$0
TOTAL CREDITS				\$179
TOTAL VALUE WITH CREDITS				(\$3,233)

d. Sucrose to ethanol (by simple fermentation) and bagasse to electricity (by conventional combustion)

In contrast with the SSF process that requires the use of acid and enzymes to liberate the sugar molecules that are bound in the cellulose and hemicellulose, this approach uses simple fermentation to convert the sucrose expressed in the juice to ethanol. The physical plant for this system is simplified and less costly.

Prepared cane is the raw material. The cane is crushed and squeezed to produce juice containing sucrose. The sucrose containing juice is filtered and put into a simple fermentation device where yeast converts the sucrose and remaining soluble sugars to ethanol. The remaining fiber (bagasse) is then used as a fuel to produce process heat and electricity. Any remaining electricity in excess of the process requirements is sold to the utility at the avoided rate of 5 cents per kilowatt hour. Economic performance of this scenario is summarized in Table VI-8.

The amount of prepared cane biomass required to produce the required volumes of ethanol is substantially greater than in the SSF approach. In this instance, the capital and operating costs for the facility were reduced because using just the sugar juice to produce ethanol did not require the expense of the specialized equipment and operating costs of hydrolyzing the fibrous material to the component sugars and fermentation of the 5 carbon sugars. In spite of these advantages, this approach results in a net loss of more than \$3,200 per acre

The possibility that there may be improvements in production technology that can have significant impact on the economic performance is most likely. Whether any combination of improvements can make this industry self-sustaining remains to be determined. This is the focus of programs now in progress at PICHTR, NREL, TVA, Oak Ridge National Laboratory and various university and government facilities.

4. Options for Producing Electricity From Biomass at the Sugar Mill.

The previous section reviewed the options for using the facilities at the sugar mill to produce ethanol and some energy with residual biomass or by-products. This section emphasizes the use of prepared cane biomass to produce electricity. The stand alone options for producing electricity using prepared cane as the source of biomass at the mill include :

- e. Conventional steam boiler using bagasse derived from prepared cane as the fuel in the existing facilities.* This is the same as *a.* above "business as usual".
- f. Simple retrofit option - optimizing the conventional steam system with improvements using prepared cane as the fuel source .*

- g. The biomass gasifier - optimizing the conventional steam system with improvements in the boiler and addition of a gasifier to process the bagasse to methane for the production of electricity.*

The following evaluation provides a projection of economic performance of the three approaches with biomass supplied at different prices.

The assumptions presented below apply to the analyses:

ASSUMPTIONS:	
Tons Bagasse /Barrel Oil.....	1.00
BTU/Barrel Oil.....	6,200,000
OIL (cost/barrel).....	\$16.00
Value/million BTU.....	\$5.16
Sugar Industry (BTU/kWh).....	10,250
Theoretical BTU/kWh.....	3,414
Sugar Industry (BTU/kWh).....	10,250

As in the above scenarios, income from operations was chosen as a method of conducting a preliminary financial analysis on the effects various electrical options have on the economic performance of a sample sugar mill. Tables VI-9 through VI-11 show the total income from operations for a possible sugar mill with each of the three electric options. Prepared cane costs are assumed to be \$38 per wet ton (\$109 per dry ton).

- e. Conventional steam boiler using bagasse derived from prepared cane as the fuel in the existing facilities.*

Total income from operations for the business as usual option - sugarcane processed to sugar and molasses, and bagasse converted to electricity in a conventional steam combustion power facility - is estimated at a profit of \$4,555 per harvested acre (Table VI -9). This scenario is based on a ten year average of data available and supporting assumptions and cannot be extrapolated to the entire industry.

- f. Simple retrofit option - optimizing the conventional steam system with improvements using prepared cane as the fuel source.*

The total income from operations for the business as usual option with inclusion of retrofit option 2b - sugarcane processed to sugar and molasses, and bagasse converted to electricity via the retrofit option 2b - described in Chapter VI is approximately \$350.00 per harvested acre (Table VI-10). This indicates a slightly positive cash flow from operations and warrants a more in depth financial analysis to determine if this cash flow is enough to create a viable business opportunity.

- g. The biomass gasifier - optimizing the conventional steam system with improvements in the boiler and addition of a gasifier to process the bagasse to methane.*

Total income from operations for the business as usual option with inclusion of a biomass gasifier option - sugarcane processed to sugar and molasses and bagasse converted to electricity via a biomass gasifier option described - in the Chapter VI is approximately \$94.00 per harvested acre. If tax credits are added the revenue per acre is \$1,193.00 (Table VI-11).

TABLE VI-9
BUSINESS AS USUAL WITH CONVENTIONAL STEAM COMBUSTION OPTION

ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE				
Sugar Company Harvesting With Open Field Burning (Scenario 1A)				
Sugarcane Processed To Sugar and Molasses/Bagasse Burned for Electricity				
(Business As Usual/Conventional Steam Combustion Option)				
	YIELD KWh or tons per harv. acre	COST OF OPERATION S \$/ton Prep cane	VALUE OF PRODUCT \$/ton or kWh	NET VALUE \$/harv. acre
REVENUES				
96DA Sugar (tons per harvested acre)	12.16		\$360.00	4,377
Molasses (tons per harvested acre)	2.95		\$40.00	118
Electricity Sales (kWh's/harv. acre)	95,332		\$0.05	4,767
Total Revenues				\$9,261
COSTS OF OPERATIONS				
Prep Cane (wet tons)	123.04			
Cultivation		\$18.96		(2,332)
Harvesting/Hauling		\$3.31		(407)
Cleaning/Shredding		\$2.17		(268)
Diffusion		\$0.14		(17)
Dewatering		\$0.15		(18)
Waste Disposal		\$0.01		(2)
Boiling House/Processing		\$1.62		(199)
Electricity Production		\$2.69		(331)
Other Factory		\$3.40		(418)
G&A Costs		\$5.80		(714)
Total Costs		\$38.25		(\$4,706)
TOTAL INCOME FROM OPERATIONS (per acre)				\$4,555
	YIELD gallons or kWh		VALUE \$ per gal or kWh	NET VALUE \$ per harvested acre
CREDITS/EXEMPTIONS				
DFS Electric Credit	0		0.015	\$0
Electricity Tax Credits				\$0
TOTAL VALUE WITH CREDITS				\$4,555

TABLE VI-10
BUSINESS AS USUAL WITH RETROFIT- OPTION 2B

ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE				
Sugar Company Harvesting With Open Field Burning (Scenario 1B)				
Sugarcane Processed To Sugar and Molasses/ Bagasse Burned for Electricity				
(Business As Usual/Inclusion of Retrofit Option)				
	YIELD KWh or tons	COST OF OPERATIONS \$/ton Prep cane	VALUE OF PRODUCT \$/ton or kWh	NET VALUE \$/harv. acre
REVENUES				
96DA Sugar (tons per harv. acre)	12.16		\$360.00	4,377
Molasses (tons per harvested acre)	2.95		\$40.00	118
Electricity Sales (kWh's/harv. acre)	15,769		\$0.05	788
Total Revenues				\$5,283
COSTS OF OPERATIONS				
Prepared Cane (tons/harvested acre)	123.04			
Cultivation		\$18.96		(2,332)
Harvesting/Hauling		\$3.31		(407)
Cleaning/Shredding		\$2.17		(268)
Diffusion		\$0.14		(17)
Dewatering		\$0.15		(18)
Waste Disposal		\$0.01		(2)
Boiling House/Processing		\$1.62		(199)
Electricity Production		\$2.81		(345)
Other Factory		\$3.40		(418)
G&A Costs		\$5.80		(714)
Total Costs		\$38.37		(\$4,721)
TOTAL INCOME FROM OPERATIONS (per acre)				\$561.92
	YIELD gallons or kWh		VALUE \$ per gal or kWh	NET VALUE \$ per harvested acre
CREDITS/EXEMPTIONS				
DFS Electric Credit	0		0.015	\$0
Electricity Tax Credits				\$0
TOTAL VALUE WITH CREDITS				\$562

TABLE VI -11
BUSINESS AS USUAL WITH BIOMASS GASIFIER

ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE				
Sugar Company Harvesting With Open Field Burning (Senario 1C)				
Sugarcane Processed To Sugar and Molasses/ Bagasse Burned for Electricity				
(Business As Usual/Inclusion of Gasifier Option)				
	YIELD KWh or tons	COST OF OPERATIONS \$/ton Prep cane	VALUE OF PRODUCT \$/ton or kWh	NET VALUE \$/harv. acre
REVENUES				
96DA Sugar (tons per harv. acre)	12.16		\$360.00	4,377
Molasses (tons per harvested acre)	2.95		\$40.00	118
Electricity Sales (kWh's/harv. acre)	22,391		\$0.05	1,120
Total Revenues				\$5,614
COSTS OF OPERATIONS				
Prepared Cane (tons/harv. acre)	123.04			
Cultivation		\$18.96		(2,332)
Harvesting/Hauling		\$3.31		(407)
Cleaning/Shredding		\$2.17		(268)
Diffusion		\$0.14		(17)
Dewatering		\$0.15		(18)
Drying		\$0.20		(25)
Waste Disposal		\$0.01		(2)
Boiling House/Processing		\$1.62		(199)
Electricity Production		\$2.90		(357)
Other Factory		\$3.40		(418)
G&A Costs		\$5.80		(714)
Total Costs		\$38.67		(\$4,757)
TOTAL INCOME FROM OPERATIONS (per acre)				\$857
	YIELD gallons or kWh		VALUE \$ per gal or kWh	NET VALUE \$ per harvested acre
CREDITS/EXEMPTIONS				
DFS Electric Credit	22,391		0.015	\$336
Electricity Tax Credits				\$336
TOTAL VALUE WITH CREDITS				\$1,193

TABLE VI-12
PROCESS ECONOMIC SUMMARY
(VALUES PER HARVESTED ACRE PREPARED CANE)

Scenario	Products Using Prepared Cane	Sales Value	Production Costs/Acre	Profit per acre	Tax Benefits Concessions	Profit After Tax
1	Prep. Cane to Sugar & Molasses & Energy	\$4,904	(\$4,706)	\$197	\$0	\$197
2	Juice to Ethanol Simple Fer Bagasse to Ethanol SSF	\$3,647	(\$7,161)	(\$3,513)	\$347	(\$3,167)
3	Juice to Sugar & Molasses SSF Bagasse to Ethanol	\$6,411	(\$6,288)	\$123	\$167	\$291
4	Juice to Ethanol- Bagasse to Electric	\$2,141	(\$5,553)	(\$3,413)	\$179	(\$3,223)
5	Prep. Cane to Sugar & Molasses Bagasse to Electric	\$4,990	(\$5,522)	(\$532)	\$123	(\$409)
6	Power Plant Retrofit	\$5,756	(\$5,400)	\$355	\$352	\$708
7	Addition of Cassifier	\$6,187	(\$6093)	\$94	\$481	\$575

Profitability is dependent on the location of the market. Serious consideration must be given to the costs of transporting ethanol produced on one island to meet the demands on another island. Factors such as back hauling to Oahu from the outer islands may present an opportunity to reduce these costs. All these factors must be considered in evaluating the business opportunity.

¹Ethanol Production in Hawaii 1994 Department of Business Economic Development and Tourism

²HSPA subcontract Report to PICHTR

³Avoided cost established by the PUC

VII. REGULATIONS, PERMITS, AND BENEFITS [TASK - 8]

A. ENVIRONMENTAL AND COMMUNITY RELATED CONCERNS AND BENEFITS

Environmental, safety, and health issues have taken on increased significance as it is increasingly necessary to adequately address these issues in order to obtain permits and approvals for new facilities. Biomass energy projects are no exception to this rule. Failure to recognize the time and costs associated with the permitting process could cause significant impacts to the overall project schedule. The legal and political aspects of establishing a new endeavor can be as difficult and time consuming as the actual physical implementation of the activity. Information was collected and consolidated on permit requirements. Environmental and community issues such as biodiversity, aesthetic value, and social acceptability of the proposed options were outlined to ensure that a potential project is in the widest sense "sustainable" in the area.

This section of the report provides overviews of the federal, state, and county permitting processes along with a comprehensive list of potential permits. Predictions of which permits are "likely" to be required for an ethanol and/or electricity production facility are presented below. In addition, the major permits and approvals, preliminary schedules and cost estimates are provided. Recommendations are made relating to permits and approvals.

There are environmental and social costs associated with all industrial processes. Technically informed individuals understand that the environmental costs of using biomass as feedstocks for energy production are much less than those associated with fossil fuels. But it is naive to assume that these notions are generally accepted in the community at large.

1. Environmental Issues - Benefits Versus Costs

There are costs and benefits associated with any development. In designing a project, it is essential to make every effort to minimize the risks and then make decisions, based on an analysis of the best available information, to balance the remaining risks and rewards.

Possible benefits of programs that emphasize use of biomass to produce energy include:

- a. Biomass to energy programs can contribute to the environmental quality of local areas as well as globally by:
 1. Reducing sulfur emissions caused by burning petroleum based fuels, thus contributing to the reduction in acid rain;
 2. Reducing carbon dioxide emissions, thus reducing the greenhouse effect resulting from fossil fuel combustion; (by using biomass to produce

electricity and transportation fuels, carbon dioxide stored by the plants during their growing season is recycled, upon emission, back into the crops of the next growing season, thus providing a short-term carbon dioxide closed loop and thereby creating a zero net carbon dioxide emission; reducing carbon monoxide); and

3. Improving combustion efficiency and increasing the octane rating of transportation fuels when gasoline is blended with 10% ethanol (carbon monoxide emissions is reduced by 10 to 30%) reducing volatile organic and aromatic hydrocarbon emissions (at blends greater than 10% ethanol); both potentially carcinogenic.
- b. Reducing risks associated with imported oil, i.e. potential for oil spills.
- c. Providing a means to reduce the problems associated with solid waste disposal and landfills.
- d. Making available a locally produced soil supplement.
- e. Contributing to the balance of payments on imports versus exports. The security position of Hawaii could be enhanced by offsetting the dependence on imported oil with locally produced and renewable energy. The state's balance of trade would be improved by reducing purchases of imported oil.

Possible costs or risks include:

- a. Soil erosion on highly erodible lands.
- b. Nutrient leaching resulting in declines in soil fertility.
- c. Soil and chemical runoff possibly resulting in regional adverse water quality.
- d. Adverse affects on infrastructure due to large trucks transporting biomass to the processing plant from the growing areas and fuel from the plant to the distribution outlets.
- e. Improper storage of biomass resulting in spontaneous combustion or proliferation of pests and insects.

2. Biodiversity

In Hawaii, the stewardship of large parcels of land has been successfully managed for over 150 years by the agriculture industry. A program of sustainable agriculture on these lands has been accomplished over this period of time. Simply stated, successful stewardship of land involves the preservation of land and life over time. The Hawaii sugar plantations have certainly accomplished this. Lands that are being considered for the development of biomass energy programs in the state of Hawaii are the same lands which have been under cultivation for the past 150 years. If these lands are removed from agricultural practices, they run the risk of being developed in ways which may prove to be much less forgiving and sustainable. Thus, perhaps, adversely affecting the conservation of biological diversity of these areas. Many of these lands have served as a successful buffer zone between development and Hawaii's tropical rain forests.

B. REGULATIONS

The regulatory processes should be considered a tiered system with the traditional separation of federal, state, and county authorities. There are some instances where regulatory responsibilities overlap or are shared among the various regulatory agencies. This tends to complicate the permitting process and may obscure the identity of appropriate regulatory agencies and the procedural sequence in which one can best obtain the required approvals.

1. Federal

As a general rule, the federal government's regulatory role in the state of Hawaii applies to work in navigable waters, work in and around airports and related facilities, and the protection of wetlands. For a sustainable biomass energy project, the federal role would probably include review and approval of environmental documents and involvement with protecting the natural resources (air, water, land).

2. State

Activities regulated by the State of Hawaii focus on public health, welfare, and the management of natural and human resources.

3. County

The County of Hawaii regulates activities that are more directly concerned with land use, zoning, and development of facilities.

C. PERMITS AND APPROVALS

It is advisable for applicants to seek assistance to determine permit requirements among the three levels of government. With a better understanding of the broader regulatory requirements, one can also determine which approvals can be obtained concurrently to help streamline the permitting process.

To assist with streamlining the permitting process, the State of Hawaii designated the Office of State Planning (OSP) as the lead agency for implementation of a consolidated application process (CAP). The consolidated application process facilitates regulatory processing by providing a forum in which applicants may present and discuss their projects with regulatory agencies. Through this pre-application meeting, government agency representatives learn about the project and comment on the expected permit requirements, applicants can better plan and prepare for the permit process by establishing more accurate time frames, and the possibility for concurrent processing and combined public hearings can also be established.

Each county government in the state of Hawaii operates a Central Coordinating Agency (CCA) to assist applicants in the processing of county permits and approvals.

The Central Coordinating Agencies focus principally on county regulatory processes and the streamlining of interagency processes within the county. For the County of Hawaii, the CCA is its planning department.

Based on the preliminary investigation undertaken for this study, the possible number of federal, state and county permits and approvals have been estimated to be as high as 100 for a biomass energy facility (See Table VII-1). This could include as many as 75 different agencies which could be included in the review process. For an ethanol and/or electricity production facility built in conjunction with an existing sugar company facility, the actual numbers of permits and agencies are expected to be much less.

Table VII-1
Estimated Maximum Number of Permits and Agencies

	Federal	State of Hawaii	County of Hawaii	Total
No. Permits/Approvals	24	48	35	107
No. Agencies	20	30	25	75

1. Federal Permits

The primary federal agencies expected to be involved in the permitting process includes: Department of Energy (DOE), Environmental Protection Agency (EPA), and Department of Agriculture (DOA). In addition, there could be a number of secondary agencies that may also be involved such as the National Park Service (NPS), U.S. Fish and Wildlife Service (USFWS), and National Marine Fisheries Service (NMFS).

2. State Permits

The primary State of Hawaii agencies expected to be involved in the review/approval process includes: Department of Health (DOH), Office of State Planning (OSP), and the Office of Environmental Quality Control (OEQC). In addition there could be a number of secondary agencies that may also be involved such as the Department of Land and Natural Resources (DLNR), Land Use Commission, and Department of Transportation (DOT).

3. County Permits

The primary county of Hawaii agencies expected to be involved in the permitting process includes: Planning Department, Department of Public Works, and the Fire Department. In addition there could be a number of secondary agencies that may also be involved such as the Engineering Department, Department of Water Supply, and Wastewater Department.

For a comprehensive list of federal, state, and county permits and approvals and the primary responsible agencies refer to Table VIII-2. ¹ These tables were, in a large part, modified from a briefing document entitled "Energy Management and Permitting Analysis"². Possible permits and agencies responsible have been organized into five broad categories:

1. Environmental Review,
2. Environmental Permits,
3. Construction & Operating Permits,
4. Land Use Permits, and
5. Utility Permits.

**Table VII-2
List of Possible Permits and Approvals**

CATEGORY	FEDERAL	STATE OF HAWAII	COUNTY OF HAWAII
Environmental Review	EPA/DOE - (1) NEPA EA/FONSI or EIS DOE - (1) Environmental Baseline Study	OEQC - (1) SOH EA/ND or EIS OSP - (1) Clearinghouse Review	Planning Department - (1) SOH EA or EIS Review
Environmental Permits	EPA - (1) PSD (3) Hazardous Waste Generator (3) TSD (1) Ocean Dumping Review (2) Injection Control Review COE - (2) Section 404 USFWS - (2) Endangered Species NMFS - (2) Clean Water Act (2) Marine Mammal Exemption (2) Endangered Species Park Service - (1) PSD (1) Visibility Analysis Coast Guard - (3) Notice-Submerged Cable (3) Notice-Cable Laying (3) Bridge/Causeway Permit	DOH - (1) PSD (1) Health Risk Assessment (2) Variance from Pollution Control (1) NPDES (1) Water Quality Certification (2) Injection Control Permit (2) Underground Storage Tank (2) Hazardous TSD Permit (1) SARA Reporting (2) Zone of Mixing Permit (2) Drinking Water Approval (2) Private Wastewater Permit OSP - (1) CZM Consistency	DPW - (2) Discharge of Water Permit (2) Industrial Wastewater Discharge Certificate

Table VII-2
List of Possible Permits and Approvals
 (cont'd.)

CATEGORY	FEDERAL	STATE OF HAWAII	COUNTY OF HAWAII
Land Use Permits	DOA, SCS - (1) Prime Farmland (1) 1995 Farm Bill FAA - (3) Notice-Construction Within Airspace	Land Use Commission - (2) Special Use Permit (2) District Boundary Amendment DLNR - (2) Conservation District Use (2) Easement for Use of state Lands (2) Well Drilling/Modification (2) Groundwater Control Area (3) Stream Channel Alteration (2) Historic Site Review (3) Forest Reserve Special Permit (2) Wildlife Sanctuary Entry Permit (3) Closed Watershed Entry Permit (3) Natural Area Reserves (3) Geothermal Resource Subzone	CCA - (1) SMA Permit (2) Special Use Permit (3) Subdivision Permit (2) Flood Hazard Controls (2) Land Use Boundary Amendment (3) Development Plan Amendment (3) General Plan Amendment (2) Zoning Change DPW - (1) Grading, Grubbing, Excavating (1) Road Use/Modification Permit (2) Sewer Connection Permit (2) Flood Hazard District Permit (3) Subdivision Approval
Land Use Permits	DOA, SCS - (1) Prime Farmland (1) 1995 Farm Bill FAA - (3) Notice-Construction Within Airspace	OSP - (1) SMA Permit* HCDA - (2) Community Development Permit DOT - (3) Energy Corridor Lease (3) Airport Zone Land Use Permit	Dept of Planning - (2) Special Use Permit (1) SMA Permit (3) Shoreline Setback Variance (3) Subdivision Land Permit (3) Community Plan Amendment (2) Conditional Use Permit (3) Urban Land Use Classification (2) Historic District Application
Utility Permits	FERC - (1) Utility/QF Filings	PUC - (2) Transmission Line Approval (3) Special Order No. 6 Exemption (2) General Order No. 7 (2) Public Convenience /Necessity	CCA - (2) Public Utility Joint Venture

D. APPROVALS

As part of this study, an attempt was made to predict which permits and approvals would "Likely" (= "1"), "Possibly" (= "2"), or "Unlikely" (= "3") be required for an ethanol and/or electricity production facility located in the Hamakua/Hilo region of the Big Island. To address the broadest possible scenario, the following assumptions and information were used to make the predictions:

- The facility would be newly constructed (not a retrofit of existing factory).
- The facility would be of commercial size (25 million gals/year or 25 MW).
- Preliminary information was provided by OSP, OEQC, Hawaii Planning Department, HSC, HCPC, HELCO, HECO, HCDA, and DOA.
- Information from experience gained by PICHTTR during the Biomass Gasifier Facility permitting process would be made available.
- Site may be located within a General Industrial District, so Special Use Permit (SUP) may not be required.
- Site would be located near or on existing HSC or HCPC factory site.

1. Electricity Versus Ethanol Option:

There are slight differences in the permitting requirements between a stand alone electricity facility, a stand alone ethanol facility, and an electricity/ethanol facility. The ethanol facility may require more permits relating to waste streams, SARA. Reporting of any hazardous chemicals, and a DOT permit for ethanol transportation. The electricity facility may have more air emission concerns, and therefore, may require more permits. Since there are relatively few differences between the two options, it is expected that a combination electricity/ethanol production facility would have similar permitting requirements to the two stand alone options.

Table VIII-3 summarizes all the permits and approvals that are considered to "likely" be required for a biomass energy facility in the Hamakua/Hilo region on the island of Hawaii. If the existing HSC or HCPC factory is retrofitted, the modified plant could possibly be 'grandfathered' under existing permits which would reduce the number of new permits required dramatically. Although this is possible, it is not likely due to recent environmental concerns associated with existing factories (i.e. HSC) and stricter environmental regulations today.

Table VII-3
Likely Permits and Approvals

CATEGORY	FEDERAL	STATE OF HAWAII	COUNTY OF HAWAII
Environmental Review	EPA/DOE - (1) NEPA EA/FONSI or EIS DOE - (1) Environmental Baseline Study	OEQC - (1) SOH EA/ND or EIS OSP - (1) Clearinghouse Review	Planning Department - (1) SOH EA or EIS Review
Environmental Permits	EPA - (1) PSD (1) Ocean Dumping Review Park Service - (1) PSD (1) Visibility Analysis	DOH - (1) PSD (1) Health Risk Assessment (1) NPDES (1) Water Quality Certification OSP - (1) CZM Consistency	DPW - (1) Discharge of Waters Permit (1) Industrial Wastewater Discharge Certificate
Construction & Operating Permits		DOH - (1) ATC (1) PTO (1) Allowable Noise Levels Permit DLNR - (1) Pressurized Vessel Permit DOT - (1) Ethanol Transportation	CCA - (1) Grading, Grubbing, Excavating (1) Building Permit DPW - (1) Building, Electrical, Plumbing Fire Department - (1) Combustible Liquid/Gas Tanks Installation/Use Permits
Land Use Permits	DOA, SCS - (1) Prime Farmland (1) 1995 Farm Bill	OSP - (1) SMA Permit*	CCA - (1) SMA Permit DPW - (1) Grading, Grubbing, Excavating (1) Road Use/Modification Permit Dept of Planning - (1) SMA Permit
Utility Permits	FERC - (1) Utility/QF Filings		

Figure VII -1
Permit Timing

Critical

Milestone

Noncritical

Summary

Progress

Rolled Up

Figure VII -1
Permit Timing (continued)

Critical

Noncritical

Progress

Milestone

Summary

Rolled Up

Figure VII -1
Permit Timing (continued)

ID	Name	Duration	Year 1				Year 2				Year 3			
			Qtr 1	Qtr 2	Qtr 3	Qtr 4	Qtr 1	Qtr 2	Qtr 3	Qtr 4	Qtr 1	Qtr 2	Qtr 3	Qtr 4
70	Water Quality Certification	152d												
71	Prepare WQC Application	6w												
72	Submit WQC Application	0d												
73	Review of WQC Application	4w												
74	Public Notification	2w												
75	WQC Public Hearing	0d												
76	Determination on WQC	0d												
77	WQC Issued	0d												

Critical

Noncritical

Progress

Milestone

Summary

Rolled Up

E. RECOMMENDATIONS FOR SUCCESSFUL PERMITTING

Based on PICHTR's experiences with the Biomass Gasifier Facility (BGF) and the precursory investigation of permitting issues for this Sustainable Biomass Energy Study, the following recommendations are believed to be appropriate for both a generic project/location and for a specific dedicated biomass energy production facility in the Hamakua/Hilo region of the Big Island:

- To insure that permits and approvals are obtained expediently, it is recommended that this work be started as soon as possible.
- To avoid duplication of effort, make as early as possible a determination of which federal, state, and county permits and approvals will be required for the proposed project.
- In order to avoid delays and confrontations with the general public, it is recommended that early and frequent consultations, meetings, and communications be initiated with community and environmental groups.
- It is also recommended that early and frequent consultations, meetings, and communications be initiated with federal, state, and county agencies. This is necessary to develop detailed planning, coordination of the permitting process, and verification that requirements are being met and concerns are being addressed.
- To streamline the complex permit/approval process, it is recommended that a coordinated effort be developed among all three levels of government (i.e., determine lead agency for duplicated documents, such as EA. or EIS, and prepare single comprehensive documents where possible, limit overlapped effort, combine public meetings and hearings, etc.). This will help minimize the delays and added costs often attributed to the regulatory requirements.
- Develop a detailed and integrated permit/approval schedule.
- Define and "fix" the proposed facility's design as early as possible. Avoid substantial design changes that might lead to requirements by certain agencies to submit new or revised documents.
- Pay particular attention to accurately preparing and completing all documents, otherwise significant delays in the permitting process could result. Try to anticipate all problems, concerns, and comments ahead of time and address them in the documents.
- Obtain, as early as possible, specifications for all input, output, and product streams (composition, quantity, etc.). This information is necessary to prepare documents such as ATC, EA./EIS, and HRA, and to determine if any special permits are required. If existing information is unavailable or unacceptable for proposed project, this would more than likely create a need to perform PDU-like

testing. Unplanned testing would significantly impact the project schedule and costs and could impact what permits are required.

- Consider and investigate alternative sites and biomass conversion processes. This is especially important to meet EA/EIS requirements. If possible, try to get consensus from public, groups, and agencies on "best" site in advance. This may eliminate any need to obtain data for more than one site.
- Make every effort possible to develop and maintain good working relations with and the support of newspaper, magazine, radio, and television reporters.
- Avoid "negative/scary buzz" words, such as "experimental", "steam-explosion", and "acid", in project literature, verbal, and written communications.
- Expect the permits/approvals process to take time and money. Avoid the unrealistic assumption that "it will be easy". There is no such thing as a "one-stop" permitting (i.e., it took PICHTR two years to obtain the BGF Authority to Construct from the State Department of Health).

Specific References:

1. "An Applicant Guide to State Permits and Approvals for Land and Water Use Development", Hawaii Coastal Zone Management (CZM) Program, Department of Planning and Economic Development (CZM now regulated by Office of State Planning), June 1986.
2. "Energy Management and Permitting Analysis, Hawaii Integrated Energy Policy Development (HEP)" Briefing Document, RCG/Hagler, Bailly, Inc., October 4, 1991.

F. BENEFITS

1. Social Acceptability and Community Support

As indicated in the draft of the *Hilo-Hamakua Economic Development Plan*, preliminary "community vision" for the Hilo/Hamakua region, established through a series of community workshops, is one of integrated and diversified agriculture. It has been envisioned by members of the community that they would like to see small family farms run as interconnected operations which utilize recycling and multiple use self-sufficiency systems with coordinated planting, harvesting, processing and marketing efforts. They would like to see strong linkages established with the University of Hawaii's technical resources and field work. They would also like to see continued community development through grassroots planning processes. An integrated biomass energy program fits nicely with much of this community vision. An industry based on energy production from sustainable biomass would support the initial efforts and vision of community based economic development programs.

The opportunity to retain the agricultural base through the production of dedicated biomass feedstock supports and preserves the historic way of life in these rural communities. The development of this industry further supports rural economic development by strengthening and diversifying the economic base. Results of a study for the Southeastern Regional Biomass Energy Program showed significant potential to increase income and employment and improve the region's balance of trade through the use of biomass to energy programs. These programs diversified the regions economic base, while providing a means for retaining an economically sustainable agriculture based community.³

2. Employment

Hawaii County's residential population was approximately 130,500 (approximately 11% of The state's total) in 1992 and it is projected to be over 200,000 by the year 2010. The county of Hawaii's residential population is currently centered in two areas - South Hilo/Puna (approximately 65,000) and North Kona (approximately 25,000).⁴

The county of Hawaii accounts for about 9 percent of the state's total personal income. Total job count on the Big Island for January through June 1993 was 60,230. Total civilian labor force for the same period was 67,620. Historically, the county of Hawaii has been economically dependent upon agriculture. The agriculture industry directly accounts for roughly 10 percent of the Big Island employment.

The three regions most severely effected by the pending decline in the sugar industry on the island of Hawaii are; Hamakua (approximately 5,500 residents), North Hilo (approximately 1,500 residents), and Ka'u (approximately 4,500 residents). Hamakua Sugar Company employed approximately 750 people directly at full production. Mauna Kea Agribusiness Company employs approximately 450 people directly and Ka'u Sugar Company employs approximately 350 people directly.

Together, approximately 1550 people will lose their jobs, accounting for approximately 13 percent of the islands total job count.

The loss of these jobs will obviously have a severe direct affect on the economies of these rural areas and the county overall. The indirect multiplier effect will further depress the economic outlook. First Hawaiian Bank estimates an indirect income multiplier for the sugar industry to be approximately 1.3. That is, a \$100 dollar direct contribution from the industry would, through successive re-spending, create another \$30 additional dollars of contribution to the economy of the region.⁵

Assuming a biomass to ethanol industry developed, sustained agriculture would result in the establishment of ethanol refineries. An ethanol refinery would have economic advantages over a petroleum refinery. Petroleum refineries create about 1/2 to 1 full-time in-plant production job for every 1 million gallons of gasoline produced. Ethanol refineries employ 3-5 full-time people in-plant for every 1 million gallons of ethanol produced. If ethanol were to gain a 10 percent or 40 million gallon market share in Hawaii, the industry would create an additional 150-180 in-plant jobs. This may be nearly comparable to the in-plant jobs created in producing the 400 million gallons of gasoline Hawaii consumes. If ethanol were to replace 50 percent of the gasoline consumed in Hawaii the resulting industry could create more than 2,000 production jobs. In-plant jobs represent only one aspect of the economic benefits ethanol production brings rural communities. Equally important is the beneficial impact of keeping, in the producing region, millions of dollars in business spending.

3. Economic Advantages

A dollar spent on producing ethanol is largely spent inside the state while a significant amount of the dollar spent on producing gasoline leaves the state. For example, 45 to 55 cents of each gallon of gasoline represents the cost of crude oil, all of which leaves the state. On the other hand, at least 40 to 50 cents of the cost of producing a gallon of ethanol represents the cost of producing the biomass crop, all of which is grown within the state.

Studies of California's agricultural economy report a combined inter-industry multiplier of 2.5 or more, representing the multiple of farm revenues constituting total inter-industry effects on the state economy. In contrast, Hawaii's tourism multiplier is estimated to be 2.04. Because multipliers generally cluster around 2.0 for most industries, agriculture's higher multiplier typically means that investments in agricultural production generate economy-wide impacts at least 25 percent greater than that associated with other industries.⁶

¹ Acronyms used in this table are presented in Appendix

² Prepared by RCG/Hagler, Bailly, Inc. (October 4, 1991).

-
- ³ Source: Meridian Corporation. 1989. "Economic Impact of Industrial Wood Energy Use in the Southeast Region of the U.S.: Volume 1: Summary Report", Southeast Regional Biomass Energy Program, administered for the U.S. Department of Energy by the Tennessee Valley Authority, Muscle Shoals, Alabama.
- ⁴ Source: Supplemental To Economic Indicators, First Hawaiian Bank. September/October 1993 and The State of Hawaii Data Book, 1990)
- ⁵ Source: Supplement to Economic Indicators - First Hawaiian Bank, September/October 1993).
- ⁶ Source: The Mason Research Foundation. Division of Simco Incorporated of U.S.A.Phase One Final Report. Chinese Tallow Tree Research. Growing Oil On Trees. June 30, 1992.)

VIII. MARKETS, PRODUCTS, & CO-PRODUCTS [TASK - 10]

The two primary products envisioned from a sustainable biomass energy facility are electricity and ethanol for use as a liquid transportation fuel. Potential markets for primary products, co-products, and potential higher value products which may result from conversion of biomass are outlined below. Emphasis has been given to local market potential.

A. MARKETS FOR ETHANOL

Liquid transportation fuels may be shipped between islands as well as out of state. Therefore, potential markets are located:

- on the island of Hawaii;
- on other islands (Maui, Lanai, Molokai, Oahu, Kauai) in the state;
- in the continental United States; and
- in other countries.

This section focuses on markets within Hawaii (1 and 2 above). Consideration of other markets may be warranted at a later date. However, they are not addressed here due to their complexity and sensitivity to fluctuations in commodities markets, international exchange rates, etc.

1. State Demand

Transportation fuels (primarily gasoline and diesel, with some propane) account for about 20% of the state's total petroleum demand. Gasoline represents about 94% of the ground transportation energy demand in the state. Use of gasoline in Hawaii ranges from 23 million gallons per year on Kauai, to 56 million gallons per year on the island of Hawaii, to over 250 million gallons per year on Oahu. In 1992, the statewide total was about 382 million gallons per year. Demand for ground transportation fuels is expected to continue and to increase.¹ Gasoline consumption by county is shown in Figure VIII-1.

2. Potential Markets for Fuel-Grade Ethanol

Ethanol may be used in the transportation fuel market in the following ways:

- In a 10% blend with gasoline, in existing vehicles;
- In the form of a gasoline additive such as ethyl tertiary butyl ether (ETBE) or tertiary amyl ethyl ether (TAEE), in existing vehicles;
- In an 85% blend with gasoline (85% ethanol, 15% gasoline) in specially-designed light duty vehicles (cars or vans); and

- As a "neat" fuel (100% ethanol) in specially-designed heavy duty vehicles (trucks or buses). Diesel fuel, which accounts for about six percent of the on-highway ground transportation energy demand in the state, is shown in Figure VIII-2.

Figure VIII-1

On-Highway Use of Gasoline, 1980-1992, by County

Figure VIII-2

On-Highway Use of Diesel, 1980-1992, by County

3. Theoretical Market Size and Market Constraints:

Each of the four uses outlined above are subject to the following constraints:

- Baseline demand for the traditional fuel;

- Availability of vehicles able to use the replacement product;
- Availability of the replacement product at a competitive price;
- Availability of the infrastructure necessary for distribution of the replacement product; and
- Willingness of the public to use the replacement product.

For the purpose of comparison, the above-listed uses and constraints, as well as theoretical market sizes, are shown in Table VIII-1.

Table VIII-1
Ethanol as a Transportation Fuel

	A. Baseline demand for the traditional fuel	B. Vehicles able to use the replacement product	C. Infrastructure for distribution of the replacement product	Potential market size (theoretical)
1. 10% ethanol	380 million gallons per year, $x \leq 10\%$	YES	YES	30 - 40 million gallons per year
2. ETBE or TAE	380 million gallons per year	YES	YES	10 - 20 million gallons per year
3. 85% ethanol in light duty vehicles	380 million gallons per year	Vehicles commercially available.	Equipment commercially available.	480 million gallons per year
4. 100% ethanol in trucks, buses	25 million gallons per year	Vehicles commercially available.	Equipment commercially available.	50 million gallons per year

4. Practical Considerations:

The constraints to theoretical markets listed above introduce additional costs and complexity to each scenario. Costs (including shipping, infrastructure, and vehicle costs), benefits, and strategies are being addressed in the previously-referenced work in progress by the State Department of Business, Economic Development & Tourism on developing a "Transportation Energy Strategy".

Possible markets for ethanol fuel include: use as a transportation fuel, fuel additive, or as a fuel for electricity production. The potential market sizes, competition, and incentives for six possibilities are discussed briefly below. (For more detailed information on calculations and applications of tax credits and/or exemptions, see Appendix.)

a. As a blending agent (10%) with gasoline

1. Market: 382 million gallons of gasoline were sold in the state in 1992. A 10% blend with all gasoline would require about 38 million gallons per year.

2. Competition: 1) Locally-available gasolines; and
2) Ethanol from out of state

a. Locally-available gasolines

\$ 0.85	rack price (approximately)
+ 0.09	retail overhead
+ 0.184	federal tax
+ 0.325	state and county fuel tax (Honolulu rate)
+ 0.039	state 4% tax
<hr/>	
\$ 1.49	retail gasoline price per gallon

Gasohol to compete with local gasoline:

\$ 0.788	for 0.9 gallon \$0.875 (unleaded regular + 2.5¢ ²) gasoline
+ 0.163	for 0.1 gallons ethanol (this is the maximum possible, which will still result in the same "bottom line" price to the consumer)
+ 0.09	retail overhead
+ 0.130	federal fuel tax
- 0.01	federal small producer credit (for facilities of less than 30 million gallons per year; credit applies only to the first 15 million gallons)
+ 0.004	federal income tax on credits
+ 0.325	state and county (Honolulu rate) fuel tax
+ 0.00	state excise tax (gasohol is exempt)
<hr/>	
\$ 1.49	retail gasohol price per gallon

(Ethanol would have to be produced for less than \$1.63 per gallon.)

b. Ethanol from out of state:

Current prices for ethanol on the mainland range from \$1.11 in South Dakota to \$1.46 in the state of Washington.³

\$1.10-\$1.40/gal. (approximate 5-year range);
 + 0.10-\$0.20 shipping from West Coast to Hawaii
 (assumes parcel tanker shipments, includes terminal costs in Hawaii, does not include terminaling costs on the West Coast)

\$1.20-\$1.60/ethanol gal. for Hawaii ethanol to compete with ethanol from out of state.

(Ethanol would have to be produced for less than \$1.30 per gallon.)

3. Incentives:

5.4¢/fuel gal. federal excise tax (fuel tax) partial exemption
 (See federal fuel tax amounts listed above:

gasoline, \$0.184 per gallon;

gasohol, \$0.130 per gallon;

= partial exemption for gasohol, \$0.054 per gallon);

10¢/ethanol gal. small producer federal income tax credit (minus a percentage because credit is taxable)

b. As a blending agent (10%) in unleaded mid-grade and premium gasoline

1. **Market:** About forty-two percent of the gasoline sold in Hawaii in 1992 was mid-grade and premium blends. A 10% blend with all mid-grade and premium gasolines would require about 17 million gallons of ethanol per year.

2. Competition:

- 1) Locally-available mid-grade and premium gasoline; and
- 2) Ethanol from out of state

a. Locally-available mid-grade and premium gasolines

\$ 0.89 rack price (approximate)
 + 0.10 retail overhead
 + 0.184 federal tax
 + 0.325 state and county (Honolulu rate) fuel tax
 + 0.041 state 4% tax
 \$ 1.54 retail gasoline price per gallon

Maximum allowable cost of ethanol to compete with mid-grade and premium gasolines:

\$ 0.788	for 0.9 gallon \$0.875 (unleaded regular + 2.5¢) gasoline
+ 0.204	for 0.1 gallons ethanol at \$2.04 per gallon
+ 0.10	retail overhead
+ 0.130	federal fuel tax
- 0.01	federal small producer credit (for facilities of less than 30 million gallons per year; credit applies only to the first 15 million gallons)
+ 0.004	federal income tax on credits
+ 0.325	state and county (Honolulu rate) fuel tax
+ 0.00	state excise tax (gasohol is exempt)
<hr/>	
\$ 1.54	retail gasohol price per gallon
(Ethanol would have to be produced for less than \$2.04 per gallon.)	

b. Ethanol from out of state: Same as a. 2.b. above.

3. Tax incentives: Same as a.3. above.

c. For use in light-duty flexible-fueled vehicles (FFV)

Most major auto manufacturers have designed special "flexible-fuel vehicles" which are capable of operating on mixtures of 85% alcohol and 15% gasoline. A mixture of 85% ethanol and 15% gasoline is known as "E85" and is considered an alternative fuel. The federal government has identified increased use of alternative fuels as a means to meet national energy security, economic, and environmental goals in both the Clean Air Act Amendments of 1990 and the National Energy Policy Act of 1992 (EPACT). As described in a Congressional Research Service Issue Brief:

"The Energy Policy Act of 1992 sets a national goal of 30% penetration of nonpetroleum fuels in the light-duty vehicle market by 2010 and requires that, in sequence, the federal government, alternative fuels providers, state and local governments, and private fleets buy alternative fuel vehicles in percentages increasing over time. The Act also creates tax incentives for vehicle buyers and for alternative fuel service station operators."⁴

State government fleets are required to begin purchasing these vehicles in model year 1996. Ethanol is one of several alternative fuels. Other choices are methanol, liquefied petroleum gas (also commonly referred to as LPG or propane), natural gas, electricity, and biodiesel. Each of the fuels has benefits and disadvantages. It is unknown at this time what will be the demand for each of the alternative fuels (or for alternative fuels in general).

- 1. Market:** Unknown. Based on a number of alternative-fueled vehicles purchased. Fuel use per vehicle: less than 500 gallons gasoline (694 gallons E85, containing 590 gallons ethanol) per year. A one million gallon per year facility would provide more than enough fuel for 1695 cars.⁵ Theoretical maximum (if all gasoline-powered vehicles eventually used 85% ethanol) is projected to be more than 450 million gallons per year of ethanol. The current demand is zero.

- 2. Competition:**
1. Locally-available gasolines; and
 2. Ethanol from out of state

a. Locally-available gasoline

\$ 0.85	rack price (approximate)
+ 0.09	retail overhead (approximate)
+ 0.184	federal tax
+ 0.325	state and county fuel tax (Honolulu rate)
+ 0.039	<u>state 4% tax</u>
\$ 1.49	retail gasoline price per gallon

1.39 gallons E85 = 1 gallon gasoline. Since it takes more gallons of E85 to go the same distance, fuel cost per E85 gallon should be less. For fuel costs to be equivalent on a mile-for-mile basis, E85 retail price may not exceed \$1.07 per gallon.

Maximum allowable cost of E85:

\$ 0.1275	for 0.15 gallon gasoline (at 85¢/gallon gasoline)
+ 0.70	for 0.85 gallon ethanol (at 82¢/gallon ethanol)
+ 0.09	retail overhead
+ 0.184	federal fuel tax
- 0.459	federal tax credit
- 0.085	federal small producer credit
+ 0.19	federal income tax on credits
+ 0.325	<u>state and county fuel tax</u>
\$ 1.07	per gallon E85

(Ethanol would have to be produced for less than \$0.82 per gallon.)

- b. Ethanol from out of state:** Same as a. ii. b) above (less than \$1.30 per gallon).

3. Incentives:

- 54¢/gal. federal income tax credit;
 10¢/gal. small producer federal income tax credit (minus a percentage because credits are taxable);

Deductions for alternative fuel refueling facilities; and

Deductions for alternative fuel vehicles.

d. For use in buses

Ethanol-powered buses and trucks are in use in revenue service in several locations across the United States and in other countries (e.g. Brazil and France). Several federal programs have increased the use of alternative fuels in buses over the past several years. In 1988, the National Alternative Motor Fuels Act provided for transit agencies to begin to utilize alternative fuels in their fleets. In 1990, the Clean Air Act Amendments targeted particulate emissions from urban transit buses as an air pollution reduction objective. Alcohol fueled buses are one approach to reducing emissions of particulates. (Other options include advanced electronic engine controls, engine re-design, particulate traps, "clean diesel" fuels, catalytic converters, and various combinations of these systems.) The National Energy Policy Act of 1992 also contains provisions for alternatively-fueled buses.

Full-size transit buses which run on 100% ethanol⁶ are available for approximately \$40,000 more than for a regular bus (regular buses cost over \$200,000).

1. **Market:** Unknown. Based on number of vehicles purchased. Current demand is zero. A 1 million gallon-per-year ethanol plant would provide enough fuel for about 35 buses. A 5 million gallon-per-year ethanol plant would provide enough fuel for about 178 buses.
2. **Competition:**
 - 1) Locally-available diesel fuel; and
 - 2) Ethanol from out of state

a. Locally-available diesel fuel⁷

\$ 1.16	rack price (approximate)
0.00	federal tax
0.00	state and county fuel tax
<hr/>	
\$ 1.16	per gallon diesel

It takes approximately 1.8 gallons of ethanol to go as far as 1 gallon of diesel.⁸ Since it takes more gallons of ethanol to go the same distance, fuel cost per ethanol gallon should be less. For fuel costs to be equivalent on a mile-for-mile basis, the total price of the E100 fuel should not be more than \$0.69 per gallon.

Maximum allowable cost of ethanol to compete with diesel for use in transit buses:

\$ 1.11	(1 gallon ethanol at \$1.11 per gallon)
- 0.54	federal tax credit
- 0.10	federal small producer credit
+ 0.224	<u>federal income tax on credit</u>
\$ 0.69	per gallon total price of E100 fuel
(Ethanol would have to be produced for less than \$1.11 per gallon.)	

b. Ethanol from out of state: Same as a. ii. b). above.

3. Tax incentives: Same as c.3. above.

e. As a feedstock in the production of ETBE (ethyl tertiary butyl ether)

Ethyl tertiary butyl ether (ETBE) is a gasoline additive made from ethanol and isobutylene. ETBE is an octane enhancer (raises the octane rating of the fuel) and an oxygenate (makes the fuel cleaner-burning). The November/December 1993 issue of *Fuel Reformulation* pegged the value of one gallon of ETBE at 130% the value of one gallon unleaded regular gasoline.

1. **Market:** If ETBE was blended into all mid-grade and premium gasolines at the rate of 17.2 per cent, demand for ethanol to make the ETBE would be about 12.5 million gallons per year.

2. **Competition:**

- 1) Locally-available octane enhancers;
- 2) ETBE or other octane enhancers from out of state;
- 3) ETBE for export

a. Locally-available octane enhancers

Depends on refinery processes. If a competitive cost for ETBE is 130 percent of unleaded regular, ETBE cost per gallon would be \$1.10.

\$ 0.238	(0.68 gallons isobutylene ⁹ at approximately \$0.35 per gallon ¹⁰)
+ 0.113	processing cost (estimated)
+ 0.928	ethanol cost (0.42 gallons ethanol at \$2.20 per gallon)
- 0.2268	federal tax credit for ethanol used in ETBE
- 0.042	federal small producer credit
+ 0.094	<u>federal income tax on credits</u>
\$ 1.10	ETBE
(Ethanol would have to be produced for less than \$2.21 per gallon.)	

b. ETBE or other octane enhancers from out of state

Depends on refinery processes. If a competitive cost for ETBE is 130 per cent of unleaded regular, and average price of unleaded regular is about 49 cents per gallon, ETBE could be shipped in for about 85 cents per gallon. However, the current situation with impending reformulated gasoline regulations – requiring lower vapor pressures (ETBE has a low vapor pressure), use of oxygenates (ETBE is an oxygenate) and a requirement for a certain percentage of oxygenates to be “renewable” (ETBE is usually made from ethanol which is considered “renewable”) – may increase the value/price of ETBE.

c. ETBE for export

Depends on refinery processes. If unleaded regular on the mainland is about 49 cents, and a competitive cost for ETBE on the mainland is 130 per cent of unleaded regular (or about 64 cents), and shipping cost from Hawaii to the Mainland is about 10¢ per gallon, ETBE cost per gallon before shipping should be less than \$0.54.

\$ 0.238	(0.68 gallons isobutylene at approximately \$0.35 per gallon)
+ 0.113	processing cost (estimated)
+ 0.354	ethanol cost (0.42 gallons ethanol at \$0.84 per gallon)
- 0.2268	federal tax credit for ethanol used in ETBE
- 0.042	federal small producer credit
+ 0.094	<u>federal income tax on credit</u>
\$ 0.53	ETBE

(Ethanol would have to be produced for less than \$0.84 per gallon.)

f. For use in electricity generation

Electric utilities and combustion turbine manufacturers have evaluated the use of alcohols (methanol and ethanol) in combustion turbines. Combustion turbines operating on alcohols have shown higher efficiencies, longer operating life, and reduced emissions of NOx.¹¹

1. **Market:** If ethanol is used in a 25,000 kW steam injected combustion turbine, fuel consumption is projected to be about 0.119 gallons per kilowatt-hour,¹² or almost 3000 gallons per hour at that operating rate. statewide electricity consumption in 1992 was over nine and one-half billion kWh.
2. **Competition:**
 - 1) Conventional fossil fuels (fuel oil, diesel, and coal);
 - 2) Direct combustion of biomass;
 - 3) Other alternative energy sources for electricity generation.

Note that in the ethanol production process, lignin is a by-product which may also be burned to produce electricity. Although not explicitly valued

in this section, its electricity production value may be included by reducing the projected ethanol price by the value of the lignin, then comparing that result to the target ethanol prices identified here.

a. Conventional fossil fuels

If #6 fuel oil is \$18.00 per barrel, ethanol, competing with fuel oil, would have to be produced for not more than...

\$ 0.22 (equivalent value per gallon ethanol on energy content basis)

+ 0.126 if electricity is generated from a "dedicated feedstock supply system," Federal credit of 1.5¢ per kilowatt-hour generated (8.4 kWh per gallon ethanol $\times$ 1.5 ¢/kWh = 12.6¢/gallon ethanol)

+ 0.54 federal income tax credit for ethanol used as fuel

+ 0.10 federal credit for small (less than 30 million gpy) producers

- 0.268 federal income tax on credits

\$ 0.72 per gallon ethanol

(Ethanol would have to be produced for less than \$0.72 per gallon.)

If diesel is \$28.00 per barrel,

\$ 0.40 (equivalent value per gallon ethanol on energy content basis)

+ 0.126 if electricity is generated from a "dedicated feedstock supply system," federal credit of 1.5¢ per kilowatt-hour generated (8.4 kWh per gallon ethanol $\times$ 1.5 ¢/kWh = 12.6¢/gallon ethanol)

+ 0.54 federal income tax credit for ethanol used as fuel

+ 0.10 federal credit for small (less than 30 million gpy) producers

- 0.268 federal income tax on credits

\$ 0.87 per gallon ethanol

(Ethanol would have to be produced for less than \$0.87 per gallon.)

If coal is \$30.00 per ton,¹³

- \$ 0.11 (equivalent value per gallon ethanol on energy content basis, assuming coal at 21 million Btus per ton)
- + 0.126 if electricity is generated from a "dedicated feedstock supply system," Federal credit of 1.5¢ per kilowatt-hour generated (8.4 kWh per gallon ethanol x 1.5 ¢/kWh = 12.6¢/gallon ethanol)
- + 0.54 federal income tax credit for ethanol used as fuel
- + 0.10 federal credit for small (less than 30 million gpy) producers
- 0.268 federal income tax on credit
- \$ 0.61 per gallon ethanol
- (Ethanol would have to be produced for less than \$0.61 per gallon.)

b. Direct combustion of biomass

If biomass is \$50.00 per ton dry matter,

- \$ 0.232 (equivalent value per gallon ethanol on energy content basis)
- + 0.00 If electricity is generated from a "dedicated feedstock supply system," Federal credit of 1.5 ¢ per kilowatt-hour generated. However, if biomass for direct combustion is also from a "dedicated feedstock supply system," it would be eligible for the credit as well so there would be no net advantage for ethanol with respect to this credit.
- + 0.54 Federal income tax credit for ethanol used as fuel
- + 0.10 Federal credit for small (less than 30 million gpy) producers
- 0.224 Federal income tax on credits
- \$ 0.65 per gallon ethanol
- (Ethanol would have to be produced for less than \$0.65 per gallon.)

g. Summary of potential markets for fuel ethanol

As illustrated above, and summarized in Table VIII-2 below, there are several potential markets for fuel ethanol. The "target price" for ethanol varies, according to the competition and applicable tax incentives, from as low as around 60 cents per gallon to over \$1.50 per gallon.

Table VIII-2
Estimated "Competitive Price" For Fuel-Grade Ethanol
In Various Hawaii Applications

PRODUCT	VS:	% Ethanol By Volume In Primary Product	Competitive Retail Price for Primary Product (With ethanol cost added)	Estimated Retail Price for Primary Product (Without ethanol cost added)	Competitive Price for Quantity of Ethanol Used In Primary Product	Competitive Production Price Per Gallon of Ethanol
	-	%	\$ per gallon	\$ per gallon	\$ per gallon	\$ per gallon
Gasoline (all grades)	-	0 %	\$1.49	\$1.49	-	-
Gasoline (mid-grade & premium)	-	0 %	\$1.54	\$1.54	-	-
Ethanol shipped from the mainland	-	100 %	\$1.30	-	\$1.30	\$1.30
Hawaii Gasohol	Gasoline (all grades)	10 %	\$1.47	\$1.30	\$0.16	\$1.63
Hawaii mid-grade & premium with ethanol	Gasoline (mid-grade & premium)	10 %	\$1.54	\$1.34	\$0.20	\$2.04
E85	Gasoline (all grades)	85 %	\$1.07	\$0.37	\$0.69	\$0.82
Diesel for use in city buses	-	0 %	\$1.16	\$1.16	-	-
E100	Diesel for use in city buses	100 %	\$0.70	(\$0.42)	\$1.11	\$1.11
ETBE	Octane enhancers	42 %	\$1.11	\$0.18	\$0.93	\$2.21
Fuel oil (#6 distillate)	-	0 %	\$0.43	\$0.43	-	-
E100	Fuel oil (#6 distillate)	100%	\$0.22	(\$0.50)	\$0.72	\$0.72
Diesel (#2 distillate)	-	0%	\$0.67	\$0.67	-	-
E100	Diesel (#2 distillate)	100%	\$0.37	(\$0.50)	\$0.87	\$0.87
Coal	-	0%	\$30.00	\$30.00	-	-
E100	Coal	100%	\$0.11	(\$0.50)	\$0.61	\$0.61

It was stated earlier that "...there are a variety of technologies that may produce ethanol, depending on amounts paid for feedstock, at costs ranging from less than \$1.00 to over \$3.00 per gallon." Since a portion of the projected range of sales prices is consistent with a portion of the projected range of production costs, this first-cut estimate indicates that ethanol production for certain markets may be economically feasible.

Ethanol is only one possible output from the biomass conversion systems described in this report. Revenues received from the sale of other by-products could help to pay for a portion of the feedstock and operating costs. In Chapter V, the "ethanol production cost" did not take into account potential returns from sale of by-products, and assumed that the only revenue coming into the system was from the sale of ethanol. Therefore, the ethanol price had to be set high enough to cover 100% of the costs. In certain cases, production and sale of co-products could reduce the ethanol sales price required for an economically feasible system.

Although it is beyond the scope of this project to evaluate the outputs from all possible combinations of feedstocks and technologies (once again, this would vary by site as well), Section C below provides a general discussion of possible co-products, markets and values.

B. MARKETS FOR ELECTRICITY

The Hilo/Hamakua region is grid-connected with the rest of the island of Hawaii. Therefore, the market for the product may be described as being the electrical demand of the island. The competitor for that market would be the existing and planned electrical generation capacity. Electrical demand projections are contained in the October, 1993 *Integrated Resource Planning Report* by Hawaii Electric Light Company (HELCO), and, are shown in Table VIII-3.

Table VIII-3
HELCO's 20-Year Preferred Plan as of October, 1993

Year	Forecast Peak (MW)	DSM Peak (MW)	System Capability	Reserve Margin (MW)	Reserve Margin (%)
1993	157	157.0	205.60	48.6	31.0
1994	165	164.4	197.60	33.2	20.2
1995	171	170.0	217.60	47.6	28.0
1996	177	174.0	217.75	43.8	25.1
1997	184	179.0	235.75	56.8	31.7
1998	191	183.0	222.00	39.0	21.3
1999	199	188.0	222.00	34.0	18.1
2000	207	193.0	239.20	46.2	23.9
2001	215	199.0	250.90	51.9	26.1
2002	224	205.0	250.90	45.9	22.4
2003	233	211.0	250.90	39.9	18.9
2004	242	217.0	250.90	33.9	15.6
2005	251	223.0	269.80	46.8	21.0
2006	261	230.0	262.30	32.3	14.0
2007	271	239.0	285.00	46.0	19.2
2008	283	248.0	285.00	37.0	14.9
2009	295	259.0	300.00	41.0	15.8
2010	308	269.0	300.00	31.0	11.5
2011	321	281.0	318.90	37.9	13.5
2012	334	292.0	341.60	49.6	17.0
2013	348	304.0	341.60	37.6	12.4

Source: *Integration Report* by Hawaii Electric Light Company, October, 1993.

Electrical supply projections (including generating capacity, retirements, and additions) are shown in Table VIII-4. These projections are subject to change, as HELCO is participating in an Integrated Resource Planning docket in which both demand and supply projections are under discussion.

Table VIII-4
HELCO's Planned Capacity Additions and Retirements

Date	Resource Description	Add (MW)	Retire (MW)
01 Jun. 1993	Puna Geothermal Venture	25.0	
03 Aug 1994	Hamakua (Hamakua contract revised from 10 to 8 MW for final harvest.)		8.0
01 Jul 1995	Combustion Turbine (CT) -4 (Scheduled install date.)	20.0	
01 Sep 1995	CT-5 (Scheduled install date. Required date 4/1/96.)	20.0	
31 Dec 1995	Waimea D-8, 9, 10		2.7
31 Dec 1995	Kanoelehua D-11		2
31 Dec 1995	Shipman 1		3.4
31 Dec 1995	Kanoelehua CT-1		9
31 Dec 1995	Waimea D-12		2.75
01 Oct 1997	Steam Turbine (ST) -7 (CT-4 & CT-5 to Dual Train Combined Cycle #1)	18.0	
31 Dec 1997	Waimea D-13 & 14, Kanoelehua D-15, 16		11.0
31 Dec 1998	Kanoelehua D-17		2.75
1999	Keahole D-18, 19		5.5
2000	Dual Train Combustion Turbine (DTCT) - Phase1 (A)	22.7	
2000	Keahole D-20, 21, 22, 23		11.0
2001	DTCT-PH2 (A)	22.7	
2005	DTST-PH3 (A) (DTCT-PH1(A) and DTCT-PH2 (A) to DTCC #2)	18.9	
2005	Shipman 3		7.5
2007	DTCT-PH1 (B)	22.7	
2008	Shipman 4		7.7
2009	DTCT-PH2 (B)	22.7	
2011	DTST-PH3(B) (DTCT-PH1(B) and DTCT-PH2(B) to DTCC #3)	18.9	
2012	DTCT-PH1 (C)	22.7	

Source: *Integration Report* by Hawaii Electric Light Company, October, 1993.

As shown in Tables VIII-3 and VIII-4 above, the preferred size for capacity addition is between 18 and 25 MW. Capacity additions of this size are planned to occur approximately every two years (1995, 1997, 2000, 2001, 2005, 2007, 2009, 2011, and 2012).

C. MARKETS FOR CO-PRODUCTS AND BY-PRODUCTS

Each feedstock source and processing technology combination will produce slightly different outputs and co-products. For example, a feedstock with high levels of protein has potential to produce a high-protein animal feed supplement. A process with an overall lower energy demand, if combined with feedstocks high in lignin content, may produce greater quantities of electricity for sale to the utility.

Figure VIII-3 illustrates a "Crop Refinery" concept.¹⁴ This is analogous to an oil refinery which uses crude oil as a feedstock to produce a variety of refined products (gasoline, jet fuel, fuel oil, etc.). Revenues from all of the products contribute to the overall economic viability of the refinery.

Figure VIII-3
Crop Refinery

Modified from "An integrated forage crop refinery system"
TVA Agriculture Research Branch, April 1985.

If an oil refinery considered itself simply an "oil to gasoline" production plant, tried to price its gasoline to cover all of the costs of the refining process, and disposed of the other products (jet fuel, diesel, fuel oil, etc.) as waste products, the process would be extremely inefficient, the price of gasoline would be very high, and the problems of disposing of the unused portions of the crude oil would be expected to be substantial.

The technology of agricultural refineries is still in its infancy and is driven by the need to increase the value added in the highly subsidized farm sector. Such refineries could bring a new layer of infrastructure between farm and industry. Each unit could serve a local region and would concentrate a range of raw feedstocks for further processing. The aim would be to develop new methods of growing and using biomass crops and organic wastes which would reduce operating costs and maximize the value of harvested material. Whole crop harvesting methods would be investigated to reduce waste and provide increased yields for use as feedstocks for processing.

A number of processes available today separate lignocellulose into its component fractions using organic solvents or steam explosion technologies. Cellulose would be separated out, leaving lignin and sugars as by-products for process energy and fermentation feedstocks. As this technology becomes commercially viable, a gradual process of substitution will take place, ultimately yielding a supply of co-products for

use as fermentation feedstocks on a scale comparable with today's output of petrochemicals (See Figure VIII-4).

Figure VIII-4
Potential Product Development Through Commercial Substitution¹⁵

Developments in biotechnology will open new opportunities based initially on conventional sugar and starch crops. Potential products to emerge from this commercial application will include the following:

- Base Chemicals - Transportation Fuels - ETBE, MTBE, Carbon Dioxide;
- Base Products - Fertilizers, Soil Amendments, Biofeeds;
- Performance Chemicals - Intermediates;
- Direct Substitutions - Amino Acids, Organic Acids, Vitamins, Detergents, Ethanol, Isopropanol, Butanol;
- Indirect Substitutions - Bioinsecticides, Biopolymers, Water Management Chemicals, Paints, Lubricants, Dyes, Adhesives.
- Biotechnology Domain - Novel Products, Enzymes, Antibiotics

A discussion of "biomass to ethanol" may be, in its own way, as narrowly focused as the "oil to gasoline" production plant described above. Although actually designing the crop refinery outlined above is beyond the scope of this project, a general discussion of each of the possible by-products or co-products of such a system is provided below.

1. Protein

Some sources of lignocellulosic biomass (e.g. sorghum) can contain as much as 15% protein based on dry weight. This protein may be used in a marketable animal feed supplement. In a 1983 paper, Dale and others^{16, 17} have pointed out that "protein is a valuable component of biomass that is currently neglected in current fuels and chemicals from biomass schemes." In this paper, Dale provided some representative data on crop composition, a summary of which is presented in Table VIII-5 below.

The material described is independent of the grain in the crop. For example, in this analysis, sorghum residue contains approximately 10% protein based on dry weight. A well-balanced plant protein is worth approximately \$0.75 per pound. In this case, a ton of dry sorghum residue might contain 200 pounds of protein, for a total value of \$150.00. If the extraction costs are reasonable, plant residues may be processed to provide protein for an animal feed industry. Protein is also contained in stillage from the fermentation process (see section on stillage).

Table VIII-5

Protein Content of Selected Plant Materials

Material	Cellulose (% by weight, dry basis)	Hemicellulose (% by weight, dry basis)	Lignin (% by weight, dry basis)	Protein (% by weight, dry basis)	Other (% by weight, dry basis)
Alfalfa (leaves)	22.2%	11.0%	5.2%	28.5%	33.1%
Alfalfa (stalks)	48.5%	6.5%	16.6%	10.5%	17.9%
Sorghum residue (leaves)	25.6%	40.0%	7.8%	10.4%	16.2%
Sorghum residue (stalks)	26.1%	31.1%	8.0%	9.3%	25.5%
Corn residue (leaves)	33.2%	31.1%	7.4%	7.1%	21.2%
Corn residue (stalks)	43.1%	10.5%	9.6%	3.4%	33.4%
Sudan grass (leaves)	35.8%	29.5%	10.9%	6.7%	17.1%
Sudan grass (stalks)	44.1%	21.3%	9.1%	5.1%	20.4%

2. Lignin

Lignin is a component of lignocellulosic biomass which generally passes through the biomass to ethanol conversion system unchanged. For a plant producing 25 million gallons per year of ethanol (using assumptions stated in Chapter V), lignin production would be about 100 tons per day. Lignin has an energy value that varies by source, from about 9,100 Btu's per pound of lignin from northern red oak to

11,300 Btu's per pound of lignin from softwood.¹⁸ Another reference quotes a heat content of 12,700 Btu's per pound of "milled wood lignin."¹⁹

Extraction of lignin in the processing of biomass to ethanol has the potential to provide a high energy compound for the production of process heat and generation of electrical energy. Lignin may also be processed to specialty polymers, electrically conducting polymers, or phenolic resins, which may be used as glues or binders in production of plywood and fiberboard.

3. Furfural

Hydrolysis of biomass can result in solubilizing or liberating the sugars that constitute cellulose and hemicellulose. Xylose, the primary sugar in hemicellulose, can be further processed in the presence of acid to furfural (See Figure VIII-4).

Figure VIII-5
Xylose to Furfural

This compound can be used as a selective solvent for refining high quality lubricating oils. Hydrogenation of furfural at 200°C produces furfural alcohol which can be refluxed to produce commercial resins. Furfural can also be used to produce low temperature adhesives and protective coating for wood. It also has application in the production of nylon.

4. Carbon dioxide

For every pound of ethanol produced, approximately one pound of carbon dioxide is produced from the fermentation process. For a 25 million gallon per year plant, carbon dioxide production would be about 250 tons per day.

a. Direct sale

Carbonation. Carbon dioxide has only limited market as a beverage carbonating agent in Hawaii.

Compression to make dry ice. Dry ice is used as a cooling agent in some industries.

b. Conversion to other products

Carbon dioxide may also be directed to the production of algae or methane.

5. Algae

In photosynthesis, plants and other chlorophyll containing organisms – including algae – use energy provided by sunlight to covert carbon dioxide to sugars. This is done by the reduction of CO₂ (removing oxygen and adding hydrogen).

As a result of photosynthesis, carbon dioxide (considered a pollutant) is converted to valuable oxygen and sugars that living forms use as a source of energy. CO₂ is utilized 100% by aquatic algae to produce biomass by photosynthesis. Appropriate selection of algae has the potential to produce pharmaceuticals, animal feed ingredients, and energy products.^{20, 21, 22, 23, 24, 25} The abundance of sunlight available in Hawaii makes this possibility particularly intriguing.

6. Microbial Biomass

Yeast and other microorganisms that affect fermentation contain valuable nutrients including: nitrogen, phosphorous, potassium, and trace minerals. Fermentation (conversion of sugars to ethanol and carbon dioxide) is carried out by a variety of microorganisms. On a dry weight basis these microorganisms may contain up to 70% protein and a variety of vitamins and fatty acids . Processing produces a protein rich powder (sometimes referred to as single cell protein). Depending on species, these can be used as substitutes for soy protein or fish meal in formulating feeds for animals and aquatic species

7. Stillage

Fermentation (conversion of sugars to ethanol and carbon dioxide) is carried out by a variety of microorganisms. These microorganisms contain nitrogen, phosphorous, potassium, trace minerals, and, on a dry weight basis, may contain up to 70% protein and a variety of vitamins and fatty acids. Processing produces a protein rich powder (sometimes referred to as single cell protein). Depending on species these can be used as substitutes for soy protein or fish meal in formulating feeds for animals and aquatic species. Stillage may be anaerobically processed to produce methane.

8. Methane

Methane may be used for the generation of electricity or as a feedstock for production of other materials. Methane is not a direct product of the biomass to ethanol production process, but could be produced via anaerobic digestion of stillage and/or conversion of carbon dioxide. Proprietary designs of systems that have the capacity to convert CO₂ to methane have been developed at the experimental level.^{26, 27, 28, 29, 30, 31, 32} As this technology continues to improve, methane from carbon dioxide may become an important source of energy for biomass conversion systems.

After microbial biomass is removed the resulting "beer" must be distilled. The liquid remaining is rich in nutrients and contains particulate material that must be disposed of or utilized. When combined with other organic wastes, this material is a particularly good substrate for anaerobic fermentation to produce methane. The resulting methane may be used for process heat or to produce electricity.

9. Electricity

a. Production

There are several possibilities for production of electricity within the plant: direct incineration of lignin, incineration of stillage (the stillage would have to be dried first), or use of methane (from anaerobic digestion of stillage and conversion of carbon dioxide) in natural gas engines or gas turbines.

b. Sale to utilities

Electricity not used in the plant may be sold to a local electric utility. The amount received in payment from the utility varies from island to island and between negotiated power purchase agreements. (A power purchase agreement is a contract between the independent power producer (IPP) and the utility.) An important factor in utility payments to IPPs is whether the contract is for firm power (available upon demand by the utility) or not. Another option would be to sell biomass-derived fuel (pellets, oils, etc.) to the utility for use in their own facilities, if a long-term contract could be worked out that was acceptable to both parties.

¹ Work in progress by the State Department of Business, Economic Development & Tourism on developing a "Transportation Energy Strategy"

² According to 1990 correspondence from Pacific Resources, Inc., it would cost an additional 2 to 2.5 cents per gallon of gasoline to reduce the vapor pressure of the base gasoline for blending with ethanol.

³ "U.S. Market Fuel Ethanol." New Fuels Report. April 18, 1994. Volume 15, Number 6.

⁴ Congressional Research Service Issue Brief Number 93009, updated 01/01/94.

⁵ These estimates are for flexible-fueled vehicles. Dedicated vehicles would have better fuel economy.

⁶ "100% ethanol" and "E100" also refer to blends of 95% ethanol with 5% denaturant.

⁷ Assumes fuel used for a federally nontaxable purpose, such as by a state or local government.

⁸ U. S. Department of Energy. *Alternative Fuels Data Center Update*. Spring 1994. Volume 3, Issue 1.

⁹ Tshiteya, R. et al. 1991. Properties of Alcohol Transportation Fuels. Alcohol Fuels Reference Work #1. Prepared by Meridian Corporation for the U. S. Department of Energy.

¹⁰ Gorden, M. et al. 1989. Feasibility of the Production of Fuels and Co-products from Biomass.

¹¹ Electric Power Research Institute. 1980. AP-1712. "Test and Evaluation of Methanol in a Gas Turbine System," and personal communication, General Electric representative M. Hirakami, 1992.

¹² Based on a General Electric LM2500 combustion turbine running at 3600 RPM with shaft output of 31,200 HP.

¹³ This differs from the coal price (\$60 per ton) assumed in Chapter III, due to the assumption that a utility which purchases coal for baseload power generation may face lower prices per ton than plantations replacing bagasse with coal.

¹⁴ Broder, J. D. and J. W. Barrier. "Producing Ethanol and Coproducts from Multiple Feedstocks." Tennessee Valley Authority, for the International Summer Meeting of the American Society of Agricultural Engineers, Rapid City, S. D., June 26-29, 1988.

- 15 Modified from "Strategy for Biomass Conversion" by Bertus van der Toorn. Selected Papers: A Series of Papers, Articles, and Speeches Prepared by Shell Staff. October 1988.
- 16 Dale, B. E. "Biomass Refining: Protein and Ethanol from Alfalfa." *I&EC Product Research & Development*, 1983, vol. 22, p. 446.
- 17 Holtzapple, M. (1988) "Conversion of Grass to Highly-Digestible Animal Feed, Protein Concentrate, and Ethanol." Report, Dept. of Chem. Engineering, Texas A&M University, June, 1988.
- 18 American Society of Mechanical Engineers. *Thermodynamic Data for Biomass Materials and Waste Components*.
- 19 Falkehag, Ingemar. 1975. Lignin in Materials. Printed in *Proceedings of the Eighth Cellulose Conference*. Applied Polymer Symposia, No. 28.
- 20 Becker, E.W. "Nutritional Properties of Microalgae: Potentials and Constraints." (1986) *Handbook of Microalgal Mass Culture*. CRC Press, Inc. Boca Raton, Florida. pp. 339-419.
- 21 Cefferri, Orio, and Tiboni, Orsola. (1985) "The Biochemistry and Industrial Potential of Spirulina." *Annual Review of Microbiology*. Vol. 39: 503-526.
- 22 Cohen, Zvi, et al. (1987). "Fatty Acid Composition of Spirulina Strains Grown Under Various Conditions." *Phytochemistry*. Vol. 26.
- 23 Materassi, R. et al. (1986) "Some Consideration on the production of Lipid Substances by Microalgae and Cyanobacteria" in *Algae Biomass*. pp 619-626. Elsevier/North Holland Biomedical Press.
- 24 Richmond, A. (1986) "Microalgae of Economic Potential." in *Handbook of Microalgae Mass Culture*. CRC Press, Inc. Boca Raton, Florida. pp. 199-243.
- 25 Vaughn, S. R., R. M. McDonald, P. E. Donnelly, N. A. Hendy, and R. A. Mills. (1984) "The Biomass Refinery as a Route to Fuel Alcohol from Green Crops." *Proceedings Communications*, Vol. III, May 21-25, 1984, Ottawa, Canada, C-34, PP. 26-32.
- 26 Hayes T. D. and H. R. Isaacson. (1987) "New Concept for the Production of High-BTU Gas from Anaerobic Digestion," in *Biotechnological Advances in Processing Municipal Wastes for Fuels and Chemicals*, Noyes Data Corporation 355:374.
- 27 Jee, H., Yano, T., Nishio, N. and Nagai, S. (1987) "Biomethanation of H₂ and CO₂ by Methanobacterium thermoautotrophicum in membrane and ceramic bioreactors." *Journal of Fermentation Technology*. No. 4. Vol. 65: 413-18.
- 28 Ng, T. K., Bassat, A., and Zeikus, J. G. (1981) "Ethanol production by thermophilic bacteria: fermentation of cellulosic substrates by cocultures of Clostridium thermocellum and Clostridium thermohydrosulfuricum." *Applied and Environmental Microbiology*. No. 6, Vol. 41:1337-43.
- 29 Ng, T. K., Weimer, P. J., and Zeikus, J. G. (1977) "Cellulolytic and physiological properties of Clostridium thermocellum." *Arch. of Microbiology*. Vol. 114: 1-7.
- 30 Ng, T. K., Zeikus, J. G. (1982). "Differential metabolism of cellobiose and glucose by Clostridium thermocellum and Clostridium thermohydrosulfuricum." *Journal of Bacteriology*. No. 3. Vol. 150:1391-9.
- 31 Wiegel, J., Ljungdahl, L. G., and Rawson, J. R. (1979). "Isolation from soil and properties of the extreme thermophile Clostridium thermohydrosulfuricum." *Journal of Bacteriology*. No. 3, Vol. 139:800-10.
- 32 Zeikus, J.G. (1980). Chemical and Fuel Production by Anaerobic Bacteria. *Annual Review of Microbiology*. Vol. 34: 423-64.

IX. CONCLUSIONS AND RECOMMENDATIONS

A. PERSPECTIVE

The primary focus of this evaluation was to determine if there is potential to use lands coming out of sugar production in the Hilo/Hamakua region to cultivate biomass to produce transportation fuel and/or electricity that would offset imports and generate employment opportunities. Based on a promising outcome, the intent of the project was to use this information to develop specific encouraging opportunities. Complications regarding land tenure and other issues have compromised the potential for any immediate actions to develop programs at the Hamakua sugar site. However, the conclusions of this effort do have general application to future activities in the Hilo/Hamakua region and throughout the state of Hawaii.

1. General Conclusions

There are a number of specific opportunities to develop biomass to energy businesses in Hawaii. These will be dependent on location, feedstock, technology, and product forms. **There are specific actions that need to be taken now, either from a perspective of technology development or financial arrangements, that could increase the possibility of these opportunities coming to fruition.** Conclusions emerging from this evaluation are as follows:

- a. On a stand alone basis cultivation of crops as dedicated feedstocks for energy production in Hawaii is marginal at this time.
- b. In order to be economically competitive for energy production in Hawaii biomass must be delivered at less than \$50 per dry ton.
- d. Multiple out put products are essential to the economic viability of any dedicated process.
- c. Initially subsidies will be needed to establish infrastructure and sustain the energy industry.
- e. The use of dedicated feedstocks holds promise when integrated with appropriate waste streams.
- f. Further development of ethanol technology should be directed to constructing engineering development units for one or more technologies appropriate for promising feedstocks.
- g. The Hamakua Sugar facilities are not practical as a biomass energy system, however many of the components have potential to be used in new systems.
- h. The Hilo Coast processing Company should be considered for upgrading to augment the power supply on the island of Hawaii.

- i. Coupling ethanol and electric production using advancing technologies such as saccharification of lignocellulosic material for ethanol and biomass gasification for electricity looks promising. However, this will require further evaluation and demonstration.

B. BIOMASS

There are a number of promising technologies for converting biomass to ethanol or electricity. Supplying cultivated biomass at a cost that is appropriate to producing marketable products at a competitive price appears to be the major constraint to establishing profitable energy businesses in Hawaii. Technologies to process lignocellulosic material are close to commercial development. The entire composition of each crop must be considered in an evaluation of its potential to be used for ethanol production.

This report reviewed seven technologies that were considered to have the potential to process crops and waste biomass to ethanol. The analysis was primarily based on information provided by the developers of the technology. The analyses resulted in similar cost projections. This similarity lends a degree of confidence that, as the technologies mature, ethanol production costs in Hawaii will fall within this range. Varieties of sugarcane and sweet sorghum were the crops with the greatest potential for ethanol production. Processing all available sugars from sugar or sorghum has the potential to produce about 3,000 gallons per harvested acre.

1. Gasoline Competition

In order to be competitive on a stand alone basis, ethanol derived from biomass must compete with the rack price of gasoline, about 90 cents per gallon. To achieve this level of economic performance, crops must be supplied at a cost of less than \$50 per dry ton. Projections developed by HSPA and the sugar industry, indicated that the cost of delivering a dry ton of prepared cane for processing to ethanol and related products would be \$31.35 per wet ton or \$108 per dry ton for plantations operating on the island of Hawaii. At this cost, the price of producing ethanol from prepared cane would be approximately \$2.70 per gallon. (Ethanol qualifies for a federal blender credit of 54 cents per gallon an additional small producer credit of 10 cents per gallon. A state 4% excise tax exemption is applicable to liquid fuels containing at least 10% biomass-based ethanol.) If existing federal and state tax credits of \$1.03 were applied, the cost could be reduced to about \$1.70. Use of lignin resulting from biomass processing to produce electricity and conversion of by-products to animal feeds, fertilizers, and other potential products, would be necessary to reduce the production cost to the equivalent of the rack price of gasoline.

In the short term, the perspective for cultivating crops as the sole source of biomass, to be processed to transportation fuel and/or electricity, is not particularly promising. However, there are numerous improvements that can be achieved

through utilization of existing facilities, using waste products, and systems integration, that may establish an economically realistic basis for a biomass to energy industry in Hawaii in the future. Some of the more promising areas of opportunity include are discussed next.

2. Reducing Capital Costs

By retrofitting the sugar mills, capital expenditures may be kept to a minimum. Much of the equipment and infrastructure installed at the sugar mills has the potential to be used in the manufacture of ethanol and production of electricity. Use of these facilities can substantially reduce the capital costs as well as the time and expense of obtaining permits required to establish new operations.

3. Reducing Crop Production Costs and Improving Yields

Establishment of grower cooperatives to supply biomass to production plants reduces the substantial amount of administrative cost and overhead burden that is associated with the larger integrated plantation and sugar milling operations. Increasing biomass yields and harvestable sugar content by applying alternative production and harvesting technologies can be accomplished in the near term.

4. Using Wastewater for Irrigation

Wastewater contains significant amounts of nutrients for plant growth and provides a continuous supply of water that normally created a disposal problem. Using wastewater on cane may result in some decline in sugar production. However, the overall benefits in biomass production and other cost savings may more than offset the potential losses.

5. Using Waste as a Primary Source or to Augment Biomass Supplies

Using the green wastes as potential or lignocellulosic components of municipal solid waste that are abundant in Hawaii as feedstock. Almost 65% of the material in MSW has potential to be used as feedstock for ethanol production. Processing of the organic components in our current waste stream has the potential to produce between 10% and 20% of the annual transportation fuel requirements in the state. Diversion of these materials from the landfills could reduce the waste disposal problem, and could conceivably, result in the ethanol facility receiving tipping fees to accept these wastes.

6. Process Cost Reduction

The application of solar heating, drying, and distillation technology has the potential to reduce energy consumption.

Optimizing the production of ethanol with electricity generation and other coproducts, has the potential to improve cost performance.

Carbon dioxide, produced during fermentation, has the potential to be used to produce valuable algae species, by-products, or methane.

Development of fertilizer and animal feed ingredients using the microbial biomass produced in the fermentation process, has the potential to optimize overall economic performance of an integrated system.

C. ELECTRICITY

At current oil prices and current crop production costs, the opportunity to cultivate biomass as a dedicated feedstock for electricity production alone is not economically feasible. The most promising option appears to be a combination of biomass sources and processing technologies to reduce feedstock cost and produce the most valuable products.

As sources of biomass for electricity production, bagasse, tree, and/or grass crops that have moisture contents of less than 50%, offer the greatest potential to provide fuel for steam boilers or for gasification. Use of high BTU containing waste materials, offers the greatest potential to reduce the feedstock costs.

1. Future

Biomass to energy technology appropriate to Hawaii is still colored with a high degree of uncertainty. Indirectly, this report identified that there is a need for an "engineering scale" pre-commercial demonstration facility. Proceeding with a pre-commercial demonstration plant is essential to the demonstration of the economic feasibility of developing an industry in Hawaii. A concentrated effort by public, private, and government sources to move biomass technologies to a commercial reality in the state of Hawaii is required. This phase of development would provide necessary capital and operational costs required to ensure successful large scale commercial development.

D. IMPLEMENTATION

1. The Next Step

PICHTTR has been awarded two contracts by the National Renewable Energy Laboratory (NREL) to identify the necessary steps and time required for project implementation. Included among these steps are: estimates of the extent and timing of all environmental approvals. Preliminary site specific business plans for pre-commercial demonstration facilities at C. Brewer's Ka'u plantation on the Big Island and AMFAC's Pioneer Mill on Maui will be used to determine the feasibility of commercial operations at these sites. If warranted, "pre-commercial demonstration facilities" will be built at these sites. The intent of this effort is to establish the "hard" capital and operating costs necessary to attract the business entities which are capable of ensuring successful full scale commercial development.

2. What Can The Government Do?

In the meantime, government can initiate actions to guarantee markets through legislation. This will keep existing assets intact to support this level of development by establishing:

- ◆ Tax Incentives,
- ◆ Mandates for blended fuels, and
- ◆ Financial assistance programs to leverage investment capital from interested private sector developers.

At the final meeting of the technical and advisory teams, a number of specific recommendations were made regarding government actions. The following general suggestion resulted in specific recommendations from the team members:

"It would be beneficial to create a list of actions that local, state, and federal elected officials could consider for implementation which would assist in the development process of this industry. They need to know which recommendations need to be implemented in order to help make this concept happen. With this information in hand, they would know what would be required of them should they choose to make a decision to try and bring about the development of this industry."

Specific recommendations made by the teams members included the following:

"The State should be providing tax credits for the generation of electricity from bagasse to support the industry. This would stop it from collapsing at this dramatic rate. By supporting this industry with temporary subsidies for electricity generated by bagasse, vast acreage's will remain in production at minimal cost to the State. When one considers the alternative, this would not represent that great of an expenditure. This would be a short term solution until we have the time to further develop the concepts presented in this report."

"We should direct our efforts to create tax incentives and credits to the existing industry rather than to blue sky scenarios that might have application someday."

"I have done a preliminary, back of the envelop, calculation based on the numbers in the report and have found that for a 40,000 acre facility, the subsidy required to swing the economics of the facility back to a break even point would only be about \$1.6 million per year. Its not big bucks, in my opinion, to save plantations like that, especially when you consider the economic burden of the alternative that the State will be faced with."

"I would like to see a study done by the State on what the loss in revenues would be from the sugar companies that are going out of business; what they're going to be paying out in unemployment, and what its going to do to the overall economics of the State."

"I would like to suggest that we also make a recommendation to address the issue of a fair avoided cost rate; that we pay the sugar producing companies who generate

power a fair avoided cost rate; that we give recognition to the environmental pluses that come from the sugar industry; and that we consider environmental credits like what they are doing in Norway for keeping things green."

"A concept that I think makes sense is if we could work with the utilities and put combustion turbines in close association with the sugar mills and thereby be able to go combined cycle with the sugar operations. Under this concept, we could at least recover the heat for our operations. We should be working together.....There is no encouragement from the State to create this relationship."

3. Concluding Remarks

The National Biomass Program and U.S. industry will create an industrial investment on the order of \$25 billion dollars in advanced power generation facilities with about \$5 billion of this going to rural communities to develop a biomass supply infrastructure. The benefits include an annual personal and corporate income that is projected to be approximately \$6.2 billion per year by 2010, with about 300,000 persons employed in this renewable industry. With the creation of a strong U.S. industry, export markets will be opened up - markets that according to the Renewables Intensive Global Energy Scenario (RIGES) could produce 2606 TWh per year globally by 2025. Primary international market opportunities for biomass power are in tropical and subtropical countries where there are abundant underutilized or unutilized biomass wastes available for fuel. Hawaii is positioned to be a leader in both the development of biomass power and the export of this technology to other regions of the world.¹

E. VISION FOR THE FUTURE - A HAWAII INTEGRATED BIOMASS ENERGY PROGRAM.

In addition to the specific recommendation there needs to be a common vision of integrated actions that can lead to an environmentally sensitive and economically positive outcome. Figure IX-1 provides a vision for such a program.

Figure X-1
A Vision For The Future - Hawaii Integrated Biomass Energy System

¹Electricity From Biomass - National Biomass Power Program Five-Year Plan (FY 1994 - FY 1998) Solar Thermal and Biomass Power Division, Office of Solar Energy Conversion, U.S. Department of Energy. April 1993.

APPENDIX

	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	AA	AB	AC	AD	AE	AF	AG	AH	AI	AJ	AK	AL	AM	AN	AO	AP	AQ	AR	AS	AT	AU	AV	AW	AX	AY	AZ	BA	BB	BC	BD	BE	BF	BG	BH	BI	BJ	BK	BL	BM	BN	BO	BP	BQ	BR	BS	BT	BU	BV	BW	BX	BY	BZ	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO	CP	CQ	CR	CS	CT	CU	CV	CW	CX	CY	CA	CB	CC	CD	CE	CF	CG	CH	CI	CJ	CK	CL	CM	CN	CO
--	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

	C.	D.	E.	F.	G.	H.	I.	J.	K.	L.	M.	N.	O.	P.	Q.	R.	S.	T.	U.	V.	W.	X9/94	new new hamak	aggrade	AA	
	YEAR	acres harvested	Prepared cane (tons)	96 DA sugar (tons)	Final molasses (tons) (wet basis)	Prepared cane (tons/acre) (wet basis)	96 DA sugar (tons/acre) (dry basis)	Final molasses (tons/acre) (wet basis)	Molasses solids (%)	Molasses solids (tons/acre)	Bagasse fiber (dry tons)	Bagasse fiber (tons/acre) (dry basis)	Sugars in bagasse (tons/acre)	Sugars in molasses (tons/acre)	Tons 96 DA sugar per (wet) ton prep cane	Prepared cane (tons/acre) (dry basis)	Prepared cane yield, tons per acre per year (dry basis)	Prepared cane yield, tons per acre per year (dry basis)	Add'l unburned cane fiber, tons per acre per year (dry basis)	Unburned cane yield, tons per acre per year (wet basis)	Unburned cane yield, tons per acre per year (dry basis)	Acres harvested	Acres in crop	% acres harvested	Crop time (yr)	
68																										
69	1981	97,570	9,864,200	1,047,520	310,430	101	10.7	3.2	86%	2.7	1,506,180	14.9	0.4	1.7	0.106	28.3	45.6	12.8	3.6	52	16	97,570	216,100.00	45%	2.2	
70	1982	89,260	9,932,300	982,910	287,190	111	11.0	3.2	86%	2.8	1,508,312	17.4	0.4	1.7	0.099	31.2	48.5	13.6	4.1	56	18	89,260	204,749.00	44%	2.3	
71	1983	92,820	10,068,900	1,044,190	303,840	108	11.2	3.3	86%	2.8	1,550,848	15.6	0.4	1.7	0.104	29.7	51.8	14.2	4.0	60	18	92,820	194,258.00	48%	2.1	
72	1984	86,540	9,641,086	1,061,814	314,187	108	11.9	3.5	86%	3.0	1,451,123	15.8	0.4	1.8	0.110	30.6	51.2	14.6	4.0	59	19	86,540	188,396.00	48%	2.1	
73	1985	83,029	9,274,527	1,012,249	271,705	112	12.2	3.3	86%	2.8	1,410,821	17.0	0.4	1.7	0.109	32.0	49.4	14.1	4.1	57	18	83,029	187,858.00	44%	2.3	
74	1986	83,584	9,781,865	1,042,452	290,422	117	12.5	3.5	85%	3.0	1,481,824	17.8	0.4	1.8	0.106	33.3	53.2	15.1	4.4	61	19	83,584	184,181.00	45%	2.2	
75	1987	79,497	9,508,157	979,209	283,165	120	12.3	3.6	84%	3.0	1,463,732	18.4	0.5	1.8	0.103	33.7	52.5	14.8	4.4	60	19	79,497	180,966.00	44%	2.3	
76	1988	78,862	8,918,462	928,195	274,155	113	11.8	3.5	84%	2.9	1,463,732	18.6	0.5	1.8	0.104	33.3	50.2	14.8	4.4	58	19	78,862	177,893.00	44%	2.3	
77	1989	74,660	8,391,244	871,814	239,990	112	11.7	3.2	83%	2.7	1,283,668	17.2	0.4	1.6	0.104	31.5	49.1	13.8	4.1	56	18	74,660	170,813.00	44%	2.3	
78	1990	71,999	7,801,537	819,832	228,043	108	11.4	3.2	83%	2.6	1,187,629	16.5	0.4	1.6	0.105	30.5	48.2	13.6	4.0	55	18	71,999	162,000.00	44%	2.3	
79	1991	69,439	7,051,654	724,100	208,580	102	10.4	3.0	84%	2.5	1,101,245	15.9	0.4	1.5	0.103	28.6	45.3	12.9	3.8	52	17	69,439	155,600.00	45%	2.2	
80	1992	61,734	6,510,501	652,304	201,754	105	10.6	3.3	84%	2.7	1,036,365	16.8	0.4	1.7	0.100	30.1	47.1	13.4	4.0	54	17	61,734	--	--	2.2	
81	HIGH	97,570	10,068,900	1,061,814	314,187	120	12.5	3.6	86%	3.0	1,550,848	18.6	0.5	1.8	0.110	33.7	59	15.1	4.4	61	19	--	--	--	48%	2.3
82	LOW	61,734	6,510,501	652,304	201,754	101	10.4	3.0	83%	2.5	1,036,365	14.9	0.4	1.5	0.099	28.3	45	12.8	3.6	52	16	--	--	--	44%	2.1
83	AVERAGE	--	--	--	--	110	11.5	3.3	86%	2.8	--	16.8	0.4	1.7	0.104	31.1	49	14.0	4.1	57	18	--	--	--	45%	2.2
84	Tons sugar / ton prepared cane	0.104461	tons molasses/ton prep cane (wet)	0.030																						
85																										
86																										

	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
	COMPOSITION	Sugarcane components (dry basis)	% Sucrose	% Cellulose	% Hemicellulose	% Lignin	% Other	CONVERSION EFFICIENCIES ASSUMED	LOW END OF RANGE	HIGH END OF RANGE	USED IN CALCULATIONS		tons from MSW in Hamakua	% of total	tons from MSW in N. Hilo	% of total
87																
88	(SUCROSE,	Crop age (months)	24	24	24	24	24	Sucrose to glucose & fructose	99%	100%	99.5%	cellulose	1873	33%	521	33%
89	CELLULOSE,	Wet (fresh weight) or dry tons	dry	dry	dry	dry	dry	Cellulose to glucose	95%	100%	97.5%	hemicellulose	541	9%	150	9%
90	HEMICELLULOSE, &	Tops	0.0%	35.8%	21.4%	16.1%	26.7%	Hemicellulose to xylose	50%	90%	70.0%	lignin	948	17%	264	17%
91	LIGNIN)	Stalks	42.6%	21.8%	15.5%	11.5%	8.6%	Glucose to ethanol	95%	100%	97.5%	sum of above	3362	59%	935	59%
92	OF SUGARCANE STALKS	Trash	0.0%	35.8%	21.4%	16.1%	26.7%	Fructose to ethanol	95%	100%	97.5%	total reported	5728		1592	
93	& LEAVES	Subble	42.6%	21.8%	15.5%	11.5%	8.6%	Xylose to ethanol	40%	90%	65.0%					source: Shleser draft report, 2/94
94		Roots						Sucrose to ethanol	94%	100%	97.0%					
95			tops & trash (leaves):	ref.	18			Cellulose to ethanol	90%	100%	95.1%					
96			stalks: bagasse + sucrose + molasses					Hemicellulose to ethanol	20%	81%	50.5%					
97																
98	Molasses \$/ton (wet basis)	MOLASSES composition		Sucrose	Reducing Substances	Potassium Carbonate ash	Other carbonate ash	Other solids	Amino acids	Water	Total weight, wet basis	Total weight, dry basis				
99	\$40	ref.	Weight, kg	352	168	44	74	187	36	139	1000	861				
100		27	% by weight, wet basis	35.2%	16.8%	4.4%	7.4%	18.7%	3.6%	13.9%	100.0%					
101		p.105	% by weight, dry basis	40.9%	19.5%	5.1%	8.6%	21.7%	4.2%			100.0%				
102			fermentable sugars =	60.4%												

	C	D	E	F	G	H	I	J	K
		Experimental Yields (dry tons/gross acre/yr)	Estimated Commercial Yields (dry tons/gross acre/yr)	Estimated Commercial Yields (dry tons/net acre/yr)	Harvest Cycle (years)	Commercial Yields (dry tons gross yield/ harvest)			
103									
104	BIOMASS CROP	dry tons/gross acre/yr	dry tons/gross acre/yr (2)	dry tons/net acre/yr (3)	years	dry tons gross yield/ harvest			
105	Sweet Sorghum (6 cult.; avg. 2 crops)	23.2	17.4	14.8	0.38	6.67			
106	Sweet Sorghum (MN 1500; 2 crops)	32.7	24.5	20.8	0.38	9.41			
107	Sorghum-Sudangrass	17.6	13.2	11.2	0.33	4.3			
108	Corn (Avg. 2 crops)	20	15	12.8	0.25	3.82			
109	Alfalfa (Avg. of 2 Experiments; 22 harvests)	11.8	8.9	7.5	0.08	0.73			
110	Napiergrass (Avg. 2 crops; 5 locations)	31.8	23.9	20.3	0.55	13.07			
111	Napiergrass (Avg. 7 crops; 1 location)	19.6	14.7	12.5	0.67	9.91			
112	Eucalyptus grandis (close spacing trial)	15.9	11.9	10.1	2	23.85			
113	Eucalyptus urophylla (close spacing trial)	18.6	14	11.9	2	27.9			
114	Acacia meesii (close spacing trial)	17.1	12.8	10.9	2	25.65			
115	Eucalyptus grandis (large plots - Mt. View)	9.1	6.8	5.8	5	34.13			
116	Eucalyptus urophylla (large plots - Honokaa)	14.2	10.7	9.1	5	53.25			
117	Leucaena leucocephala (large plots - Maui)	11	8.3	7	5	41.25			
118	Leucaena leucocephala (large plots - Molokai)	9.6	7.2	6.1	5	36			
119	Eucalyptus urophylla (large plots - Kauai)	7.8	5.9	5	5	29.25			
120	Sugarcane Maui (from HSPA Variety Tests) (4)	22.2	16.7	16.7	1.95	32.39			
121	Sugarcane Ka'u (from HSPA Variety Tests) (4)	16.7	12.5	12.5	2.33	29.17			
122	Sugarcane (5 locations; 2 harvests)	19.5	14.6	14.6					
123	Commercial Sugarcane (recovered biomass) (5)								
124	1981-1992 Average			14.0					
125	1981-1992 High			15.1					
126	1981-1992 Low			12.8					
127	Notes:								
128	(1) Information taken from HSPA experiments (1982-1993)								
129	Commercial Sugarcane Data obtained from HSPA report on annual sugar yield to the USDA,								
130	and unpublished HSPA reports. Alternative biomass yield data from reports to GACC and DBEDT.								
131	(2) Experimental Yields Discount (%)	25%							
132	(3) Gross to Net Acreage Conversion (%)	15%							
133	(4) Based on HSPA net acre (Sq. Ft.)	37,026							
134	(5) Includes sugar, fiber, soluble molasses solids								

	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W
	Biomass	Sweet Sorghum (6 cult.; avg. 2 crops)	Sweet Sorghum (MN 1500; 2 crops)	Napiergrass (Avg. 2 crops; 5 locations)	Napiergrass (Avg. 1 crop; 1 location)	Eucalyptus grandis (close spacing trial)	Eucalyptus grandis (large plots - Mt. View)	Eucalyptus uncinata (close spacing trial)	Eucalyptus uncinata (large plots - Honokaa)	Eucalyptus uncinata (large plots - Kaula)	Leucaena leucocephala (large plots - Maui)	Leucaena leucocephala (large plots - Molokai)	Sugarcane Maui (from HSPA Variety Tests) (4)	Sugarcane Kauai (from HSPA Variety Tests) (4)	Sugarcane (prepared cane)	Unburned sugarcane	Newspaper	Municipal Solid Waste	Bagasse	Molasses	Sugarcane leafy trash usually burned
137	PARAMETERS																				
138	Crop Production time (years)	0.38	0.38	0.55	0.67	2.00	5.00	2.00	5.00	5.00	5.00	5.00	1.95	2.33	2.23	2.23	1144700	300230	2.23	2.23	2.23
139	Yield (wet tons/harvested acre)	10.08	26.08	46.63	35.30	47.70	48.26	45.80	106.50	58.50	88.50	72.00	107.07	87.23	108.82	118.71	0.0	0.0	31.73	3.90	16
140	Dry Matter (%)	35%	35%	35%	28%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	62%
141	Dry Matter (tons/harvested acre)	6.87	13.07	16.33	9.91	14.33	14.49	13.74	31.95	17.55	26.55	21.60	32.36	26.17	31.91	35.00	5.72	1.90	18.82	2.80	9.90
142	Fermentable sugars (% dry weight)	34%	34%	34%	0%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	6%
143	Fermentable sugars (tons/harvested acre)	36%	36%	36%	0%	40%	40%	40%	40%	40%	40%	40%	40%	40%	40%	40%	40%	40%	40%	6%	0%
144	Cellulose (% dry weight)	35%	35%	35%	32%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	38%	36%
145	Cellulose (tons/harvested acre)	15%	15%	15%	20%	13%	13%	13%	13%	13%	13%	13%	13%	13%	13%	13%	13%	13%	13%	13%	15%
146	Lignin (% dry weight)	10%	10%	10%	9%	3%	3%	3%	3%	3%	3%	3%	3%	3%	3%	3%	3%	3%	3%	3%	15%
147	Other (% dry weight)	2%	2%	2%	30%	12%	12%	12%	12%	12%	12%	12%	12%	12%	12%	12%	12%	12%	12%	12%	27%
148	Sugars (dry tons/acre)	2.26	3.23	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
149	Cellulose (dry tons/harvested acre)	2.41	3.40	4.18	3.17	9.06	12.97	10.60	20.24	11.12	17.74	15.48	11.98	10.76	8.68	10.51	3.49	0.62	6.36	0.00	3.54
150	Hemicellulose (dry tons/harvested acre)	1.10	1.55	2.61	1.98	3.10	4.44	3.63	6.82	3.80	5.78	5.04	4.53	4.06	4.95	7.07	0.92	0.18	4.54	0.00	2.12
151	Lignin (dry tons/harvested acre)	0.86	0.93	1.18	0.89	0.82	1.23	1.03	1.70	1.02	1.31	1.00	0.88	0.88	1.07	1.50	0.30	0.30	0.30	0.00	1.50
152	Glucose (dry tons/harvested acre)	3.61	5.37	4.53	3.44	9.83	14.05	11.49	21.82	12.04	18.22	16.77	17.17	15.68	19.48	28.48	3.78	0.67	7.14	0.88	3.84
153	Fructose (dry tons/harvested acre)	0.60	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
154	Xylose (dry tons/harvested acre)	0.67	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
155	Sugars, dry tons per acre per harvest	5.88	8.29	6.61	5.01	12.26	17.58	14.37	27.43	15.07	23.81	20.78	24.97	23.32	25.71	31.23	4.51	0.82	10.97	1.77	5.52
156	Biomass Yield (dry tons / gross acre / year)	17.8	24.8	23.8	14.8	11.9	6.8	14.0	10.7	6.9	8.3	7.2	16.6	12.8	14.3	17.8	8.7	1.9	7.8	1.3	4.4
157	Biomass Yield (dry tons / net acre / year)	14.8	20.8	20.3	12.5	10.1	5.8	11.9	9.1	5.0	7.0	6.1	16.7	12.6	12.2	14.9			6.4	1.1	3.8
158	Sugars - annual potential (tons/gross acre/year)	15.47	21.82	12.02	7.48	6.14	3.52	7.19	5.49	3.01	4.78	4.16	12.80	10.01	11.55	14.03			4.83	0.80	2.48
159	Tons sugar/dry ton biomass	0.88	0.88	0.51	0.51	0.52	0.52	0.52	0.52	0.52	0.58	0.58	0.77	0.80	0.81	0.80	0.78	0.43	0.85	0.63	0.56
160	Ethanol (ton)	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
161	Ethanol (pounds/gal)	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58
162	Ethanol Potential (gallons / gross acre / harvest) (considering conversion efficiencies)	893	1,175	877	665	1,098	2,431	1,987	3,782	2,083	3,301	2,881	3,538	3,311	3,642	4,377	632	114	1,449	266	735
163	Ethanol (acre/year)	2,181	3,091	1,994	992	849	488	993	758	417	660	576	1,814	1,421	1,638	1,967			651	119	330
164	Ethanol (Gallons/ton processed)	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66	43.66
165	Ethanol potential, gallons per dry ton processed (considering conversion efficiencies)	124.82	124.82	87.08	87.08	71.21	71.21	71.21	71.21	71.21	80.00	80.00	109.22	113.60	114.19	112.22	110.49	59.81	88.18	84.93	74.28
166	Ethanol potential, tons ethanol / dry ton biomass	0.44	0.44	0.25	0.25	0.26	0.26	0.26	0.26	0.26	0.29	0.29	0.38	0.40	0.40	0.40	0.38	0.21	0.33	0.32	0.28
167	LOW																				
168	Heat value (BTU/ton)	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07	3,00E+07
169	Heat value (BTU/lb)	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000	15,000
170	BTU/kWh	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000	13,000
171	kWh/dry ton biomass	227.47	227.47	207.69	207.69	163.85	163.85	163.85	163.85	163.85	176.92	176.92	248.15	248.15	245.08	311.15	484.92	361.93	461.54	461.54	371.54
172	Carbon Dioxide from Biomass																				
173	CO2 dry dry ton biomass	0.44	0.44	0.25	0.25	0.26	0.26	0.26	0.26	0.26	0.29	0.29	0.39	0.40	0.40	0.40	0.38	0.21	0.33	0.32	0.28
174	Theoretical ethanol maximum w/100% conversion at all steps (tons per dry ton biomass)	0.43	0.43	0.26	0.26	0.26	0.26	0.26	0.26	0.26	0.29	0.29	0.38	0.39	0.40	0.40	0.39	0.21	0.34	0.30	0.28

	C	D	E	F	G	H	I
136							
137	BIOMASS	=C105	=C106	=C110	=C111	=C112	=C115
138	PARAMETERS						
139	Crop Production time (years)	=G105	=G106	=G110	=G111	=G112	=G115
140	Yield (wet tons/harvested acre)	=D142/D141	=E142/E141	=F142/F141	=G142/G141	=H142/H141	=I142/I141
141	Dry Matter (%)	0.35	0.35	0.28	0.28	0.5	0.5
142	Yield (dry tons/harvested acre)	=H105	=H106	=H110	=H111	=H112	=H115
143	Fermentable sugars (% dry weight)	=0.12/D141	=0.12/E141	0	0	0	0
144	Cellulose (% dry weight)	=0.55*(1-D143)	=0.55*(1-E143)	0.32	0.32	0.38	0.38
145	Hemicellulose (% dry weight)	=0.25*(1-D143)	=0.25*(1-E143)	0.2	0.2	0.13	0.13
146	Lignin (% dry weight)	=0.15*(1-D143)	=0.15*(1-E143)	0.09	0.09	0.37	0.37
147	Other (% dry weight)	=1-(SUM(D143:D146))	=1-(SUM(E143:E146))	=1-(SUM(F143:F146))	=1-(SUM(G143:G146))	=1-(SUM(H143:H146))	=1-(SUM(I143:I146))
148	Sucrose (dry tons/acre)	=D142*D143	=E142*E143	=F142*F143	=G142*G143	=H142*H143	=I142*I143
149	Cellulose (dry tons/harvested acre)	=D142*D144	=E142*E144	=F142*F144	=G142*G144	=H142*H144	=I142*I144
150	Hemicellulose (dry tons/harvested acre)	=D142*D145	=E142*E145	=F142*F145	=G142*G145	=H142*H145	=I142*I145
151	Lignin (dry tons/harvested acre)	=D142*D146	=E142*E146	=F142*F146	=G142*G146	=H142*H146	=I142*I146
152	Glucose (dry tons/harvested acre)	=D148*\$L\$88*\$T\$99)+(D149*\$L\$89*\$S\$99)	=E148*\$L\$88*\$T\$99)+(E149*\$L\$89*\$S\$99)	=F148*\$L\$88*\$T\$99)+(F149*\$L\$89*\$S\$99)	=G148*\$L\$88*\$T\$99)+(G149*\$L\$89*\$S\$99)	=H148*\$L\$88*\$T\$99)+(H149*\$L\$89*\$S\$99)	=I148*\$L\$88*\$T\$99)+(I149*\$L\$89*\$S\$99)
153	Fructose (dry tons/harvested acre)	=D146*\$L\$88*\$U\$99	=E146*\$L\$88*\$U\$99	=F146*\$L\$88*\$U\$99	=G146*\$L\$88*\$U\$99	=H146*\$L\$88*\$U\$99	=I146*\$L\$88*\$U\$99
154	Xylose (dry tons/harvested acre)	=D150*\$L\$90*\$X\$99	=E150*\$L\$90*\$X\$99	=F150*\$L\$90*\$X\$99	=G150*\$L\$90*\$X\$99	=H150*\$L\$90*\$X\$99	=I150*\$L\$90*\$X\$99
155	Sugars, dry tons per acre per harvest	=SUM(D152:D154)	=SUM(E152:E154)	=SUM(F152:F154)	=SUM(G152:G154)	=SUM(H152:H154)	=SUM(I152:I154)
156	Biomass Yield (dry tons / gross acre / year)	=D142/D139	=E142/E139	=F142/F139	=G142/G139	=H142/H139	=I142/I139
157	Biomass Yield (dry tons / net acre / year)	=F106	=F106	=F110	=F111	=F112	=F115
158	Sugars - annual potential (tons/gross acre/year)	=D155/D139	=E155/E139	=F155/F139	=G155/G139	=H155/H139	=I155/I139
159	Tons sugars/dry ton biomass	=D155/D142	=E155/E142	=F155/F142	=G155/G142	=H155/H142	=I155/I142
160	Ethanol tons / ton sugar (5 ton per ton)	0.5	0.5	0.5	0.5	0.5	0.5
161	Ethanol (pounds/gal)	6.58	6.58	6.58	6.58	6.58	6.58
162	Ethanol Potential (gallons / gross acre / harvest)	=((D152*\$L\$91)+(D153*\$K\$92)+(D154*\$L\$93))*D	=((E152*\$L\$91)+(E153*\$K\$92)+(E154*\$L\$93))*E	=((F152*\$L\$91)+(F153*\$K\$92)+(F154*\$L\$93))*F	=((G152*\$L\$91)+(G153*\$K\$92)+(G154*\$L\$93))*G	=((H152*\$L\$91)+(H153*\$K\$92)+(H154*\$L\$93))*H	=((I152*\$L\$91)+(I153*\$K\$92)+(I154*\$L\$93))*I
163	Ethanol Potential (gallons/gross acre/year)	=D162/D139	=E162/E139	=F162/F139	=G162/G139	=H162/H139	=I162/I139
164	Ethanol Gal/wet ton processed	=D162/D140	=E162/E140	=F162/F140	=G162/G140	=H162/H140	=I162/I140
165	Ethanol potential, gallons per dry ton process	=D162/D142	=E162/E142	=F162/F142	=G162/G142	=H162/H142	=I162/I142
166	Ethanol potential, tons ethanol / dry ton biomass	=D155/D142)*0.5	=E155/E142)*0.5	=F155/F142)*0.5	=G155/G142)*0.5	=H155/H142)*0.5	=I155/I142)*0.5
167	LIGNIN						
168	Heat value(BTU/Ton)	30000000	30000000	30000000	30000000	30000000	30000000
169	Heat value(BTU/lb)	=D168/2000	=E168/2000	=F168/2000	=G168/2000	=H168/2000	=I168/2000
170	BTU/kWh	13000	13000	13000	13000	13000	13000
171	KWh/dry ton biomass	=D168/D170	=E168/E170	=F168/F170	=G168/G170	=H168/H170	=I168/I170
172	Carbon Dioxide from Biomass						
173	CO2 Vdry Vharv ton biomass	=D166	=E166	=F166	=G166	=H166	=I166
174	Theoretical ethanol maximum w/100% conversio	=((D148+D149+D150)/2)/D142	=((E148+E149+E150)/2)/E142	=((F148+F149+F150)/2)/F142	=((G148+G149+G150)/2)/G142	=((H148+H149+H150)/2)/H142	=((I148+I149+I150)/2)/I142

	J	K	L	M	N	O	P	Q
138					BIOMASS MATERIAL			
137	=C113	=C116	=C119	=C117	=C118	=C120	=C121	Sugarcane ("prepared cane")
138								A
139	=G113	=G116	=G119	=G117	=G118	=G120	=G121	=AA53
140	=J142/J141	=K142/K141	=L142/L141	=M142/M141	=N142/N141	=O142/O141	=P142/P141	=H83
141	0.5	0.5	0.5	0.5	0.5	0.3	0.3	=U31
142	=H113	=H116	=H119	=H117	=H118	=H120	=H121	=Q140/Q141
143	0	0	0	0	0	=O148/O142	=P148/P142	=Q148/Q142
144	0.38	0.38	0.38	0.43	0.43	0.37	0.37	= (1-Q143)*U144
145	0.13	0.13	0.13	0.14	0.14	0.14	0.14	= (1-Q143)*U145
146	0.37	0.37	0.37	0.25	0.25	0.15	0.15	= (1-Q143)*U146
147	=1-(SUM(J143:J146))	=1-(SUM(K143:K146))	=1-(SUM(L143:L146))	=1-(SUM(M143:M146))	=1-(SUM(N143:N146))	=1-(SUM(O143:O146))	=1-(SUM(P143:P146))	=1-SUM(Q143:Q146)
148	=J142*J143	=K142*K143	=L142*L143	=M142*M143	=N142*N143	8	8	=I83*O83*P83
149	=J142*J144	=K142*K144	=L142*L144	=M142*M144	=N142*N144	=O142*O144	=P142*P144	=Q142*Q144
150	=J142*J145	=K142*K145	=L142*L145	=M142*M145	=N142*N145	=O142*O145	=P142*P145	=Q142*Q145
151	=J142*J146	=K142*K146	=L142*L146	=M142*M146	=N142*N146	=O142*O146	=P142*P146	=Q142*Q146
152	= (J148*SL88*\$T\$99)+	= (K148*SL88*\$T\$99)+	= (L148*SL88*\$T\$99)+	= (M148*SL88*\$T\$99)+	= (N148*SL88*\$T\$99)+	= (O148*SL88*\$T\$99)+	= (P148*SL88*\$T\$99)+	= (Q148*SL88*\$T\$99)+
153	=J148*SL88*\$U\$99	=K148*SL88*\$U\$99	=L148*SL88*\$U\$99	=M148*SL88*\$U\$99	=N148*SL88*\$U\$99	=O148*SL88*\$U\$99	=P148*SL88*\$U\$99	=Q148*SL88*\$U\$99
154	=J150*SL90*\$X\$99	=K150*SL90*\$X\$99	=L150*SL90*\$X\$99	=M150*SL90*\$X\$99	=N150*SL90*\$X\$99	=O150*SL90*\$X\$99	=P150*SL90*\$X\$99	=Q150*SL90*\$X\$99
155	=SUM(J152:J154)	=SUM(K152:K154)	=SUM(L152:L154)	=SUM(M152:M154)	=SUM(N152:N154)	=SUM(O152:O154)	=SUM(P152:P154)	=SUM(Q152:Q154)
156	=J142/J139	=K142/K139	=L142/L139	=M142/M139	=N142/N139	=O142/O139	=P142/P139	=Q142/Q139
157	=F113	=F116	=F119	=F117	=F118	=F120	=F121	=Q186*0.86
158	=J155/J139	=K155/K139	=L155/L139	=M155/M139	=N155/N139	=O155/O139	=P155/P139	=Q155/Q139
159	=J155/J142	=K155/K142	=L155/L142	=M155/M142	=N155/N142	=O155/O142	=P155/P142	=Q155/Q142
160	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
161	6.58	6.58	6.58	6.58	6.58	6.58	6.58	6.58
162	=((J152*\$L91)+(J153*\$K92)+(J154*\$L93))	=((K152*\$L91)+(K153*\$K92)+(K154*\$L93))	=((L152*\$L91)+(L153*\$K92)+(L154*\$L93))	=((M152*\$L91)+(M153*\$K92)+(M154*\$L93))	=((N152*\$L91)+(N153*\$K92)+(N154*\$L93))	=((O152*\$L91)+(O153*\$K92)+(O154*\$L93))	=((P152*\$L91)+(P153*\$K92)+(P154*\$L93))	=((Q152*\$L91)+(Q153*\$K92)+(Q154*\$L93))
163	=J162/J139	=K162/K139	=L162/L139	=M162/M139	=N162/N139	=O162/O139	=P162/P139	=Q162/Q139
164	=J162/J140	=K162/K140	=L162/L140	=M162/M140	=N162/N140	=O162/O140	=P162/P140	=Q162/Q140
165	=J162/J142	=K162/K142	=L162/L142	=M162/M142	=N162/N142	=O162/O142	=P162/P142	=Q162/Q142
166	= (J155/J142)*0.5	= (K155/K142)*0.5	= (L155/L142)*0.5	= (M155/M142)*0.5	= (N155/N142)*0.5	= (O155/O142)*0.5	= (P155/P142)*0.5	= (Q155/Q142)*0.5
167								
168	30000000	30000000	30000000	30000000	30000000	30000000	30000000	30000000
169	=J168/2000	=K168/2000	=L168/2000	=M168/2000	=N168/2000	=O168/2000	=P168/2000	=Q168/2000
170	13000	13000	13000	13000	13000	13000	13000	13000
171	= (2000*J146*J169)/J1	= (2000*K146*K169)/K1	= (2000*L146*L169)/L170	= (2000*M146*M169)/M170	= (2000*N146*N169)/N170	= (2000*O146*O169)/O170	= (2000*P146*P169)/P170	= (2000*Q146*Q169)/Q170
172								
173	=J166	=K166	=L166	=M166	=N166	=O166	=P166	=Q166
174	=((J148+J149+J150)/2)	=((K148+K149+K150)/2)	=((L148+L149+L150)/2)	=((M148+M149+M150)/2)/M142	=((N148+N149+N150)/2)/N142	=((O148+O149+O150)/2)	=((P148+P149+P150)/2)/P142	=((Q148+Q149+Q150)/2)/Q142

	R	S	T	U	V	W
136						
137	Unburned sugarcane	Newspaper	Municipal Solid Waste	Bagasse	Molasses	Sugarcane: leafy trash usually burned
138		1144700	390929			B
139	=Q139	n/a	n/a	=Q139	=Q139	=Q139
140	=R142/R141	n/a	n/a	=U142/U141	=J83	=W142/W141
141	=X31	n/a	n/a	=N83	=K83	=W32
142	39	=S138/200000	=T138/200000	=N83	=V140/V141	=Q142-Q148)*0.54
143	=Q148/R142	0	0	=0.025	=F102	=D90
144	=R149/R142	0.61	=O88	0.38	0	=E90
145	=R150/R142	0.16	=O89	0.27	0	=F90
146	=R151/R142	0.21	=O90	0.2	0	=G90
147	=1-(SUM(R143:R146))	=1-(SUM(S143:S146))	=1-(SUM(T143:T146))	=1-(SUM(U143:U146))	=1-SUM(V143:V146)	=1-SUM(W143:W146)
148	=Q148-W148	=S143-S142	=T143-T142	=U142-U143	=V143-V142	=W142-W143
149	=Q149-W149	=S144-S142	=T144-T142	=U142-U144	=V142-V144	=W142-W144
150	=Q150-W150	=S145-S142	=T145-T142	=U142-U145	=V142-V145	=W142-W145
151	=Q151-W151	=S146-S142	=T146-T142	=U142-U146	=V142-V146	=W142-W146
152	=R148*SL88*ST\$99)+(R149*SL88*SS\$99)	=S148*SL88*ST\$99)+(S149*SL88*SS\$99)	=T148*SL88*ST\$99)+(T149*SL88*SS\$99)	=U148*SL88*ST\$99)+(U149*SL88*SS\$99)	=V148*SL88*ST\$99)+(V149*SL88*SS\$99)	=W148*SL88*ST\$99)+(W149*SL88*SS\$99)
153	=R148*SL88*SU\$99	=S148*SL88*SU\$99	=T148*SL88*SU\$99	=U148*SL88*SU\$99	=V148*SL88*SU\$99	=W148*SL88*SU\$99
154	=R150*SL90*SX\$99	=S150*SL90*SX\$99	=T150*SL90*SX\$99	=U150*SL90*SX\$99	=V150*SL90*SX\$99	=W150*SL90*SX\$99
155	=SUM(R152:R154)	=SUM(S152:S154)	=SUM(T152:T154)	=SUM(U152:U154)	=SUM(V152:V154)	=SUM(W152:W154)
156	=R142/R139	=S142	=T142	=U142/U139	=V142/V139	=W142/W139
157	=R156*0.85			=U156*0.85	=V156*0.85	=W156*0.85
158	=R155/R139			=U155/U139	=V155/V139	=W155/W139
159	=R155/R142	=S155/S142	=T155/T142	=U155/U142	=V155/V142	=W155/W142
160	0.5	0.5	0.5	0.5	0.5	0.5
161	6.58	6.58	6.58	6.58	6.58	6.58
162	=((R152*SL91)+(R153*SK92)+(R154*SL93))	=((S152*SL91)+(S153*SK92)+(S154*SL93))	=((T152*SL91)+(T153*SK92)+(T154*SL93))	=((U152*SL91)+(U153*SK92)+(U154*SL93))	=((V152*SL91)+(V153*SK92)+(V154*SL93))	=((W152*SL91)+(W153*SK92)+(W154*SL93))
163	=R162/R139			=U162/U139	=V162/V139	=W162/W139
164	=R162/R142			=U162/U142	=V162/V142	=W162/W142
165	=R162/R142	=S162/S142	=T162/T142	=U162/U142	=V162/V142	=W162/W142
166	=R155/R142)*0.5	=S155/S142)*0.5	=T155/T142)*0.5	=U155/U142)*0.5	=V155/V142)*0.5	=W155/W142)*0.5
167						
168	30000000	30000000	30000000	30000000	30000000	30000000
169	=R168/2000	=S168/2000	=T168/2000	=U168/2000	=V168/2000	=W168/2000
170	13000	13000	13000	13000	13000	13000
171	=R168/R146	=S168/S146	=T168/T146	=U168/U146	=V168/V146	=W168/W146
172						
173	=R168	=S168	=T168	=U168	=V168	=W168
174	=R148+R149+R150)/2)/R142	=S148+S149+S150)/2)/S142	=T148+T149+T150)/2)/T142	=U148+U149+U150)/2)/U142	=V148+V149+V150)/2)/V142	=W148+W149+W150)/2)/W142

	C	D
175	References / notes:	
176	1	Roberts & Hilton. 1988. Sugarcane bagasse as a potential source of ethanol and methanol biofuels.
177	2	Kinoshita, Charles. 1988. "Composition and processing of burned and unburned cane in Hawaii." International Sugar Journal, Volume 90, Number 1070.
178	3	Energy Report 31: HSPA unpublished data for calendar year 1991.
179	4	Kung, L. and Stanley, R. W. Nov 82. Journal of Animal Science. "effects of Stage of Maturity on the Nutritive Value of Whole-Plant Sugarcane Preserved as Silage"
180	5	Jakeway, Lee, HSPA. 1993 correspondence with Shieser, Robert A. Also Dillewijn, C. Van, 1952, Botany of Sugarcane.
181	6	Alexander, Alex. 1982. Report to U.S. Department of Energy, Production of Sugarcane and Tropical Grasses as a Renewable Energy Source.
182	7	Alexander, Alex. (per RAS) The Energy Cane Alternative
183	8	Sloane, George. 1979. HSPA/HNEI HSPA Molasses and Alcohol Stillage Characterization Project Final Report.
184	9	Alexander, A. G. 1984. Energy Cane as a Multiple-Products Alternative. Hawaii Natural Energy Institute Symposium Paper No. 2.
185	10	Mok, William Shu-Lai and Antal, Michael Jerry. 1992. Hawaii Integrated Biofuels Research Program, Final Subcontract Report Phase III. "Uncatalyzed Solvolysis of Whole Biomass Hemicellulose by Hot Compressed Liquid Water."
186	11	Approx. 50% dry weight / B. Memiam & data Vic Phillips and Thomas Crabb
187	12	Dale, Bruce E. 1983. Biomass Refining : Protein and Ethanol from Alfalfa: I&EC Research and Development. 22, 466.
188	13	Kinoshita, Charles M. 1994. Hawaii Energy Strategy Development Project 5: Transportation Energy Strategy. Hawaii Natural Energy Institute input to Parsons, Brinckerhoff, Quade and Douglas, Inc. under subcontract.
189	14	Keany, Francis. 1994, personal communication. Report to HSPA from Staketeck on analysis of sugarcane leaves.
190	15	Whole plant, 24 mos., dry weight (Dillewijn component fractions, Kinoshita est. of 35% unburned fiber)
191	16	Osgood, Robert V. and Dudley, Nicklos S. 1993. Comparative Study of Biomass Yields for Tree and Grass Crops Grown for Conversion to Energy.
192	17	Sugar content of prepared cane = sugar sold, plus sugar in molasses, plus sugar in bagasse.
193	18	Hawaiian Sugar Planters' Association. 1978. "Approximate Composition of Sugarcane and Leaf Trash on Dry Weight."
194	19	Lowest reported plantation average sugarcane yield, 1991.
195	20	Highest reported plantation average sugarcane yield, 1991.
196	21	Adjusted by variance factor derived from reported commercial yields of sugarcane, 1991.
197	22	Unknown - Shieser ethanol report reference # 81 (ref list goes to 80).
198	23	Personal communication, Dr. Robert Osgood, Hawaiian Sugar Planters Association, 1994.
199	24	Hubbard, H. M. and Kinoshita, C. K. 1993. Investigation of Biomass-for-Energy Production on Molokai
200	25	Farone, Dr. William. 1994. Correspondence with Dr. Robert Shieser dated March 26, 1994.
201	26	C. Brewer and Company, Ltd. 1981. Feasibility Study for Hilo Coast Processing Company. 11.4 Million Gallon Per Year Motor Fuel Grade Ethanol Plant.
202	27	Hawaii Natural Energy Institute. 1980. Hawaii Ethanol From Molasses Project. Phase I - Final Report.
203	28	State of Hawaii, Department of Business, Economic Development & Tourism, DATA BOOK 1992, table 556.
204	29	Estimated commercial yields of Napier Grass (dry tons/acre/year) = unburned sugarcane dry matter yields * 115%
205	30	Kinoshita, Charles M. 1990. Cogeneration in the Cane Sugar Industry.
206	31	Cheremisinoff et al. 1976. Woodwastes Utilization & Disposal.
207	32	East-West Center Program on Resources: Energy and Minerals. 1993. Fossil Energy in Hawaii.
208	33	Falkebag, Ingemar. 1975. Lignin in Materials. Printed in Proceedings of the Eighth Cellulose Conference. Applied Polymer Symposia, No. 28.
209	34	American Society of Mechanical Engineers. Thermodynamic Data for Biomass Materials and Waste Components. Sponsored by the ASME Research Committee on Industrial and Municipal Wastes.

	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
210																	
211	Data for graphs (all yields are in terms of dry tons per acre per year unless otherwise noted)	Sweet Sorghum (6 cult; avg. 2 crops)	Sweet Sorghum (MN 1500; 2 crops)	Napiergrass (Avg 2 crops; 5 locations)	Napiergrass (Avg 7 crops; 1 location)	Eucalyptus (close spacing trial)	Eucalyptus (close spacing trial)	Eucalyptus (large plots - Mt. View)	Eucalyptus (large plots - Honokaa)	Eucalyptus (large plots - Kauai)	Leucaena leucocephala (large plots - Maui)	Leucaena leucocephala (large plots - Molokai)	Sugarcane Maui (from HSPA Variety Tests) (4)	Sugarcane Kahu (from HSPA Variety Tests) (4)	Sugarcane ("prepared cane")	Sugarcane: usually burned	Unburned sugarcane
212	Wet weight (tons/acre/yr)	50	71	85	53	24	14	28	21	12	17	14	55	42	49	7	52
213	Dry matter (tons/acre/yr)	15	21	20	13	10	6	12	9	5	7	6	17	13	12	3.8	15
214	Potential ethanol yield (gallons/net acre/harvest)	708	898	745	565	1,444	2,086	1,689	3,223	1,771	2,806	2,440	3,007	2,814	3,095	625	3,720
215	Potential ethanol yield (gallons/net acre/year)	1,847	2,596	1,962	839	719	413	647	648	356	560	488	1,824	1,410	1,391	281	1,672
216	Upper Range of Experimental Yields (dry tons/acre/yr)	22	11	19	32	33											
217	Commercial Yields (dry tons/acre/yr)	17	8	14	24	25											
218	Commercial Yields (dry tons/acre/yr)	17	7	12	20	21											
219	Commercial Yields (dry tons/acre/yr)	17	7	10	20	23											
220	Lower Range of Experimental Yields (dry tons/acre/yr)	17	7	8	15	17											
221	Commercial Yields (dry tons/acre/yr)	13	7	6	13	15											
222	Commercial Yields (dry tons/acre/yr)	13	6	5	13	15											
223	NEWSPAPER MUNICIPAL SOLID WASTE MOLASSES BAGASSE UNBURNED PREPARED LEUCOEN A PTUS ASS SWEET SORGHUM																
224	BLOMSS	110	60	95	86	112	114	80	71	67	125						
225	Sugarcane Leucaena Eucalyptus Napiergrass Sweet sorghum																
226	From Upper Range of Experimental Yields (dry tons/acre/yr)	2534	880	1325	2133	4082											
227	Commercial Yields (dry tons/acre/yr)	1906	664	997	1603	3058											
228	From Upper Range of Experimental Yields (dry tons/acre/yr)	1983	560	847	1362	2596											
229	Yields (dry tons/acre/yr)	1906	768	555	1315	2896											
230	Commercial Yields (dry tons/acre/yr)	1427	576	420	886	2172											
231	From Lower Range of Estimated Commercial Yields (dry tons/net acre/yr)	1427	488	356	839	1847											

	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
232															
233	Cost Center	Sugarcane (irrigated)			Napiergrass (irrigated)		Leucaena (irrigated)		Sugarcane (rainfed)			Eucalyptus (rainfed)		Napiergrass (rainfed)	
234	tons/acre/yr	16.0	%		18.0		10.0		14.0	%		8.5		15.0	
235	Cost center	(\$/acre/yr)	(\$/ton)	of total cost	(\$/acre/yr)	(\$/ton)	(\$/acre/yr)	(\$/ton)	(\$/acre/yr)	(\$/ton)	of total cost	(\$/acre/yr)	(\$/ton)	(\$/acre/yr)	(\$/ton)
236	Landholding	\$100	\$8	8%	\$100	\$8	\$100	\$10	\$100	\$7	8%	\$100	\$12	\$100	\$7
237	Soil preparation	\$53	\$3	4%	\$27	\$2	\$5	\$1	\$53	\$4	2%	\$49	\$8	\$27	\$2
238	Planting/ratooning	\$135	\$8	10%	\$67	\$4	\$16	\$2	\$135	\$10	5%	\$16	\$2	\$67	\$4
239	Weed control	\$92	\$8	7%	\$46	\$3	\$64	\$6	\$92	\$7	4%	\$41	\$5	\$46	\$3
240	Irrigation	\$260	\$16	20%	\$371	\$21	\$328	\$33	\$0	\$0	30%	\$0	\$0	\$0	\$0
241	Fertilization	\$115	\$7	9%	\$148	\$8	\$40	\$4	\$115	\$8	12%	\$40	\$5	\$148	\$10
242	Other field	\$179	\$11	13%	\$89	\$5	\$89	\$9	\$179	\$13	7%	\$30	\$4	\$89	\$6
243	Harvesting	\$123	\$8	9%	\$115	\$6	\$238	\$24	\$123	\$9	9%	\$251	\$30	\$115	\$8
244	Hauling	\$155	\$10	12%	\$180	\$10	\$36	\$4	\$155	\$11	14%	\$48	\$6	\$180	\$12
245	G&A-Field	\$121	\$8	9%	\$114	\$6	\$92	\$9	\$95	\$7	9%	\$58	\$7	\$90	\$6
246	Research		\$0	0%		\$0		\$0		\$0	0%		\$0		\$0
247	Total delivered cost	\$1,333	\$83	100%	\$1,257	\$70	\$1,008	\$101	\$1,047	\$75	100%	\$633	\$74	\$862	\$57
248	Cost/ton		\$83			\$70		\$101		\$75			\$74		\$57
249	Cost per acre per harvest	\$2,967			\$891		\$5,040		\$2,330			\$3,165		\$474	
250															
251															
252															
253		tons sugar per wet ton prep. cane			0.1										
254		1981-92 avg. tons sugar per dry ton prep. cane			0.4										
255		1991 value of sugar per wet ton prep. cane			\$38	assumes \$360/ton raw sugar									
256		value of sugar in one dry ton prep. cane			\$129										
257		1991 production cost per ton of sugar			\$417	Includes sugar factory costs. 1991 average, from HSPA 18th Annual News Media Briefing, 3/19/92									
258		1991 tons sugar per acre			10.4	1991 average yield, unpublished HSPA data									
259		average sugarcane production cost per acre (24 month harvest)			\$4,348	Includes sugar factory costs. 1991 average, calculated									
260		tons sugar per acre			11.5	1981-92 average yield									
261		sugarcane production cost per ton of sugar adjusted to 81-92 average			\$379	1991 costs per ton sugar, adjusted for 1981-1992 average yields per acre									
262		cost per acre (24 month harvest)			\$2,648	From Osgood & Dudley, above. Does not include sugar factory costs									
263		sugar processing costs per acre			\$791	Based on Osgood & Dudley, plus Kinoshita est. cost after factory gate =									
264		sugar processing costs per ton sugar			\$69	costs per acre adjusted for 1981-1992 av. sugar yield per acre									
265		sugar processing costs for sugar in one dry ton prepared cane			\$25										
266					\$300	costs per ton sugar, using Osgood & Dudley and 1981-92 average yields									
267					-21%	% diff compared to 1991 costs (adj. for 81-92 avg. yields)									
268															
269															

	C	D	E	F	G	H	I	J	K	L	M
	COMPONENT	Bagasse	R E F #	Molasses	Sugarcane ("prepared cane")	Sugarcane: leafy trash usually burned		Unburned sugarcane			
271											
272	Tons (dry matter) per acre per harvest	16.8		2.8	31.9	9.9	2	39.0			
273	Est. max. cost per harvested acre	\$0		\$0	\$3,918	\$383		\$4,301			
274	Estimated average cost per harvested acre	\$0		\$0	\$2,648	\$259	harvesting 40% handling	\$2,907			
275	Est. min. cost per harvested acre	\$0		\$0	\$2,084	\$204		\$2,288			
276	Est. max. cost (dollars) per ton (dry matter)	\$0.00	byproduct	\$0	\$123	\$38.74		\$110.29			
277	Est. average cost per ton (dry basis)	\$0.00		\$0	\$83	\$26.18		\$74.55			
278	Est. min. cost (dollars) per ton (dry matter)	\$0.00		\$0	\$65	\$20.60		\$58.66			
279	Cost to replace dry ton bagasse w/Diesel	\$72.23	\$32.00								
280	Cost to replace dry ton bagasse w/#6 oil	\$42.28	\$20.00								
281	Cost to replace dry ton bagasse w/Coal	\$38.05	\$60.00	32							
282	Estimated upper end of range, plant gate cost per dry ton	\$72.23	16	\$47.20	\$122.80	\$38.74		\$110.29			
283	Estimated lower end of range, plant gate cost per dry ton	\$38.05		\$47.20	\$65.31	\$20.60		\$58.66			
284	BIOMASS	Sugarcane	Leucaena	Eucalyptus	Napiergrass	Sweet sorghum	Newspaper	Municipal Solid Waste	Molasses	Bagasse	Unburned sugarcane
285	Cost per acre per year	\$1,190	\$1,008	\$633	\$1,060	\$1,333	--	--	--	--	--
286	Estimated upper end of range, feedstock cost per dry ton	\$95	\$165	\$127	\$85	\$90	\$15	\$25	\$47	\$72	\$110
287	Estimated lower end of range, feedstock cost per dry ton	\$69	\$144	\$53	\$52	\$64	\$5	\$0	\$47	\$38	\$59
288	Estimated upper end of range, feedstock cost per potential ethanol gallon	\$0.83	\$2.06	\$1.78	\$1.26	\$0.72	\$0.14	\$0.42	\$0.50	\$0.84	\$0.98
289	Estimated lower end of range, feedstock cost per potential ethanol gallon	\$0.61	\$1.80	\$0.75	\$0.78	\$0.51	\$0.05	\$0.00	\$0.50	\$0.44	\$0.52
290		Cost per acre per year	Estimated upper end of range, feedstock cost per dry ton	Estimated lower end of range, feedstock cost per dry ton	Estimated upper end of range, feedstock cost per potential ethanol gallon	Estimated lower end of range, feedstock cost per potential ethanol gallon					
291	Sugarcane	\$1,190.00	\$95.20	\$69.18	\$0.83	\$0.61					
292	Leucaena	\$1,008.00	\$165.25	\$127.00	\$2.06	\$1.80					
293	Eucalyptus	\$633.00	\$126.60	\$53.19	\$1.78	\$0.75					
294	Napiergrass	\$1,059.50	\$84.76	\$52.19	\$1.26	\$0.78					
295	Sweet sorghum	\$1,333.00	\$90.07	\$64.09	\$0.72	\$0.51					
296	Newspaper	--	\$15.00	\$5.00	\$0.14	\$0.05					
297	Municipal Solid Waste	--	\$25.00	\$0.00	\$0.42	\$0.00					
298	Molasses	--	\$47.20	\$47.20	\$0.50	\$0.50					
299	Bagasse	--	\$72.23	\$38.05	\$0.84	\$0.44					
300	Unburned sugarcane	--	\$110.29	\$58.66	\$0.98	\$0.52					

	C	D	E	F	G	H
302	INDEPENDENT VARIABLES		ref #	PG #	REALITY CHECK INFO	
303	Power Law Scaling Factor	0.7			FEEDSTOCK: Sugarcane ("prepared cane")	
304	Contingency	10%			TONS FERMENTABLE SUGAR PER TON BIOMASS	0.81
305	Start-up factor	5%			TONS ETHANOL PER TON BIOMASS, ASSUMING 100% OF SUGARS ARE FERMENTED:	0.41
306	Working Capital	7.50%			MAXIMUM THEORETICAL YIELD, GALLONS ETHANOL PER TON PREPARED CANE DRY MATTER:	125.15
307	Operating Days per Year	330				
308	Personnel Scaling Factor	0.9				
309	Property Tax & Insurance	1.50%				
310	Biomass Cost/ton-					
311	PROCESS COST ONLY (BIOMASS \$0)	\$0.00				
312	BIOMASS COST 1	\$50.00			RESULTS OF REALITY CHECK:	% of theoretical
313	BIOMASS COST 2	\$109.00			NREL SSF ESTIMATED BASE COSTS	73.8%
314	Denaturant Cost, \$/gal	0.87			TVA ACID ESTIMATED BASE COSTS	63.6%
315	Denaturant Use	5.00%	26	p.12-4	STAKETECH ESTIMATED BASE COSTS	74.4%
316	Fringe Benefits	25%			BIOENERGY ESTIMATED BASE COSTS	72.2%
317	Depreciation period (yrs)	30			ARKENOL ESTIMATED BASE COSTS	72.7%
318	Salvage value (% of original value)	10%			PASZNER TECHNOLOGY ESTIMATED BASE COSTS	77.7%
319	Interest rate	0.00%			ASSUMPTION USED ABOVE IN "POTENTIAL ETHANOL GALLONS"	91.2%
320	Plant feedrate (dry tons per day)					
321	Ethanol Production (MM gal/yr)	5	PLANT SIZE 1			
322	Producing MM gal. per year-	25	PLANT SIZE 2			

	C	D	E	F	G	H	I	J	K	L	M	N
324												
325	NREL SSF ESTIMATED BASE COSTS						PROCESS COST ONLY (BIOMASS \$0)					
	NREL SSF ESTIMATED BASE COSTS						NREL SSF ESTIMATED BASE COSTS					
326	Plant feedrate (dry tons per day)	1900	Biomass Cost/ton-	\$50.00			Plant feedrate (dry tons per day)	820		Ratio of orig. to proposed size-	0.43	
327	Ethanol Production (MM gal/yr)	57.91				Ethanol Production (MM gal/yr)	25	Scaling of original data	0.56	Biomass Cost/ton-	\$0.00	
328	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
329	100	Biomass Preparation	\$6.498	Biomass	\$31,350.000	\$0.541	100	Biomass Preparation	\$3.609	Biomass	\$0.000	\$0.000
330	200	Pretreatment	\$20.634	Chemicals			200	Pretreatment	\$11.461	Chemicals		
331	210	Recycle & Recovery	\$0.000	Denaturant	\$2,200.000	\$0.038	210	Recovery & Recycle	\$0.000	Denaturant	\$1,087.500	\$0.044
332	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000
333	400	Fermentation	\$0.000	Ammonia	\$0.000	\$0.000	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000
334	410	Hexose Fermentation	\$20.235	Nutrients	\$0.000	\$0.000	410	Hexose Fermentation	\$11.239	Nutrients	\$0.000	\$0.000
335	420	Pentose Fermentation	\$5.643	Enzymes	\$0.000	\$0.000	420	Pentose Fermentation	\$3.134	Enzymes	\$0.000	\$0.000
336	500	Distillation & Dehydration	\$3.534	Yeast	\$0.000	\$0.000	500	Distillation & Dehydration	\$1.963	Yeast	\$0.000	\$0.000
337	600	By-Product Preparation	\$0.000	Other Chemicals	\$7,740.000	\$0.134	600	By-Product Preparation	\$0.000	Other Chemicals	\$3,341.392	\$0.134
338	610	Stillage Evaporation	\$0.000	RAW MATERIALS TOTAL	\$41,290.000	\$0.713	610	Stillage Evaporation	\$0.000	RAW MATERIALS TOTAL	\$4,428.892	\$0.177
339	700	Product Storage & Denature	\$2.850	Utilities			700	Product Storage & Denature	\$1.583	Utilities		
340	800	Utilities & General	\$0.000	Electricity/ Energy	(\$3,220.00)	(\$0.06)	800	Utilities & General	\$0.000	Electricity/ Energy	(\$1,390.09)	(\$0.06)
341	810	Boiler	\$18.020	Water	\$120.000	\$0.002	810	Boiler	\$10.009	Water	\$51.805	\$0.002
342	820	Non-Boiler Utilities	\$30.210	By-products	\$400.000	\$0.007	820	Non-Boiler Utilities	\$16.780	By-products	\$172.682	\$0.007
343	830	Environmental	\$3.734	VARIABLE COST TOTAL	\$38,590.000	\$0.666	830	Environmental	\$2.074	VARIABLE COST TOTAL	\$3,263.290	\$0.131
344	840	Miscellaneous & Control	\$5.786	GEN & ADMIN	\$3,500.000	\$0.060	840	Miscellaneous & Control	\$3.213	GEN & ADMIN	\$1,590.000	\$0.064
345	900	Enzyme Production	\$2.451				900	Enzyme Production	\$1.361			
346				Operators	\$3,237.000	\$0.056				Operators	\$1,519.884	\$0.061
347		Total Installed Equipment	\$119.594	Laborers	\$2,130.000	\$0.037	1000	Total Fixed Capital	\$66.426	Laborers	\$1,000.109	\$0.040
348				Technicians	\$447.000	\$0.008				Technicians	\$209.882	\$0.008
349		Fixed Capital	\$119.594	Maintenance	\$1,704.000	\$0.029	1010	Contingency	\$6.643	Maintenance	\$800.087	\$0.032
350	10%	Miscellaneous	\$11.959	Fringe Benefits	\$1,879.500	\$0.032	1020	Startup	\$3.321	Fringe Benefits	\$882.491	\$0.035
351	5%	Start-up Costs	\$5.980	TOTAL LABOR	\$9,397.500	\$0.162	1030	Working Capital	\$4.982	TOTAL LABOR	\$4,412.453	\$0.176
352	7.50%	Working capital	\$8.970	Property Tax & Insur.	\$2,197.540	\$0.038				Property Tax & Insur.	\$1,220.583	\$0.049
353				TOTAL CASH	\$53,685.040	\$0.927		TOTAL CAPITAL	\$81.372	TOTAL CASH	\$10,486.326	\$0.419
354		TOTAL CAPITAL	\$146.503	Depreciation	\$4,395.080	\$0.076				Depreciation	\$2,441.166	\$0.098
355				Interest	\$0.000	\$0.000				Interest	\$0.000	\$0.000
356				TOTAL PRODUCTION	\$58,080.119	\$1.003				TOTAL PRODUCTION	\$12,927.492	\$0.517
358								Power Law Scaling Factor	0.7	PROCESS COST ONLY (BIOMASS \$0)		\$0.00
359								Contingency	10.00%	BIOMASS COST 1		\$50.00
360								Start-up factor	5.00%	BIOMASS COST 2		\$109.00
361								Working Capital	7.50%	Denaturant Cost, \$/gal		\$0.87
362								Operating Days per Year	330	Denaturant Use		5%
363								Personnel Scaling Factor	0.9	Fringe Benefits		25%
364								Property Tax & Insurance	1.50%	Depreciation period (yrs)		30

	I	J	K	L	M	N	O	P	Q	R	S	T
324	PROCESS COST ONLY (BIOMASS \$0)						PROCESS COST ONLY (BIOMASS \$0)					
325	NREL SSF ESTIMATED BASE COSTS						NREL SSF ESTIMATED BASE COSTS					
326	Plant feedrate (dry tons per day)	820		Ratio of orig. to proposed size-	0.43		Plant feedrate (dry tons per day)	164.05	Biomass Cost/ton-	\$0.00	Ratio of orig. to proposed size-	0.09
327	Ethanol Production (MM gal/yr)	25	Scaling of original data	0.56	Biomass Cost/ton-	\$0.00	Ethanol Production (MM gal/yr)	5			Scaling of original data	0.18
328	AREA	CAPITAL COSTS	Million \$	PRODUCTI ON COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTI ON COSTS	Thous \$/Yr	\$/gal
329	100	Biomass Preparation	\$3.609	Biomass	\$0.000	\$0.000	100	Biomass Preparation	\$1.170	Biomass	\$0.000	\$0.000
330	200	Pretreatment	\$11.461	Chemicals			200	Pretreatment	\$3.715	Chemicals		
331	210	Recovery & Recycle	\$0.000	Denaturant	\$1,087.500	\$0.044	210	Recovery & Recycle	\$0.000	Denaturant	\$217.500	\$0.044
332	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000
333	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000
334	410	Hexose Fermentation	\$11.239	Nutrients	\$0.000	\$0.000	410	Hexose Fermentation	\$3.643	Nutrients	\$0.000	\$0.000
335	420	Pentose Fermentation	\$3.134	Enzymes	\$0.000	\$0.000	420	Pentose Fermentation	\$1.016	Enzymes	\$0.000	\$0.000
336	500	Distillation & Dehydration	\$1.963	Yeast	\$0.000	\$0.000	500	Distillation & Dehydration	\$0.636	Yeast	\$0.000	\$0.000
337	600	By-Product Preparation	\$0.000	Other Chemicals RAW	\$3,341.392	\$0.134	600	By-Product Preparation	\$0.000	Other Chemicals RAW	\$668.278	\$0.134
338	610	Stillage Evaporation	\$0.000	MATERIALS TOTAL	\$4,428.892	\$0.177	610	Stillage Evaporation	\$0.000	MATERIALS TOTAL	\$885.778	\$0.177
339	700	Product Storage & Denature	\$1.583	Utilities			700	Storage & Denature	\$0.513	Utilities		
340	800	Utilities & General	\$0.000	Electricity/ Energy	(\$1,390.09)	(\$0.06)	800	Utilities & General	\$0.000	Electricity/ Energy	(\$278.02)	(\$0.06)
341	810	Boiler	\$10.009	Water	\$51.805	\$0.002	810	Boiler	\$3.244	Water	\$10.361	\$0.002
342	820	Non-Boiler Utilities	\$16.780	By-products	\$172.682	\$0.007	820	Non-Boiler Utilities	\$5.439	By-products	\$34.536	\$0.007
343	830	Environmental	\$2.074	VARIABLE COST TOTAL	\$3,263.290	\$0.131	830	Environmental	\$0.672	VARIABLE COST TOTAL	\$652.658	\$0.131
344	840	Miscellaneous & Control	\$3.213	GEN & ADMIN	\$1,590.000	\$0.064	840	Miscellaneous & Control	\$1.042	GEN & ADMIN	\$373.529	\$0.075
345	900	Enzyme Production	\$1.361				900	Enzyme Production	\$0.441			
346				Operators	\$1,519.884	\$0.061				Operators	\$357.057	\$0.071
347	1000	Total Fixed Capital	\$66.426	Laborers	\$1,000.109	\$0.040	1000	Total Fixed Capital	\$21.531	Laborers	\$234.949	\$0.047
348				Technicians	\$209.882	\$0.008				Technicians	\$49.306	\$0.010
349	1010	Contingency	\$6.643	Maintenance	\$800.087	\$0.032	1010	Contingency	\$2.153	Maintenance	\$187.960	\$0.038
350	1020	Startup	\$3.321	Fringe Benefits	\$882.491	\$0.035	1020	Startup	\$1.077	Fringe Benefits	\$207.318	\$0.041
351	1030	Working Capital	\$4.982	TOTAL LABOR	\$4,412.453	\$0.176	1030	Working Capital	\$1.615	TOTAL LABOR	\$1,036.590	\$0.207
352				Property Tax & Insur.	\$1,220.583	\$0.049				Property Tax & Insur.	\$395.629	\$0.079
353		TOTAL CAPITAL	\$81.372	TOTAL CASH	\$10,486.326	\$0.419		TOTAL CAPITAL	\$26.375	TOTAL CASH	\$2,458.406	\$0.492
354				Depreciation	\$2,441.166	\$0.098				Depreciation	\$791.258	\$0.158
355				Interest	\$0.000	\$0.000				Interest	\$0.000	\$0.000
356												
357				TOTAL PRODUCTION	\$12,927.492	\$0.517				TOTAL PRODUCTION	\$3,249.664	\$0.650
358	Power Law Scaling Factor	0.7	PROCESS COST ONLY (BIOMASS \$0)			\$0.00	Power Law Scaling Factor	0.7	COST ONLY (BIOMASS \$0)			\$0.00
359	Contingency	10.00%	BIOMASS COST 1			\$50.00	Contingency	10.00%	BIOMASS COST 1			\$50.00
360	Start-up factor	5.00%	BIOMASS COST 2			\$109.00	Start-up factor	5.00%	BIOMASS COST 2			\$109.00
361	Working Capital	7.50%	Denaturant Cost, \$/gal			\$0.87	Working Capital	7.50%	Denaturant Cost, \$/gal			\$0.87
362	Operating Days per Year	330	Denaturant Use			5%	Operating Days per Year	330	Denaturant Use			5%
363	Personnel Scaling Factor	0.9	Fringe Benefits			25%	Personnel Scaling Factor	0.9	Fringe Benefits			25%
364	Property Tax & Insurance	1.50%	Depreciation period (yrs)			30	Property Tax & Insurance	1.50%	Depreciation period (yrs)			30

	I	J	K	L	M	N	O	P	Q	R	S	T
324	PROCESS COST ONLY (BIOMASS \$0)						PROCESS COST ONLY (BIOMASS \$0)					
325	NREL SSF ESTIMATED BASE COSTS						NREL SSF ESTIMATED BASE COSTS					
326	Plant feedrate (dry tons per day)	820		Ratio of orig. to proposed size-	0.43		Plant feedrate (dry tons per day)	164.05	Biomass Cost/ton-	\$0.00	Ratio of orig. to proposed size-	0.09
327	Ethanol Production (MM gal/yr)	25	Scaling of original data	0.56	Biomass Cost/ton-	\$0.00	Ethanol Production (MM gal/yr)	5			Scaling of original data	0.18
328	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
329	100	Biomass Preparation	\$3.609	Biomass	\$0.000	\$0.000	100	Biomass Preparation	\$1.170	Biomass	\$0.000	\$0.000
330	200	Pretreatment	\$11.461	Chemicals			200	Pretreatment	\$3.715	Chemicals		
331	210	Recovery & Recycle	\$0.000	Denaturant	\$1,087.500	\$0.044	210	Recovery & Recycle	\$0.000	Denaturant	\$217.500	\$0.044
332	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000
333	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000
334	410	Hexose Fermentation	\$11.239	Nutrients	\$0.000	\$0.000	410	Hexose Fermentation	\$3.643	Nutrients	\$0.000	\$0.000
335	420	Pentose Fermentation	\$3.134	Enzymes	\$0.000	\$0.000	420	Pentose Fermentation	\$1.016	Enzymes	\$0.000	\$0.000
336	500	Distillation & Dehydration	\$1.963	Yeast	\$0.000	\$0.000	500	Distillation & Dehydration	\$0.636	Yeast	\$0.000	\$0.000
337	600	By-Product Preparation	\$0.000	Other Chemicals	\$3,341.392	\$0.134	600	By-Product Preparation	\$0.000	Other Chemicals	\$668.278	\$0.134
338	610	Stillage Evaporation	\$0.000	MATERIALS TOTAL	\$4,428.892	\$0.177	610	Stillage Evaporation	\$0.000	MATERIALS TOTAL	\$885.778	\$0.177
339	700	Product Storage & Denature	\$1.583	Utilities			700	Storage & Denature	\$0.513	Utilities		
340	800	Utilities & General	\$0.000	Electricity/ Energy	(\$1,390.09)	(\$0.06)	800	Utilities & General	\$0.000	Electricity/ Energy	(\$278.02)	(\$0.06)
341	810	Boiler	\$10.009	Water	\$51.805	\$0.002	810	Boiler	\$3.244	Water	\$10.361	\$0.002
342	820	Non-Boiler Utilities	\$16.780	By-products	\$172.682	\$0.007	820	Non-Boiler Utilities	\$5.439	By-products	\$34.536	\$0.007
343	830	Environmental	\$2.074	VARIABLE COST TOTAL	\$3,263.290	\$0.131	830	Environmental	\$0.672	VARIABLE COST TOTAL	\$652.658	\$0.131
344	840	Miscellaneous & Control	\$3.213	GEN & ADMIN	\$1,590.000	\$0.064	840	Miscellaneous & Control	\$1.042	GEN & ADMIN	\$373.529	\$0.075
345	900	Enzyme Production	\$1.361				900	Enzyme Production	\$0.441			
346				Operators	\$1,519.884	\$0.061				Operators	\$357.057	\$0.071
347	1000	Total Fixed Capital	\$66.426	Laborers	\$1,000.109	\$0.040	1000	Total Fixed Capital	\$21.531	Laborers	\$234.949	\$0.047
348				Technicians	\$209.882	\$0.008				Technicians	\$49.306	\$0.010
349	1010	Contingency	\$6.643	Maintenance	\$800.087	\$0.032	1010	Contingency	\$2.153	Maintenance	\$187.960	\$0.038
350	1020	Startup	\$3.321	Fringe Benefits	\$882.491	\$0.035	1020	Startup	\$1.077	Fringe Benefits	\$207.318	\$0.041
351	1030	Working Capital	\$4.982	TOTAL LABOR	\$4,412.453	\$0.176	1030	Working Capital	\$1.615	TOTAL LABOR	\$1,036.590	\$0.207
352				Property Tax & Insur.	\$1,220.583	\$0.049				Property Tax & Insur.	\$395.629	\$0.079
353		TOTAL CAPITAL	\$81.372	TOTAL CASH	\$10,486.326	\$0.419		TOTAL CAPITAL	\$26.375	TOTAL CASH	\$2,458.406	\$0.492
354				Depreciation	\$2,441.166	\$0.098				Depreciation	\$791.258	\$0.158
355				Interest	\$0.000	\$0.000				Interest	\$0.000	\$0.000
356												
357				PRODUCT	\$12,927.492	\$0.517				PRODUCT	\$3,249.664	\$0.650
358	Power Law Scaling Factor		0.7	PROCESS COST ONLY (BIOMASS \$0)		\$0.00	Power Law Scaling Factor		0.7	PROCESS COST ONLY (BIOMASS \$0)		\$0.00
359	Contingency		10.00%	BIOMASS COST 1		\$50.00	Contingency		10.00%	BIOMASS COST 1		\$50.00
360	Start-up factor		5.00%	BIOMASS COST 2		\$109.00	Start-up factor		5.00%	BIOMASS COST 2		\$109.00
361	Working Capital		7.50%	Denaturant Cost, \$/gal		\$0.87	Working Capital		7.50%	Denaturant Cost, \$/gal		\$0.87
362	Operating Days per Year		330	Denaturant Use		5%	Operating Days per Year		330	Denaturant Use		5%
363	Personnel Scaling Factor		0.9	Fringe Benefits		25%	Personnel Scaling Factor		0.9	Fringe Benefits		25%
364	Property Tax & Insurance		1.50%	Depreciation period (yrs)		30	Property Tax & Insurance		1.50%	Depreciation period (yrs)		30

	U	V	W	X	Y	Z	AA	AB	AC	AD	AE	AF
324	BIOMASS COST 1						BIOMASS COST 1					
325	NREL SSF ESTIMATED BASE COSTS						NREL SSF ESTIMATED BASE COSTS					
326	Plant feedrate (dry tons per day)	820	Biomass Cost/ton-	\$50.00	Ratio of orig. to proposed size-	0.43	Plant feedrate (dry tons per day)	164.05	Biomass Cost/ton-	\$50.00	Ratio of orig. to proposed size-	0.09
327	Ethanol Production (MM gal/yr)	25	Scaling of original data	0.56			Ethanol Production (MM gal/yr)	5	Scaling of original data	0.18		
328	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
329	100	Biomass Preparation	\$3.609	Biomass	\$13,533.932	\$0.541	100	Biomass Preparation	\$1.170	Biomass	\$2,706.786	\$0.541
330	200	Pretreatment	\$11.461	Chemicals			200	Pretreatment	\$3.715	Chemicals		
331	210	Recovery & Recycle	\$0.000	Denaturant	\$1,087.500	\$0.044	210	Recovery & Recycle	\$0.000	Denaturant	\$217.500	\$0.044
332	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000
333	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000
334	410	Hexose Fermentation	\$11.239	Nutrients	\$0.000	\$0.000	410	Hexose Fermentation	\$3.643	Nutrients	\$0.000	\$0.000
335	420	Pentose Fermentation	\$3.134	Enzymes	\$0.000	\$0.000	420	Pentose Fermentation	\$1.016	Enzymes	\$0.000	\$0.000
336	500	Distillation & Dehydration	\$1.963	Yeast	\$0.000	\$0.000	500	Distillation & Dehydration	\$0.636	Yeast	\$0.000	\$0.000
337	600	By-Product Preparation	\$0.000	Other Chemicals	\$3,341.392	\$0.134	600	By-Product Preparation	\$0.000	Other Chemicals	\$668.278	\$0.134
338	610	Stillage Evaporation	\$0.000	RAW MATERIALS	\$17,962.824	\$0.719	610	Stillage Evaporation	\$0.000	RAW MATERIALS	\$3,592.565	\$0.719
339	700	Product Storage & Distribution	\$1.583	Utilities			700	Product Storage & Distribution	\$0.513	Utilities		
340	800	Utilities & General	\$0.000	Electricity/ Energy	(\$1,390.09)	(\$0.06)	800	Utilities & General	\$0.000	Electricity/ Energy	(\$278.02)	(\$0.06)
341	810	Boiler	\$10.009	Water	\$51.805	\$0.002	810	Boiler	\$3.244	Water	\$10.361	\$0.002
342	820	Non-Boiler Utilities	\$16.780	By-products	\$172.682	\$0.007	820	Non-Boiler Utilities	\$5.439	By-products	\$34.536	\$0.007
343	830	Environmental	\$2.074	VARIABLE COSTS	\$16,797.222	\$0.672	830	Environmental	\$0.672	VARIABLE COSTS	\$3,359.444	\$0.672
344	840	Miscellaneous & Control	\$3.213	GEN & ADMIN	\$1,590.000	\$0.064	840	Miscellaneous & Control	\$1.042	GEN & ADMIN	\$373.529	\$0.075
345	900	Enzyme Production	\$1.361				900	Enzyme Production	\$0.441			
346				Operators	\$1,519.884	\$0.061				Operators	\$357.057	\$0.071
347	1000	Total Fixed Capital	\$66.426	Laborers	\$1,000.109	\$0.040	1000	Total Fixed Capital	\$21.531	Laborers	\$234.949	\$0.047
348				Technicians	\$209.882	\$0.008				Technicians	\$49.306	\$0.010
349	1010	Contingency	\$6.643	Maintenance	\$800.087	\$0.032	1010	Contingency	\$2.153	Maintenance	\$187.960	\$0.038
350	1020	Startup	\$3.321	Fringe Benefits	\$882.491	\$0.035	1020	Startup	\$1.077	Fringe Benefits	\$207.318	\$0.041
351	1030	Working Capital	\$4.982	TOTAL LABOR	\$4,412.453	\$0.176	1030	Working Capital	\$1.615	TOTAL LABOR	\$1,036.590	\$0.207
352				Property Tax & Insurance	\$1,220.583	\$0.049				Property Tax & Insurance	\$395.629	\$0.079
353		TOTAL CAPITAL	\$81.372	TOTAL CASH	\$24,020.258	\$0.961		TOTAL CAPITAL	\$26.375	TOTAL CASH	\$5,165.193	\$1.033
354				Depreciation	\$2,441.166	\$0.098				Depreciation	\$791.258	\$0.158
355				Interest	\$0.000	\$0.000				Interest	\$0.000	\$0.000
356												
357				TOTAL PRODUCTION	\$26,461.424	\$1.058				TOTAL PRODUCTION	\$5,956.451	\$1.191
358	Power Law Scaling Factor		0.7	PROCESS COSTS	\$0.00	#####	Power Law Scaling Factor		0.7	PROCESS COSTS	\$0.00	
359	Contingency		10.00%	BIOMASS COST 1	\$50.00	#####	Contingency		10.00%	BIOMASS COST 1	\$50.00	
360	Start-up factor		5.00%	BIOMASS COST 2	\$109.00		Start-up factor		5.00%	BIOMASS COST 2	\$109.00	
361	Working Capital		7.50%	Denaturant Cost, \$/gal	\$0.87	\$1.058	Working Capital		7.50%	Denaturant Cost, \$/gal	\$0.87	
362	Operating Days per Year		330	Denaturant Use	5%		Operating Days per Year		330	Denaturant Use	5%	
363	Personnel Scaling Factor		0.9	Fringe Benefits	25%		Personnel Scaling Factor		0.9	Fringe Benefits	25%	

	AG	AH	AI	AJ	AK	AL	AM	AN	AO	AP	AQ	AR
324	BIOMASS COST 2						BIOMASS COST 2					
325	NREL SSF ESTIMATED BASE COSTS						NREL SSF ESTIMATED BASE COSTS					
	Plant feedrate (dry tons per day)	820	Biomass Cost/ton-	\$109.00	Ratio of orig. to proposed size-	0.43	Plant feedrate (dry tons per day)	164.05	Biomass Cost/ton-	\$109.00	Ratio of orig. to proposed size-	0.09
326	Ethanol Production (MM gal/yr)	25			Scaling of original data	0.56	Ethanol Production (MM gal/yr)	5		Scaling of original data	0.18	
327												
328	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
329	100	Biomass Preparation	\$3.609	Biomass	\$29,503.972	\$1.180	100	Biomass Preparation	\$1.170	Biomass	\$5,900.794	\$1.180
330	200	Pretreatment	\$11.461	Chemicals			200	Pretreatment	\$3.715	Chemicals		
331	210	Recovery & Recycle	\$0.000	Denaturant	\$1,087.500	\$0.044	210	Recovery & Recycle	\$0.000	Denaturant	\$217.500	\$0.044
332	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000	300	Hydrolysis	\$0.000	Acid	\$0.000	\$0.000
333	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000	400	Fermentation (Unallocated)	\$0.000	Ammonia	\$0.000	\$0.000
334	410	Hexose Fermentation	\$11.239	Nutrients	\$0.000	\$0.000	410	Hexose Fermentation	\$3.643	Nutrients	\$0.000	\$0.000
335	420	Pentose Fermentation	\$3.134	Enzymes	\$0.000	\$0.000	420	Pentose Fermentation	\$1.016	Enzymes	\$0.000	\$0.000
336	500	Distillation & Dehydration	\$1.963	Yeast	\$0.000	\$0.000	500	Distillation & Dehydration	\$0.636	Yeast	\$0.000	\$0.000
337	600	By-Product Preparation	\$0.000	Other Chemicals	\$3,341.392	\$0.134	600	By-Product Preparation	\$0.000	Other Chemicals	\$668.278	\$0.134
338	610	Stillage Evaporation	\$0.000	RAW MATERIALS	\$33,932.863	\$1.357	610	Stillage Evaporation	\$0.000	RAW MATERIALS	\$6,786.573	\$1.357
339	700	Product Storage & Denaturation	\$1.583	Utilities			700	Product Storage & Denaturation	\$0.513	Utilities		
340	800	Utilities & General	\$0.000	Electricity/ Energy	(\$1,390.09)	(\$0.06)	800	Utilities & General	\$0.000	Electricity/ Energy	(\$278.02)	(\$0.06)
341	810	Boiler	\$10.009	Water	\$51.805	\$0.002	810	Boiler	\$3.244	Water	\$10.361	\$0.002
342	820	Non-Boiler Utilities	\$16.780	By-products	\$172.682	\$0.007	820	Non-Boiler Utilities	\$5.439	By-products	\$34.536	\$0.007
343	830	Environmental	\$2.074	VARIABLE COSTS	\$32,767.262	\$1.311	830	Environmental	\$0.672	VARIABLE COSTS	\$6,553.452	\$1.311
344	840	Miscellaneous & Control	\$3.213	GEN & ADMIN	\$1,590.000	\$0.064	840	Miscellaneous & Control	\$1.042	GEN & ADMIN	\$373.529	\$0.075
345	900	Enzyme Production	\$1.361				900	Enzyme Production	\$0.441			
346				Operators	\$1,519.884	\$0.061				Operators	\$357.057	\$0.071
347	1000	Total Fixed Capital	\$66.426	Laborers	\$1,000.109	\$0.040	1000	Total Fixed Capital	\$21.531	Laborers	\$234.949	\$0.047
348				Technicians	\$209.882	\$0.008				Technicians	\$49.306	\$0.010
349	1010	Contingency	\$6.643	Maintenance	\$800.087	\$0.032	1010	Contingency	\$2.153	Maintenance	\$187.960	\$0.038
350	1020	Startup	\$3.321	Fringe Benefits	\$882.491	\$0.035	1020	Startup	\$1.077	Fringe Benefits	\$207.318	\$0.041
351	1030	Working Capital	\$4.982	TOTAL LABOR	\$4,412.453	\$0.176	1030	Working Capital	\$1.615	TOTAL LABOR	\$1,036.590	\$0.207
352				Property Tax & Insurance	\$1,220.583	\$0.049				Property Tax & Insurance	\$395.629	\$0.079
353		TOTAL CAPITAL	\$81.372	TOTAL CASH	\$39,990.298	\$1.600		TOTAL CAPITAL	\$26.375	TOTAL CASH	\$8,359.201	\$1.672
354				Depreciation	\$2,441.166	\$0.098				Depreciation	\$791.258	\$0.158
355				Interest	\$0.000	\$0.000				Interest	\$0.000	\$0.000
356												
357				TOTAL PROD	\$42,431.464	\$1.697				TOTAL PROD	\$9,150.459	\$1.830
358		Power Law Scaling Factor	0.7	PROCESS COSTS	\$0.00			Power Law Scaling Factor	0.7	PROCESS COSTS	\$0.00	
359		Contingency	10.00%	MASS COST 1	\$50.00			Contingency	10.00%	MASS COST 1	\$50.00	
360		Start-up factor	5.00%	MASS COST 2	\$109.00			Start-up factor	5.00%	MASS COST 2	\$109.00	
361		Working Capital	7.50%	Plant Cost, \$/gal	\$0.87			Working Capital	7.50%	Plant Cost, \$/gal	\$0.87	
362		Operating Days per Year	330	Denaturant Use	5%			Operating Days per Year	330	Denaturant Use	5%	
363		Personnel Scaling Factor	0.9	Fringe Benefits	25%			Personnel Scaling Factor	0.9	Fringe Benefits	25%	

	AS	AT	AU	AV	AW	AX	AY
324							
325		COSTS AS PERCENTAGE OF TOTAL					
326		NREL SSF ESTIMATED BASE COSTS					
327		Ethanol Production (MM gal/yr)		57.91	Biomass Cost/ton-		\$50.00
328		AREA	CAPITAL COSTS	% of capital cost	PRODUCTION COSTS	Thous \$/yr	% of \$/gallon cost
329		100	Biomass Preparation	4.4%	Biomass	1	54.0%
330		200	Pretreatment	14.1%	Chemicals	0	0.0%
331		210	Recycle & Recovery	0.0%	Denaturant	2200	3.8%
332		300	Hydrolysis	0.0%	Acid	0	0.0%
333		400	Fermentation	0.0%	Ammonia	0	0.0%
334		410	Hexose Fermentation	13.8%	Nutrients	0	0.0%
335		420	Pentose Fermentation	3.9%	Enzymes	0	0.0%
336		500	Distillation & Dehydration	2.4%	Yeast	0	0.0%
337		600	By-Product Preparation	0.0%	Other Chemicals	7740	13.3%
338		610	Stillage Evaporation	0.0%	RAW MATERIALS T	41290	71.1%
339		700	Product Storage & Denature	1.9%	Utilities	0	0.0%
340		800	Utilities & General	0.0%	Electricity/ Energy	-3220	-5.5%
341		810	Boiler	12.3%	Water	120	0.2%
342		820	Non-Boiler Utilities	20.6%	By-products	400	0.7%
343		830	Environmental	2.5%	VARIABLE COST T	38590	66.4%
344		840	Miscellaneous & Control	3.9%	GEN & ADMIN	3500	6.0%
345		900	Enzyme Production	1.7%			
346					Operators	3237	5.6%
347			Total Installed Equipment	81.6%	Laborers	2130	3.7%
348					Technicians	447	0.8%
349			Fixed Capital	81.6%	Maintenance	1704	2.9%
350		0.1	Miscellaneous	8.2%	Fringe Benefits	1880	3.2%
351		0.05	Start-up Costs	4.1%	TOTAL LABOR	9398	16.2%
352		0.075	Working capital	6.1%	Property Tax & Insur	2198	3.8%
353					TOTAL CASH	53685	92.4%
354			TOTAL CAPITAL	100.0%	Depreciation	4395	7.6%
355					Interest	0	0.0%
356							
357					TOTAL PRODUCTIO	58080	100.0%
358							
359							
360							
361							
362							
363							

	C	D	E	F	G	H
325	NREL SS					
326	-\$C\$320		1900	-\$C\$310	-\$D\$312	
327	-\$C\$321		57.91			
328	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
329	100	Biomass Preparation	-2.85*2.28	Biomass	-(E326*G326)*\$D\$307/1000	-G329/(E327*1000)
330	200	Pretreatment	-2.85*7.24	Chemicals		
331	210	Recycle & Recovery	0	Denaturant	2200	-G331/(E327*1000)
332	300	Hydrolysis	0	Acid	0	-G332/(E327*1000)
333	400	Fermentation	0	Ammonia	0	-G333/(E327*1000)
334	410	Hexose Fermentation	-2.85*7.1	Nutrients	0	-G334/(E327*1000)
335	420	Pentose Fermentation	-2.85*1.98	Enzymes	0	-G335/(E327*1000)
336	500	Distillation & Dehydration	-2.85*1.24	Yeast	0	-G336/(E327*1000)
337	600	By-Product Preparation	0	Other Chemicals	7740	-G337/(E327*1000)
338	610	Stillage Evaporation	0	RAW MATERIALS TOTAL	SUM(G329:G337)	-G338/(E327*1000)
339	700	Product Storage & Denature	-2.85*1	Utilities		
340	800	Utilities & General	0	Electricity/ Energy	-3220	-G340/(E327*1000)
341	810	Boiler	18.02	Water	120	-G341/(E327*1000)
342	820	Non-Boiler Utilities	-2.85*10.6	By-products	400	-G342/(E327*1000)
343	830	Environmental	-2.85*1.31	VARIABLE COST TOTAL	SUM(G338:G342)	-G343/(E327*1000)
344	840	Miscellaneous & Control	-2.85*2.03	GEN & ADMIN	3500	-G344/(E327*1000)
345	900	Enzyme Production	-2.85*0.86	Operators	3237	-G345/(E327*1000)
346						
347		Total Installed Equipment	-SUM(E329:E346)	Laborers	2130	-G347/(E327*1000)
348				Technicians	447	-G348/(E327*1000)
349		Fixed Capital	-E347	Maintenance	1704	-G349/(E327*1000)
350	-D304	Miscellaneous	-E349*C350	Fringe Benefits	-N363*SUM(G346:G349)	-G350/(E327*1000)
351	-D305	Start-up Costs	-E349*C351	TOTAL LABOR	-SUM(G346:G350)	-G351/(E327*1000)
352	-D306	Working capital	-E349*C352	Property Tax & Insur.	-K364*E354*1000	-G352/(E327*1000)
353				TOTAL CASH	-G343+G344+G351+G352	-G353/(E327*1000)
354	sln=straight line	TOTAL CAPITAL	-SUM(E349:E353)	Depreciation	-SLN((E354*1000)/(\$D\$318*1000*E354),\$D\$317)	-G354/(E327*1000)
355	db=real deprecia			Interest	-E354*1000*\$D\$319	-G355/(E327*1000)
356						
357				TOTAL PRODUCTION	-G353+G354+G355	-G357/(E327*1000)

I	J	K	L	M	N	O	P	Q	R	S	T
325	-\$C\$325					-\$C\$325					
326	-\$C\$326					-\$C\$326					
327	-\$C\$327					-\$C\$327					
328	-\$C\$328					-\$C\$328					
329	-\$C\$329					-\$C\$329					
330	-\$C\$330					-\$C\$330					
331	-\$C\$331					-\$C\$331					
332	-\$C\$332					-\$C\$332					
333	-\$C\$333					-\$C\$333					
334	-\$C\$334					-\$C\$334					
335	-\$C\$335					-\$C\$335					
336	-\$C\$336					-\$C\$336					
337	-\$C\$337					-\$C\$337					
338	-\$C\$338					-\$C\$338					
339	-\$C\$339					-\$C\$339					
340	-\$C\$340					-\$C\$340					
341	-\$C\$341					-\$C\$341					
342	-\$C\$342					-\$C\$342					
343	-\$C\$343					-\$C\$343					
344	-\$C\$344					-\$C\$344					
345	-\$C\$345					-\$C\$345					
346	-\$C\$346					-\$C\$346					
347	-\$C\$347					-\$C\$347					
348	-\$C\$348					-\$C\$348					
349	-\$C\$349					-\$C\$349					
350	-\$C\$350					-\$C\$350					
351	-\$C\$351					-\$C\$351					
352	-\$C\$352					-\$C\$352					
353	-\$C\$353					-\$C\$353					
354	-\$C\$354					-\$C\$354					
355	-\$C\$355					-\$C\$355					
356	-\$C\$356					-\$C\$356					
357	-\$C\$357					-\$C\$357					
358	-\$C\$358					-\$C\$358					
359	-\$C\$359					-\$C\$359					
360	-\$C\$360					-\$C\$360					
361	-\$C\$361					-\$C\$361					
362	-\$C\$362					-\$C\$362					
363	-\$C\$363					-\$C\$363					
364	-\$C\$364					-\$C\$364					
365	-\$C\$365					-\$C\$365					
366	-\$C\$366					-\$C\$366					
 											

U	V	W	X	Y	Z	AA	AB	AC	AD	AE	AF
324	=C\$31					=C\$33					
328	=C\$32					=C\$32					
326	=C\$32	=P326/P327*V327	=C\$310	=Y359	Ratio of orig. to proposed size	=V327/E327	=C\$33	=V326/V327*AB327	=C\$310	=AE359	Ratio of orig. to proposed size
327	=C\$32	=D\$322	Scaling of original d	=(V327/E327)*W358			=C\$33	=D\$321	Scaling of original	=(AB327/E327)*AC	
328	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr
329	100	Biomass Preparation	=E329*X327	Biomass	=V326*W362*X326/1000	=Y329/V327*100	100	Biomass Preparation	=E329*AD327	Biomass	=AB326*AC362*AD326/1000
330	200	Pretreatment	=E330*X327	Chemicals			200	Pretreatment	=E330*AD327	Chemicals	
331	210	Recovery & Recycle	=E331*X327	Denaturant	=V327*Y361*Y362*1000	=Y331/V327*100	210	Recovery & Recycle	=E331*AD327	Denaturant	=AB327*AE361*AE362*1000
332	300	Hydrolysis	=E332*X327	Acid	=G332*Z326	=Y332/V327*100	300	Hydrolysis	=E332*AD327	Acid	=G332*AF326
333	400	Fermentation (Unallocated)	=E333*X327	Ammonia	=G333*Z326	=Y333/V327*100	400	Fermentation (Unallocated)	=E333*AD327	Ammonia	=G333*AF326
334	410	Hexose Fermentation	=E334*X327	Nutrients	=G334*Z326	=Y334/V327*100	410	Hexose Fermentation	=E334*AD327	Nutrients	=G334*AF326
335	420	Pentose Fermentation	=E335*X327	Enzymes	=G335*Z326	=Y335/V327*100	420	Pentose Fermentation	=E335*AD327	Enzymes	=G335*AF326
336	500	Distillation & Dehydration	=E336*X327	Yeast	=G336*Z326	=Y336/V327*100	500	Distillation & Dehydration	=E336*AD327	Yeast	=G336*AF326
337	600	By-Product Preparation	=E337*X327	Other Chemicals	=G337*Z326	=Y337/V327*100	600	By-Product Preparation	=E337*AD327	Other Chemicals	=G337*AF326
338	610	Stillage Evaporation	=E338*X327	RAW MATERIALS TOT	=SUM(Y329:Y337)	=Y338/V327*100	610	Stillage Evaporation	=E338*AD327	RAW MATERIALS TOT	=SUM(AE329:AE337)
339	700	Product Storage & Denature	=E339*X327	Utilities			700	Product Storage & Denature	=E339*AD327	Utilities	
340	800	Utilities & General	=E340*X327	Electricity/ Energy	=G340*Z326	=Y340/V327*100	800	Utilities & General	=E340*AD327	Electricity/ Energy	=G340*AF326
341	810	Boiler	=E341*X327	Water	=G341*Z326	=Y341/V327*100	810	Boiler	=E341*AD327	Water	=G341*AF326
342	820	Non-Boiler Utilities	=E342*X327	By-products	=G342*Z326	=Y342/V327*100	820	Non-Boiler Utilities	=E342*AD327	By-products	=G342*AF326
343	830	Environmental	=E343*X327	VARIABLE COST TOT	=SUM(Y338:Y342)	=Y343/V327*100	830	Environmental	=E343*AD327	VARIABLE COST TOT	=SUM(AE338:AE342)
344	840	Miscellaneous & Control	=E344*X327	GEN & ADMIN	=1590*(V327/25)*W363	=Y344/V327*100	840	Miscellaneous & Control	=E344*AD327	GEN & ADMIN	=1590*(AB327/25)*AC363
345	900	Enzyme Production	=E345*X327	Operators	=G346*Z326*W363	=Y346/V327*100	900	Enzyme Production	=E345*AD327	Operators	=G346*AF326*AC363
346											
347	1000	Total Fixed Capital	=SUM(W328:W346)	Laborers	=G347*(Z326)*W363	=Y347/V327*100	1000	Total Fixed Capital	=SUM(AC328:AC346)	Laborers	=G347*(AF326)*AC363
348				Technicians	=G348*(Z326)*W363	=Y348/V327*100				Technicians	=G348*(AF326)*AC363
349	1010	Contingency	=W347*W359	Maintenance	=G349*(Z326)*W363	=Y349/V327*100	1010	Contingency	=AC347*AC359	Maintenance	=G349*(AF326)*AC363
350	1020	Startup	=W347*W360	Fringe Benefits	=Y363*SUM(Y346:Y349)	=Y350/V327*100	1020	Startup	=AC347*AC360	Fringe Benefits	=AE363*SUM(AE346:AE349)
351	1030	Working Capital	=W347*W361	TOTAL LABOR	=SUM(Y346:Y350)	=Y351/V327*100	1030	Working Capital	=AC347*AC361	TOTAL LABOR	=SUM(AE346:AE350)
352				Property Tax & Insur.	=W364*W353*1000	=Y352/V327*100				Property Tax & Insur.	=AC364*AC353*1000
353		TOTAL CAPITAL	=SUM(W347:W352)	TOTAL CASH	=Y343+Y344+Y351+Y352	=Y353/V327*100		TOTAL CAPITAL	=SUM(AC347:AC352)	TOTAL CASH	=AE343+AE344+AE351+AE352
354				Depreciation	=SLN((W353*1000)/(\$D\$318))	=Y354/V327*100				Depreciation	=SLN((AC353*1000)/(\$D\$318*1000*AC353)/\$D\$317)
355				Interest	=W353*1000*\$D\$319	=Y355/V327*100				Interest	=AC353*1000*\$D\$319
356											
357				TOTAL PRODUCTION	=Y353+Y354+Y355	=Y357/V327*100				TOTAL PRODUCTION	=AE353+AE354+AE355
358		Power Law Scaling Factor	=D\$303	=C\$311	=D\$311	=Y338+Y340+Y34		Power Law Scaling Factor	=D\$303	=C\$311	=D\$311
359		Contingency	=D\$304	=C\$312	=D\$312	=Y338+Y340+Y34		Contingency	=D\$304	=C\$312	=D\$312
360		Start-up factor	=D\$305	=C\$313	=D\$313			Start-up factor	=D\$305	=C\$313	=D\$313
361		Working Capital	=D\$306	Denaturant Cost, \$/gal	=D\$314	=Z338+Z340+Z34		Working Capital	=D\$306	Denaturant Cost, \$/g	=D\$314
362		Operating Days per Year	=D\$307	Denaturant Use	=D\$315			Operating Days per Year	=D\$307	Denaturant Use	=D\$315
363		Personnel Scaling Factor	=D\$308	Fringe Benefits	=D\$316			Personnel Scaling Factor	=D\$308	Fringe Benefits	=D\$316
364		Property Tax & Insurance	=D\$309	=C\$317	=D\$317			Property Tax & Insurance	=D\$309	=C\$317	=D\$317

	AG	AH	AI	AJ	AK	AL	AM	AN	AO	AP	AQ	AR
326	=\$C\$32C	=AB326/AB327*AH327	=\$C\$310	=AK360	Ratio of orig. to proposed size-	=AH327/E327	=\$C\$32	=AH326/AH327*AN327	=\$C\$310	=AQ360	Ratio of orig. to proposed size-	=AN327/E327
327	=\$C\$32	=\$D\$322			Scaling of original data	=(AH327/E327)*AI358	=\$C\$32	=\$D\$321	Scaling of original d	=(AN327/E327)*AO35		
328	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
329	100	Biomass Preparation	=\$E329*AL327	Biomass	=AH326*AI362*AJ326/1000	=AK329/(AH327*1000)	100	Biomass Preparation	=\$E329*AP327	Biomass	=AN326*AO362*AP326/1000	=AQ329/(AN327*1000)
330	200	Pretreatment	=\$E330*AL327	Chemicals			200	Pretreatment	=\$E330*AP327	Chemicals		
331	210	Recovery & Recycle	=\$E331*AL327	Denaturant	=AH327*AK361*AK362*1000	=AK331/(AH327*1000)	210	Recovery & Recycle	=\$E331*AP327	Denaturant	=AN327*AO361*AO362*1000	=AQ331/(AN327*1000)
332	300	Hydrolysis	=\$E332*AL327	Acid	=\$G332*AL326	=AK332/(AH327*1000)	300	Hydrolysis	=\$E332*AP327	Acid	=\$G332*AR326	=AQ332/(AN327*1000)
333	400	Fermentation (Unallocated)	=\$E333*AL327	Ammonia	=\$G333*AL326	=AK333/(AH327*1000)	400	Fermentation (Unallocated)	=\$E333*AP327	Ammonia	=\$G333*AR326	=AQ333/(AN327*1000)
334	410	Hexose Fermentation	=\$E334*AL327	Nutrients	=\$G334*AL326	=AK334/(AH327*1000)	410	Hexose Fermentation	=\$E334*AP327	Nutrients	=\$G334*AR326	=AQ334/(AN327*1000)
335	420	Pentose Fermentation	=\$E335*AL327	Enzymes	=\$G335*AL326	=AK335/(AH327*1000)	420	Pentose Fermentation	=\$E335*AP327	Enzymes	=\$G335*AR326	=AQ335/(AN327*1000)
336	500	Distillation & Dehydration	=\$E336*AL327	Yeast	=\$G336*AL326	=AK336/(AH327*1000)	500	Distillation & Dehydration	=\$E336*AP327	Yeast	=\$G336*AR326	=AQ336/(AN327*1000)
337	600	By-Product Preparation	=\$E337*AL327	Other Chemicals	=\$G337*AL326	=AK337/(AH327*1000)	600	By-Product Preparation	=\$E337*AP327	Other Chemicals	=\$G337*AR326	=AQ337/(AN327*1000)
338	610	Stillage Evaporation	=\$E338*AL327	RAW MATERIALS TOT	=SUM(AK329-AK337)	=AK338/(AH327*1000)	610	Stillage Evaporation	=\$E338*AP327	RAW MATERIALS TOT	=SUM(AQ329-AQ337)	=AQ338/(AN327*1000)
339	700	Product Storage & Denatur	=\$E339*AL327	Utilities			700	Product Storage & Denatur	=\$E339*AP327	Utilities		
340	800	Utilities & General	=\$E340*AL327	Electricity/ Energy	=\$G340*AL326	=AK340/(AH327*1000)	800	Utilities & General	=\$E340*AP327	Electricity/ Energy	=\$G340*AR326	=AQ340/(AN327*1000)
341	810	Boiler	=\$E341*AL327	Water	=\$G341*AL326	=AK341/(AH327*1000)	810	Boiler	=\$E341*AP327	Water	=\$G341*AR326	=AQ341/(AN327*1000)
342	820	Non-Boiler Utilities	=\$E342*AL327	By-products	=\$G342*AL326	=AK342/(AH327*1000)	820	Non-Boiler Utilities	=\$E342*AP327	By-products	=\$G342*AR326	=AQ342/(AN327*1000)
343	830	Environmental	=\$E343*AL327	VARIABLE COST TOT	=SUM(AK338-AK342)	=AK343/(AH327*1000)	830	Environmental	=\$E343*AP327	VARIABLE COST TOT	=SUM(AQ338-AQ342)	=AQ343/(AN327*1000)
344	840	Miscellaneous & Control	=\$E344*AL327	GEN & ADMIN	=1590*(AH327/25)*AI363	=AK344/(AH327*1000)	840	Miscellaneous & Control	=\$E344*AP327	GEN & ADMIN	=1590*(AN327/25)*AO363	=AQ344/(AN327*1000)
345	900	Enzyme Production	=\$E345*AL327	Operators	=\$G346*AL326*AI363	=AK346/(AH327*1000)	900	Enzyme Production	=\$E345*AP327	Operators	=\$G346*AR326*AO363	=AQ346/(AN327*1000)
346												
347	1000	Total Fixed Capital	=SUM(AI326-AI3	Laborers	=\$G347*(AL326)*AI363	=AK347/(AH327*1000)	1000	Total Fixed Capital	=SUM(AQ328-AO3	Laborers	=\$G347*(AR326)*AO363	=AQ347/(AN327*1000)
348				Technicians	=\$G348*(AL326)*AI363	=AK348/(AH327*1000)				Technicians	=\$G348*(AR326)*AO363	=AQ348/(AN327*1000)
349	1010	Contingency	=AI347*AI359	Maintenance	=\$G349*(AL326)*AI363	=AK349/(AH327*1000)	1010	Contingency	=AO347*AO359	Maintenance	=\$G349*(AR326)*AO363	=AQ349/(AN327*1000)
350	1020	Startup	=AI347*AI360	Fringe Benefits	=AK363*SUM(AK346-AK349)	=AK350/(AH327*1000)	1020	Startup	=AO347*AO360	Fringe Benefits	=AO363*SUM(AQ346-AQ349)	=AQ350/(AN327*1000)
351	1030	Working Capital	=AI347*AI361	TOTAL LABOR	=SUM(AK346-AK350)	=AK351/(AH327*1000)	1030	Working Capital	=AO347*AO361	TOTAL LABOR	=SUM(AQ346-AQ350)	=AQ351/(AN327*1000)
352				Property Tax & Insur.	=AI364*AI353*1000	=AK352/(AH327*1000)				Property Tax & Insur.	=AO364*AO353*1000	=AQ352/(AN327*1000)
353		TOTAL CAPITAL	=SUM(AI347-AI3	TOTAL CASH	=AK343+AK344+AK351+AK352	=AK353/(AH327*1000)		TOTAL CAPITAL	=SUM(AQ347-AO3	TOTAL CASH	=AQ343+AQ344+AQ351+AQ3	=AQ353/(AN327*1000)
354				Depreciation	=SLN((AI353*1000),(\$D\$318*100	=AK354/(AH327*1000)				Depreciation	=SLN((AO353*1000),(\$D\$318	=AQ354/(AN327*1000)
355				Interest	=AI353*1000*\$D\$319	=AK355/(AH327*1000)				Interest	=AO353*1000*\$D\$319	=AQ355/(AN327*1000)
356												
357				TOTAL PRODUCTION	=AK353+AK354+AK355	=AK357/(AH327*1000)				TOTAL PRODUCTION	=AQ353+AQ354+AQ355	=AQ357/(AN327*1000)
358		Power Law Scaling Factor	=\$D\$303		=\$C\$311	=\$D\$311		Power Law Scaling Factor	=\$D\$303		=\$C\$311	=\$D\$311
359		Contingency	=\$D\$304		=\$C\$312	=\$D\$312		Contingency	=\$D\$304		=\$C\$312	=\$D\$312
360		Start-up factor	=\$D\$305		=\$C\$313	=\$D\$313		Start-up factor	=\$D\$305		=\$C\$313	=\$D\$313
361		Working Capital	=\$D\$306		Denaturant Cost, \$/gal	=\$D\$314		Working Capital	=\$D\$306		Denaturant Cost, \$/gal	=\$D\$314
362		Operating Days per Year	=\$D\$307		Denaturant Use	=\$D\$315		Operating Days per Year	=\$D\$307		Denaturant Use	=\$D\$315
363		Personnel Scaling Factor	=\$D\$308		Fringe Benefits	=\$D\$316		Personnel Scaling Factor	=\$D\$308		Fringe Benefits	=\$D\$316
364		Property Tax & Insurance	=\$D\$309			=\$D\$317		Property Tax & Insurance	=\$D\$309			=\$D\$317

	AT	AU	AV	AW	AX	AY
325	COSTS AS PERCENTAGE OF TOTAL					
326	NREL SSF ESTIMATED BASE COSTS					
327	Ethanol Production (MM gal/yr)		57.91	Biomass Cost/ton-	\$50.00	
328	AREA	CAPITAL COSTS	% of capital cost	PRODUCTION COSTS	Thous \$/Yr	% of \$/gallon cost
329	100	Biomass Preparation	4.4%	Biomass	1	54.0%
330	200	Pretreatment	14.1%	Chemicals	0	0.0%
331	210	Recycle & Recovery	0.0%	Denaturant	2200	3.8%
332	300	Hydrolysis	0.0%	Acid	0	0.0%
333	400	Fermentation	0.0%	Ammonia	0	0.0%
334	410	Hexose Fermentation	13.8%	Nutrients	0	0.0%
335	420	Pentose Fermentation	3.9%	Enzymes	0	0.0%
336	500	Distillation & Dehydration	2.4%	Yeast	0	0.0%
337	600	By-Product Preparation	0.0%	Other Chemicals	7740	13.3%
338	610	Stillage Evaporation	0.0%	RAW MATERIALS T	41290	71.1%
339	700	Product Storage & Denature	1.9%	Utilities	0	0.0%
340	800	Utilities & General	0.0%	Electricity/ Energy	-3220	-5.5%
341	810	Boiler	12.3%	Water	120	0.2%
342	820	Non-Boiler Utilities	20.6%	By-products	400	0.7%
343	830	Environmental	2.5%	VARIABLE COST T	38590	66.4%
344	840	Miscellaneous & Control	3.9%	GEN & ADMIN	3500	6.0%
345	900	Enzyme Production	1.7%			
346				Operators	3237	5.6%
347		Total Installed Equipment	81.6%	Laborers	2130	3.7%
348				Technicians	447	0.8%
349		Fixed Capital	81.6%	Maintenance	1704	2.9%
350	0.1	Miscellaneous	8.2%	Fringe Benefits	1880	3.2%
351	0.05	Start-up Costs	4.1%	TOTAL LABOR	9398	16.2%
352	0.075	Working capital	6.1%	Property Tax & Insur	2198	3.8%
353				TOTAL CASH	53685	92.4%
354		TOTAL CAPITAL	100.0%	Depreciation	4395	7.6%
355				Interest	0	0.0%
356						
357				TOTAL PRODUCTION	58080	100.0%
358						

Page 1

Page 3

	I	J	K	L	M	N
366	=\$C366					
367	=\$D367/D1	=\$C\$320		=M399	Ratio of orig. to prop	=I368/\$D368
368	=\$D\$322	=\$C\$321		=(I368/\$D368)*K399		
369	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	1000\$/Yr	\$/gal
370	100	Biomass Preparation	=\$E370*L368	Biomass	=I367*K403*L367/1	=M370/(I368*1000)
371	200	Pretreatment	=\$E371*L368	Chemicals		
372	210	Recovery & Recycle	=\$E372*L368	Denaturant	=I368*M402*M403	=M372/(I368*1000)
373	300	Hydrolysis	=\$E373*L368	Acid	=SG373*N367	=M373/(I368*1000)
374	400	Fermentation (Unallocated)	=\$E374*L368	Ammonia	=SG374*N367	=M374/(I368*1000)
375	410	Hexose Fermentation	=\$E375*L368	Nutrients	=SG375*N367	=M375/(I368*1000)
376	420	Pentose Fermentation	=\$E376*L368	Enzymes	=SG376*N367	=M376/(I368*1000)
377	500	Distillation & Dehydration	=\$E377*L368	Yeast	=SG377*N367	=M377/(I368*1000)
378	600	By-Product Preparation	=\$E378*L368	Other Chemicals	=SG378*N367	=M378/(I368*1000)
379	610	Stillage Evaporation	=\$E379*L368	RAW MATERIALS TOTAL	=SUM(M370:M378)	=M379/(I368*1000)
380	700	Product Storage & Denature	=\$E380*L368	Utilities		
381	800	Utilities & General	=\$E381*L368	Electricity/ Energy	=SG381*N367	=M381/(I368*1000)
382	810	Boiler	=\$E382*L368	Water	=SG382*N367	=M382/(I368*1000)
383	820	Non-Boiler Utilities	=\$E383*L368	By-products	=SG383*N367	=M383/(I368*1000)
384	830	Environmental	=\$E384*L368	VARIABLE COST TOTAL	=SUM(M379:M383)	=M384/(I368*1000)
385	840	Miscellaneous & Control	=\$E385*L368	GEN & ADMIN	=1590*(I368/25)*K4	=M385/(I368*1000)
386	900	Enzyme Production	=\$E386*L368			
387				Operators	=SG387*N367*K40	=M387/(I368*1000)
388	1000	Total Fixed Capital	=SUM(K369:K387)	Laborers	=SG388*(N367)*K4	=M388/(I368*1000)
389				Technicians	=SG389*(N367)*K4	=M389/(I368*1000)
390	1010	Contingency	=K388*K400	Maintenance	=SG390*(N367)*K4	=M390/(I368*1000)
391	1020	Startup	=K388*K401	Fringe Benefits	=M404*SUM(M387)	=M391/(I368*1000)
392	1030	Working Capital	=K388*K402	TOTAL LABOR	=SUM(M387:M391)	=M392/(I368*1000)
393				Property Tax & Insur.	=K405*K394*1000	=M393/(I368*1000)
394		TOTAL CAPITAL	=SUM(K388:K393)	TOTAL CASH	=M384+M385+M39	=M394/(I368*1000)
395				Depreciation	=SLN((K394*1000))	=M395/(I368*1000)
396				Interest	=K394*1000*\$D\$31	=M396/(I368*1000)
397						
398				TOTAL PRODUCTION	=M394+M395+M39	=M398/(I368*1000)
399		Power Law Scaling Factor	=\$D\$303	=\$C\$311	=\$D\$311	
400		Contingency	=\$D\$304	=\$C\$312	=\$D\$312	
401		Start-up factor	=\$D\$305	=\$C\$313	=\$D\$313	
402		Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
403		Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
404		Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
405		Property Tax & Insurance	=\$D\$309	=\$C\$317	=\$D\$317	
406	=\$C\$311					
407	=\$C407			Ratio of orig. to proposed s	=K409/\$D409	
408	=\$C\$320	=D408/D409*K409		=\$C\$310	=M440	
409	=\$C\$321	=\$D\$322		Scaling of original data	=(K409/\$D409)*K44	
410	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
411	100	Biomass Preparation	=\$E411*M409	Biomass	=K408*K444*M408	=M411/(K409*1000)
412	200	Pretreatment	=\$E412*M409	Chemicals		
413	210	Recovery & Recycle	=\$E413*M409	Denaturant	=K409*M443*M444	=M413/(K409*1000)
414	300	Hydrolysis	=\$E414*M409	Acid	=SG414*M407	=M414/(K409*1000)
415	400	Fermentation (Unallocated)	=\$E415*M409	Ammonia	=SG415*M407	=M415/(K409*1000)
416	410	Hexose Fermentation	=\$E416*M409	Nutrients	=SG416*M407	=M416/(K409*1000)
417	420	Pentose Fermentation	=\$E417*M409	Enzymes	=SG417*M407	=M417/(K409*1000)
418	500	Distillation & Dehydration	=\$E418*M409	Yeast	=SG418*M407	=M418/(K409*1000)
419	600	By-Product Preparation	=\$E419*M409	Other Chemicals	=SG419*M407	=M419/(K409*1000)
420	610	Stillage Evaporation	=\$E420*M409	RAW MATERIALS TOTAL	=SUM(M411:M419)	=M420/(K409*1000)
421	700	Product Storage & Denature	=\$E421*M409	Utilities		
422	800	Utilities & General	=\$E422*M409	Electricity/ Energy	=SG422*M407	=M422/(K409*1000)
423	810	Boiler	=\$E423*M409	Water	=SG423*M407	=M423/(K409*1000)
424	820	Non-Boiler Utilities	=\$E424*M409	By-products	=SG424*M407	=M424/(K409*1000)
425	830	Environmental	=\$E425*M409	VARIABLE COST TOTAL	=SUM(M420:M424)	=M425/(K409*1000)
426	840	Miscellaneous & Control	=\$E426*M409	GEN & ADMIN	=1590*(K409/25)*K	=M426/(K409*1000)
427	900	Enzyme Production	=\$E427*M409			
428				Operators	=SG428*M407*K44	=M428/(K409*1000)
429	1000	Total Fixed Capital	=SUM(K410:K428)	Laborers	=SG429*(M407)*K4	=M429/(K409*1000)
430				Technicians	=SG430*(M407)*K4	=M430/(K409*1000)
431	1010	Contingency	=K429*K441	Maintenance	=SG431*(M407)*K4	=M431/(K409*1000)
432	1020	Startup	=K429*K442	Fringe Benefits	=M445*SUM(M428)	=M432/(K409*1000)
433	1030	Working Capital	=K429*K443	TOTAL LABOR	=SUM(M428:M432)	=M433/(K409*1000)
434				Property Tax & Insur.	=K446*K435*1000	=M434/(K409*1000)
435		TOTAL CAPITAL	=SUM(K429:K434)	TOTAL CASH	=M425+M426+M43	=M435/(K409*1000)
436				Depreciation	=SLN((K435*1000))	=M436/(K409*1000)
437				Interest	=K435*1000*\$D\$31	=M437/(K409*1000)
438						
439				TOTAL PRODUCTION	=M435+M436+M43	=M439/(K409*1000)
440		Power Law Scaling Factor	=\$D\$303	=\$C\$311	=\$D\$311	
441		Contingency	=\$D\$304	=\$C\$312	=\$D\$312	
442		Start-up factor	=\$D\$305	=\$C\$313	=\$D\$313	
443		Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
444		Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
445		Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
446		Property Tax & Insurance	=\$D\$309	=\$C\$317	=\$D\$317	

	O	P	Q	R	S	T
365	=\$C\$311					
366	=\$C\$366					
367	=\$C\$320	=I367/I368*P368	=\$C\$310	=S399	Ratio of orig. to propos	=P368/\$D368
368	=\$C\$321	=\$D\$321	Scaling of original de	=(P368/\$D368)*Q399		
369	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
370	100	Biomass Preparation	=\$E370*R368	Biomass	=P367*Q403/R367/10	=S370/(P368*1000)
371	200	Pretreatment	=\$E371*R368	Chemicals		
372	210	Recovery & Recycle	=\$E372*R368	Denaturant	=P368*S402*S403*10	=S372/(P368*1000)
373	300	Hydrolysis	=\$E373*R368	Acid	=G373*T367	=S373/(P368*1000)
374	400	Fermentation (Unallocated)	=\$E374*R368	Ammonia	=G374*T367	=S374/(P368*1000)
375	410	Hexose Fermentation	=\$E375*R368	Nutrients	=G375*T367	=S375/(P368*1000)
376	420	Pentose Fermentation	=\$E376*R368	Enzymes	=G376*T367	=S376/(P368*1000)
377	500	Distillation & Dehydration	=\$E377*R368	Yeast	=G377*T367	=S377/(P368*1000)
378	600	By-Product Preparation	=\$E378*R368	Other Chemicals	=G378*T367	=S378/(P368*1000)
379	610	Stillage Evaporation	=\$E379*R368	RAW MATERIALS TOTAL	=SUM(S370:S378)	=S379/(P368*1000)
380	700	Product Storage & Denature	=\$E380*R368	Utilities		
381	800	Utilities & General	=\$E381*R368	Electricity/ Energy	=G381*T367	=S381/(P368*1000)
382	810	Boiler	=\$E382*R368	Water	=G382*T367	=S382/(P368*1000)
383	820	Non-Boiler Utilities	=\$E383*R368	By-products	=G383*T367	=S383/(P368*1000)
384	830	Environmental	=\$E384*R368	VARIABLE COST TOTAL	=SUM(S379:S383)	=S384/(P368*1000)
385	840	Miscellaneous & Control	=\$E385*R368	GEN & ADMIN	=1590*(P368/25)*Q40	=S385/(P368*1000)
386	900	Enzyme Production	=\$E386*R368			
387				Operators	=G387*T367*Q404	=S387/(P368*1000)
388	1000	Total Fixed Capital	=SUM(Q369:Q387)	Laborers	=G388*(T367)*Q404	=S388/(P368*1000)
389				Technicians	=G389*(T367)*Q404	=S389/(P368*1000)
390	1010	Contingency	=Q388*Q400	Maintenance	=G390*(T367)*Q404	=S390/(P368*1000)
391	1020	Startup	=Q388*Q401	Fringe Benefits	=S404*SUM(S387:S39	=S391/(P368*1000)
392	1030	Working Capital	=Q388*Q402	TOTAL LABOR	=SUM(S387:S391)	=S392/(P368*1000)
393				Property Tax & Insur.	=Q405*Q394*1000	=S393/(P368*1000)
394		TOTAL CAPITAL	=SUM(Q388:Q393)	TOTAL CASH	=S384+S385+S392+S	=S394/(P368*1000)
395				Depreciation	=SLN((Q394*1000), (\$	=S395/(P368*1000)
396				Return on Investment	=Q394*1000*\$D\$319	=S396/(P368*1000)
397						
398				TOTAL PRODUCTION	=S394+S395+S396	=S398/(P368*1000)
399		Power Law Scaling Factor	=\$D\$303	=\$C\$311	=\$D\$311	
400		Contingency	=\$D\$304	=\$C\$312	=\$D\$312	
401		Start-up factor	=\$D\$305	=\$C\$313	=\$D\$313	
402		Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
403		Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
404		Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
405		Property Tax & Insurance	=\$D\$309	=\$C\$317	=\$D\$317	
406	=\$C\$311					
407	=\$C\$407					
408	=\$C\$320	=K408/K409*P409	=\$C\$310	=S440	Ratio of orig. to propos	=P409/\$D409
409	=\$C\$321	=\$D\$321	Scaling of original de	=(P409/\$D409)*Q440		
410	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
411	100	Biomass Preparation	=\$E411*R409	Biomass	=P408*Q444/R408/10	=S411/(P409*1000)
412	200	Pretreatment	=\$E412*R409	Chemicals		
413	210	Recovery & Recycle	=\$E413*R409	Denaturant	=P409*S443*S444*10	=S413/(P409*1000)
414	300	Hydrolysis	=\$E414*R409	Acid	=G414*T408	=S414/(P409*1000)
415	400	Fermentation (Unallocated)	=\$E415*R409	Ammonia	=G415*T408	=S415/(P409*1000)
416	410	Hexose Fermentation	=\$E416*R409	Nutrients	=G416*T408	=S416/(P409*1000)
417	420	Pentose Fermentation	=\$E417*R409	Enzymes	=G417*T408	=S417/(P409*1000)
418	500	Distillation & Dehydration	=\$E418*R409	Yeast	=G418*T408	=S418/(P409*1000)
419	600	By-Product Preparation	=\$E419*R409	Other Chemicals	=G419*T408	=S419/(P409*1000)
420	610	Stillage Evaporation	=\$E420*R409	RAW MATERIALS TOTAL	=SUM(S411:S419)	=S420/(P409*1000)
421	700	Product Storage & Denature	=\$E421*R409	Utilities		
422	800	Utilities & General	=\$E422*R409	Electricity/ Energy	=G422*T408	=S422/(P409*1000)
423	810	Boiler	=\$E423*R409	Water	=G423*T408	=S423/(P409*1000)
424	820	Non-Boiler Utilities	=\$E424*R409	By-products	=G424*T408	=S424/(P409*1000)
425	830	Environmental	=\$E425*R409	VARIABLE COST TOTAL	=SUM(S420:S424)	=S425/(P409*1000)
426	840	Miscellaneous & Control	=\$E426*R409	GEN & ADMIN	=1590*(P409/25)*Q44	=S426/(P409*1000)
427	900	Enzyme Production	=\$E427*R409			
428				Operators	=G428*T408*Q445	=S428/(P409*1000)
429	1000	Total Fixed Capital	=SUM(Q410:Q428)	Laborers	=G429*(T408)*Q445	=S429/(P409*1000)
430				Technicians	=G430*(T408)*Q445	=S430/(P409*1000)
431	1010	Contingency	=Q429*Q441	Maintenance	=G431*(T408)*Q445	=S431/(P409*1000)
432	1020	Startup	=Q429*Q442	Fringe Benefits	=S445*SUM(S428:S43	=S432/(P409*1000)
433	1030	Working Capital	=Q429*Q443	TOTAL LABOR	=SUM(S428:S432)	=S433/(P409*1000)
434				Property Tax & Insur.	=Q446*Q435*1000	=S434/(P409*1000)
435		TOTAL CAPITAL	=SUM(Q429:Q434)	TOTAL CASH	=S425+S426+S433+S	=S435/(P409*1000)
436				Depreciation	=SLN((Q435*1000), (\$	=S436/(P409*1000)
437				Interest	=Q435*1000*\$D\$319	=S437/(P409*1000)
438						
439				TOTAL PRODUCTION	=S435+S436+S437	=S439/(P409*1000)
440		Power Law Scaling Factor	=\$D\$303	=\$C\$311	=\$D\$311	
441		Contingency	=\$D\$304	=\$C\$312	=\$D\$312	
442		Start-up factor	=\$D\$305	=\$C\$313	=\$D\$313	
443		Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
444		Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
445		Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
446		Property Tax & Insurance	=\$D\$309	=\$C\$317	=\$D\$317	

	U	V	W	X	Y	Z
365	=SC\$312					
366	=SC\$366					
367	=SC\$320	=P367/P368*V368	=SC\$310	=Y400	Ratio of orig. to propose	=V368/\$D368
368	=SC\$321	=D\$322	Scaling of original data	=(V368/\$D368)*W399		
369	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
370	100	Biomass Preparation	=SE370*X368	Biomass	=V367*W403*X367/100	=Y370/(V368*100)
371	200	Pretreatment	=SE371*X368	Chemicals		
372	210	Recovery & Recycle	=SE372*X368	Denaturant	=V368*Y402*Y403*100	=Y372/(V368*100)
373	300	Hydrolysis	=SE373*X368	Acid	=G373*Z367	=Y373/(V368*100)
374	400	Fermentation (Unallocated)	=SE374*X368	Ammonia	=G374*Z367	=Y374/(V368*100)
375	410	Hexose Fermentation	=SE375*X368	Nutrients	=G375*Z367	=Y375/(V368*100)
376	420	Pentose Fermentation	=SE376*X368	Enzymes	=G376*Z367	=Y376/(V368*100)
377	500	Distillation & Dehydration	=SE377*X368	Yeast	=G377*Z367	=Y377/(V368*100)
378	600	By-Product Preparation	=SE378*X368	Other Chemicals	=G378*Z367	=Y378/(V368*100)
379	610	Stillage Evaporation	=SE379*X368	RAW MATERIALS TOTAL	=SUM(Y370:Y378)	=Y379/(V368*100)
380	700	Product Storage & Denature	=SE380*X368	Utilities		
381	800	Utilities & General	=SE381*X368	Electricity/ Energy	=G381*Z367	=Y381/(V368*100)
382	810	Boiler	=SE382*X368	Water	=G382*Z367	=Y382/(V368*100)
383	820	Non-Boiler Utilities	=SE383*X368	By-products	=G383*Z367	=Y383/(V368*100)
384	830	Environmental	=SE384*X368	VARIABLE COST TOTAL	=SUM(Y379:Y383)	=Y384/(V368*100)
385	840	Miscellaneous & Control	=SE385*X368	GEN & ADMIN	=1590*(V368/25)*W404	=Y385/(V368*100)
386	900	Enzyme Production	=SE386*X368			
387				Operators	=G387*Z367*W404	=Y387/(V368*100)
388	1000	Total Fixed Capital	=SUM(W369:W387)	Laborers	=G388*(Z367)*W404	=Y388/(V368*100)
389				Technicians	=G389*(Z367)*W404	=Y389/(V368*100)
390	1010	Contingency	=W388*W400	Maintenance	=G390*(Z367)*W404	=Y390/(V368*100)
391	1020	Startup	=W388*W401	Fringe Benefits	=Y404*SUM(Y387:Y390)	=Y391/(V368*100)
392	1030	Working Capital	=W388*W402	TOTAL LABOR	=SUM(Y387:Y391)	=Y392/(V368*100)
393				Property Tax & Insur.	=W405*W394*1000	=Y393/(V368*100)
394		TOTAL CAPITAL	=SUM(W388:W393)	TOTAL CASH	=Y384+Y385+Y392+Y3	=Y394/(V368*100)
395				Depreciation	=SLN((W394*1000),(\$D	=Y395/(V368*100)
396				Return on Investment	=W394*1000*\$D\$319	=Y396/(V368*100)
397						
398				TOTAL PRODUCTION	=Y394+Y395+Y396	=Y398/(V368*100)
399		Power Law Scaling Factor	=D\$303	=SC\$311	=D\$311	
400		Contingency	=D\$304	=SC\$312	=D\$312	
401		Start-up factor	=D\$305	=SC\$313	=D\$313	
402		Working Capital	=D\$306	Denaturant Cost, \$/gal	=D\$314	
403		Operating Days per Year	=D\$307	Denaturant Use	=D\$315	
404		Personnel Scaling Factor	=D\$308	Fringe Benefits	=D\$316	
405		Property Tax & Insurance	=D\$309	=SC\$317	=D\$317	
406	=SC\$312					
407	=SC\$407					
408	=SC\$320	=P408/P409*V409	=SC\$310	=Y441	Ratio of orig. to propose	=V409/\$D409
409	=SC\$321	=D\$322	Scaling of original data	=(V409/\$D409)*W440		
410	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
411	100	Biomass Preparation	=SE411*X409	Biomass	=V408*W444*X408/100	=Y411/(V409*100)
412	200	Pretreatment	=SE412*X409	Chemicals		
413	210	Recovery & Recycle	=SE413*X409	Denaturant	=V409*Y443*Y444*100	=Y413/(V409*100)
414	300	Hydrolysis	=SE414*X409	Acid	=G414*Z408	=Y414/(V409*100)
415	400	Fermentation (Unallocated)	=SE415*X409	Ammonia	=G415*Z408	=Y415/(V409*100)
416	410	Hexose Fermentation	=SE416*X409	Nutrients	=G416*Z408	=Y416/(V409*100)
417	420	Pentose Fermentation	=SE417*X409	Enzymes	=G417*Z408	=Y417/(V409*100)
418	500	Distillation & Dehydration	=SE418*X409	Yeast	=G418*Z408	=Y418/(V409*100)
419	600	By-Product Preparation	=SE419*X409	Other Chemicals	=G419*Z408	=Y419/(V409*100)
420	610	Stillage Evaporation	=SE420*X409	RAW MATERIALS TOTAL	=SUM(Y411:Y419)	=Y420/(V409*100)
421	700	Product Storage & Denature	=SE421*X409	Utilities		
422	800	Utilities & General	=SE422*X409	Electricity/ Energy	=G422*Z408	=Y422/(V409*100)
423	810	Boiler	=SE423*X409	Water	=G423*Z408	=Y423/(V409*100)
424	820	Non-Boiler Utilities	=SE424*X409	By-products	=G424*Z408	=Y424/(V409*100)
425	830	Environmental	=SE425*X409	VARIABLE COST TOTAL	=SUM(Y420:Y424)	=Y425/(V409*100)
426	840	Miscellaneous & Control	=SE426*X409	GEN & ADMIN	=1590*(V409/25)*W445	=Y426/(V409*100)
427	900	Enzyme Production	=SE427*X409			
428				Operators	=G428*Z408*W445	=Y428/(V409*100)
429	1000	Total Fixed Capital	=SUM(W410:W428)	Laborers	=G429*(Z408)*W445	=Y429/(V409*100)
430				Technicians	=G430*(Z408)*W445	=Y430/(V409*100)
431	1010	Contingency	=W429*W441	Maintenance	=G431*(Z408)*W445	=Y431/(V409*100)
432	1020	Startup	=W429*W442	Fringe Benefits	=Y445*SUM(Y428:Y431)	=Y432/(V409*100)
433	1030	Working Capital	=W429*W443	TOTAL LABOR	=SUM(Y428:Y432)	=Y433/(V409*100)
434				Property Tax & Insur.	=W446*W435*1000	=Y434/(V409*100)
435		TOTAL CAPITAL	=SUM(W429:W434)	TOTAL CASH	=Y425+Y426+Y433+Y4	=Y435/(V409*100)
436				Depreciation	=SLN((W435*1000),(\$D	=Y436/(V409*100)
437				Interest	=W435*1000*\$D\$319	=Y437/(V409*100)
438						
439				TOTAL PRODUCTION	=Y435+Y436+Y437	=Y439/(V409*100)
440		Power Law Scaling Factor	=D\$303	=SC\$311	=D\$311	
441		Contingency	=D\$304	=SC\$312	=D\$312	
442		Start-up factor	=D\$305	=SC\$313	=D\$313	
443		Working Capital	=D\$306	Denaturant Cost, \$/gal	=D\$314	
444		Operating Days per Year	=D\$307	Denaturant Use	=D\$315	
445		Personnel Scaling Factor	=D\$308	Fringe Benefits	=D\$316	
446		Property Tax & Insurance	=D\$309	=SC\$317	=D\$317	
447	=SC\$312					

	AA	AB	AC	AD	AE	AF
366	-\$C366					
367	-\$C\$32	=V367/V368*AB368	-\$C\$310	=AE400		Ratio of orig. to proposed s =AB368/\$D368
368	-\$C\$32	-\$D\$321	Scaling of original dat	=(AB368/\$D368)*AC399		
369	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
370	100	Biomass Preparation	=\$E370*AD368	Biomass	=AB367*AC403*AD367/10	=AE370/(AB368*100)
371	200	Pretreatment	=\$E371*AD368	Chemicals		
372	210	Recovery & Recycle	=\$E372*AD368	Denaturant	=AB368*AE402*AE403*10	=AE372/(AB368*100)
373	300	Hydrolysis	=\$E373*AD368	Acid	=\$G373*AF367	=AE373/(AB368*100)
374	400	Fermentation (Unallocated)	=\$E374*AD368	Ammonia	=\$G374*AF367	=AE374/(AB368*100)
375	410	Hexose Fermentation	=\$E375*AD368	Nutrients	=\$G375*AF367	=AE375/(AB368*100)
376	420	Pentose Fermentation	=\$E376*AD368	Enzymes	=\$G376*AF367	=AE376/(AB368*100)
377	500	Distillation & Dehydration	=\$E377*AD368	Yeast	=\$G377*AF367	=AE377/(AB368*100)
378	600	By-Product Preparation	=\$E378*AD368	Other Chemicals	=\$G378*AF367	=AE378/(AB368*100)
379	610	Stillage Evaporation	=\$E379*AD368	RAW MATERIALS TOTAL	=SUM(AE370:AE378)	=AE379/(AB368*100)
380	700	Product Storage & Denature	=\$E380*AD368	Utilities		
381	800	Utilities & General	=\$E381*AD368	Electricity/ Energy	=\$G381*AF367	=AE381/(AB368*100)
382	810	Boiler	=\$E382*AD368	Water	=\$G382*AF367	=AE382/(AB368*100)
383	820	Non-Boiler Utilities	=\$E383*AD368	By-products	=\$G383*AF367	=AE383/(AB368*100)
384	830	Environmental	=\$E384*AD368	VARIABLE COST TOTAL	=SUM(AE379:AE383)	=AE384/(AB368*100)
385	840	Miscellaneous & Control	=\$E385*AD368	GEN & ADMIN	=1590*(AB368/25)*AC404	=AE385/(AB368*100)
386	900	Enzyme Production	=\$E386*AD368			
387				Operators	=\$G387*AF367*AC404	=AE387/(AB368*100)
388	1000	Total Fixed Capital	=SUM(AC369:AC387)	Laborers	=\$G388*(AF367)*AC404	=AE388/(AB368*100)
389				Technicians	=\$G389*(AF367)*AC404	=AE389/(AB368*100)
390	1010	Contingency	=AC388*AC400	Maintenance	=\$G390*(AF367)*AC404	=AE390/(AB368*100)
391	1020	Startup	=AC388*AC401	Fringe Benefits	=AE404*SUM(AE387:AE391)	=AE391/(AB368*100)
392	1030	Working Capital	=AC388*AC402	TOTAL LABOR	=SUM(AE387:AE391)	=AE392/(AB368*100)
393				Property Tax & Insur.	=AC405*AC394*1000	=AE393/(AB368*100)
394		TOTAL CAPITAL	=SUM(AC388:AC393)	TOTAL CASH	=AE384+AE385+AE392+AE393	=AE394/(AB368*100)
395				Depreciation	=SLN((AC394*1000),(\$D\$319))	=AE395/(AB368*100)
396				Return on Investment	=AC394*1000*\$D\$319	=AE396/(AB368*100)
397						
398				TOTAL PRODUCTION	=AE394+AE395+AE396	=AE398/(AB368*100)
399		Power Law Scaling Factor	=\$D\$303	-\$C\$311	=\$D\$311	
400		Contingency	=\$D\$304	-\$C\$312	=\$D\$312	
401		Start-up factor	=\$D\$305	-\$C\$313	=\$D\$313	
402		Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
403		Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
404		Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
405		Property Tax & Insurance	=\$D\$309	-\$C\$317	=\$D\$317	
406	-\$C\$31					
407	-\$C407					
408	-\$C\$32	=V408/V409*AB409	-\$C\$310	=AE441		Ratio of orig. to proposed s =AB409/\$D409
409	-\$C\$32	-\$D\$321	Scaling of original dat	=(AB409/\$D409)*AC440		
410	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
411	100	Biomass Preparation	=\$E411*AD409	Biomass	=AB408*AC444*AD408/10	=AE411/(AB409*100)
412	200	Pretreatment	=\$E412*AD409	Chemicals		
413	210	Recovery & Recycle	=\$E413*AD409	Denaturant	=AB409*AE443*AE444*10	=AE413/(AB409*100)
414	300	Hydrolysis	=\$E414*AD409	Acid	=\$G414*AF408	=AE414/(AB409*100)
415	400	Fermentation (Unallocated)	=\$E415*AD409	Ammonia	=\$G415*AF408	=AE415/(AB409*100)
416	410	Hexose Fermentation	=\$E416*AD409	Nutrients	=\$G416*AF408	=AE416/(AB409*100)
417	420	Pentose Fermentation	=\$E417*AD409	Enzymes	=\$G417*AF408	=AE417/(AB409*100)
418	500	Distillation & Dehydration	=\$E418*AD409	Yeast	=\$G418*AF408	=AE418/(AB409*100)
419	600	By-Product Preparation	=\$E419*AD409	Other Chemicals	=\$G419*AF408	=AE419/(AB409*100)
420	610	Stillage Evaporation	=\$E420*AD409	RAW MATERIALS TOTAL	=SUM(AE411:AE419)	=AE420/(AB409*100)
421	700	Product Storage & Denature	=\$E421*AD409	Utilities		
422	800	Utilities & General	=\$E422*AD409	Electricity/ Energy	=\$G422*AF408	=AE422/(AB409*100)
423	810	Boiler	=\$E423*AD409	Water	=\$G423*AF408	=AE423/(AB409*100)
424	820	Non-Boiler Utilities	=\$E424*AD409	By-products	=\$G424*AF408	=AE424/(AB409*100)
425	830	Environmental	=\$E425*AD409	VARIABLE COST TOTAL	=SUM(AE420:AE424)	=AE425/(AB409*100)
426	840	Miscellaneous & Control	=\$E426*AD409	GEN & ADMIN	=1590*(AB409/25)*AC445	=AE426/(AB409*100)
427	900	Enzyme Production	=\$E427*AD409			
428				Operators	=\$G428*AF408*AC445	=AE428/(AB409*100)
429	1000	Total Fixed Capital	=SUM(AC410:AC428)	Laborers	=\$G429*(AF408)*AC445	=AE429/(AB409*100)
430				Technicians	=\$G430*(AF408)*AC445	=AE430/(AB409*100)
431	1010	Contingency	=AC429*AC441	Maintenance	=\$G431*(AF408)*AC445	=AE431/(AB409*100)
432	1020	Startup	=AC429*AC442	Fringe Benefits	=AE445*SUM(AE428:AE432)	=AE432/(AB409*100)
433	1030	Working Capital	=AC429*AC443	TOTAL LABOR	=SUM(AE428:AE432)	=AE433/(AB409*100)
434				Property Tax & Insur.	=AC446*AC435*1000	=AE434/(AB409*100)
435		TOTAL CAPITAL	=SUM(AC429:AC434)	TOTAL CASH	=AE425+AE426+AE433+AE434	=AE435/(AB409*100)
436				Depreciation	=SLN((AC435*1000),(\$D\$319))	=AE436/(AB409*100)
437				Interest	=AC435*1000*\$D\$319	=AE437/(AB409*100)
438						
439				TOTAL PRODUCTION	=AE435+AE436+AE437	=AE439/(AB409*100)
440		Power Law Scaling Factor	=\$D\$303	-\$C\$311	=\$D\$311	
441		Contingency	=\$D\$304	-\$C\$312	=\$D\$312	
442		Start-up factor	=\$D\$305	-\$C\$313	=\$D\$313	
443		Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
444		Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
445		Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
446		Property Tax & Insurance	=\$D\$309	-\$C\$317	=\$D\$317	

PAGE 4

	AM	AN	AO	AP	AQ	AR
366	=\$C366					
367	=\$C320	=\$AH367/AH368*AN368	=\$C3310	=\$AQ401	Ratio of orig. to proposed	=\$AN368/\$D368
368	=\$C321	=\$D\$321	Scaling of original data	=(AN368/\$D368)*AO399		
369	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
370	100	Biomass Preparation	=\$E370*AP368	Biomass	=\$AN367*AO403*AP367/10	=\$AQ370/(AN368*1000)
371	200	Pretreatment	=\$E371*AP368	Chemicals		
372	210	Recovery & Recycle	=\$E372*AP368	Denaturant	=\$AN368*AO402*AO403*1	=\$AQ372/(AN368*1000)
373	300	Hydrolysis	=\$E373*AP368	Acid	=\$G373*AR367	=\$AQ373/(AN368*1000)
374	400	Fermentation (Unallocated)	=\$E374*AP368	Ammonia	=\$G374*AR367	=\$AQ374/(AN368*1000)
375	410	Hexose Fermentation	=\$E375*AP368	Nutrients	=\$G375*AR367	=\$AQ375/(AN368*1000)
376	420	Pentose Fermentation	=\$E376*AP368	Enzymes	=\$G376*AR367	=\$AQ376/(AN368*1000)
377	500	Distillation & Dehydration	=\$E377*AP368	Yeast	=\$G377*AR367	=\$AQ377/(AN368*1000)
378	600	By-Product Preparation	=\$E378*AP368	Other Chemicals	=\$G378*AR367	=\$AQ378/(AN368*1000)
379	610	Stillage Evaporation	=\$E379*AP368	RAW MATERIALS TOTAL	=SUM(AQ370:AQ378)	=\$AQ379/(AN368*1000)
380	700	Product Storage & Denature	=\$E380*AP368	Utilities		
381	800	Utilities & General	=\$E381*AP368	Electricity/ Energy	=\$G381*AR367	=\$AQ381/(AN368*1000)
382	810	Boiler	=\$E382*AP368	Water	=\$G382*AR367	=\$AQ382/(AN368*1000)
383	820	Non-Boiler Utilities	=\$E383*AP368	By-products	=\$G383*AR367	=\$AQ383/(AN368*1000)
384	830	Environmental	=\$E384*AP368	VARIABLE COST TOTAL	=SUM(AQ379:AQ383)	=\$AQ384/(AN368*1000)
385	840	Miscellaneous & Control	=\$E385*AP368	GEN & ADMIN	=1590*(AN368/25)*AO404	=\$AQ385/(AN368*1000)
386	900	Enzyme Production	=\$E386*AP368			
387				Operators	=\$G387*AR367*AO404	=\$AQ387/(AN368*1000)
388	1000	Total Fixed Capital	=SUM(AO369:AO387)	Laborers	=\$G388*(AR367)*AO404	=\$AQ388/(AN368*1000)
389				Technicians	=\$G389*(AR367)*AO404	=\$AQ389/(AN368*1000)
390	1010	Contingency	=AO388*AO400	Maintenance	=\$G390*(AR367)*AO404	=\$AQ390/(AN368*1000)
391	1020	Startup	=AO388*AO401	Fringe Benefits	=AQ404*SUM(AQ387:AO404)	=\$AQ391/(AN368*1000)
392	1030	Working Capital	=AO388*AO402	TOTAL LABOR	=SUM(AQ387:AQ391)	=\$AQ392/(AN368*1000)
393				Property Tax & Insur.	=AO405*AO394*1000	=\$AQ393/(AN368*1000)
394		TOTAL CAPITAL	=SUM(AO388:AO393)	TOTAL CASH	=AQ384*AO385*AO392+	=\$AQ394/(AN368*1000)
395				Depreciation	=SLN((AO394*1000),(\$DS	=\$AQ395/(AN368*1000)
396				Return on Investment	=AO394*1000*\$D\$319	=\$AQ396/(AN368*1000)
397						
398				TOTAL PRODUCTION	=AQ394*AO395*AO396	=\$AQ398/(AN368*1000)
399		Power Law Scaling Factor	=\$D\$303	=\$C\$311	=\$D\$311	
400		Contingency	=\$D\$304	=\$C\$312	=\$D\$312	
401		Start-up factor	=\$D\$305	=\$C\$313	=\$D\$313	
402		Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
403		Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
404		Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
405		Property Tax & Insurance	=\$D\$309	=\$C\$317	=\$D\$317	
406	=\$C\$313					
407	=\$C\$407					
408	=\$C\$320	=\$AH408/AH409*AN409	=\$C\$310	=\$AQ442	Ratio of orig. to proposed	=\$AN409/\$D409
409	=\$C\$321	=\$D\$321	Scaling of original data	=(AN409/\$D409)*AO440		
410	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal
411	100	Biomass Preparation	=\$E411*AP409	Biomass	=\$AN408*AO444*AP408/10	=\$AQ411/(AN409*1000)
412	200	Pretreatment	=\$E412*AP409	Chemicals		
413	210	Recovery & Recycle	=\$E413*AP409	Denaturant	=\$AN409*AO443*AO444*1	=\$AQ413/(AN409*1000)
414	300	Hydrolysis	=\$E414*AP409	Acid	=\$G414*AR408	=\$AQ414/(AN409*1000)
415	400	Fermentation (Unallocated)	=\$E415*AP409	Ammonia	=\$G415*AR408	=\$AQ415/(AN409*1000)
416	410	Hexose Fermentation	=\$E416*AP409	Nutrients	=\$G416*AR408	=\$AQ416/(AN409*1000)
417	420	Pentose Fermentation	=\$E417*AP409	Enzymes	=\$G417*AR408	=\$AQ417/(AN409*1000)
418	500	Distillation & Dehydration	=\$E418*AP409	Yeast	=\$G418*AR408	=\$AQ418/(AN409*1000)
419	600	By-Product Preparation	=\$E419*AP409	Other Chemicals	=\$G419*AR408	=\$AQ419/(AN409*1000)
420	610	Stillage Evaporation	=\$E420*AP409	RAW MATERIALS TOTAL	=SUM(AQ411:AQ419)	=\$AQ420/(AN409*1000)
421	700	Product Storage & Denature	=\$E421*AP409	Utilities		
422	800	Utilities & General	=\$E422*AP409	Electricity/ Energy	=\$G422*AR408	=\$AQ422/(AN409*1000)
423	810	Boiler	=\$E423*AP409	Water	=\$G423*AR408	=\$AQ423/(AN409*1000)
424	820	Non-Boiler Utilities	=\$E424*AP409	By-products	=\$G424*AR408	=\$AQ424/(AN409*1000)
425	830	Environmental	=\$E425*AP409	VARIABLE COST TOTAL	=SUM(AQ420:AQ424)	=\$AQ425/(AN409*1000)
426	840	Miscellaneous & Control	=\$E426*AP409	GEN & ADMIN	=1590*(AN409/25)*AO445	=\$AQ426/(AN409*1000)
427	900	Enzyme Production	=\$E427*AP409			
428				Operators	=\$G428*AR408*AO445	=\$AQ428/(AN409*1000)
429	1000	Total Fixed Capital	=SUM(AO410:AO428)	Laborers	=\$G429*(AR408)*AO445	=\$AQ429/(AN409*1000)
430				Technicians	=\$G430*(AR408)*AO445	=\$AQ430/(AN409*1000)
431	1010	Contingency	=AO429*AO441	Maintenance	=\$G431*(AR408)*AO445	=\$AQ431/(AN409*1000)
432	1020	Startup	=AO429*AO442	Fringe Benefits	=AQ445*SUM(AQ428:AO445)	=\$AQ432/(AN409*1000)
433	1030	Working Capital	=AO429*AO443	TOTAL LABOR	=SUM(AQ428:AO432)	=\$AQ433/(AN409*1000)
434				Property Tax & Insur.	=AO446*AO435*1000	=\$AQ434/(AN409*1000)
435		TOTAL CAPITAL	=SUM(AO429:AO434)	TOTAL CASH	=AQ425*AO426*AO433+	=\$AQ435/(AN409*1000)
436				Depreciation	=SLN((AO435*1000),(\$DS	=\$AQ436/(AN409*1000)
437				Interest	=AO435*1000*\$D\$319	=\$AQ437/(AN409*1000)
438						
439				TOTAL PRODUCTION	=AQ435*AO436*AO437	=\$AQ439/(AN409*1000)
440		Power Law Scaling Factor	=\$D\$303	=\$C\$311	=\$D\$311	
441		Contingency	=\$D\$304	=\$C\$312	=\$D\$312	
442		Start-up factor	=\$D\$305	=\$C\$313	=\$D\$313	
443		Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
444		Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
445		Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
446		Property Tax & Insurance	=\$D\$309	=\$C\$317	=\$D\$317	

I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	AA
PROCESS COST ONLY (BIOMASS \$0)																		
STAKEHOLDERS ESTIMATED BASE COSTS																		
Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #	Plant #
447	448	449	450	451	452	453	454	455	456	457	458	459	460	461	462	463	464	465
466	467	468	469	470	471	472	473	474	475	476	477	478	479	480	481	482	483	484
485	486	487	488	489	490	491	492	493	494	495	496	497	498	499	500	501	502	503
504	505	506	507	508	509	510	511	512	513	514	515	516	517	518	519	520	521	522
523	524	525	526	527	528	529	530	531	532	533	534	535	536	537	538	539	540	541
542	543	544	545	546	547	548	549	550	551	552	553	554	555	556	557	558	559	560
561	562	563	564	565	566	567	568	569	570	571	572	573	574	575	576	577	578	579
580	581	582	583	584	585	586	587	588	589	590	591	592	593	594	595	596	597	598
599	600	601	602	603	604	605	606	607	608	609	610	611	612	613	614	615	616	617
618	619	620	621	622	623	624	625	626	627	628	629	630	631	632	633	634	635	636
637	638	639	640	641	642	643	644	645	646	647	648	649	650	651	652	653	654	655
656	657	658	659	660	661	662	663	664	665	666	667	668	669	670	671	672	673	674
675	676	677	678	679	680	681	682	683	684	685	686	687	688	689	690	691	692	693
 	

447	AB	AC	AD	AE	AF	AG	AH	AI	AJ	AK	AL	AM	AN	AO	AP	AQ	AR
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off 0.20																	
Ethanol																	
Ethanol																	
STAKECH ESTIMATED BASE COSTS																	
Biomass \$450.00																	
Ratio of off																	

AS	AT	AU	AV	AW	AX	AY
447						
448						
449						
450						
451						
452						
453						
454						
455						
456						
457						
458						
459						
460						
461						
462						
463						
464						
465						
466						
467						
468						
469						
470						
471						
472						
473						
474						
475						
476						
477						
478						
479						
480						
481						
482						
483						
484						
485						
486						
487						

529	PROCESS COST ONLY (BIOMASS \$)	PROCESS COST ONLY (BIOMASS \$)

Page 2

530	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.6	Ratio of 0.100	Plant 166.
-----	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	-------------	----------------	------------

I	J	K	L	M	N	O	P	Q	R	S	T
447	SC3311					SC3311					
448	SC448					SC448					
449	SC3320	D449/D450 J450	SC3310	M61	Ratio of orig. to pro	J450/D450	SC3320	J449/J450 P450	SC3310	S481	Ratio of orig. to pro
450	SC3321	SD3322	SD3321	(J450/D450)*K481		SC3321	SD3321	Scaling of original d	(P450/D450)*Q481		P450/D450
451	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr
452	100	Biomass Preparation	SE452/L450	Biomass	J449/K455 L449	M452(J450/100)	100	Biomass Preparation	SE452/R450	Biomass	P449/Q456 P449
453	200	Pretreatment	SE453/L450	Chemicals	J450/M464 M465	M454(J450/100)	200	Pretreatment	SE453/R450	Chemicals	P450/Q464 P450
454	210	Recovery & Recycle	SE454/L450	Denatulant	J450/M464 M465	M454(J450/100)	210	Recovery & Recycle	SE454/R450	Denatulant	P450/Q464 P450
455	300	Hydrolysis	SE455/L450	Acid	SE455/N449	M455(J450/100)	300	Hydrolysis	SE455/R450	Acid	P450/Q464 P450
456	400	Fermentation (Unallocated)	SE456/L450	Ammonia	SE456/N449	M456(J450/100)	400	Fermentation (Unallocated)	SE456/R450	Ammonia	P450/Q464 P450
457	410	Hexose Fermentation	SE457/L450	Nutrients	SE457/N449	M457(J450/100)	410	Hexose Fermentation	SE457/R450	Nutrients	P450/Q464 P450
458	420	Pentose Fermentation	SE458/L450	Enzymes	SE458/N449	M458(J450/100)	420	Pentose Fermentation	SE458/R450	Enzymes	P450/Q464 P450
459	500	Distillation & Dehydration	SE459/L450	Yeast	SE459/N449	M459(J450/100)	500	Distillation & Dehydration	SE459/R450	Yeast	P450/Q464 P450
460	600	By Product Preparation	SE460/L450	Other Chemicals	SE460/N449	M460(J450/100)	600	By Product Preparation	SE460/R450	Other Chemicals	P450/Q464 P450
461	610	Silage Evaporation	SE461/L450	RAW MATERIALS TOTAL	SUM(M452-M460)	M461(J450/100)	610	Silage Evaporation	SE461/R450	RAW MATERIALS TOTAL	SUM(M452-M460)
462	700	Product Storage & Denature	SE462/L450	Utilities	SE462/N449	M462(J450/100)	700	Product Storage & Denature	SE462/R450	Utilities	P450/Q464 P450
463	800	Utilities & General	SE463/L450	Electricity/Energy	SE463/N449	M463(J450/100)	800	Utilities & General	SE463/R450	Electricity/Energy	P450/Q464 P450
464	810	Boiler	SE464/L450	Water	SE464/N449	M464(J450/100)	810	Boiler	SE464/R450	Water	P450/Q464 P450
465	820	Non Boiler Utilities	SE465/L450	By products	SE465/N449	M465(J450/100)	820	Non Boiler Utilities	SE465/R450	By products	P450/Q464 P450
466	830	Environmental	SE466/L450	VARIABLE COST TOTAL	SUM(M461-M465)	M466(J450/100)	830	Environmental	SE466/R450	VARIABLE COST TOTAL	SUM(M461-M465)
467	940	Miscellaneous & Control	SE467/L450	GEN & ADMIN	SE467/N449	M467(J450/100)	940	Miscellaneous & Control	SE467/R450	GEN & ADMIN	P450/Q464 P450
468	900	Enzyme Production	SE468/L450	Operators	SE468/N449	M468(J450/100)	900	Enzyme Production	SE468/R450	Operators	P450/Q464 P450
469				Laborers	SE469/N449	M469(J450/100)				Laborers	P450/Q464 P450
470	1000	Total Fixed Capital	SUM(K451-K469)	Technicians	SE470/N449	M470(J450/100)	1000	Total Fixed Capital	SUM(Q451-Q469)	Technicians	P450/Q464 P450
471				Maintenance	SE471/N449	M471(J450/100)				Maintenance	P450/Q464 P450
472	1010	Contingency	K470/K482	Fringe Benefits	SE472/N449	M472(J450/100)	1010	Contingency	O470/Q482	Fringe Benefits	P450/Q464 P450
473	1020	Startup	K470/K483	TOTAL LABOR	SUM(M468-M473)	M473(J450/100)	1020	Startup	O470/Q483	TOTAL LABOR	SUM(M468-M473)
474	1030	Working Capital	K470/K484	Property Tax & Insur.	K470/K476-1000	M474(J450/100)	1030	Working Capital	O470/Q484	Property Tax & Insur.	K470/K476-1000
475				TOTAL CASH	SUM(K470-K475)	M475(J450/100)				TOTAL CASH	SUM(Q470-Q475)
476		TOTAL CAPITAL		Depreciation	SE476/N449	M476(J450/100)		TOTAL CAPITAL		Depreciation	SE476/N449
477				Interest	K476/1000 SD33	M476(J450/100)				Interest	K476/1000 SD33
478				TOTAL PRODUCTION	M476-M477-M481	M480(J450/100)				TOTAL PRODUCTION	M476-M477-M481
479											
480											
481		Power Law Scaling Factor	SD3303	SC3311	SD3311			Power Law Scaling Factor	SD3303	SC3311	SD3311
482		Contingency	SD3304	SC3312	SD3312			Contingency	SD3304	SC3312	SD3312
483		Start-up factor	SD3305	SC3313	SD3313			Start-up factor	SD3305	SC3313	SD3313
484		Working Capital	SD3306	Denatulant Cost, \$/gal	SD3314			Working Capital	SD3306	Denatulant Cost, \$/gal	SD3314
485		Operating Days per Year	SD3307	Denatulant Use	SD3315			Operating Days per Year	SD3307	Denatulant Use	SD3315
486		Personnel Scaling Factor	SD3308	Fringe Benefits	SD3316			Personnel Scaling Factor	SD3308	Fringe Benefits	SD3316
487		Property Tax & Insurance	SD3309	SC3317	SD3317			Property Tax & Insurance	SD3309	SC3317	SD3317
488	SC3311					SC3311					
489	SC489					SC489					
490	SC3320	D490/D491 J491	SC3310	M522	Ratio of orig. to pro	J491/D491	SC3320	J490/J491 P491	SC3310	S522	Ratio of orig. to pro
491	SC3321	SD3322	SD3321	(J491/D491)*K522		SC3321	SD3321	Scaling of original d	(P491/D491)*Q522		P491/D491
492	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr	\$/gal	AREA	CAPITAL COSTS	Million \$	PRODUCTION COSTS	Thous \$/Yr
493	100	Biomass Preparation	SE493/L491	Biomass	J490/K526 L490	M493(J491/100)	100	Biomass Preparation	SE493/R491	Biomass	P490/Q526 P490
494	200	Pretreatment	SE494/L491	Chemicals	J491/M525 M526	M494(J491/100)	200	Pretreatment	SE494/R491	Chemicals	P490/Q526 P490
495	210	Recovery & Recycle	SE495/L491	Denatulant	J491/M525 M526	M494(J491/100)	210	Recovery & Recycle	SE495/R491	Denatulant	P490/Q526 P490
496	300	Hydrolysis	SE496/L491	Acid	SE496/N490	M496(J491/100)	300	Hydrolysis	SE496/R491	Acid	P490/Q526 P490
497	400	Fermentation (Unallocated)	SE497/L491	Ammonia	SE497/N490	M497(J491/100)	400	Fermentation (Unallocated)	SE497/R491	Ammonia	P490/Q526 P490
498	410	Hexose Fermentation	SE498/L491	Nutrients	SE498/N490	M498(J491/100)	410	Hexose Fermentation	SE498/R491	Nutrients	P490/Q526 P490
499	420	Pentose Fermentation	SE499/L491	Enzymes	SE499/N490	M499(J491/100)	420	Pentose Fermentation	SE499/R491	Enzymes	P490/Q526 P490
500	500	Distillation & Dehydration	SE500/L491	Yeast	SE500/N490	M500(J491/100)	500	Distillation & Dehydration	SE500/R491	Yeast	P490/Q526 P490
501	600	By Product Preparation	SE501/L491	Other Chemicals	SE501/N490	M501(J491/100)	600	By Product Preparation	SE501/R491	Other Chemicals	P490/Q526 P490
502	610	Silage Evaporation	SE502/L491	RAW MATERIALS TOTAL	SUM(M493-M501)	M502(J491/100)	610	Silage Evaporation	SE502/R491	RAW MATERIALS TOTAL	SUM(M493-M501)
503	700	Product Storage & Denature	SE503/L491	Utilities	SE503/N490	M503(J491/100)	700	Product Storage & Denature	SE503/R491	Utilities	P490/Q526 P490
504	800	Utilities & General	SE504/L491	Electricity/Energy	SE504/N490	M504(J491/100)	800	Utilities & General	SE504/R491	Electricity/Energy	P490/Q526 P490
505	810	Boiler	SE505/L491	Water	SE505/N490	M505(J491/100)	810	Boiler	SE505/R491	Water	P490/Q526 P490
506	820	Non Boiler Utilities	SE506/L491	By products	SE506/N490	M506(J491/100)	820	Non Boiler Utilities	SE506/R491	By products	P490/Q526 P490
507	830	Environmental	SE507/L491	VARIABLE COST TOTAL	SUM(M502-M506)	M507(J491/100)	830	Environmental	SE507/R491	VARIABLE COST TOTAL	SUM(M502-M506)
508	940	Miscellaneous & Control	SE508/L491	GEN & ADMIN	SE508/N490	M508(J491/100)	940	Miscellaneous & Control	SE508/R491	GEN & ADMIN	P490/Q526 P490
509	900	Enzyme Production	SE509/L491	Operators	SE509/N490	M509(J491/100)	900	Enzyme Production	SE509/R491	Operators	P490/Q526 P490
510				Laborers	SE510/N490	M510(J491/100)				Laborers	P490/Q526 P490
511	1000	Total Fixed Capital	SUM(K492-K510)	Technicians	SE511/N490	M511(J491/100)	1000	Total Fixed Capital	SUM(Q492-Q510)	Technicians	P490/Q526 P490
512				Maintenance	SE512/N490	M512(J491/100)				Maintenance	P490/Q526 P490
513	1010	Contingency	K511/K528	Fringe Benefits	SE513/N490	M513(J491/100)	1010	Contingency	O511/Q528	Fringe Benefits	P490/Q526 P490
514	1020	Startup	K511/K529	TOTAL LABOR	SUM(M509-M514)	M514(J491/100)	1020	Startup	O511/Q529	TOTAL LABOR	SUM(M509-M514)
515	1030	Working Capital	K511/K528	Property Tax & Insur.	K528/K517-1000	M515(J491/100)	1030	Working Capital	O511/Q528	Property Tax & Insur.	K528/K517-1000
516				TOTAL CASH	SUM(K511-K516)	M516(J491/100)				TOTAL CASH	SUM(Q511-Q516)
517				Depreciation	SE517/N490	M517(J491/100)				Depreciation	SE517/N490
518				Interest	K517/1000 SD33	M517(J491/100)				Interest	K517/1000 SD33
519				TOTAL PRODUCTION	M517-M518-M51	M521(J491/100)				TOTAL PRODUCTION	M517-M518-M51
520											
521											
522		Power Law Scaling Factor	SD3303	SC3311	SD3311			Power Law Scaling Factor	SD3303	SC3311	SD3311
523		Contingency	SD3304	SC3312	SD3312			Contingency	SD3304	SC3312	SD3312
524		Start-up factor	SD3305	SC3313	SD3313			Start-up factor	SD3305	SC3313	SD3313
525		Working Capital	SD3306	Denatulant Cost, \$/gal	SD3314			Working Capital	SD3306	Denatulant Cost, \$/gal	SD3314
526		Operating Days per Year	SD3307	Denatulant Use	SD3315			Operating Days per Year	SD3307	Denatulant Use	SD3315
527		Personnel Scaling Factor	SD3308	Fringe Benefits	SD3316			Personnel Scaling Factor	SD3308	Fringe Benefits	SD3316
528		Property Tax & Insurance	SD3309	SC3317	SD3317			Property Tax & Insurance	SD3309	SC3317	SD3317

U	V	W	X	Y	Z	AA	AB	AC	AD	AE	AF
441	EC312					EC312					
442	EC312					EC312					
443	EC312					EC312					
444	EC312					EC312					
445	EC312					EC312					
446	EC312					EC312					
447	EC312					EC312					
448	EC312					EC312					
449	EC312					EC312					
450	EC312					EC312					
451	EC312					EC312					
452	EC312					EC312					
453	EC312					EC312					
454	EC312					EC312					
455	EC312					EC312					
456	EC312					EC312					
457	EC312					EC312					
458	EC312					EC312					
459	EC312					EC312					
460	EC312					EC312					
461	EC312					EC312					
462	EC312					EC312					
463	EC312					EC312					
464	EC312					EC312					
465	EC312					EC312					
466	EC312					EC312					
467	EC312					EC312					
468	EC312					EC312					
469	EC312					EC312					
470	EC312					EC312					
471	EC312					EC312					
472	EC312					EC312					
473	EC312					EC312					
474	EC312					EC312					
475	EC312					EC312					
476	EC312					EC312					
477	EC312					EC312					
478	EC312					EC312					
479	EC312					EC312					
480	EC312					EC312					
481	EC312					EC312					
482	EC312					EC312					
483	EC312					EC312					
484	EC312					EC312					
485	EC312					EC312					
486	EC312					EC312					
487	EC312					EC312					
488	EC312					EC312					
489	EC312					EC312					
490	EC312					EC312					
491	EC312					EC312					
492	EC312					EC312					
493	EC312					EC312					
494	EC312					EC312					
495	EC312					EC312					
496	EC312					EC312					
497	EC312					EC312					
498	EC312					EC312					
499	EC312					EC312					
500	EC312					EC312					
501	EC312					EC312					
502	EC312					EC312					
503	EC312					EC312					
504	EC312					EC312					
505	EC312					EC312					
506	EC312					EC312					
507	EC312					EC312					
508	EC312					EC312					
509	EC312					EC312					
510	EC312					EC312					
511	EC312					EC312					
512	EC312					EC312					
513	EC312					EC312					
514	EC312					EC312					
515	EC312					EC312					
516	EC312					EC312					
517	EC312					EC312					
518	EC312					EC312					
519	EC312					EC312					
520	EC312					EC312					
521	EC312					EC312					
522	EC312					EC312					
523	EC312					EC312					
524	EC312					EC312					
525	EC312					EC312					
526	EC312					EC312					
527	EC312					EC312					
528	EC312					EC312					

[illegible]

U	V	W	X	Y	Z	AA	AB	AC	AD	AE	AF
529	EC512					EC512					
530	EC530					EC530					
531	EC530	EC530	Y664			EC530					
532	EC531	EC531	Y664			EC531					
533	EC531	EC531	Y664			EC531					
534	EC531	EC531	Y664			EC531					
535	EC531	EC531	Y664			EC531					
536	EC531	EC531	Y664			EC531					
537	EC531	EC531	Y664			EC531					
538	EC531	EC531	Y664			EC531					
539	EC531	EC531	Y664			EC531					
540	EC531	EC531	Y664			EC531					
541	EC531	EC531	Y664			EC531					
542	EC531	EC531	Y664			EC531					
543	EC531	EC531	Y664			EC531					
544	EC531	EC531	Y664			EC531					
545	EC531	EC531	Y664			EC531					
546	EC531	EC531	Y664			EC531					
547	EC531	EC531	Y664			EC531					
548	EC531	EC531	Y664			EC531					
549	EC531	EC531	Y664			EC531					
550	EC531	EC531	Y664			EC531					
551	EC531	EC531	Y664			EC531					
552	EC531	EC531	Y664			EC531					
553	EC531	EC531	Y664			EC531					
554	EC531	EC531	Y664			EC531					
555	EC531	EC531	Y664			EC531					
556	EC531	EC531	Y664			EC531					
557	EC531	EC531	Y664			EC531					
558	EC531	EC531	Y664			EC531					
559	EC531	EC531	Y664			EC531					
560	EC531	EC531	Y664			EC531					
561	EC531	EC531	Y664			EC531					
562	EC531	EC531	Y664			EC531					
563	EC531	EC531	Y664			EC531					
564	EC531	EC531	Y664			EC531					
565	EC531	EC531	Y664			EC531					
566	EC531	EC531	Y664			EC531					
567	EC531	EC531	Y664			EC531					
568	EC531	EC531	Y664			EC531					
569	EC531	EC531	Y664			EC531					
570	EC531	EC531	Y664			EC531					
571	EC531	EC531	Y664			EC531					
572	EC531	EC531	Y664			EC531					
573	EC531	EC531	Y664			EC531					
574	EC531	EC531	Y664			EC531					
575	EC531	EC531	Y664			EC531					
576	EC531	EC531	Y664			EC531					
577	EC531	EC531	Y664			EC531					
578	EC531	EC531	Y664			EC531					
579	EC531	EC531	Y664			EC531					
580	EC531	EC531	Y664			EC531					
581	EC531	EC531	Y664			EC531					
582	EC531	EC531	Y664			EC531					
583	EC531	EC531	Y664			EC531					
584	EC531	EC531	Y664			EC531					
585	EC531	EC531	Y664			EC531					
586	EC531	EC531	Y664			EC531					
587	EC531	EC531	Y664			EC531					
588	EC531	EC531	Y664			EC531					
589	EC531	EC531	Y664			EC531					
590	EC531	EC531	Y664			EC531					
591	EC531	EC531	Y664			EC531					
592	EC531	EC531	Y664			EC531					
593	EC531	EC531	Y664			EC531					
594	EC531	EC531	Y664			EC531					
595	EC531	EC531	Y664			EC531					
596	EC531	EC531	Y664			EC531					
597	EC531	EC531	Y664			EC531					
598	EC531	EC531	Y664			EC531					
599	EC531	EC531	Y664			EC531					
600	EC531	EC531	Y664			EC531					

Page 1

	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
611								Biomass cost per ton (dry basis) =	\$0.00					Biomass cost per ton (dry basis) =	\$50.00		Biomass cost per ton (dry basis) =	\$109.00	
612						Process		25	Million gpy facility		5	Million gpy facility		Million gpy:	25	5	Million gpy:	25	5
613	PROCESS			Title of Table in Appendix		reference	PROCESS	Capital	Unit Cost	Biomass	Capital	Unit Cost	Biomass	PROCESS	Unit Cost	Unit Cost	PROCESS	Unit Cost	Unit Cost
614						number		(MM\$)	\$/ Gal	tons/day	(MM\$)	\$/ Gal	tons/day		\$/ Gal	\$/ Gal		\$/ Gal	\$/ Gal
615	Simultaneous saccharification and fermentation			NREL SSF ESTIMATED BASE COSTS		1.	Simultaneous saccharification and fermentation	\$81	\$0.52	820	\$26	\$0.65	184	1.	\$1.06	\$1.19	1.	\$1.70	\$1.83
616	Concentrated acid hydrolysis, neutralization and fermentation			TVA ACID ESTIMATED BASE COSTS		2.	Concentrated acid hydrolysis, neutralization and fermentation	\$99	\$1.14	952	\$32	\$1.29	190	2.	\$1.77	\$1.92	2.	\$2.51	\$2.66
617	Ammonia disruption hydrolysis and fermentation			AFEX AMMONIA ESTIMATED BASE COSTS		3.	Ammonia disruption hydrolysis and fermentation	\$124	\$0.60	863	\$40	\$0.78	173	3.	\$1.17	\$1.35	3.	\$1.84	\$2.02
618	Steam disruption, hydrolysis and fermentation			STAKETECH ESTIMATED BASE COSTS		4.	Steam disruption, hydrolysis and fermentation	\$110	\$0.52	814	\$36	\$0.69	163	4.	\$1.06	\$1.22	4.	\$1.69	\$1.86
619	Acid disruption and transgenic microorganism fermentation (Quadrex)			BIOENERGY ESTIMATED BASE COSTS		5.	Acid disruption and transgenic microorganism fermentation (Quadrex)	\$127	\$0.64	838	\$41	\$0.83	168	5.	\$1.20	\$1.38	5.	\$1.85	\$2.03
620	Concentrated acid hydrolysis, acid recycle and fermentation			ARKENOL ESTIMATED BASE COSTS		6.	Concentrated acid hydrolysis, acid recycle and fermentation	\$72	\$0.94	833	\$23	\$1.04	167	6.	\$1.49	\$1.59	6.	\$2.14	\$2.24
621	Acidified acetone extraction, hydrolysis and fermentation			PASZNER TECHNOLOGY ESTIMATED BASE COSTS		7.	Acidified acetone extraction, hydrolysis and fermentation	\$88	\$0.73	779	\$29	\$0.87	156	7.	\$1.24	\$1.39	7.	\$1.85	\$1.99

	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
611								Biomass	=K622					Biomass cost	=Q623		=P611	=T624	
612						Process		=J327	Million gpy fac		=P327	=K612		Million gpy:	=V327	=AB327	=P612	=AH327	=AN327
613	PROCESS			Title of Tab	reference	=C613	Capital	Unit Cost	Biomass	Capital	Unit Cost	Biomass		=C613	Unit Cost	Unit Cost	=P613	Unit Cost	Unit Cost
614				number			(MMS)	\$/ Gal	tons/day	(MMS)	\$/ Gal	tons/day			\$/ Gal	\$/ Gal		\$/ Gal	\$/ Gal
615	Simultaneous saccharification and fermentation			=SC325	1	=C616	=K353	=N357	=K326	=O353	=T357	=P326	=H615	=Z357	=AF357	=P616	=AL357	=AR357	
616	Concentrated acid hydrolysis, neutralization and fermentation			=SC368	2	=C618	=K394	=N398	=I367	=O394	=T396	=P367	=H616	=Z396	=AF398	=P616	=AL398	=AR398	
617	Ammonia disruption hydrolysis and fermentation			=SC407	3	=C617	=K436	=N439	=K406	=Q435	=T439	=P406	=H617	=Z439	=AF439	=P617	=AL439	=AR439	
618	Steam disruption, hydrolysis and fermentation			=SC448	4	=C618	=K476	=N480	=J449	=O476	=T480	=P449	=H618	=Z480	=AF480	=P618	=AL480	=AR480	
619	Acid disruption and transgenic microorganism fermentation (C			=SC489	5	=C619	=K517	=N521	=J490	=O517	=T521	=P490	=H619	=Z521	=AF521	=P619	=AL521	=AR521	
620	Concentrated acid hydrolysis, acid recycle and fermentation			=SC630	6	=C620	=K558	=N562	=J531	=O558	=T562	=P531	=H620	=Z562	=AF562	=P620	=AL562	=AR562	
621	Acidified acetone extraction, hydrolysis and fermentation			=SC671	7	=C621	=K599	=N603	=J572	=O599	=T603	=P572	=H621	=Z603	=AF603	=P621	=AL603	=AR603	

C	D	E	F	G	H	I	J	K	L	M	N	PROCESS COST ONLY (BIOMASS \$0)				BIOMASS COST 1							
												O	P	Q	R	S	T	U	V	W	X	Y	Z
TRADITIONAL FERMENTATION																TRADITIONAL FERMENTATION							
Plant feedrate (dry tons per day)	1456	Biomass Cost/ton	\$0.00	Ratio of org. to proposed size	1.00	Ethanol Production (MM gal/yr)	25	Scaling of original data	0.32	Plant feedrate (dry tons per day)	231	Biomass Cost/ton	\$0.00	Ratio of org. to proposed size	0.20	Plant feedrate (dry tons per day)	1456	Biomass Cost/ton	\$0.00	Ratio of org. to proposed size	1.00		
626																							
627																							
628																							
629																							
630																							
631																							
632																							
633																							
634																							
635																							
636																							
637																							
638																							
639																							
640																							
641																							
642																							
643																							
644																							
645																							
646																							
647																							
648																							
649																							
650																							
651																							
652																							
653																							
654																							
655																							
656																							
657																							
658																							
659																							
660																							
661																							
662																							
663																							
664																							
665																							
666																							

AA	AB	AC	AD	AE	AF
BIOMASS COSTS					
TRADITIONAL FERMENTATION					
626	Plant feedstuffs (Cytions per day)	291	Biomass Cost/ton.	\$0.00	Ratio of org. to proposed size
627					0.20
628	Ethanol Production (MM gal/yr)	\$	Scaling of original data	0.32	
629					
AFA	CAPITAL COSTS	MM\$	PRODUCTION COSTS	\$/yr	\$/gal
630	Biomass Preparation	\$1,170	Biomass	0	\$0.000
631	Preparation	\$0.000	Chemicals	3.18	\$0.04
632	Recovery & Waste	\$0.000	Distillation	0	\$0.000
633	Hydrolysis	\$0.000	Acid	0	\$0.000
634	Fermentation (Unfermented)	\$0.000	Ammonia	0	\$0.000
635	Fermentation	\$1,822	Indirect	0	\$0.000
636	Process Fermentation	\$0.000	Enzyme	0	\$0.000
637	Distillation & Dehydration	\$0.000	Year	0	\$0.000
638	By-Product Preparation	\$0.000	Other Chemicals	648	\$0.14
639	Silage Evaporation	\$0.000	RAW MATERIALS	848	\$0.177
640	Process Equipment	\$0.13	Utilities	0	\$0.000
641	Utilities	\$0.000	Electricity	1.76	\$0.06
642	Water	\$0.000	Water	0	\$0.000
643	Non-Electric Utilities	\$0.872	Steam	0	\$0.000
644	Environmental	\$0.872	VARIABLE COE	843	\$0.131
645	Major Equipment & Control	\$1,021	LABOR	3.71	\$0.06
646	Minor Equipment	\$0.000	Operator	1.76	\$0.06
647	Construction	\$0.000	Technician	0.97	\$0.03
648	Total Plant Cost	\$3,001	Maintenance	1.48	\$0.04
649	Contingency	\$1,330	Fringe Benefits	1.48	\$0.04
650	Working Capital	\$0.000	TOTAL LABOR	7.28	\$0.14
651	Operating Days per Year	330	Property Tax &	258	\$0.061
652	Personnel Scaling Factor	0.9	Depreciation	2.00	\$0.04
653	Property Tax & Insurance	1.00%	Interest	0	\$0.000
654			TOTAL PRODU	2,000	\$0.21
655			PROCESS COST ONLY	\$0.00	
656	Power Law Scaling Factor	0.7	BIOMASS \$9	\$0.00	
657	Contingency	10.00%	BIOMASS COST 1	\$0.00	
658	Start up factor	8.00%	BIOMASS COST 2	\$0.00	
659	Working Capital	7.00%	Distillation	\$0.87	
660	Operating Days per Year	330	Coil, Syst	6%	
661	Personnel Scaling Factor	0.9	Fringe Benefits	25%	
662	Property Tax & Insurance	1.00%	Capital Charge	0%	

C	D	E	F	G	H	I	J	K	L	M	N	
626						=\$C\$31						
627	TRADIT					=\$C\$27						
628	=\$C\$32	=((D629*1000000)/K664)/((H5+H	=\$C\$310	0		=\$C\$32	=D628/D629*J629	=\$C\$310	=M660	Ratio of orig. to proposed	=J629/\$D\$629	
629	=\$C\$32	25				=\$C\$32	=\$D\$322	Scaling of orig	=(J629/\$D\$629)*K660			
630	AREA	CAPITAL COSTS	MM\$	PRODUCTION COSTS	\$M/Yr	\$/gal	AREA	CAPITAL COSTS	MM\$	PRODUCTION COSTS	\$M/Yr	\$/gal
631	100	Biomass Preparation	3.809	Biomass	=(D628*F628)*\$D\$307/1000	=G631/(D629*1000)	100	Biomass Preparation	=\$E631*L629	Biomass	=J628*K664*L628/1000	=M631/(J629*1000)
632	200	Pretreatment		Chemicals			200	Pretreatment	=\$E632*L629	Chemicals		
633	210	Recycle & Recovery		Denaturant	=D629*M663*M664*1000	=G633/(D629*1000)	210	Recovey & Recycle	=\$E633*L629	Denaturant	=J629*M663*M664*1000	=M633/(J629*1000)
634	300	Hydrolysis		Acid	0	=G634/(D629*1000)	300	Hydrolysis	=\$E634*L629	Acid	=\$G634*N628	=M634/(J629*1000)
635	400	Fermentation		Ammonia	0	=G635/(D629*1000)	400	Fermentation (Unallocated)	=\$E635*L629	Ammonia	=\$G635*N628	=M635/(J629*1000)
636	410	Hexose Fermentation	5.62	Nutrients	0	=G636/(D629*1000)	410	Hexose Fermentation	=\$E636*L629	Nutrients	=\$G636*N628	=M636/(J629*1000)
637	420	Pentose Fermentation		Enzymes	0	=G637/(D629*1000)	420	Pentose Fermentation	=\$E637*L629	Enzymes	=\$G637*N628	=M637/(J629*1000)
638	500	Distillation& Dehydration		Yeast	0	=G638/(D629*1000)	500	Distillation & Dehydration	=\$E638*L629	Yeast	=\$G638*N628	=M638/(J629*1000)
639	600	By-Product Preparation		Other Chemicals	3341	=G639/(D629*1000)	600	By-Product Preparation	=\$E639*L629	Other Chemicals	=\$G639*N628	=M639/(J629*1000)
640	610	Stillage Evaporation		RAW MATERIALS TOTAL	=SUM(G631:G639)	=G640/(D629*1000)	610	Stillage Evaporation	=\$E640*L629	RAW MATERIALS TOTAL	=SUM(M631:M639)	=M640/(J629*1000)
641	700	Product Storage & Denature	1.583	Utilities			700	Product Storage & Denature	=\$E641*L629	Utilities		
642	800	Utilities & General		Electricity/Energy	-1390	=G642/(D629*1000)	800	Utilities & General	=\$E642*L629	Electricity/Energy	=\$G642*N628	=M642/(J629*1000)
643	810	Boiler	10.009	Water	52	=G643/(D629*1000)	810	Boiler	=\$E643*L629	Water	=\$G643*N628	=M643/(J629*1000)
644	820	Non-Boiler Utilities	16.78	By-products	173	=G644/(D629*1000)	820	Non-Boiler Utilities	=\$E644*L629	By-products	=\$G644*N628	=M644/(J629*1000)
645	830	Environmental	2.074	VARIABLE COST TOTAL	=SUM(G640:G644)	=G645/(D629*1000)	830	Environmental	=\$E645*L629	VARIABLE COST TOTAL	=SUM(M640:M644)	=M645/(J629*1000)
646	840	Miscellaneous & Control	3.213	GEN & ADMIN	1590	=G646/(D629*1000)	840	Miscellaneous & Control	=\$E646*L629	GEN & ADMIN	=1590*(J629/25)*K665	=M646/(J629*1000)
647	900	Enzyme Production		Enzyme Production			900	Enzyme Production	=\$E647*L629	Enzyme Production		
648		Total Installed Equipment	=SUM(E631:E647)	Operators	1520	=G648/(D629*1000)	1000	Total Fixed Capital	=\$E649*L629	Operators	=\$G649*N628*K665	=M648/(J629*1000)
649				Laborers	750	=G649/(D629*1000)				Laborers	=\$G650*N628*K665	=M649/(J629*1000)
650				Technicians	157	=G650/(D629*1000)				Technicians	=\$G651*N628)*K665	=M650/(J629*1000)
651		Fixed Capital	=E649	Maintenance	800	=G651/(D629*1000)	1010	Contingency	=K649*K661	Maintenance	=\$G652*N628)*K665	=M651/(J629*1000)
652	=K661	Miscellaneous	=E651*C652	Fringe Benefits	807	=G652/(D629*1000)	1020	Startup	=K649*K662	Fringe Benefits	=M665*SUM(M648:M651)	=M652/(J629*1000)
653	=K662	Start-up Costs	=E651*C653	TOTAL LABOR	=SUM(G648:G652)	=G653/(D629*1000)	1030	Working Capital	=K649*K663	TOTAL LABOR	=SUM(M648:M652)	=M653/(J629*1000)
654	=K663	Working capital	=E651*C654	Property Tax & Insur.	=K666*E656*1000	=G654/(D629*1000)				Property Tax & Insur.	=K668*K655*1000	=M654/(J629*1000)
655				TOTAL CASH	=G645+G646+G653+G654	=G655/(D629*1000)		TOTAL CAPITAL	=SUM(K649:K663)	TOTAL CASH	=M645+M646+M653+M654	=M655/(J629*1000)
656		TOTAL CAPITAL	=SUM(E651:E655)	Depreciation	=SLN((E656*1000)/(\$D\$318*1000)*E656)*\$D\$317	=G656/(D629*1000)				Depreciation	=SLN((K656*1000)/(\$D\$318*1000)*K656)*\$D\$317	=M656/(J629*1000)
657				Interest	=E656*1000*\$D\$319	=G657/(D629*1000)				Interest	=K656*1000*\$D\$319	=M657/(J629*1000)
658				TOTAL PRODUCTION	=G655+G656+G657	=G658/(D629*1000)				TOTAL PRODUCTION	=M655+M656+M657	=M658/(J629*1000)
660								Power Law Scaling Factor	=\$D\$303	=\$C\$311	=\$D\$311	
661								Contingency	=\$D\$304	=\$C\$312	=F628	
662								Start-up factor	=\$D\$305	=\$C\$313	=F628	
663								Working Capital	=\$D\$306	Denaturant Cost, \$/gal	=\$D\$314	
664								Operating Days per Year	=\$D\$307	Denaturant Use	=\$D\$315	
665								Personnel Scaling Factor	=\$D\$308	Fringe Benefits	=\$D\$316	
666								Property Tax & Insurance	=\$D\$309	Capital Charge, %/yr	=\$D\$319	

AA	AB	AC	AD	AE	AF
626 = \$C331					
627 = \$C327					
628 = \$C332 - V028V029*AB629		-\$C3310	-AE661	Ratio of orig. to proposed size-	-AB629/AD629
629 = \$C332 - \$D3321		Scaling of original data	-(AB629/AD629)*AC660		
630 AREA	CAPITAL COSTS	MM\$	PRODUCTION COSTS	\$/yr	
631 100	Biomass Preparation	-\$E631*AD629	Biomass	-\$AB629*AC664*AD629/1000	-\$AE631/AB629*1000
632 200	Pretreatment	-\$E632*AD629	Chemicals		
633 210	Recovery & Recycle	-\$E633*AD629	Denatrant	-\$AB629*E663/AB629*1000	-\$AE633/AB629*1000
634 300	Hydrolysis	-\$E634*AD629	Acid	-\$E634/AB629*1000	-\$AE634/AB629*1000
635 400	Fermentation (Uninoculated)	-\$E635*AD629	Ammonia	-\$E635/AB629*1000	-\$AE635/AB629*1000
636 410	Fermentation (Inoculated)	-\$E636*AD629	Enzymes	-\$E636/AB629*1000	-\$AE636/AB629*1000
637 420	Pentose Fermentation	-\$E637*AD629	Enzymes	-\$E637/AB629*1000	-\$AE637/AB629*1000
638 500	Distillation & Dehydration	-\$E638*AD629	Yeast	-\$E638/AB629*1000	-\$AE638/AB629*1000
639 600	By-Product Preparation	-\$E639*AD629	Other Chemicals	-\$E639/AB629*1000	-\$AE639/AB629*1000
640 610	Stillage Evaporation	-\$E640*AD629	RAW MATERIALS TOTAL	-\$SUM(AE631-AE639)	-\$E640/AB629*1000
641 700	Product Storage & Distribution	-\$E641*AD629	Utilities		
642 800	Utilities & General	-\$E642*AD629	Electricity/Energy	-\$E642/AB629*1000	-\$AE642/AB629*1000
643 810	Boiler	-\$E643*AD629	Water	-\$E643/AB629*1000	-\$AE643/AB629*1000
644 920	Non-Boiler Utilities	-\$E644*AD629	By-Products	-\$E644/AB629*1000	-\$AE644/AB629*1000
645 830	Environmental	-\$E645*AD629	VARIABLE COST TOTAL	-\$SUM(AE640-AE644)	-\$E645/AB629*1000
646 840	Miscellaneous & Contingency	-\$E646*AD629	GEN & LOAN	-\$E646/AB629*1000	-\$AE646/AB629*1000
647 900	Fixed Costs	-\$E647*AD629			
648 1000	Total Fixed Capital	-\$E648*AD629			
649 1000	Contingency	-\$E649*AD629			
650 1010	Working Capital	-\$E650*AD629			
651 1020	Start-up	-\$E651*AD629			
652 1030	Working Capital	-\$E652*AD629			
653 1040	Working Capital	-\$E653*AD629			
654 1050	Working Capital	-\$E654*AD629			
655 1060	Working Capital	-\$E655*AD629			
656 1070	Working Capital	-\$E656*AD629			
657 1080	Working Capital	-\$E657*AD629			
658 1090	Working Capital	-\$E658*AD629			
659 1100	Working Capital	-\$E659*AD629			
660 1110	Working Capital	-\$E660*AD629			
661 1120	Working Capital	-\$E661*AD629			
662 1130	Working Capital	-\$E662*AD629			
663 1140	Working Capital	-\$E663*AD629			
664 1150	Working Capital	-\$E664*AD629			
665 1160	Working Capital	-\$E665*AD629			
666 1170	Working Capital	-\$E666*AD629			
667 1180	Working Capital	-\$E667*AD629			
668 1190	Working Capital	-\$E668*AD629			
669 1200	Working Capital	-\$E669*AD629			
670 1210	Working Capital	-\$E670*AD629			
671 1220	Working Capital	-\$E671*AD629			
672 1230	Working Capital	-\$E672*AD629			
673 1240	Working Capital	-\$E673*AD629			
674 1250	Working Capital	-\$E674*AD629			
675 1260	Working Capital	-\$E675*AD629			
676 1270	Working Capital	-\$E676*AD629			
677 1280	Working Capital	-\$E677*AD629			
678 1290	Working Capital	-\$E678*AD629			
679 1300	Working Capital	-\$E679*AD629			
680 1310	Working Capital	-\$E680*AD629			
 					

	C	D	E	F	G	H	I	J	K	L	M	N	O	P
667	ENERGY VALUES (BTU)	Fiber (ton dry matter)	#2 Diesel (Bbl)	#6 fuel oil (Bbl)	Coal (ton)	Lignin (ton)	lignin ref							
668	oil & coal ref: USDOE/EIA Btu	16,800,000	5,900,000	6,300,000	21,000,000	20,714,000	34	PRODUCING SUGAR, BAGASSE, AND MOLASSES						
669	Efficiency of conversion to steam	65%	82%	82%	82%	82%	<--(lignin: est.)							
670	Assumed reduction in retrievable sucrose yield when harvest without open field burning	4%	Factors (Bbl or ton per dry ton bagasse)	Total cost per wet ton prep cane to 98 DA sugar	Field costs = ____% of total per wet ton	Field costs per wet ton prep cane	Factory costs per wet ton prep cane	SCENARIO	BASELINE	SUGAR COMPANY HARVESTING W/OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE AND MOLASSES (BUSINESS-AS-USUAL)				
671	ETHANOL \$/GALLON	\$1.30	V	\$38.47	76%	\$29.14	\$9.33	MATERIAL	TONS/ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
672	#2 DIESEL (BARREL)	\$32.00	2.28	Island plantation				SUGAR INDUSTRY PRODUCTS						
673	#6 FUEL OIL (BARREL)	\$16.00	2.11					Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
674	COAL (TON)	\$60.00	0.83	by sugar plantations,	% of total sugar elect. sales	Est. avg. retail value (\$/kWh)	Est. avg. wholesale \$/kWh	Leaves & tops (wet tons) not counted in prep. cane	0	--	--			
675	LIGNIN (TON)	--	0.64			sugar electricity \$0.13	sugar, '91	Sucrose (dry tons)	12.2	\$94.40	\$791	\$360.00	\$4,377	
676	Reduction factor for processing unburned leafy trash	0.60				Weighted factors	\$0.050	Bagasse (wet tons)	37.2	--	--	\$17.50	\$651	
677	1991 avg. residential electricity rate, \$/kWh	Kauai	\$0.14	100.12	23%	0.032	\$0.052	Molasses (wet tons)	3.0	--	--	\$40.00	\$118	
678	1991 Oahu \$/kWh	Oahu	\$0.09	45.45	11%	0.010	\$0.036							
679	1991 Maui (Island) \$/kWh	Maui Island	\$0.12	104.88	24%	0.030	\$0.048							
680	1991 Hawaii \$/kWh	Hawaii	\$0.14	180.98	42%	0.058	\$0.053	TOTAL			\$4,378		\$5,146	
681								PROFIT/LOSS PER ACRE						\$769
682														
683	SCENARIO	5	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH (LEAFY TRASH USED FOR ELECTRICITY GENERATION)					SCENARIO	6	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, LEAFY TRASH (TO ELECTRICITY), AND ETHANOL (MOLASSES TO ETHANOL)				
684	MATERIAL	TONS/ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE	MATERIAL	TONS/ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
685	SUGAR INDUSTRY PRODUCTS							SUGAR INDUSTRY PRODUCTS						
686	Prepared Cane (wet tons)	123.0	\$29.14	\$3,585				Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
687	Leaves & tops (wet tons) not counted in prep. cane	15.9	\$24.18	\$383	\$15.28	\$242		Leaves & tops (wet tons) not counted in prep. cane	15.9	\$24.18	\$383	\$15.28	\$242	
688	Sucrose (dry tons)	11.7	\$87.78	\$791	\$360.00	\$4,202		Sucrose (dry tons)	11.7	\$87.78	\$791	\$360.00	\$4,202	
689	Bagasse (wet tons)	37.2	--	--	\$17.50	\$651		Bagasse (wet tons)	37.2	--	--	\$17.50	\$651	
690	Molasses (wet tons)	3.0	--	--	\$40.00	\$118		Molasses (wet tons) to ethanol	3.0	\$38.21	\$107	\$104.59	\$309	
691														
692														
693	TOTAL			\$4,780		\$5,213		TOTAL			\$4,887		\$5,404	
694	PROFIT/LOSS PER ACRE						\$453	PROFIT/LOSS PER ACRE						\$537
695														

	C	D	E	F	G	H	I	J	K	L	M	N	O	P
696	SCENARIO	10	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING ETHANOL; BAGASSE VALUED AT COAL PRICE (SUGAR, BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)					SCENARIO	11	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR AND ETHANOL; BAGASSE VALUED AT #6 FUEL OIL PRICE (BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)				
697	MATERIAL	TONS/ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE	MATERIAL	TONS (BBLs) /ACRE	COST PER TON (BBL)	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
698	SUGAR INDUSTRY PRODUCTS							SUGAR INDUSTRY PRODUCTS						
699	Prepared Cane (wet tons)	123.0	\$29.14	\$3,585	\$0	\$0		Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
700	Unburned leafy trash (wet tons) -- to ethanol	15.9	\$24.18	\$383	\$0	\$0		Unburned leafy trash (wet tons) -- to ethanol	15.9	\$24.18	\$383			
701	Sucrose to ethanol	11.7	\$67.78	\$699	\$212.59	\$2,481		Sucrose (dry tons)	11.7	\$67.78	\$791	\$360.00	\$4,202	
702	Bagasse replaced by tons coal	7.0	\$60.00	\$423	--	\$470.13		Bagasse (wet tons) (replaced by #6 fuel oil) Bbls	23.5	\$16.00	\$376	--	\$622	
703	Molasses (wet tons) to ethanol	3.0	\$36.21	\$107	\$104.59	\$309		Molasses (wet tons) to ethanol	3.0	\$36.21	\$107	\$104.59	\$309	
704	Bagasse & unburned leafy trash (dry tons) to ethanol	29.6	\$42.50	\$1,258	\$85.00	\$2,517		Bagasse & unburned leafy trash (dry tons) to ethanol	29.6	\$42.50	\$1,258	\$85.00	\$2,517	
705	Recovered lignin (dry tons) to energy	5.5	--	--	--	see coal		Recovered lignin (dry tons) to energy	5.5	--	--	--	see fuel oil	
706	TOTAL			\$8,455		\$5,777		TOTAL			\$6,501		\$7,849	
707	PROFIT/LOSS PER ACRE						(\$878)	PROFIT/LOSS PER ACRE						\$1,149

	Q	R	S	T	U	V	W	X	Y	Z	AA	AB	AC	AD
667														
668	PRODUCING SUGAR, BAGASSE,							PRODUCING SUGAR						
669	AND ETHANOL							AND ETHANOL						
670	SCENARIO	2	SUGAR COMPANY HARVESTING W/OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, AND ETHANOL (MOLASSES TO ETHANOL)					SCENARIO	3	SUGAR COMPANY HARVESTING W/OPEN FIELD BURNING; PRODUCING SUGAR AND ETHANOL; BAGASSE VALUED AT COAL PRICE (BAGASSE AND MOLASSES TO ETHANOL)				
671	MATERIAL	TONS/ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	LOSS PER ACRE	MATERIAL	TONS/ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
672	SUGAR INDUSTRY PRODUCTS							SUGAR INDUSTRY PRODUCTS						
673	Prepared Cane (wet tons)	123.0	\$29.14	\$3,585.4				Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
674	Leaves & tops (wet tons) not counted in prep. cane	0	--	--				Leaves & tops (wet tons) not counted in prep. cane	0	--	--			
675	Sucrose (dry tons)	12.2	\$94.40	\$791.0	\$360.00	\$4,377		Sucrose (dry tons)	12.2	\$94.40	\$791	\$360.00	\$4,377	
676	Bagasse (wet tons)	37.2	--	--	\$17.50	\$651		Bagasse replaced by coal	8.8	\$60.00	\$517	--	\$470	
677	Molasses (wet tons) to ethanol	3.0	\$36.21	\$107	\$104.59	\$309		Molasses (wet tons) to ethanol	3.0	\$36.21	\$107	\$104.59	\$309	
678								Bagasse (dry tons) to ethanol	19.7	\$44.55	\$878	\$111.99	\$2,208	
679								Recovered lignin (dry tons) to energy	3.9	--	--	--	see coal	
680	TOTAL			\$4,483		\$5,337		TOTAL			\$5,878		\$7,384	
681	PROFIT/LOSS PER ACRE						\$853	PROFIT/LOSS PER ACRE						\$1,485
682														
683	SCENARIO	7	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, MOLASSES, AND ETHANOL (UNBURNED LEAFY TRASH TO ETHANOL)					SCENARIO	8	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, AND ETHANOL (MOLASSES AND UNBURNED LEAFY TRASH TO ETHANOL)				
684	MATERIAL	TONS/ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	LOSS PER ACRE	MATERIAL	TONS/ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
685	SUGAR INDUSTRY PRODUCTS							SUGAR INDUSTRY PRODUCTS						
686	Prepared Cane (wet tons)	123.0	\$29.14	\$3,585				Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
687	Unburned leafy trash (wet tons) -- to ethanol	15.9	\$24.18	\$383	--	--		Unburned leafy trash (wet tons) -- to ethanol	15.9	\$24.18	\$383			
688	Sucrose (dry tons)	11.7	\$67.78	\$791	\$360.00	\$4,202		Sucrose (dry tons)	11.7	\$67.78	\$791	\$360.00	\$4,202	
689	Bagasse (wet tons)	37.2	--	--	\$17.50	\$651		Bagasse (wet tons)	37.2	--	--	\$17.50	\$651	
690	Molasses (wet tons)	3.0	--	--	\$40.00	\$118		Molasses (wet tons) to ethanol	3.0	\$36.21	\$107	\$104.59	\$309	
691	Unburned leafy trash (dry tons) to ethanol	9.9	\$38.41	\$380	\$98.57	\$956		Unburned leafy trash (dry tons) to ethanol	9.9	38.4	380.1	98.6	\$956	
692	Recovered lignin (dry tons) to energy	2.0	--	--	\$63.48	\$126		Recovered lignin (dry tons) to energy	2.0	--	--	63.5	125.6	
693	TOTAL			\$5,140		\$6,052		TOTAL			\$5,247		\$8,117	
694	PROFIT/LOSS PER ACRE						\$912	PROFIT/LOSS PER ACRE						\$870
695														

	Q	R	S	T	U	V	W	X	Y	Z	AA	AB	AC	AD
696	SCENARIO	12	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING ETHANOL; BAGASSE VALUED AT #6 FUEL OIL PRICE (SUGAR, BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)					SCENARIO	13	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR AND ETHANOL; BAGASSE VALUED AT #2 DIESEL PRICE (BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)				
697	MATERIAL	TONS (BBLs) /ACRE	COST PER TON (BBL)	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE	MATERIAL	TONS (BBLs) /ACRE	COST PER TON (BBL)	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
698	SUGAR INDUSTRY PRODUCTS							SUGAR INDUSTRY PRODUCTS						
699	Prepared Cane (wet tons)	123.0	\$29.14	\$3,585				Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
700	Unburned leafy trash (wet tons) -- to ethanol	15.9	\$24.18	\$383				Unburned leafy trash (wet tons) -- to ethanol	15.9	\$24.18	\$383			
701	Sucrose to ethanol	11.7	\$87.78	\$899	\$212.59	\$2,481		Sucrose (dry tons)	11.7	\$87.78	\$791	\$380.00	\$4,202	
702	Bagasse (wet tons) (replaced by #6 fuel oil) Bbls	23.5	\$18.00	\$376	--	\$821.71		Bagasse (wet tons) (replaced by #2 diesel) Bbls	25.1	\$32.00	\$802	--	\$682	
703	Molasses (wet tons) to ethanol	3.0	\$38.21	\$107	\$104.59	\$309		Molasses (wet tons) to ethanol	3.0	\$38.21	\$107	\$104.59	\$309	
704	Bagasse & unburned leafy trash (dry tons) to ethanol	29.6	\$42.50	\$1,258	\$85.00	\$2,517		Bagasse & unburned leafy trash (dry tons) to ethanol	29.6	\$42.50	\$1,258	\$85.00	\$2,517	
705	Recovered lignin (dry tons) to energy	5.5	--	--	--	see fuel oil		Recovered lignin (dry tons) to energy	5.5	--	--	--	see diesel oil	
706	TOTAL			\$6,406		\$5,929		TOTAL			\$6,927		\$7,710	
707	PROFIT/LOSS PER ACRE						(\$479)	PROFIT/LOSS PER ACRE						\$782

	AE	AF	AG	AH	AI	AJ	AK
667							
668	PRODUCING						
669	ETHANOL ONLY						
670	SCENARIO	4	SUGAR COMPANY HARVESTING W/OPEN FIELD BURNING; PRODUCING ETHANOL; BAGASSE VALUED AT COAL PRICE (SUGAR, BAGASSE, AND MOLASSES TO ETHANOL)				
671	MATERIAL	TONS/ ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
672	SUGAR INDUSTRY PRODUCTS						
673	Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
674	Leaves & tops (wet tons) not counted in prep. cane	0	--	--			
675	Sucrose to ethanol	12.2	\$57.46	\$699	\$212.59	\$2,585	
676	Bagasse replaced by tons coal	8.6	\$80.00	\$517	--	\$470.13	
677	Molasses (wet tons) to ethanol	3.0	\$36.21	\$107	\$104.59	\$309	
678	Bagasse (dry tons) to ethanol	19.7	\$44.55	\$878	\$111.99	\$2,208	
679	Recovered lignin (dry tons) to energy	3.9	--	--	--	see coal	
680	TOTAL			\$5,786		\$5,572	
681	PROFIT/LOSS PER ACRE						(\$214)
682							
683	SCENARIO	9	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR AND ETHANOL; BAGASSE VALUED AT COAL PRICE (BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)				
684	MATERIAL	TONS/ ACRE	COST PER TON	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
685	SUGAR INDUSTRY PRODUCTS						
686	Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
687	Unburned leafy trash (wet tons) -- to ethanol	15.9	\$24.18	\$383			
688	Sucrose (dry tons)	11.7	\$67.78	\$791	\$360.00	\$4,202	
689	Bagasse replaced by tons coal	7.0	\$80.00	\$423	--	\$470	
690	Molasses (wet tons) to ethanol	3.0	\$36.21	\$107	\$104.59	\$309	
691	Bagasse & unburned leafy trash (dry tons) to ethanol	29.6	\$42.50	\$1,258	\$85.00	\$2,517	
692	Recovered lignin (dry tons) to energy	5.5	--	--	--	see coal	
693	TOTAL			\$6,548		\$7,498	
694	PROFIT/LOSS PER ACRE						\$950
695							

	AE	AF	AG	AH	AI	AJ	AK
	SCENARIO	14	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING ETHANOL; BAGASSE VALUED AT #2 DIESEL PRICE (SUGAR, BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)				
	MATERIAL	TONS (BBL) /ACRE	COST PER TON (BBL)	COST PER ACRE	VALUE PER TON	VALUE PER ACRE	PROFIT / LOSS PER ACRE
696							
697	SUGAR INDUSTRY PRODUCTS						
698							
699	Prepared Cane (wet tons)	123.0	\$29.14	\$3,585			
700	Unburned leafy trash (wet tons) -- to ethanol	15.9	\$24.18	\$383			
701	Sucrose to ethanol	11.7	\$87.78	\$699	\$212.59	\$2,481	
702	Bagasse (wet tons) (replaced by #2 diesel) Bbls	25.1	32.0	\$802	--	\$682	
703	Molasses (wet tons) to ethanol	3.0	\$38.21	\$107	\$104.59	\$309	
	Bagasse & unburned leafy trash (dry tons) to ethanol	29.6	\$42.50	\$1,258	\$85.00	\$2,517	
704	Recovered lignin (dry tons) to energy	5.5	--	--	--	see diesel oil	
705							
706	TOTAL			\$8,835		\$5,989	
707	PROFIT/LOSS PER ACRE						(\$848)

	C	D	E	F	G	H	I	J	K
667	ENERGY VALUES (BTU)	Fiber (ton dry m	#2 Diesel (Bbl)	#6 fuel oil (Bbl)	Coal (ton)	Lignin (ton)	lignin ref		
668	oil & coal ref: USDOE/E	=8400*2000	5900000	6300000	21000000	=(9111+10620+113	=C209	PRODUCING SUGAR, BAG	
669	Efficiency of conversion	0.65	0.82	0.82	0.82	=G669	<-(lignin: est.)		
670	Assumed reduction in r	0.04	Factors (Bbl or ton	Total cost per wet ton prep	Field costs =	% of total	Field costs per wet to	Factory costs	SCENARIO
671	ETHANOL \$/GALLON	1.3	V	=D758	=H932		=F671*G671	=F671*(1-G67	MATERIAL
672	#2 DIESEL (BARREL)	=E279	=(D668*D669)/(E66	(from Big Island plantation					SUGAR INDUSTRY PRODU
673	#6 FUEL OIL (BARREL)	16	=(D668*D669)/(F66						Prepared Cane (wet tons)
674	COAL (TON)	=E281	=(D668*D669)/(G66	Million kWh generated by s	=AF35	Est. avg. retail value	Est. avg. whole	Leaves & tops (wet tons) not	0
675	LIGNIN (TON)	--	=(D668*D669)/(H66			=H677+H678+H679		Sucrose (dry tons)	=(H5+H6)/(D5+D6)
676	Reduction factor for pro	0.5				Weighted factors	=AK43	Bagasse (wet tons)	=(O5+O6)/(D5+D6)
677	1991 avg. residential el	Kauai	0.13571	=AE48	=AF48	=E677*G677	=(I676/H675)*	Molasses (wet tons)	=(I5+I6)/(D5+D6)
678	1991 Oahu \$/kWh	Oahu	0.09354	=AE58	=AF58	=E678*G678	=(I676/H675)*		
679	1991 Maui (Island) \$/kWh	Maui Island	0.1237	=AE53	=AF53	=E679*G679	=(I676/H675)*		
680	1991 Hawaii \$/kWh	Hawaii	0.13857	=AE41	=AF41	=E680*G680	=(I676/H675)*		
681								TOTAL	
682								PROFIT/LOSS PER ACRE	
683	=J670	=C713	=E713					=C683	=C714
684	=J671	=K671	=L671	=M671	=N671	=O671	=P671	=C684	=D684
685	=J672							=C685	
686	=J673	=K673	=L673	=M673				=C686	=D686
687	=J674	=W140	=H276*W141	=E687*D687	=W141*AK52*D676*I676	=D687*G687		=C687	=D687
688	=J675	=K675*(1-D670	=F688/D688	=M675	=N675	=D688*G688		=C688	=D688
689	=J676	=K676	=L676	=M676	=N676	=D689*G689		=C689	=D689
690	=J677	=K677	=L677	=M677	=N677	=D690*G690		=C677	=F677
691									
692									
693	=J680			=SUM(F686:F691)		=SUM(H686:H691)		=Q680	
694	=J681						=H693-F693	=Q681	
695									
696	=AE683	=C718	=E718					=AE683	=C719
697	=AE684	=AF684	=AG684	=AH684	=AI684	=AJ684	=AK684	=AE684	TONS (BBLs)/ACRE
698	=AE685							=AE685	
699	=AE686	=AF686	=AG686	=AH686	=AI686	=D689*G689		=AE686	=AF686
700	=AE687	=AF687	=AG687	=AH687	=AI687	=D700*G700		=AE687	=AF687
701	=AE675	=D688	=E688	=AH675	=AI675	=D701*G701		=AE688	=AF688
702	=AE689	=AF689	=AG689	=AH689	=AI689	=AJ689		Bagasse (wet tons) (replaced	=(K676*U141)-(K705/E
703	=AE690	=AF690	=AG690	=AH690	=AI690	=D703*G703		=AE690	=AF690
704	=AE691	=AF691	=AG691	=AH691	=AI691	=D704*G704		=AE691	=AF691
705	=AE692	=AF692	=AG692	=AH692	=AI692	=AJ692		=AE692	=AF692
706	=AE693			=SUM(F699:F705)		=SUM(H699:H705)		=AE693	
707	=AE694						=H706-F706	=AE694	
708	SCENARIOS	Island assumed						=P671	RESULTS OF NUMBER

	L	M	N	O	P	Q	R	S	T	U	V	W
667												
668						PRODUCING SUG						
669						AND ETHANOL						
670	=E709					=J670	=C710	=E710				
671	COST PER TON	COST PER ACRE	VALUE PER	VALUE PER ACRE	PROFIT / LOSS	=J671	=K671	=L671	=M671	=N671	=O671	=P671
672						=J672						
673	=H671	=K673*L673				=J673	=K673	=L673	=M673			
674						=J674	=K674	=L674	=M674			
675	=I671*(K673/K675)	=G263	=AK38	=K675*N675		=J675	=K675	=L675	=M675	=N675	=R675*U675	
676			=U141*(A	=N676*K676		=J676	=K676	=L676	=M676	=N676	=R676*U676	
677			=B99	=K677*N677		Molasses (wet tons)	=K677	=H659*V164	=S677*R677	=O671*V164	=R677*U677	
678												
679												
680		=SUM(M673:M678)		=SUM(O673:O678)		=J680			=SUM(T673:T678)		=SUM(V673:V678)	
681					=O680-M680	=J681						=V680-T680
682												
683	=E714					=C683	=C715	=E715				
684	=E684	=F684	=G684	=H684	=I684	=C684	=D684	=E684	=F684	=G684	=H684	=I684
685						=C685						
686	=E686	=F686				=C686	=D686	=E686	=F686			
687	=E687	=F687	=G687	=H687		Unburned leafy tras	=D687	=E687	=F687			
688	=E688	=F688	=G688	=H688		=C688	=D688	=E688	=F688	=G688	=R688*U688	
689	=E689	=F689	=G689	=H689		=C689	=D689	=E689	=F689	=G689	=R689*U689	
690	=S677	=T677	=U677	=V677		=C690	=D690	=E690	=F690	=G690	=R690*U690	
691						Unburned leafy tras	=R687*W141	=N357*W165	=S691*R691	=W165*D671	=R691*U691	
692						=AE679	=R691*U146			=AK52/E675)*I676	=R692*U692	
693		=SUM(M686:M691)		=SUM(O686:O691)		=C693			=SUM(T686:T692)		=SUM(V686:V692)	
694					=O693-M693	=C694						=V693-T693
695												
696	=E719					=J696	=C720	=E720				
697	COST PER TON (BBL)	=AH684	=AI684	=AJ684	=AK684	=J697	=K697	=L697	=M697	=N697	=O697	=P697
698						=J698						
699	=AG686	=AH686				=J699	=K699	=L699	=M699			
700	=AG687	=AH687				=J700	=K700	=L700	=M700			
701	=AG688	=AH688	=AI688	=K701*N701		=C701	=D701	=E701	=F701	=G701	=R701*U701	
702	=D673	=L702*K702	=AI689	=O676/I676)*I679		=J702	=K702	=L702	=M702	=N702	=O702	
703	=AG690	=AH690	=AI690	=K703*N703		=J703	=K703	=L703	=M703	=N703	=R703*U703	
704	=AG691	=AH691	=G704	=K704*N704		=J704	=K704	=L704	=M704	=N704	=R704*U704	
705	=AG692	=AH692	=AI692	see fuel oil		=J705	=K705	=L705	=M705	=N705	=O705	
706		=SUM(M699:M705)		=SUM(O699:O705)		=J706			=SUM(T699:T705)		=SUM(V699:V705)	
707					=O706-M706	=J707						=V706-T706
708	GALLONS ETHANOL PRODU											

	X	Y	Z	AA	AB	AC	AD	AE	AF	AG	AH	AI	AJ
667													
668	PRODUC							PRODUCI					
669	AND ETH							ETHANOL					
670	=Q670	=C711	=E711					=X670	=C712	=E712			
671	=Q671	=R671	=S671	=T671	=U671	=V671	=W671	=X671	=Y671	=Z671	=AA671	=AB671	=AC671
672	=Q672							=X672					
673	=Q673	=R673	=S673	=T673				=X673	=Y673	=Z673	=AA673		
674	=Q674	0						=X674	0				
675	=Q675	=R675	=S675	=T675	=U675	=V675*AB675		Sucrose to	=Y675	=(T99*V99)	=AG675*AF675	=(T99*V99)+(U99*	=AF675*AI675
676	Bagasse	=(K676*U141)	=D674	=Z676*Y676		=(O676/I676)*I678		=X676	=Y676	=Z676	=AA676	=AB676	=AC676
677	=Q677	=R677	=S677	=T677	=U677	=V677*AB677		=X677	=Y677	=Z677	=AA677	=AB677	=AF677*AI677
678	Bagasse	=K676*U141	=N357*U1	=Z678*Y678	=U165*D671	=AB678*Y678		=X678	=Y678	=Z678	=AA678	=AB678	=AI678*AF678
679	Recovere	=Y678*U146				see coal		=X679	=Y679	=Z679	=AA679	=AB679	=AC679
680	=Q680			=SUM(AA673:AA679)		=SUM(AC673:AC679)		=X680			=SUM(AH673:AH679)		=SUM(AJ673:AJ679)
681	=Q681						=AC680-AA680	=X681					
682													
683	=Q683	=C716	=E716					=X683	=C717	=E717			
684	=Q684	=R684	=S684	=T684	=U684	=V684	=W684	=X684	=Y684	=Z684	=AA684	=AB684	=AC684
685	=Q685							=X685					
686	=Q686	=R686	=S686	=T686				=X686	=Y686	=Z686	=AA686		
687	=Q687	=R687	=S687	=T687				=X687	=Y687	=Z687	=AA687		
688	=Q688	=R688	=S688	=T688	=U688	=V688*AB688		=X688	=Y688	=Z688	=AA688	=AB688	=AF688*AI688
689	=Q689	=R689	=S689	=T689	=U689	=V689*AB689		=X689	=Y689	=Z689	=AA689	=AB689	=AC676
690	=Q690	=R690	=S690	=T690	=U690	=V690*AB690		=X690	=Y690	=Z690	=AA690	=AB690	=AF690*AI690
691	=Q691	=R691	=S691	=T691	=U691	=V691*AB691		Bagasse &	=(D687*W141)	=(W165*F	=AG691*AF691	=AC691/T357*D67	=AF691*AI691
692	=Q692	=R692	=S692	=T692	=U692	=V692		=X692	=Y692	=Z692	=AA692	=AB692	=AC679
693	=Q693			=SUM(AA686:AA691)		=SUM(AC686:AC691)		=X693			=SUM(AH686:AH692)		=SUM(AJ686:AJ692)
694	=Q694						=AC693-AA693	=X694					
695													
696	=J696	=C721	=E721					=Q696	=C722	=E722			
697	=J697	=K697	=L697	=M697	=N697	=O697	=P697	=Q697	=R697	=S697	=T697	=U697	=V697
698	=J698							=Q698					
699	=J699	=K699	=L699	=M699				=Q699	=R699	=S699	=T699		
700	=J700	=K700	=L700	=M700				=Q700	=R700	=S700	=T700		
701	=J701	=K701	=L701	=M701	=N701	=O701*AB701		=Q701	=R701	=S701	=T701	=U701	=AF701*AI701
702	Bagasse	=(K676*U141)	=D672	=Z702*Y702	=N702	=(O676/I676)*I677		=X702	=Y702	=Z702	=AA702	=AB702	=AC702
703	=J703	=K703	=L703	=M703	=N703	=O703*AB703		=Q703	=R703	=S703	=T703	=U703	=AF703*AI703
704	=J704	=K704	=L704	=M704	=N704	=O704*AB704		=Q704	=R704	=S704	=T704	=U704	=AF704*AI704
705	=J705	=K705	=L705	=M705	=N705	see diesel oil		=Q705	=R705	=S705	=T705	=U705	=AC705
706	=J706			=SUM(AA699:AA705)		=SUM(AC699:AC705)		=Q706			=SUM(AH699:AH705)		=SUM(AJ699:AJ705)
707	=J707						=AC706-AA706	=Q707					
708													

	AK
667	
668	
669	
670	
671	-AD671
672	
673	
674	
675	
676	
677	
678	
679	
680	
681	-AJ680-AH680
682	
683	
684	-AD684
685	
686	
687	
688	
689	
690	
691	
692	
693	
694	-AJ693-AH693
695	
696	
697	-W697
698	
699	
700	
701	
702	
703	
704	
705	
706	
707	-AJ706-AH706
708	

	C	D	E	F	G	H	I	J	K	L
	SCENARIOS	Island assumed						PROFIT / LOSS PER ACRE	RESULTS OF NUMBERED SCENARIO RUNS: \$/HARVESTED ACRE INCREASE OR DECREASE COMPARED TO BASELINE	GALLONS ETHANOL PRODUCED PER ACRE
708										
709	BASELINE	State average	SUGAR COMPANY HARVESTING W/OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE AND MOLASSES (BUSINESS-AS-USUAL)					\$769	\$0	0
710	2	State average	SUGAR COMPANY HARVESTING W/OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, AND ETHANOL (MOLASSES TO ETHANOL)					\$853	\$84	237
711	3	Oahu	SUGAR COMPANY HARVESTING W/OPEN FIELD BURNING; PRODUCING SUGAR AND ETHANOL; BAGASSE VALUED AT COAL PRICE (BAGASSE AND MOLASSES TO ETHANOL)					\$1,485	\$716	1,936
712	4	Oahu	SUGAR COMPANY HARVESTING W/OPEN FIELD BURNING; PRODUCING ETHANOL; BAGASSE VALUED AT COAL PRICE (SUGAR, BAGASSE, AND MOLASSES TO ETHANOL)					(\$214)	(\$984)	3,924
713	5	State average	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH (LEAFY TRASH USED FOR ELECTRICITY GENERATION)					\$453	(\$316)	0
714	6	State average	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, LEAFY TRASH (TO ELECTRICITY), AND ETHANOL (MOLASSES TO ETHANOL)					\$537	(\$232)	237
715	7	State average	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, MOLASSES, AND ETHANOL (UNBURNED LEAFY TRASH TO ETHANOL)					\$912	\$143	735
716	8	State average	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR, BAGASSE, AND ETHANOL (MOLASSES AND UNBURNED LEAFY TRASH TO ETHANOL)					\$870	\$101	973
717	9	Oahu	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR AND ETHANOL; BAGASSE VALUED AT COAL PRICE (BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)					\$950	\$181	2,174
718	10	Oahu	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING ETHANOL; BAGASSE VALUED AT COAL PRICE (SUGAR, BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)					(\$678)	(\$1,447)	4,082
719	11	Maui	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR AND ETHANOL; BAGASSE VALUED AT #6 FUEL OIL PRICE (BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)					\$1,149	\$379	2,174
720	12	Maui	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING ETHANOL; BAGASSE VALUED AT #6 FUEL OIL PRICE (SUGAR, BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)					(\$479)	(\$1,249)	4,082
721	13	Kauai/ Hawaii	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING SUGAR AND ETHANOL; BAGASSE VALUED AT #2 DIESEL PRICE (BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)					\$782	\$13	2,174
722	14	Kauai/ Hawaii	SUGAR COMPANY HARVESTING WITHOUT OPEN FIELD BURNING; PRODUCING ETHANOL; BAGASSE VALUED AT #2 DIESEL PRICE (SUGAR, BAGASSE, MOLASSES, AND UNBURNED LEAFY TRASH TO ETHANOL)					(\$846)	(\$1,615)	4,082

	C	D	E	F	G
743	CONSTANTS				
744	Lbs/ton	2,000	2,000		
745	Lignin BTU/pound (dry)	10,357			
746	BTU/kWh (theoretical)	3,412			
747	Oil (BTU/No.6 barrel)	6,300,000			
748	Hours per year	8760			
749					
750					
751	GENERAL SUGAR PARAMETERS	PREPARED CANE PER HARVESTED ACRE	BAGASSE PER HARVESTED ACRE		
752					
753	Crop Production time (years)	2.23	2.23		
754	Wet tons/harv. acre	123.04	37.20	'85 (avg. yr)	
755	Prep cane cost per harv. acre (field & prep)	\$3,585.36		'91, 2 Bl plantns HCPC & Kau	
756	Prep cane cost/ton after washing (wet weight)	\$29.14			
757	Total cost per harv. acre (plus factory, etc.)	\$4,732.98			
758	Total cost/ton (wet weight)	\$38.47			
759	Dry Wgt (%)	28%	52%		
760	Dry weight (tons/harv. acre)	34.46	19.35		
761	Prep cane cost/ton (dry weight)	\$104.06			
762	Yield (dry tons/harvested acre)	34.46	19.35		
763	Sucrose (% dw)	43%	3%		
764	Sucrose (total dry tons/harvested acre)	14.67	0.58	includes non-recovered sucrose	
765	Sugar Sales Price (\$ per ton)	\$360.00		'91 price	
766	Sugar Production Cost (\$ per ton)	\$389.31		'91 prices; '85 (avg. yr) tonnage	
767	Bagasse Fiber (dry tons/harv acre)	18.77	18.77		
768	Bagasse % Dry Weight	52%	52%		
769	Bagasse Wet tons / harv acre	37.20	37.20		
770	Bagasse Value (\$/wet ton)		\$16.00		
771	Molasses from Prepared cane (tons/acre)	2.95		'85 (avg. yr)	
772	Molasses value (\$/ton)	\$40.00			
773	Sugar Content of molasses	60%			
774	Sugar in molasses tons/acre	1.78			
775	Sucrose produced/tons harv acre	12.16	0.58	Sucrose in prep cane column = marketable	
776	Cellulose (% dw in prepared cane)	22%	38%		
777	Hemicellulose (% dw in prepared cane)	16%	27%		
778	Lignin (% dw in prepared cane)	11%	20%		
779	Cellulose (tons/harvested acre)	7.52	7.35		
780	Hemicellulose tons/harv acre	5.34	5.22		
781	Lignin tons/harvested acre	3.96	3.87		
782	Glucose (tons/harvested acre)	14.51	8.27		
783	Fructose (tons/harvested acre)	6.37	0.30		
784	Xylose (tons/harvested acre)	4.25	4.15		
785	FERMENTABLE SUGARS POT. (tons/harv acre)	25.13	12.73		
786	SUGAR-ANNUAL POTENTIAL (tons/acre/year)	11.29	5.72		
787	TONS SUGARS/DRY TON BIOMASS	0.73	0.66		
788	Ethanol tons /ton sugar (theoretical)	0.50	0.50		
789	Ethanol (pounds/gal)	6.58	6.58		
790	Potential ethanol (tons/harv acre)	12.56	6.36		
791	Potential ethanol (gallons/harv acre)	3,819	1,934		
792	Estimated ethanol (gallons/harv acre)	0	0		
793	TOTAL ethanol theoretical pot. (gal/harv acre)	3,819	1,934		
794	Sucrose to ethanol-conversion efficiency	97%	97%		
795	Converted sugars-conversion efficiency	65%	65%		
796	Estimated ethanol, w/convers. effic. (gal/harvested acre)	3,499	1,674		
797	Estimated ethanol w/convers. effic. (gal./ton form sugars)	139.22	131.56		
798	Ethanol potential, w/convers. effic. (gal./acre/year)	1,572	752		
799	Ethanol gal/wet ton processed	28.44	45.01		
800	Ethanol gal/dry ton processed	101.54	86.55		
801	Ethanol Sales Price per gallon	\$0.90	\$0.90		
802	Efficiency of oil to steam	82%			
803	Btu steam per bbl #6 oil	5,166,000			
804	BTU/lb steam (600 psi-750°F)	1,425			
805	Lbs steam (600 psi-750°F) produced per Bbl #6 oil	3,625			
806	Btu in steam required to produce 1 kWh	8250		derived from Pioneer Mill	
807	lbs steam to produce 1 kWh	5.79			
808	kWh per Bbl oil	626.1818182			
809	Electricity Generation Cost /kWh	\$0.037			
810	Payment from utility for electricity/kWh	\$0.05			
811	Yields /ton prepared cane(wet)				
812	DA 96 sugar (tons /ton prep cane)	0.10			
813	Bagasse wet tons /ton prep cane	0.30			
814	Lignin tons /ton prep cane	0.03			
815	ethanol gal /ton prep cane (w/convers. effic.)	28.44			
816	Btus from bagasse in 1 ton prep cane	2,562,313			
817	Energy Required For Factory Operations				
818	Tons Prepared Cane Processed Per Hour (tons)	325		Charly's 1990 cogen report, Hamakua diag.	

	C	D	E	F	G
819	Energy Available From Burning Lignin:				
820	Pounds of Lignin/ton prep cane	64.33			
821	BTU's per Pound of Lignin	10,357			
822	BTU's from Lignin/ton prep cane (Btu's)	666,313			
823	BTU Production From Lignin Per Hour (Btu's)	216,551,651			
824	Lbs of Steam From Lignin Per Hour (lbs)	124,595			
825	kWh's from lignin/ton prep cane (kWh)	66			
826	Energy Available From Burning Bagasse:				
827	BTU from Bagasse/ton prep cane (Btu's)	2,562,313			
828	BTU Production From bagasse Per Hour (Btu's)	832,751,637			
829	Lbs of Steam (600 psi-750°F) From Bagasse Per Hour (lbs)	379,800			
830	Energy Production (in kWh equiv) (kWh)	65,611			
831	Energy prod. (in kWh equiv)/ton prep cane (kWh)	202			calculated from above
832	kWh per ton prep cane	78	from cell \$D\$838		
833	kWh for sale per ton prep cane	54	from cell \$D\$837		from HSPA reports
834	Steam (600 psi-750°F) Req'd For Operations (lbs/hr)	379,800			Charly's 1990 cogen rept
835	Baseline reported total Btus in steam, per yr	2,309,000,000,000	20		hours per day
836	Baseline, reported kWh used, kWh/yr	27,630,000	311		days per year
837	Baseline, reported kWh sold, kWh/yr	62,060,000			Hamakua 1991
838	Baseline, reported kWh total per year	89,690,000			Hamakua 1991
839	Baseline, est Btus in steam used for electricity/yr	739,942,500,000			
840	Baseline est. steam (600 psi-750°F) production, lbs/yr	2,362,356,000	from cell \$D\$834		
841	Baseline, reported steam (600 psi-750°F) needed, lbs/yr	1,620,130,663	from cell \$D\$835		
842	Baseline, biomass Btus needed, per yr	3,552,307,692,308			
843	Baseline, tons prep cane for biomass Btus, per yr	1,386,368			1991 tons, Hamakua: 1146017
844	Ethanol production via SSF, using bagasse				
845	BTU's Req For SSF Ethanol (Btu's fr. steam per gal eth)	18,058			Stone paper
846	BTU's Req For SSF Ethanol (Btu per ton prep cane)	513,491			
847	Btus from Steam req for SSF ethanol (Btu/hr)	166,884,710			
848	Steam req (lbs/hr) for SSF ethanol per hour	117,096			
849	Steam required (lbs/hr) for normal operation plus SSF	496,896	HNEI COGENERATION IN SUGAR IND		
850	Steam Available From Burning Lignin (lbs/hr)	124,595			
851	Steam Shortage For Overall Plant Operations (lbs/hr)	372,301			
852	Oil Required For Shortfall (bbl/hr)	103			
853	Cost of #6 Oil Per Barrel	\$16.00			
854	Cost of oil to make up factory shortage per hour	\$1,643.36			
855	Cost of Oil Required to Make Up Shortage (\$/ton prep cane)	\$5.06			
856					
857	Electricity Generation, Retrofit Option				
858	Efficiency Rating (Retrofit Option)	21%			
859	Capacity Factor	71%	same as baseline		
860	Gross Electricity Generation Retrofit Option (MW)	35.3			
861	Auxiliary power load (MW)	3.53			
862	Steam production req'd for retrofit electricity generation (Btu/hr)	565,197,560			
863	Increased Btu in steam over baseline (Btu/hr)	23,908,996			
864	Field and Factory Load (MW)	3.5			
865	Net plant power (MW)	28			
866	Annual gross electricity production	219,566			
867	Annual electricity export, kWh	175,839			
868	Tons cane per day for all loads	2,179			
869	Tons cane per day for electricity for sale	1,372			
870	kWh produced for sale per ton prep cane	128			
871					
872	Electricity Generation, Gasifier Option				
873	Efficiency Rating (gasifier Option)	31%		20 hours per day	
874	Capacity Factor	71%		250 days per year	
875	Gross Electricity Generation Retrofit Option (MW)	29.0			
876	Auxiliary power load (MW)	2.83			
877	Steam production req'd for retrofit electricity generation (Btu/hr)	319,187,097			
878	Increased Btu in steam over baseline (Btu/hr)	(222,101,467)			
879	Field and Factory Load (MW)	3.50			
880	Net plant power (MW)	23			
881	Annual gross electricity production	180,380			
882	Annual electricity export, kWh	141,007			
883	Tons cane per day for all loads	1,143.00			
884	Tons cane per day for electricity for sale	775			
885	kWh produced for sale per ton prep cane	181.99			
886					
887					
888					

	C	D	E
741	ASSUMPTIONS FOR THESE PROJECTIONS		
742			
743	CONSTANTS		
744	Lbs/ton	2000	2000
745	Lignin BTU/pound (dry)	=H668/2000	
746	BTU/kWh (theoretical)	3412	
747	Oil (BTU/ No.6 barrel)	=F668	
748	Hours per year	=365*24	
749			
750			
751			
752	GENERAL SUGAR PARAMETERS	PREPARED CANE PER HARVESTED ACRE	BAGASSE PER HARVESTED ACRE
753	Crop Production time (years)	=AA83	=AA83
754	Wet tons/harv. acre	=(E5+E6)/(D5+D6)	=(O5+O6)/(D5+D6)
755	Prep cane cost per harv. acre (field & prep)	3585.36	
756	Prep cane cost/ton after washing (wet weight)	=D755/D754	
757	Total cost per harv. acre (plus factory, etc.)	=D755/H932	
758	Total cost/ton (wet weight)	=D757/D754	
759	Dry Wgt (%)	=(F5+F6)/(E5+E6)	=(P5+P6)/(O5+O6)
760	Dry weight (tons/harv. acre)	=D754*D759	=E754*E759
761	Prep cane cost/ton (dry weight)	=D756/D759	
762	Yield (dry tons/harvested acre)	=D754*D759	=E760
763	Sucrose (% dw)	=Q143	0.03
764	Sucrose (total dry tons/harvested acre)	=D762*D763	=E762*E763
765	Sugar Sales Price (\$ per ton)	=AK38	
766	Sugar Production Cost (\$ per ton)	=(D755/H932)/((H5+H6)/(D5+D6))	
767	Bagasse Fiber (dry tons/harv acre)	=E762-E764	=E760-E764
768	Bagasse % Dry Weight	=E759	=E759
769	Bagasse Wet tons / harv acre	=E754	=E754
770	Bagasse Value (\$/wet ton)		16
771	Molasses from Prepared cane (tons/acre)	=(I5+I6)/(D5+D6)	
772	Molasses value (\$/ton)	=B99	
773	Sugar Content of molasses	=V143	
774	Sugar in molasses tons/acre	=D771*D773	
775	Sucrose produced/tons harv acre	=(H5+H6)/(D5+D6)	=E764
776	Cellulose (% dw in prepared cane)	=Q144	=U144
777	Hemicellulose (% dw in prepared cane)	=Q145	=U145
778	Lignin (% dw in prepared cane)	=Q146	=U146
779	Cellulose (tons/harvested acre)	=D762*D776	=E762*E776
780	Hemicellulose tons/harv acre	=D762*D777	=E762*E777
781	Lignin tons/harvested acre	=D762*D778	=E762*E778
782	Glucose (tons/harvested acre)	=(D775*\$L\$88*\$T\$99)+(D779*\$L\$89*\$S\$99)	=(E775*\$L\$88*\$T\$99)+(E779*\$L\$89*\$S\$99)
783	Fructose(tons/harvested acre)	=D775*\$L\$88*\$U\$99	=E775*\$L\$88*\$U\$99
784	Xylose (tons/harvested acre)	=D780*\$L\$90*\$X\$99	=E780*\$L\$90*\$X\$99
785	FERMENTABLE SUGARS POT. (tons/harv acre)	=SUM(D782:D784)	=SUM(E782:E784)
786	SUGAR-ANNUAL POTENTIAL (tons/acre/year)	=D785/D753	=E785/E753
787	TONS SUGARS/DRY TON BIOMASS	=D785/D760	=E785/E760
788	Ethanol tons /ton sugar (theoretical)	0.5	0.5
789	Ethanol (pounds/gal)	6.58	6.58
790	Potential ethanol (tons/harv acre)	=D785*D788	=E785*E788
791	Potential ethanol (gallons/harv acre)	=D790*D744/D789	=E790*D744/E789
792	Estimated ethanol (gallons/harv acre)	=D791*E792	=E791*E792
793	TOTAL ethanol theoretical pot. (gal/harv acre)	=(D785*D788)*D744/D789	=(E785*E788)*D744/E789
794	Sucrose to ethanol-conversion efficiency	=L94	=L94
795	Converted sugars-conversion efficiency	=L93	=L93
796	Estimated ethanol, w/converts. effic. (gal/harvested acre)	=(D782+D783)*D786*D794/(D784*D788*D795)	=(E782+E783)*E786*E794/(E784*E788*E795)
797	Estimated ethanol w/converts. effic. (gal/ton term sugars)	=D796/D785	=E796/E785
798	Ethanol potential, w/converts. effic. (gal/acre/year)	=D796/D753	=E796/E753
799	Ethanol gal/wet ton processed	=D796/D754	=E796/E754
800	Ethanol gal/dry ton processed	=D796/D762	=E796/E762
801	Ethanol Sales Price per gallon	0.9	0.9
802	Efficiency of oil to steam	=F669	
803	Btu steam per bbl #6 oil	=D747*D802	
804	BTU/lb steam (600 psi-750°F)	1425.19369155403	
805	Lbs steam (600 psi-750°F) produced per BBl #6 oil	=D803/D804	
806	Btu in steam required to produce 1 kWh	8250	
807	lbs steam to produce 1 kWh	=D806/D804	
808	kWh per Bbl oil	=D803/D806	
809	Electricity Generation Cost /kWh	=(E953*C975)-E971/E970	
810	Payment from utility for electricity/kWh	0.05	
811	Yields /ton prepared cane(wet)		
812	DA 96 sugar (tons /ton prep cane)	=D775/D754	
813	Bagasse wet tons /ton prep cane	=D769/D754	
814	Lignin tons /ton prep cane	=D781/D754	
815	ethanol gal /ton prep cane (w/converts. effic.)	=D796/D754	
816	Btus from bagasse in 1 ton prep cane	=(E767/D754)*D668	
817	Energy Required For Factory Operations		
818	Tons Prepared Cane Processed Per Hour (tons)	325	

	C	D	E
819	Energy Available From Burning Lignin:		
820	Pounds of Lignin/ton prep cane	=D814*2000	
821	BTU's per Pound of Lignin	=H668/2000	
822	BTU's from Lignin/ton prep cane (Btu's)	=D820*D821	
823	BTU Production From Lignin Per Hour (Btu's)	=D822*D818	
824	Lbs of Steam From Lignin Per Hour (lbs)	=D823*H669/D804	
825	kWh's from lignin/ton prep cane (kWh)	=D824/D807/D818	
826	Energy Available From Burning Bagasse:		
827	BTU from Bagasse/ton prep cane (Btu's)	=D816	
828	BTU Production From bagasse Per Hour (Btu's)	=D827*D818	
829	Lbs of Steam (600 psi-750°F) From Bagasse Per Hour (lbs)	=D828*D669/D804	
830	Energy Production (in kWh equiv) (kWh)	=D829/D807	
831	Energy prod. (in kWh equiv)/ton prep cane (kWh)	=D830/D818	
832	kWh per ton prep cane	=D838/F37	=from cell "&CELL("address",D838)
833	kWh for sale per ton prep cane	=D837/F37	=from cell "&CELL("address",D837)
834	Steam (600 psi-750°F) Req'd For Operations (lbs/hr)	=288500+83600+7600	
835	Baseline reported total Btus in steam, per yr	=1855000000000+45+000000000	20
836	Baseline, reported kWh used, kWh/yr	=AD37*1000000	311
837	Baseline, reported kWh sold, kWh/yr	=AE37*1000000	
838	Baseline, reported kWh total per year	=D836+D837	
839	Baseline, est Btus in steam used for electricity/yr	=D838*D806	
840	Baseline est. steam (600 psi-750°F) production, lbs/yr	=D834*E835*E836	=from cell "&CELL("address",D834)
841	Baseline, reported steam (600 psi-750°F) needed, lbs/yr	=D835/D804	=from cell "&CELL("address",D835)
842	Baseline, biomass Btus needed, per yr	=D841*D804/D669	
843	Baseline, tons prep cane for biomass Btus, per yr	=D842/D816	
844	Ethanol production via SSF, using bagasse		
845	BTU's Req For SSF Ethanol (Btu's fr. steam per gal eth)	=((8.25+7.83+4.35+0.74)/4)*D746	
846	BTU's Req For SSF Ethanol (Btu per ton prep cane)	=D845*D796/D754	
847	Btus from Steam req for SSF ethanol (Btu/hr)	=D846*D818	
848	Steam req (lbs/hr) for SSF ethanol per hour	=D847/D804	
849	Steam required (lbs/hr) for normal operation plus SSF	=D848+D829	HNEI COGENERATION IN SUGAR IND
850	Steam Available From Burning Lignin (lbs/hr)	=D824	
851	Steam Shortage For Overall Plant Operations (lbs/hr)	=D849-D850	
852	Oil Required For Shortfall (bbl/hr)	=D851/D805	
853	Cost of #6 Oil Per Barrel	=D673	
854	Cost of oil to make up factory shortage per hour	=D852*D853	
855	Cost of Oil Required to Make Up Shortage (\$/ton prep cane)	=D854/D818	
856			
857	Electricity Generation, Retrofit Option		
858	Efficiency Rating (Retrofit Option)	0.2131	
859	Capacity Factor	=((E836*E835)/(365*24)	same as baseline
860	Gross Electricity Generation Retrofit Option (MW)	35.3	
861	Auxiliary power load (MW)	3.53	
862	Steam production req'd for retrofit electricity generation (Btu/hr)	=D860*1000*D746/D858	
863	Increased Btu in steam over baseline (Btu/hr)	=D862-(D834*D804)	
864	Field and Factory Load (MW)	3.5	
865	Net plant power (MW)	=D860-D861-D864	
866	Annual gross electricity production	=D860*D859*365*24	
867	Annual electricity export, kWh	=D865*E835*E836	
868	Tons cane per day for all loads	2179	
869	Tons cane per day for electricity for sale	=((D746/D858)*D866/(D668*E767/D754)	
870	kWh produced for sale per ton prep cane	=D867/D869	
871			
872	Electricity Generation, Gasifier Option		
873	Efficiency Rating (gasifier Option)	0.31	20
874	Capacity Factor	=((E836*E835)/(365*24)	250
875	Gross Electricity Generation Retrofit Option (MW)	29	
876	Auxiliary power load (MW)	2.83	
877	Steam production req'd for retrofit electricity generation (Btu/hr)	=D875*1000*D746/D873	
878	Increased Btu in steam over baseline (Btu/hr)	=D877-(D834*D804)	
879	Field and Factory Load (MW)	3.5	
880	Net plant power (MW)	=D875-D876-D879	
881	Annual gross electricity production	=D875*D874*365*24	
882	Annual electricity export, kWh	=D880*E835*E836	
883	Tons cane per day for all loads	1143	
884	Tons cane per day for electricity for sale	=((D746/D873)*D881/(D668*E767/D754)	
885	kWh produced for sale per ton prep cane	=D882/D884	
886			
887			

	I	J	K	L	M	N	O	P	Q	R	S
742	ESTIMATED INCOME FROM OPERATIONS PER HARVESTED ACRE						ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE				
743	Prepared Cane to Sugar & Molasses, Bagasse to Electricity (Business As Usual) Scenario 1					Scenario 1	Sugar Company Harvesting With Open Field Burning (Scenario 1A)				
744	Total Cane Costs =					\$38 /wet ton	Sugar Cane Processed To Sugar and Molasses/Bagasse Burned for Electricity (Business As Usual/Conventional Steam Combustion Option)				
745											
746		YIELD	COST OF	VALUE OF	NET VALUE			YIELD	COST OF	VALUE OF	NET
747		tons, kWh	OPERATIONS	PRODUCT	\$ per			KWh or tons	OPERATIONS	PRODUCT	VALUE
748		or gallons	prepared cane	\$ per ton, kWh or gallon	harvested acre			per harvested acre	\$/ton Prep cane	\$/ton or kWh	\$/harv. acre
749	REVENUES						REVENUES				
750	DA96 Sugar (tons/harvested acre)	12.16		\$360.00	\$4,377		96DA Sugar (tons per harvested acre)	12.16		\$360.00	4,377
751	Molasses (tons/harvested acre)	2.95		\$40.00	\$118		Molasses (tons per harvested acre)	2.95		\$40.00	118
752	Ethanol-SF (gals/harvested acre)	0		\$0.90	\$0		Electricity Sales (kWh's/harv. acre)	95,332		\$0.05	4,767
753	Ethanol-SSF (gals/harvested acre)	0		\$0.90	\$0		Total Revenues				\$8,261
754	Electricity sold (kWh/harvested acre)	8,161		\$0.05	\$409		COSTS OF OPERATIONS				
755	TOTAL REVENUES				\$4,804		Prep Cane (wet tons)	123.04			
756	COSTS						Cultivation		\$18.96		(2,332)
757	Prepared Cane (wet tons)	123.04					Harvesting/Hauling		\$3.31		(407)
758	Cultivation		\$18.96		(2,332)		Cleaning/Shredding		\$2.17		(268)
759	Harvesting/Hauling		\$3.31		(407)		Diffusion/Dewatering		\$0.14		(17)
760	Cleaning/Shredding		\$2.17		(268)		Waste Disposal		\$0.15		(18)
761	Diffusion/Dewatering		\$0.29		(36)		Boiling House/Processing		\$1.62		(199)
762	Waste Disposal		\$0.01		(2)		Electricity Production		\$2.69		(331)
763	Boiling House/Sugar Processing		\$1.62		(199)		Other Factory		\$3.40		(418)
764	Ethanol Production (SSF)				0		G&A Costs		\$5.80		(714)
765	Ethanol Production (SF)				0		Total Costs		\$38.25		(\$4,765)
766	Additional Fuel Costs				0		TOTAL INCOME FROM OPERATIONS (per acre)				
767	Electricity production		\$2.69		(331)						\$4,588
768	Other Factory		\$3.40		(418)			YIELD		VALUE	NET VALUE
769	G&A		\$5.80		(714)			gallons		\$ per gal	\$ per
770	TOTAL COSTS OF OPERATIONS		\$38.25		(\$4,765)			or kWh		or kWh	harvested acre
771	TOTAL INCOME FROM OPERATIONS (Per Harvested Acre)				\$187		CREDITS/EXEMPTIONS				
772							DPS Electric Credit	0		0.015	\$0
773		YIELD		VALUE	NET VALUE		Electricity Tax Credits				\$0
774		gallons		\$ per gal	\$ per		TOTAL VALUE WITH CREDITS				\$4,588
775		or kWh		or kWh	harvested acre						
776	CREDITS										
777	Federal Small Producer Credit	0		\$0.10	\$0		Scenario 1B				
778	State Indigenous Fuels Production Cr	0		\$0.00	\$0		ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE				
779							Sugar Company Harvesting With Open Field Burning (Scenario 1B)				
780	Ethanol Tax Credits				\$0		Sugar Cane Processed To Sugar and Molasses/Bagasse Burned for Electricity (Business As Usual/Inclusion of Retrofit Option)				
781	Dedicated Feedstock Electric Credit	0		\$0.015	\$0		Scenario 1B				
782	Electricity Tax Credits				\$0			YIELD	COST OF	VALUE OF	NET
783	TOTAL CREDITS				\$0			KWh or	OPERATIONS	PRODUCT	VALUE
784	TOTAL VALUE WITH CREDITS				\$187			tons	\$/ton Prep cane	\$/ton or kWh	\$/harv. acre
785							REVENUES				
786	Scenario 2					Scenario 2	96DA Sugar (tons per harv. acre)	12.16		\$360.00	4,377
787	ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE						Molasses (tons per harvested acre)	2.95		\$40.00	118
788	Prepared Cane to Sugar & Molasses, Bagasse to Ethanol by SSF, Lignin to Electricity						Electricity Sales (kWh's/harv. acre)	15,769		\$0.05	788
789	Total Cane Costs =					\$38 /wet ton	Total Revenues				\$5,283
790							COSTS OF OPERATIONS				
791		YIELD	COST OF	VALUE OF	NET VALUE		Prepared Cane (tons/harvested acre)	123.04			
792		tons, kWh	OPERATIONS	PRODUCT	\$ per		Cultivation		\$18.96		(2,332)
793		or gallons	prepared cane	\$ per ton, kWh or gallon	harvested acre		Harvesting/Hauling		\$3.31		(407)
794	REVENUES						Cleaning/Shredding		\$2.17		(268)
795	DA96 Sugar (tons/harvested acre)	12.16		\$360.00	\$4,377		Diffusion		\$0.14		(17)
796	Molasses (tons/harvested acre)	2.95		\$40.00	\$118		Dewatering		\$0.15		(18)
797	Ethanol-SF (gals/harvested acre)	0		\$0.90	\$0		Waste Disposal		\$0.01		(2)
798	Ethanol-SSF (gals/harvested acre)	1,674		\$0.90	\$1,507		Boiling House/Processing		\$1.62		(199)
799	Electricity (kWh/harvested acre)	8,161		\$0.05	\$409		Electricity Production		\$2.61		(345)
800	TOTAL REVENUES				\$6,411		Other Factory		\$3.40		(418)
801	COSTS OF OPERATIONS						G&A Costs		\$5.80		(714)
802	Prepared Cane (wet tons)	123.04					Total Costs		\$38.37		(\$4,721)
803	Cultivation		\$18.96		(2,332)		TOTAL INCOME FROM OPERATIONS (per acre)				
804	Harvesting/Hauling		\$3.31		(407)						\$561.82
805	Cleaning/Shredding		\$2.17		(268)			YIELD		VALUE	NET VALUE
806	Diffusion/Dewatering		\$0.29		(36)			gallons		\$ per gal	\$ per
807	Waste Disposal		\$0.01		(2)			or kWh		or kWh	harvested acre
808	Boiling House/Sugar Processing		\$1.62		(199)		CREDITS/EXEMPTIONS				
809	Ethanol Production (SSF)		\$7.79		(959)		DPS Electric Credit	0		0.015	\$0
810	Ethanol Production (SF)				0		Electricity Tax Credits				\$0
811	Additional Fuel Costs		\$5.06		(622)		TOTAL VALUE WITH CREDITS				\$562
812	Electricity production		\$2.69		(331)						
813	Other Factory		\$3.40		(418)						
814	G&A		\$5.80		(714)						
815	TOTAL COSTS		\$51.10		(\$6,386)						
816	TOTAL INCOME FROM OPERATIONS (Per Harvested Acre)				\$123						
817		YIELD		VALUE	NET VALUE						
818		gallons		\$ per gal	\$ per						
819		or kWh		or kWh	harvested acre						
820	CREDITS										
821	Federal Small Producer Credit	1,674		\$0.10	\$167						
822	State Indigenous Fuels Production Cr	1,674		\$0.00	\$0						
823											
824	Ethanol Tax Credits				\$167						
825	Dedicated Feedstock Electric Credit	0		\$0.015	\$0						
826	Electricity Tax Credits				\$0						
827	TOTAL CREDITS				\$167						
828	TOTAL VALUE WITH CREDITS				\$291						

	I	J	K	L	M	N	O	P	Q	R	S
829			Scenario 3						Scenario 1C		
830											
831	ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE						ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED ACRE				
832	Prepared Cane to Ethanol by Simple Fermentation, Bagasse to Electricity						Sugar Company Harvesting With Open Field Burning (Scenario 1C)				
833	Total Cane Costs :						Sugarcane Processed To Sugar and Molasses/ Bagasse Burned for Electricity				
834		\$38	/wet ton							Scenario 1C	
835											
836											
837											
838											
839											
840											
841											
842											
843											
844											
845											
846											
847											
848											
849											
850											
851											
852											
853											
854											
855											
856											
857											
858											
859											
860											
861											
862											
863											
864											
865											
866											
867											
868											
869											
870											
871											
872											
873											
874											
875	ESTIMATED INCOME FROM OPERATIONS PER HARVESTED ACRE						ESTIMATED INCOME FROM OPERATIONS PER HARVESTED ACRE				
876	Prepared Cane to Ethanol by SF, Bagasse to Ethanol by SSF, Lignin to Electricity					Scenario 4	Scenario 4				
877	Total Cane Costs :						Total Cane Costs :				
878		\$38	/wet ton								
879											
880											
881											
882											
883											
884											
885											
886											
887											
888											
889											
890											
891											
892											
893											
894											
895											
896											
897											
898											
899											
900											
901											
902											
903											
904											
905											
906											
907											
908											
909											
910											
911											
912											
913											
914											
915											
916											
917											

I	J	K	L	M	N	O	P	Q	R	S
742	ESTIMATED INCOME FROM OPERATIONS					ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED				
743	Prepared Cane to Sugar & Molasses, Bag					Sugar Company Harvesting With Open Field Burning (Scenario 1A)				
744	Total Cane Costs =	-\$05758	/wet ton	Scenario 1		Sugarcane Processed To Sugar and Molasses/Bagasse Burned for (Business As Usual/Conventional Steam Combustion Option)				Scenario 1A
745										
746		YIELD	COST OF	VALUE OF	NET		YIELD	COST OF	VALUE OF	NET
747		tons, kWh	\$ per ton of	\$ per ton, kWh	\$ per		kWh or tons	OPERATIONS	PRODUCT	VALUE
748		or gallons	prepared cane	or gallon	harvested acre		\$/ton Prep cane	\$/ton or kWh	\$/ton or kWh	\$/harv. acre
749	REVENUES					REVENUES				
750	DA96 Sugar (tons/harvested acre)	-\$05775		-\$05765	-\$05765	96DA Sugar (tons per harvested acre)	-\$05775		-\$05765	-\$05765
751	Molasses (tons/harvested acre)	-\$05771		-\$05772	-\$05772	Molasses (tons per harvested acre)	-\$05771		-\$05772	-\$05772
752	Ethanol-SF (gals/harvested acre)	0		-\$05801	-\$05801	Electricity Sales (kWh/harv. acre)	-\$0884*P755		-\$05810	-\$05810
753	Ethanol-SF (gals/harvested acre)	0		-\$05801	-\$05801	Total Revenue				=\$05810
754	Electricity sold (kWh/harvested acre)	-\$05837505		-\$05810	-\$05810	COSTS OF OPERATIONS				=\$05810
755	TOTAL REVENUES				=\$05810	Prep Cane (wet tons)	-\$05754			=\$05810
756	COSTS					Cultivation		-\$05744*G6933		=\$05744*G6933
757	Prepared Cane (wet tons)	-\$05754				Harvesting/Hauling		-\$05744*G6933		=\$05744*G6933
758	Cultivation		-\$05744*G6933		=\$05744*G6933	Cleaning/Shredding		-\$05744*G6941		=\$05744*G6941
759	Harvesting/Hauling		-\$05744*G6933		=\$05744*G6933	Diffusion		-\$05744*G6941		=\$05744*G6941
760	Cleaning/Shredding		-\$05744*G6941		=\$05744*G6941	Dewatering		-\$05744*G6943		=\$05744*G6943
761	Diffusion/Dewatering		-\$05744*G6942		=\$05744*G6942	Waste Disposal		-\$05744*G6943		=\$05744*G6943
762	Waste Disposal		-\$05744*G6943		=\$05744*G6943	Boiling House/Processing		-\$05744*G6949		=\$05744*G6949
763	Boiling House/Sugar Processing		-\$05744*G6949		=\$05744*G6949	Electricity Production		-\$05744*G6949		=\$05744*G6949
764	Ethanol Production (SSF)		-\$05744*G6949		=\$05744*G6949	Other Factory		-\$05744*G6956		=\$05744*G6956
765	Ethanol Production (SF)		-\$05744*G6949		=\$05744*G6949	G&A Costs		-\$05744*G6956		=\$05744*G6956
766	Additional Fuel Costs		-\$05744*G6949		=\$05744*G6949	Total Costs		-\$05744*G6956		=\$05744*G6956
767	Electricity production		-\$05744*G6956		=\$05744*G6956	TOTAL INCOME FROM OPERATIONS (per acre)				=\$05744*G6956
768	Other Factory		-\$05744*G6956		=\$05744*G6956					
769	G&A		-\$05744*G6956		=\$05744*G6956					
770	TOTAL COSTS OF OPERATIONS		-\$05744*G6956		=\$05744*G6956					
771	TOTAL INCOME FROM OPERATIONS (P)				=\$05744*G6956					
772						CREDITS/EXEMPTIONS				
773		YIELD	VALUE	NET		DPS Electric Credit	0			
774		gallons	\$ per gal	\$ per		Electricity Tax Credits		0.015		=\$05744*G6956
775		or kWh	or kWh	harvested acre		TOTAL VALUE WITH CREDITS				=\$05744*G6956
776	CREDITS									
777	Federal Small Producer Credit	-\$05758		0.1	-\$05758					
778	State Indigenous Fuels Production Credit	-\$05758		0	-\$05758					
779						ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED				
780	Ethanol Tax Credits				=\$05758	Sugar Company Harvesting With Open Field Burning (Scenario 1B)				
781	Dedicated Feedstock Electric Credit	0		0.015	-\$05758	Sugarcane Processed To Sugar and Molasses/Bagasse Burned for (Business As Usual/Inclusion of Retired Option)				
782	Electricity Tax Credits				=\$05758					
783	TOTAL CREDITS				=\$05758					
784	TOTAL VALUE WITH CREDITS				=\$05758					
785						REVENUES				
786						96DA Sugar (tons per harv. acre)	-\$05775		-\$05765	-\$05765
787	ESTIMATE OF INCOME FROM OPERATIONS					Molasses (tons per harvested acre)	-\$05771		-\$05772	-\$05772
788	Prepared Cane to Sugar & Molasses, Bag					Electricity Sales (kWh/harv. acre)	-\$0884*P791		-\$05810	-\$05810
789	Total Cane Costs =	-\$05758	/wet ton	Scenario 2		Total Revenue				=\$05810
790						COSTS OF OPERATIONS				
791		YIELD	COST OF	VALUE OF	NET	Prepared Cane (tons/harvested acre)	-\$05754			
792		tons, kWh	\$ per ton of	\$ per ton, kWh	\$ per	Cultivation		-\$05744*G6933		=\$05744*G6933
793		or gallons	prepared cane	or gallon	harvested acre	Harvesting/Hauling		-\$05744*G6933		=\$05744*G6933
794	REVENUES					Cleaning/Shredding		-\$05744*G6941		=\$05744*G6941
795	DA96 Sugar (tons/harvested acre)	-\$05775		-\$05765	-\$05765	Diffusion		-\$05744*G6941		=\$05744*G6941
796	Molasses (tons/harvested acre)	-\$05771		-\$05772	-\$05772	Dewatering		-\$05744*G6943		=\$05744*G6943
797	Ethanol-SF (gals/harvested acre)	0		-\$05801	-\$05801	Waste Disposal		-\$05744*G6943		=\$05744*G6943
798	Ethanol-SF (gals/harvested acre)	0		-\$05801	-\$05801	Boiling House/Processing		-\$05744*G6949		=\$05744*G6949
799	Electricity (kWh/harvested acre)	-\$05837505		-\$05810	-\$05810	Electricity Production		-\$05744*G6949		=\$05744*G6949
800	TOTAL REVENUES				=\$05810	Other Factory		-\$05744*G6956		=\$05744*G6956
801	COSTS OF OPERATIONS					G&A Costs		-\$05744*G6956		=\$05744*G6956
802	Prepared Cane (wet tons)	-\$05754				Total Costs		-\$05744*G6956		=\$05744*G6956
803	Cultivation		-\$05744*G6933		=\$05744*G6933	TOTAL INCOME FROM OPERATIONS (per acre)				=\$05744*G6956
804	Harvesting/Hauling		-\$05744*G6933		=\$05744*G6933					
805	Cleaning/Shredding		-\$05744*G6941		=\$05744*G6941					
806	Diffusion/Dewatering		-\$05744*G6942		=\$05744*G6942					
807	Waste Disposal		-\$05744*G6943		=\$05744*G6943					
808	Boiling House/Sugar Processing		-\$05744*G6949		=\$05744*G6949					
809	Ethanol Production (SSF)		-\$05744*G6949		=\$05744*G6949					
810	Ethanol Production (SF)		-\$05744*G6949		=\$05744*G6949					
811	Additional Fuel Costs		-\$05855		=\$05855					
812	Electricity production		-\$05744*G6956		=\$05744*G6956					
813	Other Factory		-\$05744*G6956		=\$05744*G6956					
814	G&A		-\$05744*G6956		=\$05744*G6956					
815	TOTAL COSTS		-\$05744*G6956		=\$05744*G6956					
816	TOTAL INCOME FROM OPERATIONS (P)				=\$05744*G6956					
817		YIELD	VALUE	NET						
818		gallons	\$ per gal	\$ per						
819		or kWh	or kWh	harvested acre						
820	CREDITS									
821	Federal Small Producer Credit	-\$05758		0.1	-\$05758					
822	State Indigenous Fuels Production Credit	-\$05758		0	-\$05758					
823										
824	Ethanol Tax Credits				=\$05758					
825	Dedicated Feedstock Electric Credit	0		0.015	-\$05758					
826	Electricity Tax Credits				=\$05758					
827	TOTAL CREDITS				=\$05758					
828	TOTAL VALUE WITH CREDITS				=\$05758					

	I	J	K	L	M	N	O	P	Q	R	S
829			Scenario 3						Scenario 1C		
830											
831	ESTIMATE OF INCOME FROM OPERATIONS						ESTIMATE OF INCOME FROM OPERATIONS PER HARVESTED				
832	Prepared Cane to Ethanol by Simple Fermentation						Sugar Company Harvesting With Open Field Burning (Scenario 1C)				
833	Total Cane Costs =						Sugarcane Processed To Sugar and Molasses/ Bagasse Burned for (Business As Usual/Inclusion of Gasifier Option)				
834											
835		YIELD	COST OF	VALUE OF				YIELD	COST OF	VALUE OF	NET
836		tons, kWh	OPERATIONS	PRODUCT	NET VALUE			KWh or	OPERATIONS	PRODUCT	VALUE
837		or gallons	\$ per ton of	\$ per ton, kWh	\$ per			tons	\$/ton Prep cane	\$/ton or kWh	\$/harv. acre
838			prepared cane	or gallon	harvested acre						
839	REVENUES						REVENUES				
840	DA96 Sugar (tons/harvested acre)	0		=\$05765	=L839*J839		96DA Sugar (tons per harv. acre)	=\$05775		=\$05765	=R839*P839
841	Molasses (tons/harvested acre)	=\$05771		=\$05772	=L840*J840		Molasses (tons per harvested acre)	=\$05771		=\$05772	=R839*P839
842	Ethanol-SF (gals/harvested acre)	=O775*J840		=\$06801	=L841*J841		Electricity Sales (kWh/harv. acre)	=\$06851		=\$06810	=R840*P840
843	Ethanol-SSF (gals/harvested acre)	0		=\$06801	=L842*J842		Total Revenues				=SUM(S839:S840)
844	Electricity (kWh/harvested acre)	=\$06837505		=\$06810	=L843*J843						
845	TOTAL REVENUES						TOTAL REVENUES				
846											
847	COSTS OF OPERATIONS						COSTS OF OPERATIONS				
848	Prepared Cane (wet tons/boil)	=\$05754					Prepared Cane (tons/harv. acre)	=\$05754			
849	Cultivation		=\$J5744*G8933		=-(K847*J846)		Cultivation		=\$J5744*G8933		=-(O844*P843)
850	Harvesting/Hauling		=\$J5744*G8938		=-(K848*J846)		Harvesting/Hauling		=\$J5744*G8938		=-(O845*P843)
851	Cleaning/Shredding		=\$J5744*G8941		=-(K849*J846)		Cleaning/Shredding		=\$J5744*G8941		=-(O846*P843)
852	Diffusion/Dewatering		=\$J5744*G8942		=-(K850*J846)		Diffusion		=\$J5744*G8941		=-(O847*P843)
853	Waste Disposal		=\$J5744*G8943		=-(K851*J846)		Dewatering		=\$J5744*G8942		=-(O848*P843)
854	Boiling House/Sugar Processing		=\$J5744*G8949		=-(K852*J846)		Drying		=\$J5744*G8943		=-(O849*P843)
855	Ethanol Production (SSF)				=-(K853*J846)		Waste Disposal		=\$J5744*G8949		=-(O850*P843)
856	Ethanol Production (SF)		=-(K659*H642)*J857		=-(K854*J846)		Boiling House/Processing		=\$J5744*G8949		=-(O851*P843)
857	Additional Fuel Costs				=-(K855*J846)		Electricity Production		=\$J5744*G8953		=-(O852*P843)
858	Electricity production		=K767		=-(K856*J846)		Other Factory		=\$J5744*G8956		=-(O853*P843)
859	Other Factory		=\$J5744*G8956		=-(K857*J846)		G&A Costs		=\$J5744*G8966		=-(O854*P843)
860	G&A		=\$J5744*G8966		=-(K858*J846)		Total Costs		=SUM(O844:O854)		=SUM(S843:S854)
861	TOTAL COSTS						TOTAL COSTS				
862											
863	TOTAL INCOME FROM OPERATIONS (P)						TOTAL INCOME FROM OPERATIONS (per acre)				
864											
865		YIELD		VALUE	NET VALUE			YIELD		VALUE	NET VALUE
866		gallons		\$ per gal	\$ per			gallons		\$ per gal	\$ per
867		or kWh		or kWh	harvested acre			or kWh		or kWh	harvested acre
868	CREDITS/EXEMPTIONS						CREDITS/EXEMPTIONS				
869	Federal Small Producer Credit	=SUM(J841:J844)		0.1	=L865*J865		DFS Electric Credit	=P840			
870	State Indigenous Fuels Production Credit	=SUM(J841:J844)		0	=L866*J866		Electricity Tax Credits			0.015	=R862*P862
871	Ethanol Tax Credits				=SUM(M865:M867)		Total Value With Credits				=S862
872	Dedicated Feedstock Electric Credit	0		0.015	=L867*J869						
873	Electricity Tax Credits				=M869		Summary of ethanol scenarios				
874	TOTAL CREDITS										
875											
876	TOTAL VALUE WITH CREDITS										
877											
878											
879											
880											
881											
882	ESTIMATED INCOME FROM OPERATIONS						ESTIMATED INCOME FROM OPERATIONS				
883	Prepared Cane to Ethanol by SF, Bagasse										
884	Total Cane Costs =	=\$05754	/wet ton								
885											
886											
887											
888											
889											
890											
891											
892											
893											
894											
895											
896											
897											
898											
899											
900											
901											
902											
903											
904											
905											
906											
907											
908											
909											
910											
911											
912											
913											
914											
915											
916											
917											