Methodology for Determining Time-Dependent Mechanical Properties of Tuff Subjected to Near-Field Repository Conditions

J. D. Blacic
R. Andersen

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

METHODOLOGY FOR DETERMINING TIME-DEPENDENT MECHANICAL PROPERTIES OF TUFF SUBJECTED TO NEAR-FIELD REPOSITORY CONDITIONS

by

J. D. Blacic and R. Andersen

ABSTRACT

We have established a methodology to determine the time dependence of strength and transport properties of tuff under conditions appropriate to a nuclear waste repository. Exploratory tests to determine the approximate magnitudes of thermo-mechanical property changes are nearly complete. In this report we describe the capabilities of an apparatus designed to precisely measure the time-dependent deformation and permeability of tuff at simulated repository conditions. Preliminary tests with this new apparatus indicate that micro-clastic creep failure of tuff occurs over a narrow strain range with little precursory Tertiary creep behavior. In one test, deformation under conditions of slowly decreasing effective pressure resulted in failure, whereas some strain indicators showed a decreasing rate of strain.

I. INTRODUCTION

The purpose of this preliminary report is to introduce the topic of time-dependent mechanical properties of tuff and to describe an approach for measuring these properties.

The objectives are listed below.

- (1) Measure deformation of tuff over an extended time at conditions of stress, temperature, confining pressure, and water pore pressure likely to be encountered in a nuclear waste repository. From these exploratory tests, we will determine if the magnitude of strength and mineralogic changes warrants a more extensive set of measurements proposed in (2) and (3) below.

- (2) Measure deformation of tuff over a sufficient range of physical variables to enable the formulation of a constitutive description that can be used in numerical models for design and performance evaluation of a repository. Particular emphasis will be placed on evaluating the possibility of delayed failure in tuff and what controls it.
- (3) A subsidiary goal is to measure the time variation of water permeability in tuff and how it is affected by slow deformation of the rock matrix.

A detailed background discussion of time-dependent microclastic deformation of repository-candidate rocks is given by Blacic¹ and will only be summarized here. The basic problem is that present design and performance calculations for a repository assume that thermomechanical and transport properties for a particular rock are constant over time. These properties are determined by standard, short-time engineering tests that do not examine a possible time dependence. Repository designs are unusual in that they must stand the test of very long term performance. Analysis that does not take into account time effects can lead to erroneous answers. For example, thermal conductivity might decrease over time as a result of slow, progressive microcracking of rock in the near field. Thermal calculations that do not incorporate this effect will underestimate near-field temperatures. Similarly, permeability of tuff is relatively low because of the apparently low connectivity of porosity. This could change substantially over time during slow deformation. Nuclide transport models that do not include this change would overestimate transit times.

A reliable evaluation of the magnitudes of these time phenomena is difficult, principally because of a lack of data. We describe below a two-part experimental approach to obtaining the required data. First we will make a preliminary evaluation of the existence of the time-dependent phenomena in tuff and a rough estimate of their magnitudes. Then, if, based on these results, analysis indicates that more precise measurements are required for design and performance calculations, we will proceed with these measurements.

The first part of our approach is almost complete. An exploratory test was performed in which samples of a variety of tuff types from the southwest part of the Nevada Test Site (NTS) were exposed to a range of temperatures, confining pressures, and water pore pressures for times of 2 to 6 months. A set of thermomechanical properties was measured at ambient conditions before and after this exposure and compared. Preliminary results indicate that

substantial and statistically significant changes occurred in tensile strength, compressive strength, and mineralogic content in some tuff types. Comparisons of data from before and after exposure of thermal conductivity and permeability are currently in progress. Details of this test are given in Ref. 2. Guided by these results, we are in the process of extending the measurements with long-term deformation (creep) tests that should indicate the magnitude of strength change more precisely. A prototype apparatus was designed and constructed for the creep measurements, and a few check-out tests have been performed. Details of the apparatus and the first few tests are given below.

II. DEVELOPMENT OF EXPERIMENTAL EQUIPMENT

Because laboratory data on time dependence of mechanical and transport properties of rock will have to be extrapolated orders of magnitude in time even to encompass the operational time period, rather precise measurements of these properties are required. Physical variables such as temperature and pressure must be controlled, and response measurements must be made over time periods of months. This requires specialized testing equipment not widely available. Consequently, we designed and built a prototype apparatus that incorporates what we believe to be current state-of-the-art capabilities in rock mechanics testing equipment. Considerable effort and time was spent developing the apparatus in order to reduce programmatic risk. If more detailed creep measurements will be required, as now appears to be the case based on the preliminary testing described above, then availability of suitable equipment will reduce time delays in the program. Even so, tests of such long duration over a range of physical conditions and rock characteristics would prevent us from obtaining this information on an accelerated or crash basis.

The apparatus is best described in terms of distinct subsystems. These are (1) differential stress, (2) confining pressure, (3) pore pressure and permeability, and (4) computer control and digital data acquisition systems.

A. Differential Stress Subsystem

The purpose of the differential stress subsystem is to rapidly attain the desired axial differential stress on the test sample and to precisely maintain that value for the duration of the test. The differential stress is applied only after steady values of confining pressure, pore pressure, and temperature

have been achieved. Because of the long duration of the planned tests, it is desirable to have an automated control system so that an operator need not always be present. The computer control and digital data acquisition subsystem is described below. We will describe only the mechanical portion of the subsystem here.

Figure 1 shows the basic components of the subsystem. The jacketed sample is contained in an externally heated pressure vessel and pressurized with silicone oil. Details of the pressure vessel design are discussed below with the description of the confining pressure subsystem. The pressure vessel is mounted within, and axial force is applied by a standard four-post hydraulic load frame. Details of the load frame are not significant; the one we use in the prototype system is capable of generating 500 000 lb of force. The important aspects of the system are how the hydraulic ram pressure is generated and automatically adjusted to maintain a constant differential stress on the test sample (shown in Fig. 2).

The ram is manually advanced or retracted for initial contact or unloading of the sample, respectively, by means of an air/oil pump (P1) actuated through regulator R1 by low-pressure house air. The direction of ram movement is determined by electric solenoid valves SV5 and SV6, and pressures are monitored on gauges G3 and G4. At the beginning of a test, once contact of the sample and the loading piston is made, the manual system is no longer used. High pressure is then applied suddenly to the ram by opening solenoid valve SV1. Before opening SV1, an accumulator (AC) is precharged from a high-pressure gas bottle (B1) through regulator R2 and gauge G2. The accumulator is a bladder type that separates the charging gas from the hydraulic oil. Because there is essentially no friction in this type of accumulator, a differential stress within about 5% of the desired value can be obtained by accurately precharging. This value is rapidly attained at sample strain rates of about 10^{-3} s^{-1} . About 2 seconds after SV1 is opened, automatic trimming of the accumulator gas pressure begins with feedback from an internal force transducer. The internal force gauge consists of a strain gauge with four active arms that is bridge-mounted on a steel end piece between the sample and the loading piston. Differential stress on the sample is calculated from the force gauge signal and the current cross sectional area of the sample that is determined from strain gauges on the sample and the

Fig. 1.
Photograph of the apparatus.

Fig. 2.

The differential stress subsystem. The following symbols are used: V = manual valve, SV = electric solenoid valve, R = regulator, B = bottle, AC = accumulator, RV = relief valve, P = pump, CKV = check valve, and G = gauge.

starting sample dimensions. The current stress is compared to the desired value and any difference controls the action of the control loop.

The actuator part of the control loop consists of solenoid valves SV2, SV3, SV4; regulator R3; manual throttling valve V3; and bottle B2. Valves SV2, SV3, and SV4 are normally closed. If, for example, an increment of pressure is required to increase the stress towards the desired value, SV2 is momentarily opened and then closed, trapping a small volume of gas in B2 at a pressure (determined by R3) higher than that in the accumulator. This increment of pressure is then injected by opening and closing SV3. To lower the applied stress, the reverse process takes place, venting an increment from the accumulator through SV4 and V3. This trimming process is under complete computer control, the details of which are described in Sec. II.D. Typically, the system is capable of maintaining a differential stress on the sample with about 0.25% precision.

B. Confining Pressure Subsystem

A schematic of the confining pressure subsystem is shown in Fig. 3. Various pressure vessels may be used in this subsystem. The one we most commonly use accepts an NX size sample (5.4 cm in diameter) and is capable of 70

Fig. 3.

Schematic of the confining pressure subsystem. The following symbols are used: B = bottle, V = manual valve, R = regulator, G = gauge, and X = pressure transducer.

MPa (10 000 psi) pressure and 250°C using external band heaters. Electrical feed-throughs for up to 40 signals are provided for internal instrumentation of the sample. These normally consist of three pairs of axial and circumferential strain gauges mounted at 120° intervals around the sample, three axial LVDT displacement transducers mounted on steel buttons that are epoxied to the sample and rotated 60° from the strain gauges, three or four thermocouples at different heights along the sample, and the internal force transducer. The rock sample is isolated from the confining pressure medium (DOW 710 silicone oil) by an RTV silastic or other barrier painted on the sample or by a viton rubber jacket. In the latter case, strain gauges or LVDT buttons cannot be mounted directly on the sample surface. Sample pore pressure access is through the sample pedestal and a hollow upper end cap.

Primary confining pressure is generated by a 15:1 piston intensifier actuated by compressed gas through regulator R1. Once pressure is attained, this system is valved off, and fine control is obtained by means of an automated, screw-driven intensifier. Pressure is measured by one of several strain gauge pressure cells, depending on pressure range and Bourdon tube gauges. The motor-driven screw intensifier is computer controlled using a feedback signal from one of the pressure transducers. By adjusting motor speed and transducer sensitivity, pressure can be controlled to within a few

pounds per square inch over long time periods. At large sample strains, screw piston displacement can be measured to obtain sample volume strain using the method described by Wawersik.³

C. Pore Pressure and Permeability Subsystem

A schematic of the pore pressure subsystem is shown in Fig. 4. Initial water pore pressure is obtained by means of an air/water pump after first evacuating the sample and pressure lines. Once pressure is attained, the pump is valved off, and fine control is obtained by actuating a bladder-type accumulator with compressed gas. This system is sufficient for long-term control of pore pressure within about 2%. For finer control required for permeability determinations, one or the other of two subsystems is used. At permeabilities above about 1 mdarcy, the sample is isolated with a Constametric-brand liquid chromatograph pump. This pump is capable of generating constant flow rates of 0.1 to 10 mL/min at line pressures up to 40 MPa. At a given flow rate, the pressure drop across the sample is measured by a differential pressure transducer (X2) to an accuracy of 0.25%. The permeability is then calculated from Darcy's equation for viscous flow through a porous medium as

$$k = \mu v L / \Delta P,$$

where k is permeability, μ is the viscosity of water, v is the volume flow rate per unit time per unit cross sectional area, and ΔP is the pressure drop over a sample of length L .

At very low permeabilities, flow rates are too low for any reasonable pressure drop and so a relaxation method is used. The method is that described by Brace et al.⁴ in which a pressure step is applied to the sample, and the exponential decay of pressure is recorded from the differential pressure gauge. Permeability is then related to the pressure decay constant, α , by the equation

$$k = \frac{\alpha \beta \mu L V_2 V_1}{A(V_2 + V_1)},$$

where k is permeability, α is the decay constant, β is the isothermal compressibility of water, μ is the dynamic viscosity of water, L is the sample length, A is the sample cross sectional area, and V_1 and V_2 are the volumes of pore fluid reservoirs at the two ends of the sample. The pressure step can be applied in a number of ways. For automated measurements in which the mean

Fig. 4.

The pore pressure and permeability system. The following symbols are used: B = bottle, R = regulator, V = manual valve, SV = electric solenoid valve, VP = vacuum pump, P = pump, G = gauge, S = test sample, F = filter, M = motor, X = pressure transducer, and DX = differential pressure transducer.

pore pressure is constant, a motorized, double-acting piston pump may be used. The pressure difference is produced by advancing the piston in one direction or the other and then opening solenoid valves SV2 and SV4 to suddenly apply the pressure step to the sample. A simpler method of applying a pressure step is to suddenly turn the stem of valve V5.

D. Computer Control and Digital Data Acquisition Subsystem

A block diagram of the computer control and digital data acquisition system is shown in Fig. 5. The principal component of this system is a Digital Equipment Corporation LSI-11 microcomputer and flexible disk system. The computer performs the following functions.

- (1) Control Differential Stress. The computer gathers force, confining pressure, and circumferential strain values from the internal load cell, pressure transducer, and sample-mounted strain gauges, respectively. This information is used to calculate the current value of the true differential stress on the test sample. The computer will then actuate a valve sequence to adjust the force so as to maintain the differential stress at the desired level, as described above.

Fig. 5.

Diagram of computer control and digital data acquisition system.

- (2) Control Confining Pressure. Feedback from the confining pressure transducer is used in a process to actuate a motor-driven pressure intensifier and maintain a desired level of pressure. Priority of confining pressure control is lower than that of differential stress. In practice, interaction between the two systems is minimal enough to avoid instability in the overall control process.
- (3) Acquire Data. The computer is continually acquiring raw data from the various transducers and storing this information on a floppy disk for postprocessing. There is a real-time display of selected test variables on a computer graphics terminal to help monitor the status of the test. The rate at which data is collected and the number of data channels used is set by the operator.

A 32-channel signal conditioner module can provide excitation, balance, and amplification for transducers, strain gauges, etc. The module, which incorporates the ability to shunt-calibrate strain gauges, has a digital voltmeter to aid setting gain and offset balancing.

A 16-channel valve-switch module and a 16-bit input/output card located in the LSI-11 computer provide the capability of opening or closing any of the

solenoid valves in the control system. The switch module also contains the power supply necessary to operate the solenoids.

The unit that controls the motor speed also controls the direction and speed of the confining pressure intensifier. The unit can be operated locally or automatically by the computer. Two channels of the valve-switch module are used by the computer to control the direction and time that the intensifier is actuated.

An analog temperature controller is used to control band heaters mounted on the pressure vessel. Feedback is obtained from platinum RTD temperature sensors, and their values are acquired by the computer for postprocessing.

Software for the system is stored on a separate floppy disk. A flow diagram of the control and data acquisition program is shown in Fig. 6, and a Fortran listing is provided in the Appendix.

E. Results of Preliminary Experiments

A few room-temperature, uniaxial creep tests were performed primarily to check out the operation of the differential stress system and the computer control and data acquisition programs. We selected samples of Grouse Canyon welded tuff from G-tunnel that were reputed to be from the same block tested by Olsson and Jones⁵ of Sandia National Laboratories (SNL). According to the SNL data, this tuff should have a uniaxial compressive strength of 180 MPa. Consequently, the first test was planned for a differential stress of 100 MPa and ambient confining pressure and temperature. Under these conditions, creep deformation lasting at least 6 weeks was anticipated. However, the sample failed catastrophically as soon as the stress was applied.

Before a second test on this tuff, some uniaxial, constant-displacement-rate tests were performed to verify the expected failure strength. At a strain rate of about 10^{-4} s^{-1} , samples with diameters of 1.25 and 2.5 cm failed at stresses ranging from 65 to 180 MPa (Fig. 7). The weakest sample contained a fragment of pumice that apparently also acted as a weak zone in the 5.4-cm-diam creep test sample. Consequently, the sample selected for the second creep test did not contain any pumice fragments visible at the surface.

In the second test, a differential stress of 75 MPa was applied and held for 5 days (Fig. 8). The load control system worked well. Some minor problems in the data acquisition systems were identified and subsequently corrected. As can be seen in Fig. 8, there was a very low rate of creep in the axial direction. In the last few days of the test, the average strain rate

Fig. 6.
Flow diagram of test control and data acquisition program.

Fig. 7.

Uniaxial stress-strain curves for Grouse Canyon welded tuff at 25°C. A and B are 0.5-in.-diam cylindrical samples and C and D are 1-in.-diam samples.

was $\sim 7 \times 10^{-10} \text{ s}^{-1}$. Most of the axial strain was recovered immediately upon unloading; the remaining amount was recovered within a few days. This observation leads us to believe that the creep strain was due to slow closing of pre-existing cracks preferentially oriented perpendicular to the principal stress direction (also, no new cracks were produced). Therefore, because we believed the sample was not damaged, we decided to reload it at a higher stress level. The sample was loaded to 100 MPa, which again should have been well below the short-time failure strength if no weak zones were present.

However, this sample again failed immediately as the higher stress was applied. Figure 9 shows the first few seconds of the test. Comparison of Fig. 8 and 9 illustrates the wide dynamic range of our digital data acquisition system and the short risetime of the stress application. The comparison also shows that at 75 MPa, the strains are the same as in the earlier loading to 75 MPa, and only a small increase in strain from this level

Fig. 8.

Axial and circumferential creep strain vs time for Grouse Canyon welded tuff. Uniaxial stress is 75 MPa and temperature is 25°C.

resulted in unstable conditions and failure. In the case of the circumferential strain, which is the most sensitive indicator of crack formation in a uniaxial test, the strain increased from a stable level of 0.8×10^{-3} to an unstable level of 1.1×10^{-3} within 1 second after the 75-MPa level was exceeded. The volume strain (axial minus twice the circumferential strain) at the end of the first loading was approximately 1.9×10^{-3} . The volume strain at the beginning of failure in the second loading was about 2.4×10^{-3} and rapidly decreasing as a result of dilatant crack formation (Fig. 9). In retrospect, it appears that if the average strain rate in the first loading to 75 MPa had been maintained for an additional 120 h, the failure-onset strain would have been reached. Thus, onset of creep failure of this tuff under uniaxial conditions in a dry atmosphere at ambient temperature and pressure appears to occur over a narrow strain range with little indication of the nearness to the failure stress. Finally, examination of the sample did not reveal any pumice fragment or other weak zone in the interior that could have been responsible for the low failure stress (90 MPa compared to 180 MPa from the SNL data and the maximum values in Fig. 7).

Fig. 9.

Uniaxial stress, axial strain, and circumferential strain vs time for same sample as in Fig. 8.

A third test was performed on a granite sample to test the confining pressure and temperature control systems. Granite was used instead of tuff because of the uncertainty in predicting the failure stress in tuff, as described above. We wanted to be certain that the sample would not fail during the check-out procedures. This test lasted approximately 3 weeks at 100°C, 10 MPa confining pressure, and 100 MPa differential stress. During this time, we tuned the temperature controller and attempted to control confining pressure. However, it was noted that small temperature variations (± 1 to 2°C) would cause unacceptable pressure variations ($\pm 10\%$) because of thermal expansion of the silicon confining pressure oil. As a result, we added the active confining pressure control that is described in Sec. II.B. With this device we are able to hold confining pressure to within $\pm 0.5\%$ of the desired value regardless of temperature or other variations.

Following these preliminary experiments and the resultant tuning of the apparatus, we began testing potential target horizon rock under conditions expected in the near field of a repository. The first of these tests has been completed, and although the test was not completely successful because of a jacket leak, some interesting results were obtained.

The test specimen was Bullfrog tuff from the 2483-ft level of hole USW-G1. The sample was 11.1 cm long and 5.4 cm in diameter. The test conditions were 100°C, 50 MPa differential stress, 20 MPa confining pressure, and 5 MPa water pore pressure. The effective confining pressure of 15 MPa was attained initially, but because a slow jacket leak developed early in the test, the effective pressure slowly dropped over the duration of the test to about 50% of its initial value. Because of the slow decrease in effective pressure, axial strain actually decreased slowly from the initial loading value while circumferential strain increased slowly (Fig. 10). Over the last 20 h of the test, the average circumferential strain rate was $1.2 \times 10^{-9} \text{ s}^{-1}$, which increased very slightly in the last 2 h. In retrospect, this almost imperceptible increase in strain rate was the onset of a type of Tertiary creep that only developed strongly in the last 200 s of the test. During this time, strain accelerated rapidly and the sample failed at a total test time of about 69 h. Figure 10 shows the average of two axial strain gauges away from the ultimate zone of failure (which apparently was also near the jacket leak because the gauge that failed showed a much greater decrease in strain over time). The increase in circumferential and volume strain at about 23 h corresponds to the time when the pore pressure accumulator was valved off, resulting in a transient increase in the rate of effective pressure decrease.

This type of sudden Tertiary creep failure is similar to that which was observed in uniaxial, room-temperature creep of Grouse Canyon welded tuff. In each case there has been little indication of the nearness to failure, and so far there is no evidence of the classical, exponentially increasing Tertiary creep that has been observed in granite and other materials. This may be a reflection of the structural inhomogeneity of our tuff samples in which failure may start in a very local region with no general increase in micro-fracturing activity that might be noticeable at strain gauges outside of the ultimate failure zone.

Although this test alone does not establish a new issue of concern, it does suggest a type of potential failure that should be evaluated. In the near field of a repository, in a material of very low permeability and relatively high water content such as a zeolitized tuff, thermal expansion of pore water or mineral dehydration water could lead to a local increase in pore pressure if the water could not leak away rapidly enough. This could lead to local rock failure initiation because of the reduction in effective pressure.

Fig. 10.

Axial, circumferential, and volume strain vs time for Bullfrog tuff experiment. Compression is positive, but the sign of the circumferential strain is reversed in the plot. Tests were performed at 100°C, 20 MPa confining pressure, 5 to 12.5 MPa pore pressure, and 50 MPa differential stress.

This would occur while at least some of the strain monitors were indicating a decreasing rate of strain because of the overall decompression associated with a falling effective pressure (analogous to the axial strain record in Fig. 10).

III. CONCLUSIONS AND STATUS

We have designed and perfected an apparatus capable of performing precise, long-term creep deformation tests on rock samples. The apparatus is capable of performing tests lasting several months at maximum differential stress of 970 MPa, confining pressure of 1200 MPa, pore pressure of 40 MPa, and temperature of 250°C. A system for measuring sample permeability under the above conditions has been designed but remains to be completed and tested.

Grouse Canyon welded tuff has a uniaxial compressive strength inhomogeneity of at least a factor of three on a scale of a few centimeters. Note that we are considering only "intact" samples not containing larger scale inhomogeneities such as joints, fractures, or lithophysae. If target horizon tuffs show a similar inhomogeneity, then many more tests will have to be performed

than originally anticipated to get good statistics on mechanical properties, or larger samples containing a representative number of inhomogeneities will have to be tested. Probably both approaches will be required.

The onset of microclastic creep failure in Grouse Canyon welded tuff at ambient conditions and Bullfrog tuff at 100°C, 15 to 7.5 MPa effective pressure, and 50 MPa differential stress appears to occur over a narrow strain range with little Tertiary creep warning. In one test of Bullfrog tuff under conditions of slowly decreasing effective pressure, a failure occurred; during the failure, some strain gauges actually indicated a decreasing rate of strain, which was caused by the overall decompression of the sample.

REFERENCES

1. J. D. Blacic, "Importance of Creep Failure of Hard Rock in the Near Field of a Nuclear Waste Repository," Los Alamos National Laboratory document LA-UR-81-2584 (1981).
3. J. Blacic, J. Carter, P. Halleck, P. Johnson, T. Shankland, R. Andersen, K. Spicchi, and A. Heller, "Effects of Long-Term Exposure of Tuffs to High-Level Nuclear Waste-Repository Conditions: Preliminary Report," Los Alamos National Laboratory report, in preparation.
3. W. R. Wawersik, "Technique and Apparatus for Strain Measurements on Rock in Constant Confining Pressure Experiments," *Rock Mech.* 7, 231-241 (1975).
4. W. F. Brace, J. B. Walsh, and W. T. Frangos, "Permeability of Granite Under High Pressure," *J. Geophys. Res.* 73, 2225-2236 (1968).
5. W. A. Olsson and A. K. Jones, "Rock Mechanics Properties of Volcanic Tuffs from the Nevada Test Site," Sandia National Laboratories report SAND80-1453 (1980).

APPENDIX

FORTRAN LISTING OF CONTROL AND DATA ACQUISITION PROGRAM

Los Alamos Identification No. LP-1465

```

C
C          PAGE 1 OF 'MAIN'
C
C      MAIN      3-18-82 1038 HRS
C  MODULES NEEDED WITH THIS PROGRAM:
C    MAIN.OBJ
C    SUBATN.OBJ
C    SUBPTZ.OBJ
C    LSILIB.OBJ
C    TIMDAT.OBJ
C    TKDATA.OBJ
C    TKLIB.OBJ
C
C  WHEN COMPILING DATACQ CHOOSE THE FORTRAN SWITCHES-
C    /OPT:SPD /NDSWAP /REC:1000 OR MORE
C  LET COMPILER KNOW 'STORE' IS A ROUTINE - NOT A VARIABLE
C    EXTERNAL STORE
C
C
C    COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
C      $ RTIME,STIME
C    COMMON/ARRAYS/CONV(32),DSRPT(15,32),DSFLAG(15),
C      $ FDSRPT(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
C    COMMON/CHAN/KLOAD,KCONF,KFORE,KDIFF,KRAD1,KRAD2,KRAD3
C    COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
C      $ IFAST,ICHAN1,ICHAN2,J,NOGRPH,IY0(32),IX(2),LEVENT,IRECRD
C    COMMON/SCREEN/KDISP,IQLOAD,IQTEMP,QONST1,QONST2,QTEMP
C    COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONISR,CPERNT,DIFDSR,
C      $ GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
C      $ ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
C      $ RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
C      $ SNAXIL,SNCONF,SNDIFF,SNLOAD,SNFORE,SNRADL,STRSS1
C
C
C    DATA IX,IY0/1295,1295,32*1560/
C    DATA DSFLAG/4HFLAG,4H CHA,4HNNEL,12*4H /
C    DATA KEVENT,LEVENT/0,0/
C    DATA IBUF/1000*0/
C    DATA NOGRPH/1/
C    DATA JUNK/19190/
C    DATA JUNK,JUNKR/19190,19191,19192,19193,19194,19195/
C
C    ICHAN1=3
C    ICHAN2=4
C    PI=3.141593
C    PJSARE=3.54656
C
CHAIN
C !! WE DON'T KNOW WHY, BUT DO THIS FIRST
C    CALL ASSIGN (ICHAN2,'DY1:EXPTD.ATA',13,'NEW',2)
C    REWIND ICHAN2
C    TYPE 211
211  FORMAT(' DO YOU WISH TO CREATE A RESTART FILE (Y OR N) ?',*)
C    ACCEPT 2300,ANSW
C    IF (ANSW.EQ.'N') GO TO 1
C    CALL CHANGE
C    CALL ASSIGN (ICHAN1,'DY0:RESTRT.DAT',14)
C    CALL WTRSTR(ICHAN1)
C    CALL CLOSE(ICHAN1)
C
C
C

```

APPENDIX (cont)

```

C
C      PAGE 2 OF 'MAIN'
C
1      CONTINUE
C INITIALIZE ALL VALVES AND TURN OFF CONF.PRESS MOTOR
    CALL SYSINT(IFLAG)
C READ FROM DISC: DATA ACQUISITION AND TEST PARAMETERS
    CALL ASSIGN (ICHAN1,'DY0:RESTRT.DAT',14)
    REWIND ICHAN1
    CALL RDRSTR(ICHAN1)
    CALL CLOSE (ICHAN1)
C ALLOW OPERATOR TO CHANGE DATA ACQ./TEST PARAMETERS
    CALL CHANGE
C CALCULATE AND DISPLAY REQUIRED ACCUMULATOR PRESSURE
    CALL ACPRES
C INITIAL START POINT FOR DATA ACQUISITION SYSTEM
    TYPE 250
    ACCEPT 2300,IDUMMY
C OPEN DATA FILE, SET FIRST DATA FILE NAME = 'DY1:EXPTD.ATA'
    CALL ASSIGN (ICHAN2,'DY1:EXPTD.ATA',13,'NEW',,2)
C REWIND ICHAN2
C WRITE HEADER DATA ON DISC
    CALL WTHEAD(ICHAN2)
C INITIALIZE DATA ACQUISITION BUFFER POINTERS AND MISC.
    CALL INTACQ
    TYPE 2400
    ACCEPT 2300,DUMMY
C GET INITIAL START TIME FOR THIS TEST
    STTIME=SECND(0.)
    CALL TIME(TIMSTR)
C WRITE RELATIVE TIME (RTIME) AND START TIME FOR THIS DISC
C THIS IS WRITTEN ONLY ONCE PER DATA FILE
    WRITE (ICHAN2) RTIME,TIMSTR
C START THE DATA ACQ. SYSTEM
    CALL TKDATA(IBUF,ISIZ,ISTCHN,NCHAN,NBUF)
    CALL SETR(JRATE,1,PRESSET,ICMF,INTCNT,STORE)
C SET DATA RATE = #3
    IFAST=0
    JUNKK=JUNKK(3)
    WRITE (ICHAN2) (JUNKK,IDUMMY=1,NCHAN+1)
    NCOUNT=IRTCNT(3)
C
C IS THIS A RESTART ?
10      TYPE 2000
    ACCEPT 2300,RSFLAG
    IF(RSFLAG.EQ.'N') GO TO 15
    IF(RSFLAG.EQ.'Y') GO TO 50
    GO TO 10
C

```

APPENDIX (cont)

```

C
C          PAGE 3 OF 'MAIN'
C
C IF NOT A RESTART, THEN:
C     COLLECT INITIAL XDUZER OFFSETS
15  CALL INTOFF
C     LET OPERATOR SET ACCUMULATOR, CONFINING AND
C     PORE PRESSURE, TEMPERATURE, AND POSITION RAM
20  TYPE 2100
     ACCEPT 2300,ANSW
     IF(ANSW.NE.'GO') GO TO 20
C     COLLECT FINAL OFFSETS
     CALL FINOFF
C     COLLECT CIRCUMFERENCE REFERENCE VALUE
     CALL CIRKFF
C     WRITE RESTART FILE
     CALL ASSIGN (ICHAN1,'DYO:RESTRT.DAT',14)
     CALL WTRSTR(ICHAN1)
     CALL CLOSE (ICHAN1)
C     SET UP GRAPHICS
     NOGRPH=0
     IX(2)=1295
C     SET DATA RATE TO FASTEST
     IFAST=1
     WRITE (ICHAN2) (JUNK,IDUMMY=1,NCHAN)
C     COLLECT DATA FOR 2 SECONDS
     T1=SECNDS(0)
30  T2=SECNDS(T1)
     IF(T2.LT.2) GO TO 30
C     POP VALVE CONTINUE FAST RATE FOR 5 SECONDS
     CALL POP
     T2=SECNDS(T1)
40  IF(T2.LT.7) GO TO 40
C     SET DATA RATE = #1
     IFAST=0
     JUNKK=JUNKR(1)
     WRITE (ICHAN2) (JUNKK,IDUMMY=1,NCHAN+1)
     NCOUNT=IRTCNT(1)
     GO TO 190
C
C IF THIS IS A RESTART, THEN:
50  CONTINUE
C     WRITE RESTART FILE
     CALL ASSIGN (ICHAN1,'DYO:RESTRT.DAT',14)
     CALL WTRSTR(ICHAN1)
     CALL CLOSE (ICHAN1)
C     CALL ACPRES
     TYPE 2100
60  ACCEPT 2300,ANSW
     IF(ANSW.NE.'GO') GO TO 60
C     SET UP GRAPHICS
     NOGRPH=0
     IX(2)=1295
C     POP VALVE
     CALL POP
     GO TO 190

```

APPENDIX (cont)

```

C
C
C
C
C THIS IS THE RESTART POINT WHEN THE CHANGE FLOPPY OPTION IS DONE
150  RTIME=SECNDS(STTIME)
      CALL TIME(TIMSTR)
C
C  WRITE RELATIVE TIME (RTIME) AND START TIME FOR THIS DISC
C
C  THIS IS WRITTEN ONLY ONCE PER DATA FILE
      WRITE (ICHAN2) RTIME,TIMSTR
C TAKE DATA AND PROCESS ANY COMMANDS FROM KEYBOARD
180  CALL TKDATA(IBUF,ISIZ,ISTCHN,NCHAN,NBUF)
      CALL SETR(JRATE,1,PRESET,ICMF,INTCNT,STORE)
C
C  PROCESS OPERATOR REQUEST (ALLOW DATA ACQ. TO INTERRUPT)
190  CALL CURATE
      MENFLG=0
C TYPE C<CR> TO CHANGE OPTIONS
100  TYPE 200
200  FORMAT (' TYPE C<CR> FOR OPTION. ',%)
      ACCEPT 210,IDUMMY
210  FORMAT (A2)
C
C  TEST IF ERROR FROM COMPLETION ROUTINE 'STORE'
      IF (ICMF.LT.0) STOP ' DATA OVERRUN, USE SLOWER RATE!!'
      IF (IDUMMY.NE.'C') GO TO 100
215  TYPE 220
220  FORMAT (' OPTIONS: ',/,
$' 1) GRAPH',/,
$' 2) NO GRAPH',/,
$' 3) CHANGE DATA RATE',/,
$' 4) WRITE EVENT FLAG',/,
$' 5) CLEAR SCREEN',/,
$' 6) NEW DATA FILE',/,
$' 7) STOP TEST',/,
$' 8) NO OPERATION',/,
$' 9) POP VALVE',/,
$' 10) BLOCK COUNT',/,
$' 11) CHANGE TEST PARAMETERS',)
      TYPE 230
230  FORMAT (' OPTION? ',%)
      ACCEPT 240,IDUMMY
240  FORMAT (I2)
      IF (IDUMMY.LT.1.OR.IDUMMY.GT.11) GO TO 215
      GO TO (500,510,520,530,540,550,560,570,580,
$ 590,600) IDUMMY
C
C GRAPH ON
500  CONTINUE
      NOGRFH=0
      IX(2)=1295
      GO TO 999
C NO GRAPH
510  CONTINUE
      NOGRFH=1
      GO TO 999

```

APPENDIX (cont)

```

C
C          PAGE 5 OF 'MAIN'
C
C CHANGE DATA RATES
520      CONTINUE
        TYPE 527
        TYPE 523,(SCANS(6))
        TYPE 525
        DO 521 IDUMMY=1,5
            TYPE 524,(IDUMMY,SCANS(IDUMMY))
            TYPE 525
521      CONTINUE
        TYPE 528
        ACCEPT 529,IRATE
        IF (IRATE.LE.0) GO TO 522
        IF (IRATE.GT.5) GO TO 520
        IFAST=0
        JUNKK=JUNKR(IRATE)
        WRITE (ICHAN2) (JUNKK,IDUMMY=1,NCHAN+1)
        NCOUNT=IRTCNT(IRATE)
        GO TO 999
522      CONTINUE
        IF (IFAST.EQ.1) GO TO 999
        IFAST=1
        WRITE (ICHAN2) (JUNKK,IDUMMY=1,NCHAN+1)
523      FORMAT(' RATE # 0 = FAST DATA RATE (SECS/SCAN) ',F10.2,*)
524      FORMAT(' RATE # ',I2,' = (SECS/SCAN) ',F10.2,*)
525      FORMAT(' ')
526      FORMAT('// ')
527      FORMAT('/// DATA ACQUISITION RATES :')
528      FORMAT('// DESIRED RATE #:',*,*)
529      FORMAT (I2)
        GO TO 999
C WRITE AN EVENT FLAG TO CHANNEL NCHAN+1
530      CONTINUE
        KEVENT=KEVENT+1
        LEVENT=KEVENT
        TYPE 531,KEVENT
531      FORMAT (' EVENT FLAG NUMBER ',I3,' WRITTEN')
        GO TO 999
C CLEAR THE SCREEN
540      CONTINUE
        CALL TKPACK('34')
        CALL TKPACK('33')
        CALL TKPACK('14')
        CALL TKPACK('30')
        GO TO 999

```


APPENDIX (cont)

```

C
C      PAGE 6 OF 'MAIN'
C
C WRITE NEW DATA FILE
550  CONTINUE
C      TURN DATA ACQ. OFF
      CALL SETR(-1,,)
C      DO DUMMY DELAY FOR COMPLETION OF PRESENT SCAN
      DO 551 IDUMMY=1,500
          DUMMY=SQRT(FLOAT(IDUMMY))*SQRT(FLOAT(IDUMMY))
551  CONTINUE
C      SET RT-11 CLOCK = BATT CLOCK (GET CORRECT DATE ,ONLY)
      CALL TIMDAT
C      CLOSE EXISTING FILE
      CALL CLOSE(ICHAN2)
      TYPE 552
552  FORMAT (/// ENTER NEW DATA FILE NAME:','$)
C      OPEN NEW DATA FILE
      CALL ASSIGN(ICHAN2,','-1)
      REWIND ICHAN2
C      WRITE HEADER DATA ON DISC
      CALL WTHEAD(ICHAN2)
C      RE-INITIALIZE SOME VARIABLES AND CLEAR SCREEN
      IFAST=0
      NCOUNT=IRTCNT(1)
      ICMF=0
      NRUF=1000/NCHAN
      IRECRD=0
      J=1
      IX(2)=1295
      CALL TKPACK(*34)
      CALL TKPACK(*33)
      CALL TKPACK(*14)
      CALL TKPACK(*30)
C      GO TO RESTART THE DATA ACQUISITION
      TYPE 553
553  FORMAT(// TYPE <RET> TO BEGIN TAKING DATA ','$)
      ACCEPT 554,DUMMY
554  FORMAT(A4)
      MENFLG=1
      GO TO 999
C NO OPERATION
570  CONTINUE
      GO TO 999
C POP VALVE TO LOAD RAM IN CREEP TEST AND BEGIN LOAD CONTROL
580  CONTINUE
      CALL POP
      GO TO 999
C BLOCK COUNT
590  CONTINUE
      IBLOCK=IRECRD*(NCHAN+2.25)/256+2
      TYPE 591,IBLOCK
591  FORMAT(/// NUMBER OF BLOCKS USED SO FAR IS: ','15)
      GO TO 999

```

APPENDIX (cont)

```

C
C          PAGE 7 OF 'MAIN'
C
C STOP
560      CONTINUE
C          TURN OFF DATA ACQ.
          CALL SETR(-2,,)
C          CLOSE EXISTING FILE
          CALL CLOSE(ICHAN2)
          CALL SYSINT
          TYPE 561
561      FORMAT (///, ' GOOD-BY FOLKS! ')
          STOP ' PROGRAM FINISHED'
C CHANGE TEST PARAMETERS
C          SET DATA RATE TO SLOWEST
600      IFAST=0
          JUNKK=JUNKR(5)
          WRITE (ICHAN2) (JUNKK,IDUMMY=1,NCHAN+1)
          NCOUNT=IRTCNT(5)
C          CLEAR SCREEN AND TURN OFF GRAPHICS
          NOGRFH=1
          CALL TKPACK(*34)
          CALL TKPACK(*33)
          CALL TKPACK(*14)
          CALL TKPACK(*30)
          GO TO 605
403      TYPE 735
          TYPE 700,DIFDSR
          CALL SAME(DIFDSR)
          VAR=100.*PERCNT
          TYPE 705,VAR
          CALL SAME(VAR)
          PERCNT=VAR/100.
          TYPE 710,CONDSR
          CALL SAME(CONDSR)
          VAR=100.*CPERNT
          TYPE 715,VAR
          CALL SAME(VAR)
          CPERNT=VAR/100.
C PRINT OUT TEST PARAMETERS
605      TYPE 735
          TYPE 700,DIFDSR
          TYPE 730
          VAR=100.*PERCNT
          TYPE 705,VAR
          TYPE 730
          TYPE 710,CONDSR
          TYPE 730
          VAR=CPERNT*100.
          TYPE 715,VAR
          TYPE 730

```

APPENDIX (cont)

```

C
C          PAGE 8 OF 'MAIN'
C
C NOW SEE IF ALL DATA CORRECT
      TYPE 720
      ACCEPT 725,ANS
      IF(ANS.EQ.'N') GO TO 603
C      REWRITE RESTART FILE
      CALL ASSIGN (ICHAN1,'DYO:RESTRT.DAT',14)
      CALL WTRSTR(ICHAN1)
      CALL CLOSE (ICHAN1)
      GO TO 999
700    FORMAT(' DESIRED DIFFERENTIAL STRESS (PSI) ',12X,F10.3,%)
705    FORMAT(' DESIRED STRESS CONTROL PERCENTAGE ',12X,F10.3,%)
710    FORMAT(' DESIRED CONFINING PRESSURE (PSI) ',13X,F10.3,%)
715    FORMAT(' DESIRED CONF. PRESS. CONTROL PERCENTAGE ',6X,F10.3,%)
720    FORMAT('// IS THIS CORRECT ? (Y OR N) %')
725    FORMAT(A4)
730    FORMAT(' ')
735    FORMAT(////' ')
C *****
999    CONTINUE
      IF(MENFLG.EQ.1)GO TO 150
      GO TO 190
C
2000   FORMAT('// IS THIS A RESTART (Y OR N) ? ',%)
2100   FORMAT('// TYPE "GO" TO CONTINUE, AFTER:',/,
$' ACCUMULATOR,CONFINING,PORE PRESSURE,TEMPERATURE SET',/,
$' RAM IS IN POSITION')
2300   FORMAT(A4)
2400   FORMAT('// TYPE <RET> TO BEGIN TAKING DATA ',%)
250    FORMAT('// PUT IN THE DATA DISC',/, ' DATA WILL BE WRITTEN TO
$ FILE DYO:EXPTDA.ATA',/, ' TYPE <RET> WHEN READY : ',%)
      END

```

APPENDIX (cont)

```

C----- START OF ALL SUBROUTINES -----
C
  SUBROUTINE ACPRES
C ACPRES CALC. AND PRINTS THE STARTING PRESSURE FOR ACCUMULATOR
  COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
    $ GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
    $ ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
    $ RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
    $ SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSSI
C CALC. FORCE ON PISTON DUE TO CONFINING PRESSURE
  FORCE1=CONDSR*PISARE
C CALC. NEEDED FORCE ON SPECIMEN
  FORCE2=DIFDSR*SPDIA*SPDIA*PI/4.
C CALC. TOTAL FORCE
  FORCE=FORCE1+FORCE2
C CALC. RAM PSI
  ACPSI=FORCE/113.1
  TYPE 10,ACPSI
10  FORMAT(/' CHARGE ACCUMULATOR TO ',F8.1,' PSI')
    RETURN
    END

  SUBROUTINE ACQPAR
C ACQPAR COLLECTS DATA ACQUISITION PARAMETERS
  COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
    $ RTIME,STTIME
  COMMON/ARRAYS/CONV(32),DSCRPT(15,32),DSFLAG(15),
    $ FDSCRPT(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
1  GO TO 40
2  TYPE 360
C COLLECT 1ST LINE OF FILE DESCRIPTION
  TYPE 200
  TYPE 320,(FDSCRPT(IDUMMY,1),IDUMMY=1,15)
  CALL SAMASC(FDSCRPT(1,1))
C COLLECT 2ND LINE
  TYPE 210
  TYPE 320,(FDSCRPT(IDUMMY,2),IDUMMY=1,15)
  CALL SAMASC(FDSCRPT(1,2))
C COLLECT A/D FULLSCALE VALUE
  FULSCL=FULSCL*2048.
  TYPE 225,FULSCL
  CALL SAME(FULSCL)
  FULSCL=FULSCL/2048.
C COLLECT NUMBER OF CHANNELS
C (CHANNELS ARE NUMBERED 0-31 ON THE RTI-1250).
20  TYPE 220,NCHAN
  CALL SAMEI(NCHAN)
  IF (NCHAN.GT.32) GO TO 20
  IF (NCHAN.LE.0) GO TO 20
C COLLECT STARTING CHANNEL NUMBER
30  TYPE 230,ISTCHN
  CALL SAMEI(ISTCHN)
  IF (ISTCHN.LT.0.OR.ISTCHN.GT.31) GO TO 30
C COLLECT CHANNEL DESCRIPTION AND CONVERSION FACTOR
  TYPE 235
C ISTCHN MAY BE 0, ARRAYS BEGIN NUMBERING WITH 1
C SO STORE ISTCHN DESCRIPTION AT 1ST LOCATION IN ARRAY
  DO 35 IDUMMY=ISTCHN+1,ISTCHN+NCHAN
C REMOVE OFFSET TO GET CORRECT CHANN NUMBER
  JDUMMY=IDUMMY-1
  TYPE 240,JDUMMY
C SET POINTER AT DESCRIPTION
  JDUMMY=IDUMMY-ISTCHN
  TYPE 320,(DSCRPT(I,JDUMMY),I=1,15)
  CALL SAMASC(DSCRPT(1,JDUMMY))
  TYPE 245,(CONV(JDUMMY))
  CALL SAME(CONV(JDUMMY))

```

APPENDIX (cont)

```

35      CONTINUE
C PRINT OUT DATA ACQUISITION PARAMETERS
40      TYPE 360
      TYPE 200
      TYPE 320,(FDSCRP(IDUMMY,1),IDUMMY=1,15)
      TYPE 300
      TYPE 210
      TYPE 320,(FDSCRP(IDUMMY,2),IDUMMY=1,15)
      TYPE 300
      FULSCL=FULSCL*2048.
      TYPE 225,FULSCL
      FULSCL=FULSCL/2048.
      TYPE 300
      TYPE 220,NCHAN
      TYPE 300
      TYPE 230,ISTCHN
      TYPE 350
      TYPE 235
      TYPE 215
      ACCEPT 330,ANSW
C PRINT CHANN DESCRIPTION AND CONV. VALUE
      KCOUNT=0
      DO 45 IDUMMY=ISTCHN+1,ISTCHN+NCHAN
      JDUMMY=IDUMMY-1
      TYPE 240,JDUMMY
      JDUMMY=IDUMMY-ISTCHN
      TYPE 320,(DSCRIPT(I,JDUMMY),I=1,15)
      TYPE 245,(CONV(JDUMMY))
      TYPE 350
      KCOUNT=KCOUNT+1
      IF(KCOUNT.LT.5) GO TO 45
      TYPE 215
      ACCEPT 330,ANSW
      KCOUNT=0
45      CONTINUE
C SEE IF O.K.
46      TYPE 310
      ACCEPT 330,ANSW
      IF(ANSW.EQ.'Y') RETURN
      IF(ANSW.EQ.'N') GO TO 2
      GO TO 46
200     FORMAT(' 1ST LINE FILE DESCRIPTION')
210     FORMAT(' 2ND LINE FILE DESCRIPTION')
215     FORMAT('// TYPE <RET> TO CONTINUE : ',%)
220     FORMAT(' NUMBER OF CHANNELS ',I2,%)
225     FORMAT(' A/D FULLSCALE (+/- VOLTS ',F10.3,%)
230     FORMAT(' STARTING CHANNEL NUMBER ',I2,%)
235     FORMAT(' DESCRIPTION AND CONVERSION VALUE(UNITS/VOLT)')
240     FORMAT(' CHAN$',I2,' DESCRIPTION:',%)
245     FORMAT(' CONV. VALUE= ',F10.3,%)
300     FORMAT(' ')
310     FORMAT('// IS THIS CORRECT (Y OR N) ',%)
320     FORMAT(4X,I5A4,%)
330     FORMAT(A4)
340     FORMAT(F10.3)
350     FORMAT('// ')
360     FORMAT(//// DATA ACQUISITION DESCRIPTION')
      RETURN
      END

```

APPENDIX (cont)

```

SUBROUTINE CHAN
C CHAN COLLECTS XDUCE CHANNEL ASSIGNMENTS
COMMON/CHAN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
1  GO TO 40
2  TYPE 360
C  COLLECT CHANNEL ASSIGNMENTS
    TYPE 200,KLOAD
    CALL SAMEI(KLOAD)
    TYPE 300
    TYPE 210,KCONF
    CALL SAMEI(KCONF)
    TYPE 300
    TYPE 220,KPORE
    CALL SAMEI(KPORE)
    TYPE 300
    TYPE 230,KDIFF
    CALL SAMEI(KDIFF)
    TYPE 300
    TYPE 240,KRAD1
    CALL SAMEI(KRAD1)
    TYPE 300
    TYPE 250,KRAD2
    CALL SAMEI(KRAD2)
    TYPE 300
    TYPE 260,KRAD3
    CALL SAMEI(KRAD3)
    TYPE 300

C PRINT CHANNEL ASSIGNMENTS
40  TYPE 360
    TYPE 200,KLOAD
    TYPE 300
    TYPE 210,KCONF
    TYPE 300
    TYPE 220,KPORE
    TYPE 300
    TYPE 230,KDIFF
    TYPE 300
    TYPE 240,KRAD1
    TYPE 300
    TYPE 250,KRAD2
    TYPE 300
    TYPE 260,KRAD3
    TYPE 300
C  SEE IF O.K.
45  TYPE 310
    ACCEPT 330,ANSW
    IF(ANSW.EQ.'Y') RETURN
    IF(ANSW.EQ.'N') GO TO 2
    GO TO 45
200  FORMAT(' LOAD CELL ',I2,%)
210  FORMAT(' CONFINING PRESSURE ',I2,%)
220  FORMAT(' PORE PRESSURE ',I2,%)
230  FORMAT(' DIFFERENTIAL PORE ',I2,%)
240  FORMAT(' RADIAL GAUGE #1 ',I2,%)
250  FORMAT(' RADIAL GAUGE #2 ',I2,%)
260  FORMAT(' RADIAL GAUGE #3 ',I2,%)
300  FORMAT(' ')
310  FORMAT('// IS THIS CORRECT (Y OR N) ',%)
330  FORMAT(A4)
350  FORMAT('// ')
360  FORMAT('/// CONTROL XDUCE CHANNEL ASSIGNMENT :')
END

```

APPENDIX (cont)

```

SUBROUTINE CHANGE
C CHANGE ALLOWS OPERATOR TO CHANGE DATA ACQ./TEST PARAMETERS
CALL CHAN
CALL PARAM
CALL ACQPAR
CALL DATRAT
RETURN
END

```

```

SUBROUTINE CIRFFF
C CIRFFF CALC. REFERENCE STRAIN A/D UNITS , SPEC.DIA/CIRCUM AFTER THE
C APPLICATION OF CONFINE/PORE PRESS AND TEMP
C ENTER SPDIA=INIT. SPECIMEN DIA. IN., ICIRI=INIT. STRAIN A/D UNITS
C EXIT REF.VALUES: SPDIAR=DIA.(IN.), CIRREF=CIRCUM.(IN.), ICIRRF=STRAIN(A/D)
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
* IFAST,ICHAN1,ICHAN2,J,NOGRFH,IYO(16),IX(2),LEVENT,IREFCD
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDISR,CPERNT,DIFDSR,
* GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
* ICFLAG,IFLAG,LOADF,LOADI,IFORE,IFOREF,PERCNT,PI,PISARE,
* RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
* SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
C MEASURE ALL 3 RADIAL GAUGES,FIND AVG.,A/D UNITS
IDATA1=IBUF((J-ISTCHN)+KRAD1)
IDATA2=IBUF((J-ISTCHN)+KRAD2)
IDATA3=IBUF((J-ISTCHN)+KRAD3)
IAVG=(IDATA1+IDATA2+IDATA3)/3
C CALC. DELTA A/D UNITS USING NO TEMP/PRESS VALUE
DELTA=IAVG-ICIRI
C CALC.EPSLON, CONVERT FROM MILLISTRAIN TO STRAIN
EPSLON=DELTA*RADCON/1000.
C CALC. NEW DIAMETER
SPDIAR=SPDIA*(1+EPSLON)
CIRREF=SPDIAR*PI
RETURN
END

```

APPENDIX (cont)

```

      SUBROUTINE CONPMP(ICFLAG)
C CONPMP INCREASESE/DECREASES CONFINE PRESS.
      IF(ICFLAG.EQ.0) GO TO 100
      GO TO(1,2,3,4),ICFLAG
      TYPE 1000,ICFLAG
1000   FORMAT('/' ERROR IN 'PUMP', ICFLAG=',I8)
      GO TO 100
C THIS DECREASES PRESSURE
C SELECT DIRECTION,TURN MOTOR ON,SAVE TIME
1      IVALVE=8
      CALL VALON(IVALVE)
      IVALVE=9
      CALL VALON(IVALVE)
      T1=SECNDS(0)
      ICFLAG=2
      GO TO 100
C IF 2 SECONDS HAVE PASSED - TURN OFF MOTOR
2      T2=SECNDS(T1)
      IF(T2.LT.2) GO TO 100
      GO TO 90
C THIS INCREASES PRESSURE
3      IVALVE=8
      CALL VALOFF(IVALVE)
      IVALVE=9
      CALL VALON(IVALVE)
      T1=SECNDS(0)
      ICFLAG=4
      GO TO 100
C IF 2 SECONDS HAVE PASSED - TURN OFF MOTOR
4      T2=SECNDS(T1)
      IF(T2.LT.2) GO TO 100
      GO TO 90
C TURN OFF MOTOR - CLEAR FLAG
90     IVALVE=9
      CALL VALOFF(IVALVE)
      IVALVE=8
      CALL VALOFF(IVALVE)
      ICFLAG=0
      GO TO 100
100    RETURN
      END

      SUBROUTINE CURATE
C CURATE CALCULATES AND DISPLAYS CURRENT DATA RATE
      COMMON/ARRAYS/CONV(32),DSCRPT(15,32),DSFLAG(15),
      $ FDCRP(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
      COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
      $ IFAST,ICHAN1,ICHAN2,J,NOGRPH,IY0(32),IX(2),LEVEN?,IRECRD
C      FIND POSITION IN ARRAY OF CURRENT DATA RATE
      IDUMMY=1
10     IF(IRTCNT(IDUMMY).EQ.NCOUNT) GO TO 20
      IDUMMY=IDUMMY+1
      IF(IDUMMY.LT.6) GO TO 10
      TYPE 200
      RETURN
20     TYPE 210,(IDUMMY,SCANS(IDUMMY))
      RETURN
200    FORMAT('/' ERROR !!! - CURRENT DATA RATE CANNOT BE CALCULATED')
210    FORMAT(' CURRENTLY RUNNING DATA RATE #',I2,
      $ ' ('',F10.2,' SECS/SCAN)')
      END

```


APPENDIX (cont)

```

      SUBROUTINE DATRAT
C DATRAT COLLECTS DATA ACQUISITION RATE PARAMETERS
      COMMON/ARRAYS/CONV(32),DSCRIPT(15,32),DSFLAG(15),
      * FDSRCP(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
      COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
      * RTIME,STTIME
      COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
      * IFAST,ICHAN1,ICHAN2,J,NODGRPH,IYO(32),IX(2),LEVENT,IRECRD
1      GO TO 25
2      TYPE 360
C COLLECT DATA RATES
15     TYPE 200,(SCANS(6))
        CALL SAME(SCANS(6))
        IF(SCANS(6).LT..01)GO TO 15
C     INSURE CORRECTNESS OF PRESET
        FRATE=1./SCANS(6)
        IDUMMY=100./FRATE
        PRESET=IDUMMY
        FRATE=100./PRESET
        SCANS(6)=1./FRATE
        IRTCNT(6)=PRESET
C     COLLECT SLOWER DATA RATES
        DO 20 IDUMMY=1,5
18     TYPE 210,(IDUMMY,SCANS(IDUMMY))
        CALL SAME(SCANS(IDUMMY))
        TYPE 300
        IF(SCANS(IDUMMY)/32000.GT.SCANS(6)) GO TO 18
C     INSURE CORRECTNESS OF RATES AND SCAN VALUES
        RATES(IDUMMY)=1./SCANS(IDUMMY)
        IRTCNT(IDUMMY)=FRATE/RATES(IDUMMY)
        RATES(IDUMMY)=FRATE/FLOAT(IRTCNT(IDUMMY))
        SCANS(IDUMMY)=1./RATES(IDUMMY)
20     CONTINUE
C PRINT OUT DATA RATES
25     TYPE 360
        TYPE 200,(SCANS(6))
        TYPE 300
        DO 30 IDUMMY=1,5
            TYPE 210,(IDUMMY,SCANS(IDUMMY))
            TYPE 300
30     CONTINUE
        TYPE 350
45     CONTINUE
C     SEE IF O.K.
        TYPE 310
        ACCEPT 330,ANSW
        IF(ANSW.EQ.'Y') RETURN
        IF(ANSW.EQ.'N') GO TO 2
        GO TO 45
200    FORMAT(' FAST DATA RATE (SECS/SCAN) ',F10.2,*)
210    FORMAT(' # ',I2,' DATA RATE (SECS/SCAN) ',F10.2,*)
300    FORMAT(' ')
310    FORMAT('// IS THIS CORRECT (Y OR N) ',*)
320    FORMAT(4X,15A4,*)
330    FORMAT(A4)
340    FORMAT(F10.3,*)
350    FORMAT('// ')
360    FORMAT('/// DATA ACQUISITION RATES :')
      END

```

APPENDIX (cont)

```

SUBROUTINE FINOFF
C FINOFF COLLECTS XDUCE OFFSET (A/D UNITS) AFTER TEMP/PRESS SET
COMMON/CHAN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
* IFAST,ICHAN1,ICHAN2,J,NOGRPH,IY0(32),IX(2),LEVENT,IRECRD
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
* GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
* ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
* RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
* SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
LOADF=IBUF((J-ISTCHN)+KLOAD)
ICONFF=IBUF((J-ISTCHN)+KCONF)
IPOREF=IBUF((J-ISTCHN)+KPORE)
C MEASURE ALL 3 RADIAL GAUGES,FIND AVG.
IDATA1=IBUF((J-ISTCHN)+KRAD1)
IDATA2=IBUF((J-ISTCHN)+KRAD2)
IDATA3=IBUF((J-ISTCHN)+KRAD3)
ICIRF=(IDATA1+IDATA2+IDATA3)/3
RETURN
END

```

```

SUBROUTINE GRIDVR
C DRAW CRUDE GRID AND PRINT VARIABLE LABELS
LOGICAL*1 CAN,SUB,ESC,FS,GS,US,DEL,LITTLA,FF
LOGICAL*1 ISTRS(15)
LOGICAL*1 OLDSTR(15)
LOGICAL*1 LABSTR(7)
C
DIMENSION KHAR(10)
DIMENSION IY(2),IXX(2)
C
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
* IFAST,ICHAN1,ICHAN2,J,NOGRPH,IY0(32),IX(2),LEVENT,IRECRD
COMMON/SCREEN/KDISP,IQLOAD,IQTEMP,QONST1,QONST2,QTEMP
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
* GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
* ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
* RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
* SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
C
DATA IXX/1295,4095/
DATA CAN,SUB,ESC,FS,GS,US,DEL,LITTLA/'30','32','33','34','35','37,
*'177','141/
DATA FF/'14/
DATA KHAR/'60','61','62','63','64','65','66','67','70','71/
DATA ICOUNT/1/
DATA LABSTR/1HS,1HT,1HR,1HE,1HS,1HS,1H=/
C
C CLEAR SCREEN
C GO TO POINT MODE
CALL TKPACK(FS)
C GO TO 4010 ALPHA,CLR SCREEN,DATA=WHITE,HOME CURSOR
CALL TKPACK(ESC)
CALL TKPACK(FF)
C GO TO ADM-3 ALPH
CALL TKPACK(CAN)
C -FULL SCALE LINE
C GO TO VECTOR MODE
CALL TKPACK(GS)

```

APPENDIX (cont)

```

C      SEND FIRST CO-ORDINATE
      CALL TKVECT(IXX(1),1)
C      SEND SECND CO-ORDINATE , DRAW LINE
      CALL TKVECT(IXX(2),1)
C -HALF SCALE LINE
C      PREPARE TO ACCEPT FIRST CO-ORD.
      CALL TKPACK(GS)
      CALL TKVECT(IXX(1),780)
      CALL TKVECT(IXX(2),780)
C 0 LINE
      CALL TKPACK(GS)
      CALL TKVECT(IXX(1),1560)
      CALL TKVECT(IXX(2),1560)
C +HALF SCALE LINE
      CALL TKPACK(GS)
      CALL TKVECT(IXX(1),2340)
      CALL TKVECT(IXX(2),2340)
C +FULL SCALE LINE
      CALL TKPACK(GS)
      CALL TKVECT(IXX(1),3120)
      CALL TKVECT(IXX(2),3120)
C
C PRINT "STRESS" TO GRAPHIC SCREEN
C      GO TO VECTOR MODE
      CALL TKPACK(GS)
C      POSITION CURSOR
      CALL TKVECT(1295,3000)
C      GO TO 4010 ALPHA MODE
      CALL TKPACK(US)
C      WRITE LABEL TO GRAPHICS SCREEN
      DO 145 IDUMMY=1,7
      CALL TKPACK(LABSTR(IDUMMY))
145      CONTINUE
C GO TO ADM-3 ALPHA
      CALL TKPACK(CAN)
      RETURN
      END

```

```

      SUBROUTINE INTACQ
C INITIALIZE PARAMETERS FOR STARTING DATA ACQUISITION SYS.
C NBUF,ICMF ARE PARAMETERS FOR TKDATA AND SETR .
C J IS AN INDEX USED IN THE COMPLETION ROUTINE.
      COMMON/ARRAYS/CONV(32),DSCRPT(15,32),DSFLAG(15),
      * FDSCRPT(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
      COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
      * RTIME,STTIME
      COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
      * IFAST,ICHAN1,ICHAN2,J,NDGRPH,IY0(32),IX(2),LEVENT,IRECRD
      IDUMMY=1000
      NBUF=IDUMMY/NCHAN
      ISIZ=NCHAN*NBUF
      IRECRD=0
      INTCNT=1
      ICMF=0
      J=1
      IFAST=0
      NCOUNT=IRTCNT(1)
      JRATE=5
      RETURN
C STTIME IS STARTING TIME IN SECONDS PAST MIDNIGHT OR BOOT
C RTIME IS TIME TIME IN SECONDS RELATIVE TO STTIME
C STTIME IS FIXED WHEN THE FIRST DATA FLOPPY IS STARTED. RTIME IS
C CALCULATED TO GIVE THE TIME FROM THE START OF THE EXPERIMENT AND IS
C WRITTEN TO EACH OF THE FLOPPYS USED IN THE TEST.
C TIMSTR IS AN ASCII STRING GIVING SYSTEM TIME IN HR:MIN:SEC FORMAT.
      END

```

APPENDIX (cont)

```

SUBROUTINE INTOFF
C INTOFF COLLECTS INITIAL OFFSET A/D UNITS FOR VARIOUS XDUCERS
COMMON/CHANN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
* IFAST,ICHAN1,ICHAN2,J,NODGRPH,IY0(32),IX(2),LEVENT,IRECRD
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
* GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
* ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
* RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
* SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1

C
C GET INIT. VALUES FOR LOAD CELL, CONFIN AND PORE XDUCERS, RADIAL GAUGES
C GET INIT. VALUES FOR LOAD CELL (LOADI)
1   LOADI=IBUF((J-ISTCHN)+KLOAD)
    IDUMMY=KLOAD
    IF(IABS(LOADI).GT.2) GO TO 1020
C GET INIT. VALUES FOR CONFINING PRESSURE (ICONFI)
    ICONFI=IBUF((J-ISTCHN)+KCONF)
    IDUMMY=KCONF
    IF(IABS(ICONFI).GT.2) GO TO 1020
C GET INIT. VALUES FOR PORE PRESSURE (IPORE)
    IPORE=IBUF((J-ISTCHN)+KPORE)
    IDUMMY=KPORE
    IF(IABS(IPORE).GT.2) GO TO 1020
C GET INIT. VALUES FOR RADIAL GAUGES (CIRIN)
C MEASURE ALL 3 RADIAL GAUGES, FIND AVG., SAVE IN A/D UNITS
    IDATA1=IBUF((J-ISTCHN)+KRAD1)
    IDUMMY=KRAD1
    IF(IABS(IDATA1).GT.2) GO TO 1020
    IDATA2=IBUF((J-ISTCHN)+KRAD2)
    IDUMMY=KRAD2
    IF(IABS(IDATA2).GT.2) GO TO 1020
    IDATA3=IBUF((J-ISTCHN)+KRAD3)
    IDUMMY=KRAD3
    IF(IABS(IDATA3).GT.2) GO TO 1020
    ICIRI=(IDATA1+IDATA2+IDATA3)/3
    RETURN
1020 TYPE 1025, IDUMMY
1025  FORMAT(/' ADJUST ZERO ON CHANNEL ',I2,' , THEN HIT <RET> ',*)
      ACCEPT 1030,ANSW
1030  FORMAT(A4)
      GO TO 1
      END

```

```

SUBROUTINE MENUE(MENFLG)
C MENUE PROCESSES OPERATOR REQUESTS
COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
* RTIME,STIME
COMMON/ARRAYS/CONV(32),DSCRIPT(15,32),DSFLAG(15),
* FDSCR(15,2),IRTCNT(4),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
* IFAST,ICHAN1,ICHAN2,J,NODGRPH,IY0(32),IX(2),LEVENT,IRECRD
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
* GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
* ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
* RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
* SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1

C
MENFLG=0
C TYPE C<CR> TO CHANGE OPTIONS
100  TYPE 200
200  FORMAT (' TYPE C<CR> FOR OPTION. ',*)
      ACCEPT 210, IDUMMY
210  FORMAT (A2)

```

APPENDIX (cont)

```

C      TEST IF ERROR FROM COMPLETION ROUTINE 'STORE'
      IF (ICMF.LT.0) STOP ' DATA OVERRUN, USE SLOWER RATE!!'
      IF (IDUMHY.NE.'C') GO TO 100
215    TYPE 220
220    FORMAT (' OPTIONS: ',/,
$'      1) GRAPH',/,
$'      2) NO GRAPH',/,
$'      3) CHANGE DATA RATE',/,
$'      4) WRITE EVENT FLAG',/,
$'      5) CLEAR SCREEN',/,
$'      6) NEW DATA FILE',/,
$'      7) STOP TEST',/,
$'      8) NO OPERATION',/,
$'      9) POP VALVE',/,
$'     10) BLOCK COUNT',/,
$'     11) CHANGE TEST PARAMETERS'.)
      TYPE 230
230    FORMAT (' OPTION? ',%)
      ACCEPT 240,IDUMHY
240    FORMAT (I2)
      IF (IDUMHY.LT.1.OR.IDUMHY.GT.11) GO TO 215
      GO TO (500,510,520,530,540,550,560,570,580,
$ 590,600) IDUMHY
C
C GRAPH ON
500    CONTINUE
      NOGRPH=0
      IX(2)=1295
      RETURN
C NO GRAPH
510    CONTINUE
      NOGRPH=1
      RETURN
C CHANGE DATA RATES
520    CONTINUE
      TYPE 527
      TYPE 523,(SCANS(6))
      TYPE 525
      DO 521 IDUMHY=1,5
        TYPE 524,(IDUMHY,SCANS(IDUMHY))
        TYPE 525
521    CONTINUE
      TYPE 528
      ACCEPT 529,IRATE
      IF (IRATE.LE.0) GO TO 522
      IF (IRATE.GT.5) GO TO 520
      IFAST=0
      JUNKK=JUNKR(IRATE)
      WRITE (ICHAN2) (JUNKK,IDUMHY=1,NCHAN+1)
      NCOUNT=IRTCNT(IRATE)
      RETURN
522    CONTINUE
      IF (IFAST.EQ.1) RETURN
      IFAST=1
      WRITE (ICHAN2) (JUNK,IDUMHY=1,NCHAN+1)
523    FORMAT(' RATE # 0 = FAST DATA RATE (SECS/SCAN) ',F10.2,%)
524    FORMAT(' RATE # ',I2,' = (SECS/SCAN) ',F10.2,%)
525    FORMAT(' ')
526    FORMAT('// ')
527    FORMAT('/// DATA ACQUISITION RATES :')
528    FORMAT('// DESIRED RATE #:',%,%)
529    FORMAT (I2)
      RETURN
C WRITE AN EVENT FLAG TO CHANNEL NCHAN+1
530    CONTINUE

```

APPENDIX (cont)

```

        KEVENT=KEVENT+1
        LEVENT=KEVENT
        TYPE 531,KEVENT
531      FORMAT (/' EVENT FLAG NUMBER ',I3,' WRITTEN')
        RETURN
C CLEAR THE SCREEN
540      CONTINUE
        CALL TKPACK('34)
        CALL TKPACK('33)
        CALL TKPACK('14)
        CALL TKPACK('30)
        RETURN
C WRITE NEW DATA FILE
550      CONTINUE
C        TURN DATA ACQ. OFF
        CALL SETR(-1,,,)
C        DO DUMMY DELAY FOR COMPLETION OF PRESENT SCAN
        DO 551 IDUMMY=1,500
            DUMMY=SQRT(FLOAT(IDUMMY))*SQRT(FLOAT(IDUMMY))
551      CONTINUE
C        SET RT-11 CLOCK = BATT CLOCK (GET CORRECT DATE ,ONLY)
        CALL TIMDAT
C        CLOSE EXISTING FILE
        CALL CLOSE(ICHAN2)
        TYPE 552
552      FORMAT (/' ENTER NEW DATA FILE NAME:',%)
C        OPEN NEW DATA FILE
        CALL ASSIGN(ICHAN2,',' , -1)
        REWIND ICHAN2
C        WRITE HEADER DATA ON DISC
        CALL WTHEAD(ICHAN2)
C        RE-INITIALIZE SOME VARIABLES AND CLEAR SCREEN
        IFAST=0
        NDCOUNT=IRTCNT(1)
        ICMF=0
        NBUF=1000/NCHAN
        IRECRD=0
        J=1
        IX(2)=1295
        CALL TKPACK('34)
        CALL TKPACK('33)
        CALL TKPACK('14)
        CALL TKPACK('30)
C        GO TO RESTART THE DATA ACQUISITION
        TYPE 553
553      FORMAT(/' TYPE <RET> TO BEGIN TAKING DATA ',%)
        ACCEPT 554,DUMMY
554      FORMAT(A4)
        MENFLG=1
        RETURN
C NO OPERATION
570      CONTINUE
        RETURN
C POP VALVE TO LOAD RAM IN CREEP TEST AND BEGIN LOAD CONTROL
580      CONTINUE
        CALL POP
        RETURN
C BLOCK COUNT
590      CONTINUE
        IBLOCK=IRECRD*(NCHAN+2.25)/256+2
        TYPE 591,IBLOCK
591      FORMAT(/' NUMBER OF BLOCKS USED SO FAR IS: ',I5)
        RETURN

```

APPENDIX (cont)

```

C STOP
560 CONTINUE
C TURN OFF DATA ACQ.
CALL SETR(-2,,)
C CLOSE EXISTING FILE
CALL CLOSE(ICHAN2)
CALL SYSINT
TYPE 561
561 FORMAT (//,' GOOD-BY FOLKS! ')
STOP ' PROGRAM FINISHED'
C CHANGE TEST PARAMETERS
C CLEAR SCREEN
600 CALL TKPACK('34')
CALL TKPACK('33')
CALL TKPACK('14')
CALL TKPACK('30')
CALL PARAM
C REWRITE RESTART FILE
CALL ASSIGN (ICHAN1,'DYO:RESTR.DAT',14)
CALL WTRSTR(ICHAN1)
CALL CLOSE (ICHAN1)
RETURN
END

```

```

SUBROUTINE NWAREA
C NWAREA MEASURES PRESENT RADIAL STRAIN AND CALCULATES THE NEW AREA
C OF THE SPECIMEN.
C ENTER CIRREF=REF.SPEC.CIRCUM.(IN.),ICIRRF=REF.STRAIN (A/D)
C EXIT AREANW=NEW AREA (IN.)
C
COMMON/CHANN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
C
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
* IFAST,ICHAN1,ICHAN2,J,NOGRPH,IY0(16),IX(2),LEVENT,IREFCD
C
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFISR,
* GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
* ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
* RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
* SNAXIL,SNCONF,SNDIFF,SNLOAD,SNFORE,SNRADL,STRESS1
C MEASURE ALL 3 RADIAL GAUGES,FIND AVG.,CONVRT TO VOLTS
IDATA1=IBUF((J-ISTCHN)+KRAD1)
IDATA2=IBUF((J-ISTCHN)+KRAD2)
IDATA3=IBUF((J-ISTCHN)+KRAD3)
IAVG=(IDATA1+IDATA2+IDATA3)/3
C CALC. DELTA A/D UNITS
DELTA=(IAVG-ICIRRF)
C CALC. NEW CIRCUM.
EPSLON=DELTA*RADCON/1000.
CIRNEW=CIRREF*(1+EPSLON)
C CALCULATE NEW AREA IN INCHES
AREANW=(CIRNEW*CIRNEW)/(4.0*PI)
RETURN
END

```

APPENDIX (cont)

```

      SUBROUTINE PARAM
C PARAM COLLECTS ALL TEST PARAMETERS
      COMMON/CHANN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
      COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
      * GAUAXL,GAURAD,ICONFP,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
      * ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
      * RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
      * SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1

C
      GO TO 80
1      TYPE 88
88      FORMAT(////' ')
      TYPE 200,SPDIA
      CALL SAME(SPDIA)
      TYPE 205,DIFDSR
      CALL SAME(DIFDSR)
      VAR=100.*PERCNT
      TYPE 208,VAR
      CALL SAME(VAR)
      PERCNT=VAR/100.
      TYPE 210,CONDSR
      CALL SAME(CONDSR)
      VAR=100.*CPERNT
      TYPE 212,VAR
      CALL SAME(VAR)
      CPERNT=VAR/100.
      TYPE 225,SNLOAD
      CALL SAME(SNLOAD)
      TYPE 230,SNCONF
      CALL SAME(SNCONF)
      TYPE 235,SNPORE
      CALL SAME(SNPORE)
      TYPE 238,SNDIFF
      CALL SAME(SNDIFF)
      TYPE 240,GAUAXL
      CALL SAME(GAUAXL)
      TYPE 245,GAURAD
      CALL SAME(GAURAD)
      TYPE 250,SNAXIL
      CALL SAME(SNAXIL)
      TYPE 255,SNRADL
      CALL SAME(SNRADL)

C CALC. AXIAL CONVERSION FACTOR
      AXLCON=GAUAXL*SNAXIL/4096.
C CALC. RADIAL CONVERSION FACTOR
      RADCON=GAURAD*SNRADL/4096.

C
C PRINT OUT TEST PARAMETERS
80      TYPE 89
89      FORMAT(////' ')
      TYPE 200,SPDIA
      TYPE 500
      TYPE 205,DIFDSR
      TYPE 500
      VAR=100.*PERCNT
      TYPE 208,VAR
      TYPE 500
      TYPE 210,CONDSR
      TYPE 500
      VAR=CPERNT*100.
      TYPE 212,VAR
      TYPE 500
      TYPE 225,SNLOAD
      TYPE 500
      TYPE 230,SNCONF

```


APPENDIX (cont)

```

TYPE 500
TYPE 235,SNPORE
TYPE 500
TYPE 238,SNDIFF
TYPE 500
TYPE 240,GAUAXL
TYPE 500
TYPE 245,GAURAD
TYPE 500
TYPE 250,SNAXIL
TYPE 500
TYPE 255,SNRADL
TYPE 500
C NOW SEE IF ALL DATA CORRECT
100 TYPE 290
ACCEPT 295,ANS
IF(ANS.EQ.'Y') RETURN
IF(ANS.EQ.'N') GO TO 1
GO TO 100
200 FORMAT(' SPECIMEN DIAMETER (INCHES) ',19X,F10.3,%)
205 FORMAT(' DESIRED DIFFERENTIAL STRESS (PSI) ',12X,F10.3,%)
208 FORMAT(' DESIRED STRESS CONTROL PERCENTAGE ',12X,F10.3,%)
210 FORMAT(' DESIRED CONFINING PRESSURE (PSI) ',13X,F10.3,%)
212 FORMAT(' DESIRED CONF. PRESS. CONTROL PERCENTAGE ',6X,F10.3,%)
225 FORMAT(' LOAD CELL RANGE (POUNDS FULL SCALE) ',10X,F10.3,%)
230 FORMAT(' CONF. PRESSURE XDUCER RANGE (PSI FULL SCALE) ',F10.3,%)
235 FORMAT(' PORE PRESSURE XDUCER RANGE (PSI FULL SCALE) ',2X,F10.3,%)
238 FORMAT(' DIFF.PORE PRESS.XDUCER RANGE (PSI FULL SCALE) ',F10.3,%)
240 FORMAT(' AXIAL STRAIN GAUGE FACTOR ',20X,F10.3,%)
245 FORMAT(' RADIAL STRAIN GAUGE FACTOR ',19X,F10.3,%)
250 FORMAT(' AXIAL STRAIN RANGE (MILLISTRAIN FULL SCALE) ',2X,F10.3,%)
255 FORMAT(' RADIAL STRAIN RANGE (MILLISTRAIN FULL SCALE) ',F10.3,%)
290 FORMAT('/' IS THIS CORRECT ? (Y OR N) '%)
295 FORMAT(A4)
300 FORMAT(F10.3)
500 FORMAT(' ')
END

```

```

SUBROUTINE POP
C POPS THE VALVE
COMMON/POPFLG/IPOP
IVALVE=0
CALL VALOFF(IVALVE)
IPOP=1
RETURN
END

```

APPENDIX (cont)

```

      SUBROUTINE PUMP(IFLAG)
C PUMP EITHER CHARGES OR DISCHARGES ACCUM., DEPENDING ON IFLAG
      IF(IFLAG.EQ.0) GO TO 100
      GO TO(1,2,3,4,5,6,7,8,9,10,100),IFLAG
      TYPE 1000,IFLAG
1000   FORMAT('/' ERROR IN 'PUMP', IFLAG=',I8)
      GO TO 100
C THIS IS THE CHARGE ROUTINE
C OPEN VAL. 1,SAVE TIME
1      IVALUE=1
      CALL VALON(IVALUE)
      T1=SECNDS(0)
      IFLAG=2
      GO TO 100
C IF 2 SECS. HAVE PASSED,CLOSE VAL. 1,SAVE TIME
2      T2=SECNDS(T1)
      IF(T2.LT.2) GO TO 100
      CALL VALOFF(IVALUE)
      T1=SECNDS(0)
      IFLAG=3
      GO TO 100
C IF 1 SEC. HAS PASSED,OPEN VAL. 2,SAVE TIME
3      T2=SECNDS(T1)
      IF(T2.LT.1) GO TO 100
      IVALUE=2
      CALL VALON(IVALUE)
      T1=SECNDS(0)
      IFLAG=4
      GO TO 100
C IF 2 SECS. HAVE PASSED, CLOSE VAL. 2, SAVE TIME
4      T2=SECNDS(T1)
      IF(T2.LT.2) GO TO 100
      CALL VALOFF(IVALUE)
      IFLAG=5
      GO TO 100
C IF 1 SEC. HAS PASSED, CLEAR IFLAG, DONE !
5      T2=SECNDS(T1)
      IF(T2.LT.1) GO TO 100
      IFLAG=0
      GO TO 100
C THIS IS THE DISCHARGE ROUTINE
C OPEN VAL. 2, SAVE TIME
6      IVALUE=2
      CALL VALON(IVALUE)
      T1=SECNDS(0)
      IFLAG=7
      GO TO 100
C IF 2 SECS. HAVE PASSED,CLOSE VALVE 2
7      T2=SECNDS(T1)
      IF(T2.LT.2) GO TO 100
      CALL VALOFF(IVALUE)
      T1=SECNDS(0)
      IFLAG=8
      GO TO 100
C IF 1 SEC. HAS PASSED,OPEN VALVE 3
8      T2=SECNDS(T1)
      IF(T2.LT.1) GO TO 100
      IVALUE=3
      CALL VALON(IVALUE)
      T1=SECNDS(0)
      IFLAG=9
      GO TO 100

```

APPENDIX (cont)

```

C IF 2 SECS. HAVE PASSED, CLOSE VALVE 3
9   T2=SECNDS(T1)
    IF(T2.LT.2) GO TO 100
    CALL VALOFF(IVALVE)
    T1=SECNDS(0)
    IFLAG=10
    GO TO 100
C IF 1 SEC. HAS PASSED, CLEAR IFLAG, DONE!
10  T2=SECNDS(T1)
    IF(T2.LT.1) GO TO 100
    IFLAG=0
    GO TO 100
100 RETURN
    END

```

```

SUBROUTINE RDACQ(ILUN)
C RDACQ READS FULSCL,FRATE,INTCNT,ISTCHN,NCHAN,PRESET,RTIME
C   STTIME FROM DISC
COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
$ RTIME,STTIME
READ (ILUN) FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
$ RTIME,STTIME
RETURN
END

```

```

SUBROUTINE RDARRAY(ILUN)
C RDARRAY READ ARRAYS CONV,IRTCNT,RATES,SCANS,TIMSTR FROM DISC
COMMON/ARRAYS/CONV(32),DSCRPT(15,32),DSFLAG(15),
$ FDSCRPT(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
C
C READ CONV
READ (ILUN) (CONV(IDUMMY),IDUMMY=1,6)
C READ IRTCNT
READ (ILUN) (IRTCNT(IDUMMY),IDUMMY=1,6)
C READ RATES
READ (ILUN) (RATES(IDUMMY),IDUMMY=1,6)
C READ SCANS
READ (ILUN) (SCANS(IDUMMY),IDUMMY=1,6)
C READ TIMSTR
READ (ILUN) TIMSTR
RETURN
END

```

APPENDIX (cont)

```

SUBROUTINE RDHEAD(ILUN)
C RDHEAD READS HEADER FROM DISC
COMMON/ARRAYS/CONV(32),DSCRPT(15,32),DSFLAG(15),
* FDSCRPT(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
* RTIME,STTIME
C
C READ FIRST FILE DESCRIPTION LINE
READ (ILUN) (FDSCRPT(IDUMMY,1),IDUMMY=1,15)
C READ SECOND FILE DESCRIPTION LINE
READ (ILUN) (FDSCRPT(IDUMMY,2),IDUMMY=1,15)
C READ NO.CHANS+FLAG
READ (ILUN) NCHAN
C CORRECT NCHAN (IT'S STORED AS NCHAN + 1 EVENT FLAG
NCHAN=NCHAN-1
C READ '2' TO SIGNIFY TYPE 2 FORMAT FILE
IDUMMY=2
READ (ILUN) IDUMMY
C READ FASTEST RATE + 5 SLOWER RATES
READ (ILUN) FRATE,(RATES(IDUMMY),IDUMMY=1,5)
C READ STARTING CHANNEL NO., A/D FULLSCALE
READ (ILUN) ISTCHN,FULSCL
DO 385 IDUMMY=1,NCHAN
C READ CHANNEL DESCRIPTION
READ (ILUN) (DSCRPT(I,IDUMMY),I=1,15)
C READ CHANNEL CONVERSION FACTOR
READ (ILUN) CONV(IDUMMY)
385 CONTINUE
C READ EVENT FLAG DESCRIPTION
READ (ILUN) (DSFLAG(IDUMMY),IDUMMY=1,15)
C READ CONVERSION FACTOR FOR FLAG CHANNEL
DUMMY=1./FULSCL
READ (ILUN) DUMMY
RETURN
END

```

```

SUBROUTINE RDRSTR(ILUN)
C RDRSTR READS FROM DISC: DATA ACQUISITION AND TEST PARAMETERS
COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
* RTIME,STTIME
COMMON/ARRAYS/CONV(32),DSCRPT(15,32),DSFLAG(15),
* FDSCRPT(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
COMMON/CHANN/KLOAD,KCONF,KPFORE,KDIFF,KRAD1,KRAD2,KRAD3
COMMON/POFFLG/IPOF
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
* IFAST,ICHAN1,ICHAN2,J,NDRPH,IYO(32),IX(2),LEVENT,IREFCD
COMMON/SCREEN/KDISP,IQLOAD,IQTEMP,QONST1,QONST2,QTEMP
COMMON/TEST/ACPS1,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
* GAUAXL,GAURAD,ICONFP,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
* ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
* RADCON,KLOAD,RSFLAG,SPDIA,SPDIAR,
* SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
CALL RDHEAD(ILUN)
CALL RDARRAY(ILUN)
CALL RDACQ(ILUN)
CALL RDTFAR(ILUN)
RETURN
END

```

APPENDIX (cont)

```

      SUBROUTINE RDTPAR(ILUN)
C RDTPAR READS TEST PARAMETERS FROM DISC
      COMMON/CHANN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
      COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
      * GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
      * ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
      * RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
      * SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
C
      READ (ILUN) ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
      * GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
      * ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
      * RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
      * SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
      READ (ILUN) KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
      RETURN
      END

      SUBROUTINE RUN
C RUN   CONTROLS DIFFERENTIAL STRESS AND CONFINING PRESS.
      COMMON/CHANN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
      COMMON/POFFLG/IPOP
      COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
      * IFAST,ICHAN1,ICHAN2,J,NOGRPH,IY0(32),IX(2),LEVENT,IREFCD
      COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERNT,DIFDSR,
      * GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
      * ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
      * RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
      * SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
C
      DATA IPOF/0/
      DATA ICFLAG/0/
      DATA IFLAG/0/
C
C IS VALVE POPPED YET?
      IF (IPOP.EQ.0) RETURN
      IVALVE=0
      CALL VALOFF(IVALVE)
20    CONTINUE
C IF ICFLAG SET, PROCESS CONFMF, OTHERWISE TEST CONF. PRESS.
      IF (ICFLAG.GT.0) GO TO 1105
C   IS CONFINING PRESSURE CORRECT ?
      ICONFF=IBUF((J-ISTCHN)+KCONF)
      CONPRS=SNCONF*(ICONFF-ICONFI)/2048.
      IF (CONPRS.GT.(CONDSR*(1.+CPERNT))) ICFLAG=1
      IF (CONPRS.LT.(CONDSR*(1.-CPERNT))) ICFLAG=3
1105  CALL CONFMF(ICFLAG)
C IF IFLAG SET, PROCESS PUMP, OTHERWISE TEST AXIAL STRESS
      IF (IFLAG.GT.0) GO TO 1150
C   CALC. NEW SPECIMEN AREA
      CALL NUAREA
C   CALC. PRESENT DIFFERENTIAL STRESS
      CALL AXSTRS
C   IS DIFFERENTIAL STRESS = DESIRED ?
      IF (STRSS1.GT.(DIFDSR*(1.+PERCNT))) IFLAG=6
      IF (STRSS1.LT.(DIFDSR*(1.-PERCNT))) IFLAG=1
1150  CALL PUMP(IFLAG)
      RETURN
      END

```

APPENDIX (cont)

```

SUBROUTINE SAMASC(VAR)
C SAMASC INPUTS ASCII STRING,DEFAULT LEAVES VARIABLE AS IS
LOGICAL*1 SCRAT(61)
DIMENSION VAR(15)
TYPE 10
CALL GETSTR(5,SCRAT,60,ERROR)
I=LEN(SCRAT)
IF(I.EQ.0) RETURN
DECODE(60,20,SCRAT)VAR
5 CONTINUE
10 FORMAT(' ',%)
20 FORMAT(15A4)
RETURN
END

```

```

SUBROUTINE SAME(VAR)
C SAME INPUTS REAL VAR.,DEFAULT LEAVES VAR. AS IS
TYPE 10
ACCEPT 100,DUMMY
IF(DUMMY.NE.0) VAR=DUMMY
10 FORMAT(' ',%)
100 FORMAT(F10.3)
RETURN
END

```

```

SUBROUTINE SAMEI(IVAR)
C SAMEI INPUTS INTEGER VAR,DEFAULT LEAVES AS IS
VAR=IVAR
CALL SAME(VAR)
IVAR=VAR+.5
RETURN
END

```

```

SUBROUTINE STORE
C STORE IS THE COMPLETION ROUTINE FOR DAT ACQ.
C THIS COMPLETION ROUTINE DOES THE FOLLOWING THINGS:
C 1: WRITES THE DATA TO
C THE DISK FILE
C 2: GRAPHS EACH CHANNEL AS A FUNCTION OF TIME ON THE
C ADM TERMINAL USING THE TK GRAPHICS SOFTWARE.
C 3: SLOW MODE WORKS AS FOLLOWS:
C A: MODE IS ACTIVE WHEN IFAST DOES NOT =1 .
C B: DNCE EVERY NCOUNT CALLS TO THE STORE ROUTINE
C ONE SET OF DATA IS SAVED AND STORED ON DISK
C AND PLOTTED ON THE ADM TERMINAL.
C 4: FAST MODE WORKS AS FOLLOWS:
C A: ACTIVATED BY IFAST=1 .
C B: DATA FROM EVERY CALL TO THE STORE ROUTINE IS
C STORED ON DISK.

```

APPENDIX (cont)

```

C      C: ONCE EVERY NCOUNT CALLS A SET OF DATA IS PLOTTED
C      ON THE ADM TERMINAL IF THE GRAPHING IS TURNED ON.
C
      COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
      * RTIME,STTIME
      COMMON/ARRAYS/CONV(32),DSCRPT(15,32),DSFLAG(15),
      * FDSCRPT(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
      COMMON/CHANN/KLOAD,KCONF,KPDR,KDIFF,KRAD1,KRAD2,KRAD3
      COMMON/PROCS/IBUF(1000),NBUF,ISIZ,NCOUNT,
      * IFAST,ICHAN1,ICHAN2,J,NDRPH,IY(32),IX(2),LEVENT,IREFD
      COMMON/SCREEN/KDISP,IQLOAD,IQTEMP,QONST1,QONST2,QTEMP
      COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CERNT,DIFDR,
      * GAUAXL,GAURAD,ICONFF,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
      * ICFLAG,IFLAG,LOADF,LOADI,IFDR,IFDRF,PERCNT,PI,PISARE,
      * RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
      * SNAXL,SNCONF,SNDIFF,SNLOAD,SNPDR,SNRADL,STRSS1
C
      LOGICAL*1 CAN,SUB,ESC,FS,GS,US,DEL,LITTLA,FF
      LOGICAL*1 ISTRS(15)
      LOGICAL*1 OLDSTR(15)
      LOGICAL*1 LABSTR(7)
C
      DIMENSION KHAR(10)
      DIMENSION IY(2),IX(2)
C
      DATA IXX/1295,4095/
      DATA CAN,SUB,ESC,FS,GS,US,DEL,LITTLA/'30','32','33','34','35','37',
      * '177','141/
      DATA FF/'14/
      DATA KHAR/'60','61','62','63','64','65','66','67','70','71/
      DATA ICOUNT/1/
      DATA LABSTR/1HS,1HT,1HR,1HE,1HS,1HS,1H=/
C
C CALL STRESS AND CONFINING PRESS. CONTROL ROUTINE
      CALL RUN
C DO BOOKKEEPING FOR DIFFERENT DATA RATES
      FAST OR SLOW MODE???
C      IF FAST, WRITE ALL OF THE DATA TO DISK
C      IF SLOW, ONLY WRITE EVERY NCOUNT' TH DATA SET
C      TO THE DISK
      IF (IFAST.EQ.1) GO TO 99
      IF (ICOUNT.GE.NCOUNT) GO TO 99
      J=J+NCHAN
      IF (J.GT.ISIZ) J=1
      GO TO 125
99  CONTINUE
C WRITE DATA TO DISC
      JO=J
      J=J+NCHAN
      WRITE (ICHAN2) (IBUF(K),K=JO,J-1),LEVENT
      IRECRD=IRECRD+1
      LEVENT=0
      IF (J.GT.ISIZ) J=1
C GRAPH DATA IF NDRPH=0
      IF (ICOUNT.LT.NCOUNT) GO TO 125
      IF (NDRPH.EQ.1) GO TO 125
      IX(1)=IX(2)
      IX(2)=IX(2)+28
      IF (IX(1).NE.1295) GO TO 110
C      DRAW GRID,WRITE LABEL
      CALL GRIDVR
110  CONTINUE
C
C SCREEN DISPLAY OF INTERNAL LOAD CELL CORRECTED FOR TEMPERATURE
C GO TO VECTOR
      CALL TKPACK(GS)

```

APPENDIX (cont)

```

C   POSITION CURSOR
      CALL TKVECT (1690,3000)
C   GO TO 4010 ALPHA
      ~ CALL TKPACK(US)
C   DATA=BLACK
      CALL TKPACK(ESC)
      CALL TKPACK(DEL)
C   ERASE PREVIOUS VALUE BY WRITTING OVER WITH BLACK
      DO 112 IDUMMY=1,15
        CALL TKPACK(OLDSTR(IDUMMY))
112   CONTINUE
      ENCODE (15,1111,ISTRS) STRSS1
1111  FORMAT (G15.7)
C   GO TO VECTOR
      CALL TKPACK(GS)
C   POSITION CURSOR
      CALL TKVECT (1690,3000)
C   GO TO 4010 ALPHA MODE
      CALL TKPACK(US)
C   SET DATA LEVEL = WHITE
      CALL TKPACK(ESC)
      CALL TKPACK(LITTLA)
C   WRITE VARIABLE TO GRAPHICS SCREEN
      DO 114 IDUMMY=1,15
        CALL TKPACK(ISTRS(IDUMMY))
        OLDSTR(IDUMMY)=ISTRS(IDUMMY)
114   CONTINUE
      CALL TKPACK(GS)
      CALL TKVECT(1295,1560)
      CALL TKPACK(US)
      CALL TKPACK(CAN)
119   CONTINUE
      DO 120 K=1,NCHAN
        IY(1)=IY0(K)
        IY(2)=.76171875*FLOAT(IBUF(J0+K-1))+1560.
        IF (IY(2).GT.3120) IY(2)=3120
        IF (IY(2).LT.0) IY(2)=0
        CALL TKPACK(GS)
        CALL TKVECT(IX(1),IY(1))
        CALL TKVECT(IX(2),IY(2))
        IF (IX(1).NE.1295) GO TO 111
        K2=K+1STCHN
        IF (K2.GT.10) K2=K2-10
        IF (K2.GT.10) K2=K2-10
        IF (K2.GT.10) K2=K2-10
        CALL TKPACK(US)
        KHAR(K2)=KHAR(K2).AND.*177
        CALL TKPACK(KHAR(K2))
111   IY0(K)=IY(2)
        CALL TKPACK(US)
        CALL TKPACK(CAN)
120   CONTINUE
        IF (IX(2).GE.4095) IX(2)=1295
C
C   EXIT THE SUBROUTINE
C
125   CONTINUE
      ICOUNT=ICOUNT+1
      IF (ICOUNT.GT.NCOUNT) ICOUNT=1
      NBUF=NBUF+1
      IF (NBUF.LE.0) TYPE 9999
9999  FORMAT (///' HELP!! DATA OVERRUN!!!')
      RETURN
C
C
300   CONTINUE

```


APPENDIX (cont)

```

301      TYPE 301
      FORMAT (////,' BAD WRITE TO DISK!!!!!!!!!!!!!!')
      IF (J.GT.ISIZ) J=1
      GO TO 125

```

```

C
C
310      CONTINUE
CALL CLOSEC(ICHAN2)
STOP ' END OF FILE REACHED!!'
END

```

```

      SUBROUTINE SYSINT(IFLAG)
C SYSINT INITIALIZES SYSTEM, ALL VALVES, IFLAG
      IFLAG=0
      IDRCR="167770
      IDROUT="167772
C DISABLE I/O CARD INTERRUPT CAPABILITY
      CALL IPOKE(IDRCR,0)
C FIRST OPEN ALL VALVES EXCEPT VALVE 0
      CALL IPOKE(IDROUT,"177776)
      RETURN
      END

```

```

      SUBROUTINE VALOFF(IVALVE)
C VALOFF DE-ENERGIZES VALVE 'IVALVE', (0-15)
      IDROUT="167772
      IBIT=2**IVALVE
      CALL IPOKE(IDROUT,IBIT.OR.IPEEK(IDROUT))
      RETURN
      END

```

```

      SUBROUTINE VALON(IVALVE)
C VALON ENERGIZES VALVE 'IVALVE', (0-15)
      IDROUT="167772
      IBIT=2**IVALVE
      IBIT=.NOT.IBIT
      CALL IPOKE(IDROUT,IBIT.AND.IPEEK(IDROUT))
      RETURN
      END

```

C

```

      SUBROUTINE WTACQ(ILUN)
C WTACQ WRITES FULSCL,FRATE,INTCNT,ISTCHN,NCHAN,PRESET,
C      STTIME TO DISC
      COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
      * RTIME,STTIME
      WRITE (ILUN) FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
      * RTIME,STTIME
      RETURN
      END

```

APPENDIX (cont)

```

SUBROUTINE WTARAY(ILUN)
C WTARAY WRITES ARRAYS CONV,IRTCNT,RATES,SCANS,TIMSTR TO DISC
COMMON/ARRAYS/CONV(32),DSCRIPT(15,32),DSFLAG(15),
$ FDSCR(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
C
C WRITE CONV
WRITE (ILUN) (CONV(IDUMMY),IDUMMY=1,6)
C WRITE IRTCNT
WRITE (ILUN) (IRTCNT(IDUMMY),IDUMMY=1,6)
C WRITE RATES
WRITE (ILUN) (RATES(IDUMMY),IDUMMY=1,6)
C WRITE SCANS
WRITE (ILUN) (SCANS(IDUMMY),IDUMMY=1,6)
C WRITE TIMSTR
WRITE (ILUN) TIMSTR
RETURN
END

SUBROUTINE WTHEAD(ILUN)
C WTHEAD WRITES HEADER TO DISC
COMMON/ARRAYS/CONV(32),DSCRIPT(15,32),DSFLAG(15),
$ FDSCR(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
$ RTIME,STIME
C
C WRITE FIRST FILE DESCRIPTION LINE
WRITE (ILUN) (FDSCR(IDUMMY,1),IDUMMY=1,15)
C WRITE SECOND FILE DESCRIPTION LINE
WRITE (ILUN) (FDSCR(IDUMMY,2),IDUMMY=1,15)
C WRITE NO.CHANS+FLAG
C STORE NCHAN= NO.CHANNELS + 1 EVENT FLAG
NCHAN=NCHAN+1
WRITE (ILUN) NCHAN
C CORRECT NCHAN
NCHAN=NCHAN-1
C WRITE '2' TO SIGNIFY TYPE 2 FORMAT FILE
IDUMMY=2
WRITE (ILUN) IDUMMY
C WRITE FASTEST RATE + 5 SLOWER RATES
WRITE (ILUN) FRATE,(RATES(IDUMMY),IDUMMY=1,5)
C WRITE STARTING CHANNEL NO., A/D FULLSCALE
WRITE (ILUN) ISTCHN,FULSCL
DO 385 IDUMMY=1,NCHAN
C WRITE CHANNEL DESCRIPTION
WRITE (ILUN) (DSCRIPT(I,IDUMMY),I=1,15)
C WRITE CHANNEL CONVERSION FACTOR
WRITE (ILUN) CONV(IDUMMY)
385 CONTINUE
C WRITE EVENT FLAG DESCRIPTION
WRITE (ILUN) (DSFLAG(IDUMMY),IDUMMY=1,15)
C WRITE CONVERSION FACTOR FOR FLAG CHANNEL
DUMMY=1./FULSCL
WRITE (ILUN) DUMMY
RETURN
END

```

APPENDIX (cont)

```

SUBROUTINE AXSTRS
C AXSTRS CALC. THE PRESENT DIFFERENTIAL STRESS
C REMEMBER! THE LOAD CELL'S OUTPUT IS THE DIFFERENCE BETWEEN
C THE LOAD AND CONFINING PRESSURE
C ENTER AREANW=SPEC.AREA(IN.),EXIT STRSS1=AXIAL STRESS (PSI)
C
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
$ IFAST,ICHAN1,ICHAN2,J,NUGRPH,IY0(16),IX(2),LEVENT,IREFCRD
C
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERN,T,DIFDSR,
$ GAUAXL,GAURAD,ICONFP,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
$ ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
$ RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
$ SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
C MEASURE LOAD,CONVRT. TO POUNDS
IDATA=IBUF((J-1)STCHN)+KLOAD)
RLOAD=(IDATA-LOADI)/2048.*SNLOAD
C CALC. STRESS
STRSS1=RLOAD/AREANW
RETURN
END

```

```

SUBROUTINE WTRSTR(ILUN)
C WTRSTR WRITES RESTART FILE
COMMON/ACQDAT/FULSCL,FRATE,INTCNT,ISTCHN,JRATE,NCHAN,PRESET,
$ RTIME,STTIME
COMMON/ARRAYS/CONV(32),DSCRPT(15,32),DSFLAG(15),
$ FDSCRPT(15,2),IRTCNT(6),JUNKR(5),RATES(6),SCANS(6),TIMSTR(2)
COMMON/CHANN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
COMMON/POPFLG/IPOP
COMMON/PROCES/IBUF(1000),NBUF,ISIZ,NCOUNT,
$ IFAST,ICHAN1,ICHAN2,J,NUGRPH,IY0(32),IX(2),LEVENT,IREFCRD
COMMON/SCREEN/KDISP,IQLOAD,IQTEMP,QONST1,QONST2,QTEMP
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERN,T,DIFDSR,
$ GAUAXL,GAURAD,ICONFP,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
$ ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
$ RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
$ SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
CALL WTHEAD(ILUN)
CALL WTRAY(ILUN)
CALL WTACQ(ILUN)
CALL WTPAR(ILUN)
RETURN
END

```

```

SUBROUTINE WTPAR(ILUN)
C WTPAR WRITES TEST PARAMETERS TO DISC
COMMON/CHANN/KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
COMMON/TEST/ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERN,T,DIFDSR,
$ GAUAXL,GAURAD,ICONFP,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
$ ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
$ RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
$ SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
C
WRITE (ILUN) ACPSI,AREANW,AXLCON,CIRREF,CONDSR,CPERN,T,DIFDSR,
$ GAUAXL,GAURAD,ICONFP,ICIRI,ICIRF,ICONFI,ICONFF,IDIFFI,
$ ICFLAG,IFLAG,LOADF,LOADI,IPORE,IPOREF,PERCNT,PI,PISARE,
$ RADCON,RLOAD,RSFLAG,SPDIA,SPDIAR,
$ SNAXIL,SNCONF,SNDIFF,SNLOAD,SNPORE,SNRADL,STRSS1
WRITE (ILUN) KLOAD,KCONF,KPORE,KDIFF,KRAD1,KRAD2,KRAD3
RETURN
END

```