Acknowledgments

This research is sponsored partially by the Ballistic Missile Defense Organization (BMDO), formerly the Strategic Defense Initiative Organization (SDIO), the Air Force Phillips Laboratory, under Grant No. F-29601-91-C-0031, and the Department of Energy's Research Program, under Grant No. DE-FG03-93ER75877/M001, to the University of New Mexico's Institute for Space and Nuclear Power Studies (UNM-ISNPS).

The authors are grateful to Ben Wernsman of UNM-ISNPS, for his help with experiments and discussions of results, and to Iouri Djashvili and Vladimir Kaibyshev, of the Russian Research Center, Kurchatov Institute, for advice on data acquisition and interpretation and for providing the original design and fabrication of the hardware.

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ng

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

A TRANSIENT MODEL OF A CESIUM-BARIUM DIODE

James Robert Luke

B. S. Physics, Boise State University, 1992

M. S. Nuclear Engineering, University of New Mexico, 1994

In this work a transient model of a Cs-Ba diode is developed, and a series of experiments is performed using a diode equipped with Langmuir probes. The Langmuir probe data show that the electron energy distribution is non-Maxwellian at low discharge currents, indicating the presence of an electron beam from the emitter. Experimental results also showed that the plasma properties are non-homogeneous across the 1 mm diode gap; the electron temperature and plasma potential were higher near the emitter and the plasma density was higher near the collector. Experimental evidence is presented to show that the discharge contracts to a filament below the maximum thermal emission current.

The effect of changing Ba pressure on the I-V characteristics is investigated experimentally. Increasing Ba pressure is found to have the following effects: (a) it decreases the minimum voltage drop, (b) makes the discharge less prone to oscillations, and (c) reduces the hysteresis of the I-V curves.

Experimental I-V curves show the presence of two knees at different thermal emission currents. The presence of adsorbed Cs on the emitter lowers the emitter work function by a small amount, increasing the emission current. The minimum observed value of emitter work function at the second knee is the same as the minimum work function for pure Ba on a molybdenum electrode published in the literature.

Based on the comparison of the model predictions with experimental measurements, it is found that the electron beam component of the discharge current is significant. In spite of this electron beam, the good agreement between the calculations

and the experiment suggests that the model assumption of a Maxwell-Boltzman electron energy distribution is justified for calculation of the rate coefficients.

The transient model calculated I-V curves compare well with the experimental I-V curves. The model predictions of electron temperature, plasma density, and plasma potential in the steady state and as a function of time during discharge also compare well with measured values.

The model calculations show that the Cs pressure in the gap decreases during the discharge to an equilibrium value lower than the original pressure. The effect of the desorption rate of Cs on the time for the pressure to reach this equilibrium is calculated. Increasing the value of the desorption energy is found to increase the hysteresis of the calculated I-V curves. An empirical value of 1.75 eV for the desorption energy is determined by comparison of the hysteresis of calculated and measured I-V curves.

Table of Contents

Abstract.....	v
List of Figures.....	ix
List of Tables.....	xi
Nomenclature.....	xii
1. Introduction.....	1
1.1 Cs-Ba Tacitron.....	5
1.2 Modeling.....	5
1.3 Previous Work.....	6
2. Objectives and Approach.....	13
3. Experimental Setup.....	15
3.1 Planar Cs-Ba Tacitron.....	15
3.2 Tacitron Test Facility.....	17
3.3 A Cs-Ba Diode.....	20
3.4 Probe Measurements.....	22
4. Transient Model of the Cs-Ba Diode.....	25
4.1 Plasma Discharge Model.....	25
4.1.1 Assumptions.....	26
4.1.2 System of Equations.....	27
4.1.3 Voltage-Driven Transient Discharge Model Solution Method.....	38
4.1.4 Voltage-Driven Discharge Model Results.....	41
4.1.5 Current-Driven Transient Discharge Model Solution Method.....	43
4.2 Current Source Circuit.....	44
4.2.1 Circuit Analysis.....	44
4.2.2 Circuit-Driven Transient Model Solution Method.....	47
4.2.3 Circuit-Driven Transient Model Results.....	50
5. Model Calculations Compared to Probe Measurements.....	57
5.1 Comparison of Hollow Collector and Solid Collector Diodes.....	57
5.2 Investigation of Model Assumptions.....	59
5.2.1 Contraction of the Discharge.....	60
5.2.2 Homogeneity of the plasma.....	62
5.2.3 Electron Energy Distribution.....	66
5.3 Thermalization of the Emitter Beam Electrons.....	69
5.3.1 Langmuir Wave Interactions.....	70
5.3.2 Electron Temperature.....	71
5.3.3 Collector Current.....	73
5.4 Steady-State Probe Data and Calculations.....	74
5.4.1 Current Driven Discharge Model Results.....	76
5.4.2 Variation of the Plasma Parameters During Measurement.....	78
5.5 Changing Plasma Conditions in Time.....	83
5.6 Desorption of Cesium From the Electrode Surfaces.....	90

5.6.1 Effect of H on the I-V Characteristics.....	92
5.7 Experimental Results	94
5.7.1 Effect of Barium Pressure on I-V Characteristics.....	95
5.7.2 The Second Knee	97
6. Summary and Conclusions	102
6.1 Recommendations for Future Work	105
Appendices	
Appendix A Vapor Pressure of Cesium and Barium.....	107
Appendix B: Probe Theory	110
Appendix C: Schottky Effect	117
Appendix D: Experimental Uncertainty	121
Appendix E: Source Codes	125
Appendix F: Capacitor Time Constant.....	134
References.....	135
Index.....	139

List of Figures

Figure 1.1 Typical I-V Characteristic	11
Figure 3.1 Cross Section of the Planar Tacitron.....	16
Figure 3.2 Tacitron Test Facility	19
Figure 3.3 Cross Section View of the Cs-Ba Diode With Two Langmuir Probes.....	21
Figure 3.4 Probe Location in the Discharge Gap	23
Figure 3.5 A Photograph of the Assembled Diode.....	23
Figure 4.1 Electron Motive Diagram for the Cs-Ba Diode.....	28
Figure 4.2 Comparison of the Transient and the Steady-State Models	42
Figure 4.3 A Schematic of the Cs-Ba Tacitron Control Circuit.....	46
Figure 4.4 Assumed Source Current in the Model	46
Figure 4.5 Flow Chart of the Circuit-Driven Transient Model	49
Figure 4.6 Comparison of Measured and Calculated Voltage and Current in I-V Mode	51
Figure 4.7 Comparison of Measured and Calculated I-V Characteristics.....	54
Figure 4.8 Normal Schottky Current as a Function of Voltage.....	55
Figure 4.9 Experimental I-V Curves at Different Cesium Pressures.....	55
Figure 5.1 Comparison of Solid and Hollow Collector Diodes	58
Figure 5.2 Oscillation of Probe Characteristic Below the Knee.....	61
Figure 5.3 Source Current Used in Time-dependent Probe Measurements	63
Figure 5.4 Oscillation of Probe Characteristic Below the Knee in I-V Mode	64
Figure 5.5 Comparison of Plasma Parameters Near the Emitter and Collector	65
Figure 5.6 Probe Characteristics Near the Emitter and Near the Collector	67
Figure 5.7 Energy of the Wave and Energy Deposited in the Plasma.....	72
Figure 5.8 Voltage and Current Measurements with T_{Cs} for Fixed Load Resistance	75
Figure 5.9 Comparison of Model Calculations with Steady-State Probe Measurements	77
Figure 5.10 Voltage and Current as a Function of Time at Collector and Probe.....	80
Figure 5.11 Change in Electron Temperature During Probe Measurement.....	81
Figure 5.12 Measured and Calculated Electron Temperature and Plasma Density.....	85
Figure 5.13 Electron Temperature and Plasma Density for Two Cs Pressures	86
Figure 5.14 Calculated Cs Pressure and Cs Coverage	88
Figure 5.15 The Effect of Desorption Energy on the Time to Reach Equilibrium	91
Figure 5.16 Effect of the Desorption Energy on the Hysteresis of I-V Curves	93
Figure 5.17 Effect of Barium Pressure on the I-V Characteristic	96
Figure 5.18 I-V Curves With Second Knees	98
Figure A.1 Vapor Pressure of Cesium as a Function of Temperature.....	108
Figure A.2 Vapor Pressure of Barium as a Function of Temperature.....	109
Figure B.1 Typical Probe Circuit.....	111
Figure B.2 Typical Probe Characteristic	111

Figure B.3 Probe Characteristic Showing Deviation From a Maxwell Distribution	115
Figure C.1 Schottky Effect.....	118
Figure C.2 Electric Fields Due to Patches With Different Work Functions.....	118
Figure C.3 Microphotographs of the Electrode Surfaces.....	120
Figure D.1 Calculated Plasma Potential.....	124

List of Tables

Table 5.1	Comparison of Measured and Calculated Collector Current from Probe Data	70
Table 5.2	Calculated Plasma Parameters at the Beginning and End of the Probe I-V Characteristic	82
Table 5.3	Emitter Work Functions in Pure Ba Vapor	99

Nomenclature

English

A	Einstein A-coefficient (s^{-1}), Richardson constant ($120 \text{ A/cm}^2\text{K}^2$)
C	a constant
D	desorption rate ($m^{-2}s^{-1}$)
dt	time step (s)
E	energy (eV), electric field (V/m)
H	desorption energy (eV)
I	current (A)
J	current density (A/m^2)
k	Boltzman's constant ($1.38 \times 10^{-23} \text{ J/K}$)
m	electron mass ($9.109 \times 10^{-31} \text{ kg}$)
M	ion mass (Cs^+ : $2.207 \times 10^{-25} \text{ kg}$)
n	plasma density (m^{-3})
N	neutral atom density (m^{-3})
P	pressure (Pa)
q	electronic charge ($1.602 \times 10^{-19} \text{ C}$)
R	resistance (Ω)
RF	rate coefficient (m^3s^{-1})
S	area (m^2)
t	time (s)
T	temperature (K)
v	speed (m/s)
V	without subscript: volume (m^3)
V	with subscript: voltage, potential

Greek

ΔV	sheath potential (eV)
ε	energy
ε_0	permittivity of free space, ($8.85 \times 10^{-12} \text{ F/M}$)
ϕ	work function (eV)
Φ	particle flux ($m^{-2}s^{-1}$)
λ	characteristic length (m)
Λ	parameter
σ	surface density (atoms/monolayer)
τ	capacitor time constant (s)
θ	coverage (fraction of monolayer)
χ	fraction of radiation lost

Subscript

0-4	energy state
a	adsorption
A	atoms
ASE	anomalous Schottky effect
B	Bohm
Ba	barium
C	collector, capacitor
CE	collector to emitter (voltage drop)
Cs	cesium
e	electron
E0	electron emission
EM	emitter
eq	equivalent
ex	excited
f	floating
i	ion
j,k	Cs excited state indices
L	load
p	plasma, probe
r	random
S	surrounding, shunt
SE	Schottky effect
source	current source
T	transistor
th	thermal

Superscript

eff	effective
-----	-----------

1. Introduction

There are three basic categories of remotely controlled switches in use today: mechanical switches or relays; semiconductor devices such as transistors and thyristors; and gas switches such as vacuum tubes, thyratrons, and tacitrons. Each type of switch is well suited to a particular type of application and range of operating conditions.

Mechanical relays, sometimes called solenoid switches, are simple to build and can carry high currents. They are rugged, but are limited as to how fast they can turn on and off, tend to be large and heavy, and suffer from reduced efficiency over time due to erosion of the contact points caused by arcing between the contacts. In one common application, solenoid switches are used to turn on the high current in automobile starter circuits.

Semiconductor switching elements have many desirable performance characteristics such as fast switching frequency, small size, and low cost. They also have a low forward voltage drop when conducting, which gives high switching efficiency. Switching efficiency is related to the forward voltage drop, V_{CE} , across the switch when conducting, and the voltage applied across the terminals of the switch, V_T , as:

$$\eta = \frac{V_T - V_{CE}}{V_T} . \quad (1.1)$$

Despite their many advantages, the application of semiconductor switches is somewhat limited by their vulnerability to high temperatures ($> 200^\circ\text{C}$) and both neutron and ionizing radiation. When operated at high temperatures, the lifetime and performance of semiconductor devices is degraded (Bromstead et al. 1993), and nuclear radiation causes displacement defects in the crystal structure (van Lint et al. 1980). Despite these limitations, semiconductor switching elements are used in power conditioning units of space nuclear power systems.

Nuclear power systems with static energy conversion devices are desirable for space applications, because of their inherent reliability and freedom from maintenance due to the absence of moving parts. Examples of static conversion systems are thermoelectric generators (TE) and thermionic converters (TI). These systems convert heat directly into electricity without any intermediate thermodynamic cycle. Each of these energy conversion systems has been demonstrated in space, on U. S. or Soviet nuclear reactor powered systems. Because neutron and gamma radiation from the reactor can cause insulation breakdown, the output voltage of these devices is low, < 100 V (Sawyer et al. 1968). The low output voltage and high power requires the use of a large diameter, massive electrical bus between the power conversion system and the power user (the payload) to minimize power loss due to Joule heating. A massive bus is very costly to place in space. To lower the overall system mass and in turn the launch cost, a power conditioning sub-system is used to convert the low voltage DC output from the energy conversion system to high voltage low current power for transmission to the payload. The power conditioning unit usually consists of semiconductor inverters and a step-up transformer. The semiconductor inverters must be cooled and shielded from radiation, which increases the mass and cost of the power conditioning system. The mass of such a power conditioning unit could be as much as 25% of the total mass of the power system (Mills and Van Hagan 1994). Therefore there is a need for power conditioning components that are light weight and capable of operating at high temperature and in radiation environments. Gas switches have these capabilities.

There are several types of gas and vacuum switches. While each is most suitable for certain applications, they all have some features in common. They consist of a hot cathode, or emitter, which is the source of electrons, a colder collector, which gathers the electrons that have crossed the gap from the emitter, and a control electrode (grid) placed between the emitter and collector. Thermionic emission occurs when free electrons in a metal have enough thermal energy to escape from the surface of the metal. The amount

of energy required to remove an electron from the surface is called the work function, and its value depends on the type of metal, microscopic surface geometry, surface coatings, crystal orientation, etc. (Herring and Nichols 1949). The lower the work function, the more electrons can escape from the metal, and the higher the emission current density.

A vacuum triode has the emitter, grid and collector enclosed in an evacuated casing. Vacuum triodes are completely grid controlled (turned on and off by the application of positive and negative potentials to the grid, respectively), but they have forward voltage drops on the order of 1 kV. This large voltage is required to move electrons through the space charge between the electrodes. This limits the use of vacuum tubes to high voltage applications.

The space charge effect in vacuum tubes is alleviated by filling the tube with a low pressure gas. When the switch is in the conducting state, the gas becomes ionized and neutralizes the space charge. The thyatron, for example, has a forward voltage drop much lower than vacuum tubes, the lowest value being close to the first ionization potential of the fill gas. Hydrogen is often used in thyatrons. The thyatron is kept in the off state by maintaining a negative potential on the grid, and turned on (put into the conducting state) by the application of a positive potential to the grid. However, it can only be turned off by removing the anode potential, which makes it undesirable for modulation of DC electric power in a power conditioning unit.

The plasmatron is another type of gas switch, which is completely grid controlled and has a low forward voltage drop. It utilizes an auxiliary discharge from an auxiliary emitter, which allows the main discharge to be controlled by the grid. Although the modulation frequency of plasmatrons can be as high as 100 kHz and the forward voltage drop less than one volt, the auxiliary discharge makes fabrication complex and limits the hold-off voltage (the maximum voltage that can be applied across the switch in the off

state) to approximately the first ionization potential of the fill gas (helium has the highest first ionization potential, 25.4 eV).

Another type of gas switch that is completely grid-controlled, has both a low forward voltage drop and a large hold-off voltage, was developed in 1954 by E. O. Johnson and co-workers at RCA (Johnson et al. 1954); they called it the "tacitron". This device incorporates the best features of the plasmatron and the thyatron. The tacitron is ignited (turned on) by a positive grid potential like the thyatron, but the grid design is such that it can be turned off when a negative potential is applied to the grid. The early hydrogen tacitrons had relatively high (> 10 V) forward voltage drops to be of interest for power conditioning in low voltage space power systems (< 100 V) because of the high ionization potential of hydrogen (13.6 eV).

Tacitrons were further developed in the 1970's in the former Soviet Union, using cesium (Cs) as the fill gas (Kaplan et al. 1977). Cesium not only has the lowest first ionization potential of any stable element (3.89 eV), but it can also be used to lower the work function of the electrodes. Alkali metal atoms such as Cs adsorb on the surface of the refractory metal electrodes, producing an electric field that lowers the work function and therefore increases the thermionic emission current. The work function of the electrode depends on the coverage of Cs on the surface, which increases with Cs vapor pressure and decreases with surface temperature. The grid is much cooler than the emitter and therefore has more adsorbed Cs and a lower work function. To prevent premature breakdown of the tacitron due to thermionic emission from the grid, the grid temperature had to be kept as low as possible, limiting the emitter temperature to ≤ 1000 K. In addition, they tried to keep the grid work function as high as possible by maintaining a low Cs pressure ($\sim 10^{-2}$ Torr), but this makes the emitter work function high as well. The combination of high emitter work function and low emitter temperature limited the maximum current density in Cs tacitrons to ~ 1 A/cm².

1.1 Cs-Ba Tacitron

To overcome the low current performance of the Cs tacitron, Kaibyshev et al. (1972) at the Kurchatov Institute in the former Soviet Union added low pressure barium (Ba) vapor (10^{-4} -- 10^{-3} Torr) to the Cs vapor. Since Ba has two valence electrons, compared to one for Cs, it adsorbs much more strongly to the electrode surfaces than Cs, and relatively high Ba coverage on the emitter surface is possible with relatively low Ba pressure. This allows the emitter work function to be lowered without otherwise affecting the discharge (Baksht et al. 1970). The minimum work function of a grid coated with adsorbed Ba is greater than the minimum work function of the same grid coated with Cs (Magera and Davis 1994), which allows the use of higher emitter temperatures (1400 -- 1500 K) without unacceptable levels of emission from the grid.

Using the Cs-Ba tacitron with a thick (0.5 mm) grid, current densities up to 10 A/cm^2 have been achieved, with hold-off voltage as high as 200 V, and modulation frequencies up to 20 kHz (supply limited) at voltage drops as low as 2.5 V (El-Genk et al. 1993, Wernsman et al. 1992, and Murray et al. 1993). Because of its ability to operate at high temperature and in the presence of radiation, the Cs-Ba tacitron is ideally suited for use in the power conditioning sub-system of space nuclear power systems, or other applications in high-temperature or radiation environments.

1.2 Modeling

Cesium and Cs-Ba tacitrons have been studied in the former Soviet Union for many years. Since 1990, investigation of the Cs-Ba tacitron has proceeded simultaneously at the Russian Scientific Center - Kurchatov Institute and the University of New Mexico's Institute for Space and Nuclear Power Studies (ISNPS). Some of these studies has focused on the understanding of the physical processes taking place inside the

tacitron during operation, and the use of test results to contribute to the development of higher performance prototype devices. An important tool in gaining this understanding is modeling. A model is a system of equations that describe the physical processes in a system. The equations are solved for some parameter that can be measured, and this parameter is compared to experimental results. If good comparison is found between the calculations and experimental data for a range of conditions, then it can be concluded that the system of equations accurately describes the actual physical processes in the device.

Modeling is a very important research and design tool for two reasons: a model can calculate physical quantities that cannot be measured, and it can predict experimental results for conditions that are beyond the capability of the existing experimental setup. In most cases, the system of equations used to describe the device includes parameters that are not or cannot be measured in the experiment. For example, although experiments can be devised to measure the Cs coverage on a metal surface under certain conditions, the coverage cannot be measured in the Cs-Ba tacitron during the discharge. However, the Cs coverage can be calculated in a model of the Cs-Ba tacitron. Models of Cs diodes and tacitrons have been developed by Baksht et al. (1977, 1978a, and 1984) and Cs-Ba diode and tacitron models have been developed by Murray et al. (1993) and Murray (1993), respectively. These models are described in the next section.

1.3 Previous Work

Much investigation, both experimental and theoretical, has been done on low temperature Cs diodes and tacitrons by F. G. Baksht and co-workers (Baksht et al. 1970, 1977, 1978a, and 1984). Based on experimental measurements, Baksht et al. (1970) showed that in a Cs diode, when the Cs vapor pressure is $\leq 10^{-2}$ Torr and the voltage drop across the diode is low (a few volts), the spatial variations of particle density and

energy are small. This allowed them to use the conservation laws for particle density and energy to develop a system of equations that describes the behavior of the plasma in a Cs diode (Baksht et al. 1977). For example, at steady state, the ionization rate must be equal to the rate of ion loss due to recombination (the only ion loss mechanism they considered). Other equations are included for electron energy balance, densities of ground state and the first four excited states of Cs, current balance at the electrodes and a voltage balance.

In addition to the assumption that all conditions are homogeneous across the diode gap, they assumed (again based on experimental measurements) that the plasma electrons have a Maxwell-Boltzman distribution of energies. This is a simplifying assumption in that the cross sections for ionization and atomic excitation can be averaged over a known and relatively simple energy distribution. Without this assumption, the distribution function must be calculated by solving the Boltzman equation (Chen 1984), which is computationally intensive.

The calculations of this steady-state model were compared to experimental data obtained from a Cs diode equipped with both Langmuir probes and optical spectroscopy for plasma diagnostics. Using this set of equations, they were able to show reasonable agreement between calculations and experimental data for Cs ion density, electron energy, and voltage drop.

After verifying the assumption that steady-state conditions in a low pressure Cs diode could be adequately modeled by the set of equations described above, Baksht et al. (1978a) extended their steady-state theoretical analysis from a diode to a tacitron. Because a tacitron has two discharge volumes separated by a grid (emitter-grid gap and grid-collector gap), and their grid was a thin wire mesh, they used a two-region analysis, where each region was described by equations very much like their earlier work (Baksht et al. 1977) on the diode, with appropriate coupling between the regions. For example, the ion density equation in each region has an additional term that represents the net flux

of ions from one region to the other. Although the important processes in a grid-controlled switching element (ignition and extinguishing) are time-dependent, they developed this steady-state model to describe the conditions that exist just prior to applying the extinguishing voltage pulse to the grid. The model calculated the voltage drop, electron temperature, ion density, and Cs ground state and excited state densities for various conditions. Again they showed reasonable agreement between the calculations and experimental results.

In order to investigate the processes causing extinguishing of the tacitron, Baksht et al. (1984) developed a time-dependent model of a Cs tacitron. They continued to use the assumptions that particle density and energy were spatially uniform in each region, and the electrons followed a Maxwell-Boltzman energy distribution. The time-dependent equations were again based on the conservation laws, but now have the form $\frac{d\psi}{dt} = \text{source} - \text{loss}$, where ψ represents the relevant quantity (particle density, energy, etc.) and the rate of change of ψ is equal to the difference between the production rate of ψ and the loss rate. For example, if ψ represents plasma density, the rate of change of plasma density equals the difference between the ionization rate and the ion loss rate. These differential equations usually cannot be integrated directly because each quantity depends on the others (ionization rate depends on neutral atom density, electron density, electron temperature, and so on), so numerical integration techniques are used. Baksht et al. (1984) calculated the plasma density, plasma potentials in each region, current decay time after extinguishing, etc. as a function of time, and showed good agreement with experimental results.

The system of equations and solutions developed by Baksht et al. (1977, 1978a, and 1984) described the conditions inside a closed volume Cs diode or tacitron. The Cs-Ba tacitron under test at ISNPS, which is described in Chapter 3, has an open discharge volume. This means that during discharge, Cs atoms and ions are free to move in and out

of the discharge volume, which can change the particle densities and pressures in the gap during the discharge. One consequence of this pressure change is that it will change the amount of Cs vapor adsorbed on the electrode surfaces. It has been shown that desorption of Cs atoms from the surfaces can greatly extend the time it takes the discharge to reach equilibrium (Murray et al. 1992). The closed-volume Cs devices also ran at lower current densities than the Cs-Ba tacitron. These differences between the Cs and Cs-Ba tacitron required changes to the model.

The steady-state equations of Baksht et al. (1977 and 1978a) were modified by Murray (Murray et al. 1993 and Murray 1993) to better represent the Cs-Ba tacitron at ISNPS. The open discharge volume required additional terms in the equations for Cs atom and ion densities and electron energy, to describe particle transport into and out of the discharge volume. Unlike the tacitron used by Baksht et al. (1978a and 1984) which had a thin ($\sim 50 \mu\text{m}$) wire mesh grid, the tacitron at ISNPS has a thick grid (0.5 mm, see Chapter 3). The use of a thick grid required a three-region analysis (emitter-grid gap, grid holes, and grid-collector gap) instead of the two-region analysis used by Baksht et al. (1977 and 1978a).

The steady-state models of the Cs-Ba diode and tacitron calculated the voltage drop as a function of the discharge current. The minimum voltage drop calculated by the diode model was shown to agree with experimental data (Murray et al. 1993). The Cs-Ba tacitron model proved useful in predicting the effect of grid transparency on the voltage drop. Although balance equations for Ba particle density and energy were not used in the models of the Cs-Ba diode or tacitron, agreement of the calculations with experimental data showed that the presence of low pressure Ba vapor in the volume does not significantly affect the discharge.

Although the steady-state calculations of Murray et al. (1993) and Murray (1993) were useful in predicting the voltage drop under various conditions, the experimental Cs-Ba tacitron did not have any plasma diagnostic equipment available to measure the

plasma parameters such as electron energy or plasma density. Furthermore, steady-state analysis has limitations. It cannot be used to investigate transient processes such as current modulation or the hysteresis in the current-voltage (I-V) characteristic of the tacitron. When the tacitron is operated in I-V mode, the current through the device is increased, and then decreased, while the voltage drop is measured. A typical I-V curve is shown in Figure 1.1. The left side of the curve in Figure 1.1 is the voltage drop measured when the current is increasing, and the right side is when the current is decreasing. The hysteresis, or difference in the voltage for a given value of current, is due to changing conditions in the plasma during the test. This phenomenon will be investigated and explained more fully in Chapter 5.

An important condition which can affect the comparison of the experimental data to model calculations is the way the experiment is controlled by the test circuitry. The circuit does not affect the steady-state conditions, but it can have a strong effect on the transient response of the diode or triode. The shape of the I-V curve in Figure 1.1 depends partly on the behavior of the test circuit and partly on plasma conditions. It is believed that the difference between the left and right sides of the I-V characteristic is due to a change in the Cs pressure in the gap, and a change in the amount of Cs vapor adsorbed on the surfaces. This change in Cs pressure and coverage is another time-dependent phenomenon, which will be discussed in Chapter 5. In this work a transient model is developed and used to investigate these time-dependent phenomena.

Because of the complexity of the triode configuration, a simpler diode model is developed in this work, to verify the governing equations and the solution procedure, as was done by Baksht, et al. (1977) and Murray et al. (1993). The diode model allows investigation of surface and volume processes, which are the same in both the diode and triode, but are simpler to calculate in the diode model. After the equations used to model these processes are verified in the simpler diode system, they can be used in a complete model of the Cs-Ba tacitron, which will be presented in a future work.

Figure 1.1 Typical I-V Characteristic.

For verification of the model calculations, experiments are performed using a Cs-Ba diode equipped with Langmuir probes. Using Langmuir probes, the electron energy, ion and electron densities, and plasma potential are measured and compared with model calculations, and some of the assumptions used in the model are tested. The model is verified by comparison of the model calculations with experimental data, including the I-V characteristics and plasma properties. The next chapter describes the objectives of this work in more detail.

2. Objectives and Approach

There are two main objectives of this work, namely: (1) to develop a time-dependent model of the low-pressure discharge that exists in the Cs-Ba diode, and (2) to perform experimental investigations to verify some of the assumptions in the model and the calculations of the model.

Development of the transient model consists of two parts: a) a discharge model of the plasma, and b) characterization of the external test circuit. Each part is tested separately, and the combined model is tested and compared to experimental data.

The discharge model calculates plasma density, densities of ground state and excited states of Cs atoms, and electron energy, as well as discharge current, voltage drop, sheath potentials and Cs coverage on the electrodes, all as a function of time. The equations used are continuity equations for particle density and energy, similar to the equations used by Baksht et al. (1977 and 1984) and Murray et al. (1993).

The second part of the model development is analysis and characterization of the external control circuit. Based on the circuit analysis, a set of equations is formulated to describe the circuit. These equations are then incorporated into the transient discharge model and compared to experimental data obtained at ISNPS.

Experimental data is obtained using a Cs-Ba diode equipped with Langmuir probes, operated over a range of input conditions. Direct experimental measurements include the voltage drop and discharge current, as a function of time and as I-V characteristics. The I-V curves are used to verify the transient solution method and the circuit analysis. Data obtained in the diode are compared to earlier data obtained in a hollow collector diode made by configuring the tacitron as a diode with the grid acting as a collector.

In addition to the voltage and current measurements, probe measurements give electron energy, plasma density, and plasma potential, from which the sheath potentials

can be calculated. Probe data obtained while the diode is operating in a steady-state mode is used for verification of the basic equations in the Cs-Ba diode model. Time-dependent probe data is obtained for direct comparison with the transient model. Probe data is also used to investigate some of the assumptions used in the model, namely the assumption of a Maxwellian electron energy distribution, spatial homogeneity of the plasma properties, and the contraction of the discharge to a filament below the thermal emission current. The transient model is used to calculate the Cs pressure and Cs coverage on the electrodes, and to explain the hysteresis of the I-V characteristics.

The next chapter describes the experimental device, the test stand and data acquisition system, and the method of obtaining time-dependent probe data. Chapter 4 explains in detail the model system of equations and solution procedure, and the analysis of the current source circuit. Model calculations are presented and compared to experimental results in Chapter 5. In the last chapter, the results are summarized and conclusions drawn, followed by recommendations for further investigation.

3. Experimental Setup

Previous Cs-Ba tacitron experiments at ISNPS (Wernsman et al 1992, El-Genk et al. 1993, Murray et al. 1993) were performed with a cylindrical tacitron. The emitter was a molybdenum (Mo) tube, and the Mo grid and collectors were arranged around the emitter. The emitter-grid gap and the grid-collector gap were concentric annuli. Some disadvantages of this design are that the spacing between emitter and grid, or between grid and collector, can not be changed easily, and the grids are difficult to construct. To allow testing of the design and placement of the grid, a planar tacitron was purchased from Kurchatov Institute in Moscow, Russia, where it was designed and built.

3.1 Planar Cs-Ba Tacitron

The planar tacitron at ISNPS has plane-parallel electrodes and grid. The principal parts of the experimental device are shown in cross-section in Figure 3.1. The emitter and collector surfaces are the flat ends of hollow molybdenum cylinders, with surface area of 2 cm² each. Inside each electrode is an electric heater wound from tungsten wire, that heats the electrode mainly by radiation. The collector is typically kept at 700 -- 800°C during tests. To obtain the typical 1100 -- 2000°C emitter temperature, a potential of about 250 V is applied between the heater and the emitter to provide additional heating by electron bombardment. The temperatures of the emitter and collector are monitored by tungsten-rhenium thermocouples.

The grid is machined from a solid disk of molybdenum 50 mm in diameter. The working part is 0.5 mm thick and drilled with numerous small holes. Several grids are available, with holes ranging from 0.4 to 0.8 mm in diameter. The grid temperature is monitored by chromium-nickel aluminum-nickel (type-K) thermocouples. All of the electrodes and grids are insulated from each other by boron-aluminum-nitride (B-Al-N)

Figure 3.1 Cross Section of the Planar Tacitron.

ceramic rings. The distance between the emitter, grid, and collector can be changed by altering the thickness of the insulating rings. Symmetry of construction allows either electrode to be operated as the emitter, by simply reversing the electrical connections outside the vacuum chamber. In this way, the effect of gap size and grid placement can be observed to some extent without disassembling the device. The discharge volume in the tacitron is open to the surrounding area, and coupled to the Cs and Ba reservoirs through tubes in the basis flange.

The electrode and grid assembly is held together by compression springs (not shown in Figure 3.1; see Figure 3.5) and rests on a stainless steel basis flange mounted in the vacuum chamber. The flange is equipped with heaters to prevent condensation of Cs and Ba on the flange. The Ba vapor comes from a Ba reservoir under the flange. The reservoir contains solid barium and is surrounded by a thermostatically controlled heater, by means of which the Ba pressure in the discharge can be selected. Vapor pressure curves as a function of reservoir temperature for Ba and Cs are given in Appendix A.

The Cs reservoir is external to the vacuum chamber. Its temperature is controlled by a combination of water cooling and a feedback-controlled heater, which maintains the set temperature to within 0.1°C . The Cs reservoir and the pipeline connecting it with the basis flange within the vacuum chamber are surrounded by a heater to prevent Cs condensation in the pipeline. Since the Cs reservoir is colder than the Ba reservoir, the Cs vapor enters the discharge volume through a 1.0 mm orifice to prevent Ba contamination of the Cs reservoir. The temperatures of the Cs and Ba reservoirs, and of the flange, are measured by type-K thermocouples.

3.2 Tacitron Test Facility

Equipment at the tacitron test facility includes the vacuum chamber, vacuum pumps, power and control systems for the various heaters, electronic circuits to operate

the tacitron itself during experiments, a data interface system, and a computer to control the device operation and store the test data. A diagram of the test facility is shown in Figure 3.2.

The vacuum chamber is made of stainless steel and has 12 high current electrical feedthroughs, two seven-pin low current feedthroughs, and two 32-pin feedthroughs for thermocouples and voltage probes. The vacuum chamber cover is equipped with a heater and a water cooling jacket. Rough vacuum in the chamber (down to 10^{-4} Torr) is produced by liquid nitrogen sorption pumps, and high vacuum (down to 10^{-8} Torr) is produced by an ion pump. Heaters for the emitter, collector, flange, and Ba reservoir are controlled manually by adjusting the heater current until the desired temperature is reached. The emitter and Ba reservoir heaters include feedback control to maintain the set temperature. The Cs reservoir heater is controlled by an automatic temperature controller which allows the operator to enter the desired temperature. The circuits that power the actual device during testing include separate systems for the electrodes and grids, for each of the various operation modes. The operation mode can be selected via the computer. Some of the experimental data used in this work is obtained with the tacitron operating in the I-V mode, in which the external source current increases linearly, and then decreases linearly, while the current through and the voltage drop across the tacitron are measured and recorded by the computer. The behavior and construction of the current source used for I-V mode operation are explained in detail in Chapter 4.

Data acquisition is computerized, using a 386 IBM-compatible PC communicating through a GPIB interface. The system measures and stores voltage and current data from each electrode and grid, simultaneously with the temperatures of all the thermocouples.

Degassing of the device after disassembly and reassembly takes about one week. Initial outgassing of the device is done by heating the vacuum chamber cover externally

Figure 3.2 Tacitron Test Facility.

for 24 hours. Then the external heat is turned off and the water cooling of the chamber cover is turned on while the tacitron is brought slowly up to temperature. The inner surface of the vacuum chamber is colder than the device, which allows vapors to condense, aiding the vacuum pump in maintaining low background pressure. All components of the device are brought slowly up to working temperature, until a good vacuum ($\sim 10^{-6}$ Torr) is obtained with all components at or above working temperature. Then the Ba is melted by heating it to the melting point, which is higher than the running temperature, and the device is ready for operation.

Data has been obtained from the Cs-Ba tacitron to compare with the calculations of the diode transient model by configuring the tacitron as a diode (Luke and El-Genk 1994, Murray et al. 1993). This can be done by rearranging the electrical connections outside the vacuum chamber. The grid power supply is disconnected, and the grid is electrically connected to the collector, thus making the grid act as a hollow collector. Although this is a convenient method of obtaining diode data for comparison with the diode transient model, it is not known whether the grid with its numerous holes behaves the same as a solid collector. In this work, experiments are performed with an actual diode. This data is compared with data obtained using the grid as a hollow collector in Chapter 5.

3.3 A Cs-Ba Diode

For verification of the transient model calculations, and investigation of some of the assumptions in the model, a set of experiments is performed using the Cs-Ba tacitron with the grid removed, so that it is an actual diode with a solid collector. Figure 3.3 shows a 1/4 section view of the diode as tested. The left side of the figure shows the outside of the device, while the right side is a cutaway view.

Figure 3.3 Cross Section View of the Cs-Ba Diode With Two Langmuir Probes.

A set of two Langmuir probes is installed in the 1.0 mm gap between the emitter and collector. The probes are tungsten wires, 0.1 mm in diameter, that stretch across the whole gap parallel to each other and to the electrode faces. The probes are held in tension by tantalum springs in the probe holders, which are supported by stainless steel rings. The probe wires pass through grooves between two ceramic insulating rings. The grooves are cut very precisely to prevent Cs leaks from the device. To investigate the assumption that the plasma conditions are homogeneous across the discharge gap, the probes were not centered between the electrodes. Instead they are 0.75 mm from the bottom electrode and 0.25 mm from the top electrode. When the top electrode is operated as the emitter, the probe is closer to the emitter, and when the electrodes are reversed the probe is near the collector. In this way any differences in the plasma parameters near the emitter and near the collector can be discovered. The location of the two probes relative to each other is shown in Figure 3.4, in which the circle represents the end of the electrode face and the lines represent the probe wires. One probe is nearer the edge of the plasma and has more surface area exposed to the plasma than the other.

A photograph of the assembled Cs-Ba diode is shown in Figure 3.5, in which can be seen the probe holders, stainless steel rings, ceramic insulators, and basis flange as described in Figure 3.3. Also shown are the probe electrical leads, the support structure and the compression springs which hold the device together. The next section describes the way probe measurements are taken, and an explanation of the interpretation of the measurements is given in Appendix B.

3.4 Probe Measurements

Using the Langmuir probe theory as explained in Appendix B, the electron energy, ion and electron densities, and plasma potential can be calculated based on experimental measurements. The calculations are based on values read from a probe I-V

Figure 3.4 Probe Location in the Discharge Gap.

Figure 3.5 A Photograph of the Assembled Diode.

curve. At the ISNPS test facility, the varying voltage required for the I-V curve is a half-sinusoid of 8 V peak, obtained by transforming 60 Hz line voltage. The current and voltage signals from the probe are measured and recorded by the computer in the same way as other test data. Probe measurements are made in both the steady-state mode and time-dependent mode. In the former, the diode is operated in a steady-state mode by applying a constant source voltage across the diode for 15 ms while the half-sinusoid voltage is applied to the probe. Time-dependent probe data is taken with the diode operating in the I-V mode, for direct comparison with the transient model. This requires the following technique. The regular probe power supply is disconnected, and a DC voltage is applied to the probe. The probe current is measured as a function of time during an I-V pulse. Then the DC voltage is changed and the probe current is recorded during another I-V pulse. After sweeping through a range of probe voltages, the recorded data are rearranged so that for each point in time along the I-V pulse, there is a range of probe voltages and currents. This gives a probe characteristic for each point in time, from which the plasma parameters are calculated as a function of time. Using this method with existing equipment, it is possible to obtain a separate probe characteristic every 10 ms for repeatable signals. These probe measurements are presented in Chapter 5, and compared to transient model calculations. In the next chapter the model system of equations and the solution method are presented.

4. Transient Model of the Cs-Ba Diode

The transient model of the Cs-Ba diode presented in this work is an extension of the steady-state model of Murray et al. (1993). The steady-state model was unable to explain the hysteresis in the measured I-V characteristic and neglected the effect of the external circuit on the operation of the diode. That model also neglected the change in Cs coverage on the electrodes during the discharge. The transient model presented herein accounts for these two phenomena, namely the external circuit and Cs desorption from the electrodes during the discharge.

In this chapter the transient diode model is presented, including the constituent equations and the solution procedure. The development of the diode transient model consists of two parts: (a) a transient discharge model of the Cs plasma and (b) characterization of the external circuit. The discharge model solution procedure is verified by comparison of a steady-state diode model similar to that of Murray et al. (1993), re-written for the planar geometry of the present experimental device. Following analysis of the external circuit and its incorporation into the transient discharge model, I-V curves calculated by the complete transient model are compared to experimental I-V curves. In Chapter 5 the transient diode model calculations are compared with probe measurements taken in the Cs-Ba diode at the ISNPS facility, and the hysteresis of the I-V curves is explained.

4.1 Plasma Discharge Model

The equations used in the Cs-Ba diode transient discharge model are similar to those used by Baksht et al. (1977, 1978a, and 1984) and Murray et al. (1993). All of these models assume that the plasma conditions are spatially homogeneous, allowing the use of balance equations for particle density and energy to describe the plasma discharge

in the device. Unlike the model of Baksht et al. which was for a closed volume discharge, the present model and that of Murray et al. are modified to account for the open discharge volume. The planar geometry of the experimental device presently installed at ISNPS required changes in the equations of Murray et al. (1993), and further changes are explained in the following sections.

4.1.1 Assumptions

In order to model the complex process of the plasma discharge in the Cs-Ba diode, several simplifying assumptions are made. The plasma is assumed to consist of electrons, singly ionized Cs ions in the ground state, and neutral Cs atoms in the ground state and the first four excited states. The Ba pressure is much lower than the Cs pressure in the diode volume ($P_{\text{Ba}} \approx 10^{-4}$ Torr and $P_{\text{Cs}} \approx 10^{-2}$ Torr), therefore it is assumed that the electrons do not interact with Ba atoms. Since the current through the device in all experiments has been less than 15 A/cm^2 , the magnetic field due to the discharge current is small, and any magnetic field effects on the plasma are neglected. It is assumed that the electrons in the bulk plasma are thermalized by many elastic collisions, therefore the inelastic collision cross sections are averaged over a Maxwell energy distribution; the validity of this assumption is investigated in Chapter 5. The measurements of Baksht et al. (1970) showed that particle density and energy vary by about a factor of two across a 1 mm Cs diode gap under conditions similar to those used in this work. Therefore, in the present model it is assumed that the plasma is homogeneous throughout the discharge volume. This assumption is investigated in Chapter 5.

The assumption of a spatially homogeneous plasma implies the absence of any electric fields in the bulk of the plasma, and that all potential drops occur in the Langmuir sheaths near the electrodes. Since the charged particles in a plasma are free to move, they tend to shield out any potential gradients in a short distance (a few Debye

lengths), leaving the bulk plasma at a uniform potential and therefore without electric fields (Chen 1984, Chapman 1980).

The mass of the electrons is much smaller than that of the Cs ions; thus they move much faster and are more easily lost from the plasma. The loss of electrons leaves the plasma at a positive potential with respect to the surroundings. This difference in potential tends to confine the electrons to the plasma. The magnitude of the potential barrier, or sheath, adjusts itself such that the flux of electrons with enough energy to escape over the sheath exactly equals the ion flux (Chen 1984), maintaining the neutrality of the plasma. In a neutral plasma the electron density n_e equals the ion density n_i . Therefore, the density of either electrons or ions is referred to as the plasma density, n .

A diagram of the assumed potential distribution in the diode during discharge is shown in Figure 4.1. In this figure, called an electron motive diagram (Herring and Nichols 1949), the emitter is on the left, the collector on the right, and positive potential is down. The emitter and collector work functions are ϕ_E and ϕ_C , respectively, the plasma potential is V_p , and V_{CE} is the voltage drop across the diode. The emitter and collector sheath potentials are ΔV_E and ΔV_C , respectively, while ΔV_S is the potential difference across the sheath between the plasma and the surroundings. These quantities are used in the balance equations that describe the plasma discharge in the Cs-Ba diode.

4.1.2 System of Equations

The system of equations that describes the plasma discharge in the diode model includes 11 balance equations: the voltage balance; the current balance at the emitter, the collector, and the plasma boundary with the surroundings; the electron energy balance; the ion density balance; and the neutral atom density balance for the ground state and each of the four excited states of Cs atoms. These equations are supplemented by additional equations as required in order to solve for all the unknown variables.

Figure 4.1 Electron Motive Diagram for the Cs-Ba Diode.

Voltage Balance Equation

The voltage balance equates the sum of the internal voltage drops in the plasma (Figure 4.1) to the external voltage drop, V_{CE} , across the diode:

$$V_{CE} = -\phi_E + \Delta V_E - \Delta V_C + \phi_C . \quad (4.1)$$

Current Balance Equations

A current balance is performed at each electrode, and between the plasma and the surrounding region. Because of the equality of the ion and electron leakage fluxes to the surroundings, the electron current drawn from the collector, I_C , is the same as the current supplied to the emitter by the external circuit, I_{EM} . The external circuit current is the sum of the internal currents at either electrode, which include the emission current, J_{E0} , the ion current, J_i , and the fraction of the random electron current that traverses the sheath. The current balance equations at the electrodes are:

(a) at the emitter:

$$I_{EM} = S_E \left(J_{E0} + J_i - J_r e^{-\frac{q\Delta V_E}{kT_e}} \right), \quad (4.2a)$$

(b) at the collector:

$$I_C = I_{EM} = S_C \left(J_r e^{-\frac{q\Delta V_C}{kT_e}} - J_i \right), \quad (4.2b)$$

where S_E is the area of the emitter, S_C is the area of the collector, J_r is the random electron current density, and T_e is the electron temperature in Kelvin. Note that in the planar diode used in these experiments, $S_E = S_C = 2 \text{ cm}^2$. During discharge, ions from the plasma enter the sheath adjacent to the electrodes with at least the Bohm speed, V_B (Bohm 1949), hence the ion current density in equations (4.2a) and (4.2b) can be given as (Chen 1984):

$$J_i = q(0.61)n v_B = q(0.61)n \sqrt{\frac{kT_e}{M}}, \quad (4.3)$$

where q is the ion charge, n is the plasma density, k is Boltzman's constant, and M is the Cs ion mass.

The random electron current density, J_r , can be derived from the mean speed of a Maxwell distribution as:

$$J_r = \frac{qn}{4} \sqrt{\frac{8kT_e}{\pi m}}, \quad (4.4)$$

where m is the electron mass.

In addition to the sheaths adjacent to each electrode, a sheath forms between the plasma discharge volume and the surrounding non-plasma region. At this boundary, the ion current out of the volume equals the fraction of the random electron current with enough energy to escape the sheath potential, ΔV_S :

$$J_i = J_r e^{-\frac{q\Delta V_S}{kT_e}}. \quad (4.5)$$

The height of the potential barrier, ΔV_S , can be calculated by substituting for J_i and J_r from equations (4.3) and (4.4) and solving equation (4.5) for ΔV_S :

$$\Delta V_S = -\frac{kT_e}{q} \ln \left(4(0.61) \sqrt{\frac{\pi m}{8M}} \right) \approx 5.78 \frac{kT_e}{q}. \quad (4.6)$$

Equations (4.2a), (4.2b), and (4.5) are the current balance equations at the emitter, collector, and surroundings, respectively. The next equation is the electron energy balance.

Electron Energy Balance

The electron energy balance equation is somewhat different from that in the steady-state models of Baksht (1977, and 1978a) and Murray et al. (1993). Both Murray et al. and Baksht et al. used a formulation for electron-impact excitation and ionization of Cs atoms which is valid only at steady state. In that formulation, when a plasma electron loses energy in an inelastic collision with a Cs atom, causing excitation or ionization, that energy is assumed to return to the plasma unless the ion or excited atom leaves the discharge volume, or de-excites either on the surface or by emitting a photon. However, the electron energy equations of Baksht et al. and Murray et al. include loss terms for the energy of ions, excited atoms, and photons that leave the discharge volume, without considering when they actually leave the volume. Therefore, unlike the steady-state models, the transient electron energy balance accounts for the fact that energy is lost from the plasma as soon as the electrons collide with and excite or ionize a Cs atom, not after the atom or ion leaves the volume or emits a photon.

The total energy in the plasma is the average energy, $\frac{3}{2} kT_e$, times the number of electrons in the plasma, nV , where V is the plasma volume. The electrons emitted from the hot cathode, or emitter, are accelerated through the emitter sheath potential ΔV_E (as shown in Figure 4.1), immediately transferring all of their energy to the bulk plasma electrons. Electrons leaving the plasma to the electrodes or to the surroundings take energy from the plasma, because only high energy electrons can succeed in escaping the potential well created by the sheaths. Thus the electron energy balance equation in the transient model is written as:

$$\begin{aligned} \frac{d}{dt} \left(\frac{3}{2} kT_e nV \right) = & J_{E0} S_E \left(\Delta V_E + \frac{2kT_{EM}}{q} \right) - J_r S_E e^{-\frac{\Delta V_E}{kT_e}} \left(\Delta V_E + \frac{2kT_e}{q} \right) \\ & - J_r S_C e^{-\frac{\Delta V_C}{kT_e}} \left(\Delta V_C + \frac{2kT_e}{q} \right) - J_r S_S e^{-\frac{\Delta V_S}{kT_e}} \left(\Delta V_S + \frac{2kT_e}{q} \right) - R_{ex}. \end{aligned} \quad (4.7)$$

The first term on the right side of equation (4.7) is the energy input to the plasma from the emitted electrons, and the next three terms denote the energy lost to the emitter, collector, and surroundings, respectively. The term R_{ex} is the energy lost by the plasma electrons due to collisions with Cs atoms causing excitation or ionization, minus the energy returned to the plasma by electron induced de-excitation of excited Cs atoms:

$$R_{\text{ex}} = qnV \left[\sum_{j=k+1}^5 \sum_{k=0}^{j-1} N_k RF_{kj} E_{kj} - \sum_{j=k+1}^4 \sum_{k=0}^{j-1} N_j RF_{jk} E_{jk} \right]. \quad (4.8)$$

The indices (0,1,2,3,4, & 5) in equation (4.8) represent the ground state, first, second, third, and fourth excited states, and ions, respectively; N_k is the density of neutral atoms in the excited state k ; and E_{kj} is the energy difference between states k and j . The rate coefficient for electron-impact transitions from state k to state j , RF_{kj} , also called $\langle \sigma v \rangle_{kj}$, is determined by averaging the collision cross sections over a Maxwell distribution of electron energies (Murray 1993). The second summation on the right hand side of equation (4.8), which represents superelastic de-excitation of Cs atoms, only goes from 0 to 4 because ion recombination in the discharge volume is neglected.

Radiation Re-absorption

In some cases, the photon emitted when an electron in an excited atom makes a transition from a higher to a lower energy state is re-absorbed by another atom in the lower state. When the photon is re-absorbed, there is no net change in the population of either of the two states, or in the electron energy. Baksht et al. (1977) calculated the probability that an emitted photon will be re-absorbed by taking into account Doppler and Stark broadening of the spectral lines. Instead of Einstein's A-coefficient in equations (4.12) and (4.13), they calculated an effective A-coefficient for the transition from state j to state k , A_{jk}^{eff} :

$$A_{jk}^{\text{eff}} = \chi_{jk} A_{jk} , \quad (4.21)$$

where χ_{jk} is a dimensionless coefficient. The method used to calculate χ_{jk} in the diode transient model follows exactly the method of Baksht et al. (1977). The effective A-coefficients, A_{jk}^{eff} , are used in equation (4.7) and the Cs atom density balance equations.

Ion Density Balance

The ion density in equations (4.3), (4.4), (4.7), and (4.8) is determined from the ion density balance in the discharge volume. The ion density balance in the present model is the same as Murray et al. (1993):

$$\frac{dn}{dt} = \sum_{k=0}^4 [nN_k RF_{ki}] - \frac{J_i}{qV} (S_S + S_E + S_C) . \quad (4.9)$$

The subscript i represents the ionic state, RF_{ki} is the rate coefficient for ionization from state k , and S_S is the leakage area from the discharge volume to the surroundings.

Cesium Atom Balance

The neutral Cs atom density balance equations are somewhat different for ground state and excited atoms, because only ground state atoms enter the discharge volume from the surroundings, and it is assumed that only ground state atoms are desorbed from the emitter and collector surfaces. This assumption is reasonable, because of the relative magnitudes of the desorption energies of the various species, as explained in the following paragraph.

The ion desorption energy, H_i , or the energy required to remove an adsorbed ion from the surface, is related to the atom desorption energy, H_A , as follows (Levine and Gyftopoulos 1964a):

$$H_i = H_A + E_i - \phi , \quad (4.10)$$

where E_i is the ionization energy of the atom and ϕ is the electron work function of the electrode surface. The desorption energy for atoms in excited state k is:

$$H_k = H_A + E_k, \quad (4.11)$$

where E_k is the excitation energy of state k . The ionization energy of Cs, E_i , is 3.89 eV; the electron work function of the Mo collector coated with adsorbed Ba, ϕ_C , is ~ 2.2 eV (Magera and Davis 1994); the energy of the first excited state of Cs is 1.4 eV; and a typical Cs atom desorption energy is 1.85 eV. Thus, from equations (4.10) and (4.11) respectively, $H_i = 3.54$ eV and $H_1 = 2.25$ eV. Since the desorption rate from the electrode surface is proportional to the inverse exponential of the desorption energy (equation (4.16)), the desorption rate of ions from the collector is 9 orders of magnitude smaller than the desorption rate of ground state atoms, and the desorption rate of Cs atoms in the first excited state is 7 orders of magnitude smaller than ground state Cs atoms. At the hot emitter, the desorption rate of ions is 5 orders of magnitude smaller than the desorption rate of ground state atoms. Therefore, although both ions and excited Cs atoms impinge upon and adsorb on the electrode surfaces, the desorption rate of ions and excited states is negligible compared to that of the ground state. Both the emitter and collector surfaces serve as loss areas for excited atoms and ions.

The balance for atoms in excited state k , for $k = (1, 2, 3, \& 4)$, is written as:

$$\frac{dN_k}{dt} = \sum_{j=0, j \neq k}^4 nN_j RF_{jk} + \sum_{j=k+1}^4 N_j A_{jk} - \sum_{j=0, j \neq k}^5 nN_k RF_{kj} - \sum_{j=0}^{k-1} N_k A_{kj} - \frac{v_A N_k}{4V} (S_S + S_E + S_C) \quad (4.12)$$

The index 5 represents the ionic state and v_A is the mean thermal speed of Cs atoms at the average vapor temperature in the diode gap. The term A_{kj} is Einstein's A-coefficient, the inverse of the lifetime of state k , which represents the time rate of spontaneous

emission of radiation from state k to state j (Eisberg and Resnick 1985). The ground state Cs atom density balance is written as:

$$\begin{aligned} \frac{dN_0}{dt} = & \sum_{j=1}^4 [nN_j RF_{j0} + N_j A_{j0}] - \sum_{j=1}^5 nN_0 RF_{0j} - \frac{v_A N_0}{4V} (S_S + S_E + S_C) \\ & + \frac{v_A N_{A0}}{4V} S_S + \frac{\sigma D_{A,C}}{V} S_C + \frac{\sigma D_{A,E}}{V} S_E , \end{aligned} \quad (4.13)$$

where N_{A0} is the density of Cs atoms in the vapor above the reservoir. The first summation on the right side of equation (4.13) is the increase in the ground state population due to electron-induced and radiation transitions from the excited energy levels to the ground state. The second sum is the loss of ground state atoms due to excitation and ionization. The third term is the loss of ground state atoms due to adsorption onto the electrode surfaces and leakage to the surroundings, while the fourth term represents the flux of atoms entering the gap from the surroundings. The last two terms denote the change in ground state density due to atoms desorbed from the collector and emitter surfaces, respectively. The desorption of Cs atoms from the electrode surfaces is addressed in the following paragraphs.

Cesium Atom Coverage

The change in Cs atom coverage on the electrode surfaces with respect to time during discharge is calculated from the difference between the flux of atoms and ions to the surface, Φ , and the desorption rate from the surface, D_A , as:

$$\frac{d\theta}{dt} = \frac{(\Phi - D_A)S}{\sigma} , \quad (4.14)$$

where θ is the Cs atom coverage expressed as a fraction of one monolayer, a monolayer being a layer one atom deep; σ is the number of atoms in a unit area of a monolayer; and S is the electrode surface area.

The flux of Cs atoms to the electrode surface is:

$$\Phi = \frac{v_A}{4} [N_0 + N_1 + N_2 + N_3 + N_4] . \quad (4.15)$$

All of the atoms that impinge on the surface adsorb there (Levine and Gyftopoulos 1964b). However, results of this model show that the ions that impinge on the surfaces do not adsorb, but recombine and return from the surface as ground state atoms. This can be understood as each ion arriving at the surface after being accelerated through the sheath sputtering off an adsorbed atom. The desorption rate expressed in an Arrhenius form (Levine and Gyftopoulos 1964b) is:

$$D_A = C\theta\sigma e^{-\frac{qH}{kT}} , \quad (4.16)$$

where H is the desorption energy in eV, T is the temperature of the surface, and C is a coefficient with units of time; D_A has units of flux ($\text{m}^{-2}\text{s}^{-1}$). The coefficient C has a theoretical value equal to the vibration frequency of the Cs atom on the surface (Fedorus et al. 1972), $C = \frac{kT}{h}$, where h is Planck's constant. The total flux of desorbed Cs atoms from the surface is D_A plus a term equal to the ion flux to the surface, representing the sputtered atoms.

In the transient diode model, equations (4.14) and (4.16) are written for both the emitter and collector surfaces, although the Cs coverage on the emitter is very small because of the high temperature required for electron emission. The reason for this is that even when θ is constant or zero, D_A is not zero.

Electron Emission

The thermal electron emission current density is given by the Richardson-Dushman equation (Herring and Nichols 1949):

$$J_{th} = AT_{EM}^2 e^{\frac{-q\phi_E}{kT_{EM}}}, \quad (4.17)$$

where T_{EM} is the emitter temperature, k is Boltzman's constant, and A is the Richardson constant ($A = 1.2 \times 10^6$ A/m²).

When there is an electric field present at the emitter, due to the emitter sheath or to an externally applied field, the emission current is greater than the thermal emission current given by equation (4.17). This is due to the Schottky effect, which is described in Appendix C. The Schottky emission equation is (Herring and Nichols 1949):

$$J_{SE} = J_{th} e^{\frac{\sqrt{\frac{q^3 E}{4\pi\epsilon_0}}}{kT_{EM}}}, \quad (4.18)$$

where E is the electric field at the emitter due to the emitter sheath and ϵ_0 is the permittivity of free space. In a plasma, the electric field near the emitter surface due to the emitter sheath is given by Baksht (1970) as:

$$E = \sqrt{\frac{M}{2q}} \sqrt{\frac{4\pi J_i}{\epsilon_0}} \sqrt[4]{q\Delta V_E}. \quad (4.19)$$

The emitter surface in the Cs-Ba diode at ISNPS is made of polycrystalline Mo. As explained in Appendix C, the emission current from a polycrystalline emitter is greater than that calculated by equation (4.18), due to the so-called anomalous Schottky effect (Herring and Nichols 1949, Baksht et al. 1978b). Because a theoretical treatment of the anomalous Schottky effect is beyond the scope of this work, the following semi-empirical equation is proposed in this work:

$$J_{ASE} = J_{SE} e^{\Lambda \sqrt{\Delta V_E}}, \quad (4.20)$$

where Λ is a parameter determined from the fit of the experimental data. In the transient discharge model, the emission current, J_{E0} , is set equal to J_{ASE} .

The governing equations of the plasma discharge model are equations (4.1), (4.2a), (4.2b), (4.7), (4.9), (4.12), (4.13) for $k = 1, 2, 3$, & 4, (4.14), (4.16), and (4.20). In these 13 equations there are 17 unknowns: T_e , n , N_0 , N_k for $k = 1, 2, 3$, & 4, ϕ_C , ϕ_E , Λ , ΔV_E , ΔV_C , θ , H , J_{E0} , V_{CE} , and I_C . Since there are more unknowns than there are equations, four variables must be eliminated by choosing values for them in order to solve for the rest. In the next section, the method of choosing these values and obtaining a time-dependent solution for the other variables is explained.

4.1.3 Voltage-Driven Transient Discharge Model Solution Method

In order to solve the system of 13 equations and 17 unknowns, the values of four variables are chosen; these are Λ , H , ϕ_C , and either I_C or V_{CE} . The parameter Λ and the value of H are chosen to fit the experimental data. Since the Mo collector is covered with adsorbed Ba, the collector work function ϕ_C is approximately constant at 2.2 eV (Magera and Davis 1994); one other value must be specified or another equation found to solve for the remaining 14 unknowns. The solution is done in one of three ways: (a) assume a constant value of V_{CE} , (b) assume a constant value of I_C , or (c) find another equation relating these two variables. Each of these three methods is described in this chapter. For comparison of the transient model with the steady-state model to verify the solution method, it is convenient to choose a constant value of V_{CE} , and allow the transient model to converge to the steady-state value. The calculated values of I_C , n , T_e , etc. should match those determined by the steady-state model of Murray et al. (1993) at

the chosen value of V_{CE} . If so, then the transient solution method is consistent with the steady-state solution method.

Voltage Driven Transient Discharge Model Solution Method

The 13 governing equations are closely coupled, each depending on several variables. For example, the electron temperature in equation (4.7) depends on n , ΔV_E , ΔV_C , and implicitly on T_e , through the rate coefficients in the R_{ex} term. The general approach is to estimate the values of quantities required to obtain a solution, solve all the equations for the unknowns, and then iterate using the new values as the estimates until the solution converges to within a specified tolerance.

Of the 13 governing equations for the plasma discharge in the Cs-Ba diode, eight involve time derivatives: equations (4.7), (4.9), (4.12), (4.13) for $k = 1, 2, 3$, & 4, and (4.14). These eight equations are the core of the transient model, and are integrated with respect to time using Euler's method. This method was chosen after a more sophisticated numerical integration algorithm, the Adams-Bashforth method, was found to yield only a small increase in accuracy, at the expense of increased computation time. The Euler method estimates the change in a variable after a small time interval Δt as shown in the following example using the plasma density n (equation 4.9). The new value of n is the sum of the value of n from the previous time step, n_o , plus the change in n during the time step, Δn : $n = n_o + \Delta n$. The value of Δn is obtained from equation (4.9) by approximating the time derivative $\frac{dn}{dt}$ as $\frac{\Delta n}{\Delta t}$, then $\Delta n = \Delta t \{RHS\}$, where RHS refers to the right-hand side of equation (4.9). All of the eight time-dependent equations are straight forward to integrate in this manner, except the electron energy balance equation, which requires some manipulation, as described in the next paragraph.

Equation (4.7), for the electron energy balance, includes two time-dependent quantities in the time derivative, T_e and n . An expression for the time rate of change of electron temperature can be obtained using the chain rule:

$$\frac{d}{dt}(nT_e) \frac{3}{2}kV = \text{RHS}$$

$$n \frac{dT_e}{dt} + T_e \frac{dn}{dt} = (\text{RHS}) \frac{2}{3kV} \quad (4.22)$$

$$\frac{dT_e}{dt} = \frac{1}{n} \left\{ (\text{RHS}) \frac{2}{3kV} - T_e \frac{dn}{dt} \right\},$$

where RHS represents the right-hand side of equation (4.7). The right side of equation (4.9) for $\frac{dn}{dt}$ is substituted into equation (4.22) to obtain an expression for T_e .

The first step in the solution of the 13 governing equations using a constant value of V_{CE} is to choose V_{CE} and estimate T_e , n , N_k , and J_{E0} . Equations (4.2a) and (4.2b) are set equal to each other, eliminating I_C . When the value of ϕ_E from equation (4.17) is substituted into equation (4.1), the result is two equations with two unknowns, ΔV_E and ΔV_C , which can be solved using the estimated values of n , J_{E0} , and T_e :

$$\Delta V_C = \frac{q}{kT_{EM}} \text{Ln} \left[\frac{J_{E0}}{AT_{EM}^2} \right] + \Delta V_E + \phi_C - V_{CE} \quad (4.23a)$$

and

$$e^{-\frac{q\Delta V_E}{kT_e}} + \frac{S_C}{S_E} e^{-\frac{q\Delta V_C}{kT_e}} = \frac{J_{E0}}{J_r} + \frac{J_i}{J_r} \left(1 + \frac{S_C}{S_E} \right). \quad (4.23b)$$

These two simultaneous equations must be solved numerically for ΔV_E and ΔV_C . After doing so, these values are used in equation (4.22) to find a new value of T_e . The new T_e is used to calculate the rate coefficients which are used in equations (4.12) and (4.13) to solve for n and N_k . Since the object of the voltage driven discharge model is to compare with the steady state model, equation (4.14) is not used, and D_A is set equal to Φ (equation (4.15)) in equation (4.13). After all unknowns are calculated, the new electron temperature is compared to the value computed in the previous time step. If the

difference is larger than a specified tolerance, all the quantities are re-calculated using the most recent calculation as the estimate. This iteration is repeated in each time step until the value of T_e converges, then I_C is calculated from equation (4.2b). The time is then incremented and the iteration begins again using the values from the last time step as the estimate. With V_{CE} as the input, the transient model converges to the same values calculated by a steady-state model, as shown in the next section.

4.1.4 Voltage-Driven Discharge Model Results

The results of the transient discharge model are compared to the calculations of the steady-state model of Murray et al. (1993) in Figure 4.2. In the figure, the steady-state model calculations are indicated by the solid lines, and the transient model results are represented by the symbols. The object of this comparison is to verify the transient solution procedure. To effect this comparison, the modified equations described earlier in this chapter were replaced with the equations of Murray et al. (1993) for this comparison only, and the steady-state model was adjusted for the planar geometry of the present experimental device. Figures 4.2a, 4.2b, and 4.2c show the calculated steady-state current, the calculated ion density and the densities of the ground state and the first excited state of cesium, and the calculated electron temperature, respectively. Figure 4.2d shows the calculated Cs coverage on the collector. As the results in Figure 4.2 show, the transient discharge model with V_{CE} as the input agrees very well with the steady-state model. This verifies that the transient discharge model solution procedure is consistent with the steady-state solution procedure.

The assumption of a constant V_{CE} in the transient model is not physically realistic, since in plasma discharges V_{CE} depends on the discharge current and not vice versa. For this reason, the transient model is solved by defining the discharge current as the input instead of the voltage, as shown in the next section.

Figure 4.2 Comparison of the Transient and the Steady-State Models.

4.1.5 Current-Driven Transient Discharge Model Solution Method

With I_C as the input instead of V_{CE} , the solution procedure is very similar to that of the voltage-driven discharge model shown above. The only difference is that the sheath potentials are obtained directly from equations (4.2a) and (4.2b) using the input value of I_C . After iterating to converge on T_e , the forward voltage drop, V_{CE} , is obtained from equation (4.1).

The calculated value of V_{CE} for a given value of I_C depends on the value of the parameter Λ . For comparison of the model calculations with steady state probe data, Λ is chosen to match the measured value of V_{CE} for each measured value of I_C . A comparison of the calculated electron temperature, plasma density, and plasma potential with measured values is presented in Chapter 5.

The voltage driven and current driven discharge models described above are transient models designed to converge to a steady state. The result of such a calculation is a point on a steady state I-V curve. However, experimental I-V curves for the Cs-Ba diode are not measured in a steady state condition. In the I-V mode, the source current is increased linearly for one ms, then decreased linearly for one ms. The time for the discharge to reach equilibrium is 2-3 ms (Murray et al. 1992), suggesting that no point on the I-V curve represents a steady state. Therefore, steady-state model calculations are not compatible with measured I-V curves. For comparison of the transient model with I-V data, the need to choose values of either I_C or V_{CE} as an input is eliminated by adding another equation to the system. The other equation is obtained by analysis of the external circuit, as described in the next section.

4.2 Current Source Circuit

To compare the transient model with experimental I-V curves, the effect of the external circuit on the discharge is determined and incorporated into the transient discharge model. Figure 4.3 shows a schematic of the tacitron control circuit. The Cs-Ba diode (labeled "D" in the figure) is connected in series with the load resistance ($R_L \approx 1\Omega$). The current source consists of a capacitor, C, that provides the source current to the diode during a test pulse; a transistor, T, which controls the current wave form during the test pulse; and a shunt resistor, R_S .

4.2.1 Circuit Analysis

During a test pulse in the I-V mode, the base current to the transistor, I_b , increases linearly for 1 ms, remains constant for 5 ms, then decreases linearly for 1 ms. The source current, I_{source} , follows approximately the base current I_b ; in the model I_{source} is assumed to increase linearly to 50 A in 1 ms, remain constant for 5 ms, and then decrease linearly to zero in 1 ms. The source current as modeled is shown in Figure 4.4. The voltage that appears at the terminals of the current source, V_{source} , is equal to the sum of the voltage drop across the load resistor and the voltage drop across the diode, V_{CE} :

$$V_{source} = V_{CE} + I_C R_L . \quad (4.24)$$

The source voltage, V_{source} , can be expressed in terms of the known source current, which is the sum of the currents through both the shunt resistor and the Cs-Ba diode:

$$I_{source} = I_S + I_C = \frac{V_{source}}{R_S} + I_C , \quad (4.25)$$

where I_S is the current through the shunt resistor R_S . Rearranging equation (4.25), an expression for V_{source} is obtained:

$$V_{source} = (I_{source} - I_C)R_S . \quad (4.26)$$

Equations (4.24) and (4.26) are solved for the values of V_{CE} and I_C , allowing a solution for all of the 14 unknowns in the governing equations.

Capacitor Voltage Limit

The assumed wave form for I_{source} shown in Figure 4.4 does not always occur. As I_{source} increases, the value of V_{source} increases also, but V_{source} cannot ever be greater than the voltage across the capacitor, V_C , minus the voltage drop across the transistor, V_T . The voltage drop across the transistor is approximately constant throughout the operating current range (Sedra and Smith 1987). In the present transient model, V_{source} is allowed to increase until $V_{source} \geq V_C - V_T$, after which equation (4.25) is used to calculate I_{source} with $V_{source} = V_C - V_T$. During the time the current is limited by the capacitor, V_{source} is approximately constant. Equation (4.24) can be rearranged to give:

$$I_C = -\frac{V_{CE}}{R_L} + \frac{V_{source}}{R_L} . \quad (4.27)$$

As this equation shows, if V_{source} is constant, then I_C is a linear function of V_{CE} with a negative slope of $\frac{1}{R_L}$, or in other words, the I-V characteristic of the diode is linear and follows the load line. The voltage across the capacitor decreases by 1 to 2 V as it discharges during the 7 ms current pulse, and V_{source} also decreases slightly, causing the I-V characteristic to deviate from the load line.

Figure 4.3 A Schematic of the Cs-Ba Tacitron Control Circuit.

Figure 4.4 Assumed Source Current in the Model.

The voltage across a discharging capacitor decays exponentially as:

$$V_C = V_0 e^{-\frac{t}{\tau}} . \quad (4.28)$$

The capacitor time constant, $\tau = RC$, is calculated in each time step from the known source current and the calculated source voltage using $R = R_{eq}$, the equivalent resistance of the whole circuit:

$$R = R_{eq} = \frac{V_{source}}{I_{source}} , \quad (4.29)$$

and the measured capacitance, $C \approx 100$ mF. The capacitor voltage is calculated in each time step using equation (4.28), with $V_0 = V_C$ from the last time step and $t = dt$ (see Appendix F).

The source current as a function of time is determined from Figure 4.4 and equations (4.25) and (4.28). Equations (4.24) and (4.26) add another unknown, V_{source} , but two equations, leaving 15 equations and 15 unknowns. A solution method depending only on I_{source} is described in the next section.

4.2.2 Circuit-Driven Transient Model Solution Method

Instead of choosing a constant value for I_C as was done in the current-driven solution of the discharge model, the circuit equations described earlier are used to solve for this quantity. The behavior of the calculated I-V curve is determined by I_{source} . In each time step, I_{source} is determined from Figure 4.4 and equations (4.25) and (4.28). The general method of solution is to estimate values of V_{source} , I_C , n , N_k for $k = 0, 1, 2, 3$, & 4, T_e , and J_{E0} , re-calculate these quantities based on the estimates, and then iterate until the solution converges to a specified tolerance in each time step. For

the solution to converge, the time step must be small. Details of this solution procedure follow, and are summarized in a flow chart shown in Figure 4.5.

Since the numerical solution will not allow initial values of T_e and n to be zero, non-zero initial values are chosen arbitrarily. A start-up procedure is used to make the calculated I-V curve independent of the chosen initial values. The source current is held constant for 300 μ s at a small non-zero value (~ 5 A) while allowing the solution to converge, as was done in the current-driven discharge model. Then I_{source} is allowed to increase as shown in Figure 4.4. At the end of the I-V pulse, I_{source} is not allowed to decrease to zero, but is held constant at a small non-zero value, again to avoid the problem of n and T_e going to zero.

The core of the circuit-driven transient model is the same as the current-driven discharge model except that I_C is calculated as follows. Expressions for ΔV_E and ΔV_C are found by solving equations (4.2a) and (4.2b) respectively. These expressions for the sheath potentials are substituted into equation (4.1), repeated here for convenience:

$$0 = -V_{CE} + \phi_C - \phi_E + \Delta V_E - \Delta V_C, \quad (4.1)$$

The emitter work function ϕ_E is obtained from equation (4.17) with $J_{th} = J_{E0}$, while V_{CE} is substituted from equation (4.24). The result is a highly non-linear function in I_C :

$$f(I_C) = I_C R_L - V_{\text{source}} + \phi_C + \frac{kT_{EM}}{q} \text{Ln} \left(\frac{J_{E0}}{120T_{EM}^2} \right) + \frac{kT_e}{q} \text{Ln} \left[\left(\frac{S_E}{S_C} \right) \frac{I_C + J_i S_C}{S_E(J_{E0} + J_i) - I_C} \right]. \quad (4.30)$$

Equation (4.30) is solved for I_C such that $f(I_C) = 0$. This equation has a vertical asymptote very near the root, with the last term on the right going to ∞ as $I_C \rightarrow S_E(J_{E0} + J_i)$. Although it would be simple to approximate I_C as the asymptotic value, the difference between I_C and the asymptotic value is $S_E J_i e^{-\frac{q\Delta V_E}{kT_e}}$, from which

Figure 4.5 Flow Chart of the Circuit-Driven Transient Model.

ΔV_E is calculated (see equation (4.2a)). Clearly, the difference between I_C and the asymptotic value cannot be neglected, particularly at low forward voltage drops when ΔV_E is small. Equation (4.30) is solved for I_C using the secant method root finder with careful choice of initial guesses. This method is relatively fast and robust if the initial guesses are chosen properly (Plybon 1992).

When the discharge current is below the maximum thermal emission current, or knee current, recent results presented in Chapter 5 indicate that the discharge contracts to a filament. The transient model approximates this effect by letting the emission current equal the random electron current below the knee.

Using the above method, the I-V curves calculated by the circuit-driven transient model compare very well with the experiment, which verifies the circuit analysis and the solution procedure. These results are presented in the next section.

4.2.3 Circuit-Driven Transient Model Results

During the transient I-V test pulse, the source current is increased linearly, held constant, then decreased linearly to zero, as explained in section 4.2.1. Figure 4.6a shows typical voltage and current signals measured in the Cs-Ba diode in I-V mode. Note that the current I_C increases almost linearly at the beginning of the pulse, in the region labeled "1" in the figure. This is the period when I_{source} is increasing linearly with time, and V_{source} is increasing also. Note that V_{CE} remains approximately constant at 2 V for a while, then increases. It is theorized that the discharge forms as a filament, and as more current is demanded by the circuit, the filament expands radially across the electrode surfaces. The voltage drop remains fairly constant until the filament expands to the full area of the electrode and cannot expand further. In chapter 5, experimental data is shown to confirm the presence of a discharge filament.

(a) Measured Discharge Current and Forward Voltage Drop

(b) Calculated Discharge Current and Forward Voltage Drop

Figure 4.6 Comparison of Measured and Calculated Voltage and Current in I-V Mode.

Further increase in discharge current occurs at the expense of increased voltage drop. The point where the voltage drop begins to increase is called the knee of the curve, and it corresponds to the maximum thermal emission current. When the sum of the voltage drop across the diode plus the voltage across the load resistance equals the capacitor voltage, it is limited by the capacitor voltage and not by the transistor.

After the discharge current peaks at 25 A, it decreases rapidly, then more slowly (region 2 in Figure 4.6a), while the forward voltage drop increases to a maximum. This is the period during which the discharge is approaching equilibrium. During the discharge, Cs ions are created, and some leak out of the discharge volume, causing the Cs pressure in the inter-electrode gap to decrease and Cs atoms to desorb from the collector surface. After the supply of Cs from the surface is exhausted, the ion leakage out of the volume reaches an equilibrium with the flux of Cs atoms from the reservoir. This leakage and Cs pressure drop is calculated in the model and observed in the experiment, as shown in the next chapter.

In regions 2 and 3 of Figure 4.6a, the voltage V_{source} is limited by the capacitor in the circuit of the current source. During this time V_{source} is approximately constant, so the I-V characteristic approximately follows the load line, but deviates from it as the capacitor discharges. In region 3, both the discharge current and the terminal voltage decrease slowly along with the capacitor voltage. In region 4, V_{source} is again limited by the transistor instead of the capacitor, and I_{source} decreases linearly to zero. Both I_C and V_{CE} also decrease to zero.

Figure 4.6b shows the calculated discharge current and forward voltage drop at the same conditions as in Figure 4.6a. The shape of the current and voltage pulses calculated by the model is very similar to the experiment. On the left side of Figure 4.6b is a region (0 to 0.3 ms) in which the calculated I_C and V_{CE} are constant. This is the result of the start-up procedure described earlier, in which I_{source} is held constant at a small non-zero value to prevent n and T_e from going to zero.

Figure 4.7 shows the voltage and current pulses from Figures 4.6a and 4.6b, plotted with the voltage on the abscissa and current on the ordinate. The solid line is experimental data, and the dashed line is the model calculation. The cross marks on the model calculation are 50 μ s intervals, and the four regions from Figures 4.6a and 4.6b are indicated by the numbers. The experimental I-V curve shows that the voltage drop across the diode remains approximately constant at about 2.3 V as the current rises, reaching the knee at 22 A. Beyond this current both the voltage and the current increase. In region 2 the current stops rising as the capacitor voltage limits V_{source} , and the I-V curve follows the load line, with a negative linear slope. The voltage and current both decrease as the capacitor discharges in region 3. In region 4, the source current drops below the capacitor limit, and the voltage drops quickly as less current is drawn by the circuit. The current drops to zero as the voltage remains nearly constant at 2.7 - 3 V. At any value of current below the knee, the voltage drop is ~ 1 V higher at the end of the test pulse than at the beginning. The reason for this hysteresis is explained in Chapter 5. The model calculations show the same behavior as and are in good agreement with the experimental data. It is worth noting that the experimental uncertainty in the measured voltage is ± 0.5 V, as explained in Appendix D.

In some cases, the experimental I-V curves indicate the presence of anomalous Schottky current. Anomalous Schottky current is any current above the normal Schottky current given by equation (4.18), which increases exponentially with the eighth root of emitter sheath potential (equation (4.19)). A plot of the normal Schottky current as a function of voltage is shown in Figure 4.8. If the measured current is above this current, then the anomalous Schottky current is predominant (Murray et al. 1993). A physical description of the anomalous Schottky effect is given in Appendix C.

Figure 4.9 shows experimental I-V curves at different Cs reservoir temperatures. Results in Figure 4.9 show that as the cesium reservoir temperature, T_{Cs} , is increased from 125°C to 155°C (2.3 mTorr to 10.8 mTorr) in 15°C increments, the minimum

Figure 4.7 Comparison of Measured and Calculated I-V Characteristics.

Figure 4.8 Normal Schottky Current as a Function of Voltage.

Figure 4.9 Experimental I-V Curves at Different Cesium Pressures.

voltage drop across the diode decreases from ~ 3.4 V to ~ 1.5 V. These results demonstrate that the minimum voltage drop during discharge depends strongly on Cs pressure. Note also that the current above the knee increases significantly as the Cs pressure is increased. This is due to the anomalous Schottky current, which increases with increasing Cs pressure in these curves (Murray et al. 1993). The I-V curve for $T_{Cs} = 125^{\circ}\text{C}$ (2.3 mTorr) shows normal Schottky current above the knee, while the curves for $T_{Cs} = 140^{\circ}\text{C}$ (5.1 mTorr) and 155°C (10.8 mTorr) show increasing contributions of anomalous Schottky current. Although the voltage drop decreases and the current increases as the Cs pressure increases, the maximum thermal emission current at the knee of the curves is almost constant and equal to 8 A.

Chapter Summary

In this chapter the transient model system of equations is developed. Three different solution procedures are presented. Using the constant voltage solution the transient discharge model is shown to be consistent with a steady-state model. The external circuit is analyzed and incorporated into the circuit-driven solution. The results of the circuit-driven transient model show that the model predictions of the I-V curves agree quite well with experimental data. This verifies that the external circuit is accurately modeled and properly coupled to the plasma discharge model of the Cs-Ba diode. The constant current solution is used in the next chapter for comparison of transient model calculations to probe data.

5. Model Calculations Compared to Probe Measurements

In this chapter the calculations of the diode transient model are verified by comparison with experimental measurements made in a Cs-Ba diode equipped with Langmuir probes. The probe data are used to investigate some of the assumptions in the model, namely (a) the electron energy distribution function, (b) homogeneity of plasma parameters across the gap, and (c) the contraction of the discharge to a filament below the knee of the I-V characteristic. Transient model results are presented to show the change of plasma parameters with time during the discharge, supported by time-dependent probe measurements. The model results are also used to explain the hysteresis in the I-V curves.

The experimental parameters (T_{EM} , T_C , R_L , etc.) are chosen based on the probe data. It was found that at high emitter temperatures ($> 1100^\circ\text{C}$), the probes become hot enough to emit electrons, which changes the probe characteristics. For this reason, all probe measurements are taken with an emitter temperature of 1100°C .

The experimental I-V curves in Chapter 4 are obtained by configuring the Cs-Ba tacitron as a diode. This is done by connecting the grid to the collector, thus making the grid act as a hollow collector (Chapter 3). However, in this chapter, the experimental data are obtained using a solid collector diode with the grid removed. A comparison of experimental I-V curves for the two types of diodes is made in the following section.

5.1 Comparison of Hollow Collector and Solid Collector Diodes

A comparison of the I-V characteristics of the two types of diodes is shown in Figure 5.1, where the dashed line is for the hollow collector diode (diode between emitter and grid) and the solid line represents the solid collector diode (grid removed). As shown in the figure, at the same conditions (diode gap = 1.0 mm, $T_{EM} = 1100^\circ\text{C}$,

(a) $T_{Cs} = 165^\circ\text{C}$ (17 mTorr)

(b) $T_{Cs} = 175^\circ\text{C}$ (27.7 mTorr)

Figure 5.1 Comparison of Solid and Hollow Collector Diodes.

$T_C = 700^\circ\text{C}$, $T_{Ba} = 550^\circ\text{C}$, and $T_{Cs} = 165^\circ\text{C}$ (Figure 5.1a) and $T_{Cs} = 175^\circ\text{C}$ (Figure 5.1b)), the I-V characteristics in the solid collector and hollow collector diodes have different shapes and different voltage drops. The solid collector diode is more likely to oscillate than the hollow collector diode. Oscillations are observed in Figure 5.1a during the portion of the I-V curve where it follows the load line, from 18 - 15 A and 3 - 4 V. An explanation of the cause of such oscillations will be offered later in this chapter.

Figure 5.1 shows that all of the curves have a thermal emission current knee at ~ 15 A. Above this current the solid collector diode shows evidence of anomalous Schottky current, while the hollow collector diode does not. The I-V curves from the hollow collector diode show less hysteresis, meaning that the left and right sides of the I-V characteristic are closer together. In Figure 5.1a, the difference between the left and right sides at 12 A is ~ 0.3 V in the hollow collector diode, while in the solid collector diode the difference is ~ 1 V. In Figure 5.1b, the voltage difference is ~ 0.4 V in the hollow collector and ~ 1 V in the solid collector diode. The reason for this difference in hysteresis could be due to the larger area for Cs adsorption in the holes of the hollow collector (grid), which provides more Cs to maintain the pressure in the gap during the discharge. The change in Cs pressure during the discharge, and the role of Cs adsorption and desorption in the discharge, are discussed later in this chapter. In the next section, probe measurements taken in the solid collector diode are used to investigate three of the transient model assumptions.

5.2 Investigation of Model Assumptions

Using Langmuir probes for plasma diagnostics, it is possible not only to measure the plasma parameters, but also to investigate some of the assumptions in the diode transient model. By inspection of the probe characteristics it is possible to observe whether the discharge contracts to a filament below the knee, and investigate the electron

energy distribution. Investigation of the assumption of homogeneity of plasma conditions across the diode gap width is made possible by varying the placement of the probes relative to the two electrodes, as explained in section 3.3.

5.2.1 Contraction of the Discharge

Experimental results in a Cs diode showed that, at discharge currents below the thermal emission current, the discharge contracts to a filament under certain conditions (Baksht et al. 1970 and 1977). The knee of the I-V characteristic corresponds to the thermal emission current, given by equation (4.17). Below this current, the discharge contracts to a smaller area with the same current density. With Langmuir probes placed in the diode, it is possible to verify the contraction of the discharge in the Cs-Ba diode. Figures 5.2a and 5.2b show the measured current and voltage at the collector and the probe, respectively. The thermal emission current for the experimental condition in Figure 5.2 is ~ 5 A, and the discharge current is held constant below the knee at ~ 2.6 A (Figure 5.2a). As the probe voltage is increased (dashed line in Figure 5.2b), the probe current (solid line) begins to oscillate widely, from near zero to 0.5 A at the peak. The probe voltage changes by more than 3 V during the oscillation. If the observed oscillation of probe current and voltage were caused by some change in the plasma conditions instead of a moving filament with constant current density, a change of that magnitude would be seen easily in the collector current and voltage. This is not the case in Figure 5.2a however, suggesting the formation of a discharge filament that moves on the electrode surface.

Oscillations in the probe voltage and current, indicating the presence of a moving filament, appear in the transient data as well. The transient probe measurements presented in this chapter are taken with a slightly different type of I-V pulse than was described in Chapter 4 and shown in Figure 4.4, because the probe measurement software

(a) Collector Voltage and Current

(b) Probe Voltage and Current

Figure 5.2 Oscillation of Probe Characteristic Below the Knee.

required the use of a different current source driver. Only the second half of the current pulse is used. Figure 5.3 shows the shape of the current source used in these measurements. The source current is initially constant at 30 A for 1 ms, then decreases linearly to zero in 3 ms. A probe measurement taken with this current source is shown in Figure 5.4. The discharge current (solid line in Figure 5.4a) decreases linearly as the source current decreases. When the discharge current decreases below the thermal emission current (~ 4 A), the probe voltage and current begin to oscillate while the collector current continues to decrease smoothly (Figure 5.4b). This confirms that the discharge filament is moving on the surface of the electrodes. The filament doesn't always move; a measurement taken a few minutes after the one shown in Figure 5.4 showed no oscillations, although it is believed that the discharge still contracted.

It is shown in this section that when operating below the thermal emission current, the discharge in the Cs-Ba diode contracts to a filament. The next assumption investigated is the homogeneity of the plasma across the 1 mm diode gap.

5.2.2 Homogeneity of the plasma

As explained in section 3.3, the probes in the experimental diode are not in the center of the 1.0 mm diode gap, but rather placed 0.25 mm from the top electrode. By switching the emitter from the top to the bottom, it is possible to take probe measurements near the emitter (0.25 mm) and near the collector (0.75 mm from the emitter), respectively.

Figure 5.5 shows the measured plasma parameters with the probe near the emitter and near the collector as a function of time during discharge. Figure 5.5a shows the plasma density, and Figure 5.5b shows the electron temperature, measured using the method explained in section 3.4. Results in Figure 5.5a show that although the plasma densities near the collector and near the emitter are initially equal, the density drops

Figure 5.3 Source Current Used in Time-dependent Probe Measurements.

(a) Collector Voltage and Current

(b) Probe Voltage and Current

Figure 5.4 Oscillation of Probe Characteristic Below the Knee in I-V Mode.

(a) Plasma Density

(b) Electron Temperature

Figure 5.5 Comparison of Plasma Parameters Near the Emitter and Collector.

faster near the emitter. At ~ 2.4 ms, the plasma density near the collector is about three times higher than near the emitter. As shown in Figure 5.5b, the electron temperature near the emitter is higher by as much as 1000 -- 1500 K. Although one of the probes was closer to the boundary of the discharge volume than the other (Figure 3.4), no significant differences in n , T_e , or V_p are found between the two probes.

Results presented in this section clearly show that the plasma is not homogeneous across the diode gap, and that the plasma density could vary by at least a factor of three, and the electron temperature by 10% or more across the gap. The next section addresses the assumption that the electrons are in thermal equilibrium with each other, or in other words the electron energy distribution is described by a Maxwell-Boltzman distribution.

5.2.3 Electron Energy Distribution

The easiest model assumption to test is the Maxwell-Boltzman electron energy distribution, because the probe theory, as explained in Appendix B, is derived based on this energy distribution. If the electrons follow a Maxwell-Boltzman energy distribution, the electron current drawn by the probe increases exponentially with decreasing negative probe voltage relative to the plasma potential. Thus, when plotted on a semi-log scale, the probe I-V characteristic should be a straight line with positive slope, from which T_e is found. If the characteristic is non-linear, then the actual energy distribution can be inferred from the nature of the deviations from linearity, as explained in Appendix B. It is found in this work that the energy distribution is close to Maxwellian at higher discharge current, but at low current the energy distribution function deviates from Maxwellian at high electron energies. The same tendencies were observed by Baksht et al. (1970) in a Cs diode.

Two typical probe characteristics taken at low discharge current are shown in Figure 5.6, with the probe closer to the emitter (5.6a) and closer to the collector (5.6b).

(a) Probe Near Emitter

(b) Probe Near Collector

Figure 5.6 Probe Characteristics Near the Emitter and Near the Collector.

The results in Figure 5.6 show that the low energy electrons (probe voltage close to zero with respect to V_p) follow the straight line indicating a Maxwell distribution, but as the probe voltage becomes more negative and the low energy electrons are repelled, the high energy electrons deviate from a Maxwell distribution. Figure 5.6a shows more electron current than expected at high electron energies (3.5 -- 5.5 eV), indicating the presence of an electron beam, or a high energy tail on the distribution. The electron beam near the emitter indicates that the electrons accelerated through the emitter sheath are not thermalized immediately.

Figure 5.6b shows fewer high energy electrons near the collector than expected based on a Maxwell-Boltzman distribution from ~ 3.2 -- 4.2 eV, and evidence of an electron beam from ~ 2.4 -- 3.0 eV. The depletion of high energy electrons near the collector may be due to inelastic collisions between electrons and Cs atoms (Gündel et al. 1991). The depletion of electrons occurs at approximately the ionization energy of Cs (3.89 eV), suggesting that direct ionization of Cs takes place near the collector. Another possible explanation for the depletion is diffusion cooling, since the collector sheath potential is ~ 3.4 eV. The actual cause may be either of these processes, or a combination of the two.

Figures 5.5 and 5.6 show that the discharge is not homogeneous across the 1 mm diode gap, and Figure 5.6 shows evidence of an electron beam. Baksht et al. (1977) showed that the beam electrons do not contribute significantly to the ionization rate, and found that in a Cs diode at low current density ($J \leq 1$ A/cm²) the beam does not add measurably to the total collector current. However, in this work it is found that the beam does contribute to the collector current. Evidence for this conclusion and the method of incorporating it into the model are presented in the next section.

5.3 Thermalization of the Emitter Beam Electrons

The Cs-Ba diode transient model described in Chapter 4 calculates voltages and currents which compare well with experimental I-V curves. However, for a given terminal voltage and current, the model calculated the electron temperature higher than and the plasma density and plasma potential lower than the measured values. To address this problem, one of the basic assumptions in the model is reconsidered as follows.

It was assumed in section 4.1 that the electron beam emerging from the emitter sheath is thermalized immediately, so that a Maxwell-Boltzman distribution of electron energies prevails throughout the gap. However, the probe data shows that this is not the case; a part of the emitter beam travels through the gap and arrives at the collector, adding to the random collector current. This is demonstrated by a simple calculation using the collector current balance, equation (4.2b), which is repeated here for convenience:

$$I_C = S_C \left(J_r e^{-\frac{q\Delta V_C}{kT_e}} - J_i \right). \quad (4.2b)$$

The quantities J_i , J_r , ΔV_C , and T_e in equation (4.2b) are obtained from the probe measurements. If equation (4.2b) is true, then the calculated value of I_C should equal the measured collector current. Measured and calculated quantities taken from the Cs-Ba diode at $T_{EM} = 1100^\circ\text{C}$, $T_C = 700^\circ\text{C}$, and $T_{Cs} = 155^\circ\text{C}$ (10.77 mTorr) are summarized in Table 5.1. As Table 5.1 shows, the calculated collector current of 3.2 A is less than one-fourth the measured current of 14.4 A. This discrepancy can be accounted for in the model by assuming that a part of the emitter electron beam traverses the gap and adds to the random electron current at the collector. A theory that leads to such a revision is described in the following sub-section.

Table 5.1 Comparison of Measured and Calculated Collector Current from Probe Data.

Measured Parameters	
I_C	14.4 A
V_{CE}	4.5 V
T_e	18000 K
n	$2.4 \times 10^{19}/m^3$
ΔV_E	10.3 V
ΔV_C	5.9 V
Calculated Parameters	
J_i equation (4.3)	$0.25 A/cm^2$
J_r equation (4.4)	$79.2 A/cm^2$
J_{E0} equation (4.2a)	$7.0 A/cm^2$
I_C equation (4.2b)	3.2 A

5.3.1 Langmuir Wave Interactions

According to the theory of Baksht et al. (1990), the mechanism by which a beam of electrons from the emitter adds energy to the bulk plasma electrons is through a wave interaction with the plasma (Wernsman 1994). The beam electrons excite a standing Langmuir wave in the diode gap at the electron plasma frequency, which is then damped out by interactions with the bulk plasma electrons. According to experimental measurements (Baksht et al. 1990), one half of the energy in the beam can be transferred to the standing plasma wave. The electron beam arrives at the collector with 1/2 of its initial energy and adds to the random electron current at the collector. Therefore, the

electron energy and current balance equations should be revised as explained in the following subsections.

5.3.2 Electron Temperature

With only half of the emitter beam energy transferred to the bulk plasma electrons, the electron energy equation must be modified. The amplitude of the standing plasma wave grows and decays exponentially with distance from the emitter. The plasma wave is excited with a characteristic length λ , and after a distance 5λ , the wave is considered fully excited. After the wave is excited, it begins to lose energy to the plasma. The wave amplitude decreases exponentially with a characteristic length 5λ , with λ given by:

$$\lambda = \frac{24 kT_e}{\pi^2 J_{E0}} \sqrt{\frac{\epsilon_0 n}{m}}, \quad (5.1)$$

where ϵ_0 is the permittivity of free space. The energy of the wave as a fraction of the beam energy, and the energy deposited in the plasma as the wave is damped out, are shown in Figure 5.7. The maximum wave energy is 1/2 the emitter beam energy. As shown in the figure, after a distance 5λ into the plasma, the wave is fully excited and begins to deposit energy to the plasma electrons. After a distance 30λ , the wave is fully damped out and has transferred all of its energy to the bulk plasma electrons. If the gap width is smaller than 30λ , only a fraction of the energy of the wave is transferred to the plasma. For the conditions in Table 5.1, Figure 5.7 shows that in the 1 mm diode gap approximately 43 % of the beam energy is transferred to the plasma electrons.

The electron energy equation as given in section 4.1 above, equation (4.7), is written with the assumption that 100% of the emitter beam energy is transferred to the bulk plasma electrons. If only a fraction of the beam energy is transferred, then the first term in equation (4.7), the source term of energy from the emitter, should be multiplied

Figure 5.7 Energy of the Wave and Energy Deposited in the Plasma.

by that fraction. The fraction has a maximum value of 1/2, and depends on the relative lengths of λ and the gap width, as depicted in Figure 5.7. The fraction, f , is given by:

$$f = \frac{1}{2} \left(1 - e^{-\frac{x}{5\lambda}} \right), \quad (5.2)$$

where $x = (d - 5\lambda)$ and d is the diode gap width. A portion of the emitter beam traverses the diode gap, adding to the electron current at the collector, requiring the following modification to the current balance equation.

5.3.3 Collector Current

Since half of the beam energy is lost to the plasma wave, the speed of the beam electrons is reduced by the square root of two. Recalling that J_{E0} is the emission current, the modified current balance equation at the collector is:

$$I_C = S_C \left(J_r e^{-\frac{q\Delta V_C}{kT_e}} - J_i + \frac{J_{E0}}{\sqrt{2}} \right). \quad (5.3)$$

Substituting the values of T_e , ΔV_C , J_r , and J_i from Table 5.1, and J_{E0} from equation (4.2a), into equation (5.3), the collector current I_C is 13.1 A, which is within the experimental uncertainty of the measured value in Table 5.1. Although the Langmuir probe data showed evidence of a depletion of high energy electrons in most cases, the data also indicates the presence of a beam near the collector. Figure 5.6b showed evidence of an electron beam near the collector, with electron energies in the range 2.4 -- 3.0 eV. The emitter sheath potential in that figure is 5.24 eV. Near the collector, the beam should have half of its original energy, or 2.6 eV, which fits within the range of the observed beam energies. When the corrections to the current balance and the electron

energy equations are incorporated into the transient discharge model, the calculated plasma density, electron temperature, and plasma potential are much closer to measured values. The results of these calculations are presented in the next section.

5.4 Steady-State Probe Data and Calculations

In this section the current-driven transient discharge model calculations are presented and compared to probe measurements of electron temperature, plasma density, and plasma potential. The probe measurements presented in this section are made with the diode running in a steady-state mode. In this mode, the source current is maintained constant for 15 ms after discharge ignition. Beginning at 5 ms after ignition, the probe voltage is swept through a 60 Hz half-sinusoid with peak of 8 V, as explained in Chapter 3. The measured probe I-V characteristics are used to determine the plasma parameters. Most of the probe measurements presented in this chapter, and throughout this section, are made with the probe closer to the collector (0.75 mm from the emitter and 0.25 mm from the collector, see Chapter 3).

Measurements of T_e , n , and V_p are made at 5°C increments in cesium reservoir temperature, T_{Cs} , from 150°C (8.5 mTorr) to 200°C (74.3 mTorr), using a constant load resistance ($R_L \sim 1\Omega$). Since only the load resistance is fixed, as T_{Cs} increases, V_{CE} decreases and the discharge current increases along the load line. To avoid the oscillation of the probe characteristics due to the discharge filament (section 5.2.1), the measurements in this section are made above the thermal emission current knee. The measured voltage and current at each T_{Cs} are shown in Figure 5.8. Results in this figure show that the discharge current and voltage are strong functions of the Cs pressure in the gap. As T_{Cs} is increased from 150°C to 200°C, the forward voltage drop decreases from 6.3 V to 1.1 V, while the discharge current increases from 14.4 A to 23 A. The experimental voltage and current values in Figure 5.8 are used as inputs to the diode

(a) Collector Voltage

(b) Collector Current

Figure 5.8 Voltage and Current Measurements with T_{Cs} for Fixed Load Resistance.

discharge model to calculate the steady-state plasma parameters, which are presented in the next sub-section.

5.4.1 Current Driven Discharge Model Results

The model predictions of the plasma parameters, using voltage and current from Figure 5.8 as inputs, are compared in Figure 5.9 with probe measurements at the same conditions. The calculations in Figure 5.9 follow the same trends as the experimental values, with T_e and V_p decreasing and n increasing as T_{Cs} increases. As shown in Figure 5.9a, the calculated electron temperature is within 10% of the measured values. The calculated plasma density in Figure 5.9b is in good agreement with the measurements at higher T_{Cs} , but is low by about a factor of two at low T_{Cs} . This is due in part to the variation in the plasma density across the diode gap and the fact that the diode model equations do not include any spatial dependence. The measurements in Figure 5.9 were made with the probe near the collector, and as shown in Figure 5.5 the plasma density near the collector can be as much as three times higher than near the emitter at low T_{Cs} . Therefore, the average plasma density is expected to be 1.5 times lower than the density measured near the collector. Reducing the measured plasma density by a factor of 1.5 at low T_{Cs} puts the calculation within the experimental uncertainty of the measured value.

The calculated plasma potentials in Figure 5.9c are generally lower than the measured values. This is due in part to a systematic error in the determination of the experimental value which overestimates V_p by about 0.5 V, as explained in Appendix D. As with the plasma density and electron temperature, the plasma potential also varies across the gap. At low T_{Cs} the plasma potential is higher near the emitter by about one volt, and the present model is expected to calculate V_p approximately 0.5 V higher than the measurement near the collector.

Figure 5.9 Comparison of Model Calculations with Steady-State Probe Measurements.

In addition to the spatial variations of the plasma parameters, the discrepancies between calculations and measurements in Figure 5.9 could be due to experimental uncertainties not included in the estimation of the error bars shown in the figure. One such uncertainty is discussed in the next sub-section.

5.4.2 Variation of the Plasma Parameters During Measurement

The experimental error bars shown in Figure 5.9 are estimated based on quantifiable uncertainties in the data, which arise through the lack of absolute precision in the measurements, such as the surface area of the probe, the value of the voltage drop and discharge current, etc. More details on the causes and the calculations of experimental uncertainty are given in Appendix D. The error bars in Figure 5.9 do not include uncertainties in the data or the probe technique that are difficult to quantify, such as the non-Maxwellian energy distribution, the effect of having different potentials along the length of the probe due to the current flowing through it, or changing discharge conditions during the measurement. A non-Maxwellian distribution would distort the probe characteristics as shown in section 5.2.3, possibly making determination of T_e difficult. If the potential varies along the length of the probe, the true probe potential would differ from the measured potential at either end. The potential would vary along the length of the probe depending on the current flowing at each point, and the characteristics would again be distorted since the electron current gathered by the probe changes exponentially with the probe potential. The change in the plasma conditions during measurement is discussed below.

The steady-state probe measurements are made by holding V_{source} constant for 15 ms while applying a 60 Hz half-sinusoid voltage pulse to the probe (Chapter 3). However, as discussed in section 4.2, V_{source} is determined by V_C , the voltage stored on the capacitor (Figure 4.3), which is discharging during the 15 ms time period. The rate

of discharge increases with I_C (equations (4.27) and (4.28)) and therefore with T_{Cs} (Figure 5.8). As the capacitor voltage decreases, both I_C and V_{CE} tend to decrease. However, at lower T_{Cs} , the capacitor voltage decreases more slowly, and V_{CE} tends to increase as ions are lost from the plasma (see the next section). Therefore, during the probe measurement, the discharge is not at a true steady state. The discharge current decreases during the measurement, while V_{CE} either increases or decreases, depending on T_{Cs} . The first 10 ms of a typical probe measurement is shown in Figure 5.10. Figure 5.10a shows the collector current and voltage, while Figure 5.10b shows the half-sinusoid voltage sweep applied to the probe starting at ~ 5 ms, and the current drawn by the probe. Observe from Figure 5.10 that while the probe voltage is increasing between 5 and 9 ms, the collector current decreases from ~ 22.7 A to ~ 21.3 A, a difference of 1.4 A. During the same time, the forward voltage drop changes from 3.48 to 3.18 V, a difference of 0.3 V. The plasma parameters are strongly dependent on I_C , and since the discharge current and plasma parameters change during the measurement, the measurement will be distorted, as explained in the following paragraph.

The probe characteristic from which T_e , n , and V_p are determined is produced by re-plotting the probe current in Figure 5.10b as a function of the probe voltage. As explained in Appendix B, if the electron distribution is Maxwellian, the probe I-V characteristic is linear when plotted on a semi-log scale, and the electron temperature is given by the slope of the line. Lower electron temperature causes the slope to be steeper (closer to vertical), while higher T_e is indicated by a more horizontal slope. If T_e changes during the probe voltage sweep, the slope of the characteristic will not be constant. Such a slope change is seen in Figure 5.11, which is Figure 5.10b re-plotted as a probe I-V characteristic, after correcting for ion current. Time points during the pulse are marked on the characteristic. Figure 5.11 shows that as the discharge current decreases with time, the slope of the probe characteristic becomes steeper, indicating that the electron temperature is decreasing. At higher T_{Cs} , both I_C and V_{CE} decrease during

(a) Collector Voltage and Current

(b) Probe Voltage and Current

Figure 5.10 Voltage and Current as a Function of Time at Collector and Probe.

Figure 5.11 Change in Electron Temperature During Probe Measurement.

the discharge, causing the electron temperature to decrease and making the probe characteristic concave upward as in Figure 5.11. At low T_{Cs} , the voltage drop and T_e increase as the current decreases, and the probe characteristics are typically concave downward.

In cases such as the one just described, the measured value of T_e in Figure 5.9 depends on the judgment of the experimenter when reading the slope of the probe I-V characteristic. The slope of the line drawn in Figure 5.11 gives the electron temperature near the beginning of the probe measurement. If the line is drawn through the upper part of the curve, the electron temperature near the end of the probe measurement is found. The calculated values of T_e at the beginning and end of the measurement in Figure 5.11 are shown in Table 5.2, along with the values of n and V_p , which depend on T_e . As the results in the table indicate, the measured values depend strongly on the interpretation of the probe characteristics, which introduces additional uncertainty to the experimental data. It should be pointed out that the problem of plasma parameters changing during measurement could be virtually eliminated by using a faster voltage sweep on the probe.

Table 5.2 Calculated Plasma Parameters at the Beginning and End of the Probe I-V Characteristic.

	Beginning	End	$\Delta\%$
T_e (K)	11339	8089	33.5 %
n (m^{-3})	4.08×10^{19}	4.78×10^{19}	16.7 %
V_p (V)	5.72	4.08	33.5 %

The results presented in this section show that plasma parameters calculated by the discharge model are in reasonable agreement with experimental values in the steady

state. It was shown in Chapter 4 that the circuit-driven transient model properly accounts for the effect of the discharging capacitor on the terminal characteristics of the Cs-Ba diode. Therefore, the transient model should compare favorably with time-dependent probe measurements. Having shown that the model can calculate the internal plasma parameters with reasonable accuracy in the steady state, the model can now be used to explain the transient processes in the discharge and the hysteresis of the I-V curves. This is done in the next two sections.

5.5 Changing Plasma Conditions in Time

In this section the changes in the plasma conditions during the discharge are explained. Model calculations are verified by experimental measurements, with emphasis on explaining the hysteresis in the I-V curves. The calculations are performed using the half I-V source current in Figure 5.3 as input to the circuit-driven transient diode model.

The terminal voltage and current characteristics indicate that even with a constant source voltage, it takes some time for the discharge to reach equilibrium. An example is the first millisecond of the discharge current and voltage in Figure 5.10a, in which V_{CE} increases and I_C decreases rapidly. This rapid changes are due to changing plasma conditions. After the first ms, I_C and V_{CE} both decrease due to the decreasing source voltage. When the operation conditions are favorable (i.e. Cs pressure sufficiently high), the discharge reaches an equilibrium after a few ms (except for the decreasing source voltage). If the initial Cs pressure is too low, however, a steady state is not reached, and the discharge either oscillates or self-extinguishes. Discharge oscillations and self-extinguishing are more prevalent at higher discharge currents, and Figure 5.1 shows that the solid collector diode is more prone to oscillation than the hollow collector diode. An explanation of the changing plasma conditions during the first few milliseconds before

equilibrium is reached follows. An explanation of the conditions leading to the observed oscillations and discharge self-extinguishing is also offered.

When the discharge ignites, ions are created and immediately begin to leave the open discharge volume due to ambipolar diffusion. Since the ions leave the volume at the Bohm speed (equation (4.3)), which is faster than the speed of the atoms entering the volume from the surroundings, the Cs pressure in the gap decreases. The decrease in Cs pressure in the gap continues until the sum of the ion and atom fluxes out of the gap equals the flux of atoms into the gap from the reservoir. As the plasma density decreases, the electron temperature increases in order to maintain the discharge current density, at the expense of increased voltage drop. The change in plasma density and electron temperature is illustrated in Figure 5.12, which shows the calculated plasma density and electron temperature as functions of time compared to experimentally measured values near the emitter and collector. Results in Figure 5.12 show the plasma density decreasing with time during the discharge, and the electron temperature increasing to compensate for the ion loss by increasing the ionization rate. The calculated values of n and T_e are in good agreement with the measured values. The calculated T_e is within 15% of the average measured value between emitter and collector, and the calculated n generally falls between the measured values. The calculated plasma density drops sooner than the measured value after 2.5 ms, because the model, as developed in Chapter 4, does not properly account for the contraction of the discharge to a filament below the knee, as discussed in section 5.2.1. The shape of the calculation depends on the form of $\Lambda(t)$ in equation (4.20). For these calculations, Λ is constant for the first millisecond, then decreases as $(1 - t^{1.2})$ to zero at 3.0 ms. With this simple formula for Λ , the calculated V_{CE} does not exactly match the measured value with time.

Calculated and measured plasma properties are compared in Figure 5.13 for two different Cs reservoir temperatures; again the model shows the same trends as the experiment. The measurements are made near the collector. Figure 5.13 shows that the

(a) Plasma Density

(b) Electron Temperature

Figure 5.12 Measured and Calculated Electron Temperature and Plasma Density.

(a) Plasma Density

(b) Electron Temperature

Figure 5.13 Electron Temperature and Plasma Density for Two Cs Pressures.

plasma density is higher and the electron temperature is lower for higher Cs reservoir temperature, T_{Cs} . This indicates that the plasma is easier to ionize when the background Cs pressure is higher, because there are more neutrals available to ionize. The leakage of ions from the discharge, decreasing the plasma density and increasing the electron temperature, are thus demonstrated by the experimental measurements and model calculations. An explanation of self-extinguishing and oscillation of the discharge at low Cs pressure is offered below.

Kaplan et al. (1979) measured a critical current density as a function of Cs pressure, above which the discharge self-extinguishes. When the initial Cs pressure is low (or I_C is high), T_e is high initially, and increases as the plasma density decreases due to ion leakage. The electron temperature increases at the expense of increasing the forward voltage drop. The ion leakage rate increases with T_e (equation (4.3)), which increases T_e even further until the voltage drop is limited by the source voltage. Beyond this point T_e cannot increase further. The plasma density drops below the critical value, causing the discharge to self-extinguish. At intermediate Cs pressures or lower currents, the increase in T_e and the corresponding increase in ionization rate can produce enough ions to lower the electron temperature, reducing the ionization rate, requiring another increase in T_e , causing oscillation of the discharge. When the Cs pressure in the gap is high enough for a given current, the discharge will reach a steady state, as seen earlier. This explanation of plasma conditions leading to oscillation and self-extinguishing is reasonable based on observed and calculated behavior of n and T_e in Figures 5.12 and 5.13. When the plasma density decreases as shown in these figures, the total Cs pressure in the discharge volume decreases also, as discussed below.

The transient model calculation of the change in Cs pressure in the discharge volume as a function of time is shown in Figure 5.14a. This figure shows the total Cs pressure (the sum of the partial pressures of ions and atoms in all states) normalized to the initial Cs pressure in the gap, which equals that of the Cs reservoir. Results in Figure

(a) Relative Cs Pressure in the Gap

(b) Cs Coverage on the Collector

Figure 5.14 Calculated Cs Pressure and Cs Coverage.

5.14a indicate that the Cs pressure in the gap drops rapidly with time after ignition reaching a minimum at ~ 1 ms; the minimum pressure is about one third the initial pressure. The time to reach this minimum pressure depends on the desorption rate of Cs atoms from the surfaces, as explained in section 5.6. Because the source current is decreasing (Figure 5.3), the discharge does not ever reach an equilibrium. As the source current is reduced, T_e decreases, the ion leakage rate decreases and the pressure rises again.

As the Cs pressure in the gap decreases during the discharge, Cs atoms desorb from the collector surface, adding to the Cs pressure in the gap. The calculated Cs coverage on the collector surface is shown in Figure 5.14b. In the low pressure Cs-Ba diode, there can be more Cs atoms adsorbed on the collector surface than there are in the discharge gap. For example, at $T_{Cs} = 155^\circ\text{C}$, P_{Cs} is 1.08×10^{-2} Torr, which corresponds to a Cs atom density of $\sim 2.3 \times 10^{20}/\text{m}^3$, or 4.6×10^{13} atoms in the discharge volume. When $\theta = 0.35$, the number of Cs atoms on the 2 cm^2 collector surface is $\sim 4 \times 10^{14}$, an order of magnitude greater than the number in the discharge gap.

Before discharge ignition, the Cs coverage on the collector surface is at equilibrium with the initial Cs pressure in the gap, i.e. the desorption flux equals the Cs atom flux to the surface from the vapor. Recall from equation (4.16) that the desorption flux increases with coverage. Following ignition the Cs pressure in the gap decreases due to ion leakage, reducing the flux of Cs to the surface, resulting in the desorption flux becoming higher than the flux from the volume. The Cs atom flux from the surface helps to maintain the pressure in the gap longer than if there were no adsorbed Cs. The Cs coverage decreases until the desorption flux equals that due to the new lower pressure in the gap. At this point the Cs pressure reaches an equilibrium, in which the total Cs atom and ion flux to the electrode surfaces and out of the volume equals the Cs atom flux into the volume from the surfaces and from the Cs reservoir. The time to reach

equilibrium depends of the desorption rate from the surface, which is discussed in the following section.

5.6 Desorption of Cesium From the Electrode Surfaces

The rate of change of Cs pressure in the diode gap and the coverage on the surfaces during discharge depend on the desorption rate of Cs from the electrode surfaces. The desorption rate of Cs depends on the surface temperature and the desorption energy, H (equation (4.16)). If H is small, the desorption rate is high and the Cs pressure in the diode gap drops quickly after ignition, eventually reaching an equilibrium value. Larger H slows down the Cs desorption from the surfaces, increasing the time to reach equilibrium. Figure 5.15 shows the effect of different values of H ($H = 1.5 - 2.0$ eV) on the time for the plasma to reach equilibrium following a step change in Cs pressure. The calculation shown in the figure is done by holding the source voltage constant in the model, then suddenly reducing the Cs pressure in the gap and the reservoir by a factor of two. This calculation, although somewhat unrealistic physically, nevertheless shows the effect of H on the time to reach equilibrium. The Cs pressure in the gap shows a spike at $100\text{ }\mu\text{s}$ when the Cs pressure is dropped in the model. Then the Cs pressure and plasma density quickly increase due to the high Cs desorption rate, reaching a maximum when the desorption rate of Cs atoms from the surface equals the net loss of Cs atoms and ions due to leakage. As the Cs coverage on the surface decreases, the desorption rate becomes less than the leakage rate, and the plasma density and Cs pressure in the gap decrease at a rate depending on H . When the supply of Cs on the surfaces is exhausted, the Cs pressure and ion density in the gap reach equilibrium values of $\sim 20\%$ and $\sim 40\%$ of the initial values, respectively. The total leakage rate of Cs atoms and ions out of the discharge volume and to the electrode surfaces corresponding to this equilibrium pressure equals the rate of Cs atoms entering the gap

(a) Calculated Pressure

(b) Calculated Plasma density

Figure 5.15 The Effect of Desorption Energy on the Time to Reach Equilibrium.

from the reservoir plus the desorption rate from the electrode surfaces. The time it takes for the discharge to reach equilibrium depends on the initial Cs pressure and the value of H (Figure 5.15). The value of H and the equilibrium time strongly influence the shape of the I-V characteristics. This effect is discussed in the next subsection.

5.6.1 Effect of H on the I-V Characteristics

The forward voltage drop and discharge current for a given load resistance, and the plasma parameters strongly depend on not only the initial Cs pressure in the gap (Figures 4.9, 5.8, and 5.9), but also on the Cs pressure in the gap during the discharge. Lower Cs pressure corresponds to lower discharge current and higher voltage drop for a given load resistance (Figure 5.8). It has been shown that for a given initial Cs pressure, I_C and V_{CE} change rapidly as the Cs pressure in the discharge gap approaches equilibrium (1st ms of Figure 5.10a, and discussion in section 5.5). In the I-V mode, the rate of change of Cs pressure in the gap, relative to the rate of change of the source current, would affect the shape of the I-V curve.

The effect of different values of H on the calculated I-V characteristic at $T_{EM} = 1100^\circ\text{C}$, $T_C = 700^\circ\text{C}$, and $T_{Cs} = 160^\circ\text{C}$ (13.6 mTorr) is shown in Figure 5.16a. The calculation shows that a higher value of H leads to greater difference in the forward voltage drop between the beginning (left side) and end (right side) of the I-V curves. From the calculation in Figure 5.16a the following trends are observed: (a) the left sides of the three I-V curves differ only slightly below the knee, because even with the lowest value of H the Cs pressure does not change much during the time ($\sim 500 \mu\text{s}$) the current is rising to the knee. (b) Above the knee, the curve with the highest H reaches the highest peak current, because the Cs pressure is higher at that point in time, $\sim 1000 \mu\text{s}$ (refer to Figure 5.15). (c) The three curves coincide below the load line at $\sim 18 \text{ A}$, between 4 V and 5 V, because they all converge to the same equilibrium pressure during

(a) Effect of H on the Hysteresis of I-V Curves

(b) Comparison of Calculated and Experimental I-V Curves

Figure 5.16 Effect of the Desorption Energy on the Hysteresis of I-V Curves.

the constant current portion of the I-V pulse. (d) The greatest difference between the curves is on the right side of the I-V characteristic as the current decreases below 17 A. As shown in Figure 5.14, when the current begins to decrease at the end of the I-V pulse, the Cs pressure in the gap increases as the rate of leakage from the gap decreases. A larger value of H makes the Cs pressure rise more slowly at the end of the I-V pulse, because the desorption rate is smaller, and the Cs atoms become trapped on the surface instead of adding to the pressure in the gap.

The value of H used in the model is chosen to fit the experimental I-V curves such as those shown in Figure 5.16b. Figure 5.16b compares the calculated I-V curve with an experimental I-V curve at the same conditions. This figure clearly shows that the calculated I-V curves are in good agreement with experimental data when $H \approx 1.75$ eV. This value of H is within the range of minimum and maximum desorption energy of Cs on Mo, 1.0 -- 2.85 eV (Magera and Davis 1994). A comparison of Figures 5.16b and 4.7 shows that the diode model calculation is in better agreement with I-V curves from the solid collector diode than the hollow collector diode.

In this section it was shown that the value of H affects the equilibrium time and the shape of the I-V characteristics, and an empirical value for H of 1.75 eV was determined from the comparison of model calculations with experimental I-V curves, which is reasonable based on published data. The next section presents experimental results related to the foregoing discussion of Cs desorption.

5.7 Experimental Results

In this section experimental results are presented that show interesting characteristics of the Cs-Ba diode, which have not been reported earlier for either the hollow collector diode or the tacitron. Results show the effect of barium pressure on the I-V characteristic, and the change in the emitter work function due to adsorbed cesium.

5.7.1 Effect of Barium Pressure on I-V Characteristics

Previous experiments with both the tacitron and the hollow collector diode have shown that barium pressure, P_{Ba} , affects the thermal emission current (the knee), but does not affect the forward voltage drop after ignition (left hand side of the I-V characteristic) (Wernsman et al. 1994, Murray et al. 1993, El-Genk et al. 1992). The solid collector diode results, however, clearly show that P_{Ba} does indeed affect the forward voltage drop. Results in Figure 5.17 show that changing the barium reservoir temperature, T_{Ba} , affects not only the forward voltage drop, but also the shape of the I-V characteristic. The shift of the I-V curve to the right at lower P_{Ba} could be due to a change in the emitter and collector work functions. The greater difference in voltage drop between the left and right sides of the I-V curve at lower T_{Ba} is due in part to the oscillations that occur at the lower Ba pressure. These oscillations increase the forward voltage drop and electron temperature and therefore increase ion leakage, which reduces the Cs pressure in the gap.

As seen in Figure 5.17, increasing P_{Ba} in the gap lowers the forward voltage drop, as well as decreasing the hysteresis of the I-V curves and making the discharge less prone to oscillations. These effects are the same as those associated with increasing Cs pressure. These results suggest that despite the relatively low Ba pressure in the diode (~ 20 times less than P_{Cs}), the Ba is somehow indirectly contributing to the plasma. The nature of this contribution is not known, but it could be argued that it is caused by the relative Ba coverage on the electrode surfaces. Changes in Ba coverage affect the desorption of Cs from the electrodes, and therefore affect the discharge.

The greater hysteresis of the I-V curves at lower T_{Ba} is due in part to the reduced Ba coverage on the collector, which increases H for Cs (Magera and Davis 1994). As explained in the previous section, increasing H widens the I-V characteristic (Figure 5.16a). Another result not previously reported for either the tacitron or the hollow

(a) $T_{EM} = 1100^\circ\text{C}$

(b) $T_{EM} = 1200^\circ\text{C}$

Figure 5.17 Effect of Barium Pressure on the I-V Characteristic.

collector diode is the presence of a second knee on the right side of the I-V characteristic; this is addressed in the next subsection.

5.7.2 The Second Knee

As seen in Figure 5.17, the I-V curves for the Cs-Ba diode show the existence of two knees at different emission currents, one on the left side of the I-V characteristic (current going up) and the other on the right side (current going down). For example, in Figure 5.17b, the $T_{Ba} = 515^{\circ}\text{C}$ curve has the first knee at ~ 12 A and 2.4 V, while the second knee is at ~ 3.5 A and 2.8 V. The two knees are indicated by circles on a typical I-V curve in Figure 5.18a, where the arrows indicate the increase and decrease of the current with time. The first knee has higher thermal emission current, which corresponds to a lower emitter work function (equation (4.17)). As stated in Chapter 1, Ba vapor is added to the gap to reduce the emitter work function below that of bare Mo, to increase the emission current. The work function is further reduced by the presence of a small amount of Cs co-adsorbed with the Ba on the emitter surface (Psarouthakis 1969, Konoplev et al. 1972, Magera and Davis 1994).

Although the change in thermal emission current is significant, the change in the emitter work function between the first and second knees is very small. The first knee in Figure 5.18a is at 13 A, or 6.5 A/cm^2 , while the second knee is at 6 A, or 3 A/cm^2 . At an emitter temperature of 1100°C , these currents correspond to emitter work functions of 2.06 eV and 2.15 eV, respectively, calculated using equation (4.17). The work function change due to co-adsorbed Cs required to achieve the higher emission current at the first knee, is 0.09 eV. A work function change of this magnitude is reasonable according to Magera and Davis (1994), who showed that even with high Ba coverage, the addition of Cs vapor can cause a work function change of 0.2 eV. A similar result was reported by Psarouthakis (1969).

(a) Typical I-V Curve Showing the Existence of Two Knees

(b) Second Knees at Two Different Cs Pressures

Figure 5.18 I-V Curves With Second Knees.

Since the desorption rate of Cs increases with increasing surface temperature (equation (4.16)), the emitter has little Cs initially, which is quickly desorbed as the Cs pressure in the gap decreases during discharge. When the Cs is desorbed from the emitter surface, the work function increases slightly to a value corresponding to the work function of Mo in pure Ba vapor. This is evidenced by the fact that the emission current of the second knee does not depend on the Cs pressure in the gap. Figure 5.18b shows the second knee at two different T_{Cs} , which correspond to widely differing P_{Cs} in the gap. Although the voltage drops corresponding to the second knees of the two curves differ by 1.75 V, they occur at the same emission current of 5 A, which means that the emitter work function is the same in both cases. The work function of the emitter in pure Ba is tabulated in Table 5.3 for various conditions. The values of emitter work function shown in the table are obtained by averaging the emission current at the second knee for several curves at each value of T_{EM} and T_{Ba} , then calculating ϕ_E using equation (4.17). Table 5.3 shows that the lowest observed value of ϕ_E is 2.21 eV, for $T_{EM} = 1100^\circ\text{C}$ and $T_{Ba} = 550^\circ\text{C}$. This value corresponds to the minimum value of the work function for pure Ba on Mo reported by Magera and Davis (1994). Increasing either T_{EM} or T_{Ba} increases ϕ_E above this minimum value. Decreasing either T_{EM} or T_{Ba} below 1100°C and 515°C respectively should also increase ϕ_E .

Table 5.3 Emitter Work Functions in Pure Ba Vapor.

T_{EM}	Emitter Work Function	
	$T_{Ba} = 515^\circ\text{C}$ (2.3×10^{-4} Torr)	$T_{Ba} = 550^\circ\text{C}$ (6.9×10^{-4} Torr)
1100°C	2.21 eV	2.25 eV
1200°C	2.34 eV	2.38 eV
1300°C	2.55 eV	--

Chapter Summary

In this chapter, experimental results were presented to verify some of the assumptions in the diode transient model. It was found that the plasma properties are not homogeneous across the discharge gap, with electron temperature varying by 10 - 15%, plasma density varying by a factor of three, and plasma potential by ~ 1 V. Experimental evidence was shown suggesting that the discharge contracts to a filament below the knee in the I-V characteristic. Probe measurements showed that the electron energy distribution is close to a Maxwell distribution function at high discharge currents, but at lower currents there is evidence of an electron beam.

A modification was made to the transient model to include the additional current at the collector due to the presence of the electron beam. With this modification, the model was shown to calculate the steady-state plasma parameters with reasonable accuracy. Transient model results were presented to explain the changing plasma conditions with time as the discharge approaches equilibrium; model predictions were verified with time-dependent probe measurements. The transient model calculations of n and T_e as a function of time were reasonably accurate when compared with measurements. An explanation of the causes of discharge oscillation and self-extinguishing was offered, and transient model calculations of the change in Cs pressure and Cs coverage on the surface during discharge were given. The effect of H on the time to reach equilibrium and on the I-V characteristics was investigated, and a value of $H = 1.75$ eV was found to give the best comparison between calculated I-V curves and experimental data. Finally, the effect of Ba pressure on the I-V characteristic and the change of the emitter work function due to adsorbed Cs were discussed. It was shown that increasing Ba pressure decreased the forward voltage drop and increased the hysteresis of the I-V curves. The I-V curves showed the existence of two thermal emission current knees, corresponding to different emitter work functions at the beginning and end of the I-V pulse. It was found that at an emitter temperature of

6. Summary and Conclusions

In this work a transient model of a Cs-Ba diode is developed and experiments are performed using a diode equipped with Langmuir probes. The experiments include measurement of the current-voltage characteristics of the diode for various conditions, and Langmuir probe measurements of the plasma properties. The probe measurements are made with the diode operating in both a steady-state mode and the I-V mode. The transient model includes equations for electron energy, plasma density, densities of ground state and the first four excited states of neutral Cs atoms, electron emission, Cs coverage on the electrode surfaces, a current balance at each electrode, and a potential balance. Model development is carried out in two steps: (a) a transient discharge model, in which either the discharge current or forward voltage drop is an input, and (b) a circuit-driven model, in which the external circuit is coupled to the transient discharge model and used to obtain a relationship between the discharge current and the forward voltage drop.

Experimental Results

Comparison is made between the I-V curves generated by two diode types, with solid and hollow collectors. The hollow collector diode is produced by configuring the grid of the tacitron (triode) as the collector, while the solid collector diode has the grid of the tacitron removed. It is found that the solid collector diode exhibits more anomalous Schottky current and greater hysteresis in the I-V curves than the hollow collector diode.

Experimental investigation of three of the model assumptions is performed. These assumptions are the validity of the Maxwellian energy distribution, contraction of the discharge to a filament below the thermal emission current, and the homogeneity of plasma properties across the diode gap. Evidence is presented showing that the discharge does contract to a filament at low current. The Langmuir probe data show that the

electron energy distribution in the discharge gap is non-Maxwellian at low discharge currents, indicating the presence of an electron beam from the emitter. The plasma properties are found to be non-homogeneous across the 1 mm diode gap, with the electron temperature being 10 -- 15% higher and the plasma potential ~ 1 V higher near the emitter, and the plasma density a factor of three higher near the collector.

The effect of changing Ba pressure on the I-V characteristics is also investigated experimentally. Increasing Ba pressure is found to have the following effects on the I-V curves: (a) it decreases the minimum voltage drop, (b) makes the discharge less prone to oscillations, and (c) reduces the hysteresis of the I-V curves. The reason for these effects is not known.

Experimental I-V curves in the solid collector diode show the presence of two knees at different thermal emission currents, corresponding to different emitter work functions at the beginning and the end of the I-V pulse. It is concluded that the presence of adsorbed Cs on the emitter lowers the emitter work function by a small amount, which corresponds to a large increase in the emission current. This reduced work function does not last long after the discharge ignites because the Cs desorbs quickly from the emitter. The higher work function at the end of the I-V pulse, corresponding to the second knee, is that of pure Ba adsorbed on the molybdenum emitter. The minimum observed value of emitter work function at the second knee, 2.21 eV, is the same as the minimum work function for pure Ba on a molybdenum electrode published in the literature.

Transient Model Results

The transient model calculated I-V curves compare well with the experimental I-V curves. This good comparison verifies that the analysis of the external circuit is accurate and the transient solution procedure is correct. The I-V curves calculated by the diode transient model are in better agreement with measured data from the solid collector diode than the hollow collector diode.

Based on the comparison of the model predictions with experimental measurements, it is concluded that the electron beam component of the collector current is significant. The electron energy equation and the current balance at the collector account for this beam current. The discharge model, with discharge current and voltage drop input, compares well with the measured values of electron temperature, plasma density, and plasma potential as a function of Cs pressure at steady state. The transient model calculations are also shown to be in good agreement with measured values of electron temperature and plasma density as functions of time during discharge.

The model is also used to calculate the Cs pressure and Cs coverage on the collector surface as a function of time. These calculations reveal that the Cs pressure in the gap decreases during the discharge to an equilibrium value about one third of the original pressure. The effect of the Cs desorption rate from the collector on the time for the Cs pressure to reach equilibrium is calculated. The value of the desorption energy is also found to have an effect on the calculated I-V curves. It is shown that increasing the desorption energy increases the hysteresis in the calculated I-V curves, by slowing the rise of Cs pressure at the end of the I-V pulse. An empirical value of 1.75 eV for the desorption energy is determined by comparison of the hysteresis of calculated and measured I-V curves. This value is consistent with published data.

The good agreement between the calculations and the experiment, in spite of the presence of the electron beam from the emitter, shows that the beam electrons do not undergo collisions with Cs atoms. Therefore the model assumption of a Maxwell-Boltzman electron energy distribution is justified for the calculation of the rate coefficients. Although the model includes no spatial dependence, the calculated plasma properties are usually within the experimental uncertainty of the average of the measurements near the emitter and collector.

6.1 Recommendations for Future Work

The addition of spatial dependence to the model that would increase its accuracy. Because of the large variation of the plasma properties across the gap, a one dimensional model should improve the accuracy of the calculations. Instead of using the more computationally intensive Boltzman equation, the present system of equations can still be used by dividing the diode gap into a series of regions, with appropriate coupling between regions.

Experimental results show that the discharge contracts to a filament below the knee corresponding to the thermal emission current. The transient model solution method must therefore be modified to take this into account by calculating the cross-sectional area of the filament as the source current is increased and/or decreased.

Changing Ba pressure is found to have a significant effect on the I-V curves in the diode. Since this effect has not been seen before in either the hollow collector diode or the tacitron, these results should be verified by repeating the measurements. Depending on the result of these measurements, the diode transient model may need to be modified to include these effects.

The change in emitter work function during the discharge and the associated change in the thermal emission current are not accounted for in the model. The thermal emission current is an input to the model, but it is not known how this current changes with time during the discharge. Experimental measurement of the emitter work function as a function of Cs and Ba vapor pressure and emitter temperature would eliminate this problem, since the Cs pressure in the diode is calculated by the model. In conjunction with this experimental work, measurement of the desorption energy of Cs as a function of Cs and Ba coverage on the electrode surfaces would eliminate the need to fit the desorption energy to the experimental data.

The most important future work is to extend the Cs-Ba diode model to be applicable to the tacitron, including the three regions of the thick-grid discharge (emitter-grid gap, grid holes, and grid-collector gap). The calculations of such a tacitron model could be verified by comparison with Langmuir probe measurements taken in a Cs-Ba tacitron.

Appendix A: Vapor Pressure of Cesium and Barium

The vapor pressure of a substance in the solid or liquid phase is the partial pressure of the vapor phase when the substance is in equilibrium with its own vapor. Since the vapor pressure of a substance is a function of temperature, the pressure of cesium or barium vapor in the experimental device can be controlled by controlling the temperature of the bulk liquid or solid in their respective reservoirs. Hatsopoulos and Gyftopoulos (1973) give an empirical correlation for the vapor pressure of liquid cesium (melting point 28.4°C):

$$P_{Cs}(\text{torr}) = \frac{2.45 \times 10^8}{\sqrt{T_{Cs}}} e^{-\frac{8910}{T_{Cs}}}, \quad (\text{A.1})$$

where T_{Cs} is the cesium reservoir temperature in Kelvin. A graph of this equation is shown in Figure A.1.

The vapor pressure data for barium are not very reliable, but the most recent correlation is from Alcock et al. (1984). They give this equation for solid barium (melting point 725°C):

$$\log_{10}(P) = 12.405 - \frac{9690}{T_{Ba}} - 2.289 \log_{10}(T_{Ba}), \quad (\text{A.2})$$

where P is the pressure in atmospheres, and T_{Ba} is the reservoir temperature in Kelvin. Equation (A.2) is valid for temperatures between 300 K and the melting point of barium. A graph of this equation is shown in Figure A.2.

Figure A.1 Vapor Pressure of Cesium as a Function of Temperature.

Figure A.2 Vapor Pressure of Barium as a Function of Temperature.

Appendix B: Probe Theory

The theory of plasma diagnostics using electrostatic probes was first proposed by Irving Langmuir in 1923 (Langmuir 1923). The method involves placing a small electrode in the plasma and varying its potential relative to the plasma potential. When the potential of the electrode is different from the plasma potential, the resulting electric field will accelerate charges of one sign and repel the other. If the potential is large enough, charges of one sign can be repelled entirely. By measuring the current drawn by the probe as a function of the potential, the electron temperature, ion density, electron density, and plasma potential can be determined.

A simple probe circuit often used in this type of measurement is shown in Figure B.1. In practice the varying potential is applied with respect to one of the electrodes (usually the emitter) which also provides the current return path. The current drawn by the probe is measured as a function of the probe voltage, and the resulting I-V characteristic is used to calculate the electron temperature, ion density, and the other plasma parameters.

A typical probe I-V characteristic is shown in Figure B.2, with electron current shown as positive current. The current drawn by the probe is the algebraic sum of the electron and ion currents. When the probe potential is negative with respect to the plasma potential, low-energy electrons are repelled, but the ion current arriving at the probe is approximately constant independent of voltage. When the probe voltage is sufficiently negative, the electron current becomes negligible and only the ion current remains (region A-B in Figure B.2). At point C in the figure, the floating potential, the electron and ion currents are equal. As the probe voltage increases (becomes less negative with respect to the plasma potential), fewer electrons are repelled and the electron current increases rapidly. When the probe voltage reaches and exceeds the plasma potential, the laws governing the rate at which electrons arrive at the probe

Figure B.1 Typical Probe Circuit.

Figure B.2 Typical Probe Characteristic.

changes and the slope of the characteristic changes (point D). Since the electrons are no longer repelled, the electron current gathered by the probe is equal to the random electron current arriving at the edge of the sheath around the probe. Region D-E can be used to calculate the electron density. The plasma potential is point D, the knee of the curve. Since the plasma potential is measured with respect to the electrode, the sheath potentials can be determined.

The plasma parameters are calculated as follows. When the probe voltage is very negative, all but the most energetic electrons are repelled and the electron current is negligible compared to the ion current. The saturation ion current arriving at the probe is the ion current arriving at the sheath edge. The ion current is given by Kagan and Perel (1964) as:

$$I_i = J_i S_p = C n_i q \sqrt{\frac{2kT_e}{M}} S_p, \quad (\text{B.1})$$

where J_i is the current density, S_p is the surface area of the sheath around the probe, n_i is the ion density, q is the electron charge, k is Boltzman's constant, T_e is the electron temperature, M is the ion mass, and C is a constant that depends on the geometry of the probe, $C = 0.8$ for spherical and $C = 0.4$ for cylindrical probes. Since in many cases the thickness of the Langmuir sheath is small compared to the dimension of the probe, in practice S_p is usually taken to be the physical surface area of the probe. Equation B.1 can be used to calculate the ion density n_i when the electron temperature is known.

The electron temperature is calculated from the electron current. Since the ion current is approximately constant as long as the probe potential is negative with respect to the plasma, the electron current is simply the total current minus the ion saturation current. If the electron energy distribution is Maxwellian, the electron current drawn by the probe at a voltage, V , less than the plasma potential, V_p , is given by Chapman (1980) as:

$$I_e = \frac{qn_e v_e}{4} e^{\frac{q(V-V_p)}{kT_e}}, \quad (B.2)$$

where n_e is the electron density and v_e is the electron speed. Taking the natural logarithm of both sides, we find:

$$\text{Ln}(I_e) = (\text{constants}) + \frac{q}{kT_e} (V - V_p). \quad (B.3)$$

When $\text{Ln}(I_e)$ is plotted as a function of the applied probe voltage, the result is a straight line with slope $\frac{q}{kT_e}$, from which the electron temperature is easily calculated.

The plasma potential, V_p , is determined by finding the point where the slope of $\text{Ln}(I_e)$ changes (point D in Figure B.2). The upper part of the curve (region D-E in Figure B.2) gives the electron density, in a manner analogous to equation (B.1), using the electron saturation current and the electron mass instead of the ion saturation current and ion mass.

The plasma potential can also be calculated from the floating potential, where the electron and ion currents are equal (Chapman 1980):

$$J_e = J_i.$$

Substituting for J_e and using equation (B.1) for J_i ,

$$\frac{qn_e v_e}{4} e^{\frac{q(V_p - V_f)}{kT_e}} = C q n_i \sqrt{\frac{2kT_e}{M}}.$$

Now solve for the plasma potential V_p :

$$V_p = V_f + \frac{kT_e}{q} \text{Ln}\left(\frac{M}{2.0106m}\right), \quad (B.4)$$

where V_f is the floating potential and m is the electron mass. Note that the plasma potential is a linear function of the electron temperature.

The above equations for electron temperature were derived assuming a Maxwell-Boltzman distribution of electron energies. If the distribution is not Maxwellian, the plot of $\ln(I_e)$ as a function of probe voltage will deviate from linearity as the energy distribution deviates from Maxwellian. Some examples of probe characteristics that might be observed in a non-Maxwellian plasma are shown in Figure B.3a. Figure B.3b shows the energy distribution inferred from the probe characteristic. The dotted line in Figure B.3a shows the linear probe characteristic expected from a thermal (Maxwellian) plasma. Curve 1 shows a high-energy tail, or beam of electrons. Such a characteristic would be expected near the emitter, before the high-energy electrons from the emitter become thermalized through collisions. Curve 2 shows a depletion of high energy electrons characteristic of inelastic collisions (Gündel et al. 1991). Such a characteristic might be expected if, for example, there was a peak in the ionization cross section at a particular energy, so that electrons with that energy collide and are scattered into a different energy group.

It is possible to calculate the electron energy distribution function itself from the second derivative of the electron current with respect to the probe potential. Using the method of Kagan et al. (1977), we find that the distribution function $f(\epsilon)$ is given by

$$f(\epsilon) = \frac{2\sqrt{2}}{q^2} \sqrt{\frac{m}{q}} \sqrt{V} \frac{d^2 J_e}{dV^2}, \quad (\text{B.5})$$

with ϵ in eV, where V is the probe potential relative to the plasma potential.

There are some practical problems associated with plasma diagnostics using Langmuir probes. The most important concern is to ensure that the probe does not disturb the plasma it is supposed to be measuring. In a low-current discharge, the probe must be very small so that it draws only an insignificant fraction of the discharge current. This is made difficult by the fact that the current drawing surface is not the physical surface of the probe, but the surface area of the sheath around the probe, which can be

(a) Probe I-V Characteristic

(b) Probable Energy Distribution

Figure B.3 Probe Characteristic Showing Deviation From a Maxwell Distribution.

significantly larger. The sheath thickness is usually unknown, and a complicated function of the ion density and the probe voltage.

Another possible problem is the probe voltage. The probe can distort the potential distribution in the plasma, and if the probe voltage exceeds the collector voltage, a second discharge can form between the emitter and the probe which will change the plasma parameters.

In the Cs-Ba diode tested at ISNPS, the probes are long thin wires that stretch across the width of the diode gap. The measured probe characteristic is an integration of the plasma conditions across the width of the gap. Furthermore, at the upper end of the probe I-V characteristic, the probe draws nearly 1 A of current. The probe wire has a small but finite resistance, so there is a potential drop along the length of the probe and different parts of the probe are at different potentials. The actual potential at each point is unknown, which makes the probe characteristic difficult to interpret, since the current drawn by the probe is exponential with probe potential (equation (B.2)).

Appendix C: Schottky Effect

The vacuum work function, ϕ_v , of a material relative to the Fermi level of that material is defined as the energy required to remove an electron from the surface and place it an infinite distance away. Very near the conducting surface, there is an attractive force on the electron, as if there were a positive image charge in the conductor. The potential due to this image force is inversely proportional to the distance from the surface (Baksht et al. 1978b):

$$V(x) = \frac{1}{4\pi\epsilon_0} \frac{q^2}{x}. \quad (C.1)$$

When an external electric field is applied, the resulting potential is the sum of the applied field and the image field (see Figure C.1). The new work function of the surface, ϕ_s , is reduced by an amount $\Delta\phi$ from the vacuum work function (Herring and Nichols 1949). The thermionic emission current increases exponentially with the square root of the applied field. This is called the Schottky effect, and it applies to monocrystalline emitters with uniform work function.

When the surface does not have uniform work function everywhere, but instead has patches with different work functions (when it is polycrystalline or it is coated with an adsorbed film), then electric fields will form between the patches. Figure C.2 shows the electric fields that would be present over adjacent patches of high and low work function (Baksht et al. 1978b). These patch electric fields tend to suppress electron emission from the low work function patches and enhance emission from the high work function patches. The electric potential near the surface in this case is the sum of the image force, the applied field, and the patch fields.

When the external applied electric field is of the same order of magnitude as the patch field, it reduces the patch field which was suppressing electron emission from the

Figure C.1 Schottky Effect.

Figure C.2 Electric Fields Due to Patches With Different Work Functions.

low work function patches, and emission is enhanced greatly. This is called the anomalous Schottky effect. When the applied field is strong enough to completely overcome the patch electric fields, then the normal Schottky effect again determines the emission current density of each patch.

Adsorbed films on the electrode surface exacerbate the anomalous Schottky effect. The desorption energy, or the binding energy of the adsorbed atom to the surface, depends on the work function of the surface, so the film will adsorb preferentially on certain patches, increasing the work function difference between patches.

The Cs-Ba diode tested in this work has an emitter made of polycrystalline molybdenum with adsorbed films of both Cs and Ba, so one would expect the anomalous Schottky effect to prevail. Furthermore, the surface itself has undergone some reconstruction of the crystal structure as a result of the high emitter temperatures used in the device. Macroscopic crystal growth can be observed on the emitter surface with the naked eye. Electron microscope photographs of the electrode surfaces are shown in Figure C.3. This figure shows not only the large surface irregularities, but the boundaries of the various crystal domains. The top electrode shows much larger crystal dimensions because it was operated most recently as the emitter. With such a non-uniform electrode surface, an entirely theoretical surface analysis is extremely difficult.

100 μm

(a) Top Electrode

100 μm

(b) Bottom Electrode

Figure C.3 Microphotographs of the Electrode Surfaces.

Appendix D: Experimental Uncertainty

It was observed during experiments that the voltage drop and shape of the I-V curve are sensitive to the values of the experimental parameters (emitter and collector temperatures, Cs and Ba reservoir temperatures). The temperatures are set by adjusting the current to the various heaters, which drifts around the set point, causing the temperatures to wander as well. The Cs reservoir is fitted with a feedback-controlled heater, which maintains the set temperature within $\pm 0.5^\circ\text{C}$. If the experimenter is careful, the collector and barium reservoir temperatures do not vary by more than $\pm 5^\circ\text{C}$ $\pm 1^\circ\text{C}$, respectively. Fine adjustment of the emitter temperature is made by adjusting the electron bombardment voltage, making it possible to maintain a particular temperature to within $\pm 5^\circ\text{C}$.

The I-V characteristic is very sensitive to even small changes in emitter temperature, shifting by ± 0.5 V with a $\pm 5^\circ\text{C}$ change in emitter temperature. Changes of $\pm 2^\circ\text{C}$ in Cs reservoir temperature can bring about the same magnitude of shift in the I-V curve. The I-V characteristic is less sensitive to the collector temperature, changing by ± 0.5 V with $\sim 20^\circ\text{C}$ temperature change.

The probe measurements also have some degree of uncertainty associated with them. Each calculated parameter (T_e , n , V_p) is computed from several measured parameters, each of which is uncertain. If a calculated quantity A is a function of several variables, $A = f(x_1, x_2, \dots, x_n)$, then the uncertainty in the value of A , w_A , is given by Holman (1984) as:

$$w_A = \left[\left(\frac{\partial f}{\partial x_1} w_{x_1} \right)^2 + \left(\frac{\partial f}{\partial x_2} w_{x_2} \right)^2 + \dots + \left(\frac{\partial f}{\partial x_n} w_{x_n} \right)^2 \right]^{\frac{1}{2}}. \quad (\text{D.1})$$

Each term in equation (D.1) is the product of the dependence of A on one of the variables, times the uncertainty in that variable. Equation (D.1) gives the uncertainty in

the measurements due to error in reading graphs, imprecise measurements, etc. It does not take into account possible systematic errors in the probe technique, such as a non-Maxwellian plasma, the unknown surface area of the sheath around the probe, or disturbance of the plasma by the probe itself, or other uncertainties which are difficult to quantify, such as the change of discharge parameters in time during the probe measurement or non-homogeneity of the plasma conditions across the length of the probe wire.

Using equation (D.1), it is found that the experimental uncertainty in electron temperature measurement is $\pm 10\%$. The measured plasma density is less certain because it depends on T_e . The uncertainty in plasma density ranges from $\pm 25\%$ at low T_{Cs} (high T_e) to $\pm 11\%$ at high T_{Cs} (low T_e). The uncertainty in the measured plasma density is mostly due to the imprecise measurement of the surface area of the probe itself. The area of the probe exposed to the plasma is not exactly known because the edge of the plasma is not well defined. As shown in Figure 3.4, the area of the probe depends on the length of the probe above the emitter face. Any uncertainty in this measurement or in the actual plasma boundary will lead to a large uncertainty in the area of the probe, especially the shorter one which is nearer the edge of the plasma. The calculated plasma potential has a constant uncertainty of ± 0.5 V; however, there seems to be a systematic error in its calculation, as explained in the next section.

Systematic Error in Calculated Plasma Potential

Due to the large surface area of the probes, in all but a few cases the probe power supply was not capable of drawing enough current to reach the electron saturation current. Therefore, it was not possible to obtain the plasma potential directly from the probe characteristic in the usual way, at the point where the slope of the characteristic changes (Appendix B). Instead, the plasma potential was calculated by equating the electron and ion currents at the floating potential, as explained in Appendix B. In the

case where it was possible to obtain the plasma potential directly, the calculated V_p is too high. Figure D.1 shows the probe characteristics for the case where direct observation of V_p is possible ($T_{Cs} = 200^\circ\text{C}$, 74.3 mTorr), for each of the two probes. The solid vertical line in each figure is the directly observed plasma potential, at the point where the slope of the characteristic changes. The observed plasma potentials are 0.164 V and 0.06 V in Figures D.1a and D.1b, respectively. Also shown in Figure D.1 is V_p calculated from the floating potential, indicated by the dashed vertical line. The calculated V_p in Figures D.1a and D.1b are 0.512 V and 0.255 V, respectively. The calculated values exceed the directly observed values by 0.348 V and 0.195 V, respectively. From this result it is inferred that the plasma potential is overestimated in all cases, but probably not by more than 0.5 V in any case.

(a) Long Probe

(b) Short Probe

Figure D.1 Calculated Plasma Potential.

Appendix E: Source Codes

The following is the source code for the current-driven transient model.

```

c                                     94-4-20
c
c      Transient simulation of the diode
c      Includes ground state, 1st,2nd,3rd & 4th excited states and ions
c      Includes the circuit to couple voltage and current

implicit double precision (A-H,O-Z)      ! declare the variables
real*8 RF(0:4,0:5),Jeo,Jr,Ji,Nao,n,me,Mi,k,phic,phie,Nc,N0,N1,N2,N3,N4,Nt
real*8 ni,N0i,N1i,N2i,N3i,N4i,Jse,Jknee,Jit,Jie,Ic,Icc,func,ff,Isource,Iss
real*8 k10L,k21L,k31L,k40L,k42L,k43L,k10D,k21D,k31D,k40D,k42D
real*8 k43D,ko10,ko21,ko31,ko40,ko42,ko43
integer z,int(11),f,flag
character*10 fl(11)
common /four/E10,E20,E21,E30,E31,E32,E40,E41,E42,E43,Ei
common /five/G0,G1,G2,G3,G4
common k,me,q,Mi,pi

open (unit=1,file='inc.inp')
read (1,*) numb
close (unit=1)
open (unit=1,file='inc.inp')
write (1,*) numb+1                      ! new file numbers for running a series
close (unit=1)

c      This is where I alter the names of the input and output files
fl(1) = 'c0.inp'                        ! input file
fl(2) = 'theta0'                        ! coverage output file
fl(3) = 'n0'                            ! atom and ion densities
fl(4) = 'flux0'                         ! flux and desorption rate
fl(5) = 'ic0'                           ! collector and source currents
fl(6) = 'dv0'                           ! sheaths and ion energy
fl(7) = 'te0'                           ! electron temperature
fl(8) = 'iv0'                           ! I-V curve
fl(9) = 'volt0'                         ! Vce and source voltage
fl(10) = 'info0'                        ! information about parameters

do z = 1,10                             ! this block changes '0' to numb
f = index(fl(z),'0')
int(z) = ichar(fl(z)(f:f))
int(z) = int(z) + numb
fl(z)(f:f) = char(int(z))
end do

open (unit=1,file=fl(1))                 ! read in the parameters
read (1,*) Tem1,Tc1,Tcs1,Tba1,Jknee,phic,Iss,ultimate time
read (1,*) dtt,tolerance,Rl,hh
read (1,*) Te,n,dumb,N1,N2,N3,N4
close (unit=1)

```

```

Tem = Tem1+273                                ! convert to Kelvin
Tc = Tc1 +273
Tcs = Tcs1+273
Tba = Tba1+273
open (unit=1,file='A.INP',status='unknown')
read (1,*) A10,A21,A31,A40,A42,A43            ! Einstein's A-coefficients
close (unit=1)
A10o = A10
A21o = A21
A31o = A31
A40o = A40
A42o = A42
A43o = A43
open (unit=1,file='E.INP',status='unknown')    ! energies between states
read (1,*) E10,E20,E21,E30,E31,E32,E40,E41,E42,E43,Ei
close (unit=1)
E15 = Ei - E10
E25 = Ei - E20
E35 = Ei - E30
E45 = Ei - E40
open (unit=1,file='G.INP',status='unknown')    ! degeneracies 2j+1
read (1,*) G0,G1,G2,G3,G4
close (unit=1)
c initialize the constants
me = 9.11D-31                                ! electron mass (kg)
q = 1.602D-19                                ! electronic charge (C)
Mi = 2.22376D-25                              ! Cs ion mass (kg)
pi = 3.14159265358979323                      !  $\pi$ 
k = 1.38D-23                                  ! Boltzman's constant (J/K)
h = 6.626176D-34                              ! Planck's constant
Y10 = h*3.0D8/(q*E10)                         ! Y is lambda upside down
Y21 = h*3.0D8/(q*E21)                         ! These are the wavelengths
Y31 = h*3.0D8/(q*E31)                         ! of the photons emitted in
Y40 = h*3.0D8/(q*E40)                         ! each of the optical transitions
Y42 = h*3.0D8/(q*E42)                         !  $\lambda = hc/E$ 
Y43 = h*3.0D8/(q*E43)                         ! meters
gamma = h/(k*Tc)                              ! vibration frequency of Cs
H = q*hh                                       ! energy of desorption (Joules)
Nc = 2.5D14                                   ! # atoms in a monolayer (1/cm2)
d = 1.0D-1                                    ! gap spacing (cm)
Se = 2.0D0                                    ! emitter area (cm2)
Sc = Se                                       ! collector area (cm2)
Sa = 1.2*Sc                                  ! adsorption area (cm2)
Ss = 2.0D0*pi*d*sqrt(Se/pi)                  ! leakage area (cm2)
V = Se*d                                      ! discharge volume (cm3)
Ta = (Tem + Tc) / 2.0D0                      ! average atom temperature (K)
va = 100. * sqrt(8.*k*Ta/(pi*Mi))             ! atom speed (cm/s)
Pcs = 2.45D8 * exp(-8910./Tcs)/sqrt(Tcs)      ! Cs pressure from eq (A.1) (torr)
A = 0.61 * 2. * sqrt(pi*me/(2.*Mi))           ! A= Ji / Jr, but it turns out to be a constant
Nao = 1.013D5*1.0D-6*Pcs/(760*k*Ta)           ! initial atom density (1/cm3)
Pcs = Nao*k*Ta
C = 1.0D-1                                    ! capacitance of capacitors
Vc = 2.4D1                                    ! initial charge on capacitors
Vt = 4.0D0                                    ! drop across transistor

```

```

Rs = 1.7D0                                ! shunt resistance
print *, 'Tcs =', Tcs
print *, 'which files? ', fl(1)
print *, 'Pcs = ', Pcs*1.0D6, ' Pa'
c set up the initial conditions
t = 0.0D0                                ! start time in seconds
m = 5000                                ! # points to skip before writing
i = 2*m
dt = dtt                                ! time step
Tkeep = Te
N0 = Nao - n - N1 - N2 - N3 - N4          ! ground state density
ve = 100.*sqrt(8.*k*Te/(pi*me))          ! electron speed (cm/s)
Jeo = 120*Tem*Tem*exp(-q*phic/(k*Tem))    ! initial guess (A/cm2)
Ji = 100.*(0.61*q*n*sqrt(k*Te/Mi))        ! ion current density (A/cm2)
Ic = Jeo*Se                              ! initial guess
if (Jeo .ge. sqrt(2)*(Ic/Sc+Ji)) Jeo = 0.99*sqrt(2)*(Ic/Sc+Ji)
Isource = Iss
Vsource = (Isource - Ic)*Rs                ! initial guess, eq. (4.25)
print *, 'Jeo,Ic,Vsource', Jeo,Ic,Vsource
flag = 0
slope = 5.0D1/1.0D-3
flux = Ji/q + va*(N0+N1+N2+N3+N4)/4.0D0    ! atom flux, eq. (4.15)
theta = gamma*flux*exp(H/(k*Tc))/Nc        ! initial coverage on collector, eq. (4.16)
the = gamma*flux*exp(H/(k*Tem))/Nc          ! initial coverage on emitter

open (unit=10,file=fl(10),status='unknown') ! information file
write (10,12) Tem,Tc,Tcs,Rl,hh,Jknee
write (10,13) phic,Sa/Sc,d,theta,the
write (10,*) 'file 1 is ',fl(1), ' He = Hc'
close (unit=10)
d = d / 100.0D0                          ! convert back to meters
12 format('Tem =',F6.0,' Tc =',F6.0,' Tcs =',F5.0,' Rl =',F6.3,
+ ' Hc =',F6.3,' Jknee =',F7.3)
13 format(' φc =',F6.3,' Sa =',F7.4,' *Sc d =',F5.2,2P,
+ ' θc =',F9.4,'%',' θe =',F9.4,'%')
open (unit=2,file=fl(2),status='unknown')
open (unit=3,file=fl(3),status='unknown')
open (unit=4,file=fl(4),status='unknown')
open (unit=5,file=fl(5),status='unknown')
open (unit=6,file=fl(6),status='unknown')
open (unit=7,file=fl(7),status='unknown')
open (unit=8,file=fl(8),status='unknown')
open (unit=9,file=fl(9),status='unknown')

call rate (Te,RF)
do while (t .lt. ultimate time)
  Tei = Te
  ni = n
  N0i = N0
  N1i = N1
  N2i = N2
  N3i = N3
  N4i = N4
  thetai = theta

```

```

thei = the
if (t .gt. .0001) then                                ! discharging capacitor
    RC = C*Vsource/Isource                            ! eq. (4.28)
    Vc = Vc*exp(-dt/RC)                              ! eq. (4.27)
    m = 3000
end if
if (t .gt. .0001 .and. t .lt. .0020) then             ! increasing current part
    Iss = Iss+slope*dt
end if
if (t .gt. .0020 .and. t .lt. .0030) then             ! constant current part
    Iss = 5.0D1
    dt = 1.5D0*dtt
end if
if (t .gt. .003) then                                  ! decreasing current
    Iss = Iss - slope*dt
end if
if (Iss .le. 3.0) Iss = 3.0D0                          ! let it steady out at end
    dt = dtt
end if
if (flag .eq. 1) then                                  ! limited by capacitor voltage
    Isource = Vsource/Rs + Ic                          ! eq. (4.24)
    m = 15000
    if (t .gt. .001) then
        m = 25000
    end if
else
    Isource = Iss
end if
if (t .gt. .003 .and. Iss .le. Isource) then           ! limited by transistor
    Isource = Iss
    m = 3000
    flag = 0
end if
do z=1,20                                              ! internal iteration until Vsource converges
    if (Jeo .le. 0) print *, 'Jeo = ',Jeo
    phie = -k*Tem*log(Jeo/(120.*Tem*Tem))/q           ! emitter work function, eq. (4.17)
    if (Te .lt. 0) print *, 'Te =',Te
    ve = 100.*sqrt(8.*k*Te/(pi*me))                  ! electron speed (cm/s)
    Jr = q*n*ve / 4.                                  ! random current from eq. (4.4) (A/cm2)
    if (Jeo .ge. sqrt(2)*(Ic/Sc+Ji)) Jeo = 0.99*sqrt(2)*(Ic/Sc+Ji)
    dVc = -k*Te*log(Ic/(Jr*Sc) + A - Jeo/(sqrt(2.D0)*Jr))/q ! eq. (5.3)
    if ((Jeo/Jr - Ic/(Jr*Se) + A) .lt. 0) then
        print *, 'Jeo/Jr,Ic/JrSe',Jeo/Jr,Ic/(Jr*Se)
        print *, 'Te,dVe,Ic',Te,dVe,Ic
    end if
    dVe = -k*Te*log(Jeo/Jr - Ic/(Jr*Se) + A)/q        ! emitter sheath potential, eq (4.2a)
c    note that these are deltas, not related in any way to differentials
    He = q*dVe/(k*Te)
    Hc = q*dVc/(k*Te)

c    this is the Rex term that appears in eq. (4.7)
    A0 = RF(0,1)*E10 + RF(0,2)*E20 + RF(0,3)*E30 + RF(0,5)*E40 +
+    RF(0,5)*Ei
    B0 = N0*A0

```

```

+      A1 = -RF(1,0)*E10 + RF(1,2)*E21 + RF(1,3)*E31 + RF(1,4)*E41 +
      RF(1,5)*E15
+      B1 = N1*A1
      A2 = -RF(2,0)*E20 - RF(2,1)*E21 + RF(2,3)*E32 + RF(2,4)*E42 +
+      RF(2,5)*E25
      B2 = N2*A2
+      A3 = -RF(3,0)*E30 - RF(3,1)*E31 - RF(3,2)*E32 + RF(3,4)*E43 +
      RF(3,5)*E35
+      B3 = N3*A3
      A4 = -RF(4,0)*E40 - RF(4,1)*E41 - RF(4,2)*E42 - RF(4,3)*E43 +
+      RF(4,5)*E45
      B4 = N4*A4
      Rex = q*(B0+B1+B2+B3+B4)          ! excited state term, eq. (4.8) (Kelvins/s)
c      actually this is Rex/(n*V)
      B1 = ve*Se*exp(-He)/(3.D0*V)
      B2 = ve*Sc*exp(-Hc)/(3.D0*V)
+      B3 = N0*RF(0,5) + N1*RF(1,5) + N2*RF(2,5) + N3*RF(3,5) +
      N4*RF(4,5) - Ji*(Sa+Ss+Se)/(q*n*V)
+      B4 = A*ve*Ss*7.7837/(6.D0*V)
      B5 = (B1+B2+B3+B4)
      C1 = Jeo*Se*(dVe+2.D0*k*Tem/q)/(3.D0*k*n*V)
      C2 = q*ve*Se*exp(-He)*dVe/(6.D0*k*V)
      C3 = q*ve*Sc*exp(-Hc)*dVc/(6.D0*k*V)
      C4 = 2.D0*Rex/(3.D0*k)
      C5 = C1-C2-C3-C4
      dTe = (C5-Te*B5)*dt              ! electron temperature, equation (4.22)
      Te = Tei + dTe
      if (abs(Tkeep - Te) .gt. 1.0) then ! recalculate rate coefficients if Te has
      call rate (Te,RF)                 ! changed by more than 1 Kelvin
      Tkeep = Te
    end if
      ve = 100.*sqrt(8.*k*Te/(pi*me))  ! electron speed (cm/s)
      Ji = 100.*(0.61*q*n*sqrt(k*Te/Mi)) ! ion current density, eq (4.3)
      dn = (n*N0*RF(0,5) + n*N1*RF(1,5) + n*N2*RF(2,5) +
+      n*N3*RF(3,5) + n*N4*RF(4,5) -
+      Ji*(Sa+Ss+Se)/(q*V))*dt
      n = ni + dn                      ! plasma density, eq. (4.9) (ions/cm3)
      Ji = 100.*(0.61*q*n*sqrt(k*Te/Mi)) ! ion current density, eq. (4.3)

c      What follows is the calculation of radiation re-absorption
      Nt = N0 + N1 + N2 + N3 + N4
      s1 = sqrt(Mi/(2.0D0*k*Ta*log(2)))
      k10L = Y10**3*g1/(g0*4.0D0*pi*pi)*N0*1.0D6*A10o*s1
      k21L = Y21**3*g2/(g1*4.0D0*pi*pi)*N1*1.0D6*A21o*s1
      k31L = Y31**3*g3/(g1*4.0D0*pi*pi)*N1*1.0D6*A31o*s1
      k40L = Y40**3*g4/(g0*4.0D0*pi*pi)*N0*1.0D6*A40o*s1
      k42L = Y42**3*g4/(g2*4.0D0*pi*pi)*N2*1.0D6*A42o*s1
      k43L = Y43**3*g4/(g3*4.0D0*pi*pi)*N3*1.0D6*A43o*s1
      s2 = sqrt(Mi/(2.*pi*k*Ta))
      k10D = Y10**3*g1/(g0*8.0D0*pi)*Nt*1.0D6*A10o*s2 ! N0
      k21D = Y21**3*g2/(g1*8.0D0*pi)*Nt*1.0D6*A21o*s2 ! N1
      k31D = Y31**3*g3/(g1*8.0D0*pi)*Nt*1.0D6*A31o*s2 ! N1
      k40D = Y40*Nt*Y40*1.0D6*Y40*g4/(g0*8.0D0*pi)*A40o*s2 ! N0
      k42D = Y42**3*g4/(g2*8.0D0*pi)*Nt*1.0D6*A42o*s2 ! N2

```

```

k43D = Y43**3*g4/(g3*8.0D0*pi)*Nt*1.0D6*A43o*s2 ! N3
ko10 = k10L*k10D/(k10L + k10D)
ko21 = k21L*k21D/(k21L + k21D)
ko31 = k31L*k31D/(k31L + k31D)
ko40 = k40L*k40D/(k40L + k40D)
ko42 = k42L*k42D/(k42L + k42D)
ko43 = k43L*k43D/(k43L + k43D)
x10L = 4.0D0/(3.0D0*sqrt(pi*ko10*d))
x21L = 4.0D0/(3.0D0*sqrt(pi*ko21*d))
x31L = 4.0D0/(3.0D0*sqrt(pi*ko31*d))
x40L = 4.0D0/(3.0D0*sqrt(pi*ko40*d))
x42L = 4.0D0/(3.0D0*sqrt(pi*ko42*d))
x43L = 4.0D0/(3.0D0*sqrt(pi*ko43*d))
x10D = 0.0D0
x21D = 0.0D0
x31D = 0.0D0
x40D = 0.0D0
x42D = 0.0D0
x43D = 0.0D0
if ((k10D*d) .ge. 1.0) x10D = sqrt(log(k10D*d)/pi)/(ko10*d)
if ((k21D*d) .ge. 1.0) x21D = sqrt(log(k21D*d)/pi)/(ko21*d)
if ((k31D*d) .ge. 1.0) x31D = sqrt(log(k31D*d)/pi)/(ko31*d)
if ((k40D*d) .ge. 1.0) x40D = sqrt(log(k40D*d)/pi)/(ko40*d)
if ((k42D*d) .ge. 1.0) x42D = sqrt(log(k42D*d)/pi)/(ko42*d)
if ((k43D*d) .ge. 1.0) x43D = sqrt(log(k43D*d)/pi)/(ko43*d)
x10 = x10D + x10L ! correction for reabsorption
x21 = x21D + x21L
x31 = x31D + x31L
x40 = x40D + x40L
x42 = x42D + x42L
x43 = x43D + x43L
if (x10 .ge. 1.0) x10 = 1.0D0
if (x21 .ge. 1.0) x21 = 1.0D0
if (x31 .ge. 1.0) x31 = 1.0D0
if (x40 .ge. 1.0) x40 = 1.0D0
if (x42 .ge. 1.0) x42 = 1.0D0
if (x43 .ge. 1.0) x43 = 1.0D0
A10 = x10 * A10o ! effective A-factor, eq. (4.21)
A21 = x21 * A21o
A31 = x31 * A31o
A40 = x40 * A40o
A42 = x42 * A42o
A43 = x43 * A43o

B1a = Nao*va*Ss/(4.D0*V)+n*N1*RF(1,0)+n*N2*RF(2,0)+N1*A10
B1b = n*N3*RF(3,0)+n*N4*RF(4,0)+N4*A40
B1 = B1a + B1b
B2 = n*RF(0,1) + n*RF(0,2) + n*RF(0,3) +
+ n*RF(0,4) + n*RF(0,5) + va*(Sa+Ss+Se)/(4.D0*V)
dN0 = (B1 - N0*B2 + (Da+sput)*Sa/V + (Dae+spute)*Se/V)*dt
N0 = N0i + dN0 ! ground state density, eq. (4.13)

B1 = n*N0*RF(0,1) + n*N2*RF(2,1) + n*N3*RF(3,1) +
+ n*N4*RF(4,1) + N2*A21 + N3*A31

```



```

+      B2 = n*RF(1,0) + A10 + n*RF(1,2) + n*RF(1,3) + n*RF(1,4) +
        n*RF(1,5) + va*(Sa+Ss+Se)/(4.D0*V)
      dN1 = (B1 - N1*B2)*dt
      N1 = N1i + dN1                                ! 1st excited state density, eq. (4.12)
+      B1 = n*N0*RF(0,2) + n*N1*RF(1,2) + n*N3*RF(3,2) +
        n*N4*RF(4,2) + N4*A42
+      B2 = n*RF(2,0) + n*RF(2,1) + A21 + n*RF(2,3) + n*RF(2,4) +
        n*RF(2,5) + va*(Sa+Ss+Se)/(4.D0*V)
+      dN2 = (B1 - N2*B2)*dt
      N2 = N2i + dN2                                ! 2nd excited state density, eq. (4.12)

      B1 = n*N0*RF(0,3) + n*N1*RF(1,3) + n*N2*RF(2,3) + N4*A43 +
        n*N4*RF(4,3)
+      B2 = n*RF(3,0) + n*RF(3,1) + n*RF(3,2) + A31 + n*RF(3,4) +
        n*RF(3,5) + va*(Sa+Ss+Se)/(4.D0*V)
+      dN3 = (B1 - N3*B2)*dt
      N3 = N3i + dN3                                ! 3rd excited state density, eq. (4.12)

      B1 = n*N0*RF(0,4) + n*N1*RF(1,4) + n*N2*RF(2,4) +
        n*N3*RF(3,4)
+      B2 = n*RF(4,0) + n*RF(4,1) + n*RF(4,2) + n*RF(4,3) + A40 +
        A42 + A43 + n*RF(4,5) + va*(Sa+Ss+Se)/(4.D0*V)
+      dN4 = (B1 - N4*B2)*dt
      N4 = N4i + dN4                                ! 4th excited state density, eq. (4.12)

      Da = (theta*Nc/gamma)*exp(-H/(k*Tc))          ! desorption rate from collector, eq. (4.16)
      flux = va*(N0+N1+N2+N3+N4)/4.0D0 + Ji/q       ! atom flux, eq. (4.15)
      sput = Ji/q
      dtheta = (flux - (Da+sput))/Nc * dt
      theta = thetai + dtheta                        ! eq. (4.14)

      Dae = (the*Nc/gamma)*exp(-H/(k*Tem))          ! from emitter, eq. (4.16)
      dthe = (flux - (Dae+sput))/Nc * dt
      the = thei + dthe                              ! eq. (4.14)

      Jr = q*n*ve / 4.                               ! random current, eq. (4.4) (A/cm2)
      Ji = 100.*(0.61*q*n*sqrt(k*Te/Mi))            ! ion current density, eq. (4.3)
      Jse = Jknee*exp(612.697*(Ji**.125)*(dVe**.125)/Tem) ! eq. (4.18)
      if (Jr .le. Jse) then
        Jeo = Jr
      else
        Jeo = Jse
      end if
      if (Jeo .ge. sqrt(2)*(Ic/Sc+Ji)) Jeo = 0.99*sqrt(2)*(Ic/Sc+Ji) ! eq. (5.3)

c    this is my Ic solver.
      fact = 9.0D-1
      do ii=1,9
        Ic = fact*(Jeo+Ji)*Se
        func = Ic*R1 - Vsource + phic + k*Te*log(Se/Sc)/q - phie + ! eq. (4.29)
+        k*Te*log((Ic+Ji*Sc-Sc*Jeo/sqrt(2.D0))/(Jeo*Se+Ji*Se-Ic))/q
        if (func .gt. 0) fact = fact - 1.0D-1
      end do
      do ii=1,50

```

```

if (((Ic+Ji*Sc-Sc*Jeo/sqrt(2)))/((Jeo+Ji)*Se-Ic)) .le. 0) then
  print *, 'log argument 1: ', ((Ic+Ji*Sc)/(Jeo*Se+Ji*Se-Ic))
  print *, 'Ic,Ji,Jeo,(Jeo+Ji)*Se',ic,ji,jeo,(Jeo+Ji)*Se
end if
func = Ic*Rl - Vsource + phic + k*Te*log(Se/Sc)/q - phie + ! eq. (4.29)
+ k*Te*log((Ic+Ji*Sc-Sc*Jeo/sqrt(2.D0))/((Jeo*Se+Ji*Se-Ic))/q)
if (func .gt. 0) then
  do jj = 1,50
    temp = Ic - func*(Ic - Icc)/(func - ff)
    Icc = Ic
    Ic = temp
    ff = func
    if (((Ic+Sc*(Ji-Jeo/sqrt(2)))/((Jeo*Se+Ji*Se-Ic))).le.0) then
      print *, 'log arg 2: ', ((Ic+Ji*Sc)/(Jeo*Se+Ji*Se-Ic))
      print *, 'Ic,Ji,Jeo,(Jeo+Ji)*Se',ic,ji,jeo,(Jeo+Ji)*Se
    end if
    func = Ic*Rl - Vsource + phic + k*Te*log(Se/Sc)/q - phie+ ! eq. (4.29)
    + k*Te*log((Ic+Ji*Sc-Sc*Jeo/sqrt(2.D0))/((Jeo*Se+Ji*Se-Ic))/q)
    if (abs(func - ff) .lt. tolerance) then
      goto 1 ! escape the Ic solver loop
    end if
  end do
end if
step = ((Jeo+Ji)*Se - Ic) * 4. / 5.
Icc = Ic
Ic = Ic + step
ff = func
end do
1 Vss = Vsource
Vsource = (Vss + (Isource - Ic)*Rs)/2.0D0
if ((Vsource+Vt) .ge. Vc) then ! capacitor voltage limit
  Vsource = Vc - Vt
  flag = 1
end if
Vce = Vsource - Ic*Rl ! eq. (4.23)

if (abs(Vsource - Vss) .le. tolerance) go to 500 ! escape the loop
end do ! end of internal iteration

500 if (i .ge. m .or. (ultimate time - t) .le. dt) then
  Pc = (N0+N1+N2+N3+N4+n)*k*Ta ! Cs pressure in the gap
  time = t * 1000000
  Nt = N0+N1+N2+N3+N4 ! total atom density
  write (2,11) time,theta,the,Pc/Pcs ! coverage and relative pressure
  write (3,10) time,n,N0,Nt
  write (4,10) time,flux,Da,Dae,sput,spute
  write (5,20) time,Ic,Isource,Jse,Jeo,Jknee
  write (6,20) time,dVe,dVc,phie,phic
  write (7,20) time,Te
  write (8,20) Vce,Ic ! time,dVe,dVc,phie,phic
  write (9,20) time,Vce,Vsource
  print 30, time,te,jeo,n,Vsource
  print 31, Ic,theta,Vce,Isource,flag,Vc
  i = 0

```

```

        end if
        t = t + dt
        i = i + 1
                                ! these decide which to print out
    end do
10    format (F10.3,1P,E11.3E3,E11.3E3,E11.3E3,E11.3E3,E11.3E3,E11.3E3)
11    format (F9.3,F11.7,F11.7,F11.7,F11.7,F11.7,F11.7,F11.7,F11.7)
20    format (0P,F10.3,F10.3,F10.3,F10.3,F10.3,F10.3)
30    format (' time',F10.3,'  $\mu$ s Te =',F10.3,' Jeo =',F7.3,1P,
+        ' n =',E12.5E2,' Vs =',0P,F7.3)
31    format (' Ic =',F7.3,2P,'  $\theta$  =',F7.3,'% Vce =',0P,F7.3,
+        ' Isource =',F7.3,' limit =',11,' Vc =',F6.2)
    close (unit=2)
    close (unit=3)
    close (unit=4)
    close (unit=5)
    close (unit=6)
    close (unit=7)
    close (unit=8)
    close (unit=9)
    print *, 'numb = ',numb
    stop 'wake up! its done!'
end

```

Appendix F: Capacitor Time Constant

The differential equation for the charge stored on a capacitor as it discharges through a constant resistance is (Serway 1983):

$$\frac{dq}{dt} = -\frac{q}{RC} . \quad (F.1)$$

Integrating this equation and dividing both sides by C , we obtain the familiar expression:

$$V = V_0 e^{-\frac{t}{\tau}} , \quad (F.2)$$

where τ is the time constant, $\tau = RC$. If the resistance is not a constant with respect to time, as in the case of the current source circuit described in Chapter 4, then τ is not constant. The exact solution of equation (F.1) with τ a function of time is:

$$V = V_0 e^{-\int \frac{dt}{\tau}} . \quad (F.3)$$

Since τ is known at each point in time, the integral is easily evaluated using an approximation such as the trapezoidal rule or Simpson's rule.

In the system of equations described in Chapter 4, the time scale of the plasma equations is much shorter than the time constant of the capacitor. The time step used in the model is on the order of nanoseconds to reflect the plasma time scale, whereas the time constant of the capacitor varies from ~ 50 -- 100 ms. In the model, $\frac{\Delta\tau}{\tau}$ is never larger than 3×10^{-5} ; therefore equation (F.2) can be used instead of equation (F.3) without any detectable change in the model results.

References

- C. B. Alcock, V. P. Itkin and M. K. Horrigan (1984) "Vapor Pressure of the Metallic Elements," *Canadian Metallurgical Quarterly*, **23**, 309-313.
- F. G. Baksht, I. G. Gverdtsiteli, G. A. Dyuzhev, V. B. Kaplan, R. Ya. Kucherov, B. Ya. Moizhes, V. K. Nevolin, G. I. Tkeshelashvili, V. P. Tsiberev, and V. G. Yur'ev (1970) "Low-Voltage Arc in a Low-pressure Cesium Converter," *Sov. Phys. Tech. Phys.*, **14**, 1153-1157.
- F. G. Baksht, G. A. Dyuzhev, V. B. Kaplan, A. A. Kostin, A. M. Martsinovskii, and V. G. Yur'ev (1977) "Quenching of Low-voltage Arc at Low Cesium Pressure," *Sov. Phys. Tech. Phys.*, **22**, 153-159.
- F. G. Baksht, V. B. Kaplan, A. A. Kostin, A. M. Martsinovskii, F. N. Rasulov, N. N. Sveshnikova, V. I. Serbin, and V. G. Yur'ev (1978a) "Stationary Conducting State of a Grid-Controlled Switching Element. I," *Sov. Phys. Tech. Phys.*, **23**, 1301-1307.
- F. G. Baksht, G. A. Dyuzhev, A. M. Martsinovskiy, B. Ya. Moyzhes, G. Ye. Pikus, E. B. Sonin, and V. G. Yurev (1978b) Thermionic Converters and Low-Temperature Plasma, Technical Information Center, U. S. Department of Energy.
- F. G. Baksht and A. A. Kostin (1984) "Theory of Switching Transients in Cesium Grid Triodes " *Sov. Phys. Tech. Phys.*, **29**, 1-6.
- F. G. Baksht, B. I. Kolosov, and A. A. Kostin (1990) Matimaticheskoe Modelirovanie Protssessov v Nizkovoltnom Plazmenno-puchkovom Razryade (Mathematical Modeling Processes in Low Voltage Plasma-wave Discharges) (in Russian) Energoatomizdat, ISBN 5-283-03943-9.
- D. Bohm (1949), in The Characteristics of Electrical Discharges in Magnetic Fields, A. Guthrie and R. Wakerling, eds., McGraw-Hill, New York, Chapter 3.
- J. R. Bromstead, G. B. Weir, and R. W. Johnson (1993) "200°C Operation of Semiconductor Power Devices," *Proceedings of the 10th Symposium on Space Nuclear Power and Propulsion*, AIP Conf. Proc. 271, American Institute of Physics, New York, 617-623.
- B. Chapman (1980) Glow Discharge Processes, John Wiley and Sons, New York.
- F. F. Chen (1984) Introduction to Plasma Physics and Controlled Fusion Vol. I: Plasma Physics, Plenum Press, New York.

- R. Eisberg and R. Resnick (1985) Quantum Physics of Atoms, Molecules, Solids, Nuclei, and Particles, John Wiley and Sons, New York.
- M. S. El-Genk, V. Kaibyshev, C. Murray, B. Wernsman, and Y. Djashishvili, (1992) "Effect of the Grid Aperture on the Operation of the Cs-Ba Tacitron Inverter," *Proceedings of 27th IECEC*, **2**, 343.
- M. S. El-Genk, V. Z. Kaibyshev, C. S. Murray, B. R. Wernsman, and Y. Djashishvili (1993) "Preliminary Performance Results of the Cs-Ba Tacitron Inverter," *IEEE Transactions on Electron Devices*, **40**, 1335-1339.
- A. G. Fedorus, A. G. Naumovets, and Yu. S. Vedula (1972) "Adsorption of Barium on Tungsten and Molybdenum (011)," *Physica Status Solidi A*, **13**, 445-456.
- H. Gündel, E. Hantzsche, and H. Hess (1991) "Low Temperature Plasmas," *European Journal of Physics*, **12**, 39-46.
- E. P. Gyftopoulos and J. D. Levine (1962) "Work Function Variation of Metals Coated by Metallic Films," *Journal of Applied Physics*, **33**, 67-73.
- G. N. Hatsopoulos and E. P. Gyftopoulos (1973) Thermionic Energy Conversion, Vol. 1, MIT Press, Massachusetts Institute of Technology, Cambridge, Massachusetts.
- C. Herring and M. H. Nichols (1949) "Thermionic Emission," *Reviews of Modern Physics*, **21**, 185-270.
- J. P. Holman (1984) Experimental Methods For Engineers, McGraw-Hill, New York.
- E. O. Johnson, J. Olmstead, and W. M. Webster (1954) "The Tacitron, A Low Noise Thyatron Capable of Current Interruption by Grid Action," *Proc. Inst. Rad. Eng.*, 1350-1361.
- Yu. M. Kagan and V. I. Perel (1964) "Probe Methods in Plasma Research," *Soviet Physics Uspekhi*, **81**, 767-793.
- Yu. M. Kagan, N. B. Kolokolov and B. P. Lavrov (1977) "Electron Energy Distribution in a Contracted Low-pressure Arc. I Probe Measurements," *Sov. Phys. Tech. Phys.*, **22**, 345-349.
- V. Z. Kaibyshev, G. A. Kuzin, and M. V. Mel'nikov (1972) "Use of a Thermionic Converter for Regulation of Current in Electric Circuits," *Sov. Phys. Tech. Phys.*, **17**, 1006-1009.

- V. B. Kaplan, A. N. Makarov, A. M. Martsinovskii, A. V. Novikov, V. I. Serbin, B. I. Tsirkeľ and V. G. Yur'ev (1977) "Novel Low-Voltage High-Temperature Switching Element for DC-to-AC Conversion. I. Effect of Grid on a Low Voltage Cesium Arc," *Sov. Phys. Tech. Phys.*, **22**, 159-165.
- V. B. Kaplan, A. M. Martsinovskii, A. S. Mustafaev, V. I. Sitnov, A. Ya. Ender, and V. G. Yur'ev (1979) "Spontaneous Current Cutoff in a High-Current Low-Pressure Cesium-Barium Discharge," *Sov. Phys. Tech. Phys.*, **24**, 325-328.
- Yu. M. Konoplev, A. G. Naumovets, and A. G. Fedorus (1972) "Simultaneous Adsorption of Cesium and Barium onto Tungsten and Niobium Crystal Surfaces," *Sov. Phys. Tech. Phys.*, **14**, 273-278.
- I. Langmuir (1923) "Positive Ion Currents in the Positive Column of the Mercury Arc," *General Electric Review*, **23**, 731-735.
- J. D. Levine and E. P. Gyftopoulos (1964a) "Adsorption Physics of Metallic Surfaces Partially Covered by Metallic Particles. I Atom and Ion Desorption Energies," *Surface Science*, **1**, 171-193.
- J. D. Levine and E. P. Gyftopoulos (1964b) "Adsorption Physics of Metallic Surfaces Partially Covered by Metallic Particles. II Desorption Rates of Atoms and Ions," *Surface Science*, **1**, 225-241.
- J. R. Luke and M. S. El-Genk (1994) "A Transient Model of a Cs-Ba Tacitron," *Proceedings of the 11th Symposium on Space Nuclear Power and Propulsion*, AIP Conf. Proc. 301, American Institute of Physics, New York, 1243-1249.
- G. G. Magera and P. R. Davis (1994) "The Coadsorption of Cs and Ba onto the (110) Surface of Mo," *Proceedings of the 11th Symposium on Space Nuclear Power and Propulsion*, AIP Conf. Proc. 301, American Institute of Physics, New York, 1153-1157.
- J. C. Mills and T. M. Van Hagan (1994) "S-PRIME/TI-SNPS Conceptual Design Summary," *Proceedings of the 11th Symposium on Space Nuclear Power and Propulsion*, AIP Conf. Proc. 301, American Institute of Physics, New York, 695-700.
- C. Murray, B. Wernsman, and M. S. El-Genk (1992) "Ignition and Extinguishing Characteristics of a Cs-Ba Tacitron," *Journal of Applied Physics*, **72**, 4556-4565.
- C. S. Murray, M. S. El-Genk, B. R. Wernsman, and V. Z. Kaibyshev (1993) "A Steady-State Model for a Low Pressure Cs-Ba Diode," *Journal of Applied Physics*, **74**, 68-76.

- C. S. Murray (1993) "Experimental and Theoretical Studies of a High Temperature Cesium-Barium Tacitron, With Application to Low Voltage-High Current Inversion" *Ph.D., Dissertation*, Department of Chemical and Nuclear Engineering, University of New Mexico, December 1993.
- B. F. Plybon (1992) An Introduction to Applied Numerical Analysis, PWS-Kent Publishing Co., Boston.
- J. Psarouthakis (1969) "Work Function Variation of Tungsten in Barium Plus Cesium and Strontium Plus Cesium Vapor Environments," *Surface Science*, 17, 316-332.
- A. S. Sedra and K. C. Smith (1987) Microelectronic Circuits, Holt, Rinehart and Winston, Orlando, Florida.
- R. A. Serway (1983) Physics For Scientists and Engineers, Saunders College Publishing, Philadelphia, Chapter 28.
- C. D. Sawyer, P. R. Hill, and D. R. Wilkins (1968) "Multimegawatt Thermionic Reactor Systems for Space Applications," *Proc. 2nd International Conf. on Thermionic Electric Power Generation*, held at Stresa, Italy, 171-182.
- V. A. J. van Lint, T. M. Flanagan, R. E. Leadin, J. A. Maber, and V. G. Rogers (1980) Mechanisms of Radiation Effects in Electronic Materials, Volume 1, John Wiley and Sons, New York.
- B. Wernsman, M. S. El-Genk, and C. S. Murray (1992) "Ignition of Cs-Ba Tacitron During Breakdown and Extinguishing Modes," *Proceedings of the 9th Symposium on Space Nuclear Power and Propulsion*, AIP Conf. Proc. 246, American Institute of Physics, New York, 410-416.
- B. Wernsman, M. S. El-Genk, and V. Z. Kaibyshev (1994) "Operation Characteristics of a Planar Cs-Ba Tacitron," *Proceedings of the 11th Symposium on Space Nuclear Power and Propulsion*, AIP Conf. Proc. 301, American Institute of Physics, New York, 1225-1232.
- B. Wernsman (1994) Private Discussion.

Index

- anomalous Schottky effect, 37, 53, 117-19
- automobile, 1
- Bohm speed, 29, 84
- Boltzman equation, 7
- capacitor time constant, 47, 134
- data acquisition, 18, 19
- desorption
 - of Cs, 9, 35, 90
 - rate, 35
- desorption energy, 33, 36, 94
 - effect on I-V, 92-94, 93
- Einstein A-coefficient, 32, 34
- Euler's method, 39
- filament, 60
- hollow collector, 20, 57, 58
- hysteresis, 10
- knee of I-V curve, 50, 52, 60
 - second knee, 97-99, 98
- Langmuir probes, 21, 22-24, 23, 110-17
- load line, 45
- magnetic field, 26
- nuclear power systems, 1, 5
- plasma wave, 70
- plasmatron, 3
- radiation
 - nuclear, 1
 - photon, 32, 35
 - thermal, 15
- relays, 1
- Richardson equation, 37
- Schottky effect, 37, 53, 117-21
- semiconductor, 1
- sheath, 26, 28, 29
- steady state model, 7, 25, 31, 38, 41
- switching efficiency, 1
- tacitron, 4, 16, 106
 - cesium, 4, 6
 - cesium-barium, 5, 8, 15-17
- thermionic converter, 2
- thermionic emission, 2
- thermoelectric generator, 2
- thyatron, 1, 3
- transistor, 1, 44, 52
- vacuum tubes, 1, 2
- vapor pressure, 107
 - barium, 109
 - cesium, 108
- work function, 3, 27, 99, 117
 - lowering by adsorption, 4, 5, 97