CONF-980412-

RECEIVED

MAY 11 1998

OSTI

Polyplanar Optic Display for Cockpit Application

James Veligdan, Cyrus Biscardi, Calvin Brewster and Leonard DeSanto
 Department of Advanced Technology, Brookhaven National Laboratory, Upton, NY 11973-5000

William Freibott
 Millennium Technology, Chandler, Arizona 85225

ABSTRACT

The Polyplanar Optical Display (POD) is a high contrast display screen being developed for cockpit applications. This display screen is 2 inches thick and has a matte black face which allows for high contrast images. The prototype being developed is a form, fit and functional replacement display for the B-52 aircraft which uses a monochrome ten-inch display.

The new display uses a long lifetime, (10,000 hour), 200 mW green solid-state laser (532 nm) as its optical source. In order to produce real-time video, the laser light is being modulated by a Digital Light Processing (DLP™) chip manufactured by Texas Instruments, Inc. A variable astigmatic focusing system is used to produce a stigmatic image on the viewing face of the POD. In addition to the optical design and speckle reduction, we discuss the electronic interfacing to the DLP™ chip, the opto-mechanical design and viewing angle characteristics.

Keywords: DMD, POD, Laser, Display, Optical, Waveguide

1. DISPLAY REQUIREMENTS

In cockpit applications, it is vitally important for a pilot to view video information even in the presence of direct sunlight. Current B-52 displays utilize CRTs with a phosphor coating on the screen face, and have inherently poor contrast in high ambient light.

This research program has been designed to meet the needs of the B-52 cockpit displays which are presently using a 10 inch monochrome CRT. Since the POD has a black display screen with inherently high contrast, this technology holds promise for superior displays in high ambient light situations. Because of the high light levels within a military cockpit, a brightness of 1200 footlamberts (fl) is sometimes required.¹ In comparison, a civilian display would be adequate providing only 200 fl. To achieve 1200 fl with a CRT, the phosphor must be driven with an intense electron beam which leads to short CRT lifetime and, therefore, high maintenance costs for the aircraft.

A laser driven display is one method to achieve these high brightness requirements while maintaining a long lifetime for the display.

Although lasers can provide an inherently high brightness and high resolution display, there has never been a method to accomplish this with high contrast. Conventional laser projection, like the type employed at laser light shows, can provide a bright image on a flat screen in a tightly controlled dark environment. In addition, a rear projection laser system could be used, however the physical size of such a device is no less bulky than that of a conventional rear projection display. The Polyplanar Optic Display (POD) being described here uses neither front nor rear projection optics. It is an internal projection system where light is projected into the waveguide structure itself. This system can have high brightness and high contrast while having a compact enclosure.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

DTIC QUALITY ASSURED

19980529 046

2. THE POLYPLANAR SCREEN

The Polyplanar screen is a unique waveguide which has been designed to be a light trap for ambient light. Since it absorbs ambient light, it appears black when it is off. In addition to this, it transmits all light incident at the input surface which is within the numerical aperture of the waveguide.

Fiber optic wave guides have been well understood and used for decades. An internal fiber known as the core (refractive index n) is surrounded by a cladding (refractive index $< n$) so that light which enters the fiber within a known acceptance angle is confined within the fiber. This confinement occurs due to total internal reflection. The same process occurs if the internal core is a sheet of glass or plastic rather than a fiber of glass. It is understood that each internal core sheet must be adjacent to a sheet of cladding to ensure total internal reflection. Such a device, when constructed with many sheets or planes of glass or plastic is called a polyplanar optic display. See Figure 1. A polyplanar optic device is analogous to a fiber optic device, however, there are a few very important distinctions.

In a fiber optic, the angular information of the incident light beam is lost as the light exits the fiber. In a planar optic sheet, the angle of the incident light (in the plane of the sheet) is preserved at the exit of the sheet. This is a very important characteristic because one now has the capability to direct light into the entrance of a planar optic sheet and have the same light exit the sheet at a predetermined location. This is crucial to the operation of this polyplanar optic display flat panel screen.

Figure 2 shows a detail of a section of the planar optic screen. Each planar sheet corresponds to exactly one vertical line of resolution. However, in a preferred embodiment, several planar sheets may be used for each vertical line of resolution. Therefore, to attain a VGA display with 480 lines of vertical resolution, the screen must contain at least 480 planar sheets. The laser light exits each planar sheet at the front-frosted face which diffuses the beam to provide an extremely wide viewing angle, like conventional CRTs. The diffusive nature of the screen allows for a very wide viewing angle of approximately 160 degrees. When the laser is off, the screen appears flat black due to the nature of the interlayer cladding which absorbs the ambient light.

One of the first design considerations in the development of the POD was that of the optical core and cladding materials. The core material must have high optical transmittance, be available in the proper thicknesses and be robust enough to be machined into a display. Although many plastics appear to have good optical properties in thin cross sections, their bulk transmission is usually poor. Acrylic, or polymethyl methacrylate (PMMA) is the exception having a high transmittance with a loss factor of as low as 50 db/km.² Although the optical and mechanical properties of PMMA are attractive, it is not presently available in sheets thinner than 0.010 inch, since there has been no need for optical quality PMMA films.

We examined an alternate method of using acrylic films in the waveguide lamina. Master Bond Corp. manufactures a line of ultraviolet curing acrylic liquids which have a viscosity low enough to be sprayed onto a substrate. We chose two materials to use in a spray deposition process. Masterbond UV-15 was chosen as the core material while UV-15-LR1 was used as the cladding. The refractive indices of the core and cladding were $n = 1.52$ and $n = 1.49$, respectively. The cladding had a black dye added to the solution in order to give the POD its black appearance. A robotically controlled spraying machine ensured a uniform thickness for each layer, however, the exact amounts of core solvent were not standardized from layer-to-layer. The feed supply for the core material had to be replenished often and the viscosity was not monitored closely enough which produced variations in thickness from 20 μm to 100 μm . See Figure 3. The cladding layers were a consistent 2 μm thickness, since the cladding feed supply only had to be filled once and the viscosity remained constant for the entire spraying operation. The sprayed screen, when completed, measured 12 in. x 18 in. x 1 1/4 in. Although occasional sheets within the waveguide exhibited good transmission, the majority of the screen had high attenuation to the incident light. This loss was due to an inadequate surface finish of each layer, which is a requirement for total internal reflection. For this process to work, either the feed material must be sprayed at a lower viscosity or the material must be allowed to flow out more than 30 seconds before UV curing takes place.

After a comparison of all available optical materials, glass was chosen as the material to be used for the display screens. A borosilicate glass from Schott Corp., D-263, was used since it was available in sheet thicknesses

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

from 0.001 inch to 0.010 inch. Although this low alkali glass is primarily manufactured for the LCD display industry, its optical properties and refractive index (1.52) make it quite suitable for our applications.

In order to fabricate a 10 inch diagonal display, 480 sheets of glass (.004 inch thick) were each cut to a size of 6 in. x 8 in. These sheets were then assembled such that there was a 0.0002 inch layer of adhesive between the sheets which served as the low index cladding. In addition to acting as a cladding, this optically black layer provides the display with its black face which gives it its high contrast. This laminated assembly of glass and cladding is then diagonally cut on a diamond band saw into two POD screens. In order to easily obtain an optically polished input face, a piece of .008 inch glass is bonded to the input face using an epoxy with a refractive index equal to that of the glass, 1.52.

3. THE LASER

One of the design criteria of this program was to have a long lifetime light source, 10,000 hours, to reduce maintenance costs as well as down time. We, therefore, chose to use a solid-state green laser operating at 532 nm.

In Phase 1 we used a small, frequency doubled Nd:YAG laser operating at 1064 nm doubled to 532 nm wavelength, built by Coherent (Model DPY315m). The Nd:YAG is pumped by a diode laser which is temperature tuned to optimize the performance of the Nd:YAG crystal. This laser produced 100 mW, cw, at a wavelength of 532 nm in the green portion of the spectrum. It measures only 1 in. x 1.5 in. x 3.5 in. and has an output beam diameter of 0.012 in. In addition, it has a small controller that measures 1 in. x 2.5 in. x 3 in. and a 28 Vdc power supply that is 1 in. x 3 in. x 11 in. The laser controller is capable of varying the laser output power from 35 mW to 100 mW. For our application we hard wired the laser to continually output maximum power.

In Phase 2 we wanted to use the most powerful laser available that would be able to fit into the confines of the display chassis. After an exhaustive search we narrowed the selection down to two lasers.

The first laser that we tried to work into our design was manufactured by Laser Power Corporation. This laser first caught our attention because of its high power and small size. It is a frequency doubled Nd:YAG laser operating in the green portion of the spectrum with an output power of 2½ W. The laser head with its heat sink was approximately 10 in. x 6 in. x 4 in. which was within our design dimensions. The heat sinking requirements of the laser head, while demanding, were still within the realm of our design.

The biggest obstacle for us was the size and power consumption of the power supply and control unit, which measured 14 in. x 10 in. x 6 in., and required 115 Vac. We immediately discussed the possibility of doing away with the ac portion of the power supply and using the 28 Vdc bus from the aircraft. The dc requirement for the laser power supply and controller is 18 Vdc but at a current of almost 20 A. Even though this laser was high power and relatively small in size, its power supply was just not small enough for our application at this time.

The second laser that we looked at was manufactured by a small company called CrystaLaser. This laser is also a frequency doubled Nd:YAG laser operating in the green portion of the spectrum with an output power of 200 mW. The laser head measures 1.25 in. x 2 in. x 6.5 in. which fit into our design even better than the Laser Power laser head because of the relaxed heat sinking requirements.

The most appealing factor in this laser was the size and power consumption of the power supply and controller. The power supply and controller measures only 2 in. x 4 in. x 6 in. and draws only 9 W of electrical energy. Originally the laser came with the choice of a 115 Vac/60 cycle or a 220 Vac/50 cycle power supply. Given the choice of 28 Vdc or 155 Vac/400 cycle, the two power sources available in the B-52, the manufacturer was willing to design and fabricate the laser with a supply that ran off the 115 Vac/400 cycle bus. The laser specifications are listed below in Table 1.

Table 1 532 nm, Single Frequency Diode Pumped, Nd: YAG Laser

Wavelength	532 nm
CW output power (mW)	> 200
Transversal mode	TEM ₀₀
TEM ₀₀ beam diameter, typical (mm)(1/e ²)	0.4 mm
TEM ₀₀ beam divergence (mrad)(1/e ²)	<2.2
Stability of output power over 8 hours (%)	3%
Noise(< 10 Hz to > 1 GHz)(% rms)	0.5%
Polarization	Linear 200:1, vertical
Inherent line width	0.1 nm
Operating voltage	115 V @ 400 Hz
Power consumption	Typical 10 W
Expected operating lifetime	> 10,000 hours

We tested the long term power stability of this laser and found it to be well within $\pm 2\%$. This laser employs active feedback to ensure power stability and its output power can vary by 10-20% during the first 30 seconds of operation. Although the output power is controllable, we adjusted the laser to always produce maximum output power and the optical modulator was used to control brightness. Figures 4 and 5 show a side and top view which details how the laser is integrated with the projection optics within the B-52 chassis.

4. SPECKLE ELIMINATION

Although the solid-state laser has many desirable traits such as long lifetime and low power consumption, it has speckle which is characteristic of all lasers. Speckle is a manifestation of the spatial coherence of laser light which makes laser-illuminated objects appear granulated in nature. Furthermore, an observer always sees the speckle in perfect focus whether or not the eye is focused on the object. Another annoying characteristic of speckle is that the speckle pattern moves with the observer's head movement even though the object being viewed does not move. We, therefore, had a goal to eliminate speckle from the display.

A common technique for reducing speckle is with the use of a moving diffuser in the laser beam path. Such a device was built and demonstrated to Brookhaven National Laboratory by Leo Beiser, Inc. The diffuser was found to have approximately 60% efficiency but it only reduced, not eliminated the speckle. We then tried injecting the laser into a glass optical fiber and physically moving the fiber to randomize the phase of the laser. Although the fiber can have an efficiency of over 90%, approximately 1 inch of fiber movement was necessary to remove most of the speckle. We then experimented with a liquid filled light guide. It was determined that a 3 mm diameter light guide with the optimum fluid was able to completely eliminate visible speckle with only .001 inch of movement. This liquid light guide was routed along the periphery of the enclosure as shown in Figure 4 and was only fastened to the chassis in three places which allowed it slight freedom to vibrate. Even aircraft vibrations as small as those from the ventilation system were sufficient to eliminate speckle. This liquid light guide had an efficiency of 60% and we are currently searching for more efficient liquid light guide materials.

5. SYSTEM LAYOUT

This current form-fit-function display differs from previous prototypes in several respects. This unit occupies 160 cubic inches less volume than the Phase 1 display such that it conforms to the B-52 size specification.

This display also has had the laser speckle removed via a liquid light guide. Earlier displays were operationally designed to accept a VCR input and use wall plug power. The current display accepts the B-52 data bus and operated on 400 Hz aircraft power.

The laser in this unit produces 200 mW which is twice the power of the previous version and this display screen has better contrast and surface finish. An improved method of screen construction has resulted in the glass layers being much more uniform. The entire lay up thickness of 480 sheets has a thickness uniformity better than .001 inch where previous versions had variations in thickness of .020 to .030 inches over the width of the 480 layers.

6. SUMMARY

The Phase 2 B-52 display was delivered on time and on budget to Wright-Patterson (U.S.) Air Force Base. We were able to successfully eliminate all visible speckle from the display through the use of a liquid light guide. Although our goal was to double the brightness of previous displays, this prototype resulted in a 15% increase due to the inefficiency of the speckle eliminator. The electronic interface was designed and built to accept the B-52 data bus and 400 Hz aircraft power.

We successfully demonstrated the capability to operate a DMD™ without its color wheel, using custom sync circuits, while illuminating it with a 200 mW solid-state laser to produce real-time video images.

7. ACKNOWLEDGMENTS

This work was sponsored by the U.S. Air Force P.R.A.M. Office. The authors wish to thank Dr. Darrel Hopper and Mr. Fred Meyer for their technical discussions and programmatic guidance as well as Leo Beiser for his contributions to the laser diffuser and fiber couplers. The authors also wish to thank Ms. Marjorie Chaloupka for her untiring efforts in contributing to the success of this program.

8. REFERENCES

1. D.G. Hopper, "Flat Panel Cockpit Display Requirements and Specifications," SPIE, Vol. 2174, Paper 9, International Society for Optical Engineering, 1994.
2. Frederick C. Allard, *Fiber Optics Handbook*, McGraw Hill, 1990, page 1-48.
3. Lars A. Yoder, "The state-of-the-art in projection display: An introduction to the Digital Light Processing (DLP™)," March 1997, Texas Instruments Web Site.
4. L. Beiser and J.T. Veligdan, "Ten inch planar optic display," Proceedings of The International Society for Optical Engineering (SPIE), Vol. 2734, April 1996.
5. Leonard DeSanto and Cyrus Biscardi, "Polyplanar Optical Display Electronics," Proceedings of The International Society for Optical Engineering (SPIE), Vol. 3057, April 1997.

Figure 1 Polyplanar Optic Display (POD)

Figure 2 Principle of Polyplanar Optics

Figure 3 Section of Polyplanar Optic Display Lamina Using Spray Deposition

Figure 4 Right Side View

Figure 5 Top View

1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525

CONF-980412--

199804 ~~199804~~

~~DOE/DP~~ USAF, XF

~~UC-706~~ UC-000, DOE/ER

DOE