DOE / PC94218-10

KINETICS AND MECHANISMS OF NO_x - CHAR REDUCTION

**E. M. SUUBERG (PRINCIPAL INVESTIGATOR)
W.D. LILLY (STAFF)
I. AARNA (Ph.D. STUDENT)**

**DIVISION OF ENGINEERING
BROWN UNIVERSITY
PROVIDENCE, RI 02912
TEL. (401) 863-1420**

**QUARTERLY TECHNICAL PROGRESS REPORT
1 NOVEMBER, 1996 - 31 JANUARY, 1997**

**PREPARED FOR:
U. S. DEPT. OF ENERGY
PITTSBURGH ENERGY TECHNOLOGY CENTER
P.O. BOX 10940
PITTSBURGH, PA 15236**

**DR. RODNEY GEISBRECHT
TECHNICAL PROJECT OFFICER**

"US/DOE Patent Clearance is not required prior to the publication of this document"

1. Introduction

The emission of nitrogen oxides from combustion of coal remains a problem of considerable interest, whether the concern is with acid rain, stratospheric ozone chemistry, or "greenhouse" gases. Whereas earlier the concern was focused mainly on NO (as a primary combustion product) and to a lesser extent NO₂ (since it is mainly a secondary product of combustion, e.g. see ref. 1), in recent years the emissions of N₂O have also captured considerable attention²⁻⁸, particularly in the context of fluidized bed combustion, in which the problem appears to be most acute. The research community has only recently begun to take solid hold on the N₂O problem. This is in part because earlier estimates of the importance of N₂O in combustion processes were clouded by artifacts in sampling which have now been resolved⁹. This project is concerned with the mechanism of reduction of both NO and N₂O by carbons.

It was recognized some years ago that NO formed during fluidized bed coal combustion can be heterogeneously reduced in-situ by the carbonaceous solid intermediates of combustion¹⁰. This has been recently supplemented by the knowledge that heterogeneous reaction with carbon can also play an important role in reducing emissions of N₂O^{2,6,7}, but that the NO-carbon reactions might also contribute to formation of N₂O^{2,8}. The precise role of carbon in N₂O reduction and formation has yet to be established, since in one case the authors of a recent study were compelled to comment that "the basic knowledge of N₂O formation and reduction still has to be improved"⁸. The same can be said of the NO-carbon system.

Interest in the NO- and N₂O-char reactions has been significant in connection with both combustor modeling, as well as in design of post-combustion NO_x control strategies. As in the case of the NO-char reactions, the reaction of N₂O with char is probably too

slow to be of significance in dilute particle phase, short residence time, pulverized coal combustion environments³. The suggestion has been made that the reactions could still be important within the pore structure of the coals, even in a pulverized firing environment¹¹. The possibility of reburning combustion gases in the presence of fresh coal or char also exists.

The above chemical processes are, however, unquestionably important in the lower temperature, slower reaction rate regime of fluidized beds⁸. Of course, it is also the lower temperatures of fluidized bed systems that lead to release of greater amounts of N₂O from these systems, since the N₂O destruction processes have higher activation energies than do formation processes⁷. Therefore, there remains a significant incentive for studies of these reactions associated with developing better control strategies associated with fluidized bed technologies.

Beyond the applicability of this chemistry in fluidized beds, there is interest in developing new post-combustion processes to control NO_x emissions. The possibility of using carbons in the role of catalysts for the catalytic DeNO_x-type processes has been explored¹². Their possible roles as catalyst supports have also been examined^{13,14}. The use of activated carbons for NO removal has been studied^{12,15,16}. And as noted above, the use of carbons, with various kinds of catalytic promoters, has been suggested as holding some promise for lowering the useful temperature range of the reduction processes into that of interest for post-combustion processing^{17,18,19,20}. Interestingly, it was even suggested a few years ago that even spent oil shale, which contains char in a largely limestone matrix, could be an effective material for reduction of NO₂^{21,22}.

2. Experimental

During this quarter, the primary focus of activity continued to be the effects of other non-inert gases on the rates of NO reduction by carbon. Earlier, we had explored the effect of CO, CO₂ and O₂ on this reaction, and found that carbon monoxide and oxygen

enhanced the rate whereas carbon dioxide inhibited the rate. The same general experimental strategy was employed here to further examine the effects of CO on the kinetics of the NO-carbon reaction at different temperatures and using different carbonaceous materials.

A quartz packed bed reactor tube of 4 mm internal diameter and 500 mm overall length was used. Generally, a bed of 20-500 mg (in a predetermined length of 1-50 mm) of carbon or char particles, held in place with quartz wool, was located at the center of the tube. The reactor was heated by an electrical tube furnace and a chromel-alumel thermocouple was placed inside the reactor tube for temperature measurements. During the reactivity measurements, the product gases were continuously analyzed for NO and NO₂ using a chemiluminescence analyzer.

To test the importance of NO reduction by the quartz reactor tube and the quartz wool, blank runs were conducted by passing NO mixtures (not containing CO) over the bed materials at different temperatures. The results showed no significant NO reduction (<1%, invariant with temperature). The same was not true when ordinary glass wool was used in the reactor. In this case, a few percent NO reduction was observed.

The CO-NO reaction may be catalyzed by char and also by the quartz tube²⁶. The quartz catalyzed NO reduction by CO might be important process in our system, because the contact times for the reactants with quartz are much longer than the contact times with char. Johnsson et al.²⁵ observed that the relative influence of NO-CO reaction catalyzed by quartz to the NO-CO reaction catalyzed by coal char is typically 10% to 50%, depending on reaction conditions. The CO concentrations in his experiments varied in the range from 2500 ppm and 3%, in our experiments we were concerned with much lower CO concentrations, typically below 200 ppm. To test the importance of NO/CO reduction by the quartz reactor tube and the quartz wool, blank runs were conducted by passing NO/CO (100 ppm NO and 300 ppm CO) mixtures over the bed materials at different

temperatures. The tests showed no significant NO reduction at temperatures below 1000_C.

The reactor containing the carbon bed was outgassed prior to each run by a one hour vacuum pumping at room temperature. This was followed by thermal surface cleaning of the carbon (at 1000_C for 1-2 hours in He) to remove surface oxides. Nitric oxide/helium mixtures of the desired concentration levels were prepared using a KIN-TEK precision calibration system. The desired NO/He or NO/CO/He mixtures (10-300 ppm of NO in He or He/CO) were obtained by controlling the flow rate of helium (usually 100 ml/min) or He/CO, and both the absolute temperature of the permeation membrane and the NO partial pressure in the KIN-TEK calibration system. In experiments in which the effect of CO concentration was explored, the desired CO concentration (50-500 ppm of CO in NO/He mixture) was obtained by preparing a desired CO/He mixture and then controlling the flow rate of the CO/He mixture added to the flowing NO/He mixture.

Specific surface areas of char samples were determined by the N₂ BET method at -196_C using an Autosorb-1 instrument (Quantachrome Co.). Prior to surface area analysis, all samples were outgassed in vacuum at 400_C for at least 4 hours.

The carbonaceous solids studied were resin char, graphite, pulverized coal combustion fly-ash and Wyodak coal pyrolysis char. The resin char samples (180-290μm particle size) were derived from phenol-formaldehyde resins made in-house. The coal char (150-212μm) was also prepared in-house from the Wyodak sample of the Argonne Premium Coal Sample Program. The chars were prepared by a two hour pyrolysis, in inert gas, at a temperature of approximately 1000_C. The graphite (180-290μm) was prepared from graphite rods. None of these samples was treated any further, except for surface cleaning.

3. The Kinetics of NO Reduction by Carbon in the Presence of Carbon Monoxide

3.1 Introduction

One of the most important environmental problems is the minimization of pollutants from industrial boilers and from vehicle engines. The combustion products typically contain CO, CO₂, H₂O, NO_x, and sometimes SO₂. All of these gases affect how the flue gas cleanup processes can be carried out. To develop more efficient cleanup processes the effects of coexisting gases on the proposed processes must be considered. The presence of other gases can significantly modify the reaction scheme.

The purpose of our study is to determine the effects of coexisting gases on NO reduction by carbons. There have been only a few systematic studies concerning these effects. Generally, O₂^{19,35} and CO^{27,36,37} appear to enhance the rate of reduction of NO, whereas the reaction has been reported to be inhibited by water vapor³⁶, at least in the high temperature region. In the 8th quarterly report we showed that the presence of CO₂ inhibited the reduction of NO by graphite. In the last quarter we reported that the reduction of NO was significantly enhanced in the presence of oxygen. During this quarter, the effect of low concentrations of CO on reduction of NO was further investigated.

The presence of CO has been noted to have significant effect on NO reduction. In the high temperature regime, added CO has been noted to enhance the NO-carbon reaction rate^{32,36}. It has been hypothesized^{27,36} that CO can assist by removing oxides from the surface of the carbon, by the well-known process that may be represented as:

where C(O) represents a surface carbon oxide, and C* represents a “free” site, active towards NO reduction. The effect of CO has been seen to decrease with increasing temperature, in the high temperature regime³⁶. This would be expected, since the desorption processes involving the surface oxides themselves would be expected to be promoted by higher temperatures. Recently, however, there has been serious questioning of whether the above reaction of CO with surface oxides is of any significance (in the O₂ gasification system)³⁸.

There is the possibility that CO may play another mechanistic role as well, since it is well established, *vide infra*, that there are surface-catalyzed routes that involve no surface carbon oxides:

The role of carbon as a catalyst for this reaction has yet to be clarified. It should be noted that there are numerous reports of surface catalyzed reactions between NO and CO (and H₂), thought to be catalyzed by char^{27,46}, iron oxide and transition metal oxides^{39,47}, carbon supported alkali^{40,48}, limestone⁴¹, alumina⁴², and quartz⁴³. The fact that such possibilities exist must be accounted for in careful studies of the effect of added CO.

The fact that CO enhances the rate of reduction has some interesting consequences for reduction of “pure” NO by carbon, inasmuch as CO is a product of the reaction. It is now believed that reactions with CO might in some situations cloud the interpretation of nominally “pure” NO kinetic studies. This issue will be discussed in the next section.

3.2 Apparent Order for NO Reduction in Fixed Bed Reactors

The majority of literature on the kinetics of the NO-carbon reaction supports the view that the reaction is very nearly first order with respect to NO, see Table 1. Also our TGA results support first-order kinetics, see Figure 1; the slope of curve determines the reaction order. There are, however, enough exceptions to this conclusion that the question of true order must still be regarded as unresolved. There have been several studies that firmly claim fractional order^{23,24,25,37,44}, see Table 2. Moreover, there is a suggestion that the order may depend upon NO concentration³⁷.

An important aspect of this problem has been noted above, in connection with the fact that CO is both a product of NO reduction, and a reactant. There are sometimes large differences between the CO/CO₂ product ratios reported by different workers. A summary of data from the literature is shown in Figure 2. Generally, the ratio of CO to CO₂ has been observed to start out at values less than unity at low temperatures, and to increase

monotonically with temperature^{24,26,28,32,45}, just as in the case of carbon gasification by oxygen. Figure 2 illustrates that there has been a wide range of behavior reported, and there is no clear explanation for the differences at present. It has also been noted that the CO/CO₂ ratio is a decreasing function of residence time, in fixed bed reactor work⁴⁴. This implies sequential reaction of CO, as expected from the above observation that the addition of CO generally enhances the reduction of NO on carbons.

The above has led to concerns about possible misinterpretation of fixed bed results, in which CO that is a product in the early part of the bed, reacts later in the bed with NO. This was the basis of a recent model which predicted precisely this behavior⁴⁹. The model was based upon the still debated reduction of surface oxides by CO (reaction (R1), above), and did not include the surface catalyzed reaction (R2). A revised version of the model will be presented shortly. Such a model requires considering explicitly the kinetics of NO reduction by CO. The role of CO in the reaction processes is still not clearly defined. An empirical approach must be adopted at this time.

3.3 Determination of apparent reaction orders from fixed bed reactor experiments

The integral method was used in data analysis, where the measured fractional conversions and initial concentrations were used in tests of proposed mathematical formulation of the reaction rate function. The proposed rate expression has the form

$$r = k_1 \cdot C_{NO}^n \quad (1)$$

Using the design equation for a fixed bed reactor and the assumed rate expression we get

$$\tau = \frac{V_R \cdot \epsilon}{V_o} = C_{NO,o} \int_0^{X_{NO}} \frac{dX_{NO}}{-r_{NO}} = C_{NO,o} \int_0^{X_{NO}} \frac{dX_{NO}}{k_1 C_{NO,o}^n \cdot (1 - X_{NO})^n} \quad (2)$$

where τ is the residence time, V_R is the reactor volume, ϵ is a bed void fraction, V_o is a volumetric flow rate, $C_{NO,o}$ is the initial concentration of nitric oxide, X_{NO} is the fractional conversion of NO, r_{NO} is the reaction rate, n is the reaction order with respect

to NO (n_1) and k_1 is the reaction rate constant. Integration of Eq. 2. gives a relation between the initial concentration and fractional conversion of NO

$$C_{NO,o}^{n-1} = \frac{1}{(1-n) \cdot k \cdot \tau} [1 - (1 - X_{NO})^{1-n}] \quad (3)$$

By taking the logarithm of both sides we get

$$\ln[C_{NO,o}] = \frac{1}{(1-n)} \ln[(1-n) \cdot k \cdot \tau] - \frac{1}{(1-n)} \ln[1 - (1 - X_{NO})^{1-n}] \quad (4)$$

A plot of $\ln[1 - (1 - X_{NO})^{1-n}]$ vs. $\ln[C_{NO,o}]$ should give a straight line and from the slope we can determine the reaction order

$$n = 1 + \text{Slope} \quad (5)$$

Reaction orders for NO reduction, using different carbon materials have been determined in packed bed reactors, and are given in Table 2. From our data, it has been concluded that the reaction order decreases with reactivity; for graphite, the reaction order is close to unity, whereas for Wyodak coal char reaction order is 0.36. The literature data also indicate that the reaction order for coal char is approximately 0.5. It is believed that the correlation with reactivity is a consequence of the higher rate of generation of CO by the more reactive materials, see Table 2.

3.4 The Kinetics of NO/CO Reduction by Carbon

3.4.1 Reaction orders

It has been suggested based upon experiments in which CO was added in the feed gas, that the surface-catalyzed reduction of NO by CO ranges from 0.18 to 0.43 order in NO and 0.38 to 0.53 in CO, for a CO concentration range measured in percent²⁵, see Table 3. On the other hand, it was implied that the CO dependence approaches zero order at concentration levels of 700 ppm or less²⁵. This latter range may be more appropriate for experiments involving CO that is present only due to NO reduction. A weak dependence on CO concentration was also noted in one other case, though in that study a stronger dependence was noted with another char (the comparison in this latter case was

complicated by the fact that the experiments were not performed at the same temperature, and it was implied that the CO plays a more important role at lower temperatures)²⁴.

In order to resolve the apparent inconsistencies concerning reaction order with respect to NO, experiments have recently been performed aimed at explaining how the nature of the kinetic experiments can lead to apparent orders different from unity. When tested at 800_C, the graphite gave an apparent reaction order of very nearly unity (0.95), for NO partial pressures ranging from 20 to 100 ppm (see Figure 3). A first order reaction should of course show no dependence of NO conversion on NO inlet concentration. A deviation from first order behavior was only observed at very low NO concentration. It is observed that when NO pressure gets very low, that the time to pseudo-steady state becomes much longer. It might be that pseudo-steady-state was not achieved during this particular experiment.

The results for a series of experiments in which 275 ppm CO and 255 ppm CO₂ were added to the feed are also shown in Figure 3. The apparent NO reaction order from the experiments with added CO is 0.56. Variation of the CO level from 50 to 150 ppm showed the reaction to be near zero order in CO concentration. The conclusions however support the view that even very low levels of CO can affect observed reaction order and kinetic constants significantly.

Thus low levels of CO can have a dramatic effect on the rate of the NO reduction process. Artifacts may be expected in experiments in which there is extensive contact in the reactor between the product CO and the primary reactants. This does not mean that near-first order behavior cannot be expected from a fixed bed reactor (Figure 3 shows it is possible for graphite), but that this type of device might be particularly prone to artifacts when operated such that there are significant levels of CO achieved in the bed (i.e., with reactive materials). This could in some cases lead to an erroneous conclusion of fractional order kinetics for the NO-carbon reaction itself, as noted in Figure 3.

3.4.2 Temperature Dependence of the Char Catalyzed NO/CO Reaction

We see strong support for the position that reports of fractional order kinetics with respect to NO partial pressure may be artifacts of performing the reaction in CO-containing atmospheres. The CO itself may be generated as a product of the reaction of NO with carbon:

This reaction may be followed in a packed bed (in which products contact the reactive medium further) by:

The reaction (R2) is surface catalyzed. In this case, the largest surface is provided by the carbon in the reactor itself. The reaction rate expression should in this case contain two terms

$$r = k_1 \cdot P_{\text{NO}}^n + k_2 \cdot P_{\text{NO}}^m \cdot P_{\text{CO}}^l \quad (6)$$

where k_1 and k_2 are reaction rate constants for reactions (R3) and (R2), respectively, and n , m and l are reaction orders with respect to NO, NO and CO, respectively. The apparent order with respect to NO may easily be fractional, in such a case. The reason that the effect of product CO is not seen in the experiments with graphite might be that the graphite is very unreactive, and the partial pressure of the CO product would be quite low throughout the packed bed.

During this quarter the main focus was on determining the temperature dependence of NO/CO-carbon reaction. This basically allows us to determine the rate constant k_2 in Equation 6. Previously we have determined values for k_1 , which are different in different temperature regimes. The value of the parameter n has been concluded to be near unity and with the limited data available at present it appears as though l can be taken as close to zero under most conditions. We evaluated the reaction order m by subtracting the "pure" NO-graphite reaction rate constants from the NO/CO-graphite reaction rate constants at different NO partial pressures and then conducting the

reaction order analysis using Equation 4. It turns out using data from Figure 3 that the NO pressure dependence during the NO/CO-graphite reaction is weak, $m=0.13$. Thus the only undetermined constant in Equation 6 is k_2 .

Figure 4 shows the kinetics of the NO-Wyodak coal char and the kinetics of NO reduction on the same char, in the presence of a significant amount of added CO. The reaction rate constant is expressed on a mass of carbon reactant basis, in both cases. In the case of the work on the effect of CO, the mixture contained 70 ppm of NO in 400 ppm CO, balance helium. Clearly, even this small amount of CO modifies the NO reduction kinetics. The major difference is that there is no clear "break" point in the kinetics of the NO/CO-Wyodak coal char reaction. The activation energy of the NO/CO-Wyodak coal char reaction is between those for the high and low temperature regimes of the NO-Wyodak coal char reaction in the absence of CO.

Since Equation 6 implies that there are two reactions occurring simultaneously, in order to get the actual kinetic data for the Wyodak char catalyzed NO/CO reaction, it is necessary to subtract the "pure" NO-Wyodak coal char reaction rate constants from NO/CO-Wyodak coal char reaction rate constants. Figure 5 shows the result of the subtraction as an Arrhenius plot giving an activation energy of 132 kJ/mol.

Figure 5 shows that the highest temperature point does not fit the trend obtained from the remaining points. There are two possibilities as to why this point is not on the curve. First, there might be a mass transfer problem at high temperatures. If the reaction is surface catalyzed, the CO and NO must be able to reach the surfaces of the char. The pure NO reaction shows no evidence of a mass transfer limitation, but it is a slower reaction. The leveling off of reaction rate in the NO/CO case could suggest depletion of CO within the particle.

Another reason that the high temperature point could fail to fit the trend is that the concentration of CO as a product of the NO-carbon reaction might become high enough so as to affect the NO-carbon reaction kinetics to the same degree as does the added CO.

This latter explanation does not appear to be as likely, since in the case of this and the other systems to be presented later there did not appear to be strong evidence of autocatalysis in the "pure" NO case. The autocatalysis must be present, however, in light of the results on apparent order in Table 2.

The exit concentrations of CO in the pure NO reaction situations have not yet been measured. The exit CO concentration can be calculated from $[CO] = [x/(2+x)]f [NO]_0$, where x is the CO to CO₂ molar ratio, f is the conversion of NO and $[NO]_0$ is the inlet concentration of NO. If an estimate of CO to CO₂ ratio of about 3 is taken on the basis of Figure 2, then $[CO]$ is at least of order 20 ppm. Of course the measured product ratios from a fixed bed reactor would already be expected to be influenced somewhat by the occurrence of reaction (R2), and the initial value of x might be somewhat higher, approaching as a limit $f[NO]_0$.

Similar experiments as shown on Figure 4 for Wyodak coal char were performed for graphite and resin char. The results are shown in Figure 7. Again the NO-carbon reaction rate constants were subtracted from NO/CO-carbon reaction rate constants and the results on N₂ BET surface area basis are shown on Figure 6. Interestingly, graphite and Wyodak coal char show similar reactivities on a surface area basis, whereas they have very different porous structures. The NO/CO-resin char reaction has much lower activation energy (54 kJ/mol) and also the scatter of data is much larger. These data imply a possible role of mass transfer, in this case. There are three experimental facts that support why the NO/CO-resin char reaction might be mass transfer limited. At low temperatures the resin char reactivities are quite close to those of Wyodak coal char. At temperatures above 650°C the reaction rate is becoming much lower, possibly because it is mass transfer limited. Second, the porous structure of Wyodak coal char and resin char are different. Third and most important, most of the resin char reactivities were measured at higher temperatures. At high temperatures mass transfer role becomes more important.

To get a better understanding of the differences in porous structure of resin char and Wyodak coal char, N₂ adsorption experiments were performed with those materials. From adsorption isotherms the pore size distribution was calculated using the method proposed by Barrett, Joyner and Halenda⁵⁰, see Figure 8. The N₂ BET surface areas of resin char and Wyodak coal char are 51 m²/g and 124 m²/g, respectively. Figure 8 tells us that the difference in surface area comes only from mesopores, the micropore and macropore surface areas are very similar. This led us believe that the access of NO or CO to micropores may be limited during the NO/CO-carbon reaction in the case of the resin char. There are no mesopores to feed micropores, in that case. Therefore we believe that reaction might become mass transfer limited at high temperatures. To clarify the role of mass transfer, an effectiveness factor analysis is needed for the NO/CO-carbon reaction. It is assumed that the NO/CO-carbon reaction occurs over the entire surface area, except, when reaction is mass transfer limited. A suitable model of transport in two different ranges of pore sizes is needed. A preliminary analysis with a single average pore size is shown in Appendix A. It is inconclusive, in that it does not clearly identify a difference in the two samples. A better model is clearly needed.

3.5 Model for NO-Carbon Reaction in the Presence of CO

A simple model for NO-carbon reaction in the presence of CO was proposed in previous section (Eq. 6):

$$r = k_1 \cdot P_{NO}^n + k_2 \cdot P_{NO}^m \cdot P_{CO}^l \quad (6)$$

All constants in this equation have been experimentally determined and the validity of this equation can be evaluated against other experimental data. The following is the list of constants earlier derived:

$$n = 1$$

$$m = 0.13$$

$$l = 0.04$$

Other constants are needed as well. The k_1 were obtained earlier:

For graphite (transition temperature 800_C):

$$k_1 = 6.2 \cdot 10^{15} \cdot \exp\left[-\frac{40909}{T}\right] \text{ in the high temperature region}$$

$$k_1 = 433 \cdot \exp\left[-\frac{9321}{T}\right] \text{ in the low temperature region}$$

The value of k_2 is obtained from Figure 6:

$$k_2 = 6.91 \cdot 10^6 \cdot \exp\left[-\frac{16956}{T}\right]$$

For Wyodak coal char (transition temperature 625_C):

$$k_1 = 6.5 \cdot 10^8 \cdot \exp\left[-\frac{22754}{T}\right] \text{ in the high temperature region}$$

$$k_1 = 25 \cdot \exp\left[-\frac{7398}{T}\right] \text{ in the low temperature region}$$

$$k_2 = 1.27 \cdot 10^6 \cdot \exp\left[-\frac{15875}{T}\right]$$

For resin char (transition temperature 725_C):

$$k_1 = 8.27 \cdot 10^6 \cdot \exp\left[-\frac{21463}{T}\right] \text{ in the high temperature region}$$

$$k_1 = 14.3 \cdot \exp\left[-\frac{8161}{T}\right] \text{ in the low temperature region}$$

$$k_2 = 17.9 \cdot \exp\left[-\frac{6513}{T}\right]$$

all reaction rate constants are given in units of $\text{g}_{\text{NO}}/\text{m}^2/\text{hr}/\text{atm-NO}$.

To verify the accuracy of this model, we first tried to predict the overall reaction order with respect to NO when CO was present. The model calculations were performed at 800_C with graphite, where NO concentration was varied between 20 and 100 ppm, and added CO concentration was 200 ppm. Figure 9 shows a plot of $\ln(-r)$ vs. $\ln P_{\text{NO}}$ for different values of l . The slope of those curves gives the apparent overall reaction order. The overall reaction order varied between 0.85 and 0.57 when n values varied between 0 and 0.3. The value 0.57 is very close to the experimentally determined value (0.56), but the l value used to get this reaction order was 0.3, not 0.04 as earlier experimentally found. This suggests that the CO concentration dependence is weak, but not as weak as we proposed earlier. Sensitivity of apparent order to the value of l is great, and the

experimental determination of order had some scatter. Thus it is difficult to assign a value to l with great confidence, except to say that it must be low.

Next the temperature dependence of the overall reaction order was explored. For resin char we experimentally found that the reaction order increased slightly with temperature, see Table 2. The model calculations were performed with graphite, where NO concentration was varied between 20 and 100 ppm, and the added CO concentration was 200 ppm. The model calculations show that the temperature dependence of the apparent reaction order is stronger than expected and that the curve goes through a minimum at around the transition temperature, see Figure 10. This kind of behavior is expected because the NO-graphite and NO/CO-graphite reaction rates are similar in the temperature range tested and also because the activation energy of the NO/CO-graphite reaction is between those for the high and low temperature regimes of the NO-graphite reaction in the absence of CO.

During the above exploration of temperature dependence, we held the CO concentration constant, but as we know from Figure 2, CO concentration increases with temperature. To get an idea of how great the variation in the apparent reaction order is when CO concentration is varied, other model tests were performed at 800_C where the CO and NO concentrations were varied between 20 and 200 ppm, and 20 and 100 ppm, respectively. Obviously, there is no CO dependence when $l = 0$, see Figure 10. Comparison of Figures 10 and 11 shows that even at $l = 0.3$ the change in reaction order due to CO concentration is smaller than the change due to temperature. So, the temperature effect dominates the variation in order.

At the same time, it is seen that as CO concentration decreases, the apparent order increases. This must be the case, since the fixed bed reactor results with no added CO gave near unity apparent order. It is unclear, in the case of a very unreactive material with respect to the NO- carbon reaction, whether CO depletion in the bed will dictate the

dominance of the first term of Equation 6, and drive the apparent order even closer to unity. Measurements of the CO/CO₂ ratio will reveal whether this is the case.

Similar model calculations, to predict the overall apparent reaction order with respect to NO, were performed for the other carbonaceous materials. The model calculations were performed at 700_C and at 800_C with Wyodak coal char and resin char, respectively. Again, the NO concentration was varied between 20 and 100 ppm, and added CO concentration was 200 ppm. In Figure 12 and 13 we have plotted $\ln(-r)$ vs. $\ln P_{NO}$ for Wyodak coal char and resin char, respectively, using different values for l . The reaction orders for those chars are almost the same at the same l values. The overall reaction orders for Wyodak coal char are much higher than expected based on experimental results (compare Figure 12 and Table 2). The expected reaction order for resin char (0.67) is close to the predicted value (0.74) when $l = 0.3$. Thus the current model is able to roughly predict the correct reaction orders for two chars with different reactivities but fails for a third. The model fails to predict that the reaction order decreases with the reactivity. This may be compensated for by decreasing the value of n with reactivity. It seems that the value of n is close to unity for graphite and resin char, but to achieve an apparent reaction order of 0.36 for Wyodak coal char when $l = 0.3$ the value of n should be 0.7. This can be checked by experiments in the TGA, in which the role of the NO/CO reaction is minimized.

Work with the model for NO-carbon reaction in the presence of CO will continue during the next quarter.

4. Plans for the Upcoming Quarter

Experiments will be continued, using the packed bed reactor and TGA/FTIR system. The mechanistic aspects of NO/O₂ carbon reaction will be studied using TGA/FTIR system. The effects of O₂ on NO-carbon reaction at temperatures below 400_C will be studied in a fixed bed reactor. Then attention will be turned to the aspects

of the thermal annealing process in Wyodak coal char. Work with the model for the NO-carbon reaction in the presence of CO will continue during the next quarter. In addition, the mechanistic implications of the results obtained to date will be examined.

5. References

1. Johnson, G.M., Smith, M.Y., Mulcahy, M., 17th Symp. (Int.) on Comb., Combustion Institute, 647 (1979).
2. deSoete, G.G. 23rd Symp. (Int.) on Combustion, The Combustion Institute, 1257 (1990).
3. Aho, M., Rantanen, J., and Linna, V., Fuel, 69, 957 (1990).
4. Aho, M. and Rantanen, J., Fuel, 68, 586 (1989).
5. Houser, T., McCarville, M., and Zhuo-Ying, G., Fuel, 67, 642 (1988).
6. Wojtowicz, M., Pels, J., Moulijn, J., Proc. 1991 Int. Conf. Coal Sci., p 452, Butterworth, Oxford, 1991.
7. Wojtowicz, M., Oude Lohuis, J., Tromp, P., Moulijn, J., Int. Conf. Fluid. Bed Comb., 1013, 1991.
8. Åmand, L., Leckner, B., and Andersson, S., Energy and Fuels, 5, 815 (1991).
9. Muzio, L. and Kramlich, J., Geophys. Res. Lett., 15, 1369 (1988).
10. Pereira, F., Beer, J., Gibbs, B. Hedley, A., 15th Symp. (Int.) on Comb., Combustion Institute, 1149 (1975).
11. Hahn, W. and Shadman, F., Comb. Sci. and Tech., 30, 89 (1983).
12. Hjalmarsson, A.M., NOx Control Technologies for Coal Combustion, IEA Coal Res. Rept. IEACR/24, 1990.
13. Inui, T., Otowa, T., and Takegami, Y., I & EC Prod. Res. Dev., 21, 56 (1982).
14. Stegenga, S., Mierop, A., deVries, C., Kapteijn, F., and Moulijn, J., Proc. 19th Biennial Conf. on Carbon, p. 74, The American Carbon Society, 1989.
15. Mochida, I., Ogaki, M., Fujitsu, H., Komatsubara, Y., and Ida, S., Fuel, 64, 1054 (1985).
16. Richter, E., Kleinschmidt, R., Pilarczyk, E., Knoblauch, K., and Juntgen, H., Thermoch. Acta, 85, 311 (1985).
17. Lai, C.-K. S., Peters, W. A. and Longwell, J. P., Energy & Fuels, 2, 586(1988).
18. Illán-Gómez, M., Linares-Solano, A., Salinas-Martinez, C., Calo, J.M., Energy and Fuels, 7, 146 (1993).
19. Yamashita, H., Tomita, A., Yamada, H., Kyotani, T., and Radovic, L., Energy and Fuels, 7, 85 (1993).
20. Okuhara, T. and Tanaka, K., J. Chem. Soc., Faraday Trans.-1, 82, 3657 (1986).
21. Taylor, R.W. and Morris, C.J., ACS Div. Fuel Chem. Prepr., 29(3), 277 (1984).
22. Personal Communication, Prof. I. Opik, May, 1992.
23. Schuler, J., Baumann, H., and Klein, J. 1987 Int. Conf. Coal. Sci., p. 857, Elsevier, (1987).

24. Rodriguez-Mirasol, J., Ooms, A.C., Kapteijn, F., Moulijn, J.A., Combustion and Flame, 99, 499 (1994).
25. Johnsson, J.E., and Dam-Johansen, K. 11th International Conference on Fluidized Bed Combustion. p. 1389, New York, (1991).
26. Berger, A., and Rotzoll, G., Fuel, 74, 452 (1995).
27. Chan, L. K., Sarofim, A. F. and Beer, J. M., Combustion and Flame, 52, 37/45 (1983).
28. Furusawa, T., Kunii, D., Osuma, A. and Yamada, N., Kogaku Kogaku, 1978, 6, 562, or International Chemical Engineering, 20, 239(1980).
29. Suuberg, E. M., Teng H. and Calo, J. M., Energy and Fuels, 6, 398 (1992).
30. Suuberg, E.M., Combust. Flame 50, 243 (1985).
31. Song, Y.H., Beer, J.M., and Sarofim, A.F., Comb. Sci. and Tech., 25, 237 (1981).
32. Tian, Y., Ph.D. Thesis, Essen, 1993.
33. Edwards, H.W., AIChE Symp. Ser. No. 126, Vol. 68, 91 (1972).
34. Bedjai, G., Orbach, H.K., and Reisenfeld, F.C., Ind. Eng. and Chem, 50, 1165, 1958.
35. Suzuki, T., Kyotani, T., and Tomita, A., Ind. Eng. Chem. Res., 33, 2840, (1994).
36. Levy, J., Chan, L., Sarofim, A.F., Beér, J.M., '18th Symp. (INT.) on Comb.', The Combustion Institute, 1981, 111.
37. Johnsson, J.E., Fuel, 73, 1398, (1994).
38. Brown, T.C. and Haynes, B.S., Energy and Fuels, 1992, 6, 154.
39. Shelef, M., Otto, K., and Gandhi, H., J. Catalysis, 1968, 12, 361.
40. Kapteijn, F., Mierop, A., Abbel, G., and Moulijn, J., Proc. Carbon 84, 1984, p. 60.
41. Tsujimura, M., Furusawa, T., and Kunii, D., J. Chem. Eng. Japan, 1983, 16, 132.
42. deSoete, G., VDI-Berichte, 1983, 489, 171.
43. Wittler, W., Schütte, K., Rotzoll, G., and Schügerl, K., Fuel, 1988, 67, 438.
44. Schuler, J., Baumann, H. and Klein, J., Erdol und Kohle-Erdgas, 1988, 41, 296.
45. Suuberg, E. M., Teng H. and Calo, J. M., '23rd Symp. (Int.) on Comb.', Combustion Institute, 1991, p.1199.
46. Furusawa, T., Tsunoda, M., Tsujimura, M., and Adschiri, T. Fuel, 1985, 64, 1306.
47. Shelef, M. and Otto, K., J. Coll. Int. Sci., , 1969, 31, 73.
48. Kapteijn, F., Mierop, A., Abbel, G., and Moulijn, J.A., J. Chem. Soc. Comm., 1984, 1085.
49. Calo, J.M. and Suuberg, E.M., 'Proceedings- 22nd Biennial Conf. on Carbon', Amer. Carbon Society, 1995, p. 618.
50. Barrett, E.P., Joyner, L.G., and Halenda, P.P., J. Amer. Chem. Soc., 73, 373, 1951.

Table 1. Reaction orders for NO-char reaction.

Materials	Reaction order	Activation energy	Reference
		[kJ/mol]	
Resin char	1.0 (500-750_C)	180 (h) 63-88 (l)	[29] (TGA)
Montana lignite coal char	1.0	168(h) 62 (l)	[27]
Graphite	1.0	239 (h)	[27]
Taiheiyo coal char	1.0	245 (h) 68 (l)	[28]
Activated carbon	1.0	181 (h) 63.5 (l)	[28]
Montana lignite coal char	1.0	137 (h)	[31]
High-volatile bituminous coal c.	1.0	167.7 (h)	[32]
Demineralized high-volatile bituminous coal c.	1.0	151.8 (h)	[32]
Low-volatile bituminous coal c.	1.0	154 (h)	[32]
Demineralized low-volatile bituminous coal c.	1.0	138.1 (h)	[32]
Graphon	1.0	86.6 (h)	[33]
Resin char	1.0 (600_C)	135 (h) 40 (l)	this study (TGA)

Table 2. Reaction orders for NO-char reaction determined in packed bed reactors.

Materials	Reaction order	Activation energy	Relative reactivities at 800_C	Reference
		[kJ/mol]	[gNO/gC•hr•atm]	
Wyodak coal char	0.36 (650_C)	198.1 (h) 38.1 (l)	450*	this study
Resin char	0.77 (550_C) 0.73 (750_C) 0.67 (800_C)	168.0 (h) 26.9 (l)	3.5	this study
Graphite	0.95 (800_C)	185-221(h) 53-79 (l)	0.7	this study
Coconut char	0.5 (650_C)	129 (h) 35 (l)	75 (tga result)	this study
Lignite coal char	0.23	116 (h)	1810	[24]
Subbituminous coal char	0.22	111 (h)	520	[24]
High-volatile bituminous coal c.	0.43	167 (h)	150	[24]
Anthracite char	0.36	181 (h)	100	[24]
Bituminous coal char	0.58	184.6 (h)	300	[25], [37]
Brown coal char	0.52	184.6 (h)	370	[25], [37]
Petroleum coke	0.49	196.2 (h)	65	[25], [37]
High-volatile bituminous coal c.	0.6	122 (h) 63 (l)	1210*	[23], [44]

* - extrapolated

Table 3. Reaction orders for NO/CO-char reaction

Material	Reaction order		Initial concentration		Reference
	NO	CO	NO,ppm	CO	
Graphite	0.56	0.04	10-150	20-200 ppm	this study
Bituminous coal char	0.43	0.38	100-800	0-3%	[25]
Brown coal char	0.39	0.53	100-800	0-3%	[25]
Petroleum coke	0.18	0.53	100-800	0-3%	[25]
Coal char	_0.5	_0	100-800	<700 ppm	[25]
Bed material	0.25	0.7	100-800	0-3%	[25]
Quartz	1	1	650-1000	0.5-5%	[26]

Figure 1. Reaction rate of resin char in the TGA, showing first order rate (T= 600_C).

Figure 2. A summary of CO/CO₂ product ratios for the NO-carbon reaction. Open diamonds-resin char, reacted with 10.1 kPa NO₂₆; closed diamonds-resin char, reacted with 2.02 kPa NO₂₆; closed circles- activated carbon³⁴; open circles- coal char²⁸; triangles- graphon³³; closed squares- graphite³²; open squares- activated carbon³².

Figure 3. The effect of CO on the apparent order of the NO-graphite reaction. All tests were performed at 800_C in a fixed bed reactor. Open diamonds- results in the absence of added CO; closed squares- results in the presence of 273 ppm of CO.

Figure 4. The effect of CO on the NO reduction by Wyodak coal char. Closed circles- results in the absence of added CO; closed squares- results in the presence of 400 ppm of CO.

Figure 5. The difference between the rate constants (on mass of carbon basis) for NO/CO- Wyodak coal char and NO- Wyodak coal char reactions.

Figure 6. The effect of CO on the NO reduction by carbons. The rate constants are expressed on a surface area basis.

Figure 7. The difference between the rate constants (on a surface area basis) for NO/CO- carbon and NO- carbon reactions. Closed circles- graphite; closed diamonds- Wyodak coal char; closed squares- resin char.

Figure 8. The pore size distribution calculated using the method proposed by Barrett, Joyner and Halenda (BJH). Open diamonds- Wyodak coal char; closed squares- resin char.

Figure 9. The determination of the overall apparent reaction order with respect to NO using the proposed model. The model calculations were performed at 800_C for graphite, where NO concentration was varied between 20 and 100 ppm, and the added CO concentration was 200 ppm. Open circles- $l=0$; closed squares- $l=0.05$; closed circles- $l=0.1$; closed diamonds: $l=0.2$, closed triangles- $l=0.3$.

Figure 10. The determination of temperature dependence of the apparent reaction order with respect to NO using the proposed model. The model calculations were performed for graphite, where NO concentration was varied between 20 and 100 ppm, and added CO concentration was 200 ppm. Open circles- $l=0$; closed squares- $l=0.05$; closed circles- $l=0.1$; closed diamonds: $l=0.2$, closed triangles- $l=0.3$.

Figure 11. The determination of the CO concentration dependence of the reaction order with respect to NO using the proposed model. The model calculations were performed for graphite, where NO and CO concentrations were varied between 20 and 100 ppm, and 20 and 200 ppm, respectively. Closed triangles- $l=0$; open circles- $l=0.05$; closed circles- $l=0.1$; closed squares- $l=0.2$; closed diamonds: $l=0.3$.

Figure 12. The determination of the overall reaction order with respect to NO using the proposed model. The model calculations were performed at 700_C for Wyodak coal char, where NO concentration was varied between 20 and 100 ppm, and added CO concentration was 200 ppm. Closed circles- $l=0$; closed squares- $l=0.05$; closed diamonds: $l=0.1$, closed triangles- $l=0.2$; open circles- $l=0.3$.

Figure 13. The determination of the overall reaction order with respect to NO using the proposed model. The model calculations were performed at 800_C for resin char, where NO concentration was varied between 20 and 100 ppm, and added CO concentration was 200 ppm. Closed circles- $l=0$; closed squares- $l=0.05$; closed diamonds: $l=0.1$, closed triangles- $l=0.2$; open circles- $l=0.3$.

APPENDIX A

Determination of the effectiveness factor for NO/CO-carbon reaction

$$R_g = 82.06$$

$$M_{NO} = 30$$

Graphite

Temperature °C	k" (no/co) g/m ² /hr/atm	ρ g/cc	A m ² /g	k _v 1/hr	R cm
650	0.063697	1.5545	1.458	364.484604	0.0275
700	0.2028	1.5545	1.458	1223.31781	0.0275
750	0.50652	1.5545	1.458	3212.40831	0.0275
800	0.80089	1.5545	1.458	5327.59376	0.0275
850	0.38704	1.5545	1.458	2694.59882	0.0275

D1 cm ² /sec	D2 cm ² /sec	Thiele Mod1	Thiele Mod2	Eff. Factor1	Eff. Factor2
2.00E-04	2.00E-03	0.61873693	0.1956618	0.9753739	0.99745703
2.00E-04	2.00E-03	1.13353803	0.3584562	0.9236297	0.99153744
2.00E-04	2.00E-03	1.83688436	0.58087384	0.82914816	0.97820497
2.00E-04	2.00E-03	2.36554926	0.74805236	0.75465215	0.96457735
2.00E-04	2.00E-03	1.68233896	0.53200229	0.85097949	0.98162617

Wyodak coal char

Temperature °C	k" (no/co) g/m ² /hr/atm	ρ g/cc	A m ² /g	k _v 1/hr	R cm
493	0.0011248	1.473	245.1	850.864479	0.019
550	0.0056365	1.473	245.1	4581.05665	0.019
600	0.020628	1.473	245.1	17783.9276	0.019
650	0.039306	1.473	245.1	35827.5299	0.019
700	0.095752	1.473	245.1	92006.1822	0.019
750	0.060857	1.473	245.1	61481.2218	0.019

D1 cm ² /sec	D2 cm ² /sec	Thiele Mod1	Thiele Mod2	Eff. Factor1	Eff. Factor2
2.00E-04	2.00E-03	1.5155497	0.4792589	0.87412498	0.98501484
2.00E-04	2.00E-03	2.98607832	0.94428088	0.67334782	0.9451907
2.00E-04	2.00E-03	4.23833993	1.34028077	0.54111412	0.89761596
2.00E-04	2.00E-03	6.79197155	2.14780999	0.37666671	0.78504471
2.00E-04	2.00E-03	5.55211685	1.75573351	0.44303027	0.84064167

Resin char

Temperature °C	k" (no/co) g/m ² /hr/atm	ρ g/cc	A m ² /g	k _v 1/hr	R cm
600	0.010549	1.2647	65.97	2101.69551	0.0275
650	0.017567	1.2647	65.97	3700.35647	0.0275
700	0.014883	1.2647	65.97	3304.81827	0.0275
750	0.034176	1.2647	65.97	7978.86515	0.0275
800	0.057719	1.2647	65.97	14133.9249	0.0275
850	0.044411	1.2647	65.97	11381.8948	0.0275

D1 cm ² /sec	D2 cm ² /sec	Thiele Mod1	Thiele Mod2	Eff. Factor1	Eff. Factor2
2.00E-04	2.00E-03	1.97146117	0.62343076	0.8100264	0.97501219
2.00E-04	2.00E-03	1.86311746	0.58916947	0.82542382	0.977598
2.00E-04	2.00E-03	2.89492294	0.91545502	0.68468489	0.94824423
2.00E-04	2.00E-03	3.85298959	1.21842229	0.57723639	0.91321628
2.00E-04	2.00E-03	3.45759188	1.09338656	0.61843783	0.92840674