143

PRESSING TECHNOLOGY

J. D. Harrell

DEVELOPMENT DIVISION

JANUARY, FEBRUARY, MARCH 1971
SANL 804-011

For
Lawrence Radiation Laboratory
Livermore, California

dy
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

Mason & Hanger-Silas Mason Co., Inc.

Pantex Plant

P. O. BOX 647
AMARILLO, TEXAS 79105
806-335-1581

operated for the
ATOMIC ENERGY COMMISSION
under

U. S. GOVERNMENT Contract DA-11-173-AMC-487 (A)

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Atomic Energy Commission, nor their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately-owned rights.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

PRESSING TECHNOLOGY

J. D. Harrell

DEVELOPMENT DIVISION

January, February, March 1971
SANL 804-011

PRESSING TECHNOLOGY

ABSTRACT

Work has started to determine pressing variables of PBX LX-10, the objective being to generate the highest density possible in an efficient manner and without major equipment modifications.

Temperatures in excess of 2000 F can be generated in an entrapped air bubble when repressing HE parts directly in oil, because of burning of the oil. Temperature over water can exceed 600 F.

DISCUSSION

STUDY OF LX-10 PRESSING VARIABLES

A study to determine the optimum process for pressing LX-10 has just begun:

1. Repeat LRL/J. R. Humphrey work for confirmation under Pantex conditions.
2. Determine the effect of Viton variations at 4.5 wt. %, 5.0 wt. %, and 5.5 wt. %.
3. Determine the best initial compaction pressure.
4. Determine the density increase resulting with dwell periods extended up to 30 minutes.
5. Determine if higher density results when a pressed billet is heated before repressing.
6. Determine relationship of initial compaction pressure and repressing pressure.
7. Determine if density is varied by a slow application of initial compacting pressures.
8. Combine all of the above information and select the process that is as near optimum as possible. Confirm that process by producing some parts.
9. Repeat the process selected in (8) above with a different lot of raw material.

COMPRESSIONAL HEATING OF GASES

A report(1) has been written for AEC-ALO (it will be published) concerning the possible hazard of air in presses during pressing. Some of the information in it is pertinent to all explosive pressing operations and the main conclusions of the investigation are therefore included here.

It is concluded from these experiments that dangerously high temperatures can be generated by compressional heating if there is a gas bubble entrapped within a prepressed part. Conversely, there is not a hazard if air or gas is distributed among the granules of commonly used PBX materials during the process of original compaction.

Figs. 1 through 4 taken from the report, represent the experiment results. A careful study of these graphs will develop several conclusions, including the primary thoughts:

1. Avoid entrapped gas bubbles in or adjacent to prepressed HE parts.
2. Avoid rapid application of compacting pressures.
3. Avoid the dieselizing effect by exposing the prepressed HE part to only water during repressing operations.

FUTURE WORK; COMMENTS; CONCLUSIONS

The LX-10 Pressing Variable Study is expected to be complete and results included in the next report.

-
1. Entrapped Air Hazard in Pressing of Explosives, I. B. Akst, Mason & Hanger - Silas Mason Co., Inc., 1970.

Fig. 1. Pressure-induced temperature rise in powder

Fig. 2. Temperature during pressurization and depressurization of a large air bubble

Fig. 3. Temperature in Nitrogen Bubble during Compression and Decompression Cycle

Fig. 4. Temperature in Air Bubble During Early Compression