MOLBO Containment Data Report

T. Stubbs

R. Heinle

June, 1997

This is an informal report intended primarily for internal or limited external distribution. The opinions and conclusions stated are those of the author and may or may not be those of the Laboratory.
Work performed under the auspices of the U.S. Department of Energy by the Lawrence Livermore National Laboratory under Contract W-7405-ENG-48.

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

This report has been reproduced
directly from the best available copy.

Available to DOE and DOE contractors from the
Office of Scientific and Technical Information
P.O. Box 62, Oak Ridge, TN 37831
Prices available from (615) 576-8401, FTS 626-8401

Available to the public from the
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Rd.,
Springfield, VA 22161

MOLBO Instrumentation Summary

Instrumentation	Fielded on this Event	Data Return	Present in this Report
<u>Plug Emplacement</u>	yes	yes	yes ^(a)
<u>Radiation</u>	yes	yes	yes
<u>Pressure</u>			
Stemming	yes	yes	yes
Challenge	no	-	-
Cavity	no	-	-
Atmospheric	no	-	-
<u>Motion</u>			
Free Field	no	-	-
Surface	yes	yes	yes
Plug	no	-	-
Stemming	no	-	-
Surface Casing	no	-	-
Emplacement Pipe	no	-	-
<u>Hydroyield^(b)</u>	yes	yes	no
<u>Collapse^(c)</u>	yes	no	-
<u>Stress</u>	no	-	-
<u>Strain^(d)</u>	yes	yes	no
<u>Other Measurements</u>	no	-	-

- (a) Description only.
(b) CORTEX and/or SLIFER in emplacement hole.
(c) EXCOR or CLIPER in emplacement hole.
(d) Strain load on emplacement pipe.

Event Personnel

Containment Physics

B. Hudson	LLNL
E. Woodward	LLNL
J. Kalinowski	EG&G/AVO
T. Stubbs	EG&G/AVO

Instrumentation

C. Cordill	LLNL
M. Hatch	EG&G/AVO
W. G. Webb	EG&G/NVO
A. E. Moeller	EG&G/NVO

Contents

1.	Event Description									
1.1	Site	.	.	.	.	.	.	.	.	1
1.2	Instrumentation	.	.	.	.	.	.	.	.	1
1.3	Emplacement	.	.	.	.	.	.	.	.	2
2.	Stemming Performance									
2.1	Radiation and Pressure			.	.	.	.	.	.	8
2.2	Motion	.	.	.	.	.	.	.	.	8
2.3	Collapse		.	.	.	.	.	.	.	9
	References	.	.	.	.	.	.	.	.	18

1. Event Description

1.1 Site

The MOLBO event was detonated in hole U20ag of the Nevada Test Site as indicated in figure 1.1. The MOLBO device had a depth-of-burial (DOB) of 636 m in the quartz-bearing rhyolites of area 20, about 20 m below the standing water level, as shown in figure 1.2⁽¹⁾. Figure 1.3 is a plan map of the immediate vicinity of hole U20ag showing the drill holes used in the construction of the cross section plot of figure 1.2. Stemming of the 2.44 m diameter emplacement hole followed the plan shown in figure 1.4. A log of the stemming operations was maintained by Holmes & Narver⁽²⁾.

Detonation time was 06:55 PST on February 12, 1982. Instrumentation to monitor collapse and chimney formation failed soon after the detonation and there was no surface expression of the collapse.

No radiation arrivals were detected above ground and the MOLBO containment was considered successful.

1.2 Instrumentation

Figure 1.5 is a schematic layout of the instrumentation designed to monitor the emplacement procedures and stemming performance of the MOLBO event.

The three stemming plugs above the MOLBO event were composed of coal-tar epoxy (LAE 59, denoted CTE). A soft layer of coal-tar and aggregate (LAE 59MY, denoted CTA) was poured on the top of each of the plugs to act as a gas seal.

Pressure and radiation was monitored in the coarse stemming just below the top plug at a depth of 23.8 m.

Vertical motion stations were fielded at 0.91 m depth in the ground surface at horizontal ranges from surface ground zero (SGZ) of 15.2, 317, 442, 884, and 1325 m. These latter three were placed on a line 15 degrees North of West from SGZ.

Data from each of the above instruments were transmitted to the recording trailer by an analog system and recorded on magnetic tape.

Two D-cables were used for quality assurance during the stemming operations and recorded post-shot. One CLIPER sensor was mounted in the emplacement hole to monitor cavity collapse and chimney formation.

A history of the fielding operations of the instrumentation is outlined in reference 4. Details of the instrumentation are given in reference 5.

1.3. Emplacement

The stemming plugs consisted of two "LAE 59" coal-tar epoxy (CTE) layers. The bottom two plugs were designed to be 3.05 m thick while the top was 5.18 m thick. All plugs were to be capped with about 1.8 m of soft coal-tar-aggregate "LAE 59MY" epoxy (CTA) to act as a gas sealant. Slight variations between design and as-built dimensions occurred. See reference 2. Stemming between the plugs consisted of layers of fines and coarse gravel. The top of the hole (above the top plug) was filled with ground surface derived backfill and the inside of the emplacement pipe above the device diagnostics section was grouted for its full length. See figure 1.4.

Figure 1.1 Map of the Nevada Test Site indicating the location of hole U20ag.

Identification of units shown on geologic map and cross section, U20ag

Quaternary units	
Qac	Alluvium and colluvium
Tertiary units	
Ttt	Trail Ridge Member, Thirsty Canyon Tuff
Ttsr	Spearhead and Rocket Wash Members, Thirsty Canyon Tuff
Tat	Air-fall and ash-flow tuff
Tma	Ammonia Tanks Member, Timber Mountain Tuff
Tmr	Rainier Mesa Member, Timber Mountain Tuff
Tp(Tb)	Bedded tuff associated with the Paintbrush Tuff
Tpc	Tiva Canyon Member, Paintbrush Tuff
Tpt	Topopah Spring Member, Paintbrush Tuff
Trpr	Quartz-rich rhyolite lava, Lavas of Scrugham Peak Quadrangle
Trpq	Quartz-bearing rhyolite lavas, Lavas of Scrugham Peak Quadrangle
Trau	Upper rhyolite lavas, Tuffs and rhyolites of Area 20
Trab	Bedded and ash-flow tuffs, Tuffs and rhyolites of Area 20
Tral	Lower rhyolite lavas, Tuffs and rhyolites of Area 20

Revised 09-15-81

Figure 1.2 East-West geologic cross section through hole U20ag.

Figure 1.3 Plan View Map of the region encompassing hole U20ag showing the holes used in the geologic cross section of figure 1.2.

Figure 1.4 As-built stemming plan for the event MOLBO in Hole U20ag.

Figure 1.5 As-built containment instrumentation plan for the emplacement hole (U20ag) on the MOLBO event.

2. Stemming Performance

2.1 Radiation and Pressure

Pressure and radiation were monitored on the MOLBO event at only location, in the coarse stemming just below the top plug. Histories of the measurements are shown for two time spans in figures 2.1 and 2.2.

The data are consistent with satisfactory containment.

2.2 Motion

Explosion-induced histories of the motion measured on the MOLBO event are shown in figures 2.3–2.6. Characteristics of the associated motion and transducers are given in tables 2.1–2.3.

Station 65, at a horizontal range of 1325 m, gave no usable data and is not further presented in this report.

As seen in figures 2.4-2.6 all surface stations underwent a period of free-fall ending in a large acceleration spike, a "slap-down". Ground shock induced spall extended to and probably beyond the most distant reporting station (station 64) at a horizontal distance of about 1.4 depths-of-burial. Explosion-induced motion is otherwise unremarkable.

2.3 Collapse

A late time signal (at about 1800 s) was seen in both the geophone (not reported) and the records from stations 63 and 64. In figure 2.7 the acceleration from both stations 63 and 64 are over-plotted during 0.5 second windows at the shock arrival and the late time signal arrival. At station 64, the explosion-induced signal arrives 103 ms later than at station 63 suggesting a transmission speed of about 3090 m/s. However, the late time signals at stations 63 and 64 are separated by only 39 ms. This indicates that the source of the disturbance was other than the emplacement hole U20ag.

The CLIPER and D-cable 92 both failed before data could be retrieved, D-cable 93 attained its final length by 2 seconds after the detonation. It is suspected that reflection of the initial shock wave from the free surface of the ground caused this loss.

Figure 2.1 Pressure and radiation measured in the coarse stemming below the top plug (station 31 at a depth of 23.8 m). Shown is the first 180 s. The slight change in pressure at and just after detonation can be explained by ground motion.

Figure 2.2 Pressure and radiation measured in the coarse stemming below the top plug (station 31 at a depth of 23.8 m). Shown is the total recorded time of greater than 30 hours.

Figure 2.3 Explosion-induced vertical motion of the ground surface at a horizontal range of 15.24 m and a depth of 0.9 m (station 61). The traces annotated with "a" are derived from the acceleration while the velocimeter-derived signals are shown as heavy traces.

Figure 2.4 Explosion-induced vertical motion of the ground surface at a horizontal range of about 317.5 m and a depth of 0.9 m (station 62). This station was emplaced in the trailer park. The traces annotated with "a" are derived from the acceleration while the velocimeter-derived signals are shown as heavy traces.

Figure 2.5 Explosion-induced vertical motion of the ground surface at a horizontal range of 441.8 m and a depth of 0.9 m located on a line 15 degrees North of West from SGZ (station 63). The velocity and displacement histories are invalid for times greater than about 1 s, the time of the slap-down which exceeded the acceleration system limits.

Figure 2.6 Explosion-induced vertical motion of the ground surface at a horizontal range of 883.5 m and a depth of 0.9 m located on a line 15 degrees North of West from SGZ (station 64). The velocity and displacement histories are invalid for times greater than about 1 s, the time of the slap-down which exceeded the acceleration system limits.

Figure 2.7 Over-plot of 5 second intervals of vertical acceleration detected at stations 63 and 64 (horizontal surface ranges are 441.8 and 883.5 m, respectively) during the explosion-induced signal and the late time (source unknown) signal.

Table 2.1 Summary of Motion

Gauge	Slant Range (m)	Arrival Time (ms)	Acceleration Peak (g)	Velocity Peak (m/s)	Displacement Peak (m)	Displacement Residual (m)
61av	636.2	315	7.5, 56.3(a)	4.3	1.54	-0.16
61uv			-	4.3	1.51	-0.07
62av	710.8	351	12.0, 24.3(a)	3.4	0.77	0.04
62uv			-	3.8	0.64	-0.04
63av	774.4	378	6.0, 10(b)	2.1	0.34	(c)
64av	1088.6	475	4.8, 10(b)	1.4	0.18	(c)
65av(d)	1470	-	-	-	-	-

(a) Slap-down.

(b) Slap-down peak not reached - - Band edge.

(c) Not able to estimate.

(d) This transducer inoperative.

Table 2.2 Accelerometer Characteristics

Gauge	Natural Frequency (Hz)	Damping Ratio	System Range (g's)
61av	590	0.65	50
62av	620	0.65	30
63av	937	NA	10
64av	916	NA	10
65av	965	NA	10

NA. Not available.

Table 2.3 Velocimeter Characteristics

Gauge	Natural Frequency (Hz)	Time to 0.5 Amplitude (s)	Calibration Temperature (°F)	Operate Temperature (°C)	System Range (m/s)
61uv	3.75	10.85	74.71	56.80	8
62uv	3.50	9.75	74.51	56.80	7.5

References

1. N. W. Howard, "U20ag Preliminary Site Characteristics Summary", DM 81-67, Lawrence Livermore National Laboratory, Livermore, CA, October 2, 1981.
2. George Kronsbein, "Containment Report for U20ag," Holmes & Narver, NTS:A2:82-15, February 3, 1982.
3. LLNL contact for additional information: R. A. Heinle (CORRTEX and SLIFER data)
4. William G. Webb, "Special Measurements Final Engineering Report MOLBO, U20ag", EG&G, Energy Measurements, Las Vegas, NV, SM:83E-99-32, 17 March, 1982.
5. William G. Webb, "Special Measurements Physics/Instrumentation Package for MOLBO, U20ag, Revision "A", Final", EG&G, Energy Measurements, Las Vegas, NV, SM:81E-93-25, 17 March, 1982.

Distribution:

LLNL

TID/Brenda Staley (3)	L-658
Test Program Library	L-160
Containment Vault	L-221
Burkhard, N.	L-221
Cooper, W.	L-160
Denny, M.	L-205
Goldwire, H.	L-221
Hannon, W. J.	L-221
Heinle, R. (5)	L-221
Mara, G.	L-149
Moran, M. T.	L-777
Moss, W.	L-200
Pawloski, G.	L-221
Rambo, J.	L-200
Valk, T.	L-154

LANL

Brunish, W.	F-659
Kunkle, T.	F-665
Trent, B.	F-664

Sandia

Bergstresser, T.	MS-1159
------------------	---------

BNL/AVO

Brown, T.	A-5
Hatch, M.	A-5
Still, G.	A-5
Stubbs, T.	A-5

BNL/NVO

Bellow, B.	N 13-20
Davies, L.	N 13-20
Moeller, A.	N 13-20
Robinson, R.	N 13-20

Defense Special Weapons Agency

Ristvet, B.

Maxwell Technologies

Peterson, E.

Eastman Cherrington Environment

Keller, C.