19
MHSMP-70-D1 EE

*Mason & Hanger-
Silas Mason Co., Inc.*

ENGINEERS AND CONTRACTORS

SINCE 1827

Pantex Plant

THERMAL PROPERTIES & CHEMICAL REACTIVITY

SANL 712-005 (Jan-Mar)

R. S. Wilson

January, February, March 1970

DEVELOPMENT DIVISION

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

js

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

THERMAL PROPERTIES & CHEMICAL REACTIVITY

R. S. Wilson

January, February, March 1970
SANL 712-005

ABSTRACT

A method using a chromatograph for a quantitative determination of the FEFO content of LX-09 was investigated. The accuracy of the initial results was variable. Difficulty has been experienced in obtaining reproducible data due to fluctuations of unknown origin in the FEFO peak. Results are given of a sample analysis of LX-09.

A modification of the procedure for determining purity with the DSC-1 is discussed.

The molar heats of decomposition of PETN, diPEHN, triPEON, and tetraPEDN were measured and correlated with the number of nitrate and ether branches present in each type of molecule and the effective contribution of each branch to the total heat of decomposition was obtained. The heats of fusion and decomposition for each compound are reported.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

FEFO Determination in LX-09

The possibility of using a gas chromatograph to determine the concentration of FEFO in LX-09 has been investigated. The primary purpose of this work was to establish a method which would require smaller amounts of material and be simpler and more readily reproducible than the fluoride analysis method¹ presently in use.

A Hewlett Packard 5750-B chromatograph equipped with dual flame ionization detectors was used. The columns were 1/8-inch x 1 meter long stainless steel tubing packed with OV-3 on Chromosorb-W. Peak area was measured with a digital integrator. The column oven was programmed from 50 to 250°C at 40° per minute with a one-minute post-injection interval.

The FEFO was dissolved in chloroform from a finely ground LX-09 sample. Chemical tests on the residue showed greater than 98% of the FEFO was removed. N-butyl ether was added as an internal standard. The ether readily separated from the solvent and FEFO peaks and showed no observable effect on the sample or evaporation loss during the analysis.

The ratio of ether to FEFO peak areas from this solution was compared with the ratio produced from a standard solution containing measured amounts of ether and FEFO in chloroform. These amounts were chosen to give approximately the same magnitude of response from the detector as did the LX-09 solution.

---

¹Selig, W., Some Analytical Methods for Explosives, Part III, UCRL-784, Sept. 1969.

The procedure was developed using columns well conditioned for FEFO. Initial results indicated the repeatability of the ratio of peak areas had a standard deviation of about 2.5%. Table I shows the results of an evaluation of the absolute accuracy obtained using two standard solutions. Calculated to the number of significant figures available, the indicated FEFO concentration was exact.

The original columns soon showed signs of deterioration and new ones were prepared using the same packing. Considerable difficulty was experienced using the newly packed columns; the FEFO peak showed large and apparently random fluctuations in size. This condition has been alleviated somewhat by continued use of the columns, but the results are still not as consistent as those obtained with the original columns. A check of the absolute accuracy of these columns showed results in error by 8.7%. Table II shows the best data obtained from an analysis of LX-09, Lot 94-7.

This method shows promise of obtaining accuracy comparable to the fluoride analysis method, and it is definitely simpler. A further attempt will be made to improve the stability of the FEFO peak by varying the operating parameters as well as investigating the possibility of using different liquid phases and supports.

Table I

Accuracy Determination with Original Columns

	<u>Sample I</u>	<u>Sample II</u>
	1.8 μ l FEFO	1.4 μ l FEFO
	1.0 μ l n-butyl ether	1.0 μ l n-butyl ether
	<u>Ratio of Ether to FEFO Peak Areas</u>	
Run No. 1	2.050	2.525
2	2.012	2.621
3	2.024	2.739
4	2.146	2.746
Average	2.058	2.658
1 σ	2.5%	3.4%

Indicated FEFO content in Sample II using Sample I as a reference: 1.4 μ l.

Table II

Quantitative Analysis of FEFO in LX-09

<u>Calibration Sample</u>		<u>LX-09 Sample</u>
1.6 μ l FEFO		0.1416 g LX-09 (Lot 94-7)
1.0 μ l n-butyl ether		1.0 μ l n-butyl ether
1 ml chloroform		1 ml chloroform
<u>Ratio of Ether to FEFO Peak Areas</u>		
Run No.	1	2.38
	2	2.39
	3	2.48
	4	2.31
	5	2.32
	6	2.36
Average	2.37	2.11
1 σ	2.4%	0.5%

Indicated FEFO concentration in LX-09: 2.2%

FEFO concentration obtained from fluoride analysis method: 2.3%

Determination of PETN Purity by DSC-1

An automatic switching circuit was built and interfaced between the DSC-1 and analog to digital converter units used for purity analysis as previously described.² This permits adding simultaneous temperature recordings to the DSC-1 output, thereby eliminating the need for manually recording the temperature and permitting a more accurate determination of the melting point.

A new computer program was written to handle this additional capability and to do a more sophisticated analysis than previously was done. An attempt to adapt this program to the PDP-8 computer was not successful because of the very limited storage available on the machine here. Therefore, an ALC routine was developed to permit direct use of the punched paper tape by the IBM 360.

This system is now operating and has been used successfully on PETN. A check of the accuracy of the analysis method is planned for the near future.

Decomposition of PETN Homologs

An effort was made to relate the molar heats of decomposition of PETN, diPEHN, triPEON, and tetraPEDN to the number of various types of molecular groups present in each molecule and to thereby determine the contribution of each group to the total heat of decomposition. Only two groups may be considered in this analysis as an attempt to evaluate any higher number leads to an indeterminate set of four equations. This restricts the choice of groups to the nitrate branch and the ether linkage. In this case, a set of four equations is obtained, any two of which may be considered independent. This necessitates applying small corrections to the heats of decomposition to obtain a unique solution.

---

²*Pantex Quarterly Report for January, February, March 1968.*

Data were obtained from the DSC-1 with samples enclosed in sealed containers perforated to release pressure. Results from a minimum of four runs of each compound are shown in Table III.

A good correlation was obtained for diPEHN, triPEON, and tetraPEDN; however, PETN differed significantly from these and was not included in the calculations. Since PETN is fundamentally different from the higher order homologs in that it contains no ether link, this result was not unexpected.

The following values were calculated from the adjusted heats of decomposition as shown in Table III.

Contribution to the molar heat of decomposition of the PETN homologs:

Ether group	119.4 kcal/mole
Nitrate group	15.4 kcal/mole
Nitrate group (from PETN)	19.4 kcal/mole

The adjusted values were obtained by applying to each heat of decomposition a correction proportional in magnitude to the heat and such that the equations yielded a unique solution. In each case the required correction was less than 0.25%.

In view of the similar structures of the ether and nitrate groups, the large difference in heats of decomposition as indicated above is somewhat surprising. It suggests the possibility that energy from the nitrate groups catalyzes the

Table III

DSC-1 Analysis of PETN Homologs

	<u>Observed Heat of Fusion</u>		<u>Observed Heat of Decomposition</u>		<u>Adjusted Heat of Decomposition</u>
	<u>kcal/mole</u>	<u>Std. Dev. (%)</u>	<u>kcal/mole</u>	<u>Std. Dev. (%)</u>	<u>kcal/mole</u>
PETN	11.1	4.5	77.4	5.4	-
diPEHN	11.1	4.0	212.4	5.1	211.9
triPEON	13.6	7.6	361.4	6.6	362.2
tetraPEDN	20.2	7.4	513.7	6.6	512.6

reaction of the ether link. This could also account for the higher heat of decomposition of the nitrate groups in PETN, which has no ether linkage. However, more detailed information than is presently available concerning the nature of the reactions would be required to make a definite evaluation.