JUL 24 1997

SANDIA REPORT

SAND95-2183 • UC-814

Unlimited Release

Printed July 1997

Yucca Mountain Site Characterization Project

Geotechnical Characterization for the Main Drift of the Exploratory Studies Facility

RECEIVED

JUL 28 1997

OSTI

Dwayne C. Kicker, Eric R. Martin, Carl E. Brechtel, Charles A. Stone, David S. Kessel

Prepared by

Sandia National Laboratories

Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy under Contract DE-AC05-84OR21400.

Approved for public release; distribution is unlimited.

Sandia National Laboratories

MASTER

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831

Prices available from (815) 676-8401, FTS 626-8401

Available to the public from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Rd
Springfield, VA 22161

NTIS price codes
Printed copy: A09
Microfiche copy: A01

Geotechnical Characterization for the Main Drift of the Exploratory Studies Facility

Dwayne C. Kicker, Eric R. Martin
Carl E. Brechtel, and Charles A. Stone
Agapito Associates, Inc.
Las Vegas, NV 89102

David S. Kessel
Yucca Mountain Project Management
Sandia National Laboratories
Albuquerque, NM 87185

Sandia Contract No. AI-7608

Abstract

Geotechnical Characterization of the Main Drift of the Exploratory Studies Facility was based on borehole data collected in site characterization drilling and on scanline rock mass quality data collected during the excavation of the North Ramp. The Main Drift is the planned 3,131-m (10,273-ft) near-horizontal tunnel to be excavated at the potential repository horizon for the Yucca Mountain Site Characterization Project. Main Drift borehole data consisted of three holes — USW SD-7, SD-9, and SD-12 — drilled along the tunnel alignment. In addition, boreholes USW UZ-14, NRG-6, and NRG-7/7A were used to supplement the database on subsurface rock conditions. Specific data summarized and presented included lithologic and rock structure core logs, rock mechanics laboratory testing, and rock mass quality indices. Cross sections with stratigraphic and thermal-mechanical units were also presented. Topics discussed in the report include geologic setting, geologic features of engineering and construction significance, anticipated ground conditions, and the range of required ground support.

Rock structural and rock mass quality data have been developed for each 3-m (10-ft) interval of core in the middle nonlithophysal stratigraphic zone of the Topopah Spring Tuff Formation. The distribution of the rock mass quality data in all boreholes used to characterize the Main Drift was assumed to be representative of the variability of the rock mass conditions to be encountered in the Main Drift. Observations in the North Ramp tunnel have been used to project conditions in the lower lithophysal zone and in fault zones.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This work was supported by the United States Department of Energy under Contract DE-AC04-94AL85000 and was prepared under the Yucca Mountain Site Characterization Project WBS numbers 1.2.3.2.6.2.1, 1.2.3.2.6.2.2, and 1.2.3.2.6.2.3, QA Grading Report #1.2.3.2.6.2.1, Revision 0. The planning document that guided this work activity was Work Agreement #071, Revision 00. The information and data documented in this report were collected under a fully qualified QA Program, except as noted in the report.

This report supports work defined in the Site Characterization Plan Section 8.3.1.14.2 and is discussed in Study Plan SP-8.3.1.14.2, Revision 0, Sections 2.3.1.3 and 2.3.2.3.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000

ACKNOWLEDGMENTS

The authors would like to acknowledge the support and contributions of the various organizations involved in conduct of the surface-based site characterization activities. Timothy J. Sullivan, Department of Energy (DOE), supported the work as WBS Element Manager responsible for the Soil and Rock Properties studies. Dale Engstrom of Spectra provided lithology logs for USW SD-7, SD-9, SD-12, and UZ-14 boreholes. David C. Buesch, U.S. Geological Survey (USGS), provided review of logs for USW SD-7 and UZ-14. Gerald Nieder-Westermann, TRW/Morrison Knudsen, assisted in the development of the Main Drift cross section. Geologists of the Drilling Support Division, Drilling Support Sample Management Department, T&MSS, were responsible for development of the field rock structural logs.

Coordination and direction of the field support activities was performed by Kenneth Skipper, Drew Coleman, and Leroy Heath of the DOE.

Contents

Acknowledgments	iii
1.0 Introduction	1-1
1.1 Purpose	1-1
1.2 Background	1-1
1.3 Scope	1-3
1.4 Quality Assurance	1-5
1.5 Report Organization	1-6
2.0 Summary and Conclusions	2-1
2.1 Introduction	2-1
2.2 Geotechnical Summary	2-1
2.2.1 Geology and Major Structural Features Along the Main Drift	2-1
2.2.2 Joint Structure	2-2
2.2.3 Hydrology	2-3
2.2.4 Rock Structure Data from the Main Drift Core	2-3
2.2.5 Intact Rock Mechanical Properties	2-4
2.2.6 Rock Mass Quality Indices	2-5
2.2.7 Rock Mass Mechanical Properties Estimates	2-6
2.3 Conclusions	2-8
3.0 Geology of the Main Drift	3-1
3.1 Introduction	3-1
3.2 Stratigraphy	3-1
3.3 Geologic Cross Sections	3-7
3.4 Thermal-Mechanical Stratigraphy	3-7
3.5 Major Structural Features	3-10
3.5.1 Yucca Mountain Structural Framework	3-10
3.5.2 Faults Recognized Along the Main Drift Alignment	3-12
3.6 Joint Structure	3-14
3.7 Hydrology	3-15
4.0 Borehole Geotechnical Data	4-1
4.1 Rock Structure Data	4-1
4.1.1 Core Recovery	4-1
4.1.2 RQD Data	4-2
4.1.3 Rock Weathering and Hardness	4-5

4.1.4	Lithophysae Content	4-5
4.1.5	Fracture Data	4-9
4.2	Rock Mechanics Laboratory Test Data	4-14
5.0	Rock Mass Quality Assessment	5-1
5.1	Introduction	5-1
5.2	Rock Mass Quality Projections for the Tptpmn	5-2
5.2.1	Rock Mass Quality Indices for the RMR System—Tptpmn	5-2
5.2.2	Rock Mass Quality Indices for the Q System—Tptpmn	5-4
5.3	Evaluation of Projected RMR and Q Results—Tptpmn	5-5
5.3.1	Correlation of Q and RMR Results	5-9
5.3.2	Comparison of Q Values from Field- and Core-Based Assessments	5-9
5.4	Indicated Ground Conditions and Support Requirements—Tptpmn	5-11
5.4.1	Key Block Stability Analysis—Tptpmn	5-11
5.4.2	Indicated Ground Support—Tptpmn	5-14
5.5	Rock Mass Quality—Tptpll	5-14
5.6	Rock Mass Quality—Fault Zones	5-14
6.0	Assessment of Rock Mass Mechanical Properties	6-1
6.1	Introduction	6-1
6.2	Rock Mass Strengths	6-1
6.2.1	Yudhbir Criterion	6-2
6.2.2	Hoek and Brown Criterion	6-3
6.2.3	Failure Criteria Parameters for Intact Strength Results	6-3
6.2.4	Design Rock Mass Strengths	6-5
6.2.5	Rock Mass Mohr-Coulomb Strength Parameters and Dilation Angles	6-5
6.3	Rock Mass Elastic Moduli	6-5
6.4	Rock Mass Poisson's Ratio	6-7
7.0	References	7-1
	Appendix A—Interim Data Transmittal References	A-1
	Appendix B—Rank-Ordered Rock Mass Quality Estimates for the Tptpmn	B-1
	Appendix C—USW SD-7, SD-9, SD-12 and UZ-14 Core Logs and Data	C-1
	Appendix D—Key Block Analysis Comparison of North Ramp and Main Drift Orientations	D-1

Figures

1-1	Plan map of conceptual repository, locations of the North Ramp, Main Drift, and south Ramp, and locations of the boreholes used to characterize the Main Drift	1-2
2-1	Projected distribution of ESD ground support category for the Tptpmn—Main Drift boreholes	2-7
3-1	Stratigraphic cross section along the ESF Main Drift	3-6
3-2	Correlation of stratigraphic and thermal-mechanical units along the ESF Main Drift alignment	3-8
3-3	Thermal-mechanical unit cross section along the main Drift	3-9
3-4	Map of ESF area showing surface location of identified faults	3-11
3-5	Surface locations of faults mapped by Scott and Bonk (1984)	3-13
4-1	Pie chart showing core recovery, lost core and rubble zones as percentage of total core in the Tptpmn—Main Drift boreholes	4-3
4-2	Histogram showing RQD frequency in the Tptpmn—Main Drift boreholes	4-4
4-3	Histogram showing <i>enhanced-RQD</i> frequency in the Tptpmn—Main Drift boreholes	4-4
4-4	Cross-hole comparison of RQD in the Tptpmn and portions of the Tptpll	4-6
4-5	Distribution of rock weathering parameters for the Tptpmn—Main Drift boreholes	4-7
4-6	Distribution of the estimated hardness rating as a percentage of the total drilling in the Tptpmn—Main Drift boreholes	4-8
4-7	Histogram of the distribution of the percent lithophysae and other cavities in the Tptpmn—Main Drift boreholes	4-9
4-8	Distribution of the structural features in the Tptpmn—Main Drift boreholes	4-11
4-9	Distribution of fracture inclinations for both uncorrected and corrected data in the Tptpmn—Main Drift boreholes	4-11
4-10	Distribution of fracture mineral infillings in the Tptpmn—Main Drift boreholes ...	4-13
4-11	Distribution of fracture infill thickness in the Tptpmn—Main Drift boreholes	4-13
4-12	Distribution of fracture planarity for the Tptpmn—Main Drift boreholes	4-15
4-13	Distribution of the fracture roughness for the Tptpmn—Main Drift boreholes	4-15
4-14a	Confined compressive strength results for the Tptpmn—NRG-6 and NRG-7/7A boreholes	4-18
4-14b	Confined compressive strength results for the Tptpmn—NRG-6, NRG-7/7A, SD-9 and SD-12 boreholes	4-18
5-1	Histograms showing the distribution of the RMR system parameters for the Tptpmn—Main Drift boreholes	5-3
5-2	Distribution of the RMR in the Tptpmn—Main Drift boreholes	5-4
5-3	Distribution of the previously assumed values and the field-assessed values of Jn and SRF	5-6

5-4	Histograms showing the distribution of the Q system parameters for the Tptpmn—Main Drift boreholes	5-7
5-5	Distribution of the estimated Q in the Tptpmn—Main Drift boreholes	5-8
5-6	Correlation of Q and RMR results for the Tptpmn—Main Drift boreholes	5-10
5-7	Comparison of cumulative frequency of occurrence of Q for both core-based and field-assessed values for the Tpc stratigraphic unit	5-10
5-8	Distribution of ground support category from NRG borehole data for the Tpc stratigraphic unit of the Tiva Canyon Formation	5-12
5-9	Distribution of ground support category from North Ramp tunnel data for the Tpc unit of the Tiva Canyon Formation	5-13
5-10	Projected distribution of ESF ground support category for the Tptpmn—Main Drift boreholes	5-15
6-1	Comparison of Tptpmn testing data to intact rock mass strength criteria	6-4
6-2	Design rock mass strength envelopes for the Tptpmn—Main Drift boreholes	6-6

Tables

1-1	Studies, objectives, and activities of the Soil and Rock Properties Study Plan— <i>Studies to Provide Soil and Rock Properties of Potential Locations of Surface and Subsurface Access Facilities</i>	1-4
1-2	Correlation of study areas and activities with specific investigations conducted in the Main Drift	1-5
1-3	Nonqualified and preliminary data and assumptions	1-6
2-1	Summary of mean values for rock mechanics laboratory test data	2-4
2-2	RMR and Q values at five levels of cumulative frequency of occurrence	2-5
2-3	Comparison of intact rock values to estimated rock mass property values for each of the five rock mass classes	2-7
3-1	Lithostratigraphic nomenclature of the Tpt at Yucca Mountain, Nevada	3-2
3-2	Thickness of stratigraphic units in Main Drift boreholes	3-4
3-3	Known faults projected to encounter the Main Drift and approximate ramp station	3-12
3-4	Orientatoin of joint sets assumed to be present in Tpt	3-15
4-1	Summary of core recovery data for the Tptpmn—Main Drift boreholes	4-2
4-2	Comparison of RQD and <i>enhanced-RQD</i> data for the Tptpmn—Main Drift boreholes	4-3
4-3	Explanation of weathering descriptions and log abbreviations	4-7
4-4	Explanation of estimated hardness and log abbreviations	4-8

4-5	Total number of core structural features in the Tptpmn—Main Drift boreholes	4-10
4-6	Summary of rock mechanics laboratory test data for Tptpmn—Main Drift boreholes	4-16
4-7	Intact rock failure criteria—Tptpmn	4-19
5-1	RMR values at five levels of cumulative frequency of occurrence	5-3
5-2	Q values at five levels of cumulative frequency of occurrence	5-8
5-3	YMP ground support categories	5-12
5-4	Comparison of key block analysis results for the North Ramp and Main Drift	5-13
6-1	Tabulation of Q, RMR ₇₉ , and design RMR _D values for the five classes of rock mass quality in the Tptpmn	6-2
6-2	Constants for the rock mass strength criteria in MPa	6-4
6-3	Range of strength parameters and dilation angles for the Mohr-Coulomb failure criterion in the Tptpmn	6-6
6-4	Range of estimated rock mass modulus for the Tptpmn	6-7

1.0 Introduction

1.1 Purpose

The purpose of this report is to provide a geological and geotechnical characterization along the path of the Exploratory Studies Facility (ESF) Main Drift to support the geotechnical design. The ESF is being constructed by the U.S. Department of Energy (DOE) and is part of the Yucca Mountain Site Characterization Project (YMP). The purpose of the site characterization activities is to evaluate the feasibility of locating a high-level nuclear waste repository at the Yucca Mountain site. This report was prepared as part of the Soil and Rock Properties studies, W.B.S. 1.2.3.2.6.2 in accordance with Study Plan 8.3.1.14.2, *Soil and Rock Properties of Potential Locations of Surface and Subsurface Access Facilities* (DOE).¹

1.2 Background

The Main Drift is the planned horizontal tunnel that will be excavated at the potential repository horizon over a length of 3,131 m (10,273 ft) between the North and South Ramps of the YMP ESF. Each of these tunnels will be excavated using a 7.62-m (25-ft) diameter tunnel boring machine (TBM). In the first phase of ESF construction, the North Ramp portal and surface pad were constructed in 1994. The second phase of construction includes the excavation of the North Ramp currently in progress. The North Ramp² extends 2804 m (9,200 ft) from the surface portal to the potential repository horizon. The Main Drift will then be constructed followed by the 1,921-m (6,302-ft) South Ramp³ to connect to the surface. A map showing the locations of the North Ramp, Main Drift, and South Ramp is shown in Figure 1-1.

Three systematic drilling (SD) exploratory boreholes (USW SD-7, SD-9, and SD-12) were drilled to characterize the geological and geotechnical rock properties along the Main Drift alignment and to support the design and construction of the Main Drift. North Ramp Geologic (NRG) holes, NRG-6 and -7/7A, and hole UZ-14 were also used to increase the available database at the Main Drift horizon. Nonqualified rock quality data from borehole USW G-4 was reported (Lin et al. 1993a), however, these data were not included in this study. Stratigraphic contacts from USW G-4 were included in the three-dimensional geologic model of the YMP site that was the basis for the development of the Main Drift cross section. The three SD holes were

¹ Department of Energy (1991). Yucca Mountain Site Characterization Project, Study Plan No. 8.3.1.14.2, *Studies to Provide Soil and Rock Properties of Potential Locations of Surface and Subsurface Access Facilities*, U.S. Geological Survey, Las Vegas, NV, November.

² ESF Layout Calculation—BABEAD000-01717-0200-00003, Rev. 02.

³ Ibid.

Figure 1-1. Plan map of conceptual repository, locations of the North Ramp, Main Drift, and South Ramp, and locations of the boreholes used to characterize the Main Drift.

located next to the planned tunnel alignment but were required to be a minimum of 15 m (49.2 ft) from the tunnel centerline as per the ESF design requirements (DOE 1994). The approximate location of these boreholes is shown in Figure 1-1.

A geologic cross section shown in Figure 3-1, Section 3.0, includes the stratigraphic units, the location of the SD boreholes, and the proposed Main Drift alignment. The Main Drift differs from the North Ramp in that the entire length of tunnel is contained in one thermal-mechanical unit—the second Topopah Spring welded unit (TSw2), which is a moderately to densely welded, devitrified ash flow of the Topopah Spring Tuff that contains less than approximately 10% by volume lithophysal cavities. The Main Drift is almost entirely within the Topopah Spring crystal-poor middle nonlithophysal stratigraphic zone (Tptpmn). Geologic, geotechnical, and geophysical logs were developed for each hole. No additional rock mechanics testing data, beyond that developed in the NRG holes was available at the time of preparation of this report. The geologic logging consisted of detailed lithologic descriptions and stratigraphic identifications. The geotechnical log recorded rock structural features such as type, fracture characteristics, rock quality designation (RQD), core recovery, weathering, hardness, and lithophysae and other void content. Physical property test data from rock mechanics testing of core included density, porosity, unconfined compressive strength, triaxial compressive strength, and Brazilian indirect tensile strength. Borehole televiwer logs also were generated for each hole.

Estimates of rock mass quality were determined using both the Q (Barton et al. 1974) and the rock mass rating (RMR) (Bieniawski 1979) systems for classifying rock masses. The geotechnical core logging data was used as input for both classification systems using the approach described by Brechtel et al. (1995).

The rock mass quality data and rock mechanics testing data were used to derive estimates of rock mass mechanical properties required for design analysis using the methodology proposed by Hardy and Bauer (1991).

Tunneling experience from the construction of the North Ramp was considered in the characterization of the Topopah Spring middle nonlithophysal zone (Tptpmn). Rock mass quality data were collected along scanlines in the Tiva Canyon Tuff (Tpc) of the North Ramp and compared to the North Ramp core-based rock quality assessments. Data from the Tiva Canyon welded tuff, excluding the high lithophysal portion, were assumed to have characteristics similar to the Tptpmn. Based on this comparison, adjustments were made to the rock quality parameters not directly derived from the core to attempt to incorporate the observed field conditions.

1.3 Scope

This report provides a geological and geotechnical characterization of the ESF Main Drift. The primary focus of this characterization is to assess the variability of rock mass quality of the Tptpmn for input to the design and the construction of the Main Drift. A geologic cross

section along the Main Drift is presented to provide the stratigraphic context of the rock properties data. Geologic description is limited to the middle nonlithophysal zone.

No new surface mapping was conducted as part of this study. Description of the faults in the vicinity of the Main Drift is based primarily on surface mapping by Scott and Bonk (1984) and recently reported results of the ongoing studies of faults by the USGS reported by Spengler et al. (1994).

Rock mass quality data in the immediate area of the Main Drift alignment was produced in three of the SD program holes, USW SD-7, SD-9, and SD-12, for direct input to this study. Since the spacing of these holes was large (>920 m; 3,018 ft), the data set from the Tptpmn was augmented by using all other available rock structure logging data (boreholes NRG-6, NRG-7/7A, and UZ-14). Because of the limited data, spatial correlation of the rock mass quality trends was not performed, and the variability of rock mass quality was therefore examined by stratigraphic depth in the unit.

The soil and rock study plan includes site characterization studies and activities required for siting and designing the ESF, including both surface structures and subsurface access structures. Table 1-1 lists the individual studies within the study plan, their objectives, and the activities included in each study. The investigation activities conducted during the Main Drift geotechnical characterization supported all three of the studies in Table 1-1.

Table 1-1. Studies, Objectives, and Activities of the Soil and Rock Properties Study Plan (8.3.1.14.2) — Studies to Provide Soil and Rock Properties of Potential Locations of Surface and Subsurface Access Facilities*

SCP Activity No.	Study	Objectives	Activities
8.3.1.14.2.1	Exploration Program	Characterize soil and rock conditions that influence ESF construction.	Site Reconnaissance Preliminary and Detailed Exploration
8.3.1.14.2.2	Laboratory Tests and Material Property Measurements	Conduct laboratory tests and material property measurements on representative samples of soil and rock.	Physical Properties and Index Laboratory Tests Mechanical and Dynamic Laboratory Property Tests
8.3.1.14.2.3	Field Tests and Characterization Measurements Study	Conduct field tests and characterization measurements to determine in situ physical, mechanical, and dynamic properties of soil and rock.	Physical Property Field Tests and Characterization Measurements Mechanical Property Field Tests Geophysical Field Measurements

*DOE, 1991.

Table 1-2 correlates study activities with specific investigations conducted during geotechnical characterization for the Main Drift. The objectives of each study are also summarized in the table.

Table 1-2. Correlation of Study Areas and Activities with Specific Investigations Conducted in the Main Drift

Study	Activity	Investigation	Objective
Exploration Program	Preliminary and Detailed Exploration	Drill SD-7, SD-9, SD-12, UZ-14, NRG-6, and NRG-7/7A.	Determine depth, thickness, and continuity of strata and thermal-mechanical (thermal-mechanical) units intersected by North Ramp cross section.
		Perform down-hole video logs.	Provide visual estimate of rock quality, fracturing density, detect free water.
		Perform geophysical logging.	Stratigraphic correlations in new holes.
Laboratory Tests and Materials Property Measurements	Physical Property and Index	Laboratory Measurements of Physical Properties—density, porosity, grain density.	Characterize bulk properties of rock for engineering designs of materials handling facilities; verify geophysical tool functions.
	Mechanical and Dynamic Laboratory Property Tests	Laboratory Mechanical Property tests—uniaxial compressive strength, triaxial strength, elastic modulus, Poisson's ratio, Brazilian tensile strength.	Measure intact rock properties to provide basis for rock mass quality assessment and rock mass mechanical properties.
	Physical Property Field Tests and Characterization Measurements	Rock Structural Logging	Describe rock structural features to support development of rock mass quality indices.
Field Tests and Characterization of Measurements		Generate Rock Mass Classification—Q and RMR	Provide basis for empirical design of tunnel support, provide basis for developing rock mass mechanical properties.
	Mechanical Property Field Tests	Generate Rock Mass Mechanical Property Estimates—Strength and Modulus	Provide design parameters for numerical analysis of thermal and seismic loading.

1.4 Quality Assurance

All core logging and rock testing data utilized in this study were generated under quality assurance (QA) procedures governing the various technical organizations involved in the activities. Data collection and collation, supporting preparation of this report, were documented in scientific notebooks and analysis files in accordance with SNL Quality Assurance Implementing Procedures (QAIPs) 20-2 and 2-4. These notebooks will be entered into the SNL participant data archive. All data presented in this report were generated under QA procedures unless otherwise noted.

Nonqualified existing data and preliminary data have been utilized in this report where qualified data do not exist or are not currently available. Table 1-3 has been developed to document these occurrences and to meet requirements of the DOE's Quality Assurance Requirements and Description for maintenance of traceability. Throughout the text, some footnotes have been utilized to refer to information relevant to the Main Drift which is in

Table 1-3. Nonqualified and Preliminary Data and Assumptions

Data or Assumptions	Data Status	Application	Data Reference	Effects
Geologic Cross Section along Main Drift	N*	Presentation of lithostratigraphic units along Main Drift, Figure 3-1	Basis of development is nonqualified 3-D geologic model of YMP site, Version YMP.R2.0	Projection of geologic contacts between SD holes, fault displacements, Table 3-3
Thermal-Mechanical Units Cross Section Figure 3-2	N*	Presentation of thermal-mechanical units along North Ramp	Basis for development is Figure 3-1	Figure 3-2

*N = Nonqualified existing data.

preparation and represents preliminary data. Other footnotes refer to qualified data submitted to the project by Technical Data Information Form (TDIF), but not assigned accession numbers required for listing in the references. These TDIF references are presented in Appendix A.

1.5 Report Organization

Following this introduction, Section 2.0 of the report presents the summary of the geotechnical characterization of the Main Drift. A description of the geology along the Main Drift is provided in Section 3.0. The geotechnical data, including rock structure data and rock mechanics laboratory test data, are presented in Section 4.0. The rock mass quality based on the geotechnical data in Section 4.0 is presented in Section 5.0. Section 6.0 presents an assessment of the rock mass mechanical properties. References are presented in Section 7.0.

Appendix A includes a list of TDIF references used in this report. Appendix B contains a rank-ordered table of rock mass quality estimates for the Tipton. Individual data and logs for boreholes USW SD-7, SD-9, SD-12 and UZ-14 are presented in Appendix C including:

- Geology and Rock Structure Log,
- Core Hole Structural Data Summary, and
- Estimated Rock Mass Quality Indices Based on Core Log Data.

Appendix D contains a key block stability analysis comparison of the North Ramp and Main Drift orientations.

2.0 Summary and Conclusions

2.1 Introduction

This section summarizes the subsurface rock conditions anticipated in the Main Drift and the impact these conditions may have on construction. Since the method of excavation and tunnel alignment have been previously chosen, this report focuses on the prediction of the rock mass characteristics and properties, and the identification of the required range of ground support. The Main Drift will be excavated between the North and South Ramps at the potential repository horizon for a distance of 3,131 m (10,273 ft) using a 7.62-m (25-ft) diameter TBM. Portal and starter tunnel facilities were completed in mid-1994 and the excavation of the North Ramp had reached 960 m at the time of preparation of this report.

The Main Drift is projected to be excavated almost entirely within the Tptpmn with only the last 237 m excavated in the Topopah Spring lower lithophysal zone (Tptpll). The geotechnical data in this report are limited to these two zones and are derived from the ESF boreholes USW NRG-6, NRG-7/7A, UZ-14, SD-7, SD-9, and SD-12. The data evaluated included lithologic and stratigraphic identifications, rock structural logs, and rock mechanics tests. Rock mass quality was then projected using core data. Geotechnical data collected during construction of the North Ramp were also used to improve the interpretation of the core hole data.

The data collection and analysis methodology used throughout are described by Brechtel et al. (1995). However, rock mass quality assessments from the North Ramp tunnel in the Tiva Canyon formation were compared to the rock mass quality predicted from the North Ramp core data to check the performance of the core-based rock quality assessment. Some parameter ranges used to estimate rock quality for the Main Drift were changed on the basis of the North Ramp experience. In addition, rock mass quality from the high lithophysae portion of the Tiva Canyon and from the "imbricate" faults intersected by the North Ramp were used to project conditions in the Tptpll and fault zones, respectively.

2.2 Geotechnical Summary

2.2.1 Geology and Major Structural Features Along the Main Drift

The Main Drift will be constructed in the Tptpmn for approximately 2,894 m (9,495 ft), and for 237 m (776 ft) in the Tptpll, both of which are zones of the Topopah Springs Tuff (Tpt), a welded volcanic ash-flow tuff of the Miocene Paintbrush group. There are two known major

structural geologic features with potential engineering and construction significance that are projected to be intersected by the Main Drift:

- the Sundance Fault Zone and
- the Abandoned Wash Fault.

Projected intersections with the Main Drift are shown in Section 3.0, Figure 3-1. No data is available on these faults at depth; however, tunneling experience in the North Ramp indicates low values of rock mass quality ($Q \leq 0.04$) can occur in the localized zone of shear movement within faults. Observed structural instability in faults has included rock fallout and instability in the crown with very low stand-up times for the newly excavated unsupported roof. In one fault zone within the North Ramp, the TBM was unable to set the gripper pads in areas of extreme rock fallout.

The Abandoned Wash Fault is a north-northeast trending fault that appears to terminate against the Ghost Dance Fault (Scott and Bonk 1984) and is considered a possible splay off the major fault. It has an approximate 74° W dip and 21 m (70 ft) of projected dip-slip displacement where it is projected to intersect the Main Drift at station 57+10 m. A parallel fault is shown on surface mapping (Section 3.0, Figure 3-4) to cross the Main Drift to the north of the Abandoned Wash Fault at approximately 54+96 m. These faults are projected to cut the tunnel at angles as low as approximately 14° which will result in the persistence of the fault zone along the tunnel for some distance. A fault in the North Ramp with a similar low angle of incidence caused construction delays.

The Sundance Fault System is a northwest trending feature with an apparent right-lateral offset of the Ghost Dance Fault of at least 52 m (Spengler et al. 1994) (Section 3.0, Figure 3-4). On the surface, this fault system consists of a zone of near vertically dipping faults at least 274 m (900 ft) wide with the dominant feature, the Sundance Fault, located at the center of the zone. The Sundance Fault is projected to cross the Main Drift alignment at station 36+40 m. Observations of the structural influence of the "imbricate" faults in the North Ramp (500–750 m) indicate that the brittle, densely welded tuff rocks exhibit a larger area of fault influence than in moderately or nonwelded tuffs. Rock damage adjacent to faults was more extensive in the densely welded tuffs. On this basis, the Sundance Fault zone is projected to have rock qualities similar to the lower 25% of the Tptpmu, with Q values projected to be between 0.04 and 0.3 through the 274-m (900-ft) area around the fault.

2.2.2 Joint Structure

The anticipated fracture patterns in the Tpt have been based on the general agreement of fracture data from both the Tpc and Tpt. Fracture data sources included oriented core data from both the Tpt and Tpc (Lin et al. 1993b),⁴ observations from the North Ramp Starter Tunnel, mapping of the Tpc in the North Ramp Tunnel, and mapping of the Tpt at Fran Ridge.⁵ The Tpc

⁴Existing data, not qualified.

⁵Preliminary data.

and Tpt , very similar in terms of rock properties, were deposited within a relatively short period of geologic time and have been subjected to the same post-emplacement tectonic stresses. The various fracture orientation data indicate similar trends in the two tuff units and it has, therefore, been assumed that the predominant joint sets observed in the Tpc of the North Ramp tunnel will be present in the Tpt of the Main Drift. Three steeply dipping joint sets are projected to occur oriented at $353^{\circ}/84^{\circ}$, $132^{\circ}/82^{\circ}$, and $262^{\circ}/78^{\circ}$ (dip direction/dip). The most frequently occurring joint set ($353^{\circ}/84^{\circ}$) strikes generally parallel to the Main Drift. This set is also generally parallel to the Ghost Dance Fault, which runs parallel to the Main Drift, approximately 170 m (558 ft) to the east. The joint set is projected to have an adverse impact on stability because of its generally parallel orientation. An analysis of the potential to form blocks that can fall from the tunnel crown (key blocks), based on these three predominant sets, indicates the maximum size key block may be approximately three times larger than in the North Ramp.

2.2.3 Hydrology

The Main Drift drilling indicated generally dry conditions along the Main Drift alignment and tunnel excavation is therefore anticipated to be in unsaturated conditions. Review of the borehole video logs from USW SD-7, SD-9, and SD-12 did not indicate any water inflow of significance to construction activities. However, perched water does occur at the YMP site, and it is possible that drilling has not sampled existing perched water along the Main Drift.

2.2.4 Rock Structure Data from the Main Drift Core

Analysis of the condition of the core from the Tptpmn was performed to project the rock mass quality. Combining the data from each of the boreholes, the amount of lost core for the Tptpmn was 15% of the total core length. Rubble zones accounted for 20% of the total length. The Tptpll to be intersected by the Main Drift was characterized by consistently higher core losses and rubble. For example, in the 24 m below the base of the Tptpmn, NRG-6 averaged 47% lost core and rubble, while NRG-7/7A averaged 77% lost core and rubble.

RQD (Deere 1968) determined for the Tptpmn is summarized in Section 4.1.2, Table 4-2, and averaged 23%. An *enhanced-RQD* was also calculated by filtering the effects of fractures judged to be coring induced and averaged 38%. The relative rock quality (Deere 1968) based on the mean RQD is very poor. The *enhanced-RQD* ranges from 1.5 to 2.6 times greater than the RQD suggesting poor rather than very poor rock quality.

A cross-hole comparison of RQD was developed for the six available holes to evaluate the potential for stratigraphically based variation of rock quality. This comparison (illustrated by Figure 4-4 in Section 4.1.2) suggested that three zones of low RQD occur at the top and middle of the Tptpmn and in the upper portion of the Tptpll. The lower part of the Tptpmn was a correlatable zone of higher RQD with a vertical thickness of approximately 20 m. The portion of the Tptpll to be intersected by the Main Drift was an interval with consistent high core loss and

rubble (47% from NRG-6 and 77% from NRG-7/7A), very low RQD (<8%), and irregular hole condition. Approximate Main Drift stations for these zones are listed in Section 4.1.2.

The weathering of the rock that constitutes the fracture surfaces (Section 4.1.3) has been described as either fresh or slightly weathered, with rock hardness primarily described as hard.

After correcting for sampling bias induced by the vertical holes using Terzaghi's (1965) correction procedure, it was found that fractures (Section 4.1.5) in the 80° to 90° dip range were the most dominant with a frequency of occurrence of 66.9%. The fracture surfaces in the Tptpmn were primarily clean. The most predominant infill materials included white crystalline (8%), white non-crystalline (10%), and black dendritic (17%). Clay infill in this zone were very scarce. The fractures were predominantly planar (66%) with a significant occurrence of irregular surfaces (21%). The small-scale roughness of the fractures was described as either moderately rough (50%) or smooth (39%).

The majority of the fractures identified in the core were judged to be coring-induced (type C) by the core loggers and represented almost half of the total fractures. These fractures were predominantly near horizontal and were not considered in assessing fracture characteristics.

2.2.5 Intact Rock Mechanical Properties

Rock mechanical properties tests were conducted on core from USW NRG-6 and NRG-7/7A in the Tptpmn. The rock mechanics laboratory test data are summarized in Table 2-1 and indicate that the rock was generally high strength, densely welded tuff. The porosities were relatively low, averaging 11%. Uniaxial compressive strength varied between 112.1 MPa (16,255 psi) and 261.9 MPa (37,975 psi) with a standard deviation equal to 29.2% of the mean

Table 2-1. Summary of Mean Values for Rock Mechanics Laboratory Test Data

Rock Property	Number of Tests	Mean Value	Standard Deviation
Uniaxial compressive strength (MPa)	13	179.80	52.50
Elastic modulus (GPa)	27	32.90	3.80
Cohesion (MPa)	13	42.50	—
Angle of internal friction (degrees)	13	49.60	—
Poisson's ratio	27	0.21	0.03
Indirect tensile strength (MPa)	7	11.40	3.20
Dry bulk density (g/cc)	36	2.25	0.08
Porosity (%)	38	11.00	3.20
Average grain density (g/cc)	18	2.53	0.01

strength of 179.8 MPa (26,070 psi). The intact elastic modulus averaged 32.9 GPa (4.77×10^6 psi) with an average Poisson's ratio of 0.21.

Confined testing was performed on small samples at confining pressures of 0, 5 and 10 MPa. Analysis of the data indicated a Mohr-Coulomb cohesion of 42.5 MPa (6,160 psi) and an angle of internal friction of 49.6° . Data are presented in Section 4.2.

2.2.6 Rock Mass Quality Indices

Rock mass quality indices, Q and RMR, were estimated for each 3-m (10-ft) interval of the Main Drift borehole data (boreholes USW SD-7, SD-9, SD-12, UZ-14, NRG-6, and NRG-7/7A) based on the described condition of the core and the rock mechanics laboratory test data. Values for two of the Q parameters, Jn and SRF, were generated using Monte Carlo simulation of distributions determined from rock quality assessments from within the North Ramp Tunnel in the Tpc. Fault zones were not specifically represented in the borehole rock quality estimates because none of the holes penetrated the fault zones. Fault conditions were therefore estimated separately based on observations in the North Ramp.

2.2.6.1 RMR and Q Data. The distribution of RMR and Q data was summarized by generating values for the Tptpmn corresponding to rock mass quality at levels of 5%, 20%, 40%, 70%, and 90% cumulative frequency of occurrence and are listed in Table 2-2. These levels of occurrence are used to generate a range of estimated rock mass mechanical properties. The values of Q or RMR at other cumulative frequency of occurrence can be read from the table in Appendix B.

Table 2-2. RMR and Q Values at Five Levels of Cumulative Frequency of Occurrence

Cumulative Frequency of Occurrence (%)	RMR	Q	Relative Rating		
			Rock Mass Quality	RMR	Q
5	50	0.14	Very Good	81-100	40-100
20	55	0.29	Good	61-80	10-40
40	58	0.42	Fair	41-60	4-10
70	63	1.39	Poor	21-40	1-4
90	67	10.56	Very Poor	<20	0.1-1

The range of RMR values for the Tptpmn is fairly small, with all intervals indicating either a fair or a good rock mass quality. The Q values range from a very poor to a good rock mass quality, with a majority of the intervals (69%) indicating a poor to very poor quality rock mass.

The core-based projections of Q from the North Ramp core data (Brechtel et al. 1995) were compared to Q values assessed from the North Ramp Tunnel excavation to verify the

methodology for determining Q and RMR from core data. The distribution of Q values was similar for both the core-based and North Ramp excavation assessments in the Tpc with the actual rock quality in the tunnel being lower than predicted. The support requirements based on the YMP Ground Support Guidelines⁶ have also been compared for both core-based and tunnel Q assessments. The distribution of support categories in both assessments was nearly identical which demonstrated that the core-based rock quality assessment had provided a realistic pre-excavation assessment of the rock mass quality that was generally well matched with field conditions observed in the Tpc.

The core rock structure data were not assembled for the portion of the Tptpl because of the high proportion of lost core and rubble. Based on the rubblized nature of the core and the presence of large lithophysae in the downhole video, the conditions are projected to be similar to the upper lithophysal zone of the Tpc. Q values ranged between 0.04 and 2.68 with a median value of 0.64 in the scanline rock mass quality descriptions of the North Ramp in the Tiva Canyon upper lithophysal zone.

2.2.6.2 Projected Range of Ground Support. The distribution of Q values and associated Q parameters (RQD/J_n and J_r/J_n) were used to identify the types of ground support indicated by the YMP Ground Support Guidelines and the relative lengths of the Main Drift that will require the indicated support. Actual ground support will be controlled by the specific capabilities of the TBM and the constructor's assessment of specific requirements for personnel safety. The distribution of the anticipated ground support for the Tptpmn in the Main Drift is shown in Figure 2-1 (ground support categories are defined in Section 5.4, Table 5-3). According to this analysis and the YMP support guidelines, 46% of the tunnel length will require rockbolts and shotcrete (category 3b) and 36% of the tunnel will require steel sets with partial lagging (category 4). Ground support requirements in the Tptpl in the Main Drift are projected to be category 4—steel sets and partial lagging—based on the consistently low RQD.

2.2.7 Rock Mass Mechanical Properties Estimates

Rock mass mechanical properties are required for input into the numerical analyses that support the geotechnical design of the Main Drift. Rock mass mechanical properties have been estimated for the Tptpmn based on the methodology proposed by Hardy and Bauer (1991) using published empirical correlations with RMR. Estimated rock mass strength for each of the five cumulative frequencies of occurrence (5%, 20%, 40%, 70%, and 90%) of RMR data is compared to intact rock strength in Table 2-3. The estimated rock mass strength represents a substantial reduction from the laboratory measurements of intact rock compressive strength that is based on empirical correlation with RMR. The method of estimating rock mass strength has not been validated and requires future ESF testing for validation.

⁶BABEAB000-01717-2100-40151-01, *Exploratory Studies Facility Package 2C, TS North Ramp Ground Support Master Elevations and Sections*, July 27, 1994.

Figure 2-1. Projected distribution of ESF ground support category for the Tptpmn—Main Drift boreholes.

Table 2-3. Comparison of Intact Rock Values to Estimated Rock Mass Property Values for Each of the Five Rock Mass Classes

Rock Mass Property	Intact Rock Values	Estimated Rock Mass Values for Cumulative Frequency of Occurrence of RMR				
		5%	20%	40%	70%	90%
Rock strength (MPa)	179.8	3.7	5.19	6.28	10.17	20.19
Cohesion, C (MPa)	42.5	1.1	1.4	1.6	2.2	4.1
Internal friction angle, ϕ (degrees)	49.6	49	49	50	50	50
Dilation angle (degrees)	25	25	25	25	25	25
Elastic modulus (GPa)	32.90	5.07	7.01	8.40	13.23	25.03
Poisson's ratio	0.21			0.21		

Rock mass strength parameters based on the Mohr-Coulomb failure criteria were determined for each of the five frequencies of occurrence as listed in Table 2-3 for the Tptpmn. Rock mass elastic modulus and the recommended value of Poisson's ratio are also listed in Table 2-3.

2.3 Conclusions

The major conclusions developed from this assessment are:

- The available subsurface data on rock structural features and rock quality appears adequate to characterize the range of conditions that will be encountered excluding the known fault zones. Cross-hole evaluation of RQD suggests some correlatable intervals of higher and lower RQD based on the distance from the top of the Tptpmn.
- There is no data on the rock characteristics in and around the two known fault zones to be intersected by the Main Drift. The width of the poor rock quality zones within the faults and the rock quality in the fault zone is unknown. The angle of incidence of the Abandoned Wash structure is low and adverse conditions associated with the fault zone could persist for some distance.
- The tuff rocks to be encountered by the Main Drift are highly fractured and have generally low rock mass quality. Rock conditions are projected to be similar to those encountered in the densely welded portions of the Tpc in the North Ramp.
- The predominant joint sets projected to occur in the Main Drift have the potential to produce unstable blocks in the roof that are approximately three times larger than in the North Ramp. This potential, coupled with the fact that the Main Drift is oriented parallel to the joint set that is the most frequently occurring, suggests that stability conditions may be more adverse in the Main Drift than in the North Ramp.
- Fault zones have not been directly characterized by the Main Drift subsurface investigations. Two major faults are identified by surface mapping, but other unmapped faults may also be present as was the case in the North Ramp.

3.0 Geology of the Main Drift

3.1 Introduction

This section provides the geologic and stratigraphic framework for the rocks encountered along the ESF Main Drift alignment. Geologic investigation of the alignment included lithologic description of core from boreholes USW SD-7, SD-9, and SD-12; analysis of geologic mapping done by Scott and Bonk (1984); and fault mapping studies by Spengler et al. (1994).

The objective of the geologic investigation of the Main Drift alignment, using the Main Drift boreholes and existing surface mapping data, was to:

- develop stratigraphic and thermal-mechanical cross sections along the drift alignment;
- locate and describe any significant faults that may cross the alignment; and
- correlate rock structure data, rock mass quality data, and rock mass properties data with the stratigraphic unit containing the Main Drift.

3.2 Stratigraphy

The ESF Main Drift alignment is planned to be excavated within the middle nonlithophysal zone of the Tpt of the Paintbrush Group. Drilling of the three SD boreholes along the drift alignment penetrated the Miocene age volcanic rocks of the Paintbrush Group, Calico Hills Formation, Prow Pass, and Bullfrog Members of the Crater Flat Tuff. The stratigraphic units found along the alignment are part of a thick sequence of bedded and ash-flow tuffs which originated in eruptions of the Timber Mountain-Oasis Valley Caldera Complex to the north of Yucca Mountain between 11 and 14 million years ago (Byers et al. 1976). The Tptm of the Paintbrush Group is the host rock for the majority of the Main Drift excavation. Litho-stratigraphic units have been described by Moyer et al. (1995).⁷

This report uses the recently developed stratigraphic nomenclature of the U.S. Geological Survey.⁸ Recent work by the USGS has modified the stratigraphy by raising the Paintbrush and Timber Mountain Tuffs to group status (Sawyer et al. 1994). The detailed nomenclature for the

⁷ Moyer, T.C., J.K. Geslin, and D.C. Buesch (1995). *Summary of Lithologic Logging of New and Existing Boreholes at Yucca Mountain, Nevada, July 1994 to November 1994*, U.S. Geological Survey Open-File Report 95-102, U.S. Department of the Interior, Denver, Colorado.

⁸ Ibid.

Tpt, based on compositional and lithologic distinctions identified in core and less on outcrop data, has been developed by the USGS⁹ and is presented in Table 3-1.

Table 3-1. Lithostratigraphic Nomenclature of the Tpt at Yucca Mountain, Nevada*

Topopah Spring Tuff	Tpt-
<u>crystal-rich member (quartz latite)</u>	<u>Tptc</u>
vitric zone	Tptrv
non- to partially welded subzone	Tptrv3
moderately welded subzone	Tptrv2
vitrophyre subzone	Tptrv1
nonlithophysal zone	Tptrn
lithophysal zone	Tptrl
crystal-rich lithophysal subzone	Tptrl2
crystal transition subzone	Tptrl1
<u>crystal-poor member (high-silica rhyolite)</u>	<u>Tptp</u>
upper lithophysal zone	Tptpul
cavernous lithophysae subzone	Tptpul2
small lithophysae subzone	Tptpul1
middle nonlithophysal zone	Tptpm
upper subzone	Tptpmu
lithophysae bearing subzone	Tptpmst
lower subzone	Tptpml
lower lithophysal zone	Tptpll
lower nonlithophysal zone	Tptpln
vitric zone	Tptpv
vitrophyre subzone	Tptpv3
moderately welded subzone	Tptpv2
non- to partially welded subzone	Tptpv1

NOTE: The lithostratigraphic nomenclature above and below the Topopah Spring Tuff is listed in Table 4-1 of Brechtel et al. (1995) *The Geotechnical Characterization of the North Ramp of the Exploratory Studies Facility*, SAND95-0488, Volume 1, Sandia National Laboratories, Albuquerque, NM.

* Moyer et al.

This scheme uses both primary compositional differences and secondary cooling and alteration features to define the stratigraphy. It is important to note that secondary features such as lithophysae and vapor-phase alteration are dependent more on cooling history of the rock mass and can crosscut the primary features such as boundary between crystal-rich and crystal-poor

⁹Ibid.

zones. Furthermore, these secondary features commonly exhibit significant lateral variation, dependent on variations in cooling history.

Boreholes USW SD-9 and SD-12 have been logged by both the USGS¹⁰ and SNL.¹¹ Stratigraphic contacts are gradational and subject to interpretation and result in minor differences in contact identification. Additionally, minor differences in nomenclature are noted as well. Borehole USW SD-7 has been logged by SNL.¹² Lithology logs produced by SNL are incorporated directly into the Geology and Rock Structure Logs developed in this study. Geologic and thermal-mechanical cross sections in this report are derived from the USGS three-dimensional Lynx model version YMP.R2.0¹³ which uses the contact elevations defined by USGS personnel.

Stratigraphic and thermal-mechanical units that were sampled within the Main Drift boreholes are summarized in Table 3-2, which lists the unit thicknesses penetrated by drilling. All of these boreholes penetrate the entire thickness of the Tpt. Description of the stratigraphic units is restricted to the Tpt for this report.

The Tpt is a multiple-flow, compound cooling unit, ash-flow tuff consisting of three eruptive pulses (Lipman et al. 1966). This unit has been divided into a lower crystal-poor unit (high-silica rhyolite) and an upper crystal-rich unit (quartz latite).¹⁴ The unit is characterized by thin zones at the top and bottom where the nonwelded tuffs grade into moderately to densely welded vitrophyre zones. The thick middle portion of the flow is moderately to densely welded, devitrified, and commonly altered by vapor-phase mineralization.

Lithophysal cavities vary throughout and break the unit into a number of distinct zones which help define both the lithostratigraphic and thermal-mechanical units. The vitric zones on the top and bottom of the flow are both nonlithophysal. The thick, devitrified middle portion of the flow, however, contains an alternating sequence of nonlithophysal and lithophysal zones, as listed in Table 3-1. While the term nonlithophysal is applied to many of the zones, it should be pointed out that minor amounts of lithophysae occur throughout the devitrified portion of the flow. These can sometimes be used to define distinct subzones, such as the lithophysal bearing subzone in the Tptpmn.

¹⁰Ibid.

¹¹Geologic Core Log for SD-9, TDIF No. 303743 DTN: SNF02052794001.001 and TDIF No. 304282 DTN: SNF02052794001.002; and Geologic Core Log for SD-12, TDIF No. 303744 DTN: SNF02012894001.001.

¹²Geologic core log for SD-7, DTN: SNT02110894001.001.

¹³Buesch, D.C., J.E. Nelson, R.P. Dickerson, R.M. Drke, and C.A. San Juan. (1996). *Distribution of Lithostratigraphic Units Within the Central Block of Yucca Mountain, Nevada: A Three-Dimensional Computer-Based Model, Version YMP.R2.0, Open-File Report 95-124*, U.S. Geological Survey, Denver, CO.

¹⁴Moyer et al.

Table 3-2. Thickness of Stratigraphic Units in Main Drift Boreholes

Stratigraphic Unit	Symbol	Thermal-Mechanical Units	Thickness (m)		
			SD-7	SD-9	SD-12
Paintbrush Group:					
Tiva Canyon Tuff	Tpc-				
welded zones, undivided	Tpcu	TCw	93.1*	17.4*	72.9*
crystal-poor vitric zone	Tpcpv	PTn	6.2	10.7	7.4
Pre-Tiva Canyon Tuff Bedded Tuff	Tpbt4		#	1.1	1.4
Yucca Mountain Tuff	Tpy		#	13.7	NP
Pre-Yucca Mountain Tuff Bedded Tuff	Tpbt3		#	4.8	3.0
Pah Canyon Tuff	Tpp		#	21.4	3.9
Pre-Pah Canyon Tuff Bedded Tuff	Tpbt2		#	8.8	7.0
Topopah Spring Tuff	Tpt-				
<u>crystal-rich member (quartz latite)</u>	Tptr-				
vitric zone, moderately & non- to partially welded	Tptrv 3 & 2		7.5	3.9	3.2
vitric zone, vitrophyre subzone	Tptrv1	TSw1	0.3	1.1	1.9
nonlithophysal zone	Tptrn		30.3	50.9	32.2
lithophysal zone	Tptrl		NP	13.7	12.2
<u>crystal-poor member (rhyolite)</u>	Ttp-				
upper lithophysal zone	Ttpul		59.3	77.0	57.1
middle nonlithophysal zone	Ttpmn	TSw2	36.8	33.2	38.1
lower lithophysal zone	Ttpll		66.1	103.6	76.9
lower nonlithophysal zone	Ttpln		52.2	54.6	72.3
vitric zone, vitrophyre subzone	Ttpv 3	TSw3	25.3	16.3	9.1
vitric zone, moderately & non- to partially welded	Ttpv 2 & 1	CHn	#	13.9	30.5
Pre-Topopah Spring Tuff Bedded Tuff	Tpbt1		#	4.8	1.1
Calico Hills Formation:	Tac				7.3*
Prow Pass Tuff:	Tcp		61.0*	103.9	
Bullfrog Tuff:	Tcb			122.6*	

*Denotes thickness of unit where both contacts not present.

NP = Unit not Present

= Unit thickness not calculated due to very limited or no recovery.

The Tptpmn is the horizon in which the Main Drift will be excavated. The thickness ranges from 33.2 m (109 ft) at SD-9, 38.1 m (125 ft) at SD-12, and 36.8 m (120.8 ft) at SD-7. This unit is rhyolitic in composition, devitrified, and moderately to densely welded. Phenocrysts form 1% to 2% of the rock and are dominated by feldspars with rare oxidized biotite. Pumice clasts and lithic clasts are present and each comprise 1% to 2% of the rock. Vapor-phase alteration is present in 5% to 20% of the rock as wisps, diffuse spots, and rims around lithophysae where present. Matrix colors typically range from light brown (2.5YR6/3) to grayish red-purple (5RP4/2) to moderate brown (5YR5/4).

Lithophysae are rare but not entirely absent. The USGS¹⁵ recognizes three subzones based largely on lithophysal content as follows:

- the lower nonlithophysal subzone in which lithophysae are absent or less than 1%,
- the middle lithophysae bearing subzone characterized by 1–3% of spherical lithophysae typically less than 30 mm in size, and
- the upper nonlithophysal subzone where lithophysae are once again absent to less than 1%.

Within the SD boreholes in this report, the middle lithophysae bearing subzone is not recognized in SD-12 and SD-7, but is seen in SD-9 and in the supplemental holes NRG-6, NRG-7/7A, and UZ-14. This suggests that this subzone will be found at the north end of the Main Drift alignment, but dies out to the south.

The cross section shown in Figure 3-1 shows the north end of the Main Drift to be just below the upper contact of the Tptpmn. As the Main Drift proceeds to the south, it will gradually penetrate deeper to near the base of this zone as it approaches the Abandoned Wash Fault. South of the Abandoned Wash Fault, the Main Drift will be below the lower contact of the Tptpmn in the Tptpll based on the thickness of this unit observed in SD-12 and SD-7 (contact not defined on cross section).

The Tptpll is characterized by extensive zones of lost core and rubble in the boreholes along the Main Drift. The thickness ranges from 104 m (340 ft) at SD-9, 77 m (252 ft) at SD-12, and 66 m (217 ft) at SD-7. This zone is densely welded and devitrified, with vapor-phase minerals lining the lithophysal cavities and extensive haloes of vapor-phase alteration (5–30% of rock volume). Matrix colors are typically light brown to moderate red, and phenocrysts of feldspar and rare oxidized biotite comprise 1–2% of the rock. Pumice and lithic clasts are present at percentages ranging from 1 to 7%.

Intact pieces of core typically show from less than 1% to several percent of lithophysal cavities. Actual percentages, however, are hard to estimate from the limited recovery and are likely much higher, on the order of 20% or more as estimated from downhole videotapes. The cavities are typically elongate, from 2 to 10 cm, but occasionally as large as 20 cm or more.

¹⁵Ibid.

This page intentionally left blank.

BOREHOLE PROJECTIONS (projected perpendicular to section)

Borehole	Projected to Section Line (meters)	Depth (m)	Projected to Section (m)
USW SD-7	100	1000.0	100.0
USW SD-8	100	1000.0	100.0
USW SD-9	100	1000.0	100.0

* Based on preliminary survey data

BOREHOLE CONTACT PROJECTIONS (projected down dip)

Borehole	Projected to Section Line (meters)	Dip (°)	Projected to Section (m)
USW SD-7	100	7.5	100.0
USW SD-8	100	8.0	100.0
USW SD-9	100	7.5	100.0

* Based on preliminary survey data

Note: Core Samples based on USGS LYXK Model YAP.R2.0. Not qualified data. Projections of stratigraphic contacts from USW SD-7, USW SD-8 and USW SD-9 are along dip direction as derived from Model YAP.R2.0 for each borehole locality.

PRELIMINARY TS MAIN DRIFT DATA

Station (ft)	Elev (ft)	TS Elev (ft)
Station 100	1000.0	1000.0
Station 200	1000.0	1000.0
Station 300	1000.0	1000.0
Station 400	1000.0	1000.0

* Estimated

STRATIGRAPHY¹

LITHO- STRATIGRAPHIC UNITS	SYMBOL	THERMAL- MECHANICAL UNITS
Two Canyon Tuff; undifferentiated, darkified	Tpoun	TDw
Two Canyon Tuff; crystal-poor, vitro, non-welded to moderately welded	Tpov1 & 2	
Pre-Two Canyon Tuff Bedded Tuff	Tpbt4	
Yucca Mountain Tuff	Tpy	
Pre-Yucca Mountain Tuff Bedded Tuff	Tpbt3	
Pal Canyon Tuff	Tpp	
Pre-Pal Canyon Tuff Bedded Tuff	Tpbt2	
Topopah Spring Tuff; crystal-rich, vitro, non-welded to moderately welded	Tpbt2 & 3	
Topopah Spring Tuff; crystal-rich, darkified, non-illithophyal (includes vitrophyres)	Tpbtm	
Topopah Spring Tuff; crystal-poor, upper illithophyal (includes crystal-rich illithophyal)	Tpbtal	
Topopah Spring Tuff; crystal-poor, middle non-illithophyal	Tpbtm	
Topopah Spring Tuff; crystal-poor, lower illithophyal	Tpbtal	
Topopah Spring Tuff; crystal-poor, lower non-illithophyal	Tpbtal	
Topopah Spring Tuff; crystal-poor, vitrophyre subzone	Tpbtv3	
Topopah Spring Tuff; crystal-poor, vitro, non-welded to moderately welded	Tpbtv1&2	

PAINTBRUSH
GROUP

¹ Stratigraphic and thermal-mechanical units as defined by Busch, et al., USGS Open File Report 94-469, 1995. "Revised stratigraphic nomenclature and macroscopic identification of lithostratigraphic units of the Paintbrush Group exposed at Yucca Mountain, Nevada".

² All contacts for USW SD-7 are preliminary; contacts for Tpbv1 and Tpbv2 are anticipated. Recovery of non-welded units within Pin very poor. Yucca Mountain Tuff not recognized. Pal Canyon Tuff not found but may be present in unexposed intervals.

³ Pin View data from North Ramp Layout Calculation, document no. BAA30000-01717-0200-00000.

LEGEND

- + BOREHOLE CONTACTS BY BOREHOLES USW SD-9 ALONG DIP; QUALIFIED DATA
- + BOREHOLE CONTACTS BY BOREHOLE USW SD-7 ALONG DIP; PRELIMINARY DATA, LOGGED BY USGS.

COMPARISON OF CONTACT PROJECTED FROM BOREHOLE CONTACT ELEVATIONS FROM LYXK MODEL

Unit	Projected Contact Elev (ft)	LYXK Model Contact Elev (ft)	Diff (ft)	Unit	Projected Contact Elev (ft)	LYXK Model Contact Elev (ft)	Diff (ft)
TDw	1200.0	1200.0	0.0	Tpbt4	1200.0	1200.0	0.0
Tpov1	1200.0	1200.0	0.0	Tpbt3	1200.0	1200.0	0.0
Tpov2	1200.0	1200.0	0.0	Tpbt2	1200.0	1200.0	0.0
Tpbtm	1200.0	1200.0	0.0	Tpbt1	1200.0	1200.0	0.0
Tpbtal	1200.0	1200.0	0.0	Tpbtv3	1200.0	1200.0	0.0
Tpbtm	1200.0	1200.0	0.0	Tpbtv1&2	1200.0	1200.0	0.0

Note: Unit not recognized in any reported or cell in

SECTION VIEW

0 100 200m
SCALE

PLAN VIEW³

TS Main Drift
183° Azimuth

← USW SD-12

← USW SD-7

ED ON PROJECTING
SD USW SD-12
A, USGS OFR95-102.

ED ON PROJECTING
ING DIP:
G NOT REVIEWED

CT ELEVATIONS
HOLES AND
MEASURED
DEL

SD-7			
Station	Depth (m)	Core Depth (m)	Remarks
0+01	1200.0	1200.0	0.0
0+02	1200.0	1200.0	0.0
0+03	1200.0	1200.0	0.0
0+04	1200.0	1200.0	0.0
0+05	1200.0	1200.0	0.0
0+06	1200.0	1200.0	0.0
0+07	1200.0	1200.0	0.0
0+08	1200.0	1200.0	0.0
0+09	1200.0	1200.0	0.0
0+10	1200.0	1200.0	0.0
0+11	1200.0	1200.0	0.0
0+12	1200.0	1200.0	0.0
0+13	1200.0	1200.0	0.0
0+14	1200.0	1200.0	0.0
0+15	1200.0	1200.0	0.0
0+16	1200.0	1200.0	0.0
0+17	1200.0	1200.0	0.0
0+18	1200.0	1200.0	0.0
0+19	1200.0	1200.0	0.0
0+20	1200.0	1200.0	0.0

Interpolated by Core model.

Figure 3-1. Stratigraphic cross section along the ESF Main Drift

3.3 Geologic Cross Sections

The geologic cross section shown in Figure 3-1, was developed to project the stratigraphic units along the Main Drift alignment, and to serve as a basis for a thermal-mechanical units cross section presented in Section 3.4. The cross section uses contact elevations and geologic structures taken directly from the digital, three-dimensional lithostratigraphic computer model of Yucca Mountain, version YMP.R2.0, developed by the Rock Characteristics Section of the USGS.¹⁶ Model version YMP.R2.0 includes boreholes USW SD-7, SD-9 and SD-12 as well as USW G-4 and, therefore, is based on the best available stratigraphic data close to the Main Drift alignment. The lithostratigraphic units have been grouped in a way that allows exact correspondence to the defined thermal-mechanical stratigraphy, but introduces some irregularities in the hierarchy of lithostratigraphic divisions.

Contact elevation data from the Main Drift SD boreholes were projected onto the section to verify the elevations of the contacts from the computer model against the existing qualified data. Solid black lines representing the boreholes are projected at actual elevation along the shortest distance (perpendicular) into the section. Stratigraphic contact elevations are shown by blue crosses adjacent to the boreholes. These contacts were projected down the average stratigraphic dip from the borehole into the plane of the cross section. The average dip of the lithostratigraphic units was used because the available dip of the top of the Tptpmn is anomalously high where compared to units above and below. The local attitudes of this contact were derived from structure contour maps of the surfaces included in the documentation of the Lynx version YMP.R2.0 model.¹⁷

3.4 Thermal-Mechanical Stratigraphy

The volcanic rocks at Yucca Mountain display a relatively narrow variance in chemical composition, but a wide range in features dependent on temperature of emplacement and cooling history. The aspects which most affect the physical and mechanical properties are the degree to which the individual particles in the deposits have been fused together or "welded" by post-emplacement heat and pressure, measured by the degree of flattening of the pumice clasts, and the resulting porosity of the rock. Repository design efforts are based on thermal-mechanical units that are defined by similarities in rock mass thermal and mechanical properties, which are largely a function of the degree of welding and porosity.

The Main Drift boreholes penetrate six previously defined thermal-mechanical units (Ortiz et al. 1985). A chart correlating Yucca Mountain stratigraphy with the thermal-mechanical units is included in Figure 3-2, and a version of the Main Drift cross section showing only thermal-mechanical units is presented in Figure 3-3. The important contact between the Tsw1 and Tsw2 has been presented here as equivalent to the base of the crystal-poor upper lithophysal

¹⁶Ibid.

¹⁷Buesch et al.

Geologic Stratigraphy		Thermal Mech. Unit	Lithologic Description	Stratigraphic Units ¹
Paintbrush Group	Alluvium	UO	Alluvium, nonwelded ashflows and bedded tuffs	QTac, Tmr, Tmbt1, Tpk1, Tpb15, Tpcrv3, Tpcrv2
	Rainier Mesa Tuff			
	Tuff Unit "X"			
	Tiva Canyon Tuff	TCw	Nonlithophysal subzone	Tpcrv1, Tpcrv
			Lithophysae-bearing subzone	Tpcrv1, Tpcrv2, Tpcrv3, Tpcrv4, Tpcrv5
			Nonlithophysal subzone	Tpcrv1, Tpcrv2
	Yucca Mtn. Tuff	PTn	Vitric nonwelded	Tpcrv2, Tpcrv1, Tpb14, Tpy, Tpb13, Tpp, Tpb12, Tptrv3, Tptrv2
	Pah Canyon Tuff			
	Topopah Spring Tuff	TSw1 ²	Nonlithophysal subzone welded devitrified tuff lithophysae poor	Tptrv1, Tptrn
			Lithophysae bearing subzone welded devitrified tuff up to 25% lithophysal cavities by volume	Tptr1, Tptpl
		TSw2	"Nonlithophysal" (contains sparse lithophysae); potential subzone repository horizon	Tptpmn, Tptpl, Tptph
		TSw3	Vitrophyre	Tptpv3
	Calico Hills Formation	CHn1	Ashflows and bedded units, may be vitric or zeolitized	Tptpv2, Tptpv1, Tpb1, Tac

¹ New USGS nomenclature, Thomas C. Moyer, et al 1995, *ibid*.

² TSw1 basal contact is variously described as the base of the Tptpl stratigraphic unit, or as the point near the base of the Tptpl where lithophysal content drops from greater than 10% to less than 10%. See Elayer (1995) for discussion.

Figure 3-2. Correlation of stratigraphic and thermal-mechanical units along the ESF Main Drift alignment (modified by Ortiz et al. 1985).

Reference Stratigraphy Unit Name (Designation)	Description
Tiva Canyon welded unit (TCw)	Moderately to densely welded, devitrified ash-flow tuff of the Tiva Canyon Tuff of the Paintbrush Group. Contains lithophysal and nonlithophysal subunits.
Upper Paintbrush nonwelded unit (PTn)	Partially welded to nonwelded, vitric and occasionally devitrified tuffaceous material of the lower Tiva Canyon, Yucca Mountain, Pah Canyon, and Topopah Spring Tuffs of the Paintbrush Group.
Topopah Spring welded unit, lithophysae-rich (TSw1)	Moderately to densely welded, devitrified ash flows of the Topopah Spring Tuff of the Paintbrush Group that locally contains more than approximately 10% by volume lithophysal cavities.
Topopah Spring welded unit, lithophysae-poor (TSw2)	Moderately to densely welded, devitrified ash flows of the Topopah Spring Tuff of the Paintbrush Group that contains less than approximately 10% by volume lithophysal cavities. This is the repository host rock.
Topopah Spring welded unit, vitrophyre (TSw3)	Vitrophyre near the base of the Topopah Spring Tuff of the Paintbrush Group.
Calico Hills nonwelded unit, undifferentiated (CHnu)	Nonwelded ashflows and bedded tuffs of Calico Hills Formation, basal Topopah Spring Tuff.

SECTION VIEW

	Thermal-Mechanical Unit
Tiva d	TCw
tuffs of pah	PTn
pah than	TSw1
pah proposed	TSw2
pinbrush	TSw3
and	CHnu

Figure 3-3. Thermal-mechanical unit cross section along the Main Drift.

unit.¹⁸ Recent work by Elayer¹⁹ suggests that the contact location should be revised to locate it as per the original definition based on approximately 10% lithophysal content. This potential change is noted in Figure 3-3.

The thermal-mechanical units are based primarily on welded versus nonwelded rocks and on the porosity and presence of lithophysal cavities. The degree of welding present within the rocks of the Paintbrush Group ranges from nonwelded bedded tuffs that can be crumbled by hand to densely welded ash-flow tuffs. As the degree of welding may vary both vertically and laterally within an ash-flow unit, the thermal-mechanical unit boundaries reflect the boundaries between welded and nonwelded zones. Thermal-mechanical unit boundaries may vary with stratigraphic units.

Of note to ESF Main Drift design is the distinction between the upper two Tpt welded units, TSw1 and TSw2. These units are both within the densely welded, devitrified portions of the Tpt, but are reported to differ in that TSw1 contains zones where void space from lithophysal cavities commonly exceeds 10% by volume. TSw2, which contains the Main Drift horizon, also contains lithophysae bearing units, but to a lesser extent. The Tptpmn, in which the majority of the Main Drift is to be excavated, is the uppermost of the three lithostratigraphic units which comprise the TSw2.

3.5 Major Structural Features

3.5.1 Yucca Mountain Structural Framework

Yucca Mountain consists of a number of north trending structural blocks that have been tilted gently eastward by major west dipping, high-angle normal faults (Scott and Bonk 1984). The structural block containing the ESF is 3–4 km wide and is shown in Figure 3-4²⁰ to be bounded on the west and east by the Solitario Canyon and Bow Ridge Faults, respectively. Estimated displacement on the Solitario Canyon Fault ranges from 400 m (1312 ft) (Carr 1984) to 500 m (1640 ft) (USGS 1984). Displacement on the Bow Ridge Fault is variously described as 120 m (400 ft) (Carr 1984) to 220 m (725 ft) (USGS 1984) and is reported as 125 m $\pm$ 9 m (410 ft $\pm$ 30 ft) along the North Ramp alignment by Buesch et al. (1994).

Faults along the west sides of the major structural blocks at Yucca Mountain typically show highly brecciated zones as wide as 500 m, while the east margins of the blocks are characterized by abundant subparallel, west dipping normal faults described by some authors as

¹⁸Peck, J.M., U.S. Clanton, C.A. Rautman, R.W. Spengler, and D. Vaniman (1991). Science Application International Corp. (SAIC), Las Vegas, Nevada, to D.C. Dobson and J.R. Dyer, Department of Energy, YMP, Nevada, May 15 letter.

¹⁹Elayer, R.W. (1995). Definition of the Potential Repository Block, Document No. BC0000000-01717-5705-00009, Revision 00, CRWMS/M&O, TRW Environmental Safety Systems, Inc., Las Vegas, Nevada.

²⁰Buesch et al.

This page intentionally left blank.

imbricate normal fault zones (Scott and Rosenbaum 1986). Individual faults within these zones typically displace strata by only a few meters and the dip of strata between the faults progressively steepens eastward toward the margins of the broken zones. These fault zones increase in width toward the southern end of Yucca Mountain, which paleomagnetic and field mapping evidence shows to have rotated about 30° in a clockwise direction relative to the north end of the mountain (Spengler and Fox 1989). A number of northwest trending, right-lateral, strike-slip faults exist in the northern portions of Yucca Mountain, but the amount of displacement is probably minor as inferred from little or no offset of stratigraphic units (Carr 1984).

3.5.2 Faults Recognized Along the Main Drift Alignment

The potential repository has been sited in the area of the central block of Yucca Mountain that is the least disrupted by faulting. Most faults within this area are north trending, down-to-the-west structures with 5 m or less offset and do not cross the Main Drift alignment, as shown in Figure 3-4, and Figure 3-5²¹ shows surface faults identified by Scott and Bonk (1984). Exceptions to this are the Ghost Dance Fault and Sundance Fault Zone. The Main Drift is located approximately 160 m (525 ft) west of the surface trace of the Ghost Dance Fault for most of its length, but crosses a possible splay of this fault system, referred to as the Abandoned Wash Fault and a small parallel structure near the south end. The only additional structures noted by Scott and Bonk (1984) that are found on the alignment are several high-angle fracture sets with no apparent offset on the crest of Live Yucca Ridge above ESF station 36+00 m.

The known and suspected faults to be encountered by the Main Drift and the projected points of intersection based on the three-dimensional geologic model and Figure 3-5 are summarized in Table 3-3. Attitudes are derived from surface mapping or geophysics and the ramp station intersections are, therefore, approximate.

Table 3-3. Known Faults Projected to Encounter the Main Drift and Approximate Ramp Station

Ramp Station (m)*	Strike	Dip	Fault Type	Projected Dip-Slip Displacement	Name
36+40	N40°W	90°	strike-slip	0 m	Sundance Fault Zone
54+96†	N25°E	—‡	normal	—‡	Unnamed Fault
57+10	N25°E	74°	normal	21 m (70 ft)	Abandoned Wash Fault

* USGS OFR-95-124¹³ and Figure 3-5.

† Intersection with ramp alignment on surface.

‡ No dip or displacement available in Scott and Bonk (1984) or USGS OFR 95-124.¹³

²¹Geology of the Exploratory Studies Facility TS Loop, CRWMS M&O, Document No. BAB000000-01717-0200-00002, Rev. 00, TRW Environmental Safety Systems, Las Vegas, Nevada.

*1b1d

The Ghost Dance Fault is reported to have 38 m of offset at the southern boundary of the proposed repository outline. However, displacement decreases to the north and is not detectable in Drill Hole Wash (Spengler et al. 1993). The Sundance Fault System is a northwest trending feature with apparent right-lateral offset of the Ghost Dance Fault of at least 52 m (Spengler et al. 1994). This structure is described as a zone of near-vertical N30°-N40°W trending faults at least 274 m (900 ft) wide, with the dominant feature at the center of the zone termed the Sundance Fault. The Sundance Fault is projected to cross the drift alignment at ramp station 36+40 m.

The fault labeled as the Abandoned Wash Fault in Figure 3-2 is a north-northeast trending fault mapped by Scott and Bonk (1984) that continues the trend of the main segment of the Abandoned Wash Fault to the south and appears to terminate against the Ghost Dance Fault. This fault is assigned a 74°W dip in the USGS²² three-dimensional model, and has approximately 21 m (70 ft) of down-to-the-west dip separation. A parallel fault crosses the Main Drift alignment on the surface at station 54+96 m, however, no data on dip or displacement is available.

3.6 Joint Structure

The welded portions of the Tpc have been recognized by Barton et al. (1989) to contain two types of fractures: post-emplacement cooling joints and later tectonic joints. The cooling joints are observed to have low roughness coefficients and a lesser dispersion of orientations. Tectonic joints generally exhibit higher roughness coefficients, a greater dispersion of orientations, and a higher number of terminations against earlier joints.

Ongoing studies by the USGS²³ recognize that jointing characteristics vary significantly, depending on the degree of welding. In general, densely welded horizons show the greatest fracture frequencies. Nonwelded tuffs, on the other hand, show very few or no joints. This is due, at least in part, to the accommodation of stress by intergranular slip within the nonwelded units.

Mapping of the fracture network at Pavement P2001 at Fran Ridge by the USGS²⁴ illustrates some of the differences in jointing style between stratigraphic horizons. At this location, the Tptpmn is observed to contain large, continuous, and well-connected fractures similar to those recognized previously in the Tpc, while the overlying upper lithophysal zone of the Tpt exhibits shorter fractures with a greater number of blind terminations and a less-connected fracture network.

²²Buesh et al.

²³Sweetkind, D.S., E.R. Verbeek, F.R. Singer, F.M. Byers, Jr., and L.G. Martin (to be published in 1995). *Surface Fracture Network at Fran Ridge Pavement P20001, near Yucca Mountain, Nye County, Nevada*, U.S. Geological Survey Administrative Report to the Department of Energy, Yucca Mountain Project Office.

²⁴Ibid.

The U.S. Bureau of Reclamation²⁵ (USBR) has identified five structural feature trends in the North Ramp based on preliminary tunnel mapping data in the Tpc:

- joint set #1: dip = 84°, dip direction = 353°
- joint set #2: dip = 82°, dip direction = 132°
- joint set #3: dip = 78°, dip direction = 262°
- joint set #4: dip = 68°, dip direction = 174°
- joint set #5: dip = 16°, dip direction = 107°

The USBR set #5 is a subhorizontal parting characterized by thin anastomosing veins of vapor-phase alteration parallel to foliation. These features are most prominent in the middle nonlithophysal zone of the Tiva and may occur in other zones. Observations in the North Ramp indicate this structural feature is only a discontinuous separation a small percentage of the time. However, this feature represents a potential discontinuity or weakness, but has been considered a joint set as per Barton et al. (1974). Based on tunnel observations, the USBR joint set #4 rarely coexists with joint set #1; therefore, joint set #4 is considered to be a subset of joint set #1 because of the similar strike.

Based on these observations from the North Ramp Tunnel, three predominant joint sets can be identified and are listed in Table 3-4. These data are similar to the analysis of fracture patterns in existing oriented-core data (Lin et al. 1993b). Because there is general agreement between data sets on fracture orientation, it was assumed that the fracture sets to be encountered in the Tpt during excavation of the Main Drift will be similar to the North Ramp and Fran Ridge data. The Tpc and Tpt are very similar in terms of rock properties, were deposited within a relatively short period of geologic time, and have been subjected to the same post emplacement tectonic stresses.

Table 3-4. Orientation of Joint Sets Assumed to be Present in Tpt

Joint Set	Dip (degrees)	Dip Direction (degrees)
1.00	84.00	353.00
2.00	82.00	132.00
3.00	78.00	262.00

3.7 Hydrology

The Main Drift will be excavated in the unsaturated portion of the YMP stratigraphy. No evidence of water inflow of construction significance was observed in video logs of SD-7, SD-9 or SD-12 in the middle nonlithophysal or lower lithophysal zones to be cut in the Main Drift. Fault zones along the ramp were not directly sampled by any of the boreholes and conditions at the faults which will be penetrated by the Main Drift are not known. Perched water has been observed at the YMP site.

²⁵ U.S. Bureau of Reclamation (1995). *Geotechnical Report for Station 0+6 to 4+00 m, North Ramp of the ESF*, Report, DTN: GS950508314224.003.

4.0 Borehole Geotechnical Data

4.1 Rock Structure Data

This section of the report presents a summary of the rock structural data from boreholes USW NRG-6, NRG-7/7A, SD-7, SD-9, SD-12, and UZ-14 as the basis of characterization of rock characteristics along the Main Drift. The majority of the Main Drift (stations 28+05 to 57+00 m) cuts across the Tptpmn, and the structural data for this entire zone has been summarized for presentation. Near station 57+00 m, the Abandoned Wash Fault is projected to intersect the Main Drift and causes an up to the south displacement of approximately 15 m. Beyond this fault, the Main Drift is projected to be excavated approximately 15–20 m below the Tptpmn/Tptpll contact. The structural character of this portion of the Tptpll is compared to the Tptpmn for the interval 57+00 to 59+37 m.

The rock structure data are discussed under the following headings:

- lost core and rubble zones,
- Rock Quality Designation (RQD),
- rock weathering and hardness,
- fracture type,
- mineral infill and thickness,
- fracture surface roughness and planarity, and
- fracture frequency.

Appendix A lists TDIF numbers and data tracking numbers (DTN) of the individual core hole logs. The core log data for USW SD-7, SD-9, SD-12 and UZ-14 are presented in Appendix C. A detailed description of the structural core logging process along with core log data for USW NRG-6 and NRG-7/7A have been previously reported by Brechtel et al. (1995).

4.1.1 Core Recovery

The amount of lost core and rubble were logged for every 3-m (10-ft) interval of core throughout each borehole. The quantity of intact core and core rubble recovered and the quantity of lost core are general indicators of both the quality of the rock and the drilling technique. Lost core is defined as gaps in the core record where the rock sample has been ground up during drilling or where an empty void/cavity exists. A rubble zone includes sections of core where the rock is fragmented to the point where logging individual fractures is not feasible. The effect of the drilling technique on the proportion of lost core and rubble has been assessed by Brechtel et al. (1995) and it was suggested that it is the fractured nature of the welded tuffs and the presence

of lithophysae voids that produce the amount of lost and rubblized core and not the coring method.

The core recovery data are summarized in Table 4-1 for the Tptpmn. This table lists the percentages of intact core, rubble zones, and lost core (normalized to the total core length within the middle nonlithophysal zone) which are compared graphically in Figure 4-1. The amount of lost core from each hole ranged from 8.8% to 34.2% of the total core interval within the stratigraphic zone. Rubble zones ranged from 11.9% to 31.4%. Overall, 65% of the total core was recovered intact and logged, 15% was lost and 20% was rubblized. This is consistent with the core recovery in other welded units considered in the analysis of the North Ramp (NRG) borehole data.

Table 4-1. Summary of Core Recovery Data for the Tptpmn—Main Drift Boreholes

Borehole	Total Logged (m)	Whole Core Recovered (m)	% of Total	Lost Core (m)	% of Total	Rubble Zones (m)	% of Total	Lost Core & Rubble (m)	% of Total
SD-7	36.6	21.2	57.9	3.9	10.7	11.5	31.4	15.4	42.1
SD-9	33.5	23.4	69.9	4.8	14.3	5.3	15.8	10.1	30.1
SD-12	39.6	27.4	69.2	3.5	8.8	8.7	22.0	12.2	30.8
NRG-6	30.5	21.8	71.5	2.7	8.9	6.0	19.7	8.7	28.5
NRG-7/7A	36.6	17.3	47.2	12.5	34.2	6.8	18.6	19.3	52.8
UZ-14	33.5	26.3	78.5	3.2	9.5	4.0	11.9	7.2	21.5
TOTAL	210.3	137.4	65.3	30.6	14.5	42.3	20.1	72.9	34.7

The upper portion of the lower lithophysal zone is characterized by very high proportions of lost core and rubble. For example, NRG-7/7A averages 62% lost core and 15% rubble in the first 24 m below the base of the Tptpmn.

4.1.2 RQD Data

RQD (Deere 1963) is a core recovery percentage that considers only those pieces of core which are 100 mm (4 in) or greater in length. This index has been widely used as a general indicator of rock mass quality and is an input for the RMR and Q systems. The RQD percentage is determined as follows:

$$\text{RQD (\%)} = \frac{\sum \text{Piece lengths} \geq 100 \text{ mm (4 inches)}}{\text{Interval length}} \times 100 \quad (4-1)$$

where all discontinuity features observed in the core were considered. Lost core and rubble zones do not contribute any piece lengths, but are considered in the interval length. RQD was determined for both the core run interval and on even 3-m (10-ft) intervals.

Figure 4-1. Pie chart showing core recovery, lost core and rubble zones as a percentage of total core in the Tptpmn—Main Drift boreholes.

The RQD used for geotechnical design purposes considered all fractures identified in the core, including those identified by the core loggers as natural, indeterminate, and drilling induced. A parameter, *enhanced-RQD*, was also calculated in which the drilling-induced fractures were not considered resulting in greater piece length determinations. The resulting core RQD and *enhanced-RQD* are compared in Table 4-2 for the Tptpmn for each of the Main Drift boreholes. Frequency histograms and the cumulative percent occurrence for RQD and *enhanced-RQD* are shown in Figures 4-2 and 4-3, respectively.

Table 4-2. Comparison of RQD and *Enhanced-RQD* Data for the Tptpmn—Main Drift Boreholes

		SD-7	SD-9	SD-12	NRG-6	NRG-7/7A	UZ-14	All Holes	Relative Rating	
RQD	Mean	15	33	24	11	15	37	23	RQD (%)	Rating
	Median	12	19	25	8	11	29	16	91-100	Excellent
	Std. Dev.	15	28	16	12	14	31	22	76-90	Good
<i>Enhanced-RQD</i>	Mean	29	49	39	28	28	55	38	51-75	Fair
	Median	26	50	38	29	28	51	33	26-50	Poor
	Std. Dev.	23	28	24	18	21	33	26	1-25	Very Poor
<i>Enhanced-RQD</i> RQD	Mean	1.9	1.5	1.6	2.6	1.8	1.5	1.7	0-1	Extremely Poor
	Median	2.2	2.6	1.5	3.6	2.5	1.8	2.1		

The relative rock quality according to the RQD system (Deere 1968) is shown in Table 4-2 to compare to the Main Drift RQD values. The relative rock quality based on average

Figure 4-2. Histogram showing RQD frequency in the Tptpmn—Main Drift boreholes.

Figure 4-3. Histogram showing *enhanced-RQD* frequency in the Tptpmn—Main Drift boreholes.

RQD in the Tptpmn ranges from poor to very poor among the various holes. Table 4-2 also shows the ratio of *enhanced-RQD* to RQD for both mean and median values. Using average values from each borehole, the *enhanced-RQD* ranges from 1.5 to 2.6 times greater than the core RQD, suggesting poor to fair rather than very poor to poor rock quality.

RQD does not provide a complete assessment of rock structural quality; however, it provides a basis for cross-hole comparison to assess the potential of variation along the Main Drift as it cuts across the strata units. This comparison is shown in Figure 4-4 which lists the 3-m (10-ft) RQD values with increasing depth from the top of the Tptpmn. The approximate ramp station is listed on the left side of the figure for 10-m vertical increments of the stratigraphy. The comparison is generalized using the mean RQD for 3-m (10-ft) intervals which are compared to stratigraphy at the right side of the table and suggests the presence of two zones of generally higher RQD. Areas of lower RQD occur above, in between, and below, with the middle area associated with the lithophysal subzone in the Tptpmn. Below the Tptpmn, the portion of the Tptpll projected to be cut by the Main Drift is characterized by very low RQD, with the low values very consistent from hole to hole.

4.1.3 Rock Weathering and Hardness

Weathering is a parameter that describes the condition of the rock that constitutes the core surface. Rock weathering is determined for each 3-m (10-ft) interval of core using the qualitative descriptors listed in Table 4-3 which are based on recommendations by the International Society of Rock Mechanics (ISRM 1981). The distribution of the rock weathering is presented graphically in Figure 4-5 for the Tptpmn. Rock for this zone is either fresh or slightly weathered (51% and 49%, respectively, of the whole core recovered).

Rock hardness is a general descriptor of the strength of the rock material. Hardness is typically determined by scratching the rock surface or by striking the rock with a hammer and observing the response of the material. However, to satisfy the technical requirements for the core samples recovered in YMP drilling, the rock hardness was subjectively estimated by visual inspection. The hardness classification descriptors are listed in Table 4-4. The distribution of rock hardness is presented graphically in Figure 4-6. The rock in the Tptpmn has been generally classified as hard (80%) and very hard (15%).

4.1.4 Lithophysae Content

The lithophysae content includes the surface area percentage of lithophysal and other voids observed in the rock and is estimated for each 3-m (10-ft) interval of core using standard charts for estimating mineral content in thin sections. The distribution of the estimated lithophysal content is shown in Figure 4-7 for the Tptpmn. Percent lithophysae is low, with an average value of 0.3%, median of 0.0%, and a standard deviation of 0.8%. Lithophysal contents of the core recovered from the Tptpll ranged from 0 to 3% (from NRG-7/7A) using the core-based descriptive method reported by Brechtel et al. (1995). However, borehole video suggests that a substantially higher volume of lithophysal cavities may be present.

*0 ft = Approximate top of Topopah Spring Tuff middle nonlithophysal zone

Figure 4-4. Cross-hole comparison of RQD in the Tptpmn and portions of the Tptpll.

Table 4-3. Explanation of Weathering Descriptions and Log Abbreviations

Weathering Class	Log Abbreviation	Further Explanation
Fresh	F	Rock and fractures not oxidized or discolored, no separation of grains, change of texture or solutioning.
Slightly weathered	S	Oxidized or discolored fractures and nearby rock, some dull feldspars, no separation of grains, minor leaching.
Moderately weathered	M	Fractures and most of the rock oxidized or discolored, partial separation of grains, rusty or cloudy crystals, moderate leaching of soluble minerals.
Intensely weathered	I	Fractures and rock totally oxidized or discolored, extensive clay alteration, leaching complete, extensive grain separation, rock is friable.
Decomposed	D	Grain separation and clay alteration complete.

F=Fresh, S=Slightly Weathered, M=Moderately Weathered,
I=Intensely Weathered, D=Decomposed

Figure 4-5. Distribution of rock weathering parameters for the Tptpmn—Main Drift boreholes.

Table 4-4. Explanation of Estimated Hardness and Log Abbreviations

Hardness Class	Log Abbreviation	Further Explanation
Extremely hard	1	Cannot be scratched, chipped only with repeated heavy hammer blows.
Very hard	2	Cannot be scratched, broken only with repeated heavy hammer blows.
Hard	3	Scratched with heavy pressure, breaks with heavy hammer blow.
Moderately hard	4	Scratched with light-moderate pressure, breaks with moderate hammer blow.
Moderately soft	5	Grooved (16th inch) with moderate heavy pressure, breaks with light hammer blow.
Soft	6	Grooved easily with light pressure, scratched with fingernail, breaks with light-moderate manual pressure.
Very soft	7	Readily gouged with fingernail, breaks with light pressure.
Soil-like	8	cohesive
Soil-like	9	non-cohesive

1=Extremely Hard, 2=Very Hard, 3=Hard, 4=Moderately Hard, 5=Moderately Soft, 6=Soft, 7=Very Soft, 8=Soil-like Cohesive, 9=Soil-like Non-cohesive

Figure 4-6. Distribution of the estimated hardness rating as a percentage of the total drilling in the Tptpmn—Main Drift boreholes.

Figure 4-7. Histogram of the distribution of the percent lithophysae and other cavities in the Tptpmn—Main Drift boreholes.

4.1.5 Fracture Data

Extensive fracture data has been collected in the core logging process for the boreholes. The information for each individual fracture can include the following:

- structural feature type,
- fracture inclination,
- fracture mineral infilling,
- fracture infilling thickness,
- fracture planarity, and
- fracture roughness.

Detailed instructions for the geotechnical logging process, including the description of these fracture characteristics, are provided by Brechtel et al. (1995). The distribution of each fracture characteristic for the Tptpmn unit is described in the following subsections. No detailed processing of fracture characteristics was performed due to the large quantity of lost core and rubble in the lower lithophysal zone.

4.1.5.1 Feature Type. There are four categories of structural features that are identified during the logging of the core:

- N—natural fractures,
- I—indeterminate (uncertain origin) fractures,
- C—coring-induced fractures, and
- V—vug or void larger than core.

Natural fractures are indicated by mineral coatings, evidence of weathering, slickensides, and lack of rematch/fit between the discontinuity surfaces across the core. The fractures judged to be coring-induced are generally perpendicular to the axis of the core and are typically clean, fresh, and fit tightly back together. Fractures identified as indeterminate (I) often have been shaped by drilling rotation and cannot clearly be identified as natural (N) or coring induced (C). Voids or vugs that are larger than the core have also been identified during the logging process.

The total occurrence of each of type of feature is listed in Table 4-5, and distribution of these structural features is shown in Figure 4-8. Coring-induced (C) fractures have the largest proportion of occurrence in the Tptpmn. Only natural (N) and indeterminate (I) fractures have been considered in assessing the other fracture characteristics which include fracture inclination, mineral infilling and thickness, fracture planarity and roughness, and fracture frequency. For the Tptpmn, N and I feature types constitute 48.5% of the total fractures.

4.1.5.2 Fracture Inclination. Fracture inclination is the angle between the plane normal to the core axis and the fracture plane. The boreholes considered in the Main Drift are vertical, and fracture inclination is the dip angle of the fracture. The frequency of occurrence of dip angles grouped in 10° increments is shown in Figure 4-9. With no correction for sampling bias applied, low-angle fractures (less than or equal to 10°) occur most frequently. Sampling fracture inclination from core hole data introduces a bias in favor of fractures that are oriented perpendicular to the core axis. This sampling bias has been corrected using Terzaghi's (1965) procedure to provide a more representative distribution of fracture inclination, which is also illustrated in Figure 4-9. The application of Terzaghi's correction to borehole data for the ESF has been described by Lin et al. (1993b) and Brechtel et al. (1995). The corrected data shows that fractures with dips in the 80° to 90° range are the most dominant with a frequency of occurrence of 66.9%. The corrected fracture frequency for fracture dips between 70° and 90° is 22.0 m⁻¹.

Table 4-5. Total Number of Core Structural Features in the Tptpmn—Main Drift Boreholes

Borehole	Total Features	Natural N	Indeterminate I	Coring Induced C	Voids V
NRG-6	330	91	35	204	0
NRG-7/7A	319	59	71	189	0
UZ-14	315	104	74	137	0
SD-7	297	98	62	137	0
SD-9	250	68	38	140	4
SD-12	363	95	114	154	0
TOTAL	1874	515	394	961	4
% of occurrence	—	27.5	21	51.3	0.2

Figure 4-8. Distribution of the structural features in the Tptpmn—Main Drift boreholes.

Figure 4-9. Distribution of fracture inclinations for both uncorrected and corrected (using Terzaghi's correction) data in the Tptpmn—Main Drift boreholes.

4.1.5.3 Fracture Infill Mineralization and Thickness. The amount and type of infill mineralization within the discontinuity effects the shear strength of the discontinuity surface and relates directly to the quality of the rock mass. The number of fractures with infill mineralization was logged using the following categories to describe the infill type:

- C—clean,
- WC—white crystalline,

- WN—white noncrystalline,
- BC—black crystalline,
- BD—black dendritic,
- TD—brown dendritic,
- TC—tan crystalline,
- SI—silica,
- MN—manganese,
- CA—calcite,
- CL—clay
- TN—tan noncrystalline,
- FE—iron, and
- BN—brown noncrystalline.

The thickness of the infill was described using the following categories:

- C—clean, no filling;
- S—very thin, surface sheen;
- T—thin (up to 0.1 inch);
- M—moderately thick (0.1-0.4 inch);
- V—very thick (0.4-1.0 inch); and
- E—extremely thick (>1.0 inch).

The distribution of infill mineralization and thickness data is illustrated in Figures 4-10 and 4-11, respectively, for the Tptpmn. The fracture surfaces in the core are primarily clean (56% of the occurrence of "N" and "I" type fractures). The predominant infill materials include white crystalline (WC, 8% occurrence), white non-crystalline (WN, 10% occurrence), and black dendritic (BD, 17% occurrence). Clay infill in this zone is very scarce (0.1% occurrence in the Main Drift boreholes). Fractures exposed in the North Ramp tend to have thicker infillings than projected from core analysis. This may be due to the tendency of softer infills to be eroded by the compressed-air coring technique.

4.1.5.4 Fracture Planarity and Roughness. Fracture planarity and roughness also contribute to the shear strength of the discontinuity surface and directly affect the quality of the rock mass. Planarity describes the overall shape of the fracture and is subdivided into the following categories:

- P—planar,
- C—curved,
- S—stepped, and
- I—irregular.

Roughness describes the local or small-scale relief of the discontinuity surface and is categorized as follows:

C=Clean, WC=White Crystalline, WN=White Noncrystalline, BC=Black Crystalline, BD=Black Dendritic, TD=Brown Dendritic, TC=Tan Crystalline, TN=Tan Noncrystalline, CA=Calcite, SI=Silica, MN=Manganese, CL=Clay

Figure 4-10. Distribution of fracture mineral infillings in the Tptpmn—Main Drift boreholes.

C=Clean; S=Very thin, surface sheen; T=Thin (<0.1"); M=Moderately thick (0.1-0.4"); V=Very thick (0.4-1.0"); E=Extremely thick (>1")

Figure 4-11. Distribution of fracture infill thickness in the Tptpmn—Main Drift boreholes.

- V—very rough,
- R—rough,
- M—moderately rough,
- S—smooth, and
- P—polished.

The distributions of the frequency of occurrence of types of fracture planarity and roughness are shown in Figures 4-12 and 4-13, respectively. The fractures in the Tptpmn are predominately planar (66 % of the total occurrence) with a significant occurrence of irregular surfaces (21%). The small-scale roughness of the fractures is primarily described as either moderately rough (50%) or smooth (39%).

4.2 Rock Mechanics Laboratory Test Data

The available rock mechanics laboratory test data for the Tptpmn at the time of initial preparation of this report were from core holes NRG-6 and -7/7A. Limited additional data was subsequently produced in holes USW SD-9 and SD-12. These data, summarized in Table 4-6, include the following rock properties:

- unconfined compressive strength;
- elastic modulus and Poisson's ratio;
- dry bulk density, porosity, average grain density;
- indirect tensile strength; and
- confined compressive strength.

The data have been combined in Table 4-6 to provide the range of values, mean, standard deviation, and number of tests for each rock property determined. The table is subdivided into two groups of summary statistics (USW NRG-6 and -7/7A versus all data) to evaluate any changes resulting from the inclusion of the SD-9 and SD-12 data.

The confined compressive strengths for intact rock were obtained in triaxial tests on 25.4-mm (1.0-in) diameter samples with confining pressures of 0, 5, and 10 MPa. The results are compared in Figure 4-14a as compressive strength versus confining pressure for NRG-7/7A samples from 262.65- and 263.78-m depths in Table 4-6, and in Figure 4-14b which includes supplemental data from boreholes SD-9 and SD-12. Least-square linear fits of the data sets were performed and plotted on these figures in the form:

$$\sigma_1 = N\sigma_3 + \sigma_c \quad (4-2)$$

where

- σ_1 = the strength of the rock at failure,
- σ_3 = the confining stress,
- σ_c = the unconfined compressive strength, and
- N = a confinement factor.

Figure 4-12. Distribution of fracture planarity for the Tptpmn—Main Drift boreholes.

Figure 4-13. Distribution of the fracture roughness for the Tptpmn—Main Drift boreholes.

Table 4-6. Summary of Rock Mechanics Laboratory Test Data for Tptpmn—Main Drift Boreholes

Core Hole	Depth		UCS ¹ (MPa)	Porosity (%)	Young's Modulus (GPa)	Poisson's Ratio	Dry Bulk Density (g/cc)	Confined Compressive Test (MPa) ²		Indirect Tensile Strength (MPa)	Average Grain Density (g/cc)
	(m)	(ft)						Confined Pressure	Axial Stress		
NRG-6	219.67	720.7 A	235.5	8.5	37.1	0.19	2.29				
	219.67	720.7 B									2.50
	226.26	742.3 A	162.3	11.0	30.6	0.20	2.25			14.50	
	226.26	742.3 B		9.7			2.28				
	226.26	742.3 C									2.53
	226.44	742.9 A	212.8	10.0	32.4	0.22	2.28			13.00	
	226.44	742.9 B		10.3			2.27				
	226.44	742.9 C									2.53
	232.53	762.9-A	112.1	9.5	29.2	0.18	2.31				2.55
	232.53	762.9-B									
	235.77	773.5 A	117.4	10.3	36.2	0.23	2.26			7.90	
	235.77	773.5-B		11.9			2.22				
	235.77	773.5-C									2.52
	236.89	777.2-A		8.0							
	236.89	777.2-B									2.50
	239.21	784.8-A	223.0	9.6	29.7	0.17	2.27				
	239.21	784.8-B		9.6			2.27			12.50	
	239.21	784.8-C									2.51
	239.45	785.6-A	218.6	9.3	30.1	0.16	2.27				
	239.45	785.6-B		9.3			2.27			14.10	
	239.45	785.6-C									2.51
	241.28	791.6-A		11.4							
	241.28	791.6-B									2.52
	243.92	806.8-A	261.9	8.0	31.7	0.16	2.31				
	243.92	806.8-B									2.51
NRG-77A	236.71	776.6-B									2.54
	236.83	777.0-A	143.8	10.6	32.9	0.22	2.27				
	243.90	800.2-A	179.2	10.3			2.27				
	245.55	805.6-A		12.6	21.4	0.27	2.23	10.00	147.10		
	245.55	805.6-B									2.53
	245.76	806.3-A	225.4	10.1	36.7	0.19	2.28				
	246.16	807.6-B									2.53
	246.37	808.3-B									2.53
	249.48	818.5-A	126.3	10.2	33.1	0.20	2.27				
	252.19	827.4-A		14.6	23.4	0.33	2.18	10.00	135.30		
	252.19	827.4-B									2.55
	252.50	828.4-A		15.9			2.16			6.10	
	259.05	849.9-A		27.7			1.84				
	260.61	855.0-A		11.0			2.25			11.60	
	261.64	858.4-B									2.53
	261.89	859.2-A	118.8	11.3	38.8	0.20	2.28				
	262.65	861.7-A		9.6	33.9	0.21	2.28	5.00	250.80		
	262.65	861.7-B									2.53
	263.78	865.4-A		10.3	32.3	0.19	2.27	10.00	325.20		
	263.78	865.4-B		10.4	34.0	0.21	2.27	10.00	354.00		
	263.78	865.4-D		11.7	32.0	0.25	2.23	10.00	235.50		
	263.78	865.4-E		10.0	34.1	0.22	2.28	10.00	316.70		
	263.78	865.4-C		10.4	35.0	0.20	2.27	5.00	259.80		
	263.78	865.4-F		10.4	34.5	0.21	2.27	5.00	322.30		
	263.78	865.4-G		11.1	34.0	0.18	2.25	5.00	255.10		
	263.78	865.4-H		11.1	36.8	0.21	2.25	5.00	231.60		

Table 4-6. Summary of Rock Mechanics Laboratory Test Data for Tptpmn—Main Drift Boreholes

Core Hole	Depth		UCS ¹ (MPa)	Porosity (%)	Young's Modulus (GPa)	Poisson's Ratio	Dry Bulk Density (g/cc)	Confined Compressive Test (MPa) ²		Indirect Tensile Strength (MPa)	Average Grain Density (g/cc)
	(m)	(ft)						Confined Pressure	Axial Stress		
NRG-7/7A	263.78	865.4-I		10.7	34.3	0.20	2.26	0.00	215.80		
	263.78	865.4-J		10.4	33.5	0.19	2.27	0.00	232.00		
	263.78	865.4-K		10.3	34.9	0.22	2.27	0.00	239.10		
	263.78	865.4-L		10.6	35.7	0.21	2.26	0.00	248.50		
	263.78	865.4-M									2.53
Summary	Minimum		112.1	8.0	21.4	0.16	1.84	-	-	6.10	2.50
Statistics	Maximum		261.9	27.7	38.8	0.33	2.31	-	-	14.50	2.55
for NRG-6	Mean		179.8	11.0	32.9	0.21	2.25	-	-	11.39	2.53
and NRG-7/7A	Standard Deviation		52.5	3.2	3.8	0.03	0.08	-	-	3.19	0.01
only ³	Number of Samples		13.0	38.0	27.0	27	36.00	-	-	7.00	18.00
SD-9	232.13	761.5-A			33.9	0.21		0.00	231.50		
	234.30	768.7-A			36.9	0.20		0.00	254.50		
	235.21	771.7-A			34.8	0.19		0.00	160.80		
	236.10	774.6-B			16.8	0.19		0.00	60.10		
	251.98	826.7-A			31.9	0.21		0.00	224.90		
	253.84	832.8-C			29.8	0.19		0.00	183.30		
	256.67	842.1-E-1			36.3	0.20		0.00	208.90		
SD-12	223.94	734.7-B			31.9	0.18		0.00	193.30		
	227.26	745.6-B			34.5	0.20		5.00	330.70		
	232.44	762.6-B			34.1	0.20		10.00	272.80		
	238.08	781.1-B			36.7	0.21		0.00	198.20		
Summary	Minimum		112.1	8.0	16.8	0.16	1.84	-	-	6.10	2.50
Statistics	Maximum		261.9	27.7	38.8	0.33	2.31	-	-	14.50	2.55
for All	Mean		179.8	11.0	32.8	0.21	2.25	-	-	11.39	2.53
Boreholes	Standard Deviation		52.5	3.2	4.4	0.03	0.08	-	-	3.19	0.01
	Number of Samples		13.0	38.0	38.0	38	36.00	-	-	7.00	18.00

¹Uniaxial compressive tests conducted on 50.8-mm (2.0-in) diameter samples.

²Triaxial (confined) compressive tests conducted on 25.4-mm (1.0-in) diameter samples.

³Used for development of rock mass mechanical properties estimates in Section 6.2.

Figure 4-14a. Confined compressive strength results for the Tptpmn—NRG-6 and NRG-7/7A boreholes.

Figure 4-14b. Confined compressive strength results for the Tptpmn—NRG-6, NRG-7/7A, SD-9 and SD-12 boreholes.

The relationship between the linear equation above and the Mohr-Coulomb parameters, cohesion (C) and internal friction angle (ϕ), is given by the following:

$$\tau = C + \sigma_n \tan \phi, \quad (4-3)$$

where

τ = shear stress,

C = cohesion = $\sigma_c / 2\sqrt{N}$,

σ_n = normal stress, and

ϕ = angle of internal friction = $2\left(\tan^{-1} \sqrt{N} - 45^\circ\right)$.

The least-square fits of the triaxial test data were performed to develop intact rock failure criteria using Equations 4-2 and 4-3. The results are listed in Table 4-7. Fits of all the NRG data produced unreasonably low values of confinement effect (N) and friction angle (ϕ). If the two extreme values were removed, a more typical friction angle of 49.6° would result. Inclusions of the SD-9 and SD-12 data produced changes in the linear equation coefficients of 39% for the slope (N) and 10% for the intercept (σ_c). These changes were considered within the existing variability.

Table 4-7. Intact Rock Failure Criteria — Tptpmn

Boreholes	Data	$\sigma_1 = N\sigma_3 + \sigma_c$		Standard Deviation (MPa)†	$C = \tau + \sigma \tan \phi$	
		N	σ_c (MPa)		C (MPa)	ϕ
NRG-6,	All values	1.6	242.4	69.2	97.1	12.6
NRG-7/7A	Excluding extreme values*	7.4	231.2	33.1	42.5	49.6
NRG-6,	All values	5.8	211.8	61.3	43.9	44.9
NRG-7/7A, SD-9, SD-12	Excluding extreme values*	10.3	207.6	46.8	32.4	55.4

* $\sigma_1 < 150$ MPa @ $\sigma_3 = 10$ MPa

† standard deviation of data from least-square equation

The mean uniaxial compressive strength for the 25.4-mm (1.0-in) diameter samples from NRG data only was 233.8 MPa. The 25.4-mm diameter mean was higher than for the 50.8-mm (2.0-in) diameter UCS tests listed in Table 4-6, which had a mean strength of 179.8 MPa and a standard deviation of 52.5 MPa. With the inclusion of the SD data, the mean unconfined strength of the 25.4-mm diameter samples was 203.9 MPa. These differences were considered to be within the existing variability of the data, and no size effects due to the sample diameters were observed.

This page intentionally left blank.

5.0 Rock Mass Quality Assessment

5.1 Introduction

Rock mass quality has been assessed using both the RMR and Q rock mass classification systems. Each of these classification systems assigns a numerical rating to a series of parameters that affect the quality of the rock mass. The parameters are related to the degree of jointing, interaction of joint orientations to form blocks, joint frictional strength, rock strength versus active stress, and hydrologic conditions. The individual parameter ratings are combined using empirical relationships to determine an overall rock quality index (Bieniawski 1979; Barton et al. 1974).

A methodology for estimating the rock mass quality parameters, Q and RMR, was developed for core rock structural data from the NRG holes, reported by Brechtel et al. (1995). This methodology has been extended to the Main Drift borehole geotechnical data with modifications that take advantage of recent rock mass description data produced in the ongoing excavation of the North Ramp. The available data on rock structural conditions in the Tptpmn is limited to the six boreholes (USW SD-7, SD-9, SD-12, NRG-6, NRG-7/7A, and UZ-14) utilized in this study. Comparison of the outcrop mapping data from Fran Ridge and structural mapping data from Tpc in the North Ramp, discussed in Section 3.6, suggests joint structures are similar. The North Ramp data²⁶ have, therefore, been used to improve the rock mass quality estimates for the Main Drift in three areas:

- The distribution of the SRF and Jn parameters in the Tpc, excluding the high lithophysae interval, have been used to modify the core-based methodology to estimate Q in the Tptpmn.
- The range of Q values from the Tpc upper lithophysal zone in the North Ramp was assumed to be representative of the portion of the Main Drift to be excavated in the Tptpll.
- The Q values developed for fault zones encountered during excavation of the North Ramp in the Tpc are projected as the basis for conditions in the faults to be encountered along the Main Drift.

²⁶Interim Data Transmittal, Yucca Mountain Site Characterization Project, Rock Mass Quality Data for NRST Stations 60 to 475 m, 475 to 530 m, and 530 to 600 m, TDIF No. 304267 DTN: SNF32120393001.001, TDIF No. 304283 DTN: SNF32120393001.002, and TDIF No. 304351 DTN: SNF32120393001.003.

5.2 Rock Mass Quality Projections for the Tptpmn

The RMR and Q indices have been estimated for the Tptpmn using the 3-m (10-ft) intervals from the core log data for USW SD-7, SD-9, SD-12, NRG-6, NRG-7/7A, and UZ-14. The rock mass quality indices are presented in log form in Appendix C. Q values in NRG-6 and NRG-7/7A have been resimulated using Jn and SRF distributions from the North Ramp data.²⁷ The resulting rock mass quality was projected to represent the expected variation that will occur as the Main Drift cuts across the zone. No spatial correlation of specific values was assumed due to the limited data; however, cross correlation of RQD data in Section 4.2.1 does suggest rock quality will vary with stratigraphic location.

5.2.1 Rock Mass Quality Indices for the RMR System—Tptpmn

The calculation of RMR as defined by Bieniawski (1979) includes the summation of the ratings of five parameters as shown in the following equation:

$$\text{RMR} = C + \text{RQD-I} + \text{JS} + \text{JC} + \text{JW} \quad (5-1)$$

where

- RMR = a dimensionless number between 0 and 100,
- C = rock strength parameter,
- RQD-I = Rock Quality Designation (RQD) parameter,
- JS = joint spacing parameter,
- JC = joint condition parameter, and
- JW = joint water parameter.

RMR includes an additional adjustment to account for the strike and dip orientations of the joints relative to the direction of mining. In this report, the application of RMR is limited to the estimation of rock mass mechanical properties which does not require joint orientation adjustment.

The distribution of each parameter (except JW) for the Tptpmn is shown in Figure 5-1. The groundwater conditions at the repository level of the Yucca Mountain site are projected to be dry. Therefore, according to the RMR guidelines, the groundwater rating (JW) was set at 15. Details of the determination of each parameter are provided by Brechtel et al. (1995). In this study, the rock strength parameter (C) was determined by Monte Carlo simulation of the rock mechanics testing data from NRG boreholes.

The RMR values for each 3-m (10-ft) interval are calculated according to Equation 5-1 by summing the individual parameter values for that interval. The distribution of RMR values for the Tptpmn is shown in Figure 5-2. The RMR data were rank ordered to determine the cumulative frequencies of occurrence and values are presented for 5%, 20%, 40%, 70% and 90% as listed in Table 5-1. These frequencies of occurrence were proposed by Hardy and Bauer

²⁷Ibid.

Figure 5-1. Histograms showing the distribution of the RMR system parameters for the Tptpmn—Main Drift boreholes.

Table 5-1. RMR Values at Five Levels of Cumulative Frequency of Occurrence

Cumulative Frequency of Occurrence (%)	RMR	Relative Rating	
5	50	very good	81-100
20	55	good	61-80
40	58	fair	41-60
70	63	poor	21-40
90	67	very poor	<20

Figure 5-2. Distribution of the RMR in the Tptpmn—Main Drift boreholes.

(1991) to develop rock mass mechanical properties that represent the range of variability. The rank-ordered data are presented in Appendix B and indicate that the RMR ranges from a fair to a good rock mass quality according to the RMR relative ratings listed in Table 5-1.

5.2.2 Rock Mass Quality Indices for the Q System—Tptpmn

The Q System uses six parameters that are combined using the following relationship to determine a numerical rating of the rock mass (Barton et al. 1974):

$$Q = \frac{RQD}{J_n} \times \frac{J_r}{J_a} \times \frac{JW}{SRF} \quad (5-2)$$

where

- RQD = Rock Quality Designation (%),
- J_n = joint set number,
- J_r = joint roughness number,
- J_a = joint alteration number,
- JW = joint water factor, and
- SRF = stress reduction factor.

The first pair of parameters (RQD/ J_n) is an approximate description of the block size. The next pair of parameters (J_r/J_a) is a measure of the interblock shear strength, and the final pair of parameters (JW/SRF) is a description of active stress.

The methodology for determining each of these parameters from core structural data has been described by Brechtel et al. (1995). The joint set number (J_n) and the stress reduction factor (SRF) cannot be readily determined from core data. Brechtel et al. (1995) assumed a uniform distribution of J_n between 4 and 9 based on available mapping data from the NRST, and a

similar methodology for determining SRF values was assumed based on the distribution conditions of the NRST. These original assumptions have been compared to parameter assessments from recent data from the Tpc²⁸ in the North Ramp. The upper lithophysal zone of the Tpc from the North Ramp data was not included because it was not considered representative of the Tptpmn. The frequencies of occurrence of both the assumed and the North Ramp values of Jn and SRF for the Tpc are shown in Figure 5-3.

The field data distribution represents the North Ramp assessments²⁹ and is similar to the original assumed distribution, but indicates conditions more adverse to stability. Jn values of 12 appear in the field data, but were not anticipated in the assumed distribution. An SRF value of 5 is more prominent in the North Ramp data primarily due to the existence of open joints. To adjust for these variances, data distributions for the Jn and SRF parameters were modified to match the distributions determined from the North Ramp field mapping in an attempt to maintain a conservative assessment of conditions in view of the data limitations.

The distribution of each Q system parameter for the Tptpmn is shown in Figure 5-4. As in the RMR system, the groundwater parameter (JW) is not shown because it is anticipated that all excavations at the ESF will be "dry" corresponding to a JW value of 1.

The Q values for each 3-m (10-ft) interval are calculated according to Equation 5-2 based on the individual parameter values for that interval. The distribution of Q values for the Tptpmn is shown in Figure 5-5. The Q data were rank ordered to determine the values at cumulative frequencies of occurrence of 5%, 20%, 40%, 70%, and 90% as listed in Table 5-2. Rank-ordered values are presented in Appendix B. It can be seen that Q ranges from a very poor to a good rock mass quality according to Q guidelines, with a majority of the intervals (64%) indicating a very poor rock mass quality.

5.3 Evaluation of Projected RMR and Q Results— Tptpmn

The Q and RMR values determined from the Main Drift borehole data (USW NRG-6, NRG-7/7A, SD-7, SD-9, SD-12, and UZ-14) have been evaluated by comparing the correlation of Q and RMR results to a case-history correlation reported by Bieniawski (1976). This provides a means to check the rock quality assessments by the core logging procedure against previously published rock quality data. The core-based Main Drift Q and RMR calculation procedure uses the methodology presented by Brechtel et al. (1995), except that adjusted data distributions for the Jn and SRF parameters were used in the Monte Carlo simulation. The effectiveness of the core-based methodology was also evaluated by comparing the core-based North Ramp data for the Tpc to the Q and RMR data determined from scanline descriptions developed during construction of the North Ramp.³⁰ This evaluation was performed to verify that the core-based

²⁸Ibid.

²⁹Ibid.

³⁰Ibid.

a. Assumed distribution of Jn and SRF

Frequency
Cumulative %

b. Distribution of North Ramp field-assessed values of Jn and SRF

Figure 5-3. Distribution of the previously assumed values (Brechtel et al. 1995) and the field-assessed values (North Ramp Tiva Canyon Member) of Jn and SRF.

Figure 5-4. Histograms showing the distribution of the Q system parameters for the Tptpmn—Main Drift boreholes.

Figure 5-5. Distribution of the estimated Q in the Tptpmn—Main Drift boreholes.

Table 5-2. Q Values at Five Levels of Cumulative Frequency of Occurrence

Cumulative Frequency of Occurrence (%)	Q	Relative Rating	
5	0.14	exceptionally good	400–1000
20	0.29	extremely good	100–400
40	0.42	very good	40–100
70	1.39	good	10–40
90	10.56	fair	4–10
		poor	1–4
		very poor	0.1–1
		extremely poor	0.01–0.1
		exceptionally poor	0.001–0.01

rock quality assessments were reasonable when compared to field assessments made in the North Ramp tunnel.

5.3.1 Correlation of Q and RMR Results

Bieniawski (1976) developed the following correlation between Q and RMR values based on 111 case histories:

$$\text{RMR} = 9 \ln(Q) + 44. \quad (5-3)$$

The case history data were also used to develop a 90% confidence interval bounding the relationship. Equation 5-3, including the confidence intervals, is shown in Figure 5-6 with correlated Q and RMR data from the Main Drift boreholes. For Q values greater than 1, the Main Drift data is generally consistent with Bieniawski's relationship of Q and RMR. However, for Q values less than 1, the Main Drift data often exceed the upper 90% confidence limit. Hardy and Bauer (1991) attributed this effect to the fact that the stress/strength term (SRF) in the Q system accounts for structural effects similar to the RQD, while the strength index in the RMR system remains fairly constant for a particular rock type. The procedure for calculating RMR for the ESF tunnels is less sensitive to joint conditions when compared to the Q system. Also, because RMR is used to determine rock mass mechanical properties in this work, it has not been adjusted for joint orientation.

5.3.2 Comparison of Q Values from Field- and Core-Based Assessments

The core-based results for Tpc are compared to actual field data from rock quality assessments in the North Ramp to assess the performance of the core-based projections. The North Ramp has not currently reached the Tptpmn and, therefore, no field data for this zone is available for comparison.

Prior to construction of the North Ramp, the rock mass quality of the North Ramp was projected using the data from the North Ramp borehole (NRG series) rock structure logs and the same core-based rock quality assessment methodology described in this section (Brechtel et al. 1995). As the North Ramp is being excavated, rock mass quality is being collected from scanline descriptions, and Q and RMR are being assessed for every 5-m interval along the tunnel length.³¹ These data have been compiled for the portion of the Tpc stratigraphic unit (North Ramp tunnel stations 0+60 to 1+88 m and 3+50 to 5+30 m) for each 5-m interval in the tunnel. The two data sets are compared in Figure 5-7 by showing the cumulative frequency of occurrence of Q values. The distributions are very similar, however, the actual rock quality in the tunnel is lower than predicted by the core.

The projected ground support requirements indicated by the two data sets in Figure 5-7 have been determined according to the YMP Ground Support Guidelines.³² The support

³¹Ibid.

³²BABEAB000-01717-2100-40151-01, Exploratory Studies Facility Package 2C, Topopah Springs North Ramp Ground Support Master Elevations and Sections, July 27, 1994.

Figure 5-6. Correlation of Q and RMR results for the Tptpmn—Main Drift boreholes.

Figure 5-7. Comparison of cumulative frequency of occurrence of Q for both core-based (predicted) and field-assessed (actual) values for the Tpc stratigraphic unit.

guidelines for each 3-m (10-ft) borehole interval of the Tpc unit (using all NRG series boreholes) were determined based on the Q parameters, and the frequency of occurrence of each support category is shown in Figure 5-8. Support categories used in this comparison are defined in Table 5-3 based on the YMP Ground Support Guidelines. The core-based data for the Tpc unit projects that the majority of the tunnel will require Category 3b support which includes a pattern of 15 rockbolts across the crown with 50–75 mm of shotcrete fully covering the tunnel wall from the crown to the invert.

Ground support requirements based on the field-assessed Q parameters and the YMP Ground Support Guidelines are presented in Figure 5-9 as frequency of occurrence. The distribution of ground support is very similar to the ground support requirements determined from borehole data indicating that the empirical approach is robust and that the core-based projections are realistic. Although differences were observed in the predicted and actual Q values, the predicted ground support distribution according to the YMP support guideline (which is based on the Q parameters) was nearly identical to the field-assessed ground support requirements.

5.4 Indicated Ground Conditions and Support Requirements—Tptpmn

Although the joint structure exposed in the North Ramp excavations is similar to jointing in the surface pavements mapped at Fran Ridge, the difference in orientation of the North Ramp and Main Drift is projected to result in more adverse ground conditions in the Main Drift. This difference is illustrated by key block analyses based on North Ramp joint orientations and comparative analysis of the two tunnel alignments, and supports the assessment of ground support requirements using the YMP Ground Support Guidelines and the projected rock quality (Q) in the Tptpmn.

5.4.1 Key Block Stability Analysis—Tptpmn

A key block stability analysis using the three joint sets in Table 5-4 has been performed comparing the North Ramp, with a tunnel azimuth of 299°, to the Main Drift which will have a tunnel azimuth of 183°. A key block is a critical block or wedge in the tunnel wall that is finite, removable, and potentially unstable (Goodman and Shi 1985). The UNWEDGE Version 2.2³³ key block stability analysis program has been used in this analysis. The program uses an ubiquitous, non-probabilistic approach to key block analysis which emphasizes the prediction of the formation of the maximum potential key block size given a particular joint set, tunnel

³³Carvalho, J., E. Hoek, and B. Li (1992). *UNWEDGE—Program to Analyze the Geometry and Stability of Underground Wedges*, Rock Engineering Group, University of Toronto, Toronto, Canada.

Figure 5-8. Distribution of ground support category from NRG borehole data for the Tpc stratigraphic unit of the Tiva Canyon Formation.

Table 5-3. YMP Ground Support Categories

YMP Ground Support Category	Description of Ground Support
1a	An array of 8 rockbolts with welded wire mesh; bolt density = 8 bolts/1.5 m
1b	An array of 8 rockbolts with welded wire mesh; bolt density = 8 bolts/1.5 m; supplement with spot bolting
2	An array of 15 rockbolts with welded wire mesh; bolt density = 15 bolts/1.5 m
3a	An array of 8 rockbolts; bolt density = 8 bolts/1.5 m; supplement with spot bolting; apply 50–75 mm shotcrete
3b	An array of 15 rockbolts; bolt density = 15 bolts/1.5 m; apply 50–75 mm shotcrete
4	Steel sets at 1.2 m spacing with partial lagging
5	Steel sets at 0.6–1.2 m spacing with full lagging

Figure 5-9. Distribution of ground support category from North Ramp tunnel data for the Tpc unit of the Tiva Canyon Formation.

Table 5-4. Comparison of Key Block Analysis Results for the North Ramp and Main Drift

Wedge #	North Ramp				Main Drift			
	Volume (m ³)	Apex Height (m)	Tonnes	Safety Factor	Volume (m ³)	Apex Height (m)	Tonnes	Safety Factor
1	21.6807	7.8	59	0	58.75	10.8	159	0
2	0.0007	0.3	<1	0.06	not formed			
3	0.0009	0.4	<1	0.55	0.01	0.4	<1	0.55
4	21.6807	7.8	59	infinite	58.75	10.8	159	infinite
5	0.0007	0.3	<1	0.53	not formed			
6	0.0009	0.4	<1	0.12	0.01	0.4	<1	0.12

orientation, and tunnel cross section. The results of the analysis are provided in Appendix D and are described below.

This analysis of the joint structure, based on the assumption of similar joint orientations in both the North Ramp and Main Drift, suggests that given similar rock mass conditions, the Main Drift will experience an increase in the frequency of ground stability problems in the crown (formation of key blocks) due to the orientation of joints relative to the tunnel alignment. A comparison of the maximum potential key block volume, apex height, block tonnage, and safety factor are shown in Table 5-4. The volume and tonnage of the maximum potential key block formed in the crown (wedge #1 in Table 5-4) is estimated to be three times greater in the Main

Drift than in the North Ramp. Although not directly resulting from the analysis, it is inferred that the Main Drift tunnel crown has the potential for more key blocks which will result in poorer ground conditions compared to the North Ramp because the most predominant joint set is generally parallel to the tunnel axis.

The effect on block formation in the tunnel walls (wedges #2, #3, #5 and #6 in Table 5-4) is mixed. The North Ramp alignment allows the potential formation of four wedge types whereas the Main Drift alignment allows only two. The analysis indicates that the relative size of the maximum potential key blocks in the tunnel wall increases in the Main Drift compared to the North Ramp, however, the block sizes are negligible with respect to ground control.

5.4.2 Indicated Ground Support—Tptpmn

The distribution of the projected rock mass quality (Q), illustrated in Figure 5-5, and the YMP Ground Support Guidelines have been used to determine support requirements using the associated Q parameters. The relative lengths of the Main Drift that will require the indicated support can be derived from the distribution of projected ground support shown in Figure 5-10. The ground support categories are described in Table 5-3. This analysis suggests that within the Tptpmn, 46% of the tunnel length will require category 3b support (rockbolts with shotcrete) and 36% of the tunnel length will require category 4 support (steel sets with partial lagging).

5.5 Rock Mass Quality—Tptpll

Specific rock mass quality assessments were not performed on the portion of the Tptpll containing the Main Drift between stations 57+00 m to 59+37 m. Recovery of core in this part of the Main Drift boreholes was very low, and the resulting RQD listed in Figure 4-4, Section 4.0, gives an average RQD of <10%. Review of downhole video records indicates that the upper portion of the Tptpll contains lithophysal cavities larger than the diameter of the core (60 mm) and that the condition of the borehole is uniformly irregular, type C3, according to the descriptive nomenclature used by Brechtel et al. (1995).

Rock mass conditions based on the core data may be similar to the upper lithophysal zone of the Tpc in the North Ramp. Rank-ordered Q data from the North Ramp in this zone of cavernous lithophysae indicated a range of Q values from 0.04 to 2.68 with a median value of 0.64. Based upon comparison of RQD, Table 4-4, Section 4.0, it is projected that ground support requirements in the portions of the Main Drift will be category 4.

5.6 Rock Mass Quality—Fault Zones

Fault zones along the Main Drift have not been sampled by the boreholes, and no direct data on the character or extent of the fault zones is available at depth. Observations in the North Ramp excavations through the Tpc indicate that rock mass quality in the densely welded tuffs is generally lower than in the nonwelded tuffs. The presence of faults in the welded tuffs adversely

Figure 5-10. Projected distribution of ESF ground support category for the Tptpmn—Main Drift boreholes.

affects rock quality in the area of the faults, as opposed to the nonwelded tuffs where the fault-related effects are more localized.

Examination of the variation of Q from the North Ramp in the area affected by the “imbricate” faults suggests a median Q of 0.44 which corresponds to roughly the lower 25% of the Tpc data. On this basis, rock quality near the points of intersection of the Main Drift with the Sundance Fault zone and the Abandoned Wash Fault are expected to be similar to the range of Q values associated with a cumulative frequency of occurrence of 25% in the Tptpmn data in Section 5.2. This would suggest Q values of 0.3 or less. In the Sundance Fault zone, these values of Q could be characteristic of the rock roughly 185 m before and after the central zone which is projected to occur at station 36+40 m. Note that this location is based on the projection of the fault zone as vertical and that there is no subsurface information. Data from discrete 5-m intervals intersected by normal faults in the North Ramp indicate Q values as low as 0.04.

This page intentionally left blank.

6.0 Assessment of Rock Mass Mechanical Properties

6.1 Introduction

Rock mass mechanical properties are required for input into the numerical analyses that support the geotechnical design of the Main Drift. Mechanical properties at the rock mass scale are known to vary significantly from mechanical rock properties determined from laboratory specimens. These differences are the result of the inherent complexities of rock as an engineering material and are primarily attributed to the jointed nature of the rock. The rock mass mechanical properties of interest included rock mass strength, the elastic modulus, and the Poisson's ratio.

Hardy and Bauer (1991) have recommended rock mass strength criteria and mechanical models for representing the rock mass response of the tuff at Yucca Mountain. Empirical methods are used with RMR data and the laboratory rock mechanical properties to estimate the rock mass mechanical properties. These empirical methods will require validation by future ESF testing.

6.2 Rock Mass Strengths

A site-specific rock mass strength criteria has been developed following the procedure of Hardy and Bauer (1991) using both the Hoek and Brown (1988) and Yudhbir et al. (1983) strength criteria. The data needed for using this approach include the rock mass quality index RMR, intact rock uniaxial compressive strength, and triaxial compressive strength data.

Both Hoek and Brown (1988) and Yudhbir et al. (1983) use the 1974 version of RMR (RMR₇₄, Bieniawski 1974a) in their rock mass strength determination. However, the site characterization of the tunnels of the ESF have adopted the most recent version of RMR (RMR₇₉, Bieniawski 1979) which uses a slightly modified method of assessing the individual parameters of the RMR system. Brechtel et al. (1995) have assessed the use of both RMR₇₄ and RMR₇₉ and found that the resulting difference in the RMR_D (design RMR determined from both the RMR and Q systems) is small and does not significantly affect the rock mass strength determination.

RMR_D is calculated by converting Q to RMR and averaging both the converted Q and the RMR. The value of Q is converted to RMR by using a correlation developed by Bieniawski (1976):

$$RMR_{CAL} = 9 \times \ln(Q) + 44 . \quad (6-1)$$

The design RMR is then determined as:

$$RMR_D = \frac{RMR_{70} + RMR_{CAL}}{2} . \quad (6-2)$$

The rock mass strengths are generated for five classes of rock mass quality based on the cumulative frequencies of occurrence of 5%, 20%, 40%, 70%, and 90% as presented in Section 5.0. The values of Q , RMR_{CAL} , RMR_{70} , and RMR_D are listed in Table 6-1 for the Tptpmn. The use of the RMR_D values in the rock mass strength determination is described in the following sections.

Table 6-1. Tabulation of Q , RMR_{70} , and Design RMR_D Values for the Five Classes of Rock Mass Quality in the Tptpmn

	Rock Mass Quality Class				
	1	2	3	4	5
Q	0.14	0.29	0.42	1.39	10.56
RMR_{CAL}	26	33	36	47	65
RMR_{70}	50	55	58	63	67
RMR_D	38	44	47	55	66

6.2.1 Yudhbir Criterion

Yudhbir et al. (1983) selected a strength criterion proposed by Bieniawski (1974b) for rock materials:

$$\sigma_1 = A \sigma_c + B \sigma_c \left(\frac{\sigma_3}{\sigma_c} \right)^\alpha , \quad (6-3)$$

where

- σ_c = intact rock uniaxial compressive strength,
- σ_1 = the strength of the rock mass,
- σ_3 = the confining stress,
- A = 1.0 for intact rock or $f(RMR)$ for rock mass, and
- α, B = rock material constants dependent on the rock type.

Yudhbir et al. (1983) developed an expression for A that makes the above strength criterion applicable to rock masses:

$$A = e^{0.0765(RMR) - 7.65} . \quad (6-4)$$

6.2.2 Hoek and Brown Criterion

Hoek and Brown (1988) have developed the following rock mass strength criterion:

$$\sigma_1 = \sigma_3 + \sqrt{m \sigma_c \sigma_3 + s \sigma_c^2}, \quad (6-5)$$

where σ_1 , σ_3 and σ_c are defined above, and m and s are constants which are a function of both the rock properties and the extent to which the rock has been fractured. For undisturbed rock masses (e.g., machine-excavated rock), m and s have been related to RMR as follows:

$$m = m_1 e^{(RMR - 100)/28} \text{ and} \quad (6-6)$$

$$s = e^{(RMR - 100)/9}. \quad (6-7)$$

The parameter m_1 is the value of m for intact rock and is found by fitting Equation 6-5 to triaxial test data from laboratory specimens where the value of s is set equal to one.

6.2.3 Failure Criteria Parameters for Intact Strength Results

Triaxial testing data, developed for 25.4-mm (1.0-in) diameter samples of the Tptpmn, were presented in Section 4.2, Table 4-6. Failure criteria based on the NRG data in Table 4-6 were used to estimate rock mass strength. The subsequent addition of test results from SD-9 and SD-12 to the database was not judged to change the intact failure criteria enough to warrant revising the analysis. Scatter in the NRG data was large and attempts to fit the nonlinear failure criteria presented in Sections 6.2.1 and 6.2.2 resulted in convex-shaped curves if extreme values were removed, or unrealistically low confining pressure effects if all data values were used. Curve parameters for Equations 6-3 and 6-5 were previously derived by Lin et al. (1993a) who analyzed a set of existing, unqualified rock mechanics testing data from the TSw2 unit. These curve parameters were tested against the qualified Tptpmn data by inspection and by error analysis, and were found to fit the NRG intact strength with the same degree of error as the linear least-square failure criteria. Figure 6-1 compares the Yudhbir and Hoek-Brown curves to the confined testing data from Table 4-6. The standard deviations of the NRG data from the curves were 34.3 and 36.6 MPa (Yudhbir and Hoek-Brown, respectively). The goodness of fit was acceptable when compared to the NRG least-square criteria (excluding extreme values) which had a standard deviation of 34.6 MPa.

The parameters B and α for the Yudhbir et al. criteria and m_1 for the Hoek and Brown criteria are listed in Table 6-2. These parameters describe the effect of confining pressure and were used with the mean value of the uniaxial compressive strength tests (179.8 MPa) for the 50.8-mm (2.0-in) diameter samples listed in Table 4-6 to define the intact failure criteria.

Figure 6-1. Comparison of Tptpmn testing data to intact rock mass strength criteria.

Table 6-2. Constants for the Rock Mass Strength Criteria in MPa

		Cumulative Frequency of Occurrence of RMR				
	Parameter	5%	20%	40%	70%	90%
Yudhbir Criterion	A	0.009	0.014	0.017	0.032	0.074
	B			2.00		
	α			0.65		
	σ_c			179.8		
Hoek & Brown Criterion	m	0.88	1.08	1.20	1.60	2.37
	s	0.0010	0.0019	0.0028	0.0066	0.0227
	m_i			8.00		
	σ_c			179.8		
Design Rock Mass Strength (MPa)	a	3.70	5.19	6.28	10.17	20.19
	b	10.59	10.60	10.58	10.45	10.12
	c	0.69	0.71	0.71	0.73	0.75

6.2.4 Design Rock Mass Strengths

Rock mass failure criteria were calculated using the parameters in Table 6-2 for intact rock with adjustment for RMR value at cumulative frequencies of occurrence of 5%, 20%, 40%, 70%, and 90%. Parameter A in the Yudhbir criteria and both m and s in the Hoek and Brown criteria are functions of RMR.

The rock mass strengths determined from both the Yudhbir et al. (1983) and Hoek and Brown (1988) criteria were then averaged to determine a site-specific rock mass strength criterion. The relationship between rock mass strength and confining stress was expressed in the form:

$$\sigma_1 = a + b\sigma_3^c, \quad (6-8)$$

where parameters a, b, and c were determined for RMR value class using a curve fit of data pins between 0 and 3 MPa confining pressure. The parameter values are presented in Table 6-2, and the rock mass strength curves are shown in Figure 6-2. The mean intact uniaxial rock strength is also plotted on Figure 6-2 to illustrate the magnitude of the reduction from intact rock strength to rock mass strength.

6.2.5 Rock Mass Mohr-Coulomb Strength Parameters and Dilation Angles

The Mohr-Coulomb strength parameters, including cohesion (C) and angle of internal friction (ϕ), and the dilation angle are commonly used to describe the rock mass strength in numerical analysis. The strength parameters were developed from a linear fit of strength data pairs (σ_1, σ_3) used to produce the strength envelopes in Figure 6-1. The linear relationship was expressed in the form of Equation 4-1. Parameters σ_c and N were used to generate a rock mass Mohr-Coulomb failure criterion relating shear (τ) and normal stress (σ_n) according to Equation 4-2. The resulting values of C and ϕ for each rock mass class are listed in Table 6-3. The non-associated flow rule suggested by Michelis and Brown (1986), which uses a dilation angle equal to half the internal friction angle, was considered suitable for the tuff rocks of the ESF (Hardy and Bauer 1991) and the resulting values for dilation angles are also listed in Table 6-3. The intact Mohr-Coulomb strength parameters (Section 4.2) are listed in Table 6-3 for comparison to the rock mass values.

6.3 Rock Mass Elastic Moduli

The following correlation between rock mass elastic modulus and RMR has been developed by Serafim and Pereira (1983) and was recommended for use by Hardy and Bauer (1991) for preliminary assessment:

Figure 6-2. Design rock mass strength envelopes for the Tptpmn—Main Drift boreholes.

Table 6-3. Range of Strength Parameters and Dilation Angles for the Mohr-Coulomb Failure Criterion in the Tptpmn

	Intact Rock ¹ Values	Cumulative Frequency of Occurrence of RMR				
		5%	20%	40%	70%	90%
Confinement factor, N	7.4	7.2	7.3	7.4	7.4	7.4
Uniaxial compressive strength, σ_c (MPa)	179.8	6.1	7.6	8.5	12.2	22.1
Cohesion, C (MPa)	33.0 ²	1.1	1.4	1.6	2.2	4.1
Internal friction angle, ϕ (degrees)	49.6 ²	49	49	50	50	50
Dilation angle (degrees)	25	25	25	25	25	25

¹NRG data in Table 4-6

²Calculated using equation 4-3, $\sigma_c = 179.8$ and $N = 7.4$

$$E = 10^{(RMR - 10) / 40}, \quad (6-9)$$

where E is expressed in GPa and $E \leq$ average intact sample modulus = 32.9 MPa. Values of rock mass moduli have been calculated for the five rock mass quality classes (using RMR_{79} as shown in Table 6-1) and are listed in Table 6-4.

Table 6-4. Range of Estimated Rock Mass Modulus (GPa) for the Tptpmn

Cumulative Frequency of Occurrence of RMR				
5%	20%	40%	70%	90%
5.07	7.01	8.40	13.23	25.03

6.4 Rock Mass Poisson's Ratio

Empirical relationships to estimate Poisson's ratio from rock mass quality are not available. The mean value of Poisson's ratio from laboratory tests (Section 4.2) were adopted as the rock mass Poisson's ratio. The rock mass Poisson's ratio for the Tptpmn is 0.21. No adjustments for rock class are recommended.

This page intentionally left blank.

7.0 References

- Barton, C.C., W.R. Page, and T.L. Morgan (1989). *Fractures in Outcrops in the Vicinity of Drill Hole USW G-4, Yucca Mountain, Nevada: Data Analysis and Compilation*, Open File Report 89-92, U.S. Geological Survey, Denver, CO.
- Barton, N.R., R. Lien, and J. Lunde (1974). Engineering Classification of Rock Masses for the Design of Tunnel Support, *Rock Mechanics*, 6(4):189-236.
- Bieniawski, Z.T. (1974a). Geomechanics Classification of Rock Masses and Its Application to Tunneling, *Advances in Rock Mechanics: Reports of Current Research, Proceedings of the Third Congress of the International Society for Rock Mechanics, Denver, CO, September 1-7, 1974*, National Academy of Sciences, Washington, DC, Vol. II, Pt. A, 27-38.
- Bieniawski, Z.T. (1974b). Estimating the Strength of Rock Materials, *Journal of the South African Institute of Mining & Metallurgy*, 74(8):312-320.
- Bieniawski, Z.T. (1976). Rock Mass Classification in Rock Engineering, *Proceedings of the Symposium on Exploration for Rock Engineering, Johannesburg, South Africa, November 1-5, 1976*, A.A. Balkema, Boston, MA, 97-106.
- Bieniawski, Z.T. (1979). The Geomechanics Classification in Rock Engineering Applications, *Proceedings of the Fourth International Congress on Rock Mechanics, Montreaux, Switzerland*, A.A. Balkema, Boston, MA, 2:41-48.
- Brechtel, C.E., M. Lin, E. Martin, and D.S. Kessel (1995). *Geotechnical Characterization of the North Ramp of the Exploratory Studies Facility*, SAND95-0488/1, Yucca Mountain Site Characterization Project, Sandia National Laboratories, Albuquerque, NM.
- Buesch, D.C., R.P. Dickerson, R.M. Drake, and R.W. Spengler (1994). Integrated Geology and Preliminary Cross Section Along the North Ramp of the Exploratory Studies Facility, Yucca Mountain, *Proceedings of the Fifth Annual International High Level Radioactive Waste Management Conference, Las Vegas, NV, May 22-26, 1994*, American Nuclear Society, La Grange Park, IL, 2:1055-1065.
- Buesch, D.C., R.W. Spengler, T.C. Moyer, and J.K. Geslin (1996). *Proposed Stratigraphic Nomenclature and Macroscopic Identification of Lithostratigraphic Units of the Paintbrush Group Exposed at Yucca Mountain, Nevada*, Open-File Report 94-469, U.S. Geological Survey, Denver, CO.
- Byers, F.M. Jr., W.J. Carr, P.P. Orkild, W.D. Quinlivan, and K.A. Sargent (1976). *Volcanic Suites and Related Cauldrons of Timber Mountain-Oasis Valley Caldera Complex*,

Southern Nevada, Professional Paper 919, U.S. Geological Survey, Washington, DC.

Carr, W.J. (1984). *Regional Structural Setting of Yucca Mountain, Southwestern Nevada, and Late Cenozoic Rates of Tectonic Activity in Part of the Southwestern Great Basin, Nevada and California*, Open-File Report 84-854, U.S. Geological Survey, Denver, CO.

Deere, D.U. (1963). Technical Description of Rock Cores for Engineering Purposes, *Felsmechanik und Ingeniurgeologie (Rock Mechanics and Engineering Geology)*, 1(1):16-22.

Deere, D.U. (1968). Geological Considerations, *Rock Mechanics in Engineering Practice*, K.G. Stagg and O.C. Zienkiewicz, eds., Wiley & Sons, New York, NY, 1-20.

DOE (U.S. Department of Energy) (1991). *Study Plan 8.3.1.14.2, Revision 0, Studies to Provide Soil and Rock Properties of Potential Locations of Surface and Subsurface Access Facilities (Effective Date 100891) Final*, U.S. Geological Survey, Las Vegas, NV.

DOE (U.S. Department of Energy) (1994). *Exploratory Studies Facility Design Requirements (ESFDR)*, YMP/CM-0019, Rev. 01, United States Department of Energy, Yucca Mountain Site Characterization Project Office, Las Vegas, NV.

Elayer, R.W. (1995). Definition of the Potential Repository Block, Document No. BC0000000-01717-5705-00009, Revision 00, CRWMS/M&O, TRW Environmental Safety Systems, Inc., Las Vegas, NV.

Goodman, R.E., and G. Shi (1985). *Block Theory and Its Application to Rock Engineering*, Prentice-Hall, Inc., Englewood Cliffs, NJ.

Hardy, M.P., and S.J. Bauer (1991). *Drift Design Methodology and Preliminary Application for the Yucca Mountain Site Characterization Project*, SAND89-0837, Sandia National Laboratories, Albuquerque, NM.

Hoek, E., and E.T. Brown (1988). The Hoek-Brown Failure Criterion—A 1988 Update, *15th Canadian Rock Mechanics Symposium, Rock Engineering for Underground Excavations, University of Toronto, 1988*, J.H. Curran, ed., University of Toronto, Department of Civil Engineering, Toronto, Ontario, Canada, 31-38.

International Society of Rock Mechanics (ISRM) (1981). Basic Geotechnical Description of Rock Masses, *International Journal of Rock Mechanics and Mining Sciences & Geomechanics Abstracts*, 18(1):85-110.

Lin, M., M.P. Hardy, and S.J. Bauer (1993a). *Fracture Analysis and Rock Quality Designation Estimation for the Yucca Mountain Site Characterization Project*, SAND92-0449, Sandia National Laboratories, Albuquerque, NM.

Lin, M., M.P. Hardy, and S.J. Bauer (1993b). *Rock Mass Mechanical Property Estimations for*

the Yucca Mountain Site Characterization Project, SAND92-0450, Sandia National Laboratories, Albuquerque, NM.

- Lipman, P.W., R.L. Christiansen, and J.T. O'Connor (1966). *A Compositionally Zoned Ash-Flow Sheet in Southern Nevada*, U.S. Geological Survey Professional Paper 524-F, United States Government Printing Office, Washington, DC.
- Michelis, P., and E.T. Brown (1986). A Yield Equation for Rock, *Canadian Geotechnical Journal*, 23:9-17.
- Moyer, T.C., J.K. Geslin, and D.C. Buesch (1995). *Summary of Lithologic Logging of New and Existing Boreholes at Yucca Mountain, Nevada, July 1994 to November 1995*, Open-File Report 95-102, U.S. Geological Survey, Denver, CO.
- Ortiz, T.S., R.L. Williams, F.B. Nimick, B.C. Whittet, and D.L. South (1985). *A Three-Dimensional Model of Reference Thermal/Mechanical and Hydrological Stratigraphy at Yucca Mountain, Southern Nevada*, SAND84-1076, Sandia National Laboratories, Albuquerque, NM.
- Sawyer, D.A., R.J. Fleck, M.A. Lanphere, R.G. Warren, D.E. Broxton, and M.R. Hudson (1994). Episodic Caldera Volcanism in the Miocene Southwestern Nevada Volcanic Field: Revised Stratigraphic Framework, $^{40}\text{Ar}/^{39}\text{Ar}$ Geochronology, and Implications for Magmatism and Extension, *Geological Society of America Bulletin*, 106(10):1304-1318.
- Scott, R.B., and J. Bonk (1984) *Preliminary Geologic Map of Yucca Mountain, Nye County, Nevada, with Geologic Sections*, Open-File Report 84-494 [scale 1:12,000], U.S. Geological Survey, Denver, CO.
- Scott, R.B., and J.R. Rosenbaum (1986). Evidence of Rotation About a Vertical Axis During Extension at Yucca Mountain, Southern Nevada, [abs.], *Eos Transactions, American Geophysical Union*, 67(16):358.
- Serafim, J.L., and J.P. Pereira (1983). Considerations on the Geomechanical Classification of Bieniawski, *Proceedings, International Symposium on Engineering Geology and Underground Construction, Lisbon, Portugal*, Laboratorio Nacional de Engenharia Civil, Lisbon, Portugal, Vol. II, II.3-II.42.
- Spengler, R.W., and K.F. Fox, Jr. (1989). Stratigraphic and Structural Framework of Yucca Mountain, Nevada, *Radioactive Waste Management and the Nuclear Fuel Cycle*, 13:21-36.
- Spengler, R.W., C.A. Braun, R.M. Linden, L.G. Martin, D.M. Ross-Brown, and R.L. Blackburn (1993). Structural Character of the Ghost Dance Fault, Yucca Mountain, Nevada, *High Level Radioactive Waste Management, Proceedings of the Fourth Annual International Conference, Las Vegas, Nevada, April 26-30, 1993*, American Nuclear Society, La Grange Park, IL, 1:653-659.

- Spengler, R.W., C.A. Braun, L.G. Martin, and C.W. Weisenberg (1994). *The Sundance Fault: A Newly Recognized Shear Zone at Yucca Mountain, Nevada*, Open-File Report 94-49, U.S. Geological Survey, Denver, CO.
- Terzaghi, R.D. (1965). Sources of Error in Joint Surveys, *Geotechnique*, 15:287-304.
- U.S. Geological Survey (USGS) (1984). *A Summary of Geologic Studies through January 1, 1983, of a Potential High-Level Radioactive Waste Repository Site at Yucca Mountain, Southern Nye County, Nevada*, USGS-OFR-84-792, U.S. Geological Survey, Denver, CO.
- Yudhbir, W. Lemanza, and F. Prinzl (1983). An Empirical Failure Criterion for Rock Masses, *Proceedings of the Fifth Congress of the International Society for Rock Mechanics, Melbourne, Australia, April 10-15, 1983*, A.A. Balkema, Boston, MA, B1-B8.

Appendix A

Interim Data Transmittal References

1. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Fracture Data Sheets — Six Groups of Detailed Line Survey Data for the Exploratory Studies Facility, North Ramp Starter Tunnel: Pilot Bore, Bench Cuts, Test Alcove #1, Slash Cuts, Drainage Cuts, and Portal Cuts," U.S. Geological Survey, U.S. Bureau of Reclamation, DTN:GS950308314224.001.
2. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Detailed Line Survey from the North Ramp of the Exploratory Studies Facility, Stations 0+60 to 4+00," U.S. Geological Survey, U.S. Bureau of Reclamation, DTN:GS950508314224.002.
3. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Geotechnical Report for Stations 0+60 to 4+00, North Ramp of the ESF," U.S. Geological Survey, U.S. Bureau of Reclamation, DTN:GS950508314224.003.
4. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Mechanical Properties Data for Drill Hole NRG-6 Samples from Depths of 462.3 ft to 1085.0 ft," Sandia National Laboratories, TDIF No. 301785, DTN:SNL02030193001.004.
5. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Mechanical Properties Data for Drill Hole NRG-6 Samples from Depths of 5.7 ft to 1092.3 ft," Sandia National Laboratories, TDIF No. 304135, DTN:SNL02030193001.022.
6. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Mechanical Properties Data for Drill Hole NRG-7/7A Samples from Depths of 507.4 ft to 881.0 ft," Sandia National Laboratories, TDIF No. 303340, DTN:SNL02030193001.019.
7. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Mechanical Properties Data for Drill Hole NRG-7/7A Samples from Depths of 345.0 ft to 1408.6 ft," Sandia National Laboratories, TDIF No. 304095, DTN:SNL02030193001.021.
8. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Rock Mass Quality for the NRT Stations 60 to 475 m," Sandia National Laboratories, TDIF No. 304267, DTN:SNF32120393001.001.
9. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Rock Mass Quality Data for NRT Stations 475 to 530 m," Sandia National Laboratories, TDIF No. 304283, DTN:SNF32120393001.002.
10. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Rock Mass Quality for NRT Stations 530 to 600 m," Sandia National Laboratories, TDIF No. 304351, DTN:SNF32120393001.003.
11. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Geologic Core Log for Hole USW SD-7," Sandia National Laboratories, DTN:SNT02110894001.001.

12. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Geologic Core Log for SD-9," Sandia National Laboratories, TDIF No. 303743
DTN:SNT02052794001.001 and TDIF No. 304282 DTN:SNT02052794001.002.
13. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Geologic Core Log for SD-12," Sandia National Laboratories, TDIF No. 303744
DTN:SNT02012894001.001.
14. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Geology and Rock Structure Log for Hole USW SD-7, 675-825 ft," Revision 0, Sandia National Laboratories, DTN:SNF29041993002.066. Superseded by .075.
15. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Geology and Rock Structure Log for Hole USW SD-9, 700-850 ft," Revision 0, Sandia National Laboratories, DTN:SNF29041993002.051. Superseded by .076.
16. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Geology and Rock Structure Log for Hole USW SD-12, 650-800 ft," Revision 0, Sandia National Laboratories, DTN:SNF29041993002.054.
17. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Geology and Rock Structure Log for Hole USW UZ-14, 700-850 ft," Revision 0, Sandia National Laboratories, DTN:SNF29041993002.079.
18. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Core Hole Rock Structure Data Summary for Hole USW SD-7, 670-830 ft" Revision 0, Sandia National Laboratories, DTN:SNF29041993002.067.
19. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Core Hole Rock Structure Data Summary for Hole USW SD-9, 700-850 ft, Middle Nonlithophysal Zone," Revision 1, Sandia National Laboratories, DTN:SNF29041993002.069.
20. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Core Hole Rock Structural Data Summary for Hole USW SD-12, 650-800 ft, Middle Nonlithophysal Zone" Revision 1, Sandia National Laboratories,
DTN:SNF29041993002.071.
21. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Core Hole Rock Structure Data Summary for Hole USW UZ-14, Middle Nonlithophysal Zone," Revision 0, Sandia National Laboratories, DTN:SNF29041993002.080.
22. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Estimated Rock Mass Quality Indices Based on Core Log Data for Hole USW NRG-6, 710-1100 ft, TSw2 Unit," Revision 4, Sandia National Laboratories, DTN:SNF29041993002.074.

23. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Estimated Rock Mass Quality Indices Based on Core Log Data for Hole USW NRG-7/7A, 770-1510 ft, TSw2 Unit," Revision 4, Sandia National Laboratories, DTN:SNF29041993002.073.
24. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Estimated Rock Mass Quality Indices Based on Core Log Data for Hole USW SD-7, 670-830 ft, TS Middle Nonlithophysal Zone," Revision 0, Sandia National Laboratories, DTN:SNF29041993002.068.
25. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Estimated Rock Mass Quality Indices Based on Core Log Data for Hole USW SD-9, 700-850 ft, TS Middle Nonlithophysal Zone," Revision 1, Sandia National Laboratories, DTN:SNF29041993002.070.
26. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Estimated Rock Mass Quality Indices Based on Core Log Data for Hole USW SD-12, 650-800 ft, Middle Nonlithophysal Zone," Revision 1, Sandia National Laboratories, DTN:SNF29041993002.072.
27. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Estimated Rock Mass Quality Indices Based on Core Log Data for Hole USW UZ-14, 700-850 ft, TS Middle Nonlithophysal Zone," Revision 0, Sandia National Laboratories, DTN:SNF29041993002.065.
28. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Rock Mass Mechanical Properties Estimates for Topopah Spring Middle Nonlithophysal Zone (NRG-6, NRG-7/7A, SD-7, SD-9, SD-12 and UZ-14)," Revision 1, Sandia National Laboratories, DTN:SNF29041993002.082.
29. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "Rank-Ordered Rock Mass Quality Indices Q and RQD for Boreholes NRG-6, NRG-7/7A, SD-7, SD-9, SD-12 and UZ-14," Revision 1, Sandia National Laboratories, DTN:SNF29041993002.081.
30. Interim Data Transmittal, Yucca Mountain Site Characterization Project, "TS Main Drift Cross Section Version QA3," Sandia National Laboratories, DTN:SNF29041993002.078.

Appendix B

Rank-Ordered Rock Mass Quality Estimates for the Tptpmn

Table B-1. Rank-Ordered Rock Mass Quality Data for Tptpmn

Count	Cumulative Frequency of Occurrence	Q	RMR	RQD
1	1%	0.11	45.98	0
2	3%	0.13	47.93	0
3	4%	0.13	48.69	0
4	6%	0.14	50.10	0
5	7%	0.18	50.50	0
6	9%	0.19	51.50	0
7	10%	0.20	52.20	0
8	12%	0.26	52.40	0
9	13%	0.26	53.00	0
10	14%	0.26	53.07	0
11	16%	0.28	53.19	0
12	17%	0.29	54.31	2
13	19%	0.29	54.72	4
14	20%	0.29	54.81	4
15	22%	0.29	55.12	5
16	23%	0.30	55.17	5
17	25%	0.30	55.20	6
18	26%	0.30	56.07	6
19	28%	0.32	56.16	7
20	29%	0.32	56.24	7
21	30%	0.33	56.50	8
22	32%	0.34	56.60	8
23	33%	0.36	56.60	10
24	35%	0.38	56.75	10
25	36%	0.38	56.95	10
26	38%	0.38	57.00	11
27	39%	0.40	57.58	11
28	41%	0.42	57.77	12
29	42%	0.45	57.95	12
30	43%	0.46	58.07	13
31	45%	0.53	58.07	13
32	46%	0.59	58.10	14
33	48%	0.61	58.73	15
34	49%	0.61	58.83	15
35	51%	0.70	59.17	16

Table B-1. *continued*

Count	Cumulative Frequency of Occurrence	Q	RMR	RQD
36	52%	0.74	59.34	17
37	54%	0.75	59.73	17
38	55%	0.78	60.00	18
39	57%	0.80	60.07	18
40	58%	0.80	61.23	19
41	59%	0.91	61.33	20
42	61%	0.92	61.43	24
43	62%	0.95	61.51	25
44	64%	0.96	61.52	25
45	65%	1.15	61.61	26
46	67%	1.18	61.70	28
47	68%	1.31	62.71	28
48	70%	1.39	62.76	29
49	71%	1.52	63.13	29
50	72%	1.55	63.33	30
51	74%	1.81	63.40	32
52	75%	1.91	63.70	32
53	77%	1.91	63.76	33
54	78%	2.37	64.07	36
55	80%	2.89	64.07	40
56	81%	2.97	64.39	41
57	83%	3.05	64.75	41
58	84%	3.64	65.44	42
59	86%	4.00	65.50	46
60	87%	4.23	65.62	48
61	88%	5.00	66.50	48
62	90%	10.56	66.66	48
63	91%	10.79	67.09	52
64	93%	11.05	67.50	62
65	94%	12.00	67.54	64
66	96%	12.38	69.50	65
67	97%	14.93	70.45	78
68	99%	21.00	75.50	82
69	100%	33.33	76.72	94

This page intentionally left blank.

Appendix C

USW SD-7, SD-9, SD-12 and UZ-14 Core Logs and Data

Geology and Rock Structure Log

Core Hole Rock Structural Data Summary

Estimated Rock Mass Quality Indices Based on Core Log Data

USW SD-7 CORE LOGS AND DATA

Geology and Rock Structure Log

Core Hole Rock Structural Data Summary

Estimated Rock Mass Quality Indices Based on Core Log Data

**YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
GEOLOGY AND ROCK STRUCTURE LOG**

Hole USW SD-7, 675-825 ft

Sandia National Laboratories

Print Date: 7/3/95

WBS 1.2.3.2.6.2

QA:1

Revision 0

BOREHOLE ID: USW SD-7
STUDY PLAN NO: 8.3.1.2.2.1
CORE SIZE: PQ
DRILL DATES: 1/25/95-1/27/95
GROUND ELEV: 4470.0 ft
COORDINATES: N758949.76
E561240.29

TOTAL DEPTH: 675-825 ft
ANGLE FROM VERT: 0°
AZIMUTH: NA

Field Rock Structure

Logged by:

A. Mendenhall
D. Switzer
C. Henson
S. Hopkins
P. Ringgenberg
M. Wagner
R. Wilcoxon
R. Morris
M. Pitterle
J. Kirkwood
C. Hermes
D. Hattler

Relogged by:

Eric R. Martin Agapito Associates, Inc.

Lithology and Stratigraphy

Logged by:

D. Engstrom Sandia National Laboratories

Checked by:

Eric R. Martin Agapito Associates, Inc.

Log prepared by Agapito Associates, Inc. for Sandia National Laboratories

EXPLANATION GEOLOGY AND ROCK STRUCTURE

FRACTURE TYPE OR FEATURE

- N Natural fractures are indicated by mineral coatings, evidence of weathering, slickensides, lack of rematch/fit between sides or by surfaces that form an ellipse in the core.
- C Coring-induced fractures are generally normal to the axis of the core or indicate some torquing of the core. They are typically clean, fresh and fit tightly back together.
- I Indeterminate fractures are those not clearly described as "N" or "C." This includes fracture surfaces that have been shaped by drilling rotation.
- H Handling-induced fractures are formed in the core by removal from the core barrel or placement in the core box. These fractures are witnessed and, according to BTP-SMF-008, are by the SMF personnel by lines parallel to the fracture on both sides of the core. "H" fractures are typically not recorded in the log unless there is a specific reason.
- V Vug or large void.
- P Foliation plane due to gravity flattening upon deposition, not a fracture.

LOST CORE AND RUBBLE

LOST CORE

20 x RUBBLE ZONE

(with average maximum diameter of rubble pieces to nearest 0.01 ft;
NM = not measured)

HARDNESS (Subjective estimate, YMP procedures do not allow core to be broken or scratched etc.)

- 1 Extremely Hard—Cannot be scratched, chipped only with repeated heavy hammer blows.
- 2 Very Hard—Cannot be scratched, broken only with repeated heavy hammer blows.
- 3 Hard—Scratched with heavy pressure, breaks with heavy hammer blow.
- 4 Moderately Hard—Scratched with light-moderate pressure, breaks with moderate hammer blow.
- 5 Moderately Soft—Grooved (16th in.) with moderate heavy pressure, breaks with light hammer blow.
- 6 Soft—Grooved easily with light pressure, scratched with fingernail, breaks with light-moderate manual pressure.
- 7 Very Soft—Readily gouged with fingernail, breaks with light manual pressure.
- 8 Soil Like—Cohesive
- 9 Soil Like—Non-cohesive

WEATHERING

- F Fresh—Rock and fractures not oxidized or discolored, no separation of grains, change of texture or solutioning.
- S Slightly Weathered—Oxidized or discolored fractures and nearby rock, some dull feldspars, no separation of grains, minor leaching.
- M Moderately Weathered—Fractures and most of rock oxidized or discolored, partial separation of grains, crystals rusty or cloudy, moderate leaching of soluble minerals.
- I Intensely Weathered—Fractures and rock totally oxidized or discolored, extensive clay alteration, leaching complete, grain separation extensive, rock is friable.
- D Decomposed—Grain separation and clay alteration complete.

PLANARITY

- P Planar V Very rough, stepped, near-normal steps and ridges occur.
- C Curved R Rough, large angular asperities can be seen.
- S Stepped M Moderately rough, asperities clearly visible, surface has an abrasive feel; to slightly rough, small asperities are visible and can be felt.
- I Irregular S Smooth, no asperities, smooth to the touch.
- P Polished, slickensided, extremely smooth and shiny.

ROUGHNESS

INFILLING THICKNESS AND MINERALIZATION

C Clean, no filling.	C Clean	CA Calcite
S Very thin, surface sheen	WC White, crystalline	SI Silica
T Thin (up to 0.1 inches)	WN White, non-crystalline	MN Manganese
M Moderately thick (0.1 - 0.4 inches)	TD Brown dendritic	CL Clay
V Very thick (0.4 - 1.0 inches)	TC Tan crystalline	BC Black crystalline
E Extremely thick, greater than 1.0 inches)	TN Tan, non-crystalline	BD Black dendritic

EXPLANATION (concluded) GEOLOGY AND ROCK STRUCTURE

CORE RQD

Core RQD is calculated using piece lengths that are defined by all fractures (type N, I, and C) that exist in the core when it is removed from the core barrel. Only handling-induced breaks are discounted in piece length determination. RQD is calculated as:

$$RQD = \frac{\sum \text{Piece lengths} \geq 0.33 \text{ ft}}{\text{Interval length}} \times 100.$$

RQD is calculated for both the core run interval (run RQD) and even 10-ft intervals. If a piece length ≥ 0.33 ft crosses over a 10-ft interval boundary, the portion of the piece length that occurs in the 10-ft interval is included in the summation.

ESTIMATED PERCENTAGE LITHOPHYSAL & OTHER CAVITIES

The percentage of lithophysal voids and other cavities is estimated for each core run interval where sufficient whole core is available. Excessive lost core and rubble zones may prevent the estimate on specific core runs. The estimate is based on comparison of the core with charts designed for estimating the proportions of various rock or mineral components. Estimates are then spot checked using a quantitative graphical summation technique to calculate the percent area occupied by lithophysal cavities in core photographs or video tape.

The estimated percent cavities volume for core runs is used to calculate a run length, weighted average for even 10-ft intervals. (Runs for which percent cavities cannot be determined are assumed to have the average percentage for the 10-ft interval; intervals for which the percent cavities were not estimated are labeled "Not Measured;" zones containing vapor-phase alteration and very small or no lithophysal cavities are labeled as <1%).

USW SD-7 (1 of 2)
Stratigraphic and Thermal-Mechanical Units Summary
0 - 800 ft

*interval from 330.5 to 362.6 contains very limited recovery of bedded till. Yucca Mountain Tuff is not recognized in this interval. Pah Canyon Tuff was not found but may exist in unrecovered interval from 342.0 to 362.6

Date: 7/5/95

USW SD-7 (2 of 2)
Stratigraphic and Thermal-Mechanical Units Summary
800 - 950 ft

Date: 7/7/95

- ¹ Lithologic log of Borehole USW SD-7. Dale Engstrom, unpublished data.
- ² Thermal-mechanical units as defined by Buesch, et al., USGS Open File Report 94-469, 1996. "Proposed stratigraphic nomenclature and macroscopic identification of lithostratigraphic units of the Paintbrush Group exposed at Yucca Mountain, Nevada."

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapito Associates, Inc.

Page 1 of 6

DEPTH (FT)	CORE		FRACTURES						ROCK QUALITY DESIGNATION-RQD (%)					FRACTURES OPEN (FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL VAPOR PHASE AND OTHER CAVITIES		ARGILLIC LITHOPHYSAL VAPOR PHASE DEHYDRIFICATION	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	% RECOVERY (RUN ROD-*)	LOST CORE & RUMBLE	PLANARITY	IRREGULARITY	SWELL	THICKNESS AND MINERALS	ORP	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDETERMINATE + INDUCED			1	2			
680.0	RUN 129	52 (11)																					487.8-682.5 ft. TOPOPAH SPRING UPPER LITHOPHYSAL ZONE cont'd. Pale red-brown (2.5R7/4), close-spaced small irregular-shaped lithophysae, coated with vapor phase rims, 2-4mm light pink-gray alteration halo makes 15-20% of rock volume, 5-6% is 1-3mm blue alteration border and mm-size blue alteration streaks through groundmass, 75% is unaltered, 2-3% quartz lathite soft lithics up to 50mm, 2-3% feldspar phenocrysts, trace biotite, poorly developed foliation.
685.0	RUN 129	41 (0)																					671.6-675.8 ft. Unrecovered.
																							676.7-677.8 ft. Broken.
																							678.9-679.3 ft. Rubble.
																							679-682.5 ft. Unrecovered.
690.0	RUN 131	100 (0)																					682.5-800.3 ft. TOPOPAH SPRING MIDDLE NONLITHOPHYSAL ZONE. Pale orange-gray (5YR7/2) densely welded, devitrified, with very weakly lithophysal cognate perime, wavy sub-horizontal lines of alteration may be replacement of flattened nonlithophysal perime, 5-7% 3-5mm long streaks of alteration apparently nucleated by small perime, rare small 3mm white subangular lithics especially at 694.1-714.7 ft., 2-3% feldspar phenocrysts, trace biotite.
695.0	RUN 131	76 (0)																					682.5-684.3 ft. Rubble.
																							684.3-684.6 ft. Unrecovered.
																							694.5-695.6 ft. Unrecovered.
																							695.6-697.6 ft. Broken.
																							697.6-699.6 ft. Unrecovered.
700.0	RUN 132	56 (0)																					

Structure file: SD7US72.STR Lithology (1):

Date: 06/07/95

H11.9 = 5.00

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapilo Associates, Inc.

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DESIGNATION (RQD) (%)				FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSEAL AND OTHER CAVITIES	AMCLIC LITHOPHYSEAL VAPOR PHASE DEVIATRITION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY			
	INTERVAL	% RECOVERY (SUN ROD-CH)	LOST CORE & RUBBLS	FRACTURE TYPE	PLANARITY	ROUGHNESS	TWILL THICKNESS AND MINERALS	DIP	INDUCED	RICE LENGTH	VERY POOR 15	POOR 30	FAIR 45	GOOD 55	NATURAL AND INDETERMINATE (+ INDUCED)	10							20	30	
705.0	RUN 134	100 (21)	.02 .15 .15	H M H	P5 P5 P5	SBD SBD SBD	90 75 80		-50					13%				<1%							682.5-803.3 ft. TOPOPAH SPRING MIDDLE NONLITHOPHYSEAL ZONE cont'd. Pale orange-gray (7.5R7/2) densely welded, devitrified, 10-15% porrice that is close to indistinguishable from matrix, light blue-gray alteration around nonlithophyal patrice shes, grainy devitrified groundmass, 10% light blue-gray alteration streaks, 1-2% feldspar phenocrysts, <1% biotite, joint orientation dominantly 30° to core axis or horizontal. 707.0-709.2 ft. Broken.
710.0	RUN 137	100 (10)	.05 .10 .15	H I H	P5 P5 P5	SBD SBD SBD	90 90 90		-70					7%				<1%							
715.0	RUN 137	100 (10)	.05 .10 .15	H I H	P5 P5 P5	SBD SBD SBD	90 90 90		-70					7%				<1%							
720.0	RUN 139	100 (10)	.05 .10 .15	H I H	P5 P5 P5	SBD SBD SBD	90 90 90		-70					7%				<1%							
725.0	RUN 139	100 (10)	.05 .10 .15	H I H	P5 P5 P5	SBD SBD SBD	90 90 90		-70					7%				<1%							725.7-726.1 ft. Unrecovered.

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DESIGNATION (RQD) (%)					FRACTURES (PER 10 FT)		HAZARDOUS WEATHERING	ESTIMATED % LITHOMYCELE AND OTHER CAVITIES	AIR/GAS LITHOMYCELE VAPOR PHASE DEVIOLATION	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
	INTERVAL	% RECOVERY (RUN ADD-ON)	LOST CORE & NUMBER	FRACTURE TYPE	PLANARITY/BOUNDRY	INFILL	THICKNESS AND MINERALS	DIP	REDUCED	PRICE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDETERMINATE (+ INDICATED)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
	100	(53)		M	PS	BSI	SWH	75 40								15 20 30																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES								ROCK QUALITY DESIGNATION (RQD) (%)					FRACTURES (PER 10 FT)					FRACTION	WEATHERING	ESTIMATED % LITHOPHYSEAL AND OTHER CAVITIES	ARGILLIC LITHOPHYSEAL VAPOR PHASE DEVITRIFICATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	% RECOVERY (RUR ROD-2)	LOST CORE	TYPE	PLANARITY/IRREGULARITY	INFILL	PRECEDENCE AND MINERALS	CM	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDUCED (PER 10 FT)	10	20	30							
755.0	RUN 144	99 (4.3)	0.08	I	CH	CH	C	90	50	.55	48%									3	A	<1%				682.5-803.3 ft. TOPOPAH SPRING MIDDLE NONLITHOPHYSEAL ZONE cont'd. Pale orange-gray (7.5R7/2) densely welded, devitrified, 10-15% pumice that is close to indistinguishable from matrix, light blue-gray alteration around nonlithophyseal pumice sites, grainy devitrified groundmass, 10% light blue-gray alteration streaks, 1-2% feldspar phenocrysts, <1% biotite, joint orientation dominantly 30° to core axis or horizontal.
760.8	RUN 145		.15	I	PH	PS	C	90	80	.40																
765.0		100 (13.1)	.07	I	PH	PS	C	50		.42										3	B	<1%				765.4-767.4 ft. Broken.
770.0	RUN 146			I	PH	PS	C	30		.90																
775.0	RUN 147	100 (13.1)	.02	I	PH	PS	C	50		.95										3	B					771.4-772.8 ft. Broken.
			.25	I	PH	PS	C	75	80	.45	17%															

Structure file: S07ABV2.27M

Lithology file:

Date: 08/07/95

spring v 9.40

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DETERMINATION (RQD) (%)					FRACTURES (PER 10 FT)		HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSE AND OTHER CAVITIES	MICRO- LITHOPHYSE VAPOR PHASE DEVITRIFICATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	% RECOVERY (RQD ROD-9)	LOST CORE & NOBLE	FRACTURE TYPE	PLANARITY	REGULARITY	THICKNESS AND MINERALS	QIP	INDICED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDUCED						
780.0	149	100 (149)	26	H	PS	SDO	45						17				3	u				682.5-803.3 ft. TOPOPAH SPRING MIDDLE NONLITHOPHYSEAL ZONE cont'd. Pale orange-gray (7.5YR7/3) densely welded although shard remnants can still be distinguished under the binocular microscope, devitrified, 15-20% cognate pumice nearly indistinguishable from matrix, most of groundmass contains poorly defined 5x10mm light pink alteration spots, 2-4% elongated to subangular crystal-rich soft lithics up to 30mm length, 2-3% small rounded mixed composition hard lithics, mostly dense red- gray or altered light gray, 3-5% feldspar phenocrysts, no biotite seen, mostly low- angle fracture weakly coated by Fe-MnOx dendrites.
785.0	150	98 (150)	22	H	PS	SDO	45										3	u				775.2-775.8 ft. Broken. 777.1-779.3 ft. Broken. 781.1-782.4 ft. Broken. 783.4-784.1 ft. Broken. 786.5-788.4 ft. Broken.
790.0	151	70 (151)	10	H	PS	SDO	35										3	u				790.6-792.2 ft. Unrecovered.
795.0	152	65 (152)	15	H	PS	SDO	35										3	u				795.4-797.1 ft. Unrecovered.
798.0	153	10 (153)	10	H	PS	SDO	35										3	u				798.7-799.5 ft. Broken

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapito Associates, Inc.

by AGGREGATE ASSOCIATES, INC.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
DEPTH (FT)	CORE		FRACTURES										ROCK QUALITY DESIGNATION RQD (%)					FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES				ANGULAR LITHOPHYSAL VAPOR PHASE DEVIATION	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
	INTERVAL	% RECOVERY (FROM RQD-PA)	LOST CORE & RUBBLES	FRACTURE TYPE	PLANARITY	ABUNDANCE	THICKNESS	MINERALS	DP	NOTED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDETERMINATE (+ ENHANCED)	10	20	30			20	30	40																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
805.0	RUN 154																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								

Structure File 807REV2 5TH Lithology File

DATE 04/07/95

NP109 v 5.00

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
CORE HOLE ROCK STRUCTURAL DATA SUMMARY
Hole USW SD-7, 670-830 ft

Sandia National Laboratories
 Print Date: 5/4/95
 WBS 1.2.3.2.6.2
 QA-1
 Revision 0

CODING EXPLANATION

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yucca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlith.
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UD—Undifferentiated Overburden
 TCW—Tiva Canyon Welded Unit
 PTn—Upper Paintbrush Nonwelded Unit
 TSw1—Topopah Spring Welded Unit—Lithophysae Rich
 TSw2—Topopah Spring Welded Unit—Lithophysae Poor
 TSw3—Topopah Spring Welded Unit—Vitrophyre
 CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

COLUMN INFORMATION (Page 3)

RQD (%)	$RQD (\%) = \frac{\sum \text{Piece lengths } \geq 0.33 \text{ ft}}{\text{Interval length}} \times 100.$
CORE RQD	Core RQD based on piece lengths defined by all types of fractures (C, I, N and V).
ENHANCED RQD	Effect of fractures identified as coring induced (Type C) are filtered from the piece lengths.
LITHOPHYSAL (and other cavities)	Percent void due to lithophysae and other cavities, estimated visually by counting the number of cavities, estimating the average diameter, calculating the void volume assuming spherical cavities, and normalizing to the core volume. NM—Not Measured
WEATHERING	Subjective evaluation of rock degradation by mechanical/chemical agents: F: Fresh S: Slightly weathered M: Moderately weathered I: Intensely weathered D: Decomposed

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
CORE HOLE ROCK STRUCTURAL DATA SUMMARY
Hole USW SD-7, 670-830 ft

Sandia National Laboratories
Print Date: 5/4/95
WBS 1.2.3.2.6.2
QA:L
Revision 0

HARDNESS Subjective evaluation of resistance to breakage:
1: Extremely hard 4: Moderately hard 7: Very soft
2: Very hard 5: Moderately soft 8: Soil-like, cohesive
3: Hard 6: Soft 9: Soil-like, non-cohesive

COLUMN INFORMATION (Page 4)

FEATURE TYPE Following codes indicate origin of feature:
N: Natural—indicated by mineral coating or evidence of weathering, slickensides, lack of fit between sides.
I: Indeterminate—origin questionable, rotated so that coatings possibly removed.
C: Coring induced—fresh, clean, tightly fitting breaks.
V: Vug or large void.

INCLINATION (degrees) Angle between plane normal to core axis and plane of fracture (Type N and I only).

MINERAL INFILLING Describes the infilling on fracture surfaces (Type N and I only):
C: Clean TD: Brown dendritic CL: Clay
WC: White crystalline TC: Tan crystalline TN: Tan noncrystalline
WN: White noncrystalline CA: Calcite FE: Iron oxide
BC: Black crystalline SI: Silica BN: Brown noncrystalline
BD: Black dendritic MN: Manganese

INFILL THICKNESS Describes the thickness of mineral infillings on the fracture surface (Type N and I only):
S: Very thin, surface sheen V: Very thick (0.4 - 1.0 inches)
T: Thin (up to 0.1 inches) E: Extremely thick, greater than 1.0 inches
M: Moderately thick (0.1-0.4 inches)

PLANARITY Describes the overall shape of the feature (Type N and I only):
P: Planar S: Stepped
C: Curved I: Irregular

ROUGHNESS Describes the local relief of the surface (Type N and I only):
V: Very rough—stepped, near-normal steps and ridges occur.
R: Rough—large angular asperities can be seen.
M: Moderately rough—asperities clearly visible, surface has abrasive feel.
S: Smooth—no asperities, smooth to the touch.
P: Polished—slickensided, extremely smooth and shiny.

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yucca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UO—Undifferentiated Overburden
 TCw—Tiva Canyon Welded Unit
 PTn—Upper Paintbrush Nonwelded Unit
 TSw1—Topopah Spring Welded Unit—Lithophysae Rich
 TSw2—Topopah Spring Welded Unit—Lithophysae Poor
 TSw3—Topopah Spring Welded Unit—Vitrophyre
 CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

Interval — 670-830 ft. Middle Nonlithocypsal Zone

^a Footage in interval may not equal 10 ft because of lost core, rubble, or omission during logging.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
 Core Hole Structural Data Summary
 Hole USW SD-7
 Interval — 670-830 ft, Middle Nonlithophysal Zone

NO. OF FRACTURES W/MINERAL INFILLING TYPE													NO. OF FRACTURES W/ INFILL THICKNESS CODE					NO. OF FRACTURES W/PLANARITY CODE				NO. OF FRACTURES W/ROUGHNESS CODE					
C	WC	WN	BC	BD	ID	TC	CA	SE	MN	CL	TN	FE	BN	S	T	M	V	E	P	C	S	I	V	R	M	S	P
		1							1					1					2						2		
4				4				1	3					8					6	1	1	1		1	4	4	
2				6					3					9					9			1		3		7	
3				4			1							8					10	1	1	1		2	1	9	
5	2	5		5				1						11	2				13	2	2				11	6	
1		4		11					1					16					18	1	1	1	1	1	9	7	
4		2		3					3					8					17		1			1	8	9	
3				5										5					7	3			1		6	3	
7		4												4					7						4	3	
7				4										3					8	1				1	2	6	
3		3		5										7	2				11	1				2	2	7	
7																			1			1		1	1		
5		2		1										4	1				6			1	1	2	4		
1		1													1				1	1		2	1	1	2		
5	2	24	0	48	0	0	1	2	11	0	0	0	0	84	6	0	0	0	116	11	6	8	4	15	56	61	0
9	1.1	14	0	28	0	0	0.6	1.1	6.3	0	0	0	0	93	6.7	0	0	0	32	7.8	4.3	8.7	2.9	11	41	45	0

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Estimated Rock Mass Quality Indices Based on Core Log Data

Hole USW SD-7

Interval — 670–830 ft, Middle Nonlithophysal Zone

END DEPTH	STRATIGRAPHY ZONE	THERMO- MECHANICAL UNIT	Q CLASSIFICATION SYSTEM ¹ Barton et al. (1974)							RMR CLASSIFICATION SYSTEM ² Bieniawski (1979)					
			RQD** (%)	J _n *	J _r	J _a	J _w	SRF*	Q*	C	RQD-I	JS	JC	JW	RMR
680	T.S. U. Lith.	TSw1	8	9.00	2.10	1.22	1.00	5.00	0.38	12	3	8	23.1	15	61.1
690	T.S. M. Nonlith.	TSw2	0	9.00	2.10	1.22	1.00	5.00	0.38	4	3	5	23.1	15	50.1
700	T.S. M. Nonlith.	TSw2	0	9.00	2.10	1.22	1.00	5.00	0.38	12	3	5	23.1	15	58.1
710	T.S. M. Nonlith.	TSw2	13	6.00	1.40	1.00	1.00	5.00	0.61	12	3	8	18.6	15	56.6
720	T.S. M. Nonlith.	TSw2	7	6.00	1.42	1.24	1.00	5.00	0.38	7	3	8	19.2	15	52.2
730	T.S. M. Nonlith.	TSw2	28	3.00	1.76	1.53	1.00	1.00	10.79	12	8	8	18.2	15	61.2
740	T.S. M. Nonlith.	TSw2	13	12.00	1.72	1.30	1.00	7.50	0.19	7	3	5	18.7	15	48.7
750	T.S. M. Nonlith.	TSw2	5	9.00	1.56	1.18	1.00	5.00	0.29	12	3	8	18.2	15	56.2
760	T.S. M. Nonlith.	TSw2	48	9.00	1.70	1.00	1.00	5.00	1.81	12	8	8	20.4	15	63.4
770	T.S. M. Nonlith.	TSw2	36	9.00	1.57	1.67	1.00	5.00	0.75	12	8	8	16.3	15	59.3
780	T.S. M. Nonlith.	TSw2	17	9.00	1.33	1.00	1.00	7.50	0.34	15	3	8	19.0	15	60.0
790	T.S. M. Nonlith.	TSw2	6	12.00	1.36	1.43	1.00	7.50	0.11	12	3	8	17.2	15	65.2
800	T.S. M. Nonlith.	TSw2	10	9.00	2.10	1.22	1.00	7.50	0.26	15	3	8	23.1	15	64.1
810	T.S. L. Lith.	TSw2	4	3.00	2.14	1.50	1.00	1.00	4.76	12	3	8	18.7	15	56.7
820	T.S. L. Lith.	TSw2	0	9.00	2.10	1.22	1.00	5.00	0.38	12	3	8	23.1	15	61.1
830	T.S. L. Lith.	TSw2	0	9.00	2.10	1.22	1.00	5.00	0.38	7	3	5	23.1	15	53.1

J_n*, SRF* = Interval values generated by Monte Carlo simulation, to calculate Q*.

RQD**: If RQD is less than 10, the value 10 is used in the calculation of Q* as per Barton et al. (1974).

¹ Barton, N., & Lien, and J. Lunde, "Engineering Classification of Rock Masses for the Design of Tunnel Support," Rock Mechanics, 6:189-236 (Springer Verlag, 1974).

² Bieniawski, Z.T., "The Geomechanics Classification in Rock Engineering Applications," Proceedings, 4th International Congress on Rock Mechanics, Montreux, Switzerland, 2:41-48 (A. A. Balkema, 1979).

Q

J_n — Joint Set Number
 J_r — Joint Roughness Number
 J_a — Joint Alteration Number
 J_w — Joint Water Reduction Factor
 SRF — Stress Reduction Factor

$$Q = (RQD/J_n)(J_r/J_a)(J_w/SRF)$$

RMR

C — Strength Index
 RQD-I — RQD Index
 JS — Joint Spacing Index
 JC — Discontinuity Condition Index
 JW — Groundwater Index

$$RMR = C + RQD-I + JS + JC + JW$$

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
ESTIMATED ROCK MASS QUALITY INDICES
BASED ON CORE LOG DATA
Hole USW SD-7, 670-830 ft, Middle Nonlithophysal Zone

Smadix National Laboratories
Print Date: 7/3/95
WBS 1.2.3.2.6.2
QA:L
Revision 0

EXPLANATION OF CALCULATION

Rock mass quality indices, Q (Barton et al., 1974) and RMR (Bieniawski, 1979), have been estimated for 10-ft intervals using Rock Structural Data Summaries developed from structural logging of the core, observations of rock conditions in the North Ramp Starter Tunnel, North Ramp tunnel, and laboratory testing data.

- Q is developed to evaluate the distribution of rock mass quality as a basis for developing the range of credible rock mass quality to establish the ground support requirements within rock units and to derive rock mass mechanical properties according to the methodology proposed by Hardy and Bauer (1991). Procedures used in the calculation were:

$$Q = \frac{RQD^{**}}{J_n^{**}} \cdot \frac{J_r}{J_u} \cdot \frac{J_w}{SRF^{*}}$$

Note: Any spatial correlation may be masked by Monte Carlo simulation of J_n and SRF.

where RQD^{**} = Core RQD where all fractures types {natural (N), indeterminate (I), coring induced (C) and vugs (V)} have been considered in determination of RQD. If the RQD is less than 10%, the value used is set to 10 as per Barton et al. (1974). By definition, soil-like materials are considered to have zero RQD.

J_n^{**} = Joint Set Numbers: Cannot be determined from the core log data and are generated by Monte-Carlo simulation assuming a uniform distribution of values between 1 and 12 derived from mapping of the North Ramp tunnel.

J_r = Joint Roughness Number: A weighted average value derived based on the N and I type fractures in the 10-ft interval.

J_a = Joint Alteration Number: A weighted average value derived from the description of N and I type fractures in the interval.

J_w = Joint Water Factor: Set equal to 1.0 assuming dry conditions.

SRF^{*} = Stress Reduction Factor: For nonwelded units, SRF is determined from the ratio of UCS/σ_1 (UCS = unconfined compressive strength, σ_1 = overburden stress). If unconfined compressive strength data is not available for the 10-ft interval, a compressive strength is generated by Monte-Carlo simulation using laboratory

Agapito Associates, Inc.

test data for the thermomechanical units. For welded tuff units, SRF cannot be determined from core log data and is generated by Monte Carlo simulation assuming a distribution derived from mapping of the North Ramp tunnel.

- The use of the Core RQD is conservative since it includes the effect of coring induced breaks. Filtering the effects of coring induced breaks from the RQD calculation ("Enhanced RQD") produced an increase in the mean RQD. The mean values for thermomechanical units in USW SD-7, 670-830 ft, Middle Nonlithophysal Zone are:

	<u>Core RQD</u>	<u>Enhanced RQD</u>
Tsw2, Middle Nonlithophysal Zone	12.2%	24.3%

- RMR is estimated based on the Rock Structural Summary log data, and rock strength data. Procedures used in the calculation were:

$$RMR = C + RQD-I + JS + JC + JW$$

where C = Rock Strength Index: Derived from compressive strength estimated by unconfined compressive strength laboratory test data for the 10-ft interval. If data is not available for the 10-ft interval, a compressive strength is generated by Monte-Carlo simulation using laboratory test data for the thermomechanical unit.

RQD-I = RQD Index: Derived using the Core RQD value for the 10-ft interval.

JS = Joint Spacing Index: Derived from the rock structural data for the 10-ft interval, excludes coring induced features.

JC = Discontinuity Condition Index: Derived from the description of fractures in the 10-ft interval.

JW = Groundwater Index: Assumed dry conditions

- Q and RMR data are presented in log format to associate parameters with depth intervals in the core log; however, any spatial correlation may be masked by Monte-Carlo simulation.

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yucca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UO—Undifferentiated Overburden
 TCw—Tiva Canyon Welded Unit
 PTn—Upper Paintbrush Nonwelded Unit
 TSw1—Topopah Spring Welded Unit—Lithophysae Rich
 TSw2—Topopah Spring Welded Unit—Lithophysae Poor
 TSw3—Topopah Spring Welded Unit—Vitrophyre
 CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Estimated Rock Mass Quality Indices Based on Core Log Data

Hole USW SD-7

Interval — 670-830 ft, Middle Nonliothophysal Zone

END DEPTH	STRATIGRAPHY ZONE	THERMO- MECHANICAL UNIT	Q CLASSIFICATION SYSTEM Barton et al (1974)							RMR CLASSIFICATION SYSTEM Bjerrawski (1979)					
			RQD** (%)	Jn*	Jr	Ja	Jw	SRF*	Q*	C	RQD-I	JS	JC	JW	RMR
680	T S U Lith	TSw1	8	9.00	2.10	1.22	1.00	5.00	0.38	12	3	8	23.1	15	61.1
690	T S M Nonlioth	TSw2	0	9.00	2.10	1.22	1.00	5.00	0.38	4	3	5	23.1	15	50.1
700	T S M Nonlioth	TSw2	0	9.00	2.10	1.22	1.00	5.00	0.38	12	3	5	23.1	15	58.1
710	T S M Nonlioth	TSw2	13	6.00	1.40	1.00	1.00	5.00	0.61	12	3	8	18.6	15	56.6
720	T S M Nonlioth	TSw2	7	6.00	1.42	1.24	1.00	5.00	0.38	7	3	8	19.2	15	52.2
730	T S M Nonlioth	TSw2	28	3.00	1.76	1.63	1.00	1.00	10.79	12	8	8	18.2	15	61.2
740	T S M Nonlioth	TSw2	13	12.00	1.72	1.30	1.00	7.50	0.19	7	3	5	18.7	15	48.7
750	T S M Nonlioth	TSw2	5	9.00	1.56	1.18	1.00	5.00	0.29	12	3	8	18.2	15	56.2
760	T S M Nonlioth	TSw2	48	9.00	1.70	1.00	1.00	5.00	1.81	12	8	8	20.4	15	63.4
770	T S M Nonlioth	TSw2	36	9.00	1.57	1.67	1.00	5.00	0.76	12	8	8	16.3	15	59.3
780	T S M Nonlioth	TSw2	17	9.00	1.33	1.00	1.00	7.50	0.34	15	3	8	19.0	15	60.0
790	T S M Nonlioth	TSw1	6	12.00	1.36	1.43	1.00	7.50	0.11	12	3	8	17.2	15	55.2
800	T S M Nonlioth	TSw2	10	9.00	2.10	1.22	1.00	7.50	0.26	15	3	8	23.1	15	64.1
810	T S L Lith	TSw2	4	3.00	2.14	1.50	1.00	1.00	4.76	12	3	5	18.7	15	56.7
820	T S L Lith	TSw2	0	9.00	2.10	1.22	1.00	5.00	0.38	12	3	8	23.1	15	61.1
830	T S L Lith	TSw2	0	9.00	2.10	1.22	1.00	5.00	0.38	7	3	5	23.1	15	63.1

Jn*, SRF* = Interval values generated by Monte Carlo simulation, to calculate Q*

RQD** If RQD is less than 10, the value 10 is used in the calculation of Q* as per Barton et al (1974)

Barton, N., R. Luen, and J. Leade, "Engineering Classification of Rock Masses for the Design of Tunnel Support,"

Rock Mechanics, 6 189-236 (Springer Verlag, 1974)

Bjerrawski, Z.T., "The Geomechanics Classification in Rock Engineering Applications," Proceedings, 4th International Congress on Rock Mechanics, Montreux, Switzerland, 2 41-48 (A. A. Balkema, 1979)

Q

Jn — Joint Set Number

Jr — Joint Roughness Number

Ja — Joint Alteration Number

Jw — Joint Water Reduction Factor

SRF — Stress Reduction Factor

$$Q = (RQD/Jn)JrJaJw/SRF$$

RMR

C — Strength Index

RQD I — RQD Index

JS — Joint Spacing Index

JC — Discontinuity Condition Index

JW — Groundwater Index

$$RMR = C + RQD I + JS + JC + JW$$

This page intentionally left blank.

USW SD-9 CORE LOGS AND DATA

Geology and Rock Structure Log

Core Hole Rock Structural Data Summary

Estimated Rock Mass Quality Indices Based on Core Log Data

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

GEOLOGY AND ROCK STRUCTURE LOG

Hole USW SD-9, 700-850 ft

Sandia National Laboratories

Print Date: 3/14/95

WBS 1.2.3.2.6.2.1

QA:L

Revision 0

BOREHOLE ID: USW SD-9
STUDY PLAN NO: 8.3.1.2.2.1
CORE SIZE: HQ
DRILL DATES: 5/94 to 11/94
GROUND ELEV: 4272.5'
COORDINATES: 767,988.6N
561,818.0E

TOTAL DEPTH: 2223.1'
ANGLE FROM VERT: 0°
AZIMUTH: n/a

Field Rock Structure

Logged by:

J. Kirkwood

D. Hattler

A. Mendenhall

R. Wilcoxon

R. Myers

G. Olsen

J. Moyer

D. Switzer

M. Pitterle

Refogged by:

Eric Martin

Drilling Support Division, Drilling
Support and Sample Management
Department, T&MSS

Agapito Associates, Inc.

Lithology and Stratigraphy

Logged by:

D. Engstrom

Sandia National Laboratories

Checked by:

E. Martin

Agapito Associates, Inc.

Log prepared by Agapito Associates, Inc. for Sandia National Laboratories

EXPLANATION GEOLOGY AND ROCK STRUCTURE

FRACTURE TYPE OR FEATURE

- N Natural fractures are indicated by mineral coatings, evidence of weathering, slickensides, lack of rematch/fit between sides or by surfaces that form an ellipse in the core.
- C Coring-induced fractures are generally normal to the axis of the core or indicate some torquing of the core. They are typically clean, fresh and fit tightly back together.
- I Indeterminate fractures are those not clearly described as "N" or "C." This includes fracture surfaces that have been shaped by drilling rotation.
- H Handling-induced fractures are formed in the core by removal from the core barrel or placement in the core box. These fractures are witnessed and, according to BTP-SMF-008, are marked by the SMP personnel by lines parallel to the fracture on both sides of the core. "H" fractures are typically not recorded in the log unless there is a specific reason.
- V Vug or large void.
- P Foliation plane due to gravity flattening upon deposition, not a fracture.

LOST CORE AND RUBBLE

LOST CORE

× 20 × RUBBLE ZONE

(with average maximum diameter of rubble pieces to nearest 0.01 ft;
NM = not measured)

HARDNESS (Subjective estimate, YMP procedures do not allow core to be broken or scratched etc.)

- 1 Extremely Hard—Cannot be scratched, chipped only with repeated heavy hammer blows.
- 2 Very Hard—Cannot be scratched, broken only with repeated heavy hammer blows.
- 3 Hard—Scratched with heavy pressure, breaks with heavy hammer blow.
- 4 Moderately Hard—Scratched with light-moderate pressure, breaks with moderate hammer blow.
- 5 Moderately Soft—Grooved (1/6th in.) with moderate heavy pressure, breaks with light hammer blow.
- 6 Soft—Grooved easily with light pressure, scratched with fingernail, breaks with light-moderate manual pressure.
- 7 Very Soft—Readily gouged with fingernail, breaks with light manual pressure.
- 8 Soil Like—Cohesive
- 9 Soil Like—Non-cohesive

WEATHERING

- F Fresh—Rock and fractures not oxidized or discolored, no separation of grains, change of texture or solutioning.
- S Slightly Weathered—Oxidized or discolored fractures and nearby rock, some dull feldspars, no separation of grains, minor leaching.
- M Moderately Weathered—Fractures and most of rock oxidized or discolored, partial separation of grains, crystals rusty or cloudy, moderate leaching of soluble minerals.
- I Intensely Weathered—Fractures and rock totally oxidized or discolored, extensive clay alteration, leaching complete, grain separation extensive, rock is friable.
- D Decomposed—Grain separation and clay alteration complete.

PLANARITY

- P Planar V Very rough, stepped, near-normal steps and ridges occur.
- C Curved R Rough, large angular asperities can be seen.
- S Stepped M Moderately rough, asperities clearly visible, surface has an abrasive feel; to slightly rough, small asperities are visible and can be felt.
- I Irregular S Smooth, no asperities, smooth to the touch.
- P Polished, slickensided, extremely smooth and shiny.

ROUGHNESS

INFILLING THICKNESS AND MINERALIZATION

C Clean, no filling.	C Clean	CA Calcite
S Very thin, surface sheen	WC White, crystalline	SI Silica
T Thin (up to 0.1 inches)	WN White, non-crystalline	MN Manganese
M Moderately thick (0.1 - 0.4 inches)	TD Brown dendritic	CL Clay
V Very thick (0.4 - 1.0 inches)	TC Tan crystalline	BC Black crystalline
E Extremely thick, greater than 1.0 inches)	TN Tan, non-crystalline	BD Black dendritic

EXPLANATION (concluded) GEOLOGY AND ROCK STRUCTURE

CORE RQD

Core RQD is calculated using piece lengths that are defined by all fractures (type N, I, and C) that exist in the core when it is removed from the core barrel. Only handling-induced breaks are discounted in piece length determination. RQD is calculated as:

$$RQD = \frac{\sum \text{Piece lengths} \geq 0.33 \text{ ft}}{\text{Interval length}} \times 100.$$

RQD is calculated for both the core run interval (run RQD) and even 10-ft intervals. If a piece length ≥ 0.33 ft crosses over a 10-ft interval boundary, the portion of the piece length that occurs in the 10-ft interval is included in the summation.

ESTIMATED PERCENTAGE LITHOPHYSAL & OTHER CAVITIES

The percentage of lithophysal voids and other cavities is estimated for each core run interval where sufficient whole core is available. Excessive lost core and rubble zones may prevent the estimate on specific core runs. The estimate is based on comparison of the core with charts designed for estimating the proportions of various rock or mineral components. Estimates are then spot checked using a quantitative graphical summation technique to calculate the percent area occupied by lithophysal cavities in core photographs or video tape.

The estimated percent cavities volume for core runs is used to calculate a run length, weighted average for even 10-ft intervals. (Runs for which percent cavities cannot be determined are assumed to have the average percentage for the 10-ft interval; intervals for which the percent cavities was not estimated are labeled "Not Measured;" zones containing vapor-phase alteration and very small or no lithophysal cavities are labeled as <1%).

USW SD-9 (1 of 3)

Stratigraphic and Thermal-Mechanical Units Summary

0 - 830 ft

USW SD-9 Stratigraphy (2 of 3)
Stratigraphic and Thermal-Mechanical Units Summary
Detail 53.6 - 157.7 ft

USW SD-9 (3 of 3)

Stratigraphic and Thermal-Mechanical Units Summary

830 - 1479.9 ft

¹ Lithologic log of Borehole USW SD-9. Dale Engstrom, unpublished data.

² U.S. Geological Survey - Graphical Lithologic Log of Borehole USW SD-9 from the surface to the base of the Paintbrush Group. T.C. Moyer and G. Mongano DTN: GS940808314211.041

³ Thermal-mechanical units as defined by Buesch, et al., USGS Open File Report 94-469, 1996, "Revised stratigraphic nomenclature and macroscopic identification of lithostratigraphic units of the Paintbrush Group exposed at Yucca Mountain, Nevada."

Date: 2/21/95

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DESIGNATION (RQD) (%)					FRACTURES (PER 10 FT)					HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES	ARGILLIC LITHOPHYSAL VAPOR PHASE DEVITRIFICATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
	INTERVAL	% RECOVERY (RUN ROD-9)	LOST CORE & RUNNELS	FRACTURE TYPE	PLANARITY/ROUGHNESS	INFILL THICKNESS AND MINERALS	DIP	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDETERMINATE (+ INDUCED)	10	20	30																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
705.0	RUN 89	75																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				</

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DESIGNATION (ROD-4)					FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES	ALGAL LITHOPHYSAL VAPOR PHASE DEVITRIFICATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
	INTERVAL	% RECOVERY (RUN ROD-4)	LOST CORE A RIBBLE	TYPE	PLANARITY	ROUGHNESS	INCL. THICKNESS AND MINERALS	DIP	INDEX	PIECE LENGTH	VERY POOR 2.5	POOR 30	FAIR 75	GOOD 95	EXCELLENT	NATURAL AND INDETERMINATE (+ INJECTED)	80							20	30																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
730.0	RUN 93																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													

DEPTH (FT)	CORE		FRACTURES										ROCK QUALITY DESIGNATION (RQD) (%)		FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES				ARGILLIC LITHOPHYSAL VAPOR PHASE DEVITRIFICATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	% RECOVERY (RUN ROD-S)	LOST CORE	RUBBLE	FRACTURE TYPE	PLANARITY	ROUGHNESS	INFILL	THICKNESS AND	NEURALS	DEF	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INHETERMINATE (+ INDUCED)	H	M	20	40			
753.0	RUN 97	68 (1.1)			M	PH	PS	C	C		45		.33													728.8-788.1 TOPOPAH SPRING MIDDLE NONLITHOPHYSAL. Upper Nonlithophysal Subzone, lithophysae lessen to <10%, densely welded, devitrified, groundmass texture finer, more compact, less grainy, mixed alteration zone with strong pervasive blue (SPB6/2) alteration and 17% white fuzzy 15mm vapor-phase streaks around pumice and lithophysae with islands of unaltered groundmass vs. orange-pink zones of unaltered groundmass speckled by 10% white alteration streaks and 7-8mm alteration spots, 17% white irregular hairline flattened pumice with 10mm fuzzy alteration halo, 1-2% feldspar phenocrysts, no biotite seen, most altered zones speckled by specular hematite, specks of dark olive green on post-oxidation surfaces
760.0	RUN 98	92 (1.1)			N	PH	PS	SNH	3-20		70		.44													751.5-755.1 Broken 752.7-755.1 Unrecovered 757.2-757.9 Broken 757.9-760.6 No Core 760.6-761.3 Broken
765.0	RUN 99	99 (1.1)			N	PH	PS	SNH	5-10		75		.70													765.0 Medium-large lithophysae, 768.2 (borehole video)
770.0	RUN 100	99 (1.1)			N	PH	PS	SNH	5-10		75		.89													769.8-770.4 Unrecovered
775.0	RUN 101	99 (1.1)			N	PH	PS	SNH	5-10		75		.89													

DEPTH (FT)	CORE		FRACTURES								ROCK QUALITY DESIGNATION (RQD) (%)		FRACTURES (PER 10 FT)		HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES	ANGULAR LITHOPHYSAL VAPOR PHASE DEVEGETATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	% RECOVERY (RQD) (%)	TYPE	PLANARITY	ROUGHNESS	INCL. THICKNESS AND MINERALS	INDICED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDURMENTED (1-10 FT)						
776.0	RUN 100	22																		776.4 Pumice reduced to irregular subhorizontal reid lines, vapor-phase mineralization.
779.0	RUN 101	40																		779.0-784.1 Broken 779.0-779.1 Unrecovered 780.2-784.1 Unrecovered
781.0	RUN 102	57																		785.7-788.1 Unrecovered
790.0	RUN 103	39																		788.1-812.5 TOPOPAH SPRING MIDDLE NONLITHOPHYSAL. Lithophysal-Bearing Subzone characterized by small close-spaced circular lithophysae lined by crystalline vapor-phase mineralization after pumice, pumice often extending into cavity wall, in 15-20mm light gray alteration spot with 1-2mm blue alteration border, groundmass more intensely blue pervasively altered from 795.0-802.5.
795.0	RUN 104	31																		791.0-793.5 Broken 791.2-793.5 Unrecovered 795.7-797.0 Broken

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES								ROCK QUALITY DESIGNATION (RQD) (%)					FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES				ANGULAR LITHOPHYSAL VAPOR PHASE DEHYDRATION WEAVING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY	
	INTERVAL	+ RECOVERY (RUN ADD-4)	LOST CORE (B. TUBBLE)	FRACTURE TYPE	PLANARITY/ROUGHNESS	INFILL	THICKNESS AND MINERALS	DIP	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INTERMEDIATE (+ INTERFERS)	M	M			M	M						
NK D	RUN 105		10	I	IV		50	50		40																		788 1-812.5 TOPOPAH SPRING MIDDLE NONLITHOPHYSAL. Lithophysal-Bearing Subzone characterized by small close-spaced circular lithophysae lined by crystalline vapor-phase mineralization after putice, putice often extending into cavity wall, in 15-20mm light gray alteration spot with 1-2mm blue alteration border, groundmass more intensely blue pervasively altered from 795.0-802.5, and much less altered below 803.3, lithophysae increase in size toward 803.3, then decrease in intensity downward.
			15	I	IV		90	35		46																		805.8-806.5 Broken
810 D	RUN 106		15	I	IV		75	75		55																		812.5-845.8, TOPOPAH SPRING MIDDLE NONLITHOPHYSAL. Lower Nonlithophysal Subzone similar to above, dense compact texture, 10% speckled by hazy 5-10mm vapor-phase streaks, some with weak blue border, 1-2% halite vapor-phase silica veinlets with 20mm blue alteration selvage each 2-3 feet, 2-3% white sandine phenocrysts, no biotite, 2% dryline and quartz latite hard lithics that average 5mm
BJ 10			20	I	IV		80	80		60																		817.1-814.3 Broken
820 D	RUN 108		15	I	IV		75	75		50																		
825 D			12	I	IV		75	75		45																		

DEPTH (FT)	CORE		FRACTURES						ROCK QUALITY DESIGNATION (RQD %)					FRACTURES (PER 16 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSEAL AND OTHER CAVITIES				ANGULAR LITHOPHYSEAL VAPOR PHASE DEUTERIFICATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	RECOVERY (% RECOVERED)	LOOSE CORE & RUBBLE	FRACTURE TYPE	PLANARITY/ ROUGHNESS	INFILL THICKNESS AND MINERALS	DP	PRODUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDUCED (% INDUCED)	NI	SI	SI	NI	SI	SI	NI	SI	SI	
8310	109	100 (71)	10		SR	C	90		1.00			40%			1										812.5-845.8, TOPOPAH SPRING MIDDLE NONLITHOPHYSEAL. Lower Nonlithophysal Subzone, similar to above, dense compact texture, 10% speckled by hazy 5-10mm vapor-phase streaks, some with weak blue border, 1-2% hairline vapor- phase silica veinlets with 20mm blue alteration selvage each 2-3 feet, 2-3% white sanidine phenocrysts, no biotite, 2% rhyolite and quartz latite hard lithics that average 5mm
8350	110	100 (54)			PH	PH	80		2.40						15										838.8-839.8, Strong blue alteration zone. 839.4, Strong vertical joints coated by white vapor-phase silica, 4-6mm pink-gray alteration halo and 1-2mm blue alteration border, below 839.8 15-20% wispy blue alteration selvages around hairline silica veinlets with 1-2mm medium-gray alteration halos, vapor-phase vein mineralization includes SiO ₂ and carbonate minerals. 841.4, Upper limit of flat recrystallized pumice with blue alteration halo. 843.5 Alteration increases, light gray 10mm alteration spot around micropumice each 1- 2" rimmed by 2-3mm blue alteration border. Below 845 occasional partially open lithophysae.
8450	111	88 (10)			PH	PH	90		1.70			18%			30										845.8-1187.0, TOPOPAH SPRING LOWER LITHOPHYSEAL ZONE. Medium red- brown (SYR6/3) 3% small pinched oval- shaped lithophysae mostly <20mm, 2-7% light gray pumice less than 35mm with thin brown alteration rims, 1-2% wide variety of lithics majority <25mm, 1-2% sandline and 0.5% biotite phenocrysts, vertical jointing common

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
CORE HOLE ROCK STRUCTURAL DATA SUMMARY
Hole USW SD-9, 700-850 ft, Middle Nonlithophysal Zone

Sandia National Laboratories
Print Date: 6/27/95
WBS 1.2.3.2.6.2
QA:1
Revision 1

REVISION HISTORY

Revision 1 Enhanced RQDs were revised upon discovery of an error in WPLLOG's calculations. This revision replaces Revision 0 in its entirety.

CODING EXPLANATION

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yuca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlith.
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UO—Undifferentiated Overburden
TCw—Tiva Canyon Welded Unit
PTn—Upper Paintbrush Nonwelded Unit
TSw1—Topopah Spring Welded Unit—Lithophysae Rich
TSw2—Topopah Spring Welded Unit—Lithophysae Poor
TSw3—Topopah Spring Welded Unit—Vitrophyre
CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

COLUMN INFORMATION (Page 3)

RQD (%) $RQD (\%) = \frac{\sum \text{Piece lengths} \geq 0.33 \text{ ft}}{\text{Interval length}} \times 100.$

CORE RQD Core RQD based on piece lengths defined by all types of fractures (C, L, N and V).

ENHANCED RQD Effect of fractures identified as coring induced (Type C) are filtered from the piece lengths.

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Sandia National Laboratories

Print Date: 6/27/95

WBS 1.2.3.2.6.2

QA.L

Revision 1

CORE HOLE ROCK STRUCTURAL DATA SUMMARY**Hole USW SD-9, 700-850 ft, Middle Nonlithophysal Zone**

LITHOPHYSAL (and other cavities)	Percent void due to lithophysae and other cavities, estimated visually by counting the number of cavities, estimating the average diameter, calculating the void volume assuming spherical cavities, and normalizing to the core volume. NM—Not Measured		
WEATHERING	Subjective evaluation of rock degradation by mechanical/chemical agents: F: Fresh S: Slightly weathered M: Moderately weathered I: Intensely weathered D: Decomposed		
HARDNESS	Subjective evaluation of resistance to breakage: 1: Extremely hard 2: Very hard 3: Hard 4: Moderately hard 5: Moderately soft 6: Soft 7: Very soft 8: Soil-like, cohesive 9: Soil-like, non-cohesive		

COLUMN INFORMATION (Page 4)

FEATURE TYPE	Following codes indicate origin of feature: N: Natural—indicated by mineral coating or evidence of weathering, slickensides, lack of fit between sides. I: Indeterminate—origin questionable, rotated so that coatings possibly removed. C: Coring induced—fresh, clean, tightly fitting breaks. V: Yug or large void.		
INCLINATION (degrees)	Angle between plane normal to core axis and plane of fracture (Type N and I only).		
MINERAL INFILLING	Describes the infilling on fracture surfaces (Type N and I only): C: Clean WC: White crystalline WN: White noncrystalline BC: Black crystalline BD: Black dendritic TD: Brown dendritic TC: Tan crystalline CA: Calcite SI: Silica MN: Manganese CL: Clay TN: Tan noncrystalline FE: Iron oxide BN: Brown noncrystalline		
INFILL THICKNESS	Describes the thickness of mineral infillings on the fracture surface (Type N and I only): S: Very thin, surface sheen T: Thin (up to 0.1 inches) M: Moderately thick (0.1-0.4 inches) V: Very thick (0.4 - 1.0 inches) E: Extremely thick, greater than 1.0 inches		
PLANARITY	Describes the overall shape of the feature (Type N and I only): P: Planar C: Curved S: Stepped I: Irregular		
ROUGHNESS	Describes the local relief of the surface (Type N and I only): V: Very rough—stepped, near-normal steps and ridges occur. R: Rough—large angular asperities can be seen. M: Moderately rough—asperities clearly visible, surface has abrasive feel. S: Smooth—no asperities, smooth to the touch. P: Polished—slickensided, extremely smooth and shiny.		

Agapito Associates, Inc.

This page intentionally left blank.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Core Hole Structural Data Summary

Hole USW SD-9

Interval—700–850 ft, Middle Neothothysal Zone

BASE OF 10-FT INTERVAL	STRATIGRAPHIC ZONE	THERMO- MECHANICAL UNIT	CORE ROD** %	ENHANCED ROD** %	ESTIMATED % CAVITIES	LOST CORE (%)	RUBBLE ZONE (%)	WEATHERING (R & 10-ft interval)***						HARDNESS (R & 10-ft interval)***																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
								F B M I D						BOOK																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
								1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
716	T.S. C.P. U. Lm.	Tbu1	9	75	2	1.6	0.0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												

* CORE ROD—Determined from place lengths formed by all types of fractures (C, I, N and V).

** ENHANCED ROD—Determined by filtering the effects of fractures identified as coring artifacts (Type C) from the place lengths.

*** Footage is interval may not equal 10 ft because of lost core, rubble, or omission during logging.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Core Hole Structural Data Summary

Hole USW 3D-9

Interval—700–850 ft, Middle Neolithophyal Zone

BASE OF 10-FT INTERVAL	STRATIGRAPHY ZONE	THERMO- MECHANICAL UNIT	FEATURE TYPE				FRACTURE FREQUENCY (ft ⁻¹ sample)	NO. OF FRACTURES WITH INCLINATION (degrees)									
			N	I	C	V		10	20	30	40	50	60	70	80	90	
710	T.S. C.P. U. Lth.	T8w1		2	35		710										
720	T.S. C.P. U. Lth.	T8w1		6	26	2	720										
730	T.S. C.P. U. Lth.	T8w1	3	2	23	1	730										
740	T.S. C.P. U. Lth.	T8w1		4	18		740										
750	T.S. C.P. M. Nonlith.	T8w2	12	10	9		750										
760	T.S. C.P. M. Nonlith.	T8w2	9	9	12		760										
770	T.S. C.P. M. Nonlith.	T8w2	30	4	6	2	770										
780	T.S. C.P. M. Nonlith.	T8w2	6	1	7	1	780										
790	T.S. C.P. M. Nonlith.	T8w2	1		2		790										
800	T.S. C.P. M. Nonlith.	T8w2	4	1	24	1	800										
810	T.S. C.P. M. Nonlith.	T8w2	5	4	21		810										
820	T.S. C.P. M. Nonlith.	T8w2	2	5	22		820										
830	T.S. C.P. M. Nonlith.	T8w2	9	3	10		830										
840	T.S. C.P. M. Nonlith.	T8w2	6	2	8		840										
850	T.S. C.P. M. Nonlith.	T8w2	4		19		850										
TOTAL			71	52	242	7											
PERCENT OF OCCURRENCE			19.1	14	56.1	1.89											

NO. OF FRACTURES W/MINERAL INFILLING TYPE														NO. OF FRACTURES W/INCL THICKNESS CODE							NO. OF FRACTURES W/PLANARITY CODE					NO. OF FRACTURES W/ROUGHNESS CODE					
WC	WN	BC	BD	TD	TC	CA	W	MN	CL	TN	FE	BN	C	S	T	M	V	E	P	C	S	I	V	R	M	S	P				
													2									1									
													8							2	1		2		4	1					
3													2	1	2					4			1		1	3					
													4							2	1				2		1				
	10		3										10	13						19		1			1	11	4				
4		1						1					9	8						10	2	1			1	8	0				
5		3											6	8	2					6		2	2		4	4	2				
4		1											1	8						2	2		2		8						
1													1							1					1						
													8							3	2				1	2	2				
4													6	4						3		1	5	2	3	3	1				
		1						1					6	2						7					5	2					
7								1					4	5	3					9	1	1			3	1	6				
8													2	2	4					9			2	1	2	2	1				
4														1	3					2	1				1	2	1				
3	3	45	0	9	0	0	0	1	2	0	0	0	82	48	14	0	0	0	78	10	6	18	3	24	46	20	0				
2	2.44	38.6	0	7.32	0	0	0	0.81	1.62	0	0	0	60.8	37.7	11.6	0	0	0	70.4	8.28	5.68	14.8	2.88	22.8	46.7	28.8	0				

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT**ESTIMATED ROCK MASS QUALITY INDICES
BASED ON CORE LOG DATA****Hole USW SD-9, 700-850 ft, Middle Nonlithophysal Zone**

Sandia National Laboratories

Print Date: 6/30/95

WBS 1.23.2.6.2.1

QA/L

Revision 1

REVISION HISTORY

Revision 1 Jn and SRF parameters revised because of additional data from tunnel mapping. Revision 0 is superseded in its entirety.

EXPLANATION OF CALCULATION

Rock mass quality indices, Q (Barton et al., 1974) and RMR (Bieniawski, 1979), have been estimated for 10-ft intervals using Rock Structural Data Summaries developed from structural logging of the core, observations of rock conditions in the North Ramp Starter Tunnel and North Ramp tunnel, and laboratory testing data.

- Q is developed to evaluate the distribution of rock mass quality as a basis for developing the range of credible rock mass quality to establish the ground support requirements within rock units and to derive rock mass mechanical properties according to the methodology proposed by Hardy and Bauer (1991). Procedures used in the calculation were:

$$Q = \frac{RQD^{**}}{J_n^{*}} \cdot \frac{J_r}{J_a} \cdot \frac{J_w}{SRF^{*}}$$

Note: Any spatial correlation may be masked by Monte Carlo simulation of Jn and SRF.

where RQD** = Core RQD where all fractures types [natural (N), indeterminate (I), coring induced (C) and vugs (V)] have been considered in determination of RQD. If the RQD is less than 10%, the value used is set to 10 as per Barton et al. (1974). By definition, soil-like materials are considered to have zero RQD.

Jn* = Joint Set Numbers: Cannot be determined from the core log data and are generated by Monte-Carlo simulation assuming a uniform distribution of values between 1 and 12 derived from mapping of the North Ramp tunnel.

Jr = Joint Roughness Number: A weighted average value derived based on the N and I type fractures in the 10-ft interval.

Ja = Joint Alteration Number: A weighted average value derived from the description of N and I type fractures in the interval.

Jw = Joint Water Factor: Set equal to 1.0 assuming dry conditions.

SRF* = Stress Reduction Factor: For nonwelded units, SRF is determined from

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Sandia National Laboratories

Print Date: 6/30/95

WBS 1.2.3.2.6.2.1

OAL

Revision 1

**ESTIMATED ROCK MASS QUALITY INDICES
BASED ON CORE LOG DATA****Hole USW SD-9, 700-850 ft, Middle Nonlithophysal Zone**

the ratio of UCS/σ_1 (UCS = unconfined compressive strength, σ_1 = overburden stress). If unconfined compressive strength data is not available for the 10-ft interval, a compressive strength is generated by Monte Carlo simulation using laboratory test data for the thermomechanical units. For welded tuff units, SRF cannot be determined from core log data and is generated by Monte Carlo simulation assuming a distribution derived from mapping of the North Ramp Tunnel.

- The use of the Core RQD is conservative since it includes the effect of coring induced breaks. Filtering the effects of coring induced breaks from the RQD calculation ("Enhanced RQD") produced an increase in the mean RQD. The mean values for thermomechanical units in USW SD-9 are:

	<u>Core RQD</u>	<u>Enhanced RQD</u>
PTn Unit	48.5%	63.3%
TSw1 Unit	16.4%	43.2%
TSw2 Unit	16.5%	31.6%

- RMR is estimated based on the Rock Structural Summary log data, and rock strength data. Procedures used in the calculation were:

$$RMR = C + RQD-I + JS + JC + JW$$

where

C = Rock Strength Index: Derived from compressive strength estimated by unconfined compressive strength test data for the 10-ft interval. If data is not available for the 10-ft interval, a compressive strength is generated by Monte-Carlo simulation using laboratory test data for the thermomechanical unit.

$RQD-I$ = RQD Index: Derived using the Core RQD value for the 10-ft interval.

JS = Joint Spacing Index: Derived from the rock structural data for the 10-ft interval, excludes coring induced features.

JC = Discontinuity Condition Index: Derived from the description of fractures in the 10-ft interval.

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Sandia National Laboratories

Print Date: 6/30/95

WBS 1.2.3.2.6.2.1

QA.L

Revision 1

ESTIMATED ROCK MASS QUALITY INDICES**BASED ON CORE LOG DATA****Hole USW SD-9, 700-850 ft, Middle Nonlithophysal Zone**

JW = Groundwater Index: Assumed dry conditions

- Q and RMR data are presented in log format to associate parameters with depth intervals in the core log; however, any spatial correlation may be masked by Monte-Carlo simulation.

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yucca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UO—Undifferentiated Overburden
TCw—Tiva Canyon Welded Unit
PTn—Upper Paintbrush Nonwelded Unit
TSw1—Topopah Spring Welded Unit—Lithophysae Rich
TSw2—Topopah Spring Welded Unit—Lithophysae Poor
TSw3—Topopah Spring Welded Unit—Vitrophyre
CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Estimated Rock Mass Quality Indices Based on Core Log Data

Hole USW SD-9

Interval — 700–850 ft, Middle Nonlithophysal Zone

END DEPTH	STRATIGRAPHY ZONE	THERMO-MECHANICAL UNIT	Q CLASSIFICATION SYSTEM ¹ Barton et al. (1974)							RMR CLASSIFICATION SYSTEM ² Bieniawski (1979)					
			RQD** (%)	J _n ^a	J _r	J _a	J _w	SRF*	Q*	C	RQD-I	JS	JC	JW	RMR
710	T.S. C.P. U. Lith.	TSw1	9	12.00	3.00	1.00	1.00	7.50	0.33	2	3	8	28.5	15	56.5
720	T.S. C.P. U. Lith.	TSw1	16	2.00	2.40	1.00	1.00	1.00	19.20	4	3	8	24.0	15	54.0
730	T.S. C.P. U. Lith.	TSw1	41	9.00	2.25	1.00	1.00	5.00	2.05	7	8	8	21.3	15	59.3
740	T.S. C.P. U. Lith.	TSw1	28	12.00	1.67	1.00	1.00	7.50	0.52	7	8	8	20.5	15	58.5
750	T.S. C.P. M. Nonlith.	TSw2	7	9.00	1.65	1.87	1.00	7.50	0.13	7	3	5	16.0	15	46.0
760	T.S. C.P. M. Nonlith.	TSw2	12	12.00	1.58	1.53	1.00	7.50	0.14	4	3	8	17.9	15	47.9
770	T.S. C.P. M. Nonlith.	TSw2	62	9.00	2.20	1.71	1.00	7.50	1.18	12	13	8	19.5	15	67.5
780	T.S. C.P. M. Nonlith.	TSw2	64	9.00	2.33	2.14	1.00	5.00	1.55	7	13	8	18.5	15	61.5
790	T.S. C.P. M. Nonlith.	TSw2	0	9.00	2.10	1.22	1.00	1.00	1.91	15	3	8	23.1	15	64.1
800	T.S. C.P. M. Nonlith.	TSw2	8	12.00	1.60	1.00	1.00	7.50	0.18	15	3	8	20.7	15	61.7
810	T.S. C.P. M. Nonlith.	TSw2	19	12.00	2.56	1.89	1.00	7.50	0.29	12	3	8	20.8	15	58.8
820	T.S. C.P. M. Nonlith.	TSw2	52	6.00	1.71	1.00	1.00	5.00	2.97	12	13	8	18.7	15	66.7
830	T.S. C.P. M. Nonlith.	TSw2	48	9.00	1.50	2.17	1.00	5.00	0.74	12	8	8	15.0	15	58.0
840	T.S. C.P. M. Nonlith.	TSw2	78	6.00	2.13	2.50	1.00	1.00	11.05	12	17	8	15.1	15	67.1
850	T.S. C.P. M. Nonlith.	TSw2	18	12.00	2.00	3.00	1.00	7.50	0.13	12	3	8	13.5	15	51.5

J_n*, SRF* — interval values generated by Monte Carlo simulation; to calculate Q*.

RQD** — If RQD is less than 10, the value 10 is used in the calculation of Q* as per Barton et al. (1974).

¹ Barton, N., R. Lien, and J. Lunde, "Engineering Classification of Rock Masses for the Design of Tunnel Support,"

Rock Mechanics, 6:189-236 (Springer Verlag, 1974).

² Bieniawski, Z.T., "The Geomechanics Classification in Rock Engineering Applications," Proceedings, 4th International Congress on Rock Mechanics, Montreux, Switzerland, 2:41-48 (A. A. Balkema, 1979).

Q

J_n — Joint Set Number

J_r — Joint Roughness Number

J_a — Joint Alteration Number

J_w — Joint Water Reduction Factor

SRF — Stress Reduction Factor

$$Q = (RQD/J_n/J_r/J_a/J_w/SRF)$$

RMR

C — Strength Index

RQD-I — RQD Index

JS — Joint Spacing Index

JC — Discontinuity Condition Index

JW — Groundwater Index

$$RMR = C + RQD-I + JS + JC + JW$$

USW SD-12 CORE LOGS AND DATA

Geology and Rock Structure Log

Core Hole Rock Structural Data Summary

Estimated Rock Mass Quality Indices Based on Core Log Data

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

GEOLOGY AND ROCK STRUCTURE LOG

Hole USW SD-12, 650-800 ft

Sandia National Laboratories

Print Date: 3/14/95

WBS 1.2.3.2.6.2.1

QA:L

Revision 0

BOREHOLE ID: USW SD-12
STUDY PLAN NO: 8.3.1.2.2.1
CORE SIZE: HQ
DRILL DATES: 5/94 to 8/94
GROUND ELEV: 4330.0'
COORDINATES: 761,957N
561,606E

TOTAL DEPTH: 1435.3'
ANGLE FROM VERT: 0°
AZIMUTH: n/a

Field Rock Structure

Logged by:

R. Henson
D. Hattler
M. Wagner
C. Hermes
D. Switzer
M. Pitterle

Relogged by:

Eric Martin

Drilling Support Division, Drilling
Support and Sample Management
Department, T&MSS

Agapito Associates, Inc.

Lithology and Stratigraphy

Logged by:

D. Engstrom

Sandia National Laboratories

Checked by:

Eric Martin

Agapito Associates, Inc.

Log prepared by Agapito Associates, Inc. for Sandia National Laboratories

EXPLANATION GEOLOGY AND ROCK STRUCTURE

FRACTURE TYPE OR FEATURE

- N** Natural fractures are indicated by mineral coatings, evidence of weathering, slickensides, lack of rematch/fit between sides or by surfaces that form an ellipse in the core.
- C** Coring-induced fractures are generally normal to the axis of the core or indicate some torquing of the core. They are typically clean, fresh and fit tightly back together.
- I** Indeterminate fractures are those not clearly described as "N" or "C." This includes fracture surfaces that have been shaped by drilling rotation.
- H** Handling-induced fractures are formed in the core by removal from the core barrel or placement in the core box. These fractures are witnessed and, according to BTP-SMF-008, are marked by the SMF personnel by lines parallel to the fracture on both sides of the core. "H" fractures are typically not recorded in the log unless there is a specific reason.
- V** Vug or large void.
- P** Foliation plane due to gravity flattening upon deposition, not a fracture.

LOST CORE AND RUBBLE

LOST CORE

$\times 20 \times$ RUBBLE ZONE
(with average maximum diameter of
rubble pieces to nearest 0.01 ft;
NM = not measured)

HARDNESS (Subjective estimate, YMP procedures do not allow core to be broken or scratched etc.)

- 1 Extremely Hard—Cannot be scratched, chipped only with repeated heavy hammer blows.
- 2 Very Hard—Cannot be scratched, broken only with repeated heavy hammer blows.
- 3 Hard—Scratched with heavy pressure, breaks with heavy hammer blow.
- 4 Moderately Hard—Scratched with light-moderate pressure, breaks with moderate hammer blow.
- 5 Moderately Soft—Grooved (16th in.) with moderate heavy pressure, breaks with light hammer blow.
- 6 Soft—Grooved easily with light pressure, scratched with fingernail, breaks with light-moderate manual pressure.
- 7 Very Soft—Readily gouged with fingernail, breaks with light manual pressure.
- 8 Soil Like—Cohesive
- 9 Soil Like—Non-cohesive

WEATHERING

- F** Fresh—Rock and fractures not oxidized or discolored, no separation of grains, change of texture or solutioning.
- S** Slightly Weathered—Oxidized or discolored fractures and nearby rock, some dull feldspars, no separation of grains, minor leaching.
- M** Moderately Weathered—Fractures and most of rock oxidized or discolored, partial separation of grains, crystals rusty or cloudy, moderate leaching of soluble minerals.
- I** Intensely Weathered—Fractures and rock totally oxidized or discolored, extensive clay alteration, leaching complete, grain separation extensive, rock is friable.
- D** Decomposed—Grain separation and clay alteration complete.

PLANARITY

ROUGHNESS

INFILLING THICKNESS AND MINERALIZATION

Y

P Planar	V Very rough, stepped, near-normal steps and ridges occur.
C Curved	R Rough, large angular asperities can be seen.
S Stepped	M Moderately rough, asperities clearly visible, surface has an abrasive feel; to slightly rough, small asperities are visible and can be felt.
I Irregular	S Smooth, no asperities, smooth to the touch.
	P Polished, slickensided, extremely smooth and shiny.

C Clean, no filling.	C Clean	CA Calcite
S Very thin, surface sheen	WC White, crystalline	SI Silica
T Thin (up to 0.1 inches)	WN White, non-crystalline	MN Manganese
M Moderately thick (0.1 - 0.4 inches)	TD Brown dendritic	CL Clay
V Very thick (0.4 - 1.0 inches)	TC Tan crystalline	BC Black crystalline
E Extremely thick, greater than 1.0 inches)	TN Tan, non-crystalline	BD Black dendritic

EXPLANATION (concluded) GEOLOGY AND ROCK STRUCTURE

CORE RQD

Core RQD is calculated using piece lengths that are defined by all fractures (type N, I, and C) that exist in the core when it is removed from the core barrel. Only handling-induced breaks are discounted in piece length determination. RQD is calculated as:

$$RQD = \frac{\sum \text{Piece lengths} \geq 0.33 \text{ ft}}{\text{Interval length}} \times 100.$$

RQD is calculated for both the core run interval (run RQD) and even 10-ft intervals. If a piece length ≥ 0.33 ft crosses over a 10-ft interval boundary, the portion of the piece length that occurs in the 10-ft interval is included in the summation.

ESTIMATED PERCENTAGE LITHOPHYSAE & OTHER CAVITIES

The percentage of lithophysal voids and other cavities is estimated for each core run interval where sufficient whole core is available. Excessive lost core and rubble zones may prevent the estimate on specific core runs. The estimate is based on comparison of the core with charts designed for estimating the proportions of various rock or mineral components. Estimates are then spot checked using a quantitative graphical summation technique to calculate the percent area occupied by lithophysal cavities in core photographs or video tape.

The estimated percent cavities volume for core runs is used to calculate a run length, weighted average for even 10-ft intervals. (Runs for which percent cavities cannot be determined are assumed to have the average percentage for the 10-ft interval; intervals for which the percent cavities was not estimated are labeled "Not Measured;" zones containing vapor-phase alteration and very small or no lithophysal cavities are labeled as <1%).

USW SD-12 (1 of 3) Stratigraphic and Thermal-Mechanical Units Summary 0 - 881 ft

Stratigraphy

Section 1

USGS 2

Thermal-mechanical

Units 3

USW SD-12 Stratigraphy (2 of 3) **Stratigraphic and Thermal-Mechanical Units Summary** **Detail 239.1 - 369.0 ft**

*Break between welded and moderately welded subzones at 324.6'.

USW SD-12 (3 of 3)
Stratigraphic and Thermal-Mechanical Units Summary
881 - 1435.3 ft

Date: 3/1/95

1. Lithologic log of Borehole USW SD-12. Dale Engstrom, unpublished data.
2. U.S. Geological Survey - Graphical Lithologic Log of Borehole USW SD-12, J.K. Geslin and J.R. Wunderlich, DTN: GS940908314211.045
3. Thermal-mechanical units as defined by Buesch, et al., USGS Open File Report 94-469, 1996. "Revised stratigraphic nomenclature and macroscopic identification of lithostratigraphic units of the Paintbrush Group exposed at Yucca Mountain, Nevada."

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DESIGNATION (RQD) (%)				FRACTURES (PER 10 FT)				HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSE AND OTHER CAVITIES				ARGILLIC LITHOPHYSE VAPOR PHASE DEHYDRATION WEATHERING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
	INTERVAL	% RECOVERY (JULY 1980-1981)	LOST CORE & RUBBLE	FRACTURE TYPE	PLANARITY	ROUGHNESS	INFILL	THICKNESS AND MINERALS	DIP	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	10			20	30																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
680.0	RUN 117	96 (113)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES										ROCK QUALITY DESIGNATION-RQD (%)					FRACTURES (CLR IN FT)			WALLNESS	WEATHERING	ESTIMATED & UNRECOVERED LITHOPHYSEAL AND OTHER CAVITIES			ARGILLIC LITHOPHYSEAL VAPOR PHASE DEHYDRATION WEILING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
	INTERVAL	RECOVERY (RUN ROD-9)	LOST CORE & RUBBLE	PLANARITY/ROUGHNESS	INTELL THICKNESS AND MINERALS	DIR	UNCLASSED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDETERMINATE (+ INDUCTION)	10	20	30	10	20	30																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
705.0	87 (0)	100 (38)	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								

GEOLOGY AND ROCK STRUCTURE LOG

Sandia National Laboratories
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DESIGNATION (RQD) (%)				FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYLITE AND OTHER CAVITIES	ABOLUC LITHOPHYLITE VAPOR PHASE DEHYDRATION	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	RECOVERY (PER 10 FT)	LOST CORE & RUBBLE	TYPE	PLANARITY	ROUGHNESS	INFILL	THICKNESS AND MINERALS	DP	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT						
	730.0	89	10						90		.40											TOPOPAH SPRING Crystal-Poor Middle. Nonlithophyal (cont.). Pale orange-gray (10R6/4) densely welded, devitrified, 12-15% speckled/streaked by 3-8mm wisps of light-gray vapor-phase alteration after xmi-size nearly invisible pumice flattened to 15-20:1, former large pumice completely flat (30:1) becoming more rare downward, replaced by light gray vapor-phase mineralization, 2-3mm blue vapor-phase alteration halo, 3-5% white sandlike plagioclase phenocrysts, biotite not seen, severely broken, MnOx speckled on fractures.
	735.0	98	10						95		.40											734.5, Increased size and number of speckles and halos, also increase in lithics, mostly (80%) small subrounded cognate flattened and soft. 17% of lithics hard exotic crystal-rich quartz latic and 3-4% very small rhyolite hard lithics, 738.0-739.0 slight increase in blue alteration.
	740.0								90		.40											739.9-742.5 rubble
	745.0	97	10						85		.18											747.4, 20mm rhyolite lithic
	750.0								20		.65											747.9-750.0 rubble

[illegible]

DEPTH (FT)	CORR	FRACTURES										ROCK QUALITY DESIGNATION (RQD) (%)					FRACTURES (PER 10 FT)					HAZINESS	WEATHERING	ESTIMATED % LITHOPHYSEAL VAPOR PHASE DEHYDRATION	ARGILLIC LITHOPHYSEAL VAPOR PHASE DEHYDRATION	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
		INTERVAL	% RECOVERY (RUN ROD-14)	LOST CORE	FRAC. TYPE	PLANARITY	ROUGHNESS	THICKNESS	MINERALS	DR	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND UNDETERMINATE (+ UNEXPOSED)	10	20	30																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
781.0	RUN 140				I	I	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	PH	

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
CORE HOLE ROCK STRUCTURAL DATA SUMMARY
Hole USW SD-12, 650-800 ft, Middle Nonlithophysal Zone

Sandia National Laboratories
Print Date: 6/30/95
WBS 1.2.3.2.6.2
QA-L
Revision 1

REVISION HISTORY

Revision 1 Enhanced RQDs at 670-680 and 770-780 ft were revised. Revision 0 superseded in its entirety.

CODING EXPLANATION

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yucca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlith.
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UO—Undifferentiated Overburden
TCw—Tiva Canyon Welded Unit
FTn—Upper Paintbrush Nonwelded Unit
TSw1—Topopah Spring Welded Unit—Lithophysae Rich
TSw2—Topopah Spring Welded Unit—Lithophysae Poor
TSw3—Topopah Spring Welded Unit—Vitrophyre
CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

COLUMN INFORMATION (Page 3)

RQD (%) $RQD (\%) = \frac{\sum \text{Piece lengths} \geq 0.33 \text{ ft}}{\text{Interval length}} \times 100.$

CORE RQD Core RQD based on piece lengths defined by all types of fractures (C, I, N and V).

ENHANCED RQD Effect of fractures identified as coring induced (Type C) are filtered from the piece lengths.

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
CORE HOLE ROCK STRUCTURAL DATA SUMMARY
Hole USW SD-12, 650-800 ft, Middle Nonlithophysal Zone

Sandia National Laboratories
 Print Date 6/30/95
 WBS 1.2.3.2 6.2
 QA L
 Revision 1

LITHOPHYSAL (and other cavities)	Percent void due to lithophysae and other cavities, estimated visually by counting the number of cavities, estimating the average diameter, calculating the void volume assuming spherical cavities, and normalizing to the core volume. NM—Not Measured		
WEATHERING	Subjective evaluation of rock degradation by mechanical/chemical agents: F: Fresh M: Moderately weathered D: Decomposed S: Slightly weathered I: Intensely weathered		
HARDNESS	Subjective evaluation of resistance to breakage: 1: Extremely hard 4: Moderately hard 7: Very soft 2: Very hard 5: Moderately soft 8: Soil-like, cohesive 3: Hard 6: Soft 9: Soil-like, non-cohesive		

COLUMN INFORMATION (Page 4)

FEATURE TYPE	Following codes indicate origin of feature: N: Natural—indicated by mineral coating or evidence of weathering, slickensides, lack of fit between sides. I: Indeterminate—origin questionable, rotated so that coatings possibly removed. C: Coring induced—fresh, clean, tightly fitting breaks. V: Vug or large void.		
INCLINATION (degrees)	Angle between plane normal to core axis and plane of fracture (Type N and I only).		
MINERAL INFILLING	Describes the infilling on fracture surfaces (Type N and I only): C: Clean TD: Brown dendritic CL: Clay WC: White crystalline TC: Tan crystalline TN: Tan noncrystalline WN: White noncrystalline CA: Calcite FE: iron oxide BC: Black crystalline SI: Silica BN: Brown noncrystalline BD: Black dendritic MN: Manganese		
INFILL THICKNESS	Describes the thickness of mineral infillings on the fracture surface (Type N and I only): S: Very thin, surface sheen V: Very thick (0.4 - 1.0 inches) T: Thin (up to 0.1 inches) E: Extremely thick, greater than 1.0 inches M: Moderately thick (0.1-0.4 inches)		
PLANARITY	Describes the overall shape of the feature (Type N and I only): P: Planar S: Stepped C: Curved I: Irregular		
ROUGHNESS	Describes the local relief of the surface (Type N and I only): V: Very rough—stepped, near-normal steps and ridges occur. R: Rough—large angular asperities can be seen. M: Moderately rough—asperities clearly visible, surface has abrasive feel. S: Smooth—no asperities, smooth to the touch. P: Polished—slickensided, extremely smooth and shiny.		

This page intentionally left blank.

Interval—650–800 ft. Middle Neolithophysal Zone

*** Footage in interval may not equal 10 ft because of lost core, subleak, or omission during logging.

Interval—650–800 ft, Middle Nemlichophyal Zone

C.

NO. OF FRACTURES W/MINERAL INFILLING TYPE														NO. OF FRACTURES W/INFILL THICKNESS					NO. OF FRACTURES W/PLANARITY CODE					NO. OF FRACTURES W/ROUGHNESS CODE				
C	WC	WN	BC	BD	TD	TC	CA	SI	MN	CL	TN	FE	BN	S	T	M	V	E	P	C	S	I	V	R	M	S	P	
4																			4								3	1
2		1		4										5					5		1					1	6	
7		1		10										11					8	5	1	1				5	10	
2		1		2										3					2	2				1	2	2		
4		1		26										26	1				26	3		1		1	8	21		
3				4										4					4	1		2		2	2	3		
3				6	1									7					6	3				1	1	7		
2				5										5					4	1		1			1	5		
12	2			2										3	1				12	2		2		2	9	2	1	
39																			37	2						35	4	
8																			4	1						2	3	
10	1	1		14										15	1				17	2		5	1	1	7	14		
18	1	5		3										6	3				16	4		1		3	12	4		
8		5													5				11	1		1		2	3	4		
5	1			2										2	1				3	2		1	2		1	3		
122	5	15	0	78	1	0	0	0	0	0	0	0	0	87	12	0	0	0	160	29	2	16	3	13	82	91	2	
55.2	2.28	6.79	0	35.3	0.45	0	0	0	0	0	0	0	0	52.9	12.1	0	0	0	77.3	14	0.97	7.73	1.52	6.57	44.9	46	1.07	

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
ESTIMATED ROCK MASS QUALITY INDICES
BASED ON CORE LOG DATA
Hole USW SD-12, 650-800 ft, Middle Nonlithophysal Zone

Sandia National Laboratories
Print Date: 7/3/95
WBS 1.23.2.6.2.1
QA/L
Revision 1

REVISION HISTORY

Revision 1 Jn and SRF parameters revised due to inclusion of additional data from mapping of the North Ramp tunnel.

EXPLANATION OF CALCULATION

Rock mass quality indices, Q (Barton et al., 1974) and RMR (Bieniawski, 1979), have been estimated for 10-ft intervals using Rock Structural Data Summaries developed from structural logging of the core, observations of rock conditions in the North Ramp Starter Tunnel and North Ramp tunnel, and laboratory testing data.

- Q is developed to evaluate the distribution of rock mass quality as a basis for developing the range of credible rock mass quality to establish the ground support requirements within rock units and to derive rock mass mechanical properties according to the methodology proposed by Hardy and Bauer (1991). Procedures used in the calculation were:

$$Q = \frac{RQD^{**}}{J_n^{*}} \cdot \frac{J_r}{J_n} \cdot \frac{J_w}{SRF^{*}}$$

Note: Any spatial correlation may be masked by Monte Carlo simulation of Jn and SRF.

where RQD^{**} = Core RQD where all fractures types [natural (N), indeterminate (I), coring induced (C) and vugs (V)] have been considered in determination of RQD. If the RQD is less than 10%, the value used is set to 10 as per Barton et al. (1974). By definition, soil-like materials are considered to have zero RQD.

J_n^{*} = Joint Set Numbers: Cannot be determined from the core log data and are generated by Monte-Carlo simulation assuming a uniform distribution of values between 1 and 12 derived from mapping of the North Ramp tunnel.

J_r = Joint Roughness Number: A weighted average value derived based on the N and I type fractures in the 10-ft interval.

J_a = Joint Alteration Number: A weighted average value derived from the description of N and I type fractures in the interval.

J_w = Joint Water Factor: Set equal to 1.0 assuming dry conditions.

SRF^{*} = Stress Reduction Factor: For nonwelded units, SRF is determined from

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Sandia National Laboratories

Print Date: 7/3/95

WBS 1.23.2.6.2.1

QA/L

Revision 1

**ESTIMATED ROCK MASS QUALITY INDICES
BASED ON CORE LOG DATA****Hole USW SD-12, 650-800 ft, Middle Nonlithophysal Zone**

the ratio of UCS/σ_1 (UCS = unconfined compressive strength, σ_1 = overburden stress). If unconfined compressive strength data is not available for the 10-ft interval, a compressive strength is generated by Monte Carlo simulation using laboratory test data for the thermomechanical units. For welded tuff units, SRF cannot be determined from core log data and is generated by Monte Carlo simulation assuming a distribution derived from mapping of the North Ramp tunnel.

- The use of the Core RQD is conservative since it includes the effect of coring induced breaks. Filtering the effects of coring induced breaks from the RQD calculation ("Enhanced RQD") produced an increase in the mean RQD. The mean values for thermomechanical units in USW SD-12 are:

	<u>Core RQD</u>	<u>Enhanced RQD</u>
TCw	35.6%	55.7%
PTn	80.1%	88.8%
TSw1	35.5%	55.3%
TSw2	13.7%	23.5%

- RMR is estimated based on the Rock Structural Summary log data, and rock strength data. Procedures used in the calculation were:

$$RMR = C + RQD-I + JS + JC + JW$$

where C = Rock Strength Index: Derived from compressive strength estimated by unconfined compressive strength laboratory test data for the 10-ft interval. If data is not available for the 10-ft interval, a compressive strength is generated by Monte-Carlo simulation using laboratory test data for the thermomechanical unit.

RQD-I = RQD Index: Derived using the Core RQD value for the 10-ft interval.

JS = Joint Spacing Index: Derived from the rock structural data for the 10-ft interval, excludes coring induced features.

JC = Discontinuity Condition Index: Derived from the description of fractures in the 10-ft interval.

JW = Groundwater Index: Assumed dry conditions

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
ESTIMATED ROCK MASS QUALITY INDICES
BASED ON CORE LOG DATA

Sandia National Laboratories
Print Date: 7/3/95
WBS 1.2.3.2.6.2.1
QA.2
Revision 1

Hole USW SD-12, 650-800 ft, Middle Nonlithophysal Zone

- Q and RMR data are presented in log format to associate parameters with depth intervals in the core log; however, any spatial correlation may be masked by Monte-Carlo simulation.

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yucca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UO—Undifferentiated Overburden
TCw—Tiva Canyon Welded Unit
PTn—Upper Paintbrush Nonwelded Unit
TSw1—Topopah Spring Welded Unit—Lithophysae Rich
TSw2—Topopah Spring Welded Unit—Lithophysae Poor
TSw3—Topopah Spring Welded Unit—Vitrophyre
CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Estimated Rock Mass Quality Indices Based on Core Log Data

Hole USW SD-12

Interval — 650–800 ft, Middle Nonlithophysal Zone

END DEPTH	STRATIGRAPHY ZONE	THERMO- MECHANICAL UNIT	Q CLASSIFICATION SYSTEM ¹ Barton et al. (1974)							RMR CLASSIFICATION SYSTEM ² Bieniawski (1979)					
			RQD** (%)	Jn*	Jr	Ja	Jw	SRF*	Q*	C	RQD-I	JS	JC	JW	RMR
660	T.S. C.P. U. Lith.	TSw1	40	6.00	0.88	1.00	1.00	5.00	1.17	4	8	8	17.6	15	52.6
670	T.S. C.P. M. Nonlith.	TSw2	41	9.00	1.29	1.29	1.00	5.00	0.91	15	8	8	18.4	15	64.4
680	T.S. C.P. M. Nonlith.	TSw2	11	9.00	1.47	1.11	1.00	5.00	0.32	12	3	8	20.7	15	58.7
690	T.S. C.P. M. Nonlith.	TSw2	28	9.00	1.80	1.40	1.00	5.00	0.80	12	8	8	20.7	15	63.7
700	T.S. C.P. M. Nonlith.	TSw2	25	9.00	1.33	1.06	1.00	5.00	0.70	7	8	8	19.0	15	57.0
710	T.S. C.P. M. Nonlith.	TSw2	20	3.00	1.86	1.00	1.00	1.00	12.38	12	3	8	22.1	15	60.1
720	T.S. C.P. M. Nonlith.	TSw2	0	9.00	2.10	1.22	1.00	7.50	0.26	12	3	5	23.1	15	58.1
730	T.S. C.P. M. Nonlith.	TSw2	4	9.00	1.33	1.00	1.00	5.00	0.30	7	3	5	20.5	15	50.5
740	T.S. C.P. M. Nonlith.	TSw2	41	9.00	1.89	1.00	1.00	7.50	1.15	12	8	8	20.8	15	63.8
750	T.S. C.P. M. Nonlith.	TSw2	24	6.00	1.90	1.00	1.00	5.00	1.52	12	3	8	19.6	15	57.6
760	T.S. C.P. M. Nonlith.	TSw2	42	9.00	1.40	1.00	1.00	5.00	1.31	15	8	8	19.5	15	65.5
770	T.S. C.P. M. Nonlith.	TSw2	0	9.00	1.61	1.08	1.00	5.00	0.33	15	3	8	20.5	15	61.5
780	T.S. C.P. M. Nonlith.	TSw2	33	6.00	1.84	1.45	1.00	5.00	1.39	12	8	8	18.6	15	61.6
790	T.S. C.P. M. Nonlith.	TSw2	46	9.00	1.67	1.77	1.00	5.00	0.96	7	8	8	16.8	15	54.8
800	T.S. C.P. L. Lith.	TSw2	8	6.00	1.67	1.00	1.00	5.00	0.56	12	3	8	21.8	15	59.8

Jn*, SRF* = interval values generated by Monte Carlo simulation; to calculate Q*.

RQD**: If RQD is less than 10, the value 10 is used in the calculation of Q* as per Barton et al. (1974).

¹ Barton, N., R. Lien, and J. Lund, "Engineering Classification of Rock Masses for the Design of Tunnel Support,"

Rock Mechanics, 6:189-236 (Springer Verlag, 1974)

² Bieniawski, Z.T., "The Geomechanics Classification in Rock Engineering Applications," Proceedings, 4th International Congress on Rock Mechanics, Montreux, Switzerland, 2:41-48 (A. A. Balkema, 1979)

Q

Jn — Joint Set Number

Jr — Joint Roughness Number

Ja — Joint Alteration Number

Jw — Joint Water Reduction Factor

SRF — Stress Reduction Factor

$$Q = (RQD/Jn)(Jr/Ja)(Jw/SRF)$$

RMR

C — Strength Index

RQD-I: RQD Index

JS — Joint Spacing Index

J_c — Discontinuity Condition Index

JW — Contradiction Index

$$RMR = C + RQD-I + JS + J_c + JW$$

USW UZ-14 CORE LOGS AND DATA

Geology and Rock Structure Log

Core Hole Rock Structural Data Summary

Estimated Rock Mass Quality Indices Based on Core Log Data

**YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
GEOLOGY AND ROCK STRUCTURE LOG**

Hole USW UZ-14, 700-850 ft

Sandia National Laboratories

Print Date: 8/2/95

WBS 1.2.3.2.6.2.1

QA:L

Revision 0

BOREHOLE ID: USW UZ-14
STUDY PLAN NO: 8.3.1.2.2.1
CORE SIZE: HQ
DRILL DATES: 6/9/93-6/24/93
GROUND ELEV: 4425.40
COORDINATES: N771309.80
E560141.57

TOTAL DEPTH: 700-850 ft (partial)
ANGLE FROM VERT: 0°
AZIMUTH: NA

Field Rock Structure

Logged by:

M. Wagner
R. Myers
M. Pitterle
R. Wilcoxon
A. Mendenhall
C. Hermes
D. Switzer
M. Edwards
R. Morris

Drilling Support Division, Drilling
Support and Sample Management
Department, T&MSS

Relogged by:

Dick Lippoth
Eric R. Martin

Agapito Associates, Inc.
Agapito Associates, Inc.

Lithology and Stratigraphy

Logged by:

D. Engstrom

Sandia National Laboratories

Checked by:

Eric R. Martin

Agapito Associates, Inc.

Log prepared by Agapito Associates, Inc. for Sandia National Laboratories

EXPLANATION GEOLOGY AND ROCK STRUCTURE

FRACTURE TYPE OR FEATURE

- N Natural fractures are indicated by mineral coatings, evidence of weathering, slickensides, lack of rematch/fit between sides or by surfaces that form an ellipse in the core.
- C Coring-induced fractures are generally normal to the axis of the core or indicate some torquing of the core. They are typically clean, fresh and fit tightly back together.
- I Indeterminate fractures are those not clearly described as "N" or "C." This includes fracture surfaces that have been shaped by drilling rotation.
- H Handling-induced fractures are formed in the core by removal from the core barrel or placement in the core box. These fractures are witnessed and, according to BTP-SMF-008, are marked by the SMF personnel by lines parallel to the fracture on both sides of the core. "H" fractures are typically not recorded in the log unless there is a specific reason.
- V Vug or large void.
- P Foliation plane due to gravity flattening upon deposition, not a fracture.

LOST CORE AND RUBBLE

LOST CORE

$\times 20 \times$ RUBBLE ZONE

(with average maximum diameter of rubble pieces to nearest 0.01 ft;

NM = not measured)

HARDNESS (Subjective estimate, YMP procedures do not allow core to be broken or scratched etc.)

- 1 Extremely Hard—Cannot be scratched, chipped only with repeated heavy hammer blows.
- 2 Very Hard—Cannot be scratched, broken only with repeated heavy hammer blows.
- 3 Hard—Scratched with heavy pressure, breaks with heavy hammer blow.
- 4 Moderately Hard—Scratched with light-moderate pressure, breaks with moderate hammer blow.
- 5 Moderately Soft—Grooved (16th in.) with moderate heavy pressure, breaks with light hammer blow.
- 6 Soft—Grooved easily with light pressure, scratched with fingernail, breaks with light-moderate manual pressure.
- 7 Very Soft—Readily gouged with fingernail, breaks with light manual pressure.
- 8 Soil Like—Cohesive
- 9 Soil Like—Non-cohesive

WEATHERING

- F Fresh—Rock and fractures not oxidized or discolored, no separation of grains, change of texture or solutioning.
- S Slightly Weathered—Oxidized or discolored fractures and nearby rock, some dull feldspars, no separation of grains, minor leaching.
- M Moderately Weathered—Fractures and most of rock oxidized or discolored, partial separation of grains, crystals rusty or cloudy, moderate leaching of soluble minerals.
- I Intensely Weathered—Fractures and rock totally oxidized or discolored, extensive clay alteration, leaching complete, grain separation extensive, rock is friable.
- D Decomposed—Grain separation and clay alteration complete.

PLANARITY

- P Planar V Very rough, stepped, near-normal steps and ridges occur.
- C Curved R Rough, large angular asperities can be seen.
- S Stepped M Moderately rough, asperities clearly visible, surface has an abrasive feel; to slightly rough, small asperities are visible and can be felt.
- I Irregular S Smooth, no asperities, smooth to the touch.
- P Polished, slickensided, extremely smooth and shiny.

ROUGHNESS

INFILLING THICKNESS AND MINERALIZATION

C Clean, no filling.	C Clean	CA Calcite
S Very thin, surface sheen	WC White, crystalline	SI Silica
T Thin (up to 0.1 inches)	WN White, non-crystalline	MN Manganese
M Moderately thick (0.1 - 0.4 inches)	TD Brown dendritic	CL Clay
V Very thick (0.4 - 1.0 inches)	TC Tan crystalline	BC Black crystalline
E Extremely thick, greater than 1.0 inches)	TN Tan, non-crystalline	BD Black dendritic

EXPLANATION (concluded) GEOLOGY AND ROCK STRUCTURE

CORE RQD

Core RQD is calculated using piece lengths that are defined by all fractures (type N, I, and C) that exist in the core when it is removed from the core barrel. Only handling-induced breaks are discounted in piece length determination. RQD is calculated as:

$$RQD = \frac{\sum \text{Piece lengths} \geq 0.33 \text{ ft}}{\text{Interval length}} \times 100.$$

RQD is calculated for both the core run interval (run RQD) and even 10-ft intervals. If a piece length ≥ 0.33 ft crosses over a 10-ft interval boundary, the portion of the piece length that occurs in the 10-ft interval is included in the summation.

ESTIMATED PERCENTAGE LITHOPHYSAL & OTHER CAVITIES

The percentage of lithophysal voids and other cavities is estimated for each core run interval where sufficient whole core is available. Excessive lost core and rubble zones may prevent the estimate on specific core runs. The estimate is based on comparison of the core with charts designed for estimating the proportions of various rock or mineral components. Estimates are then spot checked using a quantitative graphical summation technique to calculate the percent area occupied by lithophysal cavities in core photographs or video tape.

The estimated percent cavities volume for core runs is used to calculate a run length, weighted average for even 10-ft intervals. (Runs for which percent cavities cannot be determined are assumed to have the average percentage for the 10-ft interval; intervals for which the percent cavities were not estimated are labeled "Not Measured;" zones containing vapor-phase alteration and very small or no lithophysal cavities are labeled as <1%).

UZ-14 (1 of 2)
Stratigraphic and Thermal-Mechanical Units Summary
0 - 860 ft

*Break between welded and moderately welded subzones at 282.5'.

UZ-14 (2 of 2)

Stratigraphic and Thermal-Mechanical Units Summary

860 - 1420.2 ft

Date: 8/2/95
+11

- ¹ Lithologic log of Borehole UZ-14. Dale Engstrom, unpublished data. Terminology based on nomenclature of Scott & Bonk, USGS OFR 84-494.
- ² Summary of lithologic logging of new and existing boreholes at Yucca Mountain, Nevada, July 1994 to November 1994. T.C. Moyer, J.K. Geslin, and D.C. Buesch; USGS OFR 95-102, in press.
- ³ Thermal-mechanical units as defined by Buesch, et al., USGS Open File Report 94-469, 1996. "Revised stratigraphic nomenclature and macroscopic identification of lithostratigraphic units of the Paintbrush Group exposed at Yucca Mountain, Nevada."

GEOLOGY AND ROCK STRUCTURE LOG

USW 17Z-14
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES										ROCK QUALITY DESIGNATION (RMD) (%)					FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES	ARGILLIC LITHOPHYSAL VAPOR PHASE DEVITRIFICATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY					
	INTERVAL	% RECOVERY	LAST CORE	RUMBLE	FRAC. TYPE	PLANARITY	ROUGHNESS	ENTRILL	THICKNESS AND	MINERALS	QIP	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDUCED (PER 10 FT)												
205.0	↑	85	15		N	H	P	C	C		85	85	1.00							2	5										433.7-716.2 ft. TOPOPAH SPRING, UPPER LITHOPHYSAL (cont'd.) Light red gray, densely welded, devitrified, lithophysal intensity decreases downward until cavities are flat, thin, waxy, coated by crystalline vapor-phase mineralization; circular light pink-tan alteration halo around lithophysae, 50-60% of groundmass is pervasively blue altered; islands of unaltered groundmass; 1-3% quartz; late soft lithic clasts to 50mm, 2-3% feldspar phenocrysts, trace biotite.
719.8	RUN 96				N	H	P	C	C		85	85	1.00							2	5										704.7-705.1 ft. Zone of reduced lithophysal intensity.
		1.00	1.00		N	H	P	C	C		90	90	1.00							2	5										708.9 ft. Decrease in percentage of 1-3cm lithophysae. The amount of lithophysae (1-3cm diameter) decreases below 694.4 ft (possibly 693.9) and definitely below 702.5 ft.
715.0					N	H	P	C	C		90	90	1.00							2	5										716.2-828.0 ft. TOPOPAH SPRING, MIDDLE NONLITHOPHYSAL ZONE. Sudden color change to weakly mottled texture. Densely welded, devitrified. Blue alteration disappears. Orange-gray groundmass has weak vapor-phase speckles (7mm) around hairline replacement of very flat pumice (extreme welding). 1-2% feldspar phenocrysts, trace biotite.
720.0	RUN 97				N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C	C		90	90	1.00							2	5										
					N	H	P	C																							

U100 v 4 90

GEOLOGY AND ROCK STRUCTURE LOG

USW 02-14
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DESIGNATION (RQD) (%)					FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES				ANGLE LITHOPHYSAL VAPOR PHASE DEVIATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	% RECOVERY (OPEN RODS)	LOST CORE & RUBBLE	FRACTURE TYPE	PLANARITY	ROUGHNESS	INFILL	THICKNESS AND	ORIENTATIONS	DISPERSED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDETERMINATE (+ INJECTED)	10	20	30	40	50	60	70	80	90
755.0	RUN 107	75 (0)	10															2	8							716.2-828.0 ft. TOPOPAH SPRING, MIDDLE NONLITHOPHYSAL ZONE cont'd (m). Pale red-gray, densely welded, devitrified, 10% nearly invisible pumice, orange-gray groundmass has weak vapor-phase alteration speckles around hairline replacement of very fine pumice, 2-4% light gray porphyritic volcanic clasts, 2% feldspar phenocrysts, trace biotite. 744.5-757.3 ft. Shattered.
760.0	RUN 108	52 (133)	10															2	8							
765.0	RUN 110	83 (0)	10															2	8							760.5-762.1 ft. Broken.
770.0	RUN 111	33 (10)	10															2	8							768.2 ft. LITHOPHYSAL-BEARING SUBZONE. Blue moderate to intense vapor-phase alteration composes as much as 90% of rock volume. Vapor-phase alteration rims very fine pumice/hairline replacement mineralization. Patchy blue alteration texture mixed with vapor-phase alteration, (thin hairline crystalline mineralization replaces pumice. Some blue-gray alteration halos, all 95% blue pervasive alteration with rare islands of devitrified groundmass.
775.0																										

Structure file: US14REV6 STM Lithology file

Date: 08/02/95

WPI-97 v. 6.00

GEOLOGY AND ROCK STRUCTURE LOG

USW UZ-14
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES							ROCK QUALITY DESIGNATION (RQD) (%)				FRACTURES (PER 10 FT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSAL AND OTHER CAVITIES				ARGILLIC LITHOPHYSAL VAPOR PHASE DEHYDRATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	% RECOVERY (RUN LOG #)	LOST CORE & RUBBLE	FRAC TYPE	PLANARITY	BOUNDRIES	WALL THICKNESS AND MINERALS	DOF	INDUCED	PIECE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND INDETERMINATE (+ REMANENT)			1	2	3	4			
780.0	RUN 112	88 (54)	10							1.05				26%		45 (38)	4	5				2%			716.2-828.0 ft. TOPOPAH SPRING. MIDDLE NONLITHOPHYSAL ZONE cont'd (m). Light red-gray, densely welded, dovitrified, patchy eutaxitic groundmass texture; most pumice flattened to hairline replaced by vapor-phase mineralization; circular 10-20mm light pink gray alteration halos around pumice. 1-2mm blue alteration border, 2-3% feldspar phenocrysts, trace biotite; intervals of large close-spaced lithophysae from 771.1-779.5, 781.0-783.0, and 786.5-796 ft. and wide-spaced, large lithophysae from 835.5-878 ft. 775.0-778.0 ft. Broken. 778.0-786.5 ft. 2-5% lithophysae in light pink-gray alteration spots. 784.5-787.5 ft. Broken
785.0	RUN 113	85 (76)	5							1.35							4	6				2%			786.5-796.0 ft. Large lithophysae.
790.0	RUN 114	96 (73)	11							1.35							4	6							
795.0	RUN 115	94 (33)	12							1.18							4	5				2%			799.0-807.9 ft. Increase in light gray streaks to as much as 4%.

Structure file: UGAREV6 STR Lithology file:

Date: 08/02/95

WPI 14 v 6.60

GEOLOGY AND ROCK STRUCTURE LOG

USW UZ-14
by Agapito Associates, Inc.

DEPTH (FT)	CORE		FRACTURES								ROCK QUALITY DESIGNATION (RQD %)					FRACTURES (PER FOOT)			HARDNESS	WEATHERING	ESTIMATED % LITHOPHYSE AND OTHER CAVITIES					LITHOPHYSE VAPOR PHASE DEVITRIFICATION WELDING	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY
	INTERVAL	% RECOVERY (RUN ROD-SS)	USST CORE & NOBLE	FRACTURE TYPE	PLANARITY	ROUGHNESS	INFILL	THICKNESS AND MINERALS	QSP	INDUCED	PRICE LENGTH	VERY POOR 25	POOR 30	FAIR 75	GOOD 80	EXCELLENT 90	NATURAL AND INDETERMINATE (+ INHIBITED)	10			20	30	40	50				
805.0	RUN 116	100 (166)		N	PH	S++	SCA	90																				716.2-828.0 ft. TOPOPAH SPRING, MIDDLE NONLITHOPHYSEAL ZONE cont'd (fm). Light red-gray, densely welded, devitrified, patchy eutaxitic texture, crystal- lined pumice sites (veinlets) face downward. Weak alteration halo, 1-2mm wide across very flat pumice sites, primary vapor-phase crystalline mineralization gone from pumice; occasional rare veinlet of white vapor-phase mineralization. 803.1 ft. Trace porphyritic volcanic lithic clasts. 804.5-805.3 ft. Vapor-phase alteration decreasing until groundmass medium red. 808.0 ft. Light red gray.
810.0		100 (162)		N	PH	S++	SCA	90																				
815.0		100 (162)		N	PH	S++	SCA	90																				
820.0	RUN 117	100 (162)		N	PH	S++	SCA	90																				819-819.7, 820.1-820.5, 821.2-821.3, 823.8-824.0 ft. Zones of blue vapor-phase alteration.
825.0	RUN 118	99 (164)		N	PH	S++	SCA	90																				824.6-831.3 ft. Lithophyse intensity increasing.

Structure (110 02)REV.5TH lithology (110)

Date: 06/02/95

USW UZ-14

GEOLOGY AND ROCK STRUCTURE LOG

USW U2-14
by Agapito Associates, Inc.

DEPTH (FT)	CORRECTION	FRACTURES										ROCK QUALITY DESIGNATION (RQD) (%)					FRACTURES (PER FOOT)			HARDNESS	WEATHERING	ESTIMATED LITHOPHYSAL VAPOR PHASE DEVIATRICATION	GEOLOGY	LITHOLOGIC DESCRIPTION AND STRATIGRAPHY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
		INTERVAL	% RECOVERY (RUN 100-1)	LOST CORE & RUBBLE	PLANARITY/ BOLDNESS	INELL THICKNESS AND MINERALS	DP	INDUCED	PRICE LENGTH	VERY POOR	POOR	FAIR	GOOD	EXCELLENT	NATURAL AND WEATHERED (1-10)	10	20	30																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
830.0		RUN 118																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										

Structure file: U214R146 SPN Lithology file:

Date: 02/02/95

USW U2-14 v. 4.00

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
CORE HOLE ROCK STRUCTURAL DATA SUMMARY
Hole UZ-14, Middle Nonlithophysal Zone

Sandia National Laboratories
Print Date: 5/5/95
WBS 1.2.3.2.6.2
QA/L
Revision 0

CODING EXPLANATION

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yucca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlith.
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UO—Undifferentiated Overburden
TCw—Tiva Canyon Welded Unit
PTn—Upper Paintbrush Nonwelded Unit
TSw1—Topopah Spring Welded Unit—Lithophysae Rich
TSw2—Topopah Spring Welded Unit—Lithophysae Poor
TSw3—Topopah Spring Welded Unit—Vitrophyre
CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

COLUMN INFORMATION (Page 3)

RQD (%) $RQD (\%) = \frac{\sum \text{Piece lengths } \geq 0.33 \text{ ft}}{\text{Interval length}} \times 100.$

CORE RQD Core RQD based on piece lengths defined by all types of fractures (C, L, N and V).

ENHANCED RQD Effect of fractures identified as coring induced (Type C) are filtered from the piece lengths.

LITHOPHYSAL (and other cavities) Percent void due to lithophysae and other cavities, estimated visually by counting the number of cavities, estimating the average diameter, calculating the void volume assuming spherical cavities, and normalizing to the core volume.
NM—Not Measured

Agapito Associates, Inc.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
CORE HOLE ROCK STRUCTURAL DATA SUMMARY
Hole UZ-14, Middle Nonlithophysal Zone

Sandia National Laboratories
Print Date 5/5/95
WBS 1.2.3.2.6.2
QA.L
Revision 0

WEATHERING	Subjective evaluation of rock degradation by mechanical/chemical agents:		
	F: Fresh	M: Moderately weathered	D: Decomposed
HARDNESS	Subjective evaluation of resistance to breakage:		
	1: Extremely hard	4: Moderately hard	7: Very soft
	2: Very hard	5: Moderately soft	8: Soil-like, cohesive
	3: Hard	6: Soft	9: Soil-like, non-cohesive

COLUMN INFORMATION (Page 4)

FEATURE TYPE	Following codes indicate origin of feature:	
	N: Natural—indicated by mineral coating or evidence of weathering, slickensides, lack of fit between sides.	
	I: Indeterminate—origin questionable, rotated so that coatings possibly removed.	
	C: Coring induced—fresh, clean, tightly fitting breaks.	
	V: Vug or large void.	
INCLINATION (degrees)	Angle between plane normal to core axis and plane of fracture (Type N and I only).	
MINERAL INFILLING	Describes the infilling on fracture surfaces (Type N and I only):	
	C: Clean	TD: Brown dendritic
	WC: White crystalline	TC: Tan crystalline
	WN: White noncrystalline	CA: Calcite
	BC: Black crystalline	SI: Silica
	BD: Black dendritic	MN: Manganese
	CL: Clay	TN: Tan noncrystalline
INFILL THICKNESS	Describes the thickness of mineral infillings on the fracture surface (Type N and I only):	
	S: Very thin, surface sheen	V: Very thick (0.4 - 1.0 inches)
	T: Thin (up to 0.1 inches)	E: Extremely thick, greater than 1.0 inches
	M: Moderately thick (0.1-0.4 inches)	
PLANARITY	Describes the overall shape of the feature (Type N and I only):	
	P: Planar	S: Stepped
	C: Curved	I: Irregular
ROUGHNESS	Describes the local relief of the surface (Type N and I only):	
	V: Very rough—stepped, near-normal steps and ridges occur.	
	R: Rough—large angular asperities can be seen.	
	M: Moderately rough—asperities clearly visible, surface has abrasive feel.	
	S: Smooth—no asperities, smooth to the touch.	
	P: Polished—slickensided, extremely smooth and shiny.	

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Core Hole Structural Data Summary

Hole USW UZ-14

Interval — 700-850 ft, Middle Nonlithophysal Zone

NO. OF FRACTURES/WAINDRILL INFILLING TYPE													NO. OF FRACTURES/WAINDRILL THICKNESS					NO. OF FRACTURES/WAINDRILL ANNUITY CODE					NO. OF FRACTURES/WAINDRILL ANNUITY CODE				
C	WC	WN	BC	BD	TD	TC	CA	SI	NI	CI	TI	FE	BN	S	T	M	V	E	P	C	S	I	V	R	M	S	P
1	4	4					1	2						3	5				9	1		2		1	4	1	
2		4						7						3	5	1			11	1		7		1	3	5	
3							2		1					1	2				5			1		4	2		
4	9	5					1	3						3	17	2			11	3		19		4	18	5	
5		3				10		4						4	11				18	1		3		9	2	4	
6		1					2		7	1				7	1				8	1				5	1	3	
7														1	2				3	4		2		2	5	1	
8	2	1					8							5	6				7	5	1		5	6	3		
9																											
10							1							1					1	1	2		3	1			
11																											
12	5						3							5	3	2			5			3		5	2		
13	3													2	2	1			2	1		1		1	2		
14							1								1							1		1			
15																			3			2		1	4		
16																			1	2		3		5		1	
17	19	19	0	0	0	0	30	10	16	1	0	0	0	35	59	5	0	0	25	22	3	44	0	17	75	26	5
18	83	83	0	0	0	0	13	44	7	04	0	0	0	35	58	50	0	0	55	14	10	29	0	14	50	20	54

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Core Hole Structural Data Summary

Hole USW UZ-14

Interval — 700-850 ft, Middle Nonlithophysal Zone

BASE OF 10-FT INTERVAL	STRATI- GRAPHY ZONE	THERMO- MECHANICAL UNIT	CORE ROD**	ENHANCED ROD**	ESTIMATED % CAVITIES	LOST CORE (ft)	SUBSILE ZONE (ft)	WEATHERING (0 to 10-ft interval)***					HARDNESS (R in 10-ft interval)***							
								F	S	M	I	D	ROCK							
													1	2	3	4	5	6	7	8
710	T.S. C.P. U. Lih.	Isa1	56	61	2	1.6	1.4		7.7				7.7							
720	T.S. C.P. U. Lih.	Isa1	10	47	1	1.0	0.7		10.0				10.0							
730	T.S. C.P. M. Nonlith	Isa2	16	26	<1	1.7	4.9		10.0				2.0	8.0						
740	T.S. C.P. M. Nonlith	Isa2	16	29	<1	0.0	1.0		10.0				3.2	6.8						
750	T.S. C.P. M. Nonlith	Isa2	25	40	<1	0.3	0.6		10.0				10.0							
760	T.S. C.P. M. Nonlith	Isa2	6	21	<1	2.6	2.7		10.0				10.0							
770	T.S. C.P. M. Nonlith	Isa2	0	9	<1	2.2	1.2		10.0				2.1	7.9						
780	T.S. C.P. M. Nonlith	Isa2	26	61	2	1.6	0.6		10.0					6.6	3.6					
790	T.S. C.P. M. Nonlith	Isa2	40	61	2	1.4	1.5		10.0						10.0					
800	T.S. C.P. M. Nonlith	Isa2	65	93	2	0.4	0.3		10.0						10.0					
810	T.S. C.P. M. Nonlith	Isa2	32	86	<1	0.3	0.2		10.0						8.1	1.9				
820	T.S. C.P. M. Nonlith	Isa2	94	97	<1	0.0		7.9	2.1				7.9	2.1						
830	T.S. C.P. M. Nonlith	Isa2	82	98	<1	0.0	0.2	10.0					1.9		8.1					
840	T.S. C.P. L. Lih.	Isa2	64	71	1	0.9	0.8	10.0							10.0					
850	T.S. C.P. L. Lih.	Isa2	0	10	<1	3.7	1.9	10.0							10.0					

* CORE ROD—Determined from piece lengths formed by all types of fractures (C, I, N and V).

** ENHANCED ROD—Determined by filtering the effects of fractures identified as coring induced (Type C) from the piece lengths.

*** Footage in interval may not equal 10 ft because of lost core, subble, or omission during logging.

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
ESTIMATED ROCK MASS QUALITY INDICES
BASED ON CORE LOG DATA
Hole USW UZ-14, 700-850 ft, Middle Nonlithophysal Zone

Sandia National Laboratories
Print Date: 7/3/95
WBS 1.2.3.2.6.2
QA.1
Revision 0

EXPLANATION OF CALCULATION

Rock mass quality indices, Q (Barton et al., 1974) and RMR (Bieniawski, 1979), have been estimated for 10-ft intervals using Rock Structural Data Summaries developed from structural logging of the core, observations of rock conditions in the North Ramp Starter Tunnel and North Ramp tunnel, and laboratory testing data.

Q is developed to evaluate the distribution of rock mass quality as a basis for developing the range of credible rock mass quality to establish the ground support requirements within rock units and to derive rock mass mechanical properties according to the methodology proposed by Hardy and Bauer (1991). Procedures used in the calculation were:

$$Q = \frac{RQD^{**}}{J_n^{**}} \cdot \frac{J_r}{J_a} \cdot \frac{J_w}{SRF^{*}}$$

Note: Any spatial correlation may be masked by Monte Carlo simulation of J_n and SRF.

where RQD^{**} = Core RQD where all fractures types [natural (N), indeterminate (I), coring induced (C) and vugs (V)] have been considered in determination of RQD. If the RQD is less than 10%, the value used is set to 10 as per Barton et al. (1974). By definition, soil-like materials are considered to have zero RQD.

J_n^{*} = Joint Set Numbers: Cannot be determined from the core log data and are generated by Monte-Carlo simulation assuming a uniform distribution of values between 1 and 12 derived from mapping of the North Ramp tunnel.

J_r = Joint Roughness Number: A weighted average value derived based on the N and I type fractures in the 10-ft interval.

J_a = Joint Alteration Number: A weighted average value derived from the description of N and I type fractures in the interval.

J_w = Joint Water Factor: Set equal to 1.0 assuming dry conditions.

SRF^{*} = Stress Reduction Factor: For nonwelded units, SRF is determined from the ratio of UCS/σ_1 (UCS = unconfined compressive strength, σ_1 = overburden stress). If unconfined compressive strength data is not available for the 10-ft interval, a compressive strength is generated by Monte Carlo simulation using laboratory

Agapito Associates, Inc.

test data for the thermomechanical units. For welded tuff units, SRF cannot be determined from core log data and is generated by Monte Carlo simulation assuming a distribution derived from mapping of the North Ramp tunnel.

- The use of the Core RQD is conservative since it includes the effect of coring induced breaks. Filtering the effects of coring induced breaks from the RQD calculation ("Enhanced RQD") produced an increase in the mean RQD. The mean values for thermomechanical units in USW UZ-14, 700-850 ft, Middle Nonlithophysal Zone are:

	<u>Core RQD</u>	<u>Enhanced RQD</u>
Middle Nonlithophysal Zone	33.6%	55.2%

- RMR is estimated based on the Rock Structural Summary log data, and rock strength data. Procedures used in the calculation were:

$$RMR = C + RQD-I + JS + JC + JW$$

where C = Rock Strength Index: Derived from compressive strength estimated by unconfined compressive strength laboratory test data for the 10-ft interval. If data is not available for the 10-ft interval, a compressive strength is generated by Monte-Carlo simulation using laboratory test data for the thermomechanical unit.

RQD-I = RQD Index: Derived using the Core RQD value for the 10-ft interval.

JS = Joint Spacing Index: Derived from the rock structural data for the 10-ft interval, excludes coring induced features.

JC = Discontinuity Condition Index: Derived from the description of fractures in the 10-ft interval.

JW = Groundwater Index: Assumed dry conditions

- Q and RMR data are presented in log format to associate parameters with depth intervals in the core log; however, any spatial correlation may be masked by Monte-Carlo simulation.

STRATIGRAPHIC ABBREVIATIONS

T.C.	Tiva Canyon Tuff	C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone
	Bedded Tuff		
Y.M.	Yucca Mountain Tuff		
	Bedded Tuff		
P.C.	Pah Canyon Tuff		
	Bedded Tuff		
T.S.	Topopah Spring Tuff	C.R. Vitric	Crystal-Rich Vitric Zone
		C.R. Nonlith.	Crystal-Rich Nonlithophysal Zone
		C.R. Lith.	Crystal-Rich Lithophysal Zone
		C.P. U. Lith.	Crystal-Poor Upper Lithophysal Zone
		C.P. M. Nonlith.	Crystal-Poor Middle Nonlithophysal Zone
		C.P. L. Lith.	Crystal-Poor Lower Lithophysal Zone
		C.P. L. Nonlith.	Crystal-Poor Lower Nonlithophysal Zone
		C.P. Vitric	Crystal-Poor Vitric Zone Vitrophyre
		C.P. Vitric NW	Crystal-Poor Vitric Zone Non- to Partially Welded and Moderately Welded
	Bedded Tuff		
C.H.	Calico Hills Formation		

THERMOMECHANICAL UNITS

UO—Undifferentiated Overburden
 TCw—Tiva Canyon Welded Unit
 PTn—Upper Paintbrush Nonwelded Unit
 TSw1—Topopah Spring Welded Unit—Lithophysae Rich
 TSw2—Topopah Spring Welded Unit—Lithophysae Poor
 TSw3—Topopah Spring Welded Unit—Vitrophyre
 CHn1—Calico Hills and Lower Paintbrush Nonwelded Unit

YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT

Estimated Rock Mass Quality Indices Based on Core Log Data

Hole USW UZ-14

Interval — 700–850 ft, Middle Nonlithophysal Zone

END DEPTH	STRATIGRAPHY ZONE	THERMO- MECHANICAL UNIT	Q CLASSIFICATION SYSTEM ¹ Barton et al. (1974)							RMR CLASSIFICATION SYSTEM ² Bieniawski (1979)					
			RQD** (%)	J _n *	J _r	J _a	J _w	SRF*	Q*	C	RQD-I	JS	JC	JW	RMR
710	T.S. C.P. U. Lith.	TSw1	36	6.00	2.17	1.62	1.00	5.00	1.61	12	8	8	18.0	15	61.0
720	T.S. C.P. U. Lith.	TSw1	10	9.00	2.10	1.62	1.00	5.00	0.29	7	3	8	18.9	15	51.9
730	T.S. C.P. M. Nonlith.	TSw2	15	9.00	1.83	1.00	1.00	5.00	0.61	12	3	5	20.1	15	55.1
740	T.S. C.P. M. Nonlith.	TSw2	16	12.00	2.46	1.44	1.00	7.60	0.29	12	3	5	22.8	15	67.8
750	T.S. C.P. M. Nonlith.	TSw2	29	9.00	1.67	1.22	1.00	7.50	0.59	7	8	8	18.6	15	56.6
760	T.S. C.P. M. Nonlith.	TSw2	6	3.00	1.50	1.18	1.00	1.00	4.23	12	3	5	17.4	15	52.4
770	T.S. C.P. M. Nonlith.	TSw2	0	2.00	2.11	1.00	1.00	1.00	10.56	12	3	8	23.3	15	61.3
780	T.S. C.P. M. Nonlith.	TSw2	26	9.00	1.86	1.13	1.00	5.00	0.95	7	8	8	21.2	15	59.2
790	T.S. C.P. M. Nonlith.	TSw2	40	3.00	2.50	1.00	1.00	1.00	33.33	7	8	8	25.1	15	63.1
800	T.S. C.P. M. Nonlith.	TSw2	65	9.00	2.00	1.00	1.00	5.00	2.89	7	13	8	21.8	15	64.8
810	T.S. C.P. M. Nonlith.	TSw2	32	9.00	2.14	1.91	1.00	5.00	0.80	4	8	8	20.2	15	55.2
820	T.S. C.P. M. Nonlith.	TSw2	94	6.00	1.67	1.71	1.00	5.00	3.05	12	20	10	19.7	15	76.7
830	T.S. C.P. M. Nonlith.	TSw2	82	9.00	3.00	1.00	1.00	7.50	3.64	7	17	8	28.5	15	75.5
840	T.S. C.P. L. Lith.	TSw2	54	3.00	2.40	1.00	1.00	1.00	43.20	12	13	8	23.1	15	71.1
850	T.S. C.P. L. Lith.	TSw2	0	9.00	2.25	1.00	1.00	5.00	0.50	15	3	8	25.0	15	66.0

J_n*, SRF* = Interval values generated by Monte Carlo simulation; to calculate Q*.

RQD**: If RQD is less than 10, the value 10 is used in the calculation of Q* as per Barton et al. (1974).

¹ Barton, N., R. Lien, and J. Lund, "Engineering Classification of Rock Masses for the Design of Tunnel Support,"

Rock Mechanics, 6:189-236 (Springer Verlag, 1974).

² Bieniawski, Z.T., "The Geomechanics Classification in Rock Engineering Applications," Proceedings, 4th International

Congress on Rock Mechanics, Montreux, Switzerland, 2:41-48 (A. A. Balkema, 1979).

Q

J_n — Joint Set Number

J_r — Joint Roughness Number

J_a — Joint Alteration Number

J_w — Joint Water Reduction Factor

SRF — Stress Reduction Factor

$$Q = (RQD/J_n)(J_r/J_a)(J_w/SRF)$$

RMR

C — Strength Index

RQD-I — RQD Index

JS — Joint Spacing Index

JC — Discontinuity Condition Index

JW — Groundwater Index

$$RMR = C + RQD-I + JS + JC + JW$$

Appendix D

Key Block Analysis

Comparison of North Ramp and Main Drift Orientations

D.1 Introduction

Key block stability analyses have been conducted to compare potential key blocks based on joint structures mapped in the North Ramp to similar blocks created by Main Drift alignment. These analyses were designed to predict what rock mass conditions could be expected in the Main Drift assuming that the jointing conditions encountered so far in the North Ramp are also encountered in the Main Drift. Some changes in ground conditions can be expected if the assumed joint structure used in these analyses are consistent between both tunnel alignments.

D.2 Method of Analysis

The UNWEDGE²⁵ Version 2.2 key block stability analysis program was used to perform the comparative analyses. This program uses an ubiquitous, non-probabilistic approach to key block analysis which emphasizes the prediction of the formation of the maximum potential key block size given a particular joint set, tunnel orientation, and tunnel cross section. The UNWEDGE program is limited to a maximum of three joint sets in any particular analysis. UNWEDGE Version 2.2 has been verified in YMP document CSCI B0000000-01717-1200-30014 on February 2, 1995. The program and hardware used for this analysis was verified against the same problems.

Joint set data from tunnel mapping in the North Ramp were used to determine the mean joint set axes for the three joint sets. While the USBR has provided orientation data for five joint sets, only three of these sets have been used in this analysis. The USBR joint set No. 5 (as listed in Section 3.6) is a subhorizontal vapor-phase parting. Its sliding angle is very small compared to the other joint sets and observations in the North Ramp show that while this parting does act as a joint set at times, clearly visible breakage along this contact is observed only a small percentage of the time. Therefore, it has not been included in this analysis. The USBR joint set No. 4 is being assumed to be a subset of USBR joint set No. 1. This decision was based on the observation that it does not appear to coexist with joint set No. 1 frequently. The three joint set axes used in this analysis are summarized in Table D-1.

Table D-1. Joint Set Axes Used in Analysis

Joint Set Number	Dip (degrees)	Dip Direction
1	84	353
2	82	132
3	78	262

²⁵Carvalho et al.

Detailed mapping in the Tiva Canyon unit of the North Ramp has shown these to be the axes of the three primary joint sets. It is assumed for this analysis that these joint sets will also be encountered in the Topopah Spring unit of the Main Drift. The strength of this analysis rests upon the validity of this assumption.

Two sets of data were run in which the orientation of the 7.62-m-diameter circular tunnel has been varied. The first data set employs an orientation of 1° of dip on azimuth 299°; the second set employs 1° of dip on azimuth 3°. The results of a key block analysis on both data sets are compared in terms of the maximum potential key block volume, apex height, tonnage, and safety factor in Table D-2.

Table D-2. Comparison of North Ramp and Main Drift Results

Wedge No.	North Ramp Orientation				Main Drift Orientation			
	Volume (m ³)	Apex Height (m)	Tonnes	Safety Factor	Volume (m ³)	Apex Height (m)	Tonnes	Safety Factor
1	21.6807	7.8	59	0	58.7462	10.8	159	0
2	0.0007	0.3	<1	0.06	not formed			
3	0.0009	0.4	<1	0.55	0.0088	0.4	<1	0.55
4	21.6807	7.8	59	+inf	58.7462	10.8	159	+inf
5	0.0007	0.3	<1	0.53	not formed			
6	0.0009	0.4	<1	0.12	0.0088	0.4	<1	0.12

As shown by this comparison, the volume and tonnage of maximum potential key block formed in the crown increases roughly a factor of 3 in the Main Drift. This occurs in wedge No. 1 which increases from 59 to 159 tonnes. It is inferred from this information that under the assumptions noted above, the ground conditions in the Main Drift crown may have an increased potential of key block formation. It is difficult to state definitively the extent of this effect. With respect to roof bolt installation, the maximum potential block apex height increases from 7.8 to 10.8 m. However, both of these are beyond the bolt length (3-m bolts) currently being installed. The expected distribution of key block sizes can only be determined by a probabilistic key block analysis.

The effect on block formation in the tunnel walls is mixed. The North Ramp alignment allows the potential formation of four wedge types, whereas the Main Drift alignment allows only two. The block volume increases by a factor of 10 from 0.0009 to 0.009 m³. However, these block sizes are both negligible with respect to ground control. In both cases, the apex height is 0.4 m. These results can be seen in Table D-2 by inspection of wedge Nos. 2, 3, 5, and 6.

The assumption of similar joint orientations suggests worse roof conditions in the Main Drift. The effect of jointing on the ground conditions in the tunnel walls is minor.

This page intentionally left blank.

**YUCCA MOUNTAIN SITE CHARACTERIZATION PROJECT
SAND95-2183 DISTRIBUTION LIST**

1	D. A. Dreyfus (RW-1) Director OCRWM US Department of Energy 1000 Independence Avenue SW Washington, DC 20585	1	Director, Public Affairs Office c/o Technical Information Resource Center DOE Nevada Operations Office US Department of Energy P.O. Box 98518 Las Vegas, NV 89193-8518
1	L. H. Barrett (RW-2) Acting Deputy Director OCRWM US Department of Energy 1000 Independence Avenue SW Washington, DC 20585	8	Technical Information Officer DOE Nevada Operations Office US Department of Energy P.O. Box 98518 Las Vegas, NV 89193-8518
1	S. Russo (RW-40) Office of Storage and Transportation OCRWM US Department of Energy 1000 Independence Avenue SW Washington, DC 20585	1	J. R. Dyer, Deputy Project Manager Yucca Mountain Site Characterization Office US Department of Energy P.O. Box 30307 MS 523 Las Vegas, NV 89036-0307
1	R. A. Milner (RW-30) Office of Program Management and Integration OCRWM US Department of Energy 1000 Independence Avenue SW Washington, DC 20585	1	M. C. Brady Laboratory Lead for YMP M&O/Sandia National Laboratories 1180 Town Center Dr. Las Vegas, NV 89134
1	D. R. Elle, Director Environmental Protection Division DOE Nevada Field Office US Department of Energy P.O. Box 98518 Las Vegas, NV 89193-8518	1	J. A. Canepa Laboratory Lead for YMP EES-13, Mail Stop J521 M&O/Los Alamos National Laboratory P.O. Box 1663 Los Alamos, NM 87545
1	T. Wood (RW-14) Contract Management Division OCRWM US Department of Energy 1000 Independence Avenue SW Washington, DC 20585	1	Repository Licensing & Quality Assurance Project Directorate Division of Waste Management, MS T7J-9 US NRC Washington, DC 20555
4	Victoria F. Reich, Librarian Nuclear Waste Technical Review Board 1100 Wilson Blvd., Suite 910 Arlington, VA 22209	1	Senior Project Manager for Yucca Mountain Repository Project Branch Division of Waste Management, MS T7J-9 US NRC Washington, DC 20555
1	Wesley Barnes, Project Manager Yucca Mountain Site Characterization Office US Department of Energy P.O. Box 30307 MS 523 Las Vegas, NV 89036-0307	1	NRC Document Control Desk Division of Waste Management, MS T7J-9 US NRC Washington, DC 20555

1	Chad Glenn NRC Site Representative 301 E Stewart Avenue, Room 203 Las Vegas, NV 89101	1	B. T. Brady Records Specialist US Geological Survey MS 421 P.O. Box 25046 Denver, CO 80225
1	Center for Nuclear Waste Regulatory Analyses Southwest Research Institute 6220 Culebra Road Drawer 28510 San Antonio, TX 78284	1	M. D. Voegelé Deputy of Technical Operations M&O/SAIC 1180 Town Center Dr. Las Vegas, NV 89134
2	W. L. Clarke Laboratory Lead for YMP M&O/ Lawrence Livermore Nat'l Lab P.O. Box 808 (L-51) Livermore, CA 94550	2	A. T. Tamura Science and Technology Division OSTI US Department of Energy P.O. Box 62 Oak Ridge, TN 37831
1	Robert W. Craig Technical Project Officer US Geological Survey 1180 Town Center Dr. Las Vegas, NV 89134	1	P. J. Weeden, Acting Director Nuclear Radiation Assessment Div. US EPA Environmental Monitoring Sys. Lab P.O. Box 93478 Las Vegas, NV 89193-3478
1	J. S. Stuckless, Senior Science Advisor MS 425 Yucca Mountain Project Branch US Geological Survey P.O. Box 25046 Denver, CO 80225	1	John Fordham, Deputy Director Water Resources Center Desert Research Institute P.O. Box 60220 Reno, NV 89506
1	L. D. Foust, Asst. General Mgr. Nevada Site TRW Environmental Safety Systems 1180 Town Center Dr. Las Vegas, NV 89134	1	The Honorable Jim Regan Chairman Churchill County Board of Commissioners 10 W. Williams Avenue Fallon, NV 89406
1	A. L. Flint U. S. Geological Survey 1180 Town Center Dr. Las Vegas, NV 89134	1	R. R. Loux Executive Director Agency for Nuclear Projects State of Nevada Evergreen Center, Suite 252 1802 N. Carson Street Carson City, NV 89710
1	Robert L. Strickler Vice President & General Manager TRW Environmental Safety Systems, Inc. 2650 Park Tower Dr. Vienna, VA 22180	1	Brad R. Mettam Inyo County Yucca Mountain Repository Assessment Office P. O. Drawer L Independence, CA 93526
1	Jim Krulik, Technical Program Officer US Bureau of Reclamation Code D-8322 P.O. Box 25007 Denver, CO 80225-0007	1	Vernon E. Poe Office of Nuclear Projects Mineral County P.O. Box 1600 Hawthorne, NV 89415

1	Les W. Bradshaw Program Manager Nye County Nuclear Waste Repository Project Office P.O. Box 1767 Tonopah, NV 89049	1	Library Acquisitions Argonne National Laboratory Building 203, Room CE-111 9700 S. Cass Avenue Argonne, IL 60439
1	Florindo Mariani White Pine County Coordinator P. O. Box 135 Ely, NV 89301	1	Glen Van Roekel Manager, City of Caliente P.O. Box 158 Caliente, NV 89008
1	Tammy Manzini Lander County Yucca Mountain Information Officer P.O. Box 10 Austin, NV 89310	1	G. S. Bodvarsson Head, Nuclear Waste Department Lawrence Berkeley National Laboratory 1 Cyclotron Road, MS 50E Berkeley, CA 94720
1	Jason Pitts Lincoln County Nuclear Waste Program Manager P. O. Box 158 Pioche, NV 89043	1	Steve Hanauer (RW-2) OCRWM U. S. Department of Energy 1000 Independence Ave. Washington, DC 20585
1	Dennis Bechtel, Coordinator Nuclear Waste Division Clark County Dept. of Comprehensive Planning P.O. Box 55171 Las Vegas, NV 89155-1751	1	Susan B. Jones U.S. Department of Energy Yucca Mountain Site Characterization Office P.O. Box 30307 Las Vegas, NV 89036-0307
1	Juanita D. Hoffman Nuclear Waste Repository Oversight Program Esmeralda County P.O. Box 490 Goldfield, NV 89013	1	Stephan J. Broccom U.S. Department of Energy, Yucca Mountain Site Characterization Office P.O. Box 30307 Las Vegas, NV 89036-0307
1	Sandy Green Yucca Mountain Information Office Eureka County P.O. Box 714 Eureka, NV 89316	1	Dennis R. Williams U.S. Department of Energy, Yucca Mountain Site Characterization Office P.O. Box 30307 Las Vegas, NV 89036-0307
1	Economic Development Dept. City of Las Vegas 400 E. Stewart Avenue Las Vegas, NV 89101	1	Richard L. Craun U.S. Department of Energy Yucca Mountain Site Characterization Office P.O. Box 30307 Las Vegas, NV 89036-0307
1	Community Planning & Development City of North Las Vegas P.O. Box 4086 North Las Vegas, NV 89030	5	Dwayne Kicker M&O/ MK CRWMS M&O 1180 Town Center Drive MS423/618E Las Vegas, NV 89134
2	Librarian YMP Research & Study Center 1180 Town Center Drive Las Vegas, NV 89134		

1	John Pye, M&O/ MK CRWMS M&O 1180 Town Center Drive MS423/618E Las Vegas, NV 89134		MS
		2	1330 K. Hart, 6811 100/1.2.3.2.6.2.1/SAND952183/QA
1	Rick Nolting M&O/MK CRWMS M&O 1180 Town Center Drive MS423/618E Las Vegas, NV 89134	10 1 5 2	1330 WMT Library, 6752 9018 Central Technical Files, 8940-2 0899 Technical Library, 4415 0619 Review and Approval Desk, 12690, For DOE/OSTI
1	Dan McKenzie M&O/MK CRWMS M&O 1180 Town Center Drive MS423/618E Las Vegas, NV 89134		
1	David Kessel M&O/ SNL CRWMS M&O 1180 Town Center Drive MS423 Las Vegas, NV 89134		
1	William Boyle DOE/ YMSCO P.O. Box 30307 North Las Vegas, NV 89036-0307		
2	Carl Brochtel Agapito and Associates, Inc. 2620 Regatta Drive, Suite, 203 Las Vegas, NV 89128		
1	Robert W. Clayton M&O/ WCFS 1180 Town Center Drive MS423 Las Vegas, NV 89134		
1	Richard C. Quintmeyer M&O/ WCFS 1180 Town Center Drive MS423 Las Vegas, NV 89134		
1	Mark C. Tynan DOE/YMPSCO 1180 Town Center Drive MS523/HL Las Vegas, NV 89134		
1	Robin Datta M&OWCFS 1180 Town Center Drive MS423 Las Vegas, NV 89134		